

Technical Data Sheet



ASSEMBLY MATERIALS

Product Type: Flux

Product Name: NC5070

Description

No clean tacky flux for bumping, BGA, CSP, surface mount and hybrid applications.

Key Benefits

- Suitable for lead free and lead containing bumps
- Excellent wetting behaviour
- Perfect cleaning properties

Compliant Products

- TF 38
- SF 64

Applications

- Printing
- Dispensing

Flux Activity

Activity Level (J-STD 004)	Classification
ROLO	No Clean/ Solvent Clean

Halogen Content

Halogen-Zero (No halogen added in the flux)
Tolerances: Halogen < 50 ppm; measured according to BS EN 14582

Cleaning Instructions

Flux residues may remain on the circuit and do not need to be washed. For cleaning of flux residues, Zestron and Vigon cleaners can be used – see separate cleaning recommendations.

Storage

- Store the flux in tightly-sealed cartridges and avoid exposure to sunlight and high humidity
- Max expiration date: please refer to the expiry date on the label of the packaged product
- Storage condition in the refrigerator at 2 – 10 °C
- Store cartridges with tip pointing downwards

Flux Conditioning

- The flux is used as supplied and the fresh flux is applied to the board directly from a cartridge

Heraeus Electronics
Heraeus Deutschland GmbH & Co. KG
Heraeusstraße 12 – 14
63450 Hanau, Germany
www.heraeus-electronics.com

Americas
Phone +1 610 825 6050
electronics.americas@heraeus.com

China
Phone +86 21 3357 5457
electronics.china@heraeus.com

Asia Pacific
Phone +65 6571 7677
electronics.apac@heraeus.com

Europe, Middle East and Africa
Phone +49 6181 35 3069, +49 6181 35 3627
electronics.emea@heraeus.com

The descriptions and engineering data shown here have been compiled by Heraeus using commonly-accepted procedures, in conjunction with modern testing equipment, and have been compiled as according to the latest factual knowledge in our possession. The information was up-to date on the date this document was printed (latest versions can always be supplied upon request). Although the data is considered accurate, we cannot guarantee accuracy, the results obtained from its use, or any patent infringement resulting from its use (unless this is contractually and explicitly agreed in writing, in advance). The data is supplied on the condition that the user shall conduct tests to determine materials suitability for particular application.