

Patch cable - SPE-T1-CCP-SF/3,0/AWG22/CCP-SF - 1183810

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Patch cable, type: IEC 63171-2, degree of protection: IP20, cable length: 3 m, number of positions: 2, 1 Gbps, connection method: Crimp connection, connection cross section: AWG 22- 22, Single Pair Ethernet

Your advantages

- ✓ Compact design
- ✓ Connectors in accordance with IEC 63171-2
- ✓ Mechanical interlock with locking clip
- ✓ Robust industrial design
- ✓ 360° shielding
- ✓ Data transmission up to 600 MHz



Key Commercial Data

Packing unit	1
GTIN	 4 063151 221348
GTIN	4063151221348
Custom tariff number	85444290

Technical data

Dimensions

Length of cable	3.00 m
Width	7.53 mm
Height	14 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

General data

Patch cable - SPE-T1-CCP-SF/3,0/AWG22/CCP-SF - 1183810

Technical data

General data

Number of positions	2
Overvoltage category	I
Degree of pollution	2
Locking type	Locking clip
Rated voltage (III/2)	72 V DC
Connection method	Crimp connection
Insertion/withdrawal cycles	≥ 750
Contact material	Cu alloy
Contact carrier material	LCP
Contact surface material	Au
Number of slots	2
Rated current	4 A
Number of positions	2
Connection cross section AWG	22 ... 22
Transmission speed	1 Gbps ()
	100 Mbps ()
	10 Mbps ()

Cable

Cable type	PVC black
Cable structure	1x2xAWG22/7
Conductor cross section	0.33 mm ²
Core diameter including insulation	1.65 mm ±0.1 mm
Wire colors	blue, white
Shielding	Plastic-coated aluminum foil, tinned copper braided shield
External cable diameter D	5.1 mm ±0.20 mm
Outer sheath, material	PVC
Material conductor insulation	PE
Insulation resistance	min. 5 GΩ*km
Conductor resistance	59.4 Ω/km (20 °C)
Test voltage, cable	300 V (AWM style 2095)
Test voltage Core/Core	1000 V DC
Test voltage Core/Shield	2250 V DC
Other resistance	UV resistant
Flame resistance	UL 94 V0
Halogen-free	yes
Resistance to oil	yes

Standards and Regulations

Flame resistance	UL 94 V0
Resistance to oil	yes
Halogen-free	yes

Patch cable - SPE-T1-CCP-SF/3,0/AWG22/CCP-SF - 1183810

Technical data

Standards and Regulations

Other resistance	UV resistant
Flammability rating according to UL 94	V0
Standards/regulations	IEC 63171
	IEC 63171-2
	IEEE 802.3bu
	IEEE 802.3cg
	IEEE 802.3bw
	IEEE 802.3bp

Classifications

eCl@ss

eCl@ss 10.0.1	27440390
eCl@ss 11.0	27440392
eCl@ss 9.0	27440390

Accessories

Accessories

Female insert

SPE PCB connector - SPE-T1-STRM-90 - 1163797



SPE PCB connector, type: IEC 63171-2, degree of protection: IP20, number of positions: 2, CAT B (ISO/IEC 63171), connection method: THR solder connection, Single Pair Ethernet

SPE PCB connector - SPE-T1-STSM-180 - 1163798



SPE PCB connector, type: IEC 63171-2, degree of protection: IP20, number of positions: 2, CAT B (ISO/IEC 63171), connection method: THR solder connection, Single Pair Ethernet