

# **MySQL 8.0 Error Message Reference**

---

## Abstract

This is the MySQL 8.0 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 8.0. This document accompanies [Error Messages and Common Problems](#), in [MySQL 8.0 Reference Manual](#).

For help with using MySQL, please visit the [MySQL Forums](#), where you can discuss your issues with other MySQL users.

Document generated on: 2025-01-23 (revision: 80769)

---

---

## Table of Contents

Preface and Legal Notices .....	v
1 MySQL Error Reference .....	1
2 Server Error Message Reference .....	3
3 Client Error Message Reference .....	643
4 Global Error Message Reference .....	651
Index .....	661



---

# Preface and Legal Notices

This is the MySQL 8.0 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 8.0.

## Legal Notices

Copyright © 1997, 2025, Oracle and/or its affiliates.

### License Restrictions

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

### Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

### Restricted Rights Notice

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

### Hazardous Applications Notice

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

### Trademark Notice

Oracle, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

### **Third-Party Content, Products, and Services Disclaimer**

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

### **Use of This Documentation**

This documentation is NOT distributed under a GPL license. Use of this documentation is subject to the following terms:

You may create a printed copy of this documentation solely for your own personal use. Conversion to other formats is allowed as long as the actual content is not altered or edited in any way. You shall not publish or distribute this documentation in any form or on any media, except if you distribute the documentation in a manner similar to how Oracle disseminates it (that is, electronically for download on a Web site with the software) or on a CD-ROM or similar medium, provided however that the documentation is disseminated together with the software on the same medium. Any other use, such as any dissemination of printed copies or use of this documentation, in whole or in part, in another publication, requires the prior written consent from an authorized representative of Oracle. Oracle and/or its affiliates reserve any and all rights to this documentation not expressly granted above.

## **Documentation Accessibility**

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

## **Access to Oracle Support for Accessibility**

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

---

# Chapter 1 MySQL Error Reference

This document provides a reference for the various types of error messages in MySQL:

- Error messages produced only by the server: [Chapter 2, \*Server Error Message Reference\*](#)

On the server side, error messages may occur during the startup and shutdown processes, as a result of issues that occur during SQL statement execution, and so forth.

- The MySQL server writes some error messages to its error log. These indicate issues of interest to database administrators or that require DBA action.
- The server sends other error messages to client programs. These indicate issues pertaining only to a particular client. The MySQL client library takes errors received from the server and makes them available to the host client program.
- Error messages that originate only from within the MySQL client library: [Chapter 3, \*Client Error Message Reference\*](#)

Client-side error messages are generated from within the MySQL client library, usually involving problems communicating with the server.

- Error messages that are shared between the server and the client library: [Chapter 4, \*Global Error Message Reference\*](#)

Some “global” error messages are shared in the sense that they can be produced by the MySQL server or by MySQL client programs.

For a description of the types of error information MySQL provides and how to obtain information about them, see [Error Messages and Common Problems](#), in [MySQL 8.0 Reference Manual](#).





---

## Chapter 2 Server Error Message Reference

The MySQL server writes some error messages to its error log, and sends others to client programs.

Example server-side error messages written to the error log:

```
2018-10-28T13:01:32.735983Z 0 [Note] [MY-010303] [Server] Skipping
generation of SSL certificates as options related to SSL are specified.

2018-10-02T03:20:39.410387Z 768 [ERROR] [MY-010045] [Server] Event Scheduler:
[evtuser@localhost][myschema.e_daily] Unknown database 'mydb'
```

Example server-side error message sent to client programs, as displayed by the `mysql` client:

```
mysql> SELECT * FROM no_such_table;
ERROR 1146 (42S02): Table 'test.no_such_table' doesn't exist
```

Each server error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#).

In addition to the errors in the following list, the server can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: [1002](#); Symbol: [ER\\_NO](#); SQLSTATE: [HY000](#)

Message: NO

Used in the construction of other messages.

- Error number: [1003](#); Symbol: [ER\\_YES](#); SQLSTATE: [HY000](#)

Message: YES

Used in the construction of other messages.

Extended [EXPLAIN](#) format generates Note messages. [ER\\_YES](#) is used in the [Code](#) column for these messages in subsequent [SHOW WARNINGS](#) output.

- Error number: [1004](#); Symbol: [ER\\_CANT\\_CREATE\\_FILE](#); SQLSTATE: [HY000](#)

Message: Can't create file '%s' (errno: %d - %s)

Occurs for failure to create or copy a file needed for some operation.

Possible causes: Permissions problem for source file; destination file already exists but is not writeable.

- Error number: [1005](#); Symbol: [ER\\_CANT\\_CREATE\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Can't create table '%s' (errno: %d - %s)

[InnoDB](#) reports this error when a table cannot be created. If the error message refers to error 150, table creation failed because a [foreign key constraint](#) was not correctly formed. If the error message refers to error -1, table creation probably failed because the table includes a column name that matched the name of an internal [InnoDB](#) table.

- Error number: [1006](#); Symbol: [ER\\_CANT\\_CREATE\\_DB](#); SQLSTATE: [HY000](#)

Message: Can't create database '%s' (errno: %d - %s)

- 
- Error number: [1007](#); Symbol: [ER\\_DB\\_CREATE\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Can't create database '%s'; database exists  
An attempt to create a database failed because the database already exists.  
Drop the database first if you really want to replace an existing database, or add an [IF NOT EXISTS](#) clause to the [CREATE DATABASE](#) statement if to retain an existing database without having the statement produce an error.
  - Error number: [1008](#); Symbol: [ER\\_DB\\_DROP\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Can't drop database '%s'; database doesn't exist
  - Error number: [1010](#); Symbol: [ER\\_DB\\_DROP\\_RMDIR](#); SQLSTATE: [HY000](#)  
Message: Error dropping database (can't rmdir '%s', errno: %d - %s)
  - Error number: [1012](#); Symbol: [ER\\_CANT\\_FIND\\_SYSTEM\\_REC](#); SQLSTATE: [HY000](#)  
Message: Can't read record in system table  
Returned by [InnoDB](#) for attempts to access [InnoDB INFORMATION\\_SCHEMA](#) tables when [InnoDB](#) is unavailable.
  - Error number: [1013](#); Symbol: [ER\\_CANT\\_GET\\_STAT](#); SQLSTATE: [HY000](#)  
Message: Can't get status of '%s' (errno: %d - %s)
  - Error number: [1015](#); Symbol: [ER\\_CANT\\_LOCK](#); SQLSTATE: [HY000](#)  
Message: Can't lock file (errno: %d - %s)
  - Error number: [1016](#); Symbol: [ER\\_CANT\\_OPEN\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Can't open file: '%s' (errno: %d - %s)  
[InnoDB](#) reports this error when the table from the [InnoDB data files](#) cannot be found.
  - Error number: [1017](#); Symbol: [ER\\_FILE\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: Can't find file: '%s' (errno: %d - %s)
  - Error number: [1018](#); Symbol: [ER\\_CANT\\_READ\\_DIR](#); SQLSTATE: [HY000](#)  
Message: Can't read dir of '%s' (errno: %d - %s)
  - Error number: [1020](#); Symbol: [ER\\_CHECKREAD](#); SQLSTATE: [HY000](#)  
Message: Record has changed since last read in table '%s'
  - Error number: [1022](#); Symbol: [ER\\_DUP\\_KEY](#); SQLSTATE: [23000](#)  
Message: Can't write; duplicate key in table '%s'
  - Error number: [1024](#); Symbol: [ER\\_ERROR\\_ON\\_READ](#); SQLSTATE: [HY000](#)  
Message: Error reading file '%s' (errno: %d - %s)
  - Error number: [1025](#); Symbol: [ER\\_ERROR\\_ON\\_RENAME](#); SQLSTATE: [HY000](#)

---

Message: Error on rename of '%s' to '%s' (errno: %d - %s)

- Error number: 1026; Symbol: [ER\\_ERROR\\_ON\\_WRITE](#); SQLSTATE: HY000

Message: Error writing file '%s' (errno: %d - %s)

- Error number: 1027; Symbol: [ER\\_FILE\\_USED](#); SQLSTATE: HY000

Message: '%s' is locked against change

- Error number: 1028; Symbol: [ER\\_FILSORT\\_ABORT](#); SQLSTATE: HY000

Message: Sort aborted

[ER\\_FILSORT\\_ABORT](#) was removed after 8.0.18.

- Error number: 1030; Symbol: [ER\\_GET\\_ERRNO](#); SQLSTATE: HY000

Message: Got error %d - '%s' from storage engine

Check the %d value to see what the OS error means. For example, 28 indicates that you have run out of disk space.

- Error number: 1031; Symbol: [ER\\_ILLEGAL HA](#); SQLSTATE: HY000

Message: Table storage engine for '%s' doesn't have this option

- Error number: 1032; Symbol: [ER\\_KEY\\_NOT\\_FOUND](#); SQLSTATE: HY000

Message: Can't find record in '%s'

- Error number: 1033; Symbol: [ER\\_NOT FORM FILE](#); SQLSTATE: HY000

Message: Incorrect information in file: '%s'

- Error number: 1034; Symbol: [ER\\_NOT KEYFILE](#); SQLSTATE: HY000

Message: Incorrect key file for table '%s'; try to repair it

- Error number: 1035; Symbol: [ER\\_OLD KEYFILE](#); SQLSTATE: HY000

Message: Old key file for table '%s'; repair it!

- Error number: 1036; Symbol: [ER\\_OPEN AS READONLY](#); SQLSTATE: HY000

Message: Table '%s' is read only

- Error number: 1037; Symbol: [ER\\_OUTOFMEMORY](#); SQLSTATE: HY001

Message: Out of memory; restart server and try again (needed %d bytes)

- Error number: 1038; Symbol: [ER\\_OUT\\_OF\\_SORTMEMORY](#); SQLSTATE: HY001

Message: Out of sort memory, consider increasing server sort buffer size

- Error number: 1040; Symbol: [ER\\_CON\\_COUNT\\_ERROR](#); SQLSTATE: 08004

Message: Too many connections

- 
- Error number: 1041; Symbol: `ER_OUT_OF_RESOURCES`; SQLSTATE: `HY000`

Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space

- Error number: 1042; Symbol: `ER_BAD_HOST_ERROR`; SQLSTATE: `08S01`

Message: Can't get hostname for your address

- Error number: 1043; Symbol: `ER_HANDSHAKE_ERROR`; SQLSTATE: `08S01`

Message: Bad handshake

- Error number: 1044; Symbol: `ER_DBACCESS_DENIED_ERROR`; SQLSTATE: `42000`

Message: Access denied for user '%s'@'%s' to database '%s'

- Error number: 1045; Symbol: `ER_ACCESS_DENIED_ERROR`; SQLSTATE: `28000`

Message: Access denied for user '%s'@'%s' (using password: %s)

- Error number: 1046; Symbol: `ER_NO_DB_ERROR`; SQLSTATE: `3D000`

Message: No database selected

- Error number: 1047; Symbol: `ER_UNKNOWN_COM_ERROR`; SQLSTATE: `08S01`

Message: Unknown command

- Error number: 1048; Symbol: `ER_BAD_NULL_ERROR`; SQLSTATE: `23000`

Message: Column '%s' cannot be null

- Error number: 1049; Symbol: `ER_BAD_DB_ERROR`; SQLSTATE: `42000`

Message: Unknown database '%s'

- Error number: 1050; Symbol: `ER_TABLE_EXISTS_ERROR`; SQLSTATE: `42S01`

Message: Table '%s' already exists

- Error number: 1051; Symbol: `ER_BAD_TABLE_ERROR`; SQLSTATE: `42S02`

Message: Unknown table '%s'

- Error number: 1052; Symbol: `ER_NON_UNIQ_ERROR`; SQLSTATE: `23000`

Message: Column '%s' in %s is ambiguous

```
%s = column name
%s = location of column (for example, "field list")
```

Likely cause: A column appears in a query without appropriate qualification, such as in a select list or ON clause.

Examples:

```
mysql> SELECT i FROM t INNER JOIN t AS t2;
ERROR 1052 (23000): Column 'i' in field list is ambiguous

mysql> SELECT * FROM t LEFT JOIN t AS t2 ON i = i;
```

---

```
ERROR 1052 (23000): Column 'i' in on clause is ambiguous
```

Resolution:

- Qualify the column with the appropriate table name:

```
mysql> SELECT t2.i FROM t INNER JOIN t AS t2;
```

- Modify the query to avoid the need for qualification:

```
mysql> SELECT * FROM t LEFT JOIN t AS t2 USING (i);
```

- Error number: [1053](#); Symbol: [ER\\_SERVER\\_SHUTDOWN](#); SQLSTATE: [08S01](#)  
Message: Server shutdown in progress
- Error number: [1054](#); Symbol: [ER\\_BAD\\_FIELD\\_ERROR](#); SQLSTATE: [42S22](#)  
Message: Unknown column '%s' in '%s'
- Error number: [1055](#); Symbol: [ER\\_WRONG\\_FIELD\\_WITH\\_GROUP](#); SQLSTATE: [42000](#)  
Message: '%s' isn't in GROUP BY
- Error number: [1056](#); Symbol: [ER\\_WRONG\\_GROUP\\_FIELD](#); SQLSTATE: [42000](#)  
Message: Can't group on '%s'
- Error number: [1057](#); Symbol: [ER\\_WRONG\\_SUM\\_SELECT](#); SQLSTATE: [42000](#)  
Message: Statement has sum functions and columns in same statement
- Error number: [1058](#); Symbol: [ER\\_WRONG\\_VALUE\\_COUNT](#); SQLSTATE: [21S01](#)  
Message: Column count doesn't match value count
- Error number: [1059](#); Symbol: [ER\\_TOO\\_LONG\\_IDENT](#); SQLSTATE: [42000](#)  
Message: Identifier name '%s' is too long
- Error number: [1060](#); Symbol: [ER\\_DUP\\_FIELDNAME](#); SQLSTATE: [42S21](#)  
Message: Duplicate column name '%s'
- Error number: [1061](#); Symbol: [ER\\_DUP\\_KEYNAME](#); SQLSTATE: [42000](#)  
Message: Duplicate key name '%s'
- Error number: [1062](#); Symbol: [ER\\_DUP\\_ENTRY](#); SQLSTATE: [23000](#)  
Message: Duplicate entry '%s' for key %d  
The message returned with this error uses the format string for [ER\\_DUP\\_ENTRY\\_WITH\\_KEY\\_NAME](#).
- Error number: [1063](#); Symbol: [ER\\_WRONG\\_FIELD\\_SPEC](#); SQLSTATE: [42000](#)  
Message: Incorrect column specifier for column '%s'
- Error number: [1064](#); Symbol: [ER\\_PARSE\\_ERROR](#); SQLSTATE: [42000](#)  
Message: %s near '%s' at line %d

- 
- Error number: [1065](#); Symbol: [ER\\_EMPTY\\_QUERY](#); SQLSTATE: [42000](#)  
Message: Query was empty
  - Error number: [1066](#); Symbol: [ER\\_NONUNIQ\\_TABLE](#); SQLSTATE: [42000](#)  
Message: Not unique table/alias: '%s'
  - Error number: [1067](#); Symbol: [ER\\_INVALID\\_DEFAULT](#); SQLSTATE: [42000](#)  
Message: Invalid default value for '%s'
  - Error number: [1068](#); Symbol: [ER\\_MULTIPLE\\_PRI\\_KEY](#); SQLSTATE: [42000](#)  
Message: Multiple primary key defined
  - Error number: [1069](#); Symbol: [ER\\_TOO\\_MANY\\_KEYS](#); SQLSTATE: [42000](#)  
Message: Too many keys specified; max %d keys allowed
  - Error number: [1070](#); Symbol: [ER\\_TOO\\_MANY\\_KEY\\_PARTS](#); SQLSTATE: [42000](#)  
Message: Too many key parts specified; max %d parts allowed
  - Error number: [1071](#); Symbol: [ER\\_TOO\\_LONG\\_KEY](#); SQLSTATE: [42000](#)  
Message: Specified key was too long; max key length is %d bytes
  - Error number: [1072](#); Symbol: [ER\\_KEY\\_COLUMN\\_DOES\\_NOT\\_EXISTS](#); SQLSTATE: [42000](#)  
Message: Key column '%s' doesn't exist in table
  - Error number: [1073](#); Symbol: [ER\\_BLOB\\_USED\\_AS\\_KEY](#); SQLSTATE: [42000](#)  
Message: BLOB column '%s' can't be used in key specification with the used table type
  - Error number: [1074](#); Symbol: [ER\\_TOO\\_BIG\\_FIELDLENGTH](#); SQLSTATE: [42000](#)  
Message: Column length too big for column '%s' (max = %lu); use BLOB or TEXT instead
  - Error number: [1075](#); Symbol: [ER\\_WRONG\\_AUTO\\_KEY](#); SQLSTATE: [42000](#)  
Message: Incorrect table definition; there can be only one auto column and it must be defined as a key
  - Error number: [1076](#); Symbol: [ER\\_READY](#); SQLSTATE: [HY000](#)  
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d
  - Error number: [1077](#); Symbol: [ER\\_NORMAL\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: %s: Normal shutdown  
[ER\\_NORMAL\\_SHUTDOWN](#) was removed after 8.0.4.
  - Error number: [1079](#); Symbol: [ER\\_SHUTDOWN\\_COMPLETE](#); SQLSTATE: [HY000](#)  
Message: %s: Shutdown complete
  - Error number: [1080](#); Symbol: [ER\\_FORCING\\_CLOSE](#); SQLSTATE: [08S01](#)  
Message: %s: Forcing close of thread %ld user: '%s'

- 
- Error number: [1081](#); Symbol: [ER\\_IPSOCK\\_ERROR](#); SQLSTATE: [08S01](#)  
Message: Can't create IP socket
  - Error number: [1082](#); Symbol: [ER\\_NO\\_SUCH\\_INDEX](#); SQLSTATE: [42S12](#)  
Message: Table '%s' has no index like the one used in CREATE INDEX; recreate the table
  - Error number: [1083](#); Symbol: [ER\\_WRONG\\_FIELD\\_TERMINATORS](#); SQLSTATE: [42000](#)  
Message: Field separator argument is not what is expected; check the manual
  - Error number: [1084](#); Symbol: [ER\\_BLOBS\\_AND\\_NO\\_TERMINATED](#); SQLSTATE: [42000](#)  
Message: You can't use fixed rowlength with BLOBs; please use 'fields terminated by'
  - Error number: [1085](#); Symbol: [ER\\_TEXTFILE\\_NOT\\_READABLE](#); SQLSTATE: [HY000](#)  
Message: The file '%s' must be in the database directory or be readable by all
  - Error number: [1086](#); Symbol: [ER\\_FILE\\_EXISTS\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: File '%s' already exists
  - Error number: [1087](#); Symbol: [ER\\_LOAD\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Records: %ld Deleted: %ld Skipped: %ld Warnings: %ld
  - Error number: [1088](#); Symbol: [ER\\_ALTER\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Records: %ld Duplicates: %ld
  - Error number: [1089](#); Symbol: [ER\\_WRONG\\_SUB\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Incorrect prefix key; the used key part isn't a string, the used length is longer than the key part, or the storage engine doesn't support unique prefix keys
  - Error number: [1090](#); Symbol: [ER\\_CANT\\_REMOVE\\_ALL\\_FIELDS](#); SQLSTATE: [42000](#)  
Message: You can't delete all columns with ALTER TABLE; use DROP TABLE instead
  - Error number: [1091](#); Symbol: [ER\\_CANT\\_DROP\\_FIELD\\_OR\\_KEY](#); SQLSTATE: [42000](#)  
Message: Can't DROP '%s'; check that column/key exists
  - Error number: [1092](#); Symbol: [ER\\_INSERT\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Records: %ld Duplicates: %ld Warnings: %ld
  - Error number: [1093](#); Symbol: [ER\\_UPDATE\\_TABLE\\_USED](#); SQLSTATE: [HY000](#)  
Message: You can't specify target table '%s' for update in FROM clause  
  
This error occurs for attempts to select from and modify the same table within a single statement. If the select attempt occurs within a derived table, you can avoid this error by setting the [derived\\_merge](#) flag of the [optimizer\\_switch](#) system variable to force the subquery to be materialized into a temporary table, which effectively causes it to be a different table from the one modified. See [Optimizing Derived Tables, View References, and Common Table Expressions with Merging or Materialization](#).
  - Error number: [1094](#); Symbol: [ER\\_NO\\_SUCH\\_THREAD](#); SQLSTATE: [HY000](#)
-

- 
- Message: Unknown thread id: %lu
- Error number: 1095; Symbol: [ER\\_KILL\\_DENIED\\_ERROR](#); SQLSTATE: HY000  
Message: You are not owner of thread %lu
  - Error number: 1096; Symbol: [ER\\_NO\\_TABLES\\_USED](#); SQLSTATE: HY000  
Message: No tables used
  - Error number: 1097; Symbol: [ER\\_TOO\\_BIG\\_SET](#); SQLSTATE: HY000  
Message: Too many strings for column %s and SET
  - Error number: 1098; Symbol: [ER\\_NO\\_UNIQUE\\_LOGFILE](#); SQLSTATE: HY000  
Message: Can't generate a unique log-filename %s.(1-999)
  - Error number: 1099; Symbol: [ER\\_TABLE\\_NOT\\_LOCKED\\_FOR\\_WRITE](#); SQLSTATE: HY000  
Message: Table '%s' was locked with a READ lock and can't be updated
  - Error number: 1100; Symbol: [ER\\_TABLE\\_NOT\\_LOCKED](#); SQLSTATE: HY000  
Message: Table '%s' was not locked with LOCK TABLES
  - Error number: 1101; Symbol: [ER\\_BLOB\\_CANT\\_HAVE\\_DEFAULT](#); SQLSTATE: 42000  
Message: BLOB, TEXT, GEOMETRY or JSON column '%s' can't have a default value
  - Error number: 1102; Symbol: [ER\\_WRONG\\_DB\\_NAME](#); SQLSTATE: 42000  
Message: Incorrect database name '%s'
  - Error number: 1103; Symbol: [ER\\_WRONG\\_TABLE\\_NAME](#); SQLSTATE: 42000  
Message: Incorrect table name '%s'
  - Error number: 1104; Symbol: [ER\\_TOO\\_BIG\\_SELECT](#); SQLSTATE: 42000  
Message: The SELECT would examine more than MAX\_JOIN\_SIZE rows; check your WHERE and use SET SQL\_BIG\_SELECTS=1 or SET MAX\_JOIN\_SIZE=# if the SELECT is okay
  - Error number: 1105; Symbol: [ER\\_UNKNOWN\\_ERROR](#); SQLSTATE: HY000  
Message: Unknown error
  - Error number: 1106; Symbol: [ER\\_UNKNOWN\\_PROCEDURE](#); SQLSTATE: 42000  
Message: Unknown procedure '%s'
  - Error number: 1107; Symbol: [ER\\_WRONG\\_PARAMCOUNT\\_TO\\_PROCEDURE](#); SQLSTATE: 42000  
Message: Incorrect parameter count to procedure '%s'
  - Error number: 1108; Symbol: [ER\\_WRONG\\_PARAMETERS\\_TO\\_PROCEDURE](#); SQLSTATE: HY000  
Message: Incorrect parameters to procedure '%s'
  - Error number: 1109; Symbol: [ER\\_UNKNOWN\\_TABLE](#); SQLSTATE: 42S02



---

Message: Unknown table '%s' in %s

- Error number: [1110](#); Symbol: [ER\\_FIELD\\_SPECIFIED\\_TWICE](#); SQLSTATE: [42000](#)

Message: Column '%s' specified twice

- Error number: [1111](#); Symbol: [ER\\_INVALID\\_GROUP\\_FUNC\\_USE](#); SQLSTATE: [HY000](#)

Message: Invalid use of group function

- Error number: [1112](#); Symbol: [ER\\_UNSUPPORTED\\_EXTENSION](#); SQLSTATE: [42000](#)

Message: Table '%s' uses an extension that doesn't exist in this MySQL version

- Error number: [1113](#); Symbol: [ER\\_TABLE\\_MUST\\_HAVE\\_COLUMNS](#); SQLSTATE: [42000](#)

Message: A table must have at least 1 column

- Error number: [1114](#); Symbol: [ER\\_RECORD\\_FILE\\_FULL](#); SQLSTATE: [HY000](#)

Message: The table '%s' is full

[InnoDB](#) reports this error when the system tablespace runs out of free space. Reconfigure the system tablespace to add a new data file.

- Error number: [1115](#); Symbol: [ER\\_UNKNOWN\\_CHARACTER\\_SET](#); SQLSTATE: [42000](#)

Message: Unknown character set: '%s'

- Error number: [1116](#); Symbol: [ER\\_TOO\\_MANY\\_TABLES](#); SQLSTATE: [HY000](#)

Message: Too many tables; MySQL can only use %d tables in a join

- Error number: [1117](#); Symbol: [ER\\_TOO\\_MANY\\_FIELDS](#); SQLSTATE: [HY000](#)

Message: Too many columns

- Error number: [1118](#); Symbol: [ER\\_TOO\\_BIG\\_ROWSIZE](#); SQLSTATE: [42000](#)

Message: Row size too large. The maximum row size for the used table type, not counting BLOBs, is %ld. This includes storage overhead, check the manual. You have to change some columns to TEXT or BLOBs

- Error number: [1119](#); Symbol: [ER\\_STACK\\_OVERRUN](#); SQLSTATE: [HY000](#)

Message: Thread stack overrun: Used: %ld of a %ld stack. Use 'mysqld --thread\_stack=#' to specify a bigger stack if needed

- Error number: [1120](#); Symbol: [ER\\_WRONG\\_OUTER\\_JOIN](#); SQLSTATE: [42000](#)

Message: Cross dependency found in OUTER JOIN; examine your ON conditions

[ER\\_WRONG\\_OUTER\\_JOIN](#) was removed after 8.0.0.

- Error number: [1120](#); Symbol: [ER\\_WRONG\\_OUTER\\_JOIN\\_UNUSED](#); SQLSTATE: [42000](#)

Message: Cross dependency found in OUTER JOIN; examine your ON conditions

[ER\\_WRONG\\_OUTER\\_JOIN\\_UNUSED](#) was added in 8.0.1.

- 
- Error number: [1121](#); Symbol: [ER\\_NULL\\_COLUMN\\_IN\\_INDEX](#); SQLSTATE: [42000](#)  
Message: Table handler doesn't support NULL in given index. Please change column '%s' to be NOT NULL or use another handler
  - Error number: [1122](#); Symbol: [ER\\_CANT\\_FIND\\_UDF](#); SQLSTATE: [HY000](#)  
Message: Can't load function '%s'
  - Error number: [1123](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_UDF](#); SQLSTATE: [HY000](#)  
Message: Can't initialize function '%s'; %s
  - Error number: [1124](#); Symbol: [ER\\_UDF\\_NO\\_PATHS](#); SQLSTATE: [HY000](#)  
Message: No paths allowed for shared library
  - Error number: [1125](#); Symbol: [ER\\_UDF\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Function '%s' already exists
  - Error number: [1126](#); Symbol: [ER\\_CANT\\_OPEN\\_LIBRARY](#); SQLSTATE: [HY000](#)  
Message: Can't open shared library '%s' (errno: %d %s)
  - Error number: [1127](#); Symbol: [ER\\_CANT\\_FIND\\_DL\\_ENTRY](#); SQLSTATE: [HY000](#)  
Message: Can't find symbol '%s' in library
  - Error number: [1128](#); Symbol: [ER\\_FUNCTION\\_NOT\\_DEFINED](#); SQLSTATE: [HY000](#)  
Message: Function '%s' is not defined
  - Error number: [1129](#); Symbol: [ER\\_HOST\\_IS\\_BLOCKED](#); SQLSTATE: [HY000](#)  
Message: Host '%s' is blocked because of many connection errors; unblock with 'mysqladmin flush-hosts'
  - Error number: [1130](#); Symbol: [ER\\_HOST\\_NOT\\_PRIVILEGED](#); SQLSTATE: [HY000](#)  
Message: Host '%s' is not allowed to connect to this MySQL server
  - Error number: [1131](#); Symbol: [ER\\_PASSWORD\\_ANONYMOUS\\_USER](#); SQLSTATE: [42000](#)  
Message: You are using MySQL as an anonymous user and anonymous users are not allowed to change passwords
  - Error number: [1132](#); Symbol: [ER\\_PASSWORD\\_NOT\\_ALLOWED](#); SQLSTATE: [42000](#)  
Message: You must have privileges to update tables in the mysql database to be able to change passwords for others
  - Error number: [1133](#); Symbol: [ER\\_PASSWORD\\_NO\\_MATCH](#); SQLSTATE: [42000](#)  
Message: Can't find any matching row in the user table
  - Error number: [1134](#); Symbol: [ER\\_UPDATE\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Rows matched: %ld Changed: %ld Warnings: %ld

- 
- Error number: [1135](#); Symbol: [ER\\_CANT\\_CREATE\\_THREAD](#); SQLSTATE: [HY000](#)  
Message: Can't create a new thread (errno %d); if you are not out of available memory, you can consult the manual for a possible OS-dependent bug
  - Error number: [1136](#); Symbol: [ER\\_WRONG\\_VALUE\\_COUNT\\_ON\\_ROW](#); SQLSTATE: [21S01](#)  
Message: Column count doesn't match value count at row %ld
  - Error number: [1137](#); Symbol: [ER\\_CANT\\_REOPEN\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Can't reopen table: '%s'
  - Error number: [1138](#); Symbol: [ER\\_INVALID\\_USE\\_OF\\_NULL](#); SQLSTATE: [22004](#)  
Message: Invalid use of NULL value
  - Error number: [1139](#); Symbol: [ER\\_REGEX\\_ERROR](#); SQLSTATE: [42000](#)  
Message: Got error '%s' from regexp
  - Error number: [1140](#); Symbol: [ER\\_MIX\\_OF\\_GROUP\\_FUNC\\_AND\\_FIELDS](#); SQLSTATE: [42000](#)  
Message: Mixing of GROUP columns (MIN(),MAX(),COUNT(),...) with no GROUP columns is illegal if there is no GROUP BY clause
  - Error number: [1141](#); Symbol: [ER\\_NONEXISTING\\_GRANT](#); SQLSTATE: [42000](#)  
Message: There is no such grant defined for user '%s' on host '%s'
  - Error number: [1142](#); Symbol: [ER\\_TABLEACCESS\\_DENIED\\_ERROR](#); SQLSTATE: [42000](#)  
Message: %s command denied to user '%s'@'%s' for table '%s'
  - Error number: [1143](#); Symbol: [ER\\_COLUMNACCESS\\_DENIED\\_ERROR](#); SQLSTATE: [42000](#)  
Message: %s command denied to user '%s'@'%s' for column '%s' in table '%s'
  - Error number: [1144](#); Symbol: [ER\\_ILLEGAL\\_GRANT\\_FOR\\_TABLE](#); SQLSTATE: [42000](#)  
Message: Illegal GRANT/REVOKE command; please consult the manual to see which privileges can be used
  - Error number: [1145](#); Symbol: [ER\\_GRANT\\_WRONG\\_HOST\\_OR\\_USER](#); SQLSTATE: [42000](#)  
Message: The host or user argument to GRANT is too long
  - Error number: [1146](#); Symbol: [ER\\_NO\\_SUCH\\_TABLE](#); SQLSTATE: [42S02](#)  
Message: Table '%s.%s' doesn't exist
  - Error number: [1147](#); Symbol: [ER\\_NONEXISTING\\_TABLE\\_GRANT](#); SQLSTATE: [42000](#)  
Message: There is no such grant defined for user '%s' on host '%s' on table '%s'
  - Error number: [1148](#); Symbol: [ER\\_NOT\\_ALLOWED\\_COMMAND](#); SQLSTATE: [42000](#)  
Message: The used command is not allowed with this MySQL version
  - Error number: [1149](#); Symbol: [ER\\_SYNTAX\\_ERROR](#); SQLSTATE: [42000](#)

---

Message: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use

- Error number: [1152](#); Symbol: [ER\\_ABORTING\\_CONNECTION](#); SQLSTATE: [08S01](#)

Message: Aborted connection %ld to db: '%s' user: '%s' (%s)

- Error number: [1153](#); Symbol: [ER\\_NET\\_PACKET\\_TOO\\_LARGE](#); SQLSTATE: [08S01](#)

Message: Got a packet bigger than 'max\_allowed\_packet' bytes

- Error number: [1154](#); Symbol: [ER\\_NET\\_READ\\_ERROR\\_FROM\\_PIPE](#); SQLSTATE: [08S01](#)

Message: Got a read error from the connection pipe

- Error number: [1155](#); Symbol: [ER\\_NET\\_FCNTL\\_ERROR](#); SQLSTATE: [08S01](#)

Message: Got an error from fcntl()

- Error number: [1156](#); Symbol: [ER\\_NET\\_PACKETS\\_OUT\\_OF\\_ORDER](#); SQLSTATE: [08S01](#)

Message: Got packets out of order

- Error number: [1157](#); Symbol: [ER\\_NET\\_UNCOMPRESS\\_ERROR](#); SQLSTATE: [08S01](#)

Message: Couldn't uncompress communication packet

- Error number: [1158](#); Symbol: [ER\\_NET\\_READ\\_ERROR](#); SQLSTATE: [08S01](#)

Message: Got an error reading communication packets

- Error number: [1159](#); Symbol: [ER\\_NET\\_READ\\_INTERRUPTED](#); SQLSTATE: [08S01](#)

Message: Got timeout reading communication packets

- Error number: [1160](#); Symbol: [ER\\_NET\\_ERROR\\_ON\\_WRITE](#); SQLSTATE: [08S01](#)

Message: Got an error writing communication packets

- Error number: [1161](#); Symbol: [ER\\_NET\\_WRITE\\_INTERRUPTED](#); SQLSTATE: [08S01](#)

Message: Got timeout writing communication packets

- Error number: [1162](#); Symbol: [ER\\_TOO\\_LONG\\_STRING](#); SQLSTATE: [42000](#)

Message: Result string is longer than 'max\_allowed\_packet' bytes

- Error number: [1163](#); Symbol: [ER\\_TABLE\\_CANT\\_HANDLE\\_BLOB](#); SQLSTATE: [42000](#)

Message: The used table type doesn't support BLOB/TEXT columns

- Error number: [1164](#); Symbol: [ER\\_TABLE\\_CANT\\_HANDLE\\_AUTO\\_INCREMENT](#); SQLSTATE: [42000](#)

Message: The used table type doesn't support AUTO\_INCREMENT columns

- Error number: [1166](#); Symbol: [ER\\_WRONG\\_COLUMN\\_NAME](#); SQLSTATE: [42000](#)

Message: Incorrect column name '%s'

- 
- Error number: [1167](#); Symbol: [ER\\_WRONG\\_KEY\\_COLUMN](#); SQLSTATE: [42000](#)  
Message: The used storage engine can't index column '%s'
  - Error number: [1168](#); Symbol: [ER\\_WRONG\\_MRG\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Unable to open underlying table which is differently defined or of non-MyISAM type or doesn't exist
  - Error number: [1169](#); Symbol: [ER\\_DUP\\_UNIQUE](#); SQLSTATE: [23000](#)  
Message: Can't write, because of unique constraint, to table '%s'
  - Error number: [1170](#); Symbol: [ER\\_BLOB\\_KEY\\_WITHOUT\\_LENGTH](#); SQLSTATE: [42000](#)  
Message: BLOB/TEXT column '%s' used in key specification without a key length
  - Error number: [1171](#); Symbol: [ER\\_PRIMARY\\_CANT\\_HAVE\\_NULL](#); SQLSTATE: [42000](#)  
Message: All parts of a PRIMARY KEY must be NOT NULL; if you need NULL in a key, use UNIQUE instead
  - Error number: [1172](#); Symbol: [ER\\_TOO\\_MANY\\_ROWS](#); SQLSTATE: [42000](#)  
Message: Result consisted of more than one row
  - Error number: [1173](#); Symbol: [ER\\_REQUIRES\\_PRIMARY\\_KEY](#); SQLSTATE: [42000](#)  
Message: This table type requires a primary key
  - Error number: [1175](#); Symbol: [ER\\_UPDATE\\_WITHOUT\\_KEY\\_IN\\_SAFE\\_MODE](#); SQLSTATE: [HY000](#)  
Message: You are using safe update mode and you tried to update a table without a WHERE that uses a KEY column. %s
  - Error number: [1176](#); Symbol: [ER\\_KEY\\_DOES\\_NOT\\_EXISTS](#); SQLSTATE: [42000](#)  
Message: Key '%s' doesn't exist in table '%s'
  - Error number: [1177](#); Symbol: [ER\\_CHECK\\_NO\\_SUCH\\_TABLE](#); SQLSTATE: [42000](#)  
Message: Can't open table
  - Error number: [1178](#); Symbol: [ER\\_CHECK\\_NOT\\_IMPLEMENTED](#); SQLSTATE: [42000](#)  
Message: The storage engine for the table doesn't support %s
  - Error number: [1179](#); Symbol: [ER\\_CANT\\_DO\\_THIS\\_DURING\\_AN\\_TRANSACTION](#); SQLSTATE: [25000](#)  
Message: You are not allowed to execute this command in a transaction
  - Error number: [1180](#); Symbol: [ER\\_ERROR\\_DURING\\_COMMIT](#); SQLSTATE: [HY000](#)  
Message: Got error %d - '%s' during COMMIT
  - Error number: [1181](#); Symbol: [ER\\_ERROR\\_DURING\\_ROLLBACK](#); SQLSTATE: [HY000](#)  
Message: Got error %d - '%s' during ROLLBACK
  - Error number: [1182](#); Symbol: [ER\\_ERROR\\_DURING\\_FLUSH\\_LOGS](#); SQLSTATE: [HY000](#)

---

Message: Got error %d during FLUSH\_LOGS

- Error number: 1184; Symbol: [ER\\_NEW\\_ABORTING\\_CONNECTION](#); SQLSTATE: 08S01

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s)

- Error number: 1188; Symbol: [ER\\_MASTER](#); SQLSTATE: HY000

Message: Error from master: '%s'

[ER\\_MASTER](#) was removed after 8.0.32.

- Error number: 1188; Symbol: [ER\\_SOURCE](#); SQLSTATE: HY000

Message: Error from source: '%s'

[ER\\_SOURCE](#) was added in 8.0.33.

- Error number: 1189; Symbol: [ER\\_MASTER\\_NET\\_READ](#); SQLSTATE: 08S01

Message: Net error reading from master

[ER\\_MASTER\\_NET\\_READ](#) was removed after 8.0.32.

- Error number: 1189; Symbol: [ER\\_SOURCE\\_NET\\_READ](#); SQLSTATE: 08S01

Message: Net error reading from source

[ER\\_SOURCE\\_NET\\_READ](#) was added in 8.0.33.

- Error number: 1190; Symbol: [ER\\_MASTER\\_NET\\_WRITE](#); SQLSTATE: 08S01

Message: Net error writing to master

[ER\\_MASTER\\_NET\\_WRITE](#) was removed after 8.0.32.

- Error number: 1190; Symbol: [ER\\_SOURCE\\_NET\\_WRITE](#); SQLSTATE: 08S01

Message: Net error writing to source

[ER\\_SOURCE\\_NET\\_WRITE](#) was added in 8.0.33.

- Error number: 1191; Symbol: [ER\\_FT\\_MATCHING\\_KEY\\_NOT\\_FOUND](#); SQLSTATE: HY000

Message: Can't find FULLTEXT index matching the column list

- Error number: 1192; Symbol: [ER\\_LOCK\\_OR\\_ACTIVE\\_TRANSACTION](#); SQLSTATE: HY000

Message: Can't execute the given command because you have active locked tables or an active transaction

- Error number: 1193; Symbol: [ER\\_UNKNOWN\\_SYSTEM\\_VARIABLE](#); SQLSTATE: HY000

Message: Unknown system variable '%s'

- Error number: 1194; Symbol: [ER\\_CRASHED\\_ON\\_USAGE](#); SQLSTATE: HY000

Message: Table '%s' is marked as crashed and should be repaired

- 
- Error number: [1195](#); Symbol: [ER\\_CRASHED\\_ON\\_REPAIR](#); SQLSTATE: [HY000](#)  
Message: Table '%s' is marked as crashed and last (automatic?) repair failed
  - Error number: [1196](#); Symbol: [ER\\_WARNING\\_NOT\\_COMPLETE\\_ROLLBACK](#); SQLSTATE: [HY000](#)  
Message: Some non-transactional changed tables couldn't be rolled back
  - Error number: [1197](#); Symbol: [ER\\_TRANS\\_CACHE\\_FULL](#); SQLSTATE: [HY000](#)  
Message: Multi-statement transaction required more than 'max\_binlog\_cache\_size' bytes of storage; increase this mysqld variable and try again
  - Error number: [1199](#); Symbol: [ER\\_SLAVE\\_NOT\\_RUNNING](#); SQLSTATE: [HY000](#)  
Message: This operation requires a running slave; configure slave and do START SLAVE  
[ER\\_SLAVE\\_NOT\\_RUNNING](#) was removed after 8.0.32.
  - Error number: [1199](#); Symbol: [ER\\_REPLICA\\_NOT\\_RUNNING](#); SQLSTATE: [HY000](#)  
Message: This operation requires a running replica; configure replica and do START REPLICA  
[ER\\_REPLICA\\_NOT\\_RUNNING](#) was added in 8.0.33.
  - Error number: [1200](#); Symbol: [ER\\_BAD\\_SLAVE](#); SQLSTATE: [HY000](#)  
Message: The server is not configured as slave; fix in config file or with CHANGE MASTER TO  
[ER\\_BAD\\_SLAVE](#) was removed after 8.0.32.
  - Error number: [1200](#); Symbol: [ER\\_BAD\\_REPLICA](#); SQLSTATE: [HY000](#)  
Message: The server is not configured as replica; fix in config file or with CHANGE REPLICATION SOURCE TO  
[ER\\_BAD\\_REPLICA](#) was added in 8.0.33.
  - Error number: [1201](#); Symbol: [ER\\_MASTER\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Could not initialize master info structure; more error messages can be found in the MySQL error log  
[ER\\_MASTER\\_INFO](#) was removed after 8.0.32.
  - Error number: [1201](#); Symbol: [ER\\_CONNECTION\\_METADATA](#); SQLSTATE: [HY000](#)  
Message: Could not initialize connection metadata structure; more error messages can be found in the MySQL error log  
[ER\\_CONNECTION\\_METADATA](#) was added in 8.0.33.
  - Error number: [1202](#); Symbol: [ER\\_SLAVE\\_THREAD](#); SQLSTATE: [HY000](#)  
Message: Could not create slave thread; check system resources  
[ER\\_SLAVE\\_THREAD](#) was removed after 8.0.32.
  - Error number: [1202](#); Symbol: [ER\\_REPLICA\\_THREAD](#); SQLSTATE: [HY000](#)

---

Message: Could not create replica thread; check system resources

[ER\\_REPLICA\\_THREAD](#) was added in 8.0.33.

- Error number: [1203](#); Symbol: [ER\\_TOO\\_MANY\\_USER\\_CONNECTIONS](#); SQLSTATE: [42000](#)

Message: User %s already has more than 'max\_user\_connections' active connections

- Error number: [1204](#); Symbol: [ER\\_SET\\_CONSTANTS\\_ONLY](#); SQLSTATE: [HY000](#)

Message: You may only use constant expressions with SET

- Error number: [1205](#); Symbol: [ER\\_LOCK\\_WAIT\\_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: Lock wait timeout exceeded; try restarting transaction

[InnoDB](#) reports this error when lock wait timeout expires. The statement that waited too long was [rolled back](#) (not the entire [transaction](#)). You can increase the value of the [innodb\\_lock\\_wait\\_timeout](#) configuration option if SQL statements should wait longer for other transactions to complete, or decrease it if too many long-running transactions are causing [locking](#) problems and reducing [concurrency](#) on a busy system.

- Error number: [1206](#); Symbol: [ER\\_LOCK\\_TABLE\\_FULL](#); SQLSTATE: [HY000](#)

Message: The total number of locks exceeds the lock table size

[InnoDB](#) reports this error when the total number of locks exceeds the amount of memory devoted to managing locks. To avoid this error, increase the value of [innodb\\_buffer\\_pool\\_size](#). Within an individual application, a workaround may be to break a large operation into smaller pieces. For example, if the error occurs for a large [INSERT](#), perform several smaller [INSERT](#) operations.

- Error number: [1207](#); Symbol: [ER\\_READ\\_ONLY\\_TRANSACTION](#); SQLSTATE: [25000](#)

Message: Update locks cannot be acquired during a READ UNCOMMITTED transaction

- Error number: [1210](#); Symbol: [ER\\_WRONG\\_ARGUMENTS](#); SQLSTATE: [HY000](#)

Message: Incorrect arguments to %s

- Error number: [1211](#); Symbol: [ER\\_NO\\_PERMISSION\\_TO\\_CREATE\\_USER](#); SQLSTATE: [42000](#)

Message: '%s'@'%s' is not allowed to create new users

- Error number: [1213](#); Symbol: [ER\\_LOCK\\_DEADLOCK](#); SQLSTATE: [40001](#)

Message: Deadlock found when trying to get lock; try restarting transaction

[InnoDB](#) reports this error when a [transaction](#) encounters a [deadlock](#) and is automatically [rolled back](#) so that your application can take corrective action. To recover from this error, run all the operations in this transaction again. A deadlock occurs when requests for locks arrive in inconsistent order between transactions. The transaction that was rolled back released all its locks, and the other transaction can now get all the locks it requested. Thus, when you re-run the transaction that was rolled back, it might have to wait for other transactions to complete, but typically the deadlock does not recur. If you encounter frequent deadlocks, make the sequence of locking operations ([LOCK TABLES](#), [SELECT . . . FOR UPDATE](#), and so on) consistent between the different transactions or applications that experience the issue. See [Deadlocks in InnoDB](#) for details.

- Error number: [1214](#); Symbol: [ER\\_TABLE\\_CANT\\_HANDLE\\_FT](#); SQLSTATE: [HY000](#)



---

Message: The used table type doesn't support FULLTEXT indexes

- Error number: 1215; Symbol: `ER_CANNOT_ADD_FOREIGN`; SQLSTATE: `HY000`

Message: Cannot add foreign key constraint

- Error number: 1216; Symbol: `ER_NO_REFERENCED_ROW`; SQLSTATE: `23000`

Message: Cannot add or update a child row: a foreign key constraint fails

`InnoDB` reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.

- Error number: 1217; Symbol: `ER_ROW_IS_REFERENCED`; SQLSTATE: `23000`

Message: Cannot delete or update a parent row: a foreign key constraint fails

`InnoDB` reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.

- Error number: 1218; Symbol: `ER_CONNECT_TO_MASTER`; SQLSTATE: `08S01`

Message: Error connecting to master: %s

`ER_CONNECT_TO_MASTER` was removed after 8.0.32.

- Error number: 1218; Symbol: `ER_CONNECT_TO_SOURCE`; SQLSTATE: `08S01`

Message: Error connecting to source: %s

`ER_CONNECT_TO_SOURCE` was added in 8.0.33.

- Error number: 1220; Symbol: `ER_ERROR_WHEN_EXECUTING_COMMAND`; SQLSTATE: `HY000`

Message: Error when executing command %s: %s

- Error number: 1221; Symbol: `ER_WRONG_USAGE`; SQLSTATE: `HY000`

Message: Incorrect usage of %s and %s

- Error number: 1222; Symbol: `ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT`; SQLSTATE: `21000`

Message: The used SELECT statements have a different number of columns

- Error number: 1223; Symbol: `ER_CANT_UPDATE_WITH_READLOCK`; SQLSTATE: `HY000`

Message: Can't execute the query because you have a conflicting read lock

- Error number: 1224; Symbol: `ER_MIXING_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: Mixing of transactional and non-transactional tables is disabled

- Error number: 1225; Symbol: `ER_DUP_ARGUMENT`; SQLSTATE: `HY000`

Message: Option '%s' used twice in statement

- Error number: 1226; Symbol: `ER_USER_LIMIT_REACHED`; SQLSTATE: `42000`

Message: User '%s' has exceeded the '%s' resource (current value: %ld)

- 
- Error number: [1227](#); Symbol: [ER\\_SPECIFIC\\_ACCESS\\_DENIED\\_ERROR](#); SQLSTATE: [42000](#)  
Message: Access denied; you need (at least one of) the %s privilege(s) for this operation
  - Error number: [1228](#); Symbol: [ER\\_LOCAL\\_VARIABLE](#); SQLSTATE: [HY000](#)  
Message: Variable '%s' is a SESSION variable and can't be used with SET GLOBAL
  - Error number: [1229](#); Symbol: [ER\\_GLOBAL\\_VARIABLE](#); SQLSTATE: [HY000](#)  
Message: Variable '%s' is a GLOBAL variable and should be set with SET GLOBAL
  - Error number: [1230](#); Symbol: [ER\\_NO\\_DEFAULT](#); SQLSTATE: [42000](#)  
Message: Variable '%s' doesn't have a default value
  - Error number: [1231](#); Symbol: [ER\\_WRONG\\_VALUE\\_FOR\\_VAR](#); SQLSTATE: [42000](#)  
Message: Variable '%s' can't be set to the value of '%s'
  - Error number: [1232](#); Symbol: [ER\\_WRONG\\_TYPE\\_FOR\\_VAR](#); SQLSTATE: [42000](#)  
Message: Incorrect argument type to variable '%s'
  - Error number: [1233](#); Symbol: [ER\\_VAR\\_CANT\\_BE\\_READ](#); SQLSTATE: [HY000](#)  
Message: Variable '%s' can only be set, not read
  - Error number: [1234](#); Symbol: [ER\\_CANT\\_USE\\_OPTION\\_HERE](#); SQLSTATE: [42000](#)  
Message: Incorrect usage/placement of '%s'
  - Error number: [1235](#); Symbol: [ER\\_NOT\\_SUPPORTED\\_YET](#); SQLSTATE: [42000](#)  
Message: This version of MySQL doesn't yet support '%s'
  - Error number: [1236](#); Symbol: [ER\\_MASTER\\_FATAL\\_ERROR\\_READING\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: Got fatal error %d from master when reading data from binary log: '%s'  
[ER\\_MASTER\\_FATAL\\_ERROR\\_READING\\_BINLOG](#) was removed after 8.0.32.
  - Error number: [1236](#); Symbol: [ER\\_SOURCE\\_FATAL\\_ERROR\\_READING\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: Got fatal error %d from source when reading data from binary log: '%s'  
[ER\\_SOURCE\\_FATAL\\_ERROR\\_READING\\_BINLOG](#) was added in 8.0.33.
  - Error number: [1237](#); Symbol: [ER\\_SLAVE\\_IGNORED\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Slave SQL thread ignored the query because of replicate-\*-table rules  
[ER\\_SLAVE\\_IGNORED\\_TABLE](#) was removed after 8.0.32.
  - Error number: [1237](#); Symbol: [ER\\_REPLICA\\_IGNORED\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Replica SQL thread ignored the query because of replicate-\*-table rules  
[ER\\_REPLICA\\_IGNORED\\_TABLE](#) was added in 8.0.33.

- 
- Error number: [1238](#); Symbol: [ER\\_INCORRECT\\_GLOBAL\\_LOCAL\\_VAR](#); SQLSTATE: [HY000](#)  
Message: Variable '%s' is a %s variable
  - Error number: [1239](#); Symbol: [ER\\_WRONG\\_FK\\_DEF](#); SQLSTATE: [42000](#)  
Message: Incorrect foreign key definition for '%s': %s
  - Error number: [1240](#); Symbol: [ER\\_KEY\\_REF\\_DO\\_NOT\\_MATCH\\_TABLE\\_REF](#); SQLSTATE: [HY000](#)  
Message: Key reference and table reference don't match
  - Error number: [1241](#); Symbol: [ER\\_OPERAND\\_COLUMNS](#); SQLSTATE: [21000](#)  
Message: Operand should contain %d column(s)
  - Error number: [1242](#); Symbol: [ER\\_SUBQUERY\\_NO\\_1\\_ROW](#); SQLSTATE: [21000](#)  
Message: Subquery returns more than 1 row
  - Error number: [1243](#); Symbol: [ER\\_UNKNOWN\\_STMT\\_HANDLER](#); SQLSTATE: [HY000](#)  
Message: Unknown prepared statement handler (%.\*s) given to %s
  - Error number: [1244](#); Symbol: [ER\\_CORRUPT\\_HELP\\_DB](#); SQLSTATE: [HY000](#)  
Message: Help database is corrupt or does not exist
  - Error number: [1246](#); Symbol: [ER\\_AUTO\\_CONVERT](#); SQLSTATE: [HY000](#)  
Message: Converting column '%s' from %s to %s
  - Error number: [1247](#); Symbol: [ER\\_ILLEGAL\\_REFERENCE](#); SQLSTATE: [42S22](#)  
Message: Reference '%s' not supported (%s)
  - Error number: [1248](#); Symbol: [ER\\_DERIVED\\_MUST\\_HAVE\\_ALIAS](#); SQLSTATE: [42000](#)  
Message: Every derived table must have its own alias
  - Error number: [1249](#); Symbol: [ER\\_SELECT\\_REDUCED](#); SQLSTATE: [01000](#)  
Message: Select %u was reduced during optimization
  - Error number: [1250](#); Symbol: [ER\\_TABLENAME\\_NOT\\_ALLOWED\\_HERE](#); SQLSTATE: [42000](#)  
Message: Table '%s' from one of the SELECTs cannot be used in %s
  - Error number: [1251](#); Symbol: [ER\\_NOT\\_SUPPORTED\\_AUTH\\_MODE](#); SQLSTATE: [08004](#)  
Message: Client does not support authentication protocol requested by server; consider upgrading MySQL client
  - Error number: [1252](#); Symbol: [ER\\_SPATIAL\\_CANT\\_HAVE\\_NULL](#); SQLSTATE: [42000](#)  
Message: All parts of a SPATIAL index must be NOT NULL
  - Error number: [1253](#); Symbol: [ER\\_COLLATION\\_CHARSET\\_MISMATCH](#); SQLSTATE: [42000](#)  
Message: COLLATION '%s' is not valid for CHARACTER SET '%s'

- 
- Error number: [1256](#); Symbol: [ER\\_TOO\\_BIG\\_FOR\\_UNCOMPRESS](#); SQLSTATE: [HY000](#)  
Message: Uncompressed data size too large; the maximum size is %d (probably, length of uncompressed data was corrupted)
  - Error number: [1257](#); Symbol: [ER\\_ZLIB\\_Z\\_MEM\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: ZLIB: Not enough memory
  - Error number: [1258](#); Symbol: [ER\\_ZLIB\\_Z\\_BUF\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: ZLIB: Not enough room in the output buffer (probably, length of uncompressed data was corrupted)
  - Error number: [1259](#); Symbol: [ER\\_ZLIB\\_Z\\_DATA\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: ZLIB: Input data corrupted
  - Error number: [1260](#); Symbol: [ER\\_CUT\\_VALUE\\_GROUP\\_CONCAT](#); SQLSTATE: [HY000](#)  
Message: Row %u was cut by GROUP\_CONCAT()
  - Error number: [1261](#); Symbol: [ER\\_WARN\\_TOO\\_FEW\\_RECORDS](#); SQLSTATE: [01000](#)  
Message: Row %ld doesn't contain data for all columns
  - Error number: [1262](#); Symbol: [ER\\_WARN\\_TOO\\_MANY\\_RECORDS](#); SQLSTATE: [01000](#)  
Message: Row %ld was truncated; it contained more data than there were input columns
  - Error number: [1263](#); Symbol: [ER\\_WARN\\_NULL\\_TO\\_NOTNULL](#); SQLSTATE: [22004](#)  
Message: Column set to default value; NULL supplied to NOT NULL column '%s' at row %ld
  - Error number: [1264](#); Symbol: [ER\\_WARN\\_DATA\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [22003](#)  
Message: Out of range value for column '%s' at row %ld
  - Error number: [1265](#); Symbol: [WARN\\_DATA\\_TRUNCATED](#); SQLSTATE: [01000](#)  
Message: Data truncated for column '%s' at row %ld
  - Error number: [1266](#); Symbol: [ER\\_WARN\\_USING\\_OTHER\\_HANDLER](#); SQLSTATE: [HY000](#)  
Message: Using storage engine %s for table '%s'
  - Error number: [1267](#); Symbol: [ER\\_CANT\\_AGGREGATE\\_2COLLATIONS](#); SQLSTATE: [HY000](#)  
Message: Illegal mix of collations (%s,%s) and (%s,%s) for operation '%s'
  - Error number: [1269](#); Symbol: [ER\\_REVOKE\\_GRANTS](#); SQLSTATE: [HY000](#)  
Message: Can't revoke all privileges for one or more of the requested users
  - Error number: [1270](#); Symbol: [ER\\_CANT\\_AGGREGATE\\_3COLLATIONS](#); SQLSTATE: [HY000](#)  
Message: Illegal mix of collations (%s,%s), (%s,%s), (%s,%s) for operation '%s'
  - Error number: [1271](#); Symbol: [ER\\_CANT\\_AGGREGATE\\_NCOLLATIONS](#); SQLSTATE: [HY000](#)

---

Message: Illegal mix of collations for operation '%s'

- Error number: [1272](#); Symbol: [ER\\_VARIABLE\\_IS\\_NOT\\_STRUCT](#); SQLSTATE: [HY000](#)

Message: Variable '%s' is not a variable component (can't be used as XXXX.variable\_name)

- Error number: [1273](#); Symbol: [ER\\_UNKNOWN\\_COLLATION](#); SQLSTATE: [HY000](#)

Message: Unknown collation: '%s'

- Error number: [1274](#); Symbol: [ER\\_SLAVE\\_IGNORED\\_SSL\\_PARAMS](#); SQLSTATE: [HY000](#)

Message: SSL parameters in CHANGE MASTER are ignored because this MySQL slave was compiled without SSL support; they can be used later if MySQL slave with SSL is started

[ER\\_SLAVE\\_IGNORED\\_SSL\\_PARAMS](#) was removed after 8.0.32.

- Error number: [1274](#); Symbol: [ER\\_REPLICA\\_IGNORED\\_SSL\\_PARAMS](#); SQLSTATE: [HY000](#)

Message: SSL parameters in CHANGE REPLICATION SOURCE are ignored because this MySQL replica was compiled without SSL support; they can be used later if MySQL replica with SSL is started

[ER\\_REPLICA\\_IGNORED\\_SSL\\_PARAMS](#) was added in 8.0.33.

- Error number: [1275](#); Symbol: [ER\\_SERVER\\_IS\\_IN\\_SECURE\\_AUTH\\_MODE](#); SQLSTATE: [HY000](#)

Message: Server is running in --secure-auth mode, but '%s@'%s' has a password in the old format; please change the password to the new format

[ER\\_SERVER\\_IS\\_IN\\_SECURE\\_AUTH\\_MODE](#) was removed after 8.0.15.

- Error number: [1276](#); Symbol: [ER\\_WARN\\_FIELD\\_RESOLVED](#); SQLSTATE: [HY000](#)

Message: Field or reference '%s%s%s%s%s%' of SELECT #%d was resolved in SELECT #%d

- Error number: [1277](#); Symbol: [ER\\_BAD\\_SLAVE\\_UNTIL\\_COND](#); SQLSTATE: [HY000](#)

Message: Incorrect parameter or combination of parameters for START SLAVE UNTIL

[ER\\_BAD\\_SLAVE\\_UNTIL\\_COND](#) was removed after 8.0.32.

- Error number: [1277](#); Symbol: [ER\\_BAD\\_REPLICA\\_UNTIL\\_COND](#); SQLSTATE: [HY000](#)

Message: Incorrect parameter or combination of parameters for START REPLICA UNTIL

[ER\\_BAD\\_REPLICA\\_UNTIL\\_COND](#) was added in 8.0.33.

- Error number: [1278](#); Symbol: [ER\\_MISSING\\_SKIP\\_SLAVE](#); SQLSTATE: [HY000](#)

Message: It is recommended to use --skip-replica-start when doing step-by-step replication with START SLAVE UNTIL; otherwise, you will get problems if you get an unexpected slave's mysqld restart

[ER\\_MISSING\\_SKIP\\_SLAVE](#) was removed after 8.0.32.

- Error number: [1278](#); Symbol: [ER\\_MISSING\\_SKIP\\_REPLICA](#); SQLSTATE: [HY000](#)

Message: It is recommended to use --skip-replica-start when doing step-by-step replication with START REPLICA UNTIL; otherwise, you will get problems if you get an unexpected replica's mysqld restart

---

[ER\\_MISSING\\_SKIP\\_REPLICA](#) was added in 8.0.33.

- Error number: [1279](#); Symbol: [ER\\_UNTIL\\_COND\\_IGNORED](#); SQLSTATE: [HY000](#)  
Message: SQL thread is not to be started so UNTIL options are ignored
- Error number: [1280](#); Symbol: [ER\\_WRONG\\_NAME\\_FOR\\_INDEX](#); SQLSTATE: [42000](#)  
Message: Incorrect index name '%s'
- Error number: [1281](#); Symbol: [ER\\_WRONG\\_NAME\\_FOR\\_CATALOG](#); SQLSTATE: [42000](#)  
Message: Incorrect catalog name '%s'
- Error number: [1282](#); Symbol: [ER\\_WARN\\_QC\\_RESIZE](#); SQLSTATE: [HY000](#)  
Message: Query cache failed to set size %lu; new query cache size is %lu  
[ER\\_WARN\\_QC\\_RESIZE](#) was removed after 8.0.2.
- Error number: [1283](#); Symbol: [ER\\_BAD\\_FT\\_COLUMN](#); SQLSTATE: [HY000](#)  
Message: Column '%s' cannot be part of FULLTEXT index
- Error number: [1284](#); Symbol: [ER\\_UNKNOWN\\_KEY\\_CACHE](#); SQLSTATE: [HY000](#)  
Message: Unknown key cache '%s'
- Error number: [1285](#); Symbol: [ER\\_WARN\\_HOSTNAME\\_WONT\\_WORK](#); SQLSTATE: [HY000](#)  
Message: MySQL is started in --skip-name-resolve mode; you must restart it without this switch for this grant to work
- Error number: [1286](#); Symbol: [ER\\_UNKNOWN\\_STORAGE\\_ENGINE](#); SQLSTATE: [42000](#)  
Message: Unknown storage engine '%s'
- Error number: [1287](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_SYNTAX](#); SQLSTATE: [HY000](#)  
Message: '%s' is deprecated and will be removed in a future release. Please use %s instead
- Error number: [1288](#); Symbol: [ER\\_NON\\_UPDATABLE\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: The target table %s of the %s is not updatable
- Error number: [1289](#); Symbol: [ER\\_FEATURE\\_DISABLED](#); SQLSTATE: [HY000](#)  
Message: The '%s' feature is disabled; you need MySQL built with '%s' to have it working
- Error number: [1290](#); Symbol: [ER\\_OPTION\\_PREVENTS\\_STATEMENT](#); SQLSTATE: [HY000](#)  
Message: The MySQL server is running with the %s option so it cannot execute this statement
- Error number: [1291](#); Symbol: [ER\\_DUPLICATED\\_VALUE\\_IN\\_TYPE](#); SQLSTATE: [HY000](#)  
Message: Column '%s' has duplicated value '%s' in %s
- Error number: [1292](#); Symbol: [ER\\_TRUNCATED\\_WRONG\\_VALUE](#); SQLSTATE: [22007](#)  
Message: Truncated incorrect %s value: '%s'

- 
- Error number: 1294; Symbol: ER\_INVALID\_ON\_UPDATE; SQLSTATE: HY000  
Message: Invalid ON UPDATE clause for '%s' column
  - Error number: 1295; Symbol: ER\_UNSUPPORTED\_PS; SQLSTATE: HY000  
Message: This command is not supported in the prepared statement protocol yet
  - Error number: 1296; Symbol: ER\_GET\_ERRMSG; SQLSTATE: HY000  
Message: Got error %d '%s' from %s
  - Error number: 1297; Symbol: ER\_GET\_TEMPORARY\_ERRMSG; SQLSTATE: HY000  
Message: Got temporary error %d '%s' from %s
  - Error number: 1298; Symbol: ER\_UNKNOWN\_TIME\_ZONE; SQLSTATE: HY000  
Message: Unknown or incorrect time zone: '%s'
  - Error number: 1299; Symbol: ER\_WARN\_INVALID\_TIMESTAMP; SQLSTATE: HY000  
Message: Invalid TIMESTAMP value in column '%s' at row %ld
  - Error number: 1300; Symbol: ER\_INVALID\_CHARACTER\_STRING; SQLSTATE: HY000  
Message: Invalid %s character string: '%s'
  - Error number: 1301; Symbol: ER\_WARN\_ALLOWED\_PACKET\_OVERFLOWED; SQLSTATE: HY000  
Message: Result of %s() was larger than max\_allowed\_packet (%ld) - truncated
  - Error number: 1302; Symbol: ER\_CONFLICTING\_DECLARATIONS; SQLSTATE: HY000  
Message: Conflicting declarations: '%s%s' and '%s%s'
  - Error number: 1303; Symbol: ER\_SP\_NO\_RECURSIVE\_CREATE; SQLSTATE: 2F003  
Message: Can't create a %s from within another stored routine
  - Error number: 1304; Symbol: ER\_SP\_ALREADY\_EXISTS; SQLSTATE: 42000  
Message: %s %s already exists
  - Error number: 1305; Symbol: ER\_SP\_DOES\_NOT\_EXIST; SQLSTATE: 42000  
Message: %s %s does not exist
  - Error number: 1306; Symbol: ER\_SP\_DROP\_FAILED; SQLSTATE: HY000  
Message: Failed to DROP %s %s
  - Error number: 1307; Symbol: ER\_SP\_STORE\_FAILED; SQLSTATE: HY000  
Message: Failed to CREATE %s %s
  - Error number: 1308; Symbol: ER\_SP\_LILABEL\_MISMATCH; SQLSTATE: 42000  
Message: %s with no matching label: %s
  - Error number: 1309; Symbol: ER\_SP\_LABEL\_REDEFINE; SQLSTATE: 42000

- 
- Message: Redefining label %s
- Error number: 1310; Symbol: `ER_SP_LABEL_MISMATCH`; SQLSTATE: 42000  
Message: End-label %s without match
  - Error number: 1311; Symbol: `ER_SP_UNINIT_VAR`; SQLSTATE: 01000  
Message: Referring to uninitialized variable %s
  - Error number: 1312; Symbol: `ER_SP_BADSELECT`; SQLSTATE: 0A000  
Message: PROCEDURE %s can't return a result set in the given context
  - Error number: 1313; Symbol: `ER_SP_BADRETURN`; SQLSTATE: 42000  
Message: RETURN is only allowed in a FUNCTION
  - Error number: 1314; Symbol: `ER_SP_BADSTATEMENT`; SQLSTATE: 0A000  
Message: %s is not allowed in stored procedures
  - Error number: 1315; Symbol: `ER_UPDATE_LOG_DEPRECATED_IGNORED`; SQLSTATE: 42000  
Message: The update log is deprecated and replaced by the binary log; SET SQL\_LOG\_UPDATE has been ignored.
  - Error number: 1316; Symbol: `ER_UPDATE_LOG_DEPRECATED_TRANSLATED`; SQLSTATE: 42000  
Message: The update log is deprecated and replaced by the binary log; SET SQL\_LOG\_UPDATE has been translated to SET SQL\_LOG\_BIN.
  - Error number: 1317; Symbol: `ER_QUERY_INTERRUPTED`; SQLSTATE: 70100  
Message: Query execution was interrupted
  - Error number: 1318; Symbol: `ER_SP_WRONG_NO_OF_ARGS`; SQLSTATE: 42000  
Message: Incorrect number of arguments for %s %s; expected %u, got %u
  - Error number: 1319; Symbol: `ER_SP_COND_MISMATCH`; SQLSTATE: 42000  
Message: Undefined CONDITION: %s
  - Error number: 1320; Symbol: `ER_SP_NORETURN`; SQLSTATE: 42000  
Message: No RETURN found in FUNCTION %s
  - Error number: 1321; Symbol: `ER_SP_NORETURNEND`; SQLSTATE: 2F005  
Message: FUNCTION %s ended without RETURN
  - Error number: 1322; Symbol: `ER_SP_BAD_CURSOR_QUERY`; SQLSTATE: 42000  
Message: Cursor statement must be a SELECT
  - Error number: 1323; Symbol: `ER_SP_BAD_CURSOR_SELECT`; SQLSTATE: 42000  
Message: Cursor SELECT must not have INTO



- 
- Error number: 1324; Symbol: ER\_SP\_CURSOR\_MISMATCH; SQLSTATE: 42000  
Message: Undefined CURSOR: %s
  - Error number: 1325; Symbol: ER\_SP\_CURSOR\_ALREADY\_OPEN; SQLSTATE: 24000  
Message: Cursor is already open
  - Error number: 1326; Symbol: ER\_SP\_CURSOR\_NOT\_OPEN; SQLSTATE: 24000  
Message: Cursor is not open
  - Error number: 1327; Symbol: ER\_SP\_UNDECLARED\_VAR; SQLSTATE: 42000  
Message: Undeclared variable: %s
  - Error number: 1328; Symbol: ER\_SP\_WRONG\_NO\_OF\_FETCH\_ARGS; SQLSTATE: HY000  
Message: Incorrect number of FETCH variables
  - Error number: 1329; Symbol: ER\_SP\_FETCH\_NO\_DATA; SQLSTATE: 02000  
Message: No data - zero rows fetched, selected, or processed
  - Error number: 1330; Symbol: ER\_SP\_DUP\_PARAM; SQLSTATE: 42000  
Message: Duplicate parameter: %s
  - Error number: 1331; Symbol: ER\_SP\_DUP\_VAR; SQLSTATE: 42000  
Message: Duplicate variable: %s
  - Error number: 1332; Symbol: ER\_SP\_DUP\_COND; SQLSTATE: 42000  
Message: Duplicate condition: %s
  - Error number: 1333; Symbol: ER\_SP\_DUP\_CURS; SQLSTATE: 42000  
Message: Duplicate cursor: %s
  - Error number: 1334; Symbol: ER\_SP\_CANT\_ALTER; SQLSTATE: HY000  
Message: Failed to ALTER %s %s
  - Error number: 1335; Symbol: ER\_SP\_SUBSELECT\_NYI; SQLSTATE: 0A000  
Message: Subquery value not supported
  - Error number: 1336; Symbol: ER\_STMT\_NOT\_ALLOWED\_IN\_SF\_OR\_TRG; SQLSTATE: 0A000  
Message: %s is not allowed in stored function or trigger
  - Error number: 1337; Symbol: ER\_SP\_VARCOND\_AFTER\_CURSHNDLR; SQLSTATE: 42000  
Message: Variable or condition declaration after cursor or handler declaration
  - Error number: 1338; Symbol: ER\_SP\_CURSOR\_AFTER\_HANDLER; SQLSTATE: 42000  
Message: Cursor declaration after handler declaration

- 
- Error number: [1339](#); Symbol: [ER\\_SP\\_CASE\\_NOT\\_FOUND](#); SQLSTATE: [20000](#)  
Message: Case not found for CASE statement
  - Error number: [1340](#); Symbol: [ER\\_FPARSER\\_TOO\\_BIG\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Configuration file '%s' is too big
  - Error number: [1341](#); Symbol: [ER\\_FPARSER\\_BAD\\_HEADER](#); SQLSTATE: [HY000](#)  
Message: Malformed file type header in file '%s'
  - Error number: [1342](#); Symbol: [ER\\_FPARSER\\_EOF\\_IN\\_COMMENT](#); SQLSTATE: [HY000](#)  
Message: Unexpected end of file while parsing comment '%s'
  - Error number: [1343](#); Symbol: [ER\\_FPARSER\\_ERROR\\_IN\\_PARAMETER](#); SQLSTATE: [HY000](#)  
Message: Error while parsing parameter '%s' (line: '%s')
  - Error number: [1344](#); Symbol: [ER\\_FPARSER\\_EOF\\_IN\\_UNKNOWN\\_PARAMETER](#); SQLSTATE: [HY000](#)  
Message: Unexpected end of file while skipping unknown parameter '%s'
  - Error number: [1345](#); Symbol: [ER\\_VIEW\\_NO\\_EXPLAIN](#); SQLSTATE: [HY000](#)  
Message: EXPLAIN/SHOW can not be issued; lacking privileges for underlying table
  - Error number: [1347](#); Symbol: [ER\\_WRONG\\_OBJECT](#); SQLSTATE: [HY000](#)  
Message: '%s.%s' is not %s  
  
The named object is incorrect for the type of operation attempted on it. It must be an object of the named type. Example: [HANDLER OPEN](#) requires a base table, not a view. It fails if attempted on an [INFORMATION\\_SCHEMA](#) table that is implemented as a view on data dictionary tables.
  - Error number: [1348](#); Symbol: [ER\\_NONUPDATEABLE\\_COLUMN](#); SQLSTATE: [HY000](#)  
Message: Column '%s' is not updatable
  - Error number: [1350](#); Symbol: [ER\\_VIEW\\_SELECT\\_CLAUSE](#); SQLSTATE: [HY000](#)  
Message: View's SELECT contains a '%s' clause
  - Error number: [1351](#); Symbol: [ER\\_VIEW\\_SELECT\\_VARIABLE](#); SQLSTATE: [HY000](#)  
Message: View's SELECT contains a variable or parameter
  - Error number: [1352](#); Symbol: [ER\\_VIEW\\_SELECT\\_TMPTABLE](#); SQLSTATE: [HY000](#)  
Message: View's SELECT refers to a temporary table '%s'
  - Error number: [1353](#); Symbol: [ER\\_VIEW\\_WRONG\\_LIST](#); SQLSTATE: [HY000](#)  
Message: In definition of view, derived table or common table expression, SELECT list and column names list have different column counts
  - Error number: [1354](#); Symbol: [ER\\_WARN\\_VIEW\\_MERGE](#); SQLSTATE: [HY000](#)  
Message: View merge algorithm can't be used here for now (assumed undefined algorithm)

- 
- Error number: [1355](#); Symbol: [ER\\_WARN\\_VIEW\\_WITHOUT\\_KEY](#); SQLSTATE: [HY000](#)  
Message: View being updated does not have complete key of underlying table in it
  - Error number: [1356](#); Symbol: [ER\\_VIEW\\_INVALID](#); SQLSTATE: [HY000](#)  
Message: View '%s.%s' references invalid table(s) or column(s) or function(s) or definer/invoker of view lack rights to use them
  - Error number: [1357](#); Symbol: [ER\\_SP\\_NO\\_DROP\\_SP](#); SQLSTATE: [HY000](#)  
Message: Can't drop or alter a %s from within another stored routine
  - Error number: [1359](#); Symbol: [ER\\_TRG\\_ALREADY\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Trigger already exists
  - Error number: [1360](#); Symbol: [ER\\_TRG\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
Message: Trigger does not exist
  - Error number: [1361](#); Symbol: [ER\\_TRG\\_ON\\_VIEW\\_OR\\_TEMP\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Trigger's '%s' is view or temporary table
  - Error number: [1362](#); Symbol: [ER\\_TRG\\_CANT\\_CHANGE\\_ROW](#); SQLSTATE: [HY000](#)  
Message: Updating of %s row is not allowed in %strigger
  - Error number: [1363](#); Symbol: [ER\\_TRG\\_NO\\_SUCH\\_ROW\\_IN\\_TRG](#); SQLSTATE: [HY000](#)  
Message: There is no %s row in %s trigger
  - Error number: [1364](#); Symbol: [ER\\_NO\\_DEFAULT\\_FOR\\_FIELD](#); SQLSTATE: [HY000](#)  
Message: Field '%s' doesn't have a default value
  - Error number: [1365](#); Symbol: [ER\\_DIVISION\\_BY\\_ZERO](#); SQLSTATE: [22012](#)  
Message: Division by 0
  - Error number: [1366](#); Symbol: [ER\\_TRUNCATED\\_WRONG\\_VALUE\\_FOR\\_FIELD](#); SQLSTATE: [HY000](#)  
Message: Incorrect %s value: '%s' for column '%s' at row %ld
  - Error number: [1367](#); Symbol: [ER\\_ILLEGAL\\_VALUE\\_FOR\\_TYPE](#); SQLSTATE: [22007](#)  
Message: Illegal %s '%s' value found during parsing
  - Error number: [1368](#); Symbol: [ER\\_VIEW\\_NONUPD\\_CHECK](#); SQLSTATE: [HY000](#)  
Message: CHECK OPTION on non-updatable view '%s.%s'
  - Error number: [1369](#); Symbol: [ER\\_VIEW\\_CHECK\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: CHECK OPTION failed '%s.%s'
  - Error number: [1370](#); Symbol: [ER\\_PROCACCESS\\_DENIED\\_ERROR](#); SQLSTATE: [42000](#)  
Message: %s command denied to user '%s'@'%s' for routine '%s'

- 
- Error number: [1371](#); Symbol: [ER\\_RELAY\\_LOG\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed purging old relay logs: %s
  - Error number: [1373](#); Symbol: [ER\\_UNKNOWN\\_TARGET\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: Target log not found in binlog index
  - Error number: [1374](#); Symbol: [ER\\_IO\\_ERR\\_LOG\\_INDEX\\_READ](#); SQLSTATE: [HY000](#)  
Message: I/O error reading log index file
  - Error number: [1375](#); Symbol: [ER\\_BINLOG\\_PURGE\\_PROHIBITED](#); SQLSTATE: [HY000](#)  
Message: Server configuration does not permit binlog purge
  - Error number: [1376](#); Symbol: [ER\\_FSEEK\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed on fseek()
  - Error number: [1377](#); Symbol: [ER\\_BINLOG\\_PURGE\\_FATAL\\_ERR](#); SQLSTATE: [HY000](#)  
Message: Fatal error during log purge
  - Error number: [1378](#); Symbol: [ER\\_LOG\\_IN\\_USE](#); SQLSTATE: [HY000](#)  
Message: A purgeable log is in use, will not purge
  - Error number: [1379](#); Symbol: [ER\\_LOG\\_PURGE\\_UNKNOWN\\_ERR](#); SQLSTATE: [HY000](#)  
Message: Unknown error during log purge
  - Error number: [1380](#); Symbol: [ER\\_RELAY\\_LOG\\_INIT](#); SQLSTATE: [HY000](#)  
Message: Failed initializing relay log position: %s
  - Error number: [1381](#); Symbol: [ER\\_NO\\_BINARY\\_LOGGING](#); SQLSTATE: [HY000](#)  
Message: You are not using binary logging
  - Error number: [1382](#); Symbol: [ER\\_RESERVED\\_SYNTAX](#); SQLSTATE: [HY000](#)  
Message: The '%s' syntax is reserved for purposes internal to the MySQL server
  - Error number: [1390](#); Symbol: [ER\\_PS\\_MANY\\_PARAM](#); SQLSTATE: [HY000](#)  
Message: Prepared statement contains too many placeholders
  - Error number: [1391](#); Symbol: [ER\\_KEY\\_PART\\_0](#); SQLSTATE: [HY000](#)  
Message: Key part '%s' length cannot be 0
  - Error number: [1392](#); Symbol: [ER\\_VIEW\\_CHECKSUM](#); SQLSTATE: [HY000](#)  
Message: View text checksum failed
  - Error number: [1393](#); Symbol: [ER\\_VIEW\\_MULTIUPDATE](#); SQLSTATE: [HY000](#)  
Message: Can not modify more than one base table through a join view '%s.%s'

- 
- Error number: [1394](#); Symbol: [ER\\_VIEW\\_NO\\_INSERT\\_FIELD\\_LIST](#); SQLSTATE: [HY000](#)  
Message: Can not insert into join view '%s.%s' without fields list
  - Error number: [1395](#); Symbol: [ER\\_VIEW\\_DELETE\\_MERGE\\_VIEW](#); SQLSTATE: [HY000](#)  
Message: Can not delete from join view '%s.%s'
  - Error number: [1396](#); Symbol: [ER\\_CANNOT\\_USER](#); SQLSTATE: [HY000](#)  
Message: Operation %s failed for %s
  - Error number: [1397](#); Symbol: [ER\\_XAER\\_NOTA](#); SQLSTATE: [XAE04](#)  
Message: XAER\_NOTA: Unknown XID
  - Error number: [1398](#); Symbol: [ER\\_XAER\\_INVAL](#); SQLSTATE: [XAE05](#)  
Message: XAER\_INVAL: Invalid arguments (or unsupported command)
  - Error number: [1399](#); Symbol: [ER\\_XAER\\_RMFAIL](#); SQLSTATE: [XAE07](#)  
Message: XAER\_RMFAIL: The command cannot be executed when global transaction is in the %s state
  - Error number: [1400](#); Symbol: [ER\\_XAER\\_OUTSIDE](#); SQLSTATE: [XAE09](#)  
Message: XAER\_OUTSIDE: Some work is done outside global transaction
  - Error number: [1401](#); Symbol: [ER\\_XAER\\_RMERR](#); SQLSTATE: [XAE03](#)  
Message: XAER\_RMERR: Fatal error occurred in the transaction branch - check your data for consistency
  - Error number: [1402](#); Symbol: [ER\\_XA\\_RBROLLBACK](#); SQLSTATE: [XA100](#)  
Message: XA\_RBROLLBACK: Transaction branch was rolled back
  - Error number: [1403](#); Symbol: [ER\\_NONEXISTING\\_PROC\\_GRANT](#); SQLSTATE: [42000](#)  
Message: There is no such grant defined for user '%s' on host '%s' on routine '%s'
  - Error number: [1404](#); Symbol: [ER\\_PROC\\_AUTO\\_GRANT\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed to grant EXECUTE and ALTER ROUTINE privileges
  - Error number: [1405](#); Symbol: [ER\\_PROC\\_AUTO\\_REVOKE\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed to revoke all privileges to dropped routine
  - Error number: [1406](#); Symbol: [ER\\_DATA\\_TOO\\_LONG](#); SQLSTATE: [22001](#)  
Message: Data too long for column '%s' at row %ld
  - Error number: [1407](#); Symbol: [ER\\_SP\\_BAD\\_SQLSTATE](#); SQLSTATE: [42000](#)  
Message: Bad SQLSTATE: '%s'
  - Error number: [1408](#); Symbol: [ER\\_STARTUP](#); SQLSTATE: [HY000](#)  
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s

- 
- Error number: [1409](#); Symbol: [ER\\_LOAD\\_FROM\\_FIXED\\_SIZE\\_ROWS\\_TO\\_VAR](#); SQLSTATE: [HY000](#)  
Message: Can't load value from file with fixed size rows to variable
  - Error number: [1410](#); Symbol: [ER\\_CANT\\_CREATE\\_USER\\_WITH\\_GRANT](#); SQLSTATE: [42000](#)  
Message: You are not allowed to create a user with GRANT
  - Error number: [1411](#); Symbol: [ER\\_WRONG\\_VALUE\\_FOR\\_TYPE](#); SQLSTATE: [HY000](#)  
Message: Incorrect %s value: '%s' for function %s
  - Error number: [1412](#); Symbol: [ER\\_TABLE\\_DEF\\_CHANGED](#); SQLSTATE: [HY000](#)  
Message: Table definition has changed, please retry transaction
  - Error number: [1413](#); Symbol: [ER\\_SP\\_DUP\\_HANDLER](#); SQLSTATE: [42000](#)  
Message: Duplicate handler declared in the same block
  - Error number: [1414](#); Symbol: [ER\\_SP\\_NOT\\_VAR\\_ARG](#); SQLSTATE: [42000](#)  
Message: OUT or INOUT argument %d for routine %s is not a variable or NEW pseudo-variable in BEFORE trigger
  - Error number: [1415](#); Symbol: [ER\\_SP\\_NO\\_RETSET](#); SQLSTATE: [0A000](#)  
Message: Not allowed to return a result set from a %s
  - Error number: [1416](#); Symbol: [ER\\_CANT\\_CREATE\\_GEOMETRY\\_OBJECT](#); SQLSTATE: [22003](#)  
Message: Cannot get geometry object from data you send to the GEOMETRY field
  - Error number: [1418](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_ROUTINE](#); SQLSTATE: [HY000](#)  
Message: This function has none of DETERMINISTIC, NO SQL, or READS SQL DATA in its declaration and binary logging is enabled (you \*might\* want to use the less safe log\_bin\_trust\_function\_creators variable)
  - Error number: [1419](#); Symbol: [ER\\_BINLOG\\_CREATE\\_ROUTINE\\_NEED\\_SUPER](#); SQLSTATE: [HY000](#)  
Message: You do not have the SUPER privilege and binary logging is enabled (you \*might\* want to use the less safe log\_bin\_trust\_function\_creators variable)
  - Error number: [1421](#); Symbol: [ER\\_STMT\\_HAS\\_NO\\_OPEN\\_CURSOR](#); SQLSTATE: [HY000](#)  
Message: The statement (%lu) has no open cursor.
  - Error number: [1422](#); Symbol: [ER\\_COMMIT\\_NOT\\_ALLOWED\\_IN\\_SF\\_OR\\_TRG](#); SQLSTATE: [HY000](#)  
Message: Explicit or implicit commit is not allowed in stored function or trigger.
  - Error number: [1423](#); Symbol: [ER\\_NO\\_DEFAULT\\_FOR\\_VIEW\\_FIELD](#); SQLSTATE: [HY000](#)  
Message: Field of view '%s.%s' underlying table doesn't have a default value
  - Error number: [1424](#); Symbol: [ER\\_SP\\_NO\\_RECURSION](#); SQLSTATE: [HY000](#)  
Message: Recursive stored functions and triggers are not allowed.

- 
- Error number: 1425; Symbol: `ER_TOO_BIG_SCALE`; SQLSTATE: 42000  
Message: Too big scale %d specified for column '%s'. Maximum is %lu.
  - Error number: 1426; Symbol: `ER_TOO_BIG_PRECISION`; SQLSTATE: 42000  
Message: Too-big precision %d specified for '%s'. Maximum is %lu.
  - Error number: 1427; Symbol: `ER_M_BIGGER_THAN_D`; SQLSTATE: 42000  
Message: For float(M,D), double(M,D) or decimal(M,D), M must be >= D (column '%s').
  - Error number: 1428; Symbol: `ER_WRONG_LOCK_OF_SYSTEM_TABLE`; SQLSTATE: HY000  
Message: You can't combine write-locking of system tables with other tables or lock types
  - Error number: 1429; Symbol: `ER_CONNECT_TO_FOREIGN_DATA_SOURCE`; SQLSTATE: HY000  
Message: Unable to connect to foreign data source: %s
  - Error number: 1430; Symbol: `ER_QUERY_ON_FOREIGN_DATA_SOURCE`; SQLSTATE: HY000  
Message: There was a problem processing the query on the foreign data source. Data source error: %s
  - Error number: 1431; Symbol: `ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST`; SQLSTATE: HY000  
Message: The foreign data source you are trying to reference does not exist. Data source error: %s
  - Error number: 1432; Symbol: `ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE`; SQLSTATE: HY000  
Message: Can't create federated table. The data source connection string '%s' is not in the correct format
  - Error number: 1433; Symbol: `ER_FOREIGN_DATA_STRING_INVALID`; SQLSTATE: HY000  
Message: The data source connection string '%s' is not in the correct format
  - Error number: 1435; Symbol: `ER_TRG_IN_WRONG_SCHEMA`; SQLSTATE: HY000  
Message: Trigger in wrong schema
  - Error number: 1436; Symbol: `ER_STACK_OVERRUN_NEED_MORE`; SQLSTATE: HY000  
Message: Thread stack overrun: %ld bytes used of a %ld byte stack, and %ld bytes needed. Use 'mysqld --thread\_stack=#' to specify a bigger stack.
  - Error number: 1437; Symbol: `ER_TOO_LONG_BODY`; SQLSTATE: 42000  
Message: Routine body for '%s' is too long
  - Error number: 1438; Symbol: `ER_WARN_CANT_DROP_DEFAULT_KEYCACHE`; SQLSTATE: HY000  
Message: Cannot drop default keycache
  - Error number: 1439; Symbol: `ER_TOO_BIG_DISPLAYWIDTH`; SQLSTATE: 42000  
Message: Display width out of range for column '%s' (max = %lu)
  - Error number: 1440; Symbol: `ER_XAER_DUPID`; SQLSTATE: XAE08

---

Message: XAER\_DUPID: The XID already exists

- Error number: 1441; Symbol: `ER_DATETIME_FUNCTION_OVERFLOW`; SQLSTATE: 22008

Message: Datetime function: %s field overflow

- Error number: 1442; Symbol: `ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG`; SQLSTATE: HY000

Message: Can't update table '%s' in stored function/trigger because it is already used by statement which invoked this stored function/trigger.

- Error number: 1443; Symbol: `ER_VIEW_PREVENT_UPDATE`; SQLSTATE: HY000

Message: The definition of table '%s' prevents operation %s on table '%s'.

- Error number: 1444; Symbol: `ER_PS_NO_RECURSION`; SQLSTATE: HY000

Message: The prepared statement contains a stored routine call that refers to that same statement. It's not allowed to execute a prepared statement in such a recursive manner

- Error number: 1445; Symbol: `ER_SP_CANT_SET_AUTOCOMMIT`; SQLSTATE: HY000

Message: Not allowed to set autocommit from a stored function or trigger

- Error number: 1447; Symbol: `ER_VIEW_FRM_NO_USER`; SQLSTATE: HY000

Message: View '%s'.'%s' has no definer information (old table format). Current user is used as definer. Please recreate the view!

- Error number: 1448; Symbol: `ER_VIEW_OTHER_USER`; SQLSTATE: HY000

Message: You need the SUPER privilege for creation view with '%s'@'%s' definer

- Error number: 1449; Symbol: `ER_NO_SUCH_USER`; SQLSTATE: HY000

Message: The user specified as a definer ('%s'@'%s') does not exist

- Error number: 1450; Symbol: `ER_FORBID_SCHEMA_CHANGE`; SQLSTATE: HY000

Message: Changing schema from '%s' to '%s' is not allowed.

- Error number: 1451; Symbol: `ER_ROW_IS_REFERENCED_2`; SQLSTATE: 23000

Message: Cannot delete or update a parent row: a foreign key constraint fails (%s)

[InnoDB](#) reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.

- Error number: 1452; Symbol: `ER_NO_REFERENCED_ROW_2`; SQLSTATE: 23000

Message: Cannot add or update a child row: a foreign key constraint fails (%s)

[InnoDB](#) reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.

- Error number: 1453; Symbol: `ER_SP_BAD_VAR_SHADOW`; SQLSTATE: 42000

Message: Variable '%s' must be quoted with `...`, or renamed



- 
- Error number: [1454](#); Symbol: [ER\\_TRG\\_NO\\_DEFINER](#); SQLSTATE: [HY000](#)  
Message: No definer attribute for trigger '%s'. '%s'. It's disallowed to create trigger without definer.
  - Error number: [1455](#); Symbol: [ER\\_OLD\\_FILE\\_FORMAT](#); SQLSTATE: [HY000](#)  
Message: '%s' has an old format, you should re-create the '%s' object(s)
  - Error number: [1456](#); Symbol: [ER\\_SP\\_RECURSION\\_LIMIT](#); SQLSTATE: [HY000](#)  
Message: Recursive limit %d (as set by the max\_sp\_recursion\_depth variable) was exceeded for routine %s
  - Error number: [1458](#); Symbol: [ER\\_SP\\_WRONG\\_NAME](#); SQLSTATE: [42000](#)  
Message: Incorrect routine name '%s'
  - Error number: [1459](#); Symbol: [ER\\_TABLE\\_NEEDS\\_UPGRADE](#); SQLSTATE: [HY000](#)  
Message: Table upgrade required. Please do "REPAIR TABLE ` %s ` " or dump/reload to fix it!
  - Error number: [1460](#); Symbol: [ER\\_SP\\_NO\\_AGGREGATE](#); SQLSTATE: [42000](#)  
Message: AGGREGATE is not supported for stored functions
  - Error number: [1461](#); Symbol: [ER\\_MAX\\_PREPARED\\_STMT\\_COUNT\\_REACHED](#); SQLSTATE: [42000](#)  
Message: Can't create more than max\_prepared\_stmt\_count statements (current value: %lu)
  - Error number: [1462](#); Symbol: [ER\\_VIEW\\_RECURSIVE](#); SQLSTATE: [HY000](#)  
Message: ` %s `.` %s ` contains view recursion
  - Error number: [1463](#); Symbol: [ER\\_NON\\_GROUPING\\_FIELD\\_USED](#); SQLSTATE: [42000](#)  
Message: Non-grouping field '%s' is used in %s clause
  - Error number: [1464](#); Symbol: [ER\\_TABLE\\_CANT\\_HANDLE\\_SPKEYS](#); SQLSTATE: [HY000](#)  
Message: The used table type doesn't support SPATIAL indexes
  - Error number: [1465](#); Symbol: [ER\\_NO\\_TRIGGERS\\_ON\\_SYSTEM\\_SCHEMA](#); SQLSTATE: [HY000](#)  
Message: Triggers can not be created on system tables
  - Error number: [1466](#); Symbol: [ER\\_REMOVED\\_SPACES](#); SQLSTATE: [HY000](#)  
Message: Leading spaces are removed from name '%s'
  - Error number: [1467](#); Symbol: [ER\\_AUTOINC\\_READ\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to read auto-increment value from storage engine
  - Error number: [1468](#); Symbol: [ER\\_USERNAME](#); SQLSTATE: [HY000](#)  
Message: user name
  - Error number: [1469](#); Symbol: [ER\\_HOSTNAME](#); SQLSTATE: [HY000](#)  
Message: host name

- 
- Error number: 1470; Symbol: [ER\\_WRONG\\_STRING\\_LENGTH](#); SQLSTATE: HY000  
Message: String '%s' is too long for %s (should be no longer than %d)
  - Error number: 1471; Symbol: [ER\\_NON\\_INSERTABLE\\_TABLE](#); SQLSTATE: HY000  
Message: The target table %s of the %s is not insertable-into
  - Error number: 1472; Symbol: [ER\\_ADMIN\\_WRONG\\_MRG\\_TABLE](#); SQLSTATE: HY000  
Message: Table '%s' is differently defined or of non-MyISAM type or doesn't exist
  - Error number: 1473; Symbol: [ER\\_TOO\\_HIGH\\_LEVEL\\_OF\\_NESTING\\_FOR\\_SELECT](#); SQLSTATE: HY000  
Message: Too high level of nesting for select
  - Error number: 1474; Symbol: [ER\\_NAME\\_BECOMES\\_EMPTY](#); SQLSTATE: HY000  
Message: Name '%s' has become "
  - Error number: 1475; Symbol: [ER\\_AMBIGUOUS\\_FIELD\\_TERM](#); SQLSTATE: HY000  
Message: First character of the FIELDS TERMINATED string is ambiguous; please use non-optional and non-empty FIELDS ENCLOSED BY
  - Error number: 1476; Symbol: [ER\\_FOREIGN\\_SERVER\\_EXISTS](#); SQLSTATE: HY000  
Message: The foreign server, %s, you are trying to create already exists.
  - Error number: 1477; Symbol: [ER\\_FOREIGN\\_SERVER\\_DOESNT\\_EXIST](#); SQLSTATE: HY000  
Message: The foreign server name you are trying to reference does not exist. Data source error: %s
  - Error number: 1478; Symbol: [ER\\_ILLEGAL\\_HA\\_CREATE\\_OPTION](#); SQLSTATE: HY000  
Message: Table storage engine '%s' does not support the create option '%s'
  - Error number: 1479; Symbol: [ER\\_PARTITION\\_REQUIRES\\_VALUES\\_ERROR](#); SQLSTATE: HY000  
Message: Syntax error: %s PARTITIONING requires definition of VALUES %s for each partition
  - Error number: 1480; Symbol: [ER\\_PARTITION\\_WRONG\\_VALUES\\_ERROR](#); SQLSTATE: HY000  
Message: Only %s PARTITIONING can use VALUES %s in partition definition
  - Error number: 1481; Symbol: [ER\\_PARTITION\\_MAXVALUE\\_ERROR](#); SQLSTATE: HY000  
Message: MAXVALUE can only be used in last partition definition
  - Error number: 1484; Symbol: [ER\\_PARTITION\\_WRONG\\_NO\\_PART\\_ERROR](#); SQLSTATE: HY000  
Message: Wrong number of partitions defined, mismatch with previous setting
  - Error number: 1485; Symbol: [ER\\_PARTITION\\_WRONG\\_NO\\_SUBPART\\_ERROR](#); SQLSTATE: HY000  
Message: Wrong number of subpartitions defined, mismatch with previous setting
  - Error number: 1486; Symbol: [ER\\_WRONG\\_EXPR\\_IN\\_PARTITION\\_FUNC\\_ERROR](#); SQLSTATE: HY000  
Message: Constant, random or timezone-dependent expressions in (sub)partitioning function are not allowed

- 
- Error number: 1488; Symbol: [ER\\_FIELD\\_NOT\\_FOUND\\_PART\\_ERROR](#); SQLSTATE: HY000  
Message: Field in list of fields for partition function not found in table
  - Error number: 1490; Symbol: [ER\\_INCONSISTENT\\_PARTITION\\_INFO\\_ERROR](#); SQLSTATE: HY000  
Message: The partition info in the frm file is not consistent with what can be written into the frm file
  - Error number: 1491; Symbol: [ER\\_PARTITION\\_FUNC\\_NOT\\_ALLOWED\\_ERROR](#); SQLSTATE: HY000  
Message: The %s function returns the wrong type
  - Error number: 1492; Symbol: [ER\\_PARTITIONS\\_MUST\\_BE\\_DEFINED\\_ERROR](#); SQLSTATE: HY000  
Message: For %s partitions each partition must be defined
  - Error number: 1493; Symbol: [ER\\_RANGE\\_NOT\\_INCREASING\\_ERROR](#); SQLSTATE: HY000  
Message: VALUES LESS THAN value must be strictly increasing for each partition
  - Error number: 1494; Symbol: [ER\\_INCONSISTENT\\_TYPE\\_OF\\_FUNCTIONS\\_ERROR](#); SQLSTATE: HY000  
Message: VALUES value must be of same type as partition function
  - Error number: 1495; Symbol: [ER\\_MULTIPLE\\_DEF\\_CONST\\_IN\\_LIST\\_PART\\_ERROR](#); SQLSTATE: HY000  
Message: Multiple definition of same constant in list partitioning
  - Error number: 1496; Symbol: [ER\\_PARTITION\\_ENTRY\\_ERROR](#); SQLSTATE: HY000  
Message: Partitioning can not be used stand-alone in query
  - Error number: 1497; Symbol: [ER\\_MIX\\_HANDLER\\_ERROR](#); SQLSTATE: HY000  
Message: The mix of handlers in the partitions is not allowed in this version of MySQL
  - Error number: 1498; Symbol: [ER\\_PARTITION\\_NOT\\_DEFINED\\_ERROR](#); SQLSTATE: HY000  
Message: For the partitioned engine it is necessary to define all %s
  - Error number: 1499; Symbol: [ER\\_TOO\\_MANY\\_PARTITIONS\\_ERROR](#); SQLSTATE: HY000  
Message: Too many partitions (including subpartitions) were defined
  - Error number: 1500; Symbol: [ER\\_SUBPARTITION\\_ERROR](#); SQLSTATE: HY000  
Message: It is only possible to mix RANGE/LIST partitioning with HASH/KEY partitioning for subpartitioning
  - Error number: 1501; Symbol: [ER\\_CANT\\_CREATE\\_HANDLER\\_FILE](#); SQLSTATE: HY000  
Message: Failed to create specific handler file
  - Error number: 1502; Symbol: [ER\\_BLOB\\_FIELD\\_IN\\_PART\\_FUNC\\_ERROR](#); SQLSTATE: HY000  
Message: A BLOB field is not allowed in partition function
  - Error number: 1503; Symbol: [ER\\_UNIQUE\\_KEY\\_NEED\\_ALL\\_FIELDS\\_IN\\_PF](#); SQLSTATE: HY000

---

Message: A %s must include all columns in the table's partitioning function (prefixed columns are not considered).

- Error number: 1504; Symbol: ER\_NO\_PARTS\_ERROR; SQLSTATE: HY000

Message: Number of %s = 0 is not an allowed value

- Error number: 1505; Symbol: ER\_PARTITION\_MGMT\_ON\_NONPARTITIONED; SQLSTATE: HY000

Message: Partition management on a not partitioned table is not possible

- Error number: 1506; Symbol: ER\_FOREIGN\_KEY\_ON\_PARTITIONED; SQLSTATE: HY000

Message: Foreign keys are not yet supported in conjunction with partitioning

- Error number: 1507; Symbol: ER\_DROP\_PARTITION\_NON\_EXISTENT; SQLSTATE: HY000

Message: Error in list of partitions to %s

- Error number: 1508; Symbol: ER\_DROP\_LAST\_PARTITION; SQLSTATE: HY000

Message: Cannot remove all partitions, use DROP TABLE instead

- Error number: 1509; Symbol: ER\_COALESCE\_ONLY\_ON\_HASH\_PARTITION; SQLSTATE: HY000

Message: COALESCE PARTITION can only be used on HASH/KEY partitions

- Error number: 1510; Symbol: ER\_REORG\_HASH\_ONLY\_ON\_SAME\_NO; SQLSTATE: HY000

Message: REORGANIZE PARTITION can only be used to reorganize partitions not to change their numbers

- Error number: 1511; Symbol: ER\_REORG\_NO\_PARAM\_ERROR; SQLSTATE: HY000

Message: REORGANIZE PARTITION without parameters can only be used on auto-partitioned tables using HASH PARTITIONS

- Error number: 1512; Symbol: ER\_ONLY\_ON\_RANGE\_LIST\_PARTITION; SQLSTATE: HY000

Message: %s PARTITION can only be used on RANGE/LIST partitions

- Error number: 1513; Symbol: ER\_ADD\_PARTITION\_SUBPART\_ERROR; SQLSTATE: HY000

Message: Trying to Add partition(s) with wrong number of subpartitions

- Error number: 1514; Symbol: ER\_ADD\_PARTITION\_NO\_NEW\_PARTITION; SQLSTATE: HY000

Message: At least one partition must be added

- Error number: 1515; Symbol: ER\_COALESCE\_PARTITION\_NO\_PARTITION; SQLSTATE: HY000

Message: At least one partition must be coalesced

- Error number: 1516; Symbol: ER\_REORG\_PARTITION\_NOT\_EXIST; SQLSTATE: HY000

Message: More partitions to reorganize than there are partitions

- Error number: 1517; Symbol: ER\_SAME\_NAME\_PARTITION; SQLSTATE: HY000

Message: Duplicate partition name %s

- 
- Error number: 1518; Symbol: `ER_NO_BINLOG_ERROR`; SQLSTATE: `HY000`  
Message: It is not allowed to shut off binlog on this command
  - Error number: 1519; Symbol: `ER_CONSECUTIVE_REORG_PARTITIONS`; SQLSTATE: `HY000`  
Message: When reorganizing a set of partitions they must be in consecutive order
  - Error number: 1520; Symbol: `ER_REORG_OUTSIDE_RANGE`; SQLSTATE: `HY000`  
Message: Reorganize of range partitions cannot change total ranges except for last partition where it can extend the range
  - Error number: 1521; Symbol: `ER_PARTITION_FUNCTION_FAILURE`; SQLSTATE: `HY000`  
Message: Partition function not supported in this version for this handler
  - Error number: 1523; Symbol: `ER_LIMITED_PART_RANGE`; SQLSTATE: `HY000`  
Message: The %s handler only supports 32 bit integers in VALUES
  - Error number: 1524; Symbol: `ER_PLUGIN_IS_NOT_LOADED`; SQLSTATE: `HY000`  
Message: Plugin '%s' is not loaded
  - Error number: 1525; Symbol: `ER_WRONG_VALUE`; SQLSTATE: `HY000`  
Message: Incorrect %s value: '%s'
  - Error number: 1526; Symbol: `ER_NO_PARTITION_FOR_GIVEN_VALUE`; SQLSTATE: `HY000`  
Message: Table has no partition for value %s
  - Error number: 1527; Symbol: `ER_FILEGROUP_OPTION_ONLY_ONCE`; SQLSTATE: `HY000`  
Message: It is not allowed to specify %s more than once
  - Error number: 1528; Symbol: `ER_CREATE_FILEGROUP_FAILED`; SQLSTATE: `HY000`  
Message: Failed to create %s
  - Error number: 1529; Symbol: `ER_DROP_FILEGROUP_FAILED`; SQLSTATE: `HY000`  
Message: Failed to drop %s
  - Error number: 1530; Symbol: `ER_TABLESPACE_AUTO_EXTEND_ERROR`; SQLSTATE: `HY000`  
Message: The handler doesn't support autoextend of tablespaces
  - Error number: 1531; Symbol: `ER_WRONG_SIZE_NUMBER`; SQLSTATE: `HY000`  
Message: A size parameter was incorrectly specified, either number or on the form 10M
  - Error number: 1532; Symbol: `ER_SIZE_OVERFLOW_ERROR`; SQLSTATE: `HY000`  
Message: The size number was correct but we don't allow the digit part to be more than 2 billion
  - Error number: 1533; Symbol: `ER_ALTER_FILEGROUP_FAILED`; SQLSTATE: `HY000`  
Message: Failed to alter: %s

- 
- Error number: [1534](#); Symbol: [ER\\_BINLOG\\_ROW\\_LOGGING\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Writing one row to the row-based binary log failed
  - Error number: [1537](#); Symbol: [ER\\_EVENT\\_ALREADY\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Event '%s' already exists
  - Error number: [1539](#); Symbol: [ER\\_EVENT\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
Message: Unknown event '%s'
  - Error number: [1542](#); Symbol: [ER\\_EVENT\\_INTERVAL\\_NOT\\_POSITIVE\\_OR\\_TOO\\_BIG](#); SQLSTATE: [HY000](#)  
Message: INTERVAL is either not positive or too big
  - Error number: [1543](#); Symbol: [ER\\_EVENT\\_ENDS\\_BEFORE\\_STARTS](#); SQLSTATE: [HY000](#)  
Message: ENDS is either invalid or before STARTS
  - Error number: [1544](#); Symbol: [ER\\_EVENT\\_EXEC\\_TIME\\_IN\\_THE\\_PAST](#); SQLSTATE: [HY000](#)  
Message: Event execution time is in the past. Event has been disabled
  - Error number: [1551](#); Symbol: [ER\\_EVENT\\_SAME\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Same old and new event name
  - Error number: [1553](#); Symbol: [ER\\_DROP\\_INDEX\\_FK](#); SQLSTATE: [HY000](#)  
Message: Cannot drop index '%s': needed in a foreign key constraint  
[InnoDB](#) reports this error when you attempt to drop the last index that can enforce a particular referential constraint.  
  
For optimal performance with DML statements, [InnoDB](#) requires an index to exist on [foreign key](#) columns, so that [UPDATE](#) and [DELETE](#) operations on a [parent table](#) can easily check whether corresponding rows exist in the [child table](#). MySQL creates or drops such indexes automatically when needed, as a side-effect of [CREATE TABLE](#), [CREATE INDEX](#), and [ALTER TABLE](#) statements.  
  
When you drop an index, [InnoDB](#) checks if the index is used for checking a foreign key constraint. It is still OK to drop the index if there is another index that can be used to enforce the same constraint. [InnoDB](#) prevents you from dropping the last index that can enforce a particular referential constraint.
  - Error number: [1554](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_SYNTAX\\_WITH\\_VER](#); SQLSTATE: [HY000](#)  
Message: The syntax '%s' is deprecated and will be removed in MySQL %s. Please use %s instead
  - Error number: [1556](#); Symbol: [ER\\_CANT\\_LOCK\\_LOG\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: You can't use locks with log tables.
  - Error number: [1557](#); Symbol: [ER\\_FOREIGN\\_DUPLICATE\\_KEY\\_OLD\\_UNUSED](#); SQLSTATE: [23000](#)  
Message: Upholding foreign key constraints for table '%s', entry '%s', key %d would lead to a duplicate entry
  - Error number: [1558](#); Symbol: [ER\\_COL\\_COUNT\\_DoesNT\\_MATCH\\_PLEASE\\_UPDATE](#); SQLSTATE: [HY000](#)

---

Message: The column count of mysql.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

- Error number: 1559; Symbol: ER\_TEMP\_TABLE\_PREVENTS\_SWITCH\_OUT\_OF\_RBR; SQLSTATE: HY000

Message: Cannot switch out of the row-based binary log format when the session has open temporary tables

ER\_TEMP\_TABLE\_PREVENTS\_SWITCH\_OUT\_OF\_RBR was removed after 8.0.12.

- Error number: 1560; Symbol: ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_BINLOG\_FORMAT; SQLSTATE: HY000

Message: Cannot change the binary logging format inside a stored function or trigger

- Error number: 1562; Symbol: ER\_PARTITION\_NO\_TEMPORARY; SQLSTATE: HY000

Message: Cannot create temporary table with partitions

- Error number: 1563; Symbol: ER\_PARTITION\_CONST\_DOMAIN\_ERROR; SQLSTATE: HY000

Message: Partition constant is out of partition function domain

- Error number: 1564; Symbol: ER\_PARTITION\_FUNCTION\_IS\_NOT\_ALLOWED; SQLSTATE: HY000

Message: This partition function is not allowed

- Error number: 1565; Symbol: ER\_DDL\_LOG\_ERROR; SQLSTATE: HY000

Message: Error in DDL log

ER\_DDL\_LOG\_ERROR was removed after 8.0.1.

- Error number: 1566; Symbol: ER\_NULL\_IN\_VALUES\_LESS\_THAN; SQLSTATE: HY000

Message: Not allowed to use NULL value in VALUES LESS THAN

- Error number: 1567; Symbol: ER\_WRONG\_PARTITION\_NAME; SQLSTATE: HY000

Message: Incorrect partition name

- Error number: 1568; Symbol: ER\_CANT\_CHANGE\_TX\_CHARACTERISTICS; SQLSTATE: 25001

Message: Transaction characteristics can't be changed while a transaction is in progress

- Error number: 1569; Symbol: ER\_DUP\_ENTRY\_AUTOINCREMENT\_CASE; SQLSTATE: HY000

Message: ALTER TABLE causes auto\_increment resequencing, resulting in duplicate entry '%s' for key '%s'

- Error number: 1571; Symbol: ER\_EVENT\_SET\_VAR\_ERROR; SQLSTATE: HY000

Message: Error during starting/stopping of the scheduler. Error code %u

- Error number: 1572; Symbol: ER\_PARTITION\_MERGE\_ERROR; SQLSTATE: HY000

Message: Engine cannot be used in partitioned tables

- 
- Error number: [1575](#); Symbol: [ER\\_BASE64\\_DECODE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Decoding of base64 string failed
  - Error number: [1576](#); Symbol: [ER\\_EVENT\\_RECURSION\\_FORBIDDEN](#); SQLSTATE: [HY000](#)  
Message: Recursion of EVENT DDL statements is forbidden when body is present
  - Error number: [1578](#); Symbol: [ER\\_ONLY\\_INTEGERS\\_ALLOWED](#); SQLSTATE: [HY000](#)  
Message: Only integers allowed as number here
  - Error number: [1579](#); Symbol: [ER\\_UNSUPPORTED\\_LOG\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: This storage engine cannot be used for log tables
  - Error number: [1580](#); Symbol: [ER\\_BAD\\_LOG\\_STATEMENT](#); SQLSTATE: [HY000](#)  
Message: You cannot '%s' a log table if logging is enabled
  - Error number: [1581](#); Symbol: [ER\\_CANT\\_RENAME\\_LOG\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot rename '%s'. When logging enabled, rename to/from log table must rename two tables: the log table to an archive table and another table back to '%s'
  - Error number: [1582](#); Symbol: [ER\\_WRONG\\_PARAMCOUNT\\_TO\\_NATIVE\\_FCT](#); SQLSTATE: [42000](#)  
Message: Incorrect parameter count in the call to native function '%s'
  - Error number: [1583](#); Symbol: [ER\\_WRONG\\_PARAMETERS\\_TO\\_NATIVE\\_FCT](#); SQLSTATE: [42000](#)  
Message: Incorrect parameters in the call to native function '%s'
  - Error number: [1584](#); Symbol: [ER\\_WRONG\\_PARAMETERS\\_TO\\_STORED\\_FCT](#); SQLSTATE: [42000](#)  
Message: Incorrect parameters in the call to stored function %s
  - Error number: [1585](#); Symbol: [ER\\_NATIVE\\_FCT\\_NAME\\_COLLISION](#); SQLSTATE: [HY000](#)  
Message: This function '%s' has the same name as a native function
  - Error number: [1586](#); Symbol: [ER\\_DUP\\_ENTRY\\_WITH\\_KEY\\_NAME](#); SQLSTATE: [23000](#)  
Message: Duplicate entry '%s' for key '%s'  
The format string for this error is also used with [ER\\_DUP\\_ENTRY](#).
  - Error number: [1587](#); Symbol: [ER\\_BINLOG\\_PURGE\\_EMFILE](#); SQLSTATE: [HY000](#)  
Message: Too many files opened, please execute the command again
  - Error number: [1588](#); Symbol: [ER\\_EVENT\\_CANNOT\\_CREATE\\_IN\\_THE\\_PAST](#); SQLSTATE: [HY000](#)  
Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was dropped immediately after creation.
  - Error number: [1589](#); Symbol: [ER\\_EVENT\\_CANNOT\\_ALTER\\_IN\\_THE\\_PAST](#); SQLSTATE: [HY000](#)  
Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was not changed. Specify a time in the future.



- 
- Error number: [1591](#); Symbol: [ER\\_NO\\_PARTITION\\_FOR\\_GIVEN\\_VALUE\\_SILENT](#); SQLSTATE: [HY000](#)  
Message: Table has no partition for some existing values
  - Error number: [1592](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_STATEMENT](#); SQLSTATE: [HY000](#)  
Message: Unsafe statement written to the binary log using statement format since BINLOG\_FORMAT = STATEMENT. %s
  - Error number: [1593](#); Symbol: [ER\\_BINLOG\\_FATAL\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Fatal error: %s  
[ER\\_BINLOG\\_FATAL\\_ERROR](#) was added in 8.0.11.
  - Error number: [1598](#); Symbol: [ER\\_BINLOG\\_LOGGING\\_IMPOSSIBLE](#); SQLSTATE: [HY000](#)  
Message: Binary logging not possible. Message: %s
  - Error number: [1599](#); Symbol: [ER\\_VIEW\\_NO\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: View `%s`.`%s` has no creation context
  - Error number: [1600](#); Symbol: [ER\\_VIEW\\_INVALID\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: Creation context of view `%s`.`%s` is invalid
  - Error number: [1602](#); Symbol: [ER\\_TRG\\_CORRUPTED\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Corrupted TRG file for table `%s`.`%s`
  - Error number: [1603](#); Symbol: [ER\\_TRG\\_NO\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: Triggers for table `%s`.`%s` have no creation context
  - Error number: [1604](#); Symbol: [ER\\_TRG\\_INVALID\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: Trigger creation context of table `%s`.`%s` is invalid
  - Error number: [1605](#); Symbol: [ER\\_EVENT\\_INVALID\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: Creation context of event `%s`.`%s` is invalid
  - Error number: [1606](#); Symbol: [ER\\_TRG\\_CANT\\_OPEN\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot open table for trigger `%s`.`%s`
  - Error number: [1609](#); Symbol: [ER\\_NO\\_FORMAT\\_DESCRIPTION\\_EVENT\\_BEFORE\\_BINLOG\\_STATEMENT](#); SQLSTATE: [HY000](#)  
Message: The BINLOG statement of type `%s` was not preceded by a format description BINLOG statement.
  - Error number: [1610](#); Symbol: [ER\\_SLAVE\\_CORRUPT\\_EVENT](#); SQLSTATE: [HY000](#)  
Message: Corrupted replication event was detected  
[ER\\_SLAVE\\_CORRUPT\\_EVENT](#) was removed after 8.0.32.
  - Error number: [1610](#); Symbol: [ER\\_REPLICA\\_CORRUPT\\_EVENT](#); SQLSTATE: [HY000](#)
-

---

Message: Corrupted replication event was detected

[ER\\_REPLICA\\_CORRUPT\\_EVENT](#) was added in 8.0.33.

- Error number: 1612; Symbol: [ER\\_LOG\\_PURGE\\_NO\\_FILE](#); SQLSTATE: HY000

Message: Being purged log %s was not found

- Error number: 1613; Symbol: [ER\\_XA\\_RBTIMEOUT](#); SQLSTATE: XA106

Message: XA\_RBTIMEOUT: Transaction branch was rolled back: took too long

- Error number: 1614; Symbol: [ER\\_XA\\_RBDEADLOCK](#); SQLSTATE: XA102

Message: XA\_RBDEADLOCK: Transaction branch was rolled back: deadlock was detected

- Error number: 1615; Symbol: [ER\\_NEED\\_REPREPARE](#); SQLSTATE: HY000

Message: Prepared statement needs to be re-prepared

- Error number: 1617; Symbol: [WARN\\_NO\\_MASTER\\_INFO](#); SQLSTATE: HY000

Message: The master info structure does not exist

[WARN\\_NO\\_MASTER\\_INFO](#) was removed after 8.0.32.

- Error number: 1617; Symbol: [WARN\\_NO\\_CONNECTION\\_METADATA](#); SQLSTATE: HY000

Message: The connection metadata structure does not exist

[WARN\\_NO\\_CONNECTION\\_METADATA](#) was added in 8.0.33.

- Error number: 1618; Symbol: [WARN\\_OPTION\\_IGNORED](#); SQLSTATE: HY000

Message: <%s> option ignored

- Error number: 1619; Symbol: [ER\\_PLUGIN\\_DELETE\\_BUILTIN](#); SQLSTATE: HY000

Message: Built-in plugins cannot be deleted

- Error number: 1620; Symbol: [WARN\\_PLUGIN\\_BUSY](#); SQLSTATE: HY000

Message: Plugin is busy and will be uninstalled on shutdown

- Error number: 1621; Symbol: [ER\\_VARIABLE\\_IS\\_READONLY](#); SQLSTATE: HY000

Message: %s variable '%s' is read-only. Use SET %s to assign the value

- Error number: 1622; Symbol: [ER\\_WARN\\_ENGINE\\_TRANSACTION\\_ROLLBACK](#); SQLSTATE: HY000

Message: Storage engine %s does not support rollback for this statement. Transaction rolled back and must be restarted

- Error number: 1624; Symbol: [ER\\_SLAVE\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: HY000

Message: The requested value for the heartbeat period is either negative or exceeds the maximum allowed (%s seconds).

[ER\\_SLAVE\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE](#) was removed after 8.0.32.

- 
- Error number: [1624](#); Symbol: [ER\\_REPLICA\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [HY000](#)  
Message: The requested value for the heartbeat period is either negative or exceeds the maximum allowed (%s seconds).  
[ER\\_REPLICA\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE](#) was added in 8.0.33.
  - Error number: [1625](#); Symbol: [ER\\_NDB\\_REPLICATION\\_SCHEMA\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Bad schema for mysql.ndb\_replication table. Message: %s
  - Error number: [1626](#); Symbol: [ER\\_CONFLICT\\_FN\\_PARSE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error in parsing conflict function. Message: %s
  - Error number: [1627](#); Symbol: [ER\\_EXCEPTIONS\\_WRITE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Write to exceptions table failed. Message: %s
  - Error number: [1628](#); Symbol: [ER\\_TOO\\_LONG\\_TABLE\\_COMMENT](#); SQLSTATE: [HY000](#)  
Message: Comment for table '%s' is too long (max = %lu)
  - Error number: [1629](#); Symbol: [ER\\_TOO\\_LONG\\_FIELD\\_COMMENT](#); SQLSTATE: [HY000](#)  
Message: Comment for field '%s' is too long (max = %lu)
  - Error number: [1630](#); Symbol: [ER\\_FUNC\\_INEXISTENT\\_NAME\\_COLLISION](#); SQLSTATE: [42000](#)  
Message: FUNCTION %s does not exist. Check the 'Function Name Parsing and Resolution' section in the Reference Manual
  - Error number: [1631](#); Symbol: [ER\\_DATABASE\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Database
  - Error number: [1632](#); Symbol: [ER\\_TABLE\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Table
  - Error number: [1633](#); Symbol: [ER\\_PARTITION\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Partition
  - Error number: [1634](#); Symbol: [ER\\_SUBPARTITION\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Subpartition
  - Error number: [1635](#); Symbol: [ER\\_TEMPORARY\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Temporary
  - Error number: [1636](#); Symbol: [ER\\_RENAMED\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Renamed
  - Error number: [1637](#); Symbol: [ER\\_TOO\\_MANY\\_CONCURRENT\\_TRXS](#); SQLSTATE: [HY000](#)  
Message: Too many active concurrent transactions

- 
- Error number: 1638; Symbol: `WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED`; SQLSTATE: `HY000`  
Message: Non-ASCII separator arguments are not fully supported
  - Error number: 1639; Symbol: `ER_DEBUG_SYNC_TIMEOUT`; SQLSTATE: `HY000`  
Message: debug sync point wait timed out
  - Error number: 1640; Symbol: `ER_DEBUG_SYNC_HIT_LIMIT`; SQLSTATE: `HY000`  
Message: debug sync point hit limit reached
  - Error number: 1641; Symbol: `ER_DUP_SIGNAL_SET`; SQLSTATE: `42000`  
Message: Duplicate condition information item '%s'
  - Error number: 1642; Symbol: `ER_SIGNAL_WARN`; SQLSTATE: `01000`  
Message: Unhandled user-defined warning condition
  - Error number: 1643; Symbol: `ER_SIGNAL_NOT_FOUND`; SQLSTATE: `02000`  
Message: Unhandled user-defined not found condition
  - Error number: 1644; Symbol: `ER_SIGNAL_EXCEPTION`; SQLSTATE: `HY000`  
Message: Unhandled user-defined exception condition
  - Error number: 1645; Symbol: `ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER`; SQLSTATE: `0K000`  
Message: RESIGNAL when handler not active
  - Error number: 1646; Symbol: `ER_SIGNAL_BAD_CONDITION_TYPE`; SQLSTATE: `HY000`  
Message: SIGNAL/RESIGNAL can only use a CONDITION defined with SQLSTATE
  - Error number: 1647; Symbol: `WARN_COND_ITEM_TRUNCATED`; SQLSTATE: `HY000`  
Message: Data truncated for condition item '%s'
  - Error number: 1648; Symbol: `ER_COND_ITEM_TOO_LONG`; SQLSTATE: `HY000`  
Message: Data too long for condition item '%s'
  - Error number: 1649; Symbol: `ER_UNKNOWN_LOCALE`; SQLSTATE: `HY000`  
Message: Unknown locale: '%s'
  - Error number: 1650; Symbol: `ER_SLAVE_IGNORE_SERVER_IDS`; SQLSTATE: `HY000`  
Message: The requested server id %d clashes with the slave startup option --replicate-same-server-id  
`ER_SLAVE_IGNORE_SERVER_IDS` was removed after 8.0.32.
  - Error number: 1650; Symbol: `ER_REPLICA_IGNORE_SERVER_IDS`; SQLSTATE: `HY000`  
Message: The requested server id %d clashes with the replica startup option --replicate-same-server-id  
`ER_REPLICA_IGNORE_SERVER_IDS` was added in 8.0.33.

- 
- Error number: 1651; Symbol: [ER\\_QUERY\\_CACHE\\_DISABLED](#); SQLSTATE: HY000  
Message: Query cache is disabled; restart the server with query\_cache\_type=1 to enable it  
[ER\\_QUERY\\_CACHE\\_DISABLED](#) was removed after 8.0.2.
  - Error number: 1652; Symbol: [ER\\_SAME\\_NAME\\_PARTITION\\_FIELD](#); SQLSTATE: HY000  
Message: Duplicate partition field name '%s'
  - Error number: 1653; Symbol: [ER\\_PARTITION\\_COLUMN\\_LIST\\_ERROR](#); SQLSTATE: HY000  
Message: Inconsistency in usage of column lists for partitioning
  - Error number: 1654; Symbol: [ER\\_WRONG\\_TYPE\\_COLUMN\\_VALUE\\_ERROR](#); SQLSTATE: HY000  
Message: Partition column values of incorrect type
  - Error number: 1655; Symbol: [ER\\_TOO\\_MANY\\_PARTITION\\_FUNC\\_FIELDS\\_ERROR](#); SQLSTATE: HY000  
Message: Too many fields in '%s'
  - Error number: 1656; Symbol: [ER\\_MAXVALUE\\_IN\\_VALUES\\_IN](#); SQLSTATE: HY000  
Message: Cannot use MAXVALUE as value in VALUES IN
  - Error number: 1657; Symbol: [ER\\_TOO\\_MANY\\_VALUES\\_ERROR](#); SQLSTATE: HY000  
Message: Cannot have more than one value for this type of %s partitioning
  - Error number: 1658; Symbol: [ER\\_ROW\\_SINGLE\\_PARTITION\\_FIELD\\_ERROR](#); SQLSTATE: HY000  
Message: Row expressions in VALUES IN only allowed for multi-field column partitioning
  - Error number: 1659; Symbol: [ER\\_FIELD\\_TYPE\\_NOT\\_ALLOWED\\_AS\\_PARTITION\\_FIELD](#); SQLSTATE: HY000  
Message: Field '%s' is of a not allowed type for this type of partitioning
  - Error number: 1660; Symbol: [ER\\_PARTITION\\_FIELDS\\_TOO\\_LONG](#); SQLSTATE: HY000  
Message: The total length of the partitioning fields is too large
  - Error number: 1661; Symbol: [ER\\_BINLOG\\_ROW\\_ENGINE\\_AND\\_STMT\\_ENGINE](#); SQLSTATE: HY000  
Message: Cannot execute statement: impossible to write to binary log since both row-incapable engines and statement-incapable engines are involved.
  - Error number: 1662; Symbol: [ER\\_BINLOG\\_ROW\\_MODE\\_AND\\_STMT\\_ENGINE](#); SQLSTATE: HY000  
Message: Cannot execute statement: impossible to write to binary log since BINLOG\_FORMAT = ROW and at least one table uses a storage engine limited to statement-based logging.
  - Error number: 1663; Symbol: [ER\\_BINLOG\\_UNSAFE\\_AND\\_STMT\\_ENGINE](#); SQLSTATE: HY000  
Message: Cannot execute statement: impossible to write to binary log since statement is unsafe, storage engine is limited to statement-based logging, and BINLOG\_FORMAT = MIXED. %s
  - Error number: 1664; Symbol: [ER\\_BINLOG\\_ROW\\_INJECTION\\_AND\\_STMT\\_ENGINE](#); SQLSTATE: HY000

---

Message: Cannot execute statement: impossible to write to binary log since statement is in row format and at least one table uses a storage engine limited to statement-based logging.

- Error number: 1665; Symbol: `ER_BINLOG_STMT_MODE_AND_ROW_ENGINE`; SQLSTATE: `HY000`

Message: Cannot execute statement: impossible to write to binary log since `BINLOG_FORMAT = STATEMENT` and at least one table uses a storage engine limited to row-based logging. %s

- Error number: 1666; Symbol: `ER_BINLOG_ROW_INJECTION_AND_STMT_MODE`; SQLSTATE: `HY000`

Message: Cannot execute statement: impossible to write to binary log since statement is in row format and `BINLOG_FORMAT = STATEMENT`.

- Error number: 1667; Symbol: `ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE`; SQLSTATE: `HY000`

Message: Cannot execute statement: impossible to write to binary log since more than one engine is involved and at least one engine is self-logging.

- Error number: 1668; Symbol: `ER_BINLOG_UNSAFE_LIMIT`; SQLSTATE: `HY000`

Message: The statement is unsafe because it uses a `LIMIT` clause. This is unsafe because the set of rows included cannot be predicted.

- Error number: 1670; Symbol: `ER_BINLOG_UNSAFE_SYSTEM_TABLE`; SQLSTATE: `HY000`

Message: The statement is unsafe because it uses the general log, slow query log, or `performance_schema` table(s). This is unsafe because system tables may differ on replicas.

- Error number: 1671; Symbol: `ER_BINLOG_UNSAFE_AUTOINC_COLUMNS`; SQLSTATE: `HY000`

Message: Statement is unsafe because it invokes a trigger or a stored function that inserts into an `AUTO_INCREMENT` column. Inserted values cannot be logged correctly.

- Error number: 1672; Symbol: `ER_BINLOG_UNSAFE_UDF`; SQLSTATE: `HY000`

Message: Statement is unsafe because it uses a UDF which may not return the same value on the replica.

- Error number: 1673; Symbol: `ER_BINLOG_UNSAFE_SYSTEM_VARIABLE`; SQLSTATE: `HY000`

Message: Statement is unsafe because it uses a system variable that may have a different value on the replica.

- Error number: 1674; Symbol: `ER_BINLOG_UNSAFE_SYSTEM_FUNCTION`; SQLSTATE: `HY000`

Message: Statement is unsafe because it uses a system function that may return a different value on the replica.

- Error number: 1675; Symbol: `ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS`; SQLSTATE: `HY000`

Message: Statement is unsafe because it accesses a non-transactional table after accessing a transactional table within the same transaction.

- Error number: 1676; Symbol: `ER_MESSAGE_AND_STATEMENT`; SQLSTATE: `HY000`

Message: %s Statement: %s

- 
- Error number: 1677; Symbol: [ER\\_SLAVE\\_CONVERSION\\_FAILED](#); SQLSTATE: HY000  
Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'  
[ER\\_SLAVE\\_CONVERSION\\_FAILED](#) was removed after 8.0.4.
  - Error number: 1678; Symbol: [ER\\_SLAVE\\_CANT\\_CREATE\\_CONVERSION](#); SQLSTATE: HY000  
Message: Can't create conversion table for table '%s.%s'  
[ER\\_SLAVE\\_CANT\\_CREATE\\_CONVERSION](#) was removed after 8.0.32.
  - Error number: 1678; Symbol: [ER\\_REPLICA\\_CANT\\_CREATE\\_CONVERSION](#); SQLSTATE: HY000  
Message: Can't create conversion table for table '%s.%s'  
[ER\\_REPLICA\\_CANT\\_CREATE\\_CONVERSION](#) was added in 8.0.33.
  - Error number: 1679; Symbol: [ER\\_INSIDE\\_TRANSACTION\\_PREVENTS\\_SWITCH\\_BINLOG\\_FORMAT](#); SQLSTATE: HY000  
Message: Cannot modify @@session.binlog\_format inside a transaction
  - Error number: 1680; Symbol: [ER\\_PATH\\_LENGTH](#); SQLSTATE: HY000  
Message: The path specified for %s is too long.
  - Error number: 1681; Symbol: [ER\\_WARN\\_DEPRECATED\\_SYNTAX\\_NO\\_REPLACEMENT](#); SQLSTATE: HY000  
Message: '%s' is deprecated and will be removed in a future release.
  - Error number: 1682; Symbol: [ER\\_WRONG\\_NATIVE\\_TABLE\\_STRUCTURE](#); SQLSTATE: HY000  
Message: Native table '%s'.'%s' has the wrong structure
  - Error number: 1683; Symbol: [ER\\_WRONG\\_PERFSCHEMA\\_USAGE](#); SQLSTATE: HY000  
Message: Invalid performance\_schema usage.
  - Error number: 1684; Symbol: [ER\\_WARN\\_I\\_S\\_SKIPPED\\_TABLE](#); SQLSTATE: HY000  
Message: Table '%s'.'%s' was skipped since its definition is being modified by concurrent DDL statement
  - Error number: 1685; Symbol: [ER\\_INSIDE\\_TRANSACTION\\_PREVENTS\\_SWITCH\\_BINLOG\\_DIRECT](#); SQLSTATE: HY000  
Message: Cannot modify @@session.binlog\_direct\_non\_transactional\_updates inside a transaction
  - Error number: 1686; Symbol: [ER\\_STORED\\_FUNCTION\\_PREVENTS\\_SWITCH\\_BINLOG\\_DIRECT](#); SQLSTATE: HY000  
Message: Cannot change the binlog direct flag inside a stored function or trigger
  - Error number: 1687; Symbol: [ER\\_SPATIAL\\_MUST\\_HAVE\\_GEOM\\_COL](#); SQLSTATE: 42000  
Message: A SPATIAL index may only contain a geometrical type column
  - Error number: 1688; Symbol: [ER\\_TOO\\_LONG\\_INDEX\\_COMMENT](#); SQLSTATE: HY000

- 
- Message: Comment for index '%s' is too long (max = %lu)
  - Error number: 1689; Symbol: [ER\\_LOCK\\_ABORTED](#); SQLSTATE: HY000  
Message: Wait on a lock was aborted due to a pending exclusive lock
  - Error number: 1690; Symbol: [ER\\_DATA\\_OUT\\_OF\\_RANGE](#); SQLSTATE: 22003  
Message: %s value is out of range in '%s'
  - Error number: 1691; Symbol: [ER\\_WRONG\\_SPVAR\\_TYPE\\_IN\\_LIMIT](#); SQLSTATE: HY000  
Message: A variable of a non-integer based type in LIMIT clause  
[ER\\_WRONG\\_SPVAR\\_TYPE\\_IN\\_LIMIT](#) was removed after 8.0.21.
  - Error number: 1692; Symbol: [ER\\_BINLOG\\_UNSAFE\\_MULTIPLE\\_ENGINES\\_AND\\_SELF\\_LOGGING\\_ENGINE](#); SQLSTATE: HY000  
Message: Mixing self-logging and non-self-logging engines in a statement is unsafe.
  - Error number: 1693; Symbol: [ER\\_BINLOG\\_UNSAFE\\_MIXED\\_STATEMENT](#); SQLSTATE: HY000  
Message: Statement accesses nontransactional table as well as transactional or temporary table, and writes to any of them.
  - Error number: 1694; Symbol: [ER\\_INSIDE\\_TRANSACTION\\_PREVENTS\\_SWITCH\\_SQL\\_LOG\\_BIN](#); SQLSTATE: HY000  
Message: Cannot modify @@session.sql\_log\_bin inside a transaction
  - Error number: 1695; Symbol: [ER\\_STORED\\_FUNCTION\\_PREVENTS\\_SWITCH\\_SQL\\_LOG\\_BIN](#); SQLSTATE: HY000  
Message: Cannot change the sql\_log\_bin inside a stored function or trigger
  - Error number: 1696; Symbol: [ER\\_FAILED\\_READ\\_FROM\\_PAR\\_FILE](#); SQLSTATE: HY000  
Message: Failed to read from the .par file
  - Error number: 1697; Symbol: [ER\\_VALUES\\_IS\\_NOT\\_INT\\_TYPE\\_ERROR](#); SQLSTATE: HY000  
Message: VALUES value for partition '%s' must have type INT
  - Error number: 1698; Symbol: [ER\\_ACCESS\\_DENIED\\_NO\\_PASSWORD\\_ERROR](#); SQLSTATE: 28000  
Message: Access denied for user '%s'@'%s'
  - Error number: 1699; Symbol: [ER\\_SET\\_PASSWORD\\_AUTH\\_PLUGIN](#); SQLSTATE: HY000  
Message: SET PASSWORD has no significance for users authenticating via plugins  
[ER\\_SET\\_PASSWORD\\_AUTH\\_PLUGIN](#) was removed after 8.0.28.
  - Error number: 1701; Symbol: [ER\\_TRUNCATE\\_ILLEGAL\\_FK](#); SQLSTATE: 42000  
Message: Cannot truncate a table referenced in a foreign key constraint (%s)
  - Error number: 1702; Symbol: [ER\\_PLUGIN\\_IS\\_PERMANENT](#); SQLSTATE: HY000



---

Message: Plugin '%s' is force\_plus\_permanent and can not be unloaded

- Error number: 1703; Symbol: [ER\\_SLAVE\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE\\_MIN](#); SQLSTATE: HY000

Message: The requested value for the heartbeat period is less than 1 millisecond. The value is reset to 0, meaning that heartbeating will effectively be disabled.

[ER\\_SLAVE\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE\\_MIN](#) was removed after 8.0.32.

- Error number: 1703; Symbol: [ER\\_REPLICA\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE\\_MIN](#); SQLSTATE: HY000

Message: The requested value for the heartbeat period is less than 1 millisecond. The value is reset to 0, meaning that heartbeating will effectively be disabled.

[ER\\_REPLICA\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE\\_MIN](#) was added in 8.0.33.

- Error number: 1704; Symbol: [ER\\_SLAVE\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE\\_MAX](#); SQLSTATE: HY000

Message: The requested value for the heartbeat period exceeds the value of `replica\_net\_timeout` seconds. A sensible value for the period should be less than the timeout.

[ER\\_SLAVE\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE\\_MAX](#) was removed after 8.0.32.

- Error number: 1704; Symbol: [ER\\_REPLICA\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE\\_MAX](#); SQLSTATE: HY000

Message: The requested value for the heartbeat period exceeds the value of `replica\_net\_timeout` seconds. A sensible value for the period should be less than the timeout.

[ER\\_REPLICA\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE\\_MAX](#) was added in 8.0.33.

- Error number: 1705; Symbol: [ER\\_STMT\\_CACHE\\_FULL](#); SQLSTATE: HY000

Message: Multi-row statements required more than 'max\_binlog\_stmt\_cache\_size' bytes of storage; increase this mysqld variable and try again

- Error number: 1706; Symbol: [ER\\_MULTI\\_UPDATE\\_KEY\\_CONFLICT](#); SQLSTATE: HY000

Message: Primary key/partition key update is not allowed since the table is updated both as '%s' and '%s'.

- Error number: 1707; Symbol: [ER\\_TABLE\\_NEEDS\\_REBUILD](#); SQLSTATE: HY000

Message: Table rebuild required. Please do "ALTER TABLE `%s` FORCE" or dump/reload to fix it!

- Error number: 1708; Symbol: [WARN\\_OPTION\\_BELOW\\_LIMIT](#); SQLSTATE: HY000

Message: The value of '%s' should be no less than the value of '%s'

- Error number: 1709; Symbol: [ER\\_INDEX\\_COLUMN\\_TOO\\_LONG](#); SQLSTATE: HY000

Message: Index column size too large. The maximum column size is %lu bytes.

- Error number: 1710; Symbol: [ER\\_ERROR\\_IN\\_TRIGGER\\_BODY](#); SQLSTATE: HY000

---

Message: Trigger '%s' has an error in its body: '%s'

- Error number: 1711; Symbol: [ER\\_ERROR\\_IN\\_UNKNOWN\\_TRIGGER\\_BODY](#); SQLSTATE: HY000

Message: Unknown trigger has an error in its body: '%s'

- Error number: 1712; Symbol: [ER\\_INDEX\\_CORRUPT](#); SQLSTATE: HY000

Message: Index %s is corrupted

- Error number: 1713; Symbol: [ER\\_UNDO\\_RECORD\\_TOO\\_BIG](#); SQLSTATE: HY000

Message: Undo log record is too big.

- Error number: 1714; Symbol: [ER\\_BINLOG\\_UNSAFE\\_INSERT\\_IGNORE\\_SELECT](#); SQLSTATE: HY000

Message: INSERT IGNORE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: 1715; Symbol: [ER\\_BINLOG\\_UNSAFE\\_INSERT\\_SELECT\\_UPDATE](#); SQLSTATE: HY000

Message: INSERT... SELECT... ON DUPLICATE KEY UPDATE is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are updated. This order cannot be predicted and may differ on source and the replica.

- Error number: 1716; Symbol: [ER\\_BINLOG\\_UNSAFE\\_REPLACE\\_SELECT](#); SQLSTATE: HY000

Message: REPLACE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on source and the replica.

- Error number: 1717; Symbol: [ER\\_BINLOG\\_UNSAFE\\_CREATE\\_IGNORE\\_SELECT](#); SQLSTATE: HY000

Message: CREATE... IGNORE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: 1718; Symbol: [ER\\_BINLOG\\_UNSAFE\\_CREATE\\_REPLACE\\_SELECT](#); SQLSTATE: HY000

Message: CREATE... REPLACE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on source and the replica.

- Error number: 1719; Symbol: [ER\\_BINLOG\\_UNSAFE\\_UPDATE\\_IGNORE](#); SQLSTATE: HY000

Message: UPDATE IGNORE is unsafe because the order in which rows are updated determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: 1720; Symbol: [ER\\_PLUGIN\\_NO\\_UNINSTALL](#); SQLSTATE: HY000

Message: Plugin '%s' is marked as not dynamically uninstallable. You have to stop the server to uninstall it.

- Error number: 1721; Symbol: [ER\\_PLUGIN\\_NO\\_INSTALL](#); SQLSTATE: HY000

Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.

- 
- Error number: [1722](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_WRITE\\_AUTOINC\\_SELECT](#); SQLSTATE: [HY000](#)  
Message: Statements writing to a table with an auto-increment column after selecting from another table are unsafe because the order in which rows are retrieved determines what (if any) rows will be written. This order cannot be predicted and may differ on source and the replica.
  - Error number: [1723](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_CREATE\\_SELECT\\_AUTOINC](#); SQLSTATE: [HY000](#)  
Message: CREATE TABLE... SELECT... on a table with an auto-increment column is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are inserted. This order cannot be predicted and may differ on source and the replica.
  - Error number: [1724](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_INSERT\\_TWO\\_KEYS](#); SQLSTATE: [HY000](#)  
Message: INSERT... ON DUPLICATE KEY UPDATE on a table with more than one UNIQUE KEY is unsafe
  - Error number: [1725](#); Symbol: [ER\\_TABLE\\_IN\\_FK\\_CHECK](#); SQLSTATE: [HY000](#)  
Message: Table is being used in foreign key check.
  - Error number: [1726](#); Symbol: [ER\\_UNSUPPORTED\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: Storage engine '%s' does not support system tables. [%s.%s]
  - Error number: [1727](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_AUTOINC\\_NOT\\_FIRST](#); SQLSTATE: [HY000](#)  
Message: INSERT into autoincrement field which is not the first part in the composed primary key is unsafe.
  - Error number: [1728](#); Symbol: [ER\\_CANNOT\\_LOAD\\_FROM\\_TABLE\\_V2](#); SQLSTATE: [HY000](#)  
Message: Cannot load from %s.%s. The table is probably corrupted
  - Error number: [1729](#); Symbol: [ER\\_MASTER\\_DELAY\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [HY000](#)  
Message: The requested value %s for the master delay exceeds the maximum %u  
[ER\\_MASTER\\_DELAY\\_VALUE\\_OUT\\_OF\\_RANGE](#) was removed after 8.0.32.
  - Error number: [1729](#); Symbol: [ER\\_SOURCE\\_DELAY\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [HY000](#)  
Message: The requested value %s for the source delay exceeds the maximum %u  
[ER\\_SOURCE\\_DELAY\\_VALUE\\_OUT\\_OF\\_RANGE](#) was added in 8.0.33.
  - Error number: [1730](#); Symbol: [ER\\_ONLY\\_FD\\_AND\\_RBR\\_EVENTS\\_ALLOWED\\_IN\\_BINLOG\\_STATEMENT](#); SQLSTATE: [HY000](#)  
Message: Only Format\_description\_log\_event and row events are allowed in BINLOG statements (but %s was provided)
  - Error number: [1731](#); Symbol: [ER\\_PARTITION\\_EXCHANGE\\_DIFFERENT\\_OPTION](#); SQLSTATE: [HY000](#)  
Message: Non matching attribute '%s' between partition and table
  - Error number: [1732](#); Symbol: [ER\\_PARTITION\\_EXCHANGE\\_PART\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Table to exchange with partition is partitioned: '%s'

- 
- Error number: 1733; Symbol: `ER_PARTITION_EXCHANGE_TEMP_TABLE`; SQLSTATE: HY000  
Message: Table to exchange with partition is temporary: '%s'
  - Error number: 1734; Symbol: `ER_PARTITION_INSTEAD_OF_SUBPARTITION`; SQLSTATE: HY000  
Message: Subpartitioned table, use subpartition instead of partition
  - Error number: 1735; Symbol: `ER_UNKNOWN_PARTITION`; SQLSTATE: HY000  
Message: Unknown partition '%s' in table '%s'
  - Error number: 1736; Symbol: `ER_TABLES_DIFFERENT_METADATA`; SQLSTATE: HY000  
Message: Tables have different definitions
  - Error number: 1737; Symbol: `ER_ROW_DOES_NOT_MATCH_PARTITION`; SQLSTATE: HY000  
Message: Found a row that does not match the partition
  - Error number: 1738; Symbol: `ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX`; SQLSTATE: HY000  
Message: Option binlog\_cache\_size (%lu) is greater than max\_binlog\_cache\_size (%lu); setting binlog\_cache\_size equal to max\_binlog\_cache\_size.
  - Error number: 1739; Symbol: `ER_WARN_INDEX_NOT_APPLICABLE`; SQLSTATE: HY000  
Message: Cannot use %s access on index '%s' due to type or collation conversion on field '%s'
  - Error number: 1740; Symbol: `ER_PARTITION_EXCHANGE_FOREIGN_KEY`; SQLSTATE: HY000  
Message: Table to exchange with partition has foreign key references: '%s'
  - Error number: 1742; Symbol: `ER_RPL_INFO_DATA_TOO_LONG`; SQLSTATE: HY000  
Message: Data for column '%s' too long
  - Error number: 1745; Symbol: `ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX`; SQLSTATE: HY000  
Message: Option binlog\_stmt\_cache\_size (%lu) is greater than max\_binlog\_stmt\_cache\_size (%lu); setting binlog\_stmt\_cache\_size equal to max\_binlog\_stmt\_cache\_size.
  - Error number: 1746; Symbol: `ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT`; SQLSTATE: HY000  
Message: Can't update table '%s' while '%s' is being created.
  - Error number: 1747; Symbol: `ER_PARTITION_CLAUSE_ON_NONPARTITIONED`; SQLSTATE: HY000  
Message: PARTITION () clause on non partitioned table
  - Error number: 1748; Symbol: `ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET`; SQLSTATE: HY000  
Message: Found a row not matching the given partition set
  - Error number: 1750; Symbol: `ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE`; SQLSTATE: HY000  
Message: Failure while changing the type of replication repository: %s.

- 
- Error number: 1751; Symbol: `ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATED_TEMP_TABLE`; SQLSTATE: HY000  
Message: The creation of some temporary tables could not be rolled back.
  - Error number: 1752; Symbol: `ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROPPED_TEMP_TABLE`; SQLSTATE: HY000  
Message: Some temporary tables were dropped, but these operations could not be rolled back.
  - Error number: 1753; Symbol: `ER_MTS_FEATURE_IS_NOT_SUPPORTED`; SQLSTATE: HY000  
Message: %s is not supported in multi-threaded slave mode. %s  
`ER_MTS_FEATURE_IS_NOT_SUPPORTED` was removed after 8.0.32.
  - Error number: 1753; Symbol: `ER_MTA_FEATURE_IS_NOT_SUPPORTED`; SQLSTATE: HY000  
Message: %s is not supported in multi-threaded replica mode. %s  
`ER_MTA_FEATURE_IS_NOT_SUPPORTED` was added in 8.0.33.
  - Error number: 1754; Symbol: `ER_MTS_UPDATED_DBS_GREATER_MAX`; SQLSTATE: HY000  
Message: The number of modified databases exceeds the maximum %d; the database names will not be included in the replication event metadata.  
`ER_MTS_UPDATED_DBS_GREATER_MAX` was removed after 8.0.32.
  - Error number: 1754; Symbol: `ER_MTA_UPDATED_DBS_GREATER_MAX`; SQLSTATE: HY000  
Message: The number of modified databases exceeds the maximum %d; the database names will not be included in the replication event metadata.  
`ER_MTA_UPDATED_DBS_GREATER_MAX` was added in 8.0.33.
  - Error number: 1755; Symbol: `ER_MTS_CANT_PARALLEL`; SQLSTATE: HY000  
Message: Cannot execute the current event group in the parallel mode. Encountered event %s, relay-log name %s, position %s which prevents execution of this event group in parallel mode. Reason: %s.  
`ER_MTS_CANT_PARALLEL` was removed after 8.0.32.
  - Error number: 1755; Symbol: `ER_MTA_CANT_PARALLEL`; SQLSTATE: HY000  
Message: Cannot execute the current event group in the parallel mode. Encountered event %s, relay-log name %s, position %s which prevents execution of this event group in parallel mode. Reason: %s.  
`ER_MTA_CANT_PARALLEL` was added in 8.0.33.
  - Error number: 1756; Symbol: `ER_MTS_INCONSISTENT_DATA`; SQLSTATE: HY000  
Message: %s  
`ER_MTS_INCONSISTENT_DATA` was removed after 8.0.32.
  - Error number: 1756; Symbol: `ER_MTA_INCONSISTENT_DATA`; SQLSTATE: HY000  
Message: %s

---

[ER\\_MTA\\_INCONSISTENT\\_DATA](#) was added in 8.0.33.

- Error number: [1757](#); Symbol: [ER\\_FULLTEXT\\_NOT\\_SUPPORTEDED\\_WITH\\_PARTITIONING](#); SQLSTATE: [HY000](#)

Message: FULLTEXT index is not supported for partitioned tables.

- Error number: [1758](#); Symbol: [ER\\_DA\\_INVALID\\_CONDITION\\_NUMBER](#); SQLSTATE: [35000](#)

Message: Invalid condition number

- Error number: [1759](#); Symbol: [ER\\_INSECURE\\_PLAIN\\_TEXT](#); SQLSTATE: [HY000](#)

Message: Sending passwords in plain text without SSL/TLS is extremely insecure.

- Error number: [1760](#); Symbol: [ER\\_INSECURE\\_CHANGE\\_MASTER](#); SQLSTATE: [HY000](#)

Message: Storing MySQL user name or password information in the master info repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START SLAVE; see the 'START SLAVE Syntax' in the MySQL Manual for more information.

[ER\\_INSECURE\\_CHANGE\\_MASTER](#) was removed after 8.0.32.

- Error number: [1760](#); Symbol: [ER\\_INSECURE\\_CHANGE\\_SOURCE](#); SQLSTATE: [HY000](#)

Message: Storing MySQL user name or password information in the connection metadata repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START REPLICA; see the 'START REPLICA Syntax' in the MySQL Manual for more information.

[ER\\_INSECURE\\_CHANGE\\_SOURCE](#) was added in 8.0.33.

- Error number: [1761](#); Symbol: [ER\\_FOREIGN\\_DUPLICATE\\_KEY\\_WITH\\_CHILD\\_INFO](#); SQLSTATE: [23000](#)

Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in table '%s', key '%s'

- Error number: [1762](#); Symbol: [ER\\_FOREIGN\\_DUPLICATE\\_KEY\\_WITHOUT\\_CHILD\\_INFO](#); SQLSTATE: [23000](#)

Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in a child table

- Error number: [1763](#); Symbol: [ER\\_SQLTHREAD\\_WITH\\_SECURE\\_SLAVE](#); SQLSTATE: [HY000](#)

Message: Setting authentication options is not possible when only the Slave SQL Thread is being started.

[ER\\_SQLTHREAD\\_WITH\\_SECURE\\_SLAVE](#) was removed after 8.0.32.

- Error number: [1763](#); Symbol: [ER\\_SQLTHREAD\\_WITH\\_SECURE\\_REPLICA](#); SQLSTATE: [HY000](#)

Message: Setting authentication options is not possible when only the Replica SQL Thread is being started.

[ER\\_SQLTHREAD\\_WITH\\_SECURE\\_REPLICA](#) was added in 8.0.33.

- Error number: [1764](#); Symbol: [ER\\_TABLE\\_HAS\\_NO\\_FT](#); SQLSTATE: [HY000](#)

---

Message: The table does not have FULLTEXT index to support this query

- Error number: 1765; Symbol: `ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER`; SQLSTATE: HY000

Message: The system variable %s cannot be set in stored functions or triggers.

- Error number: 1766; Symbol: `ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION`; SQLSTATE: HY000

Message: The system variable %s cannot be set when there is an ongoing transaction.

- Error number: 1769; Symbol: `ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION`; SQLSTATE: HY000

Message: The statement 'SET %s' cannot invoke a stored function.

- Error number: 1770; Symbol: `ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LIST_IS_NON_NULL`; SQLSTATE: HY000

Message: The system variable @@SESSION.GTID\_NEXT cannot be 'AUTOMATIC' when @@SESSION.GTID\_NEXT\_LIST is non-NULL.

- Error number: 1772; Symbol: `ER_MALFORMED_GTID_SET_SPECIFICATION`; SQLSTATE: HY000

Message: Malformed GTID set specification '%s'.

- Error number: 1773; Symbol: `ER_MALFORMED_GTID_SET_ENCODING`; SQLSTATE: HY000

Message: Malformed GTID set encoding.

- Error number: 1774; Symbol: `ER_MALFORMED_GTID_SPECIFICATION`; SQLSTATE: HY000

Message: Malformed GTID specification '%s'.

- Error number: 1775; Symbol: `ER_GNO_EXHAUSTED`; SQLSTATE: HY000

Message: Impossible to generate GTID: the integer component reached the maximum value. Restart the server with a new server\_uuid.

- Error number: 1776; Symbol: `ER_BAD_SLAVE_AUTO_POSITION`; SQLSTATE: HY000

Message: Parameters MASTER\_LOG\_FILE, MASTER\_LOG\_POS, RELAY\_LOG\_FILE and RELAY\_LOG\_POS cannot be set when MASTER\_AUTO\_POSITION is active.

`ER_BAD_SLAVE_AUTO_POSITION` was removed after 8.0.32.

- Error number: 1776; Symbol: `ER_BAD_REPLICA_AUTO_POSITION`; SQLSTATE: HY000

Message: Parameters SOURCE\_LOG\_FILE, SOURCE\_LOG\_POS, RELAY\_LOG\_FILE and RELAY\_LOG\_POS cannot be set when SOURCE\_AUTO\_POSITION is active.

`ER_BAD_REPLICA_AUTO_POSITION` was added in 8.0.33.

- Error number: 1777; Symbol: `ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF`; SQLSTATE: HY000

Message: CHANGE REPLICATION SOURCE TO SOURCE\_AUTO\_POSITION = 1 cannot be executed because @@GLOBAL.GTID\_MODE = OFF.

- 
- Error number: 1778; Symbol:  
`ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_NEXT_IS_SET`; SQLSTATE: HY000  
  
Message: Cannot execute statements with implicit commit inside a transaction when  
`@@SESSION.GTID_NEXT == 'UUID:NUMBER'`.
  - Error number: 1779; Symbol: `ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON`;  
SQLSTATE: HY000  
  
Message: `GTID_MODE = ON` requires `ENFORCE_GTID_CONSISTENCY = ON`.
  - Error number: 1781; Symbol: `ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_OFF`;  
SQLSTATE: HY000  
  
Message: `@@SESSION.GTID_NEXT` cannot be set to `UUID:NUMBER` when  
`@@GLOBAL.GTID_MODE = OFF`.
  - Error number: 1782; Symbol:  
`ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID_MODE_IS_ON`; SQLSTATE: HY000  
  
Message: `@@SESSION.GTID_NEXT` cannot be set to `ANONYMOUS` when  
`@@GLOBAL.GTID_MODE = ON`.
  - Error number: 1783; Symbol:  
`ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_MODE_IS_OFF`; SQLSTATE: HY000  
  
Message: `@@SESSION.GTID_NEXT_LIST` cannot be set to a non-NULL value when  
`@@GLOBAL.GTID_MODE = OFF`.
  - Error number: 1785; Symbol: `ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE`; SQLSTATE: HY000  
  
Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.
  - Error number: 1786; Symbol: `ER_GTID_UNSAFE_CREATE_SELECT`; SQLSTATE: HY000  
  
Message: Statement violates GTID consistency: `CREATE TABLE ... SELECT`.
  - Error number: 1787; Symbol:  
`ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_IN_TRANSACTION`; SQLSTATE: HY000  
  
Message: Statement violates GTID consistency: `CREATE TEMPORARY TABLE` and `DROP TEMPORARY TABLE` can only be executed outside transactional context. These statements are also not allowed in a function or trigger because functions and triggers are also considered to be multi-statement transactions.  
  
`ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_IN_TRANSACTION` was removed after 8.0.12.
  - Error number: 1788; Symbol: `ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME`;  
SQLSTATE: HY000  
  
Message: The value of `@@GLOBAL.GTID_MODE` can only be changed one step at a time: `OFF <-> OFF_PERMISSIVE <-> ON_PERMISSIVE <-> ON`. Also note that this value must be stepped up or down simultaneously on all servers. See the Manual for instructions.



- 
- Error number: [1789](#); Symbol: [ER\\_MASTER\\_HAS\\_PURGED\\_REQUIRED\\_GTIDS](#); SQLSTATE: [HY000](#)  
Message: Cannot replicate because the master purged required binary logs. Replicate the missing transactions from elsewhere, or provision a new slave from backup. Consider increasing the master's binary log expiration period. %s  
[ER\\_MASTER\\_HAS\\_PURGED\\_REQUIRED\\_GTIDS](#) was removed after 8.0.32.
  - Error number: [1789](#); Symbol: [ER\\_SOURCE\\_HAS\\_PURGED\\_REQUIRED\\_GTIDS](#); SQLSTATE: [HY000](#)  
Message: Cannot replicate because the source purged required binary logs. Replicate the missing transactions from elsewhere, or provision a new replica from backup. Consider increasing the source's binary log expiration period. %s  
[ER\\_SOURCE\\_HAS\\_PURGED\\_REQUIRED\\_GTIDS](#) was added in 8.0.33.
  - Error number: [1790](#); Symbol: [ER\\_CANT\\_SET\\_GTID\\_NEXT\\_WHEN\\_OWNING\\_GTID](#); SQLSTATE: [HY000](#)  
Message: @@SESSION.GTID\_NEXT cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.
  - Error number: [1791](#); Symbol: [ER\\_UNKNOWN\\_EXPLAIN\\_FORMAT](#); SQLSTATE: [HY000](#)  
Message: Unknown EXPLAIN format name: '%s'
  - Error number: [1792](#); Symbol: [ER\\_CANT\\_EXECUTE\\_IN\\_READ\\_ONLY\\_TRANSACTION](#); SQLSTATE: [25006](#)  
Message: Cannot execute statement in a READ ONLY transaction.
  - Error number: [1793](#); Symbol: [ER\\_TOO\\_LONG\\_TABLE\\_PARTITION\\_COMMENT](#); SQLSTATE: [HY000](#)  
Message: Comment for table partition '%s' is too long (max = %lu)
  - Error number: [1794](#); Symbol: [ER\\_SLAVE\\_CONFIGURATION](#); SQLSTATE: [HY000](#)  
Message: Slave is not configured or failed to initialize properly. You must at least set --server-id to enable either a master or a slave. Additional error messages can be found in the MySQL error log.  
[ER\\_SLAVE\\_CONFIGURATION](#) was removed after 8.0.32.
  - Error number: [1794](#); Symbol: [ER\\_REPLICA\\_CONFIGURATION](#); SQLSTATE: [HY000](#)  
Message: Replica is not configured or failed to initialize properly. You must at least set --server-id to enable either a source or a replica. Additional error messages can be found in the MySQL error log.  
[ER\\_REPLICA\\_CONFIGURATION](#) was added in 8.0.33.
  - Error number: [1795](#); Symbol: [ER\\_INNODB\\_FT\\_LIMIT](#); SQLSTATE: [HY000](#)  
Message: InnoDB presently supports one FULLTEXT index creation at a time
  - Error number: [1796](#); Symbol: [ER\\_INNODB\\_NO\\_FT\\_TEMP\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot create FULLTEXT index on temporary InnoDB table
  - Error number: [1797](#); Symbol: [ER\\_INNODB\\_FT\\_WRONG\\_DOCID\\_COLUMN](#); SQLSTATE: [HY000](#)  
Message: Column '%s' is of wrong type for an InnoDB FULLTEXT index

- 
- Error number: 1798; Symbol: [ER\\_INNOODB\\_FT\\_WRONG\\_DOCID\\_INDEX](#); SQLSTATE: HY000  
Message: Index '%s' is of wrong type for an InnoDB FULLTEXT index
  - Error number: 1799; Symbol: [ER\\_INNOODB\\_ONLINE\\_LOG\\_TOO\\_BIG](#); SQLSTATE: HY000  
Message: Creating index '%s' required more than 'innodb\_online\_alter\_log\_max\_size' bytes of modification log. Please try again.
  - Error number: 1800; Symbol: [ER\\_UNKNOWN\\_ALTER\\_ALGORITHM](#); SQLSTATE: HY000  
Message: Unknown ALGORITHM '%s'
  - Error number: 1801; Symbol: [ER\\_UNKNOWN\\_ALTER\\_LOCK](#); SQLSTATE: HY000  
Message: Unknown LOCK type '%s'
  - Error number: 1802; Symbol: [ER\\_MTS\\_CHANGE\\_MASTER\\_CANT\\_RUN\\_WITH\\_GAPS](#); SQLSTATE: HY000  
Message: CHANGE MASTER cannot be executed when the slave was stopped with an error or killed in MTS mode. Consider using RESET SLAVE or START SLAVE UNTIL.  
[ER\\_MTS\\_CHANGE\\_MASTER\\_CANT\\_RUN\\_WITH\\_GAPS](#) was removed after 8.0.32.
  - Error number: 1802; Symbol: [ER\\_MTA\\_CHANGE\\_SOURCE\\_CANT\\_RUN\\_WITH\\_GAPS](#); SQLSTATE: HY000  
Message: CHANGE REPLICATION SOURCE cannot be executed when the replica was stopped with an error or killed in MTA mode. Consider using RESET REPLICA or START REPLICA UNTIL.  
[ER\\_MTA\\_CHANGE\\_SOURCE\\_CANT\\_RUN\\_WITH\\_GAPS](#) was added in 8.0.33.
  - Error number: 1803; Symbol: [ER\\_MTS\\_RECOVERY\\_FAILURE](#); SQLSTATE: HY000  
Message: Cannot recover after SLAVE errored out in parallel execution mode. Additional error messages can be found in the MySQL error log.  
[ER\\_MTS\\_RECOVERY\\_FAILURE](#) was removed after 8.0.32.
  - Error number: 1803; Symbol: [ER\\_MTA\\_RECOVERY\\_FAILURE](#); SQLSTATE: HY000  
Message: Cannot recover after REPLICA errored out in parallel execution mode. Additional error messages can be found in the MySQL error log.  
[ER\\_MTA\\_RECOVERY\\_FAILURE](#) was added in 8.0.33.
  - Error number: 1804; Symbol: [ER\\_MTS\\_RESET\\_WORKERS](#); SQLSTATE: HY000  
Message: Cannot clean up worker info tables. Additional error messages can be found in the MySQL error log.  
[ER\\_MTS\\_RESET\\_WORKERS](#) was removed after 8.0.32.
  - Error number: 1804; Symbol: [ER\\_MTA\\_RESET\\_WORKERS](#); SQLSTATE: HY000  
Message: Cannot clean up worker info tables. Additional error messages can be found in the MySQL error log.  
[ER\\_MTA\\_RESET\\_WORKERS](#) was added in 8.0.33.
  - Error number: 1805; Symbol: [ER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_CORRUPTED\\_V2](#); SQLSTATE: HY000

---

Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted

- Error number: 1806; Symbol: `ER_SLAVE_SILENT_RETRY_TRANSACTION`; SQLSTATE: HY000

Message: Slave must silently retry current transaction

`ER_SLAVE_SILENT_RETRY_TRANSACTION` was removed after 8.0.32.

- Error number: 1806; Symbol: `ER_REPLICA_SILENT_RETRY_TRANSACTION`; SQLSTATE: HY000

Message: Replica must silently retry current transaction

`ER_REPLICA_SILENT_RETRY_TRANSACTION` was added in 8.0.33.

- Error number: 1807; Symbol: `ER_DISCARD_FK_CHECKS_RUNNING`; SQLSTATE: HY000

Message: There is a foreign key check running on table '%s'. Cannot discard the table.

- Error number: 1808; Symbol: `ER_TABLE_SCHEMA_MISMATCH`; SQLSTATE: HY000

Message: Schema mismatch (%s)

- Error number: 1809; Symbol: `ER_TABLE_IN_SYSTEM_TABLESPACE`; SQLSTATE: HY000

Message: Table '%s' in system tablespace

- Error number: 1810; Symbol: `ER_IO_READ_ERROR`; SQLSTATE: HY000

Message: IO Read error: (%lu, %s) %s

- Error number: 1811; Symbol: `ER_IO_WRITE_ERROR`; SQLSTATE: HY000

Message: IO Write error: (%lu, %s) %s

- Error number: 1812; Symbol: `ER_TABLESPACE_MISSING`; SQLSTATE: HY000

Message: Tablespace is missing for table %s.

- Error number: 1813; Symbol: `ER_TABLESPACE_EXISTS`; SQLSTATE: HY000

Message: Tablespace '%s' exists.

- Error number: 1814; Symbol: `ER_TABLESPACE_DISCARDED`; SQLSTATE: HY000

Message: Tablespace has been discarded for table '%s'

- Error number: 1815; Symbol: `ER_INTERNAL_ERROR`; SQLSTATE: HY000

Message: Internal error: %s

- Error number: 1816; Symbol: `ER_INNODB_IMPORT_ERROR`; SQLSTATE: HY000

Message: ALTER TABLE %s IMPORT TABLESPACE failed with error %lu : '%s'

- Error number: 1817; Symbol: `ER_INNODB_INDEX_CORRUPT`; SQLSTATE: HY000

Message: Index corrupt: %s

- Error number: 1818; Symbol: `ER_INVALID_YEAR_COLUMN_LENGTH`; SQLSTATE: HY000

---

Message: Invalid display width. Use YEAR instead.

- Error number: 1819; Symbol: [ER\\_NOT\\_VALID\\_PASSWORD](#); SQLSTATE: HY000

Message: Your password does not satisfy the current policy requirements

- Error number: 1820; Symbol: [ER\\_MUST\\_CHANGE\\_PASSWORD](#); SQLSTATE: HY000

Message: You must reset your password using ALTER USER statement before executing this statement.

- Error number: 1821; Symbol: [ER\\_FK\\_NO\\_INDEX\\_CHILD](#); SQLSTATE: HY000

Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the foreign table '%s'

- Error number: 1822; Symbol: [ER\\_FK\\_NO\\_INDEX\\_PARENT](#); SQLSTATE: HY000

Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the referenced table '%s'

- Error number: 1823; Symbol: [ER\\_FK\\_FAIL\\_ADD\\_SYSTEM](#); SQLSTATE: HY000

Message: Failed to add the foreign key constraint '%s' to system tables

- Error number: 1824; Symbol: [ER\\_FK\\_CANNOT\\_OPEN\\_PARENT](#); SQLSTATE: HY000

Message: Failed to open the referenced table '%s'

- Error number: 1825; Symbol: [ER\\_FK\\_INCORRECT\\_OPTION](#); SQLSTATE: HY000

Message: Failed to add the foreign key constraint on table '%s'. Incorrect options in FOREIGN KEY constraint '%s'

- Error number: 1826; Symbol: [ER\\_FK\\_DUP\\_NAME](#); SQLSTATE: HY000

Message: Duplicate foreign key constraint name '%s'

- Error number: 1827; Symbol: [ER\\_PASSWORD\\_FORMAT](#); SQLSTATE: HY000

Message: The password hash doesn't have the expected format.

- Error number: 1828; Symbol: [ER\\_FK\\_COLUMN\\_CANNOT\\_DROP](#); SQLSTATE: HY000

Message: Cannot drop column '%s': needed in a foreign key constraint '%s'

- Error number: 1829; Symbol: [ER\\_FK\\_COLUMN\\_CANNOT\\_DROP\\_CHILD](#); SQLSTATE: HY000

Message: Cannot drop column '%s': needed in a foreign key constraint '%s' of table '%s'

- Error number: 1830; Symbol: [ER\\_FK\\_COLUMN\\_NOT\\_NULL](#); SQLSTATE: HY000

Message: Column '%s' cannot be NOT NULL: needed in a foreign key constraint '%s' SET NULL

- Error number: 1831; Symbol: [ER\\_DUP\\_INDEX](#); SQLSTATE: HY000

Message: Duplicate index '%s' defined on the table '%s.%s'. This is deprecated and will be disallowed in a future release.

- 
- Error number: [1832](#); Symbol: [ER\\_FK\\_COLUMN\\_CANNOT\\_CHANGE](#); SQLSTATE: [HY000](#)  
Message: Cannot change column '%s': used in a foreign key constraint '%s'
  - Error number: [1833](#); Symbol: [ER\\_FK\\_COLUMN\\_CANNOT\\_CHANGE\\_CHILD](#); SQLSTATE: [HY000](#)  
Message: Cannot change column '%s': used in a foreign key constraint '%s' of table '%s'
  - Error number: [1835](#); Symbol: [ER\\_MALFORMED\\_PACKET](#); SQLSTATE: [HY000](#)  
Message: Malformed communication packet.
  - Error number: [1836](#); Symbol: [ER\\_READ\\_ONLY\\_MODE](#); SQLSTATE: [HY000](#)  
Message: Running in read-only mode
  - Error number: [1837](#); Symbol: [ER\\_GTID\\_NEXT\\_TYPE\\_UNDEFINED\\_GROUP](#); SQLSTATE: [HY000](#)  
Message: When @@SESSION.GTID\_NEXT is set to a GTID, you must explicitly set it to a different value after a COMMIT or ROLLBACK. Please check GTID\_NEXT variable manual page for detailed explanation. Current @@SESSION.GTID\_NEXT is '%s'.  
[ER\\_GTID\\_NEXT\\_TYPE\\_UNDEFINED\\_GROUP](#) was removed after 8.0.4.
  - Error number: [1837](#); Symbol: [ER\\_GTID\\_NEXT\\_TYPE\\_UNDEFINED\\_GTID](#); SQLSTATE: [HY000](#)  
Message: When @@SESSION.GTID\_NEXT is set to a GTID, you must explicitly set it to a different value after a COMMIT or ROLLBACK. Please check GTID\_NEXT variable manual page for detailed explanation. Current @@SESSION.GTID\_NEXT is '%s'.  
[ER\\_GTID\\_NEXT\\_TYPE\\_UNDEFINED\\_GTID](#) was added in 8.0.11.
  - Error number: [1838](#); Symbol: [ER\\_VARIABLE\\_NOT\\_SETTABLE\\_IN\\_SP](#); SQLSTATE: [HY000](#)  
Message: The system variable %s cannot be set in stored procedures.
  - Error number: [1840](#); Symbol: [ER\\_CANT\\_SET\\_GTID\\_PURGED\\_WHEN\\_GTID\\_EXECUTED\\_IS\\_NOT\\_EMPTY](#); SQLSTATE: [HY000](#)  
Message: @@GLOBAL.GTID\_PURGED can only be set when @@GLOBAL.GTID\_EXECUTED is empty.
  - Error number: [1841](#); Symbol: [ER\\_CANT\\_SET\\_GTID\\_PURGED\\_WHEN\\_OWNED\\_GTIDS\\_IS\\_NOT\\_EMPTY](#); SQLSTATE: [HY000](#)  
Message: @@GLOBAL.GTID\_PURGED can only be set when there are no ongoing transactions (not even in other clients).
  - Error number: [1842](#); Symbol: [ER\\_GTID\\_PURGED\\_WAS\\_CHANGED](#); SQLSTATE: [HY000](#)  
Message: @@GLOBAL.GTID\_PURGED was changed from '%s' to '%s'.
  - Error number: [1843](#); Symbol: [ER\\_GTID\\_EXECUTED\\_WAS\\_CHANGED](#); SQLSTATE: [HY000](#)  
Message: @@GLOBAL.GTID\_EXECUTED was changed from '%s' to '%s'.
  - Error number: [1844](#); Symbol: [ER\\_BINLOG\\_STMT\\_MODE\\_AND\\_NO\\_REPL\\_TABLES](#); SQLSTATE: [HY000](#)  
Message: Cannot execute statement: impossible to write to binary log since BINLOG\_FORMAT = STATEMENT, and both replicated and non replicated tables are written to.

- 
- Error number: 1845; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTEDED; SQLSTATE: 0A000  
Message: %s is not supported for this operation. Try %s.
  - Error number: 1846; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTEDED\_REASON; SQLSTATE: 0A000  
Message: %s is not supported. Reason: %s. Try %s.
  - Error number: 1847; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTEDED\_REASON\_COPY; SQLSTATE: HY000  
Message: COPY algorithm requires a lock
  - Error number: 1848; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTEDED\_REASON\_PARTITION; SQLSTATE: HY000  
Message: Partition specific operations do not yet support LOCK/ALGORITHM
  - Error number: 1849; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTEDED\_REASON\_FK\_RENAME; SQLSTATE: HY000  
Message: Columns participating in a foreign key are renamed
  - Error number: 1850; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTEDED\_REASON\_COLUMN\_TYPE; SQLSTATE: HY000  
Message: Cannot change column type INPLACE
  - Error number: 1851; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTEDED\_REASON\_FK\_CHECK; SQLSTATE: HY000  
Message: Adding foreign keys needs foreign\_key\_checks=OFF
  - Error number: 1853; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTEDED\_REASON\_NOPK; SQLSTATE: HY000  
Message: Dropping a primary key is not allowed without also adding a new primary key
  - Error number: 1854; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTEDED\_REASON\_AUTOINC; SQLSTATE: HY000  
Message: Adding an auto-increment column requires a lock
  - Error number: 1855; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTEDED\_REASON\_HIDDEN\_FTS; SQLSTATE: HY000  
Message: Cannot replace hidden FTS\_DOC\_ID with a user-visible one
  - Error number: 1856; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTEDED\_REASON\_CHANGE\_FTS; SQLSTATE: HY000  
Message: Cannot drop or rename FTS\_DOC\_ID
  - Error number: 1857; Symbol: ER\_ALTER\_OPERATION\_NOT\_SUPPORTEDED\_REASON\_FTS; SQLSTATE: HY000  
Message: Fulltext index creation requires a lock
  - Error number: 1858; Symbol: ER\_SQL\_SLAVE\_SKIP\_COUNTER\_NOT\_SETTABLE\_IN\_GTID\_MODE; SQLSTATE: HY000

---

Message: sql\_slave\_skip\_counter can not be set when the server is running with @@GLOBAL.GTID\_MODE = ON. Instead, for each transaction that you want to skip, generate an empty transaction with the same GTID as the transaction

[ER\\_SQL\\_SLAVE\\_SKIP\\_COUNTER\\_NOT\\_SETTABLE\\_IN\\_GTID\\_MODE](#) was removed after 8.0.22.

- Error number: 1859; Symbol: [ER\\_DUP\\_UNKNOWN\\_IN\\_INDEX](#); SQLSTATE: 23000

Message: Duplicate entry for key '%s'

- Error number: 1860; Symbol: [ER\\_IDENT\\_CAUSES\\_TOO\\_LONG\\_PATH](#); SQLSTATE: HY000

Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.

- Error number: 1861; Symbol: [ER\\_ALTER\\_OPERATION\\_NOT\\_SUPPORTED\\_REASON\\_NOT\\_NULL](#); SQLSTATE: HY000

Message: cannot silently convert NULL values, as required in this SQL\_MODE

- Error number: 1862; Symbol: [ER\\_MUST\\_CHANGE\\_PASSWORD\\_LOGIN](#); SQLSTATE: HY000

Message: Your password has expired. To log in you must change it using a client that supports expired passwords.

- Error number: 1863; Symbol: [ER\\_ROW\\_IN\\_WRONG\\_PARTITION](#); SQLSTATE: HY000

Message: Found a row in wrong partition %s

- Error number: 1864; Symbol: [ER\\_MTS\\_EVENT\\_BIGGER\\_PENDING\\_JOBS\\_SIZE\\_MAX](#); SQLSTATE: HY000

Message: Cannot schedule event %s, relay-log name %s, position %s to Worker thread because its size %lu exceeds %lu of replica\_pending\_jobs\_size\_max.

[ER\\_MTS\\_EVENT\\_BIGGER\\_PENDING\\_JOBS\\_SIZE\\_MAX](#) was removed after 8.0.32.

- Error number: 1864; Symbol: [ER\\_MTA\\_EVENT\\_BIGGER\\_PENDING\\_JOBS\\_SIZE\\_MAX](#); SQLSTATE: HY000

Message: Cannot schedule event %s, relay-log name %s, position %s to Worker thread because its size %lu exceeds %lu of replica\_pending\_jobs\_size\_max.

[ER\\_MTA\\_EVENT\\_BIGGER\\_PENDING\\_JOBS\\_SIZE\\_MAX](#) was added in 8.0.33.

- Error number: 1866; Symbol: [ER\\_BINLOG\\_LOGICAL\\_CORRUPTION](#); SQLSTATE: HY000

Message: The binary log file '%s' is logically corrupted: %s

- Error number: 1867; Symbol: [ER\\_WARN\\_PURGE\\_LOG\\_IN\\_USE](#); SQLSTATE: HY000

Message: file %s was not purged because it was being read by %d thread(s), purged only %d out of %d files.

- Error number: 1868; Symbol: [ER\\_WARN\\_PURGE\\_LOG\\_IS\\_ACTIVE](#); SQLSTATE: HY000

Message: file %s was not purged because it is the active log file.

- Error number: 1869; Symbol: [ER\\_AUTO\\_INCREMENT\\_CONFLICT](#); SQLSTATE: HY000

- 
- Message: Auto-increment value in UPDATE conflicts with internally generated values
- Error number: 1870; Symbol: [WARN\\_ON\\_BLOCKHOLE\\_IN\\_RBR](#); SQLSTATE: HY000  
Message: Row events are not logged for %s statements that modify BLACKHOLE tables in row format.  
Table(s): '%s'
  - Error number: 1871; Symbol: [ER\\_SLAVE\\_MI\\_INIT\\_REPOSITORY](#); SQLSTATE: HY000  
Message: Slave failed to initialize master info structure from the repository  
[ER\\_SLAVE\\_MI\\_INIT\\_REPOSITORY](#) was removed after 8.0.32.
  - Error number: 1871; Symbol: [ER\\_REPLICA\\_CM\\_INIT\\_REPOSITORY](#); SQLSTATE: HY000  
Message: Replica failed to initialize connection metadata structure from the repository  
[ER\\_REPLICA\\_CM\\_INIT\\_REPOSITORY](#) was added in 8.0.33.
  - Error number: 1872; Symbol: [ER\\_SLAVE\\_RLI\\_INIT\\_REPOSITORY](#); SQLSTATE: HY000  
Message: Slave failed to initialize relay log info structure from the repository  
[ER\\_SLAVE\\_RLI\\_INIT\\_REPOSITORY](#) was removed after 8.0.32.
  - Error number: 1872; Symbol: [ER\\_REPLICA\\_AM\\_INIT\\_REPOSITORY](#); SQLSTATE: HY000  
Message: Replica failed to initialize applier metadata structure from the repository  
[ER\\_REPLICA\\_AM\\_INIT\\_REPOSITORY](#) was added in 8.0.33.
  - Error number: 1873; Symbol: [ER\\_ACCESS\\_DENIED\\_CHANGE\\_USER\\_ERROR](#); SQLSTATE: 28000  
Message: Access denied trying to change to user '%s'@'%s' (using password: %s). Disconnecting.
  - Error number: 1874; Symbol: [ER\\_INNO\\_DB\\_READ\\_ONLY](#); SQLSTATE: HY000  
Message: InnoDB is in read only mode.
  - Error number: 1875; Symbol: [ER\\_STOP\\_SLAVE\\_SQL\\_THREAD\\_TIMEOUT](#); SQLSTATE: HY000  
Message: STOP SLAVE command execution is incomplete: Slave SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.  
[ER\\_STOP\\_SLAVE\\_SQL\\_THREAD\\_TIMEOUT](#) was removed after 8.0.32.
  - Error number: 1875; Symbol: [ER\\_STOP\\_REPLICA\\_SQL\\_THREAD\\_TIMEOUT](#); SQLSTATE: HY000  
Message: STOP REPLICA command execution is incomplete: Replica SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.  
[ER\\_STOP\\_REPLICA\\_SQL\\_THREAD\\_TIMEOUT](#) was added in 8.0.33.
  - Error number: 1876; Symbol: [ER\\_STOP\\_SLAVE\\_IO\\_THREAD\\_TIMEOUT](#); SQLSTATE: HY000  
Message: STOP SLAVE command execution is incomplete: Slave IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.  
[ER\\_STOP\\_SLAVE\\_IO\\_THREAD\\_TIMEOUT](#) was removed after 8.0.32.



- 
- Error number: [1876](#); Symbol: [ER\\_STOP\\_REPLICA\\_IO\\_THREAD\\_TIMEOUT](#); SQLSTATE: [HY000](#)  
Message: STOP REPLICA command execution is incomplete: Replica IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.  
[ER\\_STOP\\_REPLICA\\_IO\\_THREAD\\_TIMEOUT](#) was added in 8.0.33.
  - Error number: [1877](#); Symbol: [ER\\_TABLE\\_CORRUPT](#); SQLSTATE: [HY000](#)  
Message: Operation cannot be performed. The table '%s.%s' is missing, corrupt or contains bad data.
  - Error number: [1878](#); Symbol: [ER\\_TEMP\\_FILE\\_WRITE\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Temporary file write failure.
  - Error number: [1879](#); Symbol: [ER\\_INNOODB\\_FT\\_AUX\\_NOT\\_HEX\\_ID](#); SQLSTATE: [HY000](#)  
Message: Upgrade index name failed, please use create index(alter table) algorithm copy to rebuild index.
  - Error number: [1880](#); Symbol: [ER\\_OLD\\_TEMPORALS\\_UPGRADED](#); SQLSTATE: [HY000](#)  
Message: TIME/TIMESTAMP/DATETIME columns of old format have been upgraded to the new format.
  - Error number: [1881](#); Symbol: [ER\\_INNOODB\\_FORCED\\_RECOVERY](#); SQLSTATE: [HY000](#)  
Message: Operation not allowed when innodb\_force\_recovery > 0.
  - Error number: [1882](#); Symbol: [ER\\_AES\\_INVALID\\_IV](#); SQLSTATE: [HY000](#)  
Message: The initialization vector supplied to %s is too short. Must be at least %d bytes long
  - Error number: [1883](#); Symbol: [ER\\_PLUGIN\\_CANNOT\\_BE\\_UNINSTALLED](#); SQLSTATE: [HY000](#)  
Message: Plugin '%s' cannot be uninstalled now. %s
  - Error number: [1884](#); Symbol: [ER\\_GTID\\_UNSAFE\\_BINLOG\\_SPLITTABLE\\_STATEMENT\\_AND\\_GTID\\_GROUP](#); SQLSTATE: [HY000](#)  
Message: Cannot execute statement because it needs to be written to the binary log as multiple statements, and this is not allowed when @@SESSION.GTID\_NEXT == 'UUID:NUMBER'.  
[ER\\_GTID\\_UNSAFE\\_BINLOG\\_SPLITTABLE\\_STATEMENT\\_AND\\_GTID\\_GROUP](#) was removed after 8.0.4.
  - Error number: [1884](#); Symbol: [ER\\_GTID\\_UNSAFE\\_BINLOG\\_SPLITTABLE\\_STATEMENT\\_AND\\_ASSIGNED\\_GTID](#); SQLSTATE: [HY000](#)  
Message: Cannot execute statement because it needs to be written to the binary log as multiple statements, and this is not allowed when @@SESSION.GTID\_NEXT == 'UUID:NUMBER'.  
[ER\\_GTID\\_UNSAFE\\_BINLOG\\_SPLITTABLE\\_STATEMENT\\_AND\\_ASSIGNED\\_GTID](#) was added in 8.0.11.
  - Error number: [1885](#); Symbol: [ER\\_SLAVE\\_HAS\\_MORE\\_GTIDS\\_THAN\\_MASTER](#); SQLSTATE: [HY000](#)  
Message: Slave has more GTIDs than the master has, using the master's SERVER\_UUID. This may indicate that the end of the binary log was truncated or that the last binary log file was lost, e.g., after a power or disk failure when sync\_binlog != 1. The master may or may not have rolled back transactions that were already replicated to the slave. Suggest to replicate any transactions that master has rolled

---

back from slave to master, and/or commit empty transactions on master to account for transactions that have been committed on master but are not included in GTID\_EXECUTED.

[ER\\_SLAVE\\_HAS\\_MORE\\_GTIDS\\_THAN\\_MASTER](#) was removed after 8.0.32.

- Error number: 1885; Symbol: [ER\\_REPLICA\\_HAS\\_MORE\\_GTIDS\\_THAN\\_SOURCE](#); SQLSTATE: HY000

Message: Replica has more GTIDs than the source has, using the source's SERVER\_UUID. This may indicate that the the last binary log file was truncated or lost, e.g., after a power failure when sync\_binlog != 1. The source may have rolled back transactions that were already replicated to the replica. Replicate any transactions that source has rolled back from replica to source, and/or commit empty transactions on source to account for transactions that have been committed on source but are not included in GTID\_EXECUTED.

[ER\\_REPLICA\\_HAS\\_MORE\\_GTIDS\\_THAN\\_SOURCE](#) was added in 8.0.33.

- Error number: 1886; Symbol: [ER\\_MISSING\\_KEY](#); SQLSTATE: HY000

Message: The table '%s.%s' does not have the necessary key(s) defined on it. Please check the table definition and create index(s) accordingly.

[ER\\_MISSING\\_KEY](#) was added in 8.0.4.

- Error number: 1887; Symbol: [WARN\\_NAMED\\_PIPE\\_ACCESS\\_EVERYONE](#); SQLSTATE: HY000

Message: Setting named\_pipe\_full\_access\_group='%s' is insecure. Consider using a Windows group with fewer members.

[WARN\\_NAMED\\_PIPE\\_ACCESS\\_EVERYONE](#) was added in 8.0.17.

- Error number: 3000; Symbol: [ER\\_FILE\\_CORRUPT](#); SQLSTATE: HY000

Message: File %s is corrupted

- Error number: 3001; Symbol: [ER\\_ERROR\\_ON\\_MASTER](#); SQLSTATE: HY000

Message: Query partially completed on the master (error on master: %d) and was aborted. There is a chance that your master is inconsistent at this point. If you are sure that your master is ok, run this query manually on the slave and then restart the slave with SET GLOBAL SQL\_REPLICA\_SKIP\_COUNTER=1; START SLAVE;. Query:'%s'

[ER\\_ERROR\\_ON\\_MASTER](#) was removed after 8.0.32.

- Error number: 3001; Symbol: [ER\\_ERROR\\_ON\\_SOURCE](#); SQLSTATE: HY000

Message: Query partially completed on the source (error on source: %d) and was aborted. There is a chance that your source is inconsistent at this point. If you are sure that your source is ok, run this query manually on the replica and then restart the replica with SET GLOBAL SQL\_REPLICA\_SKIP\_COUNTER=1; START REPLICA;. Query:'%s'

[ER\\_ERROR\\_ON\\_SOURCE](#) was added in 8.0.33.

- Error number: 3003; Symbol: [ER\\_STORAGE\\_ENGINE\\_NOT\\_LOADED](#); SQLSTATE: HY000

Message: Storage engine for table '%s'.'%s' is not loaded.

- Error number: 3004; Symbol: [ER\\_GET\\_STACKED\\_DA\\_WITHOUT\\_ACTIVE\\_HANDLER](#); SQLSTATE: 0Z002

---

Message: GET STACKED DIAGNOSTICS when handler not active

- Error number: 3005; Symbol: [ER\\_WARN\\_LEGACY\\_SYNTAX\\_CONVERTED](#); SQLSTATE: HY000

Message: %s is no longer supported. The statement was converted to %s.

- Error number: 3006; Symbol: [ER\\_BINLOG\\_UNSAFE\\_FULLTEXT\\_PLUGIN](#); SQLSTATE: HY000

Message: Statement is unsafe because it uses a fulltext parser plugin which may not return the same value on the replica.

- Error number: 3007; Symbol: [ER\\_CANNOT\\_DISCARD\\_TEMPORARY\\_TABLE](#); SQLSTATE: HY000

Message: Cannot DISCARD/IMPORT tablespace associated with temporary table

- Error number: 3008; Symbol: [ER\\_FK\\_DEPTH\\_EXCEEDED](#); SQLSTATE: HY000

Message: Foreign key cascade delete/update exceeds max depth of %d.

- Error number: 3009; Symbol: [ER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_PLEASE\\_UPDATE\\_V2](#); SQLSTATE: HY000

Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

- Error number: 3010; Symbol: [ER\\_WARN\\_TRIGGER\\_DOESNT\\_HAVE\\_CREATED](#); SQLSTATE: HY000

Message: Trigger %s.%s.%s does not have CREATED attribute.

- Error number: 3011; Symbol: [ER\\_REFERENCED\\_TRG\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: HY000

Message: Referenced trigger '%s' for the given action time and event type does not exist.

- Error number: 3012; Symbol: [ER\\_EXPLAIN\\_NOT\\_SUPPORTED](#); SQLSTATE: HY000

Message: EXPLAIN FOR CONNECTION command is supported only for SELECT/UPDATE/INSERT/DELETE/REPLACE

- Error number: 3013; Symbol: [ER\\_INVALID\\_FIELD\\_SIZE](#); SQLSTATE: HY000

Message: Invalid size for column '%s'.

- Error number: 3014; Symbol: [ER\\_MISSING\\_HA\\_CREATE\\_OPTION](#); SQLSTATE: HY000

Message: Table storage engine '%s' found required create option missing

- Error number: 3015; Symbol: [ER\\_ENGINE\\_OUT\\_OF\\_MEMORY](#); SQLSTATE: HY000

Message: Out of memory in storage engine '%s'.

- Error number: 3016; Symbol: [ER\\_PASSWORD\\_EXPIRE\\_ANONYMOUS\\_USER](#); SQLSTATE: HY000

Message: The password for anonymous user cannot be expired.

- Error number: 3017; Symbol: [ER\\_SLAVE\\_SQL\\_THREAD\\_MUST\\_STOP](#); SQLSTATE: HY000

Message: This operation cannot be performed with a running slave sql thread; run STOP SLAVE SQL\_THREAD first

---

[ER\\_SLAVE\\_SQL\\_THREAD\\_MUST\\_STOP](#) was removed after 8.0.32.

- Error number: 3017; Symbol: [ER\\_REPLICA\\_SQL\\_THREAD\\_MUST\\_STOP](#); SQLSTATE: HY000  
Message: This operation cannot be performed with a running replica sql thread; run STOP REPLICA SQL\_THREAD first

[ER\\_REPLICA\\_SQL\\_THREAD\\_MUST\\_STOP](#) was added in 8.0.33.

- Error number: 3018; Symbol: [ER\\_NO\\_FT\\_MATERIALIZED\\_SUBQUERY](#); SQLSTATE: HY000  
Message: Cannot create FULLTEXT index on materialized subquery
- Error number: 3019; Symbol: [ER\\_INNODB\\_UNDO\\_LOG\\_FULL](#); SQLSTATE: HY000  
Message: Undo Log error: %s
- Error number: 3020; Symbol: [ER\\_INVALID\\_ARGUMENT\\_FOR\\_LOGARITHM](#); SQLSTATE: 2201E  
Message: Invalid argument for logarithm
- Error number: 3021; Symbol: [ER\\_SLAVE\\_CHANNEL\\_IO\\_THREAD\\_MUST\\_STOP](#); SQLSTATE: HY000  
Message: This operation cannot be performed with a running slave io thread; run STOP SLAVE IO\_THREAD FOR CHANNEL '%s' first.

[ER\\_SLAVE\\_CHANNEL\\_IO\\_THREAD\\_MUST\\_STOP](#) was removed after 8.0.32.

- Error number: 3021; Symbol: [ER\\_REPLICA\\_CHANNEL\\_IO\\_THREAD\\_MUST\\_STOP](#); SQLSTATE: HY000  
Message: This operation cannot be performed with a running replica io thread; run STOP REPLICA IO\_THREAD FOR CHANNEL '%s' first.

[ER\\_REPLICA\\_CHANNEL\\_IO\\_THREAD\\_MUST\\_STOP](#) was added in 8.0.33.

- Error number: 3022; Symbol: [ER\\_WARN\\_OPEN\\_TEMP\\_TABLES\\_MUST\\_BE\\_ZERO](#); SQLSTATE: HY000  
Message: This operation may not be safe when the replica has temporary tables. The tables will be kept open until the server restarts or until the tables are deleted by any replicated DROP statement. Suggest to wait until `replica_open_temp_tables = 0`.
- Error number: 3023; Symbol: [ER\\_WARN\\_ONLY\\_MASTER\\_LOG\\_FILE\\_NO\\_POS](#); SQLSTATE: HY000  
Message: CHANGE MASTER TO with a MASTER\_LOG\_FILE clause but no MASTER\_LOG\_POS clause may not be safe. The old position value may not be valid for the new binary log file.

[ER\\_WARN\\_ONLY\\_MASTER\\_LOG\\_FILE\\_NO\\_POS](#) was removed after 8.0.32.

- Error number: 3023; Symbol: [ER\\_WARN\\_ONLY\\_SOURCE\\_LOG\\_FILE\\_NO\\_POS](#); SQLSTATE: HY000  
Message: CHANGE REPLICATION SOURCE TO with a SOURCE\_LOG\_FILE clause but no SOURCE\_LOG\_POS clause may not be safe. The old position value may not be valid for the new binary log file.

[ER\\_WARN\\_ONLY\\_SOURCE\\_LOG\\_FILE\\_NO\\_POS](#) was added in 8.0.33.

- Error number: 3024; Symbol: [ER\\_QUERY\\_TIMEOUT](#); SQLSTATE: HY000  
Message: Query execution was interrupted, maximum statement execution time exceeded

- 
- Error number: [3025](#); Symbol: [ER\\_NON\\_RO\\_SELECT\\_DISABLE\\_TIMER](#); SQLSTATE: [HY000](#)  
Message: Select is not a read only statement, disabling timer
  - Error number: [3026](#); Symbol: [ER\\_DUP\\_LIST\\_ENTRY](#); SQLSTATE: [HY000](#)  
Message: Duplicate entry '%s'.
  - Error number: [3028](#); Symbol: [ER\\_AGGREGATE\\_ORDER\\_FOR\\_UNION](#); SQLSTATE: [HY000](#)  
Message: Expression #%u of ORDER BY contains aggregate function and applies to a UNION, EXCEPT or INTERSECT
  - Error number: [3029](#); Symbol: [ER\\_AGGREGATE\\_ORDER\\_NON\\_AGG\\_QUERY](#); SQLSTATE: [HY000](#)  
Message: Expression #%u of ORDER BY contains aggregate function and applies to the result of a non-aggregated query
  - Error number: [3030](#); Symbol: [ER\\_SLAVE\\_WORKER\\_STOPPED\\_PREVIOUS\\_THD\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Slave worker has stopped after at least one previous worker encountered an error when replica-preserve-commit-order was enabled. To preserve commit order, the last transaction executed by this thread has not been committed. When restarting the slave after fixing any failed threads, you should fix this worker as well.  
  
[ER\\_SLAVE\\_WORKER\\_STOPPED\\_PREVIOUS\\_THD\\_ERROR](#) was removed after 8.0.32.
  - Error number: [3030](#); Symbol: [ER\\_REPLICA\\_WORKER\\_STOPPED\\_PREVIOUS\\_THD\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Replica worker has stopped after at least one previous worker encountered an error when replica-preserve-commit-order was enabled. To preserve commit order, the last transaction executed by this thread has not been committed. When restarting the replica after fixing any failed threads, you should fix this worker as well.  
  
[ER\\_REPLICA\\_WORKER\\_STOPPED\\_PREVIOUS\\_THD\\_ERROR](#) was added in 8.0.33.
  - Error number: [3031](#); Symbol: [ER\\_DONT\\_SUPPORT\\_SLAVE\\_PRESERVE\\_COMMIT\\_ORDER](#); SQLSTATE: [HY000](#)  
Message: slave\_preserve\_commit\_order is not supported %s.  
  
[ER\\_DONT\\_SUPPORT\\_SLAVE\\_PRESERVE\\_COMMIT\\_ORDER](#) was removed after 8.0.25.
  - Error number: [3031](#); Symbol: [ER\\_DONT\\_SUPPORT\\_REPLICA\\_PRESERVE\\_COMMIT\\_ORDER](#); SQLSTATE: [HY000](#)  
Message: replica\_preserve\_commit\_order is not supported %s.  
  
[ER\\_DONT\\_SUPPORT\\_REPLICA\\_PRESERVE\\_COMMIT\\_ORDER](#) was added in 8.0.26.
  - Error number: [3032](#); Symbol: [ER\\_SERVER\\_OFFLINE\\_MODE](#); SQLSTATE: [HY000](#)  
Message: The server is currently in offline mode
-

- 
- Error number: 3033; Symbol: `ER_GIS_DIFFERENT_SRIDS`; SQLSTATE: `HY000`  
Message: Binary geometry function %s given two geometries of different srids: %u and %u, which should have been identical.  
Geometry values passed as arguments to spatial functions must have the same SRID value.
  - Error number: 3034; Symbol: `ER_GIS_UNSUPPORTED_ARGUMENT`; SQLSTATE: `HY000`  
Message: Calling geometry function %s with unsupported types of arguments.  
A spatial function was called with a combination of argument types that the function does not support.
  - Error number: 3035; Symbol: `ER_GIS_UNKNOWN_ERROR`; SQLSTATE: `HY000`  
Message: Unknown GIS error occurred in function %s.
  - Error number: 3036; Symbol: `ER_GIS_UNKNOWN_EXCEPTION`; SQLSTATE: `HY000`  
Message: Unknown exception caught in GIS function %s.
  - Error number: 3037; Symbol: `ER_GIS_INVALID_DATA`; SQLSTATE: `22023`  
Message: Invalid GIS data provided to function %s.  
A spatial function was called with an argument not recognized as a valid geometry value.
  - Error number: 3038; Symbol: `ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION`; SQLSTATE: `HY000`  
Message: The geometry has no data in function %s.
  - Error number: 3039; Symbol: `ER_BOOST_GEOMETRY_CENTROID_EXCEPTION`; SQLSTATE: `HY000`  
Message: Unable to calculate centroid because geometry is empty in function %s.
  - Error number: 3040; Symbol: `ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION`; SQLSTATE: `HY000`  
Message: Geometry overlay calculation error: geometry data is invalid in function %s.
  - Error number: 3041; Symbol: `ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION`; SQLSTATE: `HY000`  
Message: Geometry turn info calculation error: geometry data is invalid in function %s.
  - Error number: 3042; Symbol: `ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION`; SQLSTATE: `HY000`  
Message: Analysis procedures of intersection points interrupted unexpectedly in function %s.
  - Error number: 3043; Symbol: `ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION`; SQLSTATE: `HY000`  
Message: Unknown exception thrown in function %s.
  - Error number: 3044; Symbol: `ER_STD_BAD_ALLOC_ERROR`; SQLSTATE: `HY000`  
Message: Memory allocation error: %s in function %s.
  - Error number: 3045; Symbol: `ER_STD_DOMAIN_ERROR`; SQLSTATE: `HY000`  
Message: Domain error: %s in function %s.

- 
- Error number: 3046; Symbol: [ER\\_STD\\_LENGTH\\_ERROR](#); SQLSTATE: HY000  
Message: Length error: %s in function %s.
  - Error number: 3047; Symbol: [ER\\_STD\\_INVALID\\_ARGUMENT](#); SQLSTATE: HY000  
Message: Invalid argument error: %s in function %s.
  - Error number: 3048; Symbol: [ER\\_STD\\_OUT\\_OF\\_RANGE\\_ERROR](#); SQLSTATE: HY000  
Message: Out of range error: %s in function %s.
  - Error number: 3049; Symbol: [ER\\_STD\\_OVERFLOW\\_ERROR](#); SQLSTATE: HY000  
Message: Overflow error: %s in function %s.
  - Error number: 3050; Symbol: [ER\\_STD\\_RANGE\\_ERROR](#); SQLSTATE: HY000  
Message: Range error: %s in function %s.
  - Error number: 3051; Symbol: [ER\\_STD\\_UNDERFLOW\\_ERROR](#); SQLSTATE: HY000  
Message: Underflow error: %s in function %s.
  - Error number: 3052; Symbol: [ER\\_STD\\_LOGIC\\_ERROR](#); SQLSTATE: HY000  
Message: Logic error: %s in function %s.
  - Error number: 3053; Symbol: [ER\\_STD\\_RUNTIME\\_ERROR](#); SQLSTATE: HY000  
Message: Runtime error: %s in function %s.
  - Error number: 3054; Symbol: [ER\\_STD\\_UNKNOWN\\_EXCEPTION](#); SQLSTATE: HY000  
Message: Unknown exception: %s in function %s.
  - Error number: 3055; Symbol: [ER\\_GIS\\_DATA\\_WRONG\\_ENDIANESS](#); SQLSTATE: HY000  
Message: Geometry byte string must be little endian.
  - Error number: 3056; Symbol: [ER\\_CHANGE\\_MASTER\\_PASSWORD\\_LENGTH](#); SQLSTATE: HY000  
Message: The password provided for the replication user exceeds the maximum length of 32 characters  
[ER\\_CHANGE\\_MASTER\\_PASSWORD\\_LENGTH](#) was removed after 8.0.32.
  - Error number: 3056; Symbol: [ER\\_CHANGE\\_SOURCE\\_PASSWORD\\_LENGTH](#); SQLSTATE: HY000  
Message: The password provided for the replication user exceeds the maximum length of 32 characters  
[ER\\_CHANGE\\_SOURCE\\_PASSWORD\\_LENGTH](#) was added in 8.0.33.
  - Error number: 3057; Symbol: [ER\\_USER\\_LOCK\\_WRONG\\_NAME](#); SQLSTATE: 42000  
Message: Incorrect user-level lock name '%s'. The name is empty, NULL, or can not be expressed in the current character-set.
  - Error number: 3058; Symbol: [ER\\_USER\\_LOCK\\_DEADLOCK](#); SQLSTATE: HY000  
Message: Deadlock found when trying to get user-level lock; try rolling back transaction/releasing locks and restarting lock acquisition.

---

This error is returned when the metadata locking subsystem detects a deadlock for an attempt to acquire a named lock with `GET_LOCK`.

- Error number: 3059; Symbol: `ER_REPLACE_INACCESSIBLE_ROWS`; SQLSTATE: `HY000`  
Message: REPLACE cannot be executed as it requires deleting rows that are not in the view
- Error number: 3060; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_GIS`; SQLSTATE: `HY000`  
Message: Do not support online operation on table with GIS index
- Error number: 3061; Symbol: `ER_ILLEGAL_USER_VAR`; SQLSTATE: `42000`  
Message: User variable name '%s' is illegal
- Error number: 3062; Symbol: `ER_GTID_MODE_OFF`; SQLSTATE: `HY000`  
Message: Cannot %s when GTID\_MODE = OFF.
- Error number: 3064; Symbol: `ER_INCORRECT_TYPE`; SQLSTATE: `HY000`  
Message: Incorrect type for argument %s in function %s.
- Error number: 3065; Symbol: `ER_FIELD_IN_ORDER_NOT_SELECT`; SQLSTATE: `HY000`  
Message: Expression #%u of ORDER BY clause is not in SELECT list, references column '%s' which is not in SELECT list; this is incompatible with %s
- Error number: 3066; Symbol: `ER_AGGREGATE_IN_ORDER_NOT_SELECT`; SQLSTATE: `HY000`  
Message: Expression #%u of ORDER BY clause is not in SELECT list, contains aggregate function; this is incompatible with %s
- Error number: 3067; Symbol: `ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN`; SQLSTATE: `HY000`  
Message: Supplied filter list contains a value which is not in the required format 'db\_pattern.table\_pattern'
- Error number: 3068; Symbol: `ER_NET_OK_PACKET_TOO_LARGE`; SQLSTATE: `08S01`  
Message: OK packet too large
- Error number: 3069; Symbol: `ER_INVALID_JSON_DATA`; SQLSTATE: `HY000`  
Message: Invalid JSON data provided to function %s: %s
- Error number: 3070; Symbol: `ER_INVALID_GEOJSON_MISSING_MEMBER`; SQLSTATE: `HY000`  
Message: Invalid GeoJSON data provided to function %s: Missing required member '%s'
- Error number: 3071; Symbol: `ER_INVALID_GEOJSON_WRONG_TYPE`; SQLSTATE: `HY000`  
Message: Invalid GeoJSON data provided to function %s: Member '%s' must be of type '%s'
- Error number: 3072; Symbol: `ER_INVALID_GEOJSON_UNSPECIFIED`; SQLSTATE: `HY000`  
Message: Invalid GeoJSON data provided to function %s



- 
- Error number: 3073; Symbol: `ER_DIMENSION_UNSUPPORTED`; SQLSTATE: `HY000`  
Message: Unsupported number of coordinate dimensions in function %s: Found %u, expected %u  
`ER_DIMENSION_UNSUPPORTED` was removed after 8.0.32.
  - Error number: 3074; Symbol: `ER_SLAVE_CHANNEL_DOES_NOT_EXIST`; SQLSTATE: `HY000`  
Message: Slave channel '%s' does not exist.  
`ER_SLAVE_CHANNEL_DOES_NOT_EXIST` was removed after 8.0.32.
  - Error number: 3074; Symbol: `ER_REPLICA_CHANNEL_DOES_NOT_EXIST`; SQLSTATE: `HY000`  
Message: Replica channel '%s' does not exist.  
`ER_REPLICA_CHANNEL_DOES_NOT_EXIST` was added in 8.0.33.
  - Error number: 3076; Symbol: `ER_SLAVE_CHANNEL_NAME_INVALID_OR_TOO_LONG`; SQLSTATE: `HY000`  
Message: Couldn't create channel: Channel name is either invalid or too long.  
`ER_SLAVE_CHANNEL_NAME_INVALID_OR_TOO_LONG` was removed after 8.0.32.
  - Error number: 3076; Symbol: `ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG`; SQLSTATE: `HY000`  
Message: Couldn't create channel: Channel name is either invalid or too long.  
`ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG` was added in 8.0.33.
  - Error number: 3077; Symbol: `ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY`; SQLSTATE: `HY000`  
Message: To have multiple channels, repository cannot be of type FILE; Please check the repository configuration and convert them to TABLE.  
`ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY` was removed after 8.0.32.
  - Error number: 3077; Symbol: `ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY`; SQLSTATE: `HY000`  
Message: To have multiple channels, repository cannot be of type FILE; Please check the repository configuration and convert them to TABLE.  
`ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY` was added in 8.0.33.
  - Error number: 3079; Symbol: `ER_SLAVE_MULTIPLE_CHANNELS_CMD`; SQLSTATE: `HY000`  
Message: Multiple channels exist on the slave. Please provide channel name as an argument.  
`ER_SLAVE_MULTIPLE_CHANNELS_CMD` was removed after 8.0.32.
  - Error number: 3079; Symbol: `ER_REPLICA_MULTIPLE_CHANNELS_CMD`; SQLSTATE: `HY000`  
Message: Multiple channels exist on the replica. Please provide channel name as an argument.  
`ER_REPLICA_MULTIPLE_CHANNELS_CMD` was added in 8.0.33.
  - Error number: 3080; Symbol: `ER_SLAVE_MAX_CHANNELS_EXCEEDED`; SQLSTATE: `HY000`  
Message: Maximum number of replication channels allowed exceeded.

---

`ER_SLAVE_MAX_CHANNELS_EXCEEDED` was removed after 8.0.32.

- Error number: 3080; Symbol: `ER_REPLICA_MAX_CHANNELS_EXCEEDED`; SQLSTATE: `HY000`

Message: Maximum number of replication channels allowed exceeded.

`ER_REPLICA_MAX_CHANNELS_EXCEEDED` was added in 8.0.33.

- Error number: 3081; Symbol: `ER_SLAVE_CHANNEL_MUST_STOP`; SQLSTATE: `HY000`

Message: This operation cannot be performed with running replication threads; run STOP SLAVE FOR CHANNEL '%s' first

`ER_SLAVE_CHANNEL_MUST_STOP` was removed after 8.0.32.

- Error number: 3081; Symbol: `ER_REPLICA_CHANNEL_MUST_STOP`; SQLSTATE: `HY000`

Message: This operation cannot be performed with running replication threads; run STOP REPLICA FOR CHANNEL '%s' first

`ER_REPLICA_CHANNEL_MUST_STOP` was added in 8.0.33.

- Error number: 3082; Symbol: `ER_SLAVE_CHANNEL_NOT_RUNNING`; SQLSTATE: `HY000`

Message: This operation requires running replication threads; configure slave and run START SLAVE FOR CHANNEL '%s'

`ER_SLAVE_CHANNEL_NOT_RUNNING` was removed after 8.0.32.

- Error number: 3082; Symbol: `ER_REPLICA_CHANNEL_NOT_RUNNING`; SQLSTATE: `HY000`

Message: This operation requires running replication threads; configure replica and run START REPLICA FOR CHANNEL '%s'

`ER_REPLICA_CHANNEL_NOT_RUNNING` was added in 8.0.33.

- Error number: 3083; Symbol: `ER_SLAVE_CHANNEL_WAS_RUNNING`; SQLSTATE: `HY000`

Message: Replication thread(s) for channel '%s' are already running.

`ER_SLAVE_CHANNEL_WAS_RUNNING` was removed after 8.0.32.

- Error number: 3083; Symbol: `ER_REPLICA_CHANNEL_WAS_RUNNING`; SQLSTATE: `HY000`

Message: Replication thread(s) for channel '%s' are already running.

`ER_REPLICA_CHANNEL_WAS_RUNNING` was added in 8.0.33.

- Error number: 3084; Symbol: `ER_SLAVE_CHANNEL_WAS_NOT_RUNNING`; SQLSTATE: `HY000`

Message: Replication thread(s) for channel '%s' are already stopped.

`ER_SLAVE_CHANNEL_WAS_NOT_RUNNING` was removed after 8.0.32.

- Error number: 3084; Symbol: `ER_REPLICA_CHANNEL_WAS_NOT_RUNNING`; SQLSTATE: `HY000`

Message: Replication thread(s) for channel '%s' are already stopped.

`ER_REPLICA_CHANNEL_WAS_NOT_RUNNING` was added in 8.0.33.

- 
- Error number: 3085; Symbol: [ER\\_SLAVE\\_CHANNEL\\_SQL\\_THREAD\\_MUST\\_STOP](#); SQLSTATE: HY000  
Message: This operation cannot be performed with a running slave sql thread; run STOP SLAVE SQL\_THREAD FOR CHANNEL '%s' first.  
[ER\\_SLAVE\\_CHANNEL\\_SQL\\_THREAD\\_MUST\\_STOP](#) was removed after 8.0.32.
  - Error number: 3085; Symbol: [ER\\_REPLICA\\_CHANNEL\\_SQL\\_THREAD\\_MUST\\_STOP](#); SQLSTATE: HY000  
Message: This operation cannot be performed with a running replica sql thread; run STOP REPLICA SQL\_THREAD FOR CHANNEL '%s' first.  
[ER\\_REPLICA\\_CHANNEL\\_SQL\\_THREAD\\_MUST\\_STOP](#) was added in 8.0.33.
  - Error number: 3086; Symbol: [ER\\_SLAVE\\_CHANNEL\\_SQL\\_SKIP\\_COUNTER](#); SQLSTATE: HY000  
Message: When sql\_replica\_skip\_counter > 0, it is not allowed to start more than one SQL thread by using 'START SLAVE [SQL\_THREAD]'. Value of sql\_replica\_skip\_counter can only be used by one SQL thread at a time. Please use 'START SLAVE [SQL\_THREAD] FOR CHANNEL' to start the SQL thread which will use the value of sql\_replica\_skip\_counter.  
[ER\\_SLAVE\\_CHANNEL\\_SQL\\_SKIP\\_COUNTER](#) was removed after 8.0.32.
  - Error number: 3086; Symbol: [ER\\_REPLICA\\_CHANNEL\\_SQL\\_SKIP\\_COUNTER](#); SQLSTATE: HY000  
Message: When sql\_replica\_skip\_counter > 0, it is not allowed to start more than one SQL thread by using 'START REPLICA [SQL\_THREAD]'. Value of sql\_replica\_skip\_counter can only be used by one SQL thread at a time. Please use 'START REPLICA [SQL\_THREAD] FOR CHANNEL' to start the SQL thread which will use the value of sql\_replica\_skip\_counter.  
[ER\\_REPLICA\\_CHANNEL\\_SQL\\_SKIP\\_COUNTER](#) was added in 8.0.33.
  - Error number: 3087; Symbol: [ER\\_WRONG\\_FIELD\\_WITH\\_GROUP\\_V2](#); SQLSTATE: HY000  
Message: Expression #%u of %s is not in GROUP BY clause and contains nonaggregated column '%s' which is not functionally dependent on columns in GROUP BY clause; this is incompatible with sql\_mode=only\_full\_group\_by
  - Error number: 3088; Symbol: [ER\\_MIX\\_OF\\_GROUP\\_FUNC\\_AND\\_FIELDS\\_V2](#); SQLSTATE: HY000  
Message: In aggregated query without GROUP BY, expression #%u of %s contains nonaggregated column '%s'; this is incompatible with sql\_mode=only\_full\_group\_by
  - Error number: 3089; Symbol: [ER\\_WARN\\_DEPRECATED\\_SYSVAR\\_UPDATE](#); SQLSTATE: HY000  
Message: Updating '%s' is deprecated. It will be made read-only in a future release.
  - Error number: 3090; Symbol: [ER\\_WARN\\_DEPRECATED\\_SQLMODE](#); SQLSTATE: HY000  
Message: Changing sql mode '%s' is deprecated. It will be removed in a future release.
  - Error number: 3091; Symbol: [ER\\_CANNOT\\_LOG\\_PARTIAL\\_DROP\\_DATABASE\\_WITH\\_GTID](#); SQLSTATE: HY000  
Message: DROP DATABASE failed; some tables may have been dropped but the database directory remains. The GTID has not been added to GTID\_EXECUTED and the statement was not written to the binary log. Fix this as follows: (1) remove all files from the database directory %s; (2) SET GTID\_NEXT='%s'; (3) DROP DATABASE `'%s``.
-

- 
- Error number: `3092`; Symbol: `ER_GROUP_REPLICATION_CONFIGURATION`; SQLSTATE: `HY000`  
Message: The server is not configured properly to be an active member of the group. Please see more details on error log.
  - Error number: `3093`; Symbol: `ER_GROUP_REPLICATION_RUNNING`; SQLSTATE: `HY000`  
Message: The `START GROUP_REPLICATION` command failed since the group is already running.
  - Error number: `3094`; Symbol: `ER_GROUP_REPLICATION_APPLIER_INIT_ERROR`; SQLSTATE: `HY000`  
Message: The `START GROUP_REPLICATION` command failed as the applier module failed to start.
  - Error number: `3095`; Symbol: `ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIMEOUT`; SQLSTATE: `HY000`  
Message: The `STOP GROUP_REPLICATION` command execution is incomplete: The applier thread got the stop signal while it was busy. The applier thread will stop once the current task is complete.
  - Error number: `3096`; Symbol: `ER_GROUP_REPLICATION_COMMUNICATION_LAYER_SESSION_ERROR`; SQLSTATE: `HY000`  
Message: The `START GROUP_REPLICATION` command failed as there was an error when initializing the group communication layer.
  - Error number: `3097`; Symbol: `ER_GROUP_REPLICATION_COMMUNICATION_LAYER_JOIN_ERROR`; SQLSTATE: `HY000`  
Message: The `START GROUP_REPLICATION` command failed as there was an error when joining the communication group.
  - Error number: `3098`; Symbol: `ER_BEFORE_DML_VALIDATION_ERROR`; SQLSTATE: `HY000`  
Message: The table does not comply with the requirements by an external plugin.
  - Error number: `3099`; Symbol: `ER_PREVENTS_VARIABLE_WITHOUT_RBR`; SQLSTATE: `HY000`  
Message: Cannot change the value of variable %s without binary log format as ROW.  
`transaction_write_set_extraction` option value is set and `binlog_format` is not ROW.
  - Error number: `3100`; Symbol: `ER_RUN_HOOK_ERROR`; SQLSTATE: `HY000`  
Message: Error on observer while running replication hook '%s'.
  - Error number: `3101`; Symbol: `ER_TRANSACTION_ROLLBACK_DURING_COMMIT`; SQLSTATE: `40000`  
Message: Plugin instructed the server to rollback the current transaction.  
  
When using Group Replication, this means that a transaction failed the group certification process, due to one or more members detecting a potential conflict, and was thus rolled back. See [Group Replication](#).
  - Error number: `3102`; Symbol: `ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`  
Message: Expression of generated column '%s' contains a disallowed function.
  - Error number: `3103`; Symbol: `ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN`; SQLSTATE: `HY000`

---

Message: INPLACE ADD or DROP of virtual columns cannot be combined with other ALTER TABLE actions

- Error number: 3104; Symbol: [ER\\_WRONG\\_FK\\_OPTION\\_FOR\\_GENERATED\\_COLUMN](#); SQLSTATE: HY000

Message: Cannot define foreign key with %s clause on a generated column.

- Error number: 3105; Symbol: [ER\\_NON\\_DEFAULT\\_VALUE\\_FOR\\_GENERATED\\_COLUMN](#); SQLSTATE: HY000

Message: The value specified for generated column '%s' in table '%s' is not allowed.

- Error number: 3106; Symbol: [ER\\_UNSUPPORTED\\_ACTION\\_ON\\_GENERATED\\_COLUMN](#); SQLSTATE: HY000

Message: '%s' is not supported for generated columns.

- Error number: 3107; Symbol: [ER\\_GENERATED\\_COLUMN\\_NON\\_PRIOR](#); SQLSTATE: HY000

Message: Generated column can refer only to generated columns defined prior to it.

To address this issue, change the table definition to define each generated column later than any generated columns to which it refers.

- Error number: 3108; Symbol: [ER\\_DEPENDENT\\_BY\\_GENERATED\\_COLUMN](#); SQLSTATE: HY000

Message: Column '%s' has a generated column dependency.

You cannot drop or rename a generated column if another column refers to it. You must either drop those columns as well, or redefine them not to refer to the generated column.

- Error number: 3109; Symbol: [ER\\_GENERATED\\_COLUMN\\_REF\\_AUTO\\_INC](#); SQLSTATE: HY000

Message: Generated column '%s' cannot refer to auto-increment column.

- Error number: 3110; Symbol: [ER\\_FEATURE\\_NOT\\_AVAILABLE](#); SQLSTATE: HY000

Message: The '%s' feature is not available; you need to remove '%s' or use MySQL built with '%s'

- Error number: 3111; Symbol: [ER\\_CANT\\_SET\\_GTID\\_MODE](#); SQLSTATE: HY000

Message: SET @@GLOBAL.GTID\_MODE = %s is not allowed because %s.

- Error number: 3112; Symbol: [ER\\_CANT\\_USE\\_AUTO\\_POSITION\\_WITH\\_GTID\\_MODE\\_OFF](#); SQLSTATE: HY000

Message: The replication receiver thread%s cannot start in AUTO\_POSITION mode: this server uses @@GLOBAL.GTID\_MODE = OFF.

- Error number: 3116; Symbol: [ER\\_CANT\\_ENFORCE\\_GTID\\_CONSISTENCY\\_WITH\\_ONGOING\\_GTID\\_VIOLATING\\_TX](#); SQLSTATE: HY000

Message: Cannot set ENFORCE\_GTID\_CONSISTENCY = ON because there are ongoing transactions that violate GTID consistency.

[ER\\_CANT\\_SET\\_ENFORCE\\_GTID\\_CONSISTENCY\\_ON\\_WITH\\_ONGOING\\_GTID\\_VIOLATING\\_TRANSACTIONS](#) was renamed to [ER\\_CANT\\_ENFORCE\\_GTID\\_CONSISTENCY\\_WITH\\_ONGOING\\_GTID\\_VIOLATING\\_TX](#).

- 
- Error number: 3117; Symbol: `ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TX`; SQLSTATE: HY000  
Message: There are ongoing transactions that violate GTID consistency.  
`ER_SET_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS` was renamed to `ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TX`.
  - Error number: 3118; Symbol: `ER_ACCOUNT_HAS_BEEN_LOCKED`; SQLSTATE: HY000  
Message: Access denied for user '%s'@'%s'. Account is locked.  
The account was locked with `CREATE USER ... ACCOUNT LOCK` or `ALTER USER ... ACCOUNT LOCK`. An administrator can unlock it with `ALTER USER ... ACCOUNT UNLOCK`.
  - Error number: 3119; Symbol: `ER_WRONG_TABLESPACE_NAME`; SQLSTATE: 42000  
Message: Incorrect tablespace name ` %s `
  - Error number: 3120; Symbol: `ER_TABLESPACE_IS_NOT_EMPTY`; SQLSTATE: HY000  
Message: Tablespace ` %s ` is not empty.
  - Error number: 3121; Symbol: `ER_WRONG_FILE_NAME`; SQLSTATE: HY000  
Message: Incorrect File Name '%s'.
  - Error number: 3122; Symbol: `ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION`; SQLSTATE: HY000  
Message: Inconsistent intersection points.
  - Error number: 3123; Symbol: `ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR`; SQLSTATE: HY000  
Message: Optimizer hint syntax error
  - Error number: 3124; Symbol: `ER_WARN_BAD_MAX_EXECUTION_TIME`; SQLSTATE: HY000  
Message: Unsupported MAX\_EXECUTION\_TIME
  - Error number: 3125; Symbol: `ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME`; SQLSTATE: HY000  
Message: MAX\_EXECUTION\_TIME hint is supported by top-level standalone SELECT statements only  
The `MAX_EXECUTION_TIME` optimizer hint is supported only for `SELECT` statements.
  - Error number: 3126; Symbol: `ER_WARN_CONFLICTING_HINT`; SQLSTATE: HY000  
Message: Hint %s is ignored as conflicting/duplicated
  - Error number: 3127; Symbol: `ER_WARN_UNKNOWN_QB_NAME`; SQLSTATE: HY000  
Message: Query block name %s is not found for %s hint
  - Error number: 3128; Symbol: `ER_UNRESOLVED_HINT_NAME`; SQLSTATE: HY000  
Message: Unresolved name %s for %s hint
-

- 
- Error number: [3129](#); Symbol: [ER\\_WARN\\_ON\\_MODIFYING\\_GTID\\_EXECUTED\\_TABLE](#); SQLSTATE: [HY000](#)  
  
Message: Please do not modify the %s table. This is a mysql internal system table to store GTIDs for committed transactions. Modifying it can lead to an inconsistent GTID state.
  - Error number: [3130](#); Symbol: [ER\\_PLUGGABLE\\_PROTOCOL\\_COMMAND\\_NOT\\_SUPPORTED](#); SQLSTATE: [HY000](#)  
  
Message: Command not supported by pluggable protocols
  - Error number: [3131](#); Symbol: [ER\\_LOCKING\\_SERVICE\\_WRONG\\_NAME](#); SQLSTATE: [42000](#)  
  
Message: Incorrect locking service lock name '%s'.  
  
A locking service name was specified as [NULL](#), the empty string, or a string longer than 64 characters. Namespace and lock names must be non-[NULL](#), nonempty, and no more than 64 characters long.
  - Error number: [3132](#); Symbol: [ER\\_LOCKING\\_SERVICE\\_DEADLOCK](#); SQLSTATE: [HY000](#)  
  
Message: Deadlock found when trying to get locking service lock; try releasing locks and restarting lock acquisition.
  - Error number: [3133](#); Symbol: [ER\\_LOCKING\\_SERVICE\\_TIMEOUT](#); SQLSTATE: [HY000](#)  
  
Message: Service lock wait timeout exceeded.
  - Error number: [3134](#); Symbol: [ER\\_GIS\\_MAX\\_POINTS\\_IN\\_GEOMETRY\\_OVERFLOWED](#); SQLSTATE: [HY000](#)  
  
Message: Parameter %s exceeds the maximum number of points in a geometry (%lu) in function %s.
  - Error number: [3135](#); Symbol: [ER\\_SQL\\_MODE\\_MERGED](#); SQLSTATE: [HY000](#)  
  
Message: 'NO\_ZERO\_DATE', 'NO\_ZERO\_IN\_DATE' and 'ERROR\_FOR\_DIVISION\_BY\_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.
  - Error number: [3136](#); Symbol: [ER\\_VTOKEN\\_PLUGIN\\_TOKEN\\_MISMATCH](#); SQLSTATE: [HY000](#)  
  
Message: Version token mismatch for %.\*s. Correct value %.\*s  
  
The client has set its [version\\_tokens\\_session](#) system variable to the list of tokens it requires the server to match, but the server token list has at least one matching token name that has a value different from what the client requires. See [Version Tokens](#).
  - Error number: [3137](#); Symbol: [ER\\_VTOKEN\\_PLUGIN\\_TOKEN\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
  
Message: Version token %.\*s not found.  
  
The client has set its [version\\_tokens\\_session](#) system variable to the list of tokens it requires the server to match, but the server token list is missing at least one of those tokens. See [Version Tokens](#).
  - Error number: [3138](#); Symbol: [ER\\_CANT\\_SET\\_VARIABLE\\_WHEN\\_OWNING\\_GTID](#); SQLSTATE: [HY000](#)  
  
Message: Variable %s cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.
  - Error number: [3139](#); Symbol: [ER\\_SLAVE\\_CHANNEL\\_OPERATION\\_NOT\\_ALLOWED](#); SQLSTATE: [HY000](#)
-

---

Message: %s cannot be performed on channel '%s'.

[ER\\_SLAVE\\_CHANNEL\\_OPERATION\\_NOT\\_ALLOWED](#) was removed after 8.0.32.

- Error number: 3139; Symbol: [ER\\_REPLICA\\_CHANNEL\\_OPERATION\\_NOT\\_ALLOWED](#); SQLSTATE: HY000

Message: %s cannot be performed on channel '%s'.

[ER\\_REPLICA\\_CHANNEL\\_OPERATION\\_NOT\\_ALLOWED](#) was added in 8.0.33.

- Error number: 3140; Symbol: [ER\\_INVALID\\_JSON\\_TEXT](#); SQLSTATE: 22032

Message: Invalid JSON text: "%s" at position %u in value for column '%s'.

- Error number: 3141; Symbol: [ER\\_INVALID\\_JSON\\_TEXT\\_IN\\_PARAM](#); SQLSTATE: 22032

Message: Invalid JSON text in argument %u to function %s: "%s" at position %u.%s

- Error number: 3142; Symbol: [ER\\_INVALID\\_JSON\\_BINARY\\_DATA](#); SQLSTATE: HY000

Message: The JSON binary value contains invalid data.

- Error number: 3143; Symbol: [ER\\_INVALID\\_JSON\\_PATH](#); SQLSTATE: 42000

Message: Invalid JSON path expression. The error is around character position %u.%s

- Error number: 3144; Symbol: [ER\\_INVALID\\_JSON\\_CHARSET](#); SQLSTATE: 22032

Message: Cannot create a JSON value from a string with CHARACTER SET '%s'.

- Error number: 3145; Symbol: [ER\\_INVALID\\_JSON\\_CHARSET\\_IN\\_FUNCTION](#); SQLSTATE: 22032

Message: Invalid JSON character data provided to function %s: '%s'; utf8 is required.

- Error number: 3146; Symbol: [ER\\_INVALID\\_TYPE\\_FOR\\_JSON](#); SQLSTATE: 22032

Message: Invalid data type for JSON data in argument %u to function %s; a JSON string or JSON type is required.

- Error number: 3147; Symbol: [ER\\_INVALID\\_CAST\\_TO\\_JSON](#); SQLSTATE: 22032

Message: Cannot CAST value to JSON.

- Error number: 3148; Symbol: [ER\\_INVALID\\_JSON\\_PATH\\_CHARSET](#); SQLSTATE: 42000

Message: A path expression must be encoded in the utf8 character set. The path expression '%s' is encoded in character set '%s'.

- Error number: 3149; Symbol: [ER\\_INVALID\\_JSON\\_PATH\\_WILDCARD](#); SQLSTATE: 42000

Message: In this situation, path expressions may not contain the \* and \*\* tokens or an array range.

- Error number: 3150; Symbol: [ER\\_JSON\\_VALUE\\_TOO\\_BIG](#); SQLSTATE: 22032

Message: The JSON value is too big to be stored in a JSON column.

- Error number: 3151; Symbol: [ER\\_JSON\\_KEY\\_TOO\\_BIG](#); SQLSTATE: 22032

Message: The JSON object contains a key name that is too long.



- 
- Error number: [3152](#); Symbol: [ER\\_JSON\\_USED\\_AS\\_KEY](#); SQLSTATE: [42000](#)  
Message: JSON column '%s' supports indexing only via generated columns on a specified JSON path.
  - Error number: [3153](#); Symbol: [ER\\_JSON\\_VACUOUS\\_PATH](#); SQLSTATE: [42000](#)  
Message: The path expression '\$' is not allowed in this context.
  - Error number: [3154](#); Symbol: [ER\\_JSON\\_BAD\\_ONE\\_OR\\_ALL\\_ARG](#); SQLSTATE: [42000](#)  
Message: The oneOrAll argument to %s may take these values: 'one' or 'all'.
  - Error number: [3155](#); Symbol: [ER\\_NUMERIC\\_JSON\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [22003](#)  
Message: Out of range JSON value for CAST to %s%s from column %s at row %ld
  - Error number: [3156](#); Symbol: [ER\\_INVALID\\_JSON\\_VALUE\\_FOR\\_CAST](#); SQLSTATE: [22018](#)  
Message: Invalid JSON value for CAST to %s%s from column %s at row %ld
  - Error number: [3157](#); Symbol: [ER\\_JSON\\_DOCUMENT\\_TOO\\_DEEP](#); SQLSTATE: [22032](#)  
Message: The JSON document exceeds the maximum depth.
  - Error number: [3158](#); Symbol: [ER\\_JSON\\_DOCUMENT\\_NULL\\_KEY](#); SQLSTATE: [22032](#)  
Message: JSON documents may not contain NULL member names.
  - Error number: [3159](#); Symbol: [ER\\_SECURE\\_TRANSPORT\\_REQUIRED](#); SQLSTATE: [HY000](#)  
Message: Connections using insecure transport are prohibited while --require\_secure\_transport=ON.  
  
With the [require\\_secure\\_transport](#) system variable, clients can connect only using secure transports. Qualifying connections are those using SSL, a Unix socket file, or shared memory.
  - Error number: [3160](#); Symbol: [ER\\_NO\\_SECURE\\_TRANSPORTS\\_CONFIGURED](#); SQLSTATE: [HY000](#)  
Message: No secure transports (SSL or Shared Memory) are configured, unable to set --require\_secure\_transport=ON.  
  
The [require\\_secure\\_transport](#) system variable cannot be enabled if the server does not support at least one secure transport. Configure the server with the required SSL keys/certificates to enable SSL connections, or enable the [shared\\_memory](#) system variable to enable shared-memory connections.
  - Error number: [3161](#); Symbol: [ER\\_DISABLED\\_STORAGE\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: Storage engine %s is disabled (Table creation is disallowed).  
  
An attempt was made to create a table or tablespace using a storage engine listed in the value of the [disabled\\_storage\\_engines](#) system variable, or to change an existing table or tablespace to such an engine. Choose a different storage engine.
  - Error number: [3162](#); Symbol: [ER\\_USER\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
Message: Authorization ID %s does not exist.
  - Error number: [3163](#); Symbol: [ER\\_USER\\_ALREADY\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Authorization ID %s already exists.

- 
- Error number: [3164](#); Symbol: [ER\\_AUDIT\\_API\\_ABORT](#); SQLSTATE: [HY000](#)  
Message: Aborted by Audit API ('%s';%d).  
This error indicates that an audit plugin terminated execution of an event. The message typically indicates the event subclass name and a numeric status value.
  - Error number: [3165](#); Symbol: [ER\\_INVALID\\_JSON\\_PATH\\_ARRAY\\_CELL](#); SQLSTATE: [42000](#)  
Message: A path expression is not a path to a cell in an array.
  - Error number: [3166](#); Symbol: [ER\\_BUFPOOL\\_RESIZE\\_INPROGRESS](#); SQLSTATE: [HY000](#)  
Message: Another buffer pool resize is already in progress.
  - Error number: [3167](#); Symbol: [ER\\_FEATURE\\_DISABLED\\_SEE\\_DOC](#); SQLSTATE: [HY000](#)  
Message: The '%s' feature is disabled; see the documentation for '%s'
  - Error number: [3168](#); Symbol: [ER\\_SERVER\\_ISNT\\_AVAILABLE](#); SQLSTATE: [HY000](#)  
Message: Server isn't available
  - Error number: [3169](#); Symbol: [ER\\_SESSION\\_WAS\\_KILLED](#); SQLSTATE: [HY000](#)  
Message: Session was killed
  - Error number: [3170](#); Symbol: [ER\\_CAPACITY\\_EXCEEDED](#); SQLSTATE: [HY000](#)  
Message: Memory capacity of %llu bytes for '%s' exceeded. %s
  - Error number: [3171](#); Symbol: [ER\\_CAPACITY\\_EXCEEDED\\_IN\\_RANGE\\_OPTIMIZER](#); SQLSTATE: [HY000](#)  
Message: Range optimization was not done for this query.
  - Error number: [3173](#); Symbol: [ER\\_CANT\\_WAIT\\_FOR\\_EXECUTED\\_GTID\\_SET\\_WHILE\\_OWNING\\_A\\_GTID](#); SQLSTATE: [HY000](#)  
Message: The client holds ownership of the GTID %s. Therefore, WAIT\_FOR\_EXECUTED\_GTID\_SET cannot wait for this GTID.
  - Error number: [3174](#); Symbol: [ER\\_CANNOT\\_ADD\\_FOREIGN\\_BASE\\_COL\\_VIRTUAL](#); SQLSTATE: [HY000](#)  
Message: Cannot add foreign key on the base column of indexed virtual column.
  - Error number: [3175](#); Symbol: [ER\\_CANNOT\\_CREATE\\_VIRTUAL\\_INDEX\\_CONSTRAINT](#); SQLSTATE: [HY000](#)  
Message: Cannot create index on virtual column whose base column has foreign constraint.
  - Error number: [3176](#); Symbol: [ER\\_ERROR\\_ON\\_MODIFYING\\_GTID\\_EXECUTED\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Please do not modify the %s table with an XA transaction. This is an internal system table used to store GTIDs for committed transactions. Although modifying it can lead to an inconsistent GTID state, if necessary you can modify it with a non-XA transaction.
  - Error number: [3177](#); Symbol: [ER\\_LOCK\\_REFUSED\\_BY\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: Lock acquisition refused by storage engine.

- 
- Error number: 3178; Symbol: [ER\\_UNSUPPORTED\\_ALTER\\_ONLINE\\_ON\\_VIRTUAL\\_COLUMN](#); SQLSTATE: HY000  
Message: ADD COLUMN col...VIRTUAL, ADD INDEX(col)
  - Error number: 3179; Symbol: [ER\\_MASTER\\_KEY\\_ROTATION\\_NOT\\_SUPPORTEDED\\_BY\\_SE](#); SQLSTATE: HY000  
Message: Master key rotation is not supported by storage engine.
  - Error number: 3181; Symbol: [ER\\_MASTER\\_KEY\\_ROTATION\\_BINLOG\\_FAILED](#); SQLSTATE: HY000  
Message: Write to binlog failed. However, master key rotation has been completed successfully.
  - Error number: 3182; Symbol: [ER\\_MASTER\\_KEY\\_ROTATION\\_SE\\_UNAVAILABLE](#); SQLSTATE: HY000  
Message: Storage engine is not available.
  - Error number: 3183; Symbol: [ER\\_TABLESPACE\\_CANNOT\\_ENCRYPT](#); SQLSTATE: HY000  
Message: This tablespace can't be encrypted.
  - Error number: 3184; Symbol: [ER\\_INVALID\\_ENCRYPTION\\_OPTION](#); SQLSTATE: HY000  
Message: Invalid encryption option.
  - Error number: 3185; Symbol: [ER\\_CANNOT\\_FIND\\_KEY\\_IN\\_KEYRING](#); SQLSTATE: HY000  
Message: Can't find master key from keyring, please check in the server log if a keyring is loaded and initialized successfully.
  - Error number: 3186; Symbol: [ER\\_CAPACITY\\_EXCEEDED\\_IN\\_PARSER](#); SQLSTATE: HY000  
Message: Parser bailed out for this query.
  - Error number: 3187; Symbol: [ER\\_UNSUPPORTED\\_ALTER\\_ENCRYPTION\\_INPLACE](#); SQLSTATE: HY000  
Message: Cannot alter encryption attribute by inplace algorithm.
  - Error number: 3188; Symbol: [ER\\_KEYRING\\_UDF\\_KEYRING\\_SERVICE\\_ERROR](#); SQLSTATE: HY000  
Message: Function '%s' failed because underlying keyring service returned an error. Please check if a keyring is installed and that provided arguments are valid for the keyring you are using.
  - Error number: 3189; Symbol: [ER\\_USER\\_COLUMN\\_OLD\\_LENGTH](#); SQLSTATE: HY000  
Message: It seems that your db schema is old. The %s column is 77 characters long and should be 93 characters long. Please perform the MySQL upgrade procedure.
  - Error number: 3190; Symbol: [ER\\_CANT\\_RESET\\_MASTER](#); SQLSTATE: HY000  
Message: RESET MASTER is not allowed because %s.  
[ER\\_CANT\\_RESET\\_MASTER](#) was removed after 8.0.32.
  - Error number: 3190; Symbol: [ER\\_CANT\\_RESET\\_SOURCE](#); SQLSTATE: HY000  
Message: RESET SOURCE is not allowed because %s.  
[ER\\_CANT\\_RESET\\_SOURCE](#) was added in 8.0.33.

- 
- Error number: 3191; Symbol: [ER\\_GROUP\\_REPLICATION\\_MAX\\_GROUP\\_SIZE](#); SQLSTATE: HY000  
Message: The START GROUP\_REPLICATION command failed since the group already has 9 members.
  - Error number: 3192; Symbol: [ER\\_CANNOT\\_ADD\\_FOREIGN\\_BASE\\_COL\\_STORED](#); SQLSTATE: HY000  
Message: Cannot add foreign key on the base column of stored column.
  - Error number: 3193; Symbol: [ER\\_TABLE\\_REFERENCED](#); SQLSTATE: HY000  
Message: Cannot complete the operation because table is referenced by another connection.
  - Error number: 3197; Symbol: [ER\\_XA\\_RETRY](#); SQLSTATE: HY000  
Message: The resource manager is not able to commit the transaction branch at this time. Please retry later.  
[ER\\_XA\\_RETRY](#) was added in 8.0.2.
  - Error number: 3198; Symbol: [ER\\_KEYRING\\_AWS\\_UDF\\_AWS\\_KMS\\_ERROR](#); SQLSTATE: HY000  
Message: Function %s failed due to: %s.  
[ER\\_KEYRING\\_AWS\\_UDF\\_AWS\\_KMS\\_ERROR](#) was added in 8.0.2.
  - Error number: 3199; Symbol: [ER\\_BINLOG\\_UNSAFE\\_XA](#); SQLSTATE: HY000  
Message: Statement is unsafe because it is being used inside a XA transaction. Concurrent XA transactions may deadlock on replicas when replicated using statements.  
[ER\\_BINLOG\\_UNSAFE\\_XA](#) was added in 8.0.2.
  - Error number: 3200; Symbol: [ER\\_UDF\\_ERROR](#); SQLSTATE: HY000  
Message: %s UDF failed; %s  
[ER\\_UDF\\_ERROR](#) was added in 8.0.4.
  - Error number: 3201; Symbol: [ER\\_KEYRING\\_MIGRATION\\_FAILURE](#); SQLSTATE: HY000  
Message: Can not perform keyring migration : %s  
[ER\\_KEYRING\\_MIGRATION\\_FAILURE](#) was added in 8.0.4.
  - Error number: 3202; Symbol: [ER\\_KEYRING\\_ACCESS\\_DENIED\\_ERROR](#); SQLSTATE: 42000  
Message: Access denied; you need %s privileges for this operation  
[ER\\_KEYRING\\_ACCESS\\_DENIED\\_ERROR](#) was added in 8.0.4.
  - Error number: 3203; Symbol: [ER\\_KEYRING\\_MIGRATION\\_STATUS](#); SQLSTATE: HY000  
Message: Keyring migration %s.  
[ER\\_KEYRING\\_MIGRATION\\_STATUS](#) was added in 8.0.4.
  - Error number: 3218; Symbol: [ER\\_AUDIT\\_LOG\\_UDF\\_READ\\_INVALID\\_MAX\\_ARRAY\\_LENGTH\\_ARG\\_VALUE](#); SQLSTATE: HY000

---

Message: Invalid "max\_array\_length" argument value.

[ER\\_AUDIT\\_LOG\\_UDF\\_READ\\_INVALID\\_MAX\\_ARRAY\\_LENGTH\\_ARG\\_VALUE](#) was added in 8.0.11.

- Error number: [3231](#); Symbol: [ER\\_WRITE\\_SET\\_EXCEEDS\\_LIMIT](#); SQLSTATE: [HY000](#)

Message: The size of writeset data for the current transaction exceeds a limit imposed by an external component. If using Group Replication check 'group\_replication\_transaction\_size\_limit'.

[ER\\_WRITE\\_SET\\_EXCEEDS\\_LIMIT](#) was added in 8.0.23.

- Error number: [3235](#); Symbol: [ER\\_AES\\_INVALID\\_KDF\\_NAME](#); SQLSTATE: [HY000](#)

Message: KDF method name is not valid. Please use hkdf or pbkdf2\_hmac method name

[ER\\_AES\\_INVALID\\_KDF\\_NAME](#) was added in 8.0.30.

- Error number: [3236](#); Symbol: [ER\\_AES\\_INVALID\\_KDF\\_ITERATIONS](#); SQLSTATE: [HY000](#)

Message: For KDF method pbkdf2\_hmac iterations value less than 1000 or more than 65535 is not allowed due to security reasons. Please provide iterations >= 1000 and iterations < 65535

[ER\\_AES\\_INVALID\\_KDF\\_ITERATIONS](#) was added in 8.0.30.

- Error number: [3237](#); Symbol: [WARN\\_AES\\_KEY\\_SIZE](#); SQLSTATE: [HY000](#)

Message: AES key size should be %d bytes length or secure KDF methods hkdf or pbkdf2\_hmac should be used, please provide exact AES key size or use KDF methods for better security.

[WARN\\_AES\\_KEY\\_SIZE](#) was added in 8.0.30.

- Error number: [3238](#); Symbol: [ER\\_AES\\_INVALID\\_KDF\\_OPTION\\_SIZE](#); SQLSTATE: [HY000](#)

Message: KDF option size is invalid, please provide valid size < %d bytes and not NULL

[ER\\_AES\\_INVALID\\_KDF\\_OPTION\\_SIZE](#) was added in 8.0.30.

- Error number: [3500](#); Symbol: [ER\\_UN SUPPORT\\_COMPRESSED\\_TEMPORARY\\_TABLE](#); SQLSTATE: [HY000](#)

Message: CREATE TEMPORARY TABLE is not allowed with ROW\_FORMAT=COMPRESSED or KEY\_BLOCK\_SIZE.

- Error number: [3501](#); Symbol: [ER\\_ACL\\_OPERATION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: The ACL operation failed due to the following error from SE: errcode %d - %s

- Error number: [3502](#); Symbol: [ER\\_UNSUPPORTED\\_INDEX\\_ALGORITHM](#); SQLSTATE: [HY000](#)

Message: This storage engine does not support the %s index algorithm, storage engine default was used instead.

- Error number: [3503](#); Symbol: [ER\\_NO\\_SUCH\\_DB](#); SQLSTATE: [42Y07](#)

Message: Database '%s' doesn't exist

- Error number: [3504](#); Symbol: [ER\\_TOO\\_BIG\\_ENUM](#); SQLSTATE: [HY000](#)

Message: Too many enumeration values for column %s.

- 
- Error number: 3505; Symbol: ER\_TOO\_LONG\_SET\_ENUM\_VALUE; SQLSTATE: HY000  
Message: Too long enumeration/set value for column %s.
  - Error number: 3506; Symbol: ER\_INVALID\_DD\_OBJECT; SQLSTATE: HY000  
Message: %s dictionary object is invalid. (%s)
  - Error number: 3507; Symbol: ER\_UPDATING\_DD\_TABLE; SQLSTATE: HY000  
Message: Failed to update %s dictionary object.
  - Error number: 3508; Symbol: ER\_INVALID\_DD\_OBJECT\_ID; SQLSTATE: HY000  
Message: Dictionary object id (%lu) does not exist.
  - Error number: 3509; Symbol: ER\_INVALID\_DD\_OBJECT\_NAME; SQLSTATE: HY000  
Message: Dictionary object name '%s' is invalid. (%s)
  - Error number: 3510; Symbol: ER\_TABLESPACE\_MISSING\_WITH\_NAME; SQLSTATE: HY000  
Message: Tablespace %s doesn't exist.
  - Error number: 3511; Symbol: ER\_TOO\_LONG\_ROUTINE\_COMMENT; SQLSTATE: HY000  
Message: Comment for routine '%s' is too long (max = %lu)
  - Error number: 3512; Symbol: ER\_SP\_LOAD\_FAILED; SQLSTATE: HY000  
Message: Failed to load routine '%s'.
  - Error number: 3513; Symbol: ER\_INVALID\_BITWISE\_OPERANDS\_SIZE; SQLSTATE: HY000  
Message: Binary operands of bitwise operators must be of equal length
  - Error number: 3514; Symbol: ER\_INVALID\_BITWISE\_AGGREGATE\_OPERANDS\_SIZE; SQLSTATE: HY000  
Message: Aggregate bitwise functions cannot accept arguments longer than 511 bytes; consider using the SUBSTRING() function
  - Error number: 3515; Symbol: ER\_WARN\_UNSUPPORTED\_HINT; SQLSTATE: HY000  
Message: Hints aren't supported in %s
  - Error number: 3516; Symbol: ER\_UNEXPECTED\_GEOMETRY\_TYPE; SQLSTATE: 22S01  
Message: %s value is a geometry of unexpected type %s in %s.
  - Error number: 3517; Symbol: ER\_SRS\_PARSE\_ERROR; SQLSTATE: SR002  
Message: Can't parse the spatial reference system definition of SRID %u.
  - Error number: 3518; Symbol: ER\_SRS\_PROJ\_PARAMETER\_MISSING; SQLSTATE: SR003  
Message: The spatial reference system definition for SRID %u does not specify the mandatory %s (EPSG %u) projection parameter.
  - Error number: 3519; Symbol: ER\_WARN\_SRS\_NOT\_FOUND; SQLSTATE: 01000

---

Message: There's no spatial reference system with SRID %u.

- Error number: 3520; Symbol: [ER\\_SRS\\_NOT\\_CARTESIAN](#); SQLSTATE: 22S00

Message: Function %s is only defined for Cartesian spatial reference systems, but one of its arguments is in SRID %u, which is not Cartesian.

- Error number: 3521; Symbol: [ER\\_SRS\\_NOT\\_CARTESIAN\\_UNDEFINED](#); SQLSTATE: SR001

Message: Function %s is only defined for Cartesian spatial reference systems, but one of its arguments is in SRID %u, which has not been defined.

- Error number: 3522; Symbol: [ER\\_PK\\_INDEX\\_CANT\\_BE\\_INVISIBLE](#); SQLSTATE: HY000

Message: A primary key index cannot be invisible

- Error number: 3523; Symbol: [ER\\_UNKNOWN\\_AUTHID](#); SQLSTATE: HY000

Message: Unknown authorization ID `%s` @ `%s`

- Error number: 3524; Symbol: [ER\\_FAILED\\_ROLE\\_GRANT](#); SQLSTATE: HY000

Message: Failed to grant `%s` to %s

- Error number: 3525; Symbol: [ER\\_OPEN\\_ROLE\\_TABLES](#); SQLSTATE: HY000

Message: Failed to open the security system tables

- Error number: 3526; Symbol: [ER\\_FAILED\\_DEFAULT\\_ROLES](#); SQLSTATE: HY000

Message: Failed to set default roles

- Error number: 3527; Symbol: [ER\\_COMPONENTS\\_NO\\_SCHEME](#); SQLSTATE: HY000

Message: Cannot find schema in specified URN: '%s'.

- Error number: 3528; Symbol: [ER\\_COMPONENTS\\_NO\\_SCHEME\\_SERVICE](#); SQLSTATE: HY000

Message: Cannot acquire scheme load service implementation for schema '%s' in specified URN: '%s'.

- Error number: 3529; Symbol: [ER\\_COMPONENTS\\_CANT\\_LOAD](#); SQLSTATE: HY000

Message: Cannot load component from specified URN: '%s'.

- Error number: 3530; Symbol: [ER\\_ROLE\\_NOT\\_GRANTED](#); SQLSTATE: HY000

Message: `%s` @ `%s` is not granted to `%s` @ `%s`

- Error number: 3531; Symbol: [ER\\_FAILED\\_REVOKE\\_ROLE](#); SQLSTATE: HY000

Message: Could not revoke role from `%s` @ `%s`

- Error number: 3532; Symbol: [ER\\_RENAME\\_ROLE](#); SQLSTATE: HY000

Message: Renaming of a role identifier is forbidden

- Error number: 3533; Symbol: [ER\\_COMPONENTS\\_CANT\\_ACQUIRE\\_SERVICE\\_IMPLEMENTATION](#); SQLSTATE: HY000

- 
- Message: Cannot acquire specified service implementation: '%s'.
- Error number: 3534; Symbol: `ER_COMPONENTS_CANT_SATISFY_DEPENDENCY`; SQLSTATE: `HY000`  
Message: Cannot satisfy dependency for service '%s' required by component '%s'.
  - Error number: 3535; Symbol: `ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPLEMENTATION`; SQLSTATE: `HY000`  
Message: Cannot register service implementation '%s' provided by component '%s'.
  - Error number: 3536; Symbol: `ER_COMPONENTS_LOAD_CANT_INITIALIZE`; SQLSTATE: `HY000`  
Message: Initialization method provided by component '%s' failed.
  - Error number: 3537; Symbol: `ER_COMPONENTS_UNLOAD_NOT_LOADED`; SQLSTATE: `HY000`  
Message: Component specified by URN '%s' to unload has not been loaded before.
  - Error number: 3538; Symbol: `ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE`; SQLSTATE: `HY000`  
Message: De-initialization method provided by component '%s' failed.
  - Error number: 3539; Symbol: `ER_COMPONENTS_CANT_RELEASE_SERVICE`; SQLSTATE: `HY000`  
Message: Release of previously acquired service implementation failed.
  - Error number: 3540; Symbol: `ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE`; SQLSTATE: `HY000`  
Message: Unregistration of service implementation '%s' provided by component '%s' failed during unloading of the component.
  - Error number: 3541; Symbol: `ER_COMPONENTS_CANT_UNLOAD`; SQLSTATE: `HY000`  
Message: Cannot unload component from specified URN: '%s'.
  - Error number: 3542; Symbol: `ER_WARN_UNLOAD_THE_NOT_PERSISTED`; SQLSTATE: `HY000`  
Message: The Persistent Dynamic Loader was used to unload a component '%s', but it was not used to load that component before.
  - Error number: 3543; Symbol: `ER_COMPONENT_TABLE_INCORRECT`; SQLSTATE: `HY000`  
Message: The `mysql.component` table is missing or has an incorrect definition.
  - Error number: 3544; Symbol: `ER_COMPONENT_MANIPULATE_ROW_FAILED`; SQLSTATE: `HY000`  
Message: Failed to manipulate component '%s' persistence data. Error code %d from storage engine.
  - Error number: 3545; Symbol: `ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP`; SQLSTATE: `HY000`  
Message: The component with specified URN: '%s' was specified in group more than once.
  - Error number: 3546; Symbol: `ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINTS`; SQLSTATE: `HY000`  
Message: @@GLOBAL.GTID\_PURGED cannot be changed: %s



- 
- Error number: 3547; Symbol: [ER\\_CANNOT\\_LOCK\\_USER\\_MANAGEMENT\\_CACHES](#); SQLSTATE: HY000  
Message: Can not lock user management caches for processing.
  - Error number: 3548; Symbol: [ER\\_SRS\\_NOT\\_FOUND](#); SQLSTATE: SR001  
Message: There's no spatial reference system with SRID %u.
  - Error number: 3549; Symbol: [ER\\_VARIABLE\\_NOT\\_PERSISTED](#); SQLSTATE: HY000  
Message: Variables cannot be persisted. Please retry.
  - Error number: 3550; Symbol: [ER\\_IS\\_QUERY\\_INVALID\\_CLAUSE](#); SQLSTATE: HY000  
Message: Information schema queries do not support the '%s' clause.
  - Error number: 3551; Symbol: [ER\\_UNABLE\\_TO\\_STORE\\_STATISTICS](#); SQLSTATE: HY000  
Message: Unable to store dynamic %s statistics into data dictionary.
  - Error number: 3552; Symbol: [ER\\_NO\\_SYSTEM\\_SCHEMA\\_ACCESS](#); SQLSTATE: HY000  
Message: Access to system schema '%s' is rejected.
  - Error number: 3553; Symbol: [ER\\_NO\\_SYSTEM\\_TABLESPACE\\_ACCESS](#); SQLSTATE: HY000  
Message: Access to system tablespace '%s' is rejected.
  - Error number: 3554; Symbol: [ER\\_NO\\_SYSTEM\\_TABLE\\_ACCESS](#); SQLSTATE: HY000  
Message: Access to %s '%s.%s' is rejected.
  - Error number: 3555; Symbol: [ER\\_NO\\_SYSTEM\\_TABLE\\_ACCESS\\_FOR\\_DICTIONARY\\_TABLE](#); SQLSTATE: HY000  
Message: data dictionary table  
[ER\\_NO\\_SYSTEM\\_TABLE\\_ACCESS\\_FOR\\_DICTIONARY\\_TABLE](#) was added in 8.0.1.
  - Error number: 3556; Symbol: [ER\\_NO\\_SYSTEM\\_TABLE\\_ACCESS\\_FOR\\_SYSTEM\\_TABLE](#); SQLSTATE: HY000  
Message: system table  
[ER\\_NO\\_SYSTEM\\_TABLE\\_ACCESS\\_FOR\\_SYSTEM\\_TABLE](#) was added in 8.0.1.
  - Error number: 3557; Symbol: [ER\\_NO\\_SYSTEM\\_TABLE\\_ACCESS\\_FOR\\_TABLE](#); SQLSTATE: HY000  
Message: table  
[ER\\_NO\\_SYSTEM\\_TABLE\\_ACCESS\\_FOR\\_TABLE](#) was added in 8.0.1.
  - Error number: 3558; Symbol: [ER\\_INVALID\\_OPTION\\_KEY](#); SQLSTATE: 22023  
Message: Invalid option key '%s' in function %s.  
[ER\\_INVALID\\_OPTION\\_KEY](#) was added in 8.0.1.
  - Error number: 3559; Symbol: [ER\\_INVALID\\_OPTION\\_VALUE](#); SQLSTATE: 22023

---

Message: Invalid value '%s' for option '%s' in function '%s'.

[ER\\_INVALID\\_OPTION\\_VALUE](#) was added in 8.0.1.

- Error number: 3560; Symbol: [ER\\_INVALID\\_OPTION\\_KEY\\_VALUE\\_PAIR](#); SQLSTATE: 22023

Message: The string '%s' is not a valid key %c value pair in function %s.

[ER\\_INVALID\\_OPTION\\_KEY\\_VALUE\\_PAIR](#) was added in 8.0.1.

- Error number: 3561; Symbol: [ER\\_INVALID\\_OPTION\\_START\\_CHARACTER](#); SQLSTATE: 22023

Message: The options argument in function %s starts with the invalid character '%c'.

[ER\\_INVALID\\_OPTION\\_START\\_CHARACTER](#) was added in 8.0.1.

- Error number: 3562; Symbol: [ER\\_INVALID\\_OPTION\\_END\\_CHARACTER](#); SQLSTATE: 22023

Message: The options argument in function %s ends with the invalid character '%c'.

[ER\\_INVALID\\_OPTION\\_END\\_CHARACTER](#) was added in 8.0.1.

- Error number: 3563; Symbol: [ER\\_INVALID\\_OPTION\\_CHARACTERS](#); SQLSTATE: 22023

Message: The options argument in function %s contains the invalid character sequence '%s'.

[ER\\_INVALID\\_OPTION\\_CHARACTERS](#) was added in 8.0.1.

- Error number: 3564; Symbol: [ER\\_DUPLICATE\\_OPTION\\_KEY](#); SQLSTATE: 22023

Message: Duplicate option key '%s' in function '%s'.

[ER\\_DUPLICATE\\_OPTION\\_KEY](#) was added in 8.0.1.

- Error number: 3565; Symbol: [ER\\_WARN\\_SRS\\_NOT\\_FOUND\\_AXIS\\_ORDER](#); SQLSTATE: 01000

Message: There's no spatial reference system with SRID %u. The axis order is unknown.

[ER\\_WARN\\_SRS\\_NOT\\_FOUND\\_AXIS\\_ORDER](#) was added in 8.0.1.

- Error number: 3566; Symbol: [ER\\_NO\\_ACCESS\\_TO\\_NATIVE\\_FCT](#); SQLSTATE: HY000

Message: Access to native function '%s' is rejected.

[ER\\_NO\\_ACCESS\\_TO\\_NATIVE\\_FCT](#) was added in 8.0.1.

- Error number: 3567; Symbol: [ER\\_RESET\\_MASTER\\_TO\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: HY000

Message: The requested value '%llu' for the next binary log index is out of range. Please use a value between '1' and '%lu'.

[ER\\_RESET\\_MASTER\\_TO\\_VALUE\\_OUT\\_OF\\_RANGE](#) was added in 8.0.1, removed after 8.0.32.

- Error number: 3567; Symbol: [ER\\_RESET\\_SOURCE\\_TO\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: HY000

Message: The requested value '%llu' for the next binary log index is out of range. Please use a value between '1' and '%lu'.

[ER\\_RESET\\_SOURCE\\_TO\\_VALUE\\_OUT\\_OF\\_RANGE](#) was added in 8.0.33.

- 
- Error number: 3568; Symbol: [ER\\_UNRESOLVED\\_TABLE\\_LOCK](#); SQLSTATE: HY000  
Message: Unresolved table name %s in locking clause.  
[ER\\_UNRESOLVED\\_TABLE\\_LOCK](#) was added in 8.0.1.
  - Error number: 3569; Symbol: [ER\\_DUPLICATE\\_TABLE\\_LOCK](#); SQLSTATE: HY000  
Message: Table %s appears in multiple locking clauses.  
[ER\\_DUPLICATE\\_TABLE\\_LOCK](#) was added in 8.0.1.
  - Error number: 3570; Symbol: [ER\\_BINLOG\\_UNSAFE\\_SKIP\\_LOCKED](#); SQLSTATE: HY000  
Message: Statement is unsafe because it uses SKIP LOCKED. The set of inserted values is non-deterministic.  
[ER\\_BINLOG\\_UNSAFE\\_SKIP\\_LOCKED](#) was added in 8.0.1.
  - Error number: 3571; Symbol: [ER\\_BINLOG\\_UNSAFE\\_NOWAIT](#); SQLSTATE: HY000  
Message: Statement is unsafe because it uses NOWAIT. Whether the command will succeed or fail is not deterministic.  
[ER\\_BINLOG\\_UNSAFE\\_NOWAIT](#) was added in 8.0.1.
  - Error number: 3572; Symbol: [ER\\_LOCK\\_NOWAIT](#); SQLSTATE: HY000  
Message: Statement aborted because lock(s) could not be acquired immediately and NOWAIT is set.  
[ER\\_LOCK\\_NOWAIT](#) was added in 8.0.1.
  - Error number: 3573; Symbol: [ER\\_CTE\\_RECURSIVE\\_REQUIRES\\_UNION](#); SQLSTATE: HY000  
Message: Recursive Common Table Expression '%s' should contain a UNION  
[ER\\_CTE\\_RECURSIVE\\_REQUIRES\\_UNION](#) was added in 8.0.1.
  - Error number: 3574; Symbol: [ER\\_CTE\\_RECURSIVE\\_REQUIRES\\_NONRECURSIVE\\_FIRST](#); SQLSTATE: HY000  
Message: Recursive Common Table Expression '%s' should have one or more non-recursive query blocks followed by one or more recursive ones  
[ER\\_CTE\\_RECURSIVE\\_REQUIRES\\_NONRECURSIVE\\_FIRST](#) was added in 8.0.1.
  - Error number: 3575; Symbol: [ER\\_CTE\\_RECURSIVE\\_FORBIDS\\_AGGREGATION](#); SQLSTATE: HY000  
Message: Recursive Common Table Expression '%s' can contain neither aggregation nor window functions in recursive query block  
[ER\\_CTE\\_RECURSIVE\\_FORBIDS\\_AGGREGATION](#) was added in 8.0.1.
  - Error number: 3576; Symbol: [ER\\_CTE\\_RECURSIVE\\_FORBIDDEN\\_JOIN\\_ORDER](#); SQLSTATE: HY000  
Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must neither be in the right argument of a LEFT JOIN, nor be forced to be non-first with join order hints  
[ER\\_CTE\\_RECURSIVE\\_FORBIDDEN\\_JOIN\\_ORDER](#) was added in 8.0.1.

- 
- Error number: 3577; Symbol: `ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE`; SQLSTATE: HY000  
Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must be referenced only once, and not in any subquery  
`ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE` was added in 8.0.1.
  - Error number: 3578; Symbol: `ER_SWITCH_TMP_ENGINE`; SQLSTATE: HY000  
Message: '%s' requires @@internal\_tmp\_disk\_storage\_engine=InnoDB  
`ER_SWITCH_TMP_ENGINE` was added in 8.0.1.
  - Error number: 3579; Symbol: `ER_WINDOW_NO_SUCH_WINDOW`; SQLSTATE: HY000  
Message: Window name '%s' is not defined.  
`ER_WINDOW_NO_SUCH_WINDOW` was added in 8.0.2.
  - Error number: 3580; Symbol: `ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH`; SQLSTATE: HY000  
Message: There is a circularity in the window dependency graph.  
`ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH` was added in 8.0.2.
  - Error number: 3581; Symbol: `ER_WINDOW_NO_CHILD_PARTITIONING`; SQLSTATE: HY000  
Message: A window which depends on another cannot define partitioning.  
`ER_WINDOW_NO_CHILD_PARTITIONING` was added in 8.0.2.
  - Error number: 3582; Symbol: `ER_WINDOW_NO_INHERIT_FRAME`; SQLSTATE: HY000  
Message: Window '%s' has a frame definition, so cannot be referenced by another window.  
`ER_WINDOW_NO_INHERIT_FRAME` was added in 8.0.2.
  - Error number: 3583; Symbol: `ER_WINDOW_NO_REDEFINE_ORDER_BY`; SQLSTATE: HY000  
Message: Window '%s' cannot inherit '%s' since both contain an ORDER BY clause.  
`ER_WINDOW_NO_REDEFINE_ORDER_BY` was added in 8.0.2.
  - Error number: 3584; Symbol: `ER_WINDOW_FRAME_START_ILLEGAL`; SQLSTATE: HY000  
Message: Window '%s': frame start cannot be UNBOUNDED FOLLOWING.  
`ER_WINDOW_FRAME_START_ILLEGAL` was added in 8.0.2.
  - Error number: 3585; Symbol: `ER_WINDOW_FRAME_END_ILLEGAL`; SQLSTATE: HY000  
Message: Window '%s': frame end cannot be UNBOUNDED PRECEDING.  
`ER_WINDOW_FRAME_END_ILLEGAL` was added in 8.0.2.
  - Error number: 3586; Symbol: `ER_WINDOW_FRAME_ILLEGAL`; SQLSTATE: HY000  
Message: Window '%s': frame start or end is negative, NULL or of non-integral type

---

`ER_WINDOW_FRAME_ILLEGAL` was added in 8.0.2.

- Error number: 3587; Symbol: `ER_WINDOW_RANGE_FRAME_ORDER_TYPE`; SQLSTATE: HY000

Message: Window '%s' with RANGE N PRECEDING/FOLLOWING frame requires exactly one ORDER BY expression, of numeric or temporal type

`ER_WINDOW_RANGE_FRAME_ORDER_TYPE` was added in 8.0.2.

- Error number: 3588; Symbol: `ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE`; SQLSTATE: HY000

Message: Window '%s' with RANGE frame has ORDER BY expression of datetime type. Only INTERVAL bound value allowed.

`ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE` was added in 8.0.2.

- Error number: 3589; Symbol: `ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE`; SQLSTATE: HY000

Message: Window '%s' with RANGE frame has ORDER BY expression of numeric type, INTERVAL bound value not allowed.

`ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE` was added in 8.0.2.

- Error number: 3590; Symbol: `ER_WINDOW_RANGE_BOUND_NOT_CONSTANT`; SQLSTATE: HY000

Message: Window '%s' has a non-constant frame bound.

`ER_WINDOW_RANGE_BOUND_NOT_CONSTANT` was added in 8.0.2.

- Error number: 3591; Symbol: `ER_WINDOW_DUPLICATE_NAME`; SQLSTATE: HY000

Message: Window '%s' is defined twice.

`ER_WINDOW_DUPLICATE_NAME` was added in 8.0.2.

- Error number: 3592; Symbol: `ER_WINDOW_ILLEGAL_ORDER_BY`; SQLSTATE: HY000

Message: Window '%s': ORDER BY or PARTITION BY uses legacy position indication which is not supported, use expression.

`ER_WINDOW_ILLEGAL_ORDER_BY` was added in 8.0.2.

- Error number: 3593; Symbol: `ER_WINDOW_INVALID_WINDOW_FUNC_USE`; SQLSTATE: HY000

Message: You cannot use the window function '%s' in this context.'

`ER_WINDOW_INVALID_WINDOW_FUNC_USE` was added in 8.0.2.

- Error number: 3594; Symbol: `ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE`; SQLSTATE: HY000

Message: You cannot use the alias '%s' of an expression containing a window function in this context.'

`ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE` was added in 8.0.2.

- Error number: 3595; Symbol: `ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW_SPEC`; SQLSTATE: HY000

Message: You cannot nest a window function in the specification of window '%s'.

- 
- [ER\\_WINDOW\\_NESTED\\_WINDOW\\_FUNC\\_USE\\_IN\\_WINDOW\\_SPEC](#) was added in 8.0.2.
- Error number: [3596](#); Symbol: [ER\\_WINDOW\\_ROWS\\_INTERVAL\\_USE](#); SQLSTATE: [HY000](#)  
Message: Window '%s': INTERVAL can only be used with RANGE frames.  
[ER\\_WINDOW\\_ROWS\\_INTERVAL\\_USE](#) was added in 8.0.2.
  - Error number: [3597](#); Symbol: [ER\\_WINDOW\\_NO\\_GROUP\\_ORDER](#); SQLSTATE: [HY000](#)  
Message: ASC or DESC with GROUP BY isn't allowed with window functions; put ASC or DESC in ORDER BY  
[ER\\_WINDOW\\_NO\\_GROUP\\_ORDER](#) was added in 8.0.2, removed after 8.0.12.
  - Error number: [3597](#); Symbol: [ER\\_WINDOW\\_NO\\_GROUP\\_ORDER\\_UNUSED](#); SQLSTATE: [HY000](#)  
Message: ASC or DESC with GROUP BY isn't allowed with window functions; put ASC or DESC in ORDER BY  
[ER\\_WINDOW\\_NO\\_GROUP\\_ORDER\\_UNUSED](#) was added in 8.0.13.
  - Error number: [3598](#); Symbol: [ER\\_WINDOW\\_EXPLAIN\\_JSON](#); SQLSTATE: [HY000](#)  
Message: To get information about window functions use EXPLAIN FORMAT=JSON  
[ER\\_WINDOW\\_EXPLAIN\\_JSON](#) was added in 8.0.2.
  - Error number: [3599](#); Symbol: [ER\\_WINDOW\\_FUNCTION\\_IGNORES\\_FRAME](#); SQLSTATE: [HY000](#)  
Message: Window function '%s' ignores the frame clause of window '%s' and aggregates over the whole partition  
[ER\\_WINDOW\\_FUNCTION\\_IGNORES\\_FRAME](#) was added in 8.0.2.
  - Error number: [3600](#); Symbol: [ER\\_WINDOW\\_SE\\_NOT\\_ACCEPTABLE](#); SQLSTATE: [HY000](#)  
Message: Windowing requires @@internal\_tmp\_mem\_storage\_engine=TempTable.  
[ER\\_WINDOW\\_SE\\_NOT\\_ACCEPTABLE](#) was added in 8.0.2, removed after 8.0.3.
  - Error number: [3600](#); Symbol: [ER\\_WL9236\\_NOW\\_UNUSED](#); SQLSTATE: [HY000](#)  
Message: Windowing requires @@internal\_tmp\_mem\_storage\_engine=TempTable.  
[ER\\_WL9236\\_NOW\\_UNUSED](#) was added in 8.0.4.
  - Error number: [3601](#); Symbol: [ER\\_INVALID\\_NO\\_OF\\_ARGS](#); SQLSTATE: [HY000](#)  
Message: Too many arguments for function %s: %lu; maximum allowed is %s.  
[ER\\_INVALID\\_NO\\_OF\\_ARGS](#) was added in 8.0.1.
  - Error number: [3602](#); Symbol: [ER\\_FIELD\\_IN\\_GROUPING\\_NOT\\_GROUP\\_BY](#); SQLSTATE: [HY000](#)  
Message: Argument #%u of GROUPING function is not in GROUP BY  
[ER\\_FIELD\\_IN\\_GROUPING\\_NOT\\_GROUP\\_BY](#) was added in 8.0.1.

- 
- Error number: 3603; Symbol: [ER\\_TOO\\_LONG\\_TABLESPACE\\_COMMENT](#); SQLSTATE: HY000  
Message: Comment for tablespace '%s' is too long (max = %lu)  
[ER\\_TOO\\_LONG\\_TABLESPACE\\_COMMENT](#) was added in 8.0.1.
  - Error number: 3604; Symbol: [ER\\_ENGINE\\_CANT\\_DROP\\_TABLE](#); SQLSTATE: HY000  
Message: Storage engine can't drop table '%s'  
[ER\\_ENGINE\\_CANT\\_DROP\\_TABLE](#) was added in 8.0.1.
  - Error number: 3605; Symbol: [ER\\_ENGINE\\_CANT\\_DROP\\_MISSING\\_TABLE](#); SQLSTATE: HY000  
Message: Storage engine can't drop table '%s' because it is missing. Use DROP TABLE IF EXISTS to remove it from data-dictionary.  
[ER\\_ENGINE\\_CANT\\_DROP\\_MISSING\\_TABLE](#) was added in 8.0.1.
  - Error number: 3606; Symbol: [ER\\_TABLESPACE\\_DUP\\_FILENAME](#); SQLSTATE: HY000  
Message: Duplicate file name for tablespace '%s'  
[ER\\_TABLESPACE\\_DUP\\_FILENAME](#) was added in 8.0.1.
  - Error number: 3607; Symbol: [ER\\_DB\\_DROP\\_RMDIR2](#); SQLSTATE: HY000  
Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.  
[ER\\_DB\\_DROP\\_RMDIR2](#) was added in 8.0.1.
  - Error number: 3608; Symbol: [ER\\_IMP\\_NO\\_FILES\\_MATCHED](#); SQLSTATE: HY000  
Message: No SDI files matched the pattern '%s'  
[ER\\_IMP\\_NO\\_FILES\\_MATCHED](#) was added in 8.0.1.
  - Error number: 3609; Symbol: [ER\\_IMP\\_SCHEMA\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: HY000  
Message: Schema '%s', referenced in SDI, does not exist.  
[ER\\_IMP\\_SCHEMA\\_DOES\\_NOT\\_EXIST](#) was added in 8.0.1.
  - Error number: 3610; Symbol: [ER\\_IMP\\_TABLE\\_ALREADY\\_EXISTS](#); SQLSTATE: HY000  
Message: Table '%s.%s', referenced in SDI, already exists.  
[ER\\_IMP\\_TABLE\\_ALREADY\\_EXISTS](#) was added in 8.0.1.
  - Error number: 3611; Symbol: [ER\\_IMP\\_INCOMPATIBLE\\_MYSQLD\\_VERSION](#); SQLSTATE: HY000  
Message: Imported mysqld\_version (%llu) is not compatible with current (%llu)  
[ER\\_IMP\\_INCOMPATIBLE\\_MYSQLD\\_VERSION](#) was added in 8.0.1.
  - Error number: 3612; Symbol: [ER\\_IMP\\_INCOMPATIBLE\\_DD\\_VERSION](#); SQLSTATE: HY000  
Message: Imported dd version (%u) is not compatible with current (%u)

- 
- `ER_IMP_INCOMPATIBLE_DD_VERSION` was added in 8.0.1.

    - Error number: 3613; Symbol: `ER_IMP_INCOMPATIBLE_SDI_VERSION`; SQLSTATE: HY000  
Message: Imported sdi version (%llu) is not compatible with current (%llu)  
`ER_IMP_INCOMPATIBLE_SDI_VERSION` was added in 8.0.1.
    - Error number: 3614; Symbol: `ER_WARN_INVALID_HINT`; SQLSTATE: HY000  
Message: Invalid number of arguments for hint %s  
`ER_WARN_INVALID_HINT` was added in 8.0.1.
    - Error number: 3615; Symbol: `ER_VAR_DOES_NOT_EXIST`; SQLSTATE: HY000  
Message: Variable %s does not exist in persisted config file  
`ER_VAR_DOES_NOT_EXIST` was added in 8.0.1.
    - Error number: 3616; Symbol: `ER_LONGITUDE_OUT_OF_RANGE`; SQLSTATE: 22S02  
Message: Longitude %f is out of range in function %s. It must be within (%f, %f].  
`ER_LONGITUDE_OUT_OF_RANGE` was added in 8.0.1.
    - Error number: 3617; Symbol: `ER_LATITUDE_OUT_OF_RANGE`; SQLSTATE: 22S03  
Message: Latitude %f is out of range in function %s. It must be within [%f, %f].  
`ER_LATITUDE_OUT_OF_RANGE` was added in 8.0.1.
    - Error number: 3618; Symbol: `ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS`; SQLSTATE: 22S00  
Message: %s(%s) has not been implemented for geographic spatial reference systems.  
`ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS` was added in 8.0.1.
    - Error number: 3619; Symbol: `ER_ILLEGAL_PRIVILEGE_LEVEL`; SQLSTATE: HY000  
Message: Illegal privilege level specified for %s  
`ER_ILLEGAL_PRIVILEGE_LEVEL` was added in 8.0.1.
    - Error number: 3620; Symbol: `ER_NO_SYSTEM_VIEW_ACCESS`; SQLSTATE: HY000  
Message: Access to system view INFORMATION\_SCHEMA.'%s' is rejected.  
`ER_NO_SYSTEM_VIEW_ACCESS` was added in 8.0.2.
    - Error number: 3621; Symbol: `ER_COMPONENT_FILTER_FLABBERGASTED`; SQLSTATE: HY000  
Message: The log-filter component "%s" got confused at "%s" ...  
`ER_COMPONENT_FILTER_FLABBERGASTED` was added in 8.0.2.
    - Error number: 3622; Symbol: `ER_PART_EXPR_TOO_LONG`; SQLSTATE: HY000  
Message: Partitioning expression is too long.



---

[ER\\_PART\\_EXPR\\_TOO\\_LONG](#) was added in 8.0.2.

- Error number: [3623](#); Symbol: [ER\\_UDF\\_DROP\\_DYNAMICALLY\\_REGISTERED](#); SQLSTATE: [HY000](#)  
Message: DROP FUNCTION can't drop a dynamically registered user defined function  
[ER\\_UDF\\_DROP\\_DYNAMICALLY\\_REGISTERED](#) was added in 8.0.2.
- Error number: [3624](#); Symbol: [ER\\_UNABLE\\_TO\\_STORE\\_COLUMN\\_STATISTICS](#); SQLSTATE: [HY000](#)  
Message: Unable to store column statistics for column '%s' in table '%s'. '%s'  
[ER\\_UNABLE\\_TO\\_STORE\\_COLUMN\\_STATISTICS](#) was added in 8.0.2.
- Error number: [3625](#); Symbol: [ER\\_UNABLE\\_TO\\_UPDATE\\_COLUMN\\_STATISTICS](#); SQLSTATE: [HY000](#)  
Message: Unable to update column statistics for column '%s' in table '%s'. '%s'  
[ER\\_UNABLE\\_TO\\_UPDATE\\_COLUMN\\_STATISTICS](#) was added in 8.0.2.
- Error number: [3626](#); Symbol: [ER\\_UNABLE\\_TO\\_DROP\\_COLUMN\\_STATISTICS](#); SQLSTATE: [HY000](#)  
Message: Unable to remove column statistics for column '%s' in table '%s'. '%s'  
[ER\\_UNABLE\\_TO\\_DROP\\_COLUMN\\_STATISTICS](#) was added in 8.0.2.
- Error number: [3627](#); Symbol: [ER\\_UNABLE\\_TO\\_BUILD\\_HISTOGRAM](#); SQLSTATE: [HY000](#)  
Message: Unable to build histogram statistics for column '%s' in table '%s'. '%s'  
[ER\\_UNABLE\\_TO\\_BUILD\\_HISTOGRAM](#) was added in 8.0.2.
- Error number: [3628](#); Symbol: [ER\\_MANDATORY\\_ROLE](#); SQLSTATE: [HY000](#)  
Message: The role %s is a mandatory role and can't be revoked or dropped. The restriction can be lifted by excluding the role identifier from the global variable mandatory\_roles.  
[ER\\_MANDATORY\\_ROLE](#) was added in 8.0.2.
- Error number: [3629](#); Symbol: [ER\\_MISSING\\_TABLESPACE\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Tablespace '%s' does not have a file named '%s'  
[ER\\_MISSING\\_TABLESPACE\\_FILE](#) was added in 8.0.3.
- Error number: [3630](#); Symbol: [ER\\_PERSIST\\_ONLY\\_ACCESS\\_DENIED\\_ERROR](#); SQLSTATE: [42000](#)  
Message: Access denied; you need %s privileges for this operation  
[ER\\_PERSIST\\_ONLY\\_ACCESS\\_DENIED\\_ERROR](#) was added in 8.0.3.
- Error number: [3631](#); Symbol: [ER\\_CMD\\_NEED\\_SUPER](#); SQLSTATE: [HY000](#)  
Message: You need the SUPER privilege for command '%s'  
[ER\\_CMD\\_NEED\\_SUPER](#) was added in 8.0.3.
- Error number: [3632](#); Symbol: [ER\\_PATH\\_IN\\_DATADIR](#); SQLSTATE: [HY000](#)

---

Message: Path is within the current data directory '%s'

[ER\\_PATH\\_IN\\_DATADIR](#) was added in 8.0.3.

- Error number: 3633; Symbol: [ER\\_DDL\\_IN\\_PROGRESS](#); SQLSTATE: HY000

Message: Concurrent DDL is performed during the operation. Please try again.

[ER\\_DDL\\_IN\\_PROGRESS](#) was added in 8.0.3, removed after 8.0.16.

- Error number: 3633; Symbol: [ER\\_CLONE\\_DDL\\_IN\\_PROGRESS](#); SQLSTATE: HY000

Message: Concurrent DDL is performed during clone operation. Please try again.

[ER\\_CLONE\\_DDL\\_IN\\_PROGRESS](#) was added in 8.0.17.

- Error number: 3634; Symbol: [ER\\_TOO\\_MANY\\_CONCURRENT\\_CLONES](#); SQLSTATE: HY000

Message: Too many concurrent clone operations. Maximum allowed - %d.

[ER\\_TOO\\_MANY\\_CONCURRENT\\_CLONES](#) was added in 8.0.3, removed after 8.0.16.

- Error number: 3634; Symbol: [ER\\_CLONE\\_TOO\\_MANY\\_CONCURRENT\\_CLONES](#); SQLSTATE: HY000

Message: Too many concurrent clone operations. Maximum allowed - %d.

[ER\\_CLONE\\_TOO\\_MANY\\_CONCURRENT\\_CLONES](#) was added in 8.0.17.

- Error number: 3635; Symbol: [ER\\_APPLIER\\_LOG\\_EVENT\\_VALIDATION\\_ERROR](#); SQLSTATE: HY000

Message: The table in transaction %s does not comply with the requirements by an external plugin.

[ER\\_APPLIER\\_LOG\\_EVENT\\_VALIDATION\\_ERROR](#) was added in 8.0.3.

- Error number: 3636; Symbol: [ER\\_CTE\\_MAX\\_RECURSION\\_DEPTH](#); SQLSTATE: HY000

Message: Recursive query aborted after %u iterations. Try increasing @@cte\_max\_recursion\_depth to a larger value.

[ER\\_CTE\\_MAX\\_RECURSION\\_DEPTH](#) was added in 8.0.3.

- Error number: 3637; Symbol: [ER\\_NOT\\_HINT\\_UPDATABLE\\_VARIABLE](#); SQLSTATE: HY000

Message: Variable %s cannot be set using SET\_VAR hint.

[ER\\_NOT\\_HINT\\_UPDATABLE\\_VARIABLE](#) was added in 8.0.3.

- Error number: 3638; Symbol: [ER\\_CREDENTIALS\\_CONTRADICT\\_TO\\_HISTORY](#); SQLSTATE: HY000

Message: Cannot use these credentials for '%.\*s@%.\*s' because they contradict the password history policy

[ER\\_CREDENTIALS\\_CONTRADICT\\_TO\\_HISTORY](#) was added in 8.0.3.

- Error number: 3639; Symbol: [ER\\_WARNING\\_PASSWORD\\_HISTORY\\_CLAUSES\\_VOID](#); SQLSTATE: HY000

Message: Non-zero password history clauses ignored for user '%s'@'%s' as its authentication plugin %s does not support password history

---

[ER\\_WARNING\\_PASSWORD\\_HISTORY\\_CLAUSES\\_VOID](#) was added in 8.0.3.

- Error number: 3640; Symbol: [ER\\_CLIENT\\_DOES\\_NOT\\_SUPPORT](#); SQLSTATE: HY000

Message: The client doesn't support %s

[ER\\_CLIENT\\_DOES\\_NOT\\_SUPPORT](#) was added in 8.0.3.

- Error number: 3641; Symbol: [ER\\_I\\_S\\_SKIPPED\\_TABLESPACE](#); SQLSTATE: HY000

Message: Tablespace '%s' was skipped since its definition is being modified by concurrent DDL statement

[ER\\_I\\_S\\_SKIPPED\\_TABLESPACE](#) was added in 8.0.3.

- Error number: 3642; Symbol: [ER\\_TABLESPACE\\_ENGINE\\_MISMATCH](#); SQLSTATE: HY000

Message: Engine '%s' does not match stored engine '%s' for tablespace '%s'

[ER\\_TABLESPACE\\_ENGINE\\_MISMATCH](#) was added in 8.0.3.

- Error number: 3643; Symbol: [ER\\_WRONG\\_SRID\\_FOR\\_COLUMN](#); SQLSTATE: HY000

Message: The SRID of the geometry does not match the SRID of the column '%s'. The SRID of the geometry is %lu, but the SRID of the column is %lu. Consider changing the SRID of the geometry or the SRID property of the column.

[ER\\_WRONG\\_SRID\\_FOR\\_COLUMN](#) was added in 8.0.3.

- Error number: 3644; Symbol: [ER\\_CANNOT\\_ALTER\\_SRID\\_DUE\\_TO\\_INDEX](#); SQLSTATE: HY000

Message: The SRID specification on the column '%s' cannot be changed because there is a spatial index on the column. Please remove the spatial index before altering the SRID specification.

[ER\\_CANNOT\\_ALTER\\_SRID\\_DUE\\_TO\\_INDEX](#) was added in 8.0.3.

- Error number: 3645; Symbol: [ER\\_WARN\\_BINLOG\\_PARTIAL\\_UPDATES\\_DISABLED](#); SQLSTATE: HY000

Message: When %s, the option binlog\_row\_value\_options=%s will be ignored and updates will be written in full format to binary log.

[ER\\_WARN\\_BINLOG\\_PARTIAL\\_UPDATES\\_DISABLED](#) was added in 8.0.3.

- Error number: 3646; Symbol: [ER\\_WARN\\_BINLOG\\_V1\\_ROW\\_EVENTS\\_DISABLED](#); SQLSTATE: HY000

Message: When %s, the option log\_bin\_use\_v1\_row\_events=1 will be ignored and row events will be written in new format to binary log.

[ER\\_WARN\\_BINLOG\\_V1\\_ROW\\_EVENTS\\_DISABLED](#) was added in 8.0.3.

- Error number: 3647; Symbol: [ER\\_WARN\\_BINLOG\\_PARTIAL\\_UPDATES\\_SUGGESTS\\_PARTIAL\\_IMAGES](#); SQLSTATE: HY000

Message: When %s, the option binlog\_row\_value\_options=%s will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to binlog\_row\_value\_options is limited to less than 50%%.

[ER\\_WARN\\_BINLOG\\_PARTIAL\\_UPDATES\\_SUGGESTS\\_PARTIAL\\_IMAGES](#) was added in 8.0.3.

- 
- Error number: 3648; Symbol: [ER\\_COULD\\_NOT\\_APPLY\\_JSON\\_DIFF](#); SQLSTATE: HY000  
Message: Could not apply JSON diff in table %.\*s, column %s.  
[ER\\_COULD\\_NOT\\_APPLY\\_JSON\\_DIFF](#) was added in 8.0.3.
  - Error number: 3649; Symbol: [ER\\_CORRUPTED\\_JSON\\_DIFF](#); SQLSTATE: HY000  
Message: Corrupted JSON diff for table %.\*s, column %s.  
[ER\\_CORRUPTED\\_JSON\\_DIFF](#) was added in 8.0.3.
  - Error number: 3650; Symbol: [ER\\_RESOURCE\\_GROUP\\_EXISTS](#); SQLSTATE: HY000  
Message: Resource Group '%s' exists  
[ER\\_RESOURCE\\_GROUP\\_EXISTS](#) was added in 8.0.3.
  - Error number: 3651; Symbol: [ER\\_RESOURCE\\_GROUP\\_NOT\\_EXISTS](#); SQLSTATE: HY000  
Message: Resource Group '%s' does not exist.  
[ER\\_RESOURCE\\_GROUP\\_NOT\\_EXISTS](#) was added in 8.0.3.
  - Error number: 3652; Symbol: [ER\\_INVALID\\_VCPU\\_ID](#); SQLSTATE: HY000  
Message: Invalid cpu id %u  
[ER\\_INVALID\\_VCPU\\_ID](#) was added in 8.0.3.
  - Error number: 3653; Symbol: [ER\\_INVALID\\_VCPU\\_RANGE](#); SQLSTATE: HY000  
Message: Invalid VCPU range %u-%u  
[ER\\_INVALID\\_VCPU\\_RANGE](#) was added in 8.0.3.
  - Error number: 3654; Symbol: [ER\\_INVALID\\_THREAD\\_PRIORITY](#); SQLSTATE: HY000  
Message: Invalid thread priority value %d for %s resource group %s. Allowed range is [%d, %d].  
[ER\\_INVALID\\_THREAD\\_PRIORITY](#) was added in 8.0.3.
  - Error number: 3655; Symbol: [ER\\_DISALLOWED\\_OPERATION](#); SQLSTATE: HY000  
Message: %s operation is disallowed on %s  
[ER\\_DISALLOWED\\_OPERATION](#) was added in 8.0.3.
  - Error number: 3656; Symbol: [ER\\_RESOURCE\\_GROUP\\_BUSY](#); SQLSTATE: HY000  
Message: Resource group %s is busy.  
[ER\\_RESOURCE\\_GROUP\\_BUSY](#) was added in 8.0.3.
  - Error number: 3657; Symbol: [ER\\_RESOURCE\\_GROUP\\_DISABLED](#); SQLSTATE: HY000  
Message: Resource group %s is disabled.  
[ER\\_RESOURCE\\_GROUP\\_DISABLED](#) was added in 8.0.3.

- 
- Error number: 3658; Symbol: `ER_FEATURE_UNSUPPORTED`; SQLSTATE: HY000  
Message: Feature %s is unsupported (%s).  
`ER_FEATURE_UNSUPPORTED` was added in 8.0.3.
  - Error number: 3659; Symbol: `ER_ATTRIBUTE_IGNORED`; SQLSTATE: HY000  
Message: Attribute %s is ignored (%s).  
`ER_ATTRIBUTE_IGNORED` was added in 8.0.3.
  - Error number: 3660; Symbol: `ER_INVALID_THREAD_ID`; SQLSTATE: HY000  
Message: Invalid thread id (%llu).  
`ER_INVALID_THREAD_ID` was added in 8.0.3.
  - Error number: 3661; Symbol: `ER_RESOURCE_GROUP_BIND_FAILED`; SQLSTATE: HY000  
Message: Unable to bind resource group %s with thread id (%llu).(%)s).  
`ER_RESOURCE_GROUP_BIND_FAILED` was added in 8.0.3.
  - Error number: 3662; Symbol: `ER_INVALID_USE_OF_FORCE_OPTION`; SQLSTATE: HY000  
Message: Option FORCE invalid as DISABLE option is not specified.  
`ER_INVALID_USE_OF_FORCE_OPTION` was added in 8.0.3.
  - Error number: 3663; Symbol: `ER_GROUP_REPLICATION_COMMAND_FAILURE`; SQLSTATE: HY000  
Message: The %s command encountered a failure. %s  
`ER_GROUP_REPLICATION_COMMAND_FAILURE` was added in 8.0.4.
  - Error number: 3664; Symbol: `ER_SDI_OPERATION_FAILED`; SQLSTATE: HY000  
Message: Failed to %s SDI '%s.%s' in tablespace '%s'.  
`ER_SDI_OPERATION_FAILED` was added in 8.0.3.
  - Error number: 3665; Symbol: `ER_MISSING_JSON_TABLE_VALUE`; SQLSTATE: 22035  
Message: Missing value for JSON\_TABLE column '%s'  
`ER_MISSING_JSON_TABLE_VALUE` was added in 8.0.4.
  - Error number: 3666; Symbol: `ER_WRONG_JSON_TABLE_VALUE`; SQLSTATE: 2203F  
Message: Can't store an array or an object in the scalar JSON\_TABLE column '%s'  
`ER_WRONG_JSON_TABLE_VALUE` was added in 8.0.4.
  - Error number: 3667; Symbol: `ER_TF_MUST_HAVE_ALIAS`; SQLSTATE: 42000  
Message: Every table function must have an alias  
`ER_TF_MUST_HAVE_ALIAS` was added in 8.0.4.

- 
- Error number: 3668; Symbol: [ER\\_TF\\_FORBIDDEN\\_JOIN\\_TYPE](#); SQLSTATE: HY000  
Message: INNER or LEFT JOIN must be used for LATERAL references made by '%s'  
[ER\\_TF\\_FORBIDDEN\\_JOIN\\_TYPE](#) was added in 8.0.4.
  - Error number: 3669; Symbol: [ER\\_JT\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: 22003  
Message: Value is out of range for JSON\_TABLE's column '%s'  
[ER\\_JT\\_VALUE\\_OUT\\_OF\\_RANGE](#) was added in 8.0.4.
  - Error number: 3670; Symbol: [ER\\_JT\\_MAX\\_NESTED\\_PATH](#); SQLSTATE: 42000  
Message: More than supported %u NESTED PATHs were found in JSON\_TABLE '%s'  
[ER\\_JT\\_MAX\\_NESTED\\_PATH](#) was added in 8.0.4.
  - Error number: 3671; Symbol: [ER\\_PASSWORD\\_EXPIRATION\\_NOT\\_SUPPORTED\\_BY\\_AUTH\\_METHOD](#); SQLSTATE: HY000  
Message: The selected authentication method %.\*s does not support password expiration  
[ER\\_PASSWORD\\_EXPIRATION\\_NOT\\_SUPPORTED\\_BY\\_AUTH\\_METHOD](#) was added in 8.0.4.
  - Error number: 3672; Symbol: [ER\\_INVALID\\_GEOJSON\\_CRS\\_NOT\\_TOP\\_LEVEL](#); SQLSTATE: HY000  
Message: Invalid GeoJSON data provided to function %s: Member 'crs' must be specified in the top level object.  
[ER\\_INVALID\\_GEOJSON\\_CRS\\_NOT\\_TOP\\_LEVEL](#) was added in 8.0.4.
  - Error number: 3673; Symbol: [ER\\_BAD\\_NULL\\_ERROR\\_NOT\\_IGNORED](#); SQLSTATE: 23000  
Message: Column '%s' cannot be null  
[ER\\_BAD\\_NULL\\_ERROR\\_NOT\\_IGNORED](#) was added in 8.0.4.
  - Error number: 3674; Symbol: [WARN\\_USELESS\\_SPATIAL\\_INDEX](#); SQLSTATE: HY000  
Message: The spatial index on column '%s' will not be used by the query optimizer since the column does not have an SRID attribute. Consider adding an SRID attribute to the column.  
[WARN\\_USELESS\\_SPATIAL\\_INDEX](#) was added in 8.0.4.
  - Error number: 3675; Symbol: [ER\\_DISK\\_FULL\\_NOWAIT](#); SQLSTATE: HY000  
Message: Create table/tablespace '%s' failed, as disk is full  
[ER\\_DISK\\_FULL\\_NOWAIT](#) was added in 8.0.4.
  - Error number: 3676; Symbol: [ER\\_PARSE\\_ERROR\\_IN\\_DIGEST\\_FN](#); SQLSTATE: HY000  
Message: Could not parse argument to digest function: "%s".  
[ER\\_PARSE\\_ERROR\\_IN\\_DIGEST\\_FN](#) was added in 8.0.4.
  - Error number: 3677; Symbol: [ER\\_UNDISCLOSED\\_PARSE\\_ERROR\\_IN\\_DIGEST\\_FN](#); SQLSTATE: HY000  
Message: Could not parse argument to digest function.

---

[ER\\_UNDISCLOSED\\_PARSE\\_ERROR\\_IN\\_DIGEST\\_FN](#) was added in 8.0.4.

- Error number: 3678; Symbol: [ER\\_SCHEMA\\_DIR\\_EXISTS](#); SQLSTATE: HY000

Message: Schema directory '%s' already exists. This must be resolved manually (e.g. by moving the schema directory to another location).

[ER\\_SCHEMA\\_DIR\\_EXISTS](#) was added in 8.0.4.

- Error number: 3679; Symbol: [ER\\_SCHEMA\\_DIR\\_MISSING](#); SQLSTATE: HY000

Message: Schema directory '%s' does not exist

[ER\\_SCHEMA\\_DIR\\_MISSING](#) was added in 8.0.4.

- Error number: 3680; Symbol: [ER\\_SCHEMA\\_DIR\\_CREATE\\_FAILED](#); SQLSTATE: HY000

Message: Failed to create schema directory '%s' (errno: %d - %s)

[ER\\_SCHEMA\\_DIR\\_CREATE\\_FAILED](#) was added in 8.0.4.

- Error number: 3681; Symbol: [ER\\_SCHEMA\\_DIR\\_UNKNOWN](#); SQLSTATE: HY000

Message: Schema '%s' does not exist, but schema directory '%s' was found. This must be resolved manually (e.g. by moving the schema directory to another location).

[ER\\_SCHEMA\\_DIR\\_UNKNOWN](#) was added in 8.0.4.

- Error number: 3682; Symbol: [ER\\_ONLY\\_IMPLEMENTED\\_FOR\\_SRID\\_0\\_AND\\_4326](#); SQLSTATE: 22S00

Message: Function %s is only defined for SRID 0 and SRID 4326.

[ER\\_ONLY\\_IMPLEMENTED\\_FOR\\_SRID\\_0\\_AND\\_4326](#) was added in 8.0.4.

- Error number: 3683; Symbol: [ER\\_BINLOG\\_EXPIRE\\_LOG\\_DAYS\\_AND\\_SECS\\_USED\\_TOGETHER](#); SQLSTATE: HY000

Message: The option expire\_logs\_days and binlog\_expire\_logs\_seconds cannot be used together. Please use binlog\_expire\_logs\_seconds to set the expire time (expire\_logs\_days is deprecated)

[ER\\_BINLOG\\_EXPIRE\\_LOG\\_DAYS\\_AND\\_SECS\\_USED\\_TOGETHER](#) was added in 8.0.11.

- Error number: 3684; Symbol: [ER\\_REGEX\\_STRING\\_NOT\\_TERMINATED](#); SQLSTATE: HY000

Message: An output string could not be zero-terminated because the length exceeds the buffer capacity.

[ER\\_REGEX\\_STRING\\_NOT\\_TERMINATED](#) was added in 8.0.4, removed after 8.0.4.

- Error number: 3684; Symbol: [ER\\_REGEX\\_BUFFER\\_OVERFLOW](#); SQLSTATE: HY000

Message: The result string is larger than the result buffer.

[ER\\_REGEX\\_BUFFER\\_OVERFLOW](#) was added in 8.0.4.

- Error number: 3685; Symbol: [ER\\_REGEX\\_ILLEGAL\\_ARGUMENT](#); SQLSTATE: HY000

Message: Illegal argument to a regular expression.

[ER\\_REGEX\\_ILLEGAL\\_ARGUMENT](#) was added in 8.0.4.

- 
- Error number: 3686; Symbol: [ER\\_REGEX\\_INDEX\\_OUTOFBOUNDS\\_ERROR](#); SQLSTATE: HY000  
Message: Index out of bounds in regular expression search.  
[ER\\_REGEX\\_INDEX\\_OUTOFBOUNDS\\_ERROR](#) was added in 8.0.4.
  - Error number: 3687; Symbol: [ER\\_REGEX\\_INTERNAL\\_ERROR](#); SQLSTATE: HY000  
Message: Internal error in the regular expression library.  
[ER\\_REGEX\\_INTERNAL\\_ERROR](#) was added in 8.0.4.
  - Error number: 3688; Symbol: [ER\\_REGEX\\_RULE\\_SYNTAX](#); SQLSTATE: HY000  
Message: Syntax error in regular expression on line %u, character %u.  
[ER\\_REGEX\\_RULE\\_SYNTAX](#) was added in 8.0.4.
  - Error number: 3689; Symbol: [ER\\_REGEX\\_BAD\\_ESCAPE\\_SEQUENCE](#); SQLSTATE: HY000  
Message: Unrecognized escape sequence in regular expression.  
[ER\\_REGEX\\_BAD\\_ESCAPE\\_SEQUENCE](#) was added in 8.0.4.
  - Error number: 3690; Symbol: [ER\\_REGEX\\_UNIMPLEMENTED](#); SQLSTATE: HY000  
Message: The regular expression contains a feature that is not implemented in this library version.  
[ER\\_REGEX\\_UNIMPLEMENTED](#) was added in 8.0.4.
  - Error number: 3691; Symbol: [ER\\_REGEX\\_MISMATCHED\\_PAREN](#); SQLSTATE: HY000  
Message: Mismatched parenthesis in regular expression.  
[ER\\_REGEX\\_MISMATCHED\\_PAREN](#) was added in 8.0.4.
  - Error number: 3692; Symbol: [ER\\_REGEX\\_BAD\\_INTERVAL](#); SQLSTATE: HY000  
Message: Incorrect description of a {min,max} interval.  
[ER\\_REGEX\\_BAD\\_INTERVAL](#) was added in 8.0.4.
  - Error number: 3693; Symbol: [ER\\_REGEX\\_MAX\\_LT\\_MIN](#); SQLSTATE: HY000  
Message: The maximum is less than the minimum in a {min,max} interval.  
[ER\\_REGEX\\_MAX\\_LT\\_MIN](#) was added in 8.0.4.
  - Error number: 3694; Symbol: [ER\\_REGEX\\_INVALID\\_BACK\\_REF](#); SQLSTATE: HY000  
Message: Invalid back-reference in regular expression.  
[ER\\_REGEX\\_INVALID\\_BACK\\_REF](#) was added in 8.0.4.
  - Error number: 3695; Symbol: [ER\\_REGEX\\_LOOK\\_BEHIND\\_LIMIT](#); SQLSTATE: HY000  
Message: The look-behind assertion exceeds the limit in regular expression.  
[ER\\_REGEX\\_LOOK\\_BEHIND\\_LIMIT](#) was added in 8.0.4.



- 
- Error number: 3696; Symbol: [ER\\_REGEX\\_MISSING\\_CLOSE\\_BRACKET](#); SQLSTATE: HY000  
Message: The regular expression contains an unclosed bracket expression.  
[ER\\_REGEX\\_MISSING\\_CLOSE\\_BRACKET](#) was added in 8.0.4.
  - Error number: 3697; Symbol: [ER\\_REGEX\\_INVALID\\_RANGE](#); SQLSTATE: HY000  
Message: The regular expression contains an [x-y] character range where x comes after y.  
[ER\\_REGEX\\_INVALID\\_RANGE](#) was added in 8.0.4.
  - Error number: 3698; Symbol: [ER\\_REGEX\\_STACK\\_OVERFLOW](#); SQLSTATE: HY000  
Message: Overflow in the regular expression backtrack stack.  
[ER\\_REGEX\\_STACK\\_OVERFLOW](#) was added in 8.0.4.
  - Error number: 3699; Symbol: [ER\\_REGEX\\_TIME\\_OUT](#); SQLSTATE: HY000  
Message: Timeout exceeded in regular expression match.  
[ER\\_REGEX\\_TIME\\_OUT](#) was added in 8.0.4.
  - Error number: 3700; Symbol: [ER\\_REGEX\\_PATTERN\\_TOO\\_BIG](#); SQLSTATE: HY000  
Message: The regular expression pattern exceeds limits on size or complexity.  
[ER\\_REGEX\\_PATTERN\\_TOO\\_BIG](#) was added in 8.0.4.
  - Error number: 3701; Symbol: [ER\\_CANT\\_SET\\_ERROR\\_LOG\\_SERVICE](#); SQLSTATE: HY000  
Message: Value for %s got confusing at or around "%s". Syntax may be wrong, component may not be INSTALLED, or a component that does not support instances may be listed more than once.  
[ER\\_CANT\\_SET\\_ERROR\\_LOG\\_SERVICE](#) was added in 8.0.4.
  - Error number: 3702; Symbol: [ER\\_EMPTY\\_PIPELINE\\_FOR\\_ERROR\\_LOG\\_SERVICE](#); SQLSTATE: HY000  
Message: Setting an empty %s pipeline disables error logging!  
[ER\\_EMPTY\\_PIPELINE\\_FOR\\_ERROR\\_LOG\\_SERVICE](#) was added in 8.0.4.
  - Error number: 3703; Symbol: [ER\\_COMPONENT\\_FILTER\\_DIAGNOSTICS](#); SQLSTATE: HY000  
Message: filter %s: %s  
[ER\\_COMPONENT\\_FILTER\\_DIAGNOSTICS](#) was added in 8.0.4.
  - Error number: 3704; Symbol: [ER\\_INNODB\\_CANNOT\\_BE\\_IGNORED](#); SQLSTATE: HY000  
Message: ignore-builtin-innodb is ignored and will be removed in future releases.  
[ER\\_INNODB\\_CANNOT\\_BE\\_IGNORED](#) was added in 8.0.2, removed after 8.0.2.
  - Error number: 3704; Symbol: [ER\\_NOT\\_IMPLEMENTED\\_FOR\\_CARTESIAN\\_SRS](#); SQLSTATE: 22S00  
Message: %s(%s) has not been implemented for Cartesian spatial reference systems.  
[ER\\_NOT\\_IMPLEMENTED\\_FOR\\_CARTESIAN\\_SRS](#) was added in 8.0.4.

- 
- Error number: 3705; Symbol: `ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS`; SQLSTATE: 22S00  
Message: %s(%s) has not been implemented for projected spatial reference systems.  
`ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS` was added in 8.0.4.
  - Error number: 3706; Symbol: `ER_NONPOSITIVE_RADIUS`; SQLSTATE: 22003  
Message: Invalid radius provided to function %s: Radius must be greater than zero.  
`ER_NONPOSITIVE_RADIUS` was added in 8.0.4.
  - Error number: 3707; Symbol: `ER_RESTART_SERVER_FAILED`; SQLSTATE: HY000  
Message: Restart server failed (%s).  
`ER_RESTART_SERVER_FAILED` was added in 8.0.4.
  - Error number: 3708; Symbol: `ER_SRS_MISSING_MANDATORY_ATTRIBUTE`; SQLSTATE: SR006  
Message: Missing mandatory attribute %s.  
`ER_SRS_MISSING_MANDATORY_ATTRIBUTE` was added in 8.0.4.
  - Error number: 3709; Symbol: `ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS`; SQLSTATE: SR006  
Message: Multiple definitions of attribute %s.  
`ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS` was added in 8.0.4.
  - Error number: 3710; Symbol: `ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE`; SQLSTATE: SR006  
Message: The spatial reference system name can't be an empty string or start or end with whitespace.  
`ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE` was added in 8.0.4.
  - Error number: 3711; Symbol: `ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE`; SQLSTATE: SR006  
Message: The organization name can't be an empty string or start or end with whitespace.  
`ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE` was added in 8.0.4.
  - Error number: 3712; Symbol: `ER_SRS_ID_ALREADY_EXISTS`; SQLSTATE: SR004  
Message: There is already a spatial reference system with SRID %u.  
`ER_SRS_ID_ALREADY_EXISTS` was added in 8.0.4.
  - Error number: 3713; Symbol: `ER_WARN_SRS_ID_ALREADY_EXISTS`; SQLSTATE: 01S00  
Message: There is already a spatial reference system with SRID %u.  
`ER_WARN_SRS_ID_ALREADY_EXISTS` was added in 8.0.4.
  - Error number: 3714; Symbol: `ER_CANT_MODIFY_SRID_0`; SQLSTATE: SR000  
Message: SRID 0 is not modifiable.  
`ER_CANT_MODIFY_SRID_0` was added in 8.0.4.

- 
- Error number: 3715; Symbol: [ER\\_WARN\\_RESERVED\\_SRID\\_RANGE](#); SQLSTATE: 01S01  
Message: The SRID range [%u, %u] has been reserved for system use. SRSs in this range may be added, modified or removed without warning during upgrade.  
[ER\\_WARN\\_RESERVED\\_SRID\\_RANGE](#) was added in 8.0.4.
  - Error number: 3716; Symbol: [ER\\_CANT\\_MODIFY\\_SRS\\_USED\\_BY\\_COLUMN](#); SQLSTATE: SR005  
Message: Can't modify SRID %u. There is at least one column depending on it.  
[ER\\_CANT\\_MODIFY\\_SRS\\_USED\\_BY\\_COLUMN](#) was added in 8.0.4.
  - Error number: 3717; Symbol: [ER\\_SRS\\_INVALID\\_CHARACTER\\_IN\\_ATTRIBUTE](#); SQLSTATE: SR006  
Message: Invalid character in attribute %s.  
[ER\\_SRS\\_INVALID\\_CHARACTER\\_IN\\_ATTRIBUTE](#) was added in 8.0.4.
  - Error number: 3718; Symbol: [ER\\_SRS\\_ATTRIBUTE\\_STRING\\_TOO\\_LONG](#); SQLSTATE: SR006  
Message: Attribute %s is too long. The maximum length is %u characters.  
[ER\\_SRS\\_ATTRIBUTE\\_STRING\\_TOO\\_LONG](#) was added in 8.0.4.
  - Error number: 3719; Symbol: [ER\\_DEPRECATED\\_UTF8\\_ALIAS](#); SQLSTATE: HY000  
Message: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.  
[ER\\_DEPRECATED\\_UTF8\\_ALIAS](#) was added in 8.0.11.
  - Error number: 3720; Symbol: [ER\\_DEPRECATED\\_NATIONAL](#); SQLSTATE: HY000  
Message: NATIONAL/NCHAR/NVARCHAR implies the character set UTF8MB3, which will be replaced by UTF8MB4 in a future release. Please consider using CHAR(x) CHARACTER SET UTF8MB4 in order to be unambiguous.  
[ER\\_DEPRECATED\\_NATIONAL](#) was added in 8.0.11.
  - Error number: 3721; Symbol: [ER\\_INVALID\\_DEFAULT\\_UTF8MB4\\_COLLATION](#); SQLSTATE: HY000  
Message: Invalid default collation %s: utf8mb4\_0900\_ai\_ci or utf8mb4\_general\_ci expected  
[ER\\_INVALID\\_DEFAULT\\_UTF8MB4\\_COLLATION](#) was added in 8.0.11.
  - Error number: 3722; Symbol: [ER\\_UNABLE\\_TO\\_COLLECT\\_LOG\\_STATUS](#); SQLSTATE: HY000  
Message: Unable to collect information for column '%s': %s.  
[ER\\_UNABLE\\_TO\\_COLLECT\\_LOG\\_STATUS](#) was added in 8.0.11.
  - Error number: 3723; Symbol: [ER\\_RESERVED\\_TABLESPACE\\_NAME](#); SQLSTATE: HY000  
Message: The table '%s' may not be created in the reserved tablespace '%s'.  
[ER\\_RESERVED\\_TABLESPACE\\_NAME](#) was added in 8.0.11.
  - Error number: 3724; Symbol: [ER\\_UNABLE\\_TO\\_SET\\_OPTION](#); SQLSTATE: HY000

---

Message: This option cannot be set %s.

[ER\\_UNABLE\\_TO\\_SET\\_OPTION](#) was added in 8.0.11.

- Error number: 3725; Symbol: [ER\\_SLAVE\\_POSSIBLY\\_DIVERGED\\_AFTER\\_DDL](#); SQLSTATE: HY000

Message: A commit for an atomic DDL statement was unsuccessful on the master and the slave. The slave supports atomic DDL statements but the master does not, so the action taken by the slave and master might differ. Check that their states have not diverged before proceeding.

[ER\\_SLAVE\\_POSSIBLY\\_DIVERGED\\_AFTER\\_DDL](#) was added in 8.0.11, removed after 8.0.32.

- Error number: 3725; Symbol: [ER\\_REPLICA\\_POSSIBLY\\_DIVERGED\\_AFTER\\_DDL](#); SQLSTATE: HY000

Message: A commit for an atomic DDL statement was unsuccessful on the source and the replica. The replica supports atomic DDL statements but the source does not, so the action taken by the replica and source might differ. Check that their states have not diverged before proceeding.

[ER\\_REPLICA\\_POSSIBLY\\_DIVERGED\\_AFTER\\_DDL](#) was added in 8.0.33.

- Error number: 3726; Symbol: [ER\\_SRS\\_NOT\\_GEOGRAPHIC](#); SQLSTATE: 22S00

Message: Function %s is only defined for geographic spatial reference systems, but one of its arguments is in SRID %u, which is not geographic.

[ER\\_SRS\\_NOT\\_GEOGRAPHIC](#) was added in 8.0.12.

- Error number: 3727; Symbol: [ER\\_POLYGON\\_TOO\\_LARGE](#); SQLSTATE: 22023

Message: Function %s encountered a polygon that was too large. Polygons must cover less than half the planet.

[ER\\_POLYGON\\_TOO\\_LARGE](#) was added in 8.0.12.

- Error number: 3728; Symbol: [ER\\_SPATIAL\\_UNIQUE\\_INDEX](#); SQLSTATE: HY000

Message: Spatial indexes can't be primary or unique indexes.

[ER\\_SPATIAL\\_UNIQUE\\_INDEX](#) was added in 8.0.12.

- Error number: 3729; Symbol: [ER\\_INDEX\\_TYPE\\_NOT\\_SUPPORTEDED\\_FOR\\_SPATIAL\\_INDEX](#); SQLSTATE: HY000

Message: The index type %s is not supported for spatial indexes.

[ER\\_INDEX\\_TYPE\\_NOT\\_SUPPORTEDED\\_FOR\\_SPATIAL\\_INDEX](#) was added in 8.0.12.

- Error number: 3730; Symbol: [ER\\_FK\\_CANNOT\\_DROP\\_PARENT](#); SQLSTATE: HY000

Message: Cannot drop table '%s' referenced by a foreign key constraint '%s' on table '%s'.

[ER\\_FK\\_CANNOT\\_DROP\\_PARENT](#) was added in 8.0.12.

- Error number: 3731; Symbol: [ER\\_GEOMETRY\\_PARAM\\_LONGITUDE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: 22S02

Message: A parameter of function %s contains a geometry with longitude %f, which is out of range. It must be within (%f, %f].

---

`ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE` was added in 8.0.12.

- Error number: 3732; Symbol: `ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE`; SQLSTATE: 22S03  
Message: A parameter of function %s contains a geometry with latitude %f, which is out of range. It must be within [%f, %f].

`ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE` was added in 8.0.12.

- Error number: 3733; Symbol: `ER_FK_CANNOT_USE_VIRTUAL_COLUMN`; SQLSTATE: HY000  
Message: Foreign key '%s' uses virtual column '%s' which is not supported.

`ER_FK_CANNOT_USE_VIRTUAL_COLUMN` was added in 8.0.12.

- Error number: 3734; Symbol: `ER_FK_NO_COLUMN_PARENT`; SQLSTATE: HY000  
Message: Failed to add the foreign key constraint. Missing column '%s' for constraint '%s' in the referenced table '%s'

`ER_FK_NO_COLUMN_PARENT` was added in 8.0.12.

- Error number: 3735; Symbol: `ER_CANT_SET_ERROR_SUPPRESSION_LIST`; SQLSTATE: HY000  
Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.

`ER_CANT_SET_ERROR_SUPPRESSION_LIST` was added in 8.0.13.

- Error number: 3736; Symbol: `ER_SRS_GEOGCS_INVALID_AXES`; SQLSTATE: SR002  
Message: The spatial reference system definition for SRID %u specifies invalid geographic axes '%s' and '%s'. One axis must be NORTH or SOUTH and the other must be EAST or WEST.

`ER_SRS_GEOGCS_INVALID_AXES` was added in 8.0.13.

- Error number: 3737; Symbol: `ER_SRS_INVALID_SEMI_MAJOR_AXIS`; SQLSTATE: SR002  
Message: The length of the semi-major axis must be a positive number.

`ER_SRS_INVALID_SEMI_MAJOR_AXIS` was added in 8.0.13.

- Error number: 3738; Symbol: `ER_SRS_INVALID_INVERSE_FLATTENING`; SQLSTATE: SR002  
Message: The inverse flattening must be larger than 1.0, or 0.0 if the ellipsoid is a sphere.

`ER_SRS_INVALID_INVERSE_FLATTENING` was added in 8.0.13.

- Error number: 3739; Symbol: `ER_SRS_INVALID_ANGULAR_UNIT`; SQLSTATE: SR002  
Message: The angular unit conversion factor must be a positive number.

`ER_SRS_INVALID_ANGULAR_UNIT` was added in 8.0.13.

- Error number: 3740; Symbol: `ER_SRS_INVALID_PRIME_MERIDIAN`; SQLSTATE: SR002  
Message: The prime meridian must be within (-180, 180] degrees, specified in the SRS angular unit.

`ER_SRS_INVALID_PRIME_MERIDIAN` was added in 8.0.13.

- 
- Error number: 3741; Symbol: `ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED`; SQLSTATE: 22S00  
Message: Transformation from SRID %u is not supported.  
`ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED` was added in 8.0.13.
  - Error number: 3742; Symbol: `ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED`; SQLSTATE: 22S00  
Message: Transformation to SRID %u is not supported.  
`ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED` was added in 8.0.13.
  - Error number: 3743; Symbol: `ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84`; SQLSTATE: 22S00  
Message: Transformation from SRID %u is not supported. The spatial reference system has no TOWGS84 clause.  
`ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84` was added in 8.0.13.
  - Error number: 3744; Symbol: `ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84`; SQLSTATE: 22S00  
Message: Transformation to SRID %u is not supported. The spatial reference system has no TOWGS84 clause.  
`ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84` was added in 8.0.13.
  - Error number: 3745; Symbol: `ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT`; SQLSTATE: HY000  
Message: Changing @@session.binlog\_format is disallowed when the session has open temporary table(s). You could wait until these temporary table(s) are dropped and try again.  
`ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT` was added in 8.0.13.
  - Error number: 3746; Symbol: `ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT`; SQLSTATE: HY000  
Message: Changing @@global.binlog\_format or @@persist.binlog\_format is disallowed when any replication channel has open temporary table(s). You could wait until Replica\_open\_temp\_tables = 0 and try again  
`ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT` was added in 8.0.13.
  - Error number: 3747; Symbol: `ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT`; SQLSTATE: HY000  
Message: Changing @@global.binlog\_format or @@persist.binlog\_format is disallowed when any replication channel applier thread is running. You could execute STOP REPLICAS SQL\_THREAD and try again.  
`ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT` was added in 8.0.13.
  - Error number: 3748; Symbol: `ER_CLIENT_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR`; SQLSTATE: HY000  
Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog\_format=STATEMENT.

---

[ER\\_CLIENT\\_GTID\\_UNSAFE\\_CREATE\\_DROP\\_TEMP\\_TABLE\\_IN\\_TRX\\_IN\\_SBR](#) was added in 8.0.13.

- Error number: 3750; Symbol: [ER\\_TABLE\\_WITHOUT\\_PK](#); SQLSTATE: HY000

Message: Unable to create or change a table without a primary key, when the system variable 'sql\_require\_primary\_key' is set. Add a primary key to the table or unset this variable to avoid this message. Note that tables without a primary key can cause performance problems in row-based replication, so please consult your DBA before changing this setting.

[ER\\_TABLE\\_WITHOUT\\_PK](#) was added in 8.0.13.

- Error number: 3751; Symbol: [WARN\\_DATA\\_TRUNCATED\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: 01000

Message: Data truncated for functional index '%s' at row %ld

[WARN\\_DATA\\_TRUNCATED\\_FUNCTIONAL\\_INDEX](#) was added in 8.0.13, removed after 8.0.16.

- Error number: 3751; Symbol: [ER\\_WARN\\_DATA\\_TRUNCATED\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: 01000

Message: Data truncated for functional index '%s' at row %ld

[ER\\_WARN\\_DATA\\_TRUNCATED\\_FUNCTIONAL\\_INDEX](#) was added in 8.0.17.

- Error number: 3752; Symbol: [ER\\_WARN\\_DATA\\_OUT\\_OF\\_RANGE\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: 22003

Message: Value is out of range for functional index '%s' at row %ld

[ER\\_WARN\\_DATA\\_OUT\\_OF\\_RANGE\\_FUNCTIONAL\\_INDEX](#) was added in 8.0.13.

- Error number: 3753; Symbol: [ER\\_FUNCTIONAL\\_INDEX\\_ON\\_JSON\\_OR\\_GEOMETRY\\_FUNCTION](#); SQLSTATE: 42000

Message: Cannot create a functional index on a function that returns a JSON or GEOMETRY value.

[ER\\_FUNCTIONAL\\_INDEX\\_ON\\_JSON\\_OR\\_GEOMETRY\\_FUNCTION](#) was added in 8.0.13.

- Error number: 3754; Symbol: [ER\\_FUNCTIONAL\\_INDEX\\_REF\\_AUTO\\_INCREMENT](#); SQLSTATE: HY000

Message: Functional index '%s' cannot refer to an auto-increment column.

[ER\\_FUNCTIONAL\\_INDEX\\_REF\\_AUTO\\_INCREMENT](#) was added in 8.0.13.

- Error number: 3755; Symbol: [ER\\_CANNOT\\_DROP\\_COLUMN\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: HY000

Message: Cannot drop column '%s' because it is used by a functional index. In order to drop the column, you must remove the functional index.

[ER\\_CANNOT\\_DROP\\_COLUMN\\_FUNCTIONAL\\_INDEX](#) was added in 8.0.13.

- Error number: 3756; Symbol: [ER\\_FUNCTIONAL\\_INDEX\\_PRIMARY\\_KEY](#); SQLSTATE: HY000

Message: The primary key cannot be a functional index

[ER\\_FUNCTIONAL\\_INDEX\\_PRIMARY\\_KEY](#) was added in 8.0.13.

- 
- Error number: 3757; Symbol: [ER\\_FUNCTIONAL\\_INDEX\\_ON\\_LOB](#); SQLSTATE: HY000  
Message: Cannot create a functional index on an expression that returns a BLOB or TEXT. Please consider using CAST.  
[ER\\_FUNCTIONAL\\_INDEX\\_ON\\_LOB](#) was added in 8.0.13.
  - Error number: 3758; Symbol: [ER\\_FUNCTIONAL\\_INDEX\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: HY000  
Message: Expression of functional index '%s' contains a disallowed function.  
[ER\\_FUNCTIONAL\\_INDEX\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#) was added in 8.0.13.
  - Error number: 3759; Symbol: [ER\\_FULLTEXT\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: HY000  
Message: Fulltext functional index is not supported.  
[ER\\_FULLTEXT\\_FUNCTIONAL\\_INDEX](#) was added in 8.0.13.
  - Error number: 3760; Symbol: [ER\\_SPATIAL\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: HY000  
Message: Spatial functional index is not supported.  
[ER\\_SPATIAL\\_FUNCTIONAL\\_INDEX](#) was added in 8.0.13.
  - Error number: 3761; Symbol: [ER\\_WRONG\\_KEY\\_COLUMN\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: HY000  
Message: The used storage engine cannot index the expression '%s'.  
[ER\\_WRONG\\_KEY\\_COLUMN\\_FUNCTIONAL\\_INDEX](#) was added in 8.0.13.
  - Error number: 3762; Symbol: [ER\\_FUNCTIONAL\\_INDEX\\_ON\\_FIELD](#); SQLSTATE: HY000  
Message: Functional index on a column is not supported. Consider using a regular index instead.  
[ER\\_FUNCTIONAL\\_INDEX\\_ON\\_FIELD](#) was added in 8.0.13.
  - Error number: 3763; Symbol: [ER\\_GENERATED\\_COLUMN\\_NAMED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: HY000  
Message: Expression of generated column '%s' contains a disallowed function: %s.  
[ER\\_GENERATED\\_COLUMN\\_NAMED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#) was added in 8.0.13.
  - Error number: 3764; Symbol: [ER\\_GENERATED\\_COLUMN\\_ROW\\_VALUE](#); SQLSTATE: HY000  
Message: Expression of generated column '%s' cannot refer to a row value.  
[ER\\_GENERATED\\_COLUMN\\_ROW\\_VALUE](#) was added in 8.0.13.
  - Error number: 3765; Symbol: [ER\\_GENERATED\\_COLUMN\\_VARIABLES](#); SQLSTATE: HY000  
Message: Expression of generated column '%s' cannot refer user or system variables.  
[ER\\_GENERATED\\_COLUMN\\_VARIABLES](#) was added in 8.0.13.



- 
- Error number: 3766; Symbol: [ER\\_DEPENDENT\\_BY\\_DEFAULT\\_GENERATED\\_VALUE](#); SQLSTATE: HY000

Message: Column '%s' of table '%s' has a default value expression dependency and cannot be dropped or renamed.

[ER\\_DEPENDENT\\_BY\\_DEFAULT\\_GENERATED\\_VALUE](#) was added in 8.0.13.

- Error number: 3767; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_NON\\_PRIOR](#); SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer to a column defined after it if that column is a generated column or has an expression as default value.

[ER\\_DEFAULT\\_VAL\\_GENERATED\\_NON\\_PRIOR](#) was added in 8.0.13.

- Error number: 3768; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_REF\\_AUTO\\_INC](#); SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer to an auto-increment column.

[ER\\_DEFAULT\\_VAL\\_GENERATED\\_REF\\_AUTO\\_INC](#) was added in 8.0.13.

- Error number: 3769; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: HY000

Message: Default value expression of column '%s' contains a disallowed function.

[ER\\_DEFAULT\\_VAL\\_GENERATED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#) was added in 8.0.13.

- Error number: 3770; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_NAMED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: HY000

Message: Default value expression of column '%s' contains a disallowed function: %s.

[ER\\_DEFAULT\\_VAL\\_GENERATED\\_NAMED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#) was added in 8.0.13.

- Error number: 3771; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_ROW\\_VALUE](#); SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer to a row value.

[ER\\_DEFAULT\\_VAL\\_GENERATED\\_ROW\\_VALUE](#) was added in 8.0.13.

- Error number: 3772; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_VARIABLES](#); SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer user or system variables.

[ER\\_DEFAULT\\_VAL\\_GENERATED\\_VARIABLES](#) was added in 8.0.13.

- Error number: 3773; Symbol: [ER\\_DEFAULT\\_AS\\_VAL\\_GENERATED](#); SQLSTATE: HY000

Message: DEFAULT function cannot be used with default value expressions

[ER\\_DEFAULT\\_AS\\_VAL\\_GENERATED](#) was added in 8.0.13.

- Error number: 3774; Symbol: [ER\\_UNSUPPORTED\\_ACTION\\_ON\\_DEFAULT\\_VAL\\_GENERATED](#); SQLSTATE: HY000

Message: '%s' is not supported for default value expressions.

[ER\\_UNSUPPORTED\\_ACTION\\_ON\\_DEFAULT\\_VAL\\_GENERATED](#) was added in 8.0.13.

- 
- Error number: 3775; Symbol: [ER\\_GTID\\_UNSAFE\\_ALTER\\_ADD\\_COL\\_WITH\\_DEFAULT\\_EXPRESSION](#); SQLSTATE: [HY000](#)  
  
Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with expression as DEFAULT.  
  
[ER\\_GTID\\_UNSAFE\\_ALTER\\_ADD\\_COL\\_WITH\\_DEFAULT\\_EXPRESSION](#) was added in 8.0.13.
  - Error number: 3776; Symbol: [ER\\_FK\\_CANNOT\\_CHANGE\\_ENGINE](#); SQLSTATE: [HY000](#)  
  
Message: Cannot change table's storage engine because the table participates in a foreign key constraint.  
  
[ER\\_FK\\_CANNOT\\_CHANGE\\_ENGINE](#) was added in 8.0.13.
  - Error number: 3777; Symbol: [ER\\_WARN\\_DEPRECATED\\_USER\\_SET\\_EXPR](#); SQLSTATE: [HY000](#)  
  
Message: Setting user variables within expressions is deprecated and will be removed in a future release. Consider alternatives: 'SET variable=expression, ...', or 'SELECT expression(s) INTO variables(s)'.  
  
[ER\\_WARN\\_DEPRECATED\\_USER\\_SET\\_EXPR](#) was added in 8.0.13.
  - Error number: 3778; Symbol: [ER\\_WARN\\_DEPRECATED\\_UTF8MB3\\_COLLATION](#); SQLSTATE: [HY000](#)  
  
Message: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.  
  
[ER\\_WARN\\_DEPRECATED\\_UTF8MB3\\_COLLATION](#) was added in 8.0.13.
  - Error number: 3779; Symbol: [ER\\_WARN\\_DEPRECATED\\_NESTED\\_COMMENT\\_SYNTAX](#); SQLSTATE: [HY000](#)  
  
Message: Nested comment syntax is deprecated and will be removed in a future release.  
  
[ER\\_WARN\\_DEPRECATED\\_NESTED\\_COMMENT\\_SYNTAX](#) was added in 8.0.13.
  - Error number: 3780; Symbol: [ER\\_FK\\_INCOMPATIBLE\\_COLUMNS](#); SQLSTATE: [HY000](#)  
  
Message: Referencing column '%s' and referenced column '%s' in foreign key constraint '%s' are incompatible.  
  
[ER\\_FK\\_INCOMPATIBLE\\_COLUMNS](#) was added in 8.0.14.
  - Error number: 3781; Symbol: [ER\\_GR\\_HOLD\\_WAIT\\_TIMEOUT](#); SQLSTATE: [HY000](#)  
  
Message: Timeout exceeded for held statement while new Group Replication primary member is applying backlog.  
  
[ER\\_GR\\_HOLD\\_WAIT\\_TIMEOUT](#) was added in 8.0.14.
  - Error number: 3782; Symbol: [ER\\_GR\\_HOLD\\_KILLED](#); SQLSTATE: [HY000](#)  
  
Message: Held statement aborted because Group Replication plugin got shut down or thread was killed while new primary member was applying backlog.  
  
[ER\\_GR\\_HOLD\\_KILLED](#) was added in 8.0.14.
  - Error number: 3783; Symbol: [ER\\_GR\\_HOLD\\_MEMBER\\_STATUS\\_ERROR](#); SQLSTATE: [HY000](#)

---

Message: Held statement was aborted due to member being in error state, while backlog is being applied during Group Replication primary election.

[ER\\_GR\\_HOLD\\_MEMBER\\_STATUS\\_ERROR](#) was added in 8.0.14.

- Error number: 3784; Symbol: [ER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_FETCH\\_KEY](#); SQLSTATE: HY000

Message: Failed to fetch key from keyring, please check if keyring is loaded.

[ER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_FETCH\\_KEY](#) was added in 8.0.14.

- Error number: 3785; Symbol: [ER\\_RPL\\_ENCRYPTION\\_KEY\\_NOT\\_FOUND](#); SQLSTATE: HY000

Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

[ER\\_RPL\\_ENCRYPTION\\_KEY\\_NOT\\_FOUND](#) was added in 8.0.14.

- Error number: 3786; Symbol: [ER\\_RPL\\_ENCRYPTION\\_KEYRING\\_INVALID\\_KEY](#); SQLSTATE: HY000

Message: Fetched an invalid key from keyring.

[ER\\_RPL\\_ENCRYPTION\\_KEYRING\\_INVALID\\_KEY](#) was added in 8.0.14.

- Error number: 3787; Symbol: [ER\\_RPL\\_ENCRYPTION\\_HEADER\\_ERROR](#); SQLSTATE: HY000

Message: Error reading a replication log encryption header: %s.

[ER\\_RPL\\_ENCRYPTION\\_HEADER\\_ERROR](#) was added in 8.0.14.

- Error number: 3788; Symbol: [ER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_ROTATE\\_LOGS](#); SQLSTATE: HY000

Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.

[ER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_ROTATE\\_LOGS](#) was added in 8.0.14.

- Error number: 3789; Symbol: [ER\\_RPL\\_ENCRYPTION\\_KEY\\_EXISTS\\_UNEXPECTED](#); SQLSTATE: HY000

Message: Key %s exists unexpected.

[ER\\_RPL\\_ENCRYPTION\\_KEY\\_EXISTS\\_UNEXPECTED](#) was added in 8.0.14.

- Error number: 3790; Symbol: [ER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_GENERATE\\_KEY](#); SQLSTATE: HY000

Message: Failed to generate key, please check if keyring is loaded.

[ER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_GENERATE\\_KEY](#) was added in 8.0.14.

- Error number: 3791; Symbol: [ER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_STORE\\_KEY](#); SQLSTATE: HY000

Message: Failed to store key, please check if keyring is loaded.

[ER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_STORE\\_KEY](#) was added in 8.0.14.

- Error number: 3792; Symbol: [ER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_REMOVE\\_KEY](#); SQLSTATE: HY000

Message: Failed to remove key, please check if keyring is loaded.

---

`ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY` was added in 8.0.14.

- Error number: 3793; Symbol: `ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION`; SQLSTATE: HY000

Message: Failed to change binlog\_encryption value. %s.

`ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION` was added in 8.0.14.

- Error number: 3794; Symbol: `ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED`; SQLSTATE: HY000

Message: Unable to recover binlog encryption master key, please check if keyring is loaded.

`ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED` was added in 8.0.14.

- Error number: 3795; Symbol: `ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE`; SQLSTATE: HY000

Message: slow query log file format changed as requested, but setting will have no effect when not actually logging to a file.

`ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE` was added in 8.0.14.

- Error number: 3796; Symbol: `ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED`; SQLSTATE: HY000

Message: The option group\_replication\_consistency cannot be used on the current member state.

`ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED` was added in 8.0.14.

- Error number: 3797; Symbol: `ER_GRP_TRX_CONSISTENCY_BEFORE`; SQLSTATE: HY000

Message: Error while waiting for group transactions commit on group\_replication\_consistency='BEFORE'.

`ER_GRP_TRX_CONSISTENCY_BEFORE` was added in 8.0.14.

- Error number: 3798; Symbol: `ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN`; SQLSTATE: HY000

Message: Error while waiting for transactions with group\_replication\_consistency='AFTER' to commit.

`ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN` was added in 8.0.14.

- Error number: 3799; Symbol: `ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED`; SQLSTATE: HY000

Message: The Group Replication plugin is stopping, therefore new transactions are not allowed to start.

`ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED` was added in 8.0.14.

- Error number: 3800; Symbol: `ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED`; SQLSTATE: HY000

Message: Expression of functional index '%s' cannot refer to a row value.

`ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED` was added in 8.0.14.

- 
- Error number: 3801; Symbol: [ER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_ENCRYPT](#); SQLSTATE: HY000  
Message: Failed to encrypt content to write into binlog file: %s.  
[ER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_ENCRYPT](#) was added in 8.0.14.
  - Error number: 3802; Symbol: [ER\\_PAGE\\_TRACKING\\_NOT\\_STARTED](#); SQLSTATE: HY000  
Message: Page Tracking is not started yet.  
[ER\\_PAGE\\_TRACKING\\_NOT\\_STARTED](#) was added in 8.0.16.
  - Error number: 3803; Symbol: [ER\\_PAGE\\_TRACKING\\_RANGE\\_NOT\\_TRACKED](#); SQLSTATE: HY000  
Message: Tracking was not enabled for the LSN range specified  
[ER\\_PAGE\\_TRACKING\\_RANGE\\_NOT\\_TRACKED](#) was added in 8.0.16.
  - Error number: 3804; Symbol: [ER\\_PAGE\\_TRACKING\\_CANNOT\\_PURGE](#); SQLSTATE: HY000  
Message: Cannot purge data when concurrent clone is in progress. Try later.  
[ER\\_PAGE\\_TRACKING\\_CANNOT\\_PURGE](#) was added in 8.0.16.
  - Error number: 3805; Symbol: [ER\\_RPL\\_ENCRYPTION\\_CANNOT\\_ROTATE\\_BINLOG\\_MASTER\\_KEY](#); SQLSTATE: HY000  
Message: Cannot rotate binary log master key when 'binlog-encryption' is off.  
[ER\\_RPL\\_ENCRYPTION\\_CANNOT\\_ROTATE\\_BINLOG\\_MASTER\\_KEY](#) was added in 8.0.16.
  - Error number: 3806; Symbol: [ER\\_BINLOG\\_MASTER\\_KEY\\_RECOVERY\\_OUT\\_OF\\_COMBINATION](#); SQLSTATE: HY000  
Message: Unable to recover binary log master key, the combination of new\_master\_key\_seqno=%u, master\_key\_seqno=%u and old\_master\_key\_seqno=%u are wrong.  
[ER\\_BINLOG\\_MASTER\\_KEY\\_RECOVERY\\_OUT\\_OF\\_COMBINATION](#) was added in 8.0.16.
  - Error number: 3807; Symbol: [ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_OPERATE\\_KEY](#); SQLSTATE: HY000  
Message: Failed to operate binary log master key on keyring, please check if keyring is loaded. The statement had no effect: the old binary log master key is still in use, the keyring, binary and relay log files are unchanged, and the server could not start using a new binary log master key for encrypting new binary and relay log files.  
[ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_OPERATE\\_KEY](#) was added in 8.0.16.
  - Error number: 3808; Symbol: [ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_ROTATE\\_LOGS](#); SQLSTATE: HY000  
Message: Failed to rotate one or more binary or relay log files. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.  
[ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_ROTATE\\_LOGS](#) was added in 8.0.16.
-

- 
- Error number: 3809; Symbol: [ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_REENCRYPT\\_LOG](#); SQLSTATE: HY000

Message: %s. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.

[ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_REENCRYPT\\_LOG](#) was added in 8.0.16.

- Error number: 3810; Symbol: [ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_CLEANUP\\_UNUSED\\_KEYS](#); SQLSTATE: HY000

Message: Failed to remove unused binary log encryption keys from the keyring, please check if keyring is loaded. The unused binary log encryption keys may still exist in the keyring, and they will be removed upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

[ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_CLEANUP\\_UNUSED\\_KEYS](#) was added in 8.0.16.

- Error number: 3811; Symbol: [ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_CLEANUP\\_AUX\\_KEY](#); SQLSTATE: HY000

Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

[ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_CLEANUP\\_AUX\\_KEY](#) was added in 8.0.16.

- Error number: 3812; Symbol: [ER\\_NON\\_BOOLEAN\\_EXPR\\_FOR\\_CHECK\\_CONSTRAINT](#); SQLSTATE: HY000

Message: An expression of non-boolean type specified to a check constraint '%s'.

[ER\\_NON\\_BOOLEAN\\_EXPR\\_FOR\\_CHECK\\_CONSTRAINT](#) was added in 8.0.16.

- Error number: 3813; Symbol: [ER\\_COLUMN\\_CHECK\\_CONSTRAINT\\_REFERENCES\\_OTHER\\_COLUMN](#); SQLSTATE: HY000

Message: Column check constraint '%s' references other column.

[ER\\_COLUMN\\_CHECK\\_CONSTRAINT\\_REFERENCES\\_OTHER\\_COLUMN](#) was added in 8.0.16.

- Error number: 3814; Symbol: [ER\\_CHECK\\_CONSTRAINT\\_NAMED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: HY000

Message: An expression of a check constraint '%s' contains disallowed function: %s.

[ER\\_CHECK\\_CONSTRAINT\\_NAMED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#) was added in 8.0.16.

- Error number: 3815; Symbol: [ER\\_CHECK\\_CONSTRAINT\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: HY000

Message: An expression of a check constraint '%s' contains disallowed function.

[ER\\_CHECK\\_CONSTRAINT\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#) was added in 8.0.16.

- Error number: 3816; Symbol: [ER\\_CHECK\\_CONSTRAINT\\_VARIABLES](#); SQLSTATE: HY000

Message: An expression of a check constraint '%s' cannot refer to a user or system variable.

---

`ER_CHECK_CONSTRAINT_VARIABLES` was added in 8.0.16.

- Error number: 3817; Symbol: `ER_CHECK_CONSTRAINT_ROW_VALUE`; SQLSTATE: HY000

Message: Check constraint '%s' cannot refer to a row value.

`ER_CHECK_CONSTRAINT_ROW_VALUE` was added in 8.0.16.

- Error number: 3818; Symbol: `ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT_COLUMN`; SQLSTATE: HY000

Message: Check constraint '%s' cannot refer to an auto-increment column.

`ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT_COLUMN` was added in 8.0.16.

- Error number: 3819; Symbol: `ER_CHECK_CONSTRAINT_VIOLATED`; SQLSTATE: HY000

Message: Check constraint '%s' is violated.

`ER_CHECK_CONSTRAINT_VIOLATED` was added in 8.0.16.

- Error number: 3820; Symbol: `ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN`; SQLSTATE: HY000

Message: Check constraint '%s' refers to non-existing column '%s'.

`ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN` was added in 8.0.16.

- Error number: 3821; Symbol: `ER_CHECK_CONSTRAINT_NOT_FOUND`; SQLSTATE: HY000

Message: Check constraint '%s' is not found in the table.

`ER_CHECK_CONSTRAINT_NOT_FOUND` was added in 8.0.16.

- Error number: 3822; Symbol: `ER_CHECK_CONSTRAINT_DUP_NAME`; SQLSTATE: HY000

Message: Duplicate check constraint name '%s'.

`ER_CHECK_CONSTRAINT_DUP_NAME` was added in 8.0.16.

- Error number: 3823; Symbol: `ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACTION_COLUMN`; SQLSTATE: HY000

Message: Column '%s' cannot be used in a check constraint '%s': needed in a foreign key constraint '%s' referential action.

`ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACTION_COLUMN` was added in 8.0.16.

- Error number: 3824; Symbol: `WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB`; SQLSTATE: HY000

Message: Creating an unencrypted table in a database with default encryption enabled.

`WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB` was added in 8.0.16.

- Error number: 3825; Symbol: `ER_INVALID_ENCRYPTION_REQUEST`; SQLSTATE: HY000

Message: Request to create %s table while using an %s tablespace.

`ER_INVALID_ENCRYPTION_REQUEST` was added in 8.0.16.

- 
- Error number: 3826; Symbol: `ER_CANNOT_SET_TABLE_ENCRYPTION`; SQLSTATE: `HY000`  
Message: Table encryption differ from its database default encryption, and user doesn't have enough privilege.  
`ER_CANNOT_SET_TABLE_ENCRYPTION` was added in 8.0.16.
  - Error number: 3827; Symbol: `ER_CANNOT_SET_DATABASE_ENCRYPTION`; SQLSTATE: `HY000`  
Message: Database default encryption differ from 'default\_table\_encryption' setting, and user doesn't have enough privilege.  
`ER_CANNOT_SET_DATABASE_ENCRYPTION` was added in 8.0.16.
  - Error number: 3828; Symbol: `ER_CANNOT_SET_TABLESPACE_ENCRYPTION`; SQLSTATE: `HY000`  
Message: Tablespace encryption differ from 'default\_table\_encryption' setting, and user doesn't have enough privilege.  
`ER_CANNOT_SET_TABLESPACE_ENCRYPTION` was added in 8.0.16.
  - Error number: 3829; Symbol: `ER_TABLESPACE_CANNOT_BE_ENCRYPTED`; SQLSTATE: `HY000`  
Message: This tablespace can't be encrypted, because one of table's schema has default encryption OFF and user doesn't have enough privilege.  
`ER_TABLESPACE_CANNOT_BE_ENCRYPTED` was added in 8.0.16.
  - Error number: 3830; Symbol: `ER_TABLESPACE_CANNOT_BE_DECRYPTED`; SQLSTATE: `HY000`  
Message: This tablespace can't be decrypted, because one of table's schema has default encryption ON and user doesn't have enough privilege.  
`ER_TABLESPACE_CANNOT_BE_DECRYPTED` was added in 8.0.16.
  - Error number: 3831; Symbol: `ER_TABLESPACE_TYPE_UNKNOWN`; SQLSTATE: `HY000`  
Message: Cannot determine the type of the tablespace named '%s'.  
`ER_TABLESPACE_TYPE_UNKNOWN` was added in 8.0.16.
  - Error number: 3832; Symbol: `ER_TARGET_TABLESPACE_UNENCRYPTED`; SQLSTATE: `HY000`  
Message: Source tablespace is encrypted but target tablespace is not.  
`ER_TARGET_TABLESPACE_UNENCRYPTED` was added in 8.0.16.
  - Error number: 3833; Symbol: `ER_CANNOT_USE_ENCRYPTION_CLAUSE`; SQLSTATE: `HY000`  
Message: ENCRYPTION clause is not valid for %s tablespace.  
`ER_CANNOT_USE_ENCRYPTION_CLAUSE` was added in 8.0.16.
  - Error number: 3834; Symbol: `ER_INVALID_MULTIPLE_CLAUSES`; SQLSTATE: `HY000`  
Message: Multiple %s clauses  
`ER_INVALID_MULTIPLE_CLAUSES` was added in 8.0.16.
  - Error number: 3835; Symbol: `ER_UNSUPPORTED_USE_OF_GRANT_AS`; SQLSTATE: `HY000`



---

Message: GRANT ... AS is currently supported only for global privileges.

[ER\\_UNSUPPORTED\\_USE\\_OF\\_GRANT\\_AS](#) was added in 8.0.16.

- Error number: 3836; Symbol: [ER\\_UNKNOWN\\_AUTH\\_ID\\_OR\\_ACCESS\\_DENIED\\_FOR\\_GRANT\\_AS](#); SQLSTATE: HY000

Message: Either some of the authorization IDs in the AS clause are invalid or the current user lacks privileges to execute the statement.

[ER\\_UNKNOWN\\_AUTH\\_ID\\_OR\\_ACCESS\\_DENIED\\_FOR\\_GRANT\\_AS](#) was added in 8.0.16.

- Error number: 3837; Symbol: [ER\\_DEPENDENT\\_BY\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: HY000

Message: Column '%s' has a functional index dependency and cannot be dropped or renamed.

[ER\\_DEPENDENT\\_BY\\_FUNCTIONAL\\_INDEX](#) was added in 8.0.17.

- Error number: 3838; Symbol: [ER\\_PLUGIN\\_NOT\\_EARLY](#); SQLSTATE: HY000

Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.

[ER\\_PLUGIN\\_NOT\\_EARLY](#) was added in 8.0.17.

- Error number: 3839; Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_START\\_SUBDIR\\_PATH](#); SQLSTATE: HY000

Message: Redo log archiving start prohibits path name in 'subdir' argument

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_START\\_SUBDIR\\_PATH](#) was added in 8.0.17.

- Error number: 3840; Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_START\\_TIMEOUT](#); SQLSTATE: HY000

Message: Redo log archiving start timed out

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_START\\_TIMEOUT](#) was added in 8.0.17.

- Error number: 3841; Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_DIRS\\_INVALID](#); SQLSTATE: HY000

Message: Server variable 'innodb\_redo\_log\_archive\_dirs' is NULL or empty

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_DIRS\\_INVALID](#) was added in 8.0.17.

- Error number: 3842; Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_LABEL\\_NOT\\_FOUND](#); SQLSTATE: HY000

Message: Label '%s' not found in server variable 'innodb\_redo\_log\_archive\_dirs'

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_LABEL\\_NOT\\_FOUND](#) was added in 8.0.17.

- Error number: 3843; Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_EMPTY](#); SQLSTATE: HY000

Message: Directory is empty after label '%s' in server variable 'innodb\_redo\_log\_archive\_dirs'

[ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_EMPTY](#) was added in 8.0.17.

- Error number: 3844; Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_NO\\_SUCH\\_DIR](#); SQLSTATE: HY000

---

Message: Redo log archive directory '%s' does not exist or is not a directory

[ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_NO\\_SUCH\\_DIR](#) was added in 8.0.17.

- Error number: 3845; Symbol: [ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_CLASH](#); SQLSTATE: HY000

Message: Redo log archive directory '%s' is in, under, or over server directory '%s' - '%s'

[ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_CLASH](#) was added in 8.0.17.

- Error number: 3846; Symbol: [ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_PERMISSIONS](#); SQLSTATE: HY000

Message: Redo log archive directory '%s' is accessible to all OS users

[ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_PERMISSIONS](#) was added in 8.0.17.

- Error number: 3847; Symbol: [ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_FILE\\_CREATE](#); SQLSTATE: HY000

Message: Cannot create redo log archive file '%s' (OS errno: %d - %s)

[ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_FILE\\_CREATE](#) was added in 8.0.17.

- Error number: 3848; Symbol: [ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_ACTIVE](#); SQLSTATE: HY000

Message: Redo log archiving has been started on '%s' - Call `innodb_redo_log_archive_stop()` first

[ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_ACTIVE](#) was added in 8.0.17.

- Error number: 3849; Symbol: [ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_INACTIVE](#); SQLSTATE: HY000

Message: Redo log archiving is not active

[ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_INACTIVE](#) was added in 8.0.17.

- Error number: 3850; Symbol: [ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_FAILED](#); SQLSTATE: HY000

Message: Redo log archiving failed: %s

[ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_FAILED](#) was added in 8.0.17.

- Error number: 3851; Symbol: [ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_SESSION](#); SQLSTATE: HY000

Message: Redo log archiving has not been started by this session

[ER\\_INNO\\_DB\\_REDO\\_LOG\\_ARCHIVE\\_SESSION](#) was added in 8.0.17.

- Error number: 3852; Symbol: [ER\\_STD\\_REGEX\\_ERROR](#); SQLSTATE: HY000

Message: Regex error: %s in function %s.

[ER\\_STD\\_REGEX\\_ERROR](#) was added in 8.0.17.

- Error number: 3853; Symbol: [ER\\_INVALID\\_JSON\\_TYPE](#); SQLSTATE: 22032

Message: Invalid JSON type in argument %u to function %s; an %s is required.

[ER\\_INVALID\\_JSON\\_TYPE](#) was added in 8.0.17.

- 
- Error number: 3854; Symbol: [ER\\_CANNOT\\_CONVERT\\_STRING](#); SQLSTATE: HY000  
Message: Cannot convert string '%s' from %s to %s  
[ER\\_CANNOT\\_CONVERT\\_STRING](#) was added in 8.0.17.
  - Error number: 3855; Symbol: [ER\\_DEPENDENT\\_BY\\_PARTITION\\_FUNC](#); SQLSTATE: HY000  
Message: Column '%s' has a partitioning function dependency and cannot be dropped or renamed.  
[ER\\_DEPENDENT\\_BY\\_PARTITION\\_FUNC](#) was added in 8.0.17.
  - Error number: 3856; Symbol: [ER\\_WARN\\_DEPRECATED\\_FLOAT\\_AUTO\\_INCREMENT](#); SQLSTATE: HY000  
Message: AUTO\_INCREMENT support for FLOAT/DOUBLE columns is deprecated and will be removed in a future release. Consider removing AUTO\_INCREMENT from column '%s'.  
[ER\\_WARN\\_DEPRECATED\\_FLOAT\\_AUTO\\_INCREMENT](#) was added in 8.0.17.
  - Error number: 3857; Symbol: [ER\\_RPL\\_CANT\\_STOP\\_SLAVE\\_WHILE\\_LOCKED\\_BACKUP](#); SQLSTATE: HY000  
Message: Cannot stop the slave SQL thread while the instance is locked for backup. Try running `UNLOCK INSTANCE` first.  
[ER\\_RPL\\_CANT\\_STOP\\_SLAVE\\_WHILE\\_LOCKED\\_BACKUP](#) was added in 8.0.17, removed after 8.0.32.
  - Error number: 3857; Symbol: [ER\\_RPL\\_CANT\\_STOP\\_REPLICA\\_WHILE\\_LOCKED\\_BACKUP](#); SQLSTATE: HY000  
Message: Cannot stop the replica SQL thread while the instance is locked for backup. Try running `UNLOCK INSTANCE` first.  
[ER\\_RPL\\_CANT\\_STOP\\_REPLICA\\_WHILE\\_LOCKED\\_BACKUP](#) was added in 8.0.33.
  - Error number: 3858; Symbol: [ER\\_WARN\\_DEPRECATED\\_FLOAT\\_DIGITS](#); SQLSTATE: HY000  
Message: Specifying number of digits for floating point data types is deprecated and will be removed in a future release.  
[ER\\_WARN\\_DEPRECATED\\_FLOAT\\_DIGITS](#) was added in 8.0.17.
  - Error number: 3859; Symbol: [ER\\_WARN\\_DEPRECATED\\_FLOAT\\_UNSIGNED](#); SQLSTATE: HY000  
Message: UNSIGNED for decimal and floating point data types is deprecated and support for it will be removed in a future release.  
[ER\\_WARN\\_DEPRECATED\\_FLOAT\\_UNSIGNED](#) was added in 8.0.17.
  - Error number: 3860; Symbol: [ER\\_WARN\\_DEPRECATED\\_INTEGER\\_DISPLAY\\_WIDTH](#); SQLSTATE: HY000  
Message: Integer display width is deprecated and will be removed in a future release.  
[ER\\_WARN\\_DEPRECATED\\_INTEGER\\_DISPLAY\\_WIDTH](#) was added in 8.0.17.

- 
- Error number: 3861; Symbol: [ER\\_WARN\\_DEPRECATED\\_ZEROFILL](#); SQLSTATE: [HY000](#)  
Message: The ZEROFILL attribute is deprecated and will be removed in a future release. Use the LPAD function to zero-pad numbers, or store the formatted numbers in a CHAR column.  
[ER\\_WARN\\_DEPRECATED\\_ZEROFILL](#) was added in 8.0.17.
  - Error number: 3862; Symbol: [ER\\_CLONE\\_DONOR](#); SQLSTATE: [HY000](#)  
Message: Clone Donor Error: %s.  
[ER\\_CLONE\\_DONOR](#) was added in 8.0.17.
  - Error number: 3863; Symbol: [ER\\_CLONE\\_PROTOCOL](#); SQLSTATE: [HY000](#)  
Message: Clone received unexpected response from Donor : %s.  
[ER\\_CLONE\\_PROTOCOL](#) was added in 8.0.17.
  - Error number: 3864; Symbol: [ER\\_CLONE\\_DONOR\\_VERSION](#); SQLSTATE: [HY000](#)  
Message: Clone Donor MySQL version: %s is different from Recipient MySQL version %s.  
[ER\\_CLONE\\_DONOR\\_VERSION](#) was added in 8.0.17.
  - Error number: 3865; Symbol: [ER\\_CLONE\\_OS](#); SQLSTATE: [HY000](#)  
Message: Clone Donor OS: %s is different from Recipient OS: %s.  
[ER\\_CLONE\\_OS](#) was added in 8.0.17.
  - Error number: 3866; Symbol: [ER\\_CLONE\\_PLATFORM](#); SQLSTATE: [HY000](#)  
Message: Clone Donor platform: %s is different from Recipient platform: %s.  
[ER\\_CLONE\\_PLATFORM](#) was added in 8.0.17.
  - Error number: 3867; Symbol: [ER\\_CLONE\\_CHARSET](#); SQLSTATE: [HY000](#)  
Message: Clone Donor collation: %s is unavailable in Recipient.  
[ER\\_CLONE\\_CHARSET](#) was added in 8.0.17.
  - Error number: 3868; Symbol: [ER\\_CLONE\\_CONFIG](#); SQLSTATE: [HY000](#)  
Message: Clone Configuration %s: Donor value: %s is different from Recipient value: %s.  
[ER\\_CLONE\\_CONFIG](#) was added in 8.0.17.
  - Error number: 3869; Symbol: [ER\\_CLONE\\_SYS\\_CONFIG](#); SQLSTATE: [HY000](#)  
Message: Clone system configuration: %s  
[ER\\_CLONE\\_SYS\\_CONFIG](#) was added in 8.0.17.
  - Error number: 3870; Symbol: [ER\\_CLONE\\_PLUGIN\\_MATCH](#); SQLSTATE: [HY000](#)  
Message: Clone Donor plugin %s is not active in Recipient.  
[ER\\_CLONE\\_PLUGIN\\_MATCH](#) was added in 8.0.17.

- 
- Error number: [3871](#); Symbol: [ER\\_CLONE\\_LOOPBACK](#); SQLSTATE: [HY000](#)  
Message: Clone cannot use loop back connection while cloning into current data directory.  
[ER\\_CLONE\\_LOOPBACK](#) was added in 8.0.17.
  - Error number: [3872](#); Symbol: [ER\\_CLONE\\_ENCRYPTION](#); SQLSTATE: [HY000](#)  
Message: Clone needs SSL connection for encrypted table.  
[ER\\_CLONE\\_ENCRYPTION](#) was added in 8.0.17.
  - Error number: [3873](#); Symbol: [ER\\_CLONE\\_DISK\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Clone estimated database size is %s. Available space %s is not enough.  
[ER\\_CLONE\\_DISK\\_SPACE](#) was added in 8.0.17.
  - Error number: [3874](#); Symbol: [ER\\_CLONE\\_IN\\_PROGRESS](#); SQLSTATE: [HY000](#)  
Message: Concurrent clone in progress. Please try after clone is complete.  
[ER\\_CLONE\\_IN\\_PROGRESS](#) was added in 8.0.17.
  - Error number: [3875](#); Symbol: [ER\\_CLONE\\_DISALLOWED](#); SQLSTATE: [HY000](#)  
Message: The clone operation cannot be executed when %s.  
[ER\\_CLONE\\_DISALLOWED](#) was added in 8.0.17.
  - Error number: [3876](#); Symbol: [ER\\_CANNOT\\_GRANT\\_ROLES\\_TO\\_ANONYMOUS\\_USER](#); SQLSTATE: [HY000](#)  
Message: Cannot grant roles to an anonymous user.  
[ER\\_CANNOT\\_GRANT\\_ROLES\\_TO\\_ANONYMOUS\\_USER](#) was added in 8.0.16.
  - Error number: [3877](#); Symbol: [ER\\_SECONDARY\\_ENGINE\\_PLUGIN](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_SECONDARY\\_ENGINE\\_PLUGIN](#) was added in 8.0.14.
  - Error number: [3878](#); Symbol: [ER\\_SECOND\\_PASSWORD\\_CANNOT\\_BE\\_EMPTY](#); SQLSTATE: [HY000](#)  
Message: Empty password can not be retained as second password for user '%s'@'%s'.  
[ER\\_SECOND\\_PASSWORD\\_CANNOT\\_BE\\_EMPTY](#) was added in 8.0.14.
  - Error number: [3879](#); Symbol: [ER\\_DB\\_ACCESS\\_DENIED](#); SQLSTATE: [HY000](#)  
Message: Access denied for AuthId `%s`@`%s` to database '%s'.  
[ER\\_DB\\_ACCESS\\_DENIED](#) was added in 8.0.16.
  - Error number: [3880](#); Symbol: [ER\\_DA\\_AUTH\\_ID\\_WITH\\_SYSTEM\\_USER\\_PRIV\\_IN\\_MANDATORY\\_ROLES](#); SQLSTATE: [HY000](#)  
Message: Cannot set mandatory\_roles: AuthId `%s`@`%s` has '%s' privilege.  
[ER\\_DA\\_AUTH\\_ID\\_WITH\\_SYSTEM\\_USER\\_PRIV\\_IN\\_MANDATORY\\_ROLES](#) was added in 8.0.17.

- 
- Error number: 3881; Symbol: [ER\\_DA\\_RPL\\_GTID\\_TABLE\\_CANNOT\\_OPEN](#); SQLSTATE: HY000  
Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.  
[ER\\_DA\\_RPL\\_GTID\\_TABLE\\_CANNOT\\_OPEN](#) was added in 8.0.17.
  - Error number: 3882; Symbol: [ER\\_GEOMETRY\\_IN\\_UNKNOWN\\_LENGTH\\_UNIT](#); SQLSTATE: SU001  
Message: The geometry passed to function %s is in SRID 0, which doesn't specify a length unit. Can't convert to '%s'.  
[ER\\_GEOMETRY\\_IN\\_UNKNOWN\\_LENGTH\\_UNIT](#) was added in 8.0.14.
  - Error number: 3883; Symbol: [ER\\_DA\\_PLUGIN\\_INSTALL\\_ERROR](#); SQLSTATE: HY000  
Message: Error installing plugin '%s': %s  
[ER\\_DA\\_PLUGIN\\_INSTALL\\_ERROR](#) was added in 8.0.17.
  - Error number: 3884; Symbol: [ER\\_NO\\_SESSION\\_TEMP](#); SQLSTATE: HY000  
Message: Storage engine could not allocate temporary tablespace for this session.  
[ER\\_NO\\_SESSION\\_TEMP](#) was added in 8.0.13.
  - Error number: 3885; Symbol: [ER\\_DA\\_UNKNOWN\\_ERROR\\_NUMBER](#); SQLSTATE: HY000  
Message: Got unknown error: %d  
[ER\\_DA\\_UNKNOWN\\_ERROR\\_NUMBER](#) was added in 8.0.17.
  - Error number: 3886; Symbol: [ER\\_COLUMN\\_CHANGE\\_SIZE](#); SQLSTATE: HY000  
Message: Could not change column '%s' of table '%s'. The resulting size of index '%s' would exceed the max key length of %d bytes.  
[ER\\_COLUMN\\_CHANGE\\_SIZE](#) was added in 8.0.14.
  - Error number: 3887; Symbol: [ER\\_REGEX\\_INVALID\\_CAPTURE\\_GROUP\\_NAME](#); SQLSTATE: HY000  
Message: A capture group has an invalid name.  
[ER\\_REGEX\\_INVALID\\_CAPTURE\\_GROUP\\_NAME](#) was added in 8.0.11.
  - Error number: 3888; Symbol: [ER\\_DA\\_SSL\\_LIBRARY\\_ERROR](#); SQLSTATE: HY000  
Message: Failed to set up SSL because of the following SSL library error: %s  
[ER\\_DA\\_SSL\\_LIBRARY\\_ERROR](#) was added in 8.0.17.
  - Error number: 3889; Symbol: [ER\\_SECONDARY\\_ENGINE](#); SQLSTATE: HY000  
Message: Secondary engine operation failed. %s.  
[ER\\_SECONDARY\\_ENGINE](#) was added in 8.0.13.
  - Error number: 3890; Symbol: [ER\\_SECONDARY\\_ENGINE\\_DDL](#); SQLSTATE: HY000  
Message: DDLs on a table with a secondary engine defined are not allowed.

---

[ER\\_SECONDARY\\_ENGINE\\_DDL](#) was added in 8.0.13.

- Error number: [3891](#); Symbol: [ER\\_INCORRECT\\_CURRENT\\_PASSWORD](#); SQLSTATE: [HY000](#)  
Message: Incorrect current password. Specify the correct password which has to be replaced.  
[ER\\_INCORRECT\\_CURRENT\\_PASSWORD](#) was added in 8.0.13.
- Error number: [3892](#); Symbol: [ER\\_MISSING\\_CURRENT\\_PASSWORD](#); SQLSTATE: [HY000](#)  
Message: Current password needs to be specified in the REPLACE clause in order to change it.  
[ER\\_MISSING\\_CURRENT\\_PASSWORD](#) was added in 8.0.13.
- Error number: [3893](#); Symbol: [ER\\_CURRENT\\_PASSWORD\\_NOT\\_REQUIRED](#); SQLSTATE: [HY000](#)  
Message: Do not specify the current password while changing it for other users.  
[ER\\_CURRENT\\_PASSWORD\\_NOT\\_REQUIRED](#) was added in 8.0.13.
- Error number: [3894](#); Symbol: [ER\\_PASSWORD\\_CANNOT\\_BE\\_RETAINED\\_ON\\_PLUGIN\\_CHANGE](#); SQLSTATE: [HY000](#)  
Message: Current password can not be retained for user '%s'@'%s' because authentication plugin is being changed.  
[ER\\_PASSWORD\\_CANNOT\\_BE\\_RETAINED\\_ON\\_PLUGIN\\_CHANGE](#) was added in 8.0.14.
- Error number: [3895](#); Symbol: [ER\\_CURRENT\\_PASSWORD\\_CANNOT\\_BE\\_RETAINED](#); SQLSTATE: [HY000](#)  
Message: Current password can not be retained for user '%s'@'%s' because new password is empty.  
[ER\\_CURRENT\\_PASSWORD\\_CANNOT\\_BE\\_RETAINED](#) was added in 8.0.14.
- Error number: [3896](#); Symbol: [ER\\_PARTIAL\\_REVOKES\\_EXIST](#); SQLSTATE: [HY000](#)  
Message: At least one partial revoke exists on a database. The system variable '@@partial\_revokes' must be set to ON.  
[ER\\_PARTIAL\\_REVOKES\\_EXIST](#) was added in 8.0.16.
- Error number: [3897](#); Symbol: [ER\\_CANNOT\\_GRANT\\_SYSTEM\\_PRIV\\_TO\\_MANDATORY\\_ROLE](#); SQLSTATE: [HY000](#)  
Message: AuthId '%s'@'%s' is set as mandatory\_roles. Cannot grant the '%s' privilege.  
[ER\\_CANNOT\\_GRANT\\_SYSTEM\\_PRIV\\_TO\\_MANDATORY\\_ROLE](#) was added in 8.0.16.
- Error number: [3898](#); Symbol: [ER\\_XA\\_REPLICATION\\_FILTERS](#); SQLSTATE: [HY000](#)  
Message: The use of replication filters with XA transactions is not supported, and can lead to an undefined state in the replica.  
[ER\\_XA\\_REPLICATION\\_FILTERS](#) was added in 8.0.12.
- Error number: [3899](#); Symbol: [ER\\_UNSUPPORTED\\_SQL\\_MODE](#); SQLSTATE: [HY000](#)  
Message: sql\_mode=0x%08x is not supported.

---

`ER_UNSUPPORTED_SQL_MODE` was added in 8.0.11.

- Error number: 3900; Symbol: `ER_REGEX_INVALID_FLAG`; SQLSTATE: HY000

Message: Invalid match mode flag in regular expression.

`ER_REGEX_INVALID_FLAG` was added in 8.0.12.

- Error number: 3901; Symbol: `ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXISTS`; SQLSTATE: HY000

Message: '%s' privilege for database '%s' exists both as partial revoke and mysql.db simultaneously. It could mean that the 'mysql' schema is corrupted.

`ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXISTS` was added in 8.0.16.

- Error number: 3902; Symbol: `ER_UNIT_NOT_FOUND`; SQLSTATE: SU001

Message: There's no unit of measure named '%s'.

`ER_UNIT_NOT_FOUND` was added in 8.0.14.

- Error number: 3903; Symbol: `ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX`; SQLSTATE: 22018

Message: Invalid JSON value for CAST for functional index '%s'.

`ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX` was added in 8.0.16.

- Error number: 3904; Symbol: `ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX`; SQLSTATE: 22003

Message: Out of range JSON value for CAST for functional index '%s'.

`ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX` was added in 8.0.16.

- Error number: 3905; Symbol: `ER_EXCEEDED_MV_KEYS_NUM`; SQLSTATE: HY000

Message: Exceeded max number of values per record for multi-valued index '%s' by %u value(s).

`ER_EXCEEDED_MV_KEYS_NUM` was added in 8.0.16.

- Error number: 3906; Symbol: `ER_EXCEEDED_MV_KEYS_SPACE`; SQLSTATE: HY000

Message: Exceeded max total length of values per record for multi-valued index '%s' by %u bytes.

`ER_EXCEEDED_MV_KEYS_SPACE` was added in 8.0.16.

- Error number: 3907; Symbol: `ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG`; SQLSTATE: 22001

Message: Data too long for functional index '%s'.

`ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG` was added in 8.0.16.

- Error number: 3908; Symbol: `ER_WRONG_MVI_VALUE`; SQLSTATE: HY000

Message: Cannot store an array or an object in a scalar key part of the index '%s'.

`ER_WRONG_MVI_VALUE` was added in 8.0.16.



- 
- Error number: [3909](#); Symbol: [ER\\_WARN\\_FUNC\\_INDEX\\_NOT\\_APPLICABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot use functional index '%s' due to type or collation conversion.  
[ER\\_WARN\\_FUNC\\_INDEX\\_NOT\\_APPLICABLE](#) was added in 8.0.16.
  - Error number: [3910](#); Symbol: [ER\\_GRP\\_RPL\\_UDF\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: The function '%s' failed. %s  
[ER\\_GRP\\_RPL\\_UDF\\_ERROR](#) was added in 8.0.13.
  - Error number: [3911](#); Symbol: [ER\\_UPDATE\\_GTID\\_PURGED\\_WITH\\_GR](#); SQLSTATE: [HY000](#)  
Message: Cannot update GTID\_PURGED with the Group Replication plugin running  
[ER\\_UPDATE\\_GTID\\_PURGED\\_WITH\\_GR](#) was added in 8.0.12.
  - Error number: [3912](#); Symbol: [ER\\_GROUPING\\_ON\\_TIMESTAMP\\_IN\\_DST](#); SQLSTATE: [HY000](#)  
Message: Grouping on temporal is non-deterministic for timezones having DST. Please consider switching to UTC for this query.  
[ER\\_GROUPING\\_ON\\_TIMESTAMP\\_IN\\_DST](#) was added in 8.0.17.
  - Error number: [3913](#); Symbol: [ER\\_TABLE\\_NAME\\_CAUSES\\_TOO\\_LONG\\_PATH](#); SQLSTATE: [HY000](#)  
Message: Long database name and identifier for object resulted in a path length too long for table '%s'. Please check the path limit for your OS.  
[ER\\_TABLE\\_NAME\\_CAUSES\\_TOO\\_LONG\\_PATH](#) was added in 8.0.4.
  - Error number: [3914](#); Symbol: [ER\\_AUDIT\\_LOG\\_INSUFFICIENT\\_PRIVILEGE](#); SQLSTATE: [HY000](#)  
Message: Request ignored for '%s'@'%s'. Role needed to perform operation: '%s'  
[ER\\_AUDIT\\_LOG\\_INSUFFICIENT\\_PRIVILEGE](#) was added in 8.0.16.
  - Error number: [3916](#); Symbol: [ER\\_DA\\_GRP\\_RPL\\_STARTED\\_AUTO\\_REJOIN](#); SQLSTATE: [HY000](#)  
Message: Started auto-rejoin procedure attempt %lu of %lu  
[ER\\_DA\\_GRP\\_RPL\\_STARTED\\_AUTO\\_REJOIN](#) was added in 8.0.17.
  - Error number: [3917](#); Symbol: [ER\\_SYSVAR\\_CHANGE\\_DURING\\_QUERY](#); SQLSTATE: [HY000](#)  
Message: A plugin was loaded or unloaded during a query, a system variable table was changed.  
[ER\\_SYSVAR\\_CHANGE\\_DURING\\_QUERY](#) was added in 8.0.18.
  - Error number: [3918](#); Symbol: [ER\\_GLOBSTAT\\_CHANGE\\_DURING\\_QUERY](#); SQLSTATE: [HY000](#)  
Message: A plugin was loaded or unloaded during a query, a global status variable was changed.  
[ER\\_GLOBSTAT\\_CHANGE\\_DURING\\_QUERY](#) was added in 8.0.18.
  - Error number: [3919](#); Symbol: [ER\\_GRP\\_RPL\\_MESSAGE\\_SERVICE\\_INIT\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: The START GROUP\_REPLICATION command failed to start its message service.

---

`ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE` was added in 8.0.18.

- Error number: 3920; Symbol: `ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_CLIENT`; SQLSTATE: HY000

Message: Invalid MASTER\_COMPRESSION\_ALGORITHMS '%s' for channel '%s'.

`ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_CLIENT` was added in 8.0.18, removed after 8.0.32.

- Error number: 3920; Symbol: `ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_CLIENT`; SQLSTATE: HY000

Message: Invalid SOURCE\_COMPRESSION\_ALGORITHMS '%s' for channel '%s'.

`ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_CLIENT` was added in 8.0.33.

- Error number: 3921; Symbol: `ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL_CLIENT`; SQLSTATE: HY000

Message: Invalid MASTER\_ZSTD\_COMPRESSION\_LEVEL %u for channel '%s'.

`ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL_CLIENT` was added in 8.0.18, removed after 8.0.32.

- Error number: 3921; Symbol: `ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CLIENT`; SQLSTATE: HY000

Message: Invalid SOURCE\_ZSTD\_COMPRESSION\_LEVEL %u for channel '%s'.

`ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CLIENT` was added in 8.0.33.

- Error number: 3922; Symbol: `ER_WRONG_COMPRESSION_ALGORITHM_CLIENT`; SQLSTATE: HY000

Message: Invalid compression algorithm '%s'.

`ER_WRONG_COMPRESSION_ALGORITHM_CLIENT` was added in 8.0.18.

- Error number: 3923; Symbol: `ER_WRONG_COMPRESSION_LEVEL_CLIENT`; SQLSTATE: HY000

Message: Invalid zstd compression level for algorithm '%s'.

`ER_WRONG_COMPRESSION_LEVEL_CLIENT` was added in 8.0.18.

- Error number: 3924; Symbol: `ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT`; SQLSTATE: HY000

Message: Specified compression algorithm list '%s' exceeds total count of 3 for channel '%s'.

`ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT` was added in 8.0.18, removed after 8.0.32.

- Error number: 3924; Symbol: `ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT`; SQLSTATE: HY000

Message: Specified compression algorithm list '%s' exceeds total count of 3 for channel '%s'.

`ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT` was added in 8.0.33.

- 
- Error number: 3925; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ANONYMOUS`; SQLSTATE: HY000  
Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' was set to ``@`%s`, but anonymous users are disallowed for PRIVILEGE\_CHECKS\_USER.  
`ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ANONYMOUS` was added in 8.0.18.
  - Error number: 3926; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST`; SQLSTATE: HY000  
Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' was set to `%s`@`%s`, but this is not an existing user.  
`ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST` was added in 8.0.18.
  - Error number: 3927; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT`; SQLSTATE: HY000  
Message: Invalid, corrupted PRIVILEGE\_CHECKS\_USER was found in the replication configuration repository for channel '%s'. Use CHANGE REPLICATION SOURCE TO PRIVILEGE\_CHECKS\_USER to correct the configuration.  
`ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT` was added in 8.0.18.
  - Error number: 3928; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV`; SQLSTATE: HY000  
Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' was set to `%s`@`%s`, but this user does not have REPLICATION\_APPLIER privilege.  
`ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV` was added in 8.0.18.
  - Error number: 3929; Symbol: `ER_WARN_DA_PRIVILEGE_NOT_REGISTERED`; SQLSTATE: HY000  
Message: Dynamic privilege '%s' is not registered with the server.  
`ER_WARN_DA_PRIVILEGE_NOT_REGISTERED` was added in 8.0.18.
  - Error number: 3930; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_INVALID`; SQLSTATE: HY000  
Message: Function '%s' failed because key is invalid.  
`ER_CLIENT_KEYRING_UDF_KEY_INVALID` was added in 8.0.19.
  - Error number: 3931; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID`; SQLSTATE: HY000  
Message: Function '%s' failed because key type is invalid.  
`ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID` was added in 8.0.19.
  - Error number: 3932; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG`; SQLSTATE: HY000  
Message: Function '%s' failed because key length is too long.  
`ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG` was added in 8.0.19.
  - Error number: 3933; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG`; SQLSTATE: HY000  
Message: Function '%s' failed because key type is too long.
-

---

`ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG` was added in 8.0.19.

- Error number: 3934; Symbol: `ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILED_REPORT`; SQLSTATE: `HY000`

Message: %s.

`ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILED_REPORT` was added in 8.0.19.

- Error number: 3935; Symbol: `ER_DA_UDF_INVALID_CHARSET_SPECIFIED`; SQLSTATE: `HY000`

Message: Invalid character set '%s' was specified. It must be either character set name or collation name as supported by server.

`ER_DA_UDF_INVALID_CHARSET_SPECIFIED` was added in 8.0.19.

- Error number: 3936; Symbol: `ER_DA_UDF_INVALID_CHARSET`; SQLSTATE: `HY000`

Message: Invalid character set '%s' was specified. It must be a character set name as supported by server.

`ER_DA_UDF_INVALID_CHARSET` was added in 8.0.19.

- Error number: 3937; Symbol: `ER_DA_UDF_INVALID_COLLATION`; SQLSTATE: `HY000`

Message: Invalid collation '%s' was specified. It must be a collation name as supported by server.

`ER_DA_UDF_INVALID_COLLATION` was added in 8.0.19.

- Error number: 3938; Symbol: `ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE`; SQLSTATE: `HY000`

Message: Invalid extension argument type '%s' was specified. Refer the MySQL manual for the valid UDF extension arguments type.

`ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE` was added in 8.0.19.

- Error number: 3939; Symbol: `ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME`; SQLSTATE: `HY000`

Message: Table has multiple constraints with the name '%s'. Please use constraint specific '%s' clause.

`ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME` was added in 8.0.19.

- Error number: 3940; Symbol: `ER_CONSTRAINT_NOT_FOUND`; SQLSTATE: `HY000`

Message: Constraint '%s' does not exist.

`ER_CONSTRAINT_NOT_FOUND` was added in 8.0.19.

- Error number: 3941; Symbol: `ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Altering constraint enforcement is not supported for the constraint '%s'. Enforcement state alter is not supported for the PRIMARY, UNIQUE and FOREIGN KEY type constraints.

`ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED` was added in 8.0.19.

- 
- Error number: 3942; Symbol: `ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS`; SQLSTATE: `HY000`  
Message: Each row of a VALUES clause must have at least one column, unless when used as source in an INSERT statement.  
`ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS` was added in 8.0.19.
  - Error number: 3943; Symbol: `ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT`; SQLSTATE: `HY000`  
Message: A VALUES clause cannot use DEFAULT values, unless used as a source in an INSERT statement.  
`ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT` was added in 8.0.19.
  - Error number: 3944; Symbol: `ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT`; SQLSTATE: `HY000`  
Message: The query does not comply with variable `require_row_format` restrictions.  
`ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT` was added in 8.0.19.
  - Error number: 3945; Symbol: `ER_REQUIRE_ROW_FORMAT_INVALID_VALUE`; SQLSTATE: `HY000`  
Message: The requested value %s is invalid for REQUIRE\_ROW\_FORMAT, must be either 0 or 1.  
`ER_REQUIRE_ROW_FORMAT_INVALID_VALUE` was added in 8.0.19.
  - Error number: 3946; Symbol: `ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY`; SQLSTATE: `HY000`  
Message: Failed to acquire lock on user management service, unable to determine if role `%s`@`%s` is mandatory  
`ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY` was added in 8.0.19.
  - Error number: 3947; Symbol: `ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST`; SQLSTATE: `HY000`  
Message: Failed to acquire lock on user management service, unable to fetch mandatory role list  
`ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST` was added in 8.0.19.
  - Error number: 3948; Symbol: `ER_CLIENT_LOCAL_FILES_DISABLED`; SQLSTATE: `42000`  
Message: Loading local data is disabled; this must be enabled on both the client and server sides  
`ER_CLIENT_LOCAL_FILES_DISABLED` was added in 8.0.19.
  - Error number: 3949; Symbol: `ER_IMP_INCOMPATIBLE_CFG_VERSION`; SQLSTATE: `HY000`  
Message: Failed to import %s because the CFG file version (%u) is not compatible with the current version (%u)  
`ER_IMP_INCOMPATIBLE_CFG_VERSION` was added in 8.0.19.
  - Error number: 3950; Symbol: `ER_DA_OOM`; SQLSTATE: `HY000`  
Message: Out of memory
-

---

[ER\\_DA\\_OOM](#) was added in 8.0.19.

- Error number: 3951; Symbol: [ER\\_DA\\_UDF\\_INVALID\\_ARGUMENT\\_TO\\_SET\\_CHARSET](#); SQLSTATE: HY000

Message: Character set can be set only for the UDF argument type STRING.

[ER\\_DA\\_UDF\\_INVALID\\_ARGUMENT\\_TO\\_SET\\_CHARSET](#) was added in 8.0.19.

- Error number: 3952; Symbol: [ER\\_DA\\_UDF\\_INVALID\\_RETURN\\_TYPE\\_TO\\_SET\\_CHARSET](#); SQLSTATE: HY000

Message: Character set can be set only for the UDF RETURN type STRING.

[ER\\_DA\\_UDF\\_INVALID\\_RETURN\\_TYPE\\_TO\\_SET\\_CHARSET](#) was added in 8.0.19.

- Error number: 3953; Symbol: [ER\\_MULTIPLE\\_INTO\\_CLAUSES](#); SQLSTATE: HY000

Message: Multiple INTO clauses in one query block.

[ER\\_MULTIPLE\\_INTO\\_CLAUSES](#) was added in 8.0.19.

- Error number: 3954; Symbol: [ER\\_MISPLACED\\_INTO](#); SQLSTATE: HY000

Message: Misplaced INTO clause, INTO is not allowed inside subqueries, and must be placed at end of UNION clauses.

[ER\\_MISPLACED\\_INTO](#) was added in 8.0.19.

- Error number: 3955; Symbol: [ER\\_USER\\_ACCESS\\_DENIED\\_FOR\\_USER\\_ACCOUNT\\_BLOCKED\\_BY\\_PASSWORD\\_LOCK](#); SQLSTATE: HY000

Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins.

[ER\\_USER\\_ACCESS\\_DENIED\\_FOR\\_USER\\_ACCOUNT\\_BLOCKED\\_BY\\_PASSWORD\\_LOCK](#) was added in 8.0.19.

- Error number: 3956; Symbol: [ER\\_WARN\\_DEPRECATED\\_YEAR\\_UNSIGNED](#); SQLSTATE: HY000

Message: UNSIGNED for the YEAR data type is deprecated and support for it will be removed in a future release.

[ER\\_WARN\\_DEPRECATED\\_YEAR\\_UNSIGNED](#) was added in 8.0.19.

- Error number: 3957; Symbol: [ER\\_CLONE\\_NETWORK\\_PACKET](#); SQLSTATE: HY000

Message: Clone needs max\_allowed\_packet value to be %u or more. Current value is %u

[ER\\_CLONE\\_NETWORK\\_PACKET](#) was added in 8.0.19.

- Error number: 3958; Symbol: [ER\\_SDI\\_OPERATION\\_FAILED\\_MISSING\\_RECORD](#); SQLSTATE: HY000

Message: Failed to %s sdi for %s.%s in %s due to missing record.

[ER\\_SDI\\_OPERATION\\_FAILED\\_MISSING\\_RECORD](#) was added in 8.0.19.

- 
- Error number: [3959](#); Symbol: [ER\\_DEPENDENT\\_BY\\_CHECK\\_CONSTRAINT](#); SQLSTATE: [HY000](#)  
Message: Check constraint '%s' uses column '%s', hence column cannot be dropped or renamed.  
[ER\\_DEPENDENT\\_BY\\_CHECK\\_CONSTRAINT](#) was added in 8.0.19.
  - Error number: [3960](#); Symbol: [ER\\_GRP\\_OPERATION\\_NOT\\_ALLOWED\\_GR\\_MUST\\_STOP](#); SQLSTATE: [HY000](#)  
Message: This operation cannot be performed while Group Replication is running; run STOP GROUP\_REPLICATION first  
[ER\\_GRP\\_OPERATION\\_NOT\\_ALLOWED\\_GR\\_MUST\\_STOP](#) was added in 8.0.20.
  - Error number: [3961](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_JSON\\_TABLE\\_ON\\_ERROR\\_ON\\_EMPTY](#); SQLSTATE: [HY000](#)  
Message: Specifying an ON EMPTY clause after the ON ERROR clause in a JSON\_TABLE column definition is deprecated syntax and will be removed in a future release. Specify ON EMPTY before ON ERROR instead.  
[ER\\_WARN\\_DEPRECATED\\_JSON\\_TABLE\\_ON\\_ERROR\\_ON\\_EMPTY](#) was added in 8.0.20.
  - Error number: [3962](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_INNER\\_INTO](#); SQLSTATE: [HY000](#)  
Message: The INTO clause is deprecated inside query blocks of query expressions and will be removed in a future release. Please move the INTO clause to the end of statement instead.  
[ER\\_WARN\\_DEPRECATED\\_INNER\\_INTO](#) was added in 8.0.20.
  - Error number: [3963](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_VALUES\\_FUNCTION\\_ALWAYS\\_NULL](#); SQLSTATE: [HY000](#)  
Message: The VALUES function is deprecated and will be removed in a future release. It always returns NULL in this context. If you meant to access a value from the VALUES clause of the INSERT statement, consider using an alias (INSERT INTO ... VALUES (...) AS alias) and reference alias.col instead of VALUES(col) in the ON DUPLICATE KEY UPDATE clause.  
[ER\\_WARN\\_DEPRECATED\\_VALUES\\_FUNCTION\\_ALWAYS\\_NULL](#) was added in 8.0.20.
  - Error number: [3964](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_SQL\\_CALC\\_FOUND\\_ROWS](#); SQLSTATE: [HY000](#)  
Message: SQL\_CALC\_FOUND\_ROWS is deprecated and will be removed in a future release. Consider using two separate queries instead.  
[ER\\_WARN\\_DEPRECATED\\_SQL\\_CALC\\_FOUND\\_ROWS](#) was added in 8.0.16.
  - Error number: [3965](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_FOUND\\_ROWS](#); SQLSTATE: [HY000](#)  
Message: FOUND\_ROWS() is deprecated and will be removed in a future release. Consider using COUNT(\*) instead.  
[ER\\_WARN\\_DEPRECATED\\_FOUND\\_ROWS](#) was added in 8.0.16.
  - Error number: [3966](#); Symbol: [ER\\_MISSING\\_JSON\\_VALUE](#); SQLSTATE: [22035](#)  
Message: No value was found by '%s' on the specified path.  
[ER\\_MISSING\\_JSON\\_VALUE](#) was added in 8.0.21.

- 
- Error number: 3967; Symbol: [ER\\_MULTIPLE\\_JSON\\_VALUES](#); SQLSTATE: 22034  
Message: More than one value was found by '%s' on the specified path.  
[ER\\_MULTIPLE\\_JSON\\_VALUES](#) was added in 8.0.21.
  - Error number: 3968; Symbol: [ER\\_HOSTNAME\\_TOO\\_LONG](#); SQLSTATE: HY000  
Message: Hostname cannot be longer than %d characters.  
[ER\\_HOSTNAME\\_TOO\\_LONG](#) was added in 8.0.21.
  - Error number: 3969; Symbol: [ER\\_WARN\\_CLIENT\\_DEPRECATED\\_PARTITION\\_PREFIX\\_KEY](#); SQLSTATE: HY000  
Message: Column '%s.%s.%s' having prefix key part '%s(%u)' is ignored by the partitioning function. Use of prefixed columns in the PARTITION BY KEY() clause is deprecated and will be removed in a future release.  
[ER\\_WARN\\_CLIENT\\_DEPRECATED\\_PARTITION\\_PREFIX\\_KEY](#) was added in 8.0.21.
  - Error number: 3970; Symbol: [ER\\_GROUP\\_REPLICATION\\_USER\\_EMPTY\\_MSG](#); SQLSTATE: HY000  
Message: The START GROUP\_REPLICATION command failed since the username provided for recovery channel is empty.  
[ER\\_GROUP\\_REPLICATION\\_USER\\_EMPTY\\_MSG](#) was added in 8.0.21.
  - Error number: 3971; Symbol: [ER\\_GROUP\\_REPLICATION\\_USER\\_MANDATORY\\_MSG](#); SQLSTATE: HY000  
Message: The START GROUP\_REPLICATION command failed since the USER option was not provided with PASSWORD for recovery channel.  
[ER\\_GROUP\\_REPLICATION\\_USER\\_MANDATORY\\_MSG](#) was added in 8.0.21.
  - Error number: 3972; Symbol: [ER\\_GROUP\\_REPLICATION\\_PASSWORD\\_LENGTH](#); SQLSTATE: HY000  
Message: The START GROUP\_REPLICATION command failed since the password provided for the recovery channel exceeds the maximum length of 32 characters.  
[ER\\_GROUP\\_REPLICATION\\_PASSWORD\\_LENGTH](#) was added in 8.0.21.
  - Error number: 3973; Symbol: [ER\\_SUBQUERY\\_TRANSFORM\\_REJECTED](#); SQLSTATE: HY000  
Message: Statement requires a transform of a subquery to a non-SET operation (like IN2EXISTS, or subquery-to-LATERAL-derived-table). This is not allowed with optimizer switch 'subquery\_to\_derived' on  
[ER\\_SUBQUERY\\_TRANSFORM\\_REJECTED](#) was added in 8.0.21.
  - Error number: 3974; Symbol: [ER\\_DA\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_FORMAT](#); SQLSTATE: HY000  
Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port)  
[ER\\_DA\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_FORMAT](#) was added in 8.0.21.



- 
- Error number: 3975; Symbol: `ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID`; SQLSTATE: HY000

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.

`ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID` was added in 8.0.21.

- Error number: 3976; Symbol: `ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART`; SQLSTATE: HY000

Message: Variable '%s' cannot be set to the value of '%s'. %s

`ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART` was added in 8.0.21.

- Error number: 3977; Symbol: `ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION`; SQLSTATE: HY000

Message: Only BINLOG INSERT, COMMIT and ROLLBACK statements are allowed after CREATE TABLE with START TRANSACTION statement.

`ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION` was added in 8.0.21.

- Error number: 3978; Symbol: `ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT`; SQLSTATE: HY000

Message: Foreign key creation is not allowed with CREATE TABLE as SELECT and CREATE TABLE with START TRANSACTION statement.

`ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT` was added in 8.0.21.

- Error number: 3979; Symbol: `ER_NOT_ALLOWED_WITH_START_TRANSACTION`; SQLSTATE: HY000

Message: START TRANSACTION clause cannot be used %s

`ER_NOT_ALLOWED_WITH_START_TRANSACTION` was added in 8.0.21.

- Error number: 3980; Symbol: `ER_INVALID_JSON_ATTRIBUTE`; SQLSTATE: HY000

Message: Invalid json attribute, error: "%s" at pos %u: '%s'

`ER_INVALID_JSON_ATTRIBUTE` was added in 8.0.21.

- Error number: 3981; Symbol: `ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED`; SQLSTATE: HY000

Message: Storage engine '%s' does not support ENGINE\_ATTRIBUTE.

`ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED` was added in 8.0.21.

- Error number: 3982; Symbol: `ER_INVALID_USER_ATTRIBUTE_JSON`; SQLSTATE: HY000

Message: The user attribute must be a valid JSON object

`ER_INVALID_USER_ATTRIBUTE_JSON` was added in 8.0.21.

- 
- Error number: 3983; Symbol: `ER_INNODB_REDO_DISABLED`; SQLSTATE: `HY000`

Message: Cannot perform operation as InnoDB redo logging is disabled. Please retry after enabling redo log with ALTER INSTANCE

`ER_INNODB_REDO_DISABLED` was added in 8.0.21.

- Error number: 3984; Symbol: `ER_INNODB_REDO_ARCHIVING_ENABLED`; SQLSTATE: `HY000`

Message: Cannot perform operation as InnoDB is archiving redo log. Please retry after stopping redo archive by invoking `innodb_redo_log_archive_stop()`

`ER_INNODB_REDO_ARCHIVING_ENABLED` was added in 8.0.21.

- Error number: 3985; Symbol: `ER_MDL_OUT_OF_RESOURCES`; SQLSTATE: `HY000`

Message: Not enough resources to complete lock request.

`ER_MDL_OUT_OF_RESOURCES` was added in 8.0.21.

- Error number: 3986; Symbol: `ER_IMPLICIT_COMPARISON_FOR_JSON`; SQLSTATE: `HY000`

Message: Evaluating a JSON value in SQL boolean context does an implicit comparison against JSON integer 0; if this is not what you want, consider converting JSON to a SQL numeric type with `JSON_VALUE RETURNING`

`ER_IMPLICIT_COMPARISON_FOR_JSON` was added in 8.0.21.

- Error number: 3987; Symbol: `ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET`; SQLSTATE: `HY000`

Message: The function %s does not support the character set '%s'.

`ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET` was added in 8.0.21.

- Error number: 3988; Symbol: `ER_IMPOSSIBLE_STRING_CONVERSION`; SQLSTATE: `HY000`

Message: Conversion from collation %s into %s impossible for %s

`ER_IMPOSSIBLE_STRING_CONVERSION` was added in 8.0.22.

- Error number: 3989; Symbol: `ER_SCHEMA_READ_ONLY`; SQLSTATE: `HY000`

Message: Schema '%s' is in read only mode.

`ER_SCHEMA_READ_ONLY` was added in 8.0.22.

- Error number: 3990; Symbol: `ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF`; SQLSTATE: `HY000`

Message: Failed to enable Asynchronous Replication Connection Failover feature. The `CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 1` can only be set when `@@GLOBAL.GTID_MODE = ON`.

`ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF` was added in 8.0.22.

- 
- Error number: 3991; Symbol: `ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF`; SQLSTATE: HY000  
  
Message: Failed to enable Asynchronous Replication Connection Failover feature. The CHANGE REPLICATION SOURCE TO SOURCE\_CONNECTION\_AUTO\_FAILOVER = 1 can only be set when SOURCE\_AUTO\_POSITION option of CHANGE REPLICATION SOURCE TO is enabled.  
  
`ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF` was added in 8.0.22.
  - Error number: 3992; Symbol: `ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECT_OFF`; SQLSTATE: HY000  
  
Message: The @@GLOBAL.GTID\_MODE = %s cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE REPLICATION SOURCE TO SOURCE\_CONNECTION\_AUTO\_FAILOVER = 1.  
  
`ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECT_OFF` was added in 8.0.22.
  - Error number: 3993; Symbol: `ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECT_OFF`; SQLSTATE: HY000  
  
Message: CHANGE REPLICATION SOURCE TO SOURCE\_AUTO\_POSITION = 0 cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE REPLICATION SOURCE TO SOURCE\_CONNECTION\_AUTO\_FAILOVER = 1.  
  
`ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECT_OFF` was added in 8.0.22.
  - Error number: 3994; Symbol: `ER_INVALID_PARAMETER_USE`; SQLSTATE: HY000  
  
Message: Invalid use of parameters in '%s'  
  
`ER_INVALID_PARAMETER_USE` was added in 8.0.22.
  - Error number: 3995; Symbol: `ER_CHARACTER_SET_MISMATCH`; SQLSTATE: HY000  
  
Message: Character set '%s' cannot be used in conjunction with '%s' in call to %s.  
  
`ER_CHARACTER_SET_MISMATCH` was added in 8.0.22.
  - Error number: 3996; Symbol: `ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED`; SQLSTATE: HY000  
  
Message: Changing %s not supported on this platform. Falling back to the default.  
  
`ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED` was added in 8.0.22.
  - Error number: 3997; Symbol: `ER_INVALID_TIME_ZONE_INTERVAL`; SQLSTATE: HY000  
  
Message: Invalid time zone interval: '%s'  
  
`ER_INVALID_TIME_ZONE_INTERVAL` was added in 8.0.22.
  - Error number: 3998; Symbol: `ER_INVALID_CAST`; SQLSTATE: HY000  
  
Message: Cannot cast value to %s.  
  
`ER_INVALID_CAST` was added in 8.0.22.
  - Error number: 3999; Symbol: `ER_HYPERGRAPH_NOT_SUPPORTED_YET`; SQLSTATE: 42000

---

Message: The hypergraph optimizer does not yet support '%s'

[ER\\_HYPERGRAPH\\_NOT\\_SUPPORTED\\_YET](#) was added in 8.0.22.

- Error number: 4000; Symbol: [ER\\_WARN\\_HYPERGRAPH\\_EXPERIMENTAL](#); SQLSTATE: HY000

Message: The hypergraph optimizer is highly experimental and is meant for testing only. Do not enable it unless you are a MySQL developer.

[ER\\_WARN\\_HYPERGRAPH\\_EXPERIMENTAL](#) was added in 8.0.22.

- Error number: 4001; Symbol: [ER\\_DA\\_NO\\_ERROR\\_LOG\\_PARSER\\_CONFIGURED](#); SQLSTATE: HY000

Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance\_schema.error\_log.

[ER\\_DA\\_NO\\_ERROR\\_LOG\\_PARSER\\_CONFIGURED](#) was added in 8.0.22.

- Error number: 4002; Symbol: [ER\\_DA\\_ERROR\\_LOG\\_TABLE\\_DISABLED](#); SQLSTATE: HY000

Message: None of the log-sinks selected in @@global.log\_error\_services supports writing to the performance schema. The server will not be able to make the current runs' error events available in performance\_schema.error\_log. To change this, add a log-sink that supports the performance schema to @@global.log\_error\_services.

[ER\\_DA\\_ERROR\\_LOG\\_TABLE\\_DISABLED](#) was added in 8.0.22.

- Error number: 4003; Symbol: [ER\\_DA\\_ERROR\\_LOG\\_MULTIPLE\\_FILTERS](#); SQLSTATE: HY000

Message: @@global.log\_error\_services lists more than one log-filter service. This is discouraged as it will make it hard to understand which rule in which filter affected a log-event.

[ER\\_DA\\_ERROR\\_LOG\\_MULTIPLE\\_FILTERS](#) was added in 8.0.22.

- Error number: 4004; Symbol: [ER\\_DA\\_CANT\\_OPEN\\_ERROR\\_LOG](#); SQLSTATE: HY000

Message: Could not open file '%s' for error logging%s%s

[ER\\_DA\\_CANT\\_OPEN\\_ERROR\\_LOG](#) was added in 8.0.22.

- Error number: 4005; Symbol: [ER\\_USER\\_REFERENCED\\_AS\\_DEFINER](#); SQLSTATE: HY000

Message: User %s is referenced as a definer account in %s.

[ER\\_USER\\_REFERENCED\\_AS\\_DEFINER](#) was added in 8.0.22.

- Error number: 4006; Symbol: [ER\\_CANNOT\\_USER\\_REFERENCED\\_AS\\_DEFINER](#); SQLSTATE: HY000

Message: Operation %s failed for %s as it is referenced as a definer account in %s.

[ER\\_CANNOT\\_USER\\_REFERENCED\\_AS\\_DEFINER](#) was added in 8.0.22.

- Error number: 4007; Symbol: [ER\\_REGEX\\_NUMBER\\_TOO\\_BIG](#); SQLSTATE: HY000

Message: Decimal number in regular expression is too large.

[ER\\_REGEX\\_NUMBER\\_TOO\\_BIG](#) was added in 8.0.22.

- Error number: 4008; Symbol: [ER\\_SPVAR\\_NONINTEGER\\_TYPE](#); SQLSTATE: HY000

---

Message: The variable "%s" has a non-integer based type

[ER\\_SPVAR\\_NONINTEGER\\_TYPE](#) was added in 8.0.22.

- Error number: 4009; Symbol: [WARN\\_UNSUPPORTED\\_ACL\\_TABLES\\_READ](#); SQLSTATE: [HY000](#)

Message: Reads with serializable isolation/SELECT FOR SHARE are not supported for ACL tables.

[WARN\\_UNSUPPORTED\\_ACL\\_TABLES\\_READ](#) was added in 8.0.22.

- Error number: 4010; Symbol: [ER\\_BINLOG\\_UNSAFE\\_ACL\\_TABLE\\_READ\\_IN\\_DML\\_DDL](#); SQLSTATE: [HY000](#)

Message: The statement is unsafe because it updates a table depending on ACL table read operation. As storage engine row locks are skipped for ACL table, it may not have same effect on source and replica.

[ER\\_BINLOG\\_UNSAFE\\_ACL\\_TABLE\\_READ\\_IN\\_DML\\_DDL](#) was added in 8.0.22.

- Error number: 4011; Symbol: [ER\\_STOP\\_REPLICA\\_MONITOR\\_IO\\_THREAD\\_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP REPLICA command execution is incomplete: Replica Monitor thread got the stop signal, thread is busy, Monitor thread will stop once the current task is complete.

[ER\\_STOP\\_REPLICA\\_MONITOR\\_IO\\_THREAD\\_TIMEOUT](#) was added in 8.0.23.

- Error number: 4012; Symbol: [ER\\_STARTING\\_REPLICA\\_MONITOR\\_IO\\_THREAD](#); SQLSTATE: [HY000](#)

Message: The Replica Monitor thread failed to start.

[ER\\_STARTING\\_REPLICA\\_MONITOR\\_IO\\_THREAD](#) was added in 8.0.23.

- Error number: 4013; Symbol: [ER\\_CANT\\_USE\\_ANONYMOUS\\_TO\\_GTID\\_WITH\\_GTID\\_MODE\\_NOT\\_ON](#); SQLSTATE: [HY000](#)

Message: Replication cannot start%s with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` as this server uses `@@GLOBAL.GTID_MODE <> ON`.

[ER\\_CANT\\_USE\\_ANONYMOUS\\_TO\\_GTID\\_WITH\\_GTID\\_MODE\\_NOT\\_ON](#) was added in 8.0.23.

- Error number: 4014; Symbol: [ER\\_CANT\\_COMBINE\\_ANONYMOUS\\_TO\\_GTID\\_AND\\_AUTOPOSITION](#); SQLSTATE: [HY000](#)

Message: The options `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` and `SOURCE_AUTO_POSITION = 1` cannot be used together.

[ER\\_CANT\\_COMBINE\\_ANONYMOUS\\_TO\\_GTID\\_AND\\_AUTOPOSITION](#) was added in 8.0.23.

- 
- Error number: 4015; Symbol:  
`ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_REQUIRES_GTID_MODE_ON`; SQLSTATE:  
`HY000`  
  
Message: CHANGE REPLICATION SOURCE TO  
`ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` cannot be executed because  
`@@GLOBAL.GTID_MODE <> ON`.  
  
`ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_REQUIRES_GTID_MODE_ON` was added in  
8.0.23.
  - Error number: 4016; Symbol: `ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MODE_ON`;  
SQLSTATE: `HY000`  
  
Message: The value of `sql_slave_skip_counter` will only take effect for channels running with  
`ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS <> OFF`.  
  
`ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MODE_ON` was added in 8.0.23, removed after  
8.0.25.
  - Error number: 4016; Symbol: `ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE_ON`;  
SQLSTATE: `HY000`  
  
Message: The value of `sql_replica_skip_counter` will only take effect for channels running with  
`ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS <> OFF`.  
  
`ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE_ON` was added in 8.0.26.
  - Error number: 4017; Symbol:  
`ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_AS_LOCAL_OR_UUID`; SQLSTATE:  
`HY000`  
  
Message: Using `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS` creates limitations on the  
replication topology - you cannot fail over between downstream and upstream servers. Only use this  
option if it is not possible to enable GTIDs on the source, for instance, because of lack of permissions.  
If possible, use the procedure for enabling GTID transactions online instead, as described in the  
documentation.  
  
`ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_AS_LOCAL_OR_UUID` was added in  
8.0.23.
  - Error number: 4018; Symbol:  
`ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL_SQL_THD_AFTER_GTIDS`; SQLSTATE:  
`HY000`  
  
Message: `WAIT_UNTIL_SQL_THREAD_AFTER_GTIDS` cannot be used on a channel configured with  
`ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`  
  
`ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL_SQL_THD_AFTER_GTIDS` was added in  
8.0.23.
  - Error number: 4019; Symbol:  
`ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS_TO_GTID`; SQLSTATE: `HY000`  
  
Message: The `SQL_AFTER_GTIDS` or `SQL_BEFORE_GTIDS` clauses for  
`START REPLICA` cannot be used when the replication channel is configured with  
`ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`.

---

[ER\\_CANT\\_SET\\_SQL\\_AFTER\\_OR\\_BEFORE\\_GTIDS\\_WITH\\_ANONYMOUS\\_TO\\_GTID](#) was added in 8.0.23.

- Error number: 4020; Symbol: [ER\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_GROUP\\_NAME](#); SQLSTATE: HY000

Message: Replication '%s' is configured with ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS = <UUID> where the UUID value is equal to the group\_replication\_group\_name

[ER\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_GROUP\\_NAME](#) was added in 8.0.23.

- Error number: 4021; Symbol: [ER\\_CANT\\_USE\\_SAME\\_UUID\\_AS\\_GROUP\\_NAME](#); SQLSTATE: HY000

Message: CHANGE REPLICATION SOURCE TO ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS = <UUID> cannot be executed because the UUID value is equal to the group\_replication\_group\_name.

[ER\\_CANT\\_USE\\_SAME\\_UUID\\_AS\\_GROUP\\_NAME](#) was added in 8.0.23.

- Error number: 4022; Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_CHANNEL\\_STILL\\_RUNNING](#); SQLSTATE: HY000

Message: The group\_replication\_recovery channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.

[ER\\_GRP\\_RPL\\_RECOVERY\\_CHANNEL\\_STILL\\_RUNNING](#) was added in 8.0.23.

- Error number: 4023; Symbol: [ER\\_INNOADB\\_INVALID\\_AUTOEXTEND\\_SIZE\\_VALUE](#); SQLSTATE: HY000

Message: AUTOEXTEND\_SIZE should be a multiple of %uM

[ER\\_INNOADB\\_INVALID\\_AUTOEXTEND\\_SIZE\\_VALUE](#) was added in 8.0.23.

- Error number: 4024; Symbol: [ER\\_INNOADB\\_INCOMPATIBLE\\_WITH\\_TABLESPACE](#); SQLSTATE: HY000

Message: InnoDB: "%s" not allowed with general tablespaces

[ER\\_INNOADB\\_INCOMPATIBLE\\_WITH\\_TABLESPACE](#) was added in 8.0.23.

- Error number: 4025; Symbol: [ER\\_INNOADB\\_AUTOEXTEND\\_SIZE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: HY000

Message: AUTOEXTEND\_SIZE value should be between %uM and %uM

[ER\\_INNOADB\\_AUTOEXTEND\\_SIZE\\_OUT\\_OF\\_RANGE](#) was added in 8.0.23.

- Error number: 4026; Symbol: [ER\\_CANNOT\\_USE\\_AUTOEXTEND\\_SIZE\\_CLAUSE](#); SQLSTATE: HY000

Message: AUTOEXTEND\_SIZE clause is not valid for %s tablespace.

[ER\\_CANNOT\\_USE\\_AUTOEXTEND\\_SIZE\\_CLAUSE](#) was added in 8.0.23.

- Error number: 4027; Symbol: [ER\\_ROLE\\_GRANTED\\_TO\\_ITSELF](#); SQLSTATE: HY000

Message: User account %s is directly or indirectly granted to the role %s. The GRANT would create a loop

[ER\\_ROLE\\_GRANTED\\_TO\\_ITSELF](#) was added in 8.0.23.

- 
- Error number: 4028; Symbol: `ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN`; SQLSTATE: HY000  
Message: A table must have at least one visible column.  
`ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN` was added in 8.0.23.
  - Error number: 4029; Symbol: `ER_INNODB_COMPRESSION_FAILURE`; SQLSTATE: HY000  
Message: Compression failed with the following error : %s  
`ER_INNODB_COMPRESSION_FAILURE` was added in 8.0.23.
  - Error number: 4030; Symbol: `ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMESPACE`; SQLSTATE: HY000  
Message: The parameter `network_namespace` is reserved for future use. Please use the CHANGE REPLICATION SOURCE command to set channel `network_namespace` parameter.  
`ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMESPACE` was added in 8.0.23.
  - Error number: 4031; Symbol: `ER_CLIENT_INTERACTION_TIMEOUT`; SQLSTATE: HY000  
Message: The client was disconnected by the server because of inactivity. See `wait_timeout` and `interactive_timeout` for configuring this behavior.  
`ER_CLIENT_INTERACTION_TIMEOUT` was added in 8.0.24.
  - Error number: 4032; Symbol: `ER_INVALID_CAST_TO_GEOMETRY`; SQLSTATE: 22S01  
Message: Invalid cast from %s to %s.  
`ER_INVALID_CAST_TO_GEOMETRY` was added in 8.0.24.
  - Error number: 4033; Symbol: `ER_INVALID_CAST_POLYGON_RING_DIRECTION`; SQLSTATE: 22S04  
Message: Invalid cast from %s to %s. A polygon ring is in the wrong direction.  
`ER_INVALID_CAST_POLYGON_RING_DIRECTION` was added in 8.0.24.
  - Error number: 4034; Symbol: `ER_GIS_DIFFERENT_SRIDS_AGGREGATION`; SQLSTATE: 22S05  
Message: Arguments to function %s contains geometries with different SRIDs: %u and %u. All geometries must have the same SRID.  
`ER_GIS_DIFFERENT_SRIDS_AGGREGATION` was added in 8.0.24.
  - Error number: 4035; Symbol: `ER_RELOAD_KEYRING_FAILURE`; SQLSTATE: HY000  
Message: Keyring reload failed. Please check error log for more details.  
`ER_RELOAD_KEYRING_FAILURE` was added in 8.0.24.
  - Error number: 4036; Symbol: `ER_SDI_GET_KEYS_INVALID_TABLESPACE`; SQLSTATE: HY000  
Message: Tablespace '%s' is invalid for SDI operations.  
`ER_SDI_GET_KEYS_INVALID_TABLESPACE` was added in 8.0.24.
  - Error number: 4037; Symbol: `ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM_SIZE`; SQLSTATE: HY000



---

Message: Value too long setting SOURCE\_COMPRESSION\_ALGORITHMS option to a %d chars long string for channel '%s'.

[ER\\_CHANGE\\_RPL\\_SRC\\_WRONG\\_COMPRESSION\\_ALGORITHM\\_SIZE](#) was added in 8.0.24.

- Error number: 4038; Symbol: [ER\\_WARN\\_DEPRECATED\\_TLS\\_VERSION\\_FOR\\_CHANNEL\\_CLI](#); SQLSTATE: [HY000](#)

Message: A deprecated TLS version %s is enabled for channel %s. Please use TLSv1.2 or higher.

[ER\\_WARN\\_DEPRECATED\\_TLS\\_VERSION\\_FOR\\_CHANNEL\\_CLI](#) was added in 8.0.26, removed after 8.0.27.

- Error number: 4039; Symbol: [ER\\_CANT\\_USE\\_SAME\\_UUID\\_AS\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: [HY000](#)

Message: CHANGE REPLICATION SOURCE TO ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS = <UUID> cannot be executed because the UUID value is equal to the group\_replication\_view\_change\_uuid.

[ER\\_CANT\\_USE\\_SAME\\_UUID\\_AS\\_VIEW\\_CHANGE\\_UUID](#) was added in 8.0.26.

- Error number: 4040; Symbol: [ER\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: [HY000](#)

Message: Replication '%s' is configured with ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS = <UUID> where the UUID value is equal to the group\_replication\_view\_change\_uuid

[ER\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_VIEW\\_CHANGE\\_UUID](#) was added in 8.0.26.

- Error number: 4041; Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_FAIL\\_GET\\_VARIABLE](#); SQLSTATE: [HY000](#)

Message: Unable to retrieve group\_replication\_view\_change\_uuid variable during server checks on replication operations.

[ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_FAIL\\_GET\\_VARIABLE](#) was added in 8.0.26.

- Error number: 4042; Symbol: [ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_AND\\_PRUNE\\_SECONDS](#); SQLSTATE: [HY000](#)

Message: Both audit\_log\_max\_size and audit\_log\_prune\_seconds are set to non-zero. audit\_log\_max\_size takes precedence and audit\_log\_prune\_seconds is ignored

[ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_AND\\_PRUNE\\_SECONDS](#) was added in 8.0.26.

- Error number: 4043; Symbol: [ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_CLOSE\\_TO\\_ROTATE\\_ON\\_SIZE](#); SQLSTATE: [HY000](#)

Message: audit\_log\_rotate\_on\_size is not granular enough for the value of audit\_log\_max\_size supplied. Should be at least %d times smaller.

[ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_CLOSE\\_TO\\_ROTATE\\_ON\\_SIZE](#) was added in 8.0.26.

- 
- Error number: 4044; Symbol: [ER\\_KERBEROS\\_CREATE\\_USER](#); SQLSTATE: HY000  
Message: Create/Alter user has failed, Configured user realm as authentication string is empty, Please make sure to configure authentication string as user realm.  
[ER\\_KERBEROS\\_CREATE\\_USER](#) was added in 8.0.26.
  - Error number: 4045; Symbol: [ER\\_INSTALL\\_PLUGIN\\_CONFLICT\\_CLIENT](#); SQLSTATE: HY000  
Message: Cannot install the %s plugin when the %s plugin is installed.  
[ER\\_INSTALL\\_PLUGIN\\_CONFLICT\\_CLIENT](#) was added in 8.0.26.
  - Error number: 4046; Symbol: [ER\\_DA\\_ERROR\\_LOG\\_COMPONENT\\_FLUSH\\_FAILED](#); SQLSTATE: HY000  
Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush file-based logs may affect log-rotation.  
[ER\\_DA\\_ERROR\\_LOG\\_COMPONENT\\_FLUSH\\_FAILED](#) was added in 8.0.26.
  - Error number: 4047; Symbol: [ER\\_WARN\\_SQL\\_AFTER\\_MTS\\_GAPS\\_GAP\\_NOT\\_CALCULATED](#); SQLSTATE: HY000  
Message: The until clause SQL\_AFTER\_MTS\_GAPS is being used for channel '%s' when GTID\_MODE = ON and SOURCE\_AUTO\_POSITION=1 meaning the server did not compute internally what gaps may exist in the relay log transaction execution. To close any execution gaps use either the SQL\_BEFORE\_GTIDS or SQL\_AFTER\_GTIDS until clause.  
[ER\\_WARN\\_SQL\\_AFTER\\_MTS\\_GAPS\\_GAP\\_NOT\\_CALCULATED](#) was added in 8.0.26.
  - Error number: 4048; Symbol: [ER\\_INVALID\\_ASSIGNMENT\\_TARGET](#); SQLSTATE: 42000  
Message: Invalid target for assignment in INSERT or UPDATE statement '%s'.  
[ER\\_INVALID\\_ASSIGNMENT\\_TARGET](#) was added in 8.0.26.
  - Error number: 4049; Symbol: [ER\\_OPERATION\\_NOT\\_ALLOWED\\_ON\\_GR\\_SECONDARY](#); SQLSTATE: HY000  
Message: This operation cannot be performed on a Group Replication secondary member, it must be done on the group primary.  
[ER\\_OPERATION\\_NOT\\_ALLOWED\\_ON\\_GR\\_SECONDARY](#) was added in 8.0.26.
  - Error number: 4050; Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CHANNEL\\_STATUS\\_PROPAGATION](#); SQLSTATE: HY000  
Message: Unable to propagate the SOURCE\_CONNECTION\_AUTO\_FAILOVER value for channel '%s' to group replication members. Please retry the operation.  
[ER\\_GRP\\_RPL\\_FAILOVER\\_CHANNEL\\_STATUS\\_PROPAGATION](#) was added in 8.0.26.
  - Error number: 4051; Symbol: [ER\\_WARN\\_AUDIT\\_LOG\\_FORMAT\\_UNIX\\_TIMESTAMP\\_ONLY\\_WHEN\\_JSON](#); SQLSTATE: HY000  
Message: audit\_log\_format\_unix\_timestamp is applicable only when audit\_log\_format = JSON.  
[ER\\_WARN\\_AUDIT\\_LOG\\_FORMAT\\_UNIX\\_TIMESTAMP\\_ONLY\\_WHEN\\_JSON](#) was added in 8.0.26.

- 
- Error number: 4052; Symbol: [ER\\_INVALID\\_MFA\\_PLUGIN\\_SPECIFIED](#); SQLSTATE: HY000  
Message: Invalid plugin "%s" specified as %d factor during "%s".  
[ER\\_INVALID\\_MFA\\_PLUGIN\\_SPECIFIED](#) was added in 8.0.27.
  - Error number: 4053; Symbol: [ER\\_IDENTIFIED\\_BY\\_UNSUPPORTED](#); SQLSTATE: HY000  
Message: IDENTIFIED BY clause during "%s" not supported for plugin "%s".  
[ER\\_IDENTIFIED\\_BY\\_UNSUPPORTED](#) was added in 8.0.27.
  - Error number: 4054; Symbol: [ER\\_INVALID\\_PLUGIN\\_FOR\\_REGISTRATION](#); SQLSTATE: HY000  
Message: This operation is not supported for plugin "%s".  
[ER\\_INVALID\\_PLUGIN\\_FOR\\_REGISTRATION](#) was added in 8.0.27.
  - Error number: 4055; Symbol: [ER\\_PLUGIN\\_REQUIRES\\_REGISTRATION](#); SQLSTATE: HY000  
Message: Authentication plugin requires registration. Please refer ALTER USER syntax or set --fido-register-factor command line option to do registration.  
[ER\\_PLUGIN\\_REQUIRES\\_REGISTRATION](#) was added in 8.0.27.
  - Error number: 4056; Symbol: [ER\\_MFA\\_METHOD\\_EXISTS](#); SQLSTATE: HY000  
Message: %d factor authentication method exists. Please do ALTER USER... DROP %d factor before doing this operation OR do ALTER USER... MODIFY %d factor... to modify existing %d factor authentication method.  
[ER\\_MFA\\_METHOD\\_EXISTS](#) was added in 8.0.27.
  - Error number: 4057; Symbol: [ER\\_MFA\\_METHOD\\_NOT\\_EXISTS](#); SQLSTATE: HY000  
Message: %d factor authentication method doesn't exist. Please do ALTER USER... ADD %d factor... before doing this operation.  
[ER\\_MFA\\_METHOD\\_NOT\\_EXISTS](#) was added in 8.0.27.
  - Error number: 4058; Symbol: [ER\\_AUTHENTICATION\\_POLICY\\_MISMATCH](#); SQLSTATE: HY000  
Message: %d factor authentication method does not match against authentication policy. Please refer @@authentication\_policy system variable.  
[ER\\_AUTHENTICATION\\_POLICY\\_MISMATCH](#) was added in 8.0.27.
  - Error number: 4059; Symbol: [ER\\_PLUGIN\\_REGISTRATION\\_DONE](#); SQLSTATE: HY000  
Message: The registration for %d factor authentication method is already completed. You cannot perform registration multiple times.  
[ER\\_PLUGIN\\_REGISTRATION\\_DONE](#) was added in 8.0.27.

- 
- Error number: 4060; Symbol: `ER_INVALID_USER_FOR_REGISTRATION`; SQLSTATE: HY000

Message: The registration operation is not allowed for user '%s'@'%s'. The operation can only be performed in user's own session.

`ER_INVALID_USER_FOR_REGISTRATION` was added in 8.0.27.

- Error number: 4061; Symbol: `ER_USER_REGISTRATION_FAILED`; SQLSTATE: HY000

Message: Authentication plugin's registration failed.

`ER_USER_REGISTRATION_FAILED` was added in 8.0.27.

- Error number: 4062; Symbol: `ER_MFA_METHODS_INVALID_ORDER`; SQLSTATE: HY000

Message: %d factor authentication method should be added before %d factor authentication method.

`ER_MFA_METHODS_INVALID_ORDER` was added in 8.0.27.

- Error number: 4063; Symbol: `ER_MFA_METHODS_IDENTICAL`; SQLSTATE: HY000

Message: Authentication factor should be different.

`ER_MFA_METHODS_IDENTICAL` was added in 8.0.27.

- Error number: 4064; Symbol: `ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_USER`; SQLSTATE: HY000

Message: The operation "%s" cannot be performed for user '%s'@'%s' configured to connect without a password.

`ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_USER` was added in 8.0.27.

- Error number: 4065; Symbol: `ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID_ONLY`; SQLSTATE: HY000

Message: GTID\_ONLY cannot be enabled for replication channel '%s'. You need GTID\_MODE = ON, SOURCE\_AUTO\_POSITION = 1 and REQUIRE\_ROW\_FORMAT = 1.

`ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID_ONLY` was added in 8.0.27.

- Error number: 4066; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FORMAT_WITH_GTID_ONLY`; SQLSTATE: HY000

Message: REQUIRE\_ROW\_FORMAT cannot be disabled for replication channel '%s' when GTID\_ONLY=1.

`ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FORMAT_WITH_GTID_ONLY` was added in 8.0.27.

- 
- Error number: 4067; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITION_WITH_GTID_ONLY`; SQLSTATE: HY000  
Message: SOURCE\_AUTO\_POSITION cannot be disabled for replication channel '%s' when GTID\_ONLY=1.  
`ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITION_WITH_GTID_ONLY` was added in 8.0.27.
  - Error number: 4068; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITHOUT_POSITIONS`; SQLSTATE: HY000  
Message: When disabling GTID\_ONLY and SOURCE\_AUTO\_POSITION FOR CHANNEL '%s' you must provide SOURCE\_LOG\_FILE and SOURCE\_LOG\_POS as source positions are invalid.  
`ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITHOUT_POSITIONS` was added in 8.0.27.
  - Error number: 4069; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POS_WITHOUT_POSITIONS`; SQLSTATE: HY000  
Message: When disabling SOURCE\_AUTO\_POSITION FOR CHANNEL '%s' you must provide SOURCE\_LOG\_FILE and SOURCE\_LOG\_POS as source positions are invalid.  
`ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POS_WITHOUT_POSITIONS` was added in 8.0.27.
  - Error number: 4070; Symbol: `ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE_NOT_ON`; SQLSTATE: HY000  
Message: When configuring a group replication channel you must do it when GTID\_MODE = ON.  
`ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE_NOT_ON` was added in 8.0.27.
  - Error number: 4071; Symbol: `ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON`; SQLSTATE: HY000  
Message: Replication cannot start%s with GTID\_ONLY = 1 as this server uses @@GLOBAL.GTID\_MODE <> ON.  
`ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON` was added in 8.0.27.
  - Error number: 4072; Symbol: `ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_INVALID_POS`; SQLSTATE: HY000  
Message: The replication positions relative to the source may be out-of-date on channel '%s', due to the use of GTID\_ONLY=1. The out-of-date positions can still be used in some cases so, in order to update them, we suggest that you start the replication to receive and apply at least one transaction, which will set the positions to valid values.  
`ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_INVALID_POS` was added in 8.0.27.
  - Error number: 4073; Symbol: `ER_DA_SSL_FIPS_MODE_ERROR`; SQLSTATE: HY000  
Message: SSL fips mode error: %s  
`ER_DA_SSL_FIPS_MODE_ERROR` was added in 8.0.27.
  - Error number: 4074; Symbol: `ER_VALUE_OUT_OF_RANGE`; SQLSTATE: HY000
-

---

Message: %s=%llu is outside the valid range [%llu,%llu]. %llu will be used.

[ER\\_VALUE\\_OUT\\_OF\\_RANGE](#) was added in 8.0.27.

- Error number: 4075; Symbol: [ER\\_FULLTEXT\\_WITH\\_ROLLUP](#); SQLSTATE: HY000

Message: MATCH does not support ROLLUP columns.

[ER\\_FULLTEXT\\_WITH\\_ROLLUP](#) was added in 8.0.28.

- Error number: 4076; Symbol: [ER\\_REGEX\\_MISSING\\_RESOURCE](#); SQLSTATE: HY000

Message: Missing locale resource in regular expression library.

[ER\\_REGEX\\_MISSING\\_RESOURCE](#) was added in 8.0.28.

- Error number: 4077; Symbol: [ER\\_WARN\\_REGEX\\_USING\\_DEFAULT](#); SQLSTATE: HY000

Message: Regular expression library used default (root) locale.

[ER\\_WARN\\_REGEX\\_USING\\_DEFAULT](#) was added in 8.0.28.

- Error number: 4078; Symbol: [ER\\_REGEX\\_MISSING\\_FILE](#); SQLSTATE: HY000

Message: Missing data file in regular expression library.

[ER\\_REGEX\\_MISSING\\_FILE](#) was added in 8.0.28.

- Error number: 4079; Symbol: [ER\\_WARN\\_DEPRECATED\\_COLLATION](#); SQLSTATE: HY000

Message: '%s' is a collation of the deprecated character set %s. Please consider using %s with an appropriate collation instead.

[ER\\_WARN\\_DEPRECATED\\_COLLATION](#) was added in 8.0.28.

- Error number: 4080; Symbol: [ER\\_CONCURRENT\\_PROCEDURE\\_USAGE](#); SQLSTATE: HY000

Message: The %s was called when there was already another concurrent call to this procedure. No action was taken. Wait for other calls to %s to finish before retrying.

[ER\\_CONCURRENT\\_PROCEDURE\\_USAGE](#) was added in 8.0.28.

- Error number: 4081; Symbol: [ER\\_DA\\_GLOBAL\\_CONN\\_LIMIT](#); SQLSTATE: HY000

Message: Connection closed. Global connection memory limit %llu bytes exceeded. Consumed %llu bytes.

[ER\\_DA\\_GLOBAL\\_CONN\\_LIMIT](#) was added in 8.0.28.

- Error number: 4082; Symbol: [ER\\_DA\\_CONN\\_LIMIT](#); SQLSTATE: HY000

Message: Connection closed. Connection memory limit %llu bytes exceeded. Consumed %llu bytes.

[ER\\_DA\\_CONN\\_LIMIT](#) was added in 8.0.28.

- Error number: 4083; Symbol:

[ER\\_ALTER\\_OPERATION\\_NOT\\_SUPPORTED\\_REASON\\_COLUMN\\_TYPE\\_INSTANT](#); SQLSTATE: HY000

Message: Need to rebuild the table to change column type

---

[ER\\_ALTER\\_OPERATION\\_NOT\\_SUPPORTED\\_REASON\\_COLUMN\\_TYPE\\_INSTANT](#) was added in 8.0.28.

- Error number: 4084; Symbol: [ER\\_WARN\\_SF\\_UDF\\_NAME\\_COLLISION](#); SQLSTATE: HY000

Message: This function '%s' has the same name as a loadable function (UDF). To invoke the stored function, it is necessary to qualify it with the schema name.

[ER\\_WARN\\_SF\\_UDF\\_NAME\\_COLLISION](#) was added in 8.0.28.

- Error number: 4085; Symbol: [ER\\_CANNOT\\_PURGE\\_BINLOG\\_WITH\\_BACKUP\\_LOCK](#); SQLSTATE: HY000

Message: Could not purge binary logs since another session is executing LOCK INSTANCE FOR BACKUP. Wait for that session to release the lock.

[ER\\_CANNOT\\_PURGE\\_BINLOG\\_WITH\\_BACKUP\\_LOCK](#) was added in 8.0.28.

- Error number: 4086; Symbol: [ER\\_TOO\\_MANY\\_WINDOWS](#); SQLSTATE: HY000

Message: Too many windows in SELECT: %d. Maximum allowed is %d. Use named windows to share windows between window functions.

[ER\\_TOO\\_MANY\\_WINDOWS](#) was added in 8.0.28.

- Error number: 4087; Symbol: [ER\\_MYSQLBACKUP\\_CLIENT\\_MSG](#); SQLSTATE: HY000

Message: %s

[ER\\_MYSQLBACKUP\\_CLIENT\\_MSG](#) was added in 8.0.28.

- Error number: 4088; Symbol: [ER\\_COMMENT\\_CONTAINS\\_INVALID\\_STRING](#); SQLSTATE: HY000

Message: Comment for %s '%s' contains an invalid %s character string: '%s'.

[ER\\_COMMENT\\_CONTAINS\\_INVALID\\_STRING](#) was added in 8.0.28.

- Error number: 4089; Symbol: [ER\\_DEFINITION\\_CONTAINS\\_INVALID\\_STRING](#); SQLSTATE: HY000

Message: Definition of %s '%s.%s' contains an invalid %s character string: '%s'.

[ER\\_DEFINITION\\_CONTAINS\\_INVALID\\_STRING](#) was added in 8.0.28.

- Error number: 4090; Symbol: [ER\\_CANT\\_EXECUTE\\_COMMAND\\_WITH\\_ASSIGNED\\_GTID\\_NEXT](#); SQLSTATE: HY000

Message: Can't execute the given command when @@SESSION.GTID\_NEXT == 'UUID:NUMBER'.

[ER\\_CANT\\_EXECUTE\\_COMMAND\\_WITH\\_ASSIGNED\\_GTID\\_NEXT](#) was added in 8.0.28.

- Error number: 4091; Symbol: [ER\\_XA\\_TEMP\\_TABLE](#); SQLSTATE: HY000

Message: XA: Temporary tables cannot be accessed inside XA transactions when xa\_detach\_on\_prepare=ON

[ER\\_XA\\_TEMP\\_TABLE](#) was added in 8.0.29.

- Error number: 4092; Symbol: [ER\\_INNODB\\_MAX\\_ROW\\_VERSION](#); SQLSTATE: HY000

Message: Maximum row versions reached for table %s. No more columns can be added or dropped instantly. Please use COPY/INPLACE.

---

[ER\\_INNOQB\\_MAX\\_ROW\\_VERSION](#) was added in 8.0.29.

- Error number: 4093; Symbol: [ER\\_INNOQB\\_INSTANT\\_ADD\\_NOT\\_SUPPORTED\\_MAX\\_SIZE](#); SQLSTATE: HY000

Message: Column can't be added with ALGORITHM=INSTANT as after this max possible row size crosses max permissible row size. Try ALGORITHM=INPLACE/COPY.

[ER\\_INNOQB\\_INSTANT\\_ADD\\_NOT\\_SUPPORTED\\_MAX\\_SIZE](#) was added in 8.0.29, removed after 8.0.31.

- Error number: 4094; Symbol: [ER\\_OPERATION\\_NOT\\_ALLOWED\\_WHILE\\_PRIMARY\\_CHANGE\\_IS\\_RUNNING](#); SQLSTATE: HY000

Message: All queries have been blocked while function 'group\_replication\_set\_as\_primary()' is executing. Please refer timeout parameter of function 'group\_replication\_set\_as\_primary()'.

[ER\\_OPERATION\\_NOT\\_ALLOWED\\_WHILE\\_PRIMARY\\_CHANGE\\_IS\\_RUNNING](#) was added in 8.0.29.

- Error number: 4095; Symbol: [ER\\_WARN\\_DEPRECATED\\_DATETIME\\_DELIMITER](#); SQLSTATE: HY000

Message: Delimiter '%s' in position %d in datetime value '%s' at row %d is deprecated. Prefer the standard '%c'.

[ER\\_WARN\\_DEPRECATED\\_DATETIME\\_DELIMITER](#) was added in 8.0.29.

- Error number: 4096; Symbol: [ER\\_WARN\\_DEPRECATED\\_SUPERFLUOUS\\_DELIMITER](#); SQLSTATE: HY000

Message: Delimiter '%s' in position %d in datetime value '%s' at row %d is superfluous and is deprecated. Please remove.

[ER\\_WARN\\_DEPRECATED\\_SUPERFLUOUS\\_DELIMITER](#) was added in 8.0.29.

- Error number: 4097; Symbol: [ER\\_CANNOT\\_PERSIST\\_SENSITIVE\\_VARIABLES](#); SQLSTATE: HY000

Message: Cannot persist SENSITIVE system variable '%s' because keyring component support is unavailable.

[ER\\_CANNOT\\_PERSIST\\_SENSITIVE\\_VARIABLES](#) was added in 8.0.29.

- Error number: 4098; Symbol: [ER\\_WARN\\_CANNOT\\_SECURELY\\_PERSIST\\_SENSITIVE\\_VARIABLES](#); SQLSTATE: HY000

Message: SENSITIVE system variable '%s' was persisted without encryption. Consider restarting server with keyring component support to persist SENSITIVE variables securely.

[ER\\_WARN\\_CANNOT\\_SECURELY\\_PERSIST\\_SENSITIVE\\_VARIABLES](#) was added in 8.0.29.

- Error number: 4099; Symbol: [ER\\_WARN\\_TRG\\_ALREADY\\_EXISTS](#); SQLSTATE: HY000

Message: Trigger '%s' already exists on the table '%s'. '%s'.

[ER\\_WARN\\_TRG\\_ALREADY\\_EXISTS](#) was added in 8.0.29.



- 
- Error number: 4100; Symbol: `ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_DIFFERENT_TABLE`; SQLSTATE: HY000  
Message: Trigger '%s'. '%s' already exists on a different table. The 'IF NOT EXISTS' clause is only supported for triggers associated with the same table.  
`ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_DIFFERENT_TABLE` was added in 8.0.29.
  - Error number: 4101; Symbol: `ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FCT_NAME_COLLISION`; SQLSTATE: HY000  
Message: This function '%s' has the same name as a native function. The 'IF NOT EXISTS' clause is not supported while creating a loadable function with the same name as a native function.  
`ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FCT_NAME_COLLISION` was added in 8.0.29.
  - Error number: 4102; Symbol: `ER_SET_PASSWORD_AUTH_PLUGIN_ERROR`; SQLSTATE: HY000  
Message: SET PASSWORD has no significance for user '%s'@'%s' as the authentication method used doesn't store authentication data in the MySQL server. Please consider using ALTER USER instead if you want to change authentication parameters.  
`ER_SET_PASSWORD_AUTH_PLUGIN_ERROR` was added in 8.0.29.
  - Error number: 4105; Symbol: `ER_SRS_INVALID_LATITUDE_OF_ORIGIN`; SQLSTATE: SR002  
Message: Latitude of origin must be within [-90, 90] degrees, specified in the SRS angular unit.  
`ER_SRS_INVALID_LATITUDE_OF_ORIGIN` was added in 8.0.30.
  - Error number: 4106; Symbol: `ER_SRS_INVALID_LONGITUDE_OF_ORIGIN`; SQLSTATE: SR002  
Message: Longitude of origin must be within (-180, 180] degrees, specified in the SRS angular unit.  
`ER_SRS_INVALID_LONGITUDE_OF_ORIGIN` was added in 8.0.30.
  - Error number: 4107; Symbol: `ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT`; SQLSTATE: SR002  
Message: The spatial reference system definition for SRID %u contains unused projection parameter "%s".  
`ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT` was added in 8.0.30.
  - Error number: 4108; Symbol: `ER_GIPK_COLUMN_EXISTS`; SQLSTATE: HY000  
Message: Failed to generate invisible primary key. Column 'my\_row\_id' already exists.  
`ER_GIPK_COLUMN_EXISTS` was added in 8.0.30.
  - Error number: 4109; Symbol: `ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS`; SQLSTATE: HY000  
Message: Failed to generate invisible primary key. Auto-increment column already exists.  
`ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS` was added in 8.0.30.

- 
- Error number: 4110; Symbol: `ER_GIPK_COLUMN_ALTER_NOT_ALLOWED`; SQLSTATE: `HY000`  
Message: Altering generated invisible primary key column 'my\_row\_id' is not allowed.  
`ER_GIPK_COLUMN_ALTER_NOT_ALLOWED` was added in 8.0.30.
  - Error number: 4111; Symbol: `ER_DROP_PK_COLUMN_TO_DROP_GIPK`; SQLSTATE: `HY000`  
Message: Please drop primary key column to be able to drop generated invisible primary key.  
`ER_DROP_PK_COLUMN_TO_DROP_GIPK` was added in 8.0.30.
  - Error number: 4112; Symbol: `ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SBR`; SQLSTATE: `HY000`  
Message: Generating an invisible primary key for a table created using `CREATE TABLE ... SELECT ...` is disallowed when `binlog_format=STATEMENT`. It cannot be guaranteed that the `SELECT` retrieves rows in the same order on source and replica. Therefore, it cannot be guaranteed that the value generated for the generated implicit primary key column will be the same on source and replica for all rows. Use `binlog_format=ROW` or `MIXED` to execute this statement.  
`ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SBR` was added in 8.0.30.
  - Error number: 4113; Symbol: `ER_DA_EXPIRE_LOGS_DAYS_IGNORED`; SQLSTATE: `HY000`  
Message: The option `expire_logs_days` cannot be used together with option `binlog_expire_logs_seconds`. To set one, first unset the other by setting it to 0.  
`ER_DA_EXPIRE_LOGS_DAYS_IGNORED` was added in 8.0.30.
  - Error number: 4114; Symbol: `ER_CTE_RECURSIVE_NOT_UNION`; SQLSTATE: `HY000`  
Message: Recursive table reference in `EXCEPT` or `INTERSECT` operand is not allowed.  
`ER_CTE_RECURSIVE_NOT_UNION` was added in 8.0.31.
  - Error number: 4115; Symbol: `ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CTX`; SQLSTATE: `HY000`  
Message: Error when trying to fetch information from security context object, when trying to connect the server.  
`ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CTX` was added in 8.0.31.
  - Error number: 4116; Symbol: `ER_COMMAND_SERVICE_BACKEND_FAILED`; SQLSTATE: `HY000`  
Message: Error in command service backend interface, because of : "%s"  
`ER_COMMAND_SERVICE_BACKEND_FAILED` was added in 8.0.31.
  - Error number: 4117; Symbol: `ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS`; SQLSTATE: `HY000`  
Message: The `PRIVILEGE_CHECKS_USER` for channel '%s' would need `FILE` privilege to execute a `LOAD DATA INFILE` statement replicated in statement format. Consider using `binlog_format=ROW` on source. If the replicated events are trusted, recover from the failure by temporarily granting `FILE` to the `PRIVILEGE_CHECKS_USER`.  
`ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS` was added in 8.0.31.

- 
- Error number: 4118; Symbol: `ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILURE`; SQLSTATE: `HY000`  
  
Message: The 'SET GLOBAL group\_replication\_force\_members=%s' command encountered a failure. %s  
  
`ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILURE` was added in 8.0.31.
  - Error number: 4119; Symbol: `ER_WARN_DEPRECATED_IDENT`; SQLSTATE: `HY000`  
  
Message: Using %s as unquoted identifier is deprecated, please use quotes or rename the identifier.  
  
`ER_WARN_DEPRECATED_IDENT` was added in 8.0.31.
  - Error number: 4120; Symbol: `ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED`; SQLSTATE: `HY000`  
  
Message: Max number of duplicate rows in INTERSECT ALL exceeded.  
  
`ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED` was added in 8.0.31.
  - Error number: 4121; Symbol: `ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT`; SQLSTATE: `HY000`  
  
Message: Query threads count(%u) exceeds transaction threads limit(%u) per group. Please use query threads count per group smaller or equal to max transaction threads limit per group  
  
`ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT` was added in 8.0.31.
  - Error number: 4122; Symbol: `ER_BAD_TIMESTAMP_FORMAT`; SQLSTATE: `HY000`  
  
Message: Invalid timestamp format in %s udf  
  
`ER_BAD_TIMESTAMP_FORMAT` was added in 8.0.31.
  - Error number: 4123; Symbol: `ER_SHAPE_PREDICTION_UDF`; SQLSTATE: `HY000`  
  
Message: SHAPE\_PREDICTION UDF %s got error because of %s.  
  
`ER_SHAPE_PREDICTION_UDF` was added in 8.0.31.
  - Error number: 4124; Symbol: `ER_SRS_INVALID_HEIGHT`; SQLSTATE: `SR002`  
  
Message: Height parameter must be non negative.  
  
`ER_SRS_INVALID_HEIGHT` was added in 8.0.32.
  - Error number: 4125; Symbol: `ER_SRS_INVALID_SCALING`; SQLSTATE: `SR002`  
  
Message: Scaling parameter must be non negative.  
  
`ER_SRS_INVALID_SCALING` was added in 8.0.32.
  - Error number: 4126; Symbol: `ER_SRS_INVALID_ZONE_WIDTH`; SQLSTATE: `SR002`  
  
Message: Zone width parameter must be an integer between 1-60.  
  
`ER_SRS_INVALID_ZONE_WIDTH` was added in 8.0.32.

- 
- Error number: 4127; Symbol: [ER\\_SRS\\_INVALID\\_LATITUDE\\_POLAR\\_STERE\\_VAR\\_A](#); SQLSTATE: SR002  
Message: Latitude of origin must be +-90 degrees, specified in the SRS angular unit, in Polar Stereographic (variant A) projection method (EPSG:9810).  
[ER\\_SRS\\_INVALID\\_LATITUDE\\_POLAR\\_STERE\\_VAR\\_A](#) was added in 8.0.32.
  - Error number: 4128; Symbol: [ER\\_WARN\\_DEPRECATED\\_CLIENT\\_NO\\_SCHEMA\\_OPTION](#); SQLSTATE: HY000  
Message: The client is using a deprecated CLIENT\_NO\_SCHEMA client option. CLIENT\_NO\_SCHEMA will be removed in a future release.  
[ER\\_WARN\\_DEPRECATED\\_CLIENT\\_NO\\_SCHEMA\\_OPTION](#) was added in 8.0.32.
  - Error number: 4129; Symbol: [ER\\_TABLE\\_NOT\\_EMPTY](#); SQLSTATE: HY000  
Message: Table '%s' is not empty.  
[ER\\_TABLE\\_NOT\\_EMPTY](#) was added in 8.0.32.
  - Error number: 4130; Symbol: [ER\\_TABLE\\_NO\\_PRIMARY\\_KEY](#); SQLSTATE: HY000  
Message: Table '%s' has no primary key.  
[ER\\_TABLE\\_NO\\_PRIMARY\\_KEY](#) was added in 8.0.32.
  - Error number: 4131; Symbol: [ER\\_TABLE\\_IN\\_SHARED\\_TABLESPACE](#); SQLSTATE: HY000  
Message: Table '%s' is in a shared tablespace.  
[ER\\_TABLE\\_IN\\_SHARED\\_TABLESPACE](#) was added in 8.0.32.
  - Error number: 4132; Symbol: [ER\\_INDEX\\_OTHER\\_THAN\\_PK](#); SQLSTATE: HY000  
Message: Table '%s' has indexes other than primary key.  
[ER\\_INDEX\\_OTHER\\_THAN\\_PK](#) was added in 8.0.32.
  - Error number: 4133; Symbol: [ER\\_LOAD\\_BULK\\_DATA\\_UNSORTED](#); SQLSTATE: HY000  
Message: [IN PRIMARY KEY ORDER] specified but data not sorted: LOAD BULK DATA into table '%s' failed: %s  
[ER\\_LOAD\\_BULK\\_DATA\\_UNSORTED](#) was added in 8.0.32.
  - Error number: 4134; Symbol: [ER\\_BULK\\_EXECUTOR\\_ERROR](#); SQLSTATE: HY000  
Message: Bulk executor error: %s  
[ER\\_BULK\\_EXECUTOR\\_ERROR](#) was added in 8.0.32.
  - Error number: 4135; Symbol: [ER\\_BULK\\_READER\\_LIBCURL\\_INIT\\_FAILED](#); SQLSTATE: HY000  
Message: Bulk reader failed to initialize libcurl  
[ER\\_BULK\\_READER\\_LIBCURL\\_INIT\\_FAILED](#) was added in 8.0.32.
  - Error number: 4136; Symbol: [ER\\_BULK\\_READER\\_LIBCURL\\_ERROR](#); SQLSTATE: HY000

---

Message: Bulk reader got libcurl error: %s

[ER\\_BULK\\_READER\\_LIBCURL\\_ERROR](#) was added in 8.0.32.

- Error number: 4137; Symbol: [ER\\_BULK\\_READER\\_SERVER\\_ERROR](#); SQLSTATE: HY000

Message: Bulk reader got error response from server: %ld

[ER\\_BULK\\_READER\\_SERVER\\_ERROR](#) was added in 8.0.32.

- Error number: 4138; Symbol: [ER\\_BULK\\_READER\\_COMMUNICATION\\_ERROR](#); SQLSTATE: HY000

Message: Bulk reader got error in communication with source server, check the error log for additional details.

[ER\\_BULK\\_READER\\_COMMUNICATION\\_ERROR](#) was added in 8.0.32.

- Error number: 4139; Symbol: [ER\\_BULK\\_LOAD\\_DATA\\_FAILED](#); SQLSTATE: HY000

Message: Bulk loader failed, mysql\_load->load returned an error, check the error log for additional details.

[ER\\_BULK\\_LOAD\\_DATA\\_FAILED](#) was added in 8.0.32.

- Error number: 4140; Symbol: [ER\\_BULK\\_LOADER\\_COLUMN\\_TOO\\_BIG\\_FOR\\_LEFTOVER\\_BUFFER](#); SQLSTATE: HY000

Message: CSV column too big for leftover buffer.

[ER\\_BULK\\_LOADER\\_COLUMN\\_TOO\\_BIG\\_FOR\\_LEFTOVER\\_BUFFER](#) was added in 8.0.32.

- Error number: 4141; Symbol: [ER\\_BULK\\_LOADER\\_COMPONENT\\_ERROR](#); SQLSTATE: HY000

Message: Bulk loader component error: %s

[ER\\_BULK\\_LOADER\\_COMPONENT\\_ERROR](#) was added in 8.0.32.

- Error number: 4142; Symbol: [ER\\_BULK\\_LOADER\\_FILE\\_CONTAINS\\_LESS\\_LINES\\_THAN\\_IGNORE\\_CLAUSE](#); SQLSTATE: HY000

Message: The first file being loaded contained less lines than the ignore clause

[ER\\_BULK\\_LOADER\\_FILE\\_CONTAINS\\_LESS\\_LINES\\_THAN\\_IGNORE\\_CLAUSE](#) was added in 8.0.32.

- Error number: 4143; Symbol: [ER\\_BULK\\_PARSER\\_MISSING\\_ENCLOSED\\_BY](#); SQLSTATE: HY000

Message: Missing ENCLOSED BY character at row %ld in file '%s'. Add OPTIONALLY to the ENCLOSED BY clause to allow this input.

[ER\\_BULK\\_PARSER\\_MISSING\\_ENCLOSED\\_BY](#) was added in 8.0.32.

- Error number: 4144; Symbol: [ER\\_BULK\\_PARSER\\_ROW\\_BUFFER\\_MAX\\_TOTAL\\_COLS\\_EXCEEDED](#); SQLSTATE: HY000

Message: The number of input columns that need to be buffered for parsing exceeded predefined buffer max size for file '%s'.

[ER\\_BULK\\_PARSER\\_ROW\\_BUFFER\\_MAX\\_TOTAL\\_COLS\\_EXCEEDED](#) was added in 8.0.32.

- 
- Error number: 4145; Symbol: `ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED`; SQLSTATE: HY000  
Message: The column data that needed to be copied due to escaped characters exceeded the size of the internal copy buffer for file '%s'.  
`ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED` was added in 8.0.32.
  - Error number: 4146; Symbol: `ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT`; SQLSTATE: HY000  
Message: Unexpected end of input found at row %ld in file '%s'. Data for some columns is missing.  
`ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT` was added in 8.0.32.
  - Error number: 4147; Symbol: `ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR`; SQLSTATE: HY000  
Message: Unexpected row terminator found at row %ld in file '%s'. Data for some columns is missing.  
`ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR` was added in 8.0.32.
  - Error number: 4148; Symbol: `ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_ENCLOSED_BY`; SQLSTATE: HY000  
Message: Unexpected characters after ending ENCLOSED BY character found at row %ld in file '%s'.  
`ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_ENCLOSED_BY` was added in 8.0.32.
  - Error number: 4149; Symbol: `ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE`; SQLSTATE: HY000  
Message: Unexpected characters after NULL escape (N) found at row %ld in file '%s'.  
`ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE` was added in 8.0.32.
  - Error number: 4150; Symbol: `ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR`; SQLSTATE: HY000  
Message: Unexpected characters after column terminator found at row %ld in file '%s'.  
`ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR` was added in 8.0.32.
  - Error number: 4151; Symbol: `ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE`; SQLSTATE: HY000  
Message: Unexpected end of input found at row %ld in file '%s' resulting in incomplete escape sequence.  
`ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE` was added in 8.0.32.
  - Error number: 4152; Symbol: `ER_LOAD_BULK_DATA_FAILED`; SQLSTATE: HY000  
Message: LOAD BULK DATA into table '%s' failed: %s  
`ER_LOAD_BULK_DATA_FAILED` was added in 8.0.32.
  - Error number: 4153; Symbol: `ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD`; SQLSTATE: HY000  
Message: Incorrect %s value: '%s' for column '%s' at row %ld in file '%s'

---

`ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD` was added in 8.0.32.

- Error number: 4154; Symbol: `ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL`; SQLSTATE: HY000

Message: NULL supplied to NOT NULL column '%s' at row %ld in file '%s'

`ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL` was added in 8.0.32.

- Error number: 4155; Symbol: `ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WITH_GR`; SQLSTATE: HY000

Message: On a Group Replication channel, setting `REQUIRE_TABLE_PRIMARY_KEY_CHECK` to 'GENERATE' is not allowed.

`ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WITH_GR` was added in 8.0.32.

- Error number: 4156; Symbol: `ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE`; SQLSTATE: HY000

Message: Cannot change the '%s' system variable in read-only mode.

`ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE` was added in 8.0.32.

- Error number: 4157; Symbol: `ER_INNOODB_INSTANT_ADD_DROP_NOT_SUPPORTEDED_MAX_SIZE`; SQLSTATE: HY000

Message: Column can't be added or dropped with `ALGORITHM=INSTANT` as either max possible row size already crosses max permissible row size or may cross it after add. Try `ALGORITHM=INPLACE/COPY`.

`ER_INNOODB_INSTANT_ADD_DROP_NOT_SUPPORTEDED_MAX_SIZE` was added in 8.0.32.

- Error number: 4158; Symbol: `ER_INNOODB_INSTANT_ADD_NOT_SUPPORTEDED_MAX_FIELDS`; SQLSTATE: HY000

Message: Column can't be added to '%s' with `ALGORITHM=INSTANT` anymore. Please try `ALGORITHM=INPLACE/COPY`.

`ER_INNOODB_INSTANT_ADD_NOT_SUPPORTEDED_MAX_FIELDS` was added in 8.0.32.

- Error number: 4159; Symbol: `ER_CANT_SET_PERSISTED`; SQLSTATE: HY000

Message: Failed to set persisted options.

`ER_CANT_SET_PERSISTED` was added in 8.0.2.

- Error number: 4160; Symbol: `ER_INSTALL_COMPONENT_SET_NULL_VALUE`; SQLSTATE: HY000

Message: The value supplied for %s in the SET list cannot be null

`ER_INSTALL_COMPONENT_SET_NULL_VALUE` was added in 8.0.33.

- Error number: 4161; Symbol: `ER_INSTALL_COMPONENT_SET_UNUSED_VALUE`; SQLSTATE: HY000

Message: The assignment of %s in SET doesn't match any of the variables registered by the component(s)

`ER_INSTALL_COMPONENT_SET_UNUSED_VALUE` was added in 8.0.33.

- 
- Error number: 4162; Symbol: [ER\\_WARN\\_DEPRECATED\\_USER\\_DEFINED\\_COLLATIONS](#); SQLSTATE: HY000  
Message: '%s' is a user defined collation. User defined collations are deprecated and will be removed in a future release. Consider using a compiled collation instead.  
[ER\\_WARN\\_DEPRECATED\\_USER\\_DEFINED\\_COLLATIONS](#) was added in 8.0.33.
  - Error number: 4163; Symbol: [ER\\_USER\\_LOCK\\_OVERLONG\\_NAME](#); SQLSTATE: 42000  
Message: User-level lock name '%s' should not exceed %d characters.  
[ER\\_USER\\_LOCK\\_OVERLONG\\_NAME](#) was added in 8.0.34.
  - Error number: 4164; Symbol: [ER\\_WARN\\_NO\\_SPACE\\_VERSION\\_COMMENT](#); SQLSTATE: HY000  
Message: Immediately starting the version comment after the version number is deprecated and may change behavior in a future release. Please insert a white-space character after the version number.  
[ER\\_WARN\\_NO\\_SPACE\\_VERSION\\_COMMENT](#) was added in 8.0.34.
  - Error number: 4165; Symbol: [ER\\_VALIDATE\\_PASSWORD\\_INSUFFICIENT\\_CHANGED\\_CHARACTERS](#); SQLSTATE: HY000  
Message: The new password must have at least '%u' characters that are different from the old password. It has only '%u' character(s) different. For this comparison, uppercase letters and lowercase letters are considered to be equal.  
[ER\\_VALIDATE\\_PASSWORD\\_INSUFFICIENT\\_CHANGED\\_CHARACTERS](#) was added in 8.0.34.
  - Error number: 4166; Symbol: [ER\\_WARN\\_DEPRECATED\\_WITH\\_NOTE](#); SQLSTATE: HY000  
Message: '%s' is deprecated and will be removed in a future release. %s  
[ER\\_WARN\\_DEPRECATED\\_WITH\\_NOTE](#) was added in 8.0.35.
  - Error number: MY-010000; Symbol: [ER\\_PARSER\\_TRACE](#); SQLSTATE: XX999  
Message: Parser saw: %s  
[ER\\_PARSER\\_TRACE](#) was added in 8.0.2.
  - Error number: MY-010001; Symbol: [ER\\_BOOTSTRAP\\_CANT\\_THREAD](#); SQLSTATE: HY000  
Message: Can't create thread to handle bootstrap (errno: %d)  
[ER\\_BOOTSTRAP\\_CANT\\_THREAD](#) was added in 8.0.2.
  - Error number: MY-010002; Symbol: [ER\\_TRIGGER\\_INVALID\\_VALUE](#); SQLSTATE: HY000  
Message: Trigger for table '%s'. '%s': invalid %s value (%s).  
[ER\\_TRIGGER\\_INVALID\\_VALUE](#) was added in 8.0.2.
  - Error number: MY-010003; Symbol: [ER\\_OPT\\_WRONG\\_TREE](#); SQLSTATE: HY000  
Message: Wrong tree: %s  
[ER\\_OPT\\_WRONG\\_TREE](#) was added in 8.0.2.



- 
- Error number: [MY-010004](#); Symbol: [ER\\_DD\\_FAILSAFE](#); SQLSTATE: [HY000](#)  
Message: Error: Invalid %s  
[ER\\_DD\\_FAILSAFE](#) was added in 8.0.2.
  - Error number: [MY-010005](#); Symbol: [ER\\_DD\\_NO\\_WRITES\\_NO\\_REPOPULATION](#); SQLSTATE: [HY000](#)  
Message: Skip re-populating collations and character sets tables in %s%read-only mode.  
[ER\\_DD\\_NO\\_WRITES\\_NO\\_REPOPULATION](#) was added in 8.0.2.
  - Error number: [MY-010006](#); Symbol: [ER\\_DD\\_VERSION\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: Using data dictionary with version '%d'.  
[ER\\_DD\\_VERSION\\_FOUND](#) was added in 8.0.2.
  - Error number: [MY-010007](#); Symbol: [ER\\_DD\\_VERSION\\_INSTALLED](#); SQLSTATE: [HY000](#)  
Message: Installed data dictionary with version %d  
[ER\\_DD\\_VERSION\\_INSTALLED](#) was added in 8.0.2.
  - Error number: [MY-010008](#); Symbol: [ER\\_DD\\_VERSION\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)  
Message: Data Dictionary version '%d' not supported.  
[ER\\_DD\\_VERSION\\_UNSUPPORTED](#) was added in 8.0.2.
  - Error number: [MY-010009](#); Symbol: [ER\\_LOG\\_SYSLOG\\_FACILITY\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed to set syslog facility to "%s", setting to "%s" (%d) instead.  
[ER\\_LOG\\_SYSLOG\\_FACILITY\\_FAIL](#) was added in 8.0.2, removed after 8.0.12.
  - Error number: [MY-010010](#); Symbol: [ER\\_LOG\\_SYSLOG\\_CANNOT\\_OPEN](#); SQLSTATE: [HY000](#)  
Message: Cannot open %s; check privileges, or remove syseventlog from --log-error-services!  
[ER\\_LOG\\_SYSLOG\\_CANNOT\\_OPEN](#) was added in 8.0.2.
  - Error number: [MY-010011](#); Symbol: [ER\\_LOG\\_SLOW\\_CANNOT\\_OPEN](#); SQLSTATE: [HY000](#)  
Message: either restart the query logging by using "SET GLOBAL SLOW\_QUERY\_LOG=ON" or  
[ER\\_LOG\\_SLOW\\_CANNOT\\_OPEN](#) was added in 8.0.2.
  - Error number: [MY-010012](#); Symbol: [ER\\_LOG\\_GENERAL\\_CANNOT\\_OPEN](#); SQLSTATE: [HY000](#)  
Message: either restart the query logging by using "SET GLOBAL GENERAL\_LOG=ON" or  
[ER\\_LOG\\_GENERAL\\_CANNOT\\_OPEN](#) was added in 8.0.2.
  - Error number: [MY-010013](#); Symbol: [ER\\_LOG\\_CANNOT\\_WRITE](#); SQLSTATE: [HY000](#)  
Message: Failed to write to %s: %s  
[ER\\_LOG\\_CANNOT\\_WRITE](#) was added in 8.0.2.

- 
- Error number: `MY-010014`; Symbol: `ER_RPL_ZOMBIE_ENCOUNTERED`; SQLSTATE: `HY000`  
Message: While initializing dump thread for replica with %s <%s>, found a zombie dump thread with the same %s. Source is killing the zombie dump thread(%u).  
`ER_RPL_ZOMBIE_ENCOUNTERED` was added in 8.0.2, removed after 8.0.40.
  - Error number: `MY-010015`; Symbol: `ER_RPL_GTID_TABLE_CANNOT_OPEN`; SQLSTATE: `HY000`  
Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.  
`ER_RPL_GTID_TABLE_CANNOT_OPEN` was added in 8.0.2.
  - Error number: `MY-010016`; Symbol: `ER_SYSTEM_SCHEMA_NOT_FOUND`; SQLSTATE: `HY000`  
Message: System schema directory does not exist.  
`ER_SYSTEM_SCHEMA_NOT_FOUND` was added in 8.0.2.
  - Error number: `MY-010017`; Symbol: `ER_DD_INIT_UPGRADE_FAILED`; SQLSTATE: `HY000`  
Message: Error in initializing dictionary, upgrade will do a cleanup and exit  
`ER_DD_INIT_UPGRADE_FAILED` was added in 8.0.2.
  - Error number: `MY-010018`; Symbol: `ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION`; SQLSTATE: `HY000`  
Message: View '%s'. '%s': unknown charset name and/or collation name (client: '%s'; connection: '%s').  
`ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION` was added in 8.0.2.
  - Error number: `MY-010019`; Symbol: `ER_DD_VIEW_CANT_ALLOC_CHARSET`; SQLSTATE: `HY000`  
Message: Error in allocating memory for character set name for view %s.%s.  
`ER_DD_VIEW_CANT_ALLOC_CHARSET` was added in 8.0.2.
  - Error number: `MY-010020`; Symbol: `ER_DD_INIT_FAILED`; SQLSTATE: `HY000`  
Message: Data Dictionary initialization failed.  
`ER_DD_INIT_FAILED` was added in 8.0.2.
  - Error number: `MY-010021`; Symbol: `ER_DD_UPDATING_PLUGIN_MD_FAILED`; SQLSTATE: `HY000`  
Message: Failed to update plugin metadata in dictionary tables.  
`ER_DD_UPDATING_PLUGIN_MD_FAILED` was added in 8.0.2.
  - Error number: `MY-010022`; Symbol: `ER_DD_POPULATING_TABLES_FAILED`; SQLSTATE: `HY000`  
Message: Failed to Populate DD tables.  
`ER_DD_POPULATING_TABLES_FAILED` was added in 8.0.2.
  - Error number: `MY-010023`; Symbol: `ER_DD_VIEW_CANT_CREATE`; SQLSTATE: `HY000`  
Message: Error in Creating View %s.%s

---

`ER_DD_VIEW_CANT_CREATE` was added in 8.0.2.

- Error number: `MY-010024`; Symbol: `ER_DD_METADATA_NOT_FOUND`; SQLSTATE: `HY000`

Message: Unable to start server. Cannot find the meta data for data dictionary table '%s'.

`ER_DD_METADATA_NOT_FOUND` was added in 8.0.2.

- Error number: `MY-010025`; Symbol: `ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN`; SQLSTATE: `HY000`

Message: Dictionary cache not empty at shutdown.

`ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN` was added in 8.0.2.

- Error number: `MY-010026`; Symbol: `ER_DD_OBJECT_REMAINS`; SQLSTATE: `HY000`

Message: Dictionary objects used but not released.

`ER_DD_OBJECT_REMAINS` was added in 8.0.2.

- Error number: `MY-010027`; Symbol: `ER_DD_OBJECT_REMAINS_IN_RELEASER`; SQLSTATE: `HY000`

Message: Dictionary objects left in default releaser.

`ER_DD_OBJECT_REMAINS_IN_RELEASER` was added in 8.0.2.

- Error number: `MY-010028`; Symbol: `ER_DD_OBJECT_RELEASER_REMAINS`; SQLSTATE: `HY000`

Message: Dictionary object auto releaser not deleted

`ER_DD_OBJECT_RELEASER_REMAINS` was added in 8.0.2.

- Error number: `MY-010029`; Symbol: `ER_DD_CANT_GET_OBJECT_KEY`; SQLSTATE: `HY000`

Message: Error: Unable to create primary object key

`ER_DD_CANT_GET_OBJECT_KEY` was added in 8.0.2.

- Error number: `MY-010030`; Symbol: `ER_DD_CANT_CREATE_OBJECT_KEY`; SQLSTATE: `HY000`

Message: Error: Unable to create object key

`ER_DD_CANT_CREATE_OBJECT_KEY` was added in 8.0.2.

- Error number: `MY-010031`; Symbol: `ER_CANT_CREATE_HANDLE_MGR_THREAD`; SQLSTATE: `HY000`

Message: Can't create handle\_manager thread (errno= %d)

`ER_CANT_CREATE_HANDLE_MGR_THREAD` was added in 8.0.2.

- Error number: `MY-010032`; Symbol: `ER_RPL_REPO_HAS_GAPS`; SQLSTATE: `HY000`

Message: It is not possible to change the type of the relay log's repository because there are workers' repositories with gaps. Please, fix the gaps first before doing such change.

`ER_RPL_REPO_HAS_GAPS` was added in 8.0.2.

- Error number: `MY-010033`; Symbol: `ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY`; SQLSTATE: `HY000`

---

Message: option 'enforce-gtid-consistency': value '%s' was not recognized. Setting enforce-gtid-consistency to OFF.

[ER\\_INVALID\\_VALUE\\_FOR\\_ENFORCE\\_GTID\\_CONSISTENCY](#) was added in 8.0.2.

- Error number: [MY-010034](#); Symbol: [ER\\_CHANGED\\_ENFORCE\\_GTID\\_CONSISTENCY](#); SQLSTATE: [HY000](#)

Message: Changed ENFORCE\_GTID\_CONSISTENCY from %s to %s.

[ER\\_CHANGED\\_ENFORCE\\_GTID\\_CONSISTENCY](#) was added in 8.0.2.

- Error number: [MY-010035](#); Symbol: [ER\\_CHANGED\\_GTID\\_MODE](#); SQLSTATE: [HY000](#)

Message: Changed GTID\_MODE from %s to %s.

[ER\\_CHANGED\\_GTID\\_MODE](#) was added in 8.0.2.

- Error number: [MY-010036](#); Symbol: [ER\\_DISABLED\\_STORAGE\\_ENGINE\\_AS\\_DEFAULT](#); SQLSTATE: [HY000](#)

Message: %s is set to a disabled storage engine %s.

[ER\\_DISABLED\\_STORAGE\\_ENGINE\\_AS\\_DEFAULT](#) was added in 8.0.2.

- Error number: [MY-010037](#); Symbol: [ER\\_DEBUG\\_SYNC\\_HIT](#); SQLSTATE: [HY000](#)

Message: Debug sync points hit: %s

[ER\\_DEBUG\\_SYNC\\_HIT](#) was added in 8.0.2.

- Error number: [MY-010038](#); Symbol: [ER\\_DEBUG\\_SYNC\\_EXECUTED](#); SQLSTATE: [HY000](#)

Message: Debug sync points executed: %s

[ER\\_DEBUG\\_SYNC\\_EXECUTED](#) was added in 8.0.2.

- Error number: [MY-010039](#); Symbol: [ER\\_DEBUG\\_SYNC\\_THREAD\\_MAX](#); SQLSTATE: [HY000](#)

Message: Debug sync points max active per thread: %s

[ER\\_DEBUG\\_SYNC\\_THREAD\\_MAX](#) was added in 8.0.2.

- Error number: [MY-010040](#); Symbol: [ER\\_DEBUG\\_SYNC\\_OOM](#); SQLSTATE: [HY000](#)

Message: Debug Sync Facility disabled due to lack of memory.

[ER\\_DEBUG\\_SYNC\\_OOM](#) was added in 8.0.2.

- Error number: [MY-010041](#); Symbol: [ER\\_CANT\\_INIT\\_TC\\_LOG](#); SQLSTATE: [HY000](#)

Message: Can't init tc log

[ER\\_CANT\\_INIT\\_TC\\_LOG](#) was added in 8.0.2.

- Error number: [MY-010042](#); Symbol: [ER\\_EVENT\\_CANT\\_INIT\\_QUEUE](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Can't initialize the execution queue

---

`ER_EVENT_CANT_INIT_QUEUE` was added in 8.0.2.

- Error number: `MY-010043`; Symbol: `ER_EVENT_PURGING_QUEUE`; SQLSTATE: `HY000`

Message: Event Scheduler: Purging the queue. %u events

`ER_EVENT_PURGING_QUEUE` was added in 8.0.2.

- Error number: `MY-010044`; Symbol: `ER_EVENT_LAST_EXECUTION`; SQLSTATE: `HY000`

Message: Event Scheduler: Last execution of %s.%s. %s

`ER_EVENT_LAST_EXECUTION` was added in 8.0.2.

- Error number: `MY-010045`; Symbol: `ER_EVENT_MESSAGE_STACK`; SQLSTATE: `HY000`

Message: %\*s

`ER_EVENT_MESSAGE_STACK` was added in 8.0.2.

- Error number: `MY-010046`; Symbol: `ER_EVENT_EXECUTION_FAILED`; SQLSTATE: `HY000`

Message: Event Scheduler: [%s].[%s.%s] event execution failed.

`ER_EVENT_EXECUTION_FAILED` was added in 8.0.2.

- Error number: `MY-010047`; Symbol: `ER_CANT_INIT_SCHEDULER_THREAD`; SQLSTATE: `HY000`

Message: Event Scheduler: Cannot initialize the scheduler thread

`ER_CANT_INIT_SCHEDULER_THREAD` was added in 8.0.2.

- Error number: `MY-010048`; Symbol: `ER_SCHEDULER_STOPPED`; SQLSTATE: `HY000`

Message: Event Scheduler: Stopped

`ER_SCHEDULER_STOPPED` was added in 8.0.2.

- Error number: `MY-010049`; Symbol: `ER_CANT_CREATE_SCHEDULER_THREAD`; SQLSTATE: `HY000`

Message: Event scheduler: Failed to start scheduler, Can not create thread for event scheduler (errno=%d)

`ER_CANT_CREATE_SCHEDULER_THREAD` was added in 8.0.2.

- Error number: `MY-010050`; Symbol: `ER_SCHEDULER_WAITING`; SQLSTATE: `HY000`

Message: Event Scheduler: Waiting for the scheduler thread to reply

`ER_SCHEDULER_WAITING` was added in 8.0.2.

- Error number: `MY-010051`; Symbol: `ER_SCHEDULER_STARTED`; SQLSTATE: `HY000`

Message: Event Scheduler: scheduler thread started with id %u

`ER_SCHEDULER_STARTED` was added in 8.0.2.

- Error number: `MY-010052`; Symbol: `ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT`; SQLSTATE: `HY000`

---

Message: Event Scheduler: Serious error during getting next event to execute. Stopping

[ER\\_SCHEDULER\\_STOPPING\\_FAILED\\_TO\\_GET\\_EVENT](#) was added in 8.0.2.

- Error number: [MY-010053](#); Symbol: [ER\\_SCHEDULER\\_STOPPING\\_FAILED\\_TO\\_CREATE\\_WORKER](#); SQLSTATE: [HY000](#)

Message: Event\_scheduler::execute\_top: Can not create event worker thread (errno=%d). Stopping event scheduler

[ER\\_SCHEDULER\\_STOPPING\\_FAILED\\_TO\\_CREATE\\_WORKER](#) was added in 8.0.2.

- Error number: [MY-010054](#); Symbol: [ER\\_SCHEDULER\\_KILLING](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Killing the scheduler thread, thread id %u

[ER\\_SCHEDULER\\_KILLING](#) was added in 8.0.2.

- Error number: [MY-010055](#); Symbol: [ER\\_UNABLE\\_TO\\_RESOLVE\\_IP](#); SQLSTATE: [HY000](#)

Message: IP address '%s' could not be resolved: %s

[ER\\_UNABLE\\_TO\\_RESOLVE\\_IP](#) was added in 8.0.2.

- Error number: [MY-010056](#); Symbol: [ER\\_UNABLE\\_TO\\_RESOLVE\\_HOSTNAME](#); SQLSTATE: [HY000](#)

Message: Host name '%s' could not be resolved: %s

[ER\\_UNABLE\\_TO\\_RESOLVE\\_HOSTNAME](#) was added in 8.0.2.

- Error number: [MY-010057](#); Symbol: [ER\\_HOSTNAME\\_RESEMBLES\\_IPV4](#); SQLSTATE: [HY000](#)

Message: IP address '%s' has been resolved to the host name '%s', which resembles IPv4-address itself.

[ER\\_HOSTNAME\\_RESEMBLES\\_IPV4](#) was added in 8.0.2.

- Error number: [MY-010058](#); Symbol: [ER\\_HOSTNAME\\_DOESNT\\_RESOLVE\\_TO](#); SQLSTATE: [HY000](#)

Message: Hostname '%s' does not resolve to '%s'.

[ER\\_HOSTNAME\\_DOESNT\\_RESOLVE\\_TO](#) was added in 8.0.2.

- Error number: [MY-010059](#); Symbol: [ER\\_ADDRESSES\\_FOR\\_HOSTNAME\\_HEADER](#); SQLSTATE: [HY000](#)

Message: Hostname '%s' has the following IP addresses:

[ER\\_ADDRESSES\\_FOR\\_HOSTNAME\\_HEADER](#) was added in 8.0.2.

- Error number: [MY-010060](#); Symbol: [ER\\_ADDRESSES\\_FOR\\_HOSTNAME\\_LIST\\_ITEM](#); SQLSTATE: [HY000](#)

Message: - %s

[ER\\_ADDRESSES\\_FOR\\_HOSTNAME\\_LIST\\_ITEM](#) was added in 8.0.2.

- Error number: [MY-010061](#); Symbol: [ER\\_TRG\\_WITHOUT\\_DEFINER](#); SQLSTATE: [HY000](#)

Message: Definer clause is missing in Trigger of Table %s. Rebuild Trigger to fix definer.

---

`ER_TRG_WITHOUT_DEFINER` was added in 8.0.2.

- Error number: `MY-010062`; Symbol: `ER_TRG_NO_CLIENT_CHARSET`; SQLSTATE: `HY000`  
Message: Client character set is missing for trigger of table %s. Using default character set.

`ER_TRG_NO_CLIENT_CHARSET` was added in 8.0.2.

- Error number: `MY-010063`; Symbol: `ER_PARSING_VIEW`; SQLSTATE: `HY000`  
Message: Error in parsing view %s.%s

`ER_PARSING_VIEW` was added in 8.0.2.

- Error number: `MY-010064`; Symbol: `ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP`; SQLSTATE: `HY000`

Message: Failed to bootstrap components infrastructure.

`ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP` was added in 8.0.2.

- Error number: `MY-010065`; Symbol: `ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN`; SQLSTATE: `HY000`

Message: Failed to shutdown components infrastructure.

`ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN` was added in 8.0.2.

- Error number: `MY-010066`; Symbol: `ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP`; SQLSTATE: `HY000`

Message: Failed to bootstrap persistent components loader.

`ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP` was added in 8.0.2.

- Error number: `MY-010067`; Symbol: `ER_DEPART_WITH_GRACE`; SQLSTATE: `HY000`

Message: Giving %d client threads a chance to die gracefully

`ER_DEPART_WITH_GRACE` was added in 8.0.2.

- Error number: `MY-010068`; Symbol: `ER_CA_SELF_SIGNED`; SQLSTATE: `HY000`

Message: CA certificate %s is self signed.

`ER_CA_SELF_SIGNED` was added in 8.0.2.

- Error number: `MY-010069`; Symbol: `ER_SSL_LIBRARY_ERROR`; SQLSTATE: `HY000`

Message: Failed to set up SSL because of the following SSL library error: %s

`ER_SSL_LIBRARY_ERROR` was added in 8.0.2.

- Error number: `MY-010070`; Symbol: `ER_NO_THD_NO_UUID`; SQLSTATE: `HY000`

Message: Failed to generate a server UUID because it is failed to allocate the THD.

`ER_NO_THD_NO_UUID` was added in 8.0.2.

- 
- Error number: `MY-010071`; Symbol: `ER_UUID_SALT`; SQLSTATE: `HY000`  
Message: Salting uuid generator variables, current\_pid: %lu, server\_start\_time: %lu, bytes\_sent: %llu,  
`ER_UUID_SALT` was added in 8.0.2.
  - Error number: `MY-010072`; Symbol: `ER_UUID_IS`; SQLSTATE: `HY000`  
Message: Generated uuid: '%s', server\_start\_time: %lu, bytes\_sent: %llu  
`ER_UUID_IS` was added in 8.0.2.
  - Error number: `MY-010073`; Symbol: `ER_UUID_INVALID`; SQLSTATE: `HY000`  
Message: The server\_uuid stored in auto.cnf file is not a valid UUID.  
`ER_UUID_INVALID` was added in 8.0.2.
  - Error number: `MY-010074`; Symbol: `ER_UUID_SCRUB`; SQLSTATE: `HY000`  
Message: Garbage characters found at the end of the server\_uuid value in auto.cnf file. It should be of  
length '%d' (UUID\_LENGTH). Clear it and restart the server.  
`ER_UUID_SCRUB` was added in 8.0.2.
  - Error number: `MY-010075`; Symbol: `ER_CREATING_NEW_UUID`; SQLSTATE: `HY000`  
Message: No existing UUID has been found, so we assume that this is the first time that this server has  
been started. Generating a new UUID: %s.  
`ER_CREATING_NEW_UUID` was added in 8.0.2.
  - Error number: `MY-010076`; Symbol: `ER_CANT_CREATE_UUID`; SQLSTATE: `HY000`  
Message: Initialization of the server's UUID failed because it could not be read from the auto.cnf file. If  
this is a new server, the initialization failed because it was not possible to generate a new UUID.  
`ER_CANT_CREATE_UUID` was added in 8.0.2.
  - Error number: `MY-010077`; Symbol: `ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE`; SQLSTATE:  
`HY000`  
Message: Unknown/unsupported storage engine: %s  
`ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE` was added in 8.0.2.
  - Error number: `MY-010078`; Symbol: `ER_SECURE_AUTH_VALUE_UNSUPPORTED`; SQLSTATE: `HY000`  
Message: Unsupported value 0 for secure-auth  
`ER_SECURE_AUTH_VALUE_UNSUPPORTED` was added in 8.0.2.
  - Error number: `MY-010079`; Symbol: `ER_INVALID_INSTRUMENT`; SQLSTATE: `HY000`  
Message: Invalid instrument name or value for performance\_schema\_instrument '%s'  
`ER_INVALID_INSTRUMENT` was added in 8.0.2.
  - Error number: `MY-010080`; Symbol: `ER_INNOODB_MANDATORY`; SQLSTATE: `HY000`



---

Message: The use of InnoDB is mandatory since MySQL 5.7. The former options like '--innodb=0/1/OFF/ON' or '--skip-innodb' are ignored.

[ER\\_INNODB\\_MANDATORY](#) was added in 8.0.2.

- Error number: [MY-010082](#); Symbol: [ER\\_OLD\\_PASSWORDS\\_NO\\_MIDDLE\\_GROUND](#); SQLSTATE: [HY000](#)

Message: Invalid old\_passwords mode: 1. Valid values are 2 and 0

[ER\\_OLD\\_PASSWORDS\\_NO\\_MIDDLE\\_GROUND](#) was added in 8.0.2, removed after 8.0.15.

- Error number: [MY-010083](#); Symbol: [ER\\_VERBOSE\\_REQUIRES\\_HELP](#); SQLSTATE: [HY000](#)

Message: --verbose is for use with --help; did you mean --log-error-verbosity?

[ER\\_VERBOSE\\_REQUIRES\\_HELP](#) was added in 8.0.2.

- Error number: [MY-010084](#); Symbol: [ER\\_POINTLESS\\_WITHOUT\\_SLOWLOG](#); SQLSTATE: [HY000](#)

Message: options --log-slow-admin-statements, --log-queries-not-using-indexes and --log-slow-replica-statements have no effect if --slow-query-log is not set

[ER\\_POINTLESS\\_WITHOUT\\_SLOWLOG](#) was added in 8.0.2.

- Error number: [MY-010085](#); Symbol: [ER\\_WASTEFUL\\_NET\\_BUFFER\\_SIZE](#); SQLSTATE: [HY000](#)

Message: net\_buffer\_length (%lu) is set to be larger than max\_allowed\_packet (%lu). Please rectify.

[ER\\_WASTEFUL\\_NET\\_BUFFER\\_SIZE](#) was added in 8.0.2.

- Error number: [MY-010086](#); Symbol: [ER\\_DEPRECATED\\_TIMESTAMP\\_IMPLICIT\\_DEFAULTS](#); SQLSTATE: [HY000](#)

Message: TIMESTAMP with implicit DEFAULT value is deprecated. Please use --explicit\_defaults\_for\_timestamp server option (see documentation for more details).

[ER\\_DEPRECATED\\_TIMESTAMP\\_IMPLICIT\\_DEFAULTS](#) was added in 8.0.2.

- Error number: [MY-010087](#); Symbol: [ER\\_FT\\_BOOL\\_SYNTAX\\_INVALID](#); SQLSTATE: [HY000](#)

Message: Invalid ft-boolean-syntax string: %s

[ER\\_FT\\_BOOL\\_SYNTAX\\_INVALID](#) was added in 8.0.2.

- Error number: [MY-010088](#); Symbol: [ER\\_CREDENTIALLESS\\_AUTO\\_USER\\_BAD](#); SQLSTATE: [HY000](#)

Message: 'NO\_AUTO\_CREATE\_USER' sql mode was not set.

[ER\\_CREDENTIALLESS\\_AUTO\\_USER\\_BAD](#) was added in 8.0.2.

- Error number: [MY-010089](#); Symbol: [ER\\_CONNECTION\\_HANDLING\\_OOM](#); SQLSTATE: [HY000](#)

Message: Could not allocate memory for connection handling

[ER\\_CONNECTION\\_HANDLING\\_OOM](#) was added in 8.0.2.

- Error number: [MY-010090](#); Symbol: [ER\\_THREAD\\_HANDLING\\_OOM](#); SQLSTATE: [HY000](#)

Message: Could not allocate memory for thread handling

- 
- `ER_THREAD_HANDLING_OOM` was added in 8.0.2.
- Error number: `MY-010091`; Symbol: `ER_CANT_CREATE_TEST_FILE`; SQLSTATE: `HY000`  
Message: Can't create test file %s  
`ER_CANT_CREATE_TEST_FILE` was added in 8.0.2.
  - Error number: `MY-010092`; Symbol: `ER_CANT_CREATE_PID_FILE`; SQLSTATE: `HY000`  
Message: Can't start server: can't create PID file: %s  
`ER_CANT_CREATE_PID_FILE` was added in 8.0.2.
  - Error number: `MY-010093`; Symbol: `ER_CANT_REMOVE_PID_FILE`; SQLSTATE: `HY000`  
Message: Unable to delete pid file: %s  
`ER_CANT_REMOVE_PID_FILE` was added in 8.0.2.
  - Error number: `MY-010094`; Symbol: `ER_CANT_CREATE_SHUTDOWN_THREAD`; SQLSTATE: `HY000`  
Message: Can't create thread to handle shutdown requests (errno= %d)  
`ER_CANT_CREATE_SHUTDOWN_THREAD` was added in 8.0.2.
  - Error number: `MY-010095`; Symbol: `ER_SEC_FILE_PRIV_CANT_ACCESS_DIR`; SQLSTATE: `HY000`  
Message: Failed to access directory for --secure-file-priv. Please make sure that directory exists and is accessible by MySQL Server. Supplied value : %s  
`ER_SEC_FILE_PRIV_CANT_ACCESS_DIR` was added in 8.0.2.
  - Error number: `MY-010096`; Symbol: `ER_SEC_FILE_PRIV_IGNORED`; SQLSTATE: `HY000`  
Message: Ignoring --secure-file-priv value as server is running with --initialize(-insecure).  
`ER_SEC_FILE_PRIV_IGNORED` was added in 8.0.2.
  - Error number: `MY-010097`; Symbol: `ER_SEC_FILE_PRIV_EMPTY`; SQLSTATE: `HY000`  
Message: Insecure configuration for --secure-file-priv: Current value does not restrict location of generated files. Consider setting it to a valid, non-empty path.  
`ER_SEC_FILE_PRIV_EMPTY` was added in 8.0.2.
  - Error number: `MY-010098`; Symbol: `ER_SEC_FILE_PRIV_NULL`; SQLSTATE: `HY000`  
Message: --secure-file-priv is set to NULL. Operations related to importing and exporting data are disabled  
`ER_SEC_FILE_PRIV_NULL` was added in 8.0.2.
  - Error number: `MY-010099`; Symbol: `ER_SEC_FILE_PRIV_DIRECTORY_INSECURE`; SQLSTATE: `HY000`  
Message: Insecure configuration for --secure-file-priv: %s is accessible through --secure-file-priv. Consider choosing a different directory.

---

`ER_SEC_FILE_PRIV_DIRECTORY_INSECURE` was added in 8.0.2.

- Error number: `MY-010100`; Symbol: `ER_SEC_FILE_PRIV_CANT_STAT`; SQLSTATE: `HY000`

Message: Failed to get stat for directory pointed out by `--secure-file-priv`

`ER_SEC_FILE_PRIV_CANT_STAT` was added in 8.0.2.

- Error number: `MY-010101`; Symbol: `ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS`; SQLSTATE: `HY000`

Message: Insecure configuration for `--secure-file-priv`: Location is accessible to all OS users. Consider choosing a different directory.

`ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS` was added in 8.0.2.

- Error number: `MY-010102`; Symbol: `ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG`; SQLSTATE: `HY000`

Message: Value for `--secure-file-priv` is longer than maximum limit of %d

`ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG` was added in 8.0.2.

- Error number: `MY-010103`; Symbol: `ER_CANT_CREATE_NAMED_PIPES_THREAD`; SQLSTATE: `HY000`

Message: Can't create thread to handle named pipes (errno= %d)

`ER_CANT_CREATE_NAMED_PIPES_THREAD` was added in 8.0.2.

- Error number: `MY-010104`; Symbol: `ER_CANT_CREATE_TCPIP_THREAD`; SQLSTATE: `HY000`

Message: Can't create thread to handle TCP/IP (errno= %d)

`ER_CANT_CREATE_TCPIP_THREAD` was added in 8.0.2.

- Error number: `MY-010105`; Symbol: `ER_CANT_CREATE_SHM_THREAD`; SQLSTATE: `HY000`

Message: Can't create thread to handle shared memory (errno= %d)

`ER_CANT_CREATE_SHM_THREAD` was added in 8.0.2.

- Error number: `MY-010106`; Symbol: `ER_CANT_CREATE_INTERRUPT_THREAD`; SQLSTATE: `HY000`

Message: Can't create interrupt-thread (error %d, errno: %d)

`ER_CANT_CREATE_INTERRUPT_THREAD` was added in 8.0.2.

- Error number: `MY-010107`; Symbol: `ER_WRITABLE_CONFIG_REMOVED`; SQLSTATE: `HY000`

Message: World-writable config file '%s' has been removed.

`ER_WRITABLE_CONFIG_REMOVED` was added in 8.0.2.

- Error number: `MY-010108`; Symbol: `ER_CORE_VALUES`; SQLSTATE: `HY000`

Message: `setrlimit` could not change the size of core files to 'infinity'; We may not be able to generate a core file on signals

`ER_CORE_VALUES` was added in 8.0.2.

- 
- Error number: [MY-010109](#); Symbol: [ER\\_WRONG\\_DATETIME\\_SPEC](#); SQLSTATE: [HY000](#)  
Message: Wrong date/time format specifier: %s  
[ER\\_WRONG\\_DATETIME\\_SPEC](#) was added in 8.0.2.
  - Error number: [MY-010110](#); Symbol: [ER\\_RPL\\_BINLOG\\_FILTERS\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Could not allocate replication and binlog filters: %s  
[ER\\_RPL\\_BINLOG\\_FILTERS\\_OOM](#) was added in 8.0.2.
  - Error number: [MY-010111](#); Symbol: [ER\\_KEYCACHE\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Cannot allocate the keycache  
[ER\\_KEYCACHE\\_OOM](#) was added in 8.0.2.
  - Error number: [MY-010112](#); Symbol: [ER\\_CONFIRMING\\_THE\\_FUTURE](#); SQLSTATE: [HY000](#)  
Message: Current time has got past year 2038. Validating current time with %d iterations before initiating the normal server shutdown process.  
[ER\\_CONFIRMING\\_THE\\_FUTURE](#) was added in 8.0.2.
  - Error number: [MY-010113](#); Symbol: [ER\\_BACK\\_IN\\_TIME](#); SQLSTATE: [HY000](#)  
Message: Iteration %d: Obtained valid current time from system  
[ER\\_BACK\\_IN\\_TIME](#) was added in 8.0.2.
  - Error number: [MY-010114](#); Symbol: [ER\\_FUTURE\\_DATE](#); SQLSTATE: [HY000](#)  
Message: Iteration %d: Current time obtained from system is greater than 2038  
[ER\\_FUTURE\\_DATE](#) was added in 8.0.2.
  - Error number: [MY-010115](#); Symbol: [ER\\_UNSUPPORTED\\_DATE](#); SQLSTATE: [HY000](#)  
Message: This MySQL server doesn't support dates later then 2038  
[ER\\_UNSUPPORTED\\_DATE](#) was added in 8.0.2.
  - Error number: [MY-010116](#); Symbol: [ER\\_STARTING\\_AS](#); SQLSTATE: [HY000](#)  
Message: %s (mysqld %s) starting as process %lu  
[ER\\_STARTING\\_AS](#) was added in 8.0.2.
  - Error number: [MY-010117](#); Symbol: [ER\\_SHUTTING\\_DOWN\\_SLAVE\\_THREADS](#); SQLSTATE: [HY000](#)  
Message: Shutting down slave threads  
[ER\\_SHUTTING\\_DOWN\\_SLAVE\\_THREADS](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010117](#); Symbol: [ER\\_SHUTTING\\_DOWN\\_REPLICA\\_THREADS](#); SQLSTATE: [HY000](#)  
Message: Shutting down replica threads  
[ER\\_SHUTTING\\_DOWN\\_REPLICA\\_THREADS](#) was added in 8.0.33.

- 
- Error number: [MY-010118](#); Symbol: [ER\\_DISCONNECTING\\_REMAINING\\_CLIENTS](#); SQLSTATE: [HY000](#)  
Message: Forcefully disconnecting %d remaining clients  
[ER\\_DISCONNECTING\\_REMAINING\\_CLIENTS](#) was added in 8.0.2.
  - Error number: [MY-010119](#); Symbol: [ER\\_ABORTING](#); SQLSTATE: [HY000](#)  
Message: Aborting  
[ER\\_ABORTING](#) was added in 8.0.2.
  - Error number: [MY-010120](#); Symbol: [ER\\_BINLOG\\_END](#); SQLSTATE: [HY000](#)  
Message: Binlog end  
[ER\\_BINLOG\\_END](#) was added in 8.0.2.
  - Error number: [MY-010121](#); Symbol: [ER\\_CALL\\_ME\\_LOCALHOST](#); SQLSTATE: [HY000](#)  
Message: gethostname failed, using '%s' as hostname  
[ER\\_CALL\\_ME\\_LOCALHOST](#) was added in 8.0.2.
  - Error number: [MY-010122](#); Symbol: [ER\\_USER\\_REQUIRES\\_ROOT](#); SQLSTATE: [HY000](#)  
Message: One can only use the --user switch if running as root  
[ER\\_USER\\_REQUIRES\\_ROOT](#) was added in 8.0.2.
  - Error number: [MY-010123](#); Symbol: [ER\\_REALLY\\_RUN\\_AS\\_ROOT](#); SQLSTATE: [HY000](#)  
Message: Fatal error: Please read "Security" section of the manual to find out how to run mysqld as root!  
[ER\\_REALLY\\_RUN\\_AS\\_ROOT](#) was added in 8.0.2.
  - Error number: [MY-010124](#); Symbol: [ER\\_USER\\_WHAT\\_USER](#); SQLSTATE: [HY000](#)  
Message: Fatal error: Can't change to run as user '%s' ; Please check that the user exists!  
[ER\\_USER\\_WHAT\\_USER](#) was added in 8.0.2.
  - Error number: [MY-010125](#); Symbol: [ER\\_TRANSPORTS\\_WHAT\\_TRANSPORTS](#); SQLSTATE: [HY000](#)  
Message: Server is started with --require-secure-transport=ON but no secure transports (SSL or Shared Memory) are configured.  
[ER\\_TRANSPORTS\\_WHAT\\_TRANSPORTS](#) was added in 8.0.2.
  - Error number: [MY-010126](#); Symbol: [ER\\_FAIL\\_SETGID](#); SQLSTATE: [HY000](#)  
Message: setgid: %s  
[ER\\_FAIL\\_SETGID](#) was added in 8.0.2.
  - Error number: [MY-010127](#); Symbol: [ER\\_FAIL\\_SETUID](#); SQLSTATE: [HY000](#)  
Message: setuid: %s  
[ER\\_FAIL\\_SETUID](#) was added in 8.0.2.

- 
- Error number: `MY-010128`; Symbol: `ER_FAIL_SETREGID`; SQLSTATE: `HY000`  
Message: `setregid: %s`  
`ER_FAIL_SETREGID` was added in 8.0.2.
  - Error number: `MY-010129`; Symbol: `ER_FAIL_SETREUID`; SQLSTATE: `HY000`  
Message: `setreuid: %s`  
`ER_FAIL_SETREUID` was added in 8.0.2.
  - Error number: `MY-010130`; Symbol: `ER_FAIL_CHROOT`; SQLSTATE: `HY000`  
Message: `chroot: %s`  
`ER_FAIL_CHROOT` was added in 8.0.2.
  - Error number: `MY-010131`; Symbol: `ER_WIN_LISTEN_BUT_HOW`; SQLSTATE: `HY000`  
Message: `TCP/IP, --shared-memory, or --named-pipe should be configured on NT OS`  
`ER_WIN_LISTEN_BUT_HOW` was added in 8.0.2.
  - Error number: `MY-010132`; Symbol: `ER_NOT_RIGHT_NOW`; SQLSTATE: `HY000`  
Message: `CTRL-C ignored during startup`  
`ER_NOT_RIGHT_NOW` was added in 8.0.2.
  - Error number: `MY-010133`; Symbol: `ER_FIXING_CLIENT_CHARSET`; SQLSTATE: `HY000`  
Message: `'%s' can not be used as client character set. '%s' will be used as default client character set.`  
`ER_FIXING_CLIENT_CHARSET` was added in 8.0.2.
  - Error number: `MY-010134`; Symbol: `ER_OOM`; SQLSTATE: `HY000`  
Message: `Out of memory`  
`ER_OOM` was added in 8.0.2.
  - Error number: `MY-010135`; Symbol: `ER_FAILED_TO_LOCK_MEM`; SQLSTATE: `HY000`  
Message: `Failed to lock memory. Errno: %d`  
`ER_FAILED_TO_LOCK_MEM` was added in 8.0.2.
  - Error number: `MY-010136`; Symbol: `ER_MYINIT_FAILED`; SQLSTATE: `HY000`  
Message: `my_init() failed.`  
`ER_MYINIT_FAILED` was added in 8.0.2.
  - Error number: `MY-010137`; Symbol: `ER_BEG_INITFILE`; SQLSTATE: `HY000`  
Message: `Execution of init_file '%s' started.`  
`ER_BEG_INITFILE` was added in 8.0.2.

- 
- Error number: [MY-010138](#); Symbol: [ER\\_END\\_INITFILE](#); SQLSTATE: [HY000](#)  
Message: Execution of init\_file '%s' ended.  
[ER\\_END\\_INITFILE](#) was added in 8.0.2.
  - Error number: [MY-010139](#); Symbol: [ER\\_CHANGED\\_MAX\\_OPEN\\_FILES](#); SQLSTATE: [HY000](#)  
Message: Changed limits: max\_open\_files: %lu (requested %lu)  
[ER\\_CHANGED\\_MAX\\_OPEN\\_FILES](#) was added in 8.0.2.
  - Error number: [MY-010140](#); Symbol: [ER\\_CANT\\_INCREASE\\_MAX\\_OPEN\\_FILES](#); SQLSTATE: [HY000](#)  
Message: Could not increase number of max\_open\_files to more than %lu (request: %lu)  
[ER\\_CANT\\_INCREASE\\_MAX\\_OPEN\\_FILES](#) was added in 8.0.2.
  - Error number: [MY-010141](#); Symbol: [ER\\_CHANGED\\_MAX\\_CONNECTIONS](#); SQLSTATE: [HY000](#)  
Message: Changed limits: max\_connections: %lu (requested %lu)  
[ER\\_CHANGED\\_MAX\\_CONNECTIONS](#) was added in 8.0.2.
  - Error number: [MY-010142](#); Symbol: [ER\\_CHANGED\\_TABLE\\_OPEN\\_CACHE](#); SQLSTATE: [HY000](#)  
Message: Changed limits: table\_open\_cache: %lu (requested %lu)  
[ER\\_CHANGED\\_TABLE\\_OPEN\\_CACHE](#) was added in 8.0.2.
  - Error number: [MY-010143](#); Symbol: [ER\\_THE\\_USER\\_ABIDES](#); SQLSTATE: [HY000](#)  
Message: Ignoring user change to '%s' because the user was set to '%s' earlier on the command line  
[ER\\_THE\\_USER\\_ABIDES](#) was added in 8.0.2.
  - Error number: [MY-010144](#); Symbol: [ER\\_RPL\\_CANT\\_ADD\\_DO\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Could not add do table rule '%s'!  
[ER\\_RPL\\_CANT\\_ADD\\_DO\\_TABLE](#) was added in 8.0.2.
  - Error number: [MY-010145](#); Symbol: [ER\\_RPL\\_CANT\\_ADD\\_IGNORE\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Could not add ignore table rule '%s'!  
[ER\\_RPL\\_CANT\\_ADD\\_IGNORE\\_TABLE](#) was added in 8.0.2.
  - Error number: [MY-010146](#); Symbol: [ER\\_TRACK\\_VARIABLES\\_BOGUS](#); SQLSTATE: [HY000](#)  
Message: The variable session\_track\_system\_variables either has duplicate values or invalid values.  
[ER\\_TRACK\\_VARIABLES\\_BOGUS](#) was added in 8.0.2.
  - Error number: [MY-010147](#); Symbol: [ER\\_EXCESS\\_ARGUMENTS](#); SQLSTATE: [HY000](#)  
Message: Too many arguments (first extra is '%s').  
[ER\\_EXCESS\\_ARGUMENTS](#) was added in 8.0.2.

- 
- Error number: `MY-010148`; Symbol: `ER_VERBOSE_HINT`; SQLSTATE: `HY000`  
Message: Use `--verbose --help` to get a list of available options!  
`ER_VERBOSE_HINT` was added in 8.0.2.
  - Error number: `MY-010149`; Symbol: `ER_CANT_READ_ERRMSG`; SQLSTATE: `HY000`  
Message: Unable to read `errmsg.sys` file  
`ER_CANT_READ_ERRMSG` was added in 8.0.2.
  - Error number: `MY-010150`; Symbol: `ER_CANT_INIT_DBS`; SQLSTATE: `HY000`  
Message: Can't init databases  
`ER_CANT_INIT_DBS` was added in 8.0.2.
  - Error number: `MY-010151`; Symbol: `ER_LOG_OUTPUT_CONTRADICTION`; SQLSTATE: `HY000`  
Message: There were other values specified to log-output besides NONE. Disabling slow and general logs anyway.  
`ER_LOG_OUTPUT_CONTRADICTION` was added in 8.0.2.
  - Error number: `MY-010152`; Symbol: `ER_NO_CSV_NO_LOG_TABLES`; SQLSTATE: `HY000`  
Message: CSV engine is not present, falling back to the log files  
`ER_NO_CSV_NO_LOG_TABLES` was added in 8.0.2.
  - Error number: `MY-010153`; Symbol: `ER_RPL_REWRITEDB_MISSING_ARROW`; SQLSTATE: `HY000`  
Message: Bad syntax in `replicate-rewrite-db` - missing `'->'`!  
`ER_RPL_REWRITEDB_MISSING_ARROW` was added in 8.0.2.
  - Error number: `MY-010154`; Symbol: `ER_RPL_REWRITEDB_EMPTY_FROM`; SQLSTATE: `HY000`  
Message: Bad syntax in `replicate-rewrite-db` - empty FROM db!  
`ER_RPL_REWRITEDB_EMPTY_FROM` was added in 8.0.2.
  - Error number: `MY-010155`; Symbol: `ER_RPL_REWRITEDB_EMPTY_TO`; SQLSTATE: `HY000`  
Message: Bad syntax in `replicate-rewrite-db` - empty TO db!  
`ER_RPL_REWRITEDB_EMPTY_TO` was added in 8.0.2.
  - Error number: `MY-010156`; Symbol: `ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE`; SQLSTATE: `HY000`  
Message: Although a path was specified for the `%s`, log tables are used. To enable logging to files use the `--log-output=file` option.  
`ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE` was added in 8.0.2.
  - Error number: `MY-010157`; Symbol: `ER_LOG_FILE_INVALID`; SQLSTATE: `HY000`  
Message: Invalid value for `%s`: `%s`



---

`ER_LOG_FILE_INVALID` was added in 8.0.2.

- Error number: `MY-010158`; Symbol:

`ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_UNSUPPORTED`; SQLSTATE: `HY000`

Message: The server option 'lower\_case\_table\_names' is configured to use case sensitive table names but the data directory is on a case-insensitive file system which is an unsupported combination. Please consider either using a case sensitive file system for your data directory or switching to a case-insensitive table name mode.

`ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_UNSUPPORTED` was added in 8.0.2.

- Error number: `MY-010159`; Symbol: `ER_LOWER_CASE_TABLE_NAMES_USING_2`; SQLSTATE: `HY000`

Message: Setting lower\_case\_table\_names=2 because file system for %s is case insensitive

`ER_LOWER_CASE_TABLE_NAMES_USING_2` was added in 8.0.2.

- Error number: `MY-010160`; Symbol: `ER_LOWER_CASE_TABLE_NAMES_USING_0`; SQLSTATE: `HY000`

Message: lower\_case\_table\_names was set to 2, even though your the file system '%s' is case sensitive. Now setting lower\_case\_table\_names to 0 to avoid future problems.

`ER_LOWER_CASE_TABLE_NAMES_USING_0` was added in 8.0.2.

- Error number: `MY-010161`; Symbol: `ER_NEED_LOG_BIN`; SQLSTATE: `HY000`

Message: You need to use --log-bin to make %s work.

`ER_NEED_LOG_BIN` was added in 8.0.2.

- Error number: `MY-010162`; Symbol: `ER_NEED_FILE_INSTEAD_OF_DIR`; SQLSTATE: `HY000`

Message: Path '%s' is a directory name, please specify a file name for %s option

`ER_NEED_FILE_INSTEAD_OF_DIR` was added in 8.0.2.

- Error number: `MY-010163`; Symbol: `ER_LOG_BIN_BETTER_WITH_NAME`; SQLSTATE: `HY000`

Message: No argument was provided to --log-bin, and --log-bin-index was not used; so replication may break when this MySQL server acts as a source and has his hostname changed!! Please use '--log-bin=%s' to avoid this problem.

`ER_LOG_BIN_BETTER_WITH_NAME` was added in 8.0.2.

- Error number: `MY-010164`; Symbol: `ER_BINLOG_NEEDS_SERVERID`; SQLSTATE: `HY000`

Message: You have enabled the binary log, but you haven't provided the mandatory server-id. Please refer to the proper server start-up parameters documentation

`ER_BINLOG_NEEDS_SERVERID` was added in 8.0.2.

- Error number: `MY-010165`; Symbol: `ER_RPL_CANT_MAKE_PATHS`; SQLSTATE: `HY000`

Message: Unable to create replication path names: out of memory or path names too long (path name exceeds %d or file name exceeds %d).

`ER_RPL_CANT_MAKE_PATHS` was added in 8.0.2.

- 
- Error number: [MY-010166](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_GTID](#); SQLSTATE: [HY000](#)  
Message: Failed to initialize GTID structures.  
[ER\\_CANT\\_INITIALIZE\\_GTID](#) was added in 8.0.2.
  - Error number: [MY-010167](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_EARLY\\_PLUGINS](#); SQLSTATE: [HY000](#)  
Message: Failed to initialize early plugins.  
[ER\\_CANT\\_INITIALIZE\\_EARLY\\_PLUGINS](#) was added in 8.0.2.
  - Error number: [MY-010168](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_BUILTIN\\_PLUGINS](#); SQLSTATE: [HY000](#)  
Message: Failed to initialize builtin plugins.  
[ER\\_CANT\\_INITIALIZE\\_BUILTIN\\_PLUGINS](#) was added in 8.0.2.
  - Error number: [MY-010169](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_DYNAMIC\\_PLUGINS](#); SQLSTATE: [HY000](#)  
Message: Failed to initialize dynamic plugins.  
[ER\\_CANT\\_INITIALIZE\\_DYNAMIC\\_PLUGINS](#) was added in 8.0.2.
  - Error number: [MY-010170](#); Symbol: [ER\\_PERFSCHEMA\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Performance schema disabled (reason: init failed).  
[ER\\_PERFSCHEMA\\_INIT\\_FAILED](#) was added in 8.0.2.
  - Error number: [MY-010171](#); Symbol: [ER\\_STACKSIZE\\_UNEXPECTED](#); SQLSTATE: [HY000](#)  
Message: Asked for %lu thread stack, but got %ld  
[ER\\_STACKSIZE\\_UNEXPECTED](#) was added in 8.0.2.
  - Error number: [MY-010172](#); Symbol: [ER\\_CANT\\_SET\\_DATADIR](#); SQLSTATE: [HY000](#)  
Message: failed to set datadir to %s  
[ER\\_CANT\\_SET\\_DATADIR](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010173](#); Symbol: [ER\\_CANT\\_STAT\\_DATADIR](#); SQLSTATE: [HY000](#)  
Message: Can't read data directory's stats (%d): %s. Assuming that it's not owned by the same user/group  
[ER\\_CANT\\_STAT\\_DATADIR](#) was added in 8.0.2.
  - Error number: [MY-010174](#); Symbol: [ER\\_CANT\\_CHOWN\\_DATADIR](#); SQLSTATE: [HY000](#)  
Message: Can't change data directory owner to %s  
[ER\\_CANT\\_CHOWN\\_DATADIR](#) was added in 8.0.2.
  - Error number: [MY-010175](#); Symbol: [ER\\_CANT\\_SET\\_UP\\_PERSISTED\\_VALUES](#); SQLSTATE: [HY000](#)  
Message: Setting persistent options failed.  
[ER\\_CANT\\_SET\\_UP\\_PERSISTED\\_VALUES](#) was added in 8.0.2.

- 
- Error number: [MY-010176](#); Symbol: [ER\\_CANT\\_SAVE\\_GTIDS](#); SQLSTATE: [HY000](#)  
Message: Failed to save the set of Global Transaction Identifiers of the last binary log into the `mysql.gtid_executed` table while the server was shutting down. The next server restart will make another attempt to save Global Transaction Identifiers into the table.  
[ER\\_CANT\\_SAVE\\_GTIDS](#) was added in 8.0.2.
  - Error number: [MY-010177](#); Symbol: [ER\\_AUTH\\_CANT\\_SET\\_DEFAULT\\_PLUGIN](#); SQLSTATE: [HY000](#)  
Message: Can't start server: Invalid value for `--default-authentication-plugin`  
[ER\\_AUTH\\_CANT\\_SET\\_DEFAULT\\_PLUGIN](#) was added in 8.0.2.
  - Error number: [MY-010178](#); Symbol: [ER\\_CANT\\_JOIN\\_SHUTDOWN\\_THREAD](#); SQLSTATE: [HY000](#)  
Message: Could not join `%sthread`. error: `%d`  
[ER\\_CANT\\_JOIN\\_SHUTDOWN\\_THREAD](#) was added in 8.0.2.
  - Error number: [MY-010179](#); Symbol: [ER\\_CANT\\_HASH\\_DO\\_AND\\_IGNORE\\_RULES](#); SQLSTATE: [HY000](#)  
Message: An error occurred while building `do_table` and `ignore_table` rules to hashes for global replication filter.  
[ER\\_CANT\\_HASH\\_DO\\_AND\\_IGNORE\\_RULES](#) was added in 8.0.2.
  - Error number: [MY-010180](#); Symbol: [ER\\_CANT\\_OPEN\\_CA](#); SQLSTATE: [HY000](#)  
Message: Error opening CA certificate file  
[ER\\_CANT\\_OPEN\\_CA](#) was added in 8.0.2.
  - Error number: [MY-010181](#); Symbol: [ER\\_CANT\\_ACCESS\\_CAPATH](#); SQLSTATE: [HY000](#)  
Message: Error accessing directory pointed by `--ssl-capath`  
[ER\\_CANT\\_ACCESS\\_CAPATH](#) was added in 8.0.2.
  - Error number: [MY-010182](#); Symbol: [ER\\_SSL\\_TRYING\\_DATADIR\\_DEFAULTS](#); SQLSTATE: [HY000](#)  
Message: Found `%s`, `%s` and `%s` in data directory. Trying to enable SSL support using them.  
[ER\\_SSL\\_TRYING\\_DATADIR\\_DEFAULTS](#) was added in 8.0.2.
  - Error number: [MY-010183](#); Symbol: [ER\\_AUTO\\_OPTIONS\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to create `%s`(file: `'%s'`, errno `%d`)  
[ER\\_AUTO\\_OPTIONS\\_FAILED](#) was added in 8.0.2.
  - Error number: [MY-010184](#); Symbol: [ER\\_CANT\\_INIT\\_TIMER](#); SQLSTATE: [HY000](#)  
Message: Failed to initialize timer component (errno `%d`).  
[ER\\_CANT\\_INIT\\_TIMER](#) was added in 8.0.2.
  - Error number: [MY-010185](#); Symbol: [ER\\_SERVERID\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)  
Message: server-id configured is too large to represent with server-id-bits configured.

---

`ER_SERVERID_TOO_LARGE` was added in 8.0.2.

- Error number: `MY-010186`; Symbol: `ER_DEFAULT_SE_UNAVAILABLE`; SQLSTATE: `HY000`

Message: Default%s storage engine (%s) is not available

`ER_DEFAULT_SE_UNAVAILABLE` was added in 8.0.2.

- Error number: `MY-010187`; Symbol: `ER_CANT_OPEN_ERROR_LOG`; SQLSTATE: `HY000`

Message: Could not open file '%s' for error logging%s%s

`ER_CANT_OPEN_ERROR_LOG` was added in 8.0.2.

- Error number: `MY-010188`; Symbol: `ER_INVALID_ERROR_LOG_NAME`; SQLSTATE: `HY000`

Message: Invalid log file name after expanding symlinks: '%s'

`ER_INVALID_ERROR_LOG_NAME` was added in 8.0.2.

- Error number: `MY-010189`; Symbol: `ER_RPL_INFINITY_DENIED`; SQLSTATE: `HY000`

Message: using `--replicate-same-server-id` in conjunction with `--log-replica-updates` is impossible, it would lead to infinite loops in this server.

`ER_RPL_INFINITY_DENIED` was added in 8.0.2.

- Error number: `MY-010190`; Symbol: `ER_RPL_INFINITY_IGNORED`; SQLSTATE: `HY000`

Message: using `--replicate-same-server-id` in conjunction with `--log-replica-updates` would lead to infinite loops in this server. However this will be ignored as the `--log-bin` option is not defined or your server is running with global transaction identifiers enabled.

`ER_RPL_INFINITY_IGNORED` was added in 8.0.2.

- Error number: `MY-010191`; Symbol: `ER_NDB_TABLES_NOT_READY`; SQLSTATE: `HY000`

Message: NDB : Tables not available after %lu seconds. Consider increasing `--ndb-wait-setup` value

`ER_NDB_TABLES_NOT_READY` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010192`; Symbol: `ER_TABLE_CHECK_INTACT`; SQLSTATE: `HY000`

Message: %s

`ER_TABLE_CHECK_INTACT` was added in 8.0.2.

- Error number: `MY-010193`; Symbol: `ER_DD_TABLESPACE_NOT_FOUND`; SQLSTATE: `HY000`

Message: Unable to start server. The data dictionary tablespace '%s' does not exist.

`ER_DD_TABLESPACE_NOT_FOUND` was added in 8.0.2.

- Error number: `MY-010194`; Symbol: `ER_DD_TRG_CONNECTION_COLLATION_MISSING`; SQLSTATE: `HY000`

Message: Connection collation is missing for trigger of table %s. Using default connection collation.

`ER_DD_TRG_CONNECTION_COLLATION_MISSING` was added in 8.0.2.

- 
- Error number: `MY-010195`; Symbol: `ER_DD_TRG_DB_COLLATION_MISSING`; SQLSTATE: `HY000`  
Message: Database collation is missing for trigger of table %s. Using Default character set.  
`ER_DD_TRG_DB_COLLATION_MISSING` was added in 8.0.2.
  - Error number: `MY-010196`; Symbol: `ER_DD_TRG_DEFINER_OOM`; SQLSTATE: `HY000`  
Message: Error in Memory allocation for Definer %s for Trigger.  
`ER_DD_TRG_DEFINER_OOM` was added in 8.0.2.
  - Error number: `MY-010197`; Symbol: `ER_DD_TRG_FILE_UNREADABLE`; SQLSTATE: `HY000`  
Message: Error in reading %s.TRG file.  
`ER_DD_TRG_FILE_UNREADABLE` was added in 8.0.2.
  - Error number: `MY-010198`; Symbol: `ER_TRG_CANT_PARSE`; SQLSTATE: `HY000`  
Message: Error in parsing Triggers from %s.TRG file.  
`ER_TRG_CANT_PARSE` was added in 8.0.2.
  - Error number: `MY-010199`; Symbol: `ER_DD_TRG_CANT_ADD`; SQLSTATE: `HY000`  
Message: Error in creating DD entry for Trigger %s.%s  
`ER_DD_TRG_CANT_ADD` was added in 8.0.2.
  - Error number: `MY-010200`; Symbol: `ER_DD_CANT_RESOLVE_VIEW`; SQLSTATE: `HY000`  
Message: Resolving dependency for the view '%s.%s' failed. View is no more valid to use  
`ER_DD_CANT_RESOLVE_VIEW` was added in 8.0.2.
  - Error number: `MY-010201`; Symbol: `ER_DD_VIEW_WITHOUT_DEFINER`; SQLSTATE: `HY000`  
Message: %s.%s has no definer (as per an old view format). Current user is used as definer. Please recreate the view.  
`ER_DD_VIEW_WITHOUT_DEFINER` was added in 8.0.2.
  - Error number: `MY-010202`; Symbol: `ER_PLUGIN_INIT_FAILED`; SQLSTATE: `HY000`  
Message: Plugin '%s' init function returned error.  
`ER_PLUGIN_INIT_FAILED` was added in 8.0.2.
  - Error number: `MY-010203`; Symbol: `ER_RPL_TRX_DELEGATES_INIT_FAILED`; SQLSTATE: `HY000`  
Message: Initialization of transaction delegates failed. Please report a bug.  
`ER_RPL_TRX_DELEGATES_INIT_FAILED` was added in 8.0.2.
  - Error number: `MY-010204`; Symbol: `ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED`; SQLSTATE: `HY000`  
Message: Initialization binlog storage delegates failed. Please report a bug.

- 
- [ER\\_RPL\\_BINLOG\\_STORAGE\\_DELEGATES\\_INIT\\_FAILED](#) was added in 8.0.2.
- Error number: [MY-010205](#); Symbol: [ER\\_RPL\\_BINLOG\\_TRANSMIT\\_DELEGATES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Initialization of binlog transmit delegates failed. Please report a bug.  
[ER\\_RPL\\_BINLOG\\_TRANSMIT\\_DELEGATES\\_INIT\\_FAILED](#) was added in 8.0.2.
  - Error number: [MY-010206](#); Symbol: [ER\\_RPL\\_BINLOG\\_RELAY\\_DELEGATES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Initialization binlog relay IO delegates failed. Please report a bug.  
[ER\\_RPL\\_BINLOG\\_RELAY\\_DELEGATES\\_INIT\\_FAILED](#) was added in 8.0.2.
  - Error number: [MY-010207](#); Symbol: [ER\\_RPL\\_PLUGIN\\_FUNCTION\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Run function '...' in plugin '%s' failed  
[ER\\_RPL\\_PLUGIN\\_FUNCTION\\_FAILED](#) was added in 8.0.2.
  - Error number: [MY-010208](#); Symbol: [ER\\_SQL\\_HA\\_READ\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: mysql\_ha\_read: Got error %d when reading table '%s'  
[ER\\_SQL\\_HA\\_READ\\_FAILED](#) was added in 8.0.2.
  - Error number: [MY-010209](#); Symbol: [ER\\_SR\\_BOGUS\\_VALUE](#); SQLSTATE: [HY000](#)  
Message: Stored routine '%s'. '%s': invalid value in column %s.  
[ER\\_SR\\_BOGUS\\_VALUE](#) was added in 8.0.2.
  - Error number: [MY-010210](#); Symbol: [ER\\_SR\\_INVALID\\_CONTEXT](#); SQLSTATE: [HY000](#)  
Message: Invalid creation context '%s.%s'.  
[ER\\_SR\\_INVALID\\_CONTEXT](#) was added in 8.0.2.
  - Error number: [MY-010211](#); Symbol: [ER\\_READING\\_TABLE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Got error %d when reading table '%s'  
[ER\\_READING\\_TABLE\\_FAILED](#) was added in 8.0.2.
  - Error number: [MY-010212](#); Symbol: [ER\\_DES\\_FILE\\_WRONG\\_KEY](#); SQLSTATE: [HY000](#)  
Message: load\_des\_file: Found wrong key\_number: %c  
[ER\\_DES\\_FILE\\_WRONG\\_KEY](#) was added in 8.0.2.
  - Error number: [MY-010214](#); Symbol: [ER\\_JSON\\_PARSE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Persisted config file is corrupt. Please ensure mysqld-auto.cnf file is valid JSON.  
[ER\\_JSON\\_PARSE\\_ERROR](#) was added in 8.0.2.
  - Error number: [MY-010215](#); Symbol: [ER\\_CONFIG\\_OPTION\\_WITHOUT\\_GROUP](#); SQLSTATE: [HY000](#)

---

Message: Found option without preceding group in config file

[ER\\_CONFIG\\_OPTION\\_WITHOUT\\_GROUP](#) was added in 8.0.2.

- Error number: [MY-010216](#); Symbol: [ER\\_VALGRIND\\_DO\\_QUICK\\_LEAK\\_CHECK](#); SQLSTATE: [HY000](#)

Message: VALGRIND\_DO\_QUICK\_LEAK\_CHECK

[ER\\_VALGRIND\\_DO\\_QUICK\\_LEAK\\_CHECK](#) was added in 8.0.2.

- Error number: [MY-010217](#); Symbol: [ER\\_VALGRIND\\_COUNT\\_LEAKS](#); SQLSTATE: [HY000](#)

Message: VALGRIND\_COUNT\_LEAKS reports %lu leaked bytes for query '%.\*s'

[ER\\_VALGRIND\\_COUNT\\_LEAKS](#) was added in 8.0.2.

- Error number: [MY-010218](#); Symbol: [ER\\_LOAD\\_DATA\\_INFILE\\_FAILED\\_IN\\_UNEXPECTED\\_WAY](#); SQLSTATE: [HY000](#)

Message: LOAD DATA INFILE in the replica SQL Thread can only read from --replica-load-tmpdir. Please, report a bug.

[ER\\_LOAD\\_DATA\\_INFILE\\_FAILED\\_IN\\_UNEXPECTED\\_WAY](#) was added in 8.0.2.

- Error number: [MY-010219](#); Symbol: [ER\\_UNKNOWN\\_ERROR\\_NUMBER](#); SQLSTATE: [HY000](#)

Message: Got unknown error: %d

[ER\\_UNKNOWN\\_ERROR\\_NUMBER](#) was added in 8.0.2.

- Error number: [MY-010220](#); Symbol: [ER\\_UDF\\_CANT\\_ALLOC\\_FOR\\_STRUCTURES](#); SQLSTATE: [HY000](#)

Message: Can't allocate memory for udf structures

[ER\\_UDF\\_CANT\\_ALLOC\\_FOR\\_STRUCTURES](#) was added in 8.0.2.

- Error number: [MY-010221](#); Symbol: [ER\\_UDF\\_CANT\\_ALLOC\\_FOR\\_FUNCTION](#); SQLSTATE: [HY000](#)

Message: Can't alloc memory for udf function: '%s'

[ER\\_UDF\\_CANT\\_ALLOC\\_FOR\\_FUNCTION](#) was added in 8.0.2.

- Error number: [MY-010222](#); Symbol: [ER\\_UDF\\_INVALID\\_ROW\\_IN\\_FUNCTION\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Invalid row in mysql.func table for function '%s'

[ER\\_UDF\\_INVALID\\_ROW\\_IN\\_FUNCTION\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010223](#); Symbol: [ER\\_UDF\\_CANT\\_OPEN\\_FUNCTION\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Could not open the mysql.func table. Please perform the MySQL upgrade procedure.

[ER\\_UDF\\_CANT\\_OPEN\\_FUNCTION\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010224](#); Symbol: [ER\\_XA\\_RECOVER\\_FOUND\\_TRX\\_IN\\_SE](#); SQLSTATE: [HY000](#)

Message: Found %d prepared transaction(s) in %s

---

[ER\\_XA\\_RECOVER\\_FOUND\\_TRX\\_IN\\_SE](#) was added in 8.0.2.

- Error number: [MY-010225](#); Symbol: [ER\\_XA\\_RECOVER\\_FOUND\\_XA\\_TRX](#); SQLSTATE: [HY000](#)  
Message: Found %d prepared XA transactions

[ER\\_XA\\_RECOVER\\_FOUND\\_XA\\_TRX](#) was added in 8.0.2.

- Error number: [MY-010226](#); Symbol: [ER\\_XA\\_IGNOREING\\_XID](#); SQLSTATE: [HY000](#)  
Message: ignore xid %s

[ER\\_XA\\_IGNOREING\\_XID](#) was added in 8.0.2, removed after 8.0.29.

- Error number: [MY-010227](#); Symbol: [ER\\_XA\\_COMMITTING\\_XID](#); SQLSTATE: [HY000](#)  
Message: commit xid %s

[ER\\_XA\\_COMMITTING\\_XID](#) was added in 8.0.2, removed after 8.0.29.

- Error number: [MY-010228](#); Symbol: [ER\\_XA\\_ROLLING\\_BACK\\_XID](#); SQLSTATE: [HY000](#)  
Message: rollback xid %s

[ER\\_XA\\_ROLLING\\_BACK\\_XID](#) was added in 8.0.2, removed after 8.0.29.

- Error number: [MY-010229](#); Symbol: [ER\\_XA\\_STARTING\\_RECOVERY](#); SQLSTATE: [HY000](#)  
Message: Starting XA crash recovery...

[ER\\_XA\\_STARTING\\_RECOVERY](#) was added in 8.0.2.

- Error number: [MY-010230](#); Symbol: [ER\\_XA\\_NO\\_MULTI\\_2PC\\_HEURISTIC\\_RECOVER](#); SQLSTATE: [HY000](#)

Message: --tc-heuristic-recover rollback strategy is not safe on systems with more than one 2-phase-commit-capable storage engine. Aborting crash recovery.

[ER\\_XA\\_NO\\_MULTI\\_2PC\\_HEURISTIC\\_RECOVER](#) was added in 8.0.2.

- Error number: [MY-010231](#); Symbol: [ER\\_XA\\_RECOVER\\_EXPLANATION](#); SQLSTATE: [HY000](#)

Message: Found %d prepared transactions! It means that mysqld was not shut down properly last time and critical recovery information (last binlog or %s file) was manually deleted after a crash. You have to start mysqld with --tc-heuristic-recover switch to commit or rollback pending transactions.

[ER\\_XA\\_RECOVER\\_EXPLANATION](#) was added in 8.0.2.

- Error number: [MY-010232](#); Symbol: [ER\\_XA\\_RECOVERY\\_DONE](#); SQLSTATE: [HY000](#)

Message: XA crash recovery finished.

[ER\\_XA\\_RECOVERY\\_DONE](#) was added in 8.0.2.

- Error number: [MY-010233](#); Symbol: [ER\\_TRX\\_GTID\\_COLLECT\\_REJECT](#); SQLSTATE: [HY000](#)

Message: Failed to collect GTID to send in the response packet!

[ER\\_TRX\\_GTID\\_COLLECT\\_REJECT](#) was added in 8.0.2.



- 
- Error number: [MY-010234](#); Symbol: [ER\\_SQL\\_AUTHOR\\_DEFAULT\\_ROLES\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: MYSQL.DEFAULT\_ROLES couldn't be updated for authorization identifier %s  
[ER\\_SQL\\_AUTHOR\\_DEFAULT\\_ROLES\\_FAIL](#) was added in 8.0.2.
  - Error number: [MY-010235](#); Symbol: [ER\\_SQL\\_USER\\_TABLE\\_CREATE\\_WARNING](#); SQLSTATE: [HY000](#)  
Message: Following users were specified in CREATE USER IF NOT EXISTS but they already exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s  
[ER\\_SQL\\_USER\\_TABLE\\_CREATE\\_WARNING](#) was added in 8.0.2.
  - Error number: [MY-010236](#); Symbol: [ER\\_SQL\\_USER\\_TABLE\\_ALTER\\_WARNING](#); SQLSTATE: [HY000](#)  
Message: Following users were specified in ALTER USER IF EXISTS but they do not exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s  
[ER\\_SQL\\_USER\\_TABLE\\_ALTER\\_WARNING](#) was added in 8.0.2.
  - Error number: [MY-010237](#); Symbol: [ER\\_ROW\\_IN\\_WRONG\\_PARTITION\\_PLEASE\\_REPAIR](#); SQLSTATE: [HY000](#)  
Message: Table '%s' corrupted: row in wrong partition: %s -- Please REPAIR the table!  
[ER\\_ROW\\_IN\\_WRONG\\_PARTITION\\_PLEASE\\_REPAIR](#) was added in 8.0.2.
  - Error number: [MY-010238](#); Symbol: [ER\\_MYISAM\\_CRASHED\\_ERROR\\_IN\\_THREAD](#); SQLSTATE: [HY000](#)  
Message: Got an error from thread\_id=%u, %s:%d  
[ER\\_MYISAM\\_CRASHED\\_ERROR\\_IN\\_THREAD](#) was added in 8.0.2.
  - Error number: [MY-010239](#); Symbol: [ER\\_MYISAM\\_CRASHED\\_ERROR\\_IN](#); SQLSTATE: [HY000](#)  
Message: Got an error from unknown thread, %s:%d  
[ER\\_MYISAM\\_CRASHED\\_ERROR\\_IN](#) was added in 8.0.2.
  - Error number: [MY-010240](#); Symbol: [ER\\_TOO\\_MANY\\_STORAGE\\_ENGINES](#); SQLSTATE: [HY000](#)  
Message: Too many storage engines!  
[ER\\_TOO\\_MANY\\_STORAGE\\_ENGINES](#) was added in 8.0.2.
  - Error number: [MY-010241](#); Symbol: [ER\\_SE\\_TYPECODE\\_CONFLICT](#); SQLSTATE: [HY000](#)  
Message: Storage engine '%s' has conflicting typecode. Assigning value %d.  
[ER\\_SE\\_TYPECODE\\_CONFLICT](#) was added in 8.0.2.
  - Error number: [MY-010242](#); Symbol: [ER\\_TRX\\_WRITE\\_SET\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Out of memory on transaction write set extraction  
[ER\\_TRX\\_WRITE\\_SET\\_OOM](#) was added in 8.0.2.
  - Error number: [MY-010243](#); Symbol: [ER\\_HANDLERTON\\_OOM](#); SQLSTATE: [HY000](#)

---

Message: Unable to allocate memory for plugin '%s' handler on.

[ER\\_HANDLERTON\\_OOM](#) was added in 8.0.2.

- Error number: [MY-010244](#); Symbol: [ER\\_CONN\\_SHM\\_LISTENER](#); SQLSTATE: [HY000](#)

Message: Shared memory setting up listener

[ER\\_CONN\\_SHM\\_LISTENER](#) was added in 8.0.2.

- Error number: [MY-010245](#); Symbol: [ER\\_CONN\\_SHM\\_CANT\\_CREATE\\_SERVICE](#); SQLSTATE: [HY000](#)

Message: Can't create shared memory service: %s. : %s

[ER\\_CONN\\_SHM\\_CANT\\_CREATE\\_SERVICE](#) was added in 8.0.2.

- Error number: [MY-010246](#); Symbol: [ER\\_CONN\\_SHM\\_CANT\\_CREATE\\_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Can't create shared memory connection: %s. : %s

[ER\\_CONN\\_SHM\\_CANT\\_CREATE\\_CONNECTION](#) was added in 8.0.2.

- Error number: [MY-010247](#); Symbol: [ER\\_CONN\\_PIP\\_CANT\\_CREATE\\_EVENT](#); SQLSTATE: [HY000](#)

Message: Can't create event, last error=%u

[ER\\_CONN\\_PIP\\_CANT\\_CREATE\\_EVENT](#) was added in 8.0.2.

- Error number: [MY-010248](#); Symbol: [ER\\_CONN\\_PIP\\_CANT\\_CREATE\\_PIPE](#); SQLSTATE: [HY000](#)

Message: Can't create new named pipe!: %s

[ER\\_CONN\\_PIP\\_CANT\\_CREATE\\_PIPE](#) was added in 8.0.2.

- Error number: [MY-010249](#); Symbol: [ER\\_CONN\\_PER\\_THREAD\\_NO\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create thread to handle new connection(errno= %d)

[ER\\_CONN\\_PER\\_THREAD\\_NO\\_THREAD](#) was added in 8.0.2.

- Error number: [MY-010250](#); Symbol: [ER\\_CONN\\_TCP\\_NO\\_SOCKET](#); SQLSTATE: [HY000](#)

Message: Failed to create a socket for %s '%s': errno: %d.

[ER\\_CONN\\_TCP\\_NO\\_SOCKET](#) was added in 8.0.2.

- Error number: [MY-010251](#); Symbol: [ER\\_CONN\\_TCP\\_CREATED](#); SQLSTATE: [HY000](#)

Message: Server socket created on IP: '%s'.

[ER\\_CONN\\_TCP\\_CREATED](#) was added in 8.0.2.

- Error number: [MY-010252](#); Symbol: [ER\\_CONN\\_TCP\\_ADDRESS](#); SQLSTATE: [HY000](#)

Message: Server hostname (bind-address): '%s'; port: %d

[ER\\_CONN\\_TCP\\_ADDRESS](#) was added in 8.0.2.

- Error number: [MY-010253](#); Symbol: [ER\\_CONN\\_TCP\\_IPV6\\_AVAILABLE](#); SQLSTATE: [HY000](#)

---

Message: IPv6 is available.

[ER\\_CONN\\_TCP\\_IPV6\\_AVAILABLE](#) was added in 8.0.2.

- Error number: [MY-010254](#); Symbol: [ER\\_CONN\\_TCP\\_IPV6\\_UNAVAILABLE](#); SQLSTATE: [HY000](#)

Message: IPv6 is not available.

[ER\\_CONN\\_TCP\\_IPV6\\_UNAVAILABLE](#) was added in 8.0.2.

- Error number: [MY-010255](#); Symbol: [ER\\_CONN\\_TCP\\_ERROR\\_WITH\\_STRERROR](#); SQLSTATE: [HY000](#)

Message: Can't create IP socket: %s

[ER\\_CONN\\_TCP\\_ERROR\\_WITH\\_STRERROR](#) was added in 8.0.2.

- Error number: [MY-010256](#); Symbol: [ER\\_CONN\\_TCP\\_CANT\\_RESOLVE\\_HOSTNAME](#); SQLSTATE: [HY000](#)

Message: Can't start server: cannot resolve hostname!

[ER\\_CONN\\_TCP\\_CANT\\_RESOLVE\\_HOSTNAME](#) was added in 8.0.2.

- Error number: [MY-010257](#); Symbol: [ER\\_CONN\\_TCP\\_IS\\_THERE\\_ANOTHER\\_USING\\_PORT](#); SQLSTATE: [HY000](#)

Message: Do you already have another mysqld server running on port: %d ?

[ER\\_CONN\\_TCP\\_IS\\_THERE\\_ANOTHER\\_USING\\_PORT](#) was added in 8.0.2.

- Error number: [MY-010258](#); Symbol: [ER\\_CONN\\_UNIX\\_IS\\_THERE\\_ANOTHER\\_USING\\_SOCKET](#); SQLSTATE: [HY000](#)

Message: Do you already have another mysqld server running on socket: %s ?

[ER\\_CONN\\_UNIX\\_IS\\_THERE\\_ANOTHER\\_USING\\_SOCKET](#) was added in 8.0.2.

- Error number: [MY-010259](#); Symbol: [ER\\_CONN\\_UNIX\\_PID\\_CLAIMED\\_SOCKET\\_FILE](#); SQLSTATE: [HY000](#)

Message: Another process with pid %d is using unix socket file.

[ER\\_CONN\\_UNIX\\_PID\\_CLAIMED\\_SOCKET\\_FILE](#) was added in 8.0.2.

- Error number: [MY-010260](#); Symbol: [ER\\_CONN\\_TCP\\_CANT\\_RESET\\_V6ONLY](#); SQLSTATE: [HY000](#)

Message: Failed to reset IPV6\_V6ONLY flag (error: %d). The server will listen to IPv6 addresses only.

[ER\\_CONN\\_TCP\\_CANT\\_RESET\\_V6ONLY](#) was added in 8.0.2.

- Error number: [MY-010261](#); Symbol: [ER\\_CONN\\_TCP\\_BIND\\_RETRY](#); SQLSTATE: [HY000](#)

Message: Retrying bind on TCP/IP port %u

[ER\\_CONN\\_TCP\\_BIND\\_RETRY](#) was added in 8.0.2.

- Error number: [MY-010262](#); Symbol: [ER\\_CONN\\_TPC\\_BIND\\_FAIL](#); SQLSTATE: [HY000](#)

Message: Can't start server: Bind on TCP/IP port: %s

---

`ER_CONN_TPC_BIND_FAIL` was added in 8.0.2, removed after 8.0.11.

- Error number: `MY-010262`; Symbol: `ER_CONN_TCP_BIND_FAIL`; SQLSTATE: `HY000`

Message: Can't start server: Bind on TCP/IP port: %s

`ER_CONN_TCP_BIND_FAIL` was added in 8.0.12.

- Error number: `MY-010263`; Symbol: `ER_CONN_TCP_IP_NOT_LOGGED`; SQLSTATE: `HY000`

Message: Fails to print out IP-address.

`ER_CONN_TCP_IP_NOT_LOGGED` was added in 8.0.2.

- Error number: `MY-010264`; Symbol: `ER_CONN_TCP_RESOLVE_INFO`; SQLSTATE: `HY000`

Message: - '%s' resolves to '%s';

`ER_CONN_TCP_RESOLVE_INFO` was added in 8.0.2.

- Error number: `MY-010265`; Symbol: `ER_CONN_TCP_START_FAIL`; SQLSTATE: `HY000`

Message: Can't start server: listen() on TCP/IP port: %s

`ER_CONN_TCP_START_FAIL` was added in 8.0.2.

- Error number: `MY-010266`; Symbol: `ER_CONN_TCP_LISTEN_FAIL`; SQLSTATE: `HY000`

Message: listen() on TCP/IP failed with error %d

`ER_CONN_TCP_LISTEN_FAIL` was added in 8.0.2.

- Error number: `MY-010267`; Symbol: `ER_CONN_UNIX_PATH_TOO_LONG`; SQLSTATE: `HY000`

Message: The socket file path is too long (> %u): %s

`ER_CONN_UNIX_PATH_TOO_LONG` was added in 8.0.2.

- Error number: `MY-010268`; Symbol: `ER_CONN_UNIX_LOCK_FILE_FAIL`; SQLSTATE: `HY000`

Message: Unable to setup unix socket lock file.

`ER_CONN_UNIX_LOCK_FILE_FAIL` was added in 8.0.2.

- Error number: `MY-010269`; Symbol: `ER_CONN_UNIX_NO_FD`; SQLSTATE: `HY000`

Message: Can't start server: UNIX Socket : %s

`ER_CONN_UNIX_NO_FD` was added in 8.0.2.

- Error number: `MY-010270`; Symbol: `ER_CONN_UNIX_NO_BIND_NO_START`; SQLSTATE: `HY000`

Message: Can't start server : Bind on unix socket: %s

`ER_CONN_UNIX_NO_BIND_NO_START` was added in 8.0.2.

- Error number: `MY-010271`; Symbol: `ER_CONN_UNIX_LISTEN_FAILED`; SQLSTATE: `HY000`

Message: listen() on Unix socket failed with error %d

---

`ER_CONN_UNIX_LISTEN_FAILED` was added in 8.0.2.

- Error number: `MY-010272`; Symbol: `ER_CONN_UNIX_LOCK_FILE_GIVING_UP`; SQLSTATE: `HY000`  
Message: Unable to create unix socket lock file %s after retries.

`ER_CONN_UNIX_LOCK_FILE_GIVING_UP` was added in 8.0.2.

- Error number: `MY-010273`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_CREATE`; SQLSTATE: `HY000`  
Message: Could not create unix socket lock file %s.

`ER_CONN_UNIX_LOCK_FILE_CANT_CREATE` was added in 8.0.2.

- Error number: `MY-010274`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_OPEN`; SQLSTATE: `HY000`  
Message: Could not open unix socket lock file %s.

`ER_CONN_UNIX_LOCK_FILE_CANT_OPEN` was added in 8.0.2.

- Error number: `MY-010275`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_READ`; SQLSTATE: `HY000`  
Message: Could not read unix socket lock file %s.

`ER_CONN_UNIX_LOCK_FILE_CANT_READ` was added in 8.0.2.

- Error number: `MY-010276`; Symbol: `ER_CONN_UNIX_LOCK_FILE_EMPTY`; SQLSTATE: `HY000`  
Message: Unix socket lock file is empty %s.

`ER_CONN_UNIX_LOCK_FILE_EMPTY` was added in 8.0.2.

- Error number: `MY-010277`; Symbol: `ER_CONN_UNIX_LOCK_FILE_PIDLESS`; SQLSTATE: `HY000`  
Message: Invalid pid in unix socket lock file %s.

`ER_CONN_UNIX_LOCK_FILE_PIDLESS` was added in 8.0.2.

- Error number: `MY-010278`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_WRITE`; SQLSTATE: `HY000`  
Message: Could not write unix socket lock file %s errno %d.

`ER_CONN_UNIX_LOCK_FILE_CANT_WRITE` was added in 8.0.2.

- Error number: `MY-010279`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_DELETE`; SQLSTATE: `HY000`  
Message: Could not remove unix socket lock file %s errno %d.

`ER_CONN_UNIX_LOCK_FILE_CANT_DELETE` was added in 8.0.2.

- Error number: `MY-010280`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_SYNC`; SQLSTATE: `HY000`  
Message: Could not sync unix socket lock file %s errno %d.

`ER_CONN_UNIX_LOCK_FILE_CANT_SYNC` was added in 8.0.2.

- Error number: `MY-010281`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE`; SQLSTATE: `HY000`  
Message: Could not close unix socket lock file %s errno %d.

- 
- `ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE` was added in 8.0.2.
- Error number: `MY-010282`; Symbol: `ER_CONN_SOCKET_SELECT_FAILED`; SQLSTATE: `HY000`  
Message: mysqld: Got error %d from select  
`ER_CONN_SOCKET_SELECT_FAILED` was added in 8.0.2.
  - Error number: `MY-010283`; Symbol: `ER_CONN_SOCKET_ACCEPT_FAILED`; SQLSTATE: `HY000`  
Message: Error in accept: %s  
`ER_CONN_SOCKET_ACCEPT_FAILED` was added in 8.0.2.
  - Error number: `MY-010284`; Symbol: `ER_AUTH_RSA_CANT_FIND`; SQLSTATE: `HY000`  
Message: RSA %s key file not found: %s. Some authentication plugins will not work.  
`ER_AUTH_RSA_CANT_FIND` was added in 8.0.2.
  - Error number: `MY-010285`; Symbol: `ER_AUTH_RSA_CANT_PARSE`; SQLSTATE: `HY000`  
Message: Failure to parse RSA %s key (file exists): %s: %s  
`ER_AUTH_RSA_CANT_PARSE` was added in 8.0.2.
  - Error number: `MY-010286`; Symbol: `ER_AUTH_RSA_CANT_READ`; SQLSTATE: `HY000`  
Message: Failure to read key file: %s  
`ER_AUTH_RSA_CANT_READ` was added in 8.0.2.
  - Error number: `MY-010287`; Symbol: `ER_AUTH_RSA_FILES_NOT_FOUND`; SQLSTATE: `HY000`  
Message: RSA key files not found. Some authentication plugins will not work.  
`ER_AUTH_RSA_FILES_NOT_FOUND` was added in 8.0.2.
  - Error number: `MY-010288`; Symbol: `ER_CONN_ATTR_TRUNCATED`; SQLSTATE: `HY000`  
Message: Connection attributes of length %lu were truncated (%d bytes lost) for connection %llu, user %s@%s (as %s), auth: %s  
`ER_CONN_ATTR_TRUNCATED` was added in 8.0.2.
  - Error number: `MY-010289`; Symbol: `ER_X509_CIPHERS_MISMATCH`; SQLSTATE: `HY000`  
Message: X.509 ciphers mismatch: should be '%s' but is '%s'  
`ER_X509_CIPHERS_MISMATCH` was added in 8.0.2.
  - Error number: `MY-010290`; Symbol: `ER_X509_ISSUER_MISMATCH`; SQLSTATE: `HY000`  
Message: X.509 issuer mismatch: should be '%s' but is '%s'  
`ER_X509_ISSUER_MISMATCH` was added in 8.0.2.
  - Error number: `MY-010291`; Symbol: `ER_X509_SUBJECT_MISMATCH`; SQLSTATE: `HY000`

---

Message: X.509 subject mismatch: should be '%s' but is '%s'

[ER\\_X509\\_SUBJECT\\_MISMATCH](#) was added in 8.0.2.

- Error number: [MY-010292](#); Symbol: [ER\\_AUTH\\_CANT\\_ACTIVATE\\_ROLE](#); SQLSTATE: [HY000](#)

Message: Failed to activate default role %s for %s

[ER\\_AUTH\\_CANT\\_ACTIVATE\\_ROLE](#) was added in 8.0.2.

- Error number: [MY-010293](#); Symbol: [ER\\_X509\\_NEEDS\\_RSA\\_PRIVKEY](#); SQLSTATE: [HY000](#)

Message: Could not generate RSA private key required for X.509 certificate.

[ER\\_X509\\_NEEDS\\_RSA\\_PRIVKEY](#) was added in 8.0.2.

- Error number: [MY-010294](#); Symbol: [ER\\_X509\\_CANT\\_WRITE\\_KEY](#); SQLSTATE: [HY000](#)

Message: Could not write key file: %s

[ER\\_X509\\_CANT\\_WRITE\\_KEY](#) was added in 8.0.2.

- Error number: [MY-010295](#); Symbol: [ER\\_X509\\_CANT\\_CHMOD\\_KEY](#); SQLSTATE: [HY000](#)

Message: Could not set file permission for %s

[ER\\_X509\\_CANT\\_CHMOD\\_KEY](#) was added in 8.0.2.

- Error number: [MY-010296](#); Symbol: [ER\\_X509\\_CANT\\_READ\\_CA\\_KEY](#); SQLSTATE: [HY000](#)

Message: Could not read CA key file: %s

[ER\\_X509\\_CANT\\_READ\\_CA\\_KEY](#) was added in 8.0.2.

- Error number: [MY-010297](#); Symbol: [ER\\_X509\\_CANT\\_READ\\_CA\\_CERT](#); SQLSTATE: [HY000](#)

Message: Could not read CA certificate file: %s

[ER\\_X509\\_CANT\\_READ\\_CA\\_CERT](#) was added in 8.0.2.

- Error number: [MY-010298](#); Symbol: [ER\\_X509\\_CANT\\_CREATE\\_CERT](#); SQLSTATE: [HY000](#)

Message: Could not generate X.509 certificate.

[ER\\_X509\\_CANT\\_CREATE\\_CERT](#) was added in 8.0.2.

- Error number: [MY-010299](#); Symbol: [ER\\_X509\\_CANT\\_WRITE\\_CERT](#); SQLSTATE: [HY000](#)

Message: Could not write certificate file: %s

[ER\\_X509\\_CANT\\_WRITE\\_CERT](#) was added in 8.0.2.

- Error number: [MY-010300](#); Symbol: [ER\\_AUTH\\_CANT\\_CREATE\\_RSA\\_PAIR](#); SQLSTATE: [HY000](#)

Message: Could not generate RSA Private/Public key pair

[ER\\_AUTH\\_CANT\\_CREATE\\_RSA\\_PAIR](#) was added in 8.0.2.

- Error number: [MY-010301](#); Symbol: [ER\\_AUTH\\_CANT\\_WRITE\\_PRIVKEY](#); SQLSTATE: [HY000](#)

---

Message: Could not write private key file: %s

[ER\\_AUTH\\_CANT\\_WRITE\\_PRIVKEY](#) was added in 8.0.2.

- Error number: [MY-010302](#); Symbol: [ER\\_AUTH\\_CANT\\_WRITE\\_PUBKEY](#); SQLSTATE: [HY000](#)

Message: Could not write public key file: %s

[ER\\_AUTH\\_CANT\\_WRITE\\_PUBKEY](#) was added in 8.0.2.

- Error number: [MY-010303](#); Symbol: [ER\\_AUTH\\_SSL\\_CONF\\_PREVENTS\\_CERT\\_GENERATION](#); SQLSTATE: [HY000](#)

Message: Skipping generation of SSL certificates as options related to SSL are specified.

[ER\\_AUTH\\_SSL\\_CONF\\_PREVENTS\\_CERT\\_GENERATION](#) was added in 8.0.2.

- Error number: [MY-010304](#); Symbol: [ER\\_AUTH\\_USING\\_EXISTING\\_CERTS](#); SQLSTATE: [HY000](#)

Message: Skipping generation of SSL certificates as certificate files are present in data directory.

[ER\\_AUTH\\_USING\\_EXISTING\\_CERTS](#) was added in 8.0.2.

- Error number: [MY-010305](#); Symbol: [ER\\_AUTH\\_CERTS\\_SAVED\\_TO\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: Auto generated SSL certificates are placed in data directory.

[ER\\_AUTH\\_CERTS\\_SAVED\\_TO\\_DATADIR](#) was added in 8.0.2.

- Error number: [MY-010306](#); Symbol: [ER\\_AUTH\\_CERT\\_GENERATION\\_DISABLED](#); SQLSTATE: [HY000](#)

Message: Skipping generation of SSL certificates as --auto\_generate\_certs is set to OFF.

[ER\\_AUTH\\_CERT\\_GENERATION\\_DISABLED](#) was added in 8.0.2.

- Error number: [MY-010307](#); Symbol: [ER\\_AUTH\\_RSA\\_CONF\\_PREVENTS\\_KEY\\_GENERATION](#); SQLSTATE: [HY000](#)

Message: Skipping generation of RSA key pair through %s as options related to RSA keys are specified.

[ER\\_AUTH\\_RSA\\_CONF\\_PREVENTS\\_KEY\\_GENERATION](#) was added in 8.0.2.

- Error number: [MY-010308](#); Symbol: [ER\\_AUTH\\_KEY\\_GENERATION\\_SKIPPED\\_PAIR\\_PRESENT](#); SQLSTATE: [HY000](#)

Message: Skipping generation of RSA key pair through %s as key files are present in data directory.

[ER\\_AUTH\\_KEY\\_GENERATION\\_SKIPPED\\_PAIR\\_PRESENT](#) was added in 8.0.2.

- Error number: [MY-010309](#); Symbol: [ER\\_AUTH\\_KEYS\\_SAVED\\_TO\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: Auto generated RSA key files through %s are placed in data directory.

[ER\\_AUTH\\_KEYS\\_SAVED\\_TO\\_DATADIR](#) was added in 8.0.2.

- Error number: [MY-010310](#); Symbol: [ER\\_AUTH\\_KEY\\_GENERATION\\_DISABLED](#); SQLSTATE: [HY000](#)

Message: Skipping generation of RSA key pair as %s is set to OFF.



---

[ER\\_AUTH\\_KEY\\_GENERATION\\_DISABLED](#) was added in 8.0.2.

- Error number: [MY-010311](#); Symbol: [ER\\_AUTHCACHE\\_PROXIES\\_PRIV\\_SKIPPED\\_NEEDS\\_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'proxies\_priv' entry '%s@%s %s@%s' ignored in --skip-name-resolve mode.

[ER\\_AUTHCACHE\\_PROXIES\\_PRIV\\_SKIPPED\\_NEEDS\\_RESOLVE](#) was added in 8.0.2.

- Error number: [MY-010312](#); Symbol: [ER\\_AUTHCACHE\\_PLUGIN\\_MISSING](#); SQLSTATE: [HY000](#)

Message: The plugin '%s' used to authenticate user '%s'@'%s' is not loaded. Nobody can currently login using this account.

[ER\\_AUTHCACHE\\_PLUGIN\\_MISSING](#) was added in 8.0.2.

- Error number: [MY-010313](#); Symbol: [ER\\_AUTHCACHE\\_PLUGIN\\_CONFIG](#); SQLSTATE: [HY000](#)

Message: The plugin '%s' is used to authenticate user '%s'@'%s', %s configured. Nobody can currently login using this account.

[ER\\_AUTHCACHE\\_PLUGIN\\_CONFIG](#) was added in 8.0.2.

- Error number: [MY-010314](#); Symbol: [ER\\_AUTHCACHE\\_ROLE\\_TABLES\\_DODGY](#); SQLSTATE: [HY000](#)

Message: Could not load mysql.role\_edges and mysql.default\_roles tables. ACL DDLs will not work unless mysql\_upgrade is executed.

[ER\\_AUTHCACHE\\_ROLE\\_TABLES\\_DODGY](#) was added in 8.0.2, removed after 8.0.4.

- Error number: [MY-010315](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_SKIPPED\\_NEEDS\\_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'user' entry '%s@%s' ignored in --skip-name-resolve mode.

[ER\\_AUTHCACHE\\_USER\\_SKIPPED\\_NEEDS\\_RESOLVE](#) was added in 8.0.2.

- Error number: [MY-010316](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_TABLE\\_DODGY](#); SQLSTATE: [HY000](#)

Message: Fatal error: Could not read the column 'authentication\_string' from table 'mysql.user'. Please perform the MySQL upgrade procedure.

[ER\\_AUTHCACHE\\_USER\\_TABLE\\_DODGY](#) was added in 8.0.2.

- Error number: [MY-010317](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_IGNORED\\_DEPRECATED\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: User entry '%s'@'%s' has a deprecated pre-4.1 password. The user will be ignored and no one can login with this user anymore.

[ER\\_AUTHCACHE\\_USER\\_IGNORED\\_DEPRECATED\\_PASSWORD](#) was added in 8.0.2.

- Error number: [MY-010318](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_IGNORED\\_NEEDS\\_PLUGIN](#); SQLSTATE: [HY000](#)

Message: User entry '%s'@'%s' has an empty plugin value. The user will be ignored and no one can login with this user anymore.

---

[ER\\_AUTHCACHE\\_USER\\_IGNORED\\_NEEDS\\_PLUGIN](#) was added in 8.0.2.

- Error number: [MY-010319](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_IGNORED\\_INVALID\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Found invalid password for user: '%s@%s'; Ignoring user

[ER\\_AUTHCACHE\\_USER\\_IGNORED\\_INVALID\\_PASSWORD](#) was added in 8.0.2.

- Error number: [MY-010320](#); Symbol: [ER\\_AUTHCACHE\\_EXPIRED\\_PASSWORD\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: 'user' entry '%s@%s' has the password ignore flag raised, but its authentication plugin doesn't support password expiration. The user id will be ignored.

[ER\\_AUTHCACHE\\_EXPIRED\\_PASSWORD\\_UNSUPPORTED](#) was added in 8.0.2.

- Error number: [MY-010321](#); Symbol: [ER\\_NO\\_SUPER\\_WITHOUT\\_USER\\_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Some of the user accounts with SUPER privileges were disabled because of empty mysql.user.plugin value. If you are upgrading from MySQL 5.6 to MySQL 5.7 it means that substitution for the empty plugin column was not possible. Probably because of pre 4.1 password hash. If your account is disabled you will need to perform the MySQL upgrade procedure. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.

[ER\\_NO\\_SUPER\\_WITHOUT\\_USER\\_PLUGIN](#) was added in 8.0.2.

- Error number: [MY-010322](#); Symbol: [ER\\_AUTHCACHE\\_DB\\_IGNORED\\_EMPTY\\_NAME](#); SQLSTATE: [HY000](#)

Message: Found an entry in the 'db' table with empty database name; Skipped

[ER\\_AUTHCACHE\\_DB\\_IGNORED\\_EMPTY\\_NAME](#) was added in 8.0.2.

- Error number: [MY-010323](#); Symbol: [ER\\_AUTHCACHE\\_DB\\_SKIPPED\\_NEEDS\\_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'db' entry '%s %s@%s' ignored in --skip-name-resolve mode.

[ER\\_AUTHCACHE\\_DB\\_SKIPPED\\_NEEDS\\_RESOLVE](#) was added in 8.0.2.

- Error number: [MY-010324](#); Symbol: [ER\\_AUTHCACHE\\_DB\\_ENTRY\\_LOWERCASED\\_REVOKE\\_WILL\\_FAIL](#); SQLSTATE: [HY000](#)

Message: 'db' entry '%s %s@%s' had database in mixed case that has been forced to lowercase because lower\_case\_table\_names is set. It will not be possible to remove this privilege using REVOKE.

[ER\\_AUTHCACHE\\_DB\\_ENTRY\\_LOWERCASED\\_REVOKE\\_WILL\\_FAIL](#) was added in 8.0.2.

- Error number: [MY-010325](#); Symbol: [ER\\_AUTHCACHE\\_TABLE\\_PROXIES\\_PRIV\\_MISSING](#); SQLSTATE: [HY000](#)

Message: The system table mysql.proxies\_priv is missing. Please perform the MySQL upgrade procedure.

[ER\\_AUTHCACHE\\_TABLE\\_PROXIES\\_PRIV\\_MISSING](#) was added in 8.0.2.

- 
- Error number: `MY-010326`; Symbol: `ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES`; SQLSTATE: `HY000`  
Message: Fatal error: Can't open and lock privilege tables: %s  
`ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES` was added in 8.0.2.
  - Error number: `MY-010327`; Symbol: `ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM`; SQLSTATE: `HY000`  
Message: Fatal: can't initialize grant subsystem - '%s'  
`ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM` was added in 8.0.2.
  - Error number: `MY-010328`; Symbol: `ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE`; SQLSTATE: `HY000`  
Message: 'procs\_priv' entry '%s %s@%' ignored in --skip-name-resolve mode.  
`ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE` was added in 8.0.2.
  - Error number: `MY-010329`; Symbol: `ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROUTINE_TYPE`; SQLSTATE: `HY000`  
Message: 'procs\_priv' entry '%s' ignored, bad routine type  
`ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROUTINE_TYPE` was added in 8.0.2.
  - Error number: `MY-010330`; Symbol: `ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE`; SQLSTATE: `HY000`  
Message: 'tables\_priv' entry '%s %s@%' ignored in --skip-name-resolve mode.  
`ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE` was added in 8.0.2.
  - Error number: `MY-010331`; Symbol: `ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCOMPLETE`; SQLSTATE: `HY000`  
Message: Failed to add %s in extra\_users. Binary log entry may miss some of the users.  
`ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCOMPLETE` was added in 8.0.2.
  - Error number: `MY-010332`; Symbol: `ER_DD_SCHEMA_NOT_FOUND`; SQLSTATE: `HY000`  
Message: Unable to start server. The data dictionary schema '%s' does not exist.  
`ER_DD_SCHEMA_NOT_FOUND` was added in 8.0.2.
  - Error number: `MY-010333`; Symbol: `ER_DD_TABLE_NOT_FOUND`; SQLSTATE: `HY000`  
Message: Unable to start server. The data dictionary table '%s' does not exist.  
`ER_DD_TABLE_NOT_FOUND` was added in 8.0.2.
  - Error number: `MY-010334`; Symbol: `ER_DD_SE_INIT_FAILED`; SQLSTATE: `HY000`  
Message: Failed to initialize DD Storage Engine  
`ER_DD_SE_INIT_FAILED` was added in 8.0.2.

- 
- Error number: [MY-010335](#); Symbol: [ER\\_DD\\_ABORTING\\_PARTIAL\\_UPGRADE](#); SQLSTATE: [HY000](#)  
Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.  
[ER\\_DD\\_ABORTING\\_PARTIAL\\_UPGRADE](#) was added in 8.0.2.
  - Error number: [MY-010336](#); Symbol: [ER\\_DD\\_FRM\\_EXISTS\\_FOR\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Found .frm file with same name as one of the Dictionary Tables.  
[ER\\_DD\\_FRM\\_EXISTS\\_FOR\\_TABLE](#) was added in 8.0.2.
  - Error number: [MY-010337](#); Symbol: [ER\\_DD\\_CREATED\\_FOR\\_UPGRADE](#); SQLSTATE: [HY000](#)  
Message: Created Data Dictionary for upgrade  
[ER\\_DD\\_CREATED\\_FOR\\_UPGRADE](#) was added in 8.0.2.
  - Error number: [MY-010338](#); Symbol: [ER\\_ERRMSG\\_CANT\\_FIND\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Can't find error-message file '%s'. Check error-message file location and 'lc-messages-dir' configuration directive.  
[ER\\_ERRMSG\\_CANT\\_FIND\\_FILE](#) was added in 8.0.2.
  - Error number: [MY-010339](#); Symbol: [ER\\_ERRMSG\\_LOADING\\_55\\_STYLE](#); SQLSTATE: [HY000](#)  
Message: Using pre 5.5 semantics to load error messages from %s. If this is not intended, refer to the documentation for valid usage of --lc-messages-dir and --language parameters.  
[ER\\_ERRMSG\\_LOADING\\_55\\_STYLE](#) was added in 8.0.2.
  - Error number: [MY-010340](#); Symbol: [ER\\_ERRMSG\\_MISSING\\_IN\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Error message file '%s' had only %d error messages, but it should contain at least %d error messages. Check that the above file is the right version for this program!  
[ER\\_ERRMSG\\_MISSING\\_IN\\_FILE](#) was added in 8.0.2.
  - Error number: [MY-010341](#); Symbol: [ER\\_ERRMSG\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Not enough memory for messagefile '%s'  
[ER\\_ERRMSG\\_OOM](#) was added in 8.0.2.
  - Error number: [MY-010342](#); Symbol: [ER\\_ERRMSG\\_CANT\\_READ](#); SQLSTATE: [HY000](#)  
Message: Can't read from messagefile '%s'  
[ER\\_ERRMSG\\_CANT\\_READ](#) was added in 8.0.2.
  - Error number: [MY-010343](#); Symbol: [ER\\_TABLE\\_INCOMPATIBLE\\_DECIMAL\\_FIELD](#); SQLSTATE: [HY000](#)  
Message: Found incompatible DECIMAL field '%s' in %s; Please do "ALTER TABLE ` %s ` FORCE" to fix it!  
[ER\\_TABLE\\_INCOMPATIBLE\\_DECIMAL\\_FIELD](#) was added in 8.0.2.

- 
- Error number: [MY-010344](#); Symbol: [ER\\_TABLE\\_INCOMPATIBLE\\_YEAR\\_FIELD](#); SQLSTATE: [HY000](#)  
Message: Found incompatible YEAR(x) field '%s' in %s; Please do "ALTER TABLE ` %s ` FORCE" to fix it!  
[ER\\_TABLE\\_INCOMPATIBLE\\_YEAR\\_FIELD](#) was added in 8.0.2.
  - Error number: [MY-010345](#); Symbol: [ER\\_INVALID\\_CHARSET\\_AND\\_DEFAULT\\_IS\\_MB](#); SQLSTATE: [HY000](#)  
Message: '%s' had no or invalid character set, and default character set is multi-byte, so character column sizes may have changed  
[ER\\_INVALID\\_CHARSET\\_AND\\_DEFAULT\\_IS\\_MB](#) was added in 8.0.2.
  - Error number: [MY-010346](#); Symbol: [ER\\_TABLE\\_WRONG\\_KEY\\_DEFINITION](#); SQLSTATE: [HY000](#)  
Message: Found wrong key definition in %s; Please do "ALTER TABLE ` %s ` FORCE " to fix it!  
[ER\\_TABLE\\_WRONG\\_KEY\\_DEFINITION](#) was added in 8.0.2.
  - Error number: [MY-010347](#); Symbol: [ER\\_CANT\\_OPEN\\_FRM\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Unable to open file %s  
[ER\\_CANT\\_OPEN\\_FRM\\_FILE](#) was added in 8.0.2.
  - Error number: [MY-010348](#); Symbol: [ER\\_CANT\\_READ\\_FRM\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Error in reading file %s  
[ER\\_CANT\\_READ\\_FRM\\_FILE](#) was added in 8.0.2.
  - Error number: [MY-010349](#); Symbol: [ER\\_TABLE\\_CREATED\\_WITH\\_DIFFERENT\\_VERSION](#); SQLSTATE: [HY000](#)  
Message: Table '%s' was created with a different version of MySQL and cannot be read  
[ER\\_TABLE\\_CREATED\\_WITH\\_DIFFERENT\\_VERSION](#) was added in 8.0.2.
  - Error number: [MY-010350](#); Symbol: [ER\\_VIEW\\_UNPARSABLE](#); SQLSTATE: [HY000](#)  
Message: Unable to read view %s  
[ER\\_VIEW\\_UNPARSABLE](#) was added in 8.0.2.
  - Error number: [MY-010351](#); Symbol: [ER\\_FILE\\_TYPE\\_UNKNOWN](#); SQLSTATE: [HY000](#)  
Message: File %s has unknown type in its header.  
[ER\\_FILE\\_TYPE\\_UNKNOWN](#) was added in 8.0.2.
  - Error number: [MY-010352](#); Symbol: [ER\\_INVALID\\_INFO\\_IN\\_FRM](#); SQLSTATE: [HY000](#)  
Message: Incorrect information in file %s  
[ER\\_INVALID\\_INFO\\_IN\\_FRM](#) was added in 8.0.2.
  - Error number: [MY-010353](#); Symbol: [ER\\_CANT\\_OPEN\\_AND\\_LOCK\\_PRIVILEGE\\_TABLES](#); SQLSTATE: [HY000](#)

---

Message: Can't open and lock privilege tables: %s

[ER\\_CANT\\_OPEN\\_AND\\_LOCK\\_PRIVILEGE\\_TABLES](#) was added in 8.0.2.

- Error number: MY-010354; Symbol:

[ER\\_AUDIT\\_PLUGIN\\_DOES\\_NOT\\_SUPPORT\\_AUDIT\\_AUTH\\_EVENTS](#); SQLSTATE: HY000

Message: Plugin '%s' cannot subscribe to MYSQL\_AUDIT\_AUTHORIZATION events. Currently not supported.

[ER\\_AUDIT\\_PLUGIN\\_DOES\\_NOT\\_SUPPORT\\_AUDIT\\_AUTH\\_EVENTS](#) was added in 8.0.2.

- Error number: MY-010355; Symbol: [ER\\_AUDIT\\_PLUGIN\\_HAS\\_INVALID\\_DATA](#); SQLSTATE: HY000

Message: Plugin '%s' has invalid data.

[ER\\_AUDIT\\_PLUGIN\\_HAS\\_INVALID\\_DATA](#) was added in 8.0.2.

- Error number: MY-010356; Symbol: [ER\\_TZ\\_OOM\\_INITIALIZING\\_TIME\\_ZONES](#); SQLSTATE: HY000

Message: Fatal error: OOM while initializing time zones

[ER\\_TZ\\_OOM\\_INITIALIZING\\_TIME\\_ZONES](#) was added in 8.0.2.

- Error number: MY-010357; Symbol: [ER\\_TZ\\_CANT\\_OPEN\\_AND\\_LOCK\\_TIME\\_ZONE\\_TABLE](#); SQLSTATE: HY000

Message: Can't open and lock time zone table: %s trying to live without them

[ER\\_TZ\\_CANT\\_OPEN\\_AND\\_LOCK\\_TIME\\_ZONE\\_TABLE](#) was added in 8.0.2.

- Error number: MY-010358; Symbol: [ER\\_TZ\\_OOM\\_LOADING\\_LEAP\\_SECOND\\_TABLE](#); SQLSTATE: HY000

Message: Fatal error: Out of memory while loading mysql.time\_zone\_leap\_second table

[ER\\_TZ\\_OOM\\_LOADING\\_LEAP\\_SECOND\\_TABLE](#) was added in 8.0.2.

- Error number: MY-010359; Symbol: [ER\\_TZ\\_TOO\\_MANY\\_LEAPS\\_IN\\_LEAP\\_SECOND\\_TABLE](#); SQLSTATE: HY000

Message: Fatal error: While loading mysql.time\_zone\_leap\_second table: too much leaps

[ER\\_TZ\\_TOO\\_MANY\\_LEAPS\\_IN\\_LEAP\\_SECOND\\_TABLE](#) was added in 8.0.2.

- Error number: MY-010360; Symbol: [ER\\_TZ\\_ERROR\\_LOADING\\_LEAP\\_SECOND\\_TABLE](#); SQLSTATE: HY000

Message: Fatal error: Error while loading mysql.time\_zone\_leap\_second table

[ER\\_TZ\\_ERROR\\_LOADING\\_LEAP\\_SECOND\\_TABLE](#) was added in 8.0.2.

- Error number: MY-010361; Symbol: [ER\\_TZ\\_UNKNOWN\\_OR\\_ILLEGAL\\_DEFAULT\\_TIME\\_ZONE](#); SQLSTATE: HY000

Message: Fatal error: Illegal or unknown default time zone '%s'

[ER\\_TZ\\_UNKNOWN\\_OR\\_ILLEGAL\\_DEFAULT\\_TIME\\_ZONE](#) was added in 8.0.2.

- 
- Error number: `MY-010362`; Symbol: `ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE`; SQLSTATE: `HY000`  
  
Message: Can't find description of time zone '%.s'  
  
`ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE` was added in 8.0.2.
  - Error number: `MY-010363`; Symbol: `ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID`; SQLSTATE: `HY000`  
  
Message: Can't find description of time zone '%u'  
  
`ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID` was added in 8.0.2.
  - Error number: `MY-010364`; Symbol: `ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE`; SQLSTATE: `HY000`  
  
Message: Error while loading time zone description from mysql.time\_zone\_transition\_type table: too big transition type id  
  
`ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE` was added in 8.0.2.
  - Error number: `MY-010365`; Symbol: `ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEED_SPACE`; SQLSTATE: `HY000`  
  
Message: Error while loading time zone description from mysql.time\_zone\_transition\_type table: not enough room for abbreviations  
  
`ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEED_SPACE` was added in 8.0.2.
  - Error number: `MY-010366`; Symbol: `ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR`; SQLSTATE: `HY000`  
  
Message: Error while loading time zone description from mysql.time\_zone\_transition\_type table  
  
`ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR` was added in 8.0.2.
  - Error number: `MY-010367`; Symbol: `ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS`; SQLSTATE: `HY000`  
  
Message: Error while loading time zone description from mysql.time\_zone\_transition table: too much transitions  
  
`ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS` was added in 8.0.2.
  - Error number: `MY-010368`; Symbol: `ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE`; SQLSTATE: `HY000`  
  
Message: Error while loading time zone description from mysql.time\_zone\_transition table: bad transition type id  
  
`ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE` was added in 8.0.2.
  - Error number: `MY-010369`; Symbol: `ER_TZ_TRANSITION_TABLE_LOAD_ERROR`; SQLSTATE: `HY000`  
  
Message: Error while loading time zone description from mysql.time\_zone\_transition table  
  
`ER_TZ_TRANSITION_TABLE_LOAD_ERROR` was added in 8.0.2.

- 
- Error number: `MY-010370`; Symbol: `ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE`; SQLSTATE: `HY000`  
Message: loading time zone without transition types  
`ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE` was added in 8.0.2.
  - Error number: `MY-010371`; Symbol: `ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION`; SQLSTATE: `HY000`  
Message: Out of memory while loading time zone description  
`ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION` was added in 8.0.2.
  - Error number: `MY-010372`; Symbol: `ER_TZ_CANT_BUILD_MKTIME_MAP`; SQLSTATE: `HY000`  
Message: Unable to build mktime map for time zone  
`ER_TZ_CANT_BUILD_MKTIME_MAP` was added in 8.0.2.
  - Error number: `MY-010373`; Symbol: `ER_TZ_OOM_WHILE_LOADING_TIME_ZONE`; SQLSTATE: `HY000`  
Message: Out of memory while loading time zone  
`ER_TZ_OOM_WHILE_LOADING_TIME_ZONE` was added in 8.0.2.
  - Error number: `MY-010374`; Symbol: `ER_TZ_OOM_WHILE_SETTING_TIME_ZONE`; SQLSTATE: `HY000`  
Message: Fatal error: Out of memory while setting new time zone  
`ER_TZ_OOM_WHILE_SETTING_TIME_ZONE` was added in 8.0.2.
  - Error number: `MY-010375`; Symbol: `ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_CONDITION_BAD`; SQLSTATE: `HY000`  
Message: Slave SQL thread is stopped because UNTIL condition is bad(%s:%llu).  
`ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_CONDITION_BAD` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010375`; Symbol: `ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION_BAD`; SQLSTATE: `HY000`  
Message: Replica SQL thread is stopped because UNTIL condition is bad(%s:%llu).  
`ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION_BAD` was added in 8.0.33.
  - Error number: `MY-010376`; Symbol: `ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED`; SQLSTATE: `HY000`  
Message: Slave SQL thread stopped because it reached its UNTIL position %llu  
`ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010376`; Symbol: `ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED`; SQLSTATE: `HY000`  
Message: Replica SQL thread stopped because it reached its UNTIL position %llu



---

[ER\\_REPLICA\\_SQL\\_THREAD\\_STOPPED\\_UNTIL\\_POSITION\\_REACHED](#) was added in 8.0.33.

- Error number: [MY-010377](#); Symbol:

[ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_BEFORE\\_GTIDS\\_ALREADY\\_APPLIED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread stopped because UNTIL SQL\_BEFORE\_GTIDS %s is already applied

[ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_BEFORE\\_GTIDS\\_ALREADY\\_APPLIED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010377](#); Symbol:

[ER\\_REPLICA\\_SQL\\_THREAD\\_STOPPED\\_BEFORE\\_GTIDS\\_ALREADY\\_APPLIED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped because UNTIL SQL\_BEFORE\_GTIDS %s is already applied

[ER\\_REPLICA\\_SQL\\_THREAD\\_STOPPED\\_BEFORE\\_GTIDS\\_ALREADY\\_APPLIED](#) was added in 8.0.33.

- Error number: [MY-010378](#); Symbol: [ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_BEFORE\\_GTIDS\\_REACHED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread stopped because it reached UNTIL SQL\_BEFORE\_GTIDS %s

[ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_BEFORE\\_GTIDS\\_REACHED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010378](#); Symbol:

[ER\\_REPLICA\\_SQL\\_THREAD\\_STOPPED\\_BEFORE\\_GTIDS\\_REACHED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped because it reached UNTIL SQL\_BEFORE\_GTIDS %s

[ER\\_REPLICA\\_SQL\\_THREAD\\_STOPPED\\_BEFORE\\_GTIDS\\_REACHED](#) was added in 8.0.33.

- Error number: [MY-010379](#); Symbol: [ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_AFTER\\_GTIDS\\_REACHED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread stopped because it reached UNTIL SQL\_AFTER\_GTIDS %s

[ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_AFTER\\_GTIDS\\_REACHED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010379](#); Symbol: [ER\\_REPLICA\\_SQL\\_THREAD\\_STOPPED\\_AFTER\\_GTIDS\\_REACHED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped because it reached UNTIL SQL\_AFTER\_GTIDS %s

[ER\\_REPLICA\\_SQL\\_THREAD\\_STOPPED\\_AFTER\\_GTIDS\\_REACHED](#) was added in 8.0.33.

- Error number: [MY-010380](#); Symbol: [ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_GAP\\_TRX\\_PROCESSED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread stopped according to UNTIL SQL\_AFTER\_MTS\_GAPS as it has processed all gap transactions left from the previous slave session.

[ER\\_SLAVE\\_SQL\\_THREAD\\_STOPPED\\_GAP\\_TRX\\_PROCESSED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010380](#); Symbol: [ER\\_REPLICA\\_SQL\\_THREAD\\_STOPPED\\_GAP\\_TRX\\_PROCESSED](#); SQLSTATE: [HY000](#)

---

Message: Replica SQL thread stopped according to UNTIL SQL\_AFTER\_MTS\_GAPS as it has processed all gap transactions left from the previous replica session.

`ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED` was added in 8.0.33.

- Error number: `MY-010381`; Symbol: `ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED`; SQLSTATE: `HY000`

Message: Group Replication plugin is not installed.

`ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED` was added in 8.0.2.

- Error number: `MY-010382`; Symbol: `ER_GTID_ALREADY_ADDED_BY_USER`; SQLSTATE: `HY000`

Message: The transaction owned GTID is already in the %s table, which is caused by an explicit modifying from user client.

`ER_GTID_ALREADY_ADDED_BY_USER` was added in 8.0.2.

- Error number: `MY-010383`; Symbol: `ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE`; SQLSTATE: `HY000`

Message: Failed to delete the row: '%s' from the `gtid_executed` table.

`ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE` was added in 8.0.2.

- Error number: `MY-010384`; Symbol: `ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE`; SQLSTATE: `HY000`

Message: Failed to compress the `gtid_executed` table.

`ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE` was added in 8.0.2.

- Error number: `MY-010385`; Symbol: `ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_OOM`; SQLSTATE: `HY000`

Message: Failed to compress the `gtid_executed` table, because it is failed to allocate the THD.

`ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_OOM` was added in 8.0.2.

- Error number: `MY-010386`; Symbol: `ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_COMPRESSION`; SQLSTATE: `HY000`

Message: Failed to initialize thread attribute when creating compression thread.

`ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_COMPRESSION` was added in 8.0.2.

- Error number: `MY-010387`; Symbol: `ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THREAD`; SQLSTATE: `HY000`

Message: Can not create thread to compress `gtid_executed` table (errno= %d)

`ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THREAD` was added in 8.0.2.

- Error number: `MY-010388`; Symbol: `ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREAD`; SQLSTATE: `HY000`

Message: Could not join `gtid_executed` table compression thread. error:%d

---

[ER\\_FAILED\\_TO\\_JOIN\\_GTID\\_TABLE\\_COMPRESSION\\_THREAD](#) was added in 8.0.2.

- Error number: [MY-010389](#); Symbol: [ER\\_NPIPE\\_FAILED\\_TO\\_INIT\\_SECURITY\\_DESCRIPTOR](#); SQLSTATE: [HY000](#)

Message: Can't start server : Initialize security descriptor: %s

[ER\\_NPIPE\\_FAILED\\_TO\\_INIT\\_SECURITY\\_DESCRIPTOR](#) was added in 8.0.2.

- Error number: [MY-010390](#); Symbol: [ER\\_NPIPE\\_FAILED\\_TO\\_SET\\_SECURITY\\_DESCRIPTOR](#); SQLSTATE: [HY000](#)

Message: Can't start server : Set security descriptor: %s

[ER\\_NPIPE\\_FAILED\\_TO\\_SET\\_SECURITY\\_DESCRIPTOR](#) was added in 8.0.2.

- Error number: [MY-010391](#); Symbol: [ER\\_NPIPE\\_PIPE\\_ALREADY\\_IN\\_USE](#); SQLSTATE: [HY000](#)

Message: Can't start server : Named Pipe "%s" already in use.

[ER\\_NPIPE\\_PIPE\\_ALREADY\\_IN\\_USE](#) was added in 8.0.2.

- Error number: [MY-010392](#); Symbol: [ER\\_NDB\\_SLAVE\\_SAW\\_EPOCH\\_LOWER\\_THAN\\_PREVIOUS\\_ON\\_START](#); SQLSTATE: [HY000](#)

Message: NDB Slave : At SQL thread start applying epoch %llu/%llu (%llu) from Master ServerId %u which is lower than previously applied epoch %llu/%llu (%llu). Group Master Log : %s Group Master Log Pos : %llu. Check slave positioning.

[ER\\_NDB\\_SLAVE\\_SAW\\_EPOCH\\_LOWER\\_THAN\\_PREVIOUS\\_ON\\_START](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010393](#); Symbol: [ER\\_NDB\\_SLAVE\\_SAW\\_EPOCH\\_LOWER\\_THAN\\_PREVIOUS](#); SQLSTATE: [HY000](#)

Message: NDB Slave : SQL thread stopped as applying epoch %llu/%llu (%llu) from Master ServerId %u which is lower than previously applied epoch %llu/%llu (%llu). Group Master Log : %s Group Master Log Pos : %llu

[ER\\_NDB\\_SLAVE\\_SAW\\_EPOCH\\_LOWER\\_THAN\\_PREVIOUS](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010394](#); Symbol: [ER\\_NDB\\_SLAVE\\_SAW\\_ALREADY\\_COMMITTED\\_EPOCH](#); SQLSTATE: [HY000](#)

Message: NDB Slave : SQL thread stopped as attempted to reapply already committed epoch %llu/%llu (%llu) from server id %u. Group Master Log : %s Group Master Log Pos : %llu.

[ER\\_NDB\\_SLAVE\\_SAW\\_ALREADY\\_COMMITTED\\_EPOCH](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010395](#); Symbol: [ER\\_NDB\\_SLAVE\\_PREVIOUS\\_EPOCH\\_NOT\\_COMMITTED](#); SQLSTATE: [HY000](#)

Message: NDB Slave : SQL thread stopped as attempting to apply new epoch %llu/%llu (%llu) while lower received epoch %llu/%llu (%llu) has not been committed. Master server id : %u. Group Master Log : %s Group Master Log Pos : %llu.

[ER\\_NDB\\_SLAVE\\_PREVIOUS\\_EPOCH\\_NOT\\_COMMITTED](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: `MY-010396`; Symbol: `ER_NDB_SLAVE_MISSING_DATA_FOR_TIMESTAMP_COLUMN`; SQLSTATE: `HY000`  
Message: NDB Slave: missing data for %s timestamp column %u.  
`ER_NDB_SLAVE_MISSING_DATA_FOR_TIMESTAMP_COLUMN` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010397`; Symbol: `ER_NDB_SLAVE_LOGGING_EXCEPTIONS_TO`; SQLSTATE: `HY000`  
Message: NDB Slave: Table %s.%s logging exceptions to %s.%s  
`ER_NDB_SLAVE_LOGGING_EXCEPTIONS_TO` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010398`; Symbol: `ER_NDB_SLAVE_LOW_EPOCH_RESOLUTION`; SQLSTATE: `HY000`  
Message: NDB Slave: Table %s.%s : %s, low epoch resolution  
`ER_NDB_SLAVE_LOW_EPOCH_RESOLUTION` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010399`; Symbol: `ER_NDB_INFO_FOUND_UNEXPECTED_FIELD_TYPE`; SQLSTATE: `HY000`  
Message: Found unexpected field type %u  
`ER_NDB_INFO_FOUND_UNEXPECTED_FIELD_TYPE` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010400`; Symbol: `ER_NDB_INFO_FAILED_TO_CREATE_NDBINFO`; SQLSTATE: `HY000`  
Message: Failed to create NdbInfo  
`ER_NDB_INFO_FAILED_TO_CREATE_NDBINFO` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010401`; Symbol: `ER_NDB_INFO_FAILED_TO_INIT_NDBINFO`; SQLSTATE: `HY000`  
Message: Failed to init NdbInfo  
`ER_NDB_INFO_FAILED_TO_INIT_NDBINFO` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010402`; Symbol: `ER_NDB_CLUSTER_WRONG_NUMBER_OF_FUNCTION_ARGUMENTS`; SQLSTATE: `HY000`  
Message: `ndb_serialize_cond`: Unexpected mismatch of found and expected number of function arguments %u  
`ER_NDB_CLUSTER_WRONG_NUMBER_OF_FUNCTION_ARGUMENTS` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010403`; Symbol: `ER_NDB_CLUSTER_SCHEMA_INFO`; SQLSTATE: `HY000`  
Message: %s - %s.%s  
`ER_NDB_CLUSTER_SCHEMA_INFO` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010404`; Symbol: `ER_NDB_CLUSTER_GENERIC_MESSAGE`; SQLSTATE: `HY000`  
Message: %s  
`ER_NDB_CLUSTER_GENERIC_MESSAGE` was added in 8.0.2, removed after 8.0.13.

- 
- Error number: [MY-010405](#); Symbol: [ER\\_RPL\\_CANT\\_OPEN\\_INFO\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Info table is not ready to be used. Table '%s.%s' cannot be opened.  
[ER\\_RPL\\_CANT\\_OPEN\\_INFO\\_TABLE](#) was added in 8.0.2.
  - Error number: [MY-010406](#); Symbol: [ER\\_RPL\\_CANT\\_SCAN\\_INFO\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Info table is not ready to be used. Table '%s.%s' cannot be scanned.  
[ER\\_RPL\\_CANT\\_SCAN\\_INFO\\_TABLE](#) was added in 8.0.2.
  - Error number: [MY-010407](#); Symbol: [ER\\_RPL\\_CORRUPTED\\_INFO\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Corrupted table %s.%s. Check out table definition.  
[ER\\_RPL\\_CORRUPTED\\_INFO\\_TABLE](#) was added in 8.0.2.
  - Error number: [MY-010408](#); Symbol: [ER\\_RPL\\_CORRUPTED\\_KEYS\\_IN\\_INFO\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Info table has a problem with its key field(s). Table '%s.%s' expected field #%u to be '%s' but found '%s' instead.  
[ER\\_RPL\\_CORRUPTED\\_KEYS\\_IN\\_INFO\\_TABLE](#) was added in 8.0.2.
  - Error number: [MY-010409](#); Symbol: [ER\\_RPL\\_WORKER\\_ID\\_IS](#); SQLSTATE: [HY000](#)  
Message: Choosing worker id %lu, the following is going to be %lu  
[ER\\_RPL\\_WORKER\\_ID\\_IS](#) was added in 8.0.2.
  - Error number: [MY-010410](#); Symbol: [ER\\_RPL\\_INCONSISTENT\\_TIMESTAMPS\\_IN\\_TRX](#); SQLSTATE: [HY000](#)  
Message: Transaction is tagged with inconsistent logical timestamps: sequence\_number (%lld) <= last\_committed (%lld)  
[ER\\_RPL\\_INCONSISTENT\\_TIMESTAMPS\\_IN\\_TRX](#) was added in 8.0.2.
  - Error number: [MY-010411](#); Symbol: [ER\\_RPL\\_INCONSISTENT\\_SEQUENCE\\_NO\\_IN\\_TRX](#); SQLSTATE: [HY000](#)  
Message: Transaction's sequence number is inconsistent with that of a preceding one: sequence\_number (%lld) <= previous sequence\_number (%lld)  
[ER\\_RPL\\_INCONSISTENT\\_SEQUENCE\\_NO\\_IN\\_TRX](#) was added in 8.0.2.
  - Error number: [MY-010412](#); Symbol: [ER\\_RPL\\_CHANNELS\\_REQUIRE\\_TABLES\\_AS\\_INFO\\_REPOSITORIES](#); SQLSTATE: [HY000](#)  
Message: For the creation of replication channels the connection metadata and applier metadata repositories must be set to TABLE  
[ER\\_RPL\\_CHANNELS\\_REQUIRE\\_TABLES\\_AS\\_INFO\\_REPOSITORIES](#) was added in 8.0.2.
  - Error number: [MY-010413](#); Symbol: [ER\\_RPL\\_CHANNELS\\_REQUIRE\\_NON\\_ZERO\\_SERVER\\_ID](#); SQLSTATE: [HY000](#)
-

---

Message: For the creation of replication channels the server id must be different from 0

[ER\\_RPL\\_CHANNELS\\_REQUIRE\\_NON\\_ZERO\\_SERVER\\_ID](#) was added in 8.0.2.

- Error number: [MY-010414](#); Symbol: [ER\\_RPL\\_REPO\\_SHOULD\\_BE\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Replica: Wrong repository. Repository should be TABLE

[ER\\_RPL\\_REPO\\_SHOULD\\_BE\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010415](#); Symbol: [ER\\_RPL\\_ERROR\\_CREATING\\_MASTER\\_INFO](#); SQLSTATE: [HY000](#)

Message: Error creating master info: %s.

[ER\\_RPL\\_ERROR\\_CREATING\\_MASTER\\_INFO](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010415](#); Symbol: [ER\\_RPL\\_ERROR\\_CREATING\\_CONNECTION\\_METADATA](#); SQLSTATE: [HY000](#)

Message: Error creating connection metadata: %s.

[ER\\_RPL\\_ERROR\\_CREATING\\_CONNECTION\\_METADATA](#) was added in 8.0.33.

- Error number: [MY-010416](#); Symbol: [ER\\_RPL\\_ERROR\\_CHANGING\\_MASTER\\_INFO\\_REPO\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Error changing the type of master info's repository: %s.

[ER\\_RPL\\_ERROR\\_CHANGING\\_MASTER\\_INFO\\_REPO\\_TYPE](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010416](#); Symbol: [ER\\_RPL\\_ERROR\\_CHANGING\\_CONNECTION\\_METADATA\\_REPO\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Error changing the type of connection metadata's repository: %s.

[ER\\_RPL\\_ERROR\\_CHANGING\\_CONNECTION\\_METADATA\\_REPO\\_TYPE](#) was added in 8.0.33.

- Error number: [MY-010417](#); Symbol: [ER\\_RPL\\_CHANGING\\_RELAY\\_LOG\\_INFO\\_REPO\\_TYPE\\_FAILED\\_DUE\\_TO\\_GAPS](#); SQLSTATE: [HY000](#)

Message: It is not possible to change the type of the relay log repository because there are workers repositories with possible execution gaps. The value of --relay\_log\_info\_repository is altered to one of the found Worker repositories. The gaps have to be sorted out before resuming with the type change.

[ER\\_RPL\\_CHANGING\\_RELAY\\_LOG\\_INFO\\_REPO\\_TYPE\\_FAILED\\_DUE\\_TO\\_GAPS](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010417](#); Symbol: [ER\\_RPL\\_CHANGING\\_APPLIER\\_METADATA\\_REPO\\_TYPE\\_FAILED\\_DUE\\_TO\\_GAPS](#); SQLSTATE: [HY000](#)

Message: It is not possible to change the type of the relay log repository because there are workers repositories with possible execution gaps. The value of --relay\_log\_info\_repository is altered to one of the found Worker repositories. The gaps have to be sorted out before resuming with the type change.

[ER\\_RPL\\_CHANGING\\_APPLIER\\_METADATA\\_REPO\\_TYPE\\_FAILED\\_DUE\\_TO\\_GAPS](#) was added in 8.0.33.

- Error number: [MY-010418](#); Symbol: [ER\\_RPL\\_ERROR\\_CREATING\\_RELAY\\_LOG\\_INFO](#); SQLSTATE: [HY000](#)

---

Message: Error creating relay log info: %s.

`ER_RPL_ERROR_CREATING_RELAY_LOG_INFO` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010418`; Symbol: `ER_RPL_ERROR_CREATING_APPLIER_METADATA`; SQLSTATE: `HY000`

Message: Error creating applier metadata: %s.

`ER_RPL_ERROR_CREATING_APPLIER_METADATA` was added in 8.0.33.

- Error number: `MY-010419`; Symbol: `ER_RPL_ERROR_CHANGING_RELAY_LOG_INFO_REPO_TYPE`; SQLSTATE: `HY000`

Message: Error changing the type of relay log info's repository: %s.

`ER_RPL_ERROR_CHANGING_RELAY_LOG_INFO_REPO_TYPE` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010419`; Symbol: `ER_RPL_ERROR_CHANGING_APPLIER_METADATA_REPO_TYPE`; SQLSTATE: `HY000`

Message: Error changing the type of applier metadata's repository: %s.

`ER_RPL_ERROR_CHANGING_APPLIER_METADATA_REPO_TYPE` was added in 8.0.33.

- Error number: `MY-010420`; Symbol: `ER_RPL_FAILED_TO_DELETE_FROM_SLAVE_WORKERS_INFO_REPOSITORY`; SQLSTATE: `HY000`

Message: Could not delete from Slave Workers info repository.

`ER_RPL_FAILED_TO_DELETE_FROM_SLAVE_WORKERS_INFO_REPOSITORY` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010420`; Symbol: `ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKERS_INFO_REPOSITORY`; SQLSTATE: `HY000`

Message: Could not delete from Replica Workers info repository.

`ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKERS_INFO_REPOSITORY` was added in 8.0.33.

- Error number: `MY-010421`; Symbol: `ER_RPL_FAILED_TO_RESET_STATE_IN_SLAVE_INFO_REPOSITORY`; SQLSTATE: `HY000`

Message: Could not store the reset Slave Worker state into the slave info repository.

`ER_RPL_FAILED_TO_RESET_STATE_IN_SLAVE_INFO_REPOSITORY` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010421`; Symbol: `ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO_REPOSITORY`; SQLSTATE: `HY000`

Message: Could not store the reset Replica Worker state into the replica info repository.

`ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO_REPOSITORY` was added in 8.0.33.

- Error number: `MY-010422`; Symbol: `ER_RPL_ERROR_CHECKING_REPOSITORY`; SQLSTATE: `HY000`

Message: Error in checking %s repository info type of %s.

---

`ER_RPL_ERROR_CHECKING_REPOSITORY` was added in 8.0.2.

- Error number: `MY-010423`; Symbol: `ER_RPL_SLAVE_GENERIC_MESSAGE`; SQLSTATE: `HY000`  
Message: Slave: %s

`ER_RPL_SLAVE_GENERIC_MESSAGE` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010423`; Symbol: `ER_RPL_REPLICA_GENERIC_MESSAGE`; SQLSTATE: `HY000`  
Message: Replica: %s

`ER_RPL_REPLICA_GENERIC_MESSAGE` was added in 8.0.33.

- Error number: `MY-010424`; Symbol: `ER_RPL_SLAVE_COULD_NOT_CREATE_CHANNEL_LIST`; SQLSTATE: `HY000`  
Message: Slave: Could not create channel list

`ER_RPL_SLAVE_COULD_NOT_CREATE_CHANNEL_LIST` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010424`; Symbol: `ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_LIST`; SQLSTATE: `HY000`  
Message: Replica: Could not create channel list

`ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_LIST` was added in 8.0.33.

- Error number: `MY-010425`; Symbol: `ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORIES`; SQLSTATE: `HY000`

Message: Replica: This replica was a multisourced replica previously which is supported only by both TABLE based connection metadata and applier metadata repositories. Found one or both of the info repos to be type FILE. Set both repos to type TABLE.

`ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORIES` was added in 8.0.2.

- Error number: `MY-010426`; Symbol: `ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE`; SQLSTATE: `HY000`

Message: Slave: Failed to initialize the master info structure for channel '%s'; its record may still be present in 'mysql.slave\_master\_info' table, consider deleting it.

`ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010426`; Symbol: `ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_METADATA_STRUCTURE`; SQLSTATE: `HY000`

Message: Replica: Failed to initialize the connection metadata structure for channel '%s'; its record may still be present in the applier metadata repository, consider deleting it.

`ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_METADATA_STRUCTURE` was added in 8.0.33.

- Error number: `MY-010427`; Symbol: `ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRUCTURE`; SQLSTATE: `HY000`

Message: Failed to initialize the master info structure%s



---

`ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRUCTURE` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010427`; Symbol: `ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA_STRUCTURE`; SQLSTATE: `HY000`

Message: Failed to initialize the connection metadata structure%s

`ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA_STRUCTURE` was added in 8.0.33.

- Error number: `MY-010428`; Symbol: `ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM_MASTER_INFO`; SQLSTATE: `HY000`

Message: Slave: Failed to create a channel from master info table repository.

`ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM_MASTER_INFO` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010428`; Symbol: `ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL_FROM_CONNECTION_METADATA`; SQLSTATE: `HY000`

Message: Replica: Failed to create a channel from connection metadata repository.

`ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL_FROM_CONNECTION_METADATA` was added in 8.0.33.

- Error number: `MY-010429`; Symbol: `ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE`; SQLSTATE: `HY000`

Message: Failed to create a new info file (file '%s', errno %d)

`ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE` was added in 8.0.2.

- Error number: `MY-010430`; Symbol: `ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE`; SQLSTATE: `HY000`

Message: Failed to create a cache on info file (file '%s')

`ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE` was added in 8.0.2.

- Error number: `MY-010431`; Symbol: `ER_RPL_FAILED_TO_OPEN_INFO_FILE`; SQLSTATE: `HY000`

Message: Failed to open the existing info file (file '%s', errno %d)

`ER_RPL_FAILED_TO_OPEN_INFO_FILE` was added in 8.0.2.

- Error number: `MY-010432`; Symbol: `ER_RPL_GTID_MEMORY_FINALY_AVAILABLE`; SQLSTATE: `HY000`

Message: Server overcomes the temporary 'out of memory' in '%d' tries while allocating a new chunk of intervals for storing GTIDs.

`ER_RPL_GTID_MEMORY_FINALY_AVAILABLE` was added in 8.0.2.

- Error number: `MY-010433`; Symbol: `ER_SERVER_COST_UNKNOWN_COST_CONSTANT`; SQLSTATE: `HY000`

---

Message: Unknown cost constant "%s" in mysql.server\_cost table

[ER\\_SERVER\\_COST\\_UNKNOWN\\_COST\\_CONSTANT](#) was added in 8.0.2.

- Error number: [MY-010434](#); Symbol: [ER\\_SERVER\\_COST\\_INVALID\\_COST\\_CONSTANT](#); SQLSTATE: [HY000](#)

Message: Invalid value for cost constant "%s" in mysql.server\_cost table: %.1f

[ER\\_SERVER\\_COST\\_INVALID\\_COST\\_CONSTANT](#) was added in 8.0.2.

- Error number: [MY-010435](#); Symbol: [ER\\_ENGINE\\_COST\\_UNKNOWN\\_COST\\_CONSTANT](#); SQLSTATE: [HY000](#)

Message: Unknown cost constant "%s" in mysql.engine\_cost table

[ER\\_ENGINE\\_COST\\_UNKNOWN\\_COST\\_CONSTANT](#) was added in 8.0.2.

- Error number: [MY-010436](#); Symbol: [ER\\_ENGINE\\_COST\\_UNKNOWN\\_STORAGE\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Unknown storage engine "%s" in mysql.engine\_cost table

[ER\\_ENGINE\\_COST\\_UNKNOWN\\_STORAGE\\_ENGINE](#) was added in 8.0.2.

- Error number: [MY-010437](#); Symbol: [ER\\_ENGINE\\_COST\\_INVALID\\_DEVICE\\_TYPE\\_FOR\\_SE](#); SQLSTATE: [HY000](#)

Message: Invalid device type %d for "%s" storage engine for cost constant "%s" in mysql.engine\_cost table

[ER\\_ENGINE\\_COST\\_INVALID\\_DEVICE\\_TYPE\\_FOR\\_SE](#) was added in 8.0.2.

- Error number: [MY-010438](#); Symbol: [ER\\_ENGINE\\_COST\\_INVALID\\_CONST\\_CONSTANT\\_FOR\\_SE\\_AND\\_DEVICE](#); SQLSTATE: [HY000](#)

Message: Invalid value for cost constant "%s" for "%s" storage engine and device type %d in mysql.engine\_cost table: %.1f

[ER\\_ENGINE\\_COST\\_INVALID\\_CONST\\_CONSTANT\\_FOR\\_SE\\_AND\\_DEVICE](#) was added in 8.0.2.

- Error number: [MY-010439](#); Symbol: [ER\\_SERVER\\_COST\\_FAILED\\_TO\\_READ](#); SQLSTATE: [HY000](#)

Message: Error while reading from mysql.server\_cost table.

[ER\\_SERVER\\_COST\\_FAILED\\_TO\\_READ](#) was added in 8.0.2.

- Error number: [MY-010440](#); Symbol: [ER\\_ENGINE\\_COST\\_FAILED\\_TO\\_READ](#); SQLSTATE: [HY000](#)

Message: Error while reading from mysql.engine\_cost table.

[ER\\_ENGINE\\_COST\\_FAILED\\_TO\\_READ](#) was added in 8.0.2.

- 
- Error number: `MY-010441`; Symbol: `ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES`; SQLSTATE: `HY000`  
Message: Failed to open optimizer cost constant tables  
`ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES` was added in 8.0.2.
  - Error number: `MY-010442`; Symbol: `ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM`; SQLSTATE: `HY000`  
Message: Unsupported non-ignorable event fed into the event stream.  
`ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM` was added in 8.0.2.
  - Error number: `MY-010443`; Symbol: `ER_RPL_GTID_LOG_EVENT_IN_STREAM`; SQLSTATE: `HY000`  
Message: `GTID_LOG_EVENT` or `ANONYMOUS_GTID_LOG_EVENT` is not expected in an event stream %s.  
`ER_RPL_GTID_LOG_EVENT_IN_STREAM` was added in 8.0.2.
  - Error number: `MY-010444`; Symbol: `ER_RPL_UNEXPECTED_BEGIN_IN_STREAM`; SQLSTATE: `HY000`  
Message: `QUERY(BEGIN)` is not expected in an event stream in the middle of a %s.  
`ER_RPL_UNEXPECTED_BEGIN_IN_STREAM` was added in 8.0.2.
  - Error number: `MY-010445`; Symbol: `ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_LOG_EVENT_IN_STREAM`; SQLSTATE: `HY000`  
Message: `QUERY(COMMIT or ROLLBACK)` or `XID_LOG_EVENT` is not expected in an event stream %s.  
`ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_LOG_EVENT_IN_STREAM` was added in 8.0.2.
  - Error number: `MY-010446`; Symbol: `ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM`; SQLSTATE: `HY000`  
Message: `QUERY(XA ROLLBACK)` is not expected in an event stream %s.  
`ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM` was added in 8.0.2.
  - Error number: `MY-010447`; Symbol: `ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER`; SQLSTATE: `HY000`  
Message: Event Scheduler: [%s].[%s.%s] execution failed, failed to authenticate the user.  
`ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER` was added in 8.0.2.
  - Error number: `MY-010448`; Symbol: `ER_EVENT_EXECUTION_FAILED_USER_LOST_EVENT_PRIVILEGE`; SQLSTATE: `HY000`  
Message: Event Scheduler: [%s].[%s.%s] execution failed, user no longer has `EVENT` privilege.  
`ER_EVENT_EXECUTION_FAILED_USER_LOST_EVENT_PRIVILEGE` was added in 8.0.2.
  - Error number: `MY-010449`; Symbol: `ER_EVENT_ERROR_DURING_COMPILATION`; SQLSTATE: `HY000`  
Message: Event Scheduler: %serror during compilation of %s.%s
-

---

`ER_EVENT_ERROR_DURING_COMPILATION` was added in 8.0.2.

- Error number: `MY-010450`; Symbol: `ER_EVENT_DROPPING`; SQLSTATE: `HY000`

Message: Event Scheduler: Dropping %s.%s

`ER_EVENT_DROPPING` was added in 8.0.2.

- Error number: `MY-010451`; Symbol: `ER_NDB_SCHEMA_GENERIC_MESSAGE`; SQLSTATE: `HY000`

Message: Ndb schema[%s.%s]: %s

`ER_NDB_SCHEMA_GENERIC_MESSAGE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010452`; Symbol: `ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR`; SQLSTATE: `HY000`

Message: In RBR mode, Replica received incompatible DECIMAL field (old-style decimal field) from Source while creating conversion table. Please consider changing datatype on Source to new style decimal by executing ALTER command for column Name: %s.%s.%s.

`ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR` was added in 8.0.2.

- Error number: `MY-010453`; Symbol: `ER_INIT_ROOT_WITHOUT_PASSWORD`; SQLSTATE: `HY000`

Message: root@localhost is created with an empty password ! Please consider switching off the --initialize-insecure option.

`ER_INIT_ROOT_WITHOUT_PASSWORD` was added in 8.0.2.

- Error number: `MY-010454`; Symbol: `ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT`; SQLSTATE: `HY000`

Message: A temporary password is generated for root@localhost: %s

`ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT` was added in 8.0.2.

- Error number: `MY-010455`; Symbol: `ER_INIT_CANT_OPEN_BOOTSTRAP_FILE`; SQLSTATE: `HY000`

Message: Failed to open the bootstrap file %s

`ER_INIT_CANT_OPEN_BOOTSTRAP_FILE` was added in 8.0.2.

- Error number: `MY-010456`; Symbol: `ER_INIT_BOOTSTRAP_COMPLETE`; SQLSTATE: `HY000`

Message: Bootstrapping complete

`ER_INIT_BOOTSTRAP_COMPLETE` was added in 8.0.2.

- Error number: `MY-010457`; Symbol: `ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE`; SQLSTATE: `HY000`

Message: --initialize specified but the data directory has files in it. Aborting.

`ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE` was added in 8.0.2.

- Error number: `MY-010458`; Symbol: `ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE`; SQLSTATE: `HY000`

Message: --initialize specified on an existing data directory.

---

`ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE` was added in 8.0.2.

- Error number: `MY-010459`; Symbol: `ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE`; SQLSTATE: `HY000`

Message: --initialize specified but the data directory exists and the path is too long. Aborting.

`ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE` was added in 8.0.2.

- Error number: `MY-010460`; Symbol: `ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE`; SQLSTATE: `HY000`

Message: --initialize specified but the data directory exists and is not writable. Aborting.

`ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE` was added in 8.0.2.

- Error number: `MY-010461`; Symbol: `ER_INIT_CREATING_DD`; SQLSTATE: `HY000`

Message: Creating the data directory %s

`ER_INIT_CREATING_DD` was added in 8.0.2.

- Error number: `MY-010462`; Symbol: `ER_RPL_BINLOG_STARTING_DUMP`; SQLSTATE: `HY000`

Message: Start binlog\_dump to source\_thread\_id(%u) replica\_server(%u), pos(%s, %llu)

`ER_RPL_BINLOG_STARTING_DUMP` was added in 8.0.2.

- Error number: `MY-010463`; Symbol: `ER_RPL_BINLOG_MASTER_SENDS_HEARTBEAT`; SQLSTATE: `HY000`

Message: master sends heartbeat message

`ER_RPL_BINLOG_MASTER_SENDS_HEARTBEAT` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010463`; Symbol: `ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT`; SQLSTATE: `HY000`

Message: source sends heartbeat message

`ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT` was added in 8.0.33.

- Error number: `MY-010464`; Symbol: `ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO`; SQLSTATE: `HY000`

Message: the rest of heartbeat info skipped ...

`ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO` was added in 8.0.2.

- Error number: `MY-010465`; Symbol: `ER_RPL_BINLOG_MASTER_USES_CHECKSUM_AND_SLAVE_CANT`; SQLSTATE: `HY000`

Message: Master is configured to log replication events with checksum, but will not send such events to slaves that cannot process them

`ER_RPL_BINLOG_MASTER_USES_CHECKSUM_AND_SLAVE_CANT` was added in 8.0.2, removed after 8.0.32.

- 
- Error number: `MY-010465`; Symbol: `ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLICA_CANT`; SQLSTATE: `HY000`  
Message: Source is configured to log replication events with checksum, but will not send such events to replicas that cannot process them  
`ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLICA_CANT` was added in 8.0.33.
  - Error number: `MY-010466`; Symbol: `ER_NDB_QUERY_FAILED`; SQLSTATE: `HY000`  
Message: NDB: Query '%s' failed, error: %d: %s  
`ER_NDB_QUERY_FAILED` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010467`; Symbol: `ER_KILLING_THREAD`; SQLSTATE: `HY000`  
Message: Killing thread %lu  
`ER_KILLING_THREAD` was added in 8.0.2.
  - Error number: `MY-010468`; Symbol: `ER_DETACHING_SESSION_LEFT_BY_PLUGIN`; SQLSTATE: `HY000`  
Message: Plugin %s is deinitializing a thread but left a session attached. Detaching it forcefully.  
`ER_DETACHING_SESSION_LEFT_BY_PLUGIN` was added in 8.0.2.
  - Error number: `MY-010469`; Symbol: `ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN`; SQLSTATE: `HY000`  
Message: Failed to detach the session.  
`ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN` was added in 8.0.2.
  - Error number: `MY-010470`; Symbol: `ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN`; SQLSTATE: `HY000`  
Message: Closed forcefully %u session%s left opened by plugin %s  
`ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN` was added in 8.0.2.
  - Error number: `MY-010471`; Symbol: `ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS`; SQLSTATE: `HY000`  
Message: Failed to decrement the number of threads  
`ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS` was added in 8.0.2.
  - Error number: `MY-010472`; Symbol: `ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS`; SQLSTATE: `HY000`  
Message: Plugin %s did not deinitialize %u threads  
`ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS` was added in 8.0.2.

- 
- Error number: [MY-010473](#); Symbol: [ER\\_KILLED\\_THREADS\\_OF\\_PLUGIN](#); SQLSTATE: [HY000](#)  
Message: Killed %u threads of plugin %s  
[ER\\_KILLED\\_THREADS\\_OF\\_PLUGIN](#) was added in 8.0.2.
  - Error number: [MY-010474](#); Symbol: [ER\\_NDB\\_SLAVE\\_MAX\\_REPLICATED\\_EPOCH\\_UNKNOWN](#); SQLSTATE: [HY000](#)  
Message: NDB Slave : Could not determine maximum replicated epoch from %s.%s at Slave start, error %u %s  
[ER\\_NDB\\_SLAVE\\_MAX\\_REPLICATED\\_EPOCH\\_UNKNOWN](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010475](#); Symbol: [ER\\_NDB\\_SLAVE\\_MAX\\_REPLICATED\\_EPOCH\\_SET\\_TO](#); SQLSTATE: [HY000](#)  
Message: NDB Slave : MaxReplicatedEpoch set to %llu (%u/%u) at Slave start  
[ER\\_NDB\\_SLAVE\\_MAX\\_REPLICATED\\_EPOCH\\_SET\\_TO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010476](#); Symbol: [ER\\_NDB\\_NODE\\_ID\\_AND\\_MANAGEMENT\\_SERVER\\_INFO](#); SQLSTATE: [HY000](#)  
Message: NDB: NodelD is %lu, management server '%s:%lu'  
[ER\\_NDB\\_NODE\\_ID\\_AND\\_MANAGEMENT\\_SERVER\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010477](#); Symbol: [ER\\_NDB\\_DISCONNECT\\_INFO](#); SQLSTATE: [HY000](#)  
Message: tid %u: node[%u] transaction\_hint=%u, transaction\_no\_hint=%u  
[ER\\_NDB\\_DISCONNECT\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010478](#); Symbol: [ER\\_NDB\\_COLUMN\\_DEFAULTS\\_DIFFER](#); SQLSTATE: [HY000](#)  
Message: NDB Internal error: Default values differ for column %u, ndb\_default: %d  
[ER\\_NDB\\_COLUMN\\_DEFAULTS\\_DIFFER](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010479](#); Symbol: [ER\\_NDB\\_COLUMN\\_SHOULD\\_NOT\\_HAVE\\_NATIVE\\_DEFAULT](#); SQLSTATE: [HY000](#)  
Message: NDB Internal error: Column %u has native default, but shouldn't. Flags=%u, type=%u  
[ER\\_NDB\\_COLUMN\\_SHOULD\\_NOT\\_HAVE\\_NATIVE\\_DEFAULT](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010480](#); Symbol: [ER\\_NDB\\_FIELD\\_INFO](#); SQLSTATE: [HY000](#)  
Message: field[ name: '%s', type: %u, real\_type: %u, flags: 0x%x, is\_null: %d]  
[ER\\_NDB\\_FIELD\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010481](#); Symbol: [ER\\_NDB\\_COLUMN\\_INFO](#); SQLSTATE: [HY000](#)  
Message: ndbCol[name: '%s', type: %u, column\_no: %d, nullable: %d]  
[ER\\_NDB\\_COLUMN\\_INFO](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: `MY-010482`; Symbol: `ER_NDB_OOM_IN_FIX_UNIQUE_INDEX_ATTR_ORDER`; SQLSTATE: `HY000`  
Message: `fix_unique_index_attr_order: my_malloc(%u) failure`  
`ER_NDB_OOM_IN_FIX_UNIQUE_INDEX_ATTR_ORDER` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010483`; Symbol: `ER_NDB_SLAVE_MALFORMED_EVENT_RECEIVED_ON_TABLE`; SQLSTATE: `HY000`  
Message: `NDB Slave : Malformed event received on table %s cannot parse. Stopping Slave.`  
`ER_NDB_SLAVE_MALFORMED_EVENT_RECEIVED_ON_TABLE` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010484`; Symbol: `ER_NDB_SLAVE_CONFLICT_FUNCTION_REQUIRES_ROLE`; SQLSTATE: `HY000`  
Message: `NDB Slave : Conflict function %s defined on table %s requires ndb_slave_conflict_role variable to be set. Stopping slave.`  
`ER_NDB_SLAVE_CONFLICT_FUNCTION_REQUIRES_ROLE` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010485`; Symbol: `ER_NDB_SLAVE_CONFLICT_DETECTION_REQUIRES_TRANSACTION_IDS`; SQLSTATE: `HY000`  
Message: `NDB Slave : Transactional conflict detection defined on table %s, but events received without transaction ids. Check --ndb-log-transaction-id setting on upstream Cluster.`  
`ER_NDB_SLAVE_CONFLICT_DETECTION_REQUIRES_TRANSACTION_IDS` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010486`; Symbol: `ER_NDB_SLAVE_BINLOG_MISSING_INFO_FOR_CONFLICT_DETECTION`; SQLSTATE: `HY000`  
Message: `NDB Slave : Binlog event on table %s missing info necessary for conflict detection. Check binlog format options on upstream cluster.`  
`ER_NDB_SLAVE_BINLOG_MISSING_INFO_FOR_CONFLICT_DETECTION` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010487`; Symbol: `ER_NDB_ERROR_IN_READAUTOINCREMENTVALUE`; SQLSTATE: `HY000`  
Message: `Error %lu in readAutoIncrementValue(): %s`  
`ER_NDB_ERROR_IN_READAUTOINCREMENTVALUE` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010488`; Symbol: `ER_NDB_FOUND_UNCOMMITTED_AUTOCOMMIT`; SQLSTATE: `HY000`  
Message: `found uncommitted autocommit+rbwr transaction, commit status: %d`  
`ER_NDB_FOUND_UNCOMMITTED_AUTOCOMMIT` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010489`; Symbol: `ER_NDB_SLAVE_TOO_MANY_RETRIES`; SQLSTATE: `HY000`  
Message: `Ndb slave retried transaction %u time(s) in vain. Giving up.`  
`ER_NDB_SLAVE_TOO_MANY_RETRIES` was added in 8.0.2, removed after 8.0.13.



- 
- Error number: [MY-010490](#); Symbol: [ER\\_NDB\\_SLAVE\\_ERROR\\_IN\\_UPDATE\\_CREATE\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Error %lu in ::update\_create\_info(): %s  
[ER\\_NDB\\_SLAVE\\_ERROR\\_IN\\_UPDATE\\_CREATE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010491](#); Symbol: [ER\\_NDB\\_SLAVE\\_CANT\\_ALLOCATE\\_TABLE\\_SHARE](#); SQLSTATE: [HY000](#)  
Message: NDB: allocating table share for %s failed  
[ER\\_NDB\\_SLAVE\\_CANT\\_ALLOCATE\\_TABLE\\_SHARE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010492](#); Symbol: [ER\\_NDB\\_BINLOG\\_ERROR\\_INFO\\_FROM\\_DA](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: (%d)%s  
[ER\\_NDB\\_BINLOG\\_ERROR\\_INFO\\_FROM\\_DA](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010493](#); Symbol: [ER\\_NDB\\_BINLOG\\_CREATE\\_TABLE\\_EVENT](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: CREATE TABLE Event: %s  
[ER\\_NDB\\_BINLOG\\_CREATE\\_TABLE\\_EVENT](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010494](#); Symbol: [ER\\_NDB\\_BINLOG\\_FAILED\\_CREATE\\_TABLE\\_EVENT\\_OPERATIONS](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: FAILED CREATE TABLE event operations. Event: %s  
[ER\\_NDB\\_BINLOG\\_FAILED\\_CREATE\\_TABLE\\_EVENT\\_OPERATIONS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010495](#); Symbol: [ER\\_NDB\\_BINLOG\\_RENAME\\_EVENT](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: RENAME Event: %s  
[ER\\_NDB\\_BINLOG\\_RENAME\\_EVENT](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010496](#); Symbol: [ER\\_NDB\\_BINLOG\\_FAILED\\_CREATE\\_EVENT\\_OPERATIONS\\_DURING\\_RENAME](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: FAILED create event operations during RENAME. Event %s  
[ER\\_NDB\\_BINLOG\\_FAILED\\_CREATE\\_EVENT\\_OPERATIONS\\_DURING\\_RENAME](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010497](#); Symbol: [ER\\_NDB\\_UNEXPECTED\\_RENAME\\_TYPE](#); SQLSTATE: [HY000](#)  
Message: Unexpected rename case detected, sql\_command: %d  
[ER\\_NDB\\_UNEXPECTED\\_RENAME\\_TYPE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010498](#); Symbol: [ER\\_NDB\\_ERROR\\_IN\\_GET\\_AUTO\\_INCREMENT](#); SQLSTATE: [HY000](#)  
Message: Error %lu in ::get\_auto\_increment(): %s  
[ER\\_NDB\\_ERROR\\_IN\\_GET\\_AUTO\\_INCREMENT](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: `MY-010499`; Symbol: `ER_NDB_CREATING_SHARE_IN_OPEN`; SQLSTATE: `HY000`  
Message: Calling `ndbcluster_create_binlog_setup(%s)` in `::open`  
`ER_NDB_CREATING_SHARE_IN_OPEN` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010500`; Symbol: `ER_NDB_TABLE_OPENED_READ_ONLY`; SQLSTATE: `HY000`  
Message: table '`%s`' opened read only  
`ER_NDB_TABLE_OPENED_READ_ONLY` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010501`; Symbol: `ER_NDB_INITIALIZE_GIVEN_CLUSTER_PLUGIN_DISABLED`; SQLSTATE: `HY000`  
Message: NDB: '--initialize' -> ndbcluster plugin disabled  
`ER_NDB_INITIALIZE_GIVEN_CLUSTER_PLUGIN_DISABLED` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010502`; Symbol: `ER_NDB_BINLOG_FORMAT_CHANGED_FROM_STMT_TO_MIXED`; SQLSTATE: `HY000`  
Message: NDB: Changed global value of `binlog_format` from `STATEMENT` to `MIXED`  
`ER_NDB_BINLOG_FORMAT_CHANGED_FROM_STMT_TO_MIXED` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010503`; Symbol: `ER_NDB_TRAILING_SHARE_RELEASED_BY_CLOSE_CACHED_TABLES`; SQLSTATE: `HY000`  
Message: NDB\_SHARE: trailing share `%s`, released by `close_cached_tables`  
`ER_NDB_TRAILING_SHARE_RELEASED_BY_CLOSE_CACHED_TABLES` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010504`; Symbol: `ER_NDB_SHARE_ALREADY_EXISTS`; SQLSTATE: `HY000`  
Message: NDB\_SHARE: `%s` already exists `use_count=%d`. Moving away for safety, but possible memleak.  
`ER_NDB_SHARE_ALREADY_EXISTS` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010505`; Symbol: `ER_NDB_HANDLE_TRAILING_SHARE_INFO`; SQLSTATE: `HY000`  
Message: `handle_trailing_share: %s use_count: %u`  
`ER_NDB_HANDLE_TRAILING_SHARE_INFO` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010506`; Symbol: `ER_NDB_CLUSTER_GET_SHARE_INFO`; SQLSTATE: `HY000`  
Message: `ndbcluster_get_share: %s use_count: %u`  
`ER_NDB_CLUSTER_GET_SHARE_INFO` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010507`; Symbol: `ER_NDB_CLUSTER_REAL_FREE_SHARE_INFO`; SQLSTATE: `HY000`  
Message: `ndbcluster_real_free_share: %s use_count: %u`

---

[ER\\_NDB\\_CLUSTER\\_REAL\\_FREE\\_SHARE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010508](#); Symbol: [ER\\_NDB\\_CLUSTER\\_REAL\\_FREE\\_SHARE\\_DROP\\_FAILED](#); SQLSTATE: [HY000](#)

Message: `ndbcluster_real_free_share: %s, still open - ignored 'free' (leaked?)`

[ER\\_NDB\\_CLUSTER\\_REAL\\_FREE\\_SHARE\\_DROP\\_FAILED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010509](#); Symbol: [ER\\_NDB\\_CLUSTER\\_FREE\\_SHARE\\_INFO](#); SQLSTATE: [HY000](#)

Message: `ndbcluster_free_share: %s use_count: %u`

[ER\\_NDB\\_CLUSTER\\_FREE\\_SHARE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010510](#); Symbol: [ER\\_NDB\\_CLUSTER\\_MARK\\_SHARE\\_DROPPED\\_INFO](#); SQLSTATE: [HY000](#)

Message: `ndbcluster_mark_share_dropped: %s use_count: %u`

[ER\\_NDB\\_CLUSTER\\_MARK\\_SHARE\\_DROPPED\\_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010511](#); Symbol: [ER\\_NDB\\_CLUSTER\\_MARK\\_SHARE\\_DROPPED\\_DESTROYING\\_SHARE](#); SQLSTATE: [HY000](#)

Message: `ndbcluster_mark_share_dropped: destroys share %s`

[ER\\_NDB\\_CLUSTER\\_MARK\\_SHARE\\_DROPPED\\_DESTROYING\\_SHARE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010512](#); Symbol: [ER\\_NDB\\_CLUSTER\\_OOM\\_THD\\_NDB](#); SQLSTATE: [HY000](#)

Message: `Could not allocate Thd_ndb object`

[ER\\_NDB\\_CLUSTER\\_OOM\\_THD\\_NDB](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010513](#); Symbol: [ER\\_NDB\\_BINLOG\\_NDB\\_TABLES\\_INITIALLY\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)

Message: `NDB Binlog: Ndb tables initially read only.`

[ER\\_NDB\\_BINLOG\\_NDB\\_TABLES\\_INITIALLY\\_READ\\_ONLY](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010514](#); Symbol: [ER\\_NDB\\_UTIL\\_THREAD\\_OOM](#); SQLSTATE: [HY000](#)

Message: `ndb util thread: malloc failure, query cache not maintained properly`

[ER\\_NDB\\_UTIL\\_THREAD\\_OOM](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010515](#); Symbol: [ER\\_NDB\\_ILLEGAL\\_VALUE\\_FOR\\_NDB\\_RECV\\_THREAD\\_CPU\\_MASK](#); SQLSTATE: [HY000](#)

Message: `Trying to set ndb_recv_thread_cpu_mask to illegal value = %s, ignored`

[ER\\_NDB\\_ILLEGAL\\_VALUE\\_FOR\\_NDB\\_RECV\\_THREAD\\_CPU\\_MASK](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: `MY-010516`; Symbol: `ER_NDB_TOO_MANY_CPUS_IN_NDB_RECV_THREAD_CPU_MASK`; SQLSTATE: `HY000`  
  
Message: Trying to set too many CPU's in `ndb_recv_thread_cpu_mask`, ignored this variable, erroneous value = %s  
  
`ER_NDB_TOO_MANY_CPUS_IN_NDB_RECV_THREAD_CPU_MASK` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010517`; Symbol: `ER_DEBUG_CHECK_SHARES_OPEN`; SQLSTATE: `HY000`  
  
Message: `debug_check_shares` open:  
  
`ER_DEBUG_CHECK_SHARES_OPEN` was added in 8.0.2.
  - Error number: `MY-010518`; Symbol: `ER_DEBUG_CHECK_SHARES_INFO`; SQLSTATE: `HY000`  
  
Message: %s.%s: state: %s(%u) use\_count: %u  
  
`ER_DEBUG_CHECK_SHARES_INFO` was added in 8.0.2.
  - Error number: `MY-010519`; Symbol: `ER_DEBUG_CHECK_SHARES_DROPPED`; SQLSTATE: `HY000`  
  
Message: `debug_check_shares` dropped:  
  
`ER_DEBUG_CHECK_SHARES_DROPPED` was added in 8.0.2.
  - Error number: `MY-010520`; Symbol: `ER_INVALID_OR_OLD_TABLE_OR_DB_NAME`; SQLSTATE: `HY000`  
  
Message: Invalid (old?) table or database name '%s'  
  
`ER_INVALID_OR_OLD_TABLE_OR_DB_NAME` was added in 8.0.2.
  - Error number: `MY-010521`; Symbol: `ER_TC_RECOVERING_AFTER_CRASH_USING`; SQLSTATE: `HY000`  
  
Message: Recovering after a crash using %s  
  
`ER_TC_RECOVERING_AFTER_CRASH_USING` was added in 8.0.2.
  - Error number: `MY-010522`; Symbol: `ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVER`; SQLSTATE: `HY000`  
  
Message: Cannot perform automatic crash recovery when `--tc-heuristic-recover` is used  
  
`ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVER` was added in 8.0.2.
  - Error number: `MY-010523`; Symbol: `ER_TC_BAD_MAGIC_IN_TC_LOG`; SQLSTATE: `HY000`  
  
Message: Bad magic header in tc log  
  
`ER_TC_BAD_MAGIC_IN_TC_LOG` was added in 8.0.2.
  - Error number: `MY-010524`; Symbol: `ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY`; SQLSTATE: `HY000`  
  
Message: Recovery failed! You must enable exactly %d storage engines that support two-phase commit protocol  
  
`ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY` was added in 8.0.2.

- 
- Error number: `MY-010525`; Symbol: `ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS`; SQLSTATE: `HY000`  
  
Message: Crash recovery failed. Either correct the problem (if it's, for example, out of memory error) and restart, or delete tc log and start mysqld with `--tc-heuristic-recover={commit|rollback}`  
  
`ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS` was added in 8.0.2.
  - Error number: `MY-010526`; Symbol: `ER_TC_HEURISTIC_RECOVERY_MODE`; SQLSTATE: `HY000`  
  
Message: Heuristic crash recovery mode  
  
`ER_TC_HEURISTIC_RECOVERY_MODE` was added in 8.0.2.
  - Error number: `MY-010527`; Symbol: `ER_TC_HEURISTIC_RECOVERY_FAILED`; SQLSTATE: `HY000`  
  
Message: Heuristic crash recovery failed  
  
`ER_TC_HEURISTIC_RECOVERY_FAILED` was added in 8.0.2.
  - Error number: `MY-010528`; Symbol: `ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVER`; SQLSTATE: `HY000`  
  
Message: Please restart mysqld without `--tc-heuristic-recover`  
  
`ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVER` was added in 8.0.2.
  - Error number: `MY-010529`; Symbol: `ER_RPL_SLAVE_FAILED_TO_CREATE_OR_RECOVER_INFO_REPOSITORIES`; SQLSTATE: `HY000`  
  
Message: Failed to create or recover replication info repositories.  
  
`ER_RPL_SLAVE_FAILED_TO_CREATE_OR_RECOVER_INFO_REPOSITORIES` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010529`; Symbol: `ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER_INFO_REPOSITORIES`; SQLSTATE: `HY000`  
  
Message: Failed to create or recover replication info repositories.  
  
`ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER_INFO_REPOSITORIES` was added in 8.0.33.
  - Error number: `MY-010530`; Symbol: `ER_RPL_SLAVE_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF`; SQLSTATE: `HY000`  
  
Message: Detected misconfiguration: replication channel '%s' was configured with `AUTO_POSITION = 1`, but the server was started with `--gtid-mode=off`. Either reconfigure replication using `CHANGE MASTER TO MASTER_AUTO_POSITION = 0 FOR CHANNEL '%s'`, or change `GTID_MODE` to some value other than `OFF`, before starting the slave receiver thread.  
  
`ER_RPL_SLAVE_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010530`; Symbol: `ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF`; SQLSTATE: `HY000`  
  
Message: Detected misconfiguration: replication channel '%s' was configured with `AUTO_POSITION = 1`, but the server was started with `--gtid-mode=off`. Either reconfigure replication using `CHANGE`
-

---

REPLICATION SOURCE TO SOURCE\_AUTO\_POSITION = 0 FOR CHANNEL '%s', or change GTID\_MODE to some value other than OFF, before starting the replica receiver thread.

[ER\\_RPL\\_REPLICA\\_AUTO\\_POSITION\\_IS\\_1\\_AND\\_GTID\\_MODE\\_IS\\_OFF](#) was added in 8.0.33.

- Error number: [MY-010531](#); Symbol: [ER\\_RPL\\_SLAVE\\_CANT\\_START\\_SLAVE\\_FOR\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Slave: Could not start slave for channel '%s'. operation discontinued

[ER\\_RPL\\_SLAVE\\_CANT\\_START\\_SLAVE\\_FOR\\_CHANNEL](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010531](#); Symbol: [ER\\_RPL\\_REPLICA\\_CANT\\_START\\_REPLICA\\_FOR\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Replica: Could not start replica for channel '%s'. operation discontinued

[ER\\_RPL\\_REPLICA\\_CANT\\_START\\_REPLICA\\_FOR\\_CHANNEL](#) was added in 8.0.33.

- Error number: [MY-010532](#); Symbol: [ER\\_RPL\\_SLAVE\\_CANT\\_STOP\\_SLAVE\\_FOR\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Slave: Could not stop slave for channel '%s' operation discontinued

[ER\\_RPL\\_SLAVE\\_CANT\\_STOP\\_SLAVE\\_FOR\\_CHANNEL](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010532](#); Symbol: [ER\\_RPL\\_REPLICA\\_CANT\\_STOP\\_REPLICA\\_FOR\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Replica: Could not stop replica for channel '%s' operation discontinued

[ER\\_RPL\\_REPLICA\\_CANT\\_STOP\\_REPLICA\\_FOR\\_CHANNEL](#) was added in 8.0.33.

- Error number: [MY-010533](#); Symbol: [ER\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_MASTER](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: Could not locate rotate event from the master.

[ER\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_MASTER](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010533](#); Symbol: [ER\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_SOURCE](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: Could not locate rotate event from the source.

[ER\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_SOURCE](#) was added in 8.0.33.

- Error number: [MY-010534](#); Symbol: [ER\\_RPL\\_RECOVERY\\_ERROR\\_READ\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: Error reading events from relay log: %d

[ER\\_RPL\\_RECOVERY\\_ERROR\\_READ\\_RELAY\\_LOG](#) was added in 8.0.2.

- Error number: [MY-010535](#); Symbol: [ER\\_RPL\\_RECOVERY\\_ERROR\\_FREEING\\_IO\\_CACHE](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: Error while freeing IO\_CACHE object

---

`ER_RPL_RECOVERY_ERROR_FREEING_IO_CACHE` was added in 8.0.2, removed after 8.0.12.

- Error number: `MY-010536`; Symbol: `ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION_CHANNEL`; SQLSTATE: `HY000`

Message: Relay log recovery skipped for group replication channel.

`ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION_CHANNEL` was added in 8.0.2.

- Error number: `MY-010537`; Symbol: `ER_RPL_RECOVERY_ERROR`; SQLSTATE: `HY000`

Message: Error during --relay-log-recovery: %s

`ER_RPL_RECOVERY_ERROR` was added in 8.0.2.

- Error number: `MY-010538`; Symbol: `ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX`; SQLSTATE: `HY000`

Message: Error during --relay-log-recovery: Could not read relay log index file due to an IO error.

`ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX` was added in 8.0.2.

- Error number: `MY-010539`; Symbol: `ER_RPL_RECOVERY_FILE_MASTER_POS_INFO`; SQLSTATE: `HY000`

Message: Recovery from master pos %ld and file %s%. Previous relay log pos and relay log file had been set to %lld, %s respectively.

`ER_RPL_RECOVERY_FILE_MASTER_POS_INFO` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010539`; Symbol: `ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO`; SQLSTATE: `HY000`

Message: Recovery from source pos %ld and file %s%. Previous relay log pos and relay log file had been set to %lld, %s respectively.

`ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO` was added in 8.0.33.

- Error number: `MY-010540`; Symbol: `ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUIRES_POSITION`; SQLSTATE: `HY000`

Message: Error during --relay-log-recovery: `replicate_same_server_id` is in use and sql thread's positions are not initialized, hence relay log recovery cannot happen.

`ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUIRES_POSITION` was added in 8.0.2.

- Error number: `MY-010541`; Symbol: `ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR`; SQLSTATE: `HY000`

Message: MTS recovery: starting coordinator thread to fill MTS gaps.

`ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010541`; Symbol: `ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR`; SQLSTATE: `HY000`

Message: MTA recovery: starting coordinator thread to fill MTA gaps.

---

[ER\\_RPL\\_MTA\\_RECOVERY\\_STARTING\\_COORDINATOR](#) was added in 8.0.33.

- Error number: [MY-010542](#); Symbol: [ER\\_RPL\\_MTS\\_RECOVERY\\_FAILED\\_TO\\_START\\_COORDINATOR](#); SQLSTATE: [HY000](#)

Message: MTS recovery: failed to start the coordinator thread. Check the error log for additional details.

[ER\\_RPL\\_MTS\\_RECOVERY\\_FAILED\\_TO\\_START\\_COORDINATOR](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010542](#); Symbol: [ER\\_RPL\\_MTA\\_RECOVERY\\_FAILED\\_TO\\_START\\_COORDINATOR](#); SQLSTATE: [HY000](#)

Message: MTA recovery: failed to start the coordinator thread. Check the error log for additional details.

[ER\\_RPL\\_MTA\\_RECOVERY\\_FAILED\\_TO\\_START\\_COORDINATOR](#) was added in 8.0.33.

- Error number: [MY-010543](#); Symbol: [ER\\_RPL\\_MTS\\_AUTOMATIC\\_RECOVERY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: MTS recovery: automatic recovery failed. Either the slave server had stopped due to an error during an earlier session or relay logs are corrupted. Fix the cause of the slave side error and restart the slave server or consider using RESET SLAVE.

[ER\\_RPL\\_MTS\\_AUTOMATIC\\_RECOVERY\\_FAILED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010543](#); Symbol: [ER\\_RPL\\_MTA\\_AUTOMATIC\\_RECOVERY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: MTA recovery: automatic recovery failed. Either the replica server had stopped due to an error during an earlier session or relay logs are corrupted. Fix the cause of the replica side error and restart the replica server or consider using RESET REPLICATION.

[ER\\_RPL\\_MTA\\_AUTOMATIC\\_RECOVERY\\_FAILED](#) was added in 8.0.33.

- Error number: [MY-010544](#); Symbol: [ER\\_RPL\\_MTS\\_RECOVERY\\_CANT\\_OPEN\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)

Message: Failed to open the relay log '%s' (relay\_log\_pos %s).

[ER\\_RPL\\_MTS\\_RECOVERY\\_CANT\\_OPEN\\_RELAY\\_LOG](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010544](#); Symbol: [ER\\_RPL\\_MTA\\_RECOVERY\\_CANT\\_OPEN\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)

Message: Failed to open the relay log '%s' (relay\_log\_pos %s).

[ER\\_RPL\\_MTA\\_RECOVERY\\_CANT\\_OPEN\\_RELAY\\_LOG](#) was added in 8.0.33.

- Error number: [MY-010545](#); Symbol: [ER\\_RPL\\_MTS\\_RECOVERY\\_SUCCESSFUL](#); SQLSTATE: [HY000](#)

Message: MTS recovery: completed successfully.

[ER\\_RPL\\_MTS\\_RECOVERY\\_SUCCESSFUL](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010545](#); Symbol: [ER\\_RPL\\_MTA\\_RECOVERY\\_SUCCESSFUL](#); SQLSTATE: [HY000](#)

Message: MTA recovery: completed successfully.



---

[ER\\_RPL\\_MTA\\_RECOVERY\\_SUCCESSFUL](#) was added in 8.0.33.

- Error number: [MY-010546](#); Symbol: [ER\\_RPL\\_SERVER\\_ID\\_MISSING](#); SQLSTATE: [HY000](#)

Message: Server id not set, will not start replica%s

[ER\\_RPL\\_SERVER\\_ID\\_MISSING](#) was added in 8.0.2.

- Error number: [MY-010547](#); Symbol: [ER\\_RPL\\_CANT\\_CREATE\\_SLAVE\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create slave thread%s.

[ER\\_RPL\\_CANT\\_CREATE\\_SLAVE\\_THREAD](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010547](#); Symbol: [ER\\_RPL\\_CANT\\_CREATE\\_REPLICA\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create replica thread%s.

[ER\\_RPL\\_CANT\\_CREATE\\_REPLICA\\_THREAD](#) was added in 8.0.33.

- Error number: [MY-010548](#); Symbol: [ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_WAS\\_KILLED](#); SQLSTATE: [HY000](#)

Message: The slave IO thread%s was killed while executing initialization query '%s'

[ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_WAS\\_KILLED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010548](#); Symbol: [ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_WAS\\_KILLED](#); SQLSTATE: [HY000](#)

Message: The replica IO thread%s was killed while executing initialization query '%s'

[ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_WAS\\_KILLED](#) was added in 8.0.33.

- Error number: [MY-010549](#); Symbol: [ER\\_RPL\\_SLAVE\\_MASTER\\_UUID\\_HAS\\_CHANGED](#); SQLSTATE: [HY000](#)

Message: The master's UUID has changed, although this should not happen unless you have changed it manually. The old UUID was %s.

[ER\\_RPL\\_SLAVE\\_MASTER\\_UUID\\_HAS\\_CHANGED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010550](#); Symbol: [ER\\_RPL\\_SLAVE\\_USES\\_CHECKSUM\\_AND\\_MASTER\\_PRE\\_50](#); SQLSTATE: [HY000](#)

Message: Found a master with MySQL server version older than 5.0. With checksums enabled on the slave, replication might not work correctly. To ensure correct replication, restart the slave server with --replica\_sql\_verify\_checksum=0.

[ER\\_RPL\\_SLAVE\\_USES\\_CHECKSUM\\_AND\\_MASTER\\_PRE\\_50](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010550](#); Symbol: [ER\\_RPL\\_REPLICA\\_USES\\_CHECKSUM\\_AND\\_SOURCE\\_PRE\\_50](#); SQLSTATE: [HY000](#)

Message: Found a source with MySQL server version older than 5.0. With checksums enabled on the replica, replication might not work correctly. To ensure correct replication, restart the replica server with --replica\_sql\_verify\_checksum=0.

[ER\\_RPL\\_REPLICA\\_USES\\_CHECKSUM\\_AND\\_SOURCE\\_PRE\\_50](#) was added in 8.0.33.

- 
- Error number: `MY-010551`; Symbol: `ER_RPL_SLAVE_SECONDS_BEHIND_MASTER_DUBIOUS`; SQLSTATE: `HY000`  
  
Message: "SELECT UNIX\_TIMESTAMP()" failed on master, do not trust column Seconds\_Behind\_Master of SHOW SLAVE STATUS. Error: %s (%d)  
  
`ER_RPL_SLAVE_SECONDS_BEHIND_MASTER_DUBIOUS` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010551`; Symbol: `ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS`; SQLSTATE: `HY000`  
  
Message: "SELECT UNIX\_TIMESTAMP()" failed on source, do not trust column Seconds\_Behind\_Source of SHOW REPLICA STATUS. Error: %s (%d)  
  
`ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS` was added in 8.0.33.
  - Error number: `MY-010552`; Symbol: `ER_RPL_SLAVE_CANT_FLUSH_MASTER_INFO_FILE`; SQLSTATE: `HY000`  
  
Message: Failed to flush master info file.  
  
`ER_RPL_SLAVE_CANT_FLUSH_MASTER_INFO_FILE` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010552`; Symbol: `ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_METADATA_REPOS`; SQLSTATE: `HY000`  
  
Message: Failed to flush connection metadata repository.  
  
`ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_METADATA_REPOS` was added in 8.0.33.
  - Error number: `MY-010553`; Symbol: `ER_RPL_SLAVE_REPORT_HOST_TOO_LONG`; SQLSTATE: `HY000`  
  
Message: The length of report\_host is %zu. It is larger than the max length(%d), so this slave cannot be registered to the master%s.  
  
`ER_RPL_SLAVE_REPORT_HOST_TOO_LONG` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010553`; Symbol: `ER_RPL_REPLICA_REPORT_HOST_TOO_LONG`; SQLSTATE: `HY000`  
  
Message: The length of report\_host is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.  
  
`ER_RPL_REPLICA_REPORT_HOST_TOO_LONG` was added in 8.0.33.
  - Error number: `MY-010554`; Symbol: `ER_RPL_SLAVE_REPORT_USER_TOO_LONG`; SQLSTATE: `HY000`  
  
Message: The length of report\_user is %zu. It is larger than the max length(%d), so this slave cannot be registered to the master%s.  
  
`ER_RPL_SLAVE_REPORT_USER_TOO_LONG` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010554`; Symbol: `ER_RPL_REPLICA_REPORT_USER_TOO_LONG`; SQLSTATE: `HY000`  
  
Message: The length of report\_user is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.  
  
`ER_RPL_REPLICA_REPORT_USER_TOO_LONG` was added in 8.0.33.

- 
- Error number: [MY-010555](#); Symbol: [ER\\_RPL\\_SLAVE\\_REPORT\\_PASSWORD\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
  
Message: The length of report\_password is %zu. It is larger than the max length(%d), so this slave cannot be registered to the master%s.  
  
[ER\\_RPL\\_SLAVE\\_REPORT\\_PASSWORD\\_TOO\\_LONG](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010555](#); Symbol: [ER\\_RPL\\_REPLICA\\_REPORT\\_PASSWORD\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
  
Message: The length of report\_password is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.  
  
[ER\\_RPL\\_REPLICA\\_REPORT\\_PASSWORD\\_TOO\\_LONG](#) was added in 8.0.33.
  - Error number: [MY-010556](#); Symbol: [ER\\_RPL\\_SLAVE\\_ERROR\\_RETRYING](#); SQLSTATE: [HY000](#)  
  
Message: Error on %s: %d %s, will retry in %d secs  
  
[ER\\_RPL\\_SLAVE\\_ERROR\\_RETRYING](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010556](#); Symbol: [ER\\_RPL\\_REPLICA\\_ERROR\\_RETRYING](#); SQLSTATE: [HY000](#)  
  
Message: Error on %s: %d %s, will retry in %d secs  
  
[ER\\_RPL\\_REPLICA\\_ERROR\\_RETRYING](#) was added in 8.0.33.
  - Error number: [MY-010557](#); Symbol: [ER\\_RPL\\_SLAVE\\_ERROR\\_READING\\_FROM\\_SERVER](#); SQLSTATE: [HY000](#)  
  
Message: Error reading packet from server%s: %s (server\_errno=%d)  
  
[ER\\_RPL\\_SLAVE\\_ERROR\\_READING\\_FROM\\_SERVER](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010557](#); Symbol: [ER\\_RPL\\_REPLICA\\_ERROR\\_READING\\_FROM\\_SERVER](#); SQLSTATE: [HY000](#)  
  
Message: Error reading packet from server%s: %s (server\_errno=%d)  
  
[ER\\_RPL\\_REPLICA\\_ERROR\\_READING\\_FROM\\_SERVER](#) was added in 8.0.33.
  - Error number: [MY-010558](#); Symbol: [ER\\_RPL\\_SLAVE\\_DUMP\\_THREAD\\_KILLED\\_BY\\_MASTER](#); SQLSTATE: [HY000](#)  
  
Message: Slave%s: received end packet from server due to dump thread being killed on master. Dump threads are killed for example during master shutdown, explicitly by a user, or when the master receives a binlog send request from a duplicate server UUID <%s> : Error %s  
  
[ER\\_RPL\\_SLAVE\\_DUMP\\_THREAD\\_KILLED\\_BY\\_MASTER](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010558](#); Symbol: [ER\\_RPL\\_REPLICA\\_DUMP\\_THREAD\\_KILLED\\_BY\\_SOURCE](#); SQLSTATE: [HY000](#)  
  
Message: Replica%s: received end packet from server due to dump thread being killed on source. Dump threads are killed for example during source shutdown, explicitly by a user, or when the source receives a binlog send request from a duplicate server UUID <%s> : Error %s  
  
[ER\\_RPL\\_REPLICA\\_DUMP\\_THREAD\\_KILLED\\_BY\\_SOURCE](#) was added in 8.0.33.
-

- 
- Error number: [MY-010559](#); Symbol: [ER\\_RPL\\_MTS\\_STATISTICS](#); SQLSTATE: [HY000](#)

Message: Multi-threaded slave statistics%s: seconds elapsed = %lu; events assigned = %llu; worker queues filled over overrun level = %lu; waited due a Worker queue full = %lu; waited due the total size = %lu; waited at clock conflicts = %llu waited (count) when Workers occupied = %lu waited when Workers occupied = %llu

[ER\\_RPL\\_MTS\\_STATISTICS](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010559](#); Symbol: [ER\\_RPL\\_MTA\\_STATISTICS](#); SQLSTATE: [HY000](#)

Message: Multi-threaded replica statistics%s: seconds elapsed = %lu; events assigned = %llu; worker queues filled over overrun level = %lu; waited due a Worker queue full = %lu; waited due the total size = %lu; waited at clock conflicts = %llu waited (count) when Workers occupied = %lu waited when Workers occupied = %llu

[ER\\_RPL\\_MTA\\_STATISTICS](#) was added in 8.0.33.

- Error number: [MY-010560](#); Symbol: [ER\\_RPL\\_MTS\\_RECOVERY\\_COMPLETE](#); SQLSTATE: [HY000](#)

Message: Slave%s: MTS Recovery has completed at relay log %s, position %llu master log %s, position %llu.

[ER\\_RPL\\_MTS\\_RECOVERY\\_COMPLETE](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010560](#); Symbol: [ER\\_RPL\\_MTA\\_RECOVERY\\_COMPLETE](#); SQLSTATE: [HY000](#)

Message: Replica%s: MTA Recovery has completed at relay log %s, position %llu source log %s, position %llu.

[ER\\_RPL\\_MTA\\_RECOVERY\\_COMPLETE](#) was added in 8.0.33.

- Error number: [MY-010561](#); Symbol: [ER\\_RPL\\_SLAVE\\_CANT\\_INIT\\_RELAY\\_LOG\\_POSITION](#); SQLSTATE: [HY000](#)

Message: Error initializing relay log position%s: %s

[ER\\_RPL\\_SLAVE\\_CANT\\_INIT\\_RELAY\\_LOG\\_POSITION](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010561](#); Symbol: [ER\\_RPL\\_REPLICA\\_CANT\\_INIT\\_RELAY\\_LOG\\_POSITION](#); SQLSTATE: [HY000](#)

Message: Error initializing relay log position%s: %s

[ER\\_RPL\\_REPLICA\\_CANT\\_INIT\\_RELAY\\_LOG\\_POSITION](#) was added in 8.0.33.

- Error number: [MY-010562](#); Symbol: [ER\\_RPL\\_SLAVE\\_CONNECTED\\_TO\\_MASTER\\_REPLICATION\\_STARTED](#); SQLSTATE: [HY000](#)

Message: Slave I/O thread%s: connected to master '%s@%s:%d', replication started in log '%s' at position %s

[ER\\_RPL\\_SLAVE\\_CONNECTED\\_TO\\_MASTER\\_REPLICATION\\_STARTED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010563](#); Symbol: [ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_KILLED](#); SQLSTATE: [HY000](#)

Message: Slave I/O thread%s killed while connecting to master

---

[ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_KILLED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010563](#); Symbol: [ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_KILLED](#); SQLSTATE: [HY000](#)

Message: Replica I/O thread%s killed while connecting to source

[ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_KILLED](#) was added in 8.0.33.

- Error number: [MY-010564](#); Symbol: [ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_CANT\\_REGISTER\\_ON\\_MASTER](#); SQLSTATE: [HY000](#)

Message: Slave I/O thread couldn't register on master

[ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_CANT\\_REGISTER\\_ON\\_MASTER](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010564](#); Symbol: [ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_CANT\\_REGISTER\\_ON\\_SOURCE](#); SQLSTATE: [HY000](#)

Message: Replica I/O thread couldn't register on source

[ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_CANT\\_REGISTER\\_ON\\_SOURCE](#) was added in 8.0.33.

- Error number: [MY-010565](#); Symbol: [ER\\_RPL\\_SLAVE\\_FORCING\\_TO\\_RECONNECT\\_IO\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Forcing to reconnect slave I/O thread%s

[ER\\_RPL\\_SLAVE\\_FORCING\\_TO\\_RECONNECT\\_IO\\_THREAD](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010565](#); Symbol: [ER\\_RPL\\_REPLICA\\_FORCING\\_TO\\_RECONNECT\\_IO\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Forcing to reconnect replica I/O thread%s

[ER\\_RPL\\_REPLICA\\_FORCING\\_TO\\_RECONNECT\\_IO\\_THREAD](#) was added in 8.0.33.

- Error number: [MY-010566](#); Symbol: [ER\\_RPL\\_SLAVE\\_ERROR\\_REQUESTING\\_BINLOG\\_DUMP](#); SQLSTATE: [HY000](#)

Message: Failed on request\_dump() %s

[ER\\_RPL\\_SLAVE\\_ERROR\\_REQUESTING\\_BINLOG\\_DUMP](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010566](#); Symbol: [ER\\_RPL\\_REPLICA\\_ERROR\\_REQUESTING\\_BINLOG\\_DUMP](#); SQLSTATE: [HY000](#)

Message: Failed on request\_dump() %s

[ER\\_RPL\\_REPLICA\\_ERROR\\_REQUESTING\\_BINLOG\\_DUMP](#) was added in 8.0.33.

- Error number: [MY-010567](#); Symbol: [ER\\_RPL\\_LOG\\_ENTRY\\_EXCEEDS\\_SLAVE\\_MAX\\_ALLOWED\\_PACKET](#); SQLSTATE: [HY000](#)

Message: Log entry on master is longer than slave\_max\_allowed\_packet (%lu) on slave. If the entry is correct, restart the server with a higher value of slave\_max\_allowed\_packet

[ER\\_RPL\\_LOG\\_ENTRY\\_EXCEEDS\\_SLAVE\\_MAX\\_ALLOWED\\_PACKET](#) was added in 8.0.2, removed after 8.0.25.

- 
- Error number: `MY-010567`; Symbol: `ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PACKET`; SQLSTATE: `HY000`  
Message: Log entry on source is longer than `replica_max_allowed_packet` (%lu) on replica. If the entry is correct, restart the server with a higher value of `replica_max_allowed_packet`  
`ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PACKET` was added in 8.0.26.
  - Error number: `MY-010568`; Symbol: `ER_RPL_SLAVE_STOPPING_AS_MASTER_OOM`; SQLSTATE: `HY000`  
Message: Stopping slave I/O thread due to out-of-memory error from master  
`ER_RPL_SLAVE_STOPPING_AS_MASTER_OOM` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010568`; Symbol: `ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM`; SQLSTATE: `HY000`  
Message: Stopping replica I/O thread due to out-of-memory error from source  
`ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM` was added in 8.0.33.
  - Error number: `MY-010569`; Symbol: `ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE`; SQLSTATE: `HY000`  
Message: Slave I/O thread aborted while waiting for relay log space  
`ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010569`; Symbol: `ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE`; SQLSTATE: `HY000`  
Message: Replica I/O thread aborted while waiting for relay log space  
`ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE` was added in 8.0.33.
  - Error number: `MY-010570`; Symbol: `ER_RPL_SLAVE_IO_THREAD_EXITING`; SQLSTATE: `HY000`  
Message: Slave I/O thread exiting%s, read up to log '%s', position %s  
`ER_RPL_SLAVE_IO_THREAD_EXITING` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010570`; Symbol: `ER_RPL_REPLICA_IO_THREAD_EXITING`; SQLSTATE: `HY000`  
Message: Replica I/O thread exiting%s, read up to log '%s', position %s  
`ER_RPL_REPLICA_IO_THREAD_EXITING` was added in 8.0.33.
  - Error number: `MY-010571`; Symbol: `ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER`; SQLSTATE: `HY000`  
Message: Failed during slave worker initialization%s  
`ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010571`; Symbol: `ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER`; SQLSTATE: `HY000`

---

Message: Failed during replica worker initialization%s

[ER\\_RPL\\_REPLICA\\_CANT\\_INITIALIZE\\_REPLICA\\_WORKER](#) was added in 8.0.33.

- Error number: [MY-010572](#); Symbol: [ER\\_RPL\\_MTS\\_GROUP\\_RECOVERY\\_RELAY\\_LOG\\_INFO\\_FOR\\_WORKER](#); SQLSTATE: [HY000](#)

Message: Slave: MTS group recovery relay log info based on Worker-Id %lu, group\_relay\_log\_name %s, group\_relay\_log\_pos %llu group\_master\_log\_name %s, group\_master\_log\_pos %llu

[ER\\_RPL\\_MTS\\_GROUP\\_RECOVERY\\_RELAY\\_LOG\\_INFO\\_FOR\\_WORKER](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010572](#); Symbol: [ER\\_RPL\\_MTA\\_GROUP\\_RECOVERY\\_APPLIER\\_METADATA\\_FOR\\_WORKER](#); SQLSTATE: [HY000](#)

Message: Replica: MTA group recovery applier metadata based on Worker-Id %lu, group\_relay\_log\_name %s, group\_relay\_log\_pos %llu group\_source\_log\_name %s, group\_source\_log\_pos %llu

[ER\\_RPL\\_MTA\\_GROUP\\_RECOVERY\\_APPLIER\\_METADATA\\_FOR\\_WORKER](#) was added in 8.0.33.

- Error number: [MY-010573](#); Symbol: [ER\\_RPL\\_ERROR\\_LOOKING\\_FOR\\_LOG](#); SQLSTATE: [HY000](#)

Message: Error looking for %s.

[ER\\_RPL\\_ERROR\\_LOOKING\\_FOR\\_LOG](#) was added in 8.0.2.

- Error number: [MY-010574](#); Symbol: [ER\\_RPL\\_MTS\\_GROUP\\_RECOVERY\\_RELAY\\_LOG\\_INFO](#); SQLSTATE: [HY000](#)

Message: Slave: MTS group recovery relay log info group\_master\_log\_name %s, event\_master\_log\_pos %llu.

[ER\\_RPL\\_MTS\\_GROUP\\_RECOVERY\\_RELAY\\_LOG\\_INFO](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010574](#); Symbol: [ER\\_RPL\\_MTA\\_GROUP\\_RECOVERY\\_APPLIER\\_METADATA](#); SQLSTATE: [HY000](#)

Message: Replica: MTA group recovery applier metadata group\_source\_log\_name %s, event\_source\_log\_pos %llu.

[ER\\_RPL\\_MTA\\_GROUP\\_RECOVERY\\_APPLIER\\_METADATA](#) was added in 8.0.33.

- Error number: [MY-010575](#); Symbol: [ER\\_RPL\\_CANT\\_FIND\\_FOLLOWUP\\_FILE](#); SQLSTATE: [HY000](#)

Message: Error looking for file after %s.

[ER\\_RPL\\_CANT\\_FIND\\_FOLLOWUP\\_FILE](#) was added in 8.0.2.

- Error number: [MY-010576](#); Symbol: [ER\\_RPL\\_MTS\\_CHECKPOINT\\_PERIOD\\_DIFFERS\\_FROM\\_CNT](#); SQLSTATE: [HY000](#)

Message: This an error cnt != mta\_checkpoint\_period

[ER\\_RPL\\_MTS\\_CHECKPOINT\\_PERIOD\\_DIFFERS\\_FROM\\_CNT](#) was added in 8.0.2, removed after 8.0.32.

- 
- Error number: `MY-010576`; Symbol: `ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_CNT`; SQLSTATE: `HY000`  
Message: This an error cnt != mta\_checkpoint\_period  
`ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_CNT` was added in 8.0.33.
  - Error number: `MY-010577`; Symbol: `ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED`; SQLSTATE: `HY000`  
Message: Failed during slave worker thread creation%s  
`ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010577`; Symbol: `ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED`; SQLSTATE: `HY000`  
Message: Failed during replica worker thread creation%s  
`ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED` was added in 8.0.33.
  - Error number: `MY-010578`; Symbol: `ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED_WITH_ERRNO`; SQLSTATE: `HY000`  
Message: Failed during slave worker thread creation%s (errno= %d)  
`ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED_WITH_ERRNO` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010578`; Symbol: `ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED_WITH_ERRNO`; SQLSTATE: `HY000`  
Message: Failed during replica worker thread creation%s (errno= %d)  
`ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED_WITH_ERRNO` was added in 8.0.33.
  - Error number: `MY-010579`; Symbol: `ER_RPL_SLAVE_FAILED_TO_INIT_PARTITIONS_HASH`; SQLSTATE: `HY000`  
Message: Failed to init partitions hash  
`ER_RPL_SLAVE_FAILED_TO_INIT_PARTITIONS_HASH` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010579`; Symbol: `ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HASH`; SQLSTATE: `HY000`  
Message: Failed to init partitions hash  
`ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HASH` was added in 8.0.33.
  - Error number: `MY-010580`; Symbol: `ER_RPL_SLAVE_NDB_TABLES_NOT_AVAILABLE`; SQLSTATE: `HY000`  
Message: Slave SQL thread : NDB : Tables not available after %lu seconds. Consider increasing --ndb-wait-setup value  
`ER_RPL_SLAVE_NDB_TABLES_NOT_AVAILABLE` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010581`; Symbol: `ER_RPL_SLAVE_SQL_THREAD_STARTING`; SQLSTATE: `HY000`



---

Message: Slave SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s

[ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_STARTING](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010581](#); Symbol: [ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_STARTING](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s

[ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_STARTING](#) was added in 8.0.33.

- Error number: [MY-010582](#); Symbol: [ER\\_RPL\\_SLAVE\\_SKIP\\_COUNTER\\_EXECUTED](#); SQLSTATE: [HY000](#)

Message: 'SQL\_REPLICA\_SKIP\_COUNTER=%ld' executed at relay\_log\_file='%s', relay\_log\_pos='%ld', master\_log\_name='%s', master\_log\_pos='%ld' and new position at relay\_log\_file='%s', relay\_log\_pos='%ld', master\_log\_name='%s', master\_log\_pos='%ld'

[ER\\_RPL\\_SLAVE\\_SKIP\\_COUNTER\\_EXECUTED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010582](#); Symbol: [ER\\_RPL\\_REPLICA\\_SKIP\\_COUNTER\\_EXECUTED](#); SQLSTATE: [HY000](#)

Message: 'SQL\_REPLICA\_SKIP\_COUNTER=%ld' executed at relay\_log\_file='%s', relay\_log\_pos='%ld', source\_log\_name='%s', source\_log\_pos='%ld' and new position at relay\_log\_file='%s', relay\_log\_pos='%ld', source\_log\_name='%s', source\_log\_pos='%ld'

[ER\\_RPL\\_REPLICA\\_SKIP\\_COUNTER\\_EXECUTED](#) was added in 8.0.33.

- Error number: [MY-010583](#); Symbol: [ER\\_RPL\\_SLAVE\\_ADDITIONAL\\_ERROR\\_INFO\\_FROM\\_DA](#); SQLSTATE: [HY000](#)

Message: Slave (additional info): %s Error\_code: MY-%06d

[ER\\_RPL\\_SLAVE\\_ADDITIONAL\\_ERROR\\_INFO\\_FROM\\_DA](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010583](#); Symbol: [ER\\_RPL\\_REPLICA\\_ADDITIONAL\\_ERROR\\_INFO\\_FROM\\_DA](#); SQLSTATE: [HY000](#)

Message: Replica (additional info): %s Error\_code: MY-%06d

[ER\\_RPL\\_REPLICA\\_ADDITIONAL\\_ERROR\\_INFO\\_FROM\\_DA](#) was added in 8.0.33.

- Error number: [MY-010584](#); Symbol: [ER\\_RPL\\_SLAVE\\_ERROR\\_INFO\\_FROM\\_DA](#); SQLSTATE: [HY000](#)

Message: Slave: %s Error\_code: MY-%06d

[ER\\_RPL\\_SLAVE\\_ERROR\\_INFO\\_FROM\\_DA](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010584](#); Symbol: [ER\\_RPL\\_REPLICA\\_ERROR\\_INFO\\_FROM\\_DA](#); SQLSTATE: [HY000](#)

Message: Replica: %s Error\_code: MY-%06d

[ER\\_RPL\\_REPLICA\\_ERROR\\_INFO\\_FROM\\_DA](#) was added in 8.0.33.

- Error number: [MY-010585](#); Symbol: [ER\\_RPL\\_SLAVE\\_ERROR\\_LOADING\\_USER\\_DEFINED\\_LIBRARY](#); SQLSTATE: [HY000](#)

---

Message: Error loading user-defined library, slave SQL thread aborted. Install the missing library, and restart the slave SQL thread with "SLAVE START". We stopped at log '%s' position %s

[ER\\_RPL\\_SLAVE\\_ERROR\\_LOADING\\_USER\\_DEFINED\\_LIBRARY](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010585](#); Symbol: [ER\\_RPL\\_REPLICA\\_ERROR\\_LOADING\\_USER\\_DEFINED\\_LIBRARY](#); SQLSTATE: [HY000](#)

Message: Error loading user-defined library, replica SQL thread aborted. Install the missing library, and restart the replica SQL thread with "START REPLICA". We stopped at log '%s' position %s

[ER\\_RPL\\_REPLICA\\_ERROR\\_LOADING\\_USER\\_DEFINED\\_LIBRARY](#) was added in 8.0.33.

- Error number: [MY-010586](#); Symbol: [ER\\_RPL\\_SLAVE\\_ERROR\\_RUNNING\\_QUERY](#); SQLSTATE: [HY000](#)

Message: Error running query, slave SQL thread aborted. Fix the problem, and restart the slave SQL thread with "SLAVE START". We stopped at log '%s' position %s

[ER\\_RPL\\_SLAVE\\_ERROR\\_RUNNING\\_QUERY](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010586](#); Symbol: [ER\\_RPL\\_REPLICA\\_ERROR\\_RUNNING\\_QUERY](#); SQLSTATE: [HY000](#)

Message: Error running query, replica SQL thread aborted. Fix the problem, and restart the replica SQL thread with "START REPLICA". We stopped at log '%s' position %s

[ER\\_RPL\\_REPLICA\\_ERROR\\_RUNNING\\_QUERY](#) was added in 8.0.33.

- Error number: [MY-010587](#); Symbol: [ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_EXITING](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread%s exiting, replication stopped in log '%s' at position %s

[ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_EXITING](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010587](#); Symbol: [ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_EXITING](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread%s exiting, replication stopped in log '%s' at position %s

[ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_EXITING](#) was added in 8.0.33.

- Error number: [MY-010588](#); Symbol: [ER\\_RPL\\_SLAVE\\_READ\\_INVALID\\_EVENT\\_FROM\\_MASTER](#); SQLSTATE: [HY000](#)

Message: Read invalid event from master: '%s', master could be corrupt but a more likely cause of this is a bug

[ER\\_RPL\\_SLAVE\\_READ\\_INVALID\\_EVENT\\_FROM\\_MASTER](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010588](#); Symbol: [ER\\_RPL\\_REPLICA\\_READ\\_INVALID\\_EVENT\\_FROM\\_SOURCE](#); SQLSTATE: [HY000](#)

Message: Read invalid event from source: '%s', source could be corrupt but a more likely cause of this is a bug

[ER\\_RPL\\_REPLICA\\_READ\\_INVALID\\_EVENT\\_FROM\\_SOURCE](#) was added in 8.0.33.

- Error number: [MY-010589](#); Symbol: [ER\\_RPL\\_SLAVE\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

---

Message: The queue event failed for channel '%s' as its configuration is invalid.

[ER\\_RPL\\_SLAVE\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_CONFIGURATION](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010589](#); Symbol:

[ER\\_RPL\\_REPLICA\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: The queue event failed for channel '%s' as its configuration is invalid.

[ER\\_RPL\\_REPLICA\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_CONFIGURATION](#) was added in 8.0.33.

- Error number: [MY-010590](#); Symbol:

[ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#); SQLSTATE: [HY000](#)

Message: An unexpected event sequence was detected by the IO thread while queuing the event received from master '%s' binary log file, at position %llu.

[ER\\_RPL\\_SLAVE\\_IO\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010590](#); Symbol:

[ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#); SQLSTATE: [HY000](#)

Message: An unexpected event sequence was detected by the IO thread while queuing the event received from source '%s' binary log file, at position %llu.

[ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#) was added in 8.0.33.

- Error number: [MY-010591](#); Symbol: [ER\\_RPL\\_SLAVE\\_CANT\\_USE\\_CHARSET](#); SQLSTATE: [HY000](#)

Message: '%s' can not be used as client character set. '%s' will be used as default client character set while connecting to master.

[ER\\_RPL\\_SLAVE\\_CANT\\_USE\\_CHARSET](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010591](#); Symbol: [ER\\_RPL\\_REPLICA\\_CANT\\_USE\\_CHARSET](#); SQLSTATE: [HY000](#)

Message: '%s' can not be used as client character set. '%s' will be used as default client character set while connecting to source.

[ER\\_RPL\\_REPLICA\\_CANT\\_USE\\_CHARSET](#) was added in 8.0.33.

- Error number: [MY-010592](#); Symbol:

[ER\\_RPL\\_SLAVE\\_CONNECTED\\_TO\\_MASTER\\_REPLICATION\\_RESUMED](#); SQLSTATE: [HY000](#)

Message: Slave%s: connected to master '%s@%s:%d', replication resumed in log '%s' at position %s

[ER\\_RPL\\_SLAVE\\_CONNECTED\\_TO\\_MASTER\\_REPLICATION\\_RESUMED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010592](#); Symbol:

[ER\\_RPL\\_REPLICA\\_CONNECTED\\_TO\\_SOURCE\\_REPLICATION\\_RESUMED](#); SQLSTATE: [HY000](#)

Message: Replica%s: connected to source '%s@%s:%d', replication resumed in log '%s' at position %s

[ER\\_RPL\\_REPLICA\\_CONNECTED\\_TO\\_SOURCE\\_REPLICATION\\_RESUMED](#) was added in 8.0.33.

- 
- Error number: `MY-010593`; Symbol: `ER_RPL_SLAVE_NEXT_LOG_IS_ACTIVE`; SQLSTATE: `HY000`  
Message: next log '%s' is active  
`ER_RPL_SLAVE_NEXT_LOG_IS_ACTIVE` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010593`; Symbol: `ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE`; SQLSTATE: `HY000`  
Message: next log '%s' is active  
`ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE` was added in 8.0.33.
  - Error number: `MY-010594`; Symbol: `ER_RPL_SLAVE_NEXT_LOG_IS_INACTIVE`; SQLSTATE: `HY000`  
Message: next log '%s' is not active  
`ER_RPL_SLAVE_NEXT_LOG_IS_INACTIVE` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010594`; Symbol: `ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE`; SQLSTATE: `HY000`  
Message: next log '%s' is not active  
`ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE` was added in 8.0.33.
  - Error number: `MY-010595`; Symbol: `ER_RPL_SLAVE_SQL_THREAD_IO_ERROR_READING_EVENT`; SQLSTATE: `HY000`  
Message: Slave SQL thread%s: I/O error reading event (errno: %d cur\_log->error: %d)  
`ER_RPL_SLAVE_SQL_THREAD_IO_ERROR_READING_EVENT` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010595`; Symbol: `ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT`; SQLSTATE: `HY000`  
Message: Replica SQL thread%s: I/O error reading event (errno: %d cur\_log->error: %d)  
`ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT` was added in 8.0.33.
  - Error number: `MY-010596`; Symbol: `ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENTS`; SQLSTATE: `HY000`  
Message: Error reading relay log event%s: %s  
`ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENTS` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010596`; Symbol: `ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS`; SQLSTATE: `HY000`  
Message: Error reading relay log event%s: %s  
`ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS` was added in 8.0.33.

- 
- Error number: [MY-010597](#); Symbol: [ER\\_SLAVE\\_CHANGE\\_MASTER\\_TO\\_EXECUTED](#); SQLSTATE: [HY000](#)  
Message: 'CHANGE MASTER TO%s executed'. Previous state master\_host='%s', master\_port=%u, master\_log\_file='%s', master\_log\_pos= %ld, master\_bind='%s'. New state master\_host='%s', master\_port= %u, master\_log\_file='%s', master\_log\_pos= %ld, master\_bind='%s'.  
[ER\\_SLAVE\\_CHANGE\\_MASTER\\_TO\\_EXECUTED](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010597](#); Symbol: [ER\\_REPLICA\\_CHANGE\\_SOURCE\\_TO\\_EXECUTED](#); SQLSTATE: [HY000](#)  
Message: 'CHANGE REPLICATION SOURCE TO%s executed'. Previous state source\_host='%s', source\_port= %u, source\_log\_file='%s', source\_log\_pos= %ld, source\_bind='%s'. New state source\_host='%s', source\_port= %u, source\_log\_file='%s', source\_log\_pos= %ld, source\_bind='%s'.  
[ER\\_REPLICA\\_CHANGE\\_SOURCE\\_TO\\_EXECUTED](#) was added in 8.0.33.
  - Error number: [MY-010598](#); Symbol: [ER\\_RPL\\_SLAVE\\_NEW\\_MASTER\\_INFO\\_NEEDS\\_REPOS\\_TYPE\\_OTHER\\_THAN\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Slave: Cannot create new master info structure when repositories are of type FILE. Convert slave repositories to TABLE to replicate from multiple sources.  
[ER\\_RPL\\_SLAVE\\_NEW\\_MASTER\\_INFO\\_NEEDS\\_REPOS\\_TYPE\\_OTHER\\_THAN\\_FILE](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010598](#); Symbol: [ER\\_RPL\\_REPLICA\\_NEW\\_C\\_M\\_NEEDS\\_REPOS\\_TYPE\\_OTHER\\_THAN\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Replica: Cannot create new connection metadata structure when repositories are of type FILE. Convert replica repositories to TABLE to replicate from multiple sources.  
[ER\\_RPL\\_REPLICA\\_NEW\\_C\\_M\\_NEEDS\\_REPOS\\_TYPE\\_OTHER\\_THAN\\_FILE](#) was added in 8.0.33.
  - Error number: [MY-010599](#); Symbol: [ER\\_RPL\\_FAILED\\_TO\\_STAT\\_LOG\\_IN\\_INDEX](#); SQLSTATE: [HY000](#)  
Message: log %s listed in the index, but failed to stat.  
[ER\\_RPL\\_FAILED\\_TO\\_STAT\\_LOG\\_IN\\_INDEX](#) was added in 8.0.2.
  - Error number: [MY-010600](#); Symbol: [ER\\_RPL\\_LOG\\_NOT\\_FOUND\\_WHILE\\_COUNTING\\_RELAY\\_LOG\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Could not find first log while counting relay log space.  
[ER\\_RPL\\_LOG\\_NOT\\_FOUND\\_WHILE\\_COUNTING\\_RELAY\\_LOG\\_SPACE](#) was added in 8.0.2.
  - Error number: [MY-010601](#); Symbol: [ER\\_SLAVE\\_CANT\\_USE\\_TMPDIR](#); SQLSTATE: [HY000](#)  
Message: Unable to use slave's temporary directory '%s'.  
[ER\\_SLAVE\\_CANT\\_USE\\_TMPDIR](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010601](#); Symbol: [ER\\_REPLICA\\_CANT\\_USE\\_TMPDIR](#); SQLSTATE: [HY000](#)  
Message: Unable to use replica's temporary directory '%s'.  
[ER\\_REPLICA\\_CANT\\_USE\\_TMPDIR](#) was added in 8.0.33.
-

- 
- Error number: `MY-010602`; Symbol: `ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY`; SQLSTATE: `HY000`  
Message: Path '%s' is a directory name, please specify a file name for --relay-log option.  
`ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY` was added in 8.0.2.
  - Error number: `MY-010603`; Symbol: `ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY`; SQLSTATE: `HY000`  
Message: Path '%s' is a directory name, please specify a file name for --relay-log-index option.  
`ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY` was added in 8.0.2.
  - Error number: `MY-010604`; Symbol: `ER_RPL_PLEASE_USE_OPTION_RELAY_LOG`; SQLSTATE: `HY000`  
Message: Neither --relay-log nor --relay-log-index were used; so replication may break when this MySQL server acts as a replica and has his hostname changed!! Please use '--relay-log=%s' to avoid this problem.  
`ER_RPL_PLEASE_USE_OPTION_RELAY_LOG` was added in 8.0.2.
  - Error number: `MY-010605`; Symbol: `ER_RPL_OPEN_INDEX_FILE_FAILED`; SQLSTATE: `HY000`  
Message: Failed in open\_index\_file() called from Relay\_log\_info::rli\_init\_info().  
`ER_RPL_OPEN_INDEX_FILE_FAILED` was added in 8.0.2.
  - Error number: `MY-010606`; Symbol: `ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_RLI_INIT_INFO`; SQLSTATE: `HY000`  
Message: Failed in init\_gtid\_sets() called from Relay\_log\_info::rli\_init\_info().  
`ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_RLI_INIT_INFO` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010606`; Symbol: `ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO`; SQLSTATE: `HY000`  
Message: Failed in init\_gtid\_sets() called from Relay\_log\_info::rli\_init\_info().  
`ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO` was added in 8.0.33.
  - Error number: `MY-010607`; Symbol: `ER_RPL_CANT_OPEN_LOG_IN_RLI_INIT_INFO`; SQLSTATE: `HY000`  
Message: Failed in open\_log() called from Relay\_log\_info::rli\_init\_info().  
`ER_RPL_CANT_OPEN_LOG_IN_RLI_INIT_INFO` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010607`; Symbol: `ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO`; SQLSTATE: `HY000`  
Message: Failed in open\_log() called from Relay\_log\_info::rli\_init\_info().  
`ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO` was added in 8.0.33.
  - Error number: `MY-010608`; Symbol: `ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION`; SQLSTATE: `HY000`

---

Message: Error writing relay log configuration.

[ER\\_RPL\\_ERROR\\_WRITING\\_RELAY\\_LOG\\_CONFIGURATION](#) was added in 8.0.2.

- Error number: [MY-010609](#); Symbol: [ER\\_NDB\\_OOM\\_GET\\_NDB\\_BLOBS\\_VALUE](#); SQLSTATE: [HY000](#)

Message: get\_ndb\_blobs\_value: my\_malloc(%u) failed

[ER\\_NDB\\_OOM\\_GET\\_NDB\\_BLOBS\\_VALUE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010610](#); Symbol: [ER\\_NDB\\_THREAD\\_TIMED\\_OUT](#); SQLSTATE: [HY000](#)

Message: NDB: Thread id %u timed out (30s) waiting for epoch %u/%u to be handled. Progress : %u/%u  
-> %u/%u.

[ER\\_NDB\\_THREAD\\_TIMED\\_OUT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010611](#); Symbol: [ER\\_NDB\\_TABLE\\_IS\\_NOT\\_DISTRIBUTED](#); SQLSTATE: [HY000](#)

Message: NDB: Inconsistency detected in distributed privilege tables. Table '%s.%s' is not distributed

[ER\\_NDB\\_TABLE\\_IS\\_NOT\\_DISTRIBUTED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010612](#); Symbol: [ER\\_NDB\\_CREATING\\_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB: Creating %s.%s

[ER\\_NDB\\_CREATING\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010613](#); Symbol: [ER\\_NDB\\_FLUSHING\\_TABLE\\_INFO](#); SQLSTATE: [HY000](#)

Message: NDB: Flushing %s.%s

[ER\\_NDB\\_FLUSHING\\_TABLE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010614](#); Symbol: [ER\\_NDB\\_CLEANING\\_STRAY\\_TABLES](#); SQLSTATE: [HY000](#)

Message: NDB: Cleaning stray tables from database '%s'

[ER\\_NDB\\_CLEANING\\_STRAY\\_TABLES](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010615](#); Symbol: [ER\\_NDB\\_DISCOVERED\\_MISSING\\_DB](#); SQLSTATE: [HY000](#)

Message: NDB: Discovered missing database '%s'

[ER\\_NDB\\_DISCOVERED\\_MISSING\\_DB](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010616](#); Symbol: [ER\\_NDB\\_DISCOVERED\\_REMAINING\\_DB](#); SQLSTATE: [HY000](#)

Message: NDB: Discovered remaining database '%s'

[ER\\_NDB\\_DISCOVERED\\_REMAINING\\_DB](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010617](#); Symbol: [ER\\_NDB\\_CLUSTER\\_FIND\\_ALL\\_DBS\\_RETRY](#); SQLSTATE: [HY000](#)

Message: NDB: ndbcluster\_find\_all\_databases retry: %u - %s

[ER\\_NDB\\_CLUSTER\\_FIND\\_ALL\\_DBS\\_RETRY](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: `MY-010618`; Symbol: `ER_NDB_CLUSTER_FIND_ALL_DBS_FAIL`; SQLSTATE: `HY000`  
Message: NDB: ndbcluster\_find\_all\_databases fail: %u - %s  
`ER_NDB_CLUSTER_FIND_ALL_DBS_FAIL` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010619`; Symbol: `ER_NDB_SKIPPING_SETUP_TABLE`; SQLSTATE: `HY000`  
Message: NDB: skipping setup table %s.%s, in state %d  
`ER_NDB_SKIPPING_SETUP_TABLE` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010620`; Symbol: `ER_NDB_FAILED_TO_SETUP_TABLE`; SQLSTATE: `HY000`  
Message: NDB: failed to setup table %s.%s, error: %d, %s  
`ER_NDB_FAILED_TO_SETUP_TABLE` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010621`; Symbol: `ER_NDB_MISSING_FRM_DISCOVERING`; SQLSTATE: `HY000`  
Message: NDB: missing frm for %s.%s, discovering...  
`ER_NDB_MISSING_FRM_DISCOVERING` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010622`; Symbol: `ER_NDB_MISMATCH_IN_FRM_DISCOVERING`; SQLSTATE: `HY000`  
Message: NDB: mismatch in frm for %s.%s, discovering...  
`ER_NDB_MISMATCH_IN_FRM_DISCOVERING` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010623`; Symbol: `ER_NDB_BINLOG_CLEANING_UP_SETUP_LEFTOVERS`; SQLSTATE: `HY000`  
Message: ndb\_binlog\_setup: Clean up leftovers  
`ER_NDB_BINLOG_CLEANING_UP_SETUP_LEFTOVERS` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010624`; Symbol: `ER_NDB_WAITING_INFO`; SQLSTATE: `HY000`  
Message: NDB %s: waiting max %u sec for %s %s. epochs: (%u/%u,%u/%u,%u/%u) injector proc\_info: %s  
`ER_NDB_WAITING_INFO` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010625`; Symbol: `ER_NDB_WAITING_INFO_WITH_MAP`; SQLSTATE: `HY000`  
Message: NDB %s: waiting max %u sec for %s %s. epochs: (%u/%u,%u/%u,%u/%u) injector proc\_info: %s map: %x%08x  
`ER_NDB_WAITING_INFO_WITH_MAP` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010626`; Symbol: `ER_NDB_TIMEOUT_WHILE_DISTRIBUTING`; SQLSTATE: `HY000`  
Message: NDB %s: distributing %s timed out. Ignoring...  
`ER_NDB_TIMEOUT_WHILE_DISTRIBUTING` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010627`; Symbol: `ER_NDB_NOT_WAITING_FOR_DISTRIBUTING`; SQLSTATE: `HY000`



---

Message: NDB %s: not waiting for distributing %s

[ER\\_NDB\\_NOT\\_WAITING\\_FOR\\_DISTRIBUTING](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010628](#); Symbol: [ER\\_NDB\\_DISTRIBUTED\\_INFO](#); SQLSTATE: [HY000](#)

Message: NDB: distributed %s.%s(%u/%u) type: %s(%u) query: '%s' to %x%08x

[ER\\_NDB\\_DISTRIBUTED\\_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010629](#); Symbol: [ER\\_NDB\\_DISTRIBUTION\\_COMPLETE](#); SQLSTATE: [HY000](#)

Message: NDB: distribution of %s.%s(%u/%u) type: %s(%u) query: '%s' - complete!

[ER\\_NDB\\_DISTRIBUTION\\_COMPLETE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010630](#); Symbol: [ER\\_NDB\\_SCHEMA\\_DISTRIBUTION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: NDB Schema dist: Data node: %d failed, subscriber bitmask %x%08x

[ER\\_NDB\\_SCHEMA\\_DISTRIBUTION\\_FAILED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010631](#); Symbol: [ER\\_NDB\\_SCHEMA\\_DISTRIBUTION\\_REPORTS\\_SUBSCRIBE](#); SQLSTATE: [HY000](#)

Message: NDB Schema dist: Data node: %d reports subscribe from node %d, subscriber bitmask %x%08x

[ER\\_NDB\\_SCHEMA\\_DISTRIBUTION\\_REPORTS\\_SUBSCRIBE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010632](#); Symbol: [ER\\_NDB\\_SCHEMA\\_DISTRIBUTION\\_REPORTS\\_UNSUBSCRIBE](#); SQLSTATE: [HY000](#)

Message: NDB Schema dist: Data node: %d reports unsubscribe from node %d, subscriber bitmask %x%08x

[ER\\_NDB\\_SCHEMA\\_DISTRIBUTION\\_REPORTS\\_UNSUBSCRIBE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010633](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_DISCOVER\\_TABLE\\_FROM\\_SCHEMA\\_EVENT](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Could not discover table '%s.%s' from binlog schema event '%s' from node %d. my\_errno: %d

[ER\\_NDB\\_BINLOG\\_CANT\\_DISCOVER\\_TABLE\\_FROM\\_SCHEMA\\_EVENT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010634](#); Symbol: [ER\\_NDB\\_BINLOG\\_SIGNALLING\\_UNKNOWN\\_VALUE](#); SQLSTATE: [HY000](#)

Message: NDB: unknown value for binlog signalling 0x%X, %s not logged

[ER\\_NDB\\_BINLOG\\_SIGNALLING\\_UNKNOWN\\_VALUE](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: `MY-010635`; Symbol: `ER_NDB_BINLOG_REPLY_TO`; SQLSTATE: `HY000`  
Message: NDB: reply to %s.%s(%u/%u) from %s to %x%08x  
`ER_NDB_BINLOG_REPLY_TO` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010636`; Symbol: `ER_NDB_BINLOG_CANT_RELEASE_SLOCK`; SQLSTATE: `HY000`  
Message: NDB: Could not release slock on '%s.%s', Error code: %d Message: %s  
`ER_NDB_BINLOG_CANT_RELEASE_SLOCK` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010637`; Symbol: `ER_NDB_CANT_FIND_TABLE`; SQLSTATE: `HY000`  
Message: NDB schema: Could not find table '%s.%s' in NDB  
`ER_NDB_CANT_FIND_TABLE` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010638`; Symbol: `ER_NDB_DISCARDING_EVENT_NO_OBJ`; SQLSTATE: `HY000`  
Message: NDB: Discarding event...no obj: %s (%u/%u)  
`ER_NDB_DISCARDING_EVENT_NO_OBJ` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010639`; Symbol: `ER_NDB_DISCARDING_EVENT_ID_VERSION_MISMATCH`; SQLSTATE: `HY000`  
Message: NDB: Discarding event...key: %s non matching id/version [%u/%u] != [%u/%u]  
`ER_NDB_DISCARDING_EVENT_ID_VERSION_MISMATCH` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010640`; Symbol: `ER_NDB_CLEAR_SLOCK_INFO`; SQLSTATE: `HY000`  
Message: NDB: CLEAR\_SLOCK key: %s(%u/%u) %x%08x, from %s to %x%08x  
`ER_NDB_CLEAR_SLOCK_INFO` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010641`; Symbol: `ER_NDB_BINLOG_SKIPPING_LOCAL_TABLE`; SQLSTATE: `HY000`  
Message: NDB Binlog: Skipping locally defined table '%s.%s' from binlog schema event '%s' from node %d.  
`ER_NDB_BINLOG_SKIPPING_LOCAL_TABLE` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010642`; Symbol: `ER_NDB_BINLOG_ONLINE_ALTER_RENAME`; SQLSTATE: `HY000`  
Message: NDB Binlog: handling online alter/rename  
`ER_NDB_BINLOG_ONLINE_ALTER_RENAME` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010643`; Symbol: `ER_NDB_BINLOG_CANT_REOPEN_SHADOW_TABLE`; SQLSTATE: `HY000`  
Message: NDB Binlog: Failed to re-open shadow table %s.%s  
`ER_NDB_BINLOG_CANT_REOPEN_SHADOW_TABLE` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010644`; Symbol: `ER_NDB_BINLOG_ONLINE_ALTER_RENAME_COMPLETE`; SQLSTATE: `HY000`

---

Message: NDB Binlog: handling online alter/rename done

[ER\\_NDB\\_BINLOG\\_ONLINE\\_ALTER\\_RENAME\\_COMPLETE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010645](#); Symbol: [ER\\_NDB\\_BINLOG\\_SKIPPING\\_DROP\\_OF\\_LOCAL\\_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Skipping drop of locally defined table '%s.%s' from binlog schema event '%s' from node %d.

[ER\\_NDB\\_BINLOG\\_SKIPPING\\_DROP\\_OF\\_LOCAL\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010646](#); Symbol: [ER\\_NDB\\_BINLOG\\_SKIPPING\\_RENAME\\_OF\\_LOCAL\\_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Skipping renaming locally defined table '%s.%s' from binlog schema event '%s' from node %d.

[ER\\_NDB\\_BINLOG\\_SKIPPING\\_RENAME\\_OF\\_LOCAL\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010647](#); Symbol: [ER\\_NDB\\_BINLOG\\_SKIPPING\\_DROP\\_OF\\_DB\\_CONTAINING\\_LOCAL\\_TABLES](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Skipping drop database '%s' since it contained local tables binlog schema event '%s' from node %d.

[ER\\_NDB\\_BINLOG\\_SKIPPING\\_DROP\\_OF\\_DB\\_CONTAINING\\_LOCAL\\_TABLES](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010648](#); Symbol: [ER\\_NDB\\_BINLOG\\_GOT\\_DIST\\_PRIV\\_EVENT\\_FLUSHING\\_PRIVILEGES](#); SQLSTATE: [HY000](#)

Message: Got dist\_priv event: %s, flushing privileges

[ER\\_NDB\\_BINLOG\\_GOT\\_DIST\\_PRIV\\_EVENT\\_FLUSHING\\_PRIVILEGES](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010649](#); Symbol: [ER\\_NDB\\_BINLOG\\_GOT\\_SCHEMA\\_EVENT](#); SQLSTATE: [HY000](#)

Message: NDB: got schema event on %s.%s(%u/%u) query: '%s' type: %s(%d) node: %u slock: %x %08x

[ER\\_NDB\\_BINLOG\\_GOT\\_SCHEMA\\_EVENT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010650](#); Symbol: [ER\\_NDB\\_BINLOG\\_SKIPPING\\_OLD\\_SCHEMA\\_OPERATION](#); SQLSTATE: [HY000](#)

Message: NDB schema: Skipping old schema operation(RENAME\_TABLE\_NEW) on %s.%s

[ER\\_NDB\\_BINLOG\\_SKIPPING\\_OLD\\_SCHEMA\\_OPERATION](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010651](#); Symbol: [ER\\_NDB\\_CLUSTER\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: NDB Schema dist: cluster failure at epoch %u/%u.

[ER\\_NDB\\_CLUSTER\\_FAILURE](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: `MY-010652`; Symbol: `ER_NDB_TABLES_INITIALLY_READ_ONLY_ON_RECONNECT`; SQLSTATE: `HY000`  
Message: NDB Binlog: ndb tables initially read only on reconnect.  
`ER_NDB_TABLES_INITIALLY_READ_ONLY_ON_RECONNECT` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010653`; Symbol: `ER_NDB_IGNOREING_UNKNOWN_EVENT`; SQLSTATE: `HY000`  
Message: NDB Schema dist: unknown event %u, ignoring...  
`ER_NDB_IGNOREING_UNKNOWN_EVENT` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010654`; Symbol: `ER_NDB_BINLOG_OPENING_INDEX`; SQLSTATE: `HY000`  
Message: NDB Binlog: Opening ndb\_binlog\_index: %d, '%s'  
`ER_NDB_BINLOG_OPENING_INDEX` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010655`; Symbol: `ER_NDB_BINLOG_CANT_LOCK_NDB_BINLOG_INDEX`; SQLSTATE: `HY000`  
Message: NDB Binlog: Unable to lock table ndb\_binlog\_index  
`ER_NDB_BINLOG_CANT_LOCK_NDB_BINLOG_INDEX` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010656`; Symbol: `ER_NDB_BINLOG_INJECTING_RANDOM_WRITE_FAILURE`; SQLSTATE: `HY000`  
Message: NDB Binlog: Injecting random write failure  
`ER_NDB_BINLOG_INJECTING_RANDOM_WRITE_FAILURE` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010657`; Symbol: `ER_NDB_BINLOG_CANT_WRITE_TO_NDB_BINLOG_INDEX`; SQLSTATE: `HY000`  
Message: NDB Binlog: Failed writing to ndb\_binlog\_index for epoch %u/%u orig\_server\_id %u orig\_epoch %u/%u with error %d.  
`ER_NDB_BINLOG_CANT_WRITE_TO_NDB_BINLOG_INDEX` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010658`; Symbol: `ER_NDB_BINLOG_WRITING_TO_NDB_BINLOG_INDEX`; SQLSTATE: `HY000`  
Message: NDB Binlog: Writing row (%s) to ndb\_binlog\_index - %s  
`ER_NDB_BINLOG_WRITING_TO_NDB_BINLOG_INDEX` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010659`; Symbol: `ER_NDB_BINLOG_CANT_COMMIT_TO_NDB_BINLOG_INDEX`; SQLSTATE: `HY000`  
Message: NDB Binlog: Failed committing transaction to ndb\_binlog\_index with error %d.  
`ER_NDB_BINLOG_CANT_COMMIT_TO_NDB_BINLOG_INDEX` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010660`; Symbol: `ER_NDB_BINLOG_WRITE_TO_NDB_BINLOG_INDEX_FAILED_AFTER_KILL`; SQLSTATE: `HY000`  
Message: NDB Binlog: Failed writing to ndb\_binlog\_index table while retrying after kill during shutdown

---

[ER\\_NDB\\_BINLOG\\_WRITE\\_TO\\_NDB\\_BINLOG\\_INDEX\\_FAILED\\_AFTER\\_KILL](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010661](#); Symbol: [ER\\_NDB\\_BINLOG\\_USING\\_SERVER\\_ID\\_0\\_SLAVES\\_WILL\\_NOT](#); SQLSTATE: [HY000](#)

Message: NDB: server id set to zero - changes logged to bin log with server id zero will be logged with another server id by slave mysqlds

[ER\\_NDB\\_BINLOG\\_USING\\_SERVER\\_ID\\_0\\_SLAVES\\_WILL\\_NOT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010662](#); Symbol: [ER\\_NDB\\_SERVER\\_ID\\_RESERVED\\_OR\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)

Message: NDB: server id provided is too large to be represented in opt\_server\_id\_bits or is reserved

[ER\\_NDB\\_SERVER\\_ID\\_RESERVED\\_OR\\_TOO\\_LARGE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010663](#); Symbol: [ER\\_NDB\\_BINLOG\\_NDB\\_LOG\\_TRANSACTION\\_ID\\_REQUIRES\\_V2\\_ROW\\_EVENTS](#); SQLSTATE: [HY000](#)

Message: NDB: --ndb-log-transaction-id requires v2 Binlog row events but server is using v1.

[ER\\_NDB\\_BINLOG\\_NDB\\_LOG\\_TRANSACTION\\_ID\\_REQUIRES\\_V2\\_ROW\\_EVENTS](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010664](#); Symbol: [ER\\_NDB\\_BINLOG\\_NDB\\_LOG\\_APPLY\\_STATUS\\_FORCING\\_FULL\\_USE\\_WRITE](#); SQLSTATE: [HY000](#)

Message: NDB: ndb-log-apply-status forcing %s.%s to FULL USE\_WRITE

[ER\\_NDB\\_BINLOG\\_NDB\\_LOG\\_APPLY\\_STATUS\\_FORCING\\_FULL\\_USE\\_WRITE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010665](#); Symbol: [ER\\_NDB\\_BINLOG\\_GENERIC\\_MESSAGE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: %s

[ER\\_NDB\\_BINLOG\\_GENERIC\\_MESSAGE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010666](#); Symbol: [ER\\_NDB\\_CONFLICT\\_GENERIC\\_MESSAGE](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_NDB\\_CONFLICT\\_GENERIC\\_MESSAGE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010667](#); Symbol: [ER\\_NDB\\_TRANS\\_DEPENDENCY\\_TRACKER\\_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_NDB\\_TRANS\\_DEPENDENCY\\_TRACKER\\_ERROR](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010668](#); Symbol: [ER\\_NDB\\_CONFLICT\\_FN\\_PARSE\\_ERROR](#); SQLSTATE: [HY000](#)

Message: NDB Slave: Table %s.%s : Parse error on conflict fn : %s

- 
- [ER\\_NDB\\_CONFLICT\\_FN\\_PARSE\\_ERROR](#) was added in 8.0.2, removed after 8.0.13.
- Error number: [MY-010669](#); Symbol: [ER\\_NDB\\_CONFLICT\\_FN\\_SETUP\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: NDB Slave: Table %s.%s : %s  
[ER\\_NDB\\_CONFLICT\\_FN\\_SETUP\\_ERROR](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010670](#); Symbol: [ER\\_NDB\\_BINLOG\\_FAILED\\_TO\\_GET\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: Failed to get table %s from ndb: %s, %d  
[ER\\_NDB\\_BINLOG\\_FAILED\\_TO\\_GET\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010671](#); Symbol: [ER\\_NDB\\_BINLOG\\_NOT\\_LOGGING](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: NOT logging %s  
[ER\\_NDB\\_BINLOG\\_NOT\\_LOGGING](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010672](#); Symbol: [ER\\_NDB\\_BINLOG\\_CREATE\\_TABLE\\_EVENT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: FAILED CREATE (DISCOVER) TABLE Event: %s  
[ER\\_NDB\\_BINLOG\\_CREATE\\_TABLE\\_EVENT\\_FAILED](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010673](#); Symbol: [ER\\_NDB\\_BINLOG\\_CREATE\\_TABLE\\_EVENT\\_INFO](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: CREATE (DISCOVER) TABLE Event: %s  
[ER\\_NDB\\_BINLOG\\_CREATE\\_TABLE\\_EVENT\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010674](#); Symbol: [ER\\_NDB\\_BINLOG\\_DISCOVER\\_TABLE\\_EVENT\\_INFO](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: DISCOVER TABLE Event: %s  
[ER\\_NDB\\_BINLOG\\_DISCOVER\\_TABLE\\_EVENT\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010675](#); Symbol: [ER\\_NDB\\_BINLOG\\_BLOB\\_REQUIRES\\_PK](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: logging of table %s with BLOB attribute and no PK is not supported  
[ER\\_NDB\\_BINLOG\\_BLOB\\_REQUIRES\\_PK](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010676](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_EVENT\\_IN\\_DB](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: Unable to create event in database. Event: %s Error Code: %d Message: %s  
[ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_EVENT\\_IN\\_DB](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010677](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_EVENT\\_IN\\_DB\\_AND\\_CANT\\_DROP](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: Unable to create event in database. Attempt to correct with drop failed. Event: %s Error Code: %d Message: %s

---

[ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_EVENT\\_IN\\_DB\\_AND\\_CANT\\_DROP](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010678](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_EVENT\\_IN\\_DB\\_DROPPED](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Unable to create event in database. Attempt to correct with drop ok, but create failed. Event: %s Error Code: %d Message: %s

[ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_EVENT\\_IN\\_DB\\_DROPPED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010679](#); Symbol: [ER\\_NDB\\_BINLOG\\_DISCOVER\\_REUSING\\_OLD\\_EVENT\\_OPS](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: discover reusing old ev op

[ER\\_NDB\\_BINLOG\\_DISCOVER\\_REUSING\\_OLD\\_EVENT\\_OPS](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010680](#); Symbol: [ER\\_NDB\\_BINLOG\\_CREATING\\_NDBEVENTOPERATION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Creating NdbEventOperation failed for %s

[ER\\_NDB\\_BINLOG\\_CREATING\\_NDBEVENTOPERATION\\_FAILED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010681](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_BLOB](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Creating NdbEventOperation blob field %u handles failed (code=%d) for %s

[ER\\_NDB\\_BINLOG\\_CANT\\_CREATE\\_BLOB](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010682](#); Symbol: [ER\\_NDB\\_BINLOG\\_NDBEVENT\\_EXECUTE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: ndbevent->execute failed for %s; %d %s

[ER\\_NDB\\_BINLOG\\_NDBEVENT\\_EXECUTE\\_FAILED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010683](#); Symbol: [ER\\_NDB\\_CREATE\\_EVENT\\_OPS\\_LOGGING\\_INFO](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: logging %s (%s,%s)

[ER\\_NDB\\_CREATE\\_EVENT\\_OPS\\_LOGGING\\_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010684](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_DROP\\_EVENT\\_FROM\\_DB](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Unable to drop event in database. Event: %s Error Code: %d Message: %s

[ER\\_NDB\\_BINLOG\\_CANT\\_DROP\\_EVENT\\_FROM\\_DB](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010685](#); Symbol: [ER\\_NDB\\_TIMED\\_OUT\\_IN\\_DROP\\_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB %s: %s timed out. Ignoring...

[ER\\_NDB\\_TIMED\\_OUT\\_IN\\_DROP\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.

- 
- Error number: [MY-010686](#); Symbol: [ER\\_NDB\\_BINLOG\\_UNHANDLED\\_ERROR\\_FOR\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: unhandled error %d for table %s  
[ER\\_NDB\\_BINLOG\\_UNHANDLED\\_ERROR\\_FOR\\_TABLE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010687](#); Symbol: [ER\\_NDB\\_BINLOG\\_CLUSTER\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: cluster failure for %s at epoch %u/%u.  
[ER\\_NDB\\_BINLOG\\_CLUSTER\\_FAILURE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010688](#); Symbol: [ER\\_NDB\\_BINLOG\\_UNKNOWN\\_NON\\_DATA\\_EVENT](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: unknown non data event %d for %s. Ignoring...  
[ER\\_NDB\\_BINLOG\\_UNKNOWN\\_NON\\_DATA\\_EVENT](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010689](#); Symbol: [ER\\_NDB\\_BINLOG\\_INJECTOR\\_DISCARDING\\_ROW\\_EVENT\\_METADATA](#); SQLSTATE: [HY000](#)  
Message: NDB: Binlog Injector discarding row event meta data as server is using v1 row events. (%u %x)  
[ER\\_NDB\\_BINLOG\\_INJECTOR\\_DISCARDING\\_ROW\\_EVENT\\_METADATA](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010690](#); Symbol: [ER\\_NDB\\_REMAINING\\_OPEN\\_TABLES](#); SQLSTATE: [HY000](#)  
Message: remove\_all\_event\_operations: Remaining open tables:  
[ER\\_NDB\\_REMAINING\\_OPEN\\_TABLES](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010691](#); Symbol: [ER\\_NDB\\_REMAINING\\_OPEN\\_TABLE\\_INFO](#); SQLSTATE: [HY000](#)  
Message: %s.%s, use\_count: %u  
[ER\\_NDB\\_REMAINING\\_OPEN\\_TABLE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010692](#); Symbol: [ER\\_NDB\\_COULD\\_NOT\\_GET\\_APPLY\\_STATUS\\_SHARE](#); SQLSTATE: [HY000](#)  
Message: NDB: Could not get apply status share  
[ER\\_NDB\\_COULD\\_NOT\\_GET\\_APPLY\\_STATUS\\_SHARE](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010693](#); Symbol: [ER\\_NDB\\_BINLOG\\_SERVER\\_SHUTDOWN\\_DURING\\_NDB\\_CLUSTER\\_START](#); SQLSTATE: [HY000](#)  
Message: NDB Binlog: Server shutdown detected while waiting for ndbcluster to start...  
[ER\\_NDB\\_BINLOG\\_SERVER\\_SHUTDOWN\\_DURING\\_NDB\\_CLUSTER\\_START](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010694](#); Symbol: [ER\\_NDB\\_BINLOG\\_CLUSTER\\_RESTARTED\\_RESET\\_MASTER\\_SUGGESTED](#); SQLSTATE: [HY000](#)



---

Message: NDB Binlog: cluster has been restarted --initial or with older filesystem.  
ndb\_latest\_handled\_binlog\_epoch: %u/%u, while current epoch: %u/%u. RESET MASTER should be issued. Resetting ndb\_latest\_handled\_binlog\_epoch.

[ER\\_NDB\\_BINLOG\\_CLUSTER\\_RESTARTED\\_RESET\\_MASTER\\_SUGGESTED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010695](#); Symbol: [ER\\_NDB\\_BINLOG\\_CLUSTER\\_HAS\\_RECONNECTED](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: cluster has reconnected. Changes to the database that occurred while disconnected will not be in the binlog

[ER\\_NDB\\_BINLOG\\_CLUSTER\\_HAS\\_RECONNECTED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010696](#); Symbol: [ER\\_NDB\\_BINLOG\\_STARTING\\_LOG\\_AT\\_EPOCH](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: starting log at epoch %u/%u

[ER\\_NDB\\_BINLOG\\_STARTING\\_LOG\\_AT\\_EPOCH](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010697](#); Symbol: [ER\\_NDB\\_BINLOG\\_NDB\\_TABLES\\_WRITABLE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: ndb tables writable

[ER\\_NDB\\_BINLOG\\_NDB\\_TABLES\\_WRITABLE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010698](#); Symbol: [ER\\_NDB\\_BINLOG\\_SHUTDOWN\\_DETECTED](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Server shutdown detected...

[ER\\_NDB\\_BINLOG\\_SHUTDOWN\\_DETECTED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010699](#); Symbol: [ER\\_NDB\\_BINLOG\\_LOST\\_SCHEMA\\_CONNECTION\\_WAITING](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Just lost schema connection, hanging around

[ER\\_NDB\\_BINLOG\\_LOST\\_SCHEMA\\_CONNECTION\\_WAITING](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010700](#); Symbol: [ER\\_NDB\\_BINLOG\\_LOST\\_SCHEMA\\_CONNECTION\\_CONTINUING](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: ...and on our way

[ER\\_NDB\\_BINLOG\\_LOST\\_SCHEMA\\_CONNECTION\\_CONTINUING](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010701](#); Symbol: [ER\\_NDB\\_BINLOG\\_ERROR\\_HANDLING\\_SCHEMA\\_EVENT](#); SQLSTATE: [HY000](#)

Message: NDB: error %lu (%s) on handling binlog schema event

[ER\\_NDB\\_BINLOG\\_ERROR\\_HANDLING\\_SCHEMA\\_EVENT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010702](#); Symbol: [ER\\_NDB\\_BINLOG\\_CANT\\_INJECT\\_APPLY\\_STATUS\\_WRITE\\_ROW](#); SQLSTATE: [HY000](#)

---

Message: NDB Binlog: Failed to inject apply status write row

[ER\\_NDB\\_BINLOG\\_CANT\\_INJECT\\_APPLY\\_STATUS\\_WRITE\\_ROW](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010703](#); Symbol: [ER\\_NDB\\_BINLOG\\_ERROR\\_DURING\\_GCI\\_ROLLBACK](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Error during ROLLBACK of GCI %u/%u. Error: %d

[ER\\_NDB\\_BINLOG\\_ERROR\\_DURING\\_GCI\\_ROLLBACK](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010704](#); Symbol: [ER\\_NDB\\_BINLOG\\_ERROR\\_DURING\\_GCI\\_COMMIT](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Error during COMMIT of GCI. Error: %d

[ER\\_NDB\\_BINLOG\\_ERROR\\_DURING\\_GCI\\_COMMIT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010705](#); Symbol: [ER\\_NDB\\_BINLOG\\_LATEST\\_TRX\\_IN\\_EPOCH\\_NOT\\_IN\\_BINLOG](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: latest transaction in epoch %u/%u not in binlog as latest handled epoch is %u/%u

[ER\\_NDB\\_BINLOG\\_LATEST\\_TRX\\_IN\\_EPOCH\\_NOT\\_IN\\_BINLOG](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010706](#); Symbol: [ER\\_NDB\\_BINLOG\\_RELEASING\\_EXTRA\\_SHARE\\_REFERENCES](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Release extra share references

[ER\\_NDB\\_BINLOG\\_RELEASING\\_EXTRA\\_SHARE\\_REFERENCES](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010707](#); Symbol: [ER\\_NDB\\_BINLOG\\_REMAINING\\_OPEN\\_TABLES](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: remaining open tables:

[ER\\_NDB\\_BINLOG\\_REMAINING\\_OPEN\\_TABLES](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010708](#); Symbol: [ER\\_NDB\\_BINLOG\\_REMAINING\\_OPEN\\_TABLE\\_INFO](#); SQLSTATE: [HY000](#)

Message: %s.%s state: %u use\_count: %u

[ER\\_NDB\\_BINLOG\\_REMAINING\\_OPEN\\_TABLE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010709](#); Symbol: [ER\\_TREE\\_CORRUPT\\_PARENT\\_SHOULD\\_POINT\\_AT\\_PARENT](#); SQLSTATE: [HY000](#)

Message: Wrong tree: Parent doesn't point at parent

[ER\\_TREE\\_CORRUPT\\_PARENT\\_SHOULD\\_POINT\\_AT\\_PARENT](#) was added in 8.0.2.

- Error number: [MY-010710](#); Symbol: [ER\\_TREE\\_CORRUPT\\_ROOT\\_SHOULD\\_BE\\_BLACK](#); SQLSTATE: [HY000](#)

---

Message: Wrong tree: Root should be black

[ER\\_TREE\\_CORRUPT\\_ROOT\\_SHOULD\\_BE\\_BLACK](#) was added in 8.0.2.

- Error number: [MY-010711](#); Symbol: [ER\\_TREE\\_CORRUPT\\_2\\_CONSECUTIVE\\_REDS](#); SQLSTATE: [HY000](#)

Message: Wrong tree: Found two red in a row

[ER\\_TREE\\_CORRUPT\\_2\\_CONSECUTIVE\\_REDS](#) was added in 8.0.2.

- Error number: [MY-010712](#); Symbol: [ER\\_TREE\\_CORRUPT\\_RIGHT\\_IS\\_LEFT](#); SQLSTATE: [HY000](#)

Message: Wrong tree: Found right == left

[ER\\_TREE\\_CORRUPT\\_RIGHT\\_IS\\_LEFT](#) was added in 8.0.2.

- Error number: [MY-010713](#); Symbol: [ER\\_TREE\\_CORRUPT\\_INCORRECT\\_BLACK\\_COUNT](#); SQLSTATE: [HY000](#)

Message: Wrong tree: Incorrect black-count: %d - %d

[ER\\_TREE\\_CORRUPT\\_INCORRECT\\_BLACK\\_COUNT](#) was added in 8.0.2.

- Error number: [MY-010714](#); Symbol: [ER\\_WRONG\\_COUNT\\_FOR\\_ORIGIN](#); SQLSTATE: [HY000](#)

Message: Use\_count: Wrong count %lu for origin %p

[ER\\_WRONG\\_COUNT\\_FOR\\_ORIGIN](#) was added in 8.0.2.

- Error number: [MY-010715](#); Symbol: [ER\\_WRONG\\_COUNT\\_FOR\\_KEY](#); SQLSTATE: [HY000](#)

Message: Use\_count: Wrong count for key at %p, %lu should be %lu

[ER\\_WRONG\\_COUNT\\_FOR\\_KEY](#) was added in 8.0.2.

- Error number: [MY-010716](#); Symbol: [ER\\_WRONG\\_COUNT\\_OF\\_ELEMENTS](#); SQLSTATE: [HY000](#)

Message: Wrong number of elements: %u (should be %u) for tree at %p

[ER\\_WRONG\\_COUNT\\_OF\\_ELEMENTS](#) was added in 8.0.2.

- Error number: [MY-010717](#); Symbol: [ER\\_RPL\\_ERROR\\_READING\\_SLAVE\\_WORKER\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Error reading slave worker configuration

[ER\\_RPL\\_ERROR\\_READING\\_SLAVE\\_WORKER\\_CONFIGURATION](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010717](#); Symbol: [ER\\_RPL\\_ERROR\\_READING\\_REPLICA\\_WORKER\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Error reading replica worker configuration

[ER\\_RPL\\_ERROR\\_READING\\_REPLICA\\_WORKER\\_CONFIGURATION](#) was added in 8.0.33.

- Error number: [MY-010718](#); Symbol: [ER\\_RPL\\_ERROR\\_WRITING\\_SLAVE\\_WORKER\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

---

Message: Error writing slave worker configuration

[ER\\_RPL\\_ERROR\\_WRITING\\_SLAVE\\_WORKER\\_CONFIGURATION](#) was added in 8.0.2, removed after 8.0.18.

- Error number: [MY-010719](#); Symbol: [ER\\_RPL\\_FAILED\\_TO\\_OPEN\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)

Message: Failed to open relay log %s, error: %s

[ER\\_RPL\\_FAILED\\_TO\\_OPEN\\_RELAY\\_LOG](#) was added in 8.0.2.

- Error number: [MY-010720](#); Symbol: [ER\\_RPL\\_WORKER\\_CANT\\_READ\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)

Message: Error when worker read relay log events, relay log name %s, position %llu

[ER\\_RPL\\_WORKER\\_CANT\\_READ\\_RELAY\\_LOG](#) was added in 8.0.2.

- Error number: [MY-010721](#); Symbol: [ER\\_RPL\\_WORKER\\_CANT\\_FIND\\_NEXT\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)

Message: Failed to find next relay log when retrying the transaction, current relay log is %s

[ER\\_RPL\\_WORKER\\_CANT\\_FIND\\_NEXT\\_RELAY\\_LOG](#) was added in 8.0.2.

- Error number: [MY-010722](#); Symbol: [ER\\_RPL\\_MTS\\_SLAVE\\_COORDINATOR\\_HAS\\_WAITED](#); SQLSTATE: [HY000](#)

Message: Multi-threaded slave: Coordinator has waited %lu times hitting replica\_pending\_jobs\_size\_max; current event size = %zu.

[ER\\_RPL\\_MTS\\_SLAVE\\_COORDINATOR\\_HAS\\_WAITED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010722](#); Symbol: [ER\\_RPL\\_MTA\\_REPLICA\\_COORDINATOR\\_HAS\\_WAITED](#); SQLSTATE: [HY000](#)

Message: Multi-threaded replica: Coordinator has waited %lu times hitting replica\_pending\_jobs\_size\_max; current event size = %zu.

[ER\\_RPL\\_MTA\\_REPLICA\\_COORDINATOR\\_HAS\\_WAITED](#) was added in 8.0.33.

- Error number: [MY-010723](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_WRITE\\_DROP\\_FOR\\_TEMP\\_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to write the DROP statement for temporary tables to binary log

[ER\\_BINLOG\\_FAILED\\_TO\\_WRITE\\_DROP\\_FOR\\_TEMP\\_TABLES](#) was added in 8.0.2.

- Error number: [MY-010724](#); Symbol: [ER\\_BINLOG\\_OOM\\_WRITING\\_DELETE\\_WHILE\\_OPENING\\_HEAP\\_TABLE](#); SQLSTATE: [HY000](#)

Message: When opening HEAP table, could not allocate memory to write 'DELETE FROM ` %s `.` %s ` ' to the binary log

[ER\\_BINLOG\\_OOM\\_WRITING\\_DELETE\\_WHILE\\_OPENING\\_HEAP\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010725](#); Symbol: [ER\\_FAILED\\_TO\\_REPAIR\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Couldn't repair table: %s.%s

---

[ER\\_FAILED\\_TO\\_REPAIR\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010726](#); Symbol: [ER\\_FAILED\\_TO\\_REMOVE\\_TEMP\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Could not remove temporary table: '%s', error: %d

[ER\\_FAILED\\_TO\\_REMOVE\\_TEMP\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010727](#); Symbol: [ER\\_SYSTEM\\_TABLE\\_NOT\\_TRANSACTIONAL](#); SQLSTATE: [HY000](#)

Message: System table '%.\*s' is expected to be transactional.

[ER\\_SYSTEM\\_TABLE\\_NOT\\_TRANSACTIONAL](#) was added in 8.0.2.

- Error number: [MY-010728](#); Symbol: [ER\\_RPL\\_ERROR\\_WRITING\\_MASTER\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Error writing master configuration.

[ER\\_RPL\\_ERROR\\_WRITING\\_MASTER\\_CONFIGURATION](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010728](#); Symbol: [ER\\_RPL\\_ERROR\\_WRITING\\_SOURCE\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Error writing source configuration.

[ER\\_RPL\\_ERROR\\_WRITING\\_SOURCE\\_CONFIGURATION](#) was added in 8.0.33.

- Error number: [MY-010729](#); Symbol: [ER\\_RPL\\_ERROR\\_READING\\_MASTER\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Error reading master configuration.

[ER\\_RPL\\_ERROR\\_READING\\_MASTER\\_CONFIGURATION](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010729](#); Symbol: [ER\\_RPL\\_ERROR\\_READING\\_SOURCE\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Error reading source configuration.

[ER\\_RPL\\_ERROR\\_READING\\_SOURCE\\_CONFIGURATION](#) was added in 8.0.33.

- Error number: [MY-010730](#); Symbol: [ER\\_RPL\\_SSL\\_INFO\\_IN\\_MASTER\\_INFO\\_IGNORED](#); SQLSTATE: [HY000](#)

Message: SSL information in the master info file are ignored because this MySQL slave was compiled without SSL support.

[ER\\_RPL\\_SSL\\_INFO\\_IN\\_MASTER\\_INFO\\_IGNORED](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010730](#); Symbol: [ER\\_RPL\\_SSL\\_INFO\\_IN\\_CONNECTION\\_METADATA\\_IGNORED](#); SQLSTATE: [HY000](#)

Message: SSL information in the connection metadata repository are ignored because this MySQL replica was compiled without SSL support.

[ER\\_RPL\\_SSL\\_INFO\\_IN\\_CONNECTION\\_METADATA\\_IGNORED](#) was added in 8.0.33.

- 
- Error number: `MY-010731`; Symbol: `ER_PLUGIN_FAILED_DEINITIALIZATION`; SQLSTATE: `HY000`  
Message: Plugin '%s' of type %s failed deinitialization  
`ER_PLUGIN_FAILED_DEINITIALIZATION` was added in 8.0.2.
  - Error number: `MY-010732`; Symbol: `ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION`; SQLSTATE: `HY000`  
Message: Plugin '%s' has ref\_count=%d after deinitialization.  
`ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION` was added in 8.0.2.
  - Error number: `MY-010733`; Symbol: `ER_PLUGIN_SHUTTING_DOWN_PLUGIN`; SQLSTATE: `HY000`  
Message: Shutting down plugin '%s'  
`ER_PLUGIN_SHUTTING_DOWN_PLUGIN` was added in 8.0.2.
  - Error number: `MY-010734`; Symbol: `ER_PLUGIN_REGISTRATION_FAILED`; SQLSTATE: `HY000`  
Message: Plugin '%s' registration as a %s failed.  
`ER_PLUGIN_REGISTRATION_FAILED` was added in 8.0.2.
  - Error number: `MY-010735`; Symbol: `ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE`; SQLSTATE: `HY000`  
Message: Could not open the mysql.plugin table. Please perform the MySQL upgrade procedure.  
`ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE` was added in 8.0.2.
  - Error number: `MY-010736`; Symbol: `ER_PLUGIN_CANT_LOAD`; SQLSTATE: `HY000`  
Message: Couldn't load plugin named '%s' with soname '%s'.  
`ER_PLUGIN_CANT_LOAD` was added in 8.0.2.
  - Error number: `MY-010737`; Symbol: `ER_PLUGIN_LOAD_PARAMETER_TOO_LONG`; SQLSTATE: `HY000`  
Message: plugin-load parameter too long  
`ER_PLUGIN_LOAD_PARAMETER_TOO_LONG` was added in 8.0.2.
  - Error number: `MY-010738`; Symbol: `ER_PLUGIN_FORCING_SHUTDOWN`; SQLSTATE: `HY000`  
Message: Plugin '%s' will be forced to shutdown  
`ER_PLUGIN_FORCING_SHUTDOWN` was added in 8.0.2.
  - Error number: `MY-010739`; Symbol: `ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN`; SQLSTATE: `HY000`  
Message: Plugin '%s' has ref\_count=%d after shutdown.  
`ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN` was added in 8.0.2.
  - Error number: `MY-010740`; Symbol: `ER_PLUGIN_UNKNOWN_VARIABLE_TYPE`; SQLSTATE: `HY000`  
Message: Unknown variable type code 0x%x in plugin '%s'.

---

`ER_PLUGIN_UNKNOWN_VARIABLE_TYPE` was added in 8.0.2.

- Error number: `MY-010741`; Symbol: `ER_PLUGIN_VARIABLE_SET_READ_ONLY`; SQLSTATE: `HY000`

Message: Server variable %s of plugin %s was forced to be read-only: string variable without `update_func` and `PLUGIN_VAR_MEMALLOC` flag

`ER_PLUGIN_VARIABLE_SET_READ_ONLY` was added in 8.0.2.

- Error number: `MY-010742`; Symbol: `ER_PLUGIN_VARIABLE_MISSING_NAME`; SQLSTATE: `HY000`

Message: Missing variable name in plugin '%s'.

`ER_PLUGIN_VARIABLE_MISSING_NAME` was added in 8.0.2.

- Error number: `MY-010743`; Symbol: `ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL`; SQLSTATE: `HY000`

Message: Thread local variable '%s' not allocated in plugin '%s'.

`ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL` was added in 8.0.2.

- Error number: `MY-010744`; Symbol: `ER_PLUGIN_OOM`; SQLSTATE: `HY000`

Message: Out of memory for plugin '%s'.

`ER_PLUGIN_OOM` was added in 8.0.2.

- Error number: `MY-010745`; Symbol: `ER_PLUGIN_BAD_OPTIONS`; SQLSTATE: `HY000`

Message: Bad options for plugin '%s'.

`ER_PLUGIN_BAD_OPTIONS` was added in 8.0.2.

- Error number: `MY-010746`; Symbol: `ER_PLUGIN_PARSING_OPTIONS_FAILED`; SQLSTATE: `HY000`

Message: Parsing options for plugin '%s' failed.

`ER_PLUGIN_PARSING_OPTIONS_FAILED` was added in 8.0.2.

- Error number: `MY-010747`; Symbol: `ER_PLUGIN_DISABLED`; SQLSTATE: `HY000`

Message: Plugin '%s' is disabled.

`ER_PLUGIN_DISABLED` was added in 8.0.2.

- Error number: `MY-010748`; Symbol: `ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES`; SQLSTATE: `HY000`

Message: Plugin '%s' has conflicting system variables

`ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES` was added in 8.0.2.

- Error number: `MY-010749`; Symbol: `ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS`; SQLSTATE: `HY000`

Message: Setting persistent options for plugin '%s' failed.

`ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS` was added in 8.0.2.

- 
- Error number: `MY-010750`; Symbol: `ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR`; SQLSTATE: `HY000`  
Message: Failed on my\_net\_write, writing to stderr instead: %s  
`ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR` was added in 8.0.2.
  - Error number: `MY-010751`; Symbol: `ER_RETRYING_REPAIR_WITHOUT_QUICK`; SQLSTATE: `HY000`  
Message: Retrying repair of: '%s' without quick  
`ER_RETRYING_REPAIR_WITHOUT_QUICK` was added in 8.0.2.
  - Error number: `MY-010752`; Symbol: `ER_RETRYING_REPAIR_WITH_KEYCACHE`; SQLSTATE: `HY000`  
Message: Retrying repair of: '%s' with keycache  
`ER_RETRYING_REPAIR_WITH_KEYCACHE` was added in 8.0.2.
  - Error number: `MY-010753`; Symbol: `ER_FOUND_ROWS_WHILE_REPAIRING`; SQLSTATE: `HY000`  
Message: Found %s of %s rows when repairing '%s'  
`ER_FOUND_ROWS_WHILE_REPAIRING` was added in 8.0.2.
  - Error number: `MY-010754`; Symbol: `ER_ERROR_DURING_OPTIMIZE_TABLE`; SQLSTATE: `HY000`  
Message: Warning: Optimize table got errno %d on %s.%s, retrying  
`ER_ERROR_DURING_OPTIMIZE_TABLE` was added in 8.0.2.
  - Error number: `MY-010755`; Symbol: `ER_ERROR_ENABLING_KEYS`; SQLSTATE: `HY000`  
Message: Warning: Enabling keys got errno %d on %s.%s, retrying  
`ER_ERROR_ENABLING_KEYS` was added in 8.0.2.
  - Error number: `MY-010756`; Symbol: `ER_CHECKING_TABLE`; SQLSTATE: `HY000`  
Message: Checking table: '%s'  
`ER_CHECKING_TABLE` was added in 8.0.2.
  - Error number: `MY-010757`; Symbol: `ER_RECOVERING_TABLE`; SQLSTATE: `HY000`  
Message: Recovering table: '%s'  
`ER_RECOVERING_TABLE` was added in 8.0.2.
  - Error number: `MY-010758`; Symbol: `ER_CANT_CREATE_TABLE_SHARE_FROM_FRM`; SQLSTATE: `HY000`  
Message: Error in creating TABLE\_SHARE from %s.frm file.  
`ER_CANT_CREATE_TABLE_SHARE_FROM_FRM` was added in 8.0.2.
  - Error number: `MY-010759`; Symbol: `ER_CANT_LOCK_TABLE`; SQLSTATE: `HY000`  
Message: Unable to acquire lock on %s.%s



---

`ER_CANT_LOCK_TABLE` was added in 8.0.2.

- Error number: `MY-010760`; Symbol: `ER_CANT_ALLOC_TABLE_OBJECT`; SQLSTATE: `HY000`

Message: Error in allocation memory for TABLE object.

`ER_CANT_ALLOC_TABLE_OBJECT` was added in 8.0.2.

- Error number: `MY-010761`; Symbol: `ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE`; SQLSTATE: `HY000`

Message: Error in creating handler object for table %s.%s

`ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE` was added in 8.0.2.

- Error number: `MY-010762`; Symbol: `ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE`; SQLSTATE: `HY000`

Message: Error in setting handler reference for table %s.%s

`ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE` was added in 8.0.2.

- Error number: `MY-010763`; Symbol: `ER_CANT_LOCK_TABLESPACE`; SQLSTATE: `HY000`

Message: Unable to acquire lock on tablespace name %s

`ER_CANT_LOCK_TABLESPACE` was added in 8.0.2.

- Error number: `MY-010764`; Symbol: `ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD`; SQLSTATE: `HY000`

Message: Error in processing generated columns for table %s.%s

`ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD` was added in 8.0.2.

- Error number: `MY-010765`; Symbol: `ER_DD_ERROR_CREATING_ENTRY`; SQLSTATE: `HY000`

Message: Error in Creating DD entry for %s.%s

`ER_DD_ERROR_CREATING_ENTRY` was added in 8.0.2.

- Error number: `MY-010766`; Symbol: `ER_DD_CANT_FETCH_TABLE_DATA`; SQLSTATE: `HY000`

Message: Error in fetching %s.%s table data from dictionary

`ER_DD_CANT_FETCH_TABLE_DATA` was added in 8.0.2.

- Error number: `MY-010767`; Symbol: `ER_DD_CANT_FIX_SE_DATA`; SQLSTATE: `HY000`

Message: Error in fixing SE data for %s.%s

`ER_DD_CANT_FIX_SE_DATA` was added in 8.0.2.

- Error number: `MY-010768`; Symbol: `ER_DD_CANT_CREATE_SP`; SQLSTATE: `HY000`

Message: Error in creating stored program '%s.%s'

`ER_DD_CANT_CREATE_SP` was added in 8.0.2.

- 
- Error number: `MY-010769`; Symbol: `ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET`; SQLSTATE: `HY000`

Message: Unable to open db.opt file %s. Using default Character set.

`ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET` was added in 8.0.2.

- Error number: `MY-010770`; Symbol: `ER_CANT_CREATE_CACHE_FOR_DB_OPT`; SQLSTATE: `HY000`

Message: Unable to initialize IO cache to open db.opt file %s.

`ER_CANT_CREATE_CACHE_FOR_DB_OPT` was added in 8.0.2.

- Error number: `MY-010771`; Symbol: `ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT`; SQLSTATE: `HY000`

Message: Unable to identify the charset in %s. Using default character set.

`ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT` was added in 8.0.2.

- Error number: `MY-010772`; Symbol: `ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET`; SQLSTATE: `HY000`

Message: db.opt file not found for %s database. Using default Character set.

`ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET` was added in 8.0.2.

- Error number: `MY-010773`; Symbol: `ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD`; SQLSTATE: `HY000`

Message: Event '%s'. '%s': invalid value in column mysql.event.time\_zone.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

`ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD` was added in 8.0.2.

- Error number: `MY-010774`; Symbol: `ER_EVENT_CANT_FIND_TIMEZONE`; SQLSTATE: `HY000`

Message: Event '%s'. '%s': has invalid time zone value

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

`ER_EVENT_CANT_FIND_TIMEZONE` was added in 8.0.2.

- Error number: `MY-010775`; Symbol: `ER_EVENT_CANT_GET_CHARSET`; SQLSTATE: `HY000`

Message: Event '%s'. '%s': invalid value in column mysql.event.character\_set\_client.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

`ER_EVENT_CANT_GET_CHARSET` was added in 8.0.2.

- 
- Error number: [MY-010776](#); Symbol: [ER\\_EVENT\\_CANT\\_GET\\_COLLATION](#); SQLSTATE: [HY000](#)

Message: Event '%s'. '%s': invalid value in column mysql.event.collation\_connection.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

[ER\\_EVENT\\_CANT\\_GET\\_COLLATION](#) was added in 8.0.2.

- Error number: [MY-010777](#); Symbol: [ER\\_EVENT\\_CANT\\_OPEN\\_TABLE\\_MYSQL\\_EVENT](#); SQLSTATE: [HY000](#)

Message: Failed to open mysql.event Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

[ER\\_EVENT\\_CANT\\_OPEN\\_TABLE\\_MYSQL\\_EVENT](#) was added in 8.0.2.

- Error number: [MY-010778](#); Symbol: [ER\\_CANT\\_PARSE\\_STORED\\_ROUTINE\\_BODY](#); SQLSTATE: [HY000](#)

Message: Parsing '%s.%s' routine body failed.%s

[ER\\_CANT\\_PARSE\\_STORED\\_ROUTINE\\_BODY](#) was added in 8.0.2.

- Error number: [MY-010779](#); Symbol: [ER\\_CANT\\_OPEN\\_TABLE\\_MYSQL\\_PROC](#); SQLSTATE: [HY000](#)

Message: Failed to open mysql.proc Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.proc` system table and migrates its contents to the internal data dictionary.

[ER\\_CANT\\_OPEN\\_TABLE\\_MYSQL\\_PROC](#) was added in 8.0.2.

- Error number: [MY-010780](#); Symbol: [ER\\_CANT\\_READ\\_TABLE\\_MYSQL\\_PROC](#); SQLSTATE: [HY000](#)

Message: Failed to read mysql.proc table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.proc` system table and migrates its contents to the internal data dictionary.

[ER\\_CANT\\_READ\\_TABLE\\_MYSQL\\_PROC](#) was added in 8.0.2.

- Error number: [MY-010781](#); Symbol: [ER\\_FILE\\_EXISTS\\_DURING\\_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Found %s file in mysql schema. DD will create .ibd file with same name. Please rename table and start upgrade process again.

[ER\\_FILE\\_EXISTS\\_DURING\\_UPGRADE](#) was added in 8.0.2.

- Error number: [MY-010782](#); Symbol: [ER\\_CANT\\_OPEN\\_DATADIR\\_AFTER\\_UPGRADE\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Unable to open the data directory %s during clean up after upgrade failed

[ER\\_CANT\\_OPEN\\_DATADIR\\_AFTER\\_UPGRADE\\_FAILURE](#) was added in 8.0.2.

- 
- Error number: [MY-010783](#); Symbol: [ER\\_CANT\\_SET\\_PATH\\_FOR](#); SQLSTATE: [HY000](#)  
Message: Failed to set path %s  
[ER\\_CANT\\_SET\\_PATH\\_FOR](#) was added in 8.0.2.
  - Error number: [MY-010784](#); Symbol: [ER\\_CANT\\_OPEN\\_DIR](#); SQLSTATE: [HY000](#)  
Message: Failed to open dir %s  
[ER\\_CANT\\_OPEN\\_DIR](#) was added in 8.0.2.
  - Error number: [MY-010785](#); Symbol: [ER\\_NDB\\_EMPTY\\_NODEID\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#); SQLSTATE: [HY000](#)  
Message: NDB: Found empty nodeid specified in --ndb-cluster-connection-pool-nodeids='%s'.  
[ER\\_NDB\\_EMPTY\\_NODEID\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010786](#); Symbol: [ER\\_NDB\\_CANT\\_PARSE\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#); SQLSTATE: [HY000](#)  
Message: NDB: Could not parse '%s' in --ndb-cluster-connection-pool-nodeids='%s'.  
[ER\\_NDB\\_CANT\\_PARSE\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010787](#); Symbol: [ER\\_NDB\\_INVALID\\_NODEID\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#); SQLSTATE: [HY000](#)  
Message: NDB: Invalid nodeid %d in --ndb-cluster-connection-pool-nodeids='%s'.  
[ER\\_NDB\\_INVALID\\_NODEID\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010788](#); Symbol: [ER\\_NDB\\_DUPLICATE\\_NODEID\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#); SQLSTATE: [HY000](#)  
Message: NDB: Found duplicate nodeid %d in --ndb-cluster-connection-pool-nodeids='%s'.  
[ER\\_NDB\\_DUPLICATE\\_NODEID\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010789](#); Symbol: [ER\\_NDB\\_POOL\\_SIZE\\_MUST\\_MATCH\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#); SQLSTATE: [HY000](#)  
Message: NDB: The size of the cluster connection pool must be equal to the number of nodeids in --ndb-cluster-connection-pool-nodeids='%s'.  
[ER\\_NDB\\_POOL\\_SIZE\\_MUST\\_MATCH\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
  - Error number: [MY-010790](#); Symbol: [ER\\_NDB\\_NODEID\\_NOT\\_FIRST\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#); SQLSTATE: [HY000](#)

---

Message: NDB: The nodeid specified by --ndb-nodeid must be equal to the first nodeid in --ndb-cluster-connection-pool-nodeids='%s'.

[ER\\_NDB\\_NODEID\\_NOT\\_FIRST\\_IN\\_NDB\\_CLUSTER\\_CONNECTION\\_POOL\\_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010791](#); Symbol: [ER\\_NDB\\_USING\\_NODEID](#); SQLSTATE: [HY000](#)

Message: NDB: using nodeid %u

[ER\\_NDB\\_USING\\_NODEID](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010792](#); Symbol: [ER\\_NDB\\_CANT\\_ALLOC\\_GLOBAL\\_NDB\\_CLUSTER\\_CONNECTION](#); SQLSTATE: [HY000](#)

Message: NDB: failed to allocate global ndb cluster connection

[ER\\_NDB\\_CANT\\_ALLOC\\_GLOBAL\\_NDB\\_CLUSTER\\_CONNECTION](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010793](#); Symbol: [ER\\_NDB\\_CANT\\_ALLOC\\_GLOBAL\\_NDB\\_OBJECT](#); SQLSTATE: [HY000](#)

Message: NDB: failed to allocate global ndb object

[ER\\_NDB\\_CANT\\_ALLOC\\_GLOBAL\\_NDB\\_OBJECT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010794](#); Symbol: [ER\\_NDB\\_USING\\_NODEID\\_LIST](#); SQLSTATE: [HY000](#)

Message: NDB[%u]: using nodeid %u

[ER\\_NDB\\_USING\\_NODEID\\_LIST](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010795](#); Symbol: [ER\\_NDB\\_CANT\\_ALLOC\\_NDB\\_CLUSTER\\_CONNECTION](#); SQLSTATE: [HY000](#)

Message: NDB[%u]: failed to allocate cluster connect object

[ER\\_NDB\\_CANT\\_ALLOC\\_NDB\\_CLUSTER\\_CONNECTION](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010796](#); Symbol: [ER\\_NDB\\_STARTING\\_CONNECT\\_THREAD](#); SQLSTATE: [HY000](#)

Message: NDB[%u]: starting connect thread

[ER\\_NDB\\_STARTING\\_CONNECT\\_THREAD](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010797](#); Symbol: [ER\\_NDB\\_NODE\\_INFO](#); SQLSTATE: [HY000](#)

Message: NDB[%u]: NodeID: %d, %s

[ER\\_NDB\\_NODE\\_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010798](#); Symbol: [ER\\_NDB\\_CANT\\_START\\_CONNECT\\_THREAD](#); SQLSTATE: [HY000](#)

Message: NDB[%u]: failed to start connect thread

[ER\\_NDB\\_CANT\\_START\\_CONNECT\\_THREAD](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010799](#); Symbol: [ER\\_NDB\\_GENERIC\\_ERROR](#); SQLSTATE: [HY000](#)

---

Message: NDB: error (%u) %s

[ER\\_NDB\\_GENERIC\\_ERROR](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010800](#); Symbol: [ER\\_NDB\\_CPU\\_MASK\\_TOO\\_SHORT](#); SQLSTATE: [HY000](#)

Message: Ignored receive thread CPU mask, mask too short, %u CPUs needed in mask, only %u CPUs provided

[ER\\_NDB\\_CPU\\_MASK\\_TOO\\_SHORT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010801](#); Symbol: [ER\\_EVENT\\_ERROR\\_CREATING\\_QUERY\\_TO\\_WRITE\\_TO\\_BINLOG](#); SQLSTATE: [HY000](#)

Message: Event Error: An error occurred while creating query string, before writing it into binary log.

[ER\\_EVENT\\_ERROR\\_CREATING\\_QUERY\\_TO\\_WRITE\\_TO\\_BINLOG](#) was added in 8.0.2.

- Error number: [MY-010802](#); Symbol: [ER\\_EVENT\\_SCHEDULER\\_ERROR\\_LOADING\\_FROM\\_DB](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error while loading from disk.

[ER\\_EVENT\\_SCHEDULER\\_ERROR\\_LOADING\\_FROM\\_DB](#) was added in 8.0.2.

- Error number: [MY-010803](#); Symbol: [ER\\_EVENT\\_SCHEDULER\\_ERROR\\_GETTING\\_EVENT\\_OBJECT](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error getting event object.

[ER\\_EVENT\\_SCHEDULER\\_ERROR\\_GETTING\\_EVENT\\_OBJECT](#) was added in 8.0.2.

- Error number: [MY-010804](#); Symbol: [ER\\_EVENT\\_SCHEDULER\\_GOT\\_BAD\\_DATA\\_FROM\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error while loading events from mysql.events. The table probably contains bad data or is corrupted

[ER\\_EVENT\\_SCHEDULER\\_GOT\\_BAD\\_DATA\\_FROM\\_TABLE](#) was added in 8.0.2.

- Error number: [MY-010805](#); Symbol: [ER\\_EVENT\\_CANT\\_GET\\_LOCK\\_FOR\\_DROPPING\\_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to obtain lock for dropping event %s from schema %s

[ER\\_EVENT\\_CANT\\_GET\\_LOCK\\_FOR\\_DROPPING\\_EVENT](#) was added in 8.0.2.

- Error number: [MY-010806](#); Symbol: [ER\\_EVENT\\_UNABLE\\_TO\\_DROP\\_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to drop event %s from schema %s

[ER\\_EVENT\\_UNABLE\\_TO\\_DROP\\_EVENT](#) was added in 8.0.2.

- Error number: [MY-010807](#); Symbol: [ER\\_BINLOG\\_ATTACHING\\_THREAD\\_MEMORY\\_FINALY\\_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: Server overcomes the temporary 'out of memory' in '%d' tries while attaching to session thread during the group commit phase.

---

[ER\\_BINLOG\\_ATTACHING\\_THREAD\\_MEMORY\\_FINALY\\_AVAILABLE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010808](#); Symbol: [ER\\_BINLOG\\_CANT\\_RESIZE\\_CACHE](#); SQLSTATE: [HY000](#)

Message: Unable to resize binlog IOCACHE auxiliary file

[ER\\_BINLOG\\_CANT\\_RESIZE\\_CACHE](#) was added in 8.0.2.

- Error number: [MY-010809](#); Symbol: [ER\\_BINLOG\\_FILE\\_BEING\\_READ\\_NOT\\_PURGED](#); SQLSTATE: [HY000](#)

Message: file %s was not purged because it was being read by thread number %u

[ER\\_BINLOG\\_FILE\\_BEING\\_READ\\_NOT\\_PURGED](#) was added in 8.0.2.

- Error number: [MY-010810](#); Symbol: [ER\\_BINLOG\\_IO\\_ERROR\\_READING\\_HEADER](#); SQLSTATE: [HY000](#)

Message: I/O error reading the header from the binary log, errno=%d, io cache code=%d

[ER\\_BINLOG\\_IO\\_ERROR\\_READING\\_HEADER](#) was added in 8.0.2.

- Error number: [MY-010811](#); Symbol: [ER\\_BINLOG\\_CANT\\_OPEN\\_LOG](#); SQLSTATE: [HY000](#)

Message: Failed to open log (file '%s', errno %d)

[ER\\_BINLOG\\_CANT\\_OPEN\\_LOG](#) was added in 8.0.2, removed after 8.0.12.

- Error number: [MY-010812](#); Symbol: [ER\\_BINLOG\\_CANT\\_CREATE\\_CACHE\\_FOR\\_LOG](#); SQLSTATE: [HY000](#)

Message: Failed to create a cache on log (file '%s')

[ER\\_BINLOG\\_CANT\\_CREATE\\_CACHE\\_FOR\\_LOG](#) was added in 8.0.2, removed after 8.0.12.

- Error number: [MY-010813](#); Symbol: [ER\\_BINLOG\\_FILE\\_EXTENSION\\_NUMBER\\_EXHAUSTED](#); SQLSTATE: [HY000](#)

Message: Log filename extension number exhausted: %06lu. Please fix this by archiving old logs and updating the index files.

[ER\\_BINLOG\\_FILE\\_EXTENSION\\_NUMBER\\_EXHAUSTED](#) was added in 8.0.2.

- Error number: [MY-010814](#); Symbol: [ER\\_BINLOG\\_FILE\\_NAME\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)

Message: Log filename too large: %s%s (%zu). Please fix this by archiving old logs and updating the index files.

[ER\\_BINLOG\\_FILE\\_NAME\\_TOO\\_LONG](#) was added in 8.0.2.

- Error number: [MY-010815](#); Symbol: [ER\\_BINLOG\\_FILE\\_EXTENSION\\_NUMBER\\_RUNNING\\_LOW](#); SQLSTATE: [HY000](#)

Message: Next log extension: %lu. Remaining log filename extensions: %lu. Please consider archiving some logs.

[ER\\_BINLOG\\_FILE\\_EXTENSION\\_NUMBER\\_RUNNING\\_LOW](#) was added in 8.0.2.

- 
- Error number: [MY-010816](#); Symbol: [ER\\_BINLOG\\_CANT\\_OPEN\\_FOR\\_LOGGING](#); SQLSTATE: [HY000](#)  
Message: Could not open %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.  
[ER\\_BINLOG\\_CANT\\_OPEN\\_FOR\\_LOGGING](#) was added in 8.0.2.
  - Error number: [MY-010817](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_SYNC\\_INDEX\\_FILE](#); SQLSTATE: [HY000](#)  
Message: MYSQL\_BIN\_LOG::open\_index\_file failed to sync the index file.  
[ER\\_BINLOG\\_FAILED\\_TO\\_SYNC\\_INDEX\\_FILE](#) was added in 8.0.2.
  - Error number: [MY-010818](#); Symbol: [ER\\_BINLOG\\_ERROR\\_READING\\_GTIDS\\_FROM\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Error reading GTIDs from relaylog: %d  
[ER\\_BINLOG\\_ERROR\\_READING\\_GTIDS\\_FROM\\_RELAY\\_LOG](#) was added in 8.0.2.
  - Error number: [MY-010819](#); Symbol: [ER\\_BINLOG\\_EVENTS\\_READ\\_FROM\\_RELAY\\_LOG\\_INFO](#); SQLSTATE: [HY000](#)  
Message: %lu events read in relaylog file '%s' for updating Retrieved\_Gtid\_Set and/or IO thread transaction parser state.  
[ER\\_BINLOG\\_EVENTS\\_READ\\_FROM\\_RELAY\\_LOG\\_INFO](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-010819](#); Symbol: [ER\\_BINLOG\\_EVENTS\\_READ\\_FROM\\_APPLIER\\_METADATA](#); SQLSTATE: [HY000](#)  
Message: %lu events read in relaylog file '%s' for updating Retrieved\_Gtid\_Set and/or IO thread transaction parser state.  
[ER\\_BINLOG\\_EVENTS\\_READ\\_FROM\\_APPLIER\\_METADATA](#) was added in 8.0.33.
  - Error number: [MY-010820](#); Symbol: [ER\\_BINLOG\\_ERROR\\_READING\\_GTIDS\\_FROM\\_BINARY\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Error reading GTIDs from binary log: %d  
[ER\\_BINLOG\\_ERROR\\_READING\\_GTIDS\\_FROM\\_BINARY\\_LOG](#) was added in 8.0.2.
  - Error number: [MY-010821](#); Symbol: [ER\\_BINLOG\\_EVENTS\\_READ\\_FROM\\_BINLOG\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Read %lu events from binary log file '%s' to determine the GTIDs purged from binary logs.  
[ER\\_BINLOG\\_EVENTS\\_READ\\_FROM\\_BINLOG\\_INFO](#) was added in 8.0.2.
  - Error number: [MY-010822](#); Symbol: [ER\\_BINLOG\\_CANT\\_GENERATE\\_NEW\\_FILE\\_NAME](#); SQLSTATE: [HY000](#)  
Message: MYSQL\_BIN\_LOG::open failed to generate new file name.  
[ER\\_BINLOG\\_CANT\\_GENERATE\\_NEW\\_FILE\\_NAME](#) was added in 8.0.2.
-



- 
- Error number: `MY-010823`; Symbol: `ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN`; SQLSTATE: `HY000`  
Message: `MYSQL_BIN_LOG::open` failed to sync the index file.  
`ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN` was added in 8.0.2.
  - Error number: `MY-010824`; Symbol: `ER_BINLOG_CANT_USE_FOR_LOGGING`; SQLSTATE: `HY000`  
Message: Could not use %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.  
`ER_BINLOG_CANT_USE_FOR_LOGGING` was added in 8.0.2.
  - Error number: `MY-010825`; Symbol: `ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING`; SQLSTATE: `HY000`  
Message: While rebuilding index file %s: Failed to close the index file.  
`ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING` was added in 8.0.2.
  - Error number: `MY-010826`; Symbol: `ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING`; SQLSTATE: `HY000`  
Message: While rebuilding index file %s: Failed to delete the existing index file. It could be that file is being used by some other process.  
`ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING` was added in 8.0.2.
  - Error number: `MY-010827`; Symbol: `ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING`; SQLSTATE: `HY000`  
Message: While rebuilding index file %s: Failed to rename the new index file to the existing index file.  
`ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING` was added in 8.0.2.
  - Error number: `MY-010828`; Symbol: `ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING`; SQLSTATE: `HY000`  
Message: After rebuilding the index file %s: Failed to open the index file.  
`ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING` was added in 8.0.2.
  - Error number: `MY-010829`; Symbol: `ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX`; SQLSTATE: `HY000`  
Message: `MYSQL_BIN_LOG::add_log_to_index` failed to append log file name: %s, to crash safe index file.  
`ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX` was added in 8.0.2.
  - Error number: `MY-010830`; Symbol: `ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG_FILES`; SQLSTATE: `HY000`  
Message: Failed to locate old binlog or relay log files  
`ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG_FILES` was added in 8.0.2.
  - Error number: `MY-010831`; Symbol: `ER_BINLOG_CANT_DELETE_FILE`; SQLSTATE: `HY000`
-

---

Message: Failed to delete file '%s'

`ER_BINLOG_CANT_DELETE_FILE` was added in 8.0.2.

- Error number: `MY-010832`; Symbol: `ER_BINLOG_CANT_SET_TMP_INDEX_NAME`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::set_crash_safe_index_file_name` failed to set file name.

`ER_BINLOG_CANT_SET_TMP_INDEX_NAME` was added in 8.0.2.

- Error number: `MY-010833`; Symbol: `ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::open_crash_safe_index_file` failed to open temporary index file.

`ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE` was added in 8.0.2.

- Error number: `MY-010834`; Symbol: `ER_BINLOG_ERROR_GETTING_NEXT_LOG_FROM_INDEX`; SQLSTATE: `HY000`

Message: next log error: %d offset: %s log: %s included: %d

`ER_BINLOG_ERROR_GETTING_NEXT_LOG_FROM_INDEX` was added in 8.0.2, removed after 8.0.12.

- Error number: `MY-010835`; Symbol: `ER_BINLOG_CANT_OPEN_TMP_INDEX`; SQLSTATE: `HY000`

Message: %s failed to open the crash safe index file.

`ER_BINLOG_CANT_OPEN_TMP_INDEX` was added in 8.0.2.

- Error number: `MY-010836`; Symbol: `ER_BINLOG_CANT_COPY_INDEX_TO_TMP`; SQLSTATE: `HY000`

Message: %s failed to copy index file to crash safe index file.

`ER_BINLOG_CANT_COPY_INDEX_TO_TMP` was added in 8.0.2.

- Error number: `MY-010837`; Symbol: `ER_BINLOG_CANT_CLOSE_TMP_INDEX`; SQLSTATE: `HY000`

Message: %s failed to close the crash safe index file.

`ER_BINLOG_CANT_CLOSE_TMP_INDEX` was added in 8.0.2.

- Error number: `MY-010838`; Symbol: `ER_BINLOG_CANT_MOVE_TMP_TO_INDEX`; SQLSTATE: `HY000`

Message: %s failed to move crash safe index file to index file.

`ER_BINLOG_CANT_MOVE_TMP_TO_INDEX` was added in 8.0.2.

- Error number: `MY-010839`; Symbol:

`ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN_INDEX`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_logs` was called with file %s not listed in the index.

`ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN_INDEX` was added in 8.0.2.

- Error number: `MY-010840`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_logs` failed to sync the index file.

---

`ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE` was added in 8.0.2.

- Error number: `MY-010841`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_logs` failed to copy %s to register file.

`ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER_FILE` was added in 8.0.2.

- Error number: `MY-010842`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_logs` failed to flush register file.

`ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE` was added in 8.0.2.

- Error number: `MY-010843`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_logs` failed to update the index file

`ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE` was added in 8.0.2.

- Error number: `MY-010844`; Symbol: `ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_logs` failed to process registered files that would be purged.

`ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG` was added in 8.0.2.

- Error number: `MY-010845`; Symbol: `ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::set_purge_index_file_name` failed to set file name.

`ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME` was added in 8.0.2.

- Error number: `MY-010846`; Symbol: `ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::open_purge_index_file` failed to open register file.

`ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE` was added in 8.0.2.

- Error number: `MY-010847`; Symbol: `ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_index_entry` failed to reinit register file for read

`ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE` was added in 8.0.2.

- Error number: `MY-010848`; Symbol: `ER_BINLOG_FAILED_TO_READ_REGISTER_FILE`; SQLSTATE: `HY000`

Message: `MYSQL_BIN_LOG::purge_index_entry` error %d reading from register file.

`ER_BINLOG_FAILED_TO_READ_REGISTER_FILE` was added in 8.0.2.

- 
- Error number: `MY-010849`; Symbol: `ER_CANT_STAT_FILE`; SQLSTATE: `HY000`  
Message: Failed to execute `mysql_file_stat` on file '%s'  
`ER_CANT_STAT_FILE` was added in 8.0.2.
  - Error number: `MY-010850`; Symbol: `ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH_FILES`; SQLSTATE: `HY000`  
Message: Failed to delete log file '%s'; consider examining correspondence of your binlog index file to the actual binlog files  
`ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH_FILES` was added in 8.0.2.
  - Error number: `MY-010851`; Symbol: `ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_INDEX`; SQLSTATE: `HY000`  
Message: Failed to delete file '%s' and read the binlog index file  
`ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_INDEX` was added in 8.0.2.
  - Error number: `MY-010852`; Symbol: `ER_BINLOG_FAILED_TO_DELETE_LOG_FILE`; SQLSTATE: `HY000`  
Message: Failed to delete log file '%s'  
`ER_BINLOG_FAILED_TO_DELETE_LOG_FILE` was added in 8.0.2.
  - Error number: `MY-010853`; Symbol: `ER_BINLOG_LOGGING_INCIDENT_TO_STOP_SLAVES`; SQLSTATE: `HY000`  
Message: %s An incident event has been written to the binary log which will stop the slaves.  
`ER_BINLOG_LOGGING_INCIDENT_TO_STOP_SLAVES` was added in 8.0.2, removed after 8.0.32.
  - Error number: `MY-010853`; Symbol: `ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS`; SQLSTATE: `HY000`  
Message: %s An incident event has been written to the binary log which will stop the replicas.  
`ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS` was added in 8.0.33.
  - Error number: `MY-010854`; Symbol: `ER_BINLOG_CANT_FIND_LOG_IN_INDEX`; SQLSTATE: `HY000`  
Message: `find_log_pos()` failed (error: %d)  
`ER_BINLOG_CANT_FIND_LOG_IN_INDEX` was added in 8.0.2.
  - Error number: `MY-010855`; Symbol: `ER_BINLOG_RECOVERING_AFTER_CRASH_USING`; SQLSTATE: `HY000`  
Message: Recovering after a crash using %s  
`ER_BINLOG_RECOVERING_AFTER_CRASH_USING` was added in 8.0.2.

- 
- Error number: [MY-010856](#); Symbol: [ER\\_BINLOG\\_CANT\\_OPEN\\_CRASHED\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: Failed to open the crashed binlog file when source server is recovering it.  
[ER\\_BINLOG\\_CANT\\_OPEN\\_CRASHED\\_BINLOG](#) was added in 8.0.2.
  - Error number: [MY-010857](#); Symbol: [ER\\_BINLOG\\_CANT\\_TRIM\\_CRASHED\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: Failed to trim the crashed binlog file when source server is recovering it.  
[ER\\_BINLOG\\_CANT\\_TRIM\\_CRASHED\\_BINLOG](#) was added in 8.0.2.
  - Error number: [MY-010858](#); Symbol: [ER\\_BINLOG\\_CRASHED\\_BINLOG\\_TRIMMED](#); SQLSTATE: [HY000](#)  
Message: Crashed binlog file %s size is %llu, but recovered up to %llu. Binlog trimmed to %llu bytes.  
[ER\\_BINLOG\\_CRASHED\\_BINLOG\\_TRIMMED](#) was added in 8.0.2.
  - Error number: [MY-010859](#); Symbol: [ER\\_BINLOG\\_CANT\\_CLEAR\\_IN\\_USE\\_FLAG\\_FOR\\_CRASHED\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: Failed to clear LOG\_EVENT\_BINLOG\_IN\_USE\_F for the crashed binlog file when source server is recovering it.  
[ER\\_BINLOG\\_CANT\\_CLEAR\\_IN\\_USE\\_FLAG\\_FOR\\_CRASHED\\_BINLOG](#) was added in 8.0.2.
  - Error number: [MY-010860](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_RUN\\_AFTER\\_SYNC\\_HOOK](#); SQLSTATE: [HY000](#)  
Message: Failed to run 'after\_sync' hooks  
[ER\\_BINLOG\\_FAILED\\_TO\\_RUN\\_AFTER\\_SYNC\\_HOOK](#) was added in 8.0.2.
  - Error number: [MY-010861](#); Symbol: [ER\\_TURNING\\_LOGGING\\_OFF\\_FOR\\_THE\\_DURATION](#); SQLSTATE: [HY000](#)  
Message: %s Hence turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.  
[ER\\_TURNING\\_LOGGING\\_OFF\\_FOR\\_THE\\_DURATION](#) was added in 8.0.2.
  - Error number: [MY-010862](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_RUN\\_AFTER\\_FLUSH\\_HOOK](#); SQLSTATE: [HY000](#)  
Message: Failed to run 'after\_flush' hooks  
[ER\\_BINLOG\\_FAILED\\_TO\\_RUN\\_AFTER\\_FLUSH\\_HOOK](#) was added in 8.0.2.
  - Error number: [MY-010863](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Crash recovery failed. Either correct the problem (if it's, for example, out of memory error) and restart, or delete (or rename) binary log and start mysqld with --tc-heuristic-recover={commit|rollback}  
[ER\\_BINLOG\\_CRASH\\_RECOVERY\\_FAILED](#) was added in 8.0.2, removed after 8.0.29.
-

- 
- Error number: `MY-010864`; Symbol: `ER_BINLOG_WARNING_SUPPRESSED`; SQLSTATE: `HY000`  
Message: The following warning was suppressed %d times during the last %d seconds in the error log  
`ER_BINLOG_WARNING_SUPPRESSED` was added in 8.0.2.
  - Error number: `MY-010865`; Symbol: `ER_NDB_LOG_ENTRY`; SQLSTATE: `HY000`  
Message: NDB: %s  
`ER_NDB_LOG_ENTRY` was added in 8.0.2.
  - Error number: `MY-010866`; Symbol: `ER_NDB_LOG_ENTRY_WITH_PREFIX`; SQLSTATE: `HY000`  
Message: NDB %s: %s  
`ER_NDB_LOG_ENTRY_WITH_PREFIX` was added in 8.0.2.
  - Error number: `MY-010867`; Symbol: `ER_NDB_BINLOG_CANT_CREATE_PURGE_THD`; SQLSTATE: `HY000`  
Message: NDB: Unable to purge %s.%s File=%s (failed to setup thd)  
`ER_NDB_BINLOG_CANT_CREATE_PURGE_THD` was added in 8.0.2, removed after 8.0.13.
  - Error number: `MY-010868`; Symbol: `ER_INNODB_UNKNOWN_COLLATION`; SQLSTATE: `HY000`  
Message: Unknown collation #%lu.  
`ER_INNODB_UNKNOWN_COLLATION` was added in 8.0.2.
  - Error number: `MY-010869`; Symbol: `ER_INNODB_INVALID_LOG_GROUP_HOME_DIR`; SQLSTATE: `HY000`  
Message: syntax error in innodb\_log\_group\_home\_dir  
`ER_INNODB_INVALID_LOG_GROUP_HOME_DIR` was added in 8.0.2.
  - Error number: `MY-010870`; Symbol: `ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY`; SQLSTATE: `HY000`  
Message: syntax error in innodb\_undo\_directory  
`ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY` was added in 8.0.2.
  - Error number: `MY-010871`; Symbol: `ER_INNODB_ILLEGAL_COLON_IN_POOL`; SQLSTATE: `HY000`  
Message: InnoDB: innodb\_buffer\_pool\_filename cannot have colon (:) in the file name.  
`ER_INNODB_ILLEGAL_COLON_IN_POOL` was added in 8.0.2.
  - Error number: `MY-010872`; Symbol: `ER_INNODB_INVALID_PAGE_SIZE`; SQLSTATE: `HY000`  
Message: InnoDB: Invalid page size=%lu.  
`ER_INNODB_INVALID_PAGE_SIZE` was added in 8.0.2.

- 
- Error number: [MY-010873](#); Symbol: [ER\\_INNODB\\_DIRTY\\_WATER\\_MARK\\_NOT\\_LOW](#); SQLSTATE: [HY000](#)  
Message: InnoDB: innodb\_max\_dirty\_pages\_pct\_lwm cannot be set higher than innodb\_max\_dirty\_pages\_pct. Setting innodb\_max\_dirty\_pages\_pct\_lwm to %lf  
[ER\\_INNODB\\_DIRTY\\_WATER\\_MARK\\_NOT\\_LOW](#) was added in 8.0.2.
  - Error number: [MY-010874](#); Symbol: [ER\\_INNODB\\_IO\\_CAPACITY\\_EXCEEDS\\_MAX](#); SQLSTATE: [HY000](#)  
Message: InnoDB: innodb\_io\_capacity cannot be set higher than innodb\_io\_capacity\_max. Setting innodb\_io\_capacity to %lu  
[ER\\_INNODB\\_IO\\_CAPACITY\\_EXCEEDS\\_MAX](#) was added in 8.0.2.
  - Error number: [MY-010875](#); Symbol: [ER\\_INNODB\\_FILES\\_SAME](#); SQLSTATE: [HY000](#)  
Message: %s and %s file names seem to be the same.  
[ER\\_INNODB\\_FILES\\_SAME](#) was added in 8.0.2.
  - Error number: [MY-010876](#); Symbol: [ER\\_INNODB\\_UNREGISTERED\\_TRX\\_ACTIVE](#); SQLSTATE: [HY000](#)  
Message: Transaction not registered for MySQL 2PC, but transaction is active  
[ER\\_INNODB\\_UNREGISTERED\\_TRX\\_ACTIVE](#) was added in 8.0.2.
  - Error number: [MY-010877](#); Symbol: [ER\\_INNODB\\_CLOSING\\_CONNECTION\\_ROLLS\\_BACK](#); SQLSTATE: [HY000](#)  
Message: MySQL is closing a connection that has an active InnoDB transaction. %llu row modifications will roll back.  
[ER\\_INNODB\\_CLOSING\\_CONNECTION\\_ROLLS\\_BACK](#) was added in 8.0.2.
  - Error number: [MY-010878](#); Symbol: [ER\\_INNODB\\_TRX\\_XLATION\\_TABLE\\_OOM](#); SQLSTATE: [HY000](#)  
Message: InnoDB: fail to allocate memory for index translation table. Number of Index:%lu, array size: %lu  
[ER\\_INNODB\\_TRX\\_XLATION\\_TABLE\\_OOM](#) was added in 8.0.2.
  - Error number: [MY-010879](#); Symbol: [ER\\_INNODB\\_CANT\\_FIND\\_INDEX\\_IN\\_INNODB\\_DD](#); SQLSTATE: [HY000](#)  
Message: Cannot find index %s in InnoDB index dictionary.  
[ER\\_INNODB\\_CANT\\_FIND\\_INDEX\\_IN\\_INNODB\\_DD](#) was added in 8.0.2.
  - Error number: [MY-010880](#); Symbol: [ER\\_INNODB\\_INDEX\\_COLUMN\\_INFO\\_UNLIKE\\_MYSQLS](#); SQLSTATE: [HY000](#)  
Message: Found index %s whose column info does not match that of MySQL.  
[ER\\_INNODB\\_INDEX\\_COLUMN\\_INFO\\_UNLIKE\\_MYSQLS](#) was added in 8.0.2.

- 
- Error number: `MY-010881`; Symbol: `ER_INNODB_CANT_OPEN_TABLE`; SQLSTATE: `HY000`  
Message: Failed to open table %s.  
`ER_INNODB_CANT_OPEN_TABLE` was added in 8.0.2, removed after 8.0.18.
  - Error number: `MY-010882`; Symbol: `ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR`; SQLSTATE: `HY000`  
Message: Build InnoDB index translation table for Table %s failed  
`ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR` was added in 8.0.2.
  - Error number: `MY-010883`; Symbol: `ER_INNODB_PK_NOT_IN_MYSQL`; SQLSTATE: `HY000`  
Message: Table %s has a primary key in InnoDB data dictionary, but not in MySQL!  
`ER_INNODB_PK_NOT_IN_MYSQL` was added in 8.0.2.
  - Error number: `MY-010884`; Symbol: `ER_INNODB_PK_ONLY_IN_MYSQL`; SQLSTATE: `HY000`  
Message: Table %s has no primary key in InnoDB data dictionary, but has one in MySQL! If you created the table with a MySQL version < 3.23.54 and did not define a primary key, but defined a unique key with all non-NULL columns, then MySQL internally treats that key as the primary key. You can fix this error by dump + DROP + CREATE + reimport of the table.  
`ER_INNODB_PK_ONLY_IN_MYSQL` was added in 8.0.2.
  - Error number: `MY-010885`; Symbol: `ER_INNODB_CLUSTERED_INDEX_PRIVATE`; SQLSTATE: `HY000`  
Message: Table %s key\_used\_on\_scan is %lu even though there is no primary key inside InnoDB.  
`ER_INNODB_CLUSTERED_INDEX_PRIVATE` was added in 8.0.2.
  - Error number: `MY-010886`; Symbol: `ER_INNODB_PARTITION_TABLE_LOWERCASED`; SQLSTATE: `HY000`  
Message: Partition table %s opened after converting to lower case. The table may have been moved from a case-insensitive file system. Please recreate the table in the current file system.  
`ER_INNODB_PARTITION_TABLE_LOWERCASED` was added in 8.0.2, removed after 8.0.18.
  - Error number: `MY-010887`; Symbol: `ER_ERRMSG_REPLACEMENT_DODGY`; SQLSTATE: `HY000`  
Message: Cannot replace error message (%s,%s,%s) "%s" with "%s"; wrong number or type of %% substitutions.  
`ER_ERRMSG_REPLACEMENT_DODGY` was added in 8.0.2.
  - Error number: `MY-010888`; Symbol: `ER_ERRMSG_REPLACEMENTS_FAILED`; SQLSTATE: `HY000`  
Message: Table for error message replacements could not be found or read, or one or more replacements could not be applied.  
`ER_ERRMSG_REPLACEMENTS_FAILED` was added in 8.0.2.
  - Error number: `MY-010889`; Symbol: `ER_NPIPE_CANT_CREATE`; SQLSTATE: `HY000`  
Message: %s: %s



---

[ER\\_NPIPE\\_CANT\\_CREATE](#) was added in 8.0.2.

- Error number: [MY-010890](#); Symbol: [ER\\_PARTITION\\_MOVE\\_CREATED\\_DUPLICATE\\_ROW\\_PLEASE\\_FIX](#); SQLSTATE: [HY000](#)

Message: Table '%s': Delete from part %d failed with error %d. But it was already inserted into part %d, when moving the misplaced row! Please manually fix the duplicate row: %s

[ER\\_PARTITION\\_MOVE\\_CREATED\\_DUPLICATE\\_ROW\\_PLEASE\\_FIX](#) was added in 8.0.2.

- Error number: [MY-010891](#); Symbol: [ER\\_AUDIT\\_CANT\\_ABORT\\_COMMAND](#); SQLSTATE: [HY000](#)

Message: Command '%s' cannot be aborted. The trigger error was (%d) [%s]: %s

[ER\\_AUDIT\\_CANT\\_ABORT\\_COMMAND](#) was added in 8.0.2.

- Error number: [MY-010892](#); Symbol: [ER\\_AUDIT\\_CANT\\_ABORT\\_EVENT](#); SQLSTATE: [HY000](#)

Message: Event '%s' cannot be aborted. The trigger error was (%d) [%s]: %s

[ER\\_AUDIT\\_CANT\\_ABORT\\_EVENT](#) was added in 8.0.2.

- Error number: [MY-010893](#); Symbol: [ER\\_AUDIT\\_WARNING](#); SQLSTATE: [HY000](#)

Message: %s. The trigger error was (%d) [%s]: %s

[ER\\_AUDIT\\_WARNING](#) was added in 8.0.2.

- Error number: [MY-010894](#); Symbol: [ER\\_NDB\\_NUMBER\\_OF\\_CHANNELS](#); SQLSTATE: [HY000](#)

Message: Slave SQL: Configuration with number of replication masters = %u' is not supported when applying to Ndb

[ER\\_NDB\\_NUMBER\\_OF\\_CHANNELS](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010895](#); Symbol: [ER\\_NDB\\_SLAVE\\_PARALLEL\\_WORKERS](#); SQLSTATE: [HY000](#)

Message: Slave SQL: Configuration 'slave\_parallel\_workers = %lu' is not supported when applying to Ndb

[ER\\_NDB\\_SLAVE\\_PARALLEL\\_WORKERS](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010896](#); Symbol: [ER\\_NDB\\_DISTRIBUTING\\_ERR](#); SQLSTATE: [HY000](#)

Message: NDB %s: distributing %s err: %u

[ER\\_NDB\\_DISTRIBUTING\\_ERR](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010897](#); Symbol: [ER\\_RPL\\_SLAVE\\_INSECURE\\_CHANGE\\_MASTER](#); SQLSTATE: [HY000](#)

Message: Storing MySQL user name or password information in the master info repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START SLAVE; see the 'START SLAVE Syntax' in the MySQL Manual for more information.

[ER\\_RPL\\_SLAVE\\_INSECURE\\_CHANGE\\_MASTER](#) was added in 8.0.4, removed after 8.0.32.

- 
- Error number: `MY-010897`; Symbol: `ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE`; SQLSTATE: `HY000`

Message: Storing MySQL user name or password information in the connection metadata repository is not secure and is therefore not recommended. Please consider using the `USER` and `PASSWORD` connection options for `START REPLICA`; see the 'START REPLICA Syntax' in the MySQL Manual for more information.

`ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE` was added in 8.0.33.

- Error number: `MY-010898`; Symbol: `ER_RPL_SLAVE_FLUSH_RELAY_LOGS_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: `FLUSH RELAY LOGS` cannot be performed on channel '%s'.

`ER_RPL_SLAVE_FLUSH_RELAY_LOGS_NOT_ALLOWED` was added in 8.0.4, removed after 8.0.15.

- Error number: `MY-010899`; Symbol: `ER_RPL_SLAVE_INCORRECT_CHANNEL`; SQLSTATE: `HY000`

Message: Slave channel '%s' does not exist.

`ER_RPL_SLAVE_INCORRECT_CHANNEL` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-010899`; Symbol: `ER_RPL_REPLICA_INCORRECT_CHANNEL`; SQLSTATE: `HY000`

Message: Replica channel '%s' does not exist.

`ER_RPL_REPLICA_INCORRECT_CHANNEL` was added in 8.0.33.

- Error number: `MY-010900`; Symbol: `ER_FAILED_TO_FIND_DL_ENTRY`; SQLSTATE: `HY000`

Message: Can't find symbol '%s' in library.

`ER_FAILED_TO_FIND_DL_ENTRY` was added in 8.0.4.

- Error number: `MY-010901`; Symbol: `ER_FAILED_TO_OPEN_SHARED_LIBRARY`; SQLSTATE: `HY000`

Message: Can't open shared library '%s' (errno: %d %s).

`ER_FAILED_TO_OPEN_SHARED_LIBRARY` was added in 8.0.4.

- Error number: `MY-010902`; Symbol: `ER_THREAD_PRIORITY_IGNORED`; SQLSTATE: `HY000`

Message: Thread priority attribute setting in Resource Group SQL shall be ignored due to unsupported platform or insufficient privilege.

`ER_THREAD_PRIORITY_IGNORED` was added in 8.0.4.

- Error number: `MY-010903`; Symbol: `ER_BINLOG_CACHE_SIZE_TOO_LARGE`; SQLSTATE: `HY000`

Message: Option `binlog_cache_size` (%lu) is greater than `max_binlog_cache_size` (%lu); setting `binlog_cache_size` equal to `max_binlog_cache_size`.

`ER_BINLOG_CACHE_SIZE_TOO_LARGE` was added in 8.0.4.

- 
- Error number: [MY-010904](#); Symbol: [ER\\_BINLOG\\_STMT\\_CACHE\\_SIZE\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)  
  
Message: Option `binlog_stmt_cache_size` (%lu) is greater than `max_binlog_stmt_cache_size` (%lu); setting `binlog_stmt_cache_size` equal to `max_binlog_stmt_cache_size`.  
  
[ER\\_BINLOG\\_STMT\\_CACHE\\_SIZE\\_TOO\\_LARGE](#) was added in 8.0.4.
  - Error number: [MY-010905](#); Symbol: [ER\\_FAILED\\_TO\\_GENERATE\\_UNIQUE\\_LOGFILE](#); SQLSTATE: [HY000](#)  
  
Message: Can't generate a unique log-filename %s.(1-999).  
  
[ER\\_FAILED\\_TO\\_GENERATE\\_UNIQUE\\_LOGFILE](#) was added in 8.0.4.
  - Error number: [MY-010906](#); Symbol: [ER\\_FAILED\\_TO\\_READ\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: Error reading file '%s' (errno: %d - %s)  
  
[ER\\_FAILED\\_TO\\_READ\\_FILE](#) was added in 8.0.4.
  - Error number: [MY-010907](#); Symbol: [ER\\_FAILED\\_TO\\_WRITE\\_TO\\_FILE](#); SQLSTATE: [HY000](#)  
  
Message: Error writing file '%s' (errno: %d - %s)  
  
[ER\\_FAILED\\_TO\\_WRITE\\_TO\\_FILE](#) was added in 8.0.4.
  - Error number: [MY-010908](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_MESSAGE\\_AND\\_STATEMENT](#); SQLSTATE: [HY000](#)  
  
Message: %s Statement: %s  
  
[ER\\_BINLOG\\_UNSAFE\\_MESSAGE\\_AND\\_STATEMENT](#) was added in 8.0.4.
  - Error number: [MY-010909](#); Symbol: [ER\\_FORCE\\_CLOSE\\_THREAD](#); SQLSTATE: [HY000](#)  
  
Message: %s: Forcing close of thread %ld user: '%s'.  
  
[ER\\_FORCE\\_CLOSE\\_THREAD](#) was added in 8.0.4.
  - Error number: [MY-010910](#); Symbol: [ER\\_SERVER\\_SHUTDOWN\\_COMPLETE](#); SQLSTATE: [HY000](#)  
  
Message: %s: Shutdown complete (mysqld %s) %s.  
  
[ER\\_SERVER\\_SHUTDOWN\\_COMPLETE](#) was added in 8.0.4.
  - Error number: [MY-010911](#); Symbol: [ER\\_RPL\\_CANT\\_HAVE\\_SAME\\_BASENAME](#); SQLSTATE: [HY000](#)  
  
Message: Cannot have same base name '%s' for both binary and relay logs. Please check %s (default '%s' if --log-bin option is not used, default '%s' if --log-bin option is used without argument) and %s (default '%s') options to ensure they do not conflict.  
  
[ER\\_RPL\\_CANT\\_HAVE\\_SAME\\_BASENAME](#) was added in 8.0.3.
-

- 
- Error number: `MY-010912`; Symbol: `ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON`; SQLSTATE: `HY000`  
Message: `GTID_MODE = ON` requires `ENFORCE_GTID_CONSISTENCY = ON`.  
`ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON` was added in 8.0.4.
  - Error number: `MY-010913`; Symbol: `ER_WARN_NO_SERVERID_SPECIFIED`; SQLSTATE: `HY000`  
Message: You have not provided a mandatory server-id. Servers in a replication topology must have unique server-ids. Please refer to the proper server start-up parameters documentation.  
`ER_WARN_NO_SERVERID_SPECIFIED` was added in 8.0.3.
  - Error number: `MY-010914`; Symbol: `ER_ABORTING_USER_CONNECTION`; SQLSTATE: `HY000`  
Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).  
`ER_ABORTING_USER_CONNECTION` was added in 8.0.4.
  - Error number: `MY-010915`; Symbol: `ER_SQL_MODE_MERGED_WITH_STRICT_MODE`; SQLSTATE: `HY000`  
Message: 'NO\_ZERO\_DATE', 'NO\_ZERO\_IN\_DATE' and 'ERROR\_FOR\_DIVISION\_BY\_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.  
`ER_SQL_MODE_MERGED_WITH_STRICT_MODE` was added in 8.0.4.
  - Error number: `MY-010916`; Symbol: `ER_GTID_PURGED_WAS_UPDATED`; SQLSTATE: `HY000`  
Message: @@GLOBAL.GTID\_PURGED was changed from '%s' to '%s'.  
`ER_GTID_PURGED_WAS_UPDATED` was added in 8.0.4.
  - Error number: `MY-010917`; Symbol: `ER_GTID_EXECUTED_WAS_UPDATED`; SQLSTATE: `HY000`  
Message: @@GLOBAL.GTID\_EXECUTED was changed from '%s' to '%s'.  
`ER_GTID_EXECUTED_WAS_UPDATED` was added in 8.0.4.
  - Error number: `MY-010918`; Symbol: `ER_DEPRECATED_MSG_WITH_REPLACEMENT`; SQLSTATE: `HY000`  
Message: '%s' is deprecated and will be removed in a future release. Please use %s instead.  
`ER_DEPRECATED_MSG_WITH_REPLACEMENT` was added in 8.0.4.
  - Error number: `MY-010919`; Symbol: `ER_TRG_CREATION_CTX_NOT_SET`; SQLSTATE: `HY000`  
Message: Triggers for table `'%s`.`'%s` have no creation context  
`ER_TRG_CREATION_CTX_NOT_SET` was added in 8.0.4.
  - Error number: `MY-010920`; Symbol: `ER_FILE_HAS_OLD_FORMAT`; SQLSTATE: `HY000`  
Message: '%s' has an old format, you should re-create the '%s' object(s)  
`ER_FILE_HAS_OLD_FORMAT` was added in 8.0.4.
  - Error number: `MY-010921`; Symbol: `ER_VIEW_CREATION_CTX_NOT_SET`; SQLSTATE: `HY000`

---

Message: View ``%s`.`%s` has no creation context

[ER\\_VIEW\\_CREATION\\_CTX\\_NOT\\_SET](#) was added in 8.0.4.

- Error number: [MY-010923](#); Symbol: [ER\\_TABLE\\_UPGRADE\\_REQUIRED](#); SQLSTATE: [HY000](#)

Message: Table upgrade required. Please do "REPAIR TABLE ``%s`" or dump/reload to fix it!

[ER\\_TABLE\\_UPGRADE\\_REQUIRED](#) was added in 8.0.4.

- Error number: [MY-010924](#); Symbol: [ER\\_GET\\_ERRNO\\_FROM\\_STORAGE\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Got error %d - '%s' from storage engine.

[ER\\_GET\\_ERRNO\\_FROM\\_STORAGE\\_ENGINE](#) was added in 8.0.4.

- Error number: [MY-010925](#); Symbol: [ER\\_ACCESS\\_DENIED\\_ERROR\\_WITHOUT\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'

[ER\\_ACCESS\\_DENIED\\_ERROR\\_WITHOUT\\_PASSWORD](#) was added in 8.0.4.

- Error number: [MY-010926](#); Symbol: [ER\\_ACCESS\\_DENIED\\_ERROR\\_WITH\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s' (using password: %s)

[ER\\_ACCESS\\_DENIED\\_ERROR\\_WITH\\_PASSWORD](#) was added in 8.0.4.

- Error number: [MY-010927](#); Symbol: [ER\\_ACCESS\\_DENIED\\_FOR\\_USER\\_ACCOUNT\\_LOCKED](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'. Account is locked.

[ER\\_ACCESS\\_DENIED\\_FOR\\_USER\\_ACCOUNT\\_LOCKED](#) was added in 8.0.4.

- Error number: [MY-010928](#); Symbol: [ER\\_MUST\\_CHANGE\\_EXPIRED\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Your password has expired. To log in you must change it using a client that supports expired passwords.

[ER\\_MUST\\_CHANGE\\_EXPIRED\\_PASSWORD](#) was added in 8.0.4, removed after 8.0.28.

- Error number: [MY-010929](#); Symbol: [ER\\_SYSTEM\\_TABLES\\_NOT\\_SUPPORTED\\_BY\\_STORAGE\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Storage engine '%s' does not support system tables. [%s.%s].

[ER\\_SYSTEM\\_TABLES\\_NOT\\_SUPPORTED\\_BY\\_STORAGE\\_ENGINE](#) was added in 8.0.4.

- Error number: [MY-010930](#); Symbol: [ER\\_FILESORT\\_TERMINATED](#); SQLSTATE: [HY000](#)

Message: Sort aborted

[ER\\_FILESORT\\_TERMINATED](#) was added in 8.0.4, removed after 8.0.18.

- Error number: [MY-010931](#); Symbol: [ER\\_SERVER\\_STARTUP\\_MSG](#); SQLSTATE: [HY000](#)

---

Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s.

[ER\\_SERVER\\_STARTUP\\_MSG](#) was added in 8.0.4.

- Error number: [MY-010932](#); Symbol: [ER\\_FAILED\\_TO\\_FIND\\_LOCALE\\_NAME](#); SQLSTATE: [HY000](#)

Message: Unknown locale: '%s'.

[ER\\_FAILED\\_TO\\_FIND\\_LOCALE\\_NAME](#) was added in 8.0.4.

- Error number: [MY-010933](#); Symbol: [ER\\_FAILED\\_TO\\_FIND\\_COLLATION\\_NAME](#); SQLSTATE: [HY000](#)

Message: Unknown collation: '%s'.

[ER\\_FAILED\\_TO\\_FIND\\_COLLATION\\_NAME](#) was added in 8.0.4.

- Error number: [MY-010934](#); Symbol: [ER\\_SERVER\\_OUT\\_OF\\_RESOURCES](#); SQLSTATE: [HY000](#)

Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space

[ER\\_SERVER\\_OUT\\_OF\\_RESOURCES](#) was added in 8.0.4.

- Error number: [MY-010935](#); Symbol: [ER\\_SERVER\\_OUTOFMEMORY](#); SQLSTATE: [HY000](#)

Message: Out of memory; restart server and try again (needed %d bytes)

[ER\\_SERVER\\_OUTOFMEMORY](#) was added in 8.0.4.

- Error number: [MY-010936](#); Symbol: [ER\\_INVALID\\_COLLATION\\_FOR\\_CHARSET](#); SQLSTATE: [HY000](#)

Message: COLLATION '%s' is not valid for CHARACTER SET '%s'

[ER\\_INVALID\\_COLLATION\\_FOR\\_CHARSET](#) was added in 8.0.4.

- Error number: [MY-010937](#); Symbol: [ER\\_CANT\\_START\\_ERROR\\_LOG\\_SERVICE](#); SQLSTATE: [HY000](#)

Message: Failed to set %s at or around "%s" -- service is valid, but can not be initialized; please check its configuration and make sure it can read its input(s) and write to its output(s).

[ER\\_CANT\\_START\\_ERROR\\_LOG\\_SERVICE](#) was added in 8.0.4.

- Error number: [MY-010938](#); Symbol: [ER\\_CREATING\\_NEW\\_UUID\\_FIRST\\_START](#); SQLSTATE: [HY000](#)

Message: Generating a new UUID: %s.

[ER\\_CREATING\\_NEW\\_UUID\\_FIRST\\_START](#) was added in 8.0.4.

- Error number: [MY-010939](#); Symbol: [ER\\_FAILED\\_TO\\_GET\\_ABSOLUTE\\_PATH](#); SQLSTATE: [HY000](#)

Message: Failed to get absolute path of program executable %s

[ER\\_FAILED\\_TO\\_GET\\_ABSOLUTE\\_PATH](#) was added in 8.0.4.

- Error number: [MY-010940](#); Symbol: [ER\\_PERFSHEMA\\_COMPONENTS\\_INFRASTRUCTURE\\_BOOTSTRAP](#); SQLSTATE: [HY000](#)

Message: Failed to bootstrap performance schema components infrastructure.

---

`ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP` was added in 8.0.4.

- Error number: `MY-010941`; Symbol: `ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN`; SQLSTATE: `HY000`

Message: Failed to deinit performance schema components infrastructure.

`ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN` was added in 8.0.4.

- Error number: `MY-010942`; Symbol: `ER_DUP_FD_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Could not open duplicate fd for %s: %s.

`ER_DUP_FD_OPEN_FAILED` was added in 8.0.4.

- Error number: `MY-010943`; Symbol: `ER_SYSTEM_VIEW_INIT_FAILED`; SQLSTATE: `HY000`

Message: System views initialization failed.

`ER_SYSTEM_VIEW_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-010944`; Symbol: `ER_RESOURCE_GROUP_POST_INIT_FAILED`; SQLSTATE: `HY000`

Message: Resource group post initialization failed.

`ER_RESOURCE_GROUP_POST_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-010945`; Symbol: `ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED`; SQLSTATE: `HY000`

Message: Resource Group subsystem initialization failed.

`ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-010946`; Symbol: `ER_FAILED_START_MYSQLD_DAEMON`; SQLSTATE: `HY000`

Message: Failed to start mysqld daemon. Check mysqld error log.

`ER_FAILED_START_MYSQLD_DAEMON` was added in 8.0.4.

- Error number: `MY-010947`; Symbol: `ER_CANNOT_CHANGE_TO_ROOT_DIR`; SQLSTATE: `HY000`

Message: Cannot change to root directory: %s.

`ER_CANNOT_CHANGE_TO_ROOT_DIR` was added in 8.0.4.

- Error number: `MY-010948`; Symbol: `ER_PERSISTENT_PRIVILEGES_BOOTSTRAP`; SQLSTATE: `HY000`

Message: Failed to bootstrap persistent privileges.

`ER_PERSISTENT_PRIVILEGES_BOOTSTRAP` was added in 8.0.4.

- Error number: `MY-010949`; Symbol: `ER_BASEDIR_SET_TO`; SQLSTATE: `HY000`

Message: Basedir set to %s.

`ER_BASEDIR_SET_TO` was added in 8.0.4.

- 
- Error number: `MY-010950`; Symbol: `ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED`; SQLSTATE: `HY000`  
  
Message: Could not add wild do table rule '%s'!  
  
`ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED` was added in 8.0.4.
  - Error number: `MY-010951`; Symbol: `ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED`; SQLSTATE: `HY000`  
  
Message: Could not add wild ignore table rule '%s'!  
  
`ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED` was added in 8.0.4.
  - Error number: `MY-010952`; Symbol: `ER_PRIVILEGE_SYSTEM_INIT_FAILED`; SQLSTATE: `HY000`  
  
Message: The privilege system failed to initialize correctly. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.  
  
`ER_PRIVILEGE_SYSTEM_INIT_FAILED` was added in 8.0.4.
  - Error number: `MY-010953`; Symbol: `ER_CANNOT_SET_LOG_ERROR_SERVICES`; SQLSTATE: `HY000`  
  
Message: Cannot set services "%s" requested in --log-error-services, using defaults.  
  
`ER_CANNOT_SET_LOG_ERROR_SERVICES` was added in 8.0.4.
  - Error number: `MY-010954`; Symbol: `ER_PERFSCHEMA_TABLES_INIT_FAILED`; SQLSTATE: `HY000`  
  
Message: Performance schema tables initialization failed.  
  
`ER_PERFSCHEMA_TABLES_INIT_FAILED` was added in 8.0.4.
  - Error number: `MY-010955`; Symbol: `ER_TX_EXTRACTION_ALGORITHM_FOR_BINLOG_TX_DEPEDENCY_TRACKING`; SQLSTATE: `HY000`  
  
Message: The transaction\_write\_set\_extraction must be set to %s when binlog\_transaction\_dependency\_tracking is %s.  
  
`ER_TX_EXTRACTION_ALGORITHM_FOR_BINLOG_TX_DEPEDENCY_TRACKING` was added in 8.0.4.
  - Error number: `MY-010956`; Symbol: `ER_INVALID_REPLICATION_TIMESTAMPS`; SQLSTATE: `HY000`  
  
Message: Invalid replication timestamps: original commit timestamp is more recent than the immediate commit timestamp. This may be an issue if delayed replication is active. Make sure that servers have their clocks set to the correct time. No further message will be emitted until after timestamps become valid again.  
  
`ER_INVALID_REPLICATION_TIMESTAMPS` was added in 8.0.4, removed after 8.0.25.
  - Error number: `MY-010957`; Symbol: `ER_RPL_TIMESTAMPS_RETURNED_TO_NORMAL`; SQLSTATE: `HY000`  
  
Message: The replication timestamps have returned to normal values.  
  
`ER_RPL_TIMESTAMPS_RETURNED_TO_NORMAL` was added in 8.0.4, removed after 8.0.25.
  - Error number: `MY-010958`; Symbol: `ER_BINLOG_FILE_OPEN_FAILED`; SQLSTATE: `HY000`



---

Message: %s.

[ER\\_BINLOG\\_FILE\\_OPEN\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-010959](#); Symbol: [ER\\_BINLOG\\_EVENT\\_WRITE\\_TO\\_STMT\\_CACHE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to write an incident event into stmt\_cache.

[ER\\_BINLOG\\_EVENT\\_WRITE\\_TO\\_STMT\\_CACHE\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-010960](#); Symbol: [ER\\_SLAVE\\_RELAY\\_LOG\\_TRUNCATE\\_INFO](#); SQLSTATE: [HY000](#)

Message: Relaylog file %s size was %llu, but was truncated at %llu.

[ER\\_SLAVE\\_RELAY\\_LOG\\_TRUNCATE\\_INFO](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-010960](#); Symbol: [ER\\_REPLICA\\_RELAY\\_LOG\\_TRUNCATE\\_INFO](#); SQLSTATE: [HY000](#)

Message: Relaylog file %s size was %llu, but was truncated at %llu.

[ER\\_REPLICA\\_RELAY\\_LOG\\_TRUNCATE\\_INFO](#) was added in 8.0.33.

- Error number: [MY-010961](#); Symbol: [ER\\_SLAVE\\_RELAY\\_LOG\\_PURGE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to purge relay log files. %s:%s.

[ER\\_SLAVE\\_RELAY\\_LOG\\_PURGE\\_FAILED](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-010961](#); Symbol: [ER\\_REPLICA\\_RELAY\\_LOG\\_PURGE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to purge relay log files. %s:%s.

[ER\\_REPLICA\\_RELAY\\_LOG\\_PURGE\\_FAILED](#) was added in 8.0.33.

- Error number: [MY-010962](#); Symbol: [ER\\_RPL\\_SLAVE\\_FILTER\\_CREATE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Slave: failed in creating filter for channel '%s'.

[ER\\_RPL\\_SLAVE\\_FILTER\\_CREATE\\_FAILED](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-010962](#); Symbol: [ER\\_RPL\\_REPLICA\\_FILTER\\_CREATE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Replica: failed in creating filter for channel '%s'.

[ER\\_RPL\\_REPLICA\\_FILTER\\_CREATE\\_FAILED](#) was added in 8.0.33.

- Error number: [MY-010963](#); Symbol: [ER\\_RPL\\_SLAVE\\_GLOBAL\\_FILTERS\\_COPY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Slave: failed in copying the global filters to its own per-channel filters on configuration for channel '%s'.

[ER\\_RPL\\_SLAVE\\_GLOBAL\\_FILTERS\\_COPY\\_FAILED](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-010963](#); Symbol: [ER\\_RPL\\_REPLICA\\_GLOBAL\\_FILTERS\\_COPY\\_FAILED](#); SQLSTATE: [HY000](#)

---

Message: Replica: failed in copying the global filters to its own per-channel filters on configuration for channel '%s'.

[ER\\_RPL\\_REPLICA\\_GLOBAL\\_FILTERS\\_COPY\\_FAILED](#) was added in 8.0.33.

- Error number: [MY-010964](#); Symbol: [ER\\_RPL\\_SLAVE\\_RESET\\_FILTER\\_OPTIONS](#); SQLSTATE: [HY000](#)

Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.

[ER\\_RPL\\_SLAVE\\_RESET\\_FILTER\\_OPTIONS](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-010964](#); Symbol: [ER\\_RPL\\_REPLICA\\_RESET\\_FILTER\\_OPTIONS](#); SQLSTATE: [HY000](#)

Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.

[ER\\_RPL\\_REPLICA\\_RESET\\_FILTER\\_OPTIONS](#) was added in 8.0.33.

- Error number: [MY-010965](#); Symbol: [ER\\_MISSING\\_GRANT\\_SYSTEM\\_TABLE](#); SQLSTATE: [HY000](#)

Message: The system table mysql.global\_grants is missing. Please perform the MySQL upgrade procedure.

[ER\\_MISSING\\_GRANT\\_SYSTEM\\_TABLE](#) was added in 8.0.4.

- Error number: [MY-010966](#); Symbol: [ER\\_MISSING\\_ACL\\_SYSTEM\\_TABLE](#); SQLSTATE: [HY000](#)

Message: ACL table mysql.%.\*s missing. Some operations may fail.

[ER\\_MISSING\\_ACL\\_SYSTEM\\_TABLE](#) was added in 8.0.4.

- Error number: [MY-010967](#); Symbol: [ER\\_ANONYMOUS\\_AUTH\\_ID\\_NOT\\_ALLOWED\\_IN\\_MANDATORY\\_ROLES](#); SQLSTATE: [HY000](#)

Message: Can't set mandatory\_role %s@%s: Anonymous authorization IDs are not allowed as roles.

[ER\\_ANONYMOUS\\_AUTH\\_ID\\_NOT\\_ALLOWED\\_IN\\_MANDATORY\\_ROLES](#) was added in 8.0.4.

- Error number: [MY-010968](#); Symbol: [ER\\_UNKNOWN\\_AUTH\\_ID\\_IN\\_MANDATORY\\_ROLE](#); SQLSTATE: [HY000](#)

Message: Can't set mandatory\_role: There's no such authorization ID %s@%s.

[ER\\_UNKNOWN\\_AUTH\\_ID\\_IN\\_MANDATORY\\_ROLE](#) was added in 8.0.4.

- Error number: [MY-010969](#); Symbol: [ER\\_WRITE\\_ROW\\_TO\\_PARTITION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Table '%s' failed to move/insert a row from part %d into part %d: %s.

[ER\\_WRITE\\_ROW\\_TO\\_PARTITION\\_FAILED](#) was added in 8.0.4.

- 
- Error number: `MY-010970`; Symbol: `ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED`; SQLSTATE: `HY000`  
  
Message: Skipped updating resource group metadata in InnoDB read only mode.  
  
`ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED` was added in 8.0.4.
  - Error number: `MY-010971`; Symbol: `ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA`; SQLSTATE: `HY000`  
  
Message: Failed to persist resource group %s to Data Dictionary.  
  
`ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA` was added in 8.0.4.
  - Error number: `MY-010972`; Symbol: `ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP`; SQLSTATE: `HY000`  
  
Message: Failed to deserialize resource group %s.  
  
`ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP` was added in 8.0.4.
  - Error number: `MY-010973`; Symbol: `ER_FAILED_TO_UPDATE_RESOURCE_GROUP`; SQLSTATE: `HY000`  
  
Message: Update of resource group %s failed.  
  
`ER_FAILED_TO_UPDATE_RESOURCE_GROUP` was added in 8.0.4.
  - Error number: `MY-010974`; Symbol: `ER_RESOURCE_GROUP_VALIDATION_FAILED`; SQLSTATE: `HY000`  
  
Message: Validation of resource group %s failed. Resource group is disabled.  
  
`ER_RESOURCE_GROUP_VALIDATION_FAILED` was added in 8.0.4.
  - Error number: `MY-010975`; Symbol: `ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP`; SQLSTATE: `HY000`  
  
Message: Unable to allocate memory for Resource Group %s.  
  
`ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP` was added in 8.0.4.
  - Error number: `MY-010976`; Symbol: `ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP_HASH`; SQLSTATE: `HY000`  
  
Message: Failed to allocate memory for resource group hash.  
  
`ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP_HASH` was added in 8.0.4.
  - Error number: `MY-010977`; Symbol: `ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP`; SQLSTATE: `HY000`  
  
Message: Failed to add resource group %s to resource group map.  
  
`ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP` was added in 8.0.4.

- 
- Error number: `MY-010978`; Symbol: `ER_RESOURCE_GROUP_IS_DISABLED`; SQLSTATE: `HY000`  
Message: Resource group feature is disabled. (Server is compiled with `DISABLE_PSI_THREAD`).  
`ER_RESOURCE_GROUP_IS_DISABLED` was added in 8.0.4.
  - Error number: `MY-010979`; Symbol: `ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER`; SQLSTATE: `HY000`  
Message: Unable to apply resource group controller %s.  
`ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER` was added in 8.0.4.
  - Error number: `MY-010980`; Symbol: `ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP`; SQLSTATE: `HY000`  
Message: Unable to acquire lock on the resource group %s. Hint to switch resource group shall be ignored.  
`ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP` was added in 8.0.4.
  - Error number: `MY-010981`; Symbol: `ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED`; SQLSTATE: `HY000`  
Message: PFS %s notification function registration failed.  
`ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED` was added in 8.0.4.
  - Error number: `MY-010982`; Symbol: `ER_RES_GRP_SET_THR_AFFINITY_FAILED`; SQLSTATE: `HY000`  
Message: Unable to bind thread id %llu to cpu id %u (error code %d - %s).  
`ER_RES_GRP_SET_THR_AFFINITY_FAILED` was added in 8.0.4.
  - Error number: `MY-010983`; Symbol: `ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED`; SQLSTATE: `HY000`  
Message: Unable to bind thread id %llu to cpu ids (error code %d - %s).  
`ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED` was added in 8.0.4.
  - Error number: `MY-010984`; Symbol: `ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED`; SQLSTATE: `HY000`  
Message: Unbind thread id %llu failed. (error code %d - %s).  
`ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED` was added in 8.0.4.
  - Error number: `MY-010985`; Symbol: `ER_RES_GRP_SET_THREAD_PRIORITY_FAILED`; SQLSTATE: `HY000`  
Message: Setting thread priority %d to thread id %llu failed. (error code %d - %s).  
`ER_RES_GRP_SET_THREAD_PRIORITY_FAILED` was added in 8.0.4.
  - Error number: `MY-010986`; Symbol: `ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY`; SQLSTATE: `HY000`  
Message: Unable to determine `CAP_SYS_NICE` capability.

---

`ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY` was added in 8.0.4.

- Error number: `MY-010987`; Symbol: `ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE`; SQLSTATE: `HY000`

Message: %s failed: Failed to get handle for thread %llu.

`ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE` was added in 8.0.4.

- Error number: `MY-010988`; Symbol: `ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Retrieval of thread priority unsupported on %s.

`ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED` was added in 8.0.4.

- Error number: `MY-010989`; Symbol: `ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT`; SQLSTATE: `HY000`

Message: Unable to determine the number of CPUs.

`ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT` was added in 8.0.4.

- Error number: `MY-010990`; Symbol: `ER_RES_GRP_FEATURE_NOT_AVAILABLE`; SQLSTATE: `HY000`

Message: Resource group feature shall not be available. Incompatible thread handling option.

`ER_RES_GRP_FEATURE_NOT_AVAILABLE` was added in 8.0.4.

- Error number: `MY-010991`; Symbol: `ER_RES_GRP_INVALID_THREAD_PRIORITY`; SQLSTATE: `HY000`

Message: Invalid thread priority %d for a %s resource group. Allowed range is [%d, %d].

`ER_RES_GRP_INVALID_THREAD_PRIORITY` was added in 8.0.4.

- Error number: `MY-010992`; Symbol: `ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPUID_FAILED`; SQLSTATE: `HY000`

Message: bind\_to\_cpu failed: processor\_bind for cpuid %u failed (error code %d - %s).

`ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPUID_FAILED` was added in 8.0.4.

- Error number: `MY-010993`; Symbol: `ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_FAILED`; SQLSTATE: `HY000`

Message: bind\_to\_cpu failed: processor\_bind for thread %%llx with cpu id %u (error code %d - %s).

`ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_FAILED` was added in 8.0.4.

- Error number: `MY-010994`; Symbol: `ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED`; SQLSTATE: `HY000`

Message: %s failed: processor\_affinity failed (error code %d - %s).

`ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED` was added in 8.0.4.

- Error number: `MY-010995`; Symbol: `ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED`; SQLSTATE: `HY000`

---

Message: Error in renaming mysql\_index\_stats.ibd.

[ER\\_DD\\_UPGRADE\\_RENAME\\_IDX\\_STATS\\_FILE\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-010996](#); Symbol: [ER\\_DD\\_UPGRADE\\_DD\\_OPEN\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in opening data directory %s.

[ER\\_DD\\_UPGRADE\\_DD\\_OPEN\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-010997](#); Symbol: [ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_FETCH\\_TABLESPACES](#); SQLSTATE: [HY000](#)

Message: Error in fetching list of tablespaces.

[ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_FETCH\\_TABLESPACES](#) was added in 8.0.4.

- Error number: [MY-010998](#); Symbol: [ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_ACQUIRE\\_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Error in acquiring Tablespace for SDI insertion %s.

[ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_ACQUIRE\\_TABLESPACE](#) was added in 8.0.4.

- Error number: [MY-010999](#); Symbol: [ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_RESOLVE\\_TABLESPACE\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Error in resolving Engine name for tablespace %s with engine %s.

[ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_RESOLVE\\_TABLESPACE\\_ENGINE](#) was added in 8.0.4.

- Error number: [MY-011000](#); Symbol: [ER\\_FAILED\\_TO\\_CREATE\\_SDI\\_FOR\\_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Error in creating SDI for %s tablespace.

[ER\\_FAILED\\_TO\\_CREATE\\_SDI\\_FOR\\_TABLESPACE](#) was added in 8.0.4.

- Error number: [MY-011001](#); Symbol: [ER\\_FAILED\\_TO\\_STORE\\_SDI\\_FOR\\_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Error in storing SDI for %s tablespace.

[ER\\_FAILED\\_TO\\_STORE\\_SDI\\_FOR\\_TABLESPACE](#) was added in 8.0.4.

- Error number: [MY-011002](#); Symbol: [ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_FETCH\\_TABLES](#); SQLSTATE: [HY000](#)

Message: Error in fetching list of tables.

[ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_FETCH\\_TABLES](#) was added in 8.0.4.

- Error number: [MY-011003](#); Symbol: [ER\\_DD\\_UPGRADE\\_DD\\_POPULATED](#); SQLSTATE: [HY000](#)

Message: Finished populating Data Dictionary tables with data.

[ER\\_DD\\_UPGRADE\\_DD\\_POPULATED](#) was added in 8.0.4.

- 
- Error number: `MY-011004`; Symbol: `ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED`; SQLSTATE: `HY000`  
Message: Could not open the upgrade info file '%s' in the MySQL servers datadir, errno: %d.  
`ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED` was added in 8.0.4.
  - Error number: `MY-011005`; Symbol: `ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED`; SQLSTATE: `HY000`  
Message: Could not close the upgrade info file '%s' in the MySQL servers datadir, errno: %d.  
`ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED` was added in 8.0.4.
  - Error number: `MY-011006`; Symbol: `ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED`; SQLSTATE: `HY000`  
Message: Got error %d from SE while migrating tablespaces.  
`ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED` was added in 8.0.4.
  - Error number: `MY-011007`; Symbol: `ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS`; SQLSTATE: `HY000`  
Message: Error in creating TABLE statistics entry. Fix statistics data by using ANALYZE command.  
`ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS` was added in 8.0.4.
  - Error number: `MY-011008`; Symbol: `ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED`; SQLSTATE: `HY000`  
Message: Finished migrating TABLE statistics data.  
`ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED` was added in 8.0.4.
  - Error number: `MY-011009`; Symbol: `ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS`; SQLSTATE: `HY000`  
Message: Error in creating Index statistics entry. Fix statistics data by using ANALYZE command.  
`ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS` was added in 8.0.4.
  - Error number: `MY-011010`; Symbol: `ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED`; SQLSTATE: `HY000`  
Message: Finished migrating INDEX statistics data.  
`ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED` was added in 8.0.4.
  - Error number: `MY-011011`; Symbol: `ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR`; SQLSTATE: `HY000`  
Message: Failed to find valid data directory.  
`ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR` was added in 8.0.4.
  - Error number: `MY-011012`; Symbol: `ER_DD_UPGRADE_START`; SQLSTATE: `HY000`  
Message: Starting upgrade of data directory.

---

`ER_DD_UPGRADE_START` was added in 8.0.4.

- Error number: `MY-011013`; Symbol: `ER_DD_UPGRADE_FAILED_INIT_DD_SE`; SQLSTATE: `HY000`

Message: Failed to initialize DD Storage Engine.

`ER_DD_UPGRADE_FAILED_INIT_DD_SE` was added in 8.0.4.

- Error number: `MY-011014`; Symbol: `ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_ABORT`; SQLSTATE: `HY000`

Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.

`ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_ABORT` was added in 8.0.4.

- Error number: `MY-011015`; Symbol: `ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_CONTINUE`; SQLSTATE: `HY000`

Message: Found partially upgraded DD. Upgrade will continue and start the server.

`ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_CONTINUE` was added in 8.0.4.

- Error number: `MY-011016`; Symbol: `ER_DD_UPGRADE_SE_LOGS_FAILED`; SQLSTATE: `HY000`

Message: Error in upgrading engine logs.

`ER_DD_UPGRADE_SE_LOGS_FAILED` was added in 8.0.4.

- Error number: `MY-011017`; Symbol: `ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED`; SQLSTATE: `HY000`

Message: Error in updating SDI information.

`ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED` was added in 8.0.4.

- Error number: `MY-011018`; Symbol: `ER_SKIP_UPDATING_METADATA_IN_SE_RO_MODE`; SQLSTATE: `HY000`

Message: Skip updating %s metadata in InnoDB read-only mode.

`ER_SKIP_UPDATING_METADATA_IN_SE_RO_MODE` was added in 8.0.4.

- Error number: `MY-011019`; Symbol: `ER_CREATED_SYSTEM_WITH_VERSION`; SQLSTATE: `HY000`

Message: Created system views with I\_S version %d.

`ER_CREATED_SYSTEM_WITH_VERSION` was added in 8.0.4.

- Error number: `MY-011020`; Symbol: `ER_UNKNOWN_ERROR_DETECTED_IN_SE`; SQLSTATE: `HY000`

Message: Unknown error detected %d in handler.

`ER_UNKNOWN_ERROR_DETECTED_IN_SE` was added in 8.0.4.

- Error number: `MY-011021`; Symbol: `ER_READ_LOG_EVENT_FAILED`; SQLSTATE: `HY000`

Message: Error in Log\_event::read\_log\_event(): '%s', data\_len: %lu, event\_type: %d.



---

`ER_READ_LOG_EVENT_FAILED` was added in 8.0.4.

- Error number: `MY-011022`; Symbol: `ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG`; SQLSTATE: `HY000`

Message: The row data is greater than 4GB, which is too big to write to the binary log.

`ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG` was added in 8.0.4.

- Error number: `MY-011023`; Symbol: `ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY`; SQLSTATE: `HY000`

Message: Unable to construct DROP EVENT SQL query string.

`ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY` was added in 8.0.4.

- Error number: `MY-011024`; Symbol: `ER_FAILED_TO_BINLOG_DROP_EVENT`; SQLSTATE: `HY000`

Message: Unable to binlog drop event %s.%s.

`ER_FAILED_TO_BINLOG_DROP_EVENT` was added in 8.0.4.

- Error number: `MY-011025`; Symbol: `ER_FAILED_TO_START_SLAVE_THREAD`; SQLSTATE: `HY000`

Message: Failed to start slave threads for channel '%s'.

`ER_FAILED_TO_START_SLAVE_THREAD` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011025`; Symbol: `ER_FAILED_TO_START_REPLICA_THREAD`; SQLSTATE: `HY000`

Message: Failed to start replica threads for channel '%s'.

`ER_FAILED_TO_START_REPLICA_THREAD` was added in 8.0.33.

- Error number: `MY-011026`; Symbol: `ER_RPL_IO_THREAD_KILLED`; SQLSTATE: `HY000`

Message: %s%s.

`ER_RPL_IO_THREAD_KILLED` was added in 8.0.4.

- Error number: `MY-011027`; Symbol: `ER_SLAVE_RECONNECT_FAILED`; SQLSTATE: `HY000`

Message: Failed registering on master, reconnecting to try again, log '%s' at position %s. %s.

`ER_SLAVE_RECONNECT_FAILED` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011027`; Symbol: `ER_REPLICA_RECONNECT_FAILED`; SQLSTATE: `HY000`

Message: Failed registering on source, reconnecting to try again, log '%s' at position %s. %s.

`ER_REPLICA_RECONNECT_FAILED` was added in 8.0.33.

- Error number: `MY-011028`; Symbol: `ER_SLAVE_KILLED_AFTER_RECONNECT`; SQLSTATE: `HY000`

Message: Slave I/O thread killed during or after reconnect.

`ER_SLAVE_KILLED_AFTER_RECONNECT` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011028`; Symbol: `ER_REPLICA_KILLED_AFTER_RECONNECT`; SQLSTATE: `HY000`

---

Message: Replica I/O thread killed during or after reconnect.

[ER\\_REPLICA\\_KILLED\\_AFTER\\_RECONNECT](#) was added in 8.0.33.

- Error number: [MY-011029](#); Symbol: [ER\\_SLAVE\\_NOT\\_STARTED\\_ON\\_SOME\\_CHANNELS](#); SQLSTATE: [HY000](#)

Message: Some of the channels are not created/initialized properly. Check for additional messages above. You will not be able to start replication on those channels until the issue is resolved and the server restarted.

[ER\\_SLAVE\\_NOT\\_STARTED\\_ON\\_SOME\\_CHANNELS](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011029](#); Symbol: [ER\\_REPLICA\\_NOT\\_STARTED\\_ON\\_SOME\\_CHANNELS](#); SQLSTATE: [HY000](#)

Message: Some of the channels are not created/initialized properly. Check for additional messages above. You will not be able to start replication on those channels until the issue is resolved and the server restarted.

[ER\\_REPLICA\\_NOT\\_STARTED\\_ON\\_SOME\\_CHANNELS](#) was added in 8.0.33.

- Error number: [MY-011030](#); Symbol: [ER\\_FAILED\\_TO\\_ADD\\_RPL\\_FILTER](#); SQLSTATE: [HY000](#)

Message: Failed to add a replication filter into filter map for channel '%s'.

[ER\\_FAILED\\_TO\\_ADD\\_RPL\\_FILTER](#) was added in 8.0.4.

- Error number: [MY-011031](#); Symbol: [ER\\_PER\\_CHANNEL\\_RPL\\_FILTER\\_CONF\\_FOR\\_GRP\\_RPL](#); SQLSTATE: [HY000](#)

Message: There are per-channel replication filter(s) configured for group replication channel '%s' which is disallowed. The filter(s) have been discarded.

[ER\\_PER\\_CHANNEL\\_RPL\\_FILTER\\_CONF\\_FOR\\_GRP\\_RPL](#) was added in 8.0.4.

- Error number: [MY-011032](#); Symbol: [ER\\_RPL\\_FILTERS\\_NOT\\_ATTACHED\\_TO\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.

[ER\\_RPL\\_FILTERS\\_NOT\\_ATTACHED\\_TO\\_CHANNEL](#) was added in 8.0.4.

- Error number: [MY-011033](#); Symbol: [ER\\_FAILED\\_TO\\_BUILD\\_DO\\_AND\\_IGNORE\\_TABLE\\_HASHES](#); SQLSTATE: [HY000](#)

Message: An error occurred while building do\_table and ignore\_table rules to hashes for per-channel filter.

[ER\\_FAILED\\_TO\\_BUILD\\_DO\\_AND\\_IGNORE\\_TABLE\\_HASHES](#) was added in 8.0.4.

- Error number: [MY-011034](#); Symbol: [ER\\_CLONE\\_PLUGIN\\_NOT\\_LOADED](#); SQLSTATE: [HY000](#)

Message: Clone plugin not loaded.

[ER\\_CLONE\\_PLUGIN\\_NOT\\_LOADED](#) was added in 8.0.4, removed after 8.0.16.

- 
- Error number: [MY-011034](#); Symbol: [ER\\_CLONE\\_PLUGIN\\_NOT\\_LOADED\\_TRACE](#); SQLSTATE: [HY000](#)  
Message: Clone plugin cannot be loaded.  
[ER\\_CLONE\\_PLUGIN\\_NOT\\_LOADED\\_TRACE](#) was added in 8.0.17.
  - Error number: [MY-011035](#); Symbol: [ER\\_CLONE\\_HANDLER\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Clone Handler exists.  
[ER\\_CLONE\\_HANDLER\\_EXISTS](#) was added in 8.0.4, removed after 8.0.16.
  - Error number: [MY-011035](#); Symbol: [ER\\_CLONE\\_HANDLER\\_EXIST\\_TRACE](#); SQLSTATE: [HY000](#)  
Message: Clone Handler exists.  
[ER\\_CLONE\\_HANDLER\\_EXIST\\_TRACE](#) was added in 8.0.17.
  - Error number: [MY-011036](#); Symbol: [ER\\_FAILED\\_TO\\_CREATE\\_CLONE\\_HANDLER](#); SQLSTATE: [HY000](#)  
Message: Could not create Clone Handler.  
[ER\\_FAILED\\_TO\\_CREATE\\_CLONE\\_HANDLER](#) was added in 8.0.4, removed after 8.0.16.
  - Error number: [MY-011036](#); Symbol: [ER\\_CLONE\\_CREATE\\_HANDLER\\_FAIL\\_TRACE](#); SQLSTATE: [HY000](#)  
Message: Could not create Clone Handler.  
[ER\\_CLONE\\_CREATE\\_HANDLER\\_FAIL\\_TRACE](#) was added in 8.0.17.
  - Error number: [MY-011037](#); Symbol: [ER\\_CYCLE\\_TIMER\\_IS\\_NOT\\_AVAILABLE](#); SQLSTATE: [HY000](#)  
Message: The CYCLE timer is not available. WAIT events in the performance\_schema will not be timed.  
[ER\\_CYCLE\\_TIMER\\_IS\\_NOT\\_AVAILABLE](#) was added in 8.0.4.
  - Error number: [MY-011038](#); Symbol: [ER\\_NANOSECOND\\_TIMER\\_IS\\_NOT\\_AVAILABLE](#); SQLSTATE: [HY000](#)  
Message: The NANOSECOND timer is not available. IDLE/STAGE/STATEMENT/TRANSACTION events in the performance\_schema will not be timed.  
[ER\\_NANOSECOND\\_TIMER\\_IS\\_NOT\\_AVAILABLE](#) was added in 8.0.4.
  - Error number: [MY-011039](#); Symbol: [ER\\_MICROSECOND\\_TIMER\\_IS\\_NOT\\_AVAILABLE](#); SQLSTATE: [HY000](#)  
Message: The MICROSECOND timer is not available. IDLE/STAGE/STATEMENT/TRANSACTION events in the performance\_schema will not be timed.  
[ER\\_MICROSECOND\\_TIMER\\_IS\\_NOT\\_AVAILABLE](#) was added in 8.0.4.
  - Error number: [MY-011040](#); Symbol: [ER\\_PFS\\_MALLOC\\_ARRAY\\_OVERFLOW](#); SQLSTATE: [HY000](#)  
Message: Failed to allocate memory for %zu chunks each of size %zu for buffer '%s' due to overflow.  
[ER\\_PFS\\_MALLOC\\_ARRAY\\_OVERFLOW](#) was added in 8.0.4.
  - Error number: [MY-011041](#); Symbol: [ER\\_PFS\\_MALLOC\\_ARRAY\\_OOM](#); SQLSTATE: [HY000](#)
-

---

Message: Failed to allocate %zu bytes for buffer '%s' due to out-of-memory.

[ER\\_PFS\\_MALLOC\\_ARRAY\\_OOM](#) was added in 8.0.4.

- Error number: [MY-011042](#); Symbol: [ER\\_INNOQB\\_FAILED\\_TO\\_FIND\\_IDX\\_WITH\\_KEY\\_NO](#); SQLSTATE: [HY000](#)

Message: InnoDB could not find index %s key no %u for table %s through its index translation table.

[ER\\_INNOQB\\_FAILED\\_TO\\_FIND\\_IDX\\_WITH\\_KEY\\_NO](#) was added in 8.0.4.

- Error number: [MY-011043](#); Symbol: [ER\\_INNOQB\\_FAILED\\_TO\\_FIND\\_IDX](#); SQLSTATE: [HY000](#)

Message: Cannot find index %s in InnoDB index translation table.

[ER\\_INNOQB\\_FAILED\\_TO\\_FIND\\_IDX](#) was added in 8.0.4.

- Error number: [MY-011044](#); Symbol: [ER\\_INNOQB\\_FAILED\\_TO\\_FIND\\_IDX\\_FROM\\_DICT\\_CACHE](#); SQLSTATE: [HY000](#)

Message: InnoDB could not find key no %u with name %s from dict cache for table %s.

[ER\\_INNOQB\\_FAILED\\_TO\\_FIND\\_IDX\\_FROM\\_DICT\\_CACHE](#) was added in 8.0.4.

- Error number: [MY-011045](#); Symbol: [ER\\_INNOQB\\_ACTIVE\\_INDEX\\_CHANGE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: InnoDB: change\_active\_index(%u) failed.

[ER\\_INNOQB\\_ACTIVE\\_INDEX\\_CHANGE\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-011046](#); Symbol: [ER\\_INNOQB\\_DIFF\\_IN\\_REF\\_LEN](#); SQLSTATE: [HY000](#)

Message: Stored ref len is %lu, but table ref len is %lu.

[ER\\_INNOQB\\_DIFF\\_IN\\_REF\\_LEN](#) was added in 8.0.4.

- Error number: [MY-011047](#); Symbol: [ER\\_WRONG\\_TYPE\\_FOR\\_COLUMN\\_PREFIX\\_IDX\\_FLD](#); SQLSTATE: [HY000](#)

Message: MySQL is trying to create a column prefix index field, on an inappropriate data type. Table name %s, column name %s.

[ER\\_WRONG\\_TYPE\\_FOR\\_COLUMN\\_PREFIX\\_IDX\\_FLD](#) was added in 8.0.4.

- Error number: [MY-011048](#); Symbol: [ER\\_INNOQB\\_CANNOT\\_CREATE\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Cannot create table %s.

[ER\\_INNOQB\\_CANNOT\\_CREATE\\_TABLE](#) was added in 8.0.4.

- Error number: [MY-011049](#); Symbol: [ER\\_INNOQB\\_INTERNAL\\_INDEX](#); SQLSTATE: [HY000](#)

Message: Found index %s in InnoDB index list but not its MySQL index number. It could be an InnoDB internal index.

[ER\\_INNOQB\\_INTERNAL\\_INDEX](#) was added in 8.0.4.

- 
- Error number: [MY-011050](#); Symbol: [ER\\_INNODB\\_IDX\\_CNT\\_MORE\\_THAN\\_DEFINED\\_IN\\_MYSQL](#); SQLSTATE: [HY000](#)  
  
Message: InnoDB: Table %s contains %lu indexes inside InnoDB, which is different from the number of indexes %u defined in MySQL.  
  
[ER\\_INNODB\\_IDX\\_CNT\\_MORE\\_THAN\\_DEFINED\\_IN\\_MYSQL](#) was added in 8.0.4.
  - Error number: [MY-011051](#); Symbol: [ER\\_INNODB\\_IDX\\_CNT\\_FEWER\\_THAN\\_DEFINED\\_IN\\_MYSQL](#); SQLSTATE: [HY000](#)  
  
Message: Table %s contains fewer indexes inside InnoDB than are defined in the MySQL. Have you mixed up with data dictionary from different installation?  
  
[ER\\_INNODB\\_IDX\\_CNT\\_FEWER\\_THAN\\_DEFINED\\_IN\\_MYSQL](#) was added in 8.0.4.
  - Error number: [MY-011052](#); Symbol: [ER\\_INNODB\\_IDX\\_COLUMN\\_CNT\\_DIFF](#); SQLSTATE: [HY000](#)  
  
Message: Index %s of %s has %lu columns unique inside InnoDB, but MySQL is asking statistics for %lu columns. Have you mixed data dictionary from different installation?  
  
[ER\\_INNODB\\_IDX\\_COLUMN\\_CNT\\_DIFF](#) was added in 8.0.4.
  - Error number: [MY-011053](#); Symbol: [ER\\_INNODB\\_USE\\_MONITOR\\_GROUP\\_NAME](#); SQLSTATE: [HY000](#)  
  
Message: Monitor counter '%s' cannot be turned on/off individually. Please use its module name to turn on/off the counters in the module as a group.  
  
[ER\\_INNODB\\_USE\\_MONITOR\\_GROUP\\_NAME](#) was added in 8.0.4.
  - Error number: [MY-011054](#); Symbol: [ER\\_INNODB\\_MONITOR\\_DEFAULT\\_VALUE\\_NOT\\_DEFINED](#); SQLSTATE: [HY000](#)  
  
Message: Default value is not defined for this set option. Please specify correct counter or module name.  
  
[ER\\_INNODB\\_MONITOR\\_DEFAULT\\_VALUE\\_NOT\\_DEFINED](#) was added in 8.0.4.
  - Error number: [MY-011055](#); Symbol: [ER\\_INNODB\\_MONITOR\\_IS\\_ENABLED](#); SQLSTATE: [HY000](#)  
  
Message: InnoDB: Monitor %s is already enabled.  
  
[ER\\_INNODB\\_MONITOR\\_IS\\_ENABLED](#) was added in 8.0.4.
  - Error number: [MY-011056](#); Symbol: [ER\\_INNODB\\_INVALID\\_MONITOR\\_COUNTER\\_NAME](#); SQLSTATE: [HY000](#)  
  
Message: Invalid monitor counter : %s.  
  
[ER\\_INNODB\\_INVALID\\_MONITOR\\_COUNTER\\_NAME](#) was added in 8.0.4.
  - Error number: [MY-011057](#); Symbol: [ER\\_WIN\\_LOAD\\_LIBRARY\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: LoadLibrary("%s") failed: GetLastError returns %lu.  
  
[ER\\_WIN\\_LOAD\\_LIBRARY\\_FAILED](#) was added in 8.0.4.
  - Error number: [MY-011058](#); Symbol: [ER\\_PARTITION\\_HANDLER\\_ADMIN\\_MSG](#); SQLSTATE: [HY000](#)  
  
Message: %s.
-

- 
- `ER_PARTITION_HANDLER_ADMIN_MSG` was added in 8.0.4.
- Error number: `MY-011059`; Symbol: `ER_RPL_RLI_INIT_INFO_MSG`; SQLSTATE: `HY000`  
Message: %s.  
`ER_RPL_RLI_INIT_INFO_MSG` was added in 8.0.4, removed after 8.0.32.
  - Error number: `MY-011059`; Symbol: `ER_RPL_AM_INIT_INFO_MSG`; SQLSTATE: `HY000`  
Message: %s.  
`ER_RPL_AM_INIT_INFO_MSG` was added in 8.0.33.
  - Error number: `MY-011060`; Symbol: `ER_DD_UPGRADE_TABLE_INTACT_ERROR`; SQLSTATE: `HY000`  
Message: %s.  
`ER_DD_UPGRADE_TABLE_INTACT_ERROR` was added in 8.0.4.
  - Error number: `MY-011061`; Symbol: `ER_SERVER_INIT_COMPILED_IN_COMMANDS`; SQLSTATE: `HY000`  
Message: %s.  
`ER_SERVER_INIT_COMPILED_IN_COMMANDS` was added in 8.0.4.
  - Error number: `MY-011062`; Symbol: `ER_MYISAM_CHECK_METHOD_ERROR`; SQLSTATE: `HY000`  
Message: %s.  
`ER_MYISAM_CHECK_METHOD_ERROR` was added in 8.0.4.
  - Error number: `MY-011063`; Symbol: `ER_MYISAM_CRASHED_ERROR`; SQLSTATE: `HY000`  
Message: %s.  
`ER_MYISAM_CRASHED_ERROR` was added in 8.0.4.
  - Error number: `MY-011064`; Symbol: `ER_WAITPID_FAILED`; SQLSTATE: `HY000`  
Message: Unable to wait for process %lld.  
`ER_WAITPID_FAILED` was added in 8.0.4.
  - Error number: `MY-011065`; Symbol: `ER_FAILED_TO_FIND_MYSQLD_STATUS`; SQLSTATE: `HY000`  
Message: Unable to determine if daemon is running: %s (rc=%d).  
`ER_FAILED_TO_FIND_MYSQLD_STATUS` was added in 8.0.4.
  - Error number: `MY-011066`; Symbol: `ER_INNODB_ERROR_LOGGER_MSG`; SQLSTATE: `HY000`  
Message: %s  
`ER_INNODB_ERROR_LOGGER_MSG` was added in 8.0.4.
  - Error number: `MY-011067`; Symbol: `ER_INNODB_ERROR_LOGGER_FATAL_MSG`; SQLSTATE: `HY000`

---

Message: [FATAL] InnoDB: %s

[ER\\_INNODB\\_ERROR\\_LOGGER\\_FATAL\\_MSG](#) was added in 8.0.4.

- Error number: [MY-011068](#); Symbol: [ER\\_DEPRECATED\\_SYNTAX\\_WITH\\_REPLACEMENT](#); SQLSTATE: [HY000](#)

Message: The syntax '%s' is deprecated and will be removed in a future release. Please use %s instead.

[ER\\_DEPRECATED\\_SYNTAX\\_WITH\\_REPLACEMENT](#) was added in 8.0.4.

- Error number: [MY-011069](#); Symbol: [ER\\_DEPRECATED\\_SYNTAX\\_NO\\_REPLACEMENT](#); SQLSTATE: [HY000](#)

Message: The syntax '%s' is deprecated and will be removed in a future release.

[ER\\_DEPRECATED\\_SYNTAX\\_NO\\_REPLACEMENT](#) was added in 8.0.4.

- Error number: [MY-011070](#); Symbol: [ER\\_DEPRECATED\\_MSG\\_NO\\_REPLACEMENT](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release.

[ER\\_DEPRECATED\\_MSG\\_NO\\_REPLACEMENT](#) was added in 8.0.4.

- Error number: [MY-011071](#); Symbol: [ER\\_LOG\\_PRINTF\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_LOG\\_PRINTF\\_MSG](#) was added in 8.0.4.

- Error number: [MY-011072](#); Symbol: [ER\\_BINLOG\\_LOGGING\\_NOT\\_POSSIBLE](#); SQLSTATE: [HY000](#)

Message: Binary logging not possible. Message: %s.

[ER\\_BINLOG\\_LOGGING\\_NOT\\_POSSIBLE](#) was added in 8.0.4.

- Error number: [MY-011073](#); Symbol: [ER\\_FAILED\\_TO\\_SET\\_PERSISTED\\_OPTIONS](#); SQLSTATE: [HY000](#)

Message: Failed to set persisted options.

[ER\\_FAILED\\_TO\\_SET\\_PERSISTED\\_OPTIONS](#) was added in 8.0.4.

- Error number: [MY-011074](#); Symbol: [ER\\_COMPONENTS\\_FAILED\\_TO\\_ACQUIRE\\_SERVICE\\_IMPLEMENTATION](#); SQLSTATE: [HY000](#)

Message: Cannot acquire specified service implementation: '%s'.

[ER\\_COMPONENTS\\_FAILED\\_TO\\_ACQUIRE\\_SERVICE\\_IMPLEMENTATION](#) was added in 8.0.4.

- Error number: [MY-011075](#); Symbol: [ER\\_RES\\_GRP\\_INVALID\\_VCPU\\_RANGE](#); SQLSTATE: [HY000](#)

Message: Invalid VCPU range %u-%u.

[ER\\_RES\\_GRP\\_INVALID\\_VCPU\\_RANGE](#) was added in 8.0.4.

- Error number: [MY-011076](#); Symbol: [ER\\_RES\\_GRP\\_INVALID\\_VCPU\\_ID](#); SQLSTATE: [HY000](#)

Message: Invalid cpu id %u.

---

`ER_RES_GRP_INVALID_VCPU_ID` was added in 8.0.4.

- Error number: `MY-011077`; Symbol: `ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE`; SQLSTATE: `HY000`

Message: Got error %d during FLUSH\_LOGS.

`ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE` was added in 8.0.4.

- Error number: `MY-011078`; Symbol: `ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY`; SQLSTATE: `HY000`

Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.

`ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY` was added in 8.0.4.

- Error number: `MY-011079`; Symbol: `ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOGETHER`; SQLSTATE: `HY000`

Message: The option `expire_logs_days` cannot be used together with option `binlog_expire_logs_seconds`. Therefore, value of `expire_logs_days` is ignored.

`ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOGETHER` was added in 8.0.4, removed after 8.0.4.

- Error number: `MY-011079`; Symbol: `ER_EXPIRE_LOGS_DAYS_IGNORED`; SQLSTATE: `HY000`

Message: The option `expire_logs_days` cannot be used together with option `binlog_expire_logs_seconds`. Therefore, value of `expire_logs_days` is ignored.

`ER_EXPIRE_LOGS_DAYS_IGNORED` was added in 8.0.4.

- Error number: `MY-011080`; Symbol: `ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG`; SQLSTATE: `HY000`

Message: malformed or very old relay log which does not have FormatDescriptor.

`ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG` was added in 8.0.4.

- Error number: `MY-011081`; Symbol: `ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG`; SQLSTATE: `HY000`

Message: Upgrade of view '%s.%s' failed. Re-create the view with the explicit column name lesser than 64 characters.

`ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG` was added in 8.0.4.

- Error number: `MY-011082`; Symbol: `ER_TABLE_NEEDS_DUMP_UPGRADE`; SQLSTATE: `HY000`

Message: Table upgrade required for `%s`.`%s`. Please dump/reload table to fix it!

`ER_TABLE_NEEDS_DUMP_UPGRADE` was added in 8.0.4.

- Error number: `MY-011083`; Symbol: `ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE`; SQLSTATE: `HY000`

Message: Error in updating version number in %s tablespace.



---

`ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE` was added in 8.0.4.

- Error number: `MY-011084`; Symbol: `ER_KEYRING_MIGRATION_FAILED`; SQLSTATE: `HY000`  
Message: Keyring migration failed.

`ER_KEYRING_MIGRATION_FAILED` was added in 8.0.4.

- Error number: `MY-011085`; Symbol: `ER_KEYRING_MIGRATION_SUCCESSFUL`; SQLSTATE: `HY000`  
Message: Keyring migration successful.

`ER_KEYRING_MIGRATION_SUCCESSFUL` was added in 8.0.4.

- Error number: `MY-011086`; Symbol: `ER_RESTART_RECEIVED_INFO`; SQLSTATE: `HY000`  
Message: Received RESTART from user %s. Restarting mysqld (Version: %s).

`ER_RESTART_RECEIVED_INFO` was added in 8.0.4.

- Error number: `MY-011087`; Symbol: `ER_LCTN_CHANGED`; SQLSTATE: `HY000`  
Message: Different lower\_case\_table\_names settings for server ('%u') and data dictionary ('%u').

`ER_LCTN_CHANGED` was added in 8.0.4.

- Error number: `MY-011088`; Symbol: `ER_DD_INITIALIZE`; SQLSTATE: `HY000`  
Message: Data dictionary initializing version '%u'.

`ER_DD_INITIALIZE` was added in 8.0.4.

- Error number: `MY-011089`; Symbol: `ER_DD_RESTART`; SQLSTATE: `HY000`  
Message: Data dictionary restarting version '%u'.

`ER_DD_RESTART` was added in 8.0.4.

- Error number: `MY-011090`; Symbol: `ER_DD_UPGRADE`; SQLSTATE: `HY000`  
Message: Data dictionary upgrading from version '%u' to '%u'.

`ER_DD_UPGRADE` was added in 8.0.4.

- Error number: `MY-011091`; Symbol: `ER_DD_UPGRADE_OFF`; SQLSTATE: `HY000`  
Message: Data dictionary upgrade prohibited by the command line option '--no\_dd\_upgrade'.

`ER_DD_UPGRADE_OFF` was added in 8.0.4.

- Error number: `MY-011092`; Symbol: `ER_DD_UPGRADE_VERSION_NOT_SUPPORTED`; SQLSTATE: `HY000`  
Message: Upgrading the data dictionary from dictionary version '%u' is not supported.

`ER_DD_UPGRADE_VERSION_NOT_SUPPORTED` was added in 8.0.4.

- Error number: `MY-011093`; Symbol: `ER_DD_UPGRADE_SCHEMA_UNAVAILABLE`; SQLSTATE: `HY000`

---

Message: Upgrading the data dictionary failed, temporary schema name '%s' not available.

[ER\\_DD\\_UPGRADE\\_SCHEMA\\_UNAVAILABLE](#) was added in 8.0.4.

- Error number: [MY-011094](#); Symbol: [ER\\_DD\\_MINOR\\_DOWNGRADE](#); SQLSTATE: [HY000](#)

Message: Data dictionary minor downgrade from version '%u' to '%u'.

[ER\\_DD\\_MINOR\\_DOWNGRADE](#) was added in 8.0.4.

- Error number: [MY-011095](#); Symbol: [ER\\_DD\\_MINOR\\_DOWNGRADE\\_VERSION\\_NOT\\_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Minor downgrade of the Data dictionary from dictionary version '%u' is not supported.

[ER\\_DD\\_MINOR\\_DOWNGRADE\\_VERSION\\_NOT\\_SUPPORTED](#) was added in 8.0.4.

- Error number: [MY-011096](#); Symbol: [ER\\_DD\\_NO\\_VERSION\\_FOUND](#); SQLSTATE: [HY000](#)

Message: No data dictionary version number found.

[ER\\_DD\\_NO\\_VERSION\\_FOUND](#) was added in 8.0.4.

- Error number: [MY-011097](#); Symbol: [ER\\_THREAD\\_POOL\\_NOT\\_SUPPORTED\\_ON\\_PLATFORM](#); SQLSTATE: [HY000](#)

Message: Thread pool not supported, requires a minimum of %s.

[ER\\_THREAD\\_POOL\\_NOT\\_SUPPORTED\\_ON\\_PLATFORM](#) was added in 8.0.4.

- Error number: [MY-011098](#); Symbol: [ER\\_THREAD\\_POOL\\_SIZE\\_TOO\\_LOW](#); SQLSTATE: [HY000](#)

Message: thread\_pool\_size=0 means thread pool disabled, Allowed range of thread\_pool\_size is %d-%d.

[ER\\_THREAD\\_POOL\\_SIZE\\_TOO\\_LOW](#) was added in 8.0.4.

- Error number: [MY-011099](#); Symbol: [ER\\_THREAD\\_POOL\\_SIZE\\_TOO\\_HIGH](#); SQLSTATE: [HY000](#)

Message: thread\_pool\_size=%lu is too high, %d is maximum, thread pool is disabled. Allowed range of thread\_pool\_size is %d-%d.

[ER\\_THREAD\\_POOL\\_SIZE\\_TOO\\_HIGH](#) was added in 8.0.4.

- Error number: [MY-011100](#); Symbol: [ER\\_THREAD\\_POOL\\_ALGORITHM\\_INVALID](#); SQLSTATE: [HY000](#)

Message: thread\_pool\_algorithm can be set to 0 and 1, 0 indicates the default low concurrency algorithm, 1 means a high concurrency algorithm.

[ER\\_THREAD\\_POOL\\_ALGORITHM\\_INVALID](#) was added in 8.0.4.

- Error number: [MY-011101](#); Symbol: [ER\\_THREAD\\_POOL\\_INVALID\\_STALL\\_LIMIT](#); SQLSTATE: [HY000](#)

Message: thread\_pool\_stall\_limit can be %d at minimum and %d at maximum, smaller values would render the thread pool fairly useless and higher values could make it possible to have undetected deadlock issues in the MySQL Server.

[ER\\_THREAD\\_POOL\\_INVALID\\_STALL\\_LIMIT](#) was added in 8.0.4.

- 
- Error number: `MY-011102`; Symbol: `ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER`; SQLSTATE: `HY000`  
  
Message: Invalid value of `thread_pool_prio_kickup_timer` specified. Value of `thread_pool_prio_kickup_timer` should be in range 0-4294967294.  
  
`ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER` was added in 8.0.4.
  - Error number: `MY-011103`; Symbol: `ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID`; SQLSTATE: `HY000`  
  
Message: `thread_pool_max_unused_threads` cannot be set higher than %d.  
  
`ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID` was added in 8.0.4.
  - Error number: `MY-011104`; Symbol: `ER_THREAD_POOL_CON_HANDLER_INIT_FAILED`; SQLSTATE: `HY000`  
  
Message: Failed to instantiate the connection handler object.  
  
`ER_THREAD_POOL_CON_HANDLER_INIT_FAILED` was added in 8.0.4.
  - Error number: `MY-011105`; Symbol: `ER_THREAD_POOL_INIT_FAILED`; SQLSTATE: `HY000`  
  
Message: Failed to initialize thread pool plugin.  
  
`ER_THREAD_POOL_INIT_FAILED` was added in 8.0.4.
  - Error number: `MY-011107`; Symbol: `ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA`; SQLSTATE: `HY000`  
  
Message: Can't setup connection teardown thread-specific data.  
  
`ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA` was added in 8.0.4.
  - Error number: `MY-011108`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER_THD`; SQLSTATE: `HY000`  
  
Message: Creation of connect handler thread failed.  
  
`ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER_THD` was added in 8.0.4.
  - Error number: `MY-011109`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_CONN`; SQLSTATE: `HY000`  
  
Message: Failed to create thd and authenticate connection.  
  
`ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_CONN` was added in 8.0.4.
  - Error number: `MY-011110`; Symbol: `ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT`; SQLSTATE: `HY000`  
  
Message: Failed to process connection event.  
  
`ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT` was added in 8.0.4.
  - Error number: `MY-011111`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_POOL`; SQLSTATE: `HY000`

---

Message: Can't create pool thread (error %d, errno: %d).

`ER_THREAD_POOL_FAILED_TO_CREATE_POOL` was added in 8.0.4.

- Error number: `MY-011112`; Symbol: `ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS`; SQLSTATE: `HY000`

Message: %.\*s.

`ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS` was added in 8.0.4.

- Error number: `MY-011113`; Symbol: `ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED`; SQLSTATE: `HY000`

Message: `tp_group_low_level_init()` failed.

`ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-011114`; Symbol: `ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED`; SQLSTATE: `HY000`

Message: Rearm failed even after 30 seconds, can't continue without notify socket.

`ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED` was added in 8.0.4.

- Error number: `MY-011115`; Symbol: `ER_THREAD_POOL_BUFFER_TOO_SMALL`; SQLSTATE: `HY000`

Message: %s: %s buffer is too small

`ER_THREAD_POOL_BUFFER_TOO_SMALL` was added in 8.0.4.

- Error number: `MY-011116`; Symbol: `ER_MECAB_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Mecab v%s is not supported, the lowest version supported is v%s.

`ER_MECAB_NOT_SUPPORTED` was added in 8.0.4.

- Error number: `MY-011117`; Symbol: `ER_MECAB_NOT_VERIFIED`; SQLSTATE: `HY000`

Message: Mecab v%s is not verified, the highest version supported is v%s.

`ER_MECAB_NOT_VERIFIED` was added in 8.0.4.

- Error number: `MY-011118`; Symbol: `ER_MECAB_CREATING_MODEL`; SQLSTATE: `HY000`

Message: Mecab: Trying createModel(%s).

`ER_MECAB_CREATING_MODEL` was added in 8.0.4.

- Error number: `MY-011119`; Symbol: `ER_MECAB_FAILED_TO_CREATE_MODEL`; SQLSTATE: `HY000`

Message: Mecab: createModel() failed: %s.

`ER_MECAB_FAILED_TO_CREATE_MODEL` was added in 8.0.4.

- Error number: `MY-011120`; Symbol: `ER_MECAB_FAILED_TO_CREATE_TRIGGER`; SQLSTATE: `HY000`

Message: Mecab: createTagger() failed: %s.

---

`ER_MECAB_FAILED_TO_CREATE_TRIGGER` was added in 8.0.4.

- Error number: `MY-011121`; Symbol: `ER_MECAB_UNSUPPORTED_CHARSET`; SQLSTATE: `HY000`  
Message: Mecab: Unsupported dictionary charset %s.

`ER_MECAB_UNSUPPORTED_CHARSET` was added in 8.0.4.

- Error number: `MY-011122`; Symbol: `ER_MECAB_CHARSET_LOADED`; SQLSTATE: `HY000`  
Message: Mecab: Loaded dictionary charset is %s.

`ER_MECAB_CHARSET_LOADED` was added in 8.0.4.

- Error number: `MY-011123`; Symbol: `ER_MECAB_PARSE_FAILED`; SQLSTATE: `HY000`  
Message: Mecab: parse() failed: %s.

`ER_MECAB_PARSE_FAILED` was added in 8.0.4.

- Error number: `MY-011124`; Symbol: `ER_MECAB_OOM_WHILE_PARSING_TEXT`; SQLSTATE: `HY000`  
Message: Mecab: parse() failed: out of memory.

`ER_MECAB_OOM_WHILE_PARSING_TEXT` was added in 8.0.4.

- Error number: `MY-011125`; Symbol: `ER_MECAB_CREATE_LATTICE_FAILED`; SQLSTATE: `HY000`  
Message: Mecab: createLattice() failed: %s.

`ER_MECAB_CREATE_LATTICE_FAILED` was added in 8.0.4.

- Error number: `MY-011126`; Symbol: `ER_SEMISYNC_TRACE_ENTER_FUNC`; SQLSTATE: `HY000`  
Message: ---> %s enter.

`ER_SEMISYNC_TRACE_ENTER_FUNC` was added in 8.0.4.

- Error number: `MY-011127`; Symbol: `ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE`; SQLSTATE: `HY000`  
Message: <--- %s exit (%d).

`ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE` was added in 8.0.4.

- Error number: `MY-011128`; Symbol: `ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE`; SQLSTATE: `HY000`  
Message: <--- %s exit (%s).

`ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE` was added in 8.0.4.

- Error number: `MY-011129`; Symbol: `ER_SEMISYNC_TRACE_EXIT`; SQLSTATE: `HY000`  
Message: <--- %s exit.

`ER_SEMISYNC_TRACE_EXIT` was added in 8.0.4.

- Error number: `MY-011130`; Symbol: `ER_SEMISYNC_RPL_INIT_FOR_TRX`; SQLSTATE: `HY000`

---

Message: Semi-sync replication initialized for transactions.

`ER_SEMISYNC_RPL_INIT_FOR_TRX` was added in 8.0.4.

- Error number: `MY-011131`; Symbol: `ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE`; SQLSTATE: `HY000`

Message: %s: transaction node allocation failed for: (%s, %lu).

`ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE` was added in 8.0.4.

- Error number: `MY-011132`; Symbol: `ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER`; SQLSTATE: `HY000`

Message: %s: binlog write out-of-order, tail (%s, %lu), new node (%s, %lu).

`ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER` was added in 8.0.4.

- Error number: `MY-011133`; Symbol: `ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY`; SQLSTATE: `HY000`

Message: %s: insert (%s, %lu) in entry(%u).

`ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY` was added in 8.0.4.

- Error number: `MY-011134`; Symbol: `ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY`; SQLSTATE: `HY000`

Message: %s: probe (%s, %lu) in entry(%u).

`ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY` was added in 8.0.4.

- Error number: `MY-011135`; Symbol: `ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_NODES`; SQLSTATE: `HY000`

Message: %s: cleared all nodes.

`ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_NODES` was added in 8.0.4.

- Error number: `MY-011136`; Symbol: `ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TILL_POS`; SQLSTATE: `HY000`

Message: %s: cleared %d nodes back until pos (%s, %lu).

`ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TILL_POS` was added in 8.0.4.

- Error number: `MY-011137`; Symbol: `ER_SEMISYNC_REPLY_MAGIC_NO_ERROR`; SQLSTATE: `HY000`

Message: Read semi-sync reply magic number error.

`ER_SEMISYNC_REPLY_MAGIC_NO_ERROR` was added in 8.0.4.

- Error number: `MY-011138`; Symbol: `ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL`; SQLSTATE: `HY000`

Message: Read semi-sync reply length error: packet is too small.

`ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL` was added in 8.0.4.

- 
- Error number: [MY-011139](#); Symbol: [ER\\_SEMISYNC\\_REPLY\\_BINLOG\\_FILE\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)  
Message: Read semi-sync reply binlog file length too large.  
[ER\\_SEMISYNC\\_REPLY\\_BINLOG\\_FILE\\_TOO\\_LARGE](#) was added in 8.0.4.
  - Error number: [MY-011140](#); Symbol: [ER\\_SEMISYNC\\_SERVER\\_REPLY](#); SQLSTATE: [HY000](#)  
Message: %s: Got reply(%s, %lu) from server %u.  
[ER\\_SEMISYNC\\_SERVER\\_REPLY](#) was added in 8.0.4.
  - Error number: [MY-011141](#); Symbol: [ER\\_SEMISYNC\\_FUNCTION\\_CALLED\\_TWICE](#); SQLSTATE: [HY000](#)  
Message: %s called twice.  
[ER\\_SEMISYNC\\_FUNCTION\\_CALLED\\_TWICE](#) was added in 8.0.4.
  - Error number: [MY-011142](#); Symbol: [ER\\_SEMISYNC\\_RPL\\_ENABLED\\_ON\\_MASTER](#); SQLSTATE: [HY000](#)  
Message: Semi-sync replication enabled on the master.  
[ER\\_SEMISYNC\\_RPL\\_ENABLED\\_ON\\_MASTER](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011142](#); Symbol: [ER\\_SEMISYNC\\_RPL\\_ENABLED\\_ON\\_SOURCE](#); SQLSTATE: [HY000](#)  
Message: Semi-sync replication enabled on the source.  
[ER\\_SEMISYNC\\_RPL\\_ENABLED\\_ON\\_SOURCE](#) was added in 8.0.33.
  - Error number: [MY-011143](#); Symbol: [ER\\_SEMISYNC\\_MASTER\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Cannot allocate memory to enable semi-sync on the master.  
[ER\\_SEMISYNC\\_MASTER\\_OOM](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011143](#); Symbol: [ER\\_SEMISYNC\\_SOURCE\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Cannot allocate memory to enable semi-sync on the source.  
[ER\\_SEMISYNC\\_SOURCE\\_OOM](#) was added in 8.0.33.
  - Error number: [MY-011144](#); Symbol: [ER\\_SEMISYNC\\_DISABLED\\_ON\\_MASTER](#); SQLSTATE: [HY000](#)  
Message: Semi-sync replication disabled on the master.  
[ER\\_SEMISYNC\\_DISABLED\\_ON\\_MASTER](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011144](#); Symbol: [ER\\_SEMISYNC\\_DISABLED\\_ON\\_SOURCE](#); SQLSTATE: [HY000](#)  
Message: Semi-sync replication disabled on the source.  
[ER\\_SEMISYNC\\_DISABLED\\_ON\\_SOURCE](#) was added in 8.0.33.
  - Error number: [MY-011145](#); Symbol: [ER\\_SEMISYNC\\_FORCED\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: SEMISYNC: Forced shutdown. Some updates might not be replicated.  
[ER\\_SEMISYNC\\_FORCED\\_SHUTDOWN](#) was added in 8.0.4.

- 
- Error number: `MY-011146`; Symbol: `ER_SEMISYNC_MASTER_GOT_REPLY_AT_POS`; SQLSTATE: `HY000`  
Message: %s: Got reply at (%s, %lu).  
`ER_SEMISYNC_MASTER_GOT_REPLY_AT_POS` was added in 8.0.4, removed after 8.0.32.
  - Error number: `MY-011146`; Symbol: `ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS`; SQLSTATE: `HY000`  
Message: %s: Got reply at (%s, %lu).  
`ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS` was added in 8.0.33.
  - Error number: `MY-011147`; Symbol: `ER_SEMISYNC_MASTER_SIGNAL_ALL_WAITING_THREADS`; SQLSTATE: `HY000`  
Message: %s: signal all waiting threads.  
`ER_SEMISYNC_MASTER_SIGNAL_ALL_WAITING_THREADS` was added in 8.0.4, removed after 8.0.32.
  - Error number: `MY-011147`; Symbol: `ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THREADS`; SQLSTATE: `HY000`  
Message: %s: signal all waiting threads.  
`ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THREADS` was added in 8.0.33.
  - Error number: `MY-011148`; Symbol: `ER_SEMISYNC_MASTER_TRX_WAIT_POS`; SQLSTATE: `HY000`  
Message: %s: wait pos (%s, %lu), repl(%d).  
`ER_SEMISYNC_MASTER_TRX_WAIT_POS` was added in 8.0.4, removed after 8.0.32.
  - Error number: `MY-011148`; Symbol: `ER_SEMISYNC_SOURCE_TRX_WAIT_POS`; SQLSTATE: `HY000`  
Message: %s: wait pos (%s, %lu), repl(%d).  
`ER_SEMISYNC_SOURCE_TRX_WAIT_POS` was added in 8.0.33.
  - Error number: `MY-011149`; Symbol: `ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD`; SQLSTATE: `HY000`  
Message: %s: Binlog reply is ahead (%s, %lu).  
`ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD` was added in 8.0.4.
  - Error number: `MY-011150`; Symbol: `ER_SEMISYNC_MOVE_BACK_WAIT_POS`; SQLSTATE: `HY000`  
Message: %s: move back wait position (%s, %lu).  
`ER_SEMISYNC_MOVE_BACK_WAIT_POS` was added in 8.0.4.
  - Error number: `MY-011151`; Symbol: `ER_SEMISYNC_INIT_WAIT_POS`; SQLSTATE: `HY000`  
Message: %s: init wait position (%s, %lu).  
`ER_SEMISYNC_INIT_WAIT_POS` was added in 8.0.4.
  - Error number: `MY-011152`; Symbol: `ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT`; SQLSTATE: `HY000`



---

Message: %s: wait %lu ms for binlog sent (%s, %lu).

`ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT` was added in 8.0.4.

- Error number: `MY-011153`; Symbol: `ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT`; SQLSTATE: `HY000`

Message: Timeout waiting for reply of binlog (file: %s, pos: %lu), semi-sync up to file %s, position %lu.

`ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT` was added in 8.0.4.

- Error number: `MY-011154`; Symbol: `ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT_TRX_FAILED`; SQLSTATE: `HY000`

Message: Assessment of waiting time for commitTrx failed at wait position (%s, %lu).

`ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT_TRX_FAILED` was added in 8.0.4.

- Error number: `MY-011155`; Symbol: `ER_SEMISYNC_RPL_SWITCHED_OFF`; SQLSTATE: `HY000`

Message: Semi-sync replication switched OFF.

`ER_SEMISYNC_RPL_SWITCHED_OFF` was added in 8.0.4.

- Error number: `MY-011156`; Symbol: `ER_SEMISYNC_RPL_SWITCHED_ON`; SQLSTATE: `HY000`

Message: Semi-sync replication switched ON at (%s, %lu).

`ER_SEMISYNC_RPL_SWITCHED_ON` was added in 8.0.4.

- Error number: `MY-011157`; Symbol: `ER_SEMISYNC_NO_SPACE_IN_THE_PKT`; SQLSTATE: `HY000`

Message: No enough space in the packet for semi-sync extra header, semi-sync replication disabled.

`ER_SEMISYNC_NO_SPACE_IN_THE_PKT` was added in 8.0.4.

- Error number: `MY-011158`; Symbol: `ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO`; SQLSTATE: `HY000`

Message: %s: server(%d), (%s, %lu) sync(%d), repl(%d).

`ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO` was added in 8.0.4.

- Error number: `MY-011159`; Symbol: `ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE`; SQLSTATE: `HY000`

Message: Semi-sync failed to insert tranx\_node for binlog file: %s, position: %lu.

`ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE` was added in 8.0.4.

- Error number: `MY-011160`; Symbol: `ER_SEMISYNC_TRX_SKIPPED_AT_POS`; SQLSTATE: `HY000`

Message: %s: Transaction skipped at (%s, %lu).

`ER_SEMISYNC_TRX_SKIPPED_AT_POS` was added in 8.0.4.

- Error number: `MY-011161`; Symbol: `ER_SEMISYNC_MASTER_FAILED_ON_NET_FLUSH`; SQLSTATE: `HY000`

---

Message: Semi-sync master failed on net\_flush() before waiting for replica reply.

`ER_SEMISYNC_MASTER_FAILED_ON_NET_FLUSH` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011161`; Symbol: `ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH`; SQLSTATE: `HY000`

Message: Semi-sync source failed on net\_flush() before waiting for replica reply.

`ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH` was added in 8.0.33.

- Error number: `MY-011162`; Symbol: `ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER`; SQLSTATE: `HY000`

Message: The received ack is smaller than m\_greatest\_ack.

`ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER` was added in 8.0.4.

- Error number: `MY-011163`; Symbol: `ER_SEMISYNC_ADD_ACK_TO_SLOT`; SQLSTATE: `HY000`

Message: Add the ack into slot %u.

`ER_SEMISYNC_ADD_ACK_TO_SLOT` was added in 8.0.4.

- Error number: `MY-011164`; Symbol: `ER_SEMISYNC_UPDATE_EXISTING_SLAVE_ACK`; SQLSTATE: `HY000`

Message: Update an existing ack in slot %u.

`ER_SEMISYNC_UPDATE_EXISTING_SLAVE_ACK` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011164`; Symbol: `ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK`; SQLSTATE: `HY000`

Message: Update an existing ack in slot %u.

`ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK` was added in 8.0.33.

- Error number: `MY-011165`; Symbol: `ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD`; SQLSTATE: `HY000`

Message: Failed to start semi-sync ACK receiver thread, could not create thread(errno=%d).

`ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD` was added in 8.0.4.

- Error number: `MY-011166`; Symbol: `ER_SEMISYNC_STARTING_ACK_RECEIVER_THD`; SQLSTATE: `HY000`

Message: Starting ack receiver thread.

`ER_SEMISYNC_STARTING_ACK_RECEIVER_THD` was added in 8.0.4.

- Error number: `MY-011167`; Symbol: `ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET`; SQLSTATE: `HY000`

Message: Failed to wait on semi-sync dump sockets, error: errno=%d.

`ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET` was added in 8.0.4.

- 
- Error number: [MY-011168](#); Symbol: [ER\\_SEMISYNC\\_STOPPING\\_ACK\\_RECEIVER\\_THREAD](#); SQLSTATE: [HY000](#)  
  
Message: Stopping ack receiver thread.  
  
[ER\\_SEMISYNC\\_STOPPING\\_ACK\\_RECEIVER\\_THREAD](#) was added in 8.0.4.
  - Error number: [MY-011169](#); Symbol: [ER\\_SEMISYNC\\_FAILED\\_REGISTER\\_SLAVE\\_TO\\_RECEIVER](#); SQLSTATE: [HY000](#)  
  
Message: Failed to register slave to semi-sync ACK receiver thread.  
  
[ER\\_SEMISYNC\\_FAILED\\_REGISTER\\_SLAVE\\_TO\\_RECEIVER](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011169](#); Symbol: [ER\\_SEMISYNC\\_FAILED\\_REGISTER\\_REPLICA\\_TO\\_RECEIVER](#); SQLSTATE: [HY000](#)  
  
Message: Failed to register replica to semi-sync ACK receiver thread.  
  
[ER\\_SEMISYNC\\_FAILED\\_REGISTER\\_REPLICA\\_TO\\_RECEIVER](#) was added in 8.0.33.
  - Error number: [MY-011170](#); Symbol: [ER\\_SEMISYNC\\_START\\_BINLOG\\_DUMP\\_TO\\_SLAVE](#); SQLSTATE: [HY000](#)  
  
Message: Start %s binlog\_dump to slave (server\_id: %d), pos(%s, %lu).  
  
[ER\\_SEMISYNC\\_START\\_BINLOG\\_DUMP\\_TO\\_SLAVE](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011170](#); Symbol: [ER\\_SEMISYNC\\_START\\_BINLOG\\_DUMP\\_TO\\_REPLICA](#); SQLSTATE: [HY000](#)  
  
Message: Start %s binlog\_dump to replica (server\_id: %d), pos(%s, %lu).  
  
[ER\\_SEMISYNC\\_START\\_BINLOG\\_DUMP\\_TO\\_REPLICA](#) was added in 8.0.33.
  - Error number: [MY-011171](#); Symbol: [ER\\_SEMISYNC\\_STOP\\_BINLOG\\_DUMP\\_TO\\_SLAVE](#); SQLSTATE: [HY000](#)  
  
Message: Stop %s binlog\_dump to slave (server\_id: %d).  
  
[ER\\_SEMISYNC\\_STOP\\_BINLOG\\_DUMP\\_TO\\_SLAVE](#) was added in 8.0.4, removed after 8.0.32.
  - Error number: [MY-011171](#); Symbol: [ER\\_SEMISYNC\\_STOP\\_BINLOG\\_DUMP\\_TO\\_REPLICA](#); SQLSTATE: [HY000](#)  
  
Message: Stop %s binlog\_dump to replica (server\_id: %d).  
  
[ER\\_SEMISYNC\\_STOP\\_BINLOG\\_DUMP\\_TO\\_REPLICA](#) was added in 8.0.33.
  - Error number: [MY-011172](#); Symbol: [ER\\_SEMISYNC\\_UNREGISTER\\_TRX\\_OBSERVER\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: unregister\_trans\_observer failed.  
  
[ER\\_SEMISYNC\\_UNREGISTER\\_TRX\\_OBSERVER\\_FAILED](#) was added in 8.0.4.
  - Error number: [MY-011173](#); Symbol: [ER\\_SEMISYNC\\_UNREGISTER\\_BINLOG\\_STORAGE\\_OBSERVER\\_FAILED](#); SQLSTATE: [HY000](#)
-

---

Message: unregister\_binlog\_storage\_observer failed.

[ER\\_SEMISYNC\\_UNREGISTER\\_BINLOG\\_STORAGE\\_OBSERVER\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-011174](#); Symbol: [ER\\_SEMISYNC\\_UNREGISTER\\_BINLOG\\_TRANSMIT\\_OBSERVER\\_FAILED](#); SQLSTATE: [HY000](#)

Message: unregister\_binlog\_transmit\_observer failed.

[ER\\_SEMISYNC\\_UNREGISTER\\_BINLOG\\_TRANSMIT\\_OBSERVER\\_FAILED](#) was added in 8.0.4.

- Error number: [MY-011175](#); Symbol: [ER\\_SEMISYNC\\_UNREGISTERED\\_REPLICATOR](#); SQLSTATE: [HY000](#)

Message: unregister\_replicator OK.

[ER\\_SEMISYNC\\_UNREGISTERED\\_REPLICATOR](#) was added in 8.0.4.

- Error number: [MY-011176](#); Symbol: [ER\\_SEMISYNC\\_SOCKET\\_FD\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)

Message: Semisync replica socket fd is %u. select() cannot handle if the socket fd is bigger than %u (FD\_SETSIZE).

[ER\\_SEMISYNC\\_SOCKET\\_FD\\_TOO\\_LARGE](#) was added in 8.0.4.

- Error number: [MY-011177](#); Symbol: [ER\\_SEMISYNC\\_SLAVE\\_REPLY](#); SQLSTATE: [HY000](#)

Message: %s: reply - %d.

[ER\\_SEMISYNC\\_SLAVE\\_REPLY](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011177](#); Symbol: [ER\\_SEMISYNC\\_REPLICA\\_REPLY](#); SQLSTATE: [HY000](#)

Message: %s: reply - %d.

[ER\\_SEMISYNC\\_REPLICA\\_REPLY](#) was added in 8.0.33.

- Error number: [MY-011178](#); Symbol: [ER\\_SEMISYNC\\_MISSING\\_MAGIC\\_NO\\_FOR\\_SEMISYNC\\_PKT](#); SQLSTATE: [HY000](#)

Message: Missing magic number for semi-sync packet, packet len: %lu.

[ER\\_SEMISYNC\\_MISSING\\_MAGIC\\_NO\\_FOR\\_SEMISYNC\\_PKT](#) was added in 8.0.4.

- Error number: [MY-011179](#); Symbol: [ER\\_SEMISYNC\\_SLAVE\\_START](#); SQLSTATE: [HY000](#)

Message: Slave I/O thread: Start %s replication to master '%s@%s:%d' in log '%s' at position %lu.

[ER\\_SEMISYNC\\_SLAVE\\_START](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011179](#); Symbol: [ER\\_SEMISYNC\\_REPLICA\\_START](#); SQLSTATE: [HY000](#)

Message: Replica I/O thread: Start %s replication to source '%s@%s:%d' in log '%s' at position %lu.

[ER\\_SEMISYNC\\_REPLICA\\_START](#) was added in 8.0.33.

- Error number: [MY-011180](#); Symbol: [ER\\_SEMISYNC\\_SLAVE\\_REPLY\\_WITH\\_BINLOG\\_INFO](#); SQLSTATE: [HY000](#)

---

Message: %s: reply (%s, %lu).

[ER\\_SEMISYNC\\_SLAVE\\_REPLY\\_WITH\\_BINLOG\\_INFO](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011180](#); Symbol: [ER\\_SEMISYNC\\_REPLICA\\_REPLY\\_WITH\\_BINLOG\\_INFO](#); SQLSTATE: [HY000](#)

Message: %s: reply (%s, %lu).

[ER\\_SEMISYNC\\_REPLICA\\_REPLY\\_WITH\\_BINLOG\\_INFO](#) was added in 8.0.33.

- Error number: [MY-011181](#); Symbol: [ER\\_SEMISYNC\\_SLAVE\\_NET\\_FLUSH\\_REPLY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Semi-sync slave net\_flush() reply failed.

[ER\\_SEMISYNC\\_SLAVE\\_NET\\_FLUSH\\_REPLY\\_FAILED](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011181](#); Symbol: [ER\\_SEMISYNC\\_REPLICA\\_NET\\_FLUSH\\_REPLY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Semi-sync replica net\_flush() reply failed.

[ER\\_SEMISYNC\\_REPLICA\\_NET\\_FLUSH\\_REPLY\\_FAILED](#) was added in 8.0.33.

- Error number: [MY-011182](#); Symbol: [ER\\_SEMISYNC\\_SLAVE\\_SEND\\_REPLY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Semi-sync slave send reply failed: %s (%d).

[ER\\_SEMISYNC\\_SLAVE\\_SEND\\_REPLY\\_FAILED](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011182](#); Symbol: [ER\\_SEMISYNC\\_REPLICA\\_SEND\\_REPLY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Semi-sync replica send reply failed: %s (%d).

[ER\\_SEMISYNC\\_REPLICA\\_SEND\\_REPLY\\_FAILED](#) was added in 8.0.33.

- Error number: [MY-011183](#); Symbol: [ER\\_SEMISYNC\\_EXECUTION\\_FAILED\\_ON\\_MASTER](#); SQLSTATE: [HY000](#)

Message: Execution failed on master: %s; error %d

[ER\\_SEMISYNC\\_EXECUTION\\_FAILED\\_ON\\_MASTER](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011183](#); Symbol: [ER\\_SEMISYNC\\_EXECUTION\\_FAILED\\_ON\\_SOURCE](#); SQLSTATE: [HY000](#)

Message: Execution failed on source: %s; error %d

[ER\\_SEMISYNC\\_EXECUTION\\_FAILED\\_ON\\_SOURCE](#) was added in 8.0.33.

- 
- Error number: `MY-011184`; Symbol: `ER_SEMISYNC_NOT_SUPPORTED_BY_MASTER`; SQLSTATE: `HY000`  
  
Message: Master server does not support semi-sync, fallback to asynchronous replication  
  
`ER_SEMISYNC_NOT_SUPPORTED_BY_MASTER` was added in 8.0.4, removed after 8.0.32.
  - Error number: `MY-011184`; Symbol: `ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE`; SQLSTATE: `HY000`  
  
Message: Source server does not support semi-sync, fallback to asynchronous replication  
  
`ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE` was added in 8.0.33.
  - Error number: `MY-011185`; Symbol: `ER_SEMISYNC_SLAVE_SET_FAILED`; SQLSTATE: `HY000`  
  
Message: Set 'rpl\_semi\_sync\_replica=1' on master failed  
  
`ER_SEMISYNC_SLAVE_SET_FAILED` was added in 8.0.4, removed after 8.0.32.
  - Error number: `MY-011185`; Symbol: `ER_SEMISYNC_REPLICA_SET_FAILED`; SQLSTATE: `HY000`  
  
Message: Set 'rpl\_semi\_sync\_replica=1' on source failed  
  
`ER_SEMISYNC_REPLICA_SET_FAILED` was added in 8.0.33.
  - Error number: `MY-011186`; Symbol: `ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THD`; SQLSTATE: `HY000`  
  
Message: Failed to stop ack receiver thread on my\_thread\_join, errno(%d).  
  
`ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THD` was added in 8.0.4.
  - Error number: `MY-011187`; Symbol: `ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES`; SQLSTATE: `HY000`  
  
Message: Failed to read the firewall tables  
  
`ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES` was added in 8.0.4.
  - Error number: `MY-011188`; Symbol: `ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES`; SQLSTATE: `HY000`  
  
Message: Failed to register dynamic privileges  
  
`ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES` was added in 8.0.4.
  - Error number: `MY-011189`; Symbol: `ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED`; SQLSTATE: `HY000`  
  
Message: Statement was truncated and not recorded: %s  
  
`ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED` was added in 8.0.4.

- 
- Error number: `MY-011190`; Symbol: `ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT`; SQLSTATE: `HY000`  
Message: Statement with no text was not recorded  
`ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT` was added in 8.0.4.
  - Error number: `MY-011191`; Symbol: `ER_FIREWALL_SUSPICIOUS_STMT`; SQLSTATE: `HY000`  
Message: SUSPICIOUS STATEMENT from '%s'. Reason: %s Statement: %s  
`ER_FIREWALL_SUSPICIOUS_STMT` was added in 8.0.4.
  - Error number: `MY-011192`; Symbol: `ER_FIREWALL_ACCESS_DENIED`; SQLSTATE: `HY000`  
Message: ACCESS DENIED for '%s'. Reason: %s Statement: %s  
`ER_FIREWALL_ACCESS_DENIED` was added in 8.0.4.
  - Error number: `MY-011193`; Symbol: `ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE`; SQLSTATE: `HY000`  
Message: Skipped unknown user mode '%s'  
`ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE` was added in 8.0.4.
  - Error number: `MY-011194`; Symbol: `ER_FIREWALL_RELOADING_CACHE`; SQLSTATE: `HY000`  
Message: Reloading cache from disk  
`ER_FIREWALL_RELOADING_CACHE` was added in 8.0.4.
  - Error number: `MY-011195`; Symbol: `ER_FIREWALL_RESET_FOR_USER`; SQLSTATE: `HY000`  
Message: FIREWALL RESET for '%s'  
`ER_FIREWALL_RESET_FOR_USER` was added in 8.0.4.
  - Error number: `MY-011196`; Symbol: `ER_FIREWALL_STATUS_FLUSHED`; SQLSTATE: `HY000`  
Message: Counters are reset to zero  
`ER_FIREWALL_STATUS_FLUSHED` was added in 8.0.4.
  - Error number: `MY-011197`; Symbol: `ER_KEYRING_LOGGER_ERROR_MSG`; SQLSTATE: `HY000`  
Message: %s  
`ER_KEYRING_LOGGER_ERROR_MSG` was added in 8.0.4.
  - Error number: `MY-011198`; Symbol: `ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED`; SQLSTATE: `HY000`  
Message: Audit Log plugin supports filtering mode, which has not been installed yet. Audit Log plugin will run in the legacy mode, which will be removed in the next release.  
`ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED` was added in 8.0.4.
  - Error number: `MY-011199`; Symbol: `ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST`; SQLSTATE: `HY000`

---

Message: Previously exclude list is used, now we start using include list, exclude list is set to NULL.

`ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST` was added in 8.0.4.

- Error number: `MY-011200`; Symbol:

`ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER_POLICIES`; SQLSTATE: `HY000`

Message: Cannot set `audit_log_policy` simultaneously with either `audit_log_connection_policy` or `audit_log_statement_policy`, setting `audit_log_connection_policy` and `audit_log_statement_policy` based on `audit_log_policy`.

`ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER_POLICIES` was added in 8.0.4.

- Error number: `MY-011201`; Symbol: `ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED`; SQLSTATE: `HY000`

Message: Both include and exclude lists provided, include list is preferred, exclude list is set to NULL.

`ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED` was added in 8.0.4.

- Error number: `MY-011202`; Symbol: `ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR`; SQLSTATE: `HY000`

Message: Could not access '%s' directory.

`ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR` was added in 8.0.4.

- Error number: `MY-011203`; Symbol: `ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED`; SQLSTATE: `HY000`

Message: Could not rename file from '%s' to '%s'.

`ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED` was added in 8.0.4.

- Error number: `MY-011204`; Symbol: `ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS`; SQLSTATE: `HY000`

Message: File '%s' should not exist. It may be incomplete. The server crashed.

`ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS` was added in 8.0.4.

- Error number: `MY-011205`; Symbol:

`ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE_FILE_MANUALLY`; SQLSTATE: `HY000`

Message: Could not rename file from '%s' to '%s'. Remove the file manually.

`ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE_FILE_MANUALLY` was added in 8.0.4.

- Error number: `MY-011206`; Symbol: `ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED`; SQLSTATE: `HY000`

Message: Incomplete file renamed from '%s' to '%s'.

`ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED` was added in 8.0.4.

- Error number: `MY-011207`; Symbol: `ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE`; SQLSTATE: `HY000`



---

Message: Error writing file '%s' (errno: %d - %s).

[ER\\_AUDIT\\_LOG\\_WRITER\\_FAILED\\_TO\\_WRITE\\_TO\\_FILE](#) was added in 8.0.4.

- Error number: [MY-011208](#); Symbol: [ER\\_AUDIT\\_LOG\\_EC\\_WRITER\\_FAILED\\_TO\\_INIT\\_ENCRYPTION](#); SQLSTATE: [HY000](#)

Message: Could not initialize audit log file encryption.

[ER\\_AUDIT\\_LOG\\_EC\\_WRITER\\_FAILED\\_TO\\_INIT\\_ENCRYPTION](#) was added in 8.0.4.

- Error number: [MY-011209](#); Symbol: [ER\\_AUDIT\\_LOG\\_EC\\_WRITER\\_FAILED\\_TO\\_INIT\\_COMPRESSION](#); SQLSTATE: [HY000](#)

Message: Could not initialize audit log file compression.

[ER\\_AUDIT\\_LOG\\_EC\\_WRITER\\_FAILED\\_TO\\_INIT\\_COMPRESSION](#) was added in 8.0.4.

- Error number: [MY-011210](#); Symbol: [ER\\_AUDIT\\_LOG\\_EC\\_WRITER\\_FAILED\\_TO\\_CREATE\\_FILE](#); SQLSTATE: [HY000](#)

Message: Could not create '%s' file for audit logging.

[ER\\_AUDIT\\_LOG\\_EC\\_WRITER\\_FAILED\\_TO\\_CREATE\\_FILE](#) was added in 8.0.4.

- Error number: [MY-011211](#); Symbol: [ER\\_AUDIT\\_LOG\\_RENAME\\_LOG\\_FILE\\_BEFORE\\_FLUSH](#); SQLSTATE: [HY000](#)

Message: Audit log file (%s) must be manually renamed before audit\_log\_flush is set to true.

[ER\\_AUDIT\\_LOG\\_RENAME\\_LOG\\_FILE\\_BEFORE\\_FLUSH](#) was added in 8.0.4.

- Error number: [MY-011212](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILTER\\_RESULT\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_AUDIT\\_LOG\\_FILTER\\_RESULT\\_MSG](#) was added in 8.0.4.

- Error number: [MY-011213](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_READER\\_FAILED\\_TO\\_PARSE](#); SQLSTATE: [HY000](#)

Message: Error parsing JSON event. Event not accessible.

[ER\\_AUDIT\\_LOG\\_JSON\\_READER\\_FAILED\\_TO\\_PARSE](#) was added in 8.0.4.

- Error number: [MY-011214](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_READER\\_BUF\\_TOO\\_SMALL](#); SQLSTATE: [HY000](#)

Message: Buffer is too small to hold JSON event. Number of events skipped: %zu.

[ER\\_AUDIT\\_LOG\\_JSON\\_READER\\_BUF\\_TOO\\_SMALL](#) was added in 8.0.4.

- Error number: [MY-011215](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_READER\\_FAILED\\_TO\\_OPEN\\_FILE](#); SQLSTATE: [HY000](#)

Message: Could not open JSON file for reading. Reading next file if exists.

[ER\\_AUDIT\\_LOG\\_JSON\\_READER\\_FAILED\\_TO\\_OPEN\\_FILE](#) was added in 8.0.4.

- 
- Error number: `MY-011216`; Symbol: `ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR`; SQLSTATE: `HY000`  
Message: JSON file parsing error. Reading next file if exists  
`ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR` was added in 8.0.4.
  - Error number: `MY-011217`; Symbol: `ER_AUDIT_LOG_FILTER_INVALID_COLUMN_COUNT`; SQLSTATE: `HY000`  
Message: Invalid column count in the '%s.%s' table.  
`ER_AUDIT_LOG_FILTER_INVALID_COLUMN_COUNT` was added in 8.0.4, removed after 8.0.25.
  - Error number: `MY-011218`; Symbol: `ER_AUDIT_LOG_FILTER_INVALID_COLUMN_DEFINITION`; SQLSTATE: `HY000`  
Message: Invalid column definition of the '%s.%s' table.  
`ER_AUDIT_LOG_FILTER_INVALID_COLUMN_DEFINITION` was added in 8.0.4, removed after 8.0.25.
  - Error number: `MY-011219`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FLDS`; SQLSTATE: `HY000`  
Message: Could not store field of the %s table.  
`ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FLDS` was added in 8.0.4.
  - Error number: `MY-011220`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE`; SQLSTATE: `HY000`  
Message: Could not update %s table.  
`ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE` was added in 8.0.4.
  - Error number: `MY-011221`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE`; SQLSTATE: `HY000`  
Message: Could not insert into %s table.  
`ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE` was added in 8.0.4.
  - Error number: `MY-011222`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE`; SQLSTATE: `HY000`  
Message: Could not delete from %s table.  
`ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE` was added in 8.0.4.
  - Error number: `MY-011223`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ`; SQLSTATE: `HY000`  
Message: Could not initialize %s table for reading.  
`ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ` was added in 8.0.4.
  - Error number: `MY-011224`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE`; SQLSTATE: `HY000`

---

Message: Could not read %s table.

`ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE` was added in 8.0.4.

- Error number: `MY-011225`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE_AFTER_READING`; `SQLSTATE: HY000`

Message: Could not close %s table reading.

`ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE_AFTER_READING` was added in 8.0.4.

- Error number: `MY-011226`; Symbol: `ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY`; `SQLSTATE: HY000`

Message: Both user and host columns of %s table cannot be empty.

`ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY` was added in 8.0.4.

- Error number: `MY-011227`; Symbol: `ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY`; `SQLSTATE: HY000`

Message: Filtername column of %s table cannot be empty.

`ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY` was added in 8.0.4.

- Error number: `MY-011228`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED`; `SQLSTATE: HY000`

Message: Dictionary file not specified

`ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED` was added in 8.0.4.

- Error number: `MY-011229`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED`; `SQLSTATE: HY000`

Message: Dictionary file not loaded

`ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED` was added in 8.0.4.

- Error number: `MY-011230`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_TOO_BIG`; `SQLSTATE: HY000`

Message: Dictionary file size exceeded `MAX_DICTIONARY_FILE_LENGTH`, not loaded

`ER_VALIDATE_PWD_DICT_FILE_TOO_BIG` was added in 8.0.4.

- Error number: `MY-011231`; Symbol: `ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE`; `SQLSTATE: HY000`

Message: Exception while reading the dictionary file

`ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE` was added in 8.0.4.

- Error number: `MY-011232`; Symbol: `ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CTX`; `SQLSTATE: HY000`

Message: Can't retrieve the %s from the security context

`ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CTX` was added in 8.0.4.

- 
- Error number: `MY-011233`; Symbol: `ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX`; SQLSTATE: `HY000`  
Message: Can't retrieve the security context  
`ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX` was added in 8.0.4.
  - Error number: `MY-011234`; Symbol: `ER_VALIDATE_PWD_LENGTH_CHANGED`; SQLSTATE: `HY000`  
Message: Effective value of `validate_password_length` is changed. New value is %d  
`ER_VALIDATE_PWD_LENGTH_CHANGED` was added in 8.0.4.
  - Error number: `MY-011235`; Symbol: `ER_REWRITER_QUERY_ERROR_MSG`; SQLSTATE: `HY000`  
Message: %s  
`ER_REWRITER_QUERY_ERROR_MSG` was added in 8.0.4.
  - Error number: `MY-011236`; Symbol: `ER_REWRITER_QUERY_FAILED`; SQLSTATE: `HY000`  
Message: Rewritten query failed to parse:%s  
`ER_REWRITER_QUERY_FAILED` was added in 8.0.4.
  - Error number: `MY-011237`; Symbol: `ER_XPLUGIN_STARTUP_FAILED`; SQLSTATE: `HY000`  
Message: Startup failed with error "%s"  
`ER_XPLUGIN_STARTUP_FAILED` was added in 8.0.4.
  - Error number: `MY-011238`; Symbol: `ER_XPLUGIN_SERVER_EXITING`; SQLSTATE: `HY000`  
Message: Exiting  
`ER_XPLUGIN_SERVER_EXITING` was added in 8.0.4, removed after 8.0.12.
  - Error number: `MY-011239`; Symbol: `ER_XPLUGIN_SERVER_EXITED`; SQLSTATE: `HY000`  
Message: Exit done  
`ER_XPLUGIN_SERVER_EXITED` was added in 8.0.4, removed after 8.0.12.
  - Error number: `MY-011240`; Symbol: `ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER`; SQLSTATE: `HY000`  
Message: Using SSL configuration from MySQL Server  
`ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER` was added in 8.0.4.
  - Error number: `MY-011241`; Symbol: `ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX`; SQLSTATE: `HY000`  
Message: Using SSL configuration from Mysqlx Plugin  
`ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX` was added in 8.0.4.
  - Error number: `MY-011242`; Symbol: `ER_XPLUGIN_FAILED_TO_USE_SSL_CONF`; SQLSTATE: `HY000`  
Message: Neither MySQL Server nor Mysqlx Plugin has valid SSL configuration

---

`ER_XPLUGIN_FAILED_TO_USE_SSL_CONF` was added in 8.0.4.

- Error number: `MY-011243`; Symbol: `ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION`; SQLSTATE: `HY000`

Message: Using %s for TLS connections

`ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION` was added in 8.0.4.

- Error number: `MY-011244`; Symbol: `ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_XPLUGIN`; SQLSTATE: `HY000`

Message: For more information, please see the Using Secure Connections with X Plugin section in the MySQL documentation

`ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_XPLUGIN` was added in 8.0.4.

- Error number: `MY-011245`; Symbol: `ER_XPLUGIN_ERROR_MSG`; SQLSTATE: `HY000`

Message: %s

`ER_XPLUGIN_ERROR_MSG` was added in 8.0.4.

- Error number: `MY-011246`; Symbol: `ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING`; SQLSTATE: `HY000`

Message: Failed to parse stored authentication string for %s. Please check if mysql.user table not corrupted

`ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING` was added in 8.0.4.

- Error number: `MY-011247`; Symbol: `ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH`; SQLSTATE: `HY000`

Message: Error in generating multi-round hash for %s. Plugin can not perform authentication without it. This may be a transient problem

`ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH` was added in 8.0.4.

- Error number: `MY-011248`; Symbol: `ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL`; SQLSTATE: `HY000`

Message: Authentication requires either RSA keys or SSL encryption

`ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL` was added in 8.0.4.

- Error number: `MY-011249`; Symbol: `ER_SHA_PWD_RSA_KEY_TOO_LONG`; SQLSTATE: `HY000`

Message: RSA key cipher length of %u is too long. Max value is %u

`ER_SHA_PWD_RSA_KEY_TOO_LONG` was added in 8.0.4.

- Error number: `MY-011250`; Symbol: `ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLES`; SQLSTATE: `HY000`

Message: Failed to open the %s filter tables

`ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLES` was added in 8.0.4.

- 
- Error number: `MY-011251`; Symbol: `ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE`; SQLSTATE: `HY000`  
Message: Failed to open '%s.%s' %s table  
`ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE` was added in 8.0.4.
  - Error number: `MY-011252`; Symbol: `ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG`; SQLSTATE: `HY000`  
Message: %s  
`ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG` was added in 8.0.4.
  - Error number: `MY-011253`; Symbol: `ER_CONN_CONTROL_ERROR_MSG`; SQLSTATE: `HY000`  
Message: %s  
`ER_CONN_CONTROL_ERROR_MSG` was added in 8.0.4.
  - Error number: `MY-011254`; Symbol: `ER_GRP_RPL_ERROR_MSG`; SQLSTATE: `HY000`  
Message: %s  
`ER_GRP_RPL_ERROR_MSG` was added in 8.0.4.
  - Error number: `MY-011255`; Symbol: `ER_SHA_PWD_SALT_FOR_USER_CORRUPT`; SQLSTATE: `HY000`  
Message: Password salt for user '%s' is corrupt  
`ER_SHA_PWD_SALT_FOR_USER_CORRUPT` was added in 8.0.4.
  - Error number: `MY-011256`; Symbol: `ER_SYS_VAR_COMPONENT_OOM`; SQLSTATE: `HY000`  
Message: Out of memory for component system variable '%s'.  
`ER_SYS_VAR_COMPONENT_OOM` was added in 8.0.4.
  - Error number: `MY-011257`; Symbol: `ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY`; SQLSTATE: `HY000`  
Message: variable %s of component %s was forced to be read-only: string variable without update\_func and PLUGIN\_VAR\_MEMALLOC flag.  
`ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY` was added in 8.0.4.
  - Error number: `MY-011258`; Symbol: `ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE`; SQLSTATE: `HY000`  
Message: Unknown variable type code 0x%x in component '%s'.  
`ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE` was added in 8.0.4.
  - Error number: `MY-011259`; Symbol: `ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE_OPTIONS`; SQLSTATE: `HY000`  
Message: Parsing options for variable '%s' failed.  
`ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE_OPTIONS` was added in 8.0.4.

- 
- Error number: [MY-011260](#); Symbol: [ER\\_SYS\\_VAR\\_COMPONENT\\_FAILED\\_TO\\_MAKE\\_VARIABLE\\_PERSISTENT](#); SQLSTATE: [HY000](#)  
Message: Setting persistent options for component variable '%s' failed.  
[ER\\_SYS\\_VAR\\_COMPONENT\\_FAILED\\_TO\\_MAKE\\_VARIABLE\\_PERSISTENT](#) was added in 8.0.4.
  - Error number: [MY-011261](#); Symbol: [ER\\_COMPONENT\\_FILTER\\_CONFUSED](#); SQLSTATE: [HY000](#)  
Message: The log-filter component "%s" got confused at "%s" (state: %s) ...  
[ER\\_COMPONENT\\_FILTER\\_CONFUSED](#) was added in 8.0.4.
  - Error number: [MY-011262](#); Symbol: [ER\\_STOP\\_SLAVE\\_IO\\_THREAD\\_DISK\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Waiting until I/O thread for channel '%s' finish writing to disk before stopping. Free some disk space or use 'KILL' to abort I/O thread operation. Notice that aborting the I/O thread while rotating the relay log might corrupt the relay logs, requiring a server restart to fix it.  
[ER\\_STOP\\_SLAVE\\_IO\\_THREAD\\_DISK\\_SPACE](#) was added in 8.0.2, removed after 8.0.32.
  - Error number: [MY-011262](#); Symbol: [ER\\_STOP\\_REPLICA\\_IO\\_THREAD\\_DISK\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Waiting until I/O thread for channel '%s' finish writing to disk before stopping. Free some disk space or use 'KILL' to abort I/O thread operation. Notice that aborting the I/O thread while rotating the relay log might corrupt the relay logs, requiring a server restart to fix it.  
[ER\\_STOP\\_REPLICA\\_IO\\_THREAD\\_DISK\\_SPACE](#) was added in 8.0.33.
  - Error number: [MY-011263](#); Symbol: [ER\\_LOG\\_FILE\\_CANNOT\\_OPEN](#); SQLSTATE: [HY000](#)  
Message: Could not use %s for logging (error %d - %s). Turning logging off for the server process. To turn it on again: fix the cause, then %s restart the MySQL server.  
[ER\\_LOG\\_FILE\\_CANNOT\\_OPEN](#) was added in 8.0.2.
  - Error number: [MY-011268](#); Symbol: [ER\\_PERSIST\\_OPTION\\_STATUS](#); SQLSTATE: [HY000](#)  
Message: Configuring persisted options failed: "%s".  
[ER\\_PERSIST\\_OPTION\\_STATUS](#) was added in 8.0.11.
  - Error number: [MY-011269](#); Symbol: [ER\\_NOT\\_IMPLEMENTED\\_GET\\_TABLESPACE\\_STATISTICS](#); SQLSTATE: [HY000](#)  
Message: The storage engine '%s' does not provide dynamic table statistics  
[ER\\_NOT\\_IMPLEMENTED\\_GET\\_TABLESPACE\\_STATISTICS](#) was added in 8.0.11.
  - Error number: [MY-011272](#); Symbol: [ER\\_SSL\\_FIPS\\_MODE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: SSL fips mode error: %s  
[ER\\_SSL\\_FIPS\\_MODE\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011273](#); Symbol: [ER\\_CONN\\_INIT\\_CONNECT\\_IGNORED](#); SQLSTATE: [HY000](#)  
Message: init\_connect variable is ignored for user: %s host: %s due to expired password.

---

`ER_CONN_INIT_CONNECT_IGNORED` was added in 8.0.11.

- Error number: `MY-011275`; Symbol: `ER_REWRITER_OOM`; SQLSTATE: `HY000`

Message: Out of memory.

`ER_REWRITER_OOM` was added in 8.0.11.

- Error number: `MY-011276`; Symbol: `ER_REWRITER_TABLE_MALFORMED_ERROR`; SQLSTATE: `HY000`

Message: Wrong column count or names when loading rules.

`ER_REWRITER_TABLE_MALFORMED_ERROR` was added in 8.0.11.

- Error number: `MY-011277`; Symbol: `ER_REWRITER_LOAD_FAILED`; SQLSTATE: `HY000`

Message: Some rules failed to load.

`ER_REWRITER_LOAD_FAILED` was added in 8.0.11.

- Error number: `MY-011278`; Symbol: `ER_REWRITER_READ_FAILED`; SQLSTATE: `HY000`

Message: Got error from storage engine while refreshing rewrite rules.

`ER_REWRITER_READ_FAILED` was added in 8.0.11.

- Error number: `MY-011279`; Symbol: `ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to initialize `Connection_event_coordinator`

`ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED` was added in 8.0.11.

- Error number: `MY-011280`; Symbol: `ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_UPDATE_FAILED`; SQLSTATE: `HY000`

Message: Failed to update connection delay triggered stats

`ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_UPDATE_FAILED` was added in 8.0.11.

- Error number: `MY-011281`; Symbol: `ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_RESET_FAILED`; SQLSTATE: `HY000`

Message: Failed to reset connection delay triggered stats

`ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_RESET_FAILED` was added in 8.0.11.

- Error number: `MY-011282`; Symbol: `ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE`; SQLSTATE: `HY000`

Message: Unexpected option type for connection delay.

`ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE` was added in 8.0.11.

- Error number: `MY-011283`; Symbol: `ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to initialize `Connection_delay_action`



---

`ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED` was added in 8.0.11.

- Error number: `MY-011284`; Symbol: `ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY`; SQLSTATE: `HY000`

Message: Could not set %s delay for connection delay.

`ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY` was added in 8.0.11.

- Error number: `MY-011285`; Symbol: `ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_HASH`; SQLSTATE: `HY000`

Message: Failed to update connection delay hash for account : %s

`ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_HASH` was added in 8.0.11.

- Error number: `MY-011286`; Symbol: `ER_XPLUGIN_FORCE_STOP_CLIENT`; SQLSTATE: `HY000`

Message: %s: Force stopping client because exception occurred: %s

`ER_XPLUGIN_FORCE_STOP_CLIENT` was added in 8.0.11.

- Error number: `MY-011287`; Symbol: `ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED`; SQLSTATE: `HY000`

Message: %s.%u: Maximum number of authentication attempts reached, login failed.

`ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED` was added in 8.0.11.

- Error number: `MY-011288`; Symbol: `ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED`; SQLSTATE: `HY000`

Message: Error allocating Buffer\_page: %s

`ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED` was added in 8.0.11.

- Error number: `MY-011289`; Symbol: `ER_XPLUGIN_DETECTED_HANGING_CLIENTS`; SQLSTATE: `HY000`

Message: Detected %u hanging client(s)

`ER_XPLUGIN_DETECTED_HANGING_CLIENTS` was added in 8.0.11.

- Error number: `MY-011290`; Symbol: `ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT`; SQLSTATE: `HY000`

Message: Error accepting client

`ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT` was added in 8.0.11.

- Error number: `MY-011291`; Symbol: `ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT`; SQLSTATE: `HY000`

Message: Internal error scheduling client for execution

`ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT` was added in 8.0.11.

- Error number: `MY-011292`; Symbol: `ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES`; SQLSTATE: `HY000`

---

Message: Preparation of I/O interfaces failed, X Protocol won't be accessible

[ER\\_XPLUGIN\\_FAILED\\_TO\\_PREPARE\\_IO\\_INTERFACES](#) was added in 8.0.11.

- Error number: [MY-011293](#); Symbol: [ER\\_XPLUGIN\\_SRV\\_SESSION\\_INIT\\_THREAD\\_FAILED](#); SQLSTATE: [HY000](#)

Message: `srv_session_init_thread` returned error

[ER\\_XPLUGIN\\_SRV\\_SESSION\\_INIT\\_THREAD\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011294](#); Symbol: [ER\\_XPLUGIN\\_UNABLE\\_TO\\_USE\\_USER\\_SESSION\\_ACCOUNT](#); SQLSTATE: [HY000](#)

Message: Unable to use user `mysql.session` account when connecting the server for internal plugin requests.

[ER\\_XPLUGIN\\_UNABLE\\_TO\\_USE\\_USER\\_SESSION\\_ACCOUNT](#) was added in 8.0.11.

- Error number: [MY-011295](#); Symbol: [ER\\_XPLUGIN\\_REFERENCE\\_TO\\_USER\\_ACCOUNT\\_DOC\\_SECTION](#); SQLSTATE: [HY000](#)

Message: For more information, please see the X Plugin User Account section in the MySQL documentation

[ER\\_XPLUGIN\\_REFERENCE\\_TO\\_USER\\_ACCOUNT\\_DOC\\_SECTION](#) was added in 8.0.11.

- Error number: [MY-011296](#); Symbol: [ER\\_XPLUGIN\\_UNEXPECTED\\_EXCEPTION\\_DISPATCHING\\_CMD](#); SQLSTATE: [HY000](#)

Message: `%s`: Unexpected exception dispatching command: `%s`

[ER\\_XPLUGIN\\_UNEXPECTED\\_EXCEPTION\\_DISPATCHING\\_CMD](#) was added in 8.0.11.

- Error number: [MY-011297](#); Symbol: [ER\\_XPLUGIN\\_EXCEPTION\\_IN\\_TASK\\_SCHEDULER](#); SQLSTATE: [HY000](#)

Message: Exception in post: `%s`

[ER\\_XPLUGIN\\_EXCEPTION\\_IN\\_TASK\\_SCHEDULER](#) was added in 8.0.11.

- Error number: [MY-011298](#); Symbol: [ER\\_XPLUGIN\\_TASK\\_SCHEDULING\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Internal error scheduling task

[ER\\_XPLUGIN\\_TASK\\_SCHEDULING\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011299](#); Symbol: [ER\\_XPLUGIN\\_EXCEPTION\\_IN\\_EVENT\\_LOOP](#); SQLSTATE: [HY000](#)

Message: Exception in event loop: "`%s`": `%s`

[ER\\_XPLUGIN\\_EXCEPTION\\_IN\\_EVENT\\_LOOP](#) was added in 8.0.11.

- Error number: [MY-011300](#); Symbol: [ER\\_XPLUGIN\\_LISTENER\\_SETUP\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Setup of `%s` failed, `%s`

[ER\\_XPLUGIN\\_LISTENER\\_SETUP\\_FAILED](#) was added in 8.0.11.

- 
- Error number: [MY-011301](#); Symbol: [ER\\_XPLUING\\_NET\\_STARTUP\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_XPLUING\\_NET\\_STARTUP\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011302](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_AT\\_SSL\\_CONF](#); SQLSTATE: [HY000](#)  
Message: Failed at SSL configuration: "%s"  
[ER\\_XPLUGIN\\_FAILED\\_AT\\_SSL\\_CONF](#) was added in 8.0.11.
  - Error number: [MY-011303](#); Symbol: [ER\\_XPLUGIN\\_CLIENT\\_SSL\\_HANDSHAKE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Error during SSL handshake for client connection (%i)  
[ER\\_XPLUGIN\\_CLIENT\\_SSL\\_HANDSHAKE\\_FAILED](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011304](#); Symbol: [ER\\_XPLUGIN\\_SSL\\_HANDSHAKE\\_WITH\\_SERVER\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: %s: Error during SSL handshake  
[ER\\_XPLUGIN\\_SSL\\_HANDSHAKE\\_WITH\\_SERVER\\_FAILED](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011305](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_CREATE\\_SESSION\\_FOR\\_CONN](#); SQLSTATE: [HY000](#)  
Message: %s: Error creating session for connection from %s  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_CREATE\\_SESSION\\_FOR\\_CONN](#) was added in 8.0.11.
  - Error number: [MY-011306](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_INITIALIZE\\_SESSION](#); SQLSTATE: [HY000](#)  
Message: %s: Error initializing session for connection: %s  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_INITIALIZE\\_SESSION](#) was added in 8.0.11.
  - Error number: [MY-011307](#); Symbol: [ER\\_XPLUGIN\\_MESSAGE\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
Message: %s: Message of size %u received, exceeding the limit of %i  
[ER\\_XPLUGIN\\_MESSAGE\\_TOO\\_LONG](#) was added in 8.0.11.
  - Error number: [MY-011308](#); Symbol: [ER\\_XPLUGIN\\_UNINITIALIZED\\_MESSAGE](#); SQLSTATE: [HY000](#)  
Message: Message is not properly initialized: %s  
[ER\\_XPLUGIN\\_UNINITIALIZED\\_MESSAGE](#) was added in 8.0.11.
  - Error number: [MY-011309](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_SET\\_MIN\\_NUMBER\\_OF\\_WORKERS](#); SQLSTATE: [HY000](#)  
Message: Unable to set minimal number of workers to %u; actual value is %i  
[ER\\_XPLUGIN\\_FAILED\\_TO\\_SET\\_MIN\\_NUMBER\\_OF\\_WORKERS](#) was added in 8.0.11.

- 
- Error number: `MY-011310`; Symbol: `ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION`; SQLSTATE: `HY000`  
  
Message: Unable to accept connection, disconnecting client  
  
`ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION` was added in 8.0.11.
  - Error number: `MY-011311`; Symbol: `ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED`; SQLSTATE: `HY000`  
  
Message: All I/O interfaces are disabled, X Protocol won't be accessible  
  
`ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED` was added in 8.0.11.
  - Error number: `MY-011312`; Symbol: `ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT`; SQLSTATE: `HY000`  
  
Message: %s: Invalid message %i received during client initialization  
  
`ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT` was added in 8.0.11, removed after 8.0.12.
  - Error number: `MY-011313`; Symbol: `ER_XPLUGIN_CLOSING_CLIENTS_ON_SHUTDOWN`; SQLSTATE: `HY000`  
  
Message: %s: closing client because of shutdown (state: %i)  
  
`ER_XPLUGIN_CLOSING_CLIENTS_ON_SHUTDOWN` was added in 8.0.11, removed after 8.0.12.
  - Error number: `MY-011314`; Symbol: `ER_XPLUGIN_ERROR_READING_SOCKET`; SQLSTATE: `HY000`  
  
Message: %s: Error reading from socket %s (%i)  
  
`ER_XPLUGIN_ERROR_READING_SOCKET` was added in 8.0.11.
  - Error number: `MY-011315`; Symbol: `ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_MSG_BODY`; SQLSTATE: `HY000`  
  
Message: %s: peer disconnected while reading message body  
  
`ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_MSG_BODY` was added in 8.0.11.
  - Error number: `MY-011316`; Symbol: `ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION`; SQLSTATE: `HY000`  
  
Message: client\_id:%s - %s while reading from socket, closing connection  
  
`ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION` was added in 8.0.11.
  - Error number: `MY-011317`; Symbol: `ER_XPLUGIN_INVALID_AUTH_METHOD`; SQLSTATE: `HY000`  
  
Message: %s.%u: Invalid authentication method %s  
  
`ER_XPLUGIN_INVALID_AUTH_METHOD` was added in 8.0.11, removed after 8.0.12.

- 
- Error number: [MY-011318](#); Symbol: [ER\\_XPLUGIN\\_UNEXPECTED\\_MSG\\_DURING\\_AUTHENTICATION](#); SQLSTATE: [HY000](#)  
Message: %s: Unexpected message of type %i received during authentication  
[ER\\_XPLUGIN\\_UNEXPECTED\\_MSG\\_DURING\\_AUTHENTICATION](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011319](#); Symbol: [ER\\_XPLUGIN\\_ERROR\\_WRITING\\_TO\\_CLIENT](#); SQLSTATE: [HY000](#)  
Message: Error writing to client: %s (%i)  
[ER\\_XPLUGIN\\_ERROR\\_WRITING\\_TO\\_CLIENT](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011320](#); Symbol: [ER\\_XPLUGIN\\_SCHEDULER\\_STARTED](#); SQLSTATE: [HY000](#)  
Message: Scheduler "%s" started.  
[ER\\_XPLUGIN\\_SCHEDULER\\_STARTED](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011321](#); Symbol: [ER\\_XPLUGIN\\_SCHEDULER\\_STOPPED](#); SQLSTATE: [HY000](#)  
Message: Scheduler "%s" stopped.  
[ER\\_XPLUGIN\\_SCHEDULER\\_STOPPED](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011322](#); Symbol: [ER\\_XPLUGIN\\_LISTENER\\_SYS\\_VARIABLE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Please see the MySQL documentation for '%s' system variables to fix the error  
[ER\\_XPLUGIN\\_LISTENER\\_SYS\\_VARIABLE\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011323](#); Symbol: [ER\\_XPLUGIN\\_LISTENER\\_STATUS\\_MSG](#); SQLSTATE: [HY000](#)  
Message: X Plugin ready for connections. %s  
[ER\\_XPLUGIN\\_LISTENER\\_STATUS\\_MSG](#) was added in 8.0.11.
  - Error number: [MY-011324](#); Symbol: [ER\\_XPLUGIN\\_RETRYING\\_BIND\\_ON\\_PORT](#); SQLSTATE: [HY000](#)  
Message: Retrying `bind()` on TCP/IP port %i  
[ER\\_XPLUGIN\\_RETRYING\\_BIND\\_ON\\_PORT](#) was added in 8.0.11.
  - Error number: [MY-011325](#); Symbol: [ER\\_XPLUGIN\\_SHUTDOWN\\_TRIGGERED](#); SQLSTATE: [HY000](#)  
Message: Shutdown triggered by mysqld abort flag  
[ER\\_XPLUGIN\\_SHUTDOWN\\_TRIGGERED](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011326](#); Symbol: [ER\\_XPLUGIN\\_USER\\_ACCOUNT\\_WITH\\_ALL\\_PERMISSIONS](#); SQLSTATE: [HY000](#)  
Message: Using %s account for authentication which has all required permissions  
[ER\\_XPLUGIN\\_USER\\_ACCOUNT\\_WITH\\_ALL\\_PERMISSIONS](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011327](#); Symbol: [ER\\_XPLUGIN\\_EXISTING\\_USER\\_ACCOUNT\\_WITH\\_INCOMPLETE\\_GRANTS](#); SQLSTATE: [HY000](#)
-

---

Message: Using existing %s account for authentication. Incomplete grants will be fixed

[ER\\_XPLUGIN\\_EXISTING\\_USER\\_ACCOUNT\\_WITH\\_INCOMPLETE\\_GRANTS](#) was added in 8.0.11.

- Error number: [MY-011328](#); Symbol: [ER\\_XPLUGIN\\_SERVER\\_STARTS\\_HANDLING\\_CONNECTIONS](#); SQLSTATE: [HY000](#)

Message: Server starts handling incoming connections

[ER\\_XPLUGIN\\_SERVER\\_STARTS\\_HANDLING\\_CONNECTIONS](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011329](#); Symbol: [ER\\_XPLUGIN\\_SERVER\\_STOPPED\\_HANDLING\\_CONNECTIONS](#); SQLSTATE: [HY000](#)

Message: Stopped handling incoming connections

[ER\\_XPLUGIN\\_SERVER\\_STOPPED\\_HANDLING\\_CONNECTIONS](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011330](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_INTERRUPT\\_SESSION](#); SQLSTATE: [HY000](#)

Message: %s: Could not interrupt client session

[ER\\_XPLUGIN\\_FAILED\\_TO\\_INTERRUPT\\_SESSION](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011331](#); Symbol: [ER\\_XPLUGIN\\_CLIENT\\_RELEASE\\_TRIGGERED](#); SQLSTATE: [HY000](#)

Message: %s: release triggered by timeout in state:%i

[ER\\_XPLUGIN\\_CLIENT\\_RELEASE\\_TRIGGERED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011332](#); Symbol: [ER\\_XPLUGIN\\_IPv6\\_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: IPv6 is available

[ER\\_XPLUGIN\\_IPv6\\_AVAILABLE](#) was added in 8.0.11.

- Error number: [MY-011333](#); Symbol: [ER\\_XPLUGIN\\_UNIX\\_SOCKET\\_NOT\\_CONFIGURED](#); SQLSTATE: [HY000](#)

Message: UNIX socket not configured

[ER\\_XPLUGIN\\_UNIX\\_SOCKET\\_NOT\\_CONFIGURED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011334](#); Symbol: [ER\\_XPLUGIN\\_CLIENT\\_KILL\\_MSG](#); SQLSTATE: [HY000](#)

Message: Kill client: %i %s

[ER\\_XPLUGIN\\_CLIENT\\_KILL\\_MSG](#) was added in 8.0.11.

- Error number: [MY-011335](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_GET\\_SECURITY\\_CTX](#); SQLSTATE: [HY000](#)

Message: Could not get security context for session

[ER\\_XPLUGIN\\_FAILED\\_TO\\_GET\\_SECURITY\\_CTX](#) was added in 8.0.11.

- 
- Error number: [MY-011336](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_SWITCH\\_SECURITY\\_CTX\\_TO\\_ROOT](#); SQLSTATE: [HY000](#)

Message: Unable to switch security context to root

[ER\\_XPLUGIN\\_FAILED\\_TO\\_SWITCH\\_SECURITY\\_CTX\\_TO\\_ROOT](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011337](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_CLOSE\\_SQL\\_SESSION](#); SQLSTATE: [HY000](#)

Message: Error closing SQL session

[ER\\_XPLUGIN\\_FAILED\\_TO\\_CLOSE\\_SQL\\_SESSION](#) was added in 8.0.11.

- Error number: [MY-011338](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_EXECUTE\\_ADMIN\\_CMD](#); SQLSTATE: [HY000](#)

Message: Error executing admin command %s: %s

[ER\\_XPLUGIN\\_FAILED\\_TO\\_EXECUTE\\_ADMIN\\_CMD](#) was added in 8.0.11.

- Error number: [MY-011339](#); Symbol: [ER\\_XPLUGIN\\_EMPTY\\_ADMIN\\_CMD](#); SQLSTATE: [HY000](#)

Message: Error executing empty admin command

[ER\\_XPLUGIN\\_EMPTY\\_ADMIN\\_CMD](#) was added in 8.0.11.

- Error number: [MY-011340](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_GET\\_SYS\\_VAR](#); SQLSTATE: [HY000](#)

Message: Unable to retrieve system variable '%s'

[ER\\_XPLUGIN\\_FAILED\\_TO\\_GET\\_SYS\\_VAR](#) was added in 8.0.11.

- Error number: [MY-011341](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_GET\\_CREATION\\_STMT](#); SQLSTATE: [HY000](#)

Message: Unable to get creation stmt for collection '%s'; query result size: %lu

[ER\\_XPLUGIN\\_FAILED\\_TO\\_GET\\_CREATION\\_STMT](#) was added in 8.0.11.

- Error number: [MY-011342](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_GET\\_ENGINE\\_INFO](#); SQLSTATE: [HY000](#)

Message: Unable to get engine info for collection '%s'; creation stmt: %s

[ER\\_XPLUGIN\\_FAILED\\_TO\\_GET\\_ENGINE\\_INFO](#) was added in 8.0.11.

- Error number: [MY-011343](#); Symbol: [ER\\_XPLUGIN\\_FAIL\\_TO\\_GET\\_RESULT\\_DATA](#); SQLSTATE: [HY000](#)

Message: Error getting result data: %s

[ER\\_XPLUGIN\\_FAIL\\_TO\\_GET\\_RESULT\\_DATA](#) was added in 8.0.11, removed after 8.0.12.

- 
- Error number: `MY-011344`; Symbol: `ER_XPLUGIN_CAPABILITY_EXPIRED_PASSWORD`; SQLSTATE: `HY000`  
Message: Capability expired password failed with error: %s  
`ER_XPLUGIN_CAPABILITY_EXPIRED_PASSWORD` was added in 8.0.11, removed after 8.0.12.
  - Error number: `MY-011345`; Symbol: `ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG`; SQLSTATE: `HY000`  
Message: Failed to set `SO_REUSEADDR` flag (error: %d).  
`ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG` was added in 8.0.11.
  - Error number: `MY-011346`; Symbol: `ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION`; SQLSTATE: `HY000`  
Message: Could not open internal MySQL session  
`ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION` was added in 8.0.11.
  - Error number: `MY-011347`; Symbol: `ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT`; SQLSTATE: `HY000`  
Message: Unable to switch context to user %s  
`ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT` was added in 8.0.11.
  - Error number: `MY-011348`; Symbol: `ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF`; SQLSTATE: `HY000`  
Message: Can't unregister '%s' user defined function  
`ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF` was added in 8.0.11.
  - Error number: `MY-011349`; Symbol: `ER_XPLUGIN_GET_PEER_ADDRESS_FAILED`; SQLSTATE: `HY000`  
Message: %s: get peer address failed, can't resolve IP to hostname  
`ER_XPLUGIN_GET_PEER_ADDRESS_FAILED` was added in 8.0.11, removed after 8.0.12.
  - Error number: `MY-011350`; Symbol: `ER_XPLUGIN_CAPABILITY_CLIENT_INTERACTIVE_FAILED`; SQLSTATE: `HY000`  
Message: Capability client interactive failed with error: %s  
`ER_XPLUGIN_CAPABILITY_CLIENT_INTERACTIVE_FAILED` was added in 8.0.11, removed after 8.0.12.
  - Error number: `MY-011351`; Symbol: `ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG`; SQLSTATE: `HY000`  
Message: Failed to reset `IPV6_V6ONLY` flag (error: %d). The server will listen to IPv6 addresses only.  
`ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG` was added in 8.0.11.
  - Error number: `MY-011352`; Symbol: `ER_KEYRING_INVALID_KEY_TYPE`; SQLSTATE: `HY000`  
Message: Invalid key type



---

[ER\\_KEYRING\\_INVALID\\_KEY\\_TYPE](#) was added in 8.0.11.

- Error number: [MY-011353](#); Symbol: [ER\\_KEYRING\\_INVALID\\_KEY\\_LENGTH](#); SQLSTATE: [HY000](#)

Message: Invalid key length for given block cipher

[ER\\_KEYRING\\_INVALID\\_KEY\\_LENGTH](#) was added in 8.0.11.

- Error number: [MY-011354](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_CREATE\\_KEYRING\\_DIR](#); SQLSTATE: [HY000](#)

Message: Could not create keyring directory. The keyring\_file will stay unusable until correct path to the keyring directory gets provided

[ER\\_KEYRING\\_FAILED\\_TO\\_CREATE\\_KEYRING\\_DIR](#) was added in 8.0.11.

- Error number: [MY-011355](#); Symbol: [ER\\_KEYRING\\_FILE\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: keyring\_file initialization failure. Please check if the keyring\_file\_data points to readable keyring file or keyring file can be created in the specified location. The keyring\_file will stay unusable until correct path to the keyring file gets provided

[ER\\_KEYRING\\_FILE\\_INIT\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011356](#); Symbol: [ER\\_KEYRING\\_INTERNAL\\_EXCEPTION\\_FAILED\\_FILE\\_INIT](#); SQLSTATE: [HY000](#)

Message: keyring\_file initialization failure due to internal exception inside the plugin.

[ER\\_KEYRING\\_INTERNAL\\_EXCEPTION\\_FAILED\\_FILE\\_INIT](#) was added in 8.0.11.

- Error number: [MY-011357](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_GENERATE\\_KEY](#); SQLSTATE: [HY000](#)

Message: Failed to generate a key due to internal exception inside keyring\_file plugin

[ER\\_KEYRING\\_FAILED\\_TO\\_GENERATE\\_KEY](#) was added in 8.0.11.

- Error number: [MY-011358](#); Symbol: [ER\\_KEYRING\\_CHECK\\_KEY\\_FAILED\\_DUE\\_TO\\_INVALID\\_KEY](#); SQLSTATE: [HY000](#)

Message: Error while %s key: invalid key\_type

[ER\\_KEYRING\\_CHECK\\_KEY\\_FAILED\\_DUE\\_TO\\_INVALID\\_KEY](#) was added in 8.0.11.

- Error number: [MY-011359](#); Symbol: [ER\\_KEYRING\\_CHECK\\_KEY\\_FAILED\\_DUE\\_TO\\_EMPTY\\_KEY\\_ID](#); SQLSTATE: [HY000](#)

Message: Error while %s key: key\_id cannot be empty

[ER\\_KEYRING\\_CHECK\\_KEY\\_FAILED\\_DUE\\_TO\\_EMPTY\\_KEY\\_ID](#) was added in 8.0.11.

- Error number: [MY-011360](#); Symbol: [ER\\_KEYRING\\_OPERATION\\_FAILED\\_DUE\\_TO\\_INTERNAL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to %s due to internal exception inside %s plugin

[ER\\_KEYRING\\_OPERATION\\_FAILED\\_DUE\\_TO\\_INTERNAL\\_ERROR](#) was added in 8.0.11.

- 
- Error number: `MY-011361`; Symbol: `ER_KEYRING_INCORRECT_FILE`; SQLSTATE: `HY000`  
Message: Incorrect Keyring file  
`ER_KEYRING_INCORRECT_FILE` was added in 8.0.11.
  - Error number: `MY-011362`; Symbol: `ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE`; SQLSTATE: `HY000`  
Message: Found malformed keyring backup file - removing it  
`ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE` was added in 8.0.11.
  - Error number: `MY-011363`; Symbol: `ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE`; SQLSTATE: `HY000`  
Message: Error while restoring keyring from backup file cannot overwrite keyring with backup  
`ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE` was added in 8.0.11.
  - Error number: `MY-011364`; Symbol: `ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE`; SQLSTATE: `HY000`  
Message: Error while flushing in-memory keyring into keyring file  
`ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE` was added in 8.0.11.
  - Error number: `MY-011365`; Symbol: `ER_KEYRING_FAILED_TO_GET_FILE_STAT`; SQLSTATE: `HY000`  
Message: Error while reading stat for %s. Please check if file %s was not removed. OS returned this error: %s  
`ER_KEYRING_FAILED_TO_GET_FILE_STAT` was added in 8.0.11.
  - Error number: `MY-011366`; Symbol: `ER_KEYRING_FAILED_TO_REMOVE_FILE`; SQLSTATE: `HY000`  
Message: Could not remove file %s OS returned this error: %s  
`ER_KEYRING_FAILED_TO_REMOVE_FILE` was added in 8.0.11.
  - Error number: `MY-011367`; Symbol: `ER_KEYRING_FAILED_TO_TRUNCATE_FILE`; SQLSTATE: `HY000`  
Message: Could not truncate file %s. OS returned this error: %s  
`ER_KEYRING_FAILED_TO_TRUNCATE_FILE` was added in 8.0.11.
  - Error number: `MY-011368`; Symbol: `ER_KEYRING_UNKNOWN_ERROR`; SQLSTATE: `HY000`  
Message: Unknown error %d  
`ER_KEYRING_UNKNOWN_ERROR` was added in 8.0.11.
  - Error number: `MY-011369`; Symbol: `ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA`; SQLSTATE: `HY000`  
Message: keyring\_file\_data cannot be set to new value as the keyring file cannot be created/accessed in the provided path  
`ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA` was added in 8.0.11.

- 
- Error number: `MY-011370`; Symbol: `ER_KEYRING_FILE_IO_ERROR`; SQLSTATE: `HY000`  
Message: %s  
`ER_KEYRING_FILE_IO_ERROR` was added in 8.0.11.
  - Error number: `MY-011371`; Symbol: `ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT`; SQLSTATE: `HY000`  
Message: Error while loading keyring content. The keyring might be malformed  
`ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT` was added in 8.0.11.
  - Error number: `MY-011372`; Symbol: `ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING`; SQLSTATE: `HY000`  
Message: Could not flush keys to keyring  
`ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING` was added in 8.0.11.
  - Error number: `MY-011373`; Symbol: `ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP`; SQLSTATE: `HY000`  
Message: Could not flush keys to keyring's backup  
`ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP` was added in 8.0.11.
  - Error number: `MY-011374`; Symbol: `ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEY_ID`; SQLSTATE: `HY000`  
Message: Error while fetching key: key\_id cannot be empty  
`ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEY_ID` was added in 8.0.11.
  - Error number: `MY-011375`; Symbol: `ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_ID`; SQLSTATE: `HY000`  
Message: Error while removing key: key\_id cannot be empty  
`ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_ID` was added in 8.0.11.
  - Error number: `MY-011376`; Symbol: `ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURED`; SQLSTATE: `HY000`  
Message: For keyring\_okv to be initialized, please point keyring\_okv\_conf\_dir variable to a directory with Oracle Key Vault configuration file and ssl materials  
`ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURED` was added in 8.0.11.
  - Error number: `MY-011377`; Symbol: `ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONF`; SQLSTATE: `HY000`  
Message: keyring\_okv initialization failure. Please check that the keyring\_okv\_conf\_dir points to a readable directory and that the directory contains Oracle Key Vault configuration file and ssl materials. Please also check that Oracle Key Vault is up and running.  
`ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONF` was added in 8.0.11.
-

- 
- Error number: MY-011378; Symbol: ER\_KEYRING\_OKV\_INIT\_FAILED\_DUE\_TO\_INTERNAL\_ERROR; SQLSTATE: HY000  
Message: keyring\_okv initialization failure due to internal exception inside the plugin  
ER\_KEYRING\_OKV\_INIT\_FAILED\_DUE\_TO\_INTERNAL\_ERROR was added in 8.0.11.
  - Error number: MY-011379; Symbol: ER\_KEYRING\_OKV\_INVALID\_KEY\_TYPE; SQLSTATE: HY000  
Message: Invalid key type  
ER\_KEYRING\_OKV\_INVALID\_KEY\_TYPE was added in 8.0.11.
  - Error number: MY-011380; Symbol: ER\_KEYRING\_OKV\_INVALID\_KEY\_LENGTH\_FOR\_CIPHER; SQLSTATE: HY000  
Message: Invalid key length for given block cipher  
ER\_KEYRING\_OKV\_INVALID\_KEY\_LENGTH\_FOR\_CIPHER was added in 8.0.11.
  - Error number: MY-011381; Symbol: ER\_KEYRING\_OKV\_FAILED\_TO\_GENERATE\_KEY\_DUE\_TO\_INTERNAL\_ERROR; SQLSTATE: HY000  
Message: Failed to generate a key due to internal exception inside keyring\_okv plugin  
ER\_KEYRING\_OKV\_FAILED\_TO\_GENERATE\_KEY\_DUE\_TO\_INTERNAL\_ERROR was added in 8.0.11.
  - Error number: MY-011382; Symbol: ER\_KEYRING\_OKV\_FAILED\_TO\_FIND\_SERVER\_ENTRY; SQLSTATE: HY000  
Message: Could not find entry for server in configuration file %s  
ER\_KEYRING\_OKV\_FAILED\_TO\_FIND\_SERVER\_ENTRY was added in 8.0.11.
  - Error number: MY-011383; Symbol: ER\_KEYRING\_OKV\_FAILED\_TO\_FIND\_STANDBY\_SERVER\_ENTRY; SQLSTATE: HY000  
Message: Could not find entry for standby server in configuration file %s  
ER\_KEYRING\_OKV\_FAILED\_TO\_FIND\_STANDBY\_SERVER\_ENTRY was added in 8.0.11.
  - Error number: MY-011384; Symbol: ER\_KEYRING\_OKV\_FAILED\_TO\_PARSE\_CONF\_FILE; SQLSTATE: HY000  
Message: Could not parse the %s file provided  
ER\_KEYRING\_OKV\_FAILED\_TO\_PARSE\_CONF\_FILE was added in 8.0.11.
  - Error number: MY-011385; Symbol: ER\_KEYRING\_OKV\_FAILED\_TO\_LOAD\_KEY\_UID; SQLSTATE: HY000  
Message: Could not load keys' uids from the OKV server  
ER\_KEYRING\_OKV\_FAILED\_TO\_LOAD\_KEY\_UID was added in 8.0.11.
  - Error number: MY-011386; Symbol: ER\_KEYRING\_OKV\_FAILED\_TO\_INIT\_SSL\_LAYER; SQLSTATE: HY000  
Message: Could not initialize ssl layer

---

`ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER` was added in 8.0.11.

- Error number: `MY-011387`; Symbol: `ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT`; SQLSTATE: `HY000`

Message: Could not initialize OKV client

`ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT` was added in 8.0.11.

- Error number: `MY-011388`; Symbol: `ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED`; SQLSTATE: `HY000`

Message: Could not connect to the OKV server

`ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED` was added in 8.0.11.

- Error number: `MY-011389`; Symbol: `ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY`; SQLSTATE: `HY000`

Message: Could not remove the key

`ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY` was added in 8.0.11.

- Error number: `MY-011390`; Symbol: `ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE`; SQLSTATE: `HY000`

Message: Could not add attribute, attribute\_name=%s attribute value=%s

`ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE` was added in 8.0.11.

- Error number: `MY-011391`; Symbol: `ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY`; SQLSTATE: `HY000`

Message: Could not generate the key.

`ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY` was added in 8.0.11.

- Error number: `MY-011392`; Symbol: `ER_KEYRING_OKV_FAILED_TO_STORE_KEY`; SQLSTATE: `HY000`

Message: Could not store the key.

`ER_KEYRING_OKV_FAILED_TO_STORE_KEY` was added in 8.0.11.

- Error number: `MY-011393`; Symbol: `ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS`; SQLSTATE: `HY000`

Message: Could not activate the key.

`ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS` was added in 8.0.11.

- Error number: `MY-011394`; Symbol: `ER_KEYRING_OKV_FAILED_TO_FETCH_KEY`; SQLSTATE: `HY000`

Message: Could not fetch generated key

`ER_KEYRING_OKV_FAILED_TO_FETCH_KEY` was added in 8.0.11.

- Error number: `MY-011395`; Symbol: `ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY`; SQLSTATE: `HY000`

---

Message: Could not store/generate the key - failed to set key attribute x-key-ready

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_STORE\\_OR\\_GENERATE\\_KEY](#) was added in 8.0.11.

- Error number: MY-011396; Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_RETRIEVE\\_KEY\\_SIGNATURE](#); SQLSTATE: HY000

Message: Could not retrieve key signature from custom attributes

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_RETRIEVE\\_KEY\\_SIGNATURE](#) was added in 8.0.11.

- Error number: MY-011397; Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_RETRIEVE\\_KEY](#); SQLSTATE: HY000

Message: Could not retrieve key from OKV

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_RETRIEVE\\_KEY](#) was added in 8.0.11.

- Error number: MY-011398; Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_LOAD\\_SSL\\_TRUST\\_STORE](#); SQLSTATE: HY000

Message: Error loading trust store

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_LOAD\\_SSL\\_TRUST\\_STORE](#) was added in 8.0.11.

- Error number: MY-011399; Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_SET\\_CERTIFICATE\\_FILE](#); SQLSTATE: HY000

Message: Error setting the certificate file.

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_SET\\_CERTIFICATE\\_FILE](#) was added in 8.0.11.

- Error number: MY-011400; Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_SET\\_KEY\\_FILE](#); SQLSTATE: HY000

Message: Error setting the key file.

[ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_SET\\_KEY\\_FILE](#) was added in 8.0.11.

- Error number: MY-011401; Symbol: [ER\\_KEYRING\\_OKV\\_KEY\\_MISMATCH](#); SQLSTATE: HY000

Message: Private key does not match the certificate public key

[ER\\_KEYRING\\_OKV\\_KEY\\_MISMATCH](#) was added in 8.0.11.

- Error number: MY-011402; Symbol: [ER\\_KEYRING\\_ENCRYPTED\\_FILE\\_INCORRECT\\_KEYRING\\_FILE](#); SQLSTATE: HY000

Message: Incorrect Keyring file

[ER\\_KEYRING\\_ENCRYPTED\\_FILE\\_INCORRECT\\_KEYRING\\_FILE](#) was added in 8.0.11.

- 
- Error number: `MY-011403`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILED`; SQLSTATE: `HY000`  
Message: Keyring\_encrypted\_file decryption failed. Please verify --keyring-encrypted-file-password option value.  
`ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILED` was added in 8.0.11.
  - Error number: `MY-011404`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP_FILE`; SQLSTATE: `HY000`  
Message: Found malformed keyring backup file - removing it  
`ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP_FILE` was added in 8.0.11.
  - Error number: `MY-011405`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING`; SQLSTATE: `HY000`  
Message: Error while restoring keyring from backup file cannot overwrite keyring with backup  
`ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING` was added in 8.0.11.
  - Error number: `MY-011406`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING`; SQLSTATE: `HY000`  
Message: Error while flushing in-memory keyring into keyring file  
`ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING` was added in 8.0.11.
  - Error number: `MY-011407`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED`; SQLSTATE: `HY000`  
Message: Keyring\_encrypted\_file encryption failed. Please verify --keyring-encrypted-file-password option value.  
`ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED` was added in 8.0.11.
  - Error number: `MY-011408`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR`; SQLSTATE: `HY000`  
Message: keyring\_encrypted\_file\_data cannot be set to new value as the keyring file cannot be created/ accessed in the provided path  
`ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR` was added in 8.0.11.
  - Error number: `MY-011409`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEYRING_DIR`; SQLSTATE: `HY000`  
Message: Could not create keyring directory The keyring\_encrypted\_file will stay unusable until correct path to the keyring directory gets provided  
`ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEYRING_DIR` was added in 8.0.11.
  - Error number: `MY-011410`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID`; SQLSTATE: `HY000`  
Message: The keyring\_encrypted\_file\_password must be set to a valid value.  
`ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID` was added in 8.0.11.
-

- 
- Error number: `MY-011411`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG`; SQLSTATE: `HY000`

Message: Too long keyring\_encrypted\_file\_password value.

`ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG` was added in 8.0.11.

- Error number: `MY-011412`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE`; SQLSTATE: `HY000`

Message: keyring\_encrypted\_file initialization failure. Please check if the keyring\_encrypted\_file\_data points to readable keyring file or keyring file can be created in the specified location or password to decrypt keyring file is correct.

`ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE` was added in 8.0.11.

- Error number: `MY-011413`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: keyring\_encrypted\_file initialization failure due to internal exception inside the plugin

`ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INTERNAL_ERROR` was added in 8.0.11.

- Error number: `MY-011414`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: Failed to generate a key due to internal exception inside keyring\_encrypted\_file plugin

`ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_INTERNAL_ERROR` was added in 8.0.11.

- Error number: `MY-011415`; Symbol: `ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID`; SQLSTATE: `HY000`

Message: keyring\_aws\_cmk\_id cannot be set to the new value as AWS KMS seems to not understand the id provided. Please check that CMK id provided is correct.

`ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID` was added in 8.0.11.

- Error number: `MY-011416`; Symbol: `ER_KEYRING_AWS_FAILED_TO_SET_REGION`; SQLSTATE: `HY000`

Message: keyring\_aws\_region cannot be set to the new value as AWS KMS seems to not understand the region provided. Please check that region provided is correct.

`ER_KEYRING_AWS_FAILED_TO_SET_REGION` was added in 8.0.11.

- Error number: `MY-011417`; Symbol: `ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not open keyring\_aws configuration file: %s. OS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE` was added in 8.0.11.



- 
- Error number: `MY-011418`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF_FILE`; SQLSTATE: `HY000`  
Message: Could not read AWS access key id from keyring\_aws configuration file: %s. OS returned this error: %s  
`ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF_FILE` was added in 8.0.11.
  - Error number: `MY-011419`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF_FILE`; SQLSTATE: `HY000`  
Message: Could not read AWS access key from keyring\_aws configuration file: %s. OS returned this error: %s  
`ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF_FILE` was added in 8.0.11.
  - Error number: `MY-011420`; Symbol: `ER_KEYRING_AWS_INVALID_CONF_FILE_PATH`; SQLSTATE: `HY000`  
Message: Path to keyring aws configuration file cannot be empty  
`ER_KEYRING_AWS_INVALID_CONF_FILE_PATH` was added in 8.0.11.
  - Error number: `MY-011421`; Symbol: `ER_KEYRING_AWS_INVALID_DATA_FILE_PATH`; SQLSTATE: `HY000`  
Message: Path to keyring\_aws storage file cannot be empty.  
`ER_KEYRING_AWS_INVALID_DATA_FILE_PATH` was added in 8.0.11.
  - Error number: `MY-011422`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DIR`; SQLSTATE: `HY000`  
Message: Unable to create/access keyring directory.  
`ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DIR` was added in 8.0.11.
  - Error number: `MY-011423`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DATA_FILE`; SQLSTATE: `HY000`  
Message: Unable to create/access keyring\_aws storage file. Please check if keyring\_aws\_data\_file points to location where keyring file can be created/accessed. Please also make sure that MySQL server's user has high enough privileges to access this location.  
`ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DATA_FILE` was added in 8.0.11.
  - Error number: `MY-011424`; Symbol: `ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`  
Message: keyring\_aws initialization failed due to internal error when initializing synchronization primitive - %s. OS returned this error: %s:  
`ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR` was added in 8.0.11.
-

- 
- Error number: `MY-011425`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE`; SQLSTATE: `HY000`

Message: Could not access keyring\_aws storage file in the path provided. Please check if the keyring\_aws directory can be accessed by MySQL Server

`ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE` was added in 8.0.11.

- Error number: `MY-011426`; Symbol: `ER_KEYRING_AWS_CMK_ID_NOT_SET`; SQLSTATE: `HY000`

Message: keyring\_aws\_cmk\_id has to be set

`ER_KEYRING_AWS_CMK_ID_NOT_SET` was added in 8.0.11.

- Error number: `MY-011427`; Symbol: `ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL_FROM_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not get AWS KMS credentials from the configuration file

`ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL_FROM_CONF_FILE` was added in 8.0.11.

- Error number: `MY-011428`; Symbol: `ER_KEYRING_AWS_INIT_FAILURE`; SQLSTATE: `HY000`

Message: keyring\_aws initialization failure.

`ER_KEYRING_AWS_INIT_FAILURE` was added in 8.0.11.

- Error number: `MY-011429`; Symbol: `ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: keyring\_aws initialization failure due to internal exception inside the plugin

`ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTERNAL_ERROR` was added in 8.0.11.

- Error number: `MY-011430`; Symbol: `ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER`; SQLSTATE: `HY000`

Message: Invalid key length for given block cipher

`ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER` was added in 8.0.11.

- Error number: `MY-011431`; Symbol: `ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: Failed to generate a key due to internal exception inside keyring\_file plugin

`ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR` was added in 8.0.11.

- Error number: `MY-011432`; Symbol: `ER_KEYRING_AWS_INCORRECT_FILE`; SQLSTATE: `HY000`

Message: Incorrect Keyring file

`ER_KEYRING_AWS_INCORRECT_FILE` was added in 8.0.11.

- 
- Error number: `MY-011433`; Symbol: `ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE`; SQLSTATE: `HY000`  
Message: Found malformed keyring backup file - removing it  
`ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE` was added in 8.0.11.
  - Error number: `MY-011434`; Symbol: `ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE`; SQLSTATE: `HY000`  
Message: Error while restoring keyring from backup file cannot overwrite keyring with backup  
`ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE` was added in 8.0.11.
  - Error number: `MY-011435`; Symbol: `ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE`; SQLSTATE: `HY000`  
Message: Error while flushing in-memory keyring into keyring file  
`ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE` was added in 8.0.11.
  - Error number: `MY-011436`; Symbol: `ER_KEYRING_AWS_INCORRECT_REGION`; SQLSTATE: `HY000`  
Message: Wrong region  
`ER_KEYRING_AWS_INCORRECT_REGION` was added in 8.0.11.
  - Error number: `MY-011437`; Symbol: `ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS`; SQLSTATE: `HY000`  
Message: Could not connect to AWS KMS with the credentials provided. Please make sure they are correct. AWS KMS returned this error: %s  
`ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS` was added in 8.0.11.
  - Error number: `MY-011438`; Symbol: `ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY`; SQLSTATE: `HY000`  
Message: Could not generate a new key. AWS KMS returned this error: %s  
`ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY` was added in 8.0.11.
  - Error number: `MY-011439`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY`; SQLSTATE: `HY000`  
Message: Could not encrypt key. AWS KMS returned this error: %s  
`ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY` was added in 8.0.11.
  - Error number: `MY-011440`; Symbol: `ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY`; SQLSTATE: `HY000`  
Message: Could not re-encrypt key. AWS KMS returned this error: %s  
`ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY` was added in 8.0.11.
  - Error number: `MY-011441`; Symbol: `ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY`; SQLSTATE: `HY000`
-

---

Message: Could not decrypt key. AWS KMS returned this error: %s

[ER\\_KEYRING\\_AWS\\_FAILED\\_TO\\_DECRYPT\\_KEY](#) was added in 8.0.11.

- Error number: MY-011442; Symbol: [ER\\_KEYRING\\_AWS\\_FAILED\\_TO\\_ROTATE\\_CMK](#); SQLSTATE: HY000

Message: Could not rotate the CMK. AWS KMS returned this error: %s

[ER\\_KEYRING\\_AWS\\_FAILED\\_TO\\_ROTATE\\_CMK](#) was added in 8.0.11.

- Error number: MY-011443; Symbol: [ER\\_GRP\\_RPL\\_GTID\\_ALREADY\\_USED](#); SQLSTATE: HY000

Message: The requested GTID '%s:%lld' was already used, the transaction will rollback.

[ER\\_GRP\\_RPL\\_GTID\\_ALREADY\\_USED](#) was added in 8.0.11.

- Error number: MY-011444; Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_KILLED](#); SQLSTATE: HY000

Message: The group replication applier thread was killed.

[ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_KILLED](#) was added in 8.0.11.

- Error number: MY-011445; Symbol: [ER\\_GRP\\_RPL\\_EVENT\\_HANDLING\\_ERROR](#); SQLSTATE: HY000

Message: Error at event handling! Got error: %d.

[ER\\_GRP\\_RPL\\_EVENT\\_HANDLING\\_ERROR](#) was added in 8.0.11.

- Error number: MY-011446; Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_GTID\\_EXECUTION\\_INFO](#); SQLSTATE: HY000

Message: Error when extracting group GTID execution information, some recovery operations may face future issues.

[ER\\_GRP\\_RPL\\_ERROR\\_GTID\\_EXECUTION\\_INFO](#) was added in 8.0.11.

- Error number: MY-011447; Symbol: [ER\\_GRP\\_RPL\\_CERTIFICATE\\_SIZE\\_ERROR](#); SQLSTATE: HY000

Message: An error occurred when trying to reduce the Certification information size for transmission.

[ER\\_GRP\\_RPL\\_CERTIFICATE\\_SIZE\\_ERROR](#) was added in 8.0.11.

- Error number: MY-011448; Symbol: [ER\\_GRP\\_RPL\\_CREATE\\_APPLIER\\_CACHE\\_ERROR](#); SQLSTATE: HY000

Message: Failed to create group replication pipeline applier cache!

[ER\\_GRP\\_RPL\\_CREATE\\_APPLIER\\_CACHE\\_ERROR](#) was added in 8.0.11.

- Error number: MY-011449; Symbol: [ER\\_GRP\\_RPL\\_UNBLOCK\\_WAITING\\_THD](#); SQLSTATE: HY000

Message: Unblocking the group replication thread waiting for applier to start, as the start group replication was killed.

[ER\\_GRP\\_RPL\\_UNBLOCK\\_WAITING\\_THD](#) was added in 8.0.11.

- Error number: MY-011450; Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_PIPELINE\\_NOT\\_DISPOSED](#); SQLSTATE: HY000

---

Message: The group replication applier pipeline was not properly disposed. Check the error log for further info.

[ER\\_GRP\\_RPL\\_APPLIER\\_PIPELINE\\_NOT\\_DISPOSED](#) was added in 8.0.11.

- Error number: [MY-011451](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_EXECUTION\\_ABORTED](#); SQLSTATE: [HY000](#)

Message: The applier thread execution was aborted. Unable to process more transactions, this member will now leave the group.

[ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_EXECUTION\\_ABORTED](#) was added in 8.0.11.

- Error number: [MY-011452](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_EXECUTION\\_FATAL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error during execution on the Applier process of Group Replication. The server will now leave the group.

[ER\\_GRP\\_RPL\\_APPLIER\\_EXECUTION\\_FATAL\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011453](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_STOPPING\\_CHANNELS](#); SQLSTATE: [HY000](#)

Message: Error stopping all replication channels while server was leaving the group. %s

[ER\\_GRP\\_RPL\\_ERROR\\_STOPPING\\_CHANNELS](#) was added in 8.0.11.

- Error number: [MY-011454](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_SENDING\\_SINGLE\\_PRIMARY\\_MSSG](#); SQLSTATE: [HY000](#)

Message: Error sending single primary message informing that primary did apply relay logs.

[ER\\_GRP\\_RPL\\_ERROR\\_SENDING\\_SINGLE\\_PRIMARY\\_MSSG](#) was added in 8.0.11.

- Error number: [MY-011455](#); Symbol: [ER\\_GRP\\_RPL\\_UPDATE\\_TRANS\\_SNAPSHOT\\_VER\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating transaction snapshot version after transaction being positively certified.

[ER\\_GRP\\_RPL\\_UPDATE\\_TRANS\\_SNAPSHOT\\_VER\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011456](#); Symbol: [ER\\_GRP\\_RPL\\_SIDNO\\_FETCH\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error fetching transaction sidno after transaction being positively certified.

[ER\\_GRP\\_RPL\\_SIDNO\\_FETCH\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011457](#); Symbol: [ER\\_GRP\\_RPL\\_BROADCAST\\_COMMIT\\_TRANS\\_MSSG\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Broadcast of committed transactions message failed.

[ER\\_GRP\\_RPL\\_BROADCAST\\_COMMIT\\_TRANS\\_MSSG\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011458](#); Symbol: [ER\\_GRP\\_RPL\\_GROUP\\_NAME\\_PARSE\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Unable to parse the `group_replication_group_name` during the Certification module initialization.

---

`ER_GRP_RPL_GROUP_NAME_PARSE_ERROR` was added in 8.0.11.

- Error number: `MY-011459`; Symbol: `ER_GRP_RPL_ADD_GRPSID_TO_GRPGTIDSID_MAP_ERROR`; SQLSTATE: `HY000`

Message: Unable to add the `group_sid` in the `group_gtid_sid_map` during the Certification module initialization.

`ER_GRP_RPL_ADD_GRPSID_TO_GRPGTIDSID_MAP_ERROR` was added in 8.0.11.

- Error number: `MY-011460`; Symbol: `ER_GRP_RPL_UPDATE_GRPGTID_EXECUTED_ERROR`; SQLSTATE: `HY000`

Message: Error updating `group_gtid_executed` GTID set during the Certification module initialization.

`ER_GRP_RPL_UPDATE_GRPGTID_EXECUTED_ERROR` was added in 8.0.11.

- Error number: `MY-011461`; Symbol: `ER_GRP_RPL_DONOR_TRANS_INFO_ERROR`; SQLSTATE: `HY000`

Message: Unable to handle the donor's transaction information when initializing the conflict detection component. Possible out of memory error.

`ER_GRP_RPL_DONOR_TRANS_INFO_ERROR` was added in 8.0.11.

- Error number: `MY-011462`; Symbol: `ER_GRP_RPL_SERVER_CONN_ERROR`; SQLSTATE: `HY000`

Message: Error when establishing a server connection during the Certification module initialization.

`ER_GRP_RPL_SERVER_CONN_ERROR` was added in 8.0.11.

- Error number: `MY-011463`; Symbol: `ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET`; SQLSTATE: `HY000`

Message: Error when extracting this member GTID executed set. Certification module can't be properly initialized.

`ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET` was added in 8.0.11.

- Error number: `MY-011464`; Symbol: `ER_GRP_RPL_ADD_GTID_TO_GRPGTID_EXECUTED_ERROR`; SQLSTATE: `HY000`

Message: Error while adding the server GTID EXECUTED set to the `group_gtid_execute` during the Certification module initialization.

`ER_GRP_RPL_ADD_GTID_TO_GRPGTID_EXECUTED_ERROR` was added in 8.0.11.

- Error number: `MY-011465`; Symbol: `ER_GRP_RPL_ERROR_FETCHING_GTID_SET`; SQLSTATE: `HY000`

Message: Error when extracting this member retrieved set for its applier. Certification module can't be properly initialized.

`ER_GRP_RPL_ERROR_FETCHING_GTID_SET` was added in 8.0.11.

- Error number: `MY-011466`; Symbol: `ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTED_ERROR`; SQLSTATE: `HY000`

Message: Error while adding the member retrieved set to the `group_gtid_executed` during the Certification module initialization.

---

[ER\\_GRP\\_RPL\\_ADD\\_RETRIEVED\\_SET\\_TO\\_GRP\\_GTID\\_EXECUTED\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011467](#); Symbol: [ER\\_GRP\\_RPL\\_CERTIFICATION\\_INITIALIZATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error during Certification module initialization.

[ER\\_GRP\\_RPL\\_CERTIFICATION\\_INITIALIZATION\\_FAILURE](#) was added in 8.0.11.

- Error number: [MY-011468](#); Symbol: [ER\\_GRP\\_RPL\\_UPDATE\\_LAST\\_CONFLICT\\_FREE\\_TRANS\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Unable to update last conflict free transaction, this transaction will not be tracked on `performance_schema.replication_group_member_stats.last_conflict_free_transaction`.

[ER\\_GRP\\_RPL\\_UPDATE\\_LAST\\_CONFLICT\\_FREE\\_TRANS\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011469](#); Symbol: [ER\\_GRP\\_RPL\\_UPDATE\\_TRANS\\_SNAPSHOT\\_REF\\_VER\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating transaction snapshot version reference for internal storage.

[ER\\_GRP\\_RPL\\_UPDATE\\_TRANS\\_SNAPSHOT\\_REF\\_VER\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011470](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_TRANS\\_SIDNO\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error fetching transaction sidno while adding to the `group_gtid_executed` set.

[ER\\_GRP\\_RPL\\_FETCH\\_TRANS\\_SIDNO\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011471](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_VERIFYING\\_SIDNO](#); SQLSTATE: [HY000](#)

Message: Error while ensuring the sidno be present in the `group_gtid_executed`.

[ER\\_GRP\\_RPL\\_ERROR\\_VERIFYING\\_SIDNO](#) was added in 8.0.11.

- Error number: [MY-011472](#); Symbol: [ER\\_GRP\\_RPL\\_CANT\\_GENERATE\\_GTID](#); SQLSTATE: [HY000](#)

Message: Impossible to generate Global Transaction Identifier: the integer component reached the maximal value. Restart the group with a new `group_replication_group_name`.

[ER\\_GRP\\_RPL\\_CANT\\_GENERATE\\_GTID](#) was added in 8.0.11.

- Error number: [MY-011473](#); Symbol: [ER\\_GRP\\_RPL\\_INVALID\\_GTID\\_SET](#); SQLSTATE: [HY000](#)

Message: Invalid stable transactions set.

[ER\\_GRP\\_RPL\\_INVALID\\_GTID\\_SET](#) was added in 8.0.11.

- Error number: [MY-011474](#); Symbol: [ER\\_GRP\\_RPL\\_UPDATE\\_GTID\\_SET\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating stable transactions set.

[ER\\_GRP\\_RPL\\_UPDATE\\_GTID\\_SET\\_ERROR](#) was added in 8.0.11.

- 
- Error number: `MY-011475`; Symbol: `ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS`; SQLSTATE: `HY000`

Message: There was an error when filling the missing GTIDs on the applier channel received set. Despite not critical, on the long run this may cause performance issues.

`ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS` was added in 8.0.11.

- Error number: `MY-011476`; Symbol: `ER_GRP_RPL_SKIP_COMPUTATION_TRANS_COMMITTED`; SQLSTATE: `HY000`

Message: Skipping the computation of the `Transactions_committed_all_members` field as an older instance of this computation is still ongoing.

`ER_GRP_RPL_SKIP_COMPUTATION_TRANS_COMMITTED` was added in 8.0.11, removed after 8.0.26.

- Error number: `MY-011477`; Symbol: `ER_GRP_RPL_NULL_PACKET`; SQLSTATE: `HY000`

Message: Null packet on certifier's queue.

`ER_GRP_RPL_NULL_PACKET` was added in 8.0.11.

- Error number: `MY-011478`; Symbol: `ER_GRP_RPL_CANT_READ_GTID`; SQLSTATE: `HY000`

Message: Error reading GTIDs from the message.

`ER_GRP_RPL_CANT_READ_GTID` was added in 8.0.11.

- Error number: `MY-011479`; Symbol: `ER_GRP_RPL_PROCESS_GTID_SET_ERROR`; SQLSTATE: `HY000`

Message: Error processing stable transactions set.

`ER_GRP_RPL_PROCESS_GTID_SET_ERROR` was added in 8.0.11.

- Error number: `MY-011480`; Symbol: `ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR`; SQLSTATE: `HY000`

Message: Error processing intersection of stable transactions set.

`ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR` was added in 8.0.11.

- Error number: `MY-011481`; Symbol: `ER_GRP_RPL_SET_STABLE_TRANS_ERROR`; SQLSTATE: `HY000`

Message: Error setting stable transactions set.

`ER_GRP_RPL_SET_STABLE_TRANS_ERROR` was added in 8.0.11.

- Error number: `MY-011482`; Symbol: `ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED`; SQLSTATE: `HY000`

Message: Error reading `group_gtid_extracted` from the `View_change_log_event`.

`ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED` was added in 8.0.11.



- 
- Error number: [MY-011483](#); Symbol: [ER\\_GRP\\_RPL\\_CANT\\_READ\\_WRITE\\_SET\\_ITEM](#); SQLSTATE: [HY000](#)  
Message: Error reading the write set item '%s' from the View\_change\_log\_event.  
[ER\\_GRP\\_RPL\\_CANT\\_READ\\_WRITE\\_SET\\_ITEM](#) was added in 8.0.11.
  - Error number: [MY-011484](#); Symbol: [ER\\_GRP\\_RPL\\_INIT\\_CERTIFICATION\\_INFO\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Error during certification\_info initialization.  
[ER\\_GRP\\_RPL\\_INIT\\_CERTIFICATION\\_INFO\\_FAILURE](#) was added in 8.0.11.
  - Error number: [MY-011485](#); Symbol: [ER\\_GRP\\_RPL\\_CONFLICT\\_DETECTION\\_DISABLED](#); SQLSTATE: [HY000](#)  
Message: Primary had applied all relay logs, disabled conflict detection.  
[ER\\_GRP\\_RPL\\_CONFLICT\\_DETECTION\\_DISABLED](#) was added in 8.0.11.
  - Error number: [MY-011486](#); Symbol: [ER\\_GRP\\_RPL\\_MSG\\_DISCARDED](#); SQLSTATE: [HY000](#)  
Message: Message received while the plugin is not ready, message discarded.  
[ER\\_GRP\\_RPL\\_MSG\\_DISCARDED](#) was added in 8.0.11.
  - Error number: [MY-011487](#); Symbol: [ER\\_GRP\\_RPL\\_MISSING\\_GRP\\_RPL\\_APPLIER](#); SQLSTATE: [HY000](#)  
Message: Message received without a proper group replication applier.  
[ER\\_GRP\\_RPL\\_MISSING\\_GRP\\_RPL\\_APPLIER](#) was added in 8.0.11.
  - Error number: [MY-011488](#); Symbol: [ER\\_GRP\\_RPL\\_CERTIFIER\\_MSSG\\_PROCESS\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error processing message in Certifier.  
[ER\\_GRP\\_RPL\\_CERTIFIER\\_MSSG\\_PROCESS\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011489](#); Symbol: [ER\\_GRP\\_RPL\\_SRV\\_NOT\\_ONLINE](#); SQLSTATE: [HY000](#)  
Message: This server was not declared online since it is on status %s.  
[ER\\_GRP\\_RPL\\_SRV\\_NOT\\_ONLINE](#) was added in 8.0.11.
  - Error number: [MY-011490](#); Symbol: [ER\\_GRP\\_RPL\\_SRV\\_ONLINE](#); SQLSTATE: [HY000](#)  
Message: This server was declared online within the replication group.  
[ER\\_GRP\\_RPL\\_SRV\\_ONLINE](#) was added in 8.0.11.
  - Error number: [MY-011491](#); Symbol: [ER\\_GRP\\_RPL\\_DISABLE\\_SRV\\_READ\\_MODE\\_RESTRICTED](#); SQLSTATE: [HY000](#)  
Message: When declaring the plugin online it was not possible to disable the server read mode settings. Try to disable it manually.  
[ER\\_GRP\\_RPL\\_DISABLE\\_SRV\\_READ\\_MODE\\_RESTRICTED](#) was added in 8.0.11.

- 
- Error number: `MY-011492`; Symbol: `ER_GRP_RPL_MEM_ONLINE`; SQLSTATE: `HY000`  
Message: The member with address %s:%u was declared online within the replication group.  
`ER_GRP_RPL_MEM_ONLINE` was added in 8.0.11.
  - Error number: `MY-011493`; Symbol: `ER_GRP_RPL_MEM_UNREACHABLE`; SQLSTATE: `HY000`  
Message: Member with address %s:%u has become unreachable.  
`ER_GRP_RPL_MEM_UNREACHABLE` was added in 8.0.11.
  - Error number: `MY-011494`; Symbol: `ER_GRP_RPL_MEM_REACHABLE`; SQLSTATE: `HY000`  
Message: Member with address %s:%u is reachable again.  
`ER_GRP_RPL_MEM_REACHABLE` was added in 8.0.11.
  - Error number: `MY-011495`; Symbol: `ER_GRP_RPL_SRV_BLOCKED`; SQLSTATE: `HY000`  
Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked until contact with the majority is restored. It is possible to use `group_replication_force_members` to force a new group membership.  
`ER_GRP_RPL_SRV_BLOCKED` was added in 8.0.11.
  - Error number: `MY-011496`; Symbol: `ER_GRP_RPL_SRV_BLOCKED_FOR_SECS`; SQLSTATE: `HY000`  
Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked for the next %lu seconds. Unless contact with the majority is restored, after this time the member will error out and leave the group. It is possible to use `group_replication_force_members` to force a new group membership.  
`ER_GRP_RPL_SRV_BLOCKED_FOR_SECS` was added in 8.0.11.
  - Error number: `MY-011497`; Symbol: `ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED`; SQLSTATE: `HY000`  
Message: A group membership change was received but the plugin is already leaving due to the configured timeout on `group_replication_unreachable_majority_timeout` option.  
`ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED` was added in 8.0.11.
  - Error number: `MY-011498`; Symbol: `ER_GRP_RPL_MEMBER_CONTACT_RESTORED`; SQLSTATE: `HY000`  
Message: The member has resumed contact with a majority of the members in the group. Regular operation is restored and transactions are unblocked.  
`ER_GRP_RPL_MEMBER_CONTACT_RESTORED` was added in 8.0.11.
  - Error number: `MY-011499`; Symbol: `ER_GRP_RPL_MEMBER_REMOVED`; SQLSTATE: `HY000`  
Message: Members removed from the group: %s  
`ER_GRP_RPL_MEMBER_REMOVED` was added in 8.0.11.
  - Error number: `MY-011500`; Symbol: `ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP`; SQLSTATE: `HY000`  
Message: Primary server with address %s left the group. Electing new Primary.

---

`ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP` was added in 8.0.11.

- Error number: `MY-011501`; Symbol: `ER_GRP_RPL_MEMBER_ADDED`; SQLSTATE: `HY000`

Message: Members joined the group: %s

`ER_GRP_RPL_MEMBER_ADDED` was added in 8.0.11.

- Error number: `MY-011502`; Symbol: `ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR`; SQLSTATE: `HY000`

Message: There was a previous plugin error while the member joined the group. The member will now exit the group.

`ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR` was added in 8.0.11.

- Error number: `MY-011503`; Symbol: `ER_GRP_RPL_MEMBER_CHANGE`; SQLSTATE: `HY000`

Message: Group membership changed to %s on view %s.

`ER_GRP_RPL_MEMBER_CHANGE` was added in 8.0.11.

- Error number: `MY-011504`; Symbol: `ER_GRP_RPL_MEMBER_LEFT_GRP`; SQLSTATE: `HY000`

Message: Group membership changed: This member has left the group.

`ER_GRP_RPL_MEMBER_LEFT_GRP` was added in 8.0.11.

- Error number: `MY-011505`; Symbol: `ER_GRP_RPL_MEMBER_EXPELLED`; SQLSTATE: `HY000`

Message: Member was expelled from the group due to network failures, changing member status to ERROR.

`ER_GRP_RPL_MEMBER_EXPELLED` was added in 8.0.11.

- Error number: `MY-011506`; Symbol: `ER_GRP_RPL_SESSION_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Unable to open session to (re)set read only mode. Skipping.

`ER_GRP_RPL_SESSION_OPEN_FAILED` was added in 8.0.11.

- Error number: `MY-011507`; Symbol: `ER_GRP_RPL_NEW_PRIMARY_ELECTED`; SQLSTATE: `HY000`

Message: A new primary with address %s:%u was elected. %s

`ER_GRP_RPL_NEW_PRIMARY_ELECTED` was added in 8.0.11.

- Error number: `MY-011508`; Symbol: `ER_GRP_RPL_DISABLE_READ_ONLY_FAILED`; SQLSTATE: `HY000`

Message: Unable to disable super read only flag. Try to disable it manually

`ER_GRP_RPL_DISABLE_READ_ONLY_FAILED` was added in 8.0.11.

- Error number: `MY-011509`; Symbol: `ER_GRP_RPL_ENABLE_READ_ONLY_FAILED`; SQLSTATE: `HY000`

Message: Unable to set super read only flag. Try to set it manually.

`ER_GRP_RPL_ENABLE_READ_ONLY_FAILED` was added in 8.0.11.

- 
- Error number: `MY-011510`; Symbol: `ER_GRP_RPL_SRV_PRIMARY_MEM`; SQLSTATE: `HY000`  
Message: This server is working as primary member.  
`ER_GRP_RPL_SRV_PRIMARY_MEM` was added in 8.0.11.
  - Error number: `MY-011511`; Symbol: `ER_GRP_RPL_SRV_SECONDARY_MEM`; SQLSTATE: `HY000`  
Message: This server is working as secondary member with primary member address %s:%u.  
`ER_GRP_RPL_SRV_SECONDARY_MEM` was added in 8.0.11.
  - Error number: `MY-011512`; Symbol: `ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM`; SQLSTATE: `HY000`  
Message: Unable to set any member as primary. No suitable candidate.  
`ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM` was added in 8.0.11.
  - Error number: `MY-011513`; Symbol: `ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR`; SQLSTATE: `HY000`  
Message: Error when activating super\_read\_only mode on start. The member will now exit the group.  
`ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR` was added in 8.0.11.
  - Error number: `MY-011514`; Symbol: `ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE`; SQLSTATE: `HY000`  
Message: Group contains %lu members which is greater than group\_replication\_auto\_increment\_increment value of %lu. This can lead to a higher transactional abort rate.  
`ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE` was added in 8.0.11.
  - Error number: `MY-011515`; Symbol: `ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM`; SQLSTATE: `HY000`  
Message: Member with address '%s:%u' didn't provide any data during the last group change. Group information can be outdated and lead to errors on recovery.  
`ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM` was added in 8.0.11.
  - Error number: `MY-011516`; Symbol: `ER_GRP_RPL_MEMBER_ALREADY_EXISTS`; SQLSTATE: `HY000`  
Message: There is already a member with server\_uuid %s. The member will now exit the group.  
`ER_GRP_RPL_MEMBER_ALREADY_EXISTS` was added in 8.0.11.
  - Error number: `MY-011517`; Symbol: `ER_GRP_RPL_GRP_CHANGE_INFO_EXTRACT_ERROR`; SQLSTATE: `HY000`  
Message: Error when extracting information for group change. Operations and checks made to group joiners may be incomplete.  
`ER_GRP_RPL_GRP_CHANGE_INFO_EXTRACT_ERROR` was added in 8.0.11, removed after 8.0.26.

- 
- Error number: [MY-011518](#); Symbol: [ER\\_GRP\\_RPL\\_GTID\\_EXECUTED\\_EXTRACT\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error when extracting this member GTID executed set. Operations and checks made to group joiners may be incomplete.  
  
[ER\\_GRP\\_RPL\\_GTID\\_EXECUTED\\_EXTRACT\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011519](#); Symbol: [ER\\_GRP\\_RPL\\_GTID\\_SET\\_EXTRACT\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error when extracting this member retrieved set for its applier. Operations and checks made to group joiners may be incomplete.  
  
[ER\\_GRP\\_RPL\\_GTID\\_SET\\_EXTRACT\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011520](#); Symbol: [ER\\_GRP\\_RPL\\_START\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: The START GROUP\_REPLICATION command failed since the group already has 9 members.  
  
[ER\\_GRP\\_RPL\\_START\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011521](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_VER\\_INCOMPATIBLE](#); SQLSTATE: [HY000](#)  
  
Message: Member version is incompatible with the group.  
  
[ER\\_GRP\\_RPL\\_MEMBER\\_VER\\_INCOMPATIBLE](#) was added in 8.0.11.
  - Error number: [MY-011522](#); Symbol: [ER\\_GRP\\_RPL\\_TRANS\\_NOT\\_PRESENT\\_IN\\_GRP](#); SQLSTATE: [HY000](#)  
  
Message: The member contains transactions not present in the group. The member will now exit the group.  
  
[ER\\_GRP\\_RPL\\_TRANS\\_NOT\\_PRESENT\\_IN\\_GRP](#) was added in 8.0.11.
  - Error number: [MY-011523](#); Symbol: [ER\\_GRP\\_RPL\\_TRANS\\_GREATER\\_THAN\\_GRP](#); SQLSTATE: [HY000](#)  
  
Message: It was not possible to assess if the member has more transactions than the group. The member will now exit the group.  
  
[ER\\_GRP\\_RPL\\_TRANS\\_GREATER\\_THAN\\_GRP](#) was added in 8.0.11.
  - Error number: [MY-011524](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_VERSION\\_LOWER\\_THAN\\_GRP](#); SQLSTATE: [HY000](#)  
  
Message: Member version is lower than some group member, but since option 'group\_replication\_allow\_local\_lower\_version\_join' is enabled, member will be allowed to join.  
  
[ER\\_GRP\\_RPL\\_MEMBER\\_VERSION\\_LOWER\\_THAN\\_GRP](#) was added in 8.0.11.
  - Error number: [MY-011525](#); Symbol: [ER\\_GRP\\_RPL\\_LOCAL\\_GTID\\_SETS\\_PROCESS\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error processing local GTID sets when comparing this member transactions against the group.  
  
[ER\\_GRP\\_RPL\\_LOCAL\\_GTID\\_SETS\\_PROCESS\\_ERROR](#) was added in 8.0.11.
-

- 
- Error number: `MY-011526`; Symbol: `ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP`; SQLSTATE: `HY000`  
  
Message: This member has more executed transactions than those present in the group. Local transactions: %s > Group transactions: %s  
  
`ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP` was added in 8.0.11.
  - Error number: `MY-011527`; Symbol: `ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP`; SQLSTATE: `HY000`  
  
Message: The member is configured with a `group_replication_gtid_assignment_block_size` option value '%llu' different from the group '%llu'. The member will now exit the group.  
  
`ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP` was added in 8.0.11.
  - Error number: `MY-011528`; Symbol: `ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_GRP`; SQLSTATE: `HY000`  
  
Message: The member is configured with a transaction-write-set-extraction option value '%s' different from the group '%s'. The member will now exit the group.  
  
`ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_GRP` was added in 8.0.11.
  - Error number: `MY-011529`; Symbol: `ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP_CFG`; SQLSTATE: `HY000`  
  
Message: The member configuration is not compatible with the group configuration. Variables such as `group_replication_single_primary_mode` or `group_replication_enforce_update_everywhere_checks` must have the same value on every server in the group. (member configuration option: [%s], group configuration option: [%s]).  
  
`ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP_CFG` was added in 8.0.11.
  - Error number: `MY-011530`; Symbol: `ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR`; SQLSTATE: `HY000`  
  
Message: Error stopping all replication channels while server was leaving the group. %s  
  
`ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR` was added in 8.0.11.
  - Error number: `MY-011531`; Symbol: `ER_GRP_RPL_PURGE_APPLIERS_LOGS`; SQLSTATE: `HY000`  
  
Message: Detected previous RESET SOURCE invocation or an issue exists in the group replication applier relay log. Purging existing applier logs.  
  
`ER_GRP_RPL_PURGE_APPLIERS_LOGS` was added in 8.0.11.
  - Error number: `MY-011532`; Symbol: `ER_GRP_RPL_RESET_APPLIERS_MODULE_LOGS_ERROR`; SQLSTATE: `HY000`  
  
Message: Unknown error occurred while resetting applier's module logs.  
  
`ER_GRP_RPL_RESET_APPLIERS_MODULE_LOGS_ERROR` was added in 8.0.11.
  - Error number: `MY-011533`; Symbol: `ER_GRP_RPL_APPLIERS_THD_SETUP_ERROR`; SQLSTATE: `HY000`  
  
Message: Failed to setup the group replication applier thread.

---

[ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_SETUP\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011534](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_START\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error while starting the group replication applier thread

[ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_START\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011535](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_STOP\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Failed to stop the group replication applier thread.

[ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_STOP\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-011536](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_TRANS\\_DATA\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to fetch transaction data containing required transaction info for applier

[ER\\_GRP\\_RPL\\_FETCH\\_TRANS\\_DATA\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011537](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_IO\\_THD\\_PRIMARY\\_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start slave IO THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

[ER\\_GRP\\_RPL\\_SLAVE\\_IO\\_THD\\_PRIMARY\\_UNKNOWN](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-011537](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_IO\\_THD\\_PRIMARY\\_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start replica IO THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

[ER\\_GRP\\_RPL\\_REPLICA\\_IO\\_THD\\_PRIMARY\\_UNKNOWN](#) was added in 8.0.33.

- Error number: [MY-011538](#); Symbol: [ER\\_GRP\\_RPL\\_SALVE\\_IO\\_THD\\_ON\\_SECONDARY\\_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start replica IO THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

[ER\\_GRP\\_RPL\\_SALVE\\_IO\\_THD\\_ON\\_SECONDARY\\_MEMBER](#) was added in 8.0.11.

- Error number: [MY-011539](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_SQL\\_THD\\_PRIMARY\\_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start slave SQL THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

[ER\\_GRP\\_RPL\\_SLAVE\\_SQL\\_THD\\_PRIMARY\\_UNKNOWN](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-011539](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_SQL\\_THD\\_PRIMARY\\_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start replica SQL THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

---

[ER\\_GRP\\_RPL\\_REPLICA\\_SQL\\_THD\\_PRIMARY\\_UNKNOWN](#) was added in 8.0.33.

- Error number: [MY-011540](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_SQL\\_THD\\_ON\\_SECONDARY\\_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start slave SQL THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

[ER\\_GRP\\_RPL\\_SLAVE\\_SQL\\_THD\\_ON\\_SECONDARY\\_MEMBER](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-011540](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_SQL\\_THD\\_ON\\_SECONDARY\\_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start replica SQL THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

[ER\\_GRP\\_RPL\\_REPLICA\\_SQL\\_THD\\_ON\\_SECONDARY\\_MEMBER](#) was added in 8.0.33.

- Error number: [MY-011541](#); Symbol: [ER\\_GRP\\_RPL\\_NEEDS\\_INNODB\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Table %s does not use the InnoDB storage engine. This is not compatible with Group Replication.

[ER\\_GRP\\_RPL\\_NEEDS\\_INNODB\\_TABLE](#) was added in 8.0.11.

- Error number: [MY-011542](#); Symbol: [ER\\_GRP\\_RPL\\_PRIMARY\\_KEY\\_NOT\\_DEFINED](#); SQLSTATE: [HY000](#)

Message: Table %s does not have any PRIMARY KEY. This is not compatible with Group Replication.

[ER\\_GRP\\_RPL\\_PRIMARY\\_KEY\\_NOT\\_DEFINED](#) was added in 8.0.11.

- Error number: [MY-011543](#); Symbol: [ER\\_GRP\\_RPL\\_FK\\_WITH\\_CASCADE\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: Table %s has a foreign key with 'CASCADE', 'SET NULL' or 'SET DEFAULT' clause. This is not compatible with Group Replication.

[ER\\_GRP\\_RPL\\_FK\\_WITH\\_CASCADE\\_UNSUPPORTED](#) was added in 8.0.11.

- Error number: [MY-011544](#); Symbol: [ER\\_GRP\\_RPL\\_AUTO\\_INC\\_RESET](#); SQLSTATE: [HY000](#)

Message: group\_replication\_auto\_increment\_increment is reset to %lu

[ER\\_GRP\\_RPL\\_AUTO\\_INC\\_RESET](#) was added in 8.0.11.

- Error number: [MY-011545](#); Symbol: [ER\\_GRP\\_RPL\\_AUTO\\_INC\\_OFFSET\\_RESET](#); SQLSTATE: [HY000](#)

Message: auto\_increment\_offset is reset to %lu

[ER\\_GRP\\_RPL\\_AUTO\\_INC\\_OFFSET\\_RESET](#) was added in 8.0.11.

- Error number: [MY-011546](#); Symbol: [ER\\_GRP\\_RPL\\_AUTO\\_INC\\_SET](#); SQLSTATE: [HY000](#)

Message: group\_replication\_auto\_increment\_increment is set to %lu

[ER\\_GRP\\_RPL\\_AUTO\\_INC\\_SET](#) was added in 8.0.11.

- Error number: [MY-011547](#); Symbol: [ER\\_GRP\\_RPL\\_AUTO\\_INC\\_OFFSET\\_SET](#); SQLSTATE: [HY000](#)



---

Message: auto\_increment\_offset is set to %lu

ER\_GRP\_RPL\_AUTO\_INC\_OFFSET\_SET was added in 8.0.11.

- Error number: MY-011548; Symbol: ER\_GRP\_RPL\_FETCH\_TRANS\_CONTEXT\_FAILED; SQLSTATE: HY000

Message: Failed to fetch transaction context containing required transaction info for certification

ER\_GRP\_RPL\_FETCH\_TRANS\_CONTEXT\_FAILED was added in 8.0.11.

- Error number: MY-011549; Symbol: ER\_GRP\_RPL\_FETCH\_FORMAT\_DESC\_LOG\_EVENT\_FAILED; SQLSTATE: HY000

Message: Failed to fetch Format\_description\_log\_event containing required server info for applier

ER\_GRP\_RPL\_FETCH\_FORMAT\_DESC\_LOG\_EVENT\_FAILED was added in 8.0.11.

- Error number: MY-011550; Symbol: ER\_GRP\_RPL\_FETCH\_TRANS\_CONTEXT\_LOG\_EVENT\_FAILED; SQLSTATE: HY000

Message: Failed to fetch Transaction\_context\_log\_event containing required transaction info for certification

ER\_GRP\_RPL\_FETCH\_TRANS\_CONTEXT\_LOG\_EVENT\_FAILED was added in 8.0.11.

- Error number: MY-011551; Symbol: ER\_GRP\_RPL\_FETCH\_SNAPSHOT\_VERSION\_FAILED; SQLSTATE: HY000

Message: Failed to read snapshot version from transaction context event required for certification

ER\_GRP\_RPL\_FETCH\_SNAPSHOT\_VERSION\_FAILED was added in 8.0.11.

- Error number: MY-011552; Symbol: ER\_GRP\_RPL\_FETCH\_GTID\_LOG\_EVENT\_FAILED; SQLSTATE: HY000

Message: Failed to fetch Gtid\_log\_event containing required transaction info for certification

ER\_GRP\_RPL\_FETCH\_GTID\_LOG\_EVENT\_FAILED was added in 8.0.11.

- Error number: MY-011553; Symbol: ER\_GRP\_RPL\_UPDATE\_SERV\_CERTIFICATE\_FAILED; SQLSTATE: HY000

Message: Unable to update certification result on server side, thread\_id: %lu

ER\_GRP\_RPL\_UPDATE\_SERV\_CERTIFICATE\_FAILED was added in 8.0.11.

- Error number: MY-011554; Symbol: ER\_GRP\_RPL\_ADD\_GTID\_INFO\_WITH\_LOCAL\_GTID\_FAILED; SQLSTATE: HY000

Message: Unable to add gtid information to the group\_gtid\_executed set when gtid was provided for local transactions

ER\_GRP\_RPL\_ADD\_GTID\_INFO\_WITH\_LOCAL\_GTID\_FAILED was added in 8.0.11.

- Error number: MY-011555; Symbol: ER\_GRP\_RPL\_ADD\_GTID\_INFO\_WITHOUT\_LOCAL\_GTID\_FAILED; SQLSTATE: HY000

---

Message: Unable to add gtid information to the group\_gtid\_executed set when no gtid was provided for local transactions

[ER\\_GRP\\_RPL\\_ADD\\_GTID\\_INFO\\_WITHOUT\\_LOCAL\\_GTID\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011556](#); Symbol: [ER\\_GRP\\_RPL\\_NOTIFY\\_CERTIFICATION\\_OUTCOME\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to notify certification outcome

[ER\\_GRP\\_RPL\\_NOTIFY\\_CERTIFICATION\\_OUTCOME\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011557](#); Symbol: [ER\\_GRP\\_RPL\\_ADD\\_GTID\\_INFO\\_WITH\\_REMOTE\\_GTID\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to add gtid information to the group\_gtid\_executed set when gtid was provided for remote transactions

[ER\\_GRP\\_RPL\\_ADD\\_GTID\\_INFO\\_WITH\\_REMOTE\\_GTID\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011558](#); Symbol: [ER\\_GRP\\_RPL\\_ADD\\_GTID\\_INFO\\_WITHOUT\\_REMOTE\\_GTID\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to add gtid information to the group\_gtid\_executed set when gtid was not provided for remote transactions

[ER\\_GRP\\_RPL\\_ADD\\_GTID\\_INFO\\_WITHOUT\\_REMOTE\\_GTID\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011559](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_VIEW\\_CHANGE\\_LOG\\_EVENT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to fetch View\_change\_log\_event containing required info for certification

[ER\\_GRP\\_RPL\\_FETCH\\_VIEW\\_CHANGE\\_LOG\\_EVENT\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011560](#); Symbol: [ER\\_GRP\\_RPL\\_CONTACT\\_WITH\\_SRV\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error when contacting the server to ensure the proper logging of a group change in the binlog

[ER\\_GRP\\_RPL\\_CONTACT\\_WITH\\_SRV\\_FAILED](#) was added in 8.0.11, removed after 8.0.31.

- Error number: [MY-011561](#); Symbol: [ER\\_GRP\\_RPL\\_SRV\\_WAIT\\_TIME\\_OUT](#); SQLSTATE: [HY000](#)

Message: Timeout when waiting for the server to execute local transactions in order assure the group change proper logging

[ER\\_GRP\\_RPL\\_SRV\\_WAIT\\_TIME\\_OUT](#) was added in 8.0.11, removed after 8.0.31.

- Error number: [MY-011562](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_LOG\\_EVENT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to fetch Log\_event containing required server info for applier

[ER\\_GRP\\_RPL\\_FETCH\\_LOG\\_EVENT\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-011563](#); Symbol: [ER\\_GRP\\_RPL\\_START\\_GRP\\_RPL\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with --initialize, --initialize-insecure or --upgrade=MINIMAL on a server upgrade.

---

`ER_GRP_RPL_START_GRP_RPL_FAILED` was added in 8.0.11.

- Error number: `MY-011564`; Symbol: `ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL`; SQLSTATE: `HY000`

Message: Failed to establish an internal server connection to execute plugin operations

`ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL` was added in 8.0.11.

- Error number: `MY-011565`; Symbol: `ER_GRP_RPL_SUPER_READ_ON`; SQLSTATE: `HY000`

Message: Setting `super_read_only=ON`.

`ER_GRP_RPL_SUPER_READ_ON` was added in 8.0.11.

- Error number: `MY-011566`; Symbol: `ER_GRP_RPL_SUPER_READ_OFF`; SQLSTATE: `HY000`

Message: Setting `super_read_only=OFF`.

`ER_GRP_RPL_SUPER_READ_OFF` was added in 8.0.11.

- Error number: `MY-011567`; Symbol: `ER_GRP_RPL_KILLED_SESSION_ID`; SQLSTATE: `HY000`

Message: killed session id: %d status: %d

`ER_GRP_RPL_KILLED_SESSION_ID` was added in 8.0.11.

- Error number: `MY-011568`; Symbol: `ER_GRP_RPL_KILLED_FAILED_ID`; SQLSTATE: `HY000`

Message: killed failed id: %d failed: %d

`ER_GRP_RPL_KILLED_FAILED_ID` was added in 8.0.11.

- Error number: `MY-011569`; Symbol: `ER_GRP_RPL_INTERNAL_QUERY`; SQLSTATE: `HY000`

Message: Internal query: %s result in error. Error number: %ld

`ER_GRP_RPL_INTERNAL_QUERY` was added in 8.0.11.

- Error number: `MY-011570`; Symbol: `ER_GRP_RPL_COPY_FROM_EMPTY_STRING`; SQLSTATE: `HY000`

Message: Error copying from empty string

`ER_GRP_RPL_COPY_FROM_EMPTY_STRING` was added in 8.0.11.

- Error number: `MY-011571`; Symbol: `ER_GRP_RPL_QUERY_FAIL`; SQLSTATE: `HY000`

Message: Query execution resulted in failure. errno: %d

`ER_GRP_RPL_QUERY_FAIL` was added in 8.0.11.

- Error number: `MY-011572`; Symbol: `ER_GRP_RPL_CREATE_SESSION_UNABLE`; SQLSTATE: `HY000`

Message: Unable to create a session for executing the queries on the server

`ER_GRP_RPL_CREATE_SESSION_UNABLE` was added in 8.0.11.

- Error number: `MY-011573`; Symbol: `ER_GRP_RPL_MEMBER_NOT_FOUND`; SQLSTATE: `HY000`

---

Message: The member with address %s:%u has unexpectedly disappeared, killing the current group replication recovery connection

[ER\\_GRP\\_RPL\\_MEMBER\\_NOT\\_FOUND](#) was added in 8.0.11.

- Error number: MY-011574; Symbol: [ER\\_GRP\\_RPL\\_MAXIMUM\\_CONNECTION\\_RETRIES\\_REACHED](#); SQLSTATE: HY000

Message: Maximum number of retries when trying to connect to a donor reached. Aborting group replication incremental recovery.

[ER\\_GRP\\_RPL\\_MAXIMUM\\_CONNECTION\\_RETRIES\\_REACHED](#) was added in 8.0.11.

- Error number: MY-011575; Symbol: [ER\\_GRP\\_RPL\\_ALL\\_DONORS\\_LEFT\\_ABORT\\_RECOVERY](#); SQLSTATE: HY000

Message: All donors left. Aborting group replication incremental recovery.

[ER\\_GRP\\_RPL\\_ALL\\_DONORS\\_LEFT\\_ABORT\\_RECOVERY](#) was added in 8.0.11.

- Error number: MY-011576; Symbol: [ER\\_GRP\\_RPL\\_ESTABLISH\\_RECOVERY\\_WITH\\_DONOR](#); SQLSTATE: HY000

Message: Establishing group recovery connection with a possible donor. Attempt %d/%d

[ER\\_GRP\\_RPL\\_ESTABLISH\\_RECOVERY\\_WITH\\_DONOR](#) was added in 8.0.11.

- Error number: MY-011577; Symbol: [ER\\_GRP\\_RPL\\_ESTABLISH\\_RECOVERY\\_WITH\\_ANOTHER\\_DONOR](#); SQLSTATE: HY000

Message: Retrying group recovery connection with another donor. Attempt %d/%d

[ER\\_GRP\\_RPL\\_ESTABLISH\\_RECOVERY\\_WITH\\_ANOTHER\\_DONOR](#) was added in 8.0.11.

- Error number: MY-011578; Symbol: [ER\\_GRP\\_RPL\\_NO\\_VALID\\_DONOR](#); SQLSTATE: HY000

Message: No valid donors exist in the group, retrying

[ER\\_GRP\\_RPL\\_NO\\_VALID\\_DONOR](#) was added in 8.0.11.

- Error number: MY-011579; Symbol: [ER\\_GRP\\_RPL\\_CONFIG\\_RECOVERY](#); SQLSTATE: HY000

Message: Error when configuring the asynchronous recovery channel connection to the donor.

[ER\\_GRP\\_RPL\\_CONFIG\\_RECOVERY](#) was added in 8.0.11.

- Error number: MY-011580; Symbol: [ER\\_GRP\\_RPL\\_ESTABLISHING\\_CONN\\_GRP\\_REC\\_DONOR](#); SQLSTATE: HY000

Message: Establishing connection to a group replication recovery donor %s at %s port: %d.

[ER\\_GRP\\_RPL\\_ESTABLISHING\\_CONN\\_GRP\\_REC\\_DONOR](#) was added in 8.0.11.

- 
- Error number: [MY-011581](#); Symbol: [ER\\_GRP\\_RPL\\_CREATE\\_GRP\\_RPL\\_REC\\_CHANNEL](#); SQLSTATE: [HY000](#)  
Message: Error while creating the group replication recovery channel with donor %s at %s port: %d.  
[ER\\_GRP\\_RPL\\_CREATE\\_GRP\\_RPL\\_REC\\_CHANNEL](#) was added in 8.0.11.
  - Error number: [MY-011582](#); Symbol: [ER\\_GRP\\_RPL\\_DONOR\\_SERVER\\_CONN](#); SQLSTATE: [HY000](#)  
Message: There was an error when connecting to the donor server. Please check that group\_replication\_recovery channel credentials and all MEMBER\_HOST column values of performance\_schema.replication\_group\_members table are correct and DNS resolvable.  
[ER\\_GRP\\_RPL\\_DONOR\\_SERVER\\_CONN](#) was added in 8.0.11.
  - Error number: [MY-011583](#); Symbol: [ER\\_GRP\\_RPL\\_CHECK\\_STATUS\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: For details please check performance\_schema.replication\_connection\_status table and error log messages of Replica I/O for channel group\_replication\_recovery.  
[ER\\_GRP\\_RPL\\_CHECK\\_STATUS\\_TABLE](#) was added in 8.0.11.
  - Error number: [MY-011584](#); Symbol: [ER\\_GRP\\_RPL\\_STARTING\\_GRP\\_REC](#); SQLSTATE: [HY000](#)  
Message: Error while starting the group replication incremental recovery receiver/applier threads  
[ER\\_GRP\\_RPL\\_STARTING\\_GRP\\_REC](#) was added in 8.0.11.
  - Error number: [MY-011585](#); Symbol: [ER\\_GRP\\_RPL\\_DONOR\\_CONN\\_TERMINATION](#); SQLSTATE: [HY000](#)  
Message: Terminating existing group replication donor connection and purging the corresponding logs.  
[ER\\_GRP\\_RPL\\_DONOR\\_CONN\\_TERMINATION](#) was added in 8.0.11.
  - Error number: [MY-011586](#); Symbol: [ER\\_GRP\\_RPL\\_STOPPING\\_GRP\\_REC](#); SQLSTATE: [HY000](#)  
Message: Error when stopping the group replication incremental recovery's donor connection  
[ER\\_GRP\\_RPL\\_STOPPING\\_GRP\\_REC](#) was added in 8.0.11.
  - Error number: [MY-011587](#); Symbol: [ER\\_GRP\\_RPL\\_PURGE\\_REC](#); SQLSTATE: [HY000](#)  
Message: Error when purging the group replication recovery's relay logs  
[ER\\_GRP\\_RPL\\_PURGE\\_REC](#) was added in 8.0.11.
  - Error number: [MY-011588](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_KILL\\_CONN\\_REC\\_DONOR\\_APPLIER](#); SQLSTATE: [HY000](#)  
Message: Unable to kill the current group replication recovery donor connection after an applier error. Incremental recovery will shutdown.  
[ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_KILL\\_CONN\\_REC\\_DONOR\\_APPLIER](#) was added in 8.0.11.
  - Error number: [MY-011589](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_KILL\\_CONN\\_REC\\_DONOR\\_FAILOVER](#); SQLSTATE: [HY000](#)  
Message: Unable to kill the current group replication recovery donor connection during failover. Incremental recovery will shutdown.
-

---

`ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FAILOVER` was added in 8.0.11.

- Error number: `MY-011590`; Symbol: `ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT`; SQLSTATE: `HY000`

Message: Unexpected error when notifying an internal component named %s regarding a group membership event.

`ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT` was added in 8.0.11.

- Error number: `MY-011591`; Symbol: `ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION`; SQLSTATE: `HY000`

Message: An undefined error was found while broadcasting an internal group membership notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!

`ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION` was added in 8.0.11.

- Error number: `MY-011592`; Symbol: `ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS_NOTIFICATION`; SQLSTATE: `HY000`

Message: An undefined error was found while broadcasting an internal group member status notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!

`ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS_NOTIFICATION` was added in 8.0.11.

- Error number: `MY-011593`; Symbol: `ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION_HASH`; SQLSTATE: `HY000`

Message: No memory to generate write identification hash

`ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION_HASH` was added in 8.0.11.

- Error number: `MY-011594`; Symbol: `ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED`; SQLSTATE: `HY000`

Message: Base 64 encoding of the write identification hash failed

`ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED` was added in 8.0.11.

- Error number: `MY-011595`; Symbol: `ER_GRP_RPL_INVALID_BINLOG_FORMAT`; SQLSTATE: `HY000`

Message: Binlog format should be ROW for Group Replication

`ER_GRP_RPL_INVALID_BINLOG_FORMAT` was added in 8.0.11.

- Error number: `MY-011596`; Symbol: `ER_GRP_RPL_BINLOG_CHECKSUM_SET`; SQLSTATE: `HY000`

Message: binlog\_checksum should be NONE for Group Replication

`ER_GRP_RPL_BINLOG_CHECKSUM_SET` was added in 8.0.11, removed after 8.0.20.

- Error number: `MY-011597`; Symbol: `ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOT_SET`; SQLSTATE: `HY000`

Message: A transaction\_write\_set\_extraction algorithm should be selected when running Group Replication

---

`ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOT_SET` was added in 8.0.11.

- Error number: `MY-011598`; Symbol: `ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION`; SQLSTATE: `HY000`

Message: Transaction isolation level (tx\_isolation) is set to SERIALIZABLE, which is not compatible with Group Replication

`ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION` was added in 8.0.11.

- Error number: `MY-011599`; Symbol: `ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING`; SQLSTATE: `HY000`

Message: Transaction cannot be executed while Group Replication is stopping.

`ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING` was added in 8.0.11.

- Error number: `MY-011600`; Symbol: `ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING`; SQLSTATE: `HY000`

Message: Transaction cannot be executed while Group Replication is recovering. Try again when the server is ONLINE.

`ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING` was added in 8.0.11.

- Error number: `MY-011601`; Symbol: `ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE`; SQLSTATE: `HY000`

Message: Transaction cannot be executed while Group Replication is on ERROR state. Check for errors and restart the plugin

`ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE` was added in 8.0.11.

- Error number: `MY-011602`; Symbol: `ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE`; SQLSTATE: `HY000`

Message: Transaction cannot be executed while Group Replication is OFFLINE. Check for errors and restart the plugin

`ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE` was added in 8.0.11.

- Error number: `MY-011603`; Symbol: `ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED_FOR_SESSION`; SQLSTATE: `HY000`

Message: We can only use one cache type at a time on session %u

`ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED_FOR_SESSION` was added in 8.0.11.

- Error number: `MY-011604`; Symbol: `ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_READ`; SQLSTATE: `HY000`

Message: Failed to reinit binlog cache log for read on session %u

`ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_READ` was added in 8.0.11.

- Error number: `MY-011605`; Symbol: `ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT`; SQLSTATE: `HY000`

---

Message: Failed to create the context of the current transaction on session %u

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_CREATE\\_TRANS\\_CONTEXT](#) was added in 8.0.11.

- Error number: [MY-011606](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_EXTRACT\\_TRANS\\_WRITE\\_SET](#); SQLSTATE: [HY000](#)

Message: Failed to extract the set of items written during the execution of the current transaction on session %u

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_EXTRACT\\_TRANS\\_WRITE\\_SET](#) was added in 8.0.11.

- Error number: [MY-011607](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_GATHER\\_TRANS\\_WRITE\\_SET](#); SQLSTATE: [HY000](#)

Message: Failed to gather the set of items written during the execution of the current transaction on session %u

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_GATHER\\_TRANS\\_WRITE\\_SET](#) was added in 8.0.11.

- Error number: [MY-011608](#); Symbol: [ER\\_GRP\\_RPL\\_TRANS\\_SIZE\\_EXCEEDS\\_LIMIT](#); SQLSTATE: [HY000](#)

Message: Error on session %u. Transaction of size %llu exceeds specified limit %lu. To increase the limit please adjust `group_replication_transaction_size_limit` option.

[ER\\_GRP\\_RPL\\_TRANS\\_SIZE\\_EXCEEDS\\_LIMIT](#) was added in 8.0.11.

- Error number: [MY-011609](#); Symbol: [ER\\_GRP\\_RPL\\_REINIT\\_OF\\_INTERNAL\\_CACHE\\_FOR\\_READ\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while re-initializing an internal cache, for read operations, on session %u

[ER\\_GRP\\_RPL\\_REINIT\\_OF\\_INTERNAL\\_CACHE\\_FOR\\_READ\\_FAILED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011610](#); Symbol: [ER\\_GRP\\_RPL\\_APPENDING\\_DATA\\_TO\\_INTERNAL\\_CACHE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while appending data to an internal cache on session %u

[ER\\_GRP\\_RPL\\_APPENDING\\_DATA\\_TO\\_INTERNAL\\_CACHE\\_FAILED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011611](#); Symbol: [ER\\_GRP\\_RPL\\_WRITE\\_TO\\_BINLOG\\_CACHE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while writing binary log cache on session %u

[ER\\_GRP\\_RPL\\_WRITE\\_TO\\_BINLOG\\_CACHE\\_FAILED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011611](#); Symbol: [ER\\_GRP\\_RPL\\_WRITE\\_TO\\_TRANSACTION\\_MESSAGE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while writing to transaction message on session %u

[ER\\_GRP\\_RPL\\_WRITE\\_TO\\_TRANSACTION\\_MESSAGE\\_FAILED](#) was added in 8.0.13.



- 
- Error number: [MY-011612](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_REGISTER\\_TRANS\\_OUTCOME\\_NOTIFICATION](#); SQLSTATE: [HY000](#)  
Message: Unable to register for getting notifications regarding the outcome of the transaction on session %u  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_REGISTER\\_TRANS\\_OUTCOME\\_NOTIFICATION](#) was added in 8.0.11.
  - Error number: [MY-011613](#); Symbol: [ER\\_GRP\\_RPL\\_MSG\\_TOO\\_LONG\\_BROADCASTING\\_TRANS\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Error broadcasting transaction to the group on session %u. Message is too big.  
[ER\\_GRP\\_RPL\\_MSG\\_TOO\\_LONG\\_BROADCASTING\\_TRANS\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011614](#); Symbol: [ER\\_GRP\\_RPL\\_BROADCASTING\\_TRANS\\_TO\\_GRP\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Error while broadcasting the transaction to the group on session %u  
[ER\\_GRP\\_RPL\\_BROADCASTING\\_TRANS\\_TO\\_GRP\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011615](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_WHILE\\_WAITING\\_FOR\\_CONFLICT\\_DETECTION](#); SQLSTATE: [HY000](#)  
Message: Error while waiting for conflict detection procedure to finish on session %u  
[ER\\_GRP\\_RPL\\_ERROR\\_WHILE\\_WAITING\\_FOR\\_CONFLICT\\_DETECTION](#) was added in 8.0.11.
  - Error number: [MY-011616](#); Symbol: [ER\\_GRP\\_RPL\\_REINIT\\_OF\\_INTERNAL\\_CACHE\\_FOR\\_WRITE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Error while re-initializing an internal cache, for write operations, on session %u  
[ER\\_GRP\\_RPL\\_REINIT\\_OF\\_INTERNAL\\_CACHE\\_FOR\\_WRITE\\_FAILED](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011617](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_CREATE\\_COMMIT\\_CACHE](#); SQLSTATE: [HY000](#)  
Message: Failed to create group replication commit cache on session %u  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_CREATE\\_COMMIT\\_CACHE](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011618](#); Symbol: [ER\\_GRP\\_RPL\\_REINIT\\_OF\\_COMMIT\\_CACHE\\_FOR\\_WRITE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to reinit group replication commit cache for write on session %u  
[ER\\_GRP\\_RPL\\_REINIT\\_OF\\_COMMIT\\_CACHE\\_FOR\\_WRITE\\_FAILED](#) was added in 8.0.11, removed after 8.0.12.
  - Error number: [MY-011619](#); Symbol: [ER\\_GRP\\_RPL\\_PREV\\_REC\\_SESSION\\_RUNNING](#); SQLSTATE: [HY000](#)  
Message: A previous recovery session is still running. Please stop the group replication plugin and wait for it to stop  
[ER\\_GRP\\_RPL\\_PREV\\_REC\\_SESSION\\_RUNNING](#) was added in 8.0.11, removed after 8.0.22.
-

- 
- Error number: [MY-011620](#); Symbol: [ER\\_GRP\\_RPL\\_FATAL\\_REC\\_PROCESS](#); SQLSTATE: [HY000](#)  
Message: Fatal error during the incremental recovery process of Group Replication. The server will leave the group.  
[ER\\_GRP\\_RPL\\_FATAL\\_REC\\_PROCESS](#) was added in 8.0.11.
  - Error number: [MY-011621](#); Symbol: [ER\\_GRP\\_RPL\\_WHILE\\_STOPPING\\_REP\\_CHANNEL](#); SQLSTATE: [HY000](#)  
Message: Error stopping all replication channels while server was leaving the group. %s  
[ER\\_GRP\\_RPL\\_WHILE\\_STOPPING\\_REP\\_CHANNEL](#) was added in 8.0.11, removed after 8.0.17.
  - Error number: [MY-011622](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_EVALUATE\\_APPLIER\\_STATUS](#); SQLSTATE: [HY000](#)  
Message: Unable to evaluate the group replication applier execution status. Group replication recovery will shutdown to avoid data corruption.  
[ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_EVALUATE\\_APPLIER\\_STATUS](#) was added in 8.0.11.
  - Error number: [MY-011623](#); Symbol: [ER\\_GRP\\_RPL\\_ONLY\\_ONE\\_SERVER\\_ALIVE](#); SQLSTATE: [HY000](#)  
Message: Only one server alive. Declaring this server as online within the replication group  
[ER\\_GRP\\_RPL\\_ONLY\\_ONE\\_SERVER\\_ALIVE](#) was added in 8.0.11.
  - Error number: [MY-011624](#); Symbol: [ER\\_GRP\\_RPL\\_CERTIFICATION\\_REC\\_PROCESS](#); SQLSTATE: [HY000](#)  
Message: Error when processing certification information in the incremental recovery process  
[ER\\_GRP\\_RPL\\_CERTIFICATION\\_REC\\_PROCESS](#) was added in 8.0.11.
  - Error number: [MY-011625](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_ENSURE\\_EXECUTION\\_REC](#); SQLSTATE: [HY000](#)  
Message: Unable to ensure the execution of group transactions received during recovery.  
[ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_ENSURE\\_EXECUTION\\_REC](#) was added in 8.0.11.
  - Error number: [MY-011626](#); Symbol: [ER\\_GRP\\_RPL\\_WHILE\\_SENDING\\_MSG\\_REC](#); SQLSTATE: [HY000](#)  
Message: Error while sending message in the group replication incremental recovery process.  
[ER\\_GRP\\_RPL\\_WHILE\\_SENDING\\_MSG\\_REC](#) was added in 8.0.11.
  - Error number: [MY-011627](#); Symbol: [ER\\_GRP\\_RPL\\_READ\\_UNABLE\\_FOR\\_SUPER\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)  
Message: Unable to read the server value for the super\_read\_only variable.  
[ER\\_GRP\\_RPL\\_READ\\_UNABLE\\_FOR\\_SUPER\\_READ\\_ONLY](#) was added in 8.0.11, removed after 8.0.31.
  - Error number: [MY-011628](#); Symbol: [ER\\_GRP\\_RPL\\_READ\\_UNABLE\\_FOR\\_READ\\_ONLY\\_SUPER\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)  
Message: Unable to read the server values for the read\_only and super\_read\_only variables.

---

`ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER_READ_ONLY` was added in 8.0.11.

- Error number: `MY-011629`; Symbol: `ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE`; SQLSTATE: `HY000`

Message: Unable to reset the server read mode settings. Try to reset them manually.

`ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE` was added in 8.0.11.

- Error number: `MY-011630`; Symbol: `ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS`; SQLSTATE: `HY000`

Message: Due to a plugin error, some transactions were unable to be certified and will now rollback.

`ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS` was added in 8.0.11.

- Error number: `MY-011631`; Symbol: `ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS`; SQLSTATE: `HY000`

Message: Error when trying to unblock non certified or consistent transactions. Check for consistency errors when restarting the service

`ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS` was added in 8.0.11.

- Error number: `MY-011632`; Symbol: `ER_GRP_RPL_SERVER_WORKING_AS_SECONDARY`; SQLSTATE: `HY000`

Message: This server is working as secondary member with primary member address %s:%u.

`ER_GRP_RPL_SERVER_WORKING_AS_SECONDARY` was added in 8.0.11, removed after 8.0.20.

- Error number: `MY-011633`; Symbol: `ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID`; SQLSTATE: `HY000`

Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with `server_id=0`. Please, restart the server with `server_id` larger than 0.

`ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID` was added in 8.0.11.

- Error number: `MY-011634`; Symbol: `ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY`; SQLSTATE: `HY000`

Message: `group_replication_force_members` must be empty on group start. Current value: '%s'

`ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY` was added in 8.0.11.

- Error number: `MY-011635`; Symbol: `ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON_SERVER_START`; SQLSTATE: `HY000`

Message: It was not possible to guarantee the initialization of plugin structures on server start

`ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON_SERVER_START` was added in 8.0.11.

- Error number: `MY-011636`; Symbol: `ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE`; SQLSTATE: `HY000`

Message: Could not enable the server read only mode and guarantee a safe recovery execution

`ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE` was added in 8.0.11.

- 
- Error number: `MY-011637`; Symbol: `ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE`; SQLSTATE: `HY000`

Message: Error on group communication engine initialization

`ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE` was added in 8.0.11.

- Error number: `MY-011638`; Symbol: `ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH_ASYNC_CHANNELS`; SQLSTATE: `HY000`

Message: Can't start group replication on secondary member with single-primary mode while asynchronous replication channels are running.

`ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH_ASYNC_CHANNELS` was added in 8.0.11.

- Error number: `MY-011639`; Symbol: `ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE`; SQLSTATE: `HY000`

Message: Error on group communication engine start

`ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE` was added in 8.0.11.

- Error number: `MY-011640`; Symbol: `ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP`; SQLSTATE: `HY000`

Message: Timeout on wait for view after joining group

`ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP` was added in 8.0.11.

- Error number: `MY-011641`; Symbol: `ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_INTERFACE`; SQLSTATE: `HY000`

Message: Error calling group communication interfaces

`ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_INTERFACE` was added in 8.0.11.

- Error number: `MY-011642`; Symbol: `ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP`; SQLSTATE: `HY000`

Message: Member server\_uuid is incompatible with the group. Server\_uuid %s matches group\_replication\_group\_name %s.

`ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP` was added in 8.0.11.

- Error number: `MY-011643`; Symbol: `ER_GRP_RPL_MEMBER_CONF_INFO`; SQLSTATE: `HY000`

Message: Member configuration: member\_id: %lu; member\_uuid: "%s"; single-primary mode: "%s"; group\_replication\_auto\_increment\_increment: %lu; group\_replication\_view\_change\_uuid: "%s";

`ER_GRP_RPL_MEMBER_CONF_INFO` was added in 8.0.11.

- Error number: `MY-011644`; Symbol: `ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GRP`; SQLSTATE: `HY000`

Message: Unable to confirm whether the server has left the group or not. Check performance\_schema.replication\_group\_members to check group membership information.

`ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GRP` was added in 8.0.11.

- 
- Error number: [MY-011645](#); Symbol: [ER\\_GRP\\_RPL\\_SERVER\\_IS\\_ALREADY\\_LEAVING](#); SQLSTATE: [HY000](#)  
Message: Skipping leave operation: concurrent attempt to leave the group is on-going.  
[ER\\_GRP\\_RPL\\_SERVER\\_IS\\_ALREADY\\_LEAVING](#) was added in 8.0.11.
  - Error number: [MY-011646](#); Symbol: [ER\\_GRP\\_RPL\\_SERVER\\_ALREADY\\_LEFT](#); SQLSTATE: [HY000](#)  
Message: Skipping leave operation: member already left the group.  
[ER\\_GRP\\_RPL\\_SERVER\\_ALREADY\\_LEFT](#) was added in 8.0.11.
  - Error number: [MY-011647](#); Symbol: [ER\\_GRP\\_RPL\\_WAITING\\_FOR\\_VIEW\\_UPDATE](#); SQLSTATE: [HY000](#)  
Message: Going to wait for view modification  
[ER\\_GRP\\_RPL\\_WAITING\\_FOR\\_VIEW\\_UPDATE](#) was added in 8.0.11.
  - Error number: [MY-011648](#); Symbol: [ER\\_GRP\\_RPL\\_TIMEOUT\\_RECEIVING\\_VIEW\\_CHANGE\\_ON\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: While leaving the group due to a stop, shutdown or failure there was a timeout receiving a view change. This can lead to a possible inconsistent state. Check the log for more details  
[ER\\_GRP\\_RPL\\_TIMEOUT\\_RECEIVING\\_VIEW\\_CHANGE\\_ON\\_SHUTDOWN](#) was added in 8.0.11.
  - Error number: [MY-011649](#); Symbol: [ER\\_GRP\\_RPL\\_REQUESTING\\_NON\\_MEMBER\\_SERVER\\_TO\\_LEAVE](#); SQLSTATE: [HY000](#)  
Message: Requesting to leave the group despite of not being a member  
[ER\\_GRP\\_RPL\\_REQUESTING\\_NON\\_MEMBER\\_SERVER\\_TO\\_LEAVE](#) was added in 8.0.11.
  - Error number: [MY-011650](#); Symbol: [ER\\_GRP\\_RPL\\_IS\\_STOPPING](#); SQLSTATE: [HY000](#)  
Message: Plugin 'group\_replication' is stopping.  
[ER\\_GRP\\_RPL\\_IS\\_STOPPING](#) was added in 8.0.11.
  - Error number: [MY-011651](#); Symbol: [ER\\_GRP\\_RPL\\_IS\\_STOPPED](#); SQLSTATE: [HY000](#)  
Message: Plugin 'group\_replication' has been stopped.  
[ER\\_GRP\\_RPL\\_IS\\_STOPPED](#) was added in 8.0.11.
  - Error number: [MY-011652](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_ENABLE\\_READ\\_ONLY\\_MODE\\_ON\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: On plugin shutdown it was not possible to enable the server read only mode. Local transactions will be accepted and committed.  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_ENABLE\\_READ\\_ONLY\\_MODE\\_ON\\_SHUTDOWN](#) was added in 8.0.11.
  - Error number: [MY-011653](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_MODULE\\_TERMINATION\\_TIMED\\_OUT\\_ON\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: On shutdown there was a timeout on the Group Replication recovery module termination. Check the log for more details

---

`ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMED_OUT_ON_SHUTDOWN` was added in 8.0.11.

- Error number: `MY-011654`; Symbol:

`ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SHUTDOWN`; `SQLSTATE: HY000`

Message: On shutdown there was a timeout on the Group Replication applier termination.

`ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SHUTDOWN` was added in 8.0.11.

- Error number: `MY-011655`; Symbol: `ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE`; `SQLSTATE: HY000`

Message: Unexpected failure while shutting down registry module!

`ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE` was added in 8.0.11.

- Error number: `MY-011656`; Symbol: `ER_GRP_RPL_FAILED_TO_INIT_HANDLER`; `SQLSTATE: HY000`

Message: Failure during Group Replication handler initialization

`ER_GRP_RPL_FAILED_TO_INIT_HANDLER` was added in 8.0.11.

- Error number: `MY-011657`; Symbol:

`ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER`; `SQLSTATE: HY000`

Message: Failure when registering the server state observers

`ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER` was added in 8.0.11.

- Error number: `MY-011658`; Symbol:

`ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVER`; `SQLSTATE: HY000`

Message: Failure when registering the transactions state observers

`ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVER` was added in 8.0.11.

- Error number: `MY-011659`; Symbol:

`ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER`; `SQLSTATE: HY000`

Message: Failure when registering the binlog state observers

`ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER` was added in 8.0.11.

- Error number: `MY-011660`; Symbol: `ER_GRP_RPL_FAILED_TO_START_ON_BOOT`; `SQLSTATE: HY000`

Message: Unable to start Group Replication on boot

`ER_GRP_RPL_FAILED_TO_START_ON_BOOT` was added in 8.0.11.

- Error number: `MY-011661`; Symbol: `ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL`; `SQLSTATE: HY000`

Message: Failure when stopping Group Replication on plugin uninstall

`ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL` was added in 8.0.11.

- Error number: `MY-011662`; Symbol:

`ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER`; `SQLSTATE: HY000`

---

Message: Failure when unregistering the server state observers

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_UNREGISTER\\_SERVER\\_STATE\\_OBSERVER](#) was added in 8.0.11.

- Error number: [MY-011663](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_UNREGISTER\\_TRANS\\_STATE\\_OBSERVER](#); SQLSTATE: [HY000](#)

Message: Failure when unregistering the transactions state observers

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_UNREGISTER\\_TRANS\\_STATE\\_OBSERVER](#) was added in 8.0.11.

- Error number: [MY-011664](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_UNREGISTER\\_BINLOG\\_STATE\\_OBSERVER](#); SQLSTATE: [HY000](#)

Message: Failure when unregistering the binlog state observers

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_UNREGISTER\\_BINLOG\\_STATE\\_OBSERVER](#) was added in 8.0.11.

- Error number: [MY-011665](#); Symbol: [ER\\_GRP\\_RPL\\_ALL\\_OBSERVERS\\_UNREGISTERED](#); SQLSTATE: [HY000](#)

Message: All Group Replication server observers have been successfully unregistered

[ER\\_GRP\\_RPL\\_ALL\\_OBSERVERS\\_UNREGISTERED](#) was added in 8.0.11.

- Error number: [MY-011666](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_PARSE\\_THE\\_GRP\\_NAME](#); SQLSTATE: [HY000](#)

Message: Unable to parse the group\_replication\_group\_name.

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_PARSE\\_THE\\_GRP\\_NAME](#) was added in 8.0.11.

- Error number: [MY-011667](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_GENERATE\\_SIDNO\\_FOR\\_GRP](#); SQLSTATE: [HY000](#)

Message: Unable to parse the group\_replication\_group\_name.

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_GENERATE\\_SIDNO\\_FOR\\_GRP](#) was added in 8.0.11.

- Error number: [MY-011668](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_NOT\\_STARTED\\_DUE\\_TO\\_RUNNING\\_PREV\\_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Cannot start the Group Replication applier as a previous shutdown is still running: The thread will stop once its task is complete.

[ER\\_GRP\\_RPL\\_APPLIER\\_NOT\\_STARTED\\_DUE\\_TO\\_RUNNING\\_PREV\\_SHUTDOWN](#) was added in 8.0.11.

- Error number: [MY-011669](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INIT\\_APPLIER\\_MODULE](#); SQLSTATE: [HY000](#)

Message: Unable to initialize the Group Replication applier module.

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INIT\\_APPLIER\\_MODULE](#) was added in 8.0.11.

- 
- Error number: [MY-011670](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_INITIALIZED](#); SQLSTATE: [HY000](#)  
Message: Group Replication applier module successfully initialized!  
[ER\\_GRP\\_RPL\\_APPLIER\\_INITIALIZED](#) was added in 8.0.11.
  - Error number: [MY-011671](#); Symbol: [ER\\_GRP\\_RPL\\_COMMUNICATION\\_SSL\\_CONF\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Group communication SSL configuration: group\_replication\_ssl\_mode: "%s"; server\_key\_file: "%s"; server\_cert\_file: "%s"; client\_key\_file: "%s"; client\_cert\_file: "%s"; ca\_file: "%s"; ca\_path: "%s"; cipher: "%s"; tls\_version: "%s"; tls\_ciphersuites: "%s"; crl\_file: "%s"; crl\_path: "%s"; ssl\_fips\_mode: "%s"  
[ER\\_GRP\\_RPL\\_COMMUNICATION\\_SSL\\_CONF\\_INFO](#) was added in 8.0.11.
  - Error number: [MY-011672](#); Symbol: [ER\\_GRP\\_RPL\\_ABORTS\\_AS\\_SSL\\_NOT\\_SUPPORTEDED\\_BY\\_MYSQLD](#); SQLSTATE: [HY000](#)  
Message: MySQL server does not have SSL support and group\_replication\_ssl\_mode is "%s", START GROUP\_REPLICATION will abort  
[ER\\_GRP\\_RPL\\_ABORTS\\_AS\\_SSL\\_NOT\\_SUPPORTEDED\\_BY\\_MYSQLD](#) was added in 8.0.11.
  - Error number: [MY-011673](#); Symbol: [ER\\_GRP\\_RPL\\_SSL\\_DISABLED](#); SQLSTATE: [HY000](#)  
Message: Group communication SSL configuration: group\_replication\_ssl\_mode: "%s"  
[ER\\_GRP\\_RPL\\_SSL\\_DISABLED](#) was added in 8.0.11.
  - Error number: [MY-011674](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_INIT\\_COMMUNICATION\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: Unable to initialize the group communication engine  
[ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_INIT\\_COMMUNICATION\\_ENGINE](#) was added in 8.0.11.
  - Error number: [MY-011675](#); Symbol: [ER\\_GRP\\_RPL\\_BINLOG\\_DISABLED](#); SQLSTATE: [HY000](#)  
Message: Binlog must be enabled for Group Replication  
[ER\\_GRP\\_RPL\\_BINLOG\\_DISABLED](#) was added in 8.0.11.
  - Error number: [MY-011676](#); Symbol: [ER\\_GRP\\_RPL\\_GTID\\_MODE\\_OFF](#); SQLSTATE: [HY000](#)  
Message: Gtid mode should be ON for Group Replication  
[ER\\_GRP\\_RPL\\_GTID\\_MODE\\_OFF](#) was added in 8.0.11.
  - Error number: [MY-011677](#); Symbol: [ER\\_GRP\\_RPL\\_LOG\\_SLAVE\\_UPDATES\\_NOT\\_SET](#); SQLSTATE: [HY000](#)  
Message: LOG\_SLAVE\_UPDATES should be ON for Group Replication  
[ER\\_GRP\\_RPL\\_LOG\\_SLAVE\\_UPDATES\\_NOT\\_SET](#) was added in 8.0.11, removed after 8.0.25.
  - Error number: [MY-011677](#); Symbol: [ER\\_GRP\\_RPL\\_LOG\\_REPLICA\\_UPDATES\\_NOT\\_SET](#); SQLSTATE: [HY000](#)  
Message: LOG\_REPLICA\_UPDATES should be ON for Group Replication



---

`ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET` was added in 8.0.26.

- Error number: `MY-011678`; Symbol: `ER_GRP_RPL_INVALID_TRANS_WRITE_SET_EXTRACTION_VALUE`; SQLSTATE: `HY000`

Message: Extraction of transaction write sets requires an hash algorithm configuration. Please, double check that the parameter `transaction-write-set-extraction` is set to a valid algorithm.

`ER_GRP_RPL_INVALID_TRANS_WRITE_SET_EXTRACTION_VALUE` was added in 8.0.11.

- Error number: `MY-011679`; Symbol: `ER_GRP_RPL_RELAY_LOG_INFO_REPO_MUST_BE_TABLE`; SQLSTATE: `HY000`

Message: Relay log info repository must be set to TABLE

`ER_GRP_RPL_RELAY_LOG_INFO_REPO_MUST_BE_TABLE` was added in 8.0.11, removed after 8.0.32.

- Error number: `MY-011679`; Symbol: `ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_TABLE`; SQLSTATE: `HY000`

Message: Applier metadata repository must be set to TABLE

`ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_TABLE` was added in 8.0.33.

- Error number: `MY-011680`; Symbol: `ER_GRP_RPL_MASTER_INFO_REPO_MUST_BE_TABLE`; SQLSTATE: `HY000`

Message: Master info repository must be set to TABLE.

`ER_GRP_RPL_MASTER_INFO_REPO_MUST_BE_TABLE` was added in 8.0.11, removed after 8.0.32.

- Error number: `MY-011680`; Symbol: `ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_TABLE`; SQLSTATE: `HY000`

Message: Connection metadata repository must be set to TABLE.

`ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_TABLE` was added in 8.0.33.

- Error number: `MY-011681`; Symbol: `ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_APPLIER`; SQLSTATE: `HY000`

Message: In order to use parallel applier on Group Replication, parameter `replica-parallel-type` must be set to 'LOGICAL\_CLOCK'.

`ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_APPLIER` was added in 8.0.11.

- Error number: `MY-011682`; Symbol: `ER_GRP_RPL_SLAVE_PRESERVE_COMMIT_ORDER_NOT_SET`; SQLSTATE: `HY000`

Message: Group Replication requires `slave-preserve-commit-order` to be set to ON when using more than 1 applier threads.

`ER_GRP_RPL_SLAVE_PRESERVE_COMMIT_ORDER_NOT_SET` was added in 8.0.11, removed after 8.0.25.

- Error number: `MY-011682`; Symbol: `ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT_SET`; SQLSTATE: `HY000`

---

Message: Group Replication requires replica-preserve-commit-order to be set to ON when using more than 1 applier threads.

[ER\\_GRP\\_RPL\\_REPLICA\\_PRESERVE\\_COMMIT\\_ORDER\\_NOT\\_SET](#) was added in 8.0.26.

- Error number: MY-011683; Symbol:

[ER\\_GRP\\_RPL\\_SINGLE\\_PRIM\\_MODE\\_NOT\\_ALLOWED\\_WITH\\_UPDATE\\_EVERYWHERE](#); SQLSTATE: HY000

Message: It is not allowed to run single primary mode with 'group\_replication\_enforce\_update\_everywhere\_checks' enabled.

[ER\\_GRP\\_RPL\\_SINGLE\\_PRIM\\_MODE\\_NOT\\_ALLOWED\\_WITH\\_UPDATE\\_EVERYWHERE](#) was added in 8.0.11.

- Error number: MY-011684; Symbol: [ER\\_GRP\\_RPL\\_MODULE\\_TERMINATE\\_ERROR](#); SQLSTATE: HY000

Message: error\_message: %s

[ER\\_GRP\\_RPL\\_MODULE\\_TERMINATE\\_ERROR](#) was added in 8.0.11.

- Error number: MY-011685; Symbol: [ER\\_GRP\\_RPL\\_GRP\\_NAME\\_OPTION\\_MANDATORY](#); SQLSTATE: HY000

Message: The group\_replication\_group\_name option is mandatory

[ER\\_GRP\\_RPL\\_GRP\\_NAME\\_OPTION\\_MANDATORY](#) was added in 8.0.11.

- Error number: MY-011686; Symbol: [ER\\_GRP\\_RPL\\_GRP\\_NAME\\_IS\\_TOO\\_LONG](#); SQLSTATE: HY000

Message: The group\_replication\_group\_name '%s' is not a valid UUID, its length is too big

[ER\\_GRP\\_RPL\\_GRP\\_NAME\\_IS\\_TOO\\_LONG](#) was added in 8.0.11.

- Error number: MY-011687; Symbol: [ER\\_GRP\\_RPL\\_GRP\\_NAME\\_IS\\_NOT\\_VALID\\_UUID](#); SQLSTATE: HY000

Message: The group\_replication\_group\_name '%s' is not a valid UUID

[ER\\_GRP\\_RPL\\_GRP\\_NAME\\_IS\\_NOT\\_VALID\\_UUID](#) was added in 8.0.11.

- Error number: MY-011688; Symbol:

[ER\\_GRP\\_RPL\\_FLOW\\_CTRL\\_MIN\\_QUOTA\\_GREATER\\_THAN\\_MAX\\_QUOTA](#); SQLSTATE: HY000

Message: group\_replication\_flow\_control\_min\_quota cannot be larger than group\_replication\_flow\_control\_max\_quota

[ER\\_GRP\\_RPL\\_FLOW\\_CTRL\\_MIN\\_QUOTA\\_GREATER\\_THAN\\_MAX\\_QUOTA](#) was added in 8.0.11.

- Error number: MY-011689; Symbol:

[ER\\_GRP\\_RPL\\_FLOW\\_CTRL\\_MIN\\_RECOVERY\\_QUOTA\\_GREATER\\_THAN\\_MAX\\_QUOTA](#); SQLSTATE: HY000

Message: group\_replication\_flow\_control\_min\_recovery\_quota cannot be larger than group\_replication\_flow\_control\_max\_quota

[ER\\_GRP\\_RPL\\_FLOW\\_CTRL\\_MIN\\_RECOVERY\\_QUOTA\\_GREATER\\_THAN\\_MAX\\_QUOTA](#) was added in 8.0.11.

- 
- Error number: [MY-011690](#); Symbol: [ER\\_GRP\\_RPL\\_FLOW\\_CTRL\\_MAX\\_QUOTA\\_SMALLER\\_THAN\\_MIN\\_QUOTAS](#); SQLSTATE: [HY000](#)  
Message: group\_replication\_flow\_control\_max\_quota cannot be smaller than group\_replication\_flow\_control\_min\_quota or group\_replication\_flow\_control\_min\_recovery\_quota  
[ER\\_GRP\\_RPL\\_FLOW\\_CTRL\\_MAX\\_QUOTA\\_SMALLER\\_THAN\\_MIN\\_QUOTAS](#) was added in 8.0.11.
  - Error number: [MY-011691](#); Symbol: [ER\\_GRP\\_RPL\\_INVALID\\_SSL\\_RECOVERY\\_STRING](#); SQLSTATE: [HY000](#)  
Message: The given value for recovery ssl option 'group\_replication\_%s' is invalid as its length is beyond the limit  
[ER\\_GRP\\_RPL\\_INVALID\\_SSL\\_RECOVERY\\_STRING](#) was added in 8.0.11.
  - Error number: [MY-011692](#); Symbol: [ER\\_GRP\\_RPL\\_SUPPORTS\\_ONLY\\_ONE\\_FORCE\\_MEMBERS\\_SET](#); SQLSTATE: [HY000](#)  
Message: There is one group\_replication\_force\_members operation already ongoing  
[ER\\_GRP\\_RPL\\_SUPPORTS\\_ONLY\\_ONE\\_FORCE\\_MEMBERS\\_SET](#) was added in 8.0.11, removed after 8.0.30.
  - Error number: [MY-011693](#); Symbol: [ER\\_GRP\\_RPL\\_FORCE\\_MEMBERS\\_SET\\_UPDATE\\_NOT\\_ALLOWED](#); SQLSTATE: [HY000](#)  
Message: group\_replication\_force\_members can only be updated when Group Replication is running and a majority of the members are unreachable  
[ER\\_GRP\\_RPL\\_FORCE\\_MEMBERS\\_SET\\_UPDATE\\_NOT\\_ALLOWED](#) was added in 8.0.11, removed after 8.0.30.
  - Error number: [MY-011694](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_COMMUNICATION\\_INIT\\_WITH\\_CONF](#); SQLSTATE: [HY000](#)  
Message: Initialized group communication with configuration: group\_replication\_group\_name: '%s'; group\_replication\_local\_address: '%s'; group\_replication\_group\_seeds: '%s'; group\_replication\_bootstrap\_group: '%s'; group\_replication\_poll\_spin\_loops: %lu; group\_replication\_compression\_threshold: %lu; group\_replication\_ip\_allowlist: '%s'; group\_replication\_communication\_debug\_options: '%s'; group\_replication\_member\_expel\_timeout: '%lu'; group\_replication\_communication\_max\_message\_size: %lu; group\_replication\_message\_cache\_size: '%luu'; group\_replication\_communication\_stack: '%lu'  
[ER\\_GRP\\_RPL\\_GRP\\_COMMUNICATION\\_INIT\\_WITH\\_CONF](#) was added in 8.0.11.
  - Error number: [MY-011695](#); Symbol: [ER\\_GRP\\_RPL\\_UNKNOWN\\_GRP\\_RPL\\_APPLIER\\_PIPELINE\\_REQUESTED](#); SQLSTATE: [HY000](#)  
Message: Unknown group replication applier pipeline requested  
[ER\\_GRP\\_RPL\\_UNKNOWN\\_GRP\\_RPL\\_APPLIER\\_PIPELINE\\_REQUESTED](#) was added in 8.0.11.
  - Error number: [MY-011696](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_BOOTSTRAP\\_EVENT\\_HANDLING\\_INFRASTRUCTURE](#); SQLSTATE: [HY000](#)  
Message: Unable to bootstrap group replication event handling infrastructure. Unknown handler type: %d
-

---

`ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING_INFRASTRUCTURE` was added in 8.0.11.

- Error number: `MY-011697`; Symbol: `ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED`; SQLSTATE: `HY000`

Message: One of the group replication applier handlers is null due to an initialization error

`ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED` was added in 8.0.11.

- Error number: `MY-011698`; Symbol: `ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE`; SQLSTATE: `HY000`

Message: A group replication applier handler, marked as unique, is already in use.

`ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE` was added in 8.0.11.

- Error number: `MY-011699`; Symbol: `ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE`; SQLSTATE: `HY000`

Message: A group replication applier handler role, that was marked as unique, is already in use.

`ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE` was added in 8.0.11.

- Error number: `MY-011700`; Symbol: `ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER`; SQLSTATE: `HY000`

Message: Error on group replication applier handler initialization

`ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER` was added in 8.0.11.

- Error number: `MY-011701`; Symbol: `ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_THREAD`; SQLSTATE: `HY000`

Message: Error when initializing a session thread for internal server connection.

`ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_THREAD` was added in 8.0.11.

- Error number: `MY-011702`; Symbol: `ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED`; SQLSTATE: `HY000`

Message: Error running internal SQL query: %s. The internal server communication session is not initialized

`ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED` was added in 8.0.11.

- Error number: `MY-011703`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED`; SQLSTATE: `HY000`

Message: Error running internal SQL query: %s. The internal server session was killed or server is shutting down.

`ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED` was added in 8.0.11.

- Error number: `MY-011704`; Symbol: `ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY`; SQLSTATE: `HY000`

Message: Error running internal SQL query: %s. Got internal SQL error: %s(%d)

---

`ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY` was added in 8.0.11.

- Error number: `MY-011705`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE`; SQLSTATE: `HY000`

Message: Error running internal SQL query: %s. Internal failure.

`ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE` was added in 8.0.11.

- Error number: `MY-011706`; Symbol: `ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION_STATE`; SQLSTATE: `HY000`

Message: Error, maximum number of retries exceeded when waiting for the internal server session state to be operating

`ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION_STATE` was added in 8.0.11.

- Error number: `MY-011707`; Symbol: `ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECURITY_CTX`; SQLSTATE: `HY000`

Message: Error when trying to fetch security context when contacting the server for internal plugin requests.

`ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECURITY_CTX` was added in 8.0.11.

- Error number: `MY-011708`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER`; SQLSTATE: `HY000`

Message: There was an error when trying to access the server with user: %s. Make sure the user is present in the server and that the MySQL upgrade procedure was run correctly.

`ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER` was added in 8.0.11.

- Error number: `MY-011709`; Symbol: `ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER`; SQLSTATE: `HY000`

Message: Failed to establish an internal server connection to execute plugin operations since the server does not have available connections, please increase @@GLOBAL.MAX\_CONNECTIONS. Server error: %i.

`ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER` was added in 8.0.11.

- Error number: `MY-011710`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN`; SQLSTATE: `HY000`

Message: Failed to establish an internal server connection to execute plugin operations. Server error: %i. Server error message: %s

`ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN` was added in 8.0.11.

- 
- Error number: `MY-011711`; Symbol: `ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_MEMBER`; `SQLSTATE: HY000`  
Message: This member could not reach a majority of the members for more than %ld seconds. The member will now leave the group as instructed by the `group_replication_unreachable_majority_timeout` option.  
`ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_MEMBER` was added in 8.0.11.
  - Error number: `MY-011712`; Symbol: `ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERRORS`; `SQLSTATE: HY000`  
Message: The server was automatically set into read only mode after an error was detected.  
`ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERRORS` was added in 8.0.11.
  - Error number: `MY-011713`; Symbol: `ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION`; `SQLSTATE: HY000`  
Message: Unable to log notification to table (errno: %lu) (res: %d)! Message: %s  
`ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION` was added in 8.0.11.
  - Error number: `MY-011714`; Symbol: `ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED`; `SQLSTATE: HY000`  
Message: Failure in group communication engine '%s' initialization  
`ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED` was added in 8.0.11.
  - Error number: `MY-011715`; Symbol: `ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER_FAILED`; `SQLSTATE: HY000`  
Message: Unable to set the group communication engine logger  
`ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER_FAILED` was added in 8.0.11.
  - Error number: `MY-011716`; Symbol: `ER_GRP_RPL_DEBUG_OPTIONS`; `SQLSTATE: HY000`  
Message: Current debug options are: '%s'.  
`ER_GRP_RPL_DEBUG_OPTIONS` was added in 8.0.11.
  - Error number: `MY-011717`; Symbol: `ER_GRP_RPL_INVALID_DEBUG_OPTIONS`; `SQLSTATE: HY000`  
Message: Some debug options in '%s' are not valid.  
`ER_GRP_RPL_INVALID_DEBUG_OPTIONS` was added in 8.0.11.
  - Error number: `MY-011718`; Symbol: `ER_GRP_RPL_EXIT_GRP_GCS_ERROR`; `SQLSTATE: HY000`  
Message: Error calling group communication interfaces while trying to leave the group  
`ER_GRP_RPL_EXIT_GRP_GCS_ERROR` was added in 8.0.11.

- 
- Error number: [MY-011719](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_MEMBER\\_OFFLINE](#); SQLSTATE: [HY000](#)  
Message: Member is not ONLINE, it is not possible to force a new group membership  
[ER\\_GRP\\_RPL\\_GRP\\_MEMBER\\_OFFLINE](#) was added in 8.0.11.
  - Error number: [MY-011720](#); Symbol: [ER\\_GRP\\_RPL\\_GCS\\_INTERFACE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error calling group communication interfaces  
[ER\\_GRP\\_RPL\\_GCS\\_INTERFACE\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011721](#); Symbol: [ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_SET\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error setting group\_replication\_force\_members value '%s' on group communication interfaces  
[ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_SET\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011722](#); Symbol: [ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_SET](#); SQLSTATE: [HY000](#)  
Message: The group\_replication\_force\_members value '%s' was set in the group communication interfaces  
[ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_SET](#) was added in 8.0.11.
  - Error number: [MY-011723](#); Symbol: [ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_TIME\\_OUT](#); SQLSTATE: [HY000](#)  
Message: Timeout on wait for view after setting group\_replication\_force\_members value '%s' into group communication interfaces  
[ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_TIME\\_OUT](#) was added in 8.0.11.
  - Error number: [MY-011724](#); Symbol: [ER\\_GRP\\_RPL\\_BROADCAST\\_COMMIT\\_MSSG\\_TOO\\_BIG](#); SQLSTATE: [HY000](#)  
Message: Broadcast of committed transactions message failed. Message is too big.  
[ER\\_GRP\\_RPL\\_BROADCAST\\_COMMIT\\_MSSG\\_TOO\\_BIG](#) was added in 8.0.11.
  - Error number: [MY-011725](#); Symbol: [ER\\_GRP\\_RPL\\_SEND\\_STATS\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error while sending stats message  
[ER\\_GRP\\_RPL\\_SEND\\_STATS\\_ERROR](#) was added in 8.0.11.
  - Error number: [MY-011726](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_STATS\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Flow control - update member stats: %s stats certifier\_queue %d, applier\_queue %d certified %ld (%ld), applied %ld (%ld), local %ld (%ld), quota %ld (%ld) mode=%d  
[ER\\_GRP\\_RPL\\_MEMBER\\_STATS\\_INFO](#) was added in 8.0.11.

- 
- Error number: `MY-011727`; Symbol: `ER_GRP_RPL_FLOW_CONTROL_STATS`; SQLSTATE: `HY000`  
Message: Flow control: throttling to %ld commits per %ld sec, with %d writing and %d non-recovering members, min capacity %lld, lim throttle %lld  
`ER_GRP_RPL_FLOW_CONTROL_STATS` was added in 8.0.11.
  - Error number: `MY-011728`; Symbol: `ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT`; SQLSTATE: `HY000`  
Message: Unable to convert a packet into an event on the applier. Error: %s  
`ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT` was added in 8.0.11.
  - Error number: `MY-011729`; Symbol: `ER_GRP_RPL_PIPELINE_CREATE_FAILED`; SQLSTATE: `HY000`  
Message: Failed to create group replication pipeline cache.  
`ER_GRP_RPL_PIPELINE_CREATE_FAILED` was added in 8.0.11.
  - Error number: `MY-011730`; Symbol: `ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE`; SQLSTATE: `HY000`  
Message: Failed to reinit group replication pipeline cache for write.  
`ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE` was added in 8.0.11.
  - Error number: `MY-011731`; Symbol: `ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET`; SQLSTATE: `HY000`  
Message: Unable to convert the event into a packet on the applier. Error: %s  
`ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET` was added in 8.0.11.
  - Error number: `MY-011732`; Symbol: `ER_GRP_RPL_PIPELINE_FLUSH_FAIL`; SQLSTATE: `HY000`  
Message: Failed to flush group replication pipeline cache.  
`ER_GRP_RPL_PIPELINE_FLUSH_FAIL` was added in 8.0.11.
  - Error number: `MY-011733`; Symbol: `ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ`; SQLSTATE: `HY000`  
Message: Failed to reinit group replication pipeline cache for read.  
`ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ` was added in 8.0.11.
  - Error number: `MY-011734`; Symbol: `ER_GRP_RPL_STOP_REP_CHANNEL`; SQLSTATE: `HY000`  
Message: Error stopping all replication channels while server was leaving the group. Got error: %d. Please check the error log for more details.  
`ER_GRP_RPL_STOP_REP_CHANNEL` was added in 8.0.11, removed after 8.0.17.
  - Error number: `MY-011735`; Symbol: `ER_GRP_RPL_GCS_GR_ERROR_MSG`; SQLSTATE: `HY000`  
Message: %s  
`ER_GRP_RPL_GCS_GR_ERROR_MSG` was added in 8.0.11.



- 
- Error number: [MY-011736](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_IO\\_THREAD\\_UNBLOCKED](#); SQLSTATE: [HY000](#)  
  
Message: The slave IO thread of channel '%s' is unblocked as the member is declared ONLINE now.  
  
[ER\\_GRP\\_RPL\\_SLAVE\\_IO\\_THREAD\\_UNBLOCKED](#) was added in 8.0.11, removed after 8.0.32.
  - Error number: [MY-011736](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_IO\\_THREAD\\_UNBLOCKED](#); SQLSTATE: [HY000](#)  
  
Message: The replica IO thread of channel '%s' is unblocked as the member is declared ONLINE now.  
  
[ER\\_GRP\\_RPL\\_REPLICA\\_IO\\_THREAD\\_UNBLOCKED](#) was added in 8.0.33.
  - Error number: [MY-011737](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_IO\\_THREAD\\_ERROR\\_OUT](#); SQLSTATE: [HY000](#)  
  
Message: The slave IO thread of channel '%s' will error out as the member failed to come ONLINE.  
  
[ER\\_GRP\\_RPL\\_SLAVE\\_IO\\_THREAD\\_ERROR\\_OUT](#) was added in 8.0.11, removed after 8.0.32.
  - Error number: [MY-011737](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_IO\\_THREAD\\_ERROR\\_OUT](#); SQLSTATE: [HY000](#)  
  
Message: The replica IO thread of channel '%s' will error out as the member failed to come ONLINE.  
  
[ER\\_GRP\\_RPL\\_REPLICA\\_IO\\_THREAD\\_ERROR\\_OUT](#) was added in 8.0.33.
  - Error number: [MY-011738](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_APPLIER\\_THREAD\\_UNBLOCKED](#); SQLSTATE: [HY000](#)  
  
Message: The slave applier thread of channel '%s' is unblocked as the member is declared ONLINE now.  
  
[ER\\_GRP\\_RPL\\_SLAVE\\_APPLIER\\_THREAD\\_UNBLOCKED](#) was added in 8.0.11, removed after 8.0.32.
  - Error number: [MY-011738](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_APPLIER\\_THREAD\\_UNBLOCKED](#); SQLSTATE: [HY000](#)  
  
Message: The replica applier thread of channel '%s' is unblocked as the member is declared ONLINE now.  
  
[ER\\_GRP\\_RPL\\_REPLICA\\_APPLIER\\_THREAD\\_UNBLOCKED](#) was added in 8.0.33.
  - Error number: [MY-011739](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_APPLIER\\_THREAD\\_ERROR\\_OUT](#); SQLSTATE: [HY000](#)  
  
Message: The slave applier thread of channel '%s' will error out as the member failed to come ONLINE.  
  
[ER\\_GRP\\_RPL\\_SLAVE\\_APPLIER\\_THREAD\\_ERROR\\_OUT](#) was added in 8.0.11, removed after 8.0.32.
  - Error number: [MY-011739](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_APPLIER\\_THREAD\\_ERROR\\_OUT](#); SQLSTATE: [HY000](#)  
  
Message: The replica applier thread of channel '%s' will error out as the member failed to come ONLINE.  
  
[ER\\_GRP\\_RPL\\_REPLICA\\_APPLIER\\_THREAD\\_ERROR\\_OUT](#) was added in 8.0.33.
-

- 
- Error number: [MY-011740](#); Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_CREATE\\_OR\\_GET\\_CONNECTION](#); SQLSTATE: [HY000](#)  
  
Message: LDAP authentication initialize: failed to create/ get connection from the pool.  
  
[ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_CREATE\\_OR\\_GET\\_CONNECTION](#) was added in 8.0.11.
  - Error number: [MY-011741](#); Symbol: [ER\\_LDAP\\_AUTH\\_DEINIT\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: LDAP authentication de\_initialize Failed  
  
[ER\\_LDAP\\_AUTH\\_DEINIT\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011742](#); Symbol: [ER\\_LDAP\\_AUTH\\_SKIPPING\\_USER\\_GROUP\\_SEARCH](#); SQLSTATE: [HY000](#)  
  
Message: Skipping group search, No group attribute mentioned  
  
[ER\\_LDAP\\_AUTH\\_SKIPPING\\_USER\\_GROUP\\_SEARCH](#) was added in 8.0.11.
  - Error number: [MY-011743](#); Symbol: [ER\\_LDAP\\_AUTH\\_POOL\\_DISABLE\\_MAX\\_SIZE\\_ZERO](#); SQLSTATE: [HY000](#)  
  
Message: Pool max size is 0, connection pool is disabled  
  
[ER\\_LDAP\\_AUTH\\_POOL\\_DISABLE\\_MAX\\_SIZE\\_ZERO](#) was added in 8.0.11.
  - Error number: [MY-011744](#); Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_CREATE\\_LDAP\\_OBJECT\\_CREATOR](#); SQLSTATE: [HY000](#)  
  
Message: Connection pool initialization, failed to create LDAP object creator  
  
[ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_CREATE\\_LDAP\\_OBJECT\\_CREATOR](#) was added in 8.0.11.
  - Error number: [MY-011745](#); Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_CREATE\\_LDAP\\_OBJECT](#); SQLSTATE: [HY000](#)  
  
Message: Connection pool initialization, failed to create LDAP object  
  
[ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_CREATE\\_LDAP\\_OBJECT](#) was added in 8.0.11.
  - Error number: [MY-011746](#); Symbol: [ER\\_LDAP\\_AUTH\\_TLS\\_CONF](#); SQLSTATE: [HY000](#)  
  
Message: LDAP TLS configuration  
  
[ER\\_LDAP\\_AUTH\\_TLS\\_CONF](#) was added in 8.0.11.
  - Error number: [MY-011747](#); Symbol: [ER\\_LDAP\\_AUTH\\_TLS\\_CONNECTION](#); SQLSTATE: [HY000](#)  
  
Message: LDAP TLS connection  
  
[ER\\_LDAP\\_AUTH\\_TLS\\_CONNECTION](#) was added in 8.0.11.
  - Error number: [MY-011748](#); Symbol: [ER\\_LDAP\\_AUTH\\_CONN\\_POOL\\_NOT\\_CREATED](#); SQLSTATE: [HY000](#)  
  
Message: LDAP pool is not created.

- 
- Error number: `MY-011749`; Symbol: `ER_LDAP_AUTH_CONN_POOL_INITIALIZING`; SQLSTATE: `HY000`  
  
Message: LDAP pool is initializing  
  
`ER_LDAP_AUTH_CONN_POOL_INITIALIZING` was added in 8.0.11.
  - Error number: `MY-011750`; Symbol: `ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING`; SQLSTATE: `HY000`  
  
Message: LDAP pool is de-initializing  
  
`ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING` was added in 8.0.11.
  - Error number: `MY-011751`; Symbol: `ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED`; SQLSTATE: `HY000`  
  
Message: Pool max size old and new values are 0  
  
`ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED` was added in 8.0.11.
  - Error number: `MY-011752`; Symbol: `ER_LDAP_AUTH_POOL_REINITIALIZING`; SQLSTATE: `HY000`  
  
Message: LDAP pool is re-initializing  
  
`ER_LDAP_AUTH_POOL_REINITIALIZING` was added in 8.0.11.
  - Error number: `MY-011753`; Symbol: `ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET`; SQLSTATE: `HY000`  
  
Message: Plug-in has failed to write the packet.  
  
`ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET` was added in 8.0.11.
  - Error number: `MY-011754`; Symbol: `ER_LDAP_AUTH_SETTING_USERNAME`; SQLSTATE: `HY000`  
  
Message: Setting LDAP user name as : %s  
  
`ER_LDAP_AUTH_SETTING_USERNAME` was added in 8.0.11.
  - Error number: `MY-011755`; Symbol: `ER_LDAP_AUTH_USER_AUTH_DATA`; SQLSTATE: `HY000`  
  
Message: User authentication data: %s size: %lu  
  
`ER_LDAP_AUTH_USER_AUTH_DATA` was added in 8.0.11.
  - Error number: `MY-011756`; Symbol: `ER_LDAP_AUTH_INFO_FOR_USER`; SQLSTATE: `HY000`  
  
Message: User is authenticated as: %s external user: %s  
  
`ER_LDAP_AUTH_INFO_FOR_USER` was added in 8.0.11.
  - Error number: `MY-011757`; Symbol: `ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO`; SQLSTATE: `HY000`  
  
Message: Group search information base DN: %s scope: %d filter: %s attribute: %s  
  
`ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO` was added in 8.0.11.

- 
- Error number: `MY-011758`; Symbol: `ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL`; SQLSTATE: `HY000`  
Message: Special handling for group search, {GA} found  
`ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL` was added in 8.0.11.
  - Error number: `MY-011759`; Symbol: `ER_LDAP_AUTH_GRP_IS_FULL_DN`; SQLSTATE: `HY000`  
Message: Group search special handling, group full DN found.  
`ER_LDAP_AUTH_GRP_IS_FULL_DN` was added in 8.0.11.
  - Error number: `MY-011760`; Symbol: `ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP`; SQLSTATE: `HY000`  
Message: User %s is not member of any group.  
`ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP` was added in 8.0.11.
  - Error number: `MY-011761`; Symbol: `ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS`; SQLSTATE: `HY000`  
Message: User %s is member of more than one group  
`ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS` was added in 8.0.11.
  - Error number: `MY-011762`; Symbol: `ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES`; SQLSTATE: `HY000`  
Message: For user %s has multiple user group names. Please check if group attribute name is correct  
`ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES` was added in 8.0.11.
  - Error number: `MY-011763`; Symbol: `ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME`; SQLSTATE: `HY000`  
Message: Searched group name: %s  
`ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME` was added in 8.0.11.
  - Error number: `MY-011764`; Symbol: `ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP`; SQLSTATE: `HY000`  
Message: LDAP authentication object creation time\_stamp: %s dn: %s  
`ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP` was added in 8.0.11.
  - Error number: `MY-011765`; Symbol: `ER_LDAP_AUTH_CERTIFICATE_NAME`; SQLSTATE: `HY000`  
Message: Certificate name: %s  
`ER_LDAP_AUTH_CERTIFICATE_NAME` was added in 8.0.11.
  - Error number: `MY-011766`; Symbol: `ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT`; SQLSTATE: `HY000`  
Message: Failed to pool de-initialized: pool is already reconstructing  
`ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT` was added in 8.0.11.

- 
- Error number: [MY-011767](#); Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_INITIALIZE\\_POOL\\_IN\\_RECONSTRUCTING](#); SQLSTATE: [HY000](#)  
Message: Pool initialization failed: pool is already initialized  
[ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_INITIALIZE\\_POOL\\_IN\\_RECONSTRUCTING](#) was added in 8.0.11.
  - Error number: [MY-011768](#); Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_INITIALIZE\\_POOL\\_IN\\_INIT\\_STATE](#); SQLSTATE: [HY000](#)  
Message: Pool initialization failed: pool is initializing  
[ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_INITIALIZE\\_POOL\\_IN\\_INIT\\_STATE](#) was added in 8.0.11.
  - Error number: [MY-011769](#); Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_INITIALIZE\\_POOL\\_IN\\_DEINIT\\_STATE](#); SQLSTATE: [HY000](#)  
Message: Pool initialization failed: pool is de-initializing  
[ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_INITIALIZE\\_POOL\\_IN\\_DEINIT\\_STATE](#) was added in 8.0.11.
  - Error number: [MY-011770](#); Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_DEINITIALIZE\\_POOL\\_IN\\_RECONSTRUCT\\_STATE](#); SQLSTATE: [HY000](#)  
Message: Failed to pool deinitialized: pool is already reconstructing  
[ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_DEINITIALIZE\\_POOL\\_IN\\_RECONSTRUCT\\_STATE](#) was added in 8.0.11.
  - Error number: [MY-011771](#); Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_DEINITIALIZE\\_NOT\\_READY\\_POOL](#); SQLSTATE: [HY000](#)  
Message: Failed to pool deinitialized : pool is not ready  
[ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_DEINITIALIZE\\_NOT\\_READY\\_POOL](#) was added in 8.0.11.
  - Error number: [MY-011772](#); Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_GET\\_CONNECTION\\_AS\\_PLUGIN\\_NOT\\_READY](#); SQLSTATE: [HY000](#)  
Message: Ldap\_connection\_pool::get: Failed to return connection as plug-in is not ready/initializing/de-initializing  
[ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_GET\\_CONNECTION\\_AS\\_PLUGIN\\_NOT\\_READY](#) was added in 8.0.11.
  - Error number: [MY-011773](#); Symbol: [ER\\_LDAP\\_AUTH\\_CONNECTION\\_POOL\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Connection pool has failed to initialized  
[ER\\_LDAP\\_AUTH\\_CONNECTION\\_POOL\\_INIT\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011774](#); Symbol: [ER\\_LDAP\\_AUTH\\_MAX\\_ALLOWED\\_CONNECTION\\_LIMIT\\_HIT](#); SQLSTATE: [HY000](#)  
Message: Ldap\_connetion\_pool::get LDAP maximum connection allowed size is reached. Increase the maximum limit.  
[ER\\_LDAP\\_AUTH\\_MAX\\_ALLOWED\\_CONNECTION\\_LIMIT\\_HIT](#) was added in 8.0.11.
-

- 
- Error number: [MY-011775](#); Symbol: [ER\\_LDAP\\_AUTH\\_MAX\\_POOL\\_SIZE\\_SET\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Set max pool size failed.  
  
[ER\\_LDAP\\_AUTH\\_MAX\\_POOL\\_SIZE\\_SET\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011776](#); Symbol: [ER\\_LDAP\\_AUTH\\_PLUGIN\\_FAILED\\_TO\\_READ\\_PACKET](#); SQLSTATE: [HY000](#)  
  
Message: Plug-in has failed to read the packet from client  
  
[ER\\_LDAP\\_AUTH\\_PLUGIN\\_FAILED\\_TO\\_READ\\_PACKET](#) was added in 8.0.11.
  - Error number: [MY-011777](#); Symbol: [ER\\_LDAP\\_AUTH\\_CREATING\\_LDAP\\_CONNECTION](#); SQLSTATE: [HY000](#)  
  
Message: Ldap\_authentication::initialize: creating new LDAP connection.  
  
[ER\\_LDAP\\_AUTH\\_CREATING\\_LDAP\\_CONNECTION](#) was added in 8.0.11.
  - Error number: [MY-011778](#); Symbol: [ER\\_LDAP\\_AUTH\\_GETTING\\_CONNECTION\\_FROM\\_POOL](#); SQLSTATE: [HY000](#)  
  
Message: Ldap\_authentication::initialize: getting connection from pool.  
  
[ER\\_LDAP\\_AUTH\\_GETTING\\_CONNECTION\\_FROM\\_POOL](#) was added in 8.0.11.
  - Error number: [MY-011779](#); Symbol: [ER\\_LDAP\\_AUTH\\_RETURNING\\_CONNECTION\\_TO\\_POOL](#); SQLSTATE: [HY000](#)  
  
Message: Ldap\_authentication::de\_initialize putting back connection in the pool  
  
[ER\\_LDAP\\_AUTH\\_RETURNING\\_CONNECTION\\_TO\\_POOL](#) was added in 8.0.11.
  - Error number: [MY-011780](#); Symbol: [ER\\_LDAP\\_AUTH\\_SEARCH\\_USER\\_GROUP\\_ATTR\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
  
Message: Ldap\_authentication::search\_user\_group no group attribute found  
  
[ER\\_LDAP\\_AUTH\\_SEARCH\\_USER\\_GROUP\\_ATTR\\_NOT\\_FOUND](#) was added in 8.0.11.
  - Error number: [MY-011781](#); Symbol: [ER\\_LDAP\\_AUTH\\_LDAP\\_INFO\\_NULL](#); SQLSTATE: [HY000](#)  
  
Message: Ldap\_connection\_pool::put ldap info null  
  
[ER\\_LDAP\\_AUTH\\_LDAP\\_INFO\\_NULL](#) was added in 8.0.11.
  - Error number: [MY-011782](#); Symbol: [ER\\_LDAP\\_AUTH\\_FREEING\\_CONNECTION](#); SQLSTATE: [HY000](#)  
  
Message: Ldap\_connection\_pool::put connection is freeing.  
  
[ER\\_LDAP\\_AUTH\\_FREEING\\_CONNECTION](#) was added in 8.0.11.

- 
- Error number: [MY-011783](#); Symbol: [ER\\_LDAP\\_AUTH\\_CONNECTION\\_PUSHED\\_TO\\_POOL](#); SQLSTATE: [HY000](#)  
  
Message: Ldap\_connection\_pool::put connection in pushed in the pool  
  
[ER\\_LDAP\\_AUTH\\_CONNECTION\\_PUSHED\\_TO\\_POOL](#) was added in 8.0.11.
  - Error number: [MY-011784](#); Symbol: [ER\\_LDAP\\_AUTH\\_CONNECTION\\_CREATOR\\_ENTER](#); SQLSTATE: [HY000](#)  
  
Message: Ldap\_connection\_creator::Ldap\_connection\_creator  
  
[ER\\_LDAP\\_AUTH\\_CONNECTION\\_CREATOR\\_ENTER](#) was added in 8.0.11.
  - Error number: [MY-011785](#); Symbol: [ER\\_LDAP\\_AUTH\\_STARTING\\_TLS](#); SQLSTATE: [HY000](#)  
  
Message: starting TLS  
  
[ER\\_LDAP\\_AUTH\\_STARTING\\_TLS](#) was added in 8.0.11.
  - Error number: [MY-011786](#); Symbol: [ER\\_LDAP\\_AUTH\\_CONNECTION\\_GET\\_LDAP\\_INFO\\_NULL](#); SQLSTATE: [HY000](#)  
  
Message: Ldap\_connection\_pool::get: (ldap\_info == NULL)|| (\*ldap\_info)  
  
[ER\\_LDAP\\_AUTH\\_CONNECTION\\_GET\\_LDAP\\_INFO\\_NULL](#) was added in 8.0.11.
  - Error number: [MY-011787](#); Symbol: [ER\\_LDAP\\_AUTH\\_DELETING\\_CONNECTION\\_KEY](#); SQLSTATE: [HY000](#)  
  
Message: Ldap\_connection\_pool::deinit: deleting connection key %s  
  
[ER\\_LDAP\\_AUTH\\_DELETING\\_CONNECTION\\_KEY](#) was added in 8.0.11.
  - Error number: [MY-011788](#); Symbol: [ER\\_LDAP\\_AUTH\\_POOLED\\_CONNECTION\\_KEY](#); SQLSTATE: [HY000](#)  
  
Message: Ldap\_connection\_pool::get pooled connection key: %s  
  
[ER\\_LDAP\\_AUTH\\_POOLED\\_CONNECTION\\_KEY](#) was added in 8.0.11.
  - Error number: [MY-011789](#); Symbol: [ER\\_LDAP\\_AUTH\\_CREATE\\_CONNECTION\\_KEY](#); SQLSTATE: [HY000](#)  
  
Message: Ldap\_connection\_pool::get create connection key: %s  
  
[ER\\_LDAP\\_AUTH\\_CREATE\\_CONNECTION\\_KEY](#) was added in 8.0.11.
  - Error number: [MY-011790](#); Symbol: [ER\\_LDAP\\_AUTH\\_COMMUNICATION\\_HOST\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: LDAP communication host %s port %u  
  
[ER\\_LDAP\\_AUTH\\_COMMUNICATION\\_HOST\\_INFO](#) was added in 8.0.11.
  - Error number: [MY-011791](#); Symbol: [ER\\_LDAP\\_AUTH\\_METHOD\\_TO\\_CLIENT](#); SQLSTATE: [HY000](#)  
  
Message: Sending authentication method to client : %s  
  
[ER\\_LDAP\\_AUTH\\_METHOD\\_TO\\_CLIENT](#) was added in 8.0.11.
-

- 
- Error number: [MY-011792](#); Symbol: [ER\\_LDAP\\_AUTH\\_SASL\\_REQUEST\\_FROM\\_CLIENT](#); SQLSTATE: [HY000](#)  
Message: SASL request received from mysql client: %s  
[ER\\_LDAP\\_AUTH\\_SASL\\_REQUEST\\_FROM\\_CLIENT](#) was added in 8.0.11.
  - Error number: [MY-011793](#); Symbol: [ER\\_LDAP\\_AUTH\\_SASL\\_PROCESS\\_SASL](#); SQLSTATE: [HY000](#)  
Message: Ldap\_sasl\_authentication::process\_sasl rc: %s  
[ER\\_LDAP\\_AUTH\\_SASL\\_PROCESS\\_SASL](#) was added in 8.0.11.
  - Error number: [MY-011794](#); Symbol: [ER\\_LDAP\\_AUTH\\_SASL\\_BIND\\_SUCCESS\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Ldap\_sasl\_authentication::process\_sasl sasl bind succeed. dn: %s method: %s server credential: %s  
[ER\\_LDAP\\_AUTH\\_SASL\\_BIND\\_SUCCESS\\_INFO](#) was added in 8.0.11.
  - Error number: [MY-011795](#); Symbol: [ER\\_LDAP\\_AUTH\\_STARTED\\_FOR\\_USER](#); SQLSTATE: [HY000](#)  
Message: LDAP authentication started for user name: %s  
[ER\\_LDAP\\_AUTH\\_STARTED\\_FOR\\_USER](#) was added in 8.0.11.
  - Error number: [MY-011796](#); Symbol: [ER\\_LDAP\\_AUTH\\_DISTINGUISHED\\_NAME](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_LDAP\\_AUTH\\_DISTINGUISHED\\_NAME](#) was added in 8.0.11.
  - Error number: [MY-011797](#); Symbol: [ER\\_LDAP\\_AUTH\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: LDAP authentication initialize is failed with: %s  
[ER\\_LDAP\\_AUTH\\_INIT\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011798](#); Symbol: [ER\\_LDAP\\_AUTH\\_OR\\_GROUP\\_RETRIEVAL\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: LDAP authentication failed or group retrieval failed: %s  
[ER\\_LDAP\\_AUTH\\_OR\\_GROUP\\_RETRIEVAL\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011799](#); Symbol: [ER\\_LDAP\\_AUTH\\_USER\\_GROUP\\_SEARCH\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Search user group has failed: %s  
[ER\\_LDAP\\_AUTH\\_USER\\_GROUP\\_SEARCH\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011800](#); Symbol: [ER\\_LDAP\\_AUTH\\_USER\\_BIND\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: LDAP user bind has failed: %s



- 
- Error number: `MY-011801`; Symbol: `ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION`; SQLSTATE: `HY000`  
Message: Connection pool get: Failed to create LDAP connection. %s  
`ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION` was added in 8.0.11.
  - Error number: `MY-011802`; Symbol: `ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION`; SQLSTATE: `HY000`  
Message: Failed to create new LDAP connection: %s  
`ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION` was added in 8.0.11.
  - Error number: `MY-011803`; Symbol: `ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION`; SQLSTATE: `HY000`  
Message: Failed to establish TLS connection: %s  
`ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION` was added in 8.0.11.
  - Error number: `MY-011804`; Symbol: `ER_LDAP_AUTH_FAILED_TO_SEARCH_DN`; SQLSTATE: `HY000`  
Message: Failed to search user full dn: %s  
`ER_LDAP_AUTH_FAILED_TO_SEARCH_DN` was added in 8.0.11.
  - Error number: `MY-011805`; Symbol: `ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER`; SQLSTATE: `HY000`  
Message: Ldap\_connection\_pool::reinit  
`ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER` was added in 8.0.11.
  - Error number: `MY-011806`; Symbol: `ER_SYSTEMD_NOTIFY_PATH_TOO_LONG`; SQLSTATE: `HY000`  
Message: The path '%s', from the NOTIFY\_SOCKET environment variable, is too long. At %u bytes it exceeds the limit of %u bytes for an AF\_UNIX socket.  
`ER_SYSTEMD_NOTIFY_PATH_TOO_LONG` was added in 8.0.11.
  - Error number: `MY-011807`; Symbol: `ER_SYSTEMD_NOTIFY_CONNECT_FAILED`; SQLSTATE: `HY000`  
Message: Failed to connect to systemd notification socket named %s. Error: '%s'  
`ER_SYSTEMD_NOTIFY_CONNECT_FAILED` was added in 8.0.11.
  - Error number: `MY-011808`; Symbol: `ER_SYSTEMD_NOTIFY_WRITE_FAILED`; SQLSTATE: `HY000`  
Message: Failed to write '%s' to systemd notification. Error: '%s'  
`ER_SYSTEMD_NOTIFY_WRITE_FAILED` was added in 8.0.11.
  - Error number: `MY-011809`; Symbol: `ER_FOUND_MISSING_GTIDS`; SQLSTATE: `HY000`  
Message: Cannot replicate to server with server\_uuid='%s' because the present server has purged required binary logs. The connecting server needs to replicate the missing transactions from elsewhere, or be replaced by a new server created from a more recent backup. To prevent this error in the future, consider increasing the binary log expiration period on the present server. %s.

---

`ER_FOUND_MISSING_GTIDS` was added in 8.0.11.

- Error number: `MY-011810`; Symbol: `ER_PID_FILE_PRIV_DIRECTORY_INSECURE`; SQLSTATE: `HY000`

Message: Insecure configuration for --pid-file: Location '%s' in the path is accessible to all OS users. Consider choosing a different directory.

`ER_PID_FILE_PRIV_DIRECTORY_INSECURE` was added in 8.0.11.

- Error number: `MY-011811`; Symbol: `ER_CANT_CHECK_PID_PATH`; SQLSTATE: `HY000`

Message: Can't start server: can't check PID filepath: %s

`ER_CANT_CHECK_PID_PATH` was added in 8.0.11.

- Error number: `MY-011812`; Symbol: `ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: validate\_password status variables registration failed.

`ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED` was added in 8.0.11.

- Error number: `MY-011813`; Symbol: `ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: validate\_password status variables unregistration failed.

`ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED` was added in 8.0.11.

- Error number: `MY-011814`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Dictionary file open failed

`ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED` was added in 8.0.11.

- Error number: `MY-011815`; Symbol: `ER_VALIDATE_PWD_COULD_BE_NULL`; SQLSTATE: `HY000`

Message: given password string could be null

`ER_VALIDATE_PWD_COULD_BE_NULL` was added in 8.0.11.

- Error number: `MY-011816`; Symbol: `ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED`; SQLSTATE: `HY000`

Message: failed to convert the password string to lower case

`ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED` was added in 8.0.11.

- Error number: `MY-011817`; Symbol: `ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED`; SQLSTATE: `HY000`

Message: failed to convert the password string into a buffer

`ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED` was added in 8.0.11.

- 
- Error number: [MY-011818](#); Symbol: [ER\\_VALIDATE\\_PWD\\_STRING\\_HANDLER\\_MEM\\_ALLOCATION\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: memory allocation failed for string handler  
[ER\\_VALIDATE\\_PWD\\_STRING\\_HANDLER\\_MEM\\_ALLOCATION\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011819](#); Symbol: [ER\\_VALIDATE\\_PWD\\_STRONG\\_POLICY\\_DICT\\_FILE\\_UNSPECIFIED](#); SQLSTATE: [HY000](#)  
Message: Since the `validate_password_policy` is mentioned as Strong, dictionary file must be specified  
[ER\\_VALIDATE\\_PWD\\_STRONG\\_POLICY\\_DICT\\_FILE\\_UNSPECIFIED](#) was added in 8.0.11.
  - Error number: [MY-011820](#); Symbol: [ER\\_VALIDATE\\_PWD\\_CONVERT\\_TO\\_BUFFER\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: `convert_to_buffer` service failed  
[ER\\_VALIDATE\\_PWD\\_CONVERT\\_TO\\_BUFFER\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011821](#); Symbol: [ER\\_VALIDATE\\_PWD\\_VARIABLE\\_REGISTRATION\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: %s variable registration failed.  
[ER\\_VALIDATE\\_PWD\\_VARIABLE\\_REGISTRATION\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011822](#); Symbol: [ER\\_VALIDATE\\_PWD\\_VARIABLE\\_UNREGISTRATION\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: %s variable unregistration failed.  
[ER\\_VALIDATE\\_PWD\\_VARIABLE\\_UNREGISTRATION\\_FAILED](#) was added in 8.0.11.
  - Error number: [MY-011823](#); Symbol: [ER\\_KEYRING\\_MIGRATION\\_EXTRA\\_OPTIONS](#); SQLSTATE: [HY000](#)  
Message: Please specify options specific to keyring migration. Any additional options can be ignored.  
NOTE: Although some options are valid, migration tool can still report error example: plugin variables for which plugin is not loaded yet.  
[ER\\_KEYRING\\_MIGRATION\\_EXTRA\\_OPTIONS](#) was added in 8.0.11.
  - Error number: [MY-011825](#); Symbol: [ER\\_IB\\_MSG\\_0](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_0](#) was added in 8.0.11.
  - Error number: [MY-011826](#); Symbol: [ER\\_IB\\_MSG\\_1](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1](#) was added in 8.0.11.

- 
- Error number: [MY-011827](#); Symbol: [ER\\_IB\\_MSG\\_2](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_2](#) was added in 8.0.11.
  - Error number: [MY-011828](#); Symbol: [ER\\_IB\\_MSG\\_3](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_3](#) was added in 8.0.11.
  - Error number: [MY-011829](#); Symbol: [ER\\_IB\\_MSG\\_4](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_4](#) was added in 8.0.11.
  - Error number: [MY-011830](#); Symbol: [ER\\_IB\\_MSG\\_5](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_5](#) was added in 8.0.11.
  - Error number: [MY-011831](#); Symbol: [ER\\_IB\\_MSG\\_6](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_6](#) was added in 8.0.11.
  - Error number: [MY-011832](#); Symbol: [ER\\_IB\\_MSG\\_7](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_7](#) was added in 8.0.11.
  - Error number: [MY-011833](#); Symbol: [ER\\_IB\\_MSG\\_8](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_8](#) was added in 8.0.11.
  - Error number: [MY-011834](#); Symbol: [ER\\_IB\\_MSG\\_9](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_9](#) was added in 8.0.11.
  - Error number: [MY-011835](#); Symbol: [ER\\_IB\\_MSG\\_10](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_10](#) was added in 8.0.11.
  - Error number: [MY-011836](#); Symbol: [ER\\_IB\\_MSG\\_11](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_11](#) was added in 8.0.11.

- 
- Error number: `MY-011837`; Symbol: `ER_IB_MSG_12`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_12` was added in 8.0.11.
  - Error number: `MY-011838`; Symbol: `ER_IB_MSG_13`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_13` was added in 8.0.11.
  - Error number: `MY-011839`; Symbol: `ER_IB_MSG_14`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_14` was added in 8.0.11.
  - Error number: `MY-011840`; Symbol: `ER_IB_MSG_15`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_15` was added in 8.0.11.
  - Error number: `MY-011841`; Symbol: `ER_IB_MSG_16`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_16` was added in 8.0.11.
  - Error number: `MY-011842`; Symbol: `ER_IB_MSG_17`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_17` was added in 8.0.11.
  - Error number: `MY-011843`; Symbol: `ER_IB_MSG_18`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_18` was added in 8.0.11.
  - Error number: `MY-011844`; Symbol: `ER_IB_MSG_19`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_19` was added in 8.0.11.
  - Error number: `MY-011845`; Symbol: `ER_IB_MSG_20`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_20` was added in 8.0.11.
  - Error number: `MY-011846`; Symbol: `ER_IB_MSG_21`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_21` was added in 8.0.11.

- 
- Error number: [MY-011847](#); Symbol: [ER\\_IB\\_MSG\\_22](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_22](#) was added in 8.0.11.
  - Error number: [MY-011848](#); Symbol: [ER\\_IB\\_MSG\\_23](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_23](#) was added in 8.0.11.
  - Error number: [MY-011849](#); Symbol: [ER\\_IB\\_MSG\\_24](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_24](#) was added in 8.0.11.
  - Error number: [MY-011850](#); Symbol: [ER\\_IB\\_MSG\\_25](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_25](#) was added in 8.0.11.
  - Error number: [MY-011851](#); Symbol: [ER\\_IB\\_MSG\\_26](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_26](#) was added in 8.0.11.
  - Error number: [MY-011852](#); Symbol: [ER\\_IB\\_MSG\\_27](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_27](#) was added in 8.0.11.
  - Error number: [MY-011853](#); Symbol: [ER\\_IB\\_MSG\\_28](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_28](#) was added in 8.0.11.
  - Error number: [MY-011854](#); Symbol: [ER\\_IB\\_MSG\\_29](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_29](#) was added in 8.0.11.
  - Error number: [MY-011855](#); Symbol: [ER\\_IB\\_MSG\\_30](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_30](#) was added in 8.0.11.
  - Error number: [MY-011856](#); Symbol: [ER\\_IB\\_MSG\\_31](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_31](#) was added in 8.0.11.

- 
- Error number: [MY-011857](#); Symbol: [ER\\_IB\\_MSG\\_32](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_32](#) was added in 8.0.11.
  - Error number: [MY-011858](#); Symbol: [ER\\_IB\\_MSG\\_33](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_33](#) was added in 8.0.11.
  - Error number: [MY-011859](#); Symbol: [ER\\_IB\\_MSG\\_34](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_34](#) was added in 8.0.11.
  - Error number: [MY-011860](#); Symbol: [ER\\_IB\\_MSG\\_35](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_35](#) was added in 8.0.11.
  - Error number: [MY-011861](#); Symbol: [ER\\_IB\\_MSG\\_36](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_36](#) was added in 8.0.11.
  - Error number: [MY-011862](#); Symbol: [ER\\_IB\\_MSG\\_37](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_37](#) was added in 8.0.11.
  - Error number: [MY-011863](#); Symbol: [ER\\_IB\\_MSG\\_38](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_38](#) was added in 8.0.11.
  - Error number: [MY-011864](#); Symbol: [ER\\_IB\\_MSG\\_39](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_39](#) was added in 8.0.11.
  - Error number: [MY-011865](#); Symbol: [ER\\_IB\\_MSG\\_40](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_40](#) was added in 8.0.11.
  - Error number: [MY-011866](#); Symbol: [ER\\_IB\\_MSG\\_41](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_41](#) was added in 8.0.11.

- 
- Error number: [MY-011867](#); Symbol: [ER\\_IB\\_MSG\\_42](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_42](#) was added in 8.0.11.
  - Error number: [MY-011868](#); Symbol: [ER\\_IB\\_MSG\\_43](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_43](#) was added in 8.0.11.
  - Error number: [MY-011869](#); Symbol: [ER\\_IB\\_MSG\\_44](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_44](#) was added in 8.0.11.
  - Error number: [MY-011870](#); Symbol: [ER\\_IB\\_MSG\\_45](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_45](#) was added in 8.0.11.
  - Error number: [MY-011871](#); Symbol: [ER\\_IB\\_MSG\\_46](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_46](#) was added in 8.0.11.
  - Error number: [MY-011872](#); Symbol: [ER\\_IB\\_MSG\\_47](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_47](#) was added in 8.0.11.
  - Error number: [MY-011873](#); Symbol: [ER\\_IB\\_MSG\\_48](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_48](#) was added in 8.0.11.
  - Error number: [MY-011874](#); Symbol: [ER\\_IB\\_MSG\\_49](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_49](#) was added in 8.0.11.
  - Error number: [MY-011875](#); Symbol: [ER\\_IB\\_MSG\\_50](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_50](#) was added in 8.0.11.
  - Error number: [MY-011876](#); Symbol: [ER\\_IB\\_MSG\\_51](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_51](#) was added in 8.0.11.



- 
- Error number: [MY-011877](#); Symbol: [ER\\_IB\\_MSG\\_52](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_52](#) was added in 8.0.11.
  - Error number: [MY-011878](#); Symbol: [ER\\_IB\\_MSG\\_53](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_53](#) was added in 8.0.11.
  - Error number: [MY-011879](#); Symbol: [ER\\_IB\\_MSG\\_54](#); SQLSTATE: [HY000](#)  
Message: Failed to set NUMA memory policy of buffer pool page frames with mbind(%p,%zu,%s,,,,,,  
%s) failed with %s  
[ER\\_IB\\_MSG\\_54](#) was added in 8.0.11.
  - Error number: [MY-011880](#); Symbol: [ER\\_IB\\_MSG\\_55](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_55](#) was added in 8.0.11.
  - Error number: [MY-011881](#); Symbol: [ER\\_IB\\_MSG\\_56](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_56](#) was added in 8.0.11.
  - Error number: [MY-011882](#); Symbol: [ER\\_IB\\_MSG\\_57](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_57](#) was added in 8.0.11.
  - Error number: [MY-011883](#); Symbol: [ER\\_IB\\_MSG\\_58](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_58](#) was added in 8.0.11.
  - Error number: [MY-011884](#); Symbol: [ER\\_IB\\_MSG\\_59](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_59](#) was added in 8.0.11.
  - Error number: [MY-011885](#); Symbol: [ER\\_IB\\_MSG\\_60](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_60](#) was added in 8.0.11.
  - Error number: [MY-011886](#); Symbol: [ER\\_IB\\_MSG\\_61](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_61](#) was added in 8.0.11.

- 
- Error number: [MY-011887](#); Symbol: [ER\\_IB\\_MSG\\_62](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_62](#) was added in 8.0.11.
  - Error number: [MY-011888](#); Symbol: [ER\\_IB\\_MSG\\_63](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_63](#) was added in 8.0.11.
  - Error number: [MY-011889](#); Symbol: [ER\\_IB\\_MSG\\_64](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_64](#) was added in 8.0.11.
  - Error number: [MY-011890](#); Symbol: [ER\\_IB\\_MSG\\_65](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_65](#) was added in 8.0.11.
  - Error number: [MY-011891](#); Symbol: [ER\\_IB\\_MSG\\_66](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_66](#) was added in 8.0.11.
  - Error number: [MY-011892](#); Symbol: [ER\\_IB\\_MSG\\_67](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_67](#) was added in 8.0.11.
  - Error number: [MY-011893](#); Symbol: [ER\\_IB\\_MSG\\_68](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_68](#) was added in 8.0.11.
  - Error number: [MY-011894](#); Symbol: [ER\\_IB\\_MSG\\_69](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_69](#) was added in 8.0.11.
  - Error number: [MY-011895](#); Symbol: [ER\\_IB\\_MSG\\_70](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_70](#) was added in 8.0.11.
  - Error number: [MY-011896](#); Symbol: [ER\\_IB\\_MSG\\_71](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_71](#) was added in 8.0.11.

- 
- Error number: `MY-011897`; Symbol: `ER_IB_MSG_72`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_72` was added in 8.0.11.
  - Error number: `MY-011898`; Symbol: `ER_IB_MSG_73`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_73` was added in 8.0.11.
  - Error number: `MY-011899`; Symbol: `ER_IB_MSG_74`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_74` was added in 8.0.11.
  - Error number: `MY-011900`; Symbol: `ER_IB_MSG_75`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_75` was added in 8.0.11.
  - Error number: `MY-011901`; Symbol: `ER_IB_MSG_76`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_76` was added in 8.0.11.
  - Error number: `MY-011902`; Symbol: `ER_IB_MSG_77`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_77` was added in 8.0.11.
  - Error number: `MY-011903`; Symbol: `ER_IB_MSG_78`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_78` was added in 8.0.11.
  - Error number: `MY-011904`; Symbol: `ER_IB_MSG_79`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_79` was added in 8.0.11.
  - Error number: `MY-011905`; Symbol: `ER_IB_MSG_80`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_80` was added in 8.0.11.
  - Error number: `MY-011906`; Symbol: `ER_IB_MSG_81`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_81` was added in 8.0.11.

- 
- Error number: [MY-011907](#); Symbol: [ER\\_IB\\_MSG\\_82](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_82](#) was added in 8.0.11.
  - Error number: [MY-011908](#); Symbol: [ER\\_IB\\_MSG\\_83](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_83](#) was added in 8.0.11.
  - Error number: [MY-011909](#); Symbol: [ER\\_IB\\_MSG\\_84](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_84](#) was added in 8.0.11.
  - Error number: [MY-011910](#); Symbol: [ER\\_IB\\_MSG\\_85](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_85](#) was added in 8.0.11.
  - Error number: [MY-011911](#); Symbol: [ER\\_IB\\_MSG\\_86](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_86](#) was added in 8.0.11.
  - Error number: [MY-011912](#); Symbol: [ER\\_IB\\_MSG\\_87](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_87](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011913](#); Symbol: [ER\\_IB\\_MSG\\_88](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_88](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011914](#); Symbol: [ER\\_IB\\_MSG\\_89](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_89](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011915](#); Symbol: [ER\\_IB\\_MSG\\_90](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_90](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011916](#); Symbol: [ER\\_IB\\_MSG\\_91](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_91](#) was added in 8.0.11, removed after 8.0.13.

- 
- Error number: [MY-011917](#); Symbol: [ER\\_IB\\_MSG\\_92](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_92](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011918](#); Symbol: [ER\\_IB\\_MSG\\_93](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_93](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011919](#); Symbol: [ER\\_IB\\_MSG\\_94](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_94](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011920](#); Symbol: [ER\\_IB\\_MSG\\_95](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_95](#) was added in 8.0.11.
  - Error number: [MY-011921](#); Symbol: [ER\\_IB\\_MSG\\_96](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_96](#) was added in 8.0.11.
  - Error number: [MY-011922](#); Symbol: [ER\\_IB\\_MSG\\_97](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_97](#) was added in 8.0.11.
  - Error number: [MY-011923](#); Symbol: [ER\\_IB\\_MSG\\_98](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_98](#) was added in 8.0.11.
  - Error number: [MY-011924](#); Symbol: [ER\\_IB\\_MSG\\_99](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_99](#) was added in 8.0.11.
  - Error number: [MY-011925](#); Symbol: [ER\\_IB\\_MSG\\_100](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_100](#) was added in 8.0.11.
  - Error number: [MY-011926](#); Symbol: [ER\\_IB\\_MSG\\_101](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_101](#) was added in 8.0.11.

- 
- Error number: [MY-011927](#); Symbol: [ER\\_IB\\_MSG\\_102](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_102](#) was added in 8.0.11.
  - Error number: [MY-011928](#); Symbol: [ER\\_IB\\_MSG\\_103](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_103](#) was added in 8.0.11.
  - Error number: [MY-011929](#); Symbol: [ER\\_IB\\_MSG\\_104](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_104](#) was added in 8.0.11.
  - Error number: [MY-011930](#); Symbol: [ER\\_IB\\_MSG\\_105](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_105](#) was added in 8.0.11.
  - Error number: [MY-011931](#); Symbol: [ER\\_IB\\_MSG\\_106](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_106](#) was added in 8.0.11.
  - Error number: [MY-011932](#); Symbol: [ER\\_IB\\_MSG\\_107](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_107](#) was added in 8.0.11.
  - Error number: [MY-011933](#); Symbol: [ER\\_IB\\_MSG\\_108](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_108](#) was added in 8.0.11.
  - Error number: [MY-011934](#); Symbol: [ER\\_IB\\_MSG\\_109](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_109](#) was added in 8.0.11.
  - Error number: [MY-011935](#); Symbol: [ER\\_IB\\_MSG\\_110](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_110](#) was added in 8.0.11.
  - Error number: [MY-011936](#); Symbol: [ER\\_IB\\_MSG\\_111](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_111](#) was added in 8.0.11.

- 
- Error number: [MY-011937](#); Symbol: [ER\\_IB\\_MSG\\_112](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_112](#) was added in 8.0.11.
  - Error number: [MY-011938](#); Symbol: [ER\\_IB\\_MSG\\_113](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_113](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011939](#); Symbol: [ER\\_IB\\_MSG\\_114](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_114](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011940](#); Symbol: [ER\\_IB\\_MSG\\_115](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_115](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011941](#); Symbol: [ER\\_IB\\_MSG\\_116](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_116](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011942](#); Symbol: [ER\\_IB\\_MSG\\_117](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_117](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011943](#); Symbol: [ER\\_IB\\_MSG\\_118](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_118](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-011944](#); Symbol: [ER\\_IB\\_MSG\\_119](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_119](#) was added in 8.0.11.
  - Error number: [MY-011945](#); Symbol: [ER\\_IB\\_MSG\\_120](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_120](#) was added in 8.0.11.
  - Error number: [MY-011946](#); Symbol: [ER\\_IB\\_MSG\\_121](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_121](#) was added in 8.0.11.

- 
- Error number: [MY-011947](#); Symbol: [ER\\_IB\\_MSG\\_122](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_122](#) was added in 8.0.11.
  - Error number: [MY-011948](#); Symbol: [ER\\_IB\\_MSG\\_123](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_123](#) was added in 8.0.11.
  - Error number: [MY-011949](#); Symbol: [ER\\_IB\\_MSG\\_124](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_124](#) was added in 8.0.11.
  - Error number: [MY-011950](#); Symbol: [ER\\_IB\\_MSG\\_125](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_125](#) was added in 8.0.11.
  - Error number: [MY-011951](#); Symbol: [ER\\_IB\\_MSG\\_126](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_126](#) was added in 8.0.11.
  - Error number: [MY-011952](#); Symbol: [ER\\_IB\\_MSG\\_127](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_127](#) was added in 8.0.11.
  - Error number: [MY-011953](#); Symbol: [ER\\_IB\\_MSG\\_128](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_128](#) was added in 8.0.11.
  - Error number: [MY-011954](#); Symbol: [ER\\_IB\\_MSG\\_129](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_129](#) was added in 8.0.11.
  - Error number: [MY-011955](#); Symbol: [ER\\_IB\\_MSG\\_130](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_130](#) was added in 8.0.11.
  - Error number: [MY-011956](#); Symbol: [ER\\_IB\\_MSG\\_131](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_131](#) was added in 8.0.11.



- 
- Error number: [MY-011957](#); Symbol: [ER\\_IB\\_MSG\\_132](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_132](#) was added in 8.0.11.
  - Error number: [MY-011958](#); Symbol: [ER\\_IB\\_MSG\\_133](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_133](#) was added in 8.0.11.
  - Error number: [MY-011959](#); Symbol: [ER\\_IB\\_MSG\\_134](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_134](#) was added in 8.0.11.
  - Error number: [MY-011960](#); Symbol: [ER\\_IB\\_MSG\\_135](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_135](#) was added in 8.0.11.
  - Error number: [MY-011961](#); Symbol: [ER\\_IB\\_MSG\\_136](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_136](#) was added in 8.0.11.
  - Error number: [MY-011962](#); Symbol: [ER\\_IB\\_MSG\\_137](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_137](#) was added in 8.0.11.
  - Error number: [MY-011963](#); Symbol: [ER\\_IB\\_MSG\\_138](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_138](#) was added in 8.0.11.
  - Error number: [MY-011964](#); Symbol: [ER\\_IB\\_MSG\\_139](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_139](#) was added in 8.0.11.
  - Error number: [MY-011965](#); Symbol: [ER\\_IB\\_MSG\\_140](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_140](#) was added in 8.0.11.
  - Error number: [MY-011966](#); Symbol: [ER\\_IB\\_MSG\\_141](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_141](#) was added in 8.0.11.

- 
- Error number: [MY-011967](#); Symbol: [ER\\_IB\\_MSG\\_142](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_142](#) was added in 8.0.11.
  - Error number: [MY-011968](#); Symbol: [ER\\_IB\\_MSG\\_143](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_143](#) was added in 8.0.11.
  - Error number: [MY-011969](#); Symbol: [ER\\_IB\\_MSG\\_144](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_144](#) was added in 8.0.11.
  - Error number: [MY-011970](#); Symbol: [ER\\_IB\\_MSG\\_145](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_145](#) was added in 8.0.11.
  - Error number: [MY-011971](#); Symbol: [ER\\_IB\\_MSG\\_146](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_146](#) was added in 8.0.11.
  - Error number: [MY-011972](#); Symbol: [ER\\_IB\\_MSG\\_147](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_147](#) was added in 8.0.11.
  - Error number: [MY-011973](#); Symbol: [ER\\_IB\\_MSG\\_148](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_148](#) was added in 8.0.11.
  - Error number: [MY-011974](#); Symbol: [ER\\_IB\\_MSG\\_149](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_149](#) was added in 8.0.11, removed after 8.0.16.
  - Error number: [MY-011974](#); Symbol: [ER\\_IB\\_CLONE\\_INTERNAL](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_CLONE\\_INTERNAL](#) was added in 8.0.17.
  - Error number: [MY-011975](#); Symbol: [ER\\_IB\\_MSG\\_150](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_150](#) was added in 8.0.11, removed after 8.0.16.

- 
- Error number: [MY-011975](#); Symbol: [ER\\_IB\\_CLONE\\_TIMEOUT](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_CLONE\\_TIMEOUT](#) was added in 8.0.17.
  - Error number: [MY-011976](#); Symbol: [ER\\_IB\\_MSG\\_151](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_151](#) was added in 8.0.11, removed after 8.0.16.
  - Error number: [MY-011976](#); Symbol: [ER\\_IB\\_CLONE\\_STATUS\\_FILE](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_CLONE\\_STATUS\\_FILE](#) was added in 8.0.17.
  - Error number: [MY-011977](#); Symbol: [ER\\_IB\\_MSG\\_152](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_152](#) was added in 8.0.11, removed after 8.0.16.
  - Error number: [MY-011977](#); Symbol: [ER\\_IB\\_CLONE\\_SQL](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_CLONE\\_SQL](#) was added in 8.0.17.
  - Error number: [MY-011978](#); Symbol: [ER\\_IB\\_MSG\\_153](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_153](#) was added in 8.0.11, removed after 8.0.16.
  - Error number: [MY-011978](#); Symbol: [ER\\_IB\\_CLONE\\_VALIDATE](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_CLONE\\_VALIDATE](#) was added in 8.0.17.
  - Error number: [MY-011979](#); Symbol: [ER\\_IB\\_MSG\\_154](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_154](#) was added in 8.0.11, removed after 8.0.16.
  - Error number: [MY-011979](#); Symbol: [ER\\_IB\\_CLONE\\_PUNCH\\_HOLE](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_CLONE\\_PUNCH\\_HOLE](#) was added in 8.0.17.
  - Error number: [MY-011980](#); Symbol: [ER\\_IB\\_MSG\\_155](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_155](#) was added in 8.0.11, removed after 8.0.16.

- 
- Error number: `MY-011980`; Symbol: `ER_IB_CLONE_GTID_PERSIST`; `SQLSTATE: HY000`  
Message: %s  
`ER_IB_CLONE_GTID_PERSIST` was added in 8.0.17.
  - Error number: `MY-011981`; Symbol: `ER_IB_MSG_156`; `SQLSTATE: HY000`  
Message: %s  
`ER_IB_MSG_156` was added in 8.0.11.
  - Error number: `MY-011982`; Symbol: `ER_IB_MSG_157`; `SQLSTATE: HY000`  
Message: %s  
`ER_IB_MSG_157` was added in 8.0.11.
  - Error number: `MY-011983`; Symbol: `ER_IB_MSG_158`; `SQLSTATE: HY000`  
Message: %s  
`ER_IB_MSG_158` was added in 8.0.11.
  - Error number: `MY-011984`; Symbol: `ER_IB_MSG_159`; `SQLSTATE: HY000`  
Message: %s  
`ER_IB_MSG_159` was added in 8.0.11.
  - Error number: `MY-011985`; Symbol: `ER_IB_MSG_160`; `SQLSTATE: HY000`  
Message: %s  
`ER_IB_MSG_160` was added in 8.0.11.
  - Error number: `MY-011986`; Symbol: `ER_IB_MSG_161`; `SQLSTATE: HY000`  
Message: %s  
`ER_IB_MSG_161` was added in 8.0.11.
  - Error number: `MY-011987`; Symbol: `ER_IB_MSG_162`; `SQLSTATE: HY000`  
Message: %s  
`ER_IB_MSG_162` was added in 8.0.11.
  - Error number: `MY-011988`; Symbol: `ER_IB_MSG_163`; `SQLSTATE: HY000`  
Message: %s  
`ER_IB_MSG_163` was added in 8.0.11.
  - Error number: `MY-011989`; Symbol: `ER_IB_MSG_164`; `SQLSTATE: HY000`  
Message: %s  
`ER_IB_MSG_164` was added in 8.0.11.

- 
- Error number: [MY-011990](#); Symbol: [ER\\_IB\\_MSG\\_165](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_165](#) was added in 8.0.11.
  - Error number: [MY-011991](#); Symbol: [ER\\_IB\\_MSG\\_166](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_166](#) was added in 8.0.11.
  - Error number: [MY-011992](#); Symbol: [ER\\_IB\\_MSG\\_167](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_167](#) was added in 8.0.11.
  - Error number: [MY-011993](#); Symbol: [ER\\_IB\\_MSG\\_168](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_168](#) was added in 8.0.11.
  - Error number: [MY-011994](#); Symbol: [ER\\_IB\\_MSG\\_169](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_169](#) was added in 8.0.11.
  - Error number: [MY-011995](#); Symbol: [ER\\_IB\\_MSG\\_170](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_170](#) was added in 8.0.11.
  - Error number: [MY-011996](#); Symbol: [ER\\_IB\\_MSG\\_171](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_171](#) was added in 8.0.11.
  - Error number: [MY-011997](#); Symbol: [ER\\_IB\\_MSG\\_172](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_172](#) was added in 8.0.11.
  - Error number: [MY-011998](#); Symbol: [ER\\_IB\\_MSG\\_173](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_173](#) was added in 8.0.11.
  - Error number: [MY-011999](#); Symbol: [ER\\_IB\\_MSG\\_174](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_174](#) was added in 8.0.11.

- 
- Error number: [MY-012000](#); Symbol: [ER\\_IB\\_MSG\\_175](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_175](#) was added in 8.0.11.
  - Error number: [MY-012001](#); Symbol: [ER\\_IB\\_MSG\\_176](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_176](#) was added in 8.0.11.
  - Error number: [MY-012002](#); Symbol: [ER\\_IB\\_MSG\\_177](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_177](#) was added in 8.0.11.
  - Error number: [MY-012003](#); Symbol: [ER\\_IB\\_MSG\\_178](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_178](#) was added in 8.0.11.
  - Error number: [MY-012004](#); Symbol: [ER\\_IB\\_MSG\\_179](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_179](#) was added in 8.0.11.
  - Error number: [MY-012005](#); Symbol: [ER\\_IB\\_MSG\\_180](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_180](#) was added in 8.0.11.
  - Error number: [MY-012006](#); Symbol: [ER\\_IB\\_MSG\\_181](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_181](#) was added in 8.0.11, removed after 8.0.31.
  - Error number: [MY-012006](#); Symbol: [ER\\_IB\\_LONG\\_AHI\\_DISABLE\\_WAIT](#); SQLSTATE: [HY000](#)  
Message: Waited for %u secs for hash index ref\_count (%zu) to drop to 0. index: "%s" table: "%s"  
[ER\\_IB\\_LONG\\_AHI\\_DISABLE\\_WAIT](#) was added in 8.0.32.
  - Error number: [MY-012007](#); Symbol: [ER\\_IB\\_MSG\\_182](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_182](#) was added in 8.0.11.
  - Error number: [MY-012008](#); Symbol: [ER\\_IB\\_MSG\\_183](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_183](#) was added in 8.0.11.

- 
- Error number: [MY-012009](#); Symbol: [ER\\_IB\\_MSG\\_184](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_184](#) was added in 8.0.11.
  - Error number: [MY-012010](#); Symbol: [ER\\_IB\\_MSG\\_185](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_185](#) was added in 8.0.11.
  - Error number: [MY-012011](#); Symbol: [ER\\_IB\\_MSG\\_186](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_186](#) was added in 8.0.11.
  - Error number: [MY-012012](#); Symbol: [ER\\_IB\\_MSG\\_187](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_187](#) was added in 8.0.11.
  - Error number: [MY-012013](#); Symbol: [ER\\_IB\\_MSG\\_188](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_188](#) was added in 8.0.11.
  - Error number: [MY-012014](#); Symbol: [ER\\_IB\\_MSG\\_189](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_189](#) was added in 8.0.11.
  - Error number: [MY-012015](#); Symbol: [ER\\_IB\\_MSG\\_190](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_190](#) was added in 8.0.11.
  - Error number: [MY-012016](#); Symbol: [ER\\_IB\\_MSG\\_191](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_191](#) was added in 8.0.11.
  - Error number: [MY-012017](#); Symbol: [ER\\_IB\\_MSG\\_192](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_192](#) was added in 8.0.11.
  - Error number: [MY-012018](#); Symbol: [ER\\_IB\\_MSG\\_193](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_193](#) was added in 8.0.11.

- 
- Error number: [MY-012019](#); Symbol: [ER\\_IB\\_MSG\\_194](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_194](#) was added in 8.0.11.
  - Error number: [MY-012020](#); Symbol: [ER\\_IB\\_MSG\\_195](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_195](#) was added in 8.0.11.
  - Error number: [MY-012021](#); Symbol: [ER\\_IB\\_MSG\\_196](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_196](#) was added in 8.0.11.
  - Error number: [MY-012022](#); Symbol: [ER\\_IB\\_MSG\\_197](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_197](#) was added in 8.0.11.
  - Error number: [MY-012023](#); Symbol: [ER\\_IB\\_MSG\\_198](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_198](#) was added in 8.0.11.
  - Error number: [MY-012024](#); Symbol: [ER\\_IB\\_MSG\\_199](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_199](#) was added in 8.0.11.
  - Error number: [MY-012025](#); Symbol: [ER\\_IB\\_MSG\\_200](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_200](#) was added in 8.0.11.
  - Error number: [MY-012026](#); Symbol: [ER\\_IB\\_MSG\\_201](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_201](#) was added in 8.0.11.
  - Error number: [MY-012027](#); Symbol: [ER\\_IB\\_MSG\\_202](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_202](#) was added in 8.0.11.
  - Error number: [MY-012028](#); Symbol: [ER\\_IB\\_MSG\\_203](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_203](#) was added in 8.0.11.



- 
- Error number: [MY-012029](#); Symbol: [ER\\_IB\\_MSG\\_204](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_204](#) was added in 8.0.11.
  - Error number: [MY-012030](#); Symbol: [ER\\_IB\\_MSG\\_205](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_205](#) was added in 8.0.11.
  - Error number: [MY-012031](#); Symbol: [ER\\_IB\\_MSG\\_206](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_206](#) was added in 8.0.11.
  - Error number: [MY-012032](#); Symbol: [ER\\_IB\\_MSG\\_207](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_207](#) was added in 8.0.11.
  - Error number: [MY-012033](#); Symbol: [ER\\_IB\\_MSG\\_208](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_208](#) was added in 8.0.11.
  - Error number: [MY-012034](#); Symbol: [ER\\_IB\\_MSG\\_209](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_209](#) was added in 8.0.11.
  - Error number: [MY-012035](#); Symbol: [ER\\_IB\\_MSG\\_210](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_210](#) was added in 8.0.11.
  - Error number: [MY-012036](#); Symbol: [ER\\_IB\\_MSG\\_211](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_211](#) was added in 8.0.11.
  - Error number: [MY-012037](#); Symbol: [ER\\_IB\\_MSG\\_212](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_212](#) was added in 8.0.11.
  - Error number: [MY-012038](#); Symbol: [ER\\_IB\\_MSG\\_213](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_213](#) was added in 8.0.11.

- 
- Error number: [MY-012039](#); Symbol: [ER\\_IB\\_MSG\\_214](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_214](#) was added in 8.0.11.
  - Error number: [MY-012040](#); Symbol: [ER\\_IB\\_MSG\\_215](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_215](#) was added in 8.0.11.
  - Error number: [MY-012041](#); Symbol: [ER\\_IB\\_MSG\\_216](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_216](#) was added in 8.0.11.
  - Error number: [MY-012042](#); Symbol: [ER\\_IB\\_MSG\\_217](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_217](#) was added in 8.0.11.
  - Error number: [MY-012043](#); Symbol: [ER\\_IB\\_MSG\\_218](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_218](#) was added in 8.0.11.
  - Error number: [MY-012044](#); Symbol: [ER\\_IB\\_MSG\\_219](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_219](#) was added in 8.0.11.
  - Error number: [MY-012045](#); Symbol: [ER\\_IB\\_MSG\\_220](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_220](#) was added in 8.0.11.
  - Error number: [MY-012046](#); Symbol: [ER\\_IB\\_MSG\\_221](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_221](#) was added in 8.0.11.
  - Error number: [MY-012047](#); Symbol: [ER\\_IB\\_MSG\\_222](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_222](#) was added in 8.0.11.
  - Error number: [MY-012048](#); Symbol: [ER\\_IB\\_MSG\\_223](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_223](#) was added in 8.0.11.

- 
- Error number: [MY-012049](#); Symbol: [ER\\_IB\\_MSG\\_224](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_224](#) was added in 8.0.11.
  - Error number: [MY-012050](#); Symbol: [ER\\_IB\\_MSG\\_225](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_225](#) was added in 8.0.11.
  - Error number: [MY-012051](#); Symbol: [ER\\_IB\\_MSG\\_226](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_226](#) was added in 8.0.11.
  - Error number: [MY-012052](#); Symbol: [ER\\_IB\\_MSG\\_227](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_227](#) was added in 8.0.11.
  - Error number: [MY-012053](#); Symbol: [ER\\_IB\\_MSG\\_228](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_228](#) was added in 8.0.11.
  - Error number: [MY-012054](#); Symbol: [ER\\_IB\\_MSG\\_229](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_229](#) was added in 8.0.11.
  - Error number: [MY-012055](#); Symbol: [ER\\_IB\\_MSG\\_230](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_230](#) was added in 8.0.11.
  - Error number: [MY-012056](#); Symbol: [ER\\_IB\\_MSG\\_231](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_231](#) was added in 8.0.11.
  - Error number: [MY-012057](#); Symbol: [ER\\_IB\\_MSG\\_232](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_232](#) was added in 8.0.11.
  - Error number: [MY-012058](#); Symbol: [ER\\_IB\\_MSG\\_233](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_233](#) was added in 8.0.11.

- 
- Error number: [MY-012059](#); Symbol: [ER\\_IB\\_MSG\\_234](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_234](#) was added in 8.0.11.
  - Error number: [MY-012060](#); Symbol: [ER\\_IB\\_MSG\\_235](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_235](#) was added in 8.0.11.
  - Error number: [MY-012061](#); Symbol: [ER\\_IB\\_MSG\\_236](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_236](#) was added in 8.0.11.
  - Error number: [MY-012062](#); Symbol: [ER\\_IB\\_MSG\\_237](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_237](#) was added in 8.0.11.
  - Error number: [MY-012063](#); Symbol: [ER\\_IB\\_MSG\\_238](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_238](#) was added in 8.0.11.
  - Error number: [MY-012064](#); Symbol: [ER\\_IB\\_MSG\\_239](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_239](#) was added in 8.0.11.
  - Error number: [MY-012065](#); Symbol: [ER\\_IB\\_MSG\\_240](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_240](#) was added in 8.0.11.
  - Error number: [MY-012066](#); Symbol: [ER\\_IB\\_MSG\\_241](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_241](#) was added in 8.0.11.
  - Error number: [MY-012067](#); Symbol: [ER\\_IB\\_MSG\\_242](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_242](#) was added in 8.0.11.
  - Error number: [MY-012068](#); Symbol: [ER\\_IB\\_MSG\\_243](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_243](#) was added in 8.0.11.

- 
- Error number: [MY-012069](#); Symbol: [ER\\_IB\\_MSG\\_244](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_244](#) was added in 8.0.11.
  - Error number: [MY-012070](#); Symbol: [ER\\_IB\\_MSG\\_245](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_245](#) was added in 8.0.11.
  - Error number: [MY-012071](#); Symbol: [ER\\_IB\\_MSG\\_246](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_246](#) was added in 8.0.11.
  - Error number: [MY-012072](#); Symbol: [ER\\_IB\\_MSG\\_247](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_247](#) was added in 8.0.11.
  - Error number: [MY-012073](#); Symbol: [ER\\_IB\\_MSG\\_248](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_248](#) was added in 8.0.11.
  - Error number: [MY-012074](#); Symbol: [ER\\_IB\\_MSG\\_249](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_249](#) was added in 8.0.11.
  - Error number: [MY-012075](#); Symbol: [ER\\_IB\\_MSG\\_250](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_250](#) was added in 8.0.11.
  - Error number: [MY-012076](#); Symbol: [ER\\_IB\\_MSG\\_251](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_251](#) was added in 8.0.11.
  - Error number: [MY-012077](#); Symbol: [ER\\_IB\\_MSG\\_252](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_252](#) was added in 8.0.11.
  - Error number: [MY-012078](#); Symbol: [ER\\_IB\\_MSG\\_253](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_253](#) was added in 8.0.11.

- 
- Error number: [MY-012079](#); Symbol: [ER\\_IB\\_MSG\\_254](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_254](#) was added in 8.0.11.
  - Error number: [MY-012080](#); Symbol: [ER\\_IB\\_MSG\\_255](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_255](#) was added in 8.0.11.
  - Error number: [MY-012081](#); Symbol: [ER\\_IB\\_MSG\\_256](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_256](#) was added in 8.0.11.
  - Error number: [MY-012082](#); Symbol: [ER\\_IB\\_MSG\\_257](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_257](#) was added in 8.0.11.
  - Error number: [MY-012083](#); Symbol: [ER\\_IB\\_MSG\\_258](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_258](#) was added in 8.0.11.
  - Error number: [MY-012084](#); Symbol: [ER\\_IB\\_MSG\\_259](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_259](#) was added in 8.0.11.
  - Error number: [MY-012085](#); Symbol: [ER\\_IB\\_MSG\\_260](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_260](#) was added in 8.0.11.
  - Error number: [MY-012086](#); Symbol: [ER\\_IB\\_MSG\\_261](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_261](#) was added in 8.0.11.
  - Error number: [MY-012087](#); Symbol: [ER\\_IB\\_MSG\\_262](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_262](#) was added in 8.0.11.
  - Error number: [MY-012088](#); Symbol: [ER\\_IB\\_MSG\\_263](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_263](#) was added in 8.0.11.

- 
- Error number: [MY-012089](#); Symbol: [ER\\_IB\\_MSG\\_264](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_264](#) was added in 8.0.11.
  - Error number: [MY-012090](#); Symbol: [ER\\_IB\\_MSG\\_265](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_265](#) was added in 8.0.11.
  - Error number: [MY-012091](#); Symbol: [ER\\_IB\\_MSG\\_266](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_266](#) was added in 8.0.11.
  - Error number: [MY-012092](#); Symbol: [ER\\_IB\\_MSG\\_267](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_267](#) was added in 8.0.11.
  - Error number: [MY-012093](#); Symbol: [ER\\_IB\\_MSG\\_268](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_268](#) was added in 8.0.11.
  - Error number: [MY-012094](#); Symbol: [ER\\_IB\\_MSG\\_269](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_269](#) was added in 8.0.11.
  - Error number: [MY-012095](#); Symbol: [ER\\_IB\\_MSG\\_270](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_270](#) was added in 8.0.11.
  - Error number: [MY-012096](#); Symbol: [ER\\_IB\\_MSG\\_271](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_271](#) was added in 8.0.11.
  - Error number: [MY-012097](#); Symbol: [ER\\_IB\\_MSG\\_272](#); SQLSTATE: [HY000](#)  
Message: Table flags are 0x%lx in the data dictionary but the flags in file %s are 0x%llx!  
[ER\\_IB\\_MSG\\_272](#) was added in 8.0.11.
  - Error number: [MY-012098](#); Symbol: [ER\\_IB\\_MSG\\_273](#); SQLSTATE: [HY000](#)  
Message: Can't read encryption key from file %s!  
[ER\\_IB\\_MSG\\_273](#) was added in 8.0.11.

- 
- Error number: [MY-012099](#); Symbol: [ER\\_IB\\_MSG\\_274](#); SQLSTATE: [HY000](#)  
Message: Cannot close file %s, because n\_pending\_flushes %zu  
[ER\\_IB\\_MSG\\_274](#) was added in 8.0.11, removed after 8.0.27.
  - Error number: [MY-012100](#); Symbol: [ER\\_IB\\_MSG\\_275](#); SQLSTATE: [HY000](#)  
Message: Cannot close file %s, because modification count %lld != flush count %lld  
[ER\\_IB\\_MSG\\_275](#) was added in 8.0.11, removed after 8.0.27.
  - Error number: [MY-012101](#); Symbol: [ER\\_IB\\_MSG\\_276](#); SQLSTATE: [HY000](#)  
Message: Cannot close file %s, because it is in use  
[ER\\_IB\\_MSG\\_276](#) was added in 8.0.11, removed after 8.0.27.
  - Error number: [MY-012102](#); Symbol: [ER\\_IB\\_MSG\\_277](#); SQLSTATE: [HY000](#)  
Message: Open file list len in shard %zu is %llu  
[ER\\_IB\\_MSG\\_277](#) was added in 8.0.11, removed after 8.0.27.
  - Error number: [MY-012103](#); Symbol: [ER\\_IB\\_MSG\\_278](#); SQLSTATE: [HY000](#)  
Message: Tablespace %s, waiting for IO to stop for %lld seconds  
[ER\\_IB\\_MSG\\_278](#) was added in 8.0.11.
  - Error number: [MY-012104](#); Symbol: [ER\\_IB\\_MSG\\_279](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_279](#) was added in 8.0.11, removed after 8.0.27.
  - Error number: [MY-012105](#); Symbol: [ER\\_IB\\_MSG\\_280](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_280](#) was added in 8.0.11.
  - Error number: [MY-012106](#); Symbol: [ER\\_IB\\_MSG\\_281](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_281](#) was added in 8.0.11.
  - Error number: [MY-012107](#); Symbol: [ER\\_IB\\_MSG\\_282](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_282](#) was added in 8.0.11.
  - Error number: [MY-012108](#); Symbol: [ER\\_IB\\_MSG\\_283](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_283](#) was added in 8.0.11.



- 
- Error number: [MY-012109](#); Symbol: [ER\\_IB\\_MSG\\_284](#); SQLSTATE: [HY000](#)  
Message: You must raise the value of `innodb_open_files` in `my.cnf`! Remember that InnoDB keeps all redo log files and all system tablespace files open for the whole time `mysqld` is running, and needs to open also some `.ibd` files if the file-per-table storage model is used. Current open files `%zu`, max allowed open files `%zu`.  
[ER\\_IB\\_MSG\\_284](#) was added in 8.0.11.
  - Error number: [MY-012110](#); Symbol: [ER\\_IB\\_MSG\\_285](#); SQLSTATE: [HY000](#)  
Message: Max tablespace id is too high, `%lu`  
[ER\\_IB\\_MSG\\_285](#) was added in 8.0.11.
  - Error number: [MY-012111](#); Symbol: [ER\\_IB\\_MSG\\_286](#); SQLSTATE: [HY000](#)  
Message: Trying to access missing tablespace `%lu`  
[ER\\_IB\\_MSG\\_286](#) was added in 8.0.11, removed after 8.0.27.
  - Error number: [MY-012111](#); Symbol: [ER\\_IB\\_WARN\\_ACCESSING\\_NONEXISTINC\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Trying to access missing tablespace `%lu`  
[ER\\_IB\\_WARN\\_ACCESSING\\_NONEXISTINC\\_SPACE](#) was added in 8.0.28.
  - Error number: [MY-012112](#); Symbol: [ER\\_IB\\_MSG\\_287](#); SQLSTATE: [HY000](#)  
Message: Trying to close/delete tablespace '`%s`' but there are `%lu` pending operations on it.  
[ER\\_IB\\_MSG\\_287](#) was added in 8.0.11.
  - Error number: [MY-012113](#); Symbol: [ER\\_IB\\_MSG\\_288](#); SQLSTATE: [HY000](#)  
Message: Trying to delete/close tablespace '`%s`' but there are `%lu` flushes and `%zu` pending I/O's on it.  
[ER\\_IB\\_MSG\\_288](#) was added in 8.0.11.
  - Error number: [MY-012114](#); Symbol: [ER\\_IB\\_MSG\\_289](#); SQLSTATE: [HY000](#)  
Message: `%s`  
[ER\\_IB\\_MSG\\_289](#) was added in 8.0.11.
  - Error number: [MY-012115](#); Symbol: [ER\\_IB\\_MSG\\_290](#); SQLSTATE: [HY000](#)  
Message: Cannot delete tablespace `%lu` because it is not found in the tablespace memory cache.  
[ER\\_IB\\_MSG\\_290](#) was added in 8.0.11, removed after 8.0.17.
  - Error number: [MY-012116](#); Symbol: [ER\\_IB\\_MSG\\_291](#); SQLSTATE: [HY000](#)  
Message: While deleting tablespace `%lu` in DISCARD TABLESPACE. File rename/delete failed: `%s`  
[ER\\_IB\\_MSG\\_291](#) was added in 8.0.11.
  - Error number: [MY-012117](#); Symbol: [ER\\_IB\\_MSG\\_292](#); SQLSTATE: [HY000](#)

---

Message: Cannot delete tablespace %lu in DISCARD TABLESPACE: %s

[ER\\_IB\\_MSG\\_292](#) was added in 8.0.11.

- Error number: [MY-012118](#); Symbol: [ER\\_IB\\_MSG\\_293](#); SQLSTATE: [HY000](#)

Message: Cannot rename '%s' to '%s' for space ID %lu because the source file does not exist.

[ER\\_IB\\_MSG\\_293](#) was added in 8.0.11.

- Error number: [MY-012119](#); Symbol: [ER\\_IB\\_MSG\\_294](#); SQLSTATE: [HY000](#)

Message: Cannot rename '%s' to '%s' for space ID %lu because the target file exists. Remove the target file and try again.

[ER\\_IB\\_MSG\\_294](#) was added in 8.0.11.

- Error number: [MY-012120](#); Symbol: [ER\\_IB\\_MSG\\_295](#); SQLSTATE: [HY000](#)

Message: Cannot rename file '%s' (space id %lu) retried %llu times. There are either pending IOs or flushes or the file is being extended.

[ER\\_IB\\_MSG\\_295](#) was added in 8.0.11.

- Error number: [MY-012121](#); Symbol: [ER\\_IB\\_MSG\\_296](#); SQLSTATE: [HY000](#)

Message: Cannot find space id %lu in the tablespace memory cache, though the file '%s' in a rename operation should have that ID.

[ER\\_IB\\_MSG\\_296](#) was added in 8.0.11.

- Error number: [MY-012122](#); Symbol: [ER\\_IB\\_MSG\\_297](#); SQLSTATE: [HY000](#)

Message: Rename waiting for IO to resume

[ER\\_IB\\_MSG\\_297](#) was added in 8.0.11.

- Error number: [MY-012123](#); Symbol: [ER\\_IB\\_MSG\\_298](#); SQLSTATE: [HY000](#)

Message: Cannot find tablespace for '%s' in the tablespace memory cache

[ER\\_IB\\_MSG\\_298](#) was added in 8.0.11.

- Error number: [MY-012124](#); Symbol: [ER\\_IB\\_MSG\\_299](#); SQLSTATE: [HY000](#)

Message: Cannot find tablespace for '%s' in the tablespace memory cache

[ER\\_IB\\_MSG\\_299](#) was added in 8.0.11.

- Error number: [MY-012125](#); Symbol: [ER\\_IB\\_MSG\\_300](#); SQLSTATE: [HY000](#)

Message: Tablespace '%s' is already in the tablespace memory cache

[ER\\_IB\\_MSG\\_300](#) was added in 8.0.11.

- Error number: [MY-012126](#); Symbol: [ER\\_IB\\_MSG\\_301](#); SQLSTATE: [HY000](#)

Message: Cannot create file '%s'

---

[ER\\_IB\\_MSG\\_301](#) was added in 8.0.11.

- Error number: [MY-012127](#); Symbol: [ER\\_IB\\_MSG\\_302](#); SQLSTATE: [HY000](#)

Message: The file '%s' already exists though the corresponding table did not exist. Have you moved InnoDB .ibd files around without using the SQL commands DISCARD TABLESPACE and IMPORT TABLESPACE, or did mysqld crash in the middle of CREATE TABLE? You can resolve the problem by removing the file '%s' under the 'datadir' of MySQL.

[ER\\_IB\\_MSG\\_302](#) was added in 8.0.11, removed after 8.0.16.

- Error number: [MY-012127](#); Symbol: [ER\\_IB\\_MSG\\_UNEXPECTED\\_FILE\\_EXISTS](#); SQLSTATE: [HY000](#)

Message: The file '%s' already exists though the corresponding table did not exist. Have you moved InnoDB .ibd files around without using the SQL commands DISCARD TABLESPACE and IMPORT TABLESPACE, or did mysqld crash in the middle of CREATE TABLE? You can resolve the problem by removing the file '%s' under the 'datadir' of MySQL.

[ER\\_IB\\_MSG\\_UNEXPECTED\\_FILE\\_EXISTS](#) was added in 8.0.17.

- Error number: [MY-012128](#); Symbol: [ER\\_IB\\_MSG\\_303](#); SQLSTATE: [HY000](#)

Message: posix\_fallocate(): Failed to preallocate data for file %s, desired size %llu Operating system error number %d - %s. Check that the disk is not full or a disk quota exceeded. Make sure the file system supports this function. Refer to your operating system documentation for operating system error code information.

[ER\\_IB\\_MSG\\_303](#) was added in 8.0.11.

- Error number: [MY-012129](#); Symbol: [ER\\_IB\\_MSG\\_304](#); SQLSTATE: [HY000](#)

Message: Could not write the first page to tablespace '%s'

[ER\\_IB\\_MSG\\_304](#) was added in 8.0.11.

- Error number: [MY-012130](#); Symbol: [ER\\_IB\\_MSG\\_305](#); SQLSTATE: [HY000](#)

Message: File flush of tablespace '%s' failed

[ER\\_IB\\_MSG\\_305](#) was added in 8.0.11.

- Error number: [MY-012131](#); Symbol: [ER\\_IB\\_MSG\\_306](#); SQLSTATE: [HY000](#)

Message: Could not find a valid tablespace file for `%s`. %s

[ER\\_IB\\_MSG\\_306](#) was added in 8.0.11.

- Error number: [MY-012132](#); Symbol: [ER\\_IB\\_MSG\\_307](#); SQLSTATE: [HY000](#)

Message: Ignoring data file '%s' with space ID %lu. Another data file called '%s' exists with the same space ID

[ER\\_IB\\_MSG\\_307](#) was added in 8.0.11.

- Error number: [MY-012133](#); Symbol: [ER\\_IB\\_MSG\\_308](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_308](#) was added in 8.0.11.

- Error number: [MY-012134](#); Symbol: [ER\\_IB\\_MSG\\_309](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_309](#) was added in 8.0.11.

- Error number: [MY-012135](#); Symbol: [ER\\_IB\\_MSG\\_310](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_310](#) was added in 8.0.11.

- Error number: [MY-012136](#); Symbol: [ER\\_IB\\_MSG\\_311](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_311](#) was added in 8.0.11.

- Error number: [MY-012137](#); Symbol: [ER\\_IB\\_MSG\\_312](#); SQLSTATE: [HY000](#)

Message: Can't set encryption information for tablespace %s!

[ER\\_IB\\_MSG\\_312](#) was added in 8.0.11.

- Error number: [MY-012138](#); Symbol: [ER\\_IB\\_MSG\\_313](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_313](#) was added in 8.0.11.

- Error number: [MY-012139](#); Symbol: [ER\\_IB\\_MSG\\_314](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_314](#) was added in 8.0.11.

- Error number: [MY-012140](#); Symbol: [ER\\_IB\\_MSG\\_315](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_315](#) was added in 8.0.11.

- Error number: [MY-012141](#); Symbol: [ER\\_IB\\_MSG\\_316](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_316](#) was added in 8.0.11.

- Error number: [MY-012142](#); Symbol: [ER\\_IB\\_MSG\\_317](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_317](#) was added in 8.0.11.

- Error number: [MY-012143](#); Symbol: [ER\\_IB\\_MSG\\_318](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_318](#) was added in 8.0.11.

- Error number: [MY-012144](#); Symbol: [ER\\_IB\\_MSG\\_319](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_319](#) was added in 8.0.11.

- Error number: [MY-012145](#); Symbol: [ER\\_IB\\_MSG\\_320](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_320](#) was added in 8.0.11.

- Error number: [MY-012146](#); Symbol: [ER\\_IB\\_MSG\\_321](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_321](#) was added in 8.0.11.

- Error number: [MY-012147](#); Symbol: [ER\\_IB\\_MSG\\_322](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_322](#) was added in 8.0.11.

- Error number: [MY-012148](#); Symbol: [ER\\_IB\\_MSG\\_323](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_323](#) was added in 8.0.11.

- Error number: [MY-012149](#); Symbol: [ER\\_IB\\_MSG\\_324](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_324](#) was added in 8.0.11.

- Error number: [MY-012150](#); Symbol: [ER\\_IB\\_MSG\\_325](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_325](#) was added in 8.0.11.

- Error number: [MY-012151](#); Symbol: [ER\\_IB\\_MSG\\_326](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_326](#) was added in 8.0.11.

- Error number: [MY-012152](#); Symbol: [ER\\_IB\\_MSG\\_327](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_327](#) was added in 8.0.11, removed after 8.0.27.

- Error number: [MY-012153](#); Symbol: [ER\\_IB\\_MSG\\_328](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_328](#) was added in 8.0.11.

- Error number: [MY-012154](#); Symbol: [ER\\_IB\\_MSG\\_329](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_329](#) was added in 8.0.11.

- Error number: [MY-012155](#); Symbol: [ER\\_IB\\_MSG\\_330](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_330](#) was added in 8.0.11.

- Error number: [MY-012156](#); Symbol: [ER\\_IB\\_MSG\\_331](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_331](#) was added in 8.0.11.

- Error number: [MY-012157](#); Symbol: [ER\\_IB\\_MSG\\_332](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_332](#) was added in 8.0.11.

- Error number: [MY-012158](#); Symbol: [ER\\_IB\\_MSG\\_333](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_333](#) was added in 8.0.11.

- Error number: [MY-012159](#); Symbol: [ER\\_IB\\_MSG\\_334](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_334](#) was added in 8.0.11.

- Error number: [MY-012160](#); Symbol: [ER\\_IB\\_MSG\\_335](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_335](#) was added in 8.0.11.

- Error number: [MY-012161](#); Symbol: [ER\\_IB\\_MSG\\_336](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_336](#) was added in 8.0.11.

- Error number: [MY-012162](#); Symbol: [ER\\_IB\\_MSG\\_337](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_337](#) was added in 8.0.11.

- Error number: [MY-012163](#); Symbol: [ER\\_IB\\_MSG\\_338](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_338](#) was added in 8.0.11.

- Error number: [MY-012164](#); Symbol: [ER\\_IB\\_MSG\\_339](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_339](#) was added in 8.0.11.

- Error number: [MY-012165](#); Symbol: [ER\\_IB\\_MSG\\_340](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_340](#) was added in 8.0.11.

- Error number: [MY-012166](#); Symbol: [ER\\_IB\\_MSG\\_341](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_341](#) was added in 8.0.11.

- Error number: [MY-012167](#); Symbol: [ER\\_IB\\_MSG\\_342](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_342](#) was added in 8.0.11.

- Error number: [MY-012168](#); Symbol: [ER\\_IB\\_MSG\\_343](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_343](#) was added in 8.0.11.

- Error number: [MY-012169](#); Symbol: [ER\\_IB\\_MSG\\_344](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_344](#) was added in 8.0.11.

- Error number: [MY-012170](#); Symbol: [ER\\_IB\\_MSG\\_345](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_345](#) was added in 8.0.11.

- Error number: [MY-012171](#); Symbol: [ER\\_IB\\_MSG\\_346](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_346](#) was added in 8.0.11.

- Error number: [MY-012172](#); Symbol: [ER\\_IB\\_MSG\\_347](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_347](#) was added in 8.0.11.

- Error number: [MY-012173](#); Symbol: [ER\\_IB\\_MSG\\_348](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_348](#) was added in 8.0.11.

- Error number: [MY-012174](#); Symbol: [ER\\_IB\\_MSG\\_349](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_349](#) was added in 8.0.11.

- Error number: [MY-012175](#); Symbol: [ER\\_IB\\_MSG\\_350](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_350](#) was added in 8.0.11.

- Error number: [MY-012176](#); Symbol: [ER\\_IB\\_MSG\\_351](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_351](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012177](#); Symbol: [ER\\_IB\\_MSG\\_352](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_352](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012177](#); Symbol: [ER\\_IB\\_MSG\\_UNPROTECTED\\_LOCATION\\_ALLOWED](#); SQLSTATE: [HY000](#)

Message: The datafile '%s' for tablespace %s is in an unprotected location. This file cannot be recovered after a crash until this location is added to innodb\_directories.

[ER\\_IB\\_MSG\\_UNPROTECTED\\_LOCATION\\_ALLOWED](#) was added in 8.0.21.

- Error number: [MY-012178](#); Symbol: [ER\\_IB\\_MSG\\_353](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_353](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012179](#); Symbol: [ER\\_IB\\_MSG\\_354](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_354](#) was added in 8.0.11.

- Error number: [MY-012180](#); Symbol: [ER\\_IB\\_MSG\\_355](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_355](#) was added in 8.0.11.

- Error number: [MY-012181](#); Symbol: [ER\\_IB\\_MSG\\_356](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_356](#) was added in 8.0.11.

- Error number: [MY-012182](#); Symbol: [ER\\_IB\\_MSG\\_357](#); SQLSTATE: [HY000](#)



---

Message: %s

[ER\\_IB\\_MSG\\_357](#) was added in 8.0.11.

- Error number: [MY-012183](#); Symbol: [ER\\_IB\\_MSG\\_358](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_358](#) was added in 8.0.11.

- Error number: [MY-012184](#); Symbol: [ER\\_IB\\_MSG\\_359](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_359](#) was added in 8.0.11.

- Error number: [MY-012185](#); Symbol: [ER\\_IB\\_MSG\\_360](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_360](#) was added in 8.0.11.

- Error number: [MY-012186](#); Symbol: [ER\\_IB\\_MSG\\_361](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_361](#) was added in 8.0.11.

- Error number: [MY-012187](#); Symbol: [ER\\_IB\\_MSG\\_362](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_362](#) was added in 8.0.11.

- Error number: [MY-012188](#); Symbol: [ER\\_IB\\_MSG\\_363](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_363](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012189](#); Symbol: [ER\\_IB\\_MSG\\_364](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_364](#) was added in 8.0.11.

- Error number: [MY-012190](#); Symbol: [ER\\_IB\\_MSG\\_365](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_365](#) was added in 8.0.11.

- Error number: [MY-012191](#); Symbol: [ER\\_IB\\_MSG\\_366](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_366](#) was added in 8.0.11, removed after 8.0.18.

- Error number: [MY-012191](#); Symbol: [ER\\_IB\\_MSG\\_IGNORE\\_SCAN\\_PATH](#); SQLSTATE: [HY000](#)

---

Message: Scan path '%s' is ignored because %s

[ER\\_IB\\_MSG\\_IGNORE\\_SCAN\\_PATH](#) was added in 8.0.19.

- Error number: [MY-012192](#); Symbol: [ER\\_IB\\_MSG\\_367](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_367](#) was added in 8.0.11.

- Error number: [MY-012193](#); Symbol: [ER\\_IB\\_MSG\\_368](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_368](#) was added in 8.0.11.

- Error number: [MY-012194](#); Symbol: [ER\\_IB\\_MSG\\_369](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_369](#) was added in 8.0.11.

- Error number: [MY-012195](#); Symbol: [ER\\_IB\\_MSG\\_370](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_370](#) was added in 8.0.11.

- Error number: [MY-012196](#); Symbol: [ER\\_IB\\_MSG\\_371](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_371](#) was added in 8.0.11.

- Error number: [MY-012197](#); Symbol: [ER\\_IB\\_MSG\\_372](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_372](#) was added in 8.0.11.

- Error number: [MY-012198](#); Symbol: [ER\\_IB\\_MSG\\_373](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_373](#) was added in 8.0.11.

- Error number: [MY-012199](#); Symbol: [ER\\_IB\\_MSG\\_374](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_374](#) was added in 8.0.11.

- Error number: [MY-012200](#); Symbol: [ER\\_IB\\_MSG\\_375](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_375](#) was added in 8.0.11.

- Error number: [MY-012201](#); Symbol: [ER\\_IB\\_MSG\\_376](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_376](#) was added in 8.0.11.

- Error number: [MY-012202](#); Symbol: [ER\\_IB\\_MSG\\_377](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_377](#) was added in 8.0.11.

- Error number: [MY-012203](#); Symbol: [ER\\_IB\\_MSG\\_378](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_378](#) was added in 8.0.11.

- Error number: [MY-012204](#); Symbol: [ER\\_IB\\_MSG\\_379](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_379](#) was added in 8.0.11.

- Error number: [MY-012205](#); Symbol: [ER\\_IB\\_MSG\\_380](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_380](#) was added in 8.0.11.

- Error number: [MY-012206](#); Symbol: [ER\\_IB\\_MSG\\_381](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_381](#) was added in 8.0.11.

- Error number: [MY-012207](#); Symbol: [ER\\_IB\\_MSG\\_382](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_382](#) was added in 8.0.11.

- Error number: [MY-012208](#); Symbol: [ER\\_IB\\_MSG\\_383](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_383](#) was added in 8.0.11.

- Error number: [MY-012209](#); Symbol: [ER\\_IB\\_MSG\\_384](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_384](#) was added in 8.0.11.

- Error number: [MY-012210](#); Symbol: [ER\\_IB\\_MSG\\_385](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_385](#) was added in 8.0.11.

- Error number: [MY-012211](#); Symbol: [ER\\_IB\\_MSG\\_386](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_386](#) was added in 8.0.11.

- Error number: [MY-012212](#); Symbol: [ER\\_IB\\_MSG\\_387](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_387](#) was added in 8.0.11.

- Error number: [MY-012213](#); Symbol: [ER\\_IB\\_MSG\\_388](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_388](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012213](#); Symbol: [ER\\_IB\\_MSG\\_GENERAL\\_TABLESPACE\\_UNDER\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: A general tablespace cannot be located under the datadir. Cannot open file '%s'.

[ER\\_IB\\_MSG\\_GENERAL\\_TABLESPACE\\_UNDER\\_DATADIR](#) was added in 8.0.21.

- Error number: [MY-012214](#); Symbol: [ER\\_IB\\_MSG\\_389](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_389](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012214](#); Symbol: [ER\\_IB\\_MSG\\_IMPLICIT\\_TABLESPACE\\_IN\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: A file-per-table tablespace cannot be located in the datadir. Cannot open file '%s'.

[ER\\_IB\\_MSG\\_IMPLICIT\\_TABLESPACE\\_IN\\_DATADIR](#) was added in 8.0.21.

- Error number: [MY-012215](#); Symbol: [ER\\_IB\\_MSG\\_390](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_390](#) was added in 8.0.11.

- Error number: [MY-012216](#); Symbol: [ER\\_IB\\_MSG\\_391](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_391](#) was added in 8.0.11.

- Error number: [MY-012217](#); Symbol: [ER\\_IB\\_MSG\\_392](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_392](#) was added in 8.0.11.

- Error number: [MY-012218](#); Symbol: [ER\\_IB\\_MSG\\_393](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_393](#) was added in 8.0.11.

- 
- Error number: [MY-012219](#); Symbol: [ER\\_IB\\_MSG\\_394](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_394](#) was added in 8.0.11.
  - Error number: [MY-012220](#); Symbol: [ER\\_IB\\_MSG\\_395](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_395](#) was added in 8.0.11.
  - Error number: [MY-012221](#); Symbol: [ER\\_IB\\_MSG\\_396](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_396](#) was added in 8.0.11.
  - Error number: [MY-012222](#); Symbol: [ER\\_IB\\_MSG\\_397](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_397](#) was added in 8.0.11.
  - Error number: [MY-012223](#); Symbol: [ER\\_IB\\_MSG\\_398](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_398](#) was added in 8.0.11.
  - Error number: [MY-012224](#); Symbol: [ER\\_IB\\_MSG\\_399](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_399](#) was added in 8.0.11.
  - Error number: [MY-012225](#); Symbol: [ER\\_IB\\_MSG\\_400](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_400](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012226](#); Symbol: [ER\\_IB\\_MSG\\_401](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_401](#) was added in 8.0.11.
  - Error number: [MY-012227](#); Symbol: [ER\\_IB\\_MSG\\_402](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_402](#) was added in 8.0.11.
  - Error number: [MY-012228](#); Symbol: [ER\\_IB\\_MSG\\_403](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_403](#) was added in 8.0.11.

- 
- Error number: [MY-012229](#); Symbol: [ER\\_IB\\_MSG\\_404](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_404](#) was added in 8.0.11.
  - Error number: [MY-012230](#); Symbol: [ER\\_IB\\_MSG\\_405](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_405](#) was added in 8.0.11.
  - Error number: [MY-012231](#); Symbol: [ER\\_IB\\_MSG\\_406](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_406](#) was added in 8.0.11.
  - Error number: [MY-012232](#); Symbol: [ER\\_IB\\_MSG\\_407](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_407](#) was added in 8.0.11.
  - Error number: [MY-012233](#); Symbol: [ER\\_IB\\_MSG\\_408](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_408](#) was added in 8.0.11.
  - Error number: [MY-012234](#); Symbol: [ER\\_IB\\_MSG\\_409](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_409](#) was added in 8.0.11.
  - Error number: [MY-012235](#); Symbol: [ER\\_IB\\_MSG\\_410](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_410](#) was added in 8.0.11.
  - Error number: [MY-012236](#); Symbol: [ER\\_IB\\_MSG\\_411](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_411](#) was added in 8.0.11.
  - Error number: [MY-012237](#); Symbol: [ER\\_IB\\_MSG\\_412](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_412](#) was added in 8.0.11.
  - Error number: [MY-012238](#); Symbol: [ER\\_IB\\_MSG\\_413](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_413](#) was added in 8.0.11.

- 
- Error number: [MY-012239](#); Symbol: [ER\\_IB\\_MSG\\_414](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_414](#) was added in 8.0.11.
  - Error number: [MY-012240](#); Symbol: [ER\\_IB\\_MSG\\_415](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_415](#) was added in 8.0.11.
  - Error number: [MY-012241](#); Symbol: [ER\\_IB\\_MSG\\_416](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_416](#) was added in 8.0.11.
  - Error number: [MY-012242](#); Symbol: [ER\\_IB\\_MSG\\_417](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_417](#) was added in 8.0.11.
  - Error number: [MY-012243](#); Symbol: [ER\\_IB\\_MSG\\_418](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_418](#) was added in 8.0.11.
  - Error number: [MY-012244](#); Symbol: [ER\\_IB\\_MSG\\_419](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_419](#) was added in 8.0.11.
  - Error number: [MY-012245](#); Symbol: [ER\\_IB\\_MSG\\_420](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_420](#) was added in 8.0.11.
  - Error number: [MY-012246](#); Symbol: [ER\\_IB\\_MSG\\_421](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_421](#) was added in 8.0.11.
  - Error number: [MY-012247](#); Symbol: [ER\\_IB\\_MSG\\_422](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_422](#) was added in 8.0.11.
  - Error number: [MY-012248](#); Symbol: [ER\\_IB\\_MSG\\_423](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_423](#) was added in 8.0.11.

- 
- Error number: [MY-012249](#); Symbol: [ER\\_IB\\_MSG\\_424](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_424](#) was added in 8.0.11.
  - Error number: [MY-012250](#); Symbol: [ER\\_IB\\_MSG\\_425](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_425](#) was added in 8.0.11.
  - Error number: [MY-012251](#); Symbol: [ER\\_IB\\_MSG\\_426](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_426](#) was added in 8.0.11.
  - Error number: [MY-012252](#); Symbol: [ER\\_IB\\_MSG\\_427](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_427](#) was added in 8.0.11.
  - Error number: [MY-012253](#); Symbol: [ER\\_IB\\_MSG\\_428](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_428](#) was added in 8.0.11.
  - Error number: [MY-012254](#); Symbol: [ER\\_IB\\_MSG\\_429](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_429](#) was added in 8.0.11.
  - Error number: [MY-012255](#); Symbol: [ER\\_IB\\_MSG\\_430](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_430](#) was added in 8.0.11.
  - Error number: [MY-012256](#); Symbol: [ER\\_IB\\_MSG\\_431](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_431](#) was added in 8.0.11.
  - Error number: [MY-012257](#); Symbol: [ER\\_IB\\_MSG\\_432](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_432](#) was added in 8.0.11.
  - Error number: [MY-012258](#); Symbol: [ER\\_IB\\_MSG\\_433](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_433](#) was added in 8.0.11.



- 
- Error number: [MY-012259](#); Symbol: [ER\\_IB\\_MSG\\_434](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_434](#) was added in 8.0.11.
  - Error number: [MY-012260](#); Symbol: [ER\\_IB\\_MSG\\_435](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_435](#) was added in 8.0.11.
  - Error number: [MY-012261](#); Symbol: [ER\\_IB\\_MSG\\_436](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_436](#) was added in 8.0.11.
  - Error number: [MY-012262](#); Symbol: [ER\\_IB\\_MSG\\_437](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_437](#) was added in 8.0.11.
  - Error number: [MY-012263](#); Symbol: [ER\\_IB\\_MSG\\_438](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_438](#) was added in 8.0.11.
  - Error number: [MY-012264](#); Symbol: [ER\\_IB\\_MSG\\_439](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_439](#) was added in 8.0.11.
  - Error number: [MY-012265](#); Symbol: [ER\\_IB\\_MSG\\_440](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_440](#) was added in 8.0.11.
  - Error number: [MY-012266](#); Symbol: [ER\\_IB\\_MSG\\_441](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_441](#) was added in 8.0.11.
  - Error number: [MY-012267](#); Symbol: [ER\\_IB\\_MSG\\_442](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_442](#) was added in 8.0.11.
  - Error number: [MY-012268](#); Symbol: [ER\\_IB\\_MSG\\_443](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_443](#) was added in 8.0.11.

- 
- Error number: [MY-012269](#); Symbol: [ER\\_IB\\_MSG\\_444](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_444](#) was added in 8.0.11, removed after 8.0.36.
  - Error number: [MY-012270](#); Symbol: [ER\\_IB\\_MSG\\_445](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_445](#) was added in 8.0.11.
  - Error number: [MY-012271](#); Symbol: [ER\\_IB\\_MSG\\_446](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_446](#) was added in 8.0.11.
  - Error number: [MY-012272](#); Symbol: [ER\\_IB\\_MSG\\_447](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_447](#) was added in 8.0.11.
  - Error number: [MY-012273](#); Symbol: [ER\\_IB\\_MSG\\_448](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_448](#) was added in 8.0.11.
  - Error number: [MY-012274](#); Symbol: [ER\\_IB\\_MSG\\_449](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_449](#) was added in 8.0.11.
  - Error number: [MY-012275](#); Symbol: [ER\\_IB\\_MSG\\_450](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_450](#) was added in 8.0.11.
  - Error number: [MY-012276](#); Symbol: [ER\\_IB\\_MSG\\_451](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_451](#) was added in 8.0.11.
  - Error number: [MY-012277](#); Symbol: [ER\\_IB\\_MSG\\_452](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_452](#) was added in 8.0.11.
  - Error number: [MY-012278](#); Symbol: [ER\\_IB\\_MSG\\_453](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_453](#) was added in 8.0.11.

- 
- Error number: [MY-012279](#); Symbol: [ER\\_IB\\_MSG\\_454](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_454](#) was added in 8.0.11.
  - Error number: [MY-012280](#); Symbol: [ER\\_IB\\_MSG\\_455](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_455](#) was added in 8.0.11.
  - Error number: [MY-012281](#); Symbol: [ER\\_IB\\_MSG\\_456](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_456](#) was added in 8.0.11.
  - Error number: [MY-012282](#); Symbol: [ER\\_IB\\_MSG\\_457](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_457](#) was added in 8.0.11.
  - Error number: [MY-012283](#); Symbol: [ER\\_IB\\_MSG\\_458](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_458](#) was added in 8.0.11.
  - Error number: [MY-012284](#); Symbol: [ER\\_IB\\_MSG\\_459](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_459](#) was added in 8.0.11.
  - Error number: [MY-012285](#); Symbol: [ER\\_IB\\_MSG\\_460](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_460](#) was added in 8.0.11.
  - Error number: [MY-012286](#); Symbol: [ER\\_IB\\_MSG\\_461](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_461](#) was added in 8.0.11.
  - Error number: [MY-012287](#); Symbol: [ER\\_IB\\_MSG\\_462](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_462](#) was added in 8.0.11.
  - Error number: [MY-012288](#); Symbol: [ER\\_IB\\_MSG\\_463](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_463](#) was added in 8.0.11.

- 
- Error number: [MY-012289](#); Symbol: [ER\\_IB\\_MSG\\_464](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_464](#) was added in 8.0.11.
  - Error number: [MY-012290](#); Symbol: [ER\\_IB\\_MSG\\_465](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_465](#) was added in 8.0.11.
  - Error number: [MY-012291](#); Symbol: [ER\\_IB\\_MSG\\_466](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_466](#) was added in 8.0.11.
  - Error number: [MY-012292](#); Symbol: [ER\\_IB\\_MSG\\_467](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_467](#) was added in 8.0.11.
  - Error number: [MY-012293](#); Symbol: [ER\\_IB\\_MSG\\_468](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_468](#) was added in 8.0.11.
  - Error number: [MY-012294](#); Symbol: [ER\\_IB\\_MSG\\_469](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_469](#) was added in 8.0.11.
  - Error number: [MY-012295](#); Symbol: [ER\\_IB\\_MSG\\_470](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_470](#) was added in 8.0.11.
  - Error number: [MY-012296](#); Symbol: [ER\\_IB\\_MSG\\_471](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_471](#) was added in 8.0.11.
  - Error number: [MY-012297](#); Symbol: [ER\\_IB\\_MSG\\_472](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_472](#) was added in 8.0.11.
  - Error number: [MY-012298](#); Symbol: [ER\\_IB\\_MSG\\_473](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_473](#) was added in 8.0.11.

- 
- Error number: [MY-012299](#); Symbol: [ER\\_IB\\_MSG\\_474](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_474](#) was added in 8.0.11.
  - Error number: [MY-012300](#); Symbol: [ER\\_IB\\_MSG\\_475](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_475](#) was added in 8.0.11.
  - Error number: [MY-012301](#); Symbol: [ER\\_IB\\_MSG\\_476](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_476](#) was added in 8.0.11.
  - Error number: [MY-012302](#); Symbol: [ER\\_IB\\_MSG\\_477](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_477](#) was added in 8.0.11.
  - Error number: [MY-012303](#); Symbol: [ER\\_IB\\_MSG\\_478](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_478](#) was added in 8.0.11.
  - Error number: [MY-012304](#); Symbol: [ER\\_IB\\_MSG\\_479](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_479](#) was added in 8.0.11.
  - Error number: [MY-012305](#); Symbol: [ER\\_IB\\_MSG\\_480](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_480](#) was added in 8.0.11.
  - Error number: [MY-012306](#); Symbol: [ER\\_IB\\_MSG\\_481](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_481](#) was added in 8.0.11.
  - Error number: [MY-012307](#); Symbol: [ER\\_IB\\_MSG\\_482](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_482](#) was added in 8.0.11.
  - Error number: [MY-012308](#); Symbol: [ER\\_IB\\_MSG\\_483](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_483](#) was added in 8.0.11.

- 
- Error number: [MY-012309](#); Symbol: [ER\\_IB\\_MSG\\_484](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_484](#) was added in 8.0.11.
  - Error number: [MY-012310](#); Symbol: [ER\\_IB\\_MSG\\_485](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_485](#) was added in 8.0.11.
  - Error number: [MY-012311](#); Symbol: [ER\\_IB\\_MSG\\_486](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_486](#) was added in 8.0.11.
  - Error number: [MY-012312](#); Symbol: [ER\\_IB\\_MSG\\_487](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_487](#) was added in 8.0.11.
  - Error number: [MY-012313](#); Symbol: [ER\\_IB\\_MSG\\_488](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_488](#) was added in 8.0.11.
  - Error number: [MY-012314](#); Symbol: [ER\\_IB\\_MSG\\_489](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_489](#) was added in 8.0.11.
  - Error number: [MY-012315](#); Symbol: [ER\\_IB\\_MSG\\_490](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_490](#) was added in 8.0.11.
  - Error number: [MY-012316](#); Symbol: [ER\\_IB\\_MSG\\_491](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_491](#) was added in 8.0.11.
  - Error number: [MY-012317](#); Symbol: [ER\\_IB\\_MSG\\_492](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_492](#) was added in 8.0.11.
  - Error number: [MY-012318](#); Symbol: [ER\\_IB\\_MSG\\_493](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_493](#) was added in 8.0.11.

- 
- Error number: [MY-012319](#); Symbol: [ER\\_IB\\_MSG\\_494](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_494](#) was added in 8.0.11.
  - Error number: [MY-012320](#); Symbol: [ER\\_IB\\_MSG\\_495](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_495](#) was added in 8.0.11.
  - Error number: [MY-012321](#); Symbol: [ER\\_IB\\_MSG\\_496](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_496](#) was added in 8.0.11.
  - Error number: [MY-012322](#); Symbol: [ER\\_IB\\_MSG\\_497](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_497](#) was added in 8.0.11.
  - Error number: [MY-012323](#); Symbol: [ER\\_IB\\_MSG\\_498](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_498](#) was added in 8.0.11.
  - Error number: [MY-012324](#); Symbol: [ER\\_IB\\_MSG\\_499](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_499](#) was added in 8.0.11.
  - Error number: [MY-012325](#); Symbol: [ER\\_IB\\_MSG\\_500](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_500](#) was added in 8.0.11.
  - Error number: [MY-012326](#); Symbol: [ER\\_IB\\_MSG\\_501](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_501](#) was added in 8.0.11.
  - Error number: [MY-012327](#); Symbol: [ER\\_IB\\_MSG\\_502](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_502](#) was added in 8.0.11.
  - Error number: [MY-012328](#); Symbol: [ER\\_IB\\_MSG\\_503](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_503](#) was added in 8.0.11.

- 
- Error number: [MY-012329](#); Symbol: [ER\\_IB\\_MSG\\_504](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_504](#) was added in 8.0.11.
  - Error number: [MY-012330](#); Symbol: [ER\\_IB\\_MSG\\_505](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_505](#) was added in 8.0.11.
  - Error number: [MY-012331](#); Symbol: [ER\\_IB\\_MSG\\_506](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_506](#) was added in 8.0.11.
  - Error number: [MY-012332](#); Symbol: [ER\\_IB\\_MSG\\_507](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_507](#) was added in 8.0.11.
  - Error number: [MY-012333](#); Symbol: [ER\\_IB\\_MSG\\_508](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_508](#) was added in 8.0.11.
  - Error number: [MY-012334](#); Symbol: [ER\\_IB\\_MSG\\_509](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_509](#) was added in 8.0.11.
  - Error number: [MY-012335](#); Symbol: [ER\\_IB\\_MSG\\_510](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_510](#) was added in 8.0.11.
  - Error number: [MY-012336](#); Symbol: [ER\\_IB\\_MSG\\_511](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_511](#) was added in 8.0.11.
  - Error number: [MY-012337](#); Symbol: [ER\\_IB\\_MSG\\_512](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_512](#) was added in 8.0.11.
  - Error number: [MY-012338](#); Symbol: [ER\\_IB\\_MSG\\_513](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_513](#) was added in 8.0.11.



- 
- Error number: [MY-012339](#); Symbol: [ER\\_IB\\_MSG\\_514](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_514](#) was added in 8.0.11.
  - Error number: [MY-012340](#); Symbol: [ER\\_IB\\_MSG\\_515](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_515](#) was added in 8.0.11.
  - Error number: [MY-012341](#); Symbol: [ER\\_IB\\_MSG\\_516](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_516](#) was added in 8.0.11.
  - Error number: [MY-012342](#); Symbol: [ER\\_IB\\_MSG\\_517](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_517](#) was added in 8.0.11.
  - Error number: [MY-012343](#); Symbol: [ER\\_IB\\_MSG\\_518](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_518](#) was added in 8.0.11.
  - Error number: [MY-012344](#); Symbol: [ER\\_IB\\_MSG\\_519](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_519](#) was added in 8.0.11.
  - Error number: [MY-012345](#); Symbol: [ER\\_IB\\_MSG\\_520](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_520](#) was added in 8.0.11.
  - Error number: [MY-012346](#); Symbol: [ER\\_IB\\_MSG\\_521](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_521](#) was added in 8.0.11.
  - Error number: [MY-012347](#); Symbol: [ER\\_IB\\_MSG\\_522](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_522](#) was added in 8.0.11.
  - Error number: [MY-012348](#); Symbol: [ER\\_IB\\_MSG\\_523](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_523](#) was added in 8.0.11.

- 
- Error number: [MY-012349](#); Symbol: [ER\\_IB\\_MSG\\_524](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_524](#) was added in 8.0.11.
  - Error number: [MY-012350](#); Symbol: [ER\\_IB\\_MSG\\_525](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_525](#) was added in 8.0.11.
  - Error number: [MY-012351](#); Symbol: [ER\\_IB\\_MSG\\_526](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_526](#) was added in 8.0.11.
  - Error number: [MY-012352](#); Symbol: [ER\\_IB\\_MSG\\_527](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_527](#) was added in 8.0.11.
  - Error number: [MY-012353](#); Symbol: [ER\\_IB\\_MSG\\_528](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_528](#) was added in 8.0.11, removed after 8.0.18.
  - Error number: [MY-012354](#); Symbol: [ER\\_IB\\_MSG\\_529](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_529](#) was added in 8.0.11, removed after 8.0.18.
  - Error number: [MY-012355](#); Symbol: [ER\\_IB\\_MSG\\_530](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_530](#) was added in 8.0.11.
  - Error number: [MY-012356](#); Symbol: [ER\\_IB\\_MSG\\_531](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_531](#) was added in 8.0.11.
  - Error number: [MY-012357](#); Symbol: [ER\\_IB\\_MSG\\_532](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_532](#) was added in 8.0.11.
  - Error number: [MY-012358](#); Symbol: [ER\\_IB\\_MSG\\_533](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_533](#) was added in 8.0.11.

- 
- Error number: [MY-012359](#); Symbol: [ER\\_IB\\_MSG\\_534](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_534](#) was added in 8.0.11.
  - Error number: [MY-012360](#); Symbol: [ER\\_IB\\_MSG\\_535](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_535](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012361](#); Symbol: [ER\\_IB\\_MSG\\_536](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_536](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012362](#); Symbol: [ER\\_IB\\_MSG\\_537](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_537](#) was added in 8.0.11.
  - Error number: [MY-012363](#); Symbol: [ER\\_IB\\_MSG\\_538](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_538](#) was added in 8.0.11.
  - Error number: [MY-012364](#); Symbol: [ER\\_IB\\_MSG\\_539](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_539](#) was added in 8.0.11.
  - Error number: [MY-012365](#); Symbol: [ER\\_IB\\_MSG\\_540](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_540](#) was added in 8.0.11.
  - Error number: [MY-012366](#); Symbol: [ER\\_IB\\_MSG\\_541](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_541](#) was added in 8.0.11.
  - Error number: [MY-012367](#); Symbol: [ER\\_IB\\_MSG\\_542](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_542](#) was added in 8.0.11.
  - Error number: [MY-012368](#); Symbol: [ER\\_IB\\_MSG\\_543](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_543](#) was added in 8.0.11.

- 
- Error number: [MY-012369](#); Symbol: [ER\\_IB\\_MSG\\_544](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_544](#) was added in 8.0.11.
  - Error number: [MY-012370](#); Symbol: [ER\\_IB\\_MSG\\_545](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_545](#) was added in 8.0.11.
  - Error number: [MY-012371](#); Symbol: [ER\\_IB\\_MSG\\_546](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_546](#) was added in 8.0.11.
  - Error number: [MY-012372](#); Symbol: [ER\\_IB\\_MSG\\_547](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_547](#) was added in 8.0.11.
  - Error number: [MY-012373](#); Symbol: [ER\\_IB\\_MSG\\_548](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_548](#) was added in 8.0.11.
  - Error number: [MY-012374](#); Symbol: [ER\\_IB\\_MSG\\_549](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_549](#) was added in 8.0.11.
  - Error number: [MY-012375](#); Symbol: [ER\\_IB\\_MSG\\_550](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_550](#) was added in 8.0.11.
  - Error number: [MY-012376](#); Symbol: [ER\\_IB\\_MSG\\_551](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_551](#) was added in 8.0.11.
  - Error number: [MY-012377](#); Symbol: [ER\\_IB\\_MSG\\_552](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_552](#) was added in 8.0.11.
  - Error number: [MY-012378](#); Symbol: [ER\\_IB\\_MSG\\_553](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_553](#) was added in 8.0.11.

- 
- Error number: [MY-012379](#); Symbol: [ER\\_IB\\_MSG\\_554](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_554](#) was added in 8.0.11.
  - Error number: [MY-012380](#); Symbol: [ER\\_IB\\_MSG\\_555](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_555](#) was added in 8.0.11.
  - Error number: [MY-012381](#); Symbol: [ER\\_IB\\_MSG\\_556](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_556](#) was added in 8.0.11.
  - Error number: [MY-012382](#); Symbol: [ER\\_IB\\_MSG\\_557](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_557](#) was added in 8.0.11.
  - Error number: [MY-012383](#); Symbol: [ER\\_IB\\_MSG\\_558](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_558](#) was added in 8.0.11.
  - Error number: [MY-012384](#); Symbol: [ER\\_IB\\_MSG\\_559](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_559](#) was added in 8.0.11.
  - Error number: [MY-012385](#); Symbol: [ER\\_IB\\_MSG\\_560](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_560](#) was added in 8.0.11.
  - Error number: [MY-012386](#); Symbol: [ER\\_IB\\_MSG\\_561](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_561](#) was added in 8.0.11.
  - Error number: [MY-012387](#); Symbol: [ER\\_IB\\_MSG\\_562](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_562](#) was added in 8.0.11.
  - Error number: [MY-012388](#); Symbol: [ER\\_IB\\_MSG\\_563](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_563](#) was added in 8.0.11.

- 
- Error number: [MY-012389](#); Symbol: [ER\\_IB\\_MSG\\_564](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_564](#) was added in 8.0.11.
  - Error number: [MY-012390](#); Symbol: [ER\\_IB\\_MSG\\_565](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_565](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012390](#); Symbol: [ER\\_IB\\_MSG\\_INVALID\\_LOCATION\\_FOR\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot create a tablespace for table %s because the directory is not a valid location. %s  
[ER\\_IB\\_MSG\\_INVALID\\_LOCATION\\_FOR\\_TABLE](#) was added in 8.0.21.
  - Error number: [MY-012391](#); Symbol: [ER\\_IB\\_MSG\\_566](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_566](#) was added in 8.0.11.
  - Error number: [MY-012392](#); Symbol: [ER\\_IB\\_MSG\\_567](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_567](#) was added in 8.0.11.
  - Error number: [MY-012393](#); Symbol: [ER\\_IB\\_MSG\\_568](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_568](#) was added in 8.0.11.
  - Error number: [MY-012394](#); Symbol: [ER\\_IB\\_MSG\\_569](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_569](#) was added in 8.0.11.
  - Error number: [MY-012395](#); Symbol: [ER\\_IB\\_MSG\\_570](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_570](#) was added in 8.0.11.
  - Error number: [MY-012396](#); Symbol: [ER\\_IB\\_MSG\\_571](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_571](#) was added in 8.0.11.
  - Error number: [MY-012397](#); Symbol: [ER\\_IB\\_MSG\\_572](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_572](#) was added in 8.0.11, removed after 8.0.18.

- 
- Error number: [MY-012398](#); Symbol: [ER\\_IB\\_MSG\\_573](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_573](#) was added in 8.0.11.
  - Error number: [MY-012399](#); Symbol: [ER\\_IB\\_MSG\\_574](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_574](#) was added in 8.0.11.
  - Error number: [MY-012400](#); Symbol: [ER\\_IB\\_MSG\\_575](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_575](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012401](#); Symbol: [ER\\_IB\\_MSG\\_576](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_576](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012402](#); Symbol: [ER\\_IB\\_MSG\\_577](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_577](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012403](#); Symbol: [ER\\_IB\\_MSG\\_578](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_578](#) was added in 8.0.11.
  - Error number: [MY-012404](#); Symbol: [ER\\_IB\\_MSG\\_579](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_579](#) was added in 8.0.11.
  - Error number: [MY-012405](#); Symbol: [ER\\_IB\\_MSG\\_580](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_580](#) was added in 8.0.11.
  - Error number: [MY-012406](#); Symbol: [ER\\_IB\\_MSG\\_581](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_581](#) was added in 8.0.11.
  - Error number: [MY-012407](#); Symbol: [ER\\_IB\\_MSG\\_582](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_582](#) was added in 8.0.11.

- 
- Error number: [MY-012408](#); Symbol: [ER\\_IB\\_MSG\\_583](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_583](#) was added in 8.0.11.
  - Error number: [MY-012409](#); Symbol: [ER\\_IB\\_MSG\\_584](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_584](#) was added in 8.0.11.
  - Error number: [MY-012410](#); Symbol: [ER\\_IB\\_MSG\\_585](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_585](#) was added in 8.0.11.
  - Error number: [MY-012411](#); Symbol: [ER\\_IB\\_MSG\\_586](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_586](#) was added in 8.0.11.
  - Error number: [MY-012412](#); Symbol: [ER\\_IB\\_MSG\\_587](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_587](#) was added in 8.0.11.
  - Error number: [MY-012413](#); Symbol: [ER\\_IB\\_MSG\\_588](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_588](#) was added in 8.0.11.
  - Error number: [MY-012414](#); Symbol: [ER\\_IB\\_MSG\\_589](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_589](#) was added in 8.0.11.
  - Error number: [MY-012415](#); Symbol: [ER\\_IB\\_MSG\\_590](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_590](#) was added in 8.0.11.
  - Error number: [MY-012416](#); Symbol: [ER\\_IB\\_MSG\\_591](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_591](#) was added in 8.0.11.
  - Error number: [MY-012417](#); Symbol: [ER\\_IB\\_MSG\\_592](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_592](#) was added in 8.0.11.



- 
- Error number: [MY-012418](#); Symbol: [ER\\_IB\\_MSG\\_593](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_593](#) was added in 8.0.11.
  - Error number: [MY-012419](#); Symbol: [ER\\_IB\\_MSG\\_594](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_594](#) was added in 8.0.11.
  - Error number: [MY-012420](#); Symbol: [ER\\_IB\\_MSG\\_595](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_595](#) was added in 8.0.11.
  - Error number: [MY-012421](#); Symbol: [ER\\_IB\\_MSG\\_596](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_596](#) was added in 8.0.11.
  - Error number: [MY-012422](#); Symbol: [ER\\_IB\\_MSG\\_597](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_597](#) was added in 8.0.11.
  - Error number: [MY-012423](#); Symbol: [ER\\_IB\\_MSG\\_598](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_598](#) was added in 8.0.11.
  - Error number: [MY-012424](#); Symbol: [ER\\_IB\\_MSG\\_599](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_599](#) was added in 8.0.11.
  - Error number: [MY-012425](#); Symbol: [ER\\_IB\\_MSG\\_600](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_600](#) was added in 8.0.11.
  - Error number: [MY-012426](#); Symbol: [ER\\_IB\\_MSG\\_601](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_601](#) was added in 8.0.11.
  - Error number: [MY-012427](#); Symbol: [ER\\_IB\\_MSG\\_602](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_602](#) was added in 8.0.11.

- 
- Error number: [MY-012428](#); Symbol: [ER\\_IB\\_MSG\\_603](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_603](#) was added in 8.0.11.
  - Error number: [MY-012429](#); Symbol: [ER\\_IB\\_MSG\\_604](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_604](#) was added in 8.0.11.
  - Error number: [MY-012430](#); Symbol: [ER\\_IB\\_MSG\\_605](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_605](#) was added in 8.0.11.
  - Error number: [MY-012431](#); Symbol: [ER\\_IB\\_MSG\\_606](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_606](#) was added in 8.0.11.
  - Error number: [MY-012432](#); Symbol: [ER\\_IB\\_MSG\\_607](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_607](#) was added in 8.0.11.
  - Error number: [MY-012433](#); Symbol: [ER\\_IB\\_MSG\\_608](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_608](#) was added in 8.0.11.
  - Error number: [MY-012434](#); Symbol: [ER\\_IB\\_MSG\\_609](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_609](#) was added in 8.0.11.
  - Error number: [MY-012435](#); Symbol: [ER\\_IB\\_MSG\\_610](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_610](#) was added in 8.0.11.
  - Error number: [MY-012436](#); Symbol: [ER\\_IB\\_MSG\\_611](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_611](#) was added in 8.0.11.
  - Error number: [MY-012437](#); Symbol: [ER\\_IB\\_MSG\\_612](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_612](#) was added in 8.0.11.

- 
- Error number: [MY-012438](#); Symbol: [ER\\_IB\\_MSG\\_613](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_613](#) was added in 8.0.11.
  - Error number: [MY-012439](#); Symbol: [ER\\_IB\\_MSG\\_614](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_614](#) was added in 8.0.11.
  - Error number: [MY-012440](#); Symbol: [ER\\_IB\\_MSG\\_615](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_615](#) was added in 8.0.11.
  - Error number: [MY-012441](#); Symbol: [ER\\_IB\\_MSG\\_616](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_616](#) was added in 8.0.11.
  - Error number: [MY-012442](#); Symbol: [ER\\_IB\\_MSG\\_617](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_617](#) was added in 8.0.11.
  - Error number: [MY-012443](#); Symbol: [ER\\_IB\\_MSG\\_618](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_618](#) was added in 8.0.11.
  - Error number: [MY-012444](#); Symbol: [ER\\_IB\\_MSG\\_619](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_619](#) was added in 8.0.11.
  - Error number: [MY-012445](#); Symbol: [ER\\_IB\\_MSG\\_620](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_620](#) was added in 8.0.11.
  - Error number: [MY-012446](#); Symbol: [ER\\_IB\\_MSG\\_621](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_621](#) was added in 8.0.11.
  - Error number: [MY-012447](#); Symbol: [ER\\_IB\\_MSG\\_622](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_622](#) was added in 8.0.11.

- 
- Error number: [MY-012448](#); Symbol: [ER\\_IB\\_MSG\\_623](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_623](#) was added in 8.0.11.
  - Error number: [MY-012449](#); Symbol: [ER\\_IB\\_MSG\\_624](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_624](#) was added in 8.0.11.
  - Error number: [MY-012450](#); Symbol: [ER\\_IB\\_MSG\\_625](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_625](#) was added in 8.0.11.
  - Error number: [MY-012451](#); Symbol: [ER\\_IB\\_MSG\\_626](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_626](#) was added in 8.0.11.
  - Error number: [MY-012452](#); Symbol: [ER\\_IB\\_MSG\\_627](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_627](#) was added in 8.0.11.
  - Error number: [MY-012453](#); Symbol: [ER\\_IB\\_MSG\\_628](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_628](#) was added in 8.0.11.
  - Error number: [MY-012454](#); Symbol: [ER\\_IB\\_MSG\\_629](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_629](#) was added in 8.0.11.
  - Error number: [MY-012455](#); Symbol: [ER\\_IB\\_MSG\\_630](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_630](#) was added in 8.0.11.
  - Error number: [MY-012456](#); Symbol: [ER\\_IB\\_MSG\\_631](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_631](#) was added in 8.0.11.
  - Error number: [MY-012457](#); Symbol: [ER\\_IB\\_MSG\\_632](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_632](#) was added in 8.0.11.

- 
- Error number: [MY-012458](#); Symbol: [ER\\_IB\\_MSG\\_633](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_633](#) was added in 8.0.11.
  - Error number: [MY-012459](#); Symbol: [ER\\_IB\\_MSG\\_634](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_634](#) was added in 8.0.11.
  - Error number: [MY-012460](#); Symbol: [ER\\_IB\\_MSG\\_635](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_635](#) was added in 8.0.11.
  - Error number: [MY-012461](#); Symbol: [ER\\_IB\\_MSG\\_636](#); SQLSTATE: [HY000](#)  
Message: Blocked High Priority Transaction (ID %llu, Thread ID %s) forces rollback of the blocking transaction (ID %llu - %s).  
[ER\\_IB\\_MSG\\_636](#) was added in 8.0.11.
  - Error number: [MY-012462](#); Symbol: [ER\\_IB\\_MSG\\_637](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_637](#) was added in 8.0.11.
  - Error number: [MY-012463](#); Symbol: [ER\\_IB\\_MSG\\_638](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_638](#) was added in 8.0.11.
  - Error number: [MY-012464](#); Symbol: [ER\\_IB\\_MSG\\_639](#); SQLSTATE: [HY000](#)  
Message: Blocked High Priority Transaction (Thread ID %s) waking up the blocking transaction (ID %llu) by pretending it's a deadlock victim.  
[ER\\_IB\\_MSG\\_639](#) was added in 8.0.11.
  - Error number: [MY-012465](#); Symbol: [ER\\_IB\\_MSG\\_640](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_640](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012466](#); Symbol: [ER\\_IB\\_MSG\\_641](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_641](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012467](#); Symbol: [ER\\_IB\\_MSG\\_642](#); SQLSTATE: [HY000](#)  
Message: %s

---

[ER\\_IB\\_MSG\\_642](#) was added in 8.0.11.

- Error number: [MY-012468](#); Symbol: [ER\\_IB\\_MSG\\_643](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_643](#) was added in 8.0.11.

- Error number: [MY-012469](#); Symbol: [ER\\_IB\\_MSG\\_644](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_644](#) was added in 8.0.11.

- Error number: [MY-012470](#); Symbol: [ER\\_IB\\_MSG\\_645](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_645](#) was added in 8.0.11.

- Error number: [MY-012471](#); Symbol: [ER\\_IB\\_MSG\\_646](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_646](#) was added in 8.0.11.

- Error number: [MY-012472](#); Symbol: [ER\\_IB\\_MSG\\_647](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_647](#) was added in 8.0.11.

- Error number: [MY-012473](#); Symbol: [ER\\_IB\\_MSG\\_648](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_648](#) was added in 8.0.11.

- Error number: [MY-012474](#); Symbol: [ER\\_IB\\_MSG\\_649](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_649](#) was added in 8.0.11.

- Error number: [MY-012475](#); Symbol: [ER\\_IB\\_MSG\\_650](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_650](#) was added in 8.0.11.

- Error number: [MY-012476](#); Symbol: [ER\\_IB\\_MSG\\_651](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_651](#) was added in 8.0.11.

- Error number: [MY-012477](#); Symbol: [ER\\_IB\\_MSG\\_652](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_652](#) was added in 8.0.11.

- Error number: [MY-012478](#); Symbol: [ER\\_IB\\_MSG\\_653](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_653](#) was added in 8.0.11, removed after 8.0.15.

- Error number: [MY-012478](#); Symbol: [ER\\_IB\\_MSG\\_DDL\\_LOG\\_DELETE\\_BY\\_ID\\_OK](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_DDL\\_LOG\\_DELETE\\_BY\\_ID\\_OK](#) was added in 8.0.16.

- Error number: [MY-012479](#); Symbol: [ER\\_IB\\_MSG\\_654](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_654](#) was added in 8.0.11.

- Error number: [MY-012480](#); Symbol: [ER\\_IB\\_MSG\\_655](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_655](#) was added in 8.0.11.

- Error number: [MY-012481](#); Symbol: [ER\\_IB\\_MSG\\_656](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_656](#) was added in 8.0.11.

- Error number: [MY-012482](#); Symbol: [ER\\_IB\\_MSG\\_657](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_657](#) was added in 8.0.11.

- Error number: [MY-012483](#); Symbol: [ER\\_IB\\_MSG\\_658](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_658](#) was added in 8.0.11.

- Error number: [MY-012484](#); Symbol: [ER\\_IB\\_MSG\\_659](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_659](#) was added in 8.0.11.

- Error number: [MY-012485](#); Symbol: [ER\\_IB\\_MSG\\_660](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_660](#) was added in 8.0.11.

- Error number: [MY-012486](#); Symbol: [ER\\_IB\\_MSG\\_661](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_661](#) was added in 8.0.11.

- Error number: [MY-012487](#); Symbol: [ER\\_IB\\_MSG\\_662](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_662](#) was added in 8.0.11.

- Error number: [MY-012488](#); Symbol: [ER\\_IB\\_MSG\\_663](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_663](#) was added in 8.0.11.

- Error number: [MY-012489](#); Symbol: [ER\\_IB\\_MSG\\_664](#); SQLSTATE: [HY000](#)

Message: The transaction log size is too large for innodb\_log\_buffer\_size (%lu >= %lu / 2). Trying to extend it.

[ER\\_IB\\_MSG\\_664](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012490](#); Symbol: [ER\\_IB\\_MSG\\_665](#); SQLSTATE: [HY000](#)

Message: innodb\_log\_buffer\_size was extended to %lu bytes.

[ER\\_IB\\_MSG\\_665](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012491](#); Symbol: [ER\\_IB\\_MSG\\_666](#); SQLSTATE: [HY000](#)

Message: The transaction log files are too small for the single transaction log (size=%lu). So, the last checkpoint age might exceed the log group capacity %llu.

[ER\\_IB\\_MSG\\_666](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012492](#); Symbol: [ER\\_IB\\_MSG\\_667](#); SQLSTATE: [HY000](#)

Message: The age of the last checkpoint is %llu, which exceeds the log group capacity %llu.

[ER\\_IB\\_MSG\\_667](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012493](#); Symbol: [ER\\_IB\\_MSG\\_668](#); SQLSTATE: [HY000](#)

Message: Cannot continue operation. ib\_logfiles are too small for innodb\_thread\_concurrency %lu. The combined size of ib\_logfiles should be bigger than 200 kB \* innodb\_thread\_concurrency. To get mysqld to start up, set innodb\_thread\_concurrency in my.cnf to a lower value, for example, to 8. After an ERROR-FREE shutdown of mysqld you can adjust the size of ib\_logfiles. %s

[ER\\_IB\\_MSG\\_668](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012494](#); Symbol: [ER\\_IB\\_MSG\\_669](#); SQLSTATE: [HY000](#)

Message: Redo log was encrypted, but keyring plugin is not loaded.

[ER\\_IB\\_MSG\\_669](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012495](#); Symbol: [ER\\_IB\\_MSG\\_670](#); SQLSTATE: [HY000](#)

Message: Read redo log encryption metadata successful.



---

[ER\\_IB\\_MSG\\_670](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012496](#); Symbol: [ER\\_IB\\_MSG\\_671](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace encryption metadata.

[ER\\_IB\\_MSG\\_671](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012497](#); Symbol: [ER\\_IB\\_MSG\\_672](#); SQLSTATE: [HY000](#)

Message: Cannot read the encryption information in log file header, please check if keyring plugin loaded and the key file exists.

[ER\\_IB\\_MSG\\_672](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012498](#); Symbol: [ER\\_IB\\_MSG\\_673](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted in read-only mode.

[ER\\_IB\\_MSG\\_673](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012499](#); Symbol: [ER\\_IB\\_MSG\\_674](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted.

[ER\\_IB\\_MSG\\_674](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012500](#); Symbol: [ER\\_IB\\_MSG\\_675](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted.

[ER\\_IB\\_MSG\\_675](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012501](#); Symbol: [ER\\_IB\\_MSG\\_676](#); SQLSTATE: [HY000](#)

Message: Redo log encryption is enabled.

[ER\\_IB\\_MSG\\_676](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012502](#); Symbol: [ER\\_IB\\_MSG\\_677](#); SQLSTATE: [HY000](#)

Message: Flush Waiting for archiver to catch up lag LSN: %llu

[ER\\_IB\\_MSG\\_677](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012503](#); Symbol: [ER\\_IB\\_MSG\\_678](#); SQLSTATE: [HY000](#)

Message: Flush overwriting data to archive - wait too long (1 minute) lag LSN: %llu

[ER\\_IB\\_MSG\\_678](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012504](#); Symbol: [ER\\_IB\\_MSG\\_679](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_679](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012505](#); Symbol: [ER\\_IB\\_MSG\\_680](#); SQLSTATE: [HY000](#)

---

Message: Starting shutdown...

[ER\\_IB\\_MSG\\_680](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012506](#); Symbol: [ER\\_IB\\_MSG\\_681](#); SQLSTATE: [HY000](#)

Message: Waiting for %s to exit

[ER\\_IB\\_MSG\\_681](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012507](#); Symbol: [ER\\_IB\\_MSG\\_682](#); SQLSTATE: [HY000](#)

Message: Waiting for %lu active transactions to finish

[ER\\_IB\\_MSG\\_682](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012508](#); Symbol: [ER\\_IB\\_MSG\\_683](#); SQLSTATE: [HY000](#)

Message: Waiting for master thread to be suspended

[ER\\_IB\\_MSG\\_683](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012509](#); Symbol: [ER\\_IB\\_MSG\\_684](#); SQLSTATE: [HY000](#)

Message: Waiting for page\_cleaner to finish flushing of buffer pool

[ER\\_IB\\_MSG\\_684](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012510](#); Symbol: [ER\\_IB\\_MSG\\_685](#); SQLSTATE: [HY000](#)

Message: Pending checkpoint\_writes: %lu. Pending log flush writes: %lu.

[ER\\_IB\\_MSG\\_685](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012511](#); Symbol: [ER\\_IB\\_MSG\\_686](#); SQLSTATE: [HY000](#)

Message: Waiting for %lu buffer page I/Os to complete

[ER\\_IB\\_MSG\\_686](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012512](#); Symbol: [ER\\_IB\\_MSG\\_687](#); SQLSTATE: [HY000](#)

Message: MySQL has requested a very fast shutdown without flushing the InnoDB buffer pool to data files. At the next mysqld startup InnoDB will do a crash recovery!

[ER\\_IB\\_MSG\\_687](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012513](#); Symbol: [ER\\_IB\\_MSG\\_688](#); SQLSTATE: [HY000](#)

Message: Background thread %s woke up during shutdown

[ER\\_IB\\_MSG\\_688](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012514](#); Symbol: [ER\\_IB\\_MSG\\_689](#); SQLSTATE: [HY000](#)

Message: Waiting for archiver to finish archiving page and log

[ER\\_IB\\_MSG\\_689](#) was added in 8.0.11, removed after 8.0.13.

- 
- Error number: [MY-012515](#); Symbol: [ER\\_IB\\_MSG\\_690](#); SQLSTATE: [HY000](#)  
Message: Background thread %s woke up during shutdown  
[ER\\_IB\\_MSG\\_690](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012516](#); Symbol: [ER\\_IB\\_MSG\\_691](#); SQLSTATE: [HY000](#)  
Message: Waiting for dirty buffer pages to be flushed  
[ER\\_IB\\_MSG\\_691](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012517](#); Symbol: [ER\\_IB\\_MSG\\_692](#); SQLSTATE: [HY000](#)  
Message: Log sequence number at shutdown %llu is lower than at startup %llu!  
[ER\\_IB\\_MSG\\_692](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012518](#); Symbol: [ER\\_IB\\_MSG\\_693](#); SQLSTATE: [HY000](#)  
Message: Waiting for archiver to finish archiving page and log  
[ER\\_IB\\_MSG\\_693](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012519](#); Symbol: [ER\\_IB\\_MSG\\_694](#); SQLSTATE: [HY000](#)  
Message: ##### CORRUPT LOG RECORD FOUND #####  
[ER\\_IB\\_MSG\\_694](#) was added in 8.0.11.
  - Error number: [MY-012520](#); Symbol: [ER\\_IB\\_MSG\\_695](#); SQLSTATE: [HY000](#)  
Message: Log record type %d, page %lu:%lu. Log parsing proceeded successfully up to %llu. Previous log record type %d, is multi %llu Recv offset %zd, prev %llu  
[ER\\_IB\\_MSG\\_695](#) was added in 8.0.11.
  - Error number: [MY-012521](#); Symbol: [ER\\_IB\\_MSG\\_696](#); SQLSTATE: [HY000](#)  
Message: Hex dump starting %llu bytes before and ending %llu bytes after the corrupted record:  
[ER\\_IB\\_MSG\\_696](#) was added in 8.0.11.
  - Error number: [MY-012522](#); Symbol: [ER\\_IB\\_MSG\\_697](#); SQLSTATE: [HY000](#)  
Message: Set innodb\_force\_recovery to ignore this error.  
[ER\\_IB\\_MSG\\_697](#) was added in 8.0.11.
  - Error number: [MY-012523](#); Symbol: [ER\\_IB\\_MSG\\_698](#); SQLSTATE: [HY000](#)  
Message: The log file may have been corrupt and it is possible that the log scan did not proceed far enough in recovery! Please run CHECK TABLE on your InnoDB tables to check that they are ok! If mysqld crashes after this recovery; %s  
[ER\\_IB\\_MSG\\_698](#) was added in 8.0.11, removed after 8.0.29.
-

- 
- Error number: [MY-012523](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_CORRUPT](#); SQLSTATE: [HY000](#)  
Message: The redo log file may have been corrupt and it is possible that the log scan did not proceed far enough in recovery! Please run CHECK TABLE on your InnoDB tables to check that they are ok! If mysqld crashes after this recovery; %s  
[ER\\_IB\\_MSG\\_LOG\\_CORRUPT](#) was added in 8.0.30.
  - Error number: [MY-012524](#); Symbol: [ER\\_IB\\_MSG\\_699](#); SQLSTATE: [HY000](#)  
Message: %llu pages with log records were left unprocessed!  
[ER\\_IB\\_MSG\\_699](#) was added in 8.0.11.
  - Error number: [MY-012525](#); Symbol: [ER\\_IB\\_MSG\\_700](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_700](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012525](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_OLD\\_AND\\_LOG\\_CORRUPTED](#); SQLSTATE: [HY000](#)  
Message: Upgrade after a crash is not supported. This redo log was created with %s, and it appears corrupted. Please follow the instructions at %s  
[ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_OLD\\_AND\\_LOG\\_CORRUPTED](#) was added in 8.0.30.
  - Error number: [MY-012526](#); Symbol: [ER\\_IB\\_MSG\\_701](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_701](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012526](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_OLD\\_AND\\_NO\\_CLEAN\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: Upgrade is not supported after a crash or shutdown with innodb\_fast\_shutdown = 2. This redo log was created with %s, and it appears logically non empty. Please follow the instructions at %s  
[ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_OLD\\_AND\\_NO\\_CLEAN\\_SHUTDOWN](#) was added in 8.0.30.
  - Error number: [MY-012527](#); Symbol: [ER\\_IB\\_MSG\\_702](#); SQLSTATE: [HY000](#)  
Message: Invalid redo log header checksum.  
[ER\\_IB\\_MSG\\_702](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012528](#); Symbol: [ER\\_IB\\_MSG\\_703](#); SQLSTATE: [HY000](#)  
Message: Unsupported redo log format (%lu). The redo log was created before MySQL 5.7.9  
[ER\\_IB\\_MSG\\_703](#) was added in 8.0.11, removed after 8.0.13.
  - Error number: [MY-012529](#); Symbol: [ER\\_IB\\_MSG\\_704](#); SQLSTATE: [HY000](#)  
Message: Redo log format is v%lu. The redo log was created before MySQL 8.0.3.  
[ER\\_IB\\_MSG\\_704](#) was added in 8.0.11, removed after 8.0.29.

- 
- Error number: [MY-012529](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_BEFORE\\_8\\_0\\_30](#); SQLSTATE: [HY000](#)  
Message: Redo log format is v%lu. The redo log was created before MySQL 8.0.30.  
[ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_BEFORE\\_8\\_0\\_30](#) was added in 8.0.30.
  - Error number: [MY-012530](#); Symbol: [ER\\_IB\\_MSG\\_705](#); SQLSTATE: [HY000](#)  
Message: Unknown redo log format (%lu). Please follow the instructions at %s upgrading-downgrading.html.  
[ER\\_IB\\_MSG\\_705](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012530](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_FORMAT\\_UNKNOWN](#); SQLSTATE: [HY000](#)  
Message: Unknown redo log format (v%lu) in file %s. Please follow the instructions at %s  
[ER\\_IB\\_MSG\\_LOG\\_FILE\\_FORMAT\\_UNKNOWN](#) was added in 8.0.30.
  - Error number: [MY-012531](#); Symbol: [ER\\_IB\\_MSG\\_706](#); SQLSTATE: [HY000](#)  
Message: No valid checkpoint found (corrupted redo log). You can try --innodb-force-recovery=6 as a last resort.  
[ER\\_IB\\_MSG\\_706](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012531](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_CHECKPOINT\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: No valid checkpoint found (corrupted redo log). You can try --innodb-force-recovery=6 as a last resort.  
[ER\\_IB\\_MSG\\_RECOVERY\\_CHECKPOINT\\_NOT\\_FOUND](#) was added in 8.0.30.
  - Error number: [MY-012532](#); Symbol: [ER\\_IB\\_MSG\\_707](#); SQLSTATE: [HY000](#)  
Message: Applying a batch of %llu redo log records ...  
[ER\\_IB\\_MSG\\_707](#) was added in 8.0.11.
  - Error number: [MY-012533](#); Symbol: [ER\\_IB\\_MSG\\_708](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_708](#) was added in 8.0.11.
  - Error number: [MY-012534](#); Symbol: [ER\\_IB\\_MSG\\_709](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_709](#) was added in 8.0.11.
  - Error number: [MY-012535](#); Symbol: [ER\\_IB\\_MSG\\_710](#); SQLSTATE: [HY000](#)  
Message: Apply batch completed!  
[ER\\_IB\\_MSG\\_710](#) was added in 8.0.11.
  - Error number: [MY-012536](#); Symbol: [ER\\_IB\\_MSG\\_711](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_711](#) was added in 8.0.11.

- Error number: [MY-012537](#); Symbol: [ER\\_IB\\_MSG\\_712](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_712](#) was added in 8.0.11.

- Error number: [MY-012538](#); Symbol: [ER\\_IB\\_MSG\\_713](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_713](#) was added in 8.0.11.

- Error number: [MY-012539](#); Symbol: [ER\\_IB\\_MSG\\_714](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_714](#) was added in 8.0.11.

- Error number: [MY-012540](#); Symbol: [ER\\_IB\\_MSG\\_715](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_715](#) was added in 8.0.11.

- Error number: [MY-012541](#); Symbol: [ER\\_IB\\_MSG\\_716](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_716](#) was added in 8.0.11.

- Error number: [MY-012542](#); Symbol: [ER\\_IB\\_MSG\\_717](#); SQLSTATE: [HY000](#)

Message: An optimized(without redo logging) DDL operation has been performed. All modified pages may not have been flushed to the disk yet. This offline backup may not be consistent

[ER\\_IB\\_MSG\\_717](#) was added in 8.0.11.

- Error number: [MY-012543](#); Symbol: [ER\\_IB\\_MSG\\_718](#); SQLSTATE: [HY000](#)

Message: Extending tablespace : %lu space name: %s to new size: %lu pages during recovery.

[ER\\_IB\\_MSG\\_718](#) was added in 8.0.11.

- Error number: [MY-012544](#); Symbol: [ER\\_IB\\_MSG\\_719](#); SQLSTATE: [HY000](#)

Message: Could not extend tablespace: %lu space name: %s to new size: %lu pages during recovery.

[ER\\_IB\\_MSG\\_719](#) was added in 8.0.11.

- Error number: [MY-012545](#); Symbol: [ER\\_IB\\_MSG\\_720](#); SQLSTATE: [HY000](#)

Message: Log block %lu at lsn %llu has valid header, but checksum field contains %lu, should be %lu.

[ER\\_IB\\_MSG\\_720](#) was added in 8.0.11.

- 
- Error number: [MY-012546](#); Symbol: [ER\\_IB\\_MSG\\_721](#); SQLSTATE: [HY000](#)  
Message: Recovery skipped, --innodb-read-only set!  
[ER\\_IB\\_MSG\\_721](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012546](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_SKIPPED\\_IN\\_READ\\_ONLY\\_MODE](#); SQLSTATE: [HY000](#)  
Message: Recovery skipped, --innodb-read-only set!  
[ER\\_IB\\_MSG\\_RECOVERY\\_SKIPPED\\_IN\\_READ\\_ONLY\\_MODE](#) was added in 8.0.30.
  - Error number: [MY-012547](#); Symbol: [ER\\_IB\\_MSG\\_722](#); SQLSTATE: [HY000](#)  
Message: Log scan progressed past the checkpoint LSN %llu.  
[ER\\_IB\\_MSG\\_722](#) was added in 8.0.11.
  - Error number: [MY-012548](#); Symbol: [ER\\_IB\\_MSG\\_723](#); SQLSTATE: [HY000](#)  
Message: Log parsing buffer overflow. Recovery may have failed! Please set log\_buffer\_size to a value higher than %lu.  
[ER\\_IB\\_MSG\\_723](#) was added in 8.0.11.
  - Error number: [MY-012549](#); Symbol: [ER\\_IB\\_MSG\\_724](#); SQLSTATE: [HY000](#)  
Message: Set innodb\_force\_recovery to ignore this error.  
[ER\\_IB\\_MSG\\_724](#) was added in 8.0.11.
  - Error number: [MY-012550](#); Symbol: [ER\\_IB\\_MSG\\_725](#); SQLSTATE: [HY000](#)  
Message: Doing recovery: scanned up to log sequence number %llu  
[ER\\_IB\\_MSG\\_725](#) was added in 8.0.11.
  - Error number: [MY-012551](#); Symbol: [ER\\_IB\\_MSG\\_726](#); SQLSTATE: [HY000](#)  
Message: Database was not shutdown normally!  
[ER\\_IB\\_MSG\\_726](#) was added in 8.0.11.
  - Error number: [MY-012552](#); Symbol: [ER\\_IB\\_MSG\\_727](#); SQLSTATE: [HY000](#)  
Message: Starting crash recovery.  
[ER\\_IB\\_MSG\\_727](#) was added in 8.0.11.
  - Error number: [MY-012553](#); Symbol: [ER\\_IB\\_MSG\\_728](#); SQLSTATE: [HY000](#)  
Message: The user has set SRV\_FORCE\_NO\_LOG\_REDO on, skipping log redo  
[ER\\_IB\\_MSG\\_728](#) was added in 8.0.11.
  - Error number: [MY-012554](#); Symbol: [ER\\_IB\\_MSG\\_729](#); SQLSTATE: [HY000](#)  
Message: Cannot restore from mysqlbackup, InnoDB running in read-only mode!

---

`ER_IB_MSG_729` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012554`; Symbol: `ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY_MODE`; `SQLSTATE: HY000`

Message: Cannot restore from mysqlbackup, InnoDB running in read-only mode!

`ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY_MODE` was added in 8.0.30.

- Error number: `MY-012555`; Symbol: `ER_IB_MSG_730`; `SQLSTATE: HY000`

Message: The log file was created by mysqlbackup --apply-log at %s. The following crash recovery is part of a normal restore.

`ER_IB_MSG_730` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012555`; Symbol: `ER_IB_MSG_LOG_FILES_CREATED_BY_MEB`; `SQLSTATE: HY000`

Message: The redo log file was created by mysqlbackup --apply-log at %s. The following crash recovery is part of a normal restore.

`ER_IB_MSG_LOG_FILES_CREATED_BY_MEB` was added in 8.0.30.

- Error number: `MY-012556`; Symbol: `ER_IB_MSG_731`; `SQLSTATE: HY000`

Message: Opening cloned database

`ER_IB_MSG_731` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012556`; Symbol: `ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE`; `SQLSTATE: HY000`

Message: Opening cloned database

`ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE` was added in 8.0.30.

- Error number: `MY-012557`; Symbol: `ER_IB_MSG_732`; `SQLSTATE: HY000`

Message: Redo log is from an earlier version, v%lu.

`ER_IB_MSG_732` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012557`; Symbol: `ER_IB_MSG_LOG_FORMAT_OLD`; `SQLSTATE: HY000`

Message: Redo log is from an earlier version, v%lu.

`ER_IB_MSG_LOG_FORMAT_OLD` was added in 8.0.30.

- Error number: `MY-012558`; Symbol: `ER_IB_MSG_733`; `SQLSTATE: HY000`

Message: Redo log format v%lu not supported. Current supported format is v%lu.

`ER_IB_MSG_733` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012558`; Symbol: `ER_IB_MSG_LOG_FORMAT_NOT_SUPPORTED`; `SQLSTATE: HY000`

Message: Redo log format v%lu not supported. Current supported format is v%lu.

`ER_IB_MSG_LOG_FORMAT_NOT_SUPPORTED` was added in 8.0.30, removed after 8.0.32.



- 
- Error number: [MY-012559](#); Symbol: [ER\\_IB\\_MSG\\_734](#); SQLSTATE: [HY000](#)  
Message: Are you sure you are using the right ib\_logfiles to start up the database? Log sequence number in the ib\_logfiles is %llu, less than the log sequence number in the first system tablespace file header, %llu.  
[ER\\_IB\\_MSG\\_734](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012559](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_CHECKPOINT\\_FROM\\_BEFORE\\_CLEAN\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: Are you sure you are using the right redo log files to start up the database? Log sequence number in the redo log files is %llu, less than the log sequence number in the first system tablespace file header, %llu.  
[ER\\_IB\\_MSG\\_RECOVERY\\_CHECKPOINT\\_FROM\\_BEFORE\\_CLEAN\\_SHUTDOWN](#) was added in 8.0.30.
  - Error number: [MY-012560](#); Symbol: [ER\\_IB\\_MSG\\_735](#); SQLSTATE: [HY000](#)  
Message: The log sequence number %llu in the system tablespace does not match the log sequence number %llu in the ib\_logfiles!  
[ER\\_IB\\_MSG\\_735](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012560](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_IS\\_NEEDED](#); SQLSTATE: [HY000](#)  
Message: The log sequence number %llu in the system tablespace does not match the log sequence number %llu in the redo log files!  
[ER\\_IB\\_MSG\\_RECOVERY\\_IS\\_NEEDED](#) was added in 8.0.30.
  - Error number: [MY-012561](#); Symbol: [ER\\_IB\\_MSG\\_736](#); SQLSTATE: [HY000](#)  
Message: Can't initiate database recovery, running in read-only-mode.  
[ER\\_IB\\_MSG\\_736](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012561](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_IN\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)  
Message: Can't initiate database recovery, running in read-only-mode.  
[ER\\_IB\\_MSG\\_RECOVERY\\_IN\\_READ\\_ONLY](#) was added in 8.0.30.
  - Error number: [MY-012562](#); Symbol: [ER\\_IB\\_MSG\\_737](#); SQLSTATE: [HY000](#)  
Message: We scanned the log up to %llu. A checkpoint was at %llu and the maximum LSN on a database page was %llu. It is possible that the database is now corrupt!  
[ER\\_IB\\_MSG\\_737](#) was added in 8.0.11.
  - Error number: [MY-012563](#); Symbol: [ER\\_IB\\_MSG\\_738](#); SQLSTATE: [HY000](#)  
Message: Waiting for recv\_writer to finish flushing of buffer pool  
[ER\\_IB\\_MSG\\_738](#) was added in 8.0.11.
  - Error number: [MY-012564](#); Symbol: [ER\\_IB\\_MSG\\_739](#); SQLSTATE: [HY000](#)  
Message: Recovery parsing buffer extended to %zu.

---

[ER\\_IB\\_MSG\\_739](#) was added in 8.0.11.

- Error number: [MY-012565](#); Symbol: [ER\\_IB\\_MSG\\_740](#); SQLSTATE: [HY000](#)

Message: Out of memory while resizing recovery parsing buffer.

[ER\\_IB\\_MSG\\_740](#) was added in 8.0.11.

- Error number: [MY-012566](#); Symbol: [ER\\_IB\\_MSG\\_741](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_741](#) was added in 8.0.11.

- Error number: [MY-012567](#); Symbol: [ER\\_IB\\_MSG\\_742](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_742](#) was added in 8.0.11.

- Error number: [MY-012568](#); Symbol: [ER\\_IB\\_MSG\\_743](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_743](#) was added in 8.0.11.

- Error number: [MY-012569](#); Symbol: [ER\\_IB\\_MSG\\_744](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_744](#) was added in 8.0.11.

- Error number: [MY-012570](#); Symbol: [ER\\_IB\\_MSG\\_745](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_745](#) was added in 8.0.11.

- Error number: [MY-012571](#); Symbol: [ER\\_IB\\_MSG\\_746](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_746](#) was added in 8.0.11.

- Error number: [MY-012572](#); Symbol: [ER\\_IB\\_MSG\\_747](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_747](#) was added in 8.0.11.

- Error number: [MY-012573](#); Symbol: [ER\\_IB\\_MSG\\_748](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_748](#) was added in 8.0.11.

- Error number: [MY-012574](#); Symbol: [ER\\_IB\\_MSG\\_749](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_749](#) was added in 8.0.11.

- Error number: [MY-012575](#); Symbol: [ER\\_IB\\_MSG\\_750](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_750](#) was added in 8.0.11.

- Error number: [MY-012576](#); Symbol: [ER\\_IB\\_MSG\\_751](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_751](#) was added in 8.0.11.

- Error number: [MY-012577](#); Symbol: [ER\\_IB\\_MSG\\_752](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_752](#) was added in 8.0.11.

- Error number: [MY-012578](#); Symbol: [ER\\_IB\\_MSG\\_753](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_753](#) was added in 8.0.11.

- Error number: [MY-012579](#); Symbol: [ER\\_IB\\_MSG\\_754](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_754](#) was added in 8.0.11.

- Error number: [MY-012580](#); Symbol: [ER\\_IB\\_MSG\\_755](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_755](#) was added in 8.0.11.

- Error number: [MY-012581](#); Symbol: [ER\\_IB\\_MSG\\_756](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_756](#) was added in 8.0.11.

- Error number: [MY-012582](#); Symbol: [ER\\_IB\\_MSG\\_757](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_757](#) was added in 8.0.11.

- Error number: [MY-012583](#); Symbol: [ER\\_IB\\_MSG\\_758](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_758](#) was added in 8.0.11.

- Error number: [MY-012584](#); Symbol: [ER\\_IB\\_MSG\\_759](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_759](#) was added in 8.0.11.

- Error number: [MY-012585](#); Symbol: [ER\\_IB\\_MSG\\_760](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_760](#) was added in 8.0.11.

- Error number: [MY-012586](#); Symbol: [ER\\_IB\\_MSG\\_761](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_761](#) was added in 8.0.11.

- Error number: [MY-012587](#); Symbol: [ER\\_IB\\_MSG\\_762](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_762](#) was added in 8.0.11.

- Error number: [MY-012588](#); Symbol: [ER\\_IB\\_MSG\\_763](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_763](#) was added in 8.0.11.

- Error number: [MY-012589](#); Symbol: [ER\\_IB\\_MSG\\_764](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_764](#) was added in 8.0.11.

- Error number: [MY-012590](#); Symbol: [ER\\_IB\\_MSG\\_765](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_765](#) was added in 8.0.11.

- Error number: [MY-012591](#); Symbol: [ER\\_IB\\_MSG\\_766](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_766](#) was added in 8.0.11.

- Error number: [MY-012592](#); Symbol: [ER\\_IB\\_MSG\\_767](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_767](#) was added in 8.0.11.

- Error number: [MY-012593](#); Symbol: [ER\\_IB\\_MSG\\_768](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_768](#) was added in 8.0.11.

- Error number: [MY-012594](#); Symbol: [ER\\_IB\\_MSG\\_769](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_769](#) was added in 8.0.11.

- Error number: [MY-012595](#); Symbol: [ER\\_IB\\_MSG\\_770](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_770](#) was added in 8.0.11.

- Error number: [MY-012596](#); Symbol: [ER\\_IB\\_MSG\\_771](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_771](#) was added in 8.0.11.

- Error number: [MY-012597](#); Symbol: [ER\\_IB\\_MSG\\_772](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_772](#) was added in 8.0.11.

- Error number: [MY-012598](#); Symbol: [ER\\_IB\\_MSG\\_773](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_773](#) was added in 8.0.11.

- Error number: [MY-012599](#); Symbol: [ER\\_IB\\_MSG\\_774](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_774](#) was added in 8.0.11.

- Error number: [MY-012600](#); Symbol: [ER\\_IB\\_MSG\\_775](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_775](#) was added in 8.0.11.

- Error number: [MY-012601](#); Symbol: [ER\\_IB\\_MSG\\_776](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_776](#) was added in 8.0.11.

- Error number: [MY-012602](#); Symbol: [ER\\_IB\\_MSG\\_777](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_777](#) was added in 8.0.11.

- Error number: [MY-012603](#); Symbol: [ER\\_IB\\_MSG\\_778](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_778](#) was added in 8.0.11.

- Error number: [MY-012604](#); Symbol: [ER\\_IB\\_MSG\\_779](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_779](#) was added in 8.0.11.

- Error number: [MY-012605](#); Symbol: [ER\\_IB\\_MSG\\_780](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_780](#) was added in 8.0.11.

- Error number: [MY-012606](#); Symbol: [ER\\_IB\\_MSG\\_781](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_781](#) was added in 8.0.11.

- Error number: [MY-012607](#); Symbol: [ER\\_IB\\_MSG\\_782](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_782](#) was added in 8.0.11.

- Error number: [MY-012608](#); Symbol: [ER\\_IB\\_MSG\\_783](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_783](#) was added in 8.0.11.

- Error number: [MY-012609](#); Symbol: [ER\\_IB\\_MSG\\_784](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_784](#) was added in 8.0.11.

- Error number: [MY-012610](#); Symbol: [ER\\_IB\\_MSG\\_785](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_785](#) was added in 8.0.11.

- Error number: [MY-012611](#); Symbol: [ER\\_IB\\_MSG\\_786](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_786](#) was added in 8.0.11.

- Error number: [MY-012612](#); Symbol: [ER\\_IB\\_MSG\\_787](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_787](#) was added in 8.0.11.

- Error number: [MY-012613](#); Symbol: [ER\\_IB\\_MSG\\_788](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_788](#) was added in 8.0.11.

- Error number: [MY-012614](#); Symbol: [ER\\_IB\\_MSG\\_789](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_789](#) was added in 8.0.11.

- Error number: [MY-012615](#); Symbol: [ER\\_IB\\_MSG\\_790](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_790](#) was added in 8.0.11.

- Error number: [MY-012616](#); Symbol: [ER\\_IB\\_MSG\\_791](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_791](#) was added in 8.0.11.

- Error number: [MY-012617](#); Symbol: [ER\\_IB\\_MSG\\_792](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_792](#) was added in 8.0.11.

- Error number: [MY-012618](#); Symbol: [ER\\_IB\\_MSG\\_793](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_793](#) was added in 8.0.11.

- Error number: [MY-012619](#); Symbol: [ER\\_IB\\_MSG\\_794](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_794](#) was added in 8.0.11.

- Error number: [MY-012620](#); Symbol: [ER\\_IB\\_MSG\\_795](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_795](#) was added in 8.0.11.

- Error number: [MY-012621](#); Symbol: [ER\\_IB\\_MSG\\_796](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_796](#) was added in 8.0.11.

- Error number: [MY-012622](#); Symbol: [ER\\_IB\\_MSG\\_797](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_797](#) was added in 8.0.11.

- Error number: [MY-012623](#); Symbol: [ER\\_IB\\_MSG\\_798](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_798](#) was added in 8.0.11.

- Error number: [MY-012624](#); Symbol: [ER\\_IB\\_MSG\\_799](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_799](#) was added in 8.0.11.

- Error number: [MY-012625](#); Symbol: [ER\\_IB\\_MSG\\_800](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_800](#) was added in 8.0.11, removed after 8.0.39.

- Error number: [MY-012626](#); Symbol: [ER\\_IB\\_MSG\\_801](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_801](#) was added in 8.0.11.

- Error number: [MY-012627](#); Symbol: [ER\\_IB\\_MSG\\_802](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_802](#) was added in 8.0.11.

- Error number: [MY-012628](#); Symbol: [ER\\_IB\\_MSG\\_803](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_803](#) was added in 8.0.11.

- Error number: [MY-012629](#); Symbol: [ER\\_IB\\_MSG\\_804](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_804](#) was added in 8.0.11.

- Error number: [MY-012630](#); Symbol: [ER\\_IB\\_MSG\\_805](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_805](#) was added in 8.0.11.

- Error number: [MY-012631](#); Symbol: [ER\\_IB\\_MSG\\_806](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_806](#) was added in 8.0.11.

- Error number: [MY-012632](#); Symbol: [ER\\_IB\\_MSG\\_807](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_807](#) was added in 8.0.11.

- Error number: [MY-012633](#); Symbol: [ER\\_IB\\_MSG\\_808](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_808](#) was added in 8.0.11.

- Error number: [MY-012634](#); Symbol: [ER\\_IB\\_MSG\\_809](#); SQLSTATE: [HY000](#)

Message: %s



---

[ER\\_IB\\_MSG\\_809](#) was added in 8.0.11.

- Error number: [MY-012635](#); Symbol: [ER\\_IB\\_MSG\\_810](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_810](#) was added in 8.0.11.

- Error number: [MY-012636](#); Symbol: [ER\\_IB\\_MSG\\_811](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_811](#) was added in 8.0.11.

- Error number: [MY-012637](#); Symbol: [ER\\_IB\\_MSG\\_812](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_812](#) was added in 8.0.11.

- Error number: [MY-012638](#); Symbol: [ER\\_IB\\_MSG\\_813](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_813](#) was added in 8.0.11.

- Error number: [MY-012639](#); Symbol: [ER\\_IB\\_MSG\\_814](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_814](#) was added in 8.0.11.

- Error number: [MY-012640](#); Symbol: [ER\\_IB\\_MSG\\_815](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_815](#) was added in 8.0.11.

- Error number: [MY-012641](#); Symbol: [ER\\_IB\\_MSG\\_816](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_816](#) was added in 8.0.11.

- Error number: [MY-012642](#); Symbol: [ER\\_IB\\_MSG\\_817](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_817](#) was added in 8.0.11.

- Error number: [MY-012643](#); Symbol: [ER\\_IB\\_MSG\\_818](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_818](#) was added in 8.0.11.

- Error number: [MY-012644](#); Symbol: [ER\\_IB\\_MSG\\_819](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_819](#) was added in 8.0.11.

- Error number: [MY-012645](#); Symbol: [ER\\_IB\\_MSG\\_820](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_820](#) was added in 8.0.11.

- Error number: [MY-012646](#); Symbol: [ER\\_IB\\_MSG\\_821](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_821](#) was added in 8.0.11.

- Error number: [MY-012647](#); Symbol: [ER\\_IB\\_MSG\\_822](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_822](#) was added in 8.0.11.

- Error number: [MY-012648](#); Symbol: [ER\\_IB\\_MSG\\_823](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_823](#) was added in 8.0.11.

- Error number: [MY-012649](#); Symbol: [ER\\_IB\\_MSG\\_824](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_824](#) was added in 8.0.11.

- Error number: [MY-012650](#); Symbol: [ER\\_IB\\_MSG\\_825](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_825](#) was added in 8.0.11.

- Error number: [MY-012651](#); Symbol: [ER\\_IB\\_MSG\\_826](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_826](#) was added in 8.0.11.

- Error number: [MY-012652](#); Symbol: [ER\\_IB\\_MSG\\_827](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_827](#) was added in 8.0.11.

- Error number: [MY-012653](#); Symbol: [ER\\_IB\\_MSG\\_828](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_828](#) was added in 8.0.11.

- Error number: [MY-012654](#); Symbol: [ER\\_IB\\_MSG\\_829](#); SQLSTATE: [HY000](#)

Message: %s

---

[ER\\_IB\\_MSG\\_829](#) was added in 8.0.11.

- Error number: [MY-012655](#); Symbol: [ER\\_IB\\_MSG\\_830](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_830](#) was added in 8.0.11.

- Error number: [MY-012656](#); Symbol: [ER\\_IB\\_MSG\\_831](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_831](#) was added in 8.0.11.

- Error number: [MY-012657](#); Symbol: [ER\\_IB\\_MSG\\_832](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_832](#) was added in 8.0.11.

- Error number: [MY-012658](#); Symbol: [ER\\_IB\\_MSG\\_833](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_833](#) was added in 8.0.11.

- Error number: [MY-012659](#); Symbol: [ER\\_IB\\_MSG\\_834](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_834](#) was added in 8.0.11.

- Error number: [MY-012660](#); Symbol: [ER\\_IB\\_MSG\\_835](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_835](#) was added in 8.0.11.

- Error number: [MY-012661](#); Symbol: [ER\\_IB\\_MSG\\_836](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_836](#) was added in 8.0.11.

- Error number: [MY-012662](#); Symbol: [ER\\_IB\\_MSG\\_837](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_837](#) was added in 8.0.11.

- Error number: [MY-012663](#); Symbol: [ER\\_IB\\_MSG\\_838](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_838](#) was added in 8.0.11.

- Error number: [MY-012664](#); Symbol: [ER\\_IB\\_MSG\\_839](#); SQLSTATE: [HY000](#)

Message: %s

- 
- [ER\\_IB\\_MSG\\_839](#) was added in 8.0.11.
- Error number: [MY-012665](#); Symbol: [ER\\_IB\\_MSG\\_840](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_840](#) was added in 8.0.11.
  - Error number: [MY-012666](#); Symbol: [ER\\_IB\\_MSG\\_841](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_841](#) was added in 8.0.11.
  - Error number: [MY-012667](#); Symbol: [ER\\_IB\\_MSG\\_842](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_842](#) was added in 8.0.11.
  - Error number: [MY-012668](#); Symbol: [ER\\_IB\\_MSG\\_843](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_843](#) was added in 8.0.11, removed after 8.0.32.
  - Error number: [MY-012668](#); Symbol: [ER\\_IB\\_MSG\\_CANT\\_ENCRYPT\\_REDO\\_LOG\\_DATA](#); SQLSTATE: [HY000](#)  
Message: Can't encrypt data of redo log  
[ER\\_IB\\_MSG\\_CANT\\_ENCRYPT\\_REDO\\_LOG\\_DATA](#) was added in 8.0.33.
  - Error number: [MY-012669](#); Symbol: [ER\\_IB\\_MSG\\_844](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_844](#) was added in 8.0.11.
  - Error number: [MY-012670](#); Symbol: [ER\\_IB\\_MSG\\_845](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_845](#) was added in 8.0.11.
  - Error number: [MY-012671](#); Symbol: [ER\\_IB\\_MSG\\_846](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_846](#) was added in 8.0.11, removed after 8.0.36.
  - Error number: [MY-012671](#); Symbol: [ER\\_IB\\_MSG\\_CANT\\_DECRYPT\\_REDO\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Decryption of redo log block at offset %llu in file %s failed because there's no keyring configured  
[ER\\_IB\\_MSG\\_CANT\\_DECRYPT\\_REDO\\_LOG](#) was added in 8.0.37.
  - Error number: [MY-012672](#); Symbol: [ER\\_IB\\_MSG\\_847](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_847](#) was added in 8.0.11.

- Error number: [MY-012673](#); Symbol: [ER\\_IB\\_MSG\\_848](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_848](#) was added in 8.0.11.

- Error number: [MY-012674](#); Symbol: [ER\\_IB\\_MSG\\_849](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_849](#) was added in 8.0.11.

- Error number: [MY-012675](#); Symbol: [ER\\_IB\\_MSG\\_850](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_850](#) was added in 8.0.11.

- Error number: [MY-012676](#); Symbol: [ER\\_IB\\_MSG\\_851](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_851](#) was added in 8.0.11.

- Error number: [MY-012677](#); Symbol: [ER\\_IB\\_MSG\\_852](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_852](#) was added in 8.0.11.

- Error number: [MY-012678](#); Symbol: [ER\\_IB\\_MSG\\_853](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_853](#) was added in 8.0.11.

- Error number: [MY-012679](#); Symbol: [ER\\_IB\\_MSG\\_854](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_854](#) was added in 8.0.11.

- Error number: [MY-012680](#); Symbol: [ER\\_IB\\_MSG\\_855](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_855](#) was added in 8.0.11.

- Error number: [MY-012681](#); Symbol: [ER\\_IB\\_MSG\\_856](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_856](#) was added in 8.0.11.

- Error number: [MY-012682](#); Symbol: [ER\\_IB\\_MSG\\_857](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_857](#) was added in 8.0.11.

- Error number: [MY-012683](#); Symbol: [ER\\_IB\\_MSG\\_858](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_858](#) was added in 8.0.11.

- Error number: [MY-012684](#); Symbol: [ER\\_IB\\_MSG\\_859](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_859](#) was added in 8.0.11.

- Error number: [MY-012685](#); Symbol: [ER\\_IB\\_MSG\\_860](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_860](#) was added in 8.0.11.

- Error number: [MY-012686](#); Symbol: [ER\\_IB\\_MSG\\_861](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_861](#) was added in 8.0.11.

- Error number: [MY-012687](#); Symbol: [ER\\_IB\\_MSG\\_862](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_862](#) was added in 8.0.11.

- Error number: [MY-012688](#); Symbol: [ER\\_IB\\_MSG\\_863](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_863](#) was added in 8.0.11.

- Error number: [MY-012689](#); Symbol: [ER\\_IB\\_MSG\\_864](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_864](#) was added in 8.0.11.

- Error number: [MY-012690](#); Symbol: [ER\\_IB\\_MSG\\_865](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_865](#) was added in 8.0.11.

- Error number: [MY-012691](#); Symbol: [ER\\_IB\\_MSG\\_866](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_866](#) was added in 8.0.11.

- Error number: [MY-012692](#); Symbol: [ER\\_IB\\_MSG\\_867](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_867](#) was added in 8.0.11.

- Error number: [MY-012693](#); Symbol: [ER\\_IB\\_MSG\\_868](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_868](#) was added in 8.0.11.

- Error number: [MY-012694](#); Symbol: [ER\\_IB\\_MSG\\_869](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_869](#) was added in 8.0.11.

- Error number: [MY-012695](#); Symbol: [ER\\_IB\\_MSG\\_870](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_870](#) was added in 8.0.11.

- Error number: [MY-012696](#); Symbol: [ER\\_IB\\_MSG\\_871](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_871](#) was added in 8.0.11.

- Error number: [MY-012697](#); Symbol: [ER\\_IB\\_MSG\\_872](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_872](#) was added in 8.0.11.

- Error number: [MY-012698](#); Symbol: [ER\\_IB\\_MSG\\_873](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_873](#) was added in 8.0.11.

- Error number: [MY-012699](#); Symbol: [ER\\_IB\\_MSG\\_874](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_874](#) was added in 8.0.11.

- Error number: [MY-012700](#); Symbol: [ER\\_IB\\_MSG\\_875](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_875](#) was added in 8.0.11.

- Error number: [MY-012701](#); Symbol: [ER\\_IB\\_MSG\\_876](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_876](#) was added in 8.0.11.

- Error number: [MY-012702](#); Symbol: [ER\\_IB\\_MSG\\_877](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_877](#) was added in 8.0.11.

- Error number: [MY-012703](#); Symbol: [ER\\_IB\\_MSG\\_878](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_878](#) was added in 8.0.11.

- Error number: [MY-012704](#); Symbol: [ER\\_IB\\_MSG\\_879](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_879](#) was added in 8.0.11.

- Error number: [MY-012705](#); Symbol: [ER\\_IB\\_MSG\\_880](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_880](#) was added in 8.0.11.

- Error number: [MY-012706](#); Symbol: [ER\\_IB\\_MSG\\_881](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_881](#) was added in 8.0.11.

- Error number: [MY-012707](#); Symbol: [ER\\_IB\\_MSG\\_882](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_882](#) was added in 8.0.11.

- Error number: [MY-012708](#); Symbol: [ER\\_IB\\_MSG\\_883](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_883](#) was added in 8.0.11.

- Error number: [MY-012709](#); Symbol: [ER\\_IB\\_MSG\\_884](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_884](#) was added in 8.0.11.

- Error number: [MY-012710](#); Symbol: [ER\\_IB\\_MSG\\_885](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_885](#) was added in 8.0.11.

- Error number: [MY-012711](#); Symbol: [ER\\_IB\\_MSG\\_886](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_886](#) was added in 8.0.11.

- Error number: [MY-012712](#); Symbol: [ER\\_IB\\_MSG\\_887](#); SQLSTATE: [HY000](#)



---

Message: %s

[ER\\_IB\\_MSG\\_887](#) was added in 8.0.11.

- Error number: [MY-012713](#); Symbol: [ER\\_IB\\_MSG\\_888](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_888](#) was added in 8.0.11.

- Error number: [MY-012714](#); Symbol: [ER\\_IB\\_MSG\\_889](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_889](#) was added in 8.0.11.

- Error number: [MY-012715](#); Symbol: [ER\\_IB\\_MSG\\_890](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_890](#) was added in 8.0.11.

- Error number: [MY-012716](#); Symbol: [ER\\_IB\\_MSG\\_891](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_891](#) was added in 8.0.11.

- Error number: [MY-012717](#); Symbol: [ER\\_IB\\_MSG\\_892](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_892](#) was added in 8.0.11.

- Error number: [MY-012718](#); Symbol: [ER\\_IB\\_MSG\\_893](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_893](#) was added in 8.0.11.

- Error number: [MY-012719](#); Symbol: [ER\\_IB\\_MSG\\_894](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_894](#) was added in 8.0.11.

- Error number: [MY-012720](#); Symbol: [ER\\_IB\\_MSG\\_895](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_895](#) was added in 8.0.11.

- Error number: [MY-012721](#); Symbol: [ER\\_IB\\_MSG\\_896](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_896](#) was added in 8.0.11.

- Error number: [MY-012722](#); Symbol: [ER\\_IB\\_MSG\\_897](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_897](#) was added in 8.0.11.

- Error number: [MY-012723](#); Symbol: [ER\\_IB\\_MSG\\_898](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_898](#) was added in 8.0.11.

- Error number: [MY-012724](#); Symbol: [ER\\_IB\\_MSG\\_899](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_899](#) was added in 8.0.11.

- Error number: [MY-012725](#); Symbol: [ER\\_IB\\_MSG\\_900](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_900](#) was added in 8.0.11.

- Error number: [MY-012726](#); Symbol: [ER\\_IB\\_MSG\\_901](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_901](#) was added in 8.0.11.

- Error number: [MY-012727](#); Symbol: [ER\\_IB\\_MSG\\_902](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_902](#) was added in 8.0.11.

- Error number: [MY-012728](#); Symbol: [ER\\_IB\\_MSG\\_903](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_903](#) was added in 8.0.11.

- Error number: [MY-012729](#); Symbol: [ER\\_IB\\_MSG\\_904](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_904](#) was added in 8.0.11.

- Error number: [MY-012730](#); Symbol: [ER\\_IB\\_MSG\\_905](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_905](#) was added in 8.0.11.

- Error number: [MY-012731](#); Symbol: [ER\\_IB\\_MSG\\_906](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_906](#) was added in 8.0.11.

- Error number: [MY-012732](#); Symbol: [ER\\_IB\\_MSG\\_907](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_907](#) was added in 8.0.11.

- Error number: [MY-012733](#); Symbol: [ER\\_IB\\_MSG\\_908](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_908](#) was added in 8.0.11.

- Error number: [MY-012734](#); Symbol: [ER\\_IB\\_MSG\\_909](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_909](#) was added in 8.0.11.

- Error number: [MY-012735](#); Symbol: [ER\\_IB\\_MSG\\_910](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_910](#) was added in 8.0.11.

- Error number: [MY-012736](#); Symbol: [ER\\_IB\\_MSG\\_911](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_911](#) was added in 8.0.11.

- Error number: [MY-012737](#); Symbol: [ER\\_IB\\_MSG\\_912](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_912](#) was added in 8.0.11.

- Error number: [MY-012738](#); Symbol: [ER\\_IB\\_MSG\\_913](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_913](#) was added in 8.0.11.

- Error number: [MY-012739](#); Symbol: [ER\\_IB\\_MSG\\_914](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_914](#) was added in 8.0.11.

- Error number: [MY-012740](#); Symbol: [ER\\_IB\\_MSG\\_915](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_915](#) was added in 8.0.11.

- Error number: [MY-012741](#); Symbol: [ER\\_IB\\_MSG\\_916](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_916](#) was added in 8.0.11.

- Error number: [MY-012742](#); Symbol: [ER\\_IB\\_MSG\\_917](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_917](#) was added in 8.0.11.

- Error number: [MY-012743](#); Symbol: [ER\\_IB\\_MSG\\_918](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_918](#) was added in 8.0.11.

- Error number: [MY-012744](#); Symbol: [ER\\_IB\\_MSG\\_919](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_919](#) was added in 8.0.11.

- Error number: [MY-012745](#); Symbol: [ER\\_IB\\_MSG\\_920](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_920](#) was added in 8.0.11.

- Error number: [MY-012746](#); Symbol: [ER\\_IB\\_MSG\\_921](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_921](#) was added in 8.0.11.

- Error number: [MY-012747](#); Symbol: [ER\\_IB\\_MSG\\_922](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_922](#) was added in 8.0.11.

- Error number: [MY-012748](#); Symbol: [ER\\_IB\\_MSG\\_923](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_923](#) was added in 8.0.11.

- Error number: [MY-012749](#); Symbol: [ER\\_IB\\_MSG\\_924](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_924](#) was added in 8.0.11.

- Error number: [MY-012750](#); Symbol: [ER\\_IB\\_MSG\\_925](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_925](#) was added in 8.0.11.

- Error number: [MY-012751](#); Symbol: [ER\\_IB\\_MSG\\_926](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_926](#) was added in 8.0.11.

- Error number: [MY-012752](#); Symbol: [ER\\_IB\\_MSG\\_927](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_927](#) was added in 8.0.11.

- Error number: [MY-012753](#); Symbol: [ER\\_IB\\_MSG\\_928](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_928](#) was added in 8.0.11.

- Error number: [MY-012754](#); Symbol: [ER\\_IB\\_MSG\\_929](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_929](#) was added in 8.0.11.

- Error number: [MY-012755](#); Symbol: [ER\\_IB\\_MSG\\_930](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_930](#) was added in 8.0.11.

- Error number: [MY-012756](#); Symbol: [ER\\_IB\\_MSG\\_931](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_931](#) was added in 8.0.11.

- Error number: [MY-012757](#); Symbol: [ER\\_IB\\_MSG\\_932](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_932](#) was added in 8.0.11.

- Error number: [MY-012758](#); Symbol: [ER\\_IB\\_MSG\\_933](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_933](#) was added in 8.0.11.

- Error number: [MY-012759](#); Symbol: [ER\\_IB\\_MSG\\_934](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_934](#) was added in 8.0.11.

- Error number: [MY-012760](#); Symbol: [ER\\_IB\\_MSG\\_935](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_935](#) was added in 8.0.11.

- Error number: [MY-012761](#); Symbol: [ER\\_IB\\_MSG\\_936](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_936](#) was added in 8.0.11.

- Error number: [MY-012762](#); Symbol: [ER\\_IB\\_MSG\\_937](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_937](#) was added in 8.0.11.

- Error number: [MY-012763](#); Symbol: [ER\\_IB\\_MSG\\_938](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_938](#) was added in 8.0.11.

- Error number: [MY-012764](#); Symbol: [ER\\_IB\\_MSG\\_939](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_939](#) was added in 8.0.11.

- Error number: [MY-012765](#); Symbol: [ER\\_IB\\_MSG\\_940](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_940](#) was added in 8.0.11.

- Error number: [MY-012766](#); Symbol: [ER\\_IB\\_MSG\\_941](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_941](#) was added in 8.0.11.

- Error number: [MY-012767](#); Symbol: [ER\\_IB\\_MSG\\_942](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_942](#) was added in 8.0.11.

- Error number: [MY-012768](#); Symbol: [ER\\_IB\\_MSG\\_943](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_943](#) was added in 8.0.11.

- Error number: [MY-012769](#); Symbol: [ER\\_IB\\_MSG\\_944](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_944](#) was added in 8.0.11.

- Error number: [MY-012770](#); Symbol: [ER\\_IB\\_MSG\\_945](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_945](#) was added in 8.0.11.

- Error number: [MY-012771](#); Symbol: [ER\\_IB\\_MSG\\_946](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_946](#) was added in 8.0.11.

- Error number: [MY-012772](#); Symbol: [ER\\_IB\\_MSG\\_947](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_947](#) was added in 8.0.11.

- Error number: [MY-012773](#); Symbol: [ER\\_IB\\_MSG\\_948](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_948](#) was added in 8.0.11.

- Error number: [MY-012774](#); Symbol: [ER\\_IB\\_MSG\\_949](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_949](#) was added in 8.0.11.

- Error number: [MY-012775](#); Symbol: [ER\\_IB\\_MSG\\_950](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_950](#) was added in 8.0.11.

- Error number: [MY-012776](#); Symbol: [ER\\_IB\\_MSG\\_951](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_951](#) was added in 8.0.11.

- Error number: [MY-012777](#); Symbol: [ER\\_IB\\_MSG\\_952](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_952](#) was added in 8.0.11.

- Error number: [MY-012778](#); Symbol: [ER\\_IB\\_MSG\\_953](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_953](#) was added in 8.0.11.

- Error number: [MY-012779](#); Symbol: [ER\\_IB\\_MSG\\_954](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_954](#) was added in 8.0.11.

- Error number: [MY-012780](#); Symbol: [ER\\_IB\\_MSG\\_955](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_955](#) was added in 8.0.11.

- Error number: [MY-012781](#); Symbol: [ER\\_IB\\_MSG\\_956](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_956](#) was added in 8.0.11.

- Error number: [MY-012782](#); Symbol: [ER\\_IB\\_MSG\\_957](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_957](#) was added in 8.0.11.

- Error number: [MY-012783](#); Symbol: [ER\\_IB\\_MSG\\_958](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_958](#) was added in 8.0.11.

- Error number: [MY-012784](#); Symbol: [ER\\_IB\\_MSG\\_959](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_959](#) was added in 8.0.11.

- Error number: [MY-012785](#); Symbol: [ER\\_IB\\_MSG\\_960](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_960](#) was added in 8.0.11.

- Error number: [MY-012786](#); Symbol: [ER\\_IB\\_MSG\\_961](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_961](#) was added in 8.0.11.

- Error number: [MY-012787](#); Symbol: [ER\\_IB\\_MSG\\_962](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_962](#) was added in 8.0.11.

- Error number: [MY-012788](#); Symbol: [ER\\_IB\\_MSG\\_963](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_963](#) was added in 8.0.11.

- Error number: [MY-012789](#); Symbol: [ER\\_IB\\_MSG\\_964](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_964](#) was added in 8.0.11.

- Error number: [MY-012790](#); Symbol: [ER\\_IB\\_MSG\\_965](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_965](#) was added in 8.0.11.

- Error number: [MY-012791](#); Symbol: [ER\\_IB\\_MSG\\_966](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_966](#) was added in 8.0.11.

- Error number: [MY-012792](#); Symbol: [ER\\_IB\\_MSG\\_967](#); SQLSTATE: [HY000](#)



---

Message: %s

[ER\\_IB\\_MSG\\_967](#) was added in 8.0.11.

- Error number: [MY-012793](#); Symbol: [ER\\_IB\\_MSG\\_968](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_968](#) was added in 8.0.11.

- Error number: [MY-012794](#); Symbol: [ER\\_IB\\_MSG\\_969](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_969](#) was added in 8.0.11.

- Error number: [MY-012795](#); Symbol: [ER\\_IB\\_MSG\\_970](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_970](#) was added in 8.0.11.

- Error number: [MY-012796](#); Symbol: [ER\\_IB\\_MSG\\_971](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_971](#) was added in 8.0.11.

- Error number: [MY-012797](#); Symbol: [ER\\_IB\\_MSG\\_972](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_972](#) was added in 8.0.11.

- Error number: [MY-012798](#); Symbol: [ER\\_IB\\_MSG\\_973](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_973](#) was added in 8.0.11.

- Error number: [MY-012799](#); Symbol: [ER\\_IB\\_MSG\\_974](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_974](#) was added in 8.0.11.

- Error number: [MY-012800](#); Symbol: [ER\\_IB\\_MSG\\_975](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_975](#) was added in 8.0.11.

- Error number: [MY-012801](#); Symbol: [ER\\_IB\\_MSG\\_976](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_976](#) was added in 8.0.11.

- Error number: [MY-012802](#); Symbol: [ER\\_IB\\_MSG\\_977](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_977](#) was added in 8.0.11.

- Error number: [MY-012803](#); Symbol: [ER\\_IB\\_MSG\\_978](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_978](#) was added in 8.0.11.

- Error number: [MY-012804](#); Symbol: [ER\\_IB\\_MSG\\_979](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_979](#) was added in 8.0.11.

- Error number: [MY-012805](#); Symbol: [ER\\_IB\\_MSG\\_980](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_980](#) was added in 8.0.11.

- Error number: [MY-012806](#); Symbol: [ER\\_IB\\_MSG\\_981](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_981](#) was added in 8.0.11.

- Error number: [MY-012807](#); Symbol: [ER\\_IB\\_MSG\\_982](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_982](#) was added in 8.0.11.

- Error number: [MY-012808](#); Symbol: [ER\\_IB\\_MSG\\_983](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_983](#) was added in 8.0.11.

- Error number: [MY-012809](#); Symbol: [ER\\_IB\\_MSG\\_984](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_984](#) was added in 8.0.11.

- Error number: [MY-012810](#); Symbol: [ER\\_IB\\_MSG\\_985](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_985](#) was added in 8.0.11.

- Error number: [MY-012811](#); Symbol: [ER\\_IB\\_MSG\\_986](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_986](#) was added in 8.0.11.

- Error number: [MY-012812](#); Symbol: [ER\\_IB\\_MSG\\_987](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_987](#) was added in 8.0.11.

- Error number: [MY-012813](#); Symbol: [ER\\_IB\\_MSG\\_988](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_988](#) was added in 8.0.11.

- Error number: [MY-012814](#); Symbol: [ER\\_IB\\_MSG\\_989](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_989](#) was added in 8.0.11.

- Error number: [MY-012815](#); Symbol: [ER\\_IB\\_MSG\\_990](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_990](#) was added in 8.0.11.

- Error number: [MY-012816](#); Symbol: [ER\\_IB\\_MSG\\_991](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_991](#) was added in 8.0.11.

- Error number: [MY-012817](#); Symbol: [ER\\_IB\\_MSG\\_992](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_992](#) was added in 8.0.11.

- Error number: [MY-012818](#); Symbol: [ER\\_IB\\_MSG\\_993](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_993](#) was added in 8.0.11.

- Error number: [MY-012819](#); Symbol: [ER\\_IB\\_MSG\\_994](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_994](#) was added in 8.0.11.

- Error number: [MY-012820](#); Symbol: [ER\\_IB\\_MSG\\_995](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_995](#) was added in 8.0.11.

- Error number: [MY-012821](#); Symbol: [ER\\_IB\\_MSG\\_996](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_996](#) was added in 8.0.11.

- Error number: [MY-012822](#); Symbol: [ER\\_IB\\_MSG\\_997](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_997](#) was added in 8.0.11.

- Error number: [MY-012823](#); Symbol: [ER\\_IB\\_MSG\\_998](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_998](#) was added in 8.0.11.

- Error number: [MY-012824](#); Symbol: [ER\\_IB\\_MSG\\_999](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_999](#) was added in 8.0.11.

- Error number: [MY-012825](#); Symbol: [ER\\_IB\\_MSG\\_1000](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1000](#) was added in 8.0.11.

- Error number: [MY-012826](#); Symbol: [ER\\_IB\\_MSG\\_1001](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1001](#) was added in 8.0.11.

- Error number: [MY-012827](#); Symbol: [ER\\_IB\\_MSG\\_1002](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1002](#) was added in 8.0.11.

- Error number: [MY-012828](#); Symbol: [ER\\_IB\\_MSG\\_1003](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1003](#) was added in 8.0.11.

- Error number: [MY-012829](#); Symbol: [ER\\_IB\\_MSG\\_1004](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1004](#) was added in 8.0.11.

- Error number: [MY-012830](#); Symbol: [ER\\_IB\\_MSG\\_1005](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1005](#) was added in 8.0.11.

- Error number: [MY-012831](#); Symbol: [ER\\_IB\\_MSG\\_1006](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1006](#) was added in 8.0.11.

- Error number: [MY-012832](#); Symbol: [ER\\_IB\\_MSG\\_1007](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_1007](#) was added in 8.0.11.

- Error number: [MY-012833](#); Symbol: [ER\\_IB\\_MSG\\_1008](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1008](#) was added in 8.0.11.

- Error number: [MY-012834](#); Symbol: [ER\\_IB\\_MSG\\_1009](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1009](#) was added in 8.0.11.

- Error number: [MY-012835](#); Symbol: [ER\\_IB\\_MSG\\_1010](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1010](#) was added in 8.0.11.

- Error number: [MY-012836](#); Symbol: [ER\\_IB\\_MSG\\_1011](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1011](#) was added in 8.0.11.

- Error number: [MY-012837](#); Symbol: [ER\\_IB\\_MSG\\_1012](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1012](#) was added in 8.0.11.

- Error number: [MY-012838](#); Symbol: [ER\\_IB\\_MSG\\_1013](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1013](#) was added in 8.0.11.

- Error number: [MY-012839](#); Symbol: [ER\\_IB\\_MSG\\_1014](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1014](#) was added in 8.0.11.

- Error number: [MY-012840](#); Symbol: [ER\\_IB\\_MSG\\_1015](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1015](#) was added in 8.0.11.

- Error number: [MY-012841](#); Symbol: [ER\\_IB\\_MSG\\_1016](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1016](#) was added in 8.0.11.

- Error number: [MY-012842](#); Symbol: [ER\\_IB\\_MSG\\_1017](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_1017](#) was added in 8.0.11.

- Error number: [MY-012843](#); Symbol: [ER\\_IB\\_MSG\\_1018](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1018](#) was added in 8.0.11.

- Error number: [MY-012844](#); Symbol: [ER\\_IB\\_MSG\\_1019](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1019](#) was added in 8.0.11.

- Error number: [MY-012845](#); Symbol: [ER\\_IB\\_MSG\\_1020](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1020](#) was added in 8.0.11.

- Error number: [MY-012846](#); Symbol: [ER\\_IB\\_MSG\\_1021](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1021](#) was added in 8.0.11.

- Error number: [MY-012847](#); Symbol: [ER\\_IB\\_MSG\\_1022](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1022](#) was added in 8.0.11.

- Error number: [MY-012848](#); Symbol: [ER\\_IB\\_MSG\\_1023](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1023](#) was added in 8.0.11.

- Error number: [MY-012849](#); Symbol: [ER\\_IB\\_MSG\\_1024](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1024](#) was added in 8.0.11.

- Error number: [MY-012850](#); Symbol: [ER\\_IB\\_MSG\\_1025](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1025](#) was added in 8.0.11.

- Error number: [MY-012851](#); Symbol: [ER\\_IB\\_MSG\\_1026](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1026](#) was added in 8.0.11.

- Error number: [MY-012852](#); Symbol: [ER\\_IB\\_MSG\\_1027](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_1027](#) was added in 8.0.11.

- Error number: [MY-012853](#); Symbol: [ER\\_IB\\_MSG\\_1028](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1028](#) was added in 8.0.11.

- Error number: [MY-012854](#); Symbol: [ER\\_IB\\_MSG\\_1029](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1029](#) was added in 8.0.11.

- Error number: [MY-012855](#); Symbol: [ER\\_IB\\_MSG\\_1030](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1030](#) was added in 8.0.11.

- Error number: [MY-012856](#); Symbol: [ER\\_IB\\_MSG\\_1031](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1031](#) was added in 8.0.11.

- Error number: [MY-012857](#); Symbol: [ER\\_IB\\_MSG\\_1032](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1032](#) was added in 8.0.11.

- Error number: [MY-012858](#); Symbol: [ER\\_IB\\_MSG\\_1033](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1033](#) was added in 8.0.11.

- Error number: [MY-012859](#); Symbol: [ER\\_IB\\_MSG\\_1034](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1034](#) was added in 8.0.11.

- Error number: [MY-012860](#); Symbol: [ER\\_IB\\_MSG\\_1035](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1035](#) was added in 8.0.11.

- Error number: [MY-012861](#); Symbol: [ER\\_IB\\_MSG\\_1036](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1036](#) was added in 8.0.11.

- Error number: [MY-012862](#); Symbol: [ER\\_IB\\_MSG\\_1037](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_1037](#) was added in 8.0.11.

- Error number: [MY-012863](#); Symbol: [ER\\_IB\\_MSG\\_1038](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1038](#) was added in 8.0.11.

- Error number: [MY-012864](#); Symbol: [ER\\_IB\\_MSG\\_1039](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1039](#) was added in 8.0.11.

- Error number: [MY-012865](#); Symbol: [ER\\_IB\\_MSG\\_1040](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1040](#) was added in 8.0.11.

- Error number: [MY-012866](#); Symbol: [ER\\_IB\\_MSG\\_1041](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1041](#) was added in 8.0.11.

- Error number: [MY-012867](#); Symbol: [ER\\_IB\\_MSG\\_1042](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1042](#) was added in 8.0.11.

- Error number: [MY-012868](#); Symbol: [ER\\_IB\\_MSG\\_1043](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1043](#) was added in 8.0.11.

- Error number: [MY-012869](#); Symbol: [ER\\_IB\\_MSG\\_1044](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1044](#) was added in 8.0.11.

- Error number: [MY-012870](#); Symbol: [ER\\_IB\\_MSG\\_1045](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1045](#) was added in 8.0.11.

- Error number: [MY-012871](#); Symbol: [ER\\_IB\\_MSG\\_1046](#); SQLSTATE: [HY000](#)

Message: Old log sequence number %llu was greater than the new log sequence number %llu. Please submit a bug report to <http://bugs.mysql.com>

[ER\\_IB\\_MSG\\_1046](#) was added in 8.0.11.



- 
- Error number: [MY-012872](#); Symbol: [ER\\_IB\\_MSG\\_1047](#); SQLSTATE: [HY000](#)  
Message: Semaphore wait has lasted > %llu seconds. We intentionally crash the server because it appears to be hung.  
[ER\\_IB\\_MSG\\_1047](#) was added in 8.0.11.
  - Error number: [MY-012873](#); Symbol: [ER\\_IB\\_MSG\\_1048](#); SQLSTATE: [HY000](#)  
Message: Waiting for %llu table(s) to be dropped  
[ER\\_IB\\_MSG\\_1048](#) was added in 8.0.11.
  - Error number: [MY-012874](#); Symbol: [ER\\_IB\\_MSG\\_1049](#); SQLSTATE: [HY000](#)  
Message: Waiting for change buffer merge to complete number of bytes of change buffer just merged: %llu  
[ER\\_IB\\_MSG\\_1049](#) was added in 8.0.11.
  - Error number: [MY-012875](#); Symbol: [ER\\_IB\\_MSG\\_1050](#); SQLSTATE: [HY000](#)  
Message: Can't set undo tablespace(s) to be encrypted since --innodb\_undo\_tablespaces=0.  
[ER\\_IB\\_MSG\\_1050](#) was added in 8.0.11, removed after 8.0.15.
  - Error number: [MY-012876](#); Symbol: [ER\\_IB\\_MSG\\_1051](#); SQLSTATE: [HY000](#)  
Message: Can't set undo tablespace(s) to be encrypted in read-only-mode.  
[ER\\_IB\\_MSG\\_1051](#) was added in 8.0.11.
  - Error number: [MY-012877](#); Symbol: [ER\\_IB\\_MSG\\_1052](#); SQLSTATE: [HY000](#)  
Message: Can't set undo tablespace '%s' to be encrypted.  
[ER\\_IB\\_MSG\\_1052](#) was added in 8.0.11.
  - Error number: [MY-012878](#); Symbol: [ER\\_IB\\_MSG\\_1053](#); SQLSTATE: [HY000](#)  
Message: Can't set undo tablespace '%s' to be encrypted. Failed to write header page.  
[ER\\_IB\\_MSG\\_1053](#) was added in 8.0.11.
  - Error number: [MY-012879](#); Symbol: [ER\\_IB\\_MSG\\_1054](#); SQLSTATE: [HY000](#)  
Message: Can't set undo tablespace '%s' to be encrypted. Error %d - %s  
[ER\\_IB\\_MSG\\_1054](#) was added in 8.0.11.
  - Error number: [MY-012880](#); Symbol: [ER\\_IB\\_MSG\\_1055](#); SQLSTATE: [HY000](#)  
Message: Encryption is enabled for undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_1055](#) was added in 8.0.11.
  - Error number: [MY-012881](#); Symbol: [ER\\_IB\\_MSG\\_1056](#); SQLSTATE: [HY000](#)  
Message: Can't rotate encryption on undo tablespace '%s'.

- 
- [ER\\_IB\\_MSG\\_1056](#) was added in 8.0.11.
- Error number: [MY-012882](#); Symbol: [ER\\_IB\\_MSG\\_1057](#); SQLSTATE: [HY000](#)  
Message: Encryption is enabled for undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_1057](#) was added in 8.0.11.
  - Error number: [MY-012883](#); Symbol: [ER\\_IB\\_MSG\\_1058](#); SQLSTATE: [HY000](#)  
Message: os\_file\_get\_status() failed on '%s'. Can't determine file permissions.  
[ER\\_IB\\_MSG\\_1058](#) was added in 8.0.11.
  - Error number: [MY-012884](#); Symbol: [ER\\_IB\\_MSG\\_1059](#); SQLSTATE: [HY000](#)  
Message: %s can't be opened in %s mode.  
[ER\\_IB\\_MSG\\_1059](#) was added in 8.0.11.
  - Error number: [MY-012885](#); Symbol: [ER\\_IB\\_MSG\\_1060](#); SQLSTATE: [HY000](#)  
Message: '%s' not a regular file.  
[ER\\_IB\\_MSG\\_1060](#) was added in 8.0.11.
  - Error number: [MY-012886](#); Symbol: [ER\\_IB\\_MSG\\_1061](#); SQLSTATE: [HY000](#)  
Message: Cannot create %s  
[ER\\_IB\\_MSG\\_1061](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012886](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_OS\\_CREATE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Cannot create %s  
[ER\\_IB\\_MSG\\_LOG\\_FILE\\_OS\\_CREATE\\_FAILED](#) was added in 8.0.30.
  - Error number: [MY-012887](#); Symbol: [ER\\_IB\\_MSG\\_1062](#); SQLSTATE: [HY000](#)  
Message: Setting log file %s size to %llu MB. Progress : %u%%  
[ER\\_IB\\_MSG\\_1062](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012887](#); Symbol: [ER\\_IB\\_MSG\\_FILE\\_RESIZE](#); SQLSTATE: [HY000](#)  
Message: Setting file %s size to %llu MB. Progress : %u%%  
[ER\\_IB\\_MSG\\_FILE\\_RESIZE](#) was added in 8.0.30.
  - Error number: [MY-012888](#); Symbol: [ER\\_IB\\_MSG\\_1063](#); SQLSTATE: [HY000](#)  
Message: Cannot set log file %s to size %llu MB  
[ER\\_IB\\_MSG\\_1063](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-012888](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_RESIZE\\_FAILED](#); SQLSTATE: [HY000](#)

---

Message: Cannot resize redo log file %s to %llu MB (%s)

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_RESIZE\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-012889](#); Symbol: [ER\\_IB\\_MSG\\_1064](#); SQLSTATE: [HY000](#)

Message: Cannot create log files in read-only mode

[ER\\_IB\\_MSG\\_1064](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012889](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_CREATE\\_AND\\_READ\\_ONLY\\_MODE](#); SQLSTATE: [HY000](#)

Message: Cannot create redo log files in read-only mode (--innodb-read-only).

[ER\\_IB\\_MSG\\_LOG\\_FILES\\_CREATE\\_AND\\_READ\\_ONLY\\_MODE](#) was added in 8.0.30.

- Error number: [MY-012890](#); Symbol: [ER\\_IB\\_MSG\\_1065](#); SQLSTATE: [HY000](#)

Message: Redo log encryption is enabled, but the keyring is not loaded.

[ER\\_IB\\_MSG\\_1065](#) was added in 8.0.11.

- Error number: [MY-012891](#); Symbol: [ER\\_IB\\_MSG\\_1066](#); SQLSTATE: [HY000](#)

Message: Cannot create file for log file %s.

[ER\\_IB\\_MSG\\_1066](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012891](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_PREPARE\\_ON\\_CREATE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to create redo log file %s (error: %d) for start LSN %llu

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_PREPARE\\_ON\\_CREATE\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-012892](#); Symbol: [ER\\_IB\\_MSG\\_1067](#); SQLSTATE: [HY000](#)

Message: Renaming log file %s to %s

[ER\\_IB\\_MSG\\_1067](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012893](#); Symbol: [ER\\_IB\\_MSG\\_1068](#); SQLSTATE: [HY000](#)

Message: New log files created, LSN=%llu

[ER\\_IB\\_MSG\\_1068](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012893](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: New redo log files created, LSN=%llu

[ER\\_IB\\_MSG\\_LOG\\_FILES\\_INITIALIZED](#) was added in 8.0.30.

- Error number: [MY-012894](#); Symbol: [ER\\_IB\\_MSG\\_1069](#); SQLSTATE: [HY000](#)

Message: Unable to open '%s'.

[ER\\_IB\\_MSG\\_1069](#) was added in 8.0.11, removed after 8.0.29.

- 
- Error number: [MY-012894](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_OPEN\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Unable to open '%s' (error: %d).  
[ER\\_IB\\_MSG\\_LOG\\_FILE\\_OPEN\\_FAILED](#) was added in 8.0.30.
  - Error number: [MY-012895](#); Symbol: [ER\\_IB\\_MSG\\_1070](#); SQLSTATE: [HY000](#)  
Message: Cannot create construction log file '%s' for undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_1070](#) was added in 8.0.11.
  - Error number: [MY-012896](#); Symbol: [ER\\_IB\\_MSG\\_1071](#); SQLSTATE: [HY000](#)  
Message: Creating UNDO Tablespace %s  
[ER\\_IB\\_MSG\\_1071](#) was added in 8.0.11.
  - Error number: [MY-012897](#); Symbol: [ER\\_IB\\_MSG\\_1072](#); SQLSTATE: [HY000](#)  
Message: Setting file %s size to %llu MB  
[ER\\_IB\\_MSG\\_1072](#) was added in 8.0.11.
  - Error number: [MY-012898](#); Symbol: [ER\\_IB\\_MSG\\_1073](#); SQLSTATE: [HY000](#)  
Message: Physically writing the file full  
[ER\\_IB\\_MSG\\_1073](#) was added in 8.0.11.
  - Error number: [MY-012899](#); Symbol: [ER\\_IB\\_MSG\\_1074](#); SQLSTATE: [HY000](#)  
Message: Error in creating %s: probably out of disk space  
[ER\\_IB\\_MSG\\_1074](#) was added in 8.0.11.
  - Error number: [MY-012900](#); Symbol: [ER\\_IB\\_MSG\\_1075](#); SQLSTATE: [HY000](#)  
Message: Can't set encryption metadata for space %s  
[ER\\_IB\\_MSG\\_1075](#) was added in 8.0.11.
  - Error number: [MY-012901](#); Symbol: [ER\\_IB\\_MSG\\_1076](#); SQLSTATE: [HY000](#)  
Message: Cannot read first page of '%s' - %s  
[ER\\_IB\\_MSG\\_1076](#) was added in 8.0.11.
  - Error number: [MY-012902](#); Symbol: [ER\\_IB\\_MSG\\_1077](#); SQLSTATE: [HY000](#)  
Message: Undo tablespace number %lu was being truncated when mysqld quit.  
[ER\\_IB\\_MSG\\_1077](#) was added in 8.0.11.
  - Error number: [MY-012903](#); Symbol: [ER\\_IB\\_MSG\\_1078](#); SQLSTATE: [HY000](#)  
Message: Cannot recover a truncated undo tablespace in read-only mode  
[ER\\_IB\\_MSG\\_1078](#) was added in 8.0.11.

- 
- Error number: [MY-012904](#); Symbol: [ER\\_IB\\_MSG\\_1079](#); SQLSTATE: [HY000](#)  
Message: Reconstructing undo tablespace number %lu.  
[ER\\_IB\\_MSG\\_1079](#) was added in 8.0.11.
  - Error number: [MY-012905](#); Symbol: [ER\\_IB\\_MSG\\_1080](#); SQLSTATE: [HY000](#)  
Message: Cannot create %s because %s already uses Space ID=%lu! Did you change innodb\_undo\_directory?  
[ER\\_IB\\_MSG\\_1080](#) was added in 8.0.11.
  - Error number: [MY-012906](#); Symbol: [ER\\_IB\\_MSG\\_1081](#); SQLSTATE: [HY000](#)  
Message: UNDO tablespace %s must be %s  
[ER\\_IB\\_MSG\\_1081](#) was added in 8.0.11.
  - Error number: [MY-012907](#); Symbol: [ER\\_IB\\_MSG\\_1082](#); SQLSTATE: [HY000](#)  
Message: Error creating file for %s  
[ER\\_IB\\_MSG\\_1082](#) was added in 8.0.11.
  - Error number: [MY-012908](#); Symbol: [ER\\_IB\\_MSG\\_1083](#); SQLSTATE: [HY000](#)  
Message: Error reading encryption for %s  
[ER\\_IB\\_MSG\\_1083](#) was added in 8.0.11.
  - Error number: [MY-012909](#); Symbol: [ER\\_IB\\_MSG\\_1084](#); SQLSTATE: [HY000](#)  
Message: Unable to open undo tablespace number %lu  
[ER\\_IB\\_MSG\\_1084](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012909](#); Symbol: [ER\\_IB\\_MSG\\_CANNOT\\_OPEN\\_57\\_UNDO](#); SQLSTATE: [HY000](#)  
Message: Unable to open undo tablespace number %lu  
[ER\\_IB\\_MSG\\_CANNOT\\_OPEN\\_57\\_UNDO](#) was added in 8.0.21.
  - Error number: [MY-012910](#); Symbol: [ER\\_IB\\_MSG\\_1085](#); SQLSTATE: [HY000](#)  
Message: Opened %llu existing undo tablespaces.  
[ER\\_IB\\_MSG\\_1085](#) was added in 8.0.11.
  - Error number: [MY-012911](#); Symbol: [ER\\_IB\\_MSG\\_1086](#); SQLSTATE: [HY000](#)  
Message: Cannot create undo tablespaces since innodb\_%s has been set. Using %llu existing undo tablespaces.  
[ER\\_IB\\_MSG\\_1086](#) was added in 8.0.11.
  - Error number: [MY-012912](#); Symbol: [ER\\_IB\\_MSG\\_1087](#); SQLSTATE: [HY000](#)  
Message: Cannot continue InnoDB startup in %s mode because there are no existing undo tablespaces found.

---

[ER\\_IB\\_MSG\\_1087](#) was added in 8.0.11.

- Error number: [MY-012913](#); Symbol: [ER\\_IB\\_MSG\\_1088](#); SQLSTATE: [HY000](#)

Message: Could not create undo tablespace '%s'.

[ER\\_IB\\_MSG\\_1088](#) was added in 8.0.11.

- Error number: [MY-012914](#); Symbol: [ER\\_IB\\_MSG\\_1089](#); SQLSTATE: [HY000](#)

Message: Error %d - %s - opening newly created undo tablespace '%s'.

[ER\\_IB\\_MSG\\_1089](#) was added in 8.0.11.

- Error number: [MY-012915](#); Symbol: [ER\\_IB\\_MSG\\_1090](#); SQLSTATE: [HY000](#)

Message: Created %llu undo tablespaces.

[ER\\_IB\\_MSG\\_1090](#) was added in 8.0.11.

- Error number: [MY-012916](#); Symbol: [ER\\_IB\\_MSG\\_1091](#); SQLSTATE: [HY000](#)

Message: Unable to create encrypted undo tablespace number %lu. please check if the keyring is initialized correctly

[ER\\_IB\\_MSG\\_1091](#) was added in 8.0.11.

- Error number: [MY-012917](#); Symbol: [ER\\_IB\\_MSG\\_1092](#); SQLSTATE: [HY000](#)

Message: Encryption is enabled for undo tablespace number %lu.

[ER\\_IB\\_MSG\\_1092](#) was added in 8.0.11.

- Error number: [MY-012918](#); Symbol: [ER\\_IB\\_MSG\\_1093](#); SQLSTATE: [HY000](#)

Message: Unable to initialize the header page in undo tablespace number %lu.

[ER\\_IB\\_MSG\\_1093](#) was added in 8.0.11.

- Error number: [MY-012919](#); Symbol: [ER\\_IB\\_MSG\\_1094](#); SQLSTATE: [HY000](#)

Message: Cannot delete old undo tablespaces because they contain undo logs for XA PREPARED transactions.

[ER\\_IB\\_MSG\\_1094](#) was added in 8.0.11.

- Error number: [MY-012920](#); Symbol: [ER\\_IB\\_MSG\\_1095](#); SQLSTATE: [HY000](#)

Message: Upgrading %zu existing undo tablespaces that were tracked in the system tablespace to %lu new independent undo tablespaces.

[ER\\_IB\\_MSG\\_1095](#) was added in 8.0.11.

- Error number: [MY-012921](#); Symbol: [ER\\_IB\\_MSG\\_1096](#); SQLSTATE: [HY000](#)

Message: Deleting %llu new independent undo tablespaces that we just created.

[ER\\_IB\\_MSG\\_1096](#) was added in 8.0.11.

- 
- Error number: [MY-012922](#); Symbol: [ER\\_IB\\_MSG\\_1097](#); SQLSTATE: [HY000](#)  
Message: Waiting for purge to start  
[ER\\_IB\\_MSG\\_1097](#) was added in 8.0.11.
  - Error number: [MY-012923](#); Symbol: [ER\\_IB\\_MSG\\_1098](#); SQLSTATE: [HY000](#)  
Message: Creating shared tablespace for temporary tables  
[ER\\_IB\\_MSG\\_1098](#) was added in 8.0.11.
  - Error number: [MY-012924](#); Symbol: [ER\\_IB\\_MSG\\_1099](#); SQLSTATE: [HY000](#)  
Message: The %s data file must be writable!  
[ER\\_IB\\_MSG\\_1099](#) was added in 8.0.11.
  - Error number: [MY-012925](#); Symbol: [ER\\_IB\\_MSG\\_1100](#); SQLSTATE: [HY000](#)  
Message: Could not create the shared %s.  
[ER\\_IB\\_MSG\\_1100](#) was added in 8.0.11.
  - Error number: [MY-012926](#); Symbol: [ER\\_IB\\_MSG\\_1101](#); SQLSTATE: [HY000](#)  
Message: Unable to create the shared %s.  
[ER\\_IB\\_MSG\\_1101](#) was added in 8.0.11.
  - Error number: [MY-012927](#); Symbol: [ER\\_IB\\_MSG\\_1102](#); SQLSTATE: [HY000](#)  
Message: The %s data file cannot be re-opened after check\_file\_spec() succeeded!  
[ER\\_IB\\_MSG\\_1102](#) was added in 8.0.11.
  - Error number: [MY-012928](#); Symbol: [ER\\_IB\\_MSG\\_1103](#); SQLSTATE: [HY000](#)  
Message: %d threads created by InnoDB had not exited at shutdown!  
[ER\\_IB\\_MSG\\_1103](#) was added in 8.0.11.
  - Error number: [MY-012929](#); Symbol: [ER\\_IB\\_MSG\\_1104](#); SQLSTATE: [HY000](#)  
Message: InnoDB Database creation was aborted %swith error %s. You may need to delete the ibdata1 file before trying to start up again.  
[ER\\_IB\\_MSG\\_1104](#) was added in 8.0.11.
  - Error number: [MY-012930](#); Symbol: [ER\\_IB\\_MSG\\_1105](#); SQLSTATE: [HY000](#)  
Message: Plugin initialization aborted %swith error %s.  
[ER\\_IB\\_MSG\\_1105](#) was added in 8.0.11.
  - Error number: [MY-012931](#); Symbol: [ER\\_IB\\_MSG\\_1106](#); SQLSTATE: [HY000](#)  
Message: Waiting for %llu buffer page I/Os to complete  
[ER\\_IB\\_MSG\\_1106](#) was added in 8.0.11, removed after 8.0.29.

- 
- Error number: `MY-012931`; Symbol: `ER_IB_MSG_BUF_PENDING_IO`; SQLSTATE: `HY000`  
Message: Waiting for %zu buffer page I/Os to complete.  
`ER_IB_MSG_BUF_PENDING_IO` was added in 8.0.30.
  - Error number: `MY-012932`; Symbol: `ER_IB_MSG_1107`; SQLSTATE: `HY000`  
Message: PUNCH HOLE support available  
`ER_IB_MSG_1107` was added in 8.0.11.
  - Error number: `MY-012933`; Symbol: `ER_IB_MSG_1108`; SQLSTATE: `HY000`  
Message: PUNCH HOLE support not available  
`ER_IB_MSG_1108` was added in 8.0.11.
  - Error number: `MY-012934`; Symbol: `ER_IB_MSG_1109`; SQLSTATE: `HY000`  
Message: Size of InnoDB's ulint is %zu but size of void\* is %zu. The sizes should be the same so that on a 64-bit platforms you can allocate more than 4 GB of memory.  
`ER_IB_MSG_1109` was added in 8.0.11.
  - Error number: `MY-012935`; Symbol: `ER_IB_MSG_1110`; SQLSTATE: `HY000`  
Message: Database upgrade cannot be accomplished in read-only mode.  
`ER_IB_MSG_1110` was added in 8.0.11.
  - Error number: `MY-012936`; Symbol: `ER_IB_MSG_1111`; SQLSTATE: `HY000`  
Message: Database upgrade cannot be accomplished with innodb\_force\_recovery > 0  
`ER_IB_MSG_1111` was added in 8.0.11.
  - Error number: `MY-012937`; Symbol: `ER_IB_MSG_1112`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_1112` was added in 8.0.11.
  - Error number: `MY-012938`; Symbol: `ER_IB_MSG_1113`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_1113` was added in 8.0.11.
  - Error number: `MY-012939`; Symbol: `ER_IB_MSG_1114`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_1114` was added in 8.0.11.
  - Error number: `MY-012940`; Symbol: `ER_IB_MSG_1115`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_1115` was added in 8.0.11.



- 
- Error number: [MY-012941](#); Symbol: [ER\\_IB\\_MSG\\_1116](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1116](#) was added in 8.0.11.
  - Error number: [MY-012942](#); Symbol: [ER\\_IB\\_MSG\\_1117](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1117](#) was added in 8.0.11.
  - Error number: [MY-012943](#); Symbol: [ER\\_IB\\_MSG\\_1118](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1118](#) was added in 8.0.11, removed after 8.0.22.
  - Error number: [MY-012944](#); Symbol: [ER\\_IB\\_MSG\\_1119](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1119](#) was added in 8.0.11.
  - Error number: [MY-012945](#); Symbol: [ER\\_IB\\_MSG\\_1120](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1120](#) was added in 8.0.11.
  - Error number: [MY-012946](#); Symbol: [ER\\_IB\\_MSG\\_1121](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1121](#) was added in 8.0.11.
  - Error number: [MY-012947](#); Symbol: [ER\\_IB\\_MSG\\_1122](#); SQLSTATE: [HY000](#)  
Message: MySQL was built without a memory barrier capability on this architecture, which might allow a mutex/rw\_lock violation under high thread concurrency. This may cause a hang.  
[ER\\_IB\\_MSG\\_1122](#) was added in 8.0.11.
  - Error number: [MY-012948](#); Symbol: [ER\\_IB\\_MSG\\_1123](#); SQLSTATE: [HY000](#)  
Message: Compressed tables use zlib %s  
[ER\\_IB\\_MSG\\_1123](#) was added in 8.0.11.
  - Error number: [MY-012949](#); Symbol: [ER\\_IB\\_MSG\\_1124](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1124](#) was added in 8.0.11.
  - Error number: [MY-012950](#); Symbol: [ER\\_IB\\_MSG\\_1125](#); SQLSTATE: [HY000](#)  
Message: Startup called second time during the process lifetime. In the MySQL Embedded Server Library you cannot call `server_init()` more than once during the process lifetime.

- 
- [ER\\_IB\\_MSG\\_1125](#) was added in 8.0.11.
- Error number: [MY-012951](#); Symbol: [ER\\_IB\\_MSG\\_1126](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1126](#) was added in 8.0.11.
  - Error number: [MY-012952](#); Symbol: [ER\\_IB\\_MSG\\_1127](#); SQLSTATE: [HY000](#)  
Message: Unable to create monitor file %s: %s  
[ER\\_IB\\_MSG\\_1127](#) was added in 8.0.11.
  - Error number: [MY-012953](#); Symbol: [ER\\_IB\\_MSG\\_1128](#); SQLSTATE: [HY000](#)  
Message: Disabling background ibuf IO read threads.  
[ER\\_IB\\_MSG\\_1128](#) was added in 8.0.11.
  - Error number: [MY-012954](#); Symbol: [ER\\_IB\\_MSG\\_1129](#); SQLSTATE: [HY000](#)  
Message: Cannot initialize AIO sub-system  
[ER\\_IB\\_MSG\\_1129](#) was added in 8.0.11.
  - Error number: [MY-012955](#); Symbol: [ER\\_IB\\_MSG\\_1130](#); SQLSTATE: [HY000](#)  
Message: Initializing buffer pool, total size = %lf%c, instances = %lu, chunk size =%lf%c  
[ER\\_IB\\_MSG\\_1130](#) was added in 8.0.11.
  - Error number: [MY-012956](#); Symbol: [ER\\_IB\\_MSG\\_1131](#); SQLSTATE: [HY000](#)  
Message: Cannot allocate memory for the buffer pool  
[ER\\_IB\\_MSG\\_1131](#) was added in 8.0.11.
  - Error number: [MY-012957](#); Symbol: [ER\\_IB\\_MSG\\_1132](#); SQLSTATE: [HY000](#)  
Message: Completed initialization of buffer pool  
[ER\\_IB\\_MSG\\_1132](#) was added in 8.0.11.
  - Error number: [MY-012958](#); Symbol: [ER\\_IB\\_MSG\\_1133](#); SQLSTATE: [HY000](#)  
Message: Small buffer pool size (%lluM), the flst\_validate() debug function can cause a deadlock if the buffer pool fills up.  
[ER\\_IB\\_MSG\\_1133](#) was added in 8.0.11.
  - Error number: [MY-012959](#); Symbol: [ER\\_IB\\_MSG\\_1134](#); SQLSTATE: [HY000](#)  
Message: Could not open or create the system tablespace. If you tried to add new data files to the system tablespace, and it failed here, you should now edit innodb\_data\_file\_path in my.cnf back to what it was, and remove the new ibdata files InnoDB created in this failed attempt. InnoDB only wrote those files full of zeros, but did not yet use them in any way. But be careful: do not remove old data files which contain your precious data!

---

`ER_IB_MSG_1134` was added in 8.0.11.

- Error number: `MY-012960`; Symbol: `ER_IB_MSG_1135`; SQLSTATE: `HY000`

Message: Cannot create log files because data files are corrupt or the database was not shut down cleanly after creating the data files.

`ER_IB_MSG_1135` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012960`; Symbol: `ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORRUPTED`; SQLSTATE: `HY000`

Message: Cannot create redo log files because data files are corrupt or the database was not shut down cleanly after creating the data files.

`ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORRUPTED` was added in 8.0.30.

- Error number: `MY-012961`; Symbol: `ER_IB_MSG_1136`; SQLSTATE: `HY000`

Message: Only one log file found

`ER_IB_MSG_1136` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012961`; Symbol: `ER_IB_MSG_LOG_FILES_INVALID_SET`; SQLSTATE: `HY000`

Message: Only one redo log file found

`ER_IB_MSG_LOG_FILES_INVALID_SET` was added in 8.0.30.

- Error number: `MY-012962`; Symbol: `ER_IB_MSG_1137`; SQLSTATE: `HY000`

Message: Log file %s size %llu is not a multiple of innodb\_page\_size

`ER_IB_MSG_1137` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012962`; Symbol: `ER_IB_MSG_LOG_FILE_SIZE_INVALID`; SQLSTATE: `HY000`

Message: The redo log file %s size %llu is not a multiple of innodb\_page\_size

`ER_IB_MSG_LOG_FILE_SIZE_INVALID` was added in 8.0.30.

- Error number: `MY-012963`; Symbol: `ER_IB_MSG_1138`; SQLSTATE: `HY000`

Message: Log file %s is of different size %llu bytes than other log files %llu bytes!

`ER_IB_MSG_1138` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012963`; Symbol: `ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES`; SQLSTATE: `HY000`

Message: The redo log file %s is of different size %llu bytes than other log files %llu bytes!

`ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES` was added in 8.0.30.

- Error number: `MY-012964`; Symbol: `ER_IB_MSG_1139`; SQLSTATE: `HY000`

Message: Use `--innodb-directories` to find the tablespace files. If that fails then use `--innodb-force-recovery=1` to ignore this and to permanently lose all changes to the missing tablespace(s)

---

[ER\\_IB\\_MSG\\_1139](#) was added in 8.0.11.

- Error number: [MY-012965](#); Symbol: [ER\\_IB\\_MSG\\_1140](#); SQLSTATE: [HY000](#)

Message: The log file may have been corrupt and it is possible that the log scan or parsing did not proceed far enough in recovery. Please run CHECK TABLE on your InnoDB tables to check that they are ok! It may be safest to recover your InnoDB database from a backup!

[ER\\_IB\\_MSG\\_1140](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012965](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_CORRUPT](#); SQLSTATE: [HY000](#)

Message: The redo log file may have been corrupt and it is possible that the log scan or parsing did not proceed far enough in recovery. Please run CHECK TABLE on your InnoDB tables to check that they are ok! It may be safest to recover your InnoDB database from a backup!

[ER\\_IB\\_MSG\\_RECOVERY\\_CORRUPT](#) was added in 8.0.30.

- Error number: [MY-012966](#); Symbol: [ER\\_IB\\_MSG\\_1141](#); SQLSTATE: [HY000](#)

Message: Cannot resize log files in read-only mode.

[ER\\_IB\\_MSG\\_1141](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012966](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_RESIZE\\_ON\\_START\\_IN\\_READ\\_ONLY\\_MODE](#); SQLSTATE: [HY000](#)

Message: Cannot resize redo log files in read-only mode. Provide --innodb\_redo\_log\_capacity >= %lluMB or start without --innodb-read-only.

[ER\\_IB\\_MSG\\_LOG\\_FILES\\_RESIZE\\_ON\\_START\\_IN\\_READ\\_ONLY\\_MODE](#) was added in 8.0.30, removed after 8.0.32.

- Error number: [MY-012967](#); Symbol: [ER\\_IB\\_MSG\\_1142](#); SQLSTATE: [HY000](#)

Message: Cannot open DD tablespace.

[ER\\_IB\\_MSG\\_1142](#) was added in 8.0.11.

- Error number: [MY-012968](#); Symbol: [ER\\_IB\\_MSG\\_1143](#); SQLSTATE: [HY000](#)

Message: Starting to delete and rewrite log files.

[ER\\_IB\\_MSG\\_1143](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012968](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_REWRITING](#); SQLSTATE: [HY000](#)

Message: Starting to delete and rewrite redo log files.

[ER\\_IB\\_MSG\\_LOG\\_FILES\\_REWRITING](#) was added in 8.0.30.

- Error number: [MY-012969](#); Symbol: [ER\\_IB\\_MSG\\_1144](#); SQLSTATE: [HY000](#)

Message: Undo from 5.7 found. It will be purged

[ER\\_IB\\_MSG\\_1144](#) was added in 8.0.11.

- Error number: [MY-012970](#); Symbol: [ER\\_IB\\_MSG\\_1145](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_1145](#) was added in 8.0.11.

- Error number: [MY-012971](#); Symbol: [ER\\_IB\\_MSG\\_1146](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1146](#) was added in 8.0.11.

- Error number: [MY-012972](#); Symbol: [ER\\_IB\\_MSG\\_1147](#); SQLSTATE: [HY000](#)

Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is %lu pages

[ER\\_IB\\_MSG\\_1147](#) was added in 8.0.11.

- Error number: [MY-012973](#); Symbol: [ER\\_IB\\_MSG\\_1148](#); SQLSTATE: [HY000](#)

Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited `innodb_data_file_path` in `my.cnf` in an inappropriate way, removing `ibdata` files from there? You can set `innodb_force_recovery=1` in `my.cnf` to force a startup if you are trying to recover a badly corrupt database.

[ER\\_IB\\_MSG\\_1148](#) was added in 8.0.11.

- Error number: [MY-012974](#); Symbol: [ER\\_IB\\_MSG\\_1149](#); SQLSTATE: [HY000](#)

Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is only %lu pages

[ER\\_IB\\_MSG\\_1149](#) was added in 8.0.11.

- Error number: [MY-012975](#); Symbol: [ER\\_IB\\_MSG\\_1150](#); SQLSTATE: [HY000](#)

Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited `innodb_data_file_path` in `my.cnf` in an InnoDB: inappropriate way, removing `ibdata` files from there? You can set `innodb_force_recovery=1` in `my.cnf` to force InnoDB: a startup if you are trying to recover a badly corrupt database.

[ER\\_IB\\_MSG\\_1150](#) was added in 8.0.11.

- Error number: [MY-012976](#); Symbol: [ER\\_IB\\_MSG\\_1151](#); SQLSTATE: [HY000](#)

Message: %s started; log sequence number %llu

[ER\\_IB\\_MSG\\_1151](#) was added in 8.0.11.

- Error number: [MY-012977](#); Symbol: [ER\\_IB\\_MSG\\_1152](#); SQLSTATE: [HY000](#)

Message: Waiting for purge to complete

[ER\\_IB\\_MSG\\_1152](#) was added in 8.0.11.

- Error number: [MY-012978](#); Symbol: [ER\\_IB\\_MSG\\_1153](#); SQLSTATE: [HY000](#)

Message: Waiting for `dict_stats_thread` to exit

[ER\\_IB\\_MSG\\_1153](#) was added in 8.0.11, removed after 8.0.20.

- 
- Error number: [MY-012979](#); Symbol: [ER\\_IB\\_MSG\\_1154](#); SQLSTATE: [HY000](#)  
Message: Query counter shows %lld queries still inside InnoDB at shutdown  
[ER\\_IB\\_MSG\\_1154](#) was added in 8.0.11.
  - Error number: [MY-012980](#); Symbol: [ER\\_IB\\_MSG\\_1155](#); SQLSTATE: [HY000](#)  
Message: Shutdown completed; log sequence number %llu  
[ER\\_IB\\_MSG\\_1155](#) was added in 8.0.11.
  - Error number: [MY-012981](#); Symbol: [ER\\_IB\\_MSG\\_1156](#); SQLSTATE: [HY000](#)  
Message: Cannot continue operation.  
[ER\\_IB\\_MSG\\_1156](#) was added in 8.0.11.
  - Error number: [MY-012982](#); Symbol: [ER\\_IB\\_MSG\\_1157](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1157](#) was added in 8.0.11.
  - Error number: [MY-012983](#); Symbol: [ER\\_IB\\_MSG\\_1158](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1158](#) was added in 8.0.11.
  - Error number: [MY-012984](#); Symbol: [ER\\_IB\\_MSG\\_1159](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1159](#) was added in 8.0.11.
  - Error number: [MY-012985](#); Symbol: [ER\\_IB\\_MSG\\_1160](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1160](#) was added in 8.0.11.
  - Error number: [MY-012986](#); Symbol: [ER\\_IB\\_MSG\\_1161](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1161](#) was added in 8.0.11.
  - Error number: [MY-012987](#); Symbol: [ER\\_IB\\_MSG\\_1162](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1162](#) was added in 8.0.11.
  - Error number: [MY-012988](#); Symbol: [ER\\_IB\\_MSG\\_1163](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1163](#) was added in 8.0.11.

- 
- Error number: [MY-012989](#); Symbol: [ER\\_IB\\_MSG\\_1164](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1164](#) was added in 8.0.11.
  - Error number: [MY-012990](#); Symbol: [ER\\_IB\\_MSG\\_1165](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1165](#) was added in 8.0.11.
  - Error number: [MY-012991](#); Symbol: [ER\\_IB\\_MSG\\_1166](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1166](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012991](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_FAIL\\_TO\\_READ\\_LOG\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Unable to read the existing undo truncate log file '%s'. The error is %s  
[ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_FAIL\\_TO\\_READ\\_LOG\\_FILE](#) was added in 8.0.21.
  - Error number: [MY-012992](#); Symbol: [ER\\_IB\\_MSG\\_1167](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1167](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012992](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_MARKED\\_FOR\\_TRUNCATE](#); SQLSTATE: [HY000](#)  
Message: Undo tablespace %s is marked for truncate  
[ER\\_IB\\_MSG\\_UNDO\\_MARKED\\_FOR\\_TRUNCATE](#) was added in 8.0.21.
  - Error number: [MY-012993](#); Symbol: [ER\\_IB\\_MSG\\_1168](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1168](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012994](#); Symbol: [ER\\_IB\\_MSG\\_1169](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1169](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012994](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_START](#); SQLSTATE: [HY000](#)  
Message: Truncating UNDO tablespace %s  
[ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_START](#) was added in 8.0.21.
  - Error number: [MY-012995](#); Symbol: [ER\\_IB\\_MSG\\_1170](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1170](#) was added in 8.0.11, removed after 8.0.20.

- 
- Error number: [MY-012996](#); Symbol: [ER\\_IB\\_MSG\\_1171](#); SQLSTATE: [HY000](#)  
Message: Cannot create truncate log for undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_1171](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012996](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_LOG\\_CREATE](#); SQLSTATE: [HY000](#)  
Message: Cannot create truncate log for undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_LOG\\_CREATE](#) was added in 8.0.21.
  - Error number: [MY-012997](#); Symbol: [ER\\_IB\\_MSG\\_1172](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1172](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012998](#); Symbol: [ER\\_IB\\_MSG\\_1173](#); SQLSTATE: [HY000](#)  
Message: Failed to truncate undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_1173](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-012998](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Failed to truncate undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_FAILURE](#) was added in 8.0.21.
  - Error number: [MY-012999](#); Symbol: [ER\\_IB\\_MSG\\_1174](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1174](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-013000](#); Symbol: [ER\\_IB\\_MSG\\_1175](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1175](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-013000](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_COMPLETE](#); SQLSTATE: [HY000](#)  
Message: Completed truncate of undo tablespace %s.  
[ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_COMPLETE](#) was added in 8.0.21.
  - Error number: [MY-013001](#); Symbol: [ER\\_IB\\_MSG\\_1176](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1176](#) was added in 8.0.11, removed after 8.0.20.
  - Error number: [MY-013002](#); Symbol: [ER\\_IB\\_MSG\\_1177](#); SQLSTATE: [HY000](#)  
Message: %s



---

[ER\\_IB\\_MSG\\_1177](#) was added in 8.0.11.

- Error number: [MY-013003](#); Symbol: [ER\\_IB\\_MSG\\_1178](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1178](#) was added in 8.0.11.

- Error number: [MY-013004](#); Symbol: [ER\\_IB\\_MSG\\_1179](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1179](#) was added in 8.0.11.

- Error number: [MY-013005](#); Symbol: [ER\\_IB\\_MSG\\_1180](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1180](#) was added in 8.0.11.

- Error number: [MY-013006](#); Symbol: [ER\\_IB\\_MSG\\_1181](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1181](#) was added in 8.0.11.

- Error number: [MY-013007](#); Symbol: [ER\\_IB\\_MSG\\_1182](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1182](#) was added in 8.0.11.

- Error number: [MY-013008](#); Symbol: [ER\\_IB\\_MSG\\_1183](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1183](#) was added in 8.0.11.

- Error number: [MY-013009](#); Symbol: [ER\\_IB\\_MSG\\_1184](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1184](#) was added in 8.0.11.

- Error number: [MY-013010](#); Symbol: [ER\\_IB\\_MSG\\_1185](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1185](#) was added in 8.0.11.

- Error number: [MY-013011](#); Symbol: [ER\\_IB\\_MSG\\_1186](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1186](#) was added in 8.0.11.

- Error number: [MY-013012](#); Symbol: [ER\\_IB\\_MSG\\_1187](#); SQLSTATE: [HY000](#)

Message: %s

---

`ER_IB_MSG_1187` was added in 8.0.11.

- Error number: `MY-013013`; Symbol: `ER_IB_MSG_1188`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1188` was added in 8.0.11.

- Error number: `MY-013014`; Symbol: `ER_IB_MSG_1189`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1189` was added in 8.0.11.

- Error number: `MY-013015`; Symbol: `ER_IB_MSG_1190`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1190` was added in 8.0.11, removed after 8.0.20.

- Error number: `MY-013015`; Symbol: `ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED`; SQLSTATE: `HY000`

Message: Rollback of non-prepared transactions completed

`ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED` was added in 8.0.21.

- Error number: `MY-013016`; Symbol: `ER_IB_MSG_1191`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1191` was added in 8.0.11.

- Error number: `MY-013017`; Symbol: `ER_IB_MSG_1192`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1192` was added in 8.0.11.

- Error number: `MY-013018`; Symbol: `ER_IB_MSG_1193`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1193` was added in 8.0.11.

- Error number: `MY-013019`; Symbol: `ER_IB_MSG_1194`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1194` was added in 8.0.11.

- Error number: `MY-013020`; Symbol: `ER_IB_MSG_1195`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1195` was added in 8.0.11.

- Error number: `MY-013021`; Symbol: `ER_IB_MSG_1196`; SQLSTATE: `HY000`

---

Message: %s

[ER\\_IB\\_MSG\\_1196](#) was added in 8.0.11.

- Error number: [MY-013022](#); Symbol: [ER\\_IB\\_MSG\\_1197](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1197](#) was added in 8.0.11.

- Error number: [MY-013023](#); Symbol: [ER\\_IB\\_MSG\\_1198](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1198](#) was added in 8.0.11.

- Error number: [MY-013024](#); Symbol: [ER\\_IB\\_MSG\\_1199](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1199](#) was added in 8.0.11.

- Error number: [MY-013025](#); Symbol: [ER\\_IB\\_MSG\\_1200](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1200](#) was added in 8.0.11.

- Error number: [MY-013026](#); Symbol: [ER\\_IB\\_MSG\\_1201](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1201](#) was added in 8.0.11.

- Error number: [MY-013027](#); Symbol: [ER\\_IB\\_MSG\\_1202](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1202](#) was added in 8.0.11.

- Error number: [MY-013028](#); Symbol: [ER\\_IB\\_MSG\\_1203](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1203](#) was added in 8.0.11.

- Error number: [MY-013029](#); Symbol: [ER\\_IB\\_MSG\\_1204](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1204](#) was added in 8.0.11.

- Error number: [MY-013030](#); Symbol: [ER\\_IB\\_MSG\\_1205](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1205](#) was added in 8.0.11.

- Error number: [MY-013031](#); Symbol: [ER\\_IB\\_MSG\\_1206](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_1206](#) was added in 8.0.11.

- Error number: [MY-013032](#); Symbol: [ER\\_IB\\_MSG\\_1207](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1207](#) was added in 8.0.11.

- Error number: [MY-013033](#); Symbol: [ER\\_IB\\_MSG\\_1208](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1208](#) was added in 8.0.11.

- Error number: [MY-013034](#); Symbol: [ER\\_IB\\_MSG\\_1209](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1209](#) was added in 8.0.11.

- Error number: [MY-013035](#); Symbol: [ER\\_IB\\_MSG\\_1210](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1210](#) was added in 8.0.11.

- Error number: [MY-013036](#); Symbol: [ER\\_IB\\_MSG\\_1211](#); SQLSTATE: [HY000](#)

Message: Blocked High Priority Transaction (ID %llu, Thread ID %s) killed the blocking transaction (ID %llu - %s) by rolling it back.

[ER\\_IB\\_MSG\\_1211](#) was added in 8.0.11.

- Error number: [MY-013037](#); Symbol: [ER\\_IB\\_MSG\\_1212](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1212](#) was added in 8.0.11.

- Error number: [MY-013038](#); Symbol: [ER\\_IB\\_MSG\\_1213](#); SQLSTATE: [HY000](#)

Message: gettimeofday() failed: %s

[ER\\_IB\\_MSG\\_1213](#) was added in 8.0.11.

- Error number: [MY-013039](#); Symbol: [ER\\_IB\\_MSG\\_1214](#); SQLSTATE: [HY000](#)

Message: Can't create UNDO tablespace %s %s

[ER\\_IB\\_MSG\\_1214](#) was added in 8.0.11.

- Error number: [MY-013040](#); Symbol: [ER\\_IB\\_MSG\\_1215](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1215](#) was added in 8.0.11.

- 
- Error number: [MY-013041](#); Symbol: [ER\\_IB\\_MSG\\_1216](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1216](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-013041](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_RESIZE\\_ON\\_START](#); SQLSTATE: [HY000](#)  
Message: Resizing redo log from %lluM to %lluM (LSN=%llu) synchronously. If this takes too long, consider starting the server with large --innodb\_redo\_log\_capacity, and resizing the redo log online using SET.  
[ER\\_IB\\_MSG\\_LOG\\_FILES\\_RESIZE\\_ON\\_START](#) was added in 8.0.30.
  - Error number: [MY-013042](#); Symbol: [ER\\_IB\\_MSG\\_1217](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1217](#) was added in 8.0.11.
  - Error number: [MY-013043](#); Symbol: [ER\\_IB\\_MSG\\_1218](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1218](#) was added in 8.0.11.
  - Error number: [MY-013044](#); Symbol: [ER\\_IB\\_MSG\\_1219](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1219](#) was added in 8.0.11.
  - Error number: [MY-013045](#); Symbol: [ER\\_IB\\_MSG\\_1220](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1220](#) was added in 8.0.11.
  - Error number: [MY-013046](#); Symbol: [ER\\_IB\\_MSG\\_1221](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1221](#) was added in 8.0.11.
  - Error number: [MY-013047](#); Symbol: [ER\\_IB\\_MSG\\_1222](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1222](#) was added in 8.0.11.
  - Error number: [MY-013048](#); Symbol: [ER\\_IB\\_MSG\\_1223](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1223](#) was added in 8.0.11.
  - Error number: [MY-013049](#); Symbol: [ER\\_IB\\_MSG\\_1224](#); SQLSTATE: [HY000](#)  
Message: %s

---

[ER\\_IB\\_MSG\\_1224](#) was added in 8.0.11.

- Error number: [MY-013050](#); Symbol: [ER\\_IB\\_MSG\\_1225](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1225](#) was added in 8.0.11.

- Error number: [MY-013051](#); Symbol: [ER\\_IB\\_MSG\\_1226](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1226](#) was added in 8.0.11.

- Error number: [MY-013052](#); Symbol: [ER\\_IB\\_MSG\\_1227](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1227](#) was added in 8.0.11.

- Error number: [MY-013053](#); Symbol: [ER\\_IB\\_MSG\\_1228](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1228](#) was added in 8.0.11.

- Error number: [MY-013054](#); Symbol: [ER\\_IB\\_MSG\\_1229](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1229](#) was added in 8.0.11.

- Error number: [MY-013055](#); Symbol: [ER\\_IB\\_MSG\\_1230](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1230](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-013056](#); Symbol: [ER\\_IB\\_MSG\\_1231](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1231](#) was added in 8.0.11.

- Error number: [MY-013057](#); Symbol: [ER\\_IB\\_MSG\\_1232](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1232](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-013058](#); Symbol: [ER\\_IB\\_MSG\\_1233](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1233](#) was added in 8.0.11.

- Error number: [MY-013059](#); Symbol: [ER\\_IB\\_MSG\\_1234](#); SQLSTATE: [HY000](#)

Message: %s

---

`ER_IB_MSG_1234` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-013059`; Symbol: `ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE`; SQLSTATE: `HY000`

Message: Out of space in the redo log. Checkpoint LSN: %llu. Consider increasing `innodb_redo_log_capacity`.

`ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE` was added in 8.0.30.

- Error number: `MY-013060`; Symbol: `ER_IB_MSG_1235`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1235` was added in 8.0.11.

- Error number: `MY-013061`; Symbol: `ER_IB_MSG_1236`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1236` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-013061`; Symbol: `ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER`; SQLSTATE: `HY000`

Message: Log writer waited too long for redo-archiver to advance (1 second). There are unarchived: %llu bytes. Archiver LSN: %llu. Aborted the redo-archiver. Consider increasing `innodb_redo_log_capacity`.

`ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER` was added in 8.0.30.

- Error number: `MY-013062`; Symbol: `ER_IB_MSG_1237`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1237` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-013062`; Symbol: `ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER`; SQLSTATE: `HY000`

Message: Log writer is waiting for redo-archiver to catch up unarchived: %llu bytes. Archiver LSN: %llu. Consider increasing `innodb_redo_log_capacity`.

`ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER` was added in 8.0.30.

- Error number: `MY-013063`; Symbol: `ER_IB_MSG_1238`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1238` was added in 8.0.11.

- Error number: `MY-013064`; Symbol: `ER_IB_MSG_1239`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1239` was added in 8.0.11.

- Error number: `MY-013065`; Symbol: `ER_IB_MSG_1240`; SQLSTATE: `HY000`

Message: %s

- 
- [ER\\_IB\\_MSG\\_1240](#) was added in 8.0.11, removed after 8.0.29.
- Error number: [MY-013066](#); Symbol: [ER\\_IB\\_MSG\\_1241](#); SQLSTATE: [HY000](#)  
Message: %s
- [ER\\_IB\\_MSG\\_1241](#) was added in 8.0.11.
- Error number: [MY-013067](#); Symbol: [ER\\_IB\\_MSG\\_1242](#); SQLSTATE: [HY000](#)  
Message: Can't set redo log tablespace to be encrypted in read-only mode.
- [ER\\_IB\\_MSG\\_1242](#) was added in 8.0.11, removed after 8.0.29.
- Error number: [MY-013067](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_CANNOT\\_ENCRYPT\\_IN\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)  
Message: Can't set redo log files to be encrypted in read-only mode.
- [ER\\_IB\\_MSG\\_LOG\\_FILES\\_CANNOT\\_ENCRYPT\\_IN\\_READ\\_ONLY](#) was added in 8.0.30.
- Error number: [MY-013068](#); Symbol: [ER\\_IB\\_MSG\\_1243](#); SQLSTATE: [HY000](#)  
Message: Can't set redo log tablespace to be encrypted.
- [ER\\_IB\\_MSG\\_1243](#) was added in 8.0.11, removed after 8.0.29.
- Error number: [MY-013068](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_ENCRYPTION\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Can't set redo log files to be encrypted.
- [ER\\_IB\\_MSG\\_LOG\\_FILES\\_ENCRYPTION\\_INIT\\_FAILED](#) was added in 8.0.30.
- Error number: [MY-013069](#); Symbol: [ER\\_IB\\_MSG\\_1244](#); SQLSTATE: [HY000](#)  
Message: Can't set redo log tablespace to be encrypted.
- [ER\\_IB\\_MSG\\_1244](#) was added in 8.0.11, removed after 8.0.29.
- Error number: [MY-013070](#); Symbol: [ER\\_IB\\_MSG\\_1245](#); SQLSTATE: [HY000](#)  
Message: Redo log encryption is enabled.
- [ER\\_IB\\_MSG\\_1245](#) was added in 8.0.11.
- Error number: [MY-013071](#); Symbol: [ER\\_IB\\_MSG\\_1246](#); SQLSTATE: [HY000](#)  
Message: Waiting for archiver to finish archiving page and log
- [ER\\_IB\\_MSG\\_1246](#) was added in 8.0.11.
- Error number: [MY-013072](#); Symbol: [ER\\_IB\\_MSG\\_1247](#); SQLSTATE: [HY000](#)  
Message: Starting shutdown...
- [ER\\_IB\\_MSG\\_1247](#) was added in 8.0.11.
- Error number: [MY-013073](#); Symbol: [ER\\_IB\\_MSG\\_1248](#); SQLSTATE: [HY000](#)



---

Message: Waiting for %s to exit.

[ER\\_IB\\_MSG\\_1248](#) was added in 8.0.11.

- Error number: [MY-013074](#); Symbol: [ER\\_IB\\_MSG\\_1249](#); SQLSTATE: [HY000](#)

Message: Waiting for rollback of %zu recovered transactions, before shutdown.

[ER\\_IB\\_MSG\\_1249](#) was added in 8.0.11.

- Error number: [MY-013075](#); Symbol: [ER\\_IB\\_MSG\\_1250](#); SQLSTATE: [HY000](#)

Message: Waiting for master thread to be suspended.

[ER\\_IB\\_MSG\\_1250](#) was added in 8.0.11.

- Error number: [MY-013076](#); Symbol: [ER\\_IB\\_MSG\\_1251](#); SQLSTATE: [HY000](#)

Message: Waiting for page\_cleaner to finish flushing of buffer pool.

[ER\\_IB\\_MSG\\_1251](#) was added in 8.0.11.

- Error number: [MY-013077](#); Symbol: [ER\\_IB\\_MSG\\_1252](#); SQLSTATE: [HY000](#)

Message: Waiting for %lu buffer page I/Os to complete.

[ER\\_IB\\_MSG\\_1252](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-013077](#); Symbol: [ER\\_IB\\_MSG\\_BUF\\_PENDING\\_IO\\_ON\\_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Shutdown is waiting for %zu buffer page I/Os to complete.

[ER\\_IB\\_MSG\\_BUF\\_PENDING\\_IO\\_ON\\_SHUTDOWN](#) was added in 8.0.30.

- Error number: [MY-013078](#); Symbol: [ER\\_IB\\_MSG\\_1253](#); SQLSTATE: [HY000](#)

Message: MySQL has requested a very fast shutdown without flushing the InnoDB buffer pool to data files. At the next mysqld startup InnoDB will do a crash recovery!

[ER\\_IB\\_MSG\\_1253](#) was added in 8.0.11.

- Error number: [MY-013079](#); Symbol: [ER\\_IB\\_MSG\\_1254](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1254](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-013080](#); Symbol: [ER\\_IB\\_MSG\\_1255](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1255](#) was added in 8.0.11.

- Error number: [MY-013081](#); Symbol: [ER\\_IB\\_MSG\\_1256](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1256](#) was added in 8.0.11.

- 
- Error number: [MY-013082](#); Symbol: [ER\\_IB\\_MSG\\_1257](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1257](#) was added in 8.0.11.
  - Error number: [MY-013083](#); Symbol: [ER\\_IB\\_MSG\\_1258](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1258](#) was added in 8.0.11.
  - Error number: [MY-013084](#); Symbol: [ER\\_IB\\_MSG\\_1259](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1259](#) was added in 8.0.11.
  - Error number: [MY-013085](#); Symbol: [ER\\_IB\\_MSG\\_1260](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1260](#) was added in 8.0.11.
  - Error number: [MY-013086](#); Symbol: [ER\\_IB\\_MSG\\_1261](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1261](#) was added in 8.0.11.
  - Error number: [MY-013087](#); Symbol: [ER\\_IB\\_MSG\\_1262](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1262](#) was added in 8.0.11.
  - Error number: [MY-013088](#); Symbol: [ER\\_IB\\_MSG\\_1263](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1263](#) was added in 8.0.11.
  - Error number: [MY-013089](#); Symbol: [ER\\_IB\\_MSG\\_1264](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1264](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-013089](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_HEADER\\_INVALID\\_CHECKSUM](#); SQLSTATE: [HY000](#)  
Message: Invalid redo log header checksum.  
[ER\\_IB\\_MSG\\_LOG\\_FILE\\_HEADER\\_INVALID\\_CHECKSUM](#) was added in 8.0.30.
  - Error number: [MY-013090](#); Symbol: [ER\\_IB\\_MSG\\_1265](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1265](#) was added in 8.0.11, removed after 8.0.29.

- 
- Error number: [MY-013090](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_BEFORE\\_5\\_7\\_9](#); SQLSTATE: [HY000](#)  
Message: Unsupported redo log format (v%lu). The redo log was created before MySQL 5.7.9  
[ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_BEFORE\\_5\\_7\\_9](#) was added in 8.0.30.
  - Error number: [MY-013091](#); Symbol: [ER\\_IB\\_MSG\\_1266](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1266](#) was added in 8.0.11.
  - Error number: [MY-013092](#); Symbol: [ER\\_IB\\_MSG\\_1267](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1267](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-013092](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_CONCURRENCY\\_MARGIN\\_UNSAFE](#); SQLSTATE: [HY000](#)  
Message: Cannot continue operation. The innodb\_redo\_log\_capacity=%lluM is too small for the innodb\_thread\_concurrency=%lu. The capacity of redo should be >= %lluM. To get mysqld running, set innodb\_thread\_concurrency to a smaller value or increase innodb\_redo\_log\_capacity. %s  
[ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_CONCURRENCY\\_MARGIN\\_UNSAFE](#) was added in 8.0.30.
  - Error number: [MY-013093](#); Symbol: [ER\\_IB\\_MSG\\_1268](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1268](#) was added in 8.0.11.
  - Error number: [MY-013094](#); Symbol: [ER\\_IB\\_MSG\\_1269](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1269](#) was added in 8.0.11.
  - Error number: [MY-013095](#); Symbol: [ER\\_IB\\_MSG\\_1270](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_1270](#) was added in 8.0.11, removed after 8.0.29.
  - Error number: [MY-013095](#); Symbol: [ER\\_IB\\_MSG\\_THREAD\\_CONCURRENCY\\_CHANGED](#); SQLSTATE: [HY000](#)  
Message: User has set innodb\_thread\_concurrency to %lu.  
[ER\\_IB\\_MSG\\_THREAD\\_CONCURRENCY\\_CHANGED](#) was added in 8.0.30.
  - Error number: [MY-013096](#); Symbol: [ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_STOP\\_CMD\\_EXEC\\_TIMEOUT](#); SQLSTATE: [HY000](#)  
Message: STOP SLAVE command execution is incomplete: Slave SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.  
[ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_STOP\\_CMD\\_EXEC\\_TIMEOUT](#) was added in 8.0.11, removed after 8.0.32.

- 
- Error number: `MY-013096`; Symbol: `ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT`; SQLSTATE: `HY000`

Message: STOP REPLICA command execution is incomplete: Replica SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.

`ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT` was added in 8.0.33.

- Error number: `MY-013097`; Symbol: `ER_RPL_SLAVE_IO_THREAD_STOP_CMD_EXEC_TIMEOUT`; SQLSTATE: `HY000`

Message: STOP SLAVE command execution is incomplete: Slave IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.

`ER_RPL_SLAVE_IO_THREAD_STOP_CMD_EXEC_TIMEOUT` was added in 8.0.11, removed after 8.0.32.

- Error number: `MY-013097`; Symbol: `ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEOUT`; SQLSTATE: `HY000`

Message: STOP REPLICA command execution is incomplete: Replica IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.

`ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEOUT` was added in 8.0.33.

- Error number: `MY-013098`; Symbol: `ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE`; SQLSTATE: `HY000`

Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.

`ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE` was added in 8.0.11.

- Error number: `MY-013099`; Symbol: `ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT`; SQLSTATE: `HY000`

Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.

`ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT` was added in 8.0.11.

- Error number: `MY-013100`; Symbol: `ER_RPL_GTID_UNSAFE_STMT_ON_TEMPORARY_TABLE`; SQLSTATE: `HY000`

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE can only be executed outside transactional context. These statements are also not allowed in a function or trigger because functions and triggers are also considered to be multi-statement transactions.

`ER_RPL_GTID_UNSAFE_STMT_ON_TEMPORARY_TABLE` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-013101`; Symbol: `ER_BINLOG_ROW_VALUE_OPTION_IGNORED`; SQLSTATE: `HY000`

Message: When %s, the option `binlog_row_value_options=%s` will be ignored and updates will be written in full format to binary log.

`ER_BINLOG_ROW_VALUE_OPTION_IGNORED` was added in 8.0.11.

- 
- Error number: `MY-013102`; Symbol: `ER_BINLOG_USE_V1_ROW_EVENTS_IGNORED`; SQLSTATE: `HY000`  
Message: When %s, the option `log_bin_use_v1_row_events=1` will be ignored and row events will be written in new format to binary log.  
`ER_BINLOG_USE_V1_ROW_EVENTS_IGNORED` was added in 8.0.11.
  - Error number: `MY-013103`; Symbol: `ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFTER_IMAGES`; SQLSTATE: `HY000`  
Message: When %s, the option `binlog_row_value_options=%s` will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to `binlog_row_value_options` is limited to less than 50%%.  
`ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFTER_IMAGES` was added in 8.0.11.
  - Error number: `MY-013104`; Symbol: `ER_CONNECTION_ABORTED`; SQLSTATE: `HY000`  
Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).  
`ER_CONNECTION_ABORTED` was added in 8.0.11.
  - Error number: `MY-013105`; Symbol: `ER_NORMAL_SERVER_SHUTDOWN`; SQLSTATE: `HY000`  
Message: %s: Normal shutdown.  
`ER_NORMAL_SERVER_SHUTDOWN` was added in 8.0.11.
  - Error number: `MY-013106`; Symbol: `ER_KEYRING_MIGRATE_FAILED`; SQLSTATE: `HY000`  
Message: Can not perform keyring migration : %s.  
`ER_KEYRING_MIGRATE_FAILED` was added in 8.0.11.
  - Error number: `MY-013107`; Symbol: `ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GRP`; SQLSTATE: `HY000`  
Message: The member is configured with a `lower_case_table_names` option value '%u' different from the group '%u'. The member will now exit the group. If there is existing data on member, it may be incompatible with group if it was created with a `lower_case_table_names` value different from the group.  
`ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GRP` was added in 8.0.11.
  - Error number: `MY-013108`; Symbol: `ER_OOM_SAVE_GTIDS`; SQLSTATE: `HY000`  
Message: An out-of-memory error occurred while saving the set of GTIDs from the last binary log into the `mysql.gtid_executed` table  
`ER_OOM_SAVE_GTIDS` was added in 8.0.11.
  - Error number: `MY-013109`; Symbol: `ER_LCTN_NOT_FOUND`; SQLSTATE: `HY000`  
Message: The `lower_case_table_names` setting for the data dictionary was not found. Starting the server using `lower_case_table_names = '%u'`.  
`ER_LCTN_NOT_FOUND` was added in 8.0.11.
  - Error number: `MY-013111`; Symbol: `ER_COMPONENT_FILTER_WRONG_VALUE`; SQLSTATE: `HY000`
-

---

Message: Variable '%s' can't be set to the value of '%s'

[ER\\_COMPONENT\\_FILTER\\_WRONG\\_VALUE](#) was added in 8.0.11.

- Error number: [MY-013112](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_STOP\\_SERVICES](#); SQLSTATE: [HY000](#)

Message: Stopping services failed with error "%s"

[ER\\_XPLUGIN\\_FAILED\\_TO\\_STOP\\_SERVICES](#) was added in 8.0.11.

- Error number: [MY-013113](#); Symbol: [ER\\_INCONSISTENT\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Query caused different errors on source and replica. Error on source: message (format)='%s' error code=%d; Error on replica:actual message='%s', error code=%d. Default database:'%s'. Query:'%s'

- Error number: [MY-013114](#); Symbol: [ER\\_SERVER\\_MASTER\\_FATAL\\_ERROR\\_READING\\_BINLOG](#); SQLSTATE: [HY000](#)

Message: Got fatal error %d from master when reading data from binary log: '%s'

[ER\\_SERVER\\_MASTER\\_FATAL\\_ERROR\\_READING\\_BINLOG](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-013114](#); Symbol: [ER\\_SERVER\\_SOURCE\\_FATAL\\_ERROR\\_READING\\_BINLOG](#); SQLSTATE: [HY000](#)

Message: Got fatal error %d from source when reading data from binary log: '%s'

[ER\\_SERVER\\_SOURCE\\_FATAL\\_ERROR\\_READING\\_BINLOG](#) was added in 8.0.33.

- Error number: [MY-013115](#); Symbol: [ER\\_NETWORK\\_READ\\_EVENT\\_CHECKSUM\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Replication event checksum verification failed while reading from network.

- Error number: [MY-013116](#); Symbol: [ER\\_SLAVE\\_CREATE\\_EVENT\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to create %s

[ER\\_SLAVE\\_CREATE\\_EVENT\\_FAILURE](#) was removed after 8.0.32.

- Error number: [MY-013116](#); Symbol: [ER\\_REPLICA\\_CREATE\\_EVENT\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to create %s

[ER\\_REPLICA\\_CREATE\\_EVENT\\_FAILURE](#) was added in 8.0.33.

- Error number: [MY-013117](#); Symbol: [ER\\_SLAVE\\_FATAL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error: %s

[ER\\_SLAVE\\_FATAL\\_ERROR](#) was removed after 8.0.32.

- Error number: [MY-013117](#); Symbol: [ER\\_REPLICA\\_FATAL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error: %s

[ER\\_REPLICA\\_FATAL\\_ERROR](#) was added in 8.0.33.

- Error number: [MY-013118](#); Symbol: [ER\\_SLAVE\\_HEARTBEAT\\_FAILURE](#); SQLSTATE: [HY000](#)

---

Message: Unexpected master's heartbeat data: %s

[ER\\_SLAVE\\_HEARTBEAT\\_FAILURE](#) was removed after 8.0.32.

- Error number: [MY-013118](#); Symbol: [ER\\_REPLICA\\_HEARTBEAT\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Unexpected source's heartbeat data: %s

[ER\\_REPLICA\\_HEARTBEAT\\_FAILURE](#) was added in 8.0.33.

- Error number: [MY-013119](#); Symbol: [ER\\_SLAVE\\_INCIDENT](#); SQLSTATE: [HY000](#)

Message: The incident %s occurred on the master. Message: %s

[ER\\_SLAVE\\_INCIDENT](#) was removed after 8.0.32.

- Error number: [MY-013119](#); Symbol: [ER\\_REPLICA\\_INCIDENT](#); SQLSTATE: [HY000](#)

Message: The incident %s occurred on the source. Message: %s

[ER\\_REPLICA\\_INCIDENT](#) was added in 8.0.33.

- Error number: [MY-013120](#); Symbol: [ER\\_SLAVE\\_MASTER\\_COM\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Master command %s failed: %s

[ER\\_SLAVE\\_MASTER\\_COM\\_FAILURE](#) was removed after 8.0.32.

- Error number: [MY-013120](#); Symbol: [ER\\_REPLICA\\_SOURCE\\_COM\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Source command %s failed: %s

[ER\\_REPLICA\\_SOURCE\\_COM\\_FAILURE](#) was added in 8.0.33.

- Error number: [MY-013121](#); Symbol: [ER\\_SLAVE\\_RELAY\\_LOG\\_READ\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log read failure: %s

[ER\\_SLAVE\\_RELAY\\_LOG\\_READ\\_FAILURE](#) was removed after 8.0.32.

- Error number: [MY-013121](#); Symbol: [ER\\_REPLICA\\_RELAY\\_LOG\\_READ\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log read failure: %s

[ER\\_REPLICA\\_RELAY\\_LOG\\_READ\\_FAILURE](#) was added in 8.0.33.

- Error number: [MY-013122](#); Symbol: [ER\\_SLAVE\\_RELAY\\_LOG\\_WRITE\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log write failure: %s

[ER\\_SLAVE\\_RELAY\\_LOG\\_WRITE\\_FAILURE](#) was removed after 8.0.32.

- Error number: [MY-013122](#); Symbol: [ER\\_REPLICA\\_RELAY\\_LOG\\_WRITE\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log write failure: %s

[ER\\_REPLICA\\_RELAY\\_LOG\\_WRITE\\_FAILURE](#) was added in 8.0.33.

- Error number: [MY-013123](#); Symbol: [ER\\_SERVER\\_SLAVE\\_MI\\_INIT\\_REPOSITORY](#); SQLSTATE: [HY000](#)

- 
- Message: Slave failed to initialize master info structure from the repository  
`ER_SERVER_SLAVE_MI_INIT_REPOSITORY` was added in 8.0.11, removed after 8.0.32.
- Error number: `MY-013123`; Symbol: `ER_SERVER_REPLICA_CM_INIT_REPOSITORY`; SQLSTATE: `HY000`  
Message: Replica failed to initialize connection metadata structure from the repository  
`ER_SERVER_REPLICA_CM_INIT_REPOSITORY` was added in 8.0.33.
  - Error number: `MY-013124`; Symbol: `ER_SERVER_SLAVE_RLI_INIT_REPOSITORY`; SQLSTATE: `HY000`  
Message: Slave failed to initialize relay log info structure from the repository  
`ER_SERVER_SLAVE_RLI_INIT_REPOSITORY` was added in 8.0.11, removed after 8.0.32.
  - Error number: `MY-013124`; Symbol: `ER_SERVER_REPLICA_AM_INIT_REPOSITORY`; SQLSTATE: `HY000`  
Message: Replica failed to initialize applier metadata structure from the repository  
`ER_SERVER_REPLICA_AM_INIT_REPOSITORY` was added in 8.0.33.
  - Error number: `MY-013125`; Symbol: `ER_SERVER_NET_PACKET_TOO_LARGE`; SQLSTATE: `HY000`  
Message: Got a packet bigger than 'max\_allowed\_packet' bytes  
`ER_SERVER_NET_PACKET_TOO_LARGE` was added in 8.0.11.
  - Error number: `MY-013126`; Symbol: `ER_SERVER_NO_SYSTEM_TABLE_ACCESS`; SQLSTATE: `HY000`  
Message: Access to %s '%s.%s' is rejected.  
`ER_SERVER_NO_SYSTEM_TABLE_ACCESS` was added in 8.0.11.
  - Error number: `MY-013127`; Symbol: `ER_SERVER_UNKNOWN_ERROR`; SQLSTATE: `HY000`  
Message: Unknown error  
`ER_SERVER_UNKNOWN_ERROR` was added in 8.0.11, removed after 8.0.32.
  - Error number: `MY-013128`; Symbol: `ER_SERVER_UNKNOWN_SYSTEM_VARIABLE`; SQLSTATE: `HY000`  
Message: Unknown system variable '%s'  
`ER_SERVER_UNKNOWN_SYSTEM_VARIABLE` was added in 8.0.11.
  - Error number: `MY-013129`; Symbol: `ER_SERVER_NO_SESSION_TO_SEND_TO`; SQLSTATE: `HY000`  
Message: A message intended for a client cannot be sent there as no client-session is attached.  
Therefore, we're sending the information to the error-log instead: MY-%06d - %s  
`ER_SERVER_NO_SESSION_TO_SEND_TO` was added in 8.0.11.
  - Error number: `MY-013130`; Symbol: `ER_SERVER_NEW_ABORTING_CONNECTION`; SQLSTATE: `08S01`  
Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s; diagnostics area: MY-%06d - %s)



---

`ER_SERVER_NEW_ABORTING_CONNECTION` was added in 8.0.11.

- Error number: `MY-013131`; Symbol: `ER_SERVER_OUT_OF_SORTMEMORY`; SQLSTATE: `HY000`

Message: Out of sort memory, consider increasing server sort buffer size!

`ER_SERVER_OUT_OF_SORTMEMORY` was added in 8.0.11.

- Error number: `MY-013132`; Symbol: `ER_SERVER_RECORD_FILE_FULL`; SQLSTATE: `HY000`

Message: The table '%s' is full!

`ER_SERVER_RECORD_FILE_FULL` was added in 8.0.11.

- Error number: `MY-013133`; Symbol: `ER_SERVER_DISK_FULL_NOWAIT`; SQLSTATE: `HY000`

Message: Create table/tablespace '%s' failed, as disk is full.

`ER_SERVER_DISK_FULL_NOWAIT` was added in 8.0.11.

- Error number: `MY-013134`; Symbol: `ER_SERVER_HANDLER_ERROR`; SQLSTATE: `HY000`

Message: Handler reported error %d - %s

`ER_SERVER_HANDLER_ERROR` was added in 8.0.11.

- Error number: `MY-013135`; Symbol: `ER_SERVER_NOT_FORM_FILE`; SQLSTATE: `HY000`

Message: Incorrect information in file: '%s'

`ER_SERVER_NOT_FORM_FILE` was added in 8.0.11.

- Error number: `MY-013136`; Symbol: `ER_SERVER_CANT_OPEN_FILE`; SQLSTATE: `HY000`

Message: Can't open file: '%s' (OS errno: %d - %s)

`ER_SERVER_CANT_OPEN_FILE` was added in 8.0.11.

- Error number: `MY-013137`; Symbol: `ER_SERVER_FILE_NOT_FOUND`; SQLSTATE: `HY000`

Message: Can't find file: '%s' (OS errno: %d - %s)

`ER_SERVER_FILE_NOT_FOUND` was added in 8.0.11.

- Error number: `MY-013138`; Symbol: `ER_SERVER_FILE_USED`; SQLSTATE: `HY000`

Message: '%s' is locked against change (OS errno: %d - %s)

`ER_SERVER_FILE_USED` was added in 8.0.11.

- Error number: `MY-013139`; Symbol: `ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2`; SQLSTATE: `HY000`

Message: Cannot load from %s.%s. The table is probably corrupted!

`ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2` was added in 8.0.11.

- Error number: `MY-013140`; Symbol: `ER_ERROR_INFO_FROM_DA`; SQLSTATE: `HY000`

---

Message: Error in diagnostics area: MY-%06d - %s

[ER\\_ERROR\\_INFO\\_FROM\\_DA](#) was added in 8.0.11.

- Error number: [MY-013141](#); Symbol: [ER\\_SERVER\\_TABLE\\_CHECK\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Incorrect definition of table %s.%s: expected column '%s' at position %d, found '%s'.

[ER\\_SERVER\\_TABLE\\_CHECK\\_FAILED](#) was added in 8.0.11.

- Error number: [MY-013142](#); Symbol: [ER\\_SERVER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_PLEASE\\_UPDATE\\_V2](#); SQLSTATE: [HY000](#)

Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

[ER\\_SERVER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_PLEASE\\_UPDATE\\_V2](#) was added in 8.0.11.

- Error number: [MY-013143](#); Symbol: [ER\\_SERVER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_CORRUPTED\\_V2](#); SQLSTATE: [HY000](#)

Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted

[ER\\_SERVER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_CORRUPTED\\_V2](#) was added in 8.0.11.

- Error number: [MY-013144](#); Symbol: [ER\\_SERVER\\_ACL\\_TABLE\\_ERROR](#); SQLSTATE: [HY000](#)

Message:

[ER\\_SERVER\\_ACL\\_TABLE\\_ERROR](#) was added in 8.0.11.

- Error number: [MY-013145](#); Symbol: [ER\\_SERVER\\_SLAVE\\_INIT\\_QUERY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread aborted. Can't execute init\_replica query, MY-%06d - '%s'

[ER\\_SERVER\\_SLAVE\\_INIT\\_QUERY\\_FAILED](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-013145](#); Symbol: [ER\\_SERVER\\_REPLICA\\_INIT\\_QUERY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread aborted. Can't execute init\_replica query, MY-%06d - '%s'

[ER\\_SERVER\\_REPLICA\\_INIT\\_QUERY\\_FAILED](#) was added in 8.0.33.

- Error number: [MY-013146](#); Symbol: [ER\\_SERVER\\_SLAVE\\_CONVERSION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'

[ER\\_SERVER\\_SLAVE\\_CONVERSION\\_FAILED](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-013146](#); Symbol: [ER\\_SERVER\\_REPLICA\\_CONVERSION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'

[ER\\_SERVER\\_REPLICA\\_CONVERSION\\_FAILED](#) was added in 8.0.33.

- Error number: [MY-013147](#); Symbol: [ER\\_SERVER\\_SLAVE\\_IGNORED\\_TABLE](#); SQLSTATE: [HY000](#)

---

Message: Slave SQL thread ignored the query because of replicate-\*-table rules

`ER_SERVER_SLAVE_IGNORED_TABLE` was added in 8.0.11, removed after 8.0.32.

- Error number: `MY-013147`; Symbol: `ER_SERVER_REPLICA_IGNORED_TABLE`; SQLSTATE: `HY000`

Message: Replica SQL thread ignored the query because of replicate-\*-table rules

`ER_SERVER_REPLICA_IGNORED_TABLE` was added in 8.0.33.

- Error number: `MY-013148`; Symbol: `ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION`; SQLSTATE: `HY000`

Message: Cannot replicate anonymous transaction when `AUTO_POSITION = 1`, at file %s, position %lld.

- Error number: `MY-013149`; Symbol: `ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_ON`; SQLSTATE: `HY000`

Message: Cannot replicate anonymous transaction when `@@GLOBAL.GTID_MODE = ON`, at file %s, position %lld.

- Error number: `MY-013150`; Symbol: `ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF`; SQLSTATE: `HY000`

Message: Cannot replicate GTID-transaction when `@@GLOBAL.GTID_MODE = OFF`, at file %s, position %lld.

- Error number: `MY-013151`; Symbol: `ER_SERVER_TEST_MESSAGE`; SQLSTATE: `HY000`

Message: Simulated error

`ER_SERVER_TEST_MESSAGE` was added in 8.0.11.

- Error number: `MY-013152`; Symbol: `ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR`; SQLSTATE: `HY000`

Message: %s

`ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR` was added in 8.0.11.

- Error number: `MY-013153`; Symbol: `ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED`; SQLSTATE: `HY000`

Message: Audit Log filtering has not been installed.

`ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED` was added in 8.0.11.

- Error number: `MY-013154`; Symbol: `ER_PLUGIN_FAILED_TO_OPEN_TABLES`; SQLSTATE: `HY000`

Message: Failed to open the %s filter tables.

`ER_PLUGIN_FAILED_TO_OPEN_TABLES` was added in 8.0.11.

- Error number: `MY-013155`; Symbol: `ER_PLUGIN_FAILED_TO_OPEN_TABLE`; SQLSTATE: `HY000`

Message: Failed to open '%s.%s' %s table.

`ER_PLUGIN_FAILED_TO_OPEN_TABLE` was added in 8.0.11.

- 
- Error number: `MY-013156`; Symbol: `ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`  
  
Message: Filter name cannot be empty.  
  
`ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY` was added in 8.0.11.
  - Error number: `MY-013157`; Symbol: `ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER`; SQLSTATE: `HY000`  
  
Message: Invalid character in the user name.  
  
`ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER` was added in 8.0.11.
  - Error number: `MY-013158`; Symbol: `ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE`; SQLSTATE: `HY000`  
  
Message: Request ignored for '%s'@'%s'. SUPER or AUDIT\_ADMIN needed to perform operation  
  
`ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE` was added in 8.0.11.
  - Error number: `MY-013159`; Symbol: `ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED`; SQLSTATE: `HY000`  
  
Message: No keyring installed.  
  
`ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED` was added in 8.0.11.
  - Error number: `MY-013160`; Symbol: `ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER`; SQLSTATE: `HY000`  
  
Message: Invalid character in the host name.  
  
`ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER` was added in 8.0.11.
  - Error number: `MY-013161`; Symbol: `ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_SET`; SQLSTATE: `HY000`  
  
Message: Audit log encryption password has not been set; it will be generated automatically. Use `audit_log_encryption_password_get` to obtain the password or `audit_log_encryption_password_set` to set a new one.  
  
`ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_SET` was added in 8.0.11.
  - Error number: `MY-013162`; Symbol: `ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY`; SQLSTATE: `HY000`  
  
Message: Could not create AES key. OpenSSL's `EVP_BytesToKey` function failed.  
  
`ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY` was added in 8.0.11.
  - Error number: `MY-013163`; Symbol: `ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_FETCHED`; SQLSTATE: `HY000`  
  
Message: Audit log encryption password cannot be fetched from the keyring. Password used so far is used for encryption.  
  
`ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_FETCHED` was added in 8.0.11.

- 
- Error number: `MY-013164`; Symbol: `ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS`; SQLSTATE: `HY000`  
Message: Could not reinitialize audit log filters.  
`ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS` was added in 8.0.11.
  - Error number: `MY-013165`; Symbol: `ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`  
Message: User cannot be empty.  
`ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY` was added in 8.0.11.
  - Error number: `MY-013166`; Symbol: `ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHANUMERIC`; SQLSTATE: `HY000`  
Message: First character of the user name must be alphanumeric.  
`ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHANUMERIC` was added in 8.0.11.
  - Error number: `MY-013167`; Symbol: `ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST`; SQLSTATE: `HY000`  
Message: Specified filter has not been found.  
`ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST` was added in 8.0.11.
  - Error number: `MY-013168`; Symbol: `ER_IB_MSG_1271`; SQLSTATE: `HY000`  
Message: Cannot upgrade server earlier than 5.7 to 8.0  
`ER_IB_MSG_1271` was added in 8.0.11.
  - Error number: `MY-013169`; Symbol: `ER_STARTING_INIT`; SQLSTATE: `HY000`  
Message: %s (mysqld %s) initializing of server in progress as process %lu  
`ER_STARTING_INIT` was added in 8.0.11.
  - Error number: `MY-013170`; Symbol: `ER_ENDING_INIT`; SQLSTATE: `HY000`  
Message: %s (mysqld %s) initializing of server has completed  
`ER_ENDING_INIT` was added in 8.0.11.
  - Error number: `MY-013171`; Symbol: `ER_IB_MSG_1272`; SQLSTATE: `HY000`  
Message: Cannot boot server version %lu on data directory built by version %llu. Downgrade is not supported  
`ER_IB_MSG_1272` was added in 8.0.11.
  - Error number: `MY-013172`; Symbol: `ER_SERVER_SHUTDOWN_INFO`; SQLSTATE: `HY000`  
Message: Received SHUTDOWN from user %s. Shutting down mysqld (Version: %s).  
`ER_SERVER_SHUTDOWN_INFO` was added in 8.0.12.
  - Error number: `MY-013173`; Symbol: `ER_GRP_RPL_PLUGIN_ABORT`; SQLSTATE: `HY000`

---

Message: The plugin encountered a critical error and will abort: %s

[ER\\_GRP\\_RPL\\_PLUGIN\\_ABORT](#) was added in 8.0.12.

- Error number: [MY-013177](#); Symbol: [ER\\_AUDIT\\_LOG\\_TABLE\\_DEFINITION\\_NOT\\_UPDATED](#); SQLSTATE: [HY000](#)

Message: '%s.%s' table definition has not been upgraded; Please perform the MySQL upgrade procedure.

[ER\\_AUDIT\\_LOG\\_TABLE\\_DEFINITION\\_NOT\\_UPDATED](#) was added in 8.0.12.

- Error number: [MY-013178](#); Symbol: [ER\\_DD\\_INITIALIZE\\_SQL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Execution of server-side SQL statement '%s' failed with error code = %d, error message = '%s'.

[ER\\_DD\\_INITIALIZE\\_SQL\\_ERROR](#) was added in 8.0.12.

- Error number: [MY-013179](#); Symbol: [ER\\_NO\\_PATH\\_FOR\\_SHARED\\_LIBRARY](#); SQLSTATE: [HY000](#)

Message: No paths allowed for shared library.

[ER\\_NO\\_PATH\\_FOR\\_SHARED\\_LIBRARY](#) was added in 8.0.13.

- Error number: [MY-013180](#); Symbol: [ER\\_UDF\\_ALREADY\\_EXISTS](#); SQLSTATE: [HY000](#)

Message: Function '%s' already exists.

[ER\\_UDF\\_ALREADY\\_EXISTS](#) was added in 8.0.13.

- Error number: [MY-013181](#); Symbol: [ER\\_SET\\_EVENT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Got Error: %ld from SetEvent.

[ER\\_SET\\_EVENT\\_FAILED](#) was added in 8.0.13.

- Error number: [MY-013182](#); Symbol: [ER\\_FAILED\\_TO\\_ALLOCATE\\_SSL\\_BIO](#); SQLSTATE: [HY000](#)

Message: Error allocating SSL BIO.

[ER\\_FAILED\\_TO\\_ALLOCATE\\_SSL\\_BIO](#) was added in 8.0.13.

- Error number: [MY-013183](#); Symbol: [ER\\_IB\\_MSG\\_1273](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1273](#) was added in 8.0.13.

- Error number: [MY-013184](#); Symbol: [ER\\_PID\\_FILEPATH\\_LOCATIONS\\_INACCESSIBLE](#); SQLSTATE: [HY000](#)

Message: One or several locations were inaccessible while checking PID filepath.

[ER\\_PID\\_FILEPATH\\_LOCATIONS\\_INACCESSIBLE](#) was added in 8.0.13.

- Error number: [MY-013185](#); Symbol: [ER\\_UNKNOWN\\_VARIABLE\\_IN\\_PERSISTED\\_CONFIG\\_FILE](#); SQLSTATE: [HY000](#)

---

Message: Currently unknown variable '%s' was read from the persisted config file.

[ER\\_UNKNOWN\\_VARIABLE\\_IN\\_PERSISTED\\_CONFIG\\_FILE](#) was added in 8.0.13.

- Error number: [MY-013186](#); Symbol: [ER\\_FAILED\\_TO\\_HANDLE\\_DEFAULTS\\_FILE](#); SQLSTATE: [HY000](#)

Message: Fatal error in defaults handling. Program aborted!

[ER\\_FAILED\\_TO\\_HANDLE\\_DEFAULTS\\_FILE](#) was added in 8.0.13.

- Error number: [MY-013187](#); Symbol: [ER\\_DUPLICATE\\_SYS\\_VAR](#); SQLSTATE: [HY000](#)

Message: Duplicate variable name '%s'.

[ER\\_DUPLICATE\\_SYS\\_VAR](#) was added in 8.0.13.

- Error number: [MY-013188](#); Symbol: [ER\\_FAILED\\_TO\\_INIT\\_SYS\\_VAR](#); SQLSTATE: [HY000](#)

Message: Failed to initialize system variables.

[ER\\_FAILED\\_TO\\_INIT\\_SYS\\_VAR](#) was added in 8.0.13.

- Error number: [MY-013189](#); Symbol: [ER\\_SYS\\_VAR\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Variable name '%s' not found.

[ER\\_SYS\\_VAR\\_NOT\\_FOUND](#) was added in 8.0.13.

- Error number: [MY-013190](#); Symbol: [ER\\_IB\\_MSG\\_1274](#); SQLSTATE: [HY000](#)

Message: Some (%d) threads are still active

[ER\\_IB\\_MSG\\_1274](#) was added in 8.0.13.

- Error number: [MY-013191](#); Symbol: [ER\\_IB\\_MSG\\_1275](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1275](#) was added in 8.0.13.

- Error number: [MY-013192](#); Symbol: [ER\\_TARGET\\_TS\\_UNENCRYPTED](#); SQLSTATE: [HY000](#)

Message: Source tablespace is encrypted but target tablespace is not.

[ER\\_TARGET\\_TS\\_UNENCRYPTED](#) was added in 8.0.13, removed after 8.0.15.

- Error number: [MY-013193](#); Symbol: [ER\\_IB\\_MSG\\_1276](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1276](#) was added in 8.0.13, removed after 8.0.13.

- Error number: [MY-013193](#); Symbol: [ER\\_IB\\_MSG\\_WAIT\\_FOR\\_ENCRYPT\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Waiting for tablespace\_alter\_encrypt\_thread to exit

[ER\\_IB\\_MSG\\_WAIT\\_FOR\\_ENCRYPT\\_THREAD](#) was added in 8.0.14.

- Error number: [MY-013194](#); Symbol: [ER\\_IB\\_MSG\\_1277](#); SQLSTATE: [HY000](#)

---

Message: %s

[ER\\_IB\\_MSG\\_1277](#) was added in 8.0.13.

- Error number: [MY-013195](#); Symbol: [ER\\_IB\\_MSG\\_1278](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1278](#) was added in 8.0.13, removed after 8.0.13.

- Error number: [MY-013195](#); Symbol: [ER\\_IB\\_MSG\\_NO\\_ENCRYPT\\_PROGRESS\\_FOUND](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_NO\\_ENCRYPT\\_PROGRESS\\_FOUND](#) was added in 8.0.14.

- Error number: [MY-013196](#); Symbol: [ER\\_IB\\_MSG\\_1279](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1279](#) was added in 8.0.13, removed after 8.0.13.

- Error number: [MY-013196](#); Symbol: [ER\\_IB\\_MSG\\_RESUME\\_OP\\_FOR\\_SPACE](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_RESUME\\_OP\\_FOR\\_SPACE](#) was added in 8.0.14.

- Error number: [MY-013197](#); Symbol: [ER\\_IB\\_MSG\\_1280](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1280](#) was added in 8.0.13.

- Error number: [MY-013198](#); Symbol: [ER\\_IB\\_MSG\\_1281](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1281](#) was added in 8.0.13.

- Error number: [MY-013199](#); Symbol: [ER\\_IB\\_MSG\\_1282](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1282](#) was added in 8.0.13.

- Error number: [MY-013200](#); Symbol: [ER\\_IB\\_MSG\\_1283](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1283](#) was added in 8.0.13.

- Error number: [MY-013201](#); Symbol: [ER\\_IB\\_MSG\\_1284](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1284](#) was added in 8.0.13.



- 
- Error number: [MY-013202](#); Symbol: [ER\\_CANT\\_SET\\_ERROR\\_SUPPRESSION\\_LIST\\_FROM\\_COMMAND\\_LINE](#); SQLSTATE: [HY000](#)  
Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.  
[ER\\_CANT\\_SET\\_ERROR\\_SUPPRESSION\\_LIST\\_FROM\\_COMMAND\\_LINE](#) was added in 8.0.13.
  - Error number: [MY-013203](#); Symbol: [ER\\_INVALID\\_VALUE\\_OF\\_BIND\\_ADDRESSES](#); SQLSTATE: [HY000](#)  
Message: Invalid value for command line option bind-addresses: '%s'  
[ER\\_INVALID\\_VALUE\\_OF\\_BIND\\_ADDRESSES](#) was added in 8.0.13.
  - Error number: [MY-013204](#); Symbol: [ER\\_RELAY\\_LOG\\_SPACE\\_LIMIT\\_DISABLED](#); SQLSTATE: [HY000](#)  
Message: Ignoring the @@global.relay\_log\_space\_limit option because @@global.relay\_log\_purge is disabled.  
[ER\\_RELAY\\_LOG\\_SPACE\\_LIMIT\\_DISABLED](#) was added in 8.0.13.
  - Error number: [MY-013205](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_GTID\\_SET\\_EXTRACTION](#); SQLSTATE: [HY000](#)  
Message: Error when extracting GTID execution information: %s  
[ER\\_GRP\\_RPL\\_ERROR\\_GTID\\_SET\\_EXTRACTION](#) was added in 8.0.13.
  - Error number: [MY-013206](#); Symbol: [ER\\_GRP\\_RPL\\_MISSING\\_GRP\\_RPL\\_ACTION\\_COORDINATOR](#); SQLSTATE: [HY000](#)  
Message: Message received without a proper group coordinator module.  
[ER\\_GRP\\_RPL\\_MISSING\\_GRP\\_RPL\\_ACTION\\_COORDINATOR](#) was added in 8.0.13.
  - Error number: [MY-013207](#); Symbol: [ER\\_GRP\\_RPL\\_JOIN\\_WHEN\\_GROUP\\_ACTION\\_RUNNING](#); SQLSTATE: [HY000](#)  
Message: A member cannot join the group while a group configuration operation '%s' is running initiated by '%s'.  
[ER\\_GRP\\_RPL\\_JOIN\\_WHEN\\_GROUP\\_ACTION\\_RUNNING](#) was added in 8.0.13.
  - Error number: [MY-013208](#); Symbol: [ER\\_GRP\\_RPL\\_JOINER\\_EXIT\\_WHEN\\_GROUP\\_ACTION\\_RUNNING](#); SQLSTATE: [HY000](#)  
Message: A member is joining the group while a group configuration operation '%s' is running initiated by '%s'. The member will now leave the group.  
[ER\\_GRP\\_RPL\\_JOINER\\_EXIT\\_WHEN\\_GROUP\\_ACTION\\_RUNNING](#) was added in 8.0.13.
  - Error number: [MY-013209](#); Symbol: [ER\\_GRP\\_RPL\\_CHANNEL\\_THREAD\\_WHEN\\_GROUP\\_ACTION\\_RUNNING](#); SQLSTATE: [HY000](#)  
Message: Can't start %s for channel '%s' when group replication is running a group configuration operation '%s' initiated by '%s'.  
[ER\\_GRP\\_RPL\\_CHANNEL\\_THREAD\\_WHEN\\_GROUP\\_ACTION\\_RUNNING](#) was added in 8.0.13.

- 
- Error number: [MY-013210](#); Symbol: [ER\\_GRP\\_RPL\\_APPOINTED\\_PRIMARY\\_NOT\\_PRESENT](#); SQLSTATE: [HY000](#)  
  
Message: A primary election was invoked but the requested primary member is not in the group. Request ignored.  
  
[ER\\_GRP\\_RPL\\_APPOINTED\\_PRIMARY\\_NOT\\_PRESENT](#) was added in 8.0.13.
  - Error number: [MY-013211](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_ON\\_MESSAGE\\_SENDING](#); SQLSTATE: [HY000](#)  
  
Message: Error while sending message. Context: %s  
  
[ER\\_GRP\\_RPL\\_ERROR\\_ON\\_MESSAGE\\_SENDING](#) was added in 8.0.13.
  - Error number: [MY-013212](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error while executing a group configuration operation: %s  
  
[ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_ERROR](#) was added in 8.0.13.
  - Error number: [MY-013213](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_LOCAL\\_TERMINATION](#); SQLSTATE: [HY000](#)  
  
Message: Configuration operation '%s' terminated. %s  
  
[ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_LOCAL\\_TERMINATION](#) was added in 8.0.13.
  - Error number: [MY-013214](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_START](#); SQLSTATE: [HY000](#)  
  
Message: Starting group operation local execution: %s  
  
[ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_START](#) was added in 8.0.13.
  - Error number: [MY-013215](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_END](#); SQLSTATE: [HY000](#)  
  
Message: Termination of group operation local execution: %s  
  
[ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_END](#) was added in 8.0.13.
  - Error number: [MY-013216](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_KILLED\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: A configuration change was killed in this member. The member will now leave the group as its configuration may have diverged.  
  
[ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_KILLED\\_ERROR](#) was added in 8.0.13.
  - Error number: [MY-013217](#); Symbol: [ER\\_GRP\\_RPL\\_PRIMARY\\_ELECTION\\_PROCESS\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: There was an issue on the primary election process: %s The member will now leave the group.  
  
[ER\\_GRP\\_RPL\\_PRIMARY\\_ELECTION\\_PROCESS\\_ERROR](#) was added in 8.0.13.

- 
- Error number: [MY-013218](#); Symbol: [ER\\_GRP\\_RPL\\_PRIMARY\\_ELECTION\\_STOP\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: There was an issue when stopping a previous election process: %s  
  
[ER\\_GRP\\_RPL\\_PRIMARY\\_ELECTION\\_STOP\\_ERROR](#) was added in 8.0.13.
  - Error number: [MY-013219](#); Symbol: [ER\\_GRP\\_RPL\\_NO\\_STAGE\\_SERVICE](#); SQLSTATE: [HY000](#)  
  
Message: It was not possible to initialize stage logging for this task. The operation will still run without stage tracking.  
  
[ER\\_GRP\\_RPL\\_NO\\_STAGE\\_SERVICE](#) was added in 8.0.13.
  - Error number: [MY-013220](#); Symbol: [ER\\_GRP\\_RPL\\_UDF\\_REGISTER\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Could not execute the installation of Group Replication UDF function: %s. Check if the function is already present, if so, try to remove it  
  
[ER\\_GRP\\_RPL\\_UDF\\_REGISTER\\_ERROR](#) was added in 8.0.13.
  - Error number: [MY-013221](#); Symbol: [ER\\_GRP\\_RPL\\_UDF\\_UNREGISTER\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Could not uninstall Group Replication UDF functions. Try to remove them manually if present.  
  
[ER\\_GRP\\_RPL\\_UDF\\_UNREGISTER\\_ERROR](#) was added in 8.0.13.
  - Error number: [MY-013222](#); Symbol: [ER\\_GRP\\_RPL\\_UDF\\_REGISTER\\_SERVICE\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Could not execute the installation of Group Replication UDF functions. Check for other errors in the log and try to reinstall the plugin  
  
[ER\\_GRP\\_RPL\\_UDF\\_REGISTER\\_SERVICE\\_ERROR](#) was added in 8.0.13.
  - Error number: [MY-013223](#); Symbol: [ER\\_GRP\\_RPL\\_SERVER\\_UDF\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: The function '%s' failed. %s  
  
[ER\\_GRP\\_RPL\\_SERVER\\_UDF\\_ERROR](#) was added in 8.0.17.
  - Error number: [MY-013227](#); Symbol: [ER\\_SERVER\\_WRONG\\_VALUE\\_FOR\\_VAR](#); SQLSTATE: [HY000](#)  
  
Message: Variable '%s' can't be set to the value of '%s'  
  
[ER\\_SERVER\\_WRONG\\_VALUE\\_FOR\\_VAR](#) was added in 8.0.13.
  - Error number: [MY-013228](#); Symbol: [ER\\_COULD\\_NOT\\_CREATE\\_WINDOWS\\_REGISTRY\\_KEY](#); SQLSTATE: [HY000](#)  
  
Message: %s was unable to create a new Windows registry key %s for %s; continuing to use the previous ident.  
  
[ER\\_COULD\\_NOT\\_CREATE\\_WINDOWS\\_REGISTRY\\_KEY](#) was added in 8.0.13.

- 
- Error number: `MY-013229`; Symbol: `ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR`; SQLSTATE: `HY000`  
Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog\_format=STATEMENT.  
`ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR` was added in 8.0.13.
  - Error number: `MY-013233`; Symbol: `ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX`; SQLSTATE: `HY000`  
Message: Unable to switch security context to user: %s  
`ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX` was added in 8.0.13.
  - Error number: `MY-013234`; Symbol: `ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION`; SQLSTATE: `HY000`  
Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with expression as DEFAULT.  
`ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION` was added in 8.0.13.
  - Error number: `MY-013235`; Symbol: `ER_UPGRADE_PARSE_ERROR`; SQLSTATE: `HY000`  
Message: Error in parsing %s '%s'.'%s' during upgrade. %s  
`ER_UPGRADE_PARSE_ERROR` was added in 8.0.13.
  - Error number: `MY-013236`; Symbol: `ER_DATA_DIRECTORY_UNUSABLE`; SQLSTATE: `HY000`  
Message: The designated data directory %s is unusable. You can remove all files that the server added to it.  
`ER_DATA_DIRECTORY_UNUSABLE` was added in 8.0.13.
  - Error number: `MY-013237`; Symbol: `ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND`; SQLSTATE: `HY000`  
Message: Group search rebinding via root DN: %s  
`ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND` was added in 8.0.13.
  - Error number: `MY-013238`; Symbol: `ER_PLUGIN_INSTALL_ERROR`; SQLSTATE: `HY000`  
Message: Error installing plugin '%s': %s  
`ER_PLUGIN_INSTALL_ERROR` was added in 8.0.13.
  - Error number: `MY-013239`; Symbol: `ER_PLUGIN_UNINSTALL_ERROR`; SQLSTATE: `HY000`  
Message: Error uninstalling plugin '%s': %s  
`ER_PLUGIN_UNINSTALL_ERROR` was added in 8.0.13.
  - Error number: `MY-013240`; Symbol: `ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE`; SQLSTATE: `HY000`

---

Message: Partitioned table '%s' is not allowed to use shared tablespace '%s'. Please move all partitions to file-per-table tablespaces before upgrade.

[ER\\_SHARED\\_TABLESPACE\\_USED\\_BY\\_PARTITIONED\\_TABLE](#) was added in 8.0.13.

- Error number: [MY-013241](#); Symbol: [ER\\_UNKNOWN\\_TABLESPACE\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Cannot determine the type of the tablespace named '%s'.

[ER\\_UNKNOWN\\_TABLESPACE\\_TYPE](#) was added in 8.0.13.

- Error number: [MY-013242](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_UTF8\\_ALIAS\\_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.

[ER\\_WARN\\_DEPRECATED\\_UTF8\\_ALIAS\\_OPTION](#) was added in 8.0.13.

- Error number: [MY-013243](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_UTF8MB3\\_CHARSET\\_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: The character set UTF8MB3 is deprecated and will be removed in a future release. Please consider using UTF8MB4 instead.

[ER\\_WARN\\_DEPRECATED\\_UTF8MB3\\_CHARSET\\_OPTION](#) was added in 8.0.13.

- Error number: [MY-013244](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_UTF8MB3\\_COLLATION\\_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.

[ER\\_WARN\\_DEPRECATED\\_UTF8MB3\\_COLLATION\\_OPTION](#) was added in 8.0.13.

- Error number: [MY-013245](#); Symbol: [ER\\_SSL\\_MEMORY\\_INSTRUMENTATION\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: The SSL library function %s failed. This is typically caused by the SSL library already being used. As a result the SSL memory allocation will not be instrumented.

[ER\\_SSL\\_MEMORY\\_INSTRUMENTATION\\_INIT\\_FAILED](#) was added in 8.0.13.

- Error number: [MY-013246](#); Symbol: [ER\\_IB\\_MSG\\_MADV\\_DONTDUMP\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: Disabling @@core\_file because @@innodb\_buffer\_pool\_in\_core\_file is disabled, yet MADV\_DONTDUMP is not supported on this platform

[ER\\_IB\\_MSG\\_MADV\\_DONTDUMP\\_UNSUPPORTED](#) was added in 8.0.14.

- Error number: [MY-013247](#); Symbol: [ER\\_IB\\_MSG\\_MADVISE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Disabling @@core\_file because @@innodb\_buffer\_pool\_in\_core\_file is disabled, yet madvise(%p,%zu,%s) failed with %s

[ER\\_IB\\_MSG\\_MADVISE\\_FAILED](#) was added in 8.0.14.

- 
- Error number: [MY-013249](#); Symbol: [ER\\_WARN\\_REMOVED\\_SQL\\_MODE](#); SQLSTATE: [HY000](#)  
Message: sql\_mode=0x%08x has been removed and will be ignored  
[ER\\_WARN\\_REMOVED\\_SQL\\_MODE](#) was added in 8.0.14.
  - Error number: [MY-013250](#); Symbol: [ER\\_IB\\_MSG\\_FAILED\\_TO\\_ALLOCATE\\_WAIT](#); SQLSTATE: [HY000](#)  
Message: Failed to allocate memory for a pool of size %zu bytes. Will wait for %zu seconds for a thread to free a resource.  
[ER\\_IB\\_MSG\\_FAILED\\_TO\\_ALLOCATE\\_WAIT](#) was added in 8.0.14.
  - Error number: [MY-013251](#); Symbol: [ER\\_IB\\_MSG\\_NUM\\_POOLS](#); SQLSTATE: [HY000](#)  
Message: Number of pools: %zu  
[ER\\_IB\\_MSG\\_NUM\\_POOLS](#) was added in 8.0.14, removed after 8.0.30.
  - Error number: [MY-013252](#); Symbol: [ER\\_IB\\_MSG\\_USING\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Using undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_USING\\_UNDO\\_SPACE](#) was added in 8.0.14.
  - Error number: [MY-013253](#); Symbol: [ER\\_IB\\_MSG\\_FAIL\\_TO\\_SAVE\\_SPACE\\_STATE](#); SQLSTATE: [HY000](#)  
Message: %s Unable to save the current state of tablespace '%s' to the data dictionary  
[ER\\_IB\\_MSG\\_FAIL\\_TO\\_SAVE\\_SPACE\\_STATE](#) was added in 8.0.14.
  - Error number: [MY-013254](#); Symbol: [ER\\_IB\\_MSG\\_MAX\\_UNDO\\_SPACES\\_REACHED](#); SQLSTATE: [HY000](#)  
Message: Cannot create undo tablespace %s at %s because %d undo tablespaces already exist.  
[ER\\_IB\\_MSG\\_MAX\\_UNDO\\_SPACES\\_REACHED](#) was added in 8.0.14.
  - Error number: [MY-013255](#); Symbol: [ER\\_IB\\_MSG\\_ERROR\\_OPENING\\_NEW\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Error %d opening newly created undo tablespace %s.  
[ER\\_IB\\_MSG\\_ERROR\\_OPENING\\_NEW\\_UNDO\\_SPACE](#) was added in 8.0.14.
  - Error number: [MY-013256](#); Symbol: [ER\\_IB\\_MSG\\_FAILED\\_SDI\\_Z\\_BUF\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: SDI Compression failed, Z\_BUF\_ERROR  
[ER\\_IB\\_MSG\\_FAILED\\_SDI\\_Z\\_BUF\\_ERROR](#) was added in 8.0.14.
  - Error number: [MY-013257](#); Symbol: [ER\\_IB\\_MSG\\_FAILED\\_SDI\\_Z\\_MEM\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: SDI Compression failed, Z\_MEM\_ERROR  
[ER\\_IB\\_MSG\\_FAILED\\_SDI\\_Z\\_MEM\\_ERROR](#) was added in 8.0.14.
  - Error number: [MY-013258](#); Symbol: [ER\\_IB\\_MSG\\_SDI\\_Z\\_STREAM\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: SDI Compression failed, Z\_STREAM\_ERROR

---

[ER\\_IB\\_MSG\\_SDI\\_Z\\_STREAM\\_ERROR](#) was added in 8.0.14.

- Error number: [MY-013259](#); Symbol: [ER\\_IB\\_MSG\\_SDI\\_Z\\_UNKNOWN\\_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_SDI\\_Z\\_UNKNOWN\\_ERROR](#) was added in 8.0.14.

- Error number: [MY-013260](#); Symbol: [ER\\_IB\\_MSG\\_FOUND\\_WRONG\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)

Message: Expected to find undo tablespace '%s' for Space ID=%lu, but found '%s' instead! Did you change innodb\_undo\_directory?

[ER\\_IB\\_MSG\\_FOUND\\_WRONG\\_UNDO\\_SPACE](#) was added in 8.0.14.

- Error number: [MY-013261](#); Symbol: [ER\\_IB\\_MSG\\_NOT\\_END\\_WITH\\_IBU](#); SQLSTATE: [HY000](#)

Message: Cannot use %s as an undo tablespace because it does not end with '.ibu'.

[ER\\_IB\\_MSG\\_NOT\\_END\\_WITH\\_IBU](#) was added in 8.0.14.

- Error number: [MY-013262](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNC\\_EMPTY\\_FILE](#); SQLSTATE: [HY000](#)

Message: ib\_undo\_trunc\_empty\_file

[ER\\_IB\\_MSG\\_UNDO\\_TRUNC\\_EMPTY\\_FILE](#) was added in 8.0.14, removed after 8.0.20.

- Error number: [MY-013263](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNC\\_BEFOR\\_DD\\_UPDATE](#); SQLSTATE: [HY000](#)

Message: ib\_undo\_trunc\_before\_dd\_update

[ER\\_IB\\_MSG\\_UNDO\\_TRUNC\\_BEFOR\\_DD\\_UPDATE](#) was added in 8.0.14, removed after 8.0.20.

- Error number: [MY-013264](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNC\\_BEFORE\\_UNDO\\_LOGGING](#); SQLSTATE: [HY000](#)

Message: ib\_undo\_trunc\_before\_done\_logging

[ER\\_IB\\_MSG\\_UNDO\\_TRUNC\\_BEFORE\\_UNDO\\_LOGGING](#) was added in 8.0.14, removed after 8.0.20.

- Error number: [MY-013265](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNC\\_BEFORE\\_RSEG](#); SQLSTATE: [HY000](#)

Message: ib\_undo\_trunc\_before\_rsegs

[ER\\_IB\\_MSG\\_UNDO\\_TRUNC\\_BEFORE\\_RSEG](#) was added in 8.0.14, removed after 8.0.20.

- Error number: [MY-013266](#); Symbol: [ER\\_IB\\_MSG\\_FAILED\\_TO\\_FINISH\\_TRUNCATE](#); SQLSTATE: [HY000](#)

Message: %s Failed to finish truncating Undo Tablespace '%s'

[ER\\_IB\\_MSG\\_FAILED\\_TO\\_FINISH\\_TRUNCATE](#) was added in 8.0.14.

- 
- Error number: `MY-013267`; Symbol: `ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACES`; SQLSTATE: `HY000`  
  
Message: The setting `INNODB_UNDO_TABLESPACES` is deprecated and is no longer used. InnoDB always creates 2 undo tablespaces to start with. If you need more, please use `CREATE UNDO TABLESPACE`.  
  
`ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACES` was added in 8.0.14.
  - Error number: `MY-013268`; Symbol: `ER_IB_MSG_DIR_DOES_NOT_EXIST`; SQLSTATE: `HY000`  
  
Message: The directory '%s' does not exist.  
  
`ER_IB_MSG_DIR_DOES_NOT_EXIST` was added in 8.0.14, removed after 8.0.20.
  - Error number: `MY-013268`; Symbol: `ER_IB_MSG_WRONG_TABLESPACE_DIR`; SQLSTATE: `HY000`  
  
Message: The directory for tablespace %s does not exist or is incorrect.  
  
`ER_IB_MSG_WRONG_TABLESPACE_DIR` was added in 8.0.21.
  - Error number: `MY-013269`; Symbol: `ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS`; SQLSTATE: `HY000`  
  
Message: %s  
  
`ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS` was added in 8.0.14.
  - Error number: `MY-013270`; Symbol: `ER_CLONE_REMOTE_ERROR`; SQLSTATE: `HY000`  
  
Message: Clone Remote Error: %s.  
  
`ER_CLONE_REMOTE_ERROR` was added in 8.0.14, removed after 8.0.16.
  - Error number: `MY-013270`; Symbol: `ER_CLONE_DONOR_TRACE`; SQLSTATE: `HY000`  
  
Message: Clone donor reported : %s.  
  
`ER_CLONE_DONOR_TRACE` was added in 8.0.17.
  - Error number: `MY-013271`; Symbol: `ER_CLONE_PROTOCOL_ERROR`; SQLSTATE: `HY000`  
  
Message: Clone Protocol Error: %s.  
  
`ER_CLONE_PROTOCOL_ERROR` was added in 8.0.14, removed after 8.0.16.
  - Error number: `MY-013271`; Symbol: `ER_CLONE_PROTOCOL_TRACE`; SQLSTATE: `HY000`  
  
Message: Clone received unexpected response from donor : %s.  
  
`ER_CLONE_PROTOCOL_TRACE` was added in 8.0.17.
  - Error number: `MY-013272`; Symbol: `ER_CLONE_INFO_CLIENT`; SQLSTATE: `HY000`  
  
Message: Client: %s.  
  
`ER_CLONE_INFO_CLIENT` was added in 8.0.14, removed after 8.0.16.
  - Error number: `MY-013272`; Symbol: `ER_CLONE_CLIENT_TRACE`; SQLSTATE: `HY000`



---

Message: Client: %s.

[ER\\_CLONE\\_CLIENT\\_TRACE](#) was added in 8.0.17.

- Error number: [MY-013273](#); Symbol: [ER\\_CLONE\\_INFO\\_SERVER](#); SQLSTATE: [HY000](#)

Message: Server: %s.

[ER\\_CLONE\\_INFO\\_SERVER](#) was added in 8.0.14, removed after 8.0.16.

- Error number: [MY-013273](#); Symbol: [ER\\_CLONE\\_SERVER\\_TRACE](#); SQLSTATE: [HY000](#)

Message: Server: %s.

[ER\\_CLONE\\_SERVER\\_TRACE](#) was added in 8.0.17.

- Error number: [MY-013274](#); Symbol: [ER\\_THREAD\\_POOL\\_PFS\\_TABLES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize the performance schema tables service.

[ER\\_THREAD\\_POOL\\_PFS\\_TABLES\\_INIT\\_FAILED](#) was added in 8.0.14.

- Error number: [MY-013275](#); Symbol: [ER\\_THREAD\\_POOL\\_PFS\\_TABLES\\_ADD\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to add thread pool performance schema tables.

[ER\\_THREAD\\_POOL\\_PFS\\_TABLES\\_ADD\\_FAILED](#) was added in 8.0.14.

- Error number: [MY-013276](#); Symbol: [ER\\_CANT\\_SET\\_DATA\\_DIR](#); SQLSTATE: [HY000](#)

Message: Failed to set datadir to '%s' (OS errno: %d - %s)

[ER\\_CANT\\_SET\\_DATA\\_DIR](#) was added in 8.0.14.

- Error number: [MY-013277](#); Symbol: [ER\\_INNODB\\_INVALID\\_INNODB\\_UNDO\\_DIRECTORY\\_LOCATION](#); SQLSTATE: [HY000](#)

Message: The innodb\_undo\_directory is not allowed to be an ancestor of the datadir.

[ER\\_INNODB\\_INVALID\\_INNODB\\_UNDO\\_DIRECTORY\\_LOCATION](#) was added in 8.0.14.

- Error number: [MY-013278](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_FETCH\\_KEY](#); SQLSTATE: [HY000](#)

Message: Failed to fetch key from keyring, please check if keyring is loaded.

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_FETCH\\_KEY](#) was added in 8.0.14.

- Error number: [MY-013279](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_KEY\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_KEY\\_NOT\\_FOUND](#) was added in 8.0.14.

- 
- Error number: `MY-013280`; Symbol: `ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY`; SQLSTATE: `HY000`  
Message: Fetched an invalid key from keyring.  
`ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY` was added in 8.0.14.
  - Error number: `MY-013281`; Symbol: `ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR`; SQLSTATE: `HY000`  
Message: Error reading a replication log encryption header: %s.  
`ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR` was added in 8.0.14.
  - Error number: `MY-013282`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS`; SQLSTATE: `HY000`  
Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.  
`ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS` was added in 8.0.14.
  - Error number: `MY-013283`; Symbol: `ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED`; SQLSTATE: `HY000`  
Message: Key %s exists unexpected.  
`ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED` was added in 8.0.14.
  - Error number: `MY-013284`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY`; SQLSTATE: `HY000`  
Message: Failed to generate key, please check if keyring is loaded.  
`ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY` was added in 8.0.14.
  - Error number: `MY-013285`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY`; SQLSTATE: `HY000`  
Message: Failed to store key, please check if keyring is loaded.  
`ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY` was added in 8.0.14.
  - Error number: `MY-013286`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY`; SQLSTATE: `HY000`  
Message: Failed to remove key, please check if keyring is loaded.  
`ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY` was added in 8.0.14.
  - Error number: `MY-013287`; Symbol: `ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED`; SQLSTATE: `HY000`  
Message: Unable to recover binlog encryption master key, please check if keyring is loaded.  
`ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED` was added in 8.0.14.
  - Error number: `MY-013288`; Symbol: `ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE`; SQLSTATE: `HY000`

---

Message: Failed to initialize binlog encryption, please check if keyring is loaded.

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_UNABLE\\_TO\\_INITIALIZE](#) was added in 8.0.14.

- Error number: [MY-013289](#); Symbol:

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_UNABLE\\_TO\\_ROTATE\\_MASTER\\_KEY\\_AT\\_STARTUP](#); SQLSTATE: HY000

Message: Failed to rotate binlog encryption master key at startup, please check if keyring is loaded.

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_UNABLE\\_TO\\_ROTATE\\_MASTER\\_KEY\\_AT\\_STARTUP](#) was added in 8.0.14.

- Error number: [MY-013290](#); Symbol:

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_IGNORE\\_ROTATE\\_MASTER\\_KEY\\_AT\\_STARTUP](#); SQLSTATE: HY000

Message: Ignoring binlog\_rotate\_encryption\_master\_key\_at\_startup because binlog\_encryption option is disabled.

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_IGNORE\\_ROTATE\\_MASTER\\_KEY\\_AT\\_STARTUP](#) was added in 8.0.14.

- Error number: [MY-013291](#); Symbol: [ER\\_INVALID\\_ADMIN\\_ADDRESS](#); SQLSTATE: HY000

Message: Invalid value for command line option admin-address: '%s'

[ER\\_INVALID\\_ADMIN\\_ADDRESS](#) was added in 8.0.14.

- Error number: [MY-013292](#); Symbol: [ER\\_SERVER\\_STARTUP\\_ADMIN\\_INTERFACE](#); SQLSTATE: HY000

Message: Admin interface ready for connections, address: '%s' port: %d

[ER\\_SERVER\\_STARTUP\\_ADMIN\\_INTERFACE](#) was added in 8.0.14.

- Error number: [MY-013293](#); Symbol: [ER\\_CANT\\_CREATE\\_ADMIN\\_THREAD](#); SQLSTATE: HY000

Message: Can't create thread to handle admin connections (errno= %d)

[ER\\_CANT\\_CREATE\\_ADMIN\\_THREAD](#) was added in 8.0.14.

- Error number: [MY-013294](#); Symbol: [ER\\_WARNING\\_RETAIN\\_CURRENT\\_PASSWORD\\_CLAUSE\\_VOID](#); SQLSTATE: HY000

Message: RETAIN CURRENT PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s does not support multiple passwords.

[ER\\_WARNING\\_RETAIN\\_CURRENT\\_PASSWORD\\_CLAUSE\\_VOID](#) was added in 8.0.14.

- Error number: [MY-013295](#); Symbol: [ER\\_WARNING\\_DISCARD\\_OLD\\_PASSWORD\\_CLAUSE\\_VOID](#); SQLSTATE: HY000

Message: DISCARD OLD PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s does not support multiple passwords.

[ER\\_WARNING\\_DISCARD\\_OLD\\_PASSWORD\\_CLAUSE\\_VOID](#) was added in 8.0.14.

- Error number: [MY-013299](#); Symbol: [ER\\_WARNING\\_AUTHCACHE\\_INVALID\\_USER\\_ATTRIBUTES](#); SQLSTATE: HY000

---

Message: Can not read and process value of User\_attributes column from mysql.user table for user: '%s@%s'; Ignoring user.

[ER\\_WARNING\\_AUTHCACHE\\_INVALID\\_USER\\_ATTRIBUTES](#) was added in 8.0.14.

- Error number: MY-013300; Symbol:  
[ER\\_MYSQL\\_NATIVE\\_PASSWORD\\_SECOND\\_PASSWORD\\_USED\\_INFORMATION](#); SQLSTATE: HY000

Message: Second password was used for login by user: '%s'@'%s'.

[ER\\_MYSQL\\_NATIVE\\_PASSWORD\\_SECOND\\_PASSWORD\\_USED\\_INFORMATION](#) was added in 8.0.14.

- Error number: MY-013301; Symbol:  
[ER\\_SHA256\\_PASSWORD\\_SECOND\\_PASSWORD\\_USED\\_INFORMATION](#); SQLSTATE: HY000

Message: Second password was used for login by user: '%s'@'%s'.

[ER\\_SHA256\\_PASSWORD\\_SECOND\\_PASSWORD\\_USED\\_INFORMATION](#) was added in 8.0.14.

- Error number: MY-013302; Symbol:  
[ER\\_CACHING\\_SHA2\\_PASSWORD\\_SECOND\\_PASSWORD\\_USED\\_INFORMATION](#); SQLSTATE: HY000

Message: Second password was used for login by user: '%s'@'%s'.

[ER\\_CACHING\\_SHA2\\_PASSWORD\\_SECOND\\_PASSWORD\\_USED\\_INFORMATION](#) was added in 8.0.14.

- Error number: MY-013303; Symbol: [ER\\_GRP\\_RPL\\_SEND\\_TRX\\_PREPARED\\_MESSAGE\\_FAILED](#); SQLSTATE: HY000

Message: Error sending transaction '%d:%lld' prepared message from session '%u'.

[ER\\_GRP\\_RPL\\_SEND\\_TRX\\_PREPARED\\_MESSAGE\\_FAILED](#) was added in 8.0.14.

- Error number: MY-013304; Symbol:  
[ER\\_GRP\\_RPL\\_RELEASE\\_COMMIT\\_AFTER\\_GROUP\\_PREPARE\\_FAILED](#); SQLSTATE: HY000

Message: Error releasing transaction '%d:%lld' for commit on session '%u' after being prepared on all group members.

[ER\\_GRP\\_RPL\\_RELEASE\\_COMMIT\\_AFTER\\_GROUP\\_PREPARE\\_FAILED](#) was added in 8.0.14.

- Error number: MY-013305; Symbol:  
[ER\\_GRP\\_RPL\\_TRX\\_ALREADY\\_EXISTS\\_ON\\_TCM\\_ON\\_AFTER\\_CERTIFICATION](#); SQLSTATE: HY000

Message: Transaction '%d:%lld' already exists on Group Replication consistency manager while being registered after conflict detection.

[ER\\_GRP\\_RPL\\_TRX\\_ALREADY\\_EXISTS\\_ON\\_TCM\\_ON\\_AFTER\\_CERTIFICATION](#) was added in 8.0.14.

- Error number: MY-013306; Symbol:  
[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INSERT\\_TRX\\_ON\\_TCM\\_ON\\_AFTER\\_CERTIFICATION](#); SQLSTATE: HY000

Message: Error registering transaction '%d:%lld' on Group Replication consistency manager after conflict detection.

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INSERT\\_TRX\\_ON\\_TCM\\_ON\\_AFTER\\_CERTIFICATION](#) was added in 8.0.14.

- 
- Error number: `MY-013307`; Symbol:  
`ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_PREPARE_FAILED`; SQLSTATE: `HY000`  
  
Message: Error registering transaction '%d:%lld' from session '%u' to wait for being prepared on all group members.  
  
`ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_PREPARE_FAILED` was added in 8.0.14.
  - Error number: `MY-013308`; Symbol: `ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED`; SQLSTATE: `HY000`  
  
Message: Error on transaction '%d:%lld' from session '%u' while waiting for being prepared on all group members.  
  
`ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED` was added in 8.0.14.
  - Error number: `MY-013309`; Symbol:  
`ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLE_REMOTE_PREPARE`; SQLSTATE: `HY000`  
  
Message: Transaction '%d:%lld' does not exist on Group Replication consistency manager while receiving remote transaction prepare.  
  
`ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLE_REMOTE_PREPARE` was added in 8.0.14.
  - Error number: `MY-013310`; Symbol:  
`ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES_COMMIT_FAILED`; SQLSTATE: `HY000`  
  
Message: Error releasing transaction '%d:%lld' for execution on session '%u' after its dependencies did complete commit.  
  
`ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES_COMMIT_FAILED` was added in 8.0.14.
  - Error number: `MY-013311`; Symbol:  
`ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES_FAILED`; SQLSTATE: `HY000`  
  
Message: Error registering transaction from session '%u' to wait for its dependencies to complete commit.  
  
`ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES_FAILED` was added in 8.0.14.
  - Error number: `MY-013312`; Symbol: `ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED`; SQLSTATE: `HY000`  
  
Message: Error on session '%u' while waiting for its dependencies to complete commit.  
  
`ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED` was added in 8.0.14.
  - Error number: `MY-013313`; Symbol:  
`ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED`; SQLSTATE: `HY000`  
  
Message: Error registering transaction from session '%u' to wait for sync before execution.  
  
`ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED` was added in 8.0.14.
  - Error number: `MY-013314`; Symbol: `ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAILED`; SQLSTATE: `HY000`
-

---

Message: Error sending sync before execution message from session '%u'.

[ER\\_GRP\\_RPL\\_SEND\\_TRX\\_SYNC\\_BEFORE\\_EXECUTION\\_FAILED](#) was added in 8.0.14.

- Error number: MY-013315; Symbol: [ER\\_GRP\\_RPL\\_TRX\\_WAIT\\_FOR\\_SYNC\\_BEFORE\\_EXECUTION\\_FAILED](#); SQLSTATE: HY000

Message: Error on transaction from session '%u' while waiting for sync before execution.

[ER\\_GRP\\_RPL\\_TRX\\_WAIT\\_FOR\\_SYNC\\_BEFORE\\_EXECUTION\\_FAILED](#) was added in 8.0.14.

- Error number: MY-013316; Symbol: [ER\\_GRP\\_RPL\\_RELEASE\\_BEGIN\\_TRX\\_AFTER\\_WAIT\\_FOR\\_SYNC\\_BEFORE\\_EXEC](#); SQLSTATE: HY000

Message: Error releasing transaction for execution on session '%u' after wait for sync before execution.

[ER\\_GRP\\_RPL\\_RELEASE\\_BEGIN\\_TRX\\_AFTER\\_WAIT\\_FOR\\_SYNC\\_BEFORE\\_EXEC](#) was added in 8.0.14.

- Error number: MY-013317; Symbol: [ER\\_GRP\\_RPL\\_TRX\\_WAIT\\_FOR\\_GROUP\\_GTID\\_EXECUTED](#); SQLSTATE: HY000

Message: Error waiting for group executed transactions commit on session '%u'.

[ER\\_GRP\\_RPL\\_TRX\\_WAIT\\_FOR\\_GROUP\\_GTID\\_EXECUTED](#) was added in 8.0.14.

- Error number: MY-013320; Symbol: [ER\\_WARN\\_PROPERTY\\_STRING\\_PARSE\\_FAILED](#); SQLSTATE: HY000

Message: Could not parse key-value pairs in property string '%s'

[ER\\_WARN\\_PROPERTY\\_STRING\\_PARSE\\_FAILED](#) was added in 8.0.14.

- Error number: MY-013321; Symbol: [ER\\_INVALID\\_PROPERTY\\_KEY](#); SQLSTATE: HY000

Message: Property key '%s' is invalid.

[ER\\_INVALID\\_PROPERTY\\_KEY](#) was added in 8.0.14.

- Error number: MY-013322; Symbol: [ER\\_GRP\\_RPL\\_GTID\\_SET\\_EXTRACT\\_ERROR\\_DURING\\_RECOVERY](#); SQLSTATE: HY000

Message: Error when extracting the group\_replication\_applier channel received transactions set. Unable to ensure the execution of group transactions received during recovery.

[ER\\_GRP\\_RPL\\_GTID\\_SET\\_EXTRACT\\_ERROR\\_DURING\\_RECOVERY](#) was added in 8.0.14.

- Error number: MY-013323; Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_ENCRYPT](#); SQLSTATE: HY000

Message: Failed to encrypt content to write into binlog file: %s.

[ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_ENCRYPT](#) was added in 8.0.14.

- 
- Error number: `MY-013324`; Symbol: `ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE_HEADER`; SQLSTATE: `HY000`  
Message: Cannot get the server version number from the dictionary tablespace header.  
`ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE_HEADER` was added in 8.0.14.
  - Error number: `MY-013325`; Symbol: `ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE_HEADER`; SQLSTATE: `HY000`  
Message: Cannot set the server version number in the dictionary tablespace header.  
`ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE_HEADER` was added in 8.0.14.
  - Error number: `MY-013326`; Symbol: `ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED`; SQLSTATE: `HY000`  
Message: Upgrading the server from server version '%u' is not supported.  
`ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED` was added in 8.0.14.
  - Error number: `MY-013327`; Symbol: `ER_SERVER_UPGRADE_FROM_VERSION`; SQLSTATE: `HY000`  
Message: MySQL server upgrading from version '%u' to '%u'.  
`ER_SERVER_UPGRADE_FROM_VERSION` was added in 8.0.14.
  - Error number: `MY-013328`; Symbol: `ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL`; SQLSTATE: `HY000`  
Message: The certification information could not be set in this server: '%s'  
`ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL` was added in 8.0.14.
  - Error number: `MY-013329`; Symbol: `ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING`; SQLSTATE: `HY000`  
Message: A request to force a new group membership was issued when the member is leaving the group.  
`ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING` was added in 8.0.14.
  - Error number: `MY-013330`; Symbol: `ER_TRG_WRONG_ORDER`; SQLSTATE: `HY000`  
Message: Trigger %s.%s for table %s.%s is listed in wrong order. Please drop and recreate all triggers for the table.  
`ER_TRG_WRONG_ORDER` was added in 8.0.14.
  - Error number: `MY-013332`; Symbol: `ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL`; SQLSTATE: `HY000`  
Message: Special handling for group search, {GA} not found  
`ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL` was added in 8.0.14.
  - Error number: `MY-013333`; Symbol: `ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO`; SQLSTATE: `HY000`

---

Message: User group retrieval: User object has group information

[ER\\_LDAP\\_AUTH\\_GRP\\_USER\\_OBJECT\\_HAS\\_GROUP\\_INFO](#) was added in 8.0.14.

- Error number: MY-013334; Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_INFO\\_FOUND\\_IN\\_MANY\\_OBJECTS](#); SQLSTATE: HY000

Message: Group information found in multiple user objects. Search filter configuration is incorrect.

[ER\\_LDAP\\_AUTH\\_GRP\\_INFO\\_FOUND\\_IN\\_MANY\\_OBJECTS](#) was added in 8.0.14.

- Error number: MY-013335; Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_INCORRECT\\_ATTRIBUTE](#); SQLSTATE: HY000

Message: User group retrieval: no group attribute found. Incorrect group search attribute.

[ER\\_LDAP\\_AUTH\\_GRP\\_INCORRECT\\_ATTRIBUTE](#) was added in 8.0.14.

- Error number: MY-013336; Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_NULL\\_ATTRIBUTE\\_VALUE](#); SQLSTATE: HY000

Message: User group retrieval: Group attribute values is NULL.

[ER\\_LDAP\\_AUTH\\_GRP\\_NULL\\_ATTRIBUTE\\_VALUE](#) was added in 8.0.14.

- Error number: MY-013337; Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_DN\\_PARSING\\_FAILED](#); SQLSTATE: HY000

Message: User group retrieval: parsing DN failed.

[ER\\_LDAP\\_AUTH\\_GRP\\_DN\\_PARSING\\_FAILED](#) was added in 8.0.14.

- Error number: MY-013338; Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_OBJECT\\_HAS\\_USER\\_INFO](#); SQLSTATE: HY000

Message: User group retrieval: Group object has user information

[ER\\_LDAP\\_AUTH\\_GRP\\_OBJECT\\_HAS\\_USER\\_INFO](#) was added in 8.0.14.

- Error number: MY-013339; Symbol: [ER\\_LDAP\\_AUTH\\_LDAPS](#); SQLSTATE: HY000

Message: Reserved port for ldaps using ldaps

[ER\\_LDAP\\_AUTH\\_LDAPS](#) was added in 8.0.14.

- Error number: MY-013340; Symbol: [ER\\_LDAP\\_MAPPING\\_GET\\_USER\\_PROXY](#); SQLSTATE: HY000

Message: Get user proxy

[ER\\_LDAP\\_MAPPING\\_GET\\_USER\\_PROXY](#) was added in 8.0.14.

- Error number: MY-013341; Symbol: [ER\\_LDAP\\_MAPPING\\_USER\\_DONT\\_BELONG\\_GROUP](#); SQLSTATE: HY000

Message: Get user proxy: User doesn't belongs to any group, user name will be treated as authenticated user.

[ER\\_LDAP\\_MAPPING\\_USER\\_DONT\\_BELONG\\_GROUP](#) was added in 8.0.14.

- Error number: MY-013342; Symbol: [ER\\_LDAP\\_MAPPING\\_INFO](#); SQLSTATE: HY000



---

Message: Get user proxy: configured mapping info: %s

[ER\\_LDAP\\_MAPPING\\_INFO](#) was added in 8.0.14.

- Error number: [MY-013343](#); Symbol: [ER\\_LDAP\\_MAPPING\\_EMPTY\\_MAPPING](#); SQLSTATE: [HY000](#)

Message: Get user proxy: User doesn't have group mapping information, First LDAP group will be treated as authenticated user.

[ER\\_LDAP\\_MAPPING\\_EMPTY\\_MAPPING](#) was added in 8.0.14.

- Error number: [MY-013344](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PROCESS\\_MAPPING](#); SQLSTATE: [HY000](#)

Message: Process group proxy mapping

[ER\\_LDAP\\_MAPPING\\_PROCESS\\_MAPPING](#) was added in 8.0.14.

- Error number: [MY-013345](#); Symbol: [ER\\_LDAP\\_MAPPING\\_CHECK\\_DELIMI\\_QUOTE](#); SQLSTATE: [HY000](#)

Message: Check delimiter after quote

[ER\\_LDAP\\_MAPPING\\_CHECK\\_DELIMI\\_QUOTE](#) was added in 8.0.14.

- Error number: [MY-013346](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER](#); SQLSTATE: [HY000](#)

Message: Processing delimiter

[ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER](#) was added in 8.0.14.

- Error number: [MY-013347](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER\\_EQUAL\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Processing delimiter, separator = not found, resetting position

[ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER\\_EQUAL\\_NOT\\_FOUND](#) was added in 8.0.14.

- Error number: [MY-013348](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER\\_TRY\\_COMMA](#); SQLSTATE: [HY000](#)

Message: "Processing delimiter, failed to get data for = separator try for separator ,"

[ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER\\_TRY\\_COMMA](#) was added in 8.0.14.

- Error number: [MY-013349](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER\\_COMMA\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Processing delimiter, separator , not found, resetting position

[ER\\_LDAP\\_MAPPING\\_PROCESS\\_DELIMITER\\_COMMA\\_NOT\\_FOUND](#) was added in 8.0.14.

- Error number: [MY-013350](#); Symbol: [ER\\_LDAP\\_MAPPING\\_NO\\_SEPEARATOR\\_END\\_OF\\_GROUP](#); SQLSTATE: [HY000](#)

Message: Processing delimiter: No mapping separator is found, end of group information

[ER\\_LDAP\\_MAPPING\\_NO\\_SEPEARATOR\\_END\\_OF\\_GROUP](#) was added in 8.0.14.

- Error number: [MY-013351](#); Symbol: [ER\\_LDAP\\_MAPPING\\_GETTING\\_NEXT\\_MAPPING](#); SQLSTATE: [HY000](#)

---

Message: Getting next mapping information

[ER\\_LDAP\\_MAPPING\\_GETTING\\_NEXT\\_MAPPING](#) was added in 8.0.14.

- Error number: [MY-013352](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PARSING\\_CURRENT\\_STATE](#); SQLSTATE: [HY000](#)

Message: Parsing mapping, current state: %d delimiter char: %c

[ER\\_LDAP\\_MAPPING\\_PARSING\\_CURRENT\\_STATE](#) was added in 8.0.14.

- Error number: [MY-013353](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PARSING\\_MAPPING\\_INFO](#); SQLSTATE: [HY000](#)

Message: Parsing mapping info, LDAP group: %s MySQL proxy: %s

[ER\\_LDAP\\_MAPPING\\_PARSING\\_MAPPING\\_INFO](#) was added in 8.0.14.

- Error number: [MY-013354](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PARSING\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Mapping parsing error

[ER\\_LDAP\\_MAPPING\\_PARSING\\_ERROR](#) was added in 8.0.14.

- Error number: [MY-013355](#); Symbol: [ER\\_LDAP\\_MAPPING\\_TRIMMING\\_SPACES](#); SQLSTATE: [HY000](#)

Message: Trimming left spaces

[ER\\_LDAP\\_MAPPING\\_TRIMMING\\_SPACES](#) was added in 8.0.14.

- Error number: [MY-013356](#); Symbol: [ER\\_LDAP\\_MAPPING\\_IS\\_QUOTE](#); SQLSTATE: [HY000](#)

Message: Checking if current characters is quote

[ER\\_LDAP\\_MAPPING\\_IS\\_QUOTE](#) was added in 8.0.14.

- Error number: [MY-013357](#); Symbol: [ER\\_LDAP\\_MAPPING\\_NON\\_DESIRED\\_STATE](#); SQLSTATE: [HY000](#)

Message: Not desired state or un-defined states.

[ER\\_LDAP\\_MAPPING\\_NON\\_DESIRED\\_STATE](#) was added in 8.0.14.

- Error number: [MY-013358](#); Symbol: [ER\\_INVALID\\_NAMED\\_PIPE\\_FULL\\_ACCESS\\_GROUP](#); SQLSTATE: [HY000](#)

Message: Invalid value for named\_pipe\_full\_access\_group.

[ER\\_INVALID\\_NAMED\\_PIPE\\_FULL\\_ACCESS\\_GROUP](#) was added in 8.0.14.

- Error number: [MY-013359](#); Symbol: [ER\\_PREPARE\\_FOR\\_SECONDARY\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Retry the statement using a secondary storage engine.

[ER\\_PREPARE\\_FOR\\_SECONDARY\\_ENGINE](#) was added in 8.0.16.

- Error number: [MY-013360](#); Symbol: [ER\\_SERVER\\_WARN\\_DEPRECATED](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead

---

`ER_SERVER_WARN_DEPRECATED` was added in 8.0.16.

- Error number: `MY-013361`; Symbol: `ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES`; SQLSTATE: `HY000`

Message: Cannot set mandatory\_roles: AuthId ``%s``@``%s`` has ``%s`' privilege.

`ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES` was added in 8.0.16.

- Error number: `MY-013362`; Symbol: `ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION`; SQLSTATE: `HY000`

Message: Unable to recover binary log master key, the combination of `new_master_key_seqno=%u`, `master_key_seqno=%u` and `old_master_key_seqno=%u` are wrong.

`ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION` was added in 8.0.16.

- Error number: `MY-013363`; Symbol: `ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY`; SQLSTATE: `HY000`

Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

`ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY` was added in 8.0.16.

- Error number: `MY-013368`; Symbol: `ER_TURNING_ON_PARTIAL_REVOKEES`; SQLSTATE: `HY000`

Message: At least one partial revoke exists on a database. Turning ON the system variable '@@partial\_revokes'.

`ER_TURNING_ON_PARTIAL_REVOKEES` was added in 8.0.16.

- Error number: `MY-013369`; Symbol: `ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT`; SQLSTATE: `HY000`

Message: For user '`%s`'@'`%s`', one or more privileges granted through mysql.db for database '`%s`', conflict with partial revoke. It could mean 'mysql' schema is corrupted.

`ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT` was added in 8.0.16.

- Error number: `MY-013370`; Symbol: `ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS`; SQLSTATE: `HY000`

Message: For user `%s`, ignored restrictions for privilege(s) '`%s`' for database '`%s`' as these are not valid database privileges.

`ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS` was added in 8.0.16.

- Error number: `MY-013371`; Symbol: `ER_WARN_INVALID_DB_RESTRICTIONS`; SQLSTATE: `HY000`

Message: For user `%s`, ignored restrictions for privilege(s) '`%s`' for database '`%s`' as corresponding global privilege(s) are not granted.

`ER_WARN_INVALID_DB_RESTRICTIONS` was added in 8.0.16.

- 
- Error number: `MY-013372`; Symbol: `ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL`; SQLSTATE: `HY000`  
Message: '%s' is an invalid value for `group_replication_communication_protocol_join`, please use a MySQL version between 5.7.14 and this server's version  
`ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL` was added in 8.0.16.
  - Error number: `MY-013373`; Symbol: `ER_GRP_RPL_STARTED_AUTO_REJOIN`; SQLSTATE: `HY000`  
Message: Started auto-rejoin procedure attempt %lu of %lu  
`ER_GRP_RPL_STARTED_AUTO_REJOIN` was added in 8.0.16.
  - Error number: `MY-013374`; Symbol: `ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN`; SQLSTATE: `HY000`  
Message: Timeout while waiting for a view change event during the auto-rejoin procedure  
`ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN` was added in 8.0.16.
  - Error number: `MY-013375`; Symbol: `ER_GRP_RPL_FINISHED_AUTO_REJOIN`; SQLSTATE: `HY000`  
Message: Auto-rejoin procedure attempt %lu of %lu finished. Member was%s able to join the group.  
`ER_GRP_RPL_FINISHED_AUTO_REJOIN` was added in 8.0.16.
  - Error number: `MY-013376`; Symbol: `ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_GRP`; SQLSTATE: `HY000`  
Message: The member is configured with a `default_table_encryption` option value '%d' different from the group '%d'. The member will now exit the group.  
`ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_GRP` was added in 8.0.16.
  - Error number: `MY-013377`; Symbol: `ER_SERVER_UPGRADE_OFF`; SQLSTATE: `HY000`  
Message: Server shutting down because upgrade is required, yet prohibited by the command line option '--upgrade=NONE'.  
`ER_SERVER_UPGRADE_OFF` was added in 8.0.16.
  - Error number: `MY-013378`; Symbol: `ER_SERVER_UPGRADE_SKIP`; SQLSTATE: `HY000`  
Message: Server upgrade is required, but skipped by command line option '--upgrade=MINIMAL'.  
`ER_SERVER_UPGRADE_SKIP` was added in 8.0.16.
  - Error number: `MY-013379`; Symbol: `ER_SERVER_UPGRADE_PENDING`; SQLSTATE: `HY000`  
Message: Server upgrade started with version %d, but server upgrade of version %d is still pending.  
`ER_SERVER_UPGRADE_PENDING` was added in 8.0.16.
  - Error number: `MY-013380`; Symbol: `ER_SERVER_UPGRADE_FAILED`; SQLSTATE: `HY000`  
Message: Failed to upgrade server.  
`ER_SERVER_UPGRADE_FAILED` was added in 8.0.16.

- 
- Error number: [MY-013381](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_STATUS](#); SQLSTATE: [HY000](#)  
Message: Server upgrade from '%d' to '%d' %s.  
[ER\\_SERVER\\_UPGRADE\\_STATUS](#) was added in 8.0.16.
  - Error number: [MY-013382](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_REPAIR\\_REQUIRED](#); SQLSTATE: [HY000](#)  
Message: Table '%s' requires repair.  
[ER\\_SERVER\\_UPGRADE\\_REPAIR\\_REQUIRED](#) was added in 8.0.16.
  - Error number: [MY-013383](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_REPAIR\\_STATUS](#); SQLSTATE: [HY000](#)  
Message: Table '%s' repair %s.  
[ER\\_SERVER\\_UPGRADE\\_REPAIR\\_STATUS](#) was added in 8.0.16.
  - Error number: [MY-013384](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_INFO\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Could not open server upgrade info file '%s' for writing. Please make sure the file is writable.  
[ER\\_SERVER\\_UPGRADE\\_INFO\\_FILE](#) was added in 8.0.16.
  - Error number: [MY-013385](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_SYS\\_SCHEMA](#); SQLSTATE: [HY000](#)  
Message: Upgrading the sys schema.  
[ER\\_SERVER\\_UPGRADE\\_SYS\\_SCHEMA](#) was added in 8.0.16.
  - Error number: [MY-013386](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_MYSQL\\_TABLES](#); SQLSTATE: [HY000](#)  
Message: Running queries to upgrade MySQL server.  
[ER\\_SERVER\\_UPGRADE\\_MYSQL\\_TABLES](#) was added in 8.0.16.
  - Error number: [MY-013387](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_SYSTEM\\_TABLES](#); SQLSTATE: [HY000](#)  
Message: Upgrading system table data.  
[ER\\_SERVER\\_UPGRADE\\_SYSTEM\\_TABLES](#) was added in 8.0.16.
  - Error number: [MY-013388](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_EMPTY\\_SYS](#); SQLSTATE: [HY000](#)  
Message: Found empty sys database. Installing the sys schema.  
[ER\\_SERVER\\_UPGRADE\\_EMPTY\\_SYS](#) was added in 8.0.16.
  - Error number: [MY-013389](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_NO\\_SYS\\_VERSION](#); SQLSTATE: [HY000](#)  
Message: A sys schema exists with no sys.version view. If you have a user created sys schema, this must be renamed for the upgrade to succeed.  
[ER\\_SERVER\\_UPGRADE\\_NO\\_SYS\\_VERSION](#) was added in 8.0.16.
  - Error number: [MY-013390](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_SYS\\_VERSION\\_EMPTY](#); SQLSTATE: [HY000](#)  
Message: A sys schema exists with a sys.version view, but it returns no results.

---

`ER_SERVER_UPGRADE_SYS_VERSION_EMPTY` was added in 8.0.16.

- Error number: `MY-013391`; Symbol: `ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED`; SQLSTATE: `HY000`

Message: Found outdated sys schema version %s.

`ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED` was added in 8.0.16.

- Error number: `MY-013392`; Symbol: `ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE`; SQLSTATE: `HY000`

Message: The sys schema is already up to date (version %s).

`ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE` was added in 8.0.16.

- Error number: `MY-013393`; Symbol: `ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT`; SQLSTATE: `HY000`

Message: Found %d sys %s, but expected %d. Re-installing the sys schema.

`ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT` was added in 8.0.16.

- Error number: `MY-013394`; Symbol: `ER_SERVER_UPGRADE_CHECKING_DB`; SQLSTATE: `HY000`

Message: Checking '%s' schema.

`ER_SERVER_UPGRADE_CHECKING_DB` was added in 8.0.16.

- Error number: `MY-013395`; Symbol: `ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT`; SQLSTATE: `HY000`

Message: Too many concurrent transactions while clearing the DDL Log. Please increase the number of Rollback Segments.

`ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT` was added in 8.0.16.

- Error number: `MY-013396`; Symbol: `ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER`; SQLSTATE: `HY000`

Message: Error in DDL Log recovery during Post-Recovery processing.

`ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER` was added in 8.0.16.

- Error number: `MY-013397`; Symbol: `ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT`; SQLSTATE: `HY000`

Message: Error in Post-Tablespace-Encryption during Post-Recovery processing.

`ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT` was added in 8.0.16.

- Error number: `MY-013398`; Symbol: `ER_IB_MSG_DDL_LOG_FAIL_POST_DDL`; SQLSTATE: `HY000`

Message: Error in DDL Log cleanup during Post-DDL processing.

`ER_IB_MSG_DDL_LOG_FAIL_POST_DDL` was added in 8.0.16.

- 
- Error number: `MY-013399`; Symbol: `ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION`; SQLSTATE: `HY000`  
Message: '%s' statement is unsafe because it uses a system function that may return a different value on the replica.  
`ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION` was added in 8.0.16.
  - Error number: `MY-013400`; Symbol: `ER_SERVER_UPGRADE_HELP_TABLE_STATUS`; SQLSTATE: `HY000`  
Message: Upgrade of help tables %s.  
`ER_SERVER_UPGRADE_HELP_TABLE_STATUS` was added in 8.0.16.
  - Error number: `MY-013401`; Symbol: `ER_GRP_RPL_SRV_GTID_WAIT_ERROR`; SQLSTATE: `HY000`  
Message: Error when waiting for the server to execute local transactions in order assure the group change proper logging  
`ER_GRP_RPL_SRV_GTID_WAIT_ERROR` was added in 8.0.16, removed after 8.0.31.
  - Error number: `MY-013402`; Symbol: `ER_GRP_DELAYED_VCLE_LOGGING`; SQLSTATE: `HY000`  
Message: Unable to log the group change View log event in its exaction position in the log. This will not however affect the group replication recovery process or the overall plugin process.  
`ER_GRP_DELAYED_VCLE_LOGGING` was added in 8.0.16, removed after 8.0.31.
  - Error number: `MY-013404`; Symbol: `ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READONLY`; SQLSTATE: `HY000`  
Message: Unable to create a new binlog file: Table `mysql.gtid\_executed` couldn't be opened. %s  
`ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READONLY` was added in 8.0.16.
  - Error number: `MY-013405`; Symbol: `ER_NETWORK_NAMESPACES_NOT_SUPPORTED`; SQLSTATE: `HY000`  
Message: Network Namespaces is not supported on this platform  
`ER_NETWORK_NAMESPACES_NOT_SUPPORTED` was added in 8.0.16.
  - Error number: `MY-013406`; Symbol: `ER_UNKNOWN_NETWORK_NAMESPACE`; SQLSTATE: `HY000`  
Message: Unknown network namespace '%s'  
`ER_UNKNOWN_NETWORK_NAMESPACE` was added in 8.0.16.
  - Error number: `MY-013407`; Symbol: `ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WILDCARD_ADDRESS`; SQLSTATE: `HY000`  
Message: Network namespace not allowed for wildcard interface address  
`ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WILDCARD_ADDRESS` was added in 8.0.16.
  - Error number: `MY-013408`; Symbol: `ER_SETNS_FAILED`; SQLSTATE: `HY000`  
Message: setns() failed with error '%s'

---

`ER_SETNS_FAILED` was added in 8.0.16.

- Error number: `MY-013409`; Symbol: `ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BIND`; SQLSTATE: `HY000`

Message: Wildcard address value not allowed for multivalued bind address

`ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BIND` was added in 8.0.16.

- Error number: `MY-013410`; Symbol: `ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG`; SQLSTATE: `HY000`

Message: The path to a special network namespace file is too long. (got %u > max %u)

`ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG` was added in 8.0.16.

- Error number: `MY-013411`; Symbol: `ER_IB_MSG_TOO_LONG_PATH`; SQLSTATE: `HY000`

Message: Cannot create tablespace '%s'. The filepath is too long for this OS.

`ER_IB_MSG_TOO_LONG_PATH` was added in 8.0.16.

- Error number: `MY-013412`; Symbol: `ER_IB_RECV_FIRST_REC_GROUP_INVALID`; SQLSTATE: `HY000`

Message: The last block of redo had corrupted first\_rec\_group and became fixed (%u -> %u).

`ER_IB_RECV_FIRST_REC_GROUP_INVALID` was added in 8.0.16.

- Error number: `MY-013413`; Symbol: `ER_DD_UPGRADE_COMPLETED`; SQLSTATE: `HY000`

Message: Data dictionary upgrade from version '%u' to '%u' completed.

`ER_DD_UPGRADE_COMPLETED` was added in 8.0.16.

- Error number: `MY-013414`; Symbol: `ER_SSL_SERVER_CERT_VERIFY_FAILED`; SQLSTATE: `HY000`

Message: Server SSL certificate doesn't verify: %s

`ER_SSL_SERVER_CERT_VERIFY_FAILED` was added in 8.0.16.

- Error number: `MY-013415`; Symbol: `ER_PERSIST_OPTION_USER_TRUNCATED`; SQLSTATE: `HY000`

Message: Truncated a user name for %s that was too long while reading the persisted variables file

`ER_PERSIST_OPTION_USER_TRUNCATED` was added in 8.0.16.

- Error number: `MY-013416`; Symbol: `ER_PERSIST_OPTION_HOST_TRUNCATED`; SQLSTATE: `HY000`

Message: Truncated a host name for %s that was too long while reading the persisted variables file

`ER_PERSIST_OPTION_HOST_TRUNCATED` was added in 8.0.16.

- Error number: `MY-013417`; Symbol: `ER_NET_WAIT_ERROR`; SQLSTATE: `HY000`

Message: The wait\_timeout period was exceeded, the idle time since last command was too long.

`ER_NET_WAIT_ERROR` was added in 8.0.16.

- Error number: `MY-013418`; Symbol: `ER_IB_MSG_1285`; SQLSTATE: `HY000`



---

Message: '%s' found not encrypted while '%s' is ON. Trying to encrypt it now.

[ER\\_IB\\_MSG\\_1285](#) was added in 8.0.16.

- Error number: [MY-013419](#); Symbol: [ER\\_IB\\_MSG\\_CLOCK\\_MONOTONIC\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: CLOCK\_MONOTONIC is unsupported, so do not change the system time when MySQL is running !

[ER\\_IB\\_MSG\\_CLOCK\\_MONOTONIC\\_UNSUPPORTED](#) was added in 8.0.16.

- Error number: [MY-013420](#); Symbol: [ER\\_IB\\_MSG\\_CLOCK\\_GETTIME\\_FAILED](#); SQLSTATE: [HY000](#)

Message: clock\_gettime() failed: %s

[ER\\_IB\\_MSG\\_CLOCK\\_GETTIME\\_FAILED](#) was added in 8.0.16.

- Error number: [MY-013421](#); Symbol: [ER\\_PLUGIN\\_NOT\\_EARLY\\_DUP](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.

[ER\\_PLUGIN\\_NOT\\_EARLY\\_DUP](#) was added in 8.0.16.

- Error number: [MY-013422](#); Symbol: [ER\\_PLUGIN\\_NO\\_INSTALL\\_DUP](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.

[ER\\_PLUGIN\\_NO\\_INSTALL\\_DUP](#) was added in 8.0.16.

- Error number: [MY-013425](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_DEFAULT\\_EXPRESSION\\_IN\\_SUBSTATEMENT](#); SQLSTATE: [HY000](#)

Message: The statement is unsafe because it invokes a trigger or a stored function that modifies a table that has a column with a DEFAULT expression that may return a different value on the replica.

[ER\\_BINLOG\\_UNSAFE\\_DEFAULT\\_EXPRESSION\\_IN\\_SUBSTATEMENT](#) was added in 8.0.16.

- Error number: [MY-013426](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_VER\\_READ\\_COMPATIBLE](#); SQLSTATE: [HY000](#)

Message: Member version is read compatible with the group.

[ER\\_GRP\\_RPL\\_MEMBER\\_VER\\_READ\\_COMPATIBLE](#) was added in 8.0.16.

- Error number: [MY-013427](#); Symbol: [ER\\_LOCK\\_ORDER\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Lock order disabled (reason: init failed).

[ER\\_LOCK\\_ORDER\\_INIT\\_FAILED](#) was added in 8.0.16.

- Error number: [MY-013428](#); Symbol: [ER\\_AUDIT\\_LOG\\_KEYRING\\_ID\\_TIMESTAMP\\_VALUE\\_IS\\_INVALID](#); SQLSTATE: [HY000](#)

Message: Keyring ID timestamp value is invalid: '%s'

[ER\\_AUDIT\\_LOG\\_KEYRING\\_ID\\_TIMESTAMP\\_VALUE\\_IS\\_INVALID](#) was added in 8.0.16.

- 
- Error number: MY-013429; Symbol: ER\_AUDIT\_LOG\_FILE\_NAME\_TIMESTAMP\_VALUE\_IS\_MISSING\_OR\_INVALID; SQLSTATE: HY000  
Message: Cannot process audit log file. File name timestamp value is missing or invalid: '%s'  
ER\_AUDIT\_LOG\_FILE\_NAME\_TIMESTAMP\_VALUE\_IS\_MISSING\_OR\_INVALID was added in 8.0.16.
  - Error number: MY-013430; Symbol: ER\_AUDIT\_LOG\_FILE\_NAME\_DOES\_NOT\_HAVE\_REQUIRED\_FORMAT; SQLSTATE: HY000  
Message: Cannot process audit log file. File name does not have required format: '%s'  
ER\_AUDIT\_LOG\_FILE\_NAME\_DOES\_NOT\_HAVE\_REQUIRED\_FORMAT was added in 8.0.16.
  - Error number: MY-013431; Symbol: ER\_AUDIT\_LOG\_FILE\_NAME\_KEYRING\_ID\_VALUE\_IS\_MISSING; SQLSTATE: HY000  
Message: Cannot process audit log file. File name keyring ID value is missing: '%s'  
ER\_AUDIT\_LOG\_FILE\_NAME\_KEYRING\_ID\_VALUE\_IS\_MISSING was added in 8.0.16.
  - Error number: MY-013432; Symbol: ER\_AUDIT\_LOG\_FILE\_HAS\_BEEN\_SUCCESSFULLY\_PROCESSED; SQLSTATE: HY000  
Message: Audit log file has been successfully processed: '%s'  
ER\_AUDIT\_LOG\_FILE\_HAS\_BEEN\_SUCCESSFULLY\_PROCESSED was added in 8.0.16.
  - Error number: MY-013433; Symbol: ER\_AUDIT\_LOG\_COULD\_NOT\_OPEN\_FILE\_FOR\_READING; SQLSTATE: HY000  
Message: Could not open audit log file for reading: '%s'  
ER\_AUDIT\_LOG\_COULD\_NOT\_OPEN\_FILE\_FOR\_READING was added in 8.0.16.
  - Error number: MY-013434; Symbol: ER\_AUDIT\_LOG\_INVALID\_FILE\_CONTENT; SQLSTATE: HY000  
Message: Invalid audit log file content: '%s'  
ER\_AUDIT\_LOG\_INVALID\_FILE\_CONTENT was added in 8.0.16.
  - Error number: MY-013435; Symbol: ER\_AUDIT\_LOG\_CANNOT\_READ\_PASSWORD; SQLSTATE: HY000  
Message: Cannot read password: '%s'.  
ER\_AUDIT\_LOG\_CANNOT\_READ\_PASSWORD was added in 8.0.16.
  - Error number: MY-013436; Symbol: ER\_AUDIT\_LOG\_CANNOT\_STORE\_PASSWORD; SQLSTATE: HY000  
Message: Cannot store password: '%s'.  
ER\_AUDIT\_LOG\_CANNOT\_STORE\_PASSWORD was added in 8.0.16.
  - Error number: MY-013437; Symbol: ER\_AUDIT\_LOG\_CANNOT\_REMOVE\_PASSWORD; SQLSTATE: HY000  
Message: Cannot remove password: '%s'.  
ER\_AUDIT\_LOG\_CANNOT\_REMOVE\_PASSWORD was added in 8.0.16.

- 
- Error number: [MY-013438](#); Symbol: [ER\\_AUDIT\\_LOG\\_PASSWORD\\_HAS\\_BEEN\\_COPIED](#); SQLSTATE: [HY000](#)  
Message: 'audit\_log' password has been copied into '%s' and will be removed with first purged password.  
[ER\\_AUDIT\\_LOG\\_PASSWORD\\_HAS\\_BEEN\\_COPIED](#) was added in 8.0.16.
  - Error number: [MY-013447](#); Symbol: [ER\\_LDAP\\_EMPTY\\_USERDN\\_PASSWORD](#); SQLSTATE: [HY000](#)  
Message: Empty user dn or password is not allowed, not attempting LDAP bind.  
[ER\\_LDAP\\_EMPTY\\_USERDN\\_PASSWORD](#) was added in 8.0.16.
  - Error number: [MY-013449](#); Symbol: [ER\\_ACL\\_WRONG\\_OR\\_MISSING\\_ACL\\_TABLES\\_LOG](#); SQLSTATE: [HY000](#)  
Message: The current layout of the ACL tables does not conform to the server's expected layout. They're either altered, missing or not upgraded from a previous version. However a best effort attempt to read data from these tables will still be made.  
[ER\\_ACL\\_WRONG\\_OR\\_MISSING\\_ACL\\_TABLES\\_LOG](#) was added in 8.0.17.
  - Error number: [MY-013450](#); Symbol: [ER\\_LOCK\\_ORDER\\_FAILED\\_WRITE\\_FILE](#); SQLSTATE: [HY000](#)  
Message: LOCK\_ORDER: Failed to write to file <%s>.  
[ER\\_LOCK\\_ORDER\\_FAILED\\_WRITE\\_FILE](#) was added in 8.0.17.
  - Error number: [MY-013451](#); Symbol: [ER\\_LOCK\\_ORDER\\_FAILED\\_READ\\_FILE](#); SQLSTATE: [HY000](#)  
Message: LOCK\_ORDER: Failed to read from file <%s>.  
[ER\\_LOCK\\_ORDER\\_FAILED\\_READ\\_FILE](#) was added in 8.0.17.
  - Error number: [MY-013452](#); Symbol: [ER\\_LOCK\\_ORDER\\_MESSAGE](#); SQLSTATE: [HY000](#)  
Message: LOCK\_ORDER message: %s  
[ER\\_LOCK\\_ORDER\\_MESSAGE](#) was added in 8.0.17.
  - Error number: [MY-013453](#); Symbol: [ER\\_LOCK\\_ORDER\\_DEPENDENCIES\\_SYNTAX](#); SQLSTATE: [HY000](#)  
Message: Lock order dependencies file <%s> (%d:%d) - (%d:%d) : %s  
[ER\\_LOCK\\_ORDER\\_DEPENDENCIES\\_SYNTAX](#) was added in 8.0.17.
  - Error number: [MY-013454](#); Symbol: [ER\\_LOCK\\_ORDER\\_SCANNER\\_SYNTAX](#); SQLSTATE: [HY000](#)  
Message: Lock order scanner: (%d:%d) - (%d:%d) : %s  
[ER\\_LOCK\\_ORDER\\_SCANNER\\_SYNTAX](#) was added in 8.0.17.
  - Error number: [MY-013455](#); Symbol: [ER\\_DATA\\_DIRECTORY\\_UNUSABLE\\_DELETABLE](#); SQLSTATE: [HY000](#)  
Message: The newly created data directory %s by --initialize is unusable. You can remove it.  
[ER\\_DATA\\_DIRECTORY\\_UNUSABLE\\_DELETABLE](#) was added in 8.0.17.
-

- 
- Error number: [MY-013456](#); Symbol: [ER\\_IB\\_MSG\\_BTREE\\_LEVEL\\_LIMIT\\_EXCEEDED](#); SQLSTATE: [HY000](#)  
  
Message: No. of B-tree level created for index %s has crossed the permissible limit. If debug option innodb\_limit\_optimistic\_insert\_debug is being used try tweaking it to include more records in a page.  
  
[ER\\_IB\\_MSG\\_BTREE\\_LEVEL\\_LIMIT\\_EXCEEDED](#) was added in 8.0.17.
  - Error number: [MY-013457](#); Symbol: [ER\\_IB\\_CLONE\\_START\\_STOP](#); SQLSTATE: [HY000](#)  
  
Message: %s  
  
[ER\\_IB\\_CLONE\\_START\\_STOP](#) was added in 8.0.17.
  - Error number: [MY-013458](#); Symbol: [ER\\_IB\\_CLONE\\_OPERATION](#); SQLSTATE: [HY000](#)  
  
Message: %s  
  
[ER\\_IB\\_CLONE\\_OPERATION](#) was added in 8.0.17.
  - Error number: [MY-013459](#); Symbol: [ER\\_IB\\_CLONE\\_RESTART](#); SQLSTATE: [HY000](#)  
  
Message: %s  
  
[ER\\_IB\\_CLONE\\_RESTART](#) was added in 8.0.17.
  - Error number: [MY-013460](#); Symbol: [ER\\_IB\\_CLONE\\_USER\\_DATA](#); SQLSTATE: [HY000](#)  
  
Message: Clone removing all user data for provisioning: %s  
  
[ER\\_IB\\_CLONE\\_USER\\_DATA](#) was added in 8.0.17.
  - Error number: [MY-013461](#); Symbol: [ER\\_IB\\_CLONE\\_NON\\_INNODB\\_TABLE](#); SQLSTATE: [HY000](#)  
  
Message: Non innodb table: %s.%s is not cloned and is empty.  
  
[ER\\_IB\\_CLONE\\_NON\\_INNODB\\_TABLE](#) was added in 8.0.17.
  - Error number: [MY-013462](#); Symbol: [ER\\_CLONE\\_SHUTDOWN\\_TRACE](#); SQLSTATE: [HY000](#)  
  
Message: Clone shutting down server as RESTART failed. Please start server to complete clone operation.  
  
[ER\\_CLONE\\_SHUTDOWN\\_TRACE](#) was added in 8.0.17.
  - Error number: [MY-013463](#); Symbol: [ER\\_GRP\\_RPL\\_GTID\\_PURGED\\_EXTRACT\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error when extracting this member GTID purged set. Operations and checks made to group joiners may be incomplete.  
  
[ER\\_GRP\\_RPL\\_GTID\\_PURGED\\_EXTRACT\\_ERROR](#) was added in 8.0.17.
  - Error number: [MY-013464](#); Symbol: [ER\\_GRP\\_RPL\\_CLONE\\_PROCESS\\_PREPARE\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: There was an issue when configuring the remote cloning process: %s  
  
[ER\\_GRP\\_RPL\\_CLONE\\_PROCESS\\_PREPARE\\_ERROR](#) was added in 8.0.17.

- 
- Error number: [MY-013465](#); Symbol: [ER\\_GRP\\_RPL\\_CLONE\\_PROCESS\\_EXEC\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: There was an issue when cloning from another server: %s  
  
[ER\\_GRP\\_RPL\\_CLONE\\_PROCESS\\_EXEC\\_ERROR](#) was added in 8.0.17.
  - Error number: [MY-013466](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_EVAL\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: There was an issue when trying to evaluate the best distributed recovery strategy while joining.%s  
  
[ER\\_GRP\\_RPL\\_RECOVERY\\_EVAL\\_ERROR](#) was added in 8.0.17.
  - Error number: [MY-013467](#); Symbol: [ER\\_GRP\\_RPL\\_NO\\_POSSIBLE\\_RECOVERY](#); SQLSTATE: [HY000](#)  
  
Message: No valid or ONLINE members exist to get the missing data from the group. For cloning check if donors of the same version and with clone plugin installed exist. For incremental recovery check if you have donors where the required data was not purged from the binary logs.  
  
[ER\\_GRP\\_RPL\\_NO\\_POSSIBLE\\_RECOVERY](#) was added in 8.0.17.
  - Error number: [MY-013468](#); Symbol: [ER\\_GRP\\_RPL\\_CANT\\_KILL\\_THREAD](#); SQLSTATE: [HY000](#)  
  
Message: The group replication plugin could not kill the plugin routine for %s. %s  
  
[ER\\_GRP\\_RPL\\_CANT\\_KILL\\_THREAD](#) was added in 8.0.17.
  - Error number: [MY-013469](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_CLONE\\_THRESHOLD](#); SQLSTATE: [HY000](#)  
  
Message: This member will start distributed recovery using clone. It is due to the number of missing transactions being higher than the configured threshold of %llu.  
  
[ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_CLONE\\_THRESHOLD](#) was added in 8.0.17.
  - Error number: [MY-013470](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_CLONE\\_PURGED](#); SQLSTATE: [HY000](#)  
  
Message: This member will start distributed recovery using clone. It is due to no ONLINE member has the missing data for recovering in its binary logs.  
  
[ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_CLONE\\_PURGED](#) was added in 8.0.17.
  - Error number: [MY-013471](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_CHOICE](#); SQLSTATE: [HY000](#)  
  
Message: Distributed recovery will transfer data using: %s  
  
[ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_CHOICE](#) was added in 8.0.17.
  - Error number: [MY-013472](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_FALLBACK](#); SQLSTATE: [HY000](#)  
  
Message: Due to some issue on the previous step distributed recovery is now executing: %s  
  
[ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_FALLBACK](#) was added in 8.0.17.
  - Error number: [MY-013473](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_NO\\_FALLBACK](#); SQLSTATE: [HY000](#)

---

Message: Due to a critical cloning error or lack of donors, distributed recovery cannot be executed. The member will now leave the group.

[ER\\_GRP\\_RPL\\_RECOVERY\\_STRAT\\_NO\\_FALLBACK](#) was added in 8.0.17.

- Error number: [MY-013474](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_THREAD\\_ERROR\\_ON\\_CLONE](#); SQLSTATE: [HY000](#)

Message: The '%s' thread of channel '%s' will error out as the server will attempt to clone another server

[ER\\_GRP\\_RPL\\_SLAVE\\_THREAD\\_ERROR\\_ON\\_CLONE](#) was added in 8.0.17, removed after 8.0.32.

- Error number: [MY-013474](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_THREAD\\_ERROR\\_ON\\_CLONE](#); SQLSTATE: [HY000](#)

Message: The '%s' thread of channel '%s' will error out as the server will attempt to clone another server

[ER\\_GRP\\_RPL\\_REPLICA\\_THREAD\\_ERROR\\_ON\\_CLONE](#) was added in 8.0.33.

- Error number: [MY-013475](#); Symbol: [ER\\_UNKNOWN\\_TABLE\\_IN\\_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Unknown table '%s'

[ER\\_UNKNOWN\\_TABLE\\_IN\\_UPGRADE](#) was added in 8.0.17.

- Error number: [MY-013476](#); Symbol: [ER\\_IDENT\\_CAUSES\\_TOO\\_LONG\\_PATH\\_IN\\_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.

[ER\\_IDENT\\_CAUSES\\_TOO\\_LONG\\_PATH\\_IN\\_UPGRADE](#) was added in 8.0.17.

- Error number: [MY-013477](#); Symbol: [ER\\_XA\\_CANT\\_CREATE\\_MDL\\_BACKUP](#); SQLSTATE: [HY000](#)

Message: XA: Failed to take MDL Lock backup of PREPARED XA transaction during client disconnect.

[ER\\_XA\\_CANT\\_CREATE\\_MDL\\_BACKUP](#) was added in 8.0.13.

- Error number: [MY-013478](#); Symbol: [ER\\_AUDIT\\_LOG\\_SUPER\\_PRIVILEGE\\_REQUIRED](#); SQLSTATE: [HY000](#)

Message: SUPER privilege or AUDIT\_ADMIN role required for '%s'@'%s' user.

[ER\\_AUDIT\\_LOG\\_SUPER\\_PRIVILEGE\\_REQUIRED](#) was added in 8.0.11.

- Error number: [MY-013479](#); Symbol: [ER\\_AUDIT\\_LOG\\_UDF\\_INVALID\\_ARGUMENT\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Invalid argument type

[ER\\_AUDIT\\_LOG\\_UDF\\_INVALID\\_ARGUMENT\\_TYPE](#) was added in 8.0.11.

- 
- Error number: [MY-013480](#); Symbol: [ER\\_AUDIT\\_LOG\\_UDF\\_INVALID\\_ARGUMENT\\_COUNT](#); SQLSTATE: [HY000](#)  
  
Message: Invalid argument count  
  
[ER\\_AUDIT\\_LOG\\_UDF\\_INVALID\\_ARGUMENT\\_COUNT](#) was added in 8.0.11.
  - Error number: [MY-013481](#); Symbol: [ER\\_AUDIT\\_LOG\\_HAS\\_NOT\\_BEEN\\_INSTALLED](#); SQLSTATE: [HY000](#)  
  
Message: audit\_log plugin has not been installed using INSTALL PLUGIN syntax.  
  
[ER\\_AUDIT\\_LOG\\_HAS\\_NOT\\_BEEN\\_INSTALLED](#) was added in 8.0.11.
  - Error number: [MY-013482](#); Symbol: [ER\\_AUDIT\\_LOG\\_UDF\\_READ\\_INVALID\\_MAX\\_ARRAY\\_LENGTH\\_ARG\\_TYPE](#); SQLSTATE: [HY000](#)  
  
Message: Invalid "max\_array\_length" argument type.  
  
[ER\\_AUDIT\\_LOG\\_UDF\\_READ\\_INVALID\\_MAX\\_ARRAY\\_LENGTH\\_ARG\\_TYPE](#) was added in 8.0.11.
  - Error number: [MY-013483](#); Symbol: [ER\\_LOG\\_CANNOT\\_WRITE\\_EXTENDED](#); SQLSTATE: [HY000](#)  
  
Message: Failed to write to %s: %s (%s)  
  
[ER\\_LOG\\_CANNOT\\_WRITE\\_EXTENDED](#) was added in 8.0.17.
  - Error number: [MY-013484](#); Symbol: [ER\\_UPGRADE\\_WITH\\_PARTITIONED\\_TABLES\\_REJECTED](#); SQLSTATE: [HY000](#)  
  
Message: Upgrading from server version %d with partitioned tables and lower\_case\_table\_names == 1 on a case sensitive file system may cause issues, and is therefore prohibited. To upgrade anyway, restart the new server version with the command line option 'upgrade=FORCE'. When upgrade is completed, please execute 'RENAME TABLE <part\_table\_name> TO <new\_table\_name>; RENAME TABLE <new\_table\_name> TO <part\_table\_name>;' for each of the partitioned tables. Please see the documentation for further information.  
  
[ER\\_UPGRADE\\_WITH\\_PARTITIONED\\_TABLES\\_REJECTED](#) was added in 8.0.17, removed after 8.0.18.
  - Error number: [MY-013485](#); Symbol: [ER\\_KEYRING\\_AWS\\_INCORRECT\\_PROXY](#); SQLSTATE: [HY000](#)  
  
Message: Incorrect environment variable %s, invalid port: %s  
  
[ER\\_KEYRING\\_AWS\\_INCORRECT\\_PROXY](#) was added in 8.0.18.
  - Error number: [MY-013486](#); Symbol: [ER\\_GRP\\_RPL\\_SERVER\\_SET\\_TO\\_OFFLINE\\_MODE\\_DUE\\_TO\\_ERRORS](#); SQLSTATE: [HY000](#)  
  
Message: The server was automatically set into offline mode after an error was detected.  
  
[ER\\_GRP\\_RPL\\_SERVER\\_SET\\_TO\\_OFFLINE\\_MODE\\_DUE\\_TO\\_ERRORS](#) was added in 8.0.18.
  - Error number: [MY-013487](#); Symbol: [ER\\_GRP\\_RPL\\_MESSAGE\\_SERVICE\\_FATAL\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: A message sent through the Group Replication message deliver service was not delivered successfully. The server will now leave the group. Try to add the server back to the group and check if the problem persists, or check previous messages in the log for hints of what could be the problem.
-

---

`ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR` was added in 8.0.18.

- Error number: `MY-013488`; Symbol: `ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG`; SQLSTATE: `HY000`

Message: Invalid `SOURCE_COMPRESSION_ALGORITHMS` '%s' found in repository for channel '%s'. Resetting to 'uncompressed' (no compression).

`ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG` was added in 8.0.18.

- Error number: `MY-013489`; Symbol: `ER_WARN_WRONG_COMPRESSION_LEVEL_LOG`; SQLSTATE: `HY000`

Message: Invalid `SOURCE_ZSTD_COMPRESSION_LEVEL` found in repository for channel '%s'. Resetting to %u.

`ER_WARN_WRONG_COMPRESSION_LEVEL_LOG` was added in 8.0.18.

- Error number: `MY-013490`; Symbol: `ER_PROTOCOL_COMPRESSION_RESET_LOG`; SQLSTATE: `HY000`

Message: Option `--protocol-compression-algorithms` is reset to default value.

`ER_PROTOCOL_COMPRESSION_RESET_LOG` was added in 8.0.18.

- Error number: `MY-013491`; Symbol: `ER_XPLUGIN_COMPRESSION_ERROR`; SQLSTATE: `HY000`

Message: Fatal error while compressing outgoing data - %s

`ER_XPLUGIN_COMPRESSION_ERROR` was added in 8.0.18.

- Error number: `MY-013492`; Symbol: `ER_MYSQLBACKUP_MSG`; SQLSTATE: `HY000`

Message: %s

`ER_MYSQLBACKUP_MSG` was added in 8.0.18.

- Error number: `MY-013493`; Symbol: `ER_WARN_UNKNOWN_KEYRING_AWS_REGION`; SQLSTATE: `HY000`

Message: Unknown keyring\_aws\_region '%s'. Connection to AWS KMS may fail.

`ER_WARN_UNKNOWN_KEYRING_AWS_REGION` was added in 8.0.18.

- Error number: `MY-013494`; Symbol: `ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST`; SQLSTATE: `HY000`

Message: `PRIVILEGE_CHECKS_USER` for replication channel '%s' was set to ``%s`@`%s``, but this is not an existing user. Correct this before starting replication threads.

`ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST` was added in 8.0.18.

- Error number: `MY-013495`; Symbol: `ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT`; SQLSTATE: `HY000`

Message: Invalid, corrupted `PRIVILEGE_CHECKS_USER` was found in the replication configuration repository for channel '%s'. Use `CHANGE REPLICATION SOURCE TO PRIVILEGE_CHECKS_USER` to correct the configuration.

`ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT` was added in 8.0.18.



- 
- Error number: [MY-013496](#); Symbol: [ER\\_WARN\\_LOG\\_PRIVILEGE\\_CHECKS\\_USER\\_NEEDS\\_RPL\\_APPLIER\\_PRIV](#); SQLSTATE: HY000  
Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' was set to '%s'@'%s', but this user does not have REPLICATION\_APPLIER privilege. Correct this before starting the replication threads.  
[ER\\_WARN\\_LOG\\_PRIVILEGE\\_CHECKS\\_USER\\_NEEDS\\_RPL\\_APPLIER\\_PRIV](#) was added in 8.0.18.
  - Error number: [MY-013497](#); Symbol: [ER\\_FILE\\_PRIVILEGE\\_FOR\\_REPLICATION\\_CHECKS](#); SQLSTATE: HY000  
Message: The PRIVILEGE\_CHECKS\_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using binlog\_format=ROW on master. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE\_CHECKS\_USER.  
[ER\\_FILE\\_PRIVILEGE\\_FOR\\_REPLICATION\\_CHECKS](#) was added in 8.0.18, removed after 8.0.30.
  - Error number: [MY-013497](#); Symbol: [ER\\_OBSOLETE\\_FILE\\_PRIVILEGE\\_FOR\\_REPLICATION\\_CHECKS](#); SQLSTATE: HY000  
Message: The PRIVILEGE\_CHECKS\_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using binlog\_format=ROW on source. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE\_CHECKS\_USER.  
[ER\\_OBSOLETE\\_FILE\\_PRIVILEGE\\_FOR\\_REPLICATION\\_CHECKS](#) was added in 8.0.31.
  - Error number: [MY-013498](#); Symbol: [ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_STARTING\\_WITH\\_PRIVILEGE\\_CHECKS](#); SQLSTATE: HY000  
Message: Slave SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s, user: '%s'@'%s', roles: %s  
[ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_STARTING\\_WITH\\_PRIVILEGE\\_CHECKS](#) was added in 8.0.18, removed after 8.0.32.
  - Error number: [MY-013498](#); Symbol: [ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_STARTING\\_WITH\\_PRIVILEGE\\_CHECKS](#); SQLSTATE: HY000  
Message: Replica SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s, user: '%s'@'%s', roles: %s  
[ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_STARTING\\_WITH\\_PRIVILEGE\\_CHECKS](#) was added in 8.0.33.
  - Error number: [MY-013499](#); Symbol: [ER\\_AUDIT\\_LOG\\_CANNOT\\_GENERATE\\_PASSWORD](#); SQLSTATE: HY000  
Message: Cannot generate password: '%s'  
[ER\\_AUDIT\\_LOG\\_CANNOT\\_GENERATE\\_PASSWORD](#) was added in 8.0.18.
  - Error number: [MY-013500](#); Symbol: [ER\\_INIT\\_FAILED\\_TO\\_GENERATE\\_ROOT\\_PASSWORD](#); SQLSTATE: HY000  
Message: Failed to generate a random password for root. Probabably not enough entropy.  
[ER\\_INIT\\_FAILED\\_TO\\_GENERATE\\_ROOT\\_PASSWORD](#) was added in 8.0.18.
-

- 
- Error number: [MY-013501](#); Symbol: [ER\\_PLUGIN\\_LOAD\\_OPTIONS\\_IGNORED](#); SQLSTATE: [HY000](#)  
Message: Ignoring --plugin-load[\_add] list as the server is running with --initialize(-insecure).  
[ER\\_PLUGIN\\_LOAD\\_OPTIONS\\_IGNORED](#) was added in 8.0.18.
  - Error number: [MY-013502](#); Symbol: [ER\\_WARN\\_AUTH\\_ID\\_WITH\\_SYSTEM\\_USER\\_PRIV\\_IN\\_MANDATORY\\_ROLES](#); SQLSTATE: [HY000](#)  
Message: Cannot set mandatory\_roles: AuthId `[%s](#)`@`[%s](#)` has '[%s](#)' privilege. AuthId(s) set in the mandatory\_roles are ignored.  
[ER\\_WARN\\_AUTH\\_ID\\_WITH\\_SYSTEM\\_USER\\_PRIV\\_IN\\_MANDATORY\\_ROLES](#) was added in 8.0.18.
  - Error number: [MY-013503](#); Symbol: [ER\\_IB\\_MSG\\_SKIP\\_HIDDEN\\_DIR](#); SQLSTATE: [HY000](#)  
Message: Directory '[%s](#)' will not be scanned because it is a hidden directory.  
[ER\\_IB\\_MSG\\_SKIP\\_HIDDEN\\_DIR](#) was added in 8.0.18.
  - Error number: [MY-013504](#); Symbol: [ER\\_WARN\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_MASTER\\_EOF](#); SQLSTATE: [HY000](#)  
Message: Server was not able to find a rotate event from master server to initialize relay log recovery for channel '[%s](#)'. Skipping relay log recovery for the channel.  
[ER\\_WARN\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_MASTER\\_EOF](#) was added in 8.0.19, removed after 8.0.32.
  - Error number: [MY-013504](#); Symbol: [ER\\_WARN\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_SOURCE\\_EOF](#); SQLSTATE: [HY000](#)  
Message: Server was not able to find a rotate event from source server to initialize relay log recovery for channel '[%s](#)'. Skipping relay log recovery for the channel.  
[ER\\_WARN\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_SOURCE\\_EOF](#) was added in 8.0.33.
  - Error number: [MY-013505](#); Symbol: [ER\\_IB\\_LOB\\_ROLLBACK\\_INDEX\\_LEN](#); SQLSTATE: [HY000](#)  
Message: Rolling back LOB for transaction [%llu](#) undo number [%llu](#) : current index length [%llu](#). (iteration [%llu](#))  
[ER\\_IB\\_LOB\\_ROLLBACK\\_INDEX\\_LEN](#) was added in 8.0.19.
  - Error number: [MY-013506](#); Symbol: [ER\\_CANT\\_PROCESS\\_EXPRESSION\\_FOR\\_GENERATED\\_COLUMN\\_TO\\_DD](#); SQLSTATE: [HY000](#)  
Message: Error in processing (possibly deprecated) expression or function '[%s](#)' for generated column [%s.%s.%s](#)  
[ER\\_CANT\\_PROCESS\\_EXPRESSION\\_FOR\\_GENERATED\\_COLUMN\\_TO\\_DD](#) was added in 8.0.19.

- 
- Error number: [MY-013507](#); Symbol: [ER\\_RPL\\_SLAVE\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_NON\\_ROW\\_FORMAT](#); SQLSTATE: [HY000](#)  
Message: The queue event failed for channel '%s' as an invalid event according to REQUIRE\_ROW\_FORMAT was found.  
[ER\\_RPL\\_SLAVE\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_NON\\_ROW\\_FORMAT](#) was added in 8.0.19, removed after 8.0.32.
  - Error number: [MY-013507](#); Symbol: [ER\\_RPL\\_REPLICA\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_NON\\_ROW\\_FORMAT](#); SQLSTATE: [HY000](#)  
Message: The queue event failed for channel '%s' as an invalid event according to REQUIRE\_ROW\_FORMAT was found.  
[ER\\_RPL\\_REPLICA\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_NON\\_ROW\\_FORMAT](#) was added in 8.0.33.
  - Error number: [MY-013508](#); Symbol: [ER\\_RPL\\_SLAVE\\_APPLY\\_LOG\\_EVENT\\_FAILED\\_INVALID\\_NON\\_ROW\\_FORMAT](#); SQLSTATE: [HY000](#)  
Message: The application of relay events failed for channel '%s' as an invalid event according to REQUIRE\_ROW\_FORMAT was found.  
[ER\\_RPL\\_SLAVE\\_APPLY\\_LOG\\_EVENT\\_FAILED\\_INVALID\\_NON\\_ROW\\_FORMAT](#) was added in 8.0.19, removed after 8.0.30.
  - Error number: [MY-013508](#); Symbol: [ER\\_OBSOLETE\\_REQUIRE\\_ROW\\_FORMAT\\_VIOLATION](#); SQLSTATE: [HY000](#)  
Message: The application of relay events failed for channel '%s' as an invalid event according to REQUIRE\_ROW\_FORMAT was found.  
[ER\\_OBSOLETE\\_REQUIRE\\_ROW\\_FORMAT\\_VIOLATION](#) was added in 8.0.31.
  - Error number: [MY-013509](#); Symbol: [ER\\_LOG\\_PRIV\\_CHECKS\\_REQUIRE\\_ROW\\_FORMAT\\_NOT\\_SET](#); SQLSTATE: [HY000](#)  
Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' can't be set to `'%s`@`%s` unless REQUIRE\_ROW\_FORMAT is also set to %d.  
[ER\\_LOG\\_PRIV\\_CHECKS\\_REQUIRE\\_ROW\\_FORMAT\\_NOT\\_SET](#) was added in 8.0.19.
  - Error number: [MY-013510](#); Symbol: [ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#); SQLSTATE: [HY000](#)  
Message: An unexpected event sequence was detected by the SQL thread while applying an event.  
[ER\\_RPL\\_SLAVE\\_SQL\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#) was added in 8.0.19, removed after 8.0.32.
  - Error number: [MY-013510](#); Symbol: [ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#); SQLSTATE: [HY000](#)  
Message: An unexpected event sequence was detected by the SQL thread while applying an event.  
[ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#) was added in 8.0.33.
  - Error number: [MY-013511](#); Symbol: [ER\\_IB\\_MSG\\_UPGRADE\\_PARTITION\\_FILE](#); SQLSTATE: [HY000](#)

---

Message: Updating partition file name '%s' to '%s' and all other partition files during upgrade

[ER\\_IB\\_MSG\\_UPGRADE\\_PARTITION\\_FILE](#) was added in 8.0.19.

- Error number: MY-013512; Symbol: [ER\\_IB\\_MSG\\_DOWNGRADE\\_PARTITION\\_FILE](#); SQLSTATE: HY000

Message: Updating partition file name '%s' to '%s' and all other partition files during downgrade

[ER\\_IB\\_MSG\\_DOWNGRADE\\_PARTITION\\_FILE](#) was added in 8.0.19.

- Error number: MY-013513; Symbol: [ER\\_IB\\_MSG\\_UPGRADE\\_PARTITION\\_FILE\\_IMPORT](#); SQLSTATE: HY000

Message: Updating partition file name '%s' to '%s' for import

[ER\\_IB\\_MSG\\_UPGRADE\\_PARTITION\\_FILE\\_IMPORT](#) was added in 8.0.19.

- Error number: MY-013514; Symbol: [ER\\_IB\\_WARN\\_OPEN\\_PARTITION\\_FILE](#); SQLSTATE: HY000

Message: Unable to open partition file with new name '%s'. Please check if innodb\_directories is set to include all external file paths

[ER\\_IB\\_WARN\\_OPEN\\_PARTITION\\_FILE](#) was added in 8.0.19.

- Error number: MY-013515; Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CORRECTED](#); SQLSTATE: HY000

Message: %s DD ID: %llu - Partition tablespace %u, name '%s' is corrected to '%s'

[ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CORRECTED](#) was added in 8.0.19.

- Error number: MY-013516; Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CHANGED\\_PATH](#); SQLSTATE: HY000

Message: %s DD ID: %llu - Tablespace %u, name '%s', '%s' is moved to '%s'

[ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CHANGED\\_PATH](#) was added in 8.0.19.

- Error number: MY-013517; Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CHANGED\\_NAME](#); SQLSTATE: HY000

Message: %s DD ID: %llu - Partition tablespace %u, name '%s', '%s' is updated to '%s'

[ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CHANGED\\_NAME](#) was added in 8.0.19.

- Error number: MY-013518; Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_TOO\\_MANY](#); SQLSTATE: HY000

Message: %s Too many files have been moved, disabling logging of detailed messages

[ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_TOO\\_MANY](#) was added in 8.0.19.

- Error number: MY-013519; Symbol: [ER\\_GR\\_ELECTED\\_PRIMARY\\_GTID\\_INFORMATION](#); SQLSTATE: HY000

Message: Elected primary member %s: %s

[ER\\_GR\\_ELECTED\\_PRIMARY\\_GTID\\_INFORMATION](#) was added in 8.0.19.

- 
- Error number: `MY-013520`; Symbol: `ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED`; SQLSTATE: `HY000`  
  
Message: Schema name '%s' containing upper case characters is not allowed with `lower_case_table_names = 1`.  
  
`ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED` was added in 8.0.19.
  - Error number: `MY-013521`; Symbol: `ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED`; SQLSTATE: `HY000`  
  
Message: Table name '%s.%s' containing upper case characters is not allowed with `lower_case_table_names = 1`.  
  
`ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED` was added in 8.0.19.
  - Error number: `MY-013522`; Symbol: `ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK`; SQLSTATE: `HY000`  
  
Message: Schema name '%s' containing upper case characters, used by foreign key '%s' in table '%s.%s', is not allowed with `lower_case_table_names = 1`.  
  
`ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK` was added in 8.0.19.
  - Error number: `MY-013523`; Symbol: `ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK`; SQLSTATE: `HY000`  
  
Message: Table name '%s.%s' containing upper case characters, used by foreign key '%s' in table '%s.%s', is not allowed with `lower_case_table_names = 1`.  
  
`ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK` was added in 8.0.19.
  - Error number: `MY-013524`; Symbol: `ER_IB_MSG_DICT_PARTITION_NOT_FOUND`; SQLSTATE: `HY000`  
  
Message: Table Partition: %s is not found in InnoDB dictionary  
  
`ER_IB_MSG_DICT_PARTITION_NOT_FOUND` was added in 8.0.19.
  - Error number: `MY-013525`; Symbol: `ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK`; SQLSTATE: `HY000`  
  
Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins. Use `FLUSH PRIVILEGES` or `ALTER USER` to reset.  
  
`ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK` was added in 8.0.19.
  - Error number: `MY-013526`; Symbol: `ER_INNOODB_OUT_OF_RESOURCES`; SQLSTATE: `HY000`  
  
Message: %s  
  
`ER_INNOODB_OUT_OF_RESOURCES` was added in 8.0.19.
  - Error number: `MY-013527`; Symbol: `ER_DD_UPGRADE_FOUND_PREPARED_XA_TRANSACTION`; SQLSTATE: `HY000`  
  
Message: Upgrade cannot proceed due to an existing prepared XA transaction.  
  
`ER_DD_UPGRADE_FOUND_PREPARED_XA_TRANSACTION` was added in 8.0.19.
-

- 
- Error number: [MY-013528](#); Symbol: [ER\\_MIGRATE\\_TABLE\\_TO\\_DD\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Could not allocate memory for key\_info when migrating table %s.%s  
[ER\\_MIGRATE\\_TABLE\\_TO\\_DD\\_OOM](#) was added in 8.0.19.
  - Error number: [MY-013529](#); Symbol: [ER\\_RPL\\_RELAY\\_LOG\\_RECOVERY\\_INFO\\_AFTER\\_CLONE](#); SQLSTATE: [HY000](#)  
Message: Applier metadata information for channel '%s' was found after a clone operation. Relay log recovery will be executed to adjust positions and file information for this new server. Should that automatic procedure fail please adjust the positions through 'CHANGE REPLICATION SOURCE TO'  
[ER\\_RPL\\_RELAY\\_LOG\\_RECOVERY\\_INFO\\_AFTER\\_CLONE](#) was added in 8.0.19.
  - Error number: [MY-013530](#); Symbol: [ER\\_IB\\_MSG\\_57\\_UNDO\\_SPACE\\_DELETE\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed to delete 5.7 undo tablespace: %s during upgrade  
[ER\\_IB\\_MSG\\_57\\_UNDO\\_SPACE\\_DELETE\\_FAIL](#) was added in 8.0.19.
  - Error number: [MY-013531](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1285](#); SQLSTATE: [HY000](#)  
Message: Empty doublewrite file: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1285](#) was added in 8.0.20.
  - Error number: [MY-013532](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1286](#); SQLSTATE: [HY000](#)  
Message: Using '%s' for doublewrite  
[ER\\_IB\\_MSG\\_DBLWR\\_1286](#) was added in 8.0.20.
  - Error number: [MY-013533](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1287](#); SQLSTATE: [HY000](#)  
Message: Error reading doublewrite buffer from the system tablespace  
[ER\\_IB\\_MSG\\_DBLWR\\_1287](#) was added in 8.0.20.
  - Error number: [MY-013534](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1288](#); SQLSTATE: [HY000](#)  
Message: Cannot create doublewrite buffer: you must increase your buffer pool size. Cannot continue operation.  
[ER\\_IB\\_MSG\\_DBLWR\\_1288](#) was added in 8.0.20.
  - Error number: [MY-013535](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1290](#); SQLSTATE: [HY000](#)  
Message: The page in the doublewrite file is corrupt. Cannot continue operation. You can try to recover the database with innodb\_force\_recovery=6  
[ER\\_IB\\_MSG\\_DBLWR\\_1290](#) was added in 8.0.20.
  - Error number: [MY-013536](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1291](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1291](#) was added in 8.0.20, removed after 8.0.20.

- 
- Error number: [MY-013536](#); Symbol: [ER\\_IB\\_MSG\\_BAD\\_DBLWR\\_FILE\\_NAME](#); SQLSTATE: [HY000](#)  
Message: The doublewrite filename '%s' is incorrect.  
[ER\\_IB\\_MSG\\_BAD\\_DBLWR\\_FILE\\_NAME](#) was added in 8.0.21.
  - Error number: [MY-013537](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1292](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1292](#) was added in 8.0.20, removed after 8.0.20.
  - Error number: [MY-013538](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1293](#); SQLSTATE: [HY000](#)  
Message: Doublewrite file create failed: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1293](#) was added in 8.0.20.
  - Error number: [MY-013539](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1294](#); SQLSTATE: [HY000](#)  
Message: DBLWRThread: pthread\_setaffinity() failed!  
[ER\\_IB\\_MSG\\_DBLWR\\_1294](#) was added in 8.0.20.
  - Error number: [MY-013540](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1295](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1295](#) was added in 8.0.20.
  - Error number: [MY-013541](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1296](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1296](#) was added in 8.0.20.
  - Error number: [MY-013542](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1297](#); SQLSTATE: [HY000](#)  
Message: Doublewrite file read failed: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1297](#) was added in 8.0.20.
  - Error number: [MY-013543](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1298](#); SQLSTATE: [HY000](#)  
Message: Dump of the data file page:  
[ER\\_IB\\_MSG\\_DBLWR\\_1298](#) was added in 8.0.20.
  - Error number: [MY-013544](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1300](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1300](#) was added in 8.0.20.
  - Error number: [MY-013545](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1301](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1301](#) was added in 8.0.20.

- 
- Error number: `MY-013546`; Symbol: `ER_IB_MSG_DBLWR_1304`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_DBLWR_1304` was added in 8.0.20.
  - Error number: `MY-013547`; Symbol: `ER_IB_MSG_DBLWR_1305`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_DBLWR_1305` was added in 8.0.20.
  - Error number: `MY-013548`; Symbol: `ER_IB_MSG_DBLWR_1306`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_DBLWR_1306` was added in 8.0.20.
  - Error number: `MY-013549`; Symbol: `ER_IB_MSG_DBLWR_1307`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_DBLWR_1307` was added in 8.0.20.
  - Error number: `MY-013550`; Symbol: `ER_IB_MSG_DBLWR_1308`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_DBLWR_1308` was added in 8.0.20.
  - Error number: `MY-013551`; Symbol: `ER_IB_MSG_DBLWR_1309`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_DBLWR_1309` was added in 8.0.20.
  - Error number: `MY-013552`; Symbol: `ER_IB_MSG_DBLWR_1310`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_DBLWR_1310` was added in 8.0.20.
  - Error number: `MY-013553`; Symbol: `ER_IB_MSG_DBLWR_1311`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_DBLWR_1311` was added in 8.0.20.
  - Error number: `MY-013554`; Symbol: `ER_IB_MSG_DBLWR_1312`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_DBLWR_1312` was added in 8.0.20.
  - Error number: `MY-013555`; Symbol: `ER_IB_MSG_DBLWR_1313`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_DBLWR_1313` was added in 8.0.20.



- 
- Error number: [MY-013556](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1314](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1314](#) was added in 8.0.20.
  - Error number: [MY-013557](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1315](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1315](#) was added in 8.0.20.
  - Error number: [MY-013558](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1316](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1316](#) was added in 8.0.20.
  - Error number: [MY-013559](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1317](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1317](#) was added in 8.0.20.
  - Error number: [MY-013560](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1318](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1318](#) was added in 8.0.20.
  - Error number: [MY-013561](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1319](#); SQLSTATE: [HY000](#)  
Message: Doublewrite load file %s size %lu is not a multiple of the configured page size %lu"  
[ER\\_IB\\_MSG\\_DBLWR\\_1319](#) was added in 8.0.20.
  - Error number: [MY-013562](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1320](#); SQLSTATE: [HY000](#)  
Message: Doublewrite file %s truncate failed  
[ER\\_IB\\_MSG\\_DBLWR\\_1320](#) was added in 8.0.20.
  - Error number: [MY-013563](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1321](#); SQLSTATE: [HY000](#)  
Message: Doublewrite file %s failed to writ zeros  
[ER\\_IB\\_MSG\\_DBLWR\\_1321](#) was added in 8.0.20.
  - Error number: [MY-013564](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1322](#); SQLSTATE: [HY000](#)  
Message: Doublewrite create file %s size %lu is not a multiple of the configured page size %lu"  
[ER\\_IB\\_MSG\\_DBLWR\\_1322](#) was added in 8.0.20.
  - Error number: [MY-013565](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1323](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_IB\\_MSG\\_DBLWR\\_1323](#) was added in 8.0.20.

- 
- Error number: `MY-013566`; Symbol: `ER_IB_MSG_DBLWR_1324`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_DBLWR_1324` was added in 8.0.20.
  - Error number: `MY-013567`; Symbol: `ER_IB_MSG_DBLWR_1325`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_DBLWR_1325` was added in 8.0.20.
  - Error number: `MY-013568`; Symbol: `ER_IB_MSG_DBLWR_1326`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_DBLWR_1326` was added in 8.0.20.
  - Error number: `MY-013569`; Symbol: `ER_IB_MSG_DBLWR_1327`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_DBLWR_1327` was added in 8.0.20.
  - Error number: `MY-013570`; Symbol: `ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN`; SQLSTATE: `HY000`  
Message: Could not flush all GTIDs during slow shutdown. Will recover GTIDs when server restarts.  
`ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN` was added in 8.0.20.
  - Error number: `MY-013571`; Symbol: `ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL`; SQLSTATE: `HY000`  
Message: Failed to delete 5.7 stat tablespace: %s during upgrade  
`ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL` was added in 8.0.20.
  - Error number: `MY-013572`; Symbol: `ER_NDBINFO_UPGRADING_SCHEMA`; SQLSTATE: `HY000`  
Message: Installing ndbinfo schema version %s  
`ER_NDBINFO_UPGRADING_SCHEMA` was added in 8.0.20.
  - Error number: `MY-013573`; Symbol: `ER_NDBINFO_NOT_UPGRADING_SCHEMA`; SQLSTATE: `HY000`  
Message: Installed ndbinfo schema is current. Not upgrading.  
`ER_NDBINFO_NOT_UPGRADING_SCHEMA` was added in 8.0.20.
  - Error number: `MY-013574`; Symbol: `ER_NDBINFO_UPGRADING_SCHEMA_FAIL`; SQLSTATE: `HY000`  
Message: Failed to upgrade ndbinfo schema.  
`ER_NDBINFO_UPGRADING_SCHEMA_FAIL` was added in 8.0.20.
  - Error number: `MY-013575`; Symbol: `ER_IB_MSG_CREATE_LOG_FILE`; SQLSTATE: `HY000`  
Message: Creating log file %s  
`ER_IB_MSG_CREATE_LOG_FILE` was added in 8.0.20, removed after 8.0.29.

- 
- Error number: [MY-013576](#); Symbol: [ER\\_IB\\_MSG\\_INNODB\\_START\\_INITIALIZE](#); SQLSTATE: [HY000](#)  
Message: InnoDB initialization has started.  
[ER\\_IB\\_MSG\\_INNODB\\_START\\_INITIALIZE](#) was added in 8.0.20.
  - Error number: [MY-013577](#); Symbol: [ER\\_IB\\_MSG\\_INNODB\\_END\\_INITIALIZE](#); SQLSTATE: [HY000](#)  
Message: InnoDB initialization has ended.  
[ER\\_IB\\_MSG\\_INNODB\\_END\\_INITIALIZE](#) was added in 8.0.20.
  - Error number: [MY-013578](#); Symbol: [ER\\_IB\\_MSG\\_PAGE\\_ARCH\\_NO\\_RESET\\_POINTS](#); SQLSTATE: [HY000](#)  
Message: Could not find appropriate reset points.  
[ER\\_IB\\_MSG\\_PAGE\\_ARCH\\_NO\\_RESET\\_POINTS](#) was added in 8.0.20.
  - Error number: [MY-013579](#); Symbol: [ER\\_IB\\_WRN\\_PAGE\\_ARCH\\_FLUSH\\_DATA](#); SQLSTATE: [HY000](#)  
Message: Unable to flush. Page archiving data may be corrupt in case of a crash.  
[ER\\_IB\\_WRN\\_PAGE\\_ARCH\\_FLUSH\\_DATA](#) was added in 8.0.20.
  - Error number: [MY-013580](#); Symbol: [ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_INVALID\\_DOUBLE\\_WRITE\\_BUF](#); SQLSTATE: [HY000](#)  
Message: Page archiver's doublewrite buffer for %ld is not valid.  
[ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_INVALID\\_DOUBLE\\_WRITE\\_BUF](#) was added in 8.0.20.
  - Error number: [MY-013581](#); Symbol: [ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_RECOVERY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Page archiver system's recovery failed.  
[ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_RECOVERY\\_FAILED](#) was added in 8.0.20.
  - Error number: [MY-013582](#); Symbol: [ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_INVALID\\_FORMAT](#); SQLSTATE: [HY000](#)  
Message: Invalid archived file name format. The archived file is supposed to have the format %s + [0-9]\*.  
[ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_INVALID\\_FORMAT](#) was added in 8.0.20.
  - Error number: [MY-013583](#); Symbol: [ER\\_INVALID\\_XPLUGIN\\_SOCKET\\_SAME\\_AS\\_SERVER](#); SQLSTATE: [HY000](#)  
Message: X Plugins UNIX socket must use different file than MySQL server. X Plugin won't be accessible through UNIX socket  
[ER\\_INVALID\\_XPLUGIN\\_SOCKET\\_SAME\\_AS\\_SERVER](#) was added in 8.0.20.
  - Error number: [MY-013584](#); Symbol: [ER\\_INNODB\\_UNABLE\\_TO\\_ACQUIRE\\_DD\\_OBJECT](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_INNODB\\_UNABLE\\_TO\\_ACQUIRE\\_DD\\_OBJECT](#) was added in 8.0.20.
-

- 
- Error number: `MY-013585`; Symbol: `ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX_KEY`; SQLSTATE: `HY000`

Message: Column '%s.%s.%s' having prefix key part '%s(%u)' is ignored by the partitioning function. Use of prefixed columns in the PARTITION BY KEY() clause is deprecated and will be removed in a future release.

`ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX_KEY` was added in 8.0.21.

- Error number: `MY-013586`; Symbol: `ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN`; SQLSTATE: `HY000`

Message: Undo Truncation is occurring too often. Consider increasing `--innodb-max-undo-log-size`.

`ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN` was added in 8.0.21.

- Error number: `MY-013587`; Symbol: `ER_GRP_RPL_IS_STARTING`; SQLSTATE: `HY000`

Message: Plugin 'group\_replication' is starting.

`ER_GRP_RPL_IS_STARTING` was added in 8.0.21.

- Error number: `MY-013588`; Symbol: `ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE`; SQLSTATE: `HY000`

Message: Cannot create tablespace %s because the directory is not a valid location. %s

`ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE` was added in 8.0.21.

- Error number: `MY-013589`; Symbol: `ER_IB_MSG_INVALID_LOCATION_WRONG_DB`; SQLSTATE: `HY000`

Message: Scanned file '%s' for tablespace %s cannot be opened because it is not in a sub-directory named for the schema.

`ER_IB_MSG_INVALID_LOCATION_WRONG_DB` was added in 8.0.21.

- Error number: `MY-013590`; Symbol: `ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE`; SQLSTATE: `HY000`

Message: Cannot find undo tablespace %s with filename '%s' as indicated by the Data Dictionary. Did you move or delete this tablespace? Any undo logs in it cannot be used.

`ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE` was added in 8.0.21.

- Error number: `MY-013591`; Symbol: `ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT`; SQLSTATE: `HY000`

Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port)

`ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT` was added in 8.0.21.

- Error number: `MY-013592`; Symbol: `ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID`; SQLSTATE: `HY000`

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.

`ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID` was added in 8.0.21.

- 
- Error number: `MY-013593`; Symbol: `ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_ENDPOINT`; SQLSTATE: `HY000`  
Message: Received invalid recovery endpoints configuration from donor. This member is not a valid donor for recovery, so it will be skipped.  
`ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_ENDPOINT` was added in 8.0.21.
  - Error number: `MY-013594`; Symbol: `ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IPS`; SQLSTATE: `HY000`  
Message: Failed to retrieve IP addresses from enabled host network interfaces.  
`ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IPS` was added in 8.0.21.
  - Error number: `MY-013595`; Symbol: `ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR`; SQLSTATE: `HY000`  
Message: Failed to initialize TLS for channel: %s. See below for the description of exact issue.  
`ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR` was added in 8.0.21.
  - Error number: `MY-013596`; Symbol: `ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS`; SQLSTATE: `HY000`  
Message: Validation of value '%s' set to `Mysqlx\_bind\_address` failed: %s. Skipping this value.  
`ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS` was added in 8.0.21.
  - Error number: `MY-013597`; Symbol: `ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS`; SQLSTATE: `HY000`  
Message: Value '%s' set to `Mysqlx\_bind\_address`, X Plugin can't bind to it. Skipping this value.  
`ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS` was added in 8.0.21.
  - Error number: `MY-013598`; Symbol: `ER_IB_ERR_RECOVERY_REDO_DISABLED`; SQLSTATE: `HY000`  
Message: Server was killed when InnoDB redo logging was disabled. Data files could be corrupt. You can try to restart the database with `innodb_force_recovery=6`  
`ER_IB_ERR_RECOVERY_REDO_DISABLED` was added in 8.0.21.
  - Error number: `MY-013599`; Symbol: `ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED`; SQLSTATE: `HY000`  
Message: InnoDB cannot do cold shutdown 'innodb\_fast\_shutdown = 2' and is forcing 'innodb\_fast\_shutdown = 1' as redo logging is disabled. InnoDB would flush all dirty pages to ensure physical data consistency.  
`ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED` was added in 8.0.21.
  - Error number: `MY-013600`; Symbol: `ER_IB_WRN_REDO_DISABLED`; SQLSTATE: `HY000`  
Message: InnoDB redo logging is disabled. All data could be lost in case of a server crash.  
`ER_IB_WRN_REDO_DISABLED` was added in 8.0.21.
  - Error number: `MY-013601`; Symbol: `ER_IB_WRN_REDO_ENABLED`; SQLSTATE: `HY000`

---

Message: InnoDB redo logging is enabled. Data is now safe and can be recovered in case of a server crash.

`ER_IB_WRN_REDO_ENABLED` was added in 8.0.21.

- Error number: `MY-013602`; Symbol: `ER_TLS_CONFIGURED_FOR_CHANNEL`; SQLSTATE: `HY000`

Message: Channel %s configured to support TLS. Encrypted connections are now supported for this channel.

`ER_TLS_CONFIGURED_FOR_CHANNEL` was added in 8.0.21.

- Error number: `MY-013603`; Symbol: `ER_TLS_CONFIGURATION_REUSED`; SQLSTATE: `HY000`

Message: No TLS configuration was given for channel %s; re-using TLS configuration of channel %s.

`ER_TLS_CONFIGURATION_REUSED` was added in 8.0.21.

- Error number: `MY-013604`; Symbol: `ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED`; SQLSTATE: `HY000`

Message: Skipping InnoDB tablespace path validation. Manually moved tablespace files will not be detected!

`ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED` was added in 8.0.21.

- Error number: `MY-013605`; Symbol: `ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES`; SQLSTATE: `HY000`

Message: Upgrade failed because database contains discarded tablespaces.

`ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES` was added in 8.0.21.

- Error number: `MY-013606`; Symbol: `ER_USERNAME_TRUNCATED`; SQLSTATE: `HY000`

Message: The user name '%s' exceeds the maximum number of allowed characters %d and is truncated.

`ER_USERNAME_TRUNCATED` was added in 8.0.21.

- Error number: `MY-013607`; Symbol: `ER_HOSTNAME_TRUNCATED`; SQLSTATE: `HY000`

Message: The host name '%s' exceeds the maximum number of allowed characters %d and is truncated.

`ER_HOSTNAME_TRUNCATED` was added in 8.0.21.

- Error number: `MY-013608`; Symbol: `ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED`; SQLSTATE: `HY000`

Message: Rollback of non-prepared transactions not completed, due to fast shutdown

`ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED` was added in 8.0.21.

- Error number: `MY-013609`; Symbol: `ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME`; SQLSTATE: `HY000`

Message: Found an entry in the 'role\_edges' table with empty authorization ID; Skipped

---

`ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME` was added in 8.0.21.

- Error number: `MY-013610`; Symbol: `ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION_ID`; SQLSTATE: `HY000`

Message: Found an entry in the 'role\_edges' table with unknown authorization ID '%s'; Skipped

`ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION_ID` was added in 8.0.21.

- Error number: `MY-013611`; Symbol: `ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME`; SQLSTATE: `HY000`

Message: Found an entry in the 'default\_roles' table with empty authorization ID; Skipped

`ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME` was added in 8.0.21.

- Error number: `MY-013612`; Symbol: `ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION_ID`; SQLSTATE: `HY000`

Message: Found an entry in the 'default\_roles' table with unknown authorization ID '%s'; Skipped

`ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION_ID` was added in 8.0.21.

- Error number: `MY-013613`; Symbol: `ER_IB_ERR_DDL_LOG_INSERT_FAILURE`; SQLSTATE: `HY000`

Message: Couldn't insert entry in ddl log for ddl.

`ER_IB_ERR_DDL_LOG_INSERT_FAILURE` was added in 8.0.21.

- Error number: `MY-013614`; Symbol: `ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION`; SQLSTATE: `HY000`

Message: %s

`ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION` was added in 8.0.21.

- Error number: `MY-013615`; Symbol: `ER_IB_RELOCK_LATCH_ORDER_VIOLATION`; SQLSTATE: `HY000`

Message: %s

`ER_IB_RELOCK_LATCH_ORDER_VIOLATION` was added in 8.0.21.

- Error number: `MY-013621`; Symbol: `ER_IB_MSG_1357`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1357` was added in 8.0.21.

- Error number: `MY-013622`; Symbol: `ER_IB_MSG_1358`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1358` was added in 8.0.21.

- Error number: `MY-013623`; Symbol: `ER_IB_MSG_1359`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1359` was added in 8.0.21.

- 
- Error number: MY-013624; Symbol: ER\_IB\_FAILED\_TO\_DELETE\_TABLESPACE\_FILE; SQLSTATE: HY000  
Message: %s  
ER\_IB\_FAILED\_TO\_DELETE\_TABLESPACE\_FILE was added in 8.0.21.
  - Error number: MY-013625; Symbol: ER\_IB\_UNABLE\_TO\_EXPAND\_TEMPORARY\_TABLESPACE\_POOL; SQLSTATE: HY000  
Message: %s  
ER\_IB\_UNABLE\_TO\_EXPAND\_TEMPORARY\_TABLESPACE\_POOL was added in 8.0.21.
  - Error number: MY-013626; Symbol: ER\_IB\_TMP\_TABLESPACE\_CANNOT\_CREATE\_DIRECTORY; SQLSTATE: HY000  
Message: %s  
ER\_IB\_TMP\_TABLESPACE\_CANNOT\_CREATE\_DIRECTORY was added in 8.0.21.
  - Error number: MY-013627; Symbol: ER\_IB\_MSG\_SCANNING\_TEMP\_TABLESPACE\_DIR; SQLSTATE: HY000  
Message: %s  
ER\_IB\_MSG\_SCANNING\_TEMP\_TABLESPACE\_DIR was added in 8.0.21.
  - Error number: MY-013628; Symbol: ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_DOESNT\_EXIST; SQLSTATE: HY000  
Message: %s  
ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_DOESNT\_EXIST was added in 8.0.21.
  - Error number: MY-013629; Symbol: ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_EMPTY; SQLSTATE: HY000  
Message: %s  
ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_EMPTY was added in 8.0.21.
  - Error number: MY-013630; Symbol: ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_CONTAINS\_SEMICOLON; SQLSTATE: HY000  
Message: %s  
ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_CONTAINS\_SEMICOLON was added in 8.0.21.
  - Error number: MY-013631; Symbol: ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_SUBDIR\_OF\_DATADIR; SQLSTATE: HY000  
Message: %s  
ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_SUBDIR\_OF\_DATADIR was added in 8.0.21.
  - Error number: MY-013632; Symbol: ER\_IB\_ERR\_SCHED\_SETAFFINITY\_FAILED; SQLSTATE: HY000



---

Message: %s

[ER\\_IB\\_ERR\\_SCHED\\_SETAFFINITY\\_FAILED](#) was added in 8.0.21.

- Error number: [MY-013633](#); Symbol: [ER\\_IB\\_ERR\\_UNKNOWN\\_PAGE\\_FETCH\\_MODE](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_ERR\\_UNKNOWN\\_PAGE\\_FETCH\\_MODE](#) was added in 8.0.21.

- Error number: [MY-013634](#); Symbol: [ER\\_IB\\_ERR\\_LOG\\_PARSING\\_BUFFER\\_OVERFLOW](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_ERR\\_LOG\\_PARSING\\_BUFFER\\_OVERFLOW](#) was added in 8.0.21.

- Error number: [MY-013635](#); Symbol: [ER\\_IB\\_ERR\\_NOT\\_ENOUGH\\_MEMORY\\_FOR\\_PARSE\\_BUFFER](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_ERR\\_NOT\\_ENOUGH\\_MEMORY\\_FOR\\_PARSE\\_BUFFER](#) was added in 8.0.21.

- Error number: [MY-013636](#); Symbol: [ER\\_IB\\_MSG\\_1372](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1372](#) was added in 8.0.21.

- Error number: [MY-013637](#); Symbol: [ER\\_IB\\_MSG\\_1373](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1373](#) was added in 8.0.21.

- Error number: [MY-013638](#); Symbol: [ER\\_IB\\_MSG\\_1374](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1374](#) was added in 8.0.21.

- Error number: [MY-013639](#); Symbol: [ER\\_IB\\_MSG\\_1375](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_MSG\\_1375](#) was added in 8.0.21.

- Error number: [MY-013640](#); Symbol: [ER\\_IB\\_ERR\\_ZLIB\\_UNCOMPRESS\\_FAILED](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_ERR\\_ZLIB\\_UNCOMPRESS\\_FAILED](#) was added in 8.0.21.

- Error number: [MY-013641](#); Symbol: [ER\\_IB\\_ERR\\_ZLIB\\_BUF\\_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_ERR\\_ZLIB\\_BUF\\_ERROR](#) was added in 8.0.21.

- 
- Error number: `MY-013642`; Symbol: `ER_IB_ERR_ZLIB_MEM_ERROR`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_ERR_ZLIB_MEM_ERROR` was added in 8.0.21.
  - Error number: `MY-013643`; Symbol: `ER_IB_ERR_ZLIB_DATA_ERROR`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_ERR_ZLIB_DATA_ERROR` was added in 8.0.21.
  - Error number: `MY-013644`; Symbol: `ER_IB_ERR_ZLIB_UNKNOWN_ERROR`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_ERR_ZLIB_UNKNOWN_ERROR` was added in 8.0.21.
  - Error number: `MY-013645`; Symbol: `ER_IB_MSG_1381`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_1381` was added in 8.0.21.
  - Error number: `MY-013646`; Symbol: `ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER` was added in 8.0.21.
  - Error number: `MY-013647`; Symbol: `ER_IB_ERR_INDEX_DUPLICATE_KEY`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_ERR_INDEX_DUPLICATE_KEY` was added in 8.0.21.
  - Error number: `MY-013648`; Symbol: `ER_IB_ERR_FOUND_N_DUPLICATE_KEYS`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_ERR_FOUND_N_DUPLICATE_KEYS` was added in 8.0.21.
  - Error number: `MY-013649`; Symbol: `ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER` was added in 8.0.21.
  - Error number: `MY-013650`; Symbol: `ER_IB_ERR_PARALLEL_READ_OOM`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_ERR_PARALLEL_READ_OOM` was added in 8.0.21.
  - Error number: `MY-013651`; Symbol: `ER_IB_MSG_UNDO_MARKED_ACTIVE`; SQLSTATE: `HY000`  
Message: The state of undo tablespace %s is set to active implicitly.

---

[ER\\_IB\\_MSG\\_UNDO\\_MARKED\\_ACTIVE](#) was added in 8.0.21.

- Error number: [MY-013652](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_ALTERED\\_ACTIVE](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to 'active' by ALTER TABLESPACE.

[ER\\_IB\\_MSG\\_UNDO\\_ALTERED\\_ACTIVE](#) was added in 8.0.21.

- Error number: [MY-013653](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_ALTERED\\_INACTIVE](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to 'inactive' by ALTER TABLESPACE.

[ER\\_IB\\_MSG\\_UNDO\\_ALTERED\\_INACTIVE](#) was added in 8.0.21.

- Error number: [MY-013654](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_MARKED\\_EMPTY](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to 'empty'.

[ER\\_IB\\_MSG\\_UNDO\\_MARKED\\_EMPTY](#) was added in 8.0.21.

- Error number: [MY-013655](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_CLONE](#); SQLSTATE: [HY000](#)

Message: Delaying truncate of undo tablespace %s due to clone activity.

[ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_CLONE](#) was added in 8.0.21.

- Error number: [MY-013656](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_MDL](#); SQLSTATE: [HY000](#)

Message: Delaying truncate of undo tablespace %s due to a metadata lock.

[ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_MDL](#) was added in 8.0.21.

- Error number: [MY-013657](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_INJECT\\_CRASH](#); SQLSTATE: [HY000](#)

Message: Injected debug crash point: %s

[ER\\_IB\\_MSG\\_UNDO\\_INJECT\\_CRASH](#) was added in 8.0.21, removed after 8.0.21.

- Error number: [MY-013657](#); Symbol: [ER\\_IB\\_MSG\\_INJECT\\_CRASH](#); SQLSTATE: [HY000](#)

Message: Injected debug crash point: %s

[ER\\_IB\\_MSG\\_INJECT\\_CRASH](#) was added in 8.0.22.

- Error number: [MY-013658](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_INJECT\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Injected debug failure point: %s

[ER\\_IB\\_MSG\\_UNDO\\_INJECT\\_FAILURE](#) was added in 8.0.21, removed after 8.0.21.

- Error number: [MY-013658](#); Symbol: [ER\\_IB\\_MSG\\_INJECT\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Injected debug failure point: %s

[ER\\_IB\\_MSG\\_INJECT\\_FAILURE](#) was added in 8.0.22.

- 
- Error number: `MY-013659`; Symbol: `ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN`; SQLSTATE: `HY000`

Message: Timeout while waiting for a view change event during the leave step before a auto-rejoin attempt.

`ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN` was added in 8.0.22.

- Error number: `MY-013660`; Symbol: `ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE`; SQLSTATE: `HY000`

Message: Failed to automatically re-connect to a different source, for channel '%s', because %s. To fix this %s.

`ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE` was added in 8.0.22.

- Error number: `MY-013661`; Symbol: `ER_UDF_REGISTER_SERVICE_ERROR`; SQLSTATE: `HY000`

Message: Could not execute the installation of UDF functions. Check for other errors in the log

`ER_UDF_REGISTER_SERVICE_ERROR` was added in 8.0.22.

- Error number: `MY-013662`; Symbol: `ER_UDF_REGISTER_ERROR`; SQLSTATE: `HY000`

Message: Could not execute the installation of UDF function: %s. Check if the function is already present, if so, try to remove it.

`ER_UDF_REGISTER_ERROR` was added in 8.0.22.

- Error number: `MY-013663`; Symbol: `ER_UDF_UNREGISTER_ERROR`; SQLSTATE: `HY000`

Message: Could not uninstall UDF functions. Try to remove them manually if present.

`ER_UDF_UNREGISTER_ERROR` was added in 8.0.22.

- Error number: `MY-013664`; Symbol: `ER_EMPTY_PRIVILEGE_NAME_IGNORED`; SQLSTATE: `HY000`

Message: An empty or illegal privilege identifier was ignored when global privileges were read from disk.

`ER_EMPTY_PRIVILEGE_NAME_IGNORED` was added in 8.0.22.

- Error number: `MY-013665`; Symbol: `ER_IB_MSG_INCORRECT_SIZE`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_INCORRECT_SIZE` was added in 8.0.22.

- Error number: `MY-013666`; Symbol: `ER_TMPDIR_PATH_TOO_LONG`; SQLSTATE: `HY000`

Message: A tmpdir temporary path "%s" is too long (> %zu) for this OS. This would not leave enough space for a temporary filename of length %zu within it.

`ER_TMPDIR_PATH_TOO_LONG` was added in 8.0.22.

- 
- Error number: [MY-013667](#); Symbol: [ER\\_ERROR\\_LOG\\_DESTINATION\\_NOT\\_A\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Error-log destination "%s" is not a file. Can not restore error log messages from previous run.  
[ER\\_ERROR\\_LOG\\_DESTINATION\\_NOT\\_A\\_FILE](#) was added in 8.0.22.
  - Error number: [MY-013668](#); Symbol: [ER\\_NO\\_ERROR\\_LOG\\_PARSER\\_CONFIGURED](#); SQLSTATE: [HY000](#)  
Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance\_schema.error\_log.  
[ER\\_NO\\_ERROR\\_LOG\\_PARSER\\_CONFIGURED](#) was added in 8.0.22.
  - Error number: [MY-013669](#); Symbol: [ER\\_UPGRADE\\_NONEXISTENT\\_SCHEMA](#); SQLSTATE: [HY000](#)  
Message: The schema "%s" referenced by %s "%s" does not exist. Please clean up any orphan %s before upgrading.  
[ER\\_UPGRADE\\_NONEXISTENT\\_SCHEMA](#) was added in 8.0.22.
  - Error number: [MY-013670](#); Symbol: [ER\\_IB\\_MSG\\_CREATED\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Created undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_CREATED\\_UNDO\\_SPACE](#) was added in 8.0.22.
  - Error number: [MY-013671](#); Symbol: [ER\\_IB\\_MSG\\_DROPPED\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Dropped undo tablespace '%s'.  
[ER\\_IB\\_MSG\\_DROPPED\\_UNDO\\_SPACE](#) was added in 8.0.22.
  - Error number: [MY-013672](#); Symbol: [ER\\_IB\\_MSG\\_MASTER\\_KEY\\_ROTATED](#); SQLSTATE: [HY000](#)  
Message: The InnoDB Encryption Master Key has been rotated in %d tablespaces.  
[ER\\_IB\\_MSG\\_MASTER\\_KEY\\_ROTATED](#) was added in 8.0.22.
  - Error number: [MY-013673](#); Symbol: [ER\\_IB\\_DBLWR\\_DECOMPRESS\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to decompress a DBLWR page (err=%d). The original size is %d. Reporting the dblwr page as corrupted.  
[ER\\_IB\\_DBLWR\\_DECOMPRESS\\_FAILED](#) was added in 8.0.23.
  - Error number: [MY-013674](#); Symbol: [ER\\_IB\\_DBLWR\\_DECRYPT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Decrypting a page in doublewrite file failed: %s.  
[ER\\_IB\\_DBLWR\\_DECRYPT\\_FAILED](#) was added in 8.0.23.
  - Error number: [MY-013675](#); Symbol: [ER\\_IB\\_DBLWR\\_KEY\\_MISSING](#); SQLSTATE: [HY000](#)  
Message: Encryption key missing: %s.  
[ER\\_IB\\_DBLWR\\_KEY\\_MISSING](#) was added in 8.0.23.
  - Error number: [MY-013676](#); Symbol: [ER\\_INNO\\_DB\\_IO\\_WRITE\\_ERROR\\_RETRYING](#); SQLSTATE: [HY000](#)

---

Message: I/O error while writing to file: %s. Retrying ...

[ER\\_INNODB\\_IO\\_WRITE\\_ERROR\\_RETRYING](#) was added in 8.0.23.

- Error number: [MY-013677](#); Symbol: [ER\\_INNODB\\_IO\\_WRITE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to write data to file: %s

[ER\\_INNODB\\_IO\\_WRITE\\_FAILED](#) was added in 8.0.23.

- Error number: [MY-013678](#); Symbol: [ER\\_LOG\\_COMPONENT\\_CANNOT\\_INIT](#); SQLSTATE: [HY000](#)

Message: Log component %s failed to initialize.

[ER\\_LOG\\_COMPONENT\\_CANNOT\\_INIT](#) was added in 8.0.23.

- Error number: [MY-013679](#); Symbol: [ER\\_RPL\\_ASYNC\\_CHANNEL\\_CANT\\_CONNECT](#); SQLSTATE: [HY000](#)

Message: The Monitor IO thread failed to connect to the source (host:%s port:%u network\_namespace:%s) for channel '%s', thence it will try to connect to another source.

[ER\\_RPL\\_ASYNC\\_CHANNEL\\_CANT\\_CONNECT](#) was added in 8.0.23.

- Error number: [MY-013680](#); Symbol: [ER\\_RPL\\_ASYNC\\_SENDER\\_ADDED](#); SQLSTATE: [HY000](#)

Message: The source (host:%s port:%u network\_namespace:%s) for channel '%s' has joined the group (group\_name: %s), and so added its entry into replication\_asynchronous\_connection\_failover table.

[ER\\_RPL\\_ASYNC\\_SENDER\\_ADDED](#) was added in 8.0.23.

- Error number: [MY-013681](#); Symbol: [ER\\_RPL\\_ASYNC\\_SENDER\\_REMOVED](#); SQLSTATE: [HY000](#)

Message: The source (host:%s port:%u network\_namespace:%s) for channel '%s' has left the group (group\_name: %s), and so removed its entry from replication\_asynchronous\_connection\_failover table.

[ER\\_RPL\\_ASYNC\\_SENDER\\_REMOVED](#) was added in 8.0.23.

- Error number: [MY-013682](#); Symbol: [ER\\_RPL\\_ASYNC\\_CHANNEL\\_STOPPED\\_QUORUM\\_LOST](#); SQLSTATE: [HY000](#)

Message: The Monitor IO thread detected that the source (host:%s port:%u network\_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.

[ER\\_RPL\\_ASYNC\\_CHANNEL\\_STOPPED\\_QUORUM\\_LOST](#) was added in 8.0.23.

- Error number: [MY-013683](#); Symbol: [ER\\_RPL\\_ASYNC\\_CHANNEL\\_CANT\\_CONNECT\\_NO\\_QUORUM](#); SQLSTATE: [HY000](#)

Message: The IO thread detected that the source (host:%s port:%u network\_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.

[ER\\_RPL\\_ASYNC\\_CHANNEL\\_CANT\\_CONNECT\\_NO\\_QUORUM](#) was added in 8.0.23.

- Error number: [MY-013684](#); Symbol: [ER\\_RPL\\_ASYNC\\_EXECUTING\\_QUERY](#); SQLSTATE: [HY000](#)

Message: %s on the source (host:%s port:%u network\_namespace:%s) for channel '%s'.

[ER\\_RPL\\_ASYNC\\_EXECUTING\\_QUERY](#) was added in 8.0.23.

- 
- Error number: [MY-013685](#); Symbol: [ER\\_RPL\\_REPLICA\\_MONITOR\\_IO\\_THREAD\\_EXITING](#); SQLSTATE: HY000

Message: Replica Monitor IO thread exiting.

[ER\\_RPL\\_REPLICA\\_MONITOR\\_IO\\_THREAD\\_EXITING](#) was added in 8.0.23.

- Error number: [MY-013686](#); Symbol: [ER\\_RPL\\_ASYNC\\_MANAGED\\_NAME\\_REMOVED](#); SQLSTATE: HY000

Message: The group (group\_name: %s) for the channel '%s' has been removed, and so removed its entry from replication\_asynchronous\_connection\_failover\_managed and all the group members from replication\_asynchronous\_connection\_failover table.

[ER\\_RPL\\_ASYNC\\_MANAGED\\_NAME\\_REMOVED](#) was added in 8.0.23.

- Error number: [MY-013687](#); Symbol: [ER\\_RPL\\_ASYNC\\_MANAGED\\_NAME\\_ADDED](#); SQLSTATE: HY000

Message: The group (group\_name: %s) for the channel '%s' has been added, and so added its entry in replication\_asynchronous\_connection\_failover\_managed and source to replication\_asynchronous\_connection\_failover table.

[ER\\_RPL\\_ASYNC\\_MANAGED\\_NAME\\_ADDED](#) was added in 8.0.23.

- Error number: [MY-013688](#); Symbol: [ER\\_RPL\\_ASYNC\\_READ\\_FAILOVER\\_TABLE](#); SQLSTATE: HY000

Message: Error reading failover sources for channel '%s' from replication\_asynchronous\_connection\_failover table.

[ER\\_RPL\\_ASYNC\\_READ\\_FAILOVER\\_TABLE](#) was added in 8.0.23.

- Error number: [MY-013689](#); Symbol: [ER\\_RPL\\_REPLICA\\_MONITOR\\_IO\\_THREAD\\_RECONNECT\\_CHANNEL](#); SQLSTATE: HY000

Message: Error %s the channel '%s', the operation will be automatically retried.

[ER\\_RPL\\_REPLICA\\_MONITOR\\_IO\\_THREAD\\_RECONNECT\\_CHANNEL](#) was added in 8.0.23.

- Error number: [MY-013690](#); Symbol: [ER\\_SLAVE\\_ANONYMOUS\\_TO\\_GTID\\_IS\\_LOCAL\\_OR\\_UUID\\_AND\\_GTID\\_MODE\\_NOT\\_ON](#); SQLSTATE: HY000

Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'`, which is invalid when `GTID_MODE <> ON`. If you intend to use `GTID_MODE = ON` everywhere, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = OFF` and use the procedure for enabling GTIDs online (see the documentation). If you intend to use GTIDs on this replica and cannot enable GTIDs on the source, enable `GTID_MODE = ON` and leave `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`. If you intend to not use GTIDs at all in the replication topology, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS=OFF` and leave `GTID_MODE = '%s'`.

[ER\\_SLAVE\\_ANONYMOUS\\_TO\\_GTID\\_IS\\_LOCAL\\_OR\\_UUID\\_AND\\_GTID\\_MODE\\_NOT\\_ON](#) was added in 8.0.23, removed after 8.0.32.

- 
- Error number: [MY-013690](#); Symbol: [ER\\_REPLICA\\_ANON\\_TO\\_GTID\\_IS\\_LOCAL\\_OR\\_UUID\\_AND\\_GTID\\_MODE\\_NOT\\_ON](#); SQLSTATE: [HY000](#)  
  
Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'`, which is invalid when `GTID_MODE <> ON`. If you intend to use `GTID_MODE = ON` everywhere, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = OFF` and use the procedure for enabling GTIDs online (see the documentation). If you intend to use GTIDs on this replica and cannot enable GTIDs on the source, enable `GTID_MODE = ON` and leave `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`. If you intend to not use GTIDs at all in the replication topology, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS=OFF` and leave `GTID_MODE = '%s'`.  
  
[ER\\_REPLICA\\_ANON\\_TO\\_GTID\\_IS\\_LOCAL\\_OR\\_UUID\\_AND\\_GTID\\_MODE\\_NOT\\_ON](#) was added in 8.0.33.
  - Error number: [MY-013691](#); Symbol: [ER\\_REPLICA\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_GROUP\\_NAME](#); SQLSTATE: [HY000](#)  
  
Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'` which is equal to `group_replication_group_name`. To fix this issue, either change the `group_replication_group_name` or use a different value for `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS`.  
  
[ER\\_REPLICA\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_GROUP\\_NAME](#) was added in 8.0.23.
  - Error number: [MY-013692](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_NAME\\_IS\\_SAME\\_AS\\_ANONYMOUS\\_TO\\_GTID\\_UUID](#); SQLSTATE: [HY000](#)  
  
Message: The `group_replication_group_name '%s'` is the same as the UUID value for `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS` in a server channel  
  
[ER\\_GRP\\_RPL\\_GRP\\_NAME\\_IS\\_SAME\\_AS\\_ANONYMOUS\\_TO\\_GTID\\_UUID](#) was added in 8.0.23.
  - Error number: [MY-013693](#); Symbol: [ER\\_WARN\\_GTID\\_THRESHOLD\\_BREACH](#); SQLSTATE: [HY000](#)  
  
Message: The integer component of the GTID number is high. Suggest restarting the server with a new `server_uuid` to prevent it from reaching the maximum number  $2^{63}-1$ , which will make it impossible to write the binary log and invoke the behavior specified by `binlog_error_action`.  
  
[ER\\_WARN\\_GTID\\_THRESHOLD\\_BREACH](#) was added in 8.0.23.
  - Error number: [MY-013694](#); Symbol: [ER\\_HEALTH\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: %s  
  
[ER\\_HEALTH\\_INFO](#) was added in 8.0.23.
  - Error number: [MY-013695](#); Symbol: [ER\\_HEALTH\\_WARNING](#); SQLSTATE: [HY000](#)  
  
Message: %s  
  
[ER\\_HEALTH\\_WARNING](#) was added in 8.0.23.
  - Error number: [MY-013696](#); Symbol: [ER\\_HEALTH\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: %s  
  
[ER\\_HEALTH\\_ERROR](#) was added in 8.0.23.



- 
- Error number: [MY-013697](#); Symbol: [ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_1](#); SQLSTATE: [HY000](#)  
  
Message: %s: Warning Level 1 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB  
  
[ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_1](#) was added in 8.0.23.
  - Error number: [MY-013698](#); Symbol: [ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_2](#); SQLSTATE: [HY000](#)  
  
Message: %s: Warning Level 2 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB  
  
[ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_2](#) was added in 8.0.23.
  - Error number: [MY-013699](#); Symbol: [ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_3](#); SQLSTATE: [HY000](#)  
  
Message: %s: Warning Level 3 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB  
  
[ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_3](#) was added in 8.0.23.
  - Error number: [MY-013700](#); Symbol: [ER\\_IB\\_INNODB\\_TBSP\\_OUT\\_OF\\_SPACE](#); SQLSTATE: [HY000](#)  
  
Message: InnoDB: Size of tablespace %s is more than the maximum size allowed.  
  
[ER\\_IB\\_INNODB\\_TBSP\\_OUT\\_OF\\_SPACE](#) was added in 8.0.23.
  - Error number: [MY-013701](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_CHANNEL\\_STILL\\_RUNNING](#); SQLSTATE: [HY000](#)  
  
Message: The group\_replication\_applier channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.  
  
[ER\\_GRP\\_RPL\\_APPLIER\\_CHANNEL\\_STILL\\_RUNNING](#) was added in 8.0.23.
  - Error number: [MY-013702](#); Symbol: [ER\\_RPL\\_ASYNC\\_RECONNECT\\_GTID\\_MODE\\_OFF\\_CHANNEL](#); SQLSTATE: [HY000](#)  
  
Message: Detected misconfiguration: replication channel '%s' was configured with `SOURCE_CONNECTION_AUTO_FAILOVER = 1`, but the server was started with a value other than `--gtid-mode = ON`. Either reconfigure replication using `CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 0 FOR CHANNEL '%s'`, or change `GTID_MODE` to value `ON`, before starting the replica receiver thread.  
  
[ER\\_RPL\\_ASYNC\\_RECONNECT\\_GTID\\_MODE\\_OFF\\_CHANNEL](#) was added in 8.0.23.
  - Error number: [MY-013703](#); Symbol: [ER\\_FIREWALL\\_SERVICES\\_NOT\\_ACQUIRED](#); SQLSTATE: [HY000](#)  
  
Message: Could not acquire required component services.  
  
[ER\\_FIREWALL\\_SERVICES\\_NOT\\_ACQUIRED](#) was added in 8.0.23.
-

- 
- Error number: `MY-013704`; Symbol: `ER_FIREWALL_UDF_REGISTER_FAILED`; SQLSTATE: `HY000`  
Message: Automatic registration of function(s) failed.  
`ER_FIREWALL_UDF_REGISTER_FAILED` was added in 8.0.23.
  - Error number: `MY-013705`; Symbol: `ER_FIREWALL_PFS_TABLE_REGISTER_FAILED`; SQLSTATE: `HY000`  
Message: Automatic registration of Performance schema table(s) failed.  
`ER_FIREWALL_PFS_TABLE_REGISTER_FAILED` was added in 8.0.23.
  - Error number: `MY-013706`; Symbol: `ER_IB_MSG_STATS_SAMPLING_TOO_LARGE`; SQLSTATE: `HY000`  
Message: %s  
`ER_IB_MSG_STATS_SAMPLING_TOO_LARGE` was added in 8.0.23.
  - Error number: `MY-013707`; Symbol: `ER_AUDIT_LOG_FILE_PRUNE_FAILED`; SQLSTATE: `HY000`  
Message: Failed to auto-prune file '%s', Error (%d): %s  
`ER_AUDIT_LOG_FILE_PRUNE_FAILED` was added in 8.0.24.
  - Error number: `MY-013708`; Symbol: `ER_AUDIT_LOG_FILE_AUTO_PRUNED`; SQLSTATE: `HY000`  
Message: File '%s' auto-pruned  
`ER_AUDIT_LOG_FILE_AUTO_PRUNED` was added in 8.0.24.
  - Error number: `MY-013709`; Symbol: `ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT`; SQLSTATE: `HY000`  
Message: Received an error while processing components from manifest file: %s  
`ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT` was added in 8.0.24.
  - Error number: `MY-013710`; Symbol: `ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT`; SQLSTATE: `HY000`  
Message: Received an error while unloading components read from manifest file: %s  
`ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT` was added in 8.0.24.
  - Error number: `MY-013711`; Symbol: `ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_NOT_RO`; SQLSTATE: `HY000`  
Message: Manifest file '%s' is not read-only. For better security, please make sure that the file is read-only.  
`ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_NOT_RO` was added in 8.0.24.
  - Error number: `MY-013712`; Symbol: `ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND`; SQLSTATE: `HY000`  
Message: No suitable '%s' service implementation found to fulfill the request.  
`ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND` was added in 8.0.24.

- 
- Error number: `MY-013713`; Symbol: `ER_NOTE_KEYRING_COMPONENT_INITIALIZED`; SQLSTATE: `HY000`  
Message: Keyring component initialized successfully.  
`ER_NOTE_KEYRING_COMPONENT_INITIALIZED` was added in 8.0.24.
  - Error number: `MY-013714`; Symbol: `ER_KEYRING_COMPONENT_NOT_INITIALIZED`; SQLSTATE: `HY000`  
Message: The component is not initialized properly. Make sure that configuration is proper and use `ALTER INSTANCE RELOAD KEYRING` to reinitialize the component.  
`ER_KEYRING_COMPONENT_NOT_INITIALIZED` was added in 8.0.24.
  - Error number: `MY-013715`; Symbol: `ER_KEYRING_COMPONENT_EXCEPTION`; SQLSTATE: `HY000`  
Message: Keyring component encountered an exception while executing : '%s' API of service: '%s'  
`ER_KEYRING_COMPONENT_EXCEPTION` was added in 8.0.24.
  - Error number: `MY-013716`; Symbol: `ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR`; SQLSTATE: `HY000`  
Message: Failed to allocated memory for '%s' while executing: '%s' API of service: '%s'  
`ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR` was added in 8.0.24.
  - Error number: `MY-013717`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE_BLOCK_SIZE`; SQLSTATE: `HY000`  
Message: Empty or 0 values for AES encryption mode and/or block size are not permitted.  
`ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE_BLOCK_SIZE` was added in 8.0.24.
  - Error number: `MY-013718`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER_EMPTY`; SQLSTATE: `HY000`  
Message: A valid data identifier is required in order to fetch the key required for the AES operation.  
`ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER_EMPTY` was added in 8.0.24.
  - Error number: `MY-013719`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY`; SQLSTATE: `HY000`  
Message: Key identified by Data ID: '%s' and Auth ID: '%s' is not of type AES.  
`ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY` was added in 8.0.24.
  - Error number: `MY-013720`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR`; SQLSTATE: `HY000`  
Message: Encountered error: '%s' while executing '%s' API of keyring\_aes service. Key details are Data ID: '%s' and Auth ID: '%s'.  
`ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR` was added in 8.0.24.
  - Error number: `MY-013721`; Symbol: `ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND`; SQLSTATE: `HY000`

---

Message: Could not find the data corresponding to Data ID: '%s', Auth ID: '%s'.

[ER\\_NOTE\\_KEYRING\\_COMPONENT\\_READ\\_DATA\\_NOT\\_FOUND](#) was added in 8.0.24.

- Error number: [MY-013722](#); Symbol: [ER\\_NOTE\\_KEYRING\\_COMPONENT\\_WRITE\\_MAXIMUM\\_DATA\\_LENGTH](#); SQLSTATE: [HY000](#)

Message: Maximum permissible size of data is '%zu' bits

[ER\\_NOTE\\_KEYRING\\_COMPONENT\\_WRITE\\_MAXIMUM\\_DATA\\_LENGTH](#) was added in 8.0.24.

- Error number: [MY-013723](#); Symbol: [ER\\_NOTE\\_KEYRING\\_COMPONENT\\_STORE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error writing data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.

[ER\\_NOTE\\_KEYRING\\_COMPONENT\\_STORE\\_FAILED](#) was added in 8.0.24.

- Error number: [MY-013724](#); Symbol: [ER\\_NOTE\\_KEYRING\\_COMPONENT\\_REMOVE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error removing data for Data ID: '%s', Auth ID: '%s'. Either data does not exists with same identifier or keyring backend encountered an error.

[ER\\_NOTE\\_KEYRING\\_COMPONENT\\_REMOVE\\_FAILED](#) was added in 8.0.24.

- Error number: [MY-013725](#); Symbol: [ER\\_NOTE\\_KEYRING\\_COMPONENT\\_GENERATE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error generating data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.

[ER\\_NOTE\\_KEYRING\\_COMPONENT\\_GENERATE\\_FAILED](#) was added in 8.0.24.

- Error number: [MY-013726](#); Symbol: [ER\\_NOTE\\_KEYRING\\_COMPONENT\\_KEYS\\_METADATA\\_ITERATOR\\_FETCH\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to get metadata from current keys metadata iterator position.

[ER\\_NOTE\\_KEYRING\\_COMPONENT\\_KEYS\\_METADATA\\_ITERATOR\\_FETCH\\_FAILED](#) was added in 8.0.24.

- Error number: [MY-013727](#); Symbol: [ER\\_NOTE\\_KEYRING\\_COMPONENT\\_METADATA\\_ITERATOR\\_INVALID\\_OUT\\_PARAM](#); SQLSTATE: [HY000](#)

Message: Key and value length parameters must not be null.

[ER\\_NOTE\\_KEYRING\\_COMPONENT\\_METADATA\\_ITERATOR\\_INVALID\\_OUT\\_PARAM](#) was added in 8.0.24.

- Error number: [MY-013728](#); Symbol: [ER\\_IB\\_WRN\\_FAILED\\_TO\\_ACQUIRE\\_SERVICE](#); SQLSTATE: [HY000](#)

Message: Innodb could not acquire service : %s

[ER\\_IB\\_WRN\\_FAILED\\_TO\\_ACQUIRE\\_SERVICE](#) was added in 8.0.24.

- Error number: [MY-013729](#); Symbol: [ER\\_IB\\_WRN\\_OLD\\_GEOMETRY\\_TYPE](#); SQLSTATE: [HY000](#)

---

Message: Column %s of type GEOMETRY is in old (5.6) format which could be deprecated in the future. To change the format to latest, please consider rebuilding the table after the upgrade.

[ER\\_IB\\_WRN\\_OLD\\_GEOMETRY\\_TYPE](#) was added in 8.0.24.

- Error number: [MY-013730](#); Symbol: [ER\\_NET\\_WAIT\\_ERROR2](#); SQLSTATE: [HY000](#)

Message: 'wait\_timeout' period of %s seconds was exceeded for %s. The idle time since last command was too long.

[ER\\_NET\\_WAIT\\_ERROR2](#) was added in 8.0.26.

- Error number: [MY-013731](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_TRIGGERED](#); SQLSTATE: [HY000](#)

Message: The member action "%s" for event "%s" with priority "%u" will be run.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_TRIGGERED](#) was added in 8.0.26.

- Error number: [MY-013732](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_FAILURE\\_IGNORE](#); SQLSTATE: [HY000](#)

Message: The member action "%s" for event "%s" with priority "%u" failed, this error is ignored as instructed. Please check previous messages in the error log for hints about what could have caused this failure.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_FAILURE\\_IGNORE](#) was added in 8.0.26.

- Error number: [MY-013733](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: The member action "%s" for event "%s" with priority "%u" failed. Please check previous messages in the error log for hints about what could have caused this failure.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_FAILURE](#) was added in 8.0.26.

- Error number: [MY-013734](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_PARSE\\_ON\\_RECEIVE](#); SQLSTATE: [HY000](#)

Message: Unable to parse the member actions configuration sent by the primary.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_PARSE\\_ON\\_RECEIVE](#) was added in 8.0.26.

- Error number: [MY-013735](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UPDATE\\_ACTIONS](#); SQLSTATE: [HY000](#)

Message: Unable to update the member actions configuration with the one sent by the primary. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version'.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UPDATE\\_ACTIONS](#) was added in 8.0.26.

- Error number: [MY-013736](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_GET\\_EXCHANGEABLE\\_DATA](#); SQLSTATE: [HY000](#)

Message: Unable to read the member actions configuration during group membership change. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version'.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_GET\\_EXCHANGEABLE\\_DATA](#) was added in 8.0.26.

- 
- Error number: [MY-013737](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_DEFAULT\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: This member joined a group on which all members do not support member actions, as such it did reset its member configuration to the default one.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_DEFAULT\\_CONFIGURATION](#) was added in 8.0.26.

- Error number: [MY-013738](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UNABLE\\_TO\\_SET\\_DEFAULT\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Unable to reset to member actions default configuration on member join. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version'.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UNABLE\\_TO\\_SET\\_DEFAULT\\_CONFIGURATION](#) was added in 8.0.26.

- Error number: [MY-013739](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_PARSE\\_ON\\_MEMBER\\_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to parse the member actions configuration sent by the group on member join.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_PARSE\\_ON\\_MEMBER\\_JOIN](#) was added in 8.0.26.

- Error number: [MY-013740](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UPDATE\\_ACTIONS\\_ON\\_MEMBER\\_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to update the member actions configuration on member join. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version'.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UPDATE\\_ACTIONS\\_ON\\_MEMBER\\_JOIN](#) was added in 8.0.26.

- Error number: [MY-013741](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_INVALID\\_ACTIONS\\_ON\\_MEMBER\\_JOIN](#); SQLSTATE: [HY000](#)

Message: The group members were unable to send their member actions configuration. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version' on all members.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_INVALID\\_ACTIONS\\_ON\\_MEMBER\\_JOIN](#) was added in 8.0.26.

- Error number: [MY-013742](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_ENABLED](#); SQLSTATE: [HY000](#)

Message: Member action enabled: "%s", type: "%s", event: "%s", priority: "%u", error\_handling: "%s".

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_ENABLED](#) was added in 8.0.26.

- Error number: [MY-013743](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_DISABLED](#); SQLSTATE: [HY000](#)

Message: Member action disabled: "%s", type: "%s", event: "%s", priority: "%u", error\_handling: "%s".

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_DISABLED](#) was added in 8.0.26.

- Error number: [MY-013744](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTIONS\\_RESET](#); SQLSTATE: [HY000](#)

Message: Member actions configuration was reset.

[ER\\_GRP\\_RPL\\_MEMBER\\_ACTIONS\\_RESET](#) was added in 8.0.26.

- Error number: [MY-013745](#); Symbol: [ER\\_DEPRECATED\\_TLS\\_VERSION\\_SESSION](#); SQLSTATE: [HY000](#)

---

Message: Accepted a connection with deprecated protocol '%s' for account '%s'@'%s' from host '%s'. Client supplied username '%s'

[ER\\_DEPRECATED\\_TLS\\_VERSION\\_SESSION](#) was added in 8.0.26, removed after 8.0.27.

- Error number: [MY-013746](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_TLS\\_VERSION\\_FOR\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: A deprecated TLS version %s is enabled for channel %s

[ER\\_WARN\\_DEPRECATED\\_TLS\\_VERSION\\_FOR\\_CHANNEL](#) was added in 8.0.26, removed after 8.0.27.

- Error number: [MY-013747](#); Symbol: [ER\\_FIREWALL\\_DEPRECATED\\_USER\\_PROFILE](#); SQLSTATE: [HY000](#)

Message: User profile '%s\ ' loaded. Firewall user profiles are deprecated, consider migrating to group profiles.

[ER\\_FIREWALL\\_DEPRECATED\\_USER\\_PROFILE](#) was added in 8.0.26.

- Error number: [MY-013748](#); Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_INVALID](#); SQLSTATE: [HY000](#)

Message: Invalid input value for group\_replication\_view\_change\_uuid '%s'. Please, provide a valid UUID.

[ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_INVALID](#) was added in 8.0.26.

- Error number: [MY-013749](#); Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_SAME\\_AS\\_GROUP\\_NAME](#); SQLSTATE: [HY000](#)

Message: Variable 'group\_replication\_view\_change\_uuid' cannot be set to the value of '%s'. If you want to use the UUID of 'group\_replication\_group\_name' for the UUID of View\_change\_log\_events, please set 'group\_replication\_view\_change\_uuid' to AUTOMATIC.

[ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_SAME\\_AS\\_GROUP\\_NAME](#) was added in 8.0.26.

- Error number: [MY-013750](#); Symbol: [ER\\_GRP\\_RPL\\_GROUP\\_NAME\\_SAME\\_AS\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: [HY000](#)

Message: group\_replication\_group\_name '%s', which is the same as group\_replication\_view\_change\_uuid. Please change group\_replication\_view\_change\_uuid to AUTOMATIC

[ER\\_GRP\\_RPL\\_GROUP\\_NAME\\_SAME\\_AS\\_VIEW\\_CHANGE\\_UUID](#) was added in 8.0.26.

- Error number: [MY-013751](#); Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_IS\\_SAME\\_AS\\_ANONYMOUS\\_TO\\_GTID\\_UUID](#); SQLSTATE: [HY000](#)

Message: The group\_replication\_view\_change\_uuid '%s' is the same as the UUID value for ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS in a server channel

[ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_IS\\_SAME\\_AS\\_ANONYMOUS\\_TO\\_GTID\\_UUID](#) was added in 8.0.26.

- Error number: [MY-013752](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_VIEW\\_CHANGE\\_UUID\\_IS\\_INCOMPATIBLE\\_WITH\\_SERVER\\_UUID](#); SQLSTATE: [HY000](#)

---

Message: group\_replication\_view\_change\_uuid is incompatible with group.  
group\_replication\_view\_change\_uuid %s matches server\_uuid %s.

[ER\\_GRP\\_RPL\\_GRP\\_VIEW\\_CHANGE\\_UUID\\_IS\\_INCOMPATIBLE\\_WITH\\_SERVER\\_UUID](#) was added in 8.0.26.

- Error number: MY-013753; Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_DIFF\\_FROM\\_GRP](#); SQLSTATE: HY000

Message: The member is configured with a group\_replication\_view\_change\_uuid option value '%s' different from the group '%s'. The member will now exit the group.

[ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_DIFF\\_FROM\\_GRP](#) was added in 8.0.26.

- Error number: MY-013754; Symbol: [ER\\_WARN\\_REPLICA\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: HY000

Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'` which is equal to `group_replication_view_change_uuid`. To fix this issue, either change the `group_replication_view_change_uuid` or use a different value for `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS`.

[ER\\_WARN\\_REPLICA\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_VIEW\\_CHANGE\\_UUID](#) was added in 8.0.26.

- Error number: MY-013755; Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_PARSE\\_THE\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: HY000

Message: Unable to parse the `group_replication_view_change_uuid`.

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_PARSE\\_THE\\_VIEW\\_CHANGE\\_UUID](#) was added in 8.0.26.

- Error number: MY-013756; Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_GENERATE\\_SIDNO\\_FOR\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: HY000

Message: Unable to generate sidno for `group_replication_view_change_uuid`.

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_GENERATE\\_SIDNO\\_FOR\\_VIEW\\_CHANGE\\_UUID](#) was added in 8.0.26.

- Error number: MY-013757; Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_PARSE\\_ERROR](#); SQLSTATE: HY000

Message: Unable to parse the `group_replication_view_change_uuid` during the Certification module initialization.

[ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_PARSE\\_ERROR](#) was added in 8.0.26.

- Error number: MY-013758; Symbol: [ER\\_GRP\\_RPL\\_UPDATE\\_GRPGTID\\_VIEW\\_CHANGE\\_UUID\\_EXECUTED\\_ERROR](#); SQLSTATE: HY000

Message: Error updating `group_gtid_executed` GTID set with view change uuid during the Certification module initialization.

[ER\\_GRP\\_RPL\\_UPDATE\\_GRPGTID\\_VIEW\\_CHANGE\\_UUID\\_EXECUTED\\_ERROR](#) was added in 8.0.26.



- 
- Error number: `MY-013759`; Symbol: `ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP_ERROR`; SQLSTATE: `HY000`  
Message: Unable to add the group\_replication\_view\_change\_uuid sidno in the group\_gtid\_sid\_map during the Certification module initialization.  
`ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP_ERROR` was added in 8.0.26.
  - Error number: `MY-013760`; Symbol: `ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR`; SQLSTATE: `HY000`  
Message: Unable to handle the donor's view change uuid transaction information when initializing the conflict detection component. Possible out of memory error.  
`ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR` was added in 8.0.26.
  - Error number: `MY-013761`; Symbol: `ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE`; SQLSTATE: `HY000`  
Message: Unable to retrieve group\_replication\_view\_change\_uuid during server checks on replication operations.  
`ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE` was added in 8.0.26.
  - Error number: `MY-013762`; Symbol: `ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS_LOG`; SQLSTATE: `HY000`  
Message: Both audit\_log\_max\_size and audit\_log\_prune\_seconds are set to non-zero. audit\_log\_max\_size takes precedence and audit\_log\_prune\_seconds is ignored  
`ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS_LOG` was added in 8.0.26.
  - Error number: `MY-013763`; Symbol: `ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE_LOG`; SQLSTATE: `HY000`  
Message: audit\_log\_rotate\_on\_size is not granular enough for the value of audit\_log\_max\_size supplied. Should be at least %d times smaller.  
`ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE_LOG` was added in 8.0.26.
  - Error number: `MY-013764`; Symbol: `ER_PLUGIN_INVALID_TABLE_DEFINITION`; SQLSTATE: `HY000`  
Message: Invalid table definition for '%s.%s'.  
`ER_PLUGIN_INVALID_TABLE_DEFINITION` was added in 8.0.26.
  - Error number: `MY-013765`; Symbol: `ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG`; SQLSTATE: `HY000`  
Message: %s  
`ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG` was added in 8.0.26.
  - Error number: `MY-013766`; Symbol: `ER_INSTALL_PLUGIN_CONFLICT_LOG`; SQLSTATE: `HY000`  
Message: Cannot install the %s plugin when the %s plugin is installed.  
`ER_INSTALL_PLUGIN_CONFLICT_LOG` was added in 8.0.26.
-

- 
- Error number: [MY-013767](#); Symbol: [ER\\_DEPRECATED\\_PERSISTED\\_VARIABLE\\_WITH\\_ALIAS](#); SQLSTATE: [HY000](#)

Message: The variable %s has been renamed to %s, and the old name deprecated. Only the old name was found in the persisted variable file. Next time the file is saved, both names will be stored. Issue any SET PERSIST command to save the file, get rid of this warning, and prepare the persisted configuration for when the variable is removed in a future version.

[ER\\_DEPRECATED\\_PERSISTED\\_VARIABLE\\_WITH\\_ALIAS](#) was added in 8.0.26.

- Error number: [MY-013768](#); Symbol: [ER\\_LOG\\_COMPONENT\\_FLUSH\\_FAILED](#); SQLSTATE: [HY000](#)

Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush file-based logs may affect log-rotation.

[ER\\_LOG\\_COMPONENT\\_FLUSH\\_FAILED](#) was added in 8.0.26.

- Error number: [MY-013769](#); Symbol: [ER\\_IB\\_MSG\\_REENCRYPTED\\_TABLESPACE\\_KEY](#); SQLSTATE: [HY000](#)

Message: Tablespace key for %s has been re-encrypted using the latest InnoDB master key. However, we recommend that you rebuild the table for better security.

[ER\\_IB\\_MSG\\_REENCRYPTED\\_TABLESPACE\\_KEY](#) was added in 8.0.26.

- Error number: [MY-013770](#); Symbol: [ER\\_IB\\_MSG\\_REENCRYPTED\\_GENERAL\\_TABLESPACE\\_KEY](#); SQLSTATE: [HY000](#)

Message: Tablespace key for %s has been re-encrypted using the latest InnoDB master key. However, we recommend that you reencrypt the tablespace for better security.

[ER\\_IB\\_MSG\\_REENCRYPTED\\_GENERAL\\_TABLESPACE\\_KEY](#) was added in 8.0.26.

- Error number: [MY-013771](#); Symbol: [ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_DBLWR\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Page Archiver's doublewrite buffer initialisation failed. Page tracking is at risk of losing tracked information.

[ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_DBLWR\\_INIT\\_FAILED](#) was added in 8.0.26.

- Error number: [MY-013772](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_NO\\_SPACE\\_IN\\_REDO\\_LOG\\_\\_SKIP\\_IBUF\\_MERGES](#); SQLSTATE: [HY000](#)

Message: There is not enough free space in the redo log during recovery to perform pending ibuf merges. Please retry starting MySQL with --innodb-force-recovery=4.

[ER\\_IB\\_MSG\\_RECOVERY\\_NO\\_SPACE\\_IN\\_REDO\\_LOG\\_\\_SKIP\\_IBUF\\_MERGES](#) was added in 8.0.26.

- Error number: [MY-013773](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_NO\\_SPACE\\_IN\\_REDO\\_LOG\\_\\_UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: There is not enough free space in the redo log during recovery, restore from backup (or retry with --innodb-force-recovery=6).

[ER\\_IB\\_MSG\\_RECOVERY\\_NO\\_SPACE\\_IN\\_REDO\\_LOG\\_\\_UNEXPECTED](#) was added in 8.0.26.

- 
- Error number: [MY-013774](#); Symbol: [ER\\_WARN\\_AUDIT\\_LOG\\_FORMAT\\_UNIX\\_TIMESTAMP\\_ONLY\\_WHEN\\_JSON\\_LOG](#); SQLSTATE: [HY000](#)  
Message: `audit_log_format_unix_timestamp` is applicable only when `audit_log_format = JSON`.  
[ER\\_WARN\\_AUDIT\\_LOG\\_FORMAT\\_UNIX\\_TIMESTAMP\\_ONLY\\_WHEN\\_JSON\\_LOG](#) was added in 8.0.26.
  - Error number: [MY-013775](#); Symbol: [ER\\_PREPARE\\_FOR\\_PRIMARY\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: Retry the statement using the primary storage engine.  
[ER\\_PREPARE\\_FOR\\_PRIMARY\\_ENGINE](#) was added in 8.0.26.
  - Error number: [MY-013776](#); Symbol: [ER\\_IB\\_MSG\\_PAR\\_RSEG\\_INIT\\_COMPLETE\\_MSG](#); SQLSTATE: [HY000](#)  
Message: Parallel initialization of rseg complete  
[ER\\_IB\\_MSG\\_PAR\\_RSEG\\_INIT\\_COMPLETE\\_MSG](#) was added in 8.0.27.
  - Error number: [MY-013777](#); Symbol: [ER\\_IB\\_MSG\\_PAR\\_RSEG\\_INIT\\_TIME\\_MSG](#); SQLSTATE: [HY000](#)  
Message: Time taken to initialize rseg using %u thread: %u ms.  
[ER\\_IB\\_MSG\\_PAR\\_RSEG\\_INIT\\_TIME\\_MSG](#) was added in 8.0.27.
  - Error number: [MY-013778](#); Symbol: [ER\\_DDL\\_MSG\\_1](#); SQLSTATE: [HY000](#)  
Message: DDL failed to create a thread to load an index, fall back to single thread  
[ER\\_DDL\\_MSG\\_1](#) was added in 8.0.27.
  - Error number: [MY-013779](#); Symbol: [ER\\_MTR\\_MSG\\_1](#); SQLSTATE: [HY000](#)  
Message: `Debug_check_no_latching` failed, `slot->type=%d`  
[ER\\_MTR\\_MSG\\_1](#) was added in 8.0.27.
  - Error number: [MY-013780](#); Symbol: [ER\\_GRP\\_RPL\\_MYSQL\\_NETWORK\\_PROVIDER\\_CLIENT\\_ERROR\\_CONN\\_ERR](#); SQLSTATE: [HY000](#)  
Message: Failed to establish MySQL client connection in Group Replication. Error establishing connection. Please refer to the manual to make sure that you configured Group Replication properly to work with MySQL Protocol connections.  
[ER\\_GRP\\_RPL\\_MYSQL\\_NETWORK\\_PROVIDER\\_CLIENT\\_ERROR\\_CONN\\_ERR](#) was added in 8.0.27.
  - Error number: [MY-013781](#); Symbol: [ER\\_GRP\\_RPL\\_MYSQL\\_NETWORK\\_PROVIDER\\_CLIENT\\_ERROR\\_COMMAND\\_ERR](#); SQLSTATE: [HY000](#)  
Message: Failed to establish MySQL client connection in Group Replication. Error sending connection delegation command. Please refer to the manual to make sure that you configured Group Replication properly to work with MySQL Protocol connections.  
[ER\\_GRP\\_RPL\\_MYSQL\\_NETWORK\\_PROVIDER\\_CLIENT\\_ERROR\\_COMMAND\\_ERR](#) was added in 8.0.27.
  - Error number: [MY-013782](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_GET\\_EXCHANGEABLE\\_DATA](#); SQLSTATE: [HY000](#)

---

Message: Unable to read the replication failover channels configuration during group membership change. Please check the tables 'mysql.replication\_asynchronous\_connection\_failover', 'mysql.replication\_asynchronous\_connection\_failover\_managed' and 'mysql.replication\_group\_configuration\_version'.

[ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_GET\\_EXCHANGEABLE\\_DATA](#) was added in 8.0.27.

- Error number: [MY-013783](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_DEFAULT\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: This member joined a group on which all members do not support replication failover channels integration on Group Replication, as such it did reset its replication failover channels configuration to the default one.

[ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_DEFAULT\\_CONFIGURATION](#) was added in 8.0.27.

- Error number: [MY-013784](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_UNABLE\\_TO\\_SET\\_DEFAULT\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Unable to reset to replication failover channels default configuration on member join. Please check the tables 'mysql.replication\_asynchronous\_connection\_failover', 'mysql.replication\_asynchronous\_connection\_failover\_managed' and 'mysql.replication\_group\_configuration\_version'.

[ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_UNABLE\\_TO\\_SET\\_DEFAULT\\_CONFIGURATION](#) was added in 8.0.27.

- Error number: [MY-013785](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_PARSE\\_ON\\_MEMBER\\_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to parse the replication failover channels configuration sent by the group on member join.

[ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_PARSE\\_ON\\_MEMBER\\_JOIN](#) was added in 8.0.27.

- Error number: [MY-013786](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_CHANNEL\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)

Message: Unable to set SOURCE\_CONNECTION\_AUTO\_FAILOVER on a non-existent or misconfigured replication channel '%s', please create the channel and rejoin the server to the group.

[ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_CHANNEL\\_DOES\\_NOT\\_EXIST](#) was added in 8.0.27.

- Error number: [MY-013787](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_REGISTER\\_MESSAGE\\_LISTENER\\_SERVICE](#); SQLSTATE: [HY000](#)

Message: Unable to register the listener 'replication\_asynchronous\_connection\_failover\_configuration' to the service 'group\_replication\_message\_service\_rcv'.

[ER\\_GRP\\_RPL\\_FAILOVER\\_REGISTER\\_MESSAGE\\_LISTENER\\_SERVICE](#) was added in 8.0.27.

- Error number: [MY-013788](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_PRIMARY\\_WITHOUT\\_MAJORITY](#); SQLSTATE: [HY000](#)

Message: This server is not able to reach a majority of members in the group. This server will skip the replication failover channels handling until this server is back to the group majority.

[ER\\_GRP\\_RPL\\_FAILOVER\\_PRIMARY\\_WITHOUT\\_MAJORITY](#) was added in 8.0.27.

- 
- Error number: [MY-013789](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_PRIMARY\\_BACK\\_TO\\_MAJORITY](#); SQLSTATE: [HY000](#)  
  
Message: This server is back to the group majority. Replication failover channels handling is resumed.  
  
[ER\\_GRP\\_RPL\\_FAILOVER\\_PRIMARY\\_BACK\\_TO\\_MAJORITY](#) was added in 8.0.27.
  - Error number: [MY-013790](#); Symbol: [ER\\_RPL\\_INCREMENTING\\_MEMBER\\_ACTION\\_VERSION](#); SQLSTATE: [HY000](#)  
  
Message: Error incrementing member action configuration version for %s.%s table.  
  
[ER\\_RPL\\_INCREMENTING\\_MEMBER\\_ACTION\\_VERSION](#) was added in 8.0.27.
  - Error number: [MY-013791](#); Symbol: [ER\\_GRP\\_RPL\\_SLAVE\\_THREAD\\_ERROR\\_ON\\_SECONDARY\\_MEMBER](#); SQLSTATE: [HY000](#)  
  
Message: The '%s' thread of channel '%s' will error out as this server is a group secondary.  
  
[ER\\_GRP\\_RPL\\_SLAVE\\_THREAD\\_ERROR\\_ON\\_SECONDARY\\_MEMBER](#) was added in 8.0.27, removed after 8.0.32.
  - Error number: [MY-013791](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_THREAD\\_ERROR\\_ON\\_SECONDARY\\_MEMBER](#); SQLSTATE: [HY000](#)  
  
Message: The '%s' thread of channel '%s' will error out as this server is a group secondary.  
  
[ER\\_GRP\\_RPL\\_REPLICA\\_THREAD\\_ERROR\\_ON\\_SECONDARY\\_MEMBER](#) was added in 8.0.33.
  - Error number: [MY-013792](#); Symbol: [ER\\_IB\\_MSG\\_CLONE\\_DDL\\_NTFN](#); SQLSTATE: [HY000](#)  
  
Message: Clone DDL Notification: %s  
  
[ER\\_IB\\_MSG\\_CLONE\\_DDL\\_NTFN](#) was added in 8.0.27.
  - Error number: [MY-013793](#); Symbol: [ER\\_IB\\_MSG\\_CLONE\\_DDL\\_APPLY](#); SQLSTATE: [HY000](#)  
  
Message: Clone DDL APPLY: %s  
  
[ER\\_IB\\_MSG\\_CLONE\\_DDL\\_APPLY](#) was added in 8.0.27.
  - Error number: [MY-013794](#); Symbol: [ER\\_IB\\_MSG\\_CLONE\\_DDL\\_INVALIDATE](#); SQLSTATE: [HY000](#)  
  
Message: Clone DDL Invalidate : %s  
  
[ER\\_IB\\_MSG\\_CLONE\\_DDL\\_INVALIDATE](#) was added in 8.0.27.
  - Error number: [MY-013795](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_ENCRYPTION\\_INFO\\_LOADED](#); SQLSTATE: [HY000](#)  
  
Message: Encryption key is loaded for undo tablespace '%s'.  
  
[ER\\_IB\\_MSG\\_UNDO\\_ENCRYPTION\\_INFO\\_LOADED](#) was added in 8.0.27.

- 
- Error number: `MY-013796`; Symbol: `ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH`; SQLSTATE: `HY000`  
  
Message: Ignoring encryption INFO size in redo log: %zu, expected: %zu  
  
`ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH` was added in 8.0.27.
  - Error number: `MY-013797`; Symbol: `ER_INVALID_AUTHENTICATION_POLICY`; SQLSTATE: `HY000`  
  
Message: Option `--authentication-policy` is set to an invalid value. Please check if the specified authentication plugins are valid.  
  
`ER_INVALID_AUTHENTICATION_POLICY` was added in 8.0.27.
  - Error number: `MY-013798`; Symbol: `ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED`; SQLSTATE: `HY000`  
  
Message: Signature verification failed during registration.  
  
`ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED` was added in 8.0.27.
  - Error number: `MY-013799`; Symbol: `ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT_BUFFER`; SQLSTATE: `HY000`  
  
Message: Buffer too small to hold registration challenge response.  
  
`ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT_BUFFER` was added in 8.0.27.
  - Error number: `MY-013800`; Symbol: `ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT`; SQLSTATE: `HY000`  
  
Message: FIDO device authenticator data corrupt.  
  
`ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT` was added in 8.0.27.
  - Error number: `MY-013801`; Symbol: `ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT`; SQLSTATE: `HY000`  
  
Message: FIDO device signature corrupt.  
  
`ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT` was added in 8.0.27.
  - Error number: `MY-013802`; Symbol: `ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED`; SQLSTATE: `HY000`  
  
Message: Signature verification failed during authentication.  
  
`ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED` was added in 8.0.27.
  - Error number: `MY-013803`; Symbol: `ER_AUTHENTICATION_PLUGIN_OOM`; SQLSTATE: `HY000`  
  
Message: Out of memory.  
  
`ER_AUTHENTICATION_PLUGIN_OOM` was added in 8.0.27.

- 
- Error number: [MY-013804](#); Symbol: [ER\\_AUTHENTICATION\\_PLUGIN\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Can't initialize logging service  
[ER\\_AUTHENTICATION\\_PLUGIN\\_LOG](#) was added in 8.0.27.
  - Error number: [MY-013805](#); Symbol: [ER\\_WARN\\_REPLICA\\_GTID\\_ONLY\\_AND\\_GTID\\_MODE\\_NOT\\_ON](#); SQLSTATE: [HY000](#)  
Message: Replication channel '%s' is configured with GTID\_ONLY=1, which is invalid when GTID\_MODE <> ON. If you intend to disable GTIDs in the replication topology, change GTID\_ONLY to 0.  
[ER\\_WARN\\_REPLICA\\_GTID\\_ONLY\\_AND\\_GTID\\_MODE\\_NOT\\_ON](#) was added in 8.0.27.
  - Error number: [MY-013806](#); Symbol: [ER\\_WARN\\_L\\_DISABLE\\_GTID\\_ONLY\\_WITH\\_SOURCE\\_AUTO\\_POS\\_INVALID\\_POS](#); SQLSTATE: [HY000](#)  
Message: The replication positions relative to the source may be out-of-date on channel '%s', due to the use of GTID\_ONLY=1. The out-of-date positions can still be used in some cases so, in order to update them, we suggest that you start the replication to receive and apply at least one transaction, which will set the positions to valid values.  
[ER\\_WARN\\_L\\_DISABLE\\_GTID\\_ONLY\\_WITH\\_SOURCE\\_AUTO\\_POS\\_INVALID\\_POS](#) was added in 8.0.27.
  - Error number: [MY-013807](#); Symbol: [ER\\_RPL\\_CANNOT\\_OPEN\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Could not open relay log: %s  
[ER\\_RPL\\_CANNOT\\_OPEN\\_RELAY\\_LOG](#) was added in 8.0.27.
  - Error number: [MY-013808](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_PLUGIN\\_NOT\\_INITIALIZED](#); SQLSTATE: [HY000](#)  
Message: Authentication plugin not initialized.  
[ER\\_AUTHENTICATION\\_OCI\\_PLUGIN\\_NOT\\_INITIALIZED](#) was added in 8.0.27.
  - Error number: [MY-013809](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_PRIVATE\\_KEY\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Cannot use the generated private key file.  
[ER\\_AUTHENTICATION\\_OCI\\_PRIVATE\\_KEY\\_ERROR](#) was added in 8.0.27.
  - Error number: [MY-013810](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_DOWNLOAD\\_PUBLIC\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Unavailable public key with fingerprint %s for user %s in tenancy %s .  
[ER\\_AUTHENTICATION\\_OCI\\_DOWNLOAD\\_PUBLIC\\_KEY](#) was added in 8.0.27.
  - Error number: [MY-013811](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_IMDS](#); SQLSTATE: [HY000](#)  
Message: Cannot obtain the OCI configuration from the IMDS service.  
[ER\\_AUTHENTICATION\\_OCI\\_IMDS](#) was added in 8.0.27.
  - Error number: [MY-013812](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_IAM](#); SQLSTATE: [HY000](#)
-

---

Message: Cannot initialize the IAM service.

[ER\\_AUTHENTICATION\\_OCI\\_IAM](#) was added in 8.0.27.

- Error number: [MY-013813](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_INVALID\\_AUTHENTICATION\\_STRING](#); SQLSTATE: [HY000](#)

Message: Invalid authentication string details for user: `%s`@`%s`.

[ER\\_AUTHENTICATION\\_OCI\\_INVALID\\_AUTHENTICATION\\_STRING](#) was added in 8.0.27.

- Error number: [MY-013814](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_NO\\_MATCHING\\_GROUPS](#); SQLSTATE: [HY000](#)

Message: None of the groups returned by IAM matches any of the entries from authentication string.

[ER\\_AUTHENTICATION\\_OCI\\_NO\\_MATCHING\\_GROUPS](#) was added in 8.0.27.

- Error number: [MY-013815](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_NO\\_GROUPS\\_FOUND](#); SQLSTATE: [HY000](#)

Message: User is not part of any groups. However, account is configured to use group mapping.

[ER\\_AUTHENTICATION\\_OCI\\_NO\\_GROUPS\\_FOUND](#) was added in 8.0.27.

- Error number: [MY-013816](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_NONCE](#); SQLSTATE: [HY000](#)

Message: Received OpenSSL error: %s while authenticating user %s with fingerprint %s in tenancy %s.

[ER\\_AUTHENTICATION\\_OCI\\_NONCE](#) was added in 8.0.27.

- Error number: [MY-013817](#); Symbol: [ER\\_HEALTH\\_WARNING\\_MEMORY\\_USAGE\\_LEVEL\\_1](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 1 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%0.2f%%, mysqlid=%llu MiB

[ER\\_HEALTH\\_WARNING\\_MEMORY\\_USAGE\\_LEVEL\\_1](#) was added in 8.0.27.

- Error number: [MY-013818](#); Symbol: [ER\\_HEALTH\\_WARNING\\_MEMORY\\_USAGE\\_LEVEL\\_2](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 2 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%0.2f%%, mysqlid=%llu MiB

[ER\\_HEALTH\\_WARNING\\_MEMORY\\_USAGE\\_LEVEL\\_2](#) was added in 8.0.27.

- Error number: [MY-013819](#); Symbol: [ER\\_HEALTH\\_WARNING\\_MEMORY\\_USAGE\\_LEVEL\\_3](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 3 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%0.2f%%, mysqlid=%llu MiB

[ER\\_HEALTH\\_WARNING\\_MEMORY\\_USAGE\\_LEVEL\\_3](#) was added in 8.0.27.

- Error number: [MY-013820](#); Symbol: [ER\\_GRP\\_RPL\\_SET\\_SINGLE\\_CONSENSUS\\_LEADER](#); SQLSTATE: [HY000](#)



---

Message: The member %s:%u, with UUID: %s, was set as the single preferred consensus leader.

[ER\\_GRP\\_RPL\\_SET\\_SINGLE\\_CONSENSUS\\_LEADER](#) was added in 8.0.27.

- Error number: [MY-013821](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_SET\\_SINGLE\\_CONSENSUS\\_LEADER](#); SQLSTATE: [HY000](#)

Message: Something went wrong trying to set the member %s:%u, with UUID: %s, as the single preferred consensus leader. Please query the `performance_schema.replication_group_communication_information` table to see whether the operation took effect, i.e. whether the preferred consensus leader matches the current primary. If not, consider electing a different primary to try again. Please check the error log and `GCS_DEBUG_TRACE` for more information that may help understanding what went wrong.

[ER\\_GRP\\_RPL\\_ERROR\\_SET\\_SINGLE\\_CONSENSUS\\_LEADER](#) was added in 8.0.27.

- Error number: [MY-013822](#); Symbol: [ER\\_GRP\\_RPL\\_SET\\_MULTI\\_CONSENSUS\\_LEADER](#); SQLSTATE: [HY000](#)

Message: All members were set as consensus leaders.

[ER\\_GRP\\_RPL\\_SET\\_MULTI\\_CONSENSUS\\_LEADER](#) was added in 8.0.27.

- Error number: [MY-013823](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_SET\\_MULTI\\_CONSENSUS\\_LEADER](#); SQLSTATE: [HY000](#)

Message: Something went wrong trying to set all members as consensus leaders. Please query the `performance_schema.replication_group_communication_information` table to see whether the operation took effect, i.e. whether the consensus leaders match all members. If not, consider resetting the group communication protocol to a version < 8.0.22, or switch to single-primary mode and back again to multi-primary mode, to try again. Please check the error log and `GCS_DEBUG_TRACE` for more information that may help understanding what went wrong.

[ER\\_GRP\\_RPL\\_ERROR\\_SET\\_MULTI\\_CONSENSUS\\_LEADER](#) was added in 8.0.27.

- Error number: [MY-013824](#); Symbol: [ER\\_GRP\\_RPL\\_PAXOS\\_SINGLE\\_LEADER\\_DIFF\\_FROM\\_GRP](#); SQLSTATE: [HY000](#)

Message: This member is configured with a `group_replication_paxos_single_leader` option value of '%d' that is different from the group's value ('%d'). This member will now exit the group.

[ER\\_GRP\\_RPL\\_PAXOS\\_SINGLE\\_LEADER\\_DIFF\\_FROM\\_GRP](#) was added in 8.0.27.

- Error number: [MY-013825](#); Symbol: [ER\\_MFA\\_USER\\_ATTRIBUTES\\_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Invalid and/or corrupted multi factor authentication methods in `User_attributes` column in `mysql.user` table. "%s".

[ER\\_MFA\\_USER\\_ATTRIBUTES\\_CORRUPT](#) was added in 8.0.27.

- Error number: [MY-013826](#); Symbol: [ER\\_MFA\\_PLUGIN\\_NOT\\_LOADED](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is not loaded; Ignoring user

[ER\\_MFA\\_PLUGIN\\_NOT\\_LOADED](#) was added in 8.0.27.

- Error number: [MY-013827](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_CHARSET\\_OPTION](#); SQLSTATE: [HY000](#)

---

Message: %s: The character set %s is deprecated and will be removed in a future release. Please consider using %s instead.

[ER\\_WARN\\_DEPRECATED\\_CHARSET\\_OPTION](#) was added in 8.0.28.

- Error number: [MY-013828](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_COLLATION\\_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: '%s' is a collation of the deprecated character set %s. Please consider using %s with an appropriate collation instead.

[ER\\_WARN\\_DEPRECATED\\_COLLATION\\_OPTION](#) was added in 8.0.28.

- Error number: [MY-013829](#); Symbol: [ER\\_REGEXP\\_MISSING\\_ICU\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: Missing data directory for ICU regular expressions: %s.

[ER\\_REGEXP\\_MISSING\\_ICU\\_DATADIR](#) was added in 8.0.28.

- Error number: [MY-013830](#); Symbol: [ER\\_IB\\_WARN\\_MANY\\_NON\\_LRU\\_FILES\\_OPENED](#); SQLSTATE: [HY000](#)

Message: More than 90%% of files opened out of the innodb\_open\_files limit are files that are not easy to close. The performance of system may degrade. Consider increasing value of the innodb\_open\_files system variable. There are %zu such files opened out of the total limit for all files opened of %zu.

[ER\\_IB\\_WARN\\_MANY\\_NON\\_LRU\\_FILES\\_OPENED](#) was added in 8.0.28.

- Error number: [MY-013831](#); Symbol: [ER\\_IB\\_MSG\\_TRYING\\_TO\\_OPEN\\_FILE\\_FOR\\_LONG\\_TIME](#); SQLSTATE: [HY000](#)

Message: Trying to open a file for %lld seconds. Configuration only allows for %zu open files. Consider setting innobase\_open\_files higher.

[ER\\_IB\\_MSG\\_TRYING\\_TO\\_OPEN\\_FILE\\_FOR\\_LONG\\_TIME](#) was added in 8.0.28.

- Error number: [MY-013832](#); Symbol: [ER\\_GLOBAL\\_CONN\\_LIMIT](#); SQLSTATE: [HY000](#)

Message: Connection closed. Global connection memory limit %llu bytes exceeded. Consumed %llu bytes.

[ER\\_GLOBAL\\_CONN\\_LIMIT](#) was added in 8.0.28.

- Error number: [MY-013833](#); Symbol: [ER\\_CONN\\_LIMIT](#); SQLSTATE: [HY000](#)

Message: Connection closed. Connection memory limit %llu bytes exceeded. Consumed %llu bytes.

[ER\\_CONN\\_LIMIT](#) was added in 8.0.28.

- Error number: [MY-013834](#); Symbol: [ER\\_WARN\\_AUDIT\\_LOG\\_DISABLED](#); SQLSTATE: [HY000](#)

Message: Audit Log is disabled. Enable it with audit\_log\_disable = false.

[ER\\_WARN\\_AUDIT\\_LOG\\_DISABLED](#) was added in 8.0.28.

- Error number: [MY-013835](#); Symbol: [ER\\_INVALID\\_TLS\\_VERSION](#); SQLSTATE: [HY000](#)

Message: Option --tls-version or --admin-tls-version is set to an invalid value %s.

---

`ER_INVALID_TLS_VERSION` was added in 8.0.28.

- Error number: `MY-013836`; Symbol: `ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY`; SQLSTATE: `HY000`

Message: Relay log recovery on channel with `GTID_ONLY=1`. The channel will switch to a new relay log and the GTID protocol will be used to replicate unapplied transactions.

`ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY` was added in 8.0.28.

- Error number: `MY-013837`; Symbol: `ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED`; SQLSTATE: `HY000`

Message: Number of `STANDBY_SERVER` values exceeded maximum limit of 64.

`ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED` was added in 8.0.29.

- Error number: `MY-013838`; Symbol: `ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING`; SQLSTATE: `HY000`

Message: Source keyring does not have any keys to migrate.

`ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING` was added in 8.0.29.

- Error number: `MY-013839`; Symbol: `ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES`; SQLSTATE: `HY000`

Message: Cannot persist `SENSITIVE` system variables because keyring component support is unavailable and `persist_sensitive_variables_in_plaintext` is set to `OFF`. Please make sure that keyring services are active and required keys are available.

`ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES` was added in 8.0.29.

- Error number: `MY-013840`; Symbol: `ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES`; SQLSTATE: `HY000`

Message: Cannot interpret persisted `SENSITIVE` system variables. Please make sure that keyring services are active and required keys are available.

`ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES` was added in 8.0.29.

- Error number: `MY-013841`; Symbol: `ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED`; SQLSTATE: `HY000`

Message: Keyring has to be loaded through manifest file in order to support secure storage for persisted variables

`ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED` was added in 8.0.29.

- Error number: `MY-013842`; Symbol: `ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND`; SQLSTATE: `HY000`

Message: Could not find master key %s in keyring

`ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND` was added in 8.0.29.

- Error number: `MY-013843`; Symbol: `ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_GENERATED`; SQLSTATE: `HY000`

---

Message: A new master key %s could not be generated

[ER\\_PERSISTED\\_VARIABLES\\_MASTER\\_KEY\\_CANNOT\\_BE\\_GENERATED](#) was added in 8.0.29.

- Error number: [MY-013844](#); Symbol: [ER\\_PERSISTED\\_VARIABLES\\_ENCRYPTION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to encrypt %s using %s

[ER\\_PERSISTED\\_VARIABLES\\_ENCRYPTION\\_FAILED](#) was added in 8.0.29.

- Error number: [MY-013845](#); Symbol: [ER\\_PERSISTED\\_VARIABLES\\_DECRYPTION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to decrypt %s using %s

[ER\\_PERSISTED\\_VARIABLES\\_DECRYPTION\\_FAILED](#) was added in 8.0.29.

- Error number: [MY-013846](#); Symbol: [ER\\_PERSISTED\\_VARIABLES\\_LACK\\_KEYRING\\_SUPPORT](#); SQLSTATE: [HY000](#)

Message: Persisting SENSITIVE variables in encrypted form requires keyring component loaded through manifest file.

[ER\\_PERSISTED\\_VARIABLES\\_LACK\\_KEYRING\\_SUPPORT](#) was added in 8.0.29.

- Error number: [MY-013847](#); Symbol: [ER\\_MY\\_MALLOC\\_USING\\_JEMALLOC](#); SQLSTATE: [HY000](#)

Message: Using jemalloc.dll for my\_malloc and ut::malloc etc.

[ER\\_MY\\_MALLOC\\_USING\\_JEMALLOC](#) was added in 8.0.29.

- Error number: [MY-013848](#); Symbol: [ER\\_MY\\_MALLOC\\_USING\\_STD\\_MALLOC](#); SQLSTATE: [HY000](#)

Message: %s.

[ER\\_MY\\_MALLOC\\_USING\\_STD\\_MALLOC](#) was added in 8.0.29.

- Error number: [MY-013849](#); Symbol: [ER\\_MY\\_MALLOC\\_LOADLIBRARY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: %s.

[ER\\_MY\\_MALLOC\\_LOADLIBRARY\\_FAILED](#) was added in 8.0.29.

- Error number: [MY-013850](#); Symbol: [ER\\_MY\\_MALLOC\\_GETPROCADDRESS\\_FAILED](#); SQLSTATE: [HY000](#)

Message: %s.

[ER\\_MY\\_MALLOC\\_GETPROCADDRESS\\_FAILED](#) was added in 8.0.29.

- Error number: [MY-013851](#); Symbol: [ER\\_ACCOUNT\\_WITH\\_EXPIRED\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Password for the account '%s'@'%s' has expired. To log in, either change it using a client that supports expired passwords or send the change request to an administrator.

[ER\\_ACCOUNT\\_WITH\\_EXPIRED\\_PASSWORD](#) was added in 8.0.29.

- Error number: [MY-013852](#); Symbol: [ER\\_THREAD\\_POOL\\_PLUGIN\\_STARTED](#); SQLSTATE: [HY000](#)

---

Message: Thread pool plugin started successfully with parameters: %s

[ER\\_THREAD\\_POOL\\_PLUGIN\\_STARTED](#) was added in 8.0.4.

- Error number: [MY-013853](#); Symbol: [ER\\_THREAD\\_POOL\\_DEDICATED\\_LISTENERS\\_INVALID](#); SQLSTATE: [HY000](#)

Message: thread\_pool\_dedicated\_listeners cannot be set unless thread\_pool\_max\_transactions\_limit > 0

[ER\\_THREAD\\_POOL\\_DEDICATED\\_LISTENERS\\_INVALID](#) was added in 8.0.29.

- Error number: [MY-013854](#); Symbol: [ER\\_IB\\_DBLWR\\_BYTES\\_INFO](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_DBLWR\\_BYTES\\_INFO](#) was added in 8.0.30.

- Error number: [MY-013855](#); Symbol: [ER\\_IB\\_RDBLWR\\_BYTES\\_INFO](#); SQLSTATE: [HY000](#)

Message: %s

[ER\\_IB\\_RDBLWR\\_BYTES\\_INFO](#) was added in 8.0.30.

- Error number: [MY-013856](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_IS\\_EMPTY](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is empty, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file or try recovering without the redo files, in read-only mode, by providing --innodb-force-recovery=6.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_IS\\_EMPTY](#) was added in 8.0.30.

- Error number: [MY-013857](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_TOO\\_SMALL](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is smaller than %llu bytes, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_TOO\\_SMALL](#) was added in 8.0.30.

- Error number: [MY-013858](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_TOO\\_BIG](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is larger than %llu bytes, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_TOO\\_BIG](#) was added in 8.0.30.

- Error number: [MY-013859](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_HEADER\\_READ\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to read header of the redo log file %s

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_HEADER\\_READ\\_FAILED](#) was added in 8.0.30.

- 
- Error number: `MY-013860`; Symbol: `ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE`; SQLSTATE: `HY000`  
Message: --initialize specified but the redo log directory %s has redo log files inside. Aborting.  
`ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE` was added in 8.0.30.
  - Error number: `MY-013861`; Symbol: `ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED`; SQLSTATE: `HY000`  
Message: Failed to list redo log files in the redo log directory %s  
`ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED` was added in 8.0.30.
  - Error number: `MY-013862`; Symbol: `ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR`; SQLSTATE: `HY000`  
Message: Neither found %s subdirectory, nor %s\* files in %s  
`ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR` was added in 8.0.30.
  - Error number: `MY-013863`; Symbol: `ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY_MODE`; SQLSTATE: `HY000`  
Message: Cannot restore cloned data directory, InnoDB running in read-only mode!  
`ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY_MODE` was added in 8.0.30.
  - Error number: `MY-013864`; Symbol: `ER_IB_MSG_LOG_WRITER_WRITE_FAILED`; SQLSTATE: `HY000`  
Message: Error %d encountered when writing to the redo log file: %s.  
`ER_IB_MSG_LOG_WRITER_WRITE_FAILED` was added in 8.0.30.
  - Error number: `MY-013865`; Symbol: `ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE`; SQLSTATE: `HY000`  
Message: Redo log writer is waiting for a new redo log file. Consider increasing `innodb_redo_log_capacity`.  
`ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE` was added in 8.0.30.
  - Error number: `MY-013866`; Symbol: `ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG_FILE`; SQLSTATE: `HY000`  
Message: Found checkpoint LSN %llu in a redo log file %s, but the file represents range of LSN values [%llu, %llu), so the file is corrupted.  
`ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG_FILE` was added in 8.0.30.
  - Error number: `MY-013867`; Symbol: `ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN`; SQLSTATE: `HY000`  
Message: Redo log is running out of free space, pausing user threads... Consider increasing `innodb_redo_log_capacity`.  
`ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN` was added in 8.0.30.
  - Error number: `MY-013868`; Symbol: `ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN`; SQLSTATE: `HY000`

---

Message: Redo log reclaimed some free space, resuming user threads.

`ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN` was added in 8.0.30.

- Error number: `MY-013869`; Symbol: `ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED`; SQLSTATE: `HY000`

Message: Ignored deprecated configuration parameter `innodb_log_file_size`. Used `innodb_redo_log_capacity` instead.

`ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED` was added in 8.0.30.

- Error number: `MY-013870`; Symbol: `ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED`; SQLSTATE: `HY000`

Message: Ignored deprecated configuration parameter `innodb_log_files_in_group`. Used `innodb_redo_log_capacity` instead.

`ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED` was added in 8.0.30.

- Error number: `MY-013871`; Symbol: `ER_IB_MSG_LOG_UPGRADE_FORCED_RECV`; SQLSTATE: `HY000`

Message: Cannot upgrade format (`v%lu`) of redo log files when `innodb-force-recovery > 0`.

`ER_IB_MSG_LOG_UPGRADE_FORCED_RECV` was added in 8.0.30.

- Error number: `MY-013872`; Symbol: `ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE`; SQLSTATE: `HY000`

Message: Cannot upgrade format (`v%lu`) of redo log files in read-only mode (`--innodb-read-only`).

`ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE` was added in 8.0.30.

- Error number: `MY-013873`; Symbol: `ER_IB_MSG_LOG_UPGRADE_CLONED_DB`; SQLSTATE: `HY000`

Message: Cannot upgrade format (`v%lu`) of redo log files on cloned data directory. Please use an older version of MySQL - recover and shutdown (with `innodb-fast-shutdown < 2`).

`ER_IB_MSG_LOG_UPGRADE_CLONED_DB` was added in 8.0.30.

- Error number: `MY-013874`; Symbol: `ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES`; SQLSTATE: `HY000`

Message: Cannot upgrade format (`v%lu`) of redo log files because they are marked as uninitialized. Please use an older version of MySQL - recover and shutdown (with `innodb-fast-shutdown < 2`).

`ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES` was added in 8.0.30.

- Error number: `MY-013875`; Symbol: `ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED`; SQLSTATE: `HY000`

Message: Cannot upgrade format (`v%lu`) of redo log files when the redo log is corrupted. Please use an older version of MySQL - recover and shutdown (with `innodb-fast-shutdown < 2`).

`ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED` was added in 8.0.30.

- Error number: `MY-013876`; Symbol: `ER_IB_MSG_LOG_UPGRADE_NON_PERSISTED_DD_METADATA__UNEXPECTED`; SQLSTATE: `HY000`

---

Message: Cannot upgrade format (v%lu) of redo log files when there is non-persisted DD metadata in redo. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

[ER\\_IB\\_MSG\\_LOG\\_UPGRADE\\_NON\\_PERSISTED\\_DD\\_METADATA\\_\\_UNEXPECTED](#) was added in 8.0.30, removed after 8.0.32.

- Error number: [MY-013877](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_UPGRADE\\_FLUSH\\_FAILED\\_\\_UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: Cannot upgrade format (v%lu) of redo log files, because InnoDB failed to reach state in which redo log is logically empty. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

[ER\\_IB\\_MSG\\_LOG\\_UPGRADE\\_FLUSH\\_FAILED\\_\\_UNEXPECTED](#) was added in 8.0.30, removed after 8.0.32.

- Error number: [MY-013878](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_RESIZE\\_ON\\_START\\_FAILED\\_\\_UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: Failed to resize the redo log synchronously, because InnoDB failed to reach state in which redo log is logically empty. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

[ER\\_IB\\_MSG\\_LOG\\_FILES\\_RESIZE\\_ON\\_START\\_FAILED\\_\\_UNEXPECTED](#) was added in 8.0.30, removed after 8.0.32.

- Error number: [MY-013879](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_FOREIGN\\_UUID](#); SQLSTATE: [HY000](#)

Message: The redo log file %s comes from other data directory than redo log file %s.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_FOREIGN\\_UUID](#) was added in 8.0.30.

- Error number: [MY-013880](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_INVALID\\_START\\_LSN](#); SQLSTATE: [HY000](#)

Message: The redo log file %s has invalid start\_lsn %llu.

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_INVALID\\_START\\_LSN](#) was added in 8.0.30.

- Error number: [MY-013881](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_INVALID\\_LSN\\_RANGES](#); SQLSTATE: [HY000](#)

Message: The redo log file %s has start\_lsn %llu but expected %llu (end\_lsn of the previous redo log file).

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_INVALID\\_LSN\\_RANGES](#) was added in 8.0.30.

- Error number: [MY-013882](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_MISSING\\_FOR\\_ID](#); SQLSTATE: [HY000](#)

Message: Missing redo log file %s (with start\_lsn = %llu).

[ER\\_IB\\_MSG\\_LOG\\_FILE\\_MISSING\\_FOR\\_ID](#) was added in 8.0.30.

- Error number: [MY-013883](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_CHECKPOINT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: The latest found checkpoint is at lsn = %llu in redo log file %s.

[ER\\_IB\\_MSG\\_LOG\\_CHECKPOINT\\_FOUND](#) was added in 8.0.30.



- 
- Error number: `MY-013884`; Symbol: `ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED`; SQLSTATE: `HY000`  
  
Message: User has set `innodb_redo_log_capacity` to %lluM.  
  
`ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED` was added in 8.0.30.
  - Error number: `MY-013885`; Symbol: `ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED`; SQLSTATE: `HY000`  
  
Message: Redo log has been requested to resize from %lluM to %lluM.  
  
`ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED` was added in 8.0.30.
  - Error number: `MY-013886`; Symbol: `ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED`; SQLSTATE: `HY000`  
  
Message: Redo log resize has been cancelled.  
  
`ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED` was added in 8.0.30.
  - Error number: `MY-013887`; Symbol: `ER_IB_MSG_LOG_FILES_RESIZE_FINISHED`; SQLSTATE: `HY000`  
  
Message: Redo log has been resized to %lluM.  
  
`ER_IB_MSG_LOG_FILES_RESIZE_FINISHED` was added in 8.0.30.
  - Error number: `MY-013888`; Symbol: `ER_IB_MSG_LOG_FILES_UPGRADE`; SQLSTATE: `HY000`  
  
Message: Upgrading redo log: %lluM, LSN=%llu.  
  
`ER_IB_MSG_LOG_FILES_UPGRADE` was added in 8.0.30.
  - Error number: `MY-013889`; Symbol: `ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE`; SQLSTATE: `HY000`  
  
Message: Marked the current redo log file %s as incomplete.  
  
`ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE` was added in 8.0.30.
  - Error number: `MY-013890`; Symbol: `ER_IB_MSG_LOG_FILE_REMOVE_FAILED`; SQLSTATE: `HY000`  
  
Message: Failed to remove redo log file %s.  
  
`ER_IB_MSG_LOG_FILE_REMOVE_FAILED` was added in 8.0.30.
  - Error number: `MY-013891`; Symbol: `ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED`; SQLSTATE: `HY000`  
  
Message: Failed to rename %s when creating redo log file %s (error: %d)  
  
`ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED` was added in 8.0.30.

- 
- Error number: `MY-013892`; Symbol: `ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATOR`; SQLSTATE: `HY000`

Message: Redo log files created by unknown creator %s.

`ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATOR` was added in 8.0.30.

- Error number: `MY-013893`; Symbol: `ER_IB_MSG_LOG_FILES_FOUND_MISSING`; SQLSTATE: `HY000`

Message: Found existing redo log files, but at least one is missing. It is unknown if recovery could reach physically consistent state. Please consider restoring from backup or providing `--innodb-force-recovery > 0`.

`ER_IB_MSG_LOG_FILES_FOUND_MISSING` was added in 8.0.30.

- Error number: `MY-013894`; Symbol: `ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW`; SQLSTATE: `HY000`

Message: Found redo log file %s which has format (v%lu) and is stored outside #innodb\_redo.

`ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW` was added in 8.0.30.

- Error number: `MY-013895`; Symbol: `ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD`; SQLSTATE: `HY000`

Message: Found redo log file %s which has format (v%lu) and is stored inside #innodb\_redo.

`ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD` was added in 8.0.30.

- Error number: `MY-013896`; Symbol: `ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS`; SQLSTATE: `HY000`

Message: Found redo log files with different formats: %s has format v%lu, %s has format v%lu.

`ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS` was added in 8.0.30.

- Error number: `MY-013897`; Symbol: `ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0`; SQLSTATE: `HY000`

Message: Missing `ib_logfile0` in the directory %s.

`ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0` was added in 8.0.30.

- Error number: `MY-013898`; Symbol: `ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED`; SQLSTATE: `HY000`

Message: Failed to initialize services required to handle redo log PFS tables.

`ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED` was added in 8.0.30.

- Error number: `MY-013899`; Symbol: `ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED`; SQLSTATE: `HY000`

Message: Failed to create redo log PFS tables.

`ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED` was added in 8.0.30.

- 
- Error number: [MY-013900](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_TRUNCATE](#); SQLSTATE: [HY000](#)  
Message: Truncating redo log file %s...  
[ER\\_IB\\_MSG\\_LOG\\_FILE\\_TRUNCATE](#) was added in 8.0.30.
  - Error number: [MY-013901](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_RESIZE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to resize unused redo log file %s to %llu MB (%s).  
[ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_RESIZE\\_FAILED](#) was added in 8.0.30.
  - Error number: [MY-013902](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_REMOVE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to remove unused redo log file %s.  
[ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_REMOVE\\_FAILED](#) was added in 8.0.30.
  - Error number: [MY-013903](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_RENAME\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to rename unused redo log file %s to %s.  
[ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_RENAME\\_FAILED](#) was added in 8.0.30.
  - Error number: [MY-013904](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_MARK\\_AS\\_IN\\_USE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to mark unused redo log file %s as in use (by renaming to %s).  
[ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_MARK\\_AS\\_IN\\_USE\\_FAILED](#) was added in 8.0.30.
  - Error number: [MY-013905](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_MARK\\_AS\\_UNUSED\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to mark redo log file %s as unused (by renaming to %s).  
[ER\\_IB\\_MSG\\_LOG\\_FILE\\_MARK\\_AS\\_UNUSED\\_FAILED](#) was added in 8.0.30.
  - Error number: [MY-013906](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_DEDICATED\\_SERVER\\_IGNORED](#); SQLSTATE: [HY000](#)  
Message: Option `innodb_dedicated_server` is ignored for `innodb_redo_log_capacity`, because `innodb_redo_log_capacity`, `innodb_log_file_size` or `innodb_log_files_in_group` is specified explicitly. Redo log capacity: %lluM.  
[ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_DEDICATED\\_SERVER\\_IGNORED](#) was added in 8.0.30.
  - Error number: [MY-013907](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_LEGACY\\_USAGE](#); SQLSTATE: [HY000](#)  
Message: Deprecated configuration parameters `innodb_log_file_size` and/or `innodb_log_files_in_group` have been used to compute `innodb_redo_log_capacity=%llu`. Please use `innodb_redo_log_capacity` instead.  
[ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_LEGACY\\_USAGE](#) was added in 8.0.30.
-

- 
- Error number: [MY-013908](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_LOG\\_VIEW\\_CHANGE](#); SQLSTATE: [HY000](#)

Message: This member was unable to log the View\_change\_log\_event into the binary log, hence it will leave the group. Please check that there is available disk space and add the member back to the group.

[ER\\_GRP\\_RPL\\_FAILED\\_TO\\_LOG\\_VIEW\\_CHANGE](#) was added in 8.0.29.

- Error number: [MY-013909](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_MALFORMED\\_LOG](#); SQLSTATE: [HY000](#)

Message: Found invalid event sequence while recovering from binary log file '%s', between positions %llu and %llu: %s. The recovery process was stopped early and no transaction was recovered. Side effects may be transactions in an inconsistent state between the binary log and the storage engines, or transactions kept by storage engines in a prepared state (possibly holding locks). Either fix the issues with the binary log or, to release possibly acquired locks, disable the binary log during server recovery. Note that disabling the binary log may lead to loss of transactions that were already acknowledged as successful to client connections and may have been replicated to other servers in the topology.

[ER\\_BINLOG\\_CRASH\\_RECOVERY\\_MALFORMED\\_LOG](#) was added in 8.0.30.

- Error number: [MY-013910](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ERROR\\_RETURNED\\_SE](#); SQLSTATE: [HY000](#)

Message: Storage engines failed to recover one or more transactions. The recovery process was stopped early, check previous messages for the details on failed transactions. Side effects may be transactions in an inconsistent state between the binary log and the storage engines, or transactions kept by storage engines in a prepared state (possibly holding locks). Either fix the issues with the storage engine (out-of-memory, no disk space, etc) or, to release possibly acquired locks held by XA transactions, disable the binary log during server recovery and check consistency between storage engines and binary log files.

[ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ERROR\\_RETURNED\\_SE](#) was added in 8.0.30.

- Error number: [MY-013911](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ENGINE\\_RESULTS](#); SQLSTATE: [HY000](#)

Message: Crash recovery finished in %s engine. %s

[ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ENGINE\\_RESULTS](#) was added in 8.0.30.

- Error number: [MY-013912](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_COMMIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to commit %s in %s, with failure code %s.

[ER\\_BINLOG\\_CRASH\\_RECOVERY\\_COMMIT\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-013913](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ROLLBACK\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to rollback %s in %s, with failure code %s.

[ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ROLLBACK\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-013914](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_PREPARE\\_FAILED](#); SQLSTATE: [HY000](#)

---

Message: Failed to prepare %s in %s, with failure code %s.

[ER\\_BINLOG\\_CRASH\\_RECOVERY\\_PREPARE\\_FAILED](#) was added in 8.0.30.

- Error number: [MY-013915](#); Symbol: [ER\\_COMPONENT\\_EE\\_SYS\\_VAR\\_REGISTRATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot register variable '%s'. Please check if it is not already registered by another component.

[ER\\_COMPONENT\\_EE\\_SYS\\_VAR\\_REGISTRATION\\_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013916](#); Symbol: [ER\\_COMPONENT\\_EE\\_SYS\\_VAR\\_DEREGISTRATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot unregister variable '%s'. Please check if it was registered properly in the first place.

[ER\\_COMPONENT\\_EE\\_SYS\\_VAR\\_DEREGISTRATION\\_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013917](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_REGISTRATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot register function '%s'. Please check if it is not already registered.

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_REGISTRATION\\_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013918](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_DEREGISTRATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot unregister function '%s'. Please check if it was registered properly in the first place.

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_DEREGISTRATION\\_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013919](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_INVALID\\_ARGUMENTS](#); SQLSTATE: [HY000](#)

Message: Invalid arguments to function '%s'. Expected values: %s.

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_INVALID\\_ARGUMENTS](#) was added in 8.0.30.

- Error number: [MY-013920](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_INVALID\\_ALGORITHM](#); SQLSTATE: [HY000](#)

Message: Invalid algorithm value '%s' in function %s.

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_INVALID\\_ALGORITHM](#) was added in 8.0.30.

- Error number: [MY-013921](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_KEY\\_LENGTH\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [HY000](#)

Message: Invalid key length '%d' for function '%s' with algorithm '%s'. Please provide a value between [%d, %d].

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_KEY\\_LENGTH\\_OUT\\_OF\\_RANGE](#) was added in 8.0.30.

- Error number: [MY-013922](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_PRIVATE\\_KEY\\_GENERATION\\_FAILURE](#); SQLSTATE: [HY000](#)

---

Message: Failed to generate private key of length '%d' with algorithm '%s' in function '%s'. More details about the error would have been logged before this message.

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_PRIVATE\\_KEY\\_GENERATION\\_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013923](#); Symbol:

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_PUBLIC\\_KEY\\_GENERATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to generate public key with algorithm '%s' for given private key in function '%s'. More details about the error would have been logged before this message.

[ER\\_COMPONENT\\_EE\\_FUNCTION\\_PUBLIC\\_KEY\\_GENERATION\\_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013924](#); Symbol: [ER\\_COMPONENT\\_EE\\_DATA\\_LENGTH\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [HY000](#)

Message: Invalid data length '%d' (in bytes) for function '%s' with algorithm '%s'. The maximum support data length for given private key is %d (in bytes).

[ER\\_COMPONENT\\_EE\\_DATA\\_LENGTH\\_OUT\\_OF\\_RANGE](#) was added in 8.0.30.

- Error number: [MY-013925](#); Symbol: [ER\\_COMPONENT\\_EE\\_DATA\\_ENCRYPTION\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not encrypt data in function '%s' using algorithm '%s'. Data length was '%d' bytes. More details about the error would have been logged before this message.

[ER\\_COMPONENT\\_EE\\_DATA\\_ENCRYPTION\\_ERROR](#) was added in 8.0.30.

- Error number: [MY-013926](#); Symbol: [ER\\_COMPONENT\\_EE\\_DATA\\_DECRYPTION\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not decrypt data in function '%s' using algorithm '%s'. Data length was '%d' bytes. More details about the error would have been logged before this message.

[ER\\_COMPONENT\\_EE\\_DATA\\_DECRYPTION\\_ERROR](#) was added in 8.0.30.

- Error number: [MY-013927](#); Symbol: [ER\\_COMPONENT\\_EE\\_DATA\\_SIGN\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not sign data in function '%s' using algorithm '%s' and digest type '%s'. More details about the error would have logged before this message.

[ER\\_COMPONENT\\_EE\\_DATA\\_SIGN\\_ERROR](#) was added in 8.0.30.

- Error number: [MY-013928](#); Symbol: [ER\\_COMPONENT\\_EE\\_OPENSSL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Received OpenSSL error in function '%s' for algorithm '%s': '%s'

[ER\\_COMPONENT\\_EE\\_OPENSSL\\_ERROR](#) was added in 8.0.30.

- Error number: [MY-013929](#); Symbol: [ER\\_COMPONENT\\_EE\\_INSUFFICIENT\\_LENGTH](#); SQLSTATE: [HY000](#)

Message: In function '%s' with algorithm '%s': insufficient output buffer length '%zu'. Required length '%zu'.

[ER\\_COMPONENT\\_EE\\_INSUFFICIENT\\_LENGTH](#) was added in 8.0.30.

- 
- Error number: [MY-013930](#); Symbol: [ER\\_SYSTEMD\\_NOTIFY\\_DEBUG](#); SQLSTATE: [HY000](#)  
Message: %s%s  
[ER\\_SYSTEMD\\_NOTIFY\\_DEBUG](#) was added in 8.0.30.
  - Error number: [MY-013931](#); Symbol: [ER\\_TMP\\_SESSION\\_FOR\\_VAR](#); SQLSTATE: [HY000](#)  
Message: Setting session values for system variables only makes sense in a user session (failed to set '%s').  
[ER\\_TMP\\_SESSION\\_FOR\\_VAR](#) was added in 8.0.30.
  - Error number: [MY-013932](#); Symbol: [ER\\_BUILD\\_ID](#); SQLSTATE: [HY000](#)  
Message: BuildID[sha1]=%s  
[ER\\_BUILD\\_ID](#) was added in 8.0.30.
  - Error number: [MY-013933](#); Symbol: [ER\\_THREAD\\_POOL\\_CANNOT\\_REGISTER\\_DYNAMIC\\_PRIVILEGE](#); SQLSTATE: [HY000](#)  
Message: Failed to register dynamic privilege %s.  
[ER\\_THREAD\\_POOL\\_CANNOT\\_REGISTER\\_DYNAMIC\\_PRIVILEGE](#) was added in 8.0.30.
  - Error number: [MY-013934](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_WRITER\\_WAIT\\_ON\\_CONSUMER](#); SQLSTATE: [HY000](#)  
Message: Redo log writer is waiting for %s redo log consumer which is currently reading LSN=%llu preventing reclamation of subsequent portion of the redo log. Consider increasing innodb\_redo\_log\_capacity.  
[ER\\_IB\\_MSG\\_LOG\\_WRITER\\_WAIT\\_ON\\_CONSUMER](#) was added in 8.0.30.
  - Error number: [MY-013935](#); Symbol: [ER\\_CONDITIONAL\\_DEBUG](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_CONDITIONAL\\_DEBUG](#) was added in 8.0.30.
  - Error number: [MY-013936](#); Symbol: [ER\\_IB\\_MSG\\_PARSE\\_OLD\\_REDO\\_INDEX\\_VERSION](#); SQLSTATE: [HY000](#)  
Message: Recovery: Generating index information for INSTANT DDL Table in 8.0.29 format  
[ER\\_IB\\_MSG\\_PARSE\\_OLD\\_REDO\\_INDEX\\_VERSION](#) was added in 8.0.30.
  - Error number: [MY-013937](#); Symbol: [ER\\_RES\\_GRP\\_FAILED\\_TO\\_SWITCH\\_RESOURCE\\_GROUP](#); SQLSTATE: [HY000](#)  
Message: Failed to switch resource group. %s  
[ER\\_RES\\_GRP\\_FAILED\\_TO\\_SWITCH\\_RESOURCE\\_GROUP](#) was added in 8.0.30, removed after 8.0.31.
  - Error number: [MY-013938](#); Symbol: [ER\\_RES\\_GRP\\_SWITCH\\_FAILED\\_COULD\\_NOT\\_ACQUIRE\\_GLOBAL\\_LOCK](#); SQLSTATE: [HY000](#)  
Message: Failed to switch resource group. Could not acquire resource groups global lock.

---

[ER\\_RES\\_GRP\\_SWITCH\\_FAILED\\_COULD\\_NOT\\_ACQUIRE\\_GLOBAL\\_LOCK](#) was added in 8.0.30, removed after 8.0.31.

- Error number: [MY-013939](#); Symbol: [ER\\_RES\\_GRP\\_SWITCH\\_FAILED\\_COULD\\_NOT\\_ACQUIRE\\_LOCK](#); SQLSTATE: [HY000](#)

Message: Failed to switch resource group. Could not acquire lock on resource group %s.

[ER\\_RES\\_GRP\\_SWITCH\\_FAILED\\_COULD\\_NOT\\_ACQUIRE\\_LOCK](#) was added in 8.0.30, removed after 8.0.31.

- Error number: [MY-013940](#); Symbol: [ER\\_RES\\_GRP\\_SWITCH\\_FAILED\\_UNABLE\\_TO\\_APPLY\\_RES\\_GRP](#); SQLSTATE: [HY000](#)

Message: Failed to switch resource group. Unable to apply resource group controller %s.

[ER\\_RES\\_GRP\\_SWITCH\\_FAILED\\_UNABLE\\_TO\\_APPLY\\_RES\\_GRP](#) was added in 8.0.30, removed after 8.0.31.

- Error number: [MY-013941](#); Symbol: [ER\\_IB\\_MSG\\_CLEAR\\_INSTANT\\_DROP\\_COLUMN\\_METADATA](#); SQLSTATE: [HY000](#)

Message: Failed to clear instant drop column metadata for table %s

[ER\\_IB\\_MSG\\_CLEAR\\_INSTANT\\_DROP\\_COLUMN\\_METADATA](#) was added in 8.0.30.

- Error number: [MY-013942](#); Symbol: [ER\\_COMPONENT\\_KEYRING\\_OCI\\_OPEN\\_KEY\\_FILE](#); SQLSTATE: [HY000](#)

Message: Cannot open signing key file %s.

[ER\\_COMPONENT\\_KEYRING\\_OCI\\_OPEN\\_KEY\\_FILE](#) was added in 8.0.31.

- Error number: [MY-013943](#); Symbol: [ER\\_COMPONENT\\_KEYRING\\_OCI\\_CREATE\\_PRIVATE\\_KEY](#); SQLSTATE: [HY000](#)

Message: Out of memory! Cannot create private key.

[ER\\_COMPONENT\\_KEYRING\\_OCI\\_CREATE\\_PRIVATE\\_KEY](#) was added in 8.0.31.

- Error number: [MY-013944](#); Symbol: [ER\\_COMPONENT\\_KEYRING\\_OCI\\_READ\\_KEY\\_FILE](#); SQLSTATE: [HY000](#)

Message: Cannot read signing key file %s.

[ER\\_COMPONENT\\_KEYRING\\_OCI\\_READ\\_KEY\\_FILE](#) was added in 8.0.31.

- Error number: [MY-013945](#); Symbol: [ER\\_NOTE\\_COMPONENT\\_KEYRING\\_OCI\\_MISSING\\_NAME\\_OR\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Incomplete key: missing Name/Type for the Key: %s.

[ER\\_NOTE\\_COMPONENT\\_KEYRING\\_OCI\\_MISSING\\_NAME\\_OR\\_TYPE](#) was added in 8.0.31.

- Error number: [MY-013946](#); Symbol: [ER\\_WARN\\_COMPONENT\\_KEYRING\\_OCI\\_DUPLICATE\\_KEY](#); SQLSTATE: [HY000](#)

Message: Duplicate key found in keyring with Name: %s and Owner: %s.



---

`ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEY` was added in 8.0.31.

- Error number: `MY-013947`; Symbol: `ER_KEYRING_OCI_PARSE_JSON`; SQLSTATE: `HY000`  
Message: Error parsing JSON response %s.

`ER_KEYRING_OCI_PARSE_JSON` was added in 8.0.31.

- Error number: `MY-013948`; Symbol: `ER_KEYRING_OCI_INVALID_JSON`; SQLSTATE: `HY000`  
Message: Invalid JSON response!

`ER_KEYRING_OCI_INVALID_JSON` was added in 8.0.31.

- Error number: `MY-013949`; Symbol: `ER_KEYRING_OCI_HTTP_REQUEST`; SQLSTATE: `HY000`  
Message: HTTP request failed with error: '%s'

`ER_KEYRING_OCI_HTTP_REQUEST` was added in 8.0.31.

- Error number: `MY-013950`; Symbol: `ER_THREAD_POOL_SYSVAR_CHANGE`; SQLSTATE: `HY000`  
Message: Variable `thread_pool.%s` was updated: %s

`ER_THREAD_POOL_SYSVAR_CHANGE` was added in 8.0.31.

- Error number: `MY-013951`; Symbol: `ER_STACK_BACKTRACE`; SQLSTATE: `HY000`  
Message: %s

`ER_STACK_BACKTRACE` was added in 8.0.31.

- Error number: `MY-013952`; Symbol: `ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_CODE`; SQLSTATE: `HY000`  
Message: Status code %u: Completed

`ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_CODE` was added in 8.0.31.

- Error number: `MY-013953`; Symbol: `ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE`; SQLSTATE: `HY000`  
Message: Status code %u: %u%% complete

`ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE` was added in 8.0.31.

- Error number: `MY-013954`; Symbol: `ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS`; SQLSTATE: `HY000`  
Message: Status code %u: %s

`ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS` was added in 8.0.31.

- Error number: `MY-013955`; Symbol: `ER_THREAD_POOL_QUERY_THREADS_PER_GROUP_INVALID`; SQLSTATE: `HY000`  
Message: Invalid value set to `thread_pool_query_threads_per_group`. Valid value range is %u - %u.

`ER_THREAD_POOL_QUERY_THREADS_PER_GROUP_INVALID` was added in 8.0.31.

- 
- Error number: `MY-013956`; Symbol: `ER_THREAD_POOL_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT`; SQLSTATE: `HY000`  
Message: Query threads count(%u) exceeds transaction threads limit(%u) per group. Please use query threads count per group smaller or equal to max transaction threads limit per group  
`ER_THREAD_POOL_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT` was added in 8.0.31.
  - Error number: `MY-013957`; Symbol: `ER_IB_MSG_INVALID_PAGE_TYPE`; SQLSTATE: `HY000`  
Message: Found page type mismatch. Expected %u, found %u, in page: space\_id=%lu page\_no= %lu  
`ER_IB_MSG_INVALID_PAGE_TYPE` was added in 8.0.32.
  - Error number: `MY-013958`; Symbol: `ER_IB_PARALLEL_READER_WORKER_INFO`; SQLSTATE: `HY000`  
Message: preader: space\_id=%zu, table=%s, index=%s, scan\_ctx=%zu, ctx=%zu, thread\_id=%zu, n\_threads=%zu  
`ER_IB_PARALLEL_READER_WORKER_INFO` was added in 8.0.32.
  - Error number: `MY-013959`; Symbol: `ER_IB_BULK_LOAD_SUBTREE_INFO`; SQLSTATE: `HY000`  
Message: bulkload: space\_id=%zu, table=%s, index=%s, height=%zu, n\_extents=%zu, n\_pages=%zu  
`ER_IB_BULK_LOAD_SUBTREE_INFO` was added in 8.0.32.
  - Error number: `MY-013960`; Symbol: `ER_IB_BULK_FLUSHER_INFO`; SQLSTATE: `HY000`  
Message: bulkflusher: sleep\_count=%zu, sleep\_duration=%zu milliseconds, total\_sleep=%zu milliseconds, pages\_flushed=%zu  
`ER_IB_BULK_FLUSHER_INFO` was added in 8.0.32.
  - Error number: `MY-013961`; Symbol: `ER_IB_BUFFER_POOL_OVERUSE`; SQLSTATE: `HY000`  
Message: %s: Over 67 percent of the buffer pool (curr\_size=%zu MB) is occupied by lock heaps or the adaptive hash index or BUF\_BLOCK\_MEMORY pages. Check that your transactions do not set too many row locks. Maybe you should make the buffer pool bigger?. Starting the InnoDB Monitor to print diagnostics.  
`ER_IB_BUFFER_POOL_OVERUSE` was added in 8.0.32.
  - Error number: `MY-013962`; Symbol: `ER_IB_BUFFER_POOL_FULL`; SQLSTATE: `HY000`  
Message: %s: Over 95 percent of the buffer pool (curr\_size=%zu MB) is occupied by lock heaps or the adaptive hash index or BUF\_BLOCK\_MEMORY pages. Check that your transactions do not set too many row locks. Maybe you should make the buffer pool bigger?. We intentionally generate a seg fault to print a stack trace on Linux!  
`ER_IB_BUFFER_POOL_FULL` was added in 8.0.32.
  - Error number: `MY-013963`; Symbol: `ER_IB_DUPLICATE_KEY`; SQLSTATE: `HY000`  
Message: %s: table=%s, index=%s, n\_uniq=%zu, n\_fields=%zu, lhs=(%s), rhs=(%s)  
`ER_IB_DUPLICATE_KEY` was added in 8.0.32.

- 
- Error number: [MY-013964](#); Symbol: [ER\\_REPLICATION\\_INCOMPATIBLE\\_TABLE\\_WITH\\_GIPK](#); SQLSTATE: [HY000](#)  
  
Message: Failed to apply row event with %d columns, originating from a server of version %s on table '%s.%s', which has %d columns, one of which is a generated implicit primary key. Replication is unsupported when the source server is older than 8.0.30, the replica table has a generated implicit primary key, and there is a difference in column count, not counting the replica's generated implicit primary key. Align the table schemas on source and replica, and restart replication.  
  
[ER\\_REPLICATION\\_INCOMPATIBLE\\_TABLE\\_WITH\\_GIPK](#) was added in 8.0.32.
  - Error number: [MY-013965](#); Symbol: [ER\\_BULK\\_EXECUTOR\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Bulk executor: %s  
  
[ER\\_BULK\\_EXECUTOR\\_INFO](#) was added in 8.0.32.
  - Error number: [MY-013966](#); Symbol: [ER\\_BULK\\_LOADER\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Bulk loader: %s  
  
[ER\\_BULK\\_LOADER\\_INFO](#) was added in 8.0.32.
  - Error number: [MY-013967](#); Symbol: [ER\\_BULK\\_LOADER\\_FILE\\_CONTAINS\\_LESS\\_LINES\\_THAN\\_IGNORE\\_CLAUSE\\_LOG](#); SQLSTATE: [HY000](#)  
  
Message: The first file being loaded contained less lines than the ignore clause  
  
[ER\\_BULK\\_LOADER\\_FILE\\_CONTAINS\\_LESS\\_LINES\\_THAN\\_IGNORE\\_CLAUSE\\_LOG](#) was added in 8.0.32.
  - Error number: [MY-013968](#); Symbol: [ER\\_BULK\\_READER\\_INFO](#); SQLSTATE: [HY000](#)  
  
Message: Bulk reader: %s  
  
[ER\\_BULK\\_READER\\_INFO](#) was added in 8.0.32.
  - Error number: [MY-013969](#); Symbol: [ER\\_BULK\\_READER\\_LIBCURL\\_INIT\\_FAILED\\_LOG](#); SQLSTATE: [HY000](#)  
  
Message: Bulk reader failed to initialize libcurl  
  
[ER\\_BULK\\_READER\\_LIBCURL\\_INIT\\_FAILED\\_LOG](#) was added in 8.0.32.
  - Error number: [MY-013970](#); Symbol: [ER\\_BULK\\_READER\\_LIBCURL\\_ERROR\\_LOG](#); SQLSTATE: [HY000](#)  
  
Message: Bulk reader got libcurl error: %s  
  
[ER\\_BULK\\_READER\\_LIBCURL\\_ERROR\\_LOG](#) was added in 8.0.32.
  - Error number: [MY-013971](#); Symbol: [ER\\_BULK\\_READER\\_SERVER\\_ERROR\\_LOG](#); SQLSTATE: [HY000](#)  
  
Message: Bulk reader got error response from server: %ld  
  
[ER\\_BULK\\_READER\\_SERVER\\_ERROR\\_LOG](#) was added in 8.0.32.
  - Error number: [MY-013972](#); Symbol: [ER\\_BULK\\_READER\\_COMMUNICATION\\_ERROR\\_LOG](#); SQLSTATE: [HY000](#)

---

Message: Bulk reader got error in communication with source server, check the error log for additional details

[ER\\_BULK\\_READER\\_COMMUNICATION\\_ERROR\\_LOG](#) was added in 8.0.32.

- Error number: MY-013973; Symbol: [ER\\_BULK\\_PARSER\\_MISSING\\_ENCLOSED\\_BY\\_LOG](#); SQLSTATE: HY000

Message: Missing ENCLOSED BY character at row %ld in file %s. Add OPTIONALLY to the ENCLOSED BY clause to allow this input.

[ER\\_BULK\\_PARSER\\_MISSING\\_ENCLOSED\\_BY\\_LOG](#) was added in 8.0.32.

- Error number: MY-013974; Symbol: [ER\\_BULK\\_PARSER\\_ROW\\_BUFFER\\_MAX\\_TOTAL\\_COLS\\_EXCEEDED\\_LOG](#); SQLSTATE: HY000

Message: The number of input columns that need to be buffered for parsing exceeded predefined buffer max size for file '%s'.

[ER\\_BULK\\_PARSER\\_ROW\\_BUFFER\\_MAX\\_TOTAL\\_COLS\\_EXCEEDED\\_LOG](#) was added in 8.0.32.

- Error number: MY-013975; Symbol: [ER\\_BULK\\_PARSER\\_COPY\\_BUFFER\\_SIZE\\_EXCEEDED\\_LOG](#); SQLSTATE: HY000

Message: The column data that needed to be copied due to escaped characters exceeded the size of the internal copy buffer for file '%s'.

[ER\\_BULK\\_PARSER\\_COPY\\_BUFFER\\_SIZE\\_EXCEEDED\\_LOG](#) was added in 8.0.32.

- Error number: MY-013976; Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_END\\_OF\\_INPUT\\_LOG](#); SQLSTATE: HY000

Message: Unexpected end of input found at row %ld in file '%s'. Data for some columns is missing.

[ER\\_BULK\\_PARSER\\_UNEXPECTED\\_END\\_OF\\_INPUT\\_LOG](#) was added in 8.0.32.

- Error number: MY-013977; Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_ROW\\_TERMINATOR\\_LOG](#); SQLSTATE: HY000

Message: Unexpected row terminator found at row %ld in file '%s'. Data for some columns is missing.

[ER\\_BULK\\_PARSER\\_UNEXPECTED\\_ROW\\_TERMINATOR\\_LOG](#) was added in 8.0.32.

- Error number: MY-013978; Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_ENDING\\_ENCLOSED\\_BY\\_LOG](#); SQLSTATE: HY000

Message: Unexpected characters after ending ENCLOSED BY character found at row %ld in file '%s'.

[ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_ENDING\\_ENCLOSED\\_BY\\_LOG](#) was added in 8.0.32.

- Error number: MY-013979; Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_NULL\\_ESCAPE\\_LOG](#); SQLSTATE: HY000

Message: Unexpected characters after NULL escape (N) found at row %ld in file '%s'.

[ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_NULL\\_ESCAPE\\_LOG](#) was added in 8.0.32.

- 
- Error number: [MY-013980](#); Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_COLUMN\\_TERMINATOR\\_LOG](#); SQLSTATE: HY000  
Message: Unexpected characters after column terminator found at row %ld in file '%s'.  
[ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_COLUMN\\_TERMINATOR\\_LOG](#) was added in 8.0.32.
  - Error number: [MY-013981](#); Symbol: [ER\\_BULK\\_PARSER\\_INCOMPLETE\\_ESCAPE\\_SEQUENCE\\_LOG](#); SQLSTATE: HY000  
Message: Unexpected end of input found at row %ld in file '%s' resulting in incomplete escape sequence.  
[ER\\_BULK\\_PARSER\\_INCOMPLETE\\_ESCAPE\\_SEQUENCE\\_LOG](#) was added in 8.0.32.
  - Error number: [MY-013982](#); Symbol: [ER\\_LOAD\\_BULK\\_DATA\\_WRONG\\_VALUE\\_FOR\\_FIELD\\_LOG](#); SQLSTATE: HY000  
Message: Incorrect %s value: '%s' for column '%s' at row %ld in file '%s'  
[ER\\_LOAD\\_BULK\\_DATA\\_WRONG\\_VALUE\\_FOR\\_FIELD\\_LOG](#) was added in 8.0.32.
  - Error number: [MY-013983](#); Symbol: [ER\\_LOAD\\_BULK\\_DATA\\_WARN\\_NULL\\_TO\\_NOTNULL\\_LOG](#); SQLSTATE: HY000  
Message: NULL supplied to NOT NULL column '%s' at row %ld in file '%s'  
[ER\\_LOAD\\_BULK\\_DATA\\_WARN\\_NULL\\_TO\\_NOTNULL\\_LOG](#) was added in 8.0.32.
  - Error number: [MY-013984](#); Symbol: [ER\\_IB\\_BULK\\_LOAD\\_THREAD\\_FAIL](#); SQLSTATE: HY000  
Message: %s: LOAD BULK DATA thread failure (err=%lu), table=%s, index=%s  
[ER\\_IB\\_BULK\\_LOAD\\_THREAD\\_FAIL](#) was added in 8.0.32.
  - Error number: [MY-013985](#); Symbol: [ER\\_IB\\_BULK\\_LOAD\\_MERGE\\_FAIL](#); SQLSTATE: HY000  
Message: %s: Failed to merge sub-trees in LOAD BULK DATA, table=%s, index=%s, details=%s  
[ER\\_IB\\_BULK\\_LOAD\\_MERGE\\_FAIL](#) was added in 8.0.32.
  - Error number: [MY-013986](#); Symbol: [ER\\_IB\\_LOAD\\_BULK\\_CONCURRENCY\\_REDUCED](#); SQLSTATE: HY000  
Message: LOAD BULK DATA: Buffer pool size is %zu. Reducing concurrency from %zu to %zu. table=%s.  
[ER\\_IB\\_LOAD\\_BULK\\_CONCURRENCY\\_REDUCED](#) was added in 8.0.32.
  - Error number: [MY-013987](#); Symbol: [ER\\_PLUGIN\\_EXCEPTION\\_OPERATION\\_FAILED](#); SQLSTATE: HY000  
Message: C++ Exception caught while %s the %s plugin: [%s]  
[ER\\_PLUGIN\\_EXCEPTION\\_OPERATION\\_FAILED](#) was added in 8.0.32.
  - Error number: [MY-013988](#); Symbol: [ER\\_REQUIRE\\_TABLE\\_PRIMARY\\_KEY\\_CHECK\\_GENERATE\\_WITH\\_GR\\_IN\\_REPO](#); SQLSTATE: HY000
-

---

Message: Replication configuration appears to be corrupted. On Group Replication channel '%s', setting REQUIRE\_TABLE\_PRIMARY\_KEY\_CHECK to 'GENERATE' is not allowed. Run RESET REPLICA ALL to reset it.

[ER\\_REQUIRE\\_TABLE\\_PRIMARY\\_KEY\\_CHECK\\_GENERATE\\_WITH\\_GR\\_IN\\_REPO](#) was added in 8.0.32.

- Error number: MY-013989; Symbol: [ER\\_CHECK\\_TABLE\\_INSTANT\\_VERSION\\_BIT\\_SET](#); SQLSTATE: HY000

Message: Record has both instant and version bit set.

[ER\\_CHECK\\_TABLE\\_INSTANT\\_VERSION\\_BIT\\_SET](#) was added in 8.0.32.

- Error number: MY-013990; Symbol: [ER\\_GRP\\_RPL\\_PAXOS\\_SINGLE\\_LEADER\\_DIFF\\_FROM\\_OLD\\_GRP](#); SQLSTATE: HY000

Message: This member is configured with a group\_replication\_paxos\_single\_leader option value of 1 and it is trying to join a group with Communication Protocol Version below 8.0.27. In order to join this group, group\_replication\_paxos\_single\_leader value must be configured to the value 0. This member will now exit the group.

[ER\\_GRP\\_RPL\\_PAXOS\\_SINGLE\\_LEADER\\_DIFF\\_FROM\\_OLD\\_GRP](#) was added in 8.0.32.

- Error number: MY-013991; Symbol: [ER\\_IB\\_WRN\\_IGNORE\\_REDO\\_LOG\\_CAPACITY](#); SQLSTATE: HY000

Message: Ignored the innodb-redo-log-capacity option in the Innodb read-only mode. Server is using active redo log files.

[ER\\_IB\\_WRN\\_IGNORE\\_REDO\\_LOG\\_CAPACITY](#) was added in 8.0.32.

- Error number: MY-013992; Symbol: [ER\\_IB\\_PRIMARY\\_KEY\\_IS\\_INSTANT](#); SQLSTATE: HY000

Message: Unexpected INSTANTLY Added / Dropped column: '%s' at position %lu for Table '%s', Index '%s' while getting Primary Key for row logging

[ER\\_IB\\_PRIMARY\\_KEY\\_IS\\_INSTANT](#) was added in 8.0.32.

- Error number: MY-013993; Symbol: [ER\\_THREAD\\_POOL\\_IDLE\\_CONNECTION\\_CLOSED](#); SQLSTATE: HY000

Message: %s

[ER\\_THREAD\\_POOL\\_IDLE\\_CONNECTION\\_CLOSED](#) was added in 8.0.32.

- Error number: MY-013994; Symbol: [ER\\_IB\\_HIDDEN\\_NAME\\_CONFLICT](#); SQLSTATE: HY000

Message: Column name %s and internally generated INSTANT DROP column name %s is causing a conflict.

[ER\\_IB\\_HIDDEN\\_NAME\\_CONFLICT](#) was added in 8.0.32.

- Error number: MY-013995; Symbol: [ER\\_IB\\_DICT\\_INVALID\\_COLUMN\\_POSITION](#); SQLSTATE: HY000

Message: Field number: %llu too large, Total fields in Record: %zu.

[ER\\_IB\\_DICT\\_INVALID\\_COLUMN\\_POSITION](#) was added in 8.0.32.

- Error number: MY-013996; Symbol: [ER\\_IB\\_DICT\\_LOG\\_TABLE\\_INFO](#); SQLSTATE: HY000

---

Message: %s

[ER\\_IB\\_DICT\\_LOG\\_TABLE\\_INFO](#) was added in 8.0.32.

- Error number: [MY-013997](#); Symbol: [ER\\_RPL\\_ASYNC\\_NEXT\\_FAILOVER\\_CHANNEL\\_SELECTED](#); SQLSTATE: [HY000](#)

Message: The connection has timed out after %lu retries connecting to '%s@%s:%d'%s, and therefore the MySQL server is going to attempt an asynchronous replication connection failover, to '%s@%s:%d'

[ER\\_RPL\\_ASYNC\\_NEXT\\_FAILOVER\\_CHANNEL\\_SELECTED](#) was added in 8.0.33.

- Error number: [MY-013998](#); Symbol: [ER\\_RPL\\_REPLICA\\_SOURCE\\_UUID\\_HAS\\_NOT\\_CHANGED](#); SQLSTATE: [HY000](#)

Message: The Replica which was connected to source '%s:%d', is now connected to new source '%s:%d', but still has the same server\_uuid %s.

[ER\\_RPL\\_REPLICA\\_SOURCE\\_UUID\\_HAS\\_NOT\\_CHANGED](#) was added in 8.0.33.

- Error number: [MY-013999](#); Symbol: [ER\\_RPL\\_REPLICA\\_SOURCE\\_UUID\\_HAS\\_CHANGED\\_HOST\\_PORT\\_UNCHANGED](#); SQLSTATE: [HY000](#)

Message: The server\_uuid for source server '%s:%d' has changed from %s to %s. This should not happen unless you have changed it manually.

[ER\\_RPL\\_REPLICA\\_SOURCE\\_UUID\\_HAS\\_CHANGED\\_HOST\\_PORT\\_UNCHANGED](#) was added in 8.0.33.

- Error number: [MY-014000](#); Symbol: [ER\\_RPL\\_REPLICA\\_SOURCE\\_UUID\\_HOST\\_PORT\\_HAS\\_CHANGED](#); SQLSTATE: [HY000](#)

Message: The source server has changed from '%s:%d' with server\_uuid %s, to '%s:%d' with server\_uuid %s.

[ER\\_RPL\\_REPLICA\\_SOURCE\\_UUID\\_HOST\\_PORT\\_HAS\\_CHANGED](#) was added in 8.0.33.

- Error number: [MY-014001](#); Symbol: [ER\\_RPL\\_REPLICA\\_CONNECTED\\_TO\\_SOURCE\\_RPL\\_STARTED\\_FILE\\_BASED](#); SQLSTATE: [HY000](#)

Message: Replica receiver thread%s: connected to source '%s@%s:%d' with server\_uuid=%s, server\_id=%d. Starting replication from file '%s', position '%s'.

[ER\\_RPL\\_REPLICA\\_CONNECTED\\_TO\\_SOURCE\\_RPL\\_STARTED\\_FILE\\_BASED](#) was added in 8.0.33.

- Error number: [MY-014002](#); Symbol: [ER\\_RPL\\_REPLICA\\_CONNECTED\\_TO\\_SOURCE\\_RPL\\_STARTED\\_GTID\\_BASED](#); SQLSTATE: [HY000](#)

Message: Replica receiver thread%s: connected to source '%s@%s:%d' with server\_uuid=%s, server\_id=%d. Starting GTID-based replication.

[ER\\_RPL\\_REPLICA\\_CONNECTED\\_TO\\_SOURCE\\_RPL\\_STARTED\\_GTID\\_BASED](#) was added in 8.0.33.

- Error number: [MY-014003](#); Symbol: [ER\\_IB\\_INDEX\\_LOADER\\_DONE](#); SQLSTATE: [HY000](#)

Message: Loader::build\_all(): Completed building %zu indexes for old\_table=%s, new\_table=%s, err=%zu.

[ER\\_IB\\_INDEX\\_LOADER\\_DONE](#) was added in 8.0.32.

- 
- Error number: `MY-014004`; Symbol: `ER_IB_INDEX_BUILDER_DONE`; SQLSTATE: `HY000`  
Message: Builder::finish(): Completed building index=%s of table=%s, err=%zu.  
`ER_IB_INDEX_BUILDER_DONE` was added in 8.0.32.
  - Error number: `MY-014005`; Symbol: `ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS_OPTION`; SQLSTATE: `HY000`  
Message: %s: '%s' is a user defined collation. User defined collations are deprecated and will be removed in a future release. Consider using a compiled collation instead.  
`ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS_OPTION` was added in 8.0.33.
  - Error number: `MY-014006`; Symbol: `ER_IB_INDEX_BUILDER_INIT`; SQLSTATE: `HY000`  
Message: Builder::init(): Initialize for building index=%s of table=%s, n\_threads=%zu, sort buffer size=%zu bytes, i/o buffer size=%zu bytes.  
`ER_IB_INDEX_BUILDER_INIT` was added in 8.0.33.
  - Error number: `MY-014007`; Symbol: `ER_IB_SELECT_COUNT_STAR`; SQLSTATE: `HY000`  
Message: SELECT COUNT(\*) FROM table=%s, n\_threads=%zu, n\_partitions=%zu.  
`ER_IB_SELECT_COUNT_STAR` was added in 8.0.33.
  - Error number: `MY-014008`; Symbol: `ER_IB_INDEX_LOG_VERSION_MISMATCH`; SQLSTATE: `HY000`  
Message: Index log version %u did not match. Max index version is %u. Recovery can't continue. Please make sure server is not starting up with the datadir generated in future version.  
`ER_IB_INDEX_LOG_VERSION_MISMATCH` was added in 8.0.33.
  - Error number: `MY-014009`; Symbol: `ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_MULTIPLE_KEYRING`; SQLSTATE: `HY000`  
Message: Multiple keyring component URNs '%s' found in manifest file '%s'. Only one keyring component can be loaded at a time.  
`ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_MULTIPLE_KEYRING` was added in 8.0.33.
  - Error number: `MY-014010`; Symbol: `ER_GRP_RPL_HAS_STARTED`; SQLSTATE: `HY000`  
Message: Plugin 'group\_replication' has been started.  
`ER_GRP_RPL_HAS_STARTED` was added in 8.0.33.
  - Error number: `MY-014011`; Symbol: `ER_CHECK_TABLE_MIN_REC_FLAG_SET`; SQLSTATE: `HY000`  
Message: Minimum record flag is wrongly set to rec on page '%lu' at level '%lu' for index '%s' of table '%s'.  
`ER_CHECK_TABLE_MIN_REC_FLAG_SET` was added in 8.0.33.



- 
- Error number: [MY-014012](#); Symbol: [ER\\_CHECK\\_TABLE\\_MIN\\_REC\\_FLAG\\_NOT\\_SET](#); SQLSTATE: [HY000](#)  
  
Message: Minimum record flag is not set to first rec on page '%lu' at level '%lu' for index '%s' of table '%s'.  
  
[ER\\_CHECK\\_TABLE\\_MIN\\_REC\\_FLAG\\_NOT\\_SET](#) was added in 8.0.33.
  - Error number: [MY-014013](#); Symbol: [ER\\_NOTE\\_COMPONENT\\_SLOT\\_REGISTRATION\\_SUCCESS](#); SQLSTATE: [HY000](#)  
  
Message: Successfully registered slot '%d' for component '%s'.  
  
[ER\\_NOTE\\_COMPONENT\\_SLOT\\_REGISTRATION\\_SUCCESS](#) was added in 8.0.33.
  - Error number: [MY-014014](#); Symbol: [ER\\_NOTE\\_COMPONENT\\_SLOT\\_DEREGISTRATION\\_SUCCESS](#); SQLSTATE: [HY000](#)  
  
Message: Successfully de-registered slot '%d' from component '%s'.  
  
[ER\\_NOTE\\_COMPONENT\\_SLOT\\_DEREGISTRATION\\_SUCCESS](#) was added in 8.0.33.
  - Error number: [MY-014015](#); Symbol: [ER\\_WARN\\_CANNOT\\_FREE\\_COMPONENT\\_DATA\\_DEALLOCATION\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Cannot free resources stored by component '%s' in thread with ID: '%d'. Component failed to free required resources.  
  
[ER\\_WARN\\_CANNOT\\_FREE\\_COMPONENT\\_DATA\\_DEALLOCATION\\_FAILED](#) was added in 8.0.33.
  - Error number: [MY-014016](#); Symbol: [ER\\_IB\\_RESURRECT\\_TRX\\_INSERT](#); SQLSTATE: [HY000](#)  
  
Message: Transaction ID: %lu found for resurrecting inserts  
  
[ER\\_IB\\_RESURRECT\\_TRX\\_INSERT](#) was added in 8.0.33.
  - Error number: [MY-014017](#); Symbol: [ER\\_IB\\_RESURRECT\\_TRX\\_UPDATE](#); SQLSTATE: [HY000](#)  
  
Message: Transaction ID: %lu found for resurrecting updates  
  
[ER\\_IB\\_RESURRECT\\_TRX\\_UPDATE](#) was added in 8.0.33.
  - Error number: [MY-014018](#); Symbol: [ER\\_IB\\_RESURRECT\\_IDENTIFY\\_TABLE\\_TO\\_LOCK](#); SQLSTATE: [HY000](#)  
  
Message: Identified table ID: %lu to acquire lock  
  
[ER\\_IB\\_RESURRECT\\_IDENTIFY\\_TABLE\\_TO\\_LOCK](#) was added in 8.0.33.
  - Error number: [MY-014019](#); Symbol: [ER\\_IB\\_RESURRECT\\_ACQUIRE\\_TABLE\\_LOCK](#); SQLSTATE: [HY000](#)  
  
Message: Acquired lock on table ID: %lu, name: %s  
  
[ER\\_IB\\_RESURRECT\\_ACQUIRE\\_TABLE\\_LOCK](#) was added in 8.0.33.

- 
- Error number: `MY-014020`; Symbol: `ER_IB_RESURRECT_RECORD_PROGRESS`; SQLSTATE: `HY000`  
Message: Records read: %lu - Pages read: %lu  
`ER_IB_RESURRECT_RECORD_PROGRESS` was added in 8.0.33.
  - Error number: `MY-014021`; Symbol: `ER_IB_RESURRECT_RECORD_COMPLETE`; SQLSTATE: `HY000`  
Message: Total records resurrected: %lu - Total pages read: %lu - Total tables acquired: %lu  
`ER_IB_RESURRECT_RECORD_COMPLETE` was added in 8.0.33.
  - Error number: `MY-014022`; Symbol: `ER_IB_RESURRECT_TRX_INSERT_COMPLETE`; SQLSTATE: `HY000`  
Message: Resurrected %lu transactions doing inserts.  
`ER_IB_RESURRECT_TRX_INSERT_COMPLETE` was added in 8.0.33.
  - Error number: `MY-014023`; Symbol: `ER_IB_RESURRECT_TRX_UPDATE_COMPLETE`; SQLSTATE: `HY000`  
Message: Resurrected %lu transactions doing updates.  
`ER_IB_RESURRECT_TRX_UPDATE_COMPLETE` was added in 8.0.33.
  - Error number: `MY-014024`; Symbol: `ER_AUTHENTICATION_OCI_INVALID_TOKEN`; SQLSTATE: `HY000`  
Message: Invalid security token provided by '%s' for '%s'@'%s': %s.  
`ER_AUTHENTICATION_OCI_INVALID_TOKEN` was added in 8.0.33.
  - Error number: `MY-014025`; Symbol: `ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH`; SQLSTATE: `HY000`  
Message: Unknown user/tenancy (user: %s tenancy: %s) found in security token provided by '%s' for '%s'@'%s'.  
`ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH` was added in 8.0.33.
  - Error number: `MY-014026`; Symbol: `ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED`; SQLSTATE: `HY000`  
Message: Verification failed for security token provided by '%s' for '%s'@'%s' : %s.  
`ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED` was added in 8.0.33.
  - Error number: `MY-014027`; Symbol: `ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY`; SQLSTATE: `HY000`  
Message: Could not download IDDP Public key. Please check if security token provided by '%s' for '%s'@'%s' is valid.  
`ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY` was added in 8.0.33.
  - Error number: `MY-014028`; Symbol: `ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS_IN_TOKEN`; SQLSTATE: `HY000`

---

Message: None of the groups extracted from security token matches any of the entries from authentication string.

[ER\\_AUTHENTICATION\\_OCI\\_NO\\_MATCHING\\_GROUPS\\_IN\\_TOKEN](#) was added in 8.0.33, removed after 8.0.33.

- Error number: [MY-014029](#); Symbol: [ER\\_SYS\\_VAR\\_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register variable '%s'. Please check if it is not already registered by another component.

[ER\\_SYS\\_VAR\\_REGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014030](#); Symbol: [ER\\_SYS\\_VAR\\_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister variable '%s'. Please check if it was registered properly in the first place.

[ER\\_SYS\\_VAR\\_DEREGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014031](#); Symbol: [ER\\_UDF\\_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register function '%s'. Please check if it is not already registered by another component.

[ER\\_UDF\\_REGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014032](#); Symbol: [ER\\_UDF\\_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister function '%s'. Please check if it was registered properly in the first place.

[ER\\_UDF\\_DEREGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014033](#); Symbol: [ER\\_PRIVILEGE\\_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register privilege '%s'. Please check if it is not already registered.

[ER\\_PRIVILEGE\\_REGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014034](#); Symbol: [ER\\_PRIVILEGE\\_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister privilege '%s'. Please check if it was registered properly in the first place.

[ER\\_PRIVILEGE\\_DEREGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014035](#); Symbol: [ER\\_UDF\\_EXEC\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error while executing UDF %s.

[ER\\_UDF\\_EXEC\\_FAILURE](#) was added in 8.0.33.

- Error number: [MY-014036](#); Symbol: [ER\\_UDF\\_EXEC\\_FAILURE\\_REASON](#); SQLSTATE: [HY000](#)

Message: Error while executing UDF %s: %s.

[ER\\_UDF\\_EXEC\\_FAILURE\\_REASON](#) was added in 8.0.33.

- Error number: [MY-014037](#); Symbol: [ER\\_COMPONENT\\_SERVICE\\_CALL](#); SQLSTATE: [HY000](#)

Message: %s failed.

---

`ER_COMPONENT_SERVICE_CALL` was added in 8.0.33.

- Error number: `MY-014038`; Symbol: `ER_COMPONENT_SERVICE_CALL_RESULT`; `SQLSTATE: HY000`  
Message: %s failed with %u.

`ER_COMPONENT_SERVICE_CALL_RESULT` was added in 8.0.33.

- Error number: `MY-014039`; Symbol: `ER_COMPONENT_LOCK`; `SQLSTATE: HY000`  
Message: Lock failed at %s : %u.

`ER_COMPONENT_LOCK` was added in 8.0.33.

- Error number: `MY-014040`; Symbol: `ER_COMPONENT_UNLOCK`; `SQLSTATE: HY000`  
Message: Lock from %s : %u failed to unlock.

`ER_COMPONENT_UNLOCK` was added in 8.0.33.

- Error number: `MY-014041`; Symbol: `ER_COMPONENT_MASKING_OTHER_ERROR`; `SQLSTATE: HY000`  
Message: Masking component error: '%s'.

`ER_COMPONENT_MASKING_OTHER_ERROR` was added in 8.0.33.

- Error number: `MY-014042`; Symbol: `ER_COMPONENT_MASKING_ABI`; `SQLSTATE: HY000`  
Message: %s failed.

`ER_COMPONENT_MASKING_ABI` was added in 8.0.33.

- Error number: `MY-014043`; Symbol: `ER_COMPONENT_MASKING_ABI_REASON`; `SQLSTATE: HY000`  
Message: %s failed because %s.

`ER_COMPONENT_MASKING_ABI_REASON` was added in 8.0.33.

- Error number: `MY-014044`; Symbol: `ER_COMPONENT_MASKING_RANDOM_CREATE`; `SQLSTATE: HY000`  
Message: Creation of random context failed.

`ER_COMPONENT_MASKING_RANDOM_CREATE` was added in 8.0.33.

- Error number: `MY-014045`; Symbol: `ER_COMPONENT_MASKING_RANDOM_CREATE_REASON`; `SQLSTATE: HY000`  
Message: Creation of random context failed because %s.

`ER_COMPONENT_MASKING_RANDOM_CREATE_REASON` was added in 8.0.33.

- Error number: `MY-014046`; Symbol: `ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE`; `SQLSTATE: HY000`  
Message: Cannot access %s.%s table.

`ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE` was added in 8.0.33.

- Error number: `MY-014047`; Symbol: `ER_REDUCED_DBLWR_FILE_CORRUPTED`; `SQLSTATE: HY000`

---

Message: Cannot recover from detect\_only doublewrite buffer as page %u from batch doublewrite file is corrupted.

[ER\\_REDUCED\\_DBLWR\\_FILE\\_CORRUPTED](#) was added in 8.0.30.

- Error number: [MY-014048](#); Symbol: [ER\\_REDUCED\\_DBLWR\\_PAGE\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Database page corruption of tablespace %s space\_id: %u page\_num: %u. Cannot recover it from the doublewrite buffer because it was written in detect\_only-doublewrite mode.

[ER\\_REDUCED\\_DBLWR\\_PAGE\\_FOUND](#) was added in 8.0.30.

- Error number: [MY-014049](#); Symbol: [ER\\_CONN\\_INIT\\_CONNECT\\_IGNORED\\_MFA](#); SQLSTATE: [HY000](#)

Message: init\_connect variable is ignored for user: %s host: %s due to multi-factor registration required sandboxing

[ER\\_CONN\\_INIT\\_CONNECT\\_IGNORED\\_MFA](#) was added in 8.0.33.

- Error number: [MY-014050](#); Symbol: [ER\\_SECONDARY\\_ENGINE\\_DDL\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Execution of alter table %s %s failed because %s.

[ER\\_SECONDARY\\_ENGINE\\_DDL\\_FAILED](#) was added in 8.0.33.

- Error number: [MY-014051](#); Symbol: [ER\\_THREAD\\_POOL\\_CONNECTION\\_REPORT](#); SQLSTATE: [HY000](#)

Message: TP conn (port: managed(delta), active, opened, closed, added, dropped): %s

[ER\\_THREAD\\_POOL\\_CONNECTION\\_REPORT](#) was added in 8.0.33.

- Error number: [MY-014052](#); Symbol: [ER\\_WARN\\_SCHEDULED\\_TASK\\_RUN\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Scheduled run of task %s failed

[ER\\_WARN\\_SCHEDULED\\_TASK\\_RUN\\_FAILED](#) was added in 8.0.34.

- Error number: [MY-014053](#); Symbol: [ER\\_AUDIT\\_LOG\\_INVALID\\_FLUSH\\_INTERVAL\\_VALUE](#); SQLSTATE: [HY000](#)

Message: Invalid flush interval specified: %lu. Valid values are 0 (off) or greater than or equal to %d. Adjusting to %d

[ER\\_AUDIT\\_LOG\\_INVALID\\_FLUSH\\_INTERVAL\\_VALUE](#) was added in 8.0.34.

- Error number: [MY-014054](#); Symbol: [ER\\_LOG\\_CANNOT\\_PURGE\\_BINLOG\\_WITH\\_BACKUP\\_LOCK](#); SQLSTATE: [HY000](#)

Message: Could not purge binary logs since another session is executing LOCK INSTANCE FOR BACKUP. Wait for that session to release the lock.

[ER\\_LOG\\_CANNOT\\_PURGE\\_BINLOG\\_WITH\\_BACKUP\\_LOCK](#) was added in 8.0.34.

- Error number: [MY-014055](#); Symbol: [ER\\_CONVERT\\_MULTI\\_VALUE](#); SQLSTATE: [HY000](#)

Message: Multi-values cannot be converted to MySQL format: %s

[ER\\_CONVERT\\_MULTI\\_VALUE](#) was added in 8.0.35.

- 
- Error number: [MY-014056](#); Symbol: [ER\\_IB\\_DDL\\_CONVERT\\_HEAP\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: Heap required to convert columns is not present.  
[ER\\_IB\\_DDL\\_CONVERT\\_HEAP\\_NOT\\_FOUND](#) was added in 8.0.35.
  - Error number: [MY-014057](#); Symbol: [ER\\_SERVER\\_DOWNGRADE\\_FROM\\_VERSION](#); SQLSTATE: [HY000](#)  
Message: MySQL server downgrading from version '%u' to '%u'.  
[ER\\_SERVER\\_DOWNGRADE\\_FROM\\_VERSION](#) was added in 8.0.35.
  - Error number: [MY-014058](#); Symbol: [ER\\_BEYOND\\_SERVER\\_DOWNGRADE\\_THRESHOLD](#); SQLSTATE: [HY000](#)  
Message: Invalid MySQL server downgrade: Cannot downgrade from %u to %u. Target MySQL server version is lower than the server downgrade threshold %u.  
[ER\\_BEYOND\\_SERVER\\_DOWNGRADE\\_THRESHOLD](#) was added in 8.0.35.
  - Error number: [MY-014059](#); Symbol: [ER\\_BEYOND\\_SERVER\\_UPGRADE\\_THRESHOLD](#); SQLSTATE: [HY000](#)  
Message: Invalid MySQL server upgrade: Cannot upgrade from %u to %u. Target MySQL server version is lower than the server upgrade threshold %u.  
[ER\\_BEYOND\\_SERVER\\_UPGRADE\\_THRESHOLD](#) was added in 8.0.35.
  - Error number: [MY-014060](#); Symbol: [ER\\_INVALID\\_SERVER\\_UPGRADE\\_NOT\\_LTS](#); SQLSTATE: [HY000](#)  
Message: Invalid MySQL server upgrade: Cannot upgrade from %u to %u. Upgrade to next major version is only allowed from the last LTS release, which version %u is not.  
[ER\\_INVALID\\_SERVER\\_UPGRADE\\_NOT\\_LTS](#) was added in 8.0.35.
  - Error number: [MY-014061](#); Symbol: [ER\\_INVALID\\_SERVER\\_DOWNGRADE\\_NOT\\_PATCH](#); SQLSTATE: [HY000](#)  
Message: Invalid MySQL server downgrade: Cannot downgrade from %u to %u. Downgrade is only permitted between patch releases.  
[ER\\_INVALID\\_SERVER\\_DOWNGRADE\\_NOT\\_PATCH](#) was added in 8.0.35.
  - Error number: [MY-014062](#); Symbol: [ER\\_FAILED\\_GET\\_DD\\_PROPERTY](#); SQLSTATE: [HY000](#)  
Message: Failed to get the data dictionary property %s.  
[ER\\_FAILED\\_GET\\_DD\\_PROPERTY](#) was added in 8.0.35.
  - Error number: [MY-014063](#); Symbol: [ER\\_FAILED\\_SET\\_DD\\_PROPERTY](#); SQLSTATE: [HY000](#)  
Message: Failed to set the data dictionary property %s.  
[ER\\_FAILED\\_SET\\_DD\\_PROPERTY](#) was added in 8.0.35.
  - Error number: [MY-014064](#); Symbol: [ER\\_SERVER\\_DOWNGRADE\\_STATUS](#); SQLSTATE: [HY000](#)  
Message: Server downgrade from '%d' to '%d' %s.  
[ER\\_SERVER\\_DOWNGRADE\\_STATUS](#) was added in 8.0.35.

- 
- Error number: [MY-014065](#); Symbol: [ER\\_INFORMATION\\_SCHEMA\\_VERSION\\_CHANGE](#); SQLSTATE: [HY000](#)  
  
Message: %s information schema from version %u to %u.  
  
[ER\\_INFORMATION\\_SCHEMA\\_VERSION\\_CHANGE](#) was added in 8.0.35.
  - Error number: [MY-014066](#); Symbol: [ER\\_PERFORMANCE\\_SCHEMA\\_VERSION\\_CHANGE](#); SQLSTATE: [HY000](#)  
  
Message: %s performance schema from version %u to %u.  
  
[ER\\_PERFORMANCE\\_SCHEMA\\_VERSION\\_CHANGE](#) was added in 8.0.35.
  - Error number: [MY-014067](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_OR\\_BLOCKED\\_CIPHER](#); SQLSTATE: [HY000](#)  
  
Message: Value for option '%s' contains cipher '%s' that is either blocked or deprecated (and will be removed in a future release). Please refer to the documentation for more details.  
  
[ER\\_WARN\\_DEPRECATED\\_OR\\_BLOCKED\\_CIPHER](#) was added in 8.0.35.
  - Error number: [MY-014068](#); Symbol: [ER\\_IB\\_MSG\\_DDL\\_FAIL\\_NO\\_BUILDER](#); SQLSTATE: [HY000](#)  
  
Message: DDL failed as Builder is already freed. Builder: state=%u, error\_state=%u. Index: id=%zu, name='%s', space\_id=%u, page=%u. Table: old\_name='%s', new\_name='%s'.  
  
[ER\\_IB\\_MSG\\_DDL\\_FAIL\\_NO\\_BUILDER](#) was added in 8.0.36.
  - Error number: [MY-014069](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_INFO\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
  
Message: Member identified %s: '%s' does not exist on Group Replication membership during %s.  
  
[ER\\_GRP\\_RPL\\_MEMBER\\_INFO\\_DOES\\_NOT\\_EXIST](#) was added in 8.0.36.
  - Error number: [MY-014070](#); Symbol: [ER\\_USAGE\\_DEPRECATION\\_COUNTER](#); SQLSTATE: [HY000](#)  
  
Message: Deprecated '%s' used %s times, last time used '%s'.  
  
[ER\\_USAGE\\_DEPRECATION\\_COUNTER](#) was added in 8.0.36.
  - Error number: [MY-014071](#); Symbol: [ER\\_WAITING\\_FOR\\_NO\\_CONNECTIONS](#); SQLSTATE: [HY000](#)  
  
Message: Waiting for %u connections to be closed.  
  
[ER\\_WAITING\\_FOR\\_NO\\_CONNECTIONS](#) was added in 8.0.38.
  - Error number: [MY-014072](#); Symbol: [ER\\_WAITING\\_FOR\\_NO\\_THDS](#); SQLSTATE: [HY000](#)  
  
Message: Waiting for THDs in partition %u to be closed, %u still left. %u THDs left in total for all partitions.  
  
[ER\\_WAITING\\_FOR\\_NO\\_THDS](#) was added in 8.0.38.

- 
- Error number: [MY-014073](#); Symbol: [ER\\_IB\\_INDEX\\_PART\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
Message: Index %s of %s.%s exceeds limit of %lu bytes per column.  
[ER\\_IB\\_INDEX\\_PART\\_TOO\\_LONG](#) was added in 8.0.38.
  - Error number: [MY-014074](#); Symbol: [ER\\_DD\\_UPDATE\\_DATADIR\\_FLAG\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed to update data directory flag for dd table with tablespace id '%llu' when ibd file for '%s' is moved to new location '%s' during server shutdown  
[ER\\_DD\\_UPDATE\\_DATADIR\\_FLAG\\_FAIL](#) was added in 8.0.38.
  - Error number: [MY-014075](#); Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_PREV](#); SQLSTATE: [HY000](#)  
Message: %s DD ID: %llu - Tablespace %u, name '%s', found at '%s' outside default data directory, but DD misses info about DATA DIRECTORY  
[ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_PREV](#) was added in 8.0.38.
  - Error number: [MY-014075](#); Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_PREV\\_OR\\_HAS\\_DATADIR](#); SQLSTATE: [HY000](#)  
Message: %s DD ID: %llu - Tablespace %u, name '%s', found at '%s' outside default data directory. It is either moved or is created with 'DATA DIRECTORY'  
[ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_PREV\\_OR\\_HAS\\_DATADIR](#) was added in 8.0.39, removed after 8.0.40.
  - Error number: [MY-014076](#); Symbol: [ER\\_RPL\\_KILL\\_OLD\\_DUMP\\_THREAD\\_ENCOUNTERED](#); SQLSTATE: [HY000](#)  
Message: Upon reconnection with the replica, while initializing the dump thread for %s <%s>, an existing dump thread with the same %s was detected. The source is terminating the previous dump thread (%u), which is normal and expected.  
[ER\\_RPL\\_KILL\\_OLD\\_DUMP\\_THREAD\\_ENCOUNTERED](#) was added in 8.0.41.
  - Error number: [MY-014077](#); Symbol: [ER\\_RPL\\_MTA\\_ALLOW\\_COMMIT\\_OUT\\_OF\\_ORDER](#); SQLSTATE: [HY000](#)  
Message: The transaction '%s' will commit out of order with respect to its source to follow the group global order.  
[ER\\_RPL\\_MTA\\_ALLOW\\_COMMIT\\_OUT\\_OF\\_ORDER](#) was added in 8.0.41.
  - Error number: [MY-014078](#); Symbol: [ER\\_CHECK\\_TABLE\\_FUNCTIONS](#); SQLSTATE: [HY000](#)  
Message: Can not open table `%s`.`%s`; functions in constraints, partitions, or virtual columns may have failed.  
[ER\\_CHECK\\_TABLE\\_FUNCTIONS](#) was added in 8.0.42.
  - Error number: [MY-014079](#); Symbol: [ER\\_CHECK\\_TABLE\\_FUNCTIONS\\_DETAIL](#); SQLSTATE: [HY000](#)  
Message: %s  
[ER\\_CHECK\\_TABLE\\_FUNCTIONS\\_DETAIL](#) was added in 8.0.42.



---

## Chapter 3 Client Error Message Reference

Client error messages originate from within the MySQL client library. Here is an example client error message, as displayed by the `mysql` client:

```
$> mysql -h no-such-host
ERROR 2005 (HY000): Unknown MySQL server host 'no-such-host' (0)
```

Each client error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For client errors, the SQLSTATE value is always 'HY000' (general error), so it is not meaningful for distinguishing one client error from another.

The client library also makes available to host client programs any errors that originate on the server side and are received by the client from the server. For a list of server-side errors, see [Chapter 2, Server Error Message Reference](#).

In addition to the errors in the following list, the client library can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: 2000; Symbol: `CR_UNKNOWN_ERROR`;  
Message: Unknown MySQL error
- Error number: 2001; Symbol: `CR_SOCKET_CREATE_ERROR`;  
Message: Can't create UNIX socket (%d)
- Error number: 2002; Symbol: `CR_CONNECTION_ERROR`;  
Message: Can't connect to local MySQL server through socket '%s' (%d)
- Error number: 2003; Symbol: `CR_CONN_HOST_ERROR`;  
Message: Can't connect to MySQL server on '%s:%u' (%d)
- Error number: 2004; Symbol: `CR_IPSOCK_ERROR`;  
Message: Can't create TCP/IP socket (%d)
- Error number: 2005; Symbol: `CR_UNKNOWN_HOST`;  
Message: Unknown MySQL server host '%s' (%d)
- Error number: 2006; Symbol: `CR_SERVER_GONE_ERROR`;  
Message: MySQL server has gone away
- Error number: 2007; Symbol: `CR_VERSION_ERROR`;  
Message: Protocol mismatch; server version = %d, client version = %d
- Error number: 2008; Symbol: `CR_OUT_OF_MEMORY`;  
Message: MySQL client ran out of memory
- Error number: 2009; Symbol: `CR_WRONG_HOST_INFO`;  
Message: Wrong host info

- 
- Error number: [2010](#); Symbol: [CR\\_LOCALHOST\\_CONNECTION](#);  
Message: Localhost via UNIX socket
  - Error number: [2011](#); Symbol: [CR\\_TCP\\_CONNECTION](#);  
Message: %s via TCP/IP
  - Error number: [2012](#); Symbol: [CR\\_SERVER\\_HANDSHAKE\\_ERR](#);  
Message: Error in server handshake
  - Error number: [2013](#); Symbol: [CR\\_SERVER\\_LOST](#);  
Message: Lost connection to MySQL server during query
  - Error number: [2014](#); Symbol: [CR\\_COMMANDS\\_OUT\\_OF\\_SYNC](#);  
Message: Commands out of sync; you can't run this command now  
  
Commands were executed in an improper order. This error occurs when a function is called that is not appropriate for the current state of the connection. For example, if `mysql_stmt_fetch()` is not called enough times to read an entire result set (that is, enough times to return `MYSQL_NO_DATA`), this error may occur for the following C API call.
  - Error number: [2015](#); Symbol: [CR\\_NAMEDPIPE\\_CONNECTION](#);  
Message: Named pipe: %s
  - Error number: [2016](#); Symbol: [CR\\_NAMEDPIPEWAIT\\_ERROR](#);  
Message: Can't wait for named pipe to host: %s pipe: %s (%lu)
  - Error number: [2017](#); Symbol: [CR\\_NAMEDPIPEOPEN\\_ERROR](#);  
Message: Can't open named pipe to host: %s pipe: %s (%lu)
  - Error number: [2018](#); Symbol: [CR\\_NAMEDPIPESETSTATE\\_ERROR](#);  
Message: Can't set state of named pipe to host: %s pipe: %s (%lu)
  - Error number: [2019](#); Symbol: [CR\\_CANT\\_READ\\_CHARSET](#);  
Message: Can't initialize character set %s (path: %s)
  - Error number: [2020](#); Symbol: [CR\\_NET\\_PACKET\\_TOO\\_LARGE](#);  
Message: Got packet bigger than 'max\_allowed\_packet' bytes
  - Error number: [2021](#); Symbol: [CR\\_EMBEDDED\\_CONNECTION](#);  
Message: Embedded server
  - Error number: [2022](#); Symbol: [CR\\_PROBE\\_SLAVE\\_STATUS](#);  
Message: Error on SHOW SLAVE STATUS:  
  
[CR\\_PROBE\\_SLAVE\\_STATUS](#) was removed after 8.0.32.
  - Error number: [2022](#); Symbol: [CR\\_PROBE\\_REPLICA\\_STATUS](#);

---

Message: Error on SHOW REPLICA STATUS:

[CR\\_PROBE\\_REPLICA\\_STATUS](#) was added in 8.0.33.

- Error number: [2023](#); Symbol: [CR\\_PROBE\\_SLAVE\\_HOSTS](#);

Message: Error on SHOW SLAVE HOSTS:

[CR\\_PROBE\\_SLAVE\\_HOSTS](#) was removed after 8.0.32.

- Error number: [2023](#); Symbol: [CR\\_PROBE\\_REPLICA\\_HOSTS](#);

Message: Error on SHOW REPLICA HOSTS:

[CR\\_PROBE\\_REPLICA\\_HOSTS](#) was added in 8.0.33.

- Error number: [2024](#); Symbol: [CR\\_PROBE\\_SLAVE\\_CONNECT](#);

Message: Error connecting to slave:

[CR\\_PROBE\\_SLAVE\\_CONNECT](#) was removed after 8.0.32.

- Error number: [2024](#); Symbol: [CR\\_PROBE\\_REPLICA\\_CONNECT](#);

Message: Error connecting to replica:

[CR\\_PROBE\\_REPLICA\\_CONNECT](#) was added in 8.0.33.

- Error number: [2025](#); Symbol: [CR\\_PROBE\\_MASTER\\_CONNECT](#);

Message: Error connecting to master:

[CR\\_PROBE\\_MASTER\\_CONNECT](#) was removed after 8.0.32.

- Error number: [2025](#); Symbol: [CR\\_PROBE\\_SOURCE\\_CONNECT](#);

Message: Error connecting to source:

[CR\\_PROBE\\_SOURCE\\_CONNECT](#) was added in 8.0.33.

- Error number: [2026](#); Symbol: [CR\\_SSL\\_CONNECTION\\_ERROR](#);

Message: SSL connection error: %s

- Error number: [2027](#); Symbol: [CR\\_MALFORMED\\_PACKET](#);

Message: Malformed packet

- Error number: [2028](#); Symbol: [CR\\_WRONG\\_LICENSE](#);

Message: This client library is licensed only for use with MySQL servers having '%s' license

- Error number: [2029](#); Symbol: [CR\\_NULL\\_POINTER](#);

Message: Invalid use of null pointer

- Error number: [2030](#); Symbol: [CR\\_NO\\_PREPARE\\_STMT](#);

Message: Statement not prepared

- 
- Error number: [2031](#); Symbol: [CR\\_PARAMS\\_NOT\\_BOUND](#);  
Message: No data supplied for parameters in prepared statement
  - Error number: [2032](#); Symbol: [CR\\_DATA\\_TRUNCATED](#);  
Message: Data truncated
  - Error number: [2033](#); Symbol: [CR\\_NO\\_PARAMETERS\\_EXISTS](#);  
Message: No parameters exist in the statement
  - Error number: [2034](#); Symbol: [CR\\_INVALID\\_PARAMETER\\_NO](#);  
Message: Invalid parameter number  
  
The column number for `mysql_stmt_fetch_column()` was invalid.  
  
The parameter number for `mysql_stmt_send_long_data()` was invalid.  
  
A key name was empty or the amount of connection attribute data for `mysql_options4()` exceeds the 64KB limit.
  - Error number: [2035](#); Symbol: [CR\\_INVALID\\_BUFFER\\_USE](#);  
Message: Can't send long data for non-string/non-binary data types (parameter: %d)
  - Error number: [2036](#); Symbol: [CR\\_UNSUPPORTED\\_PARAM\\_TYPE](#);  
Message: Using unsupported buffer type: %d (parameter: %d)
  - Error number: [2037](#); Symbol: [CR\\_SHARED\\_MEMORY\\_CONNECTION](#);  
Message: Shared memory: %s
  - Error number: [2038](#); Symbol: [CR\\_SHARED\\_MEMORY\\_CONNECT\\_REQUEST\\_ERROR](#);  
Message: Can't open shared memory; client could not create request event (%lu)
  - Error number: [2039](#); Symbol: [CR\\_SHARED\\_MEMORY\\_CONNECT\\_ANSWER\\_ERROR](#);  
Message: Can't open shared memory; no answer event received from server (%lu)
  - Error number: [2040](#); Symbol: [CR\\_SHARED\\_MEMORY\\_CONNECT\\_FILE\\_MAP\\_ERROR](#);  
Message: Can't open shared memory; server could not allocate file mapping (%lu)
  - Error number: [2041](#); Symbol: [CR\\_SHARED\\_MEMORY\\_CONNECT\\_MAP\\_ERROR](#);  
Message: Can't open shared memory; server could not get pointer to file mapping (%lu)
  - Error number: [2042](#); Symbol: [CR\\_SHARED\\_MEMORY\\_FILE\\_MAP\\_ERROR](#);  
Message: Can't open shared memory; client could not allocate file mapping (%lu)
  - Error number: [2043](#); Symbol: [CR\\_SHARED\\_MEMORY\\_MAP\\_ERROR](#);  
Message: Can't open shared memory; client could not get pointer to file mapping (%lu)
  - Error number: [2044](#); Symbol: [CR\\_SHARED\\_MEMORY\\_EVENT\\_ERROR](#);

---

Message: Can't open shared memory; client could not create %s event (%lu)

- Error number: 2045; Symbol: CR\_SHARED\_MEMORY\_CONNECT\_ABANDONED\_ERROR;

Message: Can't open shared memory; no answer from server (%lu)

- Error number: 2046; Symbol: CR\_SHARED\_MEMORY\_CONNECT\_SET\_ERROR;

Message: Can't open shared memory; cannot send request event to server (%lu)

- Error number: 2047; Symbol: CR\_CONN\_UNKNOW\_PROTOCOL;

Message: Wrong or unknown protocol

- Error number: 2048; Symbol: CR\_INVALID\_CONN\_HANDLE;

Message: Invalid connection handle

- Error number: 2049; Symbol: CR\_UNUSED\_1;

Message: Connection using old (pre-4.1.1) authentication protocol refused (client option 'secure\_auth' enabled)

- Error number: 2050; Symbol: CR\_FETCH\_CANCELED;

Message: Row retrieval was canceled by mysql\_stmt\_close() call

- Error number: 2051; Symbol: CR\_NO\_DATA;

Message: Attempt to read column without prior row fetch

- Error number: 2052; Symbol: CR\_NO\_STMT\_METADATA;

Message: Prepared statement contains no metadata

- Error number: 2053; Symbol: CR\_NO\_RESULT\_SET;

Message: Attempt to read a row while there is no result set associated with the statement

- Error number: 2054; Symbol: CR\_NOT\_IMPLEMENTED;

Message: This feature is not implemented yet

- Error number: 2055; Symbol: CR\_SERVER\_LOST\_EXTENDED;

Message: Lost connection to MySQL server at '%s', system error: %d

- Error number: 2056; Symbol: CR\_STMT\_CLOSED;

Message: Statement closed indirectly because of a preceding %s() call

- Error number: 2057; Symbol: CR\_NEW\_STMT\_METADATA;

Message: The number of columns in the result set differs from the number of bound buffers. You must reset the statement, rebind the result set columns, and execute the statement again

- Error number: 2058; Symbol: CR\_ALREADY\_CONNECTED;

Message: This handle is already connected. Use a separate handle for each connection.

- 
- Error number: [2059](#); Symbol: [CR\\_AUTH\\_PLUGIN\\_CANNOT\\_LOAD](#);  
Message: Authentication plugin '%s' cannot be loaded: %s
  - Error number: [2060](#); Symbol: [CR\\_DUPLICATE\\_CONNECTION\\_ATTR](#);  
Message: There is an attribute with the same name already  
A duplicate connection attribute name was specified for `mysql_options4()`.
  - Error number: [2061](#); Symbol: [CR\\_AUTH\\_PLUGIN\\_ERR](#);  
Message: Authentication plugin '%s' reported error: %s
  - Error number: [2062](#); Symbol: [CR\\_INSECURE\\_API\\_ERR](#);  
Message: Insecure API function call: '%s' Use instead: '%s'  
An insecure function call was detected. Modify the application to use the suggested alternative function instead.
  - Error number: [2063](#); Symbol: [CR\\_FILE\\_NAME\\_TOO\\_LONG](#);  
Message: File name is too long  
[CR\\_FILE\\_NAME\\_TOO\\_LONG](#) was added in 8.0.1.
  - Error number: [2064](#); Symbol: [CR\\_SSL\\_FIPS\\_MODE\\_ERR](#);  
Message: Set FIPS mode ON/STRICT failed  
[CR\\_SSL\\_FIPS\\_MODE\\_ERR](#) was added in 8.0.11.
  - Error number: [2065](#); Symbol: [CR\\_COMPRESSION\\_NOT\\_SUPPORTED](#);  
Message: Compression protocol not supported with asynchronous protocol  
[CR\\_COMPRESSION\\_NOT\\_SUPPORTED](#) was added in 8.0.16, removed after 8.0.20.
  - Error number: [2065](#); Symbol: [CR\\_DEPRECATED\\_COMPRESSION\\_NOT\\_SUPPORTED](#);  
Message: Compression protocol not supported with asynchronous protocol  
[CR\\_DEPRECATED\\_COMPRESSION\\_NOT\\_SUPPORTED](#) was added in 8.0.21.
  - Error number: [2066](#); Symbol: [CR\\_COMPRESSION\\_WRONGLY\\_CONFIGURED](#);  
Message: Connection failed due to wrongly configured compression algorithm  
[CR\\_COMPRESSION\\_WRONGLY\\_CONFIGURED](#) was added in 8.0.18.
  - Error number: [2067](#); Symbol: [CR\\_KERBEROS\\_USER\\_NOT\\_FOUND](#);  
Message: SSO user not found, Please perform SSO authentication using kerberos.  
[CR\\_KERBEROS\\_USER\\_NOT\\_FOUND](#) was added in 8.0.20.
  - Error number: [2068](#); Symbol: [CR\\_LOAD\\_DATA\\_LOCAL\\_INFILE\\_REJECTED](#);  
Message: LOAD DATA LOCAL INFILE file request rejected due to restrictions on access.

---

`CR_LOAD_DATA_LOCAL_INFILE_REJECTED` was added in 8.0.21.

- Error number: `2069`; Symbol: `CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL`;

Message: Determining the real path for '%s' failed with error (%d): %s

`CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL` was added in 8.0.21.

- Error number: `2070`; Symbol: `CR_DNS_SRV_LOOKUP_FAILED`;

Message: DNS SRV lookup failed with error : %d

`CR_DNS_SRV_LOOKUP_FAILED` was added in 8.0.22.

- Error number: `2071`; Symbol: `CR_MANDATORY_TRACKER_NOT_FOUND`;

Message: Client does not recognise tracker type %d marked as mandatory by server.

`CR_MANDATORY_TRACKER_NOT_FOUND` was added in 8.0.27.

- Error number: `2072`; Symbol: `CR_INVALID_FACTOR_NO`;

Message: Invalid first argument for `MYSQL_OPT_USER_PASSWORD` option. Valid value should be between 1 and 3 inclusive.

`CR_INVALID_FACTOR_NO` was added in 8.0.27.

- Error number: `2073`; Symbol: `CR_CANT_GET_SESSION_DATA`;

Message: Can't get session data: %s

`CR_CANT_GET_SESSION_DATA` was added in 8.0.29.

- Error number: `2074`; Symbol: `CR_INVALID_CLIENT_CHARSET`;

Message: '%s' character set is having more than 1 byte minimum character length, which cannot be used as a client character set. Please use any of the single byte minimum ones, e.g. `utf8mb4`, `latin1` etc.

`CR_INVALID_CLIENT_CHARSET` was added in 8.0.33.





---

## Chapter 4 Global Error Message Reference

This document lists “global” error messages that are shared in the sense that they can be produced by the MySQL server or by MySQL client programs. These errors have error codes in the range from 1 to 999.

Each global error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For global errors, the SQLSTATE value is always 'HY000' (general error), so it is not meaningful for distinguishing one client error from another.

If the server writes a message to the error log that has a global error code, it pads the error code with leading zeros to six digits and adds a prefix of `MY-` (example: `MY-000022`). The following list displays error codes in that format.

If a client returns a message with a global error code, it adds no zero-padding or prefix to the error code.

- Error number: 1; Symbol: `EE_CANTCREATEFILE`;  
Message: Can't create/write to file '%s' (OS errno %d - %s)
- Error number: 2; Symbol: `EE_READ`;  
Message: Error reading file '%s' (OS errno %d - %s)
- Error number: 3; Symbol: `EE_WRITE`;  
Message: Error writing file '%s' (OS errno %d - %s)
- Error number: 4; Symbol: `EE_BADCLOSE`;  
Message: Error on close of '%s' (OS errno %d - %s)
- Error number: 5; Symbol: `EE_OUTOFMEMORY`;  
Message: Out of memory (Needed %u bytes)
- Error number: 6; Symbol: `EE_DELETE`;  
Message: Error on delete of '%s' (OS errno %d - %s)
- Error number: 7; Symbol: `EE_LINK`;  
Message: Error on rename of '%s' to '%s' (OS errno %d - %s)
- Error number: 9; Symbol: `EE_EOFERR`;  
Message: Unexpected EOF found when reading file '%s' (OS errno %d - %s)
- Error number: 10; Symbol: `EE_CANTLOCK`;  
Message: Can't lock file (OS errno %d - %s)
- Error number: 11; Symbol: `EE_CANTUNLOCK`;  
Message: Can't unlock file (OS errno %d - %s)
- Error number: 12; Symbol: `EE_DIR`;

- 
- Message: Can't read dir of '%s' (OS errno %d - %s)
  - Error number: [13](#); Symbol: [EE\\_STAT](#);  
Message: Can't get stat of '%s' (OS errno %d - %s)
  - Error number: [14](#); Symbol: [EE\\_CANT\\_CHSIZE](#);  
Message: Can't change size of file (OS errno %d - %s)
  - Error number: [15](#); Symbol: [EE\\_CANT\\_OPEN\\_STREAM](#);  
Message: Can't open stream from handle (OS errno %d - %s)
  - Error number: [16](#); Symbol: [EE\\_GETWD](#);  
Message: Can't get working directory (OS errno %d - %s)
  - Error number: [17](#); Symbol: [EE\\_SETWD](#);  
Message: Can't change dir to '%s' (OS errno %d - %s)
  - Error number: [18](#); Symbol: [EE\\_LINK\\_WARNING](#);  
Message: Warning: '%s' had %d links
  - Error number: [19](#); Symbol: [EE\\_OPEN\\_WARNING](#);  
Message: Warning: %d files and %d streams are left open
  - Error number: [20](#); Symbol: [EE\\_DISK\\_FULL](#);  
Message: Disk is full writing '%s' (OS errno %d - %s). Waiting for someone to free space...
  - Error number: [21](#); Symbol: [EE\\_CANT\\_MKDIR](#);  
Message: Can't create directory '%s' (OS errno %d - %s)
  - Error number: [22](#); Symbol: [EE\\_UNKNOWN\\_CHARSET](#);  
Message: Character set '%s' is not a compiled character set and is not specified in the '%s' file
  - Error number: [23](#); Symbol: [EE\\_OUT\\_OF\\_FILERESOURCES](#);  
Message: Out of resources when opening file '%s' (OS errno %d - %s)
  - Error number: [24](#); Symbol: [EE\\_CANT\\_READLINK](#);  
Message: Can't read value for symlink '%s' (Error %d - %s)
  - Error number: [25](#); Symbol: [EE\\_CANT\\_SYMLINK](#);  
Message: Can't create symlink '%s' pointing at '%s' (Error %d - %s)
  - Error number: [26](#); Symbol: [EE\\_REALPATH](#);  
Message: Error on realpath() on '%s' (Error %d - %s)
  - Error number: [27](#); Symbol: [EE\\_SYNC](#);

---

Message: Can't sync file '%s' to disk (OS errno %d - %s)

- Error number: 28; Symbol: `EE_UNKNOWN_COLLATION`;

Message: Collation '%s' is not a compiled collation and is not specified in the '%s' file

- Error number: 29; Symbol: `EE_FILENOTFOUND`;

Message: File '%s' not found (OS errno %d - %s)

- Error number: 30; Symbol: `EE_FILE_NOT_CLOSED`;

Message: File '%s' (fileno: %d) was not closed

- Error number: 31; Symbol: `EE_CHANGE_OWNERSHIP`;

Message: Cannot change ownership of the file '%s' (OS errno %d - %s)

- Error number: 32; Symbol: `EE_CHANGE_PERMISSIONS`;

Message: Cannot change permissions of the file '%s' (OS errno %d - %s)

- Error number: 33; Symbol: `EE_CANT_SEEK`;

Message: Cannot seek in file '%s' (OS errno %d - %s)

- Error number: 34; Symbol: `EE_CAPACITY_EXCEEDED`;

Message: Memory capacity exceeded (capacity %llu bytes)

- Error number: 35; Symbol: `EE_DISK_FULL_WITH_RETRY_MSG`;

Message: Disk is full writing '%s' (OS errno %d - %s). Waiting for someone to free space... Retry in %d secs. Message reprinted in %d secs.

`EE_DISK_FULL_WITH_RETRY_MSG` was added in 8.0.13.

- Error number: 36; Symbol: `EE_FAILED_TO_CREATE_TIMER`;

Message: Failed to create timer (OS errno %d).

`EE_FAILED_TO_CREATE_TIMER` was added in 8.0.13.

- Error number: 37; Symbol: `EE_FAILED_TO_DELETE_TIMER`;

Message: Failed to delete timer (OS errno %d).

`EE_FAILED_TO_DELETE_TIMER` was added in 8.0.13.

- Error number: 38; Symbol: `EE_FAILED_TO_CREATE_TIMER_QUEUE`;

Message: Failed to create timer queue (OS errno %d).

`EE_FAILED_TO_CREATE_TIMER_QUEUE` was added in 8.0.13.

- Error number: 39; Symbol: `EE_FAILED_TO_START_TIMER_NOTIFY_THREAD`;

Message: Failed to start timer notify thread.

---

`EE_FAILED_TO_START_TIMER_NOTIFY_THREAD` was added in 8.0.13.

- Error number: 40; Symbol: `EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT_EVENT`;  
Message: Failed to create event to interrupt timer notifier thread (OS errno %d).

`EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT_EVENT` was added in 8.0.13.

- Error number: 41; Symbol: `EE_EXITING_TIMER_NOTIFY_THREAD`;  
Message: Failed to register timer event with queue (OS errno %d), exiting timer notifier thread.

`EE_EXITING_TIMER_NOTIFY_THREAD` was added in 8.0.13.

- Error number: 42; Symbol: `EE_WIN_LIBRARY_LOAD_FAILED`;  
Message: LoadLibrary("kernel32.dll") failed: GetLastError returns %lu.

`EE_WIN_LIBRARY_LOAD_FAILED` was added in 8.0.13.

- Error number: 43; Symbol: `EE_WIN_RUN_TIME_ERROR_CHECK`;  
Message: %s.

`EE_WIN_RUN_TIME_ERROR_CHECK` was added in 8.0.13.

- Error number: 44; Symbol: `EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE`;  
Message: Failed to determine large page size.

`EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE` was added in 8.0.13.

- Error number: 45; Symbol: `EE_FAILED_TO_KILL_ALL_THREADS`;  
Message: Error in my\_thread\_global\_end(): %d thread(s) did not exit.

`EE_FAILED_TO_KILL_ALL_THREADS` was added in 8.0.13.

- Error number: 46; Symbol: `EE_FAILED_TO_CREATE_IO_COMPLETION_PORT`;  
Message: Failed to create IO completion port (OS errno %d).

`EE_FAILED_TO_CREATE_IO_COMPLETION_PORT` was added in 8.0.13.

- Error number: 47; Symbol: `EE_FAILED_TO_OPEN_DEFAULTS_FILE`;  
Message: Failed to open required defaults file: %s

`EE_FAILED_TO_OPEN_DEFAULTS_FILE` was added in 8.0.13.

- Error number: 48; Symbol: `EE_FAILED_TO_HANDLE_DEFAULTS_FILE`;  
Message: Fatal error in defaults handling. Program aborted!

`EE_FAILED_TO_HANDLE_DEFAULTS_FILE` was added in 8.0.13.

- Error number: 49; Symbol: `EE_WRONG_DIRECTIVE_IN_CONFIG_FILE`;  
Message: Wrong '!%s' directive in config file %s at line %d.

---

`EE_WRONG_DIRECTIVE_IN_CONFIG_FILE` was added in 8.0.13.

- Error number: 50; Symbol: `EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION`;  
Message: Skipping '%s' directive as maximum include recursion level was reached in file %s at line %d.

`EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION` was added in 8.0.13.

- Error number: 51; Symbol: `EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE`;  
Message: Wrong group definition in config file %s at line %d.

`EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE` was added in 8.0.13.

- Error number: 52; Symbol: `EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE`;  
Message: Found option without preceding group in config file %s at line %d.

`EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE` was added in 8.0.13.

- Error number: 53; Symbol: `EE_CONFIG_FILE_PERMISSION_ERROR`;  
Message: %s should be readable/writable only by current user.

`EE_CONFIG_FILE_PERMISSION_ERROR` was added in 8.0.13.

- Error number: 54; Symbol: `EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE`;  
Message: World-writable config file '%s' is ignored.

`EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE` was added in 8.0.13.

- Error number: 55; Symbol: `EE_USING_DISABLED_OPTION`;  
Message: %s: Option '%s' was used, but is disabled.

`EE_USING_DISABLED_OPTION` was added in 8.0.13.

- Error number: 56; Symbol: `EE_USING_DISABLED_SHORT_OPTION`;  
Message: %s: Option '-%c' was used, but is disabled.

`EE_USING_DISABLED_SHORT_OPTION` was added in 8.0.13.

- Error number: 57; Symbol: `EE_USING_PASSWORD_ON_CLI_IS_INSECURE`;  
Message: Using a password on the command line interface can be insecure.

`EE_USING_PASSWORD_ON_CLI_IS_INSECURE` was added in 8.0.13.

- Error number: 58; Symbol: `EE_UNKNOWN_SUFFIX_FOR_VARIABLE`;  
Message: Unknown suffix '%c' used for variable '%s' (value '%s').

`EE_UNKNOWN_SUFFIX_FOR_VARIABLE` was added in 8.0.13.

- Error number: 59; Symbol: `EE_SSL_ERROR_FROM_FILE`;  
Message: SSL error: %s from '%s'.

---

`EE_SSL_ERROR_FROM_FILE` was added in 8.0.13.

- Error number: 60; Symbol: `EE_SSL_ERROR`;

Message: SSL error: %s.

`EE_SSL_ERROR` was added in 8.0.13.

- Error number: 61; Symbol: `EE_NET_SEND_ERROR_IN_BOOTSTRAP`;

Message: %d %s.

`EE_NET_SEND_ERROR_IN_BOOTSTRAP` was added in 8.0.13.

- Error number: 62; Symbol: `EE_PACKETS_OUT_OF_ORDER`;

Message: Packets out of order (found %u, expected %u).

`EE_PACKETS_OUT_OF_ORDER` was added in 8.0.13.

- Error number: 63; Symbol: `EE_UNKNOWN_PROTOCOL_OPTION`;

Message: Unknown option to protocol: %s.

`EE_UNKNOWN_PROTOCOL_OPTION` was added in 8.0.13.

- Error number: 64; Symbol: `EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY`;

Message: Failed to locate server public key '%s'.

`EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY` was added in 8.0.13.

- Error number: 65; Symbol: `EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT`;

Message: Public key is not in Privacy Enhanced Mail format: '%s'.

`EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT` was added in 8.0.13.

- Error number: 66; Symbol: `EE_DEBUG_INFO`;

Message: %s.

`EE_DEBUG_INFO` was added in 8.0.13.

- Error number: 67; Symbol: `EE_UNKNOWN_VARIABLE`;

Message: unknown variable '%s'.

`EE_UNKNOWN_VARIABLE` was added in 8.0.13.

- Error number: 68; Symbol: `EE_UNKNOWN_OPTION`;

Message: unknown option '--%s'.

`EE_UNKNOWN_OPTION` was added in 8.0.13.

- Error number: 69; Symbol: `EE_UNKNOWN_SHORT_OPTION`;

Message: %s: unknown option '-%c'.

---

`EE_UNKNOWN_SHORT_OPTION` was added in 8.0.13.

- Error number: 70; Symbol: `EE_OPTION_WITHOUT_ARGUMENT`;

Message: %s: option '--%s' cannot take an argument.

`EE_OPTION_WITHOUT_ARGUMENT` was added in 8.0.13.

- Error number: 71; Symbol: `EE_OPTION_REQUIRES_ARGUMENT`;

Message: %s: option '--%s' requires an argument.

`EE_OPTION_REQUIRES_ARGUMENT` was added in 8.0.13.

- Error number: 72; Symbol: `EE_SHORT_OPTION_REQUIRES_ARGUMENT`;

Message: %s: option '-%c' requires an argument.

`EE_SHORT_OPTION_REQUIRES_ARGUMENT` was added in 8.0.13.

- Error number: 73; Symbol: `EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE`;

Message: %s: ignoring option '--%s' due to invalid value '%s'.

`EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE` was added in 8.0.13.

- Error number: 74; Symbol: `EE_OPTION_WITH_EMPTY_VALUE`;

Message: %s: Empty value for '%s' specified.

`EE_OPTION_WITH_EMPTY_VALUE` was added in 8.0.13.

- Error number: 75; Symbol: `EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION`;

Message: %s: Maximum value of '%s' cannot be set.

`EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION` was added in 8.0.13.

- Error number: 76; Symbol: `EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION`;

Message: option '%s': boolean value '%s' was not recognized. Set to OFF.

`EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 77; Symbol: `EE_FAILED_TO_SET_OPTION_VALUE`;

Message: %s: Error while setting value '%s' to '%s'.

`EE_FAILED_TO_SET_OPTION_VALUE` was added in 8.0.13.

- Error number: 78; Symbol: `EE_INCORRECT_INT_VALUE_FOR_OPTION`;

Message: Incorrect integer value: '%s'.

`EE_INCORRECT_INT_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 79; Symbol: `EE_INCORRECT_UINT_VALUE_FOR_OPTION`;

Message: Incorrect unsigned integer value: '%s'.

---

`EE_INCORRECT_UINT_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 80; Symbol: `EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION`;

Message: option '%s': signed value %s adjusted to %s.

`EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 81; Symbol: `EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION`;

Message: option '%s': unsigned value %s adjusted to %s.

`EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 82; Symbol: `EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION`;

Message: option '%s': value %s adjusted to %s.

`EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 83; Symbol: `EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION`;

Message: option '%s': value %g adjusted to %g.

`EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 84; Symbol: `EE_INVALID_DECIMAL_VALUE_FOR_OPTION`;

Message: Invalid decimal value for option '%s'.

`EE_INVALID_DECIMAL_VALUE_FOR_OPTION` was added in 8.0.13.

- Error number: 85; Symbol: `EE_COLLATION_PARSER_ERROR`;

Message: %s.

`EE_COLLATION_PARSER_ERROR` was added in 8.0.13.

- Error number: 86; Symbol: `EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE_CHAR`;

Message: Failed to reset before a primary ignorable character %s.

`EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE_CHAR` was added in 8.0.13.

- Error number: 87; Symbol: `EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE_CHAR`;

Message: Failed to reset before a tertiary ignorable character %s.

`EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE_CHAR` was added in 8.0.13.

- Error number: 88; Symbol: `EE_SHIFT_CHAR_OUT_OF_RANGE`;

Message: Shift character out of range: %s.

`EE_SHIFT_CHAR_OUT_OF_RANGE` was added in 8.0.13.

- Error number: 89; Symbol: `EE_RESET_CHAR_OUT_OF_RANGE`;

Message: Reset character out of range: %s.



---

`EE_RESET_CHAR_OUT_OF_RANGE` was added in 8.0.13.

- Error number: 90; Symbol: `EE_UNKNOWN_LDML_TAG`;

Message: Unknown LDML tag: '%.\*s'.

`EE_UNKNOWN_LDML_TAG` was added in 8.0.13.

- Error number: 91; Symbol: `EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE_CHAR`;

Message: Failed to reset before a secondary ignorable character %s.

`EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE_CHAR` was added in 8.0.16.

- Error number: 92; Symbol: `EE_FAILED_PROCESSING_DIRECTIVE`;

Message: Stopped processing the '%s' directive in file %s at line %d.

`EE_FAILED_PROCESSING_DIRECTIVE` was added in 8.0.27.

- Error number: 93; Symbol: `EE_PTHREAD_KILL_FAILED`;

Message: pthread\_kill(thread\_id:%lu, signal:%s) returned '%s'.

`EE_PTHREAD_KILL_FAILED` was added in 8.0.31.



---

# Index

## C

- CR\_ALREADY\_CONNECTED error code, 647
- CR\_AUTH\_PLUGIN\_CANNOT\_LOAD error code, 648
- CR\_AUTH\_PLUGIN\_ERR error code, 648
- CR\_CANT\_GET\_SESSION\_DATA error code, 649
- CR\_CANT\_READ\_CHARSET error code, 644
- CR\_COMMANDS\_OUT\_OF\_SYNC error code, 644
- CR\_COMPRESSION\_NOT\_SUPPORTED error code, 648
- CR\_COMPRESSION\_WRONGLY\_CONFIGURED error code, 648
- CR\_CONNECTION\_ERROR error code, 643
- CR\_CONN\_HOST\_ERROR error code, 643
- CR\_CONN\_UNKNOW\_PROTOCOL error code, 647
- CR\_DATA\_TRUNCATED error code, 646
- CR\_DEPRECATED\_COMPRESSION\_NOT\_SUPPORTED error code, 648
- CR\_DNS\_SRV\_LOOKUP\_FAILED error code, 649
- CR\_DUPLICATE\_CONNECTION\_ATTR error code, 648
- CR\_EMBEDDED\_CONNECTION error code, 644
- CR\_FETCH\_CANCELED error code, 647
- CR\_FILE\_NAME\_TOO\_LONG error code, 648
- CR\_INSECURE\_API\_ERR error code, 648
- CR\_INVALID\_BUFFER\_USE error code, 646
- CR\_INVALID\_CLIENT\_CHARSET error code, 649
- CR\_INVALID\_CONN\_HANDLE error code, 647
- CR\_INVALID\_FACTOR\_NO error code, 649
- CR\_INVALID\_PARAMETER\_NO error code, 646
- CR\_IPSOCK\_ERROR error code, 643
- CR\_KERBEROS\_USER\_NOT\_FOUND error code, 648
- CR\_LOAD\_DATA\_LOCAL\_INFILE\_REALPATH\_FAIL error code, 649
- CR\_LOAD\_DATA\_LOCAL\_INFILE\_REJECTED error code, 649
- CR\_LOCALHOST\_CONNECTION error code, 644
- CR\_MALFORMED\_PACKET error code, 645
- CR\_MANDATORY\_TRACKER\_NOT\_FOUND error code, 649
- CR\_NAMEDPIPEOPEN\_ERROR error code, 644
- CR\_NAMEDPIPESETSTATE\_ERROR error code, 644
- CR\_NAMEDPIPEWAIT\_ERROR error code, 644
- CR\_NAMEDPIPE\_CONNECTION error code, 644
- CR\_NET\_PACKET\_TOO\_LARGE error code, 644
- CR\_NEW\_STMT\_METADATA error code, 647
- CR\_NOT\_IMPLEMENTED error code, 647
- CR\_NO\_DATA error code, 647
- CR\_NO\_PARAMETERS\_EXISTS error code, 646
- CR\_NO\_PREPARE\_STMT error code, 645
- CR\_NO\_RESULT\_SET error code, 647
- CR\_NO\_STMT\_METADATA error code, 647
- CR\_NULL\_POINTER error code, 645
- CR\_OUT\_OF\_MEMORY error code, 643
- CR\_PARAMS\_NOT\_BOUND error code, 646
- CR\_PROBE\_MASTER\_CONNECT error code, 645
- CR\_PROBE\_REPLICA\_CONNECT error code, 645
- CR\_PROBE\_REPLICA\_HOSTS error code, 645
- CR\_PROBE\_REPLICA\_STATUS error code, 645
- CR\_PROBE\_SLAVE\_CONNECT error code, 645
- CR\_PROBE\_SLAVE\_HOSTS error code, 645
- CR\_PROBE\_SLAVE\_STATUS error code, 644
- CR\_PROBE\_SOURCE\_CONNECT error code, 645
- CR\_SERVER\_GONE\_ERROR error code, 643
- CR\_SERVER\_HANDSHAKE\_ERR error code, 644
- CR\_SERVER\_LOST error code, 644
- CR\_SERVER\_LOST\_EXTENDED error code, 647
- CR\_SHARED\_MEMORY\_CONNECTION error code, 646
- CR\_SHARED\_MEMORY\_CONNECT\_ABANDONED\_ERROR error code, 647
- CR\_SHARED\_MEMORY\_CONNECT\_ANSWER\_ERROR error code, 646
- CR\_SHARED\_MEMORY\_CONNECT\_FILE\_MAP\_ERROR error code, 646
- CR\_SHARED\_MEMORY\_CONNECT\_MAP\_ERROR error code, 646
- CR\_SHARED\_MEMORY\_CONNECT\_REQUEST\_ERROR error code, 646
- CR\_SHARED\_MEMORY\_CONNECT\_SET\_ERROR error code, 647
- CR\_SHARED\_MEMORY\_EVENT\_ERROR error code, 647
- CR\_SHARED\_MEMORY\_FILE\_MAP\_ERROR error code, 646
- CR\_SHARED\_MEMORY\_MAP\_ERROR error code, 646
- CR\_SOCKET\_CREATE\_ERROR error code, 643
- CR\_SSL\_CONNECTION\_ERROR error code, 645
- CR\_SSL\_FIPS\_MODE\_ERR error code, 648
- CR\_STMT\_CLOSED error code, 647
- CR\_TCP\_CONNECTION error code, 644
- CR\_UNKNOWN\_ERROR error code, 643
- CR\_UNKNOWN\_HOST error code, 643
- CR\_UNSUPPORTED\_PARAM\_TYPE error code, 646
- CR\_UNUSED\_1 error code, 647
- CR\_VERSION\_ERROR error code, 643
- CR\_WRONG\_HOST\_INFO error code, 643
- CR\_WRONG\_LICENSE error code, 645

## E

- EE\_ADJUSTED\_DOUBLE\_VALUE\_FOR\_OPTION error code, 658
- EE\_ADJUSTED\_SIGNED\_VALUE\_FOR\_OPTION error code, 658
- EE\_ADJUSTED\_ULONGLONG\_VALUE\_FOR\_OPTION error code, 658

---

EE\_ADJUSTED\_UNSIGNED\_VALUE\_FOR\_OPTION error code, 658  
 EE\_BADCLOSE error code, 651  
 EE\_CANTCREATEFILE error code, 651  
 EE\_CANTLOCK error code, 651  
 EE\_CANTUNLOCK error code, 651  
 EE\_CANT\_CHSIZE error code, 652  
 EE\_CANT\_MKDIR error code, 652  
 EE\_CANT\_OPEN\_STREAM error code, 652  
 EE\_CANT\_READLINK error code, 652  
 EE\_CANT\_SEEK error code, 653  
 EE\_CANT\_SYMLINK error code, 652  
 EE\_CAPACITY\_EXCEEDED error code, 653  
 EE\_CHANGE\_OWNERSHIP error code, 653  
 EE\_CHANGE\_PERMISSIONS error code, 653  
 EE\_COLLATION\_PARSER\_ERROR error code, 658  
 EE\_CONFIG\_FILE\_PERMISSION\_ERROR error code, 655  
 EE\_DEBUG\_INFO error code, 656  
 EE\_DELETE error code, 651  
 EE\_DIR error code, 652  
 EE\_DISK\_FULL error code, 652  
 EE\_DISK\_FULL\_WITH\_RETRY\_MSG error code, 653  
 EE\_EOFERR error code, 651  
 EE\_EXITING\_TIMER\_NOTIFY\_THREAD error code, 654  
 EE\_FAILED\_PROCESSING\_DIRECTIVE error code, 659  
 EE\_FAILED\_TO\_ASSIGN\_MAX\_VALUE\_TO\_OPTION error code, 657  
 EE\_FAILED\_TO\_CREATE\_IO\_COMPLETION\_PORT error code, 654  
 EE\_FAILED\_TO\_CREATE\_TIMER error code, 653  
 EE\_FAILED\_TO\_CREATE\_TIMER\_NOTIFY\_THREAD\_INTERRUPTIBLE error code, 654  
 EE\_FAILED\_TO\_CREATE\_TIMER\_QUEUE error code, 653  
 EE\_FAILED\_TO\_DELETE\_TIMER error code, 653  
 EE\_FAILED\_TO\_DETERMINE\_LARGE\_PAGE\_SIZE error code, 654  
 EE\_FAILED\_TO\_HANDLE\_DEFAULTS\_FILE error code, 654  
 EE\_FAILED\_TO\_KILL\_ALL\_THREADS error code, 654  
 EE\_FAILED\_TO\_LOCATE\_SERVER\_PUBLIC\_KEY error code, 656  
 EE\_FAILED\_TO\_OPEN\_DEFAULTS\_FILE error code, 654  
 EE\_FAILED\_TO\_RESET\_BEFORE\_PRIMARY\_IGNOREABLE\_ERROR error code, 658  
 EE\_FAILED\_TO\_RESET\_BEFORE\_SECONDARY\_IGNOREABLE\_ERROR error code, 659  
 EE\_FAILED\_TO\_RESET\_BEFORE\_TERTIARY\_IGNOREABLE\_ERROR error code, 658  
 EE\_FAILED\_TO\_SET\_OPTION\_VALUE error code, 657  
 EE\_FAILED\_TO\_START\_TIMER\_NOTIFY\_THREAD error code, 654  
 EE\_FILENOTFOUND error code, 653  
 EE\_FILE\_NOT\_CLOSED error code, 653  
 EE\_GETWD error code, 652  
 EE\_IGNORE\_WORLD\_WRITABLE\_CONFIG\_FILE error code, 655  
 EE\_INCORRECT\_BOOLEAN\_VALUE\_FOR\_OPTION error code, 657  
 EE\_INCORRECT\_GRP\_DEFINITION\_IN\_CONFIG\_FILE error code, 655  
 EE\_INCORRECT\_INT\_VALUE\_FOR\_OPTION error code, 657  
 EE\_INCORRECT\_UINT\_VALUE\_FOR\_OPTION error code, 658  
 EE\_INVALID\_DECIMAL\_VALUE\_FOR\_OPTION error code, 658  
 EE\_LINK error code, 651  
 EE\_LINK\_WARNING error code, 652  
 EE\_NET\_SEND\_ERROR\_IN\_BOOTSTRAP error code, 656  
 EE\_OPEN\_WARNING error code, 652  
 EE\_OPTION\_IGNORED\_DUE\_TO\_INVALID\_VALUE error code, 657  
 EE\_OPTION\_REQUIRES\_ARGUMENT error code, 657  
 EE\_OPTION\_WITHOUT\_ARGUMENT error code, 657  
 EE\_OPTION\_WITHOUT\_GRP\_IN\_CONFIG\_FILE error code, 655  
 EE\_OPTION\_WITH\_EMPTY\_VALUE error code, 657  
 EE\_OUTOFMEMORY error code, 651  
 EE\_OUT\_OF\_FILERESOURCES error code, 652  
 EE\_PACKETS\_OUT\_OF\_ORDER error code, 656  
 EE\_PTHREAD\_KILL\_FAILED error code, 659  
 EE\_PUBLIC\_KEY\_NOT\_IN\_PEM\_FORMAT error code, 656  
 EE\_READ error code, 651  
 EE\_REALPATH error code, 652  
 EE\_RESET\_CHAR\_OUT\_OF\_RANGE error code, 659  
 EE\_SETWD error code, 652  
 EE\_SHIFT\_CHAR\_OUT\_OF\_RANGE error code, 658  
 EE\_SHORT\_OPTION\_REQUIRES\_ARGUMENT error code, 657  
 EE\_SKIPPING\_DIRECTIVE\_DUE\_TO\_MAX\_INCLUDE\_RECURSION error code, 655  
 EE\_SSL\_ERROR error code, 656  
 EE\_SSL\_ERROR\_FROM\_FILE error code, 656  
 EE\_STAT error code, 652  
 EE\_SYMLINK error code, 653  
 EE\_UNKNOWN\_CHARSET error code, 652  
 EE\_UNKNOWN\_COLLATION error code, 653  
 EE\_UNKNOWN\_LDML\_TAG error code, 659  
 EE\_UNKNOWN\_OPTION error code, 656  
 EE\_UNKNOWN\_PROTOCOL\_OPTION error code, 656  
 EE\_UNKNOWN\_SHORT\_OPTION error code, 657

---

EE\_UNKNOWN\_SUFFIX\_FOR\_VARIABLE error code, 655  
 EE\_UNKNOWN\_VARIABLE error code, 656  
 EE\_USING\_DISABLED\_OPTION error code, 655  
 EE\_USING\_DISABLED\_SHORT\_OPTION error code, 655  
 EE\_USING\_PASSWORD\_ON\_CLI\_IS\_INSECURE error code, 655  
 EE\_WIN\_LIBRARY\_LOAD\_FAILED error code, 654  
 EE\_WIN\_RUN\_TIME\_ERROR\_CHECK error code, 654  
 EE\_WRITE error code, 651  
 EE\_WRONG\_DIRECTIVE\_IN\_CONFIG\_FILE error code, 655  
 error code  
     CR\_ALREADY\_CONNECTED, 647  
     CR\_AUTH\_PLUGIN\_CANNOT\_LOAD, 648  
     CR\_AUTH\_PLUGIN\_ERR, 648  
     CR\_CANT\_GET\_SESSION\_DATA, 649  
     CR\_CANT\_READ\_CHARSET, 644  
     CR\_COMMANDS\_OUT\_OF\_SYNC, 644  
     CR\_COMPRESSION\_NOT\_SUPPORTED, 648  
     CR\_COMPRESSION\_WRONGLY\_CONFIGURED, 648  
     CR\_CONNECTION\_ERROR, 643  
     CR\_CONN\_HOST\_ERROR, 643  
     CR\_CONN\_UNKNOW\_PROTOCOL, 647  
     CR\_DATA\_TRUNCATED, 646  
     CR\_DEPRECATED\_COMPRESSION\_NOT\_SUPPORTED, 648  
     CR\_DNS\_SRV\_LOOKUP\_FAILED, 649  
     CR\_DUPLICATE\_CONNECTION\_ATTR, 648  
     CR\_EMBEDDED\_CONNECTION, 644  
     CR\_FETCH\_CANCELED, 647  
     CR\_FILE\_NAME\_TOO\_LONG, 648  
     CR\_INSECURE\_API\_ERR, 648  
     CR\_INVALID\_BUFFER\_USE, 646  
     CR\_INVALID\_CLIENT\_CHARSET, 649  
     CR\_INVALID\_CONN\_HANDLE, 647  
     CR\_INVALID\_FACTOR\_NO, 649  
     CR\_INVALID\_PARAMETER\_NO, 646  
     CR\_IPSOCK\_ERROR, 643  
     CR\_KERBEROS\_USER\_NOT\_FOUND, 648  
     CR\_LOAD\_DATA\_LOCAL\_INFILE\_REALPATH\_FAIL, 649  
     CR\_LOAD\_DATA\_LOCAL\_INFILE\_REJECTED, 649  
     CR\_LOCALHOST\_CONNECTION, 644  
     CR\_MALFORMED\_PACKET, 645  
     CR\_MANDATORY\_TRACKER\_NOT\_FOUND, 649  
     CR\_NAMEDPIPEOPEN\_ERROR, 644  
     CR\_NAMEDPIPESETSTATE\_ERROR, 644  
     CR\_NAMEDPIPEWAIT\_ERROR, 644  
     CR\_NAMEDPIPE\_CONNECTION, 644  
     CR\_NET\_PACKET\_TOO\_LARGE, 644  
     CR\_NEW\_STMT\_METADATA, 647  
     CR\_NOT\_IMPLEMENTED, 647  
     CR\_NO\_DATA, 647  
     CR\_NO\_PARAMETERS\_EXISTS, 646  
     CR\_NO\_PREPARE\_STMT, 645  
     CR\_NO\_RESULT\_SET, 647  
     CR\_NO\_STMT\_METADATA, 647  
     CR\_NULL\_POINTER, 645  
     CR\_OUT\_OF\_MEMORY, 643  
     CR\_PARAMS\_NOT\_BOUND, 646  
     CR\_PROBE\_MASTER\_CONNECT, 645  
     CR\_PROBE\_REPLICA\_CONNECT, 645  
     CR\_PROBE\_REPLICA\_HOSTS, 645  
     CR\_PROBE\_REPLICA\_STATUS, 645  
     CR\_PROBE\_SLAVE\_CONNECT, 645  
     CR\_PROBE\_SLAVE\_HOSTS, 645  
     CR\_PROBE\_SLAVE\_STATUS, 644  
     CR\_PROBE\_SOURCE\_CONNECT, 645  
     CR\_SERVER\_GONE\_ERROR, 643  
     CR\_SERVER\_HANDSHAKE\_ERR, 644  
     CR\_SERVER\_LOST, 644  
     CR\_SERVER\_LOST\_EXTENDED, 647  
     CR\_SHARED\_MEMORY\_CONNECTION, 646  
     CR\_SHARED\_MEMORY\_CONNECT\_ABANDONED\_ERROR, 647  
     CR\_SHARED\_MEMORY\_CONNECT\_ANSWER\_ERROR, 646  
     CR\_SHARED\_MEMORY\_CONNECT\_FILE\_MAP\_ERROR, 646  
     CR\_SHARED\_MEMORY\_CONNECT\_MAP\_ERROR, 646  
     CR\_SHARED\_MEMORY\_CONNECT\_REQUEST\_ERROR, 646  
     CR\_SHARED\_MEMORY\_CONNECT\_SET\_ERROR, 647  
     CR\_SHARED\_MEMORY\_EVENT\_ERROR, 647  
     CR\_SHARED\_MEMORY\_FILE\_MAP\_ERROR, 646  
     CR\_SHARED\_MEMORY\_MAP\_ERROR, 646  
     CR\_SOCKET\_CREATE\_ERROR, 643  
     CR\_SSL\_CONNECTION\_ERROR, 645  
     CR\_SSL\_FIPS\_MODE\_ERR, 648  
     CR\_STMT\_CLOSED, 647  
     CR\_TCP\_CONNECTION, 644  
     CR\_UNKNOWN\_ERROR, 643  
     CR\_UNKNOWN\_HOST, 643  
     CR\_UNSUPPORTED\_PARAM\_TYPE, 646  
     CR\_UNUSED\_1, 647  
     CR\_VERSION\_ERROR, 643  
     CR\_WRONG\_HOST\_INFO, 643  
     CR\_WRONG\_LICENSE, 645  
     EE\_ADJUSTED\_DOUBLE\_VALUE\_FOR\_OPTION, 658  
     EE\_ADJUSTED\_SIGNED\_VALUE\_FOR\_OPTION, 658

---

---

EE\_ADJUSTED\_ULONGLONG\_VALUE\_FOR\_OPTION, 658  
 EE\_ADJUSTED\_UNSIGNED\_VALUE\_FOR\_OPTION, 658  
 EE\_BADCLOSE, 651  
 EE\_CANTCREATEFILE, 651  
 EE\_CANTLOCK, 651  
 EE\_CANTUNLOCK, 651  
 EE\_CANT\_CHSIZE, 652  
 EE\_CANT\_MKDIR, 652  
 EE\_CANT\_OPEN\_STREAM, 652  
 EE\_CANT\_READLINK, 652  
 EE\_CANT\_SEEK, 653  
 EE\_CANT\_SYMLINK, 652  
 EE\_CAPACITY\_EXCEEDED, 653  
 EE\_CHANGE\_OWNERSHIP, 653  
 EE\_CHANGE\_PERMISSIONS, 653  
 EE\_COLLATION\_PARSER\_ERROR, 658  
 EE\_CONFIG\_FILE\_PERMISSION\_ERROR, 655  
 EE\_DEBUG\_INFO, 656  
 EE\_DELETE, 651  
 EE\_DIR, 652  
 EE\_DISK\_FULL, 652  
 EE\_DISK\_FULL\_WITH\_RETRY\_MSG, 653  
 EE\_EOFERR, 651  
 EE\_EXITING\_TIMER\_NOTIFY\_THREAD, 654  
 EE\_FAILED\_PROCESSING\_DIRECTIVE, 659  
 EE\_FAILED\_TO\_ASSIGN\_MAX\_VALUE\_TO\_OPTION, 657  
 EE\_FAILED\_TO\_CREATE\_IO\_COMPLETION\_PORT, 654  
 EE\_FAILED\_TO\_CREATE\_TIMER, 653  
 EE\_FAILED\_TO\_CREATE\_TIMER\_NOTIFY\_THREAD\_INTERRUPTIBLE, 654  
 EE\_FAILED\_TO\_CREATE\_TIMER\_QUEUE, 653  
 EE\_FAILED\_TO\_DELETE\_TIMER, 653  
 EE\_FAILED\_TO\_DETERMINE\_LARGE\_PAGE\_SIZE, 654  
 EE\_FAILED\_TO\_HANDLE\_DEFAULTS\_FILE, 654  
 EE\_FAILED\_TO\_KILL\_ALL\_THREADS, 654  
 EE\_FAILED\_TO\_LOCATE\_SERVER\_PUBLIC\_KEY, 656  
 EE\_FAILED\_TO\_OPEN\_DEFAULTS\_FILE, 654  
 EE\_FAILED\_TO\_RESET\_BEFORE\_PRIMARY\_IGNOREABLE\_ERROR, 658  
 EE\_FAILED\_TO\_RESET\_BEFORE\_SECONDARY\_IGNOREABLE\_ERROR, 659  
 EE\_FAILED\_TO\_RESET\_BEFORE\_TERTIARY\_IGNOREABLE\_ERROR, 658  
 EE\_FAILED\_TO\_SET\_OPTION\_VALUE, 657  
 EE\_FAILED\_TO\_START\_TIMER\_NOTIFY\_THREAD, 654  
 EE\_FILENOTFOUND, 653  
 EE\_FILE\_NOT\_CLOSED, 653  
 EE\_GETWD, 652  
 EE\_IGNORE\_WORLD\_WRITABLE\_CONFIG\_FILE, 655  
 EE\_INCORRECT\_BOOLEAN\_VALUE\_FOR\_OPTION, 657  
 EE\_INCORRECT\_GRP\_DEFINITION\_IN\_CONFIG\_FILE, 655  
 EE\_INCORRECT\_INT\_VALUE\_FOR\_OPTION, 657  
 EE\_INCORRECT\_UINT\_VALUE\_FOR\_OPTION, 658  
 EE\_INVALID\_DECIMAL\_VALUE\_FOR\_OPTION, 658  
 EE\_LINK, 651  
 EE\_LINK\_WARNING, 652  
 EE\_NET\_SEND\_ERROR\_IN\_BOOTSTRAP, 656  
 EE\_OPEN\_WARNING, 652  
 EE\_OPTION\_IGNORED\_DUE\_TO\_INVALID\_VALUE, 657  
 EE\_OPTION\_REQUIRES\_ARGUMENT, 657  
 EE\_OPTION\_WITHOUT\_ARGUMENT, 657  
 EE\_OPTION\_WITHOUT\_GRP\_IN\_CONFIG\_FILE, 655  
 EE\_OPTION\_WITH\_EMPTY\_VALUE, 657  
 EE\_OUTOFMEMORY, 651  
 EE\_OUT\_OF\_FILERESOURCES, 652  
 EE\_PACKETS\_OUT\_OF\_ORDER, 656  
 EE\_PTHREAD\_KILL\_FAILED, 659  
 EE\_PUBLIC\_KEY\_NOT\_IN\_PEM\_FORMAT, 656  
 EE\_READ, 651  
 EE\_REALPATH, 652  
 EE\_RESET\_CHAR\_OUT\_OF\_RANGE, 659  
 EE\_SETWD, 652  
 EE\_SHIFT\_CHAR\_OUT\_OF\_RANGE, 658  
 EE\_SHORT\_OPTION\_REQUIRES\_ARGUMENT, 657  
 EE\_SKIP\_FILE\_DIRECTIVE\_DUE\_TO\_MAX\_INCLUDE\_RECURSION, 655  
 EE\_SSL\_ERROR, 656  
 EE\_SSL\_ERROR\_FROM\_FILE, 656  
 EE\_STAT, 652  
 EE\_SYNC, 653  
 EE\_UNKNOWN\_CHARSET, 652  
 EE\_UNKNOWN\_COLLATION, 653  
 EE\_UNKNOWN\_LDML\_TAG, 659  
 EE\_UNKNOWN\_OPTION, 656  
 EE\_UNKNOWN\_PROTOCOL\_OPTION, 656  
 EE\_UNKNOWN\_SHORT\_OPTION, 657  
 EE\_UNKNOWN\_SUFFIX\_FOR\_VARIABLE, 655  
 EE\_UNKNOWN\_VARIABLE, 656  
 EE\_USING\_DISABLED\_OPTION, 655  
 EE\_USING\_DISABLED\_SHORT\_OPTION, 655  
 EE\_USING\_PASSWORD\_ON\_CLI\_IS\_INSECURE, 655  
 EE\_WIN\_LIBRARY\_LOAD\_FAILED, 654  
 EE\_WIN\_RUN\_TIME\_ERROR\_CHECK, 654  
 EE\_WRITE, 651  
 EE\_WRONG\_DIRECTIVE\_IN\_CONFIG\_FILE, 655

---

ER_ABORTING, 175	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK,
ER_ABORTING_CONNECTION, 14	64
ER_ABORTING_USER_CONNECTION, 278	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FTS,
ER_ACCESS_DENIED_CHANGE_USER_ERROR,	64
66	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_GIS,
ER_ACCESS_DENIED_ERROR, 6	74
ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD,	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_HID,
279	64
ER_ACCESS_DENIED_ERROR_WITH_PASSWORD,	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NO,
279	64
ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED,	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NO,
575	65
ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED,	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_PA,
279	64
ER_ACCESS_DENIED_NO_PASSWORD_ERROR,	ER_AMBIGUOUS_FIELD_TERM, 36
50	ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDAT,
ER_ACCOUNT_HAS_BEEN_LOCKED, 80	284
ER_ACCOUNT_WITH_EXPIRED_PASSWORD, 614	ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NA,
ER_ACL_OPERATION_FAILED, 87	145
ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG,	ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHAN,
565	147
ER_ADDRESSES_FOR_HOSTNAME_HEADER, 168	ER_APPLIER_LOG_EVENT_VALIDATION_ERROR,
ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM,	100
168	ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_R,
ER_ADD_PARTITION_NO_NEW_PARTITION, 38	144
ER_ADD_PARTITION_SUBPART_ERROR, 38	ER_ATTRIBUTE_IGNORED, 103
ER_ADMIN_WRONG_MRG_TABLE, 36	ER_AUDIT_API_ABORT, 84
ER_AES_INVALID_IV, 67	ER_AUDIT_CANT_ABORT_COMMAND, 275
ER_AES_INVALID_KDF_ITERATIONS, 87	ER_AUDIT_CANT_ABORT_EVENT, 275
ER_AES_INVALID_KDF_NAME, 87	ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD,
ER_AES_INVALID_KDF_OPTION_SIZE, 87	571
ER_AGGREGATE_IN_ORDER_NOT_SELECT, 74	ER_AUDIT_LOG_CANNOT_READ_PASSWORD,
ER_AGGREGATE_ORDER_FOR_UNION, 71	564
ER_AGGREGATE_ORDER_NON_AGG_QUERY, 71	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD,
ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPOR	64,
134	ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTH,
ER_ALTER_FILEGROUP_FAILED, 39	314
ER_ALTER_INFO, 9	ER_AUDIT_LOG_CANNOT_STORE_PASSWORD,
ER_ALTER_OPERATION_NOT_SUPPORTED, 64	564
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY,
64	534
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_AU	ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING,
64	564
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_C	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILE,
64	315
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_C	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRES,
64	315
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_C	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPT,
153	315
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_C	ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE,
64	534
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_C	ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BE,
64	534
	ER_AUDIT_LOG_FILE_AUTO_PRUNED, 596

---

ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PROCESSED, 564	ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE, 315
ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT, 564	ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE, 315
ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING, 564	ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR, 316
ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING_OR_INVALID, 564	ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY, 535
ER_AUDIT_LOG_FILE_PRUNE_FAILED, 596	ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID, 568
ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE, 317	ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED, 316
ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE, 316	ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED, 314
ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ, 316	ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED, 565
ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE, 316	ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH, 315
ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE, 317	ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED, 568
ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FILTERS, 316	ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST, 314
ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE, 316	ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED, 536
ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY, 317	ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE, 534
ER_AUDIT_LOG_FILTER_INVALID_COLUMN_COUNT, 316	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT, 569
ER_AUDIT_LOG_FILTER_INVALID_COLUMN_DEFINITION, 316	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE, 568
ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED, 313	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH, 569
ER_AUDIT_LOG_FILTER_RESULT_MSG, 315	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH, 87
ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY, 317	ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHA, 535
ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED, 569	ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER, 534
ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER, 534	ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS, 314
ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR, 314	ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE, 315
ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE, 131	ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED, 314
ER_AUDIT_LOG_INVALID_FILE_CONTENT, 564	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED, 314
ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE, 639	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE_FILTER, 314
ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED, 533	ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EVENTS, 200
ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST, 535	ER_AUDIT_PLUGIN_HAS_INVALID_DATA, 200
ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY, 534	ER_AUDIT_WARNING, 275
ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR, 533	ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM, 197
ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL, 315	



---

ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE TABLES,	ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS_IN_
197	637
ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_ENTRY,	ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED,
196	609
ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME,	ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR,
196	609
ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE,	ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH,
196	636
ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME,	ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED,
585	636
ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION,	ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT,
585	608
ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED,	ER_AUTHENTICATION_PLUGIN_LOG,
196	609
ER_AUTHCACHE_PLUGIN_CONFIG,	ER_AUTHENTICATION_PLUGIN_OOM,
195	608
ER_AUTHCACHE_PLUGIN_MISSING,	ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED,
195	608
ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROUTINE_TYPE,	ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT,
197	608
ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE,	ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT,
197	608
ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOLVE,	ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED,
195	608
ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME,	ER_AUTHENTICATION_POLICY_MISMATCH,
585	149
ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION,	ER_AUTH_CANT_ACTIVATE_ROLE,
585	193
ER_AUTHCACHE_ROLE_TABLES_DODGY,	ER_AUTH_CANT_CREATE_RSA_PAIR,
195	193
ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE,	ER_AUTH_CANT_SET_DEFAULT_PLUGIN,
197	181
ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING,	ER_AUTH_CANT_WRITE_PRIVKEY,
196	194
ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD,	ER_AUTH_CANT_WRITE_PUBKEY,
195	194
ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD,	ER_AUTH_CERTS_SAVED_TO_DATADIR,
196	194
ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN,	ER_AUTH_CERT_GENERATION_DISABLED,
195	194
ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE,	ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY,
195	557
ER_AUTHCACHE_USER_TABLE_DODGY,	ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG,
195	603
ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY,	ER_AUTH_KEYS_SAVED_TO_DATADIR,
636	194
ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY,	ER_AUTH_KEY_GENERATION_DISABLED,
609	195
ER_AUTHENTICATION_OCI_IAM,	ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT,
610	194
ER_AUTHENTICATION_OCI_IMDS,	ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG,
609	320
ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_STRING,	ER_AUTH_RSA_CANT_FIND,
610	192
ER_AUTHENTICATION_OCI_INVALID_TOKEN,	ER_AUTH_RSA_CANT_PARSE,
636	192
ER_AUTHENTICATION_OCI_NONCE,	ER_AUTH_RSA_CANT_READ,
610	192
ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND,	ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION,
610	194
ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS,	ER_AUTH_RSA_FILES_NOT_FOUND,
610	192
	ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION,
	194
	ER_AUTH_USING_EXISTING_CERTS,
	194
	ER_AUTOINC_READ_FAILED,
	35
	ER_AUTO_CONVERT,
	21
	ER_AUTO_INCREMENT_CONFLICT,
	66
	ER_AUTO_OPTIONS_FAILED,
	181

---

---

ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFFER	ER_BINLOG_CANT_OPEN_TMP_INDEX, 268
57	ER_BINLOG_CANT_RESIZE_CACHE, 265
ER_BACK_IN_TIME, 174	ER_BINLOG_CANT_SET_TMP_INDEX_NAME, 268
ER_BAD_DB_ERROR, 6	ER_BINLOG_CANT_TRIM_CRASHED_BINLOG, 271
ER_BAD_FIELD_ERROR, 7	ER_BINLOG_CANT_USE_FOR_LOGGING, 267
ER_BAD_FT_COLUMN, 24	ER_BINLOG_CRASHED_BINLOG_TRIMMED, 271
ER_BAD_HOST_ERROR, 6	ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED,
ER_BAD_LOG_STATEMENT, 42	622
ER_BAD_NULL_ERROR, 6	ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS,
ER_BAD_NULL_ERROR_NOT_IGNORED, 104	622
ER_BAD_REPLICA, 17	ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED_SE,
ER_BAD_REPLICA_AUTO_POSITION, 57	622
ER_BAD_REPLICA_UNTIL_COND, 23	ER_BINLOG_CRASH_RECOVERY_FAILED, 271
ER_BAD_SLAVE, 17	ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG,
ER_BAD_SLAVE_AUTO_POSITION, 57	622
ER_BAD_SLAVE_UNTIL_COND, 23	ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED,
ER_BAD_TABLE_ERROR, 6	623
ER_BAD_TIMESTAMP_FORMAT, 157	ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED,
ER_BASE64_DECODE_ERROR, 42	622
ER_BASEDIR_SET_TO, 281	ER_BINLOG_CREATE_ROUTINE_NEED_SUPER,
ER_BEFORE_DML_VALIDATION_ERROR, 78	32
ER_BEG_INITFILE, 176	ER_BINLOG_END, 175
ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD,	ER_BINLOG_ERROR_GETTING_NEXT_LOG_FROM_INDEX,
640	268
ER_BEYOND_SERVER_UPGRADE_THRESHOLD,	ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG,
640	266
ER_BINLOG_ATTACHING_THREAD_MEMORY_FINAL	ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG,
264	266
ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX,	ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA,
54	266
ER_BINLOG_CACHE_SIZE_TOO_LARGE, 276	ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO,
ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX,	266
267	ER_BINLOG_EVENTS_READ_FROM_RELAY_LOG_INFO,
ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASH	ER_BINLOG,
271	ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED,
ER_BINLOG_CANT_CLOSE_TMP_INDEX, 268	283
ER_BINLOG_CANT_COPY_INDEX_TO_TMP, 268	ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOGETH
ER_BINLOG_CANT_CREATE_CACHE_FOR_LOG,	298
265	ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED_TOGETH
ER_BINLOG_CANT_DELETE_FILE, 268	105
ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG	ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUIL
270	INDEX,
ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX	ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUIL
270	LOG,
ER_BINLOG_CANT_FIND_LOG_IN_INDEX, 270	267
ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME,	ER_BINLOG_FAILED_TO_DELETE_LOG_FILE, 270
266	ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUIL
ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY	LOG,
267	ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE,
ER_BINLOG_CANT_MOVE_TMP_TO_INDEX, 268	269
ER_BINLOG_CANT_OPEN_CRASHED_BINLOG,	ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE,
271	268
ER_BINLOG_CANT_OPEN_FOR_LOGGING, 266	ER_BINLOG_FAILED_TO_READ_REGISTER_FILE,
ER_BINLOG_CANT_OPEN_LOG, 265	269

ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE, 269	ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN, 268
ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_FLUSHING, 267	ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER_FILE, 269
ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK, 271	ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE, 269
ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK, 271	ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE, 268
ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME, 269	ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE, 269
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE, 266	ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG, 269
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN, 267	ER_BINLOG_PURGE_PROHIBITED, 30
ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLE, 254	ER_BINLOG_RECOVERING_AFTER_CRASH_USING, 270
ER_BINLOG_FATAL_ERROR, 43	ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE, 47
ER_BINLOG_FILE_BEING_READ_NOT_PURGED, 265	ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE, 48
ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED, 265	ER_BINLOG_ROW_INJECTION_AND_STMT_MODE, 48
ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LONG, 265	ER_BINLOG_ROW_LOGGING_FAILED, 40
ER_BINLOG_FILE_NAME_TOO_LONG, 265	ER_BINLOG_ROW_MODE_AND_STMT_ENGINE, 47
ER_BINLOG_FILE_OPEN_FAILED, 283	ER_BINLOG_ROW_VALUE_OPTION_IGNORED, 526
ER_BINLOG_IO_ERROR_READING_HEADER, 265	ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFFIX, 527
ER_BINLOG_LOGGING_IMPOSSIBLE, 43	ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX, 54
ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS, 270	ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE, 277
ER_BINLOG_LOGGING_INCIDENT_TO_STOP_SLAVES, 270	ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES, 63
ER_BINLOG_LOGGING_NOT_POSSIBLE, 297	ER_BINLOG_STMT_MODE_AND_ROW_ENGINE, 48
ER_BINLOG_LOGICAL_CORRUPTION, 65	ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READONLY, 561
ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG, 298	ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL, 143
ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION, 119	ER_BINLOG_UNSAFE_AUTOINC_COLUMNS, 47
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP, 120	ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST, 53
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP, 120	ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT, 62
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE, 119	CRYPTO_LOG, 52
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT, 120	ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT, 52
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE, 119	ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC, 53
ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING, 48	ENGINE, 563
ER_BINLOG_NEEDS_SERVERID, 179	ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBSTRACTION, 69
ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING, 254	ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN, 69
ER_BINLOG_PURGE_EMFILE, 42	ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT, 52
ER_BINLOG_PURGE_FATAL_ERR, 30	ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE, 52

---

ER\_BINLOG\_UNSAFE\_INSERT\_TWO\_KEYS, 53  
ER\_BINLOG\_UNSAFE\_LIMIT, 48  
ER\_BINLOG\_UNSAFE\_MESSAGE\_AND\_STATEMENT, 277  
ER\_BINLOG\_UNSAFE\_MIXED\_STATEMENT, 50  
ER\_BINLOG\_UNSAFE\_MULTIPLE\_ENGINES\_AND\_SELF\_LOGGING\_ENGINE, 50  
ER\_BINLOG\_UNSAFE\_NONTRANS\_AFTER\_TRANS, 48  
ER\_BINLOG\_UNSAFE\_NOWAIT, 93  
ER\_BINLOG\_UNSAFE\_REPLACE\_SELECT, 52  
ER\_BINLOG\_UNSAFE\_ROUTINE, 32  
ER\_BINLOG\_UNSAFE\_SKIP\_LOCKED, 93  
ER\_BINLOG\_UNSAFE\_STATEMENT, 43  
ER\_BINLOG\_UNSAFE\_SYSTEM\_FUNCTION, 48  
ER\_BINLOG\_UNSAFE\_SYSTEM\_TABLE, 48  
ER\_BINLOG\_UNSAFE\_SYSTEM\_VARIABLE, 48  
ER\_BINLOG\_UNSAFE\_UDF, 48  
ER\_BINLOG\_UNSAFE\_UPDATE\_IGNORE, 52  
ER\_BINLOG\_UNSAFE\_WRITE\_AUTOINC\_SELECT, 53  
ER\_BINLOG\_UNSAFE\_XA, 86  
ER\_BINLOG\_USE\_V1\_ROW\_EVENTS\_IGNORED, 527  
ER\_BINLOG\_WARNING\_SUPPRESSED, 272  
ER\_BLOBS\_AND\_NO\_TERMINATED, 9  
ER\_BLOB\_CANT\_HAVE\_DEFAULT, 10  
ER\_BLOB\_FIELD\_IN\_PART\_FUNC\_ERROR, 37  
ER\_BLOB\_KEY\_WITHOUT\_LENGTH, 15  
ER\_BLOB\_USED\_AS\_KEY, 8  
ER\_BOOST\_GEOMETRY\_CENTROID\_EXCEPTION, 72  
ER\_BOOST\_GEOMETRY\_EMPTY\_INPUT\_EXCEPTION, 72  
ER\_BOOST\_GEOMETRY\_INCONSISTENT\_TURNS\_EXCEPTION, 80  
ER\_BOOST\_GEOMETRY\_OVERLAY\_INVALID\_INPUT\_EXCEPTION, 72  
ER\_BOOST\_GEOMETRY\_SELF\_INTERSECTION\_POINT\_EXCEPTION, 72  
ER\_BOOST\_GEOMETRY\_TURN\_INFO\_EXCEPTION, 72  
ER\_BOOST\_GEOMETRY\_UNKNOWN\_EXCEPTION, 72  
ER\_BOOTSTRAP\_CANT\_THREAD, 162  
ER\_BUFPOOL\_RESIZE\_INPROGRESS, 84  
ER\_BUILD\_ID, 625  
ER\_BULK\_EXECUTOR\_ERROR, 158  
ER\_BULK\_EXECUTOR\_INFO, 629  
ER\_BULK\_LOADER\_COLUMN\_TOO\_BIG\_FOR\_LEFTOVER\_BUFFER, 159  
ER\_BULK\_LOADER\_COMPONENT\_ERROR, 159  
ER\_BULK\_LOADER\_FILE\_CONTAINS\_LESS\_LINES\_THAN\_IGNORED, 159  
ER\_BULK\_LOADER\_FILE\_CONTAINS\_LESS\_LINES\_THAN\_IGNORED\_LOG, 629  
ER\_BULK\_LOAD\_DATA\_FAILED, 159  
ER\_BULK\_PARSER\_COPY\_BUFFER\_SIZE\_EXCEEDED, 160  
ER\_BULK\_PARSER\_COPY\_BUFFER\_SIZE\_EXCEEDED\_LOG, 630  
ER\_BULK\_PARSER\_INCOMPLETE\_ESCAPE\_SEQUENCE, 160  
ER\_BULK\_PARSER\_INCOMPLETE\_ESCAPE\_SEQUENCE\_LOG, 631  
ER\_BULK\_PARSER\_MISSING\_ENCLOSED\_BY, 159  
ER\_BULK\_PARSER\_MISSING\_ENCLOSED\_BY\_LOG, 630  
ER\_BULK\_PARSER\_ROW\_BUFFER\_MAX\_TOTAL\_COLS\_EXCEEDED, 159  
ER\_BULK\_PARSER\_ROW\_BUFFER\_MAX\_TOTAL\_COLS\_EXCEEDED\_LOG, 630  
ER\_BULK\_PARSER\_UNEXPECTED\_CHAR\_AFTER\_COLUMN\_TERMINATOR, 160  
ER\_BULK\_PARSER\_UNEXPECTED\_CHAR\_AFTER\_COLUMN\_TERMINATOR\_LOG, 631  
ER\_BULK\_PARSER\_UNEXPECTED\_CHAR\_AFTER\_ENDING\_ESCAPE\_SEQUENCE, 160  
ER\_BULK\_PARSER\_UNEXPECTED\_CHAR\_AFTER\_ENDING\_ESCAPE\_SEQUENCE\_LOG, 630  
ER\_BULK\_PARSER\_UNEXPECTED\_CHAR\_AFTER\_NULL\_ESCAPE\_SEQUENCE, 160  
ER\_BULK\_PARSER\_UNEXPECTED\_CHAR\_AFTER\_NULL\_ESCAPE\_SEQUENCE\_LOG, 630  
ER\_BULK\_PARSER\_UNEXPECTED\_END\_OF\_INPUT, 160  
ER\_BULK\_PARSER\_UNEXPECTED\_END\_OF\_INPUT\_LOG, 630  
ER\_BULK\_PARSER\_UNEXPECTED\_ROW\_TERMINATOR, 160  
ER\_BULK\_PARSER\_UNEXPECTED\_ROW\_TERMINATOR\_LOG, 630  
ER\_BULK\_READER\_COMMUNICATION\_ERROR, 159  
ER\_BULK\_READER\_COMMUNICATION\_ERROR\_LOG, 630  
ER\_BULK\_READER\_INFO, 629  
ER\_BULK\_READER\_LIBCURL\_ERROR, 159  
ER\_BULK\_READER\_LIBCURL\_ERROR\_LOG, 629  
ER\_BULK\_READER\_LIBCURL\_INIT\_FAILED, 158  
ER\_BULK\_READER\_LIBCURL\_INIT\_FAILED\_LOG, 629  
ER\_BULK\_READER\_SERVER\_ERROR, 159  
ER\_BULK\_READER\_SERVER\_ERROR\_LOG, 629  
ER\_CACHING\_SHA2\_PASSWORD\_SECOND\_PASSWORD\_USAGE\_IGNORED, 159  
ER\_CALL\_ME\_LOCALHOST, 175

---

ER\_CANNOT\_ADD\_FOREIGN, 19  
ER\_CANNOT\_ADD\_FOREIGN\_BASE\_COL\_STORED, 86  
ER\_CANNOT\_ADD\_FOREIGN\_BASE\_COL\_VIRTUAL, 84  
ER\_CANNOT\_ALTER\_SRID\_DUE\_TO\_INDEX, 101  
ER\_CANNOT\_CHANGE\_TO\_ROOT\_DIR, 281  
ER\_CANNOT\_CONVERT\_STRING, 125  
ER\_CANNOT\_CREATE\_VIRTUAL\_INDEX\_CONSTRAINT, 84  
ER\_CANNOT\_DISCARD\_TEMPORARY\_TABLE, 69  
ER\_CANNOT\_DROP\_COLUMN\_FUNCTIONAL\_INDEX, 113  
ER\_CANNOT\_FIND\_KEY\_IN\_KEYRING, 85  
ER\_CANNOT\_GET\_SERVER\_VERSION\_FROM\_TABLESPACE\_HEADER, 553  
ER\_CANNOT\_GRANT\_ROLES\_TO\_ANONYMOUS\_USER, 127  
ER\_CANNOT\_GRANT\_SYSTEM\_PRIV\_TO\_MANDATORY\_PROCESS, 129  
ER\_CANNOT\_INTERPRET\_PERSISTED\_SENSITIVE\_VARIABLES, 613  
ER\_CANNOT\_LOAD\_FROM\_TABLE\_V2, 53  
ER\_CANNOT\_LOCK\_USER\_MANAGEMENT\_CACHES, 91  
ER\_CANNOT\_LOG\_PARTIAL\_DROP\_DATABASE\_WITH\_GRID, 77  
ER\_CANNOT\_PERSIST\_SENSITIVE\_VARIABLES, 154  
ER\_CANNOT\_PURGE\_BINLOG\_WITH\_BACKUP\_LOCK, 153  
ER\_CANNOT\_SET\_DATABASE\_ENCRYPTION, 122  
ER\_CANNOT\_SET\_LOG\_ERROR\_SERVICES, 282  
ER\_CANNOT\_SET\_SERVER\_VERSION\_IN\_TABLESPACE\_HEADER, 553  
ER\_CANNOT\_SET\_TABLESPACE\_ENCRYPTION, 122  
ER\_CANNOT\_SET\_TABLE\_ENCRYPTION, 122  
ER\_CANNOT\_USER, 31  
ER\_CANNOT\_USER\_REFERENCED\_AS\_DEFINER, 142  
ER\_CANNOT\_USE\_AUTOEXTEND\_SIZE\_CLAUSE, 145  
ER\_CANNOT\_USE\_ENCRYPTION\_CLAUSE, 122  
ER\_CANT\_ACCESS\_CAPATH, 181  
ER\_CANT\_AGGREGATE\_2COLLATIONS, 22  
ER\_CANT\_AGGREGATE\_3COLLATIONS, 22  
ER\_CANT\_AGGREGATE\_NCOLLATIONS, 23  
ER\_CANT\_ALLOC\_TABLE\_OBJECT, 259  
ER\_CANT\_CHANGE\_SYS\_VAR\_IN\_READ\_ONLY\_MODE, 161  
ER\_CANT\_CHANGE\_TX\_CHARACTERISTICS, 41  
ER\_CANT\_CHECK\_PID\_PATH, 388  
ER\_CANT\_CHOWN\_DATADIR, 180  
ER\_CANT\_COMBINE\_ANONYMOUS\_TO\_GTID\_AND\_AUTO, 143  
ER\_CANT\_CREATE\_ADMIN\_THREAD, 549  
ER\_CANT\_CREATE\_CACHE\_FOR\_DB\_OPT, 260  
ER\_CANT\_CREATE\_DB, 3  
ER\_CANT\_CREATE\_FILE, 3  
ER\_CANT\_CREATE\_GEOMETRY\_OBJECT, 32  
ER\_CANT\_CREATE\_HANDLER\_FILE, 37  
ER\_CANT\_CREATE\_HANDLER\_OBJECT\_FOR\_TABLE, 259  
ER\_CANT\_CREATE\_HANDLE\_MGR\_THREAD, 165  
ER\_CANT\_CREATE\_INTERRUPT\_THREAD, 173  
ER\_CANT\_CREATE\_NAMED\_PIPES\_THREAD, 173  
ER\_CANT\_CREATE\_PID\_FILE, 172  
ER\_CANT\_CREATE\_SCHEDULER\_THREAD, 167  
ER\_CANT\_CREATE\_SHM\_THREAD, 173  
ER\_CANT\_CREATE\_SHUTDOWN\_THREAD, 172  
ER\_CANT\_CREATE\_TABLE, 3  
ER\_CANT\_CREATE\_TABLE\_SHARE\_FROM\_FRM, 258  
ER\_CANT\_CREATE\_TCPIP\_THREAD, 173  
ER\_CANT\_CREATE\_TEST\_FILE, 172  
ER\_CANT\_CREATE\_THREAD, 13  
ER\_CANT\_CREATE\_USER\_WITH\_GRANT, 32  
ER\_CANT\_CREATE\_UUID, 170  
ER\_CANT\_DETACH\_SESSION\_LEFT\_BY\_PLUGIN, 216  
ER\_CANT\_DO\_IMPLICIT\_COMMIT\_IN\_TRX\_WHEN\_GTID\_N, 58  
ER\_CANT\_DO\_THIS\_DURING\_AN\_TRANSACTION, 15  
ER\_CANT\_DROP\_FIELD\_OR\_KEY, 9  
ER\_CANT\_ENFORCE\_GTID\_CONSISTENCY\_WITH\_ONGOI, 79  
ER\_CANT\_EXECUTE\_COMMAND\_WITH\_ASSIGNED\_GTID, 153  
ER\_CANT\_EXECUTE\_IN\_READ\_ONLY\_TRANSACTION, 59  
ER\_CANT\_FIND\_DL\_ENTRY, 12  
ER\_CANT\_FIND\_SYSTEM\_REC, 4  
ER\_CANT\_FIND\_UDF, 12  
ER\_CANT\_GET\_STAT, 4  
ER\_CANT\_HASH\_DO\_AND\_IGNORE\_RULES, 181  
ER\_CANT\_IDENTIFY\_CHARSET\_USING\_DEFAULT, 260  
ER\_CANT\_INCREASE\_MAX\_OPEN\_FILES, 177  
ER\_CANT\_INITIALIZE\_BUILTIN\_PLUGINS, 180  
ER\_CANT\_INITIALIZE\_DYNAMIC\_PLUGINS, 180  
ER\_CANT\_INITIALIZE\_EARLY\_PLUGINS, 180  
ER\_CANT\_INITIALIZE\_GTID, 180  
ER\_CANT\_INITIALIZE\_UDF, 12  
ER\_CANT\_INIT\_DBS, 178  
ER\_CANT\_INIT\_SCHEDULER\_THREAD, 167  
ER\_CANT\_INIT\_TC\_LOG, 166

---

---

ER\_CANT\_INIT\_TIMER, 181  
ER\_CANT\_JOIN\_SHUTDOWN\_THREAD, 181  
ER\_CANT\_LOCK, 4  
ER\_CANT\_LOCK\_LOG\_TABLE, 40  
ER\_CANT\_LOCK\_TABLE, 259  
ER\_CANT\_LOCK\_TABLESPACE, 259  
ER\_CANT\_MODIFY\_SRID\_0, 108  
ER\_CANT\_MODIFY\_SRS\_USED\_BY\_COLUMN, 109  
ER\_CANT\_OPEN\_AND\_LOCK\_PRIVILEGE\_TABLES, 200  
ER\_CANT\_OPEN\_CA, 181  
ER\_CANT\_OPEN\_DATADIR\_AFTER\_UPGRADE\_FAILURE, 259  
261  
ER\_CANT\_OPEN\_DB\_OPT\_USING\_DEFAULT\_CHARSET, 260  
260  
ER\_CANT\_OPEN\_DIR, 262  
ER\_CANT\_OPEN\_ERROR\_LOG, 182  
ER\_CANT\_OPEN\_FILE, 4  
ER\_CANT\_OPEN\_FRM\_FILE, 199  
ER\_CANT\_OPEN\_LIBRARY, 12  
ER\_CANT\_OPEN\_TABLE\_MYSQL\_PROC, 261  
ER\_CANT\_PARSE\_STORED\_ROUTINE\_BODY, 261  
ER\_CANT\_PROCESS\_EXPRESSION\_FOR\_GENERATED\_COLUMNS\_UPDATE\_TABLE\_IN\_CREATE\_TABLE\_SELECT, 572  
572  
ER\_CANT\_READ\_DIR, 4  
ER\_CANT\_READ\_ERRMSG, 178  
ER\_CANT\_READ\_FRM\_FILE, 199  
ER\_CANT\_READ\_TABLE\_MYSQL\_PROC, 261  
ER\_CANT\_REMOVE\_ALL\_FIELDS, 9  
ER\_CANT\_REMOVE\_PID\_FILE, 172  
ER\_CANT\_RENAME\_LOG\_TABLE, 42  
ER\_CANT\_REOPEN\_TABLE, 13  
ER\_CANT\_REPLICATE\_ANONYMOUS\_WITH\_AUTO\_POSITION, 533  
533  
ER\_CANT\_REPLICATE\_ANONYMOUS\_WITH\_GTID\_MODE\_OFF, 533  
533  
ER\_CANT\_REPLICATE\_GTID\_WITH\_GTID\_MODE\_OFF, 533  
533  
ER\_CANT\_RESET\_MASTER, 85  
ER\_CANT\_RESET\_SOURCE, 85  
ER\_CANT\_SAVE\_GTIDS, 181  
ER\_CANT\_SET\_ANONYMOUS\_TO\_GTID\_AND\_WAIT\_UNTIL\_SQL\_THD\_AFTER\_GTIDS, 144  
144  
ER\_CANT\_SET\_DATADIR, 180  
ER\_CANT\_SET\_DATA\_DIR, 547  
ER\_CANT\_SET\_ERROR\_LOG\_SERVICE, 107  
ER\_CANT\_SET\_ERROR\_SUPPRESSION\_LIST, 111  
ER\_CANT\_SET\_ERROR\_SUPPRESSION\_LIST\_FROM\_COMMAND\_LINE, 539  
539  
ER\_CANT\_SET\_GTID\_MODE, 79  
ER\_CANT\_SET\_GTID\_NEXT\_LIST\_TO\_NON\_NULL\_WHEN\_GTID\_MODE\_IS\_OFF, 58  
58  
ER\_CANT\_SET\_GTID\_NEXT\_TO\_ANONYMOUS\_WHEN\_GTID\_MODE\_IS\_TABLE, 58  
58  
ER\_CANT\_SET\_GTID\_NEXT\_TO\_GTID\_WHEN\_GTID\_MODE\_IS, 58  
58  
ER\_CANT\_SET\_GTID\_NEXT\_WHEN\_OWNING\_GTID, 59  
59  
ER\_CANT\_SET\_GTID\_PURGED\_DUE\_SETS\_CONSTRAINTS, 90  
90  
ER\_CANT\_SET\_GTID\_PURGED\_WHEN\_GTID\_EXECUTED\_IS, 63  
63  
ER\_CANT\_SET\_GTID\_PURGED\_WHEN\_OWNED\_GTIDS\_IS\_NO, 63  
63  
ER\_CANT\_SET\_HANDLER\_REFERENCE\_FOR\_TABLE, 259  
259  
ER\_CANT\_SET\_PATH\_FOR, 262  
ER\_CANT\_SET\_PERSISTED, 161  
ER\_CANT\_SET\_SQL\_AFTER\_OR\_BEFORE\_GTIDS\_WITH\_ANO, 144  
144  
ER\_CANT\_SET\_UP\_PERSISTED\_VALUES, 180  
ER\_CANT\_SET\_VARIABLE\_WHEN\_OWNING\_GTID, 81  
81  
ER\_CANT\_START\_ERROR\_LOG\_SERVICE, 280  
ER\_CANT\_STAT\_DATADIR, 180  
ER\_CANT\_STAT\_FILE, 270  
ER\_CANT\_UPDATE\_COLUMN\_UPDATE\_TABLE\_IN\_CREATE\_TABLE\_SELECT, 54  
54  
ER\_CANT\_UPDATE\_USED\_TABLE\_IN\_SF\_OR\_TRG, 34  
34  
ER\_CANT\_UPDATE\_WITH\_READLOCK, 19  
ER\_CANT\_UPGRADE\_GENERATED\_COLUMNS\_TO\_DD, 259  
259  
ER\_CANT\_USE\_ANONYMOUS\_TO\_GTID\_WITH\_GTID\_MODE\_OFF, 143  
143  
ER\_CANT\_USE\_AUTO\_POSITION\_WITH\_GTID\_MODE\_OFF, 519  
519  
ER\_CANT\_USE\_GTID\_ONLY\_WITH\_GTID\_MODE\_NOT\_ON, 519  
519  
ER\_CANT\_USE\_OPTION\_HERE, 20  
ER\_CANT\_USE\_SAME\_UUID\_AS\_GROUP\_NAME, 145  
145  
ER\_CANT\_USE\_SAME\_UUID\_AS\_VIEW\_CHANGE\_UUID, 147  
147  
ER\_CANT\_WAIT\_FOR\_EXECUTED\_GTID\_SET\_WHILE\_OWNING, 84  
84  
ER\_CAPACITY\_EXCEEDED, 84  
ER\_CAPACITY\_EXCEEDED\_IN\_PARSER, 85  
ER\_CAPACITY\_EXCEEDED\_IN\_RANGE\_OPTIMIZER, 84  
84  
ER\_CA\_SELF\_SIGNED, 169  
ER\_CHANGE\_MASTER\_ENFORCE\_GTID\_CONSISTENCY, 166  
166  
ER\_CHANGED\_GTID\_MODE, 166  
ER\_CHANGED\_MAX\_CONNECTIONS, 177  
ER\_CHANGED\_MAX\_OPEN\_FILES, 177  
ER\_CHANGED\_TABLE\_OPEN\_CACHE, 177  
ER\_CHANGE\_MASTER\_PASSWORD\_LENGTH, 73

---

ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_CHECKTABLE_MIN_REC_FLAG_NOT_SET, 132	ER_CHECKTABLE_MIN_REC_FLAG_NOT_SET, 635
ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_CHECKTABLE_MIN_REC_FLAG_SET, 132	ER_CHECKTABLE_MIN_REC_FLAG_SET, 634
ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECK, 132	ER_CLIENT_DOES_NOT_SUPPORT, 101
ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID_ONLY_ID_UNSAFE_CREATE_DROP_TEMP_TABLE, 150	ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECK, 156
ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITIONING_WITH_GTID_ONLY_TIMEOUT, 151	ER_GTID_ONLY_ID_UNSAFE_CREATE_DROP_TEMP_TABLE, 112
ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITIONING_WITHOUT_POSITIONS, 151	ER_POSITIONING_WITH_GTID_ONLY_TIMEOUT, 146
ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITHOUT_POSITIONS, 151	ER_CLIENT_KEYRING_UDF_KEY_INVALID, 133
ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROWS_FORMAT_WITH_GTID_ONLY, 150	ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG, 133
ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE_NOT_ALLOWED, 151	ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID, 133
ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE, 54	ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG, 133
ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM_SIZE, 147	ER_CLIENT_LOCAL_FILES_DISABLED, 135
ER_CHANGE_SOURCE_PASSWORD_LENGTH, 73	ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ADMIN, 133
ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_CLIENT, 132	ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT, 133
ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT, 132	ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST, 133
ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CLIENT_TRACE, 132	ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIC, 133
ER_CHARACTER_SET_MISMATCH, 141	ER_CLONE_CHARSET, 126
ER_CHECKING_TABLE, 258	ER_CLONE_CLIENT_TRACE, 547
ER_CHECKREAD, 4	ER_CLONE_CONFIG, 126
ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFERENCED_COLUMNS, 121	ER_CLONE_CREATE_HANDLER_FAIL_TRACE, 293
ER_CHECK_CONSTRAINT_DUP_NAME, 121	ER_CLONE_DDL_IN_PROGRESS, 100
ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED, 120	ER_CLONE_DISALLOWED, 127
ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED, 120	ER_CLONE_DISKSPACE, 127
ER_CHECK_CONSTRAINT_NOT_FOUND, 121	ER_CLONE_DONOR, 126
ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENTED_COLUMN, 121	ER_CLONE_DONOR_TRACE, 546
ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN, 121	ER_CLONE_DONOR_VERSION, 126
ER_CHECK_CONSTRAINT_ROW_VALUE, 121	ER_CLONE_ENCRYPTION, 127
ER_CHECK_CONSTRAINT_VARIABLES, 121	ER_CLONE_HANDLER_EXISTS, 293
ER_CHECK_CONSTRAINT_VIOLATED, 121	ER_CLONE_HANDLER_EXIST_TRACE, 293
ER_CHECK_NOT_IMPLEMENTED, 15	ER_CLONE_INFO_CLIENT, 546
ER_CHECK_NO_SUCH_TABLE, 15	ER_CLONE_INFO_SERVER, 547
ER_CHECK_TABLE_FUNCTIONS, 642	ER_CLONE_IN_PROGRESS, 127
ER_CHECK_TABLE_FUNCTIONS_DETAIL, 642	ER_CLONE_LOOPBACK, 127
ER_CHECK_TABLE_INSTANT_VERSION_BIT_SET, 632	ER_CLONE_NETWORK_PACKET, 136
	ER_CLONE_OS, 126
	ER_CLONE_PLATFORM, 126
	ER_CLONE_PLUGIN_MATCH, 126
	ER_CLONE_PLUGIN_NOT_LOADED, 292
	ER_CLONE_PLUGIN_NOT_LOADED_TRACE, 293
	ER_CLONE_PROTOCOL, 126
	ER_CLONE_PROTOCOL_ERROR, 546
	ER_CLONE_PROTOCOL_TRACE, 546
	ER_CLONE_REMOTE_ERROR, 546
	ER_CLONE_SERVER_TRACE, 547

---

---

ER_CLONE_SHUTDOWN_TRACE, 566	ER_COMPONENT_EE_DATA_DECRYPTION_ERROR, 624
ER_CLONE_SYS_CONFIG, 126	ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR, 624
ER_CLONE_TOO_MANY_CONCURRENT_CLONES, 100	ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE, 624
ER_CMD_NEED_SUPER, 99	ER_COMPONENT_EE_DATA_SIGN_ERROR, 624
ER_COALESCE_ONLY_ON_HASH_PARTITION, 38	ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAILURE, 623
ER_COALESCE_PARTITION_NO_PARTITION, 38	ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM, 623
ER_COLLATION_CHARSET_MISMATCH, 21	ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENTS, 623
ER_COLUMNACCESS_DENIED_ERROR, 13	ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF_RANGE, 623
ER_COLUMN_CHANGE_SIZE, 128	ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION_FAILURE, 624
ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_COLUMN, 623	ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION_FAILURE, 624
ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2, 61	ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILURE, 623
ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE, 41	ER_COMPONENT_EE_INSUFFICIENT_LENGTH, 624
ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2, 69	ER_COMPONENT_EE_OPENSSL_ERROR, 624
ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CTX, 156	ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILURE, 623
ER_COMMAND_SERVICE_BACKEND_FAILED, 156	ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE, 623
ER_COMMENT_CONTAINS_INVALID_STRING, 153	ER_COMPONENT_FILTER_CONFUSED, 321
ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG, 32	ER_COMPONENT_FILTER_DIAGNOSTICS, 107
ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION, 90	ER_COMPONENT_FILTER_FLABBERGASTED, 98
ER_COMPONENTS_CANT_LOAD, 89	ER_COMPONENT_FILTER_WRONG_VALUE, 528
ER_COMPONENTS_CANT_RELEASE_SERVICE, 90	ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY, 626
ER_COMPONENTS_CANT_SATISFY_DEPENDENCY, 90	ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE, 626
ER_COMPONENTS_CANT_UNLOAD, 90	ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE, 626
ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION, 297	ER_COMPONENT_LOCK, 638
ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP, 169	ER_COMPONENT_MANIPULATE_ROW_FAILED, 90
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT, 596	ER_COMPONENT_MASKING_ABI, 638
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT, 596	ER_COMPONENT_MASKING_ABI_REASON, 638
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN, 169	ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE, 638
ER_COMPONENTS_LOAD_CANT_INITIALIZE, 90	ER_COMPONENT_MASKING_OTHER_ERROR, 638
ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPLEMENTATION, 90	ER_COMPONENT_MASKING_RANDOM_CREATE, 638
ER_COMPONENTS_NO_SCHEME, 89	ER_COMPONENT_MASKING_RANDOM_CREATE_REASON, 638
ER_COMPONENTS_NO_SCHEME_SERVICE, 89	ER_COMPONENT_SERVICE_CALL, 638
ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP, 169	ER_COMPONENT_SERVICE_CALL_RESULT, 638
ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE, 90	ER_COMPONENT_TABLE_INCORRECT, 90
ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE_IMPLEMENTATION, 90	ER_COMPONENT_UNLOCK, 638
ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP, 90	ER_CONCURRENT_PROCEDURE_USAGE, 152
ER_COMPONENTS_UNLOAD_NOT_LOADED, 90	



---

ER\_CONDITIONAL\_DEBUG, 625  
 ER\_COND\_ITEM\_TOO\_LONG, 46  
 ER\_CONFIG\_OPTION\_WITHOUT\_GROUP, 185  
 ER\_CONFIRMING\_THE\_FUTURE, 174  
 ER\_CONFLICTING\_DECLARATIONS, 25  
 ER\_CONFLICT\_FN\_PARSE\_ERROR, 45  
 ER\_CONNECTION\_ABORTED, 527  
 ER\_CONNECTION\_HANDLING\_OOM, 171  
 ER\_CONNECTION\_METADATA, 17  
 ER\_CONNECT\_TO\_FOREIGN\_DATA\_SOURCE, 33  
 ER\_CONNECT\_TO\_MASTER, 19  
 ER\_CONNECT\_TO\_SOURCE, 19  
 ER\_CONN\_ATTR\_TRUNCATED, 192  
 ER\_CONN\_CONTROL\_DELAY\_ACTION\_INIT\_FAILED, 323  
 ER\_CONN\_CONTROL\_ERROR\_MSG, 320  
 ER\_CONN\_CONTROL\_EVENT\_COORDINATOR\_INIT\_FAILED, 322  
 ER\_CONN\_CONTROL\_FAILED\_TO\_SET\_CONN\_DELAY, 323  
 ER\_CONN\_CONTROL\_FAILED\_TO\_UPDATE\_CONN\_DELAY, 323  
 ER\_CONN\_CONTROL\_INVALID\_CONN\_DELAY\_TYPE, 322  
 ER\_CONN\_CONTROL\_STAT\_CONN\_DELAY\_TRIGGERED, 322  
 ER\_CONN\_CONTROL\_STAT\_CONN\_DELAY\_TRIGGERED\_UPDATE\_FAILED, 322  
 ER\_CONN\_INIT\_CONNECT\_IGNORED, 322  
 ER\_CONN\_INIT\_CONNECT\_IGNORED\_MFA, 639  
 ER\_CONN\_LIMIT, 612  
 ER\_CONN\_PER\_THREAD\_NO\_THREAD, 188  
 ER\_CONN\_PIP\_CANT\_CREATE\_EVENT, 188  
 ER\_CONN\_PIP\_CANT\_CREATE\_PIPE, 188  
 ER\_CONN\_SHM\_CANT\_CREATE\_CONNECTION, 188  
 ER\_CONN\_SHM\_CANT\_CREATE\_SERVICE, 188  
 ER\_CONN\_SHM\_LISTENER, 188  
 ER\_CONN\_SOCKET\_ACCEPT\_FAILED, 192  
 ER\_CONN\_SOCKET\_SELECT\_FAILED, 192  
 ER\_CONN\_TCP\_ADDRESS, 188  
 ER\_CONN\_TCP\_BIND\_FAIL, 190  
 ER\_CONN\_TCP\_BIND\_RETRY, 189  
 ER\_CONN\_TCP\_CANT\_RESET\_V6ONLY, 189  
 ER\_CONN\_TCP\_CANT\_RESOLVE\_HOSTNAME, 189  
 ER\_CONN\_TCP\_CREATED, 188  
 ER\_CONN\_TCP\_ERROR\_WITH\_STRERROR, 189  
 ER\_CONN\_TCP\_IPV6\_AVAILABLE, 189  
 ER\_CONN\_TCP\_IPV6\_UNAVAILABLE, 189  
 ER\_CONN\_TCP\_IP\_NOT\_LOGGED, 190  
 ER\_CONN\_TCP\_IS\_THERE\_ANOTHER\_USING\_PORT, 189  
 ER\_CONN\_TCP\_LISTEN\_FAIL, 190  
 ER\_CONN\_TCP\_NO\_SOCKET, 188  
 ER\_CONN\_TCP\_RESOLVE\_INFO, 190  
 ER\_CONN\_TCP\_START\_FAIL, 190  
 ER\_CONN\_TPC\_BIND\_FAIL, 190  
 ER\_CONN\_UNIX\_IS\_THERE\_ANOTHER\_USING\_SOCKET, 189  
 ER\_CONN\_UNIX\_LISTEN\_FAILED, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_CLOSE, 192  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_CREATE, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_DELETE, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_OPEN, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_READ, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_SYNC, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_WRITE, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_EMPTY, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_FAIL, 190  
 ER\_CONN\_UNIX\_LOCK\_FILE\_GIVING\_UP, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_PIDLESS, 191  
 ER\_CONN\_UNIX\_NO\_BIND\_NO\_START, 190  
 ER\_CONN\_UNIX\_NO\_FD, 190  
 ER\_CONN\_UNIX\_PATH\_TOO\_LONG, 190  
 ER\_CONN\_UNIX\_PID\_CLAIMED\_SOCKET\_FILE, 189  
 ER\_CONSECUTIVE\_REORG\_PARTITIONS, 39  
 ER\_CREATE\_FAILED, NOT\_FOUND, 134  
 ER\_CONVERT\_MULTI\_VALUE, 639  
 ER\_UPDATE\_FAILED, 5  
 ER\_CORE\_VALUES, 173  
 ER\_CORRUPTED\_JSON\_DIFF, 102  
 ER\_CORRUPT\_HELP\_DB, 21  
 ER\_COULD\_NOT\_APPLY\_JSON\_DIFF, 102  
 ER\_COULD\_NOT\_CREATE\_WINDOWS\_REGISTRY\_KEY, 541  
 ER\_COULD\_NOT\_REINITIALIZE\_AUDIT\_LOG\_FILTERS, 535  
 ER\_CRASHED\_ON\_REPAIR, 17  
 ER\_CRASHED\_ON\_USAGE, 16  
 ER\_CREATED\_SYSTEM\_WITH\_VERSION, 290  
 ER\_CREATE\_FILEGROUP\_FAILED, 39  
 ER\_CREATE\_SELECT\_WITH\_GIPK\_DISALLOWED\_IN\_SBR, 156  
 ER\_CREATING\_NEW\_UUID, 170  
 ER\_CREATING\_NEW\_UUID\_FIRST\_START, 280  
 ER\_CREDENTIALLESS\_AUTO\_USER\_BAD, 171  
 ER\_CREDENTIALS\_CONTRADICT\_TO\_HISTORY, 100  
 ER\_CTE\_MAX\_RECURSION\_DEPTH, 100  
 ER\_CTE\_RECURSIVE\_FORBIDDEN\_JOIN\_ORDER, 93  
 ER\_CTE\_RECURSIVE\_FORBIDS\_AGGREGATION, 93  
 ER\_CTE\_RECURSIVE\_NOT\_UNION, 156  
 ER\_CTE\_RECURSIVE\_REQUIRES\_NONRECURSIVE\_FIRST, 93

---

---

ER\_CTE\_RECURSIVE\_REQUIRES\_SINGLE\_REFERENCER  
94  
ER\_CTE\_RECURSIVE\_REQUIRES\_UNION, 93  
ER\_CURRENT\_PASSWORD\_CANNOT\_BE\_RETAINED,  
129  
ER\_CURRENT\_PASSWORD\_NOT\_REQUIRED, 129  
ER\_CUT\_VALUE\_GROUP\_CONCAT, 22  
ER\_CYCLE\_TIMER\_IS\_NOT\_AVAILABLE, 293  
ER\_DATABASE\_NAME, 45  
ER\_DATA\_DIRECTORY\_UNUSABLE, 542  
ER\_DATA\_DIRECTORY\_UNUSABLE\_DELETABLE,  
565  
ER\_DATA\_OUT\_OF\_RANGE, 50  
ER\_DATA\_TOO\_LONG, 31  
ER\_DATETIME\_FUNCTION\_OVERFLOW, 34  
ER\_DA\_AUTH\_ID\_WITH\_SYSTEM\_USER\_PRIV\_IN\_MANE  
127  
ER\_DA\_CANT\_OPEN\_ERROR\_LOG, 142  
ER\_DA\_CONN\_LIMIT, 152  
ER\_DA\_ERROR\_LOG\_COMPONENT\_FLUSH\_FAILED,  
148  
ER\_DA\_ERROR\_LOG\_MULTIPLE\_FILTERS, 142  
ER\_DA\_ERROR\_LOG\_TABLE\_DISABLED, 142  
ER\_DA\_EXPIRE\_LOGS\_DAYS\_IGNORED, 156  
ER\_DA\_GLOBAL\_CONN\_LIMIT, 152  
ER\_DA\_GRP\_RPL\_RECOVERY\_ENDPOINT\_FORMAT,  
138  
ER\_DA\_GRP\_RPL\_RECOVERY\_ENDPOINT\_INVALID,  
139  
ER\_DA\_GRP\_RPL\_STARTED\_AUTO\_REJOIN, 131  
ER\_DA\_INVALID\_CONDITION\_NUMBER, 56  
ER\_DA\_NO\_ERROR\_LOG\_PARSER\_CONFIGURED,  
142  
ER\_DA\_OOM, 135  
ER\_DA\_PLUGIN\_INSTALL\_ERROR, 128  
ER\_DA\_RPL\_GTID\_TABLE\_CANNOT\_OPEN, 128  
ER\_DA\_SSL\_FIPS\_MODE\_ERROR, 151  
ER\_DA\_SSL\_LIBRARY\_ERROR, 128  
ER\_DA\_UDF\_INVALID\_ARGUMENT\_TO\_SET\_CHARSET,  
136  
ER\_DA\_UDF\_INVALID\_CHARSET, 134  
ER\_DA\_UDF\_INVALID\_CHARSET\_SPECIFIED, 134  
ER\_DA\_UDF\_INVALID\_COLLATION, 134  
ER\_DA\_UDF\_INVALID\_EXTENSION\_ARGUMENT\_TYPE,  
134  
ER\_DA\_UDF\_INVALID\_RETURN\_TYPE\_TO\_SET\_CHARS  
136  
ER\_DA\_UNKNOWN\_ERROR\_NUMBER, 128  
ER\_DBACCESS\_DENIED\_ERROR, 6  
ER\_DEBUG\_CHECK\_SHARES\_DROPPED, 222  
ER\_DEBUG\_CHECK\_SHARES\_INFO, 222  
ER\_DEBUG\_CHECK\_SHARES\_OPEN, 222  
ER\_DB\_ACCESS\_DENIED, 127  
ER\_DB\_CREATE\_EXISTS, 4  
ER\_DB\_DROP\_EXISTS, 4  
ER\_DB\_DROP\_RMDIR, 4  
ER\_DB\_DROP\_RMDIR2, 97  
ER\_DB\_OPT\_NOT\_FOUND\_USING\_DEFAULT\_CHARSET,  
260  
ER\_DDL\_IN\_PROGRESS, 100  
ER\_DDL\_LOG\_ERROR, 41  
ER\_DDL\_MSG\_1, 605  
ER\_DD\_ABORTING\_PARTIAL\_UPGRADE, 198  
ER\_DD\_CACHE\_NOT\_EMPTY\_AT\_SHUTDOWN,  
165  
ER\_DD\_CANT\_CREATE\_OBJECT\_KEY, 165  
ER\_DD\_CANT\_CREATE\_SP, 259  
ER\_DD\_CANT\_FETCH\_TABLE\_DATA, 259  
ER\_DD\_CANT\_FIX\_SE\_DATA, 259  
ER\_DD\_CANT\_SET\_OBJECT\_KEY, 165  
ER\_DD\_CANT\_RESOLVE\_VIEW, 183  
ER\_DD\_CREATED\_FOR\_UPGRADE, 198  
ER\_DD\_ERROR\_CREATING\_ENTRY, 259  
ER\_DD\_FAILSAFE, 163  
ER\_DD\_FRM\_EXISTS\_FOR\_TABLE, 198  
ER\_DD\_INITIALIZE, 299  
ER\_DD\_INITIALIZE\_SQL\_ERROR, 536  
ER\_DD\_INIT\_FAILED, 164  
ER\_DD\_INIT\_UPGRADE\_FAILED, 164  
ER\_DD\_METADATA\_NOT\_FOUND, 165  
ER\_DD\_MINOR\_DOWNGRADE, 300  
ER\_DD\_MINOR\_DOWNGRADE\_VERSION\_NOT\_SUPPORTED,  
300  
ER\_DD\_NO\_VERSION\_FOUND, 300  
ER\_DD\_NO\_WRITES\_NO\_REPOPULATION, 163  
ER\_DD\_OBJECT\_RELEASER\_REMAINS, 165  
ER\_DD\_OBJECT\_REMAINS, 165  
ER\_DD\_OBJECT\_REMAINS\_IN\_RELEASER, 165  
ER\_DD\_POPULATING\_TABLES\_FAILED, 164  
ER\_DD\_RESTART, 299  
ER\_DD\_SCHEMA\_NOT\_FOUND, 197  
ER\_DD\_SE\_INIT\_FAILED, 197  
ER\_DD\_TABLESPACE\_NOT\_FOUND, 182  
ER\_DD\_TABLE\_NOT\_FOUND, 197  
ER\_DD\_TRG\_CANT\_ADD, 183  
ER\_DD\_TRG\_CONNECTION\_COLLATION\_MISSING,  
182  
ER\_DD\_TRG\_DB\_COLLATION\_MISSING, 183  
ER\_DD\_TRG\_DEFINER\_OOM, 183  
ER\_DD\_TRG\_FILE\_UNREADABLE, 183  
ER\_DD\_UPDATE\_DATADIR\_FLAG\_FAIL, 642  
ER\_DD\_UPDATING\_PLUGIN\_MD\_FAILED, 164  
ER\_DD\_UPGRADE, 299  
ER\_DD\_UPGRADE\_COMPLETED, 562  
ER\_DD\_UPGRADE\_DD\_OPEN\_FAILED, 288  
ER\_DD\_UPGRADE\_DD\_POPULATED, 288  
ER\_DD\_UPGRADE\_FAILED\_FIND\_VALID\_DATA\_DIR,  
289

---

ER_DD_UPGRADE_FAILED_INIT_DD_SE, 290	ER_DEBUG_SYNC_TIMEOUT, 46
ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE, 288	ER_DEFAULT_AS_VAL_GENERATED, 115
ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS, 289	ER_DEFAULT_SE_UNAVAILABLE, 182
ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS, 289	ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALLOWED, 115
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES, 288	ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_INVALID, 115
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES, 288	ER_DEFAULT_VAL_GENERATED_NON_PRIOR, 115
ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE, 288	ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC, 115
ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE, 299	ER_DEFAULT_VAL_GENERATED_ROW_VALUE, 115
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD, 290	ER_DEFINITION_CONTAINS_INVALID_STRING, 158
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD, 290	ER_ABORT, 158
ER_DD_UPGRADE_FOUND_PREPARED_XA_TRANSACTION, 575	ER_DEPART_WITH_GRACE, 169
ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED, 289	ER_DEPENDENT_BY_CHECK_CONSTRAINT, 137
ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED, 289	ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE, 105
ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED, 289	ER_DEPENDENT_BY_FUNCTIONAL_INDEX, 123
ER_DD_UPGRADE_OFF, 299	ER_DEPENDENT_BY_GENERATED_COLUMN, 79
ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED, 288	ER_DEPENDENT_BY_PARTITION_FUNC, 125
ER_DD_UPGRADE_SCHEMA_UNAVAILABLE, 300	ER_DEPRECATED_NATIONAL, 109
ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED, 290	ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS, 604
ER_DD_UPGRADE_SE_LOGS_FAILED, 290	ER_DEPRECATED_SYNTAX_NO_REPLACEMENT, 297
ER_DD_UPGRADE_START, 290	ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT, 297
ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED, 289	ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS, 171
ER_DD_UPGRADE_TABLE_INTACT_ERROR, 296	ER_DEPRECATED_TLS_VERSION_SESSION, 601
ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED, 289	ER_DEPRECATED_UTF8_ALIAS, 109
ER_DD_UPGRADE_VERSION_NOT_SUPPORTED, 299	ER_DEPRECATED_MSG_NO_REPLACEMENT, 297
ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG, 298	ER_DEPRECATED_MSG_WITH_REPLACEMENT, 278
ER_DD_VERSION_FOUND, 163	ER_DERIVED_MUST_HAVE_ALIAS, 21
ER_DD_VERSION_INSTALLED, 163	ER_DES_FILE_WRONG_KEY, 184
ER_DD_VERSION_UNSUPPORTED, 163	ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN, 216
ER_DD_VIEW_CANT_ALLOC_CHARSET, 164	ER_DETACHING_SESSION_LEFT_BY_PLUGIN, 216
ER_DD_VIEW_CANT_CREATE, 165	ER_DIMENSION_UNSUPPORTED, 75
ER_DD_VIEW_WITHOUT_DEFINER, 183	ER_DISABLED_STORAGE_ENGINE, 83
ER_DEBUG_SYNC_EXECUTED, 166	ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT, 166
ER_DEBUG_SYNC_HIT, 166	ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECT, 141
ER_DEBUG_SYNC_HIT_LIMIT, 46	ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECT, 141
ER_DEBUG_SYNC_OOM, 166	ER_DISALLOWED_OPERATION, 102
ER_DEBUG_SYNC_THREAD_MAX, 166	ER_DISCARD_FK_CHECKS_RUNNING, 61
	ER_DISCONNECTING_REMAINING_CLIENTS, 175
	ER_DISK_FULL_NOWAIT, 104
	ER_DIVISION_BY_ZERO, 29

---

---

ER\_DONT\_SUPPORT\_REPLICA\_PRESERVE\_COMMIT\_ORDER, 71  
ER\_DONT\_SUPPORT\_SLAVE\_PRESERVE\_COMMIT\_ORDER, 71  
ER\_DROP\_DATABASE\_FAILED\_RMDIR\_MANUALLY, 298  
ER\_DROP\_FILEGROUP\_FAILED, 39  
ER\_DROP\_INDEX\_FK, 40  
ER\_DROP\_LAST\_PARTITION, 38  
ER\_DROP\_PARTITION\_NON\_EXISTENT, 38  
ER\_DROP\_PK\_COLUMN\_TO\_DROP\_GIPK, 156  
ER\_DUPLICATED\_VALUE\_IN\_TYPE, 24  
ER\_DUPLICATE\_OPTION\_KEY, 92  
ER\_DUPLICATE\_SYS\_VAR, 537  
ER\_DUPLICATE\_TABLE\_LOCK, 93  
ER\_DUP\_ARGUMENT, 19  
ER\_DUP\_ENTRY, 7  
ER\_DUP\_ENTRY\_AUTOINCREMENT\_CASE, 41  
ER\_DUP\_ENTRY\_WITH\_KEY\_NAME, 42  
ER\_DUP\_FD\_OPEN\_FAILED, 281  
ER\_DUP\_FIELDNAME, 7  
ER\_DUP\_INDEX, 62  
ER\_DUP\_KEY, 4  
ER\_DUP\_KEYNAME, 7  
ER\_DUP\_LIST\_ENTRY, 71  
ER\_DUP\_SIGNAL\_SET, 46  
ER\_DUP\_UNIQUE, 15  
ER\_DUP\_UNKNOWN\_IN\_INDEX, 65  
ER\_EMPTY\_PIPELINE\_FOR\_ERROR\_LOG\_SERVICE, 107  
ER\_EMPTY\_PRIVILEGE\_NAME\_IGNORED, 590  
ER\_EMPTY\_QUERY, 8  
ER\_ENDING\_INIT, 535  
ER\_END\_INITFILE, 177  
ER\_ENFORCE\_GTID\_CONSISTENCY\_WARN\_WITH\_ONLINE, 80  
ER\_ENGINE\_ATTRIBUTE\_NOT\_SUPPORTED, 139  
ER\_ENGINE\_CANT\_DROP\_MISSING\_TABLE, 97  
ER\_ENGINE\_CANT\_DROP\_TABLE, 97  
ER\_ENGINE\_COST\_FAILED\_TO\_READ, 212  
ER\_ENGINE\_COST\_INVALID\_CONST\_CONSTANT\_FOR\_SE, 212  
ER\_ENGINE\_COST\_INVALID\_DEVICE\_TYPE\_FOR\_SE, 212  
ER\_ENGINE\_COST\_UNKNOWN\_COST\_CONSTANT, 212  
ER\_ENGINE\_COST\_UNKNOWN\_STORAGE\_ENGINE, 212  
ER\_ENGINE\_OUT\_OF\_MEMORY, 69  
ER\_ERRMSG\_CANT\_FIND\_FILE, 198  
ER\_ERRMSG\_CANT\_READ, 198  
ER\_ERRMSG\_LOADING\_55\_STYLE, 198  
ER\_ERRMSG\_MISSING\_IN\_FILE, 198  
ER\_ERRMSG\_OOM, 198  
ER\_ERRMSG\_REPLACEMENTS\_FAILED, 274  
ER\_ERRMSG\_REPLACEMENT\_DODGY, 274  
ER\_ERROR\_DURING\_COMMIT, 15  
ER\_ERROR\_DURING\_FLUSH\_LOGS, 16  
ER\_ERROR\_DURING\_FLUSH\_LOG\_COMMIT\_PHASE, 298  
ER\_ERROR\_DURING\_OPTIMIZE\_TABLE, 258  
ER\_ERROR\_DURING\_ROLLBACK, 15  
ER\_ERROR\_ENABLING\_KEYS, 258  
ER\_ERROR\_INFO\_FROM\_DA, 532  
ER\_ERROR\_IN\_TRIGGER\_BODY, 52  
ER\_ERROR\_IN\_UNKNOWN\_TRIGGER\_BODY, 52  
ER\_ERROR\_LOG\_DESTINATION\_NOT\_A\_FILE, 591  
ER\_ERROR\_ON\_MASTER, 68  
ER\_ERROR\_ON\_MODIFYING\_GTID\_EXECUTED\_TABLE, 84  
ER\_ERROR\_ON\_READ, 4  
ER\_ERROR\_ON\_RENAME, 5  
ER\_ERROR\_ON\_SOURCE, 68  
ER\_ERROR\_ON\_WRITE, 5  
ER\_ERROR\_WHEN\_EXECUTING\_COMMAND, 19  
ER\_EVENT\_ALREADY\_EXISTS, 40  
ER\_EVENT\_CANNOT ALTER IN THE PAST, 42  
ER\_EVENT\_CANNOT\_CREATE\_IN\_THE\_PAST, 42  
ER\_EVENT\_CANT\_FIND\_TIMEZONE, 260  
ER\_EVENT\_CANT\_GET\_CHARSET, 260  
ER\_EVENT\_CANT\_GET\_COLLATION, 261  
ER\_EVENT\_CANT\_GET\_LOCK\_FOR\_DROPPING\_EVENT, 264  
ER\_EVENT\_CANT\_GET\_TIMEZONE\_FROM\_FIELD, 260  
ER\_EVENT\_CANT\_INIT\_QUEUE, 167  
ER\_EVENT\_CANT\_OPEN\_TABLE\_MYSQL\_EVENT, 261  
ER\_EVENT\_CANT\_READ\_INDEX, 40  
ER\_EVENT\_DOES\_NOT\_EXIST, 40  
ER\_EVENT\_DROPPING, 214  
ER\_EVENT\_ENDS\_BEFORE\_STARTS, 40  
ER\_EVENT\_ERROR\_CREATING\_QUERY\_TO\_WRITE\_TO\_BINLOG, 264  
ER\_EVENT\_ERROR\_DURING\_COMPILATION, 214  
ER\_EVENT\_ERROR\_DURING\_EXECUTION\_FAILED, 167  
ER\_EVENT\_EXECUTION\_FAILED\_CANT\_AUTHENTICATE\_USER, 213  
ER\_EVENT\_EXECUTION\_FAILED\_USER\_LOST\_EVEN\_PRIVILEGE, 213  
ER\_EVENT\_EXEC\_TIME\_IN\_THE\_PAST, 40  
ER\_EVENT\_INTERVAL\_NOT\_POSITIVE\_OR\_TOO\_BIG, 40  
ER\_EVENT\_INVALID\_CREATION\_CTX, 43  
ER\_EVENT\_LAST\_EXECUTION, 167  
ER\_EVENT\_MESSAGE\_STACK, 167  
ER\_EVENT\_PURGING\_QUEUE, 167  
ER\_EVENT\_RECURSION\_FORBIDDEN, 42  
ER\_EVENT\_SAME\_NAME, 40

---

ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT_OBJECT, 264	ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY, 135
ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB, 264	ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST, 135
ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE, 264	ER_FAILED_TO_FIND_COLLATION_NAME, 280
ER_EVENT_SET_VAR_ERROR, 41	ER_FAILED_TO_FIND_DL_ENTRY, 276
ER_EVENT_UNABLE_TO_DROP_EVENT, 264	ER_FAILED_TO_FIND_LOCALE_NAME, 280
ER_EXCEEDED_MV_KEYS_NUM, 130	ER_FAILED_TO_FIND_MYSQLD_STATUS, 296
ER_EXCEEDED_MV_KEYS_SPACE, 130	ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE, 277
ER_EXCEPTIONS_WRITE_ERROR, 45	ER_FAILED_TO_GET_ABSOLUTE_PATH, 280
ER_EXCESS_ARGUMENTS, 177	ER_FAILED_TO_HANDLE_DEFAULTS_FILE, 537
ER_EXPIRE_LOGS_DAYS_IGNORED, 298	ER_FAILED_TO_INIT_SYS_VAR, 537
ER_EXPLAIN_NOT_SUPPORTED, 69	ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_C, 204
ER_FAILED_DEFAULT_ROLES, 89	ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THRE, 205
ER_FAILED_GET_DD_PROPERTY, 640	ER_FAILED_TO_LOCK_MEM, 176
ER_FAILED_READ_FROM_PAR_FILE, 50	ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES, 213
ER_FAILED_REVOKE_ROLE, 89	ER_FAILED_TO_OPEN_SHARED_LIBRARY, 276
ER_FAILED_ROLE_GRANT, 89	ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA, 285
ER_FAILED_SET_DD_PROPERTY, 640	ER_FAILED_TO_READ_FILE, 277
ER_FAILED_START_MYSQLD_DAEMON, 281	ER_FAILED_TO_REMOVE_TEMP_TABLE, 255
ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP, 286	ER_FAILED_TO_REPAIR_TABLE, 254
ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP, 285	ER_FAILED_TO_SET_PERSISTED_OPTIONS, 297
ER_FAILED_TO_ADD_RPL_FILTER, 292	ER_FAILED_TO_START_REPLICA_THREAD, 291
ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP, 285	ER_FAILED_TO_START_SLAVE_THREAD, 291
ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP_HASH, 285	ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE, 288
ER_FAILED_TO_ALLOCATE_SSL_BIO, 536	ER_FAILED_TO_UPDATE_RESOURCE_GROUP, 285
ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROL, 286	ER_FAILED_TO_WRITE_TO_FILE, 277
ER_FAILED_TO_BINLOG_DROP_EVENT, 291	ER_FAIL_CHROOT, 176
ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES, 292	ER_FAIL_SETGID, 175
ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE, 204	ER_FAIL_SETREGID, 176
ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_COPY, 204	ER_FAIL_SETREUID, 176
ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY, 291	ER_FAIL_SETUID, 175
ER_FAILED_TO_CREATE_CLONE_HANDLER, 293	ER_FEATURE_DISABLED, 24
ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THREAD, 204	ER_FEATURE_DISABLED_SEE_DOC, 84
ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE, 288	ER_FEATURE_NOT_AVAILABLE, 79
ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS, 216	ER_FEATURE_UNSUPPORTED, 103
ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE, 204	ER_FIELD_IN_GROUPING_NOT_GROUP_BY, 96
ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP, 285	ER_FIELD_IN_ORDER_NOT_SELECT, 74
	ER_FIELD_NOT_FOUND_PART_ERROR, 37
	ER_FIELD_SPECIFIED_TWICE, 11
	ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD, 47
	ER_FILEGROUP_OPTION_ONLY_ONCE, 39
	ER_FILESORT_TERMINATED, 279
	ER_FILE_CORRUPT, 68
	ER_FILE_EXISTS_DURING_UPGRADE, 261
	ER_FILE_EXISTS_ERROR, 9

---

---

ER\_FILE\_HAS\_OLD\_FORMAT, 278  
 ER\_FILE\_NOT\_FOUND, 4  
 ER\_FILE\_PRIVILEGE\_FOR\_REPLICATION\_CHECKS,  
 571  
 ER\_FILE\_TYPE\_UNKNOWN, 199  
 ER\_FILE\_USED, 5  
 ER\_FILSORT\_ABORT, 5  
 ER\_FIREWALL\_ACCESS\_DENIED, 313  
 ER\_FIREWALL\_DEPRECATED\_USER\_PROFILE,  
 601  
 ER\_FIREWALL\_FAILED\_TO\_READ\_FIREWALL\_TABLES,  
 312  
 ER\_FIREWALL\_FAILED\_TO\_REG\_DYNAMIC\_PRIVILEGES,  
 312  
 ER\_FIREWALL\_PFS\_TABLE\_REGISTER\_FAILED,  
 596  
 ER\_FIREWALL\_RECORDING\_STMT\_WAS\_TRUNCATED,  
 312  
 ER\_FIREWALL\_RECORDING\_STMT\_WITHOUT\_TEXT,  
 313  
 ER\_FIREWALL\_RELOADING\_CACHE, 313  
 ER\_FIREWALL\_RESET\_FOR\_USER, 313  
 ER\_FIREWALL\_SERVICES\_NOT\_ACQUIRED, 595  
 ER\_FIREWALL\_SKIPPED\_UNKNOWN\_USER\_MODE,  
 313  
 ER\_FIREWALL\_STATUS\_FLUSHED, 313  
 ER\_FIREWALL\_SUSPICIOUS\_STMT, 313  
 ER\_FIREWALL\_UDF\_REGISTER\_FAILED, 596  
 ER\_FIXING\_CLIENT\_CHARSET, 176  
 ER\_FK\_CANNOT\_CHANGE\_ENGINE, 116  
 ER\_FK\_CANNOT\_DROP\_PARENT, 110  
 ER\_FK\_CANNOT\_OPEN\_PARENT, 62  
 ER\_FK\_CANNOT\_USE\_VIRTUAL\_COLUMN, 111  
 ER\_FK\_COLUMN\_CANNOT\_CHANGE, 63  
 ER\_FK\_COLUMN\_CANNOT\_CHANGE\_CHILD, 63  
 ER\_FK\_COLUMN\_CANNOT\_DROP, 62  
 ER\_FK\_COLUMN\_CANNOT\_DROP\_CHILD, 62  
 ER\_FK\_COLUMN\_NOT\_NULL, 62  
 ER\_FK\_DEPTH\_EXCEEDED, 69  
 ER\_FK\_DUP\_NAME, 62  
 ER\_FK\_FAIL\_ADD\_SYSTEM, 62  
 ER\_FK\_INCOMPATIBLE\_COLUMNS, 116  
 ER\_FK\_INCORRECT\_OPTION, 62  
 ER\_FK\_NO\_COLUMN\_PARENT, 111  
 ER\_FK\_NO\_INDEX\_CHILD, 62  
 ER\_FK\_NO\_INDEX\_PARENT, 62  
 ER\_FORBID\_SCHEMA\_CHANGE, 34  
 ER\_FORCE\_CLOSE\_THREAD, 277  
 ER\_FORCING\_CLOSE, 8  
 ER\_FOREIGN\_DATA\_SOURCE\_DOESNT\_EXIST,  
 33  
 ER\_FOREIGN\_DATA\_STRING\_INVALID, 33  
 ER\_FOREIGN\_DATA\_STRING\_INVALID\_CANT\_CREATE,  
 128  
 33  
 ER\_FOREIGN\_DUPLICATE\_KEY\_OLD\_UNUSED, 40  
 ER\_FOREIGN\_DUPLICATE\_KEY\_WITHOUT\_CHILD\_INFO,  
 56  
 ER\_FOREIGN\_DUPLICATE\_KEY\_WITH\_CHILD\_INFO,  
 56  
 ER\_FOREIGN\_KEY\_ON\_PARTITIONED, 38  
 ER\_FOREIGN\_KEY\_WITH\_ATOMIC\_CREATE\_SELECT,  
 139  
 ER\_FOREIGN\_SERVER\_DOESNT\_EXIST, 36  
 ER\_FOREIGN\_SERVER\_EXISTS, 36  
 ER\_FOUND\_MISSING\_GTIDS, 387  
 ER\_FOUND\_ROWS\_WHILE\_REPAIRING, 258  
 ER\_FPARSER\_BAD\_HEADER, 28  
 ER\_FPARSER\_EOF\_IN\_COMMENT, 28  
 ER\_FPARSER\_EOF\_IN\_UNKNOWN\_PARAMETER,  
 28  
 ER\_FPARSER\_ERROR\_IN\_PARAMETER, 28  
 ER\_FPARSER\_TOO\_BIG\_FILE, 28  
 ER\_FSEEK\_FAIL, 30  
 ER\_FT\_BOOL\_SYNTAX\_INVALID, 171  
 ER\_FT\_MATCHING\_KEY\_NOT\_FOUND, 16  
 ER\_FULLTEXT\_FUNCTIONAL\_INDEX, 114  
 ER\_FULLTEXT\_NOT\_SUPPORTED\_WITH\_PARTITIONING,  
 56  
 ER\_FULLTEXT\_WITH\_ROLLUP, 152  
 ER\_FUNCTIONAL\_INDEX\_DATA\_IS\_TOO\_LONG,  
 130  
 ER\_FUNCTIONAL\_INDEX\_FUNCTION\_IS\_NOT\_ALLOWED,  
 114  
 ER\_FUNCTIONAL\_INDEX\_ON\_FIELD, 114  
 ER\_FUNCTIONAL\_INDEX\_ON\_JSON\_OR\_GEOMETRY\_FUNCTION,  
 113  
 ER\_FUNCTIONAL\_INDEX\_ON\_LOB, 114  
 ER\_FUNCTIONAL\_INDEX\_PRIMARY\_KEY, 113  
 ER\_FUNCTIONAL\_INDEX\_REF\_AUTO\_INCREMENT,  
 113  
 ER\_FUNCTIONAL\_INDEX\_ROW\_VALUE\_IS\_NOT\_ALLOWED,  
 118  
 ER\_FUNCTION\_DOES\_NOT\_SUPPORT\_CHARACTER\_SET,  
 140  
 ER\_FUNCTION\_NOT\_DEFINED, 12  
 ER\_FUNC\_INEXISTENT\_NAME\_COLLISION, 45  
 ER\_FUTURE\_DATE, 174  
 ER\_GENERATED\_COLUMN\_FUNCTION\_IS\_NOT\_ALLOWED,  
 78  
 ER\_GENERATED\_COLUMN\_NAMED\_FUNCTION\_IS\_NOT\_ALLOWED,  
 114  
 ER\_GENERATED\_COLUMN\_NON\_PRIOR, 79  
 ER\_GENERATED\_COLUMN\_REF\_AUTO\_INC, 79  
 ER\_GENERATED\_COLUMN\_ROW\_VALUE, 114  
 ER\_GENERATED\_COLUMN\_VARIABLES, 114  
 ER\_GEOMETRY\_IN\_UNKNOWN\_LENGTH\_UNIT,

---

ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE, 111	ER_GRP_OPERATION_NOT_ALLOWED_GR_MUST_STOP, 137
ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE, 111	ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_M, 370
ER_GET_ERRMSG, 25	ER_GRP_RPL_ADD_GRPSID_TO_GRPGTIDSID_MAP_ERR, 344
ER_GET_ERRNO, 5	ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_I, 356
ER_GET_ERRNO_FROM_STORAGE_ENGINE, 279	ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID, 356
ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER, 69	ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAIL, 355
ER_GET_TEMPORARY_ERRMSG, 25	ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FA, 356
ER_GIPK_COLUMN_ALTER_NOT_ALLOWED, 156	ER_GRP_RPL_ADD_GTID_TO_GRPGTID_EXECUTED_ERR, 344
ER_GIPK_COLUMN_EXISTS, 155	ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXE, 344
ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS, 155	ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_M, 603
ER_GIS_DATA_WRONG_ENDIANESS, 73	ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY, 358
ER_GIS_DIFFERENT_SRIDS, 72	ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED, 369
ER_GIS_DIFFERENT_SRIDS_AGGREGATION, 146	ER_GRP_RPL_APPENDING_DATA_TO_INTERNAL_CACHE, 362
ER_GIS_INVALID_DATA, 72	ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING, 595
ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED, 81	ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR, 343
ER_GIS_UNKNOWN_ERROR, 72	ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE, 374
ER_GIS_UNKNOWN_EXCEPTION, 72	ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED, 374
ER_GIS_UNSUPPORTED_ARGUMENT, 72	ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE, 374
ER_GLOBAL_CONN_LIMIT, 612	ER_GRP_RPL_APPLIER_INITIALIZED, 370
ER_GLOBAL_VARIABLE, 20	ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_TA, 370
ER_GLOBSTAT_CHANGE_DURING_QUERY, 131	ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNIN, 369
ER_GNO_EXHAUSTED, 57	ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED, 343
ER_GRANT_WRONG_HOST_OR_USER, 13	ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON, 368
ER_GROUPING_ON_TIMESTAMP_IN_DST, 131	ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED, 342
ER_GROUP_REPLICATION_APPLIER_INIT_ERROR, 78	ER_GRP_RPL_APPLIER_THD_KILLED, 342
ER_GROUP_REPLICATION_COMMAND_FAILURE, 103	ER_GRP_RPL_APPLIER_THD_SETUP_ERROR, 353
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_JOIN_ERROR, 78	ER_GRP_RPL_APPLIER_THD_START_ERROR, 353
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_SESSION_ERROR, 78	ER_GRP_RPL_APPLIER_THD_STOP_ERROR, 353
ER_GROUP_REPLICATION_CONFIGURATION, 78	ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT, 540
ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILURE, 157	ER_GRP_RPL_AUTO_INC_OFFSET_RESET, 354
ER_GROUP_REPLICATION_MAX_GROUP_SIZE, 86	
ER_GROUP_REPLICATION_PASSWORD_LENGTH, 138	
ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED, 204	
ER_GROUP_REPLICATION_RUNNING, 78	
ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIMEOUT, 78	
ER_GROUP_REPLICATION_USER_EMPTY_MSG, 138	
ER_GROUP_REPLICATION_USER_MANDATORY_MSG, 138	
ER_GRP_DELAYED_VCLE_LOGGING, 561	

---

ER_GRP_RPL_AUTO_INC_OFFSET_SET, 355	ER_GRP_RPL_CONFIGURATION_ACTION_START, 540
ER_GRP_RPL_AUTO_INC_RESET, 354	ER_GRP_RPL_CONFIG_RECOVERY, 358
ER_GRP_RPL_AUTO_INC_SET, 354	ER_GRP_RPL_CONFLICT_DETECTION_DISABLED, 347
ER_GRP_RPL_BINLOG_CHECKSUM_SET, 360	ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_T
ER_GRP_RPL_BINLOG_DISABLED, 370	371
ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP, 352	ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL, 357
ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED, 363	ER_GRP_RPL_CONTACT_WITH_SRV_FAILED, 356
ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG, 377	ER_GRP_RPL_COPY_FROM_EMPTY_STRING, 357
ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED, 343	ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR, 342
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE, 361	ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL, 359
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE, 361	ER_GRP_RPL_CREATE_SESSION_UNABLE, 357
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING, 361	ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM, 350
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING, 361	ER_GRP_RPL_DEBUG_OPTIONS, 376
ER_GRP_RPL_CANT_GENERATE_GTID, 345	ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_C, 558
ER_GRP_RPL_CANT_KILL_THREAD, 567	ER_GRP_RPL_DISABLE_READ_ONLY_FAILED, 349
ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED, 346	ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED, 347
ER_GRP_RPL_CANT_READ_GTID, 346	ER_GRP_RPL_DONOR_CONN_TERMINATION, 359
ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM, 347	ER_GRP_RPL_DONOR_SERVER_CONN, 359
ER_GRP_RPL_CERTIFICATE_SIZE_ERROR, 342	ER_GRP_RPL_DONOR_TRANS_INFO_ERROR, 344
ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE, 345	ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_E, 603
ER_GRP_RPL_CERTIFICATION_REC_PROCESS, 364	ER_GRP_RPL_ENABLE_READ_ONLY_FAILED, 349
ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR, 347	ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET, 344
ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED, 348	ER_GRP_RPL_ERROR_FETCHING_GTID_SET, 344
ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING, 539	ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO, 342
ER_GRP_RPL_CHECK_STATUS_TABLE, 359	ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION, 539
ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR, 567	ER_GRP_RPL_ERROR_MSG, 320
ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR, 566	ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL, 553
ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO, 370	ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING, 540
ER_GRP_RPL_CONFIGURATION_ACTION_END, 540	ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSG, 343
ER_GRP_RPL_CONFIGURATION_ACTION_ERROR, 540	ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER, 611
ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR, 540	ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER, 611
ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION, 540	ER_GRP_RPL_ERROR_STOPPING_CHANNELS, 343
	ER_GRP_RPL_ERROR_VERIFYING_SIDNO, 345
	ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_DE



ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR, 358	ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_O 368
ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER 358	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME 363
ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR, 358	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OB 368
ER_GRP_RPL_EVENT_HANDLING_ERROR, 342	ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR 361
ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE, 350	ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODU 361
ER_GRP_RPL_EXIT_GRP_GCS_ERROR, 376	ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODU 361
ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING 374	ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENO 361
ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP 360	ER_GRP_RPL_FAILED_TO_START_ON_BOOT, 368
ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATE 360	ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WIT 366
ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION 366	ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVE 365
ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GRP, 366	ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL 368
ER_GRP_RPL_FAILED_TO_CREATE_COMMIT_CACHE, 363	ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE, 369
ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT, 362	ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE, 369
ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE, 367	ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE, 369
ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY 365	ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGAT 148
ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET, 362	ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT E 606
ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET, 362	ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATI 606
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP, 369	ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE D 606
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW, 602	ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER JO 606
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER, 374	ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DEFA 606
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE, 369	ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY 607
ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGIN 366	ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY 606
ER_GRP_RPL_FAILED_TO_INIT_HANDLER, 368	ER_GRP_RPL_FAILOVER_REGISTER_MESSAGE_LISTENE 606
ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON, 550	ER_GRP_RPL_FATAL_REC_PROCESS, 364
ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE, 622	ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAIL 355
ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP 360	ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED, 355
ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME, 369	ER_GRP_RPL_FETCH_LOG_EVENT_FAILED, 356
ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE 602	ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED, 355
ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE, 368	ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED, 355
	SERVER, 355

ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED, 355	ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR, 351
ER_GRP_RPL_FETCH_TRANS_DATA_FAILED, 353	ER_GRP_RPL_GTID_MODE_OFF, 370
ER_GRP_RPL_FETCH_TRANS_SIDNO_ERROR, 345	ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR, 566
ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED, 356	ER_GRP_RPL_GTID_SET_EXTRACT_ERROR, 351
ER_GRP_RPL_FINISHED_AUTO_REJOIN, 558	ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOVER, 552
ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED, 354	ER_GRP_RPL_HAS_STARTED, 634
ER_GRP_RPL_FLOW_CONTROL_STATS, 378	ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_APP, 371
ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_GRP_QUOTA, 373	ER_GRP_RPL_INVALID_BINLOG_FORMAT, 360
ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_GRP_QUOTA, 372	ER_GRP_RPL_INVALID_DEBUG_OPTIONS, 376
ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX, 372	ER_GRP_RPL_INVALID_GTID_SET, 345
ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY, 365	ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING, 373
ER_GRP_RPL_FORCE_MEMBERS_SET_UPDATE_NOT_ALLOWED, 373	ER_GRP_RPL_INVALID_TRANS_WRITE_SET_EXTRACTION_V, 371
ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING, 553	ER_GRP_RPL_IS_STARTING, 582
ER_GRP_RPL_FORCE_MEMBER_VALUE_SET, 377	ER_GRP_RPL_IS_STOPPED, 367
ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR, 377	ER_GRP_RPL_IS_STOPPING, 367
ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT, 377	ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING, 539
ER_GRP_RPL_GCS_GR_ERROR_MSG, 378	ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING, 539
ER_GRP_RPL_GCS_INTERFACE_ERROR, 377	ER_GRP_RPL_KILLED_FAILED_ID, 357
ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION, 376	ER_GRP_RPL_KILLED_SESSION_ID, 357
ER_GRP_RPL_GROUP_NAME_PARSE_ERROR, 344	ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR, 351
ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_LOG, 601	ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET, 371
ER_GRP_RPL_GRP_CHANGE_INFO_EXTRACT_ERROR, 350	ER_GRP_RPL_LOG_SLAVE_UPDATES_NOT_SET, 370
ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED, 376	ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_G, 527
ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONFLICT, 373	ER_GRP_RPL_MASTER_INFO_REPO_MUST_BE_TABLE, 371
ER_GRP_RPL_GRP_MEMBER_OFFLINE, 377	ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED, 358
ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID, 372	ER_GRP_RPL_MEMBER_ACTIONS_RESET, 600
ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_REPO_UUID, 594	ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION, 600
ER_GRP_RPL_GRP_NAME_IS_TOO_LONG, 372	ER_GRP_RPL_MEMBER_ACTION_DISABLED, 600
ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY, 372	ER_GRP_RPL_MEMBER_ACTION_ENABLED, 600
ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPLETE, 602	ER_GRP_RPL_MEMBER_ACTION_FAILURE, 599
ER_GRP_RPL_GTID_ALREADY_USED, 342	ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE, 599
	ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE_DATA, 599

---

ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER_JOIN,	347
600	ER_GRP_RPL_MEMBER_JOINING_DISCARDED, 347
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER_JOIN,	348
600	ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVE,	361
599	ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED
ER_GRP_RPL_MEMBER_ACTION_TRIGGERED,	605
599	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ER
ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT_CONFIGURATION,	605
600	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ER
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS,	349
599	ER_GRP_RPL_NEEDS_INNODB_TABLE, 354
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_MEMBER_JOIN,	356
600	ER_GRP_RPL_NEW_PRIMARY_ELECTED, 349
ER_GRP_RPL_MEMBER_ADDED, 349	ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED
ER_GRP_RPL_MEMBER_ALREADY_EXISTS, 350	ER_GRP_RPL_NO_MEMBER_JOIN,
ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP,	352
352	ER_GRP_RPL_NO_POSSIBLE_RECOVERY, 567
ER_GRP_RPL_MEMBER_CHANGE, 349	ER_GRP_RPL_NO_STAGE_SERVICE, 541
ER_GRP_RPL_MEMBER_CONF_INFO, 366	ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM, 350
ER_GRP_RPL_MEMBER_CONTACT_RESTORED,	348
348	ER_GRP_RPL_NO_VALID_DONOR, 358
ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR,	349
349	ER_GRP_RPL_NULL_PACKET, 346
ER_GRP_RPL_MEMBER_EXPELLED, 349	ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE, 364
ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST,	641
641	ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION
ER_GRP_RPL_MEMBER_LEFT_GRP, 349	ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GRP,
ER_GRP_RPL_MEMBER_NOT_FOUND, 358	611
ER_GRP_RPL_MEMBER_REMOVED, 348	ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_OLD
ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP,	366
366	632
ER_GRP_RPL_MEMBER_STATS_INFO, 377	ER_GRP_RPL_PIPELINE_CREATE_FAILED, 378
ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR,	352
352	ER_GRP_RPL_PIPELINE_FLUSH_FAIL, 378
ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP,	352
352	ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ,
ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP,	351
351	378
ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE,	351
351	ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE,
ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE,	563
563	ER_GRP_RPL_PLUGIN_ABORT, 536
ER_GRP_RPL_MEM_ONLINE, 348	ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON
ER_GRP_RPL_MEM_REACHABLE, 348	365
ER_GRP_RPL_MEM_UNREACHABLE, 348	ER_GRP_RPL_PREV_REC_SESSION_RUNNING,
ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR,	570
570	363
ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE,	132
132	ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR,
ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR,	539
539	ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR,
ER_GRP_RPL_MISSING_GRP_RPL_APPLIER, 347	364
ER_GRP_RPL_MODULE_TERMINATE_ERROR, 372	541
	ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED, 354
	ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP,
	349
	ER_GRP_RPL_PROCESS_GTID_SET_ERROR, 346
	ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERF
	346
	ER_GRP_RPL_PURGE_APPLIER_LOGS, 352
	ER_GRP_RPL_PURGE_REC, 359
	ER_GRP_RPL_QUERY_FAIL, 357
	ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER,
	363
	ER_GRP_RPL_READ_UNABLE_FOR_SUPER_READ_ONLY,
	364

---

ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS, 346	ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT_S 372
ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING, 145	ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_MEMBE 354
ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT, 582	ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN, 354
ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IPS, 583	ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE, 568
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID, 582	ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECONDARY_ 607
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_ENDPOINT, 583	ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_TO_LE 367
ER_GRP_RPL_RECOVERY_EVAL_ERROR, 567	ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR, 352
ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMEOUT, 368	ER_GRP_RPL_RESET_OUT_ON_SHUTDOWN, 353
ER_GRP_RPL_RECOVERY_STRAT_CHOICE, 567	ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMBER, 353
ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED, 567	ER_GRP_RPL_SEND_STATS_ERROR, 377
ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD, 567	ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED, 550
ER_GRP_RPL_RECOVERY_STRAT_FALLBACK, 567	ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAIL 552
ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK, 568	ER_GRP_RPL_SERVER_ALREADY_LEFT, 367
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES, 551	ER_GRP_RPL_SERVER_CONN_ERROR, 344
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_SYNC, 551	ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING, 367
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFORE_EXECUTION, 551	ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO_E 559
ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_WRITER, 363	ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERR 376
ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_READ_ONLY, 362	ER_GRP_RPL_SERVER_UDF_ERROR, 541
ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_WRITER, 363	ER_GRP_RPL_SERVER_WORKING_AS_SECONDARY, 365
ER_GRP_RPL_RELAY_LOG_INFO_REPO_MUST_BE_TABLE, 371	ER_GRP_RPL_SESSION_OPEN_FAILED, 349
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES, 551	ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER_F 376
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR_SYNC_BEFORE_EXECUTION, 552	ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER, 511
ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPARE, 550	ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER, 511
ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT, 379	ER_GRP_RPL_SET_STABLE_TRANS_ERROR, 346
ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED, 379	ER_GRP_RPL_SET_SYNC_BEFORE_EXECUTE, 343
ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN, 353	ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_WITH_U 572
ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT, 379	ER_GRP_RPL_SKIP_COMPUTATION_TRANS_COMMITTED, 576
ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED, 379	ER_GRP_RPL_SLAVE_APPLIER_THREAD_ERROR_OUT, 579
	ER_GRP_RPL_SLAVE_APPLIER_THREAD_UNBLOCKED, 579
	ER_GRP_RPL_SLAVE_IO_THD_PRIMARY_UNKNOWN, 353
	ER_GRP_RPL_SLAVE_IO_THREAD_ERROR_OUT, 379
	ER_GRP_RPL_SLAVE_IO_THREAD_ERROR_OUT, 379

---

ER_GRP_RPL_SLAVE_IO_THREAD_UNBLOCKED, 379	ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP, 366
ER_GRP_RPL_SLAVE_PRESERVE_COMMIT_ORDER_NOT_SUPPORTED, 371	ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN, 590
ER_GRP_RPL_SLAVE_SQL_THD_ON_SECONDARY_MEMBER, 354	ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN, 558
ER_GRP_RPL_SLAVE_SQL_THD_PRIMARY_UNKNOWN, 353	ER_GRP_RPL_TIMEOUT_RECEIVING_VIEW_CHANGE_ON, 367
ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_CLONE, 568	ER_GRP_RPL_TRANS_GREATER_THAN_GRP_MEMBER, 351
ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_SECONDARY_MEMBER, 607	ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP_MEMBER, 351
ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED, 374	ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT, 362
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECONDARY_TRANSACTION, 375	ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOT_SUPPORTED, 361
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECONDARY_TRANSACTION, 375	ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_TRANSACTION, 352
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_ON_SECONDARY, 374	ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AFFECTED_SERVER, 550
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY, 374	ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLER_SERVER, 551
ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SECONDARY, 375	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED_ON_SECONDARY, 552
ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SECONDARY, 375	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED_ON_SECONDARY, 551
ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER, 375	ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION_ON_SECONDARY, 552
ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONNECT, 375	ER_GRP_RPL_UDF_ERROR, 131
ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE, 375	ER_GRP_RPL_UDF_REGISTER_ERROR, 541
ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED, 374	ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR, 541
ER_GRP_RPL_SRV_BLOCKED, 348	ER_GRP_RPL_UDF_UNREGISTER_ERROR, 541
ER_GRP_RPL_SRV_BLOCKED_FOR_SECS, 348	ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS, 365
ER_GRP_RPL_SRV_GTID_WAIT_ERROR, 561	ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET, 378
ER_GRP_RPL_SRV_NOT_ONLINE, 347	ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT, 378
ER_GRP_RPL_SRV_ONLINE, 347	ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_RECORD, 364
ER_GRP_RPL_SRV_PRIMARY_MEM, 350	ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS, 364
ER_GRP_RPL_SRV_SECONDARY_MEM, 350	ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE, 370
ER_GRP_RPL_SRV_WAIT_TIME_OUT, 356	ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLIER, 359
ER_GRP_RPL_SSL_DISABLED, 370	ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FACTOR, 360
ER_GRP_RPL_STARTED_AUTO_REJOIN, 558	ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE, 365
ER_GRP_RPL_STARTING_GRP_REC, 359	ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS, 365
ER_GRP_RPL_START_FAILED, 351	ER_GRP_RPL_UNBLOCK_WAITING_THD, 342
ER_GRP_RPL_START_GRP_RPL_FAILED, 357	ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE, 373
ER_GRP_RPL_STOPPING_GRP_REC, 359	
ER_GRP_RPL_STOP_REP_CHANNEL, 378	
ER_GRP_RPL_SUPER_READ_OFF, 357	
ER_GRP_RPL_SUPER_READ_ON, 357	
ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR, 350	
ER_GRP_RPL_SUPPORTS_ONLY_ONE_FORCE_MEMBER, 373	

---

ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_MEMBER	ER_GRP_MEMBER_EXECUTED_WAS_UPDATED, 278
376	ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME
ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION,	58
361	ER_GTID_MODE_OFF, 74
ER_GRP_RPL_UPDATE_GRPGTID_EXECUTED_ERROR,	ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY
344	58
ER_GRP_RPL_UPDATE_GRPGTID_VIEW_CHANGE_UUID_ERROR,	ER_GTID_NEXT_TYPE_CAN_BE_AUTOMATIC_IF_GTID_NEXT_LIST_IS_EMPTY
602	57
ER_GRP_RPL_UPDATE_GTID_SET_ERROR,	345
ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANSACTION_ERROR,	ER_GTID_NEXT_TYPE_UNDEFINED_GROUP, 63
345	ER_GTID_NEXT_TYPE_UNDEFINED_GTID, 63
ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED,	ER_GTID_PURGED_WAS_CHANGED, 63
355	ER_GTID_PURGED_WAS_UPDATED, 278
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VERSION_ERROR,	ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION
345	116
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_VERSION_ERROR,	ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_TRANSACTION
343	67
ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRPGTID,	ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_TRANSACTION
602	57
ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE,	ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_IN_TRANSACTION
147	58
ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID,	601
ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANOTHER,	ER_GTID_UNSAFE_CREATE_SELECT, 58
601	ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE, ANONYMOUS_TO_GTID_UUID,
ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR,	ER_HANDLERTON_OOM, 188
602	ER_HANDSHAKE_ERROR, 6
ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME,	ER_HEALTH_ERROR, 594
601	ER_HEALTH_INFO, 594
ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE,	ER_HEALTH_WARNING, 594
ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED,	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1, 595
551	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2, 595
ER_GRP_RPL_WHILE_SENDING_MSG_REC,	595
ER_GRP_RPL_WHILE_STOPPING_REP_CHANNEL,	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3, 595
364	595
ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED,	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1, 610
360	610
ER_GRP_RPL_WRITE_TO_BINLOG_CACHE_FAILED,	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2, 610
362	610
ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FILE_FAILED,	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3, 610
362	610
ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN,	ER_HOSTNAME, 35
118	ER_HOSTNAME_DOESNT_RESOLVE_TO, 168
ER_GRP_TRX_CONSISTENCY_BEFORE,	118
ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED,	ER_HOSTNAME_RESEMBLES_IPV4, 168
118	ER_HOSTNAME_TOO_LONG, 138
ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED,	ER_HOSTNAME_TRUNCATED, 584
118	ER_HOST_IS_BLOCKED, 12
ER_GR_ELECTED_PRIMARY_GTID_INFORMATION,	ER_HOST_NOT_PRIVILEGED, 12
574	ER_HYPERGRAPH_NOT_SUPPORTED_YET, 142
ER_GR_HOLD_KILLED,	116
ER_GR_HOLD_MEMBER_STATUS_ERROR,	117
ER_GR_HOLD_WAIT_TIMEOUT,	116
ER_GTID_ALREADY_ADDED_BY_USER,	204
ER_GTID_EXECUTED_WAS_CHANGED,	63
	ER_IB_BUFFER_POOL_FULL, 628
	ER_IB_BUFFER_POOL_OVERUSE, 628
	ER_IB_BULK_FLUSHER_INFO, 628
	ER_IB_BULK_LOAD_MERGE_FAIL, 631
	ER_IB_BULK_LOAD_SUBTREE_INFO, 628
	ER_IB_BULK_LOAD_THREAD_FAIL, 631

---

ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES,	584	ER_IB_ERR_ZLIB_DATA_ERROR,	588
ER_IB_CLONE_GTID_PERSIST,	406	ER_IB_ERR_ZLIB_MEM_ERROR,	588
ER_IB_CLONE_INTERNAL,	404	ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED,	587
ER_IB_CLONE_NON_INNODB_TABLE,	566	ER_IB_ERR_ZLIB_UNKNOWN_ERROR,	588
ER_IB_CLONE_OPERATION,	566	ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE,	586
ER_IB_CLONE_PUNCH_HOLE,	405	ER_IB_HIDDEN_NAME_CONFLICT,	632
ER_IB_CLONE_RESTART,	566	ER_IB_INDEX_BUILDER_DONE,	634
ER_IB_CLONE_SQL,	405	ER_IB_INDEX_BUILDER_INIT,	634
ER_IB_CLONE_START_STOP,	566	ER_IB_INDEX_LOADER_DONE,	633
ER_IB_CLONE_STATUS_FILE,	405	ER_IB_INDEX_LOG_VERSION_MISMATCH,	634
ER_IB_CLONE_TIMEOUT,	405	ER_IB_INDEX_PART_TOO_LONG,	642
ER_IB_CLONE_USER_DATA,	566	ER_IB_INNODB_TBSP_OUT_OF_SPACE,	595
ER_IB_CLONE_VALIDATE,	405	ER_IB_LOAD_BULK_CONCURRENCY_REDUCED,	631
ER_IB_DBLWR_BYTES_INFO,	615	ER_IB_LOB_ROLLBACK_INDEX_LEN,	572
ER_IB_DBLWR_DECOMPRESS_FAILED,	591	ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION,	585
ER_IB_DBLWR_DECRYPT_FAILED,	591	ER_IB_LONG_AHI_DISABLE_WAIT,	408
ER_IB_DBLWR_KEY_MISSING,	591	ER_IB_MSG_0,	389
ER_IB_DDL_CONVERT_HEAP_NOT_FOUND,	640	ER_IB_MSG_1,	389
ER_IB_DICT_INVALID_COLUMN_POSITION,	632	ER_IB_MSG_10,	390
ER_IB_DICT_LOG_TABLE_INFO,	633	ER_IB_MSG_100,	399
ER_IB_DUPLICATE_KEY,	628	ER_IB_MSG_1000,	494
ER_IB_ERR_DDL_LOG_INSERT_FAILURE,	585	ER_IB_MSG_1001,	494
ER_IB_ERR_FOUND_N_DUPLICATE_KEYS,	588	ER_IB_MSG_1002,	494
ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER,	588	ER_IB_MSG_1003,	494
ER_IB_ERR_INDEX_DUPLICATE_KEY,	588	ER_IB_MSG_1004,	494
ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER,	588	ER_IB_MSG_1005,	494
ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW,	587	ER_IB_MSG_1006,	494
ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER,	587	ER_IB_MSG_1007,	495
ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED,	604	ER_IB_MSG_1008,	495
ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE_BUFFER,	581	ER_IB_MSG_1009,	495
ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT,	581	ER_IB_MSG_101,	399
ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED,	581	ER_IB_MSG_1010,	495
ER_IB_ERR_PARALLEL_READ_OOM,	588	ER_IB_MSG_1011,	495
ER_IB_ERR_RECOVERY_REDO_DISABLED,	583	ER_IB_MSG_1012,	495
ER_IB_ERR_SCHED_SETAFFINITY_FAILED,	587	ER_IB_MSG_1013,	495
ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMLOCK,	586	ER_IB_MSG_1014,	495
ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST,	586	ER_IB_MSG_1015,	495
ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY,	586	ER_IB_MSG_1016,	495
ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATAFILE,	586	ER_IB_MSG_1017,	496
ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE,	587	ER_IB_MSG_1018,	496
ER_IB_ERR_ZLIB_BUF_ERROR,	587	ER_IB_MSG_1019,	496
		ER_IB_MSG_102,	400
		ER_IB_MSG_1020,	496
		ER_IB_MSG_1021,	496
		ER_IB_MSG_1022,	496
		ER_IB_MSG_1023,	496
		ER_IB_MSG_1024,	496
		ER_IB_MSG_1025,	496
		ER_IB_MSG_1026,	496
		ER_IB_MSG_1027,	497
		ER_IB_MSG_1028,	497

---

---

ER\_IB\_MSG\_1029, 497  
ER\_IB\_MSG\_103, 400  
ER\_IB\_MSG\_1030, 497  
ER\_IB\_MSG\_1031, 497  
ER\_IB\_MSG\_1032, 497  
ER\_IB\_MSG\_1033, 497  
ER\_IB\_MSG\_1034, 497  
ER\_IB\_MSG\_1035, 497  
ER\_IB\_MSG\_1036, 497  
ER\_IB\_MSG\_1037, 498  
ER\_IB\_MSG\_1038, 498  
ER\_IB\_MSG\_1039, 498  
ER\_IB\_MSG\_104, 400  
ER\_IB\_MSG\_1040, 498  
ER\_IB\_MSG\_1041, 498  
ER\_IB\_MSG\_1042, 498  
ER\_IB\_MSG\_1043, 498  
ER\_IB\_MSG\_1044, 498  
ER\_IB\_MSG\_1045, 498  
ER\_IB\_MSG\_1046, 498  
ER\_IB\_MSG\_1047, 499  
ER\_IB\_MSG\_1048, 499  
ER\_IB\_MSG\_1049, 499  
ER\_IB\_MSG\_105, 400  
ER\_IB\_MSG\_1050, 499  
ER\_IB\_MSG\_1051, 499  
ER\_IB\_MSG\_1052, 499  
ER\_IB\_MSG\_1053, 499  
ER\_IB\_MSG\_1054, 499  
ER\_IB\_MSG\_1055, 499  
ER\_IB\_MSG\_1056, 500  
ER\_IB\_MSG\_1057, 500  
ER\_IB\_MSG\_1058, 500  
ER\_IB\_MSG\_1059, 500  
ER\_IB\_MSG\_106, 400  
ER\_IB\_MSG\_1060, 500  
ER\_IB\_MSG\_1061, 500  
ER\_IB\_MSG\_1062, 500  
ER\_IB\_MSG\_1063, 500  
ER\_IB\_MSG\_1064, 501  
ER\_IB\_MSG\_1065, 501  
ER\_IB\_MSG\_1066, 501  
ER\_IB\_MSG\_1067, 501  
ER\_IB\_MSG\_1068, 501  
ER\_IB\_MSG\_1069, 501  
ER\_IB\_MSG\_107, 400  
ER\_IB\_MSG\_1070, 502  
ER\_IB\_MSG\_1071, 502  
ER\_IB\_MSG\_1072, 502  
ER\_IB\_MSG\_1073, 502  
ER\_IB\_MSG\_1074, 502  
ER\_IB\_MSG\_1075, 502  
ER\_IB\_MSG\_1076, 502  
ER\_IB\_MSG\_1077, 502

ER\_IB\_MSG\_1078, 502  
ER\_IB\_MSG\_1079, 503  
ER\_IB\_MSG\_108, 400  
ER\_IB\_MSG\_1080, 503  
ER\_IB\_MSG\_1081, 503  
ER\_IB\_MSG\_1082, 503  
ER\_IB\_MSG\_1083, 503  
ER\_IB\_MSG\_1084, 503  
ER\_IB\_MSG\_1085, 503  
ER\_IB\_MSG\_1086, 503  
ER\_IB\_MSG\_1087, 504  
ER\_IB\_MSG\_1088, 504  
ER\_IB\_MSG\_1089, 504  
ER\_IB\_MSG\_109, 400  
ER\_IB\_MSG\_1090, 504  
ER\_IB\_MSG\_1091, 504  
ER\_IB\_MSG\_1092, 504  
ER\_IB\_MSG\_1093, 504  
ER\_IB\_MSG\_1094, 504  
ER\_IB\_MSG\_1095, 504  
ER\_IB\_MSG\_1096, 504  
ER\_IB\_MSG\_1097, 505  
ER\_IB\_MSG\_1098, 505  
ER\_IB\_MSG\_1099, 505  
ER\_IB\_MSG\_11, 390  
ER\_IB\_MSG\_110, 400  
ER\_IB\_MSG\_1100, 505  
ER\_IB\_MSG\_1101, 505  
ER\_IB\_MSG\_1102, 505  
ER\_IB\_MSG\_1103, 505  
ER\_IB\_MSG\_1104, 505  
ER\_IB\_MSG\_1105, 505  
ER\_IB\_MSG\_1106, 505  
ER\_IB\_MSG\_1107, 506  
ER\_IB\_MSG\_1108, 506  
ER\_IB\_MSG\_1109, 506  
ER\_IB\_MSG\_111, 400  
ER\_IB\_MSG\_1110, 506  
ER\_IB\_MSG\_1111, 506  
ER\_IB\_MSG\_1112, 506  
ER\_IB\_MSG\_1113, 506  
ER\_IB\_MSG\_1114, 506  
ER\_IB\_MSG\_1115, 506  
ER\_IB\_MSG\_1116, 507  
ER\_IB\_MSG\_1117, 507  
ER\_IB\_MSG\_1118, 507  
ER\_IB\_MSG\_1119, 507  
ER\_IB\_MSG\_112, 401  
ER\_IB\_MSG\_1120, 507  
ER\_IB\_MSG\_1121, 507  
ER\_IB\_MSG\_1122, 507  
ER\_IB\_MSG\_1123, 507  
ER\_IB\_MSG\_1124, 507  
ER\_IB\_MSG\_1125, 508



---

ER_IB_MSG_1126, 508	ER_IB_MSG_1175, 514
ER_IB_MSG_1127, 508	ER_IB_MSG_1176, 514
ER_IB_MSG_1128, 508	ER_IB_MSG_1177, 515
ER_IB_MSG_1129, 508	ER_IB_MSG_1178, 515
ER_IB_MSG_113, 401	ER_IB_MSG_1179, 515
ER_IB_MSG_1130, 508	ER_IB_MSG_118, 401
ER_IB_MSG_1131, 508	ER_IB_MSG_1180, 515
ER_IB_MSG_1132, 508	ER_IB_MSG_1181, 515
ER_IB_MSG_1133, 508	ER_IB_MSG_1182, 515
ER_IB_MSG_1134, 509	ER_IB_MSG_1183, 515
ER_IB_MSG_1135, 509	ER_IB_MSG_1184, 515
ER_IB_MSG_1136, 509	ER_IB_MSG_1185, 515
ER_IB_MSG_1137, 509	ER_IB_MSG_1186, 515
ER_IB_MSG_1138, 509	ER_IB_MSG_1187, 516
ER_IB_MSG_1139, 510	ER_IB_MSG_1188, 516
ER_IB_MSG_114, 401	ER_IB_MSG_1189, 516
ER_IB_MSG_1140, 510	ER_IB_MSG_119, 401
ER_IB_MSG_1141, 510	ER_IB_MSG_1190, 516
ER_IB_MSG_1142, 510	ER_IB_MSG_1191, 516
ER_IB_MSG_1143, 510	ER_IB_MSG_1192, 516
ER_IB_MSG_1144, 510	ER_IB_MSG_1193, 516
ER_IB_MSG_1145, 511	ER_IB_MSG_1194, 516
ER_IB_MSG_1146, 511	ER_IB_MSG_1195, 516
ER_IB_MSG_1147, 511	ER_IB_MSG_1196, 517
ER_IB_MSG_1148, 511	ER_IB_MSG_1197, 517
ER_IB_MSG_1149, 511	ER_IB_MSG_1198, 517
ER_IB_MSG_115, 401	ER_IB_MSG_1199, 517
ER_IB_MSG_1150, 511	ER_IB_MSG_12, 391
ER_IB_MSG_1151, 511	ER_IB_MSG_120, 401
ER_IB_MSG_1152, 511	ER_IB_MSG_1200, 517
ER_IB_MSG_1153, 511	ER_IB_MSG_1201, 517
ER_IB_MSG_1154, 512	ER_IB_MSG_1202, 517
ER_IB_MSG_1155, 512	ER_IB_MSG_1203, 517
ER_IB_MSG_1156, 512	ER_IB_MSG_1204, 517
ER_IB_MSG_1157, 512	ER_IB_MSG_1205, 517
ER_IB_MSG_1158, 512	ER_IB_MSG_1206, 518
ER_IB_MSG_1159, 512	ER_IB_MSG_1207, 518
ER_IB_MSG_116, 401	ER_IB_MSG_1208, 518
ER_IB_MSG_1160, 512	ER_IB_MSG_1209, 518
ER_IB_MSG_1161, 512	ER_IB_MSG_121, 401
ER_IB_MSG_1162, 512	ER_IB_MSG_1210, 518
ER_IB_MSG_1163, 512	ER_IB_MSG_1211, 518
ER_IB_MSG_1164, 513	ER_IB_MSG_1212, 518
ER_IB_MSG_1165, 513	ER_IB_MSG_1213, 518
ER_IB_MSG_1166, 513	ER_IB_MSG_1214, 518
ER_IB_MSG_1167, 513	ER_IB_MSG_1215, 518
ER_IB_MSG_1168, 513	ER_IB_MSG_1216, 519
ER_IB_MSG_1169, 513	ER_IB_MSG_1217, 519
ER_IB_MSG_117, 401	ER_IB_MSG_1218, 519
ER_IB_MSG_1170, 513	ER_IB_MSG_1219, 519
ER_IB_MSG_1171, 514	ER_IB_MSG_122, 402
ER_IB_MSG_1172, 514	ER_IB_MSG_1220, 519
ER_IB_MSG_1173, 514	ER_IB_MSG_1221, 519
ER_IB_MSG_1174, 514	ER_IB_MSG_1222, 519

ER\_IB\_MSG\_1223, 519  
ER\_IB\_MSG\_1224, 520  
ER\_IB\_MSG\_1225, 520  
ER\_IB\_MSG\_1226, 520  
ER\_IB\_MSG\_1227, 520  
ER\_IB\_MSG\_1228, 520  
ER\_IB\_MSG\_1229, 520  
ER\_IB\_MSG\_123, 402  
ER\_IB\_MSG\_1230, 520  
ER\_IB\_MSG\_1231, 520  
ER\_IB\_MSG\_1232, 520  
ER\_IB\_MSG\_1233, 520  
ER\_IB\_MSG\_1234, 521  
ER\_IB\_MSG\_1235, 521  
ER\_IB\_MSG\_1236, 521  
ER\_IB\_MSG\_1237, 521  
ER\_IB\_MSG\_1238, 521  
ER\_IB\_MSG\_1239, 521  
ER\_IB\_MSG\_124, 402  
ER\_IB\_MSG\_1240, 522  
ER\_IB\_MSG\_1241, 522  
ER\_IB\_MSG\_1242, 522  
ER\_IB\_MSG\_1243, 522  
ER\_IB\_MSG\_1244, 522  
ER\_IB\_MSG\_1245, 522  
ER\_IB\_MSG\_1246, 522  
ER\_IB\_MSG\_1247, 522  
ER\_IB\_MSG\_1248, 523  
ER\_IB\_MSG\_1249, 523  
ER\_IB\_MSG\_125, 402  
ER\_IB\_MSG\_1250, 523  
ER\_IB\_MSG\_1251, 523  
ER\_IB\_MSG\_1252, 523  
ER\_IB\_MSG\_1253, 523  
ER\_IB\_MSG\_1254, 523  
ER\_IB\_MSG\_1255, 523  
ER\_IB\_MSG\_1256, 523  
ER\_IB\_MSG\_1257, 524  
ER\_IB\_MSG\_1258, 524  
ER\_IB\_MSG\_1259, 524  
ER\_IB\_MSG\_126, 402  
ER\_IB\_MSG\_1260, 524  
ER\_IB\_MSG\_1261, 524  
ER\_IB\_MSG\_1262, 524  
ER\_IB\_MSG\_1263, 524  
ER\_IB\_MSG\_1264, 524  
ER\_IB\_MSG\_1265, 524  
ER\_IB\_MSG\_1266, 525  
ER\_IB\_MSG\_1267, 525  
ER\_IB\_MSG\_1268, 525  
ER\_IB\_MSG\_1269, 525  
ER\_IB\_MSG\_127, 402  
ER\_IB\_MSG\_1270, 525  
ER\_IB\_MSG\_1271, 535

ER\_IB\_MSG\_1272, 535  
ER\_IB\_MSG\_1273, 536  
ER\_IB\_MSG\_1274, 537  
ER\_IB\_MSG\_1275, 537  
ER\_IB\_MSG\_1276, 537  
ER\_IB\_MSG\_1277, 538  
ER\_IB\_MSG\_1278, 538  
ER\_IB\_MSG\_1279, 538  
ER\_IB\_MSG\_128, 402  
ER\_IB\_MSG\_1280, 538  
ER\_IB\_MSG\_1281, 538  
ER\_IB\_MSG\_1282, 538  
ER\_IB\_MSG\_1283, 538  
ER\_IB\_MSG\_1284, 538  
ER\_IB\_MSG\_1285, 563  
ER\_IB\_MSG\_129, 402  
ER\_IB\_MSG\_13, 391  
ER\_IB\_MSG\_130, 402  
ER\_IB\_MSG\_131, 402  
ER\_IB\_MSG\_132, 403  
ER\_IB\_MSG\_133, 403  
ER\_IB\_MSG\_134, 403  
ER\_IB\_MSG\_135, 403  
ER\_IB\_MSG\_1357, 585  
ER\_IB\_MSG\_1358, 585  
ER\_IB\_MSG\_1359, 585  
ER\_IB\_MSG\_136, 403  
ER\_IB\_MSG\_137, 403  
ER\_IB\_MSG\_1372, 587  
ER\_IB\_MSG\_1373, 587  
ER\_IB\_MSG\_1374, 587  
ER\_IB\_MSG\_1375, 587  
ER\_IB\_MSG\_138, 403  
ER\_IB\_MSG\_1381, 588  
ER\_IB\_MSG\_139, 403  
ER\_IB\_MSG\_14, 391  
ER\_IB\_MSG\_140, 403  
ER\_IB\_MSG\_141, 403  
ER\_IB\_MSG\_142, 404  
ER\_IB\_MSG\_143, 404  
ER\_IB\_MSG\_144, 404  
ER\_IB\_MSG\_145, 404  
ER\_IB\_MSG\_146, 404  
ER\_IB\_MSG\_147, 404  
ER\_IB\_MSG\_148, 404  
ER\_IB\_MSG\_149, 404  
ER\_IB\_MSG\_15, 391  
ER\_IB\_MSG\_150, 404  
ER\_IB\_MSG\_151, 405  
ER\_IB\_MSG\_152, 405  
ER\_IB\_MSG\_153, 405  
ER\_IB\_MSG\_154, 405  
ER\_IB\_MSG\_155, 405  
ER\_IB\_MSG\_156, 406

---

ER\_IB\_MSG\_157, 406  
ER\_IB\_MSG\_158, 406  
ER\_IB\_MSG\_159, 406  
ER\_IB\_MSG\_16, 391  
ER\_IB\_MSG\_160, 406  
ER\_IB\_MSG\_161, 406  
ER\_IB\_MSG\_162, 406  
ER\_IB\_MSG\_163, 406  
ER\_IB\_MSG\_164, 406  
ER\_IB\_MSG\_165, 407  
ER\_IB\_MSG\_166, 407  
ER\_IB\_MSG\_167, 407  
ER\_IB\_MSG\_168, 407  
ER\_IB\_MSG\_169, 407  
ER\_IB\_MSG\_17, 391  
ER\_IB\_MSG\_170, 407  
ER\_IB\_MSG\_171, 407  
ER\_IB\_MSG\_172, 407  
ER\_IB\_MSG\_173, 407  
ER\_IB\_MSG\_174, 407  
ER\_IB\_MSG\_175, 408  
ER\_IB\_MSG\_176, 408  
ER\_IB\_MSG\_177, 408  
ER\_IB\_MSG\_178, 408  
ER\_IB\_MSG\_179, 408  
ER\_IB\_MSG\_18, 391  
ER\_IB\_MSG\_180, 408  
ER\_IB\_MSG\_181, 408  
ER\_IB\_MSG\_182, 408  
ER\_IB\_MSG\_183, 408  
ER\_IB\_MSG\_184, 409  
ER\_IB\_MSG\_185, 409  
ER\_IB\_MSG\_186, 409  
ER\_IB\_MSG\_187, 409  
ER\_IB\_MSG\_188, 409  
ER\_IB\_MSG\_189, 409  
ER\_IB\_MSG\_19, 391  
ER\_IB\_MSG\_190, 409  
ER\_IB\_MSG\_191, 409  
ER\_IB\_MSG\_192, 409  
ER\_IB\_MSG\_193, 409  
ER\_IB\_MSG\_194, 410  
ER\_IB\_MSG\_195, 410  
ER\_IB\_MSG\_196, 410  
ER\_IB\_MSG\_197, 410  
ER\_IB\_MSG\_198, 410  
ER\_IB\_MSG\_199, 410  
ER\_IB\_MSG\_2, 390  
ER\_IB\_MSG\_20, 391  
ER\_IB\_MSG\_200, 410  
ER\_IB\_MSG\_201, 410  
ER\_IB\_MSG\_202, 410  
ER\_IB\_MSG\_203, 410  
ER\_IB\_MSG\_204, 411  
ER\_IB\_MSG\_205, 411  
ER\_IB\_MSG\_206, 411  
ER\_IB\_MSG\_207, 411  
ER\_IB\_MSG\_208, 411  
ER\_IB\_MSG\_209, 411  
ER\_IB\_MSG\_21, 391  
ER\_IB\_MSG\_210, 411  
ER\_IB\_MSG\_211, 411  
ER\_IB\_MSG\_212, 411  
ER\_IB\_MSG\_213, 411  
ER\_IB\_MSG\_214, 412  
ER\_IB\_MSG\_215, 412  
ER\_IB\_MSG\_216, 412  
ER\_IB\_MSG\_217, 412  
ER\_IB\_MSG\_218, 412  
ER\_IB\_MSG\_219, 412  
ER\_IB\_MSG\_22, 392  
ER\_IB\_MSG\_220, 412  
ER\_IB\_MSG\_221, 412  
ER\_IB\_MSG\_222, 412  
ER\_IB\_MSG\_223, 412  
ER\_IB\_MSG\_224, 413  
ER\_IB\_MSG\_225, 413  
ER\_IB\_MSG\_226, 413  
ER\_IB\_MSG\_227, 413  
ER\_IB\_MSG\_228, 413  
ER\_IB\_MSG\_229, 413  
ER\_IB\_MSG\_23, 392  
ER\_IB\_MSG\_230, 413  
ER\_IB\_MSG\_231, 413  
ER\_IB\_MSG\_232, 413  
ER\_IB\_MSG\_233, 413  
ER\_IB\_MSG\_234, 414  
ER\_IB\_MSG\_235, 414  
ER\_IB\_MSG\_236, 414  
ER\_IB\_MSG\_237, 414  
ER\_IB\_MSG\_238, 414  
ER\_IB\_MSG\_239, 414  
ER\_IB\_MSG\_24, 392  
ER\_IB\_MSG\_240, 414  
ER\_IB\_MSG\_241, 414  
ER\_IB\_MSG\_242, 414  
ER\_IB\_MSG\_243, 414  
ER\_IB\_MSG\_244, 415  
ER\_IB\_MSG\_245, 415  
ER\_IB\_MSG\_246, 415  
ER\_IB\_MSG\_247, 415  
ER\_IB\_MSG\_248, 415  
ER\_IB\_MSG\_249, 415  
ER\_IB\_MSG\_25, 392  
ER\_IB\_MSG\_250, 415  
ER\_IB\_MSG\_251, 415  
ER\_IB\_MSG\_252, 415  
ER\_IB\_MSG\_253, 415

ER\_IB\_MSG\_254, 416  
ER\_IB\_MSG\_255, 416  
ER\_IB\_MSG\_256, 416  
ER\_IB\_MSG\_257, 416  
ER\_IB\_MSG\_258, 416  
ER\_IB\_MSG\_259, 416  
ER\_IB\_MSG\_26, 392  
ER\_IB\_MSG\_260, 416  
ER\_IB\_MSG\_261, 416  
ER\_IB\_MSG\_262, 416  
ER\_IB\_MSG\_263, 416  
ER\_IB\_MSG\_264, 417  
ER\_IB\_MSG\_265, 417  
ER\_IB\_MSG\_266, 417  
ER\_IB\_MSG\_267, 417  
ER\_IB\_MSG\_268, 417  
ER\_IB\_MSG\_269, 417  
ER\_IB\_MSG\_27, 392  
ER\_IB\_MSG\_270, 417  
ER\_IB\_MSG\_271, 417  
ER\_IB\_MSG\_272, 417  
ER\_IB\_MSG\_273, 417  
ER\_IB\_MSG\_274, 418  
ER\_IB\_MSG\_275, 418  
ER\_IB\_MSG\_276, 418  
ER\_IB\_MSG\_277, 418  
ER\_IB\_MSG\_278, 418  
ER\_IB\_MSG\_279, 418  
ER\_IB\_MSG\_28, 392  
ER\_IB\_MSG\_280, 418  
ER\_IB\_MSG\_281, 418  
ER\_IB\_MSG\_282, 418  
ER\_IB\_MSG\_283, 418  
ER\_IB\_MSG\_284, 419  
ER\_IB\_MSG\_285, 419  
ER\_IB\_MSG\_286, 419  
ER\_IB\_MSG\_287, 419  
ER\_IB\_MSG\_288, 419  
ER\_IB\_MSG\_289, 419  
ER\_IB\_MSG\_29, 392  
ER\_IB\_MSG\_290, 419  
ER\_IB\_MSG\_291, 419  
ER\_IB\_MSG\_292, 420  
ER\_IB\_MSG\_293, 420  
ER\_IB\_MSG\_294, 420  
ER\_IB\_MSG\_295, 420  
ER\_IB\_MSG\_296, 420  
ER\_IB\_MSG\_297, 420  
ER\_IB\_MSG\_298, 420  
ER\_IB\_MSG\_299, 420  
ER\_IB\_MSG\_3, 390  
ER\_IB\_MSG\_30, 392  
ER\_IB\_MSG\_300, 420  
ER\_IB\_MSG\_301, 421

ER\_IB\_MSG\_302, 421  
ER\_IB\_MSG\_303, 421  
ER\_IB\_MSG\_304, 421  
ER\_IB\_MSG\_305, 421  
ER\_IB\_MSG\_306, 421  
ER\_IB\_MSG\_307, 421  
ER\_IB\_MSG\_308, 422  
ER\_IB\_MSG\_309, 422  
ER\_IB\_MSG\_31, 392  
ER\_IB\_MSG\_310, 422  
ER\_IB\_MSG\_311, 422  
ER\_IB\_MSG\_312, 422  
ER\_IB\_MSG\_313, 422  
ER\_IB\_MSG\_314, 422  
ER\_IB\_MSG\_315, 422  
ER\_IB\_MSG\_316, 422  
ER\_IB\_MSG\_317, 422  
ER\_IB\_MSG\_318, 423  
ER\_IB\_MSG\_319, 423  
ER\_IB\_MSG\_32, 393  
ER\_IB\_MSG\_320, 423  
ER\_IB\_MSG\_321, 423  
ER\_IB\_MSG\_322, 423  
ER\_IB\_MSG\_323, 423  
ER\_IB\_MSG\_324, 423  
ER\_IB\_MSG\_325, 423  
ER\_IB\_MSG\_326, 423  
ER\_IB\_MSG\_327, 423  
ER\_IB\_MSG\_328, 424  
ER\_IB\_MSG\_329, 424  
ER\_IB\_MSG\_33, 393  
ER\_IB\_MSG\_330, 424  
ER\_IB\_MSG\_331, 424  
ER\_IB\_MSG\_332, 424  
ER\_IB\_MSG\_333, 424  
ER\_IB\_MSG\_334, 424  
ER\_IB\_MSG\_335, 424  
ER\_IB\_MSG\_336, 424  
ER\_IB\_MSG\_337, 424  
ER\_IB\_MSG\_338, 425  
ER\_IB\_MSG\_339, 425  
ER\_IB\_MSG\_34, 393  
ER\_IB\_MSG\_340, 425  
ER\_IB\_MSG\_341, 425  
ER\_IB\_MSG\_342, 425  
ER\_IB\_MSG\_343, 425  
ER\_IB\_MSG\_344, 425  
ER\_IB\_MSG\_345, 425  
ER\_IB\_MSG\_346, 425  
ER\_IB\_MSG\_347, 425  
ER\_IB\_MSG\_348, 426  
ER\_IB\_MSG\_349, 426  
ER\_IB\_MSG\_35, 393  
ER\_IB\_MSG\_350, 426

---

ER\_IB\_MSG\_351, 426  
ER\_IB\_MSG\_352, 426  
ER\_IB\_MSG\_353, 426  
ER\_IB\_MSG\_354, 426  
ER\_IB\_MSG\_355, 426  
ER\_IB\_MSG\_356, 426  
ER\_IB\_MSG\_357, 427  
ER\_IB\_MSG\_358, 427  
ER\_IB\_MSG\_359, 427  
ER\_IB\_MSG\_36, 393  
ER\_IB\_MSG\_360, 427  
ER\_IB\_MSG\_361, 427  
ER\_IB\_MSG\_362, 427  
ER\_IB\_MSG\_363, 427  
ER\_IB\_MSG\_364, 427  
ER\_IB\_MSG\_365, 427  
ER\_IB\_MSG\_366, 427  
ER\_IB\_MSG\_367, 428  
ER\_IB\_MSG\_368, 428  
ER\_IB\_MSG\_369, 428  
ER\_IB\_MSG\_37, 393  
ER\_IB\_MSG\_370, 428  
ER\_IB\_MSG\_371, 428  
ER\_IB\_MSG\_372, 428  
ER\_IB\_MSG\_373, 428  
ER\_IB\_MSG\_374, 428  
ER\_IB\_MSG\_375, 428  
ER\_IB\_MSG\_376, 429  
ER\_IB\_MSG\_377, 429  
ER\_IB\_MSG\_378, 429  
ER\_IB\_MSG\_379, 429  
ER\_IB\_MSG\_38, 393  
ER\_IB\_MSG\_380, 429  
ER\_IB\_MSG\_381, 429  
ER\_IB\_MSG\_382, 429  
ER\_IB\_MSG\_383, 429  
ER\_IB\_MSG\_384, 429  
ER\_IB\_MSG\_385, 429  
ER\_IB\_MSG\_386, 430  
ER\_IB\_MSG\_387, 430  
ER\_IB\_MSG\_388, 430  
ER\_IB\_MSG\_389, 430  
ER\_IB\_MSG\_39, 393  
ER\_IB\_MSG\_390, 430  
ER\_IB\_MSG\_391, 430  
ER\_IB\_MSG\_392, 430  
ER\_IB\_MSG\_393, 430  
ER\_IB\_MSG\_394, 431  
ER\_IB\_MSG\_395, 431  
ER\_IB\_MSG\_396, 431  
ER\_IB\_MSG\_397, 431  
ER\_IB\_MSG\_398, 431  
ER\_IB\_MSG\_399, 431  
ER\_IB\_MSG\_4, 390

ER\_IB\_MSG\_40, 393  
ER\_IB\_MSG\_400, 431  
ER\_IB\_MSG\_401, 431  
ER\_IB\_MSG\_402, 431  
ER\_IB\_MSG\_403, 431  
ER\_IB\_MSG\_404, 432  
ER\_IB\_MSG\_405, 432  
ER\_IB\_MSG\_406, 432  
ER\_IB\_MSG\_407, 432  
ER\_IB\_MSG\_408, 432  
ER\_IB\_MSG\_409, 432  
ER\_IB\_MSG\_41, 393  
ER\_IB\_MSG\_410, 432  
ER\_IB\_MSG\_411, 432  
ER\_IB\_MSG\_412, 432  
ER\_IB\_MSG\_413, 432  
ER\_IB\_MSG\_414, 433  
ER\_IB\_MSG\_415, 433  
ER\_IB\_MSG\_416, 433  
ER\_IB\_MSG\_417, 433  
ER\_IB\_MSG\_418, 433  
ER\_IB\_MSG\_419, 433  
ER\_IB\_MSG\_42, 394  
ER\_IB\_MSG\_420, 433  
ER\_IB\_MSG\_421, 433  
ER\_IB\_MSG\_422, 433  
ER\_IB\_MSG\_423, 433  
ER\_IB\_MSG\_424, 434  
ER\_IB\_MSG\_425, 434  
ER\_IB\_MSG\_426, 434  
ER\_IB\_MSG\_427, 434  
ER\_IB\_MSG\_428, 434  
ER\_IB\_MSG\_429, 434  
ER\_IB\_MSG\_43, 394  
ER\_IB\_MSG\_430, 434  
ER\_IB\_MSG\_431, 434  
ER\_IB\_MSG\_432, 434  
ER\_IB\_MSG\_433, 434  
ER\_IB\_MSG\_434, 435  
ER\_IB\_MSG\_435, 435  
ER\_IB\_MSG\_436, 435  
ER\_IB\_MSG\_437, 435  
ER\_IB\_MSG\_438, 435  
ER\_IB\_MSG\_439, 435  
ER\_IB\_MSG\_44, 394  
ER\_IB\_MSG\_440, 435  
ER\_IB\_MSG\_441, 435  
ER\_IB\_MSG\_442, 435  
ER\_IB\_MSG\_443, 435  
ER\_IB\_MSG\_444, 436  
ER\_IB\_MSG\_445, 436  
ER\_IB\_MSG\_446, 436  
ER\_IB\_MSG\_447, 436  
ER\_IB\_MSG\_448, 436

---

ER\_IB\_MSG\_449, 436  
ER\_IB\_MSG\_45, 394  
ER\_IB\_MSG\_450, 436  
ER\_IB\_MSG\_451, 436  
ER\_IB\_MSG\_452, 436  
ER\_IB\_MSG\_453, 436  
ER\_IB\_MSG\_454, 437  
ER\_IB\_MSG\_455, 437  
ER\_IB\_MSG\_456, 437  
ER\_IB\_MSG\_457, 437  
ER\_IB\_MSG\_458, 437  
ER\_IB\_MSG\_459, 437  
ER\_IB\_MSG\_46, 394  
ER\_IB\_MSG\_460, 437  
ER\_IB\_MSG\_461, 437  
ER\_IB\_MSG\_462, 437  
ER\_IB\_MSG\_463, 437  
ER\_IB\_MSG\_464, 438  
ER\_IB\_MSG\_465, 438  
ER\_IB\_MSG\_466, 438  
ER\_IB\_MSG\_467, 438  
ER\_IB\_MSG\_468, 438  
ER\_IB\_MSG\_469, 438  
ER\_IB\_MSG\_47, 394  
ER\_IB\_MSG\_470, 438  
ER\_IB\_MSG\_471, 438  
ER\_IB\_MSG\_472, 438  
ER\_IB\_MSG\_473, 438  
ER\_IB\_MSG\_474, 439  
ER\_IB\_MSG\_475, 439  
ER\_IB\_MSG\_476, 439  
ER\_IB\_MSG\_477, 439  
ER\_IB\_MSG\_478, 439  
ER\_IB\_MSG\_479, 439  
ER\_IB\_MSG\_48, 394  
ER\_IB\_MSG\_480, 439  
ER\_IB\_MSG\_481, 439  
ER\_IB\_MSG\_482, 439  
ER\_IB\_MSG\_483, 439  
ER\_IB\_MSG\_484, 440  
ER\_IB\_MSG\_485, 440  
ER\_IB\_MSG\_486, 440  
ER\_IB\_MSG\_487, 440  
ER\_IB\_MSG\_488, 440  
ER\_IB\_MSG\_489, 440  
ER\_IB\_MSG\_49, 394  
ER\_IB\_MSG\_490, 440  
ER\_IB\_MSG\_491, 440  
ER\_IB\_MSG\_492, 440  
ER\_IB\_MSG\_493, 440  
ER\_IB\_MSG\_494, 441  
ER\_IB\_MSG\_495, 441  
ER\_IB\_MSG\_496, 441  
ER\_IB\_MSG\_497, 441

ER\_IB\_MSG\_498, 441  
ER\_IB\_MSG\_499, 441  
ER\_IB\_MSG\_5, 390  
ER\_IB\_MSG\_50, 394  
ER\_IB\_MSG\_500, 441  
ER\_IB\_MSG\_501, 441  
ER\_IB\_MSG\_502, 441  
ER\_IB\_MSG\_503, 441  
ER\_IB\_MSG\_504, 442  
ER\_IB\_MSG\_505, 442  
ER\_IB\_MSG\_506, 442  
ER\_IB\_MSG\_507, 442  
ER\_IB\_MSG\_508, 442  
ER\_IB\_MSG\_509, 442  
ER\_IB\_MSG\_51, 394  
ER\_IB\_MSG\_510, 442  
ER\_IB\_MSG\_511, 442  
ER\_IB\_MSG\_512, 442  
ER\_IB\_MSG\_513, 442  
ER\_IB\_MSG\_514, 443  
ER\_IB\_MSG\_515, 443  
ER\_IB\_MSG\_516, 443  
ER\_IB\_MSG\_517, 443  
ER\_IB\_MSG\_518, 443  
ER\_IB\_MSG\_519, 443  
ER\_IB\_MSG\_52, 395  
ER\_IB\_MSG\_520, 443  
ER\_IB\_MSG\_521, 443  
ER\_IB\_MSG\_522, 443  
ER\_IB\_MSG\_523, 443  
ER\_IB\_MSG\_524, 444  
ER\_IB\_MSG\_525, 444  
ER\_IB\_MSG\_526, 444  
ER\_IB\_MSG\_527, 444  
ER\_IB\_MSG\_528, 444  
ER\_IB\_MSG\_529, 444  
ER\_IB\_MSG\_53, 395  
ER\_IB\_MSG\_530, 444  
ER\_IB\_MSG\_531, 444  
ER\_IB\_MSG\_532, 444  
ER\_IB\_MSG\_533, 444  
ER\_IB\_MSG\_534, 445  
ER\_IB\_MSG\_535, 445  
ER\_IB\_MSG\_536, 445  
ER\_IB\_MSG\_537, 445  
ER\_IB\_MSG\_538, 445  
ER\_IB\_MSG\_539, 445  
ER\_IB\_MSG\_54, 395  
ER\_IB\_MSG\_540, 445  
ER\_IB\_MSG\_541, 445  
ER\_IB\_MSG\_542, 445  
ER\_IB\_MSG\_543, 445  
ER\_IB\_MSG\_544, 446  
ER\_IB\_MSG\_545, 446

---

ER\_IB\_MSG\_546, 446  
ER\_IB\_MSG\_547, 446  
ER\_IB\_MSG\_548, 446  
ER\_IB\_MSG\_549, 446  
ER\_IB\_MSG\_55, 395  
ER\_IB\_MSG\_550, 446  
ER\_IB\_MSG\_551, 446  
ER\_IB\_MSG\_552, 446  
ER\_IB\_MSG\_553, 446  
ER\_IB\_MSG\_554, 447  
ER\_IB\_MSG\_555, 447  
ER\_IB\_MSG\_556, 447  
ER\_IB\_MSG\_557, 447  
ER\_IB\_MSG\_558, 447  
ER\_IB\_MSG\_559, 447  
ER\_IB\_MSG\_56, 395  
ER\_IB\_MSG\_560, 447  
ER\_IB\_MSG\_561, 447  
ER\_IB\_MSG\_562, 447  
ER\_IB\_MSG\_563, 447  
ER\_IB\_MSG\_564, 448  
ER\_IB\_MSG\_565, 448  
ER\_IB\_MSG\_566, 448  
ER\_IB\_MSG\_567, 448  
ER\_IB\_MSG\_568, 448  
ER\_IB\_MSG\_569, 448  
ER\_IB\_MSG\_57, 395  
ER\_IB\_MSG\_570, 448  
ER\_IB\_MSG\_571, 448  
ER\_IB\_MSG\_572, 448  
ER\_IB\_MSG\_573, 449  
ER\_IB\_MSG\_574, 449  
ER\_IB\_MSG\_575, 449  
ER\_IB\_MSG\_576, 449  
ER\_IB\_MSG\_577, 449  
ER\_IB\_MSG\_578, 449  
ER\_IB\_MSG\_579, 449  
ER\_IB\_MSG\_57\_STAT\_SPACE\_DELETE\_FAIL, 580  
ER\_IB\_MSG\_57\_UNDO\_SPACE\_DELETE\_FAIL, 576  
ER\_IB\_MSG\_58, 395  
ER\_IB\_MSG\_580, 449  
ER\_IB\_MSG\_581, 449  
ER\_IB\_MSG\_582, 449  
ER\_IB\_MSG\_583, 450  
ER\_IB\_MSG\_584, 450  
ER\_IB\_MSG\_585, 450  
ER\_IB\_MSG\_586, 450  
ER\_IB\_MSG\_587, 450  
ER\_IB\_MSG\_588, 450  
ER\_IB\_MSG\_589, 450  
ER\_IB\_MSG\_59, 395  
ER\_IB\_MSG\_590, 450  
ER\_IB\_MSG\_591, 450  
ER\_IB\_MSG\_592, 450  
ER\_IB\_MSG\_593, 451  
ER\_IB\_MSG\_594, 451  
ER\_IB\_MSG\_595, 451  
ER\_IB\_MSG\_596, 451  
ER\_IB\_MSG\_597, 451  
ER\_IB\_MSG\_598, 451  
ER\_IB\_MSG\_599, 451  
ER\_IB\_MSG\_6, 390  
ER\_IB\_MSG\_60, 395  
ER\_IB\_MSG\_600, 451  
ER\_IB\_MSG\_601, 451  
ER\_IB\_MSG\_602, 451  
ER\_IB\_MSG\_603, 452  
ER\_IB\_MSG\_604, 452  
ER\_IB\_MSG\_605, 452  
ER\_IB\_MSG\_606, 452  
ER\_IB\_MSG\_607, 452  
ER\_IB\_MSG\_608, 452  
ER\_IB\_MSG\_609, 452  
ER\_IB\_MSG\_61, 395  
ER\_IB\_MSG\_610, 452  
ER\_IB\_MSG\_611, 452  
ER\_IB\_MSG\_612, 452  
ER\_IB\_MSG\_613, 453  
ER\_IB\_MSG\_614, 453  
ER\_IB\_MSG\_615, 453  
ER\_IB\_MSG\_616, 453  
ER\_IB\_MSG\_617, 453  
ER\_IB\_MSG\_618, 453  
ER\_IB\_MSG\_619, 453  
ER\_IB\_MSG\_62, 396  
ER\_IB\_MSG\_620, 453  
ER\_IB\_MSG\_621, 453  
ER\_IB\_MSG\_622, 453  
ER\_IB\_MSG\_623, 454  
ER\_IB\_MSG\_624, 454  
ER\_IB\_MSG\_625, 454  
ER\_IB\_MSG\_626, 454  
ER\_IB\_MSG\_627, 454  
ER\_IB\_MSG\_628, 454  
ER\_IB\_MSG\_629, 454  
ER\_IB\_MSG\_63, 396  
ER\_IB\_MSG\_630, 454  
ER\_IB\_MSG\_631, 454  
ER\_IB\_MSG\_632, 454  
ER\_IB\_MSG\_633, 455  
ER\_IB\_MSG\_634, 455  
ER\_IB\_MSG\_635, 455  
ER\_IB\_MSG\_636, 455  
ER\_IB\_MSG\_637, 455  
ER\_IB\_MSG\_638, 455  
ER\_IB\_MSG\_639, 455  
ER\_IB\_MSG\_64, 396  
ER\_IB\_MSG\_640, 455

---

ER\_IB\_MSG\_641, 455  
ER\_IB\_MSG\_642, 456  
ER\_IB\_MSG\_643, 456  
ER\_IB\_MSG\_644, 456  
ER\_IB\_MSG\_645, 456  
ER\_IB\_MSG\_646, 456  
ER\_IB\_MSG\_647, 456  
ER\_IB\_MSG\_648, 456  
ER\_IB\_MSG\_649, 456  
ER\_IB\_MSG\_65, 396  
ER\_IB\_MSG\_650, 456  
ER\_IB\_MSG\_651, 456  
ER\_IB\_MSG\_652, 457  
ER\_IB\_MSG\_653, 457  
ER\_IB\_MSG\_654, 457  
ER\_IB\_MSG\_655, 457  
ER\_IB\_MSG\_656, 457  
ER\_IB\_MSG\_657, 457  
ER\_IB\_MSG\_658, 457  
ER\_IB\_MSG\_659, 457  
ER\_IB\_MSG\_66, 396  
ER\_IB\_MSG\_660, 457  
ER\_IB\_MSG\_661, 458  
ER\_IB\_MSG\_662, 458  
ER\_IB\_MSG\_663, 458  
ER\_IB\_MSG\_664, 458  
ER\_IB\_MSG\_665, 458  
ER\_IB\_MSG\_666, 458  
ER\_IB\_MSG\_667, 458  
ER\_IB\_MSG\_668, 458  
ER\_IB\_MSG\_669, 458  
ER\_IB\_MSG\_67, 396  
ER\_IB\_MSG\_670, 459  
ER\_IB\_MSG\_671, 459  
ER\_IB\_MSG\_672, 459  
ER\_IB\_MSG\_673, 459  
ER\_IB\_MSG\_674, 459  
ER\_IB\_MSG\_675, 459  
ER\_IB\_MSG\_676, 459  
ER\_IB\_MSG\_677, 459  
ER\_IB\_MSG\_678, 459  
ER\_IB\_MSG\_679, 459  
ER\_IB\_MSG\_68, 396  
ER\_IB\_MSG\_680, 460  
ER\_IB\_MSG\_681, 460  
ER\_IB\_MSG\_682, 460  
ER\_IB\_MSG\_683, 460  
ER\_IB\_MSG\_684, 460  
ER\_IB\_MSG\_685, 460  
ER\_IB\_MSG\_686, 460  
ER\_IB\_MSG\_687, 460  
ER\_IB\_MSG\_688, 460  
ER\_IB\_MSG\_689, 460  
ER\_IB\_MSG\_69, 396

ER\_IB\_MSG\_690, 461  
ER\_IB\_MSG\_691, 461  
ER\_IB\_MSG\_692, 461  
ER\_IB\_MSG\_693, 461  
ER\_IB\_MSG\_694, 461  
ER\_IB\_MSG\_695, 461  
ER\_IB\_MSG\_696, 461  
ER\_IB\_MSG\_697, 461  
ER\_IB\_MSG\_698, 461  
ER\_IB\_MSG\_699, 462  
ER\_IB\_MSG\_7, 390  
ER\_IB\_MSG\_70, 396  
ER\_IB\_MSG\_700, 462  
ER\_IB\_MSG\_701, 462  
ER\_IB\_MSG\_702, 462  
ER\_IB\_MSG\_703, 462  
ER\_IB\_MSG\_704, 462  
ER\_IB\_MSG\_705, 463  
ER\_IB\_MSG\_706, 463  
ER\_IB\_MSG\_707, 463  
ER\_IB\_MSG\_708, 463  
ER\_IB\_MSG\_709, 463  
ER\_IB\_MSG\_71, 396  
ER\_IB\_MSG\_710, 463  
ER\_IB\_MSG\_711, 464  
ER\_IB\_MSG\_712, 464  
ER\_IB\_MSG\_713, 464  
ER\_IB\_MSG\_714, 464  
ER\_IB\_MSG\_715, 464  
ER\_IB\_MSG\_716, 464  
ER\_IB\_MSG\_717, 464  
ER\_IB\_MSG\_718, 464  
ER\_IB\_MSG\_719, 464  
ER\_IB\_MSG\_72, 397  
ER\_IB\_MSG\_720, 464  
ER\_IB\_MSG\_721, 465  
ER\_IB\_MSG\_722, 465  
ER\_IB\_MSG\_723, 465  
ER\_IB\_MSG\_724, 465  
ER\_IB\_MSG\_725, 465  
ER\_IB\_MSG\_726, 465  
ER\_IB\_MSG\_727, 465  
ER\_IB\_MSG\_728, 465  
ER\_IB\_MSG\_729, 466  
ER\_IB\_MSG\_73, 397  
ER\_IB\_MSG\_730, 466  
ER\_IB\_MSG\_731, 466  
ER\_IB\_MSG\_732, 466  
ER\_IB\_MSG\_733, 466  
ER\_IB\_MSG\_734, 467  
ER\_IB\_MSG\_735, 467  
ER\_IB\_MSG\_736, 467  
ER\_IB\_MSG\_737, 467  
ER\_IB\_MSG\_738, 467



---

ER\_IB\_MSG\_739, 468  
ER\_IB\_MSG\_74, 397  
ER\_IB\_MSG\_740, 468  
ER\_IB\_MSG\_741, 468  
ER\_IB\_MSG\_742, 468  
ER\_IB\_MSG\_743, 468  
ER\_IB\_MSG\_744, 468  
ER\_IB\_MSG\_745, 468  
ER\_IB\_MSG\_746, 468  
ER\_IB\_MSG\_747, 468  
ER\_IB\_MSG\_748, 468  
ER\_IB\_MSG\_749, 469  
ER\_IB\_MSG\_75, 397  
ER\_IB\_MSG\_750, 469  
ER\_IB\_MSG\_751, 469  
ER\_IB\_MSG\_752, 469  
ER\_IB\_MSG\_753, 469  
ER\_IB\_MSG\_754, 469  
ER\_IB\_MSG\_755, 469  
ER\_IB\_MSG\_756, 469  
ER\_IB\_MSG\_757, 469  
ER\_IB\_MSG\_758, 469  
ER\_IB\_MSG\_759, 470  
ER\_IB\_MSG\_76, 397  
ER\_IB\_MSG\_760, 470  
ER\_IB\_MSG\_761, 470  
ER\_IB\_MSG\_762, 470  
ER\_IB\_MSG\_763, 470  
ER\_IB\_MSG\_764, 470  
ER\_IB\_MSG\_765, 470  
ER\_IB\_MSG\_766, 470  
ER\_IB\_MSG\_767, 470  
ER\_IB\_MSG\_768, 470  
ER\_IB\_MSG\_769, 471  
ER\_IB\_MSG\_77, 397  
ER\_IB\_MSG\_770, 471  
ER\_IB\_MSG\_771, 471  
ER\_IB\_MSG\_772, 471  
ER\_IB\_MSG\_773, 471  
ER\_IB\_MSG\_774, 471  
ER\_IB\_MSG\_775, 471  
ER\_IB\_MSG\_776, 471  
ER\_IB\_MSG\_777, 471  
ER\_IB\_MSG\_778, 471  
ER\_IB\_MSG\_779, 472  
ER\_IB\_MSG\_78, 397  
ER\_IB\_MSG\_780, 472  
ER\_IB\_MSG\_781, 472  
ER\_IB\_MSG\_782, 472  
ER\_IB\_MSG\_783, 472  
ER\_IB\_MSG\_784, 472  
ER\_IB\_MSG\_785, 472  
ER\_IB\_MSG\_786, 472  
ER\_IB\_MSG\_787, 472

ER\_IB\_MSG\_788, 472  
ER\_IB\_MSG\_789, 473  
ER\_IB\_MSG\_79, 397  
ER\_IB\_MSG\_790, 473  
ER\_IB\_MSG\_791, 473  
ER\_IB\_MSG\_792, 473  
ER\_IB\_MSG\_793, 473  
ER\_IB\_MSG\_794, 473  
ER\_IB\_MSG\_795, 473  
ER\_IB\_MSG\_796, 473  
ER\_IB\_MSG\_797, 473  
ER\_IB\_MSG\_798, 473  
ER\_IB\_MSG\_799, 474  
ER\_IB\_MSG\_8, 390  
ER\_IB\_MSG\_80, 397  
ER\_IB\_MSG\_800, 474  
ER\_IB\_MSG\_801, 474  
ER\_IB\_MSG\_802, 474  
ER\_IB\_MSG\_803, 474  
ER\_IB\_MSG\_804, 474  
ER\_IB\_MSG\_805, 474  
ER\_IB\_MSG\_806, 474  
ER\_IB\_MSG\_807, 474  
ER\_IB\_MSG\_808, 474  
ER\_IB\_MSG\_809, 475  
ER\_IB\_MSG\_81, 397  
ER\_IB\_MSG\_810, 475  
ER\_IB\_MSG\_811, 475  
ER\_IB\_MSG\_812, 475  
ER\_IB\_MSG\_813, 475  
ER\_IB\_MSG\_814, 475  
ER\_IB\_MSG\_815, 475  
ER\_IB\_MSG\_816, 475  
ER\_IB\_MSG\_817, 475  
ER\_IB\_MSG\_818, 475  
ER\_IB\_MSG\_819, 476  
ER\_IB\_MSG\_82, 398  
ER\_IB\_MSG\_820, 476  
ER\_IB\_MSG\_821, 476  
ER\_IB\_MSG\_822, 476  
ER\_IB\_MSG\_823, 476  
ER\_IB\_MSG\_824, 476  
ER\_IB\_MSG\_825, 476  
ER\_IB\_MSG\_826, 476  
ER\_IB\_MSG\_827, 476  
ER\_IB\_MSG\_828, 476  
ER\_IB\_MSG\_829, 477  
ER\_IB\_MSG\_83, 398  
ER\_IB\_MSG\_830, 477  
ER\_IB\_MSG\_831, 477  
ER\_IB\_MSG\_832, 477  
ER\_IB\_MSG\_833, 477  
ER\_IB\_MSG\_834, 477  
ER\_IB\_MSG\_835, 477

---

ER\_IB\_MSG\_836, 477  
ER\_IB\_MSG\_837, 477  
ER\_IB\_MSG\_838, 477  
ER\_IB\_MSG\_839, 478  
ER\_IB\_MSG\_84, 398  
ER\_IB\_MSG\_840, 478  
ER\_IB\_MSG\_841, 478  
ER\_IB\_MSG\_842, 478  
ER\_IB\_MSG\_843, 478  
ER\_IB\_MSG\_844, 478  
ER\_IB\_MSG\_845, 478  
ER\_IB\_MSG\_846, 478  
ER\_IB\_MSG\_847, 479  
ER\_IB\_MSG\_848, 479  
ER\_IB\_MSG\_849, 479  
ER\_IB\_MSG\_85, 398  
ER\_IB\_MSG\_850, 479  
ER\_IB\_MSG\_851, 479  
ER\_IB\_MSG\_852, 479  
ER\_IB\_MSG\_853, 479  
ER\_IB\_MSG\_854, 479  
ER\_IB\_MSG\_855, 479  
ER\_IB\_MSG\_856, 479  
ER\_IB\_MSG\_857, 480  
ER\_IB\_MSG\_858, 480  
ER\_IB\_MSG\_859, 480  
ER\_IB\_MSG\_86, 398  
ER\_IB\_MSG\_860, 480  
ER\_IB\_MSG\_861, 480  
ER\_IB\_MSG\_862, 480  
ER\_IB\_MSG\_863, 480  
ER\_IB\_MSG\_864, 480  
ER\_IB\_MSG\_865, 480  
ER\_IB\_MSG\_866, 480  
ER\_IB\_MSG\_867, 481  
ER\_IB\_MSG\_868, 481  
ER\_IB\_MSG\_869, 481  
ER\_IB\_MSG\_87, 398  
ER\_IB\_MSG\_870, 481  
ER\_IB\_MSG\_871, 481  
ER\_IB\_MSG\_872, 481  
ER\_IB\_MSG\_873, 481  
ER\_IB\_MSG\_874, 481  
ER\_IB\_MSG\_875, 481  
ER\_IB\_MSG\_876, 481  
ER\_IB\_MSG\_877, 482  
ER\_IB\_MSG\_878, 482  
ER\_IB\_MSG\_879, 482  
ER\_IB\_MSG\_88, 398  
ER\_IB\_MSG\_880, 482  
ER\_IB\_MSG\_881, 482  
ER\_IB\_MSG\_882, 482  
ER\_IB\_MSG\_883, 482  
ER\_IB\_MSG\_884, 482

ER\_IB\_MSG\_885, 482  
ER\_IB\_MSG\_886, 482  
ER\_IB\_MSG\_887, 483  
ER\_IB\_MSG\_888, 483  
ER\_IB\_MSG\_889, 483  
ER\_IB\_MSG\_89, 398  
ER\_IB\_MSG\_890, 483  
ER\_IB\_MSG\_891, 483  
ER\_IB\_MSG\_892, 483  
ER\_IB\_MSG\_893, 483  
ER\_IB\_MSG\_894, 483  
ER\_IB\_MSG\_895, 483  
ER\_IB\_MSG\_896, 483  
ER\_IB\_MSG\_897, 484  
ER\_IB\_MSG\_898, 484  
ER\_IB\_MSG\_899, 484  
ER\_IB\_MSG\_9, 390  
ER\_IB\_MSG\_90, 398  
ER\_IB\_MSG\_900, 484  
ER\_IB\_MSG\_901, 484  
ER\_IB\_MSG\_902, 484  
ER\_IB\_MSG\_903, 484  
ER\_IB\_MSG\_904, 484  
ER\_IB\_MSG\_905, 484  
ER\_IB\_MSG\_906, 484  
ER\_IB\_MSG\_907, 485  
ER\_IB\_MSG\_908, 485  
ER\_IB\_MSG\_909, 485  
ER\_IB\_MSG\_91, 398  
ER\_IB\_MSG\_910, 485  
ER\_IB\_MSG\_911, 485  
ER\_IB\_MSG\_912, 485  
ER\_IB\_MSG\_913, 485  
ER\_IB\_MSG\_914, 485  
ER\_IB\_MSG\_915, 485  
ER\_IB\_MSG\_916, 485  
ER\_IB\_MSG\_917, 486  
ER\_IB\_MSG\_918, 486  
ER\_IB\_MSG\_919, 486  
ER\_IB\_MSG\_92, 399  
ER\_IB\_MSG\_920, 486  
ER\_IB\_MSG\_921, 486  
ER\_IB\_MSG\_922, 486  
ER\_IB\_MSG\_923, 486  
ER\_IB\_MSG\_924, 486  
ER\_IB\_MSG\_925, 486  
ER\_IB\_MSG\_926, 486  
ER\_IB\_MSG\_927, 487  
ER\_IB\_MSG\_928, 487  
ER\_IB\_MSG\_929, 487  
ER\_IB\_MSG\_93, 399  
ER\_IB\_MSG\_930, 487  
ER\_IB\_MSG\_931, 487  
ER\_IB\_MSG\_932, 487

---

ER\_IB\_MSG\_933, 487  
ER\_IB\_MSG\_934, 487  
ER\_IB\_MSG\_935, 487  
ER\_IB\_MSG\_936, 487  
ER\_IB\_MSG\_937, 488  
ER\_IB\_MSG\_938, 488  
ER\_IB\_MSG\_939, 488  
ER\_IB\_MSG\_94, 399  
ER\_IB\_MSG\_940, 488  
ER\_IB\_MSG\_941, 488  
ER\_IB\_MSG\_942, 488  
ER\_IB\_MSG\_943, 488  
ER\_IB\_MSG\_944, 488  
ER\_IB\_MSG\_945, 488  
ER\_IB\_MSG\_946, 488  
ER\_IB\_MSG\_947, 489  
ER\_IB\_MSG\_948, 489  
ER\_IB\_MSG\_949, 489  
ER\_IB\_MSG\_95, 399  
ER\_IB\_MSG\_950, 489  
ER\_IB\_MSG\_951, 489  
ER\_IB\_MSG\_952, 489  
ER\_IB\_MSG\_953, 489  
ER\_IB\_MSG\_954, 489  
ER\_IB\_MSG\_955, 489  
ER\_IB\_MSG\_956, 489  
ER\_IB\_MSG\_957, 490  
ER\_IB\_MSG\_958, 490  
ER\_IB\_MSG\_959, 490  
ER\_IB\_MSG\_96, 399  
ER\_IB\_MSG\_960, 490  
ER\_IB\_MSG\_961, 490  
ER\_IB\_MSG\_962, 490  
ER\_IB\_MSG\_963, 490  
ER\_IB\_MSG\_964, 490  
ER\_IB\_MSG\_965, 490  
ER\_IB\_MSG\_966, 490  
ER\_IB\_MSG\_967, 491  
ER\_IB\_MSG\_968, 491  
ER\_IB\_MSG\_969, 491  
ER\_IB\_MSG\_97, 399  
ER\_IB\_MSG\_970, 491  
ER\_IB\_MSG\_971, 491  
ER\_IB\_MSG\_972, 491  
ER\_IB\_MSG\_973, 491  
ER\_IB\_MSG\_974, 491  
ER\_IB\_MSG\_975, 491  
ER\_IB\_MSG\_976, 491  
ER\_IB\_MSG\_977, 492  
ER\_IB\_MSG\_978, 492  
ER\_IB\_MSG\_979, 492  
ER\_IB\_MSG\_98, 399  
ER\_IB\_MSG\_980, 492  
ER\_IB\_MSG\_981, 492

ER\_IB\_MSG\_982, 492  
ER\_IB\_MSG\_983, 492  
ER\_IB\_MSG\_984, 492  
ER\_IB\_MSG\_985, 492  
ER\_IB\_MSG\_986, 492  
ER\_IB\_MSG\_987, 493  
ER\_IB\_MSG\_988, 493  
ER\_IB\_MSG\_989, 493  
ER\_IB\_MSG\_99, 399  
ER\_IB\_MSG\_990, 493  
ER\_IB\_MSG\_991, 493  
ER\_IB\_MSG\_992, 493  
ER\_IB\_MSG\_993, 493  
ER\_IB\_MSG\_994, 493  
ER\_IB\_MSG\_995, 493  
ER\_IB\_MSG\_996, 493  
ER\_IB\_MSG\_997, 494  
ER\_IB\_MSG\_998, 494  
ER\_IB\_MSG\_999, 494  
ER\_IB\_MSG\_BAD\_DBLWR\_FILE\_NAME, 577  
ER\_IB\_MSG\_BTREE\_LEVEL\_LIMIT\_EXCEEDED,  
566  
ER\_IB\_MSG\_BUF\_PENDING\_IO, 506  
ER\_IB\_MSG\_BUF\_PENDING\_IO\_ON\_SHUTDOWN,  
523  
ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_CODE\_STATUS,  
627  
ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_COMPLETE\_CUR\_CODE  
627  
ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_PROGRESS\_UPDATE,  
627  
ER\_IB\_MSG\_CANNOT\_FIND\_DD\_UNDO\_SPACE,  
582  
ER\_IB\_MSG\_CANNOT\_OPEN\_57\_UNDO, 503  
ER\_IB\_MSG\_CANT\_DECRYPT\_REDO\_LOG, 478  
ER\_IB\_MSG\_CANT\_ENCRYPT\_REDO\_LOG\_DATA,  
478  
ER\_IB\_MSG\_CLEAR\_INSTANT\_DROP\_COLUMN\_METADATA  
626  
ER\_IB\_MSG\_CLOCK\_GETTIME\_FAILED, 563  
ER\_IB\_MSG\_CLOCK\_MONOTONIC\_UNSUPPORTED,  
563  
ER\_IB\_MSG\_CLONE\_DDL\_APPLY, 607  
ER\_IB\_MSG\_CLONE\_DDL\_INVALIDATE, 607  
ER\_IB\_MSG\_CLONE\_DDL\_NTFN, 607  
ER\_IB\_MSG\_CREATED\_UNDO\_SPACE, 591  
ER\_IB\_MSG\_CREATE\_LOG\_FILE, 580  
ER\_IB\_MSG\_DATA\_DIRECTORY\_NOT\_INITIALIZED\_OR\_CO  
509  
ER\_IB\_MSG\_DBLWR\_1285, 576  
ER\_IB\_MSG\_DBLWR\_1286, 576  
ER\_IB\_MSG\_DBLWR\_1287, 576  
ER\_IB\_MSG\_DBLWR\_1288, 576  
ER\_IB\_MSG\_DBLWR\_1290, 576

---

ER_IB_MSG_DBLWR_1291, 576	ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME, 574
ER_IB_MSG_DBLWR_1292, 577	ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH, 574
ER_IB_MSG_DBLWR_1293, 577	ER_IB_MSG_FIL_STATE_MOVED_CORRECTED, 574
ER_IB_MSG_DBLWR_1294, 577	ER_IB_MSG_FIL_STATE_MOVED_PREV, 642
ER_IB_MSG_DBLWR_1295, 577	ER_IB_MSG_FIL_STATE_MOVED_PREV_OR_HAS_DATADIR, 642
ER_IB_MSG_DBLWR_1296, 577	ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY, 574
ER_IB_MSG_DBLWR_1297, 577	ER_IB_MSG_FOUND_WRONG_UNDO_SPACE, 545
ER_IB_MSG_DBLWR_1298, 577	ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR, 430
ER_IB_MSG_DBLWR_1300, 577	ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN, 580
ER_IB_MSG_DBLWR_1301, 577	ER_IB_MSG_IGNORE_SCAN_PATH, 428
ER_IB_MSG_DBLWR_1304, 578	ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR, 430
ER_IB_MSG_DBLWR_1305, 578	ER_IB_MSG_INCORRECT_SIZE, 590
ER_IB_MSG_DBLWR_1306, 578	ER_IB_MSG_INJECT_CRASH, 589
ER_IB_MSG_DBLWR_1307, 578	ER_IB_MSG_INJECT_FAILURE, 589
ER_IB_MSG_DBLWR_1308, 578	ER_IB_MSG_INNODB_END_INITIALIZE, 581
ER_IB_MSG_DBLWR_1309, 578	ER_IB_MSG_INNODB_START_INITIALIZE, 581
ER_IB_MSG_DBLWR_1310, 578	ER_IB_MSG_INVALID_LOCATION_FOR_TABLE, 448
ER_IB_MSG_DBLWR_1311, 578	ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE, 582
ER_IB_MSG_DBLWR_1312, 578	ER_IB_MSG_INVALID_LOCATION_WRONG_DB, 582
ER_IB_MSG_DBLWR_1313, 578	ER_IB_MSG_INVALID_PAGE_TYPE, 628
ER_IB_MSG_DBLWR_1314, 579	ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS, 546
ER_IB_MSG_DBLWR_1315, 579	ER_IB_MSG_LOG_CHECKPOINT_FOUND, 618
ER_IB_MSG_DBLWR_1316, 579	ER_IB_MSG_LOG_CORRUPT, 462
ER_IB_MSG_DBLWR_1317, 579	ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY, 522
ER_IB_MSG_DBLWR_1318, 579	ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED, 619
ER_IB_MSG_DBLWR_1319, 579	ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE, 466
ER_IB_MSG_DBLWR_1320, 579	ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY, 616
ER_IB_MSG_DBLWR_1321, 579	ER_IB_MSG_LOG_FILES_CREATED_BY_MEB, 466
ER_IB_MSG_DBLWR_1322, 579	ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY, 466
ER_IB_MSG_DBLWR_1323, 579	ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATOR, 620
ER_IB_MSG_DBLWR_1324, 580	ER_IB_MSG_LOG_FILES_CREATE_AND_READ_ONLY_MODE, 501
ER_IB_MSG_DBLWR_1325, 580	ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES, 509
ER_IB_MSG_DBLWR_1326, 580	ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED, 522
ER_IB_MSG_DBLWR_1327, 580	ER_IB_MSG_LOG_FILES_FOUND_MISSING, 620
ER_IB_MSG_DDL_FAIL_NO_BUILDER, 641	ER_IB_MSG_LOG_FILES_INITIALIZED, 501
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK, 457	ER_IB_MSG_LOG_FILES_INVALID_SET, 509
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT, 560	
ER_IB_MSG_DDL_LOG_FAIL_POST_DDL, 560	
ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACE, 546	
ER_IB_MSG_DICT_PARTITION_NOT_FOUND, 575	
ER_IB_MSG_DIR_DOES_NOT_EXIST, 546	
ER_IB_MSG_DOWNGRADE_PARTITION_FILE, 574	
ER_IB_MSG_DROPPED_UNDO_SPACE, 591	
ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE, 544	
ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR, 544	
ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR, 544	
ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT, 544	
ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE, 545	
ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE, 544	
ER_IB_MSG_FILE_RESIZE, 500	

---

ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED, 619	ER_IB_MSG_LOG_FORMAT_NOT_SUPPORTED, 466
ER_IB_MSG_LOG_FILES_RESIZE_FINISHED, 619	ER_IB_MSG_LOG_FORMAT_OLD, 466
ER_IB_MSG_LOG_FILES_RESIZE_ON_START, 519	ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED
ER_IB_MSG_LOG_FILES_RESIZE_ON_START_FAILED, 618	466 UNEXPECTED,
ER_IB_MSG_LOG_FILES_RESIZE_ON_START_IN_READ, 510	ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTD ONLY_MODE,
ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED, 619	ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED, 616
ER_IB_MSG_LOG_FILES_REWRITING, 510	ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR, 616
ER_IB_MSG_LOG_FILES_UPGRADE, 619	ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZ 616
ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS, 620	ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN_UN 525
ER_IB_MSG_LOG_FILE_FOREIGN_UUID, 618	ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORE 621
ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW, 620	ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED, 617
ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD, 620	ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE, 621
ER_IB_MSG_LOG_FILE_FORMAT_UNKNOWN, 463	ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED, 617
ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM, 524	ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED, 617
ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED, 615	ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED, 620
ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES, 618	ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED, 620
ER_IB_MSG_LOG_FILE_INVALID_START_LSN, 618	ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0, 620
ER_IB_MSG_LOG_FILE_IS_EMPTY, 615	ER_IB_MSG_LOG_UPGRADE_CLONED_DB, 617
ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED, 621	ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECT 617
ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE, 619	ER_IB_MSG_LOG_UPGRADE_FLUSH_FAILED__UNEXPEC 618
ER_IB_MSG_LOG_FILE_MISSING_FOR_ID, 618	ER_IB_MSG_LOG_UPGRADE_FORCED_RECV, 617
ER_IB_MSG_LOG_FILE_OPEN_FAILED, 502	ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE, 617
ER_IB_MSG_LOG_FILE_OS_CREATE_FAILED, 500	ER_IB_MSG_LOG_UPGRADE_NON_PERSISTED_DD_META 618
ER_IB_MSG_LOG_FILE_PREPARE_ON_CREATE_FAILED, 501	ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES, 617
ER_IB_MSG_LOG_FILE_REMOVE_FAILED, 619	ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER, 521
ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED, 619	ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN, 616
ER_IB_MSG_LOG_FILE_RESIZE_FAILED, 501	ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN, 617
ER_IB_MSG_LOG_FILE_SIZE_INVALID, 509	ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE, 521
ER_IB_MSG_LOG_FILE_TOO_BIG, 615	ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER, 521
ER_IB_MSG_LOG_FILE_TOO_SMALL, 615	ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER, 625
ER_IB_MSG_LOG_FILE_TRUNCATE, 621	ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE, 616
ER_IB_MSG_LOG_FILE_UNUSED_MARK_AS_IN_USE_FAILED, 621	ER_IB_MSG_LOG_WRITER_WRITE_FAILED, 616
ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED, 621	ER_IB_MSG_MADVISE_FAILED, 543
ER_IB_MSG_LOG_FILE_UNUSED_RENAME_FAILED, 621	
ER_IB_MSG_LOG_FILE_UNUSED_RESIZE_FAILED, 621	
ER_IB_MSG_LOG_FORMAT_BEFORE_5_7_9, 525	
ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30, 463	

---

ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED, 543	ER_IB_MSG_UNDO_ALTERED_ACTIVE, 589
ER_IB_MSG_MASTER_KEY_ROTATED, 591	ER_IB_MSG_UNDO_ALTERED_INACTIVE, 589
ER_IB_MSG_MAX_UNDO_SPACES_REACHED, 544	ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED, 607
ER_IB_MSG_NOT_END_WITH_IBU, 545	ER_IB_MSG_UNDO_INJECT_CRASH, 589
ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND, 538	ER_IB_MSG_UNDO_INJECT_FAILURE, 589
ER_IB_MSG_NUM_POOLS, 544	ER_IB_MSG_UNDO_MARKED_ACTIVE, 588
ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS, 581	ER_IB_MSG_UNDO_MARKED_EMPTY, 589
ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION, 625	ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE, 513
ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG, 605	ER_IB_MSG_UNDO_TRUNCATE_COMPLETE, 514
ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG, 605	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE, 589
ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER, 560	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE, 514
ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT, 560	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE, 514
ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE 467	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL, 589
ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND, 463	ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE, 513
ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOGFILE, 616	ER_IB_MSG_UNDO_TRUNCATE_START, 513
ER_IB_MSG_RECOVERY_CORRUPT, 510	ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN, 582
ER_IB_MSG_RECOVERY_IN_READ_ONLY, 467	ER_IB_MSG_UNDO_TRUNC_BEFORE_UNDO_LOGGING, 545
ER_IB_MSG_RECOVERY_IS_NEEDED, 467	ER_IB_MSG_UNDO_TRUNC_BEFORE_DD_UPDATE, 545
ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG 604	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE, 545
ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG 604	ER_IB_MSG_UNDO_TRUNC_BEFORE_RSEG, 545
ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE, 465	ER_IB_MSG_UNEXPECTED_FILE_EXISTS, 421
ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE 604	ER_IB_MSG_UNEXPECTED_INPROTECTED_LOCATION_ALLOWED, 426
ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY, 604	ER_IB_MSG_UPGRADE_PARTITION_FILE, 574
ER_IB_MSG_RESUME_OP_FOR_SPACE, 538	ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT, 574
ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR, 586	ER_IB_MSG_USING_UNDO_SPACE, 544
ER_IB_MSG_SDI_Z_STREAM_ERROR, 544	ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD, 537
ER_IB_MSG_SDI_Z_UNKNOWN_ERROR, 545	ER_IB_MSG_WRONG_TABLESPACE_DIR, 546
ER_IB_MSG_SKIP_HIDDEN_DIR, 572	ER_IB_PARALLEL_READER_WORKER_INFO, 628
ER_IB_MSG_STATS_SAMPLING_TOO_LARGE, 596	ER_IB_PRIMARY_KEY_IS_INSTANT, 632
ER_IB_MSG_THREAD_CONCURRENCY_CHANGED, 525	ER_IB_RDBLWR_BYTES_INFO, 615
ER_IB_MSG_TOO_LONG_PATH, 562	ER_IB_RECV_FIRST_REC_GROUP_INVALID, 562
ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED, 516	ER_IB_RELOCK_LATCH_ORDER_VIOLATION, 585
ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED, 584	ER_IB_RESURRECT_ACQUIRE_TABLE_LOCK, 635
ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME, 612	ER_IB_RESURRECT_IDENTIFY_TABLE_TO_LOCK, 635
	ER_IB_RESURRECT_RECORD_COMPLETE, 636
	ER_IB_RESURRECT_RECORD_PROGRESS, 636
	ER_IB_RESURRECT_TRX_INSERT, 635
	ER_IB_RESURRECT_TRX_INSERT_COMPLETE, 636
	ER_IB_RESURRECT_TRX_UPDATE, 635
	ER_IB_RESURRECT_TRX_UPDATE_COMPLETE, 636

---

ER\_IB\_SELECT\_COUNT\_STAR, 634  
 ER\_IB\_TABLESPACE\_PATH\_VALIDATION\_SKIPPED, 584  
 ER\_IB\_TMP\_TABLESPACE\_CANNOT\_CREATE\_DIRECTORY, 586  
 ER\_IB\_UNABLE\_TO\_EXPAND\_TEMPORARY\_TABLESPACE, 586  
 ER\_IB\_WARN\_ACCESSING\_NONEXISTING\_SPACE, 419  
 ER\_IB\_WARN\_MANY\_NON\_LRU\_FILES\_OPENED, 612  
 ER\_IB\_WARN\_OPEN\_PARTITION\_FILE, 574  
 ER\_IB\_WRN\_ENCRYPTION\_INFO\_SIZE\_MISMATCH, 608  
 ER\_IB\_WRN\_FAILED\_TO\_ACQUIRE\_SERVICE, 598  
 ER\_IB\_WRN\_FAST\_SHUTDOWN\_REDO\_DISABLED, 583  
 ER\_IB\_WRN\_IGNORE\_REDO\_LOG\_CAPACITY, 632  
 ER\_IB\_WRN\_OLD\_GEOMETRY\_TYPE, 599  
 ER\_IB\_WRN\_PAGE\_ARCH\_FLUSH\_DATA, 581  
 ER\_IB\_WRN\_REDO\_DISABLED, 583  
 ER\_IB\_WRN\_REDO\_ENABLED, 584  
 ER\_IDENTIFIED\_BY\_UNSUPPORTED, 149  
 ER\_IDENT\_CAUSES\_TOO\_LONG\_PATH, 65  
 ER\_IDENT\_CAUSES\_TOO\_LONG\_PATH\_IN\_UPGRADE, 568  
 ER\_IF\_NOT\_EXISTS\_UNSUPPORTED\_TRG\_EXISTS\_ON\_DIFFERENT\_TABLE, 155  
 ER\_IF\_NOT\_EXISTS\_UNSUPPORTED\_UDF\_NATIVE\_FUNC, 155  
 ER\_ILLEGAL\_GRANT\_FOR\_TABLE, 13  
 ER\_ILLEGAL\_HA, 5  
 ER\_ILLEGAL\_HA\_CREATE\_OPTION, 36  
 ER\_ILLEGAL\_PRIVILEGE\_LEVEL, 98  
 ER\_ILLEGAL\_REFERENCE, 21  
 ER\_ILLEGAL\_USER\_VAR, 74  
 ER\_ILLEGAL\_VALUE\_FOR\_TYPE, 29  
 ER\_IMPLICIT\_COMPARISON\_FOR\_JSON, 140  
 ER\_IMPOSSIBLE\_STRING\_CONVERSION, 140  
 ER\_IMP\_INCOMPATIBLE\_CFG\_VERSION, 135  
 ER\_IMP\_INCOMPATIBLE\_DD\_VERSION, 98  
 ER\_IMP\_INCOMPATIBLE\_MYSQLD\_VERSION, 97  
 ER\_IMP\_INCOMPATIBLE\_SDI\_VERSION, 98  
 ER\_IMP\_NO\_FILES\_MATCHED, 97  
 ER\_IMP\_SCHEMA\_DOES\_NOT\_EXIST, 97  
 ER\_IMP\_TABLE\_ALREADY\_EXISTS, 97  
 ER\_INCONSISTENT\_ERROR, 528  
 ER\_INCONSISTENT\_PARTITION\_INFO\_ERROR, 37  
 ER\_INCONSISTENT\_TYPE\_OF\_FUNCTIONS\_ERROR, 37  
 ER\_INCORRECT\_CURRENT\_PASSWORD, 129  
 ER\_INCORRECT\_GLOBAL\_LOCAL\_VAR, 21  
 ER\_INCORRECT\_TYPE, 74  
 ER\_INDEX\_COLUMN\_TOO\_LONG, 51  
 ER\_INDEX\_CORRUPT, 52  
 ER\_INDEX\_OTHER\_THAN\_PK, 158  
 ER\_INDEX\_TYPE\_NOT\_SUPPORTED\_FOR\_SPATIAL\_INDEX, 62  
 ER\_INFORMATION\_SCHEMA\_VERSION\_CHANGE, 62  
 ER\_INIT\_BOOTSTRAP\_COMPLETE, 214  
 ER\_INIT\_CANT\_OPEN\_BOOTSTRAP\_FILE, 214  
 ER\_INIT\_CREATING\_DD, 215  
 ER\_INIT\_DATADIR\_EXISTS\_AND\_NOT\_WRITABLE\_WONT\_START, 215  
 ER\_INIT\_DATADIR\_EXISTS\_AND\_PATH\_TOO\_LONG\_WONT\_START, 215  
 ER\_INIT\_DATADIR\_EXISTS\_WONT\_INITIALIZE, 214  
 ER\_INIT\_DATADIR\_NOT\_EMPTY\_WONT\_INITIALIZE, 214  
 ER\_INIT\_FAILED\_TO\_GENERATE\_ROOT\_PASSWORD, 571  
 ER\_INIT\_GENERATING\_TEMP\_PASSWORD\_FOR\_ROOT, 214  
 ER\_INIT\_ROOT\_WITHOUT\_PASSWORD, 214  
 ER\_INNODB\_ACTIVE\_INDEX\_CHANGE\_FAILED, 294  
 ER\_INNODB\_AUTOEXTEND\_SIZE\_OUT\_OF\_RANGE, 145  
 ER\_INNODB\_CANNOT\_BE\_IGNORED, 107  
 ER\_INNODB\_CANNOT\_CREATE\_TABLE, 294  
 ER\_INNODB\_CANT\_BUILD\_INDEX\_XLATION\_TABLE\_FOR\_INDEX, 274  
 ER\_INNODB\_CANT\_FIND\_INDEX\_IN\_INNODB\_DD, 273  
 ER\_INNODB\_CANT\_OPEN\_TABLE, 274  
 ER\_INNODB\_CLOSING\_CONNECTION\_ROLLS\_BACK, 273  
 ER\_INNODB\_CLUSTERED\_INDEX\_PRIVATE, 274  
 ER\_INNODB\_COMPRESSION\_FAILURE, 146  
 ER\_INNODB\_DIFF\_IN\_REF\_LEN, 294  
 ER\_INNODB\_DIRTY\_WATER\_MARK\_NOT\_LOW, 273  
 ER\_INNODB\_ERROR\_LOGGER\_FATAL\_MSG, 297  
 ER\_INNODB\_ERROR\_LOGGER\_MSG, 296  
 ER\_INNODB\_FAILED\_TO\_FIND\_IDX, 294  
 ER\_INNODB\_FAILED\_TO\_FIND\_IDX\_FROM\_DICT\_CACHE, 294  
 ER\_INNODB\_FAILED\_TO\_FIND\_IDX\_WITH\_KEY\_NO, 294  
 ER\_INNODB\_FILES\_SAME, 273  
 ER\_INNODB\_FORCED\_RECOVERY, 67  
 ER\_INNODB\_FT\_AUX\_NOT\_HEX\_ID, 67  
 ER\_INNODB\_FT\_LIMIT, 59  
 ER\_INNODB\_FT\_WRONG\_DOCID\_COLUMN, 59  
 ER\_INNODB\_FT\_WRONG\_DOCID\_INDEX, 60  
 ER\_INNODB\_IDX\_CNT\_FEWER\_THAN\_DEFINED\_IN\_MYSQLD, 295

---

---

ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL,	ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS,
295	124
ER_INNODB_IDX_COLUMN_CNT_DIFF, 295	ER_INNODB_REDO_LOG_ARCHIVE_FAILED, 124
ER_INNODB_ILLEGAL_COLON_IN_POOL, 272	ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE,
ER_INNODB_IMPORT_ERROR, 61	124
ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE,	ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE,
145	124
ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS,	ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND,
273	123
ER_INNODB_INDEX_CORRUPT, 61	ER_INNODB_REDO_LOG_ARCHIVE_NO_SUCH_DIR,
ER_INNODB_INSTANT_ADD_DROP_NOT_SUPPORTED,	MAX_SIZE,
161	ER_INNODB_REDO_LOG_ARCHIVE_SESSION, 124
ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_F	ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH,
161	123
ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_S	ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT,
154	123
ER_INNODB_INTERNAL_INDEX, 294	ER_INNODB_TRX_XLATION_TABLE_OOM, 273
ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE,	ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT,
145	581
ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY,	ER_INNODB_UNDO_LOG_FULL, 70
272	ER_INNODB_UNKNOWN_COLLATION, 272
ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_L	ER_INNODB_UNREGISTERED_TRX_ACTIVE, 273
547	ER_INNODB_USE_MONITOR_GROUP_NAME, 295
ER_INNODB_INVALID_LOG_GROUP_HOME_DIR,	ER_INSECURE_CHANGE_MASTER, 56
272	ER_INSECURE_CHANGE_SOURCE, 56
ER_INNODB_INVALID_MONITOR_COUNTER_NAME,	ER_INSECURE_PLAIN_TEXT, 56
295	ER_INSERT_INFO, 9
ER_INNODB_INVALID_PAGE_SIZE, 272	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_DIF
ER_INNODB_IO_CAPACITY_EXCEEDS_MAX, 273	49
ER_INNODB_IO_WRITE_ERROR_RETRYING, 592	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FO
ER_INNODB_IO_WRITE_FAILED, 592	49
ER_INNODB_MANDATORY, 171	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOG_E
ER_INNODB_MAX_ROW_VERSION, 153	50
ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED,	ER_INSTALL_COMPONENT_SET_NULL_VALUE,
295	161
ER_INNODB_MONITOR_IS_ENABLED, 295	ER_INSTALL_COMPONENT_SET_UNUSED_VALUE,
ER_INNODB_NO_FT_TEMP_TABLE, 59	161
ER_INNODB_ONLINE_LOG_TOO_BIG, 60	ER_INSTALL_PLUGIN_CONFLICT_CLIENT, 148
ER_INNODB_OUT_OF_RESOURCES, 575	ER_INSTALL_PLUGIN_CONFLICT_LOG, 603
ER_INNODB_PARTITION_TABLE_LOWERCASED,	ER_INTERNAL_ERROR, 61
274	ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED,
ER_INNODB_PK_NOT_IN_MYSQL, 274	157
ER_INNODB_PK_ONLY_IN_MYSQL, 274	ER_INVALID_ADMIN_ADDRESS, 549
ER_INNODB_READ_ONLY, 66	ER_INVALID_ARGUMENT_FOR_LOGARITHM, 70
ER_INNODB_REDO_ARCHIVING_ENABLED, 140	ER_INVALID_ASSIGNMENT_TARGET, 148
ER_INNODB_REDO_DISABLED, 140	ER_INVALID_AUTHENTICATION_POLICY, 608
ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE, 124	ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE,
ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID,	88
123	ER_INVALID_BITWISE_OPERANDS_SIZE, 88
ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH,	ER_INVALID_CAST, 141
124	ER_INVALID_CAST_POLYGON_RING_DIRECTION,
ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY,	146
123	ER_INVALID_CAST_TO_GEOMETRY, 146
	ER_INVALID_CAST_TO_JSON, 82



---

ER\_INVALID\_CHARACTER\_STRING, 25  
 ER\_INVALID\_CHARSET\_AND\_DEFAULT\_IS\_MB, 199  
 ER\_INVALID\_COLLATION\_FOR\_CHARSET, 280  
 ER\_INVALID\_DD\_OBJECT, 88  
 ER\_INVALID\_DD\_OBJECT\_ID, 88  
 ER\_INVALID\_DD\_OBJECT\_NAME, 88  
 ER\_INVALID\_DEFAULT, 8  
 ER\_INVALID\_DEFAULT\_UTF8MB4\_COLLATION, 109  
 ER\_INVALID\_ENCRYPTION\_OPTION, 85  
 ER\_INVALID\_ENCRYPTION\_REQUEST, 121  
 ER\_INVALID\_ERROR\_LOG\_NAME, 182  
 ER\_INVALID\_FIELD\_SIZE, 69  
 ER\_INVALID\_GEOJSON\_CRS\_NOT\_TOP\_LEVEL, 104  
 ER\_INVALID\_GEOJSON\_MISSING\_MEMBER, 74  
 ER\_INVALID\_GEOJSON\_UNSPECIFIED, 74  
 ER\_INVALID\_GEOJSON\_WRONG\_TYPE, 74  
 ER\_INVALID\_GROUP\_FUNC\_USE, 11  
 ER\_INVALID\_INFO\_IN\_FRM, 199  
 ER\_INVALID\_INSTRUMENT, 170  
 ER\_INVALID\_JSON\_ATTRIBUTE, 139  
 ER\_INVALID\_JSON\_BINARY\_DATA, 82  
 ER\_INVALID\_JSON\_CHARSET, 82  
 ER\_INVALID\_JSON\_CHARSET\_IN\_FUNCTION, 82  
 ER\_INVALID\_JSON\_DATA, 74  
 ER\_INVALID\_JSON\_PATH, 82  
 ER\_INVALID\_JSON\_PATH\_ARRAY\_CELL, 84  
 ER\_INVALID\_JSON\_PATH\_CHARSET, 82  
 ER\_INVALID\_JSON\_PATH\_WILDCARD, 82  
 ER\_INVALID\_JSON\_TEXT, 82  
 ER\_INVALID\_JSON\_TEXT\_IN\_PARAM, 82  
 ER\_INVALID\_JSON\_TYPE, 124  
 ER\_INVALID\_JSON\_VALUE\_FOR\_CAST, 83  
 ER\_INVALID\_JSON\_VALUE\_FOR\_FUNC\_INDEX, 130  
 ER\_INVALID\_MFA\_OPERATIONS\_FOR\_PASSWORDLESS\_LOGIN, 150  
 ER\_INVALID\_MFA\_PLUGIN\_SPECIFIED, 149  
 ER\_INVALID\_MULTIPLE\_CLAUSES, 122  
 ER\_INVALID\_NAMED\_PIPE\_FULL\_ACCESS\_GROUP, 556  
 ER\_INVALID\_NO\_OF\_ARGS, 96  
 ER\_INVALID\_ON\_UPDATE, 25  
 ER\_INVALID\_OPTION\_CHARACTERS, 92  
 ER\_INVALID\_OPTION\_END\_CHARACTER, 92  
 ER\_INVALID\_OPTION\_KEY, 91  
 ER\_INVALID\_OPTION\_KEY\_VALUE\_PAIR, 92  
 ER\_INVALID\_OPTION\_START\_CHARACTER, 92  
 ER\_INVALID\_OPTION\_VALUE, 92  
 ER\_INVALID\_OR\_OLD\_TABLE\_OR\_DB\_NAME, 222  
 ER\_INVALID\_PARAMETER\_USE, 141  
 ER\_INVALID\_PLUGIN\_FOR\_REGISTRATION, 149  
 ER\_INVALID\_PROPERTY\_KEY, 552  
 ER\_INVALID\_REPLICATION\_TIMESTAMPS, 282  
 ER\_INVALID\_RPL\_WILD\_TABLE\_FILTER\_PATTERN, 74  
 ER\_INVALID\_SERVER\_DOWNGRADE\_NOT\_PATCH, 640  
 ER\_INVALID\_SERVER\_UPGRADE\_NOT\_LTS, 640  
 ER\_INVALID\_THREAD\_ID, 103  
 ER\_INVALID\_THREAD\_PRIORITY, 102  
 ER\_INVALID\_TIME\_ZONE\_INTERVAL, 141  
 ER\_INVALID\_TLS\_VERSION, 613  
 ER\_INVALID\_TYPE\_FOR\_JSON, 82  
 ER\_INVALID\_USER\_ATTRIBUTE\_JSON, 139  
 ER\_INVALID\_USER\_FOR\_REGISTRATION, 150  
 ER\_INVALID\_USE\_OF\_FORCE\_OPTION, 103  
 ER\_INVALID\_USE\_OF\_NULL, 13  
 ER\_INVALID\_VALUE\_FOR\_ENFORCE\_GTID\_CONSISTENCY, 166  
 ER\_INVALID\_VALUE\_OF\_BIND\_ADDRESSES, 539  
 ER\_INVALID\_VCPU\_ID, 102  
 ER\_INVALID\_VCPU\_RANGE, 102  
 ER\_INVALID\_XPLUGIN\_SOCKET\_SAME\_AS\_SERVER, 581  
 ER\_INVALID\_YEAR\_COLUMN\_LENGTH, 62  
 ER\_IO\_ERR\_LOG\_INDEX\_READ, 30  
 ER\_IO\_READ\_ERROR, 61  
 ER\_IO\_WRITE\_ERROR, 61  
 ER\_IPSOCK\_ERROR, 9  
 ER\_IS\_QUERY\_INVALID\_CLAUSE, 91  
 ER\_I\_S\_SKIPPED\_TABLESPACE, 101  
 ER\_JSON\_BAD\_ONE\_OR\_ALL\_ARG, 83  
 ER\_JSON\_DOCUMENT\_NULL\_KEY, 83  
 ER\_JSON\_DOCUMENT\_TOO\_DEEP, 83  
 ER\_JSON\_KEY\_TOO\_BIG, 82  
 ER\_JSON\_PARSE\_ERROR, 184  
 ER\_JSON\_SCHEMA\_VALIDATION\_ERROR\_WITH\_DETAILS, 134  
 ER\_JSON\_USED\_AS\_KEY, 83  
 ER\_JSON\_VACUOUS\_PATH, 83  
 ER\_JSON\_VALUE\_OUT\_OF\_RANGE\_FOR\_FUNC\_INDEX, 130  
 ER\_JSON\_VALUE\_TOO\_BIG, 82  
 ER\_JT\_MAX\_NESTED\_PATH, 104  
 ER\_JT\_VALUE\_OUT\_OF\_RANGE, 104  
 ER\_KERBEROS\_CREATE\_USER, 148  
 ER\_KEYCACHE\_OOM, 174  
 ER\_KEYRING\_ACCESS\_DENIED\_ERROR, 86  
 ER\_KEYRING\_AWS\_CMK\_ID\_NOT\_SET, 340  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ACCESS\_DATA\_FILE, 340  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ACCESS\_KEY\_FROM\_COS, 339  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ACCESS\_KEY\_ID\_FROM\_COS, 339

---

ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DATA_COMPONENT,	ER_KEYRING_DATA_COMPONENT_NOT_INITIALIZED,
339	597
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DIR,	ER_KEYRING_DIR_ENCRYPTED_FILE_DECRYPTION_FAILED,
339	337
ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS,	ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED,
341	337
ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY,	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEYRING,
342	337
ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY,	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING,
341	337
ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE,	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING,
341	337
ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_KEYRING_ERROR,	ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP_FILE,
340	337
ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEYRING,	ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_KEYRING_ERROR,
341	338
ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIALS_FROM_REGION,	ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_FILE_PATH,
340	336
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_PLUGIN_ERROR,	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INTERNAL_PLUGIN_ERROR,
339	338
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INIT_FAILURE,	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE,
340	338
ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE,	ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR,
338	337
ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE,	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID,
341	337
ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY,	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG,
341	338
ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK,	ER_KEYRING_FAILED_TO_CREATE_KEYRING_DIR,
342	331
ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID,	ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE,
338	332
ER_KEYRING_AWS_FAILED_TO_SET_REGION,	ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING,
338	333
ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE,	ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP_FILE,
341	333
ER_KEYRING_AWS_INCORRECT_FILE,	ER_KEYRING_FAILED_TO_GENERATE_KEY,
340	331
ER_KEYRING_AWS_INCORRECT_PROXY,	ER_KEYRING_FAILED_TO_GET_FILE_STAT,
569	332
ER_KEYRING_AWS_INCORRECT_REGION,	ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT,
341	333
ER_KEYRING_AWS_INIT_FAILURE,	ER_KEYRING_FAILED_TO_REMOVE_FILE,
340	332
ER_KEYRING_AWS_INVALID_CONF_FILE_PATH,	ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_ID,
339	333
ER_KEYRING_AWS_INVALID_DATA_FILE_PATH,	ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE,
339	332
ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER,	ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA,
340	332
ER_KEYRING_AWS_UDF_AWS_KMS_ERROR,	ER_KEYRING_FAILED_TO_TRUNCATE_FILE,
86	332
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY_ID,	ER_KEYRING_FILE_INIT_FAILED,
331	331
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEYRING_FILE_IO_ERROR,	ER_KEYRING_FILE_IO_ERROR,
331	333
ER_KEYRING_COMPONENT_EXCEPTION,	ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE,
597	332
ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR,	ER_KEYRING_INCORRECT_FILE,
597	332

---

ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE_INIT,	331	ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGUR	333
ER_KEYRING_INVALID_KEY_LENGTH,	331	ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_C	333
ER_KEYRING_INVALID_KEY_TYPE,	330	ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ER	334
ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEY,	333	ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER,	334
ER_KEYRING_LOGGER_ERROR_MSG,	313	ER_KEYRING_OKV_INVALID_KEY_TYPE,	334
ER_KEYRING_MIGRATE_FAILED,	527	ER_KEYRING_OKV_KEY_MISMATCH,	336
ER_KEYRING_MIGRATION_EXTRA_OPTIONS,	389	ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEED	613
ER_KEYRING_MIGRATION_FAILED,	299	ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_E	331
ER_KEYRING_MIGRATION_FAILURE,	86	ER_KEYRING_UDF_KEYRING_SERVICE_ERROR,	85
ER_KEYRING_MIGRATION_STATUS,	86	ER_KEYRING_UNKNOWN_ERROR,	332
ER_KEYRING_MIGRATION_SUCCESSFUL,	299	ER_KEY_COLUMN_DOES_NOT_EXITS,	8
ER_KEYRING_OCI_HTTP_REQUEST,	627	ER_KEY_DOES_NOT_EXITS,	15
ER_KEYRING_OCI_INVALID_JSON,	627	ER_KEY_NOT_FOUND,	5
ER_KEYRING_OCI_PARSE_JSON,	627	ER_KEY_PART_0,	30
ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED,	335	ER_KEY_REF_DO_NOT_MATCH_TABLE_REF,	21
ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS,	335	ER_KILLED_THREADS_OF_PLUGIN,	217
ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE,	335	ER_KILLING_THREAD,	216
ER_KEYRING_OKV_FAILED_TO_FETCH_KEY,	335	ER_KILL_DENIED_ERROR,	10
ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY,	334	ER_KEY_RANGE_OUT_OF_RANGE,	98
ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER,	334	ER_LCTN_CHANGED,	299
ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY,	335	ER_LCTN_NOT_FOUND,	527
ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR,	334	ER_LDAP_AUTH_CERTIFICATE_NAME,	382
ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT,	335	ER_LDAP_AUTH_CONNECTION_HOST_INFO,	385
ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER,	335	ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER,	385
ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID,	334	ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL,	385
ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE,	336	ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED,	387
ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE,	334	ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER,	387
ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY,	335	ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL,	385
ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY,	336	ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING,	381
ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE,	336	ER_LDAP_AUTH_CONN_POOL_INITIALIZING,	381
ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE,	336	ER_LDAP_AUTH_CONN_POOL_NOT_CREATED,	380
ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE,	336	ER_LDAP_AUTH_CREATE_CONNECTION_KEY,	385
ER_KEYRING_OKV_FAILED_TO_STORE_KEY,	335	ER_LDAP_AUTH_CREATING_LDAP_CONNECTION,	384
ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY,	336	ER_LDAP_AUTH_DEINIT_FAILED,	380
		ER_LDAP_AUTH_DELETING_CONNECTION_KEY,	385
		ER_LDAP_AUTH_DISTINGUISHED_NAME,	386

---

ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION, 387	ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP, 382
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT, 380	ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED, 386
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CREATOR, 380	ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET, 384
ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION, 380	ER_LDAP_AUTH_POOLED_CONNECTION_KEY, 385
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY, 383	ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO, 380
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECORD, 383	ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION, 387
ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION, 387	ER_LDAP_AUTH_POOL_REINITIALIZING, 381
ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN, 383	ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL, 384
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT, 383	ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO, 386
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT, 383	ER_LDAP_AUTH_SASL_PROCESS_SASL, 386
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT, 383	ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT, 386
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECORD, 383	ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME, 382
ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT, 382	ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND, 384
ER_LDAP_AUTH_FAILED_TO_SEARCH_DN, 387	ER_LDAP_AUTH_SETTING_USERNAME, 381
ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET, 381	ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH, 380
ER_LDAP_AUTH_FREEING_CONNECTION, 384	ER_LDAP_AUTH_STARTED_FOR_USER, 386
ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL, 384	ER_LDAP_AUTH_STARTING_TLS, 385
ER_LDAP_AUTH_GRP_DN_PARSING_FAILED, 554	ER_LDAP_AUTH_TLS_CONF, 380
ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE, 554	ER_LDAP_AUTH_TLS_CONNECTION, 380
ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS, 554	ER_LDAP_AUTH_USER_AUTH_DATA, 381
ER_LDAP_AUTH_GRP_IS_FULL_DN, 382	ER_LDAP_AUTH_USER_BIND_FAILED, 386
ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE, 554	ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS, 382
ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO, 554	ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED, 386
ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL, 553	ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO, 381
ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL, 382	ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND, 542
ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO, 554	ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES, 382
ER_LDAP_AUTH_INFO_FOR_USER, 381	ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP, 382
ER_LDAP_AUTH_INIT_FAILED, 386	ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED, 381
ER_LDAP_AUTH_LDAPS, 554	ER_LDAP_EMPTY_USERDN_PASSWORD, 565
ER_LDAP_AUTH_LDAP_INFO_NULL, 384	ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE, 555
ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT, 383	ER_LDAP_MAPPING_EMPTY_MAPPING, 555
ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED, 384	ER_LDAP_MAPPING_GETTING_NEXT_MAPPING, 556
ER_LDAP_AUTH_METHOD_TO_CLIENT, 385	ER_LDAP_MAPPING_GET_USER_PROXY, 554
	ER_LDAP_MAPPING_INFO, 555

---

ER\_LDAP\_MAPPING\_IS\_QUOTE, 556  
ER\_LDAP\_MAPPING\_NON\_DESIRED\_STATE, 556  
ER\_LDAP\_MAPPING\_NO\_SEPARATOR\_END\_OF\_GROUP, 555  
ER\_LDAP\_MAPPING\_PARSING\_CURRENT\_STATE, 556  
ER\_LDAP\_MAPPING\_PARSING\_ERROR, 556  
ER\_LDAP\_MAPPING\_PARSING\_MAPPING\_INFO, 556  
ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER, 555  
ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_COMMA, 555  
ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_EQUAL, 555  
ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_TRY\_COMMA, 555  
ER\_LDAP\_MAPPING\_PROCESS\_MAPPING, 555  
ER\_LDAP\_MAPPING\_TRIMMING\_SPACES, 556  
ER\_LDAP\_MAPPING\_USER\_DONT\_BELONG\_GROUP, 554  
ER\_LIMITED\_PART\_RANGE, 39  
ER\_LOAD\_BULK\_DATA\_FAILED, 160  
ER\_LOAD\_BULK\_DATA\_UNSORTED, 158  
ER\_LOAD\_BULK\_DATA\_WARN\_NULL\_TO\_NOTNULL, 161  
ER\_LOAD\_BULK\_DATA\_WARN\_NULL\_TO\_NOTNULL\_LOG, 631  
ER\_LOAD\_BULK\_DATA\_WRONG\_VALUE\_FOR\_FIELD, 161  
ER\_LOAD\_BULK\_DATA\_WRONG\_VALUE\_FOR\_FIELD\_LOG, 631  
ER\_LOAD\_DATA\_INFILE\_FAILED\_IN\_UNEXPECTED\_WARN, 185  
ER\_LOAD\_FROM\_FIXED\_SIZE\_ROWS\_TO\_VAR, 32  
ER\_LOAD\_INFO, 9  
ER\_LOCAL\_VARIABLE, 20  
ER\_LOCKING\_SERVICE\_DEADLOCK, 81  
ER\_LOCKING\_SERVICE\_TIMEOUT, 81  
ER\_LOCKING\_SERVICE\_WRONG\_NAME, 81  
ER\_LOCK\_ABORTED, 50  
ER\_LOCK\_DEADLOCK, 18  
ER\_LOCK\_NOWAIT, 93  
ER\_LOCK\_ORDER\_DEPENDENCIES\_SYNTAX, 565  
ER\_LOCK\_ORDER\_FAILED\_READ\_FILE, 565  
ER\_LOCK\_ORDER\_FAILED\_WRITE\_FILE, 565  
ER\_LOCK\_ORDER\_INIT\_FAILED, 563  
ER\_LOCK\_ORDER\_MESSAGE, 565  
ER\_LOCK\_ORDER\_SCANNER\_SYNTAX, 565  
ER\_LOCK\_OR\_ACTIVE\_TRANSACTION, 16  
ER\_LOCK\_REFUSED\_BY\_ENGINE, 84  
ER\_LOCK\_TABLE\_FULL, 18  
ER\_LOCK\_WAIT\_TIMEOUT, 18  
ER\_LOG\_BIN\_BETTER\_WITH\_NAME, 179  
ER\_LOG\_CANNOT\_PURGE\_BINLOG\_WITH\_BACKUP\_LOCK, 639  
ER\_LOG\_CANNOT\_WRITE, 163  
ER\_LOG\_CANNOT\_WRITE\_EXTENDED, 569  
ER\_LOG\_COMPONENT\_CANNOT\_INIT, 592  
ER\_LOG\_COMPONENT\_FLUSH\_FAILED, 604  
ER\_LOG\_FILES\_GIVEN\_LOG\_OUTPUT\_IS\_TABLE, 178  
ER\_LOG\_FILE\_CANNOT\_OPEN, 321  
ER\_LOG\_FILE\_INVALID, 179  
ER\_LOG\_GENERAL\_CANNOT\_OPEN, 163  
ER\_LOG\_IN\_USE, 30  
ER\_LOG\_INVALID\_OUTPUT\_CONTRADICTION, 178  
ER\_LOG\_PRINTF\_MSG, 297  
ER\_LOG\_PRIV\_CHECKS\_REQUIRE\_ROW\_FORMAT\_NOT\_FOUND, 573  
ER\_LOG\_PURGE\_NO\_FILE, 44  
ER\_LOG\_PURGE\_UNKNOWN\_ERR, 30  
ER\_LOG\_SLOW\_CANNOT\_OPEN, 163  
ER\_LOG\_SYSLOG\_CANNOT\_OPEN, 163  
ER\_LOG\_SYSLOG\_FACILITY\_FAIL, 163  
ER\_LONGITUDE\_OUT\_OF\_RANGE, 98  
ER\_LOWER\_CASE\_TABLE\_NAMES\_CS\_DD\_ON\_CI\_FS\_UN, 179  
ER\_LOWER\_CASE\_TABLE\_NAMES\_USING\_0, 179  
ER\_LOWER\_CASE\_TABLE\_NAMES\_USING\_2, 179  
ER\_MALFORMED\_GTID\_SET\_ENCODING, 57  
ER\_MALFORMED\_GTID\_SET\_SPECIFICATION, 57  
ER\_MALFORMED\_GTID\_SPECIFICATION, 57  
ER\_MALFORMED\_PACKET, 63  
ER\_MANDATORY\_ROLE, 99  
ER\_MASTER, 16  
ER\_MASTER\_DELAY\_VALUE\_OUT\_OF\_RANGE, 53  
ER\_MASTER\_FATAL\_ERROR\_READING\_BINLOG, 20  
ER\_MASTER\_HAS\_PURGED\_REQUIRED\_GTIDS, 59  
ER\_MASTER\_INFO, 17  
ER\_MASTER\_KEY\_ROTATION\_BINLOG\_FAILED, 85  
ER\_MASTER\_KEY\_ROTATION\_NOT\_SUPPORTED\_BY\_SE, 85  
ER\_MASTER\_KEY\_ROTATION\_SE\_UNAVAILABLE, 85  
ER\_MASTER\_NET\_READ, 16  
ER\_MASTER\_NET\_WRITE, 16  
ER\_MAXVALUE\_IN\_VALUES\_IN, 47  
ER\_MAX\_PREPARED\_STMT\_COUNT\_REACHED, 35  
ER\_MDL\_OUT\_OF\_RESOURCES, 140  
ER\_MECAB\_CHARSET\_LOADED, 303  
ER\_MECAB\_CREATE\_LATTICE\_FAILED, 303  
ER\_MECAB\_CREATING\_MODEL, 302  
ER\_MECAB\_FAILED\_TO\_CREATE\_MODEL, 302

---

---

ER\_MECAB\_FAILED\_TO\_CREATE\_TRIGGER, 303  
 ER\_MECAB\_NOT\_SUPPORTED, 302  
 ER\_MECAB\_NOT\_VERIFIED, 302  
 ER\_MECAB\_OOM\_WHILE\_PARSING\_TEXT, 303  
 ER\_MECAB\_PARSE\_FAILED, 303  
 ER\_MECAB\_UNSUPPORTED\_CHARSET, 303  
 ER\_MESSAGE\_AND\_STATEMENT, 48  
 ER\_MFA\_METHODS\_IDENTICAL, 150  
 ER\_MFA\_METHODS\_INVALID\_ORDER, 150  
 ER\_MFA\_METHOD\_EXISTS, 149  
 ER\_MFA\_METHOD\_NOT\_EXISTS, 149  
 ER\_MFA\_PLUGIN\_NOT\_LOADED, 611  
 ER\_MFA\_USER\_ATTRIBUTES\_CORRUPT, 611  
 ER\_MICROSECOND\_TIMER\_IS\_NOT\_AVAILABLE,  
 293  
 ER\_MIGRATE\_TABLE\_TO\_DD\_OOM, 576  
 ER\_MISPLACED\_INTO, 136  
 ER\_MISSING\_ACL\_SYSTEM\_TABLE, 284  
 ER\_MISSING\_CURRENT\_PASSWORD, 129  
 ER\_MISSING\_GRANT\_SYSTEM\_TABLE, 284  
 ER\_MISSING\_HA\_CREATE\_OPTION, 69  
 ER\_MISSING\_JSON\_TABLE\_VALUE, 103  
 ER\_MISSING\_JSON\_VALUE, 137  
 ER\_MISSING\_KEY, 68  
 ER\_MISSING\_SKIP\_REPLICA, 24  
 ER\_MISSING\_SKIP\_SLAVE, 23  
 ER\_MISSING\_TABLESPACE\_FILE, 99  
 ER\_MIXING\_NOT\_ALLOWED, 19  
 ER\_MIX\_HANDLER\_ERROR, 37  
 ER\_MIX\_OF\_GROUP\_FUNC\_AND\_FIELDS, 13  
 ER\_MIX\_OF\_GROUP\_FUNC\_AND\_FIELDS\_V2, 77  
 ER\_MTA\_CANT\_PARALLEL, 55  
 ER\_MTA\_CHANGE\_SOURCE\_CANT\_RUN\_WITH\_GAPS,  
 60  
 ER\_MTA\_EVENT\_BIGGER\_PENDING\_JOBS\_SIZE\_MAX,  
 65  
 ER\_MTA\_FEATURE\_IS\_NOT\_SUPPORTED, 55  
 ER\_MTA\_INCONSISTENT\_DATA, 56  
 ER\_MTA\_RECOVERY\_FAILURE, 60  
 ER\_MTA\_RESET\_WORKERS, 60  
 ER\_MTA\_UPDATED\_DBS\_GREATER\_MAX, 55  
 ER\_MTR\_MSG\_1, 605  
 ER\_MTS\_CANT\_PARALLEL, 55  
 ER\_MTS\_CHANGE\_MASTER\_CANT\_RUN\_WITH\_GAPS,  
 60  
 ER\_MTS\_EVENT\_BIGGER\_PENDING\_JOBS\_SIZE\_MAX,  
 65  
 ER\_MTS\_FEATURE\_IS\_NOT\_SUPPORTED, 55  
 ER\_MTS\_INCONSISTENT\_DATA, 55  
 ER\_MTS\_RECOVERY\_FAILURE, 60  
 ER\_MTS\_RESET\_WORKERS, 60  
 ER\_MTS\_UPDATED\_DBS\_GREATER\_MAX, 55  
 ER\_MULTIPLE\_CONSTRAINTS\_WITH\_SAME\_NAME,  
 134  
 ER\_MULTIPLE\_DEF\_CONST\_IN\_LIST\_PART\_ERROR,  
 37  
 ER\_MULTIPLE\_INTO\_CLAUSES, 136  
 ER\_MULTIPLE\_JSON\_VALUES, 138  
 ER\_MULTIPLE\_PRI\_KEY, 8  
 ER\_MULTI\_UPDATE\_KEY\_CONFLICT, 51  
 ER\_MUST\_CHANGE\_EXPIRED\_PASSWORD, 279  
 ER\_MUST\_CHANGE\_PASSWORD, 62  
 ER\_MUST\_CHANGE\_PASSWORD\_LOGIN, 65  
 ER\_MYINIT\_FAILED, 176  
 ER\_MYISAM\_CHECK\_METHOD\_ERROR, 296  
 ER\_MYISAM\_CRASHED\_ERROR, 296  
 ER\_MYISAM\_CRASHED\_ERROR\_IN, 187  
 ER\_MYISAM\_CRASHED\_ERROR\_IN\_THREAD, 187  
 ER\_MYSQLBACKUP\_CLIENT\_MSG, 153  
 ER\_MYSQLBACKUP\_MSG, 570  
 ER\_MYSQL\_NATIVE\_PASSWORD\_SECOND\_PASSWORD\_USE,  
 550  
 ER\_MY\_MALLOC\_GETPROCADDRESS\_FAILED,  
 614  
 ER\_MY\_MALLOC\_LOADLIBRARY\_FAILED, 614  
 ER\_MY\_MALLOC\_USING\_JEMALLOC, 614  
 ER\_MY\_MALLOC\_USING\_STD\_MALLOC, 614  
 ER\_MY\_NET\_WRITE\_FAILED\_FALLING\_BACK\_ON\_STDERR,  
 258  
 ER\_M\_BIGGER\_THAN\_D, 33  
 ER\_NAME\_BECOMES\_EMPTY, 36  
 ER\_NANOSECOND\_TIMER\_IS\_NOT\_AVAILABLE,  
 293  
 ER\_NATIVE\_FCT\_NAME\_COLLISION, 42  
 ER\_NDBINFO\_NOT\_UPGRADING\_SCHEMA, 580  
 ER\_NDBINFO\_UPGRADING\_SCHEMA, 580  
 ER\_NDBINFO\_UPGRADING\_SCHEMA\_FAIL, 580  
 ER\_NDB\_BINLOG\_BLOB\_REQUIRES\_PK, 248  
 ER\_NDB\_BINLOG\_CANT\_COMMIT\_TO\_NDB\_BINLOG\_INDEX,  
 246  
 ER\_NDB\_BINLOG\_CANT\_CREATE\_BLOB, 249  
 ER\_NDB\_BINLOG\_CANT\_CREATE\_EVENT\_IN\_DB,  
 248  
 ER\_NDB\_BINLOG\_CANT\_CREATE\_EVENT\_IN\_DB\_AND\_CANT,  
 249  
 ER\_NDB\_BINLOG\_CANT\_CREATE\_EVENT\_IN\_DB\_DROPPED,  
 249  
 ER\_NDB\_BINLOG\_CANT\_CREATE\_PURGE\_THD,  
 272  
 ER\_NDB\_BINLOG\_CANT\_DISCOVER\_TABLE\_FROM\_SCHEMA,  
 243  
 ER\_NDB\_BINLOG\_CANT\_DROP\_EVENT\_FROM\_DB,  
 249  
 ER\_NDB\_BINLOG\_CANT\_INJECT\_APPLY\_STATUS\_WRITE\_RO,  
 252  
 ER\_NDB\_BINLOG\_CANT\_LOCK\_NDB\_BINLOG\_INDEX,  
 246  
 ER\_NDB\_BINLOG\_CANT\_RELEASE\_SLOCK, 244

---

ER_NDB_BINLOG_CANT_REOPEN_SHADOW_TABLE, 244	ER_NDB_BINLOG_NDB_LOG_TRANSACTION_ID_REQUIRE 247
ER_NDB_BINLOG_CANT_WRITE_TO_NDB_BINLOG_INDEX, 246	ER_NDB_BINLOG_NDB_TABLES_INITIALLY_READ_ONLY, 221
ER_NDB_BINLOG_CLEANING_UP_SETUP_LEFTOVERS, 242	ER_NDB_BINLOG_NDB_TABLES_WRITABLE, 251
ER_NDB_BINLOG_CLUSTER_FAILURE, 250	ER_NDB_BINLOG_NOT_LOGGING, 248
ER_NDB_BINLOG_CLUSTER_HAS_RECONNECTED, 251	ER_NDB_BINLOG_ONLINE_ALTER_RENAME, 244
ER_NDB_BINLOG_CLUSTER_RESTARTED_RESET_MASTER, 251	ER_NDB_BINLOG_ONLINE_ALTER_RENAME_COMPLETE, 245
ER_NDB_BINLOG_CREATE_TABLE_EVENT, 219	ER_NDB_BINLOG_OPENING_INDEX, 246
ER_NDB_BINLOG_CREATE_TABLE_EVENT_FAILED, 248	ER_NDB_BINLOG_RELEASING_EXTRA_SHARE_REFEREN 252
ER_NDB_BINLOG_CREATE_TABLE_EVENT_INFO, 248	ER_NDB_BINLOG_REMAINING_OPEN_TABLES, 252
ER_NDB_BINLOG_CREATING_NDBEVENTOPERATION_FAILED, 249	ER_NDB_BINLOG_REMAINING_OPEN_TABLE_INFO, 252
ER_NDB_BINLOG_DISCOVER_REUSING_OLD_EVENT_OPS, 249	ER_NDB_BINLOG_RENAME_EVENT, 219
ER_NDB_BINLOG_DISCOVER_TABLE_EVENT_INFO, 248	ER_NDB_BINLOG_REPLY_TO, 244
ER_NDB_BINLOG_ERROR_DURING_GCI_COMMIT, 252	ER_NDB_BINLOG_SERVER_SHUTDOWN_DURING_NDB_C 250
ER_NDB_BINLOG_ERROR_DURING_GCI_ROLLBACK, 252	ER_NDB_BINLOG_SHUTDOWN_DETECTED, 251
ER_NDB_BINLOG_ERROR_HANDLING_SCHEMA_EVENT, 251	ER_NDB_BINLOG_SIGNALLING_UNKNOWN_VALUE, 243
ER_NDB_BINLOG_ERROR_INFO_FROM_DA, 219	ER_NDB_BINLOG_SKIPPING_DROP_OF_DB_CONTAINING 245
ER_NDB_BINLOG_FAILED_CREATE_EVENT_OPERATION, 219	ER_NDB_BINLOG_SKIPPING_DROP_OF_LOCAL_TABLE, 245
ER_NDB_BINLOG_FAILED_CREATE_TABLE_EVENT_OPE 219	ER_NDB_BINLOG_SKIPPING_LOCAL_TABLE, 244
ER_NDB_BINLOG_FAILED_TO_GET_TABLE, 248	ER_NDB_BINLOG_SKIPPING_OLD_SCHEMA_OPERATION, 245
ER_NDB_BINLOG_FORMAT_CHANGED_FROM_STMT_T 220	ER_NDB_BINLOG_SKIPPING_RENAME_OF_LOCAL_TABLE 245
ER_NDB_BINLOG_GENERIC_MESSAGE, 247	ER_NDB_BINLOG_STARTING_LOG_AT_EPOCH, 251
ER_NDB_BINLOG_GOT_DIST_PRIV_EVENT_FLUSHING, 245	ER_NDB_BINLOG_UNHANDLED_ERROR_FOR_TABLE, 250
ER_NDB_BINLOG_GOT_SCHEMA_EVENT, 245	ER_NDB_BINLOG_UNKNOWN_NON_DATA_EVENT, 250
ER_NDB_BINLOG_INJECTING_RANDOM_WRITE_FAILURE, 246	ER_NDB_BINLOG_USING_SERVER_ID_0_SLAVES_WILL_N 247
ER_NDB_BINLOG_INJECTOR_DISCARDING_ROW_EVENT 250	ER_NDB_BINLOG_WRITE_TO_NDB_BINLOG_INDEX_FAIL 247
ER_NDB_BINLOG_LATEST_TRX_IN_EPOCH_NOT_IN_BI 252	ER_NDB_BINLOG_WRITING_TO_NDB_BINLOG_INDEX, 246
ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONTE 251	ER_NDB_CANT_ALLOC_GLOBAL_NDB_CLUSTER_CONNE 263
ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_WAITI 251	ER_NDB_CANT_ALLOC_GLOBAL_NDB_OBJECT, 263
ER_NDB_BINLOG_NDBEVENT_EXECUTE_FAILED, 249	ER_NDB_CANT_ALLOC_NDB_CLUSTER_CONNECTION, 263
ER_NDB_BINLOG_NDB_LOG_APPLY_STATUS_FORCING 247	ER_NDB_CANT_FIND_TABLE, 244
	ER_NDB_CANT_PARSE_NDB_CLUSTER_CONNECTION_PO 262
	ER_NDB_CANT_START_CONNECT_THREAD, 263

---

---

ER\_NDB\_CLEANING\_STRAY\_TABLES, 241  
 ER\_NDB\_CLEAR\_SLOCK\_INFO, 244  
 ER\_NDB\_CLUSTER\_FAILURE, 245  
 ER\_NDB\_CLUSTER\_FIND\_ALL\_DBS\_FAIL, 242  
 ER\_NDB\_CLUSTER\_FIND\_ALL\_DBS\_RETRY, 241  
 ER\_NDB\_CLUSTER\_FREE\_SHARE\_INFO, 221  
 ER\_NDB\_CLUSTER\_GENERIC\_MESSAGE, 206  
 ER\_NDB\_CLUSTER\_GET\_SHARE\_INFO, 220  
 ER\_NDB\_CLUSTER\_MARK\_SHARE\_DROPPED\_DESTROYING\_SHARE, 206  
 ER\_NDB\_CLUSTER\_MARK\_SHARE\_DROPPED\_INFO, 221  
 ER\_NDB\_CLUSTER\_OOM\_THD\_NDB, 221  
 ER\_NDB\_CLUSTER\_REAL\_FREE\_SHARE\_DROP\_FAILED, 220  
 ER\_NDB\_CLUSTER\_REAL\_FREE\_SHARE\_INFO, 220  
 ER\_NDB\_CLUSTER\_SCHEMA\_INFO, 206  
 ER\_NDB\_CLUSTER\_WRONG\_NUMBER\_OF\_FUNCTION\_ARGUMENTS, 206  
 ER\_NDB\_COLUMN\_DEFAULTS\_DIFFER, 217  
 ER\_NDB\_COLUMN\_INFO, 217  
 ER\_NDB\_COLUMN\_SHOULD\_NOT\_HAVE\_NATIVE\_DEFAULT, 217  
 ER\_NDB\_CONFLICT\_FN\_PARSE\_ERROR, 248  
 ER\_NDB\_CONFLICT\_FN\_SETUP\_ERROR, 248  
 ER\_NDB\_CONFLICT\_GENERIC\_MESSAGE, 247  
 ER\_NDB\_COULD\_NOT\_GET\_APPLY\_STATUS\_SHARE, 250  
 ER\_NDB\_CPU\_MASK\_TOO\_SHORT, 264  
 ER\_NDB\_CREATE\_EVENT\_OPS\_LOGGING\_INFO, 249  
 ER\_NDB\_CREATING\_SHARE\_IN\_OPEN, 220  
 ER\_NDB\_CREATING\_TABLE, 241  
 ER\_NDB\_DISCARDING\_EVENT\_ID\_VERSION\_MISMATCH, 244  
 ER\_NDB\_DISCARDING\_EVENT\_NO\_OBJ, 244  
 ER\_NDB\_DISCONNECT\_INFO, 217  
 ER\_NDB\_DISCOVERED\_MISSING\_DB, 241  
 ER\_NDB\_DISCOVERED\_REMAINING\_DB, 241  
 ER\_NDB\_DISTRIBUTED\_INFO, 243  
 ER\_NDB\_DISTRIBUTING\_ERR, 275  
 ER\_NDB\_DISTRIBUTION\_COMPLETE, 243  
 ER\_NDB\_DUPLICATE\_NODEID\_IN\_NDB\_CLUSTER\_CONNECTION\_POOL\_NODEIDS, 262  
 ER\_NDB\_EMPTY\_NODEID\_IN\_NDB\_CLUSTER\_CONNECTION\_POOL\_NODEIDS, 262  
 ER\_NDB\_ERROR\_IN\_GET\_AUTO\_INCREMENT, 219  
 ER\_NDB\_ERROR\_IN\_READAUTOINCREMENTVALUE, 218  
 ER\_NDB\_FAILED\_TO\_SET\_UP\_TABLE, 242  
 ER\_NDB\_FIELD\_INFO, 217  
 ER\_NDB\_FLUSHING\_TABLE\_INFO, 241  
 ER\_NDB\_FOUND\_UNCOMMITTED\_AUTOCOMMIT, 218  
 ER\_NDB\_GENERIC\_ERROR, 264  
 ER\_NDB\_HANDLE\_TRAILING\_SHARE\_INFO, 220  
 ER\_NDB\_IGNORING\_UNKNOWN\_EVENT, 246  
 ER\_NDB\_ILLEGAL\_VALUE\_FOR\_NDB\_RECV\_THREAD\_CPU\_MASK, 221  
 ER\_NDB\_INFO\_FAILED\_TO\_CREATE\_NDBINFO, 206  
 ER\_NDB\_INFO\_FAILED\_TO\_INIT\_NDBINFO, 206  
 ER\_NDB\_INFO\_FOUND\_UNEXPECTED\_FIELD\_TYPE, 206  
 ER\_NDB\_INITIALIZE\_GIVEN\_CLUSTER\_PLUGIN\_DISABLED, 220  
 ER\_NDB\_INVALID\_NODEID\_IN\_NDB\_CLUSTER\_CONNECTION\_POOL\_NODEIDS, 262  
 ER\_NDB\_LOG\_ENTRY, 272  
 ER\_NDB\_LOG\_ENTRY\_WITH\_PREFIX, 272  
 ER\_NDB\_METADATA\_MISMATCH\_IN\_FRM\_DISCOVERING, 242  
 ER\_NDB\_MISSING\_FRM\_DISCOVERING, 242  
 ER\_NDB\_NODEID\_NOT\_FIRST\_IN\_NDB\_CLUSTER\_CONNECTION\_POOL\_NODEIDS, 263  
 ER\_NDB\_NODE\_ID\_AND\_MANAGEMENT\_SERVER\_INFO, 217  
 ER\_NDB\_NODE\_INFO, 263  
 ER\_NDB\_NOT\_WAITING\_FOR\_DISTRIBUTING, 243  
 ER\_NDB\_NUMBER\_OF\_CHANNELS, 275  
 ER\_NDB\_OOM\_GET\_NDB\_BLOBS\_VALUE, 241  
 ER\_NDB\_OOM\_IN\_FIX\_UNIQUE\_INDEX\_ATTR\_ORDER, 218  
 ER\_NDB\_POOL\_SIZE\_MUST\_MATCH\_NDB\_CLUSTER\_CONNECTION\_POOL\_SIZE, 262  
 ER\_NDB\_QUERY\_FAILED, 216  
 ER\_NDB\_REMAINING\_OPEN\_TABLES, 250  
 ER\_NDB\_REMAINING\_OPEN\_TABLE\_INFO, 250  
 ER\_NDB\_REPLICATION\_SCHEMA\_ERROR, 45  
 ER\_NDB\_SCHEMA\_DISTRIBUTION\_FAILED, 243  
 ER\_NDB\_SCHEMA\_DISTRIBUTION\_REPORTS\_SUBSCRIBE, 243  
 ER\_NDB\_SCHEMA\_DISTRIBUTION\_REPORTS\_UNSUBSCRIBE, 243  
 ER\_NDB\_SCHEMA\_GENERIC\_MESSAGE, 214  
 ER\_NDB\_SERVER\_ID\_RESERVED\_OR\_TOO\_LARGE, 217  
 ER\_NDB\_SHARE\_ALREADY\_EXISTS, 220  
 ER\_NDB\_SETUP\_TABLE, 242  
 ER\_NDB\_SLAVE\_BINLOG\_MISSING\_INFO\_FOR\_CONFLICT\_DETECTION, 218  
 ER\_NDB\_SLAVE\_CANT\_ALLOCATE\_TABLE\_SHARE, 219  
 ER\_NDB\_SLAVE\_CONFLICT\_DETECTION\_REQUIRES\_TRANSACTION\_CHARACTERISTICS, 218  
 ER\_NDB\_SLAVE\_CONFLICT\_FUNCTION\_REQUIRES\_ROLE, 218



---

ER_NDB_SLAVE_ERROR_IN_UPDATE_CREATE_INFO, 219	ER_NET_ERROR_ON_WRITE, 14
ER_NDB_SLAVE_LOGGING_EXCEPTIONS_TO, 206	ER_NET_FCNTL_ERROR, 14
ER_NDB_SLAVE_LOW_EPOCH_RESOLUTION, 206	ER_NET_OK_PACKET_TOO_LARGE, 74
ER_NDB_SLAVE_MALFORMED_EVENT_RECEIVED_ON_TABLET, 218	ER_NET_PACKETS_OUT_OF_ORDER, 14
ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_SET_TO, 217	ER_NET_PACKET_TOO_LARGE, 14
ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_UNKNOWN, 217	ER_NET_READ_ERROR, 14
ER_NDB_SLAVE_MISSING_DATA_FOR_TIMESTAMP_COLUMN, 206	ER_NET_READ_ERROR_FROM_PIPE, 14
ER_NDB_SLAVE_PARALLEL_WORKERS, 275	ER_NET_READ_INTERRUPTED, 14
ER_NDB_SLAVE_PREVIOUS_EPOCH_NOT_COMMITTED, 205	ER_NET_UNCOMPRESS_ERROR, 14
ER_NDB_SLAVE_SAW_ALREADY_COMMITTED_EPOCH, 205	ER_NET_WAIT_ERROR, 562
ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS, 205	ER_NET_WAIT_ERROR2, 599
ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS_CONSTANT, 205	ER_NET_WRITE_INTERRUPTED, 14
ER_NDB_SLAVE_TOO_MANY_RETRIES, 218	ER_NEW_ABORTING_CONNECTION, 16
ER_NDB_STARTING_CONNECT_THREAD, 263	ER_NO, 3
ER_NDB_TABLES_INITIALLY_READ_ONLY_ON_RECONNECT, 246	ER_NONEXISTING_GRANT, 13
ER_NDB_TABLES_NOT_READY, 182	ER_NONEXISTING_PROC_GRANT, 31
ER_NDB_TABLE_IS_NOT_DISTRIBUTED, 241	ER_NONEXISTING_TABLE_GRANT, 13
ER_NDB_TABLE_OPENED_READ_ONLY, 220	ER_NONPOSITIVE_RADIUS, 108
ER_NDB_THREAD_TIMED_OUT, 241	ER_NONUNIQ_TABLE, 8
ER_NDB_TIMED_OUT_IN_DROP_TABLE, 249	ER_NONUNIQ_TABLE_COLUMN, 28
ER_NDB_TIMEOUT_WHILE_DISTRIBUTING, 242	ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT, 120
ER_NDB_TOO_MANY_CPUS_IN_NDB_RECV_THREAD, 222	ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN, 120
ER_NDB_TRAILING_SHARE_RELEASED_BY_CLOSE_CACHE, 220	ER_NON_GROUPING_FIELD_USED, 35
ER_NDB_TRANS_DEPENDENCY_TRACKER_ERROR, 247	ER_NON_INSERTABLE_TABLE, 36
ER_NDB_UNEXPECTED_RENAME_TYPE, 219	ER_NON_RO_SELECT_DISABLE_TIMER, 71
ER_NDB_USING_NODEID, 263	ER_NON_UNIQ_ERROR, 6
ER_NDB_USING_NODEID_LIST, 263	ER_NON_UPDATABLE_TABLE, 24
ER_NDB_UTIL_THREAD_OOM, 221	ER_NORMAL_SERVER_SHUTDOWN, 527
ER_NDB_WAITING_INFO, 242	ER_NORMAL_SHUTDOWN, 8
ER_NDB_WAITING_INFO_WITH_MAP, 242	ER_NORMAL_MASK_COMPONENT_KEYRING_OCI_MISSING_NAME, 626
ER_NEED_FILE_INSTEAD_OF_DIR, 179	ER_NORMAL_MASK_COMPONENT_SLOT_DEREGISTRATION_SUCCESS, 635
ER_NEED_LOG_BIN, 179	ER_NOTE_COMPONENT_SLOT_REGISTRATION_SUCCESS, 635
ER_NEED_REPREPARE, 44	ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIED, 597
ER_NETWORK_NAMESPACES_NOT_SUPPORTED, 561	ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY, 597
ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG, 562	ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE, 597
ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WRITE, 561	ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR, 597
ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE, 528	ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED, 598
	ER_NOTE_KEYRING_COMPONENT_INITIALIZED, 597
	ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR_FORWARD_ADDRESS, 598
	ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATOR_FORWARD_ADDRESS, 598

---

---

ER\_NOTE\_KEYRING\_COMPONENT\_READ\_DATA\_NOT\_FOUND, SUCH\_USER, 34  
598  
ER\_NOTE\_KEYRING\_COMPONENT\_REMOVE\_FAILED, ER\_NO\_SUPER\_WITHOUT\_USER\_PLUGIN, 196  
598  
ER\_NOTE\_KEYRING\_COMPONENT\_STORE\_FAILED, ER\_NO\_SYSTEM\_SCHEMA\_ACCESS, 91  
598  
ER\_NOTE\_KEYRING\_COMPONENT\_WRITE\_MAXIMUM\_DATA\_LENGTH, ER\_NO\_SYSTEM\_TABLESPACE\_ACCESS, 91  
598  
ER\_NOT\_ALLOWED\_COMMAND, 13 ER\_NO\_SYSTEM\_TABLE\_ACCESS, 91  
ER\_NOT\_ALLOWED\_WITH\_START\_TRANSACTION, ER\_NO\_SYSTEM\_TABLE\_ACCESS\_FOR\_DICTIONARY\_TABLESPACE, 91  
139  
ER\_NOT\_FORM\_FILE, 5 ER\_NO\_SYSTEM\_TABLE\_ACCESS\_FOR\_SYSTEM\_TABLE, 91  
ER\_NOT\_HINT\_UPDATABLE\_VARIABLE, 100 ER\_NO\_SYSTEM\_TABLE\_ACCESS\_FOR\_TABLE, 91  
ER\_NOT\_IMPLEMENTED\_FOR\_CARTESIAN\_SRS, ER\_NO\_SYSTEM\_VIEW\_ACCESS, 98  
107 ER\_NO\_TABLES\_USED, 10  
ER\_NOT\_IMPLEMENTED\_FOR\_GEOGRAPHIC\_SRS, ER\_NO\_THD\_NO\_UUID, 169  
98 ER\_NO\_TRIGGERS\_ON\_SYSTEM\_SCHEMA, 35  
ER\_NOT\_IMPLEMENTED\_FOR\_PROJECTED\_SRS, ER\_NO\_UNIQUE\_LOGFILE, 10  
108 ER\_NPIPE\_CANT\_CREATE, 274  
ER\_NOT\_IMPLEMENTED\_GET\_TABLESPACE\_STATISTICS, ER\_NPIPE\_FAILED\_TO\_INIT\_SECURITY\_DESCRIPTOR, 205  
321 ER\_NPIPE\_FAILED\_TO\_SET\_SECURITY\_DESCRIPTOR, 205  
ER\_NOT\_KEYFILE, 5 ER\_NPIPE\_PIPE\_ALREADY\_IN\_USE, 205  
ER\_NOT\_RIGHT\_NOW, 176 ER\_NULL\_COLUMN\_IN\_INDEX, 12  
ER\_NOT\_SUPPORTED\_AUTH\_MODE, 21 ER\_NULL\_IN\_VALUES\_LESS\_THAN, 41  
ER\_NOT\_SUPPORTED\_YET, 20 ER\_NUMERIC\_JSON\_VALUE\_OUT\_OF\_RANGE, 83  
ER\_NOT\_VALID\_PASSWORD, 62 ER\_OBSOLETE\_FILE\_PRIVILEGE\_FOR\_REPLICATION\_CHECKPOINT, 571  
ER\_NO\_ACCESS\_TO\_NATIVE\_FCT, 92 ER\_OBSOLETE\_REQUIRE\_ROW\_FORMAT\_VIOLATION, 573  
ER\_NO\_BINARY\_LOGGING, 30 ER\_OLD\_FILE\_FORMAT, 35  
ER\_NO\_BINLOG\_ERROR, 39 ER\_OLD\_KEYFILE, 5  
ER\_NO\_CSV\_NO\_LOG\_TABLES, 178 ER\_OLD\_PASSWORDS\_NO\_MIDDLE\_GROUND, 171  
ER\_NO\_DB\_ERROR, 6 ER\_OLD\_TEMPORALS\_UPGRADED, 67  
ER\_NO\_DEFAULT, 20 ER\_ONLY\_FD\_AND\_RBR\_EVENTS\_ALLOWED\_IN\_BINLOG\_STATE, 53  
ER\_NO\_DEFAULT\_FOR\_FIELD, 29 ER\_OPERATION\_NOT\_IMPLEMENTED\_FOR\_SRID\_0\_AND\_4326, 105  
ER\_NO\_DEFAULT\_FOR\_VIEW\_FIELD, 32 ER\_ONLY\_INTEGERS\_ALLOWED, 42  
ER\_NO\_ERROR\_LOG\_PARSER\_CONFIGURED, 591 ER\_ONLY\_ON\_RANGE\_LIST\_PARTITION, 38  
ER\_NO\_FORMAT\_DESCRIPTION\_EVENT\_BEFORE\_BINLOG\_STATE, 43 ER\_OOM, 176  
ER\_NO\_FT\_MATERIALIZED\_SUBQUERY, 70 ER\_OOM\_SAVE\_GTIDS, 527  
ER\_NO\_PARTITION\_FOR\_GIVEN\_VALUE, 39 ER\_OPEN\_AS\_READONLY, 5  
ER\_NO\_PARTITION\_FOR\_GIVEN\_VALUE\_SILENT, 43 ER\_OPEN\_ROLE\_TABLES, 89  
ER\_NO\_PARTS\_ERROR, 38 ER\_OPERAND\_COLUMNS, 21  
ER\_NO\_PATH\_FOR\_SHARED\_LIBRARY, 536 ER\_OPERATION\_NOT\_ALLOWED\_ON\_GR\_SECONDARY, 148  
ER\_NO\_PERMISSION\_TO\_CREATE\_USER, 18 ER\_OPERATION\_NOT\_ALLOWED\_WHILE\_PRIMARY\_CHANGE, 154  
ER\_NO\_REFERENCED\_ROW, 19 ER\_OPTION\_PREVENTS\_STATEMENT, 24  
ER\_NO\_REFERENCED\_ROW\_2, 34 ER\_OPT\_WRONG\_TREE, 162  
ER\_NO\_SECURE\_TRANSPORTS\_CONFIGURED, 83 ER\_OUTOFMEMORY, 5  
ER\_NO\_SESSION\_TEMP, 128 ER\_OUT\_OF\_RESOURCES, 6  
ER\_NO\_SUCH\_DB, 87 ER\_OUT\_OF\_SORTMEMORY, 5  
ER\_NO\_SUCH\_INDEX, 9  
ER\_NO\_SUCH\_TABLE, 13  
ER\_NO\_SUCH\_THREAD, 10

---

ER_PAGE_TRACKING_CANNOT_PURGE, 119	ER_PERFORMANCE_SCHEMA_VERSION_CHANGE, 641
ER_PAGE_TRACKING_NOT_STARTED, 119	ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_BO, 280
ER_PAGE_TRACKING_RANGE_NOT_TRACKED, 119	ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_SH, 281
ER_PARSER_TRACE, 162	ER_PERFSCHEMA_INIT_FAILED, 180
ER_PARSE_ERROR, 7	ER_PERFSCHEMA_TABLES_INIT_FAILED, 282
ER_PARSE_ERROR_IN_DIGEST_FN, 104	ER_PERSISTED_VARIABLES_DECRYPTION_FAILED, 614
ER_PARSING_VIEW, 169	ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED, 614
ER_PARTIAL_REVOKES_EXIST, 129	ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRE, 613
ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXIST, 130	ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT, 614
ER_PARTITIONS_MUST_BE_DEFINED_ERROR, 37	ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE, 614
ER_PARTITION_CLAUSE_ON_NONPARTITIONED, 54	ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND, 613
ER_PARTITION_COLUMN_LIST_ERROR, 47	ER_PERSISTENT_PRIVILEGES_BOOTSTRAP, 281
ER_PARTITION_CONST_DOMAIN_ERROR, 41	ER_PERSIST_ONLY_ACCESS_DENIED_ERROR, 99
ER_PARTITION_ENTRY_ERROR, 37	ER_PERSIST_OPTION_HOST_TRUNCATED, 562
ER_PARTITION_EXCHANGE_DIFFERENT_OPTION, 53	ER_PERSIST_OPTION_STATUS, 321
ER_PARTITION_EXCHANGE_FOREIGN_KEY, 54	ER_PERSIST_OPTION_USER_TRUNCATED, 562
ER_PARTITION_EXCHANGE_PART_TABLE, 53	ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL, 292
ER_PARTITION_EXCHANGE_TEMP_TABLE, 54	ER_PFS_MALLOC_ARRAY_OOM, 294
ER_PARTITION_FIELDS_TOO_LONG, 47	ER_PFS_MALLOC_ARRAY_OVERFLOW, 293
ER_PARTITION_FUNCTION_FAILURE, 39	ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED, 286
ER_PARTITION_FUNCTION_IS_NOT_ALLOWED, 41	ER_PFS_PATH_LOCATIONS_INACCESSIBLE, 536
ER_PARTITION_FUNC_NOT_ALLOWED_ERROR, 37	ER_PID_FILE_PRIV_DIRECTORY_INSECURE, 388
ER_PARTITION_HANDLER_ADMIN_MSG, 296	ER_PK_INDEX_CANT_BE_INVISIBLE, 89
ER_PARTITION_INSTEAD_OF_SUBPARTITION, 54	ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED, 81
ER_PARTITION_MAXVALUE_ERROR, 36	ER_PLUGIN_BAD_OPTIONS, 257
ER_PARTITION_MERGE_ERROR, 41	ER_PLUGIN_CANNOT_BE_UNINSTALLED, 67
ER_PARTITION_MGMT_ON_NONPARTITIONED, 38	ER_PLUGIN_CANT_LOAD, 256
ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW, 275	ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE, 256
ER_PARTITION_NAME, 45	ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS, 257
ER_PARTITION_NOT_DEFINED_ERROR, 37	ER_PLUGIN_CHANGE_IN_COMMON_FAILED_TO_OPEN_FILTER_TABLE, 319
ER_PARTITION_NO_TEMPORARY, 41	ER_PLUGIN_CHANGE_IN_COMMON_FAILED_TO_OPEN_TABLE, 320
ER_PARTITION_REQUIRES_VALUES_ERROR, 36	ER_PLUGIN_DELETE_BUILTIN, 44
ER_PARTITION_WRONG_NO_PART_ERROR, 36	ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS, 216
ER_PARTITION_WRONG_NO_SUBPART_ERROR, 36	ER_PLUGIN_DISABLED, 257
ER_PARTITION_WRONG_VALUES_ERROR, 36	ER_PLUGIN_EXCEPTION_OPERATION_FAILED, 631
ER_PART_EXPR_TOO_LONG, 99	
ER_PASSWORD_ANONYMOUS_USER, 12	
ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHANGE, 129	
ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTH_PLUGIN, 104	
ER_PASSWORD_EXPIRE_ANONYMOUS_USER, 69	
ER_PASSWORD_FORMAT, 62	
ER_PASSWORD_NOT_ALLOWED, 12	
ER_PASSWORD_NO_MATCH, 12	
ER_PATH_IN_DATADIR, 100	
ER_PATH_LENGTH, 49	

---

---

ER\_PLUGIN\_FAILED\_DEINITIALIZATION, 256  
 ER\_PLUGIN\_FAILED\_TO\_OPEN\_TABLE, 533  
 ER\_PLUGIN\_FAILED\_TO\_OPEN\_TABLES, 533  
 ER\_PLUGIN\_FORCING\_SHUTDOWN, 256  
 ER\_PLUGIN\_HAS\_CONFLICTING\_SYSTEM\_VARIABLES, 257  
 ER\_PLUGIN\_HAS\_NONZERO\_REFCOUNT\_AFTER\_DEINITIALIZATION, 256  
 ER\_PLUGIN\_HAS\_NONZERO\_REFCOUNT\_AFTER\_SHUTDOWN, 256  
 ER\_PLUGIN\_INIT\_FAILED, 183  
 ER\_PLUGIN\_INSTALL\_ERROR, 542  
 ER\_PLUGIN\_INVALID\_TABLE\_DEFINITION, 603  
 ER\_PLUGIN\_IS\_NOT\_LOADED, 39  
 ER\_PLUGIN\_IS\_PERMANENT, 51  
 ER\_PLUGIN\_LOAD\_OPTIONS\_IGNORED, 572  
 ER\_PLUGIN\_LOAD\_PARAMETER\_TOO\_LONG, 256  
 ER\_PLUGIN\_NOT\_EARLY, 123  
 ER\_PLUGIN\_NOT\_EARLY\_DUP, 563  
 ER\_PLUGIN\_NO\_INSTALL, 52  
 ER\_PLUGIN\_NO\_INSTALL\_DUP, 563  
 ER\_PLUGIN\_NO\_UNINSTALL, 52  
 ER\_PLUGIN\_OOM, 257  
 ER\_PLUGIN\_PARSING\_OPTIONS\_FAILED, 257  
 ER\_PLUGIN\_REGISTRATION\_DONE, 149  
 ER\_PLUGIN\_REGISTRATION\_FAILED, 256  
 ER\_PLUGIN\_REQUIRES\_REGISTRATION, 149  
 ER\_PLUGIN\_SHUTTING\_DOWN\_PLUGIN, 256  
 ER\_PLUGIN\_UNINSTALL\_ERROR, 542  
 ER\_PLUGIN\_UNKNOWN\_VARIABLE\_TYPE, 257  
 ER\_PLUGIN\_VARIABLE\_MISSING\_NAME, 257  
 ER\_PLUGIN\_VARIABLE\_NOT\_ALLOCATED\_THREAD\_LOCAL, 257  
 ER\_PLUGIN\_VARIABLE\_SET\_READ\_ONLY, 257  
 ER\_POINTLESS\_WITHOUT\_SLOWLOG, 171  
 ER\_POLYGON\_TOO\_LARGE, 110  
 ER\_PREPARE\_FOR\_PRIMARY\_ENGINE, 605  
 ER\_PREPARE\_FOR\_SECONDARY\_ENGINE, 556  
 ER\_PREVENTS\_VARIABLE\_WITHOUT\_RBR, 78  
 ER\_PRIMARY\_CANT\_HAVE\_NULL, 15  
 ER\_PRIVILEGE\_DEREGISTRATION, 637  
 ER\_PRIVILEGE\_REGISTRATION, 637  
 ER\_PRIVILEGE\_SYSTEM\_INIT\_FAILED, 282  
 ER\_PROCACCESS\_DENIED\_ERROR, 29  
 ER\_PROC\_AUTO\_GRANT\_FAIL, 31  
 ER\_PROC\_AUTO\_REVOKE\_FAIL, 31  
 ER\_PROTOCOL\_COMPRESSION\_RESET\_LOG, 570  
 ER\_PS\_MANY\_PARAM, 30  
 ER\_PS\_NO\_RECURSION, 34  
 ER\_QUERY\_CACHE\_DISABLED, 47  
 ER\_QUERY\_INTERRUPTED, 26  
 ER\_QUERY\_ON\_FOREIGN\_DATA\_SOURCE, 33  
 ER\_QUERY\_TIMEOUT, 70  
 ER\_RANGE\_NOT\_INCREASING\_ERROR, 37  
 ER\_READING\_TABLE\_FAILED, 184  
 ER\_READY, 8  
 ER\_READ\_LOG\_EVENT\_FAILED, 291  
 ER\_READ\_ONLY\_MODE, 63  
 ER\_READ\_ONLY\_TRANSACTION, 18  
 ER\_READ\_ONLY\_TRANSACTION\_RUN\_AS\_ROOT, 175  
 ER\_RECORD\_FILE\_FULL, 11  
 ER\_RECOVERING\_TABLE, 258  
 ER\_REDUCED\_DBLWR\_FILE\_CORRUPTED, 639  
 ER\_REDUCED\_DBLWR\_PAGE\_FOUND, 639  
 ER\_REFERENCED\_TRG\_DOES\_NOT\_EXIST, 69  
 ER\_REGEXP\_BAD\_ESCAPE\_SEQUENCE, 106  
 ER\_REGEXP\_BAD\_INTERVAL, 106  
 ER\_REGEXP\_BUFFER\_OVERFLOW, 105  
 ER\_REGEXP\_ERROR, 13  
 ER\_REGEXP\_ILLEGAL\_ARGUMENT, 105  
 ER\_REGEXP\_INDEX\_OUTOFBOUNDS\_ERROR, 106  
 ER\_REGEXP\_INTERNAL\_ERROR, 106  
 ER\_REGEXP\_INVALID\_BACK\_REF, 106  
 ER\_REGEXP\_INVALID\_CAPTURE\_GROUP\_NAME, 128  
 ER\_REGEXP\_INVALID\_FLAG, 130  
 ER\_REGEXP\_INVALID\_RANGE, 107  
 ER\_REGEXP\_LOOK\_BEHIND\_LIMIT, 106  
 ER\_REGEXP\_MAX\_LT\_MIN, 106  
 ER\_REGEXP\_MISMATCHED\_PAREN, 106  
 ER\_REGEXP\_MISSING\_CLOSE\_BRACKET, 107  
 ER\_REGEXP\_MISSING\_FILE, 152  
 ER\_REGEXP\_MISSING\_ICU\_DATADIR, 612  
 ER\_REGEXP\_MISSING\_RESOURCE, 152  
 ER\_REGEXP\_PATTERN\_TOO\_BIG, 107  
 ER\_REGEXP\_RULE\_SYNTAX, 106  
 ER\_REGEXP\_STACK\_OVERFLOW, 107  
 ER\_REGEXP\_STRING\_NOT\_TERMINATED, 105  
 ER\_REGEXP\_TIME\_OUT, 107  
 ER\_REGEXP\_UNIMPLEMENTED, 106  
 ER\_REGEX\_NUMBER\_TOO\_BIG, 142  
 ER\_RELAY\_LOG\_FAIL, 30  
 ER\_RELAY\_LOG\_INIT, 30  
 ER\_RELAY\_LOG\_SPACE\_LIMIT\_DISABLED, 539  
 ER\_RELOAD\_KEYRING\_FAILURE, 146  
 ER\_REMOVED\_SPACES, 35  
 ER\_RENAMED\_NAME, 45  
 ER\_RENAME\_ROLE, 89  
 ER\_REORG\_HASH\_ONLY\_ON\_SAME\_NO, 38  
 ER\_REORG\_NO\_PARAM\_ERROR, 38  
 ER\_REORG\_OUTSIDE\_RANGE, 39  
 ER\_REORG\_PARTITION\_NOT\_EXIST, 38  
 ER\_REPLACE\_INACCESSIBLE\_ROWS, 74  
 ER\_REPLICATION\_INCOMPATIBLE\_TABLE\_WITH\_GIPK, 629  
 ER\_REPLICA\_AM\_INIT\_REPOSITORY, 66

---

ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_SOURCE, 594	ER_REPLICA_CHANNEL_DOES_NOT_EXIST, 75	ER_REPLICA_RELAY_LOG_WRITE_FAILURE, 529
ER_REPLICA_ANON_TO_GTID_IS_LOCAL_OR_UUID_AND_UUID_SOURCE, 594	ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP, 70	ER_REPLICA_SILENT_RETRY_TRANSACTION, 61
ER_REPLICA_CANT_CREATE_CONVERSION, 49	ER_REPLICA_CHANNEL_MUST_STOP, 76	ER_REPLICA_SLAVE_CONNECTION_FAILURE, 529
ER_REPLICA_CANT_USE_TEMPDIR, 239	ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG, 75	ER_REPLICA_SQL_THREAD_MUST_STOP, 70
ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED, 239	ER_REPLICA_CHANNEL_NOT_RUNNING, 76	ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTIDS_RECEIVED, 203
ER_REPLICA_CHANNEL_DOES_NOT_EXIST, 75	ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED, 82	ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_RECEIVED, 203
ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP, 70	ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER, 77	ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_RECEIVED, 203
ER_REPLICA_CHANNEL_MUST_STOP, 76	ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP, 77	ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSING, 204
ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG, 75	ER_REPLICA_CHANNEL_WAS_NOT_RUNNING, 76	ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION_MET, 202
ER_REPLICA_CHANNEL_NOT_RUNNING, 76	ER_REPLICA_CM_INIT_REPOSITORY, 66	ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION_RECEIVED, 203
ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED, 82	ER_REPLICA_CONFIGURATION, 59	ER_REPLICA_THREAD, 18
ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER, 77	ER_REPLICA_CORRUPT_EVENT, 44	ER_REPLICA_WORKER_STOPPED_PREVIOUS_THD_ERROR, 71
ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP, 77	ER_REPLICA_CREATE_EVENT_FAILURE, 528	ER_REQUIRES_PRIMARY_KEY, 15
ER_REPLICA_CHANNEL_WAS_NOT_RUNNING, 76	ER_REPLICA_FATAL_ERROR, 528	ER_REQUIRE_ROW_FORMAT_INVALID_VALUE, 135
ER_REPLICA_CHANNEL_WAS_RUNNING, 76	ER_REPLICA_HAS_MORE_GTIDS_THAN_SOURCE, 68	ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_FAILURE, 161
ER_REPLICA_CM_INIT_REPOSITORY, 66	ER_REPLICA_HEARTBEAT_FAILURE, 529	ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_FAILURE, 161
ER_REPLICA_CONFIGURATION, 59	ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE, 45	ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_FAILURE, 632
ER_REPLICA_CORRUPT_EVENT, 44	ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX, 51	ER_RESERVED_SYNTAX, 30
ER_REPLICA_CREATE_EVENT_FAILURE, 528	ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN, 51	ER_RESERVED_TABLESPACE_NAME, 109
ER_REPLICA_FATAL_ERROR, 528	ER_REPLICA_IGNORED_SSL_PARAMS, 23	ER_RESET_MASTER_TO_VALUE_OUT_OF_RANGE, 92
ER_REPLICA_HAS_MORE_GTIDS_THAN_SOURCE, 68	ER_REPLICA_IGNORED_TABLE, 20	ER_RESET_SOURCE_TO_VALUE_OUT_OF_RANGE, 92
ER_REPLICA_HEARTBEAT_FAILURE, 529	ER_REPLICA_IGNORE_SERVER_IDS, 46	ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER, 46
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE, 45	ER_REPLICA_INCIDENT, 529	ER_RESOURCE_GROUP_BIND_FAILED, 103
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX, 51	ER_REPLICA_KILLED_AFTER_RECONNECT, 292	ER_RESOURCE_GROUP_BUSY, 102
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN, 51	ER_REPLICA_MAX_CHANNELS_EXCEEDED, 76	ER_RESOURCE_GROUP_DISABLED, 102
ER_REPLICA_IGNORED_SSL_PARAMS, 23	ER_REPLICA_MULTIPLE_CHANNELS_CMD, 75	ER_RESOURCE_GROUP_EXISTS, 102
ER_REPLICA_IGNORED_TABLE, 20	ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY, 75	ER_RESOURCE_GROUP_IS_DISABLED, 286
ER_REPLICA_IGNORE_SERVER_IDS, 46	ER_REPLICA_NOT_RUNNING, 17	ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED, 285
ER_REPLICA_INCIDENT, 529	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS, 292	ER_RESOURCE_GROUP_NOT_EXISTS, 102
ER_REPLICA_KILLED_AFTER_RECONNECT, 292	ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL, 110	ER_RESOURCE_GROUP_POST_INIT_FAILED, 281
ER_REPLICA_MAX_CHANNELS_EXCEEDED, 76	ER_REPLICA_RECONNECT_FAILED, 291	ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED, 281
ER_REPLICA_MULTIPLE_CHANNELS_CMD, 75	ER_REPLICA_RELAY_LOG_PURGE_FAILED, 283	ER_RESOURCE_GROUP_VALIDATION_FAILED, 285
ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY, 75	ER_REPLICA_RELAY_LOG_READ_FAILURE, 529	ER_RESTART_RECEIVED_INFO, 299
ER_REPLICA_NOT_RUNNING, 17	ER_REPLICA_RELAY_LOG_TRUNCATE_INFO, 283	ER_RESTART_SERVER_FAILED, 108
ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS, 292		ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT, 287
ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL, 110		ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY, 287
ER_REPLICA_RECONNECT_FAILED, 291		ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE, 287

---

ER_RES_GRP_FAILED_TO_SWITCH_RESOURCE_GROUP,	ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST,
625	592
ER_RES_GRP_FEATURE_NOT_AVAILABLE, 287	ER_RPL_ASYNC_EXECUTING_QUERY, 592
ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED,	ER_RPL_ASYNC_MANAGED_NAME_ADDED, 593
287	ER_RPL_ASYNC_MANAGED_NAME_REMOVED,
ER_RES_GRP_INVALID_THREAD_PRIORITY, 287	593
ER_RES_GRP_INVALID_VCPU_ID, 298	ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTED,
ER_RES_GRP_INVALID_VCPU_RANGE, 297	633
ER_RES_GRP_SET_THREAD_PRIORITY_FAILED,	ER_RPL_ASYNC_READ_FAILOVER_TABLE, 593
286	ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF,
ER_RES_GRP_SET_THR_AFFINITY_FAILED, 286	141
ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED,	ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE,
286	590
ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED,	ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF,
287	140
ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPU_ID_FAILED,	ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL,
287	595
ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_ID_FAILED,	ER_RPL_ASYNC_SENDER_ADDED, 592
287	ER_RPL_ASYNC_SENDER_REMOVED, 592
ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE_GLOBAL_LOCK,	ER_RPL_BINLOG_FILTERS_OOM, 174
626	ER_RPL_BINLOG_MASTER SENDS HEARTBEAT,
ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE_LOCK,	215
626	ER_RPL_BINLOG_MASTER USES CHECKSUM AND SLAVE ID,
ER_RES_GRP_SWITCH_FAILED_UNABLE_TO_APPLY_RESETS_GRP,	215
626	ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED,
ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED,	184
286	ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO,
ER_RETRYING_REPAIR_WITHOUT_QUICK, 258	215
ER_RETRYING_REPAIR_WITH_KEYCACHE, 258	ER_RPL_BINLOG_SOURCE SENDS HEARTBEAT,
ER_REVOKE_GRANTS, 22	215
ER_REWRITER_LOAD_FAILED, 322	ER_RPL_BINLOG_SOURCE USES CHECKSUM AND REPLICATION,
ER_REWRITER_OOM, 322	216
ER_REWRITER_QUERY_ERROR_MSG, 318	ER_RPL_BINLOG_STARTING_DUMP, 215
ER_REWRITER_QUERY_FAILED, 318	ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED,
ER_REWRITER_READ_FAILED, 322	184
ER_REWRITER_TABLE_MALFORMED_ERROR,	ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED,
322	184
ER_ROLE_GRANTED_TO_ITSELF, 145	ER_RPL_CANNOT_OPEN_RELAY_LOG, 609
ER_ROLE_NOT_GRANTED, 89	ER_RPL_CANT_ADD_DO_TABLE, 177
ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG,	ER_RPL_CANT_ADD_IGNORE_TABLE, 177
291	ER_RPL_CANT_CREATE_REPLICA_THREAD, 227
ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET,	ER_RPL_CANT_CREATE_SLAVE_THREAD, 227
54	ER_RPL_CANT_FIND_FOLLOWUP_FILE, 233
ER_ROW_DOES_NOT_MATCH_PARTITION, 54	ER_RPL_CANT_HAVE_SAME_BASENAME, 277
ER_ROW_IN_WRONG_PARTITION, 65	ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO,
ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR,	240
187	ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_RLI_INIT_INFO,
ER_ROW_IS_REFERENCED, 19	240
ER_ROW_IS_REFERENCED_2, 34	ER_RPL_CANT_MAKE_PATHS, 179
ER_ROW_SINGLE_PARTITION_FIELD_ERROR, 47	ER_RPL_CANT_OPEN_INFO_TABLE, 207
ER_RPL_AM_INIT_INFO_MSG, 296	ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO,
ER_RPL_ASYNC_CHANNEL_CANT_CONNECT, 592	240
ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM,	ER_RPL_CANT_OPEN_LOG_IN_RLI_INIT_INFO,
592	240

ER_RPL_CANT_SCAN_INFO_TABLE, 207	ER_RPL_ERROR_CREATING_RELAY_LOG_INFO,
ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKU	209,
125	ER_RPL_ERROR_LOOKING_FOR_LOG, 233
ER_RPL_CANT_STOP_SLAVE_WHILE_LOCKED_BACKU	ER_RPL_ERROR_READING_MASTER_CONFIGURATION,
125	255
ER_RPL_CHANGING_APPLIER_METADATA_REPO_TYPE	ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGUR
208	253
ER_RPL_CHANGING_RELAY_LOG_INFO_REPO_TYPE	ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGUR
208	253
ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_I	ER_RPL_ERROR_READING_SOURCE_CONFIGURATION,
208	255
ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPO	ER_RPL_ERROR_WRITING_MASTER_CONFIGURATION,
207	255
ER_RPL_CORRUPTED_INFO_TABLE, 207	ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION
ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE,	241
207	ER_RPL_ERROR_WRITING_SLAVE_WORKER_CONFIGUR
ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MAS	TER_KEY,
119	ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION,
ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT,	255
119	ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE,
ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY,	211
117	ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE,
ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY,	211
117	ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKER
ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY,	209
117	ER_RPL_FAILED_TO_DELETE_FROM_SLAVE_WORKERS
ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS,	209
117	ER_RPL_FAILED_TO_OPEN_INFO_FILE, 211
ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY,	ER_RPL_FAILED_TO_OPEN_RELAY_LOG, 254
117	ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO_F
ER_RPL_ENCRYPTION_HEADER_ERROR, 117	209
ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY,	ER_RPL_FAILED_TO_RESET_STATE_IN_SLAVE_INFO_RE
117	209
ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED,	ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX, 239
117	ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL,
ER_RPL_ENCRYPTION_KEY_NOT_FOUND, 117	292
ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAIL	ED, ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED,
118	282
ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION	ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED,
118	282
ER_RPL_ERROR_CHANGING_APPLIER_METADATA_REPO	TYPE, ER_RPL_GTID_LOG_EVENT_IN_STREAM, 213
209	ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE,
ER_RPL_ERROR_CHANGING_CONNECTION_METADATA	211, ER_REPO_TYPE,
208	ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONS
ER_RPL_ERROR_CHANGING_MASTER_INFO_REPO_T	YPE,
208	ER_RPL_GTID_TABLE_CANNOT_OPEN, 164
ER_RPL_ERROR_CHANGING_RELAY_LOG_INFO_REPO	TYPE, ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT
209	542
ER_RPL_ERROR_CHECKING_REPOSITORY, 210	ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT,
ER_RPL_ERROR_CREATING_APPLIER_METADATA,	526
209	ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE,
ER_RPL_ERROR_CREATING_CONNECTION_METADATA	526
208	ER_RPL_GTID_UNSAFE_STMT_ON_TEMPORARY_TABLE,
ER_RPL_ERROR_CREATING_MASTER_INFO, 208	526

---

ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR, 214	ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR,
ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX,	225
207	ER_RPL_MTS_RECOVERY_SUCCESSFUL, 226
ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX,	ER_RPL_MTS_SLAVE_COORDINATOR_HAS_WAITED,
207	254
ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION,	ER_RPL_MTS_STATISTICS, 230
607	ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITO
ER_RPL_INFINITY_DENIED, 182	210
ER_RPL_INFINITY_IGNORED, 182	ER_RPL_OPEN_INDEX_FILE_FAILED, 240
ER_RPL_INFO_DATA_TOO_LONG, 54	ER_RPL_PLEASE_USE_OPTION_RELAY_LOG, 240
ER_RPL_IO_THREAD_KILLED, 291	ER_RPL_PLUGIN_FUNCTION_FAILED, 184
ER_RPL_KILL_OLD_DUMP_THREAD_ENCOUNTERED,	ER_RPL_RECOVERY_ERROR, 225
642	ER_RPL_RECOVERY_ERROR_FREEING_IO_CACHE,
ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWE	225
232	ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG,
ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWE	224
231	ER_RPL_RECOVERY_FILE_MASTER_POS_INFO,
ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY	225
239	ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO,
ER_RPL_MTA_ALLOW_COMMIT_OUT_OF_ORDER,	225
642	ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_IND
ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED,	225
226	ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER,
ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM	224
234	ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE,
ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA	224
233	ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUIRE
ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA	225
233	FOR_WORKER,
ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG,	225
226	ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION_CHAN
ER_RPL_MTA_RECOVERY_COMPLETE, 230	240
ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDI	240
226	ATOR, RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY,
ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR,	240
226	613
ER_RPL_MTA_RECOVERY_SUCCESSFUL, 227	ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLONE,
ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED,	576
254	ER_RPL_REPLICA_ADDITIONAL_ERROR_INFO_FROM_DA,
ER_RPL_MTA_STATISTICS, 230	235
ER_RPL_MTS_AUTOMATIC_RECOVERY_FAILED,	ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_MODE
226	224
ER_RPL_MTS_CHECKPOINT_PERIOD_DIFFERS_FROM	228
233	ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_METADATA,
ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO,	233
233	ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER,
ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO	230
233	FOR_WORKER, ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION,
ER_RPL_MTS_RECOVERY_CANT_OPEN_RELAY_LOG,	224
226	ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNEL,
ER_RPL_MTS_RECOVERY_COMPLETE, 230	224
ER_RPL_MTS_RECOVERY_FAILED_TO_START_COORDI	224
226	ATOR, ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNEL,
	ER_RPL_REPLICA_CANT_USE_CHARSET, 237

---



---

ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICA_FROM_RESERVED,	MONITOR_IO_THREAD_RECONNECT_
237	593
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_FROM_RESERVED,	NEW_C_M_NEEDS_REPOS_TYPE_OTH
633	239
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_FROM_RESERVED,	REPLICA_NEXT_LOG_IS_ACTIVE, 238
633	ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE, 238
ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_LIST,	RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CON
210	237
ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE,	RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_NON
229	573
ER_RPL_REPLICA_ERROR_INFO_FROM_DA, 235	ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE
ER_RPL_REPLICA_ERROR_LOADING_USER_DEFINED,	LIBRARY,
236	ER_RPL_REPLICA_REPORT_HOST_TOO_LONG,
ER_RPL_REPLICA_ERROR_READING_FROM_SERVER,	228
229	ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG,
ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS,	238
238	ER_RPL_REPLICA_REPORT_USER_TOO_LONG,
ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP,	228
231	ER_RPL_REPLICA_RESET_FILTER_OPTIONS, 284
ER_RPL_REPLICA_ERROR_RETRYING, 229	ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS,
ER_RPL_REPLICA_ERROR_RUNNING_QUERY,	228
236	ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED,
ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL_FROM_SOURCE,	CONNECTION_METADATA,
211	ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED_HOST
ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER_BINLOG,	INFO_REPOSITORIES,
223	ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED,
ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_METADATA,	METADATA_STRUCTURE,
210	ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CH
ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA,	METADATA_STRUCTURE,
211	ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECT
ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HASH,	573
234	ER_RPL_REPLICA_SQL_THREAD_EXITING, 236
ER_RPL_REPLICA_FILTER_CREATE_FAILED, 283	ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_E
ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD,	236,
231	ER_RPL_REPLICA_SQL_THREAD_STARTING, 235
ER_RPL_REPLICA_GENERIC_MESSAGE, 210	ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_PRIV
ER_RPL_REPLICA_GLOBAL_FILTERS_COPY_FAILED,	571
284	ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIME
ER_RPL_REPLICA_INCORRECT_CHANNEL, 276	526
ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE,	ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM,
276	232
ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_REPLICATION_PHASES,	ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM,
232	227
ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SOURCE,	RPL_WORKER_THREAD_CREATION_FAILED
231	234
ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE,	RPL_WORKER_THREAD_CREATION_FAILED
237	234
ER_RPL_REPLICA_IO_THREAD_EXITING, 232	ER_RPL_REPO_HAS_GAPS, 165
ER_RPL_REPLICA_IO_THREAD_KILLED, 231	ER_RPL_REPO_SHOULD_BE_TABLE, 208
ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIME_OUT,	RPL_REWRITEDB_EMPTY_FROM, 178
526	ER_RPL_REWRITEDB_EMPTY_TO, 178
ER_RPL_REPLICA_IO_THREAD_WAS_KILLED, 227	ER_RPL_REWRITEDB_MISSING_ARROW, 178
ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING,	ER_RPL_RLI_INIT_INFO_MSG, 296
593	ER_RPL_SERVER_ID_MISSING, 227

---

ER_RPL_SLAVE_ADDITIONAL_ERROR_INFO_FROM_DAEMON	235	ER_RPL_SLAVE_INCORRECT_CHANNEL,	276
ER_RPL_SLAVE_APPLY_LOG_EVENT_FAILED_INVALID_ID	573	ER_RPL_SLAVE_INSECURE_CHANGE_MASTER,	270
ER_RPL_SLAVE_AUTO_POSITION_IS_1_AND_GTID_MODE	223	NON_ROW_FORMAT,	
ER_RPL_SLAVE_CANT_FLUSH_MASTER_INFO_FILE,	228	ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_RELAY	
ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER,	232	IO_THREAD_IS_OFF,	212
ER_RPL_SLAVE_CANT_INIT_RELAY_LOG_POSITION,	230	ER_RPL_SLAVE_IO_THREAD_CANT_REGISTER_ON_MASTER	
ER_RPL_SLAVE_CANT_START_SLAVE_FOR_CHANNEL,	224	ER_RPL_SLAVE_IO_THREAD_DETECTED_UNEXPECTED_EVENT	
ER_RPL_SLAVE_CANT_STOP_SLAVE_FOR_CHANNEL,	224	ER_RPL_SLAVE_IO_THREAD_EXITING,	232
ER_RPL_SLAVE_CANT_USE_CHARSET,	237	ER_RPL_SLAVE_IO_THREAD_KILLED,	231
ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION	237	ER_RPL_SLAVE_IO_THREAD_STOP_CMD_EXEC_TIMEOUT,	526
ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION	230	ER_RPL_SLAVE_IO_THREAD_WAS_KILLED,	227
ER_RPL_SLAVE_COULD_NOT_CREATE_CHANNEL_LISTENER	210	ER_RPL_SLAVE_MASTER_UUID_HAS_CHANGED,	227
ER_RPL_SLAVE_DUMP_THREAD_KILLED_BY_MASTER,	229	ER_RPL_SLAVE_NDB_TABLES_NOT_AVAILABLE,	
ER_RPL_SLAVE_ERROR_INFO_FROM_DAEMON,	235	ION_RESUMED,	
ER_RPL_SLAVE_ERROR_LOADING_USER_DEFINED_LIBRARIES	236	ER_RPL_SLAVE_NEW_MASTER_INFO_NEEDS_REPOS_TYPE	
ER_RPL_SLAVE_ERROR_READING_FROM_SERVER,	229	ION_STARTED,	
ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENT	238	ER_RPL_SLAVE_NEXT_LOG_IS_ACTIVE,	238
ER_RPL_SLAVE_ERROR_REQUESTING_BINLOG_DUMP	231	ER_RPL_SLAVE_NEXT_LOG_IS_INACTIVE,	238
ER_RPL_SLAVE_ERROR_RETRYING,	229	ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION	
ER_RPL_SLAVE_ERROR_RUNNING_QUERY,	236	ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_NON_ROW_FORMAT	
ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM_MASTER_INFO	211	ER_RPL_SLAVE_READ_INVALID_EVENT_FROM_MASTER,	236
ER_RPL_SLAVE_FAILED_TO_CREATE_OR_RECOVER_INFORMATION	223	ER_RPL_SLAVE_REPORT_HOST_TOO_LONG,	228
ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE	210	ER_RPL_SLAVE_REPORT_PASSWORD_TOO_LONG,	229
ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRUCTURE	211	ER_RPL_SLAVE_REPORT_USER_TOO_LONG,	228
ER_RPL_SLAVE_FAILED_TO_INIT_PARTITIONS_HASH,	234	ER_RPL_SLAVE_RESET_FILTER_OPTIONS,	284
ER_RPL_SLAVE_FILTER_CREATE_FAILED,	283	ER_RPL_SLAVE_SECONDS_BEHIND_MASTER_DUBIOUS,	228
ER_RPL_SLAVE_FLUSH_RELAY_LOGS_NOT_ALLOWED	276	ER_RPL_SLAVE_SKIP_COUNTER_EXECUTED,	235
ER_RPL_SLAVE_FORCING_TO_RECONNECT_IO_THREAD	231	ER_RPL_SLAVE_SLAVE_SQL_THREAD_DETECTED_UNEXPECTED_EVENT	
ER_RPL_SLAVE_GENERIC_MESSAGE,	210	ER_RPL_SLAVE_STOPPING_SLAVE_THREADS_THREAD_EXITING,	236
ER_RPL_SLAVE_GLOBAL_FILTERS_COPY_FAILED,	283	ER_RPL_SLAVE_SQL_THREAD_IO_ERROR_READING_EVENT	
		ER_RPL_SLAVE_STOPPING_SLAVE_THREADS_THREAD_EXITING,	236
		ER_RPL_SLAVE_SQL_THREAD_STARTING,	235
		ER_RPL_SLAVE_SQL_THREAD_STARTING_WITH_PRIVILEGES	
		ER_RPL_SLAVE_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT,	525
		ER_RPL_SLAVE_STOPPING_AS_MASTER_OOM,	
		ER_RPL_SLAVE_STOPPING_SLAVE_THREADS_THREAD_EXITING,	236
		ER_RPL_SLAVE_USES_CHECKSUM_AND_MASTER_PRE_50,	
		ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED,	234
		ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED_WITHOUT_ERROR	

---

ER\_RPL\_SSL\_INFO\_IN\_CONNECTION\_METADATA\_IGNORED, 172  
255  
ER\_RPL\_SSL\_INFO\_IN\_MASTER\_INFO\_IGNORED, 173  
255  
ER\_RPL\_TIMESTAMPS\_RETURNED\_TO\_NORMAL, 173  
282  
ER\_RPL\_TRX\_DELEGATES\_INIT\_FAILED, 183  
ER\_RPL\_UNEXPECTED\_BEGIN\_IN\_STREAM, 213  
ER\_RPL\_UNEXPECTED\_COMMIT\_ROLLBACK\_OR\_XID\_ERROR, 213  
ER\_RPL\_UNEXPECTED\_XA\_ROLLBACK\_IN\_STREAM, 213  
ER\_RPL\_UNSUPPORTED\_UNIGNORABLE\_EVENT\_IN\_STREAM, 213  
ER\_RPL\_WORKER\_CANT\_FIND\_NEXT\_RELAY\_LOG, 254  
ER\_RPL\_WORKER\_CANT\_READ\_RELAY\_LOG, 254  
ER\_RPL\_WORKER\_ID\_IS, 207  
ER\_RPL\_ZOMBIE\_ENCOUNTERED, 164  
ER\_RUNNING\_APPLIER\_PREVENTS\_SWITCH\_GLOBAL\_INFORM, 112  
ER\_RUN\_HOOK\_ERROR, 78  
ER\_SAME\_NAME\_PARTITION, 38  
ER\_SAME\_NAME\_PARTITION\_FIELD, 47  
ER\_SCHEDULER\_KILLING, 168  
ER\_SCHEDULER\_STARTED, 167  
ER\_SCHEDULER\_STOPPED, 167  
ER\_SCHEDULER\_STOPPING\_FAILED\_TO\_CREATE\_WORKER, 168  
ER\_SCHEDULER\_STOPPING\_FAILED\_TO\_GET\_EVENT, 168  
ER\_SCHEDULER\_WAITING, 167  
ER\_SCHEMA\_DIR\_CREATE\_FAILED, 105  
ER\_SCHEMA\_DIR\_EXISTS, 105  
ER\_SCHEMA\_DIR\_MISSING, 105  
ER\_SCHEMA\_DIR\_UNKNOWN, 105  
ER\_SCHEMA\_NAME\_IN\_UPPER\_CASE\_NOT\_ALLOWED, 575  
ER\_SCHEMA\_NAME\_IN\_UPPER\_CASE\_NOT\_ALLOWED\_FOR\_SCHEMA, 575  
ER\_SCHEMA\_READ\_ONLY, 140  
ER\_SDI\_GET\_KEYS\_INVALID\_TABLESPACE, 146  
ER\_SDI\_OPERATION\_FAILED, 103  
ER\_SDI\_OPERATION\_FAILED\_MISSING\_RECORD, 136  
ER\_SECONDARY\_ENGINE, 128  
ER\_SECONDARY\_ENGINE\_DDL, 129  
ER\_SECONDARY\_ENGINE\_DDL\_FAILED, 639  
ER\_SECONDARY\_ENGINE\_PLUGIN, 127  
ER\_SECOND\_PASSWORD\_CANNOT\_BE\_EMPTY, 127  
ER\_SECURE\_AUTH\_VALUE\_UNSUPPORTED, 170  
ER\_SECURE\_TRANSPORT\_REQUIRED, 83  
ER\_SEC\_FILE\_PRIV\_ARGUMENT\_TOO\_LONG, 173  
ER\_SEC\_FILE\_PRIV\_CANT\_ACCESS\_DIR, 172  
ER\_SEC\_FILE\_PRIV\_CANT\_STAT, 173  
ER\_SEC\_FILE\_PRIV\_DIRECTORY\_INSECURE, 173  
ER\_SEC\_FILE\_PRIV\_DIRECTORY\_PERMISSIONS, 173  
ER\_SEC\_FILE\_PRIV\_EMPTY, 172  
ER\_SEC\_FILE\_PRIV\_IGNORED, 172  
ER\_SEC\_FILE\_PRIV\_NULL, 172  
ER\_SEMI\_SYNC\_ADD\_ACK\_TO\_SLOT, 308  
ER\_SEMI\_SYNC\_BINLOG\_REPLY\_IS\_AHEAD, 306  
ER\_SEMI\_SYNC\_BINLOG\_WRITE\_OUT\_OF\_ORDER, 306  
ER\_SEMI\_SYNC\_CLEARED\_ACTIVE\_TRANSACTION\_TILL\_POINT, 304  
ER\_SEMI\_SYNC\_CLEARED\_ALL\_ACTIVE\_TRANSACTION\_NODES, 304  
ER\_SEMI\_SYNC\_DISABLED\_ON\_MASTER, 305  
ER\_SEMI\_SYNC\_DISABLED\_ON\_SOURCE, 305  
ER\_SEMI\_SYNC\_EXECUTION\_FAILED\_ON\_MASTER, 311  
ER\_SEMI\_SYNC\_EXECUTION\_FAILED\_ON\_SOURCE, 311  
ER\_SEMI\_SYNC\_FAILED\_REGISTER\_REPLICA\_TO\_RECEIVER, 309  
ER\_SEMI\_SYNC\_FAILED\_REGISTER\_SLAVE\_TO\_RECEIVER, 309  
ER\_SEMI\_SYNC\_FAILED\_TO\_ALLOCATE\_TRX\_NODE, 304  
ER\_SEMI\_SYNC\_FAILED\_TO\_INSERT\_TRX\_NODE, 307  
ER\_SEMI\_SYNC\_FAILED\_TO\_START\_ACK\_RECEIVER\_THREAD, 308  
ER\_SEMI\_SYNC\_FAILED\_TO\_STOP\_ACK\_RECEIVER\_THREAD, 312  
ER\_SEMI\_SYNC\_FAILED\_TO\_WAIT\_ON\_DUMP\_SOCKET, 308  
ER\_SEMI\_SYNC\_FORCED\_SHUTDOWN, 305  
ER\_SEMI\_SYNC\_FUNCTION\_CALLED\_TWICE, 305  
ER\_SEMI\_SYNC\_INIT\_WAIT\_POS, 306  
ER\_SEMI\_SYNC\_INSERT\_LOG\_INFO\_IN\_ENTRY, 304  
ER\_SEMI\_SYNC\_MASTER\_FAILED\_ON\_NET\_FLUSH, 308  
ER\_SEMI\_SYNC\_MASTER\_GOT\_REPLY\_AT\_POS, 306  
ER\_SEMI\_SYNC\_MASTER\_OOM, 305  
ER\_SEMI\_SYNC\_MASTER\_SIGNAL\_ALL\_WAITING\_THREADS, 306  
ER\_SEMI\_SYNC\_MASTER\_TRX\_WAIT\_POS, 306  
ER\_SEMI\_SYNC\_MISSING\_MAGIC\_NO\_FOR\_SEMI\_SYNC\_PACKET, 310  
ER\_SEMI\_SYNC\_MOVE\_BACK\_WAIT\_POS, 306

---

---

ER_SEMISYNC_NOT_SUPPORTED_BY_MASTER, 312	ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD, 309
ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE, 312	ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA, 309
ER_SEMISYNC_NO_SPACE_IN_THE_PKT, 307	ER_SEMISYNC_STOP_BINLOG_DUMP_TO_SLAVE, 309
ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY, 304	ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO, 307
ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER, 308	ER_SEMISYNC_TRACE_ENTER_FUNC, 303
ER_SEMISYNC_REPLICA_NET_FLUSH_REPLY_FAILED, 311	ER_SEMISYNC_TRACE_EXIT, 303
ER_SEMISYNC_REPLICA_REPLY, 310	ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE, 303
ER_SEMISYNC_REPLICA_REPLY_WITH_BINLOG_INFO, 311	ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE, 303
ER_SEMISYNC_REPLICA_SEND_REPLY_FAILED, 311	ER_SEMISYNC_TRX_SKIPPED_AT_POS, 307
ER_SEMISYNC_REPLICA_SET_FAILED, 312	ER_SEMISYNC_UNREGISTERED_REPLICATOR, 310
ER_SEMISYNC_REPLICA_START, 310	ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER, 310
ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE, 305	ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER, 310
ER_SEMISYNC_REPLY_MAGIC_NO_ERROR, 304	ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED, 309
ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL, 304	ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK, 308
ER_SEMISYNC_RPL_ENABLED_ON_MASTER, 305	ER_SEMISYNC_UPDATE_EXISTING_SLAVE_ACK, 308
ER_SEMISYNC_RPL_ENABLED_ON_SOURCE, 305	ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT, 307
ER_SEMISYNC_RPL_INIT_FOR_TRX, 304	ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT_TRX, 307
ER_SEMISYNC_RPL_SWITCHED_OFF, 307	ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT, 307
ER_SEMISYNC_RPL_SWITCHED_ON, 307	ER_SERVERID_TOO_LARGE, 182
ER_SEMISYNC_SERVER_REPLY, 305	ER_SERVER_ACL_TABLE_ERROR, 532
ER_SEMISYNC_SLAVE_NET_FLUSH_REPLY_FAILED, 311	ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_C, 557
ER_SEMISYNC_SLAVE_REPLY, 310	ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CL, 557
ER_SEMISYNC_SLAVE_REPLY_WITH_BINLOG_INFO, 311	ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION, 561
ER_SEMISYNC_SLAVE_SEND_REPLY_FAILED, 311	ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2, 531
ER_SEMISYNC_SLAVE_SET_FAILED, 312	ER_SERVER_CANT_OPEN_FILE, 531
ER_SEMISYNC_SLAVE_START, 310	ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V, 532
ER_SEMISYNC_SOCKET_FD_TOO_LARGE, 310	ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDAT, 532
ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH, 308	ER_SERVER_COST_FAILED_TO_READ, 212
ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS, 306	ER_SERVER_COST_INVALID_COST_CONSTANT, 212
ER_SEMISYNC_SOURCE_OOM, 305	ER_SERVER_COST_UNKNOWN_COST_CONSTANT, 212
ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THRE, 306	ER_SERVER_DISK_FULL_NOWAIT, 531
ER_SEMISYNC_SOURCE_TRX_WAIT_POS, 306	
ER_SEMISYNC_STARTING_ACK_RECEIVER_THD, 308	
ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA, 309	
ER_SEMISYNC_START_BINLOG_DUMP_TO_SLAVE, 309	

---

ER_SERVER_DOWNGRADE_FROM_VERSION, 640	ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVER
ER_SERVER_DOWNGRADE_STATUS, 640	548
ER_SERVER_FILE_NOT_FOUND, 531	ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE,
ER_SERVER_FILE_USED, 531	549
ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE	ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_M
542	549
ER_SERVER_HANDLER_ERROR, 531	ER_SERVER_SHUTDOWN, 7
ER_SERVER_INIT_COMPILED_IN_COMMANDS,	ER_SERVER_SHUTDOWN_COMPLETE, 277
296	ER_SERVER_SHUTDOWN_INFO, 535
ER_SERVER_ISNT_AVAILABLE, 84	ER_SERVER_SLAVE_CONVERSION_FAILED, 532
ER_SERVER_IS_IN_SECURE_AUTH_MODE, 23	ER_SERVER_SLAVE_IGNORED_TABLE, 533
ER_SERVER_MASTER_FATAL_ERROR_READING_BINLOG,	ER_SERVER_SLAVE_INIT_QUERY_FAILED, 532
528	ER_SERVER_SLAVE_MI_INIT_REPOSITORY, 530
ER_SERVER_NET_PACKET_TOO_LARGE, 530	ER_SERVER_SLAVE_RLI_INIT_REPOSITORY, 530
ER_SERVER_NEW_ABORTING_CONNECTION, 531	ER_SERVER_SOURCE_FATAL_ERROR_READING_BINLOG,
ER_SERVER_NOT_FORM_FILE, 531	528
ER_SERVER_NO_SESSION_TO_SEND_TO, 530	ER_SERVER_STARTUP_ADMIN_INTERFACE, 549
ER_SERVER_NO_SYSTEM_TABLE_ACCESS, 530	ER_SERVER_STARTUP_MSG, 280
ER_SERVER_OFFLINE_MODE, 71	ER_SERVER_TABLE_CHECK_FAILED, 532
ER_SERVER_OUTOFMEMORY, 280	ER_SERVER_TEST_MESSAGE, 533
ER_SERVER_OUT_OF_RESOURCES, 280	ER_SERVER_UNKNOWN_ERROR, 530
ER_SERVER_OUT_OF_SORTMEMORY, 531	ER_SERVER_UNKNOWN_SYSTEM_VARIABLE, 530
ER_SERVER_RECORD_FILE_FULL, 531	ER_SERVER_UPGRADE_CHECKING_DB, 560
ER_SERVER_REPLICA_AM_INIT_REPOSITORY,	ER_SERVER_UPGRADE_EMPTY_SYS, 559
530	ER_SERVER_UPGRADE_FAILED, 558
ER_SERVER_REPLICA_CM_INIT_REPOSITORY,	ER_SERVER_UPGRADE_FROM_VERSION, 553
530	ER_SERVER_UPGRADE_HELP_TABLE_STATUS,
ER_SERVER_REPLICA_CONVERSION_FAILED,	561
532	ER_SERVER_UPGRADE_INFO_FILE, 559
ER_SERVER_REPLICA_IGNORED_TABLE, 533	ER_SERVER_UPGRADE_MYSQL_TABLES, 559
ER_SERVER_REPLICA_INIT_QUERY_FAILED, 532	ER_SERVER_UPGRADE_NO_SYS_VERSION, 559
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT,	ER_SERVER_UPGRADE_OFF, 558
552	ER_SERVER_UPGRADE_PENDING, 558
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY,	ER_SERVER_UPGRADE_REPAIR_REQUIRED, 559
547	ER_SERVER_UPGRADE_REPAIR_STATUS, 559
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE	ER_SERVER_UPGRADE_SKIP, 558
548	ER_SERVER_UPGRADE_STATUS, 559
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE	ER_SERVER_UPGRADE_SYSTEM_TABLES, 559
548	ER_SERVER_UPGRADE_SYS_SCHEMA, 559
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE	ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT,
548	LOGS,
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE	560
548	KEY, ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED,
ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR,	560
548	ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE,
ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER	560
549	KEY, ER_SERVER_UPGRADE_SYS_VERSION_EMPTY,
ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID	559
548	KEY, ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED,
ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXP	553
548	ER_SERVER_WARN_DEPRECATED, 556
ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND,	ER_SERVER_WRONG_VALUE_FOR_VAR, 541
547	ER_SESSION_WAS_KILLED, 84
	ER_SETNS_FAILED, 562
	ER_SET_CONSTANTS_ONLY, 18

---

---

ER\_SET\_EVENT\_FAILED, 536  
 ER\_SET\_PASSWORD\_AUTH\_PLUGIN, 50  
 ER\_SET\_PASSWORD\_AUTH\_PLUGIN\_ERROR, 155  
 ER\_SET\_STATEMENT\_CANNOT\_INVOKE\_FUNCTION, 57  
 ER\_SE\_TYPECODE\_CONFLICT, 187  
 ER\_SHA256\_PASSWORD\_SECOND\_PASSWORD\_USED, 550  
 ER\_SHAPE\_PREDICTION\_UDF, 157  
 ER\_SHARED\_TABLESPACE\_USED\_BY\_PARTITIONED\_TABLES, 543  
 ER\_SHA\_PWD\_AUTH\_REQUIRES\_RSA\_OR\_SSL, 319  
 ER\_SHA\_PWD\_FAILED\_TO\_GENERATE\_MULTI\_ROUND\_HASH, 319  
 ER\_SHA\_PWD\_FAILED\_TO\_PARSE\_AUTH\_STRING, 319  
 ER\_SHA\_PWD\_RSA\_KEY\_TOO\_LONG, 319  
 ER\_SHA\_PWD\_SALT\_FOR\_USER\_CORRUPT, 320  
 ER\_SHUTDOWN\_COMPLETE, 8  
 ER\_SHUTTING\_DOWN\_REPLICA\_THREADS, 174  
 ER\_SHUTTING\_DOWN\_SLAVE\_THREADS, 174  
 ER\_SIGNAL\_BAD\_CONDITION\_TYPE, 46  
 ER\_SIGNAL\_EXCEPTION, 46  
 ER\_SIGNAL\_NOT\_FOUND, 46  
 ER\_SIGNAL\_WARN, 46  
 ER\_SIZE\_OVERFLOW\_ERROR, 39  
 ER\_SKIP\_UPDATING\_METADATA\_IN\_SE\_RO\_MODE, 290  
 ER\_SLAVE\_ANONYMOUS\_TO\_GTID\_IS\_LOCAL\_OR\_UIO, 593  
 ER\_SLAVE\_CANT\_CREATE\_CONVERSION, 49  
 ER\_SLAVE\_CANT\_USE\_TEMPDIR, 239  
 ER\_SLAVE\_CHANGE\_MASTER\_TO\_EXECUTED, 239  
 ER\_SLAVE\_CHANNEL\_DOES\_NOT\_EXIST, 75  
 ER\_SLAVE\_CHANNEL\_IO\_THREAD\_MUST\_STOP, 70  
 ER\_SLAVE\_CHANNEL\_MUST\_STOP, 76  
 ER\_SLAVE\_CHANNEL\_NAME\_INVALID\_OR\_TOO\_LONG, 75  
 ER\_SLAVE\_CHANNEL\_NOT\_RUNNING, 76  
 ER\_SLAVE\_CHANNEL\_OPERATION\_NOT\_ALLOWED, 82  
 ER\_SLAVE\_CHANNEL\_SQL\_SKIP\_COUNTER, 77  
 ER\_SLAVE\_CHANNEL\_SQL\_THREAD\_MUST\_STOP, 77  
 ER\_SLAVE\_CHANNEL\_WAS\_NOT\_RUNNING, 76  
 ER\_SLAVE\_CHANNEL\_WAS\_RUNNING, 76  
 ER\_SLAVE\_CONFIGURATION, 59  
 ER\_SLAVE\_CONVERSION\_FAILED, 49  
 ER\_SLAVE\_CORRUPT\_EVENT, 43  
 ER\_SLAVE\_CREATE\_EVENT\_FAILURE, 528  
 ER\_SLAVE\_FATAL\_ERROR, 528  
 ER\_SLAVE\_HAS\_MORE\_GTIDS\_THAN\_MASTER, 68  
 ER\_SLAVE\_HEARTBEAT\_FAILURE, 529  
 ER\_SLAVE\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE, 44  
 ER\_SLAVE\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE\_MAX\_INFORMATION, 51  
 ER\_SLAVE\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE\_MIN\_INFORMATION, 51  
 ER\_SLAVE\_IGNORED\_SSL\_PARAMS, 23  
 ER\_SLAVE\_IGNORED\_TABLE, 20  
 ER\_SLAVE\_IGNORE\_SERVER\_IDS, 46  
 ER\_SLAVE\_INCIDENT, 529  
 ER\_SLAVE\_KILLED\_AFTER\_RECONNECT, 291  
 ER\_SLAVE\_MASTER\_COM\_FAILURE, 529  
 ER\_SLAVE\_MAX\_CHANNELS\_EXCEEDED, 76  
 ER\_SLAVE\_MI\_INIT\_REPOSITORY, 66  
 ER\_SLAVE\_MULTIPLE\_CHANNELS\_CMD, 75  
 ER\_SLAVE\_NEW\_CHANNEL\_WRONG\_REPOSITORY, 75  
 ER\_SLAVE\_NOT\_RUNNING, 17  
 ER\_SLAVE\_NOT\_STARTED\_ON\_SOME\_CHANNELS, 292  
 ER\_SLAVE\_POSSIBLY\_DIVERGED\_AFTER\_DDL, 110  
 ER\_SLAVE\_RECONNECT\_FAILED, 291  
 ER\_SLAVE\_RELAY\_LOG\_PURGE\_FAILED, 283  
 ER\_SLAVE\_RELAY\_LOG\_READ\_FAILURE, 529  
 ER\_SLAVE\_RELAY\_LOG\_TRUNCATE\_INFO, 283  
 ER\_SLAVE\_REPLICATION\_MODE\_CHANGE\_FAILURE, 529  
 ER\_SLAVE\_RLI\_INIT\_REPOSITORY, 66  
 ER\_SLAVE\_SILENT\_RETRY\_TRANSACTION, 61  
 ER\_SLAVE\_SQL\_THREAD\_MUST\_STOP, 70  
 ER\_SLAVE\_SQL\_THREAD\_STOPPED\_AFTER\_GTIDS\_REACHED, 203  
 ER\_SLAVE\_SQL\_THREAD\_STOPPED\_BEFORE\_GTIDS\_ALREADY, 203  
 ER\_SLAVE\_SQL\_THREAD\_STOPPED\_BEFORE\_GTIDS\_REACHED, 203  
 ER\_SLAVE\_SQL\_THREAD\_STOPPED\_GAP\_TRX\_PROCESSED, 203  
 ER\_SLAVE\_SQL\_THREAD\_STOPPED\_UNTIL\_CONDITION\_BAD, 202  
 ER\_SLAVE\_SQL\_THREAD\_STOPPED\_UNTIL\_POSITION\_REACHED, 202  
 ER\_SLAVE\_THREAD, 17  
 ER\_SLAVE\_WORKER\_STOPPED\_PREVIOUS\_THD\_ERROR, 71  
 ER\_SLOW\_LOG\_MODE\_IGNORED\_WHEN\_NOT\_LOGGING\_TO, 118  
 ER\_SOURCE, 16  
 ER\_SOURCE\_DELAY\_VALUE\_OUT\_OF\_RANGE, 53  
 ER\_SOURCE\_FATAL\_ERROR\_READING\_BINLOG, 20

---

ER\_SOURCE\_HAS\_PURGED\_REQUIRED\_GTIDS, 59  
 ER\_SOURCE\_NET\_READ, 16  
 ER\_SOURCE\_NET\_WRITE, 16  
 ER\_SPATIAL\_CANT\_HAVE\_NULL, 21  
 ER\_SPATIAL\_FUNCTIONAL\_INDEX, 114  
 ER\_SPATIAL\_MUST\_HAVE\_GEOM\_COL, 49  
 ER\_SPATIAL\_UNIQUE\_INDEX, 110  
 ER\_SPECIFIC\_ACCESS\_DENIED\_ERROR, 20  
 ER\_SPVAR\_NONINTEGER\_TYPE, 143  
 ER\_SP\_ALREADY\_EXISTS, 25  
 ER\_SP\_BADRETURN, 26  
 ER\_SP\_BADSELECT, 26  
 ER\_SP\_BADSTATEMENT, 26  
 ER\_SP\_BAD\_CURSOR\_QUERY, 26  
 ER\_SP\_BAD\_CURSOR\_SELECT, 26  
 ER\_SP\_BAD\_SQLSTATE, 31  
 ER\_SP\_BAD\_VAR\_SHADOW, 34  
 ER\_SP\_CANT\_ALTER, 27  
 ER\_SP\_CANT\_SET\_AUTOCOMMIT, 34  
 ER\_SP\_CASE\_NOT\_FOUND, 28  
 ER\_SP\_COND\_MISMATCH, 26  
 ER\_SP\_CURSOR\_AFTER\_HANDLER, 27  
 ER\_SP\_CURSOR\_ALREADY\_OPEN, 27  
 ER\_SP\_CURSOR\_MISMATCH, 27  
 ER\_SP\_CURSOR\_NOT\_OPEN, 27  
 ER\_SP\_DOES\_NOT\_EXIST, 25  
 ER\_SP\_DROP\_FAILED, 25  
 ER\_SP\_DUP\_COND, 27  
 ER\_SP\_DUP\_CURS, 27  
 ER\_SP\_DUP\_HANDLER, 32  
 ER\_SP\_DUP\_PARAM, 27  
 ER\_SP\_DUP\_VAR, 27  
 ER\_SP\_FETCH\_NO\_DATA, 27  
 ER\_SP\_LABEL\_MISMATCH, 26  
 ER\_SP\_LABEL\_REDEFINE, 26  
 ER\_SP\_LILABEL\_MISMATCH, 25  
 ER\_SP\_LOAD\_FAILED, 88  
 ER\_SP\_NORETURN, 26  
 ER\_SP\_NORETURNEND, 26  
 ER\_SP\_NOT\_VAR\_ARG, 32  
 ER\_SP\_NO\_AGGREGATE, 35  
 ER\_SP\_NO\_DROP\_SP, 29  
 ER\_SP\_NO\_RECURSION, 32  
 ER\_SP\_NO\_RECURSIVE\_CREATE, 25  
 ER\_SP\_NO\_RESET, 32  
 ER\_SP\_RECURSION\_LIMIT, 35  
 ER\_SP\_STORE\_FAILED, 25  
 ER\_SP\_SUBSELECT\_NYI, 27  
 ER\_SP\_UNDECLARED\_VAR, 27  
 ER\_SP\_UNINIT\_VAR, 26  
 ER\_SP\_VARCOND\_AFTER\_CURSHNDLR, 27  
 ER\_SP\_WRONG\_NAME, 35  
 ER\_SP\_WRONG\_NO\_OF\_ARGS, 26  
 ER\_SP\_WRONG\_NO\_OF\_FETCH\_ARGS, 27  
 ER\_SQLTHREAD\_WITH\_SECURE\_REPLICA, 56  
 ER\_SQLTHREAD\_WITH\_SECURE\_SLAVE, 56  
 ER\_SQL\_AUTHOR\_DEFAULT\_ROLES\_FAIL, 187  
 ER\_SQL\_HA\_READ\_FAILED, 184  
 ER\_SQL\_MODE\_MERGED, 81  
 ER\_SQL\_MODE\_MERGED\_WITH\_STRICT\_MODE, 278  
 ER\_SQL\_REPLICA\_SKIP\_COUNTER\_USED\_WITH\_GTID\_M, 144  
 ER\_SQL\_SLAVE\_SKIP\_COUNTER\_NOT\_SETTABLE\_IN\_GT, 65  
 ER\_SQL\_SLAVE\_SKIP\_COUNTER\_USED\_WITH\_GTID\_MOD, 144  
 ER\_SQL\_USER\_TABLE ALTER WARNING, 187  
 ER\_SQL\_USER\_TABLE\_CREATE WARNING, 187  
 ER\_SRS\_ATTRIBUTE\_STRING\_TOO\_LONG, 109  
 ER\_SRS\_GEOGCS\_INVALID\_AXES, 111  
 ER\_SRS\_ID\_ALREADY\_EXISTS, 108  
 ER\_SRS\_INVALID\_ANGULAR\_UNIT, 111  
 ER\_SRS\_INVALID\_CHARACTER\_IN\_ATTRIBUTE, 109  
 ER\_SRS\_INVALID\_HEIGHT, 157  
 ER\_SRS\_INVALID\_INVERSE\_FLATTENING, 111  
 ER\_SRS\_INVALID\_LATITUDE\_OF\_ORIGIN, 155  
 ER\_SRS\_INVALID\_LATITUDE\_POLAR\_STERE\_VAR\_A, 158  
 ER\_SRS\_INVALID\_LONGITUDE\_OF\_ORIGIN, 155  
 ER\_SRS\_INVALID\_PRIME\_MERIDIAN, 111  
 ER\_SRS\_INVALID\_SCALING, 157  
 ER\_SRS\_INVALID\_SEMI\_MAJOR\_AXIS, 111  
 ER\_SRS\_INVALID\_ZONE\_WIDTH, 157  
 ER\_SRS\_MISSING\_MANDATORY\_ATTRIBUTE, 108  
 ER\_SRS\_MULTIPLE\_ATTRIBUTE\_DEFINITIONS, 108  
 ER\_SRS\_NAME\_CANT\_BE\_EMPTY\_OR\_WHITESPACE, 108  
 ER\_SRS\_NOT\_CARTESIAN, 89  
 ER\_SRS\_NOT\_CARTESIAN\_UNDEFINED, 89  
 ER\_SRS\_NOT\_FOUND, 91  
 ER\_SRS\_NOT\_GEOGRAPHIC, 110  
 ER\_SRS\_ORGANIZATION\_CANT\_BE\_EMPTY\_OR\_WHITES, 108  
 ER\_SRS\_PARSE\_ERROR, 88  
 ER\_SRS\_PROJ\_PARAMETER\_MISSING, 88  
 ER\_SRS\_UNUSED\_PROJ\_PARAMETER\_PRESENT, 155  
 ER\_SR\_BOGUS\_VALUE, 184  
 ER\_SR\_INVALID\_CONTEXT, 184  
 ER\_SSL\_FIPS\_MODE\_ERROR, 321  
 ER\_SSL\_LIBRARY\_ERROR, 169  
 ER\_SSL\_MEMORY\_INSTRUMENTATION\_INIT\_FAILED, 543  
 ER\_SSL\_SERVER\_CERT\_VERIFY\_FAILED, 562

---

---

ER\_SSL\_TRYING\_DATADIR\_DEFAULTS, 181  
ER\_STACKSIZE\_UNEXPECTED, 180  
ER\_STACK\_BACKTRACE, 627  
ER\_STACK\_OVERRUN, 11  
ER\_STACK\_OVERRUN\_NEED\_MORE, 33  
ER\_STARTING\_AS, 174  
ER\_STARTING\_INIT, 535  
ER\_STARTING\_REPLICA\_MONITOR\_IO\_THREAD,  
143  
ER\_STARTUP, 31  
ER\_STATEMENT\_NOT\_ALLOWED\_AFTER\_START\_TRANSACTION,  
139  
ER\_STD\_BAD\_ALLOC\_ERROR, 72  
ER\_STD\_DOMAIN\_ERROR, 72  
ER\_STD\_INVALID\_ARGUMENT, 73  
ER\_STD\_LENGTH\_ERROR, 73  
ER\_STD\_LOGIC\_ERROR, 73  
ER\_STD\_OUT\_OF\_RANGE\_ERROR, 73  
ER\_STD\_OVERFLOW\_ERROR, 73  
ER\_STD\_RANGE\_ERROR, 73  
ER\_STD\_REGEX\_ERROR, 124  
ER\_STD\_RUNTIME\_ERROR, 73  
ER\_STD\_UNDERFLOW\_ERROR, 73  
ER\_STD\_UNKNOWN\_EXCEPTION, 73  
ER\_STMT\_CACHE\_FULL, 51  
ER\_STMT\_HAS\_NO\_OPEN\_CURSOR, 32  
ER\_STMT\_NOT\_ALLOWED\_IN\_SF\_OR\_TRG, 27  
ER\_STOP\_REPLICA\_IO\_THREAD\_DISK\_SPACE,  
321  
ER\_STOP\_REPLICA\_IO\_THREAD\_TIMEOUT, 67  
ER\_STOP\_REPLICA\_MONITOR\_IO\_THREAD\_TIMEOUT,  
143  
ER\_STOP\_REPLICA\_SQL\_THREAD\_TIMEOUT, 66  
ER\_STOP\_SLAVE\_IO\_THREAD\_DISK\_SPACE, 321  
ER\_STOP\_SLAVE\_IO\_THREAD\_TIMEOUT, 66  
ER\_STOP\_SLAVE\_SQL\_THREAD\_TIMEOUT, 66  
ER\_STORAGE\_ENGINE\_NOT\_LOADED, 68  
ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_BINLOG\_FORMAT,  
49  
ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_BINLOG\_FORMAT,  
41  
ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_SQL\_LOG\_BIN,  
50  
ER\_SUBPARTITION\_ERROR, 37  
ER\_SUBPARTITION\_NAME, 45  
ER\_SUBQUERY\_NO\_1\_ROW, 21  
ER\_SUBQUERY\_TRANSFORM\_REJECTED, 138  
ER\_SWITCH\_TMP\_ENGINE, 94  
ER\_SYNTAX\_ERROR, 14  
ER\_SYSTEMD\_NOTIFY\_CONNECT\_FAILED, 387  
ER\_SYSTEMD\_NOTIFY\_DEBUG, 625  
ER\_SYSTEMD\_NOTIFY\_PATH\_TOO\_LONG, 387  
ER\_SYSTEMD\_NOTIFY\_WRITE\_FAILED, 387  
ER\_SYSTEM\_SCHEMA\_NOT\_FOUND, 164  
ER\_SYSTEM\_TABLES\_NOT\_SUPPORTED\_BY\_STORAGE\_ENGINE,  
279  
ER\_SYSTEM\_TABLE\_NOT\_TRANSACTIONAL, 255  
ER\_SYSTEM\_VIEW\_INIT\_FAILED, 281  
ER\_SYSVAR\_CHANGE\_DURING\_QUERY, 131  
ER\_SYS\_VAR\_COMPONENT\_FAILED\_TO\_MAKE\_VARIABLE\_P  
321  
ER\_SYS\_VAR\_COMPONENT\_FAILED\_TO\_PARSE\_VARIABLE\_P  
320  
ER\_SYS\_VAR\_COMPONENT\_OOM, 320  
ER\_SYS\_VAR\_COMPONENT\_UNKNOWN\_VARIABLE\_TYPE,  
320  
ER\_SYS\_VAR\_COMPONENT\_VARIABLE\_SET\_READ\_ONLY,  
320  
ER\_SYS\_VAR\_DEREGISTRATION, 637  
ER\_SYS\_VAR\_NOT\_FOUND, 537  
ER\_SYS\_VAR\_REGISTRATION, 637  
ER\_TABLEACCESS\_DENIED\_ERROR, 13  
ER\_TABLENAME\_NOT\_ALLOWED\_HERE, 21  
ER\_TABLESPACE\_AUTO\_EXTEND\_ERROR, 39  
ER\_TABLESPACE\_CANNOT\_BE\_DECRYPTED, 122  
ER\_TABLESPACE\_CANNOT\_BE\_ENCRYPTED, 122  
ER\_TABLESPACE\_CANNOT\_ENCRYPT, 85  
ER\_TABLESPACE\_DISCARDED, 61  
ER\_TABLESPACE\_DUP\_FILENAME, 97  
ER\_TABLESPACE\_ENGINE\_MISMATCH, 101  
ER\_TABLESPACE\_EXISTS, 61  
ER\_TABLESPACE\_IS\_NOT\_EMPTY, 80  
ER\_TABLESPACE\_MISSING, 61  
ER\_TABLESPACE\_MISSING\_WITH\_NAME, 88  
ER\_TABLESPACE\_TYPE\_UNKNOWN, 122  
ER\_TABLES\_DIFFERENT\_METADATA, 54  
ER\_TABLE\_CANT\_HANDLE\_AUTO\_INCREMENT,  
14  
ER\_TABLE\_CANT\_HANDLE\_BLOB, 14  
ER\_TABLE\_CANT\_HANDLE\_FT, 19  
ER\_TABLE\_CANT\_HANDLE\_SPKEYS, 35  
ER\_TABLE\_CHECK\_INTEGRITY\_FAILED, 182  
ER\_TABLE\_CORRUPT, 67  
ER\_TABLE\_CREATED\_WITH\_DIFFERENT\_VERSION,  
199  
ER\_TABLE\_DEF\_CHANGED, 32  
ER\_TABLE\_EXISTS\_ERROR, 6  
ER\_TABLE\_HAS\_NO\_FT, 57  
ER\_TABLE\_INCOMPATIBLE\_DECIMAL\_FIELD, 198  
ER\_TABLE\_INCOMPATIBLE\_YEAR\_FIELD, 199  
ER\_TABLE\_IN\_FK\_CHECK, 53  
ER\_TABLE\_IN\_SHARED\_TABLESPACE, 158  
ER\_TABLE\_IN\_SYSTEM\_TABLESPACE, 61  
ER\_TABLE\_MUST\_HAVE\_A\_VISIBLE\_COLUMN,  
146  
ER\_TABLE\_MUST\_HAVE\_COLUMNS, 11  
ER\_TABLE\_NAME, 45



---

ER_TABLE_NAME_CAUSES_TOO_LONG_PATH, 131	ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_D, 301
ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED, 575	ER_THREAD_POOL_CONNECTION_REPORT, 639
ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR 575	ER_THREAD_POOL_CON_HANDLER_INIT_FAILED, 301
ER_TABLE_NEEDS_DUMP_UPGRADE, 298	ER_THREAD_POOL_DEDICATED_LISTENERS_INVALID, 615
ER_TABLE_NEEDS_REBUILD, 51	ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT, 301
ER_TABLE_NEEDS_UPGRADE, 35	ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HAN 301
ER_TABLE_NOT_EMPTY, 158	ER_THREAD_POOL_FAILED_TO_CREATE_POOL, 302
ER_TABLE_NOT_LOCKED, 10	ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUT 301
ER_TABLE_NOT_LOCKED_FOR_WRITE, 10	ER_THREAD_POOL_IDLE_CONNECTION_CLOSED, 652
ER_TABLE_NO_PRIMARY_KEY, 158	ER_THREAD_POOL_INIT_FAILED, 301
ER_TABLE_REFERENCED, 86	ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER, 301
ER_TABLE_SCHEMA_MISMATCH, 61	ER_THREAD_POOL_INVALID_STALL_LIMIT, 300
ER_TABLE_UPGRADE_REQUIRED, 279	ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED, 302
ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT, 135	ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID, 301
ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS, 135	ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM, 300
ER_TABLE_WITHOUT_PK, 113	ER_THREAD_POOL_PFS_TABLES_ADD_FAILED, 547
ER_TABLE_WRONG_KEY_DEFINITION, 199	ER_THREAD_POOL_PFS_TABLES_INIT_FAILED, 547
ER_TARGET_TABLESPACE_UNENCRYPTED, 122	ER_THREAD_POOL_PLUGIN_STARTED, 615
ER_TARGET_TS_UNENCRYPTED, 537	ER_THREAD_POOL_QUERY_THREADS_PER_GROUP_INV 625
ER_TC_BAD_MAGIC_IN_TC_LOG, 222	ER_THREAD_POOL_QUERY_THRS_PER_GRP_EXCEEDS 628
ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVER 222	ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS, 302
ER_TC_HEURISTIC_RECOVERY_FAILED, 223	ER_THREAD_POOL_SIZE_TOO_HIGH, 300
ER_TC_HEURISTIC_RECOVERY_MODE, 223	ER_THREAD_POOL_SIZE_TOO_LOW, 300
ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY, 222	ER_THREAD_POOL_SYSVAR_CHANGE, 627
ER_TC_RECOVERING_AFTER_CRASH_USING, 222	ER_THREAD_PRIORITY_IGNORED, 276
ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS, 223	ER_TLS_CONFIGURATION_REUSED, 584
ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVERY, 223	ER_TLS_CONFIGURATION_CONFIGURED_FOR_CHANNEL, 584
ER_TEMPORARY_NAME, 45	ER_TMPDIR_PATH_TOO_LONG, 590
ER_TEMP_FILE_WRITE_FAILURE, 67	ER_TMP_SESSION_FOR_VAR, 625
ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG 112	ER_TOO_BIG_DISPLAYWIDTH, 33
ER_TEMP_TABLE_PREVENTS_SWITCH_OUT_OF_RBR, 41	ER_TOO_BIG_ENUM, 87
ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG 112	ER_TOO_BIG_FIELDLENGTH, 8
ER_TEXTFILE_NOT_READABLE, 9	ER_TOO_BIG_FOR_UNCOMPRESS, 22
ER_TF_FORBIDDEN_JOIN_TYPE, 104	ER_TOO_BIG_PRECISION, 33
ER_TF_MUST_HAVE_ALIAS, 103	ER_TOO_BIG_ROW_SIZE, 11
ER_THE_USER_ABIDES, 177	ER_TOO_BIG_SCALE, 33
ER_THREAD_HANDLING_OOM, 172	ER_TOO_BIG_SELECT, 10
ER_THREAD_POOL_ALGORITHM_INVALID, 300	
ER_THREAD_POOL_BUFFER_TOO_SMALL, 302	
ER_THREAD_POOL_CANNOT_REGISTER_DYNAMIC_PLUGIN, 625	

---

---

ER\_TOO\_BIG\_SET, 10  
 ER\_TOO\_HIGH\_LEVEL\_OF\_NESTING\_FOR\_SELECT, 36  
 ER\_TOO\_LONG\_BODY, 33  
 ER\_TOO\_LONG\_FIELD\_COMMENT, 45  
 ER\_TOO\_LONG\_IDENT, 7  
 ER\_TOO\_LONG\_INDEX\_COMMENT, 50  
 ER\_TOO\_LONG\_KEY, 8  
 ER\_TOO\_LONG\_ROUTINE\_COMMENT, 88  
 ER\_TOO\_LONG\_SET\_ENUM\_VALUE, 88  
 ER\_TOO\_LONG\_STRING, 14  
 ER\_TOO\_LONG\_TABLESPACE\_COMMENT, 97  
 ER\_TOO\_LONG\_TABLE\_COMMENT, 45  
 ER\_TOO\_LONG\_TABLE\_PARTITION\_COMMENT, 59  
 ER\_TOO\_MANY\_CONCURRENT\_CLONES, 100  
 ER\_TOO\_MANY\_CONCURRENT\_TRXS, 45  
 ER\_TOO\_MANY\_FIELDS, 11  
 ER\_TOO\_MANY\_KEYS, 8  
 ER\_TOO\_MANY\_KEY\_PARTS, 8  
 ER\_TOO\_MANY\_PARTITIONS\_ERROR, 37  
 ER\_TOO\_MANY\_PARTITION\_FUNC\_FIELDS\_ERROR, 47  
 ER\_TOO\_MANY\_ROWS, 15  
 ER\_TOO\_MANY\_STORAGE\_ENGINES, 187  
 ER\_TOO\_MANY\_TABLES, 11  
 ER\_TOO\_MANY\_USER\_CONNECTIONS, 18  
 ER\_TOO\_MANY\_VALUES\_ERROR, 47  
 ER\_TOO\_MANY\_WINDOWS, 153  
 ER\_TP\_QUERY\_THRS\_PER\_GRP\_EXCEEDS\_TXN\_THR\_LIMIT, 157  
 ER\_TRACK\_VARIABLES\_BOGUS, 177  
 ER\_TRANSACTION\_ROLLBACK\_DURING\_COMMIT, 78  
 ER\_TRANSFORM\_SOURCE\_SRS\_MISSING\_TOWGS84, 112  
 ER\_TRANSFORM\_SOURCE\_SRS\_NOT\_SUPPORTED, 112  
 ER\_TRANSFORM\_TARGET\_SRS\_MISSING\_TOWGS84, 112  
 ER\_TRANSFORM\_TARGET\_SRS\_NOT\_SUPPORTED, 112  
 ER\_TRANSPORTS\_WHAT\_TRANSPORTS, 175  
 ER\_TRANS\_CACHE\_FULL, 17  
 ER\_TREE\_CORRUPT\_2\_CONSECUTIVE\_REDS, 253  
 ER\_TREE\_CORRUPT\_INCORRECT\_BLACK\_COUNT, 253  
 ER\_TREE\_CORRUPT\_PARENT\_SHOULD\_POINT\_AT\_PARENT, 252  
 ER\_TREE\_CORRUPT\_RIGHT\_IS\_LEFT, 253  
 ER\_TREE\_CORRUPT\_ROOT\_SHOULD\_BE\_BLACK, 253  
 ER\_TRG\_ALREADY\_EXISTS, 29  
 ER\_TRG\_CANT\_CHANGE\_ROW, 29  
 ER\_TRG\_CANT\_OPEN\_TABLE, 43  
 ER\_TRG\_CANT\_PARSE, 183  
 ER\_TRG\_CORRUPTED\_FILE, 43  
 ER\_TRG\_CREATION\_CTX\_NOT\_SET, 278  
 ER\_TRG\_DOES\_NOT\_EXIST, 29  
 ER\_TRG\_INVALID\_CREATION\_CTX, 43  
 ER\_TRG\_IN\_WRONG\_SCHEMA, 33  
 ER\_TRG\_NO\_CLIENT\_CHARSET, 169  
 ER\_TRG\_NO\_CREATION\_CTX, 43  
 ER\_TRG\_NO\_DEFINER, 35  
 ER\_TRG\_NO\_SUCH\_ROW\_IN\_TRG, 29  
 ER\_TRG\_ON\_VIEW\_OR\_TEMP\_TABLE, 29  
 ER\_TRG\_WITHOUT\_DEFINER, 169  
 ER\_TRG\_WRONG\_ORDER, 553  
 ER\_THEAD\_POOL\_LOW\_LEVEL\_INIT\_FAILED, 302  
 ER\_TRIGGER\_INVALID\_VALUE, 162  
 ER\_TRUNCATED\_WRONG\_VALUE, 24  
 ER\_TRUNCATED\_WRONG\_VALUE\_FOR\_FIELD, 29  
 ER\_TRUNCATE\_ILLEGAL\_FK, 50  
 ER\_TRX\_GTID\_COLLECT\_REJECT, 186  
 ER\_TRX\_WRITE\_SET\_OOM, 187  
 ER\_TURNING\_LOGGING\_OFF\_FOR\_THE\_DURATION, 271  
 ER\_TURNING\_ON\_PARTIAL\_REVOKES, 557  
 ER\_TX\_EXTRACTION\_ALGORITHM\_FOR\_BINLOG\_TX\_DEPENDENT, 282  
 ER\_TZ\_CANT\_BUILD\_MKTIME\_MAP, 202  
 ER\_TZ\_CANT\_FIND\_DESCRIPTION\_FOR\_TIME\_ZONE, 201  
 ER\_TZ\_CANT\_FIND\_DESCRIPTION\_FOR\_TIME\_ZONE\_ID, 201  
 ER\_TZ\_CANT\_OPEN\_AND\_LOCK\_TIME\_ZONE\_TABLE, 200  
 ER\_TZ\_ERROR\_LOADING\_LEAP\_SECOND\_TABLE, 200  
 ER\_TZ\_NO\_TRANSITION\_TYPES\_IN\_TIME\_ZONE, 202  
 ER\_TZ\_OOM\_INITIALIZING\_TIME\_ZONES, 200  
 ER\_TZ\_OOM\_LOADING\_LEAP\_SECOND\_TABLE, 200  
 ER\_TZ\_OOM\_LOADING\_TIME\_ZONE\_DESCRIPTION, 202  
 ER\_TZ\_OOM\_WHILE\_LOADING\_TIME\_ZONE, 202  
 ER\_TZ\_OOM\_WHILE\_SETTING\_TIME\_ZONE, 202  
 ER\_TZ\_TOO\_MANY\_LEAPS\_IN\_LEAP\_SECOND\_TABLE, 200  
 ER\_TZ\_TRANSITION\_TABLE\_BAD\_TRANSITION\_TYPE, 201  
 ER\_TZ\_TRANSITION\_TABLE\_LOAD\_ERROR, 201  
 ER\_TZ\_TRANSITION\_TABLE\_TOO\_MANY\_TRANSITIONS, 201

---

ER\_TZ\_TRANSITION\_TYPE\_TABLE\_ABBREVIATIONS\_EXCEEDS\_SPACE, 185  
201  
ER\_TZ\_TRANSITION\_TYPE\_TABLE\_LOAD\_ERROR, 201  
ER\_TZ\_TRANSITION\_TYPE\_TABLE\_TYPE\_TOO\_LARGE, 201  
ER\_TZ\_UNKNOWN\_OR\_ILLEGAL\_DEFAULT\_TIME\_ZONE, 200  
ER\_UDF\_ALREADY\_EXISTS, 536  
ER\_UDF\_CANT\_ALLOC\_FOR\_FUNCTION, 185  
ER\_UDF\_CANT\_ALLOC\_FOR\_STRUCTURES, 185  
ER\_UDF\_CANT\_OPEN\_FUNCTION\_TABLE, 185  
ER\_UDF\_DEREGISTRATION, 637  
ER\_UDF\_DROP\_DYNAMICALLY\_REGISTERED, 99  
ER\_UDF\_ERROR, 86  
ER\_UDF\_EXEC\_FAILURE, 637  
ER\_UDF\_EXEC\_FAILURE\_REASON, 637  
ER\_UDF\_EXISTS, 12  
ER\_UDF\_INVALID\_ROW\_IN\_FUNCTION\_TABLE, 185  
ER\_UDF\_NO\_PATHS, 12  
ER\_UDF\_REGISTER\_ERROR, 590  
ER\_UDF\_REGISTER\_SERVICE\_ERROR, 590  
ER\_UDF\_REGISTRATION, 637  
ER\_UDF\_UNREGISTER\_ERROR, 590  
ER\_UNKNOWN\_AUTH\_ID\_OR\_ACCESS\_DENIED\_FOR\_GRANT\_AS, 123  
ER\_UNABLE\_TO\_BUILD\_HISTOGRAM, 99  
ER\_UNABLE\_TO\_COLLECT\_LOG\_STATUS, 109  
ER\_UNABLE\_TO\_DROP\_COLUMN\_STATISTICS, 99  
ER\_UNABLE\_TO\_RESOLVE\_HOSTNAME, 168  
ER\_UNABLE\_TO\_RESOLVE\_IP, 168  
ER\_UNABLE\_TO\_SET\_OPTION, 110  
ER\_UNABLE\_TO\_STORE\_COLUMN\_STATISTICS, 99  
ER\_UNABLE\_TO\_STORE\_STATISTICS, 91  
ER\_UNABLE\_TO\_UPDATE\_COLUMN\_STATISTICS, 99  
ER\_UNDISCLOSED\_PARSE\_ERROR\_IN\_DIGEST\_FN, 105  
ER\_UNDO\_RECORD\_TOO\_BIG, 52  
ER\_UNEXPECTED\_GEOMETRY\_TYPE, 88  
ER\_UNIQUE\_KEY\_NEED\_ALL\_FIELDS\_IN\_PF, 38  
ER\_UNIT\_NOT\_FOUND, 130  
ER\_UNKNOWN\_ALTER\_ALGORITHM, 60  
ER\_UNKNOWN\_ALTER\_LOCK, 60  
ER\_UNKNOWN\_AUTHID, 89  
ER\_UNKNOWN\_AUTH\_ID\_IN\_MANDATORY\_ROLE, 284  
ER\_UNKNOWN\_CHARACTER\_SET, 11  
ER\_UNKNOWN\_COLLATION, 23  
ER\_UNKNOWN\_COM\_ERROR, 6  
ER\_UNKNOWN\_ERROR, 10  
ER\_UNKNOWN\_ERROR\_DETECTED\_IN\_SE, 290  
ER\_UNKNOWN\_EXPLAIN\_FORMAT, 59  
ER\_UNKNOWN\_KEY\_CACHE, 24  
ER\_UNKNOWN\_LOCALE, 46  
ER\_UNKNOWN\_NETWORK\_NAMESPACE, 561  
ER\_UNKNOWN\_PARTITION, 54  
ER\_UNKNOWN\_PROCEDURE, 10  
ER\_UNKNOWN\_STMT\_HANDLER, 21  
ER\_UNKNOWN\_STORAGE\_ENGINE, 24  
ER\_UNKNOWN\_SYSTEM\_VARIABLE, 16  
ER\_UNKNOWN\_TABLE, 11  
ER\_UNKNOWN\_TABLESPACE\_TYPE, 543  
ER\_UNKNOWN\_TABLE\_IN\_UPGRADE, 568  
ER\_UNKNOWN\_TARGET\_BINLOG, 30  
ER\_UNKNOWN\_TIME\_ZONE, 25  
ER\_UNKNOWN\_UNSUPPORTED\_STORAGE\_ENGINE, 170  
ER\_UNKNOWN\_VARIABLE\_IN\_PERSISTED\_CONFIG\_FILE, 537  
ER\_UNRESOLVED\_HINT\_NAME, 80  
ER\_UNRESOLVED\_TABLE\_LOCK, 93  
ER\_UNSUPPORTED\_LOG\_ENGINE, 42  
ER\_UNSUPPORTED\_ACTION\_ON\_DEFAULT\_VAL\_GENERATION, 115  
ER\_UNSUPPORTED\_ACTION\_ON\_GENERATED\_COLUMN, 115  
ER\_UNSUPPORTED\_ALTER\_ENCRYPTION\_INPLACE, 85  
ER\_UNSUPPORTED\_ALTER\_INPLACE\_ON\_VIRTUAL\_COLUMNS, 79  
ER\_UNSUPPORTED\_ALTER\_ONLINE\_ON\_VIRTUAL\_COLUMNS, 85  
ER\_UNSUPPORTED\_DATE, 174  
ER\_UNSUPPORTED\_ENGINE, 53  
ER\_UNSUPPORTED\_EXTENSION, 11  
ER\_UNSUPPORTED\_INDEX\_ALGORITHM, 87  
ER\_UNSUPPORTED\_PS, 25  
ER\_UNSUPPORTED\_SQL\_MODE, 130  
ER\_UNSUPPORTED\_USE\_OF\_GRANT\_AS, 123  
ER\_UNSUPPORTED\_COMPRESSED\_TEMPORARY\_TABLE, 87  
ER\_UNTIL\_COND\_IGNORED, 24  
ER\_UPDATE\_GTID\_PURGED\_WITH\_GR, 131  
ER\_UPDATE\_INFO, 12  
ER\_UPDATE\_LOG\_DEPRECATED\_IGNORED, 26  
ER\_UPDATE\_LOG\_DEPRECATED\_TRANSLATED, 26  
ER\_UPDATE\_TABLE\_USED, 9  
ER\_UPDATE\_WITHOUT\_KEY\_IN\_SAFE\_MODE, 15  
ER\_UPDATING\_DD\_TABLE, 88  
ER\_UPGRADE\_NONEXISTENT\_SCHEMA, 591  
ER\_UPGRADE\_PARSE\_ERROR, 542  
ER\_UPGRADE\_WITH\_PARTITIONED\_TABLES\_REJECTED, 569

---

---

ER_USAGE_DEPRECATION_COUNTER, 641	ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION,
ER_USERNAME, 35	389
ER_USERNAME_TRUNCATED, 584	ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED,
ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK,	
136	ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED,
ER_USER_ALREADY_EXISTS, 83	389
ER_USER_COLUMN_OLD_LENGTH, 85	ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED,
ER_USER_DOES_NOT_EXIST, 83	389
ER_USER_LIMIT_REACHED, 19	ER_VALUES_IS_NOT_INT_TYPE_ERROR, 50
ER_USER_LOCK_DEADLOCK, 74	ER_VALUE_OUT_OF_RANGE, 152
ER_USER_LOCK_OVERLONG_NAME, 162	ER_VARIABLE_IS_NOT_STRUCT, 23
ER_USER_LOCK_WRONG_NAME, 73	ER_VARIABLE_IS_READONLY, 44
ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCOMPATIBLE, NOT_PERSISTED, 91	
197	ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER,
ER_USER_REFERENCED_AS_DEFINER, 142	57
ER_USER_REGISTRATION_FAILED, 150	ER_VARIABLE_NOT_SETTABLE_IN_SP, 63
ER_USER_REQUIRES_ROOT, 175	ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION,
ER_USER_WHAT_USER, 175	57
ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_CANNOT_BE_READ_ONLY,	
144	ER_VARS_CAN_ONLY_BE_READ_ONLY,
ER_UUID_INVALID, 170	ER_VAR_DOES_NOT_EXIST, 98
ER_UUID_IS, 170	ER_VERBOSE_HINT, 178
ER_UUID_SALT, 170	ER_VERBOSE_REQUIRES_HELP, 171
ER_UUID_SCRUB, 170	ER_VIEW_CHECKSUM, 30
ER_VALGRIND_COUNT_LEAKS, 185	ER_VIEW_CHECK_FAILED, 29
ER_VALGRIND_DO_QUICK_LEAK_CHECK, 185	ER_VIEW_CREATION_CTX_NOT_SET, 279
ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGED_CHARACTERS,	
162	ER_VIEW_DELETE_MERGE_VIEW, 31
ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED,	ER_VIEW_INVALID_NO_USER, 34
389	ER_VIEW_INVALID, 29
ER_VALIDATE_PWD_COULD_BE_NULL, 388	ER_VIEW_INVALID_CREATION_CTX, 43
ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED,	ER_VIEW_MULTIUPDATE, 30
317	ER_VIEW_NONUPD_CHECK, 29
ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED,	ER_VIEW_NO_CREATION_CTX, 43
317	ER_VIEW_NO_EXPLAIN, 28
ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED,	ER_VIEW_NO_INSERT_FIELD_LIST, 31
388	ER_VIEW_OTHER_USER, 34
ER_VALIDATE_PWD_DICT_FILE_TOO_BIG, 317	ER_VIEW_PREVENT_UPDATE, 34
ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_VIEWS,	ER_VIEW_RECURSIVE, 35
317	ER_VIEW_SELECT_CLAUSE, 28
ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX,	ER_VIEW_SELECT_TMPTABLE, 28
318	ER_VIEW_SELECT_VARIABLE, 28
ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE,	ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION,
317	164
ER_VALIDATE_PWD_LENGTH_CHANGED, 318	ER_VIEW_UNPARSABLE, 199
ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED,	ER_VIEW_WRONG_LIST, 28
388	ER_VTOKEN_PLUGIN_TOKEN_MISMATCH, 81
ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED,	ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND, 81
388	ER_WAITING_FOR_NO_CONNECTIONS, 641
ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED,	ER_WAITING_FOR_NO_THDS, 641
388	ER_WAITPID_FAILED, 296
ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED,	ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES,
388	550
	ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID,
	549
	ER_WARNING_NOT_COMPLETE_ROLLBACK, 17

ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATE_TEMPORARY_TABLE, 55	ER_WARN_DEPRECATED_CHARSET_OPTION, 612
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROP_TEMPORARY_TABLE, 55	ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION, 158
ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID, 101	ER_WARN_DEPRECATED_COLLATION, 152
ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSES_VOID, 549	ER_WARN_DEPRECATED_COLLATION_OPTION, 610
ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS, 147	ER_WARN_DEPRECATED_DATETIME_DELIMITER, 610
ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS_LOG, 603	ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT, 125
ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATION_SIZE, 147	ER_WARN_DEPRECATED_FLOAT_DIGITS, 125
ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATION_SIZE_LOG, 603	ER_WARN_DEPRECATED_FLOAT_UNSIGNED, 125
ER_WARN_ALLOWED_PACKET_OVERFLOWED, 25	ER_WARN_DEPRECATED_FOUND_ROWS, 137
ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAME_SPACE, 146	ER_WARN_DEPRECATED_IDENT, 157
ER_WARN_AUDIT_LOG_DISABLED, 612	ER_WARN_DEPRECATED_INNER_INTO, 137
ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_JSON_LOG, 148	ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH, 125
ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_JSON_LOG, 605	ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_AND_MANDATORY_ROLES, 116
ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES, 572	ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX, 24
ER_WARN_BAD_MAX_EXECUTION_TIME, 80	ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER, 641
ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED, 101	ER_WARN_DEPRECATED_SQLMODE, 77
ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_UPDATES, 101	ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS, 137
ER_WARN_BINLOG_V1_ROW_EVENTS_DISABLED, 101	ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER, 137
ER_WARN_CANNOT_FREE_COMPONENT_DATA_DEALLOCATION_FAILED, 635	ER_WARN_DEPRECATED_SYNTAX, 24
ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES, 613	ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT, 49
ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES, 154	ER_WARN_DEPRECATED_SYNTAX_WITH_VER, 40
ER_WARN_CANT_DROP_DEFAULT_KEYCACHE, 33	ER_WARN_DEPRECATED_SYSVAR_UPDATE, 77
ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX_KEY, 138	ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL_KEY, 617
ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_MULTIPLE_KEYRING, 634	ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL_KEY, 617
ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_NOT_RO, 596	ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS, 612
ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEYS, 627	ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS, 612
ER_WARN_CONFLICTING_HINT, 80	ER_WARN_DEPRECATED_USER_SET_EXPR, 116
ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AU, 151	ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION, 570
ER_WARN_DATA_OUT_OF_RANGE, 22	ER_WARN_DEPRECATED_UTF8MB3_COLLATION, 116

---

ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION, 543	ER_WARN_PROPERTY_STRING_PARSE_FAILED, 552
ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION, 543	ER_WARN_PURGE_LOG_IN_USE, 65
ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS, 137	ER_WARN_PURGE_LOG_IS_ACTIVE, 65
ER_WARN_DEPRECATED_WITH_NOTE, 162	ER_WARN_QC_RESIZE, 24
ER_WARN_DEPRECATED_YEAR_UNSIGNED, 136	ER_WARN_REGEX_USING_DEFAULT, 152
ER_WARN_DEPRECATED_ZEROFILL, 126	ER_WARN_REMOVED_SQL_MODE, 544
ER_WARN_ENGINE_TRANSACTION_ROLLBACK, 44	ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS 602
ER_WARN_FIELD_RESOLVED, 23	ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_NOT_ON 609
ER_WARN_FUNC_INDEX_NOT_APPLICABLE, 131	ER_WARN_RESERVED_SRID_RANGE, 109
ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET, 603	ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MA 572
ER_WARN_GTID_THRESHOLD_BREACH, 594	ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SO 572
ER_WARN_HOSTNAME_WONT_WORK, 24	ER_WARN_SCHEDULED_TASK_RUN_FAILED, 639
ER_WARN_HYPERGRAPH_EXPERIMENTAL, 142	ER_WARN_SF_UDF_NAME_COLLISION, 153
ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS, 557	ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED FROM, 148
ER_WARN_INDEX_NOT_APPLICABLE, 54	ER_WARN_SRS_ID_ALREADY_EXISTS, 108
ER_WARN_INVALID_DB_RESTRICTIONS, 557	ER_WARN_SRS_NOT_FOUND, 89
ER_WARN_INVALID_HINT, 98	ER_WARN_SRS_NOT_FOUND_AXIS_ORDER, 92
ER_WARN_INVALID_TIMESTAMP, 25	ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR, 583
ER_WARN_I_S_SKIPPED_TABLE, 49	ER_WARN_TOO_FEW_RECORDS, 22
ER_WARN_LEGACY_SYNTAX_CONVERTED, 69	ER_WARN_TOO_MANY_RECORDS, 22
ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX_KEY, 582	ER_WARN_TRG_ALREADY_EXISTS, 154
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPTED, 570	ER_WARN_TRIGGER_DOESNT_HAVE_CREATED, 69
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST, 570	ER_WARN_UNKNOWN_KEYRING_AWS_REGION, 570
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_PERMISSION, 571	ER_WARN_UNKNOWN_QB_NAME, 80
ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE_AURORA_POS, 609	ER_WARN_UNLOAD_THE_NOT_PERSISTED, 90
ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING, 613	ER_WARN_UNSUPPORTED_HINT, 88
ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND, 596	ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME, 80
ER_WARN_NO_SERVERID_SPECIFIED, 278	ER_WARN_USING_OTHER_HANDLER, 22
ER_WARN_NO_SPACE_VERSION_COMMENT, 162	ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED, 141
ER_WARN_NULL_TO_NOTNULL, 22	ER_WARN_VIEW_MERGE, 28
ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS, 70	ER_WARN_VIEW_WITHOUT_KEY, 29
ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS, 70	ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG, 570
ER_WARN_ON_MODIFYING_GTID_EXECUTED_TABLE, 81	ER_WARN_WRONG_COMPRESSION_LEVEL_LOG, 570
ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO, 70	ER_WASTEFUL_NET_BUFFER_SIZE, 171
ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR, 80	ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BIND, 562
ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT, 557	ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH, 94
	ER_WINDOW_DUPLICATE_NAME, 95
	ER_WINDOW_EXPLAIN_JSON, 96
	ER_WINDOW_FRAME_END_ILLEGAL, 94

---

ER\_WINDOW\_FRAME\_ILLEGAL, 95  
 ER\_WINDOW\_FRAME\_START\_ILLEGAL, 94  
 ER\_WINDOW\_FUNCTION\_IGNORES\_FRAME, 96  
 ER\_WINDOW\_ILLEGAL\_ORDER\_BY, 95  
 ER\_WINDOW\_INVALID\_WINDOW\_FUNC\_ALIAS\_USE, 95  
 ER\_WINDOW\_INVALID\_WINDOW\_FUNC\_USE, 95  
 ER\_WINDOW\_NESTED\_WINDOW\_FUNC\_USE\_IN\_WINDOW\_SPEC, 96  
 ER\_WINDOW\_NO\_CHILD\_PARTITIONING, 94  
 ER\_WINDOW\_NO\_GROUP\_ORDER, 96  
 ER\_WINDOW\_NO\_GROUP\_ORDER\_UNUSED, 96  
 ER\_WINDOW\_NO\_INHERIT\_FRAME, 94  
 ER\_WINDOW\_NO\_REDEFINE\_ORDER\_BY, 94  
 ER\_WINDOW\_NO\_SUCH\_WINDOW, 94  
 ER\_WINDOW\_RANGE\_BOUND\_NOT\_CONSTANT, 95  
 ER\_WINDOW\_RANGE\_FRAME\_NUMERIC\_TYPE, 95  
 ER\_WINDOW\_RANGE\_FRAME\_ORDER\_TYPE, 95  
 ER\_WINDOW\_RANGE\_FRAME\_TEMPORAL\_TYPE, 95  
 ER\_WINDOW\_ROWS\_INTERVAL\_USE, 96  
 ER\_WINDOW\_SE\_NOT\_ACCEPTABLE, 96  
 ER\_WIN\_LISTEN\_BUT\_HOW, 176  
 ER\_WIN\_LOAD\_LIBRARY\_FAILED, 295  
 ER\_WL9236\_NOW\_UNUSED, 96  
 ER\_WRITABLE\_CONFIG\_REMOVED, 173  
 ER\_WRITE\_ROW\_TO\_PARTITION\_FAILED, 284  
 ER\_WRITE\_SET\_EXCEEDS\_LIMIT, 87  
 ER\_WRONG\_ARGUMENTS, 18  
 ER\_WRONG\_AUTO\_KEY, 8  
 ER\_WRONG\_COLUMN\_NAME, 14  
 ER\_WRONG\_COMPRESSION\_ALGORITHM\_CLIENT, 132  
 ER\_WRONG\_COMPRESSION\_LEVEL\_CLIENT, 132  
 ER\_WRONG\_COUNT\_FOR\_KEY, 253  
 ER\_WRONG\_COUNT\_FOR\_ORIGIN, 253  
 ER\_WRONG\_COUNT\_OF\_ELEMENTS, 253  
 ER\_WRONG\_DATETIME\_SPEC, 174  
 ER\_WRONG\_DB\_NAME, 10  
 ER\_WRONG\_EXPR\_IN\_PARTITION\_FUNC\_ERROR, 36  
 ER\_WRONG\_FIELD\_SPEC, 7  
 ER\_WRONG\_FIELD\_TERMINATORS, 9  
 ER\_WRONG\_FIELD\_WITH\_GROUP, 7  
 ER\_WRONG\_FIELD\_WITH\_GROUP\_V2, 77  
 ER\_WRONG\_FILE\_NAME, 80  
 ER\_WRONG\_FK\_DEF, 21  
 ER\_WRONG\_FK\_OPTION\_FOR\_GENERATED\_COLUMN, 79  
 ER\_WRONG\_GROUP\_FIELD, 7  
 ER\_WRONG\_JSON\_TABLE\_VALUE, 103  
 ER\_WRONG\_KEY\_COLUMN, 15  
 ER\_WRONG\_KEY\_COLUMN\_FUNCTIONAL\_INDEX, 114  
 ER\_WRONG\_LOCK\_OF\_SYSTEM\_TABLE, 33  
 ER\_WRONG\_MRG\_TABLE, 15  
 ER\_WRONG\_MVI\_VALUE, 130  
 ER\_WRONG\_NAME\_FOR\_CATALOG, 24  
 ER\_WRONG\_NAME\_FOR\_INDEX, 24  
 ER\_WRONG\_NATIVE\_TABLE\_STRUCTURE, 49  
 ER\_WRONG\_NUMBER\_OF\_COLUMNS\_IN\_SELECT, 19  
 ER\_WRONG\_OBJECT, 28  
 ER\_WRONG\_OUTER\_JOIN, 11  
 ER\_WRONG\_OUTER\_JOIN\_UNUSED, 11  
 ER\_WRONG\_PARAMCOUNT\_TO\_NATIVE\_FCT, 42  
 ER\_WRONG\_PARAMCOUNT\_TO\_PROCEDURE, 10  
 ER\_WRONG\_PARAMETERS\_TO\_NATIVE\_FCT, 42  
 ER\_WRONG\_PARAMETERS\_TO\_PROCEDURE, 10  
 ER\_WRONG\_PARAMETERS\_TO\_STORED\_FCT, 42  
 ER\_WRONG\_PARTITION\_NAME, 41  
 ER\_WRONG\_PERFSCHEMA\_USAGE, 49  
 ER\_WRONG\_SIZE\_NUMBER, 39  
 ER\_WRONG\_SPVAR\_TYPE\_IN\_LIMIT, 50  
 ER\_WRONG\_SRID\_FOR\_COLUMN, 101  
 ER\_WRONG\_STRING\_LENGTH, 36  
 ER\_WRONG\_SUB\_KEY, 9  
 ER\_WRONG\_SUM\_SELECT, 7  
 ER\_WRONG\_TABLESPACE\_NAME, 80  
 ER\_WRONG\_TABLE\_NAME, 10  
 ER\_WRONG\_TYPE\_COLUMN\_VALUE\_ERROR, 47  
 ER\_WRONG\_TYPE\_FOR\_COLUMN\_PREFIX\_IDX\_FLD, 294  
 ER\_WRONG\_TYPE\_FOR\_VAR, 20  
 ER\_WRONG\_USAGE, 19  
 ER\_WRONG\_VALUE, 39  
 ER\_WRONG\_VALUE\_COUNT, 7  
 ER\_WRONG\_VALUE\_COUNT\_ON\_ROW, 13  
 ER\_WRONG\_VALUE\_FOR\_TYPE, 32  
 ER\_WRONG\_VALUE\_FOR\_VAR, 20  
 ER\_WRONG\_VALUE\_FOR\_VAR\_PLUS\_ACTIONABLE\_PART, 139  
 ER\_X509\_CANT\_CHMOD\_KEY, 193  
 ER\_X509\_CANT\_CREATE\_CERT, 193  
 ER\_X509\_CANT\_READ\_CA\_CERT, 193  
 ER\_X509\_CANT\_READ\_CA\_KEY, 193  
 ER\_X509\_CANT\_WRITE\_CERT, 193  
 ER\_X509\_CANT\_WRITE\_KEY, 193  
 ER\_X509\_CIPHERS\_MISMATCH, 192  
 ER\_X509\_ISSUER\_MISMATCH, 192  
 ER\_X509\_NEEDS\_RSA\_PRIVKEY, 193  
 ER\_X509\_SUBJECT\_MISMATCH, 193  
 ER\_XAER\_DUPID, 34  
 ER\_XAER\_INVAL, 31  
 ER\_XAER\_NOTA, 31  
 ER\_XAER\_OUTSIDE, 31

---

---

ER\_XAER\_RMERR, 31  
ER\_XAER\_RMFAIL, 31  
ER\_XA\_CANT\_CREATE\_MDL\_BACKUP, 568  
ER\_XA\_COMMITTING\_XID, 186  
ER\_XA\_IGNOREING\_XID, 186  
ER\_XA\_NO\_MULTI\_2PC\_HEURISTIC\_RECOVER,  
186  
ER\_XA\_RBDEADLOCK, 44  
ER\_XA\_RBROLLBACK, 31  
ER\_XA\_RBTIMEOUT, 44  
ER\_XA\_RECOVERY\_DONE, 186  
ER\_XA\_RECOVER\_EXPLANATION, 186  
ER\_XA\_RECOVER\_FOUND\_TRX\_IN\_SE, 186  
ER\_XA\_RECOVER\_FOUND\_XA\_TRX, 186  
ER\_XA\_REPLICATION\_FILTERS, 129  
ER\_XA\_RETRY, 86  
ER\_XA\_ROLLING\_BACK\_XID, 186  
ER\_XA\_STARTING\_RECOVERY, 186  
ER\_XA\_TEMP\_TABLE, 153  
ER\_XPLUGIN\_ALL\_IO\_INTERFACES\_DISABLED,  
326  
ER\_XPLUGIN\_BUFFER\_PAGE\_ALLOC\_FAILED,  
323  
ER\_XPLUGIN\_CAPABILITY\_CLIENT\_INTERACTIVE\_FAIL  
330  
ER\_XPLUGIN\_CAPABILITY\_EXPIRED\_PASSWORD,  
330  
ER\_XPLUGIN\_CLIENT\_KILL\_MSG, 328  
ER\_XPLUGIN\_CLIENT\_RELEASE\_TRIGGERED,  
328  
ER\_XPLUGIN\_CLIENT\_SSL\_HANDSHAKE\_FAILED,  
325  
ER\_XPLUGIN\_CLOSING\_CLIENTS\_ON\_SHUTDOWN,  
326  
ER\_XPLUGIN\_COMPRESSION\_ERROR, 570  
ER\_XPLUGIN\_DETECTED\_HANGING\_CLIENTS,  
323  
ER\_XPLUGIN\_EMPTY\_ADMIN\_CMD, 329  
ER\_XPLUGIN\_ERROR\_MSG, 319  
ER\_XPLUGIN\_ERROR\_READING\_SOCKET, 326  
ER\_XPLUGIN\_ERROR\_WRITING\_TO\_CLIENT, 327  
ER\_XPLUGIN\_EXCEPTION\_IN\_EVENT\_LOOP, 324  
ER\_XPLUGIN\_EXCEPTION\_IN\_TASK\_SCHEDULER,  
324  
ER\_XPLUGIN\_EXISTING\_USER\_ACCOUNT\_WITH\_INCOM  
328  
ER\_XPLUGIN\_FAILED\_AT\_SSL\_CONF, 325  
ER\_XPLUGIN\_FAILED\_TO\_ACCEPT\_CLIENT, 323  
ER\_XPLUGIN\_FAILED\_TO\_BIND\_INTERFACE\_ADDRESSES  
583  
ER\_XPLUGIN\_FAILED\_TO\_CLOSE\_SQL\_SESSION,  
329  
ER\_XPLUGIN\_FAILED\_TO\_CREATE\_SESSION\_FOR\_CON  
325  
ER\_XPLUGIN\_FAILED\_TO\_EXECUTE\_ADMIN\_CMD,  
329  
ER\_XPLUGIN\_FAILED\_TO\_GET\_CREATION\_STMT,  
329  
ER\_XPLUGIN\_FAILED\_TO\_GET\_ENGINE\_INFO,  
329  
ER\_XPLUGIN\_FAILED\_TO\_GET\_SECURITY\_CTX,  
328  
ER\_XPLUGIN\_FAILED\_TO\_GET\_SYS\_VAR, 329  
ER\_XPLUGIN\_FAILED\_TO\_INITIALIZE\_SESSION,  
325  
ER\_XPLUGIN\_FAILED\_TO\_INTERRUPT\_SESSION,  
328  
ER\_XPLUGIN\_FAILED\_TO\_OPEN\_INTERNAL\_SESSION,  
330  
ER\_XPLUGIN\_FAILED\_TO\_PREPARE\_IO\_INTERFACES,  
324  
ER\_XPLUGIN\_FAILED\_TO\_RESET\_IPV6\_V6ONLY\_FLAG,  
330  
ER\_XPLUGIN\_FAILED\_TO\_SCHEDULE\_CLIENT,  
323  
ER\_XPLUGIN\_FAILED\_TO\_SET\_MIN\_NUMBER\_OF\_WORKERS  
325  
ER\_XPLUGIN\_FAILED\_TO\_SET\_SO\_REUSEADDR\_FLAG,  
330  
ER\_XPLUGIN\_FAILED\_TO\_STOP\_SERVICES, 528  
ER\_XPLUGIN\_FAILED\_TO\_SWITCH\_CONTEXT,  
330  
ER\_XPLUGIN\_FAILED\_TO\_SWITCH\_SECURITY\_CTX,  
542  
ER\_XPLUGIN\_FAILED\_TO\_SWITCH\_SECURITY\_CTX\_TO\_ROO  
329  
ER\_XPLUGIN\_FAILED\_TO\_UNREGISTER\_UDF, 330  
ER\_XPLUGIN\_FAILED\_TO\_USE\_SSL\_CONF, 319  
ER\_XPLUGIN\_FAILED\_TO\_VALIDATE\_ADDRESS,  
583  
ER\_XPLUGIN\_FAIL\_TO\_GET\_RESULT\_DATA, 329  
ER\_XPLUGIN\_FORCE\_STOP\_CLIENT, 323  
ER\_XPLUGIN\_GET\_PEER\_ADDRESS\_FAILED, 330  
ER\_XPLUGIN\_INVALID\_AUTH\_METHOD, 326  
ER\_XPLUGIN\_INVALID\_MSG\_DURING\_CLIENT\_INIT,  
326  
ER\_XPLUGIN\_IPv6\_AVAILABLE, 328  
ER\_XPLUGIN\_LISTENER\_SETUP\_FAILED, 324  
ER\_XPLUGIN\_LISTENER\_STATUS\_MSG, 327  
ER\_XPLUGIN\_LISTENER\_SYS\_VARIABLE\_ERROR,  
327  
ER\_XPLUGIN\_MAX\_AUTH\_ATTEMPTS\_REACHED,  
323  
ER\_XPLUGIN\_MESSAGE\_TOO\_LONG, 325  
ER\_XPLUGIN\_PEER\_DISCONNECTED\_WHILE\_READING\_MSG  
326  
ER\_XPLUGIN\_READ\_FAILED\_CLOSING\_CONNECTION,  
326



---

ER\_XPLUGIN\_REFERENCE\_TO\_SECURE\_CONN\_WITH\_WRONG\_PLUGIN, 66  
 319 WARN\_BLOCKHOLE\_IN\_RBR, 66  
 ER\_XPLUGIN\_REFERENCE\_TO\_USER\_ACCOUNT\_DOCS\_SECTION, 44  
 324 WARN\_OPTION\_BELOW\_LIMIT, 51  
 ER\_XPLUGIN\_RETRYING\_BIND\_ON\_PORT, 327 WARN\_PLUGIN\_BUSY, 44  
 ER\_XPLUGIN\_SCHEDULER\_STARTED, 327 WARN\_UNENCRYPTED\_TABLE\_IN\_ENCRYPTED\_DB, 121  
 ER\_XPLUGIN\_SCHEDULER\_STOPPED, 327 WARN\_UNSUPPORTED\_ACL\_TABLES\_READ, 143  
 ER\_XPLUGIN\_SERVER\_EXITED, 318 WARN\_USELESS\_SPATIAL\_INDEX, 104  
 ER\_XPLUGIN\_SERVER\_EXITING, 318 ER\_ABORTING error code, 175  
 ER\_XPLUGIN\_SERVER\_STARTS\_HANDLING\_CONNECTIONS, 328 ER\_ABORTING\_CONNECTION error code, 14  
 ER\_XPLUGIN\_SERVER\_STOPPED\_HANDLING\_CONNECTIONS, 328 ER\_ABORTING\_USER\_CONNECTION error code, 278  
 ER\_XPLUGIN\_SHUTDOWN\_TRIGGERED, 327 ER\_ACCESS\_DENIED\_CHANGE\_USER\_ERROR error code, 66  
 ER\_XPLUGIN\_SRV\_SESSION\_INIT\_THREAD\_FAILED, 324 ER\_ACCESS\_DENIED\_ERROR error code, 6  
 ER\_XPLUGIN\_SSL\_HANDSHAKE\_WITH\_SERVER\_FAILED, 325 ER\_ACCESS\_DENIED\_ERROR\_WITHOUT\_PASSWORD error code, 279  
 ER\_XPLUGIN\_STARTUP\_FAILED, 318 ER\_ACCESS\_DENIED\_ERROR\_WITH\_PASSWORD error code, 279  
 ER\_XPLUGIN\_TASK\_SCHEDULING\_FAILED, 324 ER\_ACCESS\_DENIED\_FOR\_USER\_ACCOUNT\_BLOCKED\_BY\_PLUGIN error code, 575  
 ER\_XPLUGIN\_UNABLE\_TO\_ACCEPT\_CONNECTION, 326 ER\_ACCESS\_DENIED\_FOR\_USER\_ACCOUNT\_LOCKED error code, 279  
 ER\_XPLUGIN\_UNABLE\_TO\_USE\_USER\_SESSION\_ACCOUNT, 324 ER\_ACCESS\_DENIED\_NO\_PASSWORD\_ERROR error code, 50  
 ER\_XPLUGIN\_UNEXPECTED\_EXCEPTION\_DISPATCHER, 324 ER\_ACCOUNT\_HAS\_BEEN\_LOCKED error code, 80  
 ER\_XPLUGIN\_UNEXPECTED\_MSG\_DURING\_AUTHENTICATION, 327 ER\_ACCOUNT\_WITH\_EXPIRED\_PASSWORD error code, 9  
 ER\_XPLUGIN\_UNINITIALIZED\_MESSAGE, 325 ER\_ACL\_OPERATION\_FAILED error code, 87  
 ER\_XPLUGIN\_UNIX\_SOCKET\_NOT\_CONFIGURED, 328 ER\_ACL\_WRONG\_OR\_MISSING\_ACL\_TABLES\_LOG error code, 565  
 ER\_XPLUGIN\_USER\_ACCOUNT\_WITH\_ALL\_PERMISSIONS, 327 ER\_ADDRESSES\_FOR\_HOSTNAME\_HEADER error code, 168  
 ER\_XPLUGIN\_USING\_SSL\_CONF\_FROM\_MYSQLX, 318 ER\_ADDRESSES\_FOR\_HOSTNAME\_LIST\_ITEM error code, 168  
 ER\_XPLUGIN\_USING\_SSL\_CONF\_FROM\_SERVER, 318 ER\_ADD\_PARTITION\_NO\_NEW\_PARTITION error code, 38  
 ER\_XPLUGIN\_USING\_SSL\_FOR\_TLS\_CONNECTION, 319 ER\_ADD\_PARTITION\_SUBPART\_ERROR error code, 38  
 ER\_XPLUING\_NET\_STARTUP\_FAILED, 325 ER\_ADMIN\_WRONG\_MRG\_TABLE error code, 36  
 ER\_YES, 3 ER\_AES\_INVALID\_IV error code, 67  
 ER\_ZLIB\_Z\_BUF\_ERROR, 22 ER\_AES\_INVALID\_KDF\_ITERATIONS error code, 87  
 ER\_ZLIB\_Z\_DATA\_ERROR, 22 ER\_AES\_INVALID\_KDF\_NAME error code, 87  
 ER\_ZLIB\_Z\_MEM\_ERROR, 22 ER\_AES\_INVALID\_KDF\_OPTION\_SIZE error code, 87  
 WARN\_AES\_KEY\_SIZE, 87 ER\_AGGREGATE\_IN\_ORDER\_NOT\_SELECT error code, 74  
 WARN\_COND\_ITEM\_TRUNCATED, 46 ER\_AGGREGATE\_ORDER\_FOR\_UNION error code, 71  
 WARN\_DATA\_TRUNCATED, 22 ER\_AGGREGATE\_ORDER\_NON\_AGG\_QUERY error code, 71  
 WARN\_DATA\_TRUNCATED\_FUNCTIONAL\_INDEX, 113 ER\_ALTER\_CONSTRAINT\_ENFORCEMENT\_NOT\_SUPPORTED error code, 134  
 WARN\_NAMED\_PIPE\_ACCESS\_EVERYONE, 68 ER\_ALTER\_FILEGROUP\_FAILED error code, 39  
 WARN\_NON\_ASCII\_SEPARATOR\_NOT\_IMPLEMENTED, 46 ER\_ALTER\_INFO error code, 9  
 WARN\_NO\_CONNECTION\_METADATA, 44 ER\_ALTER\_OPERATION\_NOT\_SUPPORTED error code, 64  
 WARN\_NO\_MASTER\_INFO, 44

---

---

ER ALTER OPERATION NOT SUPPORTED REASON error code, 64	ER AUDIT LOG COULD NOT CREATE AES KEY error code, 534
ER ALTER OPERATION NOT SUPPORTED REASON error code, 64	ER AUDIT LOG COULD NOT OPEN FILE FOR READING error code, 564
ER ALTER OPERATION NOT SUPPORTED REASON error code, 64	ER AUDIT LOG EC WRITER FAILED TO CREATE FILE error code, 315
ER ALTER OPERATION NOT SUPPORTED REASON error code, 64	ER AUDIT LOG EC WRITER FAILED TO INIT COMPRESSION error code, 315
ER ALTER OPERATION NOT SUPPORTED REASON error code, 153	ER AUDIT LOG EC WRITER FAILED TO INIT ENCRYPTION error code, 315
ER ALTER OPERATION NOT SUPPORTED REASON error code, 64	ER AUDIT LOG ENCRYPTION PASSWORD CANNOT BE FETCHED error code, 534
ER ALTER OPERATION NOT SUPPORTED REASON error code, 64	ER AUDIT LOG ENCRYPTION PASSWORD HAS NOT BEEN SET error code, 534
ER ALTER OPERATION NOT SUPPORTED REASON error code, 64	ER AUDIT LOG FILE AUTO PRUNED error code, 596
ER ALTER OPERATION NOT SUPPORTED REASON error code, 64	ER AUDIT LOG FILE HAS BEEN SUCCESSFULLY PROCESSED error code, 564
ER ALTER OPERATION NOT SUPPORTED REASON error code, 64	ER AUDIT LOG FILE NAME DOES NOT HAVE REQUIRED FORMATS error code, 564
ER ALTER OPERATION NOT SUPPORTED REASON error code, 74	ER AUDIT LOG FILE NAME KEYRING ID VALUE IS MISSING error code, 564
ER ALTER OPERATION NOT SUPPORTED REASON error code, 64	ER AUDIT LOG FILE NAME TIMESTAMP VALUE IS MISSING error code, 564
ER ALTER OPERATION NOT SUPPORTED REASON error code, 64	ER AUDIT LOG FILE PRUNE FAILED error code, 596
ER ALTER OPERATION NOT SUPPORTED REASON error code, 65	ER AUDIT LOG FILTER FAILED TO CLOSE TABLE AFTER READING error code, 317
ER ALTER OPERATION NOT SUPPORTED REASON error code, 64	ER AUDIT LOG FILTER FAILED TO DELETE FROM TABLE error code, 316
ER AMBIGUOUS FIELD TERM error code, 36	ER AUDIT LOG FILTER FAILED TO INIT TABLE FOR READING error code, 316
ER ANONYMOUS AUTH ID NOT ALLOWED IN MANDATORY ROLES error code, 284	ER AUDIT LOG FILTER FAILED TO INSERT INTO TABLE error code, 316
ER ANONYMOUS TO GTID UUID SAME AS GROUP NAME error code, 145	ER AUDIT LOG FILTER FAILED TO READ TABLE error code, 317
ER ANONYMOUS TO GTID UUID SAME AS VIEW CHANGE ID error code, 147	ER AUDIT LOG FILTER FAILED TO STORE TABLE FLDS error code, 316
ER APPLIER LOG EVENT VALIDATION ERROR error code, 100	ER AUDIT LOG FILTER FAILED TO UPDATE TABLE error code, 316
ER ASSIGN GTIDS TO ANONYMOUS TRANSACTIONS error code, 144	ER AUDIT LOG FILTER HAS GTID MODE ON error code, 316
ER ATTRIBUTE IGNORED error code, 103	ER AUDIT LOG FILTER FLD FILTERNAME CANNOT BE EMPTY error code, 317
ER AUDIT API ABORT error code, 84	ER AUDIT LOG FILTER INVALID COLUMN COUNT error code, 316
ER AUDIT CANT ABORT COMMAND error code, 275	ER AUDIT LOG FILTER INVALID COLUMN DEFINITION error code, 316
ER AUDIT CANT ABORT EVENT error code, 275	ER AUDIT LOG FILTER IS NOT INSTALLED error code, 313
ER AUDIT LOG CANNOT GENERATE PASSWORD error code, 571	ER AUDIT LOG FILTER RESULT MSG error code, 315
ER AUDIT LOG CANNOT READ PASSWORD error code, 564	ER AUDIT LOG FILTER USER AND HOST CANNOT BE EMPTY error code, 317
ER AUDIT LOG CANNOT REMOVE PASSWORD error code, 564	ER AUDIT LOG HAS NOT BEEN INSTALLED error code, 569
ER AUDIT LOG CANNOT SET LOG POLICY WITH OTHERS error code, 314	ER AUDIT LOG HOST NAME INVALID CHARACTER error code, 534
ER AUDIT LOG CANNOT STORE PASSWORD error code, 564	

---

---

ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR error code, 314	ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER error code, 534
ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE error code, 131	ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS error code, 314
ER_AUDIT_LOG_INVALID_FILE_CONTENT error code, 564	ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE error code, 315
ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE error code, 639	ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED error code, 314
ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED error code, 533	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED error code, 314
ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST error code, 535	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE_ error code, 314
ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY error code, 534	ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EV error code, 200
ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR error code, 533	ER_AUDIT_PLUGIN_HAS_INVALID_DATA error code, 200
ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL error code, 315	ER_AUDIT_WARNING error code, 275
ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE error code, 315	ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM error code, 197
ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE error code, 315	ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TAB error code, 197
ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR error code, 316	ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_WILL error code, 196
ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY error code, 535	ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME error code, 196
ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID error code, 563	ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE error code, 196
ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED error code, 534	ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAM error code, 585
ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED error code, 314	ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZA error code, 585
ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED error code, 565	ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED error code, 196
ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH error code, 315	ER_AUTHCACHE_PLUGIN_CONFIG error code, 195
ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED error code, 568	ER_AUTHCACHE_PLUGIN_MISSING error code, 195
ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST error code, 314	ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_RO error code, 197
ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED error code, 536	ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE error code, 197
ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE error code, 534	ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOLV error code, 195
ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT error code, 569	ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME error code, 585
ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE error code, 568	ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATIO error code, 585
ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH error code, 569	ER_AUTHCACHE_ROLE_TABLES_DODGY error code, 195
ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH error code, 87	ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLV error code, 197
ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHA error code, 535	ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING error code, 196
	ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWO error code, 195

---

---

ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD error code, 196	ER_AUTH_CERTS_SAVED_TO_DATADIR error code, 194
ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN error code, 195	ER_AUTH_CERT_GENERATION_DISABLED error code, 194
ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE error code, 195	ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLE error code, 557
ER_AUTHCACHE_USER_TABLE_DODGY error code, 195	ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG error code, 603
ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY error code, 636	ER_AUTH_KEYS_SAVED_TO_DATADIR error code, 194
ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY error code, 609	ER_AUTH_KEY_GENERATION_DISABLED error code, 195
ER_AUTHENTICATION_OCI_IAM error code, 610	ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT error code, 194
ER_AUTHENTICATION_OCI_IMDS error code, 609	ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG error code, 320
ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_TOKEN error code, 610	ER_AUTH_RSA_CANT_FIND error code, 192
ER_AUTHENTICATION_OCI_INVALID_TOKEN error code, 636	ER_AUTH_RSA_CANT_PARSE error code, 192
ER_AUTHENTICATION_OCI_NONCE error code, 610	ER_AUTH_RSA_CANT_READ error code, 192
ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND error code, 610	ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION error code, 194
ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS error code, 610	ER_AUTH_RSA_FILES_NOT_FOUND error code, 192
ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS_INVALID_TOKEN error code, 637	ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION error code, 194
ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED error code, 609	ER_AUTH_USING_EXISTING_CERTS error code, 194
ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR error code, 609	ER_AUTOINC_READ_FAILED error code, 35
ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH error code, 636	ER_AUTO_CONVERT error code, 21
ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED error code, 636	ER_AUTO_INCREMENT_CONFLICT error code, 66
ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT error code, 608	ER_AUTO_OPTIONS_FAILED error code, 181
ER_AUTHENTICATION_PLUGIN_LOG error code, 609	ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF error code, 57
ER_AUTHENTICATION_PLUGIN_OOM error code, 608	ER_BACK_IN_TIME error code, 174
ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED error code, 608	ER_BAD_DB_ERROR error code, 6
ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT_BUFFER error code, 608	ER_BAD_FIELD_ERROR error code, 7
ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT error code, 608	ER_BAD_FT_COLUMN error code, 24
ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED error code, 608	ER_BAD_HOST_ERROR error code, 6
ER_AUTHENTICATION_POLICY_MISMATCH error code, 149	ER_BAD_LOG_STATEMENT error code, 42
ER_AUTH_CANT_ACTIVATE_ROLE error code, 193	ER_BAD_NULL_ERROR error code, 6
ER_AUTH_CANT_CREATE_RSA_PAIR error code, 193	ER_BAD_NULL_ERROR_NOT_IGNORED error code, 6
ER_AUTH_CANT_SET_DEFAULT_PLUGIN error code, 181	ER_BAD_REPLICANT_BUFFER error code, 17
ER_AUTH_CANT_WRITE_PRIVKEY error code, 194	ER_BAD_REPLICA error code, 17
ER_AUTH_CANT_WRITE_PUBKEY error code, 194	ER_BAD_REPLICA_AUTO_POSITION error code, 57
	ER_BAD_REPLICA_UNTIL_COND error code, 23
	ER_BAD_SLAVE error code, 17
	ER_BAD_SLAVE_AUTO_POSITION error code, 57
	ER_BAD_SLAVE_UNTIL_COND error code, 23
	ER_BAD_TABLE_ERROR error code, 6
	ER_BAD_TIMESTAMP_FORMAT error code, 157
	ER_BASE64_DECODE_ERROR error code, 42
	ER_BASEDIR_SET_TO error code, 281
	ER_BEFORE_DML_VALIDATION_ERROR error code, 78
	ER_BEG_INITFILE error code, 176

---

---

ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD error code, 640	ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED_SE error code, 622
ER_BEYOND_SERVER_UPGRADE_THRESHOLD error code, 640	ER_BINLOG_CRASH_RECOVERY_FAILED error code, 271
ER_BINLOG_ATTACHING_THREAD_MEMORY_FINALY error code, 264	ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG error code, 622
ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX error code, 54	ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED error code, 623
ER_BINLOG_CACHE_SIZE_TOO_LARGE error code, 276	ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED error code, 622
ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX error code, 267	ER_BINLOG_CREATE_ROUTINE_NEED_SUPER error code, 32
ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED_BINLOG error code, 271	ER_BINLOG_END error code, 175
ER_BINLOG_CANT_CLOSE_TMP_INDEX error code, 268	ER_BINLOG_ERROR_GETTING_NEXT_LOG_FROM_INDEX error code, 268
ER_BINLOG_CANT_COPY_INDEX_TO_TMP error code, 268	ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG error code, 266
ER_BINLOG_CANT_CREATE_CACHE_FOR_LOG error code, 265	ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG error code, 266
ER_BINLOG_CANT_DELETE_FILE error code, 268	ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA error code, 266
ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_INDEX error code, 270	ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO error code, 266
ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH_FILES error code, 270	ER_BINLOG_EVENTS_READ_FROM_RELAY_LOG_INFO error code, 266
ER_BINLOG_CANT_FIND_LOG_IN_INDEX error code, 270	ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED error code, 283
ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME error code, 266	ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOGETHER error code, 298
ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG error code, 267	ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED_TOGETHER error code, 105
ER_BINLOG_CANT_MOVE_TMP_TO_INDEX error code, 268	ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING error code, 267
ER_BINLOG_CANT_OPEN_CRASHED_BINLOG error code, 271	ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING error code, 267
ER_BINLOG_CANT_OPEN_FOR_LOGGING error code, 266	ER_BINLOG_FAILED_TO_DELETE_LOG_FILE error code, 270
ER_BINLOG_CANT_OPEN_LOG error code, 265	ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING error code, 267
ER_BINLOG_CANT_OPEN_TMP_INDEX error code, 268	ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE error code, 269
ER_BINLOG_CANT_RESIZE_CACHE error code, 265	ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE error code, 268
ER_BINLOG_CANT_SET_TMP_INDEX_NAME error code, 268	ER_BINLOG_FAILED_TO_READ_REGISTER_FILE error code, 269
ER_BINLOG_CANT_TRIM_CRASHED_BINLOG error code, 271	ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE error code, 269
ER_BINLOG_CANT_USE_FOR_LOGGING error code, 267	ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING error code, 267
ER_BINLOG_CRASHED_BINLOG_TRIMMED error code, 271	ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK error code, 271
ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED error code, 622	ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK error code, 271
ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS error code, 622	

---

---

ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME error code, 269	ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE error code, 268
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE error code, 266	ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE error code, 269
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN error code, 267	ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG error code, 269
ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLE error code, 254	ER_BINLOG_PURGE_PROHIBITED error code, 30
ER_BINLOG_FATAL_ERROR error code, 43	ER_BINLOG_RECOVERING_AFTER_CRASH_USING error code, 270
ER_BINLOG_FILE_BEING_READ_NOT_PURGED error code, 265	ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE error code, 47
ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED error code, 265	ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE error code, 48
ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW error code, 265	ER_BINLOG_ROW_INJECTION_AND_STMT_MODE error code, 48
ER_BINLOG_FILE_NAME_TOO_LONG error code, 265	ER_BINLOG_ROW_LOGGING_FAILED error code, 40
ER_BINLOG_FILE_OPEN_FAILED error code, 283	ER_BINLOG_ROW_MODE_AND_STMT_ENGINE error code, 47
ER_BINLOG_IO_ERROR_READING_HEADER error code, 265	ER_BINLOG_ROW_VALUE_OPTION_IGNORED error code, 526
ER_BINLOG_LOGGING_IMPOSSIBLE error code, 43	ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFTER_I error code, 527
ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS error code, 270	ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX error code, 54
ER_BINLOG_LOGGING_INCIDENT_TO_STOP_SLAVES error code, 270	ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE error code, 277
ER_BINLOG_LOGGING_NOT_POSSIBLE error code, 297	ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES error code, 63
ER_BINLOG_LOGICAL_CORRUPTION error code, 65	ER_BINLOG_STMT_MODE_AND_ROW_ENGINE error code, 48
ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG error code, 298	ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READONLY error code, 561
ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION error code, 119	ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL error code, 543
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP error code, 120	ER_BINLOG_UNSAFE_AUTOINC_COLUMNS error code, 47
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP error code, 120	ER_BINLOG_UNSAFE_AUTOINC_COLUMNS error code, 47
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE error code, 119	ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST error code, 53
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCODE error code, 120	ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT error code, 52
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE error code, 119	ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT error code, 52
ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE error code, 48	ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC error code, 53
ER_BINLOG_NEEDS_SERVERID error code, 179	ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBSTATEMENT error code, 563
ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_RELAY_LOG error code, 254	ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN error code, 69
ER_BINLOG_PURGE_EMFILE error code, 42	ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT error code, 52
ER_BINLOG_PURGE_FATAL_ERR error code, 30	ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE error code, 52
ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_FOUND error code, 268	
ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTERED_FILE error code, 269	
ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTERED_FILE error code, 269	

---

---

ER\_BINLOG\_UNSAFE\_INSERT\_TWO\_KEYS error code, 53  
 ER\_BINLOG\_UNSAFE\_LIMIT error code, 48  
 ER\_BINLOG\_UNSAFE\_MESSAGE\_AND\_STATEMENT error code, 277  
 ER\_BINLOG\_UNSAFE\_MIXED\_STATEMENT error code, 50  
 ER\_BINLOG\_UNSAFE\_MULTIPLE\_ENGINES\_AND\_SELF\_INDEXING error code, 50  
 ER\_BINLOG\_UNSAFE\_NONTRANS\_AFTER\_TRANS error code, 48  
 ER\_BINLOG\_UNSAFE\_NOWAIT error code, 93  
 ER\_BINLOG\_UNSAFE\_REPLACE\_SELECT error code, 52  
 ER\_BINLOG\_UNSAFE\_ROUTINE error code, 32  
 ER\_BINLOG\_UNSAFE\_SKIP\_LOCKED error code, 93  
 ER\_BINLOG\_UNSAFE\_STATEMENT error code, 43  
 ER\_BINLOG\_UNSAFE\_SYSTEM\_FUNCTION error code, 48  
 ER\_BINLOG\_UNSAFE\_SYSTEM\_TABLE error code, 48  
 ER\_BINLOG\_UNSAFE\_SYSTEM\_VARIABLE error code, 48  
 ER\_BINLOG\_UNSAFE\_UDF error code, 48  
 ER\_BINLOG\_UNSAFE\_UPDATE\_IGNORE error code, 52  
 ER\_BINLOG\_UNSAFE\_WRITE\_AUTOINC\_SELECT error code, 53  
 ER\_BINLOG\_UNSAFE\_XA error code, 86  
 ER\_BINLOG\_USE\_V1\_ROW\_EVENTS\_IGNORED error code, 527  
 ER\_BINLOG\_WARNING\_SUPPRESSED error code, 272  
 ER\_BLOBS\_AND\_NO\_TERMINATED error code, 9  
 ER\_BLOB\_CANT\_HAVE\_DEFAULT error code, 10  
 ER\_BLOB\_FIELD\_IN\_PART\_FUNC\_ERROR error code, 37  
 ER\_BLOB\_KEY\_WITHOUT\_LENGTH error code, 15  
 ER\_BLOB\_USED\_AS\_KEY error code, 8  
 ER\_BOOST\_GEOMETRY\_CENTROID\_EXCEPTION error code, 72  
 ER\_BOOST\_GEOMETRY\_EMPTY\_INPUT\_EXCEPTION error code, 72  
 ER\_BOOST\_GEOMETRY\_INCONSISTENT\_TURNS\_EXCEPTION error code, 80  
 ER\_BOOST\_GEOMETRY\_OVERLAY\_INVALID\_INPUT\_EXCEPTION error code, 72  
 ER\_BOOST\_GEOMETRY\_SELF\_INTERSECTION\_POINT\_EXCEPTION error code, 72  
 ER\_BOOST\_GEOMETRY\_TURN\_INFO\_EXCEPTION error code, 72  
 ER\_BOOST\_GEOMETRY\_UNKNOWN\_EXCEPTION error code, 72  
 ER\_BOOTSTRAP\_CANT\_THREAD error code, 162  
 ER\_BUFPOOL\_RESIZE\_INPROGRESS error code, 84  
 ER\_BUILD\_ID error code, 625  
 ER\_BULK\_EXECUTOR\_ERROR error code, 158  
 ER\_BULK\_EXECUTOR\_INFO error code, 629  
 ER\_BULK\_LOADER\_COLUMN\_TOO\_BIG\_FOR\_LEFTOVER\_BUFFER error code, 159  
 ER\_BULK\_LOADER\_COMPONENT\_ERROR error code, 159  
 ER\_BULK\_LOADER\_INVALID\_FILE\_CONTAINS\_LESS\_LINES\_THAN\_IGNORED error code, 159  
 ER\_BULK\_LOADER\_FILE\_CONTAINS\_LESS\_LINES\_THAN\_IGNORED error code, 629  
 ER\_BULK\_LOADER\_INFO error code, 629  
 ER\_BULK\_LOAD\_DATA\_FAILED error code, 159  
 ER\_BULK\_PARSER\_COPY\_BUFFER\_SIZE\_EXCEEDED error code, 160  
 ER\_BULK\_PARSER\_COPY\_BUFFER\_SIZE\_EXCEEDED\_LOG error code, 630  
 ER\_BULK\_PARSER\_INCOMPLETE\_ESCAPE\_SEQUENCE error code, 160  
 ER\_BULK\_PARSER\_INCOMPLETE\_ESCAPE\_SEQUENCE\_LOG error code, 631  
 ER\_BULK\_PARSER\_MISSING\_ENCLOSED\_BY error code, 159  
 ER\_BULK\_PARSER\_MISSING\_ENCLOSED\_BY\_LOG error code, 630  
 ER\_BULK\_PARSER\_ROW\_BUFFER\_MAX\_TOTAL\_COLS\_EXCEEDED error code, 159  
 ER\_BULK\_PARSER\_ROW\_BUFFER\_MAX\_TOTAL\_COLS\_EXCEEDED\_LOG error code, 630  
 ER\_BULK\_PARSER\_UNEXPECTED\_CHAR\_AFTER\_COLUMN\_NAME error code, 160  
 ER\_BULK\_PARSER\_UNEXPECTED\_CHAR\_AFTER\_COLUMN\_NAME\_LOG error code, 631  
 ER\_BULK\_PARSER\_UNEXPECTED\_CHAR\_AFTER\_ENDING\_BRACKET error code, 160  
 ER\_BULK\_PARSER\_UNEXPECTED\_CHAR\_AFTER\_ENDING\_BRACKET\_LOG error code, 630  
 ER\_BULK\_PARSER\_UNEXPECTED\_CHAR\_AFTER\_NULL\_ESCAPE\_CHARACTER error code, 160  
 ER\_BULK\_PARSER\_UNEXPECTED\_CHAR\_AFTER\_NULL\_ESCAPE\_CHARACTER\_LOG error code, 630  
 ER\_BULK\_PARSER\_UNEXPECTED\_END\_OF\_INPUT error code, 160  
 ER\_BULK\_PARSER\_UNEXPECTED\_END\_OF\_INPUT\_LOG error code, 630  
 ER\_BULK\_PARSER\_UNEXPECTED\_ROW\_TERMINATOR error code, 630  
 ER\_BULK\_PARSER\_UNEXPECTED\_ROW\_TERMINATOR\_LOG error code, 630  
 ER\_BULK\_READER\_COMMUNICATION\_ERROR error code, 159  
 ER\_BULK\_READER\_COMMUNICATION\_ERROR\_LOG error code, 630  
 ER\_BULK\_READER\_INFO error code, 629

---

---

ER\_BULK\_READER\_LIBCURL\_ERROR error code, 159  
 ER\_BULK\_READER\_LIBCURL\_ERROR\_LOG error code, 629  
 ER\_BULK\_READER\_LIBCURL\_INIT\_FAILED error code, 158  
 ER\_BULK\_READER\_LIBCURL\_INIT\_FAILED\_LOG error code, 629  
 ER\_BULK\_READER\_SERVER\_ERROR error code, 159  
 ER\_BULK\_READER\_SERVER\_ERROR\_LOG error code, 629  
 ER\_CACHING\_SHA2\_PASSWORD\_SECOND\_PASSWORD error code, 550  
 ER\_CALL\_ME\_LOCALHOST error code, 175  
 ER\_CANNOT\_ADD\_FOREIGN error code, 19  
 ER\_CANNOT\_ADD\_FOREIGN\_BASE\_COL\_STORED error code, 86  
 ER\_CANNOT\_ADD\_FOREIGN\_BASE\_COL\_VIRTUAL error code, 84  
 ER\_CANNOT\_ALTER\_SRID\_DUE\_TO\_INDEX error code, 101  
 ER\_CANNOT\_CHANGE\_TO\_ROOT\_DIR error code, 281  
 ER\_CANNOT\_CONVERT\_STRING error code, 125  
 ER\_CANNOT\_CREATE\_VIRTUAL\_INDEX\_CONSTRAINT error code, 84  
 ER\_CANNOT\_DISCARD\_TEMPORARY\_TABLE error code, 69  
 ER\_CANNOT\_DROP\_COLUMN\_FUNCTIONAL\_INDEX error code, 113  
 ER\_CANNOT\_FIND\_KEY\_IN\_KEYRING error code, 85  
 ER\_CANNOT\_GET\_SERVER\_VERSION\_FROM\_TABLESPACE error code, 553  
 ER\_CANNOT\_GRANT\_ROLES\_TO\_ANONYMOUS\_USER error code, 127  
 ER\_CANNOT\_GRANT\_SYSTEM\_PRIV\_TO\_MANDATORY\_PROC error code, 129  
 ER\_CANNOT\_INTERPRET\_PERSISTED\_SENSITIVE\_VARIABLES error code, 613  
 ER\_CANNOT\_LOAD\_FROM\_TABLE\_V2 error code, 53  
 ER\_CANNOT\_LOCK\_USER\_MANAGEMENT\_CACHES error code, 91  
 ER\_CANNOT\_LOG\_PARTIAL\_DROP\_DATABASE\_WITH\_GRID error code, 77  
 ER\_CANNOT\_PERSIST\_SENSITIVE\_VARIABLES error code, 154  
 ER\_CANNOT\_PURGE\_BINLOG\_WITH\_BACKUP\_LOCK error code, 153  
 ER\_CANNOT\_SET\_DATABASE\_ENCRYPTION error code, 122  
 ER\_CANNOT\_SET\_LOG\_ERROR\_SERVICES error code, 282  
 ER\_CANNOT\_SET\_SERVER\_VERSION\_IN\_TABLESPACE error code, 553  
 ER\_CANNOT\_SET\_TABLESPACE\_ENCRYPTION error code, 122  
 ER\_CANNOT\_SET\_TABLE\_ENCRYPTION error code, 122  
 ER\_CANNOT\_USER error code, 31  
 ER\_CANNOT\_USER\_REFERENCED\_AS\_DEFINER error code, 142  
 ER\_CANNOT\_USE\_AUTOEXTEND\_SIZE\_CLAUSE error code, 145  
 ER\_CANNOT\_USE\_ENCRYPTION\_CLAUSE error code, 122  
 ER\_CANT\_ACCESS\_CAPATH error code, 181  
 ER\_CANT\_AGGREGATE\_2COLLATIONS error code, 22  
 ER\_CANT\_AGGREGATE\_3COLLATIONS error code, 22  
 ER\_CANT\_AGGREGATE\_NCOLLATIONS error code, 23  
 ER\_CANT\_ALLOC\_TABLE\_OBJECT error code, 259  
 ER\_CANT\_CHANGE\_SYS\_VAR\_IN\_READ\_ONLY\_MODE error code, 161  
 ER\_CANT\_CHANGE\_TX\_CHARACTERISTICS error code, 41  
 ER\_CANT\_CHECK\_PID\_PATH error code, 388  
 ER\_CANT\_CHOWN\_DATADIR error code, 180  
 ER\_CANT\_COMBINE\_ANONYMOUS\_TO\_GTID\_AND\_AUTOPOSITION error code, 143  
 ER\_CANT\_CREATE\_ADMIN\_THREAD error code, 549  
 ER\_CANT\_CREATE\_CACHE\_FOR\_DB\_OPT error code, 260  
 ER\_CANT\_CREATE\_DB error code, 3  
 ER\_CANT\_CREATE\_FILE error code, 3  
 ER\_CANT\_CREATE\_GEOMETRY\_OBJECT error code, 32  
 ER\_CANT\_CREATE\_HANDLER\_FILE error code, 37  
 ER\_CANT\_CREATE\_HANDLER\_OBJECT\_FOR\_TABLE error code, 259  
 ER\_CANT\_CREATE\_HANDLE\_MGR\_THREAD error code, 165  
 ER\_CANT\_CREATE\_INTERRUPT\_THREAD error code, 173  
 ER\_CANT\_CREATE\_NAMED\_PIPES\_THREAD error code, 173  
 ER\_CANT\_CREATE\_PID\_FILE error code, 172  
 ER\_CANT\_CREATE\_SCHEDULER\_THREAD error code, 167  
 ER\_CANT\_CREATE\_SHM\_THREAD error code, 173  
 ER\_CANT\_CREATE\_SHUTDOWN\_THREAD error code, 172  
 ER\_CANT\_CREATE\_TABLE error code, 3  
 ER\_CANT\_CREATE\_TABLE\_SHARE\_FROM\_FRM error code, 258  
 ER\_CANT\_CREATE\_TCPIP\_THREAD error code, 173  
 ER\_CANT\_CREATE\_TEST\_FILE error code, 172



---

ER\_CANT\_CREATE\_THREAD error code, 13  
 ER\_CANT\_CREATE\_USER\_WITH\_GRANT error code, 32  
 ER\_CANT\_CREATE\_UUID error code, 170  
 ER\_CANT\_DETACH\_SESSION\_LEFT\_BY\_PLUGIN error code, 216  
 ER\_CANT\_DO\_IMPLICIT\_COMMIT\_IN\_TRX\_WHEN\_GTID\_ENABLED error code, 58  
 ER\_CANT\_DO\_THIS\_DURING\_AN\_TRANSACTION error code, 15  
 ER\_CANT\_DROP\_FIELD\_OR\_KEY error code, 9  
 ER\_CANT\_ENFORCE\_GTID\_CONSISTENCY\_WITH\_ONLINE\_TRANSACTION error code, 79  
 ER\_CANT\_EXECUTE\_COMMAND\_WITH\_ASSIGNED\_GTID error code, 153  
 ER\_CANT\_EXECUTE\_IN\_READ\_ONLY\_TRANSACTION error code, 59  
 ER\_CANT\_FIND\_DL\_ENTRY error code, 12  
 ER\_CANT\_FIND\_SYSTEM\_REC error code, 4  
 ER\_CANT\_FIND\_UDF error code, 12  
 ER\_CANT\_GET\_STAT error code, 4  
 ER\_CANT\_HASH\_DO\_AND\_IGNORE\_RULES error code, 181  
 ER\_CANT\_IDENTIFY\_CHARSET\_USING\_DEFAULT error code, 260  
 ER\_CANT\_INCREASE\_MAX\_OPEN\_FILES error code, 177  
 ER\_CANT\_INITIALIZE\_BUILTIN\_PLUGINS error code, 180  
 ER\_CANT\_INITIALIZE\_DYNAMIC\_PLUGINS error code, 180  
 ER\_CANT\_INITIALIZE\_EARLY\_PLUGINS error code, 180  
 ER\_CANT\_INITIALIZE\_GTID error code, 180  
 ER\_CANT\_INITIALIZE\_UDF error code, 12  
 ER\_CANT\_INIT\_DBS error code, 178  
 ER\_CANT\_INIT\_SCHEDULER\_THREAD error code, 167  
 ER\_CANT\_INIT\_TC\_LOG error code, 166  
 ER\_CANT\_INIT\_TIMER error code, 181  
 ER\_CANT\_JOIN\_SHUTDOWN\_THREAD error code, 181  
 ER\_CANT\_LOCK error code, 4  
 ER\_CANT\_LOCK\_LOG\_TABLE error code, 40  
 ER\_CANT\_LOCK\_TABLE error code, 259  
 ER\_CANT\_LOCK\_TABLESPACE error code, 259  
 ER\_CANT\_MODIFY\_SRID\_0 error code, 108  
 ER\_CANT\_MODIFY\_SRS\_USED\_BY\_COLUMN error code, 109  
 ER\_CANT\_OPEN\_AND\_LOCK\_PRIVILEGE\_TABLES error code, 200  
 ER\_CANT\_OPEN\_CA error code, 181  
 ER\_CANT\_OPEN\_DATADIR\_AFTER\_UPGRADE\_FAILURE error code, 261  
 ER\_CANT\_OPEN\_DB\_OPT\_USING\_DEFAULT\_CHARSET error code, 260  
 ER\_CANT\_OPEN\_DIR error code, 262  
 ER\_CANT\_OPEN\_ERROR\_LOG error code, 182  
 ER\_CANT\_OPEN\_FILE error code, 4  
 ER\_CANT\_OPEN\_FRM\_FILE error code, 199  
 ER\_CANT\_OPEN\_LIBRARY error code, 12  
 ER\_CANT\_OPEN\_TABLE\_MYSQL\_PROC error code, 261  
 ER\_CANT\_PARSE\_STORED\_ROUTINE\_BODY error code, 261  
 ER\_CANT\_READ\_PROCESS\_EXPRESSION\_FOR\_GENERATED\_COLUMN error code, 572  
 ER\_CANT\_READ\_DIR error code, 4  
 ER\_CANT\_READ\_ERRMSG error code, 178  
 ER\_CANT\_READ\_FRM\_FILE error code, 199  
 ER\_CANT\_READ\_TABLE\_MYSQL\_PROC error code, 261  
 ER\_CANT\_REMOVE\_ALL\_FIELDS error code, 9  
 ER\_CANT\_REMOVE\_PID\_FILE error code, 172  
 ER\_CANT\_RENAME\_LOG\_TABLE error code, 42  
 ER\_CANT\_REOPEN\_TABLE error code, 13  
 ER\_CANT\_REPLICATE\_ANONYMOUS\_WITH\_AUTO\_POSITION error code, 533  
 ER\_CANT\_REPLICATE\_ANONYMOUS\_WITH\_GTID\_MODE\_ON error code, 533  
 ER\_CANT\_REPLICATE\_GTID\_WITH\_GTID\_MODE\_OFF error code, 533  
 ER\_CANT\_RESET\_MASTER error code, 85  
 ER\_CANT\_RESET\_SOURCE error code, 85  
 ER\_CANT\_SAVE\_GTIDS error code, 181  
 ER\_CANT\_SET\_ANONYMOUS\_TO\_GTID\_AND\_WAIT\_UNTIL error code, 144  
 ER\_CANT\_SET\_DATADIR error code, 180  
 ER\_CANT\_SET\_DATA\_DIR error code, 547  
 ER\_CANT\_SET\_ERROR\_LOG\_SERVICE error code, 107  
 ER\_CANT\_SET\_ERROR\_SUPPRESSION\_LIST error code, 111  
 ER\_CANT\_SET\_ERROR\_SUPPRESSION\_LIST\_FROM\_COMMENT error code, 539  
 ER\_CANT\_SET\_GTID\_MODE error code, 79  
 ER\_CANT\_SET\_GTID\_NEXT\_LIST\_TO\_NON\_NULL\_WHEN\_GTID error code, 58  
 ER\_CANT\_SET\_GTID\_NEXT\_TO\_ANONYMOUS\_WHEN\_GTID error code, 58  
 ER\_CANT\_SET\_GTID\_NEXT\_TO\_GTID\_WHEN\_GTID\_MODE error code, 58  
 ER\_CANT\_SET\_GTID\_NEXT\_WHEN\_OWNING\_GTID error code, 59  
 ER\_CANT\_SET\_GTID\_PURGED\_DUE\_SETS\_CONSTRAINTS error code, 90  
 ER\_CANT\_SET\_GTID\_PURGED\_WHEN\_GTID\_EXECUTED error code, 63

---

---

ER\_CANT\_SET\_GTID\_PURGED\_WHEN\_OWNED\_GTIDS error code, 63  
 ER\_CANT\_SET\_HANDLER\_REFERENCE\_FOR\_TABLE error code, 259  
 ER\_CANT\_SET\_PATH\_FOR error code, 262  
 ER\_CANT\_SET\_PERSISTED error code, 161  
 ER\_CANT\_SET\_SQL\_AFTER\_OR\_BEFORE\_GTIDS\_WITH\_HANDLER\_REFERENCE error code, 144  
 ER\_CANT\_SET\_UP\_PERSISTED\_VALUES error code, 180  
 ER\_CANT\_SET\_VARIABLE\_WHEN\_OWNING\_GTID error code, 81  
 ER\_CANT\_START\_ERROR\_LOG\_SERVICE error code, 280  
 ER\_CANT\_STAT\_DATADIR error code, 180  
 ER\_CANT\_STAT\_FILE error code, 270  
 ER\_CANT\_UPDATE\_TABLE\_IN\_CREATE\_TABLE\_SELECT error code, 54  
 ER\_CANT\_UPDATE\_USED\_TABLE\_IN\_SF\_OR\_TRG error code, 34  
 ER\_CANT\_UPDATE\_WITH\_READLOCK error code, 19  
 ER\_CANT\_UPGRADE\_GENERATED\_COLUMNS\_TO\_DD error code, 259  
 ER\_CANT\_USE\_ANONYMOUS\_TO\_GTID\_WITH\_GTID\_MODE error code, 143  
 ER\_CANT\_USE\_AUTO\_POSITION\_WITH\_GTID\_MODE\_OFF error code, 79  
 ER\_CANT\_USE\_GTID\_ONLY\_WITH\_GTID\_MODE\_NOT\_ORN error code, 151  
 ER\_CANT\_USE\_OPTION\_HERE error code, 20  
 ER\_CANT\_USE\_SAME\_UUID\_AS\_GROUP\_NAME error code, 145  
 ER\_CANT\_USE\_SAME\_UUID\_AS\_VIEW\_CHANGE\_UUID error code, 147  
 ER\_CANT\_WAIT\_FOR\_EXECUTED\_GTID\_SET\_WHILE\_OWNING\_GTID error code, 84  
 ER\_CAPACITY\_EXCEEDED error code, 84  
 ER\_CAPACITY\_EXCEEDED\_IN\_PARSER error code, 85  
 ER\_CAPACITY\_EXCEEDED\_IN\_RANGE\_OPTIMIZER error code, 84  
 ER\_CA\_SELF\_SIGNED error code, 169  
 ER\_CHANGED\_ENFORCE\_GTID\_CONSISTENCY error code, 166  
 ER\_CHANGED\_GTID\_MODE error code, 166  
 ER\_CHANGED\_MAX\_CONNECTIONS error code, 177  
 ER\_CHANGED\_MAX\_OPEN\_FILES error code, 177  
 ER\_CHANGED\_TABLE\_OPEN\_CACHE error code, 177  
 ER\_CHANGE\_MASTER\_PASSWORD\_LENGTH error code, 73  
 ER\_CHANGE\_MASTER\_WRONG\_COMPRESSION\_ALGORITHM error code, 132  
 ER\_CHANGE\_MASTER\_WRONG\_COMPRESSION\_ALGORITHM\_LIST\_CLIENT error code, 132  
 ER\_CHANGE\_REPLICATION\_SOURCE\_NO\_OPTIONS\_FOR\_GTID error code, 150  
 ER\_CHANGE\_REP\_SOURCE\_CANT\_DISABLE\_AUTO\_POSITION error code, 151  
 ER\_CHANGE\_REP\_SOURCE\_CANT\_DISABLE\_AUTO\_POS\_WITH\_HANDLER\_REFERENCE error code, 151  
 ER\_CHANGE\_REP\_SOURCE\_CANT\_DISABLE\_GTID\_ONLY\_WITH\_HANDLER\_REFERENCE error code, 151  
 ER\_CHANGE\_REP\_SOURCE\_CANT\_DISABLE\_REQ\_ROW\_FORMAT error code, 150  
 ER\_CHANGE\_REP\_SOURCE\_GR\_CHANNEL\_WITH\_GTID\_MODE error code, 151  
 ER\_CHANGE\_RPL\_INFO\_REPOSITORY\_FAILURE error code, 54  
 ER\_CHANGE\_RPL\_SRC\_WRONG\_COMPRESSION\_ALGORITHM error code, 147  
 ER\_CHANGE\_SOURCE\_PASSWORD\_LENGTH error code, 73  
 ER\_CHANGE\_SOURCE\_WRONG\_COMPRESSION\_ALGORITHM error code, 132  
 ER\_CHANGE\_SOURCE\_WRONG\_COMPRESSION\_ALGORITHM\_LIST\_CLIENT error code, 132  
 ER\_CHANGE\_SOURCE\_WRONG\_COMPRESSION\_LEVEL\_CLIENT error code, 132  
 ER\_CHARACTER\_SET\_MISMATCH error code, 141  
 ER\_CHECK\_CHECKING\_TABLE error code, 258  
 ER\_CHECKREAD error code, 4  
 ER\_CHECK\_CONSTRAINT\_CLAUSE\_USING\_FK\_REFER\_ACTION error code, 121  
 ER\_CHECK\_CONSTRAINT\_DUP\_NAME error code, 121  
 ER\_CHECK\_CONSTRAINT\_FUNCTION\_IS\_NOT\_ALLOWED error code, 121  
 ER\_CHECK\_CONSTRAINT\_NAMED\_FUNCTION\_IS\_NOT\_ALLOWED error code, 120  
 ER\_CHECK\_CONSTRAINT\_NOT\_FOUND error code, 121  
 ER\_CHECK\_CONSTRAINT\_REFERS\_AUTO\_INCREMENT\_COLUMN error code, 121  
 ER\_CHECK\_CONSTRAINT\_REFERS\_UNKNOWN\_COLUMN error code, 121  
 ER\_CHECK\_CONSTRAINT\_ROW\_VALUE error code, 121  
 ER\_CHECK\_CONSTRAINT\_VARIABLES error code, 121  
 ER\_CHECK\_CONSTRAINT\_VIOLATED error code, 121  
 ER\_CHECK\_NOT\_IMPLEMENTED error code, 15  
 ER\_CHECK\_NO\_SUCH\_TABLE error code, 15  
 ER\_CHECK\_NO\_SUCH\_TABLE\_FUNCTIONS error code, 642  
 ER\_CHECK\_TABLE\_FUNCTIONS\_DETAIL error code, 642  
 ER\_CHECK\_TABLE\_FUNCTIONS\_LIST\_CLIENT error code, 642

---

ER\_CHECK\_TABLE\_INSTANT\_VERSION\_BIT\_SET error code, 632  
 ER\_CHECK\_TABLE\_MIN\_REC\_FLAG\_NOT\_SET error code, 635  
 ER\_CHECK\_TABLE\_MIN\_REC\_FLAG\_SET error code, 634  
 ER\_CLIENT\_DOES\_NOT\_SUPPORT error code, 101  
 ER\_CLIENT\_FILE\_PRIVILEGE\_FOR\_REPLICATION\_CHECK error code, 156  
 ER\_CLIENT\_GTID\_UNSAFE\_CREATE\_DROP\_TEMP\_TABLE\_IN\_PROGRESS error code, 112  
 ER\_CLIENT\_INTERACTION\_TIMEOUT error code, 146  
 ER\_CLIENT\_KEYRING\_UDF\_KEY\_INVALID error code, 133  
 ER\_CLIENT\_KEYRING\_UDF\_KEY\_TOO\_LONG error code, 133  
 ER\_CLIENT\_KEYRING\_UDF\_KEY\_TYPE\_INVALID error code, 133  
 ER\_CLIENT\_KEYRING\_UDF\_KEY\_TYPE\_TOO\_LONG error code, 133  
 ER\_CLIENT\_LOCAL\_FILES\_DISABLED error code, 135  
 ER\_CLIENT\_PRIVILEGE\_CHECKS\_USER\_CANNOT\_BE\_PROMOTED error code, 133  
 ER\_CLIENT\_PRIVILEGE\_CHECKS\_USER\_CORRUPT error code, 133  
 ER\_CLIENT\_PRIVILEGE\_CHECKS\_USER\_DOES\_NOT\_EXIST error code, 133  
 ER\_CLIENT\_PRIVILEGE\_CHECKS\_USER\_NEEDS\_RPL\_APPLICATION error code, 133  
 ER\_CLIENT\_QUERY\_FAILURE\_INVALID\_NON\_ROW\_FORMAT error code, 135  
 ER\_CLONE\_CHARSET error code, 126  
 ER\_CLONE\_CLIENT\_TRACE error code, 547  
 ER\_CLONE\_CONFIG error code, 126  
 ER\_CLONE\_CREATE\_HANDLER\_FAIL\_TRACE error code, 293  
 ER\_CLONE\_DDL\_IN\_PROGRESS error code, 100  
 ER\_CLONE\_DISALLOWED error code, 127  
 ER\_CLONE\_DISK\_SPACE error code, 127  
 ER\_CLONE\_DONOR error code, 126  
 ER\_CLONE\_DONOR\_TRACE error code, 546  
 ER\_CLONE\_DONOR\_VERSION error code, 126  
 ER\_CLONE\_ENCRYPTION error code, 127  
 ER\_CLONE\_HANDLER\_EXISTS error code, 293  
 ER\_CLONE\_HANDLER\_EXIST\_TRACE error code, 293  
 ER\_CLONE\_INFO\_CLIENT error code, 546  
 ER\_CLONE\_INFO\_SERVER error code, 547  
 ER\_CLONE\_IN\_PROGRESS error code, 127  
 ER\_CLONE\_LOOPBACK error code, 127  
 ER\_CLONE\_NETWORK\_PACKET error code, 136  
 ER\_CLONE\_OS error code, 126  
 ER\_CLONE\_PLATFORM error code, 126  
 ER\_CLONE\_PLUGIN\_MATCH error code, 126  
 ER\_CLONE\_PLUGIN\_NOT\_LOADED error code, 292  
 ER\_CLONE\_PLUGIN\_NOT\_LOADED\_TRACE error code, 293  
 ER\_CLONE\_PROTOCOL error code, 126  
 ER\_CLONE\_PROTOCOL\_ERROR error code, 546  
 ER\_CLONE\_PROTOCOL\_TRACE error code, 546  
 ER\_CLONE\_REMOTE\_ERROR error code, 546  
 ER\_CLONE\_SERVER\_TRACE error code, 547  
 ER\_CLONE\_SHUTDOWN\_TRACE error code, 566  
 ER\_CLONE\_SYS\_CONFIG error code, 126  
 ER\_CLONE\_TOO\_MANY\_CONCURRENT\_CLONES error code, 100  
 ER\_CMD\_NEED\_SUPER error code, 99  
 ER\_COALESCE\_ONLY\_ON\_HASH\_PARTITION error code, 38  
 ER\_COALESCE\_PARTITION\_NO\_PARTITION error code, 38  
 ER\_COLLATION\_CHARSET\_MISMATCH error code, 21  
 ER\_COLUMNACCESS\_DENIED\_ERROR error code, 13  
 ER\_COLUMN\_CHANGE\_SIZE error code, 128  
 ER\_COLUMN\_CHECK\_CONSTRAINT\_REFERENCES\_OTHER error code, 120  
 ER\_COLUMN\_DOESNT\_MATCH\_CORRUPTED\_V2 error code, 61  
 ER\_COL\_COUNT\_DOESNT\_MATCH\_PLEASE\_UPDATE error code, 41  
 ER\_COL\_COUNT\_DOESNT\_MATCH\_PLEASE\_UPDATE\_V2 error code, 69  
 ER\_CONNECTION\_BACKEND\_FAILED\_TO\_FETCH\_SECURITY\_CONTEXT error code, 156  
 ER\_CONNECTION\_COMMAND\_SERVICE\_BACKEND\_FAILED error code, 156  
 ER\_COMMENT\_CONTAINS\_INVALID\_STRING error code, 153  
 ER\_COMMIT\_NOT\_ALLOWED\_IN\_SF\_OR\_TRG error code, 32  
 ER\_COMPONENTS\_CANT\_ACQUIRE\_SERVICE\_IMPLEMENTATION error code, 90  
 ER\_COMPONENTS\_CANT\_LOAD error code, 89  
 ER\_COMPONENTS\_CANT\_RELEASE\_SERVICE error code, 90  
 ER\_COMPONENTS\_CANT\_SATISFY\_DEPENDENCY error code, 90  
 ER\_COMPONENTS\_CANT\_UNLOAD error code, 90  
 ER\_COMPONENTS\_FAILED\_TO\_ACQUIRE\_SERVICE\_IMPLEMENTATION error code, 297  
 ER\_COMPONENTS\_INFRASTRUCTURE\_BOOTSTRAP error code, 169  
 ER\_COMPONENTS\_INFRASTRUCTURE\_MANIFEST\_DEINIT error code, 596  
 ER\_COMPONENTS\_INFRASTRUCTURE\_MANIFEST\_INIT error code, 596  
 ER\_COMPONENTS\_INFRASTRUCTURE\_SHUTDOWN error code, 169

---

---

ER_COMPONENTS_LOAD_CANT_INITIALIZE error code, 90	ER_COMPONENT_FILTER_WRONG_VALUE error code, 528
ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE error code, 90	ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY error code, 626
ER_COMPONENTS_NO_SCHEME error code, 89	ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE error code, 626
ER_COMPONENTS_NO_SCHEME_SERVICE error code, 89	ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE error code, 626
ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP error code, 169	ER_COMPONENT_LOCK error code, 638
ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE error code, 90	ER_COMPONENT_MANIPULATE_ROW_FAILED error code, 90
ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE error code, 90	ER_COMPONENT_MASKING_ABI error code, 638
ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP error code, 90	ER_COMPONENT_MASKING_ABI_REASON error code, 638
ER_COMPONENTS_UNLOAD_NOT_LOADED error code, 90	ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE error code, 638
ER_COMPONENT_EE_DATA_DECRYPTION_ERROR error code, 624	ER_COMPONENT_MASKING_OTHER_ERROR error code, 638
ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR error code, 624	ER_COMPONENT_MASKING_RANDOM_CREATE error code, 638
ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE error code, 624	ER_COMPONENT_MASKING_RANDOM_CREATE_REASON error code, 638
ER_COMPONENT_EE_DATA_SIGN_ERROR error code, 624	ER_COMPONENT_SERVICE_CALL error code, 638
ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAILURE error code, 623	ER_COMPONENT_SERVICE_CALL_RESULT error code, 638
ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM error code, 623	ER_COMPONENT_TABLE_INCORRECT error code, 90
ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENTS error code, 623	ER_COMPONENT_UNLOCK error code, 638
ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF_RANGE error code, 623	ER_CONCURRENT_PROCEDURE_USAGE error code, 152
ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION_FAILURE error code, 624	ER_CONDITIONAL_DEBUG error code, 625
ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION_FAILURE error code, 624	ER_COND_ITEM_TOO_LONG error code, 46
ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILURE error code, 623	ER_CONFIG_OPTION_WITHOUT_GROUP error code, 185
ER_COMPONENT_EE_INSUFFICIENT_LENGTH error code, 624	ER_CONNECTION_EXPIRE_BEFORE_THE_FUTURE error code, 174
ER_COMPONENT_EE_OPENSSL_ERROR error code, 624	ER_CONFLICTING_DECLARATIONS error code, 25
ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILURE error code, 623	ER_CONNECTION_PARSE_ERROR error code, 45
ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE error code, 623	ER_CONNECTION_ABORTED error code, 527
ER_COMPONENT_FILTER_CONFUSED error code, 321	ER_CONNECTION_HANDLING_OOM error code, 171
ER_COMPONENT_FILTER_DIAGNOSTICS error code, 107	ER_CONNECTION_METADATA error code, 17
ER_COMPONENT_FILTER_FLABBERGASTED error code, 98	ER_CONNECT_TO_FOREIGN_DATA_SOURCE error code, 33
	ER_CONNECT_TO_MASTER error code, 19
	ER_CONNECT_TO_SOURCE error code, 19
	ER_CONN_ATTR_TRUNCATED error code, 192
	ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED error code, 323
	ER_CONN_CONTROL_ERROR_MSG error code, 320
	ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED error code, 322
	ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY error code, 323
	ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_HAS error code, 323

---

---

ER\_CONN\_CONTROL\_INVALID\_CONN\_DELAY\_TYPE error code, 322  
 ER\_CONN\_CONTROL\_STAT\_CONN\_DELAY\_TRIGGERED error code, 322  
 ER\_CONN\_CONTROL\_STAT\_CONN\_DELAY\_TRIGGERED\_UPDATE\_FAILED error code, 322  
 ER\_CONN\_INIT\_CONNECT\_IGNORED error code, 322  
 ER\_CONN\_INIT\_CONNECT\_IGNORED\_MFA error code, 639  
 ER\_CONN\_LIMIT error code, 612  
 ER\_CONN\_PER\_THREAD\_NO\_THREAD error code, 188  
 ER\_CONN\_PIP\_CANT\_CREATE\_EVENT error code, 188  
 ER\_CONN\_PIP\_CANT\_CREATE\_PIPE error code, 188  
 ER\_CONN\_SHM\_CANT\_CREATE\_CONNECTION error code, 188  
 ER\_CONN\_SHM\_CANT\_CREATE\_SERVICE error code, 188  
 ER\_CONN\_SHM\_LISTENER error code, 188  
 ER\_CONN\_SOCKET\_ACCEPT\_FAILED error code, 192  
 ER\_CONN\_SOCKET\_SELECT\_FAILED error code, 192  
 ER\_CONN\_TCP\_ADDRESS error code, 188  
 ER\_CONN\_TCP\_BIND\_FAIL error code, 190  
 ER\_CONN\_TCP\_BIND\_RETRY error code, 189  
 ER\_CONN\_TCP\_CANT\_RESET\_V6ONLY error code, 189  
 ER\_CONN\_TCP\_CANT\_RESOLVE\_HOSTNAME error code, 189  
 ER\_CONN\_TCP\_CREATED error code, 188  
 ER\_CONN\_TCP\_ERROR\_WITH\_STRERROR error code, 189  
 ER\_CONN\_TCP\_IPV6\_AVAILABLE error code, 189  
 ER\_CONN\_TCP\_IPV6\_UNAVAILABLE error code, 189  
 ER\_CONN\_TCP\_IP\_NOT\_LOGGED error code, 190  
 ER\_CONN\_TCP\_IS\_THERE\_ANOTHER\_USING\_PORT error code, 189  
 ER\_CONN\_TCP\_LISTEN\_FAIL error code, 190  
 ER\_CONN\_TCP\_NO\_SOCKET error code, 188  
 ER\_CONN\_TCP\_RESOLVE\_INFO error code, 190  
 ER\_CONN\_TCP\_START\_FAIL error code, 190  
 ER\_CONN\_TPC\_BIND\_FAIL error code, 190  
 ER\_CONN\_UNIX\_IS\_THERE\_ANOTHER\_USING\_SOCKET error code, 189  
 ER\_CONN\_UNIX\_LISTEN\_FAILED error code, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_CLOSE error code, 192  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_CREATE error code, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_DELETE error code, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_OPEN error code, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_READ error code, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_SYNC error code, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_WRITE error code, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_EMPTY error code, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_FAIL error code, 190  
 ER\_CONN\_UNIX\_LOCK\_FILE\_GIVING\_UP error code, 191  
 ER\_CONN\_UNIX\_LOCK\_FILE\_PIDLESS error code, 191  
 ER\_CONN\_UNIX\_NO\_BIND\_NO\_START error code, 190  
 ER\_CONN\_UNIX\_NO\_FD error code, 190  
 ER\_CONN\_UNIX\_PATH\_TOO\_LONG error code, 190  
 ER\_CONN\_UNIX\_PID\_CLAIMED\_SOCKET\_FILE error code, 189  
 ER\_CONSECUTIVE\_REORG\_PARTITIONS error code, 39  
 ER\_CONSTRAINT\_NOT\_FOUND error code, 134  
 ER\_CONVERT\_MULTI\_VALUE error code, 639  
 ER\_CON\_COUNT\_ERROR error code, 5  
 ER\_CORE\_VALUES error code, 173  
 ER\_CORRUPTED\_JSON\_DIFF error code, 102  
 ER\_CORRUPT\_HELP\_DB error code, 21  
 ER\_COULD\_NOT\_APPLY\_JSON\_DIFF error code, 102  
 ER\_COULD\_NOT\_CREATE\_WINDOWS\_REGISTRY\_KEY error code, 541  
 ER\_COULD\_NOT\_REINITIALIZE\_AUDIT\_LOG\_FILTERS error code, 535  
 ER\_CRASHED\_ON\_REPAIR error code, 17  
 ER\_CRASHED\_ON\_USAGE error code, 16  
 ER\_CREATED\_SYSTEM\_WITH\_VERSION error code, 290  
 ER\_CREATE\_FILEGROUP\_FAILED error code, 39  
 ER\_CREATE\_SELECT\_WITH\_GIPK\_DISALLOWED\_IN\_SBR error code, 156  
 ER\_CREATING\_NEW\_UUID error code, 170  
 ER\_CREATING\_NEW\_UUID\_FIRST\_START error code, 280  
 ER\_CREDENTIALLESS\_AUTO\_USER\_BAD error code, 171  
 ER\_CREDENTIALS\_CONTRADICT\_TO\_HISTORY error code, 100  
 ER\_CTE\_MAX\_RECURSION\_DEPTH error code, 100  
 ER\_CTE\_RECURSIVE\_FORBIDDEN\_JOIN\_ORDER error code, 93  
 ER\_CTE\_RECURSIVE\_FORBIDS\_AGGREGATION error code, 93  
 ER\_CTE\_RECURSIVE\_NOT\_UNION error code, 156  
 ER\_CTE\_RECURSIVE\_REQUIRES\_NONRECURSIVE\_FIRST error code, 93

---

---

ER\_CTE\_RECURSIVE\_REQUIRES\_SINGLE\_REFERENC error code, 94  
 ER\_CTE\_RECURSIVE\_REQUIRES\_UNION error code, 93  
 ER\_CURRENT\_PASSWORD\_CANNOT\_BE\_RETAINED error code, 129  
 ER\_CURRENT\_PASSWORD\_NOT\_REQUIRED error code, 129  
 ER\_CUT\_VALUE\_GROUP\_CONCAT error code, 22  
 ER\_CYCLE\_TIMER\_IS\_NOT\_AVAILABLE error code, 293  
 ER\_DATABASE\_NAME error code, 45  
 ER\_DATA\_DIRECTORY\_UNUSABLE error code, 542  
 ER\_DATA\_DIRECTORY\_UNUSABLE\_DELETABLE error code, 565  
 ER\_DATA\_OUT\_OF\_RANGE error code, 50  
 ER\_DATA\_TOO\_LONG error code, 31  
 ER\_DATETIME\_FUNCTION\_OVERFLOW error code, 34  
 ER\_DA\_AUTH\_ID\_WITH\_SYSTEM\_USER\_PRIV\_IN\_MANTORRY error code, 127  
 ER\_DA\_CANT\_OPEN\_ERROR\_LOG error code, 142  
 ER\_DA\_CONN\_LIMIT error code, 152  
 ER\_DA\_ERROR\_LOG\_COMPONENT\_FLUSH\_FAILED error code, 148  
 ER\_DA\_ERROR\_LOG\_MULTIPLE\_FILTERS error code, 142  
 ER\_DA\_ERROR\_LOG\_TABLE\_DISABLED error code, 142  
 ER\_DA\_EXPIRE\_LOGS\_DAYS\_IGNORED error code, 156  
 ER\_DA\_GLOBAL\_CONN\_LIMIT error code, 152  
 ER\_DA\_GRP\_RPL\_RECOVERY\_ENDPOINT\_FORMAT error code, 138  
 ER\_DA\_GRP\_RPL\_RECOVERY\_ENDPOINT\_INVALID error code, 139  
 ER\_DA\_GRP\_RPL\_STARTED\_AUTO\_REJOIN error code, 131  
 ER\_DA\_INVALID\_CONDITION\_NUMBER error code, 56  
 ER\_DA\_NO\_ERROR\_LOG\_PARSER\_CONFIGURED error code, 142  
 ER\_DA\_OOM error code, 135  
 ER\_DA\_PLUGIN\_INSTALL\_ERROR error code, 128  
 ER\_DA\_RPL\_GTID\_TABLE\_CANNOT\_OPEN error code, 128  
 ER\_DA\_SSL\_FIPS\_MODE\_ERROR error code, 151  
 ER\_DA\_SSL\_LIBRARY\_ERROR error code, 128  
 ER\_DA\_UDF\_INVALID\_ARGUMENT\_TO\_SET\_CHARSET error code, 136  
 ER\_DA\_UDF\_INVALID\_CHARSET error code, 134  
 ER\_DA\_UDF\_INVALID\_CHARSET\_SPECIFIED error code, 134  
 ER\_DA\_UDF\_INVALID\_COLLATION error code, 134  
 ER\_DA\_UDF\_INVALID\_EXTENSION\_ARGUMENT\_TYPE error code, 134  
 ER\_DA\_UDF\_INVALID\_RETURN\_TYPE\_TO\_SET\_CHARSET error code, 136  
 ER\_DA\_UNKNOWN\_ERROR\_NUMBER error code, 128  
 ER\_DBACCESS\_DENIED\_ERROR error code, 6  
 ER\_DEBUG\_CHECK\_SHARES\_DROPPED error code, 222  
 ER\_DEBUG\_CHECK\_SHARES\_INFO error code, 222  
 ER\_DEBUG\_CHECK\_SHARES\_OPEN error code, 222  
 ER\_DB\_ACCESS\_DENIED error code, 127  
 ER\_DB\_CREATE\_EXISTS error code, 4  
 ER\_DB\_DROP\_EXISTS error code, 4  
 ER\_DB\_DROP\_RMDIR error code, 4  
 ER\_DB\_DROP\_RMDIR2 error code, 97  
 ER\_DB\_OPT\_NOT\_FOUND\_USING\_DEFAULT\_CHARSET error code, 260  
 ER\_DDL\_IN\_PROGRESS error code, 100  
 ER\_DDL\_LOG\_ERROR error code, 41  
 ER\_DDL\_LOG\_ERROR error code, 605  
 ER\_DD\_ABORTING\_PARTIAL\_UPGRADE error code, 198  
 ER\_DD\_CACHE\_NOT\_EMPTY\_AT\_SHUTDOWN error code, 165  
 ER\_DD\_CANT\_CREATE\_OBJECT\_KEY error code, 165  
 ER\_DD\_CANT\_CREATE\_SP error code, 259  
 ER\_DD\_CANT\_FETCH\_TABLE\_DATA error code, 259  
 ER\_DD\_CANT\_FIX\_SE\_DATA error code, 259  
 ER\_DD\_CANT\_GET\_OBJECT\_KEY error code, 165  
 ER\_DD\_CANT\_RESOLVE\_VIEW error code, 183  
 ER\_DD\_CREATED\_FOR\_UPGRADE error code, 198  
 ER\_DD\_ERROR\_CREATING\_ENTRY error code, 259  
 ER\_DD\_FAILSAFE error code, 163  
 ER\_DD\_FRM\_EXISTS\_FOR\_TABLE error code, 198  
 ER\_DD\_INITIALIZE error code, 299  
 ER\_DD\_INITIALIZE\_SQL\_ERROR error code, 536  
 ER\_DD\_INIT\_FAILED error code, 164  
 ER\_DD\_INIT\_UPGRADE\_FAILED error code, 164  
 ER\_DD\_METADATA\_NOT\_FOUND error code, 165  
 ER\_DD\_MINOR\_DOWNGRADE error code, 300  
 ER\_DD\_MINOR\_DOWNGRADE\_VERSION\_NOT\_SUPPORTED error code, 300  
 ER\_DD\_NO\_VERSION\_FOUND error code, 300  
 ER\_DD\_NO\_WRITES\_NO\_REPOPULATION error code, 163  
 ER\_DD\_OBJECT\_RELEASER\_REMAINS error code, 165  
 ER\_DD\_OBJECT\_REMAINS error code, 165  
 ER\_DD\_OBJECT\_REMAINS\_IN\_RELEASER error code, 165  
 ER\_DD\_POPULATING\_TABLES\_FAILED error code, 164  
 ER\_DD\_RESTART error code, 299  
 ER\_DD\_SCHEMA\_NOT\_FOUND error code, 197

---

ER\_DD\_SE\_INIT\_FAILED error code, 197  
 ER\_DD\_TABLESPACE\_NOT\_FOUND error code, 182  
 ER\_DD\_TABLE\_NOT\_FOUND error code, 197  
 ER\_DD\_TRG\_CANT\_ADD error code, 183  
 ER\_DD\_TRG\_CONNECTION\_COLLATION\_MISSING error code, 182  
 ER\_DD\_TRG\_DB\_COLLATION\_MISSING error code, 183  
 ER\_DD\_TRG\_DEFINER\_OOM error code, 183  
 ER\_DD\_TRG\_FILE\_UNREADABLE error code, 183  
 ER\_DD\_UPDATE\_DATADIR\_FLAG\_FAIL error code, 642  
 ER\_DD\_UPDATING\_PLUGIN\_MD\_FAILED error code, 164  
 ER\_DD\_UPGRADE error code, 299  
 ER\_DD\_UPGRADE\_COMPLETED error code, 562  
 ER\_DD\_UPGRADE\_DD\_OPEN\_FAILED error code, 288  
 ER\_DD\_UPGRADE\_DD\_POPULATED error code, 288  
 ER\_DD\_UPGRADE\_FAILED\_FIND\_VALID\_DATA\_DIR error code, 289  
 ER\_DD\_UPGRADE\_FAILED\_INIT\_DD\_SE error code, 290  
 ER\_DD\_UPGRADE\_FAILED\_TO\_ACQUIRE\_TABLESPACE error code, 288  
 ER\_DD\_UPGRADE\_FAILED\_TO\_CREATE\_INDEX\_STATS error code, 289  
 ER\_DD\_UPGRADE\_FAILED\_TO\_CREATE\_TABLE\_STATS error code, 289  
 ER\_DD\_UPGRADE\_FAILED\_TO\_FETCH\_TABLES error code, 288  
 ER\_DD\_UPGRADE\_FAILED\_TO\_FETCH\_TABLESPACES error code, 288  
 ER\_DD\_UPGRADE\_FAILED\_TO\_RESOLVE\_TABLESPACE error code, 288  
 ER\_DD\_UPGRADE\_FAILED\_TO\_UPDATE\_VER\_NO\_IN\_TABLESPACE error code, 299  
 ER\_DD\_UPGRADE\_FOUND\_PARTIALLY\_UPGRADED\_DATABASE error code, 290  
 ER\_DD\_UPGRADE\_FOUND\_PARTIALLY\_UPGRADED\_DATABASES error code, 290  
 ER\_DD\_UPGRADE\_FOUND\_PREPARED\_XA\_TRANSACTION error code, 575  
 ER\_DD\_UPGRADE\_INDEX\_STATS\_MIGRATE\_COMPLETED error code, 289  
 ER\_DD\_UPGRADE\_INFO\_FILE\_CLOSE\_FAILED error code, 289  
 ER\_DD\_UPGRADE\_INFO\_FILE\_OPEN\_FAILED error code, 289  
 ER\_DD\_UPGRADE\_OFF error code, 299  
 ER\_DD\_UPGRADE\_RENAME\_IDX\_STATS\_FILE\_FAILED error code, 288  
 ER\_DD\_UPGRADE\_SCHEMA\_UNAVAILABLE error code, 300  
 ER\_DD\_UPGRADE\_SDI\_INFO\_UPDATE\_FAILED error code, 290  
 ER\_DD\_UPGRADE\_SE\_LOGS\_FAILED error code, 290  
 ER\_DD\_UPGRADE\_START error code, 290  
 ER\_DD\_UPGRADE\_TABLESPACE\_MIGRATION\_FAILED error code, 289  
 ER\_DD\_UPGRADE\_TABLE\_INTACT\_ERROR error code, 296  
 ER\_DD\_UPGRADE\_TABLE\_STATS\_MIGRATE\_COMPLETED error code, 289  
 ER\_DD\_UPGRADE\_VERSION\_NOT\_SUPPORTED error code, 299  
 ER\_DD\_UPGRADE\_VIEW\_COLUMN\_NAME\_TOO\_LONG error code, 298  
 ER\_DD\_VERSION\_FOUND error code, 163  
 ER\_DD\_VERSION\_INSTALLED error code, 163  
 ER\_DD\_VERSION\_UNSUPPORTED error code, 163  
 ER\_DD\_VIEW\_CANT\_ALLOC\_CHARSET error code, 164  
 ER\_DD\_VIEW\_CANT\_CREATE error code, 165  
 ER\_DD\_VIEW\_WITHOUT\_DEFINER error code, 183  
 ER\_DEBUG\_SYNC\_EXECUTED error code, 166  
 ER\_DEBUG\_SYNC\_HIT error code, 166  
 ER\_DEBUG\_SYNC\_HIT\_LIMIT error code, 46  
 ER\_DEBUG\_SYNC\_OOM error code, 166  
 ER\_DEBUG\_SYNC\_THREAD\_MAX error code, 166  
 ER\_DEBUG\_SYNC\_TIMEOUT error code, 46  
 ER\_DEFAULT\_AS\_VAL\_GENERATED error code, 115  
 ER\_DEFAULT\_SE\_UNAVAILABLE error code, 182  
 ER\_DEFAULT\_VAL\_GENERATED\_FUNCTION\_IS\_NOT\_ALLOWED error code, 115  
 ER\_DEFAULT\_VAL\_GENERATED\_NAMED\_FUNCTION\_IS\_NOT\_ALLOWED error code, 115  
 ER\_DEFAULT\_VAL\_GENERATED\_NON\_PRIOR error code, 115  
 ER\_DEFAULT\_VAL\_GENERATED\_REF\_AUTO\_INCREMENT error code, 115  
 ER\_DEFAULT\_VAL\_GENERATED\_ROW\_VALUE error code, 115  
 ER\_DEFAULT\_VAL\_GENERATED\_VARIABLES error code, 115  
 ER\_DEFINITION\_CONTAINS\_INVALID\_STRING error code, 153  
 ER\_DEPART\_WITH\_GRACE error code, 169  
 ER\_DEPENDENT\_BY\_CHECK\_CONSTRAINT error code, 137  
 ER\_DEPENDENT\_BY\_DEFAULT\_GENERATED\_VALUE error code, 115  
 ER\_DEPENDENT\_BY\_FUNCTIONAL\_INDEX error code, 123  
 ER\_DEPENDENT\_BY\_GENERATED\_COLUMN error code, 79  
 ER\_DEPENDENT\_BY\_PARTITION\_FUNC error code, 125

---

---

ER\_DEPRECATED\_NATIONAL error code, 109  
ER\_DEPRECATED\_PERSISTED\_VARIABLE\_WITH\_ALIAS error code, 604  
ER\_DEPRECATED\_SYNTAX\_NO\_REPLACEMENT error code, 297  
ER\_DEPRECATED\_SYNTAX\_WITH\_REPLACEMENT error code, 297  
ER\_DEPRECATED\_TIMESTAMP\_IMPLICIT\_DEFAULTS error code, 171  
ER\_DEPRECATED\_TLS\_VERSION\_SESSION error code, 601  
ER\_DEPRECATED\_UTF8\_ALIAS error code, 109  
ER\_DEPRECATED\_MSG\_NO\_REPLACEMENT error code, 297  
ER\_DEPRECATED\_MSG\_WITH\_REPLACEMENT error code, 278  
ER\_DERIVED\_MUST\_HAVE\_ALIAS error code, 21  
ER\_DES\_FILE\_WRONG\_KEY error code, 184  
ER\_DETACHED\_SESSIONS\_LEFT\_BY\_PLUGIN error code, 216  
ER\_DETACHING\_SESSION\_LEFT\_BY\_PLUGIN error code, 216  
ER\_DIMENSION\_UNSUPPORTED error code, 75  
ER\_DISABLED\_STORAGE\_ENGINE error code, 83  
ER\_DISABLED\_STORAGE\_ENGINE\_AS\_DEFAULT error code, 166  
ER\_DISABLE\_AUTO\_POSITION\_REQUIRES\_ASYNC\_RECONNECTION error code, 141  
ER\_DISABLE\_GTID\_MODE\_REQUIRES\_ASYNC\_RECONNECTION error code, 141  
ER\_DISALLOWED\_OPERATION error code, 102  
ER\_DISCARD\_FK\_CHECKS\_RUNNING error code, 61  
ER\_DISCONNECTING\_REMAINING\_CLIENTS error code, 175  
ER\_DISK\_FULL\_NOWAIT error code, 104  
ER\_DIVISION\_BY\_ZERO error code, 29  
ER\_DONT\_SUPPORT\_REPLICA\_PRESERVE\_COMMIT\_ORDER error code, 71  
ER\_DONT\_SUPPORT\_SLAVE\_PRESERVE\_COMMIT\_ORDER error code, 71  
ER\_DROP\_DATABASE\_FAILED\_RMDIR\_MANUALLY error code, 298  
ER\_DROP\_FILEGROUP\_FAILED error code, 39  
ER\_DROP\_INDEX\_FK error code, 40  
ER\_DROP\_LAST\_PARTITION error code, 38  
ER\_DROP\_PARTITION\_NON\_EXISTENT error code, 38  
ER\_DROP\_PK\_COLUMN\_TO\_DROP\_GIPK error code, 156  
ER\_DUPLICATED\_VALUE\_IN\_TYPE error code, 24  
ER\_DUPLICATE\_OPTION\_KEY error code, 92  
ER\_DUPLICATE\_SYS\_VAR error code, 537  
ER\_DUPLICATE\_TABLE\_LOCK error code, 93  
ER\_DUP\_ARGUMENT error code, 19  
ER\_DUP\_ENTRY error code, 7  
ER\_DUP\_ENTRY\_AUTOINCREMENT\_CASE error code, 41  
ER\_DUP\_ENTRY\_WITH\_KEY\_NAME error code, 42  
ER\_DUP\_FD\_OPEN\_FAILED error code, 281  
ER\_DUP\_FIELDNAME error code, 7  
ER\_DUP\_INDEX error code, 62  
ER\_DUP\_KEY error code, 4  
ER\_DUP\_KEYNAME error code, 7  
ER\_DUP\_LIST\_ENTRY error code, 71  
ER\_DUP\_SIGNAL\_SET error code, 46  
ER\_DUP\_UNIQUE error code, 15  
ER\_DUP\_UNKNOWN\_IN\_INDEX error code, 65  
ER\_EMPTY\_PIPELINE\_FOR\_ERROR\_LOG\_SERVICE error code, 107  
ER\_EMPTY\_PRIVILEGE\_NAME\_IGNORED error code, 590  
ER\_EMPTY\_QUERY error code, 8  
ER\_ENDING\_INIT error code, 535  
ER\_END\_INITFILE error code, 177  
ER\_ENFORCE\_GTID\_CONSISTENCY\_WARN\_WITH\_ONGOING\_G error code, 80  
ER\_ENGINE\_ATTRIBUTE\_NOT\_SUPPORTED error code, 139  
ER\_ENGINE\_CANT\_DROP\_MISSING\_TABLE error code, 97  
ER\_ENGINE\_CANT\_DROP\_TABLE error code, 97  
ER\_ENGINE\_CONNECT\_HOST\_FAILED\_TO\_READ error code, 212  
ER\_ENGINE\_COST\_INVALID\_CONST\_CONSTANT\_FOR\_SE\_AND error code, 212  
ER\_ENGINE\_COST\_INVALID\_DEVICE\_TYPE\_FOR\_SE error code, 212  
ER\_ENGINE\_COST\_UNKNOWN\_COST\_CONSTANT error code, 212  
ER\_ENGINE\_COST\_UNKNOWN\_STORAGE\_ENGINE error code, 212  
ER\_ENGINE\_OUT\_OF\_MEMORY error code, 69  
ER\_ERRMSG\_CANT\_FIND\_FILE error code, 198  
ER\_ERRMSG\_CANT\_READ error code, 198  
ER\_ERRMSG\_LOADING\_55\_STYLE error code, 198  
ER\_ERRMSG\_MISSING\_IN\_FILE error code, 198  
ER\_ERRMSG\_OOM error code, 198  
ER\_ERRMSG\_REPLACEMENTS\_FAILED error code, 274  
ER\_ERRMSG\_REPLACEMENT\_DODGY error code, 274  
ER\_ERROR\_DURING\_COMMIT error code, 15  
ER\_ERROR\_DURING\_FLUSH\_LOGS error code, 16  
ER\_ERROR\_DURING\_FLUSH\_LOG\_COMMIT\_PHASE error code, 298  
ER\_ERROR\_DURING\_OPTIMIZE\_TABLE error code, 258  
ER\_ERROR\_DURING\_ROLLBACK error code, 15  
ER\_ERROR\_ENABLING\_KEYS error code, 258



---

ER\_ERROR\_INFO\_FROM\_DA error code, 532  
 ER\_ERROR\_IN\_TRIGGER\_BODY error code, 52  
 ER\_ERROR\_IN\_UNKNOWN\_TRIGGER\_BODY error code, 52  
 ER\_ERROR\_LOG\_DESTINATION\_NOT\_A\_FILE error code, 591  
 ER\_ERROR\_ON\_MASTER error code, 68  
 ER\_ERROR\_ON\_MODIFYING\_GTID\_EXECUTED\_TABLE error code, 84  
 ER\_ERROR\_ON\_READ error code, 4  
 ER\_ERROR\_ON\_RENAME error code, 5  
 ER\_ERROR\_ON\_SOURCE error code, 68  
 ER\_ERROR\_ON\_WRITE error code, 5  
 ER\_ERROR\_WHEN\_EXECUTING\_COMMAND error code, 19  
 ER\_EVENT\_ALREADY\_EXISTS error code, 40  
 ER\_EVENT\_CANNOT\_ALTER\_IN\_THE\_PAST error code, 42  
 ER\_EVENT\_CANNOT\_CREATE\_IN\_THE\_PAST error code, 42  
 ER\_EVENT\_CANT\_FIND\_TIMEZONE error code, 260  
 ER\_EVENT\_CANT\_GET\_CHARSET error code, 260  
 ER\_EVENT\_CANT\_GET\_COLLATION error code, 261  
 ER\_EVENT\_CANT\_GET\_LOCK\_FOR\_DROPPING\_EVENT error code, 264  
 ER\_EVENT\_CANT\_GET\_TIMEZONE\_FROM\_FIELD error code, 260  
 ER\_EVENT\_CANT\_INIT\_QUEUE error code, 167  
 ER\_EVENT\_CANT\_OPEN\_TABLE\_MYSQL\_EVENT error code, 261  
 ER\_EVENT\_DOES\_NOT\_EXIST error code, 40  
 ER\_EVENT\_DROPPING error code, 214  
 ER\_EVENT\_ENDS\_BEFORE\_STARTS error code, 40  
 ER\_EVENT\_ERROR\_CREATING\_QUERY\_TO\_WRITE\_TO\_BINLOG error code, 264  
 ER\_EVENT\_ERROR\_DURING\_COMPILATION error code, 214  
 ER\_EVENT\_EXECUTION\_FAILED error code, 167  
 ER\_EVENT\_EXECUTION\_FAILED\_CANT\_AUTHENTICATE error code, 213  
 ER\_EVENT\_EXECUTION\_FAILED\_USER\_LOST\_EVEN\_PRIVILEGE error code, 213  
 ER\_EVENT\_EXEC\_TIME\_IN\_THE\_PAST error code, 40  
 ER\_EVENT\_INTERVAL\_NOT\_POSITIVE\_OR\_TOO\_BIG error code, 40  
 ER\_EVENT\_INVALID\_CREATION\_CTX error code, 43  
 ER\_EVENT\_LAST\_EXECUTION error code, 167  
 ER\_EVENT\_MESSAGE\_STACK error code, 167  
 ER\_EVENT\_PURGING\_QUEUE error code, 167  
 ER\_EVENT\_RECURSION\_FORBIDDEN error code, 42  
 ER\_EVENT\_SAME\_NAME error code, 40  
 ER\_EVENT\_SCHEDULER\_ERROR\_GETTING\_EVENT\_OBJECT error code, 264  
 ER\_EVENT\_SCHEDULER\_ERROR\_LOADING\_FROM\_DB error code, 264  
 ER\_EVENT\_SCHEDULER\_GOT\_BAD\_DATA\_FROM\_TABLE error code, 264  
 ER\_EVENT\_SET\_VAR\_ERROR error code, 41  
 ER\_EVENT\_UNABLE\_TO\_DROP\_EVENT error code, 264  
 ER\_EXCEEDED\_MV\_KEYS\_NUM error code, 130  
 ER\_EXCEEDED\_MV\_KEYS\_SPACE error code, 130  
 ER\_EXCEPTIONS\_WRITE\_ERROR error code, 45  
 ER\_EXCESS\_ARGUMENTS error code, 177  
 ER\_EXPIRE\_LOGS\_DAYS\_IGNORED error code, 298  
 ER\_EXPLAIN\_NOT\_SUPPORTED error code, 69  
 ER\_FAILED\_DEFAULT\_ROLES error code, 89  
 ER\_FAILED\_GET\_DD\_PROPERTY error code, 640  
 ER\_FAILED\_READ\_FROM\_PAR\_FILE error code, 50  
 ER\_FAILED\_REVOKE\_ROLE error code, 89  
 ER\_FAILED\_ROLE\_GRANT error code, 89  
 ER\_FAILED\_SET\_DD\_PROPERTY error code, 640  
 ER\_FAILED\_START\_MYSQLD\_DAEMON error code, 281  
 ER\_FAILED\_TO\_ACQUIRE\_LOCK\_ON\_RESOURCE\_GROUP error code, 286  
 ER\_FAILED\_TO\_ADD\_RESOURCE\_GROUP\_TO\_MAP error code, 285  
 ER\_FAILED\_TO\_ADD\_RPL\_FILTER error code, 292  
 ER\_FAILED\_TO\_ALLOCATE\_MEMORY\_FOR\_RESOURCE\_GROUP error code, 285  
 ER\_FAILED\_TO\_ALLOCATE\_MEMORY\_FOR\_RESOURCE\_GROUP error code, 285  
 ER\_FAILED\_TO\_ALLOCATE\_SSL\_BIO error code, 536  
 ER\_FAILED\_TO\_APPLY\_RESOURCE\_GROUP\_CONTROLLER error code, 286  
 ER\_FAILED\_TO\_BINLOG\_DROP\_EVENT error code, 291  
 ER\_FAILED\_TO\_BUILD\_DO\_AND\_IGNORE\_TABLE\_HASHES error code, 292  
 ER\_FAILED\_TO\_COMPRESS\_GTID\_EXECUTED\_TABLE error code, 204  
 ER\_FAILED\_TO\_COMPRESS\_GTID\_EXECUTED\_TABLE\_OOM error code, 204  
 ER\_FAILED\_TO\_CONSTRUCT\_DROP\_EVENT\_QUERY error code, 291  
 ER\_FAILED\_TO\_CREATE\_CLONE\_HANDLER error code, 293  
 ER\_FAILED\_TO\_CREATE\_GTID\_TABLE\_COMPRESSION\_THRESHOLD error code, 204  
 ER\_FAILED\_TO\_CREATE\_SDI\_FOR\_TABLESPACE error code, 288  
 ER\_FAILED\_TO\_DECREMENT\_NUMBER\_OF\_THREADS error code, 216  
 ER\_FAILED\_TO\_DELETE\_FROM\_GTID\_EXECUTED\_TABLE error code, 204

---

---

ER\_FAILED\_TO\_DESERIALIZE\_RESOURCE\_GROUP error code, 285  
 ER\_FAILED\_TO\_DETERMINE\_IF\_ROLE\_IS\_MANDATORY error code, 135  
 ER\_FAILED\_TO\_FETCH\_MANDATORY\_ROLE\_LIST error code, 135  
 ER\_FAILED\_TO\_FIND\_COLLATION\_NAME error code, 280  
 ER\_FAILED\_TO\_FIND\_DL\_ENTRY error code, 276  
 ER\_FAILED\_TO\_FIND\_LOCALE\_NAME error code, 280  
 ER\_FAILED\_TO\_FIND\_MYSQLD\_STATUS error code, 296  
 ER\_FAILED\_TO\_GENERATE\_UNIQUE\_LOGFILE error code, 277  
 ER\_FAILED\_TO\_GET\_ABSOLUTE\_PATH error code, 280  
 ER\_FAILED\_TO\_HANDLE\_DEFAULTS\_FILE error code, 537  
 ER\_FAILED\_TO\_INIT\_SYS\_VAR error code, 537  
 ER\_FAILED\_TO\_INIT\_THREAD\_ATTR\_FOR\_GTID\_TABLE error code, 204  
 ER\_FAILED\_TO\_JOIN\_GTID\_TABLE\_COMPRESSION\_THREAD error code, 205  
 ER\_FAILED\_TO\_LOCK\_MEM error code, 176  
 ER\_FAILED\_TO\_OPEN\_COST\_CONSTANT\_TABLES error code, 213  
 ER\_FAILED\_TO\_OPEN\_SHARED\_LIBRARY error code, 276  
 ER\_FAILED\_TO\_PERSIST\_RESOURCE\_GROUP\_METADATA error code, 285  
 ER\_FAILED\_TO\_READ\_FILE error code, 277  
 ER\_FAILED\_TO\_REMOVE\_TEMP\_TABLE error code, 255  
 ER\_FAILED\_TO\_REPAIR\_TABLE error code, 254  
 ER\_FAILED\_TO\_SET\_PERSISTED\_OPTIONS error code, 297  
 ER\_FAILED\_TO\_START\_REPLICA\_THREAD error code, 291  
 ER\_FAILED\_TO\_START\_SLAVE\_THREAD error code, 291  
 ER\_FAILED\_TO\_STORE\_SDI\_FOR\_TABLESPACE error code, 288  
 ER\_FAILED\_TO\_UPDATE\_RESOURCE\_GROUP error code, 285  
 ER\_FAILED\_TO\_WRITE\_TO\_FILE error code, 277  
 ER\_FAIL\_CHROOT error code, 176  
 ER\_FAIL\_SETGID error code, 175  
 ER\_FAIL\_SETREGID error code, 176  
 ER\_FAIL\_SETREUID error code, 176  
 ER\_FAIL\_SETUID error code, 175  
 ER\_FEATURE\_DISABLED error code, 24  
 ER\_FEATURE\_DISABLED\_SEE\_DOC error code, 84  
 ER\_FEATURE\_NOT\_AVAILABLE error code, 79  
 ER\_FEATURE\_UNSUPPORTED error code, 103  
 ER\_FIELD\_IN\_GROUPING\_NOT\_GROUP\_BY error code, 96  
 ER\_FIELD\_IN\_ORDER\_NOT\_SELECT error code, 74  
 ER\_FIELD\_NOT\_FOUND\_PART\_ERROR error code, 37  
 ER\_FIELD\_SPECIFIED\_TWICE error code, 11  
 ER\_FIELD\_TYPE\_NOT\_ALLOWED\_AS\_PARTITION\_FIELD error code, 47  
 ER\_FILEGROUP\_OPTION\_ONLY\_ONCE error code, 39  
 ER\_FILESORT\_TERMINATED error code, 279  
 ER\_FILE\_CORRUPT error code, 68  
 ER\_FILE\_EXISTS\_DURING\_UPGRADE error code, 261  
 ER\_FILE\_EXISTS\_ERROR error code, 9  
 ER\_FILE\_HAS\_OLD\_FORMAT error code, 278  
 ER\_FILE\_NOT\_FOUND error code, 4  
 ER\_FILE\_PRIVILEGE\_FOR\_REPLICATION\_CHECKS error code, 571  
 ER\_FILE\_TYPE\_UNKNOWN error code, 199  
 ER\_FILE\_USED error code, 5  
 ER\_FILSORT\_ABORT error code, 5  
 ER\_INACCESSIBLE\_ERROR error code, 313  
 ER\_INACCESSIBLE\_TABLE error code, 313  
 ER\_INCOMPATIBLE\_TRANSACTION\_ACCESS\_DENIED error code, 313  
 ER\_FIREWALL\_DEPRECATED\_USER\_PROFILE error code, 601  
 ER\_FIREWALL\_FAILED\_TO\_READ\_FIREWALL\_TABLES error code, 312  
 ER\_FIREWALL\_FAILED\_TO\_REG\_DYNAMIC\_PRIVILEGES error code, 312  
 ER\_FIREWALL\_PFS\_TABLE\_REGISTER\_FAILED error code, 596  
 ER\_FIREWALL\_RECORDING\_STMT\_WAS\_TRUNCATED error code, 312  
 ER\_FIREWALL\_RECORDING\_STMT\_WITHOUT\_TEXT error code, 313  
 ER\_FIREWALL\_RELOADING\_CACHE error code, 313  
 ER\_FIREWALL\_RESET\_FOR\_USER error code, 313  
 ER\_FIREWALL\_SERVICES\_NOT\_ACQUIRED error code, 595  
 ER\_FIREWALL\_SKIPPED\_UNKNOWN\_USER\_MODE error code, 313  
 ER\_FIREWALL\_STATUS\_FLUSHED error code, 313  
 ER\_FIREWALL\_SUSPICIOUS\_STMT error code, 313  
 ER\_FIREWALL\_UDF\_REGISTER\_FAILED error code, 596  
 ER\_FIXING\_CLIENT\_CHARSET error code, 176  
 ER\_FK\_CANNOT\_CHANGE\_ENGINE error code, 116  
 ER\_FK\_CANNOT\_DROP\_PARENT error code, 110  
 ER\_FK\_CANNOT\_OPEN\_PARENT error code, 62  
 ER\_FK\_CANNOT\_USE\_VIRTUAL\_COLUMN error code, 111  
 ER\_FK\_COLUMN\_CANNOT\_CHANGE error code, 63  
 ER\_FK\_COLUMN\_CANNOT\_CHANGE\_CHILD error code, 63  
 ER\_FK\_COLUMN\_CANNOT\_DROP error code, 62  
 ER\_FK\_COLUMN\_CANNOT\_DROP\_CHILD error code, 62

---

ER\_FK\_COLUMN\_NOT\_NULL error code, 62  
 ER\_FK\_DEPTH\_EXCEEDED error code, 69  
 ER\_FK\_DUP\_NAME error code, 62  
 ER\_FK\_FAIL\_ADD\_SYSTEM error code, 62  
 ER\_FK\_INCOMPATIBLE\_COLUMNS error code, 116  
 ER\_FK\_INCORRECT\_OPTION error code, 62  
 ER\_FK\_NO\_COLUMN\_PARENT error code, 111  
 ER\_FK\_NO\_INDEX\_CHILD error code, 62  
 ER\_FK\_NO\_INDEX\_PARENT error code, 62  
 ER\_FORBID\_SCHEMA\_CHANGE error code, 34  
 ER\_FORCE\_CLOSE\_THREAD error code, 277  
 ER\_FORCING\_CLOSE error code, 8  
 ER\_FOREIGN\_DATA\_SOURCE\_DOESNT\_EXIST error code, 33  
 ER\_FOREIGN\_DATA\_STRING\_INVALID error code, 33  
 ER\_FOREIGN\_DATA\_STRING\_INVALID\_CANT\_CREATE error code, 33  
 ER\_FOREIGN\_DUPLICATE\_KEY\_OLD\_UNUSED error code, 40  
 ER\_FOREIGN\_DUPLICATE\_KEY\_WITHOUT\_CHILD\_INFO error code, 56  
 ER\_FOREIGN\_DUPLICATE\_KEY\_WITH\_CHILD\_INFO error code, 56  
 ER\_FOREIGN\_KEY\_ON\_PARTITIONED error code, 38  
 ER\_FOREIGN\_KEY\_WITH\_ATOMIC\_CREATE\_SELECT error code, 139  
 ER\_FOREIGN\_SERVER\_DOESNT\_EXIST error code, 36  
 ER\_FOREIGN\_SERVER\_EXISTS error code, 36  
 ER\_FOUND\_MISSING\_GTIDS error code, 387  
 ER\_FOUND\_ROWS\_WHILE\_REPAIRING error code, 258  
 ER\_FPARSER\_BAD\_HEADER error code, 28  
 ER\_FPARSER\_EOF\_IN\_COMMENT error code, 28  
 ER\_FPARSER\_EOF\_IN\_UNKNOWN\_PARAMETER error code, 28  
 ER\_FPARSER\_ERROR\_IN\_PARAMETER error code, 28  
 ER\_FPARSER\_TOO\_BIG\_FILE error code, 28  
 ER\_FSEEK\_FAIL error code, 30  
 ER\_FT\_BOOL\_SYNTAX\_INVALID error code, 171  
 ER\_FT\_MATCHING\_KEY\_NOT\_FOUND error code, 16  
 ER\_FULLTEXT\_FUNCTIONAL\_INDEX error code, 114  
 ER\_FULLTEXT\_NOT\_SUPPORTED\_WITH\_PARTITIONING error code, 56  
 ER\_FULLTEXT\_WITH\_ROLLUP error code, 152  
 ER\_FUNCTIONAL\_INDEX\_DATA\_IS\_TOO\_LONG error code, 130  
 ER\_FUNCTIONAL\_INDEX\_FUNCTION\_IS\_NOT\_ALLOWED error code, 114  
 ER\_FUNCTIONAL\_INDEX\_ON\_FIELD error code, 114  
 ER\_FUNCTIONAL\_INDEX\_ON\_JSON\_OR\_GEOMETRY\_FUNCTION error code, 113  
 ER\_FUNCTIONAL\_INDEX\_ON\_LOB error code, 114  
 ER\_FUNCTIONAL\_INDEX\_PRIMARY\_KEY error code, 113  
 ER\_FUNCTIONAL\_INDEX\_REF\_AUTO\_INCREMENT error code, 113  
 ER\_FUNCTIONAL\_INDEX\_ROW\_VALUE\_IS\_NOT\_ALLOWED error code, 118  
 ER\_FUNCTION\_DOES\_NOT\_SUPPORT\_CHARACTER\_SET error code, 140  
 ER\_FUNCTION\_NOT\_DEFINED error code, 12  
 ER\_FUNC\_INEXISTENT\_NAME\_COLLISION error code, 45  
 ER\_FUTURE\_DATE error code, 174  
 ER\_GENERATED\_COLUMN\_FUNCTION\_IS\_NOT\_ALLOWED error code, 78  
 ER\_GENERATED\_COLUMN\_NAMED\_FUNCTION\_IS\_NOT\_ALLOWED error code, 114  
 ER\_GENERATED\_COLUMN\_NON\_PRIOR error code, 79  
 ER\_GENERATED\_COLUMN\_REF\_AUTO\_INC error code, 79  
 ER\_GENERATED\_COLUMN\_ROW\_VALUE error code, 114  
 ER\_GENERATED\_COLUMN\_VARIABLES error code, 114  
 ER\_GEOMETRY\_IN\_UNKNOWN\_LENGTH\_UNIT error code, 128  
 ER\_GEOMETRY\_PARAM\_LATITUDE\_OUT\_OF\_RANGE error code, 111  
 ER\_GEOMETRY\_PARAM\_LONGITUDE\_OUT\_OF\_RANGE error code, 111  
 ER\_GET\_ERRMSG error code, 25  
 ER\_GET\_ERRNO error code, 5  
 ER\_GET\_ERRNO\_FROM\_STORAGE\_ENGINE error code, 279  
 ER\_GET\_STACKED\_DATA\_WITHOUT\_ACTIVE\_HANDLER error code, 69  
 ER\_GET\_TEMPORARY\_ERRMSG error code, 25  
 ER\_GIPK\_COLUMN ALTER NOT ALLOWED error code, 156  
 ER\_GIPK\_COLUMN\_EXISTS error code, 155  
 ER\_GIPK\_FAILED\_AUTOINC\_COLUMN\_EXISTS error code, 155  
 ER\_GIS\_DATA\_WRONG\_ENDIANESS error code, 73  
 ER\_GIS\_DIFFERENT\_SRIDS error code, 72  
 ER\_GIS\_DIFFERENT\_SRIDS\_AGGREGATION error code, 146  
 ER\_GIS\_INVALID\_DATA error code, 72  
 ER\_GIS\_MAX\_POINTS\_IN\_GEOMETRY\_OVERFLOWED error code, 81  
 ER\_GIS\_UNKNOWN\_ERROR error code, 72  
 ER\_GIS\_UNKNOWN\_EXCEPTION error code, 72  
 ER\_GIS\_UNSUPPORTED\_ARGUMENT error code, 72  
 ER\_GLOBAL\_CONN\_LIMIT error code, 612  
 ER\_GLOBAL\_VARIABLE error code, 20

---

---

ER\_GLOBSTAT\_CHANGE\_DURING\_QUERY error code, 131  
 ER\_GNO\_EXHAUSTED error code, 57  
 ER\_GRANT\_WRONG\_HOST\_OR\_USER error code, 13  
 ER\_GROUPING\_ON\_TIMESTAMP\_IN\_DST error code, 131  
 ER\_GROUP\_REPLICATION\_APPLIER\_INIT\_ERROR error code, 78  
 ER\_GROUP\_REPLICATION\_COMMAND\_FAILURE error code, 103  
 ER\_GROUP\_REPLICATION\_COMMUNICATION\_LAYER\_ERROR error code, 78  
 ER\_GROUP\_REPLICATION\_COMMUNICATION\_LAYER\_SESSION\_ERROR error code, 78  
 ER\_GROUP\_REPLICATION\_CONFIGURATION error code, 78  
 ER\_GROUP\_REPLICATION\_FORCE\_MEMBERS\_COMMAND\_FAILURE error code, 157  
 ER\_GROUP\_REPLICATION\_MAX\_GROUP\_SIZE error code, 86  
 ER\_GROUP\_REPLICATION\_PASSWORD\_LENGTH error code, 138  
 ER\_GROUP\_REPLICATION\_PLUGIN\_NOT\_INSTALLED error code, 204  
 ER\_GROUP\_REPLICATION\_RUNNING error code, 78  
 ER\_GROUP\_REPLICATION\_STOP\_APPLIER\_THREAD\_TIMEOUT error code, 78  
 ER\_GROUP\_REPLICATION\_USER\_EMPTY\_MSG error code, 138  
 ER\_GROUP\_REPLICATION\_USER\_MANDATORY\_MSG error code, 138  
 ER\_GRP\_DELAYED\_VCLE\_LOGGING error code, 561  
 ER\_GRP\_OPERATION\_NOT\_ALLOWED\_GRP\_MUST\_STOP error code, 137  
 ER\_GRP\_RPL\_ABORTS\_AS\_SSL\_NOT\_SUPPORTED\_BY\_MYSQL error code, 370  
 ER\_GRP\_RPL\_ADD\_GRP\_SID\_TO\_GRP\_GTIDS\_MAP\_ERROR error code, 344  
 ER\_GRP\_RPL\_ADD\_GTID\_INFO\_WITHOUT\_LOCAL\_GTID\_INFO error code, 356  
 ER\_GRP\_RPL\_ADD\_GTID\_INFO\_WITHOUT\_REMOTE\_GTID\_INFO error code, 356  
 ER\_GRP\_RPL\_ADD\_GTID\_INFO\_WITH\_LOCAL\_GTID\_INFO\_FAILED error code, 355  
 ER\_GRP\_RPL\_ADD\_GTID\_INFO\_WITH\_REMOTE\_GTID\_INFO\_FAILED error code, 355  
 ER\_GRP\_RPL\_ADD\_GTID\_TO\_GRP\_GTID\_EXECUTED\_ERROR error code, 344  
 ER\_GRP\_RPL\_ADD\_RETRIEVED\_SET\_TO\_GRP\_GTID\_EXECUTED\_ERROR error code, 344  
 ER\_GRP\_RPL\_ADD\_VIEW\_CHANGE\_UUID\_TO\_GRP\_SID\_MAP\_ERROR error code, 603  
 ER\_GRP\_RPL\_ALL\_DONORS\_LEFT\_ABORT\_RECOVERY error code, 358  
 ER\_GRP\_RPL\_ALL\_OBSERVERS\_UNREGISTERED error code, 369  
 ER\_GRP\_RPL\_APPENDING\_DATA\_TO\_INTERNAL\_CACHE\_FAILED error code, 362  
 ER\_GRP\_RPL\_APPLIER\_CHANNEL\_STILL\_RUNNING error code, 595  
 ER\_GRP\_RPL\_APPLIER\_EXECUTION\_FATAL\_ERROR error code, 343  
 ER\_GRP\_RPL\_APPLIER\_HANDLER\_IS\_IN\_USE error code, 374  
 ER\_GRP\_RPL\_APPLIER\_HANDLER\_NOT\_INITIALIZED error code, 374  
 ER\_GRP\_RPL\_APPLIER\_HANDLER\_ROLE\_IS\_IN\_USE error code, 374  
 ER\_GRP\_RPL\_APPLIER\_INITIALIZED error code, 370  
 ER\_GRP\_RPL\_APPLIER\_METADATA\_REPO\_MUST\_BE\_TABLE error code, 371  
 ER\_GRP\_RPL\_APPLIER\_NOT\_STARTED\_DUE\_TO\_RUNNING\_PIPELINE error code, 369  
 ER\_GRP\_RPL\_APPLIER\_PIPELINE\_NOT\_DISPOSED error code, 343  
 ER\_GRP\_RPL\_APPLIER\_TERMINATION\_TIMED\_OUT\_ON\_SHUTDOWN error code, 368  
 ER\_GRP\_RPL\_APPLIER\_THD\_EXECUTION\_ABORTED error code, 343  
 ER\_GRP\_RPL\_APPLIER\_THD\_KILLED error code, 342  
 ER\_GRP\_RPL\_APPLIER\_THD\_SETUP\_ERROR error code, 353  
 ER\_GRP\_RPL\_APPLIER\_THD\_START\_ERROR error code, 353  
 ER\_GRP\_RPL\_APPLIER\_THD\_STOP\_ERROR error code, 353  
 ER\_GRP\_RPL\_APPOINTED\_PRIMARY\_NOT\_PRESENT error code, 540  
 ER\_GRP\_RPL\_AUTO\_INC\_OFFSET\_RESET error code, 354  
 ER\_GRP\_RPL\_AUTO\_INC\_OFFSET\_SET error code, 355  
 ER\_GRP\_RPL\_AUTO\_INC\_RESET error code, 354  
 ER\_GRP\_RPL\_AUTO\_INC\_SET error code, 354  
 ER\_GRP\_RPL\_BINLOG\_CHECKSUM\_SET error code, 360  
 ER\_GRP\_RPL\_BINLOG\_DISABLED error code, 370  
 ER\_GRP\_RPL\_BLOCK\_SIZE\_DIFF\_FROM\_GRP error code, 352  
 ER\_GRP\_RPL\_BROADCASTING\_TRANS\_TO\_GRP\_FAILED error code, 363  
 ER\_GRP\_RPL\_BROADCAST\_COMMIT\_MSSG\_TOO\_BIG error code, 377  
 ER\_GRP\_RPL\_BROADCAST\_COMMIT\_TRANS\_MSSG\_FAILED error code, 360  
 ER\_GRP\_RPL\_CANNOT\_EXECUTE\_TRANS\_IN\_ERROR\_STATE error code, 361

---

ER\_GRP\_RPL\_CANNOT\_EXECUTE\_TRANS\_IN\_OFFLINE\_MODE error code, 361  
 ER\_GRP\_RPL\_CANNOT\_EXECUTE\_TRANS\_WHILE\_READING error code, 361  
 ER\_GRP\_RPL\_CANNOT\_EXECUTE\_TRANS\_WHILE\_STOPPING error code, 361  
 ER\_GRP\_RPL\_CANT\_GENERATE\_GTID error code, 345  
 ER\_GRP\_RPL\_CANT\_KILL\_THREAD error code, 567  
 ER\_GRP\_RPL\_CANT\_READ\_GRP\_GTID\_EXTRACTED error code, 346  
 ER\_GRP\_RPL\_CANT\_READ\_GTID error code, 346  
 ER\_GRP\_RPL\_CANT\_READ\_WRITE\_SET\_ITEM error code, 347  
 ER\_GRP\_RPL\_CERTIFICATE\_SIZE\_ERROR error code, 342  
 ER\_GRP\_RPL\_CERTIFICATION\_INITIALIZATION\_FAILURE error code, 345  
 ER\_GRP\_RPL\_CERTIFICATION\_REC\_PROCESS error code, 364  
 ER\_GRP\_RPL\_CERTIFIER\_MSSG\_PROCESS\_ERROR error code, 347  
 ER\_GRP\_RPL\_CHANGE\_GRP\_MEM\_NOT\_PROCESSED error code, 348  
 ER\_GRP\_RPL\_CHANNEL\_THREAD\_WHEN\_GROUP\_ACTION\_PENDING error code, 539  
 ER\_GRP\_RPL\_CHECK\_STATUS\_TABLE error code, 359  
 ER\_GRP\_RPL\_CLONE\_PROCESS\_EXEC\_ERROR error code, 567  
 ER\_GRP\_RPL\_CLONE\_PROCESS\_PREPARE\_ERROR error code, 566  
 ER\_GRP\_RPL\_COMMUNICATION\_SSL\_CONF\_INFO error code, 370  
 ER\_GRP\_RPL\_CONFIGURATION\_ACTION\_END error code, 540  
 ER\_GRP\_RPL\_CONFIGURATION\_ACTION\_ERROR error code, 540  
 ER\_GRP\_RPL\_CONFIGURATION\_ACTION\_KILLED\_ERROR error code, 540  
 ER\_GRP\_RPL\_CONFIGURATION\_ACTION\_LOCAL\_TERMINATION error code, 540  
 ER\_GRP\_RPL\_CONFIGURATION\_ACTION\_START error code, 540  
 ER\_GRP\_RPL\_CONFIG\_RECOVERY error code, 358  
 ER\_GRP\_RPL\_CONFLICT\_DETECTION\_DISABLED error code, 347  
 ER\_GRP\_RPL\_CONNECTION\_METADATA\_REPO\_MUST\_BE\_TABLE error code, 371  
 ER\_GRP\_RPL\_CONN\_INTERNAL\_PLUGIN\_FAIL error code, 357  
 ER\_GRP\_RPL\_CONTACT\_WITH\_SRV\_FAILED error code, 356  
 ER\_GRP\_RPL\_COPY\_FROM\_EMPTY\_STRING error code, 357  
 ER\_GRP\_RPL\_CREATE\_APPLIER\_CACHE\_ERROR error code, 342  
 ER\_GRP\_RPL\_CREATE\_GRP\_RPL\_REC\_CHANNEL error code, 359  
 ER\_GRP\_RPL\_CREATE\_SESSION\_UNABLE error code, 357  
 ER\_GRP\_RPL\_DATA\_NOT\_PROVIDED\_BY\_MEM error code, 350  
 ER\_GRP\_RPL\_DEBUG\_OPTIONS error code, 376  
 ER\_GRP\_RPL\_DEFAULT\_TABLE\_ENCRYPTION\_DIFF\_FROM error code, 558  
 ER\_GRP\_RPL\_DISABLE\_READ\_ONLY\_FAILED error code, 349  
 ER\_GRP\_RPL\_DISABLE\_SRV\_READ\_MODE\_RESTRICTED error code, 347  
 ER\_GRP\_RPL\_DONOR\_CONN\_TERMINATION error code, 359  
 ER\_GRP\_RPL\_DONOR\_SERVER\_CONN error code, 359  
 ER\_GRP\_RPL\_DONOR\_TRANS\_INFO\_ERROR error code, 344  
 ER\_GRP\_RPL\_DONOR\_VIEW\_CHANGE\_UUID\_TRANS\_INFO\_ERROR error code, 344  
 ER\_GRP\_RPL\_ENABLE\_READ\_ONLY\_FAILED error code, 349  
 ER\_GRP\_RPL\_ERROR\_FETCHING\_GTID\_EXECUTED\_SET error code, 344  
 ER\_GRP\_RPL\_ERROR\_FETCHING\_GTID\_SET error code, 344  
 ER\_GRP\_RPL\_ERROR\_GTID\_EXECUTION\_INFO error code, 342  
 ER\_GRP\_RPL\_ERROR\_GTID\_SET\_EXTRACTION error code, 539  
 ER\_GRP\_RPL\_ERROR\_MSG error code, 320  
 ER\_GRP\_RPL\_ERROR\_ON\_CERT\_DB\_INSTALL error code, 553  
 ER\_GRP\_RPL\_ERROR\_ON\_MESSAGE\_SENDING error code, 540  
 ER\_GRP\_RPL\_ERROR\_SENDING\_SINGLE\_PRIMARY\_MSSG error code, 343  
 ER\_GRP\_RPL\_ERROR\_SET\_MULTI\_CONSENSUS\_LEADER error code, 611  
 ER\_GRP\_RPL\_ERROR\_SET\_SINGLE\_CONSENSUS\_LEADER error code, 611  
 ER\_GRP\_RPL\_ERROR\_STOPPING\_CHANNELS error code, 343  
 ER\_GRP\_RPL\_ERROR\_VERIFYING\_SIDNO error code, 345  
 ER\_GRP\_RPL\_ERROR\_WHILE\_WAITING\_FOR\_CONFLICT\_DETECTION error code, 363  
 ER\_GRP\_RPL\_ESTABLISHING\_CONN\_GRP\_REC\_DONOR error code, 358

---

---

ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHERDONOR error code, 358	ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERV error code, 368
ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR error code, 358	ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERV error code, 368
ER_GRP_RPL_EVENT_HANDLING_ERROR error code, 342	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTI error code, 363
ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE error code, 350	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERV error code, 368
ER_GRP_RPL_EXIT_GRP_GCS_ERROR error code, 376	ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_READ error code, 361
ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING error code, 374	ER_GRP_RPL_FAILED_TO_REINIT_CORE_SHUTDOWN_REGISTRY_MODULE error code, 368
ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP error code, 360	ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE error code, 366
ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS error code, 360	ER_GRP_RPL_FAILED_TO_START_ON_BOOT error code, 368
ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_INTERFACE error code, 366	ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH_ASYNC error code, 366
ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT error code, 366	ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID error code, 365
ER_GRP_RPL_FAILED_TO_CREATE_COMMIT_CACHE error code, 363	ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL error code, 368
ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT error code, 362	ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBS error code, 369
ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE error code, 367	ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBS error code, 369
ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE error code, 365	ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBS error code, 369
ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET error code, 362	ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATION error code, 148
ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET error code, 362	ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_EXIST error code, 606
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP error code, 369	ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATION error code, 606
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW error code, 602	ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE_DATA error code, 606
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER error code, 374	ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_JOIN error code, 606
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE error code, 369	ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DEFAULT_C error code, 606
ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE error code, 366	ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY error code, 607
ER_GRP_RPL_FAILED_TO_INIT_HANDLER error code, 368	ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY error code, 606
ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON error code, 550	ER_GRP_RPL_FAILED_TO_REGISTER_MESSAGE_LISTENER_SER error code, 606
ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE error code, 622	ER_GRP_RPL_FATAL_REC_PROCESS error code, 364
ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP error code, 360	ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED error code, 355
ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME error code, 369	ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED error code, 355
ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE error code, 602	ER_GRP_RPL_FETCH_LOG_EVENT_FAILED error code, 356

---

---

ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED error code, 355	ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID error code, 372
ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED error code, 355	ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_TO error code, 594
ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED error code, 355	ER_GRP_RPL_GRP_NAME_IS_TOO_LONG error code, 372
ER_GRP_RPL_FETCH_TRANS_DATA_FAILED error code, 353	ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY error code, 372
ER_GRP_RPL_FETCH_TRANS_SIDNO_ERROR error code, 345	ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBL error code, 602
ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED error code, 356	ER_GRP_RPL_GTID_ALREADY_USED error code, 342
ER_GRP_RPL_FINISHED_AUTO_REJOIN error code, 558	ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR error code, 351
ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED error code, 354	ER_GRP_RPL_GTID_MODE_OFF error code, 370
ER_GRP_RPL_FLOW_CONTROL_STATS error code, 378	ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR error code, 566
ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_OWN_QUOTA error code, 373	ER_GRP_RPL_GTID_SET_EXTRACT_ERROR error code, 351
ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_OWN_QUOTA error code, 372	ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_REC error code, 552
ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX_QUOTA error code, 372	ER_GRP_RPL_HAS_STARTED error code, 634
ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY error code, 365	ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_AP error code, 374
ER_GRP_RPL_FORCE_MEMBERS_SET_UPDATE_NOT_ALLOWED error code, 373	ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE error code, 347
ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING error code, 553	ER_GRP_RPL_INTERNAL_QUERY error code, 357
ER_GRP_RPL_FORCE_MEMBER_VALUE_SET error code, 377	ER_GRP_RPL_INVALID_BINLOG_FORMAT error code, 360
ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR error code, 377	ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL error code, 558
ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT error code, 377	ER_GRP_RPL_INVALID_DEBUG_OPTIONS error code, 376
ER_GRP_RPL_GCS_GR_ERROR_MSG error code, 378	ER_GRP_RPL_INVALID_GTID_SET error code, 345
ER_GRP_RPL_GCS_INTERFACE_ERROR error code, 377	ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING error code, 373
ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION error code, 376	ER_GRP_RPL_INVALID_TRANS_WRITE_SET_EXTRACTION_V error code, 371
ER_GRP_RPL_GROUP_NAME_PARSE_ERROR error code, 344	ER_GRP_RPL_IS_STARTING error code, 582
ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_INFO error code, 601	ER_GRP_RPL_IS_STOPPED error code, 367
ER_GRP_RPL_GRP_CHANGE_INFO_EXTRACT_ERROR error code, 350	ER_GRP_RPL_IS_STOPPING error code, 367
ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED error code, 376	ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNN error code, 539
ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONFLICT error code, 373	ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING error code, 539
ER_GRP_RPL_GRP_MEMBER_OFFLINE error code, 377	ER_GRP_RPL_KILLED_FAILED_ID error code, 357
	ER_GRP_RPL_KILLED_SESSION_ID error code, 357
	ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR error code, 351
	ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET error code, 371
	ER_GRP_RPL_LOG_SLAVE_UPDATES_NOT_SET error code, 370
	ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_C error code, 527

---

---

ER_GRP_RPL_MASTER_INFO_REPO_MUST_BE_TABLE	ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP
error code, 371	error code, 352
ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_READ	ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP
error code, 358	error code, 351
ER_GRP_RPL_MEMBER_ACTIONS_RESET	ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE
error code, 600	error code, 351
ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION	ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE
error code, 600	error code, 563
ER_GRP_RPL_MEMBER_ACTION_DISABLED	ER_GRP_RPL_MEM_ONLINE
error code, 600	error code, 348
ER_GRP_RPL_MEMBER_ACTION_ENABLED	ER_GRP_RPL_MEM_REACHABLE
error code, 600	error code, 348
ER_GRP_RPL_MEMBER_ACTION_FAILURE	ER_GRP_RPL_MEM_UNREACHABLE
error code, 599	error code, 348
ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE	ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR
error code, 599	error code, 570
ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE	ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE
error code, 599	error code, 132
ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_Only	ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR
error code, 600	error code, 539
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER	ER_GRP_RPL_MISSING_GRP_RPL_APPLIER
error code, 600	error code, 543
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVER	ER_GRP_RPL_MEMBER_JOIN
error code, 599	error code, 572
ER_GRP_RPL_MEMBER_ACTION_TRIGGERED	ER_GRP_RPL_MODULE_TERMINATE_ERROR
error code, 599	error code, 347
ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAUL	ER_GRP_RPL_MSG_DISCARDED
error code, 600	error code, 363
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS	ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS_FAIL
error code, 599	error code, 361
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_Only	ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED_FOR
error code, 600	error code, 361
ER_GRP_RPL_MEMBER_ADDED	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_
error code, 349	error code, 605
ER_GRP_RPL_MEMBER_ALREADY_EXISTS	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_
error code, 350	error code, 605
ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_
error code, 352	error code, 605
ER_GRP_RPL_MEMBER_CHANGE	ER_GRP_RPL_NEW_PRIMARY_ELECTED
error code, 349	error code, 349
ER_GRP_RPL_MEMBER_CONF_INFO	ER_GRP_RPL_NEW_PRIMARY_ELECTED
error code, 366	error code, 349
ER_GRP_RPL_MEMBER_CONTACT_RESTORED	ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED
error code, 348	error code, 356
ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR	ER_GRP_RPL_NO_POSSIBLE_RECOVERY
error code, 349	error code, 567
ER_GRP_RPL_MEMBER_EXPELLED	ER_GRP_RPL_NO_STAGE_SERVICE
error code, 349	error code, 541
ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST	ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM
error code, 641	error code, 350
ER_GRP_RPL_MEMBER_LEFT_GRP	ER_GRP_RPL_NO_VALID_DONOR
error code, 349	error code, 358
ER_GRP_RPL_MEMBER_NOT_FOUND	ER_GRP_RPL_NULL_PACKET
error code, 358	error code, 346
ER_GRP_RPL_MEMBER_REMOVED	ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE
error code, 348	error code, 364
ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIB	ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION_
error code, 366	error code, 360
ER_GRP_RPL_MEMBER_STATS_INFO	ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GRP
error code, 377	error code, 611
ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERRO	ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_OLD_GRP
error code, 352	error code, 632
	error code, 678
	ER_GRP_RPL_PIPELINE_CREATE_FAILED
	error code, 378
	ER_GRP_RPL_PIPELINE_FLUSH_FAIL
	error code, 378

---



---

ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ error code, 378	ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK error code, 568
ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE error code, 378	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENC error code, 551
ER_GRP_RPL_PLUGIN_ABORT error code, 536	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_PRE error code, 551
ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE error code, 365	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFO error code, 551
ER_GRP_RPL_PREV_REC_SESSION_RUNNING error code, 363	ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_WRITE_FA error code, 363
ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR error code, 540	ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_READ_F error code, 362
ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR error code, 541	ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_WRITE error code, 363
ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED error code, 354	ER_GRP_RPL_RELAY_LOG_INFO_REPO_MUST_BE_TABLE error code, 371
ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP error code, 349	ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENC error code, 551
ER_GRP_RPL_PROCESS_GTID_SET_ERROR error code, 346	ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR_SY error code, 552
ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR error code, 346	ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPAR error code, 550
ER_GRP_RPL_PURGE_APPLIER_LOGS error code, 352	ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT error code, 379
ER_GRP_RPL_PURGE_REC error code, 359	ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED error code, 379
ER_GRP_RPL_QUERY_FAIL error code, 357	ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN error code, 353
ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER error code, 365	ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT error code, 379
ER_GRP_RPL_READ_UNABLE_FOR_SUPER_READ_ONLY error code, 364	ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED error code, 379
ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS error code, 346	ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT error code, 372
ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING error code, 145	ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_MEMB error code, 354
ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT error code, 582	ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN error code, 354
ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IP error code, 583	ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE error code, 607
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID error code, 582	ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECONDARY error code, 607
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR error code, 583	ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_TO_L error code, 357
ER_GRP_RPL_RECOVERY_EVAL_ERROR error code, 567	ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR error code, 352
ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMER error code, 368	ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMBER error code, 353
ER_GRP_RPL_RECOVERY_STRAT_CHOICE error code, 567	ER_GRP_RPL_SEND_STATS_ERROR error code, 377
ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED error code, 567	ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED error code, 550
ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD error code, 567	ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAI error code, 552
ER_GRP_RPL_RECOVERY_STRAT_FALLBACK error code, 567	

---

---

ER\_GRP\_RPL\_SERVER\_ALREADY\_LEFT error code, 367  
 ER\_GRP\_RPL\_SERVER\_CONN\_ERROR error code, 344  
 ER\_GRP\_RPL\_SERVER\_IS\_ALREADY\_LEAVING error code, 367  
 ER\_GRP\_RPL\_SERVER\_SET\_TO\_OFFLINE\_MODE\_DUE\_TO\_ERRORS error code, 569  
 ER\_GRP\_RPL\_SERVER\_SET\_TO\_READ\_ONLY\_DUE\_TO\_ERRORS error code, 376  
 ER\_GRP\_RPL\_SERVER\_UDF\_ERROR error code, 541  
 ER\_GRP\_RPL\_SERVER\_WORKING\_AS\_SECONDARY error code, 365  
 ER\_GRP\_RPL\_SESSION\_OPEN\_FAILED error code, 349  
 ER\_GRP\_RPL\_SET\_GRP\_COMMUNICATION\_ENG\_LOG\_ENABLED error code, 376  
 ER\_GRP\_RPL\_SET\_MULTI\_CONSENSUS\_LEADER error code, 611  
 ER\_GRP\_RPL\_SET\_SINGLE\_CONSENSUS\_LEADER error code, 611  
 ER\_GRP\_RPL\_SET\_STABLE\_TRANS\_ERROR error code, 346  
 ER\_GRP\_RPL\_SIDNO\_FETCH\_ERROR error code, 343  
 ER\_GRP\_RPL\_SINGLE\_PRIM\_MODE\_NOT\_ALLOWED\_WITH\_GRP error code, 372  
 ER\_GRP\_RPL\_SKIP\_COMPUTATION\_TRANS\_COMMITTED error code, 346  
 ER\_GRP\_RPL\_SLAVE\_APPLIER\_THREAD\_ERROR\_OUTER error code, 379  
 ER\_GRP\_RPL\_SLAVE\_APPLIER\_THREAD\_UNBLOCKED error code, 379  
 ER\_GRP\_RPL\_SLAVE\_IO\_THD\_PRIMARY\_UNKNOWN error code, 353  
 ER\_GRP\_RPL\_SLAVE\_IO\_THREAD\_ERROR\_OUT error code, 379  
 ER\_GRP\_RPL\_SLAVE\_IO\_THREAD\_UNBLOCKED error code, 379  
 ER\_GRP\_RPL\_SLAVE\_PRESERVE\_COMMIT\_ORDER\_NOT\_SET error code, 371  
 ER\_GRP\_RPL\_SLAVE\_SQL\_THD\_ON\_SECONDARY\_MEMBER error code, 354  
 ER\_GRP\_RPL\_SLAVE\_SQL\_THD\_PRIMARY\_UNKNOWN error code, 353  
 ER\_GRP\_RPL\_SLAVE\_THREAD\_ERROR\_ON\_CLONE error code, 568  
 ER\_GRP\_RPL\_SLAVE\_THREAD\_ERROR\_ON\_SECONDARY\_MEMBER error code, 607  
 ER\_GRP\_RPL\_SQL\_SERVICE\_COMM\_SESSION\_NOT\_INITIALIZED error code, 374  
 ER\_GRP\_RPL\_SQL\_SERVICE\_FAILED\_TO\_FETCH\_SECONDARY error code, 375  
 ER\_GRP\_RPL\_SQL\_SERVICE\_FAILED\_TO\_INIT\_SESSION error code, 374  
 ER\_GRP\_RPL\_SQL\_SERVICE\_FAILED\_TO\_RUN\_SQL\_QUERY error code, 374  
 ER\_GRP\_RPL\_SQL\_SERVICE\_MAX\_CONN\_ERROR\_FROM\_SERVER error code, 375  
 ER\_GRP\_RPL\_SQL\_SERVICE\_RETRIES\_EXCEEDED\_ON\_SESSION error code, 375  
 ER\_GRP\_RPL\_SQL\_SERVICE\_SERVER\_ACCESS\_DENIED\_FOR\_TRANSACTION error code, 375  
 ER\_GRP\_RPL\_SQL\_SERVICE\_SERVER\_ERROR\_ON\_CONN error code, 375  
 ER\_GRP\_RPL\_SQL\_SERVICE\_SERVER\_INTERNAL\_FAILURE error code, 375  
 ER\_GRP\_RPL\_SQL\_SERVICE\_SERVER\_SESSION\_KILLED error code, 374  
 ER\_GRP\_RPL\_SRV\_BLOCKED error code, 348  
 ER\_GRP\_RPL\_SRV\_BLOCKED\_FOR\_SECS error code, 348  
 ER\_GRP\_RPL\_SRV\_GTID\_WAIT\_ERROR error code, 561  
 ER\_GRP\_RPL\_SRV\_NOT\_ONLINE error code, 347  
 ER\_GRP\_RPL\_SRV\_ONLINE error code, 347  
 ER\_GRP\_RPL\_SRV\_PRIMARY\_MEM error code, 350  
 ER\_GRP\_RPL\_SRV\_SECONDARY\_MEM error code, 350  
 ER\_GRP\_RPL\_SRV\_WAIT\_TIME\_OUT error code, 356  
 ER\_GRP\_RPL\_SSL\_DISABLED error code, 370  
 ER\_GRP\_RPL\_STARTED\_AUTO\_REJOIN error code, 558  
 ER\_GRP\_RPL\_STARTING\_GRP\_REC error code, 359  
 ER\_GRP\_RPL\_START\_FAILED error code, 351  
 ER\_GRP\_RPL\_START\_GRP\_RPL\_FAILED error code, 357  
 ER\_GRP\_RPL\_STOPPING\_GRP\_REC error code, 359  
 ER\_GRP\_RPL\_STOP\_REP\_CHANNEL error code, 378  
 ER\_GRP\_RPL\_SUPER\_READ\_OFF error code, 357  
 ER\_GRP\_RPL\_SUPER\_READ\_ON error code, 357  
 ER\_GRP\_RPL\_SUPER\_READ\_ONLY\_ACTIVATE\_ERROR error code, 350  
 ER\_GRP\_RPL\_SUPPORTS\_ONLY\_ONE\_FORCE\_MEMBERS\_SET error code, 373  
 ER\_GRP\_RPL\_TIMEOUT\_ON\_VIEW\_AFTER\_JOINING\_GRP error code, 366  
 ER\_GRP\_RPL\_TIMEOUT\_RECEIVED\_VC\_LEAVE\_ON\_REJOIN error code, 590  
 ER\_GRP\_RPL\_TIMEOUT\_RECEIVED\_VC\_ON\_REJOIN error code, 558  
 ER\_GRP\_RPL\_TIMEOUT\_RECEIVING\_VIEW\_CHANGE\_ON\_SHUTDOWN error code, 367  
 ER\_GRP\_RPL\_TRANS\_GREATER\_THAN\_GRP error code, 351  
 ER\_GRP\_RPL\_TRANS\_NOT\_PRESENT\_IN\_GRP error code, 351  
 ER\_GRP\_RPL\_TRANS\_SIZE\_EXCEEDS\_LIMIT error code, 362

---

ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOT_SET error code, 361	ER_GRP_RPL_UPDATE_GTID_SET_ERROR error code, 345
ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_GRP error code, 352	ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANS_ERROR error code, 345
ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_APPLIER error code, 550	ER_GRP_UPDATE_SERV_CERTIFICATE_FAILED error code, 355
ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLER error code, 551	ER_GRP_UPDATE_TRANS_SNAPSHOT_REF_VER_ERROR error code, 345
ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED error code, 552	ER_GRP_UPDATE_TRANS_SNAPSHOT_VER_ERROR error code, 343
ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED error code, 551	ER_GRP_VIEW_CHANGE_UUID_DIFF_FROM_GRP error code, 602
ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED error code, 552	ER_GRP_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE error code, 147
ER_GRP_RPL_UDF_ERROR error code, 131	ER_GRP_VIEW_CHANGE_UUID_INVALID error code, 601
ER_GRP_RPL_UDF_REGISTER_ERROR error code, 541	ER_GRP_VIEW_CHANGE_UUID_IS_SAME_AS_ANONYM error code, 601
ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR error code, 541	ER_GRP_VIEW_CHANGE_UUID_PARSE_ERROR error code, 602
ER_GRP_RPL_UDF_UNREGISTER_ERROR error code, 541	ER_GRP_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME error code, 601
ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS error code, 365	ER_GRP_WAITING_FOR_VIEW_UPDATE error code, 367
ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET error code, 378	ER_GRP_WAIT_FOR_DEPENDENCIES_FAILED error code, 551
ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT error code, 378	ER_GRP_WHILE_SENDING_MSG_REC error code, 364
ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_RECORD error code, 364	ER_GRP_WHILE_STOPPING_REP_CHANNEL error code, 364
ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS error code, 364	ER_GRP_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED error code, 360
ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE error code, 370	ER_GRP_WRITE_TO_BINLOG_CACHE_FAILED error code, 362
ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLIER error code, 359	ER_GRP_WRITE_TO_TRANSACTION_MESSAGE_FAILED error code, 362
ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLIER error code, 360	ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN error code, 118
ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE error code, 365	ER_GRP_TRX_CONSISTENCY_BEFORE error code, 118
ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS error code, 365	ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED error code, 118
ER_GRP_RPL_UNBLOCK_WAITING_THD error code, 342	ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED error code, 118
ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_REQUEST error code, 373	ER_GR_ELECTED_PRIMARY_GTID_INFORMATION_FROM_MEMBER error code, 116
ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_MEMBER error code, 376	ER_GR_HOLD_KILLED error code, 116
ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION error code, 361	ER_GR_HOLD_MEMBER_STATUS_ERROR error code, 117
ER_GRP_RPL_UPDATE_GRP GTID_EXECUTED_ERROR error code, 344	ER_GR_HOLD_WAIT_TIMEOUT error code, 116
ER_GRP_RPL_UPDATE_GRP GTID_VIEW_CHANGE_UUID_EXECUTED_ERROR error code, 602	ER_GTID_ALREADY_ADDED_BY_USER error code, 116
	ER_GTID_EXECUTED_WAS_CHANGED error code, 63

---

---

ER\_GTID\_EXECUTED\_WAS\_UPDATED error code, 278  
 ER\_GTID\_MODE\_CAN\_ONLY\_CHANGE\_ONE\_STEP\_AT\_A\_TIME error code, 58  
 ER\_GTID\_MODE\_OFF error code, 74  
 ER\_GTID\_MODE\_ON\_REQUIRES\_ENFORCE\_GTID\_CONSISTENCY error code, 58  
 ER\_GTID\_NEXT\_CANT\_BE\_AUTOMATIC\_IF\_GTID\_NEXT\_IS\_BIGGER error code, 57  
 ER\_GTID\_NEXT\_TYPE\_UNDEFINED\_GROUP error code, 63  
 ER\_GTID\_NEXT\_TYPE\_UNDEFINED\_GTID error code, 63  
 ER\_GTID\_PURGED\_WAS\_CHANGED error code, 63  
 ER\_GTID\_PURGED\_WAS\_UPDATED error code, 278  
 ER\_GTID\_UNSAFE\_ALTER\_ADD\_COL\_WITH\_DEFAULT\_EXPRESSION error code, 116  
 ER\_GTID\_UNSAFE\_BINLOG\_SPLITTABLE\_STATEMENT error code, 67  
 ER\_GTID\_UNSAFE\_BINLOG\_SPLITTABLE\_STATEMENT error code, 67  
 ER\_GTID\_UNSAFE\_CREATE\_DROP\_TEMPORARY\_TABLES\_IN\_TRANSACTION error code, 58  
 ER\_GTID\_UNSAFE\_CREATE\_SELECT error code, 58  
 ER\_GTID\_UNSAFE\_NON\_TRANSACTIONAL\_TABLE error code, 58  
 ER\_HANDLERTON\_OOM error code, 188  
 ER\_HANDSHAKE\_ERROR error code, 6  
 ER\_HEALTH\_ERROR error code, 594  
 ER\_HEALTH\_INFO error code, 594  
 ER\_HEALTH\_WARNING error code, 594  
 ER\_HEALTH\_WARNING\_DISK\_USAGE\_LEVEL\_1 error code, 595  
 ER\_HEALTH\_WARNING\_DISK\_USAGE\_LEVEL\_2 error code, 595  
 ER\_HEALTH\_WARNING\_DISK\_USAGE\_LEVEL\_3 error code, 595  
 ER\_HEALTH\_WARNING\_MEMORY\_USAGE\_LEVEL\_1 error code, 610  
 ER\_HEALTH\_WARNING\_MEMORY\_USAGE\_LEVEL\_2 error code, 610  
 ER\_HEALTH\_WARNING\_MEMORY\_USAGE\_LEVEL\_3 error code, 610  
 ER\_HOSTNAME error code, 35  
 ER\_HOSTNAME\_DOESNT\_RESOLVE\_TO error code, 168  
 ER\_HOSTNAME\_RESEMBLES\_IPV4 error code, 168  
 ER\_HOSTNAME\_TOO\_LONG error code, 138  
 ER\_HOSTNAME\_TRUNCATED error code, 584  
 ER\_HOST\_IS\_BLOCKED error code, 12  
 ER\_HOST\_NOT\_PRIVILEGED error code, 12  
 ER\_HYPERGRAPH\_NOT\_SUPPORTED\_YET error code, 142  
 ER\_IB\_BUFFER\_POOL\_FULL error code, 628  
 ER\_IB\_BUFFER\_POOL\_OVERUSE error code, 628  
 ER\_IB\_BULK\_FLUSHER\_INFO error code, 628  
 ER\_IB\_BULK\_LOAD\_MERGE\_FAIL error code, 631  
 ER\_IB\_BULK\_LOAD\_SUBTREE\_INFO error code, 628  
 ER\_IB\_BULK\_LOAD\_THREAD\_FAIL error code, 631  
 ER\_IB\_CANNOT\_UPGRADE\_WITH\_DISCARDED\_TABLESPACES error code, 584  
 ER\_IB\_CLONE\_GTID\_PERSIST error code, 406  
 ER\_IB\_CLONE\_INTERNAL error code, 404  
 ER\_IB\_CLONE\_NON\_INNODB\_TABLE error code, 566  
 ER\_IB\_CLONE\_OPERATION error code, 566  
 ER\_IB\_CLONE\_PUNCH\_HOLE error code, 405  
 ER\_IB\_CLONE\_RESTART error code, 566  
 ER\_IB\_CLONE\_SQL error code, 405  
 ER\_IB\_CLONE\_START\_STOP error code, 566  
 ER\_IB\_CLONE\_STATUS\_FILE error code, 405  
 ER\_IB\_CLONE\_TIMEOUT error code, 405  
 ER\_IB\_CLONE\_UNEXPECTED\_DATA error code, 566  
 ER\_IB\_CLONE\_VALIDATE error code, 405  
 ER\_IB\_CLONE\_VALIDATE\_GROUP\_INFO error code, 615  
 ER\_IB\_DBLWR\_DECOMPRESS\_FAILED error code, 591  
 ER\_IB\_DBLWR\_DECRYPT\_FAILED error code, 591  
 ER\_IB\_DBLWR\_KEY\_MISSING error code, 591  
 ER\_IB\_DDL\_CONVERT\_HEAP\_NOT\_FOUND error code, 640  
 ER\_IB\_DICT\_INVALID\_COLUMN\_POSITION error code, 632  
 ER\_IB\_DICT\_LOG\_TABLE\_INFO error code, 633  
 ER\_IB\_DUPLICATE\_KEY error code, 628  
 ER\_IB\_ERR\_DDL\_LOG\_INSERT\_FAILURE error code, 585  
 ER\_IB\_ERR\_FOUND\_N\_DUPLICATE\_KEYS error code, 588  
 ER\_IB\_ERR\_FOUND\_N\_RECORDS\_WRONG\_ORDER error code, 588  
 ER\_IB\_ERR\_INDEX\_DUPLICATE\_KEY error code, 588  
 ER\_IB\_ERR\_INDEX\_RECORDS\_WRONG\_ORDER error code, 588  
 ER\_IB\_ERR\_LOG\_PARSING\_BUFFER\_OVERFLOW error code, 587  
 ER\_IB\_ERR\_NOT\_ENOUGH\_MEMORY\_FOR\_PARSE\_BUFFER error code, 587  
 ER\_IB\_ERR\_PAGE\_ARCH\_DBLWR\_INIT\_FAILED error code, 604  
 ER\_IB\_ERR\_PAGE\_ARCH\_INVALID\_DOUBLE\_WRITE\_BUF error code, 581  
 ER\_IB\_ERR\_PAGE\_ARCH\_INVALID\_FORMAT error code, 581  
 ER\_IB\_ERR\_PAGE\_ARCH\_RECOVERY\_FAILED error code, 581  
 ER\_IB\_ERR\_PARALLEL\_READ\_OOM error code, 588  
 ER\_IB\_ERR\_RECOVERY\_REDO\_DISABLED error code, 583

---

ER_IB_ERR_SCHED_SETAFFINITY_FAILED error code, 587	ER_IB_MSG_1014 error code, 495
ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMERROR error code, 586	ER_IB_MSG_1015 error code, 495
ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST error code, 586	ER_IB_MSG_1016 error code, 495
ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY error code, 586	ER_IB_MSG_1017 error code, 496
ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATAFILE error code, 586	ER_IB_MSG_1018 error code, 496
ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE error code, 587	ER_IB_MSG_1019 error code, 496
ER_IB_ERR_ZLIB_BUF_ERROR error code, 587	ER_IB_MSG_102 error code, 400
ER_IB_ERR_ZLIB_DATA_ERROR error code, 588	ER_IB_MSG_1020 error code, 496
ER_IB_ERR_ZLIB_MEM_ERROR error code, 588	ER_IB_MSG_1021 error code, 496
ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED error code, 587	ER_IB_MSG_1022 error code, 496
ER_IB_ERR_ZLIB_UNKNOWN_ERROR error code, 588	ER_IB_MSG_1023 error code, 496
ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE error code, 586	ER_IB_MSG_1024 error code, 496
ER_IB_HIDDEN_NAME_CONFLICT error code, 632	ER_IB_MSG_1025 error code, 496
ER_IB_INDEX_BUILDER_DONE error code, 634	ER_IB_MSG_1026 error code, 496
ER_IB_INDEX_BUILDER_INIT error code, 634	ER_IB_MSG_1027 error code, 497
ER_IB_INDEX_LOADER_DONE error code, 633	ER_IB_MSG_1028 error code, 497
ER_IB_INDEX_LOG_VERSION_MISMATCH error code, 634	ER_IB_MSG_1029 error code, 497
ER_IB_INDEX_PART_TOO_LONG error code, 642	ER_IB_MSG_103 error code, 400
ER_IB_INNODB_TBSP_OUT_OF_SPACE error code, 595	ER_IB_MSG_1030 error code, 497
ER_IB_LOAD_BULK_CONCURRENCY_REDUCED error code, 631	ER_IB_MSG_1031 error code, 497
ER_IB_LOB_ROLLBACK_INDEX_LEN error code, 572	ER_IB_MSG_1032 error code, 497
ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION error code, 585	ER_IB_MSG_1033 error code, 497
ER_IB_LONG_AHI_DISABLE_WAIT error code, 408	ER_IB_MSG_1034 error code, 497
ER_IB_MSG_0 error code, 389	ER_IB_MSG_1035 error code, 497
ER_IB_MSG_1 error code, 389	ER_IB_MSG_1036 error code, 497
ER_IB_MSG_10 error code, 390	ER_IB_MSG_1037 error code, 498
ER_IB_MSG_100 error code, 399	ER_IB_MSG_1038 error code, 498
ER_IB_MSG_1000 error code, 494	ER_IB_MSG_1039 error code, 498
ER_IB_MSG_1001 error code, 494	ER_IB_MSG_104 error code, 400
ER_IB_MSG_1002 error code, 494	ER_IB_MSG_1040 error code, 498
ER_IB_MSG_1003 error code, 494	ER_IB_MSG_1041 error code, 498
ER_IB_MSG_1004 error code, 494	ER_IB_MSG_1042 error code, 498
ER_IB_MSG_1005 error code, 494	ER_IB_MSG_1043 error code, 498
ER_IB_MSG_1006 error code, 494	ER_IB_MSG_1044 error code, 498
ER_IB_MSG_1007 error code, 495	ER_IB_MSG_1045 error code, 498
ER_IB_MSG_1008 error code, 495	ER_IB_MSG_1046 error code, 498
ER_IB_MSG_1009 error code, 495	ER_IB_MSG_1047 error code, 499
ER_IB_MSG_101 error code, 399	ER_IB_MSG_1048 error code, 499
ER_IB_MSG_1010 error code, 495	ER_IB_MSG_1049 error code, 499
ER_IB_MSG_1011 error code, 495	ER_IB_MSG_105 error code, 400
ER_IB_MSG_1012 error code, 495	ER_IB_MSG_1050 error code, 499
ER_IB_MSG_1013 error code, 495	ER_IB_MSG_1051 error code, 499
	ER_IB_MSG_1052 error code, 499
	ER_IB_MSG_1053 error code, 499
	ER_IB_MSG_1054 error code, 499
	ER_IB_MSG_1055 error code, 499
	ER_IB_MSG_1056 error code, 500
	ER_IB_MSG_1057 error code, 500
	ER_IB_MSG_1058 error code, 500
	ER_IB_MSG_1059 error code, 500
	ER_IB_MSG_106 error code, 400
	ER_IB_MSG_1060 error code, 500
	ER_IB_MSG_1061 error code, 500
	ER_IB_MSG_1062 error code, 500





---

ER\_IB\_MSG\_1258 error code, 524  
ER\_IB\_MSG\_1259 error code, 524  
ER\_IB\_MSG\_126 error code, 402  
ER\_IB\_MSG\_1260 error code, 524  
ER\_IB\_MSG\_1261 error code, 524  
ER\_IB\_MSG\_1262 error code, 524  
ER\_IB\_MSG\_1263 error code, 524  
ER\_IB\_MSG\_1264 error code, 524  
ER\_IB\_MSG\_1265 error code, 524  
ER\_IB\_MSG\_1266 error code, 525  
ER\_IB\_MSG\_1267 error code, 525  
ER\_IB\_MSG\_1268 error code, 525  
ER\_IB\_MSG\_1269 error code, 525  
ER\_IB\_MSG\_127 error code, 402  
ER\_IB\_MSG\_1270 error code, 525  
ER\_IB\_MSG\_1271 error code, 535  
ER\_IB\_MSG\_1272 error code, 535  
ER\_IB\_MSG\_1273 error code, 536  
ER\_IB\_MSG\_1274 error code, 537  
ER\_IB\_MSG\_1275 error code, 537  
ER\_IB\_MSG\_1276 error code, 537  
ER\_IB\_MSG\_1277 error code, 538  
ER\_IB\_MSG\_1278 error code, 538  
ER\_IB\_MSG\_1279 error code, 538  
ER\_IB\_MSG\_128 error code, 402  
ER\_IB\_MSG\_1280 error code, 538  
ER\_IB\_MSG\_1281 error code, 538  
ER\_IB\_MSG\_1282 error code, 538  
ER\_IB\_MSG\_1283 error code, 538  
ER\_IB\_MSG\_1284 error code, 538  
ER\_IB\_MSG\_1285 error code, 563  
ER\_IB\_MSG\_129 error code, 402  
ER\_IB\_MSG\_13 error code, 391  
ER\_IB\_MSG\_130 error code, 402  
ER\_IB\_MSG\_131 error code, 402  
ER\_IB\_MSG\_132 error code, 403  
ER\_IB\_MSG\_133 error code, 403  
ER\_IB\_MSG\_134 error code, 403  
ER\_IB\_MSG\_135 error code, 403  
ER\_IB\_MSG\_1357 error code, 585  
ER\_IB\_MSG\_1358 error code, 585  
ER\_IB\_MSG\_1359 error code, 585  
ER\_IB\_MSG\_136 error code, 403  
ER\_IB\_MSG\_137 error code, 403  
ER\_IB\_MSG\_1372 error code, 587  
ER\_IB\_MSG\_1373 error code, 587  
ER\_IB\_MSG\_1374 error code, 587  
ER\_IB\_MSG\_1375 error code, 587  
ER\_IB\_MSG\_138 error code, 403  
ER\_IB\_MSG\_1381 error code, 588  
ER\_IB\_MSG\_139 error code, 403  
ER\_IB\_MSG\_14 error code, 391  
ER\_IB\_MSG\_140 error code, 403  
ER\_IB\_MSG\_141 error code, 403

ER\_IB\_MSG\_142 error code, 404  
ER\_IB\_MSG\_143 error code, 404  
ER\_IB\_MSG\_144 error code, 404  
ER\_IB\_MSG\_145 error code, 404  
ER\_IB\_MSG\_146 error code, 404  
ER\_IB\_MSG\_147 error code, 404  
ER\_IB\_MSG\_148 error code, 404  
ER\_IB\_MSG\_149 error code, 404  
ER\_IB\_MSG\_15 error code, 391  
ER\_IB\_MSG\_150 error code, 404  
ER\_IB\_MSG\_151 error code, 405  
ER\_IB\_MSG\_152 error code, 405  
ER\_IB\_MSG\_153 error code, 405  
ER\_IB\_MSG\_154 error code, 405  
ER\_IB\_MSG\_155 error code, 405  
ER\_IB\_MSG\_156 error code, 406  
ER\_IB\_MSG\_157 error code, 406  
ER\_IB\_MSG\_158 error code, 406  
ER\_IB\_MSG\_159 error code, 406  
ER\_IB\_MSG\_16 error code, 391  
ER\_IB\_MSG\_160 error code, 406  
ER\_IB\_MSG\_161 error code, 406  
ER\_IB\_MSG\_162 error code, 406  
ER\_IB\_MSG\_163 error code, 406  
ER\_IB\_MSG\_164 error code, 406  
ER\_IB\_MSG\_165 error code, 407  
ER\_IB\_MSG\_166 error code, 407  
ER\_IB\_MSG\_167 error code, 407  
ER\_IB\_MSG\_168 error code, 407  
ER\_IB\_MSG\_169 error code, 407  
ER\_IB\_MSG\_17 error code, 391  
ER\_IB\_MSG\_170 error code, 407  
ER\_IB\_MSG\_171 error code, 407  
ER\_IB\_MSG\_172 error code, 407  
ER\_IB\_MSG\_173 error code, 407  
ER\_IB\_MSG\_174 error code, 407  
ER\_IB\_MSG\_175 error code, 408  
ER\_IB\_MSG\_176 error code, 408  
ER\_IB\_MSG\_177 error code, 408  
ER\_IB\_MSG\_178 error code, 408  
ER\_IB\_MSG\_179 error code, 408  
ER\_IB\_MSG\_18 error code, 391  
ER\_IB\_MSG\_180 error code, 408  
ER\_IB\_MSG\_181 error code, 408  
ER\_IB\_MSG\_182 error code, 408  
ER\_IB\_MSG\_183 error code, 408  
ER\_IB\_MSG\_184 error code, 409  
ER\_IB\_MSG\_185 error code, 409  
ER\_IB\_MSG\_186 error code, 409  
ER\_IB\_MSG\_187 error code, 409  
ER\_IB\_MSG\_188 error code, 409  
ER\_IB\_MSG\_189 error code, 409  
ER\_IB\_MSG\_19 error code, 391  
ER\_IB\_MSG\_190 error code, 409











---

ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL error code, 580	ER_IB_MSG_624 error code, 454
ER_IB_MSG_57_UNDO_SPACE_DELETE_FAIL error code, 576	ER_IB_MSG_625 error code, 454
ER_IB_MSG_58 error code, 395	ER_IB_MSG_626 error code, 454
ER_IB_MSG_580 error code, 449	ER_IB_MSG_627 error code, 454
ER_IB_MSG_581 error code, 449	ER_IB_MSG_628 error code, 454
ER_IB_MSG_582 error code, 449	ER_IB_MSG_629 error code, 454
ER_IB_MSG_583 error code, 450	ER_IB_MSG_63 error code, 396
ER_IB_MSG_584 error code, 450	ER_IB_MSG_630 error code, 454
ER_IB_MSG_585 error code, 450	ER_IB_MSG_631 error code, 454
ER_IB_MSG_586 error code, 450	ER_IB_MSG_632 error code, 454
ER_IB_MSG_587 error code, 450	ER_IB_MSG_633 error code, 455
ER_IB_MSG_588 error code, 450	ER_IB_MSG_634 error code, 455
ER_IB_MSG_589 error code, 450	ER_IB_MSG_635 error code, 455
ER_IB_MSG_59 error code, 395	ER_IB_MSG_636 error code, 455
ER_IB_MSG_590 error code, 450	ER_IB_MSG_637 error code, 455
ER_IB_MSG_591 error code, 450	ER_IB_MSG_638 error code, 455
ER_IB_MSG_592 error code, 450	ER_IB_MSG_639 error code, 455
ER_IB_MSG_593 error code, 451	ER_IB_MSG_64 error code, 396
ER_IB_MSG_594 error code, 451	ER_IB_MSG_640 error code, 455
ER_IB_MSG_595 error code, 451	ER_IB_MSG_641 error code, 455
ER_IB_MSG_596 error code, 451	ER_IB_MSG_642 error code, 456
ER_IB_MSG_597 error code, 451	ER_IB_MSG_643 error code, 456
ER_IB_MSG_598 error code, 451	ER_IB_MSG_644 error code, 456
ER_IB_MSG_599 error code, 451	ER_IB_MSG_645 error code, 456
ER_IB_MSG_6 error code, 390	ER_IB_MSG_646 error code, 456
ER_IB_MSG_60 error code, 395	ER_IB_MSG_647 error code, 456
ER_IB_MSG_600 error code, 451	ER_IB_MSG_648 error code, 456
ER_IB_MSG_601 error code, 451	ER_IB_MSG_649 error code, 456
ER_IB_MSG_602 error code, 451	ER_IB_MSG_65 error code, 396
ER_IB_MSG_603 error code, 452	ER_IB_MSG_650 error code, 456
ER_IB_MSG_604 error code, 452	ER_IB_MSG_651 error code, 456
ER_IB_MSG_605 error code, 452	ER_IB_MSG_652 error code, 457
ER_IB_MSG_606 error code, 452	ER_IB_MSG_653 error code, 457
ER_IB_MSG_607 error code, 452	ER_IB_MSG_654 error code, 457
ER_IB_MSG_608 error code, 452	ER_IB_MSG_655 error code, 457
ER_IB_MSG_609 error code, 452	ER_IB_MSG_656 error code, 457
ER_IB_MSG_61 error code, 395	ER_IB_MSG_657 error code, 457
ER_IB_MSG_610 error code, 452	ER_IB_MSG_658 error code, 457
ER_IB_MSG_611 error code, 452	ER_IB_MSG_659 error code, 457
ER_IB_MSG_612 error code, 452	ER_IB_MSG_66 error code, 396
ER_IB_MSG_613 error code, 453	ER_IB_MSG_660 error code, 457
ER_IB_MSG_614 error code, 453	ER_IB_MSG_661 error code, 458
ER_IB_MSG_615 error code, 453	ER_IB_MSG_662 error code, 458
ER_IB_MSG_616 error code, 453	ER_IB_MSG_663 error code, 458
ER_IB_MSG_617 error code, 453	ER_IB_MSG_664 error code, 458
ER_IB_MSG_618 error code, 453	ER_IB_MSG_665 error code, 458
ER_IB_MSG_619 error code, 453	ER_IB_MSG_666 error code, 458
ER_IB_MSG_62 error code, 396	ER_IB_MSG_667 error code, 458
ER_IB_MSG_620 error code, 453	ER_IB_MSG_668 error code, 458
ER_IB_MSG_621 error code, 453	ER_IB_MSG_669 error code, 458
ER_IB_MSG_622 error code, 453	ER_IB_MSG_67 error code, 396
ER_IB_MSG_623 error code, 454	ER_IB_MSG_670 error code, 459
	ER_IB_MSG_671 error code, 459
	ER_IB_MSG_672 error code, 459









---

ER\_IB\_MSG\_965 error code, 490  
 ER\_IB\_MSG\_966 error code, 490  
 ER\_IB\_MSG\_967 error code, 491  
 ER\_IB\_MSG\_968 error code, 491  
 ER\_IB\_MSG\_969 error code, 491  
 ER\_IB\_MSG\_97 error code, 399  
 ER\_IB\_MSG\_970 error code, 491  
 ER\_IB\_MSG\_971 error code, 491  
 ER\_IB\_MSG\_972 error code, 491  
 ER\_IB\_MSG\_973 error code, 491  
 ER\_IB\_MSG\_974 error code, 491  
 ER\_IB\_MSG\_975 error code, 491  
 ER\_IB\_MSG\_976 error code, 491  
 ER\_IB\_MSG\_977 error code, 492  
 ER\_IB\_MSG\_978 error code, 492  
 ER\_IB\_MSG\_979 error code, 492  
 ER\_IB\_MSG\_98 error code, 399  
 ER\_IB\_MSG\_980 error code, 492  
 ER\_IB\_MSG\_981 error code, 492  
 ER\_IB\_MSG\_982 error code, 492  
 ER\_IB\_MSG\_983 error code, 492  
 ER\_IB\_MSG\_984 error code, 492  
 ER\_IB\_MSG\_985 error code, 492  
 ER\_IB\_MSG\_986 error code, 492  
 ER\_IB\_MSG\_987 error code, 493  
 ER\_IB\_MSG\_988 error code, 493  
 ER\_IB\_MSG\_989 error code, 493  
 ER\_IB\_MSG\_99 error code, 399  
 ER\_IB\_MSG\_990 error code, 493  
 ER\_IB\_MSG\_991 error code, 493  
 ER\_IB\_MSG\_992 error code, 493  
 ER\_IB\_MSG\_993 error code, 493  
 ER\_IB\_MSG\_994 error code, 493  
 ER\_IB\_MSG\_995 error code, 493  
 ER\_IB\_MSG\_996 error code, 493  
 ER\_IB\_MSG\_997 error code, 494  
 ER\_IB\_MSG\_998 error code, 494  
 ER\_IB\_MSG\_999 error code, 494  
 ER\_IB\_MSG\_BAD\_DBLWR\_FILE\_NAME error code, 577  
 ER\_IB\_MSG\_BTREE\_LEVEL\_LIMIT\_EXCEEDED error code, 566  
 ER\_IB\_MSG\_BUF\_PENDING\_IO error code, 506  
 ER\_IB\_MSG\_BUF\_PENDING\_IO\_ON\_SHUTDOWN error code, 523  
 ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_CODE\_STATUS error code, 627  
 ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_COMPLETE\_CUR\_COPY error code, 627  
 ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_PROGRESS\_UPDATE error code, 627  
 ER\_IB\_MSG\_CANNOT\_FIND\_DD\_UNDO\_SPACE error code, 582  
 ER\_IB\_MSG\_CANNOT\_OPEN\_57\_UNDO error code, 503  
 ER\_IB\_MSG\_CANT\_DECRYPT\_REDO\_LOG error code, 478  
 ER\_IB\_MSG\_CANT\_ENCRYPT\_REDO\_LOG\_DATA error code, 478  
 ER\_IB\_MSG\_CLEAR\_INSTANT\_DROP\_COLUMN\_METADATA error code, 626  
 ER\_IB\_MSG\_CLOCK\_GETTIME\_FAILED error code, 563  
 ER\_IB\_MSG\_CLOCK\_MONOTONIC\_UNSUPPORTED error code, 563  
 ER\_IB\_MSG\_CLONE\_DDL\_APPLY error code, 607  
 ER\_IB\_MSG\_CLONE\_DDL\_INVALIDATE error code, 607  
 ER\_IB\_MSG\_CLONE\_DDL\_NTFN error code, 607  
 ER\_IB\_MSG\_CREATED\_UNDO\_SPACE error code, 591  
 ER\_IB\_MSG\_CREATE\_LOG\_FILE error code, 580  
 ER\_IB\_MSG\_DATA\_DIRECTORY\_NOT\_INITIALIZED\_OR\_CORRUPT error code, 509  
 ER\_IB\_MSG\_DBLWR\_1285 error code, 576  
 ER\_IB\_MSG\_DBLWR\_1286 error code, 576  
 ER\_IB\_MSG\_DBLWR\_1287 error code, 576  
 ER\_IB\_MSG\_DBLWR\_1288 error code, 576  
 ER\_IB\_MSG\_DBLWR\_1290 error code, 576  
 ER\_IB\_MSG\_DBLWR\_1291 error code, 576  
 ER\_IB\_MSG\_DBLWR\_1292 error code, 577  
 ER\_IB\_MSG\_DBLWR\_1293 error code, 577  
 ER\_IB\_MSG\_DBLWR\_1294 error code, 577  
 ER\_IB\_MSG\_DBLWR\_1295 error code, 577  
 ER\_IB\_MSG\_DBLWR\_1296 error code, 577  
 ER\_IB\_MSG\_DBLWR\_1297 error code, 577  
 ER\_IB\_MSG\_DBLWR\_1298 error code, 577  
 ER\_IB\_MSG\_DBLWR\_1300 error code, 577  
 ER\_IB\_MSG\_DBLWR\_1301 error code, 577  
 ER\_IB\_MSG\_DBLWR\_1304 error code, 578  
 ER\_IB\_MSG\_DBLWR\_1305 error code, 578  
 ER\_IB\_MSG\_DBLWR\_1306 error code, 578  
 ER\_IB\_MSG\_DBLWR\_1307 error code, 578  
 ER\_IB\_MSG\_DBLWR\_1308 error code, 578  
 ER\_IB\_MSG\_DBLWR\_1309 error code, 578  
 ER\_IB\_MSG\_DBLWR\_1310 error code, 578  
 ER\_IB\_MSG\_DBLWR\_1311 error code, 578  
 ER\_IB\_MSG\_DBLWR\_1312 error code, 578  
 ER\_IB\_MSG\_DBLWR\_1313 error code, 578  
 ER\_IB\_MSG\_DBLWR\_1314 error code, 579  
 ER\_IB\_MSG\_DBLWR\_1315 error code, 579  
 ER\_IB\_MSG\_DBLWR\_1316 error code, 579  
 ER\_IB\_MSG\_DBLWR\_1317 error code, 579  
 ER\_IB\_MSG\_DBLWR\_1318 error code, 579  
 ER\_IB\_MSG\_DBLWR\_1319 error code, 579  
 ER\_IB\_MSG\_DBLWR\_1320 error code, 579  
 ER\_IB\_MSG\_DBLWR\_1321 error code, 579

---

---

ER\_IB\_MSG\_DBLWR\_1322 error code, 579  
 ER\_IB\_MSG\_DBLWR\_1323 error code, 579  
 ER\_IB\_MSG\_DBLWR\_1324 error code, 580  
 ER\_IB\_MSG\_DBLWR\_1325 error code, 580  
 ER\_IB\_MSG\_DBLWR\_1326 error code, 580  
 ER\_IB\_MSG\_DBLWR\_1327 error code, 580  
 ER\_IB\_MSG\_DDL\_FAIL\_NO\_BUILDER error code, 641  
 ER\_IB\_MSG\_DDL\_LOG\_DELETE\_BY\_ID\_OK error code, 457  
 ER\_IB\_MSG\_DDL\_LOG\_DELETE\_BY\_ID\_TMCT error code, 560  
 ER\_IB\_MSG\_DDL\_LOG\_FAIL\_POST\_DDL error code, 560  
 ER\_IB\_MSG\_DEPRECATED\_INNODB\_UNDO\_TABLESPACE error code, 546  
 ER\_IB\_MSG\_DICT\_PARTITION\_NOT\_FOUND error code, 575  
 ER\_IB\_MSG\_DIR\_DOES\_NOT\_EXIST error code, 546  
 ER\_IB\_MSG\_DOWNGRADE\_PARTITION\_FILE error code, 574  
 ER\_IB\_MSG\_DROPPED\_UNDO\_SPACE error code, 591  
 ER\_IB\_MSG\_ERROR\_OPENING\_NEW\_UNDO\_SPACE error code, 544  
 ER\_IB\_MSG\_FAILED\_SDI\_Z\_BUF\_ERROR error code, 544  
 ER\_IB\_MSG\_FAILED\_SDI\_Z\_MEM\_ERROR error code, 544  
 ER\_IB\_MSG\_FAILED\_TO\_ALLOCATE\_WAIT error code, 544  
 ER\_IB\_MSG\_FAILED\_TO\_FINISH\_TRUNCATE error code, 545  
 ER\_IB\_MSG\_FAIL\_TO\_SAVE\_SPACE\_STATE error code, 544  
 ER\_IB\_MSG\_FILE\_RESIZE error code, 500  
 ER\_IB\_MSG\_FIL\_STATE\_MOVED\_CHANGED\_NAME error code, 574  
 ER\_IB\_MSG\_FIL\_STATE\_MOVED\_CHANGED\_PATH error code, 574  
 ER\_IB\_MSG\_FIL\_STATE\_MOVED\_CORRECTED error code, 574  
 ER\_IB\_MSG\_FIL\_STATE\_MOVED\_PREV error code, 642  
 ER\_IB\_MSG\_FIL\_STATE\_MOVED\_PREV\_OR\_HAS\_DATA error code, 642  
 ER\_IB\_MSG\_FIL\_STATE\_MOVED\_TOO\_MANY error code, 574  
 ER\_IB\_MSG\_FOUND\_WRONG\_UNDO\_SPACE error code, 545  
 ER\_IB\_MSG\_GENERAL\_TABLESPACE\_UNDER\_DATADIR error code, 430  
 ER\_IB\_MSG\_GTID\_FLUSH\_AT\_SHUTDOWN error code, 580  
 ER\_IB\_MSG\_IGNORE\_SCAN\_PATH error code, 428  
 ER\_IB\_MSG\_IMPLICIT\_TABLESPACE\_IN\_DATADIR error code, 430  
 ER\_IB\_MSG\_INCORRECT\_SIZE error code, 590  
 ER\_IB\_MSG\_INJECT\_CRASH error code, 589  
 ER\_IB\_MSG\_INJECT\_FAILURE error code, 589  
 ER\_IB\_MSG\_INNODB\_END\_INITIALIZE error code, 581  
 ER\_IB\_MSG\_INNODB\_START\_INITIALIZE error code, 581  
 ER\_IB\_MSG\_INVALID\_LOCATION\_FOR\_TABLE error code, 448  
 ER\_IB\_MSG\_INVALID\_LOCATION\_FOR\_TABLESPACE error code, 582  
 ER\_IB\_MSG\_INVALID\_LOCATION\_WRONG\_DB error code, 582  
 ER\_IB\_MSG\_INVALID\_PAGE\_TYPE error code, 628  
 ER\_IB\_MSG\_LOCK\_FREE\_HASH\_USAGE\_STATS error code, 546  
 ER\_IB\_MSG\_LOG\_CHECKPOINT\_FOUND error code, 618  
 ER\_IB\_MSG\_LOG\_CORRUPT error code, 462  
 ER\_IB\_MSG\_LOG\_FILES\_CANNOT\_ENCRYPT\_IN\_READ\_ONLY error code, 522  
 ER\_IB\_MSG\_LOG\_FILES\_CAPACITY\_CHANGED error code, 619  
 ER\_IB\_MSG\_LOG\_FILES\_CREATED\_BY\_CLONE error code, 466  
 ER\_IB\_MSG\_LOG\_FILES\_CREATED\_BY\_CLONE\_AND\_READ\_ONLY error code, 616  
 ER\_IB\_MSG\_LOG\_FILES\_CREATED\_BY\_MEB error code, 466  
 ER\_IB\_MSG\_LOG\_FILES\_CREATED\_BY\_MEB\_AND\_READ\_ONLY error code, 466  
 ER\_IB\_MSG\_LOG\_FILES\_CREATED\_BY\_UNKNOWN\_CREATOR error code, 620  
 ER\_IB\_MSG\_LOG\_FILES\_CREATE\_AND\_READ\_ONLY\_MODE error code, 501  
 ER\_IB\_MSG\_LOG\_FILES\_DIFFERENT\_SIZES error code, 509  
 ER\_IB\_MSG\_LOG\_FILES\_ENCRYPTION\_INIT\_FAILED error code, 522  
 ER\_IB\_MSG\_LOG\_FILES\_FOUND\_MISSING error code, 620  
 ER\_IB\_MSG\_LOG\_FILES\_INITIALIZED error code, 501  
 ER\_IB\_MSG\_LOG\_FILES\_INVALID\_SET error code, 509  
 ER\_IB\_MSG\_LOG\_FILES\_RESIZE\_CANCELLED error code, 619  
 ER\_IB\_MSG\_LOG\_FILES\_RESIZE\_FINISHED error code, 619  
 ER\_IB\_MSG\_LOG\_FILES\_RESIZE\_ON\_START error code, 519  
 ER\_IB\_MSG\_LOG\_FILES\_RESIZE\_ON\_START\_FAILED\_\_UNEXPECTED error code, 618

---

---

ER\_IB\_MSG\_LOG\_FILES\_RESIZE\_ON\_START\_IN\_READ\_ONLY\_MODE error code, 510  
 ER\_IB\_MSG\_LOG\_FILES\_RESIZE\_REQUESTED error code, 619  
 ER\_IB\_MSG\_LOG\_FILES\_REWRITING error code, 510  
 ER\_IB\_MSG\_LOG\_FILES\_UPGRADE error code, 619  
 ER\_IB\_MSG\_LOG\_FILE\_DIFFERENT\_FORMATS error code, 620  
 ER\_IB\_MSG\_LOG\_FILE\_FOREIGN\_UUID error code, 618  
 ER\_IB\_MSG\_LOG\_FILE\_FORMAT\_TOO\_NEW error code, 620  
 ER\_IB\_MSG\_LOG\_FILE\_FORMAT\_TOO\_OLD error code, 620  
 ER\_IB\_MSG\_LOG\_FILE\_FORMAT\_UNKNOWN error code, 463  
 ER\_IB\_MSG\_LOG\_FILE\_HEADER\_INVALID\_CHECKSUM error code, 524  
 ER\_IB\_MSG\_LOG\_FILE\_HEADER\_READ\_FAILED error code, 615  
 ER\_IB\_MSG\_LOG\_FILE\_INVALID\_LSN\_RANGES error code, 618  
 ER\_IB\_MSG\_LOG\_FILE\_INVALID\_START\_LSN error code, 618  
 ER\_IB\_MSG\_LOG\_FILE\_IS\_EMPTY error code, 615  
 ER\_IB\_MSG\_LOG\_FILE\_MARK\_AS\_UNUSED\_FAILED error code, 621  
 ER\_IB\_MSG\_LOG\_FILE\_MARK\_CURRENT\_AS\_INCOMPLETE error code, 619  
 ER\_IB\_MSG\_LOG\_FILE\_MISSING\_FOR\_ID error code, 618  
 ER\_IB\_MSG\_LOG\_FILE\_OPEN\_FAILED error code, 502  
 ER\_IB\_MSG\_LOG\_FILE\_OS\_CREATE\_FAILED error code, 500  
 ER\_IB\_MSG\_LOG\_FILE\_PREPARE\_ON\_CREATE\_FAILED error code, 501  
 ER\_IB\_MSG\_LOG\_FILE\_REMOVE\_FAILED error code, 619  
 ER\_IB\_MSG\_LOG\_FILE\_RENAME\_ON\_CREATE\_FAILED error code, 619  
 ER\_IB\_MSG\_LOG\_FILE\_RESIZE\_FAILED error code, 501  
 ER\_IB\_MSG\_LOG\_FILE\_SIZE\_INVALID error code, 509  
 ER\_IB\_MSG\_LOG\_FILE\_TOO\_BIG error code, 615  
 ER\_IB\_MSG\_LOG\_FILE\_TOO\_SMALL error code, 615  
 ER\_IB\_MSG\_LOG\_FILE\_TRUNCATE error code, 621  
 ER\_IB\_MSG\_LOG\_FILE\_UNUSED\_MARK\_AS\_IN\_USE\_FAILED error code, 621  
 ER\_IB\_MSG\_LOG\_FILE\_UNUSED\_REMOVE\_FAILED error code, 621  
 ER\_IB\_MSG\_LOG\_FILE\_UNUSED\_RENAME\_FAILED error code, 621  
 ER\_IB\_MSG\_LOG\_FILE\_UNUSED\_RESIZE\_FAILED error code, 621  
 ER\_IB\_MSG\_LOG\_FORMAT\_BEFORE\_5\_7\_9 error code, 525  
 ER\_IB\_MSG\_LOG\_FORMAT\_BEFORE\_8\_0\_30 error code, 463  
 ER\_IB\_MSG\_LOG\_FORMAT\_NOT\_SUPPORTED error code, 466  
 ER\_IB\_MSG\_LOG\_FORMAT\_OLD error code, 466  
 ER\_IB\_MSG\_LOG\_FORMAT\_OLD\_AND\_LOG\_CORRUPTED error code, 462  
 ER\_IB\_MSG\_LOG\_FORMAT\_OLD\_AND\_NO\_CLEAN\_SHUTDOWN error code, 462  
 ER\_IB\_MSG\_LOG\_INIT\_DIR\_LIST\_FAILED error code, 616  
 ER\_IB\_MSG\_LOG\_INIT\_DIR\_MISSING\_SUBDIR error code, 616  
 ER\_IB\_MSG\_LOG\_INIT\_DIR\_NOT\_EMPTY\_WONT\_INITIALIZE error code, 616  
 ER\_IB\_MSG\_LOG\_PARAMS\_CONCURRENCY\_MARGIN\_UNSAFE error code, 525  
 ER\_IB\_MSG\_LOG\_PARAMS\_DEDICATED\_SERVER\_IGNORED error code, 621  
 ER\_IB\_MSG\_LOG\_PARAMS\_FILE\_SIZE\_UNUSED error code, 617  
 ER\_IB\_MSG\_LOG\_PARAMS\_LEGACY\_USAGE error code, 621  
 ER\_IB\_MSG\_LOG\_PARAMS\_N\_FILES\_UNUSED error code, 617  
 ER\_IB\_MSG\_LOG\_PFS\_ACQUIRE\_SERVICES\_FAILED error code, 620  
 ER\_IB\_MSG\_LOG\_PFS\_CREATE\_TABLES\_FAILED error code, 620  
 ER\_IB\_MSG\_LOG\_PRE\_8\_0\_30\_MISSING\_FILE0 error code, 620  
 ER\_IB\_MSG\_LOG\_UPGRADE\_CLONED\_DB error code, 617  
 ER\_IB\_MSG\_LOG\_UPGRADE\_CORRUPTION\_\_UNEXPECTED error code, 617  
 ER\_IB\_MSG\_LOG\_UPGRADE\_FLUSH\_FAILED\_\_UNEXPECTED error code, 618  
 ER\_IB\_MSG\_LOG\_UPGRADE\_FORCED\_RECV error code, 617  
 ER\_IB\_MSG\_LOG\_UPGRADE\_IN\_READ\_ONLY\_MODE error code, 617  
 ER\_IB\_MSG\_LOG\_UPGRADE\_NON\_PERSISTED\_DD\_METADATA error code, 618  
 ER\_IB\_MSG\_LOG\_UPGRADE\_UNINITIALIZED\_FILES error code, 617  
 ER\_IB\_MSG\_LOG\_WRITER\_ABORTS\_LOG\_ARCHIVER error code, 521  
 ER\_IB\_MSG\_LOG\_WRITER\_ENTERED\_EXTRA\_MARGIN error code, 616

---

---

ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN error code, 617	ER_IB_MSG_RESUME_OP_FOR_SPACE error code, 538
ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE error code, 521	ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR error code, 586
ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER error code, 521	ER_IB_MSG_SDI_Z_STREAM_ERROR error code, 544
ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER error code, 625	ER_IB_MSG_SDI_Z_UNKNOWN_ERROR error code, 545
ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE error code, 616	ER_IB_MSG_SKIP_HIDDEN_DIR error code, 572
ER_IB_MSG_LOG_WRITER_WRITE_FAILED error code, 616	ER_IB_MSG_STATS_SAMPLING_TOO_LARGE error code, 596
ER_IB_MSG_MADVISE_FAILED error code, 543	ER_IB_MSG_THREAD_CONCURRENCY_CHANGED error code, 525
ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED error code, 543	ER_IB_MSG_TOO_LONG_PATH error code, 562
ER_IB_MSG_MASTER_KEY_ROTATED error code, 591	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED error code, 516
ER_IB_MSG_MAX_UNDO_SPACES_REACHED error code, 544	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED error code, 584
ER_IB_MSG_NOT_END_WITH_IBU error code, 545	ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME error code, 612
ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND error code, 538	ER_IB_MSG_UNDO_ALTERED_ACTIVE error code, 589
ER_IB_MSG_NUM_POOLS error code, 544	ER_IB_MSG_UNDO_ALTERED_INACTIVE error code, 589
ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS error code, 581	ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED error code, 607
ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION error code, 625	ER_IB_MSG_UNDO_INJECT_CRASH error code, 589
ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG error code, 605	ER_IB_MSG_UNDO_INJECT_FAILURE error code, 589
ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG error code, 605	ER_IB_MSG_UNDO_MARKED_ACTIVE error code, 588
ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER error code, 560	ER_IB_MSG_UNDO_MARKED_EMPTY error code, 589
ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT error code, 560	ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE error code, 513
ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE error code, 467	ER_IB_MSG_UNDO_TRUNCATE_COMPLETE error code, 514
ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND error code, 463	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE error code, 589
ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOGFILE error code, 616	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE error code, 514
ER_IB_MSG_RECOVERY_CORRUPT error code, 510	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE error code, 514
ER_IB_MSG_RECOVERY_IN_READ_ONLY error code, 467	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL error code, 589
ER_IB_MSG_RECOVERY_IS_NEEDED error code, 467	ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE error code, 513
ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG error code, 604	ER_IB_MSG_UNDO_TRUNCATE_START error code, 513
ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG_INDEX error code, 604	ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN error code, 589
ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE error code, 465	ER_IB_MSG_UNDO_TRUNC_BEFORE_UNDO_LOGGING error code, 545
ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE error code, 604	ER_IB_MSG_UNDO_TRUNC_BEFORE_DD_UPDATE error code, 545
ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY error code, 604	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE error code, 545

---

ER\_IB\_MSG\_UNDO\_TRUNK\_BEFORE\_RSEG error code, 545  
 ER\_IB\_MSG\_UNEXPECTED\_FILE\_EXISTS error code, 421  
 ER\_IB\_MSG\_UNPROTECTED\_LOCATION\_ALLOWED error code, 426  
 ER\_IB\_MSG\_UPGRADE\_PARTITION\_FILE error code, 574  
 ER\_IB\_MSG\_UPGRADE\_PARTITION\_FILE\_IMPORT error code, 574  
 ER\_IB\_MSG\_USING\_UNDO\_SPACE error code, 544  
 ER\_IB\_MSG\_WAIT\_FOR\_ENCRYPT\_THREAD error code, 537  
 ER\_IB\_MSG\_WRONG\_TABLESPACE\_DIR error code, 546  
 ER\_IB\_PARALLEL\_READER\_WORKER\_INFO error code, 628  
 ER\_IB\_PRIMARY\_KEY\_IS\_INSTANT error code, 632  
 ER\_IB\_RDBLWR\_BYTES\_INFO error code, 615  
 ER\_IB\_RECV\_FIRST\_REC\_GROUP\_INVALID error code, 562  
 ER\_IB\_RELOCK\_LATCH\_ORDER\_VIOLATION error code, 585  
 ER\_IB\_RESURRECT\_ACQUIRE\_TABLE\_LOCK error code, 635  
 ER\_IB\_RESURRECT\_IDENTIFY\_TABLE\_TO\_LOCK error code, 635  
 ER\_IB\_RESURRECT\_RECORD\_COMPLETE error code, 636  
 ER\_IB\_RESURRECT\_RECORD\_PROGRESS error code, 636  
 ER\_IB\_RESURRECT\_TRX\_INSERT error code, 635  
 ER\_IB\_RESURRECT\_TRX\_INSERT\_COMPLETE error code, 636  
 ER\_IB\_RESURRECT\_TRX\_UPDATE error code, 635  
 ER\_IB\_RESURRECT\_TRX\_UPDATE\_COMPLETE error code, 636  
 ER\_IB\_SELECT\_COUNT\_STAR error code, 634  
 ER\_IB\_TABLESPACE\_PATH\_VALIDATION\_SKIPPED error code, 584  
 ER\_IB\_TMP\_TABLESPACE\_CANNOT\_CREATE\_DIRECTORY error code, 586  
 ER\_IB\_UNABLE\_TO\_EXPAND\_TEMPORARY\_TABLESPACE error code, 586  
 ER\_IB\_WARN\_ACCESSING\_NONEXISTING\_SPACE error code, 419  
 ER\_IB\_WARN\_MANY\_NON\_LRU\_FILES\_OPENED error code, 612  
 ER\_IB\_WARN\_OPEN\_PARTITION\_FILE error code, 574  
 ER\_IB\_WRN\_ENCRYPTION\_INFO\_SIZE\_MISMATCH error code, 608  
 ER\_IB\_WRN\_FAILED\_TO\_ACQUIRE\_SERVICE error code, 598  
 ER\_IB\_WRN\_FAST\_SHUTDOWN\_REDO\_DISABLED error code, 583  
 ER\_IB\_WRN\_IGNORE\_REDO\_LOG\_CAPACITY error code, 632  
 ER\_IB\_WRN\_OLD\_GEOMETRY\_TYPE error code, 599  
 ER\_IB\_WRN\_PAGE\_ARCH\_FLUSH\_DATA error code, 581  
 ER\_IB\_WRN\_REDO\_DISABLED error code, 583  
 ER\_IB\_WRN\_REDO\_ENABLED error code, 584  
 ER\_IDENTIFIED\_BY\_UNSUPPORTED error code, 149  
 ER\_IDENT\_CAUSES\_TOO\_LONG\_PATH error code, 65  
 ER\_IDENT\_CAUSES\_TOO\_LONG\_PATH\_IN\_UPGRADE error code, 568  
 ER\_IF\_NOT\_EXISTS\_UNSUPPORTED\_TRG\_EXISTS\_ON\_DIFF error code, 155  
 ER\_IF\_NOT\_EXISTS\_UNSUPPORTED\_UDF\_NATIVE\_FCT\_NA error code, 155  
 ER\_ILLEGAL\_GRANT\_FOR\_TABLE error code, 13  
 ER\_ILLEGAL\_HA error code, 5  
 ER\_ILLEGAL\_HA\_CREATE\_OPTION error code, 36  
 ER\_ILLEGAL\_PRIVILEGE\_LEVEL error code, 98  
 ER\_ILLEGAL\_REFERENCE error code, 21  
 ER\_ILLEGAL\_USER\_VAR error code, 74  
 ER\_ILLEGAL\_VALUE\_FOR\_TYPE error code, 29  
 ER\_IMPLICIT\_COMPARISON\_FOR\_JSON error code, 140  
 ER\_IMPOSSIBLE\_STRING\_CONVERSION error code, 140  
 ER\_IMP\_INCOMPATIBLE\_CFG\_VERSION error code, 135  
 ER\_IMP\_INCOMPATIBLE\_DD\_VERSION error code, 98  
 ER\_IMP\_INCOMPATIBLE\_MYSQLD\_VERSION error code, 97  
 ER\_IMP\_INCOMPATIBLE\_SDI\_VERSION error code, 98  
 ER\_IMP\_NO\_FILES\_MATCHED error code, 97  
 ER\_IMP\_SCHEMA\_DOES\_NOT\_EXIST error code, 97  
 ER\_IMP\_TABLE\_ALREADY\_EXISTS error code, 97  
 ER\_INCONSISTENT\_ERROR error code, 528  
 ER\_INCONSISTENT\_PARTITION\_INFO\_ERROR error code, 37  
 ER\_INCONSISTENT\_TYPE\_OF\_FUNCTIONS\_ERROR error code, 37  
 ER\_INCORRECT\_CURRENT\_PASSWORD error code, 129  
 ER\_INCORRECT\_GLOBAL\_LOCAL\_VAR error code, 21  
 ER\_INCORRECT\_TYPE error code, 74  
 ER\_INDEX\_COLUMN\_TOO\_LONG error code, 51  
 ER\_INDEX\_CORRUPT error code, 52  
 ER\_INDEX\_OTHER\_THAN\_PK error code, 158  
 ER\_INDEX\_TYPE\_NOT\_SUPPORTED\_FOR\_SPATIAL\_INDEX error code, 110  
 ER\_INFORMATION\_SCHEMA\_VERSION\_CHANGE error code, 641

---

---

ER\_INIT\_BOOTSTRAP\_COMPLETE error code, 214  
 ER\_INIT\_CANT\_OPEN\_BOOTSTRAP\_FILE error code, 214  
 ER\_INIT\_CREATING\_DD error code, 215  
 ER\_INIT\_DATADIR\_EXISTS\_AND\_NOT\_WRITABLE\_WONT\_INITIALIZE error code, 215  
 ER\_INIT\_DATADIR\_EXISTS\_AND\_PATH\_TOO\_LONG\_WONT\_INITIALIZE error code, 215  
 ER\_INIT\_DATADIR\_EXISTS\_WONT\_INITIALIZE error code, 214  
 ER\_INIT\_DATADIR\_NOT\_EMPTY\_WONT\_INITIALIZE error code, 214  
 ER\_INIT\_FAILED\_TO\_GENERATE\_ROOT\_PASSWORD error code, 571  
 ER\_INIT\_GENERATING\_TEMP\_PASSWORD\_FOR\_ROOT error code, 214  
 ER\_INIT\_ROOT\_WITHOUT\_PASSWORD error code, 214  
 ER\_INNOODB\_ACTIVE\_INDEX\_CHANGE\_FAILED error code, 294  
 ER\_INNOODB\_AUTOEXTEND\_SIZE\_OUT\_OF\_RANGE error code, 145  
 ER\_INNOODB\_CANNOT\_BE\_IGNORED error code, 107  
 ER\_INNOODB\_CANNOT\_CREATE\_TABLE error code, 294  
 ER\_INNOODB\_CANT\_BUILD\_INDEX\_XLATION\_TABLE\_FOR error code, 274  
 ER\_INNOODB\_CANT\_FIND\_INDEX\_IN\_INNOODB\_DD error code, 273  
 ER\_INNOODB\_CANT\_OPEN\_TABLE error code, 274  
 ER\_INNOODB\_CLOSING\_CONNECTION\_ROLLS\_BACK error code, 273  
 ER\_INNOODB\_CLUSTERED\_INDEX\_PRIVATE error code, 274  
 ER\_INNOODB\_COMPRESSION\_FAILURE error code, 146  
 ER\_INNOODB\_DIFF\_IN\_REF\_LEN error code, 294  
 ER\_INNOODB\_DIRTY\_WATER\_MARK\_NOT\_LOW error code, 273  
 ER\_INNOODB\_ERROR\_LOGGER\_FATAL\_MSG error code, 297  
 ER\_INNOODB\_ERROR\_LOGGER\_MSG error code, 296  
 ER\_INNOODB\_FAILED\_TO\_FIND\_IDX error code, 294  
 ER\_INNOODB\_FAILED\_TO\_FIND\_IDX\_FROM\_DICT\_CACHER error code, 294  
 ER\_INNOODB\_FAILED\_TO\_FIND\_IDX\_WITH\_KEY\_NO error code, 294  
 ER\_INNOODB\_FILES\_SAME error code, 273  
 ER\_INNOODB\_FORCED\_RECOVERY error code, 67  
 ER\_INNOODB\_FT\_AUX\_NOT\_HEX\_ID error code, 67  
 ER\_INNOODB\_FT\_LIMIT error code, 59  
 ER\_INNOODB\_FT\_WRONG\_DOCID\_COLUMN error code, 59  
 ER\_INNOODB\_FT\_WRONG\_DOCID\_INDEX error code, 60  
 ER\_INNOODB\_IDX\_CNT\_FEWER\_THAN\_DEFINED\_IN\_MYSQL error code, 295  
 ER\_INNOODB\_IDX\_CNT\_MORE\_THAN\_DEFINED\_IN\_MYSQL error code, 295  
 ER\_INNOODB\_INDEX\_COLUMN\_CNT\_DIFF error code, 295  
 ER\_INNOODB\_ILLEGAL\_COLON\_IN\_POOL error code, 272  
 ER\_INNOODB\_IMPORT\_ERROR error code, 61  
 ER\_INNOODB\_INCOMPATIBLE\_WITH\_TABLESPACE error code, 145  
 ER\_INNOODB\_INDEX\_COLUMN\_INFO\_UNLIKE\_MYSQLS error code, 273  
 ER\_INNOODB\_INDEX\_CORRUPT error code, 61  
 ER\_INNOODB\_INSTANT\_ADD\_DROP\_NOT\_SUPPORTED\_MAX\_SIZE error code, 161  
 ER\_INNOODB\_INSTANT\_ADD\_NOT\_SUPPORTED\_MAX\_FIELDS error code, 161  
 ER\_INNOODB\_INSTANT\_ADD\_NOT\_SUPPORTED\_MAX\_SIZE error code, 154  
 ER\_INNOODB\_INTERNAL\_INDEX error code, 294  
 ER\_INNOODB\_INVALID\_AUTOEXTEND\_SIZE\_VALUE error code, 145  
 ER\_INNOODB\_INVALID\_INNOODB\_UNDO\_DIRECTORY error code, 272  
 ER\_INNOODB\_INVALID\_INNOODB\_UNDO\_DIRECTORY\_LOCATION error code, 547  
 ER\_INNOODB\_INVALID\_LOG\_GROUP\_HOME\_DIR error code, 272  
 ER\_INNOODB\_INVALID\_MONITOR\_COUNTER\_NAME error code, 295  
 ER\_INNOODB\_INVALID\_PAGE\_SIZE error code, 272  
 ER\_INNOODB\_IO\_CAPACITY\_EXCEEDS\_MAX error code, 273  
 ER\_INNOODB\_IO\_WRITE\_ERROR\_RETRYING error code, 592  
 ER\_INNOODB\_IO\_WRITE\_FAILED error code, 592  
 ER\_INNOODB\_MANDATORY error code, 171  
 ER\_INNOODB\_MAX\_ROW\_VERSION error code, 153  
 ER\_INNOODB\_MONITOR\_DEFAULT\_VALUE\_NOT\_DEFINED error code, 295  
 ER\_INNOODB\_MONITOR\_IS\_ENABLED error code, 295  
 ER\_INNOODB\_NO\_FT\_TEMP\_TABLE error code, 59  
 ER\_INNOODB\_ONLINE\_LOG\_TOO\_BIG error code, 60  
 ER\_INNOODB\_OUT\_OF\_RESOURCES error code, 575  
 ER\_INNOODB\_PARTITION\_TABLE\_LOWERCASED error code, 274  
 ER\_INNOODB\_PK\_NOT\_IN\_MYSQL error code, 274  
 ER\_INNOODB\_PK\_ONLY\_IN\_MYSQL error code, 274  
 ER\_INNOODB\_READ\_ONLY error code, 66  
 ER\_INNOODB\_REDO\_ARCHIVING\_ENABLED error code, 140  
 ER\_INNOODB\_REDO\_DISABLED error code, 140

---

ER\_INNOODB\_REDO\_LOG\_ARCHIVE\_ACTIVE error code, 124  
 ER\_INNOODB\_REDO\_LOG\_ARCHIVE\_DIRS\_INVALID error code, 123  
 ER\_INNOODB\_REDO\_LOG\_ARCHIVE\_DIR\_CLASH error code, 124  
 ER\_INNOODB\_REDO\_LOG\_ARCHIVE\_DIR\_EMPTY error code, 123  
 ER\_INNOODB\_REDO\_LOG\_ARCHIVE\_DIR\_PERMISSIONS error code, 124  
 ER\_INNOODB\_REDO\_LOG\_ARCHIVE\_FAILED error code, 124  
 ER\_INNOODB\_REDO\_LOG\_ARCHIVE\_FILE\_CREATE error code, 124  
 ER\_INNOODB\_REDO\_LOG\_ARCHIVE\_INACTIVE error code, 124  
 ER\_INNOODB\_REDO\_LOG\_ARCHIVE\_LABEL\_NOT\_FOUND error code, 123  
 ER\_INNOODB\_REDO\_LOG\_ARCHIVE\_NO\_SUCH\_DIR error code, 124  
 ER\_INNOODB\_REDO\_LOG\_ARCHIVE\_SESSION error code, 124  
 ER\_INNOODB\_REDO\_LOG\_ARCHIVE\_START\_SUBDIR\_PATH error code, 123  
 ER\_INNOODB\_REDO\_LOG\_ARCHIVE\_START\_TIMEOUT error code, 123  
 ER\_INNOODB\_TRX\_XLATION\_TABLE\_OOM error code, 273  
 ER\_INNOODB\_UNABLE\_TO\_ACQUIRE\_DD\_OBJECT error code, 581  
 ER\_INNOODB\_UNDO\_LOG\_FULL error code, 70  
 ER\_INNOODB\_UNKNOWN\_COLLATION error code, 272  
 ER\_INNOODB\_UNREGISTERED\_TRX\_ACTIVE error code, 273  
 ER\_INNOODB\_USE\_MONITOR\_GROUP\_NAME error code, 295  
 ER\_INSECURE\_CHANGE\_MASTER error code, 56  
 ER\_INSECURE\_CHANGE\_SOURCE error code, 56  
 ER\_INSECURE\_PLAIN\_TEXT error code, 56  
 ER\_INSERT\_INFO error code, 9  
 ER\_INSIDE\_TRANSACTION\_PREVENTS\_SWITCH\_BINLOG\_FORMAT error code, 49  
 ER\_INSIDE\_TRANSACTION\_PREVENTS\_SWITCH\_BINLOG\_FORMAT error code, 49  
 ER\_INSIDE\_TRANSACTION\_PREVENTS\_SWITCH\_SQL\_LOG\_BIN error code, 50  
 ER\_INSTALL\_COMPONENT\_SET\_NULL\_VALUE error code, 161  
 ER\_INSTALL\_COMPONENT\_SET\_UNUSED\_VALUE error code, 161  
 ER\_INSTALL\_PLUGIN\_CONFLICT\_CLIENT error code, 148  
 ER\_INSTALL\_PLUGIN\_CONFLICT\_LOG error code, 603  
 ER\_INTERNAL\_ERROR error code, 61  
 ER\_INTERSECT\_ALL\_MAX\_DUPLICATES\_EXCEEDED error code, 157  
 ER\_INVALID\_ADMIN\_ADDRESS error code, 549  
 ER\_INVALID\_ARGUMENT\_FOR\_LOGARITHM error code, 70  
 ER\_INVALID\_ASSIGNMENT\_TARGET error code, 148  
 ER\_INVALID\_AUTHENTICATION\_POLICY error code, 608  
 ER\_INVALID\_BITWISE\_AGGREGATE\_OPERANDS\_SIZE error code, 88  
 ER\_INVALID\_BITWISE\_OPERANDS\_SIZE error code, 88  
 ER\_INVALID\_CAST error code, 141  
 ER\_INVALID\_CAST\_POLYGON\_RING\_DIRECTION error code, 146  
 ER\_INVALID\_CAST\_TO\_GEOMETRY error code, 146  
 ER\_INVALID\_CAST\_TO\_JSON error code, 82  
 ER\_INVALID\_CHARACTER\_STRING error code, 25  
 ER\_INVALID\_CHARSET\_AND\_DEFAULT\_IS\_MB error code, 199  
 ER\_INVALID\_COLLATION\_FOR\_CHARSET error code, 270  
 ER\_INVALID\_DD\_OBJECT error code, 88  
 ER\_INVALID\_DD\_OBJECT\_ID error code, 88  
 ER\_INVALID\_DD\_OBJECT\_NAME error code, 88  
 ER\_INVALID\_DEFAULT error code, 8  
 ER\_INVALID\_DEFAULT\_UTF8MB4\_COLLATION error code, 109  
 ER\_INVALID\_ENCRYPTION\_OPTION error code, 85  
 ER\_INVALID\_ENCRYPTION\_REQUEST error code, 121  
 ER\_INVALID\_ERROR\_LOG\_NAME error code, 182  
 ER\_INVALID\_FIELD\_SIZE error code, 69  
 ER\_INVALID\_GEOJSON CRS\_NOT\_TOP\_LEVEL error code, 104  
 ER\_INVALID\_GEOJSON\_MISSING\_MEMBER error code, 74  
 ER\_INVALID\_GEOJSON\_UNSPECIFIED error code, 74  
 ER\_INVALID\_GEOJSON\_WRONG\_TYPE error code, 74  
 ER\_INVALID\_GROUP\_FUNC\_USE error code, 11  
 ER\_INVALID\_INDEX\_INFO\_IN\_FRM error code, 199  
 ER\_INVALID\_INSTRUMENT error code, 170  
 ER\_INVALID\_JSON\_ATTRIBUTE error code, 139  
 ER\_INVALID\_JSON\_BINARY\_DATA error code, 82  
 ER\_INVALID\_JSON\_CHARSET error code, 82  
 ER\_INVALID\_JSON\_CHARSET\_IN\_FUNCTION error code, 82  
 ER\_INVALID\_JSON\_DATA error code, 74  
 ER\_INVALID\_JSON\_PATH error code, 82  
 ER\_INVALID\_JSON\_PATH\_ARRAY\_CELL error code, 84  
 ER\_INVALID\_JSON\_PATH\_CHARSET error code, 82  
 ER\_INVALID\_JSON\_PATH\_WILDCARD error code, 82  
 ER\_INVALID\_JSON\_TEXT error code, 82

---

---

ER\_INVALID\_JSON\_TEXT\_IN\_PARAM error code, 82  
 ER\_INVALID\_JSON\_TYPE error code, 124  
 ER\_INVALID\_JSON\_VALUE\_FOR\_CAST error code, 83  
 ER\_INVALID\_JSON\_VALUE\_FOR\_FUNC\_INDEX error code, 130  
 ER\_INVALID\_MFA\_OPERATIONS\_FOR\_PASSWORDLESS\_USER error code, 150  
 ER\_INVALID\_MFA\_PLUGIN\_SPECIFIED error code, 149  
 ER\_INVALID\_MULTIPLE\_CLAUSES error code, 122  
 ER\_INVALID\_NAMED\_PIPE\_FULL\_ACCESS\_GROUP error code, 556  
 ER\_INVALID\_NO\_OF\_ARGS error code, 96  
 ER\_INVALID\_ON\_UPDATE error code, 25  
 ER\_INVALID\_OPTION\_CHARACTERS error code, 92  
 ER\_INVALID\_OPTION\_END\_CHARACTER error code, 92  
 ER\_INVALID\_OPTION\_KEY error code, 91  
 ER\_INVALID\_OPTION\_KEY\_VALUE\_PAIR error code, 92  
 ER\_INVALID\_OPTION\_START\_CHARACTER error code, 92  
 ER\_INVALID\_OPTION\_VALUE error code, 92  
 ER\_INVALID\_OR\_OLD\_TABLE\_OR\_DB\_NAME error code, 222  
 ER\_INVALID\_PARAMETER\_USE error code, 141  
 ER\_INVALID\_PLUGIN\_FOR\_REGISTRATION error code, 149  
 ER\_INVALID\_PROPERTY\_KEY error code, 552  
 ER\_INVALID\_REPLICATION\_TIMESTAMPS error code, 282  
 ER\_INVALID\_RPL\_WILD\_TABLE\_FILTER\_PATTERN error code, 74  
 ER\_INVALID\_SERVER\_DOWNGRADE\_NOT\_PATCH error code, 640  
 ER\_INVALID\_SERVER\_UPGRADE\_NOT\_LTS error code, 640  
 ER\_INVALID\_THREAD\_ID error code, 103  
 ER\_INVALID\_THREAD\_PRIORITY error code, 102  
 ER\_INVALID\_TIME\_ZONE\_INTERVAL error code, 141  
 ER\_INVALID\_TLS\_VERSION error code, 613  
 ER\_INVALID\_TYPE\_FOR\_JSON error code, 82  
 ER\_INVALID\_USER\_ATTRIBUTE\_JSON error code, 139  
 ER\_INVALID\_USER\_FOR\_REGISTRATION error code, 150  
 ER\_INVALID\_USE\_OF\_FORCE\_OPTION error code, 103  
 ER\_INVALID\_USE\_OF\_NULL error code, 13  
 ER\_INVALID\_VALUE\_FOR\_ENFORCE\_GTID\_CONSISTENCY error code, 166  
 ER\_INVALID\_VALUE\_OF\_BIND\_ADDRESSES error code, 539  
 ER\_INVALID\_VCPU\_ID error code, 102  
 ER\_INVALID\_VCPU\_RANGE error code, 102  
 ER\_INVALID\_XPLUGIN\_SOCKET\_SAME\_AS\_SERVER error code, 581  
 ER\_INVALID\_YEAR\_COLUMN\_LENGTH error code, 62  
 ER\_IO\_ERR\_LOG\_INDEX\_READ error code, 30  
 ER\_IO\_READ\_ERROR error code, 61  
 ER\_IO\_WRITE\_ERROR error code, 61  
 ER\_IPSOCK\_ERROR error code, 9  
 ER\_IS\_QUERY\_INVALID\_CLAUSE error code, 91  
 ER\_I\_S\_SKIPPED\_TABLESPACE error code, 101  
 ER\_JSON\_BAD\_ONE\_OR\_ALL\_ARG error code, 83  
 ER\_JSON\_DOCUMENT\_NULL\_KEY error code, 83  
 ER\_JSON\_DOCUMENT\_TOO\_DEEP error code, 83  
 ER\_JSON\_KEY\_TOO\_BIG error code, 82  
 ER\_JSON\_PARSE\_ERROR error code, 184  
 ER\_JSON\_SCHEMA\_VALIDATION\_ERROR\_WITH\_DETAILED\_REPORT error code, 134  
 ER\_JSON\_USED\_AS\_KEY error code, 83  
 ER\_JSON\_VACUOUS\_PATH error code, 83  
 ER\_JSON\_VALUE\_OUT\_OF\_RANGE\_FOR\_FUNC\_INDEX error code, 130  
 ER\_JSON\_VALUE\_TOO\_BIG error code, 82  
 ER\_JT\_MAX\_NESTED\_PATH error code, 104  
 ER\_JT\_VALUE\_OUT\_OF\_RANGE error code, 104  
 ER\_KERBEROS\_CREATE\_USER error code, 148  
 ER\_KEYCACHE\_OOM error code, 174  
 ER\_KEYRING\_ACCESS\_DENIED\_ERROR error code, 86  
 ER\_KEYRING\_AWS\_CMK\_ID\_NOT\_SET error code, 340  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ACCESS\_DATA\_FILE error code, 340  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ACCESS\_KEY\_FROM\_CONF\_FILE error code, 339  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ACCESS\_KEY\_ID\_FROM\_CONF\_FILE error code, 339  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ACCESS\_OR\_CREATE\_KEYRING error code, 339  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ACCESS\_OR\_CREATE\_KEYRING error code, 339  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ACCESS\_OR\_CREATE\_KEYRING error code, 339  
 ER\_KEYRING\_AWS\_FAILED\_TO\_CONNECT\_KMS error code, 341  
 ER\_KEYRING\_AWS\_FAILED\_TO\_DECRYPT\_KEY error code, 342  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ENCRYPT\_KEY error code, 341  
 ER\_KEYRING\_AWS\_FAILED\_TO\_FLUSH\_KEYRING\_TO\_FILE error code, 341  
 ER\_KEYRING\_AWS\_FAILED\_TO\_GENERATE\_KEY\_DUE\_TO\_INTERRUPT error code, 340  
 ER\_KEYRING\_AWS\_FAILED\_TO\_GENERATE\_NEW\_KEY error code, 341  
 ER\_KEYRING\_AWS\_FAILED\_TO\_GET\_KMS\_CREDENTIAL\_FROM error code, 340



---

ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR error code, 339	ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP_FILE error code, 337
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTERNAL_ERROR error code, 340	ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_PLUGIN_ERROR error code, 338
ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE error code, 338	ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_FILE error code, 336
ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE error code, 341	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INTERNAL_ERROR error code, 338
ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY error code, 341	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE error code, 338
ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK error code, 342	ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR error code, 337
ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID error code, 338	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID error code, 337
ER_KEYRING_AWS_FAILED_TO_SET_REGION error code, 338	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG error code, 338
ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE error code, 341	ER_KEYRING_FAILED_TO_CREATE_KEYRING_DIR error code, 331
ER_KEYRING_AWS_INCORRECT_FILE error code, 340	ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE error code, 332
ER_KEYRING_AWS_INCORRECT_PROXY error code, 569	ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING error code, 333
ER_KEYRING_AWS_INCORRECT_REGION error code, 341	ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP error code, 333
ER_KEYRING_AWS_INIT_FAILURE error code, 340	ER_KEYRING_FAILED_TO_GENERATE_KEY error code, 331
ER_KEYRING_AWS_INVALID_CONF_FILE_PATH error code, 339	ER_KEYRING_FAILED_TO_GET_FILE_STAT error code, 332
ER_KEYRING_AWS_INVALID_DATA_FILE_PATH error code, 339	ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT error code, 333
ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER error code, 340	ER_KEYRING_FAILED_TO_REMOVE_FILE error code, 332
ER_KEYRING_AWS_UDF_AWS_KMS_ERROR error code, 86	ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_KEYRING error code, 333
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEYRING error code, 331	ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE error code, 332
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY error code, 331	ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA error code, 332
ER_KEYRING_COMPONENT_EXCEPTION error code, 597	ER_KEYRING_FAILED_TO_TRUNCATE_FILE error code, 332
ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR error code, 597	ER_KEYRING_FILE_INIT_FAILED error code, 331
ER_KEYRING_COMPONENT_NOT_INITIALIZED error code, 597	ER_KEYRING_FILE_IO_ERROR error code, 333
ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILED error code, 337	ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE error code, 332
ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED error code, 337	ER_KEYRING_INCORRECT_FILE error code, 332
ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEYRING error code, 337	ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE_INIT error code, 331
ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING error code, 337	ER_KEYRING_INVALID_KEY_LENGTH error code, 331
ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING error code, 337	ER_KEYRING_INVALID_KEY_TYPE error code, 330
ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_ROTATE_CMK error code, 337	ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEYRING error code, 333
ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING error code, 337	ER_KEYRING_LOGGER_ERROR_MSG error code, 313
	ER_KEYRING_MIGRATE_FAILED error code, 527

---

---

ER\_KEYRING\_MIGRATION\_EXTRA\_OPTIONS error code, 389  
 ER\_KEYRING\_MIGRATION\_FAILED error code, 299  
 ER\_KEYRING\_MIGRATION\_FAILURE error code, 86  
 ER\_KEYRING\_MIGRATION\_STATUS error code, 86  
 ER\_KEYRING\_MIGRATION\_SUCCESSFUL error code, 299  
 ER\_KEYRING\_OCI\_HTTP\_REQUEST error code, 627  
 ER\_KEYRING\_OCI\_INVALID\_JSON error code, 627  
 ER\_KEYRING\_OCI\_PARSE\_JSON error code, 627  
 ER\_KEYRING\_OKV\_CONNECTION\_TO\_SERVER\_FAILED error code, 335  
 ER\_KEYRING\_OKV\_FAILED\_TO\_ACTIVATE\_KEYS error code, 335  
 ER\_KEYRING\_OKV\_FAILED\_TO\_ADD\_ATTRIBUTE error code, 335  
 ER\_KEYRING\_OKV\_FAILED\_TO\_FETCH\_KEY error code, 335  
 ER\_KEYRING\_OKV\_FAILED\_TO\_FIND\_SERVER\_ENTRY error code, 334  
 ER\_KEYRING\_OKV\_FAILED\_TO\_FIND\_STANDBY\_SERVER error code, 334  
 ER\_KEYRING\_OKV\_FAILED\_TO\_GENERATE\_KEY error code, 335  
 ER\_KEYRING\_OKV\_FAILED\_TO\_GENERATE\_KEY\_DUE\_TO\_INTERNAL\_ERROR error code, 334  
 ER\_KEYRING\_OKV\_FAILED\_TO\_INIT\_CLIENT error code, 335  
 ER\_KEYRING\_OKV\_FAILED\_TO\_INIT\_SSL\_LAYER error code, 335  
 ER\_KEYRING\_OKV\_FAILED\_TO\_LOAD\_KEY\_UID error code, 334  
 ER\_KEYRING\_OKV\_FAILED\_TO\_LOAD\_SSL\_TRUST\_STORE error code, 336  
 ER\_KEYRING\_OKV\_FAILED\_TO\_PARSE\_CONF\_FILE error code, 334  
 ER\_KEYRING\_OKV\_FAILED\_TO\_REMOVE\_KEY error code, 335  
 ER\_KEYRING\_OKV\_FAILED\_TO\_RETRIEVE\_KEY error code, 336  
 ER\_KEYRING\_OKV\_FAILED\_TO\_RETRIEVE\_KEY\_SIGNATURE error code, 336  
 ER\_KEYRING\_OKV\_FAILED\_TO\_SET\_CERTIFICATE\_FILE error code, 336  
 ER\_KEYRING\_OKV\_FAILED\_TO\_SET\_KEY\_FILE error code, 336  
 ER\_KEYRING\_OKV\_FAILED\_TO\_STORE\_KEY error code, 335  
 ER\_KEYRING\_OKV\_FAILED\_TO\_STORE\_OR\_GENERATE\_KEY error code, 336  
 ER\_KEYRING\_OKV\_INCORRECT\_KEY\_VAULT\_CONFIGURATION error code, 333  
 ER\_KEYRING\_OKV\_INIT\_FAILED\_DUE\_TO\_INCORRECT\_CONFIGURATION error code, 333  
 ER\_KEYRING\_OKV\_INIT\_FAILED\_DUE\_TO\_INTERNAL\_ERROR error code, 334  
 ER\_KEYRING\_OKV\_INVALID\_KEY\_LENGTH\_FOR\_CIPHER error code, 334  
 ER\_KEYRING\_OKV\_INVALID\_KEY\_TYPE error code, 334  
 ER\_KEYRING\_OKV\_KEY\_MISMATCH error code, 336  
 ER\_KEYRING\_OKV\_STANDBY\_SERVER\_COUNT\_EXCEEDED error code, 613  
 ER\_KEYRING\_OPERATION\_FAILED\_DUE\_TO\_INTERNAL\_ERROR error code, 331  
 ER\_KEYRING\_UDF\_KEYRING\_SERVICE\_ERROR error code, 85  
 ER\_KEYRING\_UNKNOWN\_ERROR error code, 332  
 ER\_KEY\_COLUMN\_DOES\_NOT\_EXISTS error code, 8  
 ER\_KEY\_DOES\_NOT\_EXISTS error code, 15  
 ER\_KEY\_NOT\_FOUND error code, 5  
 ER\_KEY\_PART\_0 error code, 30  
 ER\_KEY\_REF\_DO\_NOT\_MATCH\_TABLE\_REF error code, 21  
 ER\_KEYRING\_THREADS\_OF\_PLUGIN error code, 217  
 ER\_KILLING\_THREAD error code, 216  
 ER\_KILL\_DENIED\_ERROR error code, 10  
 ER\_LATITUDE\_OUT\_OF\_RANGE error code, 98  
 ER\_LISTENER\_ALREADY\_EXISTS error code, 299  
 ER\_LCTN\_NOT\_FOUND error code, 527  
 ER\_LDAP\_AUTH\_CERTIFICATE\_NAME error code, 382  
 ER\_LDAP\_AUTH\_COMMUNICATION\_HOST\_INFO error code, 385  
 ER\_LDAP\_AUTH\_CONNECTION\_CREATOR\_ENTER error code, 385  
 ER\_LDAP\_AUTH\_CONNECTION\_GET\_LDAP\_INFO\_NULL\_OR\_0 error code, 385  
 ER\_LDAP\_AUTH\_CONNECTION\_POOL\_INIT\_FAILED error code, 383  
 ER\_LDAP\_AUTH\_CONNECTION\_POOL\_REINIT\_ENTER error code, 387  
 ER\_LDAP\_AUTH\_CONNECTION\_PUSHED\_TO\_POOL error code, 385  
 ER\_LDAP\_AUTH\_CONN\_POOL\_DEINITIALIZING error code, 381  
 ER\_LDAP\_AUTH\_CONN\_POOL\_INITIALIZING error code, 381  
 ER\_LDAP\_AUTH\_CONN\_POOL\_NOT\_CREATED error code, 380  
 ER\_LDAP\_AUTH\_CREATE\_CONNECTION\_KEY error code, 385  
 ER\_LDAP\_AUTH\_CREATING\_LDAP\_CONNECTION\_ERROR error code, 384  
 ER\_LDAP\_AUTH\_DEINIT\_FAILED error code, 380  
 ER\_LDAP\_AUTH\_DELETING\_CONNECTION\_KEY error code, 385  
 ER\_LDAP\_AUTH\_DISTINGUISHED\_NAME error code, 386

---

ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION error code, 387	ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT error code, 383
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT error code, 380	ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED error code, 384
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT error code, 380	ER_LDAP_AUTH_METHOD_TO_CLIENT error code, 385
ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION error code, 380	ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP error code, 382
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY error code, 383	ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED error code, 386
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONNECT error code, 383	ER_LDAP_AUTH_PAUSE_FAILED_TO_READ_PACKET error code, 384
ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION error code, 387	ER_LDAP_AUTH_POOLED_CONNECTION_KEY error code, 385
ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PENDING error code, 383	ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO error code, 380
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT error code, 383	ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION error code, 387
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT error code, 383	ER_LDAP_AUTH_POOL_REINITIALIZING error code, 381
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONNECT error code, 383	ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL error code, 384
ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT error code, 382	ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO error code, 386
ER_LDAP_AUTH_FAILED_TO_SEARCH_DN error code, 387	ER_LDAP_AUTH_SASL_PROCESS_SASL error code, 386
ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET error code, 381	ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT error code, 386
ER_LDAP_AUTH_FREEING_CONNECTION error code, 384	ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME error code, 382
ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL error code, 384	ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND error code, 384
ER_LDAP_AUTH_GRP_DN_PARSING_FAILED error code, 554	ER_LDAP_AUTH_SETTING_USERNAME error code, 381
ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE error code, 554	ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH error code, 380
ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS error code, 554	ER_LDAP_AUTH_STARTED_FOR_USER error code, 386
ER_LDAP_AUTH_GRP_IS_FULL_DN error code, 382	ER_LDAP_AUTH_STARTING_TLS error code, 385
ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE error code, 554	ER_LDAP_AUTH_TLS_CONF error code, 380
ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO error code, 554	ER_LDAP_AUTH_TLS_CONNECTION error code, 380
ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL error code, 553	ER_LDAP_AUTH_USER_AUTH_DATA error code, 381
ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL error code, 382	ER_LDAP_AUTH_USER_BIND_FAILED error code, 386
ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO error code, 554	ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS error code, 382
ER_LDAP_AUTH_INFO_FOR_USER error code, 381	ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED error code, 386
ER_LDAP_AUTH_INIT_FAILED error code, 386	ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO error code, 381
ER_LDAP_AUTH_LDAPS error code, 554	ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND error code, 542
ER_LDAP_AUTH_LDAP_INFO_NULL error code, 384	ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES error code, 382

---

---

ER\_LDAP\_AUTH\_USER\_NOT\_FOUND\_IN\_ANY\_GRP error code, 382  
 ER\_LDAP\_AUTH\_ZERO\_MAX\_POOL\_SIZE\_UNCHANGED error code, 381  
 ER\_LDAP\_EMPTY\_USERDN\_PASSWORD error code, 565  
 ER\_LDAP\_MAPPING\_CHECK\_DELIMI\_QUOTE error code, 555  
 ER\_LDAP\_MAPPING\_EMPTY\_MAPPING error code, 555  
 ER\_LDAP\_MAPPING\_GETTING\_NEXT\_MAPPING error code, 556  
 ER\_LDAP\_MAPPING\_GET\_USER\_PROXY error code, 554  
 ER\_LDAP\_MAPPING\_INFO error code, 555  
 ER\_LDAP\_MAPPING\_IS\_QUOTE error code, 556  
 ER\_LDAP\_MAPPING\_NON\_DESIRED\_STATE error code, 556  
 ER\_LDAP\_MAPPING\_NO\_SEPEARATOR\_END\_OF\_GROUP error code, 555  
 ER\_LDAP\_MAPPING\_PARSING\_CURRENT\_STATE error code, 556  
 ER\_LDAP\_MAPPING\_PARSING\_ERROR error code, 556  
 ER\_LDAP\_MAPPING\_PARSING\_MAPPING\_INFO error code, 556  
 ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER error code, 555  
 ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_COMMA\_NOT\_FOUND error code, 555  
 ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_EQUAL\_NOT\_FOUND error code, 555  
 ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_TRY\_COMMA error code, 555  
 ER\_LDAP\_MAPPING\_PROCESS\_MAPPING error code, 555  
 ER\_LDAP\_MAPPING\_TRIMMING\_SPACES error code, 556  
 ER\_LDAP\_MAPPING\_USER\_DONT\_BELONG\_GROUP error code, 554  
 ER\_LIMITED\_PART\_RANGE error code, 39  
 ER\_LOAD\_BULK\_DATA\_FAILED error code, 160  
 ER\_LOAD\_BULK\_DATA\_UNSORTED error code, 158  
 ER\_LOAD\_BULK\_DATA\_WARN\_NULL\_TO\_NOTNULL error code, 161  
 ER\_LOAD\_BULK\_DATA\_WARN\_NULL\_TO\_NOTNULL\_LOG error code, 631  
 ER\_LOAD\_BULK\_DATA\_WRONG\_VALUE\_FOR\_FIELD error code, 161  
 ER\_LOAD\_BULK\_DATA\_WRONG\_VALUE\_FOR\_FIELD\_LOG error code, 631  
 ER\_LOAD\_DATA\_INFILE\_FAILED\_IN\_UNEXPECTED\_WARN error code, 185  
 ER\_LOAD\_FROM\_FIXED\_SIZE\_ROWS\_TO\_VAR error code, 32  
 ER\_LOAD\_INFO error code, 9  
 ER\_LOCAL\_VARIABLE error code, 20  
 ER\_LOCKING\_SERVICE\_DEADLOCK error code, 81  
 ER\_LOCKING\_SERVICE\_TIMEOUT error code, 81  
 ER\_LOCKING\_SERVICE\_WRONG\_NAME error code, 81  
 ER\_LOCK\_ABORTED error code, 50  
 ER\_LOCK\_DEADLOCK error code, 18  
 ER\_LOCK\_NOWAIT error code, 93  
 ER\_LOCK\_ORDER\_DEPENDENCIES\_SYNTAX error code, 565  
 ER\_LOCK\_ORDER\_FAILED\_READ\_FILE error code, 565  
 ER\_LOCK\_ORDER\_FAILED\_WRITE\_FILE error code, 565  
 ER\_LOCK\_ORDER\_INIT\_FAILED error code, 563  
 ER\_LOCK\_ORDER\_MESSAGE error code, 565  
 ER\_LOCK\_ORDER\_SCANNER\_SYNTAX error code, 565  
 ER\_LOCK\_OR\_ACTIVE\_TRANSACTION error code, 16  
 ER\_LOCK\_REFUSED\_BY\_ENGINE error code, 84  
 ER\_LOCK\_TABLE\_FULL error code, 18  
 ER\_LOCK\_WAIT\_TIMEOUT error code, 18  
 ER\_LOG\_BIN\_BETTER\_WITH\_NAME error code, 179  
 ER\_LOG\_CANNOT\_PURGE\_BINLOG\_WITH\_BACKUP\_LOCK error code, 639  
 ER\_LOG\_CANNOT\_WRITE error code, 163  
 ER\_LOG\_CANNOT\_WRITE\_EXTENDED error code, 569  
 ER\_LOG\_COMPONENT\_CANNOT\_INIT error code, 592  
 ER\_LOG\_COMPONENT\_FLUSH\_FAILED error code, 604  
 ER\_LOG\_FILES\_GIVEN\_LOG\_OUTPUT\_IS\_TABLE error code, 178  
 ER\_LOG\_FILE\_CANNOT\_OPEN error code, 321  
 ER\_LOG\_FILE\_INVALID error code, 179  
 ER\_LOG\_GENERAL\_CANNOT\_OPEN error code, 163  
 ER\_LOG\_IN\_USE error code, 30  
 ER\_LOG\_OUTPUT\_CONTRADICTION error code, 178  
 ER\_LOG\_PRINTF\_MSG error code, 297  
 ER\_LOG\_PRIV\_CHECKS\_REQUIRE\_ROW\_FORMAT\_NOT\_SET error code, 573  
 ER\_LOG\_PURGE\_NO\_FILE error code, 44  
 ER\_LOG\_PURGE\_UNKNOWN\_ERR error code, 30  
 ER\_LOG\_SLOW\_CANNOT\_OPEN error code, 163  
 ER\_LOG\_SYSLOG\_CANNOT\_OPEN error code, 163  
 ER\_LOG\_SYSLOG\_FACILITY\_FAIL error code, 163  
 ER\_LOG\_LONGITUDE\_OUT\_OF\_RANGE error code, 98  
 ER\_LOWER\_CASE\_TABLE\_NAMES\_CS\_DD\_ON\_CI\_FS\_UNSUPPORTED error code, 179  
 ER\_LOWER\_CASE\_TABLE\_NAMES\_USING\_0 error code, 179

---

ER\_LOWER\_CASE\_TABLE\_NAMES\_USING\_2 error code, 179  
 ER\_MALFORMED\_GTID\_SET\_ENCODING error code, 57  
 ER\_MALFORMED\_GTID\_SET\_SPECIFICATION error code, 57  
 ER\_MALFORMED\_GTID\_SPECIFICATION error code, 57  
 ER\_MALFORMED\_PACKET error code, 63  
 ER\_MANDATORY\_ROLE error code, 99  
 ER\_MASTER error code, 16  
 ER\_MASTER\_DELAY\_VALUE\_OUT\_OF\_RANGE error code, 53  
 ER\_MASTER\_FATAL\_ERROR\_READING\_BINLOG error code, 20  
 ER\_MASTER\_HAS\_PURGED\_REQUIRED\_GTIDS error code, 59  
 ER\_MASTER\_INFO error code, 17  
 ER\_MASTER\_KEY\_ROTATION\_BINLOG\_FAILED error code, 85  
 ER\_MASTER\_KEY\_ROTATION\_NOT\_SUPPORTED\_BY\_SLAVE error code, 85  
 ER\_MASTER\_KEY\_ROTATION\_SE\_UNAVAILABLE error code, 85  
 ER\_MASTER\_NET\_READ error code, 16  
 ER\_MASTER\_NET\_WRITE error code, 16  
 ER\_MAXVALUE\_IN\_VALUES\_IN error code, 47  
 ER\_MAX\_PREPARED\_STMT\_COUNT\_REACHED error code, 35  
 ER\_MDL\_OUT\_OF\_RESOURCES error code, 140  
 ER\_MECAB\_CHARSET\_LOADED error code, 303  
 ER\_MECAB\_CREATE\_LATTICE\_FAILED error code, 303  
 ER\_MECAB\_CREATING\_MODEL error code, 302  
 ER\_MECAB\_FAILED\_TO\_CREATE\_MODEL error code, 302  
 ER\_MECAB\_FAILED\_TO\_CREATE\_TRIGGER error code, 303  
 ER\_MECAB\_NOT\_SUPPORTED error code, 302  
 ER\_MECAB\_NOT\_VERIFIED error code, 302  
 ER\_MECAB\_OOM\_WHILE\_PARSING\_TEXT error code, 303  
 ER\_MECAB\_PARSE\_FAILED error code, 303  
 ER\_MECAB\_UNSUPPORTED\_CHARSET error code, 303  
 ER\_MESSAGE\_AND\_STATEMENT error code, 48  
 ER\_MFA\_METHODS\_IDENTICAL error code, 150  
 ER\_MFA\_METHODS\_INVALID\_ORDER error code, 150  
 ER\_MFA\_METHOD\_EXISTS error code, 149  
 ER\_MFA\_METHOD\_NOT\_EXISTS error code, 149  
 ER\_MFA\_PLUGIN\_NOT\_LOADED error code, 611  
 ER\_MFA\_USER\_ATTRIBUTES\_CORRUPT error code, 611  
 ER\_MICROSECOND\_TIMER\_IS\_NOT\_AVAILABLE error code, 293  
 ER\_MIGRATE\_TABLE\_TO\_DD\_OOM error code, 576  
 ER\_MISPLACED\_INTO error code, 136  
 ER\_MISSING\_ACL\_SYSTEM\_TABLE error code, 284  
 ER\_MISSING\_CURRENT\_PASSWORD error code, 129  
 ER\_MISSING\_GRANT\_SYSTEM\_TABLE error code, 284  
 ER\_MISSING\_HA\_CREATE\_OPTION error code, 69  
 ER\_MISSING\_JSON\_TABLE\_VALUE error code, 103  
 ER\_MISSING\_JSON\_VALUE error code, 137  
 ER\_MISSING\_KEY error code, 68  
 ER\_MISSING\_SKIP\_REPLICA error code, 24  
 ER\_MISSING\_SKIP\_SLAVE error code, 23  
 ER\_MISSING\_TABLESPACE\_FILE error code, 99  
 ER\_MIXING\_NOT\_ALLOWED error code, 19  
 ER\_MIX\_HANDLER\_ERROR error code, 37  
 ER\_MIX\_OF\_GROUP\_FUNC\_AND\_FIELDS error code, 13  
 ER\_MIX\_OF\_GROUP\_FUNC\_AND\_FIELDS\_V2 error code, 77  
 ER\_MTA\_CANT\_PARALLEL error code, 55  
 ER\_MTA\_CHANGE\_SOURCE\_CANT\_RUN\_WITH\_GAPS error code, 60  
 ER\_MTA\_EVENT\_BIGGER\_PENDING\_JOBS\_SIZE\_MAX error code, 65  
 ER\_MTA\_FEATURE\_IS\_NOT\_SUPPORTED error code, 55  
 ER\_MTA\_INCONSISTENT\_DATA error code, 56  
 ER\_MTA\_RECOVERY\_FAILURE error code, 60  
 ER\_MTA\_RESET\_WORKERS error code, 60  
 ER\_MTA\_UPDATED\_DBS\_GREATER\_MAX error code, 55  
 ER\_MTR\_MSG\_1 error code, 605  
 ER\_MTS\_CANT\_PARALLEL error code, 55  
 ER\_MTS\_CHANGE\_MASTER\_CANT\_RUN\_WITH\_GAPS error code, 60  
 ER\_MTS\_EVENT\_BIGGER\_PENDING\_JOBS\_SIZE\_MAX error code, 65  
 ER\_MTS\_FEATURE\_IS\_NOT\_SUPPORTED error code, 55  
 ER\_MTS\_INCONSISTENT\_DATA error code, 55  
 ER\_MTS\_RECOVERY\_FAILURE error code, 60  
 ER\_MTS\_RESET\_WORKERS error code, 60  
 ER\_MTS\_UPDATED\_DBS\_GREATER\_MAX error code, 55  
 ER\_MULTIPLE\_CONSTRAINTS\_WITH\_SAME\_NAME error code, 134  
 ER\_MULTIPLE\_DEF\_CONST\_IN\_LIST\_PART\_ERROR error code, 37  
 ER\_MULTIPLE\_INTO\_CLAUSES error code, 136  
 ER\_MULTIPLE\_JSON\_VALUES error code, 138  
 ER\_MULTIPLE\_PRI\_KEY error code, 8  
 ER\_MULTI\_UPDATE\_KEY\_CONFLICT error code, 51

---

---

ER\_MUST\_CHANGE\_EXPIRED\_PASSWORD error code, 279  
 ER\_MUST\_CHANGE\_PASSWORD error code, 62  
 ER\_MUST\_CHANGE\_PASSWORD\_LOGIN error code, 65  
 ER\_MYINIT\_FAILED error code, 176  
 ER\_MYISAM\_CHECK\_METHOD\_ERROR error code, 296  
 ER\_MYISAM\_CRASHED\_ERROR error code, 296  
 ER\_MYISAM\_CRASHED\_ERROR\_IN error code, 187  
 ER\_MYISAM\_CRASHED\_ERROR\_IN\_THREAD error code, 187  
 ER\_MYSQLBACKUP\_CLIENT\_MSG error code, 153  
 ER\_MYSQLBACKUP\_MSG error code, 570  
 ER\_MYSQL\_NATIVE\_PASSWORD\_SECOND\_PASSWORD error code, 550  
 ER\_MY\_MALLOC\_GETPROCADDRESS\_FAILED error code, 614  
 ER\_MY\_MALLOC\_LOADLIBRARY\_FAILED error code, 614  
 ER\_MY\_MALLOC\_USING\_JEMALLOC error code, 614  
 ER\_MY\_MALLOC\_USING\_STD\_MALLOC error code, 614  
 ER\_MY\_NET\_WRITE\_FAILED\_FALLING\_BACK\_ON\_STD error code, 258  
 ER\_M\_BIGGER\_THAN\_D error code, 33  
 ER\_NAME\_BECOMES\_EMPTY error code, 36  
 ER\_NANOSECOND\_TIMER\_IS\_NOT\_AVAILABLE error code, 293  
 ER\_NATIVE\_FCT\_NAME\_COLLISION error code, 42  
 ER\_NDBINFO\_NOT\_UPGRADING\_SCHEMA error code, 580  
 ER\_NDBINFO\_UPGRADING\_SCHEMA error code, 580  
 ER\_NDBINFO\_UPGRADING\_SCHEMA\_FAIL error code, 580  
 ER\_NDB\_BINLOG\_BLOB\_REQUIRES\_PK error code, 248  
 ER\_NDB\_BINLOG\_CANT\_COMMIT\_TO\_NDB\_BINLOG\_INDEX error code, 246  
 ER\_NDB\_BINLOG\_CANT\_CREATE\_BLOB error code, 249  
 ER\_NDB\_BINLOG\_CANT\_CREATE\_EVENT\_IN\_DB error code, 248  
 ER\_NDB\_BINLOG\_CANT\_CREATE\_EVENT\_IN\_DB\_AND\_CANT\_DROP error code, 249  
 ER\_NDB\_BINLOG\_CANT\_CREATE\_EVENT\_IN\_DB\_DROP error code, 249  
 ER\_NDB\_BINLOG\_CANT\_CREATE\_PURGE\_THD error code, 272  
 ER\_NDB\_BINLOG\_CANT\_DISCOVER\_TABLE\_FROM\_SCHEMA error code, 243  
 ER\_NDB\_BINLOG\_CANT\_DROP\_EVENT\_FROM\_DB error code, 249  
 ER\_NDB\_BINLOG\_CANT\_INJECT\_APPLY\_STATUS\_WRITE\_ROW error code, 252  
 ER\_NDB\_BINLOG\_CANT\_LOCK\_NDB\_BINLOG\_INDEX error code, 246  
 ER\_NDB\_BINLOG\_CANT\_RELEASE\_SLOCK error code, 244  
 ER\_NDB\_BINLOG\_CANT\_REOPEN\_SHADOW\_TABLE error code, 244  
 ER\_NDB\_BINLOG\_CANT\_WRITE\_TO\_NDB\_BINLOG\_INDEX error code, 246  
 ER\_NDB\_BINLOG\_CLEANING\_UP\_SETUP\_LEFTOVERS error code, 242  
 ER\_NDB\_BINLOG\_CLUSTER\_FAILURE error code, 250  
 ER\_NDB\_BINLOG\_CLUSTER\_HAS\_RECONNECTED error code, 250  
 ER\_NDB\_BINLOG\_CLUSTER\_INFORMATION error code, 250  
 ER\_NDB\_BINLOG\_CLUSTER\_RESTARTED\_RESET\_MASTER\_SU error code, 251  
 ER\_NDB\_BINLOG\_CREATE\_TABLE\_EVENT error code, 219  
 ER\_NDB\_BINLOG\_CREATE\_TABLE\_EVENT\_FAILED error code, 248  
 ER\_NDB\_BINLOG\_CREATE\_TABLE\_EVENT\_INFO error code, 248  
 ER\_NDB\_BINLOG\_CREATING\_NDBEVENTOPERATION\_FAILED error code, 249  
 ER\_NDB\_BINLOG\_DISCOVER\_REUSING\_OLD\_EVENT\_OPS error code, 249  
 ER\_NDB\_BINLOG\_DISCOVER\_TABLE\_EVENT\_INFO error code, 248  
 ER\_NDB\_BINLOG\_ERROR\_DURING\_GCI\_COMMIT error code, 252  
 ER\_NDB\_BINLOG\_ERROR\_DURING\_GCI\_ROLLBACK error code, 252  
 ER\_NDB\_BINLOG\_ERROR\_HANDLING\_SCHEMA\_EVENT error code, 251  
 ER\_NDB\_BINLOG\_ERROR\_INFO\_FROM\_DA error code, 219  
 ER\_NDB\_BINLOG\_FAILED\_CREATE\_EVENT\_OPERATIONS\_DUR error code, 219  
 ER\_NDB\_BINLOG\_FAILED\_CREATE\_TABLE\_EVENT\_OPERATION error code, 219  
 ER\_NDB\_BINLOG\_FAILED\_TO\_GET\_TABLE error code, 248  
 ER\_NDB\_BINLOG\_FORMAT\_CHANGED\_FROM\_STMT\_TO\_MIXED error code, 220  
 ER\_NDB\_BINLOG\_GENERIC\_MESSAGE error code, 247  
 ER\_NDB\_BINLOG\_GOT\_DIST\_PRIV\_EVENT\_FLUSHING\_PRIVILEGE error code, 245  
 ER\_NDB\_BINLOG\_GOT\_SCHEMA\_EVENT error code, 245  
 ER\_NDB\_BINLOG\_INJECTING\_RANDOM\_WRITE\_FAILURE error code, 246

---

ER_NDB_BINLOG_INJECTOR_DISCARDING_ROW_EVENTS error code, 250	ER_NDB_BINLOG_USING_SERVER_ID_0_SLAVES_WILL_NOT error code, 247
ER_NDB_BINLOG_LATEST_TRX_IN_EPOCH_NOT_IN_BINLOG error code, 252	ER_NDB_BINLOG_WRITE_TO_NDB_BINLOG_INDEX_FAILED error code, 247
ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONNECTION error code, 251	ER_NDB_BINLOG_WRITING_TO_NDB_BINLOG_INDEX error code, 246
ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_WAITING error code, 251	ER_NDB_CANT_ALLOC_GLOBAL_NDB_CLUSTER_CONNECTION error code, 263
ER_NDB_BINLOG_NDBEVENT_EXECUTE_FAILED error code, 249	ER_NDB_CANT_ALLOC_GLOBAL_NDB_OBJECT error code, 263
ER_NDB_BINLOG_NDB_LOG_APPLY_STATUS_FORCING error code, 247	ER_NDB_CANT_WRITE_NDB_CLUSTER_CONNECTION error code, 263
ER_NDB_BINLOG_NDB_LOG_TRANSACTION_ID_REQUIRED error code, 247	ER_NDB_CANT_WRITE_EVENTS error code, 244
ER_NDB_BINLOG_NDB_TABLES_INITIALLY_READ_ONLY error code, 221	ER_NDB_CANT_PARSE_NDB_CLUSTER_CONNECTION_POOL error code, 262
ER_NDB_BINLOG_NDB_TABLES_WRITABLE error code, 251	ER_NDB_CANT_START_CONNECT_THREAD error code, 263
ER_NDB_BINLOG_NOT_LOGGING error code, 248	ER_NDB_CLEANING_STRAY_TABLES error code, 241
ER_NDB_BINLOG_ONLINE_ALTER_RENAME error code, 244	ER_NDB_CLEAR_SLOCK_INFO error code, 244
ER_NDB_BINLOG_ONLINE_ALTER_RENAME_COMPLETED error code, 245	ER_NDB_CLUSTER_FAILURE error code, 245
ER_NDB_BINLOG_OPENING_INDEX error code, 246	ER_NDB_CLUSTER_FIND_ALL_DBS_FAIL error code, 242
ER_NDB_BINLOG_RELEASING_EXTRA_SHARE_REFERENCES error code, 252	ER_NDB_CLUSTER_FIND_ALL_DBS_RETRY error code, 241
ER_NDB_BINLOG_REMAINING_OPEN_TABLES error code, 252	ER_NDB_CLUSTER_FREE_SHARE_INFO error code, 221
ER_NDB_BINLOG_REMAINING_OPEN_TABLE_INFO error code, 252	ER_NDB_CLUSTER_GENERIC_MESSAGE error code, 206
ER_NDB_BINLOG_RENAME_EVENT error code, 219	ER_NDB_CLUSTER_GET_SHARE_INFO error code, 220
ER_NDB_BINLOG_REPLY_TO error code, 244	ER_NDB_CLUSTER_MARK_SHARE_DROPPED_DESTROYING error code, 221
ER_NDB_BINLOG_SERVER_SHUTDOWN_DURING_NDB_CLUSTER error code, 250	ER_NDB_CLUSTER_MARK_SHARE_DROPPED_INFO error code, 221
ER_NDB_BINLOG_SHUTDOWN_DETECTED error code, 251	ER_NDB_CLUSTER_OOM_THD_NDB error code, 221
ER_NDB_BINLOG_SIGNALLING_UNKNOWN_VALUE error code, 243	ER_NDB_CLUSTER_REAL_FREE_SHARE_DROP_FAILED error code, 221
ER_NDB_BINLOG_SKIPPING_DROP_OF_DB_CONTAINING_LOCAL TABLES error code, 245	ER_NDB_CLUSTER_REAL_FREE_SHARE_INFO error code, 221
ER_NDB_BINLOG_SKIPPING_DROP_OF_LOCAL_TABLE error code, 245	ER_NDB_CLUSTER_SCHEMA_INFO error code, 206
ER_NDB_BINLOG_SKIPPING_LOCAL_TABLE error code, 244	ER_NDB_CLUSTER_WRONG_NUMBER_OF_FUNCTION_ARGUMENTS error code, 206
ER_NDB_BINLOG_SKIPPING_OLD_SCHEMA_OPERATION error code, 245	ER_NDB_COLUMN_DEFAULTS_DIFFER error code, 217
ER_NDB_BINLOG_SKIPPING_RENAME_OF_LOCAL_TABLE error code, 245	ER_NDB_COLUMN_INFO error code, 217
ER_NDB_BINLOG_STARTING_LOG_AT_EPOCH error code, 251	ER_NDB_COLUMN_SHOULD_NOT_HAVE_NATIVE_DEFAULT error code, 217
ER_NDB_BINLOG_UNHANDLED_ERROR_FOR_TABLE error code, 250	ER_NDB_CONFLICT_FN_PARSE_ERROR error code, 248
ER_NDB_BINLOG_UNKNOWN_NON_DATA_EVENT error code, 250	ER_NDB_CONFLICT_FN_SETUP_ERROR error code, 248
	ER_NDB_CONFLICT_GENERIC_MESSAGE error code, 247

---

---

ER\_NDB\_COULD\_NOT\_GET\_APPLY\_STATUS\_SHARE error code, 250  
 ER\_NDB\_CPU\_MASK\_TOO\_SHORT error code, 264  
 ER\_NDB\_CREATE\_EVENT\_OPS\_LOGGING\_INFO error code, 249  
 ER\_NDB\_CREATING\_SHARE\_IN\_OPEN error code, 220  
 ER\_NDB\_CREATING\_TABLE error code, 241  
 ER\_NDB\_DISCARDING\_EVENT\_ID\_VERSION\_MISMATCH error code, 244  
 ER\_NDB\_DISCARDING\_EVENT\_NO\_OBJ error code, 244  
 ER\_NDB\_DISCONNECT\_INFO error code, 217  
 ER\_NDB\_DISCOVERED\_MISSING\_DB error code, 241  
 ER\_NDB\_DISCOVERED\_REMAINING\_DB error code, 241  
 ER\_NDB\_DISTRIBUTED\_INFO error code, 243  
 ER\_NDB\_DISTRIBUTING\_ERR error code, 275  
 ER\_NDB\_DISTRIBUTION\_COMPLETE error code, 243  
 ER\_NDB\_DUPLICATE\_NODEID\_IN\_NDB\_CLUSTER\_CONNECTION error code, 262  
 ER\_NDB\_EMPTY\_NODEID\_IN\_NDB\_CLUSTER\_CONNECTION error code, 262  
 ER\_NDB\_ERROR\_IN\_GET\_AUTO\_INCREMENT error code, 219  
 ER\_NDB\_ERROR\_IN\_READAUTOINCREMENTVALUE error code, 218  
 ER\_NDB\_FAILED\_TO\_SET\_UP\_TABLE error code, 242  
 ER\_NDB\_FIELD\_INFO error code, 217  
 ER\_NDB\_FLUSHING\_TABLE\_INFO error code, 241  
 ER\_NDB\_FOUND\_UNCOMMITTED\_AUTOCOMMIT error code, 218  
 ER\_NDB\_GENERIC\_ERROR error code, 264  
 ER\_NDB\_HANDLE\_TRAILING\_SHARE\_INFO error code, 220  
 ER\_NDB\_IGNORING\_UNKNOWN\_EVENT error code, 246  
 ER\_NDB\_ILLEGAL\_VALUE\_FOR\_NDB\_RECV\_THREAD\_GRP\_MASK error code, 221  
 ER\_NDB\_INFO\_FAILED\_TO\_CREATE\_NDBINFO error code, 206  
 ER\_NDB\_INFO\_FAILED\_TO\_INIT\_NDBINFO error code, 206  
 ER\_NDB\_INFO\_FOUND\_UNEXPECTED\_FIELD\_TYPE error code, 206  
 ER\_NDB\_INITIALIZE\_GIVEN\_CLUSTER\_PLUGIN\_DISABLED error code, 220  
 ER\_NDB\_INVALID\_NODEID\_IN\_NDB\_CLUSTER\_CONNECTION error code, 262  
 ER\_NDB\_LOG\_ENTRY error code, 272  
 ER\_NDB\_LOG\_ENTRY\_WITH\_PREFIX error code, 272  
 ER\_NDB\_MISMATCH\_IN\_FRM\_DISCOVERING error code, 242  
 ER\_NDB\_MISSING\_FRM\_DISCOVERING error code, 242  
 ER\_NDB\_NODEID\_NOT\_FIRST\_IN\_NDB\_CLUSTER\_CONNECTION error code, 263  
 ER\_NDB\_NODE\_ID\_AND\_MANAGEMENT\_SERVER\_INFO error code, 217  
 ER\_NDB\_NODE\_INFO error code, 263  
 ER\_NDB\_NOT\_WAITING\_FOR\_DISTRIBUTING error code, 243  
 ER\_NDB\_NUMBER\_OF\_CHANNELS error code, 275  
 ER\_NDB\_OOM\_GET\_NDB\_BLOBS\_VALUE error code, 241  
 ER\_NDB\_OOM\_IN\_FIX\_UNIQUE\_INDEX\_ATTR\_ORDER error code, 218  
 ER\_NDB\_POOL\_SIZE\_MUST\_MATCH\_NDB\_CLUSTER\_CONNECTION error code, 262  
 ER\_NDB\_QUERY\_FAILED error code, 216  
 ER\_NDB\_REMAINING\_OPEN\_TABLES error code, 250  
 ER\_NDB\_REMAINING\_OPEN\_TABLE\_INFO error code, 250  
 ER\_NDB\_REPLICATION\_SCHEMA\_ERROR error code, 218  
 ER\_NDB\_SCHEMA\_DISTRIBUTION\_FAILED error code, 243  
 ER\_NDB\_SCHEMA\_DISTRIBUTION\_REPORTS\_SUBSCRIBE error code, 243  
 ER\_NDB\_SCHEMA\_DISTRIBUTION\_REPORTS\_UNSUBSCRIBE error code, 243  
 ER\_NDB\_SCHEMA\_GENERIC\_MESSAGE error code, 214  
 ER\_NDB\_SERVER\_ID\_RESERVED\_OR\_TOO\_LARGE error code, 247  
 ER\_NDB\_SHARE\_ALREADY\_EXISTS error code, 220  
 ER\_NDB\_SKIPPING\_SETUP\_TABLE error code, 242  
 ER\_NDB\_SLAVE\_BINLOG\_MISSING\_INFO\_FOR\_CONFLICT\_DETECTION error code, 218  
 ER\_NDB\_SLAVE\_CANT\_ALLOCATE\_TABLE\_SHARE error code, 219  
 ER\_NDB\_SLAVE\_CONFLICT\_DETECTION\_REQUIRES\_TRANSACTION error code, 218  
 ER\_NDB\_SLAVE\_CONFLICT\_FUNCTION\_REQUIRES\_ROLE error code, 218  
 ER\_NDB\_SLAVE\_ERROR\_IN\_UPDATE\_CREATE\_INFO error code, 219  
 ER\_NDB\_SLAVE\_LOGGING\_EXCEPTIONS\_TO error code, 206  
 ER\_NDB\_SLAVE\_LOW\_EPOCH\_RESOLUTION error code, 218  
 ER\_NDB\_SLAVE\_MALFORMED\_EVENT\_RECEIVED\_ON\_TABLE error code, 218  
 ER\_NDB\_SLAVE\_MAX\_REPLICATED\_EPOCH\_SET\_TO error code, 217  
 ER\_NDB\_SLAVE\_MAX\_REPLICATED\_EPOCH\_UNKNOWN error code, 217



---

ER\_NDB\_SLAVE\_MISSING\_DATA\_FOR\_TIMESTAMP\_COLUMN error code, 206  
 ER\_NDB\_SLAVE\_PARALLEL\_WORKERS error code, 275  
 ER\_NDB\_SLAVE\_PREVIOUS\_EPOCH\_NOT\_COMMITTED error code, 205  
 ER\_NDB\_SLAVE\_SAW\_ALREADY\_COMMITTED\_EPOCH error code, 205  
 ER\_NDB\_SLAVE\_SAW\_EPOCH\_LOWER\_THAN\_PREVIOUS error code, 205  
 ER\_NDB\_SLAVE\_SAW\_EPOCH\_LOWER\_THAN\_PREVIOUS error code, 205  
 ER\_NDB\_SLAVE\_TOO\_MANY\_RETRIES error code, 218  
 ER\_NDB\_STARTING\_CONNECT\_THREAD error code, 263  
 ER\_NDB\_TABLES\_INITIALLY\_READ\_ONLY\_ON\_RECONNECT error code, 246  
 ER\_NDB\_TABLES\_NOT\_READY error code, 182  
 ER\_NDB\_TABLE\_IS\_NOT\_DISTRIBUTED error code, 241  
 ER\_NDB\_TABLE\_OPENED\_READ\_ONLY error code, 220  
 ER\_NDB\_THREAD\_TIMED\_OUT error code, 241  
 ER\_NDB\_TIMED\_OUT\_IN\_DROP\_TABLE error code, 249  
 ER\_NDB\_TIMEOUT\_WHILE\_DISTRIBUTING error code, 242  
 ER\_NDB\_TOO\_MANY\_CPUS\_IN\_NDB\_RECV\_THREAD error code, 222  
 ER\_NDB\_TRAILING\_SHARE\_RELEASED\_BY\_CLOSE\_CURSOR error code, 220  
 ER\_NDB\_TRANS\_DEPENDENCY\_TRACKER\_ERROR error code, 247  
 ER\_NDB\_UNEXPECTED\_RENAME\_TYPE error code, 219  
 ER\_NDB\_USING\_NODEID error code, 263  
 ER\_NDB\_USING\_NODEID\_LIST error code, 263  
 ER\_NDB\_UTIL\_THREAD\_OOM error code, 221  
 ER\_NDB\_WAITING\_INFO error code, 242  
 ER\_NDB\_WAITING\_INFO\_WITH\_MAP error code, 242  
 ER\_NEED\_FILE\_INSTEAD\_OF\_DIR error code, 179  
 ER\_NEED\_LOG\_BIN error code, 179  
 ER\_NEED\_REPREPARE error code, 44  
 ER\_NETWORK\_NAMESPACES\_NOT\_SUPPORTED error code, 561  
 ER\_NETWORK\_NAMESPACE\_FILE\_PATH\_TOO\_LONG error code, 562  
 ER\_NETWORK\_NAMESPACE\_NOT\_ALLOWED\_FOR\_WRITE error code, 561  
 ER\_NETWORK\_READ\_EVENT\_CHECKSUM\_FAILURE error code, 528  
 ER\_NET\_ERROR\_ON\_WRITE error code, 14  
 ER\_NET\_FCNTL\_ERROR error code, 14  
 ER\_NET\_OK\_PACKET\_TOO\_LARGE error code, 74  
 ER\_NET\_PACKETS\_OUT\_OF\_ORDER error code, 14  
 ER\_NET\_PACKET\_TOO\_LARGE error code, 14  
 ER\_NET\_READ\_ERROR error code, 14  
 ER\_NET\_READ\_ERROR\_FROM\_PIPE error code, 14  
 ER\_NET\_READ\_INTERRUPTED error code, 14  
 ER\_NET\_UNCOMPRESS\_ERROR error code, 14  
 ER\_NET\_WAIT\_ERROR error code, 562  
 ER\_NET\_WAIT\_ERROR2 error code, 599  
 ER\_NET\_WRITE\_INTERRUPTED error code, 14  
 ER\_NO\_ABORTING\_CONNECTION error code, 16  
 ER\_NO error code, 3  
 ER\_NONEXISTING\_GRANT error code, 13  
 ER\_NONEXISTING\_PROC\_GRANT error code, 31  
 ER\_NONEXISTING\_TABLE\_GRANT error code, 13  
 ER\_NONPOSITIVE\_RADIUS error code, 108  
 ER\_NONUNIQ\_TABLE error code, 8  
 ER\_NONUPDATEABLE\_COLUMN error code, 28  
 ER\_NON\_BOOLEAN\_EXPR\_FOR\_CHECK\_CONSTRAINT error code, 120  
 ER\_NON\_DEFAULT\_VALUE\_FOR\_GENERATED\_COLUMN error code, 79  
 ER\_NON\_GROUPING\_FIELD\_USED error code, 35  
 ER\_NON\_INSERTABLE\_TABLE error code, 36  
 ER\_NON\_RO\_SELECT\_DISABLE\_TIMER error code, 71  
 ER\_NON\_UNIQ\_ERROR error code, 6  
 ER\_NON\_UPDATABLE\_TABLE error code, 24  
 ER\_NORMAL\_SERVER\_SHUTDOWN error code, 527  
 ER\_NORMAL\_SHUTDOWN error code, 8  
 ER\_NOTE\_COMPONENT\_KEYRING\_OCI\_MISSING\_NAME\_OF\_ARCHIVED\_TABLE error code, 626  
 ER\_NOTE\_COMPONENT\_SLOT\_DEREGISTRATION\_SUCCESS error code, 635  
 ER\_NOTE\_COMPONENT\_SLOT\_REGISTRATION\_SUCCESS error code, 635  
 ER\_NOTE\_KEYRING\_COMPONENT\_AES\_DATA\_IDENTIFIER error code, 597  
 ER\_NOTE\_KEYRING\_COMPONENT\_AES\_INVALID\_KEY error code, 597  
 ER\_NOTE\_KEYRING\_COMPONENT\_AES\_INVALID\_MODE\_BLOCK error code, 597  
 ER\_NOTE\_KEYRING\_COMPONENT\_AES\_OPERATION\_ERROR error code, 597  
 ER\_NOTE\_KEYRING\_COMPONENT\_GENERATE\_FAILED error code, 598  
 ER\_NOTE\_KEYRING\_COMPONENT\_INITIALIZED error code, 597  
 ER\_NOTE\_KEYRING\_COMPONENT\_KEYS\_METADATA\_ITERATOR error code, 598  
 ER\_NOTE\_KEYRING\_COMPONENT\_METADATA\_ITERATOR error code, 598  
 ER\_NOTE\_KEYRING\_COMPONENT\_READ\_DATA\_NOT\_FOUND error code, 598

---

---

ER\_NOTE\_KEYRING\_COMPONENT\_REMOVE\_FAILED error code, 598  
 ER\_NOTE\_KEYRING\_COMPONENT\_STORE\_FAILED error code, 598  
 ER\_NOTE\_KEYRING\_COMPONENT\_WRITE\_MAXIMUM\_ERROR\_CODE error code, 598  
 ER\_NOT\_ALLOWED\_COMMAND error code, 13  
 ER\_NOT\_ALLOWED\_WITH\_START\_TRANSACTION error code, 139  
 ER\_NOT\_FORM\_FILE error code, 5  
 ER\_NOT\_HINT\_UPDATABLE\_VARIABLE error code, 100  
 ER\_NOT\_IMPLEMENTED\_FOR\_CARTESIAN\_SRS error code, 107  
 ER\_NOT\_IMPLEMENTED\_FOR\_GEOGRAPHIC\_SRS error code, 98  
 ER\_NOT\_IMPLEMENTED\_FOR\_PROJECTED\_SRS error code, 108  
 ER\_NOT\_IMPLEMENTED\_GET\_TABLESPACE\_STATISTICS error code, 321  
 ER\_NOT\_KEYFILE error code, 5  
 ER\_NOT\_RIGHT\_NOW error code, 176  
 ER\_NOT\_SUPPORTED\_AUTH\_MODE error code, 21  
 ER\_NOT\_SUPPORTED\_YET error code, 20  
 ER\_NOT\_VALID\_PASSWORD error code, 62  
 ER\_NO\_ACCESS\_TO\_NATIVE\_FCT error code, 92  
 ER\_NO\_BINARY\_LOGGING error code, 30  
 ER\_NO\_BINLOG\_ERROR error code, 39  
 ER\_NO\_CSV\_NO\_LOG\_TABLES error code, 178  
 ER\_NO\_DB\_ERROR error code, 6  
 ER\_NO\_DEFAULT error code, 20  
 ER\_NO\_DEFAULT\_FOR\_FIELD error code, 29  
 ER\_NO\_DEFAULT\_FOR\_VIEW\_FIELD error code, 32  
 ER\_NO\_ERROR\_LOG\_PARSER\_CONFIGURED error code, 591  
 ER\_NO\_FORMAT\_DESCRIPTION\_EVENT\_BEFORE\_BINLOG\_STATEMENT error code, 43  
 ER\_NO\_FT\_MATERIALIZED\_SUBQUERY error code, 70  
 ER\_NO\_PARTITION\_FOR\_GIVEN\_VALUE error code, 39  
 ER\_NO\_PARTITION\_FOR\_GIVEN\_VALUE\_SILENT error code, 43  
 ER\_NO\_PARTS\_ERROR error code, 38  
 ER\_NO\_PATH\_FOR\_SHARED\_LIBRARY error code, 536  
 ER\_NO\_PERMISSION\_TO\_CREATE\_USER error code, 18  
 ER\_NO\_REFERENCED\_ROW error code, 19  
 ER\_NO\_REFERENCED\_ROW\_2 error code, 34  
 ER\_NO\_SECURE\_TRANSPORTS\_CONFIGURED error code, 83  
 ER\_NO\_SESSION\_TEMP error code, 128  
 ER\_NO\_SUCH\_DB error code, 87  
 ER\_NO\_SUCH\_INDEX error code, 9  
 ER\_NO\_SUCH\_TABLE error code, 13  
 ER\_NO\_SUCH\_THREAD error code, 10  
 ER\_NO\_SUCH\_USER error code, 34  
 ER\_NO\_SUCH\_PLUGIN\_WITHOUT\_USER\_PLUGIN error code, 196  
 ER\_NO\_SYSTEM\_SCHEMA\_ACCESS error code, 91  
 ER\_NO\_SYSTEM\_TABLESPACE\_ACCESS error code, 91  
 ER\_NO\_SYSTEM\_TABLE\_ACCESS error code, 91  
 ER\_NO\_SYSTEM\_TABLE\_ACCESS\_FOR\_DICTIONARY\_TABLE error code, 91  
 ER\_NO\_SYSTEM\_TABLE\_ACCESS\_FOR\_SYSTEM\_TABLE error code, 91  
 ER\_NO\_SYSTEM\_TABLE\_ACCESS\_FOR\_TABLE error code, 91  
 ER\_NO\_SYSTEM\_VIEW\_ACCESS error code, 98  
 ER\_NO\_TABLES\_USED error code, 10  
 ER\_NO\_THD\_NO\_UUID error code, 169  
 ER\_NO\_TRIGGERS\_ON\_SYSTEM\_SCHEMA error code, 35  
 ER\_NO\_UNIQUE\_LOGFILE error code, 10  
 ER\_NPIPE\_CANT\_CREATE error code, 274  
 ER\_NPIPE\_FAILED\_TO\_INIT\_SECURITY\_DESCRIPTOR error code, 205  
 ER\_NPIPE\_FAILED\_TO\_SET\_SECURITY\_DESCRIPTOR error code, 205  
 ER\_NPIPE\_PIPE\_ALREADY\_IN\_USE error code, 205  
 ER\_NULL\_COLUMN\_IN\_INDEX error code, 12  
 ER\_NULL\_IN\_VALUES\_LESS\_THAN error code, 41  
 ER\_NUMERIC\_JSON\_VALUE\_OUT\_OF\_RANGE error code, 83  
 ER\_OBSOLETE\_FILE\_PRIVILEGE\_FOR\_REPLICATION\_CHECKS error code, 571  
 ER\_OBSOLETE\_REQUIRE\_ROW\_FORMAT\_VIOLATION error code, 571  
 ER\_OLD\_FILE\_FORMAT error code, 35  
 ER\_OLD\_KEYFILE error code, 5  
 ER\_OLD\_PASSWORDS\_NO\_MIDDLE\_GROUND error code, 171  
 ER\_OLD\_TEMPORALS\_UPGRADED error code, 67  
 ER\_ONLY\_FD\_AND\_RBR\_EVENTS\_ALLOWED\_IN\_BINLOG\_STATEMENT error code, 53  
 ER\_ONLY\_IMPLEMENTED\_FOR\_SRID\_0\_AND\_4326 error code, 105  
 ER\_ONLY INTEGERS\_ALLOWED error code, 42  
 ER\_ONLY\_ON\_RANGE\_LIST\_PARTITION error code, 38  
 ER\_OOM error code, 176  
 ER\_OOM\_SAVE\_GTIDS error code, 527  
 ER\_OPEN\_AS\_READONLY error code, 5  
 ER\_OPEN\_ROLE\_TABLES error code, 89  
 ER\_OPERAND\_COLUMNS error code, 21

---

ER\_OPERATION\_NOT\_ALLOWED\_ON\_GR\_SECONDARY error code, 148  
 ER\_OPERATION\_NOT\_ALLOWED\_WHILE\_PRIMARY\_CHANGE\_IS\_RUNNING error code, 154  
 ER\_OPTION\_PREVENTS\_STATEMENT error code, 24  
 ER\_OPT\_WRONG\_TREE error code, 162  
 ER\_OUTOFMEMORY error code, 5  
 ER\_OUT\_OF\_RESOURCES error code, 6  
 ER\_OUT\_OF\_SORTMEMORY error code, 5  
 ER\_PAGE\_TRACKING\_CANNOT\_PURGE error code, 119  
 ER\_PAGE\_TRACKING\_NOT\_STARTED error code, 119  
 ER\_PAGE\_TRACKING\_RANGE\_NOT\_TRACKED error code, 119  
 ER\_PARSER\_TRACE error code, 162  
 ER\_PARSE\_ERROR error code, 7  
 ER\_PARSE\_ERROR\_IN\_DIGEST\_FN error code, 104  
 ER\_PARSING\_VIEW error code, 169  
 ER\_PARTIAL\_REVOKES\_EXIST error code, 129  
 ER\_PARTIAL\_REVOKE\_AND\_DB\_GRANT\_BOTH\_EXISTS error code, 130  
 ER\_PARTITIONS\_MUST\_BE\_DEFINED\_ERROR error code, 37  
 ER\_PARTITION\_CLAUSE\_ON\_NONPARTITIONED error code, 54  
 ER\_PARTITION\_COLUMN\_LIST\_ERROR error code, 47  
 ER\_PARTITION\_CONST\_DOMAIN\_ERROR error code, 41  
 ER\_PARTITION\_ENTRY\_ERROR error code, 37  
 ER\_PARTITION\_EXCHANGE\_DIFFERENT\_OPTION error code, 53  
 ER\_PARTITION\_EXCHANGE\_FOREIGN\_KEY error code, 54  
 ER\_PARTITION\_EXCHANGE\_PART\_TABLE error code, 53  
 ER\_PARTITION\_EXCHANGE\_TEMP\_TABLE error code, 54  
 ER\_PARTITION\_FIELDS\_TOO\_LONG error code, 47  
 ER\_PARTITION\_FUNCTION\_FAILURE error code, 39  
 ER\_PARTITION\_FUNCTION\_IS\_NOT\_ALLOWED error code, 41  
 ER\_PARTITION\_FUNC\_NOT\_ALLOWED\_ERROR error code, 37  
 ER\_PARTITION\_HANDLER\_ADMIN\_MSG error code, 296  
 ER\_PARTITION\_INSTEAD\_OF\_SUBPARTITION error code, 54  
 ER\_PARTITION\_MAXVALUE\_ERROR error code, 36  
 ER\_PARTITION\_MERGE\_ERROR error code, 41  
 ER\_PARTITION\_MGMT\_ON\_NONPARTITIONED error code, 38  
 ER\_PARTITION\_MOVE\_CREATED\_DUPLICATE\_ROW\_PLEASE\_FIX error code, 275  
 ER\_PARTITION\_NAME error code, 45  
 ER\_PARTITION\_NOT\_DEFINED\_ERROR error code, 36  
 ER\_PARTITION\_NO\_TEMPORARY error code, 41  
 ER\_PARTITION\_REQUIRES\_VALUES\_ERROR error code, 36  
 ER\_PARTITION\_WRONG\_NO\_PART\_ERROR error code, 36  
 ER\_PARTITION\_WRONG\_NO\_SUBPART\_ERROR error code, 36  
 ER\_PARTITION\_WRONG\_VALUES\_ERROR error code, 36  
 ER\_PART\_EXPR\_TOO\_LONG error code, 99  
 ER\_PASSWORD\_ANONYMOUS\_USER error code, 12  
 ER\_PASSWORD\_CANNOT\_BE\_RETAINED\_ON\_PLUGIN\_CHANGE error code, 129  
 ER\_PASSWORD\_EXPIRATION\_NOT\_SUPPORTED\_BY\_AUTH\_PLUGIN error code, 104  
 ER\_PASSWORD\_EXPIRE\_ANONYMOUS\_USER error code, 69  
 ER\_PASSWORD\_FORMAT error code, 62  
 ER\_PASSWORD\_NOT\_ALLOWED error code, 12  
 ER\_PASSWORD\_NO\_MATCH error code, 12  
 ER\_PATH\_IN\_DATADIR error code, 100  
 ER\_PATH\_LENGTH error code, 49  
 ER\_PERFORMANCE\_SCHEMA\_VERSION\_CHANGE error code, 641  
 ER\_PERFSCHEMA\_COMPONENTS\_INFRASTRUCTURE\_BOOTSTRAP\_FAILED error code, 280  
 ER\_PERFSCHEMA\_COMPONENTS\_INFRASTRUCTURE\_SHUTDOWN\_FAILED error code, 281  
 ER\_PERFSCHEMA\_INIT\_FAILED error code, 180  
 ER\_PERFSCHEMA\_TABLES\_INIT\_FAILED error code, 282  
 ER\_PERSISTED\_VARIABLES\_DECRYPTION\_FAILED error code, 614  
 ER\_PERSISTED\_VARIABLES\_ENCRYPTION\_FAILED error code, 614  
 ER\_PERSISTED\_VARIABLES\_KEYRING\_SUPPORT\_REQUIRED error code, 613  
 ER\_PERSISTED\_VARIABLES\_LACK\_KEYRING\_SUPPORT error code, 614  
 ER\_PERSISTED\_VARIABLES\_MASTER\_KEY\_CANNOT\_BE\_GENERATED error code, 614  
 ER\_PERSISTED\_VARIABLES\_MASTER\_KEY\_NOT\_FOUND error code, 613  
 ER\_PERSISTENT\_PRIVILEGES\_BOOTSTRAP error code, 281  
 ER\_PERSIST\_ONLY\_ACCESS\_DENIED\_ERROR error code, 99  
 ER\_PERSIST\_OPTION\_HOST\_TRUNCATED error code, 562  
 ER\_PLUGIN\_STATUS error code, 321

---

---

ER\_PERSIST\_OPTION\_USER\_TRUNCATED error code, 562  
 ER\_PER\_CHANNEL\_RPL\_FILTER\_CONF\_FOR\_GRP\_RPL error code, 292  
 ER\_PFS\_MALLOC\_ARRAY\_OOM error code, 294  
 ER\_PFS\_MALLOC\_ARRAY\_OVERFLOW error code, 293  
 ER\_PFS\_NOTIFICATION\_FUNCTION\_REGISTER\_FAILED error code, 286  
 ER\_PID\_FILEPATH\_LOCATIONS\_INACCESSIBLE error code, 536  
 ER\_PID\_FILE\_PRIV\_DIRECTORY\_INSECURE error code, 388  
 ER\_PK\_INDEX\_CANT\_BE\_INVISIBLE error code, 89  
 ER\_PLUGGABLE\_PROTOCOL\_COMMAND\_NOT\_SUPPORTED error code, 81  
 ER\_PLUGIN\_BAD\_OPTIONS error code, 257  
 ER\_PLUGIN\_CANNOT\_BE\_UNINSTALLED error code, 67  
 ER\_PLUGIN\_CANT\_LOAD error code, 256  
 ER\_PLUGIN\_CANT\_OPEN\_PLUGIN\_TABLE error code, 256  
 ER\_PLUGIN\_CANT\_SET\_PERSISTENT\_OPTIONS error code, 257  
 ER\_PLUGIN\_COMMON\_FAILED\_TO\_OPEN\_FILTER\_TABLE error code, 319  
 ER\_PLUGIN\_COMMON\_FAILED\_TO\_OPEN\_TABLE error code, 320  
 ER\_PLUGIN\_DELETE\_BUILTIN error code, 44  
 ER\_PLUGIN\_DID\_NOT\_DEINITIALIZE\_THREADS error code, 216  
 ER\_PLUGIN\_DISABLED error code, 257  
 ER\_PLUGIN\_EXCEPTION\_OPERATION\_FAILED error code, 631  
 ER\_PLUGIN\_FAILED\_DEINITIALIZATION error code, 256  
 ER\_PLUGIN\_FAILED\_TO\_OPEN\_TABLE error code, 533  
 ER\_PLUGIN\_FAILED\_TO\_OPEN\_TABLES error code, 533  
 ER\_PLUGIN\_FORCING\_SHUTDOWN error code, 256  
 ER\_PLUGIN\_HAS\_CONFLICTING\_SYSTEM\_VARIABLES error code, 257  
 ER\_PLUGIN\_HAS\_NONZERO\_REFCOUNT\_AFTER\_DEINITIALIZATION error code, 256  
 ER\_PLUGIN\_HAS\_NONZERO\_REFCOUNT\_AFTER\_SHUTDOWN error code, 256  
 ER\_PLUGIN\_INIT\_FAILED error code, 183  
 ER\_PLUGIN\_INSTALL\_ERROR error code, 542  
 ER\_PLUGIN\_INVALID\_TABLE\_DEFINITION error code, 603  
 ER\_PLUGIN\_IS\_NOT\_LOADED error code, 39  
 ER\_PLUGIN\_IS\_PERMANENT error code, 51  
 ER\_PLUGIN\_LOAD\_OPTIONS\_IGNORED error code, 572  
 ER\_PLUGIN\_LOAD\_PARAMETER\_TOO\_LONG error code, 256  
 ER\_PLUGIN\_NOT\_EARLY error code, 123  
 ER\_PLUGIN\_NOT\_EARLY\_DUP error code, 563  
 ER\_PLUGIN\_NO\_INSTALL error code, 52  
 ER\_PLUGIN\_NO\_INSTALL\_DUP error code, 563  
 ER\_PLUGIN\_NO\_UNINSTALL error code, 52  
 ER\_PLUGIN\_OOM error code, 257  
 ER\_PLUGIN\_PARSING\_OPTIONS\_FAILED error code, 257  
 ER\_PLUGIN\_REGISTRATION\_DONE error code, 149  
 ER\_PLUGIN\_REGISTRATION\_FAILED error code, 256  
 ER\_PLUGIN\_REQUIRES\_REGISTRATION error code, 149  
 ER\_PLUGIN\_SHUTTING\_DOWN\_PLUGIN error code, 256  
 ER\_PLUGIN\_UNINSTALL\_ERROR error code, 542  
 ER\_PLUGIN\_UNKNOWN\_VARIABLE\_TYPE error code, 257  
 ER\_PLUGIN\_VARIABLE\_MISSING\_NAME error code, 257  
 ER\_PLUGIN\_VARIABLE\_NOT\_ALLOCATED\_THREAD\_LOCAL error code, 257  
 ER\_PLUGIN\_VARIABLE\_SET\_READ\_ONLY error code, 257  
 ER\_POINTLESS\_WITHOUT\_SLOWLOG error code, 171  
 ER\_POLYGON\_TOO\_LARGE error code, 110  
 ER\_PREPARE\_FOR\_PRIMARY\_ENGINE error code, 605  
 ER\_PREPARE\_FOR\_SECONDARY\_ENGINE error code, 556  
 ER\_PREVENTS\_VARIABLE\_WITHOUT\_RBR error code, 78  
 ER\_PRIMARY\_CANT\_HAVE\_NULL error code, 15  
 ER\_PRIVILEGE\_DEREGISTRATION error code, 637  
 ER\_PRIVILEGE\_REGISTRATION error code, 637  
 ER\_PRIVILEGE\_SYSTEM\_INIT\_FAILED error code, 282  
 ER\_PROCACCESS\_DENIED\_ERROR error code, 29  
 ER\_PROC\_AUTO\_GRANT\_FAIL error code, 31  
 ER\_PROC\_AUTO\_REVOKE\_FAIL error code, 31  
 ER\_PROTOCOL\_COMPRESSION\_RESET\_LOG error code, 170  
 ER\_PS\_MANY\_PARAM error code, 30  
 ER\_PS\_NO\_RECURSION error code, 34  
 ER\_QUERY\_CACHE\_DISABLED error code, 47  
 ER\_QUERY\_INTERRUPTED error code, 26  
 ER\_QUERY\_ON\_FOREIGN\_DATA\_SOURCE error code, 33  
 ER\_QUERY\_TIMEOUT error code, 70  
 ER\_RANGE\_NOT\_INCREASING\_ERROR error code, 37  
 ER\_READING\_TABLE\_FAILED error code, 184

---

ER\_READY error code, 8  
ER\_READ\_LOG\_EVENT\_FAILED error code, 291  
ER\_READ\_ONLY\_MODE error code, 63  
ER\_READ\_ONLY\_TRANSACTION error code, 18  
ER\_REALLY\_RUN\_AS\_ROOT error code, 175  
ER\_RECORD\_FILE\_FULL error code, 11  
ER\_RECOVERING\_TABLE error code, 258  
ER\_REDUCED\_DBLWR\_FILE\_CORRUPTED error code, 639  
ER\_REDUCED\_DBLWR\_PAGE\_FOUND error code, 639  
ER\_REFERENCED\_TRG\_DOES\_NOT\_EXIST error code, 69  
ER\_REGEX\_BAD\_ESCAPE\_SEQUENCE error code, 106  
ER\_REGEX\_BAD\_INTERVAL error code, 106  
ER\_REGEX\_BUFFER\_OVERFLOW error code, 105  
ER\_REGEX\_ERROR error code, 13  
ER\_REGEX\_ILLEGAL\_ARGUMENT error code, 105  
ER\_REGEX\_INDEX\_OUTOFBOUNDS\_ERROR error code, 106  
ER\_REGEX\_INTERNAL\_ERROR error code, 106  
ER\_REGEX\_INVALID\_BACK\_REF error code, 106  
ER\_REGEX\_INVALID\_CAPTURE\_GROUP\_NAME error code, 128  
ER\_REGEX\_INVALID\_FLAG error code, 130  
ER\_REGEX\_INVALID\_RANGE error code, 107  
ER\_REGEX\_LOOK\_BEHIND\_LIMIT error code, 106  
ER\_REGEX\_MAX\_LT\_MIN error code, 106  
ER\_REGEX\_MISMATCHED\_PAREN error code, 106  
ER\_REGEX\_MISSING\_CLOSE\_BRACKET error code, 107  
ER\_REGEX\_MISSING\_FILE error code, 152  
ER\_REGEX\_MISSING\_ICU\_DATADIR error code, 612  
ER\_REGEX\_MISSING\_RESOURCE error code, 152  
ER\_REGEX\_PATTERN\_TOO\_BIG error code, 107  
ER\_REGEX\_RULE\_SYNTAX error code, 106  
ER\_REGEX\_STACK\_OVERFLOW error code, 107  
ER\_REGEX\_STRING\_NOT\_TERMINATED error code, 105  
ER\_REGEX\_TIME\_OUT error code, 107  
ER\_REGEX\_UNIMPLEMENTED error code, 106  
ER\_REGEX\_NUMBER\_TOO\_BIG error code, 142  
ER\_RELAY\_LOG\_FAIL error code, 30  
ER\_RELAY\_LOG\_INIT error code, 30  
ER\_RELAY\_LOG\_SPACE\_LIMIT\_DISABLED error code, 539  
ER\_RELOAD\_KEYRING\_FAILURE error code, 146  
ER\_REMOVED\_SPACES error code, 35  
ER\_RENAMED\_NAME error code, 45  
ER\_RENAME\_ROLE error code, 89  
ER\_REORG\_HASH\_ONLY\_ON\_SAME\_NO error code, 38  
ER\_REORG\_NO\_PARAM\_ERROR error code, 38  
ER\_REORG\_OUTSIDE\_RANGE error code, 39  
ER\_REORG\_PARTITION\_NOT\_EXIST error code, 38  
ER\_REPLACE\_INACCESSIBLE\_ROWS error code, 74  
ER\_REPLICATION\_INCOMPATIBLE\_TABLE\_WITH\_GIPK error code, 629  
ER\_REPLICA\_AM\_INIT\_REPOSITORY error code, 66  
ER\_REPLICA\_ANONYMOUS\_TO\_GTID\_UUID\_SAME\_AS\_GRO error code, 594  
ER\_REPLICA\_ANON\_TO\_GTID\_IS\_LOCAL\_OR\_UUID\_AND\_G error code, 594  
ER\_REPLICA\_CANT\_CREATE\_CONVERSION error code, 49  
ER\_REPLICA\_CANT\_USE\_TEMPDIR error code, 239  
ER\_REPLICA\_CHANGE\_SOURCE\_TO\_EXECUTED error code, 239  
ER\_REPLICA\_CHANNEL\_DOES\_NOT\_EXIST error code, 75  
ER\_REPLICA\_CHANNEL\_IO\_THREAD\_MUST\_STOP error code, 70  
ER\_REPLICA\_CHANNEL\_MUST\_STOP error code, 76  
ER\_REPLICA\_CHANNEL\_NAME\_INVALID\_OR\_TOO\_LONG error code, 75  
ER\_REPLICA\_CHANNEL\_NOT\_RUNNING error code, 76  
ER\_REPLICA\_CHANNEL\_OPERATION\_NOT\_ALLOWED error code, 82  
ER\_REPLICA\_CHANNEL\_SQL\_SKIP\_COUNTER error code, 77  
ER\_REPLICA\_CHANNEL\_SQL\_THREAD\_MUST\_STOP error code, 77  
ER\_REPLICA\_CHANNEL\_WAS\_NOT\_RUNNING error code, 76  
ER\_REPLICA\_CHANNEL\_WAS\_RUNNING error code, 76  
ER\_REPLICA\_CM\_INIT\_REPOSITORY error code, 66  
ER\_REPLICA\_CONFIGURATION error code, 59  
ER\_REPLICA\_CORRUPT\_EVENT error code, 44  
ER\_REPLICA\_CREATE\_EVENT\_FAILURE error code, 528  
ER\_REPLICA\_FATAL\_ERROR error code, 528  
ER\_REPLICA\_HAS\_MORE\_GTIDS\_THAN\_SOURCE error code, 68  
ER\_REPLICA\_HEARTBEAT\_FAILURE error code, 529  
ER\_REPLICA\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE error code, 45  
ER\_REPLICA\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE\_MAX error code, 51  
ER\_REPLICA\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE\_MIN error code, 51  
ER\_REPLICA\_IGNORED\_SSL\_PARAMS error code, 23  
ER\_REPLICA\_IGNORED\_TABLE error code, 20  
ER\_REPLICA\_IGNORE\_SERVER\_IDS error code, 46  
ER\_REPLICA\_INCIDENT error code, 529

---

---

ER\_REPLICA\_KILLED\_AFTER\_RECONNECT error code, 292  
 ER\_REPLICA\_MAX\_CHANNELS\_EXCEEDED error code, 76  
 ER\_REPLICA\_MULTIPLE\_CHANNELS\_CMD error code, 75  
 ER\_REPLICA\_NEW\_CHANNEL\_WRONG\_REPOSITORY error code, 75  
 ER\_REPLICA\_NOT\_RUNNING error code, 17  
 ER\_REPLICA\_NOT\_STARTED\_ON\_SOME\_CHANNELS error code, 292  
 ER\_REPLICA\_POSSIBLY\_DIVERGED\_AFTER\_DDL error code, 110  
 ER\_REPLICA\_RECONNECT\_FAILED error code, 291  
 ER\_REPLICA\_RELAY\_LOG\_PURGE\_FAILED error code, 283  
 ER\_REPLICA\_RELAY\_LOG\_READ\_FAILURE error code, 529  
 ER\_REPLICA\_RELAY\_LOG\_TRUNCATE\_INFO error code, 283  
 ER\_REPLICA\_RELAY\_LOG\_WRITE\_FAILURE error code, 529  
 ER\_REPLICA\_SILENT\_RETRY\_TRANSACTION error code, 61  
 ER\_REPLICA\_SOURCE\_COM\_FAILURE error code, 529  
 ER\_REPLICA\_SQL\_THREAD\_MUST\_STOP error code, 70  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_AFTER\_GTIDS error code, 203  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_BEFORE\_GTIDS error code, 203  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_BEFORE\_GTIDS error code, 203  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_BEFORE\_GTIDS error code, 203  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_GAP\_TRX\_PROCESSED error code, 204  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_UNTIL\_CONDITION met error code, 202  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_UNTIL\_POSITION REACHED error code, 203  
 ER\_REPLICA\_THREAD error code, 18  
 ER\_REPLICA\_WORKER\_STOPPED\_PREVIOUS\_THD\_ERROR error code, 71  
 ER\_REQUIRES\_PRIMARY\_KEY error code, 15  
 ER\_REQUIRE\_ROW\_FORMAT\_INVALID\_VALUE error code, 135  
 ER\_REQUIRE\_TABLE\_PRIMARY\_KEY\_CHECK\_GENERATED error code, 161  
 ER\_REQUIRE\_TABLE\_PRIMARY\_KEY\_CHECK\_GENERATED error code, 632  
 ER\_RESERVED\_SYNTAX error code, 30  
 ER\_RESERVED\_TABLESPACE\_NAME error code, 109  
 ER\_RESET\_MASTER\_TO\_VALUE\_OUT\_OF\_RANGE error code, 92  
 ER\_RESET\_SOURCE\_TO\_VALUE\_OUT\_OF\_RANGE error code, 92  
 ER\_RESIGNAL\_WITHOUT\_ACTIVE\_HANDLER error code, 46  
 ER\_RESOURCE\_GROUP\_BIND\_FAILED error code, 103  
 ER\_RESOURCE\_GROUP\_BUSY error code, 102  
 ER\_RESOURCE\_GROUP\_DISABLED error code, 102  
 ER\_RESOURCE\_GROUP\_EXISTS error code, 102  
 ER\_RESOURCE\_GROUP\_IS\_DISABLED error code, 286  
 ER\_RESOURCE\_GROUP\_METADATA\_UPDATE\_SKIPPED error code, 285  
 ER\_RESOURCE\_GROUP\_NOT\_EXISTS error code, 102  
 ER\_RESOURCE\_GROUP\_POST\_INIT\_FAILED error code, 281  
 ER\_RESOURCE\_GROUP\_SUBSYSTEM\_INIT\_FAILED error code, 281  
 ER\_RESOURCE\_GROUP\_VALIDATION\_FAILED error code, 285  
 ER\_RESTART\_RECEIVED\_INFO error code, 299  
 ER\_RESTART\_SERVER\_FAILED error code, 108  
 ER\_RES\_GRP\_FAILED\_DETERMINE\_CPU\_COUNT error code, 287  
 ER\_RES\_GRP\_FAILED\_TO\_DETERMINE\_NICE\_CAPABILITY error code, 287  
 ER\_RES\_GRP\_FAILED\_TO\_GET\_THREAD\_HANDLE error code, 287  
 ER\_RES\_GRP\_FAILED\_TO\_SWITCH\_RESOURCE\_GROUP error code, 626  
 ER\_RES\_GRP\_FEATURE\_NOT\_AVAILABLE error code, 287  
 ER\_RES\_GRP\_GET\_THREAD\_PRIO\_NOT\_SUPPORTED error code, 287  
 ER\_RES\_GRP\_INVALID\_THREAD\_PRIORITY error code, 287  
 ER\_RES\_GRP\_INVALID\_VCPU\_ID error code, 298  
 ER\_RES\_GRP\_INVALID\_VCPU\_RANGE error code, 297  
 ER\_RES\_GRP\_SET\_THREAD\_PRIORITY\_FAILED error code, 286  
 ER\_RES\_GRP\_SET\_THR\_AFFINITY\_FAILED error code, 286  
 ER\_RES\_GRP\_SET\_THR\_AFFINITY\_TO\_CPUS\_FAILED error code, 286  
 ER\_RES\_GRP\_SOLARIS\_PROCESSOR\_AFFINITY\_FAILED error code, 287  
 ER\_RES\_GRP\_SOLARIS\_PROCESSOR\_BIND\_TO\_CPUID\_FAILED error code, 287  
 ER\_RES\_GRP\_SOLARIS\_PROCESSOR\_BIND\_TO\_THREAD\_FAILED error code, 287  
 ER\_RES\_GRP\_SWITCH\_FAILED\_COULD\_NOT\_ACQUIRE\_GLOBAL error code, 626

---

---

ER\_RES\_GRP\_SWITCH\_FAILED\_COULD\_NOT\_ACQUIRE\_LOCK error code, 626  
 ER\_RES\_GRP\_SWITCH\_FAILED\_UNABLE\_TO\_APPLY\_REPLICATION error code, 626  
 ER\_RES\_GRP\_THD\_UNBIND\_FROM\_CPU\_FAILED error code, 286  
 ER\_RETRYING\_REPAIR\_WITHOUT\_QUICK error code, 258  
 ER\_RETRYING\_REPAIR\_WITH\_KEYCACHE error code, 258  
 ER\_REVOKE\_GRANTS error code, 22  
 ER\_REWRITER\_LOAD\_FAILED error code, 322  
 ER\_REWRITER\_OOM error code, 322  
 ER\_REWRITER\_QUERY\_ERROR\_MSG error code, 318  
 ER\_REWRITER\_QUERY\_FAILED error code, 318  
 ER\_REWRITER\_READ\_FAILED error code, 322  
 ER\_REWRITER\_TABLE\_MALFORMED\_ERROR error code, 322  
 ER\_ROLE\_GRANTED\_TO\_ITSELF error code, 145  
 ER\_ROLE\_NOT\_GRANTED error code, 89  
 ER\_ROW\_DATA\_TOO\_BIG\_TO\_WRITE\_IN\_BINLOG error code, 291  
 ER\_ROW\_DOES\_NOT\_MATCH\_GIVEN\_PARTITION\_SET error code, 54  
 ER\_ROW\_DOES\_NOT\_MATCH\_PARTITION error code, 54  
 ER\_ROW\_IN\_WRONG\_PARTITION error code, 65  
 ER\_ROW\_IN\_WRONG\_PARTITION\_PLEASE\_REPAIR error code, 187  
 ER\_ROW\_IS\_REFERENCED error code, 19  
 ER\_ROW\_IS\_REFERENCED\_2 error code, 34  
 ER\_ROW\_SINGLE\_PARTITION\_FIELD\_ERROR error code, 47  
 ER\_RPL\_AM\_INIT\_INFO\_MSG error code, 296  
 ER\_RPL\_ASYNC\_CHANNEL\_CANT\_CONNECT error code, 592  
 ER\_RPL\_ASYNC\_CHANNEL\_CANT\_CONNECT\_NO\_QUORUM error code, 592  
 ER\_RPL\_ASYNC\_CHANNEL\_STOPPED\_QUORUM\_LOST error code, 592  
 ER\_RPL\_ASYNC\_EXECUTING\_QUERY error code, 592  
 ER\_RPL\_ASYNC\_MANAGED\_NAME\_ADDED error code, 593  
 ER\_RPL\_ASYNC\_MANAGED\_NAME\_REMOVED error code, 593  
 ER\_RPL\_ASYNC\_NEXT\_FAILOVER\_CHANNEL\_SELECTED error code, 633  
 ER\_RPL\_ASYNC\_READ\_FAILOVER\_TABLE error code, 593  
 ER\_RPL\_ASYNC\_RECONNECT\_AUTO\_POSITION\_OFF error code, 141  
 ER\_RPL\_ASYNC\_RECONNECT\_FAIL\_NO\_SOURCE error code, 590  
 ER\_RPL\_ASYNC\_RECONNECT\_GTID\_MODE\_OFF error code, 140  
 ER\_RPL\_ASYNC\_RECONNECT\_GTID\_MODE\_OFF\_CHANNEL error code, 595  
 ER\_RPL\_ASYNC\_SENDER\_ADDED error code, 592  
 ER\_RPL\_ASYNC\_SENDER\_REMOVED error code, 592  
 ER\_RPL\_BINLOG\_FILTERS\_OOM error code, 174  
 ER\_RPL\_BINLOG\_MASTER\_SENDS\_HEARTBEAT error code, 215  
 ER\_RPL\_BINLOG\_MASTER\_USES\_CHECKSUM\_AND\_SLAVE error code, 215  
 ER\_RPL\_BINLOG\_RELAY\_DELEGATES\_INIT\_FAILED error code, 184  
 ER\_RPL\_BINLOG\_SKIPPING\_REMAINING\_HEARTBEAT\_INFORMATION error code, 215  
 ER\_RPL\_BINLOG\_SOURCE\_SENDS\_HEARTBEAT error code, 215  
 ER\_RPL\_BINLOG\_SOURCE\_USES\_CHECKSUM\_AND\_REPLICATION error code, 216  
 ER\_RPL\_BINLOG\_STARTING\_DUMP error code, 215  
 ER\_RPL\_BINLOG\_STORAGE\_DELEGATES\_INIT\_FAILED error code, 184  
 ER\_RPL\_BINLOG\_TRANSMIT\_DELEGATES\_INIT\_FAILED error code, 184  
 ER\_RPL\_CANNOT\_OPEN\_RELAY\_LOG error code, 609  
 ER\_RPL\_CANT\_ADD\_DO\_TABLE error code, 177  
 ER\_RPL\_CANT\_ADD\_IGNORE\_TABLE error code, 177  
 ER\_RPL\_CANT\_CREATE\_REPLICA\_THREAD error code, 227  
 ER\_RPL\_CANT\_CREATE\_SLAVE\_THREAD error code, 227  
 ER\_RPL\_CANT\_FIND\_FOLLOWUP\_FILE error code, 233  
 ER\_RPL\_CANT\_HAVE\_SAME\_BASENAME error code, 277  
 ER\_RPL\_CANT\_INITIALIZE\_GTID\_SETS\_IN\_AM\_INIT\_INFO error code, 240  
 ER\_RPL\_CANT\_INITIALIZE\_GTID\_SETS\_IN\_RLI\_INIT\_INFO error code, 240  
 ER\_RPL\_CANT\_MAKE\_PATHS error code, 179  
 ER\_RPL\_CANT\_OPEN\_INFO\_TABLE error code, 207  
 ER\_RPL\_CANT\_OPEN\_LOG\_IN\_AM\_INIT\_INFO error code, 240  
 ER\_RPL\_CANT\_OPEN\_LOG\_IN\_RLI\_INIT\_INFO error code, 240  
 ER\_RPL\_CANT\_SCAN\_INFO\_TABLE error code, 207  
 ER\_RPL\_CANT\_STOP\_REPLICA\_WHILE\_LOCKED\_BACKUP error code, 125  
 ER\_RPL\_CANT\_STOP\_SLAVE\_WHILE\_LOCKED\_BACKUP error code, 125  
 ER\_RPL\_CHANGING\_APPLIER\_METADATA\_REPO\_TYPE\_FAILED error code, 208

---

---

ER_RPL_CHANGING_RELAY_LOG_INFO_REPO_TYPE_FAILED error code, 208	ER_RPL_ERROR_CHECKING_FOR_LOG error code, 233
ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID error code, 208	ER_RPL_ERROR_READING_MASTER_CONFIGURATION error code, 255
ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPOSITORY error code, 207	ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION error code, 253
ER_RPL_CORRUPTED_INFO_TABLE error code, 207	ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION error code, 253
ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE error code, 207	ER_RPL_ERROR_READING_SOURCE_CONFIGURATION error code, 255
ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY error code, 119	ER_RPL_ERROR_WRITING_MASTER_CONFIGURATION error code, 255
ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT error code, 119	ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION error code, 241
ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY error code, 117	ER_RPL_ERROR_WRITING_SLAVE_WORKER_CONFIGURATION error code, 254
ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY error code, 117	ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION error code, 255
ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY error code, 117	ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE error code, 211
ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS error code, 117	ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE error code, 211
ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY error code, 117	ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKERS_INFO error code, 209
ER_RPL_ENCRYPTION_HEADER_ERROR error code, 117	ER_RPL_FAILED_TO_DELETE_FROM_SLAVE_WORKERS_INFO error code, 209
ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY error code, 117	ER_RPL_FAILED_TO_OPEN_INFO_FILE error code, 211
ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED error code, 117	ER_RPL_FAILED_TO_OPEN_RELAY_LOG error code, 254
ER_RPL_ENCRYPTION_KEY_NOT_FOUND error code, 117	ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO_REPOSITORY error code, 209
ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED error code, 118	ER_RPL_FAILED_TO_RESET_STATE_IN_SLAVE_INFO_REPOSITORY error code, 209
ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION error code, 118	ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX error code, 255
ER_RPL_ERROR_CHANGING_APPLIER_METADATA_REMOTE error code, 209	ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL error code, 292
ER_RPL_ERROR_CHANGING_CONNECTION_METADATA_REMOTE error code, 208	ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED error code, 282
ER_RPL_ERROR_CHANGING_MASTER_INFO_REPO_TYPE error code, 208	ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED error code, 282
ER_RPL_ERROR_CHANGING_RELAY_LOG_INFO_REPO_TYPE error code, 209	ER_RPL_GTID_LOG_EVENT_IN_STREAM error code, 213
ER_RPL_ERROR_CHECKING_REPOSITORY error code, 210	ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE error code, 211
ER_RPL_ERROR_CREATING_APPLIER_METADATA error code, 209	ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY error code, 278
ER_RPL_ERROR_CREATING_CONNECTION_METADATA error code, 208	ER_RPL_GTID_TABLE_CANNOT_OPEN error code, 164
ER_RPL_ERROR_CREATING_MASTER_INFO error code, 208	ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION error code, 542
ER_RPL_ERROR_CREATING_RELAY_LOG_INFO error code, 209	ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT error code, 526



---

ER\_RPL\_GTID\_UNSAFE\_STMT\_ON\_NON\_TRANS\_TABLE error code, 526  
 ER\_RPL\_GTID\_UNSAFE\_STMT\_ON\_TEMPORARY\_TABLE error code, 526  
 ER\_RPL\_INCOMPATIBLE\_DECIMAL\_IN\_RBR error code, 214  
 ER\_RPL\_INCONSISTENT\_SEQUENCE\_NO\_IN\_TRX error code, 207  
 ER\_RPL\_INCONSISTENT\_TIMESTAMPS\_IN\_TRX error code, 207  
 ER\_RPL\_INCREMENTING\_MEMBER\_ACTION\_VERSION error code, 607  
 ER\_RPL\_INFINITY\_DENIED error code, 182  
 ER\_RPL\_INFINITY\_IGNORED error code, 182  
 ER\_RPL\_INFO\_DATA\_TOO\_LONG error code, 54  
 ER\_RPL\_IO\_THREAD\_KILLED error code, 291  
 ER\_RPL\_KILL\_OLD\_DUMP\_THREAD\_ENCOUNTERED error code, 642  
 ER\_RPL\_LOG\_ENTRY\_EXCEEDS\_REPLICA\_MAX\_ALLOWED error code, 232  
 ER\_RPL\_LOG\_ENTRY\_EXCEEDS\_SLAVE\_MAX\_ALLOWED error code, 231  
 ER\_RPL\_LOG\_NOT\_FOUND\_WHILE\_COUNTING\_RELAY error code, 239  
 ER\_RPL\_MTA\_ALLOW\_COMMIT\_OUT\_OF\_ORDER error code, 642  
 ER\_RPL\_MTA\_AUTOMATIC\_RECOVERY\_FAILED error code, 226  
 ER\_RPL\_MTA\_CHECKPOINT\_PERIOD\_DIFFERS\_FROM\_MTA error code, 234  
 ER\_RPL\_MTA\_GROUP\_RECOVERY\_APPLIER\_METADATA\_ERROR error code, 233  
 ER\_RPL\_MTA\_GROUP\_RECOVERY\_APPLIER\_METADATA\_ERROR\_FOR\_WRITE error code, 233  
 ER\_RPL\_MTA\_RECOVERY\_CANT\_OPEN\_RELAY\_LOG error code, 226  
 ER\_RPL\_MTA\_RECOVERY\_COMPLETE error code, 230  
 ER\_RPL\_MTA\_RECOVERY\_FAILED\_TO\_START\_COORDINATOR error code, 226  
 ER\_RPL\_MTA\_RECOVERY\_STARTING\_COORDINATOR error code, 226  
 ER\_RPL\_MTA\_RECOVERY\_SUCCESSFUL error code, 227  
 ER\_RPL\_MTA\_REPLICA\_COORDINATOR\_HAS\_WAITED error code, 254  
 ER\_RPL\_MTA\_STATISTICS error code, 230  
 ER\_RPL\_MTS\_AUTOMATIC\_RECOVERY\_FAILED error code, 226  
 ER\_RPL\_MTS\_CHECKPOINT\_PERIOD\_DIFFERS\_FROM\_MTA error code, 233  
 ER\_RPL\_MTS\_GROUP\_RECOVERY\_RELAY\_LOG\_INFO\_FOR error code, 233  
 ER\_RPL\_MTS\_GROUP\_RECOVERY\_RELAY\_LOG\_INFO\_FOR error code, 233  
 ER\_RPL\_MTS\_RECOVERY\_CANT\_OPEN\_RELAY\_LOG error code, 226  
 ER\_RPL\_MTS\_RECOVERY\_COMPLETE error code, 230  
 ER\_RPL\_MTS\_RECOVERY\_FAILED\_TO\_START\_COORDINATOR error code, 226  
 ER\_RPL\_MTS\_RECOVERY\_STARTING\_COORDINATOR error code, 225  
 ER\_RPL\_MTS\_RECOVERY\_SUCCESSFUL error code, 226  
 ER\_RPL\_MTS\_SLAVE\_COORDINATOR\_HAS\_WAITED error code, 254  
 ER\_RPL\_MTS\_STATISTICS error code, 230  
 ER\_RPL\_MULTISOURCE\_REQUIRES\_TABLE\_TYPE\_REPOSITION error code, 210  
 ER\_RPL\_OPEN\_INDEX\_FILE\_FAILED error code, 240  
 ER\_RPL\_PLUGIN\_USE\_OPTION\_RELAY\_LOG error code, 240  
 ER\_RPL\_PLUGIN\_FUNCTION\_FAILED error code, 184  
 ER\_RPL\_RECOVERY\_ERROR error code, 225  
 ER\_RPL\_RECOVERY\_ERROR\_FREEING\_IO\_CACHE error code, 225  
 ER\_RPL\_RECOVERY\_ERROR\_READ\_RELAY\_LOG error code, 224  
 ER\_RPL\_RECOVERY\_FILE\_MASTER\_POS\_INFO error code, 225  
 ER\_RPL\_RECOVERY\_FILE\_SOURCE\_POS\_INFO error code, 225  
 ER\_RPL\_RECOVERY\_IO\_ERROR\_READING\_RELAY\_LOG\_INFO error code, 225  
 ER\_RPL\_RECOVERY\_NO\_ROTATE\_EVENT\_FROM\_MASTER error code, 224  
 ER\_RPL\_RECOVERY\_NO\_ROTATE\_EVENT\_FROM\_SOURCE error code, 224  
 ER\_RPL\_RECOVERY\_REPLICATE\_SAME\_SERVER\_ID\_REQUIRED error code, 225  
 ER\_RPL\_RECOVERY\_SKIPPED\_GROUP\_REPLICATION\_CHANNEL error code, 225  
 ER\_RPL\_RELAY\_LOG\_INDEX\_NEEDS\_FILE\_NOT\_DIRECTORY error code, 240  
 ER\_RPL\_RELAY\_LOG\_NEEDS\_FILE\_NOT\_DIRECTORY error code, 240  
 ER\_RPL\_RELAY\_LOG\_RECOVERY\_GTID\_ONLY error code, 613  
 ER\_RPL\_RELAY\_LOG\_RECOVERY\_INFO\_AFTER\_CLONE error code, 576  
 ER\_RPL\_REPLICA\_ADDITIONAL\_ERROR\_INFO\_FROM\_DATA error code, 235  
 ER\_RPL\_REPLICA\_AUTO\_POSITION\_IS\_1\_AND\_GTID\_MODE error code, 224  
 ER\_RPL\_REPLICA\_CANT\_FLUSH\_CONNECTION\_METADATA error code, 228

---

---

ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER error code, 233	ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE error code, 276
ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION error code, 230	ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_RELAY error code, 232
ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNEL error code, 224	ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SOURCE error code, 231
ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNEL error code, 224	ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED_EVENT error code, 237
ER_RPL_REPLICA_CANT_USE_CHARSET error code, 237	ER_RPL_REPLICA_IO_THREAD_EXITING error code, 232
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICA_FROM_PRESUMED error code, 237	ER_RPL_REPLICA_IO_THREAD_KILLED error code, 231
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 633	ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 526
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_THREAD_WAS_KILLED error error code, 633	ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING code, 227
ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_LIST error code, 210	ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING error code, 593
ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE error code, 229	ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_CHANNEL error code, 593
ER_RPL_REPLICA_ERROR_INFO_FROM_DA error code, 235	ER_RPL_REPLICA_NEW_C_M_NEEDS_REPOS_TYPE_OTHER_THAN_C_M error code, 239
ER_RPL_REPLICA_ERROR_LOADING_USER_DEFINED_EVENTS error code, 236	ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE error code, 238
ER_RPL_REPLICA_ERROR_READING_FROM_SERVER error code, 229	ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE error code, 238
ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS error code, 238	ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION error code, 237
ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP error code, 231	ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_NON_ROW_FORMAT error code, 573
ER_RPL_REPLICA_ERROR_RETRYING error code, 229	ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE error code, 236
ER_RPL_REPLICA_ERROR_RUNNING_QUERY error code, 236	ER_RPL_REPLICA_REPORT_HOST_TOO_LONG error code, 228
ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL_FROM_CONNECTION_INFORMATION error code, 211	ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG error code, 229
ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER_BINLOG_REPOSitories error code, 223	ER_RPL_REPLICA_REPORT_USER_TOO_LONG error code, 228
ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_METADATA_STRUCTURE error code, 210	ER_RPL_REPLICA_SKIP_COUNTER_OVERFLOW error code, 284
ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA_STRUCTURE error code, 211	ER_RPL_REPLICA_SKIP_COUNTER_OVERFLOW error code, 228
ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HASH error code, 234	ER_RPL_REPLICA_SKIP_COUNTER_OVERFLOW error code, 235
ER_RPL_REPLICA_FILTER_CREATE_FAILED error code, 283	ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED_HOST_PORT error code, 633
ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD error code, 231	ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED error code, 633
ER_RPL_REPLICA_GENERIC_MESSAGE error code, 210	ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CHANGED error code, 633
ER_RPL_REPLICA_GLOBAL_FILTERS_COPY_FAILED error code, 284	ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED_EVENT error code, 573
ER_RPL_REPLICA_INCORRECT_CHANNEL error code, 276	ER_RPL_REPLICA_SQL_THREAD_EXITING error code, 236

---

---

ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_FROM_SERVER error code, 238	ER_RPL_SLAVE_ERROR_READING_FROM_SERVER error code, 229
ER_RPL_REPLICA_SQL_THREAD_STARTING error code, 235	ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENTS error code, 238
ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_PRIMARY_CHECKSUM_ERROR error code, 571	ER_RPL_SLAVE_ERROR_REQUESTING_BINLOG_DUMP error code, 231
ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 526	ER_RPL_SLAVE_ERROR_RETRYING error code, 229
ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM error code, 232	ER_RPL_SLAVE_ERROR_RUNNING_QUERY error code, 236
ER_RPL_REPLICA_USES_CHECKSUM_AND_SOURCE_POS error code, 227	ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM_MASTER error code, 211
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED error code, 234	ER_RPL_SLAVE_FAILED_TO_CREATE_OR_RECOVER_INFO error code, 223
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED_WITH_ERROR error code, 234	ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE error code, 211
ER_RPL_REPO_HAS_GAPS error code, 165	ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRUCTURE error code, 211
ER_RPL_REPO_SHOULD_BE_TABLE error code, 208	ER_RPL_SLAVE_FAILED_TO_INIT_PARTITIONS_HASH error code, 234
ER_RPL_REWRITEDB_EMPTY_FROM error code, 178	ER_RPL_SLAVE_FILTER_CREATE_FAILED error code, 283
ER_RPL_REWRITEDB_EMPTY_TO error code, 178	ER_RPL_SLAVE_FLUSH_RELAY_LOGS_NOT_ALLOWED error code, 276
ER_RPL_REWRITEDB_MISSING_ARROW error code, 178	ER_RPL_SLAVE_FORCING_TO_RECONNECT_IO_THREAD error code, 231
ER_RPL_RLI_INIT_INFO_MSG error code, 296	ER_RPL_SLAVE_GENERIC_MESSAGE error code, 210
ER_RPL_SERVER_ID_MISSING error code, 227	ER_RPL_SLAVE_GLOBAL_FILTERS_COPY_FAILED error code, 283
ER_RPL_SLAVE_ADDITIONAL_ERROR_INFO_FROM_DATA error code, 235	ER_RPL_SLAVE_INCORRECT_CHANNEL error code, 276
ER_RPL_SLAVE_APPLY_LOG_EVENT_FAILED_INVALID_POSITION error code, 573	ER_RPL_SLAVE_INSECURE_CHANGE_MASTER error code, 275
ER_RPL_SLAVE_AUTO_POSITION_IS_1_AND_GTID_MODE error code, 223	ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_RELAY error code, 232
ER_RPL_SLAVE_CANT_FLUSH_MASTER_INFO_FILE error code, 228	ER_RPL_SLAVE_IO_THREAD_CANT_REGISTER_ON_MASTER error code, 231
ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER error code, 232	ER_RPL_SLAVE_IO_THREAD_DETECTED_UNEXPECTED_EVENT error code, 237
ER_RPL_SLAVE_CANT_INIT_RELAY_LOG_POSITION error code, 230	ER_RPL_SLAVE_IO_THREAD_EXITING error code, 232
ER_RPL_SLAVE_CANT_START_SLAVE_FOR_CHANNEL error code, 224	ER_RPL_SLAVE_IO_THREAD_KILLED error code, 231
ER_RPL_SLAVE_CANT_STOP_SLAVE_FOR_CHANNEL error code, 224	ER_RPL_SLAVE_IO_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 526
ER_RPL_SLAVE_CANT_USE_CHARSET error code, 237	ER_RPL_SLAVE_IO_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 526
ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION error code, 237	ER_RPL_SLAVE_IO_THREAD_WAS_KILLED error code, 231
ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION error code, 230	ER_RPL_SLAVE_MASTER_UUID_HAS_CHANGED error code, 227
ER_RPL_SLAVE_COULD_NOT_CREATE_CHANNEL_LIST error code, 210	ER_RPL_SLAVE_NDB_TABLES_NOT_AVAILABLE error code, 234
ER_RPL_SLAVE_DUMP_THREAD_KILLED_BY_MASTER error code, 229	ER_RPL_SLAVE_NEW_MASTER_INFO_NEEDS_REPOS_TYPE error code, 239
ER_RPL_SLAVE_ERROR_INFO_FROM_DATA error code, 235	ER_RPL_SLAVE_NEXT_LOG_IS_ACTIVE error code, 236
ER_RPL_SLAVE_ERROR_LOADING_USER_DEFINED_LIBRARY error code, 236	

---

---

ER\_RPL\_SLAVE\_NEXT\_LOG\_IS\_INACTIVE error code, 238  
 ER\_RPL\_SLAVE\_QUEUE\_EVENT\_FAILED\_INVALID\_CONNECTION error code, 237  
 ER\_RPL\_SLAVE\_QUEUE\_EVENT\_FAILED\_INVALID\_NONERROWFORWORKER error code, 573  
 ER\_RPL\_SLAVE\_READ\_INVALID\_EVENT\_FROM\_MASTER error code, 236  
 ER\_RPL\_SLAVE\_REPORT\_HOST\_TOO\_LONG error code, 228  
 ER\_RPL\_SLAVE\_REPORT\_PASSWORD\_TOO\_LONG error code, 229  
 ER\_RPL\_SLAVE\_REPORT\_USER\_TOO\_LONG error code, 228  
 ER\_RPL\_SLAVE\_RESET\_FILTER\_OPTIONS error code, 284  
 ER\_RPL\_SLAVE\_SECONDS\_BEHIND\_MASTER\_DUBIOUS error code, 228  
 ER\_RPL\_SLAVE\_SKIP\_COUNTER\_EXECUTED error code, 235  
 ER\_RPL\_SLAVE\_SQL\_THREAD\_DETECTED\_UNEXPECTED\_SEQUENCE error code, 573  
 ER\_RPL\_SLAVE\_SQL\_THREAD\_EXITING error code, 236  
 ER\_RPL\_SLAVE\_SQL\_THREAD\_IO\_ERROR\_READING\_EVENTS error code, 238  
 ER\_RPL\_SLAVE\_SQL\_THREAD\_STARTING error code, 235  
 ER\_RPL\_SLAVE\_SQL\_THREAD\_STARTING\_WITH\_PRIVILEGES error code, 571  
 ER\_RPL\_SLAVE\_SQL\_THREAD\_STOP\_CMD\_EXEC\_TIMEOUT error code, 525  
 ER\_RPL\_SLAVE\_STOPPING\_AS\_MASTER\_OOM error code, 232  
 ER\_RPL\_SLAVE\_USES\_CHECKSUM\_AND\_MASTER\_PROTOCOL error code, 227  
 ER\_RPL\_SLAVE\_WORKER\_THREAD\_CREATION\_FAILED error code, 234  
 ER\_RPL\_SLAVE\_WORKER\_THREAD\_CREATION\_FAILED\_WITH\_ERRNO error code, 234  
 ER\_RPL\_SSL\_INFO\_IN\_CONNECTION\_METADATA\_IGNORED error code, 255  
 ER\_RPL\_SSL\_INFO\_IN\_MASTER\_INFO\_IGNORED error code, 255  
 ER\_RPL\_TIMESTAMPS\_RETURNED\_TO\_NORMAL error code, 282  
 ER\_RPL\_TRX\_DELEGATES\_INIT\_FAILED error code, 183  
 ER\_RPL\_UNEXPECTED\_BEGIN\_IN\_STREAM error code, 213  
 ER\_RPL\_UNEXPECTED\_COMMIT\_ROLLBACK\_OR\_XID\_ERROR\_IN\_STREAM error code, 213  
 ER\_RPL\_UNEXPECTED\_XA\_ROLLBACK\_IN\_STREAM error code, 213  
 ER\_RPL\_UNSUPPORTED\_UNIGNORABLE\_EVENT\_IN\_STREAM error code, 213  
 ER\_RPL\_WORKER\_CANT\_FIND\_NEXT\_RELAY\_LOG error code, 254  
 ER\_RPL\_WORKER\_CANT\_READ\_RELAY\_LOG error code, 254  
 ER\_RPL\_WORKER\_ID\_IS error code, 207  
 ER\_RPL\_ZOMBIE\_ENCOUNTED error code, 164  
 ER\_RUNNING\_APPLIER\_PREVENTS\_SWITCH\_GLOBAL\_BINLOG error code, 112  
 ER\_RUN\_HOOK\_ERROR error code, 78  
 ER\_SAME\_NAME\_PARTITION error code, 38  
 ER\_SAME\_NAME\_PARTITION\_FIELD error code, 47  
 ER\_SCHEDULER\_KILLING error code, 168  
 ER\_SCHEDULER\_STARTED error code, 167  
 ER\_SCHEDULER\_STOPPED error code, 167  
 ER\_SCHEDULER\_STOPPING\_FAILED\_TO\_CREATE\_WORKER error code, 168  
 ER\_SCHEDULER\_STOPPING\_FAILED\_TO\_GET\_EVENT error code, 168  
 ER\_SEND\_SEQUENCE\_NUMBER error code, 167  
 ER\_SCHEMA\_DIR\_CREATE\_FAILED error code, 105  
 ER\_SCHEMA\_DIR\_EXISTS error code, 105  
 ER\_SCHEMA\_DIR\_MISSING error code, 105  
 ER\_SCHEMA\_DIR\_UNKNOWN error code, 105  
 ER\_SCHEMA\_NAME\_IN\_UPPER\_CASE\_NOT\_ALLOWED error code, 575  
 ER\_SCHEMA\_NAME\_IN\_UPPER\_CASE\_NOT\_ALLOWED\_FOR\_FOREIGN\_KEYS error code, 575  
 ER\_SCHEMA\_READ\_ONLY error code, 140  
 ER\_SDI\_GET\_KEYS\_INVALID\_TABLESPACE error code, 146  
 ER\_SDI\_OPERATION\_FAILED error code, 103  
 ER\_SDI\_OPERATION\_FAILED\_MISSING\_RECORD error code, 136  
 ER\_SECONDARY\_ENGINE error code, 128  
 ER\_SECONDARY\_ENGINE\_DDL error code, 129  
 ER\_SECONDARY\_ENGINE\_DDL\_FAILED error code, 130  
 ER\_SECONDARY\_ENGINE\_DDL\_FAILED\_WITH\_ERRNO error code, 130  
 ER\_SECONDARY\_ENGINE\_PLUGIN error code, 127  
 ER\_SECOND\_PASSWORD\_CANNOT\_BE\_EMPTY error code, 127  
 ER\_SECURE\_AUTH\_VALUE\_UNSUPPORTED error code, 170  
 ER\_SECURE\_TRANSPORT\_REQUIRED error code, 83  
 ER\_SEC\_FILE\_PRIV\_ARGUMENT\_TOO\_LONG error code, 173  
 ER\_SEC\_FILE\_PRIV\_CANT\_ACCESS\_DIR error code, 172  
 ER\_SEC\_FILE\_PRIV\_CANT\_STAT error code, 173  
 ER\_SECONDARY\_ENGINE\_DIRECTORY\_INSECURE error code, 173  
 ER\_SEC\_FILE\_PRIV\_DIRECTORY\_PERMISSIONS error code, 173

---

---

ER\_SEC\_FILE\_PRIV\_EMPTY error code, 172  
 ER\_SEC\_FILE\_PRIV\_IGNORED error code, 172  
 ER\_SEC\_FILE\_PRIV\_NULL error code, 172  
 ER\_SELECT\_REDUCED error code, 21  
 ER\_SEMISYNC\_ADD\_ACK\_TO\_SLOT error code, 308  
 ER\_SEMISYNC\_BINLOG\_REPLY\_IS\_AHEAD error code, 306  
 ER\_SEMISYNC\_BINLOG\_WRITE\_OUT\_OF\_ORDER error code, 304  
 ER\_SEMISYNC\_CLEARED\_ACTIVE\_TRANSACTION\_TILL\_POS error code, 304  
 ER\_SEMISYNC\_CLEARED\_ALL\_ACTIVE\_TRANSACTION\_NODES error code, 304  
 ER\_SEMISYNC\_DISABLED\_ON\_MASTER error code, 305  
 ER\_SEMISYNC\_DISABLED\_ON\_SOURCE error code, 305  
 ER\_SEMISYNC\_EXECUTION\_FAILED\_ON\_MASTER error code, 311  
 ER\_SEMISYNC\_EXECUTION\_FAILED\_ON\_SOURCE error code, 311  
 ER\_SEMISYNC\_FAILED\_REGISTER\_REPLICA\_TO\_RECEIVER error code, 309  
 ER\_SEMISYNC\_FAILED\_REGISTER\_SLAVE\_TO\_RECEIVER error code, 309  
 ER\_SEMISYNC\_FAILED\_TO\_ALLOCATE\_TRX\_NODE error code, 304  
 ER\_SEMISYNC\_FAILED\_TO\_INSERT\_TRX\_NODE error code, 307  
 ER\_SEMISYNC\_FAILED\_TO\_START\_ACK\_RECEIVER\_THREADS error code, 308  
 ER\_SEMISYNC\_FAILED\_TO\_STOP\_ACK\_RECEIVER\_THREADS error code, 312  
 ER\_SEMISYNC\_FAILED\_TO\_WAIT\_ON\_DUMP\_SOCKET error code, 308  
 ER\_SEMISYNC\_FORCED\_SHUTDOWN error code, 305  
 ER\_SEMISYNC\_FUNCTION\_CALLED\_TWICE error code, 305  
 ER\_SEMISYNC\_INIT\_WAIT\_POS error code, 306  
 ER\_SEMISYNC\_INSERT\_LOG\_INFO\_IN\_ENTRY error code, 304  
 ER\_SEMISYNC\_MASTER\_FAILED\_ON\_NET\_FLUSH error code, 308  
 ER\_SEMISYNC\_MASTER\_GOT\_REPLY\_AT\_POS error code, 306  
 ER\_SEMISYNC\_MASTER\_OOM error code, 305  
 ER\_SEMISYNC\_MASTER\_SIGNAL\_ALL\_WAITING\_THREADS error code, 306  
 ER\_SEMISYNC\_MASTER\_TRX\_WAIT\_POS error code, 306  
 ER\_SEMISYNC\_MISSING\_MAGIC\_NO\_FOR\_SEMISYNC\_PKT error code, 310  
 ER\_SEMISYNC\_MOVE\_BACK\_WAIT\_POS error code, 306  
 ER\_SEMISYNC\_NOT\_SUPPORTED\_BY\_MASTER error code, 312  
 ER\_SEMISYNC\_NOT\_SUPPORTED\_BY\_SOURCE error code, 312  
 ER\_SEMISYNC\_NO\_SPACE\_IN\_THE\_PKT error code, 307  
 ER\_SEMISYNC\_PROBE\_LOG\_INFO\_IN\_ENTRY error code, 304  
 ER\_SEMISYNC\_RECEIVED\_ACK\_IS\_SMALLER error code, 308  
 ER\_SEMISYNC\_REPLICA\_NET\_FLUSH\_REPLY\_FAILED error code, 311  
 ER\_SEMISYNC\_REPLICA\_REPLY error code, 310  
 ER\_SEMISYNC\_REPLICA\_REPLY\_WITH\_BINLOG\_INFO error code, 311  
 ER\_SEMISYNC\_REPLICA\_SEND\_REPLY\_FAILED error code, 311  
 ER\_SEMISYNC\_REPLICA\_SET\_FAILED error code, 312  
 ER\_SEMISYNC\_REPLICA\_START error code, 310  
 ER\_SEMISYNC\_REPLY\_BINLOG\_FILE\_TOO\_LARGE error code, 305  
 ER\_SEMISYNC\_REPLY\_MAGIC\_NO\_ERROR error code, 304  
 ER\_SEMISYNC\_REPLY\_PKT\_LENGTH\_TOO\_SMALL error code, 304  
 ER\_SEMISYNC\_RPL\_ENABLED\_ON\_MASTER error code, 305  
 ER\_SEMISYNC\_RPL\_ENABLED\_ON\_SOURCE error code, 305  
 ER\_SEMISYNC\_RPL\_INIT\_FOR\_TRX error code, 304  
 ER\_SEMISYNC\_RPL\_SWITCHED\_OFF error code, 307  
 ER\_SEMISYNC\_RPL\_SWITCHED\_ON error code, 307  
 ER\_SEMISYNC\_SERVER\_REPLY error code, 305  
 ER\_SEMISYNC\_SLAVE\_NET\_FLUSH\_REPLY\_FAILED error code, 311  
 ER\_SEMISYNC\_SLAVE\_REPLY error code, 310  
 ER\_SEMISYNC\_SLAVE\_REPLY\_WITH\_BINLOG\_INFO error code, 311  
 ER\_SEMISYNC\_SLAVE\_SEND\_REPLY\_FAILED error code, 311  
 ER\_SEMISYNC\_SLAVE\_SET\_FAILED error code, 312  
 ER\_SEMISYNC\_SLAVE\_START error code, 310  
 ER\_SEMISYNC\_SOCKET\_FD\_TOO\_LARGE error code, 310  
 ER\_SEMISYNC\_SOURCE\_FAILED\_ON\_NET\_FLUSH error code, 308  
 ER\_SEMISYNC\_SOURCE\_GOT\_REPLY\_AT\_POS error code, 306  
 ER\_SEMISYNC\_SOURCE\_OOM error code, 305  
 ER\_SEMISYNC\_SOURCE\_SIGNAL\_ALL\_WAITING\_THREADS error code, 306  
 ER\_SEMISYNC\_SOURCE\_TRX\_WAIT\_POS error code, 306

---

---

ER_SEMISYNC_STARTING_ACK_RECEIVER_THD error code, 308	ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE error code, 532
ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA error code, 309	ER_SERVER_COST_FAILED_TO_READ error code, 212
ER_SEMISYNC_START_BINLOG_DUMP_TO_SLAVE error code, 309	ER_SERVER_COST_INVALID_COST_CONSTANT error code, 212
ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD error code, 309	ER_SERVER_COST_UNKNOWN_COST_CONSTANT error code, 212
ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA error code, 309	ER_SERVER_DISK_FULL_NOWAIT error code, 531
ER_SEMISYNC_STOP_BINLOG_DUMP_TO_SLAVE error code, 309	ER_SERVER_DOWNGRADE_FROM_VERSION error code, 640
ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO error code, 307	ER_SERVER_DOWNGRADE_STATUS error code, 640
ER_SEMISYNC_TRACE_ENTER_FUNC error code, 303	ER_SERVER_FILE_NOT_FOUND error code, 531
ER_SEMISYNC_TRACE_EXIT error code, 303	ER_SERVER_FILE_USED error code, 531
ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE error code, 303	ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN error code, 542
ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE error code, 303	ER_SERVER_HANDLER_ERROR error code, 531
ER_SEMISYNC_TRX_SKIPPED_AT_POS error code, 307	ER_SERVER_INIT_COMPILED_IN_COMMANDS error code, 296
ER_SEMISYNC_UNREGISTERED_REPLICATOR error code, 310	ER_SERVER_ISNT_AVAILABLE error code, 84
ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER error code, 310	ER_SERVER_IS_IN_SECURE_AUTH_MODE error code, 23
ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER error code, 310	ER_SERVER_MASTER_FATAL_ERROR_READING_BINLOG error code, 528
ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED error code, 309	ER_SERVER_PACKET_TOO_LARGE error code, 530
ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK error code, 308	ER_SERVER_SLAVE_NEW_ABORTING_CONNECTION error code, 531
ER_SEMISYNC_UPDATE_EXISTING_SLAVE_ACK error code, 308	ER_SERVER_NOT_FORM_FILE error code, 531
ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT error code, 307	ER_SERVER_NO_SESSION_TO_SEND_TO error code, 530
ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMENT error code, 307	ER_SERVER_NO_SYSTEM_TABLE_ACCESS error code, 530
ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT error code, 307	ER_SERVER_OFFLINE_MODE error code, 71
ER_SERVERID_TOO_LARGE error code, 182	ER_SERVER_OUTOFMEMORY error code, 280
ER_SERVER_ACL_TABLE_ERROR error code, 532	ER_SERVER_OUT_OF_RESOURCES error code, 280
ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_SYNC error code, 557	ER_SERVER_OUT_OF_SORTMEMORY error code, 531
ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAILED error code, 557	ER_SERVER_RECORD_FILE_FULL error code, 531
ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION error code, 561	ER_SERVER_REPLICA_AM_INIT_REPOSITORY error code, 530
ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2 error code, 531	ER_SERVER_REPLICA_CM_INIT_REPOSITORY error code, 530
ER_SERVER_CANT_OPEN_FILE error code, 531	ER_SERVER_REPLICA_CONVERSION_FAILED error code, 532
ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED error code, 532	ER_SERVER_REPLICA_IGNORED_TABLE error code, 533
	ER_SERVER_REPLICA_INIT_QUERY_FAILED error code, 532
	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT error code, 552
	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY error code, 547

---

---

ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY error code, 548	ER_SERVER_UPGRADE_HELP_TABLE_STATUS error code, 561
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY error code, 548	ER_SERVER_UPGRADE_INFO_FILE error code, 559
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_KEYS error code, 548	ER_SERVER_UPGRADE_MYSQL_TABLES error code, 559
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY error code, 548	ER_SERVER_UPGRADE_NO_SYS_VERSION error code, 559
ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR error code, 548	ER_SERVER_UPGRADE_OFF error code, 558
ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER_KEY error code, 549	ER_SERVER_UPGRADE_PENDING error code, 558
ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY error code, 548	ER_SERVER_UPGRADE_REPAIR_REQUIRED error code, 559
ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED error code, 548	ER_SERVER_UPGRADE_REPAIR_STATUS error code, 559
ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND error code, 547	ER_SERVER_UPGRADE_SKIP error code, 558
ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED error code, 548	ER_SERVER_UPGRADE_STATUS error code, 559
ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE error code, 549	ER_SERVER_UPGRADE_SYSTEM_TABLES error code, 559
ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER_KEY error code, 549	ER_SERVER_UPGRADE_SYS_SCHEMA error code, 559
ER_SERVER_SHUTDOWN error code, 7	ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT error code, 560
ER_SERVER_SHUTDOWN_COMPLETE error code, 277	ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED error code, 560
ER_SERVER_SHUTDOWN_INFO error code, 535	ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE error code, 560
ER_SERVER_SLAVE_CONVERSION_FAILED error code, 532	ER_SERVER_UPGRADE_SYS_VERSION_EMPTY error code, 559
ER_SERVER_SLAVE_IGNORED_TABLE error code, 533	ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED error code, 553
ER_SERVER_SLAVE_INIT_QUERY_FAILED error code, 532	ER_SERVER_WARN_DEPRECATED error code, 556
ER_SERVER_SLAVE_MI_INIT_REPOSITORY error code, 530	ER_SERVER_WRONG_VALUE_FOR_VAR error code, 541
ER_SERVER_SLAVE_RLI_INIT_REPOSITORY error code, 530	ER_SESSION_WAS_KILLED error code, 84
ER_SERVER_SOURCE_FATAL_ERROR_READING_BINLOG error code, 528	ER_SETNS_FAILED error code, 562
ER_SERVER_STARTUP_ADMIN_INTERFACE error code, 549	ER_SET_CONSTANTS_ONLY error code, 18
ER_SERVER_STARTUP_MSG error code, 280	ER_SET_EVENT_FAILED error code, 536
ER_SERVER_TABLE_CHECK_FAILED error code, 532	ER_SET_PASSWORD_AUTH_PLUGIN error code, 50
ER_SERVER_TEST_MESSAGE error code, 533	ER_SET_PASSWORD_AUTH_PLUGIN_ERROR error code, 155
ER_SERVER_UNKNOWN_ERROR error code, 530	ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION error code, 57
ER_SERVER_UNKNOWN_SYSTEM_VARIABLE error code, 530	ER_SE_TYPECODE_CONFLICT error code, 187
ER_SERVER_UPGRADE_CHECKING_DB error code, 560	ER_SHA256_PASSWORD_SECOND_PASSWORD_USED_INFO error code, 550
ER_SERVER_UPGRADE_EMPTY_SYS error code, 559	ER_SHAPE_PREDICTION_UDF error code, 157
ER_SERVER_UPGRADE_FAILED error code, 558	ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE error code, 543
ER_SERVER_UPGRADE_FROM_VERSION error code, 553	ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL error code, 319
	ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH error code, 319
	ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING error code, 319
	ER_SHA_PWD_RSA_KEY_TOO_LONG error code, 319

---

---

ER\_SHA\_PWD\_SALT\_FOR\_USER\_CORRUPT error code, 320  
 ER\_SHUTDOWN\_COMPLETE error code, 8  
 ER\_SHUTTING\_DOWN\_REPLICA\_THREADS error code, 174  
 ER\_SHUTTING\_DOWN\_SLAVE\_THREADS error code, 174  
 ER\_SIGNAL\_BAD\_CONDITION\_TYPE error code, 46  
 ER\_SIGNAL\_EXCEPTION error code, 46  
 ER\_SIGNAL\_NOT\_FOUND error code, 46  
 ER\_SIGNAL\_WARN error code, 46  
 ER\_SIZE\_OVERFLOW\_ERROR error code, 39  
 ER\_SKIP\_UPDATING\_METADATA\_IN\_SE\_RO\_MODE error code, 290  
 ER\_SLAVE\_ANONYMOUS\_TO\_GTID\_IS\_LOCAL\_OR\_USER\_DEFINED\_NOT\_STARTED\_ON\_SOME\_CHANNELS error code, 593  
 ER\_SLAVE\_CANT\_CREATE\_CONVERSION error code, 49  
 ER\_SLAVE\_CANT\_USE\_TEMPDIR error code, 239  
 ER\_SLAVE\_CHANGE\_MASTER\_TO\_EXECUTED error code, 239  
 ER\_SLAVE\_CHANNEL\_DOES\_NOT\_EXIST error code, 75  
 ER\_SLAVE\_CHANNEL\_IO\_THREAD\_MUST\_STOP error code, 70  
 ER\_SLAVE\_CHANNEL\_MUST\_STOP error code, 76  
 ER\_SLAVE\_CHANNEL\_NAME\_INVALID\_OR\_TOO\_LONG error code, 75  
 ER\_SLAVE\_CHANNEL\_NOT\_RUNNING error code, 76  
 ER\_SLAVE\_CHANNEL\_OPERATION\_NOT\_ALLOWED error code, 82  
 ER\_SLAVE\_CHANNEL\_SQL\_SKIP\_COUNTER error code, 77  
 ER\_SLAVE\_CHANNEL\_SQL\_THREAD\_MUST\_STOP error code, 77  
 ER\_SLAVE\_CHANNEL\_WAS\_NOT\_RUNNING error code, 76  
 ER\_SLAVE\_CHANNEL\_WAS\_RUNNING error code, 76  
 ER\_SLAVE\_CONFIGURATION error code, 59  
 ER\_SLAVE\_CONVERSION\_FAILED error code, 49  
 ER\_SLAVE\_CORRUPT\_EVENT error code, 43  
 ER\_SLAVE\_CREATE\_EVENT\_FAILURE error code, 528  
 ER\_SLAVE\_FATAL\_ERROR error code, 528  
 ER\_SLAVE\_HAS\_MORE\_GTIDS\_THAN\_MASTER error code, 68  
 ER\_SLAVE\_HEARTBEAT\_FAILURE error code, 529  
 ER\_SLAVE\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE error code, 44  
 ER\_SLAVE\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE\_MAX error code, 51  
 ER\_SLAVE\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE\_MIN error code, 51  
 ER\_SLAVE\_IGNORED\_SSL\_PARAMS error code, 23  
 ER\_SLAVE\_IGNORED\_TABLE error code, 20  
 ER\_SLAVE\_IGNORE\_SERVER\_IDS error code, 46  
 ER\_SLAVE\_INCIDENT error code, 529  
 ER\_SLAVE\_KILLED\_AFTER\_RECONNECT error code, 291  
 ER\_SLAVE\_MASTER\_COM\_FAILURE error code, 529  
 ER\_SLAVE\_MAX\_CHANNELS\_EXCEEDED error code, 76  
 ER\_SLAVE\_MI\_INIT\_REPOSITORY error code, 66  
 ER\_SLAVE\_MULTIPLE\_CHANNELS\_CMD error code, 75  
 ER\_SLAVE\_NEW\_CHANNEL\_WRONG\_REPOSITORY error code, 75  
 ER\_SLAVE\_NOT\_RUNNING error code, 17  
 ER\_SLAVE\_NOT\_STARTED\_ON\_SOME\_CHANNELS error code, 292  
 ER\_SLAVE\_POSSIBLY\_DIVERGED\_AFTER\_DDL error code, 110  
 ER\_SLAVE\_RECONNECT\_FAILED error code, 291  
 ER\_SLAVE\_RELAY\_LOG\_PURGE\_FAILED error code, 283  
 ER\_SLAVE\_RELAY\_LOG\_READ\_FAILURE error code, 529  
 ER\_SLAVE\_RELAY\_LOG\_TRUNCATE\_INFO error code, 283  
 ER\_SLAVE\_RELAY\_LOG\_WRITE\_FAILURE error code, 529  
 ER\_SLAVE\_RLI\_INIT\_REPOSITORY error code, 66  
 ER\_SLAVE\_SILENT\_RETRY\_TRANSACTION error code, 61  
 ER\_SLAVE\_SQL\_THREAD\_MUST\_STOP error code, 70  
 ER\_SLAVE\_SQL\_THREAD\_STOPPED\_AFTER\_GTIDS\_REACHED error code, 203  
 ER\_SLAVE\_SQL\_THREAD\_STOPPED\_BEFORE\_GTIDS\_ALREADY error code, 203  
 ER\_SLAVE\_SQL\_THREAD\_STOPPED\_BEFORE\_GTIDS\_REACHED error code, 203  
 ER\_SLAVE\_SQL\_THREAD\_STOPPED\_GAP\_TRX\_PROCESSED error code, 203  
 ER\_SLAVE\_SQL\_THREAD\_STOPPED\_UNTIL\_CONDITION\_BAD error code, 202  
 ER\_SLAVE\_SQL\_THREAD\_STOPPED\_UNTIL\_POSITION\_REACHED error code, 202  
 ER\_SLAVE\_THREAD error code, 17  
 ER\_SLAVE\_WORKER\_STOPPED\_PREVIOUS\_THD\_ERROR error code, 71  
 ER\_SLOW\_LOG\_MODE\_IGNORED\_WHEN\_NOT\_LOGGING\_TO\_FILE error code, 118  
 ER\_SOURCE error code, 16  
 ER\_SOURCE\_DELAY\_VALUE\_OUT\_OF\_RANGE error code, 53  
 ER\_SOURCE\_FATAL\_ERROR\_READING\_BINLOG error code, 20



---

ER\_SOURCE\_HAS\_PURGED\_REQUIRED\_GTIDS error code, 59  
 ER\_SOURCE\_NET\_READ error code, 16  
 ER\_SOURCE\_NET\_WRITE error code, 16  
 ER\_SPATIAL\_CANT\_HAVE\_NULL error code, 21  
 ER\_SPATIAL\_FUNCTIONAL\_INDEX error code, 114  
 ER\_SPATIAL\_MUST\_HAVE\_GEOM\_COL error code, 49  
 ER\_SPATIAL\_UNIQUE\_INDEX error code, 110  
 ER\_SPECIFIC\_ACCESS\_DENIED\_ERROR error code, 20  
 ER\_SPVAR\_NONINTEGER\_TYPE error code, 143  
 ER\_SP\_ALREADY\_EXISTS error code, 25  
 ER\_SP\_BADRETURN error code, 26  
 ER\_SP\_BADSELECT error code, 26  
 ER\_SP\_BADSTATEMENT error code, 26  
 ER\_SP\_BAD\_CURSOR\_QUERY error code, 26  
 ER\_SP\_BAD\_CURSOR\_SELECT error code, 26  
 ER\_SP\_BAD\_SQLSTATE error code, 31  
 ER\_SP\_BAD\_VAR\_SHADOW error code, 34  
 ER\_SP\_CANT\_ALTER error code, 27  
 ER\_SP\_CANT\_SET\_AUTOCOMMIT error code, 34  
 ER\_SP\_CASE\_NOT\_FOUND error code, 28  
 ER\_SP\_COND\_MISMATCH error code, 26  
 ER\_SP\_CURSOR\_AFTER\_HANDLER error code, 27  
 ER\_SP\_CURSOR\_ALREADY\_OPEN error code, 27  
 ER\_SP\_CURSOR\_MISMATCH error code, 27  
 ER\_SP\_CURSOR\_NOT\_OPEN error code, 27  
 ER\_SP\_DOES\_NOT\_EXIST error code, 25  
 ER\_SP\_DROP\_FAILED error code, 25  
 ER\_SP\_DUP\_COND error code, 27  
 ER\_SP\_DUP\_CURS error code, 27  
 ER\_SP\_DUP\_HANDLER error code, 32  
 ER\_SP\_DUP\_PARAM error code, 27  
 ER\_SP\_DUP\_VAR error code, 27  
 ER\_SP\_FETCH\_NO\_DATA error code, 27  
 ER\_SP\_LABEL\_MISMATCH error code, 26  
 ER\_SP\_LABEL\_REDEFINE error code, 26  
 ER\_SP\_LILABEL\_MISMATCH error code, 25  
 ER\_SP\_LOAD\_FAILED error code, 88  
 ER\_SP\_NORETURN error code, 26  
 ER\_SP\_NORETURNEND error code, 26  
 ER\_SP\_NOT\_VAR\_ARG error code, 32  
 ER\_SP\_NO\_AGGREGATE error code, 35  
 ER\_SP\_NO\_DROP\_SP error code, 29  
 ER\_SP\_NO\_RECURSION error code, 32  
 ER\_SP\_NO\_RECURSIVE\_CREATE error code, 25  
 ER\_SP\_NO\_RETSET error code, 32  
 ER\_SP\_RECURSION\_LIMIT error code, 35  
 ER\_SP\_STORE\_FAILED error code, 25  
 ER\_SP\_SUBSELECT\_NYL error code, 27  
 ER\_SP\_UNDECLARED\_VAR error code, 27  
 ER\_SP\_UNINIT\_VAR error code, 26  
 ER\_SP\_VARCOND\_AFTER\_CURSHNDLR error code, 27  
 ER\_SP\_WRONG\_NAME error code, 35  
 ER\_SP\_WRONG\_NO\_OF\_ARGS error code, 26  
 ER\_SP\_WRONG\_NO\_OF\_FETCH\_ARGS error code, 27  
 ER\_SQLTHREAD\_WITH\_SECURE\_REPLICA error code, 56  
 ER\_SQLTHREAD\_WITH\_SECURE\_SLAVE error code, 56  
 ER\_SQL\_AUTHOR\_DEFAULT\_ROLES\_FAIL error code, 187  
 ER\_SQL\_HA\_READ\_FAILED error code, 184  
 ER\_SQL\_MODE\_MERGED error code, 81  
 ER\_SQL\_MODE\_MERGED\_WITH\_STRICT\_MODE error code, 278  
 ER\_SQL\_REPLICA\_SKIP\_COUNTER\_USED\_WITH\_GTID\_MODE error code, 144  
 ER\_SQL\_SLAVE\_SKIP\_COUNTER\_NOT\_SETTABLE\_IN\_GTID\_MODE error code, 65  
 ER\_SQL\_SLAVE\_SKIP\_COUNTER\_USED\_WITH\_GTID\_MODE error code, 144  
 ER\_SQL\_USER\_TABLE ALTER WARNING error code, 187  
 ER\_SQL\_USER\_TABLE\_CREATE WARNING error code, 187  
 ER\_SRS\_ATTRIBUTE\_STRING\_TOO\_LONG error code, 109  
 ER\_SRS\_GEOGCS\_INVALID\_AXES error code, 111  
 ER\_SRS\_ID\_ALREADY\_EXISTS error code, 108  
 ER\_SRS\_INVALID\_ANGULAR\_UNIT error code, 111  
 ER\_SRS\_INVALID\_CHARACTER\_IN\_ATTRIBUTE error code, 109  
 ER\_SRS\_INVALID\_HEIGHT error code, 157  
 ER\_SRS\_INVALID\_INVERSE\_FLATTENING error code, 111  
 ER\_SRS\_INVALID\_LATITUDE\_OF\_ORIGIN error code, 155  
 ER\_SRS\_INVALID\_LATITUDE\_POLAR\_STERE\_VAR\_A error code, 158  
 ER\_SRS\_INVALID\_LONGITUDE\_OF\_ORIGIN error code, 155  
 ER\_SRS\_INVALID\_PRIME\_MERIDIAN error code, 111  
 ER\_SRS\_INVALID\_SCALING error code, 157  
 ER\_SRS\_INVALID\_SEMI\_MAJOR\_AXIS error code, 111  
 ER\_SRS\_INVALID\_ZONE\_WIDTH error code, 157  
 ER\_SRS\_MISSING\_MANDATORY\_ATTRIBUTE error code, 108  
 ER\_SRS\_MULTIPLE\_ATTRIBUTE\_DEFINITIONS error code, 108  
 ER\_SRS\_NAME\_CANT\_BE\_EMPTY\_OR\_WHITESPACE error code, 108  
 ER\_SRS\_NOT\_CARTESIAN error code, 89  
 ER\_SRS\_NOT\_CARTESIAN\_UNDEFINED error code, 89  
 ER\_SRS\_NOT\_FOUND error code, 91

---

---

ER\_SRS\_NOT\_GEOGRAPHIC error code, 110  
 ER\_SRS\_ORGANIZATION\_CANT\_BE\_EMPTY\_OR\_WHITE\_SPACE error code, 108  
 ER\_SRS\_PARSE\_ERROR error code, 88  
 ER\_SRS\_PROJ\_PARAMETER\_MISSING error code, 88  
 ER\_SRS\_UNUSED\_PROJ\_PARAMETER\_PRESENT error code, 155  
 ER\_SR\_BOGUS\_VALUE error code, 184  
 ER\_SR\_INVALID\_CONTEXT error code, 184  
 ER\_SSL\_FIPS\_MODE\_ERROR error code, 321  
 ER\_SSL\_LIBRARY\_ERROR error code, 169  
 ER\_SSL\_MEMORY\_INSTRUMENTATION\_INIT\_FAILED error code, 543  
 ER\_SSL\_SERVER\_CERT\_VERIFY\_FAILED error code, 562  
 ER\_SSL\_TRYING\_DATADIR\_DEFAULTS error code, 181  
 ER\_STACKSIZE\_UNEXPECTED error code, 180  
 ER\_STACK\_BACKTRACE error code, 627  
 ER\_STACK\_OVERRUN error code, 11  
 ER\_STACK\_OVERRUN\_NEED\_MORE error code, 33  
 ER\_STARTING\_AS error code, 174  
 ER\_STARTING\_INIT error code, 535  
 ER\_STARTING\_REPLICA\_MONITOR\_IO\_THREAD error code, 143  
 ER\_STARTUP error code, 31  
 ER\_STATEMENT\_NOT\_ALLOWED\_AFTER\_START\_TRANSACTION error code, 139  
 ER\_STD\_BAD\_ALLOC\_ERROR error code, 72  
 ER\_STD\_DOMAIN\_ERROR error code, 72  
 ER\_STD\_INVALID\_ARGUMENT error code, 73  
 ER\_STD\_LENGTH\_ERROR error code, 73  
 ER\_STD\_LOGIC\_ERROR error code, 73  
 ER\_STD\_OUT\_OF\_RANGE\_ERROR error code, 73  
 ER\_STD\_OVERFLOW\_ERROR error code, 73  
 ER\_STD\_RANGE\_ERROR error code, 73  
 ER\_STD\_REGEX\_ERROR error code, 124  
 ER\_STD\_RUNTIME\_ERROR error code, 73  
 ER\_STD\_UNDERFLOW\_ERROR error code, 73  
 ER\_STD\_UNKNOWN\_EXCEPTION error code, 73  
 ER\_STMT\_CACHE\_FULL error code, 51  
 ER\_STMT\_HAS\_NO\_OPEN\_CURSOR error code, 32  
 ER\_STMT\_NOT\_ALLOWED\_IN\_SF\_OR\_TRG error code, 27  
 ER\_STOP\_REPLICA\_IO\_THREAD\_DISK\_SPACE error code, 321  
 ER\_STOP\_REPLICA\_IO\_THREAD\_TIMEOUT error code, 67  
 ER\_STOP\_REPLICA\_MONITOR\_IO\_THREAD\_TIMEOUT error code, 143  
 ER\_STOP\_REPLICA\_SQL\_THREAD\_TIMEOUT error code, 66  
 ER\_STOP\_SLAVE\_IO\_THREAD\_DISK\_SPACE error code, 321  
 ER\_STOP\_SLAVE\_IO\_THREAD\_TIMEOUT error code, 66  
 ER\_STOP\_SLAVE\_SQL\_THREAD\_TIMEOUT error code, 66  
 ER\_STORAGE\_ENGINE\_NOT\_LOADED error code, 68  
 ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_BINLOG\_DIRECT error code, 49  
 ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_BINLOG\_FORMAT error code, 41  
 ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_SQL\_LOG\_BIN error code, 50  
 ER\_SUBPARTITION\_ERROR error code, 37  
 ER\_SUBPARTITION\_NAME error code, 45  
 ER\_SUBQUERY\_NO\_1\_ROW error code, 21  
 ER\_SUBQUERY\_TRANSFORM\_REJECTED error code, 138  
 ER\_SWITCH\_TMP\_ENGINE error code, 94  
 ER\_SYNTAX\_ERROR error code, 14  
 ER\_SYSTEMD\_NOTIFY\_CONNECT\_FAILED error code, 387  
 ER\_SYSTEMD\_NOTIFY\_DEBUG error code, 625  
 ER\_SYSTEMD\_NOTIFY\_PATH\_TOO\_LONG error code, 387  
 ER\_SYSTEMD\_NOTIFY\_WRITE\_FAILED error code, 387  
 ER\_SYSTEM\_SCHEMA\_NOT\_FOUND error code, 164  
 ER\_SYSTEM\_TABLES\_NOT\_SUPPORTED\_BY\_STORAGE\_ENGINE error code, 279  
 ER\_SYSTEM\_TABLE\_NOT\_TRANSACTIONAL error code, 255  
 ER\_SYSTEM\_VIEW\_INIT\_FAILED error code, 281  
 ER\_SYSVAR\_CHANGE\_DURING\_QUERY error code, 131  
 ER\_SYS\_VAR\_COMPONENT\_FAILED\_TO\_MAKE\_VARIABLE\_PER error code, 321  
 ER\_SYS\_VAR\_COMPONENT\_FAILED\_TO\_PARSE\_VARIABLE\_OP error code, 320  
 ER\_SYS\_VAR\_COMPONENT\_OOM error code, 320  
 ER\_SYS\_VAR\_COMPONENT\_UNKNOWN\_VARIABLE\_TYPE error code, 320  
 ER\_SYS\_VAR\_COMPONENT\_VARIABLE\_SET\_READ\_ONLY error code, 320  
 ER\_SYS\_VAR\_DEREGISTRATION error code, 637  
 ER\_SYS\_VAR\_NOT\_FOUND error code, 537  
 ER\_SYS\_VAR\_REGISTRATION error code, 637  
 ER\_TABLEACCESS\_DENIED\_ERROR error code, 13  
 ER\_TABLENAME\_NOT\_ALLOWED\_HERE error code, 21  
 ER\_TABLESPACE\_AUTO\_EXTEND\_ERROR error code, 39  
 ER\_TABLESPACE\_CANNOT\_BE\_DECRYPTED error code, 122  
 ER\_TABLESPACE\_CANNOT\_BE\_ENCRYPTED error code, 122

---

ER\_TABLESPACE\_CANNOT\_ENCRYPT error code, 85  
 ER\_TABLESPACE\_DISCARDED error code, 61  
 ER\_TABLESPACE\_DUP\_FILENAME error code, 97  
 ER\_TABLESPACE\_ENGINE\_MISMATCH error code, 101  
 ER\_TABLESPACE\_EXISTS error code, 61  
 ER\_TABLESPACE\_IS\_NOT\_EMPTY error code, 80  
 ER\_TABLESPACE\_MISSING error code, 61  
 ER\_TABLESPACE\_MISSING\_WITH\_NAME error code, 88  
 ER\_TABLESPACE\_TYPE\_UNKNOWN error code, 122  
 ER\_TABLES\_DIFFERENT\_METADATA error code, 54  
 ER\_TABLE\_CANT\_HANDLE\_AUTO\_INCREMENT error code, 14  
 ER\_TABLE\_CANT\_HANDLE\_BLOB error code, 14  
 ER\_TABLE\_CANT\_HANDLE\_FT error code, 19  
 ER\_TABLE\_CANT\_HANDLE\_SPKEYS error code, 35  
 ER\_TABLE\_CHECK\_INTACT error code, 182  
 ER\_TABLE\_CORRUPT error code, 67  
 ER\_TABLE\_CREATED\_WITH\_DIFFERENT\_VERSION error code, 199  
 ER\_TABLE\_DEF\_CHANGED error code, 32  
 ER\_TABLE\_EXISTS\_ERROR error code, 6  
 ER\_TABLE\_HAS\_NO\_FT error code, 57  
 ER\_TABLE\_INCOMPATIBLE\_DECIMAL\_FIELD error code, 198  
 ER\_TABLE\_INCOMPATIBLE\_YEAR\_FIELD error code, 199  
 ER\_TABLE\_IN\_FK\_CHECK error code, 53  
 ER\_TABLE\_IN\_SHARED\_TABLESPACE error code, 158  
 ER\_TABLE\_IN\_SYSTEM\_TABLESPACE error code, 61  
 ER\_TABLE\_MUST\_HAVE\_A\_VISIBLE\_COLUMN error code, 146  
 ER\_TABLE\_MUST\_HAVE\_COLUMNS error code, 11  
 ER\_TABLE\_NAME error code, 45  
 ER\_TABLE\_NAME\_CAUSES\_TOO\_LONG\_PATH error code, 131  
 ER\_TABLE\_NAME\_IN\_UPPER\_CASE\_NOT\_ALLOWED error code, 575  
 ER\_TABLE\_NAME\_IN\_UPPER\_CASE\_NOT\_ALLOWED\_FOR\_FK error code, 575  
 ER\_TABLE\_NEEDS\_DUMP\_UPGRADE error code, 298  
 ER\_TABLE\_NEEDS\_REBUILD error code, 51  
 ER\_TABLE\_NEEDS\_UPGRADE error code, 35  
 ER\_TABLE\_NOT\_EMPTY error code, 158  
 ER\_TABLE\_NOT\_LOCKED error code, 10  
 ER\_TABLE\_NOT\_LOCKED\_FOR\_WRITE error code, 10  
 ER\_TABLE\_NO\_PRIMARY\_KEY error code, 158  
 ER\_TABLE\_REFERENCED error code, 86  
 ER\_TABLE\_SCHEMA\_MISMATCH error code, 61  
 ER\_TABLE\_UPGRADE\_REQUIRED error code, 279  
 ER\_TABLE\_VALUE\_CONSTRUCTOR\_CANNOT\_HAVE\_DEFAULT error code, 135  
 ER\_TABLE\_VALUE\_CONSTRUCTOR\_MUST\_HAVE\_COLUMNS error code, 135  
 ER\_TABLE\_WITHOUT\_PK error code, 113  
 ER\_TABLE\_WRONG\_KEY\_DEFINITION error code, 199  
 ER\_TARGET\_TABLESPACE\_UNENCRYPTED error code, 122  
 ER\_TARGET\_TS\_UNENCRYPTED error code, 537  
 ER\_TC\_BAD\_MAGIC\_IN\_TC\_LOG error code, 222  
 ER\_TC\_CANT\_AUTO\_RECOVER\_WITH\_TC\_HEURISTIC\_RECOVER error code, 222  
 ER\_TC\_HEURISTIC\_RECOVERY\_FAILED error code, 223  
 ER\_TC\_HEURISTIC\_RECOVERY\_MODE error code, 223  
 ER\_TC\_NEED\_N\_SE\_SUPPORTING\_2PC\_FOR\_RECOVERY error code, 222  
 ER\_TC\_RECOVERING\_AFTER\_CRASH\_USING error code, 222  
 ER\_TC\_RECOVERY\_FAILED\_THESE\_ARE\_YOUR\_OPTIONS error code, 223  
 ER\_TC\_RESTART\_WITHOUT\_TC\_HEURISTIC\_RECOVER error code, 223  
 ER\_TEMPORARY\_NAME error code, 45  
 ER\_TEMP\_FILE\_WRITE\_FAILURE error code, 67  
 ER\_TEMP\_TABLE\_PREVENTS\_SWITCH\_GLOBAL\_BINLOG\_FILE error code, 112  
 ER\_TEMP\_TABLE\_PREVENTS\_SWITCH\_OUT\_OF\_RBR error code, 41  
 ER\_TEMP\_TABLE\_PREVENTS\_SWITCH\_SESSION\_BINLOG\_FILE error code, 112  
 ER\_TEXTFILE\_NOT\_READABLE error code, 9  
 ER\_TF\_FORBIDDEN\_JOIN\_TYPE error code, 104  
 ER\_TF\_MUST\_HAVE\_ALIAS error code, 103  
 ER\_THE\_USER\_ABIDES error code, 177  
 ER\_THREAD\_HANDLING\_OOM error code, 172  
 ER\_THREAD\_POOL\_ALGORITHM\_INVALID error code, 300  
 ER\_THREAD\_POOL\_BUFFER\_TOO\_SMALL error code, 302  
 ER\_THREAD\_POOL\_CANNOT\_REGISTER\_DYNAMIC\_PRIVILEGE error code, 625  
 ER\_THREAD\_POOL\_CANNOT\_SET\_THREAD\_SPECIFIC\_DATA error code, 301  
 ER\_THREAD\_POOL\_CONNECTION\_REPORT error code, 639  
 ER\_THREAD\_POOL\_CON\_HANDLER\_INIT\_FAILED error code, 301  
 ER\_THREAD\_POOL\_DEDICATED\_LISTENERS\_INVALID error code, 615  
 ER\_THREAD\_POOL\_FAILED\_PROCESS\_CONNECT\_EVENT error code, 301  
 ER\_THREAD\_POOL\_FAILED\_TO\_CREATE\_CONNECT\_HANDLER error code, 301

---

---

ER\_THREAD\_POOL\_FAILED\_TO\_CREATE\_POOL error code, 302  
 ER\_THREAD\_POOL\_FAILED\_TO\_CREATE\_THD\_AND\_AU error code, 301  
 ER\_THREAD\_POOL\_IDLE\_CONNECTION\_CLOSED error code, 632  
 ER\_THREAD\_POOL\_INIT\_FAILED error code, 301  
 ER\_THREAD\_POOL\_INVALID\_PRIO\_KICKUP\_TIMER error code, 301  
 ER\_THREAD\_POOL\_INVALID\_STALL\_LIMIT error code, 300  
 ER\_THREAD\_POOL\_LOW\_LEVEL\_REARM\_FAILED error code, 302  
 ER\_THREAD\_POOL\_MAX\_UNUSED\_THREADS\_INVALID error code, 301  
 ER\_THREAD\_POOL\_NOT\_SUPPORTED\_ON\_PLATFORM error code, 300  
 ER\_THREAD\_POOL\_PFS\_TABLES\_ADD\_FAILED error code, 547  
 ER\_THREAD\_POOL\_PFS\_TABLES\_INIT\_FAILED error code, 547  
 ER\_THREAD\_POOL\_PLUGIN\_STARTED error code, 615  
 ER\_THREAD\_POOL\_QUERY\_THREADS\_PER\_GROUP\_INVALID error code, 627  
 ER\_THREAD\_POOL\_QUERY\_THRS\_PER\_GRP\_EXCEEDS error code, 628  
 ER\_THREAD\_POOL\_RATE\_LIMITED\_ERROR\_MSGS error code, 302  
 ER\_THREAD\_POOL\_SIZE\_TOO\_HIGH error code, 300  
 ER\_THREAD\_POOL\_SIZE\_TOO\_LOW error code, 300  
 ER\_THREAD\_POOL\_SYSVAR\_CHANGE error code, 627  
 ER\_THREAD\_PRIORITY\_IGNORED error code, 276  
 ER\_TLS\_CONFIGURATION\_REUSED error code, 584  
 ER\_TLS\_CONFIGURED\_FOR\_CHANNEL error code, 584  
 ER\_TMPDIR\_PATH\_TOO\_LONG error code, 590  
 ER\_TMP\_SESSION\_FOR\_VAR error code, 625  
 ER\_TOO\_BIG\_DISPLAYWIDTH error code, 33  
 ER\_TOO\_BIG\_ENUM error code, 87  
 ER\_TOO\_BIG\_FIELDLENGTH error code, 8  
 ER\_TOO\_BIG\_FOR\_UNCOMPRESS error code, 22  
 ER\_TOO\_BIG\_PRECISION error code, 33  
 ER\_TOO\_BIG\_ROWSIZE error code, 11  
 ER\_TOO\_BIG\_SCALE error code, 33  
 ER\_TOO\_BIG\_SELECT error code, 10  
 ER\_TOO\_BIG\_SET error code, 10  
 ER\_TOO\_HIGH\_LEVEL\_OF\_NESTING\_FOR\_SELECT error code, 36  
 ER\_TOO\_LONG\_BODY error code, 33  
 ER\_TOO\_LONG\_FIELD\_COMMENT error code, 45  
 ER\_TOO\_LONG\_IDENT error code, 7  
 ER\_TOO\_LONG\_INDEX\_COMMENT error code, 50  
 ER\_TOO\_LONG\_KEY error code, 8  
 ER\_TOO\_LONG\_ROUTINE\_COMMENT error code, 88  
 ER\_TOO\_LONG\_SET\_ENUM\_VALUE error code, 88  
 ER\_TOO\_LONG\_STRING error code, 14  
 ER\_TOO\_LONG\_TABLESPACE\_COMMENT error code, 97  
 ER\_TOO\_LONG\_TABLE\_COMMENT error code, 45  
 ER\_TOO\_LONG\_TABLE\_PARTITION\_COMMENT error code, 59  
 ER\_TOO\_MANY\_CONCURRENT\_CLONES error code, 100  
 ER\_TOO\_MANY\_CONCURRENT\_TRXS error code, 45  
 ER\_TOO\_MANY\_FIELDS error code, 11  
 ER\_TOO\_MANY\_KEYS error code, 8  
 ER\_TOO\_MANY\_KEY\_PARTS error code, 8  
 ER\_TOO\_MANY\_PARTITIONS\_ERROR error code, 37  
 ER\_TOO\_MANY\_PARTITION\_FUNC\_FIELDS\_ERROR error code, 47  
 ER\_TOO\_MANY\_ROWS error code, 15  
 ER\_TOO\_MANY\_STORAGE\_ENGINES error code, 187  
 ER\_TOO\_MANY\_TABLES error code, 11  
 ER\_TOO\_MANY\_USER\_CONNECTIONS error code, 18  
 ER\_TOO\_MANY\_VALUES\_ERROR error code, 47  
 ER\_TOO\_MANY\_WINDOWS error code, 153  
 ER\_TP\_QUERY\_THRS\_PER\_GRP\_EXCEEDS\_TXN\_THR\_LIMIT error code, 157  
 ER\_TRACK\_VARIABLES\_BOGUS error code, 177  
 ER\_TRANSACTION\_ROLLBACK\_DURING\_COMMIT error code, 78  
 ER\_TRANSFORM\_SOURCE\_SRS\_MISSING\_TOWGS84 error code, 112  
 ER\_TRANSFORM\_SOURCE\_SRS\_NOT\_SUPPORTED error code, 112  
 ER\_TRANSFORM\_TARGET\_SRS\_MISSING\_TOWGS84 error code, 112  
 ER\_TRANSFORM\_TARGET\_SRS\_NOT\_SUPPORTED error code, 112  
 ER\_TRANSPORTS\_WHAT\_TRANSPORTS error code, 175  
 ER\_TRANS\_CACHE\_FULL error code, 17  
 ER\_TREE\_CORRUPT\_2\_CONSECUTIVE\_REDS error code, 253  
 ER\_TREE\_CORRUPT\_INCORRECT\_BLACK\_COUNT error code, 253  
 ER\_TREE\_CORRUPT\_PARENT\_SHOULD\_POINT\_AT\_PARENT error code, 252  
 ER\_TREE\_CORRUPT\_RIGHT\_IS\_LEFT error code, 253  
 ER\_TREE\_CORRUPT\_ROOT\_SHOULD\_BE\_BLACK error code, 253  
 ER\_TRG\_ALREADY\_EXISTS error code, 29  
 ER\_TRG\_CANT\_CHANGE\_ROW error code, 29  
 ER\_TRG\_CANT\_OPEN\_TABLE error code, 43  
 ER\_TRG\_CANT\_PARSE error code, 183  
 ER\_TRG\_CORRUPTED\_FILE error code, 43

---

ER\_TRG\_CREATION\_CTX\_NOT\_SET error code, 278  
 ER\_TRG\_DOES\_NOT\_EXIST error code, 29  
 ER\_TRG\_INVALID\_CREATION\_CTX error code, 43  
 ER\_TRG\_IN\_WRONG\_SCHEMA error code, 33  
 ER\_TRG\_NO\_CLIENT\_CHARSET error code, 169  
 ER\_TRG\_NO\_CREATION\_CTX error code, 43  
 ER\_TRG\_NO\_DEFINER error code, 35  
 ER\_TRG\_NO\_SUCH\_ROW\_IN\_TRG error code, 29  
 ER\_TRG\_ON\_VIEW\_OR\_TEMP\_TABLE error code, 29  
 ER\_TRG\_WITHOUT\_DEFINER error code, 169  
 ER\_TRG\_WRONG\_ORDER error code, 553  
 ER\_TRHEAD\_POOL\_LOW\_LEVEL\_INIT\_FAILED error code, 302  
 ER\_TRIGGER\_INVALID\_VALUE error code, 162  
 ER\_TRUNCATED\_WRONG\_VALUE error code, 24  
 ER\_TRUNCATED\_WRONG\_VALUE\_FOR\_FIELD error code, 29  
 ER\_TRUNCATE\_ILLEGAL\_FK error code, 50  
 ER\_TRX\_GTID\_COLLECT\_REJECT error code, 186  
 ER\_TRX\_WRITE\_SET\_OOM error code, 187  
 ER\_TURNING\_LOGGING\_OFF\_FOR\_THE\_DURATION error code, 271  
 ER\_TURNING\_ON\_PARTIAL\_REVOKES error code, 557  
 ER\_TX\_EXTRACTION\_ALGORITHM\_FOR\_BINLOG\_TX\_DEPENDENCY\_TRACKING error code, 282  
 ER\_TZ\_CANT\_BUILD\_MKTIME\_MAP error code, 202  
 ER\_TZ\_CANT\_FIND\_DESCRIPTION\_FOR\_TIME\_ZONE error code, 201  
 ER\_TZ\_CANT\_FIND\_DESCRIPTION\_FOR\_TIME\_ZONE\_1 error code, 201  
 ER\_TZ\_CANT\_OPEN\_AND\_LOCK\_TIME\_ZONE\_TABLE error code, 200  
 ER\_TZ\_ERROR\_LOADING\_LEAP\_SECOND\_TABLE error code, 200  
 ER\_TZ\_NO\_TRANSITION\_TYPES\_IN\_TIME\_ZONE error code, 202  
 ER\_TZ\_OOM\_INITIALIZING\_TIME\_ZONES error code, 200  
 ER\_TZ\_OOM\_LOADING\_LEAP\_SECOND\_TABLE error code, 200  
 ER\_TZ\_OOM\_LOADING\_TIME\_ZONE\_DESCRIPTION error code, 202  
 ER\_TZ\_OOM\_WHILE\_LOADING\_TIME\_ZONE error code, 202  
 ER\_TZ\_OOM\_WHILE\_SETTING\_TIME\_ZONE error code, 202  
 ER\_TZ\_TOO\_MANY\_LEAPS\_IN\_LEAP\_SECOND\_TABLE error code, 200  
 ER\_TZ\_TRANSITION\_TABLE\_BAD\_TRANSITION\_TYPE error code, 201  
 ER\_TZ\_TRANSITION\_TABLE\_LOAD\_ERROR error code, 201  
 ER\_TZ\_TRANSITION\_TABLE\_TOO\_MANY\_TRANSITIONS error code, 201  
 ER\_TZ\_TRANSITION\_TYPE\_TABLE\_ABBREVIATIONS\_EXCEEDED error code, 201  
 ER\_TZ\_TRANSITION\_TYPE\_TABLE\_LOAD\_ERROR error code, 201  
 ER\_TZ\_TRANSITION\_TYPE\_TABLE\_TYPE\_TOO\_LARGE error code, 201  
 ER\_TZ\_UNKNOWN\_OR\_ILLEGAL\_DEFAULT\_TIME\_ZONE error code, 200  
 ER\_UDF\_ALREADY\_EXISTS error code, 536  
 ER\_UDF\_CANT\_ALLOC\_FOR\_FUNCTION error code, 185  
 ER\_UDF\_CANT\_ALLOC\_FOR\_STRUCTURES error code, 185  
 ER\_UDF\_CANT\_OPEN\_FUNCTION\_TABLE error code, 185  
 ER\_UDF\_DEREGISTRATION error code, 637  
 ER\_UDF\_DROP\_DYNAMICALLY\_REGISTERED error code, 99  
 ER\_UDF\_ERROR error code, 86  
 ER\_UDF\_EXEC\_FAILURE error code, 637  
 ER\_UDF\_EXEC\_FAILURE\_REASON error code, 637  
 ER\_UDF\_EXISTS error code, 12  
 ER\_UDF\_INVALID\_ARGUMENT\_IN\_FUNCTION\_TABLE error code, 185  
 ER\_UDF\_NO\_PATHS error code, 12  
 ER\_UDF\_REGISTER\_ERROR error code, 590  
 ER\_UDF\_REGISTER\_SERVICE\_ERROR error code, 590  
 ER\_UDF\_REGISTRATION error code, 637  
 ER\_UDF\_UNREGISTER\_ERROR error code, 590  
 ER\_UNKNOWN\_AUTH\_ID\_OR\_ACCESS\_DENIED\_FOR\_GRANT error code, 123  
 ER\_UNABLE\_TO\_BUILD\_HISTOGRAM error code, 99  
 ER\_UNABLE\_TO\_COLLECT\_LOG\_STATUS error code, 109  
 ER\_UNABLE\_TO\_DROP\_COLUMN\_STATISTICS error code, 99  
 ER\_UNABLE\_TO\_RESOLVE\_HOSTNAME error code, 168  
 ER\_UNABLE\_TO\_RESOLVE\_IP error code, 168  
 ER\_UNABLE\_TO\_SET\_OPTION error code, 110  
 ER\_UNABLE\_TO\_STORE\_COLUMN\_STATISTICS error code, 99  
 ER\_UNABLE\_TO\_STORE\_STATISTICS error code, 91  
 ER\_UNABLE\_TO\_UPDATE\_COLUMN\_STATISTICS error code, 99  
 ER\_UNDISCLOSED\_PARSE\_ERROR\_IN\_DIGEST\_FN error code, 105  
 ER\_UNDO\_RECORD\_TOO\_BIG error code, 52  
 ER\_UNEXPECTED\_GEOMETRY\_TYPE error code, 88  
 ER\_UNIQUE\_KEY\_NEED\_ALL\_FIELDS\_IN\_PF error code, 38

---

---

ER\_UNIT\_NOT\_FOUND error code, 130  
 ER\_UNKNOWN\_ALTER\_ALGORITHM error code, 60  
 ER\_UNKNOWN\_ALTER\_LOCK error code, 60  
 ER\_UNKNOWN\_AUTHID error code, 89  
 ER\_UNKNOWN\_AUTH\_ID\_IN\_MANDATORY\_ROLE error code, 284  
 ER\_UNKNOWN\_CHARACTER\_SET error code, 11  
 ER\_UNKNOWN\_COLLATION error code, 23  
 ER\_UNKNOWN\_COM\_ERROR error code, 6  
 ER\_UNKNOWN\_ERROR error code, 10  
 ER\_UNKNOWN\_ERROR\_DETECTED\_IN\_SE error code, 290  
 ER\_UNKNOWN\_ERROR\_NUMBER error code, 185  
 ER\_UNKNOWN\_EXPLAIN\_FORMAT error code, 59  
 ER\_UNKNOWN\_KEY\_CACHE error code, 24  
 ER\_UNKNOWN\_LOCALE error code, 46  
 ER\_UNKNOWN\_NETWORK\_NAMESPACE error code, 561  
 ER\_UNKNOWN\_PARTITION error code, 54  
 ER\_UNKNOWN\_PROCEDURE error code, 10  
 ER\_UNKNOWN\_STMT\_HANDLER error code, 21  
 ER\_UNKNOWN\_STORAGE\_ENGINE error code, 24  
 ER\_UNKNOWN\_SYSTEM\_VARIABLE error code, 16  
 ER\_UNKNOWN\_TABLE error code, 11  
 ER\_UNKNOWN\_TABLESPACE\_TYPE error code, 543  
 ER\_UNKNOWN\_TABLE\_IN\_UPGRADE error code, 568  
 ER\_UNKNOWN\_TARGET\_BINLOG error code, 30  
 ER\_UNKNOWN\_TIME\_ZONE error code, 25  
 ER\_UNKNOWN\_UNSUPPORTED\_STORAGE\_ENGINE error code, 170  
 ER\_UNKNOWN\_VARIABLE\_IN\_PERSISTED\_CONFIG\_FILE error code, 537  
 ER\_UNRESOLVED\_HINT\_NAME error code, 80  
 ER\_UNRESOLVED\_TABLE\_LOCK error code, 93  
 ER\_UNSUPPORTED\_LOG\_ENGINE error code, 42  
 ER\_UNSUPPORTED\_ACTION\_ON\_DEFAULT\_VAL\_GENERATED error code, 115  
 ER\_UNSUPPORTED\_ACTION\_ON\_GENERATED\_COLUMN error code, 79  
 ER\_UNSUPPORTED\_ALTER\_ENCRYPTION\_INPLACE error code, 85  
 ER\_UNSUPPORTED\_ALTER\_INPLACE\_ON\_VIRTUAL\_COLUMNS error code, 79  
 ER\_UNSUPPORTED\_ALTER\_ONLINE\_ON\_VIRTUAL\_COLUMNS error code, 85  
 ER\_UNSUPPORTED\_DATE error code, 174  
 ER\_UNSUPPORTED\_ENGINE error code, 53  
 ER\_UNSUPPORTED\_EXTENSION error code, 11  
 ER\_UNSUPPORTED\_INDEX\_ALGORITHM error code, 87  
 ER\_UNSUPPORTED\_PS error code, 25  
 ER\_UNSUPPORTED\_SQL\_MODE error code, 130  
 ER\_UNSUPPORTED\_USE\_OF\_GRANT\_AS error code, 123  
 ER\_UNSUPPORTED\_COMPRESSED\_TEMPORARY\_TABLE error code, 87  
 ER\_UNTIL\_COND\_IGNORED error code, 24  
 ER\_UPDATE\_GTID\_PURGED\_WITH\_GR error code, 131  
 ER\_UPDATE\_INFO error code, 12  
 ER\_UPDATE\_LOG\_DEPRECATED\_IGNORED error code, 26  
 ER\_UPDATE\_LOG\_DEPRECATED\_TRANSLATED error code, 26  
 ER\_UPDATE\_TABLE\_USED error code, 9  
 ER\_UPDATE\_WITHOUT\_KEY\_IN\_SAFE\_MODE error code, 15  
 ER\_UPDATING\_DD\_TABLE error code, 88  
 ER\_UPGRADE\_NONEXISTENT\_SCHEMA error code, 591  
 ER\_UPGRADE\_PARSE\_ERROR error code, 542  
 ER\_UPGRADE\_WITH\_PARTITIONED\_TABLES\_REJECTED error code, 569  
 ER\_USAGE\_DEPRECATION\_COUNTER error code, 641  
 ER\_USERNAME error code, 35  
 ER\_USERNAME\_TRUNCATED error code, 584  
 ER\_USER\_ACCESS\_DENIED\_FOR\_USER\_ACCOUNT\_BLOCKED error code, 136  
 ER\_USER\_ALREADY\_EXISTS error code, 83  
 ER\_USER\_COLUMN\_OLD\_LENGTH error code, 85  
 ER\_USER\_DOES\_NOT\_EXIST error code, 83  
 ER\_USER\_LIMIT\_REACHED error code, 19  
 ER\_USER\_LOCK\_DEADLOCK error code, 74  
 ER\_USER\_LOCK\_OVERLONG\_NAME error code, 162  
 ER\_USER\_LOCK\_WRONG\_NAME error code, 73  
 ER\_USER\_NOT\_IN\_EXTRA\_USERS\_BINLOG\_POSSIBLY\_INCOMPLETE error code, 197  
 ER\_USER\_REFERENCED\_AS\_DEFINER error code, 142  
 ER\_USER\_REGISTRATION\_FAILED error code, 150  
 ER\_USER\_REQUIRES\_ROOT error code, 175  
 ER\_USER\_WHAT\_USER error code, 175  
 ER\_USING\_ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS error code, 144  
 ER\_UUID\_INVALID error code, 170  
 ER\_UUID\_IS error code, 170  
 ER\_UUID\_SALT error code, 170  
 ER\_UUID\_SCRUB error code, 170  
 ER\_VALGRIND\_COUNT\_LEAKS error code, 185  
 ER\_VALGRIND\_DO\_QUICK\_LEAK\_CHECK error code, 185  
 ER\_VALIDATE\_PASSWORD\_INSUFFICIENT\_CHANGED\_CHARACTERS error code, 162  
 ER\_VALIDATE\_PWD\_CONVERT\_TO\_BUFFER\_FAILED error code, 389  
 ER\_VALIDATE\_PWD\_COULD\_BE\_NULL error code, 388

---

ER\_VALIDATE\_PWD\_DICT\_FILE\_NOT\_LOADED error code, 317  
 ER\_VALIDATE\_PWD\_DICT\_FILE\_NOT\_SPECIFIED error code, 317  
 ER\_VALIDATE\_PWD\_DICT\_FILE\_OPEN\_FAILED error code, 388  
 ER\_VALIDATE\_PWD\_DICT\_FILE\_TOO\_BIG error code, 317  
 ER\_VALIDATE\_PWD\_FAILED\_TO\_GET\_FLD\_FROM\_SECURITY\_DICT error code, 317  
 ER\_VALIDATE\_PWD\_FAILED\_TO\_GET\_SECURITY\_CTX error code, 318  
 ER\_VALIDATE\_PWD\_FAILED\_TO\_READ\_DICT\_FILE error code, 317  
 ER\_VALIDATE\_PWD\_LENGTH\_CHANGED error code, 318  
 ER\_VALIDATE\_PWD\_STATUS\_VAR\_REGISTRATION\_FAILED error code, 388  
 ER\_VALIDATE\_PWD\_STATUS\_VAR\_UNREGISTRATION\_FAILED error code, 388  
 ER\_VALIDATE\_PWD\_STRING\_CONV\_TO\_BUFFER\_FAILED error code, 388  
 ER\_VALIDATE\_PWD\_STRING\_CONV\_TO\_LOWERCASE\_FAILED error code, 388  
 ER\_VALIDATE\_PWD\_STRING\_HANDLER\_MEM\_ALLOCATION\_FAILED error code, 389  
 ER\_VALIDATE\_PWD\_STRONG\_POLICY\_DICT\_FILE\_UNSPECIFIED error code, 389  
 ER\_VALIDATE\_PWD\_VARIABLE\_REGISTRATION\_FAILED error code, 389  
 ER\_VALIDATE\_PWD\_VARIABLE\_UNREGISTRATION\_FAILED error code, 389  
 ER\_VALUES\_IS\_NOT\_INT\_TYPE\_ERROR error code, 50  
 ER\_VALUE\_OUT\_OF\_RANGE error code, 152  
 ER\_VARIABLE\_IS\_NOT\_STRUCT error code, 23  
 ER\_VARIABLE\_IS\_READONLY error code, 44  
 ER\_VARIABLE\_NOT\_PERSISTED error code, 91  
 ER\_VARIABLE\_NOT\_SETTABLE\_IN\_SF\_OR\_TRIGGER error code, 57  
 ER\_VARIABLE\_NOT\_SETTABLE\_IN\_SP error code, 63  
 ER\_VARIABLE\_NOT\_SETTABLE\_IN\_TRANSACTION error code, 57  
 ER\_VAR\_CANT\_BE\_READ error code, 20  
 ER\_VAR\_DOES\_NOT\_EXIST error code, 98  
 ER\_VERBOSE\_HINT error code, 178  
 ER\_VERBOSE\_REQUIRES\_HELP error code, 171  
 ER\_VIEW\_CHECKSUM error code, 30  
 ER\_VIEW\_CHECK\_FAILED error code, 29  
 ER\_VIEW\_CREATION\_CTX\_NOT\_SET error code, 279  
 ER\_VIEW\_DELETE\_MERGE\_VIEW error code, 31  
 ER\_VIEW\_FRM\_NO\_USER error code, 34  
 ER\_VIEW\_INVALID error code, 29  
 ER\_VIEW\_INVALID\_CREATION\_CTX error code, 43  
 ER\_VIEW\_MULTIUPDATE error code, 30  
 ER\_VIEW\_NONUPD\_CHECK error code, 29  
 ER\_VIEW\_NO\_CREATION\_CTX error code, 43  
 ER\_VIEW\_NO\_EXPLAIN error code, 28  
 ER\_VIEW\_NO\_INSERT\_FIELD\_LIST error code, 31  
 ER\_VIEW\_OTHER\_USER error code, 34  
 ER\_VIEW\_PREVENT\_UPDATE error code, 34  
 ER\_VIEW\_RECURSIVE error code, 35  
 ER\_VIEW\_SELECT\_CLAUSE error code, 28  
 ER\_VIEW\_SELECT\_TMPTABLE error code, 28  
 ER\_VIEW\_SELECT\_VARIABLE error code, 28  
 ER\_VIEW\_UNKNOWN\_CHARSET\_OR\_COLLATION error code, 164  
 ER\_VIEW\_UNPARSABLE error code, 199  
 ER\_VIEW\_WRONG\_LIST error code, 28  
 ER\_VTOKEN\_PLUGIN\_TOKEN\_MISMATCH error code, 641  
 ER\_VTOKEN\_PLUGIN\_TOKEN\_NOT\_FOUND error code, 641  
 ER\_WAITING\_FOR\_NO\_CONNECTIONS error code, 641  
 ER\_WAITING\_FOR\_NO\_THDS error code, 641  
 ER\_WRONG\_PID\_FAILED error code, 296  
 ER\_WARNING\_AUTHCACHE\_INVALID\_USER\_ATTRIBUTES error code, 549  
 ER\_WARNING\_DISCARD\_OLD\_PASSWORD\_CLAUSE\_VOID error code, 549  
 ER\_WARNING\_NOT\_COMPLETE\_ROLLBACK error code, 17  
 ER\_WARNING\_NOT\_COMPLETE\_ROLLBACK\_WITH\_CREATE\_INDEX error code, 55  
 ER\_WARNING\_NOT\_COMPLETE\_ROLLBACK\_WITH\_DROP\_INDEX error code, 55  
 ER\_WARNING\_PASSWORD\_HISTORY\_CLAUSES\_VOID error code, 101  
 ER\_WARNING\_RETAIN\_CURRENT\_PASSWORD\_CLAUSE\_VOID error code, 549  
 ER\_WARN\_ADUIT\_LOG\_MAX\_SIZE\_AND\_PRUNE\_SECONDS error code, 147  
 ER\_WARN\_ADUIT\_LOG\_MAX\_SIZE\_AND\_PRUNE\_SECONDS error code, 603  
 ER\_WARN\_ADUIT\_LOG\_MAX\_SIZE\_CLOSE\_TO\_ROTATE\_ON\_FAILURE error code, 147  
 ER\_WARN\_ADUIT\_LOG\_MAX\_SIZE\_CLOSE\_TO\_ROTATE\_ON\_FAILURE error code, 603  
 ER\_WARN\_ALLOWED\_PACKET\_OVERFLOWED error code, 25  
 ER\_WARN\_ASYNC\_CONN\_FAILOVER\_NETWORK\_NAMESPACE error code, 146  
 ER\_WARN\_AUDIT\_LOG\_DISABLED error code, 612  
 ER\_WARN\_AUDIT\_LOG\_FORMAT\_UNIX\_TIMESTAMP\_ONLY\_DISABLED error code, 148  
 ER\_WARN\_AUDIT\_LOG\_FORMAT\_UNIX\_TIMESTAMP\_ONLY\_DISABLED error code, 605

---

---

ER\_WARN\_AUTH\_ID\_WITH\_SYSTEM\_USER\_PRIV\_IN\_MANDATORY\_RESOURCES error code, 157  
 error code, 572  
 ER\_WARN\_BAD\_MAX\_EXECUTION\_TIME error code, 80  
 ER\_WARN\_BINLOG\_PARTIAL\_UPDATES\_DISABLED error code, 101  
 ER\_WARN\_BINLOG\_PARTIAL\_UPDATES\_SUGGESTS\_PARTIAL\_IMAGES error code, 101  
 ER\_WARN\_BINLOG\_V1\_ROW\_EVENTS\_DISABLED error code, 101  
 ER\_WARN\_CANNOT\_FREE\_COMPONENT\_DATA\_DEALLOCATION\_FAILED error code, 635  
 ER\_WARN\_CANNOT\_PERSIST\_SENSITIVE\_VARIABLES error code, 613  
 ER\_WARN\_CANNOT\_SECURELY\_PERSIST\_SENSITIVE\_VARIABLES error code, 154  
 ER\_WARN\_CANT\_DROP\_DEFAULT\_KEYCACHE error code, 33  
 ER\_WARN\_CLIENT\_DEPRECATED\_PARTITION\_PREFIX\_KEY error code, 138  
 ER\_WARN\_COMPONENTS\_INFRASTRUCTURE\_MANIFEST\_SCHEMA error code, 634  
 ER\_WARN\_COMPONENTS\_INFRASTRUCTURE\_MANIFEST\_SCHEMA error code, 596  
 ER\_WARN\_COMPONENT\_KEYRING\_OCI\_DUPLICATE\_KEY error code, 627  
 ER\_WARN\_CONFLICTING\_HINT error code, 80  
 ER\_WARN\_C\_DISABLE\_GTID\_ONLY\_WITH\_SOURCE\_AUTO\_POS\_INDEXTOP error code, 151  
 ER\_WARN\_DATA\_OUT\_OF\_RANGE error code, 22  
 ER\_WARN\_DATA\_OUT\_OF\_RANGE\_FUNCTIONAL\_INDEX error code, 113  
 ER\_WARN\_DATA\_TRUNCATED\_FUNCTIONAL\_INDEX error code, 113  
 ER\_WARN\_DA\_PRIVILEGE\_NOT\_REGISTERED error code, 133  
 ER\_WARN\_DEPRECATED\_CHARSET\_OPTION error code, 612  
 ER\_WARN\_DEPRECATED\_CLIENT\_NO\_SCHEMA\_OPTION error code, 158  
 ER\_WARN\_DEPRECATED\_COLLATION error code, 152  
 ER\_WARN\_DEPRECATED\_COLLATION\_OPTION error code, 612  
 ER\_WARN\_DEPRECATED\_DATETIME\_DELIMITER error code, 154  
 ER\_WARN\_DEPRECATED\_FLOAT\_AUTO\_INCREMENT error code, 125  
 ER\_WARN\_DEPRECATED\_FLOAT\_DIGITS error code, 125  
 ER\_WARN\_DEPRECATED\_FLOAT\_UNSIGNED error code, 125  
 ER\_WARN\_DEPRECATED\_FOUND\_ROWS error code, 137  
 ER\_WARN\_DEPRECATED\_IDENT error code, 157  
 ER\_WARN\_DEPRECATED\_INNER\_INTO error code, 137  
 ER\_WARN\_DEPRECATED\_INTEGER\_DISPLAY\_WIDTH error code, 125  
 ER\_WARN\_DEPRECATED\_JSON\_TABLE\_ON\_ERROR\_ON\_EMPTY error code, 137  
 ER\_WARN\_DEPRECATED\_NESTED\_COMMENT\_SYNTAX error code, 116  
 ER\_WARN\_DEPRECATED\_OR\_BLOCKED\_CIPHER error code, 137  
 ER\_WARN\_DEPRECATED\_SQLMODE error code, 77  
 ER\_WARN\_DEPRECATED\_SQL\_CALC\_FOUND\_ROWS error code, 137  
 ER\_WARN\_DEPRECATED\_SUPERFLUOUS\_DELIMITER error code, 154  
 ER\_WARN\_DEPRECATED\_SYNTAX error code, 24  
 ER\_WARN\_DEPRECATED\_SYNTAX\_NO\_REPLACEMENT error code, 49  
 ER\_WARN\_DEPRECATED\_SYNTAX\_WITH\_VER error code, 49  
 ER\_WARN\_DEPRECATED\_SYSVAR\_UPDATE error code, 107  
 ER\_WARN\_DEPRECATED\_TLS\_VERSION\_FOR\_CHANNEL error code, 601  
 ER\_WARN\_DEPRECATED\_TLS\_VERSION\_FOR\_CHANNEL\_CLI error code, 147  
 ER\_WARN\_DEPRECATED\_USER\_DEFINED\_COLLATIONS error code, 162  
 ER\_WARN\_DEPRECATED\_USER\_DEFINED\_COLLATIONS\_OPTION error code, 634  
 ER\_WARN\_DEPRECATED\_USER\_SET\_EXPR error code, 116  
 ER\_WARN\_DEPRECATED\_UTF8MB3\_CHARSET\_OPTION error code, 543  
 ER\_WARN\_DEPRECATED\_UTF8MB3\_COLLATION error code, 116  
 ER\_WARN\_DEPRECATED\_UTF8MB3\_COLLATION\_OPTION error code, 543  
 ER\_WARN\_DEPRECATED\_UTF8\_ALIAS\_OPTION error code, 543  
 ER\_WARN\_DEPRECATED\_VALUES\_FUNCTION\_ALWAYS\_NULL error code, 137  
 ER\_WARN\_DEPRECATED\_WITH\_NOTE error code, 162  
 ER\_WARN\_DEPRECATED\_YEAR\_UNSIGNED error code, 136  
 ER\_WARN\_DEPRECATED\_ZEROFILL error code, 126  
 ER\_WARN\_ENGINE\_TRANSACTION\_ROLLBACK error code, 44  
 ER\_WARN\_FIELD\_RESOLVED error code, 23  
 ER\_WARN\_FUNC\_INDEX\_NOT\_APPLICABLE error code, 131



---

ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE error code, 603	ER_WARN_REGEX_USING_DEFAULT error code, 152
ER_WARN_GTID_THRESHOLD_BREACH error code, 594	ER_WARN_REMOVED_SQL_MODE error code, 544
ER_WARN_HOSTNAME_WONT_WORK error code, 24	ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_A error code, 602
ER_WARN_HYPERGRAPH_EXPERIMENTAL error code, 142	ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_NOT_O error code, 609
ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS error code, 557	ER_WARN_RESERVED_SRID_RANGE error code, 109
ER_WARN_INDEX_NOT_APPLICABLE error code, 54	ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_M error code, 572
ER_WARN_INVALID_DB_RESTRICTIONS error code, 557	ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_S error code, 572
ER_WARN_INVALID_HINT error code, 98	ER_WARN_SCHEDULED_TASK_RUN_FAILED error code, 639
ER_WARN_INVALID_TIMESTAMP error code, 25	ER_WARN_SF_UDF_NAME_COLLISION error code, 153
ER_WARN_I_S_SKIPPED_TABLE error code, 49	ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATE error code, 148
ER_WARN_LEGACY_SYNTAX_CONVERTED error code, 69	ER_WARN_SRS_ID_ALREADY_EXISTS error code, 108
ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX_KEY error code, 582	ER_WARN_SRS_NOT_FOUND error code, 89
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT error code, 570	ER_WARN_SRS_NOT_FOUND_AXIS_ORDER error code, 92
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST error code, 570	ER_WARN_SRS_UNSUPPORTED error code, 92
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_PRIVILEGE error code, 571	ER_WARN_STREAM_CHANNEL_INITIALIZATION_ERROR error code, 583
ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE_AU error code, 609	ER_WARN_TOO_MANY_RECORDS error code, 22
ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING error code, 613	ER_WARN_TOO_MANY_RECORDS error code, 22
ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND error code, 596	ER_WARN_TRG_ALREADY_EXISTS error code, 154
ER_WARN_NO_SERVERID_SPECIFIED error code, 278	ER_WARN_TRIGGER_DOESNT_HAVE_CREATED error code, 69
ER_WARN_NO_SPACE_VERSION_COMMENT error code, 162	ER_WARN_UNKNOWN_KEYRING_AWS_REGION error code, 570
ER_WARN_NULL_TO_NOTNULL error code, 22	ER_WARN_UNKNOWN_QB_NAME error code, 80
ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS error code, 70	ER_WARN_UNLOAD_THE_NOT_PERSISTED error code, 90
ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS error code, 70	ER_WARN_UNSUPPORTED_HINT error code, 88
ER_WARN_ON_MODIFYING_GTID_EXECUTED_TABLE error code, 81	ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME error code, 80
ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO error code, 70	ER_WARN_USING_OTHER_HANDLER error code, 22
ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR error code, 80	ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED error code, 141
ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT error code, 557	ER_WARN_VIEW_MERGE error code, 28
ER_WARN_PROPERTY_STRING_PARSE_FAILED error code, 552	ER_WARN_VIEW_WITHOUT_KEY error code, 29
ER_WARN_PURGE_LOG_IN_USE error code, 65	ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG error code, 570
ER_WARN_PURGE_LOG_IS_ACTIVE error code, 65	ER_WARN_WRONG_COMPRESSION_LEVEL_LOG error code, 570
ER_WARN_QC_RESIZE error code, 24	ER_WASTEFUL_NET_BUFFER_SIZE error code, 171
	ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BIND error code, 562
	ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH error code, 94
	ER_WINDOW_DUPLICATE_NAME error code, 95
	ER_WINDOW_EXPLAIN_JSON error code, 96

---

---

ER\_WINDOW\_FRAME\_END\_ILLEGAL error code, 94  
ER\_WINDOW\_FRAME\_ILLEGAL error code, 95  
ER\_WINDOW\_FRAME\_START\_ILLEGAL error code, 94  
ER\_WINDOW\_FUNCTION\_IGNORES\_FRAME error code, 96  
ER\_WINDOW\_ILLEGAL\_ORDER\_BY error code, 95  
ER\_WINDOW\_INVALID\_WINDOW\_FUNC\_ALIAS\_USE error code, 95  
ER\_WINDOW\_INVALID\_WINDOW\_FUNC\_USE error code, 95  
ER\_WINDOW\_NESTED\_WINDOW\_FUNC\_USE\_IN\_WINDOW\_SPEC error code, 96  
ER\_WINDOW\_NO\_CHILD\_PARTITIONING error code, 94  
ER\_WINDOW\_NO\_GROUP\_ORDER error code, 96  
ER\_WINDOW\_NO\_GROUP\_ORDER\_UNUSED error code, 96  
ER\_WINDOW\_NO\_INHERIT\_FRAME error code, 94  
ER\_WINDOW\_NO\_REDEFINE\_ORDER\_BY error code, 94  
ER\_WINDOW\_NO\_SUCH\_WINDOW error code, 94  
ER\_WINDOW\_RANGE\_BOUND\_NOT\_CONSTANT error code, 95  
ER\_WINDOW\_RANGE\_FRAME\_NUMERIC\_TYPE error code, 95  
ER\_WINDOW\_RANGE\_FRAME\_ORDER\_TYPE error code, 95  
ER\_WINDOW\_RANGE\_FRAME\_TEMPORAL\_TYPE error code, 95  
ER\_WINDOW\_ROWS\_INTERVAL\_USE error code, 96  
ER\_WINDOW\_SE\_NOT\_ACCEPTABLE error code, 96  
ER\_WIN\_LISTEN\_BUT\_HOW error code, 176  
ER\_WIN\_LOAD\_LIBRARY\_FAILED error code, 295  
ER\_WL9236\_NOW\_UNUSED error code, 96  
ER\_WRITABLE\_CONFIG\_REMOVED error code, 173  
ER\_WRITE\_ROW\_TO\_PARTITION\_FAILED error code, 284  
ER\_WRITE\_SET\_EXCEEDS\_LIMIT error code, 87  
ER\_WRONG\_ARGUMENTS error code, 18  
ER\_WRONG\_AUTO\_KEY error code, 8  
ER\_WRONG\_COLUMN\_NAME error code, 14  
ER\_WRONG\_COMPRESSION\_ALGORITHM\_CLIENT error code, 132  
ER\_WRONG\_COMPRESSION\_LEVEL\_CLIENT error code, 132  
ER\_WRONG\_COUNT\_FOR\_KEY error code, 253  
ER\_WRONG\_COUNT\_FOR\_ORIGIN error code, 253  
ER\_WRONG\_COUNT\_OF\_ELEMENTS error code, 253  
ER\_WRONG\_DATETIME\_SPEC error code, 174  
ER\_WRONG\_DB\_NAME error code, 10  
ER\_WRONG\_EXPR\_IN\_PARTITION\_FUNC\_ERROR error code, 36  
ER\_WRONG\_FIELD\_SPEC error code, 7  
ER\_WRONG\_FIELD\_TERMINATORS error code, 9  
ER\_WRONG\_FIELD\_WITH\_GROUP error code, 7  
ER\_WRONG\_FIELD\_WITH\_GROUP\_V2 error code, 77  
ER\_WRONG\_FILE\_NAME error code, 80  
ER\_WRONG\_FK\_DEF error code, 21  
ER\_WRONG\_FK\_OPTION\_FOR\_GENERATED\_COLUMN error code, 79  
ER\_WRONG\_GROUP\_FIELD error code, 7  
ER\_WRONG\_JSON\_TABLE\_VALUE error code, 103  
ER\_WRONG\_KEY\_COLUMN error code, 15  
ER\_WRONG\_KEY\_COLUMN\_FUNCTIONAL\_INDEX error code, 114  
ER\_WRONG\_LOCK\_OF\_SYSTEM\_TABLE error code, 33  
ER\_WRONG\_MRG\_TABLE error code, 15  
ER\_WRONG\_MVI\_VALUE error code, 130  
ER\_WRONG\_NAME\_FOR\_CATALOG error code, 24  
ER\_WRONG\_NAME\_FOR\_INDEX error code, 24  
ER\_WRONG\_NATIVE\_TABLE\_STRUCTURE error code, 49  
ER\_WRONG\_NUMBER\_OF\_COLUMNS\_IN\_SELECT error code, 19  
ER\_WRONG\_OBJECT error code, 28  
ER\_WRONG\_OUTER\_JOIN error code, 11  
ER\_WRONG\_OUTER\_JOIN\_UNUSED error code, 11  
ER\_WRONG\_PARAMCOUNT\_TO\_NATIVE\_FCT error code, 42  
ER\_WRONG\_PARAMCOUNT\_TO\_PROCEDURE error code, 10  
ER\_WRONG\_PARAMETERS\_TO\_NATIVE\_FCT error code, 42  
ER\_WRONG\_PARAMETERS\_TO\_PROCEDURE error code, 10  
ER\_WRONG\_PARAMETERS\_TO\_STORED\_FCT error code, 42  
ER\_WRONG\_PARTITION\_NAME error code, 41  
ER\_WRONG\_PERFSHEMA\_USAGE error code, 49  
ER\_WRONG\_SIZE\_NUMBER error code, 39  
ER\_WRONG\_SPVAR\_TYPE\_IN\_LIMIT error code, 50  
ER\_WRONG\_SRID\_FOR\_COLUMN error code, 101  
ER\_WRONG\_STRING\_LENGTH error code, 36  
ER\_WRONG\_SUB\_KEY error code, 9  
ER\_WRONG\_SUM\_SELECT error code, 7  
ER\_WRONG\_TABLESPACE\_NAME error code, 80  
ER\_WRONG\_TABLE\_NAME error code, 10  
ER\_WRONG\_TYPE\_COLUMN\_VALUE\_ERROR error code, 47  
ER\_WRONG\_TYPE\_FOR\_COLUMN\_PREFIX\_IDX\_FLD error code, 294  
ER\_WRONG\_TYPE\_FOR\_VAR error code, 20  
ER\_WRONG\_USAGE error code, 19  
ER\_WRONG\_VALUE error code, 39  
ER\_WRONG\_VALUE\_COUNT error code, 7  
ER\_WRONG\_VALUE\_COUNT\_ON\_ROW error code, 13  
ER\_WRONG\_VALUE\_FOR\_TYPE error code, 32

---

ER\_WRONG\_VALUE\_FOR\_VAR error code, 20  
 ER\_WRONG\_VALUE\_FOR\_VAR\_PLUS\_ACTIONABLE\_PAGES error code, 139  
 ER\_X509\_CANT\_CHMOD\_KEY error code, 193  
 ER\_X509\_CANT\_CREATE\_CERT error code, 193  
 ER\_X509\_CANT\_READ\_CA\_CERT error code, 193  
 ER\_X509\_CANT\_READ\_CA\_KEY error code, 193  
 ER\_X509\_CANT\_WRITE\_CERT error code, 193  
 ER\_X509\_CANT\_WRITE\_KEY error code, 193  
 ER\_X509\_CIPHERS\_MISMATCH error code, 192  
 ER\_X509\_ISSUER\_MISMATCH error code, 192  
 ER\_X509\_NEEDS\_RSA\_PRIVKEY error code, 193  
 ER\_X509\_SUBJECT\_MISMATCH error code, 193  
 ER\_XAER\_DUPID error code, 34  
 ER\_XAER\_INVALID error code, 31  
 ER\_XAER\_NOTA error code, 31  
 ER\_XAER\_OUTSIDE error code, 31  
 ER\_XAER\_RMERR error code, 31  
 ER\_XAER\_RMFAIL error code, 31  
 ER\_XA\_CANT\_CREATE\_MDL\_BACKUP error code, 568  
 ER\_XA\_COMMITTING\_XID error code, 186  
 ER\_XA\_IGNOREING\_XID error code, 186  
 ER\_XA\_NO\_MULTI\_2PC\_HEURISTIC\_RECOVER error code, 186  
 ER\_XA\_RBDEADLOCK error code, 44  
 ER\_XA\_RBROLLBACK error code, 31  
 ER\_XA\_RBTIMEOUT error code, 44  
 ER\_XA\_RECOVERY\_DONE error code, 186  
 ER\_XA\_RECOVER\_EXPLANATION error code, 186  
 ER\_XA\_RECOVER\_FOUND\_TRX\_IN\_SE error code, 186  
 ER\_XA\_RECOVER\_FOUND\_XA\_TRX error code, 186  
 ER\_XA\_REPLICATION\_FILTERS error code, 129  
 ER\_XA\_RETRY error code, 86  
 ER\_XA\_ROLLING\_BACK\_XID error code, 186  
 ER\_XA\_STARTING\_RECOVERY error code, 186  
 ER\_XA\_TEMP\_TABLE error code, 153  
 ER\_XPLUGIN\_ALL\_IO\_INTERFACES\_DISABLED error code, 326  
 ER\_XPLUGIN\_BUFFER\_PAGE\_ALLOC\_FAILED error code, 323  
 ER\_XPLUGIN\_CAPABILITY\_CLIENT\_INTERACTIVE\_FAILED error code, 330  
 ER\_XPLUGIN\_CAPABILITY\_EXPIRED\_PASSWORD error code, 330  
 ER\_XPLUGIN\_CLIENT\_KILL\_MSG error code, 328  
 ER\_XPLUGIN\_CLIENT\_RELEASE\_TRIGGERED error code, 328  
 ER\_XPLUGIN\_CLIENT\_SSL\_HANDSHAKE\_FAILED error code, 325  
 ER\_XPLUGIN\_CLOSING\_CLIENTS\_ON\_SHUTDOWN error code, 326  
 ER\_XPLUGIN\_COMPRESSION\_ERROR error code, 327  
 ER\_XPLUGIN\_DETECTED\_HANGING\_CLIENTS error code, 323  
 ER\_XPLUGIN\_EMPTY\_ADMIN\_CMD error code, 329  
 ER\_XPLUGIN\_ERROR\_MSG error code, 319  
 ER\_XPLUGIN\_ERROR\_READING\_SOCKET error code, 326  
 ER\_XPLUGIN\_ERROR\_WRITING\_TO\_CLIENT error code, 327  
 ER\_XPLUGIN\_EXCEPTION\_IN\_EVENT\_LOOP error code, 324  
 ER\_XPLUGIN\_EXCEPTION\_IN\_TASK\_SCHEDULER error code, 324  
 ER\_XPLUGIN\_EXISTING\_USER\_ACCOUNT\_WITH\_INCOMPLETE error code, 328  
 ER\_XPLUGIN\_FAILED\_AT\_SSL\_CONF error code, 325  
 ER\_XPLUGIN\_FAILED\_TO\_ACCEPT\_CLIENT error code, 323  
 ER\_XPLUGIN\_FAILED\_TO\_BIND\_INTERFACE\_ADDRESS error code, 583  
 ER\_XPLUGIN\_FAILED\_TO\_CLOSE\_SQL\_SESSION error code, 329  
 ER\_XPLUGIN\_FAILED\_TO\_CREATE\_SESSION\_FOR\_CONNECTION error code, 325  
 ER\_XPLUGIN\_FAILED\_TO\_EXECUTE\_ADMIN\_CMD error code, 329  
 ER\_XPLUGIN\_FAILED\_TO\_GET\_CREATION\_STMT error code, 329  
 ER\_XPLUGIN\_FAILED\_TO\_GET\_ENGINE\_INFO error code, 329  
 ER\_XPLUGIN\_FAILED\_TO\_GET\_SECURITY\_CTX error code, 328  
 ER\_XPLUGIN\_FAILED\_TO\_GET\_SYS\_VAR error code, 329  
 ER\_XPLUGIN\_FAILED\_TO\_INITIALIZE\_SESSION error code, 325  
 ER\_XPLUGIN\_FAILED\_TO\_INTERRUPT\_SESSION error code, 328  
 ER\_XPLUGIN\_FAILED\_TO\_OPEN\_INTERNAL\_SESSION error code, 330  
 ER\_XPLUGIN\_FAILED\_TO\_PREPARE\_IO\_INTERFACES error code, 324  
 ER\_XPLUGIN\_FAILED\_TO\_RESET\_IPV6\_V6ONLY\_FLAG error code, 330  
 ER\_XPLUGIN\_FAILED\_TO\_SCHEDULE\_CLIENT error code, 323  
 ER\_XPLUGIN\_FAILED\_TO\_SET\_MIN\_NUMBER\_OF\_WORKERS error code, 325  
 ER\_XPLUGIN\_FAILED\_TO\_SET\_SO\_REUSEADDR\_FLAG error code, 330  
 ER\_XPLUGIN\_FAILED\_TO\_STOP\_SERVICES error code, 528

---

---

ER\_XPLUGIN\_FAILED\_TO\_SWITCH\_CONTEXT error code, 330  
 ER\_XPLUGIN\_FAILED\_TO\_SWITCH\_SECURITY\_CTX error code, 542  
 ER\_XPLUGIN\_FAILED\_TO\_SWITCH\_SECURITY\_CTX\_TOO\_LONG error code, 329  
 ER\_XPLUGIN\_FAILED\_TO\_UNREGISTER\_UDF error code, 330  
 ER\_XPLUGIN\_FAILED\_TO\_USE\_SSL\_CONF error code, 319  
 ER\_XPLUGIN\_FAILED\_TO\_VALIDATE\_ADDRESS error code, 583  
 ER\_XPLUGIN\_FAIL\_TO\_GET\_RESULT\_DATA error code, 329  
 ER\_XPLUGIN\_FORCE\_STOP\_CLIENT error code, 323  
 ER\_XPLUGIN\_GET\_PEER\_ADDRESS\_FAILED error code, 330  
 ER\_XPLUGIN\_INVALID\_AUTH\_METHOD error code, 326  
 ER\_XPLUGIN\_INVALID\_MSG\_DURING\_CLIENT\_INIT error code, 326  
 ER\_XPLUGIN\_IPv6\_AVAILABLE error code, 328  
 ER\_XPLUGIN\_LISTENER\_SETUP\_FAILED error code, 324  
 ER\_XPLUGIN\_LISTENER\_STATUS\_MSG error code, 327  
 ER\_XPLUGIN\_LISTENER\_SYS\_VARIABLE\_ERROR error code, 327  
 ER\_XPLUGIN\_MAX\_AUTH\_ATTEMPTS\_REACHED error code, 323  
 ER\_XPLUGIN\_MESSAGE\_TOO\_LONG error code, 325  
 ER\_XPLUGIN\_PEER\_DISCONNECTED\_WHILE\_READING\_MSG\_BODY error code, 326  
 ER\_XPLUGIN\_READ\_FAILED\_CLOSING\_CONNECTION error code, 326  
 ER\_XPLUGIN\_REFERENCE\_TO\_SECURE\_CONN\_WITH\_XPLUGIN error code, 319  
 ER\_XPLUGIN\_REFERENCE\_TO\_USER\_ACCOUNT\_DOC\_SECTION error code, 324  
 ER\_XPLUGIN\_RETRYING\_BIND\_ON\_PORT error code, 327  
 ER\_XPLUGIN\_SCHEDULER\_STARTED error code, 327  
 ER\_XPLUGIN\_SCHEDULER\_STOPPED error code, 327  
 ER\_XPLUGIN\_SERVER\_EXITED error code, 318  
 ER\_XPLUGIN\_SERVER\_EXITING error code, 318  
 ER\_XPLUGIN\_SERVER\_STARTS\_HANDLING\_CONNECTIONS error code, 328  
 ER\_XPLUGIN\_SERVER\_STOPPED\_HANDLING\_CONNECTIONS error code, 328  
 ER\_XPLUGIN\_SHUTDOWN\_TRIGGERED error code, 327  
 ER\_XPLUGIN\_SRV\_SESSION\_INIT\_THREAD\_FAILED error code, 324  
 ER\_XPLUGIN\_SSL\_HANDSHAKE\_WITH\_SERVER\_FAILED error code, 325  
 ER\_XPLUGIN\_STARTUP\_FAILED error code, 318  
 ER\_XPLUGIN\_TASK\_SCHEDULING\_FAILED error code, 324  
 ER\_XPLUGIN\_UNABLE\_TO\_ACCEPT\_CONNECTION error code, 326  
 ER\_XPLUGIN\_UNABLE\_TO\_USE\_USER\_SESSION\_ACCOUNT error code, 324  
 ER\_XPLUGIN\_UNEXPECTED\_EXCEPTION\_DISPATCHING\_CMD error code, 324  
 ER\_XPLUGIN\_UNEXPECTED\_MSG\_DURING\_AUTHENTICATION error code, 327  
 ER\_XPLUGIN\_UNINITIALIZED\_MESSAGE error code, 325  
 ER\_XPLUGIN\_UNIX\_SOCKET\_NOT\_CONFIGURED error code, 328  
 ER\_XPLUGIN\_USER\_ACCOUNT\_WITH\_ALL\_PERMISSIONS error code, 327  
 ER\_XPLUGIN\_USING\_SSL\_CONF\_FROM\_MYSQLX error code, 318  
 ER\_XPLUGIN\_USING\_SSL\_CONF\_FROM\_SERVER error code, 318  
 ER\_XPLUGIN\_USING\_SSL\_FOR\_TLS\_CONNECTION error code, 319  
 ER\_XPLUING\_NET\_STARTUP\_FAILED error code, 325  
 ER\_YES error code, 3  
 ER\_ZLIB\_Z\_BUF\_ERROR error code, 22  
 ER\_ZLIB\_Z\_DATA\_ERROR error code, 22  
 ER\_ZLIB\_Z\_MEM\_ERROR error code, 22  
 WARN\_AES\_KEY\_SIZE error code, 87  
 WARN\_COND\_ITEM\_TRUNCATED error code, 46  
 WARN\_DATA\_TRUNCATED error code, 22  
 WARN\_DATA\_TRUNCATED\_FUNCTIONAL\_INDEX error code, 113  
 WARN\_NAMED\_PIPE\_ACCESS\_EVERYONE error code, 68  
 WARN\_NON\_ASCII\_SEPARATOR\_NOT\_IMPLEMENTED error code, 46  
 WARN\_NO\_CONNECTION\_METADATA error code, 44  
 WARN\_NO\_MASTER\_INFO error code, 44  
 WARN\_ON\_BLOCKHOLE\_IN\_RBR error code, 66  
 WARN\_OPTION\_BELOW\_LIMIT error code, 51  
 WARN\_OPTION\_IGNORED error code, 44  
 WARN\_PLUGIN\_BUSY error code, 44  
 WARN\_UNENCRYPTED\_TABLE\_IN\_ENCRYPTED\_DB error code, 121  
 WARN\_UNSUPPORTED\_ACL\_TABLES\_READ error code, 143  
 WARN\_USELESS\_SPATIAL\_INDEX error code, 104